

MISP CLI

Automate all the things

CIRCL / Team MISP Project

MISP Project

CRI MISP 2024

MISP
INTELLIGENCE SHARING

MISP CLI

Automate all the things

CIRCL / Team MISP Project

MISP Project

CRI MISP 2024

MISP CLI functionalities

- The MISP API is great for remotely executing administrative tasks
- But sometimes we want to simplify the process / avoid having to deal with authentication
- MISP also has an extensive CLI sub-system for this reason

MISP CLI functionalities
- The MISP API is great for remotely executing administrative tasks
- But sometimes we want to simplify the process / avoid having to deal with authentication
- MISP also has an extensive CLI sub-system for this reason

Types of objectives for the scripts

- Automating recurring tasks
- Recovery from loss of access
- Updates / initialisation
- Background worker management

Types of objectives for the scripts
- Automating recurring tasks
- Recovery from loss of access
- Updates / initialisation
- Background worker management

CLI documentation

- https://path.to.your.misp/events/automation

Administering the background workers via the API.


You can start/stop and view the bacground workers via the API.

Add worker: `http://localhost:5001/servers/startWorker/[queue_name]`
Stop worker: `http://localhost:5001/servers/stopWorker/[worker_pid]`
Get worker info: `http://localhost:5001/servers/getWorkers`

Administering MISP via the CLI

Certain administrative tasks are exposed to the API, these help with maintaining and configuring MISP in an automated way / via external tools.:

Get Setting: `MISP/app/Console/cake Admin getSetting [setting]`
Set Setting: `MISP/app/Console/cake Admin setSetting [setting] [value]`
Get Authkey: `MISP/app/Console/cake Admin getAuthkey [email]`
Set Baseurl: `MISP/app/Console/cake Baseurl [baseurl]`
Change Password: `MISP/app/Console/cake Password [email] [new_password] [--override_password_change]`
Clear Bruteforce Entries: `MISP/app/Console/cake Admin clearBruteforce [user_email]`
Run Database Update: `MISP/app/Console/cake Admin updateDatabase`
Update All JSON Structures: `MISP/app/Console/cake Admin updateJSON`
Update Galaxy Definitions: `MISP/app/Console/cake Admin updateGalaxies`
Update Taxonomy Definitions: `MISP/app/Console/cake Admin updateTaxonomies`
Update Object Templates: `MISP/app/Console/cake Admin updateObjectTemplates`
Update Warninglists: `MISP/app/Console/cake Admin updateWarningLists`



Usage

```
/var/www/MISP/app/Console/cake [Shell] [Command]
[parameters]
```

- Example:
  - `/var/www/MISP/app/Console/cake Password "andras.iklody@gmail.com" "Nutella"`
  - Change password to "Nutella" for my user
  - Some shells are single use and don't need a command parameter
- Also used by the background processing
- Automation is meant to be used via cron jobs

Usage

/var/www/MISP/app/Console/cake [Shell] [Command] [parameters]
- Example:
  - /var/www/MISP/app/Console/cake Password "andras.iklody@gmail.com" "Nutella"
  - Change password to "Nutella" for my user
  - Some shells are single use and don't need a command parameter
- Also used by the background processing
- Automation is meant to be used via cron jobs

Automation via crontab

- Edit crontab of www-data user
- `crontab -u www-data -e`
- `0 3,9,15,21 * * * /var/www/MISP/app/Console/cake Server pull 1 30 full`
- Pull server ID #30 as user #1 every 6 hours
- `@hourly /var/www/MISP/app/Console/cake Server cacheFeed 1 csv full`
- Cache all csv feeds as user #1 every hour

Automation via crontab
- Edit crontab of www-data user
- crontab -u www-data -e
- 0 3,9,15,21 * * * /var/www/MISP/app/Console/cake Server pull 1 30 full
- Pull server ID #30 as user #1 every 6 hours
- @hourly /var/www/MISP/app/Console/cake Server cacheFeed 1 csv full
- Cache all csv feeds as user #1 every hour