

1.3.1__duplicate_removal

March 11, 2021

1 1.3.x Remove duplicate text chunks for each admission

2 THIS MUST BE RUN WITH PYTHON 3.7.x or the regex won't work

- custom tokenizer to split on . + space or \n
- saves the concatenation of unique tokens in db transfused_notes_unique ctrl_notes_unique for analysis
- last ran 8/23/2019 on AWS large instance Windows OS

```
[1]: # -*- coding: utf-8 -*-
from datetime import datetime
import time
import re
import pandas as pd

import sys
import psycpg2
from sqlalchemy import create_engine, update, event
from tqdm import trange, tqdm_notebook

from time import sleep
from importlib_metadata import version

if sys.platform == "darwin":
    conn = psycpg2.connect("dbname=mimic user=xxxxxxxxxxx_
    ↳options=--search_path=mimiciii");
    engine = create_engine('postgresql://xxxxxxxxxxx@localhost/mimic')
    path1 = './replication/'

cur = conn.cursor();
cur.execute("""SET search_path = mimiciii;""")

libraries = ['pandas', 'psycpg2', 'tqdm', 'scipy']
```

```

print('last ran: ',datetime.now() )
print("Python Version:", sys.version[0:7])
print( "operating system:", sys.platform)

for lib in libraries:
    print(lib + ' version: ' + version(lib))

```

```

last ran: 2019-12-25 10:37:27.773955
Python Version: 3.7.3 (
operating system: darwin
pandas version: 0.24.2
psycpg2 version: 2.7.6.1
tqdm version: 4.32.1
scipy version: 1.2.1

```

3 Transfused

- 21443

create a new table transfused_notes_unique in the Postgres database

```

[2]: cur.execute("""DROP TABLE IF EXISTS mimiciii.transfused_notes_unique;

CREATE TABLE mimiciii.transfused_notes_unique
(hadm_id int,
text varchar);""")

conn.commit();

```

get list of **hadm_ids** from the transfused admissions

```

[3]: xf = pd.read_sql("""
SELECT hadm_id
FROM mimiciii.transfused_notes_sink """, engine)

xf_ids = xf.hadm_id.unique()
len(xf)

```

[3]: 21443

this helps us execute multiple calls to the database using pandas

```

[4]: @event.listens_for(engine, 'before_cursor_execute')
def receive_before_cursor_execute(conn, cursor, statement, params, context,
↪executemany):
    #print("FUNC call")
    if executemany:
        cursor.fast_executemany = True

```

```
[5]: def mark_duplicates(input_tokens):
    '''
        Function uses a set() and list to generates each token with html tags added,
        ↳to duplicate tokens.
        INPUT: input_tokens = string of tokenized text (can be sentences,
        ↳paragraphs, words etc)

        OUTPUT: a single token at a time (generator) until the end of the
        ↳input_tokens.
    '''

    # create hash of tokens
    tokens_set = set()
    tokens_set_add = tokens_set.add

    for token in input_tokens:

        #skip any empty tokens
        if token == '':
            pass

        elif token not in tokens_set:
            tokens_set_add(token)
            yield token

        else:
            pass

def tokenize2(t):

    tok_new = []

    # find any \n followed by an uppercase letter, a number, or a dash
    sent_token = re.split(r"(?=\n\s*[A-Z1-9#-]+.*)", t)

    # replace \n with a space with a space
    sent_token = [re.sub(r"$\n+", "", i) for i in sent_token] # remove from end
    sent_token = [re.sub(r"^\\n", "", i) for i in sent_token] #remove from front
    # line feeds + whitespace or not
    sent_token = [re.sub(r"\s+\\n\s+", " ", i) for i in sent_token]
    sent_token = [re.sub(r"\s+\\n", " ", i) for i in sent_token]
    sent_token = [re.sub(r"\\n\s+", " ", i) for i in sent_token]
    sent_token = [re.sub(r"\\n", " ", i) for i in sent_token]

    #remove front/end whitespace
```

```

sent_token = [i.strip(' ') for i in sent_token]

for i in sent_token:
    if i != '':
        tok_new.append(i)

return tok_new

def save_tokens(token):
    for enum_num, enum_token in enumerate(token):
        yield str(enum_num), enum_token

def bloatectomy(input_text):
    '''Function to tokenize, remove duplicates, and output a string.
    Tokenization is done at each period followed by a space, or a newline.

    INPUT: input_text = text to be tokenized
    OUTPUT: an string with duplicate tokens removed.
    '''
    # tokenize 1

    tok = re.split(r"(.+?\.[\s\n]+)", input_text, flags=re.DOTALL)
    # whitespace around tokens can cause a duplicate to be missed
    tok = [i.strip(' ') for i in tok]

    #tokenize 2
    new_tok = []

    for num, t in enumerate(tok):

        n_tok = tokenize2(t)

        new_tok.extend(n_tok)

    # save numbered list
    numbered_output = list(save_tokens(new_tok))

    # detect and mark/remove duplicates
    u_set = list(mark_duplicates(new_tok))

    uniq =str("\n ".join(u_set))

    return uniq

```

3.0.1 check to make sure it's working

```
[6]: hadm_id_sample = #an hadm_id from the database
pt_all_xf = pd.read_sql("""SELECT * FROM mimiciii.transfused_notes_sink WHERE_
↳hadm_id IN (hadm_id_sample);""", engine)
print(bloatectomy(pt_all_xf))
```

```
[6]: fake_text = '''Assessment and Plan
61 yo male Hep C cirrhosis and HCC presents with probable lower GIB and
renal failure of unclear duration.
Abd pain:
-other labs: PT / PTT / INR:16.6//                                1.5, CK / CKMB /

Troponin-T:4390/40/0.21, ALT / AST:258/575, Alk Phos / T Bili:232/5.9,
ICU Care
-other labs: PT / PTT / INR:16.6//                                1.5, CK / CKMB /
Communication:                                                    Comments:
icu Care
Assessment and Plan
Chief Complaint:
61 yo male Hep C cirrhosis and HCC presents with probable lower GIB and
renal failure of unclear duration.
# Abd pain:'''
```

```
[7]: print(bloatectomy(fake_text))
```

```
Assessment and Plan
61 yo male Hep C cirrhosis and HCC presents with probable lower GIB and renal
failure of unclear duration.
Abd pain:
-other labs: PT / PTT / INR:16.6//                                1.5, CK / CKMB /
Troponin-T:4390/40/0.21, ALT / AST:258/575, Alk Phos / T Bili:232/5.9,
ICU Care
Communication:                                                    Comments: icu Care
Chief Complaint:
# Abd pain:
```

3.1 split each admission's notes into sentences, strip whitespace from edges, remove duplicates, join, store in new table

should take approx 19 minutes

```
[8]: s = time.time()

for j in tqdm_notebook(xf_ids):

    sql = """
```

```

SELECT hadm_id, text
FROM mimiciii.transfused_notes_sink
    WHERE hadm_id in ({0})
"""

# run sql query above to pull all notes for one admission (already in order
↳by date)
sql = sql.format(j)
xnotes = pd.read_sql(sql, engine)

# split into tokens based on a period followed by a space or a newline \n
↳(the period and \n are included in the token)
input_notes = xnotes.text.tolist()[0]

unique_tokens = bloatectomy(input_notes)

# save as a new dataframe
xtext2 = [(j, unique_tokens)]
xfulltext=pd.DataFrame(xtext2, columns=['hadm_id', 'text'])

# append user and single note to the new table in database
table_name = 'transfused_notes_unique'

z = time.time()

xfulltext.to_sql(table_name, con=engine, if_exists='append', chunksize=1,
↳index=False, schema='mimiciii')

#print('per hadmid-',(time.time() - z)/60,'min')

print('total-', (time.time() - s)/60,'minutes')

conn.commit()

```

```
HBox(children=(IntProgress(value=0, max=21443), HTML(value='')))
```

```
total- 27.955767035484314 minutes
```

```

[9]: cur.execute(""" SELECT COUNT(*), COUNT(DISTINCT hadm_id) FROM
↳transfused_notes_unique;""")

print( pd.DataFrame(cur.fetchall(), columns=[ 'total notes count', 'xf
↳admissions with notes'])).to_string(index=False))

```

total notes count	xf admissions with notes
21443	21443

4 Control

- unique admissions = 27,888

```
[10]: cur.execute("""DROP TABLE IF EXISTS mimiciii.ctrl_notes_unique;

CREATE TABLE mimiciii.ctrl_notes_unique
(hadm_id int,
 text varchar);""")

conn.commit();
```

```
[11]: xf = pd.read_sql("""
SELECT hadm_id
FROM mimiciii.ctrl_notes_sink """, engine)

# get list of ids
cxf_ids = xf.hadm_id.unique()
```

this will take about 15 minutes to run

```
[12]: s = time.time()

for j in tqdm_notebook(cxf_ids):

    sql = """
    SELECT hadm_id, text
    FROM mimiciii.ctrl_notes_sink
    WHERE hadm_id in ({0})
    """

    # run sql query above to pull all notes for one admission (already in order
    ↳by date)
    sql = sql.format(j)
    cnotes = pd.read_sql(sql, engine)

    # split into tokens based on a period followed by a space or a newline \n
    ↳ (the period and \n are included in the token)
    input_cnotes = cnotes.text.tolist()[0]

    unique_tokens = bloatectomy(input_cnotes)
```

```

# save as a new dataframe
xtext2 = [(j, unique_tokens)]
xfulltext=pd.DataFrame(xtext2, columns=['hadm_id', 'text'])

# append user and single note to the new table in database
table_name = 'ctrl_notes_unique'

z = time.time()

xfulltext.to_sql(table_name, con=engine, if_exists='append', chunksize=1,
↳index=False, schema='mimiciiii')

# print('per hadmid-',time.time() - z)

print('total-', (time.time() - s)/60,'minutes')

conn.commit()

```

HBox(children=(IntProgress(value=0, max=27888), HTML(value='')))

total- 38.29251765012741 minutes

```

[13]: cur.execute(""" SELECT COUNT(*), COUNT(DISTINCT hadm_id) FROM ctrl_notes_unique;
↳""")

print( pd.DataFrame(cur.fetchall(), columns=[ 'total notes count', 'ctrl_
↳admissions with notes']).to_string(index=False))

```

total notes count	ctrl admissions with notes
27888	27888

```

[14]: conn.commit()
cur.close()
conn.close()

```