

# Warmup

Draw an **object diagram** depicting the state of the program's memory after executing the code to the right.

Assume the following subtype relationships:


- Cat <: Pet
- Manx <: Cat
- Birman <: Cat

```
Pet p = new Birman();
```

```
Cat c = (Cat)p;
```

```
p = new Manx();
```

```
Manx m = (Manx)p;
```



# Warmup

What is the **dynamic type** of the object referenced by c?

```
Pet p = new Birman();
```

```
Cat c = (Cat)p;
```

```
p = new Manx();
```

```
Manx m = (Manx)p;
```

- A. Pet
- B. Cat
- C. Birman
- D. Manx
- E. A `ClassCastException` would be thrown




# Warmup (solution)

```
Pet p = new Birman();
```

```
Cat c = (Cat)p;
```

```
p = new Manx();
```

```
Manx m = (Manx)p;
```



# CS 2110

## Lecture 6

Inheritance, equality



Coming up

---

A2 released

---

A1 grades incoming

---

Quiz 3

# ORGANIZATION CHART

of

## THE TABULATING MACHINE CO.

### BOARD OF DIRECTORS - C-T-R- CO.

Alfred DeBuys	Clarence P. King
George W. Fairchild	Stacy C. Richmond
Charles R. Flint	Joseph E. Rogers
A. Ward Ford	Christopher D. Smithers
Oscar L. Gubelman	Thomas J. Watson
Samuel M. Hastings	George I. Wilber
John W. Herbert	Rollin S. Woodruff
Joel S. Coffin	

### OFFICERS-C-T-R-CO.

Thomas J. Watson - Pres & Genl. Mgr.  
George W. Fairchild - Vice-President  
James S. Ogsbury - Secy & Treasurer

COMPUTING-TABULATING-RECORDING CO.  
Offices - 50 Broad St. - New York City

### THE TABULATING MACHINE CO.

General Offices - 50 Broad St.  
New York City

#### DIRECTORS


George M. Bond James S. Ogsbury  
George W. Fairchild Gershom Smith  
Thomas J. Watson

FACTORIES - WASHINGTON, D. C.  
- ENDICOTT, N. Y.  
- DAYTON, O.

THOMAS J. WATSON *President*  
R. L. Houston *General Manager*

#### OFFICERS

Thomas J. Watson - President  
Gershom Smith - Vice-President  
R. L. Houston - Treasurer  
W. D. Jones - Asst. Treasurer  
James S. Ogsbury - Secretary  
O. E. Braitmayer - Asst. Secretary



# Chess pieces revisited

```
public class Knight
    implements Piece {
    private int row;
    private int col;
    private int player;
    public int player() {
        return player;
    }
    // ...
}
```

```
public class King
    implements Piece {
    private int row;
    private int col;
    private int player;
    private boolean hasMoved;
    public int player() {
        return player;
    }
    // ...
}
```

# Chess pieces revisited

```
public class Knight
    implements Piece {
    private int row;
    private int col;
    private int player;
    public int player() {
        return player;
    }
    // ...
}
```

```
public class King
    implements Piece {
    private int row;
    private int col;
    private int player;
    private boolean hasMoved;
    public int player() {
        return player;
    }
    // ...
}
```



# DRY principle: Don't repeat yourself

---

- Duplicated code is not just tedious to write (or copy-paste) the first time
  - To fix a bug in duplicated code, must find all instances
  - Modifications that aren't repeated everywhere lead to deviation in "common" behavior
- OOP languages can help you avoid duplication



# Commonality beyond interfaces

- Interfaces guarantee *availability* of behaviors
- What if types have similar state? Identical behaviors?
  - Interfaces can't provide fields or method bodies that depend on fields
  - (they can provide method bodies that depend only on other methods)
- **Subclasses** allow a *derived class* to **inherit** fields and method bodies from a *parent class*
  - `class Derived extends Parent {...}`
  - Implies a *subtype* relationship: `Derived <: Parent`

# Piece as a *superclass*

```
public class Piece {  
    private int row;  
    private int col;  
    private int player;  
  
    public Piece(int row,  
                 int col, int player) {  
        this.row = row;  
        this.col = col;  
        this.player = player;  
    }  
}
```

```
    public int player() {  
        return player;  
    }  
  
    public boolean legalMove(  
        int dstRow, int dstCol,  
        Board board) { ??? }  
}
```

# King as a subclass

```
public class King
    extends Piece {
    private boolean hasMoved;

    public King(int player) {
        super((player==1)?0:7,
              3, player);
        hasMoved = false;
    }
}
```

```
@Override
    public boolean legalMove(
        int dstRow
        int dstCol,
        Board board) {...}
}
```

# Object diagram showing inheritance

King

Piece

row: int

player: int

col: int

- player()
- ~~legalMove()~~

King

hasMoved: int

- @Override  
legalMove()

Parent section  
(above)


Derived section  
(below)

# Accessibility


- Subclasses cannot see private members of parent class
  - Is this a concern?
- “Specialization interface”: in what ways can subclasses tweak the behavior of a parent?
  - Another layer of **encapsulation**
- **private** (“don’t mess with my invariants”)
  - Parent class has exclusive responsibility
- **protected** (“I’m trusting you”)
  - Derived classes have rights and responsibilities
- **public**
  - The “client interface” is also usable by derived classes

# Constructors

- Since some state *could* be private, subclass *must* call a parent class constructor
  - Invoked using `super()`
  - Must be *first* statement in subclass constructor



- Delegation order: fully construct superclass, then specialize




# Overriding

- A subclass method with the same signature as a parent class method will **override** it
  - Whenever that method is invoked on the object, the *subclass* version will be executed
  - Consequence of **dynamic dispatch**

```
class Piece {  
    boolean legalMove(  
        int r, int c, Board b) {  
        // IDK?  
    }  
}  
  
class Pawn {  
    @Override  
    boolean legalMove(  
        int r, int c, Board b) {  
        // Pawn logic  
    }  
}
```



# Dynamic dispatch illustrated




```
Piece p = selectPiece();  
// user selects a Pawn  
p.move(newRow, newCol);  
// which class's move()  
// code is run?
```

# Overriding

- A subclass method with the same signature as a parent class method will **override** it
  - Whenever that method is invoked on the object, the *subclass* version will be executed
  - Consequence of **dynamic dispatch**
- Impossible for *client* to request a parent implementation
  - Only subclass impl could know about all the relevant invariants
- Subclass may delegate to its parent's implementation
  - `@Override`  
`public void move(int r, int c) {`  
`super.move(r, c);`  
`checkPromotion();`  
`}`
- No way to prefer “grandparent’s” implementation

# Bottom-up rule



*Pawn*

```
class Piece {
    boolean legalMove(...) {}
    void move(...) {
        if (legalMove(...)) {}
    }
}
class Pawn {
    @Override boolean legalMove(...) {}
    @Override void move(...) {
        super.move(...);
        checkPromotion();
    }
}
```

# Checkpoint



```
class Parent {  
    int foo(int x) { /* Parent impl */ }  
    int bar(int x) {  
        return foo(2*x + 1);  
    }  
}  
  
class Derived extends Parent {  
    int foo(int x) { /* Derived impl */ }  
}  
  
class Child extends Parent {  
    int bar(int x) {  
        return super.foo(x - 1);  
    }  
}
```

Which blocks of code are executed when the following client code is run?

```
Parent p = new Derived();  
int ans = p.bar(42);
```


- A: `/* Parent impl */`
- B: `/* Derived impl */`
- C: Both `Parent impl` and `Derived impl`
- D: None of these
- E: Compile-time error

# Checkpoint

```
class Parent {  
    int foo(int x) { /* Parent impl */ }  
    int bar(int x) {  
        return foo(2*x + 1);  
    }  
}  
class Derived extends Parent {  
    int foo(int x) { /* Derived impl */ }  
}  
class Child extends Parent {  
    int bar(int x) {  
        return super.foo(x - 1);  
    }  
}
```

Which blocks of code are executed  
when the following client code is run?

```
Parent p = new Derived();  
int ans = p.bar(42);
```



# Abstract classes

- How should Piece implement `legalMove()` itself?
- Who should be allowed to construct a Piece?
  - Not a concern with **interface** – no method bodies, no constructor
- Abstract classes
  - Cannot be constructed on their own (must construct a subclass)
    - Even though they may define a constructor
  - May have abstract methods
    - Declarations only (like interfaces)
- Subclass must override all abstract methods, or be abstract itself

# Piece as an abstract superclass

```
public abstract class Piece {  
    protected int row;  
    protected int col;  
    private int player;  
  
    protected Piece(int row,  
                    int col, int player) {  
        this.row = row;  
        this.col = col;  
        this.player = player;  
    }  
}
```

```
    public int player() {  
        return player;  
    }  
  
    public abstract boolean  
        legalMove(int dstRow,  
                  int dstCol, Board board);  
}
```


Class Object





# Relationships

- Java only supports *single inheritance*
  - Only one superclass
  - Reserve for “is-a” relationship
- Classes may implement multiple interfaces
  - “Can-do” relationship
- Interfaces may extend (multiple) other interfaces



# Relationships

- Don't forget about **composition**
  - Reference an instance of another class in a field
  - “Has a” relationship
  - Often most flexible, maintainable kind of relationship

# Object

- All classes are a subtype of Object
  - If no `extends` clause, then `Object` is the superclass
  - Interfaces implicitly must be implemented by an `Object`
- `Object` provides useful universal methods that you may want to override
  - `toString()`
  - `equals()`
  - `hashCode()`

# toString() example: Point

```
public class Point {  
    private double x;  
    private double y;  
  
    @Override  
    public String toString() {  
        return "(" + x + "," + y + ")";  
    }  
}
```

# Equality

## Referential equality (identity)

- Are two objects the same object?
- Test using `==`
- Best avoided in most client code
  - Let classes define their own equivalence relations

## Logical equality (state)

- Should two objects be considered equivalent (substitutable)?
- Test using `equals()`
  - Defaults to referential equality
  - May override `equals()` to define value equality
    - Danger if class is mutable

# Equivalence relations

- Reflexive
  - You equal yourself
- Symmetric
  - If you equal someone, they equal you
- Transitive
  - If you equal someone and they equal someone else, you also equal that someone else

# Overriding .equals()

```
@Override
```

```
public boolean equals(Object other) {  
    if (!(other instanceof Point)) {  
        return false;  
    }  
    Point p = (Point) other;  
    return x == p.x && y == p.y;  
}
```


*Warning: not **symmetric** if  
subclasses might be compared  
with superclasses*

# getClass()

- To look at the exact dynamic type of an object (rather than an upper bound), use [getClass\(\)](#) (inherited from Object)
  - Reserve for special cases
- Stronger equals() template:

```
@Override
public boolean equals(Object obj) {
    if ((obj == null) || (getClass() != obj.getClass())) {
        return false;
    }
    MyClass objAsMC = (MyClass) obj;
    // Compare fields
}
```





# Exceptions

try, catch, throw(s)