

Universidad Nacional de San Agustín de Arequipa

Pocochuk's Mafia

Juan Soto B, Julio Yauri, Alejandro Phocco

2026-11-07

1 Contest 1

2 Mathematics 1

3 Data structures 3

4 Numerical 6

5 Number theory 10

6 Combinatorial 12

7 Graph 13

8 Geometry 21

9 Strings 27

10 Various 29

Contest (1)

template.cpp

```
#include <bits/stdc++.h>
using namespace std;

#define rep(i, a, b) for(int i = a; i < (b); ++i)
#define all(x) begin(x), end(x)
#define sz(x) (int)(x).size()
typedef long long ll;
typedef pair<int, int> pii;
typedef vector<int> vi;
typedef vector<vi> vvi;

int main() {
  cin.tie(0)->sync_with_stdio(0);
  cin.exceptions(cin.failbit);
}
```

.bashrc

```
alias c='g++ -Wall -Wconversion -Wfatal-errors -g -std=c++17 \
  -fsanitize=undefined,address'
xmodmap -e 'clear lock' -e 'keycode 66=less greater' #caps = <>
```

.vimrc

```
set cin aw ai is ts=4 sw=4 tm=50 nu noeb bg=dark ru cul
sy on   |   im jk <esc>   |   im kj <esc>   |   no ; :
" Select region and then type :Hash to hash your selection.
" Useful for verifying that there aren't mistypes.
ca Hash w !cpp -dD -P -fpreprocessed \| tr -d '[:space:]' \
 \| md5sum \| cut -c-6
```

hash.sh

```
# Hashes a file, ignoring all whitespace and comments. Use for
# verifying that code was correctly typed.
cpp -dD -P -fpreprocessed | tr -d '[:space:]'| md5sum |cut -c-6
```

troubleshoot.txt

```
Pre-submit:
Write a few simple test cases if sample is not enough.
Are time limits close? If so, generate max cases.
Is the memory usage fine?
Could anything overflow?
Make sure to submit the right file.

Wrong answer:
Print your solution! Print debug output, as well.
Are you clearing all data structures between test cases?
Can your algorithm handle the whole range of input?
Read the full problem statement again.
Do you handle all corner cases correctly?
Have you understood the problem correctly?
Any uninitialized variables?
Any overflows?
Confusing N and M, i and j, etc.?
Are you sure your algorithm works?
What special cases have you not thought of?
Are you sure the STL functions you use work as you think?
Add some assertions, maybe resubmit.
Create some testcases to run your algorithm on.
Go through the algorithm for a simple case.
Go through this list again.
Explain your algorithm to a teammate.
Ask the teammate to look at your code.
Go for a small walk, e.g. to the toilet.
Is your output format correct? (including whitespace)
Rewrite your solution from the start or let a teammate do it.

Runtime error:
Have you tested all corner cases locally?
Any uninitialized variables?
Are you reading or writing outside the range of any vector?
Any assertions that might fail?
Any possible division by 0? (mod 0 for example)
Any possible infinite recursion?
Invalidated pointers or iterators?
Are you using too much memory?
Debug with resubmits (e.g. remapped signals, see Various).

Time limit exceeded:
Do you have any possible infinite loops?
What is the complexity of your algorithm?
Are you copying a lot of unnecessary data? (References)
How big is the input and output? (consider scanf)
Avoid vector, map. (use arrays/unordered_map)
What do your teammates think about your algorithm?

Memory limit exceeded:
What is the max amount of memory your algorithm should need?
Are you clearing all data structures between test cases?
```

Mathematics (2)

2.1 Equations

$$ax^2 + bx + c = 0 \Rightarrow x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$$

The extremum is given by $x = -b/2a$.

$$\begin{aligned} ax + by &= e \\ cx + dy &= f \end{aligned} \Rightarrow \begin{aligned} x &= \frac{ed - bf}{ad - bc} \\ y &= \frac{af - ec}{ad - bc} \end{aligned}$$

In general, given an equation $Ax = b$, the solution to a variable x_i is given by

$$x_i = \frac{\det A_i'}{\det A}$$

where A_i' is A with the i'th column replaced by b.

2.2 Recurrences

If $a_n = c_1 a_{n-1} + \cdots + c_k a_{n-k}$, and $r_1, \ldots, r_k$ are distinct roots of $x^k - c_1 x^{k-1} - \cdots - c_k$, there are $d_1, \ldots, d_k$ s.t.

$$a_n = d_1 r_1^n + \cdots + d_k r_k^n.$$

Non-distinct roots r become polynomial factors, e.g. $a_n = (d_1 n + d_2) r^n$.

2.3 Trigonometry

$$\sin(v + w) = \sin v \cos w + \cos v \sin w$$
$$\cos(v + w) = \cos v \cos w - \sin v \sin w$$

$$\tan(v + w) = \frac{\tan v + \tan w}{1 - \tan v \tan w}$$
$$\sin v + \sin w = 2 \sin \frac{v + w}{2} \cos \frac{v - w}{2}$$
$$\cos v + \cos w = 2 \cos \frac{v + w}{2} \cos \frac{v - w}{2}$$

$$(V + W) \tan(v - w)/2 = (V - W) \tan(v + w)/2$$

where V, W are lengths of sides opposite angles v, w.

$$a \cos x + b \sin x = r \cos(x - \phi)$$
$$a \sin x + b \cos x = r \sin(x + \phi)$$

where $r = \sqrt{a^2 + b^2}, \phi = \text{atan2}(b, a)$.

2.4 Geometry

2.4.1 Triangles

Side lengths: a, b, c

Semiperimeter: $p = \frac{a + b + c}{2}$

Area: $A = \sqrt{p(p - a)(p - b)(p - c)}$

Circumradius: $R = \frac{abc}{4A}$

Inradius: $r = \frac{A}{p}$

Length of median (divides triangle into two equal-area triangles): $m_a = \frac{1}{2}\sqrt{2b^2 + 2c^2 - a^2}$

Length of bisector (divides angles in two):

$$s_a = \sqrt{bc\left[1 - \left(\frac{a}{b+c}\right)^2\right]}$$

Law of sines: $\frac{\sin\alpha}{a} = \frac{\sin\beta}{b} = \frac{\sin\gamma}{c} = \frac{1}{2R}$

Law of cosines: $a^2 = b^2 + c^2 - 2bc\cos\alpha$

Law of tangents: $\frac{a+b}{a-b} = \frac{\tan\frac{\alpha+\beta}{2}}{\tan\frac{\alpha-\beta}{2}}$


2.4.2 Quadrilaterals

With side lengths a, b, c, d, diagonals e, f, diagonals angle θ, area A and magic flux $F = b^2 + d^2 - a^2 - c^2$:

$$4A = 2ef \cdot \sin\theta = F\tan\theta = \sqrt{4e^2f^2 - F^2}$$

For cyclic quadrilaterals the sum of opposite angles is $180°$, $ef = ac + bd$, and $A = \sqrt{(p-a)(p-b)(p-c)(p-d)}$.

2.4.3 Spherical coordinates



$$\begin{array}{cc} x = r\sin\theta\cos\phi & r = \sqrt{x^2+y^2+z^2} \\ y = r\sin\theta\sin\phi & \theta = \operatorname{acos}(z/\sqrt{x^2+y^2+z^2}) \\ z = r\cos\theta & \phi = \operatorname{atan2}(y,x) \end{array}$$

2.5 Derivatives/Integrals

$$\begin{array}{cc} \frac{d}{dx}\arcsin x = \frac{1}{\sqrt{1-x^2}} & \frac{d}{dx}\arccos x = -\frac{1}{\sqrt{1-x^2}} \\ \frac{d}{dx}\tan x = 1 + \tan^2 x & \frac{d}{dx}\arctan x = \frac{1}{1+x^2} \\ \int \tan ax = -\frac{\ln|\cos ax|}{a} & \int x\sin ax = \frac{\sin ax - ax\cos ax}{a^2} \\ \int e^{-x^2} = \frac{\sqrt{\pi}}{2}\operatorname{erf}(x) & \int xe^{ax}dx = \frac{e^{ax}}{a^2}(ax-1) \end{array}$$

Integration by parts:

$$\int_a^b f(x)g(x)dx = [F(x)g(x)]_a^b - \int_a^b F(x)g'(x)dx$$

2.6 Sums

$$c^a + c^{a+1} + \cdots + c^b = \frac{c^{b+1} - c^a}{c-1}, c \neq 1$$

$$1 + 2 + 3 + \cdots + n = \frac{n(n+1)}{2}$$

$$1^2 + 2^2 + 3^2 + \cdots + n^2 = \frac{n(2n+1)(n+1)}{6}$$

$$1^3 + 2^3 + 3^3 + \cdots + n^3 = \frac{n^2(n+1)^2}{4}$$

$$1^4 + 2^4 + 3^4 + \cdots + n^4 = \frac{n(n+1)(2n+1)(3n^2+3n-1)}{30}$$

2.7 Series

$$e^x = 1 + x + \frac{x^2}{2!} + \frac{x^3}{3!} + \ldots, (-\infty < x < \infty)$$

$$\ln(1+x) = x - \frac{x^2}{2} + \frac{x^3}{3} - \frac{x^4}{4} + \ldots, (-1 < x \leq 1)$$

$$\sqrt{1+x} = 1 + \frac{x}{2} - \frac{x^2}{8} + \frac{2x^3}{32} - \frac{5x^4}{128} + \ldots, (-1 \leq x \leq 1)$$

$$\sin x = x - \frac{x^3}{3!} + \frac{x^5}{5!} - \frac{x^7}{7!} + \ldots, (-\infty < x < \infty)$$

$$\cos x = 1 - \frac{x^2}{2!} + \frac{x^4}{4!} - \frac{x^6}{6!} + \ldots, (-\infty < x < \infty)$$

2.8 Probability theory

Let X be a discrete random variable with probability $p_X(x)$ of assuming the value x. It will then have an expected value (mean) $\mu = \mathbb{E}(X) = \sum_x xp_X(x)$ and variance $\sigma^2 = V(X) = \mathbb{E}(X^2) - (\mathbb{E}(X))^2 = \sum_x (x - \mathbb{E}(X))^2 p_X(x)$ where σ is the standard deviation. If X is instead continuous it will have a probability density function $f_X(x)$ and the sums above will instead be integrals with $p_X(x)$ replaced by $f_X(x)$.

Expectation is linear:

$$\mathbb{E}(aX + bY) = a\mathbb{E}(X) + b\mathbb{E}(Y)$$

For independent X and Y,

$$V(aX + bY) = a^2V(X) + b^2V(Y).$$

2.8.1 Discrete distributions

Binomial distribution

The number of successes in n independent yes/no experiments, each which yields success with probability p is $\mathrm{Bin}(n,p)$, $n = 1, 2, \ldots$, $0 \leq p \leq 1$.

$$p(k) = \binom{n}{k}p^k(1-p)^{n-k}$$

$$\mu = np,\ \sigma^2 = np(1-p)$$

$\mathrm{Bin}(n,p)$ is approximately $\mathrm{Po}(np)$ for small p.

First success distribution

The number of trials needed to get the first success in independent yes/no experiments, each which yields success with probability p is $\mathrm{Fs}(p)$, $0 \leq p \leq 1$.

$$p(k) = p(1-p)^{k-1},\ k = 1, 2, \ldots$$

$$\mu = \frac{1}{p},\ \sigma^2 = \frac{1-p}{p^2}$$

Poisson distribution

The number of events occurring in a fixed period of time t if these events occur with a known average rate κ and independently of the time since the last event is $\mathrm{Po}(\lambda)$, $\lambda = t\kappa$.

$$p(k) = e^{-\lambda}\frac{\lambda^k}{k!}, k = 0, 1, 2, \ldots$$

$$\mu = \lambda,\ \sigma^2 = \lambda$$

2.8.2 Continuous distributions

Uniform distribution

If the probability density function is constant between a and b and 0 elsewhere it is $\mathrm{U}(a,b)$, $a < b$.

$$f(x) = \begin{cases} \frac{1}{b-a} & a < x < b \\ 0 & \text{otherwise} \end{cases}$$

$$\mu = \frac{a+b}{2},\ \sigma^2 = \frac{(b-a)^2}{12}$$

Exponential distribution

The time between events in a Poisson process is $\mathrm{Exp}(\lambda)$, $\lambda > 0$.

$$f(x) = \begin{cases} \lambda e^{-\lambda x} & x \geq 0 \\ 0 & x < 0 \end{cases}$$

$$\mu = \frac{1}{\lambda},\ \sigma^2 = \frac{1}{\lambda^2}$$

Normal distribution

Most real random values with mean μ and variance σ^2 are well described by $\mathcal{N}(\mu, \sigma^2)$, $\sigma > 0$.

$$f(x) = \frac{1}{\sqrt{2\pi\sigma^2}}e^{-\frac{(x-\mu)^2}{2\sigma^2}}$$

If $X_1 \sim \mathcal{N}(\mu_1, \sigma_1^2)$ and $X_2 \sim \mathcal{N}(\mu_2, \sigma_2^2)$ are independent, then

$$aX_1 + bX_2 + c \sim \mathcal{N}(a\mu_1 + b\mu_2 + c, a^2\sigma_1^2 + b^2\sigma_2^2)$$

2.9 Markov chains

A *Markov chain* is a discrete random process with the property that the next state depends only on the current state. Let $X_1, X_2, \ldots$ be a sequence of random variables generated by the Markov process. Then there is a transition matrix $\mathbf{P} = (p_{ij})$, with $p_{ij} = \Pr(X_n = i | X_{n-1} = j)$, and $\mathbf{p}^{(n)} = \mathbf{P}^n \mathbf{p}^{(0)}$ is the probability distribution for X_n (i.e., $p_i^{(n)} = \Pr(X_n = i)$), where $\mathbf{p}^{(0)}$ is the initial distribution.

π is a stationary distribution if $\pi = \mathbf{P}\pi$. If the Markov chain is *irreducible* (it is possible to get to any state from any state), then $\pi_i = \frac{1}{\mathbb{E}(T_i)}$ where $\mathbb{E}(T_i)$ is the expected time between two visits in state i. π_j/π_i is the expected number of visits in state j between two visits in state i.

For a connected, undirected and non-bipartite graph, where the transition probability is uniform among all neighbors, π_i is proportional to node i's degree.

A Markov chain is *ergodic* if the asymptotic distribution is independent of the initial distribution. A finite Markov chain is ergodic iff it is irreducible and *aperiodic* (i.e., the gcd of cycle lengths is 1). $\lim_{k\to\infty} \mathbf{P}^k = \mathbf{1}\pi$.

A Markov chain is an A-chain if the states can be partitioned into two sets $\mathbf{A}$ and $\mathbf{G}$, such that all states in $\mathbf{A}$ are absorbing ($p_{ii} = 1$), and all states in $\mathbf{G}$ leads to an absorbing state in $\mathbf{A}$. The probability for absorption in state $i \in \mathbf{A}$, when the initial state is j, is $a_{ij} = p_{ij} + \sum_{k\in\mathbf{G}} a_{ik} p_{kj}$. The expected time until absorption, when the initial state is i, is $t_i = 1 + \sum_{k\in\mathbf{G}} p_{ki} t_k$.

Data structures (3)

OrderStatisticTree.h

Description: A set (not multiset!) with support for finding the n'th element, and finding the index of an element. To get a map, change `null_type`.
Time: $\mathcal{O}(\log N)$

782797, 16 lines

```
#include <bits/extc++.h>
using namespace __gnu_pbds;

template<class T>
using Tree = tree<T, null_type, less<T>, rb_tree_tag,
    tree_order_statistics_node_update>;

void example() {
  Tree<int> t, t2; t.insert(8);
  auto it = t.insert(10).first;
  assert(it == t.lower_bound(9));
  assert(t.order_of_key(10) == 1);
  assert(t.order_of_key(11) == 2);
  assert(*t.find_by_order(0) == 8);
  t.join(t2); // assuming T< T2 or T> T2, merge t2 into t
}
```

HashMap.h

Description: Hash map with mostly the same API as unordered_map, but ~3x faster. Uses 1.5x memory. Initial capacity must be a power of 2 (if provided).

d77092, 7 lines

```
#include <bits/extc++.h>
// To use most bits rather than just the lowest ones:
struct chash { // large odd number for C
  const uint64_t C = ll(4e18 * acos(0)) | 71;
  ll operator()(ll x) const { return __builtin_bswap64(x*C); }
};
__gnu_pbds::gp_hash_table<ll,int,chash> h({},{},{},{},{1<<16});
```

SegmentTree.h

Description: Zero-indexed max-tree. Bounds are inclusive to the left and exclusive to the right. Can be changed by modifying T, f and unit.
Time: $\mathcal{O}(\log N)$

0f4bdb, 19 lines

```
struct Tree {
  typedef int T;
  static constexpr T unit = INT_MIN;
  T f(T a, T b) { return max(a, b); } // (any associative fn)
  vector<T> s; int n;
  Tree(int n = 0, T def = unit) : s(2*n, def), n(n) {}
  void update(int pos, T val) {
    for (s[pos += n] = val; pos /= 2;)
      s[pos] = f(s[pos * 2], s[pos * 2 + 1]);
  }
  T query(int b, int e) { // query [b, e)
    T ra = unit, rb = unit;
    for (b += n, e += n; b < e; b /= 2, e /= 2) {
      if (b % 2) ra = f(ra, s[b++]);
      if (e % 2) rb = f(s[--e], rb);
    }
    return f(ra, rb);
  }
};
```

MergeSortTree.h

Description: Save the entire sorted array in every node of the segment tree
Time: $\mathcal{O}(N \log N)$

f07e6a, 14 lines

```
void build(int v, int tl, int tr) {
  if(tl == tr) {
    tree[v] = vi(1, arr[tl]);
    return;
  }
  int tm = (tl + tr) / 2;
  build(2 * v, tl, tm);
  build(2 * v + 1, tm + 1, tr);
  merge(tree[v * 2].begin(), tree[v * 2].end(),
      tree[v * 2 + 1].begin(), tree[v * 2 + 1].end(),
      back_inserter(tree[v]));

}
// use lower/upper bound on queries
```

UnionFindRollback.h

Description: Disjoint-set data structure with undo. If undo is not needed, skip st, time() and rollback().
Usage: `int t = uf.time(); ...; uf.rollback(t);`
Time: $\mathcal{O}(\log(N))$

de4ad0, 21 lines

```
struct RollbackUF {
  vi e; vector<pii> st;
  RollbackUF(int n) : e(n, -1) {}
  int size(int x) { return -e[find(x)]; }
  int find(int x) { return e[x] < 0 ? x : find(e[x]); }
  int time() { return sz(st); }
  void rollback(int t) {
    for (int i = time(); i --> t;)
      e[st[i].first] = st[i].second;
    st.resize(t);
  }
  bool join(int a, int b) {
    a = find(a), b = find(b);
    if (a == b) return false;
    if (e[a] > e[b]) swap(a, b);
    st.push_back({a, e[a]});
    st.push_back({b, e[b]});
    e[a] += e[b]; e[b] = a;
    return true;
  }
};
```

SubMatrix.h

Description: Calculate submatrix sums quickly, given upper-left and lower-right corners (half-open).
Usage: `SubMatrix<int> m(matrix);`
`m.sum(0, 0, 2, 2); // top left 4 elements`
Time: $\mathcal{O}\left(N^2 + Q\right)$

c59ada, 13 lines

```
template<class T>
struct SubMatrix {
  vector<vector<T>> p;
  SubMatrix(vector<vector<T>>& v) {
    int R = sz(v), C = sz(v[0]);
    p.assign(R+1, vector<T>(C+1));
    rep(r,0,R) rep(c,0,C)
      p[r+1][c+1] = v[r][c] + p[r][c+1] + p[r+1][c] - p[r][c];
  }
  T sum(int u, int l, int d, int r) {
    return p[d][r] - p[d][l] - p[u][r] + p[u][l];
  }
};
```

Matrix.h

Description: Basic operations on square matrices.
Usage: `Matrix<int, 3> A;`
`A.d = {{{{1,2,3}}, {{4,5,6}}, {{7,8,9}}}};`
`array<int, 3> vec = {1,2,3};`
`vec = (A^N) * vec;`

4da5a2, 26 lines

```
template<class T, int N> struct Matrix {
  typedef Matrix M;
  array<array<T, N>, N> d{};
  M operator*(const M& m) const {
    M a;
    rep(i,0,N) rep(j,0,N)
      rep(k,0,N) a.d[i][k] += d[i][j] * m.d[j][k];
    return a;
  }
  array<T, N> operator*(const array<T, N>& vec) const {
    array<T, N> ret{};
    rep(i,0,N) rep(j,0,N) ret[i] += d[i][j] * vec[j];
    return ret;
  }
  M operator^(ll p) const {
    assert(p >= 0);
    M a, b(*this);
    rep(i,0,N) a.d[i][i] = 1;
    while (p) {
      if (p&1) a = a*b;
      b = b*b;
      p >>= 1;
    }
    return a;
  }
};
```

LineContainer.h

Description: Container where you can add lines of the form kx+m, and query maximum values at points x. Useful for dynamic programming ("convex hull trick").
Time: $\mathcal{O}(\log N)$ 8ec1c7, 30 lines

```
struct Line {
  mutable ll k, m, p;
  bool operator<(const Line& o) const { return k < o.k; }
  bool operator<(ll x) const { return p < x; }
};

struct LineContainer : multiset<Line, less<>> {
  // (for doubles, use inf = 1/.0, div(a,b) = a/b)
  static const ll inf = LLONG_MAX;
  ll div(ll a, ll b) { // floored division
    return a / b - ((a ^ b) < 0 && a % b); }
  bool isect(iterator x, iterator y) {
    if (y == end()) return x->p = inf, 0;
    if (x->k == y->k) x->p = x->m > y->m ? inf : -inf;
    else x->p = div(y->m - x->m, x->k - y->k);
    return x->p >= y->p;
  }
  void add(ll k, ll m) {
    auto z = insert({k, m, 0}), y = z++, x = y;
    while (isect(y, z)) z = erase(z);
    if (x != begin() && isect(--x, y)) isect(x, y = erase(y));
    while ((y = x) != begin() && (--x)->p >= y->p)
      isect(x, erase(y));
  }
  ll query(ll x) {
    assert(!empty());
    auto l = *lower_bound(x);
    return l.k * x + l.m;
  }
};
```

Treap.h

Description: A short self-balancing tree. It acts as a sequential container with log-time splits/joins, and is easy to augment with additional data.
Time: $\mathcal{O}(\log N)$ 1754b4, 53 lines

```
struct Node {
  Node *l = 0, *r = 0;
  int val, y, c = 1;
  Node(int val) : val(val), y(rand()) {}
  void recalc();
};

int cnt(Node* n) { return n ? n->c : 0; }
void Node::recalc() { c = cnt(l) + cnt(r) + 1; }

template<class F> void each(Node* n, F f) {
  if (n) { each(n->l, f); f(n->val); each(n->r, f); }
}

pair<Node*, Node*> split(Node* n, int k) {
  if (!n) return {};
  if (cnt(n->l) >= k) { // "n->val >= k" for lower_bound(k)
    auto [L,R] = split(n->l, k);
    n->l = R;
    n->recalc();
    return {L, n};
  } else {
    auto [L,R] = split(n->r,k - cnt(n->l) - 1); // and just "k"
    n->r = L;
    n->recalc();
    return {n, R};
  }
}

Node* merge(Node* l, Node* r) {
  if (!l) return r;
  if (!r) return l;
  if (l->y > r->y) {
    l->r = merge(l->r, r);
    return l->recalc(), l;
  } else {
    r->l = merge(l, r->l);
    return r->recalc(), r;
  }
}

Node* ins(Node* t, Node* n, int pos) {
  auto [l,r] = split(t, pos);
  return merge(merge(l, n), r);
}

// Example application: move the range [l, r) to index k
void move(Node*& t, int l, int r, int k) {
  Node *a, *b, *c;
  tie(a,b) = split(t, l); tie(b,c) = split(b, r - l);
  if (k <= l) t = merge(ins(a, b, k), c);
  else t = merge(a, ins(c, b, k - r));
}
```

FenwickTree.h

Description: Computes partial sums a[0] + a[1] + ... + a[pos - 1], and updates single elements a[i], taking the difference between the old and new value.
Time: Both operations are $\mathcal{O}(\log N)$. e62fac, 22 lines

```
struct FT {
  vector<ll> s;
  FT(int n) : s(n) {}
  void update(int pos, ll dif) { // a[pos] += dif
    for (; pos < sz(s); pos |= pos + 1) s[pos] += dif;
  }
  ll query(int pos) { // sum of values in [0, pos)
    ll res = 0;
    for (; pos > 0; pos &= pos - 1) res += s[pos-1];
    return res;
  }
  int lower_bound(ll sum) {// min pos st sum of [0, pos] >= sum
    // Returns n if no sum is >= sum, or -1 if empty sum is.
    if (sum <= 0) return -1;
    int pos = 0;
    for (int pw = 1 << 25; pw; pw >>= 1) {
      if (pos + pw <= sz(s) && s[pos + pw-1] < sum)
        pos += pw, sum -= s[pos-1];
    }
    return pos;
  }
};
```

FenwickTree2d.h

Description: Computes sums a[i,j] for all i<I, j<J, and increases single elements a[i,j]. Requires that the elements to be updated are known in advance (call fakeUpdate() before init()).
Time: $\mathcal{O}\left(\log^2 N\right)$. (Use persistent segment trees for $\mathcal{O}(\log N)$.)
"FenwickTree.h" 157f07, 22 lines

```
struct FT2 {
  vector<vi> ys; vector<FT> ft;
  FT2(int limx) : ys(limx) {}
  void fakeUpdate(int x, int y) {
    for (; x < sz(ys); x |= x + 1) ys[x].push_back(y);
  }
  void init() {
    for (vi& v : ys) sort(all(v)), ft.emplace_back(sz(v));
  }
  int ind(int x, int y) {
    return (int)(lower_bound(all(ys[x]), y) - ys[x].begin()); }
  void update(int x, int y, ll dif) {
    for (; x < sz(ys); x |= x + 1)
      ft[x].update(ind(x, y), dif);
  }
  ll query(int x, int y) {
    ll sum = 0;
    for (; x; x &= x - 1)
      sum += ft[x-1].query(ind(x-1, y));
    return sum;
  }
};
```

BIT2D.h

Description: $(x1, y1)(x2, y2)$ querys in $O(Qlog^2N)$.
Time: $\mathcal{O}\left(Q \log^2 N\right)$ 24a6a2, 21 lines

```
const int N = 1000 + 100;
inline int lso(int nm){return (nm & (-nm));}
vector<vi> ft(N , vi(N, 0));

void update(int x, int y, int val){
    for(; x < N ; x += lso(x))
        for(int j = y; j < N; j += lso(j))
            ft[x][j] += val;
}

int query(int x , int y){
    int ans = 0;
    for(; x ; x -= lso(x))
        for(int j = y; j; j -= lso(j))
            ans += ft[x][j];
    return ans;
}

int get(int x1, int y1 , int x2 , int y2){
    return query(x2 , y2) - query(x1 - 1 , y2) - query(x2 , y1
        - 1) + query(x1 - 1 , y1 - 1);
}
```

RMQ.h

Description: Range Minimum Queries on an array. Returns min(V[a], V[a + 1], ... V[b - 1]) in constant time.
Usage: `RMQ rmq(values);`
`rmq.query(inclusive, exclusive);`
Time: $\mathcal{O}(|V| \log |V| + Q)$ 510c32, 16 lines

```
template<class T>
struct RMQ {
  vector<vector<T>> jmp;
  RMQ(const vector<T>& V) : jmp(1, V) {
    for (int pw = 1, k = 1; pw * 2 <= sz(V); pw *= 2, ++k) {
      jmp.emplace_back(sz(V) - pw * 2 + 1);
      rep(j,0,sz(jmp[k]))
        jmp[k][j] = min(jmp[k - 1][j], jmp[k - 1][j + pw]);
    }
  }
  T query(int a, int b) {
    assert(a < b); // or return inf if a == b
    int dep = 31 - __builtin_clz(b - a);
    return min(jmp[dep][a], jmp[dep][b - (1 << dep)]);
  }
};
```

MoQueries.h

Description: Answer interval or tree path queries by finding an approximate TSP through the queries, and moving from one query to the next by adding/removing points at the ends. If values are on tree edges, change `step` to add/remove the edge (a, c) and remove the initial `add` call (but keep `in`).
Time: $\mathcal{O}\left(N\sqrt{Q}\right)$
a12ef4, 49 lines

```
void add(int ind, int end) { ... } // add a[ind] (end = 0 or 1)
void del(int ind, int end) { ... } // remove a[ind]
int calc() { ... } // compute current answer

vi mo(vector<pii> Q) {
  int L = 0, R = 0, blk = 350; // ~N/sqrt(Q)
  vi s(sz(Q)), res = s;
#define K(x) pii(x.first/blk, x.second ^ -(x.first/blk & 1))
  iota(all(s), 0);
  sort(all(s), [&](int s, int t){ return K(Q[s]) < K(Q[t]); });
  for (int qi : s) {
    pii q = Q[qi];
    while (L > q.first) add(--L, 0);
    while (R < q.second) add(R++, 1);
    while (L < q.first) del(L++, 0);
    while (R > q.second) del(--R, 1);
    res[qi] = calc();
  }
  return res;
}

vi moTree(vector<array<int, 2>> Q, vector<vi>& ed, int root=0){
  int N = sz(ed), pos[2] = {}, blk = 350; // ~N/sqrt(Q)
  vi s(sz(Q)), res = s, I(N), L(N), R(N), in(N), par(N);
  add(0, 0), in[0] = 1;
  auto dfs = [&](int x, int p, int dep, auto& f) -> void {
    par[x] = p;
    L[x] = N;
    if (dep) I[x] = N++;
    for (int y : ed[x]) if (y != p) f(y, x, !dep, f);
    if (!dep) I[x] = N++;
    R[x] = N;
  };
  dfs(root, -1, 0, dfs);
#define K(x) pii(I[x[0]] / blk, I[x[1]] ^ -(I[x[0]] / blk & 1))
  iota(all(s), 0);
  sort(all(s), [&](int s, int t){ return K(Q[s]) < K(Q[t]); });
  for (int qi : s) rep(end,0,2) {
    int &a = pos[end], b = Q[qi][end], i = 0;
#define step(c) { if (in[c]) { del(a, end); in[a] = 0; } \
                  else { add(c, end); in[c] = 1; } a = c; }
    while (!(L[b] <= L[a] && R[a] <= R[b]))
      I[i++] = b, b = par[b];
    while (a != b) step(par[a]);
    while (i--) step(I[i]);
    if (end) res[qi] = calc();
  }
  return res;
}
```

MoLechugon.h

Description: Ans querys offline in N * SQRT(Q).
Time: $\mathcal{O}\left(N\sqrt{Q}\right)$
b11c26, 55 lines

```
const int N = 2e5 + 10;
int arr[N];
int cnt[1000020];
int BLOCK_SIZE; // 450 aprox for N = 2e5 , 350 for N = 1e5
struct query{
    int l;
    int r;
    int idx;
    query(){}
    query(int l,  int r , int idx) : l(l) , r(r) , idx(idx){}
    bool operator<(const query& rhs) const {
        if(l / BLOCK_SIZE == rhs.l / BLOCK_SIZE)
            return r < rhs.r;
        return l / BLOCK_SIZE < rhs.l / BLOCK_SIZE;
    }
};
ll ans = 0;
void add(int id){
    int x = arr[id];
    ans -= 1ll * cnt[x] * cnt[x] * x;
    cnt[x]++;
    ans += 1ll * cnt[x] * cnt[x] * x;
}
void remove(int id){
    int x = arr[id];
    ans -= 1ll * cnt[x] * cnt[x] * x;
    cnt[x]--;
    ans += 1ll * cnt[x] * cnt[x] * x;
}

int main(){
    ios_base::sync_with_stdio(0);
    cin.tie(0);
    int n; cin >> n;
    int q; cin >> q;
    BLOCK_SIZE = static_cast<int>(sqrt(n));
    for(int i = 0; i < n; i++) cin >> arr[i];
    vl res(q);
    vector<query> QS;
    for(int i = 0; i < q; i++){
        int l,r; cin >> l >> r;
        --l ; --r;
        QS.emplace_back(l,r,i);
    }
    sort(all(QS));
    int left = 0;
    int right = -1;
    for(auto [l,r,id] : QS){
        while(left > l)  add(--left);
        while(right < r) add(++right);
        while(left < l)  remove(left++);
        while(right > r) remove(right--);
        res[id] = ans;
    }
}
```

PersistentSegTree.h

Description: Persistent Segment Tree for range sum. Remember to save the roots when needed.
Time: $\mathcal{O}\left(\log N\right)$
f648d9, 57 lines

```
class PersistentSegtree {
private:
  struct Node {ll sum = 0; int l = 0, r = 0;};
  const int n;
  vector<Node> tree;
  int timer = 1;

  Node join(int l, int r) { return Node{tree[l].sum + tree[r].
      sum, l, r}; }

  int build(int tl, int tr, const vector<int> &arr) {
    if (tl == tr) {
      tree[timer] = {arr[tl], 0, 0};
      return timer++;
    }

    int mid = (tl + tr) / 2;
    tree[timer] = join(build(tl, mid, arr), build(mid + 1, tr,
        arr));

    return timer++;
  }

  int set(int v, int pos, int val, int tl, int tr) {
    if (tl == tr) {
      tree[timer] = {val, 0, 0};
      return timer++;
    }

    int mid = (tl + tr) / 2;
    if (pos <= mid) {
      tree[timer] = join(set(tree[v].l, pos, val, tl, mid),
          tree[v].r);
    } else {
      tree[timer] = join(tree[v].l, set(tree[v].r, pos, val,
          mid + 1, tr));
    }

    return timer++;
  }

  ll range_sum(int v, int ql, int qr, int tl, int tr) {
    if (qr < tl || tr < ql) { return 0ll; }
    if (ql <= tl && tr <= qr) { return tree[v].sum; }

    int mid = (tl + tr) / 2;
    return range_sum(tree[v].l, ql, qr, tl, mid) +
           range_sum(tree[v].r, ql, qr, mid + 1, tr);
  }

public:
    // MX_NODES = 2 * n + q * (3 + __lg(n));
  PersistentSegtree(int n, int MX_NODES) : n(n), tree(MX_NODES)
      {}
  int build(const vector<int> &arr) { return build(0, n - 1,
      arr); }
  int set(int root, int pos, int val) { return set(root, pos,
      val, 0, n - 1); }
  ll range_sum(int root, int l, int r) { return range_sum(root,
      l, r, 0, n - 1); }
  int add_copy(int root) {
    tree[timer] = tree[root];
    return timer++;
  }
};
```

LiChaoTree.h

Description: Container (seg tree like) where you can add lines of the form kx+m, and query maximum values at points x.
Time: $\mathcal{O}\left(\log N\right)$
0202b5, 51 lines

```
struct line {
    ll a, b;
    line(ll a = 0, ll b = 0) : a(a), b(b) { }
    ll eval(ll x) { return  1LL * a * x + b ; }
};
const ll inf = 1LL << 62;
struct LiChao {
    struct node {
        node *l, *r;
        line f;
        node(ll a = 0, ll b = 0) : f(a, b), l(0), r(0) { }
        node(line v) { f = v; l = r = 0; }
    };
    node *root;
    int siz;
```

```
    void init(int siz_) { siz = siz_; root = 0; }

    void insert(node* &nd, line& v, int l, int r) {
        if(!nd) {
            nd = new node(v);
            return;
        }
        ll tl = nd -> f.eval(l), tr = nd -> f.eval(r);
        ll vl = v.eval(l), vr = v.eval(r);
        if(tl >= vl && tr >= vr) return;
        if(tl < vl && tr < vr) {
            nd -> f = v;
            return;
        }
        ll mi = l + (r - l) / 2;
        if(tl < vl) swap(nd -> f, v);
        if(nd -> f.eval(mi) > v.eval(mi)) insert(nd -> r, v, mi
             + 1, r);
        else {
            swap(nd -> f, v);
            insert(nd -> l, v, l, mi);
        }
    }
    void add_line(ll a, ll b) {
        line v(a, b);
        insert(root, v, -siz, siz);
    }

    ll query(ll x, int l, int r, node* &nd) {
        if(!nd) return -inf;
        if(l == r) return nd -> f.eval(x);

        int m = l + (r - l) / 2 ;
        if(m >= x) return max(nd -> f.eval(x), query(x, l, m,
             nd -> l));
        return max(nd -> f.eval(x), query(x, m + 1, r, nd -> r)
             );
    }
};
```

PersistentLCT.h

Description: Pretty similar to a Persistent segtree
Time: $\mathcal{O}(\log N)$

e190e8, 60 lines

```
struct line {
    ll a, b;
    line(ll a = 0, ll b = 0) : a(a), b(b) { }
    ll eval(ll x) { return  1LL * a * x + b ; }
};
const ll inf = 1LL << 62;
struct PersistentLiChao {
    struct node {
        node *l, *r;
        line f;
        node(ll a = 0, ll b = 0) : f(a, b), l(0), r(0) { }
        node(line v) { f = v; l = r = 0; }
    };
    int siz;
    PersistentLiChao(int siz_) { siz = siz_; }
    node *clone(node *t) {
        return new node(*t);
    }
    node* insert(node* nd, line v, int l, int r) {
        if(!nd) {
            return new node(v);
        }
        ll tl = nd -> f.eval(l), tr = nd -> f.eval(r);
        ll vl = v.eval(l), vr = v.eval(r);
        if(tl >= vl && tr >= vr) return nd;

        // modify the node
        node *cur = clone(nd);
        if(tl < vl && tr < vr) {
            cur -> f = v;
            return cur;
        }
        ll mi = l + (r - l) / 2;
        if(tl < vl) swap(cur -> f, v);
        if(cur -> f.eval(mi) > v.eval(mi)) {
            cur -> r = insert(cur -> r, v, mi + 1, r);
        } else {
            swap(cur -> f, v);
            cur -> l = insert(cur -> l, v, l, mi);
        }
        return cur;
    }

    node* add_line(node* root, ll a, ll b) {
        line v(a, b);
        return insert(root, v, -siz, siz);
    }

    ll query(node *nd, ll x, int l, int r) {
        if(!nd) return -inf;
        if(l == r) return nd -> f.eval(x);

        int mid = l + (r - l) / 2 ;
        if(mid >= x) return max(nd -> f.eval(x), query(nd -> l,
             x, l, mid));
        return max(nd -> f.eval(x), query(nd -> r, x, mid + 1,
             r));
    }
    ll query(node *nd, ll x) {
        return query(nd, x, -siz, siz);
    }
};
```

DisjointSparseTable.h

Description: Common sparse table, allows non-idempotent ops (0-based)
Time: $\mathcal{O}(NlogN)$ $\mathcal{O}(1)$ per query

96a8de, 30 lines

```
struct node {
    // something, overload +op, constructor...
};

struct DisjointST {
    vector<node> dp[32];

    DisjointST() {}
    DisjointST(vector<int> &arr){
        int i, c, h, l, n = (int)arr.size();
        vector<node> a(n);
        for (int i = 0; i < n; i++) a[i] = node(arr[i]);
        for (h = 0; h <= __lg(n); h++){
            dp[h].resize(n + 1);
            for (c = l = 1 << h; c < n + 1; c += (l << 1)){
                for (i = c + 1; i <= min(n, c + l); i++){
                    dp[h][i] = dp[h][i - 1] + a[i - 1];
                }
                for (i = min(n, c) - 1; i >= c - l; i--){
                    dp[h][i] = a[i] + dp[h][i + 1];
                }
            }
        }
    }

    node query(int l, int r){ // [l, r]
        int h = __lg(l ^ (r + 1));
        return dp[h][l] + dp[h][r + 1];
    }
};
```

PersistentTreap.h

Description: Treap, but persistent jejej
Time: $\mathcal{O}(logn)$

13ddb3, 61 lines

```
struct Node {
  int L, R;
  int sz;
  int x;

  Node() : L(-1), R(-1), sz(1), x() {}
};
const int SZ = (int)2e7 + 3;
Node tree[SZ];
int treeSz;

int getSize(int v) { return v == -1 ? 0 : tree[v].sz; }
int update(int v) {
  tree[v].sz = 1 + getSize(tree[v].L) + getSize(tree[v].R);
  return v;
}
int copy(int v) {
  if (v == -1) return -1;
  int u = treeSz++;
  tree[u] = tree[v];
  return u;
}
int newVertex(int x) {
  int v = treeSz++;
  tree[v].x = x;
  return v;
}
mt19937_64 rng(chrono::steady_clock::now().time_since_epoch().
    count());
ll myRand(ll B) {
  return (ull)rng() % B;
}
int merge(int L, int R) {
  if (L == -1) return R;
  if (R == -1) return L;
  int lSz = tree[L].sz, rSz = tree[R].sz;
  if (myRand(lSz + rSz) < lSz) {
    int v = copy(L);
    tree[v].R = merge(tree[v].R, R);
    return update(v);
  } else {
    int v = copy(R);
    tree[v].L = merge(L, tree[v].L);
    return update(v);
  }
}
void split(int v, int k, int &L, int &R) {
  if (v == -1) {
    L = R = -1;
    return;
  }
  int lSz = getSize(tree[v].L);
  if (k <= lSz) {
    int u = copy(v);
    split(tree[u].L, k, L, tree[u].L);
    R = update(u);
  } else {
    int u = copy(v);
    split(tree[u].R, k - lSz - 1, tree[u].R, R);
    L = update(u);
  }
```

```
}
```

Numerical (4)

4.1 Polynomials and recurrences

Polynomial.h

c9b7b0, 17 lines

```
struct Poly {
  vector<double> a;
  double operator()(double x) const {
    double val = 0;
    for (int i = sz(a); i--;) (val *= x) += a[i];
    return val;
  }
  void diff() {
    rep(i,1,sz(a)) a[i-1] = i*a[i];
    a.pop_back();
  }
  void divroot(double x0) {
    double b = a.back(), c; a.back() = 0;
    for(int i=sz(a)-1; i--;) c = a[i], a[i] = a[i+1]*x0+b, b=c;
    a.pop_back();
  }
};
```

PolyRoots.h

Description: Finds the real roots to a polynomial.
Usage: `polyRoots({{2,-3,1}},-1e9,1e9) // solve x^2-3x+2 = 0`
Time: $\mathcal{O}\left(n^2 \log(1/\epsilon)\right)$

"Polynomial.h" b00bfe, 23 lines

```
vector<double> polyRoots(Poly p, double xmin, double xmax) {
  if (sz(p.a) == 2) { return {-p.a[0]/p.a[1]}; }
  vector<double> ret;
  Poly der = p;
  der.diff();
  auto dr = polyRoots(der, xmin, xmax);
  dr.push_back(xmin-1);
  dr.push_back(xmax+1);
  sort(all(dr));
  rep(i,0,sz(dr)-1) {
    double l = dr[i], h = dr[i+1];
    bool sign = p(l) > 0;
    if (sign ^ (p(h) > 0)) {
      rep(it,0,60) { // while (h - l > 1e-8)
        double m = (l + h) / 2, f = p(m);
        if ((f <= 0) ^ sign) l = m;
        else h = m;
      }
      ret.push_back((l + h) / 2);
    }
  }
  return ret;
}
```

PolyInterpolate.h

Description: Given n points (x[i], y[i]), computes an n-1-degree polynomial p that passes through them: $p(x) = a[0] * x^0 + ... + a[n-1] * x^{n-1}$. For numerical precision, pick $x[k] = c * \cos(k/(n-1) * \pi), k = 0 \dots n-1$.
Time: $\mathcal{O}\left(n^2\right)$

08bf48, 13 lines

```
typedef vector<double> vd;
vd interpolate(vd x, vd y, int n) {
  vd res(n), temp(n);
  rep(k,0,n-1) rep(i,k+1,n)
    y[i] = (y[i] - y[k]) / (x[i] - x[k]);
  double last = 0; temp[0] = 1;
  rep(k,0,n) rep(i,0,n) {
    res[i] += y[k] * temp[i];
    swap(last, temp[i]);
    temp[i] -= last * x[k];
  }
  return res;
}
```

BerlekampMassey.h

Description: Recovers any n-order linear recurrence relation from the first $2n$ terms of the recurrence. Useful for guessing linear recurrences after brute-forcing the first terms. Should work on any field, but numerical stability for floats is not guaranteed. Output will have size $\leq n$.
Usage: `berlekampMassey({0, 1, 1, 3, 5, 11}) // {1, 2}`
Time: $\mathcal{O}\left(N^2\right)$

"../number-theory/ModPow.h" 96548b, 20 lines

```
vector<ll> berlekampMassey(vector<ll> s) {
  int n = sz(s), L = 0, m = 0;
  vector<ll> C(n), B(n), T;
  C[0] = B[0] = 1;

  ll b = 1;
  rep(i,0,n) { ++m;
    ll d = s[i] % mod;
    rep(j,1,L+1) d = (d + C[j] * s[i - j]) % mod;
    if (!d) continue;
    T = C; ll coef = d * modpow(b, mod-2) % mod;
    rep(j,m,n) C[j] = (C[j] - coef * B[j - m]) % mod;
    if (2 * L > i) continue;
    L = i + 1 - L; B = T; b = d; m = 0;
  }

  C.resize(L + 1); C.erase(C.begin());
  for (ll& x : C) x = (mod - x) % mod;
  return C;
}
```

LinearRecurrence.h

Description: Generates the k'th term of an n-order linear recurrence $S[i] = \sum_j S[i-j-1]tr[j]$, given $S[0 \dots \geq n-1]$ and $tr[0 \dots n-1]$. Faster than matrix multiplication. Useful together with Berlekamp–Massey.
Usage: `linearRec({0, 1}, {1, 1}, k) // k'th Fibonacci number`
Time: $\mathcal{O}\left(n^2 \log k\right)$

f4e444, 26 lines

```
typedef vector<ll> Poly;
ll linearRec(Poly S, Poly tr, ll k) {
  int n = sz(tr);

  auto combine = [&](Poly a, Poly b) {
    Poly res(n * 2 + 1);
    rep(i,0,n+1) rep(j,0,n+1)
      res[i + j] = (res[i + j] + a[i] * b[j]) % mod;
    for (int i = 2 * n; i > n; --i) rep(j,0,n)
      res[i - 1 - j] = (res[i - 1 - j] + res[i] * tr[j]) % mod;
    res.resize(n + 1);
    return res;
  };

  Poly pol(n + 1), e(pol);
  pol[0] = e[1] = 1;

  for (++k; k; k /= 2) {
    if (k % 2) pol = combine(pol, e);
    e = combine(e, e);
  }

  ll res = 0;
  rep(i,0,n) res = (res + pol[i + 1] * S[i]) % mod;
  return res;
}
```

GaussianElimination.h

Description: Gaussian elimination. Returns -1 if there aren't solutions, 1 if the solution is unique, 2 if there's infinite solutinos.
Time: $\mathcal{O}\left(N^3\right)$

09f2c8, 33 lines

```
const double eps = 1e-9;
int Gauss(vector<vector<double>> a, vector<double> &ans) {
  int n = (int)a.size(), m = (int)a[0].size() - 1;
  vector<int> pos(m, -1);
  double det = 1; int rank = 0;
  for(int col = 0, row = 0; col < m && row < n; ++col) {
    int mx = row;
    for(int i = row; i < n; i++) if(fabs(a[i][col]) > fabs(a[mx
        ][col])) mx = i;
    if(fabs(a[mx][col]) < eps) {det = 0; continue;}
    for(int i = col; i <= m; i++) swap(a[row][i], a[mx][i]);
    if (row != mx) det = -det;
    det *= a[row][col];
    pos[col] = row;
    for(int i = 0; i < n; i++) {
      if(i != row && fabs(a[i][col]) > eps) {
        double c = a[i][col] / a[row][col];
        for(int j = col; j <= m; j++) a[i][j] -= a[row][j] * c;
      }
    }
    ++row; ++rank;
  }
  ans.assign(m, 0);
  for(int i = 0; i < m; i++) {
    if(pos[i] != -1) ans[i] = a[pos[i]][m] / a[pos[i]][i];
  }
  for(int i = 0; i < n; i++) {
    double sum = 0;
    for(int j = 0; j < m; j++) sum += ans[j] * a[i][j];
    if(fabs(sum - a[i][m]) > eps) return -1; //no solution
  }
  for(int i = 0; i < m; i++) if(pos[i] == -1) return 2; //
      infinte solutions
  return 1; //unique solution
}
```

GaussMod2.h

Description: Gaussian elimination mod 2. Returns -1 if there aren't solutions. Returns number of free variables otherwise. n = number of equations, m = number of variables
Time: $\mathcal{O}\left((N^3)/64\right)$

3800dc, 33 lines

```
const int N = 100 + 6;
int Gauss(int n, int m, vector<bitset<N>> a, bitset<N> &ans) {
    int rank = 0, det = 1;
    vi pos(N, -1);
    for(int col = 0, row = 0; col < m && row < n; ++col) {
        int mx = row;
        rep(i,row,n) if(a[i][col]) { mx = i; break; }
        if(!a[mx][col]) { det = 0; continue; }
        swap(a[mx], a[row]);
        if(row != mx) det = det == 0 ? 0 : 1;
        det &= a[row][col];
        pos[col] = row;
        //forward elimination
        rep(i,row+1,n) if (a[i][col]) a[i] ^= a[row];
        ++row, ++rank;
    }
    ans.reset();
    //backward substituition
    for (int i = m - 1; i >= 0; i--) {
        if (pos[i] == -1) ans[i] = true;
```

```
        else {
            int k = pos[i];
            rep(j,i+1,m) if (a[k][j]) ans[i] = ans[i] ^ ans[j];
            ans[i] = ans[i] ^ a[k][m];
        }
    }

    rep(i,rank,n) if(a[i][m]) return -1; //no solution

    int free_var = 0;
    rep(i,0,m) if(pos[i] == -1) free_var++;
    return free_var; //has solution
}
```

4.2 Optimization

GoldenSectionSearch.h

Description: Finds the argument minimizing the function f in the interval $[a,b]$ assuming f is unimodal on the interval, i.e. has only one local minimum and no local maximum. The maximum error in the result is *eps*. Works equally well for maximization with a small change in the code. See TernarySearch.h in the Various chapter for a discrete version.
Usage: `double func(double x) { return 4+x+.3*x*x; }`
`double xmin = gss(-1000,1000,func);`
Time: $\mathcal{O}\left(\log((b-a)/\epsilon)\right)$

31d45b, 14 lines

```
double gss(double a, double b, double (*f)(double)) {
  double r = (sqrt(5)-1)/2, eps = 1e-7;
  double x1 = b - r*(b-a), x2 = a + r*(b-a);
  double f1 = f(x1), f2 = f(x2);
  while (b-a > eps)
    if (f1 < f2) { //change to > to find maximum
      b = x2; x2 = x1; f2 = f1;
      x1 = b - r*(b-a); f1 = f(x1);
    } else {
      a = x1; x1 = x2; f1 = f2;
      x2 = a + r*(b-a); f2 = f(x2);
    }
  return a;
}
```

HillClimbing.h

Description: Poor man's optimization for unimodal functions

8eeeaf, 14 lines

```
typedef array<double, 2> P;

template<class F> pair<double, P> hillClimb(P start, F f) {
  pair<double, P> cur(f(start), start);
  for (double jmp = 1e9; jmp > 1e-20; jmp /= 2) {
    rep(j,0,100) rep(dx,-1,2) rep(dy,-1,2) {
      P p = cur.second;
      p[0] += dx*jmp;
      p[1] += dy*jmp;
      cur = min(cur, make_pair(f(p), p));
    }
  }
  return cur;
}
```

Integrate.h

Description: Simple integration of a function over an interval using Simpson's rule. The error should be proportional to h^4, although in practice you will want to verify that the result is stable to desired precision when epsilon changes.

4756fc, 7 lines

```
template<class F>
double quad(double a, double b, F f, const int n = 1000) {
  double h = (b - a) / 2 / n, v = f(a) + f(b);
  rep(i,1,n*2)
    v += f(a + i*h) * (i&1 ? 4 : 2);
  return v * h / 3;
}
```

IntegrateAdaptive.h

Description: Fast integration using an adaptive Simpson's rule.
Usage: `double sphereVolume = quad(-1, 1, [](double x) {`
`return quad(-1, 1, [&](double y) {`
`return quad(-1, 1, [&](double z) {`
`return x*x + y*y + z*z < 1; });});});`

92dd79, 15 lines

```
typedef double d;
#define S(a,b) (f(a) + 4*f((a+b) / 2) + f(b)) * (b-a) / 6

template <class F>
d rec(F& f, d a, d b, d eps, d S) {
  d c = (a + b) / 2;
  d S1 = S(a, c), S2 = S(c, b), T = S1 + S2;
  if (abs(T - S) <= 15 * eps || b - a < 1e-10)
    return T + (T - S) / 15;
  return rec(f, a, c, eps / 2, S1) + rec(f, c, b, eps / 2, S2);
}
template<class F>
d quad(d a, d b, F f, d eps = 1e-8) {
  return rec(f, a, b, eps, S(a, b));
}
```

Simplex.h

Description: Solves a general linear maximization problem: maximize $c^T x$ subject to $Ax \leq b$, $x \geq 0$. Returns -inf if there is no solution, inf if there are arbitrarily good solutions, or the maximum value of $c^T x$ otherwise. The input vector is set to an optimal x (or in the unbounded case, an arbitrary solution fulfilling the constraints). Numerical stability is not guaranteed. For better performance, define variables such that $x = 0$ is viable.
Usage: `vvd A = {{1,-1}, {-1,1}, {-1,-2}};`
`vd b = {1,1,-4}, c = {-1,-1}, x;`
`T val = LPSolver(A, b, c).solve(x);`
Time: $\mathcal{O}\left(NM * \#pivots\right)$, where a pivot may be e.g. an edge relaxation. $\mathcal{O}\left(2^n\right)$ in the general case.

aa8530, 68 lines

```
typedef double T; // long double, Rational, double + mod<P>...
typedef vector<T> vd;
typedef vector<vd> vvd;

const T eps = 1e-8, inf = 1/.0;
#define MP make_pair
#define ltj(X) if(s == -1 || MP(X[j],N[j]) < MP(X[s],N[s])) s=j

struct LPSolver {
  int m, n;
  vi N, B;
  vvd D;

  LPSolver(const vvd& A, const vd& b, const vd& c) :
    m(sz(b)), n(sz(c)), N(n+1), B(m), D(m+2, vd(n+2)) {
      rep(i,0,m) rep(j,0,n) D[i][j] = A[i][j];
      rep(i,0,m) { B[i] = n+i; D[i][n] = -1; D[i][n+1] = b[i];}
      rep(j,0,n) { N[j] = j; D[m][j] = -c[j]; }
      N[n] = -1; D[m+1][n] = 1;
    }

  void pivot(int r, int s) {
    T *a = D[r].data(), inv = 1 / a[s];
    rep(i,0,m+2) if (i != r && abs(D[i][s]) > eps) {
      T *b = D[i].data(), inv2 = b[s] * inv;
      rep(j,0,n+2) b[j] -= a[j] * inv2;
      b[s] = a[s] * inv2;
    }
    rep(j,0,n+2) if (j != s) D[r][j] *= inv;
    rep(i,0,m+2) if (i != r) D[i][s] *= -inv;
    D[r][s] = inv;
    swap(B[r], N[s]);
  }

  bool simplex(int phase) {
    int x = m + phase - 1;
    for (;;) {
      int s = -1;
      rep(j,0,n+1) if (N[j] != -phase) ltj(D[x]);
      if (D[x][s] >= -eps) return true;
      int r = -1;
      rep(i,0,m) {
        if (D[i][s] <= eps) continue;
        if (r == -1 || MP(D[i][n+1] / D[i][s], B[i])
                     < MP(D[r][n+1] / D[r][s], B[r])) r = i;
      }
      if (r == -1) return false;
      pivot(r, s);
    }
  }

  T solve(vd &x) {
    int r = 0;
    rep(i,1,m) if (D[i][n+1] < D[r][n+1]) r = i;
    if (D[r][n+1] < -eps) {
      pivot(r, n);
      if (!simplex(2) || D[m+1][n+1] < -eps) return -inf;
      rep(i,0,m) if (B[i] == -1) {
        int s = 0;
        rep(j,1,n+1) ltj(D[i]);
        pivot(i, s);
      }
    }
    bool ok = simplex(1); x = vd(n);
    rep(i,0,m) if (B[i] < n) x[B[i]] = D[i][n+1];
    return ok ? D[m][n+1] : inf;
  }
};
```

4.3 Matrices

Determinant.h

Description: Calculates determinant of a matrix. Destroys the matrix.
Time: $\mathcal{O}\left(N^3\right)$

bd5cec, 15 lines

```
double det(vector<vector<double>>& a) {
  int n = sz(a); double res = 1;
  rep(i,0,n) {
    int b = i;
    rep(j,i+1,n) if (fabs(a[j][i]) > fabs(a[b][i])) b = j;
    if (i != b) swap(a[i], a[b]), res *= -1;
    res *= a[i][i];
    if (res == 0) return 0;
    rep(j,i+1,n) {
      double v = a[j][i] / a[i][i];
      if (v != 0) rep(k,i+1,n) a[j][k] -= v * a[i][k];
    }
  }
  return res;
}
```

IntDeterminant.h

Description: Calculates determinant using modular arithmetics. Modulos can also be removed to get a pure-integer version.
Time: $\mathcal{O}\left(N^3\right)$

3313dc, 18 lines

```
const ll mod = 12345;
ll det(vector<vector<ll>>& a) {
  int n = sz(a); ll ans = 1;
  rep(i,0,n) {
```

```
    rep(j,i+1,n) {
      while (a[j][i] != 0) { // gcd step
        ll t = a[i][i] / a[j][i];
        if (t) rep(k,i,n)
          a[i][k] = (a[i][k] - a[j][k] * t) % mod;
        swap(a[i], a[j]);
        ans *= -1;
      }
    }
    ans = ans * a[i][i] % mod;
    if (!ans) return 0;
  }
  return (ans + mod) % mod;
}
```

SolveLinear.h

Description: Solves $A * x = b$. If there are multiple solutions, an arbitrary one is returned. Returns rank, or -1 if no solutions. Data in A and b is lost.
Time: $\mathcal{O}\left(n^2m\right)$ 44c9ab, 38 lines

```
typedef vector<double> vd;
const double eps = 1e-12;

int solveLinear(vector<vd>& A, vd& b, vd& x) {
  int n = sz(A), m = sz(x), rank = 0, br, bc;
  if (n) assert(sz(A[0]) == m);
  vi col(m); iota(all(col), 0);

  rep(i,0,n) {
    double v, bv = 0;
    rep(r,i,n) rep(c,i,m)
      if ((v = fabs(A[r][c])) > bv)
        br = r, bc = c, bv = v;
    if (bv <= eps) {
      rep(j,i,n) if (fabs(b[j]) > eps) return -1;
      break;
    }
    swap(A[i], A[br]);
    swap(b[i], b[br]);
    swap(col[i], col[bc]);
    rep(j,0,n) swap(A[j][i], A[j][bc]);
    bv = 1/A[i][i];
    rep(j,i+1,n) {
      double fac = A[j][i] * bv;
      b[j] -= fac * b[i];
      rep(k,i+1,m) A[j][k] -= fac*A[i][k];
    }
    rank++;
  }

  x.assign(m, 0);
  for (int i = rank; i--;) {
    b[i] /= A[i][i];
    x[col[i]] = b[i];
    rep(j,0,i) b[j] -= A[j][i] * b[i];
  }
  return rank; // (multiple solutions if rank < m)
}
```

SolveLinear2.h

Description: To get all uniquely determined values of x back from SolveLinear, make the following changes:
"SolveLinear.h" 08e495, 7 lines

```
rep(j,0,n) if (j != i) // instead of rep(j,i+1,n)
// ... then at the end:
x.assign(m, undefined);
rep(i,0,rank) {
  rep(j,rank,m) if (fabs(A[i][j]) > eps) goto fail;
  x[col[i]] = b[i] / A[i][i];
fail:; }
```

SolveLinearBinary.h

Description: Solves $Ax = b$ over $\mathbb{F}_2$. If there are multiple solutions, one is returned arbitrarily. Returns rank, or -1 if no solutions. Destroys A and b.
Time: $\mathcal{O}\left(n^2m\right)$ fa2d7a, 34 lines

```
typedef bitset<1000> bs;

int solveLinear(vector<bs>& A, vi& b, bs& x, int m) {
  int n = sz(A), rank = 0, br;
  assert(m <= sz(x));
  vi col(m); iota(all(col), 0);
  rep(i,0,n) {
    for (br=i; br<n; ++br) if (A[br].any()) break;
    if (br == n) {
      rep(j,i,n) if(b[j]) return -1;
      break;
    }
    int bc = (int)A[br]._Find_next(i-1);
    swap(A[i], A[br]);
    swap(b[i], b[br]);
    swap(col[i], col[bc]);
    rep(j,0,n) if (A[j][i] != A[j][bc]) {
      A[j].flip(i); A[j].flip(bc);
    }
    rep(j,i+1,n) if (A[j][i]) {
      b[j] ^= b[i];
      A[j] ^= A[i];
    }
    rank++;
  }

  x = bs();
  for (int i = rank; i--;) {
    if (!b[i]) continue;
    x[col[i]] = 1;
    rep(j,0,i) b[j] ^= A[j][i];
  }
  return rank; // (multiple solutions if rank < m)
}
```

MatrixInverse.h

Description: Invert matrix A. Returns rank; result is stored in A unless singular (rank < n). Can easily be extended to prime moduli; for prime powers, repeatedly set $A^{-1} = A^{-1}(2I - AA^{-1})$ (mod p^k) where A^{-1} starts as the inverse of A mod p, and k is doubled in each step.
Time: $\mathcal{O}\left(n^3\right)$ ebfff6, 35 lines

```
int matInv(vector<vector<double>>& A) {
  int n = sz(A); vi col(n);
  vector<vector<double>> tmp(n, vector<double>(n));
  rep(i,0,n) tmp[i][i] = 1, col[i] = i;

  rep(i,0,n) {
    int r = i, c = i;
    rep(j,i,n) rep(k,i,n)
      if (fabs(A[j][k]) > fabs(A[r][c]))
        r = j, c = k;
    if (fabs(A[r][c]) < 1e-12) return i;
    A[i].swap(A[r]); tmp[i].swap(tmp[r]);
    rep(j,0,n)
      swap(A[j][i], A[j][c]), swap(tmp[j][i], tmp[j][c]);
    swap(col[i], col[c]);
    double v = A[i][i];
    rep(j,i+1,n) {
      double f = A[j][i] / v;
      A[j][i] = 0;
      rep(k,i+1,n) A[j][k] -= f*A[i][k];
      rep(k,0,n) tmp[j][k] -= f*tmp[i][k];
    }
    rep(j,i+1,n) A[i][j] /= v;
    rep(j,0,n) tmp[i][j] /= v;
    A[i][i] = 1;
  }

  for (int i = n-1; i > 0; --i) rep(j,0,i) {
    double v = A[j][i];
    rep(k,0,n) tmp[j][k] -= v*tmp[i][k];
  }

  rep(i,0,n) rep(j,0,n) A[col[i]][col[j]] = tmp[i][j];
  return n;
}
```

Tridiagonal.h

Description: $x = \text{tridiagonal}(d, p, q, b)$ solves the equation system

$$\begin{pmatrix} b_0 \\ b_1 \\ b_2 \\ b_3 \\ \vdots \\ b_{n-1} \end{pmatrix} = \begin{pmatrix} d_0 & p_0 & 0 & 0 & \cdots & 0 \\ q_0 & d_1 & p_1 & 0 & \cdots & 0 \\ 0 & q_1 & d_2 & p_2 & \cdots & 0 \\ \vdots & \vdots & \ddots & \ddots & \ddots & \vdots \\ 0 & 0 & \cdots & q_{n-3} & d_{n-2} & p_{n-2} \\ 0 & 0 & \cdots & 0 & q_{n-2} & d_{n-1} \end{pmatrix} \begin{pmatrix} x_0 \\ x_1 \\ x_2 \\ x_3 \\ \vdots \\ x_{n-1} \end{pmatrix}.$$

This is useful for solving problems on the type

$$a_i = b_i a_{i-1} + c_i a_{i+1} + d_i,\ 1 \le i \le n,$$

where a_0, a_{n+1}, b_i, c_i and d_i are known. a can then be obtained from

$$\{a_i\} = \text{tridiagonal}(\{1, -1, -1, ..., -1, 1\}, \{0, c_1, c_2, \ldots, c_n\}, \{b_1, b_2, \ldots, b_n, 0\}, \{a_0, d_1, d_2, \ldots, d_n, a_{n+1}\}).$$

Fails if the solution is not unique.
If $|d_i| > |p_i| + |q_{i-1}|$ for all i, or $|d_i| > |p_{i-1}| + |q_i|$, or the matrix is positive definite, the algorithm is numerically stable and neither `tr` nor the check for `diag[i] == 0` is needed.
Time: $\mathcal{O}\left(N\right)$ 8f9fa8, 26 lines

```
typedef double T;
vector<T> tridiagonal(vector<T> diag, const vector<T>& super,
    const vector<T>& sub, vector<T> b) {
  int n = sz(b); vi tr(n);
  rep(i,0,n-1) {
    if (abs(diag[i]) < 1e-9 * abs(super[i])) { // diag[i] == 0
      b[i+1] -= b[i] * diag[i+1] / super[i];
      if (i+2 < n) b[i+2] -= b[i] * sub[i+1] / super[i];
      diag[i+1] = sub[i]; tr[++i] = 1;
    } else {
      diag[i+1] -= super[i]*sub[i]/diag[i];
      b[i+1] -= b[i]*sub[i]/diag[i];
    }
  }
  for (int i = n; i--;) {
    if (tr[i]) {
      swap(b[i], b[i-1]);
      diag[i-1] = diag[i];
      b[i] /= super[i-1];
    } else {
      b[i] /= diag[i];
      if (i) b[i-1] -= b[i]*super[i-1];
    }
  }
  return b;
}
```

4.4 Fourier transforms

FastFourierTransform.h

Description: fft(a) computes $\hat{f}(k) = \sum_x a[x] \exp(2\pi i \cdot kx/N)$ for all k. N must be a power of 2. Useful for convolution: conv(a, b) = c, where $c[x] = \sum a[i]b[x-i]$. For convolution of complex numbers or more than two vectors: FFT, multiply pointwise, divide by n, reverse(start+1, end), FFT back. Rounding is safe if $(\sum a_i^2 + \sum b_i^2) \log_2 N < 9 \cdot 10^{14}$ (in practice 10^{16}; higher for random inputs). Otherwise, use NTT/FFTMod.
Time: $\mathcal{O}(N \log N)$ with $N = |A| + |B|$ ($\sim$1s for $N = 2^{22}$)

00ced6, 35 lines

```
typedef complex<double> C;
typedef vector<double> vd;
void fft(vector<C>& a) {
  int n = sz(a), L = 31 - __builtin_clz(n);
  static vector<complex<long double>> R(2, 1);
  static vector<C> rt(2, 1);  // (^ 10% faster if double)
  for (static int k = 2; k < n; k *= 2) {
    R.resize(n); rt.resize(n);
    auto x = polar(1.0L, acos(-1.0L) / k);
    rep(i,k,2*k) rt[i] = R[i] = i&1 ? R[i/2] * x : R[i/2];
  }
  vi rev(n);
  rep(i,0,n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
  rep(i,0,n) if (i < rev[i]) swap(a[i], a[rev[i]]);
  for (int k = 1; k < n; k *= 2)
    for (int i = 0; i < n; i += 2 * k) rep(j,0,k) {
      C z = rt[j+k] * a[i+j+k]; // (25% faster if hand-rolled)
      a[i + j + k] = a[i + j] - z;
      a[i + j] += z;
    }
}
vd conv(const vd& a, const vd& b) {
  if (a.empty() || b.empty()) return {};
  vd res(sz(a) + sz(b) - 1);
  int L = 32 - __builtin_clz(sz(res)), n = 1 << L;
  vector<C> in(n), out(n);
  copy(all(a), begin(in));
  rep(i,0,sz(b)) in[i].imag(b[i]);
  fft(in);
  for (C& x : in) x *= x;
  rep(i,0,n) out[i] = in[-i & (n - 1)] - conj(in[i]);
  fft(out);
  rep(i,0,sz(res)) res[i] = imag(out[i]) / (4 * n);
  return res;
}
```

FastFourierTransformMod.h

Description: Higher precision FFT, can be used for convolutions modulo arbitrary integers as long as $N \log_2 N \cdot \text{mod} < 8.6 \cdot 10^{14}$ (in practice 10^{16} or higher). Inputs must be in $[0, \text{mod})$.
Time: $\mathcal{O}(N \log N)$, where $N = |A| + |B|$ (twice as slow as NTT or FFT)

"FastFourierTransform.h" b82773, 22 lines

```
typedef vector<ll> vl;
template<int M> vl convMod(const vl &a, const vl &b) {
  if (a.empty() || b.empty()) return {};
  vl res(sz(a) + sz(b) - 1);
  int B=32-__builtin_clz(sz(res)), n=1<<B, cut=int(sqrt(M));
  vector<C> L(n), R(n), outs(n), outl(n);
  rep(i,0,sz(a)) L[i] = C((int)a[i] / cut, (int)a[i] % cut);
  rep(i,0,sz(b)) R[i] = C((int)b[i] / cut, (int)b[i] % cut);
  fft(L), fft(R);
  rep(i,0,n) {
    int j = -i & (n - 1);
    outl[j] = (L[i] + conj(L[j])) * R[i] / (2.0 * n);
    outs[j] = (L[i] - conj(L[j])) * R[i] / (2.0 * n) / 1i;
  }
  fft(outl), fft(outs);
  rep(i,0,sz(res)) {
    ll av = ll(real(outl[i])+.5), cv = ll(imag(outs[i])+.5);
    ll bv = ll(imag(outl[i])+.5) + ll(real(outs[i])+.5);
    res[i] = ((av % M * cut + bv) % M * cut + cv) % M;
  }
  return res;
}
```

NumberTheoreticTransform.h

Description: ntt(a) computes $\hat{f}(k) = \sum_x a[x] g^{xk}$ for all k, where $g = \text{root}^{(mod-1)/N}$. N must be a power of 2. Useful for convolution modulo specific nice primes of the form $2^a b + 1$, where the convolution result has size at most 2^a. For arbitrary modulo, see FFTMod. conv(a, b) = c, where $c[x] = \sum a[i]b[x-i]$. For manual convolution: NTT the inputs, multiply pointwise, divide by n, reverse(start+1, end), NTT back. Inputs must be in $[0, \text{mod})$.
Time: $\mathcal{O}(N \log N)$

"../number-theory/ModPow.h" d54056, 35 lines

```
const ll mod = (119 << 23) + 1, root = 62; // = 998244353
// For p < 2^30 there is also e.g. 5 << 25, 7 << 26, 479 << 21
// and 483 << 21 (same root). The last two are > 10^9.
typedef vector<ll> vl;
void ntt(vl &a) {
  int n = sz(a), L = 31 - __builtin_clz(n);
  static vl rt(2, 1);
  for (static int k = 2, s = 2; k < n; k *= 2, s++) {
    rt.resize(n);
    ll z[] = {1, modpow(root, mod >> s)};
    rep(i,k,2*k) rt[i] = rt[i / 2] * z[i & 1] % mod;
  }
  vi rev(n);
  rep(i,0,n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
  rep(i,0,n) if (i < rev[i]) swap(a[i], a[rev[i]]);
  for (int k = 1; k < n; k *= 2)
    for (int i = 0; i < n; i += 2 * k) rep(j,0,k) {
      ll z = rt[j + k] * a[i + j + k] % mod, &ai = a[i + j];
      a[i + j + k] = ai - z + (z > ai ? mod : 0);
      ai += (ai + z >= mod ? z - mod : z);
    }
}
vl conv(const vl &a, const vl &b) {
  if (a.empty() || b.empty()) return {};
  int s = sz(a) + sz(b) - 1, B = 32 - __builtin_clz(s),
      n = 1 << B;
  ll inv = modpow(n, mod - 2);
  vl L(a), R(b), out(n);
  L.resize(n), R.resize(n);
  ntt(L), ntt(R);
  rep(i,0,n)
    out[-i & (n - 1)] = (ll)L[i] * R[i] % mod * inv % mod;
  ntt(out);
  return {out.begin(), out.begin() + s};
}
```

FastSubsetTransform.h

Description: Transform to a basis with fast convolutions of the form $c[z] = \sum_{z=x \oplus y} a[x] \cdot b[y]$, where $\oplus$ is one of AND, OR, XOR. The size of a must be a power of two.
Time: $\mathcal{O}(N \log N)$

464cf3, 16 lines

```
void FST(vi& a, bool inv) {
  for (int n = sz(a), step = 1; step < n; step *= 2) {
    for (int i = 0; i < n; i += 2 * step) rep(j,i,i+step) {
      int &u = a[j], &v = a[j + step]; tie(u, v) =
        inv ? pii(v - u, u) : pii(v, u + v); // AND
        inv ? pii(v, u - v) : pii(u + v, u); // OR
        pii(u + v, u - v);                   // XOR
    }
  }
  if (inv) for (int& x : a) x /= sz(a); // XOR only
}
vi conv(vi a, vi b) {
  FST(a, 0); FST(b, 0);
  rep(i,0,sz(a)) a[i] *= b[i];
  FST(a, 1); return a;
}
```

FWHTmod3.h

Description: Transform to a basis with fast convolutions of the form $c[z] = \sum_{z=x \oplus y} a[x] \cdot b[y]$, where $\oplus$ is one of AND, OR, XOR. The size of a must be a power of two.
Time: $\mathcal{O}(N \log N)$

a42d04, 28 lines

```
struct Z{
    ll a, b;
    Z(ll x = 0, ll y = 0) : a(x), b(y) { }
    Z operator+(const Z& o) const { return Z(a + o.a, b + o.b);
        }
    Z operator+(const Z& o) const { return Z(a * o.a - b * o.b,
        a * o.b + o.a * b - b * o.b); }
};

const Z w = Z(0,1);
const Z w2 = Z(-1,-1);
using vz = vector<Z> ;

void FST(vz& a, bool inv) {
  for (int n = sz(a), step = 1; step < n; step *= 3) {
    for (int i = 0; i < n; i += 3 * step) rep(j,i,i+step) {
            Z &x = a[j], &y = a[j + step], &z = a[j + 2 * step
                ];
            tie(x, y, z) =
                inv ? make_tuple(x + y + z, x + w * y + w2 * z,
                      x + w2 * y + w * z)
                    : make_tuple(x + y + z, x + w2 * y + w * z,
                          x + w * y + w2 * z);
    }
  }
  if (inv) for (auto& x : a) x.a /= sz(a), x.b /= sz(a); XOR
      only
}

vi conv(vi a, vi b) {
  FST(a, 0); FST(b, 0);
  rep(i,0,sz(a)) a[i] *= b[i];
  FST(a, 1); return a;
}
```

Number theory (5)

5.1 Modular arithmetic

ModularArithmetic.h

Description: Operators for modular arithmetic. You need to set mod to some number first and then you can use the structure.

"euclid.h" ea1ac7, 19 lines

```
const ll mod = 17; // change to something else
struct Mod {
  ll x;
  Mod(ll y) : Mod(y%mod+mod,0){}
  Mod(ll y,int) : x(y<mod?y:y-mod){}
  Mod operator+(Mod b) { return {x + b.x,0}; }
  Mod operator-(Mod b) { return {x - b.x + mod,0}; }
  Mod operator*(Mod b) { return {x * b.x % mod,0}; }
  Mod operator/(Mod b) { return *this * invert(b); }
  Mod invert(Mod a) {
```

```
    ll x, y, g = euclid(a.x, mod, x, y);
    assert(g == 1); return x;
  }
  Mod operator^(ll e) {
    if (!e) return 1;
    Mod r = *this ^ (e / 2); r = r * r;
    return e&1 ? *this * r : r;
  }
};
```

ModInverse.h

Description: Pre-computation of modular inverses. Assumes LIM $\leq$ mod and that mod is a prime.

6f684f, 3 lines

```
const ll mod = 1000000007, LIM = 200000;
ll* inv = new ll[LIM] - 1; inv[1] = 1;
rep(i,2,LIM) inv[i] = mod - (mod / i) * inv[mod % i] % mod;
```

ModPow.h

b83e45, 8 lines

```
const ll mod = 1000000007; // faster if const

ll modpow(ll b, ll e) {
  ll ans = 1;
  for (; e; b = b * b % mod, e /= 2)
    if (e & 1) ans = ans * b % mod;
  return ans;
}
```

ModLog.h

Description: Returns the smallest $x > 0$ s.t. $a^x = b \pmod m$, or -1 if no such x exists. modLog(a,1,m) can be used to calculate the order of a.
Time: $\mathcal{O}\left(\sqrt{m}\right)$

c040b8, 11 lines

```
ll modLog(ll a, ll b, ll m) {
  ll n = (ll) sqrt(m) + 1, e = 1, f = 1, j = 1;
  unordered_map<ll, ll> A;
  while (j <= n && (e = f = e * a % m) != b % m)
    A[e * b % m] = j++;
  if (e == b % m) return j;
  if (__gcd(m, e) == __gcd(m, b))
    rep(i,2,n+2) if (A.count(e = e * f % m))
      return n * i - A[e];
  return -1;
}
```

ModSum.h

Description: Sums of mod'ed arithmetic progressions.
modsum(to, c, k, m) $= \sum_{i=0}^{\text{to}-1} (ki + c)\%m$. divsum is similar but for floored division.
Time: $\log(m)$, with a large constant.

5c5bc5, 16 lines

```
typedef unsigned long long ull;
ull sumsq(ull to) { return to / 2 * ((to-1) | 1); }

ull divsum(ull to, ull c, ull k, ull m) {
  ull res = k / m * sumsq(to) + c / m * to;
  k %= m; c %= m;
  if (!k) return res;
  ull to2 = (to * k + c) / m;
  return res + (to - 1) * to2 - divsum(to2, m-1 - c, m, k);
}

ll modsum(ull to, ll c, ll k, ll m) {
  c = ((c % m) + m) % m;
  k = ((k % m) + m) % m;
  return to * c + k * sumsq(to) - m * divsum(to, c, k, m);
}
```

ModMulLL.h

Description: Calculate $a \cdot b \bmod c$ (or $a^b \bmod c$) for $0 \leq a, b \leq c \leq 7.2 \cdot 10^{18}$.
Time: $\mathcal{O}(1)$ for modmul, $\mathcal{O}(\log b)$ for modpow

bbbd8f, 11 lines

```
typedef unsigned long long ull;
ull modmul(ull a, ull b, ull M) {
  ll ret = a * b - M * ull(1.L / M * a * b);
  return ret + M * (ret < 0) - M * (ret >= (ll)M);
}
ull modpow(ull b, ull e, ull mod) {
  ull ans = 1;
  for (; e; b = modmul(b, b, mod), e /= 2)
    if (e & 1) ans = modmul(ans, b, mod);
  return ans;
}
```

ModSqrt.h

Description: Tonelli-Shanks algorithm for modular square roots. Finds x s.t. $x^2 = a \pmod p$ ($-x$ gives the other solution).
Time: $\mathcal{O}\left(\log^2 p\right)$ worst case, $\mathcal{O}(\log p)$ for most p

"ModPow.h" 19a793, 24 lines

```
ll sqrt(ll a, ll p) {
  a %= p; if (a < 0) a += p;
  if (a == 0) return 0;
  assert(modpow(a, (p-1)/2, p) == 1); // else no solution
  if (p % 4 == 3) return modpow(a, (p+1)/4, p);
  // a^(n+3)/8 or 2^(n+3)/8 * 2^(n-1)/4 works if p % 8 == 5
  ll s = p - 1, n = 2;
  int r = 0, m;
  while (s % 2 == 0)
    ++r, s /= 2;
  while (modpow(n, (p - 1) / 2, p) != p - 1) ++n;
  ll x = modpow(a, (s + 1) / 2, p);
  ll b = modpow(a, s, p), g = modpow(n, s, p);
  for (;; r = m) {
    ll t = b;
    for (m = 0; m < r && t != 1; ++m)
      t = t * t % p;
    if (m == 0) return x;
    ll gs = modpow(g, 1LL << (r - m - 1), p);
    g = gs * gs % p;
    x = x * gs % p;
    b = b * g % p;
  }
}
```

PrimitiveRoot.h

Description: Calculates primitive root modulo p. p is prime, to make it work with any number, add the calculation of phi(p)

a14d60, 33 lines

```
int p_root(int p) {
    // divisores de phi (p primo -> phi = p - 1)
    vi facts;
    int phi = p - 1, n = phi;
    for(int i = 2; i * i <= n; i++) {
        if(n % i == 0) {
            facts.push_back(i);
            while(n % i == 0) n /= i;
        }
    }
    if(n > 1) facts.push_back(n);

    auto bp = [&](int a, int b) {
        int res = 1;
        while(b) {
            if(b & 1) res = 1LL * res * a % p;
            a = 1LL * a * a % p;
            b >>= 1;
        }
        return res;
    };

    rep(res,2,p+1) {
        bool ok = true;
        for(int f : facts) {
            // binpow modulo p
            ok &= (bp(res,phi/f) != 1);
            if(!ok) break;
        }
        if(ok) return res;
    }
    assert(false); // por si acaso
}
```

5.2 Primality

FastEratosthenes.h

Description: Prime sieve for generating all primes smaller than LIM.
Time: LIM=1e9 $\approx$ 1.5s

6b2912, 20 lines

```
const int LIM = 1e6;
bitset<LIM> isPrime;
vi eratosthenes() {
  const int S = (int)round(sqrt(LIM)), R = LIM / 2;
  vi pr = {2}, sieve(S+1); pr.reserve(int(LIM/log(LIM)*1.1));
  vector<pii> cp;
  for (int i = 3; i <= S; i += 2) if (!sieve[i]) {
    cp.push_back({i, i * i / 2});
    for (int j = i * i; j <= S; j += 2 * i) sieve[j] = 1;
  }
  for (int L = 1; L <= R; L += S) {
    array<bool, S> block{};
    for (auto &[p, idx] : cp)
      for (int i=idx; i < S+L; idx = (i+=p)) block[i-L] = 1;
    rep(i,0,min(S, R - L))
      if (!block[i]) pr.push_back((L + i) * 2 + 1);
  }
  for (int i : pr) isPrime[i] = 1;
  return pr;
}
```

MillerRabin.h

Description: Deterministic Miller-Rabin primality test. Guaranteed to work for numbers up to $7 \cdot 10^{18}$; for larger numbers, use Python and extend A randomly.
Time: 7 times the complexity of $a^b \mod c$.

"ModMulLL.h" 60dcd1, 12 lines

```
bool isPrime(ull n) {
  if (n < 2 || n % 6 % 4 != 1) return (n | 1) == 3;
  ull A[] = {2, 325, 9375, 28178, 450775, 9780504, 1795265022},
      s = __builtin_ctzll(n-1), d = n >> s;
  for (ull a : A) {   // ^ count trailing zeroes
    ull p = modpow(a%n, d, n), i = s;
    while (p != 1 && p != n - 1 && a % n && i--)
      p = modmul(p, p, n);
    if (p != n-1 && i != s) return 0;
  }
  return 1;
}
```

Factor.h

Description: Pollard-rho randomized factorization algorithm. Returns prime factors of a number, in arbitrary order (e.g. 2299 -> {11, 19, 11}).
Time: $\mathcal{O}\left(n^{1/4}\right)$, less for numbers with small factors.

"ModMulLL.h", "MillerRabin.h" d8d98d, 18 lines

```
ull pollard(ull n) {
  ull x = 0, y = 0, t = 30, prd = 2, i = 1, q;
```

```
  auto f = [&](ull x) { return modmul(x, x, n) + i; };
  while (t++ % 40 || __gcd(prd, n) == 1) {
    if (x == y) x = ++i, y = f(x);
    if ((q = modmul(prd, max(x,y) - min(x,y), n))) prd = q;
    x = f(x), y = f(f(y));
  }
  return __gcd(prd, n);
}
vector<ull> factor(ull n) {
  if (n == 1) return {};
  if (isPrime(n)) return {n};
  ull x = pollard(n);
  auto l = factor(x), r = factor(n / x);
  l.insert(l.end(), all(r));
  return l;
}
```

Mobius.h

Description: Check definition.

Time: $\mathcal{O}(N \log \log N)$

fcb4bb, 10 lines

```
const int MX = 1e6;
short mu[MX+1] = {0, 1};
void mobius() {
    for (int i = 1; i <= MX; i++) {
        if (!mu[i]) continue;
        for (int j = i*2; j <= MX; j += i) {
            mu[j] -= mu[i];
        }
    }
}
```

5.3 Divisibility

euclid.h

Description: Finds two integers x and y, such that $ax + by = \gcd(a, b)$. If you just need gcd, use the built in __gcd instead. If a and b are coprime, then x is the inverse of $a \pmod b$.

33ba8f, 5 lines

```
ll euclid(ll a, ll b, ll &x, ll &y) {
  if (!b) return x = 1, y = 0, a;
  ll d = euclid(b, a % b, y, x);
  return y -= a/b * x, d;
}
```

Diophantic.h

Description: solves ax + by = c

Time: $\mathcal{O}(\log N)$

976e96, 19 lines

```
int gcd(int a, int b, int& x, int& y) {
    if (b == 0) {
        x = 1; y = 0;
        return a;
    }
    int x1, y1;
    int d = gcd(b, a % b, x1, y1);
    x = y1; y = x1 - y1 * (a / b);
    return d;
}

bool find_any_solution(int a, int b, int c, int &x0, int &y0,
     int &g) {
    g = gcd(abs(a), abs(b), x0, y0);
    if (c % g) return false;
    x0 *= c / g; y0 *= c / g;
    if (a < 0) x0 = -x0;
    if (b < 0) y0 = -y0;
    return true;
}
```

CRT.h

Description: Chinese Remainder Theorem.

crt(a, m, b, n) computes x such that $x \equiv a \pmod m$, $x \equiv b \pmod n$. If $|a| < m$ and $|b| < n$, x will obey $0 \le x < \text{lcm}(m, n)$. Assumes $mn < 2^{62}$.

Time: $\log(n)$

"euclid.h" 04d93a, 7 lines

```
ll crt(ll a, ll m, ll b, ll n) {
  if (n > m) swap(a, b), swap(m, n);
  ll x, y, g = euclid(m, n, x, y);
  assert((a - b) % g == 0); // else no solution
  x = (b - a) % n * x % n / g * m + a;
  return x < 0 ? x + m*n/g : x;
}
```

5.3.1 Bézout's identity

For $a \neq, b \neq 0$, then $d = gcd(a, b)$ is the smallest positive integer for which there are integer solutions to

$$ax + by = d$$

If (x, y) is one solution, then all solutions are given by

$$\left(x + \frac{kb}{\gcd(a,b)}, y - \frac{ka}{\gcd(a,b)}\right), \quad k \in \mathbb{Z}$$

phiFunction.h

Description: *Euler's* ϕ function is defined as $\phi(n) :=$ # of positive integers $\le n$ that are coprime with n. $\phi(1) = 1$, p prime $\Rightarrow \phi(p^k) = (p-1)p^{k-1}$, m, n coprime $\Rightarrow \phi(mn) = \phi(m)\phi(n)$. If $n = p_1^{k_1} p_2^{k_2} ... p_r^{k_r}$ then $\phi(n) = (p_1 - 1)p_1^{k_1-1} ... (p_r - 1)p_r^{k_r-1}$. $\phi(n) = n \cdot \prod_{p|n}(1 - 1/p)$.
$\sum_{d|n} \phi(d) = n$, $\sum_{1 \le k \le n, \gcd(k,n)=1} k = n\phi(n)/2, n > 1$

Euler's thm: a, n coprime $\Rightarrow a^{\phi(n)} \equiv 1 \pmod n$.

Fermat's little thm: p prime $\Rightarrow a^{p-1} \equiv 1 \pmod p$ $\forall a$.

cf7d6d, 8 lines

```
const int LIM = 5000000;
int phi[LIM];

void calculatePhi() {
  rep(i,0,LIM) phi[i] = i&1 ? i : i/2;
  for (int i = 3; i < LIM; i += 2) if(phi[i] == i)
    for (int j = i; j < LIM; j += i) phi[j] -= phi[j] / i;
}
```

5.4 Fractions

ContinuedFractions.h

Description: Given N and a real number $x \ge 0$, finds the closest rational approximation p/q with $p, q \le N$. It will obey $|p/q - x| \le 1/qN$.

For consecutive convergents, $p_{k+1}q_k - q_{k+1}p_k = (-1)^k$. ($p_k/q_k$ alternates between $> x$ and $< x$.) If x is rational, y eventually becomes ∞; if x is the root of a degree 2 polynomial the a's eventually become cyclic.

Time: $\mathcal{O}(\log N)$

dd6c5e, 21 lines

```
typedef double d; // for N ~ 1e7; long double for N ~ 1e9
pair<ll, ll> approximate(d x, ll N) {
  ll LP = 0, LQ = 1, P = 1, Q = 0, inf = LLONG_MAX; d y = x;
  for (;;) {
    ll lim = min(P ? (N-LP) / P : inf, Q ? (N-LQ) / Q : inf),
       a = (ll)floor(y), b = min(a, lim),
       NP = b*P + LP, NQ = b*Q + LQ;
    if (a > b) {
      // If b > a/2, we have a semi-convergent that gives us a
      // better approximation; if b = a/2, we *may* have one.
      // Return {P, Q} here for a more canonical approximation.
      return (abs(x - (d)NP / (d)NQ) < abs(x - (d)P / (d)Q)) ?
        make_pair(NP, NQ) : make_pair(P, Q);
    }
    if (abs(y = 1/(y - (d)a)) > 3*N) {
      return {NP, NQ};
    }
    LP = P; P = NP;
    LQ = Q; Q = NQ;
  }
}
```

FracBinarySearch.h

Description: Given f and N, finds the smallest fraction $p/q \in [0, 1]$ such that $f(p/q)$ is true, and $p, q \le N$. You may want to throw an exception from f if it finds an exact solution, in which case N can be removed.

Usage: fracBS([](Frac f) { return f.p>=3*f.q; }, 10); // {1,3}

Time: $\mathcal{O}(\log(N))$

27ab3e, 25 lines

```
struct Frac { ll p, q; };

template<class F>
Frac fracBS(F f, ll N) {
  bool dir = 1, A = 1, B = 1;
  Frac lo{0, 1}, hi{1, 1}; // Set hi to 1/0 to search (0, N]
  if (f(lo)) return lo;
  assert(f(hi));
  while (A || B) {
    ll adv = 0, step = 1; // move hi if dir, else lo
    for (int si = 0; step; (step *= 2) >>= si) {
      adv += step;
      Frac mid{lo.p * adv + hi.p, lo.q * adv + hi.q};
      if (abs(mid.p) > N || mid.q > N || dir == !f(mid)) {
        adv -= step; si = 2;
      }
    }
    hi.p += lo.p * adv;
    hi.q += lo.q * adv;
    dir = !dir;
    swap(lo, hi);
    A = B; B = !!adv;
  }
  return dir ? hi : lo;
}
```

5.5 Pythagorean Triples

The Pythagorean triples are uniquely generated by

$$a = k \cdot (m^2 - n^2), \;\; b = k \cdot (2mn), \;\; c = k \cdot (m^2 + n^2),$$

with $m > n > 0$, $k > 0$, $m \perp n$, and either m or n even.

5.6 Primes

$p = 962592769$ is such that $2^{21} \mid p - 1$, which may be useful. For hashing use 970592641 (31-bit number), 31443539979727 (45-bit), 3006703054056749 (52-bit). There are 78498 primes less than 1 000 000.

Primitive roots exist modulo any prime power p^a, except for $p = 2, a > 2$, and there are $\phi(\phi(p^a))$ many. For $p = 2, a > 2$, the group $\mathbb{Z}_{2^a}^\times$ is instead isomorphic to $\mathbb{Z}_2 \times \mathbb{Z}_{2^{a-2}}$.

5.7 Estimates

$\sum_{d|n} d = O(n \log \log n)$.

The number of divisors of n is at most around 100 for $n < 5e4$, 500 for $n < 1e7$, 2000 for $n < 1e10$, 200 000 for $n < 1e19$.

5.8 Mobius Function

$$\mu(n) = \begin{cases} 0 & n \text{ is not square free} \\ 1 & n \text{ has even number of prime factors} \\ -1 & n \text{ has odd number of prime factors} \end{cases}$$

Mobius Inversion:

$$g(n) = \sum_{d|n} f(d) \Leftrightarrow f(n) = \sum_{d|n} \mu(d) g(n/d)$$

Other useful formulas/forms:

$\sum_{d|n} \mu(d) = [n = 1]$ (very useful)

$g(n) = \sum_{n|d} f(d) \Leftrightarrow f(n) = \sum_{n|d} \mu(d/n) g(d)$

$g(n) = \sum_{1 \le m \le n} f(\lfloor \frac{n}{m} \rfloor) \Leftrightarrow f(n) = \sum_{1 \le m \le n} \mu(m) g(\lfloor \frac{n}{m} \rfloor)$

Combinatorial (6)

6.1 Permutations

6.1.1 Factorial

n	1	2	3	4	5	6	7	8	9	10
$n!$	1	2	6	24	120	720	5040	40320	362880	3628800
n	11	12	13	14	15	16	17			
$n!$	4.0e7	4.8e8	6.2e9	8.7e10	1.3e12	2.1e13	3.6e14			
n	20	25	30	40	50	100	150	171		
$n!$	2e18	2e25	3e32	8e47	3e64	9e157	6e262	>DBL_MAX		

IntPerm.h

Description: Permutation -> integer conversion. (Not order preserving.) Integer -> permutation can use a lookup table.

Time: $\mathcal{O}(n)$ Hola toy saludando

044568, 6 lines

```
int permToInt(vi& v) {
  int use = 0, i = 0, r = 0;
  for(int x:v) r = r * ++i + __builtin_popcount(use & -(1<<x)),
    use |= 1 << x;                    // (note: minus, not ~!)
  return r;
}
```

6.1.2 Cycles

Let $g_S(n)$ be the number of n-permutations whose cycle lengths all belong to the set S. Then

$$\sum_{n=0}^{\infty} g_S(n) \frac{x^n}{n!} = \exp\left(\sum_{n \in S} \frac{x^n}{n}\right)$$

6.1.3 Derangements

Permutations of a set such that none of the elements appear in their original position.

$$D(n) = (n-1)(D(n-1)+D(n-2)) = nD(n-1)+(-1)^n = \left\lfloor \frac{n!}{e} \right\rceil$$

6.1.4 Burnside's lemma

Given a group G of symmetries and a set X, the number of elements of X *up to symmetry* equals

$$\frac{1}{|G|} \sum_{g \in G} |X^g|,$$

where X^g are the elements fixed by g ($g.x = x$).

If $f(n)$ counts "configurations" (of some sort) of length n, we can ignore rotational symmetry using $G = \mathbb{Z}_n$ to get

$$g(n) = \frac{1}{n} \sum_{k=0}^{n-1} f(\gcd(n,k)) = \frac{1}{n} \sum_{k|n} f(k) \phi(n/k).$$

6.2 Partitions and subsets

6.2.1 Partition function

Number of ways of writing n as a sum of positive integers, disregarding the order of the summands.

$$p(0) = 1,\ p(n) = \sum_{k \in \mathbb{Z} \setminus \{0\}} (-1)^{k+1} p(n - k(3k-1)/2)$$

$$p(n) \sim 0.145/n \cdot \exp(2.56\sqrt{n})$$

n	0	1	2	3	4	5	6	7	8	9	20	50	100
$p(n)$	1	1	2	3	5	7	11	15	22	30	627	~2e5	~2e8

6.2.2 Lucas' Theorem

Let n, m be non-negative integers and p a prime. Write $n = n_k p^k + ... + n_1 p + n_0$ and $m = m_k p^k + ... + m_1 p + m_0$. Then $\binom{n}{m} \equiv \prod_{i=0}^{k} \binom{n_i}{m_i} \pmod{p}$.

6.2.3 Binomials

multinomial.h

Description: Computes $\binom{k_1 + \cdots + k_n}{k_1, k_2, \ldots, k_n} = \frac{(\sum k_i)!}{k_1! k_2! \ldots k_n!}$.

a0a312, 5 lines

```
ll multinomial(vi& v) {
  ll c = 1, m = v.empty() ? 1 : v[0];
  rep(i,1,sz(v)) rep(j,0,v[i]) c = c * ++m / (j+1);
  return c;
}
```

6.3 General purpose numbers

6.3.1 Bernoulli numbers

EGF of Bernoulli numbers is $B(t) = \frac{t}{e^t - 1}$ (FFT-able).
$B[0, \ldots] = [1, -\frac{1}{2}, \frac{1}{6}, 0, -\frac{1}{30}, 0, \frac{1}{42}, \ldots]$

Sums of powers:

$$\sum_{i=1}^{n} n^m = \frac{1}{m+1} \sum_{k=0}^{m} \binom{m+1}{k} B_k \cdot (n+1)^{m+1-k}$$

Euler-Maclaurin formula for infinite sums:

$$\sum_{i=m}^{\infty} f(i) = \int_m^{\infty} f(x)dx - \sum_{k=1}^{\infty} \frac{B_k}{k!} f^{(k-1)}(m)$$

$$\approx \int_m^{\infty} f(x)dx + \frac{f(m)}{2} - \frac{f'(m)}{12} + \frac{f'''(m)}{720} + O(f^{(5)}(m))$$

6.3.2 Stirling numbers of the first kind

Number of permutations on n items with k cycles.

$$c(n,k) = c(n-1,k-1) + (n-1)c(n-1,k),\ c(0,0) = 1$$
$$\sum_{k=0}^{n} c(n,k) x^k = x(x+1)\ldots(x+n-1)$$

$c(8,k) = 8, 0, 5040, 13068, 13132, 6769, 1960, 322, 28, 1$
$c(n,2) = 0, 0, 1, 3, 11, 50, 274, 1764, 13068, 109584, \ldots$

6.3.3 Eulerian numbers

Number of permutations $\pi \in S_n$ in which exactly k elements are greater than the previous element. k j:s s.t. $\pi(j) > \pi(j+1)$, $k+1$ j:s s.t. $\pi(j) \ge j$, k j:s s.t. $\pi(j) > j$.

$$E(n,k) = (n-k)E(n-1,k-1) + (k+1)E(n-1,k)$$

$$E(n,0) = E(n,n-1) = 1$$

$$E(n,k) = \sum_{j=0}^{k} (-1)^j \binom{n+1}{j} (k+1-j)^n$$

6.3.4 Stirling numbers of the second kind

Partitions of n distinct elements into exactly k groups.

$$S(n,k) = S(n-1,k-1) + kS(n-1,k)$$

$$S(n,1) = S(n,n) = 1$$

$$S(n,k) = \frac{1}{k!} \sum_{j=0}^{k} (-1)^{k-j} \binom{k}{j} j^n$$

6.3.5 Bell numbers

Total number of partitions of n distinct elements. $B(n) = 1, 1, 2, 5, 15, 52, 203, 877, 4140, 21147, \ldots$. For p prime,

$$B(p^m + n) \equiv mB(n) + B(n+1) \pmod{p}$$

6.3.6 Labeled unrooted trees

on n vertices: n^{n-2}
on k existing trees of size n_i: $n_1 n_2 \cdots n_k n^{k-2}$
with degrees d_i: $(n-2)!/((d_1-1)! \cdots (d_n-1)!)$

6.3.7 Catalan numbers

$$C_n = \frac{1}{n+1}\binom{2n}{n} = \binom{2n}{n} - \binom{2n}{n+1} = \frac{(2n)!}{(n+1)!n!}$$

$$C_0 = 1,\ C_{n+1} = \frac{2(2n+1)}{n+2}C_n,\ C_{n+1} = \sum C_i C_{n-i}$$

$C_n = 1, 1, 2, 5, 14, 42, 132, 429, 1430, 4862, 16796, 58786, \ldots$

- sub-diagonal monotone paths in an $n \times n$ grid.
- strings with n pairs of parenthesis, correctly nested.
- binary trees with with $n+1$ leaves (0 or 2 children).
- ordered trees with $n+1$ vertices.
- ways a convex polygon with $n+2$ sides can be cut into triangles by connecting vertices with straight lines.
- permutations of $[n]$ with no 3-term increasing subseq.

Graph (7)

7.1 Fundamentals

BellmanFord.h

Description: Calculates shortest paths from s in a graph that might have negative edge weights. Unreachable nodes get dist = inf; nodes reachable through negative-weight cycles get dist = -inf. Assumes $V^2 \max|w_i| < \sim 2^{63}$.
Time: $\mathcal{O}(VE)$

830a8f, 23 lines

```
const ll inf = LLONG_MAX;
struct Ed { int a, b, w, s() { return a < b ? a : -a; }};
struct Node { ll dist = inf; int prev = -1; };

void bellmanFord(vector<Node>& nodes, vector<Ed>& eds, int s) {
  nodes[s].dist = 0;
  sort(all(eds), [](Ed a, Ed b) { return a.s() < b.s(); });

  int lim = sz(nodes) / 2 + 2; // /3+100 with shuffled vertices
  rep(i,0,lim) for (Ed ed : eds) {
    Node cur = nodes[ed.a], &dest = nodes[ed.b];
    if (abs(cur.dist) == inf) continue;
    ll d = cur.dist + ed.w;
    if (d < dest.dist) {
      dest.prev = ed.a;
      dest.dist = (i < lim-1 ? d : -inf);
    }
  }
  rep(i,0,lim) for (Ed e : eds) {
    if (nodes[e.a].dist == -inf)
      nodes[e.b].dist = -inf;
  }
}
```

FloydWarshall.h

Description: Calculates all-pairs shortest path in a directed graph that might have negative edge weights. Input is an distance matrix m, where $m[i][j] =$ `inf` if i and j are not adjacent. As output, $m[i][j]$ is set to the shortest distance between i and j, `inf` if no path, or `-inf` if the path goes through a negative-weight cycle.
Time: $\mathcal{O}(N^3)$

531245, 12 lines

```
const ll inf = 1LL << 62;
void floydWarshall(vector<vector<ll>>& m) {
  int n = sz(m);
  rep(i,0,n) m[i][i] = min(m[i][i], 0LL);
  rep(k,0,n) rep(i,0,n) rep(j,0,n)
    if (m[i][k] != inf && m[k][j] != inf) {
      auto newDist = max(m[i][k] + m[k][j], -inf);
      m[i][j] = min(m[i][j], newDist);
    }
  rep(k,0,n) if (m[k][k] < 0) rep(i,0,n) rep(j,0,n)
    if (m[i][k] != inf && m[k][j] != inf) m[i][j] = -inf;
}
```

TopoSort.h

Description: Topological sorting. Given is an oriented graph. Output is an ordering of vertices, such that there are edges only from left to right. If there are cycles, the returned list will have size smaller than n – nodes reachable from cycles will not be returned.
Time: $\mathcal{O}(|V| + |E|)$

d678d8, 8 lines

```
vi topoSort(const vector<vi>& gr) {
  vi indeg(sz(gr)), q;
  for (auto& li : gr) for (int x : li) indeg[x]++;
  rep(i,0,sz(gr)) if (indeg[i] == 0) q.push_back(i);
  rep(j,0,sz(q)) for (int x : gr[q[j]])
    if (--indeg[x] == 0) q.push_back(x);
  return q;
}
```

7.2 Network flow

PushRelabel.h

Description: Push-relabel using the highest label selection rule and the gap heuristic. Quite fast in practice. To obtain the actual flow, look at positive values only.
Time: $\mathcal{O}\left(V^2\sqrt{E}\right)$

0ae1d4, 48 lines

```
struct PushRelabel {
  struct Edge {
    int dest, back;
    ll f, c;
  };
  vector<vector<Edge>> g;
  vector<ll> ec;
  vector<Edge*> cur;
  vector<vi> hs; vi H;
  PushRelabel(int n) : g(n), ec(n), cur(n), hs(2*n), H(n) {}

  void addEdge(int s, int t, ll cap, ll rcap=0) {
    if (s == t) return;
    g[s].push_back({t, sz(g[t]), 0, cap});
    g[t].push_back({s, sz(g[s])-1, 0, rcap});
  }

  void addFlow(Edge& e, ll f) {
    Edge &back = g[e.dest][e.back];
    if (!ec[e.dest] && f) hs[H[e.dest]].push_back(e.dest);
    e.f += f; e.c -= f; ec[e.dest] += f;
    back.f -= f; back.c += f; ec[back.dest] -= f;
  }
  ll calc(int s, int t) {
    int v = sz(g); H[s] = v; ec[t] = 1;
    vi co(2*v); co[0] = v-1;
    rep(i,0,v) cur[i] = g[i].data();
    for (Edge& e : g[s]) addFlow(e, e.c);

    for (int hi = 0;;) {
      while (hs[hi].empty()) if (!hi--) return -ec[s];
      int u = hs[hi].back(); hs[hi].pop_back();
      while (ec[u] > 0)  // discharge u
        if (cur[u] == g[u].data() + sz(g[u])) {
          H[u] = 1e9;
          for (Edge& e : g[u]) if (e.c && H[u] > H[e.dest]+1)
            H[u] = H[e.dest]+1, cur[u] = &e;
          if (++co[H[u]], !--co[hi] && hi < v)
            rep(i,0,v) if (hi < H[i] && H[i] < v)
              --co[H[i]], H[i] = v + 1;
          hi = H[u];
        } else if (cur[u]->c && H[u] == H[cur[u]->dest]+1)
          addFlow(*cur[u], min(ec[u], cur[u]->c));
        else ++cur[u];
    }
  }
  bool leftOfMinCut(int a) { return H[a] >= sz(g); }
};
```

MinCostMaxFlow.h

Description: Min-cost max-flow. If costs can be negative, call setpi before maxflow, but note that negative cost cycles are not supported. To obtain the actual flow, look at positive values only.
Time: $\mathcal{O}(FE\log(V))$ where F is max flow. $\mathcal{O}(VE)$ for setpi.

58385b, 79 lines

```
#include <bits/extc++.h>

const ll INF = numeric_limits<ll>::max() / 4;

struct MCMF {
  struct edge {
    int from, to, rev;
    ll cap, cost, flow;
  };
  int N;
  vector<vector<edge>> ed;
  vi seen;
  vector<ll> dist, pi;
  vector<edge*> par;

  MCMF(int N) : N(N), ed(N), seen(N), dist(N), pi(N), par(N) {}

  void addEdge(int from, int to, ll cap, ll cost) {
    if (from == to) return;
    ed[from].push_back(edge{ from,to,sz(ed[to]),cap,cost,0 });
    ed[to].push_back(edge{ to,from,sz(ed[from])-1,0,-cost,0 });
  }

  void path(int s) {
    fill(all(seen), 0);
    fill(all(dist), INF);
    dist[s] = 0; ll di;

    __gnu_pbds::priority_queue<pair<ll, int>> q;
    vector<decltype(q)::point_iterator> its(N);
    q.push({ 0, s });

    while (!q.empty()) {
      s = q.top().second; q.pop();
      seen[s] = 1; di = dist[s] + pi[s];
      for (edge& e : ed[s]) if (!seen[e.to]) {
        ll val = di - pi[e.to] + e.cost;
        if (e.cap - e.flow > 0 && val < dist[e.to]) {
          dist[e.to] = val;
          par[e.to] = &e;
          if (its[e.to] == q.end())
            its[e.to] = q.push({ -dist[e.to], e.to });
          else
            q.modify(its[e.to], { -dist[e.to], e.to });
        }
      }
    }
    rep(i,0,N) pi[i] = min(pi[i] + dist[i], INF);
  }

  pair<ll, ll> maxflow(int s, int t) {
```

```
    ll totflow = 0, totcost = 0;
    while (path(s), seen[t]) {
      ll fl = INF;
      for (edge* x = par[t]; x; x = par[x->from])
        fl = min(fl, x->cap - x->flow);

      totflow += fl;
      for (edge* x = par[t]; x; x = par[x->from]) {
        x->flow += fl;
        ed[x->to][x->rev].flow -= fl;
      }
    }
    rep(i,0,N) for(edge& e : ed[i]) totcost += e.cost * e.flow;
    return {totflow, totcost/2};
  }

  // If some costs can be negative, call this before maxflow:
  void setpi(int s) { // (otherwise, leave this out)
    fill(all(pi), INF); pi[s] = 0;
    int it = N, ch = 1; ll v;
    while (ch-- && it--)
      rep(i,0,N) if (pi[i] != INF)
        for (edge& e : ed[i]) if (e.cap)
          if ((v = pi[i] + e.cost) < pi[e.to])
            pi[e.to] = v, ch = 1;
    assert(it >= 0); // negative cost cycle
  }
};
```

EdmondsKarp.h

Description: Flow algorithm with guaranteed complexity $O(VE^2)$. To get edge flow values, compare capacities before and after, and take the positive values only.

482fe0, 36 lines

```
template<class T> T edmondsKarp(vector<unordered_map<int, T>>&
    graph, int source, int sink) {
  assert(source != sink);
  T flow = 0;
  vi par(sz(graph)), q = par;

  for (;;) {
    fill(all(par), -1);
    par[source] = 0;
    int ptr = 1;
    q[0] = source;

    rep(i,0,ptr) {
      int x = q[i];
      for (auto e : graph[x]) {
        if (par[e.first] == -1 && e.second > 0) {
          par[e.first] = x;
          q[ptr++] = e.first;
          if (e.first == sink) goto out;
        }
      }
    }
    return flow;
out:
    T inc = numeric_limits<T>::max();
    for (int y = sink; y != source; y = par[y])
      inc = min(inc, graph[par[y]][y]);

    flow += inc;
    for (int y = sink; y != source; y = par[y]) {
      int p = par[y];
      if ((graph[p][y] -= inc) <= 0) graph[p].erase(y);
      graph[y][p] += inc;
    }
  }
}
```

Dinic.h

Description: Flow algorithm with complexity $O(VE\log U)$ where $U = \max|\text{cap}|$. $O(\min(E^{1/2}, V^{2/3})E)$ if $U = 1$; $O(\sqrt{V}E)$ for bipartite matching.

d7f0f1, 42 lines

```
struct Dinic {
  struct Edge {
    int to, rev;
    ll c, oc;
    ll flow() { return max(oc - c, 0LL); } // if you need flows
  };
  vi lvl, ptr, q;
  vector<vector<Edge>> adj;
  Dinic(int n) : lvl(n), ptr(n), q(n), adj(n) {}
  void addEdge(int a, int b, ll c, ll rcap = 0) {
    adj[a].push_back({b, sz(adj[b]), c, c});
    adj[b].push_back({a, sz(adj[a]) - 1, rcap, rcap});
  }
  ll dfs(int v, int t, ll f) {
    if (v == t || !f) return f;
    for (int& i = ptr[v]; i < sz(adj[v]); i++) {
      Edge& e = adj[v][i];
      if (lvl[e.to] == lvl[v] + 1)
        if (ll p = dfs(e.to, t, min(f, e.c))) {
          e.c -= p, adj[e.to][e.rev].c += p;
          return p;
        }
    }
    return 0;
  }
  ll calc(int s, int t) {
    ll flow = 0; q[0] = s;
    rep(L,0,31) do { // 'int L=30' maybe faster for random data
      lvl = ptr = vi(sz(q));
      int qi = 0, qe = lvl[s] = 1;
      while (qi < qe && !lvl[t]) {
        int v = q[qi++];
        for (Edge e : adj[v])
          if (!lvl[e.to] && e.c >> (30 - L))
            q[qe++] = e.to, lvl[e.to] = lvl[v] + 1;
      }
      while (ll p = dfs(s, t, LLONG_MAX)) flow += p;
    } while (lvl[t]);
    return flow;
  }
  bool leftOfMinCut(int a) { return lvl[a] != 0; }
};
```

MinCut.h

Description: After running max-flow, the left side of a min-cut from s to t is given by all vertices reachable from s, only traversing edges with positive residual capacity.

GlobalMinCut.h

Description: Find a global minimum cut in an undirected graph, as represented by an adjacency matrix.
Time: $\mathcal{O}\left(V^3\right)$

8b0e19, 21 lines

```
pair<int, vi> globalMinCut(vector<vi> mat) {
  pair<int, vi> best = {INT_MAX, {}};
  int n = sz(mat);
  vector<vi> co(n);
  rep(i,0,n) co[i] = {i};
  rep(ph,1,n) {
    vi w = mat[0];
    size_t s = 0, t = 0;
    rep(it,0,n-ph) { // O(V^2) -> O(E log V) with prio. queue
      w[t] = INT_MIN;
      s = t, t = max_element(all(w)) - w.begin();
      rep(i,0,n) w[i] += mat[t][i];
    }
    best = min(best, {w[t] - mat[t][t], co[t]});
    co[s].insert(co[s].end(), all(co[t]));
    rep(i,0,n) mat[s][i] += mat[t][i];
    rep(i,0,n) mat[i][s] = mat[s][i];
    mat[0][t] = INT_MIN;
  }
  return best;
}
```

GomoryHu.h

Description: Given a list of edges representing an undirected flow graph, returns edges of the Gomory-Hu tree. The max flow between any pair of vertices is given by minimum edge weight along the Gomory-Hu tree path.
Time: $\mathcal{O}(V)$ Flow Computations

"PushRelabel.h" 0418b3, 13 lines

```
typedef array<ll, 3> Edge;
vector<Edge> gomoryHu(int N, vector<Edge> ed) {
  vector<Edge> tree;
  vi par(N);
  rep(i,1,N) {
    PushRelabel D(N); // Dinic also works
    for (Edge t : ed) D.addEdge(t[0], t[1], t[2], t[2]);
    tree.push_back({i, par[i], D.calc(i, par[i])});
    rep(j,i+1,N)
      if (par[j] == par[i] && D.leftOfMinCut(j)) par[j] = i;
  }
  return tree;
}
```

7.3 Matching

HopcroftKarp.h

Description: Fast bipartite matching algorithm. Graph g should be a list of neighbors of the left partition, and r should be a vector full of -1's of the same size as the right partition. Returns the size of the matching. $r[i]$ will be the match for vertex i on the right side, or -1 if it's not matched.
Time: $\mathcal{O}\left(E\sqrt{V}\right)$

731cfb, 20 lines

```
int hopcroftKarp(vector<vi>& g, vi& r) {
  int n = sz(g), res = 0;
  vi l(n, -1), q(n), d(n);
  auto dfs = [&](auto f, int u) -> bool {
    int t = exchange(d[u], 0) + 1;
    for (int v : g[u])
      if (r[v] == -1 || (d[r[v]] == t && f(f, r[v])))
        return l[u] = v, r[v] = u, 1;
    return 0;
  };
  for (int t = 0, f = 0;; t = f = 0, d.assign(n, 0)) {
    rep(i,0,n) if (l[i] == -1) q[t++] = i, d[i] = 1;
    rep(i,0,t) for (int v : g[q[i]]) {
      if (r[v] == -1) f = 1;
      else if (!d[r[v]]) d[r[v]] = d[q[i]] + 1, q[t++] = r[v];
    }
    if (!f) return res;
    rep(i,0,n) if (l[i] == -1) res += dfs(dfs, i);
  }
}
```

DFSMatching.h

Description: Simple bipartite matching algorithm. Graph g should be a list of neighbors of the left partition, and $btoa$ should be a vector full of -1's of the same size as the right partition. Returns the size of the matching. $btoa[i]$ will be the match for vertex i on the right side, or -1 if it's not matched.
Usage: `vi btoa(m, -1); dfsMatching(g, btoa);`
Time: $\mathcal{O}(VE)$ 522b98, 22 lines

```
bool find(int j, vector<vi>& g, vi& btoa, vi& vis) {
  if (btoa[j] == -1) return 1;
  vis[j] = 1; int di = btoa[j];
  for (int e : g[di])
    if (!vis[e] && find(e, g, btoa, vis)) {
      btoa[e] = di;
      return 1;
    }
  return 0;
}
int dfsMatching(vector<vi>& g, vi& btoa) {
  vi vis;
  rep(i,0,sz(g)) {
    vis.assign(sz(btoa), 0);
    for (int j : g[i])
      if (find(j, g, btoa, vis)) {
        btoa[j] = i;
        break;
      }
  }
  return sz(btoa) - (int)count(all(btoa), -1);
}
```

MinimumVertexCover.h

Description: Finds a minimum vertex cover in a bipartite graph. The size is the same as the size of a maximum matching, and the complement is a maximum independent set.
"DFSMatching.h" da4196, 20 lines

```
vi cover(vector<vi>& g, int n, int m) {
  vi match(m, -1);
  int res = dfsMatching(g, match);
  vector<bool> lfound(n, true), seen(m);
  for (int it : match) if (it != -1) lfound[it] = false;
  vi q, cover;
  rep(i,0,n) if (lfound[i]) q.push_back(i);
  while (!q.empty()) {
    int i = q.back(); q.pop_back();
    lfound[i] = 1;
    for (int e : g[i]) if (!seen[e] && match[e] != -1) {
      seen[e] = true;
      q.push_back(match[e]);
    }
  }
  rep(i,0,n) if (!lfound[i]) cover.push_back(i);
  rep(i,0,m) if (seen[i]) cover.push_back(n+i);
  assert(sz(cover) == res);
  return cover;
}
```

WeightedMatching.h

Description: Given a weighted bipartite graph, matches every node on the left with a node on the right such that no nodes are in two matchings and the sum of the edge weights is minimal. Takes cost[N][M], where cost[i][j] = cost for L[i] to be matched with R[j], and returns (min cost, match), where L[i] is matched with R[match[i]]. Negate costs for max cost. Requires $N \leq M$.
Time: $\mathcal{O}(N^2M)$ 8f41c7, 24 lines

```
template<class T>
pair<T, vi> weightedMatching(vector<vector<T>> &C) {
  int i = sz(C), m = i ? sz(C[0]) : 0, c, s, r;
  vector<T> dist(m), pot(m);
  vi match(i), rev(m, -1), cols(m), prev(m);
  T d = 0, nd, cost = 0;
  while (i--) {
    rep(c,0,m) dist[c] = C[i][c], cols[c] = c, prev[c] = i;
    for (s = 0;;) {
      rep(j,s,m) {
        c = cols[j], nd = dist[c] - pot[c];
        if (j == s || d > nd) d = nd, swap(cols[s], cols[j]);
      }
      if ((r = rev[c = cols[s++]]) == -1) break;
      rep(j,0,m) if (dist[j] > (nd = C[r][j]-C[r][c]+dist[c]))
        dist[j] = nd, prev[j] = r;
    }
    cost += dist[c];
    while (s--) pot[cols[s]] = dist[cols[s]] - d;
    for (; r != i; swap(c, match[r]))
      r = rev[c] = prev[c];
  }
  return {cost, match};
}
```

GeneralMatching.h

Description: Matching for general graphs. Fails with probability N/mod.
Time: $\mathcal{O}(N^3)$
"../numerical/MatrixInverse-mod.h" cb1912, 40 lines

```
vector<pii> generalMatching(int N, vector<pii>& ed) {
  vector<vector<ll>> mat(N, vector<ll>(N)), A;
  for (pii pa : ed) {
    int a = pa.first, b = pa.second, r = rand() % mod;
    mat[a][b] = r, mat[b][a] = (mod - r) % mod;
  }

  int r = matInv(A = mat), M = 2*N - r, fi, fj;
  assert(r % 2 == 0);

  if (M != N) do {
    mat.resize(M, vector<ll>(M));
    rep(i,0,N) {
      mat[i].resize(M);
      rep(j,N,M) {
        int r = rand() % mod;
        mat[i][j] = r, mat[j][i] = (mod - r) % mod;
      }
    }
  } while (matInv(A = mat) != M);

  vi has(M, 1); vector<pii> ret;
  rep(it,0,M/2) {
    rep(i,0,M) if (has[i])
      rep(j,i+1,M) if (A[i][j] && mat[i][j]) {
        fi = i; fj = j; goto done;
    } assert(0); done:
    if (fj < N) ret.emplace_back(fi, fj);
    has[fi] = has[fj] = 0;
    rep(sw,0,2) {
      ll a = modpow(A[fi][fj], mod-2);
      rep(i,0,M) if (has[i] && A[i][fj]) {
        ll b = A[i][fj] * a % mod;
        rep(j,0,M) A[i][j] = (A[i][j] - A[fi][j] * b) % mod;
      }
      swap(fi,fj);
    }
  }
  return ret;
}
```

7.4 DFS algorithms

SCC.h

Description: Finds strongly connected components in a directed graph. If vertices u, v belong to the same component, we can reach u from v and vice versa.
Usage: `scc(graph, [&](vi& v) { ... })` visits all components in reverse topological order. `comp[i]` holds the component index of a node (a component only has edges to components with lower index). `ncomps` will contain the number of components.
Time: $\mathcal{O}(E+V)$ 76b5c9, 24 lines

```
vi val, comp, z, cont;
int Time, ncomps;
template<class G, class F> int dfs(int j, G& g, F& f) {
  int low = val[j] = ++Time, x; z.push_back(j);
  for (auto e : g[j]) if (comp[e] < 0)
    low = min(low, val[e] ?: dfs(e,g,f));

  if (low == val[j]) {
    do {
      x = z.back(); z.pop_back();
      comp[x] = ncomps;
      cont.push_back(x);
    } while (x != j);
    f(cont); cont.clear();
    ncomps++;
  }
  return val[j] = low;
}
template<class G, class F> void scc(G& g, F f) {
  int n = sz(g);
  val.assign(n, 0); comp.assign(n, -1);
  Time = ncomps = 0;
  rep(i,0,n) if (comp[i] < 0) dfs(i, g, f);
}
```

BiconnectedComponents.h

Description: Finds all biconnected components in an undirected graph, and runs a callback for the edges in each. In a biconnected component there are at least two internally disjoint paths between any two nodes (a cycle exists through them). Note that a node can be in several components. An edge which is not in a component is a bridge, i.e., not part of any cycle.
Usage: `int eid = 0; ed.resize(N);`
`for each edge (a,b) {`
`ed[a].emplace_back(b, eid);`
`ed[b].emplace_back(a, eid++); }`
`bicomps([&](const vi& edgelist) {...});`
Time: $\mathcal{O}(E+V)$ c6b7c7, 32 lines

```
vi num, st;
vector<vector<pii>> ed;
int Time;
template<class F>
int dfs(int at, int par, F& f) {
  int me = num[at] = ++Time, top = me;
  for (auto [y, e] : ed[at]) if (e != par) {
    if (num[y]) {
      top = min(top, num[y]);
      if (num[y] < me)
        st.push_back(e);
    } else {
      int si = sz(st);
      int up = dfs(y, e, f);
      top = min(top, up);
      if (up == me) {
        st.push_back(e);
        f(vi(st.begin() + si, st.end()));
        st.resize(si);
      }
```

```
      else if (up < me) st.push_back(e);
      else { /* e is a bridge */ }
    }
  }
  return top;
}

template<class F>
void bicomps(F f) {
  num.assign(sz(ed), 0);
  rep(i,0,sz(ed)) if (!num[i]) dfs(i, -1, f);
}
```

CentroidDecomposition.h

Description: Todo

11aa82, 114 lines

```
#pragma once
 const int INF = 1e6;
 const int LOG = 18;
 struct CentroidDecomposition{
     vvi tree, cd;
     vi subt, par, ans, dep;
     vector<bool> removed;
     vvi up;
     int root;
     CentroidDecomposition(int n) : tree(n), cd(n), root(-1),
          subt(n), par(n), ans(n, INF), dep(n), removed(n) {
         up.assign(LOG, vi(n, -1));
     }

     void add_edge(int u, int v) {
         tree[u].push_back(v);
         tree[v].push_back(u);
     }

     int dfs(int u, int p = -1) {
         subt[u] = 1;
         for(int v : tree[u]) {
             if(removed[v] || v == p) continue;
             subt[u] += dfs(v, u);
         }
         return subt[u];
     }

     int find_centroid(int u, int comp_sz, int p = -1) {
         for(int v : tree[u]) {
             if(removed[v] || v == p) continue;
             if(2 * subt[v] > comp_sz) return find_centroid(v,
                  comp_sz, u);
         }
         return u;
     }

     void decompose(int u, int p = -1) {
         int comp_sz = dfs(u);
         int centroid = find_centroid(u, comp_sz);
         if(root == -1) root = centroid;
         par[centroid] = p;
         if(p != -1) {
             cd[p].push_back(centroid);
             cd[centroid].push_back(p);
         }
         removed[centroid] = true;
         for(int v : tree[centroid]) {
             if(!removed[v]) decompose(v, centroid);
         }
     }

     void dfs_LCA(int u, int p = -1) {
         if(p != -1) dep[u] = dep[p] + 1;
         up[0][u] = p;
         for(int v : tree[u]) if(v != p) {
             dfs_LCA(v, u);
         }
     }

     void init_LCA(int n) {
         dfs_LCA(0);
         for(int lg = 1; lg < LOG; lg++) {
             for(int i = 0; i < n; i++) {
                 if(up[lg - 1][i] != -1)
                     up[lg][i] = up[lg - 1][up[lg - 1][i]];
             }
         }
     }

     int lift(int u, int len) {
         while(len) {
             int jump = __builtin_ctz(len);
             u = up[jump][u];
             len &= (len - 1);
         }
         return u;
     }

     int LCA(int u, int v) {
         if(dep[u] > dep[v]) swap(u, v);
         v = lift(v, dep[v] - dep[u]);
         if(u == v) return u;
         for(int lg = LOG - 1; lg >= 0; lg--) {
             if(up[lg][u] != up[lg][v]){
                 u = up[lg][u];
                 v = up[lg][v];
             }
         }
         return up[0][u];
     }

     int dist(int u, int v) {
         int lca = LCA(u, v);
         return dep[u] + dep[v] - 2 * dep[lca];
     }

     void update(int u) {
         int fu = u;
         while(u != -1) {
             ans[u] = min(ans[u], dist(fu, u));
             u = par[u];
         }
     }

     int query(int u) {
         int fu = u;
         int res = INF;
         while(u != -1) {
             res = min(res, ans[u] + dist(u, fu));
             u = par[u];
         }
         return res;
     }

 };
```

2sat.h

Description: Calculates a valid assignment to boolean variables a, b, c,... to a 2-SAT problem, so that an expression of the type $(a||b)\&\&(!a||c)\&\&(d||!b)\&\&\ldots$ becomes true, or reports that it is unsatisfiable. Negated variables are represented by bit-inversions (~x).

Usage: TwoSat ts(number of boolean variables);
ts.either(0, ~3); // Var 0 is true or var 3 is false
ts.setValue(2); // Var 2 is true
ts.atMostOne({0,~1,2}); // <= 1 of vars 0, ~1 and 2 are true
ts.solve(); // Returns true iff it is solvable
ts.values[0..N-1] holds the assigned values to the vars

Time: $\mathcal{O}(N + E)$, where N is the number of boolean variables, and E is the number of clauses.

5f9706, 56 lines

```
struct TwoSat {
  int N;
  vector<vi> gr;
  vi values; // 0 = false, 1 = true

  TwoSat(int n = 0) : N(n), gr(2*n) {}

  int addVar() { // (optional)
    gr.emplace_back();
    gr.emplace_back();
    return N++;
  }

  void either(int f, int j) {
    f = max(2*f, -1-2*f);
    j = max(2*j, -1-2*j);
    gr[f].push_back(j^1);
    gr[j].push_back(f^1);
  }
  void setValue(int x) { either(x, x); }

  void atMostOne(const vi& li) { // (optional)
    if (sz(li) <= 1) return;
    int cur = ~li[0];
    rep(i,2,sz(li)) {
      int next = addVar();
      either(cur, ~li[i]);
      either(cur, next);
      either(~li[i], next);
      cur = ~next;
    }
    either(cur, ~li[1]);
  }

  vi val, comp, z; int time = 0;
  int dfs(int i) {
    int low = val[i] = ++time, x; z.push_back(i);
    for(int e : gr[i]) if (!comp[e])
      low = min(low, val[e] ?: dfs(e));
    if (low == val[i]) do {
      x = z.back(); z.pop_back();
      comp[x] = low;
      if (values[x>>1] == -1)
        values[x>>1] = x&1;
    } while (x != i);
    return val[i] = low;
  }

  bool solve() {
    values.assign(N, -1);
    val.assign(2*N, 0); comp = val;
    rep(i,0,2*N) if (!comp[i]) dfs(i);
    rep(i,0,N) if (comp[2*i] == comp[2*i+1]) return 0;
    return 1;
  }
};
```

EulerWalk.h

Description: Eulerian undirected/directed path/cycle algorithm. Input should be a vector of (dest, global edge index), where for undirected graphs, forward/backward edges have the same index. Returns a list of nodes in the Eulerian path/cycle with src at both start and end, or empty list if no cycle/path exists. To get edge indices back, add .second to s and ret.
Time: $\mathcal{O}(V+E)$

780b64, 15 lines

```
vi eulerWalk(vector<vector<pii>>& gr, int nedges, int src=0) {
  int n = sz(gr);
  vi D(n), its(n), eu(nedges), ret, s = {src};
  D[src]++; // to allow Euler paths, not just cycles
  while (!s.empty()) {
    int x = s.back(), y, e, &it = its[x], end = sz(gr[x]);
    if (it == end){ ret.push_back(x); s.pop_back(); continue; }
    tie(y, e) = gr[x][it++];
    if (!eu[e]) {
      D[x]--, D[y]++;
      eu[e] = 1; s.push_back(y);
    }}
  for (int x : D) if (x < 0 || sz(ret) != nedges+1) return {};
  return {ret.rbegin(), ret.rend()};
}
```

EulerianWalkJulioUndir.h

Description: Eulerian walk on undirected graphs, returns path
Time: $\mathcal{O}(N+M)$

ebdc03, 55 lines

```
struct EulerianUndirected { // eulerian walk(Hierholzer)
    int n, m;
    vector<vii> g;
    vi path, degree;
    vector<bool> seen;

    EulerianUndirected(int n_, int m_) : n(n_), m(m_) {
        g.resize(n);
        seen.assign(m, false);
        degree.resize(n);
    }

    void add_edge(int u, int v, int i) {
        g[u].emplace_back(v, i);
        g[v].emplace_back(u, i);
        degree[u]++;
        degree[v]++;
    }

    void dfs(int node) {
        while(!g[node].empty()) {
            auto [son, idx] = g[node].back();
            g[node].pop_back();
            if(seen[idx]) continue;
            seen[idx] = true;
            dfs(son);
        }
        path.push_back(node);
    }

    vi solve() {
        int cnt_odd = 0;
        for(int i = 0; i < n; i++) {
            if(degree[i] % 2) {
                cnt_odd++;
            }
        }
        if(cnt_odd > 2) return {};
        int start = -1;
        if(cnt_odd == 2) {
            for(int i = 0; i < n; i++) {
                if(degree[i] % 2) start = i;
            }
        }else{
            for(int i = 0; i < n; i++) {
                if(degree[i]) start = i;
            }
        }
        assert(start != -1);
        dfs(start);
        if((int)path.size() != m + 1) return {};
        return path;
    }

};
```

EulerianWalkJulioDirected.h

Description: Eulerian walk on directed graphs, returns path
Time: $\mathcal{O}(N+M)$

1a1bb7, 57 lines

```
struct EulerianDirected {
    int n, m;
    vvi g;
    vi in, out;
    vi path;

    EulerianDirected(int n_, int m_) : n(n_), m(m_) {
        g.resize(n);
        in.resize(n);
        out.resize(n);
    }

    void add_edge(int u, int v) {
        g[u].push_back(v);
        in[v]++;
        out[u]++;
    }

    void dfs(int node) {
        while(!g[node].empty()) {
            int son = g[node].back();
            g[node].pop_back();
            dfs(son);
        }
        path.push_back(node);
    }

    vi solve() {
        int in_out = -1, out_in = -1;
        for(int i = 0; i < n; i++) {
            if(abs(in[i] - out[i]) > 1) return {};
            if(in[i] == out[i] + 1) {
                if(in_out == -1) in_out = i;
                else return {};
            }
            if(out[i] == in[i] + 1) {
                if(out_in == -1) out_in = i;
                else return {};
            }
        }
        if(in_out != -1) {
            if(out_in == -1) return {};
            dfs(out_in);
        }else{
            for(int i = 0; i < n; i++) {
                if(in[i]) {
                    dfs(i);
                    break;
                }
            }
        }
        if((int)path.size() != m + 1) return {};
        reverse(path.begin(), path.end());
        return path;
    }

};
```

7.5 Coloring

EdgeColoring.h

Description: Given a simple, undirected graph with max degree D, computes a $(D+1)$-coloring of the edges such that no neighboring edges share a color. (D-coloring is NP-hard, but can be done for bipartite graphs by repeated matchings of max-degree nodes.)
Time: $\mathcal{O}(NM)$

e210e2, 31 lines

```
vi edgeColoring(int N, vector<pii> eds) {
  vi cc(N + 1), ret(sz(eds)), fan(N), free(N), loc;
  for (pii e : eds) ++cc[e.first], ++cc[e.second];
  int u, v, ncols = *max_element(all(cc)) + 1;
  vector<vi> adj(N, vi(ncols, -1));
  for (pii e : eds) {
    tie(u, v) = e;
    fan[0] = v;
    loc.assign(ncols, 0);
    int at = u, end = u, d, c = free[u], ind = 0, i = 0;
    while (d = free[v], !loc[d] && (v = adj[u][d]) != -1)
      loc[d] = ++ind, cc[ind] = d, fan[ind] = v;
    cc[loc[d]] = c;
    for (int cd = d; at != -1; cd ^= c ^ d, at = adj[at][cd])
      swap(adj[at][cd], adj[end = at][cd ^ c ^ d]);
    while (adj[fan[i]][d] != -1) {
      int left = fan[i], right = fan[++i], e = cc[i];
      adj[u][e] = left;
      adj[left][e] = u;
      adj[right][e] = -1;
      free[right] = e;
    }
    adj[u][d] = fan[i];
    adj[fan[i]][d] = u;
    for (int y : {fan[0], u, end})
      for (int& z = free[y] = 0; adj[y][z] != -1; z++);
  }
  rep(i,0,sz(eds))
    for (tie(u, v) = eds[i]; adj[u][ret[i]] != v;) ++ret[i];
  return ret;
}
```

7.6 Heuristics

MaximalCliques.h

Description: Runs a callback for all maximal cliques in a graph (given as a symmetric bitset matrix; self-edges not allowed). Callback is given a bitset representing the maximal clique.
Time: $\mathcal{O}\left(3^{n/3}\right)$, much faster for sparse graphs

b0d5b1, 12 lines

```
typedef bitset<128> B;
template<class F>
void cliques(vector<B>& eds, F f, B P = ~B(), B X={}, B R={}) {
  if (!P.any()) { if (!X.any()) f(R); return; }
  auto q = (P | X)._Find_first();
  auto cands = P & ~eds[q];
  rep(i,0,sz(eds)) if (cands[i]) {
    R[i] = 1;
    cliques(eds, f, P & eds[i], X & eds[i], R);
    R[i] = P[i] = 0; X[i] = 1;
  }
}
```

MaximumClique.h

Description: Quickly finds a maximum clique of a graph (given as symmetric bitset matrix; self-edges not allowed). Can be used to find a maximum independent set by finding a clique of the complement graph.
Time: Runs in about 1s for n=155 and worst case random graphs (p=.90). Runs faster for sparse graphs.

f7c0bc, 49 lines

```
typedef vector<bitset<200>> vb;
struct Maxclique {
  double limit=0.025, pk=0;
  struct Vertex { int i, d=0; };
  typedef vector<Vertex> vv;
  vb e;
  vv V;
  vector<vi> C;
  vi qmax, q, S, old;
  void init(vv& r) {
    for (auto& v : r) v.d = 0;
    for (auto& v : r) for (auto j : r) v.d += e[v.i][j.i];
    sort(all(r), [](auto a, auto b) { return a.d > b.d; });
    int mxD = r[0].d;
    rep(i,0,sz(r)) r[i].d = min(i, mxD) + 1;
  }
  void expand(vv& R, int lev = 1) {
    S[lev] += S[lev - 1] - old[lev];
    old[lev] = S[lev - 1];
    while (sz(R)) {
      if (sz(q) + R.back().d <= sz(qmax)) return;
      q.push_back(R.back().i);
      vv T;
      for(auto v:R) if (e[R.back().i][v.i]) T.push_back({v.i});
      if (sz(T)) {
        if (S[lev]++ / ++pk < limit) init(T);
        int j = 0, mxk = 1, mnk = max(sz(qmax) - sz(q) + 1, 1);
        C[1].clear(), C[2].clear();
        for (auto v : T) {
          int k = 1;
          auto f = [&](int i) { return e[v.i][i]; };
          while (any_of(all(C[k]), f)) k++;
          if (k > mxk) mxk = k, C[mxk + 1].clear();
          if (k < mnk) T[j++].i = v.i;
          C[k].push_back(v.i);
        }
        if (j > 0) T[j - 1].d = 0;
        rep(k,mnk,mxk + 1) for (int i : C[k])
          T[j].i = i, T[j++].d = k;
        expand(T, lev + 1);
      } else if (sz(q) > sz(qmax)) qmax = q;
      q.pop_back(), R.pop_back();
    }
  }
  vi maxClique() { init(V), expand(V); return qmax; }
  Maxclique(vb conn) : e(conn), C(sz(e)+1), S(sz(C)), old(S) {
    rep(i,0,sz(e)) V.push_back({i});
  }
};
```

MaximumIndependentSet.h

Description: To obtain a maximum independent set of a graph, find a max clique of the complement. If the graph is bipartite, see MinimumVertexCover.

7.7 Trees

BinaryLifting.h

Description: Calculate power of two jumps in a tree, to support fast upward jumps and LCAs. Assumes the root node points to itself.
Time: construction $\mathcal{O}(N \log N)$, queries $\mathcal{O}(\log N)$

bfce85, 25 lines

```
vector<vi> treeJump(vi& P){
  int on = 1, d = 1;
  while(on < sz(P)) on *= 2, d++;
  vector<vi> jmp(d, P);
  rep(i,1,d) rep(j,0,sz(P))
    jmp[i][j] = jmp[i-1][jmp[i-1][j]];
  return jmp;
}

int jmp(vector<vi>& tbl, int nod, int steps){
  rep(i,0,sz(tbl))
    if(steps&(1<<i)) nod = tbl[i][nod];
  return nod;
}

int lca(vector<vi>& tbl, vi& depth, int a, int b) {
  if (depth[a] < depth[b]) swap(a, b);
  a = jmp(tbl, a, depth[a] - depth[b]);
  if (a == b) return a;
  for (int i = sz(tbl); i--;) {
    int c = tbl[i][a], d = tbl[i][b];
    if (c != d) a = c, b = d;
  }
  return tbl[0][a];
}
```

LCA.h

Description: Data structure for computing lowest common ancestors in a tree (with 0 as root). C should be an adjacency list of the tree, either directed or undirected.
Time: $\mathcal{O}(N \log N + Q)$

"../data-structures/RMQ.h" 0f62fb, 21 lines

```
struct LCA {
  int T = 0;
  vi time, path, ret;
  RMQ<int> rmq;

  LCA(vector<vi>& C) : time(sz(C)), rmq((dfs(C,0,-1), ret)) {}
  void dfs(vector<vi>& C, int v, int par) {
    time[v] = T++;
    for (int y : C[v]) if (y != par) {
      path.push_back(v), ret.push_back(time[v]);
      dfs(C, y, v);
    }
  }

  int lca(int a, int b) {
    if (a == b) return a;
    tie(a, b) = minmax(time[a], time[b]);
    return path[rmq.query(a, b)];
  }
  //dist(a,b){return depth[a] + depth[b] - 2*depth[lca(a,b)];}
};
```

VirtualTree.h

Description: Process the virtual tree of some vertices. Needs to process tin,lca, and is ancestor.
Time: $\mathcal{O}(N \log N)$, because of sorting

7feebf, 23 lines

```
int query(vi &v) {
    sort(all(v), [](int i, int j) { return tin[i] < tin[j]; });
    int siz = sz(v);
    rep(i,1,siz) v.push_back(LCA(v[i], v[i - 1])) ;

    sort(all(v), [](int i, int j) { return tin[i] < tin[j]; });
    v.erase(unique(v.begin(), v.end()), v.end());

    int root = v[0];
    vi st(1, root);
    rep(i,1,sz(v)) {
        while(st.size() && !anc(st.back(), v[i])) st.pop_back()
            ;
        vt[st.back()].push_back(v[i]);
        st.push_back(v[i]);
    }

    // solve
    int ans = 0 ;
    dfs2(root);
    // clear
    for(int i : v) vt[i].clear();
    return ans;
}
```

HLDLechugon.h

Description: Get the HLD from a tree.
Time: $\mathcal{O}(N \log N)$

a4ef46, 105 lines

```
const int N = 1e5 + 10 ; // Nro de Nodos
const int LOG = 18;
int up[N][LOG];
int subt[N];
int h[N];
int chain[N];
int pos;
int in[N];
vi G[N];

/*NSQ -> Funcion de consulta en rango del segment tree */
/*UPD -> Funcion de actualizacion en rango del segment tree*/
struct node{

};

void dfs(int u = 0, int pt = -1){
    subt[u] = 1;
    for(int v: G[u]){if(v == pt) continue;
        h[v] = h[u] + 1;
        up[v][0] = u;
        for(int i = 1; i < LOG; i++) up[v][i] = up[up[v][i -
            1]][i - 1];
        dfs(v , u);
        subt[u] += subt[v];
    }
}

void HLD(int u = 0, int pt = -1){
    in[u] = ++pos;
    /*Actualizacion segun logica*/
    //idx[pos] = u;

    //ids[vals[u]].insert(pos);

    int heavy = -1;
    int mx = 0;
    for(int v : G[u]){ if(v == pt) continue;
        if(subt[v] > mx){
            heavy = v;
            mx = subt[v];
        }
    }
    if(heavy != -1){
        chain[heavy] = chain[u];
        HLD(heavy , u);
    }
    for(int v : G[u]){if(v == pt || v == heavy) continue;
        HLD(v , u);
    }
```

```
}

int kth(int u , int k){
    for(int i = 0; i < LOG; i++) if((k >> i) & 1) u = up[u][i];
    return u;
}

int lca(int u , int v){
    if(h[u] < h[v]) swap(u , v);
    u = kth(u , h[u] - h[v]);
    if(u == v) return v;
    for(int i = LOG - 1; i >= 0; i--){
        if(up[u][i] != up[v][i]){
            u = up[u][i];
            v = up[v][i];
        }
    }
    return up[u][0];
}

node pathquery(int u , int anc){
    node res;
    while(h[u] > h[anc]){
        int top = chain[u];
        if(h[top] <= h[anc]) /*Acumulacion de la respuesta sin
             tomar en cuenta al LCA */
            top = kth(u , h[u] - h[anc] - 1);
        // res = res + nsq(in[top] , in[u]);
        u = up[top][0];
    }
    return res;
}
/*Query en path u y v*/
int query(int u, int v){
    int  anc  = lca(u , v);
    node left  = pathquery(u, anc);
    node right = rsq(in[anc], in[anc]) + pathquery(v , anc);
    return merge({right.ans , left.ans , left.pref + right.pref
        });
}
/*Update de u al LCA */
void pathUpd(int u , int anc, int val){
    while(h[anc] < h[u]){
        int top = chain[u];
        if(h[top] <= h[anc]){ /*Update sin actualizar el valor
             del LCA*/
            top = kth(u, h[u] - h[anc] - 1);
        }
        upd(in[top], in[u], val);
        u = up[top][0];
    }
}
/*Update en path u y v*/
void updQuery(int u, int v, int val){
    int anc = lca(u , v);
    upd(in[anc] , in[anc] , val);
    pathUpd(u , anc, val);
    pathUpd(v , anc, val);
}
```

LinkCutTree.h

Description: Represents a forest of unrooted trees. You can add and remove edges (as long as the result is still a forest), and check whether two nodes are in the same tree.
Time: All operations take amortized $\mathcal{O}(\log N)$.

0fb462, 90 lines

```
struct Node { // Splay tree. Root's pp contains tree's parent.
  Node *p = 0, *pp = 0, *c[2];
  bool flip = 0;
  Node() { c[0] = c[1] = 0; fix(); }
  void fix() {
    if (c[0]) c[0]->p = this;
    if (c[1]) c[1]->p = this;
    // (+ update sum of subtree elements etc. if wanted)
  }
  void pushFlip() {
    if (!flip) return;
    flip = 0; swap(c[0], c[1]);
    if (c[0]) c[0]->flip ^= 1;
    if (c[1]) c[1]->flip ^= 1;
  }
  int up() { return p ? p->c[1] == this : -1; }
  void rot(int i, int b) {
    int h = i ^ b;
    Node *x = c[i], *y = b == 2 ? x : x->c[h], *z = b ? y : x;
    if ((y->p = p)) p->c[up()] = y;
    c[i] = z->c[i ^ 1];
    if (b < 2) {
      x->c[h] = y->c[h ^ 1];
      y->c[h ^ 1] = x;
    }
    z->c[i ^ 1] = this;
    fix(); x->fix(); y->fix();
    if (p) p->fix();
    swap(pp, y->pp);
  }
  void splay() {
    for (pushFlip(); p; ) {
      if (p->p) p->p->pushFlip();
      p->pushFlip(); pushFlip();
      int c1 = up(), c2 = p->up();
      if (c2 == -1) p->rot(c1, 2);
      else p->p->rot(c2, c1 != c2);
    }
  }
  Node* first() {
    pushFlip();
    return c[0] ? c[0]->first() : (splay(), this);
  }
};

struct LinkCut {
  vector<Node> node;
  LinkCut(int N) : node(N) {}

  void link(int u, int v) { // add an edge (u, v)
    assert(!connected(u, v));
    makeRoot(&node[u]);
    node[u].pp = &node[v];
  }
  void cut(int u, int v) { // remove an edge (u, v)
    Node *x = &node[u], *top = &node[v];
    makeRoot(top); x->splay();
    assert(top == (x->pp ?: x->c[0]));
    if (x->pp) x->pp = 0;
    else {
      x->c[0] = top->p = 0;
      x->fix();
    }
  }
  bool connected(int u, int v) { // are u, v in the same tree?
    Node* nu = access(&node[u])->first();
    return nu == access(&node[v])->first();
  }
  void makeRoot(Node* u) {
    access(u);
    u->splay();
    if(u->c[0]) {
      u->c[0]->p = 0;
      u->c[0]->flip ^= 1;
      u->c[0]->pp = u;
      u->c[0] = 0;
      u->fix();
    }
  }
  Node* access(Node* u) {
    u->splay();
    while (Node* pp = u->pp) {
      pp->splay(); u->pp = 0;
      if (pp->c[1]) {
        pp->c[1]->p = 0; pp->c[1]->pp = pp; }
      pp->c[1] = u; pp->fix(); u = pp;
    }
    return u;
  }
};
```

DirectedMST.h

Description: Finds a minimum spanning tree/arborescence of a directed graph, given a root node. If no MST exists, returns -1.
Time: $\mathcal{O}(E \log V)$

"../data-structures/UnionFindRollback.h" 39e620, 60 lines

```
struct Edge { int a, b; ll w; };
struct Node {
  Edge key;
  Node *l, *r;
  ll delta;
  void prop() {
    key.w += delta;
    if (l) l->delta += delta;
    if (r) r->delta += delta;
    delta = 0;
  }
  Edge top() { prop(); return key; }
};
Node *merge(Node *a, Node *b) {
  if (!a || !b) return a ?: b;
  a->prop(), b->prop();
  if (a->key.w > b->key.w) swap(a, b);
  swap(a->l, (a->r = merge(b, a->r)));
  return a;
}
void pop(Node*& a) { a->prop(); a = merge(a->l, a->r); }

pair<ll, vi> dmst(int n, int r, vector<Edge>& g) {
  RollbackUF uf(n);
  vector<Node*> heap(n);
  for (Edge e : g) heap[e.b] = merge(heap[e.b], new Node{e});
  ll res = 0;
  vi seen(n, -1), path(n), par(n);
  seen[r] = r;
  vector<Edge> Q(n), in(n, {-1,-1}), comp;
  deque<tuple<int, int, vector<Edge>>> cycs;
  rep(s,0,n) {
    int u = s, qi = 0, w;
    while (seen[u] < 0) {
      if (!heap[u]) return {-1,{}};
      Edge e = heap[u]->top();
      heap[u]->delta -= e.w, pop(heap[u]);
      Q[qi] = e, path[qi++] = u, seen[u] = s;
      res += e.w, u = uf.find(e.a);
      if (seen[u] == s) {
        Node* cyc = 0;
        int end = qi, time = uf.time();
        do cyc = merge(cyc, heap[w = path[--qi]]);
        while (uf.join(u, w));
        u = uf.find(u), heap[u] = cyc, seen[u] = -1;
```

```
        cycs.push_front({u, time, {&Q[qi], &Q[end]}});
      }
    }
    rep(i,0,qi) in[uf.find(Q[i].b)] = Q[i];
  }

  for (auto& [u,t,comp] : cycs) { // restore sol (optional)
    uf.rollback(t);
    Edge inEdge = in[u];
    for (auto& e : comp) in[uf.find(e.b)] = e;
    in[uf.find(inEdge.b)] = inEdge;
  }
  rep(i,0,n) par[i] = in[i].a;
  return {res, par};
}
```

IncrementalMST.h

Description: Returns the cost of the edge that gets removed from the tree
Time: $\mathcal{O}(logN)$

f668a7, 37 lines

```
const int INF = 1e9;
struct BottleneckTree {
  vector<int> link, cost;   // all inserted costs must be < INF
  BottleneckTree(int n) : link(n, 0), cost(n, INF) {
    link[0] = -1; cost[0] = INF + 1;
  }
  void rot(int x) {
    int p = link[x], g = link[p];
    swap(cost[x], cost[p]);
    link[x] = g, link[p] = x;
  }
  void skip(int x) { link[x] = link[link[x]]; }
  void access(int x) {
    for (int p = link[x]; p != -1; p = link[x]) {
      int g = link[p];
      if (cost[x] <= cost[p]) rot(x);                    // (A)
      else if (cost[p] > cost[g]) skip(p), skip(x);      // (B)
      else if (cost[g] <= cost[x]) rot(p), skip(x);      // (C)
      else skip(x);                                      // (D)
    }
  }
  int Query(int x, int y) {       // x != y; INF if disconnected
    access(x); access(y);
    return cost[x];
  }
  int AddEdge(int x, int y, int c) {   // x != y
    access(x); access(y);
    if (cost[x] > c) swap(cost[x], c);
    return c;
  }
};

void example() {
    long long total = 0;
    int r = bt.AddEdge(x, y, c);
    total += (r == INF) ? c : c - r;   // if the edge didn't
        enter, r == c
}
```

7.8 Math

7.8.1 Number of Spanning Trees

Create an $N \times N$ matrix `mat`, and for each edge $a \to b \in G$, do `mat[a][b]--, mat[b][b]++` (and `mat[b][a]--, mat[a][a]++` if G is undirected). Remove the ith row and column and take the determinant; this yields the number of directed spanning trees rooted at i (if G is undirected, remove any row/column).

7.8.2 Erdős–Gallai theorem

A simple graph with node degrees $d_1 \geq \cdots \geq d_n$ exists iff $d_1 + \cdots + d_n$ is even and for every $k = 1 \ldots n$,

$$\sum_{i=1}^{k} d_i \leq k(k-1) + \sum_{i=k+1}^{n} \min(d_i, k).$$

7.8.3 Vértices que pertenecen a todos los maximum matching bipartitos

Crea un grafo auxiliar. Dirige las aristas no emparejadas de $L \to R$ y las emparejadas de $R \to L$. Calcula Z_L, vértices que alcanzables desde vértices libres en L. De forma análoga calcula Z_R, el conjunto buscado es $(L - Z_L) \cup (R - Z_R)$.

7.8.4 L-R Flow

Flow with demands. Nuevos vértices S' y T'. Reemplaza las aristas (u, v, l, r) por tres aristas: $(u, v, r-l)$, (S', v, l) y (u, T', l). Una arista más (T, S, ∞). Corre un primer maxflow de S' a T', si es menor a la suma de todos los l, el flujo buscado no existe. Corre un segundo maxflow de S a T, este es el flujo máximo buscado originalmente.

7.8.5 Cow Game

Resuelve un problema de maximización. Si se tienen desigualdades $d_v \leq d_u + c$, puedes construir un grafo con aristas $u \to v$ con peso c. Maximiza $a_t - a_s$ usando BellmanFord. Si no existe solución, existe un ciclo negativo o s no alcanza a t.

Geometry (8)

8.1 Geometric primitives

Point.h


Description: Class to handle points in the plane. T can be e.g. double or long long. (Avoid int.)

47ec0a, 28 lines

```
template <class T> int sgn(T x) { return (x > 0) - (x < 0); }
template<class T>
struct Point {
  typedef Point P;
  T x, y;
  explicit Point(T x=0, T y=0) : x(x), y(y) {}
  bool operator<(P p) const { return tie(x,y) < tie(p.x,p.y); }
  bool operator==(P p) const { return tie(x,y)==tie(p.x,p.y); }
  P operator+(P p) const { return P(x+p.x, y+p.y); }
  P operator-(P p) const { return P(x-p.x, y-p.y); }
  P operator*(T d) const { return P(x*d, y*d); }
  P operator/(T d) const { return P(x/d, y/d); }
  T dot(P p) const { return x*p.x + y*p.y; }
  T cross(P p) const { return x*p.y - y*p.x; }
  T cross(P a, P b) const { return (a-*this).cross(b-*this); }
  T dist2() const { return x*x + y*y; }
  double dist() const { return sqrt((double)dist2()); }
  // angle to x-axis in interval [-pi, pi]
  double angle() const { return atan2(y, x); }
  P unit() const { return *this/dist(); } // makes dist()=1
  P perp() const { return P(-y, x); } // rotates +90 degrees
  P normal() const { return perp().unit(); }
  // returns point rotated 'a' radians ccw around the origin
  P rotate(double a) const {
    return P(x*cos(a)-y*sin(a),x*sin(a)+y*cos(a)); }
  friend ostream& operator<<(ostream& os, P p) {
    return os << "(" << p.x << "," << p.y << ")"; }
};
```

lineDistance.h

Description:
Returns the signed distance between point p and the line containing points a and b. Positive value on left side and negative on right as seen from a towards b. a==b gives nan. P is supposed to be Point<T> or Point3D<T> where T is e.g. double or long long. It uses products in intermediate steps so watch out for overflow if using int or long long. Using Point3D will always give a non-negative distance. For Point3D, call .dist on the result of the cross product.




"Point.h" 53630a, 4 lines

```
template<class P>
double lineDist(P a, P b, P p) {
  return (double)(b-a).cross(p-a)/(b-a).dist();
}
```

SegmentDistance.h

Description:
Returns the shortest distance between point p and the line segment from point s to e.
Usage: `Point<double> a, b(2,2), p(1,1);`
`bool onSegment = segDist(a,b,p) < 1e-10;`




"Point.h" d5f39f, 6 lines

```
typedef Point<double> P;
double segDist(P s, P e, P p) {
  if (s==e) return (p-s).dist();
  auto d = (e-s).dist2(), t = min(d,max(.0,(p-s).dot(e-s)));
  return ((p-s)*d-(e-s)*t).dist()/d;
}
```

SegmentIntersection.h

Description:
If a unique intersection point between the line segments going from s1 to e1 and from s2 to e2 exists then it is returned. If no intersection point exists an empty vector is returned. If infinitely many exist a vector with 2 elements is returned, containing the endpoints of the common line segment. The wrong position will be returned if P is Point<ll> and the intersection point does not have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow if using int or long long.
Usage: `vector<P> inter = segInter(s1,e1,s2,e2);`
`if (sz(inter)==1)`
`cout << "segments intersect at " << inter[0] << endl;`




"Point.h", "OnSegment.h" 9d57f2, 13 lines

```
template<class P> vector<P> segInter(P a, P b, P c, P d) {
  auto oa = c.cross(d, a), ob = c.cross(d, b),
       oc = a.cross(b, c), od = a.cross(b, d);
  // Checks if intersection is single non-endpoint point.
```

```
  if (sgn(oa) * sgn(ob) < 0 && sgn(oc) * sgn(od) < 0)
    return {(a * ob - b * oa) / (ob - oa)};
  set<P> s;
  if (onSegment(c, d, a)) s.insert(a);
  if (onSegment(c, d, b)) s.insert(b);
  if (onSegment(a, b, c)) s.insert(c);
  if (onSegment(a, b, d)) s.insert(d);
  return {all(s)};
}
```

lineIntersection.h

Description:
If a unique intersection point of the lines going through s1,e1 and s2,e2 exists {1, point} is returned. If no intersection point exists {0, (0,0)} is returned and if infinitely many exists {-1, (0,0)} is returned. The wrong position will be returned if P is Point<ll> and the intersection point does not have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow if using int or ll.



Usage:
```
auto res = lineInter(s1,e1,s2,e2);
if (res.first == 1)
cout << "intersection point at " << res.second << endl;
```

"Point.h" a01f81, 8 lines

```
template<class P>
pair<int, P> lineInter(P s1, P e1, P s2, P e2) {
  auto d = (e1 - s1).cross(e2 - s2);
  if (d == 0) // if parallel
    return {-(s1.cross(e1, s2) == 0), P(0, 0)};
  auto p = s2.cross(e1, e2), q = s2.cross(e2, s1);
  return {1, (s1 * p + e1 * q) / d};
}
```

sideOf.h

Description: Returns where p is as seen from s towards e. 1/0/-1 $\Leftrightarrow$ left/on line/right. If the optional argument *eps* is given 0 is returned if p is within distance *eps* from the line. P is supposed to be Point<T> where T is e.g. double or long long. It uses products in intermediate steps so watch out for overflow if using int or long long.

Usage:
```
bool left = sideOf(p1,p2,q)==1;
```

"Point.h" ca4665, 9 lines

```
template<class P>
int sideOf(P s, P e, P p) { return sgn(s.cross(e, p)); }

template<class P>
int sideOf(P s, P e, P p, double eps) {
  auto a = (e-s).cross(p-s);
  double l = (e-s).dist()*eps;
  return (a > l) - (a < -l);
}
```

OnSegment.h

Description: Returns true iff p lies on the line segment from s to e. Use `(segDist(s,e,p)<=epsilon)` instead when using Point<double>.


"Point.h" c597e8, 3 lines

```
template<class P> bool onSegment(P s, P e, P p) {
  return p.cross(s, e) == 0 && (s - p).dot(e - p) <= 0;
}
```

linearTransformation.h

Description:

Apply the linear transformation (translation, rotation and scaling) which takes line p0-p1 to line q0-q1 to point r.



"Point.h" 7871e9, 5 lines

```
typedef Point<double> P;
P linearTransformation(P p0, P p1, P q0, P q1, P r) {
  P dp = p1-p0, dq = q1-q0, num(dp.cross(dq), dp.dot(dq));
  return q0 + P((r-p0).cross(num), (r-p0).dot(num))/dp.dist2();
}
```

LineProjectionReflection.h

Description: Projects point p onto line ab. Set refl=true to get reflection of point p across line ab instead. The wrong point will be returned if P is an integer point and the desired point doesn't have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow.

"Point.h" b5562d, 5 lines

```
template<class P>
P lineProj(P a, P b, P p, bool refl=false) {
  P v = b - a;
  return p - v.perp()*(1+refl)*v.cross(p-a)/v.dist2();
}
```

Angle.h

Description: A class for ordering angles (as represented by int points and a number of rotations around the origin). Useful for rotational sweeping. Sometimes also represents points or vectors.

Usage:
```
vector<Angle> v = {w[0], w[0].t360() ...}; // sorted
int j = 0; rep(i,0,n) { while (v[j] < v[i].t180()) ++j; }
// sweeps j such that (j-i) represents the number of positively
oriented triangles with vertices at 0 and i
```

0f0602, 35 lines

```
struct Angle {
  int x, y;
  int t;
  Angle(int x, int y, int t=0) : x(x), y(y), t(t) {}
  Angle operator-(Angle b) const { return {x-b.x, y-b.y, t}; }
  int half() const {
    assert(x || y);
    return y < 0 || (y == 0 && x < 0);
  }
  Angle t90() const { return {-y, x, t + (half() && x >= 0)}; }
  Angle t180() const { return {-x, -y, t + half()}; }
  Angle t360() const { return {x, y, t + 1}; }
};
bool operator<(Angle a, Angle b) {
  // add a.dist2() and b.dist2() to also compare distances
  return make_tuple(a.t, a.half(), a.y * (ll)b.x) <
         make_tuple(b.t, b.half(), a.x * (ll)b.y);
}

// Given two points, this calculates the smallest angle between
// them, i.e., the angle that covers the defined line segment.
pair<Angle, Angle> segmentAngles(Angle a, Angle b) {
  if (b < a) swap(a, b);
  return (b < a.t180() ?
          make_pair(a, b) : make_pair(b, a.t360()));
}
Angle operator+(Angle a, Angle b) { // point a + vector b
  Angle r(a.x + b.x, a.y + b.y, a.t);
  if (a.t180() < r) r.t--;
  return r.t180() < a ? r.t360() : r;
}
Angle angleDiff(Angle a, Angle b) { // angle b - angle a
  int tu = b.t - a.t; a.t = b.t;
  return {a.x*b.x + a.y*b.y, a.x*b.y - a.y*b.x, tu - (b < a)};
}
```

8.2 Circles

CircleIntersection.h

Description: Computes the pair of points at which two circles intersect. Returns false in case of no intersection.

"Point.h" 84d6d3, 11 lines

```
typedef Point<double> P;
bool circleInter(P a,P b,double r1,double r2,pair<P, P>* out) {
  if (a == b) { assert(r1 != r2); return false; }
  P vec = b - a;
  double d2 = vec.dist2(), sum = r1+r2, dif = r1-r2,
         p = (d2 + r1*r1 - r2*r2)/(d2*2), h2 = r1*r1 - p*p*d2;
  if (sum*sum < d2 || dif*dif > d2) return false;
  P mid = a + vec*p, per = vec.perp() * sqrt(fmax(0, h2) / d2);
  *out = {mid + per, mid - per};
  return true;
}
```

CircleTangents.h

Description: Finds the external tangents of two circles, or internal if r2 is negated. Can return 0, 1, or 2 tangents – 0 if one circle contains the other (or overlaps it, in the internal case, or if the circles are the same); 1 if the circles are tangent to each other (in which case .first = .second and the tangent line is perpendicular to the line between the centers). .first and .second give the tangency points at circle 1 and 2 respectively. To find the tangents of a circle with a point set r2 to 0.

"Point.h" b0153d, 13 lines

```
template<class P>
vector<pair<P, P>> tangents(P c1, double r1, P c2, double r2) {
  P d = c2 - c1;
  double dr = r1 - r2, d2 = d.dist2(), h2 = d2 - dr * dr;
  if (d2 == 0 || h2 < 0)  return {};
  vector<pair<P, P>> out;
  for (double sign : {-1, 1}) {
    P v = (d * dr + d.perp() * sqrt(h2) * sign) / d2;
    out.push_back({c1 + v * r1, c2 + v * r2});
  }
  if (h2 == 0) out.pop_back();
  return out;
}
```

CircleLine.h

Description: Finds the intersection between a circle and a line. Returns a vector of either 0, 1, or 2 intersection points. P is intended to be Point<double>.

"Point.h" e0cfba, 9 lines

```
template<class P>
vector<P> circleLine(P c, double r, P a, P b) {
  P ab = b - a, p = a + ab * (c-a).dot(ab) / ab.dist2();
  double s = a.cross(b, c), h2 = r*r - s*s / ab.dist2();
  if (h2 < 0) return {};
  if (h2 == 0) return {p};
  P h = ab.unit() * sqrt(h2);
  return {p - h, p + h};
}
```

CirclePolygonIntersection.h

Description: Returns the area of the intersection of a circle with a ccw polygon.

Time: $\mathcal{O}(n)$

"../../content/geometry/Point.h" 19add1, 19 lines


```
typedef Point<double> P;
#define arg(p, q) atan2(p.cross(q), p.dot(q))
double circlePoly(P c, double r, vector<P> ps) {
  auto tri = [&](P p, P q) {
    auto r2 = r * r / 2;
    P d = q - p;
    auto a = d.dot(p)/d.dist2(), b = (p.dist2()-r*r)/d.dist2();
    auto det = a * a - b;
    if (det <= 0) return arg(p, q) * r2;
    auto s = max(0., -a-sqrt(det)), t = min(1., -a+sqrt(det));
    if (t < 0 || 1 <= s) return arg(p, q) * r2;
    P u = p + d * s, v = q + d * (t-1);
    return arg(p,u) * r2 + u.cross(v)/2 + arg(v,q) * r2;
  };
```

```
  auto sum = 0.0;
  rep(i,0,sz(ps))
    sum += tri(ps[i] - c, ps[(i + 1) % sz(ps)] - c);
  return sum;
}
```

circumcircle.h

Description:

The circumcirle of a triangle is the circle intersecting all three vertices. ccRadius returns the radius of the circle going through points A, B and C and ccCenter returns the center of the same circle.



"Point.h" 6cffc5, 9 lines

```
typedef Point<double> P;
double ccRadius(P A, P B, P C) {
  return (B-A).dist()*(C-B).dist()*(A-C).dist()/
      abs((B-A).cross(C-A))/2;
}
P ccCenter(P A, P B, P C) {
  P b = C-A, c = B-A;
  return A + (b*c.dist2()-c*b.dist2()).perp()/b.cross(c)/2;
}
```

MinimumEnclosingCircle.h

Description: Computes the minimum circle that encloses a set of points.
Time: expected $\mathcal{O}(n)$

"circumcircle.h" 09dd0a, 17 lines

```
pair<P, double> mec(vector<P> ps) {
  shuffle(all(ps), mt19937(time(0)));
  P o = ps[0];
  double r = 0, EPS = 1 + 1e-8;
  rep(i,0,sz(ps)) if ((o - ps[i]).dist() > r * EPS) {
    o = ps[i], r = 0;
    rep(j,0,i) if ((o - ps[j]).dist() > r * EPS) {
      o = (ps[i] + ps[j]) / 2;
      r = (o - ps[i]).dist();
      rep(k,0,j) if ((o - ps[k]).dist() > r * EPS) {
        o = ccCenter(ps[i], ps[j], ps[k]);
        r = (o - ps[i]).dist();
      }
    }
  }
  return {o, r};
}
```

8.3 Polygons

InsidePolygon.h

Description: Returns true if p lies within the polygon. If strict is true, it returns false for points on the boundary. The algorithm uses products in intermediate steps so watch out for overflow.
Usage: `vector<P> v = {P{4,4}, P{1,2}, P{2,1}};`
`bool in = inPolygon(v, P{3, 3}, false);`
Time: $\mathcal{O}(n)$

"Point.h", "OnSegment.h", "SegmentDistance.h" 2bf504, 11 lines

```
template<class P>
bool inPolygon(vector<P> &p, P a, bool strict = true) {
  int cnt = 0, n = sz(p);
  rep(i,0,n) {
    P q = p[(i + 1) % n];
    if (onSegment(p[i], q, a)) return !strict;
    //or: if (segDist(p[i], q, a) <= eps) return !strict;
    cnt ^= ((a.y<p[i].y) - (a.y<q.y)) * a.cross(p[i], q) > 0;
  }
  return cnt;
}
```

PolygonArea.h

Description: Returns twice the signed area of a polygon. Clockwise enumeration gives negative area. Watch out for overflow if using int as T!

"Point.h" f12300, 6 lines

```
template<class T>
T polygonArea2(vector<Point<T>>& v) {
  T a = v.back().cross(v[0]);
  rep(i,0,sz(v)-1) a += v[i].cross(v[i+1]);
  return a;
}
```

PolygonCenter.h


Description: Returns the center of mass for a polygon.
Time: $\mathcal{O}(n)$

"Point.h" 9706dc, 9 lines

```
typedef Point<double> P;
P polygonCenter(const vector<P>& v) {
  P res(0, 0); double A = 0;
  for (int i = 0, j = sz(v) - 1; i < sz(v); j = i++) {
    res = res + (v[i] + v[j]) * v[j].cross(v[i]);
    A += v[j].cross(v[i]);
  }
  return res / A / 3;
}
```

PolygonCut.h

Description:
Returns a vector with the vertices of a polygon with everything to the left of the line going from s to e cut away.
Usage: `vector<P> p = ...;`
`p = polygonCut(p, P(0,0), P(1,0));`



"Point.h" d07181, 13 lines

```
typedef Point<double> P;
vector<P> polygonCut(const vector<P>& poly, P s, P e) {
  vector<P> res;
  rep(i,0,sz(poly)) {
    P cur = poly[i], prev = i ? poly[i-1] : poly.back();
    auto a = s.cross(e, cur), b = s.cross(e, prev);
    if ((a < 0) != (b < 0))
      res.push_back(cur + (prev - cur) * (a / (a - b)));
    if (a < 0)
      res.push_back(cur);
  }
  return res;
}
```

PolygonUnion.h

Description: Calculates the area of the union of n polygons (not necessarily convex). The points within each polygon must be given in CCW order. (Epsilon checks may optionally be added to sideOf/sgn, but shouldn't be needed.)
Time: $\mathcal{O}(N^2)$, where N is the total number of points

"Point.h", "sideOf.h" 3931c6, 33 lines

```
typedef Point<double> P;
double rat(P a, P b) { return sgn(b.x) ? a.x/b.x : a.y/b.y; }
double polyUnion(vector<vector<P>>& poly) {
  double ret = 0;
  rep(i,0,sz(poly)) rep(v,0,sz(poly[i])) {
    P A = poly[i][v], B = poly[i][(v + 1) % sz(poly[i])];
    vector<pair<double, int>> segs = {{0, 0}, {1, 0}};
    rep(j,0,sz(poly)) if (i != j) {
      rep(u,0,sz(poly[j])) {
        P C = poly[j][u], D = poly[j][(u + 1) % sz(poly[j])];
        int sc = sideOf(A, B, C), sd = sideOf(A, B, D);
        if (sc != sd) {
          double sa = C.cross(D, A), sb = C.cross(D, B);
          if (min(sc, sd) < 0)
            segs.emplace_back(sa / (sa - sb), sgn(sc - sd));
        } else if (!sc && !sd && j<i && sgn((B-A).dot(D-C))>0){
          segs.emplace_back(rat(C - A, B - A), 1);
          segs.emplace_back(rat(D - A, B - A), -1);
        }
      }
    }
    sort(all(segs));
    for (auto& s : segs) s.first = min(max(s.first, 0.0), 1.0);
    double sum = 0;
    int cnt = segs[0].second;
    rep(j,1,sz(segs)) {
      if (!cnt) sum += segs[j].first - segs[j - 1].first;
      cnt += segs[j].second;
    }
    ret += A.cross(B) * sum;
  }
  return ret / 2;
}
```

ConvexHull.h

Description:
Returns a vector of the points of the convex hull in counterclockwise order. Points on the edge of the hull between two other points are not considered part of the hull.
Time: $\mathcal{O}(n \log n)$

"Point.h" 310954, 13 lines

```
typedef Point<ll> P;
vector<P> convexHull(vector<P> pts) {
  if (sz(pts) <= 1) return pts;
  sort(all(pts));
  vector<P> h(sz(pts)+1);
  int s = 0, t = 0;
  for (int it = 2; it--; s = --t, reverse(all(pts)))
    for (P p : pts) {
      while (t >= s + 2 && h[t-2].cross(h[t-1], p) <= 0) t--;
      h[t++] = p;
    }
  return {h.begin(), h.begin() + t - (t == 2 && h[0] == h[1])};
}
```

HullDiameter.h

Description: Returns the two points with max distance on a convex hull (ccw, no duplicate/collinear points).
Time: $\mathcal{O}(n)$

"Point.h" c571b8, 12 lines

```
typedef Point<ll> P;
array<P, 2> hullDiameter(vector<P> S) {
  int n = sz(S), j = n < 2 ? 0 : 1;
  pair<ll, array<P, 2>> res({0, {S[0], S[0]}});
  rep(i,0,j)
    for (;; j = (j + 1) % n) {
      res = max(res, {(S[i] - S[j]).dist2(), {S[i], S[j]}});
      if ((S[(j + 1) % n] - S[j]).cross(S[i + 1] - S[i]) >= 0)
        break;
    }
  return res.second;
}
```

PointInsideHull.h

Description: Determine whether a point t lies inside a convex hull (CCW order, with no collinear points). Returns true if point lies within the hull. If strict is true, points on the boundary aren't included.
Time: $\mathcal{O}(\log N)$

"Point.h", "sideOf.h", "OnSegment.h" 71446b, 14 lines

```
typedef Point<ll> P;

bool inHull(const vector<P>& l, P p, bool strict = true) {
```

```
  int a = 1, b = sz(l) - 1, r = !strict;
  if (sz(l) < 3) return r && onSegment(l[0], l.back(), p);
  if (sideOf(l[0], l[a], l[b]) > 0) swap(a, b);
  if (sideOf(l[0], l[a], p) >= r || sideOf(l[0], l[b], p)<= -r)
    return false;
  while (abs(a - b) > 1) {
    int c = (a + b) / 2;
    (sideOf(l[0], l[c], p) > 0 ? b : a) = c;
  }
  return sgn(l[a].cross(l[b], p)) < r;
}
```

PolyTangents.h

Description: Calculates the tangent from a point to a polygon The polygon must be given in CCW order.
Time: $\mathcal{O}(\log N)$

"Point.h" 92f0a7, 23 lines

```
template<class Fun>
// tangent from p to poly
// auto t = extreme(poly, [&](const P q) { return p - q; });
int extreme(const vector<P>& poly, Fun dir) {
    int n = sz(poly), low = 0, low_sgn;
    auto nx = [&](int i) { return i + 1 == n ? 0 : i + 1 ; };
    auto pr = [&](int i) { return i ? i - 1 : n - 1; };
    auto vertexCmp = [&](int i, int j) {
        return sgn(dir(poly[j]).cross(poly[j] - poly[i]));
    };
    auto isExtreme = [&](int i , int &i_sgn) {
        return (i_sgn = vertexCmp(nx(i), i)) >= 0 && vertexCmp(
            i, pr(i)) < 0 ;
    };

    for(int high = isExtreme(0, low_sgn) ? 1 : n; low + 1 <
        high;) {
        int mid = (low + high) / 2, mid_sgn;
        if(isExtreme(mid, mid_sgn)) return mid;
        if(low_sgn != mid_sgn ? low_sgn < mid_sgn
                : low_sgn == vertexCmp(low, mid)) high = mid;
        else low = mid, low_sgn = mid_sgn;
    }
    return low ;
}
```

MinkowskiSum.h

Description: Calculates the Minkowski sum of two polygons. Be careful with precision issues, use sgn with epsilons instead of c <= 0
Time: $\mathcal{O}(N + M)$, where N and M are the size of the polygons.

"Point.h" 243a8e, 21 lines

```
void fix(poly &a) {
    int pos = 0;
    rep(i,0,sz(a)) {
        if(a[i].y < a[pos].y || (a[i].y == a[pos].y && a[i].x <
            a[pos].x)) pos = i;
    }
    rotate(a.begin(), a.begin() + pos, a.end());
}
poly minkowski_sum(poly a, poly b) {
    fix(a); fix(b);
    rep(it,0,2) a.push_back(a[it]), b.push_back(b[it]);
    int i = 0, j = 0;
    poly res;
    while(i < sz(a) - 2 || j < sz(b) - 2) {
        res.push_back(a[i] + b[j]);
        auto c = (a[i + 1] - a[i]).cross(b[j + 1] - b[j]);
        // a veces solo se necesita la segunda comprobacion
        if(i < sz(a) - 2 && c >= 0) i++;
        if(j < sz(b) - 2 && c <= 0) j++;
    }
    return res;
}
```

LineHullIntersection.h

Description: Line-convex polygon intersection. The polygon must be ccw and have no collinear points. lineHull(line, poly) returns a pair describing the intersection of a line with the polygon: $\bullet$ $(-1,-1)$ if no collision, $\bullet$ $(i,-1)$ if touching the corner i, $\bullet$ (i,i) if along side $(i,i+1)$, $\bullet$ (i,j) if crossing sides $(i,i+1)$ and $(j,j+1)$. In the last case, if a corner i is crossed, this is treated as happening on side $(i,i+1)$. The points are returned in the same order as the line hits the polygon. `extrVertex` returns the point of a hull with the max projection onto a line.
Time: $\mathcal{O}(\log n)$

"Point.h" 7cf45b, 39 lines

```
#define cmp(i,j) sgn(dir.perp().cross(poly[(i)%n]-poly[(j)%n]))
#define extr(i) cmp(i + 1, i) >= 0 && cmp(i, i - 1 + n) < 0
template <class P> int extrVertex(vector<P>& poly, P dir) {
  int n = sz(poly), lo = 0, hi = n;
  if (extr(0)) return 0;
  while (lo + 1 < hi) {
    int m = (lo + hi) / 2;
    if (extr(m)) return m;
    int ls = cmp(lo + 1, lo), ms = cmp(m + 1, m);
    (ls < ms || (ls == ms && ls == cmp(lo, m)) ? hi : lo) = m;
  }
  return lo;
}

#define cmpL(i) sgn(a.cross(poly[i], b))
template <class P>
array<int, 2> lineHull(P a, P b, vector<P>& poly) {
  int endA = extrVertex(poly, (a - b).perp());
  int endB = extrVertex(poly, (b - a).perp());
  if (cmpL(endA) < 0 || cmpL(endB) > 0)
    return {-1, -1};
  array<int, 2> res;
  rep(i,0,2) {
    int lo = endB, hi = endA, n = sz(poly);
    while ((lo + 1) % n != hi) {
      int m = ((lo + hi + (lo < hi ? 0 : n)) / 2) % n;
      (cmpL(m) == cmpL(endB) ? lo : hi) = m;
    }
    res[i] = (lo + !cmpL(hi)) % n;
    swap(endA, endB);
  }
  if (res[0] == res[1]) return {res[0], -1};
  if (!cmpL(res[0]) && !cmpL(res[1]))
    switch ((res[0] - res[1] + sz(poly) + 1) % sz(poly)) {
      case 0: return {res[0], res[0]};
      case 2: return {res[1], res[1]};
    }
  return res;
}
```

8.4 Misc. Point Set Problems

ClosestPair.h

Description: Finds the closest pair of points.
Time: $\mathcal{O}(n \log n)$

"Point.h" ac41a6, 17 lines

```
typedef Point<ll> P;
pair<P, P> closest(vector<P> v) {
  assert(sz(v) > 1);
  set<P> S;
  sort(all(v), [](P a, P b) { return a.y < b.y; });
  pair<ll, pair<P, P>> ret{LLONG_MAX, {P(), P()}};
  int j = 0;
  for (P p : v) {
    P d{1 + (ll)sqrt(ret.first), 0};
    while (v[j].y <= p.y - d.x) S.erase(v[j++]);
    auto lo = S.lower_bound(p - d), hi = S.upper_bound(p + d);
    for (; lo != hi; ++lo)
      ret = min(ret, {(*lo - p).dist2(), {*lo, p}});
    S.insert(p);
  }
  return ret.second;
}
```

ManhattanMST.h

Description: Given N points, returns up to 4*N edges, which are guaranteed to contain a minimum spanning tree for the graph with edge weights w(p, q) = —p.x - q.x— + —p.y - q.y—. Edges are in the form (distance, src, dst). Use a standard MST algorithm on the result to find the final MST.
Time: $\mathcal{O}(N \log N)$

"Point.h" df6f59, 23 lines

```
typedef Point<int> P;
vector<array<int, 3>> manhattanMST(vector<P> ps) {
  vi id(sz(ps));
  iota(all(id), 0);
  vector<array<int, 3>> edges;
  rep(k,0,4) {
    sort(all(id), [&](int i, int j) {
         return (ps[i]-ps[j]).x < (ps[j]-ps[i]).y;});
    map<int, int> sweep;
    for (int i : id) {
      for (auto it = sweep.lower_bound(-ps[i].y);
                it != sweep.end(); sweep.erase(it++)) {
        int j = it->second;
        P d = ps[i] - ps[j];
        if (d.y > d.x) break;
        edges.push_back({d.y + d.x, i, j});
      }
      sweep[-ps[i].y] = i;
    }
    for (P& p : ps) if (k & 1) p.x = -p.x; else swap(p.x, p.y);
  }
  return edges;
}
```

kdTree.h

Description: KD-tree (2d, can be extended to 3d)

"Point.h" 69ff55, 63 lines

```
typedef long long T;
typedef Point<T> P;
const T INF = numeric_limits<T>::max();

bool on_x(P a, P b) { return a.x < b.x; }
bool on_y(P a, P b) { return a.y < b.y; }

struct Node {
  P pt; // if this is a leaf, the single point in it
  T x0 = INF, x1 = -INF, y0 = INF, y1 = -INF; // bounds
  Node *first = 0, *second = 0;

  T distance(P p) { // min squared distance to a point
    T x = (p.x < x0 ? x0 : p.x > x1 ? x1 : p.x);
    T y = (p.y < y0 ? y0 : p.y > y1 ? y1 : p.y);
    return (P(x,y) - p).dist2();
  }

  Node(vector<P>&& vp) : pt(vp[0]) {
    for (P p : vp) {
      x0 = min(x0, p.x); x1 = max(x1, p.x);
      y0 = min(y0, p.y); y1 = max(y1, p.y);
    }
    if (vp.size() > 1) {
      // split on x if width >= height (not ideal...)
```

```
      sort(all(vp), x1 - x0 >= y1 - y0 ? on_x : on_y);
      // divide by taking half the array for each child (not
      // best performance with many duplicates in the middle)
      int half = sz(vp)/2;
      first = new Node({vp.begin(), vp.begin() + half});
      second = new Node({vp.begin() + half, vp.end()});
    }
  }
};

struct KDTree {
  Node* root;
  KDTree(const vector<P>& vp) : root(new Node({all(vp)})) {}

  pair<T, P> search(Node *node, P p) {
    if (!node->first) {
      // uncomment if we should not find the point itself:
      // if (p == node->pt) return {INF, P()};
      return make_pair((p - node->pt).dist2(), node->pt);
    }

    Node *f = node->first, *s = node->second;
    T bfirst = f->distance(p), bsec = s->distance(p);
    if (bfirst > bsec) swap(bsec, bfirst), swap(f, s);

    // search closest side first, other side if needed
    auto best = search(f, p);
    if (bsec < best.first)
      best = min(best, search(s, p));
    return best;
  }

  // find nearest point to a point, and its squared distance
  // (requires an arbitrary operator< for Point)
  pair<T, P> nearest(P p) {
    return search(root, p);
  }
};
```

DelaunayTriangulation.h

Description: Computes the Delaunay triangulation of a set of points. Each circumcircle contains none of the input points. If any three points are collinear or any four are on the same circle, behavior is undefined.
Time: $\mathcal{O}(n^2)$

"Point.h", "3dHull.h" c0e7bc, 10 lines

```
template<class P, class F>
void delaunay(vector<P>& ps, F trifun) {
  if (sz(ps) == 3) { int d = (ps[0].cross(ps[1], ps[2]) < 0);
    trifun(0,1+d,2-d); }
  vector<P3> p3;
  for (P p : ps) p3.emplace_back(p.x, p.y, p.dist2());
  if (sz(ps) > 3) for(auto t:hull3d(p3)) if ((p3[t.b]-p3[t.a]).
      cross(p3[t.c]-p3[t.a]).dot(P3(0,0,1)) < 0)
    trifun(t.a, t.c, t.b);
}
```

FastDelaunay.h

Description: Fast Delaunay triangulation. Each circumcircle contains none of the input points. There must be no duplicate points. If all points are on a line, no triangles will be returned. Should work for doubles as well, though there may be precision issues in 'circ'. Returns triangles in order {t[0][0], t[0][1], t[0][2], t[1][0], ...}, all counter-clockwise.
Time: $\mathcal{O}(n \log n)$

"Point.h" eefdf5, 88 lines

```
typedef Point<ll> P;
typedef struct Quad* Q;
typedef __int128_t lll; // (can be ll if coords are < 2e4)
P arb(LLONG_MAX,LLONG_MAX); // not equal to any other point

struct Quad {
  Q rot, o; P p = arb; bool mark;
  P& F() { return r()->p; }
  Q& r() { return rot->rot; }
  Q prev() { return rot->o->rot; }
  Q next() { return r()->prev(); }
} *H;

bool circ(P p, P a, P b, P c) { // is p in the circumcircle?
  lll p2 = p.dist2(), A = a.dist2()-p2,
      B = b.dist2()-p2, C = c.dist2()-p2;
  return p.cross(a,b)*C + p.cross(b,c)*A + p.cross(c,a)*B > 0;
}
Q makeEdge(P orig, P dest) {
  Q r = H ? H : new Quad{new Quad{new Quad{new Quad{0}}}};
  H = r->o; r->r()->r() = r;
  rep(i,0,4) r = r->rot, r->p = arb, r->o = i & 1 ? r : r->r();
  r->p = orig; r->F() = dest;
  return r;
}
void splice(Q a, Q b) {
  swap(a->o->rot->o, b->o->rot->o); swap(a->o, b->o);
}
Q connect(Q a, Q b) {
  Q q = makeEdge(a->F(), b->p);
  splice(q, a->next());
  splice(q->r(), b);
  return q;
}

pair<Q,Q> rec(const vector<P>& s) {
  if (sz(s) <= 3) {
    Q a = makeEdge(s[0], s[1]), b = makeEdge(s[1], s.back());
    if (sz(s) == 2) return { a, a->r() };
    splice(a->r(), b);
    auto side = s[0].cross(s[1], s[2]);
    Q c = side ? connect(b, a) : 0;
    return {side < 0 ? c->r() : a, side < 0 ? c : b->r() };
  }

#define H(e) e->F(), e->p
#define valid(e) (e->F().cross(H(base)) > 0)
  Q A, B, ra, rb;
  int half = sz(s) / 2;
  tie(ra, A) = rec({all(s) - half});
  tie(B, rb) = rec({sz(s) - half + all(s)});
  while ((B->p.cross(H(A)) < 0 && (A = A->next())) ||
         (A->p.cross(H(B)) > 0 && (B = B->r()->o)));
  Q base = connect(B->r(), A);
  if (A->p == ra->p) ra = base->r();
  if (B->p == rb->p) rb = base;

#define DEL(e, init, dir) Q e = init->dir; if (valid(e)) \
    while (circ(e->dir->F(), H(base), e->F())) { \
      Q t = e->dir; \
      splice(e, e->prev()); \
      splice(e->r(), e->r()->prev()); \
      e->o = H; H = e; e = t; \
    }
  for (;;) {
    DEL(LC, base->r(), o);  DEL(RC, base, prev());
    if (!valid(LC) && !valid(RC)) break;
    if (!valid(LC) || (valid(RC) && circ(H(RC), H(LC))))
      base = connect(RC, base->r());
    else
      base = connect(base->r(), LC->r());
  }
  return { ra, rb };
}

vector<P> triangulate(vector<P> pts) {
  sort(all(pts));  assert(unique(all(pts)) == pts.end());
  if (sz(pts) < 2) return {};
  Q e = rec(pts).first;
  vector<Q> q = {e};
  int qi = 0;
  while (e->o->F().cross(e->F(), e->p) < 0) e = e->o;
#define ADD { Q c = e; do { c->mark = 1; pts.push_back(c->p); \
  q.push_back(c->r()); c = c->next(); } while (c != e); }
  ADD; pts.clear();
  while (qi < sz(q)) if (!(e = q[qi++])->mark) ADD;
  return pts;
}
```

HalfPlaneIntersection.h

Description: Returns a convex polygon, the intersection of some half-planes. You can add a bounding box at the beginning.
Time: $\mathcal{O}(n \log n)$

"Point.h" ce46b9, 56 lines

```
struct HP {
    P a, b;
    HP() {}
    HP(P a, P b) : a(a), b(b) {}
    HP(const HP& rhs) : a(rhs.a), b(rhs.b) {}
    int operator < (const HP& rhs) const {
        P p = b - a;
        P q = rhs.b - rhs.a;
        int fp = (p.y < 0 || (fabsl(p.y) < eps && p.x < 0));
        int fq = (q.y < 0 || (fabsl(q.y) < eps && q.x < 0));
        if (fp != fq) return fp == 0;
        if (p.cross(q)) return p.cross(q) > 0;
        return p.cross(rhs.b - a) < 0;
    }
    P line_line_intersection(P a, P b, P c, P d) {
        b = b - a; d = c - d; c = c - a;
        return a + b * c.cross(d) / b.cross(d);
    }
    P intersection(const HP &v) {
        return line_line_intersection(a, b, v.a, v.b);
    }
};

int check(HP a, HP b, HP c) {
    return (a.b - a.a).cross(b.intersection(c) - a.a) > -eps;
}

vector<P> half_plane_intersection(vector<HP> h) {
    sort(all(h));
    vector<HP> tmp;
    rep(i,0,sz(h)) {
        if(!i || (h[i].b - h[i].a).cross(h[i - 1].b - h[i - 1].
            a)) {
            tmp.push_back(h[i]);
        }
    }

    h = tmp;
    vector<HP> q(sz(h) + 10);
    int qh = 0, qe = 0;
    rep(i,0,sz(h)) {
        while (qe - qh > 1 && !check(h[i], q[qe - 2], q[qe -
            1])) qe--;
        while (qe - qh > 1 && !check(h[i], q[qh], q[qh + 1]))
            qh++;
        q[qe++] = h[i];
    }
```

```
    while (qe - qh > 2 && !check(q[qh], q[qe - 2], q[qe - 1]))
        qe--;
    while (qe - qh > 2 && !check(q[qe - 1], q[qh], q[qh + 1]))
        qh++;

    vector<HP> res; rep(i,qh,qe) res.push_back(q[i]);
    vector<P> hull;
    if (sz(res) > 2) {
        rep(i,0,sz(res))
            hull.push_back(res[i].intersection(res[(i + 1) % ((
                int)res.size())]));
    }
    return hull;
}
```

HalfPlaneIntersectionRandom.h

Description: Checks if the intersection of some half-planes is non-empty
Time: $\mathcal{O}(n)$

"Point.h" 9dbd8c, 35 lines

```
struct line { P p, q; }
bool HPintersect(vector<line> v) {
    auto side = [](line &l, P p) {
        return sideOf(l.p, l.q, p) >= 0;
    };

    auto crosspoint = [](const line &l, const line &m, P &x) {
        auto inter = lineInter(l.p, l.q, m.p, m.q);
        if(inter.first <= 0) return false;
        x = inter.second;
        return true;
    };

    shuffle(all(v), mt19937(time(0)));
    P cen(0,1e9);
    rep(i,0,sz(v)) {
        line &S = v[i];
        if(side(S, cen)) continue;
        P d = (S.q - S.p).unit();
        P A = S.p - d * 1e8, B = S.p + d * 1e8;
        rep(j,0,i) {
            P x;
            line &T = v[j];
            if(crosspoint(T, S, x)) {
                int cnt = 0;
                if(!side(T, A)) A = x, cnt++;
                if(!side(T, B)) B = x, cnt++;
                if(cnt == 2) return false;
            }else if(!side(T, A)) return false;
        }
        if(B.y > A.y) swap(A, B);
        cen = A;
    }
    return true;
}
```

RectangleUnion.h

Description: Calculates the area of the union of rectangles
Time: $\mathcal{O}(N \log N)$

95cbed, 45 lines

```
struct rectangle {  ll xl, yl, xh, yh; };
ll rectangle_area(vector<rectangle> &rs) {
  vector<ll> ys; // coordinate compression
  for (auto r : rs) {
    ys.push_back(r.yl);
    ys.push_back(r.yh);
  }
  sort(ys.begin(), ys.end());
  ys.erase(unique(ys.begin(), ys.end()), ys.end());
  int n = sz(ys);
  vector<ll> C(8 * n), A(8 * n);
  function<void(int, int, int, int, int, int)> aux = [&](int a,
      int b, int c, int l, int r, int k) {
      if ((a = max(a,l)) >= (b = min(b,r))) return;
      if (a == l && b == r) C[k] += c;
      else {
          aux(a, b, c, l, (l+r)/2, 2*k+1);
          aux(a, b, c, (l+r)/2, r, 2*k+2);
      }
      if (C[k]) A[k] = ys[r] - ys[l];
      else A[k] = A[2*k+1] + A[2*k+2];
  };

  struct event {
    ll x, l, h, c;
  };

  vector<event> es;
  for (auto r : rs) {
    int l = lower_bound(ys.begin(), ys.end(), r.yl) - ys.begin
        ();
    int h = lower_bound(ys.begin(), ys.end(), r.yh) - ys.begin
        ();
    es.push_back({ r.xl, l, h, +1 });
    es.push_back({ r.xh, l, h, -1 });
  }

    sort(all(es), [](event a, event b){return a.x != b.x ? a.x
        < b.x : a.c > b.c;});

    ll area = 0, prev = 0;
  for (auto &e : es) {
    area += (e.x - prev) * A[0];
    prev = e.x;
    aux(e.l, e.h, e.c, 0, n, 0);
  }
  return area;
}
```

PlanarFaces.h

Description: Calculates the faces of a planar graph
Time: $\mathcal{O}(N \log N)$, because of sorting

c70c10, 49 lines

```
vvi find_faces(vector<P> vertices, vvi& adj) {
    int n = vertices.size();
    std::vector<std::vector<char>> used(n);
    rep(i,0,n) {
        used[i].assign(sz(adj[i]), 0);
        auto compare = [&](size_t l, size_t r) {
            P pl = vertices[l] - vertices[i];
            P pr = vertices[r] - vertices[i];
            if (pl.half() != pr.half())
                return pl.half() < pr.half();
            return pl.cross(pr) > 0;
        };
        sort(all(adj[i]), compare);
    }
    vvi faces;
    rep(i,0,n) {
        rep(edge_id,0,sz(adj[i]))  {
            if (used[i][edge_id]) continue;
            vi face;
            int v = i, e = edge_id;
            while (!used[v][e]) {
                used[v][e] = true;
                face.push_back(v);
                int u = adj[v][e];
                int e1 = std::lower_bound(adj[u].begin(), adj[u
                    ].end(), v, [&](int l, int r) {
                    Point pl = vertices[l] - vertices[u];
                    Point pr = vertices[r] - vertices[u];
                    if (pl.half() != pr.half())
                        return pl.half() < pr.half();
                    return pl.cross(pr) > 0;
                }) - adj[u].begin() + 1;
                if (e1 == sz(adj[u])) e1 = 0;
                v = u;
                e = e1;
            }
            reverse(all(face));
            Point p1 = vertices[face[0]];
            __int128 sum = 0;
            for (int j = 0; j < face.size(); ++j) {
                Point p2 = vertices[face[j]];
                Point p3 = vertices[face[(j + 1) % face.size()
                    ]];
                sum += (p2 - p1).cross(p3 - p2);
            }
            if (sum <= 0) faces.insert(faces.begin(), face);
            else faces.emplace_back(face);
        }
    }
    return faces;
}
```

8.5 3D

PolyhedronVolume.h

Description: Magic formula for the volume of a polyhedron. Faces should point outwards.

3058c3, 6 lines

```
template<class V, class L>
double signedPolyVolume(const V& p, const L& trilist) {
  double v = 0;
  for (auto i : trilist) v += p[i.a].cross(p[i.b]).dot(p[i.c]);
  return v / 6;
}
```

Point3D.h

Description: Class to handle points in 3D space. T can be e.g. double or long long.

a94b7c, 31 lines

```
template<class T> struct Point3D {
  typedef Point3D P;
  T x, y, z;
  explicit Point3D(T x=0, T y=0, T z=0) : x(x), y(y), z(z) {}
  bool operator<(P p) const {
    return tie(x, y, z) < tie(p.x, p.y, p.z); }
  bool operator==(P p) const {
    return tie(x, y, z) == tie(p.x, p.y, p.z); }
  P operator+(P p) const { return P(x+p.x, y+p.y, z+p.z); }
  P operator-(P p) const { return P(x-p.x, y-p.y, z-p.z); }
  P operator*(T d) const { return P(x*d, y*d, z*d); }
  P operator/(T d) const { return P(x/d, y/d, z/d); }
  T dot(P p) const { return x*p.x + y*p.y + z*p.z; }
  P cross(P p) const {
    return P(y*p.z - z*p.y, z*p.x - x*p.z, x*p.y - y*p.x);
  }
  T dist2() const { return x*x + y*y + z*z; }
  double dist() const { return sqrt((double)dist2()); }
  //Azimuthal angle (longitude) to x-axis in interval [-pi, pi]
  double phi() const { return atan2(y, x); }
  //Zenith angle (latitude) to the z-axis in interval [0, pi]
  double theta() const { return atan2(sqrt(x*x+y*y),z); }
  P unit() const { return *this/(T)dist(); } //makes dist()=1
  //returns unit vector normal to *this and p
  P normal(P p) const { return cross(p).unit(); }
```

```
  //returns point rotated 'angle' radians ccw around axis
  P rotate(double angle, P axis) const {
    double s = sin(angle), c = cos(angle); P u = axis.unit();
    return u*dot(u)*(1-c) + (*this)*c - cross(u)*s;
  }
};
```

3dHull.h

Description: Computes all faces of the 3-dimension hull of a point set. *No four points must be coplanar*, or else random results will be returned. All faces will point outwards.
Time: $\mathcal{O}(n^2)$

"Point3D.h" 5b45fc, 49 lines

```
typedef Point3D<double> P3;

struct PR {
  void ins(int x) { (a == -1 ? a : b) = x; }
  void rem(int x) { (a == x ? a : b) = -1; }
  int cnt() { return (a != -1) + (b != -1); }
  int a, b;
};

struct F { P3 q; int a, b, c; };

vector<F> hull3d(const vector<P3>& A) {
  assert(sz(A) >= 4);
  vector<vector<PR>> E(sz(A), vector<PR>(sz(A), {-1, -1}));
#define E(x,y) E[f.x][f.y]
  vector<F> FS;
  auto mf = [&](int i, int j, int k, int l) {
    P3 q = (A[j] - A[i]).cross((A[k] - A[i]));
    if (q.dot(A[l]) > q.dot(A[i]))
      q = q * -1;
    F f{q, i, j, k};
    E(a,b).ins(k); E(a,c).ins(j); E(b,c).ins(i);
    FS.push_back(f);
  };
  rep(i,0,4) rep(j,i+1,4) rep(k,j+1,4)
    mf(i, j, k, 6 - i - j - k);

  rep(i,4,sz(A)) {
    rep(j,0,sz(FS)) {
      F f = FS[j];
      if(f.q.dot(A[i]) > f.q.dot(A[f.a])) {
        E(a,b).rem(f.c);
        E(a,c).rem(f.b);
        E(b,c).rem(f.a);
        swap(FS[j--], FS.back());
        FS.pop_back();
      }
    }
    int nw = sz(FS);
    rep(j,0,nw) {
      F f = FS[j];
#define C(a, b, c) if (E(a,b).cnt() != 2) mf(f.a, f.b, i, f.c);
      C(a, b, c); C(a, c, b); C(b, c, a);
    }
  }
  for (F& it : FS) if ((A[it.b] - A[it.a]).cross(
    A[it.c] - A[it.a]).dot(it.q) <= 0) swap(it.c, it.b);
  return FS;
};
```

sphericalDistance.h

Description: Returns the shortest distance on the sphere with radius radius between the points with azimuthal angles (longitude) f1 (ϕ_1) and f2 (ϕ_2) from x axis and zenith angles (latitude) t1 (θ_1) and t2 (θ_2) from z axis ($0 =$ north pole). All angles measured in radians. The algorithm starts by converting the spherical coordinates to cartesian coordinates so if that is what you have you can use only the two last rows. dx*radius is then the difference between the two points in the x direction and d*radius is the total distance between the points.

611f07, 8 lines

```
double sphericalDistance(double f1, double t1,
    double f2, double t2, double radius) {
  double dx = sin(t2)*cos(f2) - sin(t1)*cos(f1);
  double dy = sin(t2)*sin(f2) - sin(t1)*sin(f1);
  double dz = cos(t2) - cos(t1);
  double d = sqrt(dx*dx + dy*dy + dz*dz);
  return radius*2*asin(d/2);
}
```

Strings (9)

KMP.h

Description: pi[x] computes the length of the longest prefix of s that ends at x, other than s[0...x] itself (abacaba -> 0010123). Can be used to find all occurrences of a string.
Time: $\mathcal{O}(n)$

d4375c, 16 lines

```
vi pi(const string& s) {
  vi p(sz(s));
  rep(i,1,sz(s)) {
    int g = p[i-1];
    while (g && s[i] != s[g]) g = p[g-1];
    p[i] = g + (s[i] == s[g]);
  }
  return p;
}

vi match(const string& s, const string& pat) {
  vi p = pi(pat + '\0' + s), res;
  rep(i,sz(p)-sz(s),sz(p))
    if (p[i] == sz(pat)) res.push_back(i - 2 * sz(pat));
  return res;
}
```

Zfunc.h

Description: z[i] computes the length of the longest common prefix of s[i:] and s, except z[0] = 0. (abacaba -> 0010301)
Time: $\mathcal{O}(n)$

ee09e2, 12 lines

```
vi Z(const string& S) {
  vi z(sz(S));
  int l = -1, r = -1;
  rep(i,1,sz(S)) {
    z[i] = i >= r ? 0 : min(r - i, z[i - l]);
    while (i + z[i] < sz(S) && S[i + z[i]] == S[z[i]])
      z[i]++;
    if (i + z[i] > r)
      l = i, r = i + z[i];
  }
  return z;
}
```

Manacher.h

Description: For each position in a string, computes half length of longest even palindrome around pos i
Time: $\mathcal{O}(N)$

3af119, 28 lines

```
vi manacher_odd(string s) {
    int n = s.size();
    s = "@" + s + "$";
    vi len(n + 1);
    int l = 1, r = 1;
    for(int i = 1; i <= n; i++) {
        len[i] = min(r - i, len[l + (r - i)]);
        while(s[i - len[i]] == s[i + len[i]]) len[i]++;
        if(i + len[i] > r) {
            l = i - len[i];
            r = i + len[i];
        }
    }
    len.erase(begin(len));
    return len;
}

// para verificar si un substring es palindromo
// return pal[l + r] >= (r - l + 1) + 1; indexando en 0
vi manacher(string s) {
    string ns(1, '#');
    for(char c : s) {
        ns.push_back(c);
        ns.push_back('#');
    }
    auto res = manacher_odd(ns);
    return vi(res.begin() + 1, res.end() - 1);
}
```

MinRotation.h

Description: Finds the lexicographically smallest rotation of a string.
Usage: rotate(v.begin(), v.begin()+minRotation(v), v.end());
Time: $\mathcal{O}(N)$

d07a42, 8 lines

```
int minRotation(string s) {
  int a=0, N=sz(s); s += s;
  rep(b,0,N) rep(k,0,N) {
    if (a+k == b || s[a+k] < s[b+k]) {b += max(0, k-1); break;}
    if (s[a+k] > s[b+k]) { a = b; break; }
  }
  return a;
}
```

SuffixArray.h

Description: Builds suffix array for a string. sa[i] is the starting index of the suffix which is i'th in the sorted suffix array. The returned vector is of size $n + 1$, and sa[0] = n. The lcp array contains longest common prefixes for neighbouring strings in the suffix array: lcp[i] = lcp(sa[i], sa[i-1]), lcp[0] = 0. The input string must not contain any nul chars.
Time: $\mathcal{O}(n \log n)$

635552, 33 lines

```
struct SuffixArray {
  vi sa, lcp;
  SuffixArray(string s, int lim=256) { // or vector<int>
    s.push_back(0); int n = sz(s), k = 0, a, b;
    vi x(all(s)), y(n), ws(max(n, lim));
    sa = lcp = y, iota(all(sa), 0);
    for (int j = 0, p = 0; p < n; j = max(1, j * 2), lim = p) {
      p = j, iota(all(y), n - j);
      rep(i,0,n) if (sa[i] >= j) y[p++] = sa[i] - j;
      fill(all(ws), 0);
      rep(i,0,n) ws[x[i]]++;
      rep(i,1,lim) ws[i] += ws[i - 1];
      for (int i = n; i--;) sa[--ws[x[y[i]]]] = y[i];
      swap(x, y), p = 1, x[sa[0]] = 0;
      rep(i,1,n) a = sa[i - 1], b = sa[i], x[b] =
        (y[a] == y[b] && y[a + j] == y[b + j]) ? p - 1 : p++;
    }
    for (int i = 0, j; i < n - 1; lcp[x[i++]] = k)
      for (k && k--, j = sa[x[i] - 1];
          s[i + k] == s[j + k]; k++);
  }
```

```
  //Longest Common Substring: construir el suffixArray s = s1 +
       "#" + s2 + "$" y m = sz(s2)
    // pair<int, int> lcs() {
    //     int mx = -1, ind = -1;
    //     for (int i = 1; i < n; i++) {
    //         if (((sa[i] < n-m-1) != (sa[i-1] < n-m-1)) && mx
        < lcp[i]) {
    //             mx = lcp[i]; ind = i;
    //         }
    //     }
    //     return {mx, ind};
    // }
};
```

SuffixTree.h

Description: Ukkonen's algorithm for online suffix tree construction. Each node contains indices [l, r) into the string, and a list of child nodes. Suffixes are given by traversals of this tree, joining [l, r) substrings. The root is 0 (has l = -1, r = 0), non-existent children are -1. To get a complete tree, append a dummy symbol – otherwise it may contain an incomplete path (still useful for substring matching, though).
Time: $\mathcal{O}(26N)$

aae0b8, 50 lines

```
struct SuffixTree {
  enum { N = 200010, ALPHA = 26 }; // N ~ 2*maxlen+10
  int toi(char c) { return c - 'a'; }
  string a; // v = cur node, q = cur position
  int t[N][ALPHA],l[N],r[N],p[N],s[N],v=0,q=0,m=2;

  void ukkadd(int i, int c) { suff:
    if (r[v]<=q) {
      if (t[v][c]==-1) { t[v][c]=m;  l[m]=i;
        p[m++]=v; v=s[v]; q=r[v];  goto suff; }
      v=t[v][c]; q=l[v];
    }
    if (q==-1 || c==toi(a[q])) q++; else {
      l[m+1]=i;  p[m+1]=m;  l[m]=l[v];  r[m]=q;
      p[m]=p[v];  t[m][c]=m+1;  t[m][toi(a[q])]=v;
      l[v]=q;  p[v]=m;  t[p[m]][toi(a[l[m]])]=m;
      v=s[p[m]];  q=l[m];
      while (q<r[m]) { v=t[v][toi(a[q])];  q+=r[v]-l[v]; }
      if (q==r[m])  s[m]=v;  else s[m]=m+2;
      q=r[v]-(q-r[m]);  m+=2;  goto suff;
    }
  }

  SuffixTree(string a) : a(a) {
    fill(r,r+N,sz(a));
    memset(s, 0, sizeof s);
    memset(t, -1, sizeof t);
    fill(t[1],t[1]+ALPHA,0);
    s[0] = 1; l[0] = l[1] = -1; r[0] = r[1] = p[0] = p[1] = 0;
    rep(i,0,sz(a)) ukkadd(i, toi(a[i]));
  }

  // example: find longest common substring (uses ALPHA = 28)
  pii best;
  int lcs(int node, int i1, int i2, int olen) {
    if (l[node] <= i1 && i1 < r[node]) return 1;
    if (l[node] <= i2 && i2 < r[node]) return 2;
    int mask = 0, len = node ? olen + (r[node] - l[node]) : 0;
    rep(c,0,ALPHA) if (t[node][c] != -1)
      mask |= lcs(t[node][c], i1, i2, len);
    if (mask == 3)
      best = max(best, {len, r[node] - len});
    return mask;
  }
  static pii LCS(string s, string t) {
    SuffixTree st(s + (char)('z' + 1) + t + (char)('z' + 2));
    st.lcs(0, sz(s), sz(s) + 1 + sz(t), 0);
    return st.best;
  }
};
```

Hashing.h

Description: Self-explanatory methods for string hashing.

2d2a67, 44 lines

```
// Arithmetic mod 2^64-1. 2x slower than mod 2^64 and more
// code, but works on evil test data (e.g. Thue-Morse, where
// ABBA... and BAAB... of length 2^10 hash the same mod 2^64).
// "typedef ull H;" instead if you think test data is random,
// or work mod 10^9+7 if the Birthday paradox is not a problem.
typedef uint64_t ull;
struct H {
  ull x; H(ull x=0) : x(x) {}
  H operator+(H o) { return x + o.x + (x + o.x < x); }
  H operator-(H o) { return *this + ~o.x; }
  H operator*(H o) { auto m = (__uint128_t)x * o.x;
    return H((ull)m) + (ull)(m >> 64); }
  ull get() const { return x + !~x; }
  bool operator==(H o) const { return get() == o.get(); }
  bool operator<(H o) const { return get() < o.get(); }
};
static const H C = (ll)1e11+3; // (order ~ 3e9; random also ok)

struct HashInterval {
  vector<H> ha, pw;
  HashInterval(string& str) : ha(sz(str)+1), pw(ha) {
    pw[0] = 1;
    rep(i,0,sz(str))
      ha[i+1] = ha[i] * C + str[i],
      pw[i+1] = pw[i] * C;
  }
  H hashInterval(int a, int b) { // hash [a, b)
    return ha[b] - ha[a] * pw[b - a];
  }
};

vector<H> getHashes(string& str, int length) {
  if (sz(str) < length) return {};
  H h = 0, pw = 1;
  rep(i,0,length)
    h = h * C + str[i], pw = pw * C;
  vector<H> ret = {h};
  rep(i,length,sz(str)) {
    ret.push_back(h = h * C + str[i] - pw * str[i-length]);
  }
  return ret;
}

H hashString(string& s){H h{}; for(char c:s) h=h*C+c;return h;}
```

Hashing2D.h

Description: Hashing 2D.
Time: $\mathcal{O}(N * M)$

703e4d, 42 lines

```
struct Hashing {
  vector<vector<int>> hs;
  vector<int> PWX, PWY;
  int n, m;
  static const int PX = 3731,  PY = 2999, mod = 998244353;
  Hashing() {}
  Hashing(vector<string>& s) {
    n = (int)s.size(), m = (int)s[0].size();
    hs.assign(n + 1, vector<int>(m + 1, 0));
    PWX.assign(n + 1, 1);
    PWY.assign(m + 1, 1);
    for (int i = 0; i < n; i++) PWX[i + 1] = 1LL * PWX[i] * PX
        % mod;
    for (int i = 0; i < m; i++) PWY[i + 1] = 1LL * PWY[i] * PY
        % mod;
    for (int i = 0; i < n; i++) {
    for (int j = 0; j < m; j++) {
      hs[i + 1][j + 1] = s[i][j] - 'a' + 1;
    }
    }
    for (int i = 0; i <= n; i++) {
    for (int j = 0; j < m; j++) {
      hs[i][j + 1] = (hs[i][j + 1] + 1LL * hs[i][j] * PY % mod)
          % mod;
    }
    }
    for (int i = 0; i < n; i++) {
    for (int j = 0; j <= m; j++) {
      hs[i + 1][j] = (hs[i + 1][j] + 1LL * hs[i][j] * PX % mod)
          % mod;
    }
    }
  }
  int get_hash(int x1, int y1, int x2, int y2) { // 1-indexed
    assert(1 <= x1 && x1 <= x2 && x2 <= n);
    assert(1 <= y1 && y1 <= y2 && y2 <= m);
    x1--;
    y1--;
    int dx = x2 - x1, dy = y2 - y1;
    return (1LL * (hs[x2][y2] - 1LL * hs[x2][y1] * PWY[dy] %
        mod + mod) % mod -
      1LL * (hs[x1][y2] - 1LL * hs[x1][y1] * PWY[dy] % mod +
          mod) % mod * PWX[dx] % mod + mod) % mod;
  }
  int get_hash() {
    return get_hash(1, 1, n, m);
  }
};
```

AhoCorasick.h

Description: Aho-Corasick automaton, used for multiple pattern matching. Initialize with AhoCorasick ac(patterns); the automaton start node will be at index 0. find(word) returns for each position the index of the longest word that ends there, or -1 if none. findAll(-, word) finds all words (up to $N\sqrt{N}$ many if no duplicate patterns) that start at each position (shortest first). Duplicate patterns are allowed; empty patterns are not. To find the longest words that start at each position, reverse all input. For large alphabets, split each symbol into chunks, with sentinel bits for symbol boundaries.
Time: construction takes $\mathcal{O}(26N)$, where N = sum of length of patterns. find(x) is $\mathcal{O}(N)$, where N = length of x. findAll is $\mathcal{O}(NM)$.

f35677, 66 lines

```
struct AhoCorasick {
  enum {alpha = 26, first = 'A'}; // change this!
  struct Node {
    // (nmatches is optional)
    int back, next[alpha], start = -1, end = -1, nmatches = 0;
    Node(int v) { memset(next, v, sizeof(next)); }
  };
  vector<Node> N;
  vi backp;
  void insert(string& s, int j) {
    assert(!s.empty());
    int n = 0;
    for (char c : s) {
      int& m = N[n].next[c - first];
      if (m == -1) { n = m = sz(N); N.emplace_back(-1); }
      else n = m;
    }
    if (N[n].end == -1) N[n].start = j;
    backp.push_back(N[n].end);
```

```
    N[n].end = j;
    N[n].nmatches++;
  }
  AhoCorasick(vector<string>& pat) : N(1, -1) {
    rep(i,0,sz(pat)) insert(pat[i], i);
    N[0].back = sz(N);
    N.emplace_back(0);

    queue<int> q;
    for (q.push(0); !q.empty(); q.pop()) {
      int n = q.front(), prev = N[n].back;
      rep(i,0,alpha) {
        int &ed = N[n].next[i], y = N[prev].next[i];
        if (ed == -1) ed = y;
        else {
          N[ed].back = y;
          (N[ed].end == -1 ? N[ed].end : backp[N[ed].start])
            = N[y].end;
          N[ed].nmatches += N[y].nmatches;
          q.push(ed);
        }
      }
    }
  }
  vi find(string word) {
    int n = 0;
    vi res; // ll count = 0;
    for (char c : word) {
      n = N[n].next[c - first];
      res.push_back(N[n].end);
      // count += N[n].nmatches;
    }
    return res;
  }
  vector<vi> findAll(vector<string>& pat, string word) {
    vi r = find(word);
    vector<vi> res(sz(word));
    rep(i,0,sz(word)) {
      int ind = r[i];
      while (ind != -1) {
        res[i - sz(pat[ind]) + 1].push_back(ind);
        ind = backp[ind];
      }
    }
    return res;
  }
};
```

Eertree.h

Description: Get the number of unique palindromic substrings online.
Time: $\mathcal{O}(N)$

94ca78, 44 lines

```
struct palindromic_tree{
  struct node{
    int next[26],fail,len;
    int cnt,num,st,ed;
    node(int l=0):fail(0),len(l),cnt(0),num(0){
      for(int i=0;i<26;++i)next[i]=0;
    }
  };
  vector<node> state;
  vector<char> s;
  int last,n;

  void init(){
    state.clear();
    s.clear();
    last=1;
    n=0;
    state.push_back(0);
    state.push_back(-1);
    state[0].fail=1;
    s.push_back(-1);
  }
  int get_fail(int x){
    while(s[n-state[x].len-1]!=s[n])x=state[x].fail;
    return x;
  }
  void add(int c){
    s.push_back(c-='a');
    ++n;
    int cur=get_fail(last);
    if(!state[cur].next[c]){
      int now=state.size();
      state.push_back(state[cur].len+2);
      state[now].fail=state[get_fail(state[cur].fail)].next[c];
      state[cur].next[c]=now;
      state[now].num=state[state[now].fail].num+1;
    }
    last=state[cur].next[c];
    ++state[last].cnt;
  }
  int size(){
    return state.size()-2;
  }
} pt;
```

CyclicSort.h

Description: Sort string cyclic shifts
Time: $\mathcal{O}(NlogN)$

930bd4, 35 lines

```
vi sort_cyclic_shifts(const string& s) {
    int n = s.size();
    const int alphabet = 256;
    vi p(n), c(n), cnt(max(alphabet, n), 0);
    rep(i,0,n) cnt[s[i]]++;
    rep(i,1,alphabet) cnt[i] += cnt[i-1];
    rep(i,0,n) p[--cnt[s[i]]] = i;
    c[p[0]] = 0;
    int classes = 1;
    rep(i,1,n) {
        if (s[p[i]] != s[p[i-1]]) classes++;
        c[p[i]] = classes - 1;
    }
    vi pn(n), cn(n);
    for (int h = 0; (1 << h) < n; ++h) {
        rep(i,0,n) {
            pn[i] = p[i] - (1 << h);
            if (pn[i] < 0) pn[i] += n;
        }
        fill(cnt.begin(), cnt.begin() + classes, 0);
        rep(i,0,n) cnt[c[pn[i]]]++;
        rep(i,1,classes) cnt[i] += cnt[i-1];
        for (int i = n-1; i >= 0; i--) p[--cnt[c[pn[i]]]] = pn[
            i];
        cn[p[0]] = 0;
        classes = 1;
        rep(i,1,n) {
            pii cur = {c[p[i]], c[(p[i] + (1 << h)) % n]};
            pii prev = {c[p[i-1]], c[(p[i-1] + (1 << h)) % n]};
            if (cur != prev) ++classes;
            cn[p[i]] = classes - 1;
        }
        c.swap(cn);
    }
    return p;
}
```

Various (10)

10.1 Intervals

IntervalContainer.h

Description: Add and remove intervals from a set of disjoint intervals. Will merge the added interval with any overlapping intervals in the set when adding. Intervals are [inclusive, exclusive).
Time: $\mathcal{O}(\log N)$

edce47, 23 lines

```
set<pii>::iterator addInterval(set<pii>& is, int L, int R) {
  if (L == R) return is.end();
  auto it = is.lower_bound({L, R}), before = it;
  while (it != is.end() && it->first <= R) {
    R = max(R, it->second);
    before = it = is.erase(it);
  }
  if (it != is.begin() && (--it)->second >= L) {
    L = min(L, it->first);
    R = max(R, it->second);
    is.erase(it);
  }
  return is.insert(before, {L,R});
}

void removeInterval(set<pii>& is, int L, int R) {
  if (L == R) return;
  auto it = addInterval(is, L, R);
  auto r2 = it->second;
  if (it->first == L) is.erase(it);
  else (int&)it->second = L;
  if (R != r2) is.emplace(R, r2);
}
```

IntervalCover.h

Description: Compute indices of smallest set of intervals covering another interval. Intervals should be [inclusive, exclusive). To support [inclusive, inclusive], change (A) to add `|| R.empty()`. Returns empty set on failure (or if G is empty).
Time: $\mathcal{O}(N \log N)$

9e9d8d, 19 lines

```
template<class T>
vi cover(pair<T, T> G, vector<pair<T, T>> I) {
  vi S(sz(I)), R;
  iota(all(S), 0);
  sort(all(S), [&](int a, int b) { return I[a] < I[b]; });
  T cur = G.first;
  int at = 0;
  while (cur < G.second) { // (A)
    pair<T, int> mx = make_pair(cur, -1);
    while (at < sz(I) && I[S[at]].first <= cur) {
      mx = max(mx, make_pair(I[S[at]].second, S[at]));
      at++;
    }
    if (mx.second == -1) return {};
    cur = mx.first;
    R.push_back(mx.second);
  }
  return R;
}
```

ConstantIntervals.h

Description: Split a monotone function on [from, to) into a minimal set of half-open intervals on which it has the same value. Runs a callback g for each such interval.
Usage: `constantIntervals(0, sz(v), [&](int x){return v[x];}, [&](int lo, int hi, T val){...});`
Time: $\mathcal{O}\left(k \log \frac{n}{k}\right)$

753a4c, 19 lines

```
template<class F, class G, class T>
void rec(int from, int to, F& f, G& g, int& i, T& p, T q) {
  if (p == q) return;
  if (from == to) {
    g(i, to, p);
    i = to; p = q;
  } else {
    int mid = (from + to) >> 1;
    rec(from, mid, f, g, i, p, f(mid));
    rec(mid+1, to, f, g, i, p, q);
  }
}
template<class F, class G>
void constantIntervals(int from, int to, F f, G g) {
  if (to <= from) return;
  int i = from; auto p = f(i), q = f(to-1);
  rec(from, to-1, f, g, i, p, q);
  g(i, to, q);
}
```

10.2 Misc. algorithms

TernarySearch.h

Description: Find the smallest i in $[a, b]$ that maximizes $f(i)$, assuming that $f(a) < \ldots < f(i) \geq \cdots \geq f(b)$. To reverse which of the sides allows non-strict inequalities, change the < marked with (A) to <=, and reverse the loop at (B). To minimize f, change it to >, also at (B).
Usage: `int ind = ternSearch(0,n-1,[&](int i){return a[i];});`
Time: $\mathcal{O}(\log(b-a))$

9155b4, 11 lines

```
template<class F>
int ternSearch(int a, int b, F f) {
  assert(a <= b);
  while (b - a >= 5) {
    int mid = (a + b) / 2;
    if (f(mid) < f(mid+1)) a = mid; // (A)
    else b = mid+1;
  }
  rep(i,a+1,b+1) if (f(a) < f(i)) a = i; // (B)
  return a;
}
```

LIS.h

Description: Compute indices for the longest increasing subsequence.
Time: $\mathcal{O}(N \log N)$

2932a0, 17 lines

```
template<class I> vi lis(const vector<I>& S) {
  if (S.empty()) return {};
  vi prev(sz(S));
  typedef pair<I, int> p;
  vector<p> res;
  rep(i,0,sz(S)) {
    // change 0 -> i for longest non-decreasing subsequence
    auto it = lower_bound(all(res), p{S[i], 0});
    if (it == res.end()) res.emplace_back(), it = res.end()-1;
    *it = {S[i], i};
    prev[i] = it == res.begin() ? 0 : (it-1)->second;
  }
  int L = sz(res), cur = res.back().second;
  vi ans(L);
  while (L--) ans[L] = cur, cur = prev[cur];
  return ans;
}
```

FastKnapsack.h

Description: Given N non-negative integer weights w and a non-negative target t, computes the maximum S <= t such that S is the sum of some subset of the weights.
Time: $\mathcal{O}(N \max(w_i))$

b20ccc, 16 lines

```
int knapsack(vi w, int t) {
  int a = 0, b = 0, x;
  while (b < sz(w) && a + w[b] <= t) a += w[b++];
  if (b == sz(w)) return a;
  int m = *max_element(all(w));
  vi u, v(2*m, -1);
  v[a+m-t] = b;
  rep(i,b,sz(w)) {
    u = v;
    rep(x,0,m) v[x+w[i]] = max(v[x+w[i]], u[x]);
    for (x = 2*m; --x > m;) rep(j, max(0,u[x]), v[x])
      v[x-w[j]] = max(v[x-w[j]], j);
  }
  for (a = t; v[a+m-t] < 0; a--) ;
  return a;
}
```

Submasks.h

Description: Enumerate every mask and submasks
Time: $\mathcal{O}(3^n)$

d4afb8, 3 lines

```
for (int m=0; m<(1<<n); ++m)
    for (int s=m; s; s=(s-1)&m)
 ... s and m ...
```

DynamicBitset.h

Description: Allows different bitset sizes (compile time)
Time: $\mathcal{O}(logn)$

613641, 8 lines

```
template <int len = 1>
void solve(int n) {
    if (n > len) {
        solve<std::min(len*2, MAXLEN)>(n);
        return;
    }
    // solution using bitset<len>
}
```

10.3 Dynamic programming

KnuthDP.h

Description: When doing DP on intervals: $a[i][j] = \min_{i<k<j}(a[i][k] + a[k][j]) + f(i,j)$, where the (minimal) optimal k increases with both i and j, one can solve intervals in increasing order of length, and search $k = p[i][j]$ for $a[i][j]$ only between $p[i][j-1]$ and $p[i+1][j]$. This is known as Knuth DP. Sufficient criteria for this are if $f(b,c) \leq f(a,d)$ and $f(a,c) + f(b,d) \leq f(a,d) + f(b,c)$ for all $a \leq b \leq c \leq d$. Consider also: LineContainer (ch. Data structures), monotone queues, ternary search.
Time: $\mathcal{O}(N^2)$

DivideAndConquerDP.h

Description: Given $a[i] = \min_{lo(i)\leq k<hi(i)}(f(i,k))$ where the (minimal) optimal k increases with i, computes $a[i]$ for $i = L..R-1$.
Time: $\mathcal{O}((N + (hi - lo))\log N)$

d38d2b, 18 lines

```
struct DP { // Modify at will:
  int lo(int ind) { return 0; }
  int hi(int ind) { return ind; }
  ll f(int ind, int k) { return dp[ind][k]; }
  void store(int ind, int k, ll v) { res[ind] = pii(k, v); }

  void rec(int L, int R, int LO, int HI) {
    if (L >= R) return;
    int mid = (L + R) >> 1;
    pair<ll, int> best(LLONG_MAX, LO);
    rep(k, max(LO,lo(mid)), min(HI,hi(mid)))
      best = min(best, make_pair(f(mid, k), k));
    store(mid, best.second, best.first);
    rec(L, mid, LO, best.second+1);
    rec(mid+1, R, best.second, HI);
  }
  void solve(int L, int R) { rec(L, R, INT_MIN, INT_MAX); }
};
```

10.4 Debugging tricks

- `signal(SIGSEGV, [](int) { _Exit(0); });` converts segfaults into Wrong Answers. Similarly one can catch SIGABRT (assertion failures) and SIGFPE (zero divisions). `_GLIBCXX_DEBUG` failures generate SIGABRT (or SIGSEGV on gcc 5.4.0 apparently).
- `feenableexcept(29);` kills the program on NaNs (1), 0-divs (4), infinities (8) and denormals (16).

10.5 Optimization tricks

`__builtin_ia32_ldmxcsr(40896);` disables denormals (which make floats 20x slower near their minimum value).

10.5.1 Bit hacks

- `x & -x` is the least bit in `x`.
- `for (int x = m; x; ) { --x &= m; ... }` loops over all subset masks of `m` (except `m` itself).
- `c = x&-x, r = x+c; (((r^x) >> 2)/c) | r` is the next number after `x` with the same number of bits set.
- `rep(b,0,K) rep(i,0,(1 << K)) if (i & 1 << b) D[i] += D[i^(1 << b)];` computes all sums of subsets.

10.5.2 Pragmas

- `#pragma GCC optimize ("Ofast")` will make GCC auto-vectorize loops and optimizes floating points better.
- `#pragma GCC target ("avx2")` can double performance of vectorized code, but causes crashes on old machines.
- `#pragma GCC optimize ("trapv")` kills the program on integer overflows (but is really slow).

FastMod.h

Description: Compute $a\%b$ about 5 times faster than usual, where b is constant but not known at compile time. Returns a value congruent to a (mod b) in the range $[0, 2b)$.

751a02, 8 lines

```
typedef unsigned long long ull;
struct FastMod {
  ull b, m;
  FastMod(ull b) : b(b), m(-1ULL / b) {}
  ull reduce(ull a) { // a % b + (0 or b)
    return a - (ull)((__uint128_t(m) * a) >> 64) * b;
  }
};
```

FastInput.h

Description: Read an integer from stdin. Usage requires your program to pipe in input from file.
Usage: `./a.out < input.txt`

Time: About 5x as fast as cin/scanf.

7b3c70, 17 lines

```
inline char gc() { // like getchar()
  static char buf[1 << 16];
  static size_t bc, be;
  if (bc >= be) {
    buf[0] = 0, bc = 0;
    be = fread(buf, 1, sizeof(buf), stdin);
  }
  return buf[bc++]; // returns 0 on EOF
}

int readInt() {
  int a, c;
  while ((a = gc()) < 40);
  if (a == '-') return -readInt();
  while ((c = gc()) >= 48) a = a * 10 + c - 480;
  return a - 48;
}
```

BumpAllocator.h

Description: When you need to dynamically allocate many objects and don't care about freeing them. "new X" otherwise has an overhead of something like 0.05us + 16 bytes per allocation.

745db2, 8 lines

```
// Either globally or in a single class:
static char buf[450 << 20];
void* operator new(size_t s) {
  static size_t i = sizeof buf;
  assert(s < i);
  return (void*)&buf[i -= s];
}
void operator delete(void*) {}
```

SmallPtr.h

Description: A 32-bit pointer that points into BumpAllocator memory.

"BumpAllocator.h" 2dd6c9, 10 lines

```
template<class T> struct ptr {
  unsigned ind;
  ptr(T* p = 0) : ind(p ? unsigned((char*)p - buf) : 0) {
    assert(ind < sizeof buf);
  }
  T& operator*() const { return *(T*)(buf + ind); }
  T* operator->() const { return &**this; }
  T& operator[](int a) const { return (&**this)[a]; }
  explicit operator bool() const { return ind; }
};
```

BumpAllocatorSTL.h

Description: BumpAllocator for STL containers.

Usage: vector<vector<int, small<int>>> ed(N);

bb66d4, 14 lines

```
char buf[450 << 20] alignas(16);
size_t buf_ind = sizeof buf;

template<class T> struct small {
  typedef T value_type;
  small() {}
  template<class U> small(const U&) {}
  T* allocate(size_t n) {
    buf_ind -= n * sizeof(T);
    buf_ind &= 0 - alignof(T);
    return (T*)(buf + buf_ind);
  }
  void deallocate(T*, size_t) {}
};
```

SIMD.h

Description: Cheat sheet of SSE/AVX intrinsics, for doing arithmetic on several numbers at once. Can provide a constant factor improvement of about 4, orthogonal to loop unrolling. Operations follow the pattern "_mm(256)?_name_(si(128|256)|epi(8|16|32|64)|pd|ps)". Not all are described here; grep for _mm_ in /usr/lib/gcc/*/4.9/include/ for more. If AVX is unsupported, try 128-bit operations, "emmintrin.h" and #define __SSE__ and __MMX__ before including it. For aligned memory use _mm_malloc(size, 32) or int buf[N] alignas(32), but prefer loadu/storeu.

551b82, 43 lines

```
#pragma GCC target ("avx2") // or sse4.1
#include "immintrin.h"

typedef __m256i mi;
#define L(x) _mm256_loadu_si256((mi*)&(x))

// High-level/specific methods:
// load(u)?_si256, store(u)?_si256, setzero_si256, _mm_malloc
// blendv_(epi8|ps|pd) (z?y:x), movemask_epi8 (hibits of bytes)
// i32gather_epi32(addr, x, 4): map addr[] over 32-b parts of x
// sad_epu8: sum of absolute differences of u8, outputs 4xi64
// maddubs_epi16: dot product of unsigned i7's, outputs 16xi15
// madd_epi16: dot product of signed i16's, outputs 8xi32
// extractf128_si256(, i) (256->128), cvtsi128_si32 (128->lo32)
// permute2f128_si256(x,x,1) swaps 128-bit lanes
// shuffle_epi32(x, 3*64+2*16+1*4+0) == x for each lane
// shuffle_epi8(x, y) takes a vector instead of an imm

// Methods that work with most data types (append e.g. _epi32):
// set1, blend (i8?x:y), add, adds (sat.), mullo, sub, and/or,
// andnot, abs, min, max, sign(1,x), cmp(gt|eq), unpack(lo|hi)

int sumi32(mi m) { union {int v[8]; mi m;} u; u.m = m;
  int ret = 0; rep(i,0,8) ret += u.v[i]; return ret; }
mi zero() { return _mm256_setzero_si256(); }
mi one() { return _mm256_set1_epi32(-1); }
bool all_zero(mi m) { return _mm256_testz_si256(m, m); }
bool all_one(mi m) { return _mm256_testc_si256(m, one()); }

ll example_filteredDotProduct(int n, short* a, short* b) {
  int i = 0; ll r = 0;
  mi zero = _mm256_setzero_si256(), acc = zero;
  while (i + 16 <= n) {
    mi va = L(a[i]), vb = L(b[i]); i += 16;
    va = _mm256_and_si256(_mm256_cmpgt_epi16(vb, va), va);
    mi vp = _mm256_madd_epi16(va, vb);
    acc = _mm256_add_epi64(_mm256_unpacklo_epi32(vp, zero),
      _mm256_add_epi64(acc, _mm256_unpackhi_epi32(vp, zero)));
  }
  union {ll v[4]; mi m;} u; u.m = acc; rep(i,0,4) r += u.v[i];
  for (;i<n;++i) if (a[i] < b[i]) r += a[i]*b[i]; // <- equiv
  return r;
}
```

10.6 JM

DigitDP.h

Description: DigitDP

Time: $\mathcal{O}(dim)$

7a4636, 33 lines

```
int low[20], high[20];
ll best[20][2][2][2];
int choose[20][2][2][2];

void init(){
    memset(best, -1, sizeof(best));
    memset(choose, -1, sizeof(choose));
}
// xd
ll dfs(int pos, int positive = 0, int smaller = 0, int bigger =
    0){
    if(pos < 0){ return 1; }
    auto &memo = best[pos][positive][smaller][bigger];
    if(memo != -1) return memo;

    int mxd = smaller ? 9 : high[pos];
    int mnd = bigger  ? 0 : low[pos];

    ll mxprod = 0;
    rep(d, mnd, mxd + 1){
        int phere = positive || d;
        int shere = smaller || d < high[pos];
        int bhere = bigger || d > low[pos];

        ll anshere = dfs(pos - 1, phere, shere, bhere);
        if(phere) anshere *= d;

        if(mxprod < anshere){
            choose[pos][positive][smaller][bigger] = d;
            mxprod = anshere;
        }
    }
    return memo = mxprod;
}
```

DiscreteLog.h

Description: DiscreteLog

Time: $\mathcal{O}\left(\sqrt{\text{mod}}\right)$

6f8096, 51 lines

```
// Returns minimal $x >= 0$ with $a ^ x  b (mod mod)$, or -1 if
    none.
ll discrete_log(int a, int b){
    a %= mod; b %= mod;

    if (mod == 1) return 0;
    if (b == 1 % mod) return 0; // x = 0 works

    int remain = 1, extra = 0;
    int g = gcd(a, mod);

    // Strip gcd factors while possible
    while (g != 1){
        if (b == remain) return extra;      // matched already
        if (b % g) return -1;               // impossible
        b /= g; mod /= g;                   // reduce modulus
            and target
        remain = mul(remain, a / g);        // accumulate
            factor
        ++extra;
        g = std::gcd(a, mod);
    }

    // Now gcd(a, mod) == 1 -> standard BSGS
    int n = sqrt(mod) + 1;

    // Baby steps: store $b * a^j$
    vii baby; baby.reserve(n);
    int cur = b;
    rep(j, 0, n){
        baby.emplace_back(cur, j);
        cur = mul(cur, a);
    }
    sort(all(baby));

    // Giant steps: multiply $remain * (a^n)^i$ and binary
        search
    int step = binpow(a, n);
    int giant = remain;
```

```
    rep(i, 1, n + 1){
        giant = mul(giant, step);

        int l = -1, r = sz(baby);
        while (r - l > 1){
            int mid = l + r >> 1;
            if (baby[mid].first <= giant) l = mid;
            else r = mid;
        }
        if (l != -1 && baby[l].first == giant){
            ll x = 1LL * i * n - baby[l].second + extra;
            if (x >= 0) return x; // minimal by construction
        }
    }
    return -1;
}
```

DiscreteRootCPAlgo.h

Description: DiscreteRoot
Time: $\mathcal{O}\left(\sqrt{n}\log n\right)$

73612c, 68 lines

```
// Finds the primitive root modulo p ptsmre xddx sda
int generator(int p) {
    vector<int> fact;
    int phi = p-1, n = phi;
    for (int i = 2; i * i <= n; ++i) {
        if (n % i == 0) {
            fact.push_back(i);
            while (n % i == 0)
                n /= i;
        }
    }
    if (n > 1)
        fact.push_back(n);

    for (int res = 2; res <= p; ++res) {
        bool ok = true;
        for (int factor : fact) {
            if (powmod(res, phi / factor, p) == 1) {
                ok = false;
                break;
            }
        }
        if (ok) return res;
    }
    return -1;
}

// This program finds all numbers x such that $x^k = a (mod n)$
int solve() {
    int n, k, a;
    scanf("%d %d %d", &n, &k, &a);
    if (a == 0) {
        puts("1\n0");
        return 0;
    }

    int g = generator(n);

    // Baby-step giant-step discrete logarithm algorithm
    int sq = (int) sqrt (n + .0) + 1;
    vector<pair<int, int>> dec(sq);
    for (int i = 1; i <= sq; ++i)
        dec[i-1] = {powmod(g, i * sq * k % (n - 1), n), i};
    sort(dec.begin(), dec.end());
    int any_ans = -1;
    for (int i = 0; i < sq; ++i) {
        int my = powmod(g, i * k % (n - 1), n) * a % n;
        auto it = lower_bound(dec.begin(), dec.end(), make_pair
            (my, 0));
        if (it != dec.end() && it->first == my) {
            any_ans = it->second * sq - i;
            break;
        }
    }
    if (any_ans == -1) {
        puts("0");
        return 0;
    }

    // Print all possible answers
    int delta = (n-1) / gcd(k, n-1);
    vector<int> ans;
    for (int cur = any_ans % delta; cur < n-1; cur += delta)
        ans.push_back(powmod(g, cur, n));
    sort(ans.begin(), ans.end());
    printf("%d\n", ans.size());
    for (int answer : ans)
        printf("%d ", answer);
}
```

DivideAndConquer.h

Description: DyC
Time: $\mathcal{O}(N)$

3a63ad, 31 lines

```
void go(int k, int l, int r, int optl, int optr){
    if(l > r) return;

    int mid = l + r >> 1;
    ll best = NIL; // neutro
    int opt = -1;

    for(int i = optl; i <= min(mid, optr); i++){
        // fix(i, mid); // fix this range(L, R) in O(n)
        ll here = dp[k - 1][i - 1] + cost(i, mid);
        if(here < best){ // act
            best = here;
            opt = i;
        }
    }
    dp[k][mid] = best;

    go(k, l, mid - 1, optl, opt);
    go(k, mid + 1, r, opt, optr);
}

int solve(){
    // precompute cost function

    // init
    rep(i, 0, k + 1) rep(j, 1, n + 1) dp[i][j] = NIL;
    rep(i, 1, n + 1) dp[1][i] = cost(1, i);

    rep(i, 2, k + 1) go(i, 1, n, 1, n);
    cout << dp[k][n] << "\n";
}
```

KnuthDPJM.h

Description: Knuth DP
Time: $\mathcal{O}(N * N)$

6ab62e, 30 lines

```
int solve() {
    int N;
    // read N and input
    int dp[N][N], opt[N][N];

    auto C = [&](int i, int j) {
        // Implement cost function C.
    };

    for (int i = 0; i < N; i++) {
        opt[i][i] = i;
        // Initialize dp[i][i] according to the problem
    }

    for (int i = N-2; i >= 0; i--) {
        for (int j = i+1; j < N; j++) {
            int mn = INT_MAX;
            int cost = C(i, j);
            for (int k = opt[i][j-1]; k <= min(j-1, opt[i+1][j
                ]); k++) {
                if (mn >= dp[i][k] + dp[k+1][j] + cost) {
                    opt[i][j] = k;
                    mn = dp[i][k] + dp[k+1][j] + cost;
                }
            }
            dp[i][j] = mn;
        }
    }

    return dp[0][N-1];
}
```

OpenCloseIntervals.h

Description: DP Open-Close
Time: $\mathcal{O}(M * N * N)$

f1cac1, 27 lines

```
// dp[i][j], i: opened, j: closed
void solve(){
    vvi dp(n + 2, vi (n + 2));
    dp[0][0] = 1;
    rep(pos, 1, m + 1){
        vvi ndp(n + 2, vi(n + 2));
        rep(i, 0, n + 1){
            rep(j, 0, n + 1){
                if(pos != x){
                    // nada
                    add(ndp[i][j], dp[i][j]);
                    // cerrar
                    if(i > j) add(ndp[i][j + 1], dp[i][j]);
                }
                // abrir
                add(ndp[i + 1][j], dp[i][j]);
                // abrir cerrar
                add(ndp[i + 1][j + 1], dp[i][j]);
            }
        }

        swap(dp, ndp);
    }

    int ans = dp[n][n];
    for(int i = 1; i <= n; i++) ans = mul(ans, i);
}
```

Rerooting.h

Description: Rerooting
Time: $\mathcal{O}(N)$

78f3f3, 73 lines

```
struct elem{
    ll subt;
    ll ans;
};

elem E() { return {0, 0}; }
```

```
// add this vertex info
elem take_vertex(elem DP, int v) { return {DP.subt + 1, DP.ans}
    ; }

// e: edge idx, (0 mod 2) => parent
// up root
elem up_root(elem DP, int e) { return {DP.subt, DP.subt + DP.
    ans}; }

// merge childrens
elem merge(elem u, elem v) { return {u.subt + v.subt, u.ans + v
    .ans}; }

void dfs(int x, vector<vector<pii>> &gph, vector<int> &ord,
    vector<int> &pae) {
  ord.push_back(x);
  for (auto &[i, y] : gph[x]) {
    gph[y].erase(find(all(gph[y]), pii{i ^ 1, x}));
    pae[y] = (i ^ 1);
    dfs(y, gph, ord, pae);
  }
}

vector<elem> solve(int n, vector<pii> edges) {
  vector<vector<pii>> gph(n);
  gph.resize(n);
  for (int i = 0; i < n - 1; i++) {
    gph[edges[i].first].push_back({2 * i, edges[i].second});
    gph[edges[i].second].push_back({2 * i + 1, edges[i].first})
        ;
  }
  vector<int> ord;
  vector<int> pae(n, -1);
  dfs(0, gph, ord, pae);
  vector<elem> dp(n, E());
  reverse(all(ord));
  for (auto &z : ord) {
    for (auto &[i, y] : gph[z]) {
      dp[z] = merge(dp[z], up_root(dp[y], i));
    }
    dp[z] = take_vertex(dp[z], z);
  }
  vector<elem> rev_dp(n, E());
  reverse(all(ord));
  for (auto &z : ord) {
    vector<elem> pref(sz(gph[z]) + 1, E());
    vector<elem> suff(sz(gph[z]) + 1, E());
    if (~pae[z])
      pref[0] = up_root(rev_dp[z], pae[z]);
    for (int i = 0; i < sz(gph[z]); i++) {
      pref[i + 1] = suff[i] = up_root(dp[gph[z][i].second], gph
          [z][i].first);
    }
    for (int i = 1; i <= sz(gph[z]); i++)
      pref[i] = merge(pref[i - 1], pref[i]);
    for (int i = sz(gph[z]) - 1; i >= 0; i--)
      suff[i] = merge(suff[i], suff[i + 1]);
    for (int i = 0; i < sz(gph[z]); i++) {
      rev_dp[gph[z][i].second] = take_vertex(merge(pref[i],
          suff[i + 1]), z);
    }
  }
  vector<elem> sln(n, E());
  for (int x = 0; x < n; x++) {
    if (~pae[x])
      sln[x] = up_root(rev_dp[x], pae[x]);
    for (auto &[i, y] : gph[x]) {
      sln[x] = merge(sln[x], up_root(dp[y], i));
    }
    sln[x] = take_vertex(sln[x], x);
  }
  return sln;
}
```

SuffixAutomaton.h

Description: Suffix Automaton
Time: $\mathcal{O}(|s|)$

2b3c49, 97 lines

```
struct SuffixAutomaton {
  int nodes;
  vector<int> link; // suffix link
  vector<int> len; // max length of the state
  vector<int> firstpos; // last position of first occurrence of
      state
  vector<vector<int>> nxt; // transitions
  vector<bool> is_clone; // clone attribute (for counting)

  SuffixAutomaton() {
    len.emplace_back(0);
    link.emplace_back(-1);
    nxt.emplace_back(vector<int>(26, 0));
    firstpos.emplace_back(-1);
    is_clone.emplace_back(false);
    nodes = 1;
  }

  void add_node(int new_len, int new_link, int new_fp, bool
      new_clone) {
    len.emplace_back(new_len);
    link.emplace_back(new_link);
    nxt.emplace_back(vector<int>(26, 0));
    firstpos.emplace_back(new_fp);
    is_clone.emplace_back(new_clone);
  }

  int add(int p, int c) {
    auto getNxt = [&] () {
      if (p == -1) return 0;
      int q = nxt[p][c];
      if (len[p] + 1 == len[q]) return q;
      int clone = nodes++;
      add_node(len[p] + 1, link[q], firstpos[q], true);
      nxt[nodes - 1] = nxt[q];
      link[q] = clone;
      while(~p and nxt[p][c] == q) {
        nxt[p][c] = clone;
        p = link[p];
      }
      return clone;
    };
    // if (nxt[c][p]) return getNxt();
    // ^ need if adding > 1 string
    int cur = nodes++; // make new state
    add_node(len[p] + 1, -1, firstpos[p] + 1, false);
    while(~p and !nxt[p][c]) {
      nxt[p][c] = cur;
      p = link[p];
    }
    int x = getNxt();
    link[cur] = x;
    return cur;
  }

  void init(string s) { // add string to automaton
    int p = 0;
    for(auto c : s) {
      p = add(p, c - 'a');
    }
  }
};
```

CentroidCollect.h

Description: Centroid Decomposition with collect.
Time: $\mathcal{O}(NlogN)$, excluding processing.

f9cb55, 75 lines

```
struct CentroidCollect {
    int n;
    vvi g;
    vi sub, dead, par;

    CentroidCollect(int n) :
        n(n), g(n), sub(n), dead(n), par(n, -1) {}

    void add_edge(int u, int v) {
        g[u].push_back(v);
        g[v].push_back(u);
    }

    int dfs(int u, int p = -1) {
        sub[u] = 1;
        for(int v : g[u]) {
            if(v == p || dead[v]) continue;
            sub[u] += dfs(v, u);
        }
        return sub[u];
    }

    int find_centroid(int u, int p, int total) {
        for(int v : g[u]) {
  }

    void print(int u){
        for(int i = 0; i < 26; i++){
            if(!nxt[u][i]) continue;
            cout << u << " " << nxt[u][i] << " " << char(i + 'a
                ') << "\n";
            print(nxt[u][i]);
        }
    }

    void countDistinctSubstrings(int n) {
    vector<long long> dis(nodes, 0);
    vector<int> vis(nodes, 0);
    queue<int> q;
    q.emplace(0);
    while(!q.empty()){
      int u = q.front(); q.pop();
      for(int c = 0; c < 26; c++){
        if(!nxt[u][c]) continue;
        if(vis[nxt[u][c]]) continue;
        vis[nxt[u][c]] = 1;
        dis[nxt[u][c]] = dis[u] + 1;
        q.emplace(nxt[u][c]);
      }
    }

    vector<int> ans(n + 2, 0);
    for(int i = 1; i < nodes; i++) {
      ans[dis[i]]++;
      ans[len[i] + 1]--;
    }

    for(int i = 1; i <= n; i++) ans[i] += ans[i - 1];

    for(int i = 1; i <= n; i++) cout << ans[i] << " ";
    cout << "\n";
    }

};
```

```
            if(v == p || dead[v]) continue;
            if(sub[v] > total / 2)
                return find_centroid(v, u, total);
        }
        return u;
    }

    void collect(int u, int p, int d, vii &v) {
        v.push_back({u, d});
        for(int to : g[u]) {
            if(to == p || dead[to]) continue;
            collect(to, u, d + 1, v);
        }
    }

    void process(int c, vii &all, vector<vii> &branches) {
        // Compute the contribution of centroid c here.
    }

    void decompose(int u, int p = -1) {
        int total = dfs(u);
        int c = find_centroid(u, -1, total);
        par[c] = p;
        dead[c] = 1;

        vii all = {{c, 0}};
        vector<vii> branches;

        for(int v : g[c]) {
            if(dead[v]) continue;

            vii here;
            collect(v, c, 1, here);

            all.insert(all.end(), here.begin(), here.end());
            branches.push_back(move(here));
        }

        process(c, all, branches);

        for(int v : g[c]) {
            if(!dead[v]) decompose(v, c);
        }
    }

    void solve() {
        fill(all(dead), 0);
        fill(all(par), -1);
        if(n) decompose(0);
    }
};
```

PalindromeDigitDP.h

Description: Counts palindromic integers in [0, X] using Digit DP. Builds the number digit by digit and checks symmetric positions using curr[]. Leading zeros are ignored, and memoized results are reused only when the current number is smaller than X.
Usage: `solve(R) - solve(L - 1)`
Time: $\mathcal{O}\left(D^2 * 10\right)$, where D is the number of digits. 09f56e, 64 lines

```
const int max_num_digits = 20;
int high[20], curr[20];
ll dp[20][20][2][2];

void init() {
    memset(dp, -1, sizeof(dp));
}

ll dfs(int start, int cur, int palin, int smaller) {
    if(cur < 0) {
        return palin;
    }

    if(smaller && dp[start][cur][palin][smaller] != -1) {
        return dp[start][cur][palin][smaller];
    }

    int mx_digit = 9;
    if(!smaller) mx_digit = high[cur];

    ll ans = 0;
    for(int xth_digit = 0; xth_digit <= mx_digit; xth_digit++)
         {
        curr[cur] = xth_digit;

        if(start == cur && xth_digit == 0) {
            ans += dfs(
                start - 1,
                cur - 1,
                palin,
                smaller || high[cur] > xth_digit
            );
        }
        else if(palin && cur < (start + 1) / 2) {
            ans += dfs(
                start,
                cur - 1,
                curr[start - cur] == xth_digit,
                smaller || high[cur] > xth_digit
            );
        }
        else {
            ans += dfs(
                start,
                cur - 1,
                palin,
                smaller || high[cur] > xth_digit
            );
        }
    }

    return dp[start][cur][palin][smaller] = ans;
}

ll solve(ll val) {
    if(val < 0) return 0;

    init();
    int i = 0;
    while(val) {
        high[i++] = val % 10;
        val /= 10;
    }
    return dfs(i - 1, i - 1, 1, 0);
}
```

DSUIndirection.h

Description: Append x and replace all current x by y (Replace Numbers). root[x] points to the active DSU representative of value x.
Time: $\mathcal{O}\left(logN\right)$ amortized with path compression (no size heuristic). ae74b4, 45 lines

```
struct DSUIndirection {
    vi par, root, val, pos;

    DSUIndirection(int N) : root(N + 1, -1) {}

    int make(int x) {
        int u = sz(par);
        par.push_back(u);
        val.push_back(x);
        return u;
    }

    int get(int u) {
        int r = u;
        while(par[r] != r) r = par[r];
        while(par[u] != u) {
            int v = par[u];
            par[u] = r;
            u = v;
        }
        return r;
    }

    void add(int x) { // Append x
        if(root[x] == -1) root[x] = make(x);
        pos.push_back(root[x]);
    }

    void replace(int x, int y) { // Replace all current x by y
        if(x == y || root[x] == -1) return;
        if(root[y] == -1) {
            root[y] = root[x];
            val[root[y]] = y;
        } else {
            par[root[x]] = root[y];
        }
        root[x] = -1;
    }

    vi result() {
        vi ans;
        for(int u : pos) ans.push_back(val[get(u)]);
        return ans;
    }
};
```

ImplicitSegTree.h

Description: Sparse segment tree: point add and range sum on [L, R). Nodes are created only when an update visits them.
Time: $\mathcal{O}\left(log(R-L)\right)$ per operation, $\mathcal{O}\left(Ulog(R-L)\right)$ memory. 58f3a3, 39 lines

```
struct Vertex{
    int mx;
    Vertex *lc = nullptr, *rc = nullptr;
    Vertex(int val = 0) : mx(val) {}
};

struct Seg{
    int n;
    Vertex *root = nullptr;

    void init(int _n){
        n = _n;
    }

    void upd(Vertex *&v, int l, int r, int pos, int val){
        if(!v) v = new Vertex();
        if(pos < l || pos > r) return;
        if(l == r){
            v->mx = val;
            return;
        }
        int mid = l + r >> 1;
        upd(v->lc, l, mid, pos, val);
        upd(v->rc, mid + 1, r, pos, val);
        v->mx = max(v->lc->mx, v->rc->mx);
```

```
    }
    void upd(int pos, int val){ upd(root, 0, n - 1, pos, val);
         }

    int q(Vertex *v, int l, int r, int lq, int rq){
        if(!v || r < lq || rq < l) return 0;
        if(lq <= l && r <= rq) return v->mx;
        int mid = l + r >> 1;
        return max(
            q(v->lc, l, mid, lq, rq),
            q(v->rc, mid + 1, r, lq, rq)
        );
    }
    int q(int lq, int rq){ return q(root, 0, n - 1, lq, rq); }
};
```

Techniques (A)

techniques.txt 159 lines

```
Recursion
Divide and conquer
  Finding interesting points in N log N
Algorithm analysis
  Master theorem
  Amortized time complexity
Greedy algorithm
  Scheduling
  Max contiguous subvector sum
  Invariants
  Huffman encoding
Graph theory
  Dynamic graphs (extra book-keeping)
  Breadth first search
  Depth first search
  * Normal trees / DFS trees
  Dijkstra's algorithm
  MST: Prim's algorithm
  Bellman-Ford
  Konig's theorem and vertex cover
  Min-cost max flow
  Lovasz toggle
  Matrix tree theorem
  Maximal matching, general graphs
  Hopcroft-Karp
  Hall's marriage theorem
  Graphical sequences
  Floyd-Warshall
  Euler cycles
  Flow networks
  * Augmenting paths
  * Edmonds-Karp
  Bipartite matching
  Min. path cover
  Topological sorting
  Strongly connected components
  2-SAT
  Cut vertices, cut-edges and biconnected components
  Edge coloring
  * Trees
  Vertex coloring
  * Bipartite graphs (=> trees)
  * 3^n (special case of set cover)
  Diameter and centroid
  K'th shortest path
  Shortest cycle
Dynamic programming
  Knapsack
  Coin change
  Longest common subsequence
  Longest increasing subsequence
  Number of paths in a dag
  Shortest path in a dag
  Dynprog over intervals
  Dynprog over subsets
  Dynprog over probabilities
  Dynprog over trees
  3^n set cover
  Divide and conquer
  Knuth optimization
  Convex hull optimizations
  RMQ (sparse table a.k.a 2^k-jumps)
  Bitonic cycle
  Log partitioning (loop over most restricted)
Combinatorics
  Computation of binomial coefficients
  Pigeon-hole principle
  Inclusion/exclusion
  Catalan number
  Pick's theorem
Number theory
  Integer parts
  Divisibility
  Euclidean algorithm
  Modular arithmetic
  * Modular multiplication
  * Modular inverses
  * Modular exponentiation by squaring
  Chinese remainder theorem
  Fermat's little theorem
  Euler's theorem
  Phi function
  Frobenius number
  Quadratic reciprocity
  Pollard-Rho
  Miller-Rabin
  Hensel lifting
  Vieta root jumping
Game theory
  Combinatorial games
  Game trees
  Mini-max
  Nim
  Games on graphs
  Games on graphs with loops
  Grundy numbers
  Bipartite games without repetition
  General games without repetition
  Alpha-beta pruning
Probability theory
Optimization
  Binary search
  Ternary search
  Unimodality and convex functions
  Binary search on derivative
Numerical methods
  Numeric integration
  Newton's method
  Root-finding with binary/ternary search
  Golden section search
Matrices
  Gaussian elimination
  Exponentiation by squaring
Sorting
  Radix sort
Geometry
  Coordinates and vectors
  * Cross product
  * Scalar product
  Convex hull
  Polygon cut
  Closest pair
  Coordinate-compression
  Quadtrees
  KD-trees
  All segment-segment intersection
Sweeping
  Discretization (convert to events and sweep)
  Angle sweeping
  Line sweeping
  Discrete second derivatives
Strings
  Longest common substring
  Palindrome subsequences
  Knuth-Morris-Pratt
  Tries
  Rolling polynomial hashes
  Suffix array
  Suffix tree
  Aho-Corasick
  Manacher's algorithm
  Letter position lists
Combinatorial search
  Meet in the middle
  Brute-force with pruning
  Best-first (A*)
  Bidirectional search
  Iterative deepening DFS / A*
Data structures
  LCA (2^k-jumps in trees in general)
  Pull/push-technique on trees
  Heavy-light decomposition
  Centroid decomposition
  Lazy propagation
  Self-balancing trees
  Convex hull trick (wcipeg.com/wiki/Convex_hull_trick)
  Monotone queues / monotone stacks / sliding queues
  Sliding queue using 2 stacks
  Persistent segment tree
```