

Adjoint Computational Electromagnetics Eigenvalue Problems

Mohamed Kamal Abd Elrahman

6 October, Giza,

Egypt

November 5, 2019

The sensitivities of eigenvalues and eigenvectors due to perturbations in the design variables are derived. The focus here is on linear, isotropic, nonmagnetic and transparent materials ¹.

¹ In transparent materials, both ϵ and μ are real and positive.

Problem Formulation

Maxwell's equation for reads

$$\nabla \times \mathbf{E} = -j\mu_0\omega\mathbf{H} \quad (1a)$$

$$\nabla \times \mathbf{H} = j\omega\epsilon_0\epsilon(r)\mathbf{E} \quad (1b)$$

which can be combined into a single PDE ²

$$\nabla \times \frac{1}{\epsilon} \nabla \times \mathbf{H} = \left(\frac{\omega}{c}\right)^2 \mathbf{H} \quad (2)$$

² We will refer to this equation as the master equation.

Equation. 2 is a standard eigenvalue problem of the form,

$$Ax = \lambda x \quad (3)$$

where we have identified the operator $A = \nabla \times \nabla \times$ and the eigenvector $x = \mathbf{E}$ with associated eigenvalue $\lambda = \omega^2$. The operator A can be shown to be hermitian and positive-semidefinite. The eigenmodes can be normalized

$$x^T x = 1 \quad (4)$$

Sensitivity Derivatives (Nondegenerate)