

Model Analysis Report

GEV Hazard Model

MKM-GH-001

Report Date: 27 March 2026

Governance Framework: SR 11-7 / SS1/23 Model Risk Management

Contents

1	Sensitivity Analysis	2
2	Stress Testing	2
2.1	Stress Scenarios	2
3	Model Performance	3

1 Sensitivity Analysis

This section presents the sensitivity of model outputs to key input parameters. Parameter perturbation ranges are chosen to cover plausible operating conditions and stress scenarios as required under SR 11-7 guidance.

Table 1: GEV return levels and exceedance by shape parameter ($\mu = 2.0$ m, $\sigma = 0.5$ m).

ξ	Tail Type	10-yr RL (m)	50-yr RL (m)	100-yr RL (m)	$P(X > 3.0)$
-0.2000	Weibull	3.42	4.96	5.77	0.1697
-0.1000	Weibull	3.26	4.39	4.92	0.1491
0.0000	Gumbel	3.12	3.95	4.30	0.1266
0.1000	Fréchet	3.01	3.62	3.84	0.1018
0.2000	Fréchet	2.91	3.35	3.50	0.0748
0.3000	Fréchet	2.82	3.15	3.25	0.0461

Table 2: GEV return levels by scale parameter ($\xi = 0$, $\mu = 2.0$ m).

σ	10-yr RL (m)	50-yr RL (m)	100-yr RL (m)	$P(X > 3.0)$
0.2000	2.45	2.78	2.92	0.0067
0.3000	2.67	3.17	3.38	0.0350
0.5000	3.12	3.95	4.30	0.1266
0.7000	3.58	4.73	5.22	0.2131
1.00	4.25	5.90	6.60	0.3078

Table 3: Poisson term structure: cumulative flood probability by year.

λ_{annual}	$P(\leq 1\text{yr})$	$P(\leq 2\text{yr})$	$P(\leq 3\text{yr})$	$P(\leq 4\text{yr})$	$P(\leq 5\text{yr})$
0.0100	0.0100	0.0198	0.0296	0.0392	0.0488
0.0200	0.0198	0.0392	0.0582	0.0769	0.0952
0.0500	0.0488	0.0952	0.1393	0.1813	0.2212
0.1000	0.0952	0.1813	0.2592	0.3297	0.3935

2 Stress Testing

This section documents stress testing scenarios applied to the model under extreme but plausible conditions.

2.1 Stress Scenarios

Table 4: Stress testing scenarios for GEV Hazard Model.

Scenario	Parameter Shock	Severity	Status
Baseline	No shock	—	Passed
Moderate stress	+2 σ inputs	Medium	Pending
Severe stress	+3 σ inputs	High	Pending
Reverse stress	Output threshold breach	Critical	Pending

Detailed stress test results will be populated as scenarios are executed. Refer to the model's validation plan for the full stress testing programme.

3 Model Performance

This section tracks key performance metrics for the model across validation and production environments.

Table 5: Performance metrics for GEV Hazard Model.

Metric	Value	Status
Unit test pass rate	See Test Results	—
Execution time (single run)	TBD	—
Numerical stability	TBD	—
Reproducibility	Deterministic	OK

This report is produced automatically; human review is required before formal model approval. Supporting artefacts are available in the model documentation directory.