

Event Frequency Model (MKM-EF-001)

Wolfram Oracle Benchmark of Annualisation, Tenor Probability, Compound Loss and Count Families

MKM Research Labs

Version 0.1 — 26-October-2026

David K Kelly

CONFIDENTIAL — PROPRIETARY

Legal Notice

PROPRIETARY AND CONFIDENTIAL

This document, including all algorithms, models, methodology, formulas, calculations, and intellectual concepts contained herein, constitutes the exclusive intellectual property and confidential trade secrets of MKM Research Labs ("MKM").

Any usage, reproduction, distribution, modification, or disclosure of this document or any portion thereof, without the express prior written authorisation from MKM Research Labs is strictly prohibited and constitutes an infringement of intellectual property rights.

The document is provided on an "as is" basis. MKM Research Labs makes no representations or warranties of any kind, express or implied, regarding its accuracy, reliability, or suitability for any particular purpose.

All rights reserved. © 2021–2026 MKM Research Labs.

Governed by the laws of the United Kingdom.

Contents

1 Executive Summary **3**

2 Model Purpose and Scope **3**

2.1 What is benchmarked 3

2.2 What is not 4

3 Mathematical Framework **4**

4 Benchmark Method **4**

5 Validation and Backtesting **5**

5.1 The model document's claims 5

5.2 The multi-year term structure 6

6 Model Limitations and Known Weaknesses **6**

7 Document History **6**

1 Executive Summary

This document benchmarks the Event Frequency Model (MKM-EF-001), which turns a gauge's event arrival rate λ and its per-event flood probability p into the annual flood probability every PRS is priced from. It asks whether the code computes what its model document (`event_frequency_plan.pdf`, v2.3) says, and whether what the document says holds.

The code computes its documented formulae. Over 161 cases — arrival rates from 0.5 to 50 a year, per-event probabilities from 10^{-6} to 0.5, tenors of 1 to 10 years with a constant and a growing rate, three loss catalogues and seven count series — every quantity agrees with a 50-digit implementation of the document's equations to better than 10^{-12} (Table 1): the annual probability and rate, the tenor probability, the compound-Poisson average annual loss and its standard error, the dispersion test and its p-values, and both families' log-likelihoods. Wolfram and the 50-digit reference agree to 4.9×10^{-30}, so the reference is confirmed by a second, independent implementation. Wolfram's own maximisation of the Negative Binomial likelihood finds nothing higher than the model's fit.

Findings (Table 2):

1. **The production term structure understates multi-year risk.** The hazard builder compounds the per-year *probabilities* as if they were intensities (`annual_hazard_by_year` into GH-001's `compute_term_structure`). The probability of at least one flood is understated by 0.10% to 17.3% across the grid, worst at one year and high λp, where it is $1-e^{-(1-e^{-\lambda p})}$ rather than $1-e^{-\lambda p}$ (Table 3). The convention is deliberate and documented in the code, to reproduce the earlier term structure; the model's own `term_exceedance_probability` is exact, and the sensitivity module uses it, so the model reports two different tenor probabilities for one gauge.

2. **Annualisation loses precision at small λp.** The code evaluates $1-\exp(-x)$, which cancels: the relative error reaches 1.0×10^{-10} below $\lambda p = 0.0001$. Immaterial at the probabilities priced, and removed exactly by $-\mathrm{expm1}(-x)$.

The document's three numerical claims hold: the closed form of §5.9 is an identity (Wolfram proves it symbolically), the gate statistic's mean $|z|$ is $\sqrt{2/\pi} = 0.798$, and the sampling errors of §7.2 scale as $1/\sqrt{n}$.

Evidence. 12 checks, outcome: all pass (Table 1).

- Wolfram: 15.0.0 for Mac OS X ARM (64-bit) (May 26, 2026) via live kernel session (wolframclient).
- Code under test, at commit `8bbb73347e54`.
- Numerics: numpy 1.26.4, scipy 1.15.1, mpmath 1.4.1.
- Generated 2026-10-26 by `python -m tools.wolfram_oracle ef001`.

2 Model Purpose and Scope

2.1 What is benchmarked

In `src/models/frequency`: `annual_exceedance_probability`, `annual_exceedance_rate` and `annual_hazard_by_year` (`annualise.py`); `term_exceedance_probability` and the rate

processes (`rate_process.py`); `analytic_average_annual_loss` and `loss_standard_error` (`ylt/_reconcile.py`); and the count families, `fit_poisson`, `fit_negbin` and `dispersion_test` (`families/`). With them, `compute_term_structure` in `src/models/hazard/gev.py`, which the per-year hazards feed. Each file is loaded on its own and called as production calls it.

2.2 What is not

The Monte Carlo year simulation is checked by its own reconciliation gate, whose statistic is tested here; the simulation's draws are not. The calibration of λ from gauge records, which the document's §6 and §8 identify as the model's open problem, is not a calculation an oracle can check. This is a benchmark of the implementation (validation question Q8), not independent validation (Q9).

3 Mathematical Framework

With $N \sim \text{Poisson}(\lambda)$ events a year, each flooding independently with probability p, the document's §5.9 gives

$$\mathbb{E}\left[(1-p)^N\right] = e^{-\lambda p}, \qquad P(\text{at least one flood in a year}) = 1 - e^{-\lambda p}, \tag{1}$$

and the aggregate rate λp, which is never smaller. Over a tenor of T years with rates $\lambda_0, \ldots, \lambda_{T-1}$ (constant, or growing geometrically as $\lambda_0(1+g)^y$), the exact tenor probability is $1 - \exp\left(-p\sum_y \lambda_y\right)$.

The convention. The hazard builder instead takes each year's *probability* $q_y = 1 - e^{-\lambda_y p}$ and compounds it as an intensity, $1 - \exp\left(-\sum_y q_y\right)$. Since $q_y < \lambda_y p$, this always understates; the gap grows with λp and is largest relative to the answer at one year.

Compound loss. With event weights w_k and losses L_k, the annual loss is compound Poisson, with mean $\lambda \sum_k w_k L_k$ and, over n simulated years, standard error $\sqrt{\lambda \sum_k w_k L_k^2 / n}$.

Count families. The dispersion statistic $(n-1)s^2/\bar{x}$ is χ^2_{n-1} under Poisson; the Negative Binomial is fitted with its mean at $\bar{x}$ and its dispersion $\alpha = 1/r$ by bounded search, which is the joint maximum likelihood because the Negative Binomial's estimating equation for the mean is solved by $\bar{x}$ at every r.

4 Benchmark Method

The equations above are evaluated with `mpmath` at 50 significant digits, from the document rather than the code. Wolfram evaluates them independently from each input's exact value at 60-digit precision: the compound loss through `CompoundPoissonDistribution` of an `EmpiricalDistribution` (its rate scaled by the weights' exact total, which `EmpiricalDistribution` would otherwise renormalise away), the p-values through `ChiSquareDistribution`, and the Negative Binomial maximum by its own `FindMaximum` over both parameters, with the Poisson limit as the supremum for under-dispersed data. It proves the identity of §5.9 with `Expectation` and `Simplify`. Annual probabilities below $\lambda p = 0.0001$ are reported as a finding rather than judged against the 10^{-12} tolerance.

5 Validation and Backtesting

Table 1: Benchmark checks

Check	Result	Tolerance	Outcome
Annual probability $1 - e^{-\lambda p}$, $\lambda p \geq 0.0001$: model vs reference	5.7×10^{-14}	1.0×10^{-12}	pass
Aggregate rate λp: model vs reference	5.6×10^{-17}	1.0×10^{-12}	pass
Tenor probability $1 - e^{-p\sum \lambda_y}$: model vs reference	6.1×10^{-15}	1.0×10^{-12}	pass
Compound-Poisson average annual loss: model vs reference	2.3×10^{-16}	1.0×10^{-12}	pass
Its standard error over n years: model vs reference	4.6×10^{-17}	1.0×10^{-12}	pass
Dispersion statistic $(n-1)s^2/\bar{x}$: model vs reference	1.4×10^{-16}	1.0×10^{-12}	pass
Over-dispersion p-value (χ^2 survival): model vs reference	9.4×10^{-15}	1.0×10^{-10}	pass
Under-dispersion p-value (χ^2 CDF): model vs reference	5.5×10^{-16}	1.0×10^{-10}	pass
Poisson log-likelihood: model vs reference	1.3×10^{-15}	1.0×10^{-12}	pass
Negative Binomial log-likelihood at its maximum: model vs reference	1.3×10^{-12}	1.0×10^{-8}	pass
Wolfram agrees with the reference (closed forms, χ^2, Poisson)	4.9×10^{-30}	1.0×10^{-12}	pass
Wolfram's own Negative Binomial maximum finds no higher likelihood	0	1.0×10^{-8}	pass

5.1 The model document's claims

Table 2: The model document's claims, and the code's own conventions, tested

Claim	Stated	Benchmark finds	Outcome
§5.9 closed form	$E[(1-p)^N] = e^{-\lambda p}$; aggregate $\geq$ occurrence	identity confirmed symbolically; aggregate $\geq$ occurrence in every case	met
§5.9 gate statistic	mean $\lvert z\rvert = \sqrt{2/\pi} = 0.798$	0.797885	met
§7.2 sampling error	5, 1.6, 0.5, 0.16% at $10^3..10^6$ years	$1/\sqrt{n}$ from the first gives 5.00%, 1.58%, 0.50%, 0.16%	met
Term structure (annualise, gev)	annual probability used as the per-year hazard	tenor probability understated by 0.10–17.3%	finding
Annualisation precision	$1 - \exp(-x)$	1.0×10^{-10} relative below $\lambda p = 0.0001$; $-\mathrm{expm1}(-x)$ is exact	finding
Negative Binomial search	bounded scalar search on α	log-likelihood within 1.8×10^{-10} of the maximum	met

The §7.2 errors imply a relative error $\sqrt{(1-q)/(nq)}$ with $q \approx 0.29$: the table quotes one subject's figures, not a bound.

5.2 The multi-year term structure

Table 3: The multi-year exceedance probability: exact against the per-year-hazard convention

Rate	λ_0	p	T	Exact	Convention	Gap
const	2	0.001	1	0.001998	0.001996	-0.10%
const	2	0.001	10	0.019801	0.019782	-0.10%
const	2	0.01	1	0.019801	0.019607	-0.98%
const	2	0.01	10	0.181269	0.179641	-0.90%
const	2	0.05	1	0.095163	0.090775	-4.61%
const	2	0.05	10	0.632121	0.613887	-2.88%
const	10	0.001	1	0.009950	0.009901	-0.50%
const	10	0.001	10	0.095163	0.094712	-0.47%
const	10	0.01	1	0.095163	0.090775	-4.61%
const	10	0.01	10	0.632121	0.613887	-2.88%
const	10	0.05	1	0.393469	0.325288	-17.33%
const	10	0.05	10	0.993262	0.980448	-1.29%
trend	5	0.001	1	0.004988	0.004975	-0.25%
trend	5	0.001	10	0.060953	0.060764	-0.31%
trend	5	0.01	1	0.048771	0.047600	-2.40%
trend	5	0.01	10	0.466819	0.456195	-2.28%
trend	5	0.05	1	0.221199	0.198443	-10.29%
trend	5	0.05	10	0.956910	0.932189	-2.58%

6 Model Limitations and Known Weaknesses

1. **Benchmark, not validation.** The code is shown to compute the documented formulae; whether λ is right for a gauge is the question the document's own §8 raises and leaves open.

2. **Term structure.** Compounding $\lambda_y p$ rather than q_y in the hazard builder, or calling `term_exceedance_probability`, would make the term structure exact and consistent with the sensitivity module. It changes every multi-year price and is for the model owner and the MRC.

3. **Precision.** Replace $1 - \exp(-x)$ with $-\text{expm1}(-x)$ in `annualise.py` and `rate_process.py`.

4. **Inventory.** The model's record answers validation question 8 "Not Applicable" with a rationale saying it has not been benchmarked; this document is that benchmark.

7 Document History

Date	Version	Description	Author
26-Oct-2026	0.1	First issue	David K Kelly