

REAL-TIME TRASHCAN RECOGNIZER AND LOCALIZER FOR THE BLIND AND VISUALLY IMPAIRED

A. Abuyazid, A. Shukla, M. Swaminathan

The University of Texas at Austin
Department of Electrical and Computer Engineering
Austin, TX 78712 USA

ABSTRACT

With 324 million people blind and visually impaired in the world and the cane still being the primary assistive device used, we approached this problem by looking at it through a different lens. Quite literally a lens. Through involvement with the National Federation of the Blind, we learned that trivial tasks such as finding a public trash can is almost impossible with merely a cane. Using cameras to help the blind is a pre-existing domain, however, we decided to attack this subproblem of navigating the user to public trash cans. Although seemingly trivial, this concept can be expanded to solve larger, problems such as steering the blind away from hazardous construction, reading signs, and perhaps one day driving (unless self driving cars are prominent by then).

Index Terms— Image processing, object detection, assistive technology

1. INTRODUCTION

These guidelines include complete descriptions of the fonts, spacing, and related information for producing your proceedings manuscripts. Please follow them and if you have any questions, direct them to Conference Management Services, Inc.: Phone +1-979-846-6800 or email to papers@2018.ieeeictp.org.

2. RELATED WORK

To achieve the best rendering both in printed proceedings and electronic proceedings, we strongly encourage you to use Times-Roman font. In addition, this will give the proceedings a more uniform look. Use a font that is no smaller than nine point type throughout the paper, including figure captions.

In nine point type font, capital letters are 2 mm high. **If you use the smallest point size, there should be no more than 3.2 lines/cm (8 lines/inch) vertically.** This is a minimum spacing; 2.75 lines/cm (7 lines/inch) will make the paper

Thanks to Dr. Alan C Bovik, Cockrell Family Regents Endowed Chair Professor, The University of Texas at Austin

much more readable. Larger type sizes require correspondingly larger vertical spacing. Please do not double-space your paper. TrueType or Postscript Type 1 fonts are preferred.

The first paragraph in each section should not be indented, but all the following paragraphs within the section should be indented as these paragraphs demonstrate.

3. PROCESS

Here we go through the process we used for crafting this device. We begin with discussing about the camera, frame processing and model, and conclude with the physical device.

3.1. REALSENSE CAMERA

For this device, we used an Intel Realsense D435 camera to use to detect the trash cans. We chose this because of its relatively small size and since it had two lenses that we could extrapolate depth from. The camera also had depth sensing capabilities, but we chose not to use that and instead use triangulation properties to infer depth because if this device were to become an actual product, the cost of obtaining a camera with depth capabilities are significantly more expensive than using two cameras side by side. The horizontal FOV (field of vision) for the Realsense camera is 86 degrees and the vertical is 57 degrees. We used the librealsense python interface [1] to capture the individual frames to use for processing. We did not have the capabilities to change the frame of the camera, but we instead modulated the rate at which we sampled the frame in software.

3.2. FRAME PRE-PROCESSING

Ultimately, this device is supposed to be a wearable device, and we kept that in mind as we determined the frame image pre-processing. From training our model, discussed in the model section, we realized that we did not need such a high resolution for the model to work and detect the trash can, so we experimented with downsampling amounts, given by the following formula, $J(i) = I(Li)$ [2], where L is the down-sampling rate. We used OpenCV [3] to specify the end di-

mensions instead of L . We found that we could downsample the image as much as half its dimensions, or $L = 2$ and the model still worked just as well. This also helped the latency of the device. Refer to **Fig 1.** to see difference in images.

3.3. DATA PRUNING AND CONNECTED COMPONENT LABELING


Since the portion of ImageNet that corresponded with trash can images was under maintenance as we were unable to access it, the ADE20K [4], was a dataset that we found that fulfilled our purpose. It contained images with pre-segmented components corresponding to object classes. We took the images with trash cans and counted the number of trash cans in an image using connected component labeling, and used the fully connected component to draw a bounding box around the trash cans. We then overlayed the coordinates of this bounding box on the original image to feed into our model.

3.4. THE MODEL

We used a platform called Gluon [5] that allowed us to create a transfer learning model to learn the trash cans. We used a MobileNet1.0 model to learn the trash cans. Since we did not need all the object classes, we morphed this MobileNet neural network into a binary classifier by having it output only whether the object was a trash can or not. A future method for this could be to train our own classifier instead of using transfer learning or eliminating the last several layers of a deep network and appending a boosting, support vector machine, etc. classifier since this method will save memory by eliminating the deep layers that learn other object classes.

3.5. BOOSTING ACCURACY VIA POST TRAINING IMAGE PROCESSING

As we trained the model on our trash can images, we noticed that there was not a very high confidence value given to a trash can and the model generalized dark rectangular objects as trash cans when they were not. To account for this, since we had limited data as well, we used several image processing techniques to feed in better images into the network. We experimented with several possibilities and combinations, including edge filtering and Felsenszwab's graph based image segmentation to boost edges, and ended up choosing a combination of median filtering and erosion with a crosshair kernel on the image. The intuition behind using a median filter was that it denoised the image enough so that it eliminated noise but maintained the edge details of the trash cans. The erosion was used because the Realsense produced small white dots that were distorting the image slightly.



(a) No downsample, unprocessed (b) Downsample, processed

Fig. 1. Disparity in model confidence between pure and processed frames.

3.6. BINOCULAR CAMERA GEOMETRY AND TRIANGULATION FOR DEPTH APPROXIMATION

In order to get an approximate depth measurement to notify the user how far away the trash can is, we used binocular camera geometry and triangulation properties. We first took the horizontal disparity between the images, the lens focal lengths, and the distance between the two stereoscopic lenses. Next we used the triangulation equation, $Z_0 = \frac{2Df}{dx}$ [2] to approximate the depth Z . We had to do some calibration (in essence, multiply by scalars and then project the results in the [0,9] interval for the embedded systems component) to get the depth to work. We then cross referenced this with the percentage of the y-axis component of the bounding box with the total height of the frame to make sure that our triangulation equation was working approximately well.

3.7. THE DEVICE


The device is in the form of a wrist band that contains a 2-dimensional array of haptic motors to relay angular position and distance feedback to the user corresponding to the found trash can. The corresponding LED grid was only for demo purposes so that the audience can view which haptic motors are being activated. We decided on a wrist cuff since the study from the paper, Guiding Blind People with Haptic Feedback, found that the wrist and spine were the best places to detect vibrational impulses [6]. In their study they used 2 wristbands, but we decided to go with one wristband representing 86 degrees since this was the horizontal FOV (field of vision) of the Intel Realsense camera.

4. RESULTS


Use footnotes sparingly (or not at all!) and place them at the bottom of the column on the page on which they are referenced. Use Times 9-point type, single-spaced. To help your



(a) Device worn on wrist



(b) Haptic motor grid



(c) LED grid

Fig. 2. Pictures of the physical device.

readers, avoid using footnotes altogether and include necessary peripheral observations in the text (within parentheses, if you prefer, as in this sentence).

5. CONCLUSION

Currently, this device is used to locate public trash cans, but the concept is transferrable to anything in its domain such as maneuvering the blind away from hazardous obstacles, reading crucial public signs, and even experiencing a motion related performance such as a play. The list goes on. In final conclusion, image processing is a computational superpower, and we wanted to ultimately use that ability to even out the playing field by offering a new perspective to the blind and visually impaired.

6. ACKNOWLEDGMENTS

Thank you, Dr. Alan C Bovik (Cockrell Family Regents Endowed Chair Professor, The University of Texas at Austin) for teaching us the concepts needed to implement this project. Also thank you to Rhanda Hasley, (President of the Dallas-Area Chapter of the National Federation for the Blind), for all of your advice.

7. REFERENCES

- [1] Intel, “librealsense,” <https://github.com/IntelRealSense/librealsense>, 2018.
- [2] Alan Bovik, “Lecture notes in digital image processing,” December 2019.
- [3] G. Bradski, “The OpenCV Library,” *Dr. Dobb’s Journal of Software Tools*, 2000.
- [4] Bolei Zhou, Hang Zhao, Xavier Puig, Sanja Fidler, Adela Barriuso, and Antonio Torralba, “Scene parsing through ade20k dataset,” in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2017.
- [5] Jian Guo, He He, Tong He, Leonard Lausen, Mu Li, Haibin Lin, Xingjian Shi, Chenguang Wang, Junyuan Xie, Sheng Zha, Aston Zhang, Hang Zhang, Zhi Zhang, Zhongyue Zhang, and Shuai Zheng, “Gluoncv and gluonnlp: Deep learning in computer vision and natural language processing,” *arXiv preprint arXiv:1907.04433*, 2019.
- [6] Slim Kammoun, Christophe Jouffrais, Tiago Guerreiro, Hugo Nicolau, and Joaquim Jorge, “Guiding blind people with haptic feedback,” in *Placeholde*, 01 2012.