The Complete HTML Reference Book

Every element and attribute from HTML 1 (1991) to the HTML Living Standard, with CSS

HTML 1 • HTML 2.0 • HTML 3.2 • HTML 4.01 • XHTML • HTML5 • Living Standard

Elements • Attributes • Global attributes • Events • Input types • CSS • Entities • Guides

Compiled from the HTML Living Standard, MDN Web Docs, htmlreference.io, codeshack.io and the W3Schools HTML and CSS tutorial.
Edition of September 2026

Contents

How to use this book **71**

Part 1: The History of HTML **74**

A short history of HTML **75**

Part 2: HTML Fundamentals **84**

HTML fundamentals **85**

Part 3: HTML Version by Version **95**

How to read this part **96**

HTML 1.0 (1991-1993) 97

HTML 2.0 (RFC 1866, 1995) 106

HTML 3.2 (W3C, January 1997) 124

HTML 4.0 and 4.01 (1997-1999) 151

HTML5 (WHATWG 2004 onwards, W3C Recommendation 2014) . . 188

The HTML Living Standard (2014-today) 243

Part 4: Global Attributes **250**

Global attributes **251**

accesskey 253

autocapitalize 254

autocorrect 255

autofocus 256
class 257
contenteditable 259
data-* 261
dir 263
draggable 264
enterkeyhint 265
exportparts 266
hidden 267
id 269
inert 270
inputmode 271
is 272
itemid, itemprop, itemref, itemscope, itemtype 273
lang 275
nonce 277
part 278
popover 279
role 281
aria-* 282
slot 284
spellcheck 285
style 286
tabindex 288
title 290
translate 292

virtualkeyboardpolicy 293
writingsuggestions 294
xml:lang, xml:base, xml:space 295

Part 5: Event Handler Attributes 296

Event handler attributes 297

onabort 302
onauxclick 303
onbeforeinput 304
onbeforematch 305
onbeforetoggle 306
onblur 307
oncancel 308
oncanplay 309
oncanplaythrough 310
onchange 311
onclick 312
onclose 313
oncontextmenu 314
oncopy, oncut, onpaste 315
oncuechange 316
ondblclick 317
ondrag, ondragend, ondragenter, ondragleave, ondragover, ondragstart, ondrop 318
ondurationchange 319
onemptied 320

onended 321
onerror 322
onfocus 323
onformdata 324
oninput 325
oninvalid 326
onkeydown 327
onkeypress 328
onkeyup 329
onload 330
onloadeddata 331
onloadedmetadata 332
onloadstart 333
onmousedown, onmouseup 334
onmouseenter, onmouseleave 335
onmousemove 336
onmouseover, onmouseout 337
onpause, onplay, onplaying 338
onpointerdown, onpointerup, onpointermove, onpointerover, onpointerout, onpointerenter, onpointerleave, onpointercancel, ongotpointercapture, onlostpointercapture 339
onprogress 341
onratechange 342
onreset 343
onresize 344
onscroll 345
onscrollend 346

onsecuritypolicyviolation 347
onseeked, onseeking 348
onselect 349
onselectionchange 350
onslotchange 351
onstalled 352
onsubmit 353
onsuspend 354
ontimeupdate 355
ontoggle 356
ontouchstart, ontouchmove, ontouchend, ontouchcancel 357
onvolumechange 358
onwaiting 359
onwheel 360
onanimationstart, onanimationend, onanimationiteration, onanimationcancel 361
ontransitionstart, ontransitionend, ontransitionrun, ontransitioncancel 362
oncontextlost, oncontextrestored 363
Window events on <body>: onafterprint, onbeforeprint, onbeforeunload, onhashchange, onlanguagechange, onmessage, onmessageerror, onoffline, ononline, onpagehide, onpagereveal, onpageshow, onpageswap, onpopstate, onrejectionhandled, onstorage, onunhandledrejection, onunload 364

Part 6: Element Reference **366**

Element index **367**

Elements by category **375**

<a> Anchor (hyperlink) 377
<abbr> Abbreviation 391
<acronym> Acronym (obsolete) 396
<address> Contact address 401
<applet> Java applet (obsolete) 405
<area> Image map area 411
<article> Self-contained article 420
<aside> Aside (sidebar / tangential content) 426
<audio> Embedded audio 431
<b> Bring attention to (bold) 440
<base> Document base URL 444
<basefont> Base font (obsolete) 449
<bdi> Bidirectional isolate 454
<bdo> Bidirectional text override 459
<bgsound> Background sound (non-standard, obsolete) 464
<big> Bigger text (obsolete) 469
<blink> Blinking text (non-standard, obsolete) 472
<blockquote> Block quotation 476
<body> Document body 481

 Line break 493
<button> Button 498
<canvas> Graphics canvas 508
<caption> Table caption 515
 Centred block (obsolete) 520
<cite> Citation (title of a work) 524
<code> Inline code 528

<col> Table column 532
<colgroup> Table column group 538
<content> Shadow DOM insertion point (obsolete) 543
<data> Machine-readable value 548
<datalist> Predefined options for an input 553
<dd> Description details 558
<del> Deleted text 563
<details> Disclosure widget 568
<dfn> Definition term 573
<dialog> Dialog box 578
<dir> Directory list (obsolete) 585
 Generic block container 590
<dl> Description list 596
<dt> Description term 602
 Emphasis 605
<embed> External content 609
<fencedframe> Fenced frame (experimental) 615
<fieldset> Form field group 620
<figcaption> Figure caption 626
<figure> Figure with optional caption 630
<font> Font (obsolete) 634
<footer> Footer 639
<form> Form 646
<frame> Frame (obsolete) 656
<frameset> Frameset (obsolete) 663
<h1> Headings h1 to h6 668

<head> Document head 674
<header> Header 680
<hgroup> Heading group 685
<hr> Thematic break (horizontal rule) 689
<html> Document root 695
<i> Idiomatic text (italic) 702
<iframe> Inline frame 706
<image> Image (non-standard alias, obsolete) 719
<img> Image 724
<input> Input control 737
<ins> Inserted text 757
<isindex> Search index prompt (obsolete) 762
<kbd> Keyboard input 767
<keygen> Key-pair generator (obsolete) 770
<label> Form control label 775
<legend> Fieldset caption 781
 List item 786
<link> External resource link 792
<listing> Listing (obsolete) 805
<main> Main content 808
<map> Image map 813
<mark> Highlighted (marked) text 818
<marquee> Scrolling text (obsolete) 822
<math> MathML root 829
<menu> Menu (toolbar list) 835
<menuitem> Menu item (obsolete) 840

<meta> Metadata 845
<meter> Scalar measurement (gauge) 854
<multicol> Multi-column text (non-standard, obsolete) 860
<nav> Navigation section 865
<nextid> Next identifier (HTML 1 editor hint) 870
<nobr> No line break (non-standard, obsolete) 875
<noembed> Fallback for embed (obsolete) 878
<noframes> Fallback for frames (obsolete) 881
<noscript> Fallback when scripting is disabled 884
<object> External object 888
 Ordered list 895
<optgroup> Option group 901
<option> Option 906
<output> Calculation or user-action result 911
<p> Paragraph 916
<param> Object parameter (deprecated) 922
<picture> Picture (responsive image container) 927
<plaintext> Plain text (obsolete) 933
<portal> Portal (experimental, abandoned) 937
<pre> Pre-formatted text 942
<progress> Progress indicator 948
<q> Inline quotation 953
<rb> Ruby base (deprecated) 958
<rp> Ruby fallback parenthesis 962
<rt> Ruby text (annotation) 965
<rtc> Ruby text container (deprecated) 968

<ruby> Ruby annotation 972
<s> Strikethrough (no longer accurate) 976
<samp> Sample output 980
<script> Script 983
<search> Search section 993
<section> Generic section 997
<select> Drop-down / list box 1002
<selectedcontent> Selected option display (customisable select) 1009
<shadow> Shadow root insertion point (obsolete) 1014
<slot> Shadow DOM slot 1018
<small> Side comment (fine print) 1025
<source> Media or image source 1029
<spacer> Spacer (non-standard, obsolete) 1035
 Generic inline container 1040
<strike> Strikethrough (obsolete) 1044
 Strong importance 1048
<style> Embedded style sheet 1052
<sub> Subscript 1058
<summary> Disclosure summary 1061
<sup> Superscript 1065
<svg> Scalable Vector Graphics root 1068
<table> Table 1075
<tbody> Table body 1086
<td> Table data cell 1092
<template> Content template 1102
<textarea> Multi-line text input 1108

<tfoot> Table footer 1118
<th> Table header cell 1123
<thead> Table header 1131
<time> Date / time 1137
<title> Document title 1142
<tr> Table row 1146
<track> Text track for media 1153
<tt> Teletype text (obsolete) 1159
<u> Unarticulated annotation (underline) 1162
 Unordered list 1166
<var> Variable 1172
<video> Embedded video 1175
<wbr> Word break opportunity 1185
<xmp> Example text (obsolete) 1189

Part 7: The input Element in Depth 1193

Input types overview 1194

input type=text 1196
input type=password 1197
input type=checkbox 1198
input type=radio 1199
input type=submit 1200
input type=reset 1201
input type=button 1202
input type=hidden 1203
input type=image 1204

input type=file 1205
input type=email 1206
input type=url 1207
input type=tel 1208
input type=search 1209
input type=number 1210
input type=range 1211
input type=color 1212
input type=date 1213
input type=time 1214
input type=datetime-local 1215
input type=month 1216
input type=week 1217

Part 8: Obsolete and Deprecated Features 1219

Obsolete elements 1220

Obsolete attributes 1222

Part 9: Attribute Reference 1225

Alphabetical attribute index 1226

abbr 1237
accept 1239
accept-charset 1241
action 1242
align 1244

alink 1266
allow 1267
allowfullscreen 1269
allowpaymentrequest 1270
alpha 1271
alt 1272
archive 1278
aria-label 1280
aria-labelledby 1281
as 1282
async 1283
attributionsrc 1284
autocomplete 1287
autofocus 1291
autoplay 1297
axis 1299
background 1301
balance 1302
behavior 1303
bgcolor 1304
blocking 1316
border 1320
bottommargin 1325
capture 1326
cellpadding 1327
cellspacing 1328

challenge 1329
char 1330
charoff 1339
charset 1348
checked 1353
cite 1355
classid 1359
clear 1360
closedby 1361
code 1362
codebase 1363
codetype 1365
color 1366
colorspace 1370
cols 1371
colspan 1374
command 1376
commandfor 1379
compact 1380
content 1386
controls 1387
controlslist 1389
coords 1391
credentialless 1393
crossorigin 1394
csp 1400

data 1401
datetime 1402
declare 1405
decoding 1406
default 1407
defer 1409
dir 1410
direction 1413
dirname 1414
disabled 1416
disablepictureinpicture 1427
disableremoteplayback 1428
display 1431
download 1432
elementtiming 1434
enctype 1435
etc. 1436
event 1437
face 1438
fetchpriority 1440
fill 1444
for 1445
form 1448
formaction 1459
formenctype 1461
formmethod 1463

formnovalidate 1465
formtarget 1467
frame 1469
frameborder 1470
framespacing 1473
gutter 1474
headers 1475
height 1477
high 1494
href 1495
hreflang 1500
hspace 1502
http-equiv 1507
icon 1508
id 1509
imagesizes 1510
imagesrcset 1511
incremental 1512
inputmode 1513
integrity 1514
ismap 1516
itemprop 1517
keytype 1518
kind 1519
label 1520
lang 1526

language 1527
leftmargin 1528
link 1529
list 1530
loading 1531
longdesc 1533
loop 1536
low 1541
lowsrc 1542
manifest 1543
marginheight 1544
marginwidth 1546
max 1548
maxlength 1551
media 1553
method 1558
min 1559
minlength 1561
moz-opaque 1563
mozactionhint 1564
multiple 1565
muted 1567
n 1569
name 1570
nohref 1590
nomodule 1591

nonce 1592
noresize 1594
noshade 1595
novalidate 1596
nowrap 1597
object 1600
onbeforeunload 1601
onhashchange 1602
onlanguagechange 1603
onload 1604
onpopstate 1605
onresize 1606
onstorage 1607
onunload 1608
open 1609
optimum 1611
orient 1612
pattern 1613
ping 1614
placeholder 1616
playsinline 1618
popovertarget 1619
popovertargetaction 1621
poster 1623
preload 1624
preserveAspectRatio 1626

profile 1627
prompt 1628
property 1629
radiogroup 1630
readonly 1631
referrerpolicy 1633
rel 1641
required 1646
results 1649
rev 1650
reversed 1652
rightmargin 1653
role 1654
rows 1655
rowspan 1657
rules 1659
sandbox 1660
scheme 1661
scope 1662
scoped 1664
scrollamount 1665
scrolldelay 1666
scrolling 1667
select 1669
selected 1670
shadowrootclonable 1671

shadowrootdelegatesfocus 1672
shadowrootmode 1673
shadowrootserializable 1674
shape 1675
size 1677
sizes 1684
span 1687
spellcheck 1689
src 1690
srcdoc 1704
srclang 1705
srcset 1706
standby 1708
start 1709
step 1710
stroke 1711
stroke-width 1712
summary 1713
target 1714
text 1720
title 1721
topmargin 1728
truespeed 1729
type 1730
typemustmatch 1748
usemap 1749

valign 1752
value 1761
valuetype 1770
version 1771
viewBox 1772
vlink 1773
volume 1774
vspace 1775
webkitdirectory 1780
width 1781
wrap 1803
xmlns 1805

Part 10: Value References **1808**

Link relationship types (rel) **1809**

Standard meta names **1812**

Autocomplete tokens **1815**

Common MIME types **1818**

URL schemes used in href **1822**

Named colours **1823**

Character entity reference **1826**

Part 11: CSS Reference 1834

CSS fundamentals 1835

CSS selectors 1843

* 1846
element 1847
.class 1848
#id 1849
[attr] 1850
[attr="value"] 1851
[attr~="word"] 1852
[attr|="en"] 1853
[attr^="https"] 1854
[attr$=".pdf"] 1855
[attr*="example"] 1856
[attr="v" i] 1857
A B 1858
A > B 1859
A + B 1860
A ~ B 1861
A, B 1862
:hover 1863
:focus / :focus-visible / :focus-within 1864
:active 1865
:visited / :link 1866
:first-child / :last-child / :only-child 1867

:nth-child(an+b) / :nth-last-child() 1868
:first-of-type / :last-of-type / :nth-of-type() 1869
:not(selector) 1870
:is(a, b) / :where(a, b) 1871
:has(selector) 1872
:empty 1873
:root 1874
:checked / :indeterminate 1875
:disabled / :enabled / :read-only / :read-write 1876
:required / :optional 1877
:valid / :invalid / :user-invalid / :in-range / :out-of-range / :placeholder-shown 1878
:target 1879
:lang(ar) 1880
:dir(rtl) 1881
:popover-open / :modal / :fullscreen / :open 1882
::before / ::after 1883
::first-line / ::first-letter 1884
::marker 1885
::placeholder 1886
::selection 1887
::backdrop 1888
::part(name) / ::slotted(sel) 1889
::file-selector-button 1890
::cue 1891

CSS property reference **1892**

Fonts and text 1892
Box model 1918
Backgrounds 1936
Layout 1943
Motion 1959
Interaction 1964

Styling HTML elements: cookbook **1976**

Lists and tables with CSS **1980**

Part 12: HTML and CSS Course **1994**

About this course **1995**

Lesson 1: Introduction and environment setup 1997
Lesson 2: Your first web page 1999
Lesson 3: Essentials - elements, attributes and nesting 2001
Lesson 4: Document structure 2003
Lesson 5: Text content 2005
Lesson 6: Lists and tables 2007
Lesson 7: Links and navigation 2009
Lesson 8: Images and media 2011
Lesson 9: Forms and validation 2013
Lesson 10: Reusable components 2015
Lesson 11: Styling essentials - the three ways to add CSS 2016
Lesson 12: Selectors and specificity 2018
Lesson 13: Cascade and inheritance 2020

Lesson 14: Typography 2021
Lesson 15: Colours and backgrounds 2023
Lesson 16: The box model 2024
Lesson 17: Layout fundamentals - normal flow 2027
Lesson 18: Positioning and z-index 2028
Lesson 19: Flexbox 2029
Lesson 20: CSS Grid 2032
Lesson 21: Layout patterns 2035
Lesson 22: Responsive design 2036
Lesson 23: Responsive components 2038
Lesson 24: Custom properties (CSS variables) 2039
Lesson 25: calc() and CSS functions 2040
Lesson 26: Transitions 2042
Lesson 27: Transforms 2044
Lesson 28: Animations 2045
Lesson 29: Effects and filters 2046
Lesson 30: Accessibility 2047
Lesson 31: Design systems 2049
Lesson 32: Performance 2051
Lesson 33: Debugging and testing 2052
Lesson 34: Tooling and automation (optional) 2054
Lesson 35: Project - a complete landing page 2055
Lesson 36: Quick quiz and answers 2060

Part 13: Practical Guides **2062**

Building a complete page step by step **2063**

Lists in depth **2066**

Tables in depth **2069**

Forms in depth **2071**

Semantic layout and accessibility **2074**

Media: images, audio and video **2076**

SEO essentials in HTML **2078**

Migrating old HTML (2, 3.2, 4) to HTML5 **2079**

Part 14: Glossary and Index **2081**

Glossary **2082**

Glossary in depth **2086**

Accessibility (a11y) 2087

ARIA 2088

Attribute 2089

Block-level element 2090

Boolean attribute 2091

Browser 2092

Cascade 2093

Character reference / entity 2094

Child / parent / sibling / ancestor / descendant 2095

Class 2096
Content model 2097
CSS 2098
Deprecated 2099
DOCTYPE 2100
DOM 2101
Element 2102
Empty / void element 2103
Flow content 2104
Focus 2105
Fragment 2106
Global attribute 2107
HTML 2108
HTTP / HTTPS 2109
Hyperlink 2110
Id 2111
Inline element 2112
JavaScript 2113
Landmark 2114
Living Standard 2115
MDN 2116
Metadata 2117
MIME type 2118
Nesting 2119
Obsolete 2120
Phrasing content 2121

Pseudo-class / pseudo-element 2122
Quirks mode 2123
Rendering 2124
Responsive design 2125
Screen reader 2126
Sectioning content 2127
Selector 2128
Semantic HTML 2129
Specificity 2130
Tag 2131
URL 2132
UTF-8 2133
Validator 2134
Viewport 2135
W3C 2136
WCAG 2137
WHATWG 2138
XHTML 2139

Alphabetical index **2140**

Part 15: Practice Projects **2166**

How to use the projects **2167**

Type: Landing page 2174
Project 1: Landing page for Cairo Book Shop 2175
Project 2: Landing page for Nile Bakery 2183

Project 3: Landing page for Pyramid Fitness 2191
Project 4: Landing page for Delta Dental Clinic 2199
Project 5: Landing page for Red Sea Travel 2207
Project 6: Landing page for Lotus Language School 2215
Project 7: Landing page for Green Leaf Cafe 2223
Project 8: Landing page for Sinai Trekking Club 2231
Project 9: Landing page for Horizon Photography 2239
Project 10: Landing page for Papyrus Stationery 2247
Project 11: Landing page for Oasis Plant Nursery 2255
Project 12: Landing page for Cedar Furniture 2263
Project 13: Landing page for Byte Repair 2271
Project 14: Landing page for Sahara Pet Care 2279
Project 15: Landing page for Alexandria Sailing School 2287
Project 16: Landing page for Habiba Handmade Jewellery 2295
Project 17: Landing page for Fayoum Pottery Studio 2303
Project 18: Landing page for Cleopatra Beauty Salon 2311
Project 19: Landing page for Suez Auto Service 2319
Project 20: Landing page for Luxor Music Academy 2327
Project 21: Landing page for Port Said Seafood 2335
Project 22: Landing page for Delta Kids Library 2343
Project 23: Landing page for Nubian Guest House 2351
Project 24: Landing page for Ismailia Cycling Store 2359
Project 25: Landing page for Minya Coding Club 2367
Type: Navigation bar 2375
Project 26: Navigation bar for Cairo Book Shop 2376
Project 27: Navigation bar for Nile Bakery 2382
Project 28: Navigation bar for Pyramid Fitness 2388
Project 29: Navigation bar for Delta Dental Clinic 2395
Project 30: Navigation bar for Red Sea Travel 2401

Project 31: Navigation bar for Lotus Language School 2407
Project 32: Navigation bar for Green Leaf Cafe 2414
Project 33: Navigation bar for Sinai Trekking Club 2420
Project 34: Navigation bar for Horizon Photography 2427
Project 35: Navigation bar for Papyrus Stationery 2433
Project 36: Navigation bar for Oasis Plant Nursery 2439
Project 37: Navigation bar for Cedar Furniture 2446
Project 38: Navigation bar for Byte Repair 2452
Project 39: Navigation bar for Sahara Pet Care 2458
Project 40: Navigation bar for Alexandria Sailing School 2464
Project 41: Navigation bar for Habiba Handmade Jewellery 2471
Project 42: Navigation bar for Fayoum Pottery Studio 2478
Project 43: Navigation bar for Cleopatra Beauty Salon 2485
Project 44: Navigation bar for Suez Auto Service 2492
Project 45: Navigation bar for Luxor Music Academy 2498
Project 46: Navigation bar for Port Said Seafood 2504
Project 47: Navigation bar for Delta Kids Library 2510
Project 48: Navigation bar for Nubian Guest House 2516
Project 49: Navigation bar for Ismailia Cycling Store 2522
Project 50: Navigation bar for Minya Coding Club 2529
Type: Price table 2535
Project 51: Price table for Cairo Book Shop 2536
Project 52: Price table for Nile Bakery 2543
Project 53: Price table for Pyramid Fitness 2550
Project 54: Price table for Delta Dental Clinic 2558
Project 55: Price table for Red Sea Travel 2565
Project 56: Price table for Lotus Language School 2572
Project 57: Price table for Green Leaf Cafe 2580
Project 58: Price table for Sinai Trekking Club 2587

Project 59: Price table for Horizon Photography 2595
Project 60: Price table for Papyrus Stationery 2602
Project 61: Price table for Oasis Plant Nursery 2609
Project 62: Price table for Cedar Furniture 2617
Project 63: Price table for Byte Repair 2624
Project 64: Price table for Sahara Pet Care 2631
Project 65: Price table for Alexandria Sailing School 2638
Project 66: Price table for Habiba Handmade Jewellery 2646
Project 67: Price table for Fayoum Pottery Studio 2654
Project 68: Price table for Cleopatra Beauty Salon 2662
Project 69: Price table for Suez Auto Service 2670
Project 70: Price table for Luxor Music Academy 2677
Project 71: Price table for Port Said Seafood 2684
Project 72: Price table for Delta Kids Library 2691
Project 73: Price table for Nubian Guest House 2698
Project 74: Price table for Ismailia Cycling Store 2705
Project 75: Price table for Minya Coding Club 2713
Type: Contact form 2720
Project 76: Contact form for Cairo Book Shop 2721
Project 77: Contact form for Nile Bakery 2728
Project 78: Contact form for Pyramid Fitness 2735
Project 79: Contact form for Delta Dental Clinic 2743
Project 80: Contact form for Red Sea Travel 2750
Project 81: Contact form for Lotus Language School 2757
Project 82: Contact form for Green Leaf Cafe 2765
Project 83: Contact form for Sinai Trekking Club 2772
Project 84: Contact form for Horizon Photography 2780
Project 85: Contact form for Papyrus Stationery 2787
Project 86: Contact form for Oasis Plant Nursery 2794

Project 87: Contact form for Cedar Furniture 2802
Project 88: Contact form for Byte Repair 2809
Project 89: Contact form for Sahara Pet Care 2816
Project 90: Contact form for Alexandria Sailing School 2823
Project 91: Contact form for Habiba Handmade Jewellery 2831
Project 92: Contact form for Fayoum Pottery Studio 2839
Project 93: Contact form for Cleopatra Beauty Salon 2847
Project 94: Contact form for Suez Auto Service 2855
Project 95: Contact form for Luxor Music Academy 2862
Project 96: Contact form for Port Said Seafood 2869
Project 97: Contact form for Delta Kids Library 2876
Project 98: Contact form for Nubian Guest House 2883
Project 99: Contact form for Ismailia Cycling Store 2890
Project 100: Contact form for Minya Coding Club 2898
Type: Photo gallery 2905
Project 101: Photo gallery for Cairo Book Shop 2906
Project 102: Photo gallery for Nile Bakery 2912
Project 103: Photo gallery for Pyramid Fitness 2918
Project 104: Photo gallery for Delta Dental Clinic 2924
Project 105: Photo gallery for Red Sea Travel 2930
Project 106: Photo gallery for Lotus Language School 2936
Project 107: Photo gallery for Green Leaf Cafe 2942
Project 108: Photo gallery for Sinai Trekking Club 2948
Project 109: Photo gallery for Horizon Photography 2954
Project 110: Photo gallery for Papyrus Stationery 2960
Project 111: Photo gallery for Oasis Plant Nursery 2966
Project 112: Photo gallery for Cedar Furniture 2972
Project 113: Photo gallery for Byte Repair 2978
Project 114: Photo gallery for Sahara Pet Care 2984

Project 115: Photo gallery for Alexandria Sailing School 2990
Project 116: Photo gallery for Habiba Handmade Jewellery 2996
Project 117: Photo gallery for Fayoum Pottery Studio 3002
Project 118: Photo gallery for Cleopatra Beauty Salon 3008
Project 119: Photo gallery for Suez Auto Service 3014
Project 120: Photo gallery for Luxor Music Academy 3020
Project 121: Photo gallery for Port Said Seafood 3026
Project 122: Photo gallery for Delta Kids Library 3032
Project 123: Photo gallery for Nubian Guest House 3038
Project 124: Photo gallery for Ismailia Cycling Store 3044
Project 125: Photo gallery for Minya Coding Club 3050
Type: About page 3056
Project 126: About page for Cairo Book Shop 3057
Project 127: About page for Nile Bakery 3064
Project 128: About page for Pyramid Fitness 3071
Project 129: About page for Delta Dental Clinic 3078
Project 130: About page for Red Sea Travel 3085
Project 131: About page for Lotus Language School 3092
Project 132: About page for Green Leaf Cafe 3099
Project 133: About page for Sinai Trekking Club 3106
Project 134: About page for Horizon Photography 3113
Project 135: About page for Papyrus Stationery 3120
Project 136: About page for Oasis Plant Nursery 3127
Project 137: About page for Cedar Furniture 3134
Project 138: About page for Byte Repair 3141
Project 139: About page for Sahara Pet Care 3148
Project 140: About page for Alexandria Sailing School 3155
Project 141: About page for Habiba Handmade Jewellery 3162
Project 142: About page for Fayoum Pottery Studio 3169

Project 143: About page for Cleopatra Beauty Salon 3176
Project 144: About page for Suez Auto Service 3183
Project 145: About page for Luxor Music Academy 3190
Project 146: About page for Port Said Seafood 3197
Project 147: About page for Delta Kids Library 3204
Project 148: About page for Nubian Guest House 3211
Project 149: About page for Ismailia Cycling Store 3218
Project 150: About page for Minya Coding Club 3225
Type: Menu list 3232
Project 151: Menu list for Cairo Book Shop 3233
Project 152: Menu list for Nile Bakery 3239
Project 153: Menu list for Pyramid Fitness 3245
Project 154: Menu list for Delta Dental Clinic 3251
Project 155: Menu list for Red Sea Travel 3257
Project 156: Menu list for Lotus Language School 3263
Project 157: Menu list for Green Leaf Cafe 3269
Project 158: Menu list for Sinai Trekking Club 3275
Project 159: Menu list for Horizon Photography 3281
Project 160: Menu list for Papyrus Stationery 3287
Project 161: Menu list for Oasis Plant Nursery 3293
Project 162: Menu list for Cedar Furniture 3299
Project 163: Menu list for Byte Repair 3305
Project 164: Menu list for Sahara Pet Care 3311
Project 165: Menu list for Alexandria Sailing School 3317
Project 166: Menu list for Habiba Handmade Jewellery 3323
Project 167: Menu list for Fayoum Pottery Studio 3329
Project 168: Menu list for Cleopatra Beauty Salon 3335
Project 169: Menu list for Suez Auto Service 3341
Project 170: Menu list for Luxor Music Academy 3347

Project 171: Menu list for Port Said Seafood 3353
Project 172: Menu list for Delta Kids Library 3359
Project 173: Menu list for Nubian Guest House 3365
Project 174: Menu list for Ismailia Cycling Store 3371
Project 175: Menu list for Minya Coding Club 3377
Type: FAQ accordion 3383
Project 176: FAQ accordion for Cairo Book Shop 3384
Project 177: FAQ accordion for Nile Bakery 3391
Project 178: FAQ accordion for Pyramid Fitness 3398
Project 179: FAQ accordion for Delta Dental Clinic 3405
Project 180: FAQ accordion for Red Sea Travel 3412
Project 181: FAQ accordion for Lotus Language School 3419
Project 182: FAQ accordion for Green Leaf Cafe 3426
Project 183: FAQ accordion for Sinai Trekking Club 3433
Project 184: FAQ accordion for Horizon Photography 3440
Project 185: FAQ accordion for Papyrus Stationery 3447
Project 186: FAQ accordion for Oasis Plant Nursery 3454
Project 187: FAQ accordion for Cedar Furniture 3461
Project 188: FAQ accordion for Byte Repair 3468
Project 189: FAQ accordion for Sahara Pet Care 3475
Project 190: FAQ accordion for Alexandria Sailing School 3482
Project 191: FAQ accordion for Habiba Handmade Jewellery 3489
Project 192: FAQ accordion for Fayoum Pottery Studio 3496
Project 193: FAQ accordion for Cleopatra Beauty Salon 3503
Project 194: FAQ accordion for Suez Auto Service 3510
Project 195: FAQ accordion for Luxor Music Academy 3517
Project 196: FAQ accordion for Port Said Seafood 3524
Project 197: FAQ accordion for Delta Kids Library 3531
Project 198: FAQ accordion for Nubian Guest House 3538

Project 199: FAQ accordion for Ismailia Cycling Store 3545
Project 200: FAQ accordion for Minya Coding Club 3552
Type: Product card 3559
Project 201: Product card for Cairo Book Shop 3560
Project 202: Product card for Nile Bakery 3566
Project 203: Product card for Pyramid Fitness 3572
Project 204: Product card for Delta Dental Clinic 3578
Project 205: Product card for Red Sea Travel 3584
Project 206: Product card for Lotus Language School 3590
Project 207: Product card for Green Leaf Cafe 3596
Project 208: Product card for Sinai Trekking Club 3602
Project 209: Product card for Horizon Photography 3608
Project 210: Product card for Papyrus Stationery 3614
Project 211: Product card for Oasis Plant Nursery 3620
Project 212: Product card for Cedar Furniture 3626
Project 213: Product card for Byte Repair 3632
Project 214: Product card for Sahara Pet Care 3638
Project 215: Product card for Alexandria Sailing School 3644
Project 216: Product card for Habiba Handmade Jewellery 3650
Project 217: Product card for Fayoum Pottery Studio 3656
Project 218: Product card for Cleopatra Beauty Salon 3662
Project 219: Product card for Suez Auto Service 3668
Project 220: Product card for Luxor Music Academy 3674
Project 221: Product card for Port Said Seafood 3680
Project 222: Product card for Delta Kids Library 3686
Project 223: Product card for Nubian Guest House 3692
Project 224: Product card for Ismailia Cycling Store 3698
Project 225: Product card for Minya Coding Club 3704
Type: Site footer 3710

Project 226: Site footer for Cairo Book Shop 3711
Project 227: Site footer for Nile Bakery 3718
Project 228: Site footer for Pyramid Fitness 3725
Project 229: Site footer for Delta Dental Clinic 3732
Project 230: Site footer for Red Sea Travel 3739
Project 231: Site footer for Lotus Language School 3746
Project 232: Site footer for Green Leaf Cafe 3753
Project 233: Site footer for Sinai Trekking Club 3760
Project 234: Site footer for Horizon Photography 3767
Project 235: Site footer for Papyrus Stationery 3774
Project 236: Site footer for Oasis Plant Nursery 3781
Project 237: Site footer for Cedar Furniture 3788
Project 238: Site footer for Byte Repair 3795
Project 239: Site footer for Sahara Pet Care 3802
Project 240: Site footer for Alexandria Sailing School 3809
Project 241: Site footer for Habiba Handmade Jewellery 3816
Project 242: Site footer for Fayoum Pottery Studio 3823
Project 243: Site footer for Cleopatra Beauty Salon 3830
Project 244: Site footer for Suez Auto Service 3837
Project 245: Site footer for Luxor Music Academy 3844
Project 246: Site footer for Port Said Seafood 3851
Project 247: Site footer for Delta Kids Library 3858
Project 248: Site footer for Nubian Guest House 3865
Project 249: Site footer for Ismailia Cycling Store 3872
Project 250: Site footer for Minya Coding Club 3879
Type: Full-screen hero banner 3886
Project 251: Full-screen hero banner for Cairo Book Shop 3887
Project 252: Full-screen hero banner for Nile Bakery 3893
Project 253: Full-screen hero banner for Pyramid Fitness 3899

Project 254: Full-screen hero banner for Delta Dental Clinic 3905
Project 255: Full-screen hero banner for Red Sea Travel 3911
Project 256: Full-screen hero banner for Lotus Language School . . . 3917
Project 257: Full-screen hero banner for Green Leaf Cafe 3924
Project 258: Full-screen hero banner for Sinai Trekking Club 3930
Project 259: Full-screen hero banner for Horizon Photography 3936
Project 260: Full-screen hero banner for Papyrus Stationery 3943
Project 261: Full-screen hero banner for Oasis Plant Nursery 3949
Project 262: Full-screen hero banner for Cedar Furniture 3955
Project 263: Full-screen hero banner for Byte Repair 3961
Project 264: Full-screen hero banner for Sahara Pet Care 3967
Project 265: Full-screen hero banner for Alexandria Sailing School . . 3973
Project 266: Full-screen hero banner for Habiba Handmade Jewellery . 3980
Project 267: Full-screen hero banner for Fayoum Pottery Studio 3987
Project 268: Full-screen hero banner for Cleopatra Beauty Salon . . . 3994
Project 269: Full-screen hero banner for Suez Auto Service 4001
Project 270: Full-screen hero banner for Luxor Music Academy 4007
Project 271: Full-screen hero banner for Port Said Seafood 4014
Project 272: Full-screen hero banner for Delta Kids Library 4020
Project 273: Full-screen hero banner for Nubian Guest House 4026
Project 274: Full-screen hero banner for Ismailia Cycling Store 4033
Project 275: Full-screen hero banner for Minya Coding Club 4040
Type: Team page 4046
Project 276: Team page for Cairo Book Shop 4047
Project 277: Team page for Nile Bakery 4053
Project 278: Team page for Pyramid Fitness 4059
Project 279: Team page for Delta Dental Clinic 4065
Project 280: Team page for Red Sea Travel 4071
Project 281: Team page for Lotus Language School 4077

Project 282: Team page for Green Leaf Cafe 4083
Project 283: Team page for Sinai Trekking Club 4089
Project 284: Team page for Horizon Photography 4095
Project 285: Team page for Papyrus Stationery 4101
Project 286: Team page for Oasis Plant Nursery 4107
Project 287: Team page for Cedar Furniture 4113
Project 288: Team page for Byte Repair 4119
Project 289: Team page for Sahara Pet Care 4125
Project 290: Team page for Alexandria Sailing School 4131
Project 291: Team page for Habiba Handmade Jewellery 4137
Project 292: Team page for Fayoum Pottery Studio 4143
Project 293: Team page for Cleopatra Beauty Salon 4149
Project 294: Team page for Suez Auto Service 4155
Project 295: Team page for Luxor Music Academy 4161
Project 296: Team page for Port Said Seafood 4167
Project 297: Team page for Delta Kids Library 4173
Project 298: Team page for Nubian Guest House 4179
Project 299: Team page for Ismailia Cycling Store 4185
Project 300: Team page for Minya Coding Club 4191
Type: Testimonials section 4197
Project 301: Testimonials section for Cairo Book Shop 4198
Project 302: Testimonials section for Nile Bakery 4205
Project 303: Testimonials section for Pyramid Fitness 4212
Project 304: Testimonials section for Delta Dental Clinic 4219
Project 305: Testimonials section for Red Sea Travel 4226
Project 306: Testimonials section for Lotus Language School 4233
Project 307: Testimonials section for Green Leaf Cafe 4241
Project 308: Testimonials section for Sinai Trekking Club 4248
Project 309: Testimonials section for Horizon Photography 4255

Project 310: Testimonials section for Papyrus Stationery 4262
Project 311: Testimonials section for Oasis Plant Nursery 4269
Project 312: Testimonials section for Cedar Furniture 4276
Project 313: Testimonials section for Byte Repair 4283
Project 314: Testimonials section for Sahara Pet Care 4290
Project 315: Testimonials section for Alexandria Sailing School 4297
Project 316: Testimonials section for Habiba Handmade Jewellery . . . 4305
Project 317: Testimonials section for Fayoum Pottery Studio 4313
Project 318: Testimonials section for Cleopatra Beauty Salon 4321
Project 319: Testimonials section for Suez Auto Service 4329
Project 320: Testimonials section for Luxor Music Academy 4336
Project 321: Testimonials section for Port Said Seafood 4343
Project 322: Testimonials section for Delta Kids Library 4350
Project 323: Testimonials section for Nubian Guest House 4357
Project 324: Testimonials section for Ismailia Cycling Store 4364
Project 325: Testimonials section for Minya Coding Club 4372
Type: Newsletter sign-up box 4379
Project 326: Newsletter sign-up box for Cairo Book Shop 4380
Project 327: Newsletter sign-up box for Nile Bakery 4387
Project 328: Newsletter sign-up box for Pyramid Fitness 4394
Project 329: Newsletter sign-up box for Delta Dental Clinic 4402
Project 330: Newsletter sign-up box for Red Sea Travel 4409
Project 331: Newsletter sign-up box for Lotus Language School 4416
Project 332: Newsletter sign-up box for Green Leaf Cafe 4424
Project 333: Newsletter sign-up box for Sinai Trekking Club 4431
Project 334: Newsletter sign-up box for Horizon Photography 4439
Project 335: Newsletter sign-up box for Papyrus Stationery 4446
Project 336: Newsletter sign-up box for Oasis Plant Nursery 4453
Project 337: Newsletter sign-up box for Cedar Furniture 4461

Project 338: Newsletter sign-up box for Byte Repair 4468
Project 339: Newsletter sign-up box for Sahara Pet Care 4475
Project 340: Newsletter sign-up box for Alexandria Sailing School . . . 4482
Project 341: Newsletter sign-up box for Habiba Handmade Jewellery . 4490
Project 342: Newsletter sign-up box for Fayoum Pottery Studio 4498
Project 343: Newsletter sign-up box for Cleopatra Beauty Salon 4506
Project 344: Newsletter sign-up box for Suez Auto Service 4514
Project 345: Newsletter sign-up box for Luxor Music Academy 4521
Project 346: Newsletter sign-up box for Port Said Seafood 4528
Project 347: Newsletter sign-up box for Delta Kids Library 4535
Project 348: Newsletter sign-up box for Nubian Guest House 4542
Project 349: Newsletter sign-up box for Ismailia Cycling Store 4549
Project 350: Newsletter sign-up box for Minya Coding Club 4557
Type: Sidebar layout 4564
Project 351: Sidebar layout for Cairo Book Shop 4565
Project 352: Sidebar layout for Nile Bakery 4572
Project 353: Sidebar layout for Pyramid Fitness 4579
Project 354: Sidebar layout for Delta Dental Clinic 4586
Project 355: Sidebar layout for Red Sea Travel 4593
Project 356: Sidebar layout for Lotus Language School 4600
Project 357: Sidebar layout for Green Leaf Cafe 4607
Project 358: Sidebar layout for Sinai Trekking Club 4614
Project 359: Sidebar layout for Horizon Photography 4621
Project 360: Sidebar layout for Papyrus Stationery 4628
Project 361: Sidebar layout for Oasis Plant Nursery 4635
Project 362: Sidebar layout for Cedar Furniture 4642
Project 363: Sidebar layout for Byte Repair 4649
Project 364: Sidebar layout for Sahara Pet Care 4656
Project 365: Sidebar layout for Alexandria Sailing School 4663

Project 366: Sidebar layout for Habiba Handmade Jewellery 4670
Project 367: Sidebar layout for Fayoum Pottery Studio 4678
Project 368: Sidebar layout for Cleopatra Beauty Salon 4685
Project 369: Sidebar layout for Suez Auto Service 4692
Project 370: Sidebar layout for Luxor Music Academy 4699
Project 371: Sidebar layout for Port Said Seafood 4706
Project 372: Sidebar layout for Delta Kids Library 4713
Project 373: Sidebar layout for Nubian Guest House 4720
Project 374: Sidebar layout for Ismailia Cycling Store 4727
Project 375: Sidebar layout for Minya Coding Club 4735
Type: Login form 4743
Project 376: Login form for Cairo Book Shop 4744
Project 377: Login form for Nile Bakery 4751
Project 378: Login form for Pyramid Fitness 4758
Project 379: Login form for Delta Dental Clinic 4765
Project 380: Login form for Red Sea Travel 4772
Project 381: Login form for Lotus Language School 4779
Project 382: Login form for Green Leaf Cafe 4786
Project 383: Login form for Sinai Trekking Club 4793
Project 384: Login form for Horizon Photography 4800
Project 385: Login form for Papyrus Stationery 4807
Project 386: Login form for Oasis Plant Nursery 4814
Project 387: Login form for Cedar Furniture 4821
Project 388: Login form for Byte Repair 4828
Project 389: Login form for Sahara Pet Care 4835
Project 390: Login form for Alexandria Sailing School 4842
Project 391: Login form for Habiba Handmade Jewellery 4849
Project 392: Login form for Fayoum Pottery Studio 4856
Project 393: Login form for Cleopatra Beauty Salon 4863

Project 394: Login form for Suez Auto Service 4870
Project 395: Login form for Luxor Music Academy 4877
Project 396: Login form for Port Said Seafood 4884
Project 397: Login form for Delta Kids Library 4891
Project 398: Login form for Nubian Guest House 4898
Project 399: Login form for Ismailia Cycling Store 4905
Project 400: Login form for Minya Coding Club 4912
Type: Vertical timeline 4919
Project 401: Vertical timeline for Cairo Book Shop 4920
Project 402: Vertical timeline for Nile Bakery 4925
Project 403: Vertical timeline for Pyramid Fitness 4930
Project 404: Vertical timeline for Delta Dental Clinic 4935
Project 405: Vertical timeline for Red Sea Travel 4940
Project 406: Vertical timeline for Lotus Language School 4945
Project 407: Vertical timeline for Green Leaf Cafe 4950
Project 408: Vertical timeline for Sinai Trekking Club 4955
Project 409: Vertical timeline for Horizon Photography 4961
Project 410: Vertical timeline for Papyrus Stationery 4966
Project 411: Vertical timeline for Oasis Plant Nursery 4971
Project 412: Vertical timeline for Cedar Furniture 4976
Project 413: Vertical timeline for Byte Repair 4981
Project 414: Vertical timeline for Sahara Pet Care 4987
Project 415: Vertical timeline for Alexandria Sailing School 4992
Project 416: Vertical timeline for Habiba Handmade Jewellery 4997
Project 417: Vertical timeline for Fayoum Pottery Studio 5003
Project 418: Vertical timeline for Cleopatra Beauty Salon 5008
Project 419: Vertical timeline for Suez Auto Service 5013
Project 420: Vertical timeline for Luxor Music Academy 5019
Project 421: Vertical timeline for Port Said Seafood 5025

Project 422: Vertical timeline for Delta Kids Library 5030
Project 423: Vertical timeline for Nubian Guest House 5035
Project 424: Vertical timeline for Ismailia Cycling Store 5040
Project 425: Vertical timeline for Minya Coding Club 5045
Type: Statistics dashboard 5050
Project 426: Statistics dashboard for Cairo Book Shop 5051
Project 427: Statistics dashboard for Nile Bakery 5059
Project 428: Statistics dashboard for Pyramid Fitness 5067
Project 429: Statistics dashboard for Delta Dental Clinic 5075
Project 430: Statistics dashboard for Red Sea Travel 5083
Project 431: Statistics dashboard for Lotus Language School 5091
Project 432: Statistics dashboard for Green Leaf Cafe 5100
Project 433: Statistics dashboard for Sinai Trekking Club 5108
Project 434: Statistics dashboard for Horizon Photography 5117
Project 435: Statistics dashboard for Papyrus Stationery 5125
Project 436: Statistics dashboard for Oasis Plant Nursery 5133
Project 437: Statistics dashboard for Cedar Furniture 5142
Project 438: Statistics dashboard for Byte Repair 5150
Project 439: Statistics dashboard for Sahara Pet Care 5158
Project 440: Statistics dashboard for Alexandria Sailing School 5166
Project 441: Statistics dashboard for Habiba Handmade Jewellery . . . 5175
Project 442: Statistics dashboard for Fayoum Pottery Studio 5184
Project 443: Statistics dashboard for Cleopatra Beauty Salon 5193
Project 444: Statistics dashboard for Suez Auto Service 5202
Project 445: Statistics dashboard for Luxor Music Academy 5210
Project 446: Statistics dashboard for Port Said Seafood 5218
Project 447: Statistics dashboard for Delta Kids Library 5226
Project 448: Statistics dashboard for Nubian Guest House 5234
Project 449: Statistics dashboard for Ismailia Cycling Store 5242

Project 450: Statistics dashboard for Minya Coding Club 5251
Type: 404 error page 5259
Project 451: 404 error page for Cairo Book Shop 5260
Project 452: 404 error page for Nile Bakery 5267
Project 453: 404 error page for Pyramid Fitness 5274
Project 454: 404 error page for Delta Dental Clinic 5281
Project 455: 404 error page for Red Sea Travel 5288
Project 456: 404 error page for Lotus Language School 5295
Project 457: 404 error page for Green Leaf Cafe 5302
Project 458: 404 error page for Sinai Trekking Club 5309
Project 459: 404 error page for Horizon Photography 5316
Project 460: 404 error page for Papyrus Stationery 5323
Project 461: 404 error page for Oasis Plant Nursery 5330
Project 462: 404 error page for Cedar Furniture 5337
Project 463: 404 error page for Byte Repair 5344
Project 464: 404 error page for Sahara Pet Care 5351
Project 465: 404 error page for Alexandria Sailing School 5358
Project 466: 404 error page for Habiba Handmade Jewellery 5365
Project 467: 404 error page for Fayoum Pottery Studio 5372
Project 468: 404 error page for Cleopatra Beauty Salon 5379
Project 469: 404 error page for Suez Auto Service 5386
Project 470: 404 error page for Luxor Music Academy 5393
Project 471: 404 error page for Port Said Seafood 5400
Project 472: 404 error page for Delta Kids Library 5407
Project 473: 404 error page for Nubian Guest House 5414
Project 474: 404 error page for Ismailia Cycling Store 5421
Project 475: 404 error page for Minya Coding Club 5428
Type: Blog article 5435
Project 476: Blog article for Cairo Book Shop 5436

Project 477: Blog article for Nile Bakery 5443
Project 478: Blog article for Pyramid Fitness 5450
Project 479: Blog article for Delta Dental Clinic 5457
Project 480: Blog article for Red Sea Travel 5464
Project 481: Blog article for Lotus Language School 5471
Project 482: Blog article for Green Leaf Cafe 5478
Project 483: Blog article for Sinai Trekking Club 5485
Project 484: Blog article for Horizon Photography 5492
Project 485: Blog article for Papyrus Stationery 5499
Project 486: Blog article for Oasis Plant Nursery 5506
Project 487: Blog article for Cedar Furniture 5513
Project 488: Blog article for Byte Repair 5520
Project 489: Blog article for Sahara Pet Care 5527
Project 490: Blog article for Alexandria Sailing School 5534
Project 491: Blog article for Habiba Handmade Jewellery 5541
Project 492: Blog article for Fayoum Pottery Studio 5548
Project 493: Blog article for Cleopatra Beauty Salon 5555
Project 494: Blog article for Suez Auto Service 5562
Project 495: Blog article for Luxor Music Academy 5569
Project 496: Blog article for Port Said Seafood 5576
Project 497: Blog article for Delta Kids Library 5583
Project 498: Blog article for Nubian Guest House 5590
Project 499: Blog article for Ismailia Cycling Store 5597
Project 500: Blog article for Minya Coding Club 5604
Type: Weekly schedule grid 5611
Project 501: Weekly schedule grid for Cairo Book Shop 5612
Project 502: Weekly schedule grid for Nile Bakery 5619
Project 503: Weekly schedule grid for Pyramid Fitness 5626
Project 504: Weekly schedule grid for Delta Dental Clinic 5633

Project 505: Weekly schedule grid for Red Sea Travel 5640
Project 506: Weekly schedule grid for Lotus Language School 5647
Project 507: Weekly schedule grid for Green Leaf Cafe 5655
Project 508: Weekly schedule grid for Sinai Trekking Club 5662
Project 509: Weekly schedule grid for Horizon Photography 5669
Project 510: Weekly schedule grid for Papyrus Stationery 5676
Project 511: Weekly schedule grid for Oasis Plant Nursery 5683
Project 512: Weekly schedule grid for Cedar Furniture 5690
Project 513: Weekly schedule grid for Byte Repair 5697
Project 514: Weekly schedule grid for Sahara Pet Care 5704
Project 515: Weekly schedule grid for Alexandria Sailing School 5711
Project 516: Weekly schedule grid for Habiba Handmade Jewellery . . 5719
Project 517: Weekly schedule grid for Fayoum Pottery Studio 5727
Project 518: Weekly schedule grid for Cleopatra Beauty Salon 5734
Project 519: Weekly schedule grid for Suez Auto Service 5742
Project 520: Weekly schedule grid for Luxor Music Academy 5749
Project 521: Weekly schedule grid for Port Said Seafood 5756
Project 522: Weekly schedule grid for Delta Kids Library 5763
Project 523: Weekly schedule grid for Nubian Guest House 5770
Project 524: Weekly schedule grid for Ismailia Cycling Store 5777
Project 525: Weekly schedule grid for Minya Coding Club 5784
Type: CV / resume page 5791
Project 526: CV / resume page for Mohamed Khattab 5792
Project 527: CV / resume page for Sara Adel 5799
Project 528: CV / resume page for Omar Farouk 5806
Project 529: CV / resume page for Dr. Hana Youssef 5813
Project 530: CV / resume page for Laila Mansour 5820
Project 531: CV / resume page for Nour El Din 5827
Project 532: CV / resume page for Karim Said 5834

Project 533: CV / resume page for Yara Hamdy 5841
Project 534: CV / resume page for Adham Nabil 5848
Project 535: CV / resume page for Dina Fathy 5855
Project 536: CV / resume page for Hossam Ali 5862
Project 537: CV / resume page for Tarek Lotfy 5869
Project 538: CV / resume page for Mostafa Gamal 5876
Project 539: CV / resume page for Rana Ibrahim 5883
Project 540: CV / resume page for Amr Selim 5890
Project 541: CV / resume page for Habiba Saleh 5897
Project 542: CV / resume page for Ahmed Mahmoud 5904
Project 543: CV / resume page for Mariam Adel 5911
Project 544: CV / resume page for Khaled Nasser 5918
Project 545: CV / resume page for Salma Ragab 5925
Project 546: CV / resume page for Sherif Wahba 5932
Project 547: CV / resume page for Ghada Kamel 5939
Project 548: CV / resume page for Fatma Hassan 5946
Project 549: CV / resume page for Bassem Adly 5953
Project 550: CV / resume page for Youssef Hany 5960
Type: Event page 5967
Project 551: Event page for Cairo Book Shop 5968
Project 552: Event page for Nile Bakery 5975
Project 553: Event page for Pyramid Fitness 5982
Project 554: Event page for Delta Dental Clinic 5989
Project 555: Event page for Red Sea Travel 5996
Project 556: Event page for Lotus Language School 6003
Project 557: Event page for Green Leaf Cafe 6010
Project 558: Event page for Sinai Trekking Club 6017
Project 559: Event page for Horizon Photography 6024
Project 560: Event page for Papyrus Stationery 6031

Project 561: Event page for Oasis Plant Nursery 6038
Project 562: Event page for Cedar Furniture 6045
Project 563: Event page for Byte Repair 6052
Project 564: Event page for Sahara Pet Care 6059
Project 565: Event page for Alexandria Sailing School 6066
Project 566: Event page for Habiba Handmade Jewellery 6073
Project 567: Event page for Fayoum Pottery Studio 6080
Project 568: Event page for Cleopatra Beauty Salon 6087
Project 569: Event page for Suez Auto Service 6094
Project 570: Event page for Luxor Music Academy 6101
Project 571: Event page for Port Said Seafood 6108
Project 572: Event page for Delta Kids Library 6115
Project 573: Event page for Nubian Guest House 6122
Project 574: Event page for Ismailia Cycling Store 6129
Project 575: Event page for Minya Coding Club 6136
Type: Printable invoice 6143
Project 576: Printable invoice for Cairo Book Shop 6144
Project 577: Printable invoice for Nile Bakery 6151
Project 578: Printable invoice for Pyramid Fitness 6158
Project 579: Printable invoice for Delta Dental Clinic 6165
Project 580: Printable invoice for Red Sea Travel 6172
Project 581: Printable invoice for Lotus Language School 6179
Project 582: Printable invoice for Green Leaf Cafe 6186
Project 583: Printable invoice for Sinai Trekking Club 6193
Project 584: Printable invoice for Horizon Photography 6200
Project 585: Printable invoice for Papyrus Stationery 6207
Project 586: Printable invoice for Oasis Plant Nursery 6214
Project 587: Printable invoice for Cedar Furniture 6221
Project 588: Printable invoice for Byte Repair 6228

Project 589: Printable invoice for Sahara Pet Care 6235
Project 590: Printable invoice for Alexandria Sailing School 6242
Project 591: Printable invoice for Habiba Handmade Jewellery 6249
Project 592: Printable invoice for Fayoum Pottery Studio 6257
Project 593: Printable invoice for Cleopatra Beauty Salon 6264
Project 594: Printable invoice for Suez Auto Service 6271
Project 595: Printable invoice for Luxor Music Academy 6278
Project 596: Printable invoice for Port Said Seafood 6285
Project 597: Printable invoice for Delta Kids Library 6292
Project 598: Printable invoice for Nubian Guest House 6299
Project 599: Printable invoice for Ismailia Cycling Store 6306
Project 600: Printable invoice for Minya Coding Club 6313
Type: Feature list with icons 6320
Project 601: Feature list with icons for Cairo Book Shop 6321
Project 602: Feature list with icons for Nile Bakery 6327
Project 603: Feature list with icons for Pyramid Fitness 6333
Project 604: Feature list with icons for Delta Dental Clinic 6339
Project 605: Feature list with icons for Red Sea Travel 6345
Project 606: Feature list with icons for Lotus Language School 6351
Project 607: Feature list with icons for Green Leaf Cafe 6357
Project 608: Feature list with icons for Sinai Trekking Club 6363
Project 609: Feature list with icons for Horizon Photography 6369
Project 610: Feature list with icons for Papyrus Stationery 6375
Project 611: Feature list with icons for Oasis Plant Nursery 6381
Project 612: Feature list with icons for Cedar Furniture 6387
Project 613: Feature list with icons for Byte Repair 6393
Project 614: Feature list with icons for Sahara Pet Care 6399
Project 615: Feature list with icons for Alexandria Sailing School . . . 6405
Project 616: Feature list with icons for Habiba Handmade Jewellery . . 6411

Project 617: Feature list with icons for Fayoum Pottery Studio 6417
Project 618: Feature list with icons for Cleopatra Beauty Salon 6423
Project 619: Feature list with icons for Suez Auto Service 6429
Project 620: Feature list with icons for Luxor Music Academy 6435
Project 621: Feature list with icons for Port Said Seafood 6441
Project 622: Feature list with icons for Delta Kids Library 6447
Project 623: Feature list with icons for Nubian Guest House 6453
Project 624: Feature list with icons for Ismailia Cycling Store 6459
Project 625: Feature list with icons for Minya Coding Club 6465
Type: Find-us page with map 6471
Project 626: Find-us page with map for Cairo Book Shop 6472
Project 627: Find-us page with map for Nile Bakery 6479
Project 628: Find-us page with map for Pyramid Fitness 6486
Project 629: Find-us page with map for Delta Dental Clinic 6493
Project 630: Find-us page with map for Red Sea Travel 6500
Project 631: Find-us page with map for Lotus Language School 6507
Project 632: Find-us page with map for Green Leaf Cafe 6514
Project 633: Find-us page with map for Sinai Trekking Club 6521
Project 634: Find-us page with map for Horizon Photography 6528
Project 635: Find-us page with map for Papyrus Stationery 6535
Project 636: Find-us page with map for Oasis Plant Nursery 6542
Project 637: Find-us page with map for Cedar Furniture 6549
Project 638: Find-us page with map for Byte Repair 6556
Project 639: Find-us page with map for Sahara Pet Care 6563
Project 640: Find-us page with map for Alexandria Sailing School . . . 6570
Project 641: Find-us page with map for Habiba Handmade Jewellery . 6577
Project 642: Find-us page with map for Fayoum Pottery Studio 6584
Project 643: Find-us page with map for Cleopatra Beauty Salon 6591
Project 644: Find-us page with map for Suez Auto Service 6598

Project 645: Find-us page with map for Luxor Music Academy 6605
Project 646: Find-us page with map for Port Said Seafood 6612
Project 647: Find-us page with map for Delta Kids Library 6619
Project 648: Find-us page with map for Nubian Guest House 6626
Project 649: Find-us page with map for Ismailia Cycling Store 6633
Project 650: Find-us page with map for Minya Coding Club 6640
Type: CSS-only tabs 6647
Project 651: CSS-only tabs for Cairo Book Shop 6648
Project 652: CSS-only tabs for Nile Bakery 6655
Project 653: CSS-only tabs for Pyramid Fitness 6662
Project 654: CSS-only tabs for Delta Dental Clinic 6670
Project 655: CSS-only tabs for Red Sea Travel 6677
Project 656: CSS-only tabs for Lotus Language School 6684
Project 657: CSS-only tabs for Green Leaf Cafe 6692
Project 658: CSS-only tabs for Sinai Trekking Club 6699
Project 659: CSS-only tabs for Horizon Photography 6707
Project 660: CSS-only tabs for Papyrus Stationery 6714
Project 661: CSS-only tabs for Oasis Plant Nursery 6721
Project 662: CSS-only tabs for Cedar Furniture 6729
Project 663: CSS-only tabs for Byte Repair 6736
Project 664: CSS-only tabs for Sahara Pet Care 6743
Project 665: CSS-only tabs for Alexandria Sailing School 6750
Project 666: CSS-only tabs for Habiba Handmade Jewellery 6758
Project 667: CSS-only tabs for Fayoum Pottery Studio 6766
Project 668: CSS-only tabs for Cleopatra Beauty Salon 6774
Project 669: CSS-only tabs for Suez Auto Service 6782
Project 670: CSS-only tabs for Luxor Music Academy 6789
Project 671: CSS-only tabs for Port Said Seafood 6796
Project 672: CSS-only tabs for Delta Kids Library 6803

Project 673: CSS-only tabs for Nubian Guest House 6810
Project 674: CSS-only tabs for Ismailia Cycling Store 6817
Project 675: CSS-only tabs for Minya Coding Club 6825
Type: Modal dialog 6832
Project 676: Modal dialog for Cairo Book Shop 6833
Project 677: Modal dialog for Nile Bakery 6839
Project 678: Modal dialog for Pyramid Fitness 6845
Project 679: Modal dialog for Delta Dental Clinic 6851
Project 680: Modal dialog for Red Sea Travel 6857
Project 681: Modal dialog for Lotus Language School 6863
Project 682: Modal dialog for Green Leaf Cafe 6869
Project 683: Modal dialog for Sinai Trekking Club 6875
Project 684: Modal dialog for Horizon Photography 6881
Project 685: Modal dialog for Papyrus Stationery 6887
Project 686: Modal dialog for Oasis Plant Nursery 6893
Project 687: Modal dialog for Cedar Furniture 6899
Project 688: Modal dialog for Byte Repair 6905
Project 689: Modal dialog for Sahara Pet Care 6911
Project 690: Modal dialog for Alexandria Sailing School 6917
Project 691: Modal dialog for Habiba Handmade Jewellery 6923
Project 692: Modal dialog for Fayoum Pottery Studio 6929
Project 693: Modal dialog for Cleopatra Beauty Salon 6935
Project 694: Modal dialog for Suez Auto Service 6941
Project 695: Modal dialog for Luxor Music Academy 6947
Project 696: Modal dialog for Port Said Seafood 6953
Project 697: Modal dialog for Delta Kids Library 6959
Project 698: Modal dialog for Nubian Guest House 6965
Project 699: Modal dialog for Ismailia Cycling Store 6971
Project 700: Modal dialog for Minya Coding Club 6977

Type: Search bar and results page 6983
Project 701: Search bar and results page for Cairo Book Shop 6984
Project 702: Search bar and results page for Nile Bakery 6993
Project 703: Search bar and results page for Pyramid Fitness 7001
Project 704: Search bar and results page for Delta Dental Clinic 7010
Project 705: Search bar and results page for Red Sea Travel 7019
Project 706: Search bar and results page for Lotus Language School . 7027
Project 707: Search bar and results page for Green Leaf Cafe 7036
Project 708: Search bar and results page for Sinai Trekking Club . . . 7045
Project 709: Search bar and results page for Horizon Photography . . 7054
Project 710: Search bar and results page for Papyrus Stationery . . . 7063
Project 711: Search bar and results page for Oasis Plant Nursery . . . 7072
Project 712: Search bar and results page for Cedar Furniture 7081
Project 713: Search bar and results page for Byte Repair 7090
Project 714: Search bar and results page for Sahara Pet Care 7098
Project 715: Search bar and results page for Alexandria Sailing School 7107
Project 716: Search bar and results page for Habiba Handmade Jewellery 7116
Project 717: Search bar and results page for Fayoum Pottery Studio . 7125
Project 718: Search bar and results page for Cleopatra Beauty Salon . 7134
Project 719: Search bar and results page for Suez Auto Service 7143
Project 720: Search bar and results page for Luxor Music Academy . . 7152
Project 721: Search bar and results page for Port Said Seafood 7161
Project 722: Search bar and results page for Delta Kids Library 7170
Project 723: Search bar and results page for Nubian Guest House . . . 7179
Project 724: Search bar and results page for Ismailia Cycling Store . . 7188
Project 725: Search bar and results page for Minya Coding Club 7197
Type: Order progress tracker 7206
Project 726: Order progress tracker for Cairo Book Shop 7207
Project 727: Order progress tracker for Nile Bakery 7214

Project 728: Order progress tracker for Pyramid Fitness 7221
Project 729: Order progress tracker for Delta Dental Clinic 7228
Project 730: Order progress tracker for Red Sea Travel 7235
Project 731: Order progress tracker for Lotus Language School 7242
Project 732: Order progress tracker for Green Leaf Cafe 7250
Project 733: Order progress tracker for Sinai Trekking Club 7257
Project 734: Order progress tracker for Horizon Photography 7266
Project 735: Order progress tracker for Papyrus Stationery 7274
Project 736: Order progress tracker for Oasis Plant Nursery 7281
Project 737: Order progress tracker for Cedar Furniture 7288
Project 738: Order progress tracker for Byte Repair 7295
Project 739: Order progress tracker for Sahara Pet Care 7303
Project 740: Order progress tracker for Alexandria Sailing School . . . 7310
Project 741: Order progress tracker for Habiba Handmade Jewellery . 7318
Project 742: Order progress tracker for Fayoum Pottery Studio 7327
Project 743: Order progress tracker for Cleopatra Beauty Salon 7335
Project 744: Order progress tracker for Suez Auto Service 7343
Project 745: Order progress tracker for Luxor Music Academy 7351
Project 746: Order progress tracker for Port Said Seafood 7360
Project 747: Order progress tracker for Delta Kids Library 7367
Project 748: Order progress tracker for Nubian Guest House 7374
Project 749: Order progress tracker for Ismailia Cycling Store 7382
Project 750: Order progress tracker for Minya Coding Club 7390
Type: Split-screen feature section 7397
Project 751: Split-screen feature section for Cairo Book Shop 7398
Project 752: Split-screen feature section for Nile Bakery 7405
Project 753: Split-screen feature section for Pyramid Fitness 7412
Project 754: Split-screen feature section for Delta Dental Clinic 7419
Project 755: Split-screen feature section for Red Sea Travel 7426

Project 756: Split-screen feature section for Lotus Language School . . 7433
Project 757: Split-screen feature section for Green Leaf Cafe 7440
Project 758: Split-screen feature section for Sinai Trekking Club 7447
Project 759: Split-screen feature section for Horizon Photography . . . 7454
Project 760: Split-screen feature section for Papyrus Stationery 7461
Project 761: Split-screen feature section for Oasis Plant Nursery . . . 7468
Project 762: Split-screen feature section for Cedar Furniture 7475
Project 763: Split-screen feature section for Byte Repair 7482
Project 764: Split-screen feature section for Sahara Pet Care 7489
Project 765: Split-screen feature section for Alexandria Sailing School 7496
Project 766: Split-screen feature section for Habiba Handmade Jewellery 7503
Project 767: Split-screen feature section for Fayoum Pottery Studio . . 7510
Project 768: Split-screen feature section for Cleopatra Beauty Salon . 7517
Project 769: Split-screen feature section for Suez Auto Service 7524
Project 770: Split-screen feature section for Luxor Music Academy . . 7531
Project 771: Split-screen feature section for Port Said Seafood 7538
Project 772: Split-screen feature section for Delta Kids Library 7545
Project 773: Split-screen feature section for Nubian Guest House . . . 7552
Project 774: Split-screen feature section for Ismailia Cycling Store . . 7559
Project 775: Split-screen feature section for Minya Coding Club 7566
Type: Statistics strip 7573
Project 776: Statistics strip for Cairo Book Shop 7574
Project 777: Statistics strip for Nile Bakery 7579
Project 778: Statistics strip for Pyramid Fitness 7584
Project 779: Statistics strip for Delta Dental Clinic 7589
Project 780: Statistics strip for Red Sea Travel 7594
Project 781: Statistics strip for Lotus Language School 7599
Project 782: Statistics strip for Green Leaf Cafe 7604
Project 783: Statistics strip for Sinai Trekking Club 7609

Project 784: Statistics strip for Horizon Photography 7614
Project 785: Statistics strip for Papyrus Stationery 7619
Project 786: Statistics strip for Oasis Plant Nursery 7624
Project 787: Statistics strip for Cedar Furniture 7629
Project 788: Statistics strip for Byte Repair 7634
Project 789: Statistics strip for Sahara Pet Care 7639
Project 790: Statistics strip for Alexandria Sailing School 7644
Project 791: Statistics strip for Habiba Handmade Jewellery 7649
Project 792: Statistics strip for Fayoum Pottery Studio 7654
Project 793: Statistics strip for Cleopatra Beauty Salon 7659
Project 794: Statistics strip for Suez Auto Service 7664
Project 795: Statistics strip for Luxor Music Academy 7669
Project 796: Statistics strip for Port Said Seafood 7674
Project 797: Statistics strip for Delta Kids Library 7679
Project 798: Statistics strip for Nubian Guest House 7684
Project 799: Statistics strip for Ismailia Cycling Store 7689
Project 800: Statistics strip for Minya Coding Club 7694
Type: Breadcrumbs and pagination 7699
Project 801: Breadcrumbs and pagination for Cairo Book Shop 7700
Project 802: Breadcrumbs and pagination for Nile Bakery 7707
Project 803: Breadcrumbs and pagination for Pyramid Fitness 7714
Project 804: Breadcrumbs and pagination for Delta Dental Clinic . . . 7721
Project 805: Breadcrumbs and pagination for Red Sea Travel 7728
Project 806: Breadcrumbs and pagination for Lotus Language School . 7735
Project 807: Breadcrumbs and pagination for Green Leaf Cafe 7742
Project 808: Breadcrumbs and pagination for Sinai Trekking Club . . . 7749
Project 809: Breadcrumbs and pagination for Horizon Photography . . 7756
Project 810: Breadcrumbs and pagination for Papyrus Stationery . . . 7763
Project 811: Breadcrumbs and pagination for Oasis Plant Nursery . . . 7770

Project 812: Breadcrumbs and pagination for Cedar Furniture 7777
Project 813: Breadcrumbs and pagination for Byte Repair 7784
Project 814: Breadcrumbs and pagination for Sahara Pet Care 7791
Project 815: Breadcrumbs and pagination for Alexandria Sailing School 7798
Project 816: Breadcrumbs and pagination for Habiba Handmade Jewellery 7805
Project 817: Breadcrumbs and pagination for Fayoum Pottery Studio . 7812
Project 818: Breadcrumbs and pagination for Cleopatra Beauty Salon . 7819
Project 819: Breadcrumbs and pagination for Suez Auto Service . . . 7826
Project 820: Breadcrumbs and pagination for Luxor Music Academy . 7833
Project 821: Breadcrumbs and pagination for Port Said Seafood 7840
Project 822: Breadcrumbs and pagination for Delta Kids Library 7847
Project 823: Breadcrumbs and pagination for Nubian Guest House . . 7854
Project 824: Breadcrumbs and pagination for Ismailia Cycling Store . . 7861
Project 825: Breadcrumbs and pagination for Minya Coding Club . . . 7868
Type: Alert message components 7875
Project 826: Alert message components for Cairo Book Shop 7876
Project 827: Alert message components for Nile Bakery 7881
Project 828: Alert message components for Pyramid Fitness 7886
Project 829: Alert message components for Delta Dental Clinic 7892
Project 830: Alert message components for Red Sea Travel 7897
Project 831: Alert message components for Lotus Language School . . 7902
Project 832: Alert message components for Green Leaf Cafe 7908
Project 833: Alert message components for Sinai Trekking Club 7913
Project 834: Alert message components for Horizon Photography . . . 7919
Project 835: Alert message components for Papyrus Stationery 7924
Project 836: Alert message components for Oasis Plant Nursery 7929
Project 837: Alert message components for Cedar Furniture 7935
Project 838: Alert message components for Byte Repair 7940
Project 839: Alert message components for Sahara Pet Care 7945

Project 840: Alert message components for Alexandria Sailing School . 7950
Project 841: Alert message components for Habiba Handmade Jewellery 7956
Project 842: Alert message components for Fayoum Pottery Studio . . 7962
Project 843: Alert message components for Cleopatra Beauty Salon . 7968
Project 844: Alert message components for Suez Auto Service 7974
Project 845: Alert message components for Luxor Music Academy . . 7979
Project 846: Alert message components for Port Said Seafood 7984
Project 847: Alert message components for Delta Kids Library 7989
Project 848: Alert message components for Nubian Guest House . . . 7994
Project 849: Alert message components for Ismailia Cycling Store . . 7999
Project 850: Alert message components for Minya Coding Club 8005
Type: Booking form in three steps 8010
Project 851: Booking form in three steps for Cairo Book Shop 8011
Project 852: Booking form in three steps for Nile Bakery 8020
Project 853: Booking form in three steps for Pyramid Fitness 8028
Project 854: Booking form in three steps for Delta Dental Clinic 8036
Project 855: Booking form in three steps for Red Sea Travel 8045
Project 856: Booking form in three steps for Lotus Language School . 8053
Project 857: Booking form in three steps for Green Leaf Cafe 8062
Project 858: Booking form in three steps for Sinai Trekking Club . . . 8070
Project 859: Booking form in three steps for Horizon Photography . . . 8079
Project 860: Booking form in three steps for Papyrus Stationery 8088
Project 861: Booking form in three steps for Oasis Plant Nursery . . . 8097
Project 862: Booking form in three steps for Cedar Furniture 8106
Project 863: Booking form in three steps for Byte Repair 8115
Project 864: Booking form in three steps for Sahara Pet Care 8123
Project 865: Booking form in three steps for Alexandria Sailing School 8131
Project 866: Booking form in three steps for Habiba Handmade Jewellery 8140
Project 867: Booking form in three steps for Fayoum Pottery Studio . . 8149

Project 868: Booking form in three steps for Cleopatra Beauty Salon . 8158
Project 869: Booking form in three steps for Suez Auto Service 8167
Project 870: Booking form in three steps for Luxor Music Academy . . 8176
Project 871: Booking form in three steps for Port Said Seafood 8185
Project 872: Booking form in three steps for Delta Kids Library 8194
Project 873: Booking form in three steps for Nubian Guest House . . . 8203
Project 874: Booking form in three steps for Ismailia Cycling Store . . 8212
Project 875: Booking form in three steps for Minya Coding Club 8221
Type: Video and audio page 8230
Project 876: Video and audio page for Cairo Book Shop 8231
Project 877: Video and audio page for Nile Bakery 8237
Project 878: Video and audio page for Pyramid Fitness 8243
Project 879: Video and audio page for Delta Dental Clinic 8249
Project 880: Video and audio page for Red Sea Travel 8255
Project 881: Video and audio page for Lotus Language School 8261
Project 882: Video and audio page for Green Leaf Cafe 8267
Project 883: Video and audio page for Sinai Trekking Club 8273
Project 884: Video and audio page for Horizon Photography 8279
Project 885: Video and audio page for Papyrus Stationery 8285
Project 886: Video and audio page for Oasis Plant Nursery 8291
Project 887: Video and audio page for Cedar Furniture 8297
Project 888: Video and audio page for Byte Repair 8303
Project 889: Video and audio page for Sahara Pet Care 8309
Project 890: Video and audio page for Alexandria Sailing School . . . 8315
Project 891: Video and audio page for Habiba Handmade Jewellery . . 8321
Project 892: Video and audio page for Fayoum Pottery Studio 8327
Project 893: Video and audio page for Cleopatra Beauty Salon 8333
Project 894: Video and audio page for Suez Auto Service 8339
Project 895: Video and audio page for Luxor Music Academy 8345

Project 896: Video and audio page for Port Said Seafood 8351
Project 897: Video and audio page for Delta Kids Library 8357
Project 898: Video and audio page for Nubian Guest House 8363
Project 899: Video and audio page for Ismailia Cycling Store 8369
Project 900: Video and audio page for Minya Coding Club 8375
Type: Product grid with clickable cards 8381
Project 901: Product grid with clickable cards for Cairo Book Shop . . 8382
Project 902: Product grid with clickable cards for Nile Bakery 8391
Project 903: Product grid with clickable cards for Pyramid Fitness . . . 8399
Project 904: Product grid with clickable cards for Delta Dental Clinic . 8407
Project 905: Product grid with clickable cards for Red Sea Travel . . . 8416
Project 906: Product grid with clickable cards for Lotus Language School 8425
Project 907: Product grid with clickable cards for Green Leaf Cafe . . . 8433
Project 908: Product grid with clickable cards for Sinai Trekking Club . 8441
Project 909: Product grid with clickable cards for Horizon Photography 8450
Project 910: Product grid with clickable cards for Papyrus Stationery . 8459
Project 911: Product grid with clickable cards for Oasis Plant Nursery . 8467
Project 912: Product grid with clickable cards for Cedar Furniture . . . 8476
Project 913: Product grid with clickable cards for Byte Repair 8484
Project 914: Product grid with clickable cards for Sahara Pet Care . . . 8492
Project 915: Product grid with clickable cards for Alexandria Sailing School 8500
Project 916: Product grid with clickable cards for Habiba Handmade Jewellery 8509
Project 917: Product grid with clickable cards for Fayoum Pottery Studio 8517
Project 918: Product grid with clickable cards for Cleopatra Beauty Salon 8526
Project 919: Product grid with clickable cards for Suez Auto Service . . 8535
Project 920: Product grid with clickable cards for Luxor Music Academy 8544
Project 921: Product grid with clickable cards for Port Said Seafood . . 8553
Project 922: Product grid with clickable cards for Delta Kids Library . . 8561

Project 923: Product grid with clickable cards for Nubian Guest House 8570
Project 924: Product grid with clickable cards for Ismailia Cycling Store 8578
Project 925: Product grid with clickable cards for Minya Coding Club . 8586
Type: Light and dark theme switcher 8594
Project 926: Light and dark theme switcher for Cairo Book Shop . . . 8595
Project 927: Light and dark theme switcher for Nile Bakery 8603
Project 928: Light and dark theme switcher for Pyramid Fitness 8611
Project 929: Light and dark theme switcher for Delta Dental Clinic . . 8619
Project 930: Light and dark theme switcher for Red Sea Travel 8627
Project 931: Light and dark theme switcher for Lotus Language School 8635
Project 932: Light and dark theme switcher for Green Leaf Cafe 8643
Project 933: Light and dark theme switcher for Sinai Trekking Club . . 8651
Project 934: Light and dark theme switcher for Horizon Photography . 8659
Project 935: Light and dark theme switcher for Papyrus Stationery . . 8667
Project 936: Light and dark theme switcher for Oasis Plant Nursery . . 8675
Project 937: Light and dark theme switcher for Cedar Furniture 8683
Project 938: Light and dark theme switcher for Byte Repair 8691
Project 939: Light and dark theme switcher for Sahara Pet Care 8699
Project 940: Light and dark theme switcher for Alexandria Sailing School 8707
Project 941: Light and dark theme switcher for Habiba Handmade Jewellery 8715
Project 942: Light and dark theme switcher for Fayoum Pottery Studio 8723
Project 943: Light and dark theme switcher for Cleopatra Beauty Salon 8731
Project 944: Light and dark theme switcher for Suez Auto Service . . . 8739
Project 945: Light and dark theme switcher for Luxor Music Academy . 8747
Project 946: Light and dark theme switcher for Port Said Seafood . . . 8755
Project 947: Light and dark theme switcher for Delta Kids Library . . . 8763
Project 948: Light and dark theme switcher for Nubian Guest House . 8771
Project 949: Light and dark theme switcher for Ismailia Cycling Store . 8779
Project 950: Light and dark theme switcher for Minya Coding Club . . 8787

Type: Printable voucher 8795
Project 951: Printable voucher for Cairo Book Shop 8796
Project 952: Printable voucher for Nile Bakery 8803
Project 953: Printable voucher for Pyramid Fitness 8810
Project 954: Printable voucher for Delta Dental Clinic 8817
Project 955: Printable voucher for Red Sea Travel 8824
Project 956: Printable voucher for Lotus Language School 8831
Project 957: Printable voucher for Green Leaf Cafe 8838
Project 958: Printable voucher for Sinai Trekking Club 8845
Project 959: Printable voucher for Horizon Photography 8852
Project 960: Printable voucher for Papyrus Stationery 8859
Project 961: Printable voucher for Oasis Plant Nursery 8866
Project 962: Printable voucher for Cedar Furniture 8873
Project 963: Printable voucher for Byte Repair 8880
Project 964: Printable voucher for Sahara Pet Care 8887
Project 965: Printable voucher for Alexandria Sailing School 8894
Project 966: Printable voucher for Habiba Handmade Jewellery 8901
Project 967: Printable voucher for Fayoum Pottery Studio 8908
Project 968: Printable voucher for Cleopatra Beauty Salon 8915
Project 969: Printable voucher for Suez Auto Service 8922
Project 970: Printable voucher for Luxor Music Academy 8929
Project 971: Printable voucher for Port Said Seafood 8936
Project 972: Printable voucher for Delta Kids Library 8943
Project 973: Printable voucher for Nubian Guest House 8950
Project 974: Printable voucher for Ismailia Cycling Store 8957
Project 975: Printable voucher for Minya Coding Club 8964
Type: Month calendar 8971
Project 976: Month calendar for Cairo Book Shop 8972
Project 977: Month calendar for Nile Bakery 8979

Project 978: Month calendar for Pyramid Fitness 8986
Project 979: Month calendar for Delta Dental Clinic 8993
Project 980: Month calendar for Red Sea Travel 9000
Project 981: Month calendar for Lotus Language School 9007
Project 982: Month calendar for Green Leaf Cafe 9014
Project 983: Month calendar for Sinai Trekking Club 9021
Project 984: Month calendar for Horizon Photography 9028
Project 985: Month calendar for Papyrus Stationery 9035
Project 986: Month calendar for Oasis Plant Nursery 9042
Project 987: Month calendar for Cedar Furniture 9049
Project 988: Month calendar for Byte Repair 9056
Project 989: Month calendar for Sahara Pet Care 9063
Project 990: Month calendar for Alexandria Sailing School 9070
Project 991: Month calendar for Habiba Handmade Jewellery 9077
Project 992: Month calendar for Fayoum Pottery Studio 9085
Project 993: Month calendar for Cleopatra Beauty Salon 9092
Project 994: Month calendar for Suez Auto Service 9099
Project 995: Month calendar for Luxor Music Academy 9106
Project 996: Month calendar for Port Said Seafood 9113
Project 997: Month calendar for Delta Kids Library 9120
Project 998: Month calendar for Nubian Guest House 9127
Project 999: Month calendar for Ismailia Cycling Store 9134
Project 1000: Month calendar for Minya Coding Club 9141
Type: Responsive hamburger menu 9148
Project 1001: Responsive hamburger menu for Cairo Book Shop . . . 9149
Project 1002: Responsive hamburger menu for Nile Bakery 9157
Project 1003: Responsive hamburger menu for Pyramid Fitness 9165
Project 1004: Responsive hamburger menu for Delta Dental Clinic . . 9173
Project 1005: Responsive hamburger menu for Red Sea Travel 9181

Project 1006: Responsive hamburger menu for Lotus Language School 9189
Project 1007: Responsive hamburger menu for Green Leaf Cafe 9197
Project 1008: Responsive hamburger menu for Sinai Trekking Club . . 9205
Project 1009: Responsive hamburger menu for Horizon Photography . 9213
Project 1010: Responsive hamburger menu for Papyrus Stationery . . 9221
Project 1011: Responsive hamburger menu for Oasis Plant Nursery . . 9229
Project 1012: Responsive hamburger menu for Cedar Furniture 9237
Project 1013: Responsive hamburger menu for Byte Repair 9245
Project 1014: Responsive hamburger menu for Sahara Pet Care 9253
Project 1015: Responsive hamburger menu for Alexandria Sailing School 9261
Project 1016: Responsive hamburger menu for Habiba Handmade Jewellery
Project 1017: Responsive hamburger menu for Fayoum Pottery Studio 9277
Project 1018: Responsive hamburger menu for Cleopatra Beauty Salon 9285
Project 1019: Responsive hamburger menu for Suez Auto Service . . 9293
Project 1020: Responsive hamburger menu for Luxor Music Academy . 9301
Project 1021: Responsive hamburger menu for Port Said Seafood . . . 9309
Project 1022: Responsive hamburger menu for Delta Kids Library . . . 9317
Project 1023: Responsive hamburger menu for Nubian Guest House . 9325
Project 1024: Responsive hamburger menu for Ismailia Cycling Store . 9333
Project 1025: Responsive hamburger menu for Minya Coding Club . . 9341
Type: Glossary with letter navigation 9349
Project 1026: Glossary with letter navigation for Cairo Book Shop . . . 9350
Project 1027: Glossary with letter navigation for Nile Bakery 9358
Project 1028: Glossary with letter navigation for Pyramid Fitness . . . 9366
Project 1029: Glossary with letter navigation for Delta Dental Clinic . . 9374
Project 1030: Glossary with letter navigation for Red Sea Travel . . . 9382
Project 1031: Glossary with letter navigation for Lotus Language School 9390
Project 1032: Glossary with letter navigation for Green Leaf Cafe . . . 9398
Project 1033: Glossary with letter navigation for Sinai Trekking Club . 9406

Project 1034: Glossary with letter navigation for Horizon Photography 9414
Project 1035: Glossary with letter navigation for Papyrus Stationery . 9422
Project 1036: Glossary with letter navigation for Oasis Plant Nursery . 9430
Project 1037: Glossary with letter navigation for Cedar Furniture . . . 9438
Project 1038: Glossary with letter navigation for Byte Repair 9446
Project 1039: Glossary with letter navigation for Sahara Pet Care . . . 9454
Project 1040: Glossary with letter navigation for Alexandria Sailing School 9462
Project 1041: Glossary with letter navigation for Habiba Handmade Jewellery 9470
Project 1042: Glossary with letter navigation for Fayoum Pottery Studio 9478
Project 1043: Glossary with letter navigation for Cleopatra Beauty Salon 9486
Project 1044: Glossary with letter navigation for Suez Auto Service . . 9494
Project 1045: Glossary with letter navigation for Luxor Music Academy 9502
Project 1046: Glossary with letter navigation for Port Said Seafood . . 9510
Project 1047: Glossary with letter navigation for Delta Kids Library . . 9518
Project 1048: Glossary with letter navigation for Nubian Guest House . 9526
Project 1049: Glossary with letter navigation for Ismailia Cycling Store 9534
Project 1050: Glossary with letter navigation for Minya Coding Club . . 9542
Type: Pricing plans comparison 9550
Project 1051: Pricing plans comparison for Cairo Book Shop 9551
Project 1052: Pricing plans comparison for Nile Bakery 9558
Project 1053: Pricing plans comparison for Pyramid Fitness 9565
Project 1054: Pricing plans comparison for Delta Dental Clinic 9573
Project 1055: Pricing plans comparison for Red Sea Travel 9580
Project 1056: Pricing plans comparison for Lotus Language School . . 9587
Project 1057: Pricing plans comparison for Green Leaf Cafe 9595
Project 1058: Pricing plans comparison for Sinai Trekking Club 9602
Project 1059: Pricing plans comparison for Horizon Photography . . . 9610
Project 1060: Pricing plans comparison for Papyrus Stationery 9617

Project 1061: Pricing plans comparison for Oasis Plant Nursery 9624
Project 1062: Pricing plans comparison for Cedar Furniture 9632
Project 1063: Pricing plans comparison for Byte Repair 9639
Project 1064: Pricing plans comparison for Sahara Pet Care 9646
Project 1065: Pricing plans comparison for Alexandria Sailing School . 9653
Project 1066: Pricing plans comparison for Habiba Handmade Jewellery 9662
Project 1067: Pricing plans comparison for Fayoum Pottery Studio . . 9671
Project 1068: Pricing plans comparison for Cleopatra Beauty Salon . . 9679
Project 1069: Pricing plans comparison for Suez Auto Service 9687
Project 1070: Pricing plans comparison for Luxor Music Academy . . . 9694
Project 1071: Pricing plans comparison for Port Said Seafood 9701
Project 1072: Pricing plans comparison for Delta Kids Library 9708
Project 1073: Pricing plans comparison for Nubian Guest House 9715
Project 1074: Pricing plans comparison for Ismailia Cycling Store . . . 9722
Project 1075: Pricing plans comparison for Minya Coding Club 9730
Type: Step-by-step how-to page 9737
Project 1076: Step-by-step how-to page for Cairo Book Shop 9738
Project 1077: Step-by-step how-to page for Nile Bakery 9746
Project 1078: Step-by-step how-to page for Pyramid Fitness 9753
Project 1079: Step-by-step how-to page for Delta Dental Clinic 9761
Project 1080: Step-by-step how-to page for Red Sea Travel 9769
Project 1081: Step-by-step how-to page for Lotus Language School . . 9776
Project 1082: Step-by-step how-to page for Green Leaf Cafe 9784
Project 1083: Step-by-step how-to page for Sinai Trekking Club 9792
Project 1084: Step-by-step how-to page for Horizon Photography . . . 9800
Project 1085: Step-by-step how-to page for Papyrus Stationery 9808
Project 1086: Step-by-step how-to page for Oasis Plant Nursery 9816
Project 1087: Step-by-step how-to page for Cedar Furniture 9824
Project 1088: Step-by-step how-to page for Byte Repair 9832

Project 1089: Step-by-step how-to page for Sahara Pet Care 9839
Project 1090: Step-by-step how-to page for Alexandria Sailing School . 9847
Project 1091: Step-by-step how-to page for Habiba Handmade Jewellery 9855
Project 1092: Step-by-step how-to page for Fayoum Pottery Studio . . 9863
Project 1093: Step-by-step how-to page for Cleopatra Beauty Salon . . 9871
Project 1094: Step-by-step how-to page for Suez Auto Service 9879
Project 1095: Step-by-step how-to page for Luxor Music Academy . . 9887
Project 1096: Step-by-step how-to page for Port Said Seafood 9895
Project 1097: Step-by-step how-to page for Delta Kids Library 9903
Project 1098: Step-by-step how-to page for Nubian Guest House . . . 9911
Project 1099: Step-by-step how-to page for Ismailia Cycling Store . . . 9919
Project 1100: Step-by-step how-to page for Minya Coding Club 9927
Type: Complete one-page website 9935
Project 1101: Complete one-page website for Cairo Book Shop 9936
Project 1102: Complete one-page website for Nile Bakery 9947
Project 1103: Complete one-page website for Pyramid Fitness 9958
Project 1104: Complete one-page website for Delta Dental Clinic . . . 9969
Project 1105: Complete one-page website for Red Sea Travel 9980
Project 1106: Complete one-page website for Lotus Language School . 9991
Project 1107: Complete one-page website for Green Leaf Cafe 10002
Project 1108: Complete one-page website for Sinai Trekking Club . . 10013
Project 1109: Complete one-page website for Horizon Photography . 10024
Project 1110: Complete one-page website for Papyrus Stationery . . 10035
Project 1111: Complete one-page website for Oasis Plant Nursery . . 10046
Project 1112: Complete one-page website for Cedar Furniture 10057
Project 1113: Complete one-page website for Byte Repair 10068
Project 1114: Complete one-page website for Sahara Pet Care 10079
Project 1115: Complete one-page website for Alexandria Sailing School 10090
Project 1116: Complete one-page website for Habiba Handmade Jewellery 10101

Project 1117: Complete one-page website for Fayoum Pottery Studio 10112
Project 1118: Complete one-page website for Cleopatra Beauty Salon 10123
Project 1119: Complete one-page website for Suez Auto Service . . . 10134
Project 1120: Complete one-page website for Luxor Music Academy . 10145
Project 1121: Complete one-page website for Port Said Seafood . . . 10156
Project 1122: Complete one-page website for Delta Kids Library . . . 10167
Project 1123: Complete one-page website for Nubian Guest House . 10178
Project 1124: Complete one-page website for Ismailia Cycling Store . 10189
Project 1125: Complete one-page website for Minya Coding Club . . 10200

How to use this book

This book is a complete desk reference for the HTML language, from the very first version published by Tim Berners-Lee in 1991 up to the HTML Living Standard that browsers implement today. It is written for people who are learning HTML for the first time and for experienced developers who need to look something up quickly.

How the book is organised

- Part 1 - History: what changed in HTML 1, 2, 3.2, 4.01, XHTML and HTML5.
- Part 2 - Fundamentals: syntax, document structure, nesting rules, content categories, comments, entities and the rules that apply to every tag.
- Part 3 - Global attributes: attributes such as id, class, style, title, hidden, lang and data-* that can be placed on any element.
- Part 4 - Event handler attributes: onclick, onload, onchange and every other on* attribute.
- Part 5 - Element reference: one full entry for every HTML element, alphabetically ordered. Each entry contains a description, syntax, content model, a table of every attribute, one or more complete examples, accessibility notes, version history and common mistakes.
- Part 6 - The input element in depth: every value of the type attribute with its own entry.
- Part 7 - Obsolete and deprecated features: elements and attributes from HTML 2, 3.2 and 4 that you may meet in old pages, with the modern replacement for each.

- Part 8 - Attribute reference: every attribute in the language listed alphabetically with the elements that accept it.
- Part 9 - Value references: link relationship types, MIME types, meta names, autocomplete tokens, colour names, URL schemes and the character entity table.
- Part 10 - Practical guides: forms, tables, lists, media, semantic layout, accessibility, SEO.
- Part 11 - Glossary and alphabetical index.

How to find something quickly

- In the HTML edition, type any word into the search box at the top: a tag name, an attribute name, a value, or a plain English word such as 'italic' or 'bottom of page'.
- In the PDF edition, use the table of contents at the front, the alphabetical index at the back, or your PDF reader's search function (Ctrl+F).
- Every element entry has the same layout, so once you know where the attribute table is in one entry you know where it is in all of them.

Conventions used in this book

Notation	Meaning
<tag>	An HTML element written with its tag name, for example <footer>.
attribute	An attribute name, written in lower case, for example href.
attribute="value"	An attribute together with an example value.
Void element	An element that has no closing tag and no content, for example .

Notation	Meaning
Deprecated	Still works in browsers but should not be used in new pages.
Obsolete	Removed from the standard; browsers may still render it for old pages.
HTML 2 / 3.2 / 4.01 / 5	The version of the specification in which a feature first appeared.

All examples in this book are complete and valid. You can copy any of them into a file named index.html and open it in a browser.

Part 1

The History of HTML

From Tim Berners-Lee's 18 tags to the Living Standard.

A short history of HTML

HTML (HyperText Markup Language) is the language used to describe the structure of pages on the World Wide Web. It has existed for more than three decades and has gone through several official versions. Knowing the history helps you understand why some tags exist, why others are marked obsolete, and why modern HTML looks the way it does.

HTML 1.0 (1991 - 1993): the beginning

In 1989 Tim Berners-Lee, a scientist at CERN in Switzerland, proposed a system for sharing documents between researchers. In 1991 he published a short document called 'HTML Tags' that described 18 elements. There was no official 'HTML 1.0' specification; the name is used informally for this first generation of the language. In 1993 Berners-Lee and Dan Connolly published an Internet Draft called 'Hypertext Markup Language (HTML)' which is often called HTML 1.0.

The first version was extremely simple. It had no images at first, no tables, no forms and no styling of any kind. Its purpose was to mark headings, paragraphs, lists and, most importantly, hyperlinks.

Element	Purpose in HTML 1
<title>	The document title.
<a>	The anchor: a hyperlink to another document. The most important invention of HTML.
<h1> to <h6>	Six levels of heading.
<p>	A paragraph break (in the earliest version it was a separator, not a container).

Element	Purpose in HTML 1
, ,	Unordered and ordered lists.
<dl>, <dt>, <dd>	Glossary (definition) lists.
<menu>, <dir>	Compact list variants (later removed).
<address>	Author contact information.
<pre>, <listing>, <xmp>, <plaintext>	Pre-formatted and literal text blocks.
<isindex>	A searchable index prompt (later removed).
<nextid>	Used by editors to generate identifiers (later removed).
<img>	Added in 1993 by Marc Andreessen for the Mosaic browser.

HTML 2.0 (1995): the first official standard

HTML 2.0 was published in November 1995 as RFC 1866 by the Internet Engineering Task Force (IETF). It gathered together everything that browsers of the time already supported and made it an official standard. It was written by Tim Berners-Lee and Dan Connolly.

New in HTML 2.0:

- Forms: <form>, <input>, <select>, <option>, <textarea>. For the first time a page could send information back to a server.
- Images with the <img> element and its src, alt and align attributes.
- Character formatting: <b>, <i>, <tt>, , , <code>, <samp>, <kbd>, <var>, <cite>.

- The <head> and <body> structure and <meta>, <base>, <link>, <isindex> in the head.
- The <blockquote>, <br>, <hr> elements.
- Character entities such as &, <, > and the ISO Latin-1 set (é and so on).
- The DOCTYPE declaration: <!DOCTYPE HTML PUBLIC "-//IETF//DTD HTML 2.0//EN">

HTML 2.0 had no tables and no way to control colours or fonts. Pages were plain grey backgrounds with black text and blue links.

HTML 3.0 (1995, never finished) and HTML 3.2 (1997)

HTML 3.0 was an ambitious draft by Dave Raggett that proposed tables, mathematical formulas, figures and text flow around images. It was too large for browsers to implement and was abandoned. Meanwhile Netscape and Microsoft added their own tags (such as <font>, , <blink> and <marquee>), starting the 'browser wars'.

The newly formed World Wide Web Consortium (W3C) responded with HTML 3.2, published in January 1997. Code-named 'Wilbur', it standardised what browsers actually did rather than what was ideal. HTML 3.2 is remembered as the version that mixed presentation into the markup.

New in HTML 3.2:

- Tables: <table>, <tr>, <td>, <th>, <caption>.
- Java applets: <applet>, <param>.

- Presentational elements: <font>, , <big>, <small>, <strike>, <u>, <sub>, <sup>.
- Client-side image maps: <map>, <area>.
- as a generic block container, with the align attribute.
- <script> and <style> were reserved for future use.
- Presentational attributes everywhere: bgcolor, text, link, vlink, alink on <body>; width, border, cellpadding, cellspacing on <table>; align on almost everything.

HTML 4.0 (1997) and HTML 4.01 (1999): separation of structure and style

HTML 4.0 was published in December 1997 and revised as HTML 4.01 in December 1999. It is the version that introduced the idea that HTML should describe structure and meaning while Cascading Style Sheets (CSS) should describe appearance. Most presentational elements of HTML 3.2 were officially deprecated.

HTML 4.01 came in three variants, chosen with the DOCTYPE:

Variant	DOCTYPE	Meaning
Strict	<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01//EN" "http://www.w3.org/TR/html4/strict.dtd">	No deprecated elements, no frames.

Variant	DOCTYPE	Meaning
Transitional	<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">	Deprecated elements allowed, to ease migration.
Frameset	<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Frameset//EN" "http://www.w3.org/TR/html4/frameset.dtd">	Same as Transitional but the body is replaced by a <frameset>.

New in HTML 4.01:

- Style sheets: the <style> element, the style attribute, the class and id attributes on all elements.
- Scripting: the <script> and <noscript> elements and the on* event attributes.
- Frames: <frameset>, <frame>, <noframes> and the inline <iframe>.
- Richer tables: <thead>, <tbody>, <tfoot>, <colgroup>, <col>, plus scope, headers, abbr, axis.
- Richer forms: <button>, <label>, <fieldset>, <legend>, <optgroup>, accesskey, tabindex, disabled, readonly.
- Internationalisation: lang and dir attributes, <bdo>, right-to-left text, Unicode support.
- Accessibility: the title attribute everywhere, alt required on <img>, longdesc, <abbr>, <acronym>.

- Generic <object> element for embedded content.
- New phrase elements: <ins>, <del>, <q>, .

XHTML 1.0 (2000) and XHTML 1.1 (2001)

XHTML was HTML 4.01 rewritten as an XML application. The elements were identical, but the syntax rules of XML applied: every tag must be closed (
 instead of <br>), all tag and attribute names must be lower case, attribute values must always be quoted, and a single error makes the whole page fail to display. XHTML 2.0 was planned as a completely new language but was abandoned in 2009 because it was not compatible with existing web pages.

HTML5 (2008 - 2014) and the HTML Living Standard (2019 - today)

In 2004 a group of browser makers (Apple, Mozilla and Opera) formed the WHATWG (Web Hypertext Application Technology Working Group) to evolve HTML in a backward-compatible way. Their work became HTML5. The W3C adopted it in 2007 and published HTML5 as a Recommendation in October 2014, followed by HTML 5.1 (2016) and HTML 5.2 (2017).

In 2019 the W3C and WHATWG agreed that there would be only one HTML specification, the WHATWG 'HTML Living Standard', which is updated continuously and has no version number. When people say 'HTML5' today they mean this living standard.

New in HTML5:

- A simple DOCTYPE: <!DOCTYPE html>

- Semantic sectioning elements: <header>, <footer>, <nav>, <main>, <article>, <section>, <aside>, <figure>, <figcaption>.
- Native audio and video: <audio>, <video>, <source>, <track>.
- Graphics: <canvas>, and inline <svg> and <math>.
- New form controls: input types email, url, tel, number, range, date, time, color, search; the placeholder, required, pattern, autofocus and autocomplete attributes; <datalist>, <output>, <progress>, <meter>.
- Interactive elements: <details>, <summary>, <dialog>.
- Text-level elements: <mark>, <time>, <data>, <wbr>, <bdi>, <ruby>, <rt>, <rp>.
- The <template>, <slot> and <picture> elements; the srcset and sizes attributes; lazy loading.
- Custom data attributes (data-*), contenteditable, draggable, hidden, spellcheck, translate.
- Removal of presentational elements: <font>, , <big>, <strike>, <tt>, frames, <applet>.
- Precise parsing rules so that every browser builds the same document tree from the same HTML, even when the HTML contains mistakes.

Timeline summary

Year	Version	Published by	Key additions
1991	HTML Tags (HTML 1)	Tim Berners-Lee, CERN	Headings, paragraphs, lists, links

Year	Version	Published by	Key additions
1993	HTML 1.0 draft	IETF draft	<img> added by Mosaic
1995	HTML 2.0	IETF RFC 1866	Forms, images, character formatting
1997	HTML 3.2	W3C	Tables, applets, <font>, , presentational attributes
1997	HTML 4.0	W3C	CSS, scripting, frames, richer tables and forms
1999	HTML 4.01	W3C	Corrections to 4.0; Strict, Transitional, Frameset
2000	XHTML 1.0	W3C	HTML 4.01 in XML syntax
2008	HTML5 first draft	WHATWG / W3C	Semantic elements, audio, video, canvas

Year	Version	Published by	Key additions
2014	HTML5 Recommendation	W3C	Official HTML5
2016 / 2017	HTML 5.1 / 5.2	W3C	<picture>, <dialog>, minor additions
2019 - today	HTML Living Standard	WHATWG	Single continuously updated specification

Part 2

HTML Fundamentals

Syntax, structure, nesting rules, content categories and entities.

HTML fundamentals

What HTML is

HTML is a markup language, not a programming language. It cannot calculate, make decisions or loop. Its only job is to wrap pieces of content in tags that say what each piece is: 'this is a heading', 'this is a paragraph', 'this is a link to another page', 'this is the footer'. The browser reads these tags, builds a tree of objects called the DOM (Document Object Model), and draws the page. CSS (Cascading Style Sheets) then controls how it looks and JavaScript controls how it behaves.

Anatomy of an element

```
<p class="intro">Hello, world!</p>
 |  |            |       |      |
 |  |            |       |      +-- closing tag
 |  |            |       +--------- content
 |  |            +----------------- end of opening tag
 |  +------------------------------ attribute name="value"
 +--------------------------------- opening tag with tag name
```

- The opening tag starts with < followed by the tag name and ends with >.
- Attributes go inside the opening tag, after the tag name, separated by spaces. Each attribute has a name and usually a value in quotes: name="value".
- The content is everything between the opening and closing tag. It can be text, other elements or both.
- The closing tag is the same as the opening tag but with a slash after the <: </p>.
- The whole thing, from < to >, is called an element.

Void elements (tags with no closing tag)

A small group of elements never have content and therefore never have a closing tag. Writing a closing tag for them is an error. In HTML5 you may write them as <br> or, in XML style, as <br />; both are accepted.

Void element	Purpose
<area>	Clickable region inside an image map
<base>	Base URL for the document
 	Line break
<col>	Table column properties
<embed>	External application content
<hr>	Thematic break (horizontal rule)
<img>	Image
<input>	Form control
<link>	External resource link (usually CSS)
<meta>	Metadata
<source>	Media or image source
<track>	Text track for media
<wbr>	Word break opportunity

The structure of a document

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Page title shown in the browser tab</title>
  <link rel="stylesheet" href="style.css">
</head>
<body>
  <header>
```

```
    <h1>Site name</h1>
    <nav><a href="/">Home</a> <a href="/about">About</a></nav>
  </header>
  <main>
    <h2>Page heading</h2>
    <p>Page content.</p>
  </main>
  <footer>
    <p>&copy; 2026 Site name</p>
  </footer>
  <script src="app.js"></script>
</body>
</html>
```

Line	What it does
<!DOCTYPE html>	Tells the browser to use the modern standards rendering mode. Always the first line. Not a tag; it has no closing tag.
<html lang="en">	The root element. Everything else goes inside. lang states the language of the page.
<head>	Information about the page that is not displayed: character set, title, links to CSS, metadata.
<meta charset="utf-8">	Declares the character encoding. Must come within the first 1024 bytes. UTF-8 supports every language.
<meta name="viewport" ...>	Makes the page scale correctly on phones.
<title>	Required. Shown in the browser tab, bookmarks and search results.
<body>	Everything the visitor sees.
<script>	JavaScript. Usually placed at the end of the body or given the defer attribute so it does not block rendering.

Attributes

Attributes give extra information about an element. They are written in the opening tag only. Rules:

- Names are case-insensitive but by convention are written in lower case.
- Values should be quoted with double quotes. Single quotes are also allowed. Quotes may be omitted only if the value contains no spaces or special characters, but it is safer to always quote.
- A boolean attribute is either present or absent; its value does not matter. <input disabled>, <input disabled=""> and <input disabled="disabled"> all mean the same thing. Writing disabled="false" still means disabled! To turn it off, remove the attribute.
- An attribute may appear only once on an element.
- Enumerated attributes accept a fixed list of keywords, for example dir="ltr" or dir="rtl".

```
<a href="https://example.com" target="_blank" rel="noopener">Visit</a>
<input type="checkbox" checked disabled>
<div id="main" class="container wide" data-user-id="42"></div>
```

Nesting

Elements must be properly nested: the element opened last must be closed first. right is correct; wrong is an error.

Not every element may go inside every other. The rules are described by content categories (see below) and are listed in the 'Permitted parents' and 'Permitted content' rows of each element entry. The most common mistakes:

- A cannot contain block-level elements such as , <ul>, <table> or another . The browser will silently

close the paragraph.

- An <a> cannot contain another <a> or any interactive element such as <button>.
- A <button> cannot contain interactive content.
- must be a direct child of <ul>, <ol> or <menu>. <tr> must be inside <table>, <thead>, <tbody> or <tfoot>. <td> and <th> must be inside <tr>. <option> must be inside <select>, <optgroup> or <datalist>.
- <header> and <footer> cannot contain another <header> or <footer>.
- Heading elements must not be placed inside another heading.

Content categories

HTML5 groups elements into categories that define where they may appear. An element may belong to several categories.

Category	Meaning	Examples
Metadata content	Sets up the presentation or behaviour of the rest of the page; lives in <head>.	<base>, <link>, <meta>, <noscript>, <script>, <style>, <title>
Flow content	Almost everything that may appear in <body>.	<p>, , <h1>, , <table>, <a>, <img>, plain text ...
Sectioning content	Defines the scope of headings and footers.	<article>, <aside>, <nav>, <section>
Heading content	Section headings.	<h1> to <h6>, <hgroup>

Category	Meaning	Examples
Phrasing content	Text and the elements that mark up text within a paragraph.	<a>, , , , <img>, <input>, <code>, plain text ...
Embedded content	Imports another resource into the page.	<audio>, <canvas>, <embed>, <iframe>, <img>, <math>, <object>, <picture>, <svg>, <video>
Interactive content	Designed for user interaction.	<a href>, <button>, <details>, <input>, <label>, <select>, <textarea>, <video controls>
Palpable content	Content that is neither empty nor hidden, so that an element has something visible.	Most flow and phrasing content
Form-associated content	Elements that have a form owner.	<button>, <fieldset>, <input>, <label>, <meter>, <object>, <output>, <select>, <textarea>

Block-level and inline elements

Before HTML5 elements were described as either block-level or inline. The terms are still very useful because they match the default CSS display of each element.

	Block-level (display: block)	Inline (display: inline)
Starts on a new line?	Yes	No; flows with the text
Takes full width?	Yes, of its container	Only as wide as its content

	Block-level (display: block)	Inline (display: inline)
Can set width/height?	Yes	No (unless display is changed)
Can contain?	Other blocks and inline elements	Only other inline elements and text
Examples	, <p>, <h1>-<h6>, , , , <table>, <form>, <header>, <footer>, <section>, <article>, <nav>, <main>, <aside>, <blockquote>, <pre>, <hr>, <figure>	, <a>, , , <b>, <i>, <img>, <code>, , <input>, <label>, <button>, <select>, <textarea>, <abbr>, <cite>, <q>, <small>, <sub>, <sup>, <time>, <mark>

Comments

```
<!-- This is a comment. The browser ignores it. -->
<!--
  Comments can span
  several lines.
-->
```

Comments may not contain the sequence -- inside them and may not be nested. Remember that visitors can read comments by viewing the page source, so never put passwords or private information in them.

Character references (entities)

Some characters have special meaning in HTML and must be written as character references when you want them to

appear as text. Every reference starts with & and ends with ;.

Character	Named reference	Numeric reference	Why it is needed
<	<	<	Starts a tag
>	>	>	Ends a tag
&	&	&	Starts a reference
"	"	"	Delimits attribute values
'	'	'	Delimits attribute values
non-breaking space			A space that will not wrap or collapse
(c)	©	©	Convenience
EUR	€	€	Convenience

Numeric references may be decimal (€) or hexadecimal (€). With UTF-8 encoding you can type most characters directly and only <, > and & really need references. The complete entity table is in Part 9.

Whitespace

In normal text the browser collapses any run of spaces, tabs and line breaks into a single space, and removes spaces at the start and end of a block. To preserve whitespace exactly, use the <pre> element or the CSS property white-space: pre. To

force a line break use <br>. To insert a space that cannot collapse use .

Case sensitivity and quoting

- Tag and attribute names are not case-sensitive in HTML (<DIV> equals), but lower case is the universal convention and is required in XHTML.
- Attribute values may be case-sensitive depending on the attribute: id and class values are case-sensitive; enumerated keywords such as type="TEXT" are not.
- Always quote attribute values. It avoids a whole category of bugs.

Character encoding

Always save your files as UTF-8 and declare it with <meta charset="utf-8"> as the first thing inside <head>. UTF-8 can represent every character of every language, including Arabic, and is the only encoding recommended by the HTML standard. If the encoding is wrong you will see question marks or strange symbols instead of your text.

Right-to-left languages

For Arabic, Hebrew, Persian and Urdu pages set dir="rtl" and the correct lang on the <html> element. The browser then aligns text to the right, mirrors lists and tables and handles mixed left-to-right words correctly.

```
<html lang="ar" dir="rtl">
```

Validation

A validator is a tool that checks your HTML for errors. Browsers are forgiving and will display broken HTML, but the result may differ between browsers and may be inaccessible. Use the free W3C validator at https://validator.w3.org/ or the Nu HTML Checker at https://validator.nu/.

The ten most common beginner mistakes

- Forgetting <!DOCTYPE html>, which puts the browser in 'quirks mode' and changes layout behaviour.
- Forgetting <meta charset="utf-8">, which breaks non-English characters.
- Forgetting to close tags, or closing them in the wrong order.
- Putting block elements inside <p>.
- Using <br> repeatedly to create space instead of CSS margins.
- Using <table> for page layout instead of CSS.
- Using <b> and <i> for emphasis where and carry the meaning.
- Omitting the alt attribute on images.
- Using for everything where <header>, <nav>, <main>, <footer> describe the content better.
- Skipping heading levels (jumping from <h1> to <h4>).

Part 3

HTML Version by Version

Which elements each version of HTML introduced, from HTML 1 to the Living Standard.

How to read this part

Each chapter lists the elements whose history mentions that version of HTML, with a one-paragraph summary. An element can appear in more than one chapter (for example when HTML 4 changed it and HTML5 changed it again). Elements marked OBSOLETE are documented for reading old pages only; use the modern replacement named in the element's full entry in Part 6.

HTML 1.0 (1991-1993)

The first HTML, described in Tim Berners-Lee's 'HTML Tags' document (1991) and the 1993 IETF draft by Berners-Lee and Dan Connolly. It had about 20 elements: headings, paragraphs, anchors, lists, addresses, preformatted text, plus a few editor hints. There were no images (the <img> tag was added by Mosaic in 1993), no tables and no forms.

Elements in this chapter: 22

Element	Meaning	Status today
<a>	Anchor (hyperlink)	current
<address>	Contact address	current
 	Line break	current
<dd>	Description details	current
<dir>	Directory list (obsolete)	obsolete
<dl>	Description list	current
<dt>	Description term	current
<h1>	Headings h1 to h6	current
<isindex>	Search index prompt (obsolete)	obsolete
	List item	current
<listing>	Listing (obsolete)	obsolete
<menu>	Menu (toolbar list)	current
<nextid>	Next identifier (HTML 1 editor hint)	obsolete
	Ordered list	current
<p>	Paragraph	current

Element	Meaning	Status today
<plaintext>	Plain text (obsolete)	obsolete
<pre>	Pre-formatted text	current
<rb>	Ruby base (deprecated)	deprecated
<ruby>	Ruby annotation	current
<title>	Document title	current
	Unordered list	current
<xmp>	Example text (obsolete)	obsolete

<a> — Anchor (hyperlink)

Status: CURRENT | Versions: HTML 1 (1991), HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <a> element (anchor) creates a hyperlink to another web page, a file, a location within the same page, an email address, a telephone number, or any other resource that can be identified by a URL. Hyperlinks are the defining feature of the World Wide Web and <a> was one of the very first elements created by Tim Berners-Lee in 1991.

```
<a href="URL">link text</a>
```

<address> — Contact address

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <address> element indicates that its content provides contact information for a person, people or an organisation. When placed inside an <article> it gives the contact details of the article's author; when placed in the page <footer> or <body> it gives the contact details for the whole document.

```
<address>contact information</address>
```


 — Line break

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <br> element produces a line break in text: the text after it starts on a new line. It is a void element with no closing tag. Use it only where the division of lines is part of the content, as in a postal address or a poem.

```
<br>
```

<dd> — Description details

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <dd> element provides the description, definition or value for the preceding term (<dt>) in a description list (<dl>). One term may have several <dd> elements, and several terms may share one <dd>. Browsers indent <dd> from the left by default.

```
<dl>
  <dt>Term</dt>
  <dd>Description</dd>
</dl>
```

<dir> — Directory list (obsolete)

Status: OBSOLETE | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

The <dir> element was a list of short items, intended to be shown in columns like a file directory listing. Browsers never implemented the columns and rendered it like <ul>. It was deprecated in HTML 4.01 and removed in HTML5. Use <ul> instead.

```
<dir><li>item</li></dir>
```

<dl> — Description list

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <dl> element represents a description list: a list of groups of terms (<dt>) and their descriptions (<dd>). Common uses are glossaries, dictionaries, metadata displays (key: value pairs), FAQ lists and product specifications.

```
<dl>
  <dt>Term</dt>
  <dd>Description</dd>
</dl>
```

<dt> — Description term

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <dt> element specifies a term, name or key in a description list (<dl>). It is followed by one or more <dd> elements that describe it. Several <dt> elements in a row share the following <dd>. A <dt> may not contain headings, sections, headers or footers.

```
<dt>Term</dt>
```

<h1> — Headings h1 to h6

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <h1> to <h6> elements represent six levels of section headings. <h1> is the highest (most important) level and <h6> the lowest. Headings describe the topic of the section that follows them, and together they form the outline of the document, like the table of contents of a book.

```
<h1>Main title</h1>
<h2>Section</h2>
<h3>Sub-section</h3>
```

<isindex> — Search index prompt (obsolete)

Status: OBSOLETE | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

The <isindex> element, one of the original 1991 elements, told the browser that the document was a searchable index and made it display a single-line text field with a prompt. Submitting the field reloaded the page with ?keywords in the URL. It was made redundant by forms in HTML 2.0, deprecated in HTML 4.01 and removed in HTML5. Use a <form> with an <input type="search">.

```
<isindex prompt="Search: ">
```

 — List item

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <li> element represents one item in a list. It must be contained in an ordered list (<ol>), an unordered list (<ul>) or a menu (<menu>). In ordered lists the value attribute sets the number of the item, and subsequent items continue counting from it.

```
<ul>
  <li>Item</li>
</ul>
```

<listing> — Listing (obsolete)

Status: OBSOLETE | Versions: HTML 1, HTML 2.0 (deprecated); obsolete

The <listing> element, from the 1991 tag set, displayed its content in a monospace font exactly as written, like <pre> but originally at a smaller size and without interpreting markup. It was deprecated already in HTML 2.0 and removed in HTML 3.2. Use <pre>, optionally with <code>.

```
<listing>text</listing>
```

<menu> — Menu (toolbar list)

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01 (deprecated), HTML5 (redefined)

The <menu> element is a semantic alternative to <ul> for a list of commands or actions, such as a toolbar of buttons. Each command is an <li> containing a <button> or similar control. Browsers render it identically to <ul>.

```
<menu>
  <li><button>Action</button></li>
</menu>
```

<nextid> — Next identifier (HTML 1 editor hint)

Status: OBSOLETE | Versions: HTML 1 / HTML 2.0 (RFC 1866); removed in HTML 3.2

The <nextid> element was used by the very first HTML editors (the NeXT-based editor written at CERN) to remember the next automatically generated anchor name, so that the editor could continue numbering anchors (z1, z2, z3...) when a document was reopened. It carried a single attribute, n, holding that name. It had no visible effect and was placed in the <head>.

```
<nextid n="z12">
```

 — Ordered list

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <ol> element represents an ordered list of items: a list where the order matters, such as the steps of a recipe, the ranking of a competition, or the chapters of a book. Browsers number the items automatically. Each item is an <li>. If the order is not meaningful, use <ul> instead.

```
<ol>
  <li>First</li>
  <li>Second</li>
</ol>
```

<p> — Paragraph

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <p> element represents a paragraph: a block of related text, usually a group of sentences on one topic. Browsers display paragraphs as blocks separated by vertical space (a margin of 1em above and below). Paragraphs are one of the most used elements in HTML and one of the original elements from 1991, where <p> was a separator between paragraphs rather than a container.

```
<p>Text of the paragraph.</p>
```

<plaintext> — Plain text (obsolete)

Status: OBSOLETE | Versions: HTML 1, HTML 2.0 (deprecated); obsolete

The <plaintext> element told the browser to treat everything after it as plain text, without interpreting any further tags, until the end of the file. It could not be closed. It was one of the 1991 elements, was deprecated in HTML 2.0 and is obsolete. Use <pre> for pre-formatted text, escaping < and & as entities, or serve the file as text/plain.

```
<plaintext>
```

<pre> — Pre-formatted text

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <pre> element represents pre-formatted text that is displayed exactly as written in the HTML file: every space, tab and line break is preserved, and a monospace (fixed-width) font is used. It is the standard way to show source code, ASCII art, poetry with meaningful spacing, email messages and terminal output.

```
<pre>
  text with
    preserved   spacing
</pre>
```

<rb> — Ruby base (deprecated)

Status: DEPRECATED | Versions: XHTML 1.1 Ruby, HTML 5.1; removed from the Living Standard

The <rb> element explicitly marked the base text component of a ruby annotation, the text that the <rt> annotation is placed above. The Living Standard removed it because the base text can simply be written directly inside <ruby>. Browsers still support it.

```
<ruby><rb>□</rb><rt>kan</rt></ruby>
```

<ruby> — Ruby annotation

Status: CURRENT | Versions: XHTML 1.1 (2001), HTML5

The <ruby> element represents small annotations rendered above, below or beside base text, most often used to show the pronunciation of East Asian characters. The name comes from a small typographic size called 'ruby' used by British printers. The base text is written directly inside <ruby>, each annotation in an <rt>, and optional fallback parentheses in <rp>.

```
<ruby>base<rp>(</rp><rt>annotation</rt><rp>)</rp></ruby>
```

<title> — Document title

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <title> element defines the title of the document, shown in the browser's title bar or tab, used as the default name for bookmarks, displayed as the clickable headline in search engine results, and announced first by screen readers when the page loads. It contains text only; any tags inside are treated as literal text. Every document must have exactly one <title>, inside <head>.

```
<title>Page title</title>
```

 — Unordered list

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <ul> element represents an unordered list of items: a list where changing the order would not change the meaning, such as a shopping list, a set of features, or the links of a navigation menu. Browsers show each item with a bullet. Each item is an <li>. If the order matters, use <ol>.

```
<ul>
  <li>Item</li>
  <li>Item</li>
</ul>
```

<xmp> — Example text (obsolete)

Status: OBSOLETE | Versions: HTML 1, HTML 2.0 (deprecated); obsolete

The <xmp> element (example) displayed its content literally, without interpreting any markup, in a monospace font, so that authors could show HTML source without escaping < and &. It was one of the 1991 elements, deprecated in HTML 2.0 and removed in HTML 3.2, although browsers still support it for old pages. Use <pre> with escaped entities.

```
<xmp><p>shown literally</p></xmp>
```

HTML 2.0 (RFC 1866, 1995)

HTML 2.0 was the first official standard, published by the IETF in November 1995. It documented what browsers already supported: images, forms (input, select, textarea), the <head>/<body> split and character entities for Latin-1.

Elements in this chapter: 44

Element	Meaning	Status today
<a>	Anchor (hyperlink)	current
<address>	Contact address	current
<b>	Bring attention to (bold)	current
<base>	Document base URL	current
<blockquote>	Block quotation	current
<body>	Document body	current
 	Line break	current
<cite>	Citation (title of a work)	current
<code>	Inline code	current
<dd>	Description details	current
<dir>	Directory list (obsolete)	obsolete
<dl>	Description list	current
<dt>	Description term	current
	Emphasis	current
<form>	Form	current
<h1>	Headings h1 to h6	current

Element	Meaning	Status today
<head>	Document head	current
<hr>	Thematic break (horizontal rule)	current
<html>	Document root	current
<i>	Idiomatic text (italic)	current
<img>	Image	current
<input>	Input control	current
<isindex>	Search index prompt (obsolete)	obsolete
<kbd>	Keyboard input	current
	List item	current
<link>	External resource link	current
<listing>	Listing (obsolete)	obsolete
<menu>	Menu (toolbar list)	current
<meta>	Metadata	current
<nextid>	Next identifier (HTML 1 editor hint)	obsolete
	Ordered list	current
<option>	Option	current
<p>	Paragraph	current
<plaintext>	Plain text (obsolete)	obsolete
<pre>	Pre-formatted text	current
<samp>	Sample output	current

Element	Meaning	Status today
<select>	Drop-down / list box	current
	Strong importance	current
<textarea>	Multi-line text input	current
<title>	Document title	current
<tt>	Teletype text (obsolete)	obsolete
	Unordered list	current
<var>	Variable	current
<xmp>	Example text (obsolete)	obsolete

<a> — Anchor (hyperlink)

Status: CURRENT | Versions: HTML 1 (1991), HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <a> element (anchor) creates a hyperlink to another web page, a file, a location within the same page, an email address, a telephone number, or any other resource that can be identified by a URL. Hyperlinks are the defining feature of the World Wide Web and <a> was one of the very first elements created by Tim Berners-Lee in 1991.

```
<a href="URL">link text</a>
```

<address> — Contact address

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <address> element indicates that its content provides contact information for a person, people or an organisation. When placed inside an <article> it gives the contact details of the article's author; when placed in the page <footer> or <body> it gives the contact details for the whole document.

```
<address>contact information</address>
```

<b> — Bring attention to (bold)

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <b> element draws the reader's attention to a span of text without giving it extra importance, emphasis or an alternative voice. Browsers render it in bold. Typical uses are keywords in a summary, product names in a review, or the lead sentence of an article.

```
<b>text</b>
```

<base> — Document base URL

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <base> element specifies the base URL used to resolve all relative URLs in the document, and/or the default target for all links and forms. There may be only one <base> element per document and it must be placed in <head>, before any element that uses a URL.

```
<base href="URL" target="_blank">
```

<blockquote> — Block quotation

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <blockquote> element indicates that the enclosed text is an extended quotation from another source. Browsers indent it on both sides by default. The optional cite attribute holds the URL of the source; a visible citation should be given with the <cite> element, usually in a <footer> inside the blockquote or in a following paragraph.

```
<blockquote cite="URL">quoted text</blockquote>
```

<body> — Document body

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <body> element contains all the content of the document that is displayed to the visitor: text, images, links, forms, media, and the scripts that operate on them. There is exactly one <body> in a document and it is the second child of <html>, after <head>.

```
<body>...</body>
```


 — Line break

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <br> element produces a line break in text: the text after it starts on a new line. It is a void element with no closing tag. Use it only where the division of lines is part of the content, as in a postal address or a poem.

```
<br>
```

<cite> — Citation (title of a work)

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <cite> element marks the title of a creative work that is being referenced: a book, article, film, song, painting, play, poem, website, legal case, computer program, and so on. Browsers render it in italics.

```
<cite>Title of Work</cite>
```

<code> — Inline code

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <code> element marks a fragment of computer code: an element name, a file name, a variable, a function, a command, or any other string a computer would recognise. Browsers render it in a monospace font.

```
<code>snippet</code>
```

<dd> — Description details

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <dd> element provides the description, definition or value for the preceding term (<dt>) in a description list (<dl>). One term may have several <dd> elements, and several terms may share one <dd>. Browsers indent <dd> from the left by default.

```
<dl>
  <dt>Term</dt>
  <dd>Description</dd>
</dl>
```

<dir> — Directory list (obsolete)

Status: OBSOLETE | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

The <dir> element was a list of short items, intended to be shown in columns like a file directory listing. Browsers never implemented the columns and rendered it like <ul>. It was deprecated in HTML 4.01 and removed in HTML5. Use <ul> instead.

```
<dir><li>item</li></dir>
```

<dl> — Description list

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <dl> element represents a description list: a list of groups of terms (<dt>) and their descriptions (<dd>). Common uses are glossaries, dictionaries, metadata displays (key: value pairs), FAQ lists and product specifications.

```
<dl>
  <dt>Term</dt>
  <dd>Description</dd>
</dl>
```

<dt> — Description term

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <dt> element specifies a term, name or key in a description list (<dl>). It is followed by one or more <dd> elements that describe it. Several <dt> elements in a row share the following <dd>. A <dt> may not contain headings, sections, headers or footers.

```
<dt>Term</dt>
```

— Emphasis

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The element marks text that has stress emphasis: the word or phrase you would say more forcefully if you were reading the sentence aloud. Changing which word is emphasised changes the meaning of the sentence. Browsers render it in italics.

```
<em>text</em>
```

<form> — Form

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <form> element represents a section of the document containing interactive controls (text boxes, check boxes, radio buttons, drop-down lists, buttons and so on) for collecting information from the user and sending it to a server. When the form is submitted, the browser gathers the name and value of every control that has a name, encodes them, and sends them to the URL in the action attribute using the HTTP method in the method attribute.

```
<form action="URL" method="post">
  ...controls...
  <button>Submit</button>
</form>
```

<h1> — Headings h1 to h6

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <h1> to <h6> elements represent six levels of section headings. <h1> is the highest (most important) level and <h6> the lowest. Headings describe the topic of the section that follows them, and together they form the outline of the document, like the table of contents of a book.

```
<h1>Main title</h1>
<h2>Section</h2>
<h3>Sub-section</h3>
```

<head> — Document head

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <head> element contains machine-readable information (metadata) about the document: its title, character encoding, links to style sheets and icons, scripts, and <meta> tags for search engines and social networks. Nothing inside <head> is displayed on the page itself, except the title, which appears in the browser tab.

```
<head>
  <meta charset="utf-8">
  <title>Title</title>
</head>
```

<hr> — Thematic break (horizontal rule)

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <hr> element represents a thematic break between paragraph-level content: a change of scene in a story, a shift of topic within a section, or a separator between groups of options in a menu. Browsers render it as a horizontal line, which is where its name (horizontal rule) comes from.

```
<hr>
```

<html> — Document root

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <html> element is the root element of an HTML document: every other element is a descendant of it. It has exactly two children: <head> followed by <body>. It comes immediately after the <!DOCTYPE html> declaration.

```
<!DOCTYPE html>
<html lang="en">
  <head>...</head>
  <body>...</body>
</html>
```

<i> — Idiomatic text (italic)

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <i> element marks a span of text that is set off from the normal prose for some reason other than emphasis or importance: an alternative voice or mood, a technical term, a taxonomic name (Homo sapiens), a phrase in another language, a thought, a ship's name, or a transliteration. Browsers render it in italics.

```
<i>text</i>
```

<img> — Image

Status: CURRENT | Versions: Mosaic (1993), HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <img> element embeds an image in the document. It is a void element; the image file is identified by the src attribute and is loaded separately. Supported formats include JPEG, PNG, GIF, WebP, AVIF, SVG, APNG, BMP and ICO. The alt attribute holds a text alternative that is displayed if the image cannot load and is read aloud by screen readers; it is required for accessibility.

```
<img src="URL" alt="description" width="W" height="H">
```

<input> — Input control

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <input> element creates an interactive control for accepting data from the user. It is the most versatile element in HTML: the type attribute selects one of more than twenty different controls, from a plain text box to a colour picker, a file chooser, a range slider or a hidden field. It is a void element.

```
<input type="text" name="field" id="field">
```

<isindex> — Search index prompt (obsolete)

Status: OBSOLETE | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

The <isindex> element, one of the original 1991 elements, told the browser that the document was a searchable index and made it display a single-line text field with a prompt. Submitting the field reloaded the page with ?keywords in the URL. It was made redundant by forms in HTML 2.0, deprecated in HTML 4.01 and removed in HTML5. Use a <form> with an <input type="search">.

```
<isindex prompt="Search: ">
```

<kbd> — Keyboard input

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <kbd> element marks text that represents user input from a keyboard, voice command, or other input device. Browsers render it in a monospace font. Nesting <kbd> elements inside a <kbd> represents individual keys in a key combination; wrapping <kbd> in <samp> represents input echoed by the system.

```
<kbd>Ctrl</kbd> + <kbd>S</kbd>
```

 — List item

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <li> element represents one item in a list. It must be contained in an ordered list (<ol>), an unordered list (<ul>) or a menu (<menu>). In ordered lists the value attribute sets the number of the item, and subsequent items continue counting from it.

```
<ul>
  <li>Item</li>
</ul>
```

<link> — External resource link

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <link> element specifies a relationship between the current document and an external resource. By far its most common use is loading a CSS style sheet (rel="stylesheet"), but it is also used for site icons (rel="icon"), web app manifests, preloading and prefetching resources, canonical URLs for search engines, alternate language versions, RSS feeds and more. It is a void element and normally lives in <head>, though body-ok link types such as stylesheet may appear in <body>.

```
<link rel="stylesheet" href="style.css">
```

<listing> — Listing (obsolete)

Status: OBSOLETE | Versions: HTML 1, HTML 2.0 (deprecated); obsolete

The <listing> element, from the 1991 tag set, displayed its content in a monospace font exactly as written, like <pre> but originally at a smaller size and without interpreting markup. It was deprecated already in HTML 2.0 and removed in HTML 3.2. Use <pre>, optionally with <code>.

```
<listing>text</listing>
```

<menu> — Menu (toolbar list)

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01 (deprecated), HTML5 (redefined)

The <menu> element is a semantic alternative to <ul> for a list of commands or actions, such as a toolbar of buttons. Each command is an <li> containing a <button> or similar control. Browsers render it identically to <ul>.

```
<menu>
  <li><button>Action</button></li>
</menu>
```

<meta> — Metadata

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <meta> element represents metadata about the document that cannot be expressed by <title>, <base>, <link>, <style> or <script>. It is a void element placed in <head>. Depending on which attributes are present it does one of four things: declares the character encoding (charset); provides document-level metadata as a name/content pair (name); simulates an HTTP response header (http-equiv); or supplies microdata (itemprop).

```
<meta charset="utf-8">
<meta name="description" content="...">
```

<nextid> — Next identifier (HTML 1 editor hint)

Status: OBSOLETE | Versions: HTML 1 / HTML 2.0 (RFC 1866); removed in HTML 3.2

The <nextid> element was used by the very first HTML editors (the NeXT-based editor written at CERN) to remember the next automatically generated anchor name, so that the editor could continue numbering anchors (z1, z2, z3...) when a document was reopened. It carried a single attribute, n, holding that name. It had no visible effect and was placed in the <head>.

```
<nextid n="z12">
```

 — Ordered list

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <ol> element represents an ordered list of items: a list where the order matters, such as the steps of a recipe, the ranking of a competition, or the chapters of a book. Browsers number the items automatically. Each item is an <li>. If the order is not meaningful, use <ul> instead.

```
<ol>
  <li>First</li>
  <li>Second</li>
</ol>
```

<option> — Option

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <option> element defines one item in a <select> drop-down list, an <optgroup>, or a <datalist> of suggestions. Its text content is what the user sees; the value attribute is what is submitted with the form. If value is omitted the text content is submitted instead.

```
<option value="v">Text</option>
```

<p> — Paragraph

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <p> element represents a paragraph: a block of related text, usually a group of sentences on one topic. Browsers display paragraphs as blocks separated by vertical space (a margin of 1em above and below). Paragraphs are one of the most used elements in HTML and one of the original elements from 1991, where <p> was a separator between paragraphs rather than a container.

```
<p>Text of the paragraph.</p>
```

<plaintext> — Plain text (obsolete)

Status: OBSOLETE | Versions: HTML 1, HTML 2.0 (deprecated); obsolete

The <plaintext> element told the browser to treat everything after it as plain text, without interpreting any further tags, until the end of the file. It could not be closed. It was one of the 1991 elements, was deprecated in HTML 2.0 and is obsolete. Use <pre> for pre-formatted text, escaping < and & as entities, or serve the file as text/plain.

```
<plaintext>
```

<pre> — Pre-formatted text

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <pre> element represents pre-formatted text that is displayed exactly as written in the HTML file: every space, tab and line break is preserved, and a monospace (fixed-width) font is used. It is the standard way to show source code, ASCII art, poetry with meaningful spacing, email messages and terminal output.

```
<pre>
  text with
    preserved   spacing
</pre>
```

<samp> — Sample output

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <samp> element marks sample or quoted output from a computer program or system: error messages, terminal output, log lines. Browsers render it in a monospace font. Nest <kbd> inside <samp> to show input echoed by the system, and <samp> inside <kbd> for input that names an on-screen item.

```
<samp>program output</samp>
```

<select> — Drop-down / list box

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <select> element creates a control for choosing one option (or, with multiple, several) from a list. It contains <option> elements, optionally grouped in <optgroup>. By default it appears as a drop-down menu; with the multiple attribute or a size greater than 1 it appears as a scrolling list box. The name attribute and the value of the chosen option(s) are submitted with the form.

```
<select name="n">
  <option value="1">One</option>
</select>
```

— Strong importance

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The element indicates that its content has strong importance, seriousness or urgency: a warning, a key instruction, the most important part of a sentence. Browsers render it in bold. Nesting inside increases the importance further.

```
<strong>important text</strong>
```

<textarea> — Multi-line text input

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <textarea> element creates a multi-line plain-text editing control, for comments, messages, addresses and any free-form text. Unlike <input>, it is not a void element: its initial value is the text between its tags, not a value attribute. Whitespace and line breaks inside the tags are preserved, so keep the closing tag right after the text to avoid unwanted spaces.

```
<textarea name="n" rows="4" cols="40">initial text</textarea>
```

<title> — Document title

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <title> element defines the title of the document, shown in the browser's title bar or tab, used as the default name for bookmarks, displayed as the clickable headline in search engine results, and announced first by screen readers when the page loads. It contains text only; any tags inside are treated as literal text. Every document must have exactly one <title>, inside <head>.

```
<title>Page title</title>
```

<tt> — Teletype text (obsolete)

Status: OBSOLETE | Versions: HTML 2.0, HTML 3.2, HTML 4.01; obsolete in HTML5

The <tt> element (teletype) rendered text in a monospace font, imitating a teletype or typewriter. It was purely presentational and HTML5 removed it. Use the semantic elements <code>, <kbd>, <samp> or <var>, or CSS font-family: monospace on a .

```
<tt>text</tt>
```

 — Unordered list

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <ul> element represents an unordered list of items: a list where changing the order would not change the meaning, such as a shopping list, a set of features, or the links of a navigation menu. Browsers show each item with a bullet. Each item is an <li>. If the order matters, use <ol>.

```
<ul>
  <li>Item</li>
  <li>Item</li>
</ul>
```

<var> — Variable

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <var> element represents the name of a variable in a mathematical expression or a programming context, or a placeholder for a value the reader must supply. Browsers render it in italics. It is one of the four 'computer' phrase elements together with <code>, <kbd> and <samp>.

```
<var>x</var>
```

<xmp> — Example text (obsolete)

Status: OBSOLETE | Versions: HTML 1, HTML 2.0 (deprecated); obsolete

The <xmp> element (example) displayed its content literally, without interpreting any markup, in a monospace font, so that authors could show HTML source without escaping < and &. It was one of the 1991 elements, deprecated in HTML 2.0 and removed in HTML 3.2, although browsers still support it for old pages. Use <pre> with escaped entities.

```
<xmp><p>shown literally</p></xmp>
```

HTML 3.2 (W3C, January 1997)

HTML 3.2 (code name 'Wilbur') was the first W3C Recommendation. It absorbed the popular Netscape and Internet Explorer extensions: tables, applets, text flow around images, subscripts and superscripts, and the presentational <font>, and <u> elements together with attributes such as bgcolor and align. Most of that presentational markup is obsolete today, replaced by CSS.

Elements in this chapter: 64

Element	Meaning	Status today
<a>	Anchor (hyperlink)	current
<address>	Contact address	current
<applet>	Java applet (obsolete)	obsolete
<area>	Image map area	current
<b>	Bring attention to (bold)	current
<base>	Document base URL	current
<basefont>	Base font (obsolete)	obsolete
<big>	Bigger text (obsolete)	obsolete
<blockquote>	Block quotation	current
<body>	Document body	current
 	Line break	current
<caption>	Table caption	current
	Centred block (obsolete)	obsolete

Element	Meaning	Status today
<cite>	Citation (title of a work)	current
<code>	Inline code	current
<dd>	Description details	current
<dfn>	Definition term	current
<dir>	Directory list (obsolete)	obsolete
	Generic block container	current
<dl>	Description list	current
<dt>	Description term	current
	Emphasis	current
<font>	Font (obsolete)	obsolete
<form>	Form	current
<h1>	Headings h1 to h6	current
<head>	Document head	current
<hr>	Thematic break (horizontal rule)	current
<html>	Document root	current
<i>	Idiomatic text (italic)	current
<img>	Image	current
<input>	Input control	current
<isindex>	Search index prompt (obsolete)	obsolete
<kbd>	Keyboard input	current
	List item	current

Element	Meaning	Status today
<link>	External resource link	current
<map>	Image map	current
<menu>	Menu (toolbar list)	current
<meta>	Metadata	current
<nextid>	Next identifier (HTML 1 editor hint)	obsolete
	Ordered list	current
<option>	Option	current
<p>	Paragraph	current
<param>	Object parameter (deprecated)	deprecated
<pre>	Pre-formatted text	current
<s>	Strikethrough (no longer accurate)	current
<samp>	Sample output	current
<script>	Script	current
<select>	Drop-down / list box	current
<small>	Side comment (fine print)	current
<strike>	Strikethrough (obsolete)	obsolete
	Strong importance	current
<style>	Embedded style sheet	current
<sub>	Subscript	current

Element	Meaning	Status today
<sup>	Superscript	current
<table>	Table	current
<td>	Table data cell	current
<textarea>	Multi-line text input	current
<th>	Table header cell	current
<title>	Document title	current
<tr>	Table row	current
<tt>	Teletype text (obsolete)	obsolete
<u>	Unarticulated annotation (underline)	current
	Unordered list	current
<var>	Variable	current

<a> — Anchor (hyperlink)

Status: CURRENT | Versions: HTML 1 (1991), HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <a> element (anchor) creates a hyperlink to another web page, a file, a location within the same page, an email address, a telephone number, or any other resource that can be identified by a URL. Hyperlinks are the defining feature of the World Wide Web and <a> was one of the very first elements created by Tim Berners-Lee in 1991.

```
<a href="URL">link text</a>
```

<address> — Contact address

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <address> element indicates that its content provides contact information for a person, people or an organisation. When placed inside an <article> it gives the contact details of the article's author; when placed in the page <footer> or <body> it gives the contact details for the whole document.

```
<address>contact information</address>
```

<applet> — Java applet (obsolete)

Status: OBSOLETE | Versions: HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

The <applet> element embedded a Java applet in the page. Applets were small Java programs that ran inside the browser with the help of a plug-in. Java applets were popular in the late 1990s but were slow, insecure and not supported on mobile devices. HTML 4.01 deprecated <applet> in favour of <object>, and HTML5 removed it entirely. No modern browser runs applets.

```
<applet code="MyApplet.class" width="300" height="200"></applet>
```

<area> — Image map area

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <area> element defines a clickable region inside an image map. An image map is an image (<img usemap="#name">) linked to a <map name="name"> element that contains one or more <area> elements. Each area has a shape and coordinates, and behaves like a hyperlink.

```
<area shape="rect" coords="x1,y1,x2,y2" href="URL" alt="text">
```

<b> — Bring attention to (bold)

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <b> element draws the reader's attention to a span of text without giving it extra importance, emphasis or an alternative voice. Browsers render it in bold. Typical uses are keywords in a summary, product names in a review, or the lead sentence of an article.

```
<b>text</b>
```

<base> — Document base URL

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <base> element specifies the base URL used to resolve all relative URLs in the document, and/or the default target for all links and forms. There may be only one <base> element per document and it must be placed in <head>, before any element that uses a URL.

```
<base href="URL" target="_blank">
```

<basefont> — Base font (obsolete)

Status: OBSOLETE | Versions: HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

The <basefont> element set the default font size, colour and face for the whole document. It was a presentational element from HTML 3.2 and was deprecated in HTML 4.01 in favour of CSS. HTML5 removed it. Use CSS on the body element instead.

```
<basefont size="3" color="black" face="Arial">
```

<big> — Bigger text (obsolete)

Status: OBSOLETE | Versions: HTML 3.2, HTML 4.01; obsolete in HTML5

The <big> element rendered its content one font size larger than the surrounding text. It was purely presentational and was removed in HTML5. Its counterpart <small> survived because it was given a new meaning (side comments and fine print). Use CSS font-size instead of <big>.

```
<big>text</big>
```

<blockquote> — Block quotation

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <blockquote> element indicates that the enclosed text is an extended quotation from another source. Browsers indent it on both sides by default. The optional cite attribute holds the URL of the source; a visible citation should be given with the <cite> element, usually in a <footer> inside the blockquote or in a following paragraph.

```
<blockquote cite="URL">quoted text</blockquote>
```

<body> — Document body

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <body> element contains all the content of the document that is displayed to the visitor: text, images, links, forms, media, and the scripts that operate on them. There is exactly one <body> in a document and it is the second child of <html>, after <head>.

```
<body>...</body>
```


 — Line break

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <br> element produces a line break in text: the text after it starts on a new line. It is a void element with no closing tag. Use it only where the division of lines is part of the content, as in a postal address or a poem.

```
<br>
```

<caption> — Table caption

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <caption> element gives a table a title or explanation. It must be the first child of the <table> element, and a table may have only one. By default it is displayed centred above the table; the CSS caption-side property can move it below.

```
<table>
  <caption>Title</caption>
  ...
</table>
```

— Centred block (obsolete)

Status: OBSOLETE | Versions: HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

The element horizontally centred its content. It was introduced by Netscape, standardised in HTML 3.2, deprecated in HTML 4.01 and removed in HTML5. It is equivalent to . Use CSS instead: text-align: center for inline content, or margin: 0 auto with a width for blocks.

```
<center>content</center>
```

<cite> — Citation (title of a work)

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <cite> element marks the title of a creative work that is being referenced: a book, article, film, song, painting, play, poem, website, legal case, computer program, and so on. Browsers render it in italics.

```
<cite>Title of Work</cite>
```

<code> — Inline code

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <code> element marks a fragment of computer code: an element name, a file name, a variable, a function, a command, or any other string a computer would recognise. Browsers render it in a monospace font.

```
<code>snippet</code>
```

<dd> — Description details

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <dd> element provides the description, definition or value for the preceding term (<dt>) in a description list (<dl>). One term may have several <dd> elements, and several terms may share one <dd>. Browsers indent <dd> from the left by default.

```
<dl>
  <dt>Term</dt>
  <dd>Description</dd>
</dl>
```

<dfn> — Definition term

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <dfn> element marks the term that is being defined in the surrounding sentence or paragraph. The nearest paragraph, description list group or section is the definition. Browsers render it in italics. If the element has a title attribute, that is the term being defined; if it contains an <abbr> with a title, the abbreviation's expansion is the term; otherwise the text content is the term.

```
<dfn>term</dfn>
```

<dir> — Directory list (obsolete)

Status: OBSOLETE | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

The <dir> element was a list of short items, intended to be shown in columns like a file directory listing. Browsers never implemented the columns and rendered it like <ul>. It was deprecated in HTML 4.01 and removed in HTML5. Use <ul> instead.

```
<dir><li>item</li></dir>
```

— Generic block container

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The element (division) is a generic container for flow content. It has no meaning of its own and no effect on the content or layout until it is styled with CSS (using class or id) or manipulated with JavaScript. Use it to group elements for styling purposes, for layout (flexbox, grid), or when no other element is more appropriate.

```
<div class="name">...</div>
```

<dl> — Description list

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <dl> element represents a description list: a list of groups of terms (<dt>) and their descriptions (<dd>). Common uses are glossaries, dictionaries, metadata displays (key: value pairs), FAQ lists and product specifications.

```
<dl>
  <dt>Term</dt>
  <dd>Description</dd>
</dl>
```

<dt> — Description term

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <dt> element specifies a term, name or key in a description list (<dl>). It is followed by one or more <dd> elements that describe it. Several <dt> elements in a row share the following <dd>. A <dt> may not contain headings, sections, headers or footers.

```
<dt>Term</dt>
```

— Emphasis

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The element marks text that has stress emphasis: the word or phrase you would say more forcefully if you were reading the sentence aloud. Changing which word is emphasised changes the meaning of the sentence. Browsers render it in italics.

```
<em>text</em>
```

<font> — Font (obsolete)

Status: OBSOLETE | Versions: HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

The <font> element set the size, colour and typeface of its text. It was the main way to style text before CSS, was deprecated in HTML 4.01 and removed in HTML5. Browsers still render it for old pages. Every use of <font> can be replaced by CSS: font-size, color and font-family.

```
<font size="4" color="red" face="Arial">text</font>
```

<form> — Form

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <form> element represents a section of the document containing interactive controls (text boxes, check boxes, radio buttons, drop-down lists, buttons and so on) for collecting information from the user and sending it to a server. When the form is submitted, the browser gathers the name and value of every control that has a name, encodes them, and sends them to the URL in the action attribute using the HTTP method in the method attribute.

```
<form action="URL" method="post">
  ...controls...
  <button>Submit</button>
</form>
```

<h1> — Headings h1 to h6

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <h1> to <h6> elements represent six levels of section headings. <h1> is the highest (most important) level and <h6> the lowest. Headings describe the topic of the section that follows them, and together they form the outline of the document, like the table of contents of a book.

```
<h1>Main title</h1>
<h2>Section</h2>
<h3>Sub-section</h3>
```

<head> — Document head

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <head> element contains machine-readable information (metadata) about the document: its title, character encoding, links to style sheets and icons, scripts, and <meta> tags for search engines and social networks. Nothing inside <head> is displayed on the page itself, except the title, which appears in the browser tab.

```
<head>
  <meta charset="utf-8">
  <title>Title</title>
</head>
```

<hr> — Thematic break (horizontal rule)

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <hr> element represents a thematic break between paragraph-level content: a change of scene in a story, a shift of topic within a section, or a separator between groups of options in a menu. Browsers render it as a horizontal line, which is where its name (horizontal rule) comes from.

```
<hr>
```

<html> — Document root

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <html> element is the root element of an HTML document: every other element is a descendant of it. It has exactly two children: <head> followed by <body>. It comes immediately after the <!DOCTYPE html> declaration.

```
<!DOCTYPE html>
<html lang="en">
  <head>...</head>
  <body>...</body>
</html>
```

<i> — Idiomatic text (italic)

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <i> element marks a span of text that is set off from the normal prose for some reason other than emphasis or importance: an alternative voice or mood, a technical term, a taxonomic name (Homo sapiens), a phrase in another language, a thought, a ship's name, or a transliteration. Browsers render it in italics.

```
<i>text</i>
```

<img> — Image

Status: CURRENT | Versions: Mosaic (1993), HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <img> element embeds an image in the document. It is a void element; the image file is identified by the src attribute and is loaded separately. Supported formats include JPEG, PNG, GIF, WebP, AVIF, SVG, APNG, BMP and ICO. The alt attribute holds a text alternative that is displayed if the image cannot load and is read aloud by screen readers; it is required for accessibility.

```
<img src="URL" alt="description" width="W" height="H">
```

<input> — Input control

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <input> element creates an interactive control for accepting data from the user. It is the most versatile element in HTML: the type attribute selects one of more than twenty different controls, from a plain text box to a colour picker, a file chooser, a range slider or a hidden field. It is a void element.

```
<input type="text" name="field" id="field">
```

<isindex> — Search index prompt (obsolete)

Status: OBSOLETE | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

The <isindex> element, one of the original 1991 elements, told the browser that the document was a searchable index and made it display a single-line text field with a prompt. Submitting the field reloaded the page with ?keywords in the URL. It was made redundant by forms in HTML 2.0, deprecated in HTML 4.01 and removed in HTML5. Use a <form> with an <input type="search">.

```
<isindex prompt="Search: ">
```

<kbd> — Keyboard input

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <kbd> element marks text that represents user input from a keyboard, voice command, or other input device. Browsers render it in a monospace font. Nesting <kbd> elements inside a <kbd> represents individual keys in a key combination; wrapping <kbd> in <samp> represents input echoed by the system.

```
<kbd>Ctrl</kbd> + <kbd>S</kbd>
```

 — List item

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <li> element represents one item in a list. It must be contained in an ordered list (<ol>), an unordered list (<ul>) or a menu (<menu>). In ordered lists the value attribute sets the number of the item, and subsequent items continue counting from it.

```
<ul>
  <li>Item</li>
</ul>
```

<link> — External resource link

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <link> element specifies a relationship between the current document and an external resource. By far its most common use is loading a CSS style sheet (rel="stylesheet"), but it is also used for site icons (rel="icon"), web app manifests, preloading and prefetching resources, canonical URLs for search engines, alternate language versions, RSS feeds and more. It is a void element and normally lives in <head>, though body-ok link types such as stylesheet may appear in <body>.

```
<link rel="stylesheet" href="style.css">
```

<map> — Image map

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <map> element, together with <area> elements, defines a client-side image map: an image with several clickable regions each linking to a different destination. The map is connected to an <img> through the img's usemap attribute, which must be # followed by the map's name.

```
<map name="n">
  <area ...>
</map>
<img usemap="#n" ...>
```

<menu> — Menu (toolbar list)

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01 (deprecated), HTML5 (redefined)

The <menu> element is a semantic alternative to <ul> for a list of commands or actions, such as a toolbar of buttons. Each command is an <li> containing a <button> or similar control. Browsers render it identically to <ul>.

```
<menu>
  <li><button>Action</button></li>
</menu>
```

<meta> — Metadata

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <meta> element represents metadata about the document that cannot be expressed by <title>, <base>, <link>, <style> or <script>. It is a void element placed in <head>. Depending on which attributes are present it does one of four things: declares the character encoding (charset); provides document-level metadata as a name/content pair (name); simulates an HTTP response header (http-equiv); or supplies microdata (itemprop).

```
<meta charset="utf-8">
<meta name="description" content="...">
```

<nextid> — Next identifier (HTML 1 editor hint)

Status: OBSOLETE | Versions: HTML 1 / HTML 2.0 (RFC 1866); removed in HTML 3.2

The <nextid> element was used by the very first HTML editors (the NeXT-based editor written at CERN) to remember the next automatically generated anchor name, so that the editor could continue numbering anchors (z1, z2, z3...) when a document was reopened. It carried a single attribute, n, holding that name. It had no visible effect and was placed in the <head>.

```
<nextid n="z12">
```

 — Ordered list

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <ol> element represents an ordered list of items: a list where the order matters, such as the steps of a recipe, the ranking of a competition, or the chapters of a book. Browsers number the items automatically. Each item is an <li>. If the order is not meaningful, use <ul> instead.

```
<ol>
  <li>First</li>
  <li>Second</li>
</ol>
```

<option> — Option

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <option> element defines one item in a <select> drop-down list, an <optgroup>, or a <datalist> of suggestions. Its text content is what the user sees; the value attribute is what is submitted with the form. If value is omitted the text content is submitted instead.

```
<option value="v">Text</option>
```

<p> — Paragraph

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <p> element represents a paragraph: a block of related text, usually a group of sentences on one topic. Browsers display paragraphs as blocks separated by vertical space (a margin of 1em above and below). Paragraphs are one of the most used elements in HTML and one of the original elements from 1991, where <p> was a separator between paragraphs rather than a container.

```
<p>Text of the paragraph.</p>
```

<param> — Object parameter (deprecated)

Status: DEPRECATED | Versions: HTML 3.2, HTML 4.01, HTML5; deprecated in the Living Standard

The <param> element defined a parameter for an <object> element, passing a name/value pair to the plug-in that displayed the object (for example the autoplay setting of a Flash movie). Since plug-ins no longer exist, the element serves no purpose; the Living Standard marks it deprecated and it is retained only for compatibility. It is a void element.

```
<object data="movie.swf">
  <param name="quality" value="high">
</object>
```

<pre> — Pre-formatted text

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <pre> element represents pre-formatted text that is displayed exactly as written in the HTML file: every space, tab and line break is preserved, and a monospace (fixed-width) font is used. It is the standard way to show source code, ASCII art, poetry with meaningful spacing, email messages and terminal output.

```
<pre>
  text with
    preserved   spacing
</pre>
```

<s> — Strikethrough (no longer accurate)

Status: CURRENT | Versions: HTML 3.2, HTML 4.01 (deprecated), HTML5 (redefined)

The <s> element renders text with a line through it and represents content that is no longer accurate or no longer relevant, such as an old price next to the new one, or a sold-out item. In HTML 4 it was a purely presentational strike-through synonym for <strike> and was deprecated; HTML5 gave it this meaning and made it valid again while removing <strike>.

```
<s>outdated text</s>
```

<samp> — Sample output

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <samp> element marks sample or quoted output from a computer program or system: error messages, terminal output, log lines. Browsers render it in a monospace font. Nest <kbd> inside <samp> to show input echoed by the system, and <samp> inside <kbd> for input that names an on-screen item.

```
<samp>program output</samp>
```

<script> — Script

Status: CURRENT | Versions: HTML 3.2 (reserved), HTML 4.01, HTML5

The <script> element embeds executable code, almost always JavaScript, or links to an external script file with the src attribute. It can also hold data blocks (JSON, templates, import maps, speculation rules) that the browser does not execute when type is set to a non-script MIME type.

```
<script src="app.js" defer></script>
<script>
  // inline code
</script>
```

<select> — Drop-down / list box

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <select> element creates a control for choosing one option (or, with multiple, several) from a list. It contains <option> elements, optionally grouped in <optgroup>. By default it appears as a drop-down menu; with the multiple attribute or a size greater than 1 it appears as a scrolling list box. The name attribute and the value of the chosen option(s) are submitted with the form.

```
<select name="n">
  <option value="1">One</option>
</select>
```

<small> — Side comment (fine print)

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5 (redefined)

The <small> element represents side comments and small print: disclaimers, caveats, legal restrictions, copyright notices, attribution. It renders the text one size smaller. In HTML 3.2 and 4 it was purely presentational ('smaller text'); HTML5 kept it and gave it this meaning, while its counterpart <big> was removed.

```
<small>fine print</small>
```

<strike> — Strikethrough (obsolete)

Status: OBSOLETE | Versions: HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

The <strike> element drew a line through its text. It was purely presentational, was deprecated in HTML 4.01 and removed in HTML5. Use <del> for removed content, <s> for content that is no longer accurate, or CSS text-decoration: line-through for pure styling.

```
<strike>text</strike>
```

— Strong importance

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The element indicates that its content has strong importance, seriousness or urgency: a warning, a key instruction, the most important part of a sentence. Browsers render it in bold. Nesting inside increases the importance further.

```
<strong>important text</strong>
```

<style> — Embedded style sheet

Status: CURRENT | Versions: HTML 3.2 (reserved), HTML 4.01, HTML5

The <style> element contains CSS rules that apply to the document. It belongs in <head>, though browsers tolerate it in <body>. A document may have any number of <style> elements; they are applied in order together with any linked style sheets. For anything larger than a few rules, an external file loaded with <link rel="stylesheet"> is better because it can be cached and shared between pages.

```
<style>
  selector { property: value; }
</style>
```

<sub> — Subscript

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <sub> element renders text as a subscript: smaller and below the baseline. Use it only where the subscript has a typographic meaning, such as chemical formulas (H_2O), mathematical variable indices (x_1) or footnote markers in some styles. For purely visual lowering, use CSS vertical-align.

```
H<sub>2</sub>O
```

<sup> — Superscript

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <sup> element renders text as a superscript: smaller and above the baseline. Use it where the superscript has meaning: exponents (x^2), ordinal suffixes (1st), footnote references, and abbreviations like Mlle. For visual raising only, use CSS.

```
x<sup>2</sup>
```

<table> — Table

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <table> element represents tabular data: information arranged in a two-dimensional grid of rows and columns, where the position of each cell gives it meaning (this value belongs to this row and this column). Examples: price lists, timetables, statistics, comparison charts, spreadsheets.

```
<table>
  <caption>Title</caption>
  <thead><tr><th>Head</th></tr></thead>
  <tbody><tr><td>Data</td></tr></tbody>
</table>
```

<td> — Table data cell

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <td> element defines a cell of a table that contains data. It must be inside a <tr>. Each <td> occupies one column by default; colspan makes it span several columns and rowspan several rows. The headers attribute can list the ids of the <th> cells that describe it, which is needed only for complex tables where scope is not enough.

```
<tr>
  <td>Data</td>
</tr>
```

<textarea> — Multi-line text input

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <textarea> element creates a multi-line plain-text editing control, for comments, messages, addresses and any free-form text. Unlike <input>, it is not a void element: its initial value is the text between its tags, not a value attribute. Whitespace and line breaks inside the tags are preserved, so keep the closing tag right after the text to avoid unwanted spaces.

```
<textarea name="n" rows="4" cols="40">initial text</textarea>
```

<th> — Table header cell

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <th> element defines a header cell in a table: a cell that labels a column or a row rather than holding data. Browsers render it bold and centred. The scope attribute states whether the header applies to its column (col), its row (row), a group of columns (colgroup) or a group of rows (rowgroup). Browsers can usually guess for simple tables, but stating it explicitly is best practice because screen readers use the header text when reading each data cell.

```
<th scope="col">Header</th>
```

<title> — Document title

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <title> element defines the title of the document, shown in the browser's title bar or tab, used as the default name for bookmarks, displayed as the clickable headline in search engine results, and announced first by screen readers when the page loads. It contains text only; any tags inside are treated as literal text. Every document must have exactly one <title>, inside <head>.

```
<title>Page title</title>
```

<tr> — Table row

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <tr> element defines a row of cells in a table. It contains <th> (header) and/or <td> (data) cells and is placed inside <table>, <thead>, <tbody> or <tfoot>. Rows are the fundamental unit of table construction: you build a table one row at a time, and the columns emerge from the cells in each row.

```
<tr>
  <td>Cell 1</td>
  <td>Cell 2</td>
</tr>
```

<tt> — Teletype text (obsolete)

Status: OBSOLETE | Versions: HTML 2.0, HTML 3.2, HTML 4.01; obsolete in HTML5

The <tt> element (teletype) rendered text in a monospace font, imitating a teletype or typewriter. It was purely presentational and HTML5 removed it. Use the semantic elements <code>, <kbd>, <samp> or <var>, or CSS font-family: monospace on a .

```
<tt>text</tt>
```

<u> — Unarticulated annotation (underline)

Status: CURRENT | Versions: HTML 3.2, HTML 4.01 (deprecated), HTML5 (redefined)

The <u> element represents a span of inline text that should be rendered in a way that indicates a non-textual annotation: most commonly, marking misspelled words (as a word processor does with a wavy red line) or labelling proper names in Chinese text. Browsers render it with a solid underline. In HTML 4 <u> simply meant 'underline' and was deprecated; HTML5 redefined it.

```
<u>text</u>
```

 — Unordered list

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <ul> element represents an unordered list of items: a list where changing the order would not change the meaning, such as a shopping list, a set of features, or the links of a navigation menu. Browsers show each item with a bullet. Each item is an <li>. If the order matters, use <ol>.

```
<ul>
  <li>Item</li>
  <li>Item</li>
</ul>
```

<var> — Variable

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <var> element represents the name of a variable in a mathematical expression or a programming context, or a placeholder for a value the reader must supply. Browsers render it in italics. It is one of the four 'computer' phrase elements together with <code>, <kbd> and <samp>.

```
<var>x</var>
```

HTML 4.0 and 4.01 (1997-1999)

HTML 4 separated structure from presentation, introduced style sheets, scripting, frames, richer tables (thead, tbody, tfoot, colgroup), richer forms (button, fieldset, legend, label, optgroup), internationalisation (dir, lang, bdo) and accessibility features. It came in Strict, Transitional and Frameset flavours. XHTML 1.0 (2000) was HTML 4.01 re-expressed in XML.

Elements in this chapter: 86

Element	Meaning	Status today
<a>	Anchor (hyperlink)	current
<abbr>	Abbreviation	current
<acronym>	Acronym (obsolete)	obsolete
<address>	Contact address	current
<applet>	Java applet (obsolete)	obsolete
<area>	Image map area	current
<b>	Bring attention to (bold)	current
<base>	Document base URL	current
<basefont>	Base font (obsolete)	obsolete
<bdo>	Bidirectional text override	current
<big>	Bigger text (obsolete)	obsolete
<blockquote>	Block quotation	current

Element	Meaning	Status today
<body>	Document body	current
 	Line break	current
<button>	Button	current
<caption>	Table caption	current
	Centred block (obsolete)	obsolete
<cite>	Citation (title of a work)	current
<code>	Inline code	current
<col>	Table column	current
<colgroup>	Table column group	current
<dd>	Description details	current
<del>	Deleted text	current
<dfn>	Definition term	current
<dir>	Directory list (obsolete)	obsolete
	Generic block container	current
<dl>	Description list	current
<dt>	Description term	current
	Emphasis	current
<fieldset>	Form field group	current
<font>	Font (obsolete)	obsolete
<form>	Form	current
<frame>	Frame (obsolete)	obsolete

Element	Meaning	Status today
<frameset>	Frameset (obsolete)	obsolete
<h1>	Headings h1 to h6	current
<head>	Document head	current
<hr>	Thematic break (horizontal rule)	current
<html>	Document root	current
<i>	Idiomatic text (italic)	current
<iframe>	Inline frame	current
<img>	Image	current
<input>	Input control	current
<ins>	Inserted text	current
<isindex>	Search index prompt (obsolete)	obsolete
<kbd>	Keyboard input	current
<label>	Form control label	current
<legend>	Fieldset caption	current
	List item	current
<link>	External resource link	current
<map>	Image map	current
<menu>	Menu (toolbar list)	current
<meta>	Metadata	current
<noframes>	Fallback for frames (obsolete)	obsolete

Element	Meaning	Status today
<noscript>	Fallback when scripting is disabled	current
<object>	External object	current
	Ordered list	current
<optgroup>	Option group	current
<option>	Option	current
<p>	Paragraph	current
<param>	Object parameter (deprecated)	deprecated
<pre>	Pre-formatted text	current
<q>	Inline quotation	current
<s>	Strikethrough (no longer accurate)	current
<samp>	Sample output	current
<script>	Script	current
<select>	Drop-down / list box	current
<small>	Side comment (fine print)	current
	Generic inline container	current
<strike>	Strikethrough (obsolete)	obsolete
	Strong importance	current
<style>	Embedded style sheet	current
<sub>	Subscript	current

Element	Meaning	Status today
<sup>	Superscript	current
<table>	Table	current
<tbody>	Table body	current
<td>	Table data cell	current
<textarea>	Multi-line text input	current
<tfoot>	Table footer	current
<th>	Table header cell	current
<thead>	Table header	current
<title>	Document title	current
<tr>	Table row	current
<tt>	Teletype text (obsolete)	obsolete
<u>	Unarticulated annotation (underline)	current
	Unordered list	current
<var>	Variable	current

<a> — Anchor (hyperlink)

Status: CURRENT | Versions: HTML 1 (1991), HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <a> element (anchor) creates a hyperlink to another web page, a file, a location within the same page, an email address, a telephone number, or any other resource that can be identified by a URL. Hyperlinks are the defining feature of the World Wide Web and <a> was one of the very first elements created by Tim Berners-Lee in 1991.

```
<a href="URL">link text</a>
```

<abbr> — Abbreviation

Status: CURRENT | Versions: HTML 4.01, HTML5

The <abbr> element marks an abbreviation or acronym. The optional title attribute holds the full expansion, which most browsers show as a tooltip when the mouse hovers over the text.

```
<abbr title="expansion">ABBR</abbr>
```

<acronym> — Acronym (obsolete)

Status: OBSOLETE | Versions: HTML 4.01; obsolete in HTML5

The <acronym> element marked an acronym: an abbreviation pronounced as a word, such as NASA or laser. HTML5 removed it because the distinction from <abbr> was confusing and browsers treated the two identically.

```
<acronym title="expansion">NASA</acronym>
```

<address> — Contact address

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <address> element indicates that its content provides contact information for a person, people or an organisation. When placed inside an <article> it gives the contact details of the article's author; when placed in the page <footer> or <body> it gives the contact details for the whole document.

```
<address>contact information</address>
```

<applet> — Java applet (obsolete)

Status: OBSOLETE | Versions: HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

The <applet> element embedded a Java applet in the page. Applets were small Java programs that ran inside the browser with the help of a plug-in. Java applets were popular in the late 1990s but were slow, insecure and not supported on mobile devices. HTML 4.01 deprecated <applet> in favour of <object>, and HTML5 removed it entirely. No modern browser runs applets.

```
<applet code="MyApplet.class" width="300" height="200"></applet>
```

<area> — Image map area

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <area> element defines a clickable region inside an image map. An image map is an image (<img usemap="#name">) linked to a <map name="name"> element that contains one or more <area> elements. Each area has a shape and coordinates, and behaves like a hyperlink.

```
<area shape="rect" coords="x1,y1,x2,y2" href="URL" alt="text">
```

<b> — Bring attention to (bold)

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <b> element draws the reader's attention to a span of text without giving it extra importance, emphasis or an alternative voice. Browsers render it in bold. Typical uses are keywords in a summary, product names in a review, or the lead sentence of an article.

```
<b>text</b>
```

<base> — Document base URL

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <base> element specifies the base URL used to resolve all relative URLs in the document, and/or the default target for all links and forms. There may be only one <base> element per document and it must be placed in <head>, before any element that uses a URL.

```
<base href="URL" target="_blank">
```

<basefont> — Base font (obsolete)

Status: OBSOLETE | Versions: HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

The <basefont> element set the default font size, colour and face for the whole document. It was a presentational element from HTML 3.2 and was deprecated in HTML 4.01 in favour of CSS. HTML5 removed it. Use CSS on the body element instead.

```
<basefont size="3" color="black" face="Arial">
```

<bdo> — Bidirectional text override

Status: CURRENT | Versions: HTML 4.01, HTML5

The <bdo> element overrides the current text direction and forces its content to be displayed in the direction given by the dir attribute, character by character, ignoring the Unicode bidirectional algorithm. The dir attribute is required.

```
<bdo dir="rtl">text</bdo>
```

<big> — Bigger text (obsolete)

Status: OBSOLETE | Versions: HTML 3.2, HTML 4.01; obsolete in HTML5

The <big> element rendered its content one font size larger than the surrounding text. It was purely presentational and was removed in HTML5. Its counterpart <small> survived because it was given a new meaning (side comments and fine print). Use CSS font-size instead of <big>.

```
<big>text</big>
```

<blockquote> — Block quotation

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <blockquote> element indicates that the enclosed text is an extended quotation from another source. Browsers indent it on both sides by default. The optional cite attribute holds the URL of the source; a visible citation should be given with the <cite> element, usually in a <footer> inside the blockquote or in a following paragraph.

```
<blockquote cite="URL">quoted text</blockquote>
```

<body> — Document body

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <body> element contains all the content of the document that is displayed to the visitor: text, images, links, forms, media, and the scripts that operate on them. There is exactly one <body> in a document and it is the second child of <html>, after <head>.

```
<body>...</body>
```


 — Line break

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <br> element produces a line break in text: the text after it starts on a new line. It is a void element with no closing tag. Use it only where the division of lines is part of the content, as in a postal address or a poem.

```
<br>
```

<button> — Button

Status: CURRENT | Versions: HTML 4.01, HTML5

The <button> element represents a clickable button that the user can activate with a mouse, keyboard, finger or voice to perform an action. Unlike <input type="button">, a <button> may contain rich content: text, images, icons and other phrasing content.

```
<button type="button">label</button>
```

<caption> — Table caption

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <caption> element gives a table a title or explanation. It must be the first child of the <table> element, and a table may have only one. By default it is displayed centred above the table; the CSS caption-side property can move it below.

```
<table>
  <caption>Title</caption>
  ...
</table>
```

— Centred block (obsolete)

Status: OBSOLETE | Versions: HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

The element horizontally centred its content. It was introduced by Netscape, standardised in HTML 3.2, deprecated in HTML 4.01 and removed in HTML5. It is equivalent to . Use CSS instead: text-align: center for inline content, or margin: 0 auto with a width for blocks.

```
<center>content</center>
```

<cite> — Citation (title of a work)

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <cite> element marks the title of a creative work that is being referenced: a book, article, film, song, painting, play, poem, website, legal case, computer program, and so on. Browsers render it in italics.

```
<cite>Title of Work</cite>
```

<code> — Inline code

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <code> element marks a fragment of computer code: an element name, a file name, a variable, a function, a command, or any other string a computer would recognise. Browsers render it in a monospace font.

```
<code>snippet</code>
```

<col> — Table column

Status: CURRENT | Versions: HTML 4.01, HTML5

The <col> element defines one or more columns in a table so that attributes and styles can be applied to whole columns at once. It is a void element and lives inside a <colgroup>. The span attribute makes one <col> stand for several consecutive columns.

```
<colgroup>
  <col span="2" style="background: #eee">
</colgroup>
```

<colgroup> — Table column group

Status: CURRENT | Versions: HTML 4.01, HTML5

The <colgroup> element groups one or more columns of a table for the purpose of styling and structure. It is placed inside <table> after the optional <caption> and before any <thead>, <tbody>, <tfoot> or <tr>. It either has a span attribute (and no children) or contains <col> elements.

```
<colgroup span="2"></colgroup>
<!-- or -->
<colgroup><col><col></colgroup>
```

<dd> — Description details

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <dd> element provides the description, definition or value for the preceding term (<dt>) in a description list (<dl>). One term may have several <dd> elements, and several terms may share one <dd>. Browsers indent <dd> from the left by default.

```
<dl>
  <dt>Term</dt>
  <dd>Description</dd>
</dl>
```

<del> — Deleted text

Status: CURRENT | Versions: HTML 4.01, HTML5

The <del> element marks text that has been deleted from a document, typically to show changes between versions ('track changes'). Browsers render it with a line through it. It is usually paired with <ins>, which marks inserted text.

```
<del datetime="YYYY-MM-DD" cite="URL">deleted text</del>
```

<dfn> — Definition term

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <dfn> element marks the term that is being defined in the surrounding sentence or paragraph. The nearest paragraph, description list group or section is the definition. Browsers render it in italics. If the element has a title attribute, that is the term being defined; if it contains an <abbr> with a title, the abbreviation's expansion is the term; otherwise the text content is the term.

```
<dfn>term</dfn>
```

<dir> — Directory list (obsolete)

Status: OBSOLETE | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

The <dir> element was a list of short items, intended to be shown in columns like a file directory listing. Browsers never implemented the columns and rendered it like <ul>. It was deprecated in HTML 4.01 and removed in HTML5. Use <ul> instead.

```
<dir><li>item</li></dir>
```

— Generic block container

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The element (division) is a generic container for flow content. It has no meaning of its own and no effect on the content or layout until it is styled with CSS (using class or id) or manipulated with JavaScript. Use it to group elements for styling purposes, for layout (flexbox, grid), or when no other element is more appropriate.

```
<div class="name">...</div>
```

<dl> — Description list

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <dl> element represents a description list: a list of groups of terms (<dt>) and their descriptions (<dd>). Common uses are glossaries, dictionaries, metadata displays (key: value pairs), FAQ lists and product specifications.

```
<dl>
  <dt>Term</dt>
  <dd>Description</dd>
</dl>
```

<dt> — Description term

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <dt> element specifies a term, name or key in a description list (<dl>). It is followed by one or more <dd> elements that describe it. Several <dt> elements in a row share the following <dd>. A <dt> may not contain headings, sections, headers or footers.

```
<dt>Term</dt>
```

— Emphasis

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The element marks text that has stress emphasis: the word or phrase you would say more forcefully if you were reading the sentence aloud. Changing which word is emphasised changes the meaning of the sentence. Browsers render it in italics.

```
<em>text</em>
```

<fieldset> — Form field group

Status: CURRENT | Versions: HTML 4.01, HTML5

The <fieldset> element groups related controls and labels inside a form, for example all the fields of a postal address, or a set of radio buttons that answer one question. The optional <legend> element, which must be the first child, gives the group a caption. Browsers draw a border around the group with the legend placed on the border.

```
<fieldset>
  <legend>Caption</legend>
  ...controls...
</fieldset>
```

<font> — Font (obsolete)

Status: OBSOLETE | Versions: HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

The <font> element set the size, colour and typeface of its text. It was the main way to style text before CSS, was deprecated in HTML 4.01 and removed in HTML5. Browsers still render it for old pages. Every use of <font> can be replaced by CSS: font-size, color and font-family.

```
<font size="4" color="red" face="Arial">text</font>
```

<form> — Form

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <form> element represents a section of the document containing interactive controls (text boxes, check boxes, radio buttons, drop-down lists, buttons and so on) for collecting information from the user and sending it to a server. When the form is submitted, the browser gathers the name and value of every control that has a name, encodes them, and sends them to the URL in the action attribute using the HTTP method in the method attribute.

```
<form action="URL" method="post">
  ...controls...
  <button>Submit</button>
</form>
```

<frame> — Frame (obsolete)

Status: OBSOLETE | Versions: Netscape 2 (1996), HTML 4.01 Frameset; obsolete in HTML5

The <frame> element defined one rectangular sub-window inside a <frameset>, each displaying a separate HTML document. Frames were used in the late 1990s to keep a navigation menu fixed while the content scrolled. They caused many problems: bookmarks and the back button did not work as expected, search engines could not index the pages properly, printing was unreliable and screen readers struggled. HTML5 removed <frame> and <frameset>. Use CSS for layout and <iframe> when you truly need to embed another document.

```
<frameset cols="200,*">
  <frame src="menu.html" name="menu">
  <frame src="main.html" name="main">
</frameset>
```

<frameset> — Frameset (obsolete)

Status: OBSOLETE | Versions: Netscape 2, HTML 4.01 Frameset; obsolete in HTML5

The <frameset> element replaced <body> in a frames document and divided the window into rows and columns, each filled by a <frame> or a nested <frameset>. It required the HTML 4.01 Frameset DOCTYPE. It is obsolete in HTML5. See <frame> for the reasons and the modern replacement.

```
<frameset rows="80,*">...</frameset>
```

<h1> — Headings h1 to h6

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <h1> to <h6> elements represent six levels of section headings. <h1> is the highest (most important) level and <h6> the lowest. Headings describe the topic of the section that follows them, and together they form the outline of the document, like the table of contents of a book.

```
<h1>Main title</h1>
<h2>Section</h2>
<h3>Sub-section</h3>
```

<head> — Document head

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <head> element contains machine-readable information (metadata) about the document: its title, character encoding, links to style sheets and icons, scripts, and <meta> tags for search engines and social networks. Nothing inside <head> is displayed on the page itself, except the title, which appears in the browser tab.

```
<head>
  <meta charset="utf-8">
  <title>Title</title>
</head>
```

<hr> — Thematic break (horizontal rule)

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <hr> element represents a thematic break between paragraph-level content: a change of scene in a story, a shift of topic within a section, or a separator between groups of options in a menu. Browsers render it as a horizontal line, which is where its name (horizontal rule) comes from.

```
<hr>
```

<html> — Document root

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <html> element is the root element of an HTML document: every other element is a descendant of it. It has exactly two children: <head> followed by <body>. It comes immediately after the <!DOCTYPE html> declaration.

```
<!DOCTYPE html>
<html lang="en">
  <head>...</head>
  <body>...</body>
</html>
```

<i> — Idiomatic text (italic)

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <i> element marks a span of text that is set off from the normal prose for some reason other than emphasis or importance: an alternative voice or mood, a technical term, a taxonomic name (Homo sapiens), a phrase in another language, a thought, a ship's name, or a transliteration. Browsers render it in italics.

```
<i>text</i>
```

<iframe> — Inline frame

Status: CURRENT | Versions: Internet Explorer 3 (1996), HTML 4.01, HTML5

The <iframe> element embeds another HTML page inside the current page, in a rectangular area called a nested browsing context. Each iframe has its own document, its own window object and its own history. Common uses are embedding videos from YouTube, maps, advertisements, payment forms, social media widgets and third-party tools.

```
<iframe src="URL" title="description" width="600" height="400"></
iframe>
```

<img> — Image

Status: CURRENT | Versions: Mosaic (1993), HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <img> element embeds an image in the document. It is a void element; the image file is identified by the src attribute and is loaded separately. Supported formats include JPEG, PNG, GIF, WebP, AVIF, SVG, APNG, BMP and ICO. The alt attribute holds a text alternative that is displayed if the image cannot load and is read aloud by screen readers; it is required for accessibility.

```
<img src="URL" alt="description" width="W" height="H">
```

<input> — Input control

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <input> element creates an interactive control for accepting data from the user. It is the most versatile element in HTML: the type attribute selects one of more than twenty different controls, from a plain text box to a colour picker, a file chooser, a range slider or a hidden field. It is a void element.

```
<input type="text" name="field" id="field">
```

<ins> — Inserted text

Status: CURRENT | Versions: HTML 4.01, HTML5

The <ins> element marks text that has been added to a document, to show changes between versions. Browsers underline it by default. It is the counterpart of <del>. Like <del> it accepts optional cite and datetime attributes that record why and when the change was made.

```
<ins datetime="YYYY-MM-DD">inserted text</ins>
```

<isindex> — Search index prompt (obsolete)

Status: OBSOLETE | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

The <isindex> element, one of the original 1991 elements, told the browser that the document was a searchable index and made it display a single-line text field with a prompt. Submitting the field reloaded the page with ?keywords in the URL. It was made redundant by forms in HTML 2.0, deprecated in HTML 4.01 and removed in HTML5. Use a <form> with an <input type="search">.

```
<isindex prompt="Search: ">
```

<kbd> — Keyboard input

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <kbd> element marks text that represents user input from a keyboard, voice command, or other input device. Browsers render it in a monospace font. Nesting <kbd> elements inside a <kbd> represents individual keys in a key combination; wrapping <kbd> in <samp> represents input echoed by the system.

```
<kbd>Ctrl</kbd> + <kbd>S</kbd>
```

<label> — Form control label

Status: CURRENT | Versions: HTML 4.01, HTML5

The <label> element gives a caption to a form control. Associating a label with a control has two big benefits: clicking the label focuses or toggles the control (a much larger click target for checkboxes and radio buttons), and screen readers announce the label when the control gets focus.

```
<label for="id">Text</label> <input id="id">
<!-- or -->
<label>Text <input></label>
```

<legend> — Fieldset caption

Status: CURRENT | Versions: HTML 4.01, HTML5

The <legend> element provides a caption for its parent <fieldset>. It must be the first child of the fieldset. Browsers draw it on top of the fieldset's border. Screen readers announce the legend together with the label of each control inside the group, which is why fieldset/legend is the recommended way to caption groups of radio buttons or checkboxes.

```
<fieldset>
  <legend>Caption</legend>
  ...
</fieldset>
```

 — List item

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <li> element represents one item in a list. It must be contained in an ordered list (<ol>), an unordered list (<ul>) or a menu (<menu>). In ordered lists the value attribute sets the number of the item, and subsequent items continue counting from it.

```
<ul>
  <li>Item</li>
</ul>
```

<link> — External resource link

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <link> element specifies a relationship between the current document and an external resource. By far its most common use is loading a CSS style sheet (rel="stylesheet"), but it is also used for site icons (rel="icon"), web app manifests, preloading and prefetching resources, canonical URLs for search engines, alternate language versions, RSS feeds and more. It is a void element and normally lives in <head>, though body-ok link types such as stylesheet may appear in <body>.

```
<link rel="stylesheet" href="style.css">
```

<map> — Image map

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <map> element, together with <area> elements, defines a client-side image map: an image with several clickable regions each linking to a different destination. The map is connected to an <img> through the img's usemap attribute, which must be # followed by the map's name.

```
<map name="n">
  <area ...>
</map>
<img usemap="#n" ...>
```

<menu> — Menu (toolbar list)

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01 (deprecated), HTML5 (redefined)

The <menu> element is a semantic alternative to <ul> for a list of commands or actions, such as a toolbar of buttons. Each command is an <li> containing a <button> or similar control. Browsers render it identically to <ul>.

```
<menu>
  <li><button>Action</button></li>
</menu>
```

<meta> — Metadata

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <meta> element represents metadata about the document that cannot be expressed by <title>, <base>, <link>, <style> or <script>. It is a void element placed in <head>. Depending on which attributes are present it does one of four things: declares the character encoding (charset); provides document-level metadata as a name/content pair (name); simulates an HTTP response header (http-equiv); or supplies microdata (itemprop).

```
<meta charset="utf-8">
<meta name="description" content="...">
```

<noframes> — Fallback for frames (obsolete)

Status: OBSOLETE | Versions: HTML 4.01 Frameset; obsolete in HTML5

The <noframes> element contained content to display in browsers that did not support frames. It became obsolete together with <frameset> and <frame> in HTML5.

```
<noframes><body>fallback</body></noframes>
```

<noscript> — Fallback when scripting is disabled

Status: CURRENT | Versions: HTML 4.01, HTML5

The <noscript> element defines content to be shown only if scripting is disabled in the browser or the browser does not support scripting. When scripting is enabled the content is ignored entirely (in fact the parser treats it as raw text). It may be used in <head> (containing only <link>, <style> and <meta>) and in <body>.

```
<noscript>fallback content</noscript>
```

<object> — External object

Status: CURRENT | Versions: HTML 4.01, HTML5

The <object> element represents an external resource, treated as an image, a nested browsing context (like an iframe) or a resource handled by a plug-in, depending on its type. It was introduced in HTML 4.01 as a universal replacement for <img>, <applet> and <embed>. Unlike <embed>, it accepts fallback content between its tags, shown if the resource cannot be displayed, and it may contain <param> elements (now obsolete) that pass parameters to plug-ins.

```
<object data="URL" type="MIME" width="W" height="H">fallback</object>
```

 — Ordered list

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <ol> element represents an ordered list of items: a list where the order matters, such as the steps of a recipe, the ranking of a competition, or the chapters of a book. Browsers number the items automatically. Each item is an <li>. If the order is not meaningful, use <ul> instead.

```
<ol>
  <li>First</li>
  <li>Second</li>
</ol>
```

<optgroup> — Option group

Status: CURRENT | Versions: HTML 4.01, HTML5

The <optgroup> element groups related <option> elements inside a <select> under a non-selectable heading given by the label attribute. Groups cannot be nested. Disabling an optgroup disables all its options.

```
<select>
  <optgroup label="Group">
    <option>...</option>
  </optgroup>
</select>
```

<option> — Option

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <option> element defines one item in a <select> drop-down list, an <optgroup>, or a <datalist> of suggestions. Its text content is what the user sees; the value attribute is what is submitted with the form. If value is omitted the text content is submitted instead.

```
<option value="v">Text</option>
```

<p> — Paragraph

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <p> element represents a paragraph: a block of related text, usually a group of sentences on one topic. Browsers display paragraphs as blocks separated by vertical space (a margin of 1em above and below). Paragraphs are one of the most used elements in HTML and one of the original elements from 1991, where <p> was a separator between paragraphs rather than a container.

```
<p>Text of the paragraph.</p>
```

<param> — Object parameter (deprecated)

Status: DEPRECATED | Versions: HTML 3.2, HTML 4.01, HTML5; deprecated in the Living Standard

The <param> element defined a parameter for an <object> element, passing a name/value pair to the plug-in that displayed the object (for example the autoplay setting of a Flash movie). Since plug-ins no longer exist, the element serves no purpose; the Living Standard marks it deprecated and it is retained only for compatibility. It is a void element.

```
<object data="movie.swf">
  <param name="quality" value="high">
</object>
```

<pre> — Pre-formatted text

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <pre> element represents pre-formatted text that is displayed exactly as written in the HTML file: every space, tab and line break is preserved, and a monospace (fixed-width) font is used. It is the standard way to show source code, ASCII art, poetry with meaningful spacing, email messages and terminal output.

```
<pre>
  text with
    preserved   spacing
</pre>
```

<q> — Inline quotation

Status: CURRENT | Versions: HTML 4.01, HTML5

The <q> element indicates a short inline quotation that sits within a sentence. Browsers automatically add quotation marks around it, choosing the correct style for the language declared with lang (curly double quotes in English, guillemets in French, and so on), so you should not type quotation marks yourself. For long quotations that need their own paragraph use <blockquote>.

```
<q cite="URL">quoted words</q>
```

<s> — Strikethrough (no longer accurate)

Status: CURRENT | Versions: HTML 3.2, HTML 4.01 (deprecated), HTML5 (redefined)

The <s> element renders text with a line through it and represents content that is no longer accurate or no longer relevant, such as an old price next to the new one, or a sold-out item. In HTML 4 it was a purely presentational strike-through synonym for <strike> and was deprecated; HTML5 gave it this meaning and made it valid again while removing <strike>.

```
<s>outdated text</s>
```

<samp> — Sample output

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <samp> element marks sample or quoted output from a computer program or system: error messages, terminal output, log lines. Browsers render it in a monospace font. Nest <kbd> inside <samp> to show input echoed by the system, and <samp> inside <kbd> for input that names an on-screen item.

```
<samp>program output</samp>
```

<script> — Script

Status: CURRENT | Versions: HTML 3.2 (reserved), HTML 4.01, HTML5

The <script> element embeds executable code, almost always JavaScript, or links to an external script file with the src attribute. It can also hold data blocks (JSON, templates, import maps, speculation rules) that the browser does not execute when type is set to a non-script MIME type.

```
<script src="app.js" defer></script>
<script>
  // inline code
</script>
```

<select> — Drop-down / list box

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <select> element creates a control for choosing one option (or, with multiple, several) from a list. It contains <option> elements, optionally grouped in <optgroup>. By default it appears as a drop-down menu; with the multiple attribute or a size greater than 1 it appears as a scrolling list box. The name attribute and the value of the chosen option(s) are submitted with the form.

```
<select name="n">
  <option value="1">One</option>
</select>
```

<small> — Side comment (fine print)

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5 (redefined)

The <small> element represents side comments and small print: disclaimers, caveats, legal restrictions, copyright notices, attribution. It renders the text one size smaller. In HTML 3.2 and 4 it was purely presentational ('smaller text'); HTML5 kept it and gave it this meaning, while its counterpart <big> was removed.

```
<small>fine print</small>
```

— Generic inline container

Status: CURRENT | Versions: HTML 4.01, HTML5

The element is a generic inline container for phrasing content. Like , it has no meaning of its own and no visual effect; it exists to be a hook for CSS (via class or id) or JavaScript, or to carry attributes such as lang or dir on a part of a sentence. It should be used only when no other element is more appropriate: , , <mark>, <time>, <abbr>, <code> and the other text-level elements all carry meaning that does not.

```
<span class="name">text</span>
```

<strike> — Strikethrough (obsolete)

Status: OBSOLETE | Versions: HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

The <strike> element drew a line through its text. It was purely presentational, was deprecated in HTML 4.01 and removed in HTML5. Use <del> for removed content, <s> for content that is no longer accurate, or CSS text-decoration: line-through for pure styling.

```
<strike>text</strike>
```

— Strong importance

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The element indicates that its content has strong importance, seriousness or urgency: a warning, a key instruction, the most important part of a sentence. Browsers render it in bold. Nesting inside increases the importance further.

```
<strong>important text</strong>
```

<style> — Embedded style sheet

Status: CURRENT | Versions: HTML 3.2 (reserved), HTML 4.01, HTML5

The <style> element contains CSS rules that apply to the document. It belongs in <head>, though browsers tolerate it in <body>. A document may have any number of <style> elements; they are applied in order together with any linked style sheets. For anything larger than a few rules, an external file loaded with <link rel="stylesheet"> is better because it can be cached and shared between pages.

```
<style>
  selector { property: value; }
</style>
```

<sub> — Subscript

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <sub> element renders text as a subscript: smaller and below the baseline. Use it only where the subscript has a typographic meaning, such as chemical formulas (H_2O), mathematical variable indices (x_1) or footnote markers in some styles. For purely visual lowering, use CSS vertical-align.

```
H<sub>2</sub>0
```

<sup> — Superscript

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <sup> element renders text as a superscript: smaller and above the baseline. Use it where the superscript has meaning: exponents (x^2), ordinal suffixes (1st), footnote references, and abbreviations like Mlle. For visual raising only, use CSS.

```
x<sup>2</sup>
```

<table> — Table

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <table> element represents tabular data: information arranged in a two-dimensional grid of rows and columns, where the position of each cell gives it meaning (this value belongs to this row and this column). Examples: price lists, timetables, statistics, comparison charts, spreadsheets.

```
<table>
  <caption>Title</caption>
  <thead><tr><th>Head</th></tr></thead>
  <tbody><tr><td>Data</td></tr></tbody>
</table>
```

<tbody> — Table body

Status: CURRENT | Versions: HTML 4.01, HTML5

The <tbody> element groups the main data rows of a table, as distinct from the header rows in <thead> and the summary rows in <tfoot>. A table may have several <tbody> elements to group rows into sections (for example one per category), which can then be styled separately. When you write <tr> directly inside <table> without a <tbody>, the browser creates one automatically, so a tbody is always present in the DOM.

```
<tbody>
  <tr>...</tr>
</tbody>
```

<td> — Table data cell

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <td> element defines a cell of a table that contains data. It must be inside a <tr>. Each <td> occupies one column by default; colspan makes it span several columns and rowspan several rows. The headers attribute can list the ids of the <th> cells that describe it, which is needed only for complex tables where scope is not enough.

```
<tr>
  <td>Data</td>
</tr>
```

<textarea> — Multi-line text input

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <textarea> element creates a multi-line plain-text editing control, for comments, messages, addresses and any free-form text. Unlike <input>, it is not a void element: its initial value is the text between its tags, not a value attribute. Whitespace and line breaks inside the tags are preserved, so keep the closing tag right after the text to avoid unwanted spaces.

```
<textarea name="n" rows="4" cols="40">initial text</textarea>
```

<tfoot> — Table footer

Status: CURRENT | Versions: HTML 4.01, HTML5

The <tfoot> element groups the rows that summarise the columns of a table: totals, averages, counts. In HTML5 it is placed after the <tbody> elements (HTML 4.01 required it before them so that the browser could render the footer before receiving all data). When printing a long table, browsers can repeat the tfoot at the bottom of every page.

```
<tfoot>
  <tr><th>Total</th><td>260</td></tr>
</tfoot>
```

<th> — Table header cell

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <th> element defines a header cell in a table: a cell that labels a column or a row rather than holding data. Browsers render it bold and centred. The scope attribute states whether the header applies to its column (col), its row (row), a group of columns (colgroup) or a group of rows (rowgroup). Browsers can usually guess for simple tables, but stating it explicitly is best practice because screen readers use the header text when reading each data cell.

```
<th scope="col">Header</th>
```

<thead> — Table header

Status: CURRENT | Versions: HTML 4.01, HTML5

The <thead> element groups the rows that hold the column headers of a table. It comes after any <caption> and <colgroup> and before <tbody> and <tfoot>. Browsers repeat the thead at the top of each printed page of a long table, and CSS position: sticky on its cells keeps the headers visible while scrolling. A table may have at most one thead.

```
<thead>
  <tr><th>Column</th></tr>
</thead>
```

<title> — Document title

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <title> element defines the title of the document, shown in the browser's title bar or tab, used as the default name for bookmarks, displayed as the clickable headline in search engine results, and announced first by screen readers when the page loads. It contains text only; any tags inside are treated as literal text. Every document must have exactly one <title>, inside <head>.

```
<title>Page title</title>
```

<tr> — Table row

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <tr> element defines a row of cells in a table. It contains <th> (header) and/or <td> (data) cells and is placed inside <table>, <thead>, <tbody> or <tfoot>. Rows are the fundamental unit of table construction: you build a table one row at a time, and the columns emerge from the cells in each row.

```
<tr>
  <td>Cell 1</td>
  <td>Cell 2</td>
</tr>
```

<tt> — Teletype text (obsolete)

Status: OBSOLETE | Versions: HTML 2.0, HTML 3.2, HTML 4.01; obsolete in HTML5

The <tt> element (teletype) rendered text in a monospace font, imitating a teletype or typewriter. It was purely presentational and HTML5 removed it. Use the semantic elements <code>, <kbd>, <samp> or <var>, or CSS font-family: monospace on a .

```
<tt>text</tt>
```

<u> — Unarticulated annotation (underline)

Status: CURRENT | Versions: HTML 3.2, HTML 4.01 (deprecated), HTML5 (redefined)

The <u> element represents a span of inline text that should be rendered in a way that indicates a non-textual annotation: most commonly, marking misspelled words (as a word processor does with a wavy red line) or labelling proper names in Chinese text. Browsers render it with a solid underline. In HTML 4 <u> simply meant 'underline' and was deprecated; HTML5 redefined it.

```
<u>text</u>
```

 — Unordered list

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <ul> element represents an unordered list of items: a list where changing the order would not change the meaning, such as a shopping list, a set of features, or the links of a navigation menu. Browsers show each item with a bullet. Each item is an <li>. If the order matters, use <ol>.

```
<ul>
  <li>Item</li>
  <li>Item</li>
</ul>
```

<var> — Variable

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <var> element represents the name of a variable in a mathematical expression or a programming context, or a placeholder for a value the reader must supply. Browsers render it in italics. It is one of the four 'computer' phrase elements together with <code>, <kbd> and <samp>.

```
<var>x</var>
```

HTML5 (WHATWG 2004 onwards, W3C Recommendation 2014)

HTML5 added semantic sectioning (header, footer, nav, main, article, section, aside), native audio and video, canvas, new form controls and input types with built-in validation, and it defined precisely how browsers must parse even broken markup. It also removed the presentational and frame elements.

Elements in this chapter: 127

Element	Meaning	Status today
<a>	Anchor (hyperlink)	current
<abbr>	Abbreviation	current
<acronym>	Acronym (obsolete)	obsolete
<address>	Contact address	current
<applet>	Java applet (obsolete)	obsolete
<area>	Image map area	current
<article>	Self-contained article	current
<aside>	Aside (sidebar / tangential content)	current
<audio>	Embedded audio	current
<b>	Bring attention to (bold)	current
<base>	Document base URL	current
<basefont>	Base font (obsolete)	obsolete

Element	Meaning	Status today
<bdi>	Bidirectional isolate	current
<bdo>	Bidirectional text override	current
<big>	Bigger text (obsolete)	obsolete
<blockquote>	Block quotation	current
<body>	Document body	current
 	Line break	current
<button>	Button	current
<canvas>	Graphics canvas	current
<caption>	Table caption	current
	Centred block (obsolete)	obsolete
<cite>	Citation (title of a work)	current
<code>	Inline code	current
<col>	Table column	current
<colgroup>	Table column group	current
<data>	Machine-readable value	current
<datalist>	Predefined options for an input	current
<dd>	Description details	current
<del>	Deleted text	current
<details>	Disclosure widget	current

Element	Meaning	Status today
<dfn>	Definition term	current
<dialog>	Dialog box	current
<dir>	Directory list (obsolete)	obsolete
	Generic block container	current
<dl>	Description list	current
<dt>	Description term	current
	Emphasis	current
<embed>	External content	current
<fieldset>	Form field group	current
<figcaption>	Figure caption	current
<figure>	Figure with optional caption	current
<font>	Font (obsolete)	obsolete
<footer>	Footer	current
<form>	Form	current
<frame>	Frame (obsolete)	obsolete
<frameset>	Frameset (obsolete)	obsolete
<h1>	Headings h1 to h6	current
<head>	Document head	current
<header>	Header	current
<hgroup>	Heading group	current
<hr>	Thematic break (horizontal rule)	current
<html>	Document root	current

Element	Meaning	Status today
<i>	Idiomatic text (italic)	current
<iframe>	Inline frame	current
<img>	Image	current
<input>	Input control	current
<ins>	Inserted text	current
<isindex>	Search index prompt (obsolete)	obsolete
<kbd>	Keyboard input	current
<keygen>	Key-pair generator (obsolete)	obsolete
<label>	Form control label	current
<legend>	Fieldset caption	current
	List item	current
<link>	External resource link	current
<main>	Main content	current
<map>	Image map	current
<mark>	Highlighted (marked) text	current
<marquee>	Scrolling text (obsolete)	obsolete
<math>	MathML root	current
<menu>	Menu (toolbar list)	current
<menuitem>	Menu item (obsolete)	obsolete
<meta>	Metadata	current

Element	Meaning	Status today
<meter>	Scalar measurement (gauge)	current
<nav>	Navigation section	current
<noframes>	Fallback for frames (obsolete)	obsolete
<noscript>	Fallback when scripting is disabled	current
<object>	External object	current
	Ordered list	current
<optgroup>	Option group	current
<option>	Option	current
<output>	Calculation or user-action result	current
<p>	Paragraph	current
<param>	Object parameter (deprecated)	deprecated
<picture>	Picture (responsive image container)	current
<pre>	Pre-formatted text	current
<progress>	Progress indicator	current
<q>	Inline quotation	current
<rb>	Ruby base (deprecated)	deprecated
<rp>	Ruby fallback parenthesis	current

Element	Meaning	Status today
<rt>	Ruby text (annotation)	current
<rtc>	Ruby text container (deprecated)	deprecated
<ruby>	Ruby annotation	current
<s>	Strikethrough (no longer accurate)	current
<samp>	Sample output	current
<script>	Script	current
<section>	Generic section	current
<select>	Drop-down / list box	current
<slot>	Shadow DOM slot	current
<small>	Side comment (fine print)	current
<source>	Media or image source	current
	Generic inline container	current
<strike>	Strikethrough (obsolete)	obsolete
	Strong importance	current
<style>	Embedded style sheet	current
<sub>	Subscript	current
<summary>	Disclosure summary	current

Element	Meaning	Status today
<sup>	Superscript	current
<svg>	Scalable Vector Graphics root	current
<table>	Table	current
<tbody>	Table body	current
<td>	Table data cell	current
<template>	Content template	current
<textarea>	Multi-line text input	current
<tfoot>	Table footer	current
<th>	Table header cell	current
<thead>	Table header	current
<time>	Date / time	current
<title>	Document title	current
<tr>	Table row	current
<track>	Text track for media	current
<tt>	Teletype text (obsolete)	obsolete
<u>	Unarticulated annotation (underline)	current
	Unordered list	current
<var>	Variable	current
<video>	Embedded video	current
<wbr>	Word break opportunity	current

<a> — Anchor (hyperlink)

Status: CURRENT | Versions: HTML 1 (1991), HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <a> element (anchor) creates a hyperlink to another web page, a file, a location within the same page, an email address, a telephone number, or any other resource that can be identified by a URL. Hyperlinks are the defining feature of the World Wide Web and <a> was one of the very first elements created by Tim Berners-Lee in 1991.

```
<a href="URL">link text</a>
```

<abbr> — Abbreviation

Status: CURRENT | Versions: HTML 4.01, HTML5

The <abbr> element marks an abbreviation or acronym. The optional title attribute holds the full expansion, which most browsers show as a tooltip when the mouse hovers over the text.

```
<abbr title="expansion">ABBR</abbr>
```

<acronym> — Acronym (obsolete)

Status: OBSOLETE | Versions: HTML 4.01; obsolete in HTML5

The <acronym> element marked an acronym: an abbreviation pronounced as a word, such as NASA or laser. HTML5 removed it because the distinction from <abbr> was confusing and browsers treated the two identically.

```
<acronym title="expansion">NASA</acronym>
```

<address> — Contact address

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <address> element indicates that its content provides contact information for a person, people or an organisation. When placed inside an <article> it gives the contact details of the article's author; when placed in the page <footer> or <body> it gives the contact details for the whole document.

```
<address>contact information</address>
```

<applet> — Java applet (obsolete)

Status: OBSOLETE | Versions: HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

The <applet> element embedded a Java applet in the page. Applets were small Java programs that ran inside the browser with the help of a plug-in. Java applets were popular in the late 1990s but were slow, insecure and not supported on mobile devices. HTML 4.01 deprecated <applet> in favour of <object>, and HTML5 removed it entirely. No modern browser runs applets.

```
<applet code="MyApplet.class" width="300" height="200"></applet>
```

<area> — Image map area

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <area> element defines a clickable region inside an image map. An image map is an image (<img usemap="#name">) linked to a <map name="name"> element that contains one or more <area> elements. Each area has a shape and coordinates, and behaves like a hyperlink.

```
<area shape="rect" coords="x1,y1,x2,y2" href="URL" alt="text">
```

<article> — Self-contained article

Status: CURRENT | Versions: HTML5

The <article> element represents a complete, self-contained piece of content that would make sense on its own if it were distributed independently, for example in an RSS feed. Typical uses are a blog post, a news story, a forum post, a product card, a user comment or an interactive widget.

```
<article>...</article>
```

<aside> — Aside (sidebar / tangential content)

Status: CURRENT | Versions: HTML5

The <aside> element represents content that is only indirectly related to the main content around it. It is often displayed as a sidebar or a call-out box: pull quotes, related links, advertising, author biographies, glossary definitions, or a list of other articles.

```
<aside>...</aside>
```

<audio> — Embedded audio

Status: CURRENT | Versions: HTML5

The <audio> element embeds sound content: music, podcasts, sound effects or recorded speech. The source may be given with the src attribute or with one or more <source> child elements so that the browser can choose a format it supports. Content placed inside the element after the <source> elements is shown only by browsers that do not support <audio> at all.

```
<audio src="file.mp3" controls></audio>
```

<b> — Bring attention to (bold)

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <b> element draws the reader's attention to a span of text without giving it extra importance, emphasis or an alternative voice. Browsers render it in bold. Typical uses are keywords in a summary, product names in a review, or the lead sentence of an article.

```
<b>text</b>
```

<base> — Document base URL

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <base> element specifies the base URL used to resolve all relative URLs in the document, and/or the default target for all links and forms. There may be only one <base> element per document and it must be placed in <head>, before any element that uses a URL.

```
<base href="URL" target="_blank">
```

<basefont> — Base font (obsolete)

Status: OBSOLETE | Versions: HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

The <basefont> element set the default font size, colour and face for the whole document. It was a presentational element from HTML 3.2 and was deprecated in HTML 4.01 in favour of CSS. HTML5 removed it. Use CSS on the body element instead.

```
<basefont size="3" color="black" face="Arial">
```

<bdi> — Bidirectional isolate

Status: CURRENT | Versions: HTML5

The <bdi> element isolates a span of text that might be written in a different direction from the text around it, so that its direction does not affect the surrounding text. It is essential when you insert user-generated text of unknown direction, such as user names, into a sentence.

```
<bdi>text of unknown direction</bdi>
```

<bdo> — Bidirectional text override

Status: CURRENT | Versions: HTML 4.01, HTML5

The <bdo> element overrides the current text direction and forces its content to be displayed in the direction given by the dir attribute, character by character, ignoring the Unicode bidirectional algorithm. The dir attribute is required.

```
<bdo dir="rtl">text</bdo>
```

<big> — Bigger text (obsolete)

Status: OBSOLETE | Versions: HTML 3.2, HTML 4.01; obsolete in HTML5

The <big> element rendered its content one font size larger than the surrounding text. It was purely presentational and was removed in HTML5. Its counterpart <small> survived because it was given a new meaning (side comments and fine print). Use CSS font-size instead of <big>.

```
<big>text</big>
```

<blockquote> — Block quotation

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <blockquote> element indicates that the enclosed text is an extended quotation from another source. Browsers indent it on both sides by default. The optional cite attribute holds the URL of the source; a visible citation should be given with the <cite> element, usually in a <footer> inside the blockquote or in a following paragraph.

```
<blockquote cite="URL">quoted text</blockquote>
```

<body> — Document body

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <body> element contains all the content of the document that is displayed to the visitor: text, images, links, forms, media, and the scripts that operate on them. There is exactly one <body> in a document and it is the second child of <html>, after <head>.

```
<body>...</body>
```


 — Line break

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <br> element produces a line break in text: the text after it starts on a new line. It is a void element with no closing tag. Use it only where the division of lines is part of the content, as in a postal address or a poem.

```
<br>
```

<button> — Button

Status: CURRENT | Versions: HTML 4.01, HTML5

The <button> element represents a clickable button that the user can activate with a mouse, keyboard, finger or voice to perform an action. Unlike <input type="button">, a <button> may contain rich content: text, images, icons and other phrasing content.

```
<button type="button">label</button>
```

<canvas> — Graphics canvas

Status: CURRENT | Versions: HTML5

The <canvas> element provides a blank, resolution-dependent bitmap surface on which JavaScript can draw graphics: shapes, text, images, animations, charts, games and image processing. The element itself does nothing; all drawing is done through the 2D context (getContext('2d')) or a WebGL / WebGPU context.

```
<canvas id="c" width="400" height="300">fallback</canvas>
```

<caption> — Table caption

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <caption> element gives a table a title or explanation. It must be the first child of the <table> element, and a table may have only one. By default it is displayed centred above the table; the CSS caption-side property can move it below.

```
<table>
  <caption>Title</caption>
  ...
</table>
```

— Centred block (obsolete)

Status: OBSOLETE | Versions: HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

The element horizontally centred its content. It was introduced by Netscape, standardised in HTML 3.2, deprecated in HTML 4.01 and removed in HTML5. It is equivalent to . Use CSS instead: text-align: center for inline content, or margin: 0 auto with a width for blocks.

```
<center>content</center>
```

<cite> — Citation (title of a work)

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <cite> element marks the title of a creative work that is being referenced: a book, article, film, song, painting, play, poem, website, legal case, computer program, and so on. Browsers render it in italics.

```
<cite>Title of Work</cite>
```

<code> — Inline code

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <code> element marks a fragment of computer code: an element name, a file name, a variable, a function, a command, or any other string a computer would recognise. Browsers render it in a monospace font.

```
<code>snippet</code>
```

<col> — Table column

Status: CURRENT | Versions: HTML 4.01, HTML5

The <col> element defines one or more columns in a table so that attributes and styles can be applied to whole columns at once. It is a void element and lives inside a <colgroup>. The span attribute makes one <col> stand for several consecutive columns.

```
<colgroup>
  <col span="2" style="background: #eee">
</colgroup>
```

<colgroup> — Table column group

Status: CURRENT | Versions: HTML 4.01, HTML5

The <colgroup> element groups one or more columns of a table for the purpose of styling and structure. It is placed inside <table> after the optional <caption> and before any <thead>, <tbody>, <tfoot> or <tr>. It either has a span attribute (and no children) or contains <col> elements.

```
<colgroup span="2"></colgroup>
<!-- or -->
<colgroup><col><col></colgroup>
```

<data> — Machine-readable value

Status: CURRENT | Versions: HTML5

The <data> element links a piece of human-readable content with a machine-readable version of the same value held in the required value attribute. It is useful for product codes, numeric values written in words, sorting keys and similar cases where a script or search engine needs the exact value while the visitor sees a friendly form.

```
<data value="machine value">human text</data>
```

<datalist> — Predefined options for an input

Status: CURRENT | Versions: HTML5

The <datalist> element contains a set of <option> elements that represent suggested values for an <input>. The input is linked to the list with its list attribute, which must equal the datalist's id. The user can pick a suggestion or type any other value, which makes it a combination of a text box and a drop-down list (a 'combobox').

```
<input list="id">
<datalist id="id">
  <option value="...">
</datalist>
```

<dd> — Description details

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <dd> element provides the description, definition or value for the preceding term (<dt>) in a description list (<dl>). One term may have several <dd> elements, and several terms may share one <dd>. Browsers indent <dd> from the left by default.

```
<dl>
  <dt>Term</dt>
  <dd>Description</dd>
</dl>
```

<del> — Deleted text

Status: CURRENT | Versions: HTML 4.01, HTML5

The <del> element marks text that has been deleted from a document, typically to show changes between versions ('track changes'). Browsers render it with a line through it. It is usually paired with <ins>, which marks inserted text.

```
<del datetime="YYYY-MM-DD" cite="URL">deleted text</del>
```

<details> — Disclosure widget

Status: CURRENT | Versions: HTML5 (5.1)

The <details> element creates a disclosure widget: a box that can be opened and closed by the user to show or hide its content, with no JavaScript at all. The first child should be a <summary> element, which provides the always-visible label and the clickable arrow. If there is no <summary> the browser shows the word 'Details'.

```
<details>
  <summary>Label</summary>
  content
</details>
```

<dfn> — Definition term

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <dfn> element marks the term that is being defined in the surrounding sentence or paragraph. The nearest paragraph, description list group or section is the definition. Browsers render it in italics. If the element has a title attribute, that is the term being defined; if it contains an <abbr> with a title, the abbreviation's expansion is the term; otherwise the text content is the term.

```
<dfn>term</dfn>
```

<dialog> — Dialog box

Status: CURRENT | Versions: HTML 5.2 / Living Standard

The <dialog> element represents a dialog box or other interactive component such as a confirmation prompt, an alert, a subwindow or a modal overlay. It is hidden by default and is shown with the open attribute or, preferably, with the JavaScript methods show() (non-modal) and showModal() (modal). A modal dialog blocks interaction with the rest of the page, is displayed on top of everything else, and can be closed with the Escape key.

```
<dialog id="d">...</dialog>
<script>document.getElementById('d').showModal()</script>
```

<dir> — Directory list (obsolete)

Status: OBSOLETE | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

The <dir> element was a list of short items, intended to be shown in columns like a file directory listing. Browsers never implemented the columns and rendered it like <ul>. It was deprecated in HTML 4.01 and removed in HTML5. Use <ul> instead.

```
<dir><li>item</li></dir>
```

— Generic block container

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The element (division) is a generic container for flow content. It has no meaning of its own and no effect on the content or layout until it is styled with CSS (using class or id) or manipulated with JavaScript. Use it to group elements for styling purposes, for layout (flexbox, grid), or when no other element is more appropriate.

```
<div class="name">...</div>
```

<dl> — Description list

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <dl> element represents a description list: a list of groups of terms (<dt>) and their descriptions (<dd>). Common uses are glossaries, dictionaries, metadata displays (key: value pairs), FAQ lists and product specifications.

```
<dl>
  <dt>Term</dt>
  <dd>Description</dd>
</dl>
```

<dt> — Description term

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <dt> element specifies a term, name or key in a description list (<dl>). It is followed by one or more <dd> elements that describe it. Several <dt> elements in a row share the following <dd>. A <dt> may not contain headings, sections, headers or footers.

```
<dt>Term</dt>
```

— Emphasis

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The element marks text that has stress emphasis: the word or phrase you would say more forcefully if you were reading the sentence aloud. Changing which word is emphasised changes the meaning of the sentence. Browsers render it in italics.

```
<em>text</em>
```

<embed> — External content

Status: CURRENT | Versions: Netscape extension (1995), standardised in HTML5

The <embed> element embeds external content at a specified point in the document. The content is provided by an external application or plug-in, or is a natively supported type such as an image, video, PDF or HTML page. It is a void element with no fallback content.

```
<embed src="file.pdf" type="application/pdf" width="600" height="400">
```

<fieldset> — Form field group

Status: CURRENT | Versions: HTML 4.01, HTML5

The <fieldset> element groups related controls and labels inside a form, for example all the fields of a postal address, or a set of radio buttons that answer one question. The optional <legend> element, which must be the first child, gives the group a caption. Browsers draw a border around the group with the legend placed on the border.

```
<fieldset>
  <legend>Caption</legend>
  ...controls...
</fieldset>
```

<figcaption> — Figure caption

Status: CURRENT | Versions: HTML5

The <figcaption> element provides a caption or legend for the content of its parent <figure> element. It must be either the first or the last child of the <figure>. The caption is programmatically associated with the figure, which gives the figure an accessible name.

```
<figure>
  <img ...>
  <figcaption>Caption</figcaption>
</figure>
```

<figure> — Figure with optional caption

Status: CURRENT | Versions: HTML5

The <figure> element represents self-contained content that is referenced from the main flow but could be moved elsewhere (to an appendix, a sidebar or another page) without affecting the meaning of the text: an illustration, a diagram, a photo, a code listing, a chart, a poem, a table. An optional <figcaption> gives it a caption.

```
<figure>
  content
  <figcaption>Caption</figcaption>
</figure>
```

<font> — Font (obsolete)

Status: OBSOLETE | Versions: HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

The <font> element set the size, colour and typeface of its text. It was the main way to style text before CSS, was deprecated in HTML 4.01 and removed in HTML5. Browsers still render it for old pages. Every use of <font> can be replaced by CSS: font-size, color and font-family.

```
<font size="4" color="red" face="Arial">text</font>
```

<footer> — Footer

Status: CURRENT | Versions: HTML5

The <footer> element represents the footer of its nearest ancestor sectioning content or sectioning root: the page (<body>), an <article>, a <section>, an <aside> or a <nav>. A footer typically contains information about the section it belongs to: who wrote it, copyright data, links to related documents, contact details, a site map, or navigation back to the top.

```
<footer>...</footer>
```

<form> — Form

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <form> element represents a section of the document containing interactive controls (text boxes, check boxes, radio buttons, drop-down lists, buttons and so on) for collecting information from the user and sending it to a server. When the form is submitted, the browser gathers the name and value of every control that has a name, encodes them, and sends them to the URL in the action attribute using the HTTP method in the method attribute.

```
<form action="URL" method="post">
  ...controls...
  <button>Submit</button>
</form>
```

<frame> — Frame (obsolete)

Status: OBSOLETE | Versions: Netscape 2 (1996), HTML 4.01 Frameset; obsolete in HTML5

The <frame> element defined one rectangular sub-window inside a <frameset>, each displaying a separate HTML document. Frames were used in the late 1990s to keep a navigation menu fixed while the content scrolled. They caused many problems: bookmarks and the back button did not work as expected, search engines could not index the pages properly, printing was unreliable and screen readers struggled. HTML5 removed <frame> and <frameset>. Use CSS for layout and <iframe> when you truly need to embed another document.

```
<frameset cols="200,*">
  <frame src="menu.html" name="menu">
  <frame src="main.html" name="main">
</frameset>
```

<frameset> — Frameset (obsolete)

Status: OBSOLETE | Versions: Netscape 2, HTML 4.01 Frameset; obsolete in HTML5

The <frameset> element replaced <body> in a frames document and divided the window into rows and columns, each filled by a <frame> or a nested <frameset>. It required the HTML 4.01 Frameset DOCTYPE. It is obsolete in HTML5. See <frame> for the reasons and the modern replacement.

```
<frameset rows="80,*">...</frameset>
```

<h1> — Headings h1 to h6

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <h1> to <h6> elements represent six levels of section headings. <h1> is the highest (most important) level and <h6> the lowest. Headings describe the topic of the section that follows them, and together they form the outline of the document, like the table of contents of a book.

```
<h1>Main title</h1>
<h2>Section</h2>
<h3>Sub-section</h3>
```

<head> — Document head

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <head> element contains machine-readable information (metadata) about the document: its title, character encoding, links to style sheets and icons, scripts, and <meta> tags for search engines and social networks. Nothing inside <head> is displayed on the page itself, except the title, which appears in the browser tab.

```
<head>
  <meta charset="utf-8">
  <title>Title</title>
</head>
```

<header> — Header

Status: CURRENT | Versions: HTML5

The <header> element represents introductory content for its nearest sectioning ancestor or for the page: typically a group of headings, a logo, a search form, the author's name, and the main navigation. A page usually has one header at the top of <body>, but articles and sections may have their own headers too.

```
<header>...</header>
```

<hgroup> — Heading group

Status: CURRENT | Versions: HTML5 (removed from W3C HTML 5.0, kept in the Living Standard with a new definition)

The <hgroup> element groups a heading (<h1>-<h6>) with one or more <p> elements that contain a subtitle, alternative title, tagline or other secondary text. It tells the browser that the paragraphs belong to the heading rather than being ordinary content.

```
<hgroup>
  <h1>Title</h1>
  <p>Subtitle</p>
</hgroup>
```

<hr> — Thematic break (horizontal rule)

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <hr> element represents a thematic break between paragraph-level content: a change of scene in a story, a shift of topic within a section, or a separator between groups of options in a menu. Browsers render it as a horizontal line, which is where its name (horizontal rule) comes from.

```
<hr>
```

<html> — Document root

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <html> element is the root element of an HTML document: every other element is a descendant of it. It has exactly two children: <head> followed by <body>. It comes immediately after the <!DOCTYPE html> declaration.

```
<!DOCTYPE html>
<html lang="en">
  <head>...</head>
  <body>...</body>
</html>
```

<i> — Idiomatic text (italic)

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <i> element marks a span of text that is set off from the normal prose for some reason other than emphasis or importance: an alternative voice or mood, a technical term, a taxonomic name (Homo sapiens), a phrase in another language, a thought, a ship's name, or a transliteration. Browsers render it in italics.

```
<i>text</i>
```

<iframe> — Inline frame

Status: CURRENT | Versions: Internet Explorer 3 (1996), HTML 4.01, HTML5

The <iframe> element embeds another HTML page inside the current page, in a rectangular area called a nested browsing context. Each iframe has its own document, its own window object and its own history. Common uses are embedding videos from YouTube, maps, advertisements, payment forms, social media widgets and third-party tools.

```
<iframe src="URL" title="description" width="600" height="400"></
iframe>
```

<img> — Image

Status: CURRENT | Versions: Mosaic (1993), HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <img> element embeds an image in the document. It is a void element; the image file is identified by the src attribute and is loaded separately. Supported formats include JPEG, PNG, GIF, WebP, AVIF, SVG, APNG, BMP and ICO. The alt attribute holds a text alternative that is displayed if the image cannot load and is read aloud by screen readers; it is required for accessibility.

```
<img src="URL" alt="description" width="W" height="H">
```

<input> — Input control

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <input> element creates an interactive control for accepting data from the user. It is the most versatile element in HTML: the type attribute selects one of more than twenty different controls, from a plain text box to a colour picker, a file chooser, a range slider or a hidden field. It is a void element.

```
<input type="text" name="field" id="field">
```

<ins> — Inserted text

Status: CURRENT | Versions: HTML 4.01, HTML5

The <ins> element marks text that has been added to a document, to show changes between versions. Browsers underline it by default. It is the counterpart of <del>. Like <del> it accepts optional cite and datetime attributes that record why and when the change was made.

```
<ins datetime="YYYY-MM-DD">inserted text</ins>
```

<isindex> — Search index prompt (obsolete)

Status: OBSOLETE | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

The <isindex> element, one of the original 1991 elements, told the browser that the document was a searchable index and made it display a single-line text field with a prompt. Submitting the field reloaded the page with ?keywords in the URL. It was made redundant by forms in HTML 2.0, deprecated in HTML 4.01 and removed in HTML5. Use a <form> with an <input type="search">.

```
<isindex prompt="Search: ">
```

<kbd> — Keyboard input

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <kbd> element marks text that represents user input from a keyboard, voice command, or other input device. Browsers render it in a monospace font. Nesting <kbd> elements inside a <kbd> represents individual keys in a key combination; wrapping <kbd> in <samp> represents input echoed by the system.

```
<kbd>Ctrl</kbd> + <kbd>S</kbd>
```

<keygen> — Key-pair generator (obsolete)

Status: OBSOLETE | Versions: Netscape, briefly in HTML5; removed

The <keygen> element generated a public/private key pair when a form was submitted, for client certificate enrolment. It came from Netscape, was added to HTML5 and then removed from the standard in 2017 and from all browsers. There is no direct replacement; use the Web Crypto API.

```
<keygen name="key" challenge="...">
```

<label> — Form control label

Status: CURRENT | Versions: HTML 4.01, HTML5

The <label> element gives a caption to a form control. Associating a label with a control has two big benefits: clicking the label focuses or toggles the control (a much larger click target for checkboxes and radio buttons), and screen readers announce the label when the control gets focus.

```
<label for="id">Text</label> <input id="id">
<!-- or -->
<label>Text <input></label>
```

<legend> — Fieldset caption

Status: CURRENT | Versions: HTML 4.01, HTML5

The <legend> element provides a caption for its parent <fieldset>. It must be the first child of the fieldset. Browsers draw it on top of the fieldset's border. Screen readers announce the legend together with the label of each control inside the group, which is why fieldset/legend is the recommended way to caption groups of radio buttons or checkboxes.

```
<fieldset>
  <legend>Caption</legend>
  ...
</fieldset>
```

 — List item

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <li> element represents one item in a list. It must be contained in an ordered list (<ol>), an unordered list (<ul>) or a menu (<menu>). In ordered lists the value attribute sets the number of the item, and subsequent items continue counting from it.

```
<ul>
  <li>Item</li>
</ul>
```

<link> — External resource link

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <link> element specifies a relationship between the current document and an external resource. By far its most common use is loading a CSS style sheet (rel="stylesheet"), but it is also used for site icons (rel="icon"), web app manifests, preloading and prefetching resources, canonical URLs for search engines, alternate language versions, RSS feeds and more. It is a void element and normally lives in <head>, though body-ok link types such as stylesheet may appear in <body>.

```
<link rel="stylesheet" href="style.css">
```

<main> — Main content

Status: CURRENT | Versions: HTML 5.1 (2016)

The <main> element represents the dominant content of the <body>: the content that is directly related to, or expands upon, the central topic of the page or the central function of the application. It excludes content repeated across pages such as the site header, navigation, sidebars, search box, logo and footer.

```
<main>...</main>
```

<map> — Image map

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <map> element, together with <area> elements, defines a client-side image map: an image with several clickable regions each linking to a different destination. The map is connected to an <img> through the img's usemap attribute, which must be # followed by the map's name.

```
<map name="n">
  <area ...>
</map>
<img usemap="#n" ...>
```

<mark> — Highlighted (marked) text

Status: CURRENT | Versions: HTML5

The <mark> element represents text that is marked or highlighted for reference because of its relevance in the current context. Typical uses: highlighting the search terms in a page of results, or drawing attention to a passage in a quotation that the current text discusses. Browsers render it with a yellow background, like a highlighter pen.

```
<mark>text</mark>
```

<marquee> — Scrolling text (obsolete)

Status: OBSOLETE | Versions: Internet Explorer 2 (1995), never standard; obsolete in HTML5 (but its behaviour is specified for compatibility)

The <marquee> element scrolled its content horizontally or vertically across the screen. It was a Microsoft extension that became infamous alongside Netscape's <blink>. HTML5 lists it as obsolete but, because so many old pages use it, browsers still implement it. Moving text is hard to read and distracting; if you need an animation, use CSS animations with a pause control and respect the prefers-reduced-motion media query.

```
<marquee>text</marquee>
```

<math> — MathML root

Status: CURRENT | Versions: HTML5 (inline MathML)

The <math> element is the top-level element of MathML (Mathematical Markup Language), which can be written directly inside HTML5 documents to display mathematical formulas. Inside <math> you use MathML elements such as <mi> (identifier), <mn> (number), <mo> (operator), <mrow> (group), <mfrac> (fraction), <msup> (superscript), <msqrt> (square root) and <mtable>. All modern browsers support MathML Core.

```
<math>
  <mi>x</mi><mo>=</mo><mn>2</mn>
</math>
```

<menu> — Menu (toolbar list)

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01 (deprecated), HTML5 (redefined)

The <menu> element is a semantic alternative to <ul> for a list of commands or actions, such as a toolbar of buttons. Each command is an <li> containing a <button> or similar control. Browsers render it identically to <ul>.

```
<menu>
  <li><button>Action</button></li>
</menu>
```

<menuitem> — Menu item (obsolete)

Status: OBSOLETE | Versions: HTML5 draft (Firefox only); removed 2017

The <menuitem> element represented a command in a <menu type="context">, letting a page add custom items to the browser's right-click menu. Only Firefox implemented it; it was removed from the standard in 2017 and from Firefox in 2020. Build custom menus with lists, buttons and JavaScript (or the popover attribute) instead.

```
<menuitem label="Refresh" onclick="...">
```

<meta> — Metadata

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <meta> element represents metadata about the document that cannot be expressed by <title>, <base>, <link>, <style> or <script>. It is a void element placed in <head>. Depending on which attributes are present it does one of four things: declares the character encoding (charset); provides document-level metadata as a name/content pair (name); simulates an HTTP response header (http-equiv); or supplies microdata (itemprop).

```
<meta charset="utf-8">
<meta name="description" content="...">
```

<meter> — Scalar measurement (gauge)

Status: CURRENT | Versions: HTML5

The <meter> element represents a scalar measurement within a known range, or a fractional value: disk usage, the relevance of a search result, password strength, a score out of ten, temperature within safe limits. Browsers render it as a gauge bar whose colour changes depending on whether the value is in the optimum, suboptimal or bad region defined by low, high and optimum.

```
<meter value="0.6">60%</meter>
```

<nav> — Navigation section

Status: CURRENT | Versions: HTML5

The <nav> element represents a section of the page whose purpose is to provide navigation links, either within the current document or to other documents. Typical uses are the main site menu, a table of contents, breadcrumbs, pagination and 'previous/next' links.

```
<nav>
  <ul>
    <li><a href="...">Link</a></li>
  </ul>
</nav>
```

<noframes> — Fallback for frames (obsolete)

Status: OBSOLETE | Versions: HTML 4.01 Frameset; obsolete in HTML5

The <noframes> element contained content to display in browsers that did not support frames. It became obsolete together with <frameset> and <frame> in HTML5.

```
<noframes><body>fallback</body></noframes>
```

<noscript> — Fallback when scripting is disabled

Status: CURRENT | Versions: HTML 4.01, HTML5

The <noscript> element defines content to be shown only if scripting is disabled in the browser or the browser does not support scripting. When scripting is enabled the content is ignored entirely (in fact the parser treats it as raw text). It may be used in <head> (containing only <link>, <style> and <meta>) and in <body>.

```
<noscript>fallback content</noscript>
```

<object> — External object

Status: CURRENT | Versions: HTML 4.01, HTML5

The <object> element represents an external resource, treated as an image, a nested browsing context (like an iframe) or a resource handled by a plug-in, depending on its type. It was introduced in HTML 4.01 as a universal replacement for <img>, <applet> and <embed>. Unlike <embed>, it accepts fallback content between its tags, shown if the resource cannot be displayed, and it may contain <param> elements (now obsolete) that pass parameters to plug-ins.

```
<object data="URL" type="MIME" width="W" height="H">fallback</object>
```

 — Ordered list

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <ol> element represents an ordered list of items: a list where the order matters, such as the steps of a recipe, the ranking of a competition, or the chapters of a book. Browsers number the items automatically. Each item is an <li>. If the order is not meaningful, use <ul> instead.

```
<ol>
  <li>First</li>
  <li>Second</li>
</ol>
```

<optgroup> — Option group

Status: CURRENT | Versions: HTML 4.01, HTML5

The <optgroup> element groups related <option> elements inside a <select> under a non-selectable heading given by the label attribute. Groups cannot be nested. Disabling an optgroup disables all its options.

```
<select>
  <optgroup label="Group">
    <option>...</option>
  </optgroup>
</select>
```

<option> — Option

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <option> element defines one item in a <select> drop-down list, an <optgroup>, or a <datalist> of suggestions. Its text content is what the user sees; the value attribute is what is submitted with the form. If value is omitted the text content is submitted instead.

```
<option value="v">Text</option>
```

<output> — Calculation or user-action result

Status: CURRENT | Versions: HTML5

The <output> element is a container into which a site or app can inject the result of a calculation or the outcome of a user action, for example the total price in a cart, the current value of a range slider, or a status message. It is form-associated and labelable, and it is an ARIA live region by default (role="status"), which means screen readers announce changes to its content automatically.

```
<output name="result" for="a b">0</output>
```

<p> — Paragraph

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <p> element represents a paragraph: a block of related text, usually a group of sentences on one topic. Browsers display paragraphs as blocks separated by vertical space (a margin of 1em above and below). Paragraphs are one of the most used elements in HTML and one of the original elements from 1991, where <p> was a separator between paragraphs rather than a container.

```
<p>Text of the paragraph.</p>
```

<param> — Object parameter (deprecated)

Status: DEPRECATED | Versions: HTML 3.2, HTML 4.01, HTML5; deprecated in the Living Standard

The <param> element defined a parameter for an <object> element, passing a name/value pair to the plug-in that displayed the object (for example the autoplay setting of a Flash movie). Since plug-ins no longer exist, the element serves no purpose; the Living Standard marks it deprecated and it is retained only for compatibility. It is a void element.

```
<object data="movie.swf">
  <param name="quality" value="high">
</object>
```

<picture> — Picture (responsive image container)

Status: CURRENT | Versions: HTML 5.1 (2016)

The <picture> element contains zero or more <source> elements and exactly one <img> element, and lets the browser choose the most suitable image from several candidates. The browser examines each <source> in order and uses the first whose media query matches and whose type it supports; if none match it falls back to the <img>. The <img> element is required: it is what is actually displayed, and it carries the alt text, width, height, loading and other attributes.

```
<picture>
  <source srcset="..." media="..." type="...">
  <img src="..." alt="...">
</picture>
```

<pre> — Pre-formatted text

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <pre> element represents pre-formatted text that is displayed exactly as written in the HTML file: every space, tab and line break is preserved, and a monospace (fixed-width) font is used. It is the standard way to show source code, ASCII art, poetry with meaningful spacing, email messages and terminal output.

```
<pre>
  text with
    preserved   spacing
</pre>
```

<progress> — Progress indicator

Status: CURRENT | Versions: HTML5

The <progress> element displays the completion progress of a task, such as a file upload, a download, a multi-step form or a loading operation. It is rendered as a progress bar. With a value attribute it shows a determinate bar (a known percentage); without value it shows an indeterminate, animated bar meaning 'working, but I do not know how long it will take'.

```
<progress value="30" max="100">30%</progress>
```

<q> — Inline quotation

Status: CURRENT | Versions: HTML 4.01, HTML5

The <q> element indicates a short inline quotation that sits within a sentence. Browsers automatically add quotation marks around it, choosing the correct style for the language declared with lang (curly double quotes in English, guillemets in French, and so on), so you should not type quotation marks yourself. For long quotations that need their own paragraph use <blockquote>.

```
<q cite="URL">quoted words</q>
```

<rb> — Ruby base (deprecated)

Status: DEPRECATED | Versions: XHTML 1.1 Ruby, HTML 5.1; removed from the Living Standard

The <rb> element explicitly marked the base text component of a ruby annotation, the text that the <rt> annotation is placed above. The Living Standard removed it because the base text can simply be written directly inside <ruby>. Browsers still support it.

```
<ruby><rb>□</rb><rt>kan</rt></ruby>
```

<rp> — Ruby fallback parenthesis

Status: CURRENT | Versions: HTML5

The <rp> element provides fallback parentheses for browsers that do not support ruby annotations. Browsers that support ruby hide the <rp> content; older browsers display it, so the annotation appears in brackets after the base text instead of above it. Place one <rp> before and one after each <rt>.

```
<ruby>□<rp>(</rp><rt>kan</rt><rp>)</rp></ruby>
```

<rt> — Ruby text (annotation)

Status: CURRENT | Versions: HTML5

The <rt> element specifies the ruby text component of a ruby annotation: the small text placed above (or beside) the base characters to show pronunciation, translation or transliteration. It is used for East Asian typography (furigana in Japanese, pinyin/zhuyin in Chinese) and increasingly for other languages. It must be inside a <ruby> element.

```
<ruby>base<rt>annotation</rt></ruby>
```

<rtc> — Ruby text container (deprecated)

Status: DEPRECATED | Versions: HTML 5.1; removed from the Living Standard

The <rtc> element grouped several <rt> annotations so that a base text could have two layers of annotation (for example pronunciation above and meaning below). Only Firefox implemented it, and the Living Standard removed it. Nest two <ruby> elements for double-sided annotations.

```
<ruby>base<rtc><rt>a</rt></rtc><rtc><rt>b</rt></rtc></ruby>
```

<ruby> — Ruby annotation

Status: CURRENT | Versions: XHTML 1.1 (2001), HTML5

The <ruby> element represents small annotations rendered above, below or beside base text, most often used to show the pronunciation of East Asian characters. The name comes from a small typographic size called 'ruby' used by British printers. The base text is written directly inside <ruby>, each annotation in an <rt>, and optional fallback parentheses in <rp>.

```
<ruby>base<rp>(</rp><rt>annotation</rt><rp>)</rp></ruby>
```

<s> — Strikethrough (no longer accurate)

Status: CURRENT | Versions: HTML 3.2, HTML 4.01 (deprecated), HTML5 (redefined)

The <s> element renders text with a line through it and represents content that is no longer accurate or no longer relevant, such as an old price next to the new one, or a sold-out item. In HTML 4 it was a purely presentational strike-through synonym for <strike> and was deprecated; HTML5 gave it this meaning and made it valid again while removing <strike>.

```
<s>outdated text</s>
```

<samp> — Sample output

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <samp> element marks sample or quoted output from a computer program or system: error messages, terminal output, log lines. Browsers render it in a monospace font. Nest <kbd> inside <samp> to show input echoed by the system, and <samp> inside <kbd> for input that names an on-screen item.

```
<samp>program output</samp>
```

<script> — Script

Status: CURRENT | Versions: HTML 3.2 (reserved), HTML 4.01, HTML5

The <script> element embeds executable code, almost always JavaScript, or links to an external script file with the src attribute. It can also hold data blocks (JSON, templates, import maps, speculation rules) that the browser does not execute when type is set to a non-script MIME type.

```
<script src="app.js" defer></script>
<script>
  // inline code
</script>
```

<section> — Generic section

Status: CURRENT | Versions: HTML5

The <section> element represents a generic, thematic grouping of content, typically with a heading. Examples: the chapters of an article, the tabs of a tabbed interface, the 'Introduction', 'Features' and 'Pricing' areas of a landing page. Each section should be identifiable, usually by an <h2>-<h6> heading as its first child.

```
<section>
  <h2>Heading</h2>
  ...
</section>
```

<select> — Drop-down / list box

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <select> element creates a control for choosing one option (or, with multiple, several) from a list. It contains <option> elements, optionally grouped in <optgroup>. By default it appears as a drop-down menu; with the multiple attribute or a size greater than 1 it appears as a scrolling list box. The name attribute and the value of the chosen option(s) are submitted with the form.

```
<select name="n">
  <option value="1">One</option>
</select>
```

<slot> — Shadow DOM slot

Status: CURRENT | Versions: HTML5 / DOM Standard (2016)

The <slot> element is a placeholder inside a web component's shadow tree that is filled with content from the light DOM (the markup written by the user of the component). A named slot receives children that have a matching slot attribute; the unnamed default slot receives all other children. Content inside the <slot> element itself is fallback content shown when nothing is slotted.

```
<slot name="title">Default title</slot>
```

<small> — Side comment (fine print)

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5 (redefined)

The <small> element represents side comments and small print: disclaimers, caveats, legal restrictions, copyright notices, attribution. It renders the text one size smaller. In HTML 3.2 and 4 it was purely presentational ('smaller text'); HTML5 kept it and gave it this meaning, while its counterpart <big> was removed.

```
<small>fine print</small>
```

<source> — Media or image source

Status: CURRENT | Versions: HTML5

The <source> element specifies one of several alternative resources for a <picture>, <audio> or <video> element. It is a void element. The browser examines the sources in order and uses the first one it can display: for <picture> it checks the media query and image type, for <audio>/<video> it checks the type (MIME type and codecs). Because it is used inside three different parents, the set of relevant attributes differs: <picture> uses srcset, sizes, media, type, width and height; media elements use src, type and (for video) media.

```
<source src="file" type="MIME">  <!-- in audio/video -->
<source srcset="file" type="MIME" media="query">  <!-- in picture -->
```

— Generic inline container

Status: CURRENT | Versions: HTML 4.01, HTML5

The element is a generic inline container for phrasing content. Like , it has no meaning of its own and no visual effect; it exists to be a hook for CSS (via class or id) or JavaScript, or to carry attributes such as lang or dir on a part of a sentence. It should be used only when no other element is more appropriate: , , <mark>, <time>, <abbr>, <code> and the other text-level elements all carry meaning that does not.

```
<span class="name">text</span>
```

<strike> — Strikethrough (obsolete)

Status: OBSOLETE | Versions: HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

The <strike> element drew a line through its text. It was purely presentational, was deprecated in HTML 4.01 and removed in HTML5. Use <del> for removed content, <s> for content that is no longer accurate, or CSS text-decoration: line-through for pure styling.

```
<strike>text</strike>
```

— Strong importance

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The element indicates that its content has strong importance, seriousness or urgency: a warning, a key instruction, the most important part of a sentence. Browsers render it in bold. Nesting inside increases the importance further.

```
<strong>important text</strong>
```

<style> — Embedded style sheet

Status: CURRENT | Versions: HTML 3.2 (reserved), HTML 4.01, HTML5

The <style> element contains CSS rules that apply to the document. It belongs in <head>, though browsers tolerate it in <body>. A document may have any number of <style> elements; they are applied in order together with any linked style sheets. For anything larger than a few rules, an external file loaded with <link rel="stylesheet"> is better because it can be cached and shared between pages.

```
<style>
  selector { property: value; }
</style>
```

<sub> — Subscript

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <sub> element renders text as a subscript: smaller and below the baseline. Use it only where the subscript has a typographic meaning, such as chemical formulas (H_2O), mathematical variable indices (x_1) or footnote markers in some styles. For purely visual lowering, use CSS vertical-align.

```
H<sub>2</sub>0
```

<summary> — Disclosure summary

Status: CURRENT | Versions: HTML5 (5.1)

The <summary> element specifies the visible heading, label or caption of a <details> element. Clicking it (or pressing Enter/Space when it is focused) toggles the details open and closed. It must be the first child of <details>. Browsers show a small triangle marker before it, which can be styled or removed with the ::marker pseudo-element or list-style: none.

```
<details>
  <summary>Label</summary>
  ...
</details>
```

<sup> — Superscript

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <sup> element renders text as a superscript: smaller and above the baseline. Use it where the superscript has meaning: exponents (x^2), ordinal suffixes (1st), footnote references, and abbreviations like Mlle. For visual raising only, use CSS.

```
x<sup>2</sup>
```

<svg> — Scalable Vector Graphics root

Status: CURRENT | Versions: HTML5 (inline SVG)

The <svg> element is the root of an inline SVG (Scalable Vector Graphics) image written directly in the HTML. SVG describes shapes with elements such as <circle>, <rect>, <line>, <path>, <text> and <g>, which scale to any size without losing sharpness, can be styled with CSS and animated with CSS or JavaScript. Inline SVG is ideal for icons, logos, charts and diagrams. SVG files can also be used through <img src="x.svg">, but then CSS from the page cannot style their insides.

```
<svg viewBox="0 0 100 100" width="100" height="100">
  <circle cx="50" cy="50" r="40"/>
</svg>
```

<table> — Table

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <table> element represents tabular data: information arranged in a two-dimensional grid of rows and columns, where the position of each cell gives it meaning (this value belongs to this row and this column). Examples: price lists, timetables, statistics, comparison charts, spreadsheets.

```
<table>
  <caption>Title</caption>
  <thead><tr><th>Head</th></tr></thead>
  <tbody><tr><td>Data</td></tr></tbody>
</table>
```

<tbody> — Table body

Status: CURRENT | Versions: HTML 4.01, HTML5

The <tbody> element groups the main data rows of a table, as distinct from the header rows in <thead> and the summary rows in <tfoot>. A table may have several <tbody> elements to group rows into sections (for example one per category), which can then be styled separately. When you write <tr> directly inside <table> without a <tbody>, the browser creates one automatically, so a tbody is always present in the DOM.

```
<tbody>
  <tr>...</tr>
</tbody>
```

<td> — Table data cell

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <td> element defines a cell of a table that contains data. It must be inside a <tr>. Each <td> occupies one column by default; colspan makes it span several columns and rowspan several rows. The headers attribute can list the ids of the <th> cells that describe it, which is needed only for complex tables where scope is not enough.

```
<tr>
  <td>Data</td>
</tr>
```

<template> — Content template

Status: CURRENT | Versions: HTML5 (2013)

The <template> element holds HTML that is not rendered when the page loads but can be cloned and inserted into the document later by JavaScript. The content is parsed into a separate document fragment (template.content): scripts inside do not run, images do not load and the markup is invisible. It is the standard way to define reusable markup for lists, cards and web components.

```
<template id="t">
  <li class="item"></li>
</template>
```

<textarea> — Multi-line text input

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <textarea> element creates a multi-line plain-text editing control, for comments, messages, addresses and any free-form text. Unlike <input>, it is not a void element: its initial value is the text between its tags, not a value attribute. Whitespace and line breaks inside the tags are preserved, so keep the closing tag right after the text to avoid unwanted spaces.

```
<textarea name="n" rows="4" cols="40">initial text</textarea>
```

<tfoot> — Table footer

Status: CURRENT | Versions: HTML 4.01, HTML5

The <tfoot> element groups the rows that summarise the columns of a table: totals, averages, counts. In HTML5 it is placed after the <tbody> elements (HTML 4.01 required it before them so that the browser could render the footer before receiving all data). When printing a long table, browsers can repeat the tfoot at the bottom of every page.

```
<tfoot>
  <tr><th>Total</th><td>260</td></tr>
</tfoot>
```

<th> — Table header cell

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <th> element defines a header cell in a table: a cell that labels a column or a row rather than holding data. Browsers render it bold and centred. The scope attribute states whether the header applies to its column (col), its row (row), a group of columns (colgroup) or a group of rows (rowgroup). Browsers can usually guess for simple tables, but stating it explicitly is best practice because screen readers use the header text when reading each data cell.

```
<th scope="col">Header</th>
```

<thead> — Table header

Status: CURRENT | Versions: HTML 4.01, HTML5

The <thead> element groups the rows that hold the column headers of a table. It comes after any <caption> and <colgroup> and before <tbody> and <tfoot>. Browsers repeat the thead at the top of each printed page of a long table, and CSS position: sticky on its cells keeps the headers visible while scrolling. A table may have at most one thead.

```
<thead>
  <tr><th>Column</th></tr>
</thead>
```

<time> — Date / time

Status: CURRENT | Versions: HTML5

The <time> element represents a specific period in time: a date, a time of day, a date and time, a duration, a week or a month. The optional datetime attribute holds the value in a machine-readable format so that browsers, search engines, calendars and scripts can understand it, while the visible content can be written in any human-friendly way ('11 September 2026', 'yesterday', '□□ □□□□□□'). If datetime is omitted, the text content itself must be in a valid format.

```
<time datetime="2026-09-11">11 September 2026</time>
```

<title> — Document title

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <title> element defines the title of the document, shown in the browser's title bar or tab, used as the default name for bookmarks, displayed as the clickable headline in search engine results, and announced first by screen readers when the page loads. It contains text only; any tags inside are treated as literal text. Every document must have exactly one <title>, inside <head>.

```
<title>Page title</title>
```

<tr> — Table row

Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

The <tr> element defines a row of cells in a table. It contains <th> (header) and/or <td> (data) cells and is placed inside <table>, <thead>, <tbody> or <tfoot>. Rows are the fundamental unit of table construction: you build a table one row at a time, and the columns emerge from the cells in each row.

```
<tr>
  <td>Cell 1</td>
  <td>Cell 2</td>
</tr>
```

<track> — Text track for media

Status: CURRENT | Versions: HTML5

The <track> element adds timed text tracks to <audio> or <video>: subtitles (translations), captions (dialogue plus sound descriptions for deaf and hard-of-hearing viewers), descriptions (spoken description of the video for blind users), chapters (navigation) and metadata (for scripts). Tracks are WebVTT files (.vtt). It is a void element placed after any <source> elements.

```
<track kind="captions" src="captions.vtt" srclang="en"
label="English" default>
```

<tt> — Teletype text (obsolete)

Status: OBSOLETE | Versions: HTML 2.0, HTML 3.2, HTML 4.01; obsolete in HTML5

The <tt> element (teletype) rendered text in a monospace font, imitating a teletype or typewriter. It was purely presentational and HTML5 removed it. Use the semantic elements <code>, <kbd>, <samp> or <var>, or CSS font-family: monospace on a .

```
<tt>text</tt>
```

<u> — Unarticulated annotation (underline)

Status: CURRENT | Versions: HTML 3.2, HTML 4.01 (deprecated), HTML5 (redefined)

The <u> element represents a span of inline text that should be rendered in a way that indicates a non-textual annotation: most commonly, marking misspelled words (as a word processor does with a wavy red line) or labelling proper names in Chinese text. Browsers render it with a solid underline. In HTML 4 <u> simply meant 'underline' and was deprecated; HTML5 redefined it.

```
<u>text</u>
```

 — Unordered list

Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <ul> element represents an unordered list of items: a list where changing the order would not change the meaning, such as a shopping list, a set of features, or the links of a navigation menu. Browsers show each item with a bullet. Each item is an <li>. If the order matters, use <ol>.

```
<ul>
  <li>Item</li>
  <li>Item</li>
</ul>
```

<var> — Variable

Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

The <var> element represents the name of a variable in a mathematical expression or a programming context, or a placeholder for a value the reader must supply. Browsers render it in italics. It is one of the four 'computer' phrase elements together with <code>, <kbd> and <samp>.

```
<var>x</var>
```

<video> — Embedded video

Status: CURRENT | Versions: HTML5

The <video> element embeds a video player in the document. The video file is given by src or by one or more <source> children (so that the browser can pick a supported format), followed by optional <track> elements for captions and subtitles, and finally fallback content for browsers without video support. Common formats are MP4 (H.264/AAC, universally supported), WebM (VP9/AV1, smaller) and, in Safari, HEVC.

```
<video src="clip.mp4" controls width="640" height="360"></video>
```

<wbr> — Word break opportunity

Status: CURRENT | Versions: Netscape / IE extension, standardised in HTML5

The <wbr> element marks a position inside a word where the browser may break the line if necessary, without inserting a hyphen or a visible character. It is useful for very long words, URLs and code identifiers that would otherwise overflow their container. If no break is needed, nothing is displayed. It is a void element.

```
Super<wbr>cali<wbr>fragilistic
```

The HTML Living Standard (2014-today)

Since 2019 the WHATWG Living Standard is the single HTML specification; there will be no 'HTML6'. Features are added continuously once two browser engines ship them: <dialog>, <template>, <slot>, <picture>, <search>, the popover attribute, lazy loading, customisable select and more.

Elements in this chapter: 13

Element	Meaning	Status today
<dialog>	Dialog box	current
<fencedframe>	Fenced frame (experimental)	experimental
<hgroup>	Heading group	current
<main>	Main content	current
<menuitem>	Menu item (obsolete)	obsolete
<param>	Object parameter (deprecated)	deprecated
<picture>	Picture (responsive image container)	current
<portal>	Portal (experimental, abandoned)	experimental
<rb>	Ruby base (deprecated)	deprecated
<rtc>	Ruby text container (deprecated)	deprecated
<search>	Search section	current

Element	Meaning	Status today
<selectedcontent>	Selected option display (customisable select)	experimental
<slot>	Shadow DOM slot	current

<dialog> — Dialog box

Status: CURRENT | Versions: HTML 5.2 / Living Standard

The <dialog> element represents a dialog box or other interactive component such as a confirmation prompt, an alert, a subwindow or a modal overlay. It is hidden by default and is shown with the open attribute or, preferably, with the JavaScript methods show() (non-modal) and showModal() (modal). A modal dialog blocks interaction with the rest of the page, is displayed on top of everything else, and can be closed with the Escape key.

```
<dialog id="d">...</dialog>
<script>document.getElementById('d').showModal()</script>
```

<fencedframe> — Fenced frame (experimental)

Status: EXPERIMENTAL | Versions: Experimental (Chromium, 2024)

The <fencedframe> element embeds another HTML page in a way that is even more isolated than an <iframe>: the embedded page cannot communicate with the embedding page, and the URL is chosen through privacy-preserving APIs rather than given directly. It is part of the Privacy Sandbox proposals for showing personalised advertisements without cross-site tracking. It is not yet a standard and is only available in Chromium browsers.

```
<fencedframe width="300" height="250"></fencedframe>
```

<hgroup> — Heading group

Status: CURRENT | Versions: HTML5 (removed from W3C HTML 5.0, kept in the Living Standard with a new definition)

The <hgroup> element groups a heading (<h1>-<h6>) with one or more <p> elements that contain a subtitle, alternative title, tagline or other secondary text. It tells the browser that the paragraphs belong to the heading rather than being ordinary content.

```
<hgroup>
  <h1>Title</h1>
  <p>Subtitle</p>
</hgroup>
```

<main> — Main content

Status: CURRENT | Versions: HTML 5.1 (2016)

The <main> element represents the dominant content of the <body>: the content that is directly related to, or expands upon, the central topic of the page or the central function of the application. It excludes content repeated across pages such as the site header, navigation, sidebars, search box, logo and footer.

```
<main>...</main>
```

<menuitem> — Menu item (obsolete)

Status: OBSOLETE | Versions: HTML5 draft (Firefox only); removed 2017

The <menuitem> element represented a command in a <menu type="context">, letting a page add custom items to the browser's right-click menu. Only Firefox implemented it; it was removed from the standard in 2017 and from Firefox in 2020. Build custom menus with lists, buttons and JavaScript (or the popover attribute) instead.

```
<menuitem label="Refresh" onclick="...">
```

<param> — Object parameter (deprecated)

Status: DEPRECATED | Versions: HTML 3.2, HTML 4.01, HTML5; deprecated in the Living Standard

The <param> element defined a parameter for an <object> element, passing a name/value pair to the plug-in that displayed the object (for example the autoplay setting of a Flash movie). Since plug-ins no longer exist, the element serves no purpose; the Living Standard marks it deprecated and it is retained only for compatibility. It is a void element.

```
<object data="movie.swf">
  <param name="quality" value="high">
</object>
```

<picture> — Picture (responsive image container)

Status: CURRENT | Versions: HTML 5.1 (2016)

The <picture> element contains zero or more <source> elements and exactly one <img> element, and lets the browser choose the most suitable image from several candidates. The browser examines each <source> in order and uses the first whose media query matches and whose type it supports; if none match it falls back to the <img>. The <img> element is required: it is what is actually displayed, and it carries the alt text, width, height, loading and other attributes.

```
<picture>
  <source srcset="..." media="..." type="...">
  <img src="..." alt="...">
</picture>
```

<portal> — Portal (experimental, abandoned)

Status: EXPERIMENTAL | Versions: Chrome experiment (2019-2022); not standardised

The <portal> element was an experiment that embedded a preview of another page, like an iframe, with the ability to 'activate' it and navigate seamlessly into it with an animation. It was available only behind a flag in Chrome and the work has been superseded by the View Transitions API and prerendering with the Speculation Rules API. Do not use it.

```
<portal src="https://example.com"></portal>
```

<rb> — Ruby base (deprecated)

Status: DEPRECATED | Versions: XHTML 1.1 Ruby, HTML 5.1; removed from the Living Standard

The <rb> element explicitly marked the base text component of a ruby annotation, the text that the <rt> annotation is placed above. The Living Standard removed it because the base text can simply be written directly inside <ruby>. Browsers still support it.

```
<ruby><rb></rb><rt>kan</rt></ruby>
```

<rtc> — Ruby text container (deprecated)

Status: DEPRECATED | Versions: HTML 5.1; removed from the Living Standard

The <rtc> element grouped several <rt> annotations so that a base text could have two layers of annotation (for example pronunciation above and meaning below). Only Firefox implemented it, and the Living Standard removed it. Nest two <ruby> elements for double-sided annotations.

```
<ruby>base<rtc><rt>a</rt></rtc><rtc><rt>b</rt></rtc></ruby>
```

<search> — Search section

Status: CURRENT | Versions: Living Standard (2023)

The <search> element represents a part of the document whose contents are search or filtering controls: a site search form, a filter panel in a product list, or the controls of a find-in-page feature. It has no visual effect; it exposes the 'search' landmark to assistive technology. It replaces the old pattern <form role="search">. The form itself still goes inside it.

```
<search>
  <form>...</form>
</search>
```

<selectedcontent> — Selected option display (customisable select)

Status: EXPERIMENTAL | Versions: Living Standard (2025, experimental)

The <selectedcontent> element is part of the customisable <select> proposal. Placed inside the <button> that sits at the start of a <select>, it mirrors the content of the currently selected <option>, so that rich option content (icons, colour swatches, descriptions) is shown in the closed control as well as in the open list. The browser clones the selected option's children into <selectedcontent> whenever the selection changes.

```
<select>
  <button><selectedcontent></selectedcontent></button>
  <option>...</option>
</select>
```

<slot> — Shadow DOM slot

Status: CURRENT | Versions: HTML5 / DOM Standard (2016)

The <slot> element is a placeholder inside a web component's shadow tree that is filled with content from the light DOM (the markup written by the user of the component). A named slot receives children that have a matching slot attribute; the unnamed default slot receives all other children. Content inside the <slot> element itself is fallback content shown when nothing is slotted.

```
<slot name="title">Default title</slot>
```

Part 4

Global Attributes

Attributes that can be used on any HTML element.

Global attributes

The attributes in this part are 'global': they may be specified on every HTML element, even those where they have no obvious effect. They are listed alphabetically. Event handler attributes (on*) are in Part 5.

Attribute	Values
accesskey	single character
autocapitalize	off | none | on | sentences | words | characters
autocorrect	on | off
autofocus	boolean
class	space-separated class names
contenteditable	true | false | plaintext-only | (empty = true)
data-*	any text
dir	ltr | rtl | auto
draggable	true | false
enterkeyhint	enter | done | go | next | previous | search | send
exportparts	comma-separated part names (optionally name:alias)
hidden	boolean | until-found
id	unique identifier
inert	boolean
inputmode	none | text | decimal | numeric | tel | search | email | url
is	custom element name
itemid, itemprop, itemref, itemscope, itemtype	various

Attribute	Values
lang	BCP 47 language tag
nonce	cryptographic number used once
part	space-separated part names
popover	auto | manual | hint | (empty = auto)
role	ARIA role name
aria-*	various
slot	slot name
spellcheck	true | false
style	CSS declarations
tabindex	integer
title	text
translate	yes | no | (empty = yes)
virtualkeyboardpolicy	auto | manual
writingsuggestions	true | false
xml:lang, xml:base, xml:space	various

Global attribute: accesskey

Values: single character | Since: HTML 4.01

Description

Defines a keyboard shortcut that activates or focuses the element. The key combination depends on the browser and operating system (usually Alt + key on Windows/Linux in Chrome and Edge, Alt + Shift + key in Firefox, Control + Option + key on macOS). Because these combinations often collide with browser and assistive-technology shortcuts, accesskey is rarely recommended; if used, document the shortcuts on the page.

Example

```
<button accesskey="s">Save (Alt+S)</button>
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: accesskey.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.
- In JavaScript read it with element.getAttribute('accesskey') or, for most global attributes, a property of the same name.

Global attribute: autocapitalize

Values: off | none | on | sentences | words | characters | Since: Living Standard

Description

Controls whether and how text input is automatically capitalised on virtual keyboards (phones and tablets). It has no effect on physical keyboards. Inherited by descendant editable elements.

Example

```
<input name="username" autocapitalize="none">
<textarea autocapitalize="sentences"></textarea>
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: autocapitalize.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.
- In JavaScript read it with element.getAttribute('autocapitalize') or, for most global attributes, a property of the same name.

Global attribute: autocorrect

Values: on | off | Since: Living Standard

Description

Controls whether the browser may automatically correct spelling in editable text. Originally a Safari extension, added to the Living Standard in 2024.

Example

```
<input name="code" autocorrect="off">
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: autocorrect.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.
- In JavaScript read it with element.getAttribute('autocorrect') or, for most global attributes, a property of the same name.

Global attribute: autofocus

Values: boolean | Since: HTML5 (global since 2019)

Description

Indicates that the element should receive focus as soon as the page loads (or the <dialog> it is in is shown). Only one element per document should have it. Use with care: moving focus automatically can disorient screen reader users and scrolls the page to the element.

Example

```
<input name="q" type="search" autofocus>
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: autofocus.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.
- In JavaScript read it with element.getAttribute('autofocus') or, for most global attributes, a property of the same name.

Global attribute: class

Values: space-separated class names | Since: HTML 4.01

Description

A list of the classes the element belongs to. Classes are the primary hook for CSS (selector .name) and for JavaScript (document.querySelectorAll('.name')). An element may have many classes and many elements may share a class. Class names are case-sensitive, should not start with a digit, and by convention use lowercase words joined with hyphens (kebab-case). Choose names that describe what the element is, not how it looks (product-card rather than red-box), so that the style can change without renaming.

Example

```
<div class="card featured">...</div>
<style>.card { border: 1px solid #ccc; } .featured { border-color:
gold; }</style>
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: class.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.

- In JavaScript read it with element.getAttribute('class') or, for most global attributes, a property of the same name.

Global attribute: contenteditable

Values: true | false | plaintext-only | (empty = true) | Since: HTML5

Description

Makes the element's content editable by the user directly in the page, turning it into a basic rich-text editor. plaintext-only allows editing text but not formatting. The property is inherited: children of an editable element are editable unless they set contenteditable="false". Combine with the input event and the document.execCommand or Selection APIs to build editors.

Example

```
<p contenteditable="true">Click here and edit this text.</p>
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: contenteditable.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.
- In JavaScript read it with element.getAttribute('contenteditable') or, for most global

attributes, a property of the same name.

Global attribute: data-*

Values: any text | Since: HTML5

Description

Custom data attributes. Any attribute whose name starts with data- is reserved for the page author's own data and is guaranteed never to be given a meaning by browsers. The value is available in JavaScript through element.dataset (data-user-id becomes dataset.userId) and in CSS through attr(). Use them to attach information to elements without misusing class or id.

Example

```
<li data-product-id="42" data-price="120">Learn HTML</li>
<script>
  const li = document.querySelector('li');
  console.log(li.dataset.productId, li.dataset.price); // "42" "120"
</script>
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: data-*.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.

- In JavaScript read it with element.getAttribute('data-*') or, for most global attributes, a property of the same name.

Global attribute: dir

Values: ltr | rtl | auto | Since: HTML 4.01

Description

The text direction of the element's content. ltr = left to right (English, French...); rtl = right to left (Arabic, Hebrew, Persian, Urdu); auto = let the browser decide from the first strongly directional character, useful for user-generated content. Set it on <html> for the whole page. It affects text alignment, the side on which bullets and scrollbars appear, and the order of table columns.

Example

```
<html lang="ar" dir="rtl">
<p dir="ltr">This English paragraph inside an Arabic page reads left
to right.</p>
<input dir="auto">
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: dir.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.
- In JavaScript read it with element.getAttribute('dir') or, for most global attributes, a property of the same name.

Global attribute: draggable

Values: true | false | Since: HTML5

Description

Whether the element can be dragged with the Drag and Drop API. Images and links are draggable by default; other elements need draggable="true". The value must be written explicitly (it is not a boolean attribute). Dragging fires dragstart, drag, dragend on the source and dragenter, dragover, drop on the target.

Example

```
<div draggable="true" ondragstart="event.dataTransfer.setData('text',
'hello')">Drag me</div>
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: draggable.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.
- In JavaScript read it with element.getAttribute('draggable') or, for most global attributes, a property of the same name.

Global attribute: enterkeyhint

Values: enter | done | go | next | previous | search | send | Since: Living Standard

Description

A hint about which label or icon to show on the Enter key of virtual keyboards, matching the action that pressing Enter will perform in this field.

Example

```
<input type="search" enterkeyhint="search">
<textarea enterkeyhint="send"></textarea>
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: enterkeyhint.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.
- In JavaScript read it with element.getAttribute('enterkeyhint') or, for most global attributes, a property of the same name.

Global attribute: exportparts

Values: comma-separated part names (optionally name:alias) | Since: CSS Shadow Parts

Description

In web components: re-exports parts from a nested shadow tree so that they can be styled from outside with the ::part() pseudo-element.

Example

```
<my-dialog exportparts="header, footer:dialog-footer"></my-dialog>
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: exportparts.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.
- In JavaScript read it with element.getAttribute('exportparts') or, for most global attributes, a property of the same name.

Global attribute: hidden

Values: boolean | until-found | Since: HTML5

Description

Indicates that the element is not (yet) relevant and should not be rendered. Browsers implement it as display: none, so any CSS that sets display on the element will override it (add [hidden] { display: none !important } to be safe). The value until-found keeps the content hidden but searchable with find-in-page and fragment links; the browser reveals it automatically when found. Do not use hidden to hide content only visually while keeping it for screen readers; use a visually-hidden CSS class instead.

Example

```
<p hidden>Not shown.</p>
<section hidden="until-found">Revealed when the user searches for
text inside it.</section>
<script>document.querySelector('p').hidden = false;</script>
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: hidden.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.

- In JavaScript read it with element.getAttribute('hidden') or, for most global attributes, a property of the same name.

Global attribute: id

Values: unique identifier | Since: HTML 4.01

Description

A unique identifier for the element within the document. No two elements may share an id. It is used as the target of fragment links (href="#id"), by CSS (#id), by JavaScript (getElementById), by <label for>, by aria-labelledby and aria-describedby, by <input list>, by <output for>, by the form attribute and by <map name>. Ids are case-sensitive, must not contain spaces, and should start with a letter.

Example

```
<h2 id="pricing">Pricing</h2>
<a href="#pricing">Jump to pricing</a>
<label for="email">Email</label> <input id="email">
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: id.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.
- In JavaScript read it with element.getAttribute('id') or, for most global attributes, a property of the same name.

Global attribute: inert

Values: boolean | Since: Living Standard (2022)

Description

Makes the element and all its descendants inert: they cannot be focused, clicked, selected or found by find-in-page, and they are hidden from assistive technology. It is the tool for disabling everything behind a custom modal dialog or an open off-canvas menu. Native <dialog> showModal() applies inertness to the rest of the page automatically.

Example

```
<main inert>Page content that cannot be interacted with while the
menu is open</main>
<nav class="drawer">Menu</nav>
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: inert.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.
- In JavaScript read it with element.getAttribute('inert') or, for most global attributes, a property of the same name.

Global attribute: inputmode

Values: none | text | decimal | numeric | tel | search | email | url | Since: HTML5

Description

A hint about which virtual keyboard to display when the element (an input, textarea or contenteditable) is focused. Unlike changing type, it does not change validation or the value: inputmode="numeric" on a text input shows a number pad but still accepts a postal code with a leading zero.

Example

```
<input name="zip" inputmode="numeric" pattern="[0-9]*">
<input name="amount" inputmode="decimal">
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: inputmode.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.
- In JavaScript read it with element.getAttribute('inputmode') or, for most global attributes, a property of the same name.

Global attribute: is

Values: custom element name | Since: HTML5 / Custom Elements

Description

Declares that a built-in element should behave like a customised built-in element defined with customElements.define(name, class, { extends: 'button' }). Not supported in Safari.

Example

```
<button is="fancy-button">Click</button>
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: is.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.
- In JavaScript read it with element.getAttribute('is') or, for most global attributes, a property of the same name.

Global attribute: itemid, itemprop, itemref, itemscope, itemtype

Values: various | Since: HTML5 Microdata

Description

Microdata attributes that embed machine-readable structured data (for example schema.org vocabularies) into the page for search engines. itemscope creates an item; itemtype gives its type URL; itemprop names a property; itemid gives a global identifier; itemref includes properties located elsewhere. JSON-LD in a <script type="application/ld+json"> is the more common approach today.

Example

```
<div itemscope itemtype="https://schema.org/Book">
  <span itemprop="name">Learn HTML</span> by
  <span itemprop="author">Sara</span>
</div>
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: itemid, itemprop, itemref, itemscope, itemtype.
- Put the value in double quotes unless it is a boolean attribute.

- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.
- In JavaScript read it with element.getAttribute('itemid, itemprop, itemref, itemscope, itemtype') or, for most global attributes, a property of the same name.

Global attribute: lang

Values: BCP 47 language tag | Since: HTML 4.01

Description

The language of the element's content. Language tags consist of a two-letter language code (en, ar, fr, de, es, zh, ja) optionally followed by a script (zh-Hans) and/or a region (en-GB, ar-EG, pt-BR). Set it on <html> for the page and on any element whose language differs. Browsers use it for hyphenation, quotation marks, font choice and spell checking; screen readers use it to switch voices; translation tools use it to decide what to translate. An empty value means the language is unknown.

Example

```
<html lang="en">
<p>The word <span lang="ar">كتاب</span> means book.</p>
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: lang.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.

- In JavaScript read it with element.getAttribute('lang') or, for most global attributes, a property of the same name.

Global attribute: nonce

Values: cryptographic number used once | Since: CSP

Description

A random token generated by the server for each response and listed in the Content-Security-Policy header, so that only the inline <script> and <style> elements carrying that nonce are allowed to run. Browsers hide the value from scripts after parsing.

Example

```
<script nonce="r4nd0m">/* allowed by CSP 'nonce-r4nd0m' */</script>
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: nonce.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.
- In JavaScript read it with element.getAttribute('nonce') or, for most global attributes, a property of the same name.

Global attribute: part

Values: space-separated part names | Since: CSS Shadow Parts

Description

In web components: names an element inside a shadow tree so that it can be styled from outside with the ::part(name) pseudo-element.

Example

```
<!-- inside the shadow tree -->
<button part="confirm">OK</button>
<!-- outside -->
<style>my-dialog::part(confirm) { background: green; }</style>
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: part.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.
- In JavaScript read it with element.getAttribute('part') or, for most global attributes, a property of the same name.

Global attribute: popover

Values: auto | manual | hint | (empty = auto) | Since: Living Standard (2023)

Description

Turns the element into a popover: hidden by default and displayed in the top layer (above everything else) when shown with a button that has popovertarget, or with showPopover()/togglePopover() in JavaScript. auto popovers close when the user clicks outside or presses Escape and only one is open at a time; manual popovers must be closed explicitly. Style the backdrop with ::backdrop and the open state with :popover-open.

Example

```
<button popovertarget="menu">Menu</button>
<div id="menu" popover>
  <a href="/profile">Profile</a>
  <a href="/logout">Log out</a>
</div>
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: popover.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.

- In JavaScript read it with element.getAttribute('popover') or, for most global attributes, a property of the same name.

Global attribute: role

Values: ARIA role name | Since: WAI-ARIA 1.0

Description

From WAI-ARIA: overrides or specifies the semantic role of the element for assistive technology, for example role="button", role="navigation", role="alert", role="tab". The first rule of ARIA is not to use it when a native element already has the right role: prefer <button> over . Use it for widgets HTML lacks (tabs, trees, comboboxes) and for landmarks in older browsers.

Example

```
<div role="alert">Your order was placed.</div>
<ul role="tablist"><li role="tab" aria-selected="true">Details</li></
ul>
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: role.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.
- In JavaScript read it with element.getAttribute('role') or, for most global attributes, a property of the same name.

Global attribute: aria-*

Values: various | Since: WAI-ARIA 1.0

Description

From WAI-ARIA: a family of attributes that describe the state and properties of elements for assistive technology. The most used: aria-label (accessible name from a string), aria-labelledby (name from another element), aria-describedby (description), aria-hidden (hide from AT), aria-expanded (open/closed), aria-current (current item), aria-live (announce changes), aria-controls, aria-selected, aria-checked, aria-disabled, aria-required, aria-invalid, aria-haspopup, aria-pressed, aria-busy, aria-modal.

Example

```
<button aria-label="Close" aria-expanded="false" aria-
controls="panel">×</button>
<div id="status" aria-live="polite"></div>
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: aria-*.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.

- In JavaScript read it with element.getAttribute('aria-*') or, for most global attributes, a property of the same name.

Global attribute: slot

Values: slot name | Since: DOM Standard

Description

Assigns the element to a named <slot> inside the shadow tree of its parent custom element.

Example

```
<user-card>
  <span slot="name">Ahmed</span>
</user-card>
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: slot.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.
- In JavaScript read it with element.getAttribute('slot') or, for most global attributes, a property of the same name.

Global attribute: spellcheck

Values: true | false | Since: HTML5

Description

Whether the browser should check the spelling and grammar of the element's editable text. Browsers decide the default per element (usually on for textarea and contenteditable, off for input). Turn it off for codes, usernames and passwords. Note: some browsers send checked text to a remote service.

Example

```
<textarea spellcheck="true"></textarea>
<input name="coupon" spellcheck="false">
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: spellcheck.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.
- In JavaScript read it with element.getAttribute('spellcheck') or, for most global attributes, a property of the same name.

Global attribute: style

Values: CSS declarations | Since: HTML 4.01

Description

Inline CSS applied to this element only. Declarations are written as property: value pairs separated by semicolons, exactly as inside a style sheet rule but without the selector and braces. Inline styles have higher specificity than any selector and are hard to override, cannot use media queries or pseudo-classes, and are blocked by strict Content Security Policies, so prefer classes and a style sheet. Inline styles are convenient for quick tests and for values computed by JavaScript.

Example

```
<p style="color: red; font-size: 1.2em; margin-bottom: 0">Inline
styled paragraph</p>
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: style.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.

- In JavaScript read it with element.getAttribute('style') or, for most global attributes, a property of the same name.

Global attribute: tabindex

Values: integer | Since: HTML 4.01

Description

Controls whether the element can be focused with the keyboard (Tab key) and in what order. tabindex="0" makes a normally non-focusable element (such as a div) focusable, in the natural document order. tabindex="-1" makes it focusable by script (element.focus()) but not by Tab; use it for the target of a skip link or a container that receives focus programmatically. Positive values (1, 2, 3...) force a custom order before all other elements and should be avoided because they make the page confusing. Interactive elements (links, buttons, form controls) are focusable without tabindex.

Example

```
<div tabindex="0" role="button">Focusable custom control</div>
<main id="content" tabindex="-1">...</main>
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: tabindex.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.

- In JavaScript read it with element.getAttribute('tabindex') or, for most global attributes, a property of the same name.

Global attribute: title

Values: text | Since: HTML 4.01

Description

Advisory information about the element, shown by most desktop browsers as a tooltip when the mouse rests on it. On <abbr> it holds the expansion; on <link rel=stylesheet> it names an alternate style sheet; on <iframe> it is the accessible name. Tooltips are not accessible to touch-screen or keyboard users and are read inconsistently by screen readers, so never put essential information only in title. Do not repeat the visible text in title; it produces double announcements.

Example

```
<abbr title="World Health Organization">WHO</abbr>
<button title="Save (Ctrl+S)">Save</button>
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: title.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.

- In JavaScript read it with element.getAttribute('title') or, for most global attributes, a property of the same name.

Global attribute: translate

Values: yes | no | (empty = yes) | Since: HTML5

Description

Whether the element's text and translatable attribute values should be translated when the page is localised by machine translation tools. Set translate="no" on brand names, code, and addresses.

Example

```
<p>Buy it at <span translate="no">Book Store</span> today.</p>
<code translate="no">getElementById</code>
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: translate.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.
- In JavaScript read it with element.getAttribute('translate') or, for most global attributes, a property of the same name.

Global attribute: virtualkeyboardpolicy

Values: auto | manual | Since: VirtualKeyboard API

Description

For editable elements: whether the virtual keyboard opens automatically on focus (auto) or only when the script calls navigator.virtualKeyboard.show() (manual).

Example

```
<div contenteditable virtualkeyboardpolicy="manual"></div>
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: virtualkeyboardpolicy.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.
- In JavaScript read it with element.getAttribute('virtualkeyboardpolicy') or, for most global attributes, a property of the same name.

Global attribute: writingsuggestions

Values: true | false | Since: Living Standard (2024)

Description

Whether the browser may offer writing suggestions (predictive text, autocomplete of sentences) in editable elements.

Example

```
<textarea writingsuggestions="false"></textarea>
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: writingsuggestions.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.
- In JavaScript read it with element.getAttribute('writingsuggestions') or, for most global attributes, a property of the same name.

Global attribute: xml:lang, xml:base, xml:space

Values: various | Since: XHTML 1.0

Description

XML attributes that only have meaning in XHTML documents served as XML. In HTML they are ignored (xml:lang must match lang if both are present).

Example

```
<html xmlns="http://www.w3.org/1999/xhtml" xml:lang="en" lang="en">
```

Where it can be used

On every HTML element, including <html>, <head> and <body>, and on elements inside <template> and shadow trees. Elements where the attribute has no practical effect (for example tabindex on <meta>) still accept it without a validation error, but such use should be avoided.

Checklist

- Write the name in lower case: xml:lang, xml:base, xml:space.
- Put the value in double quotes unless it is a boolean attribute.
- Do not repeat the same attribute twice on one start tag; browsers keep the first one only.
- In JavaScript read it with element.getAttribute('xml:lang, xml:base, xml:space') or, for most global attributes, a property of the same name.

Part 5

Event Handler Attributes

Every on* attribute and the event that triggers it.

Event handler attributes

Every HTML element accepts event handler content attributes whose value is JavaScript code run when the event fires. The attribute name is 'on' followed by the event name. In modern code it is better to attach handlers with element.addEventListener('click', fn) in a script, which keeps behaviour out of the markup and allows several handlers per event, but the attributes remain valid and are useful for quick prototypes.

```
<!-- attribute style -->
<button onclick="alert('Hi')">Say hi</button>

<!-- script style (preferred) -->
<button id="hi">Say hi</button>
<script>
  document.getElementById('hi').addEventListener('click', () => alert(
'Hi'));
</script>
```

Attribute	Event	Applies to
onabort	abort	img, audio, video, and others
onauxclick	auxclick	All elements
onbeforeinput	beforeinput	input, textarea, contenteditable
onbeforematch	beforematch	All elements
onbeforetoggle	beforetoggle	popover elements, details, dialog
onblur	blur	Focusable elements
oncancel	cancel	dialog, input type=file
oncanplay	canplay	audio, video
oncanplaythrough	canplaythrough	audio, video

Attribute	Event	Applies to
onchange	change	input, select, textarea
onclick	click	All elements
onclose	close	dialog, popover
oncontextmenu	contextmenu	All elements
oncopy, oncut, onpaste	copy, cut, paste	All elements
oncuechange	cuechange	track
ondblclick	dblclick	All elements
ondrag, ondragend, ondragenter, ondragleave, ondragover, ondragstart, ondrop	drag events	All elements
ondurationchange	durationchange	audio, video
onemptied	emptied	audio, video
onended	ended	audio, video
onerror	error	img, script, link, audio, video, body
onfocus	focus	Focusable elements
onformdata	formdata	form
oninput	input	input, select, textarea, contenteditable
oninvalid	invalid	Form controls
onkeydown	keydown	Focusable elements, document
onkeypress	keypress	-
onkeyup	keyup	Focusable elements
onload	load	img, script, link, iframe, body, object

Attribute	Event	Applies to
onloadeddata	loadeddata	audio, video
onloadedmetadata	loadedmetadata	audio, video
onloadstart	loadstart	audio, video
onmousedown, onmouseup	mousedown, mouseup	All elements
onmouseenter, onmouseleave	mouseenter, mouseleave	All elements
onmousemove	mousemove	All elements
onmouseover, onmouseout	mouseover, mouseout	All elements
onpause, onplay, onplaying	pause, play, playing	audio, video
onpointerdown, onpointerup, onpointermove, onpointerover, onpointerout, onpointerenter, onpointerleave, onpointercancel, ongotpointercapture, onlostpointercapture	pointer events	All elements
onprogress	progress	audio, video
onratechange	ratechange	audio, video
onreset	reset	form
onresize	resize	body, video
onscroll	scroll	Scrollable elements, body
onscrollend	scrollend	Scrollable elements, body
onsecuritypolicyviolation	securitypolicyviolation	All elements

Attribute	Event	Applies to
onseeked, onseeking	seeked, seeking	audio, video
onselect	select	input, textarea
onselectionchange	selectionchange	document, input, textarea
onslotchange	slotchange	slot
onstalled	stalled	audio, video
onsubmit	submit	form
onsuspend	suspend	audio, video
ontimeupdate	timeupdate	audio, video
ontoggle	toggle	details, popover elements
ontouchstart, ontouchmove, ontouchend, ontouchcancel	touch events	All elements
onvolumechange	volumechange	audio, video
onwaiting	waiting	audio, video
onwheel	wheel	All elements
onanimationstart, onanimationend, onanimationiteration, onanimationcancel	animation events	All elements
ontransitionstart, ontransitionend, ontransitionrun, ontransitioncancel	transition events	All elements
oncontextlost, oncontextrestored	contextlost, contextrestored	canvas

Attribute	Event	Applies to
Window events on <body>: onafterprint, onbeforeprint, onbeforeunload, onhashchange, onlanguagechange, onmessage, onmessageerror, onoffline, ononline, onpagehide, onpagereveal, onpageshow, onpageswap, onpopstate, onrejectionhandled, onstorage, onunhandledrejection, onunload	window events	body

Event attribute: onabort

Event name: abort | Applies to: img, audio, video, and others

Fires when

Loading of a resource was aborted.

Attribute form

```
<div onabort="console.log('abort fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('abort', function (event) {
  console.log('abort fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onauxclick

Event name: auxclick | Applies to: All elements

Fires when

A non-primary mouse button (middle, right) was clicked.

Attribute form

```
<div onauxclick="console.log('auxclick fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('auxclick', function (event) {
  console.log('auxclick fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onbeforeinput

Event name: beforeinput | Applies to: input, textarea, contenteditable

Fires when

Just before the value of an editable element changes; can be cancelled.

Attribute form

```
<div onbeforeinput="console.log('beforeinput fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('beforeinput', function (event) {
  console.log('beforeinput fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onbeforematch

Event name: beforematch | Applies to: All elements

Fires when

Content hidden with hidden=until-found is about to be revealed by find-in-page.

Attribute form

```
<div onbeforematch="console.log('beforematch fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('beforematch', function (event) {
  console.log('beforematch fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onbeforetoggle

Event name: beforetoggle | Applies to: popover elements, details, dialog

Fires when

A popover or <details> is about to open or close; cancellable for popovers.

Attribute form

```
<div onbeforetoggle="console.log('beforetoggle fired', event)">...</
div>
```

Script form (recommended)

```
element.addEventListener('beforetoggle', function (event) {
  console.log('beforetoggle fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onblur

Event name: blur | Applies to: Focusable elements

Fires when

The element lost focus. Does not bubble; use focusout for delegation.

Attribute form

```
<div onblur="console.log('blur fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('blur', function (event) {
  console.log('blur fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: oncancel

Event name: cancel | Applies to: dialog, input type=file

Fires when

The user pressed Escape in a <dialog>, or cancelled a file picker.

Attribute form

```
<div oncancel="console.log('cancel fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('cancel', function (event) {
  console.log('cancel fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: oncanplay

Event name: canplay | Applies to: audio, video

Fires when

Enough media data is available to start playing.

Attribute form

```
<div oncanplay="console.log('canplay fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('canplay', function (event) {
  console.log('canplay fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: oncanplaythrough

Event name: canplaythrough | Applies to: audio, video

Fires when

The media can probably play to the end without buffering.

Attribute form

```
<div oncanplaythrough="console.log('canplaythrough fired', event)">...
</div>
```

Script form (recommended)

```
element.addEventListener('canplaythrough', function (event) {
  console.log('canplaythrough fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onchange

Event name: change | Applies to: input, select, textarea

Fires when

The value of a form control was committed: after a text field loses focus with a changed value, or immediately when a checkbox, radio, select or file input changes. Use input for live updates.

Attribute form

```
<div onchange="console.log('change fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('change', function (event) {
  console.log('change fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onclick

Event name: click | Applies to: All elements

Fires when

The element was clicked with the primary button, tapped, or activated with Enter/Space on a button or link. The most used event attribute.

Attribute form

```
<div onclick="console.log('click fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('click', function (event) {
  console.log('click fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onclose

Event name: close | Applies to: dialog, popover

Fires when

A <dialog> was closed, or a popover was hidden.

Attribute form

```
<div onclose="console.log('close fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('close', function (event) {
  console.log('close fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: oncontextmenu

Event name: contextmenu | Applies to: All elements

Fires when

The user requested the context menu (right-click, long press, Shift+F10). Preventing default hides the browser menu.

Attribute form

```
<div oncontextmenu="console.log('contextmenu fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('contextmenu', function (event) {
  console.log('contextmenu fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: oncopy, oncut, onpaste

Event name: copy, cut, paste | Applies to: All elements

Fires when

Clipboard operations on the element.

Attribute form

```
<div oncopy, oncut, onpaste="console.log('copy, cut, paste fired',
event)">...</div>
```

Script form (recommended)

```
element.addEventListener('copy, cut, paste', function (event) {
  console.log('copy, cut, paste fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: oncuechange

Event name: cuechange | Applies to: track

Fires when

The active text track cues changed.

Attribute form

```
<div oncuechange="console.log('cuechange fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('cuechange', function (event) {
  console.log('cuechange fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: ondblclick

Event name: dblclick | Applies to: All elements

Fires when

Double click. Not fired on touch in most browsers.

Attribute form

```
<div ondblclick="console.log('dblclick fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('dblclick', function (event) {
  console.log('dblclick fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: ondrag, ondragend, ondragenter, ondragleave, ondragover, ondragstart, ondrop

Event name: drag events | Applies to: All elements

Fires when

Stages of a drag-and-drop operation: dragstart/drag/dragend on the dragged element, dragenter/dragover/dragleave/drop on the drop target. Call preventDefault in dragover to allow dropping.

Attribute form

```
<div ondrag, ondragend, ondragenter, ondragleave, ondragover,
ondragstart, ondrop="console.log('drag events fired', event)">...</
div>
```

Script form (recommended)

```
element.addEventListener('drag events', function (event) {
  console.log('drag events fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: ondurationchange

Event name: durationchange | Applies to: audio, video

Fires when

The media duration attribute was updated.

Attribute form

```
<div ondurationchange="console.log('durationchange fired', event)">...
</div>
```

Script form (recommended)

```
element.addEventListener('durationchange', function (event) {
  console.log('durationchange fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onemptied

Event name: emptied | Applies to: audio, video

Fires when

The media element became empty (for example after a network error or load()).

Attribute form

```
<div onemptied="console.log('emptied fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('emptied', function (event) {
  console.log('emptied fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onended

Event name: ended | Applies to: audio, video

Fires when

Playback reached the end.

Attribute form

```
<div onended="console.log('ended fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('ended', function (event) {
  console.log('ended fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onerror

Event name: error | Applies to: img, script, link, audio, video, body

Fires when

A resource failed to load, or a script error occurred (on body/window).

Attribute form

```
<div onerror="console.log('error fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('error', function (event) {
  console.log('error fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onfocus

Event name: focus | Applies to: Focusable elements

Fires when

The element received focus. Does not bubble; use focusin for delegation.

Attribute form

```
<div onfocus="console.log('focus fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('focus', function (event) {
  console.log('focus fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onformdata

Event name: formdata | Applies to: form

Fires when

The form's data is being constructed for submission; lets scripts add entries.

Attribute form

```
<div onformdata="console.log('formdata fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('formdata', function (event) {
  console.log('formdata fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: oninput

Event name: input | Applies to: input, select, textarea, contenteditable

Fires when

The value of an editable element changed, on every keystroke or change.

Attribute form

```
<div oninput="console.log('input fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('input', function (event) {
  console.log('input fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: oninvalid

Event name: invalid | Applies to: Form controls

Fires when

A control failed validation on submission.

Attribute form

```
<div oninvalid="console.log('invalid fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('invalid', function (event) {
  console.log('invalid fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onkeydown

Event name: keydown | Applies to: Focusable elements, document

Fires when

A key was pressed down. Repeats while held. Use event.key.

Attribute form

```
<div onkeydown="console.log('keydown fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('keydown', function (event) {
  console.log('keydown fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onkeypress

Event name: keypress | Applies to: -

Fires when

Deprecated. A character key was pressed. Use keydown.
Deprecated

Attribute form

```
<div onkeypress="console.log('keypress fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('keypress', function (event) {
  console.log('keypress fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onkeyup

Event name: keyup | Applies to: Focusable elements

Fires when

A key was released.

Attribute form

```
<div onkeyup="console.log('keyup fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('keyup', function (event) {
  console.log('keyup fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onload

Event name: load | Applies to: img, script, link, iframe, body, object

Fires when

The resource (image, script, style sheet, frame, or the whole page on body) finished loading.

Attribute form

```
<div onload="console.log('load fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('load', function (event) {
  console.log('load fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onloadeddata

Event name: loadeddata | Applies to: audio, video

Fires when

The first frame of media has loaded.

Attribute form

```
<div onloadeddata="console.log('loadeddata fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('loadeddata', function (event) {
  console.log('loadeddata fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onloadedmetadata

Event name: loadedmetadata | Applies to: audio, video

Fires when

Duration and dimensions are known.

Attribute form

```
<div onloadedmetadata="console.log('loadedmetadata fired', event)">...
</div>
```

Script form (recommended)

```
element.addEventListener('loadedmetadata', function (event) {
  console.log('loadedmetadata fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onloadstart

Event name: loadstart | Applies to: audio, video

Fires when

The browser started loading media.

Attribute form

```
<div onloadstart="console.log('loadstart fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('loadstart', function (event) {
  console.log('loadstart fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onmousedown, onmouseup

Event name: mousedown, mouseup | Applies to: All elements

Fires when

A mouse button was pressed or released.

Attribute form

```
<div onmousedown, onmouseup="console.log('mousedown, mouseup fired',
event)">...</div>
```

Script form (recommended)

```
element.addEventListener('mousedown, mouseup', function (event) {
  console.log('mousedown, mouseup fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onmouseenter, onmouseleave

Event name: mouseenter, mouseleave | Applies to: All elements

Fires when

The pointer entered or left the element (does not bubble, not fired for children).

Attribute form

```
<div onmouseenter, onmouseleave="console.log('mouseenter, mouseleave
fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('mouseenter, mouseleave', function (event) {
  console.log('mouseenter, mouseleave fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onmousemove

Event name: mousemove | Applies to: All elements

Fires when

The pointer moved over the element. Fires very often.

Attribute form

```
<div onmousemove="console.log('mousemove fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('mousemove', function (event) {
  console.log('mousemove fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onmouseover, onmouseout

Event name: mouseover, mouseout | Applies to: All elements

Fires when

The pointer entered or left the element or one of its children (bubbles).

Attribute form

```
<div onmouseover, onmouseout="console.log('mouseover, mouseout fired',
 event)">...</div>
```

Script form (recommended)

```
element.addEventListener('mouseover, mouseout', function (event) {
  console.log('mouseover, mouseout fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onpause, onplay, onplaying

Event name: pause, play, playing | Applies to: audio, video

Fires when

Playback paused / play() called / actually started after buffering.

Attribute form

```
<div onpause, onplay, onplaying="console.log('pause, play, playing
fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('pause, play, playing', function (event) {
  console.log('pause, play, playing fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onpointerdown, onpointerup, onpointermove, onpointerover, onpointerout, onpointerenter, onpointerleave, onpointercancel, ongotpointercapture, onlostpointercapture

Event name: pointer events | Applies to: All elements

Fires when

Unified events for mouse, touch and pen input. Prefer them over mouse and touch events.

Attribute form

```
<div onpointerdown, onpointerup, onpointermove, onpointerover,
onpointerout, onpointerenter, onpointerleave, onpointercancel,
ongotpointercapture, onlostpointercapture="console.log('pointer
events fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('pointer events', function (event) {
  console.log('pointer events fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).

- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onprogress

Event name: progress | Applies to: audio, video

Fires when

Periodic progress while downloading media.

Attribute form

```
<div onprogress="console.log('progress fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('progress', function (event) {
  console.log('progress fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onratechange

Event name: ratechange | Applies to: audio, video

Fires when

Playback speed changed.

Attribute form

```
<div onratechange="console.log('ratechange fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('ratechange', function (event) {
  console.log('ratechange fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onreset

Event name: reset | Applies to: form

Fires when

The form was reset.

Attribute form

```
<div onreset="console.log('reset fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('reset', function (event) {
  console.log('reset fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onresize

Event name: resize | Applies to: body, video

Fires when

The window was resized (on body); or an element resized (video). Use ResizeObserver for elements.

Attribute form

```
<div onresize="console.log('resize fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('resize', function (event) {
  console.log('resize fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onscroll

Event name: scroll | Applies to: Scrollable elements, body

Fires when

The element or document scrolled.

Attribute form

```
<div onscroll="console.log('scroll fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('scroll', function (event) {
  console.log('scroll fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onscrollend

Event name: scrollend | Applies to: Scrollable elements, body

Fires when

Scrolling finished.

Attribute form

```
<div onscrollend="console.log('scrollend fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('scrollend', function (event) {
  console.log('scrollend fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onsecuritypolicyviolation

Event name: securitypolicyviolation | Applies to: All elements

Fires when

A Content Security Policy rule was violated.

Attribute form

```
<div onsecuritypolicyviolation="console.log('securitypolicyviolation
fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('securitypolicyviolation', function (event) {
  console.log('securitypolicyviolation fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onseeked, onseeking

Event name: seeked, seeking | Applies to: audio, video

Fires when

A seek operation finished / started.

Attribute form

```
<div onseeked, onseeking="console.log('seeked, seeking fired',
event)">...</div>
```

Script form (recommended)

```
element.addEventListener('seeked, seeking', function (event) {
  console.log('seeked, seeking fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onselect

Event name: select | Applies to: input, textarea

Fires when

Text was selected inside an input or textarea.

Attribute form

```
<div onselect="console.log('select fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('select', function (event) {
  console.log('select fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onselectionchange

Event name: selectionchange | Applies to: document, input, textarea

Fires when

The document selection changed.

Attribute form

```
<div onselectionchange="console.log('selectionchange fired', event)">.
..</div>
```

Script form (recommended)

```
element.addEventListener('selectionchange', function (event) {
  console.log('selectionchange fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onslotchange

Event name: slotchange | Applies to: slot

Fires when

The nodes assigned to a slot changed.

Attribute form

```
<div onslotchange="console.log('slotchange fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('slotchange', function (event) {
  console.log('slotchange fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onstalled

Event name: stalled | Applies to: audio, video

Fires when

The browser is trying to fetch media data but none is arriving.

Attribute form

```
<div onstalled="console.log('stalled fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('stalled', function (event) {
  console.log('stalled fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onsubmit

Event name: submit | Applies to: form

Fires when

The form is about to be submitted; call preventDefault() to handle it with JavaScript.

Attribute form

```
<div onsubmit="console.log('submit fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('submit', function (event) {
  console.log('submit fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onsuspend

Event name: suspend | Applies to: audio, video

Fires when

Media loading was intentionally suspended.

Attribute form

```
<div onsuspend="console.log('suspend fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('suspend', function (event) {
  console.log('suspend fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: ontimeupdate

Event name: timeupdate | Applies to: audio, video

Fires when

The playback position changed (several times per second).

Attribute form

```
<div ontimeupdate="console.log('timeupdate fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('timeupdate', function (event) {
  console.log('timeupdate fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: ontoggle

Event name: toggle | Applies to: details, popover elements

Fires when

A <details> element or popover opened or closed.

Attribute form

```
<div ontoggle="console.log('toggle fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('toggle', function (event) {
  console.log('toggle fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: ontouchstart, ontouchmove, ontouchend, ontouchcancel

Event name: touch events | Applies to: All elements

Fires when

Touch screen interactions. Prefer pointer events.

Attribute form

```
<div ontouchstart, ontouchmove, ontouchend, ontouchcancel="console.
log('touch events fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('touch events', function (event) {
  console.log('touch events fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onvolumechange

Event name: volumechange | Applies to: audio, video

Fires when

Volume or muted state changed.

Attribute form

```
<div onvolumechange="console.log('volumechange fired', event)">...</
div>
```

Script form (recommended)

```
element.addEventListener('volumechange', function (event) {
  console.log('volumechange fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onwaiting

Event name: waiting | Applies to: audio, video

Fires when

Playback stopped because the next frame is not available.

Attribute form

```
<div onwaiting="console.log('waiting fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('waiting', function (event) {
  console.log('waiting fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onwheel

Event name: wheel | Applies to: All elements

Fires when

A mouse wheel or trackpad scroll gesture.

Attribute form

```
<div onwheel="console.log('wheel fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('wheel', function (event) {
  console.log('wheel fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: onanimationstart, onanimationend, onanimationiteration, onanimationcancel

Event name: animation events | Applies to: All elements

Fires when

CSS animation lifecycle.

Attribute form

```
<div onanimationstart, onanimationend, onanimationiteration,
onanimationcancel="console.log('animation events fired', event)">...</
div>
```

Script form (recommended)

```
element.addEventListener('animation events', function (event) {
  console.log('animation events fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: ontransitionstart, ontransitionend, ontransitionrun, ontransitioncancel

Event name: transition events | Applies to: All elements

Fires when

CSS transition lifecycle.

Attribute form

```
<div ontransitionstart, ontransitionend, ontransitionrun,
ontransitioncancel="console.log('transition events fired', event)">...
</div>
```

Script form (recommended)

```
element.addEventListener('transition events', function (event) {
  console.log('transition events fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: oncontextlost, oncontextrestored

Event name: contextlost, contextrestored | Applies to: canvas

Fires when

A canvas drawing context was lost or restored.

Attribute form

```
<div oncontextlost, oncontextrestored="console.log('contextlost,
contextrestored fired', event)">...</div>
```

Script form (recommended)

```
element.addEventListener('contextlost, contextrestored', function (
event) {
  console.log('contextlost, contextrestored fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Event attribute: Window events on <body>: onafterprint, onbeforeprint, onbeforeunload, onhashchange, onlanguagechange, onmessage, onmessageerror, onoffline, ononline, onpagehide, onpagereveal, onpageshow, onpageswap, onpopstate, onrejectionhandled, onstorage, onunhandledrejection, onunload

Event name: window events | Applies to: body

Fires when

Events that fire on the window object and are exposed as attributes on <body> (and <frameset>). See the <body> entry.

Attribute form

```
<div Window events on <body>: onafterprint, onbeforeprint,
onbeforeunload, onhashchange, onlanguagechange, onmessage,
onmessageerror, onoffline, ononline, onpagehide, onpagereveal,
onpageshow, onpageswap, onpopstate, onrejectionhandled, onstorage,
```

```
onunhandledrejection, onunload="console.log('window events fired',
event)">...</div>
```

Script form (recommended)

```
element.addEventListener('window events', function (event) {
  console.log('window events fired on', event.target);
});
```

Notes

- Inside the attribute value, the variable 'event' refers to the Event object and 'this' refers to the element.
- Returning false from the attribute code cancels the default action (same as event.preventDefault()).
- The attribute value is compiled as the body of a function, so a syntax error is reported only when the event first fires.
- Content Security Policy (CSP) headers that forbid inline scripts also block attribute handlers; addEventListener is unaffected.

Part 6

Element Reference

One complete entry for each of the 144 HTML elements, alphabetically.

Element index

Element	Meaning	Status	Since
<a>	Anchor (hyperlink)	current	HTML 1 (1991)
<abbr>	Abbreviation	current	HTML 4.01
<acronym>	Acronym (obsolete)	obsolete	HTML 4.01
<address>	Contact address	current	HTML 1
<applet>	Java applet (obsolete)	obsolete	HTML 3.2
<area>	Image map area	current	HTML 3.2
<article>	Self-contained article	current	HTML5
<aside>	Aside (sidebar / tangential content)	current	HTML5
<audio>	Embedded audio	current	HTML5
<b>	Bring attention to (bold)	current	HTML 2.0
<base>	Document base URL	current	HTML 2.0
<basefont>	Base font (obsolete)	obsolete	HTML 3.2
<bdi>	Bidirectional isolate	current	HTML5
<bdo>	Bidirectional text override	current	HTML 4.01
<bgsound>	Background sound (non-standard, obsolete)	obsolete	Internet Explorer extension
<big>	Bigger text (obsolete)	obsolete	HTML 3.2
<blink>	Blinking text (non-standard, obsolete)	obsolete	Netscape extension
<blockquote>	Block quotation	current	HTML 2.0
<body>	Document body	current	HTML 2.0

Element	Meaning	Status	Since
 	Line break	current	HTML 1
<button>	Button	current	HTML 4.01
<canvas>	Graphics canvas	current	HTML5
<caption>	Table caption	current	HTML 3.2
	Centred block (obsolete)	obsolete	HTML 3.2
<cite>	Citation (title of a work)	current	HTML 2.0
<code>	Inline code	current	HTML 2.0
<col>	Table column	current	HTML 4.01
<colgroup>	Table column group	current	HTML 4.01
<content>	Shadow DOM insertion point (obsolete)	obsolete	Shadow DOM v0 (Chrome
<data>	Machine-readable value	current	HTML5
<datalist>	Predefined options for an input	current	HTML5
<dd>	Description details	current	HTML 1
<del>	Deleted text	current	HTML 4.01
<details>	Disclosure widget	current	HTML5 (5.1)
<dfn>	Definition term	current	HTML 3.2
<dialog>	Dialog box	current	HTML 5.2 / Living Standard
<dir>	Directory list (obsolete)	obsolete	HTML 1
	Generic block container	current	HTML 3.2
<dl>	Description list	current	HTML 1
<dt>	Description term	current	HTML 1
	Emphasis	current	HTML 2.0

Element	Meaning	Status	Since
<embed>	External content	current	Netscape extension (1995)
<fencedframe>	Fenced frame (experimental)	experimental	Experimental (Chromium
<fieldset>	Form field group	current	HTML 4.01
<figcaption>	Figure caption	current	HTML5
<figure>	Figure with optional caption	current	HTML5
<font>	Font (obsolete)	obsolete	HTML 3.2
<footer>	Footer	current	HTML5
<form>	Form	current	HTML 2.0
<frame>	Frame (obsolete)	obsolete	Netscape 2 (1996)
<frameset>	Frameset (obsolete)	obsolete	Netscape 2
<h1>	Headings h1 to h6	current	HTML 1
<head>	Document head	current	HTML 2.0
<header>	Header	current	HTML5
<hgroup>	Heading group	current	HTML5 (removed from W3C HTML 5.0
<hr>	Thematic break (horizontal rule)	current	HTML 2.0
<html>	Document root	current	HTML 2.0
<i>	Idiomatic text (italic)	current	HTML 2.0
<iframe>	Inline frame	current	Internet Explorer 3 (1996)
<image>	Image (non-standard alias, obsolete)	obsolete	Never standard
<img>	Image	current	Mosaic (1993)

Element	Meaning	Status	Since
<input>	Input control	current	HTML 2.0
<ins>	Inserted text	current	HTML 4.01
<isindex>	Search index prompt (obsolete)	obsolete	HTML 1
<kbd>	Keyboard input	current	HTML 2.0
<keygen>	Key-pair generator (obsolete)	obsolete	Netscape
<label>	Form control label	current	HTML 4.01
<legend>	Fieldset caption	current	HTML 4.01
	List item	current	HTML 1
<link>	External resource link	current	HTML 2.0
<listing>	Listing (obsolete)	obsolete	HTML 1
<main>	Main content	current	HTML 5.1 (2016)
<map>	Image map	current	HTML 3.2
<mark>	Highlighted (marked) text	current	HTML5
<marquee>	Scrolling text (obsolete)	obsolete	Internet Explorer 2 (1995)
<math>	MathML root	current	HTML5 (inline MathML)
<menu>	Menu (toolbar list)	current	HTML 1
<menuitem>	Menu item (obsolete)	obsolete	HTML5 draft (Firefox only)
<meta>	Metadata	current	HTML 2.0
<meter>	Scalar measurement (gauge)	current	HTML5
<multicol>	Multi-column text (non-standard, obsolete)	obsolete	Netscape 3 only
<nav>	Navigation section	current	HTML5

Element	Meaning	Status	Since
<nextid>	Next identifier (HTML 1 editor hint)	obsolete	HTML 1 / HTML 2.0 (RFC 1866)
<nobr>	No line break (non-standard, obsolete)	obsolete	Netscape / IE extension
<noembed>	Fallback for embed (obsolete)	obsolete	Netscape extension
<noframes>	Fallback for frames (obsolete)	obsolete	HTML 4.01 Frameset
<noscript>	Fallback when scripting is disabled	current	HTML 4.01
<object>	External object	current	HTML 4.01
	Ordered list	current	HTML 1
<optgroup>	Option group	current	HTML 4.01
<option>	Option	current	HTML 2.0
<output>	Calculation or user-action result	current	HTML5
<p>	Paragraph	current	HTML 1
<param>	Object parameter (deprecated)	deprecated	HTML 3.2
<picture>	Picture (responsive image container)	current	HTML 5.1 (2016)
<plaintext>	Plain text (obsolete)	obsolete	HTML 1
<portal>	Portal (experimental, abandoned)	experimental	Chrome experiment (2019-2022)
<pre>	Pre-formatted text	current	HTML 1
<progress>	Progress indicator	current	HTML5

Element	Meaning	Status	Since
<q>	Inline quotation	current	HTML 4.01
<rb>	Ruby base (deprecated)	deprecated	XHTML 1.1 Ruby
<rp>	Ruby fallback parenthesis	current	HTML5
<rt>	Ruby text (annotation)	current	HTML5
<rtc>	Ruby text container (deprecated)	deprecated	HTML 5.1
<ruby>	Ruby annotation	current	XHTML 1.1 (2001)
<s>	Strikethrough (no longer accurate)	current	HTML 3.2
<samp>	Sample output	current	HTML 2.0
<script>	Script	current	HTML 3.2 (reserved)
<search>	Search section	current	Living Standard (2023)
<section>	Generic section	current	HTML5
<select>	Drop-down / list box	current	HTML 2.0
<selected content>	Selected option display (customisable select)	experimental	Living Standard (2025
<shadow>	Shadow root insertion point (obsolete)	obsolete	Shadow DOM v0
<slot>	Shadow DOM slot	current	HTML5 / DOM Standard (2016)
<small>	Side comment (fine print)	current	HTML 3.2
<source>	Media or image source	current	HTML5
<spacer>	Spacer (non-standard, obsolete)	obsolete	Netscape 3-4 only
	Generic inline container	current	HTML 4.01
<strike>	Strikethrough (obsolete)	obsolete	HTML 3.2

Element	Meaning	Status	Since
	Strong importance	current	HTML 2.0
<style>	Embedded style sheet	current	HTML 3.2 (reserved)
<sub>	Subscript	current	HTML 3.2
<summary>	Disclosure summary	current	HTML5 (5.1)
<sup>	Superscript	current	HTML 3.2
<svg>	Scalable Vector Graphics root	current	HTML5 (inline SVG)
<table>	Table	current	HTML 3.2
<tbody>	Table body	current	HTML 4.01
<td>	Table data cell	current	HTML 3.2
<template>	Content template	current	HTML5 (2013)
<textarea>	Multi-line text input	current	HTML 2.0
<tfoot>	Table footer	current	HTML 4.01
<th>	Table header cell	current	HTML 3.2
<thead>	Table header	current	HTML 4.01
<time>	Date / time	current	HTML5
<title>	Document title	current	HTML 1
<tr>	Table row	current	HTML 3.2
<track>	Text track for media	current	HTML5
<tt>	Teletype text (obsolete)	obsolete	HTML 2.0
<u>	Unarticulated annotation (underline)	current	HTML 3.2
	Unordered list	current	HTML 1
<var>	Variable	current	HTML 2.0

Element	Meaning	Status	Since
<video>	Embedded video	current	HTML5
<wbr>	Word break opportunity	current	Netscape / IE extension
<xmp>	Example text (obsolete)	obsolete	HTML 1

Elements by category

Category	Elements
Content sectioning	<address>, <article>, <aside>, <footer>, <h1>, <header>, <hgroup>, <main>, <nav>, <search>, <section>
Demarcating edits	<del>, <ins>
Document metadata	<base>, <head>, <link>, <meta>, <style>, <title>
Embedded content	<embed>, <fencedframe>, <iframe>, <object>, <param>, <portal>
Embedded content (MathML)	<math>
Embedded content (SVG)	<svg>
Forms	<button>, <datalist>, <fieldset>, <form>, <input>, <label>, <legend>, <meter>, <optgroup>, <option>, <output>, <progress>, <select>, <selectedcontent>, <textarea>
Image and multimedia	<area>, <audio>, <img>, <map>, <picture>, <source>, <track>, <video>
Interactive elements	<details>, <dialog>, <summary>
Main root	<html>
Obsolete	<nextid>
Obsolete embedded content	<applet>, <bgsound>, <image>, <noembed>
Obsolete forms	<isindex>, <keygen>
Obsolete frames	<frame>, <frameset>, <noframes>
Obsolete interactive	<menuitem>

Category	Elements
Obsolete presentational	<basefont>, <big>, <blink>, , <font>, <marquee>, <multicol>, <nobr>, <spacer>, <strike>, <tt>
Obsolete text content	<dir>, <listing>, <plaintext>, <xmp>
Obsolete text-level	<acronym>
Obsolete web components	<content>, <shadow>
Scripting	<canvas>, <noscript>, <script>
Scripting / web components	<template>
Sectioning root	<body>
Table content	<caption>, <col>, <colgroup>, <table>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>
Text content	<blockquote>, <dd>, , <dl>, <dt>, <figcaption>, <figure>, <hr>, , <menu>, , <p>, <pre>,
Text-level semantics	<a>, <abbr>, <b>, <bdi>, <bdo>, , <cite>, <code>, <data>, <dfn>, , <i>, <kbd>, <mark>, <q>, <s>, <samp>, <small>, , , <sub>, <sup>, <time>, <u>, <var>, <wbr>
Text-level semantics (ruby)	<rb>, <rp>, <rt>, <rtc>, <ruby>
Web components	<slot>

Quick card: <a>

Anchor (hyperlink)

The <a> element (anchor) creates a hyperlink to another web page, a file, a location within the same page, an email address, a telephone number, or any other resource that can be identified by a URL. Hyperlinks are the defining feature of the World Wide Web and <a> was one of the very first elements created by Tim Berners-Lee in 1991.

At a glance

Status	CURRENT
Versions	HTML 1 (1991), HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Text-level semantics
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	href, target, rel, download, hreflang, type, referrerpolicy, ping, attributionsrc, charset, coords, name, rev, shape
Related	<area>, <link>, <button>, <nav>

Minimal example

```
<p>Read the <a href="https://developer.mozilla.org/">MDN
documentation</a>.</p>
<p>See our <a href="about.html">About page</a>.</p>
<p>Jump to the <a href="#footer">bottom of this page</a>.</p>
```

Most common mistake

Nesting an <a> inside another <a>, or putting a <button> inside an <a>.

<a> — Anchor (hyperlink)

Category: Text-level semantics | Status: CURRENT | Versions: HTML 1 (1991), HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <a> element (anchor) creates a hyperlink to another web page, a file, a location within the same page, an email address, a telephone number, or any other resource that can be identified by a URL. Hyperlinks are the defining feature of the World Wide Web and <a> was one of the very first elements created by Tim Berners-Lee in 1991.

The content of the <a> element is what the visitor sees and clicks. It is usually text, but in HTML5 it may also be an image, a whole card of content, or any other flow content, as long as the link does not contain another link or an interactive element such as a button.

If the href attribute is missing the element is a placeholder: it is rendered as plain text, is not focusable and is not announced as a link by screen readers. This is useful, for example, for the current page in a navigation menu.

In HTML 4 the <a> element was also used to define named anchors (<a name="top">) that other links could jump to. In HTML5 the name attribute is obsolete; use the id attribute on any element instead.

Syntax

```
<a href="URL">link text</a>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, interactive content (when href is present), palpable content
Permitted content	Transparent (whatever the parent allows), but it must not contain interactive content or another <a>
Permitted parents	Any element that accepts phrasing content or flow content
Tag omission	Neither the start tag nor the end tag may be omitted
DOM interface	HTMLAnchorElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
href	URL	The address the link points to. It may be absolute (https://example.com/page), relative (about.html, ../images/photo.jpg), a fragment (#section-2), or a special scheme (mailto:, tel:, sms:, javascript:). Without href the element is not a link.	HTML 1

Attribute	Values	Description	Since
target	_self | _blank | _parent | _top | frame-name	Where to open the linked document. _self (default) opens it in the same browsing context; _blank opens a new tab or window; _parent opens it in the parent frame; _top opens it in the full window, replacing all frames. A custom name targets an <iframe> with that name.	HTML 4.01
rel	space-separated link types	The relationship between the current document and the linked document. Common values: nofollow, noopener, noreferrer, external, alternate, author, bookmark, help, license, next, prev, search, tag. See the link types table in Part 9.	HTML 4.01
download	empty or filename	Instructs the browser to download the resource instead of navigating to it. If a value is given it is used as the suggested file name. Only works for same-origin URLs and blob:/data: URLs.	HTML5
hreflang	BCP 47 language tag	The language of the linked document, for example en, ar, fr-CA. Purely advisory.	HTML 4.01
type	MIME type	The media type of the linked resource, for example application/pdf. Advisory only.	HTML 4.01

Attribute	Values	Description	Since
referrerpolicy	no-referrer | no-referrer-when-downgrade | origin | origin-when-cross-origin | same-origin | strict-origin | strict-origin-when-cross-origin | unsafe-url	How much referrer information is sent when following the link.	HTML5
ping	space-separated URLs	A list of URLs that receive a POST request with the body PING when the link is followed. Used for tracking.	HTML5
attributionsrc	empty or URL	Experimental: registers an attribution source for the Attribution Reporting API.	Living Standard
charset	character encoding	Obsolete. The character encoding of the linked resource. Use the HTTP Content-Type header instead.	HTML 4.01 (obsolete in HTML5)
coords	comma-separated numbers	Obsolete. Coordinates for use with shape in old image maps. Use <area> instead.	HTML 4.01 (obsolete in HTML5)
name	text	Obsolete. Defined a named anchor that could be linked to with #name. Use id instead.	HTML 1 (obsolete in HTML5)
rev	link types	Obsolete. Reverse relationship. Use rel instead.	HTML 4.01 (obsolete in HTML5)

Attribute	Values	Description	Since
shape	rect | circle | poly | default	Obsolete. Shape of a clickable region. Use <area> instead.	HTML 4.01 (obsolete in HTML5)

<a>: attribute by attribute

Each attribute of <a> explained in detail, with a minimal example you can copy.

href

Values: URL | Since: HTML 1

The address the link points to. It may be absolute (https://example.com/page), relative (about.html, ../images/photo.jpg), a fragment (#section-2), or a special scheme (mailto:, tel:, sms:, javascript:). Without href the element is not a link.

Write href="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<a href="https://example.com/page.html">...</a>
```

target

Values: _self | _blank | _parent | _top | frame-name | Since: HTML 4.01

Where to open the linked document. _self (default) opens it in the same browsing context; _blank opens a new tab or window; _parent opens it in the parent frame; _top opens it in the full window, replacing all frames. A custom name targets an <iframe> with that name.

Write target="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<a target="_self">...</a>
```

rel

Values: space-separated link types | Since: HTML 4.01

The relationship between the current document and the linked document. Common values: nofollow, noopener, noreferrer, external, alternate, author, bookmark, help, license, next, prev, search, tag. See the link types table in Part 9.

Write rel="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<a rel="value">...</a>
```

download

Values: empty or filename | Since: HTML5

Instructs the browser to download the resource instead of navigating to it. If a value is given it is used as the suggested file name. Only works for same-origin URLs and blob:/data: URLs.

Write download="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<a download="empty">...</a>
```

hreflang

Values: BCP 47 language tag | Since: HTML 4.01

The language of the linked document, for example en, ar, fr-CA. Purely advisory.

Write hreflang="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<a hreflang="en">...</a>
```

type

Values: MIME type | Since: HTML 4.01

The media type of the linked resource, for example application/pdf. Advisory only.

Write type="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<a type="text/plain">...</a>
```

referrerpolicy

Values: no-referrer | no-referrer-when-downgrade | origin | origin-when-cross-origin | same-origin | strict-origin | strict-origin-when-cross-origin | unsafe-url | Since: HTML5

How much referrer information is sent when following the link.

Write referrerpolicy="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<a referrerpolicy="no-referrer">...</a>
```

ping

Values: space-separated URLs | Since: HTML5

A list of URLs that receive a POST request with the body PING when the link is followed. Used for tracking.

Write ping="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<a ping="space-separated URLs">...</a>
```

attributionsrc

Values: empty or URL | Since: Living Standard

Experimental: registers an attribution source for the Attribution Reporting API.

Write attributionsrc="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<a attributionsrc="empty">...</a>
```

charset

Values: character encoding | Since: HTML 4.01 (obsolete in HTML5)

Obsolete. The character encoding of the linked resource. Use the HTTP Content-Type header instead.

Write charset="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<a charset="character encoding">...</a>
```

coords

Values: comma-separated numbers | Since: HTML 4.01 (obsolete in HTML5)

Obsolete. Coordinates for use with shape in old image maps. Use <area> instead.

Write coords="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<a coords="3">...</a>
```

name

Values: text | Since: HTML 1 (obsolete in HTML5)

Obsolete. Defined a named anchor that could be linked to with #name. Use id instead.

Write name="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<a name="value">...</a>
```

rev

Values: link types | Since: HTML 4.01 (obsolete in HTML5)

Obsolete. Reverse relationship. Use rel instead.

Write rev="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<a rev="link types">...</a>
```

shape

Values: rect | circle | poly | default | Since: HTML 4.01 (obsolete in HTML5)

Obsolete. Shape of a clickable region. Use <area> instead.

Write shape="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<a shape="rect">...</a>
```

<a>: worked examples

Basic links

```
<p>Read the <a href="https://developer.mozilla.org/">MDN
documentation</a>.</p>
<p>See our <a href="about.html">About page</a>.</p>
<p>Jump to the <a href="#footer">bottom of this page</a>.</p>
```

The first link is absolute, the second is relative to the current page, and the third is a fragment link that scrolls to the element whose id is footer.

Opening in a new tab safely

```
<a href="https://example.com" target="_blank" rel="noopener
noreferrer">
  Example (opens in a new tab)
</a>
```

When you use target="_blank" add rel="noopener" so the new page cannot access your page through window.opener. Modern browsers do this automatically, but adding it is still good practice. Tell the user that the link opens in a new tab.

Email, telephone and download links

```
<a href="mailto:info@example.com?subject=Hello">Email us</a>
<a href="tel:+201001234567">Call us: 010 0123 4567</a>
<a href="report.pdf" download="annual-report-2026.pdf">Download the
report (PDF)</a>
```

mailto: opens the visitor's email program; tel: dials on a phone; download forces a save dialog with the suggested file name.

A link wrapping a whole card (HTML5)

```
<a href="product.html" class="card">
  <img src="shoe.jpg" alt="Red running shoe">
  <h3>Running shoe</h3>
  <p>450 EGP</p>
</a>
```

Since HTML5 an anchor may contain block-level content. The entire card becomes clickable.

A placeholder link for the current page

```
<nav>
  <a>Home</a>
  <a href="shop.html">Shop</a>
  <a href="contact.html">Contact</a>
</nav>
```

Home has no href, so it is shown as text and is not focusable, which is correct for the page the visitor is already on. You could also add aria-current="page" to a real link instead.

Default browser CSS

```
a:-webkit-any-link { color: -webkit-link; cursor: pointer; text-
decoration: underline; }
```

Accessibility

- Link text must make sense on its own. Screen reader users often read a list of all links on a page; 'click here' or 'read more' tells them nothing. Prefer 'Download the 2026 price list'.
- Do not use the same link text for links that go to different places.
- When a link contains only an image, the image's alt text becomes the link text, so it must describe the destination.
- Links should look different from ordinary text (usually underlined) and have a visible focus outline.
- Do not use javascript: URLs; use a <button> for actions that are not navigation.

Common mistakes

- Nesting an <a> inside another <a>, or putting a <button> inside an <a>.
- Using an <a> without href as a button. Use <button> instead.

- Forgetting rel="noopener" with target="_blank" on old browsers.
- Using onclick="location.href=..." on a instead of a real link, which breaks keyboard access, right-click and search engines.
- Writing the URL with spaces or with backslashes instead of forward slashes.

See also

<area>, <link>, <button>, <nav>

Quick card: <abbr>

Abbreviation

The <abbr> element marks an abbreviation or acronym. The optional title attribute holds the full expansion, which most browsers show as a tooltip when the mouse hovers over the text.

At a glance

Status	CURRENT
Versions	HTML 4.01, HTML5
Category	Text-level semantics
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	title
Related	<dfn>, <acronym>

Minimal example

```
<p>The <abbr title="World Health Organization">WHO</abbr> was founded
in 1948.</p>
```

Most common mistake

Using <acronym>, which is obsolete.

<abbr> — Abbreviation

Category: Text-level semantics | Status: CURRENT | Versions: HTML 4.01, HTML5

Description

The <abbr> element marks an abbreviation or acronym. The optional title attribute holds the full expansion, which most browsers show as a tooltip when the mouse hovers over the text.

Use <abbr> the first time an abbreviation appears in a document, ideally writing the expansion in the text as well, because tooltips are not available on touch screens and are not read by every screen reader.

HTML 4.01 also had an <acronym> element for pronounceable abbreviations such as NASA. It was removed in HTML5; use <abbr> for both.

Syntax

```
<abbr title="expansion">ABBR</abbr>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, palpable content
Permitted content	Phrasing content
Permitted parents	Any element that accepts phrasing content

Property	Value
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
title	text	The full expansion of the abbreviation. On <abbr> this attribute has a specific meaning and should contain nothing else.	HTML 4.01

<abbr>: attribute by attribute

Each attribute of <abbr> explained in detail, with a minimal example you can copy.

title

Values: text | Since: HTML 4.01

The full expansion of the abbreviation. On <abbr> this attribute has a specific meaning and should contain nothing else.

Write title="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<abbr title="value">...</abbr>
```

<abbr>: worked examples

Abbreviation with tooltip

```
<p>The <abbr title="World Health Organization">WHO</abbr> was founded
in 1948.</p>
```

Hovering WHO shows 'World Health Organization'.

Defining an abbreviation with <dfn>

```
<p><dfn><abbr title="HyperText Markup Language">HTML</abbr></dfn> is
the language of the web.</p>
```

Wrapping in <dfn> marks this as the place where the term is defined.

Styling the dotted underline

```
<style>
  abbr[title] { text-decoration: underline dotted; cursor: help; }
</style>
<p>Pages are served over <abbr title="HyperText Transfer Protocol
Secure">HTTPS</abbr>.</p>
```

Most browsers already show a dotted underline; this rule makes it consistent.

Default browser CSS

```
abbr[title] { text-decoration: underline dotted; }
```

Accessibility

- Provide the expansion in plain text at least once; do not rely on the tooltip alone.
- Some screen readers can be set to read the title attribute, but it is off by default.

Common mistakes

- Using <acronym>, which is obsolete.
- Putting long explanations in title; it is for the expansion only.

See also

<dfn>, <acronym>

Quick card: <acronym>

Acronym (obsolete)

The <acronym> element marked an acronym: an abbreviation pronounced as a word, such as NASA or laser. HTML5 removed it because the distinction from <abbr> was confusing and browsers treated the two identically.

At a glance

Status	OBSOLETE
Versions	HTML 4.01; obsolete in HTML5
Category	Obsolete text-level
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	title
Related	<abbr>

Minimal example

```
<!-- HTML 4.01 -->
<acronym title="National Aeronautics and Space Administration">NASA</
acronym>

<!-- HTML5 -->
<abbr title="National Aeronautics and Space Administration">NASA</
abbr>
```

Most common mistake

Using it at all in new pages.

<acronym> — Acronym (obsolete)

Category: Obsolete text-level | Status: OBSOLETE | Versions: HTML 4.01; obsolete in HTML5

Description

The <acronym> element marked an acronym: an abbreviation pronounced as a word, such as NASA or laser. HTML5 removed it because the distinction from <abbr> was confusing and browsers treated the two identically.

Replace every <acronym> with <abbr>.

Syntax

```
<acronym title="expansion">NASA</acronym>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Phrasing content (historical)
Permitted content	Phrasing content
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
title	text	The expansion of the acronym.	HTML 4.01

<acronym>: attribute by attribute

Each attribute of <acronym> explained in detail, with a minimal example you can copy.

title

Values: text | Since: HTML 4.01

The expansion of the acronym.

Write title="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<acronym title="value">...</acronym>
```

<acronym>: worked examples

Old code and its replacement

```
<!-- HTML 4.01 -->
<acronym title="National Aeronautics and Space Administration">NASA</
acronym>

<!-- HTML5 -->
<abbr title="National Aeronautics and Space Administration">NASA</
abbr>
```

Default browser CSS

```
acronym { text-decoration: underline dotted; }
```

Accessibility

- Same as <abbr>.

Common mistakes

- Using it at all in new pages.

See also

<abbr>

Quick card: <address>

Contact address

The <address> element indicates that its content provides contact information for a person, people or an organisation. When placed inside an <article> it gives the contact details of the article's author; when placed in the page <footer> or <body> it gives the contact details for the whole document.

At a glance

Status	CURRENT
Versions	HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Content sectioning
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	None (global attributes only)
Related	<footer>, <article>, <a>

Minimal example

```
<footer>
  <address>
    Written by <a href="mailto:jane@example.com">Jane Doe</a>.<br>
    Visit us at:<br>
    Example Ltd.<br>
    12 Nile Street<br>
    Giza, Egypt
  </address>
</footer>
```

Most common mistake

Using <address> for every postal address on a page (for example in an order form).

<address> — Contact address

Category: Content sectioning | Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <address> element indicates that its content provides contact information for a person, people or an organisation. When placed inside an <article> it gives the contact details of the article's author; when placed in the page <footer> or <body> it gives the contact details for the whole document.

The contact information may be any kind: physical address, email, telephone, URL, social media handle, geographic coordinates. Despite its name, <address> is not meant for arbitrary postal addresses (such as the shipping address in an order); it is only for contact details of the author or owner of the content.

Browsers display <address> in italics by default, exactly as they did in 1991.

Syntax

```
<address>contact information</address>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	Flow content, palpable content
Permitted content	Flow content, but no heading content, no sectioning content, and no <header>, <footer> or nested <address>

Property	Value
Permitted parents	Any element that accepts flow content
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<address>: worked examples

Contact details in the page footer

```
<footer>
  <address>
    Written by <a href="mailto:jane@example.com">Jane Doe</a>.<br>
    Visit us at:<br>
    Example Ltd.<br>
    12 Nile Street<br>
    Giza, Egypt
  </address>
</footer>
```

Author contact inside an article

```
<article>
  <h2>Learning HTML</h2>
  <p>...</p>
  <address>Contact the author: <a href="tel:+201000000000">+20 100
000 0000</a></address>
</article>
```

Here the address applies to the article only.

Default browser CSS

```
address { display: block; font-style: italic; }
```

Accessibility

- Screen readers may announce the element as 'contact information', which helps users find it.

Common mistakes

- Using <address> for every postal address on a page (for example in an order form).
- Placing headings or sections inside it.

See also

<footer>, <article>, <a>

Quick card: <applet>

Java applet (obsolete)

The <applet> element embedded a Java applet in the page. Applets were small Java programs that ran inside the browser with the help of a plug-in. Java applets were popular in the late 1990s but were slow, insecure and not supported on mobile devices. HTML 4.01 deprecated <applet> in favour of <object>, and HTML5 removed it entirely. No modern browser runs applets.

At a glance

Status	OBSOLETE
Versions	HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5
Category	Obsolete embedded content
Closing tag	Required unless noted under Tag omission
Display	inline-block
Own attributes	code, codebase, archive, object, alt, name, width, align, hspace
Related	<object>, <embed>, <canvas>

Minimal example

```
<applet code="Clock.class" width="200" height="200">
  <param name="timezone" value="Africa/Cairo">
  Your browser does not support Java applets.
</applet>
```

Most common mistake

Any use in a modern page.

<applet> — Java applet (obsolete)

Category: Obsolete embedded content | Status: OBSOLETE | Versions: HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

Description

The <applet> element embedded a Java applet in the page. Applets were small Java programs that ran inside the browser with the help of a plug-in. Java applets were popular in the late 1990s but were slow, insecure and not supported on mobile devices. HTML 4.01 deprecated <applet> in favour of <object>, and HTML5 removed it entirely. No modern browser runs applets.

Syntax

```
<applet code="MyApplet.class" width="300" height="200"></applet>
```

Technical summary

Property	Value
Void element	No
Default display	inline-block
Content categories	Embedded content (historical)
Permitted content	Zero or more <param> elements followed by fallback content
Permitted parents	Any element that accepts embedded content
Tag omission	Neither tag may be omitted
DOM interface	HTMLUnknownElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
code	class file name	The name of the compiled applet class file.	HTML 3.2
codebase	URL	The base URL for the applet's class files.	HTML 3.2
archive	comma-separated URLs	JAR archives to preload.	HTML 4.01
object	file name	A serialised applet file.	HTML 4.01
alt	text	Alternative text for browsers without Java.	HTML 3.2
name	text	A name so that applets on the same page can find each other.	HTML 3.2
width / height	pixels	Size of the applet display area.	HTML 3.2
align	left | right | top | middle | bottom	Alignment relative to surrounding text.	HTML 3.2
hspace / vspace	pixels	Horizontal and vertical margins.	HTML 3.2

<applet>: attribute by attribute

Each attribute of <applet> explained in detail, with a minimal example you can copy.

code

Values: class file name | Since: HTML 3.2

The name of the compiled applet class file.

Write code="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<applet code="class file name">...</applet>
```

codebase

Values: URL | Since: HTML 3.2

The base URL for the applet's class files.

Write codebase="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<applet codebase="https://example.com/page.html">...</applet>
```

archive

Values: comma-separated URLs | Since: HTML 4.01

JAR archives to preload.

Write archive="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<applet archive="comma-separated URLs">...</applet>
```

object

Values: file name | Since: HTML 4.01

A serialised applet file.

Write object="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<applet object="file name">...</applet>
```

alt

Values: text | Since: HTML 3.2

Alternative text for browsers without Java.

Write alt="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<applet alt="value">...</applet>
```

name

Values: text | Since: HTML 3.2

A name so that applets on the same page can find each other.

Write name="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<applet name="value">...</applet>
```

width / height

Values: pixels | Since: HTML 3.2

Size of the applet display area.

Write width="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<applet width="3">...</applet>
```

align

Values: left | right | top | middle | bottom | Since: HTML 3.2

Alignment relative to surrounding text.

Write align="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<applet align="left">...</applet>
```

hspace / vspace

Values: pixels | Since: HTML 3.2

Horizontal and vertical margins.

Write hspace="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<applet hspace="3">...</applet>
```

<applet>: worked examples

Historical example

```
<applet code="Clock.class" width="200" height="200">
  <param name="timezone" value="Africa/Cairo">
  Your browser does not support Java applets.
</applet>
```

For comparison, modern pages implement such features with JavaScript and <canvas>.

Default browser CSS

```
applet { display: inline-block; }
```

Accessibility

- Applets were inaccessible to assistive technology.

Common mistakes

- Any use in a modern page.

See also

<object>, <embed>, <canvas>

Quick card: <area>

Image map area

The <area> element defines a clickable region inside an image map. An image map is an image (<img usemap="#name">) linked to a <map name="name"> element that contains one or more <area> elements. Each area has a shape and coordinates, and behaves like a hyperlink.

At a glance

Status	CURRENT
Versions	HTML 3.2, HTML 4.01, HTML5
Category	Image and multimedia
Closing tag	None (void element)
Display	inline
Own attributes	alt, coords, shape, href, target, download, rel, ping, referrerpolicy, nohref, type
Related	<map>, <img>, <a>

Minimal example

```
<img src="map.png" alt="Map of the office" usemap="#office"
width="400" height="300">
<map name="office">
  <area shape="rect" coords="0,0,200,150" href="kitchen.html"
alt="Kitchen">
  <area shape="circle" coords="300,75,50" href="meeting.html"
alt="Meeting room">
  <area shape="poly" coords="0,150,200,150,100,300" href="desks.html"
alt="Desks">
  <area shape="default" href="office.html" alt="Whole office">
</map>
```

Most common mistake

Forgetting the # in usemap="#name".

<area> — Image map area

Category: Image and multimedia | Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

Description

The <area> element defines a clickable region inside an image map. An image map is an image (<img usemap="#name">) linked to a <map name="name"> element that contains one or more <area> elements. Each area has a shape and coordinates, and behaves like a hyperlink.

<area> is a void element: it has no content and no closing tag. It may only be used inside <map>.

Syntax

```
<area shape="rect" coords="x1,y1,x2,y2" href="URL" alt="text">
```

Technical summary

Property	Value
Void element	Yes (no closing tag)
Default display	inline
Content categories	Flow content, phrasing content
Permitted content	None (void element)
Permitted parents	<map> (the <area> may be a descendant of <map> at any depth, as long as there is no intervening <a>)
Tag omission	No end tag
DOM interface	HTMLAreaElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
alt	text	Alternative text for the area. Required when href is present so that the link has an accessible name.	HTML 3.2
coords	comma-separated numbers	The coordinates of the shape in CSS pixels measured from the top-left corner of the image. rect: x1,y1,x2,y2 (top-left and bottom-right). circle: x,y,radius. poly: x1,y1,x2,y2,... (any number of points).	HTML 3.2
shape	rect | circle | poly | default	The shape of the region. default covers the whole image.	HTML 3.2
href	URL	The destination of the link.	HTML 3.2
target	_self | _blank | _parent | _top | name	Where to open the destination.	HTML 4.01
download	empty or filename	Download the resource instead of navigating.	HTML5
rel	link types	Relationship of the linked resource.	HTML5
ping	URLs	URLs to ping when the link is followed.	HTML5
referrerpolicy	referrer policy keyword	Referrer policy for the navigation.	HTML5
nohref	boolean	Obsolete. Indicated the area had no link. Simply omit href instead.	HTML 3.2 (obsolete)

Attribute	Values	Description	Since
type	MIME type	Obsolete in HTML5. Type of the linked resource.	HTML 4.01

<area>: attribute by attribute

Each attribute of <area> explained in detail, with a minimal example you can copy.

alt

Values: text | Since: HTML 3.2

Alternative text for the area. Required when href is present so that the link has an accessible name.

Write alt="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<area alt="value">
```

coords

Values: comma-separated numbers | Since: HTML 3.2

The coordinates of the shape in CSS pixels measured from the top-left corner of the image. rect: x1,y1,x2,y2 (top-left and bottom-right). circle: x,y,radius. poly: x1,y1,x2,y2,... (any number of points).

Write coords="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<area coords="3">
```

shape

Values: rect | circle | poly | default | Since: HTML 3.2

The shape of the region. default covers the whole image.

Write shape="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<area shape="rect">
```

href

Values: URL | Since: HTML 3.2

The destination of the link.

Write href="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<area href="https://example.com/page.html">
```

target

Values: _self | _blank | _parent | _top | name | Since: HTML 4.01

Where to open the destination.

Write target="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<area target="_self">
```

download

Values: empty or filename | Since: HTML5

Download the resource instead of navigating.

Write download="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<area download="empty">
```

rel

Values: link types | Since: HTML5

Relationship of the linked resource.

Write rel="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<area rel="link types">
```

ping

Values: URLs | Since: HTML5

URLs to ping when the link is followed.

Write ping="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<area ping="https://example.com/page.html">
```

referrerpolicy

Values: referrer policy keyword | Since: HTML5

Referrer policy for the navigation.

Write referrerpolicy="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<area referrerpolicy="referrer policy keyword">
```

nohref

Values: boolean | Since: HTML 3.2 (obsolete)

Obsolete. Indicated the area had no link. Simply omit href instead.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<area nohref>
```

type

Values: MIME type | Since: HTML 4.01

Obsolete in HTML5. Type of the linked resource.

Write type="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<area type="text/plain">
```

<area>: worked examples

A world map with three clickable regions

```
<img src="map.png" alt="Map of the office" usemap="#office"
width="400" height="300">
<map name="office">
  <area shape="rect" coords="0,0,200,150" href="kitchen.html"
alt="Kitchen">
  <area shape="circle" coords="300,75,50" href="meeting.html"
alt="Meeting room">
  <area shape="poly" coords="0,150,200,150,100,300" href="desks.html"
alt="Desks">
  <area shape="default" href="office.html" alt="Whole office">
</map>
```

The rectangle covers the top-left quarter, the circle has centre (300,75) and radius 50, and the polygon is a triangle. The default area catches clicks anywhere else.

Default browser CSS

```
area { display: inline; }
```

Accessibility

- Every <area> with href needs a meaningful alt.
- Image maps do not scale well on small screens; consider SVG with real links instead.

Common mistakes

- Forgetting the # in usemap="#name".
- Coordinates that do not match the displayed image size.
- Writing a closing </area> tag.

See also

<map>, <img>, <a>

Quick card: <article>

Self-contained article

The <article> element represents a complete, self-contained piece of content that would make sense on its own if it were distributed independently, for example in an RSS feed. Typical uses are a blog post, a news story, a forum post, a product card, a user comment or an interactive widget.

At a glance

Status	CURRENT
Versions	HTML5
Category	Content sectioning
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	None (global attributes only)
Related	<section>, <aside>, <header>, <footer>, <main>, <nav>

Minimal example

```
<article>
  <header>
    <h2>How I learned HTML</h2>
    <p>Posted <time datetime="2026-09-11">11 September 2026</time> by
Ahmed</p>
  </header>
  <p>It started with a single footer tag...</p>
  <footer>
    <p>Tags: html, learning</p>
  </footer>
</article>
```

Most common mistake

Using <article> for every box on the page; use <section> or for content that is not self-contained.

<article> — Self-contained article

Category: Content sectioning | Status: CURRENT | Versions: HTML5

Description

The <article> element represents a complete, self-contained piece of content that would make sense on its own if it were distributed independently, for example in an RSS feed. Typical uses are a blog post, a news story, a forum post, a product card, a user comment or an interactive widget.

An <article> usually has its own heading, and may have its own <header>, <footer> and <address>. Articles can be nested: comments on a blog post are articles inside the post's article.

The test for choosing <article> rather than <section> or is: 'Could this piece be copied to another site and still make sense?' If yes, it is an article.

Syntax

```
<article>...</article>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	Flow content, sectioning content, palpable content
Permitted content	Flow content

Property	Value
Permitted parents	Any element that accepts flow content, but not inside <address>
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<article>: worked examples

A blog post

```
<article>
  <header>
    <h2>How I learned HTML</h2>
    <p>Posted <time datetime="2026-09-11">11 September 2026</time> by
Ahmed</p>
  </header>
  <p>It started with a single footer tag...</p>
  <footer>
    <p>Tags: html, learning</p>
  </footer>
</article>
```

Nested articles for comments

```
<article>
  <h2>Post title</h2>
  <p>Post text.</p>
  <section>
    <h3>Comments</h3>
    <article>
      <p>Great post!</p>
      <footer>- Sara</footer>
    </article>
  </section>
</article>
```

Product cards in a shop

```
<article class="product">
  <img src="book.jpg" alt="Cover of Learn HTML">
  <h3>Learn HTML</h3>
  <p>120 EGP</p>
  <button>Add to cart</button>
</article>
```

Default browser CSS

```
article { display: block; }
```

Accessibility

- Screen readers expose <article> with the role 'article' and may let users jump between articles.
- Give each article a heading so it can be identified.

Common mistakes

- Using <article> for every box on the page; use <section> or for content that is not self-contained.
- Omitting a heading inside the article.

See also

<section>, <aside>, <header>, <footer>, <main>, <nav>

Quick card: <aside>

Aside (sidebar / tangential content)

The <aside> element represents content that is only indirectly related to the main content around it. It is often displayed as a sidebar or a call-out box: pull quotes, related links, advertising, author biographies, glossary definitions, or a list of other articles.

At a glance

Status	CURRENT
Versions	HTML5
Category	Content sectioning
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	None (global attributes only)
Related	<article>, <section>, <main>, <nav>

Minimal example

```
<main>
  <article>
    <h1>The Nile</h1>
    <p>The Nile is the longest river in Africa...</p>
  </article>
  <aside>
    <h2>Related</h2>
    <ul>
      <li><a href="aswan.html">Aswan Dam</a></li>
      <li><a href="delta.html">Nile Delta</a></li>
    </ul>
  </aside>
</main>
```

Most common mistake

Using <aside> for parenthetical text inside a paragraph; use parentheses or for that.

<aside> — Aside (sidebar / tangential content)

Category: Content sectioning | Status: CURRENT | Versions: HTML5

Description

The <aside> element represents content that is only indirectly related to the main content around it. It is often displayed as a sidebar or a call-out box: pull quotes, related links, advertising, author biographies, glossary definitions, or a list of other articles.

Inside an <article>, an <aside> holds content related to that article. Directly inside <body> or <main>, it holds content related to the page as a whole, such as a site-wide sidebar.

Syntax

```
<aside>...</aside>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	Flow content, sectioning content, palpable content
Permitted content	Flow content
Permitted parents	Any element that accepts flow content, but not inside <address>
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<aside>: worked examples

A sidebar with related links

```
<main>
  <article>
    <h1>The Nile</h1>
    <p>The Nile is the longest river in Africa...</p>
  </article>
  <aside>
    <h2>Related</h2>
    <ul>
      <li><a href="aswan.html">Aswan Dam</a></li>
      <li><a href="delta.html">Nile Delta</a></li>
    </ul>
  </aside>
</main>
```

A pull quote inside an article

```
<article>
  <p>Learning takes time, but every tag you learn is a tool you keep.
</p>
  <aside><q>Every tag you learn is a tool you keep.</q></aside>
  <p>...</p>
</article>
```

Default browser CSS

```
aside { display: block; }
```

Accessibility

- Exposed as a 'complementary' landmark so users can skip to or over it.

Common mistakes

- Using <aside> for parenthetical text inside a paragraph; use parentheses or for that.
- Putting the main content in an <aside>.

See also

<article>, <section>, <main>, <nav>

Quick card: <audio>

Embedded audio

The <audio> element embeds sound content: music, podcasts, sound effects or recorded speech. The source may be given with the src attribute or with one or more <source> child elements so that the browser can choose a format it supports. Content placed inside the element after the <source> elements is shown only by browsers that do not support <audio> at all.

At a glance

Status	CURRENT
Versions	HTML5
Category	Image and multimedia
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	src, controls, autoplay, loop, muted, preload, crossorigin, controlslist, disableremoteplayback
Related	<video>, <source>, <track>, <embed>, <object>

Minimal example

```
<audio src="song.mp3" controls>
  Your browser does not support the audio element.
  <a href="song.mp3">Download the song</a>.
</audio>
```

Most common mistake

Expecting autoplay with sound to work.

<audio> — Embedded audio

Category: Image and multimedia | Status: CURRENT | Versions: HTML5

Description

The <audio> element embeds sound content: music, podcasts, sound effects or recorded speech. The source may be given with the src attribute or with one or more <source> child elements so that the browser can choose a format it supports. Content placed inside the element after the <source> elements is shown only by browsers that do not support <audio> at all.

By default nothing is displayed. Add the controls attribute to show the browser's built-in play, pause, volume and progress controls, or control playback from JavaScript with the HTMLMediaElement methods play() and pause().

Browsers block automatic playback with sound until the user has interacted with the page, so autoplay usually works only together with muted.

Syntax

```
<audio src="file.mp3" controls></audio>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, embedded content; interactive and palpable if controls is present

Property	Value
Permitted content	If src is present: zero or more <track> elements then transparent content with no media elements. If src is absent: zero or more <source>, then zero or more <track>, then transparent content with no media elements
Permitted parents	Any element that accepts embedded content
Tag omission	Neither tag may be omitted
DOM interface	HTMLAudioElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
src	URL	The URL of the audio file. Alternatively use <source> children.	HTML5
controls	boolean	Show the browser's playback controls.	HTML5
autoplay	boolean	Start playing as soon as enough data has loaded. Usually blocked unless muted.	HTML5
loop	boolean	Restart from the beginning when the end is reached.	HTML5
muted	boolean	Start with the sound muted.	HTML5
preload	none | metadata | auto	A hint about how much to download before playback: nothing, only metadata such as duration (default in most browsers), or the whole file.	HTML5

Attribute	Values	Description	Since
crossorigin	anonymous | use-credentials	How to handle cross-origin requests, needed when the audio will be processed with the Web Audio API or canvas.	HTML5
controlslist	nodownload | nofullscreen | noremoteplayback	Hides specific built-in controls (non-standard, Chromium).	Living Standard
disableremoteplayback	boolean	Disables casting to remote devices.	Living Standard

<audio>: attribute by attribute

Each attribute of <audio> explained in detail, with a minimal example you can copy.

src

Values: URL | Since: HTML5

The URL of the audio file. Alternatively use <source> children.

Write src="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<audio src="https://example.com/page.html">...</audio>
```

controls

Values: boolean | Since: HTML5

Show the browser's playback controls.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<audio controls>...</audio>
```

autoplay

Values: boolean | Since: HTML5

Start playing as soon as enough data has loaded. Usually blocked unless muted.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<audio autoplay>...</audio>
```

loop

Values: boolean | Since: HTML5

Restart from the beginning when the end is reached.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<audio loop>...</audio>
```

muted

Values: boolean | Since: HTML5

Start with the sound muted.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<audio muted>...</audio>
```

preload

Values: none | metadata | auto | Since: HTML5

A hint about how much to download before playback: nothing, only metadata such as duration (default in most browsers), or the whole file.

Write preload="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<audio preload="none">...</audio>
```

crossorigin

Values: anonymous | use-credentials | Since: HTML5

How to handle cross-origin requests, needed when the audio will be processed with the Web Audio API or canvas.

Write crossorigin="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<audio crossorigin="anonymous">...</audio>
```

controlslist

Values: nodownload | nofullscreen | noremoteplayback | Since: Living Standard

Hides specific built-in controls (non-standard, Chromium).

Write controlslist="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<audio controlslist="nodownload">...</audio>
```

disableremoteplayback

Values: boolean | Since: Living Standard

Disables casting to remote devices.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<audio disableremoteplayback>...</audio>
```

<audio>: worked examples

Simple player

```
<audio src="song.mp3" controls>
  Your browser does not support the audio element.
  <a href="song.mp3">Download the song</a>.
</audio>
```

Multiple formats with <source>

```
<audio controls preload="metadata">
  <source src="podcast.opus" type="audio/ogg; codecs=opus">
  <source src="podcast.mp3" type="audio/mpeg">
  <p>Download the <a href="podcast.mp3">MP3</a>.</p>
</audio>
```

The browser uses the first source it can play. Opus is smaller; MP3 works everywhere.

Controlling playback with JavaScript

```
<audio id="beep" src="beep.wav"></audio>
<button onclick="document.getElementById('beep').play()">Play beep</
button>
```

Background music that loops (muted by default)

```
<audio src="ambient.mp3" autoplay loop muted></audio>
```

The user must unmute it themselves.

Default browser CSS

```
audio:not([controls]) { display: none !important; }
```

Accessibility

- Provide a transcript for spoken content; <track> captions are supported only on <video> in most browsers.
- Always include controls or provide your own accessible buttons.
- Never autoplay sound; it is disorienting and can hide a screen reader's speech.

Common mistakes

- Expecting autoplay with sound to work.

- Using a single format that not all browsers support.
- Forgetting the type attribute on <source>, which forces the browser to download each file to test it.

See also

<video>, <source>, <track>, <embed>, <object>

Quick card: <b>

Bring attention to (bold)

The <b> element draws the reader's attention to a span of text without giving it extra importance, emphasis or an alternative voice. Browsers render it in bold. Typical uses are keywords in a summary, product names in a review, or the lead sentence of an article.

At a glance

Status	CURRENT
Versions	HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Text-level semantics
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	None (global attributes only)
Related	, , <i>, <mark>

Minimal example

```
<p>This laptop has a <b>15-inch display</b>, <b>16 GB of RAM</b> and
a <b>1 TB SSD</b>.</p>
```

Most common mistake

Using <b> for headings instead of <h1>-<h6>.

<b> — Bring attention to (bold)

Category: Text-level semantics | Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <b> element draws the reader's attention to a span of text without giving it extra importance, emphasis or an alternative voice. Browsers render it in bold. Typical uses are keywords in a summary, product names in a review, or the lead sentence of an article.

In HTML 4 <b> was a purely presentational element meaning 'bold'. HTML5 redefined it with the meaning above so that it remains valid, but the standard says to use <b> only as a last resort when no other element is more appropriate: for importance, for emphasis, <mark> for relevance, <h1>-<h6> for headings, and CSS font-weight for pure styling.

Syntax

```
<b>text</b>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, palpable content
Permitted content	Phrasing content

Property	Value
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<b>: worked examples

Keywords in a product description

```
<p>This laptop has a <b>15-inch display</b>, <b>16 GB of RAM</b> and
a <b>1 TB SSD</b>.</p>
```

The keywords stand out but are not more 'important' in the sense.

Difference between <b> and

```
<p><strong>Warning:</strong> the <b>red</b> wire carries current.</p>
```

'Warning' is important (strong); 'red' is merely highlighted as a keyword (b).

Default browser CSS

```
b { font-weight: bold; }
```

Accessibility

- Screen readers do not announce <b> in any special way. Use when the boldness carries meaning.

Common mistakes

- Using <b> for headings instead of <h1>-<h6>.
- Using <b> for emphasis instead of or .

See also

, , <i>, <mark>

Quick card: <base>

Document base URL

The <base> element specifies the base URL used to resolve all relative URLs in the document, and/or the default target for all links and forms. There may be only one <base> element per document and it must be placed in <head>, before any element that uses a URL.

At a glance

Status	CURRENT
Versions	HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Document metadata
Closing tag	None (void element)
Display	none
Own attributes	href, target
Related	<head>, <link>, <a>

Minimal example

```
<head>
  <base href="https://cdn.example.com/assets/">
</head>
<body>
  <img src="logo.png" alt="Logo">
  <!-- loads https://cdn.example.com/assets/logo.png -->
</body>
```

Most common mistake

Placing <base> after a <link> or <script> that uses a relative URL; it does not apply retroactively.

<base> — Document base URL

Category: Document metadata | Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <base> element specifies the base URL used to resolve all relative URLs in the document, and/or the default target for all links and forms. There may be only one <base> element per document and it must be placed in <head>, before any element that uses a URL.

It is a void element. At least one of href or target must be present.

Syntax

```
<base href="URL" target="_blank">
```

Technical summary

Property	Value
Void element	Yes (no closing tag)
Default display	none
Content categories	Metadata content
Permitted content	None (void element)
Permitted parents	<head> (only one allowed)
Tag omission	No end tag
DOM interface	HTMLBaseElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
href	URL	The base URL. Relative URLs such as images/logo.png are resolved against it.	HTML 2.0
target	_self | _blank | _parent | _top | name	The default browsing context for links and forms that do not specify their own target.	HTML 4.01

<base>: attribute by attribute

Each attribute of <base> explained in detail, with a minimal example you can copy.

href

Values: URL | Since: HTML 2.0

The base URL. Relative URLs such as images/logo.png are resolved against it.

Write href="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<base href="https://example.com/page.html">
```

target

Values: _self | _blank | _parent | _top | name | Since: HTML 4.01

The default browsing context for links and forms that do not specify their own target.

Write target="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<base target="_self">
```

<base>: worked examples

Making all relative links point to another server

```
<head>
  <base href="https://cdn.example.com/assets/">
</head>
<body>
  <img src="logo.png" alt="Logo">
  <!-- loads https://cdn.example.com/assets/logo.png -->
</body>
```

Opening every link in a new tab

```
<head>
  <base target="_blank">
</head>
```

Individual links can still override this with their own target.

Default browser CSS

```
base { display: none; }
```

Accessibility

- Opening all links in new tabs without warning is confusing; use with care.

Common mistakes

- Placing <base> after a <link> or <script> that uses a relative URL; it does not apply retroactively.
- Having more than one <base>.
- Forgetting that fragment links (#top) are also affected and will navigate to the base URL.

See also

<head>, <link>, <a>

Quick card: <basefont>

Base font (obsolete)

The <basefont> element set the default font size, colour and face for the whole document. It was a presentational element from HTML 3.2 and was deprecated in HTML 4.01 in favour of CSS. HTML5 removed it. Use CSS on the body element instead.

At a glance

Status	OBSOLETE
Versions	HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5
Category	Obsolete presentational
Closing tag	None (void element)
Display	none
Own attributes	size, color, face
Related	<font>, <body>

Minimal example

```
<!-- Old -->
<basefont size="4" face="Arial" color="#333">

<!-- New -->
<style>
  body { font: 18px Arial, sans-serif; color: #333; }
</style>
```

Most common mistake

Any use.

<basefont> — Base font (obsolete)

Category: Obsolete presentational | Status: OBSOLETE | Versions: HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

Description

The <basefont> element set the default font size, colour and face for the whole document. It was a presentational element from HTML 3.2 and was deprecated in HTML 4.01 in favour of CSS. HTML5 removed it. Use CSS on the body element instead.

Syntax

```
<basefont size="3" color="black" face="Arial">
```

Technical summary

Property	Value
Void element	Yes (no closing tag)
Default display	none
Content categories	Historical
Permitted content	None
Permitted parents	<head> or <body>
Tag omission	No end tag
DOM interface	HTMLUnknownElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
size	1 to 7	Default font size on the 1-7 HTML scale (3 = normal).	HTML 3.2
color	colour	Default text colour.	HTML 4.01
face	comma-separated font names	Default font family.	HTML 4.01

<basefont>: attribute by attribute

Each attribute of <basefont> explained in detail, with a minimal example you can copy.

size

Values: 1 to 7 | Since: HTML 3.2

Default font size on the 1-7 HTML scale (3 = normal).

Write size="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<basefont size="1 to 7">
```

color

Values: colour | Since: HTML 4.01

Default text colour.

Write color="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<basefont color="#336699">
```

face

Values: comma-separated font names | Since: HTML 4.01

Default font family.

Write face="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<basefont face="value">
```

<basefont>: worked examples

Replacement in CSS

```
<!-- Old -->
<basefont size="4" face="Arial" color="#333">

<!-- New -->
<style>
  body { font: 18px Arial, sans-serif; color: #333; }
</style>
```

Common mistakes

- Any use.

See also

<font>, <body>

Quick card: <bdi>

Bidirectional isolate

The <bdi> element isolates a span of text that might be written in a different direction from the text around it, so that its direction does not affect the surrounding text. It is essential when you insert user-generated text of unknown direction, such as user names, into a sentence.

At a glance

Status	CURRENT
Versions	HTML5
Category	Text-level semantics
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	dir
Related	<bdo>,

Minimal example

```
<ul>
  <li><bdi>Ahmed</bdi>: 120 points</li>
  <li><bdi>محمد</bdi>: 95 points</li>
  <li><bdi>Sara</bdi>: 80 points</li>
</ul>
```

Most common mistake

Using <bdo> when you want isolation; <bdo> forces a direction, <bdi> isolates.

<bdi> — Bidirectional isolate

Category: Text-level semantics | Status: CURRENT | Versions: HTML5

Description

The <bdi> element isolates a span of text that might be written in a different direction from the text around it, so that its direction does not affect the surrounding text. It is essential when you insert user-generated text of unknown direction, such as user names, into a sentence.

Without isolation, an Arabic or Hebrew name followed by a number in an English sentence can cause the number and punctuation to appear in the wrong place. <bdi> tells the bidirectional algorithm to treat the inner text as a separate unit.

It is equivalent to CSS unicode-bidi: isolate, and by default its direction is auto (detected from the content).

Syntax

```
<bdi>text of unknown direction</bdi>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, palpable content
Permitted content	Phrasing content
Permitted parents	Any element that accepts phrasing content

Property	Value
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
dir	ltr | rtl | auto	On <bdi> the default is auto, unlike other elements where dir is inherited.	HTML5

<bdi>: attribute by attribute

Each attribute of <bdi> explained in detail, with a minimal example you can copy.

dir

Values: ltr | rtl | auto | Since: HTML5

On <bdi> the default is auto, unlike other elements where dir is inherited.

Write dir="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<bdi dir="ltr">...</bdi>
```

<bdi>: worked examples

User names in a leaderboard

```
<ul>
  <li><bdi>Ahmed</bdi>: 120 points</li>
  <li><bdi>دمحم</bdi>: 95 points</li>
  <li><bdi>Sara</bdi>: 80 points</li>
</ul>
```

Without <bdi> the second line could render as ': 95 points دمحم' with the colon misplaced.

Default browser CSS

```
bdi { unicode-bidi: isolate; }
```

Accessibility

- Improves reading order for screen readers as well as visual order.

Common mistakes

- Using <bdo> when you want isolation; <bdo> forces a direction, <bdi> isolates.

See also

<bdo>,

Quick card: <bdo>

Bidirectional text override

The <bdo> element overrides the current text direction and forces its content to be displayed in the direction given by the dir attribute, character by character, ignoring the Unicode bidirectional algorithm. The dir attribute is required.

At a glance

Status	CURRENT
Versions	HTML 4.01, HTML5
Category	Text-level semantics
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	dir
Related	<bdi>

Minimal example

```
<p><bdo dir="rtl">This text is reversed</bdo></p>
```

Most common mistake

Omitting dir, which is required.

<bdo> — Bidirectional text override

Category: Text-level semantics | Status: CURRENT | Versions: HTML 4.01, HTML5

Description

The <bdo> element overrides the current text direction and forces its content to be displayed in the direction given by the dir attribute, character by character, ignoring the Unicode bidirectional algorithm. The dir attribute is required.

It is rarely needed; use it when you must display text backwards, for example to show how a right-to-left string is stored, or to fix a badly encoded document.

Syntax

```
<bdo dir="rtl">text</bdo>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, palpable content
Permitted content	Phrasing content
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
dir	ltr | rtl	Required. The direction to force.	HTML 4.01

<bdo>: attribute by attribute

Each attribute of <bdo> explained in detail, with a minimal example you can copy.

dir

Values: ltr | rtl | Since: HTML 4.01

Required. The direction to force.

Write dir="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<bdo dir="ltr">...</bdo>
```

<bdo>: worked examples

Displaying English backwards

```
<p><bdo dir="rtl">This text is reversed</bdo></p>
```

Renders as 'desrever si txet sihT'.

Default browser CSS

```
bdo { unicode-bidi: isolate-override; }
```

Accessibility

- Screen readers read the characters in the overridden order, which may be nonsense; use sparingly.

Common mistakes

- Omitting dir, which is required.
- Using <bdo> for isolation; use <bdi>.

See also

<bdi>

Quick card: <bgsound>

Background sound (non-standard, obsolete)

The <bgsound> element was an Internet Explorer extension that played a sound file automatically when the page loaded. It was never part of any HTML standard and is not supported by any modern browser. Use <audio> instead.

At a glance

Status	OBSOLETE
Versions	Internet Explorer extension, never standard; obsolete
Category	Obsolete embedded content
Closing tag	None (void element)
Display	none
Own attributes	src, loop, balance, volume
Related	<audio>

Minimal example

```
<audio src="music.mp3" autoplay loop muted></audio>
```

Most common mistake

Any use.

<bgsound> — Background sound (non-standard, obsolete)

Category: Obsolete embedded content | Status: OBSOLETE | Versions: Internet Explorer extension, never standard; obsolete

Description

The <bgsound> element was an Internet Explorer extension that played a sound file automatically when the page loaded. It was never part of any HTML standard and is not supported by any modern browser. Use <audio> instead.

Syntax

```
<bgsound src="music.mid" loop="infinite">
```

Technical summary

Property	Value
Void element	Yes (no closing tag)
Default display	none
Content categories	Historical
Permitted content	None
Permitted parents	<head> or <body>
Tag omission	No end tag
DOM interface	HTMLUnknownElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
src	URL	The sound file.	IE
loop	number | infinite	Repeat count.	IE
balance	-10000 to 10000	Stereo balance.	IE
volume	-10000 to 0	Volume.	IE

<bgsound>: attribute by attribute

Each attribute of <bgsound> explained in detail, with a minimal example you can copy.

src

Values: URL | Since: IE

The sound file.

Write src="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<bgsound src="https://example.com/page.html">
```

loop

Values: number | infinite | Since: IE

Repeat count.

Write loop="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<bgsound loop="3">
```

balance

Values: -10000 to 10000 | Since: IE

Stereo balance.

Write balance="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<bgsound balance="-10000 to 10000">
```

volume

Values: -10000 to 0 | Since: IE

Volume.

Write volume="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<bgsound volume="-10000 to 0">
```

<bgsound>: worked examples

Replacement

```
<audio src="music.mp3" autoplay loop muted></audio>
```

Common mistakes

- Any use.

See also

<audio>

Quick card: <big>

Bigger text (obsolete)

The <big> element rendered its content one font size larger than the surrounding text. It was purely presentational and was removed in HTML5. Its counterpart <small> survived because it was given a new meaning (side comments and fine print). Use CSS font-size instead of <big>.

At a glance

Status	OBSOLETE
Versions	HTML 3.2, HTML 4.01; obsolete in HTML5
Category	Obsolete presentational
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	None (global attributes only)
Related	<small>,

Minimal example

```
<!-- Old -->
<p>Only <big>3 days</big> left!</p>

<!-- New -->
<p>Only <span style="font-size: larger">3 days</span> left!</p>
```

Most common mistake

Any use in new pages.

<big> — Bigger text (obsolete)

Category: Obsolete presentational | Status: OBSOLETE | Versions: HTML 3.2, HTML 4.01; obsolete in HTML5

Description

The <big> element rendered its content one font size larger than the surrounding text. It was purely presentational and was removed in HTML5. Its counterpart <small> survived because it was given a new meaning (side comments and fine print). Use CSS font-size instead of <big>.

Syntax

```
<big>text</big>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Phrasing content (historical)
Permitted content	Phrasing content
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<big>: worked examples

Replacement

```
<!-- Old -->
<p>Only <big>3 days</big> left!</p>

<!-- New -->
<p>Only <span style="font-size: larger">3 days</span> left!</p>
```

Default browser CSS

```
big { font-size: larger; }
```

Common mistakes

- Any use in new pages.

See also

<small>,

Quick card: <blink>

Blinking text (non-standard, obsolete)

The <blink> element made its text flash on and off. It was a Netscape Navigator extension from 1994, was never part of any standard, and was widely considered the most annoying element ever created. All browsers removed support by 2013. Blinking content is also an accessibility hazard for people with photosensitive epilepsy and attention disorders.

At a glance

Status	OBSOLETE
Versions	Netscape extension, never standard; obsolete
Category	Obsolete presentational
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	None (global attributes only)
Related	<marquee>

Minimal example

```
<blink>Sale!</blink>
```

Most common mistake

Any use.

<blink> — Blinking text (non-standard, obsolete)

Category: Obsolete presentational | Status: OBSOLETE | Versions: Netscape extension, never standard; obsolete

Description

The <blink> element made its text flash on and off. It was a Netscape Navigator extension from 1994, was never part of any standard, and was widely considered the most annoying element ever created. All browsers removed support by 2013. Blinking content is also an accessibility hazard for people with photosensitive epilepsy and attention disorders.

Syntax

```
<blink>text</blink>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Historical
Permitted content	Phrasing content
Permitted parents	Any
Tag omission	Neither tag may be omitted
DOM interface	HTMLUnknownElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<blink>: worked examples

Do not do this

```
<blink>Sale!</blink>
```

If you must animate, use a CSS animation with a slow, subtle effect and respect prefers-reduced-motion.

Accessibility

- Flashing content can trigger seizures. WCAG forbids flashing more than three times per second.

Common mistakes

- Any use.

See also

<marquee>

Quick card: <blockquote>

Block quotation

The <blockquote> element indicates that the enclosed text is an extended quotation from another source. Browsers indent it on both sides by default. The optional cite attribute holds the URL of the source; a visible citation should be given with the <cite> element, usually in a <footer> inside the blockquote or in a following paragraph.

At a glance

Status	CURRENT
Versions	HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Text content
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	cite
Related	<q>, <cite>, <footer>

Minimal example

```
<blockquote cite="https://www.w3.org/People/Berners-Lee/">
  <p>The Web does not just connect machines, it connects people.</p>
  <footer>- <cite>Tim Berners-Lee</cite></footer>
</blockquote>
```

Most common mistake

Using <blockquote> just to indent text; use CSS margin for that.

<blockquote> — Block quotation

Category: Text content | Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <blockquote> element indicates that the enclosed text is an extended quotation from another source. Browsers indent it on both sides by default. The optional cite attribute holds the URL of the source; a visible citation should be given with the <cite> element, usually in a <footer> inside the blockquote or in a following paragraph.

For short quotations that sit inside a sentence use <q> instead.

Syntax

```
<blockquote cite="URL">quoted text</blockquote>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	Flow content, sectioning root, palpable content
Permitted content	Flow content
Permitted parents	Any element that accepts flow content
Tag omission	Neither tag may be omitted
DOM interface	HTMLQuoteElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
cite	URL	The URL of the source document or message. Not displayed by browsers; readable by scripts and tools.	HTML 4.01

<blockquote>: attribute by attribute

Each attribute of <blockquote> explained in detail, with a minimal example you can copy.

cite

Values: URL | Since: HTML 4.01

The URL of the source document or message. Not displayed by browsers; readable by scripts and tools.

Write cite="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<blockquote cite="https://example.com/page.html">...</blockquote>
```

<blockquote>: worked examples

Quotation with source

```
<blockquote cite="https://www.w3.org/People/Berners-Lee/">
  <p>The Web does not just connect machines, it connects people.</p>
  <footer>- <cite>Tim Berners-Lee</cite></footer>
</blockquote>
```

Custom styling

```
<style>
  blockquote {
    margin: 1em 0; padding: 0.5em 1em;
    border-left: 4px solid #c8a24a; background: #fdf8f0;
  }
</style>
<blockquote><p>Practice is the only tutorial that always works.</p></
blockquote>
```

Default browser CSS

```
blockquote { display: block; margin: 1em 40px; }
```

Accessibility

- Screen readers announce 'blockquote' so users know the text is quoted.

Common mistakes

- Using <blockquote> just to indent text; use CSS margin for that.
- Putting the author's name inside the quotation as if it were quoted.

See also

<q>, <cite>, <footer>

Quick card: <body>

Document body

The <body> element contains all the content of the document that is displayed to the visitor: text, images, links, forms, media, and the scripts that operate on them. There is exactly one <body> in a document and it is the second child of <html>, after <head>.

At a glance

Status	CURRENT
Versions	HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Sectioning root
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	onafterprint, onbeforeunload, onhashchange, onlanguagechange, onload, onmessage, onoffline, onpagehide, onpopstate, onresize, onstorage, onunload, alink, background, bgcolor, link, text, vlink, bottommargin
Related	<html>, <head>, <main>, <header>, <footer>

Minimal example

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <title>Hello</title>
</head>
<body>
  <h1>Hello, world!</h1>
</body>
</html>
```

Most common mistake

Having two <body> elements.

<body> — Document body

Category: Sectioning root | Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <body> element contains all the content of the document that is displayed to the visitor: text, images, links, forms, media, and the scripts that operate on them. There is exactly one <body> in a document and it is the second child of <html>, after <head>.

In HTML 3.2 and 4.01 <body> carried presentational attributes (bgcolor, text, link, vlink, alink, background) that set page colours and background images. They are obsolete in HTML5; use CSS. The <body> element also accepts window event handler attributes such as onload and onresize, because events on the window are reflected onto the body.

The start and end tags of <body> may technically be omitted and the browser will create the element automatically, but always write them for clarity.

Syntax

```
<body>...</body>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	Sectioning root

Property	Value
Permitted content	Flow content
Permitted parents	<html>, as its second child
Tag omission	Start tag may be omitted if the body is empty or starts with non-whitespace content that is not a comment, <script> or <style>; end tag may be omitted if not followed by a comment
DOM interface	HTMLBodyElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
onafterprint, onbeforeprint	script	Fired after and before the document is printed.	HTML5
onbeforeunload	script	Fired when the user is about to leave; can prompt for confirmation.	HTML5
onhashchange	script	Fired when the URL fragment (#…) changes.	HTML5
onlanguagechange	script	Fired when the preferred language changes.	HTML5
onload	script	Fired when the whole page, including images, has loaded.	HTML 4.01
onmessage, onmessageerror	script	Fired when a message is received via postMessage.	HTML5
onoffline, ononline	script	Fired when network connectivity is lost or regained.	HTML5

Attribute	Values	Description	Since
onpagehide, onpageshow	script	Fired when navigating away from or back to the page (including from the back-forward cache).	HTML5
onpopstate	script	Fired when the active history entry changes.	HTML5
onresize	script	Fired when the window is resized.	HTML 4.01
onstorage	script	Fired when localStorage or sessionStorage changes in another tab.	HTML5
onunload	script	Fired when the document is unloaded. Unreliable; prefer pagehide.	HTML 4.01
alink	colour	Obsolete. Colour of active (being clicked) links. Use CSS a:active.	HTML 3.2
background	URL	Obsolete. Background image. Use CSS background-image.	HTML 3.2
bgcolor	colour	Obsolete. Background colour. Use CSS background-color.	HTML 3.2
link	colour	Obsolete. Colour of unvisited links. Use CSS a:link.	HTML 3.2
text	colour	Obsolete. Text colour. Use CSS color.	HTML 3.2
vlink	colour	Obsolete. Colour of visited links. Use CSS a:visited.	HTML 3.2
bottommargin, leftmargin, rightmargin, topmargin	pixels	Obsolete, non-standard. Page margins. Use CSS margin.	IE/Netscape

<body>: attribute by attribute

Each attribute of <body> explained in detail, with a minimal example you can copy.

onafterprint, onbeforeprint

Values: script | Since: HTML5

Fired after and before the document is printed.

Write onafterprint="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<body onafterprint="script">...</body>
```

onbeforeunload

Values: script | Since: HTML5

Fired when the user is about to leave; can prompt for confirmation.

Write onbeforeunload="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<body onbeforeunload="script">...</body>
```

onhashchange

Values: script | Since: HTML5

Fired when the URL fragment (#...) changes.

Write onhashchange="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<body onhashchange="script">...</body>
```

onlanguagechange

Values: script | Since: HTML5

Fired when the preferred language changes.

Write onlanguagechange="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<body onlanguagechange="script">...</body>
```

onload

Values: script | Since: HTML 4.01

Fired when the whole page, including images, has loaded.

Write onload="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<body onload="script">...</body>
```

onmessage, onmessageerror

Values: script | Since: HTML5

Fired when a message is received via postMessage.

Write onmessage="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<body onmessage="script">...</body>
```

onoffline, ononline

Values: script | Since: HTML5

Fired when network connectivity is lost or regained.

Write onoffline="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<body onoffline="script">...</body>
```

onpagehide, onpageshow

Values: script | Since: HTML5

Fired when navigating away from or back to the page (including from the back-forward cache).

Write onpagehide="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<body onpagehide="script">...</body>
```

onpopstate

Values: script | Since: HTML5

Fired when the active history entry changes.

Write onpopstate="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<body onpopstate="script">...</body>
```

onresize

Values: script | Since: HTML 4.01

Fired when the window is resized.

Write onresize="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<body onresize="script">...</body>
```

onstorage

Values: script | Since: HTML5

Fired when localStorage or sessionStorage changes in another tab.

Write onstorage="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<body onstorage="script">...</body>
```

onunload

Values: script | Since: HTML 4.01

Fired when the document is unloaded. Unreliable; prefer pagehide.

Write onunload="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<body onunload="script">...</body>
```

alink

Values: colour | Since: HTML 3.2

Obsolete. Colour of active (being clicked) links. Use CSS a:active.

Write alink="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<body alink="#336699">...</body>
```

background

Values: URL | Since: HTML 3.2

Obsolete. Background image. Use CSS background-image.

Write background="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<body background="https://example.com/page.html">...</body>
```

bgcolor

Values: colour | Since: HTML 3.2

Obsolete. Background colour. Use CSS background-color.

Write bgcolor="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<body bgcolor="#336699">...</body>
```

link

Values: colour | Since: HTML 3.2

Obsolete. Colour of unvisited links. Use CSS a:link.

Write link="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<body link="#336699">...</body>
```

text

Values: colour | Since: HTML 3.2

Obsolete. Text colour. Use CSS color.

Write text="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<body text="#336699">...</body>
```

vlink

Values: colour | Since: HTML 3.2

Obsolete. Colour of visited links. Use CSS a:visited.

Write vlink="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<body vlink="#336699">...</body>
```

bottommargin, leftmargin, rightmargin, topmargin

Values: pixels | Since: IE/Netscape

Obsolete, non-standard. Page margins. Use CSS margin.

Write bottommargin="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<body bottommargin="3">...</body>
```

<body>: worked examples

Minimal document

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <title>Hello</title>
</head>
<body>
  <h1>Hello, world!</h1>
</body>
</html>
```

HTML 3.2 colours and their CSS replacement

```
<!-- HTML 3.2 -->
<body bgcolor="#ffffff" text="#000000" link="#0000ff" vlink="#800080">

<!-- HTML5 + CSS -->
<style>
  body { background: #fff; color: #000; }
  a:link { color: blue; }
  a:visited { color: purple; }
</style>
<body>
```

Running code when the page has loaded

```
<body onload="console.log('Page loaded')">
```

Prefer addEventListener('DOMContentLoaded', ...) in a script.

Default browser CSS

```
body { display: block; margin: 8px; }
```

Accessibility

- Set the page language on <html>, not <body>.
- Keep a logical reading order in the body; CSS can rearrange the visual layout but assistive technology follows the source order.

Common mistakes

- Having two <body> elements.

- Putting <title> or <meta> in the body.
- Using the obsolete colour attributes.

See also

<html>, <head>, <main>, <header>, <footer>

Quick card:

Line break

The <br> element produces a line break in text: the text after it starts on a new line. It is a void element with no closing tag. Use it only where the division of lines is part of the content, as in a postal address or a poem.

At a glance

Status	CURRENT
Versions	HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Text-level semantics
Closing tag	None (void element)
Display	inline
Own attributes	clear
Related	<p>, <wbr>, <hr>, <pre>

Minimal example

```
<p>
  Example Ltd.<br>
  12 Nile Street<br>
  Giza, Egypt
</p>
```

Most common mistake

Using <br> for vertical spacing.

 — Line break

Category: Text-level semantics | Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <br> element produces a line break in text: the text after it starts on a new line. It is a void element with no closing tag. Use it only where the division of lines is part of the content, as in a postal address or a poem.

Do not use <br> to create space between paragraphs or blocks. Use separate <p> elements and CSS margins instead. A series of

 to push content down is a classic beginner mistake that breaks on different screen sizes and confuses screen readers.

Syntax

```
<br>
```

Technical summary

Property	Value
Void element	Yes (no closing tag)
Default display	inline
Content categories	Flow content, phrasing content
Permitted content	None (void element)
Permitted parents	Any element that accepts phrasing content
Tag omission	No end tag
DOM interface	HTMLBRElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
clear	left | right | all | none	Obsolete. Moved the following text below any floated images. Use CSS clear.	HTML 3.2

: attribute by attribute

Each attribute of <br> explained in detail, with a minimal example you can copy.

clear

Values: left | right | all | none | Since: HTML 3.2

Obsolete. Moved the following text below any floated images. Use CSS clear.

Write clear="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<br clear="left">
```


: worked examples

An address

```
<p>
  Example Ltd.<br>
  12 Nile Street<br>
  Giza, Egypt
</p>
```

A poem

```
<p>
  Roses are red,<br>
  Violets are blue,<br>
  HTML is easy,<br>
  And so are you.
</p>
```

Wrong and right

```
<!-- Wrong: spacing with br -->
<p>First</p><br><br>
<p>Second</p>

<!-- Right: spacing with CSS -->
<style>p { margin-bottom: 2em; }</style>
<p>First</p>
<p>Second</p>
```

Default browser CSS

```
br { display: inline; }
```

Accessibility

- Screen readers may announce each <br>, so many consecutive breaks are noisy.

Common mistakes

- Using <br> for vertical spacing.
- Writing </br>, which is invalid (browsers treat it as <br>).
- Using <br> to separate list items instead of /<li>.

See also

<p>, <wbr>, <hr>, <pre>

Quick card: <button>

Button

The <button> element represents a clickable button that the user can activate with a mouse, keyboard, finger or voice to perform an action. Unlike <input type="button">, a <button> may contain rich content: text, images, icons and other phrasing content.

At a glance

Status	CURRENT
Versions	HTML 4.01, HTML5
Category	Forms
Closing tag	Required unless noted under Tag omission
Display	inline-block
Own attributes	type, name, value, disabled, autofocus, form, formaction, formenctype, formmethod, formnovalidate, formtarget, popovertarget, popovertargetaction, command, commandfor
Related	<input>, <form>, <a>, <label>

Minimal example

```
<form action="/save" method="post">
  <label>Name <input name="name"></label>
  <button type="submit">Save</button>
  <button type="reset">Clear</button>
  <button type="button" onclick="alert('Just a script')">Help</button>
</form>
```

Most common mistake

Forgetting type="button" and accidentally submitting the form.

<button> — Button

Category: Forms | Status: CURRENT | Versions: HTML 4.01, HTML5

Description

The <button> element represents a clickable button that the user can activate with a mouse, keyboard, finger or voice to perform an action. Unlike <input type="button">, a <button> may contain rich content: text, images, icons and other phrasing content.

Inside a <form>, a button submits the form by default (type="submit"). Set type="button" for buttons that only run JavaScript, and type="reset" to clear the form. Because the default is submit, forgetting type="button" is a frequent cause of forms submitting unexpectedly.

The button's form-related attributes (formaction, formmethod and so on) let one form have several submit buttons that send the data to different places or in different ways.

Syntax

```
<button type="button">label</button>
```

Technical summary

Property	Value
Void element	No
Default display	inline-block
Content categories	Flow content, phrasing content, interactive content, listed, labelable, submittable, form-associated, palpable
Permitted content	Phrasing content, but no interactive content and no descendant with the tabindex attribute

Property	Value
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLButtonElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
type	submit | reset | button	submit (default) sends the form; reset restores default values; button does nothing by itself.	HTML 4.01
name	text	The name sent with the form data when this button submits the form.	HTML 4.01
value	text	The value sent with the name.	HTML 4.01
disabled	boolean	The button cannot be clicked or focused and is not submitted.	HTML 4.01
autofocus	boolean	Focus this button when the page loads (global in HTML5).	HTML5
form	form id	Associates the button with a form elsewhere in the document.	HTML5
formaction	URL	Overrides the form's action for this button.	HTML5
formenctype	application/x-www-form-urlencoded | multipart/form-data | text/plain	Overrides the form's enctype.	HTML5

Attribute	Values	Description	Since
formmethod	get | post | dialog	Overrides the form's method.	HTML5
formnovalidate	boolean	Skips validation when this button submits.	HTML5
formtarget	_self | _blank | _parent | _top | name	Overrides the form's target.	HTML5
popovertarget	element id	The popover element this button shows, hides or toggles.	Living Standard
popovertargetaction	show | hide | toggle	What to do to the popover (default toggle).	Living Standard
command	show-modal | close | request-close | show-popover | hide-popover | toggle-popover | custom	Experimental: declarative action to perform on commandfor's target.	Living Standard
commandfor	element id	Experimental: the element the command applies to.	Living Standard

<button>: attribute by attribute

Each attribute of <button> explained in detail, with a minimal example you can copy.

type

Values: submit | reset | button | Since: HTML 4.01

submit (default) sends the form; reset restores default values; button does nothing by itself.

Write type="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<button type="submit">...</button>
```

name

Values: text | Since: HTML 4.01

The name sent with the form data when this button submits the form.

Write name="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<button name="value">...</button>
```

value

Values: text | Since: HTML 4.01

The value sent with the name.

Write value="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<button value="value">...</button>
```

disabled

Values: boolean | Since: HTML 4.01

The button cannot be clicked or focused and is not submitted.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<button disabled>...</button>
```

autofocus

Values: boolean | Since: HTML5

Focus this button when the page loads (global in HTML5).

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<button autofocus>...</button>
```

form

Values: form id | Since: HTML5

Associates the button with a form elsewhere in the document.

Write form="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<button form="form id">...</button>
```

formaction

Values: URL | Since: HTML5

Overrides the form's action for this button.

Write formaction="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<button formaction="https://example.com/page.html">...</button>
```

formenctype

Values: application/x-www-form-urlencoded | multipart/form-data | text/plain | Since: HTML5

Overrides the form's enctype.

Write formenctype="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<button formenctype="application">...</button>
```

formmethod

Values: get | post | dialog | Since: HTML5

Overrides the form's method.

Write formmethod="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<button formmethod="get">...</button>
```

formnovalidate

Values: boolean | Since: HTML5

Skips validation when this button submits.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<button formnovalidate>...</button>
```

formtarget

Values: _self | _blank | _parent | _top | name | Since: HTML5

Overrides the form's target.

Write formtarget="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<button formtarget="_self">...</button>
```

popovertarget

Values: element id | Since: Living Standard

The popover element this button shows, hides or toggles.

Write popovertarget="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<button popovertarget="element id">...</button>
```

popovertargetaction

Values: show | hide | toggle | Since: Living Standard

What to do to the popover (default toggle).

Write popovertargetaction="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<button popovertargetaction="show">...</button>
```

command

Values: show-modal | close | request-close | show-popover | hide-popover | toggle-popover | custom | Since: Living Standard

Experimental: declarative action to perform on commandfor's target.

Write command="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<button command="show-modal">...</button>
```

commandfor

Values: element id | Since: Living Standard

Experimental: the element the command applies to.

Write commandfor="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<button commandfor="element id">...</button>
```

<button>: worked examples

Three button types in a form

```
<form action="/save" method="post">
  <label>Name <input name="name"></label>
  <button type="submit">Save</button>
  <button type="reset">Clear</button>
  <button type="button" onclick="alert('Just a script')">Help</button>
</form>
```

Button with an icon

```
<button type="button">
  <img src="cart.svg" alt="" width="16" height="16">
  Add to cart
</button>
```

The image is decorative (empty alt) because the text already labels the button.

Two submit buttons going to different URLs

```
<form action="/save" method="post">
  <input name="title">
  <button>Save draft</button>
  <button formaction="/publish">Publish</button>
</form>
```

Toggling a popover without JavaScript

```
<button popovertarget="tip">Show tip</button>
<div id="tip" popover>Press Ctrl+S to save.</div>
```

Icon-only button with an accessible name

```
<button type="button" aria-label="Close">&times;</button>
```

Default browser CSS

```
button { display: inline-block; text-align: center; cursor: default;
padding: 1px 6px; }
```

Accessibility

- Buttons are focusable and activated with Enter or Space automatically; a <div onclick> is not.
- Every button needs a text label or aria-label.
- Use <button> for actions and <a> for navigation.

- Do not remove the focus outline without providing an alternative.

Common mistakes

- Forgetting type="button" and accidentally submitting the form.
- Nesting an <a> or another <button> inside.
- Using or styled as a button.
- Using <input type="button"> when you need HTML content inside.

See also

<input>, <form>, <a>, <label>

Quick card: <canvas>

Graphics canvas

The <canvas> element provides a blank, resolution-dependent bitmap surface on which JavaScript can draw graphics: shapes, text, images, animations, charts, games and image processing. The element itself does nothing; all drawing is done through the 2D context (getContext('2d')) or a WebGL / WebGPU context.

At a glance

Status	CURRENT
Versions	HTML5
Category	Scripting
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	width, height, moz-opaque
Related	<svg>, <img>, <script>

Minimal example

```
<canvas id="demo" width="300" height="150">
  A blue rectangle with the text Hello.
</canvas>
<script>
  const ctx = document.getElementById('demo').getContext('2d');
  ctx.fillStyle = '#1b6fd8';
  ctx.fillRect(10, 10, 120, 80);
  ctx.fillStyle = 'white';
  ctx.font = '20px sans-serif';
  ctx.fillText('Hello', 30, 60);
</script>
```

Most common mistake

Sizing the canvas with CSS instead of width/height attributes.

<canvas> — Graphics canvas

Category: Scripting | Status: CURRENT | Versions: HTML5

Description

The <canvas> element provides a blank, resolution-dependent bitmap surface on which JavaScript can draw graphics: shapes, text, images, animations, charts, games and image processing. The element itself does nothing; all drawing is done through the 2D context (getContext('2d')) or a WebGL / WebGPU context.

The width and height attributes set the size of the drawing surface in pixels (default 300 x 150). Setting the size with CSS instead scales the bitmap and makes it blurry; always set the attributes.

Content placed between the tags is fallback content shown by browsers that do not support canvas and read by screen readers, because the drawn pixels are invisible to assistive technology.

Syntax

```
<canvas id="c" width="400" height="300">fallback</canvas>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, embedded content, palpable content

Property	Value
Permitted content	Transparent, but no interactive content other than <a>, <button>, <input> of certain types and <select> with focusable descendants
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLCanvasElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
width	positive integer	Width of the bitmap in CSS pixels. Default 300.	HTML5
height	positive integer	Height of the bitmap in CSS pixels. Default 150.	HTML5
moz-opaque	boolean	Firefox only: hints that there is no transparency, for faster rendering.	Non-standard

<canvas>: attribute by attribute

Each attribute of <canvas> explained in detail, with a minimal example you can copy.

width

Values: positive integer | Since: HTML5

Width of the bitmap in CSS pixels. Default 300.

Write width="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<canvas width="3">...</canvas>
```

height

Values: positive integer | Since: HTML5

Height of the bitmap in CSS pixels. Default 150.

Write height="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<canvas height="3">...</canvas>
```

moz-opaque

Values: boolean | Since: Non-standard

Firefox only: hints that there is no transparency, for faster rendering.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<canvas moz-opaque>...</canvas>
```

<canvas>: worked examples

Drawing a rectangle and text

```
<canvas id="demo" width="300" height="150">
  A blue rectangle with the text Hello.
</canvas>
<script>
  const ctx = document.getElementById('demo').getContext('2d');
  ctx.fillStyle = '#1b6fd8';
  ctx.fillRect(10, 10, 120, 80);
  ctx.fillStyle = 'white';
  ctx.font = '20px sans-serif';
  ctx.fillText('Hello', 30, 60);
</script>
```

Simple animation

```
<canvas id="ball" width="200" height="100"></canvas>
<script>
  const c = document.getElementById('ball'), ctx = c.getContext('2d');
  let x = 0;
  function frame() {
    ctx.clearRect(0, 0, c.width, c.height);
    ctx.beginPath(); ctx.arc(x, 50, 10, 0, Math.PI * 2); ctx.fill();
    x = (x + 2) % c.width;
    requestAnimationFrame(frame);
  }
  frame();
</script>
```

Default browser CSS

```
canvas { display: inline; }
```

Accessibility

- Canvas content is invisible to screen readers. Provide fallback content, an aria-label, or a text alternative next to it.
- For charts, provide the data as a table too.
- For diagrams and icons, SVG is usually more accessible than canvas.

Common mistakes

- Sizing the canvas with CSS instead of width/height attributes.
- Forgetting to clear before redrawing.
- Using canvas for content that should be real HTML text.

See also

<svg>, <img>, <script>

Quick card: <caption>

Table caption

The <caption> element gives a table a title or explanation. It must be the first child of the <table> element, and a table may have only one. By default it is displayed centred above the table; the CSS caption-side property can move it below.

At a glance

Status	CURRENT
Versions	HTML 3.2, HTML 4.01, HTML5
Category	Table content
Closing tag	Required unless noted under Tag omission
Display	table-caption
Own attributes	align
Related	<table>, <figcaption>

Minimal example

```
<table>
  <caption>Monthly sales, 2026</caption>
  <tr><th>Month</th><th>Sales</th></tr>
  <tr><td>January</td><td>120</td></tr>
  <tr><td>February</td><td>150</td></tr>
</table>
```

Most common mistake

Placing <caption> after <tr>.

<caption> — Table caption

Category: Table content | Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

Description

The <caption> element gives a table a title or explanation. It must be the first child of the <table> element, and a table may have only one. By default it is displayed centred above the table; the CSS caption-side property can move it below.

A caption is important for accessibility: screen readers announce it when the user enters the table, so the user knows what the data is about before hearing the cells.

Syntax

```
<table>
  <caption>Title</caption>
  ...
</table>
```

Technical summary

Property	Value
Void element	No
Default display	table-caption
Content categories	None
Permitted content	Flow content, but no descendant <table>
Permitted parents	<table>, as its first child
Tag omission	End tag may be omitted if the caption is not followed by whitespace or a comment
DOM interface	HTMLTableCaptionElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
align	top | bottom | left | right	Obsolete. Position of the caption. Use CSS caption-side and text-align.	HTML 3.2

<caption>: attribute by attribute

Each attribute of <caption> explained in detail, with a minimal example you can copy.

align

Values: top | bottom | left | right | Since: HTML 3.2

Obsolete. Position of the caption. Use CSS caption-side and text-align.

Write align="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<caption align="top">...</caption>
```

<caption>: worked examples

Table with caption

```
<table>
  <caption>Monthly sales, 2026</caption>
  <tr><th>Month</th><th>Sales</th></tr>
  <tr><td>January</td><td>120</td></tr>
  <tr><td>February</td><td>150</td></tr>
</table>
```

Caption below the table

```
<style>
  table { caption-side: bottom; }
</style>
```

Default browser CSS

```
caption { display: table-caption; text-align: center; }
```

Accessibility

- Prefer <caption> over a heading above the table; it is programmatically linked to the table.
- If the table is inside a <figure>, use <figcaption> instead of <caption>, not both.

Common mistakes

- Placing <caption> after <tr>.
- Multiple captions.

See also

<table>, <figcaption>

Quick card:

Centred block (obsolete)

The element horizontally centred its content. It was introduced by Netscape, standardised in HTML 3.2, deprecated in HTML 4.01 and removed in HTML5. It is equivalent to . Use CSS instead: text-align: center for inline content, or margin: 0 auto with a width for blocks.

At a glance

Status	OBSOLETE
Versions	HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5
Category	Obsolete presentational
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	None (global attributes only)
Related	

Minimal example

```
<!-- Old -->
<center><h1>Welcome</h1></center>

<!-- New: centre text -->
<h1 style="text-align: center">Welcome</h1>

<!-- New: centre a block -->
<div style="width: 600px; margin: 0 auto">...</div>
```

Most common mistake

Any use in new pages.

— Centred block (obsolete)

Category: Obsolete presentational | Status: OBSOLETE | Versions: HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

Description

The element horizontally centred its content. It was introduced by Netscape, standardised in HTML 3.2, deprecated in HTML 4.01 and removed in HTML5. It is equivalent to . Use CSS instead: text-align: center for inline content, or margin: 0 auto with a width for blocks.

Syntax

```
<center>content</center>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	Flow content (historical)
Permitted content	Flow content
Permitted parents	Any element that accepts flow content
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

: worked examples

Replacement

```
<!-- Old -->
<center><h1>Welcome</h1></center>

<!-- New: centre text -->
<h1 style="text-align: center">Welcome</h1>

<!-- New: centre a block -->
<div style="width: 600px; margin: 0 auto">...</div>
```

Default browser CSS

```
center { display: block; text-align: -webkit-center; }
```

Common mistakes

- Any use in new pages.

See also

Quick card: <cite>

Citation (title of a work)

The <cite> element marks the title of a creative work that is being referenced: a book, article, film, song, painting, play, poem, website, legal case, computer program, and so on. Browsers render it in italics.

At a glance

Status	CURRENT
Versions	HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Text-level semantics
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	None (global attributes only)
Related	<blockquote>, <q>, <i>

Minimal example

```
<p>I am reading <cite>The Pragmatic Programmer</cite> this month.</p>
```

Most common mistake

Using <cite> for the URL of a source; that belongs in the cite attribute of <blockquote> or <q>.

<cite> — Citation (title of a work)

Category: Text-level semantics | Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <cite> element marks the title of a creative work that is being referenced: a book, article, film, song, painting, play, poem, website, legal case, computer program, and so on. Browsers render it in italics.

In HTML 4 <cite> could also mark the name of a person being quoted. The HTML Living Standard restricts it to titles of works; a person's name is not a title. In practice many pages use it for author names inside <blockquote> footers, and validators accept it.

Syntax

```
<cite>Title of Work</cite>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, palpable content
Permitted content	Phrasing content
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted

Property	Value
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<cite>: worked examples

Book title

```
<p>I am reading <cite>The Pragmatic Programmer</cite> this month.</p>
```

Source of a quotation

```
<blockquote>
  <p>Any fool can write code that a computer can understand.</p>
  <footer>- Martin Fowler, <cite>Refactoring</cite></footer>
</blockquote>
```

Default browser CSS

```
cite { font-style: italic; }
```

Accessibility

- No special announcement; the meaning is mainly for search engines and styling.

Common mistakes

- Using <cite> for the URL of a source; that belongs in the cite attribute of <blockquote> or <q>.
- Using <i> instead of <cite> for titles.

See also

<blockquote>, <q>, <i>

Quick card: <code>

Inline code

The <code> element marks a fragment of computer code: an element name, a file name, a variable, a function, a command, or any other string a computer would recognise. Browsers render it in a monospace font.

At a glance

Status	CURRENT
Versions	HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Text-level semantics
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	None (global attributes only)
Related	<pre>, <kbd>, <samp>, <var>

Minimal example

```
<p>Use the <code>&lt;footer&gt;</code> element for the bottom of the
page and save the file as <code>index.html</code>.</p>
```

Most common mistake

Forgetting to escape < and & inside code.

<code> — Inline code

Category: Text-level semantics | Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <code> element marks a fragment of computer code: an element name, a file name, a variable, a function, a command, or any other string a computer would recognise. Browsers render it in a monospace font.

For a multi-line block of code, wrap a <code> element in a <pre> element so that line breaks and indentation are preserved. The class attribute may be used to indicate the language, conventionally as language-xxx.

Syntax

```
<code>snippet</code>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, palpable content
Permitted content	Phrasing content
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<code>: worked examples

Inline

```
<p>Use the <code>&lt;footer&gt;</code> element for the bottom of the
page and save the file as <code>index.html</code>.</p>
```

Note that < and > inside code must still be written as < and >.

Code block

```
<pre><code class="language-css">footer {
  text-align: center;
  color: gray;
}</code></pre>
```

Default browser CSS

```
code { font-family: monospace; }
```

Accessibility

- Some screen readers switch to reading punctuation when they encounter <code>.

Common mistakes

- Forgetting to escape < and & inside code.
- Using <code> alone for multi-line blocks (line breaks collapse without <pre>).

See also

<pre>, <kbd>, <samp>, <var>

Quick card: <col>

Table column

The <col> element defines one or more columns in a table so that attributes and styles can be applied to whole columns at once. It is a void element and lives inside a <colgroup>. The span attribute makes one <col> stand for several consecutive columns.

At a glance

Status	CURRENT
Versions	HTML 4.01, HTML5
Category	Table content
Closing tag	None (void element)
Display	table-column
Own attributes	span, align, bgcolor, char, charoff, valign, width
Related	<colgroup>, <table>

Minimal example

```
<table>
  <colgroup>
    <col style="background: #f0f0f0">
    <col>
    <col style="width: 200px">
  </colgroup>
  <tr><th>Item</th><th>Qty</th><th>Notes</th></tr>
  <tr><td>Pen</td><td>3</td><td>Blue ink</td></tr>
</table>
```

Most common mistake

Placing <col> outside <colgroup> (browsers insert an implicit colgroup, but be explicit).

<col> — Table column

Category: Table content | Status: CURRENT | Versions: HTML 4.01, HTML5

Description

The <col> element defines one or more columns in a table so that attributes and styles can be applied to whole columns at once. It is a void element and lives inside a <colgroup>. The span attribute makes one <col> stand for several consecutive columns.

Only a few CSS properties apply to columns: background, border, width and visibility. Text colour and font cannot be set on a column; set them on the cells.

Syntax

```
<colgroup>
  <col span="2" style="background: #eee">
</colgroup>
```

Technical summary

Property	Value
Void element	Yes (no closing tag)
Default display	table-column
Content categories	None
Permitted content	None (void element)
Permitted parents	<colgroup> that does not have a span attribute
Tag omission	No end tag
DOM interface	HTMLTableColElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
span	positive integer	How many consecutive columns this element represents. Default 1.	HTML 4.01
align	left | center | right | justify | char	Obsolete. Horizontal alignment of the cells. Use CSS text-align.	HTML 4.01
bgcolor	colour	Obsolete. Background colour. Use CSS.	HTML 4.01
char	character	Obsolete. Alignment character (for align=char).	HTML 4.01
charoff	number	Obsolete. Offset from the alignment character.	HTML 4.01
valign	top | middle | bottom | baseline	Obsolete. Vertical alignment. Use CSS vertical-align.	HTML 4.01
width	pixels or percentage	Obsolete. Column width. Use CSS width.	HTML 4.01

<col>: attribute by attribute

Each attribute of <col> explained in detail, with a minimal example you can copy.

span

Values: positive integer | Since: HTML 4.01

How many consecutive columns this element represents. Default 1.

Write span="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<col span="3">
```

align

Values: left | center | right | justify | char | Since: HTML 4.01

Obsolete. Horizontal alignment of the cells. Use CSS text-align.

Write align="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<col align="left">
```

bgcolor

Values: colour | Since: HTML 4.01

Obsolete. Background colour. Use CSS.

Write bgcolor="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<col bgcolor="#336699">
```

char

Values: character | Since: HTML 4.01

Obsolete. Alignment character (for align=char).

Write char="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<col char="character">
```

charoff

Values: number | Since: HTML 4.01

Obsolete. Offset from the alignment character.

Write charoff="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<col charoff="3">
```

valign

Values: top | middle | bottom | baseline | Since: HTML 4.01

Obsolete. Vertical alignment. Use CSS vertical-align.

Write valign="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<col valign="top">
```

width

Values: pixels or percentage | Since: HTML 4.01

Obsolete. Column width. Use CSS width.

Write width="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<col width="3">
```

<col>: worked examples

Shading the first column and widening the last

```
<table>
  <colgroup>
    <col style="background: #f0f0f0">
    <col>
    <col style="width: 200px">
  </colgroup>
  <tr><th>Item</th><th>Qty</th><th>Notes</th></tr>
  <tr><td>Pen</td><td>3</td><td>Blue ink</td></tr>
</table>
```

Default browser CSS

```
col { display: table-column; }
```

Accessibility

- Columns have no accessibility role; use <th scope="col">for column headers.

Common mistakes

- Placing <col> outside <colgroup> (browsers insert an implicit colgroup, but be explicit).
- Trying to set font or colour on <col>.

See also

<colgroup>, <table>

Quick card: <colgroup>

Table column group

The <colgroup> element groups one or more columns of a table for the purpose of styling and structure. It is placed inside <table> after the optional <caption> and before any <thead>, <tbody>, <tfoot> or <tr>. It either has a span attribute (and no children) or contains <col> elements.

At a glance

Status	CURRENT
Versions	HTML 4.01, HTML5
Category	Table content
Closing tag	Required unless noted under Tag omission
Display	table-column-group
Own attributes	span, align
Related	<col>, <table>

Minimal example

```
<table>
  <colgroup style="background: #e8f4ff"><col><col></colgroup>
  <colgroup style="background: #fff4e8"><col></colgroup>
  <tr><th>First</th><th>Last</th><th>Age</th></tr>
  <tr><td>Ahmed</td><td>Ali</td><td>20</td></tr>
</table>
```

Most common mistake

Mixing a span attribute with <col> children.

<colgroup> — Table column group

Category: Table content | Status: CURRENT | Versions: HTML 4.01, HTML5

Description

The <colgroup> element groups one or more columns of a table for the purpose of styling and structure. It is placed inside <table> after the optional <caption> and before any <thead>, <tbody>, <tfoot> or <tr>. It either has a span attribute (and no children) or contains <col> elements.

Syntax

```
<colgroup span="2"></colgroup>
<!-- or -->
<colgroup><col><col></colgroup>
```

Technical summary

Property	Value
Void element	No
Default display	table-column-group
Content categories	None
Permitted content	If span is absent: zero or more <col> and <template>. If span is present: nothing
Permitted parents	<table>, after <caption> and before <thead>, <tbody>, <tfoot> and <tr>
Tag omission	Start tag may be omitted if the first thing inside is a <col>; end tag may be omitted if not followed by whitespace or a comment
DOM interface	HTMLTableColElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
span	positive integer	Number of columns in the group when there are no <col> children.	HTML 4.01
align, bgcolor, char, charoff, valign, width	various	Obsolete presentational attributes; see <col>.	HTML 4.01

<colgroup>: attribute by attribute

Each attribute of <colgroup> explained in detail, with a minimal example you can copy.

span

Values: positive integer | Since: HTML 4.01

Number of columns in the group when there are no <col> children.

Write span="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<colgroup span="3">...</colgroup>
```

align, bgcolor, char, charoff, valign, width

Values: various | Since: HTML 4.01

Obsolete presentational attributes; see <col>.

Write align="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<colgroup align="various">...</colgroup>
```

<colgroup>: worked examples

Two groups with different backgrounds

```
<table>
  <colgroup style="background: #e8f4ff"><col><col></colgroup>
  <colgroup style="background: #fff4e8"><col></colgroup>
  <tr><th>First</th><th>Last</th><th>Age</th></tr>
  <tr><td>Ahmed</td><td>Ali</td><td>20</td></tr>
</table>
```

Default browser CSS

```
colgroup { display: table-column-group; }
```

Common mistakes

- Mixing a span attribute with <col> children.
- Placing colgroup after tbody.

See also

<col>, <table>

Quick card: <content>

Shadow DOM insertion point (obsolete)

The <content> element was part of the first, experimental version of Shadow DOM (v0). It marked the point where light DOM children were inserted into a shadow tree. It was replaced by the standardised <slot> element and removed from browsers in 2019.

At a glance

Status	OBSOLETE
Versions	Shadow DOM v0 (Chrome, 2013); obsolete
Category	Obsolete web components
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	select
Related	<slot>, <template>, <shadow>

Minimal example

```
<!-- Old -->
<content select=".title"></content>

<!-- New -->
<slot name="title"></slot>
```

Most common mistake

Any use.

<content> — Shadow DOM insertion point (obsolete)

Category: Obsolete web components | Status: OBSOLETE | Versions: Shadow DOM v0 (Chrome, 2013); obsolete

Description

The <content> element was part of the first, experimental version of Shadow DOM (v0). It marked the point where light DOM children were inserted into a shadow tree. It was replaced by the standardised <slot> element and removed from browsers in 2019.

Syntax

```
<content select=".title"></content>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Historical
Permitted content	Any
Permitted parents	Shadow root
Tag omission	Neither
DOM interface	HTMLUnknownElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
select	CSS selector	Which light DOM children to insert.	Shadow DOM v0

<content>: attribute by attribute

Each attribute of <content> explained in detail, with a minimal example you can copy.

select

Values: CSS selector | Since: Shadow DOM v0

Which light DOM children to insert.

Write select="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<content select="CSS selector">...</content>
```

<content>: worked examples

Replacement

```
<!-- Old -->
<content select=".title"></content>

<!-- New -->
<slot name="title"></slot>
```

Common mistakes

- Any use.

See also

<slot>, <template>, <shadow>

Quick card: <data>

Machine-readable value

The <data> element links a piece of human-readable content with a machine-readable version of the same value held in the required value attribute. It is useful for product codes, numeric values written in words, sorting keys and similar cases where a script or search engine needs the exact value while the visitor sees a friendly form.

At a glance

Status	CURRENT
Versions	HTML5
Category	Text-level semantics
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	value
Related	<time>, <meter>

Minimal example

```
<ul>
  <li><data value="SKU-1001">Blue notebook</data></li>
  <li><data value="SKU-1002">Red notebook</data></li>
</ul>
```

Most common mistake

Using <data> for dates; use <time>.

<data> — Machine-readable value

Category: Text-level semantics | Status: CURRENT | Versions: HTML5

Description

The <data> element links a piece of human-readable content with a machine-readable version of the same value held in the required value attribute. It is useful for product codes, numeric values written in words, sorting keys and similar cases where a script or search engine needs the exact value while the visitor sees a friendly form.

If the value is a date or time, use <time> instead, which has the same purpose but a defined format.

Syntax

```
<data value="machine value">human text</data>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, palpable content
Permitted content	Phrasing content
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLDataElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
value	text	Required. The machine-readable form of the content.	HTML5

<data>: attribute by attribute

Each attribute of <data> explained in detail, with a minimal example you can copy.

value

Values: text | Since: HTML5

Required. The machine-readable form of the content.

Write value="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<data value="value">...</data>
```

<data>: worked examples

Product codes

```
<ul>
  <li><data value="SKU-1001">Blue notebook</data></li>
  <li><data value="SKU-1002">Red notebook</data></li>
</ul>
```

Numbers written in words

```
<p>We sold <data value="1000000">one million</data> copies.</p>
```

Default browser CSS

```
data { display: inline; }
```

Accessibility

- The value attribute is not read by screen readers; the visible text must be understandable alone.

Common mistakes

- Using <data> for dates; use <time>.

See also

<time>, <meter>

Quick card: <datalist>

Predefined options for an input

The <datalist> element contains a set of <option> elements that represent suggested values for an <input>. The input is linked to the list with its list attribute, which must equal the datalist's id. The user can pick a suggestion or type any other value, which makes it a combination of a text box and a drop-down list (a 'combobox').

At a glance

Status	CURRENT
Versions	HTML5
Category	Forms
Closing tag	Required unless noted under Tag omission
Display	none
Own attributes	None (global attributes only)
Related	<input>, <option>, <select>

Minimal example

```
<label for="browser">Favourite browser</label>
<input id="browser" name="browser" list="browsers">
<datalist id="browsers">
  <option value="Chrome">
  <option value="Firefox">
  <option value="Safari">
  <option value="Edge">
</datalist>
```

Most common mistake

Mismatched id and list values.

<datalist> — Predefined options for an input

Category: Forms | Status: CURRENT | Versions: HTML5

Description

The <datalist> element contains a set of <option> elements that represent suggested values for an <input>. The input is linked to the list with its list attribute, which must equal the datalist's id. The user can pick a suggestion or type any other value, which makes it a combination of a text box and a drop-down list (a 'combobox').

The datalist itself is never displayed. Browsers show the suggestions in their own way, usually as a drop-down that filters as the user types. It works with text, search, url, tel, email, number, range, color, date and time inputs, though support for non-text types varies.

Syntax

```
<input list="id">
<datalist id="id">
  <option value="...">
</datalist>
```

Technical summary

Property	Value
Void element	No
Default display	none
Content categories	Flow content, phrasing content
Permitted content	Either phrasing content or zero or more <option> elements

Property	Value
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLDataListElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<datalist>: worked examples

Browser suggestions

```
<label for="browser">Favourite browser</label>
<input id="browser" name="browser" list="browsers">
<datalist id="browsers">
  <option value="Chrome">
  <option value="Firefox">
  <option value="Safari">
  <option value="Edge">
</datalist>
```

Labelled values

```
<input list="codes" name="country">
<datalist id="codes">
  <option value="EG">Egypt</option>
  <option value="SA">Saudi Arabia</option>
</datalist>
```

Some browsers show the label next to the value.

Tick marks on a range slider

```
<input type="range" min="0" max="100" list="ticks">
<datalist id="ticks">
  <option value="0">
  <option value="50">
  <option value="100">
</datalist>
```

Default browser CSS

```
datalist { display: none; }
```

Accessibility

- Support in screen readers is inconsistent; consider a visible hint about available values.

Common mistakes

- Mismatched id and list values.
- Expecting the user to be limited to the options (use <select> for that).

See also

<input>, <option>, <select>

Quick card: <dd>

Description details

The <dd> element provides the description, definition or value for the preceding term (<dt>) in a description list (<dl>). One term may have several <dd> elements, and several terms may share one <dd>. Browsers indent <dd> from the left by default.

At a glance

Status	CURRENT
Versions	HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Text content
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	nowrap
Related	<dl>, <dt>

Minimal example

```
<dl>
  <dt>HTML</dt>
  <dd>The language that structures web pages.</dd>
  <dt>CSS</dt>
  <dd>The language that styles web pages.</dd>
</dl>
```

Most common mistake

Using <dd> outside <dl>.

<dd> — Description details

Category: Text content | Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <dd> element provides the description, definition or value for the preceding term (<dt>) in a description list (<dl>). One term may have several <dd> elements, and several terms may share one <dd>. Browsers indent <dd> from the left by default.

Syntax

```
<dl>
  <dt>Term</dt>
  <dd>Description</dd>
</dl>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	None
Permitted content	Flow content
Permitted parents	<dl> or inside <dl>, after a <dt> or <dd>
Tag omission	End tag may be omitted if followed by another <dd> or <dt>, or if there is no more content in the parent
DOM interface	HTMLElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
nowrap	yes | no	Obsolete, non-standard. Prevented wrapping.	IE

<dd>: attribute by attribute

Each attribute of <dd> explained in detail, with a minimal example you can copy.

nowrap

Values: yes | no | Since: IE

Obsolete, non-standard. Prevented wrapping.

Write nowrap="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<dd nowrap="yes">...</dd>
```

<dd>: worked examples

Glossary

```
<dl>
  <dt>HTML</dt>
  <dd>The language that structures web pages.</dd>
  <dt>CSS</dt>
  <dd>The language that styles web pages.</dd>
</dl>
```

Several descriptions for one term

```
<dl>
  <dt>Footer</dt>
  <dd>The bottom section of a page.</dd>
  <dd>An HTML element: &lt;footer&gt;.</dd>
</dl>
```

Default browser CSS

```
dd { display: block; margin-inline-start: 40px; }
```

Accessibility

- Screen readers announce the list structure so users know which description belongs to which term.

Common mistakes

- Using <dd> outside <dl>.
- Using <dd> just for indentation.

See also

<dl>, <dt>

Quick card: <del>

Deleted text

The <del> element marks text that has been deleted from a document, typically to show changes between versions ('track changes'). Browsers render it with a line through it. It is usually paired with <ins>, which marks inserted text.

At a glance

Status	CURRENT
Versions	HTML 4.01, HTML5
Category	Demarcating edits
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	cite, datetime
Related	<ins>, <s>, <strike>

Minimal example

```
<p>The meeting is on <del datetime="2026-09-10">Monday</del> <ins
datetime="2026-09-10">Tuesday</ins>.</p>
```

Most common mistake

Using <del> for a discounted price; use <s>.

<del> — Deleted text

Category: Demarcating edits | Status: CURRENT | Versions: HTML 4.01, HTML5

Description

The <del> element marks text that has been deleted from a document, typically to show changes between versions ('track changes'). Browsers render it with a line through it. It is usually paired with <ins>, which marks inserted text.

<del> may contain either phrasing or flow content depending on where it is placed, but it should not cross the boundaries of block elements: to delete two paragraphs, wrap each in its own <del>.

For text that is no longer accurate but not part of an edit history (such as an old price), use <s> instead.

Syntax

```
<del datetime="YYYY-MM-DD" cite="URL">deleted text</del>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, palpable content
Permitted content	Transparent
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted

Property	Value
DOM interface	HTMLModElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
cite	URL	A URL explaining the change, such as a link to a change log or meeting minutes.	HTML 4.01
datetime	date or date-time string	When the change was made, in the format YYYY-MM-DD or YYYY-MM-DDThh:mm:ssZ.	HTML 4.01

<del>: attribute by attribute

Each attribute of <del> explained in detail, with a minimal example you can copy.

cite

Values: URL | Since: HTML 4.01

A URL explaining the change, such as a link to a change log or meeting minutes.

Write cite="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<del cite="https://example.com/page.html">...</del>
```

datetime

Values: date or date-time string | Since: HTML 4.01

When the change was made, in the format YYYY-MM-DD or YYYY-MM-DDThh:mm:ssZ.

Write datetime="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<del datetime="date">...</del>
```

<del>: worked examples

Showing a correction

```
<p>The meeting is on <del datetime="2026-09-10">Monday</del> <ins
datetime="2026-09-10">Tuesday</ins>.</p>
```

A completed to-do item

```
<ul>
  <li><del>Buy milk</del></li>
  <li>Write HTML</li>
</ul>
```

Default browser CSS

```
del { text-decoration: line-through; }
```

Accessibility

- Most screen readers do not announce <del> by default. If the deletion is important, add visually hidden text such as 'deleted:' or use CSS ::before content with speak.

Common mistakes

- Using <del> for a discounted price; use <s>.
- Using <strike>, which is obsolete.

See also

<ins>, <s>, <strike>

Quick card: <details>

Disclosure widget

The <details> element creates a disclosure widget: a box that can be opened and closed by the user to show or hide its content, with no JavaScript at all. The first child should be a <summary> element, which provides the always-visible label and the clickable arrow. If there is no <summary> the browser shows the word 'Details'.

At a glance

Status	CURRENT
Versions	HTML5 (5.1)
Category	Interactive elements
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	open, name
Related	<summary>, <dialog>

Minimal example

```
<details>
  <summary>How do I centre a div?</summary>
  <p>Use <code>display: flex; justify-content: center; align-items:
center;</code> on the parent.</p>
</details>
```

Most common mistake

Putting <summary> anywhere other than first.

<details> — Disclosure widget

Category: Interactive elements | Status: CURRENT | Versions: HTML5 (5.1)

Description

The <details> element creates a disclosure widget: a box that can be opened and closed by the user to show or hide its content, with no JavaScript at all. The first child should be a <summary> element, which provides the always-visible label and the clickable arrow. If there is no <summary> the browser shows the word 'Details'.

The open attribute controls whether the content is visible. Adding or removing it from script opens or closes the widget, and the element fires a toggle event when its state changes. Giving several <details> the same name attribute makes them exclusive, like an accordion: opening one closes the others.

Syntax

```
<details>
  <summary>Label</summary>
  content
</details>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	Flow content, sectioning root, interactive content, palpable content
Permitted content	One <summary> followed by flow content

Property	Value
Permitted parents	Any element that accepts flow content
Tag omission	Neither tag may be omitted
DOM interface	HTMLDetailsElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
open	boolean	The details are visible. Absent means collapsed.	HTML5
name	text	Groups details elements so that only one in the group can be open at a time.	Living Standard

<details>: attribute by attribute

Each attribute of <details> explained in detail, with a minimal example you can copy.

open

Values: boolean | Since: HTML5

The details are visible. Absent means collapsed.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<details open>...</details>
```

name

Values: text | Since: Living Standard

Groups details elements so that only one in the group can be open at a time.

Write name="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<details name="value">...</details>
```

<details>: worked examples

FAQ item

```
<details>
  <summary>How do I centre a div?</summary>
  <p>Use <code>display: flex; justify-content: center; align-items:
center;</code> on the parent.</p>
</details>
```

Open by default

```
<details open>
  <summary>Shipping information</summary>
  <p>Delivery takes 2-4 days.</p>
</details>
```

Accordion with the name attribute

```
<details name="faq"><summary>Question 1</summary><p>Answer 1</p></
details>
<details name="faq"><summary>Question 2</summary><p>Answer 2</p></
details>
```

Styling the arrow

```
<style>
  summary { cursor: pointer; font-weight: bold; }
  details[open] summary { color: #b90000; }
</style>
```

Default browser CSS

```
details { display: block; }
```

Accessibility

- Fully keyboard accessible and announced as a button with expanded/collapsed state, out of the box.
- Do not put interactive elements inside <summary>.

Common mistakes

- Putting <summary> anywhere other than first.
- Using open="false" (which still means open).

See also

<summary>, <dialog>

Quick card: <dfn>

Definition term

The <dfn> element marks the term that is being defined in the surrounding sentence or paragraph. The nearest paragraph, description list group or section is the definition. Browsers render it in italics. If the element has a title attribute, that is the term being defined; if it contains an <abbr> with a title, the abbreviation's expansion is the term; otherwise the text content is the term.

At a glance

Status	CURRENT
Versions	HTML 3.2, HTML 4.01, HTML5
Category	Text-level semantics
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	title
Related	<abbr>, <dl>, <dt>

Minimal example

```
<p>A <dfn>void element</dfn> is an element that cannot have any
content and therefore has no closing tag.</p>
```

Most common mistake

Using <dfn> on every occurrence of a term; use it only where it is defined.

<dfn> — Definition term

Category: Text-level semantics | Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

Description

The <dfn> element marks the term that is being defined in the surrounding sentence or paragraph. The nearest paragraph, description list group or section is the definition. Browsers render it in italics. If the element has a title attribute, that is the term being defined; if it contains an <abbr> with a title, the abbreviation's expansion is the term; otherwise the text content is the term.

Syntax

```
<dfn>term</dfn>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, palpable content
Permitted content	Phrasing content, but no <dfn> descendants
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
title	text	The term being defined, if different from the content.	HTML 4.01

<dfn>: attribute by attribute

Each attribute of <dfn> explained in detail, with a minimal example you can copy.

title

Values: text | Since: HTML 4.01

The term being defined, if different from the content.

Write title="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<dfn title="value">...</dfn>
```

<dfn>: worked examples

Defining a term

```
<p>A <dfn>void element</dfn> is an element that cannot have any
content and therefore has no closing tag.</p>
```

Linking to the definition

```
<p>A <dfn id="def-footer">footer</dfn> is the bottom section of a
page.</p>
...
<p>Put the copyright in the <a href="#def-footer">footer</a>.</p>
```

Default browser CSS

```
dfn { font-style: italic; }
```

Accessibility

- No special announcement; purely semantic.

Common mistakes

- Using <dfn> on every occurrence of a term; use it only where it is defined.

See also

<abbr>, <dl>, <dt>

Quick card: <dialog>

Dialog box

The <dialog> element represents a dialog box or other interactive component such as a confirmation prompt, an alert, a subwindow or a modal overlay. It is hidden by default and is shown with the open attribute or, preferably, with the JavaScript methods show() (non-modal) and showModal() (modal). A modal dialog blocks interaction with the rest of the page, is displayed on top of everything else, and can be closed with the Escape key.

At a glance

Status	CURRENT
Versions	HTML 5.2 / Living Standard
Category	Interactive elements
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	open, closedby
Related	<details>, <form>, <button>

Minimal example

```
<dialog id="confirm">
  <form method="dialog">
    <p>Delete this item?</p>
    <button value="cancel">Cancel</button>
    <button value="ok">Delete</button>
  </form>
</dialog>
<button onclick="document.getElementById('confirm').showModal(
)">Delete</button>
<script>
  const d = document.getElementById('confirm');
```

```
  d.addEventListener('close', () => console.log('User chose', d.
returnValue));
</script>
```

Most common mistake

Setting the open attribute directly for modals (no backdrop, no focus trap).

<dialog> — Dialog box

Category: Interactive elements | Status: CURRENT | Versions: HTML 5.2 / Living Standard

Description

The <dialog> element represents a dialog box or other interactive component such as a confirmation prompt, an alert, a subwindow or a modal overlay. It is hidden by default and is shown with the open attribute or, preferably, with the JavaScript methods show() (non-modal) and showModal() (modal). A modal dialog blocks interaction with the rest of the page, is displayed on top of everything else, and can be closed with the Escape key.

A <form method="dialog"> inside the dialog closes it when submitted and sets the dialog's returnValue to the value of the submit button. The ::backdrop pseudo-element styles the dimmed area behind a modal dialog.

Syntax

```
<dialog id="d">...</dialog>
<script>document.getElementById('d').showModal()</script>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	Flow content, sectioning root
Permitted content	Flow content

Property	Value
Permitted parents	Any element that accepts flow content
Tag omission	Neither tag may be omitted
DOM interface	HTMLDialogElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
open	boolean	The dialog is visible. Set it with showModal() rather than by hand so that focus and the backdrop work correctly.	HTML 5.2
closedby	any | closerequest | none	Which user actions close the dialog: any (Escape, backdrop click, close request), closerequest (Escape only, the default for modal), or none.	Living Standard

<dialog>: attribute by attribute

Each attribute of <dialog> explained in detail, with a minimal example you can copy.

open

Values: boolean | Since: HTML 5.2

The dialog is visible. Set it with showModal() rather than by hand so that focus and the backdrop work correctly.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<dialog open>...</dialog>
```

closedby

Values: any | closerequest | none | Since: Living Standard

Which user actions close the dialog: any (Escape, backdrop click, close request), closerequest (Escape only, the default for modal), or none.

Write closedby="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<dialog closedby="any">...</dialog>
```

<dialog>: worked examples

Modal confirmation

```
<dialog id="confirm">
  <form method="dialog">
    <p>Delete this item?</p>
    <button value="cancel">Cancel</button>
    <button value="ok">Delete</button>
  </form>
</dialog>
<button onclick="document.getElementById('confirm').showModal(
)">Delete</button>
<script>
  const d = document.getElementById('confirm');
  d.addEventListener('close', () => console.log('User chose', d.
returnValue));
</script>
```

Styling the backdrop

```
<style>
  dialog::backdrop { background: rgba(0, 0, 0, 0.6); }
  dialog { border: none; border-radius: 12px; padding: 24px; }
</style>
```

Default browser CSS

```
dialog { position: absolute; inset-inline: 0; width: fit-content;
margin: auto; border: solid; padding: 1em; background: Canvas; color:
CanvasText; }
dialog:not([open]) { display: none; }
```

Accessibility

- showModal() traps focus inside the dialog and returns it when closed, which custom modals often get wrong.
- Give the dialog an accessible name with aria-labelledby pointing at its heading.
- Always provide a visible close button.

Common mistakes

- Setting the open attribute directly for modals (no backdrop, no focus trap).
- Nesting a dialog inside a button or link.

See also

<details>, <form>, <button>

Quick card: <dir>

Directory list (obsolete)

The <dir> element was a list of short items, intended to be shown in columns like a file directory listing. Browsers never implemented the columns and rendered it like <ul>. It was deprecated in HTML 4.01 and removed in HTML5. Use <ul> instead.

At a glance

Status	OBSOLETE
Versions	HTML 1, HTML 2.0, HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5
Category	Obsolete text content
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	compact
Related	, <menu>

Minimal example

```
<!-- Old -->
<dir><li>index.html</li><li>style.css</li></dir>

<!-- New -->
<ul><li>index.html</li><li>style.css</li></ul>
```

Most common mistake

Any use.

<dir> — Directory list (obsolete)

Category: Obsolete text content | Status: OBSOLETE | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

Description

The <dir> element was a list of short items, intended to be shown in columns like a file directory listing. Browsers never implemented the columns and rendered it like <ul>. It was deprecated in HTML 4.01 and removed in HTML5. Use <ul> instead.

Syntax

```
<dir><li>item</li></dir>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	Historical
Permitted content	elements
Permitted parents	Flow content
Tag omission	Neither
DOM interface	HTMLDirectoryElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
compact	boolean	Obsolete. Render more compactly.	HTML 2.0

<dir>: attribute by attribute

Each attribute of <dir> explained in detail, with a minimal example you can copy.

compact

Values: boolean | Since: HTML 2.0

Obsolete. Render more compactly.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<dir compact>...</dir>
```

<dir>: worked examples

Replacement

```
<!-- Old -->
<dir><li>index.html</li><li>style.css</li></dir>

<!-- New -->
<ul><li>index.html</li><li>style.css</li></ul>
```

Default browser CSS

```
dir { display: block; list-style-type: disc; margin: 1em 0; padding-
inline-start: 40px; }
```

Common mistakes

- Any use.

See also

, <menu>

Quick card:

Generic block container

The element (division) is a generic container for flow content. It has no meaning of its own and no effect on the content or layout until it is styled with CSS (using class or id) or manipulated with JavaScript. Use it to group elements for styling purposes, for layout (flexbox, grid), or when no other element is more appropriate.

At a glance

Status	CURRENT
Versions	HTML 3.2, HTML 4.01, HTML5
Category	Text content
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	align
Related	, <section>, <article>, <main>, <header>, <footer>

Minimal example

```
<style>
  .card { border: 1px solid #ccc; border-radius: 8px; padding: 16px; }
</style>
<div class="card">
  <h2>Pizza</h2>
  <p>Delicious and cheesy.</p>
</div>
```

Most common mistake

Using where a semantic element exists.

— Generic block container

Category: Text content | Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

Description

The element (division) is a generic container for flow content. It has no meaning of its own and no effect on the content or layout until it is styled with CSS (using class or id) or manipulated with JavaScript. Use it to group elements for styling purposes, for layout (flexbox, grid), or when no other element is more appropriate.

Because it carries no meaning, should be a last resort. Before using it ask whether <header>, <nav>, <main>, <section>, <article>, <aside>, <footer>, <figure> or another element describes the content better. A page built only from divs (so-called 'div soup') works visually but tells assistive technology and search engines nothing about its structure.

The inline counterpart of is . Since HTML5, may also be used inside <dl> to wrap a <dt>/<dd> group.

Syntax

```
<div class="name">...</div>
```

Technical summary

Property	Value
Void element	No
Default display	block

Property	Value
Content categories	Flow content, palpable content
Permitted content	Flow content; inside <dl>: one or more <dt> followed by one or more <dd>
Permitted parents	Any element that accepts flow content, and <dl>
Tag omission	Neither tag may be omitted
DOM interface	HTMLDivElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
align	left | center | right | justify	Obsolete. Horizontal alignment of the content. Use CSS text-align or margin.	HTML 3.2

: attribute by attribute

Each attribute of explained in detail, with a minimal example you can copy.

align

Values: left | center | right | justify | Since: HTML 3.2

Obsolete. Horizontal alignment of the content. Use CSS text-align or margin.

Write align="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<div align="left">...</div>
```

: worked examples

Grouping for styling

```
<style>
  .card { border: 1px solid #ccc; border-radius: 8px; padding: 16px; }
</style>
<div class="card">
  <h2>Pizza</h2>
  <p>Delicious and cheesy.</p>
</div>
```

Layout with flexbox

```
<style>
  .row { display: flex; gap: 16px; }
  .row > div { flex: 1; background: #eee; padding: 8px; }
</style>
<div class="row">
  <div>Column 1</div>
  <div>Column 2</div>
  <div>Column 3</div>
</div>
```

Grouping a term and description in a list

```
<dl>
  <div>
    <dt>Name</dt>
    <dd>Ahmed</dd>
  </div>
  <div>
    <dt>Age</dt>
    <dd>20</dd>
  </div>
</dl>
```

Div versus semantic elements

```
<!-- Div soup -->
<div class="header">...</div>
<div class="nav">...</div>
<div class="footer">...</div>

<!-- Semantic -->
<header>...</header>
<nav>...</nav>
<footer>...</footer>
```

Both look identical; the second is understood by screen readers and search engines.

Default browser CSS

```
div { display: block; }
```

Accessibility

- A has no role. If you make it interactive with JavaScript you must add role, tabindex and keyboard handling yourself; usually a <button> is the right choice instead.

Common mistakes

- Using where a semantic element exists.
- Using as a button or link.
- Putting inside <p> (invalid; the browser closes the paragraph).

See also

, <section>, <article>, <main>, <header>, <footer>

Quick card: <dl>

Description list

The <dl> element represents a description list: a list of groups of terms (<dt>) and their descriptions (<dd>). Common uses are glossaries, dictionaries, metadata displays (key: value pairs), FAQ lists and product specifications.

At a glance

Status	CURRENT
Versions	HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Text content
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	compact
Related	<dt>, <dd>, ,

Minimal example

```
<dl>
  <dt>Tag</dt>
  <dd>The markup inside angle brackets, such as &lt;p&gt;.</dd>
  <dt>Element</dt>
  <dd>The opening tag, content and closing tag together.</dd>
</dl>
```

Most common mistake

Putting anything other than <dt>, <dd>, , <script>, <template> directly inside <dl>.

<dl> — Description list

Category: Text content | Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <dl> element represents a description list: a list of groups of terms (<dt>) and their descriptions (<dd>). Common uses are glossaries, dictionaries, metadata displays (key: value pairs), FAQ lists and product specifications.

In HTML 4 it was called a 'definition list' and meant only for definitions. HTML5 renamed it and broadened the meaning to any name-value groups. Since HTML5 each group may optionally be wrapped in a for styling.

Syntax

```
<dl>
  <dt>Term</dt>
  <dd>Description</dd>
</dl>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	Flow content; palpable if it contains at least one group
Permitted content	Zero or more groups each consisting of one or more <dt> followed by one or more <dd>, optionally mixed with <script> and <template>; or zero or more elements each containing such a group
Permitted parents	Any element that accepts flow content

Property	Value
Tag omission	Neither tag may be omitted
DOM interface	HTMLDListElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
compact	boolean	Obsolete. Render more compactly.	HTML 2.0

<dl>: attribute by attribute

Each attribute of <dl> explained in detail, with a minimal example you can copy.

compact

Values: boolean | Since: HTML 2.0

Obsolete. Render more compactly.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<dl compact>...</dl>
```

<dl>: worked examples

Glossary

```
<dl>
  <dt>Tag</dt>
  <dd>The markup inside angle brackets, such as &lt;p&gt;.</dd>
  <dt>Element</dt>
  <dd>The opening tag, content and closing tag together.</dd>
</dl>
```

Product specifications as key-value pairs

```
<dl>
  <dt>Weight</dt>
  <dd>1.2 kg</dd>
  <dt>Colour</dt>
  <dd>Black</dd>
  <dt>Warranty</dt>
  <dd>2 years</dd>
</dl>
```

Multiple terms sharing one description

```
<dl>
  <dt>Colour</dt>
  <dt>Color</dt>
  <dd>British and American spellings of the same word.</dd>
</dl>
```

Horizontal layout with CSS grid

```
<style>
  dl { display: grid; grid-template-columns: max-content 1fr; gap:
4px 16px; }
  dt { font-weight: bold; }
  dd { margin: 0; }
</style>
```

Default browser CSS

```
dl { display: block; margin: 1em 0; }
```

Accessibility

- Screen readers announce it as a list with terms and descriptions (support varies).
- Do not use <dl> to mark up dialogue (speaker: line); it is not a name-value list.

Common mistakes

- Putting anything other than <dt>, <dd>, , <script>, <template> directly inside <dl>.
- Using <dl> for indentation.

See also

<dt>, <dd>, <ul>,

Quick card: <dt>

Description term

The <dt> element specifies a term, name or key in a description list (<dl>). It is followed by one or more <dd> elements that describe it. Several <dt> elements in a row share the following <dd>. A <dt> may not contain headings, sections, headers or footers.

At a glance

Status	CURRENT
Versions	HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Text content
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	None (global attributes only)
Related	<dl>, <dd>, <dfn>

Minimal example

```
<dl>
  <dt>Footer</dt>
  <dd>The bottom section of a page.</dd>
</dl>
```

Most common mistake

Using <dt> outside <dl>.

<dt> — Description term

Category: Text content | Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <dt> element specifies a term, name or key in a description list (<dl>). It is followed by one or more <dd> elements that describe it. Several <dt> elements in a row share the following <dd>. A <dt> may not contain headings, sections, headers or footers.

Syntax

```
<dt>Term</dt>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	None
Permitted content	Flow content, but no <header>, <footer>, sectioning content or heading content
Permitted parents	<dl> or inside <dl>, before a <dd> or another <dt>
Tag omission	End tag may be omitted if followed by another <dt> or a <dd>
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<dt>: worked examples

Term and description

```
<dl>
  <dt>Footer</dt>
  <dd>The bottom section of a page.</dd>
</dl>
```

Default browser CSS

```
dt { display: block; }
```

Common mistakes

- Using <dt> outside <dl>.
- Putting a heading inside <dt>.

See also

<dl>, <dd>, <dfn>

Quick card:

Emphasis

The element marks text that has stress emphasis: the word or phrase you would say more forcefully if you were reading the sentence aloud. Changing which word is emphasised changes the meaning of the sentence. Browsers render it in italics.

At a glance

Status	CURRENT
Versions	HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Text-level semantics
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	None (global attributes only)
Related	, <i>, <b>, <mark>, <cite>

Minimal example

```
<p><em>I</em> did not say he stole the money.</p>
<p>I did not say he <em>stole</em> the money.</p>
<p>I did not say he stole <em>the money</em>.</p>
```

Most common mistake

Using for every italic, such as book titles (<cite>) or foreign words (<i>).

— Emphasis

Category: Text-level semantics | Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The element marks text that has stress emphasis: the word or phrase you would say more forcefully if you were reading the sentence aloud. Changing which word is emphasised changes the meaning of the sentence. Browsers render it in italics.

 is not the same as <i>. <i> marks text in an alternative voice or mood (a technical term, a foreign phrase, a ship name) without emphasis. And it is not the same as , which marks importance, seriousness or urgency rather than spoken stress. Nested elements indicate a greater degree of emphasis.

If you only want italic text for visual reasons, with no emphasis intended, use CSS font-style: italic on a instead.

Syntax

```
<em>text</em>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, palpable content

Property	Value
Permitted content	Phrasing content
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

: worked examples

Emphasis changes meaning

```
<p><em>I</em> did not say he stole the money.</p>
<p>I did not say he <em>stole</em> the money.</p>
<p>I did not say he stole <em>the money</em>.</p>
```

Each sentence has the same words but a different meaning because of where the stress falls.

em, i and strong compared

```
<p>You <em>must</em> read the <i>Odyssey</i>. <strong>Warning:</
strong> it is long.</p>
```

Default browser CSS

```
em { font-style: italic; }
```

Accessibility

- Some screen readers change voice pitch for ; most do not by default, so do not rely on it to carry critical meaning.

Common mistakes

- Using for every italic, such as book titles (<cite>) or foreign words (<i>).
- Using for whole paragraphs.

See also

, <i>, <b>, <mark>, <cite>

Quick card: <embed>

External content

The <embed> element embeds external content at a specified point in the document. The content is provided by an external application or plug-in, or is a natively supported type such as an image, video, PDF or HTML page. It is a void element with no fallback content.

At a glance

Status	CURRENT
Versions	Netscape extension (1995), standardised in HTML5
Category	Embedded content
Closing tag	None (void element)
Display	inline
Own attributes	src, type, width, height, Any other attribute
Related	<object>, <iframe>, <video>, <audio>, <picture>

Minimal example

```
<embed src="guide.pdf" type="application/pdf" width="100%"
height="600">
```

Most common mistake

Using <embed> for video or audio.

<embed> — External content

Category: Embedded content | Status: CURRENT | Versions: Netscape extension (1995), standardised in HTML5

Description

The <embed> element embeds external content at a specified point in the document. The content is provided by an external application or plug-in, or is a natively supported type such as an image, video, PDF or HTML page. It is a void element with no fallback content.

It was a Netscape invention widely used for Flash movies and was finally standardised in HTML5. Today, for video use <video>, for audio use <audio>, for other pages use <iframe>, and for PDFs <iframe> or <object> are more flexible because they allow fallback content.

Syntax

```
<embed src="file.pdf" type="application/pdf" width="600" height="400">
```

Technical summary

Property	Value
Void element	Yes (no closing tag)
Default display	inline
Content categories	Flow content, phrasing content, embedded content, interactive content, palpable content
Permitted content	None (void element)
Permitted parents	Any element that accepts embedded content
Tag omission	No end tag

Property	Value
DOM interface	HTMLEmbedElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
src	URL	The URL of the resource.	Netscape / HTML5
type	MIME type	The type of the resource, used to choose the plug-in or handler.	Netscape / HTML5
width	pixels	Width of the display area.	Netscape / HTML5
height	pixels	Height of the display area.	Netscape / HTML5
Any other attribute	text	Additional attributes are passed to the plug-in as parameters (for example, old Flash used quality, wmode, allowfullscreen).	Netscape

<embed>: attribute by attribute

Each attribute of <embed> explained in detail, with a minimal example you can copy.

src

Values: URL | Since: Netscape / HTML5

The URL of the resource.

Write src="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<embed src="https://example.com/page.html">
```

type

Values: MIME type | Since: Netscape / HTML5

The type of the resource, used to choose the plug-in or handler.

Write type="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<embed type="text/plain">
```

width

Values: pixels | Since: Netscape / HTML5

Width of the display area.

Write width="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<embed width="3">
```

height

Values: pixels | Since: Netscape / HTML5

Height of the display area.

Write height="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<embed height="3">
```

Any other attribute

Values: text | Since: Netscape

Additional attributes are passed to the plug-in as parameters (for example, old Flash used quality, wmode, allowfullscreen).

Write Any other attribute="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<embed Any other attribute="value">
```

<embed>: worked examples

Embedding a PDF

```
<embed src="guide.pdf" type="application/pdf" width="100%"
height="600">
```

Embedding a video (prefer <video>)

```
<embed src="clip.mp4" type="video/mp4" width="640" height="360">
```

Default browser CSS

```
embed { display: inline; }
```

Accessibility

- There is no fallback content and no accessible name; add a title attribute and provide a link to the resource next to it.

Common mistakes

- Using <embed> for video or audio.
- Writing a closing tag.

See also

<object>, <iframe>, <video>, <audio>, <picture>

Quick card: <fencedframe>

Fenced frame (experimental)

The <fencedframe> element embeds another HTML page in a way that is even more isolated than an <iframe>: the embedded page cannot communicate with the embedding page, and the URL is chosen through privacy-preserving APIs rather than given directly. It is part of the Privacy Sandbox proposals for showing personalised advertisements without cross-site tracking. It is not yet a standard and is only available in Chromium browsers.

At a glance

Status	EXPERIMENTAL
Versions	Experimental (Chromium, 2024)
Category	Embedded content
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	allow, width
Related	<iframe>

Minimal example

```
<fencedframe id="ad"></fencedframe>
<script>
  // config comes from an API such as Protected Audience
  // document.getElementById('ad').config = config;
</script>
```

Most common mistake

Using it in production sites today.

<fencedframe> — Fenced frame (experimental)

Category: Embedded content | Status: EXPERIMENTAL | Versions: Experimental (Chromium, 2024)

Description

The <fencedframe> element embeds another HTML page in a way that is even more isolated than an <iframe>: the embedded page cannot communicate with the embedding page, and the URL is chosen through privacy-preserving APIs rather than given directly. It is part of the Privacy Sandbox proposals for showing personalised advertisements without cross-site tracking. It is not yet a standard and is only available in Chromium browsers.

Syntax

```
<fencedframe width="300" height="250"></fencedframe>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, embedded content, interactive content, palpable content
Permitted content	None
Permitted parents	Any element that accepts embedded content
Tag omission	Neither
DOM interface	HTMLFencedFrameElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
allow	permissions policy	Features allowed inside the frame.	Experimental
width / height	pixels	Size of the frame.	Experimental

<fencedframe>: attribute by attribute

Each attribute of <fencedframe> explained in detail, with a minimal example you can copy.

allow

Values: permissions policy | Since: Experimental

Features allowed inside the frame.

Write allow="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<fencedframe allow="permissions policy">...</fencedframe>
```

width / height

Values: pixels | Since: Experimental

Size of the frame.

Write width="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<fencedframe width="3">...</fencedframe>
```

<fencedframe>: worked examples

Configured from JavaScript

```
<fencedframe id="ad"></fencedframe>
<script>
  // config comes from an API such as Protected Audience
  // document.getElementById('ad').config = config;
</script>
```

Accessibility

- Same considerations as <iframe>.

Common mistakes

- Using it in production sites today.

See also

<iframe>

Quick card: <fieldset>

Form field group

The <fieldset> element groups related controls and labels inside a form, for example all the fields of a postal address, or a set of radio buttons that answer one question. The optional <legend> element, which must be the first child, gives the group a caption. Browsers draw a border around the group with the legend placed on the border.

At a glance

Status	CURRENT
Versions	HTML 4.01, HTML5
Category	Forms
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	disabled, form, name
Related	<legend>, <form>, <input>, <label>

Minimal example

```
<fieldset>
  <legend>Payment method</legend>
  <label><input type="radio" name="pay" value="cash" checked> Cash on
delivery</label><br>
  <label><input type="radio" name="pay" value="wallet"> Mobile
wallet</label><br>
  <label><input type="radio" name="pay" value="card"> Card</label>
</fieldset>
```

Most common mistake

Using a heading instead of <legend> (the heading is not linked to the group).

<fieldset> — Form field group

Category: Forms | Status: CURRENT | Versions: HTML 4.01, HTML5

Description

The <fieldset> element groups related controls and labels inside a form, for example all the fields of a postal address, or a set of radio buttons that answer one question. The optional <legend> element, which must be the first child, gives the group a caption. Browsers draw a border around the group with the legend placed on the border.

Setting disabled on a fieldset disables every control inside it at once, which is convenient for showing or hiding optional sections of a form.

Syntax

```
<fieldset>
  <legend>Caption</legend>
  ...controls...
</fieldset>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	Flow content, sectioning root, listed, form-associated, palpable content
Permitted content	An optional <legend> followed by flow content
Permitted parents	Any element that accepts flow content
Tag omission	Neither tag may be omitted

Property	Value
DOM interface	HTMLFieldSetElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
disabled	boolean	Disables all descendant form controls (except those inside the <legend>).	HTML 4.01
form	form id	Associates the fieldset with a form elsewhere in the document.	HTML5
name	text	The name of the group, accessible from the form's elements collection.	HTML5

<fieldset>: attribute by attribute

Each attribute of <fieldset> explained in detail, with a minimal example you can copy.

disabled

Values: boolean | Since: HTML 4.01

Disables all descendant form controls (except those inside the <legend>).

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<fieldset disabled>...</fieldset>
```

form

Values: form id | Since: HTML5

Associates the fieldset with a form elsewhere in the document.

Write form="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<fieldset form="form id">...</fieldset>
```

name

Values: text | Since: HTML5

The name of the group, accessible from the form's elements collection.

Write name="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<fieldset name="value">...</fieldset>
```

<fieldset>: worked examples

Radio button group

```
<fieldset>
  <legend>Payment method</legend>
  <label><input type="radio" name="pay" value="cash" checked> Cash on
delivery</label><br>
  <label><input type="radio" name="pay" value="wallet"> Mobile
wallet</label><br>
  <label><input type="radio" name="pay" value="card"> Card</label>
</fieldset>
```

Disabling a whole section

```
<fieldset disabled>
  <legend>Shipping address (same as billing)</legend>
  <input name="street" placeholder="Street">
  <input name="city" placeholder="City">
</fieldset>
```

Removing the default border

```
<style>
  fieldset { border: none; padding: 0; margin: 0 0 1em; }
  legend { font-weight: bold; padding: 0; }
</style>
```

Default browser CSS

```
fieldset { display: block; margin-inline: 2px; padding: 0.35em 0.75em
0.625em; border: 2px groove; min-inline-size: min-content; }
```

Accessibility

- A fieldset with a legend is the standard, well-supported way to give a group of radio buttons or checkboxes a shared accessible name.
- Screen readers announce the legend when the user enters the group.

Common mistakes

- Using a heading instead of <legend> (the heading is not linked to the group).
- Nesting fieldsets too deeply.

- Forgetting that fieldset is display: block and has odd default styling that is hard to override (for example, it ignores display: flex in some browsers).

See also

<legend>, <form>, <input>, <label>

Quick card: <figcaption>

Figure caption

The <figcaption> element provides a caption or legend for the content of its parent <figure> element. It must be either the first or the last child of the <figure>. The caption is programmatically associated with the figure, which gives the figure an accessible name.

At a glance

Status	CURRENT
Versions	HTML5
Category	Text content
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	None (global attributes only)
Related	<figure>, <caption>, <img>

Minimal example

```
<figure>
  <img src="pyramids.jpg" alt="The three pyramids of Giza at sunset">
  <figcaption>Figure 1: The Giza pyramids, photographed in 2026.</
figcaption>
</figure>
```

Most common mistake

Placing figcaption in the middle of the figure.

<figcaption> — Figure caption

Category: Text content | Status: CURRENT | Versions: HTML5

Description

The <figcaption> element provides a caption or legend for the content of its parent <figure> element. It must be either the first or the last child of the <figure>. The caption is programmatically associated with the figure, which gives the figure an accessible name.

Syntax

```
<figure>
  <img ...>
  <figcaption>Caption</figcaption>
</figure>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	None
Permitted content	Flow content
Permitted parents	<figure>, as its first or last child
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<figcaption>: worked examples

Image with caption

```
<figure>
  <img src="pyramids.jpg" alt="The three pyramids of Giza at sunset">
  <figcaption>Figure 1: The Giza pyramids, photographed in 2026.</
figcaption>
</figure>
```

Caption first

```
<figure>
  <figcaption>Listing 2: A minimal page</figcaption>
  <pre><code>&lt;!DOCTYPE html&gt;...</code></pre>
</figure>
```

Default browser CSS

```
figcaption { display: block; }
```

Accessibility

- The caption becomes the figure's accessible name. The image's alt should describe the image; the caption should not merely repeat it.

Common mistakes

- Placing figcaption in the middle of the figure.
- Using figcaption outside a figure.

See also

<figure>, <caption>, <img>

Quick card: <figure>

Figure with optional caption

The <figure> element represents self-contained content that is referenced from the main flow but could be moved elsewhere (to an appendix, a sidebar or another page) without affecting the meaning of the text: an illustration, a diagram, a photo, a code listing, a chart, a poem, a table. An optional <figcaption> gives it a caption.

At a glance

Status	CURRENT
Versions	HTML5
Category	Text content
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	None (global attributes only)
Related	<figcaption>, <img>, <picture>, <table>

Minimal example

```
<figure>
  <img src="nile.jpg" alt="Boats on the Nile at Luxor" width="600"
height="400">
  <figcaption>Feluccas on the Nile.</figcaption>
</figure>
```

Most common mistake

Wrapping every image in a figure regardless of meaning.

<figure> — Figure with optional caption

Category: Text content | Status: CURRENT | Versions: HTML5

Description

The <figure> element represents self-contained content that is referenced from the main flow but could be moved elsewhere (to an appendix, a sidebar or another page) without affecting the meaning of the text: an illustration, a diagram, a photo, a code listing, a chart, a poem, a table. An optional <figcaption> gives it a caption.

A figure is not only for images. The key idea is that the content is a unit that the text refers to ('see Figure 3'). Purely decorative images are not figures.

Syntax

```
<figure>
  content
  <figcaption>Caption</figcaption>
</figure>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	Flow content, sectioning root, palpable content
Permitted content	A <figcaption> followed by flow content, or flow content followed by a <figcaption>, or flow content alone
Permitted parents	Any element that accepts flow content

Property	Value
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<figure>: worked examples

Photo

```
<figure>
  <img src="nile.jpg" alt="Boats on the Nile at Luxor" width="600"
height="400">
  <figcaption>Feluccas on the Nile.</figcaption>
</figure>
```

Code listing

```
<figure>
  <pre><code>footer { text-align: center; }</code></pre>
  <figcaption>Centring the footer text.</figcaption>
</figure>
```

Multiple images in one figure

```
<figure>
  <img src="before.jpg" alt="Room before painting">
  <img src="after.jpg" alt="Room after painting, walls now light
blue">
  <figcaption>Before and after.</figcaption>
</figure>
```

Removing default margins

```
<style>
  figure { margin: 0; }
  figure img { max-width: 100%; height: auto; }
</style>
```

Default browser CSS

```
figure { display: block; margin: 1em 40px; }
```

Accessibility

- Exposed with the 'figure' role; the figcaption labels it.

Common mistakes

- Wrapping every image in a figure regardless of meaning.
- Forgetting that browsers add a 40px left and right margin by default.

See also

<figcaption>, <img>, <picture>, <table>

Quick card: <font>

Font (obsolete)

The <font> element set the size, colour and typeface of its text. It was the main way to style text before CSS, was deprecated in HTML 4.01 and removed in HTML5. Browsers still render it for old pages. Every use of <font> can be replaced by CSS: font-size, color and font-family.

At a glance

Status	OBSOLETE
Versions	HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5
Category	Obsolete presentational
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	size, color, face
Related	<basefont>,

Minimal example

```
<!-- Old -->
<font face="Arial" size="5" color="#e60000">Sale!</font>

<!-- New -->
<span style="font-family: Arial, sans-serif; font-size: x-large;
color: #e60000">Sale!</span>
```

Most common mistake

Any use in new pages.

<font> — Font (obsolete)

Category: Obsolete presentational | Status: OBSOLETE | Versions: HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

Description

The <font> element set the size, colour and typeface of its text. It was the main way to style text before CSS, was deprecated in HTML 4.01 and removed in HTML5. Browsers still render it for old pages. Every use of <font> can be replaced by CSS: font-size, color and font-family.

The size attribute used a scale from 1 to 7 where 3 was the default; relative values such as +1 or -2 were also allowed.

Syntax

```
<font size="4" color="red" face="Arial">text</font>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Phrasing content (historical)
Permitted content	Phrasing content
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLFontElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
size	1-7 or +n / -n	Font size on the HTML scale: 1 = x-small, 2 = small, 3 = medium (default), 4 = large, 5 = x-large, 6 = xx-large, 7 = xxx-large.	HTML 3.2
color	colour name or #rrggbb	Text colour.	HTML 3.2
face	comma-separated font names	Typeface, tried in order.	HTML 3.2

<font>: attribute by attribute

Each attribute of <font> explained in detail, with a minimal example you can copy.

size

Values: 1-7 or +n / -n | Since: HTML 3.2

Font size on the HTML scale: 1 = x-small, 2 = small, 3 = medium (default), 4 = large, 5 = x-large, 6 = xx-large, 7 = xxx-large.

Write size="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<font size="1-7">...</font>
```

color

Values: colour name or #rrggbb | Since: HTML 3.2

Text colour.

Write color="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<font color="#336699">...</font>
```

face

Values: comma-separated font names | Since: HTML 3.2

Typeface, tried in order.

Write face="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<font face="value">...</font>
```

<font>: worked examples

Replacement

```
<!-- Old -->
<font face="Arial" size="5" color="#e60000">Sale!</font>

<!-- New -->
<span style="font-family: Arial, sans-serif; font-size: x-large;
color: #e60000">Sale!</span>
```

Accessibility

- Fixed font sizes set with <font> ignore user preferences.

Common mistakes

- Any use in new pages.

See also

<basefont>,

Quick card: <footer>

Footer

The <footer> element represents the footer of its nearest ancestor sectioning content or sectioning root: the page (<body>), an <article>, a <section>, an <aside> or a <nav>. A footer typically contains information about the section it belongs to: who wrote it, copyright data, links to related documents, contact details, a site map, or navigation back to the top.

At a glance

Status	CURRENT
Versions	HTML5
Category	Content sectioning
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	None (global attributes only)
Related	<header>, <address>, <nav>, <article>, <section>, <body>

Minimal example

```
<body>
  <header><h1>My Blog</h1></header>
  <main>
    <p>Today I learned <em>a lot</em> about HTML.</p>
  </main>
  <footer>
    <p>&copy; 2026 My Blog. All rights reserved.</p>
    <nav>
      <a href="about.html">About</a> |
      <a href="privacy.html">Privacy</a> |
      <a href="#top">Back to top</a>
    </nav>
```

```
    <address>Contact: <a href="mailto:me@example.com">me@example.com</
a></address>
  </footer>
</body>
```

Most common mistake

Nesting a <footer> inside another <footer> or a <header>.

<footer> — Footer

Category: Content sectioning | Status: CURRENT | Versions: HTML5

Description

The <footer> element represents the footer of its nearest ancestor sectioning content or sectioning root: the page (<body>), an <article>, a <section>, an <aside> or a <nav>. A footer typically contains information about the section it belongs to: who wrote it, copyright data, links to related documents, contact details, a site map, or navigation back to the top.

The most common use is the page footer at the bottom of <body>, but you can have as many footers as you have sections. A footer inside an <article> gives the article's metadata (author, date, tags); a footer inside a <blockquote> gives the source of the quotation.

Visually, a <footer> is nothing more than a block like a . Its value is semantic: it tells browsers, assistive technology and search engines what the content is. When a footer is a direct child of <body> it is exposed as a 'contentinfo' landmark that screen reader users can jump to. Contact information inside a footer should be wrapped in <address>. A footer may not contain another <footer> or a <header>.

Syntax

```
<footer>...</footer>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	Flow content, palpable content
Permitted content	Flow content, but no <footer> or <header> descendants
Permitted parents	Any element that accepts flow content, but not <address>
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<footer>: worked examples

Page footer

```
<body>
  <header><h1>My Blog</h1></header>
  <main>
    <p>Today I learned <em>a lot</em> about HTML.</p>
  </main>
  <footer>
    <p>&copy; 2026 My Blog. All rights reserved.</p>
    <nav>
      <a href="about.html">About</a> |
      <a href="privacy.html">Privacy</a> |
      <a href="#top">Back to top</a>
    </nav>
    <address>Contact: <a href="mailto:me@example.com">me@example.com</
a></address>
  </footer>
</body>
```

Styling a footer with CSS

```
<style>
  footer {
    background-color: #222;
    color: #fff;
    text-align: center;
    padding: 20px;
    font-family: Arial, sans-serif;
  }
  footer a { color: #ffd166; }
</style>
```

font-family sets the letter style for all text in the footer; text-align centres it.

Article footer with metadata

```
<article>
  <h2>Learning the footer element</h2>
  <p>...</p>
  <footer>
    <p>Posted by Ahmed on <time datetime="2026-09-11">11 September
2026</time></p>
    <p>Tags: html, semantics</p>
  </footer>
</article>
```

Multi-column site footer

```
<style>
  .cols { display: flex; flex-wrap: wrap; gap: 32px; justify-content:
center; }
</style>
<footer>
  <div class="cols">
    <section>
      <h3>Shop</h3>
      <ul><li><a href="/books">Books</a></li><li><a href="/
deals">Deals</a></li></ul>
    </section>
    <section>
      <h3>Help</h3>
      <ul><li><a href="/faq">FAQ</a></li><li><a href="/
returns">Returns</a></li></ul>
    </section>
  </div>
  <p>&copy; 2026 Book Store</p>
</footer>
```

Sticky footer at the bottom of short pages

```
<style>
  html, body { height: 100%; margin: 0; }
  body { display: flex; flex-direction: column; }
  main { flex: 1; }
</style>
<body>
  <main>Short content</main>
  <footer>Always at the bottom</footer>
</body>
```

Default browser CSS

```
footer { display: block; }
```

Accessibility

- A body-level footer is announced as 'content information' landmark.
- Only one body-level footer should exist; footers inside articles and sections are not landmarks.
- Keep 'back to top' links inside the footer so keyboard users can find them.

Common mistakes

- Nesting a <footer> inside another <footer> or a <header>.
- Using <footer> for a sidebar or unrelated content.
- Using when <footer> is available.
- Putting the main navigation only in the footer.

See also

<header>, <address>, <nav>, <article>, <section>, <body>

Quick card: <form>

Form

The <form> element represents a section of the document containing interactive controls (text boxes, check boxes, radio buttons, drop-down lists, buttons and so on) for collecting information from the user and sending it to a server. When the form is submitted, the browser gathers the name and value of every control that has a name, encodes them, and sends them to the URL in the action attribute using the HTTP method in the method attribute.

At a glance

Status	CURRENT
Versions	HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Forms
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	action, method, enctype, name, target, autocomplete, novalidate, accept-charset, rel, accept
Related	<input>, <button>, <label>, <select>, <textarea>, <fieldset>, <output>

Minimal example

```
<form action="/contact" method="post">
  <p>
    <label for="name">Name</label>
    <input id="name" name="name" required>
  </p>
  <p>
    <label for="email">Email</label>
    <input id="email" name="email" type="email" required>
  </p>
```

```
  <p>
    <label for="msg">Message</label>
    <textarea id="msg" name="message" rows="5" required></textarea>
  </p>
  <button type="submit">Send</button>
</form>
```

Most common mistake

Nesting forms.

<form> — Form

Category: Forms | Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <form> element represents a section of the document containing interactive controls (text boxes, check boxes, radio buttons, drop-down lists, buttons and so on) for collecting information from the user and sending it to a server. When the form is submitted, the browser gathers the name and value of every control that has a name, encodes them, and sends them to the URL in the action attribute using the HTTP method in the method attribute.

With method="get" the data is appended to the URL as a query string (?name=value&...); this is suitable for searches and filters that can be bookmarked. With method="post" the data is sent in the request body; use it for anything that changes data on the server, sends passwords or uploads files.

HTML5 added built-in validation: attributes such as required, pattern, min, max and type="email" are checked before submission and the browser shows an error message. The novalidate attribute turns this off. Forms may not be nested inside other forms.

Syntax

```
<form action="URL" method="post">
  ...controls...
  <button>Submit</button>
</form>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	Flow content, palpable content
Permitted content	Flow content, but no <form> descendants
Permitted parents	Any element that accepts flow content
Tag omission	Neither tag may be omitted
DOM interface	HTMLFormElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
action	URL	Where to send the data. If omitted, the data is sent to the current page URL.	HTML 2.0
method	get | post | dialog	The HTTP method. get puts data in the URL; post sends it in the body; dialog closes the enclosing <dialog>.	HTML 2.0
enctype	application/x-www-form-urlencoded | multipart/form-data | text/plain	How the data is encoded for post. Use multipart/form-data when the form contains <input type="file">.	HTML 2.0
name	text	A name for the form, used by scripts (document.forms.name). Must be unique among forms.	HTML 2.0

Attribute	Values	Description	Since
target	_self | _blank | _parent | _top | name	Where to display the response.	HTML 4.01
autocomplete	on | off	Whether the browser may autofill controls in this form. Default on.	HTML5
novalidate	boolean	Do not validate the form on submission.	HTML5
accept-charset	space-separated encodings	The character encodings the server accepts. Use utf-8.	HTML 4.01
rel	link types	Relationship of the target resource, for example noopener or noreferrer.	Living Standard
accept	MIME types	Obsolete. Use accept on <input type="file"> instead.	HTML 4.01

<form>: attribute by attribute

Each attribute of <form> explained in detail, with a minimal example you can copy.

action

Values: URL | Since: HTML 2.0

Where to send the data. If omitted, the data is sent to the current page URL.

Write action="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<form action="https://example.com/page.html">...</form>
```

method

Values: get | post | dialog | Since: HTML 2.0

The HTTP method. get puts data in the URL; post sends it in the body; dialog closes the enclosing <dialog>.

Write method="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<form method="get">...</form>
```

enctype

Values: application/x-www-form-urlencoded | multipart/form-data | text/plain | Since: HTML 2.0

How the data is encoded for post. Use multipart/form-data when the form contains <input type="file">.

Write enctype="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<form enctype="application">...</form>
```

name

Values: text | Since: HTML 2.0

A name for the form, used by scripts (document.forms.name). Must be unique among forms.

Write name="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<form name="value">...</form>
```

target

Values: _self | _blank | _parent | _top | name | Since: HTML 4.01

Where to display the response.

Write target="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<form target="_self">...</form>
```

autocomplete

Values: on | off | Since: HTML5

Whether the browser may autofill controls in this form. Default on.

Write autocomplete="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<form autocomplete="on">...</form>
```

novalidate

Values: boolean | Since: HTML5

Do not validate the form on submission.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<form novalidate>...</form>
```

accept-charset

Values: space-separated encodings | Since: HTML 4.01

The character encodings the server accepts. Use utf-8.

Write accept-charset="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<form accept-charset="value">...</form>
```

rel

Values: link types | Since: Living Standard

Relationship of the target resource, for example noopener or noreferrer.

Write rel="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<form rel="link types">...</form>
```

accept

Values: MIME types | Since: HTML 4.01

Obsolete. Use accept on <input type="file"> instead.

Write accept="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<form accept="text/plain">...</form>
```

<form>: worked examples

Contact form

```
<form action="/contact" method="post">
  <p>
    <label for="name">Name</label>
    <input id="name" name="name" required>
  </p>
  <p>
    <label for="email">Email</label>
    <input id="email" name="email" type="email" required>
  </p>
  <p>
    <label for="msg">Message</label>
    <textarea id="msg" name="message" rows="5" required></textarea>
  </p>
  <button type="submit">Send</button>
</form>
```

Search form using GET

```
<form action="/search" method="get" role="search">
  <label for="q">Search</label>
  <input id="q" name="q" type="search">
  <button>Go</button>
</form>
```

Submitting with 'html' typed produces the URL /search?q=html.

File upload

```
<form action="/upload" method="post" enctype="multipart/form-data">
  <input type="file" name="photo" accept="image/*">
  <button>Upload</button>
</form>
```

Handling submission with JavaScript

```
<form id="f">
  <input name="city">
  <button>Save</button>
</form>
<script>
  document.getElementById('f').addEventListener('submit', e => {
    e.preventDefault();
    const data = new FormData(e.target);
    console.log(data.get('city'));
  });
</script>
```

Default browser CSS

```
form { display: block; margin-top: 0; }
```

Accessibility

- Every control needs a <label>.
- Group related controls with <fieldset> and <legend>.
- Make error messages visible and associate them with the field using aria-describedby.
- Do not rely on placeholder text as the only label.

Common mistakes

- Nesting forms.
- Forgetting name attributes, so nothing is submitted.
- Forgetting enctype for file uploads.
- Using GET for passwords or large data.
- Having no submit button and relying on Enter alone.

See also

<input>, <button>, <label>, <select>, <textarea>, <fieldset>, <output>

Quick card: <frame>

Frame (obsolete)

The <frame> element defined one rectangular sub-window inside a <frameset>, each displaying a separate HTML document. Frames were used in the late 1990s to keep a navigation menu fixed while the content scrolled. They caused many problems: bookmarks and the back button did not work as expected, search engines could not index the pages properly, printing was unreliable and screen readers struggled. HTML5 removed <frame> and <frameset>. Use CSS for layout and <iframe> when you truly need to embed another document.

At a glance

Status	OBSOLETE
Versions	Netscape 2 (1996), HTML 4.01 Frameset; obsolete in HTML5
Category	Obsolete frames
Closing tag	None (void element)
Display	block
Own attributes	src, name, frameborder, marginwidth, noresize, scrolling, longdesc
Related	<frameset>, <noframes>, <iframe>

Minimal example

```
<style>
  body { display: grid; grid-template-columns: 200px 1fr; height:
100vh; margin: 0; }
  nav { position: sticky; top: 0; }
</style>
<body>
```

```
  <nav>Menu</nav>
  <main>Content</main>
</body>
```

Most common mistake

Any use.

<frame> — Frame (obsolete)

Category: Obsolete frames | Status: OBSOLETE | Versions: Netscape 2 (1996), HTML 4.01 Frameset; obsolete in HTML5

Description

The <frame> element defined one rectangular sub-window inside a <frameset>, each displaying a separate HTML document. Frames were used in the late 1990s to keep a navigation menu fixed while the content scrolled. They caused many problems: bookmarks and the back button did not work as expected, search engines could not index the pages properly, printing was unreliable and screen readers struggled. HTML5 removed <frame> and <frameset>. Use CSS for layout and <iframe> when you truly need to embed another document.

Syntax

```
<frameset cols="200,*">
  <frame src="menu.html" name="menu">
  <frame src="main.html" name="main">
</frameset>
```

Technical summary

Property	Value
Void element	Yes (no closing tag)
Default display	block
Content categories	Historical
Permitted content	None
Permitted parents	<frameset>

Property	Value
Tag omission	No end tag
DOM interface	HTMLFrameElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
src	URL	The document to display.	HTML 4.01
name	text	Name used as a link target.	HTML 4.01
frameborder	0 | 1	Whether to draw a border.	HTML 4.01
marginwidth / marginheight	pixels	Margins inside the frame.	HTML 4.01
noresize	boolean	User cannot resize the frame.	HTML 4.01
scrolling	yes | no | auto	Scrollbar behaviour.	HTML 4.01
longdesc	URL	Link to a long description.	HTML 4.01

<frame>: attribute by attribute

Each attribute of <frame> explained in detail, with a minimal example you can copy.

src

Values: URL | Since: HTML 4.01

The document to display.

Write src="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<frame src="https://example.com/page.html">
```

name

Values: text | Since: HTML 4.01

Name used as a link target.

Write name="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<frame name="value">
```

frameborder

Values: 0 | 1 | Since: HTML 4.01

Whether to draw a border.

Write frameborder="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<frame frameborder="0">
```

marginwidth / marginheight

Values: pixels | Since: HTML 4.01

Margins inside the frame.

Write marginwidth="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<frame marginwidth="3">
```

noresize

Values: boolean | Since: HTML 4.01

User cannot resize the frame.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<frame noresize>
```

scrolling

Values: yes | no | auto | Since: HTML 4.01

Scrollbar behaviour.

Write scrolling="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<frame scrolling="yes">
```

longdesc

Values: URL | Since: HTML 4.01

Link to a long description.

Write longdesc="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<frame longdesc="https://example.com/page.html">
```

<frame>: worked examples

Modern replacement

```
<style>
  body { display: grid; grid-template-columns: 200px 1fr; height:
100vh; margin: 0; }
  nav { position: sticky; top: 0; }
</style>
<body>
  <nav>Menu</nav>
  <main>Content</main>
</body>
```

Accessibility

- Frames were a major accessibility barrier.

Common mistakes

- Any use.

See also

<frameset>, <noframes>, <iframe>

Quick card: <frameset>

Frameset (obsolete)

The <frameset> element replaced <body> in a frames document and divided the window into rows and columns, each filled by a <frame> or a nested <frameset>. It required the HTML 4.01 Frameset DOCTYPE. It is obsolete in HTML5. See <frame> for the reasons and the modern replacement.

At a glance

Status	OBSOLETE
Versions	Netscape 2, HTML 4.01 Frameset; obsolete in HTML5
Category	Obsolete frames
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	cols, rows, border, onload
Related	<frame>, <noframes>, <iframe>

Minimal example

```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Frameset//EN">
<html>
<head><title>Frames</title></head>
<frameset cols="25%,75%">
  <frame src="nav.html">
  <frame src="content.html">
  <noframes><body>Your browser does not support frames.</body></
noframes>
</frameset>
</html>
```

Most common mistake

Any use.

<frameset> — Frameset (obsolete)

Category: Obsolete frames | Status: OBSOLETE | Versions: Netscape 2, HTML 4.01 Frameset; obsolete in HTML5

Description

The <frameset> element replaced <body> in a frames document and divided the window into rows and columns, each filled by a <frame> or a nested <frameset>. It required the HTML 4.01 Frameset DOCTYPE. It is obsolete in HTML5. See <frame> for the reasons and the modern replacement.

Syntax

```
<frameset rows="80,*">...</frameset>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	Historical
Permitted content	<frame>, <frameset>, <noframes>
Permitted parents	<html>, instead of <body>
Tag omission	Neither
DOM interface	HTMLFrameSetElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
cols	comma-separated sizes	Column widths in pixels, percentages or * (remaining space).	HTML 4.01
rows	comma-separated sizes	Row heights.	HTML 4.01
border, frameborder, framespacing	pixels / 0 | 1	Border appearance.	HTML 4.01 / non-standard
onload, onunload, and other window events	script	Window event handlers, as on <body>.	HTML 4.01

<frameset>: attribute by attribute

Each attribute of <frameset> explained in detail, with a minimal example you can copy.

cols

Values: comma-separated sizes | Since: HTML 4.01

Column widths in pixels, percentages or * (remaining space).

Write cols="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<frameset cols="comma-separated sizes">...</frameset>
```

rows

Values: comma-separated sizes | Since: HTML 4.01

Row heights.

Write rows="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<frameset rows="comma-separated sizes">...</frameset>
```

border, frameborder, framespacing

Values: pixels / 0 | 1 | Since: HTML 4.01 / non-standard

Border appearance.

Write border="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<frameset border="3">...</frameset>
```

onload, onunload, and other window events

Values: script | Since: HTML 4.01

Window event handlers, as on <body>.

Write onload="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<frameset onload="script">...</frameset>
```

<frameset>: worked examples

Historical example

```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Frameset//EN">
<html>
<head><title>Frames</title></head>
<frameset cols="25%,75%">
  <frame src="nav.html">
  <frame src="content.html">
  <noframes><body>Your browser does not support frames.</body></
noframes>
</frameset>
</html>
```

Common mistakes

- Any use.

See also

<frame>, <noframes>, <iframe>

Quick card: <h1>

Headings h1 to h6

The <h1> to <h6> elements represent six levels of section headings. <h1> is the highest (most important) level and <h6> the lowest. Headings describe the topic of the section that follows them, and together they form the outline of the document, like the table of contents of a book.

At a glance

Status	CURRENT
Versions	HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Content sectioning
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	align
Related	<hgroup>, <section>, <article>, <header>, <p>

Minimal example

```
<h1>Cooking basics</h1>
  <h2>Equipment</h2>
    <h3>Knives</h3>
    <h3>Pans</h3>
  <h2>Techniques</h2>
    <h3>Boiling</h3>
    <h3>Frying</h3>
      <h4>Deep frying</h4>
```

Most common mistake

Choosing the level by size.

<h1> — Headings h1 to h6

Category: Content sectioning | Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

This entry also covers: <h2>, <h3>, <h4>, <h5>, <h6>

Description

The <h1> to <h6> elements represent six levels of section headings. <h1> is the highest (most important) level and <h6> the lowest. Headings describe the topic of the section that follows them, and together they form the outline of the document, like the table of contents of a book.

Use heading levels to express structure, not to choose a font size. A page should normally have a single <h1> describing the whole page, <h2> for its major sections, <h3> for sub-sections inside those, and so on. Do not skip levels (for example jumping from <h2> to <h4>) because it confuses the outline. If a heading looks too big or too small, change it with CSS, not by choosing a different level.

Headings are one of the most important elements for accessibility: screen reader users navigate pages by jumping from heading to heading, and search engines give heading text extra weight.

Syntax

```
<h1>Main title</h1>
<h2>Section</h2>
<h3>Sub-section</h3>
```

Technical summary

Property	Value
Void element	No

Property	Value
Default display	block
Content categories	Flow content, heading content, palpable content
Permitted content	Phrasing content
Permitted parents	Any element that accepts flow content; also directly inside <hgroup>
Tag omission	Neither tag may be omitted
DOM interface	HTMLHeadingElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
align	left | center | right | justify	Obsolete. Use CSS text-align.	HTML 3.2

<h1>: attribute by attribute

Each attribute of <h1> explained in detail, with a minimal example you can copy.

align

Values: left | center | right | justify | Since: HTML 3.2

Obsolete. Use CSS text-align.

Write align="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<h1 align="left">...</h1>
```

<h1>: worked examples

A correct outline

```
<h1>Cooking basics</h1>
  <h2>Equipment</h2>
    <h3>Knives</h3>
    <h3>Pans</h3>
  <h2>Techniques</h2>
    <h3>Boiling</h3>
    <h3>Frying</h3>
      <h4>Deep frying</h4>
```

Indentation is only for illustration; headings are written at the same indentation as their content.

Default sizes

```
<h1>Heading 1 (2em)</h1>
<h2>Heading 2 (1.5em)</h2>
<h3>Heading 3 (1.17em)</h3>
<h4>Heading 4 (1em)</h4>
<h5>Heading 5 (0.83em)</h5>
<h6>Heading 6 (0.67em)</h6>
```

Changing the look without changing the level

```
<style>
  h2 { font-size: 1.2rem; text-transform: uppercase; letter-spacing:
0.1em; color: #555; }
</style>
<h2>Small-looking but still a level-2 heading</h2>
```

Heading with a subtitle

```
<hgroup>
  <h1>HTML Reference</h1>
  <p>Every tag from 1991 to today</p>
</hgroup>
```

Default browser CSS

```
h1 { display: block; font-size: 2em; margin-block: 0.67em; font-
weight: bold; }
```

Accessibility

- Screen reader users can list all headings and jump between them; a good heading structure is the single biggest navigation aid.

- Do not use headings for text that is merely large or bold.
- Do not leave headings empty.
- Each page should have one <h1>.

Common mistakes

- Choosing the level by size.
- Skipping levels.
- Several <h1> elements on a page (valid but unhelpful).
- Using <b> or <font size> instead of a heading.
- Placing a heading inside <p> or <a> incorrectly (a link may go inside a heading, not the reverse).

See also

<hgroup>, <section>, <article>, <header>, <p>

Quick card: <head>

Document head

The <head> element contains machine-readable information (metadata) about the document: its title, character encoding, links to style sheets and icons, scripts, and <meta> tags for search engines and social networks. Nothing inside <head> is displayed on the page itself, except the title, which appears in the browser tab.

At a glance

Status	CURRENT
Versions	HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Document metadata
Closing tag	Required unless noted under Tag omission
Display	none
Own attributes	profile
Related	<html>, <title>, <meta>, <link>, <style>, <script>, <base>

Minimal example

```
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Book Store - Home</title>
  <meta name="description" content="Buy PDF books and pay with mobile
wallet.">
  <link rel="icon" href="favicon.ico">
  <link rel="stylesheet" href="style.css">
  <script src="app.js" defer></script>
</head>
```

Most common mistake

Putting visible content (<p>, , <img>) in the head; the browser moves it to the body.

<head> — Document head

Category: Document metadata | Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <head> element contains machine-readable information (metadata) about the document: its title, character encoding, links to style sheets and icons, scripts, and <meta> tags for search engines and social networks. Nothing inside <head> is displayed on the page itself, except the title, which appears in the browser tab.

<head> is the first child of <html>. Every document must have exactly one <title> inside its head (unless the title is supplied by a higher-level protocol, such as an email subject). The tags may be omitted and the browser will create the element automatically, but always write them.

Syntax

```
<head>
  <meta charset="utf-8">
  <title>Title</title>
</head>
```

Technical summary

Property	Value
Void element	No
Default display	none
Content categories	None
Permitted content	Metadata content: exactly one <title>, at most one <base>, any number of <link>, <meta>, <script>, <style>, <noscript>, <template>

Property	Value
Permitted parents	<html>, as its first child
Tag omission	Start tag may be omitted if the first thing inside is an element; end tag may be omitted if not followed by whitespace or a comment
DOM interface	HTMLHeadElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
profile	URLs	Obsolete. Meta data profiles.	HTML 4.01

<head>: attribute by attribute

Each attribute of <head> explained in detail, with a minimal example you can copy.

profile

Values: URLs | Since: HTML 4.01

Obsolete. Meta data profiles.

Write profile="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<head profile="https://example.com/page.html">...</head>
```

<head>: worked examples

A complete, well-formed head

```
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Book Store - Home</title>
  <meta name="description" content="Buy PDF books and pay with mobile
wallet.">
  <link rel="icon" href="favicon.ico">
  <link rel="stylesheet" href="style.css">
  <script src="app.js" defer></script>
</head>
```

Order matters a little: charset first, then viewport, then title, then styles, then scripts.

Default browser CSS

```
head { display: none; }
```

Accessibility

- The <title> is the first thing a screen reader announces; make it descriptive and unique per page.

Common mistakes

- Putting visible content (<p>, , <img>) in the head; the browser moves it to the body.
- Omitting <title>.
- Placing <meta charset> after 1024 bytes of content.

See also

<html>, <title>, <meta>, <link>, <style>, <script>, <base>

Quick card: <header>

Header

The <header> element represents introductory content for its nearest sectioning ancestor or for the page: typically a group of headings, a logo, a search form, the author's name, and the main navigation. A page usually has one header at the top of <body>, but articles and sections may have their own headers too.

At a glance

Status	CURRENT
Versions	HTML5
Category	Content sectioning
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	None (global attributes only)
Related	<footer>, <nav>, <h1>, <hgroup>, <main>

Minimal example

```
<header>
  <img src="logo.svg" alt="Book Store" width="120" height="40">
  <nav>
    <a href="/">Home</a>
    <a href="/books">Books</a>
    <a href="/contact">Contact</a>
  </nav>
  <form role="search" action="/search"><input name="q" type="search"
aria-label="Search"></form>
</header>
```

Most common mistake

Nesting header inside header or footer.

<header> — Header

Category: Content sectioning | Status: CURRENT | Versions: HTML5

Description

The <header> element represents introductory content for its nearest sectioning ancestor or for the page: typically a group of headings, a logo, a search form, the author's name, and the main navigation. A page usually has one header at the top of <body>, but articles and sections may have their own headers too.

When a <header> is a direct child of <body> (not inside <article>, <aside>, <main>, <nav> or <section>) it is exposed as the 'banner' landmark. A header may not contain another <header> or a <footer>.

Syntax

```
<header>...</header>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	Flow content, palpable content
Permitted content	Flow content, but no <header> or <footer> descendants
Permitted parents	Any element that accepts flow content, but not <address>
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<header>: worked examples

Site header

```
<header>
  <img src="logo.svg" alt="Book Store" width="120" height="40">
  <nav>
    <a href="/">Home</a>
    <a href="/books">Books</a>
    <a href="/contact">Contact</a>
  </nav>
  <form role="search" action="/search"><input name="q" type="search"
aria-label="Search"></form>
</header>
```

Article header

```
<article>
  <header>
    <h2>Ten HTML tips</h2>
    <p>By Sara, <time datetime="2026-09-01">1 September 2026</time></
p>
  </header>
  <p>...</p>
</article>
```

Sticky header

```
<style>
  header { position: sticky; top: 0; background: white; box-shadow: 0
2px 4px rgba(0,0,0,.1); }
</style>
```

Default browser CSS

```
header { display: block; }
```

Accessibility

- A body-level header is the 'banner' landmark; there should be only one.
- Put the site's main <nav> inside the header so it is found quickly.

Common mistakes

- Nesting header inside header or footer.

- Using <header> for the heading text alone; a lone <h1> does not need a header wrapper.

See also

<footer>, <nav>, <h1>, <hgroup>, <main>

Quick card: <hgroup>

Heading group

The <hgroup> element groups a heading (<h1>-<h6>) with one or more <p> elements that contain a subtitle, alternative title, tagline or other secondary text. It tells the browser that the paragraphs belong to the heading rather than being ordinary content.

At a glance

Status	CURRENT
Versions	HTML5 (removed from W3C HTML 5.0, kept in the Living Standard with a new definition)
Category	Content sectioning
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	None (global attributes only)
Related	<h1>, <header>, <p>

Minimal example

```
<hgroup>
  <h1>The Complete HTML Reference</h1>
  <p>From HTML 1 to the Living Standard</p>
</hgroup>
```

Most common mistake

Placing two headings inside one hgroup (old HTML5 style).

<hgroup> — Heading group

Category: Content sectioning | Status: CURRENT | Versions: HTML5 (removed from W3C HTML 5.0, kept in the Living Standard with a new definition)

Description

The <hgroup> element groups a heading (<h1>-<h6>) with one or more <p> elements that contain a subtitle, alternative title, tagline or other secondary text. It tells the browser that the paragraphs belong to the heading rather than being ordinary content.

Its history is unusual: in early HTML5 drafts it grouped several headings of different levels and only the highest counted in the outline. The W3C dropped it in 2013, but the WHATWG kept it and in 2022 redefined it as described above. It must contain exactly one heading element.

Syntax

```
<hgroup>
  <h1>Title</h1>
  <p>Subtitle</p>
</hgroup>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	Flow content, heading content, palpable content
Permitted content	Zero or more <p>, then one <h1>-<h6>, then zero or more <p> (plus <script> and <template>)
Permitted parents	Any element that accepts flow content

Property	Value
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<hgroup>: worked examples

Title with tagline

```
<hgroup>
  <h1>The Complete HTML Reference</h1>
  <p>From HTML 1 to the Living Standard</p>
</hgroup>
```

Kicker above the headline

```
<hgroup>
  <p>Breaking news</p>
  <h2>New HTML element announced</h2>
</hgroup>
```

Default browser CSS

```
hgroup { display: block; }
```

Accessibility

- Exposed with role 'group'; the subtitle paragraphs are not read as headings, which is the desired behaviour.

Common mistakes

- Placing two headings inside one hgroup (old HTML5 style).
- Using a lower-level heading such as <h2> as the subtitle.

See also

<h1>, <header>, <p>

Quick card: <hr>

Thematic break (horizontal rule)

The <hr> element represents a thematic break between paragraph-level content: a change of scene in a story, a shift of topic within a section, or a separator between groups of options in a menu. Browsers render it as a horizontal line, which is where its name (horizontal rule) comes from.

At a glance

Status	CURRENT
Versions	HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Text content
Closing tag	None (void element)
Display	block
Own attributes	align, color, noshade, size, width
Related	<p>, , <section>

Minimal example

```
<p>The first chapter ends here.</p>
<hr>
<p>The story continues years later.</p>
```

Most common mistake

Using <hr> as a layout spacer.

<hr> — Thematic break (horizontal rule)

Category: Text content | Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <hr> element represents a thematic break between paragraph-level content: a change of scene in a story, a shift of topic within a section, or a separator between groups of options in a menu. Browsers render it as a horizontal line, which is where its name (horizontal rule) comes from.

In HTML 4 it was purely a visual line with attributes for size, width and colour. HTML5 kept the element but gave it the semantic meaning above and made the presentational attributes obsolete. If you only want a decorative line, use a CSS border instead of <hr>. It is a void element.

Syntax

```
<hr>
```

Technical summary

Property	Value
Void element	Yes (no closing tag)
Default display	block
Content categories	Flow content
Permitted content	None (void element)
Permitted parents	Any element that accepts flow content, and <select>

Property	Value
Tag omission	No end tag
DOM interface	HTMLHRElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
align	left | center | right	Obsolete. Alignment of the rule. Use CSS margin.	HTML 3.2
color	colour	Obsolete, non-standard. Colour of the rule. Use CSS border-color.	IE
noshade	boolean	Obsolete. Draw a solid line instead of a 3D groove. Use CSS.	HTML 3.2
size	pixels	Obsolete. Height of the rule. Use CSS height or border-width.	HTML 3.2
width	pixels or percentage	Obsolete. Width of the rule. Use CSS width.	HTML 3.2

<hr>: attribute by attribute

Each attribute of <hr> explained in detail, with a minimal example you can copy.

align

Values: left | center | right | Since: HTML 3.2

Obsolete. Alignment of the rule. Use CSS margin.

Write align="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<hr align="left">
```

color

Values: colour | Since: IE

Obsolete, non-standard. Colour of the rule. Use CSS border-color.

Write color="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<hr color="#336699">
```

noshade

Values: boolean | Since: HTML 3.2

Obsolete. Draw a solid line instead of a 3D groove. Use CSS.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<hr noshade>
```

size

Values: pixels | Since: HTML 3.2

Obsolete. Height of the rule. Use CSS height or border-width.

Write size="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<hr size="3">
```

width

Values: pixels or percentage | Since: HTML 3.2

Obsolete. Width of the rule. Use CSS width.

Write width="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<hr width="3">
```

<hr>: worked examples

Topic change

```
<p>The first chapter ends here.</p>
<hr>
<p>The story continues years later.</p>
```

Styled rule

```
<style>
  hr { border: none; border-top: 2px dashed #c8a24a; margin: 2em auto;
 width: 60%; }
</style>
<hr>
```

Separator inside a select list

```
<select>
  <option>Egypt</option>
  <option>Saudi Arabia</option>
  <hr>
  <option>Other</option>
</select>
```

Newer browsers draw a separator line between groups of options.

Default browser CSS

```
hr { display: block; margin: 0.5em auto; border: 1px inset; color:
gray; overflow: hidden; }
```

Accessibility

- Announced as 'separator' by screen readers. If the line is only decorative, use a CSS border so it is not announced.

Common mistakes

- Using <hr> as a layout spacer.
- Writing </hr>.

See also

<p>, <br>, <section>

Quick card: <html>

Document root

The <html> element is the root element of an HTML document: every other element is a descendant of it. It has exactly two children: <head> followed by <body>. It comes immediately after the <!DOCTYPE html> declaration.

At a glance

Status	CURRENT
Versions	HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Main root
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	lang, dir, xmlns, manifest, version
Related	<head>, <body>

Minimal example

```
<!DOCTYPE html>
<html lang="en">
<head><meta charset="utf-8"><title>Hello</title></head>
<body><p>Hello</p></body>
</html>
```

Most common mistake

Omitting lang.

<html> — Document root

Category: Main root | Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <html> element is the root element of an HTML document: every other element is a descendant of it. It has exactly two children: <head> followed by <body>. It comes immediately after the <!DOCTYPE html> declaration.

The most important attribute on <html> is lang, which declares the language of the page. It affects hyphenation, spell-checking, font selection, quotation marks, the voice used by screen readers and the behaviour of translation tools. For right-to-left languages add dir="rtl". Both tags may technically be omitted, but always write them.

Syntax

```
<!DOCTYPE html>
<html lang="en">
  <head>...</head>
  <body>...</body>
</html>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	None
Permitted content	One <head> followed by one <body>

Property	Value
Permitted parents	None (root element)
Tag omission	Start tag may be omitted if the first thing inside is not a comment; end tag may be omitted if not followed by a comment
DOM interface	HTMLHtmlElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
lang	BCP 47 language tag	The primary language of the document: en, en-GB, ar, ar-EG, fr, de, zh-Hans...	HTML 4.01
dir	ltr | rtl | auto	Text direction of the document.	HTML 4.01
xmlns	http://www.w3.org/1999/xhtml	XML namespace; required in XHTML, ignored in HTML.	XHTML 1.0
manifest	URL	Obsolete. Application cache manifest for offline pages. Replaced by service workers.	HTML5 (removed)
version	text	Obsolete. The HTML DTD version.	HTML 2.0

<html>: attribute by attribute

Each attribute of <html> explained in detail, with a minimal example you can copy.

lang

Values: BCP 47 language tag | Since: HTML 4.01

The primary language of the document: en, en-GB, ar, ar-EG, fr, de, zh-Hans...

Write lang="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<html lang="en">...</html>
```

dir

Values: ltr | rtl | auto | Since: HTML 4.01

Text direction of the document.

Write dir="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<html dir="ltr">...</html>
```

xmlns

Values: http://www.w3.org/1999/xhtml | Since: XHTML 1.0

XML namespace; required in XHTML, ignored in HTML.

Write xmlns="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<html xmlns="http:">...</html>
```

manifest

Values: URL | Since: HTML5 (removed)

Obsolete. Application cache manifest for offline pages. Replaced by service workers.

Write manifest="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<html manifest="https://example.com/page.html">...</html>
```

version

Values: text | Since: HTML 2.0

Obsolete. The HTML DTD version.

Write version="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<html version="value">...</html>
```

<html>: worked examples

English page

```
<!DOCTYPE html>
<html lang="en">
<head><meta charset="utf-8"><title>Hello</title></head>
<body><p>Hello</p></body>
</html>
```

Arabic page, right to left

```
<!DOCTYPE html>
<html lang="ar" dir="rtl">
<head><meta charset="utf-8"><title>مرحبا</title></head>
<body><p>مرحبا بكم</p></body>
</html>
```

Old DOCTYPEs for comparison

```
<!-- HTML 2.0 -->
<!DOCTYPE HTML PUBLIC "-//IETF//DTD HTML 2.0//EN">

<!-- HTML 3.2 -->
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 3.2 Final//EN">

<!-- HTML 4.01 Strict -->
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01//EN" "http://www.w3.org/
TR/html4/strict.dtd">

<!-- XHTML 1.0 Strict -->
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Strict//EN" "http://www.
w3.org/TR/xhtml1/DTD/xhtml1-strict.dtd">

<!-- HTML5 -->
<!DOCTYPE html>
```

Default browser CSS

```
html { display: block; }
```

Accessibility

- Always set lang. Without it screen readers may read the page in the wrong language with a heavy accent.

Common mistakes

- Omitting lang.

- Placing content outside <html>.
- Forgetting the DOCTYPE before it.

See also

<head>, <body>

Quick card:

Idiomatic text (italic)

The element marks a span of text that is set off from the normal prose for some reason other than emphasis or importance: an alternative voice or mood, a technical term, a taxonomic name (Homo sapiens), a phrase in another language, a thought, a ship's name, or a transliteration. Browsers render it in italics.

At a glance

Status	CURRENT
Versions	HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Text-level semantics
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	None (global attributes only)
Related	, <b>, <cite>, <dfn>

Minimal example

```
<p>The Egyptians say <i lang="ar">inshallah</i> often.</p>
<p>The domestic cat is <i>Felis catus</i>.</p>
```

Most common mistake

Using for icons with no text () is common in icon libraries but semantically wrong; add aria-hidden and a text label.

<i> — Idiomatic text (italic)

Category: Text-level semantics | Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <i> element marks a span of text that is set off from the normal prose for some reason other than emphasis or importance: an alternative voice or mood, a technical term, a taxonomic name (Homo sapiens), a phrase in another language, a thought, a ship's name, or a transliteration. Browsers render it in italics.

In HTML 4 <i> simply meant 'italic'. HTML5 gave it the meaning above so that it stays valid. Choose the most specific element first: for emphasis, <cite> for titles of works, <dfn> for defined terms, for importance. Use <i> only when none of those apply, and consider adding a class or lang attribute to say why the text is different.

Syntax

```
<i>text</i>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, palpable content
Permitted content	Phrasing content
Permitted parents	Any element that accepts phrasing content

Property	Value
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

: worked examples

Foreign phrase and scientific name

```
<p>The Egyptians say <i lang="ar">inshallah</i> often.</p>
<p>The domestic cat is <i>Felis catus</i>.</p>
```

A thought

```
<p><i>I should have used a footer</i>, she thought.</p>
```

Default browser CSS

```
i { font-style: italic; }
```

Accessibility

- No announcement in screen readers; use when the italic carries stress.

Common mistakes

- Using for icons with no text () is common in icon libraries but semantically wrong; add aria-hidden and a text label.
- Using instead of or <cite>.

See also

, <b>, <cite>, <dfn>

Quick card: <iframe>

Inline frame

The <iframe> element embeds another HTML page inside the current page, in a rectangular area called a nested browsing context. Each iframe has its own document, its own window object and its own history. Common uses are embedding videos from YouTube, maps, advertisements, payment forms, social media widgets and third-party tools.

At a glance

Status	CURRENT
Versions	Internet Explorer 3 (1996), HTML 4.01, HTML5
Category	Embedded content
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	src, srcdoc, title, name, width, height, sandbox, allow, allowfullscreen, loading, referrerpolicy, credentialless, csp, align, frameborder, longdesc, marginheight, scrolling, allowpaymentrequest
Related	<embed>, <object>, <frame>, <fencedframe>, <portal>

Minimal example

```
<iframe width="560" height="315"
  src="https://www.youtube.com/embed/qfPUMV9J5yw"
  title="HTML tutorial video"
  allow="accelerometer; autoplay; clipboard-write; encrypted-media;
gyroscope; picture-in-picture"
  allowfullscreen loading="lazy"></iframe>
```

Most common mistake

No title.

<iframe> — Inline frame

Category: Embedded content | Status: CURRENT | Versions: Internet Explorer 3 (1996), HTML 4.01, HTML5

Description

The <iframe> element embeds another HTML page inside the current page, in a rectangular area called a nested browsing context. Each iframe has its own document, its own window object and its own history. Common uses are embedding videos from YouTube, maps, advertisements, payment forms, social media widgets and third-party tools.

Because the embedded page may come from another site, iframes have security controls. The sandbox attribute restricts what the embedded page may do (run scripts, submit forms, open popups, navigate the top page). The allow attribute grants specific features such as camera or fullscreen. Sites can refuse to be framed with the X-Frame-Options or Content-Security-Policy headers.

Every iframe costs memory and processing time. Use loading="lazy" for iframes far down the page, and always give the iframe a title describing its content.

Syntax

```
<iframe src="URL" title="description" width="600" height="400"></
iframe>
```

Technical summary

Property	Value
Void element	No
Default display	inline

Property	Value
Content categories	Flow content, phrasing content, embedded content, interactive content, palpable content
Permitted content	None (the element must be empty; older browsers displayed content inside it as fallback)
Permitted parents	Any element that accepts embedded content
Tag omission	Neither tag may be omitted
DOM interface	HTMLIFrameElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
src	URL	The page to embed. about:blank shows an empty page.	HTML 4.01
srcdoc	HTML text	Inline HTML to display instead of loading src. Overrides src if present.	HTML5
title	text	A description of the embedded content for assistive technology. Strongly recommended.	HTML 4.01
name	text	A name that can be used as the target of links and forms.	HTML 4.01
width	pixels	Width of the frame (default 300).	HTML 4.01
height	pixels	Height of the frame (default 150).	HTML 4.01

Attribute	Values	Description	Since
sandbox	empty or space-separated tokens	Applies extra restrictions. Empty value = all restrictions. Tokens that lift restrictions: allow-downloads, allow-forms, allow-modals, allow-orientation-lock, allow-pointer-lock, allow-popups, allow-popups-to-escape-sandbox, allow-presentation, allow-same-origin, allow-scripts, allow-top-navigation, allow-top-navigation-by-user-activation, allow-top-navigation-to-custom-protocols.	HTML5
allow	permissions policy	Features the frame may use, for example allow="camera; microphone; fullscreen; geolocation; autoplay; picture-in-picture".	HTML5
allowfullscreen	boolean	Legacy form of allow="fullscreen".	HTML5
loading	eager | lazy	lazy defers loading until the frame is near the viewport.	Living Standard
referrerpolicy	referrer policy keyword	Which referrer to send when loading the frame.	HTML5
credentialless	boolean	Experimental: load the frame in a new, empty cookie/storage context.	Experimental
csp	policy string	Experimental: Content Security Policy to enforce on the embedded document.	Experimental

Attribute	Values	Description	Since
align	left | right | top | middle | bottom	Obsolete. Use CSS.	HTML 4.01
frameborder	0 | 1	Obsolete. Use CSS border.	HTML 4.01
longdesc	URL	Obsolete. Link to a long description.	HTML 4.01
marginheight / marginwidth	pixels	Obsolete. Use CSS in the framed document.	HTML 4.01
scrolling	yes | no | auto	Obsolete. Use CSS overflow in the framed document.	HTML 4.01
allowpaymentrequest	boolean	Obsolete. Use allow="payment".	HTML5 (removed)

<iframe>: attribute by attribute

Each attribute of <iframe> explained in detail, with a minimal example you can copy.

src

Values: URL | Since: HTML 4.01

The page to embed. about:blank shows an empty page.

Write src="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<iframe src="https://example.com/page.html">...</iframe>
```

srcdoc

Values: HTML text | Since: HTML5

Inline HTML to display instead of loading src. Overrides src if present.

Write srcdoc="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<iframe srcdoc="HTML text">...</iframe>
```

title

Values: text | Since: HTML 4.01

A description of the embedded content for assistive technology. Strongly recommended.

Write title="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<iframe title="value">...</iframe>
```

name

Values: text | Since: HTML 4.01

A name that can be used as the target of links and forms.

Write name="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<iframe name="value">...</iframe>
```

width

Values: pixels | Since: HTML 4.01

Width of the frame (default 300).

Write width="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<iframe width="3">...</iframe>
```

height

Values: pixels | Since: HTML 4.01

Height of the frame (default 150).

Write height="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<iframe height="3">...</iframe>
```

sandbox

Values: empty or space-separated tokens | Since: HTML5

Applies extra restrictions. Empty value = all restrictions. Tokens that lift restrictions: allow-downloads, allow-forms, allow-modals, allow-orientation-lock, allow-pointer-lock, allow-popups, allow-popups-to-escape-sandbox, allow-presentation, allow-same-origin, allow-scripts, allow-top-navigation, allow-top-navigation-by-user-activation, allow-top-navigation-to-custom-protocols.

Write sandbox="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<iframe sandbox="empty">...</iframe>
```

allow

Values: permissions policy | Since: HTML5

Features the frame may use, for example allow="camera; microphone; fullscreen; geolocation; autoplay; picture-in-picture".

Write allow="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<iframe allow="permissions policy">...</iframe>
```

allowfullscreen

Values: boolean | Since: HTML5

Legacy form of allow="fullscreen".

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<iframe allowfullscreen>...</iframe>
```

loading

Values: eager | lazy | Since: Living Standard

lazy defers loading until the frame is near the viewport.

Write loading="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<iframe loading="eager">...</iframe>
```

referrerpolicy

Values: referrer policy keyword | Since: HTML5

Which referrer to send when loading the frame.

Write referrerpolicy="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<iframe referrerpolicy="referrer policy keyword">...</iframe>
```

credentialless

Values: boolean | Since: Experimental

Experimental: load the frame in a new, empty cookie/storage context.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<iframe credentialless>...</iframe>
```

csp

Values: policy string | Since: Experimental

Experimental: Content Security Policy to enforce on the embedded document.

Write csp="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<iframe csp="policy string">...</iframe>
```

align

Values: left | right | top | middle | bottom | Since: HTML 4.01

Obsolete. Use CSS.

Write align="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<iframe align="left">...</iframe>
```

frameborder

Values: 0 | 1 | Since: HTML 4.01

Obsolete. Use CSS border.

Write frameborder="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<iframe frameborder="0">...</iframe>
```

longdesc

Values: URL | Since: HTML 4.01

Obsolete. Link to a long description.

Write longdesc="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<iframe longdesc="https://example.com/page.html">...</iframe>
```

marginheight / marginwidth

Values: pixels | Since: HTML 4.01

Obsolete. Use CSS in the framed document.

Write marginheight="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<iframe marginheight="3">...</iframe>
```

scrolling

Values: yes | no | auto | Since: HTML 4.01

Obsolete. Use CSS overflow in the framed document.

Write scrolling="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<iframe scrolling="yes">...</iframe>
```

allowpaymentrequest

Values: boolean | Since: HTML5 (removed)

Obsolete. Use allow="payment".

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<iframe allowpaymentrequest>...</iframe>
```

<iframe>: worked examples

Embedding a YouTube video

```
<iframe width="560" height="315"
  src="https://www.youtube.com/embed/qfPUMV9J5yw"
  title="HTML tutorial video"
  allow="accelerometer; autoplay; clipboard-write; encrypted-media;
gyroscope; picture-in-picture"
  allowfullscreen loading="lazy"></iframe>
```

Sandboxed untrusted content

```
<iframe src="https://untrusted.example.com/widget" title="Widget"
sandbox="allow-scripts"></iframe>
```

The widget can run scripts but cannot submit forms, open popups, or access cookies of its origin.

Inline document with srcdoc

```
<iframe title="Preview" srcdoc="<h1>Hello</h1><p>Rendered from srcdoc.
</p>"></iframe>
```

Responsive 16:9 video frame

```
<style>
  .video { aspect-ratio: 16 / 9; width: 100%; border: 0; }
</style>
<iframe class="video" src="..." title="Video"></iframe>
```

Targeting an iframe from a link

```
<iframe name="preview" title="Preview" src="about:blank"></iframe>
<a href="page1.html" target="preview">Load page 1 in the frame</a>
```

Default browser CSS

```
iframe { border: 2px inset; }
```

Accessibility

- Always provide a meaningful title; screen readers announce it when entering the frame.
- Content inside the iframe must itself be accessible; you cannot fix it from outside.
- Avoid iframes that steal keyboard focus or auto-play media.

Common mistakes

- No title.
- Never combining allow-scripts and allow-same-origin in sandbox for untrusted content (it lets the frame remove its own sandbox).
- Sizing with width="100%" attribute (percent is not valid; use CSS).
- Embedding sites that forbid framing and getting a blank box.

See also

<embed>, <object>, <frame>, <fencedframe>, <portal>

Quick card: <image>

Image (non-standard alias, obsolete)

<image> is an ancient, non-standard synonym for <img>. For compatibility, the HTML parser silently converts a start tag named image into img. Never write it; always use <img>.

At a glance

Status	OBSOLETE
Versions	Never standard
Category	Obsolete embedded content
Closing tag	None (void element)
Display	inline
Own attributes	src
Related	<img>

Minimal example

```
<img src="x.png" alt="Description">
```

Most common mistake

Any use.

<image> — Image (non-standard alias, obsolete)

Category: Obsolete embedded content | Status: OBSOLETE | Versions: Never standard

Description

<image> is an ancient, non-standard synonym for <img>. For compatibility, the HTML parser silently converts a start tag named image into img. Never write it; always use <img>.

Syntax

```
<image src="x.png">  <!-- becomes <img src="x.png"> -->
```

Technical summary

Property	Value
Void element	Yes (no closing tag)
Default display	inline
Content categories	Historical
Permitted content	None
Permitted parents	Phrasing content
Tag omission	No end tag
DOM interface	HTMLImageElement (after parsing)

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
src, alt, etc.	as <img>	Whatever the parser transfers to the <img> it creates.	-

<image>: attribute by attribute

Each attribute of <image> explained in detail, with a minimal example you can copy.

src, alt, etc.

Values: as <img> | Since: -

Whatever the parser transfers to the <img> it creates.

Write src="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<image src="as <img>">
```

<image>: worked examples

Use <img>

```
<img src="x.png" alt="Description">
```

Common mistakes

- Any use.

See also

Quick card: <img>

Image

The <img> element embeds an image in the document. It is a void element; the image file is identified by the src attribute and is loaded separately. Supported formats include JPEG, PNG, GIF, WebP, AVIF, SVG, APNG, BMP and ICO. The alt attribute holds a text alternative that is displayed if the image cannot load and is read aloud by screen readers; it is required for accessibility.

At a glance

Status	CURRENT
Versions	Mosaic (1993), HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Image and multimedia
Closing tag	None (void element)
Display	inline
Own attributes	src, alt, width, height, srcset, sizes, loading, decoding, fetchpriority, crossorigin, referrerpolicy, usemap, ismap, elementtiming, attributionsrc, align, border, hspace, longdesc, name, lowsrc
Related	<picture>, <source>, <figure>, <map>, <area>, <canvas>, <svg>

Minimal example

```
<img src="cat.jpg" alt="A grey cat sleeping on a red cushion"
width="400" height="300">
```

Most common mistake

Omitting alt or writing alt="image".

<img> — Image

Category: Image and multimedia | Status: CURRENT | Versions: Mosaic (1993), HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <img> element embeds an image in the document. It is a void element; the image file is identified by the src attribute and is loaded separately. Supported formats include JPEG, PNG, GIF, WebP, AVIF, SVG, APNG, BMP and ICO. The alt attribute holds a text alternative that is displayed if the image cannot load and is read aloud by screen readers; it is required for accessibility.

HTML5 added responsive-image attributes: srcset lists several versions of the image at different sizes or pixel densities and sizes tells the browser how wide the image will be displayed, so the browser can download the smallest adequate file. The loading="lazy" attribute defers loading until the image is near the viewport, and decoding="async" lets the browser decode it off the main thread.

Always give width and height attributes (the intrinsic size in pixels). The browser uses them to reserve space before the image loads, which prevents the page from jumping (layout shift). With CSS max-width: 100%; height: auto the image still scales down on small screens.

The <img> element was invented by Marc Andreessen for the Mosaic browser in 1993 and was the first element to bring graphics to the web. In HTML 3.2 and 4.01 it carried presentational attributes (align, border, hspace, vspace) that are obsolete today.

Syntax

```
<img src="URL" alt="description" width="W" height="H">
```

Technical summary

Property	Value
Void element	Yes (no closing tag)
Default display	inline
Content categories	Flow content, phrasing content, embedded content, palpable content; form-associated and interactive if it has usemap
Permitted content	None (void element)
Permitted parents	Any element that accepts embedded content
Tag omission	No end tag
DOM interface	HTMLImageElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
src	URL	The image URL. Required (unless srcset is used with a browser that supports it).	HTML 2.0
alt	text	Text alternative. Describe the content or function of the image. Use alt="" (empty) for purely decorative images so that screen readers skip them. Omitting alt entirely is an error.	HTML 2.0
width	pixels	Intrinsic width. Helps the browser reserve space.	HTML 3.2

Attribute	Values	Description	Since
height	pixels	Intrinsic height.	HTML 3.2
srcset	comma-separated candidates	Alternative image files: 'small.jpg 480w, large.jpg 1200w' (width descriptors) or 'img.jpg 1x, img@2x.jpg 2x' (density descriptors).	HTML5
sizes	media conditions and lengths	How wide the image will be rendered, for example '(max-width: 600px) 100vw, 50vw'. Required when srcset uses width descriptors.	HTML5
loading	eager | lazy	lazy delays loading until the image is near the viewport. Do not lazy-load images visible at page load.	Living Standard
decoding	sync | async | auto	Hint about how to decode the image.	Living Standard
fetchpriority	high | low | auto	Hint about the download priority; set high on the hero image.	Living Standard
crossorigin	anonymous | use-credentials	Load with CORS so the image can be used in canvas without tainting it.	HTML5
referrerpolicy	referrer policy keyword	Which referrer to send.	HTML5
usemap	#map-name	Links the image to a <map> element to make it an image map.	HTML 3.2
ismap	boolean	Makes the image a server-side image map; the click coordinates are appended to the link URL. Only valid inside <a href>.	HTML 2.0
elementtiming	text	Marks the image for the Element Timing performance API.	Living Standard

Attribute	Values	Description	Since
attributionsrc	empty or URL	Experimental attribution reporting.	Experimental
align	top | middle | bottom | left | right	Obsolete. Use CSS float or vertical-align.	HTML 2.0
border	pixels	Obsolete. Border width. Use CSS border.	HTML 3.2
hspace / vspace	pixels	Obsolete. Horizontal and vertical margins. Use CSS margin.	HTML 3.2
longdesc	URL	Obsolete. Link to a long description. Use a normal link or aria-describedby.	HTML 4.01
name	text	Obsolete. Use id.	HTML 4.01
lowsrc	URL	Obsolete, non-standard. Low-quality placeholder loaded first.	Netscape

<img>: attribute by attribute

Each attribute of <img> explained in detail, with a minimal example you can copy.

src

Values: URL | Since: HTML 2.0

The image URL. Required (unless srcset is used with a browser that supports it).

Write src="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<img src="https://example.com/page.html">
```

alt

Values: text | Since: HTML 2.0

Text alternative. Describe the content or function of the image. Use alt="" (empty) for purely decorative images so that screen readers skip them. Omitting alt entirely is an error.

Write alt="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<img alt="value">
```

width

Values: pixels | Since: HTML 3.2

Intrinsic width. Helps the browser reserve space.

Write width="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<img width="3">
```

height

Values: pixels | Since: HTML 3.2

Intrinsic height.

Write height="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<img height="3">
```

srcset

Values: comma-separated candidates | Since: HTML5

Alternative image files: 'small.jpg 480w, large.jpg 1200w' (width descriptors) or 'img.jpg 1x, img@2x.jpg 2x' (density descriptors).

Write srcset="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<img srcset="value">
```

sizes

Values: media conditions and lengths | Since: HTML5

How wide the image will be rendered, for example '(max-width: 600px) 100vw, 50vw'. Required when srcset uses width descriptors.

Write sizes="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<img sizes="value">
```

loading

Values: eager | lazy | Since: Living Standard

lazy delays loading until the image is near the viewport. Do not lazy-load images visible at page load.

Write loading="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<img loading="eager">
```

decoding

Values: sync | async | auto | Since: Living Standard

Hint about how to decode the image.

Write decoding="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<img decoding="sync">
```

fetchpriority

Values: high | low | auto | Since: Living Standard

Hint about the download priority; set high on the hero image.

Write fetchpriority="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<img fetchpriority="high">
```

crossorigin

Values: anonymous | use-credentials | Since: HTML5

Load with CORS so the image can be used in canvas without tainting it.

Write crossorigin="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<img crossorigin="anonymous">
```

referrerpolicy

Values: referrer policy keyword | Since: HTML5

Which referrer to send.

Write referrerpolicy="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<img referrerpolicy="referrer policy keyword">
```

usemap

Values: #map-name | Since: HTML 3.2

Links the image to a <map> element to make it an image map.

Write usemap="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<img usemap="#map-name">
```

ismap

Values: boolean | Since: HTML 2.0

Makes the image a server-side image map; the click coordinates are appended to the link URL. Only valid inside <a href>.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<img ismap>
```

elementtiming

Values: text | Since: Living Standard

Marks the image for the Element Timing performance API.

Write elementtiming="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<img elementtiming="value">
```

attributionsrc

Values: empty or URL | Since: Experimental

Experimental attribution reporting.

Write attributionsrc="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<img attributionsrc="empty">
```

align

Values: top | middle | bottom | left | right | Since: HTML 2.0

Obsolete. Use CSS float or vertical-align.

Write align="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<img align="top">
```

border

Values: pixels | Since: HTML 3.2

Obsolete. Border width. Use CSS border.

Write border="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<img border="3">
```

hspace / vspace

Values: pixels | Since: HTML 3.2

Obsolete. Horizontal and vertical margins. Use CSS margin.

Write hspace="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<img hspace="3">
```

longdesc

Values: URL | Since: HTML 4.01

Obsolete. Link to a long description. Use a normal link or aria-describedby.

Write longdesc="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<img longdesc="https://example.com/page.html">
```

name

Values: text | Since: HTML 4.01

Obsolete. Use id.

Write name="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<img name="value">
```

lowsrc

Values: URL | Since: Netscape

Obsolete, non-standard. Low-quality placeholder loaded first.

Write lowsrc="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<img lowsrc="https://example.com/page.html">
```

<img>: worked examples

Basic image with good alt text

```
<img src="cat.jpg" alt="A grey cat sleeping on a red cushion"
width="400" height="300">
```

Decorative image

```
<img src="divider.png" alt="" width="600" height="8">
```

Empty alt tells screen readers to ignore it.

Responsive images with srcset and sizes

```
<img src="photo-800.jpg"
  srcset="photo-400.jpg 400w, photo-800.jpg 800w, photo-1600.jpg
1600w"
  sizes="(max-width: 600px) 100vw, 600px"
  alt="Cairo skyline at night" width="800" height="533">
```

On a phone the image fills the screen, so the browser picks the 400w or 800w file; on a desktop it is shown at 600px wide.

High-DPI (retina) logo

```
<img src="logo.png" srcset="logo.png 1x, logo@2x.png 2x" alt="Book
Store" width="120" height="40">
```

Lazy loading images below the fold

```
<img src="gallery-12.jpg" alt="..." loading="lazy" decoding="async"
width="300" height="200">
```

Image as a link

```
<a href="index.html"><img src="logo.svg" alt="Book Store home"
width="120" height="40"></a>
```

The alt describes where the link goes.

Fluid image CSS

```
<style>
  img { max-width: 100%; height: auto; }
</style>
```

Keeps images inside their container on small screens while width/height attributes still prevent layout shift.

HTML 3.2 style and its replacement

```
<!-- Old -->
<img src="a.jpg" align="left" hspace="10" border="0">

<!-- New -->
<img src="a.jpg" alt="..." style="float: left; margin: 0 10px; border:
 0">
```

Default browser CSS

```
img { display: inline; }
```

Accessibility

- alt is required. Write what the image conveys, not 'image of'. Keep it under about 150 characters; for complex images give a longer description in the text.
- Text inside images cannot be read by screen readers or resized; use real text.
- Animated GIFs that flash can trigger seizures; avoid or provide a pause control.

Common mistakes

- Omitting alt or writing alt="image".
- Omitting width and height, causing layout shift.
- Using a huge original file where a resized one would do.
- Lazy-loading the hero image (it delays the largest contentful paint).
- Using the align attribute.

See also

<picture>, <source>, <figure>, <map>, <area>, <canvas>, <svg>

Quick card: <input>

Input control

The <input> element creates an interactive control for accepting data from the user. It is the most versatile element in HTML: the type attribute selects one of more than twenty different controls, from a plain text box to a colour picker, a file chooser, a range slider or a hidden field. It is a void element.

At a glance

Status	CURRENT
Versions	HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Forms
Closing tag	None (void element)
Display	inline-block
Own attributes	type, name, value, id, disabled, readonly, required, placeholder, autocomplete, autofocus, checked, maxlength, minlength, size, min, max, step, pattern, list, multiple, accept, capture, src, alt, width, form, formaction, formenctype, formmethod, formnovalidate, formtarget, dirname, inputmode, popovertarget, alpha, colorspace, align, usemap, incremental
Related	<form>, <label>, <button>, <select>, <textarea>, <datalist>, <output>, <fieldset>

Minimal example

```
<label for="user">Username</label>
<input id="user" name="user" type="text" placeholder="e.g. ahmed99"
required minlength="3" maxlength="20" autocomplete="username">
```

Most common mistake

Missing name (nothing submitted).

<input> — Input control

Category: Forms | Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <input> element creates an interactive control for accepting data from the user. It is the most versatile element in HTML: the type attribute selects one of more than twenty different controls, from a plain text box to a colour picker, a file chooser, a range slider or a hidden field. It is a void element.

HTML 2.0 defined text, password, checkbox, radio, submit, reset, hidden and image; HTML 3.2 and 4.01 added file and button; HTML5 added email, url, tel, search, number, range, color, date, month, week, time and datetime-local. Browsers fall back to type="text" for any type they do not recognise, so new types are safe to use.

Each type accepts a different subset of attributes; the complete table below lists every attribute and Part 6 of this book describes every type in its own entry with examples.

Syntax

```
<input type="text" name="field" id="field">
```

Technical summary

Property	Value
Void element	Yes (no closing tag)
Default display	inline-block

Property	Value
Content categories	Flow content, phrasing content, listed, submittable, resettable, form-associated, palpable; interactive and labelable unless type=hidden
Permitted content	None (void element)
Permitted parents	Any element that accepts phrasing content
Tag omission	No end tag
DOM interface	HTMLInputElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
type	see Part 6	The kind of control. Default text. Values: button, checkbox, color, date, datetime-local, email, file, hidden, image, month, number, password, radio, range, reset, search, submit, tel, text, time, url, week.	HTML 2.0 / HTML5
name	text	The name under which the value is submitted. Without it the control is not submitted. Radio buttons with the same name form a group.	HTML 2.0
value	text	The initial value (text types), the value submitted when checked (checkbox, radio), or the button label (submit, reset, button).	HTML 2.0
id	identifier	Links the control to a <label for="id">.	HTML 4.01

Attribute	Values	Description	Since
disabled	boolean	Cannot be used or focused and is not submitted.	HTML 4.01
readonly	boolean	Cannot be edited but is focusable and submitted. Text-like types only.	HTML 4.01
required	boolean	Must have a value before the form can be submitted.	HTML5
placeholder	text	Hint shown inside an empty text-like control. Not a substitute for a label.	HTML5
autocomplete	on | off | token list	Autofill hint: name, email, tel, street-address, postal-code, cc-number, new-password, current-password, one-time-code and more (see Part 9).	HTML5
autofocus	boolean	Focus this control on page load. Only one per page.	HTML5
checked	boolean	Initially selected (checkbox, radio).	HTML 2.0
maxlength	integer	Maximum number of characters (text-like types).	HTML 2.0
minlength	integer	Minimum number of characters.	HTML5
size	integer	Visible width in characters (text-like types). Prefer CSS width.	HTML 2.0
min	number or date	Minimum value (number, range, date/time types).	HTML5
max	number or date	Maximum value.	HTML5
step	number or any	Granularity of allowed values; 'any' allows any value.	HTML5

Attribute	Values	Description	Since
pattern	regular expression	A JavaScript regular expression the value must match (text, search, url, tel, email, password). Describe the format in title.	HTML5
list	datalist id	Links to a <datalist> of suggestions.	HTML5
multiple	boolean	Allow several values (email: comma-separated; file: several files).	HTML5
accept	MIME types / extensions	Allowed file types for type=file, for example image/*, .pdf, audio/*.	HTML 4.01
capture	user | environment	For type=file on phones: use the front (user) or back (environment) camera/microphone directly.	Media Capture spec
src	URL	The image for type=image.	HTML 2.0
alt	text	Alternative text for type=image.	HTML 2.0
width / height	pixels	Size of the image for type=image.	HTML5
form	form id	Associate with a form anywhere in the document.	HTML5
formaction	URL	Override the form action (submit, image).	HTML5
formenctype	encoding type	Override the form enctype (submit, image).	HTML5
formmethod	get | post | dialog	Override the form method (submit, image).	HTML5
formnovalidate	boolean	Skip validation when submitting with this button.	HTML5
formtarget	browsing context	Override the form target (submit, image).	HTML5

Attribute	Values	Description	Since
dirname	text	Submit the text direction of the value under this name.	HTML5
inputmode	none | text | decimal | numeric | tel | search | email | url	Which virtual keyboard to show on touch devices (global attribute).	HTML5
popovertarget / popovertargetaction	id / show | hide | toggle	Control a popover from a button-type input.	Living Standard
alpha	boolean	Experimental: allow transparency in type=color.	Experimental
colorspace	limited-srgb | display-p3	Experimental: colour space for type=color.	Experimental
align	left | right | top | middle | bottom	Obsolete. Use CSS.	HTML 3.2
usemap	#map	Obsolete on input. Use <img usemap>.	HTML 4.01
incremental, results, webkitdirectory, orient, mozactionhint	various	Non-standard browser-specific attributes.	Non-standard

<input>: attribute by attribute

Each attribute of <input> explained in detail, with a minimal example you can copy.

type

Values: see Part 6 | Since: HTML 2.0 / HTML5

The kind of control. Default text. Values: button, checkbox, color, date, datetime-local, email, file, hidden, image, month, number, password, radio, range, reset, search, submit, tel, text, time, url, week.

Write type="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input type="see Part 6">
```

name

Values: text | Since: HTML 2.0

The name under which the value is submitted. Without it the control is not submitted. Radio buttons with the same name form a group.

Write name="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input name="value">
```

value

Values: text | Since: HTML 2.0

The initial value (text types), the value submitted when checked (checkbox, radio), or the button label (submit, reset, button).

Write value="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input value="value">
```

id

Values: identifier | Since: HTML 4.01

Links the control to a <label for="id">.

Write id="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input id="identifier">
```

disabled

Values: boolean | Since: HTML 4.01

Cannot be used or focused and is not submitted.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<input disabled>
```

readonly

Values: boolean | Since: HTML 4.01

Cannot be edited but is focusable and submitted. Text-like types only.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<input readonly>
```

required

Values: boolean | Since: HTML5

Must have a value before the form can be submitted.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<input required>
```

placeholder

Values: text | Since: HTML5

Hint shown inside an empty text-like control. Not a substitute for a label.

Write placeholder="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input placeholder="value">
```

autocomplete

Values: on | off | token list | Since: HTML5

Autofill hint: name, email, tel, street-address, postal-code, cc-number, new-password, current-password, one-time-code and more (see Part 9).

Write autocomplete="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input autocomplete="on">
```

autofocus

Values: boolean | Since: HTML5

Focus this control on page load. Only one per page.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<input autofocus>
```

checked

Values: boolean | Since: HTML 2.0

Initially selected (checkbox, radio).

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<input checked>
```

maxlength

Values: integer | Since: HTML 2.0

Maximum number of characters (text-like types).

Write maxlength="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input maxlength="3">
```

minlength

Values: integer | Since: HTML5

Minimum number of characters.

Write minlength="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input minlength="3">
```

size

Values: integer | Since: HTML 2.0

Visible width in characters (text-like types). Prefer CSS width.

Write size="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input size="3">
```

min

Values: number or date | Since: HTML5

Minimum value (number, range, date/time types).

Write min="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input min="3">
```

max

Values: number or date | Since: HTML5

Maximum value.

Write max="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input max="3">
```

step

Values: number or any | Since: HTML5

Granularity of allowed values; 'any' allows any value.

Write step="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input step="3">
```

pattern

Values: regular expression | Since: HTML5

A JavaScript regular expression the value must match (text, search, url, tel, email, password). Describe the format in title.

Write pattern="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input pattern="regular expression">
```

list

Values: datalist id | Since: HTML5

Links to a <datalist> of suggestions.

Write list="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input list="datalist id">
```

multiple

Values: boolean | Since: HTML5

Allow several values (email: comma-separated; file: several files).

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<input multiple>
```

accept

Values: MIME types / extensions | Since: HTML 4.01

Allowed file types for type=file, for example image/*, .pdf, audio/*.

Write accept="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input accept="text/plain">
```

capture

Values: user | environment | Since: Media Capture spec

For type=file on phones: use the front (user) or back (environment) camera/microphone directly.

Write capture="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input capture="user">
```

src

Values: URL | Since: HTML 2.0

The image for type=image.

Write src="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input src="https://example.com/page.html">
```

alt

Values: text | Since: HTML 2.0

Alternative text for type=image.

Write alt="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input alt="value">
```

width / height

Values: pixels | Since: HTML5

Size of the image for type=image.

Write width="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input width="3">
```

form

Values: form id | Since: HTML5

Associate with a form anywhere in the document.

Write form="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input form="form id">
```

formaction

Values: URL | Since: HTML5

Override the form action (submit, image).

Write formaction="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input formaction="https://example.com/page.html">
```

formenctype

Values: encoding type | Since: HTML5

Override the form enctype (submit, image).

Write formenctype="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input formenctype="encoding type">
```

formmethod

Values: get | post | dialog | Since: HTML5

Override the form method (submit, image).

Write formmethod="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input formmethod="get">
```

formnovalidate

Values: boolean | Since: HTML5

Skip validation when submitting with this button.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<input formnovalidate>
```

formtarget

Values: browsing context | Since: HTML5

Override the form target (submit, image).

Write formtarget="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input formtarget="browsing context">
```

dirname

Values: text | Since: HTML5

Submit the text direction of the value under this name.

Write dirname="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input dirname="value">
```

inputmode

Values: none | text | decimal | numeric | tel | search | email | url | Since: HTML5

Which virtual keyboard to show on touch devices (global attribute).

Write inputmode="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input inputmode="none">
```

popovertarget / popovertargetaction

Values: id / show | hide | toggle | Since: Living Standard

Control a popover from a button-type input.

Write popovertarget="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input popovertarget="my-id">
```

alpha

Values: boolean | Since: Experimental

Experimental: allow transparency in type=color.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<input alpha>
```

colorspace

Values: limited-srgb | display-p3 | Since: Experimental

Experimental: colour space for type=color.

Write colorspace="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input colorspace="limited-srgb">
```

align

Values: left | right | top | middle | bottom | Since: HTML 3.2

Obsolete. Use CSS.

Write align="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input align="left">
```

usemap

Values: #map | Since: HTML 4.01

Obsolete on input. Use <img usemap>.

Write usemap="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input usemap="#map">
```

incremental, results, webkitdirectory, orient, mozactionhint

Values: various | Since: Non-standard

Non-standard browser-specific attributes.

Write incremental="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<input incremental="various">
```

<input>: worked examples

Text with label, placeholder and required

```
<label for="user">Username</label>
<input id="user" name="user" type="text" placeholder="e.g. ahmed99"
required minlength="3" maxlength="20" autocomplete="username">
```

Email and password

```
<label for="e">Email</label>
<input id="e" name="email" type="email" required autocomplete="email">
<label for="p">Password</label>
<input id="p" name="password" type="password" required minlength="8"
autocomplete="current-password">
```

Checkboxes and radio buttons

```
<label><input type="checkbox" name="terms" value="yes" required> I
agree to the terms</label>

<fieldset>
  <legend>Size</legend>
  <label><input type="radio" name="size" value="s"> Small</label>
  <label><input type="radio" name="size" value="m" checked> Medium</
label>
  <label><input type="radio" name="size" value="l"> Large</label>
</fieldset>
```

Number, range and date

```
<label>Quantity <input type="number" name="qty" min="1" max="10"
step="1" value="1"></label>
<label>Volume <input type="range" name="vol" min="0" max="100"
value="50"></label>
<label>Delivery date <input type="date" name="date" min="2026-09-
12"></label>
```

Pattern validation with an explanation

```
<label>Postal code <input name="zip" pattern="[0-9]{5}" title="Five
digits, for example 12511" inputmode="numeric"></label>
```

Hidden field

```
<input type="hidden" name="product_id" value="42">
```

Sent with the form but not shown.

File upload restricted to images

```
<input type="file" name="photo" accept="image/png, image/jpeg"
multiple>
```

Styling validity

```
<style>
  input:invalid { border-color: #b90000; }
  input:valid { border-color: #0f8a4c; }
  input:focus { outline: 2px solid #1b6fd8; }
</style>
```

Default browser CSS

```
input { display: inline-block; }
```

Accessibility

- Every input needs a label (visible <label> or aria-label).
- Placeholder disappears when typing; never use it as the only label.
- Use the correct type so mobile keyboards and screen readers behave correctly.
- Group radio buttons and checkboxes in a fieldset with a legend.
- Do not disable the submit button until the form is valid; let users submit and see the errors.

Common mistakes

- Missing name (nothing submitted).
- Missing label.
- Using type="number" for values that are not quantities (phone numbers, postal codes); use type="tel" or text with inputmode.
- Writing a closing </input> tag.
- Relying only on client-side validation; always validate on the server too.

See also

<form>, <label>, <button>, <select>, <textarea>, <datalist>, <output>, <fieldset>

Quick card: <ins>

Inserted text

The <ins> element marks text that has been added to a document, to show changes between versions. Browsers underline it by default. It is the counterpart of <del>. Like <del> it accepts optional cite and datetime attributes that record why and when the change was made.

At a glance

Status	CURRENT
Versions	HTML 4.01, HTML5
Category	Demarcating edits
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	cite, datetime
Related	<del>, <u>

Minimal example

```
<p>Our office is open <del>9 to 5</del> <ins datetime="2026-09-01">8
to 4</ins>.</p>
```

Most common mistake

Using <u> to show insertions.

<ins> — Inserted text

Category: Demarcating edits | Status: CURRENT | Versions: HTML 4.01, HTML5

Description

The <ins> element marks text that has been added to a document, to show changes between versions. Browsers underline it by default. It is the counterpart of <del>. Like <del> it accepts optional cite and datetime attributes that record why and when the change was made.

Syntax

```
<ins datetime="YYYY-MM-DD">inserted text</ins>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, palpable content
Permitted content	Transparent
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLModElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
cite	URL	A URL explaining the change.	HTML 4.01
datetime	date or date-time	When the change was made.	HTML 4.01

<ins>: attribute by attribute

Each attribute of <ins> explained in detail, with a minimal example you can copy.

cite

Values: URL | Since: HTML 4.01

A URL explaining the change.

Write cite="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<ins cite="https://example.com/page.html">...</ins>
```

datetime

Values: date or date-time | Since: HTML 4.01

When the change was made.

Write datetime="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<ins datetime="date">...</ins>
```

<ins>: worked examples

Tracking a change

```
<p>Our office is open <del>9 to 5</del> <ins datetime="2026-09-01">8
to 4</ins>.</p>
```

Styling insertions

```
<style>
  ins { background: #dfffe0; text-decoration: none; }
  del { background: #ffe0e0; }
</style>
```

Default browser CSS

```
ins { text-decoration: underline; }
```

Accessibility

- Not announced by most screen readers by default; add hidden text if the change must be conveyed.

Common mistakes

- Using <u> to show insertions.
- Wrapping several block elements in one inline <ins>.

See also

<del>, <u>

Quick card: <isindex>

Search index prompt (obsolete)

The <isindex> element, one of the original 1991 elements, told the browser that the document was a searchable index and made it display a single-line text field with a prompt. Submitting the field reloaded the page with ?keywords in the URL. It was made redundant by forms in HTML 2.0, deprecated in HTML 4.01 and removed in HTML5. Use a <form> with an <input type="search">.

At a glance

Status	OBSOLETE
Versions	HTML 1, HTML 2.0, HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5
Category	Obsolete forms
Closing tag	None (void element)
Display	block
Own attributes	prompt, action
Related	<form>, <input>

Minimal example

```
<form action="/search" method="get">
  <label>Search: <input type="search" name="q"></label>
</form>
```

Most common mistake

Any use.

<isindex> — Search index prompt (obsolete)

Category: Obsolete forms | Status: OBSOLETE | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

Description

The <isindex> element, one of the original 1991 elements, told the browser that the document was a searchable index and made it display a single-line text field with a prompt. Submitting the field reloaded the page with ?keywords in the URL. It was made redundant by forms in HTML 2.0, deprecated in HTML 4.01 and removed in HTML5. Use a <form> with an <input type="search">.

Syntax

```
<isindex prompt="Search: ">
```

Technical summary

Property	Value
Void element	Yes (no closing tag)
Default display	block
Content categories	Historical
Permitted content	None
Permitted parents	<head> or <body>
Tag omission	No end tag
DOM interface	HTMLUnknownElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
prompt	text	The label shown before the field.	HTML 2.0
action	URL	Where to send the query (non-standard).	Netscape

<isindex>: attribute by attribute

Each attribute of <isindex> explained in detail, with a minimal example you can copy.

prompt

Values: text | Since: HTML 2.0

The label shown before the field.

Write prompt="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<isindex prompt="value">
```

action

Values: URL | Since: Netscape

Where to send the query (non-standard).

Write action="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<isindex action="https://example.com/page.html">
```

<isindex>: worked examples

Replacement

```
<form action="/search" method="get">
  <label>Search: <input type="search" name="q"></label>
</form>
```

Common mistakes

- Any use.

See also

<form>, <input>

Quick card: <kbd>

Keyboard input

The <kbd> element marks text that represents user input from a keyboard, voice command, or other input device. Browsers render it in a monospace font. Nesting <kbd> elements inside a <kbd> represents individual keys in a key combination; wrapping <kbd> in <samp> represents input echoed by the system.

At a glance

Status	CURRENT
Versions	HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Text-level semantics
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	None (global attributes only)
Related	<code>, <samp>, <var>

Minimal example

```
<p>Press <kbd><kbd>Ctrl</kbd> + <kbd>S</kbd></kbd> to save.</p>
```

Most common mistake

Using <code> for keys.

<kbd> — Keyboard input

Category: Text-level semantics | Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <kbd> element marks text that represents user input from a keyboard, voice command, or other input device. Browsers render it in a monospace font. Nesting <kbd> elements inside a <kbd> represents individual keys in a key combination; wrapping <kbd> in <samp> represents input echoed by the system.

Syntax

```
<kbd>Ctrl</kbd> + <kbd>S</kbd>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, palpable content
Permitted content	Phrasing content
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<kbd>: worked examples

Keyboard shortcut

```
<p>Press <kbd><kbd>Ctrl</kbd> + <kbd>S</kbd></kbd> to save.</p>
```

Key-cap styling

```
<style>
  kbd { border: 1px solid #aaa; border-radius: 4px; padding: 0 4px;
background: #f5f5f5; font-size: 0.9em; box-shadow: 0 1px 0 #999; }
</style>
```

Menu selection

```
<p>Choose <kbd>File</kbd> then <kbd>Save As...</kbd>.</p>
```

Default browser CSS

```
kbd { font-family: monospace; }
```

Common mistakes

- Using <code> for keys.
- Using <kbd> for program output (use <samp>).

See also

<code>, <samp>, <var>

Quick card: <keygen>

Key-pair generator (obsolete)

The <keygen> element generated a public/private key pair when a form was submitted, for client certificate enrolment. It came from Netscape, was added to HTML5 and then removed from the standard in 2017 and from all browsers. There is no direct replacement; use the Web Crypto API.

At a glance

Status	OBSOLETE
Versions	Netscape, briefly in HTML5; removed
Category	Obsolete forms
Closing tag	None (void element)
Display	inline-block
Own attributes	challenge, keytype, name, autofocus
Related	<input>, <form>

Minimal example

```
<!-- No modern replacement in HTML; see crypto.subtle.generateKey() --
>
```

Most common mistake

Any use.

<keygen> — Key-pair generator (obsolete)

Category: Obsolete forms | Status: OBSOLETE | Versions: Netscape, briefly in HTML5; removed

Description

The <keygen> element generated a public/private key pair when a form was submitted, for client certificate enrolment. It came from Netscape, was added to HTML5 and then removed from the standard in 2017 and from all browsers. There is no direct replacement; use the Web Crypto API.

Syntax

```
<keygen name="key" challenge="...">
```

Technical summary

Property	Value
Void element	Yes (no closing tag)
Default display	inline-block
Content categories	Historical
Permitted content	None
Permitted parents	Phrasing content
Tag omission	No end tag
DOM interface	HTMLUnknownElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
challenge	text	Challenge string.	HTML5
keytype	rsa | dsa | ec	Key algorithm.	HTML5
name	text	Form field name.	HTML5
autofocus, disabled, form	-	As on other controls.	HTML5

<keygen>: attribute by attribute

Each attribute of <keygen> explained in detail, with a minimal example you can copy.

challenge

Values: text | Since: HTML5

Challenge string.

Write challenge="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<keygen challenge="value">
```

keytype

Values: rsa | dsa | ec | Since: HTML5

Key algorithm.

Write keytype="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<keygen keytype="rsa">
```

name

Values: text | Since: HTML5

Form field name.

Write name="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<keygen name="value">
```

autofocus, disabled, form

Values: - | Since: HTML5

As on other controls.

Write autofocus="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<keygen autofocus="-">
```

<keygen>: worked examples

Do not use

```
<!-- No modern replacement in HTML; see crypto.subtle.generateKey() --
>
```

Common mistakes

- Any use.

See also

<input>, <form>

Quick card: <label>

Form control label

The <label> element gives a caption to a form control. Associating a label with a control has two big benefits: clicking the label focuses or toggles the control (a much larger click target for checkboxes and radio buttons), and screen readers announce the label when the control gets focus.

At a glance

Status	CURRENT
Versions	HTML 4.01, HTML5
Category	Forms
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	for, form
Related	<input>, <select>, <textarea>, <button>, <fieldset>, <legend>

Minimal example

```
<label for="city">City</label>
<input id="city" name="city">
```

Most common mistake

for pointing to a name instead of an id.

<label> — Form control label

Category: Forms | Status: CURRENT | Versions: HTML 4.01, HTML5

Description

The <label> element gives a caption to a form control. Associating a label with a control has two big benefits: clicking the label focuses or toggles the control (a much larger click target for checkboxes and radio buttons), and screen readers announce the label when the control gets focus.

There are two ways to associate them. Explicit: give the control an id and set the label's for attribute to that id. Implicit: nest the control inside the label. You may combine both. A label may be associated with only one control, but a control may have several labels.

Labelable elements are <button>, <input> (except hidden), <meter>, <output>, <progress>, <select> and <textarea>.

Syntax

```
<label for="id">Text</label> <input id="id">
<!-- or -->
<label>Text <input></label>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, interactive content, form-associated, palpable content
Permitted content	Phrasing content, but no other <label> and at most one labelable descendant

Property	Value
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLLabelElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
for	id of a labelable element	The control this label describes.	HTML 4.01
form	form id	Obsolete in the Living Standard; was meant to associate the label with a form.	HTML5 (removed)

<label>: attribute by attribute

Each attribute of <label> explained in detail, with a minimal example you can copy.

for

Values: id of a labelable element | Since: HTML 4.01

The control this label describes.

Write for="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<label for="my-id">...</label>
```

form

Values: form id | Since: HTML5 (removed)

Obsolete in the Living Standard; was meant to associate the label with a form.

Write form="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<label form="form id">...</label>
```

<label>: worked examples

Explicit association

```
<label for="city">City</label>
<input id="city" name="city">
```

Implicit association (wrapping)

```
<label>
  <input type="checkbox" name="news"> Send me the newsletter
</label>
```

Clicking anywhere on the text toggles the box.

Labels stacked above fields

```
<style>
  label { display: block; margin-bottom: 4px; font-weight: 600; }
  input, select, textarea { display: block; width: 100%; margin-
bottom: 16px; }
</style>
```

Required-field indicator

```
<label for="n">Name <span aria-hidden="true">*</span></label>
<input id="n" name="n" required aria-required="true">
```

Default browser CSS

```
label { cursor: default; }
```

Accessibility

- A label is the correct way to name a control; aria-label is a fallback when no visible text is possible.
- Do not put headings or interactive elements inside a label.
- Keep the label visible; placeholder text is not a label.

Common mistakes

- for pointing to a name instead of an id.
- Two controls inside one label.
- Using <label> for text that is not a caption for a control.

See also

<input>, <select>, <textarea>, <button>, <fieldset>, <legend>

Quick card: <legend>

Fieldset caption

The <legend> element provides a caption for its parent <fieldset>. It must be the first child of the fieldset. Browsers draw it on top of the fieldset's border. Screen readers announce the legend together with the label of each control inside the group, which is why fieldset/legend is the recommended way to caption groups of radio buttons or checkboxes.

At a glance

Status	CURRENT
Versions	HTML 4.01, HTML5
Category	Forms
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	align
Related	<fieldset>, <label>

Minimal example

```
<fieldset>
  <legend>Contact preference</legend>
  <label><input type="radio" name="c" value="email"> Email</label>
  <label><input type="radio" name="c" value="phone"> Phone</label>
</fieldset>
```

Most common mistake

Legend not first in the fieldset.

<legend> — Fieldset caption

Category: Forms | Status: CURRENT | Versions: HTML 4.01, HTML5

Description

The <legend> element provides a caption for its parent <fieldset>. It must be the first child of the fieldset. Browsers draw it on top of the fieldset's border. Screen readers announce the legend together with the label of each control inside the group, which is why fieldset/legend is the recommended way to caption groups of radio buttons or checkboxes.

Syntax

```
<fieldset>
  <legend>Caption</legend>
  ...
</fieldset>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	None
Permitted content	Phrasing content and optionally heading content
Permitted parents	<fieldset>, as its first child
Tag omission	Neither tag may be omitted
DOM interface	HTMLLegendElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
align	left | center | right | top | bottom	Obsolete. Use CSS.	HTML 4.01

<legend>: attribute by attribute

Each attribute of <legend> explained in detail, with a minimal example you can copy.

align

Values: left | center | right | top | bottom | Since: HTML 4.01

Obsolete. Use CSS.

Write align="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<legend align="left">...</legend>
```

<legend>: worked examples

Captioned group

```
<fieldset>
  <legend>Contact preference</legend>
  <label><input type="radio" name="c" value="email"> Email</label>
  <label><input type="radio" name="c" value="phone"> Phone</label>
</fieldset>
```

Legend containing a heading

```
<fieldset>
  <legend><h2>Billing address</h2></legend>
  ...
</fieldset>
```

Allowed since the Living Standard; keeps the document outline while still captioning the group.

Default browser CSS

```
legend { display: block; padding-inline: 2px; }
```

Accessibility

- Keep legends short; they are repeated by some screen readers for every control in the group.

Common mistakes

- Legend not first in the fieldset.
- Using legend outside a fieldset.

See also

<fieldset>, <label>

Quick card:

List item

The <li> element represents one item in a list. It must be contained in an ordered list (<ol>), an unordered list (<ul>) or a menu (<menu>). In ordered lists the value attribute sets the number of the item, and subsequent items continue counting from it.

At a glance

Status	CURRENT
Versions	HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Text content
Closing tag	Required unless noted under Tag omission
Display	list-item
Own attributes	value, type
Related	, , <menu>, <dl>

Minimal example

```
<ul>
  <li>Milk</li>
  <li>Bread</li>
  <li>Eggs</li>
</ul>
```

Most common mistake

Placing <li> directly in or <body>.

 — List item

Category: Text content | Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <li> element represents one item in a list. It must be contained in an ordered list (<ol>), an unordered list (<ul>) or a menu (<menu>). In ordered lists the value attribute sets the number of the item, and subsequent items continue counting from it.

A list item may contain any flow content: paragraphs, images, nested lists, even tables. To nest a list, place the inner <ul> or <ol> inside the <li>, not between two <li> elements.

Syntax

```
<ul>
  <li>Item</li>
</ul>
```

Technical summary

Property	Value
Void element	No
Default display	list-item
Content categories	None
Permitted content	Flow content
Permitted parents	, , <menu>
Tag omission	End tag may be omitted if followed by another or if there is no more content in the parent

Property	Value
DOM interface	HTMLLIElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
value	integer	In : the ordinal number of this item. Following items count from it.	HTML 3.2
type	1 | a | A | i | I | disc | circle | square	Obsolete. Bullet or numbering style for this item. Use CSS list-style-type.	HTML 3.2

: attribute by attribute

Each attribute of <li> explained in detail, with a minimal example you can copy.

value

Values: integer | Since: HTML 3.2

In <ol>: the ordinal number of this item. Following items count from it.

Write value="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<li value="3">...</li>
```

type

Values: 1 | a | A | i | I | disc | circle | square | Since: HTML 3.2

Obsolete. Bullet or numbering style for this item. Use CSS list-style-type.

Write type="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<li type="1">...</li>
```

: worked examples

Unordered list

```
<ul>
  <li>Milk</li>
  <li>Bread</li>
  <li>Eggs</li>
</ul>
```

Displays with bullets.

Ordered list with a custom start value

```
<ol>
  <li value="10">Tenth</li>
  <li>Eleventh</li>
  <li>Twelfth</li>
</ol>
```

Nested list (correct)

```
<ul>
  <li>Fruit
    <ul>
      <li>Apples</li>
      <li>Oranges</li>
    </ul>
  </li>
  <li>Vegetables</li>
</ul>
```

The inner list is inside the first <li>.

Rich list items

```
<ol>
  <li>
    <h3>Step one</h3>
    <p>Open your editor.</p>
    <img src="editor.png" alt="Editor window" width="300"
height="200">
  </li>
</ol>
```

Horizontal menu with CSS

```
<style>
  nav ul { list-style: none; padding: 0; margin: 0; display: flex;
gap: 16px; }
</style>
<nav><ul><li><a href="/">Home</a></li><li><a href="/shop">Shop</a></
li></ul></nav>
```

Default browser CSS

```
li { display: list-item; text-align: match-parent; }
```

Accessibility

- Screen readers announce the number of items in a list and the position of each; this is lost if list-style: none is combined with display: contents in some browsers, or if you fake a list with <br>.

Common mistakes

- Placing <li> directly in or <body>.
- Nesting a list between <li> elements rather than inside one.
- Using <br> instead of separate items.

See also

, <ol>, <menu>, <dl>

Quick card: <link>

External resource link

The <link> element specifies a relationship between the current document and an external resource. By far its most common use is loading a CSS style sheet (rel="stylesheet"), but it is also used for site icons (rel="icon"), web app manifests, preloading and prefetching resources, canonical URLs for search engines, alternate language versions, RSS feeds and more. It is a void element and normally lives in <head>, though body-ok link types such as stylesheet may appear in <body>.

At a glance

Status	CURRENT
Versions	HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Document metadata
Closing tag	None (void element)
Display	none
Own attributes	rel, href, type, media, as, crossorigin, hreflang, sizes, title, integrity, referrerpolicy, fetchpriority, blocking, disabled, imagesrcset, color, charset, rev, target
Related	<style>, <a>, <script>, <meta>, <head>

Minimal example

```
<link rel="stylesheet" href="style.css">
<link rel="stylesheet" href="print.css" media="print">
<link rel="stylesheet" href="dark.css" media="(prefers-color-scheme:
dark)">
```

Most common mistake

Forgetting rel.

<link> — External resource link

Category: Document metadata | Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <link> element specifies a relationship between the current document and an external resource. By far its most common use is loading a CSS style sheet (rel="stylesheet"), but it is also used for site icons (rel="icon"), web app manifests, preloading and prefetching resources, canonical URLs for search engines, alternate language versions, RSS feeds and more. It is a void element and normally lives in <head>, though body-ok link types such as stylesheet may appear in <body>.

The rel attribute is required and determines everything else. The media attribute lets a style sheet apply only to certain devices or screen sizes; the browser still downloads it but with low priority. The full list of link types is in Part 9.

Syntax

```
<link rel="stylesheet" href="style.css">
```

Technical summary

Property	Value
Void element	Yes (no closing tag)
Default display	none
Content categories	Metadata content; flow and phrasing content if itemprop or a body-ok rel is present

Property	Value
Permitted content	None (void element)
Permitted parents	<head>; <body> for body-ok types
Tag omission	No end tag
DOM interface	HTMLLinkElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
rel	space-separated link types	Required. Relationship: stylesheet, icon, apple-touch-icon, manifest, canonical, alternate, preload, prefetch, preconnect, dns-prefetch, modulepreload, prerender, author, license, help, next, prev, search, pingback, privacy-policy, terms-of-service, expect.	HTML 2.0
href	URL	The resource URL.	HTML 2.0
type	MIME type	The type of the resource, for example text/css, image/png, application/rss+xml.	HTML 2.0
media	media query	Apply the style sheet only when the query matches: screen, print, (max-width: 600px), (prefers-color-scheme: dark).	HTML 4.01

Attribute	Values	Description	Since
as	audio | document | embed | fetch | font | image | object | script | style | track | video | worker	With rel=preload or modulepreload: the type of content being loaded, so the browser can prioritise it correctly.	Living Standard
crossorigin	anonymous | use-credentials	CORS mode for the request. Required when preloading fonts.	HTML5
hreflang	language tag	Language of the linked resource (with rel=alternate).	HTML 4.01
sizes	any or WxH list	Icon sizes, for example 16x16 32x32 or any (for SVG).	HTML5
title	text	For style sheets: the name of an alternate style sheet set. For feeds: the feed title.	HTML 2.0
integrity	hash	Subresource Integrity hash; the browser refuses the file if it does not match.	SRI spec
referrerpolicy	referrer policy	Referrer to send when fetching.	HTML5
fetchpriority	high | low | auto	Download priority hint.	Living Standard
blocking	render	Block rendering until the resource is loaded (for stylesheets/preloads/expect).	Living Standard
disabled	boolean	For style sheets: do not apply.	HTML5
imagesrcset / imagesizes	srcset / sizes syntax	With rel=preload as=image: responsive image candidates.	Living Standard

Attribute	Values	Description	Since
color	colour	With rel=mask-icon (Safari pinned tab).	Non-standard
charset	encoding	Obsolete. Character set of the resource.	HTML 4.01
rev	link types	Obsolete. Reverse relationship.	HTML 4.01
target	browsing context	Obsolete on link.	HTML 4.01

<link>: attribute by attribute

Each attribute of <link> explained in detail, with a minimal example you can copy.

rel

Values: space-separated link types | Since: HTML 2.0

Required. Relationship: stylesheet, icon, apple-touch-icon, manifest, canonical, alternate, preload, prefetch, preconnect, dns-prefetch, modulepreload, prerender, author, license, help, next, prev, search, pingback, privacy-policy, terms-of-service, expect.

Write rel="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<link rel="value">
```

href

Values: URL | Since: HTML 2.0

The resource URL.

Write href="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<link href="https://example.com/page.html">
```

type

Values: MIME type | Since: HTML 2.0

The type of the resource, for example text/css, image/png, application/rss+xml.

Write type="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<link type="text/plain">
```

media

Values: media query | Since: HTML 4.01

Apply the style sheet only when the query matches: screen, print, (max-width: 600px), (prefers-color-scheme: dark).

Write media="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<link media="media query">
```

as

Values: audio | document | embed | fetch | font | image | object | script | style | track | video | worker | Since: Living Standard

With rel=preload or modulepreload: the type of content being loaded, so the browser can prioritise it correctly.

Write as="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<link as="audio">
```

crossorigin

Values: anonymous | use-credentials | Since: HTML5

CORS mode for the request. Required when preloading fonts.

Write crossorigin="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<link crossorigin="anonymous">
```

hreflang

Values: language tag | Since: HTML 4.01

Language of the linked resource (with rel=alternate).

Write hreflang="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<link hreflang="en">
```

sizes

Values: any or WxH list | Since: HTML5

Icon sizes, for example 16x16 32x32 or any (for SVG).

Write sizes="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<link sizes="any">
```

title

Values: text | Since: HTML 2.0

For style sheets: the name of an alternate style sheet set. For feeds: the feed title.

Write title="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<link title="value">
```

integrity

Values: hash | Since: SRI spec

Subresource Integrity hash; the browser refuses the file if it does not match.

Write integrity="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<link integrity="hash">
```

referrerpolicy

Values: referrer policy | Since: HTML5

Referrer to send when fetching.

Write referrerpolicy="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<link referrerpolicy="referrer policy">
```

fetchpriority

Values: high | low | auto | Since: Living Standard

Download priority hint.

Write fetchpriority="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<link fetchpriority="high">
```

blocking

Values: render | Since: Living Standard

Block rendering until the resource is loaded (for stylesheets/preloads/expect).

Write blocking="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<link blocking="render">
```

disabled

Values: boolean | Since: HTML5

For style sheets: do not apply.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<link disabled>
```

imagesrcset / imagesizes

Values: srcset / sizes syntax | Since: Living Standard

With rel=preload as=image: responsive image candidates.

Write imagesrcset="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<link imagesrcset="srcset">
```

color

Values: colour | Since: Non-standard

With rel=mask-icon (Safari pinned tab).

Write color="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<link color="#336699">
```

charset

Values: encoding | Since: HTML 4.01

Obsolete. Character set of the resource.

Write charset="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<link charset="encoding">
```

rev

Values: link types | Since: HTML 4.01

Obsolete. Reverse relationship.

Write rev="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<link rev="link types">
```

target

Values: browsing context | Since: HTML 4.01

Obsolete on link.

Write target="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<link target="browsing context">
```

<link>: worked examples

Style sheets

```
<link rel="stylesheet" href="style.css">
<link rel="stylesheet" href="print.css" media="print">
<link rel="stylesheet" href="dark.css" media="(prefers-color-scheme:
dark)">
```

Icons

```
<link rel="icon" href="favicon.ico" sizes="32x32">
<link rel="icon" href="icon.svg" type="image/svg+xml">
<link rel="apple-touch-icon" href="apple-touch-icon.png">
<link rel="manifest" href="manifest.webmanifest">
```

Performance hints

```
<link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
<link rel="preload" href="hero.jpg" as="image" fetchpriority="high">
<link rel="preload" href="font.woff2" as="font" type="font/woff2"
crossorigin>
<link rel="prefetch" href="next-page.html">
```

SEO and alternates

```
<link rel="canonical" href="https://example.com/books/html">
<link rel="alternate" hreflang="ar" href="https://example.com/ar/
books/html">
<link rel="alternate" type="application/rss+xml" title="Blog feed"
href="/feed.xml">
```

Google Fonts

```
<link rel="preconnect" href="https://fonts.googleapis.com">
<link href="https://fonts.googleapis.com/css2?family=Cairo:wght@400;
700&display=swap" rel="stylesheet">
```

Default browser CSS

```
link { display: none; }
```

Accessibility

- Alternate style sheets (rel="alternate stylesheet" title="High contrast") can offer accessible themes in browsers that support switching.

Common mistakes

- Forgetting rel.

- Using <link> to make a hyperlink (that is <a>).
- Wrong path to the CSS file (check the browser's network tab).
- Writing </link>.

See also

<style>, <a>, <script>, <meta>, <head>

Quick card: <listing>

Listing (obsolete)

The <listing> element, from the 1991 tag set, displayed its content in a monospace font exactly as written, like <pre> but originally at a smaller size and without interpreting markup. It was deprecated already in HTML 2.0 and removed in HTML 3.2. Use <pre>, optionally with <code>.

At a glance

Status	OBSOLETE
Versions	HTML 1, HTML 2.0 (deprecated); obsolete
Category	Obsolete text content
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	None (global attributes only)
Related	<pre>, <xmp>, <plaintext>

Minimal example

```
<pre><code>line 1
line 2</code></pre>
```

Most common mistake

Any use.

<listing> — Listing (obsolete)

Category: Obsolete text content | Status: OBSOLETE | Versions: HTML 1, HTML 2.0 (deprecated); obsolete

Description

The <listing> element, from the 1991 tag set, displayed its content in a monospace font exactly as written, like <pre> but originally at a smaller size and without interpreting markup. It was deprecated already in HTML 2.0 and removed in HTML 3.2. Use <pre>, optionally with <code>.

Syntax

```
<listing>text</listing>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	Historical
Permitted content	Text
Permitted parents	Flow content
Tag omission	Neither
DOM interface	HTMLPreElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<listing>: worked examples

Replacement

```
<pre><code>line 1
line 2</code></pre>
```

Default browser CSS

```
listing { display: block; font-family: monospace; white-space: pre;
margin: 1em 0; }
```

Common mistakes

- Any use.

See also

<pre>, <xmp>, <plaintext>

Quick card: <main>

Main content

The <main> element represents the dominant content of the <body>: the content that is directly related to, or expands upon, the central topic of the page or the central function of the application. It excludes content repeated across pages such as the site header, navigation, sidebars, search box, logo and footer.

At a glance

Status	CURRENT
Versions	HTML 5.1 (2016)
Category	Content sectioning
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	None (global attributes only)
Related	<header>, <footer>, <nav>, <aside>, <article>, <section>

Minimal example

```
<body>
  <a href="#content" class="skip">Skip to main content</a>
  <header>...</header>
  <nav>...</nav>
  <main id="content">
    <h1>Page title</h1>
    <p>The unique content of this page.</p>
  </main>
  <aside>...</aside>
  <footer>...</footer>
</body>
```

Most common mistake

Two visible mains.

<main> — Main content

Category: Content sectioning | Status: CURRENT | Versions: HTML 5.1 (2016)

Description

The <main> element represents the dominant content of the <body>: the content that is directly related to, or expands upon, the central topic of the page or the central function of the application. It excludes content repeated across pages such as the site header, navigation, sidebars, search box, logo and footer.

A document must not have more than one visible <main>; additional <main> elements are allowed only if all but one carry the hidden attribute. <main> must not be a descendant of <article>, <aside>, <footer>, <header> or <nav>. It is exposed as the 'main' landmark, which lets screen reader users skip straight to the content, and it is the natural target for a 'skip to content' link.

Syntax

```
<main>...</main>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	Flow content, palpable content
Permitted content	Flow content

Property	Value
Permitted parents	<html>, <body>, , <form> without an accessible name, and autonomous custom elements; not inside article, aside, footer, header or nav
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<main>: worked examples

Page structure with skip link

```
<body>
  <a href="#content" class="skip">Skip to main content</a>
  <header>...</header>
  <nav>...</nav>
  <main id="content">
    <h1>Page title</h1>
    <p>The unique content of this page.</p>
  </main>
  <aside>...</aside>
  <footer>...</footer>
</body>
```

Visually hidden skip link that appears on focus

```
<style>
  .skip { position: absolute; left: -999px; }
  .skip:focus { left: 8px; top: 8px; background: #fff; padding: 8px; }
</style>
```

Single-page app views

```
<main id="home">Home view</main>
<main id="cart" hidden>Cart view</main>
```

Only one is visible at a time.

Default browser CSS

```
main { display: block; }
```

Accessibility

- The 'main' landmark is one of the most used shortcuts in screen readers; every page should have exactly one.

Common mistakes

- Two visible mains.
- Placing main inside article or nav.
- Putting the header and footer inside main.

See also

<header>, <footer>, <nav>, <aside>, <article>, <section>

Quick card: <map>

Image map

The <map> element, together with <area> elements, defines a client-side image map: an image with several clickable regions each linking to a different destination. The map is connected to an <img> through the img's usemap attribute, which must be # followed by the map's name.

At a glance

Status	CURRENT
Versions	HTML 3.2, HTML 4.01, HTML5
Category	Image and multimedia
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	name
Related	<area>, <img>

Minimal example

```
<img src="banner.png" alt="Shop banner" usemap="#banner" width="600"
height="100">
<map name="banner">
  <area shape="rect" coords="0,0,300,100" href="books.html"
alt="Books">
  <area shape="rect" coords="300,0,600,100" href="deals.html"
alt="Deals">
</map>
```

Most common mistake

usemap without #.

<map> — Image map

Category: Image and multimedia | Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

Description

The <map> element, together with <area> elements, defines a client-side image map: an image with several clickable regions each linking to a different destination. The map is connected to an <img> through the img's usemap attribute, which must be # followed by the map's name.

Syntax

```
<map name="n">
  <area ...>
</map>
<img usemap="#n" ...>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, palpable content
Permitted content	Transparent
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLMapElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
name	text	Required. The map's name, without #, unique among maps. If id is also given it must have the same value.	HTML 3.2

<map>: attribute by attribute

Each attribute of <map> explained in detail, with a minimal example you can copy.

name

Values: text | Since: HTML 3.2

Required. The map's name, without #, unique among maps. If id is also given it must have the same value.

Write name="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<map name="value">...</map>
```

<map>: worked examples

Navigation image with two regions

```
<img src="banner.png" alt="Shop banner" usemap="#banner" width="600"
height="100">
<map name="banner">
  <area shape="rect" coords="0,0,300,100" href="books.html"
alt="Books">
  <area shape="rect" coords="300,0,600,100" href="deals.html"
alt="Deals">
</map>
```

Default browser CSS

```
map { display: inline; }
```

Accessibility

- Each area needs alt text. Provide an equivalent text list of links if the map is complex.

Common mistakes

- usemap without #.
- Map name mismatching.
- Coordinates for a different image size than displayed.

See also

<area>, <img>

Quick card: <mark>

Highlighted (marked) text

The <mark> element represents text that is marked or highlighted for reference because of its relevance in the current context. Typical uses: highlighting the search terms in a page of results, or drawing attention to a passage in a quotation that the current text discusses. Browsers render it with a yellow background, like a highlighter pen.

At a glance

Status	CURRENT
Versions	HTML5
Category	Text-level semantics
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	None (global attributes only)
Related	, ,

Minimal example

```
<p>Results for 'footer': ... the <mark>footer</mark> element
represents the <mark>footer</mark> of its section ...</p>
```

Most common mistake

Using <mark> for decorative colour.

<mark> — Highlighted (marked) text

Category: Text-level semantics | Status: CURRENT | Versions: HTML5

Description

The <mark> element represents text that is marked or highlighted for reference because of its relevance in the current context. Typical uses: highlighting the search terms in a page of results, or drawing attention to a passage in a quotation that the current text discusses. Browsers render it with a yellow background, like a highlighter pen.

Do not confuse it with (importance) or (emphasis). <mark> is about relevance to the reader's current activity, not about the author's intent.

Syntax

```
<mark>text</mark>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, palpable content
Permitted content	Phrasing content
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<mark>: worked examples

Search results

```
<p>Results for 'footer': ... the <mark>footer</mark> element
represents the <mark>footer</mark> of its section ...</p>
```

Highlighting part of a quotation

```
<blockquote><p>Any tag you learn is <mark>a tool you keep</mark>.</
p></blockquote>
<p>The phrase 'a tool you keep' is the key idea.</p>
```

Custom colour

```
<style>
  mark { background: #ffe58a; color: inherit; padding: 0 2px; }
</style>
```

Default browser CSS

```
mark { background-color: yellow; color: black; }
```

Accessibility

- Not announced by default; if the highlight matters, add visually hidden text such as '[highlight start]'.

Common mistakes

- Using <mark> for decorative colour.
- Using <mark> instead of .

See also

, ,

Quick card: <marquee>

Scrolling text (obsolete)

The <marquee> element scrolled its content horizontally or vertically across the screen. It was a Microsoft extension that became infamous alongside Netscape's <blink>. HTML5 lists it as obsolete but, because so many old pages use it, browsers still implement it. Moving text is hard to read and distracting; if you need an animation, use CSS animations with a pause control and respect the prefers-reduced-motion media query.

At a glance

Status	OBSOLETE
Versions	Internet Explorer 2 (1995), never standard; obsolete in HTML5 (but its behaviour is specified for compatibility)
Category	Obsolete presentational
Closing tag	Required unless noted under Tag omission
Display	inline-block
Own attributes	behavior, direction, loop, scrollamount, scrolldelay, truespeed, bgcolor, width, hspace
Related	<blink>

Minimal example

```
<style>
  @keyframes slide { from { transform: translateX(100%); } to {
transform: translateX(-100%); } }
  .ticker { white-space: nowrap; overflow: hidden; }
  .ticker span { display: inline-block; animation: slide 12s linear
infinite; }
  @media (prefers-reduced-motion: reduce) { .ticker span { animation:
none; } }
</style>
<div class="ticker"><span>Breaking news...</span></div>
```

Most common mistake

Any use.

<marquee> — Scrolling text (obsolete)

Category: Obsolete presentational | Status: OBSOLETE | Versions: Internet Explorer 2 (1995), never standard; obsolete in HTML5 (but its behaviour is specified for compatibility)

Description

The <marquee> element scrolled its content horizontally or vertically across the screen. It was a Microsoft extension that became infamous alongside Netscape's <blink>. HTML5 lists it as obsolete but, because so many old pages use it, browsers still implement it. Moving text is hard to read and distracting; if you need an animation, use CSS animations with a pause control and respect the prefers-reduced-motion media query.

Syntax

```
<marquee>text</marquee>
```

Technical summary

Property	Value
Void element	No
Default display	inline-block
Content categories	Historical
Permitted content	Flow content
Permitted parents	Flow content
Tag omission	Neither
DOM interface	HTMLMarqueeElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
behavior	scroll | slide | alternate	Scrolling style.	IE
direction	left | right | up | down	Scroll direction.	IE
loop	integer | -1	Repeat count.	IE
scrollamount	pixels	Distance per step.	IE
scrolldelay	ms	Delay between steps.	IE
truespeed	boolean	Allow delays under 60 ms.	IE
bgcolor	colour	Background.	IE
width / height	size	Size.	IE
hspace / vspace	pixels	Margins.	IE

<marquee>: attribute by attribute

Each attribute of <marquee> explained in detail, with a minimal example you can copy.

behavior

Values: scroll | slide | alternate | Since: IE

Scrolling style.

Write behavior="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<marquee behavior="scroll">...</marquee>
```

direction

Values: left | right | up | down | Since: IE

Scroll direction.

Write direction="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<marquee direction="left">...</marquee>
```

loop

Values: integer | -1 | Since: IE

Repeat count.

Write loop="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<marquee loop="3">...</marquee>
```

scrollamount

Values: pixels | Since: IE

Distance per step.

Write scrollamount="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<marquee scrollamount="3">...</marquee>
```

scrolldelay

Values: ms | Since: IE

Delay between steps.

Write scrolldelay="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<marquee scrolldelay="ms">...</marquee>
```

truespeed

Values: boolean | Since: IE

Allow delays under 60 ms.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<marquee truespeed>...</marquee>
```

bgcolor

Values: colour | Since: IE

Background.

Write bgcolor="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<marquee bgcolor="#336699">...</marquee>
```

width / height

Values: size | Since: IE

Size.

Write width="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<marquee width="size">...</marquee>
```

hspace / vspace

Values: pixels | Since: IE

Margins.

Write hspace="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<marquee hspace="3">...</marquee>
```

<marquee>: worked examples

CSS replacement

```
<style>
  @keyframes slide { from { transform: translateX(100%); } to {
transform: translateX(-100%); } }
  .ticker { white-space: nowrap; overflow: hidden; }
  .ticker span { display: inline-block; animation: slide 12s linear
infinite; }
  @media (prefers-reduced-motion: reduce) { .ticker span { animation:
none; } }
</style>
<div class="ticker"><span>Breaking news...</span></div>
```

Default browser CSS

```
marquee { display: inline-block; text-align: initial; }
```

Accessibility

- Moving text violates WCAG unless it can be paused.

Common mistakes

- Any use.

See also

<blink>

Quick card: <math>

MathML root

The <math> element is the top-level element of MathML (Mathematical Markup Language), which can be written directly inside HTML5 documents to display mathematical formulas. Inside <math> you use MathML elements such as <mi> (identifier), <mn> (number), <mo> (operator), <mrow> (group), <mfrac> (fraction), <msup> (superscript), <msqrt> (square root) and <mtable>. All modern browsers support MathML Core.

At a glance

Status	CURRENT
Versions	HTML5 (inline MathML)
Category	Embedded content (MathML)
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	display, xmlns
Related	<svg>, <canvas>

Minimal example

```
<math display="block">
  <mi>x</mi><mo>=</mo>
  <mfrac>
    <mrow><mo>-</mo><mi>b</mi><mo>&#xB1;</mo><msqrt><msup><mi>b</
mi><mn>2</mn></msup><mo>-</mo><mn>4</mn><mi>a</mi><mi>c</mi></msqrt></
mrow>
    <mrow><mn>2</mn><mi>a</mi></mrow>
  </mfrac>
</math>
```

Most common mistake

Writing formulas as plain text or images.

<math> — MathML root

Category: Embedded content (MathML) | Status: CURRENT | Versions: HTML5 (inline MathML)

Description

The <math> element is the top-level element of MathML (Mathematical Markup Language), which can be written directly inside HTML5 documents to display mathematical formulas. Inside <math> you use MathML elements such as <mi> (identifier), <mn> (number), <mo> (operator), <mrow> (group), <mfrac> (fraction), <msup> (superscript), <msqrt> (square root) and <mtable>. All modern browsers support MathML Core.

Syntax

```
<math>
  <mi>x</mi><mo>=</mo><mn>2</mn>
</math>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, embedded content, palpable content
Permitted content	MathML elements
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither
DOM interface	MathMLElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
display	block | inline	Whether the formula is a block on its own line or inline in text.	MathML
xmlns	http://www.w3.org/1998/Math/MathML	Namespace; optional in HTML.	MathML

<math>: attribute by attribute

Each attribute of <math> explained in detail, with a minimal example you can copy.

display

Values: block | inline | Since: MathML

Whether the formula is a block on its own line or inline in text.

Write display="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<math display="block">...</math>
```

xmlns

Values: http://www.w3.org/1998/Math/MathML | Since: MathML

Namespace; optional in HTML.

Write xmlns="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<math xmlns="http:">...</math>
```

<math>: worked examples

Quadratic formula

```
<math display="block">
  <mi>x</mi><mo>=</mo>
  <mfrac>
    <mrow><mo>-</mo><mi>b</mi><mo>&#xB1;</mo><msqrt><msup><mi>b</
mi><mn>2</mn></msup><mo>-</mo><mn>4</mn><mi>a</mi><mi>c</mi></msqrt></
mrow>
    <mrow><mn>2</mn><mi>a</mi></mrow>
  </mfrac>
</math>
```

Inline formula

```
<p>The area of a circle is <math><mi>&#x3C0;</mi><msup><mi>r</
mi><mn>2</mn></msup></math>.</p>
```

Default browser CSS

```
math { display: inline; math-style: compact; }
math[display=block] { display: block math; math-style: normal; }
```

Accessibility

- MathML is read by modern screen readers as mathematics; images of formulas are not.

Common mistakes

- Writing formulas as plain text or images.
- Forgetting display="block" for standalone equations.

See also

<svg>, <canvas>

Quick card: <menu>

Menu (toolbar list)

The <menu> element is a semantic alternative to <ul> for a list of commands or actions, such as a toolbar of buttons. Each command is an <li> containing a <button> or similar control. Browsers render it identically to <ul>.

At a glance

Status	CURRENT
Versions	HTML 1, HTML 2.0, HTML 3.2, HTML 4.01 (deprecated), HTML5 (redefined)
Category	Text content
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	compact, type, label
Related	, , <button>, <nav>, <menuitem>

Minimal example

```
<menu>
  <li><button onclick="copy()">Copy</button></li>
  <li><button onclick="cut()">Cut</button></li>
  <li><button onclick="paste()">Paste</button></li>
</menu>
```

Most common mistake

Expecting native context menus from type="context".

<menu> — Menu (toolbar list)

Category: Text content | Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01 (deprecated), HTML5 (redefined)

Description

The <menu> element is a semantic alternative to <ul> for a list of commands or actions, such as a toolbar of buttons. Each command is an <li> containing a <button> or similar control. Browsers render it identically to <ul>.

Its history is long: in HTML 1 and 2 it was a compact list like <dir>; HTML 4.01 deprecated it; early HTML5 drafts turned it into a rich context-menu system with type="context" and <menuitem> children, which no browser except Firefox implemented and which was removed; the current definition is simply 'an unordered list of interactive items'.

Syntax

```
<menu>
  <li><button>Action</button></li>
</menu>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	Flow content; palpable if it has at least one
Permitted content	Zero or more , <script>, <template>
Permitted parents	Any element that accepts flow content

Property	Value
Tag omission	Neither tag may be omitted
DOM interface	HTMLMenuElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
compact	boolean	Obsolete. Compact rendering.	HTML 2.0
type	context | toolbar | list	Obsolete. From the abandoned HTML5 context menu design.	HTML5 draft (removed)
label	text	Obsolete. Menu label (context menus).	HTML5 draft (removed)

<menu>: attribute by attribute

Each attribute of <menu> explained in detail, with a minimal example you can copy.

compact

Values: boolean | Since: HTML 2.0

Obsolete. Compact rendering.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<menu compact>...</menu>
```

type

Values: context | toolbar | list | Since: HTML5 draft (removed)

Obsolete. From the abandoned HTML5 context menu design.

Write type="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<menu type="context">...</menu>
```

label

Values: text | Since: HTML5 draft (removed)

Obsolete. Menu label (context menus).

Write label="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<menu label="value">...</menu>
```

<menu>: worked examples

Editor toolbar

```
<menu>
  <li><button onclick="copy()">Copy</button></li>
  <li><button onclick="cut()">Cut</button></li>
  <li><button onclick="paste()">Paste</button></li>
</menu>
```

Horizontal toolbar styling

```
<style>
  menu { display: flex; gap: 8px; list-style: none; padding: 0;
margin: 0; }
</style>
```

Default browser CSS

```
menu { display: block; list-style-type: disc; margin: 1em 0; padding-
inline-start: 40px; }
```

Accessibility

- Exposed as a list, the same as <ul>. Add role="toolbar" if the list is a real toolbar with arrow-key navigation.

Common mistakes

- Expecting native context menus from type="context".
- Using <menu> for navigation links (use <nav>
).

See also

, <li>, <button>, <nav>, <menuitem>

Quick card: <menuitem>

Menu item (obsolete)

The <menuitem> element represented a command in a <menu type="context">, letting a page add custom items to the browser's right-click menu. Only Firefox implemented it; it was removed from the standard in 2017 and from Firefox in 2020. Build custom menus with lists, buttons and JavaScript (or the popover attribute) instead.

At a glance

Status	OBSOLETE
Versions	HTML5 draft (Firefox only); removed 2017
Category	Obsolete interactive
Closing tag	None (void element)
Display	none
Own attributes	label, type, icon, checked
Related	<menu>, <button>

Minimal example

```
<button popovertarget="m">Options</button>
<menu id="m" popover>
  <li><button>Refresh</button></li>
</menu>
```

Most common mistake

Any use.

<menuitem> — Menu item (obsolete)

Category: Obsolete interactive | Status: OBSOLETE | Versions: HTML5 draft (Firefox only); removed 2017

Description

The <menuitem> element represented a command in a <menu type="context">, letting a page add custom items to the browser's right-click menu. Only Firefox implemented it; it was removed from the standard in 2017 and from Firefox in 2020. Build custom menus with lists, buttons and JavaScript (or the popover attribute) instead.

Syntax

```
<menuitem label="Refresh" onclick="...">
```

Technical summary

Property	Value
Void element	Yes (no closing tag)
Default display	none
Content categories	Historical
Permitted content	None
Permitted parents	<menu>
Tag omission	No end tag
DOM interface	HTMLUnknownElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
label	text	Item text.	HTML5 draft
type	command | checkbox | radio	Kind of item.	HTML5 draft
icon	URL	Icon image.	HTML5 draft
checked, disabled, default, radiogroup, command	various	State and grouping.	HTML5 draft

<menuitem>: attribute by attribute

Each attribute of <menuitem> explained in detail, with a minimal example you can copy.

label

Values: text | Since: HTML5 draft

Item text.

Write label="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<menuitem label="value">
```

type

Values: command | checkbox | radio | Since: HTML5 draft

Kind of item.

Write type="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<menuitem type="command">
```

icon

Values: URL | Since: HTML5 draft

Icon image.

Write icon="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<menuitem icon="https://example.com/page.html">
```

checked, disabled, default, radiogroup, command

Values: various | Since: HTML5 draft

State and grouping.

Write checked="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<menuitem checked="various">
```

<menuitem>: worked examples

Replacement

```
<button popovertarget="m">Options</button>
<menu id="m" popover>
  <li><button>Refresh</button></li>
</menu>
```

Common mistakes

- Any use.

See also

<menu>, <button>

Quick card: <meta>

Metadata

The <meta> element represents metadata about the document that cannot be expressed by <title>, <base>, <link>, <style> or <script>. It is a void element placed in <head>. Depending on which attributes are present it does one of four things: declares the character encoding (charset); provides document-level metadata as a name/content pair (name); simulates an HTTP response header (http-equiv); or supplies microdata (itemprop).

At a glance

Status	CURRENT
Versions	HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Document metadata
Closing tag	None (void element)
Display	none
Own attributes	charset, name, content, http-equiv, media, property, itemprop, scheme
Related	<head>, <title>, <link>, <base>

Minimal example

```
<meta charset="utf-8">
<meta name="viewport" content="width=device-width, initial-scale=1">
```

Most common mistake

Placing charset after other content or after 1024 bytes.

<meta> — Metadata

Category: Document metadata | Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <meta> element represents metadata about the document that cannot be expressed by <title>, <base>, <link>, <style> or <script>. It is a void element placed in <head>. Depending on which attributes are present it does one of four things: declares the character encoding (charset); provides document-level metadata as a name/content pair (name); simulates an HTTP response header (http-equiv); or supplies microdata (itemprop).

The most important meta tags on every page are charset and viewport. Other frequently used names are description (shown in search results), robots, author, theme-color and the Open Graph (property="og:...") and Twitter card tags used when a page is shared on social networks. Part 9 contains the full list of standard meta names.

Syntax

```
<meta charset="utf-8">
<meta name="description" content="...">
```

Technical summary

Property	Value
Void element	Yes (no closing tag)
Default display	none
Content categories	Metadata content; flow and phrasing content if itemprop is present

Property	Value
Permitted content	None (void element)
Permitted parents	<head>; <noscript> in head; anywhere if itemprop is present
Tag omission	No end tag
DOM interface	HTMLMetaElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
charset	utf-8	Declares the document's character encoding. The only valid value in HTML5 is utf-8 (case-insensitive). Must be in the first 1024 bytes.	HTML5
name	metadata name	The kind of metadata: application-name, author, description, generator, keywords, referrer, theme-color, color-scheme, viewport, robots, googlebot, creator, publisher, and more.	HTML 2.0
content	text	The value for name or http-equiv. Required with them.	HTML 2.0
http-equiv	content-type | default-style | refresh | content-security-policy | x-ua-compatible	Pragma directive that acts like an HTTP header.	HTML 2.0
media	media query	With name=theme-color: apply only when the query matches.	Living Standard

Attribute	Values	Description	Since
property	text	Not in the HTML standard but universally used for RDFa / Open Graph tags such as og:title.	RDFa
itemprop	text	Microdata property name.	HTML5 microdata
scheme	text	Obsolete. Interpretation scheme for content.	HTML 4.01

<meta>: attribute by attribute

Each attribute of <meta> explained in detail, with a minimal example you can copy.

charset

Values: utf-8 | Since: HTML5

Declares the document's character encoding. The only valid value in HTML5 is utf-8 (case-insensitive). Must be in the first 1024 bytes.

Write charset="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<meta charset="utf-8">
```

name

Values: metadata name | Since: HTML 2.0

The kind of metadata: application-name, author, description, generator, keywords, referrer, theme-color, color-scheme, viewport, robots, googlebot, creator, publisher, and more.

Write name="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<meta name="metadata name">
```

content

Values: text | Since: HTML 2.0

The value for name or http-equiv. Required with them.

Write content="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<meta content="value">
```

http-equiv

Values: content-type | default-style | refresh | content-security-policy | x-ua-compatible | Since: HTML 2.0

Pragma directive that acts like an HTTP header.

Write http-equiv="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<meta http-equiv="content-type">
```

media

Values: media query | Since: Living Standard

With name=theme-color: apply only when the query matches.

Write media="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<meta media="media query">
```

property

Values: text | Since: RDFa

Not in the HTML standard but universally used for RDFa / Open Graph tags such as og:title.

Write property="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<meta property="value">
```

itemprop

Values: text | Since: HTML5 microdata

Microdata property name.

Write itemprop="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<meta itemprop="value">
```

scheme

Values: text | Since: HTML 4.01

Obsolete. Interpretation scheme for content.

Write scheme="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<meta scheme="value">
```

<meta>: worked examples

The essential pair

```
<meta charset="utf-8">
<meta name="viewport" content="width=device-width, initial-scale=1">
```

Without the viewport tag, phones render the page as if it were 980px wide and shrink it.

Search engine metadata

```
<meta name="description" content="Buy PDF books in Arabic and English;
 pay with mobile wallet and download instantly.">
<meta name="robots" content="index, follow">
<meta name="author" content="Book Store team">
```

Social sharing (Open Graph and Twitter)

```
<meta property="og:title" content="Learn HTML">
<meta property="og:description" content="A complete reference.">
<meta property="og:image" content="https://example.com/cover.jpg">
<meta property="og:url" content="https://example.com/html">
<meta name="twitter:card" content="summary_large_image">
```

Theme colour and colour scheme

```
<meta name="theme-color" content="#e60000">
<meta name="theme-color" content="#111" media="(prefers-color-scheme:
dark)">
<meta name="color-scheme" content="light dark">
```

Redirect after 5 seconds (use sparingly)

```
<meta http-equiv="refresh" content="5; url=https://example.com/new-
page">
```

Content Security Policy

```
<meta http-equiv="content-security-policy" content="default-src
'self'; img-src https:">
```

Old HTML 4 encoding declaration

```
<!-- HTML 4.01 -->
<meta http-equiv="Content-Type" content="text/html; charset=utf-8">

<!-- HTML5 -->
<meta charset="utf-8">
```

Default browser CSS

```
meta { display: none; }
```

Accessibility

- Never use <meta name="viewport" content="user-scalable=no"> or maximum-scale=1; it stops users zooming and fails WCAG.
- Automatic refresh/redirect disorients users; prefer server-side redirects.

Common mistakes

- Placing charset after other content or after 1024 bytes.
- Using keywords meta (ignored by search engines since 2009).
- Writing </meta>.

See also

<head>, <title>, <link>, <base>

Quick card: <meter>

Scalar measurement (gauge)

The <meter> element represents a scalar measurement within a known range, or a fractional value: disk usage, the relevance of a search result, password strength, a score out of ten, temperature within safe limits. Browsers render it as a gauge bar whose colour changes depending on whether the value is in the optimum, suboptimal or bad region defined by low, high and optimum.

At a glance

Status	CURRENT
Versions	HTML5
Category	Forms
Closing tag	Required unless noted under Tag omission
Display	inline-block
Own attributes	value, min, max, low, high, optimum, form
Related	<progress>, <output>, <input>

Minimal example

```
<label for="disk">Disk usage</label>
<meter id="disk" value="70" min="0" max="100" low="60" high="85"
optimum="20">70%</meter>
```

Most common mistake

Using it as a progress bar.

<meter> — Scalar measurement (gauge)

Category: Forms | Status: CURRENT | Versions: HTML5

Description

The <meter> element represents a scalar measurement within a known range, or a fractional value: disk usage, the relevance of a search result, password strength, a score out of ten, temperature within safe limits. Browsers render it as a gauge bar whose colour changes depending on whether the value is in the optimum, suboptimal or bad region defined by low, high and optimum.

Do not use <meter> for progress of a task; that is what <progress> is for. And do not use it for values with no known maximum (such as a bank balance) because the gauge needs a range.

Syntax

```
<meter value="0.6">60%</meter>
```

Technical summary

Property	Value
Void element	No
Default display	inline-block
Content categories	Flow content, phrasing content, labelable, palpable content
Permitted content	Phrasing content, but no <meter> descendants
Permitted parents	Any element that accepts phrasing content

Property	Value
Tag omission	Neither tag may be omitted
DOM interface	HTMLMeterElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
value	number	Required. The current value, between min and max.	HTML5
min	number	Lower bound of the range. Default 0.	HTML5
max	number	Upper bound. Default 1.	HTML5
low	number	Upper bound of the 'low' region.	HTML5
high	number	Lower bound of the 'high' region.	HTML5
optimum	number	The ideal value. Determines which region is shown as good (green) versus bad (red/yellow).	HTML5
form	form id	Associated form (for labelling purposes).	HTML5

<meter>: attribute by attribute

Each attribute of <meter> explained in detail, with a minimal example you can copy.

value

Values: number | Since: HTML5

Required. The current value, between min and max.

Write value="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<meter value="3">...</meter>
```

min

Values: number | Since: HTML5

Lower bound of the range. Default 0.

Write min="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<meter min="3">...</meter>
```

max

Values: number | Since: HTML5

Upper bound. Default 1.

Write max="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<meter max="3">...</meter>
```

low

Values: number | Since: HTML5

Upper bound of the 'low' region.

Write low="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<meter low="3">...</meter>
```

high

Values: number | Since: HTML5

Lower bound of the 'high' region.

Write high="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<meter high="3">...</meter>
```

optimum

Values: number | Since: HTML5

The ideal value. Determines which region is shown as good (green) versus bad (red/yellow).

Write optimum="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<meter optimum="3">...</meter>
```

form

Values: form id | Since: HTML5

Associated form (for labelling purposes).

Write form="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<meter form="form id">...</meter>
```

<meter>: worked examples

Disk usage

```
<label for="disk">Disk usage</label>
<meter id="disk" value="70" min="0" max="100" low="60" high="85"
optimum="20">70%</meter>
```

Because optimum is low, 70 (above low) shows in yellow and anything above 85 in red.

Score out of ten

```
<p>Rating: <meter value="8" min="0" max="10">8 out of 10</meter></p>
```

Fraction

```
<meter value="0.25">25%</meter>
```

Default range 0 to 1.

Default browser CSS

```
meter { display: inline-block; appearance: auto; }
```

Accessibility

- Provide the value as text inside the element or in a label; the bar alone is not enough.
- Always label the meter.

Common mistakes

- Using it as a progress bar.
- Omitting value.
- Value outside min-max (it is clamped).

See also

<progress>, <output>, <input>

Quick card: <multicol>

Multi-column text (non-standard, obsolete)

The <multicol> element split its content into newspaper-style columns. It existed only in Netscape Navigator 3 and 4 and was never standardised. Use the CSS multi-column properties (column-count, column-width, column-gap) instead.

At a glance

Status	OBSOLETE
Versions	Netscape 3 only; never standard
Category	Obsolete presentational
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	cols, gutter, width
Related	

Minimal example

```
<div style="column-count: 3; column-gap: 20px">Long text...</div>
```

Most common mistake

Any use.

<multicol> — Multi-column text (non-standard, obsolete)

Category: Obsolete presentational | Status: OBSOLETE | Versions: Netscape 3 only; never standard

Description

The <multicol> element split its content into newspaper-style columns. It existed only in Netscape Navigator 3 and 4 and was never standardised. Use the CSS multi-column properties (column-count, column-width, column-gap) instead.

Syntax

```
<multicol cols="3" gutter="20">text</multicol>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	Historical
Permitted content	Flow content
Permitted parents	Flow content
Tag omission	Neither
DOM interface	HTMLUnknownElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
cols	integer	Number of columns.	Netscape
gutter	pixels	Space between columns.	Netscape
width	pixels	Column width.	Netscape

<multicol>: attribute by attribute

Each attribute of <multicol> explained in detail, with a minimal example you can copy.

cols

Values: integer | Since: Netscape

Number of columns.

Write cols="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<multicol cols="3">...</multicol>
```

gutter

Values: pixels | Since: Netscape

Space between columns.

Write gutter="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<multicol gutter="3">...</multicol>
```

width

Values: pixels | Since: Netscape

Column width.

Write width="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<multicol width="3">...</multicol>
```

<multicol>: worked examples

CSS replacement

```
<div style="column-count: 3; column-gap: 20px">Long text...</div>
```

Common mistakes

- Any use.

See also

Quick card: <nav>

Navigation section

The <nav> element represents a section of the page whose purpose is to provide navigation links, either within the current document or to other documents. Typical uses are the main site menu, a table of contents, breadcrumbs, pagination and 'previous/next' links.

At a glance

Status	CURRENT
Versions	HTML5
Category	Content sectioning
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	None (global attributes only)
Related	<header>, <footer>, <a>, , <menu>, <main>

Minimal example

```
<nav aria-label="Main">
  <ul>
    <li><a href="/" aria-current="page">Home</a></li>
    <li><a href="/books">Books</a></li>
    <li><a href="/about">About</a></li>
    <li><a href="/contact">Contact</a></li>
  </ul>
</nav>
```

Most common mistake

Wrapping every link group in <nav>.

<nav> — Navigation section

Category: Content sectioning | Status: CURRENT | Versions: HTML5

Description

The <nav> element represents a section of the page whose purpose is to provide navigation links, either within the current document or to other documents. Typical uses are the main site menu, a table of contents, breadcrumbs, pagination and 'previous/next' links.

Not every group of links needs a <nav>; it is intended for major navigation blocks. The list of links in a page footer, for example, is usually fine as a plain list, although a <nav> there is also acceptable. A page can have several <nav> elements; give each an aria-label so screen reader users can tell them apart. Links inside a <nav> are conventionally wrapped in a <ul>.

Syntax

```
<nav>
  <ul>
    <li><a href="...">Link</a></li>
  </ul>
</nav>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	Flow content, sectioning content, palpable content
Permitted content	Flow content

Property	Value
Permitted parents	Any element that accepts flow content, but not <address>
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<nav>: worked examples

Main site navigation

```
<nav aria-label="Main">
  <ul>
    <li><a href="/" aria-current="page">Home</a></li>
    <li><a href="/books">Books</a></li>
    <li><a href="/about">About</a></li>
    <li><a href="/contact">Contact</a></li>
  </ul>
</nav>
```

Breadcrumbs

```
<nav aria-label="Breadcrumb">
  <ol>
    <li><a href="/">Home</a></li>
    <li><a href="/books">Books</a></li>
    <li aria-current="page">Learn HTML</li>
  </ol>
</nav>
```

Horizontal menu CSS

```
<style>
  nav ul { display: flex; gap: 24px; list-style: none; margin: 0;
padding: 0; }
  nav a { text-decoration: none; color: #1b2431; font-weight: 600; }
  nav a[aria-current="page"] { border-bottom: 2px solid #e60000; }
</style>
```

Table of contents

```
<nav aria-label="On this page">
  <h2>Contents</h2>
  <ol>
    <li><a href="#intro">Introduction</a></li>
    <li><a href="#tags">Tags</a></li>
  </ol>
</nav>
```

Default browser CSS

```
nav { display: block; }
```

Accessibility

- Exposed as the 'navigation' landmark.
- Label multiple navs with aria-label.

- Mark the current page with aria-current="page".
- Provide a skip link so keyboard users can bypass long menus.

Common mistakes

- Wrapping every link group in <nav>.
- Putting non-navigation content inside.
- Not using a list for the links.

See also

<header>, <footer>, <a>, <ul>, <menu>, <main>

Quick card: <nextid>

Next identifier (HTML 1 editor hint)

The <nextid> element was used by the very first HTML editors (the NeXT-based editor written at CERN) to remember the next automatically generated anchor name, so that the editor could continue numbering anchors (z1, z2, z3...) when a document was reopened. It carried a single attribute, n, holding that name. It had no visible effect and was placed in the <head>.

At a glance

Status	OBSOLETE
Versions	HTML 1 / HTML 2.0 (RFC 1866); removed in HTML 3.2
Category	Obsolete
Closing tag	None (void element)
Display	none
Own attributes	n
Related	<head>, <isindex>, <listing>

Minimal example

```
<head>
  <title>Welcome</title>
  <nextid n="z5">
</head>
```

Most common mistake

Any use in a new document.

<nextid> — Next identifier (HTML 1 editor hint)

Category: Obsolete | Status: OBSOLETE | Versions: HTML 1 / HTML 2.0 (RFC 1866); removed in HTML 3.2

Description

The <nextid> element was used by the very first HTML editors (the NeXT-based editor written at CERN) to remember the next automatically generated anchor name, so that the editor could continue numbering anchors (z1, z2, z3...) when a document was reopened. It carried a single attribute, n, holding that name. It had no visible effect and was placed in the <head>.

It was already marked as an editor-only feature in HTML 2.0 and was dropped from HTML 3.2. Modern browsers ignore it entirely. It is documented here only for completeness, because it appears in the earliest HTML specifications and in archived pages from 1991 to 1995.

Syntax

```
<nextid n="z12">
```

Technical summary

Property	Value
Void element	Yes (no closing tag)
Default display	none
Content categories	None (obsolete)
Permitted content	None (void element)

Property	Value
Permitted parents	<head> (historically)
Tag omission	No end tag
DOM interface	HTMLUnknownElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
n	Text (anchor name)	The next anchor name the editor should generate.	HTML 1

<nextid>: attribute by attribute

Each attribute of <nextid> explained in detail, with a minimal example you can copy.

n

Values: Text (anchor name) | Since: HTML 1

The next anchor name the editor should generate.

Write n="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<nextid n="value">
```

<nextid>: worked examples

Historical usage

```
<head>
  <title>Welcome</title>
  <nextid n="z5">
</head>
```

Ignored by all modern browsers.

Default browser CSS

```
nextid { display: none; }
```

Common mistakes

- Any use in a new document.

See also

<head>, <isindex>, <listing>

Quick card: <nobr>

No line break (non-standard, obsolete)

The <nobr> element prevented the browser from wrapping its text onto a new line. It was never standardised. Use CSS white-space: nowrap instead.

At a glance

Status	OBSOLETE
Versions	Netscape / IE extension, never standard; obsolete
Category	Obsolete presentational
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	None (global attributes only)
Related	<wbr>,

Minimal example

```
<span style="white-space: nowrap">+20 100 000 0000</span>
```

Most common mistake

Any use.

<nobr> — No line break (non-standard, obsolete)

Category: Obsolete presentational | Status: OBSOLETE | Versions: Netscape / IE extension, never standard; obsolete

Description

The <nobr> element prevented the browser from wrapping its text onto a new line. It was never standardised. Use CSS white-space: nowrap instead.

Syntax

```
<nobr>text that will not wrap</nobr>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Historical
Permitted content	Phrasing content
Permitted parents	Phrasing content
Tag omission	Neither
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<nobr>: worked examples

CSS replacement

```
<span style="white-space: nowrap">+20 100 000 0000</span>
```

Default browser CSS

```
nobr { white-space: nowrap; }
```

Common mistakes

- Any use.

See also

<wbr>,

Quick card: <noembed>

Fallback for embed (obsolete)

The <noembed> element provided fallback content for browsers that did not support <embed>. It was never standard and is obsolete. Use <object> with fallback content, or <video>/<audio> with fallback content inside them.

At a glance

Status	OBSOLETE
Versions	Netscape extension; obsolete
Category	Obsolete embedded content
Closing tag	Required unless noted under Tag omission
Display	none
Own attributes	None (global attributes only)
Related	<embed>, <object>

Minimal example

```
<object data="movie.mp4" type="video/mp4">
  <p>Your browser cannot play this video. <a href="movie.
mp4">Download it</a>.</p>
</object>
```

Most common mistake

Any use.

<noembed> — Fallback for embed (obsolete)

Category: Obsolete embedded content | Status: OBSOLETE | Versions: Netscape extension; obsolete

Description

The <noembed> element provided fallback content for browsers that did not support <embed>. It was never standard and is obsolete. Use <object> with fallback content, or <video>/<audio> with fallback content inside them.

Syntax

```
<noembed>fallback</noembed>
```

Technical summary

Property	Value
Void element	No
Default display	none
Content categories	Historical
Permitted content	Flow content
Permitted parents	Flow content
Tag omission	Neither
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<noembed>: worked examples

Replacement

```
<object data="movie.mp4" type="video/mp4">
  <p>Your browser cannot play this video. <a href="movie.
mp4">Download it</a>.</p>
</object>
```

Default browser CSS

```
noembed { display: none; }
```

Common mistakes

- Any use.

See also

<embed>, <object>

Quick card: <noframes>

Fallback for frames (obsolete)

The <noframes> element contained content to display in browsers that did not support frames. It became obsolete together with <frameset> and <frame> in HTML5.

At a glance

Status	OBSOLETE
Versions	HTML 4.01 Frameset; obsolete in HTML5
Category	Obsolete frames
Closing tag	Required unless noted under Tag omission
Display	none
Own attributes	None (global attributes only)
Related	<frameset>, <frame>

Minimal example

```
<frameset cols="200,*">
  <frame src="menu.html">
  <frame src="main.html">
  <noframes><body><p>This page uses frames.</p></body></noframes>
</frameset>
```

Most common mistake

Any use.

<noframes> — Fallback for frames (obsolete)

Category: Obsolete frames | Status: OBSOLETE | Versions: HTML 4.01 Frameset; obsolete in HTML5

Description

The <noframes> element contained content to display in browsers that did not support frames. It became obsolete together with <frameset> and <frame> in HTML5.

Syntax

```
<noframes><body>fallback</body></noframes>
```

Technical summary

Property	Value
Void element	No
Default display	none
Content categories	Historical
Permitted content	Flow content (a <body>)
Permitted parents	<frameset>
Tag omission	Neither
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<noframes>: worked examples

Historical

```
<frameset cols="200,*">
  <frame src="menu.html">
  <frame src="main.html">
  <noframes><body><p>This page uses frames.</p></body></noframes>
</frameset>
```

Default browser CSS

```
noframes { display: none; }
```

Common mistakes

- Any use.

See also

<frameset>, <frame>

Quick card: <noscript>

Fallback when scripting is disabled

The <noscript> element defines content to be shown only if scripting is disabled in the browser or the browser does not support scripting. When scripting is enabled the content is ignored entirely (in fact the parser treats it as raw text). It may be used in <head> (containing only <link>, <style> and <meta>) and in <body>.

At a glance

Status	CURRENT
Versions	HTML 4.01, HTML5
Category	Scripting
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	None (global attributes only)
Related	<script>, <template>

Minimal example

```
<noscript>
  <p><strong>This page works best with JavaScript enabled.</strong></
p>
</noscript>
```

Most common mistake

Nesting noscript.

<noscript> — Fallback when scripting is disabled

Category: Scripting | Status: CURRENT | Versions: HTML 4.01, HTML5

Description

The <noscript> element defines content to be shown only if scripting is disabled in the browser or the browser does not support scripting. When scripting is enabled the content is ignored entirely (in fact the parser treats it as raw text). It may be used in <head> (containing only <link>, <style> and <meta>) and in <body>.

Common uses: a warning that the site requires JavaScript, a non-JavaScript version of a widget, or a <link> to a style sheet that only applies when scripts are off. Tracking pixels from analytics services also use it as a fallback.

Syntax

```
<noscript>fallback content</noscript>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Metadata content, flow content, phrasing content
Permitted content	In <head>: <link>, <style>, <meta>. In <body>: transparent content, but no <noscript> descendants
Permitted parents	<head> and any element that accepts phrasing content
Tag omission	Neither tag may be omitted

Property	Value
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<noscript>: worked examples

Warning message

```
<noscript>
  <p><strong>This page works best with JavaScript enabled.</strong></
p>
</noscript>
```

Non-JavaScript style sheet

```
<head>
  <noscript><link rel="stylesheet" href="no-js.css"></noscript>
</head>
```

Image fallback for lazy-loaded pictures

```
<img data-src="big.jpg" alt="Sunset" class="lazy">
<noscript><img src="big.jpg" alt="Sunset"></noscript>
```

Default browser CSS

```
noscript { display: inline; }
```

Accessibility

- Do not assume screen reader users have scripts disabled; almost all use JavaScript-enabled browsers.

Common mistakes

- Nesting noscript.
- Expecting noscript content to appear when a script merely fails to load (it appears only when scripting is off).

See also

<script>, <template>

Quick card: <object>

External object

The <object> element represents an external resource, treated as an image, a nested browsing context (like an iframe) or a resource handled by a plug-in, depending on its type. It was introduced in HTML 4.01 as a universal replacement for <img>, <applet> and <embed>. Unlike <embed>, it accepts fallback content between its tags, shown if the resource cannot be displayed, and it may contain <param> elements (now obsolete) that pass parameters to plug-ins.

At a glance

Status	CURRENT
Versions	HTML 4.01, HTML5
Category	Embedded content
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	data, type, name, width, form, usemap, archive
Related	<embed>, <iframe>, <img>, <param>, <video>

Minimal example

```
<object data="catalogue.pdf" type="application/pdf" width="100%"
height="600">
  <p>Your browser cannot display the PDF. <a href="catalogue.
pdf">Download it</a>.</p>
</object>
```

Most common mistake

Using <object> for video.

<object> — External object

Category: Embedded content | Status: CURRENT | Versions: HTML 4.01, HTML5

Description

The <object> element represents an external resource, treated as an image, a nested browsing context (like an iframe) or a resource handled by a plug-in, depending on its type. It was introduced in HTML 4.01 as a universal replacement for <img>, <applet> and <embed>. Unlike <embed>, it accepts fallback content between its tags, shown if the resource cannot be displayed, and it may contain <param> elements (now obsolete) that pass parameters to plug-ins.

Today <object> is mainly used to embed PDFs and SVG images with fallback. For video, audio and other pages, the dedicated elements are better.

Syntax

```
<object data="URL" type="MIME" width="W" height="H">fallback</object>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, embedded content, listed, form-associated, palpable content; interactive if usemap
Permitted content	Transparent (fallback content); historically zero or more <param> first

Property	Value
Permitted parents	Any element that accepts embedded content
Tag omission	Neither tag may be omitted
DOM interface	HTMLObjectElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
data	URL	The resource URL. Required (or classid historically).	HTML 4.01
type	MIME type	The content type of the resource, for example application/pdf, image/svg+xml.	HTML 4.01
name	text	Name of the browsing context (for use as a target).	HTML 4.01
width / height	pixels	Display size.	HTML 4.01
form	form id	Associated form.	HTML5
usemap	#map	Image map to use (obsolete in the Living Standard).	HTML 4.01

Attribute	Values	Description	Since
archive, classid, codebase, codetype, declare, standby, typemustmatch, border, align, hspace, vspace	various	Obsolete attributes from HTML 4.01 plug-in usage or presentational attributes. Use CSS or drop them.	HTML 4.01 / HTML5 (removed)

<object>: attribute by attribute

Each attribute of <object> explained in detail, with a minimal example you can copy.

data

Values: URL | Since: HTML 4.01

The resource URL. Required (or classid historically).

Write data="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<object data="https://example.com/page.html">...</object>
```

type

Values: MIME type | Since: HTML 4.01

The content type of the resource, for example application/pdf, image/svg+xml.

Write type="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<object type="text/plain">...</object>
```

name

Values: text | Since: HTML 4.01

Name of the browsing context (for use as a target).

Write name="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<object name="value">...</object>
```

width / height

Values: pixels | Since: HTML 4.01

Display size.

Write width="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<object width="3">...</object>
```

form

Values: form id | Since: HTML5

Associated form.

Write form="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<object form="form id">...</object>
```

usemap

Values: #map | Since: HTML 4.01

Image map to use (obsolete in the Living Standard).

Write usemap="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<object usemap="#map">...</object>
```

archive, classid, codebase, codetype, declare, standby, typemustmatch, border, align, hspace, vspace

Values: various | Since: HTML 4.01 / HTML5 (removed)

Obsolete attributes from HTML 4.01 plug-in usage or presentational attributes. Use CSS or drop them.

Write archive="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<object archive="various">...</object>
```

<object>: worked examples

PDF with fallback link

```
<object data="catalogue.pdf" type="application/pdf" width="100%"
height="600">
  <p>Your browser cannot display the PDF. <a href="catalogue.
pdf">Download it</a>.</p>
</object>
```

SVG with PNG fallback

```
<object data="chart.svg" type="image/svg+xml" width="400"
height="300">
  <img src="chart.png" alt="Sales chart for 2026" width="400"
height="300">
</object>
```

Default browser CSS

```
object { display: inline; }
```

Accessibility

- Provide fallback content that is accessible; there is no alt attribute on object.
- Add a title for screen readers when the object is a nested page.

Common mistakes

- Using <object> for video.
- Nested objects several levels deep as a 'fallback chain' for old plug-ins.

See also

<embed>, <iframe>, <img>, <param>, <video>

Quick card:

Ordered list

The <ol> element represents an ordered list of items: a list where the order matters, such as the steps of a recipe, the ranking of a competition, or the chapters of a book. Browsers number the items automatically. Each item is an <li>. If the order is not meaningful, use <ul> instead.

At a glance

Status	CURRENT
Versions	HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Text content
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	type, start, reversed, compact
Related	, , <menu>, <dl>

Minimal example

```
<ol>
  <li>Open the editor.</li>
  <li>Write the HTML.</li>
  <li>Save as index.html.</li>
  <li>Open it in the browser.</li>
</ol>
```

Most common mistake

Using <ol> when order does not matter.

 — Ordered list

Category: Text content | Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <ol> element represents an ordered list of items: a list where the order matters, such as the steps of a recipe, the ranking of a competition, or the chapters of a book. Browsers number the items automatically. Each item is an <li>. If the order is not meaningful, use <ul> instead.

The type attribute selects the numbering system (numbers, letters, roman numerals), start sets the first number and reversed counts downward. These attributes are not presentational and remain valid in HTML5 because changing the numbering style can change the meaning of references such as 'see item iv'. For purely visual changes use CSS list-style-type.

Syntax

```
<ol>
  <li>First</li>
  <li>Second</li>
</ol>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	Flow content; palpable if it has at least one
Permitted content	Zero or more , <script>, <template>

Property	Value
Permitted parents	Any element that accepts flow content
Tag omission	Neither tag may be omitted
DOM interface	HTMLOListElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
type	1 | a | A | i | I	Numbering type: decimal (default), lowercase letters, uppercase letters, lowercase roman, uppercase roman.	HTML 3.2
start	integer	The number of the first item (always a decimal integer even if type is a or i).	HTML 3.2
reversed	boolean	Number the items in descending order.	HTML5
compact	boolean	Obsolete. Compact rendering.	HTML 2.0

: attribute by attribute

Each attribute of <ol> explained in detail, with a minimal example you can copy.

type

Values: 1 | a | A | i | I | Since: HTML 3.2

Numbering type: decimal (default), lowercase letters, uppercase letters, lowercase roman, uppercase roman.

Write type="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<ol type="1">...</ol>
```

start

Values: integer | Since: HTML 3.2

The number of the first item (always a decimal integer even if type is a or i).

Write start="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<ol start="3">...</ol>
```

reversed

Values: boolean | Since: HTML5

Number the items in descending order.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<ol reversed>...</ol>
```

compact

Values: boolean | Since: HTML 2.0

Obsolete. Compact rendering.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<ol compact>...</ol>
```

: worked examples

Steps

```
<ol>
  <li>Open the editor.</li>
  <li>Write the HTML.</li>
  <li>Save as index.html.</li>
  <li>Open it in the browser.</li>
</ol>
```

Letters and roman numerals

```
<ol type="A">
  <li>Option A</li>
  <li>Option B</li>
</ol>
<ol type="i" start="4">
  <li>iv</li>
  <li>v</li>
</ol>
```

Countdown

```
<ol reversed>
  <li>Third place</li>
  <li>Second place</li>
  <li>Winner</li>
</ol>
```

Numbers 3, 2, 1.

Nested numbering with CSS counters

```
<style>
  ol { counter-reset: item; list-style: none; }
  ol li::before { counter-increment: item; content: counters(item, '.
') ' '; }
</style>
<ol>
  <li>Intro
    <ol>
      <li>History</li>
      <li>Syntax</li>
    </ol>
  </li>
</ol>
```

Produces 1, 1.1, 1.2.

Removing the numbers

```
<ol style="list-style: none; padding: 0">...</ol>
```

Default browser CSS

```
ol { display: block; list-style-type: decimal; margin: 1em 0; padding-
inline-start: 40px; }
```

Accessibility

- Screen readers announce 'list, 4 items' and the number of each item, which is very helpful for instructions.

Common mistakes

- Using <ol> when order does not matter.
- Writing the numbers by hand inside the items.
- Putting text directly inside <ol> outside of <li>.

See also

, <li>, <menu>, <dl>

Quick card: <optgroup>

Option group

The <optgroup> element groups related <option> elements inside a <select> under a non-selectable heading given by the label attribute. Groups cannot be nested. Disabling an optgroup disables all its options.

At a glance

Status	CURRENT
Versions	HTML 4.01, HTML5
Category	Forms
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	label, disabled
Related	<select>, <option>

Minimal example

```
<label for="city">City</label>
<select id="city" name="city">
  <optgroup label="Egypt">
    <option value="cai">Cairo</option>
    <option value="giz">Giza</option>
    <option value="alx">Alexandria</option>
  </optgroup>
  <optgroup label="Saudi Arabia">
    <option value="ruh">Riyadh</option>
    <option value="jed">Jeddah</option>
  </optgroup>
</select>
```

Most common mistake

Omitting label.

<optgroup> — Option group

Category: Forms | Status: CURRENT | Versions: HTML 4.01, HTML5

Description

The <optgroup> element groups related <option> elements inside a <select> under a non-selectable heading given by the label attribute. Groups cannot be nested. Disabling an optgroup disables all its options.

Syntax

```
<select>
  <optgroup label="Group">
    <option>...</option>
  </optgroup>
</select>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	None
Permitted content	Zero or more <option>, <script>, <template>; optionally a <legend> first in newer browsers with customisable select
Permitted parents	<select>
Tag omission	End tag may be omitted if followed by another <optgroup> or if there is no more content in the parent
DOM interface	HTMLOptGroupElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
label	text	Required. The group heading shown in the list.	HTML 4.01
disabled	boolean	Disables all options in the group.	HTML 4.01

<optgroup>: attribute by attribute

Each attribute of <optgroup> explained in detail, with a minimal example you can copy.

label

Values: text | Since: HTML 4.01

Required. The group heading shown in the list.

Write label="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<optgroup label="value">...</optgroup>
```

disabled

Values: boolean | Since: HTML 4.01

Disables all options in the group.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<optgroup disabled>...</optgroup>
```

<optgroup>: worked examples

Cities grouped by country

```
<label for="city">City</label>
<select id="city" name="city">
  <optgroup label="Egypt">
    <option value="cai">Cairo</option>
    <option value="giz">Giza</option>
    <option value="alx">Alexandria</option>
  </optgroup>
  <optgroup label="Saudi Arabia">
    <option value="ruh">Riyadh</option>
    <option value="jed">Jeddah</option>
  </optgroup>
</select>
```

Default browser CSS

```
optgroup { display: block; font-weight: bold; font-style: normal; }
```

Accessibility

- Screen readers announce the group label when entering the group.

Common mistakes

- Omitting label.
- Nesting optgroups.
- Trying to make the group heading selectable.

See also

<select>, <option>

Quick card: <option>

Option

The <option> element defines one item in a <select> drop-down list, an <optgroup>, or a <datalist> of suggestions. Its text content is what the user sees; the value attribute is what is submitted with the form. If value is omitted the text content is submitted instead.

At a glance

Status	CURRENT
Versions	HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Forms
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	value, selected, disabled, label
Related	<select>, <optgroup>, <datalist>

Minimal example

```
<select name="size">
  <option value="">-- Choose a size --</option>
  <option value="s">Small</option>
  <option value="m" selected>Medium</option>
  <option value="l">Large</option>
</select>
```

Most common mistake

Nesting HTML inside option (only text is allowed).

<option> — Option

Category: Forms | Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <option> element defines one item in a <select> drop-down list, an <optgroup>, or a <datalist> of suggestions. Its text content is what the user sees; the value attribute is what is submitted with the form. If value is omitted the text content is submitted instead.

The selected attribute pre-selects the option. In a single-select list only one option should be selected; in a <select multiple> several may be. The end tag may be omitted.

Syntax

```
<option value="v">Text</option>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	None
Permitted content	Text, optionally with escaped characters
Permitted parents	<select>, <optgroup>, <datalist>
Tag omission	End tag may be omitted if followed by another <option> or <optgroup>, or if there is no more content in the parent
DOM interface	HTMLOptionElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
value	text	The value submitted when this option is selected. Defaults to the text content.	HTML 2.0
selected	boolean	Initially selected.	HTML 2.0
disabled	boolean	Cannot be selected.	HTML 4.01
label	text	Alternative label shown instead of the text content (used mainly in datalist).	HTML 4.01

<option>: attribute by attribute

Each attribute of <option> explained in detail, with a minimal example you can copy.

value

Values: text | Since: HTML 2.0

The value submitted when this option is selected. Defaults to the text content.

Write value="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<option value="value">...</option>
```

selected

Values: boolean | Since: HTML 2.0

Initially selected.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<option selected>...</option>
```

disabled

Values: boolean | Since: HTML 4.01

Cannot be selected.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<option disabled>...</option>
```

label

Values: text | Since: HTML 4.01

Alternative label shown instead of the text content (used mainly in datalist).

Write label="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<option label="value">...</option>
```

<option>: worked examples

Basic select

```
<select name="size">
  <option value="">-- Choose a size --</option>
  <option value="s">Small</option>
  <option value="m" selected>Medium</option>
  <option value="l">Large</option>
</select>
```

The first option with an empty value acts as a placeholder; combine with required to force a choice.

Disabled placeholder that cannot be re-selected

```
<select required>
  <option value="" disabled selected>Select a country</option>
  <option>Egypt</option>
</select>
```

Datalist options with labels

```
<datalist id="codes">
  <option value="EG" label="Egypt">
  <option value="SA" label="Saudi Arabia">
</datalist>
```

Default browser CSS

```
option { display: block; padding: 0 2px 1px; white-space: nowrap; min-height: 1.2em; }
```

Accessibility

- Keep option text short and unique.
- Do not rely on colour alone to differentiate options.

Common mistakes

- Nesting HTML inside option (only text is allowed).
- Multiple selected options in a single select (the last wins).
- Forgetting the value so a long label is submitted.

See also

<select>, <optgroup>, <datalist>

Quick card: <output>

Calculation or user-action result

The <output> element is a container into which a site or app can inject the result of a calculation or the outcome of a user action, for example the total price in a cart, the current value of a range slider, or a status message. It is form-associated and labelable, and it is an ARIA live region by default (role="status"), which means screen readers announce changes to its content automatically.

At a glance

Status	CURRENT
Versions	HTML5
Category	Forms
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	for, form, name
Related	<input>, <form>, <meter>, <progress>

Minimal example

```
<form oninput="total.value = Number(a.value) + Number(b.value)">
  <input type="number" id="a" name="a" value="0"> +
  <input type="number" id="b" name="b" value="0"> =
  <output name="total" for="a b">0</output>
</form>
```

Most common mistake

Using a for results that should be announced.

<output> — Calculation or user-action result

Category: Forms | Status: CURRENT | Versions: HTML5

Description

The <output> element is a container into which a site or app can inject the result of a calculation or the outcome of a user action, for example the total price in a cart, the current value of a range slider, or a status message. It is form-associated and labelable, and it is an ARIA live region by default (role="status"), which means screen readers announce changes to its content automatically.

Syntax

```
<output name="result" for="a b">0</output>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, listed, labelable, resettable, form-associated, palpable content
Permitted content	Phrasing content
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLOutputElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
for	space-separated ids	The elements that contributed to the calculation.	HTML5
form	form id	Associated form.	HTML5
name	text	Name of the output (not submitted with the form).	HTML5

<output>: attribute by attribute

Each attribute of <output> explained in detail, with a minimal example you can copy.

for

Values: space-separated ids | Since: HTML5

The elements that contributed to the calculation.

Write for="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<output for="space-separated ids">...</output>
```

form

Values: form id | Since: HTML5

Associated form.

Write form="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<output form="form id">...</output>
```

name

Values: text | Since: HTML5

Name of the output (not submitted with the form).

Write name="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<output name="value">...</output>
```

<output>: worked examples

Live sum of two inputs

```
<form oninput="total.value = Number(a.value) + Number(b.value)">
  <input type="number" id="a" name="a" value="0"> +
  <input type="number" id="b" name="b" value="0"> =
  <output name="total" for="a b">0</output>
</form>
```

Showing a slider's value

```
<label for="vol">Volume</label>
<input type="range" id="vol" min="0" max="100" value="50" oninput="v.
value = this.value">
<output id="v" for="vol">50</output>
```

Default browser CSS

```
output { display: inline; unicode-bidi: isolate; }
```

Accessibility

- Because it is a live region, changes are announced; do not update it dozens of times per second with noise.

Common mistakes

- Using a for results that should be announced.
- Expecting the value to be submitted.

See also

<input>, <form>, <meter>, <progress>

Quick card: <p>

Paragraph

The <p> element represents a paragraph: a block of related text, usually a group of sentences on one topic. Browsers display paragraphs as blocks separated by vertical space (a margin of 1em above and below). Paragraphs are one of the most used elements in HTML and one of the original elements from 1991, where <p> was a separator between paragraphs rather than a container.

At a glance

Status	CURRENT
Versions	HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Text content
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	align
Related	 , , , <blockquote>, <pre>

Minimal example

```
<p>HTML describes the structure of a page.</p>
<p>CSS describes how the page looks.</p>
```

Most common mistake

Block elements inside <p>.

— Paragraph

Category: Text content | Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The element represents a paragraph: a block of related text, usually a group of sentences on one topic. Browsers display paragraphs as blocks separated by vertical space (a margin of 1em above and below). Paragraphs are one of the most used elements in HTML and one of the original elements from 1991, where was a separator between paragraphs rather than a container.

A paragraph may contain only phrasing content (text, links, emphasis, images, and so on). It cannot contain block-level elements such as , <ul>, <table>, headings or another . If the browser encounters one of these inside a it automatically closes the paragraph first, which often produces layouts that look wrong for no obvious reason.

The end tag may be omitted because the browser knows a paragraph ends when the next block starts, but writing makes the code much clearer. Do not use empty elements to add space; use CSS margins.

Syntax

```
<p>Text of the paragraph.</p>
```

Technical summary

Property	Value
Void element	No
Default display	block

Property	Value
Content categories	Flow content, palpable content
Permitted content	Phrasing content
Permitted parents	Any element that accepts flow content
Tag omission	End tag may be omitted if the <p> is immediately followed by address, article, aside, blockquote, details, dialog, div, dl, fieldset, figcaption, figure, footer, form, h1-h6, header, hgroup, hr, main, menu, nav, ol, p, pre, search, section, table or ul, or if there is no more content in the parent (except when the parent is <a>, <audio>, <del>, <ins>, <map>, <noscript> or <video>)
DOM interface	HTMLParagraphElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
align	left | center | right | justify	Obsolete. Use CSS text-align.	HTML 3.2

<p>: attribute by attribute

Each attribute of <p> explained in detail, with a minimal example you can copy.

align

Values: left | center | right | justify | Since: HTML 3.2

Obsolete. Use CSS text-align.

Write align="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<p align="left">...</p>
```

<p>: worked examples

Two paragraphs

```
<p>HTML describes the structure of a page.</p>
<p>CSS describes how the page looks.</p>
```

Inline elements inside a paragraph

```
<p>I <em>really</em> love <a href="https://developer.mozilla.
org">MDN</a>, and I read it <strong>every day</strong>.</p>
```

Wrong: a list inside a paragraph

```
<!-- Wrong: the browser closes the <p> before the <ul> -->
<p>Shopping:
  <ul><li>Milk</li></ul>
</p>

<!-- Right -->
<p>Shopping:</p>
<ul><li>Milk</li></ul>
```

Typography with CSS

```
<style>
  p { line-height: 1.6; max-width: 65ch; margin: 0 0 1em; }
  p + p { text-indent: 1.5em; margin-top: -0.5em; }
</style>
```

65ch keeps lines at a comfortable reading length; text-indent gives book-style paragraphs.

Default browser CSS

```
p { display: block; margin-block: 1em; }
```

Accessibility

- Screen readers pause between paragraphs; use real paragraphs rather than

.
- Keep paragraphs reasonably short; long walls of text are hard for everyone.

Common mistakes

- Block elements inside <p>.
- Empty paragraphs for spacing.

- Using

 instead of a new paragraph.
- Using <p> for every line in an address (use <br> inside one <p>).

See also

, , , <blockquote>, <pre>

Quick card: <param>

Object parameter (deprecated)

The <param> element defined a parameter for an <object> element, passing a name/value pair to the plug-in that displayed the object (for example the autoplay setting of a Flash movie). Since plug-ins no longer exist, the element serves no purpose; the Living Standard marks it deprecated and it is retained only for compatibility. It is a void element.

At a glance

Status	DEPRECATED
Versions	HTML 3.2, HTML 4.01, HTML5; deprecated in the Living Standard
Category	Embedded content
Closing tag	None (void element)
Display	none
Own attributes	name, value, type, valuetype
Related	<object>, <embed>

Minimal example

```
<object data="movie.swf" type="application/x-shockwave-flash"
width="400" height="300">
  <param name="quality" value="high">
  <param name="wmode" value="transparent">
  <p>Flash is no longer supported.</p>
</object>
```

Most common mistake

Any use in new pages.

<param> — Object parameter (deprecated)

Category: Embedded content | Status: DEPRECATED | Versions: HTML 3.2, HTML 4.01, HTML5; deprecated in the Living Standard

Description

The <param> element defined a parameter for an <object> element, passing a name/value pair to the plug-in that displayed the object (for example the autoplay setting of a Flash movie). Since plug-ins no longer exist, the element serves no purpose; the Living Standard marks it deprecated and it is retained only for compatibility. It is a void element.

Syntax

```
<object data="movie.swf">
  <param name="quality" value="high">
</object>
```

Technical summary

Property	Value
Void element	Yes (no closing tag)
Default display	none
Content categories	None
Permitted content	None (void element)
Permitted parents	<object>, before any flow content
Tag omission	No end tag
DOM interface	HTMLParamElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
name	text	The parameter name.	HTML 3.2
value	text	The parameter value.	HTML 3.2
type	MIME type	Obsolete. Type of the value when valuetype=ref.	HTML 4.01
valuetype	data | ref | object	Obsolete. How to interpret value.	HTML 4.01

<param>: attribute by attribute

Each attribute of <param> explained in detail, with a minimal example you can copy.

name

Values: text | Since: HTML 3.2

The parameter name.

Write name="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<param name="value">
```

value

Values: text | Since: HTML 3.2

The parameter value.

Write value="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<param value="value">
```

type

Values: MIME type | Since: HTML 4.01

Obsolete. Type of the value when valuetype=ref.

Write type="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<param type="text/plain">
```

valuetype

Values: data | ref | object | Since: HTML 4.01

Obsolete. How to interpret value.

Write valuetype="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<param valuetype="data">
```

<param>: worked examples

Historical Flash embed

```
<object data="movie.swf" type="application/x-shockwave-flash"
width="400" height="300">
  <param name="quality" value="high">
  <param name="wmode" value="transparent">
  <p>Flash is no longer supported.</p>
</object>
```

Default browser CSS

```
param { display: none; }
```

Common mistakes

- Any use in new pages.

See also

<object>, <embed>

Quick card: <picture>

Picture (responsive image container)

The <picture> element contains zero or more <source> elements and exactly one <img> element, and lets the browser choose the most suitable image from several candidates. The browser examines each <source> in order and uses the first whose media query matches and whose type it supports; if none match it falls back to the <img>. The <img> element is required: it is what is actually displayed, and it carries the alt text, width, height, loading and other attributes.

At a glance

Status	CURRENT
Versions	HTML 5.1 (2016)
Category	Image and multimedia
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	None (global attributes only)
Related	<img>, <source>, <figure>

Minimal example

```
<picture>
  <source srcset="photo.avif" type="image/avif">
  <source srcset="photo.webp" type="image/webp">
  <img src="photo.jpg" alt="Sunset over the Nile" width="800"
height="500">
</picture>
```

Most common mistake

Omitting the <img>.

<picture> — Picture (responsive image container)

Category: Image and multimedia | Status: CURRENT | Versions: HTML 5.1 (2016)

Description

The <picture> element contains zero or more <source> elements and exactly one <img> element, and lets the browser choose the most suitable image from several candidates. The browser examines each <source> in order and uses the first whose media query matches and whose type it supports; if none match it falls back to the <img>. The <img> element is required: it is what is actually displayed, and it carries the alt text, width, height, loading and other attributes.

Use <picture> for three purposes: art direction (a cropped image on phones, a wide one on desktops), format selection (AVIF or WebP for modern browsers, JPEG for old ones), and dark-mode variants. For simply serving different sizes of the same image, srcset and sizes on a plain <img> are enough.

Syntax

```
<picture>
  <source srcset="..." media="..." type="...">
  <img src="..." alt="...">
</picture>
```

Technical summary

Property	Value
Void element	No
Default display	inline

Property	Value
Content categories	Flow content, phrasing content, embedded content, palpable content
Permitted content	Zero or more <source> elements, followed by one <img>, optionally intermixed with <script> and <template>
Permitted parents	Any element that accepts embedded content
Tag omission	Neither tag may be omitted
DOM interface	HTMLPictureElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<picture>: worked examples

Modern formats with fallback

```
<picture>
  <source srcset="photo.avif" type="image/avif">
  <source srcset="photo.webp" type="image/webp">
  <img src="photo.jpg" alt="Sunset over the Nile" width="800"
height="500">
</picture>
```

Browsers that support AVIF use it; others try WebP; the rest use JPEG.

Art direction

```
<picture>
  <source media="(max-width: 600px)" srcset="hero-portrait.jpg">
  <source media="(min-width: 601px)" srcset="hero-wide.jpg">
  <img src="hero-wide.jpg" alt="Our team in the office" width="1200"
height="600">
</picture>
```

A tight portrait crop on phones, the full wide picture on larger screens.

Dark mode image

```
<picture>
  <source media="(prefers-color-scheme: dark)" srcset="logo-dark.svg">
  <img src="logo-light.svg" alt="Book Store" width="120" height="40">
</picture>
```

Combining with srcset sizes

```
<picture>
  <source type="image/webp" srcset="p-400.webp 400w, p-800.webp 800w"
sizes="(max-width: 600px) 100vw, 600px">
  <img src="p-800.jpg" srcset="p-400.jpg 400w, p-800.jpg 800w"
sizes="(max-width: 600px) 100vw, 600px" alt="..." width="800"
height="533">
</picture>
```

Default browser CSS

```
picture { display: inline; }
```

Accessibility

- All accessibility comes from the <img>: alt text goes there, never on <source>.

Common mistakes

- Omitting the <img>.
- Putting <img> before the <source> elements (sources after img are ignored).
- Using src instead of srcset on <source>.
- Styling the <picture> instead of the <img> (picture has no box of its own in most cases).

See also

<img>, <source>, <figure>

Quick card: <plaintext>

Plain text (obsolete)

The <plaintext> element told the browser to treat everything after it as plain text, without interpreting any further tags, until the end of the file. It could not be closed. It was one of the 1991 elements, was deprecated in HTML 2.0 and is obsolete. Use <pre> for pre-formatted text, escaping < and & as entities, or serve the file as text/plain.

At a glance

Status	OBSOLETE
Versions	HTML 1, HTML 2.0 (deprecated); obsolete
Category	Obsolete text content
Closing tag	None (void element)
Display	block
Own attributes	None (global attributes only)
Related	<pre>, <xmp>, <listing>

Minimal example

```
<pre>&lt;p&gt;This shows the tag literally.&lt;/p&gt;</pre>
```

Most common mistake

Any use.

<plaintext> — Plain text (obsolete)

Category: Obsolete text content | Status: OBSOLETE | Versions: HTML 1, HTML 2.0 (deprecated); obsolete

Description

The <plaintext> element told the browser to treat everything after it as plain text, without interpreting any further tags, until the end of the file. It could not be closed. It was one of the 1991 elements, was deprecated in HTML 2.0 and is obsolete. Use <pre> for pre-formatted text, escaping < and & as entities, or serve the file as text/plain.

Syntax

```
<plaintext>
```

Technical summary

Property	Value
Void element	Yes (no closing tag)
Default display	block
Content categories	Historical
Permitted content	Everything after it
Permitted parents	Any
Tag omission	No end tag possible
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<plaintext>: worked examples

Replacement

```
<pre>&lt;p&gt;This shows the tag literally.&lt;/p&gt;</pre>
```

Default browser CSS

```
plaintext { display: block; font-family: monospace; white-space: pre;
}
```

Common mistakes

- Any use.

See also

<pre>, <xmp>, <listing>

Quick card: <portal>

Portal (experimental, abandoned)

The <portal> element was an experiment that embedded a preview of another page, like an iframe, with the ability to 'activate' it and navigate seamlessly into it with an animation. It was available only behind a flag in Chrome and the work has been superseded by the View Transitions API and prerendering with the Speculation Rules API. Do not use it.

At a glance

Status	EXPERIMENTAL
Versions	Chrome experiment (2019-2022); not standardised
Category	Embedded content
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	src, referrerpolicy
Related	<iframe>, <fencedframe>

Minimal example

```
<script type="speculationrules">
{ "prerender": [{ "urls": ["/next-page.html"] }] }
</script>
```

Most common mistake

Any use.

<portal> — Portal (experimental, abandoned)

Category: Embedded content | Status: EXPERIMENTAL | Versions: Chrome experiment (2019-2022); not standardised

Description

The <portal> element was an experiment that embedded a preview of another page, like an iframe, with the ability to 'activate' it and navigate seamlessly into it with an animation. It was available only behind a flag in Chrome and the work has been superseded by the View Transitions API and prerendering with the Speculation Rules API. Do not use it.

Syntax

```
<portal src="https://example.com"></portal>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Experimental
Permitted content	None
Permitted parents	Embedded content
Tag omission	Neither
DOM interface	HTMLPortalElement (Chrome only)

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
src	URL	Page to preview.	Experimental
referrerpolicy	policy	Referrer policy.	Experimental

<portal>: attribute by attribute

Each attribute of <portal> explained in detail, with a minimal example you can copy.

src

Values: URL | Since: Experimental

Page to preview.

Write src="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<portal src="https://example.com/page.html">...</portal>
```

referrerpolicy

Values: policy | Since: Experimental

Referrer policy.

Write referrerpolicy="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<portal referrerpolicy="policy">...</portal>
```

<portal>: worked examples

Modern alternative

```
<script type="speculationrules">
{ "prerender": [{ "urls": ["/next-page.html"] }] }
</script>
```

Common mistakes

- Any use.

See also

<iframe>, <fencedframe>

Quick card: <pre>

Pre-formatted text

The <pre> element represents pre-formatted text that is displayed exactly as written in the HTML file: every space, tab and line break is preserved, and a monospace (fixed-width) font is used. It is the standard way to show source code, ASCII art, poetry with meaningful spacing, email messages and terminal output.

At a glance

Status	CURRENT
Versions	HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Text content
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	width, wrap
Related	<code>, <samp>, <kbd>, <xmp>, <listing>, <textarea>

Minimal example

```
<pre><code>&lt;footer&gt;
  &lt;p&gt;&amp;copy; 2026&lt;/p&gt;
&lt;/footer&gt;</code></pre>
```

Most common mistake

Forgetting to escape < and &.

<pre> — Pre-formatted text

Category: Text content | Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <pre> element represents pre-formatted text that is displayed exactly as written in the HTML file: every space, tab and line break is preserved, and a monospace (fixed-width) font is used. It is the standard way to show source code, ASCII art, poetry with meaningful spacing, email messages and terminal output.

Markup inside <pre> is still interpreted, so to show HTML source you must escape < as < and & as &. For code, wrap the content in <code> inside the <pre>. A line break immediately after the opening <pre> tag is ignored by the parser, which is convenient for formatting.

Long lines in <pre> do not wrap by default and can overflow the page horizontally; add CSS overflow-x: auto or white-space: pre-wrap.

Syntax

```
<pre>
  text with
    preserved   spacing
</pre>
```

Technical summary

Property	Value
Void element	No
Default display	block

Property	Value
Content categories	Flow content, palpable content
Permitted content	Phrasing content
Permitted parents	Any element that accepts flow content
Tag omission	Neither tag may be omitted
DOM interface	HTMLPreElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
width	integer	Obsolete. Number of characters per line.	HTML 2.0
wrap	boolean	Non-standard. Wrap long lines. Use CSS white-space: pre-wrap.	Netscape

<pre>: attribute by attribute

Each attribute of <pre> explained in detail, with a minimal example you can copy.

width

Values: integer | Since: HTML 2.0

Obsolete. Number of characters per line.

Write width="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<pre width="3">...</pre>
```

wrap

Values: boolean | Since: Netscape

Non-standard. Wrap long lines. Use CSS white-space: pre-wrap.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<pre wrap>...</pre>
```

<pre>: worked examples

Code block

```
<pre><code>&lt;footer&gt;
  &lt;p&gt;&amp;copy; 2026&lt;/p&gt;
&lt;/footer&gt;</code></pre>
```

The entities display as the real characters.

ASCII art

```
<pre>
  /\_/\
 ( o.o )
  &gt; ^ &lt;
</pre>
```

Scrollable, styled code

```
<style>
  pre { background: #1e1e1e; color: #eee; padding: 16px; border-
radius: 8px; overflow-x: auto; tab-size: 2; }
</style>
```

Wrapping long lines

```
<pre style="white-space: pre-wrap; word-break: break-word">A very
long line ...</pre>
```

Default browser CSS

```
pre { display: block; font-family: monospace; white-space: pre;
margin: 1em 0; }
```

Accessibility

- For ASCII art or diagrams, add an explanation in text or a figcaption, because screen readers read the characters one by one.
- Use <pre> with <code> so assistive technology knows it is code.

Common mistakes

- Forgetting to escape < and &.
- Indenting the content in the source, which adds unwanted spaces to the output.

- Using <pre> for layout.

See also

<code>, <samp>, <kbd>, <xmp>, <listing>, <textarea>

Quick card: <progress>

Progress indicator

The <progress> element displays the completion progress of a task, such as a file upload, a download, a multi-step form or a loading operation. It is rendered as a progress bar. With a value attribute it shows a determinate bar (a known percentage); without value it shows an indeterminate, animated bar meaning 'working, but I do not know how long it will take'.

At a glance

Status	CURRENT
Versions	HTML5
Category	Forms
Closing tag	Required unless noted under Tag omission
Display	inline-block
Own attributes	value, max
Related	<meter>, <output>

Minimal example

```
<label for="up">Uploading photo</label>
<progress id="up" value="65" max="100">65%</progress>
```

Most common mistake

Using it for static measurements (use <meter>).

<progress> — Progress indicator

Category: Forms | Status: CURRENT | Versions: HTML5

Description

The <progress> element displays the completion progress of a task, such as a file upload, a download, a multi-step form or a loading operation. It is rendered as a progress bar. With a value attribute it shows a determinate bar (a known percentage); without value it shows an indeterminate, animated bar meaning 'working, but I do not know how long it will take'.

Use <meter> instead for a measurement that is not progress (disk space, a score).

Syntax

```
<progress value="30" max="100">30%</progress>
```

Technical summary

Property	Value
Void element	No
Default display	inline-block
Content categories	Flow content, phrasing content, labelable, palpable content
Permitted content	Phrasing content, but no <progress> descendants
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLProgressElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
value	number	How much has been completed, from 0 to max. Omit for an indeterminate bar.	HTML5
max	number	The total amount of work. Default 1.	HTML5

<progress>: attribute by attribute

Each attribute of <progress> explained in detail, with a minimal example you can copy.

value

Values: number | Since: HTML5

How much has been completed, from 0 to max. Omit for an indeterminate bar.

Write value="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<progress value="3">...</progress>
```

max

Values: number | Since: HTML5

The total amount of work. Default 1.

Write max="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<progress max="3">...</progress>
```

<progress>: worked examples

Determinate

```
<label for="up">Uploading photo</label>
<progress id="up" value="65" max="100">65%</progress>
```

Indeterminate

```
<progress>Loading...</progress>
```

Updating from JavaScript

```
<progress id="bar" max="100" value="0"></progress>
<script>
  let v = 0;
  const t = setInterval(() => {
    document.getElementById('bar').value = ++v;
    if (v === 100) clearInterval(t);
  }, 50);
</script>
```

Styling

```
<style>
  progress { width: 100%; height: 12px; accent-color: #0f8a4c; }
</style>
```

accent-color is the simplest cross-browser way to colour the bar.

Default browser CSS

```
progress { display: inline-block; appearance: auto; }
```

Accessibility

- Label the progress bar.
- Announce completion with a live region or by moving focus; the bar's value changes are not automatically spoken by all screen readers.

Common mistakes

- Using it for static measurements (use <meter>).
- Value greater than max.

See also

<meter>, <output>

Quick card: <q>

Inline quotation

The <q> element indicates a short inline quotation that sits within a sentence. Browsers automatically add quotation marks around it, choosing the correct style for the language declared with lang (curly double quotes in English, guillemets in French, and so on), so you should not type quotation marks yourself. For long quotations that need their own paragraph use <blockquote>.

At a glance

Status	CURRENT
Versions	HTML 4.01, HTML5
Category	Text-level semantics
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	cite
Related	<blockquote>, <cite>

Minimal example

```
<p>Tim Berners-Lee said <q>the Web is for everyone</q>.</p>
```

Most common mistake

Adding manual quotation marks inside <q>, giving double marks.

<q> — Inline quotation

Category: Text-level semantics | Status: CURRENT | Versions: HTML 4.01, HTML5

Description

The <q> element indicates a short inline quotation that sits within a sentence. Browsers automatically add quotation marks around it, choosing the correct style for the language declared with lang (curly double quotes in English, guillemets in French, and so on), so you should not type quotation marks yourself. For long quotations that need their own paragraph use <blockquote>.

Syntax

```
<q cite="URL">quoted words</q>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, palpable content
Permitted content	Phrasing content
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLQuoteElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
cite	URL	The source of the quotation. Not displayed.	HTML 4.01

<q>: attribute by attribute

Each attribute of <q> explained in detail, with a minimal example you can copy.

cite

Values: URL | Since: HTML 4.01

The source of the quotation. Not displayed.

Write cite="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<q cite="https://example.com/page.html">...</q>
```

<q>: worked examples

Basic quote

```
<p>Tim Berners-Lee said <q>the Web is for everyone</q>.</p>
```

Renders as: Tim Berners-Lee said “the Web is for everyone”.

Language-aware quotation marks

```
<p lang="fr">Il a dit <q>bonjour</q>.</p>
```

Renders with « bonjour ».

Custom quote characters

```
<style>
  q { quotes: '„' '“'; }
</style>
```

Default browser CSS

```
q { display: inline; }
q::before { content: open-quote; }
q::after { content: close-quote; }
```

Accessibility

- Screen readers may or may not announce the quotation; the generated quote marks are usually read.

Common mistakes

- Adding manual quotation marks inside <q>, giving double marks.
- Using <q> for irony or scare quotes.

See also

<blockquote>, <cite>

Quick card: <rb>

Ruby base (deprecated)

The <rb> element explicitly marked the base text component of a ruby annotation, the text that the <rt> annotation is placed above. The Living Standard removed it because the base text can simply be written directly inside <ruby>. Browsers still support it.

At a glance

Status	DEPRECATED
Versions	XHTML 1.1 Ruby, HTML 5.1; removed from the Living Standard
Category	Text-level semantics (ruby)
Closing tag	Required unless noted under Tag omission
Display	ruby-base
Own attributes	None (global attributes only)
Related	<ruby>, <rt>, <rp>, <rtc>

Minimal example

```
<!-- With rb -->
<ruby><rb>□</rb><rt>tō</rt><rb>□</rb><rt>kyō</rt></ruby>

<!-- Without rb -->
<ruby>□<rt>tō</rt>□<rt>kyō</rt></ruby>
```

Most common mistake

Relying on it in new markup.

<rb> — Ruby base (deprecated)

Category: Text-level semantics (ruby) | Status: DEPRECATED | Versions: XHTML 1.1 Ruby, HTML 5.1; removed from the Living Standard

Description

The <rb> element explicitly marked the base text component of a ruby annotation, the text that the <rt> annotation is placed above. The Living Standard removed it because the base text can simply be written directly inside <ruby>. Browsers still support it.

Syntax

```
<ruby><rb>□</rb><rt>kan</rt></ruby>
```

Technical summary

Property	Value
Void element	No
Default display	ruby-base
Content categories	None
Permitted content	Phrasing content
Permitted parents	<ruby>
Tag omission	End tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<rb>: worked examples

Old and new

```
<!-- With rb -->
<ruby><rb>□</rb><rt>tō</rt><rb>□</rb><rt>kyō</rt></ruby>

<!-- Without rb -->
<ruby>□<rt>tō</rt>□<rt>kyō</rt></ruby>
```

Default browser CSS

```
rb { display: ruby-base; }
```

Common mistakes

- Relying on it in new markup.

See also

<ruby>, <rt>, <rp>, <rtc>

Quick card: <rp>

Ruby fallback parenthesis

The <rp> element provides fallback parentheses for browsers that do not support ruby annotations. Browsers that support ruby hide the <rp> content; older browsers display it, so the annotation appears in brackets after the base text instead of above it. Place one <rp> before and one after each <rt>.

At a glance

Status	CURRENT
Versions	HTML5
Category	Text-level semantics (ruby)
Closing tag	Required unless noted under Tag omission
Display	none
Own attributes	None (global attributes only)
Related	<ruby>, <rt>

Minimal example

```
<ruby>□□<rp>(</rp><rt>□□□</rt><rp>)</rp></ruby>
```

Most common mistake

Omitting rp when supporting very old browsers.

<rp> — Ruby fallback parenthesis

Category: Text-level semantics (ruby) | Status: CURRENT | Versions: HTML5

Description

The <rp> element provides fallback parentheses for browsers that do not support ruby annotations. Browsers that support ruby hide the <rp> content; older browsers display it, so the annotation appears in brackets after the base text instead of above it. Place one <rp> before and one after each <rt>.

Syntax

```
<ruby>□<rp>(</rp><rt>kan</rt><rp>)</rp></ruby>
```

Technical summary

Property	Value
Void element	No
Default display	none
Content categories	None
Permitted content	Text
Permitted parents	<ruby>, immediately before or after an <rt>
Tag omission	End tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<rp>: worked examples

With fallback

```
<ruby>□□<rp>(</rp><rt>□□□</rt><rp>)</rp></ruby>
```

Modern browsers: annotation above. Old browsers: □□(□□□).

Default browser CSS

```
rp { display: none; }
```

Common mistakes

- Omitting rp when supporting very old browsers.

See also

<ruby>, <rt>

Quick card: <rt>

Ruby text (annotation)

The <rt> element specifies the ruby text component of a ruby annotation: the small text placed above (or beside) the base characters to show pronunciation, translation or transliteration. It is used for East Asian typography (furigana in Japanese, pinyin/zhuyin in Chinese) and increasingly for other languages. It must be inside a <ruby> element.

At a glance

Status	CURRENT
Versions	HTML5
Category	Text-level semantics (ruby)
Closing tag	Required unless noted under Tag omission
Display	ruby-text
Own attributes	None (global attributes only)
Related	<ruby>, <rp>, <rb>, <rtc>

Minimal example

```
<ruby>□□<rt>□□□</rt></ruby>
```

Most common mistake

Using <rt> outside <ruby>.

<rt> — Ruby text (annotation)

Category: Text-level semantics (ruby) | Status: CURRENT | Versions: HTML5

Description

The <rt> element specifies the ruby text component of a ruby annotation: the small text placed above (or beside) the base characters to show pronunciation, translation or transliteration. It is used for East Asian typography (furigana in Japanese, pinyin/zhuyin in Chinese) and increasingly for other languages. It must be inside a <ruby> element.

Syntax

```
<ruby>base<rt>annotation</rt></ruby>
```

Technical summary

Property	Value
Void element	No
Default display	ruby-text
Content categories	None
Permitted content	Phrasing content
Permitted parents	<ruby>
Tag omission	End tag may be omitted if followed by <rt> or <rp> or if there is no more content in the parent
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<rt>: worked examples

Japanese furigana

```
<ruby>□□<rt>□□□</rt></ruby>
```

Arabic word with transliteration

```
<ruby lang="ar">كتاب<rt lang="en">kitāb</rt></ruby>
```

Styling

```
<style>
  rt { font-size: 0.6em; color: #666; }
</style>
```

Default browser CSS

```
rt { display: ruby-text; font-size: 50%; }
```

Accessibility

- Screen readers generally read only the base text; use <rt> for supplementary information, not essential content.

Common mistakes

- Using <rt> outside <ruby>.

See also

<ruby>, <rp>, <rb>, <rtc>

Quick card: <rtc>

Ruby text container (deprecated)

The <rtc> element grouped several <rt> annotations so that a base text could have two layers of annotation (for example pronunciation above and meaning below). Only Firefox implemented it, and the Living Standard removed it. Nest two <ruby> elements for double-sided annotations.

At a glance

Status	DEPRECATED
Versions	HTML 5.1; removed from the Living Standard
Category	Text-level semantics (ruby)
Closing tag	Required unless noted under Tag omission
Display	ruby-text-container
Own attributes	None (global attributes only)
Related	<ruby>, <rt>, <rb>

Minimal example

```
<ruby>□□□<rtc><rt>jiù jīn shān</rt></rtc><rtc><rt>San Francisco</rt></
rtc></ruby>
```

Most common mistake

Relying on it.

<rtc> — Ruby text container (deprecated)

Category: Text-level semantics (ruby) | Status: DEPRECATED | Versions: HTML 5.1; removed from the Living Standard

Description

The <rtc> element grouped several <rt> annotations so that a base text could have two layers of annotation (for example pronunciation above and meaning below). Only Firefox implemented it, and the Living Standard removed it. Nest two <ruby> elements for double-sided annotations.

Syntax

```
<ruby>base<rtc><rt>a</rt></rtc><rtc><rt>b</rt></rtc></ruby>
```

Technical summary

Property	Value
Void element	No
Default display	ruby-text-container
Content categories	None
Permitted content	Phrasing content or <rt>
Permitted parents	<ruby>
Tag omission	End tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<rtc>: worked examples

Historical

```
<ruby>□□□<rtc><rt>jiù jīn shān</rt></rtc><rtc><rt>San Francisco</rt></
rtc></ruby>
```

Default browser CSS

```
rtc { display: ruby-text-container; }
```

Common mistakes

- Relying on it.

See also

<ruby>, <rt>, <rb>

Quick card: <ruby>

Ruby annotation

The <ruby> element represents small annotations rendered above, below or beside base text, most often used to show the pronunciation of East Asian characters. The name comes from a small typographic size called 'ruby' used by British printers. The base text is written directly inside <ruby>, each annotation in an <rt>, and optional fallback parentheses in <rp>.

At a glance

Status	CURRENT
Versions	XHTML 1.1 (2001), HTML5
Category	Text-level semantics (ruby)
Closing tag	Required unless noted under Tag omission
Display	ruby
Own attributes	None (global attributes only)
Related	<rt>, <rp>, <rb>, <rtc>

Minimal example

```
<ruby>□<rp>(</rp><rt>□□</rt><rp>)</rp>□<rp>(</rp><rt>□□□</rt><rp>)</
rp></ruby>
```

Most common mistake

Placing <rt> outside <ruby>.

<ruby> — Ruby annotation

Category: Text-level semantics (ruby) | Status: CURRENT | Versions: XHTML 1.1 (2001), HTML5

Description

The <ruby> element represents small annotations rendered above, below or beside base text, most often used to show the pronunciation of East Asian characters. The name comes from a small typographic size called 'ruby' used by British printers. The base text is written directly inside <ruby>, each annotation in an <rt>, and optional fallback parentheses in <rp>.

Syntax

```
<ruby>base<rp>(</rp><rt>annotation</rt><rp>)</rp></ruby>
```

Technical summary

Property	Value
Void element	No
Default display	ruby
Content categories	Flow content, phrasing content, palpable content
Permitted content	Phrasing content, <rt>, <rp>
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<ruby>: worked examples

Furigana over each character

```
<ruby>漢<rp>(</rp><rt>かん</rt><rp>)</rp>字<rp>(</rp><rt>じじ</rt><rp>)</
rp></ruby>
```

Whole word annotation

```
<ruby>北京<rt>Běijīng</rt></ruby>
```

Annotation below with CSS

```
<style>
  ruby { ruby-position: under; }
</style>
```

Default browser CSS

```
ruby { display: ruby; }
```

Accessibility

- Do not put essential meaning only in the annotation.

Common mistakes

- Placing <rt> outside <ruby>.
- Forgetting <rp> if old browser support is needed.

See also

<rt>, <rp>, <rb>, <rtc>

Quick card: <s>

Strikethrough (no longer accurate)

The <s> element renders text with a line through it and represents content that is no longer accurate or no longer relevant, such as an old price next to the new one, or a sold-out item. In HTML 4 it was a purely presentational strike-through synonym for <strike> and was deprecated; HTML5 gave it this meaning and made it valid again while removing <strike>.

At a glance

Status	CURRENT
Versions	HTML 3.2, HTML 4.01 (deprecated), HTML5 (redefined)
Category	Text-level semantics
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	None (global attributes only)
Related	<del>, <strike>, <u>

Minimal example

```
<p>Price: <s>150 EGP</s> <strong>99 EGP</strong></p>
```

Most common mistake

Using <s> for deletions in a revision (use <del>).

<s> — Strikethrough (no longer accurate)

Category: Text-level semantics | Status: CURRENT | Versions: HTML 3.2, HTML 4.01 (deprecated), HTML5 (redefined)

Description

The <s> element renders text with a line through it and represents content that is no longer accurate or no longer relevant, such as an old price next to the new one, or a sold-out item. In HTML 4 it was a purely presentational strike-through synonym for <strike> and was deprecated; HTML5 gave it this meaning and made it valid again while removing <strike>.

Do not use <s> to indicate document edits; that is what <del> is for.

Syntax

```
<s>outdated text</s>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, palpable content
Permitted content	Phrasing content
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted

Property	Value
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<s>: worked examples

Old price

```
<p>Price: <s>150 EGP</s> <strong>99 EGP</strong></p>
```

Sold-out event

```
<p><s>Workshop: Saturday 10 am</s> (sold out)</p>
```

Accessible old price

```
<p>Price: <s><span class="sr-only">Was </span>150 EGP</s> <span
class="sr-only">now </span>99 EGP</p>
```

Visually hidden words make the meaning clear to screen readers.

Default browser CSS

```
s { text-decoration: line-through; }
```

Accessibility

- The strike-through is not announced; add hidden text where the meaning matters.

Common mistakes

- Using <s> for deletions in a revision (use <del>).
- Using <strike>.

See also

<del>, <strike>, <u>

Quick card: <samp>

Sample output

The <samp> element marks sample or quoted output from a computer program or system: error messages, terminal output, log lines. Browsers render it in a monospace font. Nest <kbd> inside <samp> to show input echoed by the system, and <samp> inside <kbd> for input that names an on-screen item.

At a glance

Status	CURRENT
Versions	HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Text-level semantics
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	None (global attributes only)
Related	<code>, <kbd>, <pre>, <var>

Minimal example

```
<p>If the file is missing you will see <samp>404 Not Found</samp>.</p>
```

Most common mistake

Using <code> for output.

<samp> — Sample output

Category: Text-level semantics | Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <samp> element marks sample or quoted output from a computer program or system: error messages, terminal output, log lines. Browsers render it in a monospace font. Nest <kbd> inside <samp> to show input echoed by the system, and <samp> inside <kbd> for input that names an on-screen item.

Syntax

```
<samp>program output</samp>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, palpable content
Permitted content	Phrasing content
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<samp>: worked examples

Error message

```
<p>If the file is missing you will see <samp>404 Not Found</samp>.</p>
```

Terminal session

```
<pre><samp>$ <kbd>ls</kbd>
index.html  style.css
$ </samp></pre>
```

Default browser CSS

```
samp { font-family: monospace; }
```

Common mistakes

- Using <code> for output.
- Using <samp> for user input.

See also

<code>, <kbd>, <pre>, <var>

Quick card: <script>

Script

The <script> element embeds executable code, almost always JavaScript, or links to an external script file with the src attribute. It can also hold data blocks (JSON, templates, import maps, speculation rules) that the browser does not execute when type is set to a non-script MIME type.

At a glance

Status	CURRENT
Versions	HTML 3.2 (reserved), HTML 4.01, HTML5
Category	Scripting
Closing tag	Required unless noted under Tag omission
Display	none
Own attributes	src, type, defer, async, nomodule, crossorigin, integrity, referrerpolicy, fetchpriority, blocking, nonce, attributionsrc, charset, language, event
Related	<noscript>, <template>, <link>, <style>

Minimal example

```
<head>
  <script src="app.js" defer></script>
</head>
```

Most common mistake

Placing a blocking script in head without defer, so the page appears slowly.

<script> — Script

Category: Scripting | Status: CURRENT | Versions: HTML 3.2 (reserved), HTML 4.01, HTML5

Description

The <script> element embeds executable code, almost always JavaScript, or links to an external script file with the src attribute. It can also hold data blocks (JSON, templates, import maps, speculation rules) that the browser does not execute when type is set to a non-script MIME type.

By default a script blocks HTML parsing: the browser stops, downloads and runs the script, then continues. To avoid slowing down the page, put scripts at the end of <body> or, better, in <head> with the defer attribute (run after parsing, in order) or async (run as soon as downloaded, in any order). Module scripts (type="module") are deferred automatically and support import/export.

An element with src must be empty; inline code and src cannot be combined. Inside an inline script the sequence </script> ends the element even inside a string, so write it as '<\/script>' in JavaScript strings.

Syntax

```
<script src="app.js" defer></script>
<script>
  // inline code
</script>
```

Technical summary

Property	Value
Void element	No

Property	Value
Default display	none
Content categories	Metadata content, flow content, phrasing content, script-supporting element
Permitted content	Script code or data, depending on type; nothing if src is present
Permitted parents	Any element that accepts metadata or phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLScriptElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
src	URL	External script file.	HTML 4.01
type	omitted | module | importmap | speculationrules | MIME type	Omitted or text/javascript: classic script. module: ES module. importmap: JSON import map. Any other type: data block that is not executed.	HTML 4.01 / HTML5
defer	boolean	Download in parallel, execute after the document has been parsed, in document order. Only for external classic scripts.	HTML 4.01
async	boolean	Download in parallel, execute as soon as ready, possibly out of order. For independent scripts such as analytics.	HTML5

Attribute	Values	Description	Since
nomodule	boolean	Do not run in browsers that support modules; used to provide fallbacks for old browsers.	HTML5
crossorigin	anonymous | use-credentials	CORS setting; needed to get full error details from cross-origin scripts.	HTML5
integrity	hash	Subresource Integrity hash.	SRI
referrerpolicy	referrer policy	Referrer to send.	HTML5
fetchpriority	high | low | auto	Download priority hint.	Living Standard
blocking	render	Block rendering until the script runs.	Living Standard
nonce	text	Cryptographic nonce for Content Security Policy (global attribute).	CSP
attributionsrc	empty or URL	Experimental attribution reporting.	Experimental
charset	encoding	Obsolete. Encoding of the script; use UTF-8 for everything.	HTML 4.01
language	text	Obsolete. Scripting language name. Use type or omit.	HTML 3.2
event, for	text	Obsolete. Internet Explorer event binding.	HTML 4.01

<script>: attribute by attribute

Each attribute of <script> explained in detail, with a minimal example you can copy.

src

Values: URL | Since: HTML 4.01

External script file.

Write src="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<script src="https://example.com/page.html">...</script>
```

type

Values: omitted | module | importmap | speculationrules | MIME type | Since: HTML 4.01 / HTML5

Omitted or text/javascript: classic script. module: ES module. importmap: JSON import map. Any other type: data block that is not executed.

Write type="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<script type="text/plain">...</script>
```

defer

Values: boolean | Since: HTML 4.01

Download in parallel, execute after the document has been parsed, in document order. Only for external classic scripts.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<script defer>...</script>
```

async

Values: boolean | Since: HTML5

Download in parallel, execute as soon as ready, possibly out of order. For independent scripts such as analytics.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<script async>...</script>
```

nomodule

Values: boolean | Since: HTML5

Do not run in browsers that support modules; used to provide fallbacks for old browsers.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<script nomodule>...</script>
```

crossorigin

Values: anonymous | use-credentials | Since: HTML5

CORS setting; needed to get full error details from cross-origin scripts.

Write crossorigin="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<script crossorigin="anonymous">...</script>
```

integrity

Values: hash | Since: SRI

Subresource Integrity hash.

Write integrity="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<script integrity="hash">...</script>
```

referrerpolicy

Values: referrer policy | Since: HTML5

Referrer to send.

Write referrerpolicy="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<script referrerpolicy="referrer policy">...</script>
```

fetchpriority

Values: high | low | auto | Since: Living Standard

Download priority hint.

Write fetchpriority="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<script fetchpriority="high">...</script>
```

blocking

Values: render | Since: Living Standard

Block rendering until the script runs.

Write blocking="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<script blocking="render">...</script>
```

nonce

Values: text | Since: CSP

Cryptographic nonce for Content Security Policy (global attribute).

Write nonce="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<script nonce="value">...</script>
```

attributionsrc

Values: empty or URL | Since: Experimental

Experimental attribution reporting.

Write attributionsrc="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<script attributionsrc="empty">...</script>
```

charset

Values: encoding | Since: HTML 4.01

Obsolete. Encoding of the script; use UTF-8 for everything.

Write charset="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<script charset="encoding">...</script>
```

language

Values: text | Since: HTML 3.2

Obsolete. Scripting language name. Use type or omit.

Write language="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<script language="value">...</script>
```

event, for

Values: text | Since: HTML 4.01

Obsolete. Internet Explorer event binding.

Write event="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<script event="value">...</script>
```

<script>: worked examples

Recommended: deferred external script in head

```
<head>
  <script src="app.js" defer></script>
</head>
```

The script downloads while the HTML parses and runs when the DOM is ready.

Inline script

```
<script>
  document.querySelector('footer').textContent = '© ' + new Date().
getFullYear();
</script>
```

ES module

```
<script type="module">
  import { greet } from './greet.js';
  greet('world');
</script>
```

Async analytics

```
<script src="https://analytics.example.com/tag.js" async></script>
```

JSON data block

```
<script id="config" type="application/json">
  { "currency": "EGP", "vat": 14 }
</script>
<script>
  const cfg = JSON.parse(document.getElementById('config').
textContent);
</script>
```

Structured data for search engines

```
<script type="application/ld+json">
{ "@context": "https://schema.org", "@type": "Book", "name": "Learn
HTML" }
</script>
```

Import map

```
<script type="importmap">
{ "imports": { "lodash": "https://cdn.example.com/lodash.js" } }
</script>
```

HTML 4 style with comment hiding (no longer needed)

```
<script type="text/javascript">
<!--
  alert('old style');
//-->
</script>
```

The comment trick hid code from 1995 browsers that did not know <script>.

Default browser CSS

```
script { display: none; }
```

Accessibility

- Content generated by scripts must be as accessible as static content: manage focus, announce changes with live regions, keep keyboard support.

Common mistakes

- Placing a blocking script in head without defer, so the page appears slowly.
- Running DOM code before the elements exist (fix with defer or DOMContentLoaded).
- Writing <script src="x.js" /> (self-closing is not allowed; everything after it becomes script).
- Putting </script> inside a string.

See also

<noscript>, <template>, <link>, <style>

Quick card: <search>

Search section

The <search> element represents a part of the document whose contents are search or filtering controls: a site search form, a filter panel in a product list, or the controls of a find-in-page feature. It has no visual effect; it exposes the 'search' landmark to assistive technology. It replaces the old pattern <form role="search">. The form itself still goes inside it.

At a glance

Status	CURRENT
Versions	Living Standard (2023)
Category	Content sectioning
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	None (global attributes only)
Related	<form>, <input>, <nav>

Minimal example

```
<search>
  <form action="/search">
    <label for="q">Search books</label>
    <input id="q" name="q" type="search">
    <button>Search</button>
  </form>
</search>
```

Most common mistake

Using <search> for the search results (it is for the controls).

<search> — Search section

Category: Content sectioning | Status: CURRENT | Versions: Living Standard (2023)

Description

The <search> element represents a part of the document whose contents are search or filtering controls: a site search form, a filter panel in a product list, or the controls of a find-in-page feature. It has no visual effect; it exposes the 'search' landmark to assistive technology. It replaces the old pattern <form role="search">. The form itself still goes inside it.

Syntax

```
<search>
  <form>...</form>
</search>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	Flow content, palpable content
Permitted content	Flow content
Permitted parents	Any element that accepts flow content
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<search>: worked examples

Site search

```
<search>
  <form action="/search">
    <label for="q">Search books</label>
    <input id="q" name="q" type="search">
    <button>Search</button>
  </form>
</search>
```

Filter panel

```
<search aria-label="Filter products">
  <label><input type="checkbox" name="instock"> In stock only</label>
  <label>Max price <input type="range" name="max" min="0" max="500"></
label>
</search>
```

Default browser CSS

```
search { display: block; }
```

Accessibility

- Exposed as the 'search' landmark; screen reader users can jump straight to it.
- In older browsers add role="search" to the <search> element for the same effect.

Common mistakes

- Using <search> for the search results (it is for the controls).
- Nesting several search landmarks without labels.

See also

<form>, <input>, <nav>

Quick card: <section>

Generic section

The <section> element represents a generic, thematic grouping of content, typically with a heading. Examples: the chapters of an article, the tabs of a tabbed interface, the 'Introduction', 'Features' and 'Pricing' areas of a landing page. Each section should be identifiable, usually by an <h2>-<h6> heading as its first child.

At a glance

Status	CURRENT
Versions	HTML5
Category	Content sectioning
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	None (global attributes only)
Related	<article>, <aside>, <nav>, , <h1>, <main>

Minimal example

```
<main>
  <section id="features">
    <h2>Features</h2>
    <p>...</p>
  </section>
  <section id="pricing">
    <h2>Pricing</h2>
    <p>...</p>
  </section>
</main>
```

Most common mistake

Using <section> as a styling wrapper instead of .

<section> — Generic section

Category: Content sectioning | Status: CURRENT | Versions: HTML5

Description

The <section> element represents a generic, thematic grouping of content, typically with a heading. Examples: the chapters of an article, the tabs of a tabbed interface, the 'Introduction', 'Features' and 'Pricing' areas of a landing page. Each section should be identifiable, usually by an <h2>-<h6> heading as its first child.

Choosing between the sectioning elements: use <article> if the content is self-contained and could be syndicated; <nav> for navigation; <aside> for tangential content; <section> when the content is a distinct part of the page with its own heading; and when the grouping is only for styling or scripting and has no meaning. A <section> without a heading is usually a sign that is more appropriate.

Syntax

```
<section>
  <h2>Heading</h2>
  ...
</section>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	Flow content, sectioning content, palpable content

Property	Value
Permitted content	Flow content
Permitted parents	Any element that accepts flow content, but not <address>
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<section>: worked examples

Landing page sections

```
<main>
  <section id="features">
    <h2>Features</h2>
    <p>...</p>
  </section>
  <section id="pricing">
    <h2>Pricing</h2>
    <p>...</p>
  </section>
</main>
```

Sections inside an article

```
<article>
  <h1>Learn HTML</h1>
  <section>
    <h2>Part 1: Tags</h2>
    <p>...</p>
  </section>
  <section>
    <h2>Part 2: Attributes</h2>
    <p>...</p>
  </section>
</article>
```

Labelled section as a region landmark

```
<section aria-labelledby="faq-h">
  <h2 id="faq-h">FAQ</h2>
  ...
</section>
```

A section with an accessible name is exposed as a 'region' landmark.

Default browser CSS

```
section { display: block; }
```

Accessibility

- Sections become 'region' landmarks only when they have an accessible name (aria-labelledby or aria-label).
- Always include a heading.

Common mistakes

- Using <section> as a styling wrapper instead of .
- Sections without headings.
- Assuming <section> resets heading levels (it does not in practice; use the correct h-level).

See also

<article>, <aside>, <nav>, , <h1>, <main>

Quick card: <select>

Drop-down / list box

The <select> element creates a control for choosing one option (or, with multiple, several) from a list. It contains <option> elements, optionally grouped in <optgroup>. By default it appears as a drop-down menu; with the multiple attribute or a size greater than 1 it appears as a scrolling list box. The name attribute and the value of the chosen option(s) are submitted with the form.

At a glance

Status	CURRENT
Versions	HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Forms
Closing tag	Required unless noted under Tag omission
Display	inline-block
Own attributes	name, multiple, size, required, disabled, autofocus, autocomplete, form
Related	<option>, <optgroup>, <datalist>, <input>, <label>

Minimal example

```
<label for="pay">Payment</label>
<select id="pay" name="pay" required>
  <option value="">-- Select --</option>
  <option value="cod">Cash on delivery</option>
  <option value="wallet">Mobile wallet</option>
</select>
```

Most common mistake

No empty placeholder option with required, so the first real option is submitted silently.

<select> — Drop-down / list box

Category: Forms | Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <select> element creates a control for choosing one option (or, with multiple, several) from a list. It contains <option> elements, optionally grouped in <optgroup>. By default it appears as a drop-down menu; with the multiple attribute or a size greater than 1 it appears as a scrolling list box. The name attribute and the value of the chosen option(s) are submitted with the form.

A select is best for lists of roughly 5 to 30 fixed choices. For 2 to 4 choices radio buttons are easier to see at a glance; for very long lists or free text with suggestions use <input> with a <datalist>. Newer browsers allow a customisable select (CSS appearance: base-select) with rich option content.

Syntax

```
<select name="n">
  <option value="1">One</option>
</select>
```

Technical summary

Property	Value
Void element	No
Default display	inline-block
Content categories	Flow content, phrasing content, interactive content, listed, labelable, resettable, submittable, form-associated, palpable

Property	Value
Permitted content	Zero or more <option>, <optgroup>, <hr>, <script>, <template>; optionally a <button> first for customisable selects
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLSelectElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
name	text	Name submitted with the form.	HTML 2.0
multiple	boolean	Allow several options to be selected (Ctrl/Cmd-click).	HTML 2.0
size	integer	Number of visible rows. 1 (default) gives a drop-down; more gives a list box.	HTML 2.0
required	boolean	The user must choose an option with a non-empty value.	HTML5
disabled	boolean	The control cannot be used.	HTML 4.01
autofocus	boolean	Focus on load.	HTML5
autocomplete	token	Autofill hint, for example country, cc-exp-month.	HTML5
form	form id	Associated form.	HTML5

<select>: attribute by attribute

Each attribute of <select> explained in detail, with a minimal example you can copy.

name

Values: text | Since: HTML 2.0

Name submitted with the form.

Write name="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<select name="value">...</select>
```

multiple

Values: boolean | Since: HTML 2.0

Allow several options to be selected (Ctrl/Cmd-click).

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<select multiple>...</select>
```

size

Values: integer | Since: HTML 2.0

Number of visible rows. 1 (default) gives a drop-down; more gives a list box.

Write size="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<select size="3">...</select>
```

required

Values: boolean | Since: HTML5

The user must choose an option with a non-empty value.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<select required>...</select>
```

disabled

Values: boolean | Since: HTML 4.01

The control cannot be used.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<select disabled>...</select>
```

autofocus

Values: boolean | Since: HTML5

Focus on load.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<select autofocus>...</select>
```

autocomplete

Values: token | Since: HTML5

Autofill hint, for example country, cc-exp-month.

Write autocomplete="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<select autocomplete="token">...</select>
```

form

Values: form id | Since: HTML5

Associated form.

Write form="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<select form="form id">...</select>
```

<select>: worked examples

Drop-down with placeholder

```
<label for="pay">Payment</label>
<select id="pay" name="pay" required>
  <option value="">-- Select --</option>
  <option value="cod">Cash on delivery</option>
  <option value="wallet">Mobile wallet</option>
</select>
```

Multiple selection list box

```
<label for="langs">Languages you read</label>
<select id="langs" name="langs" multiple size="4">
  <option>Arabic</option>
  <option>English</option>
  <option>French</option>
  <option>German</option>
</select>
```

Submitted as langs=Arabic&langs=English.

Reading the value in JavaScript

```
<select id="s"><option value="a">A</option><option value="b">B</
option></select>
<script>
  document.getElementById('s').addEventListener('change', e =>
console.log(e.target.value));
</script>
```

Basic styling

```
<style>
  select { padding: 8px 12px; border: 1px solid #ccc; border-radius:
6px; font: inherit; }
</style>
```

Default browser CSS

```
select { display: inline-block; }
```

Accessibility

- Always label the select.
- Do not trigger navigation on change alone; keyboard users change the value with arrow keys and would be redirected before reaching their choice. Provide a Go button.

- Multiple selects are hard to use; consider a group of checkboxes.

Common mistakes

- No empty placeholder option with required, so the first real option is submitted silently.
- Using select for 2 choices (use radio buttons).
- Putting HTML inside <option>.

See also

<option>, <optgroup>, <datalist>, <input>, <label>

Quick card: <selectedcontent>

Selected option display (customisable select)

The <selectedcontent> element is part of the customisable <select> proposal. Placed inside the <button> that sits at the start of a <select>, it mirrors the content of the currently selected <option>, so that rich option content (icons, colour swatches, descriptions) is shown in the closed control as well as in the open list. The browser clones the selected option's children into <selectedcontent> whenever the selection changes.

At a glance

Status	EXPERIMENTAL
Versions	Living Standard (2025, experimental)
Category	Forms
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	None (global attributes only)
Related	<select>, <option>, <button>

Minimal example

```
<style>
  select, ::picker(select) { appearance: base-select; }
</style>
<select>
  <button><selectedcontent></selectedcontent></button>
  <option value="red"><span class="swatch" style="background:red"></
span> Red</option>
  <option value="green"><span class="swatch" style="background:
green"></span> Green</option>
</select>
```

Most common mistake

Placing it anywhere other than inside the leading <button> of a <select>.

<selectedcontent> — Selected option display (customisable select)

Category: Forms | Status: EXPERIMENTAL | Versions: Living Standard (2025, experimental)

Description

The <selectedcontent> element is part of the customisable <select> proposal. Placed inside the <button> that sits at the start of a <select>, it mirrors the content of the currently selected <option>, so that rich option content (icons, colour swatches, descriptions) is shown in the closed control as well as in the open list. The browser clones the selected option's children into <selectedcontent> whenever the selection changes.

It only has an effect when the select opts in with the CSS declaration appearance: base-select on both the select and its ::picker(select) pseudo-element. Browser support is still limited, so always test the fallback: browsers that do not understand it render the plain native select.

Syntax

```
<select>
  <button><selectedcontent></selectedcontent></button>
  <option>...</option>
</select>
```

Technical summary

Property	Value
Void element	No
Default display	inline

Property	Value
Content categories	None
Permitted content	Nothing authored; the browser fills it with a clone of the selected option's content
Permitted parents	A <button> that is the first child of a <select>
Tag omission	Neither tag may be omitted
DOM interface	HTMLSelectedContentElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<selectedcontent>: worked examples

Rich select with icons

```
<style>
  select, ::picker(select) { appearance: base-select; }
</style>
<select>
  <button><selectedcontent></selectedcontent></button>
  <option value="red"><span class="swatch" style="background:red"></
span> Red</option>
  <option value="green"><span class="swatch" style="background:
green"></span> Green</option>
</select>
```

The closed control shows the swatch and text of the chosen option.

Default browser CSS

```
selectedcontent { display: contents; }
```

Accessibility

- The control remains a combobox for assistive technology; the option text is announced as usual.

Common mistakes

- Placing it anywhere other than inside the leading <button> of a <select>.
- Relying on it without the appearance: base-select opt-in.
- Assuming support in every browser.

See also

<select>, <option>, <button>

Quick card: <shadow>

Shadow root insertion point (obsolete)

The <shadow> element was part of Shadow DOM v0 and marked where an older shadow root should be rendered inside a newer one. It was removed with Shadow DOM v1, which does not support multiple shadow roots per element. Use <slot>.

At a glance

Status	OBSOLETE
Versions	Shadow DOM v0; obsolete
Category	Obsolete web components
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	None (global attributes only)
Related	<slot>, <template>, <content>

Minimal example

```
<slot></slot>
```

Most common mistake

Any use.

<shadow> — Shadow root insertion point (obsolete)

Category: Obsolete web components | Status: OBSOLETE | Versions: Shadow DOM v0; obsolete

Description

The <shadow> element was part of Shadow DOM v0 and marked where an older shadow root should be rendered inside a newer one. It was removed with Shadow DOM v1, which does not support multiple shadow roots per element. Use <slot>.

Syntax

```
<shadow></shadow>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Historical
Permitted content	Any
Permitted parents	Shadow root
Tag omission	Neither
DOM interface	HTMLUnknownElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<shadow>: worked examples

Replacement

```
<slot></slot>
```

Common mistakes

- Any use.

See also

<slot>, <template>, <content>

Quick card: <slot>

Shadow DOM slot

The <slot> element is a placeholder inside a web component's shadow tree that is filled with content from the light DOM (the markup written by the user of the component). A named slot receives children that have a matching slot attribute; the unnamed default slot receives all other children. Content inside the <slot> element itself is fallback content shown when nothing is slotted.

At a glance

Status	CURRENT
Versions	HTML5 / DOM Standard (2016)
Category	Web components
Closing tag	Required unless noted under Tag omission
Display	contents
Own attributes	name
Related	<template>, <content>, <shadow>

Minimal example

```
<template id="card">
  <style>.card { border: 1px solid #ccc; padding: 12px; }</style>
  <div class="card">
    <h3><slot name="name">Anonymous</slot></h3>
    <p><slot>No description</slot></p>
  </div>
</template>

<user-card>
  <span slot="name">Ahmed</span>
  Front-end developer from Giza.
</user-card>
```

```
<script>
  customElements.define('user-card', class extends HTMLElement {
    constructor() {
      super();
      this.attachShadow({ mode: 'open' }).append(document.
getElementById('card').content.cloneNode(true));
    }
  });
</script>
```

Most common mistake

Using <slot> outside a shadow root (it does nothing).

<slot> — Shadow DOM slot

Category: Web components | Status: CURRENT | Versions: HTML5 / DOM Standard (2016)

Description

The <slot> element is a placeholder inside a web component's shadow tree that is filled with content from the light DOM (the markup written by the user of the component). A named slot receives children that have a matching slot attribute; the unnamed default slot receives all other children. Content inside the <slot> element itself is fallback content shown when nothing is slotted.

Syntax

```
<slot name="title">Default title</slot>
```

Technical summary

Property	Value
Void element	No
Default display	contents
Content categories	Flow content, phrasing content
Permitted content	Transparent (fallback content)
Permitted parents	Any element that accepts phrasing content (inside a shadow tree)
Tag omission	Neither tag may be omitted
DOM interface	HTMLSlotElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
name	text	The slot's name. Children with slot="name" are placed here. Omit for the default slot.	DOM

<slot>: attribute by attribute

Each attribute of <slot> explained in detail, with a minimal example you can copy.

name

Values: text | Since: DOM

The slot's name. Children with slot="name" are placed here. Omit for the default slot.

Write name="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<slot name="value">...</slot>
```

<slot>: worked examples

A user-card component

```
<template id="card">
  <style>.card { border: 1px solid #ccc; padding: 12px; }</style>
  <div class="card">
    <h3><slot name="name">Anonymous</slot></h3>
    <p><slot>No description</slot></p>
  </div>
</template>

<user-card>
  <span slot="name">Ahmed</span>
  Front-end developer from Giza.
</user-card>

<script>
  customElements.define('user-card', class extends HTMLElement {
    constructor() {
      super();
      this.attachShadow({ mode: 'open' }).append(document.
getElementById('card').content.cloneNode(true));
    }
  });
</script>
```

Styling slotted content

```
<style>
  ::slotted(span) { color: #b90000; }
</style>
```

Default browser CSS

```
slot { display: contents; }
```

Accessibility

- Slotted content keeps its own semantics; the shadow boundary is transparent to the accessibility tree.

Common mistakes

- Using <slot> outside a shadow root (it does nothing).
- Slot attribute on a nested descendant rather than a direct child of the host.

See also

<template>, <content>, <shadow>

Quick card: <small>

Side comment (fine print)

The <small> element represents side comments and small print: disclaimers, caveats, legal restrictions, copyright notices, attribution. It renders the text one size smaller. In HTML 3.2 and 4 it was purely presentational ('smaller text'); HTML5 kept it and gave it this meaning, while its counterpart <big> was removed.

At a glance

Status	CURRENT
Versions	HTML 3.2, HTML 4.01, HTML5 (redefined)
Category	Text-level semantics
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	None (global attributes only)
Related	<big>, <sub>, <sup>, <footer>

Minimal example

```
<footer>
  <p><small>&copy; 2026 Book Store. All rights reserved.</small></p>
</footer>
```

Most common mistake

Wrapping entire paragraphs or sections in <small> for font size.

<small> — Side comment (fine print)

Category: Text-level semantics | Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5 (redefined)

Description

The <small> element represents side comments and small print: disclaimers, caveats, legal restrictions, copyright notices, attribution. It renders the text one size smaller. In HTML 3.2 and 4 it was purely presentational ('smaller text'); HTML5 kept it and gave it this meaning, while its counterpart <big> was removed.

<small> does not reduce the importance of text. It is intended for short runs of inline text, not for whole sections; for that, use CSS font-size.

Syntax

```
<small>fine print</small>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, palpable content
Permitted content	Phrasing content
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted

Property	Value
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<small>: worked examples

Copyright in the footer

```
<footer>
  <p><small>&copy; 2026 Book Store. All rights reserved.</small></p>
</footer>
```

Price disclaimer

```
<p>From 99 EGP <small>(excluding delivery)</small></p>
```

Default browser CSS

```
small { font-size: smaller; }
```

Accessibility

- No special announcement; the meaning is visual and semantic only.

Common mistakes

- Wrapping entire paragraphs or sections in <small> for font size.
- Using <small> for sub-headings.

See also

<big>, <sub>, <sup>, <footer>

Quick card: <source>

Media or image source

The <source> element specifies one of several alternative resources for a <picture>, <audio> or <video> element. It is a void element. The browser examines the sources in order and uses the first one it can display: for <picture> it checks the media query and image type, for <audio>/<video> it checks the type (MIME type and codecs). Because it is used inside three different parents, the set of relevant attributes differs: <picture> uses srcset, sizes, media, type, width and height; media elements use src, type and (for video) media.

At a glance

Status	CURRENT
Versions	HTML5
Category	Image and multimedia
Closing tag	None (void element)
Display	none
Own attributes	src, srcset, sizes, type, media, width
Related	<picture>, <audio>, <video>, <img>, <track>

Minimal example

```
<video controls width="640" height="360">
  <source src="clip.webm" type="video/webm">
  <source src="clip.mp4" type="video/mp4">
  <p>Download the <a href="clip.mp4">video</a>.</p>
</video>
```

Most common mistake

Using src inside <picture> (must be srcset).

<source> — Media or image source

Category: Image and multimedia | Status: CURRENT | Versions: HTML5

Description

The <source> element specifies one of several alternative resources for a <picture>, <audio> or <video> element. It is a void element. The browser examines the sources in order and uses the first one it can display: for <picture> it checks the media query and image type, for <audio>/<video> it checks the type (MIME type and codecs). Because it is used inside three different parents, the set of relevant attributes differs: <picture> uses srcset, sizes, media, type, width and height; media elements use src, type and (for video) media.

Syntax

```
<source src="file" type="MIME">  <!-- in audio/video -->
<source srcset="file" type="MIME" media="query">  <!-- in picture -->
```

Technical summary

Property	Value
Void element	Yes (no closing tag)
Default display	none
Content categories	None
Permitted content	None (void element)
Permitted parents	<picture> (before the <img>), <audio>, <video> (before any <track> or flow content)
Tag omission	No end tag

Property	Value
DOM interface	HTMLSourceElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
src	URL	The media file. Required in <audio>/<video>; ignored in <picture>.	HTML5
srcset	candidate list	Image candidates. Required in <picture>; ignored in media elements.	HTML5
sizes	size list	Display widths for width-descriptor srcset (picture only).	HTML5
type	MIME type, optionally with codecs	The resource type, for example image/webp, video/mp4, video/webm; codecs="vp9, opus". Lets the browser skip unsupported files without downloading them.	HTML5
media	media query	Use this source only when the query matches. Valid in picture and video (audio ignores it in most browsers).	HTML5
width / height	pixels	Intrinsic size of the image candidate (picture only).	Living Standard

<source>: attribute by attribute

Each attribute of <source> explained in detail, with a minimal example you can copy.

src

Values: URL | Since: HTML5

The media file. Required in <audio>/<video>; ignored in <picture>.

Write src="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<source src="https://example.com/page.html">
```

srcset

Values: candidate list | Since: HTML5

Image candidates. Required in <picture>; ignored in media elements.

Write srcset="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<source srcset="candidate list">
```

sizes

Values: size list | Since: HTML5

Display widths for width-descriptor srcset (picture only).

Write sizes="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<source sizes="size list">
```

type

Values: MIME type, optionally with codecs | Since: HTML5

The resource type, for example image/webp, video/mp4, video/webm; codecs="vp9, opus". Lets the browser skip unsupported files without downloading them.

Write type="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<source type="text/plain">
```

media

Values: media query | Since: HTML5

Use this source only when the query matches. Valid in picture and video (audio ignores it in most browsers).

Write media="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<source media="media query">
```

width / height

Values: pixels | Since: Living Standard

Intrinsic size of the image candidate (picture only).

Write width="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<source width="3">
```

<source>: worked examples

Video with two formats

```
<video controls width="640" height="360">
  <source src="clip.webm" type="video/webm">
  <source src="clip.mp4" type="video/mp4">
  <p>Download the <a href="clip.mp4">video</a>.</p>
</video>
```

Picture with format and size choice

```
<picture>
  <source srcset="img.avif" type="image/avif">
  <source srcset="img.webp" type="image/webp">
  <img src="img.jpg" alt="..." width="800" height="600">
</picture>
```

Different video for small screens

```
<video controls>
  <source src="small.mp4" type="video/mp4" media="(max-width: 600px)">
  <source src="large.mp4" type="video/mp4">
</video>
```

Default browser CSS

```
source { display: none; }
```

Accessibility

- Accessibility attributes (alt, captions) go on the <img>, <video> or <track>, not on <source>.

Common mistakes

- Using src inside <picture> (must be srcset).
- Placing <source> after the <img> or after <track>.
- Omitting type, forcing the browser to download files to test them.

See also

<picture>, <audio>, <video>, <img>, <track>

Quick card: <spacer>

Spacer (non-standard, obsolete)

The <spacer> element inserted empty horizontal or vertical space, imitating the invisible 'spacer GIF' images used for layout in the 1990s. It existed only in Netscape and was never standardised. Use CSS margin, padding or gap.

At a glance

Status	OBSOLETE
Versions	Netscape 3-4 only
Category	Obsolete presentational
Closing tag	None (void element)
Display	none
Own attributes	type, size, width
Related	 , <hr>

Minimal example

```
<div style="margin-top: 20px">...</div>
```

Most common mistake

Any use.

<spacer> — Spacer (non-standard, obsolete)

Category: Obsolete presentational | Status: OBSOLETE | Versions: Netscape 3-4 only

Description

The <spacer> element inserted empty horizontal or vertical space, imitating the invisible 'spacer GIF' images used for layout in the 1990s. It existed only in Netscape and was never standardised. Use CSS margin, padding or gap.

Syntax

```
<spacer type="horizontal" size="20">
```

Technical summary

Property	Value
Void element	Yes (no closing tag)
Default display	none
Content categories	Historical
Permitted content	None
Permitted parents	Any
Tag omission	No end tag
DOM interface	HTMLUnknownElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
type	horizontal | vertical | block	Kind of space.	Netscape
size	pixels	Amount of space.	Netscape
width / height / align	-	For type=block.	Netscape

<spacer>: attribute by attribute

Each attribute of <spacer> explained in detail, with a minimal example you can copy.

type

Values: horizontal | vertical | block | Since: Netscape

Kind of space.

Write type="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<spacer type="horizontal">
```

size

Values: pixels | Since: Netscape

Amount of space.

Write size="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<spacer size="3">
```

width / height / align

Values: - | Since: Netscape

For type=block.

Write width="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<spacer width="-">
```

<spacer>: worked examples

CSS replacement

```
<div style="margin-top: 20px">...</div>
```

Common mistakes

- Any use.

See also

, <hr>

Quick card:

Generic inline container

The element is a generic inline container for phrasing content. Like , it has no meaning of its own and no visual effect; it exists to be a hook for CSS (via class or id) or JavaScript, or to carry attributes such as lang or dir on a part of a sentence. It should be used only when no other element is more appropriate: , , <mark>, <time>, <abbr>, <code> and the other text-level elements all carry meaning that does not.

At a glance

Status	CURRENT
Versions	HTML 4.01, HTML5
Category	Text-level semantics
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	None (global attributes only)
Related	, , , <mark>, <b>, <i>

Minimal example

```
<style>
  .price { color: #e60000; font-weight: bold; }
</style>
<p>The price is <span class="price">50 EGP</span> only.</p>
```

Most common mistake

Using where , or another semantic element fits.

— Generic inline container

Category: Text-level semantics | Status: CURRENT | Versions: HTML 4.01, HTML5

Description

The element is a generic inline container for phrasing content. Like , it has no meaning of its own and no visual effect; it exists to be a hook for CSS (via class or id) or JavaScript, or to carry attributes such as lang or dir on a part of a sentence. It should be used only when no other element is more appropriate: , , <mark>, <time>, <abbr>, <code> and the other text-level elements all carry meaning that does not.

 is inline: it does not start a new line and it takes only as much width as its content. is its block-level counterpart.

Syntax

```
<span class="name">text</span>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, palpable content
Permitted content	Phrasing content

Property	Value
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLSpanElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

: worked examples

Styling part of a sentence

```
<style>
  .price { color: #e60000; font-weight: bold; }
</style>
<p>The price is <span class="price">50 EGP</span> only.</p>
```

Only '50 EGP' turns red; the sentence stays on one line.

Marking a language change

```
<p>The Arabic word for book is <span lang="ar">كتاب</span>.</p>
```

A hook for JavaScript

```
<p>Items in cart: <span id="count">0</span></p>
<script>document.getElementById('count').textContent = 3;</script>
```

Visually hidden text for screen readers

```
<style>
  .sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
</style>
<button>×<span class="sr-only">Close</span></button>
```

Default browser CSS

```
span { display: inline; }
```

Accessibility

- A span has no role; never make it clickable without adding role="button", tabindex="0" and keyboard handlers, and even then a real <button> is better.

Common mistakes

- Using where , or another semantic element fits.
- Putting block elements inside a span.
- Using as a button.

See also

, , , <mark>, <b>, <i>

Quick card: <strike>

Strikethrough (obsolete)

The <strike> element drew a line through its text. It was purely presentational, was deprecated in HTML 4.01 and removed in HTML5. Use <del> for removed content, <s> for content that is no longer accurate, or CSS text-decoration: line-through for pure styling.

At a glance

Status	OBSOLETE
Versions	HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5
Category	Obsolete presentational
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	None (global attributes only)
Related	<s>, <del>

Minimal example

```
<!-- Old -->
<strike>150 EGP</strike>

<!-- New: no longer accurate -->
<s>150 EGP</s>

<!-- New: edit tracking -->
<del>150 EGP</del>
```

Most common mistake

Any use.

<strike> — Strikethrough (obsolete)

Category: Obsolete presentational | Status: OBSOLETE | Versions: HTML 3.2, HTML 4.01 (deprecated); obsolete in HTML5

Description

The <strike> element drew a line through its text. It was purely presentational, was deprecated in HTML 4.01 and removed in HTML5. Use <del> for removed content, <s> for content that is no longer accurate, or CSS text-decoration: line-through for pure styling.

Syntax

```
<strike>text</strike>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Historical
Permitted content	Phrasing content
Permitted parents	Phrasing content
Tag omission	Neither
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<strike>: worked examples

Replacements

```
<!-- Old -->
<strike>150 EGP</strike>

<!-- New: no longer accurate -->
<s>150 EGP</s>

<!-- New: edit tracking -->
<del>150 EGP</del>
```

Default browser CSS

```
strike { text-decoration: line-through; }
```

Common mistakes

- Any use.

See also

<s>, <del>

Quick card:

Strong importance

The element indicates that its content has strong importance, seriousness or urgency: a warning, a key instruction, the most important part of a sentence. Browsers render it in bold. Nesting inside increases the importance further.

At a glance

Status	CURRENT
Versions	HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Text-level semantics
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	None (global attributes only)
Related	<b>, , <mark>, <i>

Minimal example

```
<p><strong>Warning:</strong> unplug the device before opening it.</p>
```

Most common mistake

Using just for bold styling.

— Strong importance

Category: Text-level semantics | Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The element indicates that its content has strong importance, seriousness or urgency: a warning, a key instruction, the most important part of a sentence. Browsers render it in bold. Nesting inside increases the importance further.

In HTML 4 the guidance was 'use instead of <b>'; HTML5 refined it. = important; <b> = draw attention without importance (keywords); = spoken stress that changes meaning; <mark> = relevance to the reader's current task. A whole paragraph of text signals nothing because nothing stands out.

Syntax

```
<strong>important text</strong>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, palpable content
Permitted content	Phrasing content
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted

Property	Value
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

: worked examples

Warning

```
<p><strong>Warning:</strong> unplug the device before opening it.</p>
```

Key instruction in a list

```
<ul>
  <li>Save the file as <strong>index.html</strong>.</li>
  <li>Open it in a browser.</li>
</ul>
```

strong versus em

```
<p><strong>Do not</strong> touch the wire. I said <em>do not</em>.</p>
```

The first is a serious instruction; the second stresses the words.

Default browser CSS

```
strong { font-weight: bold; }
```

Accessibility

- Most screen readers do not announce by default, but it is the correct semantic element and some users enable emphasis announcements.

Common mistakes

- Using just for bold styling.
- Using for headings.
- Wrapping large blocks in .

See also

<b>, , <mark>, <i>

Quick card: <style>

Embedded style sheet

The <style> element contains CSS rules that apply to the document. It belongs in <head>, though browsers tolerate it in <body>. A document may have any number of <style> elements; they are applied in order together with any linked style sheets. For anything larger than a few rules, an external file loaded with <link rel="stylesheet"> is better because it can be cached and shared between pages.

At a glance

Status	CURRENT
Versions	HTML 3.2 (reserved), HTML 4.01, HTML5
Category	Document metadata
Closing tag	Required unless noted under Tag omission
Display	none
Own attributes	media, blocking, nonce, title, type, scoped
Related	<link>, <head>, <script>

Minimal example

```
<head>
  <style>
    body   { font-family: Arial, sans-serif; margin: 0; }
    footer { text-align: center; color: gray; padding: 20px; }
  </style>
</head>
```

Most common mistake

Putting CSS in <style> without the tags, or putting HTML inside <style>.

<style> — Embedded style sheet

Category: Document metadata | Status: CURRENT | Versions: HTML 3.2 (reserved), HTML 4.01, HTML5

Description

The <style> element contains CSS rules that apply to the document. It belongs in <head>, though browsers tolerate it in <body>. A document may have any number of <style> elements; they are applied in order together with any linked style sheets. For anything larger than a few rules, an external file loaded with <link rel="stylesheet"> is better because it can be cached and shared between pages.

The media attribute restricts the rules to certain devices or conditions. The content is raw text: the sequence </style> ends the element, and HTML entities are not decoded inside it.

Syntax

```
<style>
  selector { property: value; }
</style>
```

Technical summary

Property	Value
Void element	No
Default display	none
Content categories	Metadata content
Permitted content	CSS text

Property	Value
Permitted parents	<head>; also <noscript> in head; tolerated in <body>
Tag omission	Neither tag may be omitted
DOM interface	HTMLStyleElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
media	media query	Apply only when the query matches, for example print or (max-width: 600px). Default all.	HTML 4.01
blocking	render	Block rendering until the style sheet is applied (it does anyway for inline styles).	Living Standard
nonce	text	CSP nonce (global).	CSP
title	text	Name of an alternate style sheet set.	HTML 4.01
type	text/css	Obsolete. The only allowed value is text/css; omit it.	HTML 4.01
scoped	boolean	Removed. Was meant to scope styles to the parent element; use Shadow DOM or @scope.	HTML5 draft (removed)

<style>: attribute by attribute

Each attribute of <style> explained in detail, with a minimal example you can copy.

media

Values: media query | Since: HTML 4.01

Apply only when the query matches, for example print or (max-width: 600px). Default all.

Write media="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<style media="media query">...</style>
```

blocking

Values: render | Since: Living Standard

Block rendering until the style sheet is applied (it does anyway for inline styles).

Write blocking="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<style blocking="render">...</style>
```

nonce

Values: text | Since: CSP

CSP nonce (global).

Write nonce="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<style nonce="value">...</style>
```

title

Values: text | Since: HTML 4.01

Name of an alternate style sheet set.

Write title="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<style title="value">...</style>
```

type

Values: text/css | Since: HTML 4.01

Obsolete. The only allowed value is text/css; omit it.

Write type="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<style type="value">...</style>
```

scoped

Values: boolean | Since: HTML5 draft (removed)

Removed. Was meant to scope styles to the parent element; use Shadow DOM or @scope.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<style scoped>...</style>
```

<style>: worked examples

Basic page styles

```
<head>
  <style>
    body   { font-family: Arial, sans-serif; margin: 0; }
    footer { text-align: center; color: gray; padding: 20px; }
  </style>
</head>
```

Print-only rules

```
<style media="print">
  nav, footer { display: none; }
  a::after { content: ' (' attr(href) ')'; }
</style>
```

Dark mode

```
<style>
  @media (prefers-color-scheme: dark) {
    body { background: #111; color: #eee; }
  }
</style>
```

Default browser CSS

```
style { display: none; }
```

Accessibility

- Do not use CSS to hide content that screen readers need; display: none hides it from everyone.

Common mistakes

- Putting CSS in <style> without the tags, or putting HTML inside <style>.
- Typing </style> inside a CSS string.
- Writing type="text/css" (harmless but unnecessary).

See also

<link>, <head>, <script>

Quick card: <sub>

Subscript

The <sub> element renders text as a subscript: smaller and below the baseline. Use it only where the subscript has a typographic meaning, such as chemical formulas (H_2O), mathematical variable indices (x_1) or footnote markers in some styles. For purely visual lowering, use CSS vertical-align.

At a glance

Status	CURRENT
Versions	HTML 3.2, HTML 4.01, HTML5
Category	Text-level semantics
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	None (global attributes only)
Related	<sup>, <math>

Minimal example

```
<p>Water is H<sub>2</sub>O and carbon dioxide is CO<sub>2</sub>.</p>
```

Most common mistake

Using sub/sup for layout tweaks.

<sub> — Subscript

Category: Text-level semantics | Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

Description

The <sub> element renders text as a subscript: smaller and below the baseline. Use it only where the subscript has a typographic meaning, such as chemical formulas (H_2O), mathematical variable indices (x_1) or footnote markers in some styles. For purely visual lowering, use CSS vertical-align.

Syntax

```
H<sub>2</sub>0
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, palpable content
Permitted content	Phrasing content
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<sub>: worked examples

Chemistry

```
<p>Water is H<sub>2</sub>O and carbon dioxide is CO<sub>2</sub>.</p>
```

Maths

```
<p>The sequence a<sub>1</sub>, a<sub>2</sub>, ... a<sub>n</sub>.</p>
```

Default browser CSS

```
sub { vertical-align: sub; font-size: smaller; }
```

Accessibility

- Not announced; for critical meaning consider MathML.

Common mistakes

- Using sub/sup for layout tweaks.

See also

<sup>, <math>

Quick card: <summary>

Disclosure summary

The <summary> element specifies the visible heading, label or caption of a <details> element. Clicking it (or pressing Enter/Space when it is focused) toggles the details open and closed. It must be the first child of <details>. Browsers show a small triangle marker before it, which can be styled or removed with the ::marker pseudo-element or list-style: none.

At a glance

Status	CURRENT
Versions	HTML5 (5.1)
Category	Interactive elements
Closing tag	Required unless noted under Tag omission
Display	list-item
Own attributes	None (global attributes only)
Related	<details>

Minimal example

```
<details>
  <summary>What is a footer?</summary>
  <p>The bottom section of a page or section.</p>
</details>
```

Most common mistake

Placing summary anywhere but first.

<summary> — Disclosure summary

Category: Interactive elements | Status: CURRENT | Versions: HTML5 (5.1)

Description

The <summary> element specifies the visible heading, label or caption of a <details> element. Clicking it (or pressing Enter/Space when it is focused) toggles the details open and closed. It must be the first child of <details>. Browsers show a small triangle marker before it, which can be styled or removed with the ::marker pseudo-element or list-style: none.

Syntax

```
<details>
  <summary>Label</summary>
  ...
</details>
```

Technical summary

Property	Value
Void element	No
Default display	list-item
Content categories	None
Permitted content	Phrasing content, or one heading element
Permitted parents	<details>, as its first child
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<summary>: worked examples

FAQ

```
<details>
  <summary>What is a footer?</summary>
  <p>The bottom section of a page or section.</p>
</details>
```

Heading inside summary

```
<details>
  <summary><h3>Shipping</h3></summary>
  <p>2-4 days.</p>
</details>
```

Keeps the document outline; style the h3 with display: inline.

Custom marker

```
<style>
  summary { list-style: none; cursor: pointer; }
  summary::before { content: '+ '; }
  details[open] summary::before { content: '- '; }
</style>
```

Default browser CSS

```
summary { display: list-item; counter-increment: list-item 0; list-
style: disclosure-closed inside; }
details[open] > summary { list-style-type: disclosure-open; }
```

Accessibility

- Announced as a button with expanded/collapsed state.
- Do not put links or buttons inside summary; nested interactive elements confuse users.

Common mistakes

- Placing summary anywhere but first.
- Using summary outside details.

See also

<details>

Quick card: <sup>

Superscript

The <sup> element renders text as a superscript: smaller and above the baseline. Use it where the superscript has meaning: exponents (x^2), ordinal suffixes (1st), footnote references, and abbreviations like Mlle. For visual raising only, use CSS.

At a glance

Status	CURRENT
Versions	HTML 3.2, HTML 4.01, HTML5
Category	Text-level semantics
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	None (global attributes only)
Related	<sub>, <math>

Minimal example

```
<p>The area is 5<sup>2</sup> = 25 m<sup>2</sup>.</p>
```

Most common mistake

Using sup for trademark symbols where the ™ character already is superscript.

<sup> — Superscript

Category: Text-level semantics | Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

Description

The <sup> element renders text as a superscript: smaller and above the baseline. Use it where the superscript has meaning: exponents (x^2), ordinal suffixes (1st), footnote references, and abbreviations like Mlle. For visual raising only, use CSS.

Syntax

```
x<sup>2</sup>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, palpable content
Permitted content	Phrasing content
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<sup>: worked examples

Exponent

```
<p>The area is 5<sup>2</sup> = 25 m<sup>2</sup>.</p>
```

Footnote reference

```
<p>HTML was created in 1991.<sup><a href="#fn1" id="ref1">[1]</a></
sup></p>
```

Preventing line-height changes

```
<style>
  sup, sub { line-height: 0; }
</style>
```

Superscripts can push lines apart; zero line-height fixes it.

Default browser CSS

```
sup { vertical-align: super; font-size: smaller; }
```

Accessibility

- Not announced; complex maths should use MathML.

Common mistakes

- Using sup for trademark symbols where the ™ character already is superscript.

See also

<sub>, <math>

Quick card: <svg>

Scalable Vector Graphics root

The <svg> element is the root of an inline SVG (Scalable Vector Graphics) image written directly in the HTML. SVG describes shapes with elements such as <circle>, <rect>, <line>, <path>, <text> and <g>, which scale to any size without losing sharpness, can be styled with CSS and animated with CSS or JavaScript. Inline SVG is ideal for icons, logos, charts and diagrams. SVG files can also be used through <img src="x.svg">, but then CSS from the page cannot style their insides.

At a glance

Status	CURRENT
Versions	HTML5 (inline SVG)
Category	Embedded content (SVG)
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	viewBox, width, preserveAspectRatio, xmlns, fill, role
Related	<img>, <canvas>, <math>, <picture>

Minimal example

```
<svg viewBox="0 0 24 24" width="24" height="24" aria-hidden="true"
focusable="false">
  <path d="M12 2L2 7l10 5 10-5-10-5z" fill="currentColor"/>
</svg>
```

Most common mistake

Omitting viewBox so the graphic does not scale.

<svg> — Scalable Vector Graphics root

Category: Embedded content (SVG) | Status: CURRENT | Versions: HTML5 (inline SVG)

Description

The <svg> element is the root of an inline SVG (Scalable Vector Graphics) image written directly in the HTML. SVG describes shapes with elements such as <circle>, <rect>, <line>, <path>, <text> and <g>, which scale to any size without losing sharpness, can be styled with CSS and animated with CSS or JavaScript. Inline SVG is ideal for icons, logos, charts and diagrams. SVG files can also be used through <img src="x.svg">, but then CSS from the page cannot style their insides.

The viewBox attribute defines the internal coordinate system; width and height (or CSS) define the displayed size. This book documents SVG only at the level of the <svg> root; SVG has its own large specification.

Syntax

```
<svg viewBox="0 0 100 100" width="100" height="100">
  <circle cx="50" cy="50" r="40"/>
</svg>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, embedded content, palpable content

Property	Value
Permitted content	SVG elements
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither
DOM interface	SVGSVGElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
viewBox	min-x min-y width height	The internal coordinate system; makes the graphic scalable.	SVG
width / height	length	Displayed size.	SVG
preserveAspectRatio	keyword	How to fit the viewBox into the viewport.	SVG
xmlns	http://www.w3.org/2000/svg	Namespace; optional in HTML, required in standalone .svg files.	SVG
fill, stroke, stroke-width	colour / length	Presentation attributes for shapes (can also be CSS).	SVG
role, aria-label, aria-labelledby	-	Accessibility name and role for the graphic.	ARIA

<svg>: attribute by attribute

Each attribute of <svg> explained in detail, with a minimal example you can copy.

viewBox

Values: min-x min-y width height | Since: SVG

The internal coordinate system; makes the graphic scalable.

Write viewBox="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<svg viewBox="min-x min-y width height">...</svg>
```

width / height

Values: length | Since: SVG

Displayed size.

Write width="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<svg width="length">...</svg>
```

preserveAspectRatio

Values: keyword | Since: SVG

How to fit the viewBox into the viewport.

Write preserveAspectRatio="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<svg preserveAspectRatio="keyword">...</svg>
```

xmlns

Values: http://www.w3.org/2000/svg | Since: SVG

Namespace; optional in HTML, required in standalone .svg files.

Write xmlns="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<svg xmlns="http:">...</svg>
```

fill, stroke, stroke-width

Values: colour / length | Since: SVG

Presentation attributes for shapes (can also be CSS).

Write fill="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<svg fill="#336699">...</svg>
```

role, aria-label, aria-labelledby

Values: - | Since: ARIA

Accessibility name and role for the graphic.

Write role="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<svg role="-">...</svg>
```

<svg>: worked examples

Icon

```
<svg viewBox="0 0 24 24" width="24" height="24" aria-hidden="true"
focusable="false">
  <path d="M12 2L2 7l10 5 10-5-10-5z" fill="currentColor"/>
</svg>
```

currentColor makes the icon follow the text colour.

Accessible logo

```
<svg viewBox="0 0 200 60" width="200" height="60" role="img" aria-
labelledby="t">
  <title id="t">Book Store</title>
  <rect width="200" height="60" rx="8" fill="#e60000"/>
  <text x="100" y="38" text-anchor="middle" fill="#fff" font-
size="24">Book Store</text>
</svg>
```

Responsive SVG

```
<style>
  svg { width: 100%; height: auto; }
</style>
```

Default browser CSS

```
svg:not(:root) { overflow: hidden; }
```

Accessibility

- Decorative SVG: aria-hidden="true". Meaningful SVG: role="img" with <title> and aria-labelledby.
- Text in SVG <text> is real text and is readable, unlike text in raster images.

Common mistakes

- Omitting viewBox so the graphic does not scale.
- Forgetting focusable="false" for inline icons in old Internet Explorer.
- Huge inline SVGs repeated many times; use <use> or an external sprite.

See also

<img>, <canvas>, <math>, <picture>

Quick card: <table>

Table

The <table> element represents tabular data: information arranged in a two-dimensional grid of rows and columns, where the position of each cell gives it meaning (this value belongs to this row and this column). Examples: price lists, timetables, statistics, comparison charts, spreadsheets.

At a glance

Status	CURRENT
Versions	HTML 3.2, HTML 4.01, HTML5
Category	Table content
Closing tag	Required unless noted under Tag omission
Display	table
Own attributes	align, bgcolor, border, cellpadding, cellspacing, frame, rules, summary, width, height
Related	<tr>, <td>, <th>, <thead>, <tbody>, <tfoot>, <caption>, <colgroup>, <col>

Minimal example

```
<table>
  <caption>Book prices, September 2026</caption>
  <thead>
    <tr>
      <th scope="col">Title</th>
      <th scope="col">Format</th>
      <th scope="col">Price (EGP)</th>
    </tr>
  </thead>
  <tbody>
    <tr>
      <td>Learn HTML</td>
      <td>PDF</td>
      <td>120</td>
```

```
    </tr>
    <tr>
      <td>Learn CSS</td>
      <td>PDF</td>
      <td>140</td>
    </tr>
  </tbody>
  <tfoot>
    <tr>
      <th scope="row" colspan="2">Total</th>
      <td>260</td>
    </tr>
  </tfoot>
</table>
```

Most common mistake

Using tables for layout.

<table> — Table

Category: Table content | Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

Description

The <table> element represents tabular data: information arranged in a two-dimensional grid of rows and columns, where the position of each cell gives it meaning (this value belongs to this row and this column). Examples: price lists, timetables, statistics, comparison charts, spreadsheets.

A table is built row by row. <tr> creates a row; inside it <th> creates a header cell and <td> a data cell. Optional <thead>, <tbody> and <tfoot> group the rows; <caption> gives the table a title; <colgroup> and <col> describe columns. The cells of each row must add up to the same number of columns, taking colspan and rowspan into account.

Tables were introduced in HTML 3.2 and were immediately misused for page layout because there was no CSS. Layout tables are wrong today: they are inaccessible (screen readers announce rows and columns that mean nothing), not responsive, and hard to maintain. Use CSS flexbox and grid for layout; use <table> only for data.

Browsers render tables without borders by default. Add them with CSS. border-collapse: collapse merges adjacent cell borders into single lines, which is almost always what you want.

Syntax

```
<table>
  <caption>Title</caption>
  <thead><tr><th>Head</th></tr></thead>
```

```
  <tbody><tr><td>Data</td></tr></tbody>
</table>
```

Technical summary

Property	Value
Void element	No
Default display	table
Content categories	Flow content, palpable content
Permitted content	In this order: an optional <caption>, zero or more <colgroup>, an optional <thead>, either zero or more <tbody> or one or more <tr>, an optional <tfoot>; <script> and <template> may be intermixed
Permitted parents	Any element that accepts flow content
Tag omission	Neither tag may be omitted
DOM interface	HTMLTableElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
align	left | center | right	Obsolete. Alignment of the table on the page. Use CSS margin.	HTML 3.2
bgcolor	colour	Obsolete. Background colour. Use CSS background-color.	HTML 3.2
border	pixels	Obsolete. Border width around the table and cells. Use CSS border.	HTML 3.2
cellpadding	pixels	Obsolete. Space between cell content and cell border. Use CSS padding on td/th.	HTML 3.2

Attribute	Values	Description	Since
cellspacing	pixels	Obsolete. Space between cells. Use CSS border-spacing or border-collapse.	HTML 3.2
frame	void | above | below | hsides | lhs | rhs | vsides | box | border	Obsolete. Which outer borders to draw. Use CSS border.	HTML 4.01
rules	none | groups | rows | cols | all	Obsolete. Which inner borders to draw. Use CSS border on cells.	HTML 4.01
summary	text	Obsolete. Description of the table for screen readers. Use <caption> or aria-describedby.	HTML 4.01
width	pixels or percentage	Obsolete. Table width. Use CSS width.	HTML 3.2
height	pixels	Obsolete, non-standard. Use CSS.	Netscape

<table>: attribute by attribute

Each attribute of <table> explained in detail, with a minimal example you can copy.

align

Values: left | center | right | Since: HTML 3.2

Obsolete. Alignment of the table on the page. Use CSS margin.

Write align="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<table align="left">...</table>
```

bgcolor

Values: colour | Since: HTML 3.2

Obsolete. Background colour. Use CSS background-color.

Write bgcolor="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<table bgcolor="#336699">...</table>
```

border

Values: pixels | Since: HTML 3.2

Obsolete. Border width around the table and cells. Use CSS border.

Write border="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<table border="3">...</table>
```

cellpadding

Values: pixels | Since: HTML 3.2

Obsolete. Space between cell content and cell border. Use CSS padding on td/th.

Write cellpadding="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<table cellpadding="3">...</table>
```

cellspacing

Values: pixels | Since: HTML 3.2

Obsolete. Space between cells. Use CSS border-spacing or border-collapse.

Write cellspacing="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<table cellspacing="3">...</table>
```

frame

Values: void | above | below | hsides | lhs | rhs | vsides | box | border | Since: HTML 4.01

Obsolete. Which outer borders to draw. Use CSS border.

Write frame="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<table frame="void">...</table>
```

rules

Values: none | groups | rows | cols | all | Since: HTML 4.01

Obsolete. Which inner borders to draw. Use CSS border on cells.

Write rules="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<table rules="none">...</table>
```

summary

Values: text | Since: HTML 4.01

Obsolete. Description of the table for screen readers. Use <caption> or aria-describedby.

Write summary="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<table summary="value">...</table>
```

width

Values: pixels or percentage | Since: HTML 3.2

Obsolete. Table width. Use CSS width.

Write width="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<table width="3">...</table>
```

height

Values: pixels | Since: Netscape

Obsolete, non-standard. Use CSS.

Write height="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<table height="3">...</table>
```

<table>: worked examples

A complete data table

```
<table>
  <caption>Book prices, September 2026</caption>
  <thead>
    <tr>
      <th scope="col">Title</th>
      <th scope="col">Format</th>
      <th scope="col">Price (EGP)</th>
    </tr>
  </thead>
  <tbody>
    <tr>
      <td>Learn HTML</td>
      <td>PDF</td>
      <td>120</td>
    </tr>
    <tr>
      <td>Learn CSS</td>
      <td>PDF</td>
      <td>140</td>
    </tr>
  </tbody>
  <tfoot>
    <tr>
      <th scope="row" colspan="2">Total</th>
      <td>260</td>
    </tr>
  </tfoot>
</table>
```

Essential CSS for tables

```
<style>
  table { border-collapse: collapse; width: 100%; }
  th, td { border: 1px solid #ccc; padding: 8px 12px; text-align:
left; }
  th { background: #f4f4f4; }
  tbody tr:nth-child(even) { background: #fafafa; }
  tbody tr:hover { background: #fff4e0; }
  td.num { text-align: right; }
</style>
```

border-collapse removes double lines; nth-child gives zebra stripes; right-align numbers.

Row and column headers together

```
<table>
  <tr>
    <td></td>
    <th scope="col">Mon</th>
    <th scope="col">Tue</th>
  </tr>
  <tr>
    <th scope="row">Morning</th>
    <td>HTML</td>
    <td>CSS</td>
  </tr>
  <tr>
    <th scope="row">Afternoon</th>
    <td>Practice</td>
    <td>Project</td>
  </tr>
</table>
```

Spanning cells

```
<table>
  <tr>
    <th colspan="2">Name</th>
    <th rowspan="2">Age</th>
  </tr>
  <tr>
    <th>First</th>
    <th>Last</th>
  </tr>
  <tr>
    <td>Ahmed</td>
    <td>Ali</td>
    <td>20</td>
  </tr>
</table>
```

Each row still totals three columns.

Responsive: horizontal scroll on small screens

```
<div style="overflow-x: auto">
  <table>...</table>
</div>
```

HTML 3.2 style attributes and their CSS replacement

```
<!-- Old -->
<table border="1" cellpadding="5" cellspacing="0" width="100%"
bgcolor="#eeeeee">

<!-- New -->
<style>
  table { border-collapse: collapse; width: 100%; background: #eee; }
  td, th { border: 1px solid #000; padding: 5px; }
</style>
<table>
```

Default browser CSS

```
table { display: table; border-collapse: separate; border-spacing:
2px; box-sizing: border-box; text-indent: initial; }
```

Accessibility

- Use <th> with scope for every header so screen readers can announce 'Price, 120' instead of just '120'.
- Give every data table a <caption>.
- Avoid layout tables; if unavoidable, add role="presentation".
- Do not nest tables.
- For complex tables with multi-level headers, use the headers attribute on cells.

Common mistakes

- Using tables for layout.
- Rows with different numbers of cells.
- Forgetting border-collapse and getting double borders.
- Using <td> for headers.
- Placing text directly inside <table> or <tr>.

See also

<tr>, <td>, <th>, <thead>, <tbody>, <tfoot>, <caption>, <colgroup>, <col>

Quick card: <tbody>

Table body

The <tbody> element groups the main data rows of a table, as distinct from the header rows in <thead> and the summary rows in <tfoot>. A table may have several <tbody> elements to group rows into sections (for example one per category), which can then be styled separately. When you write <tr> directly inside <table> without a <tbody>, the browser creates one automatically, so a tbody is always present in the DOM.

At a glance

Status	CURRENT
Versions	HTML 4.01, HTML5
Category	Table content
Closing tag	Required unless noted under Tag omission
Display	table-row-group
Own attributes	align
Related	<table>, <thead>, <tfoot>, <tr>

Minimal example

```
<table>
  <thead><tr><th>Item</th><th>Price</th></tr></thead>
  <tbody>
    <tr><th colspan="2">Books</th></tr>
    <tr><td>Learn HTML</td><td>120</td></tr>
  </tbody>
  <tbody>
    <tr><th colspan="2">Courses</th></tr>
    <tr><td>CSS Basics</td><td>300</td></tr>
  </tbody>
</table>
```

Most common mistake

Putting tbody before thead.

<tbody> — Table body

Category: Table content | Status: CURRENT | Versions: HTML 4.01, HTML5

Description

The <tbody> element groups the main data rows of a table, as distinct from the header rows in <thead> and the summary rows in <tfoot>. A table may have several <tbody> elements to group rows into sections (for example one per category), which can then be styled separately. When you write <tr> directly inside <table> without a <tbody>, the browser creates one automatically, so a tbody is always present in the DOM.

Using explicit thead/tbody/tfoot lets browsers repeat the header on every printed page of a long table and lets CSS make the body scroll independently.

Syntax

```
<tbody>
  <tr>...</tr>
</tbody>
```

Technical summary

Property	Value
Void element	No
Default display	table-row-group
Content categories	None
Permitted content	Zero or more <tr>, <script>, <template>
Permitted parents	<table>, after <caption>, <colgroup> and <thead>

Property	Value
Tag omission	Start tag may be omitted if the first thing inside is a <tr> and it is not preceded by a tbody, thead or tfoot whose end tag was omitted; end tag may be omitted if followed by <tbody> or <tfoot> or if there is no more content in the parent
DOM interface	HTMLTableSectionElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
align, bgcolor, char, charoff, valign	various	Obsolete presentational attributes. Use CSS.	HTML 4.01

<tbody>: attribute by attribute

Each attribute of <tbody> explained in detail, with a minimal example you can copy.

align, bgcolor, char, charoff, valign

Values: various | Since: HTML 4.01

Obsolete presentational attributes. Use CSS.

Write align="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<tbody align="various">...</tbody>
```

<tbody>: worked examples

Multiple bodies for grouped rows

```
<table>
  <thead><tr><th>Item</th><th>Price</th></tr></thead>
  <tbody>
    <tr><th colspan="2">Books</th></tr>
    <tr><td>Learn HTML</td><td>120</td></tr>
  </tbody>
  <tbody>
    <tr><th colspan="2">Courses</th></tr>
    <tr><td>CSS Basics</td><td>300</td></tr>
  </tbody>
</table>
```

Scrolling body with fixed header

```
<style>
  .wrap { max-height: 300px; overflow-y: auto; }
  thead th { position: sticky; top: 0; background: #fff; }
</style>
<div class="wrap"><table>...</table></div>
```

Default browser CSS

```
tbody { display: table-row-group; vertical-align: middle; }
```

Accessibility

- No special role; it exists for structure and styling.

Common mistakes

- Putting tbody before thead.
- Placing cells directly inside tbody without tr.

See also

<table>, <thead>, <tfoot>, <tr>

Quick card: <td>

Table data cell

The <td> element defines a cell of a table that contains data. It must be inside a <tr>. Each <td> occupies one column by default; colspan makes it span several columns and rowspan several rows. The headers attribute can list the ids of the <th> cells that describe it, which is needed only for complex tables where scope is not enough.

At a glance

Status	CURRENT
Versions	HTML 3.2, HTML 4.01, HTML5
Category	Table content
Closing tag	Required unless noted under Tag omission
Display	table-cell
Own attributes	colspan, rowspan, headers, abbr, align, axis, bgcolor, char, height, nowrap, scope, valign, width
Related	<th>, <tr>, <table>

Minimal example

```
<table>
  <tr>
    <th>Name</th>
    <th>Age</th>
  </tr>
  <tr>
    <td>Ahmed</td>
    <td>20</td>
  </tr>
  <tr>
    <td>Sara</td>
    <td>22</td>
  </tr>
```

```
</table>
```

Most common mistake

Placing <td> outside <tr>.

<td> — Table data cell

Category: Table content | Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

Description

The <td> element defines a cell of a table that contains data. It must be inside a <tr>. Each <td> occupies one column by default; colspan makes it span several columns and rowspan several rows. The headers attribute can list the ids of the <th> cells that describe it, which is needed only for complex tables where scope is not enough.

Data cells are left-aligned and normal weight by default, in contrast to header cells (<th>) which are bold and centred. Use <th> for headers even if you restyle them, because the distinction is what screen readers rely on.

Syntax

```
<tr>
  <td>Data</td>
</tr>
```

Technical summary

Property	Value
Void element	No
Default display	table-cell
Content categories	Sectioning root
Permitted content	Flow content
Permitted parents	<tr>

Property	Value
Tag omission	Start tag required; end tag may be omitted if followed by <td> or <th> or if there is no more content in the parent
DOM interface	HTMLTableCellElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
colspan	positive integer	Number of columns the cell spans. Default 1, maximum 1000.	HTML 3.2
rowspan	non-negative integer	Number of rows the cell spans. Default 1; 0 means to the end of the row group. Maximum 65534.	HTML 3.2
headers	space-separated ids	The ids of <th> cells that provide headers for this cell.	HTML 4.01
abbr	text	Obsolete on td (valid on th). Abbreviated description.	HTML 4.01
align	left | center | right | justify | char	Obsolete. Use CSS text-align.	HTML 3.2
axis	text	Obsolete. Category names.	HTML 4.01
bgcolor	colour	Obsolete. Use CSS background-color.	HTML 3.2
char / charoff	character / number	Obsolete. Character alignment.	HTML 4.01
height	pixels	Obsolete. Use CSS height.	HTML 3.2
nowrap	boolean	Obsolete. Use CSS white-space: nowrap.	HTML 3.2
scope	-	Obsolete on td (use on th).	HTML 4.01

Attribute	Values	Description	Since
valign	top | middle | bottom | baseline	Obsolete. Use CSS vertical-align.	HTML 3.2
width	pixels or percentage	Obsolete. Use CSS width.	HTML 3.2

<td>: attribute by attribute

Each attribute of <td> explained in detail, with a minimal example you can copy.

colspan

Values: positive integer | Since: HTML 3.2

Number of columns the cell spans. Default 1, maximum 1000.

Write colspan="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<td colspan="3">...</td>
```

rowspan

Values: non-negative integer | Since: HTML 3.2

Number of rows the cell spans. Default 1; 0 means to the end of the row group. Maximum 65534.

Write rowspan="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<td rowspan="3">...</td>
```

headers

Values: space-separated ids | Since: HTML 4.01

The ids of <th> cells that provide headers for this cell.

Write headers="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<td headers="space-separated ids">...</td>
```

abbr

Values: text | Since: HTML 4.01

Obsolete on td (valid on th). Abbreviated description.

Write abbr="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<td abbr="value">...</td>
```

align

Values: left | center | right | justify | char | Since: HTML 3.2

Obsolete. Use CSS text-align.

Write align="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<td align="left">...</td>
```

axis

Values: text | Since: HTML 4.01

Obsolete. Category names.

Write axis="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<td axis="value">...</td>
```

bgcolor

Values: colour | Since: HTML 3.2

Obsolete. Use CSS background-color.

Write bgcolor="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<td bgcolor="#336699">...</td>
```

char / charoff

Values: character / number | Since: HTML 4.01

Obsolete. Character alignment.

Write char="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<td char="3">...</td>
```

height

Values: pixels | Since: HTML 3.2

Obsolete. Use CSS height.

Write height="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<td height="3">...</td>
```

nowrap

Values: boolean | Since: HTML 3.2

Obsolete. Use CSS white-space: nowrap.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<td nowrap>...</td>
```

scope

Values: - | Since: HTML 4.01

Obsolete on td (use on th).

Write scope="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<td scope="-">...</td>
```

valign

Values: top | middle | bottom | baseline | Since: HTML 3.2

Obsolete. Use CSS vertical-align.

Write valign="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<td valign="top">...</td>
```

width

Values: pixels or percentage | Since: HTML 3.2

Obsolete. Use CSS width.

Write width="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<td width="3">...</td>
```

<td>: worked examples

Basic cells

```
<table>
  <tr>
    <th>Name</th>
    <th>Age</th>
  </tr>
  <tr>
    <td>Ahmed</td>
    <td>20</td>
  </tr>
  <tr>
    <td>Sara</td>
    <td>22</td>
  </tr>
</table>
```

Row 1 has header cells, rows 2 and 3 have data cells.

colspan and rowspan

```
<table>
  <tr>
    <td rowspan="2">Spans two rows</td>
    <td>Row 1</td>
  </tr>
  <tr>
    <td>Row 2</td>
  </tr>
  <tr>
    <td colspan="2">Spans two columns</td>
  </tr>
</table>
```

Complex header association

```
<table>
  <tr>
    <th id="n">Name</th>
    <th id="q1">Q1</th>
    <th id="q2">Q2</th>
  </tr>
  <tr>
    <th id="r1" headers="n">Ahmed</th>
    <td headers="r1 q1">10</td>
    <td headers="r1 q2">12</td>
  </tr>
</table>
```

Cell styling

```
<style>
  td { padding: 8px 12px; border-bottom: 1px solid #e0e0e0; vertical-
align: top; }
  td.num { text-align: right; font-variant-numeric: tabular-nums; }
</style>
```

Default browser CSS

```
td { display: table-cell; vertical-align: inherit; padding: 1px; }
```

Accessibility

- Do not leave header cells as <td>.
- Empty cells are fine; do not fill them with   unless needed for old-browser borders.

Common mistakes

- Placing <td> outside <tr>.
- Inconsistent column counts.
- Using td for headers.

See also

<th>, <tr>, <table>

Quick card: <template>

Content template

The <template> element holds HTML that is not rendered when the page loads but can be cloned and inserted into the document later by JavaScript. The content is parsed into a separate document fragment (template.content): scripts inside do not run, images do not load and the markup is invisible. It is the standard way to define reusable markup for lists, cards and web components.

At a glance

Status	CURRENT
Versions	HTML5 (2013)
Category	Scripting / web components
Closing tag	Required unless noted under Tag omission
Display	none
Own attributes	shadowrootmode, shadowrootdelegatesfocus, shadowrootclonable, shadowrootserializable
Related	<slot>, <script>, <noscript>

Minimal example

```
<table id="cart"><tbody></tbody></table>
<template id="row">
  <tr><td class="name"></td><td class="price"></td></tr>
</template>
<script>
  const items = [['Learn HTML', 120], ['Learn CSS', 140]];
  const tpl = document.getElementById('row');
  const body = document.querySelector('#cart tbody');
  for (const [name, price] of items) {
    const clone = tpl.content.cloneNode(true);
    clone.querySelector('.name').textContent = name;
    clone.querySelector('.price').textContent = price;
```

```
    body.append(clone);
  }
</script>
```

Most common mistake

Using innerHTML on template instead of template.content.

<template> — Content template

Category: Scripting / web components | Status: CURRENT | Versions: HTML5 (2013)

Description

The <template> element holds HTML that is not rendered when the page loads but can be cloned and inserted into the document later by JavaScript. The content is parsed into a separate document fragment (template.content): scripts inside do not run, images do not load and the markup is invisible. It is the standard way to define reusable markup for lists, cards and web components.

Declarative Shadow DOM uses <template shadowrootmode="open"> inside a custom element to create a shadow root without JavaScript.

Syntax

```
<template id="t">
  <li class="item"></li>
</template>
```

Technical summary

Property	Value
Void element	No
Default display	none
Content categories	Metadata content, flow content, phrasing content, script-supporting element
Permitted content	Anything (stored in a DocumentFragment, not rendered)

Property	Value
Permitted parents	Almost anywhere: head, body, and inside table, colgroup, dl, ol, ul, select...
Tag omission	Neither tag may be omitted
DOM interface	HTMLTemplateElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
shadowrootmode	open | closed	Creates a declarative shadow root on the parent element.	Living Standard
shadowrootdelegatesfocus	boolean	Sets delegatesFocus on the declarative shadow root.	Living Standard
shadowrootclonable	boolean	Sets clonable on the declarative shadow root.	Living Standard
shadowrootserializable	boolean	Sets serializable on the declarative shadow root.	Living Standard

<template>: attribute by attribute

Each attribute of <template> explained in detail, with a minimal example you can copy.

shadowrootmode

Values: open | closed | Since: Living Standard

Creates a declarative shadow root on the parent element.

Write shadowrootmode="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<template shadowrootmode="open">...</template>
```

shadowrootdelegatesfocus

Values: boolean | Since: Living Standard

Sets delegatesFocus on the declarative shadow root.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<template shadowrootdelegatesfocus>...</template>
```

shadowrootclonable

Values: boolean | Since: Living Standard

Sets clonable on the declarative shadow root.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<template shadowrootclonable>...</template>
```

shadowrootserializable

Values: boolean | Since: Living Standard

Sets serializable on the declarative shadow root.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<template shadowrootserializable>...</template>
```

<template>: worked examples

Cloning a row template

```
<table id="cart"><tbody></tbody></table>
<template id="row">
  <tr><td class="name"></td><td class="price"></td></tr>
</template>
<script>
  const items = [['Learn HTML', 120], ['Learn CSS', 140]];
  const tpl = document.getElementById('row');
  const body = document.querySelector('#cart tbody');
  for (const [name, price] of items) {
    const clone = tpl.content.cloneNode(true);
    clone.querySelector('.name').textContent = name;
    clone.querySelector('.price').textContent = price;
    body.append(clone);
  }
</script>
```

Declarative shadow DOM

```
<my-card>
  <template shadowrootmode="open">
    <style>p { color: #b90000; }</style>
    <p><slot></slot></p>
  </template>
  Hello from the light DOM
</my-card>
```

Default browser CSS

```
template { display: none; }
```

Accessibility

- Template content is not in the accessibility tree until inserted.

Common mistakes

- Using innerHTML on template instead of template.content.
- Expecting scripts inside the template to run before insertion.

See also

<slot>, <script>, <noscript>

Quick card: <textarea>

Multi-line text input

The <textarea> element creates a multi-line plain-text editing control, for comments, messages, addresses and any free-form text. Unlike <input>, it is not a void element: its initial value is the text between its tags, not a value attribute. Whitespace and line breaks inside the tags are preserved, so keep the closing tag right after the text to avoid unwanted spaces.

At a glance

Status	CURRENT
Versions	HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Forms
Closing tag	Required unless noted under Tag omission
Display	inline-block
Own attributes	name, rows, cols, placeholder, required, disabled, readonly, maxlength, minlength, wrap, autocomplete, autofocus, spellcheck, dirname, form
Related	<input>, <form>, <label>, <output>

Minimal example

```
<label for="msg">Message</label>
<textarea id="msg" name="message" rows="5" placeholder="Write your
message..." required maxlength="500"></textarea>
```

Most common mistake

Writing <textarea value="..."> (value is not an attribute here).

<textarea> — Multi-line text input

Category: Forms | Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <textarea> element creates a multi-line plain-text editing control, for comments, messages, addresses and any free-form text. Unlike <input>, it is not a void element: its initial value is the text between its tags, not a value attribute. Whitespace and line breaks inside the tags are preserved, so keep the closing tag right after the text to avoid unwanted spaces.

The rows and cols attributes set its visible size in lines and characters; CSS width/height are more flexible. Most browsers let the user drag-resize it; control this with the CSS resize property. The field-sizing: content CSS property (new) makes it grow with its content.

Syntax

```
<textarea name="n" rows="4" cols="40">initial text</textarea>
```

Technical summary

Property	Value
Void element	No
Default display	inline-block
Content categories	Flow content, phrasing content, interactive content, listed, labelable, resettable, submittable, form-associated, palpable
Permitted content	Text

Property	Value
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLTextAreaElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
name	text	Name submitted with the form.	HTML 2.0
rows	positive integer	Visible number of lines. Default 2.	HTML 2.0
cols	positive integer	Visible width in average characters. Default 20.	HTML 2.0
placeholder	text	Hint shown when empty. Not a label.	HTML5
required	boolean	Must not be empty.	HTML5
disabled	boolean	Cannot be used or submitted.	HTML 4.01
readonly	boolean	Cannot be edited; is submitted.	HTML 4.01
maxlength	integer	Maximum characters.	HTML5
minlength	integer	Minimum characters.	HTML5
wrap	soft | hard | off	soft (default): lines wrap visually but newlines are not submitted. hard: newlines are inserted at wrap points when submitting (requires cols). off: no wrapping (non-standard).	HTML5
autocomplete	on | off | token	Autofill hint (street-address, etc.).	HTML5

Attribute	Values	Description	Since
autofocus	boolean	Focus on load.	HTML5
spellcheck	true | false	Enable or disable spell checking (global).	HTML5
dirname	text	Submit text direction.	HTML5
form	form id	Associated form.	HTML5

<textarea>: attribute by attribute

Each attribute of <textarea> explained in detail, with a minimal example you can copy.

name

Values: text | Since: HTML 2.0

Name submitted with the form.

Write name="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<textarea name="value">...</textarea>
```

rows

Values: positive integer | Since: HTML 2.0

Visible number of lines. Default 2.

Write rows="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<textarea rows="3">...</textarea>
```

cols

Values: positive integer | Since: HTML 2.0

Visible width in average characters. Default 20.

Write cols="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<textarea cols="3">...</textarea>
```

placeholder

Values: text | Since: HTML5

Hint shown when empty. Not a label.

Write placeholder="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<textarea placeholder="value">...</textarea>
```

required

Values: boolean | Since: HTML5

Must not be empty.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<textarea required>...</textarea>
```

disabled

Values: boolean | Since: HTML 4.01

Cannot be used or submitted.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<textarea disabled>...</textarea>
```

readonly

Values: boolean | Since: HTML 4.01

Cannot be edited; is submitted.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<textarea readonly>...</textarea>
```

maxlength

Values: integer | Since: HTML5

Maximum characters.

Write maxlength="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<textarea maxlength="3">...</textarea>
```

minlength

Values: integer | Since: HTML5

Minimum characters.

Write minlength="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<textarea minlength="3">...</textarea>
```

wrap

Values: soft | hard | off | Since: HTML5

soft (default): lines wrap visually but newlines are not submitted. hard: newlines are inserted at wrap points when submitting (requires cols). off: no wrapping (non-standard).

Write wrap="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<textarea wrap="soft">...</textarea>
```

autocomplete

Values: on | off | token | Since: HTML5

Autofill hint (street-address, etc.).

Write autocomplete="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<textarea autocomplete="on">...</textarea>
```

autofocus

Values: boolean | Since: HTML5

Focus on load.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<textarea autofocus>...</textarea>
```

spellcheck

Values: true | false | Since: HTML5

Enable or disable spell checking (global).

Write spellcheck="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<textarea spellcheck="true">...</textarea>
```

dirname

Values: text | Since: HTML5

Submit text direction.

Write dirname="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<textarea dirname="value">...</textarea>
```

form

Values: form id | Since: HTML5

Associated form.

Write form="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<textarea form="form id">...</textarea>
```

<textarea>: worked examples

Message field

```
<label for="msg">Message</label>
<textarea id="msg" name="message" rows="5" placeholder="Write your
message..." required maxlength="500"></textarea>
```

With initial text

```
<textarea name="bio">Write a short bio here.</textarea>
```

Styling and resize control

```
<style>
  textarea { width: 100%; min-height: 120px; padding: 8px; font:
inherit; resize: vertical; box-sizing: border-box; }
</style>
```

Character counter

```
<textarea id="t" maxlength="200"></textarea>
<output id="c" for="t">0 / 200</output>
<script>
  t.addEventListener('input', () => c.value = t.value.length + ' /
200');
</script>
```

Default browser CSS

```
textarea { display: inline-block; white-space: pre-wrap; resize: both;
 }
```

Accessibility

- Label it.
- Do not remove the resize handle without good reason.
- Announce character limits in the label or description.

Common mistakes

- Writing <textarea value="..."> (value is not an attribute here).
- Indenting the content and getting leading spaces.
- Forgetting the closing tag; everything after becomes part of the textarea.

See also

<input>, <form>, <label>, <output>

Quick card: <tfoot>

Table footer

The <tfoot> element groups the rows that summarise the columns of a table: totals, averages, counts. In HTML5 it is placed after the <tbody> elements (HTML 4.01 required it before them so that the browser could render the footer before receiving all data). When printing a long table, browsers can repeat the tfoot at the bottom of every page.

At a glance

Status	CURRENT
Versions	HTML 4.01, HTML5
Category	Table content
Closing tag	Required unless noted under Tag omission
Display	table-footer-group
Own attributes	align
Related	<table>, <thead>, <tbody>

Minimal example

```
<table>
  <thead><tr><th>Item</th><th>Price</th></tr></thead>
  <tbody>
    <tr><td>Book</td><td>120</td></tr>
    <tr><td>Pen</td><td>10</td></tr>
  </tbody>
  <tfoot>
    <tr><th scope="row">Total</th><td>130</td></tr>
  </tfoot>
</table>
```

Most common mistake

Placing tfoot in the middle of the table.

<tfoot> — Table footer

Category: Table content | Status: CURRENT | Versions: HTML 4.01, HTML5

Description

The <tfoot> element groups the rows that summarise the columns of a table: totals, averages, counts. In HTML5 it is placed after the <tbody> elements (HTML 4.01 required it before them so that the browser could render the footer before receiving all data). When printing a long table, browsers can repeat the tfoot at the bottom of every page.

Syntax

```
<tfoot>
  <tr><th>Total</th><td>260</td></tr>
</tfoot>
```

Technical summary

Property	Value
Void element	No
Default display	table-footer-group
Content categories	None
Permitted content	Zero or more <tr>, <script>, <template>
Permitted parents	<table>, after caption, colgroup, thead and tbody
Tag omission	End tag may be omitted if there is no more content in the parent
DOM interface	HTMLTableSectionElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
align, bgcolor, char, charoff, valign	various	Obsolete presentational attributes. Use CSS.	HTML 4.01

<tfoot>: attribute by attribute

Each attribute of <tfoot> explained in detail, with a minimal example you can copy.

align, bgcolor, char, charoff, valign

Values: various | Since: HTML 4.01

Obsolete presentational attributes. Use CSS.

Write align="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<tfoot align="various">...</tfoot>
```

<tfoot>: worked examples

Totals row

```
<table>
  <thead><tr><th>Item</th><th>Price</th></tr></thead>
  <tbody>
    <tr><td>Book</td><td>120</td></tr>
    <tr><td>Pen</td><td>10</td></tr>
  </tbody>
  <tfoot>
    <tr><th scope="row">Total</th><td>130</td></tr>
  </tfoot>
</table>
```

Styling

```
<style>
  tfoot { font-weight: bold; background: #f4f4f4; border-top: 2px
solid #333; }
</style>
```

Default browser CSS

```
tfoot { display: table-footer-group; vertical-align: middle; }
```

Accessibility

- No special role, but grouping totals in tfoot helps users understand the table structure.

Common mistakes

- Placing tfoot in the middle of the table.
- Multiple tfoot elements.

See also

<table>, <thead>, <tbody>

Quick card: <th>

Table header cell

The <th> element defines a header cell in a table: a cell that labels a column or a row rather than holding data. Browsers render it bold and centred. The scope attribute states whether the header applies to its column (col), its row (row), a group of columns (colgroup) or a group of rows (rowgroup). Browsers can usually guess for simple tables, but stating it explicitly is best practice because screen readers use the header text when reading each data cell.

At a glance

Status	CURRENT
Versions	HTML 3.2, HTML 4.01, HTML5
Category	Table content
Closing tag	Required unless noted under Tag omission
Display	table-cell
Own attributes	scope, colspan, rowspan, headers, abbr, align
Related	<td>, <tr>, <table>, <thead>

Minimal example

```
<table>
  <tr>
    <th scope="col">Product</th>
    <th scope="col">Price</th>
  </tr>
  <tr>
    <th scope="row">Notebook</th>
    <td>25</td>
  </tr>
</table>
```

Most common mistake

Using <td> with bold styling instead of <th>.

<th> — Table header cell

Category: Table content | Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

Description

The <th> element defines a header cell in a table: a cell that labels a column or a row rather than holding data. Browsers render it bold and centred. The scope attribute states whether the header applies to its column (col), its row (row), a group of columns (colgroup) or a group of rows (rowgroup). Browsers can usually guess for simple tables, but stating it explicitly is best practice because screen readers use the header text when reading each data cell.

Syntax

```
<th scope="col">Header</th>
```

Technical summary

Property	Value
Void element	No
Default display	table-cell
Content categories	None
Permitted content	Flow content, but no header, footer, sectioning content or heading content
Permitted parents	<tr>
Tag omission	End tag may be omitted if followed by <td> or <th> or if there is no more content in the parent
DOM interface	HTMLTableCellElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
scope	row | col | rowgroup | colgroup	Which cells this header describes.	HTML 4.01
colspan	positive integer	Columns spanned.	HTML 3.2
rowspan	non-negative integer	Rows spanned.	HTML 3.2
headers	space-separated ids	Other header cells that apply to this one (for multi-level headers).	HTML 4.01
abbr	text	A short alternative label that screen readers may use when reading the header repeatedly.	HTML 4.01
align, axis, bgcolor, char, charoff, height, nowrap, valign, width	various	Obsolete presentational attributes. Use CSS.	HTML 3.2 / 4.01

<th>: attribute by attribute

Each attribute of <th> explained in detail, with a minimal example you can copy.

scope

Values: row | col | rowgroup | colgroup | Since: HTML 4.01

Which cells this header describes.

Write scope="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<th scope="row">...</th>
```

colspan

Values: positive integer | Since: HTML 3.2

Columns spanned.

Write colspan="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<th colspan="3">...</th>
```

rowspan

Values: non-negative integer | Since: HTML 3.2

Rows spanned.

Write rowspan="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<th rowspan="3">...</th>
```

headers

Values: space-separated ids | Since: HTML 4.01

Other header cells that apply to this one (for multi-level headers).

Write headers="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<th headers="space-separated ids">...</th>
```

abbr

Values: text | Since: HTML 4.01

A short alternative label that screen readers may use when reading the header repeatedly.

Write abbr="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<th abbr="value">...</th>
```

align, axis, bgcolor, char, charoff, height, nowrap, valign, width

Values: various | Since: HTML 3.2 / 4.01

Obsolete presentational attributes. Use CSS.

Write align="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<th align="various">...</th>
```

<th>: worked examples

Column and row headers

```
<table>
  <tr>
    <th scope="col">Product</th>
    <th scope="col">Price</th>
  </tr>
  <tr>
    <th scope="row">Notebook</th>
    <td>25</td>
  </tr>
</table>
```

A screen reader on the '25' cell announces: 'Notebook, Price, 25'.

Group headers

```
<table>
  <tr>
    <th scope="colgroup" colspan="2">2025</th>
    <th scope="colgroup" colspan="2">2026</th>
  </tr>
  <tr>
    <th scope="col">Q1</th><th scope="col">Q2</th>
    <th scope="col">Q1</th><th scope="col">Q2</th>
  </tr>
</table>
```

Left-aligned headers

```
<style>
  th { text-align: left; background: #f4f4f4; }
  th[scope="row"] { font-weight: 600; }
</style>
```

Default browser CSS

```
th { display: table-cell; vertical-align: inherit; font-weight: bold;
text-align: center; padding: 1px; }
```

Accessibility

- Always use <th> for headers and set scope.
- Use abbr for long headers that will be repeated often.

Common mistakes

- Using <td> with bold styling instead of <th>.

- Omitting scope in tables with both row and column headers.

See also

<td>, <tr>, <table>, <thead>

Quick card: <thead>

Table header

The <thead> element groups the rows that hold the column headers of a table. It comes after any <caption> and <colgroup> and before <tbody> and <tfoot>. Browsers repeat the thead at the top of each printed page of a long table, and CSS position: sticky on its cells keeps the headers visible while scrolling. A table may have at most one thead.

At a glance

Status	CURRENT
Versions	HTML 4.01, HTML5
Category	Table content
Closing tag	Required unless noted under Tag omission
Display	table-header-group
Own attributes	align
Related	<table>, <tbody>, <tfoot>, <th>

Minimal example

```
<table>
  <thead>
    <tr>
      <th scope="col">Name</th>
      <th scope="col">Email</th>
    </tr>
  </thead>
  <tbody>
    <tr><td>Ahmed</td><td>ahmed@example.com</td></tr>
  </tbody>
</table>
```

Most common mistake

Two thead elements.

<thead> — Table header

Category: Table content | Status: CURRENT | Versions: HTML 4.01, HTML5

Description

The <thead> element groups the rows that hold the column headers of a table. It comes after any <caption> and <colgroup> and before <tbody> and <tfoot>. Browsers repeat the thead at the top of each printed page of a long table, and CSS position: sticky on its cells keeps the headers visible while scrolling. A table may have at most one thead.

Syntax

```
<thead>
  <tr><th>Column</th></tr>
</thead>
```

Technical summary

Property	Value
Void element	No
Default display	table-header-group
Content categories	None
Permitted content	Zero or more <tr>, <script>, <template>
Permitted parents	<table>, after caption and colgroup, before tbody, tfoot and tr
Tag omission	End tag may be omitted if followed by <tbody> or <tfoot>
DOM interface	HTMLTableSectionElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
align, bgcolor, char, charoff, valign	various	Obsolete presentational attributes. Use CSS.	HTML 4.01

<thead>: attribute by attribute

Each attribute of <thead> explained in detail, with a minimal example you can copy.

align, bgcolor, char, charoff, valign

Values: various | Since: HTML 4.01

Obsolete presentational attributes. Use CSS.

Write align="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<thead align="various">...</thead>
```

<thead>: worked examples

Header group

```
<table>
  <thead>
    <tr>
      <th scope="col">Name</th>
      <th scope="col">Email</th>
    </tr>
  </thead>
  <tbody>
    <tr><td>Ahmed</td><td>ahmed@example.com</td></tr>
  </tbody>
</table>
```

Sticky header

```
<style>
  thead th { position: sticky; top: 0; background: #fff; box-shadow:
0 1px 0 #ccc; }
</style>
```

Default browser CSS

```
thead { display: table-header-group; vertical-align: middle; }
```

Accessibility

- Helps assistive technology identify header rows; combine with th scope="col".

Common mistakes

- Two thead elements.
- Putting data rows in thead.

See also

<table>, <tbody>, <tfoot>, <th>

Quick card: <time>

Date / time

The <time> element represents a specific period in time: a date, a time of day, a date and time, a duration, a week or a month. The optional datetime attribute holds the value in a machine-readable format so that browsers, search engines, calendars and scripts can understand it, while the visible content can be written in any human-friendly way ('11 September 2026', 'yesterday', '□□ □□□□□□'). If datetime is omitted, the text content itself must be in a valid format.

At a glance

Status	CURRENT
Versions	HTML5
Category	Text-level semantics
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	datetime
Related	<data>, <article>

Minimal example

```
<p>Published <time datetime="2026-09-11">11 September 2026</time></p>
```

Most common mistake

Invalid datetime formats such as 11/09/2026.

<time> — Date / time

Category: Text-level semantics | Status: CURRENT | Versions: HTML5

Description

The <time> element represents a specific period in time: a date, a time of day, a date and time, a duration, a week or a month. The optional datetime attribute holds the value in a machine-readable format so that browsers, search engines, calendars and scripts can understand it, while the visible content can be written in any human-friendly way ('11 September 2026', 'yesterday', '□□ □□□□□□'). If datetime is omitted, the text content itself must be in a valid format.

Syntax

```
<time datetime="2026-09-11">11 September 2026</time>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, palpable content
Permitted content	Phrasing content
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLTimeElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
datetime	date/time string	Machine-readable value. Formats: 2026-09-11 (date); 14:30 or 14:30:00 (time); 2026-09-11T14:30 (local date-time); 2026-09-11T14:30Z or 2026-09-11T14:30+02:00 (with time zone); 2026-09 (month); 2026-W37 (week); 2026 (year); 09-11 (yearless date); PT2H30M or 2h 30m (duration).	HTML5

<time>: attribute by attribute

Each attribute of <time> explained in detail, with a minimal example you can copy.

datetime

Values: date/time string | Since: HTML5

Machine-readable value. Formats: 2026-09-11 (date); 14:30 or 14:30:00 (time); 2026-09-11T14:30 (local date-time); 2026-09-11T14:30Z or 2026-09-11T14:30+02:00 (with time zone); 2026-09 (month); 2026-W37 (week); 2026 (year); 09-11 (yearless date); PT2H30M or 2h 30m (duration).

Write datetime="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<time datetime="date">...</time>
```

<time>: worked examples

Publication date

```
<p>Published <time datetime="2026-09-11">11 September 2026</time></p>
```

Event with time zone

```
<p>The webinar starts at <time datetime="2026-10-01T19:00+02:00">7 pm
Cairo time on 1 October</time>.</p>
```

Duration

```
<p>Reading time: <time datetime="PT8M">8 minutes</time></p>
```

Relative text with exact value

```
<p>Posted <time datetime="2026-09-10T09:15Z" title="10 Sep 2026, 09:
15 UTC">yesterday</time></p>
```

Default browser CSS

```
time { display: inline; }
```

Accessibility

- Screen readers read the visible text, not datetime; keep the visible text understandable.

Common mistakes

- Invalid datetime formats such as 11/09/2026.
- Using <time> for vague periods ('the Middle Ages').

See also

<data>, <article>

Quick card: <title>

Document title

The <title> element defines the title of the document, shown in the browser's title bar or tab, used as the default name for bookmarks, displayed as the clickable headline in search engine results, and announced first by screen readers when the page loads. It contains text only; any tags inside are treated as literal text. Every document must have exactly one <title>, inside <head>.

At a glance

Status	CURRENT
Versions	HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Document metadata
Closing tag	Required unless noted under Tag omission
Display	none
Own attributes	None (global attributes only)
Related	<head>, <meta>, <h1>

Minimal example

```
<title>Learn HTML (PDF) - Book Store</title>
<title>Contact us - Book Store</title>
<title>Order #1042 confirmed - Book Store</title>
```

Most common mistake

Same title on every page.

<title> — Document title

Category: Document metadata | Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <title> element defines the title of the document, shown in the browser's title bar or tab, used as the default name for bookmarks, displayed as the clickable headline in search engine results, and announced first by screen readers when the page loads. It contains text only; any tags inside are treated as literal text. Every document must have exactly one <title>, inside <head>.

A good title is unique for each page, describes the page's content, puts the most specific information first ('Learn HTML - Book Store' rather than 'Book Store - Learn HTML'), and is under about 60 characters so search engines do not truncate it.

Syntax

```
<title>Page title</title>
```

Technical summary

Property	Value
Void element	No
Default display	none
Content categories	Metadata content
Permitted content	Text (not inter-element whitespace only)
Permitted parents	<head> (exactly one)

Property	Value
Tag omission	Neither tag may be omitted
DOM interface	HTMLTitleElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<title>: worked examples

Good titles

```
<title>Learn HTML (PDF) - Book Store</title>
<title>Contact us - Book Store</title>
<title>Order #1042 confirmed - Book Store</title>
```

Changing the title from JavaScript

```
<script>
  document.title = '(3) New messages - Chat';
</script>
```

Default browser CSS

```
title { display: none; }
```

Accessibility

- The title is the first thing announced; unique, descriptive titles are a WCAG requirement (2.4.2).

Common mistakes

- Same title on every page.
- Empty or missing title.
- Putting HTML tags inside.
- Keyword stuffing.

See also

<head>, <meta>, <h1>

Quick card: <tr>

Table row

The <tr> element defines a row of cells in a table. It contains <th> (header) and/or <td> (data) cells and is placed inside <table>, <thead>, <tbody> or <tfoot>. Rows are the fundamental unit of table construction: you build a table one row at a time, and the columns emerge from the cells in each row.

At a glance

Status	CURRENT
Versions	HTML 3.2, HTML 4.01, HTML5
Category	Table content
Closing tag	Required unless noted under Tag omission
Display	table-row
Own attributes	align, bgcolor, char, valign
Related	<table>, <td>, <th>, <thead>, <tbody>, <tfoot>

Minimal example

```
<table>
  <tr>
    <th>Name</th>
    <th>Age</th>
  </tr>
  <tr>
    <td>Ahmed</td>
    <td>20</td>
  </tr>
  <tr>
    <td>Sara</td>
    <td>22</td>
  </tr>
</table>
```

Most common mistake

Text or elements directly inside <tr> that are not td/th.

<tr> — Table row

Category: Table content | Status: CURRENT | Versions: HTML 3.2, HTML 4.01, HTML5

Description

The <tr> element defines a row of cells in a table. It contains <th> (header) and/or <td> (data) cells and is placed inside <table>, <thead>, <tbody> or <tfoot>. Rows are the fundamental unit of table construction: you build a table one row at a time, and the columns emerge from the cells in each row.

Syntax

```
<tr>
  <td>Cell 1</td>
  <td>Cell 2</td>
</tr>
```

Technical summary

Property	Value
Void element	No
Default display	table-row
Content categories	None
Permitted content	Zero or more <td>, <th>, <script>, <template>
Permitted parents	<table> (directly), <thead>, <tbody>, <tfoot>
Tag omission	End tag may be omitted if followed by another <tr> or if there is no more content in the parent
DOM interface	HTMLTableRowElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
align	left | center | right | justify | char	Obsolete. Use CSS text-align on cells.	HTML 3.2
bgcolor	colour	Obsolete. Use CSS background-color.	HTML 3.2
char / charoff	character / number	Obsolete.	HTML 4.01
valign	top | middle | bottom | baseline	Obsolete. Use CSS vertical-align.	HTML 3.2

<tr>: attribute by attribute

Each attribute of <tr> explained in detail, with a minimal example you can copy.

align

Values: left | center | right | justify | char | Since: HTML 3.2

Obsolete. Use CSS text-align on cells.

Write align="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<tr align="left">...</tr>
```

bgcolor

Values: colour | Since: HTML 3.2

Obsolete. Use CSS background-color.

Write bgcolor="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<tr bgcolor="#336699">...</tr>
```

char / charoff

Values: character / number | Since: HTML 4.01

Obsolete.

Write char="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<tr char="3">...</tr>
```

valign

Values: top | middle | bottom | baseline | Since: HTML 3.2

Obsolete. Use CSS vertical-align.

Write valign="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<tr valign="top">...</tr>
```

<tr>: worked examples

Three rows

```
<table>
  <tr>
    <th>Name</th>
    <th>Age</th>
  </tr>
  <tr>
    <td>Ahmed</td>
    <td>20</td>
  </tr>
  <tr>
    <td>Sara</td>
    <td>22</td>
  </tr>
</table>
```

Row styling

```
<style>
  tr:nth-child(even) { background: #f9f9f9; }
  tr:hover { background: #eef; }
  tr.selected { outline: 2px solid #1b6fd8; }
</style>
```

Adding a row with JavaScript

```
<script>
  const row = document.querySelector('table').insertRow();
  row.insertCell().textContent = 'Omar';
  row.insertCell().textContent = '25';
</script>
```

Default browser CSS

```
tr { display: table-row; vertical-align: inherit; }
```

Accessibility

- Screen readers announce row numbers; keep one logical record per row.

Common mistakes

- Text or elements directly inside <tr> that are not td/th.
- Different numbers of cells per row.
- Nesting tr inside td without a new table.

See also

<table>, <td>, <th>, <thead>, <tbody>, <tfoot>

Quick card: <track>

Text track for media

The <track> element adds timed text tracks to <audio> or <video>: subtitles (translations), captions (dialogue plus sound descriptions for deaf and hard-of-hearing viewers), descriptions (spoken description of the video for blind users), chapters (navigation) and metadata (for scripts). Tracks are WebVTT files (.vtt). It is a void element placed after any <source> elements.

At a glance

Status	CURRENT
Versions	HTML5
Category	Image and multimedia
Closing tag	None (void element)
Display	none
Own attributes	src, kind, srclang, label, default
Related	<video>, <audio>, <source>

Minimal example

```
<video controls width="640" height="360">
  <source src="lesson.mp4" type="video/mp4">
  <track kind="captions" src="lesson-en.vtt" srclang="en"
label="English captions" default>
  <track kind="subtitles" src="lesson-ar.vtt" srclang="ar"
label="العربية">
  <track kind="chapters" src="chapters.vtt" srclang="en">
</video>
```

Most common mistake

Placing track before source.

<track> — Text track for media

Category: Image and multimedia | Status: CURRENT | Versions: HTML5

Description

The <track> element adds timed text tracks to <audio> or <video>: subtitles (translations), captions (dialogue plus sound descriptions for deaf and hard-of-hearing viewers), descriptions (spoken description of the video for blind users), chapters (navigation) and metadata (for scripts). Tracks are WebVTT files (.vtt). It is a void element placed after any <source> elements.

Only one track per kind may have the default attribute. Track files loaded from another origin require CORS headers and the crossorigin attribute on the media element.

Syntax

```
<track kind="captions" src="captions.vtt" srclang="en"
label="English" default>
```

Technical summary

Property	Value
Void element	Yes (no closing tag)
Default display	none
Content categories	None
Permitted content	None (void element)
Permitted parents	<audio>, <video>, after <source> and before flow content

Property	Value
Tag omission	No end tag
DOM interface	HTMLTrackElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
src	URL	Required. The WebVTT file.	HTML5
kind	subtitles | captions | descriptions | chapters | metadata	The type of track. Default subtitles.	HTML5
srclang	language tag	Language of the track. Required for subtitles.	HTML5
label	text	Human-readable title shown in the track menu.	HTML5
default	boolean	Enable this track by default (one per kind).	HTML5

<track>: attribute by attribute

Each attribute of <track> explained in detail, with a minimal example you can copy.

src

Values: URL | Since: HTML5

Required. The WebVTT file.

Write src="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<track src="https://example.com/page.html">
```

kind

Values: subtitles | captions | descriptions | chapters | metadata | Since: HTML5

The type of track. Default subtitles.

Write kind="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<track kind="subtitles">
```

srclang

Values: language tag | Since: HTML5

Language of the track. Required for subtitles.

Write srclang="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<track srclang="en">
```

label

Values: text | Since: HTML5

Human-readable title shown in the track menu.

Write label="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<track label="value">
```

default

Values: boolean | Since: HTML5

Enable this track by default (one per kind).

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<track default>
```

<track>: worked examples

Video with captions and subtitles

```
<video controls width="640" height="360">
  <source src="lesson.mp4" type="video/mp4">
  <track kind="captions" src="lesson-en.vtt" srclang="en"
label="English captions" default>
  <track kind="subtitles" src="lesson-ar.vtt" srclang="ar"
label="العربية">
  <track kind="chapters" src="chapters.vtt" srclang="en">
</video>
```

A WebVTT file

```
WEBVTT

00:00:00.000 --> 00:00:04.000
Welcome to the HTML course.

00:00:04.500 --> 00:00:08.000
Today we learn about the footer element.
```

Save as lesson-en.vtt; the first line must be WEBVTT.

Default browser CSS

```
track { display: none; }
```

Accessibility

- Captions are required for accessible video (WCAG 1.2.2). Subtitles alone are not captions: captions also describe sounds.
- Provide descriptions for visual-only information.

Common mistakes

- Placing track before source.
- Wrong MIME type on the server (should be text/vtt).
- Two default tracks of the same kind.

See also

<video>, <audio>, <source>

Quick card: <tt>

Teletype text (obsolete)

The <tt> element (teletype) rendered text in a monospace font, imitating a teletype or typewriter. It was purely presentational and HTML5 removed it. Use the semantic elements <code>, <kbd>, <samp> or <var>, or CSS font-family: monospace on a .

At a glance

Status	OBSOLETE
Versions	HTML 2.0, HTML 3.2, HTML 4.01; obsolete in HTML5
Category	Obsolete presentational
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	None (global attributes only)
Related	<code>, <kbd>, <samp>, <var>, <pre>

Minimal example

```
<!-- Old -->
<tt>ls -la</tt>

<!-- New -->
<kbd>ls -la</kbd>  <!-- user input -->
<code>ls -la</code> <!-- code -->
<span style="font-family: monospace">ls -la</span> <!-- style only -->
```

Most common mistake

Any use.

<tt> — Teletype text (obsolete)

Category: Obsolete presentational | Status: OBSOLETE | Versions: HTML 2.0, HTML 3.2, HTML 4.01; obsolete in HTML5

Description

The <tt> element (teletype) rendered text in a monospace font, imitating a teletype or typewriter. It was purely presentational and HTML5 removed it. Use the semantic elements <code>, <kbd>, <samp> or <var>, or CSS font-family: monospace on a .

Syntax

```
<tt>text</tt>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Historical
Permitted content	Phrasing content
Permitted parents	Phrasing content
Tag omission	Neither
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<tt>: worked examples

Replacements

```
<!-- Old -->
<tt>ls -la</tt>

<!-- New -->
<kbd>ls -la</kbd>  <!-- user input -->
<code>ls -la</code> <!-- code -->
<span style="font-family: monospace">ls -la</span> <!-- style only -->
```

Default browser CSS

```
tt { font-family: monospace; }
```

Common mistakes

- Any use.

See also

<code>, <kbd>, <samp>, <var>, <pre>

Quick card: <u>

Unarticulated annotation (underline)

The <u> element represents a span of inline text that should be rendered in a way that indicates a non-textual annotation: most commonly, marking misspelled words (as a word processor does with a wavy red line) or labelling proper names in Chinese text. Browsers render it with a solid underline. In HTML 4 <u> simply meant 'underline' and was deprecated; HTML5 redefined it.

At a glance

Status	CURRENT
Versions	HTML 3.2, HTML 4.01 (deprecated), HTML5 (redefined)
Category	Text-level semantics
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	None (global attributes only)
Related	, <ins>, <s>,

Minimal example

```
<p>Please chek <u class="spelling">recieve</u> before sending.</p>
<style>.spelling { text-decoration: red wavy underline; }</style>
```

Most common mistake

Using <u> for emphasis or headings.

<u> — Unarticulated annotation (underline)

Category: Text-level semantics | Status: CURRENT | Versions: HTML 3.2, HTML 4.01 (deprecated), HTML5 (redefined)

Description

The <u> element represents a span of inline text that should be rendered in a way that indicates a non-textual annotation: most commonly, marking misspelled words (as a word processor does with a wavy red line) or labelling proper names in Chinese text. Browsers render it with a solid underline. In HTML 4 <u> simply meant 'underline' and was deprecated; HTML5 redefined it.

Because underlined text looks like a link on the web, avoid <u> for anything that is not one of its intended uses. For emphasis use ; for titles <cite>; for pure decoration CSS text-decoration.

Syntax

```
<u>text</u>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, palpable content
Permitted content	Phrasing content

Property	Value
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<u>: worked examples

Spelling error

```
<p>Please chek <u class="spelling">recieve</u> before sending.</p>
<style>.spelling { text-decoration: red wavy underline; }</style>
```

Wrong use

```
<!-- Do not do this: looks like a link and carries no meaning -->
<p><u>Important</u></p>

<!-- Do this -->
<p><strong>Important</strong></p>
```

Default browser CSS

```
u { text-decoration: underline; }
```

Accessibility

- Underlined non-link text confuses users; they may try to click it.

Common mistakes

- Using <u> for emphasis or headings.

See also

, <ins>, <s>,

Quick card:

Unordered list

The <ul> element represents an unordered list of items: a list where changing the order would not change the meaning, such as a shopping list, a set of features, or the links of a navigation menu. Browsers show each item with a bullet. Each item is an <li>. If the order matters, use <ol>.

At a glance

Status	CURRENT
Versions	HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Text content
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	type, compact
Related	, , <menu>, <dl>, <nav>

Minimal example

```
<ul>
  <li>Milk</li>
  <li>Bread</li>
  <li>Eggs</li>
</ul>
```

Most common mistake

Text directly inside <ul> outside <li>.

 — Unordered list

Category: Text content | Status: CURRENT | Versions: HTML 1, HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <ul> element represents an unordered list of items: a list where changing the order would not change the meaning, such as a shopping list, a set of features, or the links of a navigation menu. Browsers show each item with a bullet. Each item is an <li>. If the order matters, use <ol>.

Lists are among the most useful elements in HTML because they carry structure: screen readers announce how many items there are and let users jump between them. Navigation menus are almost always built as a <ul> inside a <nav>, with CSS removing the bullets and arranging the items horizontally.

Syntax

```
<ul>
  <li>Item</li>
  <li>Item</li>
</ul>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	Flow content; palpable if it has at least one
Permitted content	Zero or more , <script>, <template>

Property	Value
Permitted parents	Any element that accepts flow content
Tag omission	Neither tag may be omitted
DOM interface	HTMLUListElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
type	disc | circle | square	Obsolete. Bullet style. Use CSS list-style-type.	HTML 3.2
compact	boolean	Obsolete. Compact rendering.	HTML 2.0

: attribute by attribute

Each attribute of <ul> explained in detail, with a minimal example you can copy.

type

Values: disc | circle | square | Since: HTML 3.2

Obsolete. Bullet style. Use CSS list-style-type.

Write type="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<ul type="disc">...</ul>
```

compact

Values: boolean | Since: HTML 2.0

Obsolete. Compact rendering.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<ul compact>...</ul>
```

: worked examples

Shopping list

```
<ul>
  <li>Milk</li>
  <li>Bread</li>
  <li>Eggs</li>
</ul>
```

Shows three bulleted lines.

Nested lists

```
<ul>
  <li>Fruit
    <ul>
      <li>Apples</li>
      <li>Bananas</li>
    </ul>
  </li>
  <li>Vegetables</li>
</ul>
```

Nested lists get a different bullet automatically (disc, then circle, then square).

Bullet styles

```
<ul style="list-style-type: square">...</ul>
<ul style="list-style-type: '✓ '">...</ul>
<ul style="list-style-image: url(star.png)">...</ul>
```

Navigation menu

```
<style>
  .menu { list-style: none; margin: 0; padding: 0; display: flex; gap:
 20px; }
</style>
<nav>
  <ul class="menu">
    <li><a href="/">Home</a></li>
    <li><a href="/shop">Shop</a></li>
    <li><a href="/contact">Contact</a></li>
  </ul>
</nav>
```

Custom bullets with ::marker

```
<style>
  li::marker { color: #e60000; font-size: 1.2em; }
</style>
```

Default browser CSS

```
ul { display: block; list-style-type: disc; margin: 1em 0; padding-
inline-start: 40px; }
```

Accessibility

- Announced as 'list, 3 items'. In Safari, list-style: none removes list semantics; add role="list" to the ul to keep them.

Common mistakes

- Text directly inside <ul> outside <li>.
- Using <ul> for ordered steps.
- Using <br> or paragraphs with dashes instead of a real list.

See also

, <li>, <menu>, <dl>, <nav>

Quick card: <var>

Variable

The <var> element represents the name of a variable in a mathematical expression or a programming context, or a placeholder for a value the reader must supply. Browsers render it in italics. It is one of the four 'computer' phrase elements together with <code>, <kbd> and <samp>.

At a glance

Status	CURRENT
Versions	HTML 2.0, HTML 3.2, HTML 4.01, HTML5
Category	Text-level semantics
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	None (global attributes only)
Related	<code>, <kbd>, <samp>, <math>

Minimal example

```
<p>The area is <var>w</var> × <var>h</var>.</p>
```

Most common mistake

Using <i> or for variables.

<var> — Variable

Category: Text-level semantics | Status: CURRENT | Versions: HTML 2.0, HTML 3.2, HTML 4.01, HTML5

Description

The <var> element represents the name of a variable in a mathematical expression or a programming context, or a placeholder for a value the reader must supply. Browsers render it in italics. It is one of the four 'computer' phrase elements together with <code>, <kbd> and <samp>.

Syntax

```
<var>x</var>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, palpable content
Permitted content	Phrasing content
Permitted parents	Any element that accepts phrasing content
Tag omission	Neither tag may be omitted
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<var>: worked examples

Maths

```
<p>The area is <var>w</var> × <var>h</var>.</p>
```

Placeholder in instructions

```
<p>Type <kbd>cd <var>folder-name</var></kbd> to enter a folder.</p>
```

Default browser CSS

```
var { font-style: italic; }
```

Common mistakes

- Using <i> or for variables.

See also

<code>, <kbd>, <samp>, <math>

Quick card: <video>

Embedded video

The <video> element embeds a video player in the document. The video file is given by src or by one or more <source> children (so that the browser can pick a supported format), followed by optional <track> elements for captions and subtitles, and finally fallback content for browsers without video support. Common formats are MP4 (H.264/AAC, universally supported), WebM (VP9/AV1, smaller) and, in Safari, HEVC.

At a glance

Status	CURRENT
Versions	HTML5
Category	Image and multimedia
Closing tag	Required unless noted under Tag omission
Display	inline
Own attributes	src, controls, autoplay, loop, muted, poster, preload, width, playsinline, crossorigin, controlslist, disablepictureinpicture, disableremoteplayback
Related	<audio>, <source>, <track>, <iframe>, <picture>

Minimal example

```
<video controls width="640" height="360" poster="poster.jpg"
preload="metadata">
  <source src="lesson.webm" type="video/webm">
  <source src="lesson.mp4" type="video/mp4">
  <track kind="captions" src="lesson-en.vtt" srclang="en"
label="English" default>
  <p>Your browser cannot play this video. <a href="lesson.
mp4">Download it</a>.</p>
</video>
```

Most common mistake

Expecting sound autoplay to work.

<video> — Embedded video

Category: Image and multimedia | Status: CURRENT | Versions: HTML5

Description

The <video> element embeds a video player in the document. The video file is given by src or by one or more <source> children (so that the browser can pick a supported format), followed by optional <track> elements for captions and subtitles, and finally fallback content for browsers without video support. Common formats are MP4 (H.264/AAC, universally supported), WebM (VP9/AV1, smaller) and, in Safari, HEVC.

The controls attribute shows the built-in play/pause, seek, volume, captions, picture-in-picture and fullscreen controls. Without it you must provide your own controls through the HTMLMediaElement API. Autoplay with sound is blocked by browsers; autoplay muted (for background video) is allowed. Set width and height or CSS aspect-ratio to prevent layout shift, and use preload="none" or "metadata" to avoid downloading large files that may never be played.

Syntax

```
<video src="clip.mp4" controls width="640" height="360"></video>
```

Technical summary

Property	Value
Void element	No
Default display	inline
Content categories	Flow content, phrasing content, embedded content; interactive and palpable if controls is present

Property	Value
Permitted content	If src: zero or more <track> then transparent content with no media elements. Otherwise: zero or more <source>, zero or more <track>, then transparent content with no media elements
Permitted parents	Any element that accepts embedded content
Tag omission	Neither tag may be omitted
DOM interface	HTMLVideoElement

Attributes

In addition to the global attributes (Part 4) and event handler attributes (Part 5), this element supports the following:

Attribute	Values	Description	Since
src	URL	The video file. Or use <source> children.	HTML5
controls	boolean	Show built-in controls.	HTML5
autoplay	boolean	Start automatically (only reliable with muted).	HTML5
loop	boolean	Repeat when finished.	HTML5
muted	boolean	Start muted.	HTML5
poster	URL	Image shown before the video plays or while loading.	HTML5
preload	none | metadata | auto	How much to download before play.	HTML5
width / height	pixels	Display size; also prevents layout shift.	HTML5
playsinline	boolean	On iPhone, play inline instead of forcing fullscreen.	Living Standard

Attribute	Values	Description	Since
crossorigin	anonymous | use-credentials	CORS mode for the media (needed for canvas processing and cross-origin tracks).	HTML5
controlslist	nodownload | nofullscreen | noremoteplayback	Hide specific native controls (Chromium).	Non-standard
disablepictureinpicture	boolean	Hide the picture-in-picture option.	Living Standard
disableremoteplayback	boolean	Disable casting.	Living Standard

<video>: attribute by attribute

Each attribute of <video> explained in detail, with a minimal example you can copy.

src

Values: URL | Since: HTML5

The video file. Or use <source> children.

Write src="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<video src="https://example.com/page.html">...</video>
```

controls

Values: boolean | Since: HTML5

Show built-in controls.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<video controls>...</video>
```

autoplay

Values: boolean | Since: HTML5

Start automatically (only reliable with muted).

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<video autoplay>...</video>
```

loop

Values: boolean | Since: HTML5

Repeat when finished.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<video loop>...</video>
```

muted

Values: boolean | Since: HTML5

Start muted.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<video muted>...</video>
```

poster

Values: URL | Since: HTML5

Image shown before the video plays or while loading.

Write poster="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<video poster="https://example.com/page.html">...</video>
```

preload

Values: none | metadata | auto | Since: HTML5

How much to download before play.

Write preload="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<video preload="none">...</video>
```

width / height

Values: pixels | Since: HTML5

Display size; also prevents layout shift.

Write width="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<video width="3">...</video>
```

playsinline

Values: boolean | Since: Living Standard

On iPhone, play inline instead of forcing fullscreen.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<video playsinline>...</video>
```

crossorigin

Values: anonymous | use-credentials | Since: HTML5

CORS mode for the media (needed for canvas processing and cross-origin tracks).

Write crossorigin="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<video crossorigin="anonymous">...</video>
```

controlslist

Values: nodownload | nofullscreen | noremoteplayback | Since: Non-standard

Hide specific native controls (Chromium).

Write controlslist="..." inside the start tag. Quote the value; several attributes are separated by spaces.

```
<video controlslist="nodownload">...</video>
```

disablepictureinpicture

Values: boolean | Since: Living Standard

Hide the picture-in-picture option.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<video disablepictureinpicture>...</video>
```

disableremoteplayback

Values: boolean | Since: Living Standard

Disable casting.

Boolean attribute: write only the name to switch it on; leave it out to switch it off.

```
<video disableremoteplayback>...</video>
```

<video>: worked examples

Complete accessible video

```
<video controls width="640" height="360" poster="poster.jpg"
preload="metadata">
  <source src="lesson.webm" type="video/webm">
  <source src="lesson.mp4" type="video/mp4">
  <track kind="captions" src="lesson-en.vtt" srclang="en"
label="English" default>
  <p>Your browser cannot play this video. <a href="lesson.
mp4">Download it</a>.</p>
</video>
```

Background hero video

```
<video autoplay muted loop playsinline poster="hero.jpg" aria-
hidden="true">
  <source src="hero.mp4" type="video/mp4">
</video>
```

Muted autoplay is allowed; aria-hidden because it is decorative. Respect prefers-reduced-motion by pausing it with JavaScript.

Responsive sizing

```
<style>
  video { width: 100%; height: auto; aspect-ratio: 16 / 9; background:
 #000; }
</style>
```

Custom play button

```
<video id="v" src="clip.mp4" width="400"></video>
<button onclick="const v = document.getElementById('v'); v.paused ? v.
play() : v.pause()">Play / Pause</button>
```

Default browser CSS

```
video { object-fit: contain; }
video:not([controls]) { /* nothing shown until play */ }
```

Accessibility

- Provide captions with <track kind="captions">.
- Provide a transcript for audio and visual content.
- Never autoplay with sound.
- Keep native controls unless your custom controls are fully keyboard accessible.

- Avoid flashing content.

Common mistakes

- Expecting sound autoplay to work.
- A single format only.
- Huge files with preload="auto".
- No poster, showing a black box until play.
- Missing playsinline on iOS.

See also

<audio>, <source>, <track>, <iframe>, <picture>

Quick card: <wbr>

Word break opportunity

The <wbr> element marks a position inside a word where the browser may break the line if necessary, without inserting a hyphen or a visible character. It is useful for very long words, URLs and code identifiers that would otherwise overflow their container. If no break is needed, nothing is displayed. It is a void element.

At a glance

Status	CURRENT
Versions	Netscape / IE extension, standardised in HTML5
Category	Text-level semantics
Closing tag	None (void element)
Display	inline
Own attributes	None (global attributes only)
Related	 , <nobr>

Minimal example

```
<p>Visit https://example.com/<wbr>very/<wbr>long/<wbr>path/<wbr>to/
<wbr>a/<wbr>resource</p>
```

Most common mistake

Using <br> where a soft break is wanted.

<wbr> — Word break opportunity

Category: Text-level semantics | Status: CURRENT | Versions: Netscape / IE extension, standardised in HTML5

Description

The <wbr> element marks a position inside a word where the browser may break the line if necessary, without inserting a hyphen or a visible character. It is useful for very long words, URLs and code identifiers that would otherwise overflow their container. If no break is needed, nothing is displayed. It is a void element.

Alternatives: the zero-width space character () has the same effect; the soft hyphen () breaks with a hyphen; CSS overflow-wrap: anywhere allows breaks anywhere in overflowing words.

Syntax

```
Super<wbr>cali<wbr>fragilistic
```

Technical summary

Property	Value
Void element	Yes (no closing tag)
Default display	inline
Content categories	Flow content, phrasing content
Permitted content	None (void element)
Permitted parents	Any element that accepts phrasing content

Property	Value
Tag omission	No end tag
DOM interface	HTMLElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<wbr>: worked examples

Long URL

```
<p>Visit https://example.com/<wbr>very/<wbr>long/<wbr>path/<wbr>to/
<wbr>a/<wbr>resource</p>
```

The URL can break after each slash instead of overflowing.

Long identifier

```
<code>HTMLTable<wbr>Section<wbr>Element</code>
```

Default browser CSS

```
wbr { content: '\200B'; }
```

Accessibility

- Invisible to screen readers; does not affect pronunciation.

Common mistakes

- Using <br> where a soft break is wanted.
- Writing </wbr>.

See also

, <nobr>

Quick card: <xmp>

Example text (obsolete)

The <xmp> element (example) displayed its content literally, without interpreting any markup, in a monospace font, so that authors could show HTML source without escaping < and &. It was one of the 1991 elements, deprecated in HTML 2.0 and removed in HTML 3.2, although browsers still support it for old pages. Use <pre> with escaped entities.

At a glance

Status	OBSOLETE
Versions	HTML 1, HTML 2.0 (deprecated); obsolete
Category	Obsolete text content
Closing tag	Required unless noted under Tag omission
Display	block
Own attributes	None (global attributes only)
Related	<pre>, <listing>, <plaintext>, <code>

Minimal example

```
<pre>&lt;p&gt;shown literally&lt;/p&gt;</pre>
```

Most common mistake

Any use.

<xmp> — Example text (obsolete)

Category: Obsolete text content | Status: OBSOLETE | Versions: HTML 1, HTML 2.0 (deprecated); obsolete

Description

The <xmp> element (example) displayed its content literally, without interpreting any markup, in a monospace font, so that authors could show HTML source without escaping < and &. It was one of the 1991 elements, deprecated in HTML 2.0 and removed in HTML 3.2, although browsers still support it for old pages. Use <pre> with escaped entities.

Syntax

```
<xmp><p>shown literally</p></xmp>
```

Technical summary

Property	Value
Void element	No
Default display	block
Content categories	Historical
Permitted content	Raw text
Permitted parents	Flow content
Tag omission	Neither
DOM interface	HTMLPreElement

Attributes

This element supports only the global attributes (Part 4) and event handler attributes (Part 5).

<xmp>: worked examples

Replacement

```
<pre>&lt;p&gt;shown literally&lt;/p&gt;</pre>
```

Default browser CSS

```
xmp { display: block; font-family: monospace; white-space: pre;
margin: 1em 0; }
```

Common mistakes

- Any use.

See also

<pre>, <listing>, <plaintext>, <code>

Part 7

The input Element in Depth

Every value of the type attribute with its own entry.

Input types overview

type	Control	Since
text	Single-line text	HTML 2.0
password	Password	HTML 2.0
checkbox	Check box	HTML 2.0
radio	Radio button	HTML 2.0
submit	Submit button	HTML 2.0
reset	Reset button	HTML 2.0
button	Generic button	HTML 3.2
hidden	Hidden field	HTML 2.0
image	Image submit button	HTML 2.0
file	File chooser	HTML 3.2
email	Email address	HTML5
url	Web address	HTML5
tel	Telephone number	HTML5
search	Search field	HTML5
number	Numeric field	HTML5
range	Slider	HTML5
color	Colour picker	HTML5
date	Date	HTML5
time	Time of day	HTML5
datetime-local	Local date and time	HTML5
month	Month and year	HTML5
week	Week of the year	HTML5

<input type="text"> — Single-line text

Since: HTML 2.0

The default type. A single-line text field. Line breaks are removed from the value. Use it for names, titles, and anything that has no more specific type.

Type-specific attributes

Attribute	Note
maxlength / minlength	Length limits.
pattern	Regular expression to validate.
placeholder	Hint text.
size	Visible width in characters.
list	Datalist of suggestions.
autocomplete	Autofill token such as name, given-name, organization.
dirname	Submit text direction.

Example

```
<label for="n">Full name</label>
<input id="n" name="name" type="text" autocomplete="name" required>
```

Also accepted: the common input attributes name, value, disabled, form, autofocus, required (where meaningful), and all global attributes.

<input type="password"> — Password

Since: HTML 2.0

A single-line field whose characters are obscured with dots or asterisks. The value is still sent as plain text in the form submission, so the page must be served over HTTPS. Browsers offer to save and generate passwords when autocomplete is set to current-password or new-password.

Type-specific attributes

Attribute	Note
minlength / maxlength	Length rules.
pattern	Complexity rules (explain them in title).
autocomplete	current-password, new-password, one-time-code.

Example

```
<label for="pw">Password</label>
<input id="pw" name="password" type="password" minlength="8"
autocomplete="new-password" required>
```

Add a 'show password' toggle for usability.

Also accepted: the common input attributes name, value, disabled, form, autofocus, required (where meaningful), and all global attributes.

<input type="checkbox"> — Check box

Since: HTML 2.0

An on/off box. Each checkbox is independent; several checkboxes may share a name to send multiple values. Only checked boxes are submitted (as name=value). The indeterminate visual state can be set from JavaScript for 'some children selected'.

Type-specific attributes

Attribute	Note
checked	Initially ticked.
value	Sent when checked; default 'on'.
required	Must be ticked (useful for 'I agree').

Example

```
<label><input type="checkbox" name="topics" value="html" checked>
HTML</label>
<label><input type="checkbox" name="topics" value="css"> CSS</label>
```

Wrap the input in the label so the text is clickable.

Also accepted: the common input attributes name, value, disabled, form, autofocus, required (where meaningful), and all global attributes.

<input type="radio"> — Radio button

Since: HTML 2.0

One of a group of mutually exclusive options. All radio buttons with the same name form a group and only one can be selected. Arrow keys move the selection within the group. Always provide a default or make the group required, and caption the group with fieldset/legend.

Type-specific attributes

Attribute	Note
checked	Initially selected.
value	Sent for the selected button.
required	One button in the group must be selected.

Example

```
<fieldset>
  <legend>Delivery</legend>
  <label><input type="radio" name="d" value="standard" checked>
Standard</label>
  <label><input type="radio" name="d" value="express"> Express</label>
</fieldset>
```

Also accepted: the common input attributes name, value, disabled, form, autofocus, required (where meaningful), and all global attributes.

<input type="submit"> — Submit button

Since: HTML 2.0

A button that submits the form. Its value is the button's label and, if it has a name, is submitted too. Prefer the <button> element, which can contain HTML content.

Type-specific attributes

Attribute	Note
value	Label (default 'Submit').
formaction, formmethod, formenctype, formtarget, formnovalidate	Override form settings.

Example

```
<input type="submit" value="Send message">
```

Also accepted: the common input attributes name, value, disabled, form, autofocus, required (where meaningful), and all global attributes.

<input type="reset"> — Reset button

Since: HTML 2.0

A button that restores all controls of the form to their initial values. Rarely useful and often clicked by mistake; most forms omit it.

Type-specific attributes

Attribute	Note
value	Label (default 'Reset').

Example

```
<input type="reset" value="Clear form">
```

Also accepted: the common input attributes name, value, disabled, form, autofocus, required (where meaningful), and all global attributes.

<input type="button"> — Generic button

Since: HTML 3.2

A button with no default behaviour, for use with JavaScript. Prefer <button type="button">.

Type-specific attributes

Attribute	Note
value	Label.

Example

```
<input type="button" value="Show help" onclick="alert('Help')">
```

Also accepted: the common input attributes name, value, disabled, form, autofocus, required (where meaningful), and all global attributes.

<input type="hidden"> — Hidden field

Since: HTML 2.0

A control that is not displayed but whose value is submitted with the form. Used for record ids, CSRF tokens and other data the user does not edit. The name _charset_ has a special meaning: the browser fills it with the form's encoding.

Type-specific attributes

Attribute	Note
value	The value to submit.

Example

```
<input type="hidden" name="csrf" value="a1b2c3">
```

Never rely on hidden fields for security; users can change them.

Also accepted: the common input attributes name, value, disabled, form, autofocus, required (where meaningful), and all global attributes.

<input type="image"> — Image submit button

Since: HTML 2.0

A graphical submit button showing the image in src. When clicked it submits the form together with the click coordinates as name.x and name.y. Requires alt.

Type-specific attributes

Attribute	Note
src	Image URL.
alt	Required text alternative.
width / height	Size.
formaction etc.	Override form settings.

Example

```
<input type="image" src="go.png" alt="Search" width="32" height="32">
```

Also accepted: the common input attributes name, value, disabled, form, autofocus, required (where meaningful), and all global attributes.

<input type="file"> — File chooser

Since: HTML 3.2

Lets the user select one or more files from their device to upload. The form must use method="post" and enctype="multipart/form-data". The selected files are available in JavaScript as input.files. For security the value cannot be set by script and shows only a fake path.

Type-specific attributes

Attribute	Note
accept	Allowed types: image/*, video/*, audio/*, .pdf, application/pdf, .doc,.docx
multiple	Allow several files.
capture	user | environment: open camera/mic directly on phones.
webkitdirectory	Non-standard: choose a folder.

Example

```
<label for="cv">Upload your CV (PDF)</label>
<input id="cv" name="cv" type="file" accept=".pdf,application/pdf">
```

Also accepted: the common input attributes name, value, disabled, form, autofocus, required (where meaningful), and all global attributes.

<input type="email"> — Email address

Since: HTML5

A text field validated as an email address (or a comma-separated list with multiple). Mobile keyboards show @ and . keys. The value is trimmed and validated as user@host; a domain without a dot is accepted.

Type-specific attributes

Attribute	Note
multiple	Allow several addresses separated by commas.
pattern	Additional restriction, for example a company domain.
list	Suggestions.
maxlength / minlength / size / placeholder / readonly	As text.

Example

```
<label for="e">Email</label>
<input id="e" name="email" type="email" autocomplete="email" required>
```

Still validate on the server.

Also accepted: the common input attributes name, value, disabled, form, autofocus, required (where meaningful), and all global attributes.

<input type="url"> — Web address

Since: HTML5

A text field validated as an absolute URL (it must include a scheme such as https://). Mobile keyboards show / and .com keys.

Type-specific attributes

Attribute	Note
pattern	Extra restriction, for example https only.
list, maxlength, minlength, placeholder, readonly, size	As text.

Example

```
<label for="site">Website</label>
<input id="site" name="site" type="url" placeholder="https://example.
com">
```

Also accepted: the common input attributes name, value, disabled, form, autofocus, required (where meaningful), and all global attributes.

<input type="tel"> — Telephone number

Since: HTML5

A text field for telephone numbers. It is not validated (formats vary too much worldwide), but phones show a telephone keypad. Add pattern for a specific format.

Type-specific attributes

Attribute	Note
pattern	For example [0-9]{11} or \+20[0-9]{10}.
list, maxlength, minlength, placeholder, readonly, size	As text.

Example

```
<label for="t">Mobile</label>
<input id="t" name="tel" type="tel" autocomplete="tel" pattern="01[0-
9]{9}" title="11 digits starting with 01">
```

Also accepted: the common input attributes name, value, disabled, form, autofocus, required (where meaningful), and all global attributes.

<input type="search"> — Search field

Since: HTML5

A text field for search terms. Functionally identical to text, but some browsers style it with rounded corners and a clear (x) button, and mobile keyboards show a Search key. Line breaks are removed.

Type-specific attributes

Attribute	Note
list, maxlength, minlength, pattern, placeholder, readonly, size	As text.
incremental	Non-standard (WebKit): fire search events while typing.

Example

```
<search>
  <label for="q">Search</label>
  <input id="q" name="q" type="search" placeholder="Search books">
</search>
```

Also accepted: the common input attributes name, value, disabled, form, autofocus, required (where meaningful), and all global attributes.

<input type="number"> — Numeric field

Since: HTML5

A field for entering a number, usually with spinner arrows. Only digits, sign, decimal point and exponent are accepted; the value is validated against min, max and step. Use it only for actual quantities. For identifiers such as credit card numbers or postal codes use type="text" with inputmode="numeric" because they can have leading zeros and are not meant to be incremented.

Type-specific attributes

Attribute	Note
min / max	Range.
step	Increment; 'any' allows decimals of any precision. Default 1, which rejects 2.5 unless step is 0.5 or any.
placeholder, readonly, list	As text.

Example

```
<label for="qty">Quantity</label>
<input id="qty" name="qty" type="number" min="1" max="99" step="1"
value="1">
```

Scrolling the mouse wheel over a focused number input changes the value in some browsers.

Also accepted: the common input attributes name, value, disabled, form, autofocus, required (where meaningful), and all global attributes.

<input type="range"> — Slider

Since: HTML5

A slider for choosing an approximate number where the exact value is not important, such as volume or brightness. Default range 0-100, step 1. Show the current value with an <output> because the slider itself does not display it.

Type-specific attributes

Attribute	Note
min / max	Range.
step	Increment.
list	Datalist for tick marks.
orient	Non-standard (Firefox): vertical.

Example

```
<label for="vol">Volume</label>
<input id="vol" name="vol" type="range" min="0" max="100" value="40"
oninput="out.value = this.value">
<output id="out">40</output>
```

Also accepted: the common input attributes name, value, disabled, form, autofocus, required (where meaningful), and all global attributes.

<input type="color"> — Colour picker

Since: HTML5

A control for choosing a colour, usually opening the operating system colour picker. The value is always a lowercase hexadecimal colour such as #ff0000; alpha (transparency) is not supported unless the experimental alpha attribute is used.

Type-specific attributes

Attribute	Note
value	Initial colour in #rrggbb form (default #000000).
list	Datalist of suggested colours.
alpha, colorspace	Experimental.

Example

```
<label for="c">Theme colour</label>
<input id="c" name="color" type="color" value="#e60000">
```

Also accepted: the common input attributes name, value, disabled, form, autofocus, required (where meaningful), and all global attributes.

<input type="date"> — Date

Since: HTML5

A control for a year, month and day, usually with a calendar pop-up. The value is always in the format YYYY-MM-DD regardless of how the browser displays it to the user, so it is safe to process on the server. Safari on macOS supports it since version 14.1.

Type-specific attributes

Attribute	Note
min / max	Earliest and latest date, as YYYY-MM-DD.
step	In days.
list	Suggested dates.
readonly, required	As usual.

Example

```
<label for="d">Delivery date</label>
<input id="d" name="date" type="date" min="2026-09-12" max="2026-12-
31" required>
```

Set min to today's date with JavaScript to prevent past dates.

Also accepted: the common input attributes name, value, disabled, form, autofocus, required (where meaningful), and all global attributes.

<input type="time"> — Time of day

Since: HTML5

A control for hours and minutes (and optionally seconds), without a time zone. The value format is HH:MM or HH:MM:SS in 24-hour form.

Type-specific attributes

Attribute	Note
min / max	As HH:MM.
step	In seconds; 60 = minutes only (default), 1 = show seconds.
list	Suggested times.

Example

```
<label for="t">Appointment time</label>
<input id="t" name="time" type="time" min="09:00" max="17:00"
step="900">
```

step 900 = 15-minute increments.

Also accepted: the common input attributes name, value, disabled, form, autofocus, required (where meaningful), and all global attributes.

<input type="datetime-local">— Local date and time

Since: HTML5

A control for a date and time with no time zone, format YYYY-MM-DDTHH:MM. Convert to UTC on the server if needed. The older type="datetime" (with time zone) was removed from the standard.

Type-specific attributes

Attribute	Note
min / max	As YYYY-MM-DDTHH:MM.
step	In seconds.
list	Suggestions.

Example

```
<label for="dt">Event start</label>
<input id="dt" name="start" type="datetime-local" value="2026-10-
01T19:00">
```

Also accepted: the common input attributes name, value, disabled, form, autofocus, required (where meaningful), and all global attributes.

<input type="month"> — Month and year

Since: HTML5

A control for a month in a year, value format YYYY-MM. Useful for card expiry dates and reports. Not supported in Firefox or Safari desktop, which fall back to a text field.

Type-specific attributes

Attribute	Note
min / max	As YYYY-MM.
step	In months.
list	Suggestions.

Example

```
<label for="exp">Card expiry</label>
<input id="exp" name="exp" type="month" autocomplete="cc-exp">
```

Also accepted: the common input attributes name, value, disabled, form, autofocus, required (where meaningful), and all global attributes.

<input type="week"> — Week of the year

Since: HTML5

A control for an ISO week, value format YYYY-Www (for example 2026-W37). Limited browser support (Chromium only); others show a text field.

Type-specific attributes

Attribute	Note
min / max	As YYYY-Www.
step	In weeks.
list	Suggestions.

Example

```
<label for="w">Week</label>
<input id="w" name="week" type="week" value="2026-W37">
```

Also accepted: the common input attributes name, value, disabled, form, autofocus, required (where meaningful), and all global attributes.

Part 8

Obsolete and Deprecated Features

Old elements and attributes you may meet, with modern replacements.

Obsolete elements

These elements appeared in HTML 1, 2.0, 3.2, 4.01 or as browser extensions and are no longer part of the standard. Browsers still render most of them for compatibility with old pages, but they must not be used in new documents. Each has a full entry in Part 6; this table summarises the replacements.

Element	Status	Was used for	Use instead
<acronym>	obsolete	Acronym (obsolete)	<abbr>
<applet>	obsolete	Java applet (obsolete)	<object>, <embed>, <canvas>
<basefont>	obsolete	Base font (obsolete)	<font>, <body>
<bgsound>	obsolete	Background sound (non-standard, obsolete)	<audio>
<big>	obsolete	Bigger text (obsolete)	<small>,
<blink>	obsolete	Blinking text (non-standard, obsolete)	<marquee>
	obsolete	Centred block (obsolete)	
<content>	obsolete	Shadow DOM insertion point (obsolete)	<slot>, <template>, <shadow>
<dir>	obsolete	Directory list (obsolete)	, <menu>
<fencedframe>	experimental	Fenced frame (experimental)	<iframe>
<font>	obsolete	Font (obsolete)	<basefont>,
<frame>	obsolete	Frame (obsolete)	<frameset>, <noframes>, <iframe>

Element	Status	Was used for	Use instead
<frameset>	obsolete	Frameset (obsolete)	<frame>, <noframes>, <iframe>
<image>	obsolete	Image (non-standard alias, obsolete)	<img>
<isindex>	obsolete	Search index prompt (obsolete)	<form>, <input>
<keygen>	obsolete	Key-pair generator (obsolete)	<input>, <form>
<listing>	obsolete	Listing (obsolete)	<pre>, <xmp>, <plaintext>
<marquee>	obsolete	Scrolling text (obsolete)	<blink>
<menuitem>	obsolete	Menu item (obsolete)	<menu>, <button>
<multicol>	obsolete	Multi-column text (non-standard, obsolete)	
<nextid>	obsolete	Next identifier (HTML 1 editor hint)	<head>, <isindex>, <listing>
<nobr>	obsolete	No line break (non-standard, obsolete)	<wbr>,
<noembed>	obsolete	Fallback for embed (obsolete)	<embed>, <object>
<noframes>	obsolete	Fallback for frames (obsolete)	<frameset>, <frame>
<param>	deprecated	Object parameter (deprecated)	<object>, <embed>
<plaintext>	obsolete	Plain text (obsolete)	<pre>, <xmp>, <listing>
<portal>	experimental	Portal (experimental, abandoned)	<iframe>, <fencedframe>

Element	Status	Was used for	Use instead
<rb>	deprecated	Ruby base (deprecated)	<ruby>, <rt>, <rp>, <rtc>
<rtc>	deprecated	Ruby text container (deprecated)	<ruby>, <rt>, <rb>
<selectedcontent>	experimental	Selected option display (customisable select)	<select>, <option>, <button>
<shadow>	obsolete	Shadow root insertion point (obsolete)	<slot>, <template>, <content>
<spacer>	obsolete	Spacer (non-standard, obsolete)	 , <hr>
<strike>	obsolete	Strikethrough (obsolete)	<s>, <del>
<tt>	obsolete	Teletype text (obsolete)	<code>, <kbd>, <samp>, <var>, <pre>
<xmp>	obsolete	Example text (obsolete)	<pre>, <listing>, <plaintext>, <code>

Obsolete attributes

Presentational attributes were the HTML 3.2 way to control appearance. All of them are replaced by CSS.

Attribute	Was on	CSS replacement
align	div, p, h1-h6, table, tr, td, th, img, hr, caption, legend, iframe, object	text-align, float, vertical-align, margin
bgcolor	body, table, tr, td, th	background-color
background	body, table, td	background-image

Attribute	Was on	CSS replacement
border	img, table, object	border
cellpadding / cellspacing	table	padding on cells / border-spacing, border-collapse
width / height	table, td, th, hr, pre, applet	width, height
hspace / vspace	img, object, applet	margin
valign	tr, td, th, col, tbody, thead, tfoot	vertical-align
nowrap	td, th	white-space: nowrap
clear	br	clear
color / face / size	font, basefont	color, font-family, font-size
size / noshade	hr	height, border
text / link / vlink / alink	body	color, a:link, a:visited, a:active
type	ul, li	list-style-type
compact	dl, ol, ul, dir, menu	margin, line-height
frameborder / marginwidth / marginheight / scrolling	iframe, frame	border, padding, overflow
language	script	type (or omit)
name	a, img, form (as id)	id
longdesc	img, iframe	a link or aria-describedby
summary	table	caption, aria-describedby
charset	a, link, script	HTTP headers

Attribute	Was on	CSS replacement
rev	a, link	rel
scheme	meta	-
manifest	html	Service workers
accept	form	accept on input
archive, classid, codebase, codetype, declare, standby	object	-

Part 9

Attribute Reference

Every element-specific attribute listed alphabetically with the elements that accept it.

Alphabetical attribute index

Global attributes are in Part 4 and event attributes in Part 5. This index covers attributes specific to particular elements. Look up the attribute, find the element, then read the full entry in Part 6.

Attribute	Used on
abbr	<td>, <th>
accept	<form>, <input>
accept-charset	<form>
action	<form>, <isindex>
align	<applet>, <caption>, <col>, <colgroup>, , <h1>, <hr>, <iframe>, <img>, <input>, <legend>, <object>, <p>, <spacer>, <table>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>
alink	<body>
allow	<fencedframe>, <iframe>
allowfullscreen	<iframe>
allowpaymentrequest	<iframe>
alpha	<input>
alt	<applet>, <area>, <image>, <img>, <input>
archive	<applet>, <object>
aria-label	<svg>
aria-labelledby	<svg>
as	<link>
async	<script>
attributionsrc	<a>, <img>, <script>
autocomplete	<form>, <input>, <select>, <textarea>

Attribute	Used on
autofocus	<button>, <input>, <keygen>, <select>, <textarea>
autoplay	<audio>, <video>
axis	<td>, <th>
background	<body>
balance	<bgsound>
behavior	<marquee>
bgcolor	<body>, <col>, <colgroup>, <marquee>, <table>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>
blocking	<link>, <script>, <style>
border	<frameset>, <img>, <object>, <table>
bottommargin	<body>
capture	<input>
cellpadding	<table>
cellspacing	<table>
challenge	<keygen>
char	<col>, <colgroup>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>
charoff	<col>, <colgroup>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>
charset	<a>, <link>, <meta>, <script>
checked	<input>, <menuitem>
cite	<blockquote>, <del>, <ins>, <q>
classid	<object>
clear	
closedby	<dialog>
code	<applet>

Attribute	Used on
codebase	<applet>, <object>
codetype	<object>
color	<basefont>, <font>, <hr>, <link>
colorspace	<input>
cols	<frameset>, <multicol>, <textarea>
colspan	<td>, <th>
command	<button>, <menuitem>
commandfor	<button>
compact	<dir>, <dl>, <menu>, ,
content	<meta>
controls	<audio>, <video>
controlslist	<audio>, <video>
coords	<a>, <area>
credentialless	<iframe>
crossorigin	<audio>, <img>, <link>, <script>, <video>
csp	<iframe>
data	<object>
datetime	<del>, <ins>, <time>
declare	<object>
decoding	<img>
default	<menuitem>, <track>
defer	<script>
dir	<bdi>, <bdo>, <html>
direction	<marquee>
dirname	<input>, <textarea>

Attribute	Used on
disabled	<button>, <fieldset>, <input>, <keygen>, <link>, <menuitem>, <optgroup>, <option>, <select>, <textarea>
disablepictureinpicture	<video>
disableremoteplayback	<audio>, <video>
display	<math>
download	<a>, <area>
elementtiming	<img>
enctype	<form>
etc.	<image>
event	<script>
face	<basefont>, <font>
fetchpriority	<img>, <link>, <script>
fill	<svg>
for	<label>, <output>, <script>
form	<button>, <fieldset>, <input>, <keygen>, <label>, <meter>, <object>, <output>, <select>, <textarea>
formaction	<button>, <input>
formenctype	<button>, <input>
formmethod	<button>, <input>
formnovalidate	<button>, <input>
formtarget	<button>, <input>
frame	<table>
frameborder	<frame>, <frameset>, <iframe>

Attribute	Used on
framespacing	<frameset>
gutter	<multicol>
headers	<td>, <th>
height	<applet>, <canvas>, <embed>, <fencedframe>, <iframe>, <img>, <input>, <marquee>, <object>, <source>, <spacer>, <svg>, <table>, <td>, <th>, <video>
high	<meter>
href	<a>, <area>, <base>, <link>
hreflang	<a>, <link>
hspace	<applet>, <img>, <marquee>, <object>
http-equiv	<meta>
icon	<menuitem>
id	<input>
imagesizes	<link>
imagesrcset	<link>
incremental	<input>
inputmode	<input>
integrity	<link>, <script>
ismap	<img>
itemprop	<meta>
keytype	<keygen>
kind	<track>
label	<menu>, <menuitem>, <optgroup>, <option>, <track>
lang	<html>
language	<script>

Attribute	Used on
leftmargin	<body>
link	<body>
list	<input>
loading	<iframe>, <img>
longdesc	<frame>, <iframe>, <img>
loop	<audio>, <bgsound>, <marquee>, <video>
low	<meter>
lowsrc	<img>
manifest	<html>
marginheight	<frame>, <iframe>
marginwidth	<frame>, <iframe>
max	<input>, <meter>, <progress>
maxlength	<input>, <textarea>
media	<link>, <meta>, <source>, <style>
method	<form>
min	<input>, <meter>
minlength	<input>, <textarea>
moz-opaque	<canvas>
mozactionhint	<input>
multiple	<input>, <select>
muted	<audio>, <video>
n	<nextid>
name	<a>, <applet>, <button>, <details>, <fieldset>, <form>, <frame>, <iframe>, <img>, <input>, <keygen>, <map>, <meta>, <object>, <output>, <param>, <select>, <slot>, <textarea>

Attribute	Used on
nohref	<area>
nomodule	<script>
nonce	<script>, <style>
noresize	<frame>
noshade	<hr>
novalidate	<form>
nowrap	<dd>, <td>, <th>
object	<applet>
onbeforeunload	<body>
onhashchange	<body>
onlanguagechange	<body>
onload	<body>
onpopstate	<body>
onresize	<body>
onstorage	<body>
onunload	<body>
open	<details>, <dialog>
optimum	<meter>
orient	<input>
pattern	<input>
ping	<a>, <area>
placeholder	<input>, <textarea>
playsinline	<video>
popovertarget	<button>, <input>
popovertargetaction	<button>, <input>

Attribute	Used on
poster	<video>
preload	<audio>, <video>
preserveAspectRatio	<svg>
profile	<head>
prompt	<isindex>
property	<meta>
radiogroup	<menuitem>
readonly	<input>, <textarea>
referrerpolicy	<a>, <area>, <iframe>, <img>, <link>, <portal>, <script>
rel	<a>, <area>, <form>, <link>
required	<input>, <select>, <textarea>
results	<input>
rev	<a>, <link>
reversed	
rightmargin	<body>
role	<svg>
rows	<frameset>, <textarea>
rowspan	<td>, <th>
rules	<table>
sandbox	<iframe>
scheme	<meta>
scope	<td>, <th>
scoped	<style>
scrollamount	<marquee>
scrolldelay	<marquee>

Attribute	Used on
scrolling	<frame>, <iframe>
select	<content>
selected	<option>
shadowrootclonable	<template>
shadowrootdelegatesfocus	<template>
shadowrootmode	<template>
shadowrootserializable	<template>
shape	<a>, <area>
size	<basefont>, <font>, <hr>, <input>, <select>, <spacer>
sizes	<img>, <link>, <source>
span	<col>, <colgroup>
spellcheck	<textarea>
src	<audio>, <bgsound>, <embed>, <frame>, <iframe>, <image>, <img>, <input>, <portal>, <script>, <source>, <track>, <video>
srcdoc	<iframe>
srclang	<track>
srcset	<img>, <source>
standby	<object>
start	
step	<input>
stroke	<svg>
stroke-width	<svg>
summary	<table>

Attribute	Used on
target	<a>, <area>, <base>, <form>, <link>
text	<body>
title	<abbr>, <acronym>, <dfn>, <iframe>, <link>, <style>
topmargin	<body>
truespeed	<marquee>
type	<a>, <area>, <button>, <embed>, <input>, , <link>, <menu>, <menuitem>, <object>, , <param>, <script>, <source>, <spacer>, <style>,
typemustmatch	<object>
usemap	<img>, <input>, <object>
valign	<col>, <colgroup>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>
value	<button>, <data>, <input>, , <meter>, <option>, <param>, <progress>
valuetype	<param>
version	<html>
viewBox	<svg>
vlink	<body>
volume	<bgsound>
vspace	<applet>, <img>, <marquee>, <object>
webkitdirectory	<input>
width	<applet>, <canvas>, <col>, <colgroup>, <embed>, <fencedframe>, <hr>, <iframe>, <img>, <input>, <marquee>, <multicol>, <object>, <pre>, <source>, <spacer>, <svg>, <table>, <td>, <th>, <video>
wrap	<pre>, <textarea>

Attribute	Used on
xmlns	<html>, <math>, <svg>

Attribute: abbr

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<td>	text	HTML 4.01
<th>	text	HTML 4.01

abbr on <td>

Element: <td> (Table data cell) | Since: HTML 4.01

Description

Obsolete on td (valid on th). Abbreviated description.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<td abbr="value">...</td>
```

The same attribute on other elements

<th>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <td>. Full details of the element are in Part 6.

abbr on <th>

Element: <th> (Table header cell) | Since: HTML 4.01

Description

A short alternative label that screen readers may use when reading the header repeatedly.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<th abbr="value">...</th>
```

The same attribute on other elements

<td>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <th>. Full details of the element are in Part 6.

Attribute: accept

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<form>	MIME types	HTML 4.01
<input>	MIME types / extensions	HTML 4.01

accept on <form>

Element: <form> (Form) | Since: HTML 4.01

Description

Obsolete. Use accept on <input type="file"> instead.

Accepted values

MIME types

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<form accept="text/plain">...</form>
```

The same attribute on other elements

<input>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <form>. Full details of the element are in Part 6.

accept on <input>

Element: <input> (Input control) | Since: HTML 4.01

Description

Allowed file types for type=file, for example image/*, .pdf, audio/*.

Accepted values

MIME types / extensions

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input accept="text/plain">
```

The same attribute on other elements

<form>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

Attribute: accept-charset

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<form>	space-separated encodings	HTML 4.01

accept-charset on <form>

Element: <form> (Form) | Since: HTML 4.01

Description

The character encodings the server accepts. Use utf-8.

Accepted values

space-separated encodings

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<form accept-charset="value">...</form>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <form>. Full details of the element are in Part 6.

Attribute: action

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<form>	URL	HTML 2.0
<isindex>	URL	Netscape

action on <form>

Element: <form> (Form) | Since: HTML 2.0

Description

Where to send the data. If omitted, the data is sent to the current page URL.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<form action="https://example.com/page.html">...</form>
```

The same attribute on other elements

<isindex>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <form>. Full details of the element are in Part 6.

action on <isindex>

Element: <isindex> (Search index prompt (obsolete)) | Since: Netscape

Description

Where to send the query (non-standard).

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<isindex action="https://example.com/page.html">
```

The same attribute on other elements

<form>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <isindex>. Full details of the element are in Part 6.

Attribute: align

Accepted by 21 elements. Each use is described on the following pages.

Element	Values	Since
<applet>	left | right | top | middle | bottom	HTML 3.2
<caption>	top | bottom | left | right	HTML 3.2
<col>	left | center | right | justify | char	HTML 4.01
<colgroup>	various	HTML 4.01
	left | center | right | justify	HTML 3.2
<h1>	left | center | right | justify	HTML 3.2
<hr>	left | center | right	HTML 3.2
<iframe>	left | right | top | middle | bottom	HTML 4.01
<img>	top | middle | bottom | left | right	HTML 2.0
<input>	left | right | top | middle | bottom	HTML 3.2
<legend>	left | center | right | top | bottom	HTML 4.01
<object>	various	HTML 4.01 / HTML5 (removed)
<p>	left | center | right | justify	HTML 3.2
<spacer>	-	Netscape
<table>	left | center | right	HTML 3.2
<tbody>	various	HTML 4.01
<td>	left | center | right | justify | char	HTML 3.2
<tfoot>	various	HTML 4.01
<th>	various	HTML 3.2 / 4.01
<thead>	various	HTML 4.01
<tr>	left | center | right | justify | char	HTML 3.2

align on <applet>

Element: <applet> (Java applet (obsolete)) | Since: HTML 3.2

Description

Alignment relative to surrounding text.

Accepted values

left | right | top | middle | bottom

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<applet align="left">...</applet>
```

The same attribute on other elements

<caption>, <col>, <colgroup>, , <h1>, <hr>, <iframe>, <img>, <input>, <legend>, <object>, <p>, <spacer>, <table>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <applet>. Full details of the element are in Part 6.

align on <caption>

Element: <caption> (Table caption) | Since: HTML 3.2

Description

Obsolete. Position of the caption. Use CSS caption-side and text-align.

Accepted values

top | bottom | left | right

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<caption align="top">...</caption>
```

The same attribute on other elements

<applet>, <col>, <colgroup>, , <h1>, <hr>, <iframe>, <img>, <input>, <legend>, <object>, <p>, <spacer>, <table>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <caption>. Full details of the element are in Part 6.

align on <col>

Element: <col> (Table column) | Since: HTML 4.01

Description

Obsolete. Horizontal alignment of the cells. Use CSS text-align.

Accepted values

left | center | right | justify | char

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<col align="left">
```

The same attribute on other elements

<applet>, <caption>, <colgroup>, , <h1>, <hr>, <iframe>, <img>, <input>, <legend>, <object>, <p>, <spacer>, <table>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <col>. Full details of the element are in Part 6.

align on <colgroup>

Element: <colgroup> (Table column group) | Since: HTML 4.01

Description

Obsolete presentational attributes; see <col>.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<colgroup align="various">...</colgroup>
```

The same attribute on other elements

<applet>, <caption>, <col>, , <h1>, <hr>, <iframe>, <img>, <input>, <legend>, <object>, <p>, <spacer>, <table>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <colgroup>. Full details of the element are in Part 6.

align on

Element: (Generic block container) | Since: HTML 3.2

Description

Obsolete. Horizontal alignment of the content. Use CSS text-align or margin.

Accepted values

left | center | right | justify

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<div align="left">...</div>
```

The same attribute on other elements

<applet>, <caption>, <col>, <colgroup>, <h1>, <hr>, <iframe>, <img>, <input>, <legend>, <object>, <p>, <spacer>, <table>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on . Full details of the element are in Part 6.

align on <h1>

Element: <h1> (Headings h1 to h6) | Since: HTML 3.2

Description

Obsolete. Use CSS text-align.

Accepted values

left | center | right | justify

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<h1 align="left">...</h1>
```

The same attribute on other elements

<applet>, <caption>, <col>, <colgroup>, , <hr>, <iframe>, <img>, <input>, <legend>, <object>, <p>, <spacer>, <table>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <h1>. Full details of the element are in Part 6.

align on <hr>

Element: <hr> (Thematic break (horizontal rule)) | Since: HTML 3.2

Description

Obsolete. Alignment of the rule. Use CSS margin.

Accepted values

left | center | right

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<hr align="left">
```

The same attribute on other elements

<applet>, <caption>, <col>, <colgroup>, , <h1>, <iframe>, <img>, <input>, <legend>, <object>, <p>, <spacer>, <table>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <hr>. Full details of the element are in Part 6.

align on <iframe>

Element: <iframe> (Inline frame) | Since: HTML 4.01

Description

Obsolete. Use CSS.

Accepted values

left | right | top | middle | bottom

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<iframe align="left">...</iframe>
```

The same attribute on other elements

<applet>, <caption>, <col>, <colgroup>, , <h1>, <hr>, <img>, <input>, <legend>, <object>, <p>, <spacer>, <table>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <iframe>. Full details of the element are in Part 6.

align on <img>

Element: <img> (Image) | Since: HTML 2.0

Description

Obsolete. Use CSS float or vertical-align.

Accepted values

top | middle | bottom | left | right

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<img align="top">
```

The same attribute on other elements

<applet>, <caption>, <col>, <colgroup>, , <h1>, <hr>, <iframe>, <input>, <legend>, <object>, <p>, <spacer>, <table>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <img>. Full details of the element are in Part 6.

align on <input>

Element: <input> (Input control) | Since: HTML 3.2

Description

Obsolete. Use CSS.

Accepted values

left | right | top | middle | bottom

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input align="left">
```

The same attribute on other elements

<applet>, <caption>, <col>, <colgroup>, , <h1>, <hr>, <iframe>, <img>, <legend>, <object>, <p>, <spacer>, <table>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

align on <legend>

Element: <legend> (Fieldset caption) | Since: HTML 4.01

Description

Obsolete. Use CSS.

Accepted values

left | center | right | top | bottom

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<legend align="left">...</legend>
```

The same attribute on other elements

<applet>, <caption>, <col>, <colgroup>, , <h1>, <hr>, <iframe>, <img>, <input>, <object>, <p>, <spacer>, <table>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <legend>. Full details of the element are in Part 6.

align on <object>

Element: <object> (External object) | Since: HTML 4.01 / HTML5 (removed)

Description

Obsolete attributes from HTML 4.01 plug-in usage or presentational attributes. Use CSS or drop them.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<object align="various">...</object>
```

The same attribute on other elements

<applet>, <caption>, <col>, <colgroup>, , <h1>, <hr>, <iframe>, <img>, <input>, <legend>, <p>, <spacer>, <table>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <object>. Full details of the element are in Part 6.

align on <p>

Element: <p> (Paragraph) | Since: HTML 3.2

Description

Obsolete. Use CSS text-align.

Accepted values

left | center | right | justify

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<p align="left">...</p>
```

The same attribute on other elements

<applet>, <caption>, <col>, <colgroup>, , <h1>, <hr>, <iframe>, <img>, <input>, <legend>, <object>, <spacer>, <table>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <p>. Full details of the element are in Part 6.

align on <spacer>

Element: <spacer> (Spacer (non-standard, obsolete)) | Since: Netscape

Description

For type=block.

Accepted values

-

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<spacer align="-">
```

The same attribute on other elements

<applet>, <caption>, <col>, <colgroup>, , <h1>, <hr>, <iframe>, <img>, <input>, <legend>, <object>, <p>, <table>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <spacer>. Full details of the element are in Part 6.

align on <table>

Element: <table> (Table) | Since: HTML 3.2

Description

Obsolete. Alignment of the table on the page. Use CSS margin.

Accepted values

left | center | right

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<table align="left">...</table>
```

The same attribute on other elements

<applet>, <caption>, <col>, <colgroup>, , <h1>, <hr>, <iframe>, <img>, <input>, <legend>, <object>, <p>, <spacer>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <table>. Full details of the element are in Part 6.

align on <tbody>

Element: <tbody> (Table body) | Since: HTML 4.01

Description

Obsolete presentational attributes. Use CSS.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<tbody align="various">...</tbody>
```

The same attribute on other elements

<applet>, <caption>, <col>, <colgroup>, , <h1>, <hr>, <iframe>, <img>, <input>, <legend>, <object>, <p>, <spacer>, <table>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <tbody>. Full details of the element are in Part 6.

align on <td>

Element: <td> (Table data cell) | Since: HTML 3.2

Description

Obsolete. Use CSS text-align.

Accepted values

left | center | right | justify | char

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<td align="left">...</td>
```

The same attribute on other elements

<applet>, <caption>, <col>, <colgroup>, , <h1>, <hr>, <iframe>, <img>, <input>, <legend>, <object>, <p>, <spacer>, <table>, <tbody>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <td>. Full details of the element are in Part 6.

align on <tfoot>

Element: <tfoot> (Table footer) | Since: HTML 4.01

Description

Obsolete presentational attributes. Use CSS.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<tfoot align="various">...</tfoot>
```

The same attribute on other elements

<applet>, <caption>, <col>, <colgroup>, , <h1>, <hr>, <iframe>, <img>, <input>, <legend>, <object>, <p>, <spacer>, <table>, <tbody>, <td>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <tfoot>. Full details of the element are in Part 6.

align on <th>

Element: <th> (Table header cell) | Since: HTML 3.2 / 4.01

Description

Obsolete presentational attributes. Use CSS.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<th align="various">...</th>
```

The same attribute on other elements

<applet>, <caption>, <col>, <colgroup>, , <h1>, <hr>, <iframe>, <img>, <input>, <legend>, <object>, <p>, <spacer>, <table>, <tbody>, <td>, <tfoot>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <th>. Full details of the element are in Part 6.

align on <thead>

Element: <thead> (Table header) | Since: HTML 4.01

Description

Obsolete presentational attributes. Use CSS.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<thead align="various">...</thead>
```

The same attribute on other elements

<applet>, <caption>, <col>, <colgroup>, , <h1>, <hr>, <iframe>, <img>, <input>, <legend>, <object>, <p>, <spacer>, <table>, <tbody>, <td>, <tfoot>, <th>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <thead>. Full details of the element are in Part 6.

align on <tr>

Element: <tr> (Table row) | Since: HTML 3.2

Description

Obsolete. Use CSS text-align on cells.

Accepted values

left | center | right | justify | char

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<tr align="left">...</tr>
```

The same attribute on other elements

<applet>, <caption>, <col>, <colgroup>, , <h1>, <hr>, <iframe>, <img>, <input>, <legend>, <object>, <p>, <spacer>, <table>, <tbody>, <td>, <tfoot>, <th>, <thead>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <tr>. Full details of the element are in Part 6.

Attribute: alink

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<body>	colour	HTML 3.2

alink on <body>

Element: <body> (Document body) | Since: HTML 3.2

Description

Obsolete. Colour of active (being clicked) links. Use CSS a:active.

Accepted values

colour

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<body alink="#336699">...</body>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <body>. Full details of the element are in Part 6.

Attribute: allow

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<fencedframe>	permissions policy	Experimental
<iframe>	permissions policy	HTML5

allow on <fencedframe>

Element: <fencedframe> (Fenced frame (experimental)) | Since: Experimental

Description

Features allowed inside the frame.

Accepted values

permissions policy

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<fencedframe allow="permissions policy">...</fencedframe>
```

The same attribute on other elements

<iframe>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <fencedframe>. Full details of the element are in Part 6.

allow on <iframe>

Element: <iframe> (Inline frame) | Since: HTML5

Description

Features the frame may use, for example allow="camera; microphone; fullscreen; geolocation; autoplay; picture-in-picture".

Accepted values

permissions policy

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<iframe allow="permissions policy">...</iframe>
```

The same attribute on other elements

<fencedframe>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <iframe>. Full details of the element are in Part 6.

Attribute: allowfullscreen

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<iframe>	boolean	HTML5

allowfullscreen on <iframe>

Element: <iframe> (Inline frame) | Since: HTML5

Description

Legacy form of allow="fullscreen".

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="allowfullscreen" in XHTML style). Never write allowfullscreen="false"; that still counts as present.

```
<iframe allowfullscreen>...</iframe>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <iframe>. Full details of the element are in Part 6.

Attribute: allowpaymentrequest

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<iframe>	boolean	HTML5 (removed)

allowpaymentrequest on <iframe>

Element: <iframe> (Inline frame) | Since: HTML5 (removed)

Description

Obsolete. Use allow="payment".

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="allowpaymentrequest" in XHTML style). Never write allowpaymentrequest="false"; that still counts as present.

```
<iframe allowpaymentrequest>...</iframe>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <iframe>. Full details of the element are in Part 6.

Attribute: alpha

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<input>	boolean	Experimental

alpha on <input>

Element: <input> (Input control) | Since: Experimental

Description

Experimental: allow transparency in type=color.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="alpha" in XHTML style). Never write alpha="false"; that still counts as present.

```
<input alpha>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

Attribute: alt

Accepted by 5 elements. Each use is described on the following pages.

Element	Values	Since
<applet>	text	HTML 3.2
<area>	text	HTML 3.2
<image>	as <img>	-
<img>	text	HTML 2.0
<input>	text	HTML 2.0

alt on <applet>

Element: <applet> (Java applet (obsolete)) | Since: HTML 3.2

Description

Alternative text for browsers without Java.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<applet alt="value">...</applet>
```

The same attribute on other elements

<area>, <image>, <img>, <input>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <applet>. Full

details of the element are in Part 6.

alt on <area>

Element: <area> (Image map area) | Since: HTML 3.2

Description

Alternative text for the area. Required when href is present so that the link has an accessible name.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<area alt="value">
```

The same attribute on other elements

<applet>, <image>, <img>, <input>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <area>. Full details of the element are in Part 6.

alt on <image>

Element: <image> (Image (non-standard alias, obsolete)) | Since: -

Description

Whatever the parser transfers to the <img> it creates.

Accepted values

as <img>

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<image alt="as <img>">
```

The same attribute on other elements

<applet>, <area>, <img>, <input>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <image>. Full details of the element are in Part 6.

alt on <img>

Element: <img> (Image) | Since: HTML 2.0

Description

Text alternative. Describe the content or function of the image. Use alt="" (empty) for purely decorative images so that screen readers skip them. Omitting alt entirely is an error.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<img alt="value">
```

The same attribute on other elements

<applet>, <area>, <image>, <input>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <img>. Full details of the element are in Part 6.

alt on <input>

Element: <input> (Input control) | Since: HTML 2.0

Description

Alternative text for type=image.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input alt="value">
```

The same attribute on other elements

<applet>, <area>, <image>, <img>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

Attribute: archive

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<applet>	comma-separated URLs	HTML 4.01
<object>	various	HTML 4.01 / HTML5 (removed)

archive on <applet>

Element: <applet> (Java applet (obsolete)) | Since: HTML 4.01

Description

JAR archives to preload.

Accepted values

comma-separated URLs

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<applet archive="comma-separated URLs">...</applet>
```

The same attribute on other elements

<object>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <applet>. Full details of the element are in Part 6.

archive on <object>

Element: <object> (External object) | Since: HTML 4.01 / HTML5 (removed)

Description

Obsolete attributes from HTML 4.01 plug-in usage or presentational attributes. Use CSS or drop them.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<object archive="various">...</object>
```

The same attribute on other elements

<applet>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <object>. Full details of the element are in Part 6.

Attribute: aria-label

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<svg>	-	ARIA

aria-label on <svg>

Element: <svg> (Scalable Vector Graphics root) | Since: ARIA

Description

Accessibility name and role for the graphic.

Accepted values

-

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<svg aria-label="-">...</svg>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <svg>. Full details of the element are in Part 6.

Attribute: aria-labelledby

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<svg>	-	ARIA

aria-labelledby on <svg>

Element: <svg> (Scalable Vector Graphics root) | Since: ARIA

Description

Accessibility name and role for the graphic.

Accepted values

-

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<svg aria-labelledby="-">...</svg>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <svg>. Full details of the element are in Part 6.

Attribute: as

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<link>	audio | document | embed | fetch | font | image | object | script | style | track | video | worker	Living Standard

as on <link>

Element: <link> (External resource link) | Since: Living Standard

Description

With rel=preload or modulepreload: the type of content being loaded, so the browser can prioritise it correctly.

Accepted values

audio | document | embed | fetch | font | image | object | script | style | track | video | worker

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<link as="audio">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <link>. Full details of the element are in Part 6.

Attribute: async

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<script>	boolean	HTML5

async on <script>

Element: <script> (Script) | Since: HTML5

Description

Download in parallel, execute as soon as ready, possibly out of order. For independent scripts such as analytics.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="async" in XHTML style). Never write async="false"; that still counts as present.

```
<script async>...</script>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <script>. Full details of the element are in Part 6.

Attribute: attributionsrc

Accepted by 3 elements. Each use is described on the following pages.

Element	Values	Since
<a>	empty or URL	Living Standard
<img>	empty or URL	Experimental
<script>	empty or URL	Experimental

attributionsrc on <a>

Element: <a> (Anchor (hyperlink)) | Since: Living Standard

Description

Experimental: registers an attribution source for the Attribution Reporting API.

Accepted values

empty or URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<a attributionsrc="empty">...</a>
```

The same attribute on other elements

<img>, <script>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <a>. Full details of the element are in Part 6.

attributionsrc on <img>

Element: <img> (Image) | Since: Experimental

Description

Experimental attribution reporting.

Accepted values

empty or URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<img attributionsrc="empty">
```

The same attribute on other elements

<a>, <script>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <img>. Full details of the element are in Part 6.

attributionsrc on <script>

Element: <script> (Script) | Since: Experimental

Description

Experimental attribution reporting.

Accepted values

empty or URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<script attributionsrc="empty">...</script>
```

The same attribute on other elements

<a>, <img>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <script>. Full details of the element are in Part 6.

Attribute: autocomplete

Accepted by 4 elements. Each use is described on the following pages.

Element	Values	Since
<form>	on | off	HTML5
<input>	on | off | token list	HTML5
<select>	token	HTML5
<textarea>	on | off | token	HTML5

autocomplete on <form>

Element: <form> (Form) | Since: HTML5

Description

Whether the browser may autofill controls in this form. Default on.

Accepted values

on | off

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<form autocomplete="on">...</form>
```

The same attribute on other elements

<input>, <select>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <form>. Full details of the element are in Part 6.

autocomplete on <input>

Element: <input> (Input control) | Since: HTML5

Description

Autofill hint: name, email, tel, street-address, postal-code, cc-number, new-password, current-password, one-time-code and more (see Part 9).

Accepted values

on | off | token list

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input autocomplete="on">
```

The same attribute on other elements

<form>, <select>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

autocomplete on <select>

Element: <select> (Drop-down / list box) | Since: HTML5

Description

Autofill hint, for example country, cc-exp-month.

Accepted values

token

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<select autocomplete="token">...</select>
```

The same attribute on other elements

<form>, <input>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <select>. Full details of the element are in Part 6.

autocomplete on <textarea>

Element: <textarea> (Multi-line text input) | Since: HTML5

Description

Autofill hint (street-address, etc.).

Accepted values

on | off | token

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<textarea autocomplete="on">...</textarea>
```

The same attribute on other elements

<form>, <input>, <select>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <textarea>. Full details of the element are in Part 6.

Attribute: autofocus

Accepted by 5 elements. Each use is described on the following pages.

Element	Values	Since
<button>	boolean	HTML5
<input>	boolean	HTML5
<keygen>	-	HTML5
<select>	boolean	HTML5
<textarea>	boolean	HTML5

autofocus on <button>

Element: <button> (Button) | Since: HTML5

Description

Focus this button when the page loads (global in HTML5).

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="autofocus" in XHTML style). Never write autofocus="false"; that still counts as present.

```
<button autofocus>...</button>
```

The same attribute on other elements

<input>, <keygen>, <select>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <button>. Full details of the element are in Part 6.

autofocus on <input>

Element: <input> (Input control) | Since: HTML5

Description

Focus this control on page load. Only one per page.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="autofocus" in XHTML style). Never write autofocus="false"; that still counts as present.

```
<input autofocus>
```

The same attribute on other elements

<button>, <keygen>, <select>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

autofocus on <keygen>

Element: <keygen> (Key-pair generator (obsolete)) | Since: HTML5

Description

As on other controls.

Accepted values

-

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<keygen autofocus="-">
```

The same attribute on other elements

<button>, <input>, <select>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <keygen>. Full details of the element are in Part 6.

autofocus on <select>

Element: <select> (Drop-down / list box) | Since: HTML5

Description

Focus on load.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="autofocus" in XHTML style). Never write autofocus="false"; that still counts as present.

```
<select autofocus>...</select>
```

The same attribute on other elements

<button>, <input>, <keygen>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <select>. Full details of the element are in Part 6.

autofocus on <textarea>

Element: <textarea> (Multi-line text input) | Since: HTML5

Description

Focus on load.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="autofocus" in XHTML style). Never write autofocus="false"; that still counts as present.

```
<textarea autofocus>...</textarea>
```

The same attribute on other elements

<button>, <input>, <keygen>, <select>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <textarea>. Full details of the element are in Part 6.

Attribute: autoplay

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<audio>	boolean	HTML5
<video>	boolean	HTML5

autoplay on <audio>

Element: <audio> (Embedded audio) | Since: HTML5

Description

Start playing as soon as enough data has loaded. Usually blocked unless muted.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="autoplay" in XHTML style). Never write autoplay="false"; that still counts as present.

```
<audio autoplay>...</audio>
```

The same attribute on other elements

<video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <audio>. Full details of the element are in Part 6.

autoplay on <video>

Element: <video> (Embedded video) | Since: HTML5

Description

Start automatically (only reliable with muted).

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="autoplay" in XHTML style). Never write autoplay="false"; that still counts as present.

```
<video autoplay>...</video>
```

The same attribute on other elements

<audio>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <video>. Full details of the element are in Part 6.

Attribute: axis

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<td>	text	HTML 4.01
<th>	various	HTML 3.2 / 4.01

axis on <td>

Element: <td> (Table data cell) | Since: HTML 4.01

Description

Obsolete. Category names.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<td axis="value">...</td>
```

The same attribute on other elements

<th>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <td>. Full details of the element are in Part 6.

axis on <th>

Element: <th> (Table header cell) | Since: HTML 3.2 / 4.01

Description

Obsolete presentational attributes. Use CSS.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<th axis="various">...</th>
```

The same attribute on other elements

<td>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <th>. Full details of the element are in Part 6.

Attribute: background

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<body>	URL	HTML 3.2

background on <body>

Element: <body> (Document body) | Since: HTML 3.2

Description

Obsolete. Background image. Use CSS background-image.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<body background="https://example.com/page.html">...</body>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <body>. Full details of the element are in Part 6.

Attribute: balance

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<bgsound>	-10000 to 10000	IE

balance on <bgsound>

Element: <bgsound> (Background sound (non-standard, obsolete)) | Since: IE

Description

Stereo balance.

Accepted values

-10000 to 10000

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<bgsound balance="-10000 to 10000">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <bgsound>. Full details of the element are in Part 6.

Attribute: behavior

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<marquee>	scroll | slide | alternate	IE

behavior on <marquee>

Element: <marquee> (Scrolling text (obsolete)) | Since: IE

Description

Scrolling style.

Accepted values

scroll | slide | alternate

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<marquee behavior="scroll">...</marquee>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <marquee>. Full details of the element are in Part 6.

Attribute: bgcolor

Accepted by 11 elements. Each use is described on the following pages.

Element	Values	Since
<body>	colour	HTML 3.2
<col>	colour	HTML 4.01
<colgroup>	various	HTML 4.01
<marquee>	colour	IE
<table>	colour	HTML 3.2
<tbody>	various	HTML 4.01
<td>	colour	HTML 3.2
<tfoot>	various	HTML 4.01
<th>	various	HTML 3.2 / 4.01
<thead>	various	HTML 4.01
<tr>	colour	HTML 3.2

bgcolor on <body>

Element: <body> (Document body) | Since: HTML 3.2

Description

Obsolete. Background colour. Use CSS background-color.

Accepted values

colour

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<body bgcolor="#336699">...</body>
```

The same attribute on other elements

<col>, <colgroup>, <marquee>, <table>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <body>. Full details of the element are in Part 6.

bgcolor on <col>

Element: <col> (Table column) | Since: HTML 4.01

Description

Obsolete. Background colour. Use CSS.

Accepted values

colour

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<col bgcolor="#336699">
```

The same attribute on other elements

<body>, <colgroup>, <marquee>, <table>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <col>. Full details of the element are in Part 6.

bgcolor on <colgroup>

Element: <colgroup> (Table column group) | Since: HTML 4.01

Description

Obsolete presentational attributes; see <col>.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<colgroup bgcolor="various">...</colgroup>
```

The same attribute on other elements

<body>, <col>, <marquee>, <table>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <colgroup>. Full details of the element are in Part 6.

bgcolor on <marquee>

Element: <marquee> (Scrolling text (obsolete)) | Since: IE

Description

Background.

Accepted values

colour

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<marquee bgcolor="#336699">...</marquee>
```

The same attribute on other elements

<body>, <col>, <colgroup>, <table>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <marquee>. Full details of the element are in Part 6.

bgcolor on <table>

Element: <table> (Table) | Since: HTML 3.2

Description

Obsolete. Background colour. Use CSS background-color.

Accepted values

colour

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<table bgcolor="#336699">...</table>
```

The same attribute on other elements

<body>, <col>, <colgroup>, <marquee>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <table>. Full details of the element are in Part 6.

bgcolor on <tbody>

Element: <tbody> (Table body) | Since: HTML 4.01

Description

Obsolete presentational attributes. Use CSS.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<tbody bgcolor="various">...</tbody>
```

The same attribute on other elements

<body>, <col>, <colgroup>, <marquee>, <table>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <tbody>. Full details of the element are in Part 6.

bgcolor on <td>

Element: <td> (Table data cell) | Since: HTML 3.2

Description

Obsolete. Use CSS background-color.

Accepted values

colour

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<td bgcolor="#336699">...</td>
```

The same attribute on other elements

<body>, <col>, <colgroup>, <marquee>, <table>, <tbody>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <td>. Full details of the element are in Part 6.

bgcolor on <tfoot>

Element: <tfoot> (Table footer) | Since: HTML 4.01

Description

Obsolete presentational attributes. Use CSS.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<tfoot bgcolor="various">...</tfoot>
```

The same attribute on other elements

<body>, <col>, <colgroup>, <marquee>, <table>, <tbody>, <td>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <tfoot>. Full details of the element are in Part 6.

bgcolor on <th>

Element: <th> (Table header cell) | Since: HTML 3.2 / 4.01

Description

Obsolete presentational attributes. Use CSS.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<th bgcolor="various">...</th>
```

The same attribute on other elements

<body>, <col>, <colgroup>, <marquee>, <table>, <tbody>, <td>, <tfoot>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <th>. Full details of the element are in Part 6.

bgcolor on <thead>

Element: <thead> (Table header) | Since: HTML 4.01

Description

Obsolete presentational attributes. Use CSS.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<thead bgcolor="various">...</thead>
```

The same attribute on other elements

<body>, <col>, <colgroup>, <marquee>, <table>, <tbody>, <td>, <tfoot>, <th>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <thead>. Full details of the element are in Part 6.

bgcolor on <tr>

Element: <tr> (Table row) | Since: HTML 3.2

Description

Obsolete. Use CSS background-color.

Accepted values

colour

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<tr bgcolor="#336699">...</tr>
```

The same attribute on other elements

<body>, <col>, <colgroup>, <marquee>, <table>, <tbody>, <td>, <tfoot>, <th>, <thead>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <tr>. Full details of the element are in Part 6.

Attribute: blocking

Accepted by 3 elements. Each use is described on the following pages.

Element	Values	Since
<link>	render	Living Standard
<script>	render	Living Standard
<style>	render	Living Standard

blocking on <link>

Element: <link> (External resource link) | Since: Living Standard

Description

Block rendering until the resource is loaded (for stylesheets/preloads/expect).

Accepted values

render

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<link blocking="render">
```

The same attribute on other elements

<script>, <style>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <link>. Full details of the element are in Part 6.

blocking on <script>

Element: <script> (Script) | Since: Living Standard

Description

Block rendering until the script runs.

Accepted values

render

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<script blocking="render">...</script>
```

The same attribute on other elements

<link>, <style>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <script>. Full details of the element are in Part 6.

blocking on <style>

Element: <style> (Embedded style sheet) | Since: Living Standard

Description

Block rendering until the style sheet is applied (it does anyway for inline styles).

Accepted values

render

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<style blocking="render">...</style>
```

The same attribute on other elements

<link>, <script>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <style>. Full details of the element are in Part 6.

Attribute: border

Accepted by 4 elements. Each use is described on the following pages.

Element	Values	Since
<frameset>	pixels / 0 | 1	HTML 4.01 / non-standard
<img>	pixels	HTML 3.2
<object>	various	HTML 4.01 / HTML5 (removed)
<table>	pixels	HTML 3.2

border on <frameset>

Element: <frameset> (Frameset (obsolete)) | Since: HTML 4.01 / non-standard

Description

Border appearance.

Accepted values

pixels / 0 | 1

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<frameset border="3">...</frameset>
```

The same attribute on other elements

<img>, <object>, <table>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <frameset>. Full details of the element are in Part 6.

border on <img>

Element: <img> (Image) | Since: HTML 3.2

Description

Obsolete. Border width. Use CSS border.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<img border="3">
```

The same attribute on other elements

<frameset>, <object>, <table>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <img>. Full details of the element are in Part 6.

border on <object>

Element: <object> (External object) | Since: HTML 4.01 / HTML5 (removed)

Description

Obsolete attributes from HTML 4.01 plug-in usage or presentational attributes. Use CSS or drop them.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<object border="various">...</object>
```

The same attribute on other elements

<frameset>, <img>, <table>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <object>. Full details of the element are in Part 6.

border on <table>

Element: <table> (Table) | Since: HTML 3.2

Description

Obsolete. Border width around the table and cells. Use CSS border.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<table border="3">...</table>
```

The same attribute on other elements

<frameset>, <img>, <object>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <table>. Full details of the element are in Part 6.

Attribute: bottommargin

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<body>	pixels	IE/Netscape

bottommargin on <body>

Element: <body> (Document body) | Since: IE/Netscape

Description

Obsolete, non-standard. Page margins. Use CSS margin.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<body bottommargin="3">...</body>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <body>. Full details of the element are in Part 6.

Attribute: capture

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<input>	user | environment	Media Capture spec

capture on <input>

Element: <input> (Input control) | Since: Media Capture spec

Description

For type=file on phones: use the front (user) or back (environment) camera/microphone directly.

Accepted values

user | environment

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input capture="user">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

Attribute: cellpadding

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<table>	pixels	HTML 3.2

cellpadding on <table>

Element: <table> (Table) | Since: HTML 3.2

Description

Obsolete. Space between cell content and cell border. Use CSS padding on td/th.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<table cellpadding="3">...</table>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <table>. Full details of the element are in Part 6.

Attribute: cellspacing

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<table>	pixels	HTML 3.2

cellspacing on <table>

Element: <table> (Table) | Since: HTML 3.2

Description

Obsolete. Space between cells. Use CSS border-spacing or border-collapse.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<table cellspacing="3">...</table>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <table>. Full details of the element are in Part 6.

Attribute: challenge

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<keygen>	text	HTML5

challenge on <keygen>

Element: <keygen> (Key-pair generator (obsolete)) | Since: HTML5

Description

Challenge string.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<keygen challenge="value">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <keygen>. Full details of the element are in Part 6.

Attribute: char

Accepted by 8 elements. Each use is described on the following pages.

Element	Values	Since
<col>	character	HTML 4.01
<colgroup>	various	HTML 4.01
<tbody>	various	HTML 4.01
<td>	character / number	HTML 4.01
<tfoot>	various	HTML 4.01
<th>	various	HTML 3.2 / 4.01
<thead>	various	HTML 4.01
<tr>	character / number	HTML 4.01

char on <col>

Element: <col> (Table column) | Since: HTML 4.01

Description

Obsolete. Alignment character (for align=char).

Accepted values

character

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<col char="character">
```

The same attribute on other elements

<colgroup>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because

accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <col>. Full details of the element are in Part 6.

char on <colgroup>

Element: <colgroup> (Table column group) | Since: HTML 4.01

Description

Obsolete presentational attributes; see <col>.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<colgroup char="various">...</colgroup>
```

The same attribute on other elements

<col>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <colgroup>. Full details of the element are in Part 6.

char on <tbody>

Element: <tbody> (Table body) | Since: HTML 4.01

Description

Obsolete presentational attributes. Use CSS.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<tbody char="various">...</tbody>
```

The same attribute on other elements

<col>, <colgroup>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <tbody>. Full details of the element are in Part 6.

char on <td>

Element: <td> (Table data cell) | Since: HTML 4.01

Description

Obsolete. Character alignment.

Accepted values

character / number

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<td char="3">...</td>
```

The same attribute on other elements

<col>, <colgroup>, <tbody>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <td>. Full details of the element are in Part 6.

char on <tfoot>

Element: <tfoot> (Table footer) | Since: HTML 4.01

Description

Obsolete presentational attributes. Use CSS.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<tfoot char="various">...</tfoot>
```

The same attribute on other elements

<col>, <colgroup>, <tbody>, <td>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <tfoot>. Full details of the element are in Part 6.

char on <th>

Element: <th> (Table header cell) | Since: HTML 3.2 / 4.01

Description

Obsolete presentational attributes. Use CSS.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<th char="various">...</th>
```

The same attribute on other elements

<col>, <colgroup>, <tbody>, <td>, <tfoot>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <th>. Full details of the element are in Part 6.

char on <thead>

Element: <thead> (Table header) | Since: HTML 4.01

Description

Obsolete presentational attributes. Use CSS.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<thead char="various">...</thead>
```

The same attribute on other elements

<col>, <colgroup>, <tbody>, <td>, <tfoot>, <th>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <thead>. Full details of the element are in Part 6.

char on <tr>

Element: <tr> (Table row) | Since: HTML 4.01

Description

Obsolete.

Accepted values

character / number

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<tr char="3">...</tr>
```

The same attribute on other elements

<col>, <colgroup>, <tbody>, <td>, <tfoot>, <th>, <thead>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <tr>. Full details of the element are in Part 6.

Attribute: charoff

Accepted by 8 elements. Each use is described on the following pages.

Element	Values	Since
<col>	number	HTML 4.01
<colgroup>	various	HTML 4.01
<tbody>	various	HTML 4.01
<td>	character / number	HTML 4.01
<tfoot>	various	HTML 4.01
<th>	various	HTML 3.2 / 4.01
<thead>	various	HTML 4.01
<tr>	character / number	HTML 4.01

charoff on <col>

Element: <col> (Table column) | Since: HTML 4.01

Description

Obsolete. Offset from the alignment character.

Accepted values

number

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<col charoff="3">
```

The same attribute on other elements

<colgroup>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because

accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <col>. Full details of the element are in Part 6.

charoff on <colgroup>

Element: <colgroup> (Table column group) | Since: HTML 4.01

Description

Obsolete presentational attributes; see <col>.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<colgroup charoff="various">...</colgroup>
```

The same attribute on other elements

<col>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <colgroup>. Full details of the element are in Part 6.

charoff on <tbody>

Element: <tbody> (Table body) | Since: HTML 4.01

Description

Obsolete presentational attributes. Use CSS.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<tbody charoff="various">...</tbody>
```

The same attribute on other elements

<col>, <colgroup>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <tbody>. Full details of the element are in Part 6.

charoff on <td>

Element: <td> (Table data cell) | Since: HTML 4.01

Description

Obsolete. Character alignment.

Accepted values

character / number

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<td charoff="3">...</td>
```

The same attribute on other elements

<col>, <colgroup>, <tbody>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <td>. Full details of the element are in Part 6.

charoff on <tfoot>

Element: <tfoot> (Table footer) | Since: HTML 4.01

Description

Obsolete presentational attributes. Use CSS.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<tfoot charoff="various">...</tfoot>
```

The same attribute on other elements

<col>, <colgroup>, <tbody>, <td>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <tfoot>. Full details of the element are in Part 6.

charoff on <th>

Element: <th> (Table header cell) | Since: HTML 3.2 / 4.01

Description

Obsolete presentational attributes. Use CSS.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<th charoff="various">...</th>
```

The same attribute on other elements

<col>, <colgroup>, <tbody>, <td>, <tfoot>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <th>. Full details of the element are in Part 6.

charoff on <thead>

Element: <thead> (Table header) | Since: HTML 4.01

Description

Obsolete presentational attributes. Use CSS.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<thead charoff="various">...</thead>
```

The same attribute on other elements

<col>, <colgroup>, <tbody>, <td>, <tfoot>, <th>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <thead>. Full details of the element are in Part 6.

charoff on <tr>

Element: <tr> (Table row) | Since: HTML 4.01

Description

Obsolete.

Accepted values

character / number

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<tr charoff="3">...</tr>
```

The same attribute on other elements

<col>, <colgroup>, <tbody>, <td>, <tfoot>, <th>, <thead>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <tr>. Full details of the element are in Part 6.

Attribute: charset

Accepted by 4 elements. Each use is described on the following pages.

Element	Values	Since
<a>	character encoding	HTML 4.01 (obsolete in HTML5)
<link>	encoding	HTML 4.01
<meta>	utf-8	HTML5
<script>	encoding	HTML 4.01

charset on <a>

Element: <a> (Anchor (hyperlink)) | Since: HTML 4.01 (obsolete in HTML5)

Description

Obsolete. The character encoding of the linked resource. Use the HTTP Content-Type header instead.

Accepted values

character encoding

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<a charset="character encoding">...</a>
```

The same attribute on other elements

<link>, <meta>, <script>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <a>. Full details of the element are in Part 6.

charset on <link>

Element: <link> (External resource link) | Since: HTML 4.01

Description

Obsolete. Character set of the resource.

Accepted values

encoding

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<link charset="encoding">
```

The same attribute on other elements

<a>, <meta>, <script>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <link>. Full details of the element are in Part 6.

charset on <meta>

Element: <meta> (Metadata) | Since: HTML5

Description

Declares the document's character encoding. The only valid value in HTML5 is utf-8 (case-insensitive). Must be in the first 1024 bytes.

Accepted values

utf-8

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<meta charset="utf-8">
```

The same attribute on other elements

<a>, <link>, <script>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <meta>. Full details of the element are in Part 6.

charset on <script>

Element: <script> (Script) | Since: HTML 4.01

Description

Obsolete. Encoding of the script; use UTF-8 for everything.

Accepted values

encoding

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<script charset="encoding">...</script>
```

The same attribute on other elements

<a>, <link>, <meta>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <script>. Full details of the element are in Part 6.

Attribute: checked

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<input>	boolean	HTML 2.0
<menuitem>	various	HTML5 draft

checked on <input>

Element: <input> (Input control) | Since: HTML 2.0

Description

Initially selected (checkbox, radio).

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="checked" in XHTML style). Never write checked="false"; that still counts as present.

```
<input checked>
```

The same attribute on other elements

<menuitem>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

checked on <menuitem>

Element: <menuitem> (Menu item (obsolete)) | Since: HTML5 draft

Description

State and grouping.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<menuitem checked="various">
```

The same attribute on other elements

<input>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <menuitem>. Full details of the element are in Part 6.

Attribute: cite

Accepted by 4 elements. Each use is described on the following pages.

Element	Values	Since
<blockquote>	URL	HTML 4.01
<del>	URL	HTML 4.01
<ins>	URL	HTML 4.01
<q>	URL	HTML 4.01

cite on <blockquote>

Element: <blockquote> (Block quotation) | Since: HTML 4.01

Description

The URL of the source document or message. Not displayed by browsers; readable by scripts and tools.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<blockquote cite="https://example.com/page.html">...</blockquote>
```

The same attribute on other elements

<del>, <ins>, <q>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <blockquote>. Full details of the element are in Part 6.

cite on <del>

Element: <del> (Deleted text) | Since: HTML 4.01

Description

A URL explaining the change, such as a link to a change log or meeting minutes.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<del cite="https://example.com/page.html">...</del>
```

The same attribute on other elements

<blockquote>, <ins>, <q>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <del>. Full details of the element are in Part 6.

cite on <ins>

Element: <ins> (Inserted text) | Since: HTML 4.01

Description

A URL explaining the change.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<ins cite="https://example.com/page.html">...</ins>
```

The same attribute on other elements

<blockquote>, <del>, <q>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <ins>. Full details of the element are in Part 6.

cite on <q>

Element: <q> (Inline quotation) | Since: HTML 4.01

Description

The source of the quotation. Not displayed.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<q cite="https://example.com/page.html">...</q>
```

The same attribute on other elements

<blockquote>, <del>, <ins>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <q>. Full details of the element are in Part 6.

Attribute: classid

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<object>	various	HTML 4.01 / HTML5 (removed)

classid on <object>

Element: <object> (External object) | Since: HTML 4.01 / HTML5 (removed)

Description

Obsolete attributes from HTML 4.01 plug-in usage or presentational attributes. Use CSS or drop them.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<object classid="various">...</object>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <object>. Full details of the element are in Part 6.

Attribute: clear

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
 	left | right | all | none	HTML 3.2

clear on

Element:
 (Line break) | Since: HTML 3.2

Description

Obsolete. Moved the following text below any floated images. Use CSS clear.

Accepted values

left | right | all | none

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<br clear="left">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <br>. Full details of the element are in Part 6.

Attribute: closedby

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<dialog>	any | closerequest | none	Living Standard

closedby on <dialog>

Element: <dialog> (Dialog box) | Since: Living Standard

Description

Which user actions close the dialog: any (Escape, backdrop click, close request), closerequest (Escape only, the default for modal), or none.

Accepted values

any | closerequest | none

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<dialog closedby="any">...</dialog>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <dialog>. Full details of the element are in Part 6.

Attribute: code

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<applet>	class file name	HTML 3.2

code on <applet>

Element: <applet> (Java applet (obsolete)) | Since: HTML 3.2

Description

The name of the compiled applet class file.

Accepted values

class file name

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<applet code="class file name">...</applet>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <applet>. Full details of the element are in Part 6.

Attribute: codebase

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<applet>	URL	HTML 3.2
<object>	various	HTML 4.01 / HTML5 (removed)

codebase on <applet>

Element: <applet> (Java applet (obsolete)) | Since: HTML 3.2

Description

The base URL for the applet's class files.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<applet codebase="https://example.com/page.html">...</applet>
```

The same attribute on other elements

<object>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <applet>. Full details of the element are in Part 6.

codebase on <object>

Element: <object> (External object) | Since: HTML 4.01 / HTML5 (removed)

Description

Obsolete attributes from HTML 4.01 plug-in usage or presentational attributes. Use CSS or drop them.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<object codebase="various">...</object>
```

The same attribute on other elements

<applet>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <object>. Full details of the element are in Part 6.

Attribute: codetype

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<object>	various	HTML 4.01 / HTML5 (removed)

codetype on <object>

Element: <object> (External object) | Since: HTML 4.01 / HTML5 (removed)

Description

Obsolete attributes from HTML 4.01 plug-in usage or presentational attributes. Use CSS or drop them.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<object codetype="various">...</object>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <object>. Full details of the element are in Part 6.

Attribute: color

Accepted by 4 elements. Each use is described on the following pages.

Element	Values	Since
<basefont>	colour	HTML 4.01
<font>	colour name or #rrggbb	HTML 3.2
<hr>	colour	IE
<link>	colour	Non-standard

color on <basefont>

Element: <basefont> (Base font (obsolete)) | Since: HTML 4.01

Description

Default text colour.

Accepted values

colour

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<basefont color="#336699">
```

The same attribute on other elements

<font>, <hr>, <link>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <basefont>. Full details of the element are in Part 6.

color on <font>

Element: <font> (Font (obsolete)) | Since: HTML 3.2

Description

Text colour.

Accepted values

colour name or #rrggbb

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<font color="#336699">...</font>
```

The same attribute on other elements

<basefont>, <hr>, <link>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <font>. Full details of the element are in Part 6.

color on <hr>

Element: <hr> (Thematic break (horizontal rule)) | Since: IE

Description

Obsolete, non-standard. Colour of the rule. Use CSS border-color.

Accepted values

colour

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<hr color="#336699">
```

The same attribute on other elements

<basefont>, <font>, <link>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <hr>. Full details of the element are in Part 6.

color on <link>

Element: <link> (External resource link) | Since: Non-standard

Description

With rel=mask-icon (Safari pinned tab).

Accepted values

colour

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<link color="#336699">
```

The same attribute on other elements

<basefont>, <font>, <hr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <link>. Full details of the element are in Part 6.

Attribute: colorspace

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<input>	limited-srgb | display-p3	Experimental

colorspace on <input>

Element: <input> (Input control) | Since: Experimental

Description

Experimental: colour space for type=color.

Accepted values

limited-srgb | display-p3

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input colorspace="limited-srgb">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

Attribute: cols

Accepted by 3 elements. Each use is described on the following pages.

Element	Values	Since
<frameset>	comma-separated sizes	HTML 4.01
<multicol>	integer	Netscape
<textarea>	positive integer	HTML 2.0

cols on <frameset>

Element: <frameset> (Frameset (obsolete)) | Since: HTML 4.01

Description

Column widths in pixels, percentages or * (remaining space).

Accepted values

comma-separated sizes

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<frameset cols="comma-separated sizes">...</frameset>
```

The same attribute on other elements

<multicol>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <frameset>. Full details of the element are in Part 6.

cols on <multicol>

Element: <multicol> (Multi-column text (non-standard, obsolete)) | Since: Netscape

Description

Number of columns.

Accepted values

integer

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<multicol cols="3">...</multicol>
```

The same attribute on other elements

<frameset>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <multicol>. Full details of the element are in Part 6.

cols on <textarea>

Element: <textarea> (Multi-line text input) | Since: HTML 2.0

Description

Visible width in average characters. Default 20.

Accepted values

positive integer

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<textarea cols="3">...</textarea>
```

The same attribute on other elements

<frameset>, <multicol>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <textarea>. Full details of the element are in Part 6.

Attribute: colspan

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<td>	positive integer	HTML 3.2
<th>	positive integer	HTML 3.2

colspan on <td>

Element: <td> (Table data cell) | Since: HTML 3.2

Description

Number of columns the cell spans. Default 1, maximum 1000.

Accepted values

positive integer

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<td colspan="3">...</td>
```

The same attribute on other elements

<th>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <td>. Full details of the element are in Part 6.

colspan on <th>

Element: <th> (Table header cell) | Since: HTML 3.2

Description

Columns spanned.

Accepted values

positive integer

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<th colspan="3">...</th>
```

The same attribute on other elements

<td>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <th>. Full details of the element are in Part 6.

Attribute: command

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<button>	show-modal | close | request-close | show-popover | hide-popover | toggle-popover | custom	Living Standard
<menuitem>	various	HTML5 draft

command on <button>

Element: <button> (Button) | Since: Living Standard

Description

Experimental: declarative action to perform on commandfor's target.

Accepted values

show-modal | close | request-close | show-popover | hide-popover | toggle-popover | custom

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<button command="show-modal">...</button>
```

The same attribute on other elements

<menuitem>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <button>. Full

details of the element are in Part 6.

command on <menuitem>

Element: <menuitem> (Menu item (obsolete)) | Since: HTML5 draft

Description

State and grouping.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<menuitem command="various">
```

The same attribute on other elements

<button>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <menuitem>. Full details of the element are in Part 6.

Attribute: commandfor

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<button>	element id	Living Standard

commandfor on <button>

Element: <button> (Button) | Since: Living Standard

Description

Experimental: the element the command applies to.

Accepted values

element id

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<button commandfor="element id">...</button>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <button>. Full details of the element are in Part 6.

Attribute: compact

Accepted by 5 elements. Each use is described on the following pages.

Element	Values	Since
<dir>	boolean	HTML 2.0
<dl>	boolean	HTML 2.0
<menu>	boolean	HTML 2.0
	boolean	HTML 2.0
	boolean	HTML 2.0

compact on <dir>

Element: <dir> (Directory list (obsolete)) | Since: HTML 2.0

Description

Obsolete. Render more compactly.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="compact" in XHTML style). Never write compact="false"; that still counts as present.

```
<dir compact>...</dir>
```

The same attribute on other elements

<dl>, <menu>, <ol>, <ul>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <dir>. Full details of the element are in Part 6.

compact on <dl>

Element: <dl> (Description list) | Since: HTML 2.0

Description

Obsolete. Render more compactly.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="compact" in XHTML style). Never write compact="false"; that still counts as present.

```
<dl compact>...</dl>
```

The same attribute on other elements

<dir>, <menu>, <ol>, <ul>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <dl>. Full details of the element are in Part 6.

compact on <menu>

Element: <menu> (Menu (toolbar list)) | Since: HTML 2.0

Description

Obsolete. Compact rendering.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="compact" in XHTML style). Never write compact="false"; that still counts as present.

```
<menu compact>...</menu>
```

The same attribute on other elements

<dir>, <dl>, <ol>, <ul>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <menu>. Full details of the element are in Part 6.

compact on

Element: <ol> (Ordered list) | Since: HTML 2.0

Description

Obsolete. Compact rendering.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="compact" in XHTML style). Never write compact="false"; that still counts as present.

```
<ol compact>...</ol>
```

The same attribute on other elements

<dir>, <dl>, <menu>, <ul>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <ol>. Full details of the element are in Part 6.

compact on

Element: <ul> (Unordered list) | Since: HTML 2.0

Description

Obsolete. Compact rendering.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="compact" in XHTML style). Never write compact="false"; that still counts as present.

```
<ul compact>...</ul>
```

The same attribute on other elements

<dir>, <dl>, <menu>, <ol>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <ul>. Full details of the element are in Part 6.

Attribute: content

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<meta>	text	HTML 2.0

content on <meta>

Element: <meta> (Metadata) | Since: HTML 2.0

Description

The value for name or http-equiv. Required with them.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<meta content="value">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <meta>. Full details of the element are in Part 6.

Attribute: controls

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<audio>	boolean	HTML5
<video>	boolean	HTML5

controls on <audio>

Element: <audio> (Embedded audio) | Since: HTML5

Description

Show the browser's playback controls.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="controls" in XHTML style). Never write controls="false"; that still counts as present.

```
<audio controls>...</audio>
```

The same attribute on other elements

<video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <audio>. Full details of the element are in Part 6.

controls on <video>

Element: <video> (Embedded video) | Since: HTML5

Description

Show built-in controls.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="controls" in XHTML style). Never write controls="false"; that still counts as present.

```
<video controls>...</video>
```

The same attribute on other elements

<audio>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <video>. Full details of the element are in Part 6.

Attribute: controlslist

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<audio>	nodownload | nofullscreen | noremoteplayback	Living Standard
<video>	nodownload | nofullscreen | noremoteplayback	Non-standard

controlslist on <audio>

Element: <audio> (Embedded audio) | Since: Living Standard

Description

Hides specific built-in controls (non-standard, Chromium).

Accepted values

nodownload | nofullscreen | noremoteplayback

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<audio controlslist="nodownload">...</audio>
```

The same attribute on other elements

<video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <audio>. Full details of the element are in Part 6.

controlslist on <video>

Element: <video> (Embedded video) | Since: Non-standard

Description

Hide specific native controls (Chromium).

Accepted values

nodownload | nofullscreen | noremoteplayback

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<video controlslist="nodownload">...</video>
```

The same attribute on other elements

<audio>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <video>. Full details of the element are in Part 6.

Attribute: coords

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<a>	comma-separated numbers	HTML 4.01 (obsolete in HTML5)
<area>	comma-separated numbers	HTML 3.2

coords on <a>

Element: <a> (Anchor (hyperlink)) | Since: HTML 4.01 (obsolete in HTML5)

Description

Obsolete. Coordinates for use with shape in old image maps. Use <area> instead.

Accepted values

comma-separated numbers

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<a coords="3">...</a>
```

The same attribute on other elements

<area>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <a>. Full details of the element are in Part 6.

coords on <area>

Element: <area> (Image map area) | Since: HTML 3.2

Description

The coordinates of the shape in CSS pixels measured from the top-left corner of the image. rect: x1,y1,x2,y2 (top-left and bottom-right). circle: x,y,radius. poly: x1,y1,x2,y2,... (any number of points).

Accepted values

comma-separated numbers

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<area coords="3">
```

The same attribute on other elements

<a>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <area>. Full details of the element are in Part 6.

Attribute: credentialless

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<iframe>	boolean	Experimental

credentialless on <iframe>

Element: <iframe> (Inline frame) | Since: Experimental

Description

Experimental: load the frame in a new, empty cookie/storage context.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="credentialless" in XHTML style). Never write credentialless="false"; that still counts as present.

```
<iframe credentialless>...</iframe>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <iframe>. Full details of the element are in Part 6.

Attribute: crossorigin

Accepted by 5 elements. Each use is described on the following pages.

Element	Values	Since
<audio>	anonymous | use-credentials	HTML5
<img>	anonymous | use-credentials	HTML5
<link>	anonymous | use-credentials	HTML5
<script>	anonymous | use-credentials	HTML5
<video>	anonymous | use-credentials	HTML5

crossorigin on <audio>

Element: <audio> (Embedded audio) | Since: HTML5

Description

How to handle cross-origin requests, needed when the audio will be processed with the Web Audio API or canvas.

Accepted values

anonymous | use-credentials

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<audio crossorigin="anonymous">...</audio>
```

The same attribute on other elements

<img>, <link>, <script>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <audio>. Full details of the element are in Part 6.

crossorigin on <img>

Element: <img> (Image) | Since: HTML5

Description

Load with CORS so the image can be used in canvas without tainting it.

Accepted values

anonymous | use-credentials

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<img crossorigin="anonymous">
```

The same attribute on other elements

<audio>, <link>, <script>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <img>. Full details of the element are in Part 6.

crossorigin on <link>

Element: <link> (External resource link) | Since: HTML5

Description

CORS mode for the request. Required when preloading fonts.

Accepted values

anonymous | use-credentials

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<link crossorigin="anonymous">
```

The same attribute on other elements

<audio>, <img>, <script>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <link>. Full details of the element are in Part 6.

crossorigin on <script>

Element: <script> (Script) | Since: HTML5

Description

CORS setting; needed to get full error details from cross-origin scripts.

Accepted values

anonymous | use-credentials

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<script crossorigin="anonymous">...</script>
```

The same attribute on other elements

<audio>, <img>, <link>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <script>. Full details of the element are in Part 6.

crossorigin on <video>

Element: <video> (Embedded video) | Since: HTML5

Description

CORS mode for the media (needed for canvas processing and cross-origin tracks).

Accepted values

anonymous | use-credentials

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<video crossorigin="anonymous">...</video>
```

The same attribute on other elements

<audio>, <img>, <link>, <script>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <video>. Full details of the element are in Part 6.

Attribute: csp

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<iframe>	policy string	Experimental

csp on <iframe>

Element: <iframe> (Inline frame) | Since: Experimental

Description

Experimental: Content Security Policy to enforce on the embedded document.

Accepted values

policy string

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<iframe csp="policy string">...</iframe>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <iframe>. Full details of the element are in Part 6.

Attribute: data

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<object>	URL	HTML 4.01

data on <object>

Element: <object> (External object) | Since: HTML 4.01

Description

The resource URL. Required (or classid historically).

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<object data="https://example.com/page.html">...</object>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <object>. Full details of the element are in Part 6.

Attribute: datetime

Accepted by 3 elements. Each use is described on the following pages.

Element	Values	Since
<del>	date or date-time string	HTML 4.01
<ins>	date or date-time	HTML 4.01
<time>	date/time string	HTML5

datetime on <del>

Element: <del> (Deleted text) | Since: HTML 4.01

Description

When the change was made, in the format YYYY-MM-DD or YYYY-MM-DDThh:mm:ssZ.

Accepted values

date or date-time string

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<del datetime="date">...</del>
```

The same attribute on other elements

<ins>, <time>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <del>. Full details of the element are in Part 6.

datetime on <ins>

Element: <ins> (Inserted text) | Since: HTML 4.01

Description

When the change was made.

Accepted values

date or date-time

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<ins datetime="date">...</ins>
```

The same attribute on other elements

<del>, <time>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <ins>. Full details of the element are in Part 6.

datetime on <time>

Element: <time> (Date / time) | Since: HTML5

Description

Machine-readable value. Formats: 2026-09-11 (date); 14:30 or 14:30:00 (time); 2026-09-11T14:30 (local date-time); 2026-09-11T14:30Z or 2026-09-11T14:30+02:00 (with time zone); 2026-09 (month); 2026-W37 (week); 2026 (year); 09-11 (yearless date); PT2H30M or 2h 30m (duration).

Accepted values

date/time string

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<time datetime="date">...</time>
```

The same attribute on other elements

<del>, <ins>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <time>. Full details of the element are in Part 6.

Attribute: declare

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<object>	various	HTML 4.01 / HTML5 (removed)

declare on <object>

Element: <object> (External object) | Since: HTML 4.01 / HTML5 (removed)

Description

Obsolete attributes from HTML 4.01 plug-in usage or presentational attributes. Use CSS or drop them.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<object declare="various">...</object>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <object>. Full details of the element are in Part 6.

Attribute: decoding

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<img>	sync | async | auto	Living Standard

decoding on <img>

Element: <img> (Image) | Since: Living Standard

Description

Hint about how to decode the image.

Accepted values

sync | async | auto

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<img decoding="sync">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <img>. Full details of the element are in Part 6.

Attribute: default

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<menuitem>	various	HTML5 draft
<track>	boolean	HTML5

default on <menuitem>

Element: <menuitem> (Menu item (obsolete)) | Since: HTML5 draft

Description

State and grouping.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<menuitem default="various">
```

The same attribute on other elements

<track>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <menuitem>. Full details of the element are in Part 6.

default on <track>

Element: <track> (Text track for media) | Since: HTML5

Description

Enable this track by default (one per kind).

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="default" in XHTML style). Never write default="false"; that still counts as present.

```
<track default>
```

The same attribute on other elements

<menuitem>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <track>. Full details of the element are in Part 6.

Attribute: defer

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<script>	boolean	HTML 4.01

defer on <script>

Element: <script> (Script) | Since: HTML 4.01

Description

Download in parallel, execute after the document has been parsed, in document order. Only for external classic scripts.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="defer" in XHTML style). Never write defer="false"; that still counts as present.

```
<script defer>...</script>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <script>. Full details of the element are in Part 6.

Attribute: dir

Accepted by 3 elements. Each use is described on the following pages.

Element	Values	Since
<bdi>	ltr | rtl | auto	HTML5
<bdo>	ltr | rtl	HTML 4.01
<html>	ltr | rtl | auto	HTML 4.01

dir on <bdi>

Element: <bdi> (Bidirectional isolate) | Since: HTML5

Description

On <bdi> the default is auto, unlike other elements where dir is inherited.

Accepted values

ltr | rtl | auto

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<bdi dir="ltr">...</bdi>
```

The same attribute on other elements

<bdo>, <html>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <bdi>. Full details of the element are in Part 6.

dir on <bdo>

Element: <bdo> (Bidirectional text override) | Since: HTML 4.01

Description

Required. The direction to force.

Accepted values

ltr | rtl

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<bdo dir="ltr">...</bdo>
```

The same attribute on other elements

<bdi>, <html>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <bdo>. Full details of the element are in Part 6.

dir on <html>

Element: <html> (Document root) | Since: HTML 4.01

Description

Text direction of the document.

Accepted values

ltr | rtl | auto

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<html dir="ltr">...</html>
```

The same attribute on other elements

<bdi>, <bdo>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <html>. Full details of the element are in Part 6.

Attribute: direction

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<marquee>	left | right | up | down	IE

direction on <marquee>

Element: <marquee> (Scrolling text (obsolete)) | Since: IE

Description

Scroll direction.

Accepted values

left | right | up | down

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<marquee direction="left">...</marquee>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <marquee>. Full details of the element are in Part 6.

Attribute: dirname

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<input>	text	HTML5
<textarea>	text	HTML5

dirname on <input>

Element: <input> (Input control) | Since: HTML5

Description

Submit the text direction of the value under this name.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input dirname="value">
```

The same attribute on other elements

<textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

dirname on <textarea>

Element: <textarea> (Multi-line text input) | Since: HTML5

Description

Submit text direction.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<textarea dirname="value">...</textarea>
```

The same attribute on other elements

<input>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <textarea>. Full details of the element are in Part 6.

Attribute: disabled

Accepted by 10 elements. Each use is described on the following pages.

Element	Values	Since
<button>	boolean	HTML 4.01
<fieldset>	boolean	HTML 4.01
<input>	boolean	HTML 4.01
<keygen>	-	HTML5
<link>	boolean	HTML5
<menuitem>	various	HTML5 draft
<optgroup>	boolean	HTML 4.01
<option>	boolean	HTML 4.01
<select>	boolean	HTML 4.01
<textarea>	boolean	HTML 4.01

disabled on <button>

Element: <button> (Button) | Since: HTML 4.01

Description

The button cannot be clicked or focused and is not submitted.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="disabled" in XHTML style). Never write disabled="false"; that still counts as present.

```
<button disabled>...</button>
```

The same attribute on other elements

<fieldset>, <input>, <keygen>, <link>, <menuitem>, <optgroup>, <option>, <select>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <button>. Full details of the element are in Part 6.

disabled on <fieldset>

Element: <fieldset> (Form field group) | Since: HTML 4.01

Description

Disables all descendant form controls (except those inside the <legend>).

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="disabled" in XHTML style). Never write disabled="false"; that still counts as present.

```
<fieldset disabled>...</fieldset>
```

The same attribute on other elements

<button>, <input>, <keygen>, <link>, <menuitem>, <optgroup>, <option>, <select>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <fieldset>. Full details of the element are in Part 6.

disabled on <input>

Element: <input> (Input control) | Since: HTML 4.01

Description

Cannot be used or focused and is not submitted.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="disabled" in XHTML style). Never write disabled="false"; that still counts as present.

```
<input disabled>
```

The same attribute on other elements

<button>, <fieldset>, <keygen>, <link>, <menuitem>, <optgroup>, <option>, <select>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

disabled on <keygen>

Element: <keygen> (Key-pair generator (obsolete)) | Since: HTML5

Description

As on other controls.

Accepted values

-

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<keygen disabled="-">
```

The same attribute on other elements

<button>, <fieldset>, <input>, <link>, <menuitem>, <optgroup>, <option>, <select>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <keygen>. Full details of the element are in Part 6.

disabled on <link>

Element: <link> (External resource link) | Since: HTML5

Description

For style sheets: do not apply.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="disabled" in XHTML style). Never write disabled="false"; that still counts as present.

```
<link disabled>
```

The same attribute on other elements

<button>, <fieldset>, <input>, <keygen>, <menuitem>, <optgroup>, <option>, <select>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <link>. Full details of the element are in Part 6.

disabled on <menuitem>

Element: <menuitem> (Menu item (obsolete)) | Since: HTML5 draft

Description

State and grouping.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<menuitem disabled="various">
```

The same attribute on other elements

<button>, <fieldset>, <input>, <keygen>, <link>, <optgroup>, <option>, <select>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <menuitem>. Full details of the element are in Part 6.

disabled on <optgroup>

Element: <optgroup> (Option group) | Since: HTML 4.01

Description

Disables all options in the group.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="disabled" in XHTML style). Never write disabled="false"; that still counts as present.

```
<optgroup disabled>...</optgroup>
```

The same attribute on other elements

<button>, <fieldset>, <input>, <keygen>, <link>, <menuitem>, <option>, <select>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <optgroup>. Full details of the element are in Part 6.

disabled on <option>

Element: <option> (Option) | Since: HTML 4.01

Description

Cannot be selected.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="disabled" in XHTML style). Never write disabled="false"; that still counts as present.

```
<option disabled>...</option>
```

The same attribute on other elements

<button>, <fieldset>, <input>, <keygen>, <link>, <menuitem>, <optgroup>, <select>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <option>. Full details of the element are in Part 6.

disabled on <select>

Element: <select> (Drop-down / list box) | Since: HTML 4.01

Description

The control cannot be used.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="disabled" in XHTML style). Never write disabled="false"; that still counts as present.

```
<select disabled>...</select>
```

The same attribute on other elements

<button>, <fieldset>, <input>, <keygen>, <link>, <menuitem>, <optgroup>, <option>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <select>. Full details of the element are in Part 6.

disabled on <textarea>

Element: <textarea> (Multi-line text input) | Since: HTML 4.01

Description

Cannot be used or submitted.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="disabled" in XHTML style). Never write disabled="false"; that still counts as present.

```
<textarea disabled>...</textarea>
```

The same attribute on other elements

<button>, <fieldset>, <input>, <keygen>, <link>, <menuitem>, <optgroup>, <option>, <select>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <textarea>. Full details of the element are in Part 6.

Attribute: disablepictureinpicture

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<video>	boolean	Living Standard

disablepictureinpicture on <video>

Element: <video> (Embedded video) | Since: Living Standard

Description

Hide the picture-in-picture option.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="disablepictureinpicture" in XHTML style). Never write disablepictureinpicture="false"; that still counts as present.

```
<video disablepictureinpicture>...</video>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <video>. Full details of the element are in Part 6.

Attribute: disableremoteplayback

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<audio>	boolean	Living Standard
<video>	boolean	Living Standard

disableremoteplayback on <audio>

Element: <audio> (Embedded audio) | Since: Living Standard

Description

Disables casting to remote devices.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="disableremoteplayback" in XHTML style). Never write disableremoteplayback="false"; that still counts as present.

```
<audio disableremoteplayback>...</audio>
```

The same attribute on other elements

<video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <audio>. Full details of the element are in Part 6.

disableremoteplayback on <video>

Element: <video> (Embedded video) | Since: Living Standard

Description

Disable casting.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="disableremoteplayback" in XHTML style). Never write disableremoteplayback="false"; that still counts as present.

```
<video disableremoteplayback>...</video>
```

The same attribute on other elements

<audio>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <video>. Full details of the element are in Part 6.

Attribute: display

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<math>	block | inline	MathML

display on <math>

Element: <math> (MathML root) | Since: MathML

Description

Whether the formula is a block on its own line or inline in text.

Accepted values

block | inline

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<math display="block">...</math>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <math>. Full details of the element are in Part 6.

Attribute: download

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<a>	empty or filename	HTML5
<area>	empty or filename	HTML5

download on <a>

Element: <a> (Anchor (hyperlink)) | Since: HTML5

Description

Instructs the browser to download the resource instead of navigating to it. If a value is given it is used as the suggested file name. Only works for same-origin URLs and blob:/data: URLs.

Accepted values

empty or filename

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<a download="empty">...</a>
```

The same attribute on other elements

<area>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <a>. Full details of the element are in Part 6.

download on <area>

Element: <area> (Image map area) | Since: HTML5

Description

Download the resource instead of navigating.

Accepted values

empty or filename

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<area download="empty">
```

The same attribute on other elements

<a>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <area>. Full details of the element are in Part 6.

Attribute: elementtiming

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<img>	text	Living Standard

elementtiming on <img>

Element: <img> (Image) | Since: Living Standard

Description

Marks the image for the Element Timing performance API.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<img elementtiming="value">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <img>. Full details of the element are in Part 6.

Attribute: enctype

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<form>	application/x-www-form-urlencoded | multipart/form-data | text/plain	HTML 2.0

enctype on <form>

Element: <form> (Form) | Since: HTML 2.0

Description

How the data is encoded for post. Use multipart/form-data when the form contains <input type="file">.

Accepted values

application/x-www-form-urlencoded | multipart/form-data | text/plain

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<form enctype="application">...</form>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <form>. Full details of the element are in Part 6.

Attribute: etc.

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<image>	as <img>	-

etc. on <image>

Element: <image> (Image (non-standard alias, obsolete)) | Since: -

Description

Whatever the parser transfers to the <img> it creates.

Accepted values

as <img>

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<image etc.="as <img>">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <image>. Full details of the element are in Part 6.

Attribute: event

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<script>	text	HTML 4.01

event on <script>

Element: <script> (Script) | Since: HTML 4.01

Description

Obsolete. Internet Explorer event binding.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<script event="value">...</script>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <script>. Full details of the element are in Part 6.

Attribute: face

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<basefont>	comma-separated font names	HTML 4.01
<font>	comma-separated font names	HTML 3.2

face on <basefont>

Element: <basefont> (Base font (obsolete)) | Since: HTML 4.01

Description

Default font family.

Accepted values

comma-separated font names

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<basefont face="value">
```

The same attribute on other elements

<font>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <basefont>. Full details of the element are in Part 6.

face on <font>

Element: <font> (Font (obsolete)) | Since: HTML 3.2

Description

Typeface, tried in order.

Accepted values

comma-separated font names

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<font face="value">...</font>
```

The same attribute on other elements

<basefont>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <font>. Full details of the element are in Part 6.

Attribute: fetchpriority

Accepted by 3 elements. Each use is described on the following pages.

Element	Values	Since
<img>	high | low | auto	Living Standard
<link>	high | low | auto	Living Standard
<script>	high | low | auto	Living Standard

fetchpriority on <img>

Element: <img> (Image) | Since: Living Standard

Description

Hint about the download priority; set high on the hero image.

Accepted values

high | low | auto

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<img fetchpriority="high">
```

The same attribute on other elements

<link>, <script>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <img>. Full details

of the element are in Part 6.

fetchpriority on <link>

Element: <link> (External resource link) | Since: Living Standard

Description

Download priority hint.

Accepted values

high | low | auto

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<link fetchpriority="high">
```

The same attribute on other elements

<img>, <script>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <link>. Full details of the element are in Part 6.

fetchpriority on <script>

Element: <script> (Script) | Since: Living Standard

Description

Download priority hint.

Accepted values

high | low | auto

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<script fetchpriority="high">...</script>
```

The same attribute on other elements

<img>, <link>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <script>. Full details of the element are in Part 6.

Attribute: fill

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<svg>	colour / length	SVG

fill on <svg>

Element: <svg> (Scalable Vector Graphics root) | Since: SVG

Description

Presentation attributes for shapes (can also be CSS).

Accepted values

colour / length

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<svg fill="#336699">...</svg>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <svg>. Full details of the element are in Part 6.

Attribute: for

Accepted by 3 elements. Each use is described on the following pages.

Element	Values	Since
<label>	id of a labelable element	HTML 4.01
<output>	space-separated ids	HTML5
<script>	text	HTML 4.01

for on <label>

Element: <label> (Form control label) | Since: HTML 4.01

Description

The control this label describes.

Accepted values

id of a labelable element

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<label for="my-id">...</label>
```

The same attribute on other elements

<output>, <script>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <label>. Full details of the element are in Part 6.

for on <output>

Element: <output> (Calculation or user-action result) | Since: HTML5

Description

The elements that contributed to the calculation.

Accepted values

space-separated ids

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<output for="space-separated ids">...</output>
```

The same attribute on other elements

<label>, <script>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <output>. Full details of the element are in Part 6.

for on <script>

Element: <script> (Script) | Since: HTML 4.01

Description

Obsolete. Internet Explorer event binding.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<script for="value">...</script>
```

The same attribute on other elements

<label>, <output>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <script>. Full details of the element are in Part 6.

Attribute: form

Accepted by 10 elements. Each use is described on the following pages.

Element	Values	Since
<button>	form id	HTML5
<fieldset>	form id	HTML5
<input>	form id	HTML5
<keygen>	-	HTML5
<label>	form id	HTML5 (removed)
<meter>	form id	HTML5
<object>	form id	HTML5
<output>	form id	HTML5
<select>	form id	HTML5
<textarea>	form id	HTML5

form on <button>

Element: <button> (Button) | Since: HTML5

Description

Associates the button with a form elsewhere in the document.

Accepted values

form id

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<button form="form id">...</button>
```

The same attribute on other elements

<fieldset>, <input>, <keygen>, <label>, <meter>, <object>, <output>, <select>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <button>. Full details of the element are in Part 6.

form on <fieldset>

Element: <fieldset> (Form field group) | Since: HTML5

Description

Associates the fieldset with a form elsewhere in the document.

Accepted values

form id

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<fieldset form="form id">...</fieldset>
```

The same attribute on other elements

<button>, <input>, <keygen>, <label>, <meter>, <object>, <output>, <select>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <fieldset>. Full details of the element are in Part 6.

form on <input>

Element: <input> (Input control) | Since: HTML5

Description

Associate with a form anywhere in the document.

Accepted values

form id

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input form="form id">
```

The same attribute on other elements

<button>, <fieldset>, <keygen>, <label>, <meter>, <object>, <output>, <select>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

form on <keygen>

Element: <keygen> (Key-pair generator (obsolete)) | Since: HTML5

Description

As on other controls.

Accepted values

-

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<keygen form="-">
```

The same attribute on other elements

<button>, <fieldset>, <input>, <label>, <meter>, <object>, <output>, <select>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <keygen>. Full details of the element are in Part 6.

form on <label>

Element: <label> (Form control label) | Since: HTML5 (removed)

Description

Obsolete in the Living Standard; was meant to associate the label with a form.

Accepted values

form id

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<label form="form id">...</label>
```

The same attribute on other elements

<button>, <fieldset>, <input>, <keygen>, <meter>, <object>, <output>, <select>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <label>. Full details of the element are in Part 6.

form on <meter>

Element: <meter> (Scalar measurement (gauge)) | Since: HTML5

Description

Associated form (for labelling purposes).

Accepted values

form id

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<meter form="form id">...</meter>
```

The same attribute on other elements

<button>, <fieldset>, <input>, <keygen>, <label>, <object>, <output>, <select>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <meter>. Full details of the element are in Part 6.

form on <object>

Element: <object> (External object) | Since: HTML5

Description

Associated form.

Accepted values

form id

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<object form="form id">...</object>
```

The same attribute on other elements

<button>, <fieldset>, <input>, <keygen>, <label>, <meter>, <output>, <select>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <object>. Full details of the element are in Part 6.

form on <output>

Element: <output> (Calculation or user-action result) | Since: HTML5

Description

Associated form.

Accepted values

form id

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<output form="form id">...</output>
```

The same attribute on other elements

<button>, <fieldset>, <input>, <keygen>, <label>, <meter>, <object>, <select>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <output>. Full details of the element are in Part 6.

form on <select>

Element: <select> (Drop-down / list box) | Since: HTML5

Description

Associated form.

Accepted values

form id

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<select form="form id">...</select>
```

The same attribute on other elements

<button>, <fieldset>, <input>, <keygen>, <label>, <meter>, <object>, <output>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <select>. Full details of the element are in Part 6.

form on <textarea>

Element: <textarea> (Multi-line text input) | Since: HTML5

Description

Associated form.

Accepted values

form id

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<textarea form="form id">...</textarea>
```

The same attribute on other elements

<button>, <fieldset>, <input>, <keygen>, <label>, <meter>, <object>, <output>, <select>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <textarea>. Full details of the element are in Part 6.

Attribute: formaction

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<button>	URL	HTML5
<input>	URL	HTML5

formaction on <button>

Element: <button> (Button) | Since: HTML5

Description

Overrides the form's action for this button.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<button formaction="https://example.com/page.html">...</button>
```

The same attribute on other elements

<input>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <button>. Full details of the element are in Part 6.

formaction on <input>

Element: <input> (Input control) | Since: HTML5

Description

Override the form action (submit, image).

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input formaction="https://example.com/page.html">
```

The same attribute on other elements

<button>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

Attribute: formenctype

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<button>	application/x-www-form-urlencoded | multipart/form-data | text/plain	HTML5
<input>	encoding type	HTML5

formenctype on <button>

Element: <button> (Button) | Since: HTML5

Description

Overrides the form's enctype.

Accepted values

application/x-www-form-urlencoded | multipart/form-data | text/plain

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<button formenctype="application">...</button>
```

The same attribute on other elements

<input>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <button>. Full details of the element are in Part 6.

formenctype on <input>

Element: <input> (Input control) | Since: HTML5

Description

Override the form enctype (submit, image).

Accepted values

encoding type

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input formenctype="encoding type">
```

The same attribute on other elements

<button>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

Attribute: formmethod

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<button>	get | post | dialog	HTML5
<input>	get | post | dialog	HTML5

formmethod on <button>

Element: <button> (Button) | Since: HTML5

Description

Overrides the form's method.

Accepted values

get | post | dialog

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<button formmethod="get">...</button>
```

The same attribute on other elements

<input>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <button>. Full details of the element are in Part 6.

formmethod on <input>

Element: <input> (Input control) | Since: HTML5

Description

Override the form method (submit, image).

Accepted values

get | post | dialog

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input formmethod="get">
```

The same attribute on other elements

<button>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

Attribute: formnovalidate

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<button>	boolean	HTML5
<input>	boolean	HTML5

formnovalidate on <button>

Element: <button> (Button) | Since: HTML5

Description

Skips validation when this button submits.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="formnovalidate" in XHTML style). Never write formnovalidate="false"; that still counts as present.

```
<button formnovalidate>...</button>
```

The same attribute on other elements

<input>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <button>. Full details of the element are in Part 6.

formnovalidate on <input>

Element: <input> (Input control) | Since: HTML5

Description

Skip validation when submitting with this button.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="formnovalidate" in XHTML style). Never write formnovalidate="false"; that still counts as present.

```
<input formnovalidate>
```

The same attribute on other elements

<button>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

Attribute: formtarget

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<button>	_self | _blank | _parent | _top | name	HTML5
<input>	browsing context	HTML5

formtarget on <button>

Element: <button> (Button) | Since: HTML5

Description

Overrides the form's target.

Accepted values

_self | _blank | _parent | _top | name

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<button formtarget="_self">...</button>
```

The same attribute on other elements

<input>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <button>. Full details of the element are in Part 6.

formtarget on <input>

Element: <input> (Input control) | Since: HTML5

Description

Override the form target (submit, image).

Accepted values

browsing context

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input formtarget="browsing context">
```

The same attribute on other elements

<button>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

Attribute: frame

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<table>	void | above | below | hsides | lhs | rhs | vsides | box | border	HTML 4.01

frame on <table>

Element: <table> (Table) | Since: HTML 4.01

Description

Obsolete. Which outer borders to draw. Use CSS border.

Accepted values

void | above | below | hsides | lhs | rhs | vsides | box | border

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<table frame="void">...</table>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <table>. Full details of the element are in Part 6.

Attribute: frameborder

Accepted by 3 elements. Each use is described on the following pages.

Element	Values	Since
<frame>	0 | 1	HTML 4.01
<frameset>	pixels / 0 | 1	HTML 4.01 / non-standard
<iframe>	0 | 1	HTML 4.01

frameborder on <frame>

Element: <frame> (Frame (obsolete)) | Since: HTML 4.01

Description

Whether to draw a border.

Accepted values

0 | 1

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<frame frameborder="0">
```

The same attribute on other elements

<frameset>, <iframe>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <frame>. Full details of the element are in Part 6.

frameborder on <frameset>

Element: <frameset> (Frameset (obsolete)) | Since: HTML 4.01 / non-standard

Description

Border appearance.

Accepted values

pixels / 0 | 1

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<frameset frameborder="3">...</frameset>
```

The same attribute on other elements

<frame>, <iframe>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <frameset>. Full details of the element are in Part 6.

frameborder on <iframe>

Element: <iframe> (Inline frame) | Since: HTML 4.01

Description

Obsolete. Use CSS border.

Accepted values

0 | 1

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<iframe frameborder="0">...</iframe>
```

The same attribute on other elements

<frame>, <frameset>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <iframe>. Full details of the element are in Part 6.

Attribute: framespacing

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<frameset>	pixels / 0 | 1	HTML 4.01 / non-standard

framespacing on <frameset>

Element: <frameset> (Frameset (obsolete)) | Since: HTML 4.01 / non-standard

Description

Border appearance.

Accepted values

pixels / 0 | 1

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<frameset framespacing="3">...</frameset>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <frameset>. Full details of the element are in Part 6.

Attribute: gutter

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<multicol>	pixels	Netscape

gutter on <multicol>

Element: <multicol> (Multi-column text (non-standard, obsolete)) | Since: Netscape

Description

Space between columns.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<multicol gutter="3">...</multicol>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <multicol>. Full details of the element are in Part 6.

Attribute: headers

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<td>	space-separated ids	HTML 4.01
<th>	space-separated ids	HTML 4.01

headers on <td>

Element: <td> (Table data cell) | Since: HTML 4.01

Description

The ids of <th> cells that provide headers for this cell.

Accepted values

space-separated ids

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<td headers="space-separated ids">...</td>
```

The same attribute on other elements

<th>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <td>. Full details of the element are in Part 6.

headers on <th>

Element: <th> (Table header cell) | Since: HTML 4.01

Description

Other header cells that apply to this one (for multi-level headers).

Accepted values

space-separated ids

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<th headers="space-separated ids">...</th>
```

The same attribute on other elements

<td>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <th>. Full details of the element are in Part 6.

Attribute: height

Accepted by 16 elements. Each use is described on the following pages.

Element	Values	Since
<applet>	pixels	HTML 3.2
<canvas>	positive integer	HTML5
<embed>	pixels	Netscape / HTML5
<fencedframe>	pixels	Experimental
<iframe>	pixels	HTML 4.01
<img>	pixels	HTML 3.2
<input>	pixels	HTML5
<marquee>	size	IE
<object>	pixels	HTML 4.01
<source>	pixels	Living Standard
<spacer>	-	Netscape
<svg>	length	SVG
<table>	pixels	Netscape
<td>	pixels	HTML 3.2
<th>	various	HTML 3.2 / 4.01
<video>	pixels	HTML5

height on <applet>

Element: <applet> (Java applet (obsolete)) | Since: HTML 3.2

Description

Size of the applet display area.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<applet height="3">...</applet>
```

The same attribute on other elements

<canvas>, <embed>, <fencedframe>, <iframe>, <img>, <input>, <marquee>, <object>, <source>, <spacer>, <svg>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <applet>. Full details of the element are in Part 6.

height on <canvas>

Element: <canvas> (Graphics canvas) | Since: HTML5

Description

Height of the bitmap in CSS pixels. Default 150.

Accepted values

positive integer

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<canvas height="3">...</canvas>
```

The same attribute on other elements

<applet>, <embed>, <fencedframe>, <iframe>, <img>, <input>, <marquee>, <object>, <source>, <spacer>, <svg>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <canvas>. Full details of the element are in Part 6.

height on <embed>

Element: <embed> (External content) | Since: Netscape / HTML5

Description

Height of the display area.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<embed height="3">
```

The same attribute on other elements

<applet>, <canvas>, <fencedframe>, <iframe>, <img>, <input>, <marquee>, <object>, <source>, <spacer>, <svg>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <embed>. Full details of the element are in Part 6.

height on <fencedframe>

Element: <fencedframe> (Fenced frame (experimental)) | Since: Experimental

Description

Size of the frame.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<fencedframe height="3">...</fencedframe>
```

The same attribute on other elements

<applet>, <canvas>, <embed>, <iframe>, <img>, <input>, <marquee>, <object>, <source>, <spacer>, <svg>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <fencedframe>. Full details of the element are in Part 6.

height on <iframe>

Element: <iframe> (Inline frame) | Since: HTML 4.01

Description

Height of the frame (default 150).

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<iframe height="3">...</iframe>
```

The same attribute on other elements

<applet>, <canvas>, <embed>, <fencedframe>, <img>, <input>, <marquee>, <object>, <source>, <spacer>, <svg>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <iframe>. Full details of the element are in Part 6.

height on <img>

Element: <img> (Image) | Since: HTML 3.2

Description

Intrinsic height.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<img height="3">
```

The same attribute on other elements

<applet>, <canvas>, <embed>, <fencedframe>, <iframe>, <input>, <marquee>, <object>, <source>, <spacer>, <svg>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <img>. Full details of the element are in Part 6.

height on <input>

Element: <input> (Input control) | Since: HTML5

Description

Size of the image for type=image.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input height="3">
```

The same attribute on other elements

<applet>, <canvas>, <embed>, <fencedframe>, <iframe>, <img>, <marquee>, <object>, <source>, <spacer>, <svg>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

height on <marquee>

Element: <marquee> (Scrolling text (obsolete)) | Since: IE

Description

Size.

Accepted values

size

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<marquee height="size">...</marquee>
```

The same attribute on other elements

<applet>, <canvas>, <embed>, <fencedframe>, <iframe>, <img>, <input>, <object>, <source>, <spacer>, <svg>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <marquee>. Full details of the element are in Part 6.

height on <object>

Element: <object> (External object) | Since: HTML 4.01

Description

Display size.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<object height="3">...</object>
```

The same attribute on other elements

<applet>, <canvas>, <embed>, <fencedframe>, <iframe>, <img>, <input>, <marquee>, <source>, <spacer>, <svg>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <object>. Full details of the element are in Part 6.

height on <source>

Element: <source> (Media or image source) | Since: Living Standard

Description

Intrinsic size of the image candidate (picture only).

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<source height="3">
```

The same attribute on other elements

<applet>, <canvas>, <embed>, <fencedframe>, <iframe>, <img>, <input>, <marquee>, <object>, <spacer>, <svg>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <source>. Full details of the element are in Part 6.

height on <spacer>

Element: <spacer> (Spacer (non-standard, obsolete)) | Since: Netscape

Description

For type=block.

Accepted values

-

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<spacer height="-">
```

The same attribute on other elements

<applet>, <canvas>, <embed>, <fencedframe>, <iframe>, <img>, <input>, <marquee>, <object>, <source>, <svg>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <spacer>. Full details of the element are in Part 6.

height on <svg>

Element: <svg> (Scalable Vector Graphics root) | Since: SVG

Description

Displayed size.

Accepted values

length

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<svg height="length">...</svg>
```

The same attribute on other elements

<applet>, <canvas>, <embed>, <fencedframe>, <iframe>, <img>, <input>, <marquee>, <object>, <source>, <spacer>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <svg>. Full details of the element are in Part 6.

height on <table>

Element: <table> (Table) | Since: Netscape

Description

Obsolete, non-standard. Use CSS.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<table height="3">...</table>
```

The same attribute on other elements

<applet>, <canvas>, <embed>, <fencedframe>, <iframe>, <img>, <input>, <marquee>, <object>, <source>, <spacer>, <svg>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <table>. Full details of the element are in Part 6.

height on <td>

Element: <td> (Table data cell) | Since: HTML 3.2

Description

Obsolete. Use CSS height.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<td height="3">...</td>
```

The same attribute on other elements

<applet>, <canvas>, <embed>, <fencedframe>, <iframe>, <img>, <input>, <marquee>, <object>, <source>, <spacer>, <svg>, <table>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <td>. Full details of the element are in Part 6.

height on <th>

Element: <th> (Table header cell) | Since: HTML 3.2 / 4.01

Description

Obsolete presentational attributes. Use CSS.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<th height="various">...</th>
```

The same attribute on other elements

<applet>, <canvas>, <embed>, <fencedframe>, <iframe>, <img>, <input>, <marquee>, <object>, <source>, <spacer>, <svg>, <table>, <td>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <th>. Full details of the element are in Part 6.

height on <video>

Element: <video> (Embedded video) | Since: HTML5

Description

Display size; also prevents layout shift.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<video height="3">...</video>
```

The same attribute on other elements

<applet>, <canvas>, <embed>, <fencedframe>, <iframe>, <img>, <input>, <marquee>, <object>, <source>, <spacer>, <svg>, <table>, <td>, <th>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <video>. Full details of the element are in Part 6.

Attribute: high

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<meter>	number	HTML5

high on <meter>

Element: <meter> (Scalar measurement (gauge)) | Since: HTML5

Description

Lower bound of the 'high' region.

Accepted values

number

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<meter high="3">...</meter>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <meter>. Full details of the element are in Part 6.

Attribute: href

Accepted by 4 elements. Each use is described on the following pages.

Element	Values	Since
<a>	URL	HTML 1
<area>	URL	HTML 3.2
<base>	URL	HTML 2.0
<link>	URL	HTML 2.0

href on <a>

Element: <a> (Anchor (hyperlink)) | Since: HTML 1

Description

The address the link points to. It may be absolute (https://example.com/page), relative (about.html, ../images/photo.jpg), a fragment (#section-2), or a special scheme (mailto:, tel:, sms:, javascript:). Without href the element is not a link.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<a href="https://example.com/page.html">...</a>
```

The same attribute on other elements

<area>, <base>, <link>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <a>. Full details of the element are in Part 6.

href on <area>

Element: <area> (Image map area) | Since: HTML 3.2

Description

The destination of the link.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<area href="https://example.com/page.html">
```

The same attribute on other elements

<a>, <base>, <link>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <area>. Full details of the element are in Part 6.

href on <base>

Element: <base> (Document base URL) | Since: HTML 2.0

Description

The base URL. Relative URLs such as images/logo.png are resolved against it.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<base href="https://example.com/page.html">
```

The same attribute on other elements

<a>, <area>, <link>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <base>. Full details of the element are in Part 6.

href on <link>

Element: <link> (External resource link) | Since: HTML 2.0

Description

The resource URL.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<link href="https://example.com/page.html">
```

The same attribute on other elements

<a>, <area>, <base>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <link>. Full details of the element are in Part 6.

Attribute: hreflang

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<a>	BCP 47 language tag	HTML 4.01
<link>	language tag	HTML 4.01

hreflang on <a>

Element: <a> (Anchor (hyperlink)) | Since: HTML 4.01

Description

The language of the linked document, for example en, ar, fr-CA. Purely advisory.

Accepted values

BCP 47 language tag

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<a hreflang="en">...</a>
```

The same attribute on other elements

<link>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <a>. Full details of the element are in Part 6.

hreflang on <link>

Element: <link> (External resource link) | Since: HTML 4.01

Description

Language of the linked resource (with rel=alternate).

Accepted values

language tag

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<link hreflang="en">
```

The same attribute on other elements

<a>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <link>. Full details of the element are in Part 6.

Attribute: hspace

Accepted by 4 elements. Each use is described on the following pages.

Element	Values	Since
<applet>	pixels	HTML 3.2
<img>	pixels	HTML 3.2
<marquee>	pixels	IE
<object>	various	HTML 4.01 / HTML5 (removed)

hspace on <applet>

Element: <applet> (Java applet (obsolete)) | Since: HTML 3.2

Description

Horizontal and vertical margins.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<applet hspace="3">...</applet>
```

The same attribute on other elements

<img>, <marquee>, <object>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <applet>. Full

details of the element are in Part 6.

hspace on <img>

Element: <img> (Image) | Since: HTML 3.2

Description

Obsolete. Horizontal and vertical margins. Use CSS margin.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<img hspace="3">
```

The same attribute on other elements

<applet>, <marquee>, <object>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <img>. Full details of the element are in Part 6.

hspace on <marquee>

Element: <marquee> (Scrolling text (obsolete)) | Since: IE

Description

Margins.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<marquee hspace="3">...</marquee>
```

The same attribute on other elements

<applet>, <img>, <object>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <marquee>. Full details of the element are in Part 6.

hspace on <object>

Element: <object> (External object) | Since: HTML 4.01 / HTML5 (removed)

Description

Obsolete attributes from HTML 4.01 plug-in usage or presentational attributes. Use CSS or drop them.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<object hspace="various">...</object>
```

The same attribute on other elements

<applet>, <img>, <marquee>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <object>. Full details of the element are in Part 6.

Attribute: http-equiv

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<meta>	content-type | default-style | refresh | content-security-policy | x-ua-compatible	HTML 2.0

http-equiv on <meta>

Element: <meta> (Metadata) | Since: HTML 2.0

Description

Pragma directive that acts like an HTTP header.

Accepted values

content-type | default-style | refresh | content-security-policy | x-ua-compatible

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<meta http-equiv="content-type">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <meta>. Full details of the element are in Part 6.

Attribute: icon

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<menuitem>	URL	HTML5 draft

icon on <menuitem>

Element: <menuitem> (Menu item (obsolete)) | Since: HTML5 draft

Description

Icon image.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<menuitem icon="https://example.com/page.html">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <menuitem>. Full details of the element are in Part 6.

Attribute: id

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<input>	identifier	HTML 4.01

id on <input>

Element: <input> (Input control) | Since: HTML 4.01

Description

Links the control to a <label for="id">.

Accepted values

identifier

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input id="identifier">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

Attribute: imagesizes

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<link>	srcset / sizes syntax	Living Standard

imagesizes on <link>

Element: <link> (External resource link) | Since: Living Standard

Description

With rel=preload as=image: responsive image candidates.

Accepted values

srcset / sizes syntax

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<link imagesizes="srcset">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <link>. Full details of the element are in Part 6.

Attribute: imagesrcset

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<link>	srcset / sizes syntax	Living Standard

imagesrcset on <link>

Element: <link> (External resource link) | Since: Living Standard

Description

With rel=preload as=image: responsive image candidates.

Accepted values

srcset / sizes syntax

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<link imagesrcset="srcset">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <link>. Full details of the element are in Part 6.

Attribute: incremental

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<input>	various	Non-standard

incremental on <input>

Element: <input> (Input control) | Since: Non-standard

Description

Non-standard browser-specific attributes.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input incremental="various">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

Attribute: inputmode

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<input>	none | text | decimal | numeric | tel | search | email | url	HTML5

inputmode on <input>

Element: <input> (Input control) | Since: HTML5

Description

Which virtual keyboard to show on touch devices (global attribute).

Accepted values

none | text | decimal | numeric | tel | search | email | url

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input inputmode="none">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

Attribute: integrity

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<link>	hash	SRI spec
<script>	hash	SRI

integrity on <link>

Element: <link> (External resource link) | Since: SRI spec

Description

Subresource Integrity hash; the browser refuses the file if it does not match.

Accepted values

hash

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<link integrity="hash">
```

The same attribute on other elements

<script>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <link>. Full details of the element are in Part 6.

integrity on <script>

Element: <script> (Script) | Since: SRI

Description

Subresource Integrity hash.

Accepted values

hash

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<script integrity="hash">...</script>
```

The same attribute on other elements

<link>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <script>. Full details of the element are in Part 6.

Attribute: ismap

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<img>	boolean	HTML 2.0

ismap on <img>

Element: <img> (Image) | Since: HTML 2.0

Description

Makes the image a server-side image map; the click coordinates are appended to the link URL. Only valid inside <a href>.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="ismap" in XHTML style). Never write ismap="false"; that still counts as present.

```
<img ismap>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <img>. Full details of the element are in Part 6.

Attribute: itemprop

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<meta>	text	HTML5 microdata

itemprop on <meta>

Element: <meta> (Metadata) | Since: HTML5 microdata

Description

Microdata property name.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<meta itemprop="value">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <meta>. Full details of the element are in Part 6.

Attribute: keytype

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<keygen>	rsa | dsa | ec	HTML5

keytype on <keygen>

Element: <keygen> (Key-pair generator (obsolete)) | Since: HTML5

Description

Key algorithm.

Accepted values

rsa | dsa | ec

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<keygen keytype="rsa">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <keygen>. Full details of the element are in Part 6.

Attribute: kind

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<track>	subtitles | captions | descriptions | chapters | metadata	HTML5

kind on <track>

Element: <track> (Text track for media) | Since: HTML5

Description

The type of track. Default subtitles.

Accepted values

subtitles | captions | descriptions | chapters | metadata

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<track kind="subtitles">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <track>. Full details of the element are in Part 6.

Attribute: label

Accepted by 5 elements. Each use is described on the following pages.

Element	Values	Since
<menu>	text	HTML5 draft (removed)
<menuitem>	text	HTML5 draft
<optgroup>	text	HTML 4.01
<option>	text	HTML 4.01
<track>	text	HTML5

label on <menu>

Element: <menu> (Menu (toolbar list)) | Since: HTML5 draft (removed)

Description

Obsolete. Menu label (context menus).

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<menu label="value">...</menu>
```

The same attribute on other elements

<menuitem>, <optgroup>, <option>, <track>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <menu>. Full details of the element are in Part 6.

label on <menuitem>

Element: <menuitem> (Menu item (obsolete)) | Since: HTML5 draft

Description

Item text.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<menuitem label="value">
```

The same attribute on other elements

<menu>, <optgroup>, <option>, <track>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <menuitem>. Full details of the element are in Part 6.

label on <optgroup>

Element: <optgroup> (Option group) | Since: HTML 4.01

Description

Required. The group heading shown in the list.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<optgroup label="value">...</optgroup>
```

The same attribute on other elements

<menu>, <menuitem>, <option>, <track>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <optgroup>. Full details of the element are in Part 6.

label on <option>

Element: <option> (Option) | Since: HTML 4.01

Description

Alternative label shown instead of the text content (used mainly in datalist).

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<option label="value">...</option>
```

The same attribute on other elements

<menu>, <menuitem>, <optgroup>, <track>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <option>. Full details of the element are in Part 6.

label on <track>

Element: <track> (Text track for media) | Since: HTML5

Description

Human-readable title shown in the track menu.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<track label="value">
```

The same attribute on other elements

<menu>, <menuitem>, <optgroup>, <option>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <track>. Full details of the element are in Part 6.

Attribute: lang

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<html>	BCP 47 language tag	HTML 4.01

lang on <html>

Element: <html> (Document root) | Since: HTML 4.01

Description

The primary language of the document: en, en-GB, ar, ar-EG, fr, de, zh-Hans...

Accepted values

BCP 47 language tag

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<html lang="en">...</html>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <html>. Full details of the element are in Part 6.

Attribute: language

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<script>	text	HTML 3.2

language on <script>

Element: <script> (Script) | Since: HTML 3.2

Description

Obsolete. Scripting language name. Use type or omit.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<script language="value">...</script>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <script>. Full details of the element are in Part 6.

Attribute: leftmargin

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<body>	pixels	IE/Netscape

leftmargin on <body>

Element: <body> (Document body) | Since: IE/Netscape

Description

Obsolete, non-standard. Page margins. Use CSS margin.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<body leftmargin="3">...</body>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <body>. Full details of the element are in Part 6.

Attribute: link

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<body>	colour	HTML 3.2

link on <body>

Element: <body> (Document body) | Since: HTML 3.2

Description

Obsolete. Colour of unvisited links. Use CSS a:link.

Accepted values

colour

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<body link="#336699">...</body>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <body>. Full details of the element are in Part 6.

Attribute: list

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<input>	datalist id	HTML5

list on <input>

Element: <input> (Input control) | Since: HTML5

Description

Links to a <datalist> of suggestions.

Accepted values

datalist id

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input list="datalist id">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

Attribute: loading

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<iframe>	eager | lazy	Living Standard
<img>	eager | lazy	Living Standard

loading on <iframe>

Element: <iframe> (Inline frame) | Since: Living Standard

Description

lazy defers loading until the frame is near the viewport.

Accepted values

eager | lazy

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<iframe loading="eager">...</iframe>
```

The same attribute on other elements

<img>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <iframe>. Full details of the element are in Part 6.

loading on <img>

Element: <img> (Image) | Since: Living Standard

Description

lazy delays loading until the image is near the viewport. Do not lazy-load images visible at page load.

Accepted values

eager | lazy

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<img loading="eager">
```

The same attribute on other elements

<iframe>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <img>. Full details of the element are in Part 6.

Attribute: longdesc

Accepted by 3 elements. Each use is described on the following pages.

Element	Values	Since
<frame>	URL	HTML 4.01
<iframe>	URL	HTML 4.01
<img>	URL	HTML 4.01

longdesc on <frame>

Element: <frame> (Frame (obsolete)) | Since: HTML 4.01

Description

Link to a long description.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<frame longdesc="https://example.com/page.html">
```

The same attribute on other elements

<iframe>, <img>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <frame>. Full details of the element are in Part 6.

longdesc on <iframe>

Element: <iframe> (Inline frame) | Since: HTML 4.01

Description

Obsolete. Link to a long description.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<iframe longdesc="https://example.com/page.html">...</iframe>
```

The same attribute on other elements

<frame>, <img>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <iframe>. Full details of the element are in Part 6.

longdesc on <img>

Element: <img> (Image) | Since: HTML 4.01

Description

Obsolete. Link to a long description. Use a normal link or aria-describedby.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<img longdesc="https://example.com/page.html">
```

The same attribute on other elements

<frame>, <iframe>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <img>. Full details of the element are in Part 6.

Attribute: loop

Accepted by 4 elements. Each use is described on the following pages.

Element	Values	Since
<audio>	boolean	HTML5
<bgsound>	number | infinite	IE
<marquee>	integer | -1	IE
<video>	boolean	HTML5

loop on <audio>

Element: <audio> (Embedded audio) | Since: HTML5

Description

Restart from the beginning when the end is reached.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="loop" in XHTML style). Never write loop="false"; that still counts as present.

```
<audio loop>...</audio>
```

The same attribute on other elements

<bgsound>, <marquee>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <audio>. Full

details of the element are in Part 6.

loop on <bgsound>

Element: <bgsound> (Background sound (non-standard, obsolete)) | Since: IE

Description

Repeat count.

Accepted values

number | infinite

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<bgsound loop="3">
```

The same attribute on other elements

<audio>, <marquee>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <bgsound>. Full details of the element are in Part 6.

loop on <marquee>

Element: <marquee> (Scrolling text (obsolete)) | Since: IE

Description

Repeat count.

Accepted values

integer | -1

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<marquee loop="3">...</marquee>
```

The same attribute on other elements

<audio>, <bgsound>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <marquee>. Full details of the element are in Part 6.

loop on <video>

Element: <video> (Embedded video) | Since: HTML5

Description

Repeat when finished.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="loop" in XHTML style). Never write loop="false"; that still counts as present.

```
<video loop>...</video>
```

The same attribute on other elements

<audio>, <bgsound>, <marquee>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <video>. Full details of the element are in Part 6.

Attribute: low

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<meter>	number	HTML5

low on <meter>

Element: <meter> (Scalar measurement (gauge)) | Since: HTML5

Description

Upper bound of the 'low' region.

Accepted values

number

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<meter low="3">...</meter>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <meter>. Full details of the element are in Part 6.

Attribute: lowsrc

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<img>	URL	Netscape

lowsrc on <img>

Element: <img> (Image) | Since: Netscape

Description

Obsolete, non-standard. Low-quality placeholder loaded first.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<img lowsrc="https://example.com/page.html">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <img>. Full details of the element are in Part 6.

Attribute: manifest

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<html>	URL	HTML5 (removed)

manifest on <html>

Element: <html> (Document root) | Since: HTML5 (removed)

Description

Obsolete. Application cache manifest for offline pages. Replaced by service workers.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<html manifest="https://example.com/page.html">...</html>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <html>. Full details of the element are in Part 6.

Attribute: marginheight

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<frame>	pixels	HTML 4.01
<iframe>	pixels	HTML 4.01

marginheight on <frame>

Element: <frame> (Frame (obsolete)) | Since: HTML 4.01

Description

Margins inside the frame.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<frame marginheight="3">
```

The same attribute on other elements

<iframe>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <frame>. Full details of the element are in Part 6.

marginheight on <iframe>

Element: <iframe> (Inline frame) | Since: HTML 4.01

Description

Obsolete. Use CSS in the framed document.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<iframe marginheight="3">...</iframe>
```

The same attribute on other elements

<frame>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <iframe>. Full details of the element are in Part 6.

Attribute: marginwidth

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<frame>	pixels	HTML 4.01
<iframe>	pixels	HTML 4.01

marginwidth on <frame>

Element: <frame> (Frame (obsolete)) | Since: HTML 4.01

Description

Margins inside the frame.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<frame marginwidth="3">
```

The same attribute on other elements

<iframe>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <frame>. Full details of the element are in Part 6.

marginwidth on <iframe>

Element: <iframe> (Inline frame) | Since: HTML 4.01

Description

Obsolete. Use CSS in the framed document.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<iframe marginwidth="3">...</iframe>
```

The same attribute on other elements

<frame>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <iframe>. Full details of the element are in Part 6.

Attribute: max

Accepted by 3 elements. Each use is described on the following pages.

Element	Values	Since
<input>	number or date	HTML5
<meter>	number	HTML5
<progress>	number	HTML5

max on <input>

Element: <input> (Input control) | Since: HTML5

Description

Maximum value.

Accepted values

number or date

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input max="3">
```

The same attribute on other elements

<meter>, <progress>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

max on <meter>

Element: <meter> (Scalar measurement (gauge)) | Since: HTML5

Description

Upper bound. Default 1.

Accepted values

number

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<meter max="3">...</meter>
```

The same attribute on other elements

<input>, <progress>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <meter>. Full details of the element are in Part 6.

max on <progress>

Element: <progress> (Progress indicator) | Since: HTML5

Description

The total amount of work. Default 1.

Accepted values

number

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<progress max="3">...</progress>
```

The same attribute on other elements

<input>, <meter>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <progress>. Full details of the element are in Part 6.

Attribute: maxlength

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<input>	integer	HTML 2.0
<textarea>	integer	HTML5

maxlength on <input>

Element: <input> (Input control) | Since: HTML 2.0

Description

Maximum number of characters (text-like types).

Accepted values

integer

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input maxlength="3">
```

The same attribute on other elements

<textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

maxlength on <textarea>

Element: <textarea> (Multi-line text input) | Since: HTML5

Description

Maximum characters.

Accepted values

integer

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<textarea maxlength="3">...</textarea>
```

The same attribute on other elements

<input>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <textarea>. Full details of the element are in Part 6.

Attribute: media

Accepted by 4 elements. Each use is described on the following pages.

Element	Values	Since
<link>	media query	HTML 4.01
<meta>	media query	Living Standard
<source>	media query	HTML5
<style>	media query	HTML 4.01

media on <link>

Element: <link> (External resource link) | Since: HTML 4.01

Description

Apply the style sheet only when the query matches: screen, print, (max-width: 600px), (prefers-color-scheme: dark).

Accepted values

media query

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<link media="media query">
```

The same attribute on other elements

<meta>, <source>, <style>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <link>. Full details

of the element are in Part 6.

media on <meta>

Element: <meta> (Metadata) | Since: Living Standard

Description

With name=theme-color: apply only when the query matches.

Accepted values

media query

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<meta media="media query">
```

The same attribute on other elements

<link>, <source>, <style>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <meta>. Full details of the element are in Part 6.

media on <source>

Element: <source> (Media or image source) | Since: HTML5

Description

Use this source only when the query matches. Valid in picture and video (audio ignores it in most browsers).

Accepted values

media query

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<source media="media query">
```

The same attribute on other elements

<link>, <meta>, <style>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <source>. Full details of the element are in Part 6.

media on <style>

Element: <style> (Embedded style sheet) | Since: HTML 4.01

Description

Apply only when the query matches, for example print or (max-width: 600px). Default all.

Accepted values

media query

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<style media="media query">...</style>
```

The same attribute on other elements

<link>, <meta>, <source>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <style>. Full details of the element are in Part 6.

Attribute: method

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<form>	get | post | dialog	HTML 2.0

method on <form>

Element: <form> (Form) | Since: HTML 2.0

Description

The HTTP method. get puts data in the URL; post sends it in the body; dialog closes the enclosing <dialog>.

Accepted values

get | post | dialog

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<form method="get">...</form>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <form>. Full details of the element are in Part 6.

Attribute: min

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<input>	number or date	HTML5
<meter>	number	HTML5

min on <input>

Element: <input> (Input control) | Since: HTML5

Description

Minimum value (number, range, date/time types).

Accepted values

number or date

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input min="3">
```

The same attribute on other elements

<meter>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

min on <meter>

Element: <meter> (Scalar measurement (gauge)) | Since: HTML5

Description

Lower bound of the range. Default 0.

Accepted values

number

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<meter min="3">...</meter>
```

The same attribute on other elements

<input>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <meter>. Full details of the element are in Part 6.

Attribute: minlength

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<input>	integer	HTML5
<textarea>	integer	HTML5

minlength on <input>

Element: <input> (Input control) | Since: HTML5

Description

Minimum number of characters.

Accepted values

integer

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input minlength="3">
```

The same attribute on other elements

<textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

minlength on <textarea>

Element: <textarea> (Multi-line text input) | Since: HTML5

Description

Minimum characters.

Accepted values

integer

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<textarea minlength="3">...</textarea>
```

The same attribute on other elements

<input>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <textarea>. Full details of the element are in Part 6.

Attribute: moz-opaque

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<canvas>	boolean	Non-standard

moz-opaque on <canvas>

Element: <canvas> (Graphics canvas) | Since: Non-standard

Description

Firefox only: hints that there is no transparency, for faster rendering.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="moz-opaque" in XHTML style). Never write moz-opaque="false"; that still counts as present.

```
<canvas moz-opaque>...</canvas>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <canvas>. Full details of the element are in Part 6.

Attribute: mozactionhint

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<input>	various	Non-standard

mozactionhint on <input>

Element: <input> (Input control) | Since: Non-standard

Description

Non-standard browser-specific attributes.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input mozactionhint="various">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

Attribute: multiple

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<input>	boolean	HTML5
<select>	boolean	HTML 2.0

multiple on <input>

Element: <input> (Input control) | Since: HTML5

Description

Allow several values (email: comma-separated; file: several files).

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="multiple" in XHTML style). Never write multiple="false"; that still counts as present.

```
<input multiple>
```

The same attribute on other elements

<select>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

multiple on <select>

Element: <select> (Drop-down / list box) | Since: HTML 2.0

Description

Allow several options to be selected (Ctrl/Cmd-click).

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="multiple" in XHTML style). Never write multiple="false"; that still counts as present.

```
<select multiple>...</select>
```

The same attribute on other elements

<input>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <select>. Full details of the element are in Part 6.

Attribute: muted

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<audio>	boolean	HTML5
<video>	boolean	HTML5

muted on <audio>

Element: <audio> (Embedded audio) | Since: HTML5

Description

Start with the sound muted.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="muted" in XHTML style). Never write muted="false"; that still counts as present.

```
<audio muted>...</audio>
```

The same attribute on other elements

<video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <audio>. Full details of the element are in Part 6.

muted on <video>

Element: <video> (Embedded video) | Since: HTML5

Description

Start muted.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="muted" in XHTML style). Never write muted="false"; that still counts as present.

```
<video muted>...</video>
```

The same attribute on other elements

<audio>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <video>. Full details of the element are in Part 6.

Attribute: n

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<nextid>	Text (anchor name)	HTML 1

n on <nextid>

Element: <nextid> (Next identifier (HTML 1 editor hint)) | Since: HTML 1

Description

The next anchor name the editor should generate.

Accepted values

Text (anchor name)

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<nextid n="value">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <nextid>. Full details of the element are in Part 6.

Attribute: name

Accepted by 19 elements. Each use is described on the following pages.

Element	Values	Since
<a>	text	HTML 1 (obsolete in HTML5)
<applet>	text	HTML 3.2
<button>	text	HTML 4.01
<details>	text	Living Standard
<fieldset>	text	HTML5
<form>	text	HTML 2.0
<frame>	text	HTML 4.01
<iframe>	text	HTML 4.01
<img>	text	HTML 4.01
<input>	text	HTML 2.0
<keygen>	text	HTML5
<map>	text	HTML 3.2
<meta>	metadata name	HTML 2.0
<object>	text	HTML 4.01
<output>	text	HTML5
<param>	text	HTML 3.2
<select>	text	HTML 2.0
<slot>	text	DOM
<textarea>	text	HTML 2.0

name on <a>

Element: <a> (Anchor (hyperlink)) | Since: HTML 1 (obsolete in HTML5)

Description

Obsolete. Defined a named anchor that could be linked to with #name. Use id instead.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<a name="value">...</a>
```

The same attribute on other elements

<applet>, <button>, <details>, <fieldset>, <form>, <frame>, <iframe>, <img>, <input>, <keygen>, <map>, <meta>, <object>, <output>, <param>, <select>, <slot>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <a>. Full details of the element are in Part 6.

name on <applet>

Element: <applet> (Java applet (obsolete)) | Since: HTML 3.2

Description

A name so that applets on the same page can find each other.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<applet name="value">...</applet>
```

The same attribute on other elements

<a>, <button>, <details>, <fieldset>, <form>, <frame>, <iframe>, <img>, <input>, <keygen>, <map>, <meta>, <object>, <output>, <param>, <select>, <slot>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <applet>. Full details of the element are in Part 6.

name on <button>

Element: <button> (Button) | Since: HTML 4.01

Description

The name sent with the form data when this button submits the form.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<button name="value">...</button>
```

The same attribute on other elements

<a>, <applet>, <details>, <fieldset>, <form>, <frame>, <iframe>, <img>, <input>, <keygen>, <map>, <meta>, <object>, <output>, <param>, <select>, <slot>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <button>. Full details of the element are in Part 6.

name on <details>

Element: <details> (Disclosure widget) | Since: Living Standard

Description

Groups details elements so that only one in the group can be open at a time.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<details name="value">...</details>
```

The same attribute on other elements

<a>, <applet>, <button>, <fieldset>, <form>, <frame>, <iframe>, <img>, <input>, <keygen>, <map>, <meta>, <object>, <output>, <param>, <select>, <slot>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <details>. Full details of the element are in Part 6.

name on <fieldset>

Element: <fieldset> (Form field group) | Since: HTML5

Description

The name of the group, accessible from the form's elements collection.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<fieldset name="value">...</fieldset>
```

The same attribute on other elements

<a>, <applet>, <button>, <details>, <form>, <frame>, <iframe>, <img>, <input>, <keygen>, <map>, <meta>, <object>, <output>, <param>, <select>, <slot>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <fieldset>. Full details of the element are in Part 6.

name on <form>

Element: <form> (Form) | Since: HTML 2.0

Description

A name for the form, used by scripts (document.forms.name). Must be unique among forms.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<form name="value">...</form>
```

The same attribute on other elements

<a>, <applet>, <button>, <details>, <fieldset>, <frame>, <iframe>, <img>, <input>, <keygen>, <map>, <meta>, <object>, <output>, <param>, <select>, <slot>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <form>. Full details of the element are in Part 6.

name on <frame>

Element: <frame> (Frame (obsolete)) | Since: HTML 4.01

Description

Name used as a link target.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<frame name="value">
```

The same attribute on other elements

<a>, <applet>, <button>, <details>, <fieldset>, <form>, <iframe>, <img>, <input>, <keygen>, <map>, <meta>, <object>, <output>, <param>, <select>, <slot>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <frame>. Full details of the element are in Part 6.

name on <iframe>

Element: <iframe> (Inline frame) | Since: HTML 4.01

Description

A name that can be used as the target of links and forms.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<iframe name="value">...</iframe>
```

The same attribute on other elements

<a>, <applet>, <button>, <details>, <fieldset>, <form>, <frame>, <img>, <input>, <keygen>, <map>, <meta>, <object>, <output>, <param>, <select>, <slot>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <iframe>. Full details of the element are in Part 6.

name on <img>

Element: <img> (Image) | Since: HTML 4.01

Description

Obsolete. Use id.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<img name="value">
```

The same attribute on other elements

<a>, <applet>, <button>, <details>, <fieldset>, <form>, <frame>, <iframe>, <input>, <keygen>, <map>, <meta>, <object>, <output>, <param>, <select>, <slot>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <img>. Full details of the element are in Part 6.

name on <input>

Element: <input> (Input control) | Since: HTML 2.0

Description

The name under which the value is submitted. Without it the control is not submitted. Radio buttons with the same name form a group.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input name="value">
```

The same attribute on other elements

<a>, <applet>, <button>, <details>, <fieldset>, <form>, <frame>, <iframe>, <img>, <keygen>, <map>, <meta>, <object>, <output>, <param>, <select>, <slot>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

name on <keygen>

Element: <keygen> (Key-pair generator (obsolete)) | Since: HTML5

Description

Form field name.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<keygen name="value">
```

The same attribute on other elements

<a>, <applet>, <button>, <details>, <fieldset>, <form>, <frame>, <iframe>, <img>, <input>, <map>, <meta>, <object>, <output>, <param>, <select>, <slot>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <keygen>. Full details of the element are in Part 6.

name on <map>

Element: <map> (Image map) | Since: HTML 3.2

Description

Required. The map's name, without #, unique among maps. If id is also given it must have the same value.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<map name="value">...</map>
```

The same attribute on other elements

<a>, <applet>, <button>, <details>, <fieldset>, <form>, <frame>, <iframe>, <img>, <input>, <keygen>, <meta>, <object>, <output>, <param>, <select>, <slot>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <map>. Full details of the element are in Part 6.

name on <meta>

Element: <meta> (Metadata) | Since: HTML 2.0

Description

The kind of metadata: application-name, author, description, generator, keywords, referrer, theme-color, color-scheme, viewport, robots, googlebot, creator, publisher, and more.

Accepted values

metadata name

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<meta name="metadata name">
```

The same attribute on other elements

<a>, <applet>, <button>, <details>, <fieldset>, <form>, <frame>, <iframe>, <img>, <input>, <keygen>, <map>, <object>, <output>, <param>, <select>, <slot>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <meta>. Full details of the element are in Part 6.

name on <object>

Element: <object> (External object) | Since: HTML 4.01

Description

Name of the browsing context (for use as a target).

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<object name="value">...</object>
```

The same attribute on other elements

<a>, <applet>, <button>, <details>, <fieldset>, <form>, <frame>, <iframe>, <img>, <input>, <keygen>, <map>, <meta>, <output>, <param>, <select>, <slot>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <object>. Full details of the element are in Part 6.

name on <output>

Element: <output> (Calculation or user-action result) | Since: HTML5

Description

Name of the output (not submitted with the form).

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<output name="value">...</output>
```

The same attribute on other elements

<a>, <applet>, <button>, <details>, <fieldset>, <form>, <frame>, <iframe>, <img>, <input>, <keygen>, <map>, <meta>, <object>, <param>, <select>, <slot>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <output>. Full details of the element are in Part 6.

name on <param>

Element: <param> (Object parameter (deprecated)) | Since: HTML 3.2

Description

The parameter name.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<param name="value">
```

The same attribute on other elements

<a>, <applet>, <button>, <details>, <fieldset>, <form>, <frame>, <iframe>, <img>, <input>, <keygen>, <map>, <meta>, <object>, <output>, <select>, <slot>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <param>. Full details of the element are in Part 6.

name on <select>

Element: <select> (Drop-down / list box) | Since: HTML 2.0

Description

Name submitted with the form.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<select name="value">...</select>
```

The same attribute on other elements

<a>, <applet>, <button>, <details>, <fieldset>, <form>, <frame>, <iframe>, <img>, <input>, <keygen>, <map>, <meta>, <object>, <output>, <param>, <slot>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <select>. Full details of the element are in Part 6.

name on <slot>

Element: <slot> (Shadow DOM slot) | Since: DOM

Description

The slot's name. Children with slot="name" are placed here. Omit for the default slot.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<slot name="value">...</slot>
```

The same attribute on other elements

<a>, <applet>, <button>, <details>, <fieldset>, <form>, <frame>, <iframe>, <img>, <input>, <keygen>, <map>, <meta>, <object>, <output>, <param>, <select>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <slot>. Full details of the element are in Part 6.

name on <textarea>

Element: <textarea> (Multi-line text input) | Since: HTML 2.0

Description

Name submitted with the form.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<textarea name="value">...</textarea>
```

The same attribute on other elements

<a>, <applet>, <button>, <details>, <fieldset>, <form>, <frame>, <iframe>, <img>, <input>, <keygen>, <map>, <meta>, <object>, <output>, <param>, <select>, <slot>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <textarea>. Full details of the element are in Part 6.

Attribute: nohref

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<area>	boolean	HTML 3.2 (obsolete)

nohref on <area>

Element: <area> (Image map area) | Since: HTML 3.2 (obsolete)

Description

Obsolete. Indicated the area had no link. Simply omit href instead.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="nohref" in XHTML style). Never write nohref="false"; that still counts as present.

```
<area nohref>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <area>. Full details of the element are in Part 6.

Attribute: nomodule

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<script>	boolean	HTML5

nomodule on <script>

Element: <script> (Script) | Since: HTML5

Description

Do not run in browsers that support modules; used to provide fallbacks for old browsers.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="nomodule" in XHTML style). Never write nomodule="false"; that still counts as present.

```
<script nomodule>...</script>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <script>. Full details of the element are in Part 6.

Attribute: nonce

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<script>	text	CSP
<style>	text	CSP

nonce on <script>

Element: <script> (Script) | Since: CSP

Description

Cryptographic nonce for Content Security Policy (global attribute).

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<script nonce="value">...</script>
```

The same attribute on other elements

<style>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <script>. Full details of the element are in Part 6.

nonce on <style>

Element: <style> (Embedded style sheet) | Since: CSP

Description

CSP nonce (global).

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<style nonce="value">...</style>
```

The same attribute on other elements

<script>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <style>. Full details of the element are in Part 6.

Attribute: noresize

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<frame>	boolean	HTML 4.01

noresize on <frame>

Element: <frame> (Frame (obsolete)) | Since: HTML 4.01

Description

User cannot resize the frame.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="noresize" in XHTML style). Never write noresize="false"; that still counts as present.

```
<frame noresize>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <frame>. Full details of the element are in Part 6.

Attribute: noshade

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<hr>	boolean	HTML 3.2

noshade on <hr>

Element: <hr> (Thematic break (horizontal rule)) | Since: HTML 3.2

Description

Obsolete. Draw a solid line instead of a 3D groove. Use CSS.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="noshade" in XHTML style). Never write noshade="false"; that still counts as present.

```
<hr noshade>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <hr>. Full details of the element are in Part 6.

Attribute: novalidate

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<form>	boolean	HTML5

novalidate on <form>

Element: <form> (Form) | Since: HTML5

Description

Do not validate the form on submission.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="novalidate" in XHTML style). Never write novalidate="false"; that still counts as present.

```
<form novalidate>...</form>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <form>. Full details of the element are in Part 6.

Attribute: nowrap

Accepted by 3 elements. Each use is described on the following pages.

Element	Values	Since
<dd>	yes | no	IE
<td>	boolean	HTML 3.2
<th>	various	HTML 3.2 / 4.01

nowrap on <dd>

Element: <dd> (Description details) | Since: IE

Description

Obsolete, non-standard. Prevented wrapping.

Accepted values

yes | no

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<dd nowrap="yes">...</dd>
```

The same attribute on other elements

<td>, <th>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <dd>. Full details of the element are in Part 6.

nowrap on <td>

Element: <td> (Table data cell) | Since: HTML 3.2

Description

Obsolete. Use CSS white-space: nowrap.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="nowrap" in XHTML style). Never write nowrap="false"; that still counts as present.

```
<td nowrap>...</td>
```

The same attribute on other elements

<dd>, <th>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <td>. Full details of the element are in Part 6.

nowrap on <th>

Element: <th> (Table header cell) | Since: HTML 3.2 / 4.01

Description

Obsolete presentational attributes. Use CSS.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<th nowrap="various">...</th>
```

The same attribute on other elements

<dd>, <td>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <th>. Full details of the element are in Part 6.

Attribute: object

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<applet>	file name	HTML 4.01

object on <applet>

Element: <applet> (Java applet (obsolete)) | Since: HTML 4.01

Description

A serialised applet file.

Accepted values

file name

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<applet object="file name">...</applet>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <applet>. Full details of the element are in Part 6.

Attribute: onbeforeunload

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<body>	script	HTML5

onbeforeunload on <body>

Element: <body> (Document body) | Since: HTML5

Description

Fired when the user is about to leave; can prompt for confirmation.

Accepted values

script

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<body onbeforeunload="script">...</body>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <body>. Full details of the element are in Part 6.

Attribute: onhashchange

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<body>	script	HTML5

onhashchange on <body>

Element: <body> (Document body) | Since: HTML5

Description

Fired when the URL fragment (#...) changes.

Accepted values

script

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<body onhashchange="script">...</body>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <body>. Full details of the element are in Part 6.

Attribute: onlanguagechange

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<body>	script	HTML5

onlanguagechange on <body>

Element: <body> (Document body) | Since: HTML5

Description

Fired when the preferred language changes.

Accepted values

script

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<body onlanguagechange="script">...</body>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <body>. Full details of the element are in Part 6.

Attribute: onload

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<body>	script	HTML 4.01

onload on <body>

Element: <body> (Document body) | Since: HTML 4.01

Description

Fired when the whole page, including images, has loaded.

Accepted values

script

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<body onload="script">...</body>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <body>. Full details of the element are in Part 6.

Attribute: onpopstate

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<body>	script	HTML5

onpopstate on <body>

Element: <body> (Document body) | Since: HTML5

Description

Fired when the active history entry changes.

Accepted values

script

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<body onpopstate="script">...</body>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <body>. Full details of the element are in Part 6.

Attribute: onresize

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<body>	script	HTML 4.01

onresize on <body>

Element: <body> (Document body) | Since: HTML 4.01

Description

Fired when the window is resized.

Accepted values

script

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<body onresize="script">...</body>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <body>. Full details of the element are in Part 6.

Attribute: onstorage

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<body>	script	HTML5

onstorage on <body>

Element: <body> (Document body) | Since: HTML5

Description

Fired when localStorage or sessionStorage changes in another tab.

Accepted values

script

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<body onstorage="script">...</body>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <body>. Full details of the element are in Part 6.

Attribute: onunload

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<body>	script	HTML 4.01

onunload on <body>

Element: <body> (Document body) | Since: HTML 4.01

Description

Fired when the document is unloaded. Unreliable; prefer pagehide.

Accepted values

script

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<body onunload="script">...</body>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <body>. Full details of the element are in Part 6.

Attribute: open

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<details>	boolean	HTML5
<dialog>	boolean	HTML 5.2

open on <details>

Element: <details> (Disclosure widget) | Since: HTML5

Description

The details are visible. Absent means collapsed.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="open" in XHTML style). Never write open="false"; that still counts as present.

```
<details open>...</details>
```

The same attribute on other elements

<dialog>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <details>. Full details of the element are in Part 6.

open on <dialog>

Element: <dialog> (Dialog box) | Since: HTML 5.2

Description

The dialog is visible. Set it with showModal() rather than by hand so that focus and the backdrop work correctly.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="open" in XHTML style). Never write open="false"; that still counts as present.

```
<dialog open>...</dialog>
```

The same attribute on other elements

<details>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <dialog>. Full details of the element are in Part 6.

Attribute: optimum

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<meter>	number	HTML5

optimum on <meter>

Element: <meter> (Scalar measurement (gauge)) | Since: HTML5

Description

The ideal value. Determines which region is shown as good (green) versus bad (red/yellow).

Accepted values

number

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<meter optimum="3">...</meter>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <meter>. Full details of the element are in Part 6.

Attribute: orient

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<input>	various	Non-standard

orient on <input>

Element: <input> (Input control) | Since: Non-standard

Description

Non-standard browser-specific attributes.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input orient="various">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

Attribute: pattern

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<input>	regular expression	HTML5

pattern on <input>

Element: <input> (Input control) | Since: HTML5

Description

A JavaScript regular expression the value must match (text, search, url, tel, email, password). Describe the format in title.

Accepted values

regular expression

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input pattern="regular expression">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

Attribute: ping

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<a>	space-separated URLs	HTML5
<area>	URLs	HTML5

ping on <a>

Element: <a> (Anchor (hyperlink)) | Since: HTML5

Description

A list of URLs that receive a POST request with the body PING when the link is followed. Used for tracking.

Accepted values

space-separated URLs

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<a ping="space-separated URLs">...</a>
```

The same attribute on other elements

<area>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <a>. Full details of the element are in Part 6.

ping on <area>

Element: <area> (Image map area) | Since: HTML5

Description

URLs to ping when the link is followed.

Accepted values

URLs

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<area ping="https://example.com/page.html">
```

The same attribute on other elements

<a>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <area>. Full details of the element are in Part 6.

Attribute: placeholder

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<input>	text	HTML5
<textarea>	text	HTML5

placeholder on <input>

Element: <input> (Input control) | Since: HTML5

Description

Hint shown inside an empty text-like control. Not a substitute for a label.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input placeholder="value">
```

The same attribute on other elements

<textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

placeholder on <textarea>

Element: <textarea> (Multi-line text input) | Since: HTML5

Description

Hint shown when empty. Not a label.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<textarea placeholder="value">...</textarea>
```

The same attribute on other elements

<input>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <textarea>. Full details of the element are in Part 6.

Attribute: playsinline

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<video>	boolean	Living Standard

playsinline on <video>

Element: <video> (Embedded video) | Since: Living Standard

Description

On iPhone, play inline instead of forcing fullscreen.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="playsinline" in XHTML style). Never write playsinline="false"; that still counts as present.

```
<video playsinline>...</video>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <video>. Full details of the element are in Part 6.

Attribute: popovertarget

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<button>	element id	Living Standard
<input>	id / show | hide | toggle	Living Standard

popovertarget on <button>

Element: <button> (Button) | Since: Living Standard

Description

The popover element this button shows, hides or toggles.

Accepted values

element id

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<button popovertarget="element id">...</button>
```

The same attribute on other elements

<input>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <button>. Full details of the element are in Part 6.

popovertarget on <input>

Element: <input> (Input control) | Since: Living Standard

Description

Control a popover from a button-type input.

Accepted values

id / show | hide | toggle

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input popovertarget="my-id">
```

The same attribute on other elements

<button>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

Attribute: popovertargetaction

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<button>	show | hide | toggle	Living Standard
<input>	id / show | hide | toggle	Living Standard

popovertargetaction on <button>

Element: <button> (Button) | Since: Living Standard

Description

What to do to the popover (default toggle).

Accepted values

show | hide | toggle

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<button popovertargetaction="show">...</button>
```

The same attribute on other elements

<input>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <button>. Full details of the element are in Part 6.

popovertargetaction on <input>

Element: <input> (Input control) | Since: Living Standard

Description

Control a popover from a button-type input.

Accepted values

id / show | hide | toggle

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input popovertargetaction="my-id">
```

The same attribute on other elements

<button>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

Attribute: poster

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<video>	URL	HTML5

poster on <video>

Element: <video> (Embedded video) | Since: HTML5

Description

Image shown before the video plays or while loading.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<video poster="https://example.com/page.html">...</video>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <video>. Full details of the element are in Part 6.

Attribute: preload

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<audio>	none | metadata | auto	HTML5
<video>	none | metadata | auto	HTML5

preload on <audio>

Element: <audio> (Embedded audio) | Since: HTML5

Description

A hint about how much to download before playback: nothing, only metadata such as duration (default in most browsers), or the whole file.

Accepted values

none | metadata | auto

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<audio preload="none">...</audio>
```

The same attribute on other elements

<video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <audio>. Full details of the element are in Part 6.

preload on <video>

Element: <video> (Embedded video) | Since: HTML5

Description

How much to download before play.

Accepted values

none | metadata | auto

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<video preload="none">...</video>
```

The same attribute on other elements

<audio>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <video>. Full details of the element are in Part 6.

Attribute: preserveAspectRatio

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<svg>	keyword	SVG

preserveAspectRatio on <svg>

Element: <svg> (Scalable Vector Graphics root) | Since: SVG

Description

How to fit the viewBox into the viewport.

Accepted values

keyword

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<svg preserveAspectRatio="keyword">...</svg>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <svg>. Full details of the element are in Part 6.

Attribute: profile

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<head>	URLs	HTML 4.01

profile on <head>

Element: <head> (Document head) | Since: HTML 4.01

Description

Obsolete. Meta data profiles.

Accepted values

URLs

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<head profile="https://example.com/page.html">...</head>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <head>. Full details of the element are in Part 6.

Attribute: prompt

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<isindex>	text	HTML 2.0

prompt on <isindex>

Element: <isindex> (Search index prompt (obsolete)) | Since: HTML 2.0

Description

The label shown before the field.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<isindex prompt="value">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <isindex>. Full details of the element are in Part 6.

Attribute: property

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<meta>	text	RDFa

property on <meta>

Element: <meta> (Metadata) | Since: RDFa

Description

Not in the HTML standard but universally used for RDFa / Open Graph tags such as og:title.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<meta property="value">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <meta>. Full details of the element are in Part 6.

Attribute: radiogroup

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<menuitem>	various	HTML5 draft

radiogroup on <menuitem>

Element: <menuitem> (Menu item (obsolete)) | Since: HTML5 draft

Description

State and grouping.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<menuitem radiogroup="various">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <menuitem>. Full details of the element are in Part 6.

Attribute: readonly

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<input>	boolean	HTML 4.01
<textarea>	boolean	HTML 4.01

readonly on <input>

Element: <input> (Input control) | Since: HTML 4.01

Description

Cannot be edited but is focusable and submitted. Text-like types only.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="readonly" in XHTML style). Never write readonly="false"; that still counts as present.

```
<input readonly>
```

The same attribute on other elements

<textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

readonly on <textarea>

Element: <textarea> (Multi-line text input) | Since: HTML 4.01

Description

Cannot be edited; is submitted.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="readonly" in XHTML style). Never write readonly="false"; that still counts as present.

```
<textarea readonly>...</textarea>
```

The same attribute on other elements

<input>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <textarea>. Full details of the element are in Part 6.

Attribute: referrerpolicy

Accepted by 7 elements. Each use is described on the following pages.

Element	Values	Since
<a>	no-referrer | no-referrer-when-downgrade | origin | origin-when-cross-origin | same-origin | strict-origin | strict-origin-when-cross-origin | unsafe-url	HTML5
<area>	referrer policy keyword	HTML5
<iframe>	referrer policy keyword	HTML5
<img>	referrer policy keyword	HTML5
<link>	referrer policy	HTML5
<portal>	policy	Experimental
<script>	referrer policy	HTML5

referrerpolicy on <a>

Element: <a> (Anchor (hyperlink)) | Since: HTML5

Description

How much referrer information is sent when following the link.

Accepted values

no-referrer | no-referrer-when-downgrade | origin | origin-when-cross-origin | same-origin | strict-origin | strict-origin-when-cross-origin | unsafe-url

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<a referrerpolicy="no-referrer">...</a>
```

The same attribute on other elements

<area>, <iframe>, <img>, <link>, <portal>, <script>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <a>. Full details of the element are in Part 6.

referrerpolicy on <area>

Element: <area> (Image map area) | Since: HTML5

Description

Referrer policy for the navigation.

Accepted values

referrer policy keyword

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<area referrerpolicy="referrer policy keyword">
```

The same attribute on other elements

<a>, <iframe>, <img>, <link>, <portal>, <script>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <area>. Full details of the element are in Part 6.

referrerpolicy on <iframe>

Element: <iframe> (Inline frame) | Since: HTML5

Description

Which referrer to send when loading the frame.

Accepted values

referrer policy keyword

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<iframe referrerpolicy="referrer policy keyword">...</iframe>
```

The same attribute on other elements

<a>, <area>, <img>, <link>, <portal>, <script>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <iframe>. Full details of the element are in Part 6.

referrerpolicy on <img>

Element: <img> (Image) | Since: HTML5

Description

Which referrer to send.

Accepted values

referrer policy keyword

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<img referrerpolicy="referrer policy keyword">
```

The same attribute on other elements

<a>, <area>, <iframe>, <link>, <portal>, <script>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <img>. Full details of the element are in Part 6.

referrerpolicy on <link>

Element: <link> (External resource link) | Since: HTML5

Description

Referrer to send when fetching.

Accepted values

referrer policy

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<link referrerpolicy="referrer policy">
```

The same attribute on other elements

<a>, <area>, <iframe>, <img>, <portal>, <script>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <link>. Full details of the element are in Part 6.

referrerpolicy on <portal>

Element: <portal> (Portal (experimental, abandoned)) | Since: Experimental

Description

Referrer policy.

Accepted values

policy

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<portal referrerpolicy="policy">...</portal>
```

The same attribute on other elements

<a>, <area>, <iframe>, <img>, <link>, <script>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <portal>. Full details of the element are in Part 6.

referrerpolicy on <script>

Element: <script> (Script) | Since: HTML5

Description

Referrer to send.

Accepted values

referrer policy

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<script referrerpolicy="referrer policy">...</script>
```

The same attribute on other elements

<a>, <area>, <iframe>, <img>, <link>, <portal>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <script>. Full details of the element are in Part 6.

Attribute: rel

Accepted by 4 elements. Each use is described on the following pages.

Element	Values	Since
<a>	space-separated link types	HTML 4.01
<area>	link types	HTML5
<form>	link types	Living Standard
<link>	space-separated link types	HTML 2.0

rel on <a>

Element: <a> (Anchor (hyperlink)) | Since: HTML 4.01

Description

The relationship between the current document and the linked document. Common values: nofollow, noopener, noreferrer, external, alternate, author, bookmark, help, license, next, prev, search, tag. See the link types table in Part 9.

Accepted values

space-separated link types

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<a rel="value">...</a>
```

The same attribute on other elements

<area>, <form>, <link>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <a>. Full details of the element are in Part 6.

rel on <area>

Element: <area> (Image map area) | Since: HTML5

Description

Relationship of the linked resource.

Accepted values

link types

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<area rel="link types">
```

The same attribute on other elements

<a>, <form>, <link>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <area>. Full details of the element are in Part 6.

rel on <form>

Element: <form> (Form) | Since: Living Standard

Description

Relationship of the target resource, for example noopener or noreferrer.

Accepted values

link types

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<form rel="link types">...</form>
```

The same attribute on other elements

<a>, <area>, <link>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <form>. Full details of the element are in Part 6.

rel on <link>

Element: <link> (External resource link) | Since: HTML 2.0

Description

Required. Relationship: stylesheet, icon, apple-touch-icon, manifest, canonical, alternate, preload, prefetch, preconnect, dns-prefetch, modulepreload, prerender, author, license, help, next, prev, search, pingback, privacy-policy, terms-of-service, expect.

Accepted values

space-separated link types

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<link rel="value">
```

The same attribute on other elements

<a>, <area>, <form>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <link>. Full details of the element are in Part 6.

Attribute: required

Accepted by 3 elements. Each use is described on the following pages.

Element	Values	Since
<input>	boolean	HTML5
<select>	boolean	HTML5
<textarea>	boolean	HTML5

required on <input>

Element: <input> (Input control) | Since: HTML5

Description

Must have a value before the form can be submitted.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="required" in XHTML style). Never write required="false"; that still counts as present.

```
<input required>
```

The same attribute on other elements

<select>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

required on <select>

Element: <select> (Drop-down / list box) | Since: HTML5

Description

The user must choose an option with a non-empty value.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="required" in XHTML style). Never write required="false"; that still counts as present.

```
<select required>...</select>
```

The same attribute on other elements

<input>, <textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <select>. Full details of the element are in Part 6.

required on <textarea>

Element: <textarea> (Multi-line text input) | Since: HTML5

Description

Must not be empty.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="required" in XHTML style). Never write required="false"; that still counts as present.

```
<textarea required>...</textarea>
```

The same attribute on other elements

<input>, <select>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <textarea>. Full details of the element are in Part 6.

Attribute: results

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<input>	various	Non-standard

results on <input>

Element: <input> (Input control) | Since: Non-standard

Description

Non-standard browser-specific attributes.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input results="various">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

Attribute: rev

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<a>	link types	HTML 4.01 (obsolete in HTML5)
<link>	link types	HTML 4.01

rev on <a>

Element: <a> (Anchor (hyperlink)) | Since: HTML 4.01 (obsolete in HTML5)

Description

Obsolete. Reverse relationship. Use rel instead.

Accepted values

link types

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<a rev="link types">...</a>
```

The same attribute on other elements

<link>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <a>. Full details of the element are in Part 6.

rev on <link>

Element: <link> (External resource link) | Since: HTML 4.01

Description

Obsolete. Reverse relationship.

Accepted values

link types

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<link rev="link types">
```

The same attribute on other elements

<a>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <link>. Full details of the element are in Part 6.

Attribute: reversed

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
	boolean	HTML5

reversed on

Element: <ol> (Ordered list) | Since: HTML5

Description

Number the items in descending order.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="reversed" in XHTML style). Never write reversed="false"; that still counts as present.

```
<ol reversed>...</ol>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <ol>. Full details of the element are in Part 6.

Attribute: rightmargin

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<body>	pixels	IE/Netscape

rightmargin on <body>

Element: <body> (Document body) | Since: IE/Netscape

Description

Obsolete, non-standard. Page margins. Use CSS margin.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<body rightmargin="3">...</body>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <body>. Full details of the element are in Part 6.

Attribute: role

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<svg>	-	ARIA

role on <svg>

Element: <svg> (Scalable Vector Graphics root) | Since: ARIA

Description

Accessibility name and role for the graphic.

Accepted values

-

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<svg role="-">...</svg>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <svg>. Full details of the element are in Part 6.

Attribute: rows

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<frameset>	comma-separated sizes	HTML 4.01
<textarea>	positive integer	HTML 2.0

rows on <frameset>

Element: <frameset> (Frameset (obsolete)) | Since: HTML 4.01

Description

Row heights.

Accepted values

comma-separated sizes

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<frameset rows="comma-separated sizes">...</frameset>
```

The same attribute on other elements

<textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <frameset>. Full details of the element are in Part 6.

rows on <textarea>

Element: <textarea> (Multi-line text input) | Since: HTML 2.0

Description

Visible number of lines. Default 2.

Accepted values

positive integer

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<textarea rows="3">...</textarea>
```

The same attribute on other elements

<frameset>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <textarea>. Full details of the element are in Part 6.

Attribute: rowspan

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<td>	non-negative integer	HTML 3.2
<th>	non-negative integer	HTML 3.2

rowspan on <td>

Element: <td> (Table data cell) | Since: HTML 3.2

Description

Number of rows the cell spans. Default 1; 0 means to the end of the row group. Maximum 65534.

Accepted values

non-negative integer

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<td rowspan="3">...</td>
```

The same attribute on other elements

<th>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <td>. Full details of the element are in Part 6.

rowspan on <th>

Element: <th> (Table header cell) | Since: HTML 3.2

Description

Rows spanned.

Accepted values

non-negative integer

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<th rowspan="3">...</th>
```

The same attribute on other elements

<td>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <th>. Full details of the element are in Part 6.

Attribute: rules

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<table>	none | groups | rows | cols | all	HTML 4.01

rules on <table>

Element: <table> (Table) | Since: HTML 4.01

Description

Obsolete. Which inner borders to draw. Use CSS border on cells.

Accepted values

none | groups | rows | cols | all

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<table rules="none">...</table>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <table>. Full details of the element are in Part 6.

Attribute: sandbox

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<iframe>	empty or space-separated tokens	HTML5

sandbox on <iframe>

Element: <iframe> (Inline frame) | Since: HTML5

Description

Applies extra restrictions. Empty value = all restrictions. Tokens that lift restrictions: allow-downloads, allow-forms, allow-modals, allow-orientation-lock, allow-pointer-lock, allow-popups, allow-popups-to-escape-sandbox, allow-presentation, allow-same-origin, allow-scripts, allow-top-navigation, allow-top-navigation-by-user-activation, allow-top-navigation-to-custom-protocols.

Accepted values

empty or space-separated tokens

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<iframe sandbox="empty">...</iframe>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <iframe>. Full details of the element are in Part 6.

Attribute: scheme

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<meta>	text	HTML 4.01

scheme on <meta>

Element: <meta> (Metadata) | Since: HTML 4.01

Description

Obsolete. Interpretation scheme for content.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<meta scheme="value">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <meta>. Full details of the element are in Part 6.

Attribute: scope

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<td>	-	HTML 4.01
<th>	row | col | rowgroup | colgroup	HTML 4.01

scope on <td>

Element: <td> (Table data cell) | Since: HTML 4.01

Description

Obsolete on td (use on th).

Accepted values

-

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<td scope="-">...</td>
```

The same attribute on other elements

<th>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <td>. Full details of the element are in Part 6.

scope on <th>

Element: <th> (Table header cell) | Since: HTML 4.01

Description

Which cells this header describes.

Accepted values

row | col | rowgroup | colgroup

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<th scope="row">...</th>
```

The same attribute on other elements

<td>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <th>. Full details of the element are in Part 6.

Attribute: scoped

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<style>	boolean	HTML5 draft (removed)

scoped on <style>

Element: <style> (Embedded style sheet) | Since: HTML5 draft (removed)

Description

Removed. Was meant to scope styles to the parent element; use Shadow DOM or @scope.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="scoped" in XHTML style). Never write scoped="false"; that still counts as present.

```
<style scoped>...</style>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <style>. Full details of the element are in Part 6.

Attribute: scrollamount

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<marquee>	pixels	IE

scrollamount on <marquee>

Element: <marquee> (Scrolling text (obsolete)) | Since: IE

Description

Distance per step.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<marquee scrollamount="3">...</marquee>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <marquee>. Full details of the element are in Part 6.

Attribute: scrolldelay

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<marquee>	ms	IE

scrolldelay on <marquee>

Element: <marquee> (Scrolling text (obsolete)) | Since: IE

Description

Delay between steps.

Accepted values

ms

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<marquee scrolldelay="ms">...</marquee>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <marquee>. Full details of the element are in Part 6.

Attribute: scrolling

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<frame>	yes | no | auto	HTML 4.01
<iframe>	yes | no | auto	HTML 4.01

scrolling on <frame>

Element: <frame> (Frame (obsolete)) | Since: HTML 4.01

Description

Scrollbar behaviour.

Accepted values

yes | no | auto

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<frame scrolling="yes">
```

The same attribute on other elements

<iframe>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <frame>. Full details of the element are in Part 6.

scrolling on <iframe>

Element: <iframe> (Inline frame) | Since: HTML 4.01

Description

Obsolete. Use CSS overflow in the framed document.

Accepted values

yes | no | auto

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<iframe scrolling="yes">...</iframe>
```

The same attribute on other elements

<frame>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <iframe>. Full details of the element are in Part 6.

Attribute: select

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<content>	CSS selector	Shadow DOM v0

select on <content>

Element: <content> (Shadow DOM insertion point (obsolete)) | Since: Shadow DOM v0

Description

Which light DOM children to insert.

Accepted values

CSS selector

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<content select="CSS selector">...</content>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <content>. Full details of the element are in Part 6.

Attribute: selected

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<option>	boolean	HTML 2.0

selected on <option>

Element: <option> (Option) | Since: HTML 2.0

Description

Initially selected.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="selected" in XHTML style). Never write selected="false"; that still counts as present.

```
<option selected>...</option>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <option>. Full details of the element are in Part 6.

Attribute: shadowrootclonable

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<template>	boolean	Living Standard

shadowrootclonable on <template>

Element: <template> (Content template) | Since: Living Standard

Description

Sets clonable on the declarative shadow root.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="shadowrootclonable" in XHTML style). Never write shadowrootclonable="false"; that still counts as present.

```
<template shadowrootclonable>...</template>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <template>. Full details of the element are in Part 6.

Attribute: shadowrootdelegatesfocus

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<template>	boolean	Living Standard

shadowrootdelegatesfocus on <template>

Element: <template> (Content template) | Since: Living Standard

Description

Sets delegatesFocus on the declarative shadow root.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="shadowrootdelegatesfocus" in XHTML style). Never write shadowrootdelegatesfocus="false"; that still counts as present.

```
<template shadowrootdelegatesfocus>...</template>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <template>. Full details of the element are in Part 6.

Attribute: shadowrootmode

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<template>	open | closed	Living Standard

shadowrootmode on <template>

Element: <template> (Content template) | Since: Living Standard

Description

Creates a declarative shadow root on the parent element.

Accepted values

open | closed

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<template shadowrootmode="open">...</template>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <template>. Full details of the element are in Part 6.

Attribute: shadowrootserializable

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<template>	boolean	Living Standard

shadowrootserializable on <template>

Element: <template> (Content template) | Since: Living Standard

Description

Sets serializable on the declarative shadow root.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="shadowrootserializable" in XHTML style). Never write shadowrootserializable="false"; that still counts as present.

```
<template shadowrootserializable>...</template>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <template>. Full details of the element are in Part 6.

Attribute: shape

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<a>	rect | circle | poly | default	HTML 4.01 (obsolete in HTML5)
<area>	rect | circle | poly | default	HTML 3.2

shape on <a>

Element: <a> (Anchor (hyperlink)) | Since: HTML 4.01 (obsolete in HTML5)

Description

Obsolete. Shape of a clickable region. Use <area> instead.

Accepted values

rect | circle | poly | default

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<a shape="rect">...</a>
```

The same attribute on other elements

<area>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <a>. Full details of the element are in Part 6.

shape on <area>

Element: <area> (Image map area) | Since: HTML 3.2

Description

The shape of the region. default covers the whole image.

Accepted values

rect | circle | poly | default

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<area shape="rect">
```

The same attribute on other elements

<a>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <area>. Full details of the element are in Part 6.

Attribute: size

Accepted by 6 elements. Each use is described on the following pages.

Element	Values	Since
<basefont>	1 to 7	HTML 3.2
<font>	1-7 or +n / -n	HTML 3.2
<hr>	pixels	HTML 3.2
<input>	integer	HTML 2.0
<select>	integer	HTML 2.0
<spacer>	pixels	Netscape

size on <basefont>

Element: <basefont> (Base font (obsolete)) | Since: HTML 3.2

Description

Default font size on the 1-7 HTML scale (3 = normal).

Accepted values

1 to 7

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<basefont size="1 to 7">
```

The same attribute on other elements

<font>, <hr>, <input>, <select>, <spacer>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <basefont>. Full details of the element are in Part 6.

size on <font>

Element: <font> (Font (obsolete)) | Since: HTML 3.2

Description

Font size on the HTML scale: 1 = x-small, 2 = small, 3 = medium (default), 4 = large, 5 = x-large, 6 = xx-large, 7 = xxx-large.

Accepted values

1-7 or +n / -n

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<font size="1-7">...</font>
```

The same attribute on other elements

<basefont>, <hr>, <input>, <select>, <spacer>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <font>. Full details of the element are in Part 6.

size on <hr>

Element: <hr> (Thematic break (horizontal rule)) | Since: HTML 3.2

Description

Obsolete. Height of the rule. Use CSS height or border-width.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<hr size="3">
```

The same attribute on other elements

<basefont>, <font>, <input>, <select>, <spacer>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <hr>. Full details of the element are in Part 6.

size on <input>

Element: <input> (Input control) | Since: HTML 2.0

Description

Visible width in characters (text-like types). Prefer CSS width.

Accepted values

integer

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input size="3">
```

The same attribute on other elements

<basefont>, <font>, <hr>, <select>, <spacer>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

size on <select>

Element: <select> (Drop-down / list box) | Since: HTML 2.0

Description

Number of visible rows. 1 (default) gives a drop-down; more gives a list box.

Accepted values

integer

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<select size="3">...</select>
```

The same attribute on other elements

<basefont>, <font>, <hr>, <input>, <spacer>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <select>. Full details of the element are in Part 6.

size on <spacer>

Element: <spacer> (Spacer (non-standard, obsolete)) | Since: Netscape

Description

Amount of space.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<spacer size="3">
```

The same attribute on other elements

<basefont>, <font>, <hr>, <input>, <select>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <spacer>. Full details of the element are in Part 6.

Attribute: sizes

Accepted by 3 elements. Each use is described on the following pages.

Element	Values	Since
<img>	media conditions and lengths	HTML5
<link>	any or WxH list	HTML5
<source>	size list	HTML5

sizes on <img>

Element: <img> (Image) | Since: HTML5

Description

How wide the image will be rendered, for example '(max-width: 600px) 100vw, 50vw'. Required when srcset uses width descriptors.

Accepted values

media conditions and lengths

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<img sizes="value">
```

The same attribute on other elements

<link>, <source>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <img>. Full details of the element are in Part 6.

sizes on <link>

Element: <link> (External resource link) | Since: HTML5

Description

Icon sizes, for example 16x16 32x32 or any (for SVG).

Accepted values

any or WxH list

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<link sizes="any">
```

The same attribute on other elements

<img>, <source>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <link>. Full details of the element are in Part 6.

sizes on <source>

Element: <source> (Media or image source) | Since: HTML5

Description

Display widths for width-descriptor srcset (picture only).

Accepted values

size list

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<source sizes="size list">
```

The same attribute on other elements

<img>, <link>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <source>. Full details of the element are in Part 6.

Attribute: span

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<col>	positive integer	HTML 4.01
<colgroup>	positive integer	HTML 4.01

span on <col>

Element: <col> (Table column) | Since: HTML 4.01

Description

How many consecutive columns this element represents. Default 1.

Accepted values

positive integer

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<col span="3">
```

The same attribute on other elements

<colgroup>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <col>. Full details of the element are in Part 6.

span on <colgroup>

Element: <colgroup> (Table column group) | Since: HTML 4.01

Description

Number of columns in the group when there are no <col> children.

Accepted values

positive integer

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<colgroup span="3">...</colgroup>
```

The same attribute on other elements

<col>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <colgroup>. Full details of the element are in Part 6.

Attribute: spellcheck

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<textarea>	true | false	HTML5

spellcheck on <textarea>

Element: <textarea> (Multi-line text input) | Since: HTML5

Description

Enable or disable spell checking (global).

Accepted values

true | false

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<textarea spellcheck="true">...</textarea>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <textarea>. Full details of the element are in Part 6.

Attribute: src

Accepted by 13 elements. Each use is described on the following pages.

Element	Values	Since
<audio>	URL	HTML5
<bgsound>	URL	IE
<embed>	URL	Netscape / HTML5
<frame>	URL	HTML 4.01
<iframe>	URL	HTML 4.01
<image>	as <img>	-
<img>	URL	HTML 2.0
<input>	URL	HTML 2.0
<portal>	URL	Experimental
<script>	URL	HTML 4.01
<source>	URL	HTML5
<track>	URL	HTML5
<video>	URL	HTML5

src on <audio>

Element: <audio> (Embedded audio) | Since: HTML5

Description

The URL of the audio file. Alternatively use <source> children.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<audio src="https://example.com/page.html">...</audio>
```

The same attribute on other elements

<bgsound>, <embed>, <frame>, <iframe>, <image>, <img>, <input>, <portal>, <script>, <source>, <track>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <audio>. Full details of the element are in Part 6.

src on <bgsound>

Element: <bgsound> (Background sound (non-standard, obsolete)) | Since: IE

Description

The sound file.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<bgsound src="https://example.com/page.html">
```

The same attribute on other elements

<audio>, <embed>, <frame>, <iframe>, <image>, <img>, <input>, <portal>, <script>, <source>, <track>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <bgsound>. Full details of the element are in Part 6.

src on <embed>

Element: <embed> (External content) | Since: Netscape / HTML5

Description

The URL of the resource.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<embed src="https://example.com/page.html">
```

The same attribute on other elements

<audio>, <bgsound>, <frame>, <iframe>, <image>, <img>, <input>, <portal>, <script>, <source>, <track>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <embed>. Full details of the element are in Part 6.

src on <frame>

Element: <frame> (Frame (obsolete)) | Since: HTML 4.01

Description

The document to display.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<frame src="https://example.com/page.html">
```

The same attribute on other elements

<audio>, <bgsound>, <embed>, <iframe>, <image>, <img>, <input>, <portal>, <script>, <source>, <track>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <frame>. Full details of the element are in Part 6.

src on <iframe>

Element: <iframe> (Inline frame) | Since: HTML 4.01

Description

The page to embed. about:blank shows an empty page.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<iframe src="https://example.com/page.html">...</iframe>
```

The same attribute on other elements

<audio>, <bgsound>, <embed>, <frame>, <image>, <img>, <input>, <portal>, <script>, <source>, <track>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <iframe>. Full details of the element are in Part 6.

src on <image>

Element: <image> (Image (non-standard alias, obsolete)) | Since: -

Description

Whatever the parser transfers to the <img> it creates.

Accepted values

as <img>

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<image src="as <img>">
```

The same attribute on other elements

<audio>, <bgsound>, <embed>, <frame>, <iframe>, <img>, <input>, <portal>, <script>, <source>, <track>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <image>. Full details of the element are in Part 6.

src on <img>

Element: <img> (Image) | Since: HTML 2.0

Description

The image URL. Required (unless srcset is used with a browser that supports it).

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<img src="https://example.com/page.html">
```

The same attribute on other elements

<audio>, <bgsound>, <embed>, <frame>, <iframe>, <image>, <input>, <portal>, <script>, <source>, <track>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <img>. Full details of the element are in Part 6.

src on <input>

Element: <input> (Input control) | Since: HTML 2.0

Description

The image for type=image.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input src="https://example.com/page.html">
```

The same attribute on other elements

<audio>, <bgsound>, <embed>, <frame>, <iframe>, <image>, <img>, <portal>, <script>, <source>, <track>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

src on <portal>

Element: <portal> (Portal (experimental, abandoned)) | Since: Experimental

Description

Page to preview.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<portal src="https://example.com/page.html">...</portal>
```

The same attribute on other elements

<audio>, <bgsound>, <embed>, <frame>, <iframe>, <image>, <img>, <input>, <script>, <source>, <track>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <portal>. Full details of the element are in Part 6.

src on <script>

Element: <script> (Script) | Since: HTML 4.01

Description

External script file.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<script src="https://example.com/page.html">...</script>
```

The same attribute on other elements

<audio>, <bgsound>, <embed>, <frame>, <iframe>, <image>, <img>, <input>, <portal>, <source>, <track>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <script>. Full details of the element are in Part 6.

src on <source>

Element: <source> (Media or image source) | Since: HTML5

Description

The media file. Required in <audio>/<video>; ignored in <picture>.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<source src="https://example.com/page.html">
```

The same attribute on other elements

<audio>, <bgsound>, <embed>, <frame>, <iframe>, <image>, <img>, <input>, <portal>, <script>, <track>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <source>. Full details of the element are in Part 6.

src on <track>

Element: <track> (Text track for media) | Since: HTML5

Description

Required. The WebVTT file.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<track src="https://example.com/page.html">
```

The same attribute on other elements

<audio>, <bgsound>, <embed>, <frame>, <iframe>, <image>, <img>, <input>, <portal>, <script>, <source>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <track>. Full details of the element are in Part 6.

src on <video>

Element: <video> (Embedded video) | Since: HTML5

Description

The video file. Or use <source> children.

Accepted values

URL

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<video src="https://example.com/page.html">...</video>
```

The same attribute on other elements

<audio>, <bgsound>, <embed>, <frame>, <iframe>, <image>, <img>, <input>, <portal>, <script>, <source>, <track>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <video>. Full details of the element are in Part 6.

Attribute: srcdoc

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<iframe>	HTML text	HTML5

srcdoc on <iframe>

Element: <iframe> (Inline frame) | Since: HTML5

Description

Inline HTML to display instead of loading src. Overrides src if present.

Accepted values

HTML text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<iframe srcdoc="HTML text">...</iframe>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <iframe>. Full details of the element are in Part 6.

Attribute: srclang

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<track>	language tag	HTML5

srclang on <track>

Element: <track> (Text track for media) | Since: HTML5

Description

Language of the track. Required for subtitles.

Accepted values

language tag

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<track srclang="en">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <track>. Full details of the element are in Part 6.

Attribute: srcset

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<img>	comma-separated candidates	HTML5
<source>	candidate list	HTML5

srcset on <img>

Element: <img> (Image) | Since: HTML5

Description

Alternative image files: 'small.jpg 480w, large.jpg 1200w' (width descriptors) or 'img.jpg 1x, img@2x.jpg 2x' (density descriptors).

Accepted values

comma-separated candidates

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<img srcset="value">
```

The same attribute on other elements

<source>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <img>. Full details of the element are in Part 6.

srcset on <source>

Element: <source> (Media or image source) | Since: HTML5

Description

Image candidates. Required in <picture>; ignored in media elements.

Accepted values

candidate list

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<source srcset="candidate list">
```

The same attribute on other elements

<img>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <source>. Full details of the element are in Part 6.

Attribute: standby

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<object>	various	HTML 4.01 / HTML5 (removed)

standby on <object>

Element: <object> (External object) | Since: HTML 4.01 / HTML5 (removed)

Description

Obsolete attributes from HTML 4.01 plug-in usage or presentational attributes. Use CSS or drop them.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<object standby="various">...</object>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <object>. Full details of the element are in Part 6.

Attribute: start

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
	integer	HTML 3.2

start on

Element: <ol> (Ordered list) | Since: HTML 3.2

Description

The number of the first item (always a decimal integer even if type is a or i).

Accepted values

integer

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<ol start="3">...</ol>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <ol>. Full details of the element are in Part 6.

Attribute: step

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<input>	number or any	HTML5

step on <input>

Element: <input> (Input control) | Since: HTML5

Description

Granularity of allowed values; 'any' allows any value.

Accepted values

number or any

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input step="3">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

Attribute: stroke

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<svg>	colour / length	SVG

stroke on <svg>

Element: <svg> (Scalable Vector Graphics root) | Since: SVG

Description

Presentation attributes for shapes (can also be CSS).

Accepted values

colour / length

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<svg stroke="#336699">...</svg>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <svg>. Full details of the element are in Part 6.

Attribute: stroke-width

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<svg>	colour / length	SVG

stroke-width on <svg>

Element: <svg> (Scalable Vector Graphics root) | Since: SVG

Description

Presentation attributes for shapes (can also be CSS).

Accepted values

colour / length

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<svg stroke-width="#336699">...</svg>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <svg>. Full details of the element are in Part 6.

Attribute: summary

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<table>	text	HTML 4.01

summary on <table>

Element: <table> (Table) | Since: HTML 4.01

Description

Obsolete. Description of the table for screen readers. Use <caption> or aria-describedby.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<table summary="value">...</table>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <table>. Full details of the element are in Part 6.

Attribute: target

Accepted by 5 elements. Each use is described on the following pages.

Element	Values	Since
<a>	_self | _blank | _parent | _top | frame-name	HTML 4.01
<area>	_self | _blank | _parent | _top | name	HTML 4.01
<base>	_self | _blank | _parent | _top | name	HTML 4.01
<form>	_self | _blank | _parent | _top | name	HTML 4.01
<link>	browsing context	HTML 4.01

target on <a>

Element: <a> (Anchor (hyperlink)) | Since: HTML 4.01

Description

Where to open the linked document. _self (default) opens it in the same browsing context; _blank opens a new tab or window; _parent opens it in the parent frame; _top opens it in the full window, replacing all frames. A custom name targets an <iframe> with that name.

Accepted values

_self | _blank | _parent | _top | frame-name

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<a target="_self">...</a>
```

The same attribute on other elements

<area>, <base>, <form>, <link>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <a>. Full details of the element are in Part 6.

target on <area>

Element: <area> (Image map area) | Since: HTML 4.01

Description

Where to open the destination.

Accepted values

_self | _blank | _parent | _top | name

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<area target="_self">
```

The same attribute on other elements

<a>, <base>, <form>, <link>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <area>. Full details of the element are in Part 6.

target on <base>

Element: <base> (Document base URL) | Since: HTML 4.01

Description

The default browsing context for links and forms that do not specify their own target.

Accepted values

_self | _blank | _parent | _top | name

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<base target="_self">
```

The same attribute on other elements

<a>, <area>, <form>, <link>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <base>. Full details of the element are in Part 6.

target on <form>

Element: <form> (Form) | Since: HTML 4.01

Description

Where to display the response.

Accepted values

_self | _blank | _parent | _top | name

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<form target="_self">...</form>
```

The same attribute on other elements

<a>, <area>, <base>, <link>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <form>. Full details of the element are in Part 6.

target on <link>

Element: <link> (External resource link) | Since: HTML 4.01

Description

Obsolete on link.

Accepted values

browsing context

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<link target="browsing context">
```

The same attribute on other elements

<a>, <area>, <base>, <form>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <link>. Full details of the element are in Part 6.

Attribute: text

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<body>	colour	HTML 3.2

text on <body>

Element: <body> (Document body) | Since: HTML 3.2

Description

Obsolete. Text colour. Use CSS color.

Accepted values

colour

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<body text="#336699">...</body>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <body>. Full details of the element are in Part 6.

Attribute: title

Accepted by 6 elements. Each use is described on the following pages.

Element	Values	Since
<abbr>	text	HTML 4.01
<acronym>	text	HTML 4.01
<dfn>	text	HTML 4.01
<iframe>	text	HTML 4.01
<link>	text	HTML 2.0
<style>	text	HTML 4.01

title on <abbr>

Element: <abbr> (Abbreviation) | Since: HTML 4.01

Description

The full expansion of the abbreviation. On <abbr> this attribute has a specific meaning and should contain nothing else.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<abbr title="value">...</abbr>
```

The same attribute on other elements

<acronym>, <dfn>, <iframe>, <link>, <style>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <abbr>. Full details of the element are in Part 6.

title on <acronym>

Element: <acronym> (Acronym (obsolete)) | Since: HTML 4.01

Description

The expansion of the acronym.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<acronym title="value">...</acronym>
```

The same attribute on other elements

<abbr>, <dfn>, <iframe>, <link>, <style>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <acronym>. Full details of the element are in Part 6.

title on <dfn>

Element: <dfn> (Definition term) | Since: HTML 4.01

Description

The term being defined, if different from the content.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<dfn title="value">...</dfn>
```

The same attribute on other elements

<abbr>, <acronym>, <iframe>, <link>, <style>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <dfn>. Full details of the element are in Part 6.

title on <iframe>

Element: <iframe> (Inline frame) | Since: HTML 4.01

Description

A description of the embedded content for assistive technology. Strongly recommended.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<iframe title="value">...</iframe>
```

The same attribute on other elements

<abbr>, <acronym>, <dfn>, <link>, <style>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <iframe>. Full details of the element are in Part 6.

title on <link>

Element: <link> (External resource link) | Since: HTML 2.0

Description

For style sheets: the name of an alternate style sheet set. For feeds: the feed title.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<link title="value">
```

The same attribute on other elements

<abbr>, <acronym>, <dfn>, <iframe>, <style>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <link>. Full details of the element are in Part 6.

title on <style>

Element: <style> (Embedded style sheet) | Since: HTML 4.01

Description

Name of an alternate style sheet set.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<style title="value">...</style>
```

The same attribute on other elements

<abbr>, <acronym>, <dfn>, <iframe>, <link>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <style>. Full details of the element are in Part 6.

Attribute: topmargin

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<body>	pixels	IE/Netscape

topmargin on <body>

Element: <body> (Document body) | Since: IE/Netscape

Description

Obsolete, non-standard. Page margins. Use CSS margin.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<body topmargin="3">...</body>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <body>. Full details of the element are in Part 6.

Attribute: truespeed

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<marquee>	boolean	IE

truespeed on <marquee>

Element: <marquee> (Scrolling text (obsolete)) | Since: IE

Description

Allow delays under 60 ms.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="truespeed" in XHTML style). Never write truespeed="false"; that still counts as present.

```
<marquee truespeed>...</marquee>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <marquee>. Full details of the element are in Part 6.

Attribute: type

Accepted by 17 elements. Each use is described on the following pages.

Element	Values	Since
<a>	MIME type	HTML 4.01
<area>	MIME type	HTML 4.01
<button>	submit | reset | button	HTML 4.01
<embed>	MIME type	Netscape / HTML5
<input>	see Part 6	HTML 2.0 / HTML5
	1 | a | A | i | I | disc | circle | square	HTML 3.2
<link>	MIME type	HTML 2.0
<menu>	context | toolbar | list	HTML5 draft (removed)
<menuitem>	command | checkbox | radio	HTML5 draft
<object>	MIME type	HTML 4.01
	1 | a | A | i | I	HTML 3.2
<param>	MIME type	HTML 4.01
<script>	omitted | module | importmap | speculationrules | MIME type	HTML 4.01 / HTML5
<source>	MIME type, optionally with codecs	HTML5
<spacer>	horizontal | vertical | block	Netscape
<style>	text/css	HTML 4.01
	disc | circle | square	HTML 3.2

type on <a>

Element: <a> (Anchor (hyperlink)) | Since: HTML 4.01

Description

The media type of the linked resource, for example application/pdf. Advisory only.

Accepted values

MIME type

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<a type="text/plain">...</a>
```

The same attribute on other elements

<area>, <button>, <embed>, <input>, <li>, <link>, <menu>, <menuitem>, <object>, <ol>, <param>, <script>, <source>, <spacer>, <style>, <ul>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <a>. Full details of the element are in Part 6.

type on <area>

Element: <area> (Image map area) | Since: HTML 4.01

Description

Obsolete in HTML5. Type of the linked resource.

Accepted values

MIME type

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<area type="text/plain">
```

The same attribute on other elements

<a>, <button>, <embed>, <input>, <li>, <link>, <menu>, <menuitem>, <object>, <ol>, <param>, <script>, <source>, <spacer>, <style>, <ul>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <area>. Full details of the element are in Part 6.

type on <button>

Element: <button> (Button) | Since: HTML 4.01

Description

submit (default) sends the form; reset restores default values; button does nothing by itself.

Accepted values

submit | reset | button

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<button type="submit">...</button>
```

The same attribute on other elements

<a>, <area>, <embed>, <input>, <li>, <link>, <menu>, <menuitem>, <object>, <ol>, <param>, <script>, <source>, <spacer>, <style>, <ul>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <button>. Full details of the element are in Part 6.

type on <embed>

Element: <embed> (External content) | Since: Netscape / HTML5

Description

The type of the resource, used to choose the plug-in or handler.

Accepted values

MIME type

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<embed type="text/plain">
```

The same attribute on other elements

<a>, <area>, <button>, <input>, <li>, <link>, <menu>, <menuitem>, <object>, <ol>, <param>, <script>, <source>, <spacer>, <style>, <ul>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <embed>. Full details of the element are in Part 6.

type on <input>

Element: <input> (Input control) | Since: HTML 2.0 / HTML5

Description

The kind of control. Default text. Values: button, checkbox, color, date, datetime-local, email, file, hidden, image, month, number, password, radio, range, reset, search, submit, tel, text, time, url, week.

Accepted values

see Part 6

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input type="see Part 6">
```

The same attribute on other elements

<a>, <area>, <button>, <embed>, <li>, <link>, <menu>, <menuitem>, <object>, <ol>, <param>, <script>, <source>, <spacer>, <style>, <ul>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

type on

Element: <li> (List item) | Since: HTML 3.2

Description

Obsolete. Bullet or numbering style for this item. Use CSS list-style-type.

Accepted values

1 | a | A | i | I | disc | circle | square

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<li type="1">...</li>
```

The same attribute on other elements

<a>, <area>, <button>, <embed>, <input>, <link>, <menu>, <menuitem>, <object>, <ol>, <param>, <script>, <source>, <spacer>, <style>, <ul>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <li>. Full details of the element are in Part 6.

type on <link>

Element: <link> (External resource link) | Since: HTML 2.0

Description

The type of the resource, for example text/css, image/png, application/rss+xml.

Accepted values

MIME type

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<link type="text/plain">
```

The same attribute on other elements

<a>, <area>, <button>, <embed>, <input>, <li>, <menu>, <menuitem>, <object>, <ol>, <param>, <script>, <source>, <spacer>, <style>, <ul>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <link>. Full details of the element are in Part 6.

type on <menu>

Element: <menu> (Menu (toolbar list)) | Since: HTML5 draft (removed)

Description

Obsolete. From the abandoned HTML5 context menu design.

Accepted values

context | toolbar | list

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<menu type="context">...</menu>
```

The same attribute on other elements

<a>, <area>, <button>, <embed>, <input>, <li>, <link>, <menuitem>, <object>, <ol>, <param>, <script>, <source>, <spacer>, <style>, <ul>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <menu>. Full details of the element are in Part 6.

type on <menuitem>

Element: <menuitem> (Menu item (obsolete)) | Since: HTML5 draft

Description

Kind of item.

Accepted values

command | checkbox | radio

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<menuitem type="command">
```

The same attribute on other elements

<a>, <area>, <button>, <embed>, <input>, <li>, <link>, <menu>, <object>, <ol>, <param>, <script>, <source>, <spacer>, <style>, <ul>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <menuitem>. Full details of the element are in Part 6.

type on <object>

Element: <object> (External object) | Since: HTML 4.01

Description

The content type of the resource, for example application/pdf, image/svg+xml.

Accepted values

MIME type

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<object type="text/plain">...</object>
```

The same attribute on other elements

<a>, <area>, <button>, <embed>, <input>, <li>, <link>, <menu>, <menuitem>, <ol>, <param>, <script>, <source>, <spacer>, <style>, <ul>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <object>. Full details of the element are in Part 6.

type on

Element: <ol> (Ordered list) | Since: HTML 3.2

Description

Numbering type: decimal (default), lowercase letters, uppercase letters, lowercase roman, uppercase roman.

Accepted values

1 | a | A | i | I

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<ol type="1">...</ol>
```

The same attribute on other elements

<a>, <area>, <button>, <embed>, <input>, <li>, <link>, <menu>, <menuitem>, <object>, <param>, <script>, <source>, <spacer>, <style>, <ul>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <ol>. Full details of the element are in Part 6.

type on <param>

Element: <param> (Object parameter (deprecated)) | Since: HTML 4.01

Description

Obsolete. Type of the value when valuetype=ref.

Accepted values

MIME type

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<param type="text/plain">
```

The same attribute on other elements

<a>, <area>, <button>, <embed>, <input>, <li>, <link>, <menu>, <menuitem>, <object>, <ol>, <script>, <source>, <spacer>, <style>, <ul>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <param>. Full details of the element are in Part 6.

type on <script>

Element: <script> (Script) | Since: HTML 4.01 / HTML5

Description

Omitted or text/javascript: classic script. module: ES module. importmap: JSON import map. Any other type: data block that is not executed.

Accepted values

omitted | module | importmap | speculationrules | MIME type

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<script type="text/plain">...</script>
```

The same attribute on other elements

<a>, <area>, <button>, <embed>, <input>, <li>, <link>, <menu>, <menuitem>, <object>, <ol>, <param>, <source>, <spacer>, <style>, <ul>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <script>. Full details of the element are in Part 6.

type on <source>

Element: <source> (Media or image source) | Since: HTML5

Description

The resource type, for example image/webp, video/mp4, video/webm; codecs="vp9, opus". Lets the browser skip unsupported files without downloading them.

Accepted values

MIME type, optionally with codecs

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<source type="text/plain">
```

The same attribute on other elements

<a>, <area>, <button>, <embed>, <input>, <li>, <link>, <menu>, <menuitem>, <object>, <ol>, <param>, <script>, <spacer>, <style>, <ul>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <source>. Full details of the element are in Part 6.

type on <spacer>

Element: <spacer> (Spacer (non-standard, obsolete)) | Since: Netscape

Description

Kind of space.

Accepted values

horizontal | vertical | block

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<spacer type="horizontal">
```

The same attribute on other elements

<a>, <area>, <button>, <embed>, <input>, <li>, <link>, <menu>, <menuitem>, <object>, <ol>, <param>, <script>, <source>, <style>, <ul>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <spacer>. Full details of the element are in Part 6.

type on <style>

Element: <style> (Embedded style sheet) | Since: HTML 4.01

Description

Obsolete. The only allowed value is text/css; omit it.

Accepted values

text/css

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<style type="value">...</style>
```

The same attribute on other elements

<a>, <area>, <button>, <embed>, <input>, <li>, <link>, <menu>, <menuitem>, <object>, <ol>, <param>, <script>, <source>, <spacer>, <ul>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <style>. Full details of the element are in Part 6.

type on

Element: <ul> (Unordered list) | Since: HTML 3.2

Description

Obsolete. Bullet style. Use CSS list-style-type.

Accepted values

disc | circle | square

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<ul type="disc">...</ul>
```

The same attribute on other elements

<a>, <area>, <button>, <embed>, <input>, <li>, <link>, <menu>, <menuitem>, <object>, <ol>, <param>, <script>, <source>, <spacer>, <style>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <ul>. Full details of the element are in Part 6.

Attribute: typemustmatch

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<object>	various	HTML 4.01 / HTML5 (removed)

typemustmatch on <object>

Element: <object> (External object) | Since: HTML 4.01 / HTML5 (removed)

Description

Obsolete attributes from HTML 4.01 plug-in usage or presentational attributes. Use CSS or drop them.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<object typemustmatch="various">...</object>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <object>. Full details of the element are in Part 6.

Attribute: usemap

Accepted by 3 elements. Each use is described on the following pages.

Element	Values	Since
<img>	#map-name	HTML 3.2
<input>	#map	HTML 4.01
<object>	#map	HTML 4.01

usemap on <img>

Element: <img> (Image) | Since: HTML 3.2

Description

Links the image to a <map> element to make it an image map.

Accepted values

#map-name

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<img usemap="#map-name">
```

The same attribute on other elements

<input>, <object>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <img>. Full details of the element are in Part 6.

usemap on <input>

Element: <input> (Input control) | Since: HTML 4.01

Description

Obsolete on input. Use <img usemap>.

Accepted values

#map

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input usemap="#map">
```

The same attribute on other elements

<img>, <object>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

usemap on <object>

Element: <object> (External object) | Since: HTML 4.01

Description

Image map to use (obsolete in the Living Standard).

Accepted values

#map

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<object usemap="#map">...</object>
```

The same attribute on other elements

<img>, <input>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <object>. Full details of the element are in Part 6.

Attribute: valign

Accepted by 8 elements. Each use is described on the following pages.

Element	Values	Since
<col>	top | middle | bottom | baseline	HTML 4.01
<colgroup>	various	HTML 4.01
<tbody>	various	HTML 4.01
<td>	top | middle | bottom | baseline	HTML 3.2
<tfoot>	various	HTML 4.01
<th>	various	HTML 3.2 / 4.01
<thead>	various	HTML 4.01
<tr>	top | middle | bottom | baseline	HTML 3.2

valign on <col>

Element: <col> (Table column) | Since: HTML 4.01

Description

Obsolete. Vertical alignment. Use CSS vertical-align.

Accepted values

top | middle | bottom | baseline

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<col valign="top">
```

The same attribute on other elements

<colgroup>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because

accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <col>. Full details of the element are in Part 6.

valign on <colgroup>

Element: <colgroup> (Table column group) | Since: HTML 4.01

Description

Obsolete presentational attributes; see <col>.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<colgroup valign="various">...</colgroup>
```

The same attribute on other elements

<col>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <colgroup>. Full details of the element are in Part 6.

valign on <tbody>

Element: <tbody> (Table body) | Since: HTML 4.01

Description

Obsolete presentational attributes. Use CSS.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<tbody valign="various">...</tbody>
```

The same attribute on other elements

<col>, <colgroup>, <td>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <tbody>. Full details of the element are in Part 6.

valign on <td>

Element: <td> (Table data cell) | Since: HTML 3.2

Description

Obsolete. Use CSS vertical-align.

Accepted values

top | middle | bottom | baseline

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<td valign="top">...</td>
```

The same attribute on other elements

<col>, <colgroup>, <tbody>, <tfoot>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <td>. Full details of the element are in Part 6.

valign on <tfoot>

Element: <tfoot> (Table footer) | Since: HTML 4.01

Description

Obsolete presentational attributes. Use CSS.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<tfoot valign="various">...</tfoot>
```

The same attribute on other elements

<col>, <colgroup>, <tbody>, <td>, <th>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <tfoot>. Full details of the element are in Part 6.

valign on <th>

Element: <th> (Table header cell) | Since: HTML 3.2 / 4.01

Description

Obsolete presentational attributes. Use CSS.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<th valign="various">...</th>
```

The same attribute on other elements

<col>, <colgroup>, <tbody>, <td>, <tfoot>, <thead>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <th>. Full details of the element are in Part 6.

valign on <thead>

Element: <thead> (Table header) | Since: HTML 4.01

Description

Obsolete presentational attributes. Use CSS.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<thead valign="various">...</thead>
```

The same attribute on other elements

<col>, <colgroup>, <tbody>, <td>, <tfoot>, <th>, <tr>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <thead>. Full details of the element are in Part 6.

valign on <tr>

Element: <tr> (Table row) | Since: HTML 3.2

Description

Obsolete. Use CSS vertical-align.

Accepted values

top | middle | bottom | baseline

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<tr valign="top">...</tr>
```

The same attribute on other elements

<col>, <colgroup>, <tbody>, <td>, <tfoot>, <th>, <thead>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <tr>. Full details of the element are in Part 6.

Attribute: value

Accepted by 8 elements. Each use is described on the following pages.

Element	Values	Since
<button>	text	HTML 4.01
<data>	text	HTML5
<input>	text	HTML 2.0
	integer	HTML 3.2
<meter>	number	HTML5
<option>	text	HTML 2.0
<param>	text	HTML 3.2
<progress>	number	HTML5

value on <button>

Element: <button> (Button) | Since: HTML 4.01

Description

The value sent with the name.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<button value="value">...</button>
```

The same attribute on other elements

<data>, <input>, <li>, <meter>, <option>, <param>, <progress>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <button>. Full details of the element are in Part 6.

value on <data>

Element: <data> (Machine-readable value) | Since: HTML5

Description

Required. The machine-readable form of the content.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<data value="value">...</data>
```

The same attribute on other elements

<button>, <input>, <li>, <meter>, <option>, <param>, <progress>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <data>. Full details of the element are in Part 6.

value on <input>

Element: <input> (Input control) | Since: HTML 2.0

Description

The initial value (text types), the value submitted when checked (checkbox, radio), or the button label (submit, reset, button).

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input value="value">
```

The same attribute on other elements

<button>, <data>, <li>, <meter>, <option>, <param>, <progress>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

value on

Element: <li> (List item) | Since: HTML 3.2

Description

In <ol>: the ordinal number of this item. Following items count from it.

Accepted values

integer

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<li value="3">...</li>
```

The same attribute on other elements

<button>, <data>, <input>, <meter>, <option>, <param>, <progress>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <li>. Full details of the element are in Part 6.

value on <meter>

Element: <meter> (Scalar measurement (gauge)) | Since: HTML5

Description

Required. The current value, between min and max.

Accepted values

number

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<meter value="3">...</meter>
```

The same attribute on other elements

<button>, <data>, <input>, <li>, <option>, <param>, <progress>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <meter>. Full details of the element are in Part 6.

value on <option>

Element: <option> (Option) | Since: HTML 2.0

Description

The value submitted when this option is selected. Defaults to the text content.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<option value="value">...</option>
```

The same attribute on other elements

<button>, <data>, <input>, <li>, <meter>, <param>, <progress>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <option>. Full details of the element are in Part 6.

value on <param>

Element: <param> (Object parameter (deprecated)) | Since: HTML 3.2

Description

The parameter value.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<param value="value">
```

The same attribute on other elements

<button>, <data>, <input>, <li>, <meter>, <option>, <progress>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <param>. Full details of the element are in Part 6.

value on <progress>

Element: <progress> (Progress indicator) | Since: HTML5

Description

How much has been completed, from 0 to max. Omit for an indeterminate bar.

Accepted values

number

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<progress value="3">...</progress>
```

The same attribute on other elements

<button>, <data>, <input>, <li>, <meter>, <option>, <param>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <progress>. Full details of the element are in Part 6.

Attribute: valuetype

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<param>	data | ref | object	HTML 4.01

valuetype on <param>

Element: <param> (Object parameter (deprecated)) | Since: HTML 4.01

Description

Obsolete. How to interpret value.

Accepted values

data | ref | object

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<param valuetype="data">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <param>. Full details of the element are in Part 6.

Attribute: version

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<html>	text	HTML 2.0

version on <html>

Element: <html> (Document root) | Since: HTML 2.0

Description

Obsolete. The HTML DTD version.

Accepted values

text

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<html version="value">...</html>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <html>. Full details of the element are in Part 6.

Attribute: viewBox

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<svg>	min-x min-y width height	SVG

viewBox on <svg>

Element: <svg> (Scalable Vector Graphics root) | Since: SVG

Description

The internal coordinate system; makes the graphic scalable.

Accepted values

min-x min-y width height

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<svg viewBox="min-x min-y width height">...</svg>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <svg>. Full details of the element are in Part 6.

Attribute: vlink

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<body>	colour	HTML 3.2

vlink on <body>

Element: <body> (Document body) | Since: HTML 3.2

Description

Obsolete. Colour of visited links. Use CSS a:visited.

Accepted values

colour

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<body vlink="#336699">...</body>
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <body>. Full details of the element are in Part 6.

Attribute: volume

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<bgsound>	-10000 to 0	IE

volume on <bgsound>

Element: <bgsound> (Background sound (non-standard, obsolete)) | Since: IE

Description

Volume.

Accepted values

-10000 to 0

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<bgsound volume="-10000 to 0">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <bgsound>. Full details of the element are in Part 6.

Attribute: vspace

Accepted by 4 elements. Each use is described on the following pages.

Element	Values	Since
<applet>	pixels	HTML 3.2
<img>	pixels	HTML 3.2
<marquee>	pixels	IE
<object>	various	HTML 4.01 / HTML5 (removed)

vspace on <applet>

Element: <applet> (Java applet (obsolete)) | Since: HTML 3.2

Description

Horizontal and vertical margins.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<applet vspace="3">...</applet>
```

The same attribute on other elements

<img>, <marquee>, <object>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <applet>. Full

details of the element are in Part 6.

vspace on <img>

Element: <img> (Image) | Since: HTML 3.2

Description

Obsolete. Horizontal and vertical margins. Use CSS margin.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<img vspace="3">
```

The same attribute on other elements

<applet>, <marquee>, <object>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <img>. Full details of the element are in Part 6.

vspace on <marquee>

Element: <marquee> (Scrolling text (obsolete)) | Since: IE

Description

Margins.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<marquee vspace="3">...</marquee>
```

The same attribute on other elements

<applet>, <img>, <object>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <marquee>. Full details of the element are in Part 6.

vspace on <object>

Element: <object> (External object) | Since: HTML 4.01 / HTML5 (removed)

Description

Obsolete attributes from HTML 4.01 plug-in usage or presentational attributes. Use CSS or drop them.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<object vspace="various">...</object>
```

The same attribute on other elements

<applet>, <img>, <marquee>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <object>. Full details of the element are in Part 6.

Attribute: webkitdirectory

Accepted by 1 element. Each use is described on the following pages.

Element	Values	Since
<input>	various	Non-standard

webkitdirectory on <input>

Element: <input> (Input control) | Since: Non-standard

Description

Non-standard browser-specific attributes.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input webkitdirectory="various">
```

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

Attribute: width

Accepted by 21 elements. Each use is described on the following pages.

Element	Values	Since
<applet>	pixels	HTML 3.2
<canvas>	positive integer	HTML5
<col>	pixels or percentage	HTML 4.01
<colgroup>	various	HTML 4.01
<embed>	pixels	Netscape / HTML5
<fencedframe>	pixels	Experimental
<hr>	pixels or percentage	HTML 3.2
<iframe>	pixels	HTML 4.01
<img>	pixels	HTML 3.2
<input>	pixels	HTML5
<marquee>	size	IE
<multicol>	pixels	Netscape
<object>	pixels	HTML 4.01
<pre>	integer	HTML 2.0
<source>	pixels	Living Standard
<spacer>	-	Netscape
<svg>	length	SVG
<table>	pixels or percentage	HTML 3.2
<td>	pixels or percentage	HTML 3.2
<th>	various	HTML 3.2 / 4.01

Element	Values	Since
<video>	pixels	HTML5

width on <applet>

Element: <applet> (Java applet (obsolete)) | Since: HTML 3.2

Description

Size of the applet display area.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<applet width="3">...</applet>
```

The same attribute on other elements

<canvas>, <col>, <colgroup>, <embed>, <fencedframe>, <hr>, <iframe>, <img>, <input>, <marquee>, <multicol>, <object>, <pre>, <source>, <spacer>, <svg>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <applet>. Full details of the element are in Part 6.

width on <canvas>

Element: <canvas> (Graphics canvas) | Since: HTML5

Description

Width of the bitmap in CSS pixels. Default 300.

Accepted values

positive integer

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<canvas width="3">...</canvas>
```

The same attribute on other elements

<applet>, <col>, <colgroup>, <embed>, <fencedframe>, <hr>, <iframe>, <img>, <input>, <marquee>, <multicol>, <object>, <pre>, <source>, <spacer>, <svg>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <canvas>. Full details of the element are in Part 6.

width on <col>

Element: <col> (Table column) | Since: HTML 4.01

Description

Obsolete. Column width. Use CSS width.

Accepted values

pixels or percentage

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<col width="3">
```

The same attribute on other elements

<applet>, <canvas>, <colgroup>, <embed>, <fencedframe>, <hr>, <iframe>, <img>, <input>, <marquee>, <multicol>, <object>, <pre>, <source>, <spacer>, <svg>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <col>. Full details of the element are in Part 6.

width on <colgroup>

Element: <colgroup> (Table column group) | Since: HTML 4.01

Description

Obsolete presentational attributes; see <col>.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<colgroup width="various">...</colgroup>
```

The same attribute on other elements

<applet>, <canvas>, <col>, <embed>, <fencedframe>, <hr>, <iframe>, <img>, <input>, <marquee>, <multicol>, <object>, <pre>, <source>, <spacer>, <svg>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <colgroup>. Full details of the element are in Part 6.

width on <embed>

Element: <embed> (External content) | Since: Netscape / HTML5

Description

Width of the display area.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<embed width="3">
```

The same attribute on other elements

<applet>, <canvas>, <col>, <colgroup>, <fencedframe>, <hr>, <iframe>, <img>, <input>, <marquee>, <multicol>, <object>, <pre>, <source>, <spacer>, <svg>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <embed>. Full details of the element are in Part 6.

width on <fencedframe>

Element: <fencedframe> (Fenced frame (experimental)) | Since: Experimental

Description

Size of the frame.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<fencedframe width="3">...</fencedframe>
```

The same attribute on other elements

<applet>, <canvas>, <col>, <colgroup>, <embed>, <hr>, <iframe>, <img>, <input>, <marquee>, <multicol>, <object>, <pre>, <source>, <spacer>, <svg>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <fencedframe>. Full details of the element are in Part 6.

width on <hr>

Element: <hr> (Thematic break (horizontal rule)) | Since: HTML 3.2

Description

Obsolete. Width of the rule. Use CSS width.

Accepted values

pixels or percentage

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<hr width="3">
```

The same attribute on other elements

<applet>, <canvas>, <col>, <colgroup>, <embed>, <fencedframe>, <iframe>, <img>, <input>, <marquee>, <multicol>, <object>, <pre>, <source>, <spacer>, <svg>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <hr>. Full details of the element are in Part 6.

width on <iframe>

Element: <iframe> (Inline frame) | Since: HTML 4.01

Description

Width of the frame (default 300).

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<iframe width="3">...</iframe>
```

The same attribute on other elements

<applet>, <canvas>, <col>, <colgroup>, <embed>, <fencedframe>, <hr>, <img>, <input>, <marquee>, <multicol>, <object>, <pre>, <source>, <spacer>, <svg>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <iframe>. Full details of the element are in Part 6.

width on <img>

Element: <img> (Image) | Since: HTML 3.2

Description

Intrinsic width. Helps the browser reserve space.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<img width="3">
```

The same attribute on other elements

<applet>, <canvas>, <col>, <colgroup>, <embed>, <fencedframe>, <hr>, <iframe>, <input>, <marquee>, <multicol>, <object>, <pre>, <source>, <spacer>, <svg>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <img>. Full details of the element are in Part 6.

width on <input>

Element: <input> (Input control) | Since: HTML5

Description

Size of the image for type=image.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<input width="3">
```

The same attribute on other elements

<applet>, <canvas>, <col>, <colgroup>, <embed>, <fencedframe>, <hr>, <iframe>, <img>, <marquee>, <multicol>, <object>, <pre>, <source>, <spacer>, <svg>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <input>. Full details of the element are in Part 6.

width on <marquee>

Element: <marquee> (Scrolling text (obsolete)) | Since: IE

Description

Size.

Accepted values

size

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<marquee width="size">...</marquee>
```

The same attribute on other elements

<applet>, <canvas>, <col>, <colgroup>, <embed>, <fencedframe>, <hr>, <iframe>, <img>, <input>, <multicol>, <object>, <pre>, <source>, <spacer>, <svg>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <marquee>. Full details of the element are in Part 6.

width on <multicol>

Element: <multicol> (Multi-column text (non-standard, obsolete)) | Since: Netscape

Description

Column width.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<multicol width="3">...</multicol>
```

The same attribute on other elements

<applet>, <canvas>, <col>, <colgroup>, <embed>, <fencedframe>, <hr>, <iframe>, <img>, <input>, <marquee>, <object>, <pre>, <source>, <spacer>, <svg>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <multicol>. Full details of the element are in Part 6.

width on <object>

Element: <object> (External object) | Since: HTML 4.01

Description

Display size.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<object width="3">...</object>
```

The same attribute on other elements

<applet>, <canvas>, <col>, <colgroup>, <embed>, <fencedframe>, <hr>, <iframe>, <img>, <input>, <marquee>, <multicol>, <pre>, <source>, <spacer>, <svg>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <object>. Full details of the element are in Part 6.

width on <pre>

Element: <pre> (Pre-formatted text) | Since: HTML 2.0

Description

Obsolete. Number of characters per line.

Accepted values

integer

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<pre width="3">...</pre>
```

The same attribute on other elements

<applet>, <canvas>, <col>, <colgroup>, <embed>, <fencedframe>, <hr>, <iframe>, <img>, <input>, <marquee>, <multicol>, <object>, <source>, <spacer>, <svg>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <pre>. Full details of the element are in Part 6.

width on <source>

Element: <source> (Media or image source) | Since: Living Standard

Description

Intrinsic size of the image candidate (picture only).

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<source width="3">
```

The same attribute on other elements

<applet>, <canvas>, <col>, <colgroup>, <embed>, <fencedframe>, <hr>, <iframe>, <img>, <input>, <marquee>, <multicol>, <object>, <pre>, <spacer>, <svg>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <source>. Full details of the element are in Part 6.

width on <spacer>

Element: <spacer> (Spacer (non-standard, obsolete)) | Since: Netscape

Description

For type=block.

Accepted values

-

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<spacer width="-">
```

The same attribute on other elements

<applet>, <canvas>, <col>, <colgroup>, <embed>, <fencedframe>, <hr>, <iframe>, <img>, <input>, <marquee>, <multicol>, <object>, <pre>, <source>, <svg>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <spacer>. Full details of the element are in Part 6.

width on <svg>

Element: <svg> (Scalable Vector Graphics root) | Since: SVG

Description

Displayed size.

Accepted values

length

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<svg width="length">...</svg>
```

The same attribute on other elements

<applet>, <canvas>, <col>, <colgroup>, <embed>, <fencedframe>, <hr>, <iframe>, <img>, <input>, <marquee>, <multicol>, <object>, <pre>, <source>, <spacer>, <table>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <svg>. Full details of the element are in Part 6.

width on <table>

Element: <table> (Table) | Since: HTML 3.2

Description

Obsolete. Table width. Use CSS width.

Accepted values

pixels or percentage

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<table width="3">...</table>
```

The same attribute on other elements

<applet>, <canvas>, <col>, <colgroup>, <embed>, <fencedframe>, <hr>, <iframe>, <img>, <input>, <marquee>, <multicol>, <object>, <pre>, <source>, <spacer>, <svg>, <td>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <table>. Full details of the element are in Part 6.

width on <td>

Element: <td> (Table data cell) | Since: HTML 3.2

Description

Obsolete. Use CSS width.

Accepted values

pixels or percentage

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<td width="3">...</td>
```

The same attribute on other elements

<applet>, <canvas>, <col>, <colgroup>, <embed>, <fencedframe>, <hr>, <iframe>, <img>, <input>, <marquee>, <multicol>, <object>, <pre>, <source>, <spacer>, <svg>, <table>, <th>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <td>. Full details of the element are in Part 6.

width on <th>

Element: <th> (Table header cell) | Since: HTML 3.2 / 4.01

Description

Obsolete presentational attributes. Use CSS.

Accepted values

various

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<th width="various">...</th>
```

The same attribute on other elements

<applet>, <canvas>, <col>, <colgroup>, <embed>, <fencedframe>, <hr>, <iframe>, <img>, <input>, <marquee>, <multicol>, <object>, <pre>, <source>, <spacer>, <svg>, <table>, <td>, <video>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <th>. Full details of the element are in Part 6.

width on <video>

Element: <video> (Embedded video) | Since: HTML5

Description

Display size; also prevents layout shift.

Accepted values

pixels

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<video width="3">...</video>
```

The same attribute on other elements

<applet>, <canvas>, <col>, <colgroup>, <embed>, <fencedframe>, <hr>, <iframe>, <img>, <input>, <marquee>, <multicol>, <object>, <pre>, <source>, <spacer>, <svg>, <table>, <td>, <th>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <video>. Full details of the element are in Part 6.

Attribute: wrap

Accepted by 2 elements. Each use is described on the following pages.

Element	Values	Since
<pre>	boolean	Netscape
<textarea>	soft | hard | off	HTML5

wrap on <pre>

Element: <pre> (Pre-formatted text) | Since: Netscape

Description

Non-standard. Wrap long lines. Use CSS white-space: pre-wrap.

Accepted values

boolean

How to write it

This is a boolean attribute: its presence switches the feature on, its absence switches it off. Write just the name (or name="" / name="wrap" in XHTML style). Never write wrap="false"; that still counts as present.

```
<pre wrap>...</pre>
```

The same attribute on other elements

<textarea>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <pre>. Full details of the element are in Part 6.

wrap on <textarea>

Element: <textarea> (Multi-line text input) | Since: HTML5

Description

soft (default): lines wrap visually but newlines are not submitted. hard: newlines are inserted at wrap points when submitting (requires cols). off: no wrapping (non-standard).

Accepted values

soft | hard | off

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<textarea wrap="soft">...</textarea>
```

The same attribute on other elements

<pre>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <textarea>. Full details of the element are in Part 6.

Attribute: xmlns

Accepted by 3 elements. Each use is described on the following pages.

Element	Values	Since
<html>	http://www.w3.org/1999/xhtml	XHTML 1.0
<math>	http://www.w3.org/1998/Math/MathML	MathML
<svg>	http://www.w3.org/2000/svg	SVG

xmlns on <html>

Element: <html> (Document root) | Since: XHTML 1.0

Description

XML namespace; required in XHTML, ignored in HTML.

Accepted values

http://www.w3.org/1999/xhtml

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<html xmlns="http:">...</html>
```

The same attribute on other elements

<math>, <svg>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <html>. Full details of the element are in Part 6.

xmlns on <math>

Element: <math> (MathML root) | Since: MathML

Description

Namespace; optional in HTML.

Accepted values

http://www.w3.org/1998/Math/MathML

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<math xmlns="http:">...</math>
```

The same attribute on other elements

<html>, <svg>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <math>. Full details of the element are in Part 6.

xmlns on <svg>

Element: <svg> (Scalable Vector Graphics root) | Since: SVG

Description

Namespace; optional in HTML, required in standalone .svg files.

Accepted values

http://www.w3.org/2000/svg

How to write it

Write the attribute inside the start tag, followed by an equals sign and the value in double quotes.

```
<svg xmlns="http:">...</svg>
```

The same attribute on other elements

<html>, <math>. The meaning is similar but check each entry, because accepted values can differ.

Remember

All global attributes (Part 4) and event handler attributes (Part 5) may be combined with this one on <svg>. Full details of the element are in Part 6.

Part 10

Value References

Link types, meta names, autocomplete tokens, MIME types, URL schemes, colours and entities.

Link relationship types (rel)

Value	Allowed on	Meaning
alternate	link, a, area	An alternate version of the document: another language (with hreflang), another format (RSS feed, PDF), or an alternate style sheet (with stylesheet).
author	link, a, area	A page about the author of the document or article.
bookmark	a, area	A permalink to the nearest ancestor article.
canonical	link	The preferred URL of this page for search engines, avoiding duplicate content penalties.
dns-prefetch	link	Resolve the domain name of the given origin early.
expect	link	Block rendering until the element identified by href="#id" is parsed (for view transitions).
external	a, area, form	The link leads to a different site.
help	link, a, area, form	Context-sensitive help.
icon	link	The site icon (favicon). Combine with sizes and type. Also apple-touch-icon (non-standard) for iOS home screens.
license	link, a, area, form	The copyright licence covering the main content.
manifest	link	The web app manifest (JSON) for installable Progressive Web Apps.
me	link, a, area	The document represents the same person as the linked profile (IndieAuth / rel-me verification).

Value	Allowed on	Meaning
modulepreload	link	Preload a JavaScript module and its dependencies.
next / prev	link, a, area, form	The next or previous document in a sequence (pagination, chapters).
nofollow	a, area, form	The author does not endorse the linked page; search engines should not pass ranking credit.
noopener	a, area, form	Open the link without giving the new page access to window.opener. Implied by default for target=_blank in modern browsers.
noreferrer	a, area, form	Do not send the Referer header; also implies noopener.
opener	a, area, form	Explicitly allow window.opener for target=_blank.
pingback	link	The pingback server address for this document.
preconnect	link	Open a connection (DNS, TCP, TLS) to the origin early; use for fonts and APIs.
prefetch	link	Fetch a resource likely to be needed for the next navigation and store it in cache.
preload	link	Fetch a resource needed by the current page early with high priority. Requires as.
prerender	link	Deprecated; render a page in the background. Replaced by speculation rules.
privacy-policy	link, a, area	The privacy policy for the site.
search	link, a, area, form	A search interface for the site, often an OpenSearch description.

Value	Allowed on	Meaning
stylesheet	link	An external CSS style sheet. The most common link type.
tag	a, area	A tag (keyword) that applies to the current document.
terms-of-service	link, a, area	The terms of service for the site.

Standard meta names

Name	Meaning
application-name	Short name of the web application the page belongs to.
author	Name of the document's author.
description	A short summary of the page, often shown under the title in search results. Aim for 50-160 characters.
generator	Software that generated the page (for example a CMS).
keywords	Comma-separated keywords. Ignored by major search engines; historical.
referrer	Default referrer policy for the document: no-referrer, origin, strict-origin-when-cross-origin, and so on.
theme-color	Suggested colour for the browser UI (address bar on mobile). Accepts media.
color-scheme	Colour schemes the page supports: light, dark, light dark, only light.
viewport	Controls layout on mobile: width=device-width, initial-scale=1, plus optional minimum-scale, maximum-scale, user-scalable (do not disable zoom), viewport-fit=cover, interactive-widget.
robots	Indexing directives: index/noindex, follow/nofollow, noarchive, nosnippet, max-snippet:n, max-image-preview:large, noimageindex, notranslate, unavailable_after.
googlebot / bingbot	Same as robots but for one crawler.
google	Google-specific: nositelinkssearchbox, notranslate.
rating	Content rating: adult or RTA-5042-1996-1400-1577-RTA.
creator / publisher	The creator and publisher of the document.

Name	Meaning
format-detection	iOS: telephone=no stops phone numbers becoming links.
apple-mobile-web-app-capable / apple-mobile-web-app-status-bar-style / apple-mobile-web-app-title	iOS home-screen app behaviour (non-standard).
mobile-web-app-capable	Android equivalent (non-standard).
msapplication-TileColor / msapplication-config	Windows tile settings (non-standard).
twitter:card / twitter:site / twitter:title / twitter:description / twitter:image	Twitter/X card metadata.
property=og:title / og:type / og:image / og:url / og:description / og:site_name / og:locale	Open Graph metadata used by Facebook, LinkedIn, WhatsApp, Slack and others when a link is shared (uses property instead of name).
http-equiv=content-type	Legacy encoding declaration; use charset.
http-equiv=default-style	Name of the preferred style sheet set.
http-equiv=refresh	Reload after n seconds, optionally to another URL: content="5; url=...".
http-equiv=content-security-policy	Content Security Policy for the page.
http-equiv=x-ua-compatible	Legacy: content="IE=edge" for Internet Explorer document mode.

Name	Meaning
http-equiv=content-language	Obsolete; use lang on <html>.
http-equiv=set-cookie	Obsolete; not allowed.

Autocomplete tokens

Values for the autocomplete attribute on input, select and textarea. Combine a section, shipping/billing prefix, contact type and field: autocomplete="section-guest billing work tel".

Token	Meaning
off	Do not autofill (browsers may ignore for login fields).
on	Autofill allowed; browser guesses the field.
name	Full name.
honorific-prefix	Mr, Mrs, Dr...
given-name	First name.
additional-name	Middle name.
family-name	Last name.
honorific-suffix	Jr, PhD...
nickname	Nickname.
username	Account username.
new-password	A new password (browser may suggest one).
current-password	Existing password for login.
one-time-code	SMS/email verification code.
organization-title	Job title.
organization	Company name.
street-address	Full street address (multi-line).
address-line1 / address-line2 / address-line3	Address lines.
address-level1	Province / state / governorate.
address-level2	City.

Token	Meaning
address-level3 / address-level4	Finer divisions.
country	Country code.
country-name	Country name.
postal-code	Postal / ZIP code.
cc-name	Cardholder name.
cc-given-name / cc-additional-name / cc-family-name	Cardholder name parts.
cc-number	Card number.
cc-exp	Expiry MM/YY.
cc-exp-month / cc-exp-year	Expiry parts.
cc-csc	Security code.
cc-type	Card type.
transaction-currency	Currency code.
transaction-amount	Amount.
language	Preferred language.
bday	Birthday.
bday-day / bday-month / bday-year	Birthday parts.
sex	Gender identity as free text.
url	Home page.
photo	Photo URL.
tel	Full telephone number.

Token	Meaning
tel-country-code / tel-national / tel-area-code / tel-local / tel-extension	Telephone parts.
email	Email address.
impp	Instant messaging URL.
Prefixes: shipping / billing	shipping street-address, billing postal-code...
Prefixes: home / work / mobile / fax / pager	home tel, work email...
section-*	Groups fields into a named section: section-guest1 name.
webauthn	Allow passkey autofill (with username or current-password).

Common MIME types

MIME type	Extensions	Use
text/html	.html .htm	HTML documents
text/css	.css	Style sheets
text/javascript	.js .mjs	JavaScript (application/javascript is legacy)
application/json	.json	JSON data
application/ld+json	.jsonld	JSON-LD structured data
application/xml, text/xml	.xml	XML
image/svg+xml	.svg	SVG images
text/plain	.txt	Plain text
text/csv	.csv	Comma-separated values
text/vtt	.vtt	WebVTT subtitles
text/markdown	.md	Markdown
image/jpeg	.jpg .jpeg	Photos
image/png	.png	Lossless images with transparency
image/gif	.gif	Simple animations
image/webp	.webp	Modern lossy/lossless
image/avif	.avif	Newest, smallest
image/apng	.apng	Animated PNG
image/x-icon, image/vnd.microsoft.icon	.ico	Favicons
image/bmp	.bmp	Bitmap
image/tiff	.tif	TIFF (not displayed by browsers)

MIME type	Extensions	Use
audio/mpeg	.mp3	MP3 audio
audio/ogg	.ogg .oga .opus	Ogg Vorbis / Opus
audio/wav	.wav	Uncompressed audio
audio/aac	.aac	AAC
audio/flac	.flac	Lossless
audio/webm	.weba	WebM audio
audio/midi	.mid	MIDI
video/mp4	.mp4 .m4v	H.264/H.265 video
video/webm	.webm	VP8/VP9/AV1 video
video/ogg	.ogv	Theora
video/quicktime	.mov	QuickTime
video/x-msvideo	.avi	AVI
application/x-mpegURL	.m3u8	HLS streaming playlist
font/woff2	.woff2	Web fonts (best)
font/woff	.woff	Web fonts
font/ttf	.ttf	TrueType
font/otf	.otf	OpenType
application/pdf	.pdf	PDF
application/zip	.zip	ZIP
application/gzip	.gz	Gzip
application/octet-stream	any	Generic binary; forces download
application/msword	.doc	Word 97-2003

MIME type	Extensions	Use
application/vnd.openxmlformats-officedocument.wordprocessingml.document	.docx	Word
application/vnd.ms-excel	.xls	Excel 97-2003
application/vnd.openxmlformats-officedocument.spreadsheetml.sheet	.xlsx	Excel
application/vnd.ms-powerpoint	.ppt	PowerPoint
application/vnd.openxmlformats-officedocument.presentationml.presentation	.pptx	PowerPoint
application/x-www-form-urlencoded	-	Default form encoding
multipart/form-data	-	Form encoding for file uploads
text/event-stream	-	Server-sent events
application/wasm	.wasm	WebAssembly
application/manifest+json	.webmanifest	Web app manifest
application/rss+xml / application/atom+xml	.rss .atom	Feeds

URL schemes used in href

Scheme	Meaning
https:	Secure web page. Always use for links and resources.
http:	Insecure web page.
mailto:	Opens the mail client: mailto:a@b.com?subject=Hi&body=Text&cc=c@d.com
tel:	Dials a telephone number: tel:+201001234567
sms:	Opens SMS: sms:+2010...?body=Hello
ftp:	File transfer (no longer supported by browsers).
file:	A local file (only works locally).
data:	Inline data: .... or data:text/plain,Hello
blob:	An object URL created with URL.createObjectURL().
javascript:	Runs script when followed. Avoid; use a button.
about:	Browser pages: about:blank.
geo:	Geographic coordinates: geo:30.0131,31.2089
whatsapp: / tg: / skype:	App links (non-standard).
web+name:	Custom schemes registered with registerProtocolHandler.
#fragment	Not a scheme: a link to an id in the current page. #top and empty # scroll to the top.

Named colours

The 148 colour names recognised by CSS and by the legacy HTML color attributes, with their hexadecimal values.

Name	Hex	Name	Hex
aliceblue	#f0f8ff	antiquewhite	#faebd7
aqua	#00ffff	aquamarine	#7fffd4
azure	#f0ffff	beige	#f5f5dc
bisque	#ffe4c4	black	#000000
blanchedalmond	#ffebcd	blue	#0000ff
blueviolet	#8a2be2	brown	#a52a2a
burlywood	#deb887	cadetblue	#5f9ea0
chartreuse	#7fff00	chocolate	#d2691e
coral	#ff7f50	cornflowerblue	#6495ed
cornsilk	#fff8dc	crimson	#dc143c
cyan	#00ffff	darkblue	#00008b
darkcyan	#008b8b	darkgoldenrod	#b8860b
darkgray	#a9a9a9	darkgreen	#006400
darkkhaki	#bdb76b	darkmagenta	#8b008b
darkolivegreen	#556b2f	darkorange	#ff8c00
darkorchid	#9932cc	darkred	#8b0000
darksalmon	#e9967a	darkseagreen	#8fbc8f
darkslateblue	#483d8b	darkslategray	#2f4f4f
darkturquoise	#00ced1	darkviolet	#9400d3
deeppink	#ff1493	deepskyblue	#00bfff
dimgray	#696969	dodgerblue	#1e90ff
firebrick	#b22222	floralwhite	#fffaf0

Name	Hex	Name	Hex
forestgreen	#228b22	fuchsia	#ff00ff
gainsboro	#dcdcdc	ghostwhite	#f8f8ff
gold	#ffd700	goldenrod	#daa520
gray	#808080	green	#008000
greenyellow	#adff2f	honeydew	#f0fff0
hotpink	#ff69b4	indianred	#cd5c5c
indigo	#4b0082	ivory	#fffff0
khaki	#f0e68c	lavender	#e6e6fa
lavenderblush	#fff0f5	lawngreen	#7cfc00
lemonchiffon	#fffacd	lightblue	#add8e6
lightcoral	#f08080	lightcyan	#e0ffff
lightgoldenrodyellow	#fafad2	lightgray	#d3d3d3
lightgreen	#90ee90	lightpink	#ffb6c1
lightsalmon	#ffa07a	lightseagreen	#20b2aa
lightskyblue	#87cefa	lightslategray	#778899
lightsteelblue	#b0c4de	lightyellow	#ffffe0
lime	#00ff00	limegreen	#32cd32
linen	#faf0e6	magenta	#ff00ff
maroon	#800000	mediumaquamarine	#66cdaa
mediumblue	#0000cd	mediumorchid	#ba55d3
mediumpurple	#9370db	mediumseagreen	#3cb371
mediumslateblue	#7b68ee	mediumspringgreen	#00fa9a
mediumturquoise	#48d1cc	mediumvioletred	#c71585
midnightblue	#191970	mintcream	#f5fffa
mistyrose	#ffe4e1	moccasin	#ffe4b5

Name	Hex	Name	Hex
navajowhite	#ffdead	navy	#000080
oldlace	#fdf5e6	olive	#808000
olivedrab	#6b8e23	orange	#ffa500
orangered	#ff4500	orchid	#da70d6
palegoldenrod	#eee8aa	palegreen	#98fb98
paleturquoise	#afeeee	palevioletred	#db7093
papayawhip	#ffefd5	peachpuff	#ffdab9
peru	#cd853f	pink	#ffc0cb
plum	#dda0dd	powderblue	#b0e0e6
purple	#800080	rebeccapurple	#663399
red	#ff0000	rosybrown	#bc8f8f
royalblue	#4169e1	saddlebrown	#8b4513
salmon	#fa8072	sandybrown	#f4a460
seagreen	#2e8b57	seashell	#fff5ee
sienna	#a0522d	silver	#c0c0c0
skyblue	#87ceeb	slateblue	#6a5acd
slategray	#708090	snow	#fffafa
springgreen	#00ff7f	steelblue	#4682b4
tan	#d2b48c	teal	#008080
thistle	#d8bfd8	tomato	#ff6347
turquoise	#40e0d0	violet	#ee82ee
wheat	#f5deb3	white	#ffffff
whitesmoke	#f5f5f5	yellow	#ffff00
yellowgreen	#9acd32		

Character entity reference

Named and numeric character references. Numeric references also work in hexadecimal: € equals €. With UTF-8 you can type most of these directly; only <, > and & are essential.

Named	Numeric	Character
&	&	& ampersand
<	<	< less-than
>	>	> greater-than
"	"	" double quote
'	'	' apostrophe
		non-breaking space
		en space
		em space
		thin space
‌	‌	zero-width non-joiner
‍	‍	zero-width joiner
		soft hyphen
‎	‎	left-to-right mark
‏	‏	right-to-left mark
©	©	© copyright
®	®	® registered
™	™	™ trademark
§	§	§ section
¶	¶	¶ pilcrow
°	°	° degree

Named	Numeric	Character
µ	µ	µ micro
·	·	· middle dot
•	•	• bullet
…	…	… ellipsis
†	†	† dagger
‡	‡	‡ double dagger
‰	‰	‰ per mille
′	′	′ prime
″	″	″ double prime
–	–	– en dash
—	—	— em dash
‘	‘	‘ left single quote
’	’	’ right single quote
‚	‚	‚ single low quote
“	“	“ left double quote
”	”	” right double quote
„	„	„ double low quote
«	«	« left guillemet
»	»	» right guillemet
‹	‹	‹ single left guillemet
›	›	› single right guillemet
¡	¡	¡ inverted exclamation
¿	¿	¿ inverted question
¢	¢	¢ cent
£	£	£ pound

Named	Numeric	Character
¤	¤	¤ currency
¥	¥	¥ yen
€	€	€ euro
₺	₺	₺ lira
₹	₹	₹ rupee
₱	₱	₱ peso
±	±	± plus-minus
×	×	× multiplication
÷	÷	÷ division
−	−	− minus
½	½	½ one half
¼	¼	¼ one quarter
¾	¾	¾ three quarters
¹	¹	¹ superscript 1
²	²	² superscript 2
³	³	³ superscript 3
≠	≠	≠ not equal
≤	≤	≤ less or equal
≥	≥	≥ greater or equal
≈	≈	≈ approximately
≡	≡	≡ identical
∞	∞	∞ infinity
√	√	√ square root
∑	∑	∑ sum
∏	∏	∏ product

Named	Numeric	Character
∫	∫	∫ integral
∂	∂	∂ partial
∇	∇	∇ nabla
∈	∈	∈ element of
∉	∉	∉ not element of
⊂	⊂	⊂ subset
⊃	⊃	⊃ superset
∩	∩	∩ intersection
∪	∪	∪ union
∧	∧	∧ and
∨	∨	∨ or
¬	¬	¬ not
∀	∀	∀ for all
∃	∃	∃ exists
∅	∅	∅ empty set
⊥	⊥	⊥ perpendicular
∠	∠	∠ angle
∴	∴	∴ therefore
∝	∝	∝ proportional
ƒ	ƒ	ƒ function
∗	∗	∗ asterisk operator
⋅	⋅	⋅ dot operator
⊕	⊕	⊕ circled plus
⊗	⊗	⊗ circled times
←	←	← left arrow

Named	Numeric	Character
↑	↑	↑ up arrow
→	→	→ right arrow
↓	↓	↓ down arrow
↔	↔	↔ left-right arrow
↵	↵	↵ carriage return
⇐	⇐	⇐ double left arrow
⇑	⇑	⇑ double up arrow
⇒	⇒	⇒ double right arrow
⇓	⇓	⇓ double down arrow
⇔	⇔	⇔ double left-right arrow
♠	♠	♠ spade
♣	♣	♣ club
♥	♥	♥ heart
♦	♦	♦ diamond
◊	◊	◊ lozenge
✓	✓	✓ check mark
✗	✗	✗ ballot x
★	★	★ black star
☆	☆	☆ white star
▲	▲	▲ up triangle
▼	▼	▼ down triangle
●	●	● black circle
■	■	■ black square
Α α	Α α	Α α alpha
Β β	Β β	Β β beta

Named	Numeric	Character
Γ γ	Γ γ	Γ γ gamma
Δ δ	Δ δ	Δ δ delta
Ε ε	Ε ε	Ε ε epsilon
Ζ ζ	Ζ ζ	Ζ ζ zeta
Η η	Η η	Η η eta
Θ θ	Θ θ	Θ θ theta
Ι ι	Ι ι	Ι ι iota
Κ κ	Κ κ	Κ κ kappa
Λ λ	Λ λ	Λ λ lambda
Μ μ	Μ μ	Μ μ mu
Ν ν	Ν ν	Ν ν nu
Ξ ξ	Ξ ξ	Ξ ξ xi
Ο ο	Ο ο	Ο ο omicron
Π π	Π π	Π π pi
Ρ ρ	Ρ ρ	Ρ ρ rho
Σ σ ς	Σ σ ς	Σ σ ς sigma
Τ τ	Τ τ	Τ τ tau
Υ υ	Υ υ	Υ υ upsilon
Φ φ	Φ φ	Φ φ phi
Χ χ	Χ χ	Χ χ chi
Ψ ψ	Ψ ψ	Ψ ψ psi
Ω ω	Ω ω	Ω ω omega
À à	À à	À à
Á á	Á á	Á á
Â â	Â â	Â â

Named	Numeric	Character
Ã ã	Ã ã	Ã ã
Ä ä	Ä ä	Ä ä
Å å	Å å	Å å
Æ æ	Æ æ	Æ æ
Ç ç	Ç ç	Ç ç
È è	È è	È è
É é	É é	É é
Ê ê	Ê ê	Ê ê
Ë ë	Ë ë	Ë ë
Ì ì	Ì ì	Ì ì
Í í	Í í	Í í
Î î	Î î	Î î
Ï ï	Ï ï	Ï ï
Ð ð	Ð ð	Ð ð
Ñ ñ	Ñ ñ	Ñ ñ
Ò ò	Ò ò	Ò ò
Ó ó	Ó ó	Ó ó
Ô ô	Ô ô	Ô ô
Õ õ	Õ õ	Õ õ
Ö ö	Ö ö	Ö ö
Ø ø	Ø ø	Ø ø
Œ œ	Œ œ	Œ œ
Š š	Š š	Š š
Ù ù	Ù ù	Ù ù
Ú ú	Ú ú	Ú ú

Named	Numeric	Character
Û û	Û û	Û û
Ü ü	Ü ü	Ü ü
Ý ý	Ý ý	Ý ý
Ÿ ÿ	Ÿ ÿ	Ÿ ÿ
Þ þ	Þ þ	Þ þ
ß	ß	ß sharp s

Part 11

CSS Reference

Fundamentals, selectors, properties and a cookbook for styling HTML elements.

CSS fundamentals

CSS (Cascading Style Sheets) is the language that describes how HTML elements look: colours, fonts, spacing, size, position and layout. HTML says what something is; CSS says how it appears. The two are kept separate so that the same HTML can be shown in many ways (desktop, phone, print, dark mode) by changing only the CSS.

Three ways to add CSS

Method	How	When to use
External style sheet	<link rel="stylesheet" href="style.css"> in <head>; rules live in style.css	Always, for real projects. One file styles every page and is cached by the browser.
Internal style sheet	<style> ... </style> in <head>	Small single-page demos, emails, or page-specific overrides.
Inline style	style="color: red" attribute on an element	Quick tests and values set by JavaScript. Avoid for general styling.

```
/* style.css */
body   { font-family: Arial, sans-serif; margin: 0; }
footer { background: #222; color: #fff; text-align: center; padding:
20px; }
```

Anatomy of a rule

```
selector {
  property: value;   /* one declaration */
  property: value;
}

footer {
  color: gray;
```

```
  text-align: center;
}
```

- The selector chooses which elements the rule applies to.
- Each declaration is a property name, a colon, a value and a semicolon.
- Declarations are grouped in curly braces to form a rule (or rule set).
- Comments are written /* like this */ and may span lines.

The cascade: which rule wins

When several rules apply to the same element and property, the browser decides in this order:

- Origin and importance: author styles beat browser defaults; !important declarations beat normal ones (avoid !important; it makes styles hard to override).
- Specificity: inline style (1,0,0,0) beats id selectors (0,1,0,0), which beat class/attribute/pseudo-class selectors (0,0,1,0), which beat element/pseudo-element selectors (0,0,0,1). Count each part; the higher total wins.
- Source order: if specificity is equal, the rule that appears later wins.
- Layers (@layer) and scope (@scope) add further control in modern CSS.

```
p { color: black; }           /* specificity 0,0,0,1 */
.note { color: blue; }        /* 0,0,1,0 - wins over p */
#intro { color: green; }      /* 0,1,0,0 - wins over .note */
<p id="intro" class="note" style="color: red">  /* inline wins: red */
```

Inheritance

Some properties are inherited by child elements automatically: color, font-family, font-size, line-height, text-align, visibility, and most text properties. Others are not: margin, padding, border, background, width, height, display, position. Any property can be forced with the keywords inherit, initial, unset and revert.

Units

Unit	Meaning	Typical use
px	CSS pixel (1/96 inch)	Borders, small fixed sizes, media query breakpoints
em	Relative to the element's font size	Padding and margin that scale with text
rem	Relative to the root (html) font size, 16px by default	Font sizes, spacing - predictable and respects user settings
%	Relative to the parent's corresponding dimension	Widths in fluid layouts
vw / vh	1% of the viewport width / height	Full-screen sections, fluid type
vmin / vmax / dvh / svh / lvh	Viewport-relative variants	Mobile-safe full-height layouts (dvh)
ch	Width of the '0' character	Line length: max-width: 65ch
fr	Fraction of free space (grid only)	grid-template-columns: 1fr 2fr
deg, rad, turn	Angles	Rotations, gradients

Unit	Meaning	Typical use
s, ms	Time	Transitions and animations
pt, cm, mm, in	Physical units	Print style sheets

Colours

Notation	Example	Notes
Named colour	red, steelblue, transparent, currentColor	148 names; see Part 9
Hex	#e60000, #e60000cc (with alpha), #f00 (short)	Most common
rgb()	rgb(230 0 0), rgb(230 0 0 / 50%)	Modern space-separated syntax; commas still work
hsl()	hsl(0 100% 45%)	Hue 0-360, saturation, lightness; easy to adjust
oklch() / oklab()	oklch(60% 0.2 30)	Perceptually uniform; wide-gamut colours
color-mix()	color-mix(in oklab, red 30%, white)	Mixing colours
System colours	Canvas, CanvasText, LinkText, ButtonFace	Follow the operating system theme

The box model

Every element is a rectangular box made of four layers, from inside out: content, padding, border and margin. Width and height set the content box by default; with box-sizing:

border-box they include padding and border, which is far easier to reason about. Most projects begin with the reset *, *::before, *::after { box-sizing: border-box; }.

```
+------------------------------- margin (transparent) ---+
|  +---------------------------- border -----------------+  |
|  |  +------------------------ padding ---------------+  |  |
|  |  |                                                |  |  |
|  |  |                  content                       |  |  |
|  |  |                                                |  |  |
|  |  +------------------------------------------------+  |  |
|  +-------------------------------------------------------+  |
+-------------------------------------------------------------+
```

Vertical margins of adjacent blocks collapse into a single margin equal to the larger of the two. Padding and borders never collapse. Backgrounds cover the content and padding (and, by default, extend under the border).

Display and layout modes

display value	Behaviour
block	Starts on a new line, fills the available width, respects width/height. div, p, h1, section, footer...
inline	Flows within text, only as wide as its content, ignores width/height and vertical margins. span, a, em, strong...
inline-block	Flows within text but respects width, height and vertical margins/padding. img, button, input.
none	Removed from rendering entirely (also from the accessibility tree).
flex	The element becomes a flex container; children are laid out in a row or column with powerful alignment and distribution.
grid	The element becomes a grid container; children are placed in rows and columns defined by grid-template-*.

display value	Behaviour
inline-flex / inline-grid	As flex/grid, but the container itself flows inline.
table, table-row, table-cell…	Table layout without table elements.
list-item	Generates a bullet or number marker (li).
contents	The element's box disappears but its children remain.
flow-root	A block that contains its floats (clears them) and starts a new formatting context.

Positioning

position value	Behaviour
static	Default. Normal flow; top/left/etc. have no effect.
relative	Normal flow, then shifted by top/right/bottom/left; the original space is kept. Also creates a containing block for absolute children.
absolute	Removed from the flow and placed relative to the nearest positioned ancestor (or the initial containing block).
fixed	Removed from the flow and placed relative to the viewport; stays put when scrolling.
sticky	Behaves as relative until it reaches the threshold (top: 0), then sticks like fixed within its parent.

Flexbox in one page

```
.row {
  display: flex;              /* children become flex items in a row
*/
  flex-direction: row;        /* or column, row-reverse, column-
reverse */
  flex-wrap: wrap;            /* allow items to wrap onto new lines */
```

```
  justify-content: space-between; /* main-axis distribution: flex-
start | center | flex-end | space-around | space-evenly */
  align-items: center;        /* cross-axis alignment: stretch | flex-
start | center | flex-end | baseline */
  gap: 16px;                  /* space between items */
}
.row > .item {
  flex: 1;                    /* shorthand for flex-grow flex-shrink
flex-basis: 1 1 0 */
  order: 0;                   /* visual order */
  align-self: flex-end;       /* override align-items for one item */
}
```

Grid in one page

```
.layout {
  display: grid;
  grid-template-columns: 200px 1fr;          /* two columns */
  grid-template-rows: auto 1fr auto;         /* header, content,
footer */
  grid-template-areas:
    "header header"
    "nav    main"
    "footer footer";
  gap: 16px;
  min-height: 100vh;
}
header { grid-area: header; }
nav    { grid-area: nav; }
main   { grid-area: main; }
footer { grid-area: footer; }

/* Responsive cards without media queries */
.cards { display: grid; grid-template-columns: repeat(auto-fit,
minmax(240px, 1fr)); gap: 24px; }
```

Responsive design

```
/* Mobile first: base styles for small screens, then enhance */
.container { padding: 16px; }

@media (min-width: 600px) {
  .container { padding: 32px; }
}
@media (min-width: 1024px) {
  .container { max-width: 1180px; margin: 0 auto; }
}

/* Container queries: respond to the parent's size */
```

```
.card-wrapper { container-type: inline-size; }
@container (min-width: 400px) {
  .card { display: flex; }
}

/* User preferences */
@media (prefers-color-scheme: dark) { body { background: #111; color:
#eee; } }
@media (prefers-reduced-motion: reduce) { * { animation: none
!important; transition: none !important; } }

/* Print */
@media print { nav, footer, .no-print { display: none; } }
```

Custom properties (CSS variables)

```
:root {
  --brand: #e60000;
  --radius: 12px;
  --font: "Segoe UI", Tahoma, Arial, sans-serif;
}
.btn {
  background: var(--brand);
  border-radius: var(--radius);
  font-family: var(--font);
}
.btn.secondary { --brand: #555; }   /* override locally */
```

Transitions and animations

```
.btn { transition: background-color 0.2s ease, transform 0.2s ease; }
.btn:hover { background-color: #b90000; transform: translateY(-2px); }

@keyframes fade-in {
  from { opacity: 0; transform: translateY(8px); }
  to   { opacity: 1; transform: none; }
}
.card { animation: fade-in 0.4s ease-out both; }
```

CSS selectors

Selector	Meaning
*	Universal selector: every element.
element	Type selector: all elements with that tag name.
.class	Class selector: elements with that class.
#id	ID selector: the one element with that id.
[attr]	Attribute present.
[attr="value"]	Attribute equals value.
[attr~="word"]	Attribute contains the word in a space-separated list.
[attr|="en"]	Attribute equals en or starts with en-.
[attr^="https"]	Attribute starts with.
[attr$=".pdf"]	Attribute ends with.
[attr*="example"]	Attribute contains substring.
[attr="v" i]	Case-insensitive match.
A B	Descendant combinator: B anywhere inside A.
A > B	Child combinator: B directly inside A.
A + B	Adjacent sibling: B immediately after A.
A ~ B	General sibling: any B after A with the same parent.
A, B	Selector list: either.
:hover	Pointer is over the element.
:focus / :focus-visible / :focus-within	Element has focus / focus shown by keyboard / a descendant has focus.
:active	Being clicked.
:visited / :link	Visited / unvisited link.
:first-child / :last-child / :only-child	Position among siblings.

Selector	Meaning
:nth-child(an+b) / :nth-last-child()	Position formula: 2n (even), 2n+1 (odd), 3, -n+3 (first three).
:first-of-type / :last-of-type / :nth-of-type()	Position among siblings of the same type.
:not(selector)	Negation.
:is(a, b) / :where(a, b)	Matches any of the list; :where has zero specificity.
:has(selector)	Parent selector: element that contains a match.
:empty	No children (not even text).
:root	The <html> element.
:checked / :indeterminate	Checked checkbox/radio/option.
:disabled / :enabled / :read-only / :read-write	Form control state.
:required / :optional	Form control requirement.
:valid / :invalid / :user-invalid / :in-range / :out-of-range / :placeholder-shown	Validation state.
:target	Element whose id matches the URL fragment.
:lang(ar)	Element language.
:dir(rtl)	Text direction.
:popover-open / :modal / :fullscreen / :open	Top-layer and open states.
::before / ::after	Generated content before/after the element's content (needs content property).

Selector	Meaning
::first-line / ::first-letter	First line / first letter of a block.
::marker	List bullet or number.
::placeholder	Placeholder text in inputs.
::selection	Text selected by the user.
::backdrop	The backdrop behind a modal dialog, popover or fullscreen element.
::part(name) / ::slotted(sel)	Shadow DOM parts and slotted content.
::file-selector-button	The button in a file input.
::cue	WebVTT captions in video.

Selector: *

What it selects

Universal selector: every element.

Example

```
* { box-sizing: border-box; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll('*').length.

Selector: element

What it selects

Type selector: all elements with that tag name.

Example

```
p { line-height: 1.6; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll('element').length.

Selector: .class

What it selects

Class selector: elements with that class.

Example

```
.card { border: 1px solid #ccc; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll('.class').length.

Selector: #id

What it selects

ID selector: the one element with that id.

Example

```
#main { max-width: 960px; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll('#id').length.

Selector: [attr]

What it selects

Attribute present.

Example

```
input[required] { border-left: 3px solid red; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll('[attr]').length.

Selector: [attr="value"]

What it selects

Attribute equals value.

Example

```
input[type="checkbox"] { accent-color: green; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll('[attr="value"]').length.

Selector: [attr~="word"]

What it selects

Attribute contains the word in a space-separated list.

Example

```
[class~="featured"] { ... }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll('[attr~="word"]').length.

Selector: [attr|="en"]

What it selects

Attribute equals en or starts with en-.

Example

```
[lang|="en"] { quotes: '“' '”'; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll('[attr|="en"]').length.

Selector: [attr^="https"]

What it selects

Attribute starts with.

Example

```
a[href^="https"]::after { content: ' ↗'; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll('[attr^="https"]').length.

Selector: [attr$=".pdf"]

What it selects

Attribute ends with.

Example

```
a[href$=".pdf"] { background: url(pdf.svg) no-repeat left; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll('[attr$=".pdf"]').length.

Selector: [attr*="example"]

What it selects

Attribute contains substring.

Example

```
a[href*="example.com"] { color: green; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll('[attr*="example"]').length.

Selector: [attr="v" i]

What it selects

Case-insensitive match.

Example

```
[type="TEXT" i] { ... }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll('[attr="v" i]').length.

Selector: A B

What it selects

Descendant combinator: B anywhere inside A.

Example

```
nav a { text-decoration: none; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll('A B').length.

Selector: A > B

What it selects

Child combinator: B directly inside A.

Example

```
ul > li { list-style: square; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll('A > B').length.

Selector: A + B

What it selects

Adjacent sibling: B immediately after A.

Example

```
h2 + p { margin-top: 0; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll('A + B').length.

Selector: A ~ B

What it selects

General sibling: any B after A with the same parent.

Example

```
h2 ~ p { color: #444; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll('A ~ B').length.

Selector: A, B

What it selects

Selector list: either.

Example

```
h1, h2, h3 { font-family: Georgia, serif; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll('A, B').length.

Selector: :hover

What it selects

Pointer is over the element.

Example

```
a:hover { text-decoration: underline; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll(':hover').length.

Selector: :focus / :focus-visible / :focus-within

What it selects

Element has focus / focus shown by keyboard / a descendant has focus.

Example

```
button:focus-visible { outline: 3px solid #1b6fd8; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll(':focus / :focus-visible / :focus-within').length.

Selector: :active

What it selects

Being clicked.

Example

```
button:active { transform: scale(0.98); }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll(':active').length.

Selector: :visited / :link

What it selects

Visited / unvisited link.

Example

```
a:visited { color: purple; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll(':visited / :link').length.

Selector: :first-child / :last-child / :only-child

What it selects

Position among siblings.

Example

```
li:first-child { font-weight: bold; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll(':first-child / :last-child / :only-child').length.

Selector: :nth-child(an+b) / :nth-last-child()

What it selects

Position formula: 2n (even), 2n+1 (odd), 3, -n+3 (first three).

Example

```
tr:nth-child(even) { background: #f7f7f7; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll(':nth-child(an+b) / :nth-last-child()').length.

Selector: :first-of-type / :last-of-type / :nth-of-type()

What it selects

Position among siblings of the same type.

Example

```
p:first-of-type { font-size: 1.1em; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll(':first-of-type / :last-of-type / :nth-of-type()').length.

Selector: :not(selector)

What it selects

Negation.

Example

```
input:not([type="submit"]) { width: 100%; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll(':not(selector)').length.

Selector: :is(a, b) / :where(a, b)

What it selects

Matches any of the list; :where has zero specificity.

Example

```
:is(h1, h2, h3) a { color: inherit; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll(':is(a, b) / :where(a, b)').length.

Selector: :has(selector)

What it selects

Parent selector: element that contains a match.

Example

```
article:has(img) { display: grid; }
label:has(input:invalid) { color: red; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll(':has(selector)').length.

Selector: :empty

What it selects

No children (not even text).

Example

```
p:empty { display: none; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll(':empty').length.

Selector: :root

What it selects

The <html> element.

Example

```
:root { --gap: 16px; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll(':root').length.

Selector: :checked / :indeterminate

What it selects

Checked checkbox/radio/option.

Example

```
input:checked + label { font-weight: bold; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll(':checked / :indeterminate').length.

Selector: :disabled / :enabled / :read-only / :read-write

What it selects

Form control state.

Example

```
button:disabled { opacity: 0.5; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll(':disabled / :enabled / :read-only / :read-write').length.

Selector: :required / :optional

What it selects

Form control requirement.

Example

```
input:required { border-color: #999; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll(':required / :optional').length.

Selector: :valid / :invalid / :user-invalid / :in-range / :out-of-range / :placeholder-shown

What it selects

Validation state.

Example

```
input:user-invalid { border-color: red; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll(':valid / :invalid / :user-invalid / :in-range / :out-of-range / :placeholder-shown').length.

Selector: :target

What it selects

Element whose id matches the URL fragment.

Example

```
:target { background: #fff9c4; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll(':target').length.

Selector: :lang(ar)

What it selects

Element language.

Example

```
:lang(ar) { font-family: Cairo, sans-serif; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll(':lang(ar)').length.

Selector: :dir(rtl)

What it selects

Text direction.

Example

```
:dir(rtl) .icon { transform: scaleX(-1); }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll(':dir(rtl)').length.

Selector: :popover-open / :modal / :fullscreen / :open

What it selects

Top-layer and open states.

Example

```
dialog:modal { border-radius: 12px; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll(':popover-open / :modal / :fullscreen / :open').length.

Selector: ::before / ::after

What it selects

Generated content before/after the element's content (needs content property).

Example

```
q::before { content: open-quote; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll('::before / ::after').length.

Selector: ::first-line / ::first-letter

What it selects

First line / first letter of a block.

Example

```
p::first-letter { font-size: 2em; float: left; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll('::first-line / ::first-letter').length.

Selector: ::marker

What it selects

List bullet or number.

Example

```
li::marker { color: red; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll('::marker').length.

Selector: ::placeholder

What it selects

Placeholder text in inputs.

Example

```
input::placeholder { color: #999; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll('::placeholder').length.

Selector: ::selection

What it selects

Text selected by the user.

Example

```
::selection { background: #ffd166; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll('::selection').length.

Selector: ::backdrop

What it selects

The backdrop behind a modal dialog, popover or fullscreen element.

Example

```
dialog::backdrop { background: rgb(0 0 0 / 0.6); }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { … }.
- Test any selector in the browser console with document.querySelectorAll('::backdrop').length.

Selector: ::part(name) / ::slotted(sel)

What it selects

Shadow DOM parts and slotted content.

Example

```
my-el::part(label) { color: red; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll('::part(name) / ::slotted(sel)').length.

Selector: ::file-selector-button

What it selects

The button in a file input.

Example

```
input::file-selector-button { padding: 8px; }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll('::file-selector-button').length.

Selector: ::cue

What it selects

WebVTT captions in video.

Example

```
video::cue { background: rgb(0 0 0 / 0.8); }
```

Tips

- Selectors are case-sensitive for class names and IDs, but HTML element names are matched case-insensitively.
- Combine selectors with a comma to apply one rule to several targets: h1, h2, h3 { ... }.
- Test any selector in the browser console with document.querySelectorAll('::cue').length.

CSS property reference

Properties are grouped by purpose. Each entry gives the accepted values, an explanation and an example.

Fonts and text

font-family

Group: Fonts and text

Values

family names and generic family

Description

The typeface used for text. Give a comma-separated list, most preferred first, ending with a generic family (serif, sans-serif, monospace, cursive, fantasy, system-ui, ui-monospace, math, emoji). The browser uses the first font that is installed or loaded with @font-face. Quote names with spaces. Inherited.

Example

```
body { font-family: "Helvetica Neue", Arial, sans-serif; }
code { font-family: ui-monospace, Consolas, monospace; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

font-size

Group: Fonts and text

Values

length | percentage | keyword

Description

The size of the text. Use rem for predictable sizes that respect user preferences (1rem = 16px by default), em for sizes relative to the parent, and clamp() for fluid type. Keywords: xx-small to xxx-large, smaller, larger.

Example

```
html { font-size: 100%; }
h1 { font-size: 2rem; }
p { font-size: clamp(1rem, 0.9rem + 0.5vw, 1.25rem); }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

font-weight

Group: Fonts and text

Values

normal | bold | bolder | lighter | 100-900

Description

Thickness of the strokes. 400 = normal, 700 = bold. Variable fonts support any value in between.

Example

```
strong { font-weight: 700; }
h2 { font-weight: 600; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

font-style

Group: Fonts and text

Values

normal | italic | oblique

Description

Italic or slanted text. , <i>, <cite>, <var>, <dfn>, <address> are italic by default.

Example

```
em { font-style: italic; }
.no-italic { font-style: normal; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

font

Group: Fonts and text

Values

shorthand

Description

Shorthand for font-style, font-variant, font-weight, font-size/line-height and font-family in that order. Size and family are required.

Example

```
body { font: 16px/1.6 Arial, sans-serif; }
h1 { font: bold 2rem Georgia, serif; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

font-variant / font-variant-numeric / font-feature-settings

Group: Fonts and text

Values

various

Description

Typographic features: small caps, tabular numbers (align digits in tables), ligatures, fractions.

Example

```
td.num { font-variant-numeric: tabular-nums; }
.caps { font-variant: small-caps; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

@font-face

Group: Fonts and text

Values

at-rule

Description

Loads a custom font file so it can be used in font-family. Provide woff2, set font-display: swap to show fallback text while loading, and subset by unicode-range for speed.

Example

```
@font-face {
  font-family: "Cairo";
  src: url("cairo.woff2") format("woff2");
  font-weight: 400 700;
  font-display: swap;
}
body { font-family: "Cairo", sans-serif; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

line-height

Group: Fonts and text

Values

normal | number | length | percentage

Description

Height of each line of text. A unitless number (1.5) is best because it scales with the font size and is inherited as a factor. 1.4-1.6 is comfortable for body text.

Example

```
body { line-height: 1.6; }
h1 { line-height: 1.1; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

color

Group: Fonts and text

Values

colour

Description

The colour of the text (and the default for borders and currentColor). Inherited. Ensure at least 4.5:1 contrast with the background for body text.

Example

```
body { color: #1b2431; }
.muted { color: #6b7280; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

text-align

Group: Fonts and text

Values

start | end | left | right | center | justify

Description

Horizontal alignment of inline content inside a block. start/end follow the writing direction (best for multilingual sites). Justified text can create rivers of white space; use with hyphens: auto.

Example

```
footer { text-align: center; }
th { text-align: start; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

text-decoration

Group: Fonts and text

Values

none | underline | overline | line-through, style, colour, thickness

Description

Lines drawn on text. Shorthand for text-decoration-line, -style, -color, -thickness. Links are underlined by default; keep the underline or another clear indicator.

Example

```
a { text-decoration: none; }
a:hover { text-decoration: underline; }
.spelling { text-decoration: red wavy underline; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

text-transform

Group: Fonts and text

Values

none | capitalize | uppercase | lowercase

Description

Changes letter case for display without changing the HTML. Screen readers may spell out all-caps words.

Example

```
h2 { text-transform: uppercase; letter-spacing: 0.05em; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

text-indent

Group: Fonts and text

Values

length | percentage

Description

Indentation of the first line of a block.

Example

```
p + p { text-indent: 1.5em; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

text-shadow

Group: Fonts and text

Values

x y blur colour

Description

Shadow behind text. Several shadows may be listed.

Example

```
h1 { text-shadow: 0 2px 4px rgb(0 0 0 / 0.3); }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

letter-spacing / word-spacing

Group: Fonts and text

Values

normal | length

Description

Extra space between letters or words.

Example

```
.label { letter-spacing: 0.1em; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

white-space

Group: Fonts and text

Values

normal | nowrap | pre | pre-wrap | pre-line | break-spaces

Description

How whitespace and line breaks in the source are handled. normal collapses spaces and wraps; nowrap collapses but never wraps; pre preserves everything (like <pre>); pre-wrap preserves but wraps; pre-line collapses spaces but keeps line breaks.

Example

```
pre { white-space: pre-wrap; }
.nowrap { white-space: nowrap; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

overflow-wrap / word-break / hyphens

Group: Fonts and text

Values

normal | break-word | anywhere / normal | break-all | keep-all / none | manual | auto

Description

Control breaking of long words. overflow-wrap: anywhere breaks only when needed to avoid overflow; word-break: break-all breaks anywhere; hyphens: auto adds hyphens based on lang.

Example

```
p { overflow-wrap: anywhere; hyphens: auto; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

text-overflow

Group: Fonts and text

Values

clip | ellipsis

Description

What to show when text is clipped by overflow: hidden on a single line. Requires white-space: nowrap and overflow: hidden.

Example

```
.title { white-space: nowrap; overflow: hidden; text-overflow:
ellipsis; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

vertical-align

Group: Fonts and text

Values

baseline | sub | super | top | middle | bottom | text-top | text-bottom | length

Description

Vertical alignment of inline or table-cell content. Does not centre block elements; use flexbox for that.

Example

```
img.icon { vertical-align: middle; }
td { vertical-align: top; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

direction / unicode-bidi / writing-mode

Group: Fonts and text

Values

ltr | rtl / normal | embed | isolate | bidi-override / horizontal-tb | vertical-rl | vertical-lr

Description

Text direction and writing mode. Prefer the HTML dir attribute over the CSS direction property. writing-mode enables vertical text for East Asian typography and rotated headings.

Example

```
.vertical { writing-mode: vertical-rl; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

list-style

Group: Fonts and text

Values

shorthand: type position image

Description

Bullets and numbering for lists. list-style-type: disc, circle, square, decimal, lower-alpha, upper-roman, none, or a string. list-style-position: inside | outside. Applies to ul, ol and li.

Example

```
ul { list-style: square inside; }
nav ul { list-style: none; padding: 0; }
ol { list-style-type: upper-roman; }
li::marker { color: #e60000; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

quotes

Group: Fonts and text

Values

pairs of strings

Description

Quotation marks used by <q> and open-quote/close-quote.

Example

```
q { quotes: '«' '»'; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

content

Group: Fonts and text

Values

string | attr() | counter() | url() | open-quote | none

Description

Generated content for ::before and ::after.

Example

```
a[href^="http"]::after { content: " (" attr(href) ")"; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

counter-reset / counter-increment

Group: Fonts and text

Values

name value

Description

CSS counters for automatic numbering of headings, figures, nested lists.

Example

```
body { counter-reset: fig; }
figcaption::before { counter-increment: fig; content: "Figure "
counter(fig) ": "; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

tab-size

Group: Fonts and text

Values

integer | length

Description

Width of tab characters in <pre>.

Example

```
pre { tab-size: 2; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

user-select

Group: Fonts and text

Values

auto | none | text | all

Description

Whether the user can select the text.

Example

```
.no-copy { user-select: none; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

width / height

Group: Box model

Values

auto | length | percentage | min-content | max-content | fit-content

Description

Size of the box (content box by default; border box with box-sizing: border-box). Percentages are relative to the containing block. Prefer max-width for fluid layouts.

Example

```
.container { width: 100%; max-width: 1180px; }
img { width: 100%; height: auto; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

min-width / max-width / min-height / max-height

Group: Box model

Values

length | percentage | none

Description

Limits on size. max-width: 100% on images stops them overflowing; min-height: 100vh makes a section fill the screen.

Example

```
img { max-width: 100%; }
main { min-height: 100dvh; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

aspect-ratio

Group: Box model

Values

auto | ratio

Description

Preferred width-to-height ratio when one dimension is auto. Replaces the old padding-top hack for responsive video.

Example

```
.video { aspect-ratio: 16 / 9; width: 100%; }
.avatar { aspect-ratio: 1; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

box-sizing

Group: Box model

Values

content-box | border-box

Description

Whether width and height include padding and border. border-box is almost always what you want.

Example

```
*, *::before, *::after { box-sizing: border-box; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

margin

Group: Box model

Values

length | percentage | auto (1-4 values)

Description

Space outside the border. One value: all sides; two: vertical horizontal; three: top horizontal bottom; four: top right bottom left (clockwise). margin: 0 auto centres a block with a width. Vertical margins collapse. Logical versions: margin-block, margin-inline.

Example

```
p { margin: 0 0 1em; }
.box { margin: 20px auto; }
.card { margin-inline: auto; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

padding

Group: Box model

Values

length | percentage (1-4 values)

Description

Space between the content and the border. Same value order as margin. Cannot be negative. Backgrounds show through padding.

Example

```
button { padding: 10px 20px; }
.card { padding-block: 1rem; padding-inline: 1.5rem; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

border

Group: Box model

Values

width style colour

Description

Shorthand for border-width, border-style and border-color on all sides. Styles: none, solid, dashed, dotted, double, groove, ridge, inset, outset. Per-side: border-top, border-right, border-bottom, border-left, or logical border-block-start etc.

Example

```
.card { border: 1px solid #e7ddcb; }
blockquote { border-left: 4px solid #c8a24a; }
th, td { border-bottom: 1px solid #ddd; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

border-radius

Group: Box model

Values

length | percentage (1-4 values, optional / for elliptical)

Description

Rounds the corners. 50% on a square makes a circle. Per-corner: border-top-left-radius etc.

Example

```
.btn { border-radius: 8px; }
.avatar { border-radius: 50%; }
.pill { border-radius: 999px; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

border-collapse / border-spacing

Group: Box model

Values

separate | collapse / length

Description

Table borders: collapse merges adjacent cell borders into one; border-spacing sets the gap between cells in separate mode (replaces cellspacing).

Example

```
table { border-collapse: collapse; }
table.spaced { border-collapse: separate; border-spacing: 4px; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

outline

Group: Box model

Values

width style colour

Description

A line drawn outside the border that does not take space. Browsers use it for the keyboard focus ring; never remove it without a replacement. outline-offset moves it away from the edge.

Example

```
:focus-visible { outline: 3px solid #1b6fd8; outline-offset: 2px; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

box-shadow

Group: Box model

Values

x y blur spread colour [inset]

Description

Shadows around the box. Several shadows may be listed, separated by commas.

Example

```
.card { box-shadow: 0 10px 30px rgb(27 36 49 / 0.09); }
.inset { box-shadow: inset 0 0 0 2px #e60000; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

overflow / overflow-x / overflow-y

Group: Box model

Values

visible | hidden | clip | scroll | auto

Description

What happens when content is larger than the box. auto shows scrollbars only when needed. Setting overflow (other than visible) also clips absolutely positioned children and contains floats.

Example

```
.table-wrap { overflow-x: auto; }
.modal-body { max-height: 70vh; overflow-y: auto; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

display

Group: Box model

Values

block | inline | inline-block | flex | grid | none | contents | flow-root | list-item | table...

Description

How the element generates boxes and lays out its children. See the layout table in the CSS introduction.

Example

```
nav ul { display: flex; }
.hidden { display: none; }
span.badge { display: inline-block; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

visibility

Group: Box model

Values

visible | hidden | collapse

Description

hidden makes the element invisible but it still takes up space (unlike display: none). collapse removes table rows/columns.

Example

```
.placeholder { visibility: hidden; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

opacity

Group: Box model

Values

0 to 1

Description

Transparency of the whole element including its children. 0 is invisible but still takes space and receives clicks.

Example

```
.disabled { opacity: 0.5; }
.fade { transition: opacity 0.3s; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

object-fit / object-position

Group: Box model

Values

fill | contain | cover | none | scale-down / position

Description

How a replaced element (img, video) fits its box when the box's ratio differs from the media. cover crops to fill; contain letterboxes.

Example

```
.thumb { width: 200px; height: 150px; object-fit: cover; object-
position: center top; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

resize

Group: Box model

Values

none | both | horizontal | vertical

Description

Whether the user can resize the element (textarea by default).

Example

```
textarea { resize: vertical; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

cursor

Group: Box model

Values

auto | pointer | default | text | move | not-allowed | grab | wait | help | zoom-in | url()

Description

The mouse pointer shape over the element.

Example

```
button, [role="button"] { cursor: pointer; }
.disabled { cursor: not-allowed; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

background-color

Group: Backgrounds

Values

colour | transparent

Description

The colour behind the content and padding.

Example

```
body { background-color: #f6f1e7; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

background-image

Group: Backgrounds

Values

url() | gradient | none

Description

One or more images or gradients layered behind the element, first listed on top. Gradients: linear-gradient(), radial-gradient(), conic-gradient(), repeating-*.

Example

```
.hero { background-image: linear-gradient(rgb(0 0 0 / 0.5), rgb(0 0 0
/ 0.5)), url(hero.jpg); }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

background-size / background-position / background-repeat / background-attachment / background-clip / background-origin

Group: Backgrounds

Values

various

Description

How the image is sized (cover, contain, lengths), placed (center, top right, 50% 50%), repeated (no-repeat, repeat-x), scrolled (fixed for parallax), and which box it fills.

Example

```
.hero { background: url(hero.jpg) center / cover no-repeat; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

background

Group: Backgrounds

Values

shorthand

Description

Shorthand for all background properties: color image position / size repeat attachment origin clip.

Example

```
footer { background: #222 url(pattern.png) repeat; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

filter / backdrop-filter

Group: Backgrounds

Values

blur() | brightness() | contrast() | grayscale() | drop-shadow() | …

Description

Graphical effects applied to the element or to what is behind it (frosted glass).

Example

```
img:hover { filter: brightness(1.1); }
.glass { backdrop-filter: blur(10px); background: rgb(255 255 255 / 0.
6); }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

mix-blend-mode / isolation

Group: Backgrounds

Values

normal | multiply | screen | overlay | difference...

Description

How the element blends with what is behind it.

Example

```
.logo { mix-blend-mode: multiply; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

clip-path / mask

Group: Backgrounds

Values

shapes and images

Description

Clip the element to a shape (circle(), polygon(), inset()) or mask it with an image.

Example

```
.hex { clip-path: polygon(25% 0, 75% 0, 100% 50%, 75% 100%, 25% 100%,
0 50%); }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

position / top / right / bottom / left / inset / z-index

Group: Layout

Values

static | relative | absolute | fixed | sticky

Description

Positioning scheme and offsets. z-index orders positioned (and flex/grid) siblings on the z-axis; higher is in front; it creates stacking contexts.

Example

```
.modal { position: fixed; inset: 0; z-index: 1000; }
.badge { position: absolute; top: -8px; right: -8px; }
header { position: sticky; top: 0; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

float / clear

Group: Layout

Values

left | right | none / left | right | both

Description

Float takes an element out of flow and lets text wrap around it (its original purpose: images in text). Clear moves an element below floats. Not for page layout; use flex/grid.

Example

```
figure.left { float: left; margin: 0 1em 1em 0; }
.after { clear: both; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

flex-direction / flex-wrap / flex-flow

Group: Layout

Values

row | row-reverse | column | column-reverse / nowrap | wrap | wrap-reverse

Description

Direction of the main axis and whether items wrap. flex-flow is the shorthand.

Example

```
.row { display: flex; flex-flow: row wrap; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

justify-content

Group: Layout

Values

flex-start | flex-end | center | space-between | space-around | space-evenly | start | end

Description

Distribution of items along the main axis (flex) or of grid tracks along the inline axis.

Example

```
.toolbar { display: flex; justify-content: space-between; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

align-items / align-self / align-content

Group: Layout

Values

stretch | flex-start | flex-end | center | baseline | start | end

Description

Alignment on the cross axis: for all items, for one item, or for wrapped lines.

Example

```
.center { display: flex; align-items: center; justify-content: center;
 }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

justify-items / justify-self / place-items / place-content / place-self

Group: Layout

Values

start | end | center | stretch

Description

Grid inline-axis alignment and shorthands combining align and justify.

Example

```
.grid { display: grid; place-items: center; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

gap / row-gap / column-gap

Group: Layout

Values

length | percentage

Description

Space between flex items, grid tracks or multi-column columns. Replaces margin hacks.

Example

```
.cards { display: grid; gap: 24px 16px; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

flex / flex-grow / flex-shrink / flex-basis

Group: Layout

Values

number number length|auto

Description

How a flex item grows and shrinks relative to siblings and its starting size. flex: 1 = fill equally; flex: 0 0 200px = fixed 200px; flex: auto = size to content then grow.

Example

```
.sidebar { flex: 0 0 240px; }
.content { flex: 1; min-width: 0; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

order

Group: Layout

Values

integer

Description

Visual order of flex or grid items (does not change tab order; use sparingly).

Example

```
.first { order: -1; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

grid-template-columns / grid-template-rows

Group: Layout

Values

track sizes: length, %, fr, auto, min-content, max-content, minmax(), repeat(), fit-content()

Description

Define the explicit grid tracks. repeat(auto-fit, minmax(240px, 1fr)) creates as many columns as fit.

Example

```
.layout { display: grid; grid-template-columns: 240px 1fr; }
.gallery { grid-template-columns: repeat(auto-fill, minmax(150px,
1fr)); }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

grid-template-areas / grid-area

Group: Layout

Values

strings / name or line numbers

Description

Named regions for readable layouts. Items are placed with grid-area: name.

Example

```
.page { grid-template-areas: "head head" "nav main" "foot foot"; }
footer { grid-area: foot; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

grid-column / grid-row / grid-column-start etc.

Group: Layout

Values

line / span n / name

Description

Place an item by grid lines. span 2 makes it cover two tracks.

Example

```
.wide { grid-column: 1 / -1; }
.tall { grid-row: span 2; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

grid-auto-flow / grid-auto-rows / grid-auto-columns

Group: Layout

Values

row | column | dense / track size

Description

How auto-placed items flow and how implicit tracks are sized.

Example

```
.masonry { grid-auto-flow: dense; grid-auto-rows: 120px; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

columns / column-count / column-width / column-gap / column-rule / column-span / break-inside

Group: Layout

Values

various

Description

Multi-column text like a newspaper.

Example

```
.article { columns: 2 300px; column-gap: 32px; }
figure { break-inside: avoid; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

container-type / container-name / @container

Group: Layout

Values

inline-size | size | normal

Description

Container queries: style an element based on the size of an ancestor container instead of the viewport.

Example

```
.sidebar { container-type: inline-size; }
@container (max-width: 300px) { .card { flex-direction: column; } }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

contain / content-visibility

Group: Layout

Values

layout | paint | size | style / visible | hidden | auto

Description

Performance hints: isolate an element's rendering; content-visibility: auto skips rendering off-screen content.

Example

```
.long-list > li { content-visibility: auto; contain-intrinsic-size:
auto 80px; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

transform / transform-origin / rotate / scale / translate

Group: Motion

Values

translate() rotate() scale() skew() matrix() perspective()

Description

Move, rotate, scale or skew the element without affecting layout; hardware accelerated. The individual properties rotate, scale and translate can be set separately.

Example

```
.card:hover { transform: translateY(-4px) scale(1.02); }
.spin { rotate: 45deg; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

transition / transition-property / -duration / -timing-function / -delay

Group: Motion

Values

property time easing time

Description

Animate changes of properties smoothly. Timing functions: ease, linear, ease-in, ease-out, ease-in-out, cubic-bezier(), steps().

Example

```
a { transition: color 0.2s ease; }
.panel { transition: transform 0.3s cubic-bezier(0.2, 0.8, 0.2, 1); }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

animation / @keyframes

Group: Motion

Values

name duration timing delay iteration-count direction fill-mode play-state

Description

Keyframe animations. Respect prefers-reduced-motion.

Example

```
@keyframes pulse { 50% { opacity: 0.5; } }
.dot { animation: pulse 1s infinite; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

scroll-behavior / scroll-snap-type / scroll-snap-align / scroll-margin / scroll-padding / overscroll-behavior

Group: Motion

Values

various

Description

Smooth scrolling, snap points for carousels, and offsets for fixed headers.

Example

```
html { scroll-behavior: smooth; scroll-padding-top: 80px; }
.carousel { scroll-snap-type: x mandatory; }
.carousel > * { scroll-snap-align: start; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

will-change

Group: Motion

Values

property names

Description

Hint that a property will animate so the browser can optimise. Use sparingly.

Example

```
.drawer { will-change: transform; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

pointer-events

Group: Interaction

Values

auto | none

Description

none makes the element ignore mouse/touch events (clicks pass through).

Example

```
.overlay-text { pointer-events: none; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

accent-color

Group: Interaction

Values

colour

Description

Colour of native checkboxes, radios, range sliders and progress bars.

Example

```
:root { accent-color: #e60000; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

appearance

Group: Interaction

Values

none | auto | base-select

Description

Remove or keep the native look of form controls. none lets you restyle selects and inputs fully.

Example

```
select { appearance: none; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

color-scheme

Group: Interaction

Values

light | dark | light dark

Description

Tells the browser which colour schemes the page supports so form controls and scrollbars match.

Example

```
:root { color-scheme: light dark; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

caret-color

Group: Interaction

Values

colour

Description

Colour of the text cursor.

Example

```
input { caret-color: #e60000; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

touch-action

Group: Interaction

Values

auto | none | pan-x | pan-y | manipulation

Description

Which touch gestures the browser handles; manipulation removes the 300ms tap delay on old mobile browsers.

Example

```
button { touch-action: manipulation; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

field-sizing

Group: Interaction

Values

fixed | content

Description

Make inputs and textareas grow with their content.

Example

```
textarea { field-sizing: content; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

all

Group: Interaction

Values

initial | inherit | unset | revert

Description

Reset every property at once.

Example

```
.reset { all: unset; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

@media

Group: Interaction

Values

at-rule

Description

Conditional rules based on viewport size, orientation, resolution, hover ability, user preferences (prefers-color-scheme, prefers-reduced-motion, prefers-contrast) and output (print, screen).

Example

```
@media (max-width: 600px) { nav { display: none; } }
@media (hover: hover) { a:hover { color: red; } }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

@supports

Group: Interaction

Values

at-rule

Description

Apply rules only if the browser supports a feature.

Example

```
@supports (display: grid) { .layout { display: grid; } }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

@import / @layer / @scope / @property

Group: Interaction

Values

at-rules

Description

Import other style sheets (slow; prefer <link>), define cascade layers, scope styles to a subtree, register typed custom properties.

Example

```
@layer reset, base, components;
@layer base { body { margin: 0; } }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

@page

Group: Interaction

Values

at-rule

Description

Page size and margins for printing.

Example

```
@page { size: A4; margin: 2cm; }
```

Where to apply it

In an external style sheet (recommended), in a <style> element in the <head>, or inline in a style attribute. Check the property in your browser's developer tools (Elements panel, Styles tab): declarations shown struck through are being overridden or are invalid.

Styling HTML elements: cookbook

Styling common HTML elements: a cookbook

A sensible reset

```
*, *::before, *::after { box-sizing: border-box; }
body { margin: 0; font-family: system-ui, -apple-system, "Segoe UI",
Roboto, Arial, sans-serif; line-height: 1.6; color: #1b2431; }
img, video, svg { max-width: 100%; height: auto; display: block; }
button, input, select, textarea { font: inherit; color: inherit; }
h1, h2, h3, h4 { line-height: 1.2; margin-block: 0 0.5em; }
p, ul, ol, dl, table, figure, pre { margin-block: 0 1em; }
```

Links

```
a { color: #0b57d0; text-underline-offset: 2px; }
a:hover { color: #083b8f; }
a:focus-visible { outline: 3px solid #0b57d0; outline-offset: 2px;
border-radius: 2px; }
a[href^="http"]:not([href*="mysite.com"])::after { content: " ↗";
font-size: 0.8em; }
```

Headings with a fluid scale

```
h1 { font-size: clamp(1.8rem, 1.2rem + 2.5vw, 3rem); }
h2 { font-size: clamp(1.4rem, 1rem + 1.5vw, 2rem); }
h3 { font-size: 1.25rem; }
```

Lists

```
/* Default bullets tweaked */
ul { padding-inline-start: 1.25em; }
li + li { margin-top: 0.25em; }
li::marker { color: #e60000; }

/* Bullet-less horizontal menu */
.menu { list-style: none; margin: 0; padding: 0; display: flex; gap:
1rem; }

/* Custom check bullets */
.checks { list-style: none; padding: 0; }
.checks li::before { content: "✓ "; color: #0f8a4c; font-weight: bold;
 }

/* Description list as a two-column grid */
```

```
dl.specs { display: grid; grid-template-columns: max-content 1fr; gap:
 0.25rem 1rem; }
dl.specs dt { font-weight: 600; }
dl.specs dd { margin: 0; }
```

Tables

```
table { border-collapse: collapse; width: 100%; font-variant-numeric:
tabular-nums; }
caption { caption-side: top; text-align: start; font-weight: 600;
padding-block: 0.5rem; }
th, td { padding: 0.5rem 0.75rem; border-bottom: 1px solid #e5e5e5;
text-align: start; vertical-align: top; }
thead th { background: #f5f5f5; position: sticky; top: 0; }
tbody tr:nth-child(even) { background: #fafafa; }
tbody tr:hover { background: #fff4e0; }
td.num, th.num { text-align: end; }
.table-wrap { overflow-x: auto; }   /* wrap the table for small
screens */

/* Stacked table on phones */
@media (max-width: 600px) {
  .stack thead { display: none; }
  .stack tr { display: block; margin-bottom: 1rem; border: 1px solid
#ddd; }
  .stack td { display: flex; justify-content: space-between; }
  .stack td::before { content: attr(data-label); font-weight: 600; }
}
```

Forms

```
.field { display: grid; gap: 0.25rem; margin-bottom: 1rem; }
label { font-weight: 600; }
input, select, textarea { padding: 0.6rem 0.75rem; border: 1px solid
#c9c9c9; border-radius: 8px; background: #fff; }
input:focus-visible, select:focus-visible, textarea:focus-visible {
outline: 3px solid #0b57d0; outline-offset: 1px; border-color:
#0b57d0; }
input:user-invalid { border-color: #b90000; }
input:disabled { background: #f0f0f0; cursor: not-allowed; }
::placeholder { color: #8a8a8a; }
fieldset { border: 1px solid #ddd; border-radius: 8px; padding: 1rem;
}
legend { padding: 0 0.5rem; font-weight: 600; }
input[type="checkbox"], input[type="radio"] { width: 1.1em; height: 1.
1em; accent-color: #e60000; }
button { padding: 0.65rem 1.25rem; border: 0; border-radius: 8px;
background: #e60000; color: #fff; font-weight: 600; cursor: pointer; }
button:hover { background: #b90000; }
button:disabled { opacity: 0.5; cursor: not-allowed; }
```

Header, nav, main, footer layout

```
body { min-height: 100dvh; display: flex; flex-direction: column; }
header { position: sticky; top: 0; z-index: 10; background: #fff; box-shadow: 0 1px 0 #eee; }
header .wrap { display: flex; align-items: center; justify-content: space-between; gap: 1rem; padding: 0.75rem 1rem; }
nav ul { display: flex; gap: 1.25rem; list-style: none; margin: 0; padding: 0; }
nav a[aria-current="page"] { border-bottom: 2px solid #e60000; }
main { flex: 1; width: min(100% - 2rem, 1180px); margin-inline: auto; padding-block: 2rem; }
footer { background: #222; color: #ddd; text-align: center; padding: 2rem 1rem; margin-top: auto; }
footer a { color: #ffd166; }
```

Images and figures

```
figure { margin: 0 0 1.5rem; }
figure img { border-radius: 12px; }
figcaption { font-size: 0.9rem; color: #666; margin-top: 0.5rem; text-align: center; }
.avatar { width: 64px; aspect-ratio: 1; border-radius: 50%; object-fit: cover; }
.hero img { width: 100%; height: 50vh; object-fit: cover; }
```

Code and pre

```
code { font-family: ui-monospace, Consolas, "Courier New", monospace; font-size: 0.95em; background: #f4f4f4; padding: 0.1em 0.3em; border-radius: 4px; }
pre { background: #1e1e1e; color: #eee; padding: 1rem; border-radius: 8px; overflow-x: auto; tab-size: 2; }
pre code { background: none; padding: 0; color: inherit; }
kbd { border: 1px solid #bbb; border-bottom-width: 2px; border-radius: 4px; padding: 0 0.35em; background: #fafafa; font-size: 0.9em; }
```

Blockquote, hr, details

```
blockquote { margin: 1.5rem 0; padding: 0.75rem 1.25rem; border-inline-start: 4px solid #c8a24a; background: #fdf8f0; }
blockquote footer { font-size: 0.9rem; color: #666; }
hr { border: 0; border-top: 1px solid #e0e0e0; margin: 2rem 0; }
details { border: 1px solid #ddd; border-radius: 8px; padding: 0.5rem 1rem; }
summary { cursor: pointer; font-weight: 600; }
details[open] summary { margin-bottom: 0.5rem; }
```

Dialog and popover

```
dialog { border: 0; border-radius: 16px; padding: 1.5rem; max-width:
```

```
min(90vw, 480px); box-shadow: 0 24px 60px rgb(0 0 0 / 0.25); }
dialog::backdrop { background: rgb(0 0 0 / 0.5); backdrop-filter:
blur(2px); }
[popover] { border: 1px solid #ddd; border-radius: 12px; padding:
1rem; box-shadow: 0 10px 30px rgb(0 0 0 / 0.15); }
[popover]:popover-open { animation: fade-in 0.15s ease-out; }
```

Visually hidden (for screen readers only)

```
.sr-only {
  position: absolute; width: 1px; height: 1px; padding: 0; margin: -
1px;
  overflow: hidden; clip: rect(0 0 0 0); white-space: nowrap; border:
0;
}
```

Dark mode

```
:root { color-scheme: light dark; --bg: #fff; --ink: #1b2431; }
@media (prefers-color-scheme: dark) { :root { --bg: #111; --ink: #eee;
 } }
body { background: var(--bg); color: var(--ink); }
```

Lists and tables with CSS

Lists group related items; tables display structured data (information arranged in rows and columns so that it is easy to scan). Combining the right HTML element with a little CSS makes both far more readable and accessible. This chapter walks through every common styling task for <ul>, <ol>, <dl> and <table>, step by step, with complete copy-and-paste examples.

1. Unordered and ordered lists

Use <ul> for unordered lists (bullets) and <ol> for ordered lists (numbers). Each item goes in an <li>. The browser adds the bullets or numbers automatically, indents the list about 40 pixels and adds a blank line before and after it.

```
<ul class="features">
  <li>Responsive layout</li>
  <li>Semantic HTML</li>
  <li>Accessible components</li>
</ul>

<ol class="steps">
  <li>Plan content</li>
  <li>Structure markup</li>
  <li>Apply typography and layout</li>
</ol>
```

Changing the marker: list-style-type

The list-style-type property chooses the bullet or numbering style. It replaces the obsolete HTML type attribute.

Value	Works on	Result
disc (default for ul)	ul	Filled circle
circle	ul	Hollow circle

Value	Works on	Result
square	ul	Filled square
none	ul, ol	No marker at all (used for menus and navigation)
decimal (default for ol)	ol	1, 2, 3
decimal-leading-zero	ol	01, 02, 03
lower-alpha / upper-alpha	ol	a, b, c / A, B, C
lower-roman / upper-roman	ol	i, ii, iii / I, II, III
lower-greek	ol	alpha, beta, gamma
arabic-indic	ol	Arabic-Indic digits used in Arabic-language pages
'\2192 ' or any string	ul	A custom character such as an arrow or a check mark

```
ul.a { list-style-type: circle; }
ul.b { list-style-type: square; }
ol.c { list-style-type: upper-roman; }
ol.d { list-style-type: lower-alpha; }
ul.arrows { list-style-type: '\2192 '; }   /* a right arrow before
every item */
```

Image markers and marker position

```
ul { list-style-image: url('sqpurple.gif'); }

/* inside: the marker is part of the text and wraps with it;
   outside (default): the marker hangs in the left margin */
ul.inside  { list-style-position: inside; }
ul.outside { list-style-position: outside; }
```

The list-style shorthand

list-style sets type, position and image in one declaration, in that order. Missing values return to their defaults.

```
ul { list-style: square inside url('sqpurple.gif'); }
```

Removing default settings

To use a list as a menu, remove the marker, the margin and the padding. Setting margin and padding to 0 on the <ul> removes the indentation that browsers add; without this step the items still sit 40 pixels from the left edge.

```
ul.menu {
  list-style-type: none;
  margin: 0;
  padding: 0;
}
```

Styling the marker itself: ::marker

The ::marker pseudo-element styles only the bullet or number, leaving the item text alone. It accepts colour, font and content properties.

```
li::marker { color: #b90000; font-weight: bold; }
ol li::marker { content: counter(list-item) ') '; }
```

Custom markers with ::before (the W3Schools 'features' pattern)

For complete control replace the marker with generated content. The rules below remove the default bullets, space the items with Grid gap, give every item a card look and insert a check mark with ::before.

```
.features {
  list-style: none;
  padding: 0;
  margin: 0;
  display: grid;
  gap: 12px;
}
.features li {
  padding: 16px 20px;
  background: #fff;
  border-radius: 12px;
  box-shadow: 0 10px 25px rgba(15, 23, 42, 0.08);
}
```

```
.features li::before {
  content: '\2714';      /* heavy check mark */
  color: #04AA6D;
  margin-right: 12px;
}
```

Colouring lists

Anything added to the <ul> or <ol> affects the whole list; anything added to <li> affects one item. Padding on the list moves the markers inward as well.

```
ol {
  background: #ff9999;
  padding: 20px;
}
ul {
  background: #3399ff;
  padding: 20px;
}
ol li {
  background: #ffe5e5;
  color: darkred;
  padding: 5px;
  margin-left: 35px;
}
ul li {
  background: #cce5ff;
  color: darkblue;
  margin: 5px;
}
```

Horizontal lists: navigation bars

A navigation bar is just a list of links laid out in a row. Flexbox is the modern way; float was used before 2015.

```
<nav>
  <ul class="navbar">
    <li><a href="index.html">Home</a></li>
    <li><a href="books.html">Books</a></li>
    <li><a href="contact.html">Contact</a></li>
  </ul>
</nav>

<style>
.navbar {
  list-style: none;
```

```
  margin: 0;
  padding: 0;
  display: flex;
  gap: 4px;
  background: #333;
}
.navbar a {
  display: block;
  padding: 14px 16px;
  color: white;
  text-decoration: none;
}
.navbar a:hover { background: #111; }
</style>
```

Numbered lists with counters

CSS counters number anything, including nested headings, and let you style the number separately.

```
ol.fancy { counter-reset: item; list-style: none; padding: 0; }
ol.fancy li { counter-increment: item; margin: 8px 0; }
ol.fancy li::before {
  content: counter(item);
  display: inline-block;
  width: 1.6em; height: 1.6em; line-height: 1.6em;
  margin-right: .6em;
  text-align: center;
  border-radius: 50%;
  background: #b90000;
  color: white;
  font-weight: bold;
}
```

2. Description lists

Use <dl> with <dt> (term) and <dd> (definition) for glossaries or metadata. Browsers indent the <dd> by about 40 pixels; with CSS Grid you can lay terms and definitions out in two columns.

```
<dl class="glossary">
  <dt>HTML</dt>
  <dd>Structure of a web page.</dd>
  <dt>CSS</dt>
  <dd>Presentation and layout.</dd>
</dl>
```

```
<style>
.glossary {
  display: grid;
  grid-template-columns: max-content 1fr;
  gap: 6px 16px;
}
.glossary dt { font-weight: bold; color: #b90000; }
.glossary dd { margin: 0; }
</style>
```

3. HTML tables

<table> organises tabular data with rows (<tr>), header cells (<th>) and data cells (<td>). Tabular data is information best shown in a grid, such as price lists or schedules. Group the header row in <thead> and the data in <tbody>, and give every <th> a scope attribute so screen readers know whether it labels a column or a row.

```
<table class="pricing">
  <caption>Subscription plans</caption>
  <thead>
    <tr>
      <th scope="col">Plan</th>
      <th scope="col">Price</th>
      <th scope="col">Features</th>
    </tr>
  </thead>
  <tbody>
    <tr>
      <th scope="row">Starter</th>
      <td>$0</td>
      <td>Basic components</td>
    </tr>
    <tr>
      <th scope="row">Pro</th>
      <td>$19</td>
      <td>Advanced layouts</td>
    </tr>
  </tbody>
</table>
```

Table borders

A table has no visible borders by default. The border property must be set on the table AND on the cells; setting it on the table alone draws only the outer frame. Because each cell has its own border you get a double line between cells until you collapse them.

```
table, th, td {
  border: 1px solid black;
}
```

Collapsed borders

border-collapse: collapse merges adjacent cell borders into a single line. This is almost always what you want. The old HTML cellspacing attribute is replaced by border-spacing (only in the separate model) and cellpadding by padding on the cells.

```
table {
  border-collapse: collapse;
}
th, td {
  border: 1px solid #ddd;
  padding: 8px;
}

/* alternative: keep separate borders but control the gap */
table.spaced { border-collapse: separate; border-spacing: 6px 2px; }
```

Rounded or borderless tables

For a light look, add only a bottom border to each row. For rounded corners set overflow: hidden and border-radius on the table.

```
table { border-collapse: collapse; width: 100%; }
td, th { border-bottom: 1px solid #ddd; padding: 12px; }

table.rounded { border-radius: 12px; overflow: hidden; }
```

Table size

Width and height are set with CSS width and height on the table, rows or cells. width: 100% makes the table fill its container. The obsolete HTML width attribute did the same job.

```
table { width: 100%; }
th { height: 70px; }
td.narrow { width: 70px; }
table.fixed { table-layout: fixed; }   /* equal columns regardless of
content */
```

Alignment

text-align sets horizontal alignment (th content is centred and bold by default, td content is left aligned); vertical-align sets vertical alignment (middle by default). These replace the align and valign attributes.

```
th { text-align: left; }
td { text-align: center; height: 50px; vertical-align: bottom; }
```

Padding and spacing

padding on th/td controls the space between the border and the content. To add space between cells themselves use border-spacing (separate border model only).

```
th, td { padding: 15px; }
th, td { padding-top: 10px; padding-bottom: 20px; padding-left: 30px;
padding-right: 40px; }
```

Horizontal dividers, hover and zebra stripes

Highlight rows on hover with :hover on <tr>, and zebra-stripe with :nth-child(even). Both make long tables easier to read.

```
tr:hover { background-color: coral; }
tr:nth-child(even) { background-color: #f2f2f2; }

/* vertical zebra stripes */
th:nth-child(even), td:nth-child(even) { background-color: #d6eeee; }

/* combining both with transparency */
tr:nth-child(even) { background-color: rgba(150, 212, 212, 0.4); }
th:nth-child(even), td:nth-child(even) { background-color: rgba(150,
```

```
212, 212, 0.4); }
```

Styling the header row

```
.pricing {
  width: 100%;
  border-collapse: collapse;
  background: #fff;
  border-radius: 12px;
  overflow: hidden;
}
.pricing th, .pricing td {
  padding: 16px 20px;
  text-align: left;
}
.pricing thead {
  background: #04AA6D;
  color: #fff;
}
.pricing tbody tr:nth-child(even) {
  background: #f9fafb;
}
```

Key rules: border-collapse: collapse removes gaps, header styling highlights the labels, and :nth-child(even) zebra-stripes the rows.

Colouring individual columns

```
<table>
  <colgroup>
    <col span="2" style="background-color: #D6EEEE">
  </colgroup>
  <tr><th>MON</th><th>TUE</th><th>WED</th></tr>
  ...
</table>
```

Only a few properties work on <col>: width, visibility, background and border. For anything else target td:nth-child(n).

Responsive tables

Tables can overflow on small screens. Wrapping them in a scroll container preserves readability: mobile users swipe sideways instead of the table breaking the layout. The

wrapper is a with overflow-x: auto.

```
<div class="table-wrapper">
  <table>...</table>
</div>

<style>
.table-wrapper { overflow-x: auto; }
</style>
```

An alternative for narrow screens is to turn each row into a block and print the column label with a data attribute:

```
@media (max-width: 600px) {
  thead { display: none; }
  tr { display: block; margin-bottom: 1em; border: 1px solid #ddd; }
  td { display: flex; justify-content: space-between; padding: 8px; }
  td::before { content: attr(data-label); font-weight: bold; }
}

<!-- HTML -->
<td data-label="Price">$19</td>
```

Sticky header and caption position

```
thead th { position: sticky; top: 0; background: #fff; }
caption { caption-side: bottom; font-style: italic; padding: 8px; }
table.no-empty { empty-cells: hide; }
```

4. Accessibility tips for tables

- Always use <th> for headers and add the scope attribute (col or row). It tells assistive technology which header belongs to which cell.
- Provide captions with <caption> when the table's purpose is not obvious from the surrounding text.
- Keep tables for data, not layout. Use CSS Grid or Flexbox for page layout.
- Do not rely on colour alone (for example a red cell for 'sold out'); add text or an icon as well.

- Avoid merged cells (rowspan/colspan) in data tables where possible; if you need them, add headers/id associations.
- Right-align numbers so that digits line up, and use the same number of decimals in a column.

5. Complete example: course outline with a list and a table

This demo pairs a topic list with a simple table. The list uses square bullets while the table collapses its borders for a clean grid, with coloured headers to improve readability.

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <title>Course Outline</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <h1>Course Outline</h1>
  <ul>
    <li>HTML Basics</li>
    <li>CSS Essentials</li>
    <li>Responsive Layouts</li>
  </ul>
  <table>
    <tr><th>Module</th><th>Duration</th></tr>
    <tr><td>Getting Started</td><td>2 hrs</td></tr>
    <tr><td>Flexbox &amp; Grid</td><td>3 hrs</td></tr>
  </table>
</body>
</html>
```

```
/* styles.css */
body {
  font-family: 'Segoe UI', sans-serif;
  padding: 48px;
  background: #eef2ff;
}
ul {
  list-style: square;
}
table {
```

```
  margin-top: 32px;
  border-collapse: collapse;
  width: 100%;
  max-width: 640px;
  background: #fff;
}
th, td {
  border: 1px solid #d9e2ec;
  padding: 12px 16px;
  text-align: left;
}
th {
  background: #6366f1;
  color: #fff;
}
```

6. Quick reference: list and table properties

Property	Applies to	Purpose
list-style-type	ul, ol, li	Marker shape or numbering system
list-style-image	ul, ol, li	Image as marker
list-style-position	ul, ol, li	Marker inside or outside the item box
list-style	ul, ol, li	Shorthand for the three above
::marker	li	Style the marker only
counter-reset / counter-increment / counter()	any	Custom numbering
border-collapse	table	collapse or separate cell borders
border-spacing	table	Gap between cells (separate model)
caption-side	table	Caption above (top) or below (bottom)
empty-cells	table	show or hide borders of empty cells
table-layout	table	auto (content sized) or fixed (equal, faster)
vertical-align	td, th	top, middle, bottom

Property	Applies to	Purpose
text-align	td, th	left, center, right
padding	td, th	Space inside cells (replaces cellpadding)
:nth-child(even/odd)	tr, td	Zebra stripes
tr:hover	tr	Row highlight
overflow-x: auto	wrapper div	Scrollable table on small screens

7. Old HTML attributes and their CSS replacements

Old attribute (HTML 3.2 / 4)	Element	Use instead
type="square"	ul	list-style-type: square
type="A" / type="i"	ol	list-style-type: upper-alpha / lower-roman (type on ol is still allowed but CSS is preferred)
compact	ul, ol, dl	margin / line-height
border="1"	table	border on table, th, td
cellpadding	table	padding on th, td
cellspacing	table	border-spacing (or border-collapse: collapse)
width / height	table, td	width / height in CSS
bgcolor	table, tr, td	background-color
align	table, tr, td	text-align / margin: 0 auto
valign	tr, td	vertical-align
nowrap	td	white-space: nowrap
frame / rules	table	border on the relevant sides

Old attribute (HTML 3.2 / 4)	Element	Use instead
summary	table	<caption> or aria-describedby

Part 12

HTML and CSS Course

Thirty-six lessons from first page to finished project, following the W3Schools HTML and CSS tutorial.

About this course

This part is a guided course rather than a reference: read the lessons in order, type the examples, and change them. Its structure follows the W3Schools HTML and CSS tutorial (foundations, styling core, layout, enhancements, quality, project). Whenever a lesson mentions an element or property, the full details are in Parts 6 and 11.

Lesson	Topic
1	Introduction and environment setup
2	Your first web page
3	Essentials - elements, attributes and nesting
4	Document structure
5	Text content
6	Lists and tables
7	Links and navigation
8	Images and media
9	Forms and validation
10	Reusable components
11	Styling essentials - the three ways to add CSS
12	Selectors and specificity
13	Cascade and inheritance
14	Typography
15	Colours and backgrounds
16	The box model
17	Layout fundamentals - normal flow
18	Positioning and z-index

Lesson	Topic
19	Flexbox
20	CSS Grid
21	Layout patterns
22	Responsive design
23	Responsive components
24	Custom properties (CSS variables)
25	calc() and CSS functions
26	Transitions
27	Transforms
28	Animations
29	Effects and filters
30	Accessibility
31	Design systems
32	Performance
33	Debugging and testing
34	Tooling and automation (optional)
35	Project - a complete landing page
36	Quick quiz and answers

Lesson 1: Introduction and environment setup

HTML gives a page its structure and meaning; CSS gives it appearance and layout. Together they are the two languages every web page is made of. HTML says 'this is a heading, this is a list of three items, this is a table of prices'; CSS says 'headings are dark red and 28 pixels, the list has no bullets and sits in a row, the table has thin grey lines'.

What you need

- A text editor. Any editor that saves plain text works: UltraEdit, Notepad++, Sublime Text or VS Code. Turn on syntax highlighting for HTML and CSS.
- A browser: Chrome, Edge or Firefox. Its developer tools (press F12) show you the HTML tree, the CSS applied to each element and the box model.
- A folder for your project, for example C:\Users\you\Documents\bookshop. Keep index.html, styles.css and an images folder inside it.
- Nothing else. No server, no installation, no account. Open the .html file in the browser by double-clicking it or dragging it into a tab.

Workflow

- Write or change a file in the editor and save it (Ctrl+S).
- Switch to the browser and reload (F5). The page shows the change immediately.
- If something looks wrong, right-click it and choose Inspect. The Elements panel shows the exact HTML and the Styles panel shows which CSS rules apply and which are crossed

out (overridden).

- Validate occasionally with https://validator.w3.org/ (HTML) and https://jigsaw.w3.org/css-validator/ (CSS) to catch typos such as unclosed tags or misspelled properties.

File naming rules

- Use lower-case names with no spaces: about-us.html, not About Us.html. Web servers are case-sensitive and spaces become %20 in URLs.
- The home page is index.html: servers show it automatically when someone visits the folder.
- Save with UTF-8 encoding (in UltraEdit: File > Save As > Encoding: UTF-8, no BOM). Declare it with <meta charset="utf-8"> so that Arabic, accents and symbols display correctly.

Lesson 2: Your first web page

Every page has the same skeleton. Type it once, save it as index.html and open it in the browser.

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>My first page</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header>
    <h1>Hello, world</h1>
    <nav>
      <a href="index.html">Home</a>
      <a href="about.html">About</a>
    </nav>
  </header>
  <main>
    <p>This is my first web page. It has a heading, a paragraph and a
link to
       <a href="https://developer.mozilla.org">MDN</a>.</p>
  </main>
  <footer>
    <p>&copy; 2026 My Name</p>
  </footer>
</body>
</html>
```

Line	What it does
<!DOCTYPE html>	Tells the browser this is modern HTML (standards mode). Always the first line.
<html lang="en">	Root element. lang tells screen readers and translators the language (ar for Arabic, with dir="rtl").
<head>	Information about the page that is not displayed: encoding, title, links to CSS.
<meta charset="utf-8">	Character encoding; prevents garbled text.

Line	What it does
<meta name="viewport" ...>	Makes the page scale correctly on phones. Without it, mobile browsers pretend to be 980px wide.
<title>	Text in the browser tab, bookmarks and search results.
<link rel="stylesheet">	Loads the CSS file.
<body>	Everything visible.
<header>, <nav>, <main>, <footer>	Semantic landmarks: which part of the page is which.

Add the style sheet

Create styles.css in the same folder:

```
body {
  font-family: system-ui, Arial, sans-serif;
  line-height: 1.6;
  max-width: 60rem;
  margin: 0 auto;
  padding: 1rem;
  color: #1b2431;
}
h1 { color: #b90000; }
nav a { margin-right: 1rem; }
footer { margin-top: 3rem; font-size: .9rem; color: #666; }
```

Reload the browser. If nothing changes, check that the file is really called styles.css (not styles.css.txt), that it is in the same folder as index.html, and that the href in <link> matches exactly.

Lesson 3: Essentials - elements, attributes and nesting

An element is a start tag, content and an end tag: text . Attributes go inside the start tag as name="value" pairs. Some elements are void: they have no content and no end tag (
, <img>, <input>, <meta>, <link>, <hr>).

```
<a href="books.html" class="button" id="catalogue-link" title="See
all books">Catalogue</a>
<img src="cover.jpg" alt="Cover of Learn HTML" width="300"
height="400">
```

Nesting

Elements nest like boxes: close the inner one before the outer one. right is correct; wrong is not. Indent nested elements two spaces so the structure is visible in your editor.

Block and inline

Block-level elements (p, div, h1, ul, table, section...) start on a new line and stretch across the container. Inline elements (a, em, strong, span, img, code...) flow within the text. A block may contain inline elements; an inline element may not contain a block (except that <a> may wrap blocks in HTML5). CSS display can change this behaviour.

Comments and whitespace

```
<!-- This is a comment. Browsers ignore it. -->
<p>Multiple     spaces
   and line breaks collapse to a single space.</p>
```

Entities

Characters that have a meaning in HTML must be written as entities: < for <, > for >, & for &.   is a

non-breaking space; © is the copyright sign. See the entity table in the Value References part.

Lesson 4: Document structure

Use semantic elements to describe the parts of the page. They mean nothing visually (all look like a) but give screen readers, search engines and other developers a map of the page.

Element	Use for	How many per page
<header>	Introductory content of the page or of a section: logo, title, navigation	One per page plus one per article/section if needed
<nav>	Major navigation blocks	Usually one or two
<main>	The unique content of this page	Exactly one
<article>	Self-contained composition: blog post, product, comment	Any number
<section>	Thematic grouping with a heading	Any number
<aside>	Tangential content: sidebar, pull quote, related links	Any number
<footer>	Footer of the page or a section: copyright, contact, links	One per page plus per section

Element	Use for	How many per page
	Generic container when no semantic element fits (mostly for styling)	Any number

```
<body>
  <header>
    <h1>Cairo Book Shop</h1>
    <nav aria-label="Main">
      <ul>
        <li><a href="/">Home</a></li>
        <li><a href="/books/">Books</a></li>
        <li><a href="/contact/">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main>
    <article>
      <h2>New arrivals</h2>
      <p>...</p>
    </article>
    <aside>
      <h2>Opening hours</h2>
      <p>Saturday to Thursday, 10:00 to 22:00</p>
    </aside>
  </main>
  <footer>
    <p>&copy; 2026 Cairo Book Shop &middot; <a href="/privacy/
">Privacy</a></p>
  </footer>
</body>
```

Headings

Use one <h1> for the page title, then <h2> for main sections, <h3> inside them, and so on. Never skip levels for looks (h2 then h4); change the size with CSS instead. Screen reader users navigate by headings, so the outline must make sense on its own.

Lesson 5: Text content

Text elements carry meaning. Choose by what the text IS, not by how you want it to look; then style with CSS.

Element	Meaning	Default look
<p>	Paragraph	Block with space above and below
<h1>-<h6>	Headings	Bold, decreasing sizes
	Strong importance	Bold
	Stress emphasis	Italic
<b>	Keywords, product names, no extra importance	Bold
<i>	Different voice: technical term, foreign phrase, thought	Italic
<mark>	Highlighted for reference	Yellow background
<small>	Side comment, legal text	Smaller
<s>	No longer accurate	Strikethrough
<del> / <ins>	Removed / added text	Strikethrough / underline
<sub> / <sup>	Subscript / superscript	H2O, x2
<code>	Code fragment	Monospace
<kbd>	Keyboard input	Monospace
<samp>	Program output	Monospace

Element	Meaning	Default look
<var>	Variable	Italic
<abbr title="...">	Abbreviation	Dotted underline
<time datetime="...">	Date/time	Plain
<q>	Short inline quotation	Quotation marks
<blockquote>	Long quotation	Indented block
<cite>	Title of a work	Italic
<pre>	Preformatted text (keeps spaces and line breaks)	Monospace block
 	Line break (addresses, poems only)	-
<hr>	Thematic break	Horizontal rule

```
<article>
  <h2>Learn HTML, <small>2nd edition</small></h2>
  <p>Published <time datetime="2026-03-01">1 March 2026</time>.
     <strong>Only 5 copies left.</strong> Price: <s>150 EGP</s>
<mark>120 EGP</mark>.</p>
  <p>Press <kbd>Ctrl</kbd>+<kbd>S</kbd> to save. The <abbr
title="HyperText Markup Language">HTML</abbr> file is <code>index.
html</code>.</p>
  <blockquote cite="https://example.com/review">
    <p>The clearest introduction I have read.</p>
    <footer>&mdash; <cite>Web Weekly</cite></footer>
  </blockquote>
</article>
```

Typography basics in CSS

```
body { font-family: Georgia, 'Times New Roman', serif; font-size: 1.
05rem; line-height: 1.6; }
h1, h2, h3 { font-family: system-ui, sans-serif; line-height: 1.2; }
p { margin: 0 0 1em; max-width: 65ch; }   /* 65 characters per line
is comfortable */
```

Lesson 6: Lists and tables

Lists group related items; tables display structured data. This lesson is a summary; the chapter 'Lists and tables with CSS' in the CSS part covers every styling option in detail.

```
<ul class="features">
  <li>Responsive layout</li>
  <li>Semantic HTML</li>
  <li>Accessible components</li>
</ul>
<ol class="steps">
  <li>Plan content</li>
  <li>Structure markup</li>
  <li>Apply typography and layout</li>
</ol>
<dl class="glossary">
  <dt>HTML</dt><dd>Structure of a web page.</dd>
  <dt>CSS</dt><dd>Presentation and layout.</dd>
</dl>
```

```
/* card-style list with custom check marks */
.features { list-style: none; padding: 0; margin: 0; display: grid;
gap: 12px; }
.features li { padding: 16px 20px; background: #fff; border-radius:
12px;
               box-shadow: 0 10px 25px rgba(15, 23, 42, 0.08); }
.features li::before { content: '\2714'; color: #04AA6D; margin-right:
 12px; }
```

```
<table class="pricing">
  <thead>
    <tr><th scope="col">Plan</th><th scope="col">Price</th><th
scope="col">Features</th></tr>
  </thead>
  <tbody>
    <tr><th scope="row">Starter</th><td>$0</td><td>Basic components</
td></tr>
    <tr><th scope="row">Pro</th><td>$19</td><td>Advanced layouts</
td></tr>
  </tbody>
</table>
```

```
.pricing { width: 100%; border-collapse: collapse; background: #fff;
border-radius: 12px; overflow: hidden; }
.pricing th, .pricing td { padding: 16px 20px; text-align: left; }
.pricing thead { background: #04AA6D; color: #fff; }
.pricing tbody tr:nth-child(even) { background: #f9fafb; }
```

```
.table-wrapper { overflow-x: auto; }   /* wrap the table in this div
for small screens */
```

- Always use <th> for headers and add scope="col" or scope="row".
- Provide a <caption> when the table's purpose is not obvious.
- Keep tables for data, not layout.

Lesson 7: Links and navigation

The <a> element with an href attribute creates a hyperlink. The href can be absolute, relative to the current file, a fragment (#id) on the same page, or a special scheme such as mailto: or tel:.

```
<a href="https://example.com/">Absolute URL</a>
<a href="books/learn-html.html">Relative: file in the books folder</a>
<a href="../index.html">Relative: parent folder</a>
<a href="/contact/">Site-root relative</a>
<a href="#prices">Jump to the element with id="prices"</a>
<a href="mailto:info@example.com">Email us</a>
<a href="tel:+201001234567">Call us</a>
<a href="catalogue.pdf" download>Download the catalogue (PDF)</a>
<a href="https://partner.example" target="_blank"
rel="noopener">Opens in a new tab</a>
```

Navigation bar

```
<nav aria-label="Main">
  <ul class="nav">
    <li><a href="/" aria-current="page">Home</a></li>
    <li><a href="/books/">Books</a></li>
    <li><a href="/about/">About</a></li>
  </ul>
</nav>

<style>
.nav { display: flex; gap: 4px; list-style: none; margin: 0; padding:
0; background: #1b2431; }
.nav a { display: block; padding: 12px 18px; color: #fff; text-
decoration: none; }
.nav a:hover, .nav a:focus-visible { background: #b90000; }
.nav a[aria-current="page"] { background: #444; }
</style>
```

Link states

Style the five states in this order (LVHFA) or later rules will override earlier ones: :link, :visited, :hover, :focus, :active.

```
a:link { color: #0645ad; }
a:visited { color: #551a8b; }
a:hover { text-decoration-thickness: 2px; }
a:focus-visible { outline: 3px solid #ffbf47; outline-offset: 2px; }
a:active { color: #b90000; }
```

- Link text must make sense alone: 'Read the shipping policy', not 'click here'.
- Keep the underline or another non-colour cue so links are recognisable.
- Never remove the focus outline without providing a visible replacement.
- Use a <button> for actions (open menu, submit) and <a> for navigation.

Lesson 8: Images and media

```
<img src="images/cover.jpg" alt="Cover of Learn HTML: a red book with
white letters" width="600" height="800" loading="lazy">

<figure>
  <img src="chart.png" alt="Sales grew from 120 in January to 340 in
June">
  <figcaption>Figure 1. Monthly sales, first half of 2026.</
figcaption>
</figure>

<picture>
  <source srcset="hero.avif" type="image/avif">
  <source srcset="hero.webp" type="image/webp">
  <img src="hero.jpg" alt="The shop front at night">
</picture>

<img src="small.jpg" srcset="small.jpg 480w, medium.jpg 960w, large.
jpg 1600w"
     sizes="(max-width: 600px) 100vw, 50vw" alt="...">

<video controls width="640" poster="poster.jpg">
  <source src="tour.mp4" type="video/mp4">
  <track kind="captions" src="tour.en.vtt" srclang="en"
label="English">
  Your browser does not support video.
</video>

<audio controls src="podcast.mp3"></audio>
```

Responsive images in CSS

```
img, video { max-width: 100%; height: auto; }          /* never
overflow the container */
.thumb { width: 200px; aspect-ratio: 3 / 4; object-fit: cover; }   /*
crop to a fixed shape */
.avatar { border-radius: 50%; }
```

- alt is required. Describe the content and function; use alt="" for purely decorative images.
- Always give width and height (or aspect-ratio) so the page does not jump while images load.
- Use loading="lazy" for images below the fold, never for the main hero image.

- Prefer AVIF/WebP with a JPEG fallback in <picture>; use SVG for logos and icons.
- Provide captions for video and a transcript for audio.

Lesson 9: Forms and validation

```
<form action="/order" method="post">
  <fieldset>
    <legend>Your details</legend>
    <p>
      <label for="name">Full name</label>
      <input id="name" name="name" type="text" required
autocomplete="name">
    </p>
    <p>
      <label for="email">Email</label>
      <input id="email" name="email" type="email" required
autocomplete="email">
    </p>
    <p>
      <label for="qty">Quantity</label>
      <input id="qty" name="qty" type="number" min="1" max="10"
value="1">
    </p>
    <p>
      <label for="format">Format</label>
      <select id="format" name="format">
        <option value="pdf">PDF</option>
        <option value="print">Printed</option>
      </select>
    </p>
    <p>
      <label for="notes">Notes</label>
      <textarea id="notes" name="notes" rows="3"></textarea>
    </p>
    <p>
      <input id="terms" name="terms" type="checkbox" required>
      <label for="terms">I accept the terms</label>
    </p>
  </fieldset>
  <button type="submit">Order</button>
</form>
```

Built-in validation

Attribute	Checks
required	Field is not empty
type="email" / url / number / date	Value has the right format
min / max / step	Numeric or date range

Attribute	Checks
minlength / maxlength	Text length
pattern="[0-9]{5}"	Regular expression
novalidate (on form)	Turns built-in validation off

Styling forms and validation states

```
label { display: block; font-weight: 600; margin-bottom: .25rem; }
input, select, textarea, button { font: inherit; }
input, select, textarea {
  width: 100%; padding: .6rem .8rem; border: 1px solid #bbb; border-
radius: 6px;
}
input:focus-visible, select:focus-visible, textarea:focus-visible {
  outline: 3px solid #ffbf47; outline-offset: 1px; border-color:
#b90000;
}
input:user-invalid { border-color: #c00; background: #fff5f5; }
input:user-valid { border-color: #2a7; }
button[type="submit"] {
  background: #b90000; color: #fff; border: 0; padding: .7rem 1.4rem;
border-radius: 999px; cursor: pointer;
}
button:disabled { opacity: .5; cursor: not-allowed; }
```

- Every control needs a <label> connected by for/id (or wrapping it).
- Group radio buttons and checkboxes in a <fieldset> with a <legend>.
- Use the right type: it changes the mobile keyboard and adds validation for free.
- Show error messages in text next to the field, not only by colour.

Lesson 10: Reusable components

A component is a block of HTML plus the CSS that styles it, designed so you can copy it anywhere. Give it one class name on the outer element and prefix inner classes with it (card, card__title, card--featured) so styles do not leak.

```
<article class="card card--featured">
  <img class="card__image" src="cover.jpg" alt="">
  <div class="card__body">
    <h3 class="card__title">Learn HTML</h3>
    <p class="card__text">From zero to a complete website.</p>
    <a class="btn" href="learn-html.html">Details</a>
  </div>
</article>
```

```
.card {
  display: flex; flex-direction: column;
  border: 1px solid #e2e8f0; border-radius: 16px; overflow: hidden;
background: #fff;
}
.card__image { aspect-ratio: 3 / 4; object-fit: cover; }
.card__body { padding: 1rem 1.25rem; display: grid; gap: .5rem; }
.card__title { margin: 0; font-size: 1.1rem; }
.card--featured { border-color: #b90000; box-shadow: 0 10px 30px rgba(
185, 0, 0, .15); }
.btn {
  display: inline-block; padding: .5rem 1rem; border-radius: 999px;
  background: #b90000; color: #fff; text-decoration: none; justify-
self: start;
}
.btn:hover { background: #900; }
```

Design tokens with custom properties

```
:root {
  --brand: #b90000;
  --ink: #1b2431;
  --radius: 12px;
  --space-1: .5rem; --space-2: 1rem; --space-3: 2rem;
}
.card { border-radius: var(--radius); padding: var(--space-2); }
.btn { background: var(--brand); }
```

Change --brand once and every component follows. Put the variables in :root so they are available everywhere.

Lesson 11: Styling essentials - the three ways to add CSS

Method	How	Use when
External style sheet	<link rel="stylesheet" href="styles.css"> in <head>	Always, for real sites: one file shared by all pages, cached by the browser
Internal style sheet	<style> ... </style> in <head>	Single-page demos, emails, this reference's examples
Inline style	style="color: red" attribute on the element	Rarely: one-off values generated by a program; hard to override and maintain

Anatomy of a rule

```
selector {
  property: value;      /* a declaration */
  property: value;
}

h1 {
  color: #b90000;
  font-size: 2rem;
}
```

Comments

```
/* CSS comments look like this and can span
   several lines. There is no // comment in CSS. */
```

Units

Unit	Meaning	Typical use
px	CSS pixel	Borders, small fixed sizes
rem	Relative to the root font size (16px by default)	Font sizes, spacing, widths - respects user zoom settings

Unit	Meaning	Typical use
em	Relative to the element's own font size	Padding around text, icon sizes
%	Relative to the parent	Widths
vw / vh	1% of viewport width/height	Full-screen sections, fluid type
ch	Width of the digit 0	Line length (max-width: 65ch)
fr	Fraction of free space (Grid only)	Column tracks

Colours

```
color: red;                  /* 148 named colours */
color: #b90000;              /* hex: rr gg bb */
color: #b90000cc;            /* hex with alpha */
color: rgb(185 0 0);
color: rgb(185 0 0 / 50%);   /* 50% transparent */
color: hsl(0 100% 36%);      /* hue, saturation, lightness */
color: oklch(50% 0.2 25);    /* perceptually uniform, wide gamut */
color: currentColor;         /* the element's text colour */
```

Lesson 12: Selectors and specificity

Selectors are like addresses for elements: they point CSS at the exact parts of the page you want to change.

Selector type	Example	Matches
Type	p { }	All <p> elements
Class	.btn { }	Elements with class="btn"
ID	#hero { }	The element with id="hero"
Universal	* { }	All elements
Attribute	a[target="_blank"], input[type="email"], [class^="icon-"]	Elements by attribute presence or value
Descendant	.card p	Any <p> inside .card
Child	.card > h3	<h3> directly inside .card
Adjacent sibling	h2 + p	The <p> immediately after an <h2>
General sibling	h2 ~ p	Every <p> after an <h2> in the same parent
Pseudo-class	a:hover, input:required, li:nth-child(2n), :is(), :where(), :has()	Elements in a state or position
Pseudo-element	p::first-line, p::after, li::marker	Parts of an element

Specificity: who wins

When two rules set the same property on the same element, the more specific selector wins. Count (IDs, classes/attributes/pseudo-classes, types/pseudo-elements). Inline styles beat everything except !important. If specificity

ties, the later rule wins.

Selector	Score (id, class, type)
p	0,0,1
.card p	0,1,1
.card.highlight p	0,2,1
#feature.card p	1,1,1
style="..."	1,0,0,0 (inline)
:where(.a .b)	0,0,0 (where adds nothing)

```
<article class="card"><p>Default card text.</p></article>
<article class="card highlight"><p>Highlight card text.</p></article>
<article id="feature" class="card highlight"><p>Feature card text (ID
wins).</p></article>

<style>
.card p { color: #475569; }
.card.highlight p { color: #2563eb; }
#feature.card p { color: #be123c; }   /* highest specificity: wins */
</style>
```

Using the cascade strategically

- Write from general to specific: base styles first, overrides later.
- Prefer classes; avoid IDs and long descendant chains in selectors.
- Avoid !important. If you need it, the real fix is a better selector or order.
- Use @layer to put resets, base, components and utilities in explicit layers.
- Debug in DevTools: the Styles panel shows every matching rule, crossed out when overridden.

Lesson 13: Cascade and inheritance

The cascade decides which declaration wins, in this order: (1) origin and importance (user-agent < user < author; !important reverses), (2) cascade layers, (3) specificity, (4) source order. Inheritance passes some property values from parent to child automatically.

Inherited by default	Not inherited
color, font-*, line-height, text-align, letter-spacing, visibility, cursor, list-style, direction	margin, padding, border, background, width, height, display, position

```
body { color: #1b2431; font-family: Georgia, serif; }   /* all text
inherits these */
.box { border: 1px solid; }                              /* children
do NOT get a border */

/* keywords that work on every property */
.reset { color: inherit; }     /* take the parent's value */
.plain { all: initial; }       /* specification default */
.norm  { all: unset; }         /* inherit if inheritable, otherwise
initial */
.rev   { all: revert; }        /* browser default style */
```

Cascade layers

```
@layer reset, base, components, utilities;

@layer reset { * { margin: 0; box-sizing: border-box; } }
@layer base { body { font: 1rem/1.6 system-ui; } }
@layer components { .btn { padding: .5rem 1rem; } }
@layer utilities { .hidden { display: none; } }
/* later layers beat earlier ones regardless of specificity */
```

Lesson 14: Typography

```
body {
  font-family: 'Inter', system-ui, -apple-system, 'Segoe UI', Roboto,
sans-serif;
  font-size: clamp(1rem, 0.95rem + 0.3vw, 1.125rem);
  line-height: 1.6;
}
h1 { font-size: clamp(2rem, 1.5rem + 2.5vw, 3.5rem); line-height: 1.1;
 letter-spacing: -0.02em; }
h2 { font-size: 1.75rem; }
p  { max-width: 65ch; margin-block: 0 1em; }
.lead { font-size: 1.25rem; color: #475569; }
.caps { text-transform: uppercase; letter-spacing: .08em; font-size: .
8rem; }
.num { font-variant-numeric: tabular-nums; }   /* aligned digits in
tables */
```

Loading a web font

```
@font-face {
  font-family: 'Inter';
  src: url('fonts/inter.woff2') format('woff2');
  font-weight: 100 900;
  font-display: swap;
}
```

Or link a font service in the <head> with <link rel="preconnect"> and <link rel="stylesheet">. Always list fallback fonts after the web font.

Arabic and right-to-left text

```
<html lang="ar" dir="rtl">
...
body { font-family: 'Noto Naskh Arabic', 'Cairo', 'Segoe UI', Tahoma,
sans-serif; line-height: 1.8; }
/* use logical properties so layout mirrors automatically */
.card { padding-inline-start: 1rem; margin-inline-end: auto; border-
inline-start: 4px solid #b90000; }
```

- Font stacks: preferred font first, similar fallbacks next, generic family (serif, sans-serif, monospace) last.
- Line length 45-75 characters; line-height 1.5-1.7 for body text.

- Use rem for font sizes so users can enlarge text in their browser settings.
- Do not justify text on the web; ragged right reads better and avoids rivers.

Lesson 15: Colours and backgrounds

```
:root {
  --brand: #b90000;
  --brand-dark: color-mix(in oklab, var(--brand), black 20%);
  --surface: #fff;
  --ink: #1b2431;
}
.hero {
  background: linear-gradient(120deg, #2563eb 0%, #7c3aed 50%,
#0f172a 100%);
  color: #fff;
}
.banner {
  background-image: url('hero.jpg');
  background-size: cover;
  background-position: center;
  background-repeat: no-repeat;
}
.tint { background-color: rgb(185 0 0 / 10%); }
.card { background: var(--surface); box-shadow: 0 14px 28px rgba(15,
23, 42, 0.08); }
```

Contrast

Text must have a contrast ratio of at least 4.5:1 against its background (3:1 for large text). #767676 on white is the lightest grey that passes. Check with the DevTools colour picker or a contrast checker. Never convey information by colour alone.

Dark mode

```
:root { color-scheme: light dark; }
@media (prefers-color-scheme: dark) {
  :root { --surface: #14181f; --ink: #e6e9ef; }
}
body { background: var(--surface); color: var(--ink); }
```

Lesson 16: The box model

Every element is a rectangular box: content in the middle, padding around it, the border wrapping both, and the margin as the outside buffer between neighbours.

```
+---------------- margin (transparent) ----------------+
|  +------------- border ---------------------------+  |
|  |  +---------- padding ------------------------+ |  |
|  |  |                                          | |  |
|  |  |               content                    | |  |
|  |  |                                          | |  |
|  |  +------------------------------------------+ |  |
|  +-----------------------------------------------+  |
+-----------------------------------------------------+
```

content-box versus border-box

By default (box-sizing: content-box) width and height apply to the content only, so a 300px box with 24px padding and a 2px border is really 352px wide. With border-box the declared size includes padding and border: a 300px box stays 300px. Almost every project switches to border-box globally.

```
*, *::before, *::after { box-sizing: border-box; }

.card {
  width: 320px;
  padding: 24px;
  border: 2px solid #cbd5f5;
  margin-bottom: 24px;
}
.callout {
  margin: 32px 0;
  padding: 16px;
  border-left: 6px solid #2563eb;
  background: #eff6ff;
}
```

Shorthands

Declaration	Meaning
margin: 24px;	All four sides
margin: 24px 16px;	top/bottom 24px, left/right 16px

Declaration	Meaning
padding: 8px 12px 16px;	top 8, left/right 12, bottom 16
padding: 1px 2px 3px 4px;	top, right, bottom, left (clockwise)
border: 2px solid #1d4ed8;	width, style, colour
margin: 0 auto;	Centre a block with a width
margin-inline: auto;	Same, using logical properties

Collapsing margins

- Vertical margins between block elements collapse to the largest value (a 24px bottom margin followed by a 16px top margin gives 24px, not 40px).
- A parent and its first/last child can share margins unless padding, a border or display: flow-root intervenes.
- Margins never collapse inside Flexbox or Grid containers - one more reason to use gap.

Visualising with DevTools

Inspect an element in Chrome or Firefox and look at the Computed panel: it shows a diagram with margin, border, padding and content measurements. Hover each part to highlight it on the page.

Spacing strategies

- Create a spacing scale (base of 4 or 8 pixels) and stick to it: 4, 8, 16, 24, 32, 48.
- Store it in custom properties (--space-2: 1rem) for consistency.

- Combine gap with Flexbox or Grid to separate items instead of adding margins to each one.

Lesson 17: Layout fundamentals - normal flow

Without any layout CSS, browsers lay elements out in normal flow: block boxes stack vertically and fill the width; inline boxes flow horizontally inside lines. Every layout technique is a way of taking elements out of, or rearranging, this flow.

display value	Behaviour
block	New line, full width, respects width/height/margins
inline	Flows in text; width/height ignored; only horizontal padding/margin effective
inline-block	Flows in text but respects width/height/vertical margins
flex / inline-flex	Children laid out along one axis
grid / inline-grid	Children placed in rows and columns
flow-root	Block that contains its floats and stops margin collapsing
none	Removed from rendering and from the accessibility tree
contents	Box disappears, children remain

Floats (legacy but still useful for text wrap)

```
img.left { float: left; margin: 0 1rem 1rem 0; }
.clearfix::after { content: ''; display: block; clear: both; }
/* modern: */ .wrapper { display: flow-root; }
```

Overflow

```
.box { height: 200px; overflow: auto; }      /* scrollbars when
needed */
.clip { overflow: hidden; }                   /* cut off */
.marquee { white-space: nowrap; overflow-x: auto; }
```

Lesson 18: Positioning and z-index

position	Behaviour
static (default)	Normal flow; top/left have no effect
relative	Normal flow, then nudged by top/left; creates a reference for absolute children
absolute	Removed from flow; placed relative to the nearest positioned ancestor
fixed	Removed from flow; placed relative to the viewport; stays while scrolling
sticky	Normal flow until it reaches the given offset, then sticks (inside its parent)

```
.card { position: relative; }
.card .badge {
  position: absolute; top: 12px; right: 12px;
  background: #b90000; color: #fff; padding: 2px 8px; border-radius:
999px;
}
.site-header { position: sticky; top: 0; z-index: 10; background:
#fff; }
.back-to-top { position: fixed; bottom: 1rem; inset-inline-end: 1rem;
}
.modal-backdrop { position: fixed; inset: 0; background: rgb(0 0 0 /
50%); z-index: 100; }
```

z-index and stacking contexts

- z-index only works on positioned elements (and flex/grid items).
- Higher values are drawn on top. Keep a scale: 10 header, 100 dropdown, 1000 modal.
- opacity < 1, transform, filter and position: fixed create a new stacking context: children cannot escape it no matter how large their z-index.

Lesson 19: Flexbox

Flexbox lays out children in one dimension - a row or a column - and distributes space between them. It is ideal for navigation bars, toolbars, card strips, media objects and form rows.

Creating a flex container

```
.toolbar {
  display: flex;          /* children become flex items in a row */
  gap: 16px;
  align-items: center;
}
.toolbar .spacer { flex: 1 1 auto; }   /* pushes following items to
the right */
```

Axes and alignment

- The main axis follows flex-direction (row = horizontal, column = vertical). Distribute items along it with justify-content.
- The cross axis is perpendicular. Align items on it with align-items (all) or align-self (one).
- Use gap for consistent spacing instead of margins.

Property (container)	Values
flex-direction	row | row-reverse | column | column-reverse
flex-wrap	nowrap | wrap | wrap-reverse
justify-content	flex-start | center | flex-end | space-between | space-around | space-evenly
align-items	stretch | flex-start | center | flex-end | baseline
align-content	Same as justify-content, for multiple lines
gap	row-gap column-gap

Property (item)	Meaning
flex: grow shrink basis	How the item takes and gives up space (default 0 1 auto)
flex: 1	Equal widths, share all free space
flex: 0 0 300px	Fixed 300px, never grows or shrinks
flex: 1 1 220px	Ideal 220px, may grow or shrink; wraps nicely
order	Visual order (default 0); does not change tab order
align-self	Override align-items for one item

Card strip

```
<section class="cards">
  <article><h2>Prototype</h2><p>Validate ideas quickly with
interactive mockups.</p></article>
  <article><h2>Build</h2><p>Create accessible, responsive components
in code.</p></article>
  <article><h2>Ship</h2><p>Automate deployment pipelines and
monitoring.</p></article>
</section>

<style>
.cards {
  display: flex;
  gap: 24px;
  justify-content: center;
  align-items: stretch;
  flex-wrap: wrap;
}
.cards article {
  flex: 1 1 220px;
  padding: 24px;
  border-radius: 16px;
  background: #f1f5f9;
}
</style>
```

Common patterns

```
/* centre anything */
.center { display: flex; justify-content: center; align-items: center;
 min-height: 100vh; }

/* split layout 2:1 */
```

```
.split { display: flex; gap: 2rem; }
.split > main { flex: 2; }
.split > aside { flex: 1; }

/* media object that stacks on small screens */
.media { display: flex; gap: 1rem; flex-wrap: wrap; }
.media img { flex: 0 0 120px; }
.media .body { flex: 1 1 240px; }

/* sticky footer */
body { min-height: 100vh; display: flex; flex-direction: column; }
main { flex: 1; }
```

Lesson 20: CSS Grid

Grid lays out children in two dimensions at once. You declare tracks (columns and rows) on the container and place items into cells or areas. A track is one column or row - imagine drawing a table with lines; Grid lets you define those lines in CSS.

```
.layout {
  display: grid;
  grid-template-columns: 240px 1fr;      /* two columns */
  grid-template-rows: auto 1fr auto;     /* three rows */
  gap: 24px;
  min-height: 100vh;
}
```

Track sizing

Pattern	Meaning
300px 1fr 1fr	Fixed sidebar, two equal flexible columns
repeat(12, minmax(0, 1fr))	Classic 12-column grid
repeat(auto-fit, minmax(220px, 1fr))	As many 220px+ columns as fit; collapses empty tracks
repeat(auto-fill, minmax(220px, 1fr))	Same but keeps empty tracks
fit-content(300px)	Shrink to content, max 300px
max-content / min-content	Size to the longest / shortest content

Placing items

```
.hero .copy   { grid-column: span 6; }          /* auto row, six
columns wide */
.item         { grid-column: 1 / 7; grid-row: 2 / span 2; }
.full         { grid-column: 1 / -1; }          /* first to last line
*/

/* named areas */
.page {
```

```
  display: grid;
  grid-template-columns: 240px 1fr;
  grid-template-areas:
    'header header'
    'nav    main'
    'footer footer';
}
.page > header { grid-area: header; }
.page > nav    { grid-area: nav; }
.page > main   { grid-area: main; }
.page > footer { grid-area: footer; }
@media (max-width: 700px) {
  .page { grid-template-columns: 1fr; grid-template-areas: 'header'
'nav' 'main' 'footer'; }
}
```

Alignment

- justify-items / align-items align content inside each cell.
- justify-content / align-content distribute the whole grid inside the container.
- place-items and place-content combine both axes: place-items: center centres everything.

Marketing layout example

```
<section class="hero">
  <div class="copy">
    <h1>Design systems that scale</h1>
    <p>Unify design and engineering with a shared language.</p>
    <a class="cta" href="#">Get started</a>
  </div>
  <div class="visual">
    <h2>Release highlights</h2>
    <ul><li>Theme builder</li><li>Usage analytics</
li><li>Accessibility tracking</li></ul>
  </div>
</section>
<section class="features">
  <article><h3>Token management</h3><p>...</p></article>
  <article><h3>Component lifecycles</h3><p>...</p></article>
  <article><h3>Design reviews</h3><p>...</p></article>
</section>

.hero {
  display: grid;
```

```
  grid-template-columns: repeat(12, minmax(0, 1fr));
  gap: 24px;
  padding: 88px clamp(24px, 6vw, 80px);
  background: linear-gradient(120deg, #2563eb 0%, #7c3aed 50%,
#0f172a 100%);
  color: #fff;
}
.hero .copy   { grid-column: span 6; max-width: 480px; }
.hero .visual { grid-column: span 6; background: rgba(255,255,255,0.
09); border-radius: 24px; padding: 40px; }
.features {
  display: grid;
  gap: 24px;
  grid-template-columns: repeat(auto-fit, minmax(220px, 1fr));
  padding: clamp(32px, 5vw, 80px);
}
.features article { border: 1px solid #e2e8f0; border-radius: 20px;
padding: 28px; background: #fff; }
@media (max-width: 900px) {
  .hero .copy, .hero .visual { grid-column: 1 / -1; }
}
```

The hero spans six columns per side on large screens and collapses to full width through the media query; the feature grid adapts its card count automatically.

Lesson 21: Layout patterns

A few patterns cover most pages. Copy them and adjust the numbers.

```
/* 1. Centred content column */
.container { width: min(100% - 2rem, 70rem); margin-inline: auto; }

/* 2. Holy grail: header, sidebar, content, footer */
.holy { display: grid; grid-template-rows: auto 1fr auto; grid-
template-columns: 16rem 1fr; min-height: 100vh; }
.holy > header, .holy > footer { grid-column: 1 / -1; }

/* 3. Auto grid of cards */
.grid { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(16rem, 1fr)); }

/* 4. Sidebar that stacks when narrow (no media query) */
.with-sidebar { display: flex; flex-wrap: wrap; gap: 2rem; }
.with-sidebar > aside { flex: 1 1 15rem; }
.with-sidebar > main  { flex: 999 1 25rem; }

/* 5. Cluster of tags/buttons */
.cluster { display: flex; flex-wrap: wrap; gap: .5rem; align-items:
center; }

/* 6. Stack with consistent vertical rhythm */
.stack > * + * { margin-block-start: 1rem; }

/* 7. Cover: hero with centred content */
.cover { min-height: 100vh; display: grid; place-items: center; }

/* 8. Full-bleed section inside a narrow column */
.full-bleed { width: 100vw; margin-inline: calc(50% - 50vw); }
```

Lesson 22: Responsive design

- Add <meta name="viewport" content="width=device-width, initial-scale=1"> - without it nothing else works on phones.
- Design mobile-first: write styles for narrow screens first, then add min-width media queries for tablets and desktops.
- Use relative units (rem, %, vw, ch) so elements scale naturally.
- A breakpoint is the width where your layout needs to change. Choose breakpoints from your content, not from device names.

Mobile-first media queries

```
:root { --space: clamp(1rem, 2vw, 1.5rem); }
.page { display: grid; gap: var(--space); }
@media (min-width: 768px) {
  .page { grid-template-columns: 240px 1fr; }
}
@media (min-width: 1200px) {
  .page { grid-template-columns: 280px 2fr 1fr; }
}
```

Fluid grids and typography

```
.cards { display: grid; grid-template-columns: repeat(auto-fit,
minmax(220px, 1fr)); gap: 1.5rem; }
h1 { font-size: clamp(1.75rem, 1.2rem + 2.5vw, 3rem); }   /* min,
preferred, max */
p  { max-width: 65ch; }
```

Container queries

```
.card-holder { container-type: inline-size; }
@container (min-width: 500px) {
  .card { display: grid; grid-template-columns: 160px 1fr; }
}
```

Container queries watch the size of a parent element instead of the whole screen, so a component adapts wherever it is placed.

Responsive media

```
img, video, iframe { max-width: 100%; height: auto; }
.video-wrap { aspect-ratio: 16 / 9; }
.video-wrap iframe { width: 100%; height: 100%; }
```

Other media features

```
@media (prefers-reduced-motion: reduce) { *, *::before, *::after {
animation: none !important; transition: none !important; } }
@media (prefers-color-scheme: dark) { ... }
@media (hover: hover) { .card:hover { transform: translateY(-4px); }
}   /* only devices with a mouse */
@media print { nav, footer { display: none; } }
@media (orientation: landscape) { ... }
```

Testing

- Use DevTools device mode (Ctrl+Shift+M) to preview breakpoints.
- Test on a real phone when possible; check touch target size (at least 44x44px) and both orientations.
- Check text at 200% zoom: nothing should overlap or be cut off.

Lesson 23: Responsive components

```
/* Navigation that becomes a hamburger menu without JavaScript */
<nav class="nav">
  <input type="checkbox" id="menu" class="nav__toggle" hidden>
  <label for="menu" class="nav__button" aria-label="Menu">&#9776;</
label>
  <ul class="nav__list">
    <li><a href="/">Home</a></li>
    <li><a href="/books/">Books</a></li>
    <li><a href="/contact/">Contact</a></li>
  </ul>
</nav>

<style>
.nav__list { list-style: none; margin: 0; padding: 0; display: none; }
.nav__toggle:checked ~ .nav__list { display: block; }
@media (min-width: 700px) {
  .nav__button { display: none; }
  .nav__list { display: flex !important; gap: 1rem; }
}
</style>

/* Responsive table (see the Lists and tables chapter) */
.table-wrapper { overflow-x: auto; }

/* Responsive card: image beside text when there is room */
.card { display: grid; gap: 1rem; }
@container (min-width: 480px) { .card { grid-template-columns: 200px
1fr; } }

/* Responsive embed */
.embed { aspect-ratio: 16 / 9; width: 100%; }

/* Responsive form: labels beside fields on wide screens */
.form-row { display: grid; gap: .5rem; }
@media (min-width: 600px) { .form-row { grid-template-columns: 10rem
1fr; align-items: center; } }
```

Lesson 24: Custom properties (CSS variables)

Custom properties store a value under a name that starts with two dashes. Read it with var(). They cascade and inherit like other properties, can be changed in media queries or on a class, and can be read and set from JavaScript.

```
:root {
  --brand: #b90000;
  --radius: 12px;
  --shadow: 0 10px 25px rgb(15 23 42 / 8%);
}
.btn { background: var(--brand); border-radius: var(--radius); }
.card { box-shadow: var(--shadow); padding: var(--card-padding, 1rem);
 }   /* fallback value */

/* theming by scope */
.theme-green { --brand: #04AA6D; }

/* change on state */
.btn:hover { --brand: #900; }

/* JavaScript */
document.documentElement.style.setProperty('--brand', '#0055aa');
```

Typed properties with @property

```
@property --angle {
  syntax: '<angle>';
  inherits: false;
  initial-value: 0deg;
}
.spin { background: conic-gradient(from var(--angle), red, blue);
transition: --angle 1s; }
.spin:hover { --angle: 360deg; }
```

Lesson 25: calc() and CSS functions

Function	Purpose	Example
calc()	Arithmetic mixing units	width: calc(100% - 2rem)
min()	Smallest of several values	width: min(90%, 60rem)
max()	Largest of several values	font-size: max(1rem, 2vw)
clamp()	Value between a minimum and maximum	font-size: clamp(1rem, 2vw, 1.5rem)
var()	Read a custom property	color: var(--brand, black)
attr()	Read an HTML attribute (content only)	content: attr(data-label)
url()	Reference a file	background: url('bg.png')
rgb() hsl() oklch() color-mix()	Colours	color-mix(in oklab, red, white 30%)
linear-gradient() radial-gradient() conic-gradient()	Gradient images	background: linear-gradient(90deg, red, blue)
repeat() minmax() fit-content()	Grid tracks	repeat(auto-fit, minmax(200px, 1fr))
translate() rotate() scale()	Transforms	transform: rotate(45deg)
counter()	Generated numbering	content: counter(item)

Function	Purpose	Example
env()	Environment values (phone notches)	padding-bottom: env(safe-area-inset-bottom)
round() mod() rem() abs() sign()	Maths	width: round(down, 33.3%, 1px)

```
.sidebar { width: calc(100% / 3 - 1rem); }
.container { width: min(100% - 2rem, 70rem); }
h1 { font-size: clamp(1.75rem, 1rem + 3vw, 3rem); }
.hero { min-height: calc(100vh - var(--header-height)); }
```

Lesson 26: Transitions

A transition animates a property smoothly from its old value to its new value when the value changes (on hover, focus, class change...). Set it on the element's normal state, not on the :hover state, so it plays both ways.

```
.btn {
  background: #b90000;
  transition: background-color .2s ease, transform .15s ease;
}
.btn:hover { background: #900; transform: translateY(-2px); }

/* longhands */
.panel {
  transition-property: opacity, transform;
  transition-duration: 300ms;
  transition-timing-function: cubic-bezier(.2, .8, .2, 1);
  transition-delay: 0s;
}
```

Timing function	Feel
ease (default)	Fast start, slow end
linear	Constant speed
ease-in	Slow start
ease-out	Slow end (best for entering)
ease-in-out	Slow both ends
steps(4)	Jumps in 4 steps
cubic-bezier(x1,y1,x2,y2)	Custom curve

- Animate only transform and opacity when possible; they are cheap for the browser. Animating width, height or top causes layout work.
- Keep durations short: 150-300ms for interface feedback.
- Respect prefers-reduced-motion.

- display cannot be transitioned; use opacity/visibility or the newer transition-behavior: allow-discrete with @starting-style.

Lesson 27: Transforms

```
.a { transform: translate(20px, 10px); }      /* move */
.b { transform: rotate(15deg); }              /* turn */
.c { transform: scale(1.1); }                 /* grow 10% */
.d { transform: skewX(10deg); }               /* slant */
.e { transform: rotate(45deg) scale(.8); }    /* combined, applied
right to left */
.f { transform-origin: top left; }            /* pivot point */

/* individual properties (no ordering problems) */
.g { translate: 0 -4px; rotate: 3deg; scale: 1.05; }

/* 3D */
.scene { perspective: 800px; }
.card3d { transform: rotateY(30deg); transform-style: preserve-3d;
backface-visibility: hidden; }
```

- Transforms do not affect the layout of other elements; the box keeps its original space.
- They create a stacking context and a containing block for fixed children.
- Combine with transition for hover lift effects: .card:hover { transform: translateY(-4px); }

Lesson 28: Animations

```
@keyframes fade-up {
  from { opacity: 0; transform: translateY(12px); }
  to   { opacity: 1; transform: none; }
}
.reveal { animation: fade-up .5s ease-out both; }

@keyframes pulse {
  0%, 100% { transform: scale(1); }
  50%      { transform: scale(1.06); }
}
.badge { animation: pulse 1.5s ease-in-out infinite; }

/* longhands */
.spinner {
  animation-name: spin;
  animation-duration: 1s;
  animation-timing-function: linear;
  animation-iteration-count: infinite;
  animation-direction: normal;      /* reverse | alternate */
  animation-fill-mode: forwards;    /* keep final state */
  animation-play-state: running;    /* paused */
  animation-delay: 0s;
}
@keyframes spin { to { transform: rotate(1turn); } }

/* scroll-driven (new) */
.progress { animation: grow linear; animation-timeline: scroll(); }
@keyframes grow { from { scale: 0 1; } to { scale: 1 1; } }
```

- Use transitions for state changes and animations for things that run on their own or loop.
- Pause or remove animations for users who set prefers-reduced-motion.
- Avoid animating more than a few elements at once on mobile.

Lesson 29: Effects and filters

```
.card { box-shadow: 0 1px 2px rgb(0 0 0 / 8%), 0 8px 24px rgb(0 0 0 /
12%); }
.text { text-shadow: 0 1px 2px rgb(0 0 0 / 40%); }
.round { border-radius: 16px; }   /* 50% for a circle */
.glass { background: rgb(255 255 255 / 60%); backdrop-filter: blur(
12px); }
.grey { filter: grayscale(100%); }
.grey:hover { filter: none; }
.dim { filter: brightness(.8) contrast(1.1) saturate(1.2); }
.blurred { filter: blur(4px); }
.shadowed-png { filter: drop-shadow(0 4px 6px rgb(0 0 0 / 30%)); }   /
* follows transparent shape */
.fade { opacity: .6; }
.blend { mix-blend-mode: multiply; }
.gradient-text {
  background: linear-gradient(90deg, #b90000, #ff7a00);
  -webkit-background-clip: text; background-clip: text; color:
transparent;
}
.clipped { clip-path: circle(50%); }
.cut { clip-path: polygon(0 0, 100% 0, 100% 80%, 0 100%); }
```

Lesson 30: Accessibility

- Use semantic HTML first: headings, lists, tables, buttons, links and landmarks give screen readers structure for free.
- Every image needs alt text; decorative images use alt="".
- Every form control needs a label. Error messages must be text, associated with the field via aria-describedby.
- Keyboard: everything clickable must be reachable with Tab and operable with Enter/Space. Never remove :focus outlines without a visible replacement (:focus-visible).
- Colour contrast at least 4.5:1 for text, 3:1 for large text and UI components. Do not use colour alone to convey meaning.
- Set lang on <html>; use dir="rtl" for Arabic and Hebrew.
- Respect user preferences: prefers-reduced-motion, prefers-color-scheme, prefers-contrast.
- Use ARIA only when no native element does the job. aria-label, aria-labelledby, aria-describedby, aria-current, aria-expanded and role are the most common.
- Hide content properly: display: none / hidden attribute hides from everyone; the .sr-only pattern hides visually but keeps it for screen readers.
- Test with the keyboard alone, with a screen reader (NVDA on Windows, VoiceOver on Mac/iOS, TalkBack on Android) and with an automatic checker (Lighthouse, axe).

```
.sr-only {
  position: absolute; width: 1px; height: 1px; padding: 0; margin: -
1px;
  overflow: hidden; clip: rect(0 0 0 0); white-space: nowrap; border:
0;
}
.skip-link { position: absolute; top: -100px; }
.skip-link:focus { top: 0; }
```

```
<a class="skip-link" href="#main">Skip to content</a>
<button aria-expanded="false" aria-controls="menu">Menu</button>
<ul id="menu" hidden>...</ul>
```

Lesson 31: Design systems

A design system is the set of tokens (colours, spacing, type scale), components and rules a site is built from. Even a small site benefits: decide once, reuse everywhere.

```
:root {
  /* colour tokens */
  --c-brand: #b90000; --c-ink: #1b2431; --c-muted: #5b6472; --c-line:
#d9d2c3; --c-surface: #fff; --c-bg: #faf8f3;
  /* type scale (1.25 ratio) */
  --fs-0: 1rem; --fs-1: 1.25rem; --fs-2: 1.563rem; --fs-3: 1.953rem; -
-fs-4: 2.441rem;
  /* spacing scale */
  --s-1: .25rem; --s-2: .5rem; --s-3: 1rem; --s-4: 1.5rem; --s-5:
2rem; --s-6: 3rem;
  /* shape */
  --radius: 12px; --shadow: 0 10px 25px rgb(15 23 42 / 8%);
}
```

Naming conventions

Convention	Example	Idea
BEM	.card, .card__title, .card--featured	Block, element, modifier
Utility classes	.mt-3, .flex, .text-center	One class = one declaration
State classes	.is-open, .is-active	Toggled by JavaScript
Data attributes	[data-state="open"]	State without class juggling

File organisation

```
css/
  reset.css        /* box-sizing, margins, images */
  tokens.css       /* :root variables */
  base.css         /* body, headings, links, tables, forms */
  components/      /* card.css, button.css, nav.css */
  utilities.css    /* .sr-only, .container, .stack */

/* one entry file */
@layer reset, tokens, base, components, utilities;
@import url('reset.css') layer(reset);
```

```
@import url('tokens.css') layer(tokens);
...
```

Lesson 32: Performance

- Put CSS in <head> (render-blocking but needed first) and scripts at the end of <body> or with defer.
- Compress images: AVIF/WebP, correct dimensions, loading="lazy" below the fold, width/height attributes to avoid layout shift.
- Use font-display: swap and preload the main font: <link rel="preload" href="font.woff2" as="font" type="font/woff2" crossorigin>.
- Keep CSS small: remove unused rules, avoid deep selectors, use one style sheet per site.
- Prefer transform/opacity animations; use will-change sparingly.
- content-visibility: auto on long lists skips rendering off-screen sections.
- Preconnect to third-party origins you will use soon: <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>.
- Measure with Lighthouse (DevTools > Lighthouse) and aim for good Core Web Vitals: LCP under 2.5s, CLS under 0.1, INP under 200ms.

```
<link rel="preload" as="image" href="hero.avif" fetchpriority="high">
<img src="hero.avif" alt="..." width="1600" height="900"
fetchpriority="high">
<img src="later.jpg" alt="..." width="800" height="600"
loading="lazy" decoding="async">
<script src="app.js" defer></script>
```

Lesson 33: Debugging and testing

DevTools checklist

- Elements panel: is the HTML what you expected? Unclosed tags show up as unexpected nesting here.
- Styles panel: which rules apply? Crossed-out declarations are overridden (specificity/order) or invalid (typo). A yellow warning triangle means the property or value is unknown.
- Computed panel: the final value of every property and the box model diagram.
- Toggle :hov to force :hover/:focus states; edit values live and copy them back to your file.
- Console: red messages for 404 (file not found - check paths and spelling) and script errors.
- Network panel: is styles.css actually loading? Status 200 is good; 404 means the path is wrong.

Common CSS bugs and fixes

Symptom	Likely cause	Fix
Nothing changes	Style sheet not loaded, cached, or selector does not match	Check Network panel; hard reload (Ctrl+F5); inspect the element
Property ignored	Typo, invalid value, or property does not apply to that display type	Look for the warning icon; check width on inline elements, vertical-align on blocks
Margin does not work	Margin collapse or inline element	Use padding, display: block/flow-root, or gap
Element wider than screen	100% width plus padding (content-box)	box-sizing: border-box; max-width: 100%

Symptom	Likely cause	Fix
z-index has no effect	Element not positioned or trapped in a stacking context	Add position: relative; move it out of the transformed/opacity parent
Centre does not work	margin: auto on an element without width, or on inline	Set a width or use flex/grid centring
Text overflows box	Long word/URL	overflow-wrap: anywhere; or <wbr>
Font not applied	Wrong name, quotes, or font not loaded	Check @font-face URL in Network panel; quote multi-word names

Validate and test

- HTML validator: https://validator.w3.org/ - CSS validator: https://jigsaw.w3.org/css-validator/
- Test in at least Chrome and Firefox; check Safari on an iPhone if you can.
- Test keyboard navigation and zoom to 200%.
- Print preview (Ctrl+P) to check @media print styles.

Lesson 34: Tooling and automation (optional)

None of this is required to build a site, but as projects grow these tools save time.

Tool	What it does
Editor extensions (Prettier, Emmet, Live Server)	Auto-format, expand abbreviations (ul>li*3), reload the browser on save
Git	Version control: keep history, undo mistakes, collaborate
Sass / PostCSS	Pre-processors adding nesting, mixins, autoprefixing (CSS now has native nesting)
Stylelint / HTMLHint	Catch errors and enforce style rules automatically
Lighthouse	Audits for performance, accessibility, SEO
Bundlers (Vite, esbuild)	Combine and minify files for production
Static hosting (GitHub Pages, Netlify)	Publish a folder of HTML/CSS for free

Native CSS nesting

```
.card {
  padding: 1rem;
  & h3 { margin: 0; }
  &:hover { box-shadow: var(--shadow); }
  & .btn { margin-top: .5rem; }
  @media (min-width: 600px) { padding: 2rem; }
}
```

Lesson 35: Project - a complete landing page

This project combines everything: semantic structure, a responsive navigation, a hero built with Grid, a features section with Flexbox cards, a pricing table, a form and a footer. Copy both files, open index.html, then change the words, colours and images.

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Learn HTML and CSS</title>
  <meta name="description" content="PDF and printed books about web
development, in Arabic and English.">
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <a class="skip-link" href="#main">Skip to content</a>
  <header class="site-header">
    <a class="logo" href="/">Cairo Book Shop</a>
    <nav aria-label="Main">
      <ul class="nav">
        <li><a href="#features">Why us</a></li>
        <li><a href="#pricing">Pricing</a></li>
        <li><a href="#contact">Contact</a></li>
      </ul>
    </nav>
  </header>

  <main id="main">
    <section class="hero">
      <div class="hero__copy">
        <h1>Learn HTML and CSS from zero</h1>
        <p class="lead">Clear books, real examples, Arabic and
English editions.</p>
        <a class="btn" href="#pricing">See the books</a>
      </div>
      <img class="hero__image" src="images/books.jpg" alt="Three
books on a wooden desk" width="800" height="600">
    </section>

    <section id="features" class="features">
      <h2>Why readers choose us</h2>
      <div class="cards">
        <article class="card"><h3>Step by step</h3><p>Every chapter
```

```
builds on the last.</p></article>
        <article class="card"><h3>Searchable PDF</h3><p>Find any tag
or property in seconds.</p></article>
        <article class="card"><h3>Free updates</h3><p>New editions
delivered to your inbox.</p></article>
      </div>
    </section>

    <section id="pricing" class="pricing">
      <h2>Pricing</h2>
      <div class="table-wrapper">
        <table>
          <caption>Editions and prices</caption>
          <thead><tr><th scope="col">Edition</th><th
scope="col">Format</th><th scope="col">Price</th></tr></thead>
          <tbody>
            <tr><th scope="row">Starter</th><td>PDF</td><td>120 EGP</
td></tr>
            <tr><th scope="row">Complete</th><td>PDF + print</
td><td>350 EGP</td></tr>
          </tbody>
        </table>
      </div>
    </section>

    <section id="contact" class="contact">
      <h2>Contact us</h2>
      <form action="/contact" method="post" class="form">
        <div class="form-row"><label for="n">Name</label><input
id="n" name="name" required autocomplete="name"></div>
        <div class="form-row"><label for="e">Email</label><input
id="e" name="email" type="email" required autocomplete="email"></div>
        <div class="form-row"><label for="m">Message</label><textarea
id="m" name="message" rows="4" required></textarea></div>
        <button class="btn" type="submit">Send</button>
      </form>
    </section>
  </main>

  <footer class="site-footer">
    <p>&copy; 2026 Cairo Book Shop &middot; <a href="/privacy/
">Privacy</a> &middot; <a href="mailto:info@example.com">info@example.
com</a></p>
  </footer>
</body>
</html>

/* styles.css */
@layer reset, base, layout, components;
```

```
@layer reset {
  *, *::before, *::after { box-sizing: border-box; }
  body, h1, h2, h3, p, ul { margin: 0; }
  img { max-width: 100%; height: auto; display: block; }
}

@layer base {
  :root {
    --brand: #b90000; --ink: #1b2431; --muted: #5b6472; --line:
#d9d2c3; --bg: #faf8f3; --surface: #fff;
    --radius: 14px; --shadow: 0 10px 25px rgb(15 23 42 / 8%);
    --space: clamp(1rem, 2vw, 1.5rem);
  }
  body { font: 1.05rem/1.6 Georgia, serif; color: var(--ink);
background: var(--bg); }
  h1, h2, h3 { font-family: system-ui, sans-serif; line-height: 1.15;
}
  h1 { font-size: clamp(2rem, 1.4rem + 3vw, 3.25rem); }
  h2 { font-size: 1.75rem; margin-bottom: var(--space); }
  a { color: var(--brand); }
  a:focus-visible { outline: 3px solid #ffbf47; outline-offset: 2px; }
  .lead { font-size: 1.2rem; color: var(--muted); }
}

@layer layout {
  .site-header { position: sticky; top: 0; z-index: 10; background:
var(--surface); border-bottom: 1px solid var(--line);
                 display: flex; flex-wrap: wrap; gap: var(--space);
align-items: center; justify-content: space-between; padding: .75rem
var(--space); }
  .nav { display: flex; gap: .25rem; list-style: none; padding: 0; }
  .nav a { display: block; padding: .5rem .9rem; border-radius: 999px;
 text-decoration: none; color: var(--ink); }
  .nav a:hover { background: var(--bg); }
  main > section { padding: clamp(2rem, 6vw, 5rem) var(--space); max-
width: 70rem; margin-inline: auto; }
  .hero { display: grid; gap: var(--space); align-items: center; }
  @media (min-width: 800px) { .hero { grid-template-columns: 1.1fr
1fr; } }
  .hero__image { border-radius: var(--radius); box-shadow: var(--
shadow); }
  .cards { display: flex; flex-wrap: wrap; gap: var(--space); }
  .card { flex: 1 1 220px; }
  .site-footer { border-top: 1px solid var(--line); padding: var(--
space); text-align: center; color: var(--muted); font-size: .9rem; }
}

@layer components {
  .btn { display: inline-block; padding: .7rem 1.4rem; border-radius:
```

```
999px; border: 0; background: var(--brand); color: #fff;
         font: inherit; font-weight: 600; text-decoration: none;
cursor: pointer; transition: transform .15s, background-color .2s; }
  .btn:hover { background: #900; transform: translateY(-2px); }
  .card { background: var(--surface); border: 1px solid var(--line);
border-radius: var(--radius); padding: var(--space); box-shadow: var(-
-shadow); }
  .card h3 { margin-bottom: .5rem; }
  .table-wrapper { overflow-x: auto; }
  table { width: 100%; border-collapse: collapse; background: var(--
surface); }
  caption { text-align: left; padding: .5rem 0; color: var(--muted); }
  th, td { padding: .8rem 1rem; text-align: left; border-bottom: 1px
solid var(--line); }
  thead th { background: var(--brand); color: #fff; }
  tbody tr:nth-child(even) { background: #fcfbf8; }
  .form { display: grid; gap: 1rem; max-width: 36rem; }
  .form-row { display: grid; gap: .3rem; }
  @media (min-width: 600px) { .form-row { grid-template-columns: 8rem
1fr; align-items: start; } }
  label { font-weight: 600; }
  input, textarea { width: 100%; padding: .6rem .8rem; border: 1px
solid #bbb; border-radius: 8px; font: inherit; }
  input:focus-visible, textarea:focus-visible { outline: 3px solid
#ffbf47; border-color: var(--brand); }
  .skip-link { position: absolute; top: -100px; left: 1rem;
background: var(--brand); color: #fff; padding: .5rem 1rem; }
  .skip-link:focus { top: 1rem; }
  @media (prefers-reduced-motion: reduce) { .btn { transition: none;
} }
}
```

Exercises

- Change the colour tokens to your own brand and watch every component update.
- Add a fourth card and confirm the row wraps correctly on a narrow window.
- Add an Arabic version: set lang="ar" dir="rtl" and replace left/right properties with logical ones (inline-start / inline-end).
- Add a dark mode with prefers-color-scheme.

- Run the page through the HTML validator and Lighthouse; fix every warning.

Lesson 36: Quick quiz and answers

Question	Answer
Which element creates an ordered list?	(with items)
Which attribute connects a <label> to its control?	for, matching the control's id
What does border-collapse: collapse do?	Merges adjacent cell borders into single lines
What is the specificity of #a .b p?	1,1,1
Which CSS property makes a flex container?	display: flex
How do you make images never overflow?	img { max-width: 100%; height: auto; }
What does the viewport meta tag do?	Makes the page use the real device width on phones
Which unit is relative to the root font size?	rem
What does gap do?	Adds space between flex/grid items without margins
How do you centre a block horizontally?	Give it a width and margin-inline: auto (or use flex/grid)
Where should <main> appear?	Once per page, containing the unique content
What is the difference between <b> and ?	means importance; <b> is only visual/keyword

Question	Answer
Which selector matches every second row?	tr:nth-child(even)
What does box-sizing: border-box change?	width/height include padding and border
What replaces the bgcolor attribute?	CSS background-color

Part 13

Practical Guides

Step-by-step guidance for pages, lists, tables, forms, media, accessibility, SEO and migration.

Building a complete page step by step

This guide walks through building a small, correct web page using the elements from this book, in the order you would type them.

Step 1: The skeleton

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>My Book Store</title>
  <link rel="stylesheet" href="style.css">
</head>
<body>

</body>
</html>
```

Step 2: Landmarks

```
<body>
  <header>
    <h1>My Book Store</h1>
    <nav aria-label="Main">
      <ul>
        <li><a href="index.html" aria-current="page">Home</a></li>
        <li><a href="books.html">Books</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>

  <main>
    <!-- unique content goes here -->
  </main>

  <footer>
    <p><small>&copy; 2026 My Book Store</small></p>
  </footer>
</body>
```

Step 3: Content

```
<main>
  <section aria-labelledby="new">
    <h2 id="new">New this week</h2>
    <article class="card">
      <img src="html-book.jpg" alt="Cover of Learn HTML" width="200"
height="300">
      <h3>Learn HTML</h3>
      <p>A complete beginner's guide. <span class="price">120 EGP</
span></p>
      <button type="button">Add to cart</button>
    </article>
  </section>

  <section aria-labelledby="prices">
    <h2 id="prices">Price list</h2>
    <table>
      <caption>PDF books</caption>
      <thead><tr><th scope="col">Title</th><th scope="col">Price (
EGP)</th></tr></thead>
      <tbody>
        <tr><td>Learn HTML</td><td>120</td></tr>
        <tr><td>Learn CSS</td><td>140</td></tr>
      </tbody>
    </table>
  </section>
</main>
```

Step 4: A form

```
<section aria-labelledby="contact">
  <h2 id="contact">Contact us</h2>
  <form action="/contact" method="post">
    <div class="field">
      <label for="name">Name</label>
      <input id="name" name="name" required autocomplete="name">
    </div>
    <div class="field">
      <label for="email">Email</label>
      <input id="email" name="email" type="email" required
autocomplete="email">
    </div>
    <div class="field">
      <label for="msg">Message</label>
      <textarea id="msg" name="message" rows="4" required></textarea>
    </div>
    <button type="submit">Send</button>
  </form>
</section>
```

Step 5: The style sheet

```
/* style.css */
*, *::before, *::after { box-sizing: border-box; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: #1b2431; background: #f6f1e7; }
header, main, footer { padding: 1rem; }
header { background: #fff; box-shadow: 0 1px 0 #e7ddcb; }
nav ul { display: flex; gap: 1rem; list-style: none; padding: 0;
margin: 0; }
nav a[aria-current="page"] { font-weight: bold; }
main { max-width: 960px; margin: 0 auto; }
.card { background: #fff; border-radius: 12px; padding: 1rem; display:
 grid; gap: 0.5rem; max-width: 260px; }
.price { color: #e60000; font-weight: bold; }
table { border-collapse: collapse; width: 100%; background: #fff; }
th, td { padding: 0.5rem; border-bottom: 1px solid #e7ddcb; text-
align: left; }
.field { display: grid; gap: 0.25rem; margin-bottom: 1rem; }
input, textarea { padding: 0.5rem; border: 1px solid #ccc; border-
radius: 6px; font: inherit; }
button { background: #e60000; color: #fff; border: 0; border-radius:
6px; padding: 0.6rem 1.2rem; cursor: pointer; }
footer { text-align: center; color: #6b7280; }
```

Step 6: Check it

- Open the file in a browser and resize the window.
- Press Tab repeatedly: every link, input and button should receive a visible focus ring in a sensible order.
- Validate at validator.w3.org.
- Run Lighthouse (in Chrome DevTools) for accessibility and performance scores.

Lists in depth

HTML has three list elements: <ul> for unordered lists, <ol> for ordered lists and <dl> for description lists. Items of ul and ol are <li>; a dl uses <dt> for terms and <dd> for descriptions.

Choosing the right list

Question	Use
Does the order matter (steps, ranking)?	
Is it a set of items where order is irrelevant?	
Are they name-value pairs (term and definition, label and data)?	<dl>
Is it a toolbar of actions?	<menu>
Is it navigation links?	<nav> containing a

Numbering control on ordered lists

Attribute / CSS	Effect	Example
type="1"	1, 2, 3 (default)	<ol type="1">
type="a" / "A"	a, b, c / A, B, C	<ol type="A">
type="i" / "I"	i, ii, iii / I, II, III	<ol type="I">
start="5"	Begin at 5	<ol start="5">
reversed	Count down	<ol reversed>

Attribute / CSS	Effect	Example
<li value="10">	Set this item's number	
list-style-type: lower-greek	CSS: alpha, beta, gamma	ol { list-style-type: lower-greek; }
list-style-type: arabic-indic	CSS: Arabic-Indic digits	ol { list-style-type: arabic-indic; }

CSS list-style-type values

For <ul>: disc (default), circle, square, none, or any string such as '→ '. For <ol>: decimal, decimal-leading-zero, lower-roman, upper-roman, lower-alpha, upper-alpha, lower-greek, armenian, georgian, arabic-indic, persian, bengali, devanagari, cjk-decimal, japanese-informal, and more. list-style-position: inside puts the marker inside the item's box; outside (default) hangs it in the margin. list-style-image: url(icon.svg) uses an image; ::marker is the modern way to style markers.

Nested lists

```
<ol>
  <li>Prepare
    <ul>
      <li>Install an editor</li>
      <li>Create a folder</li>
    </ul>
  </li>
  <li>Write HTML
    <ol type="a">
      <li>Skeleton</li>
      <li>Content</li>
    </ol>
  </li>
</ol>
```

Description lists for metadata

```
<dl>
```

```
  <dt>Author</dt><dd>Sara Ali</dd>
  <dt>Published</dt><dd><time datetime="2026-09">September 2026</
time></dd>
  <dt>Pages</dt><dd>2000</dd>
</dl>
```

Common mistakes

- Text directly inside <ul> or <ol> that is not in an <li>.
- A nested list placed between <li> elements instead of inside one.
- Using <br> or paragraphs starting with '-' instead of a real list.
- Using <dl> for dialogue or for layout.

Tables in depth

Use tables for data whose meaning depends on rows and columns. A well-built table has a caption, header cells with scope, and grouped rows.

Element roles

Element	Role
<table>	The table container
<caption>	Title, first child
<colgroup> / <col>	Column groups for styling
<thead>	Header rows
<tbody>	Data rows (one or more)
<tfoot>	Summary rows
<tr>	A row
<th>	Header cell, with scope=col|row|colgroup|rowgroup
<td>	Data cell

colspan and rowspan

colspan="n" makes a cell span n columns; rowspan="n" makes it span n rows. Every row must still add up to the same number of columns. Sketch the grid on paper for complex tables.

```
<table>
  <tr><th rowspan="2">Product</th><th colspan="2">Sales</th></tr>
  <tr><th>2025</th><th>2026</th></tr>
  <tr><td>Books</td><td>120</td><td>150</td></tr>
</table>
```

HTML 3.2/4 attributes and their CSS replacements

Old attribute	CSS replacement
border="1"	th, td { border: 1px solid; }
cellpadding="5"	th, td { padding: 5px; }
cellspacing="0"	table { border-collapse: collapse; } or border-spacing: 0
width="100%"	table { width: 100%; }
bgcolor="#eee"	background-color: #eee
align="center" on table	table { margin: 0 auto; }
align="right" on td	td { text-align: right; }
valign="top"	vertical-align: top
nowrap	white-space: nowrap
summary="..."	<caption> or aria-describedby

Making tables responsive

- Wrap the table in a div with overflow-x: auto so it scrolls horizontally on phones.
- Hide less important columns on small screens with a media query.
- Stack cells into blocks with display: block and data-label attributes (see the CSS cookbook).
- Use font-variant-numeric: tabular-nums so digits line up.

Sorting and filtering

HTML has no built-in sorting. Add it with JavaScript by reading rows from tbody, sorting the array and re-appending, and mark the sorted column header with aria-sort="ascending" or "descending".

Forms in depth

A form collects input and sends it to a server or a script. Building a good form is mostly about labels, the right input types, validation and clear feedback.

Checklist

- Every control has a <label> linked by for/id or wrapping.
- Every control that must be submitted has a name.
- Use the most specific type: email, tel, url, number, date, and so on.
- Use autocomplete tokens so browsers can fill in addresses and cards.
- Group radio buttons and checkboxes with <fieldset> and <legend>.
- Mark required fields with required and say so visibly.
- Use pattern with a title explaining the format.
- Show errors next to the field and link them with aria-describedby; do not rely on colour alone.
- Use method="post" for anything that changes data; enctype="multipart/form-data" for files.
- Validate again on the server; client validation is only a convenience.

GET versus POST

	GET	POST
Data location	In the URL (?a=1&b=2)	In the request body
Bookmarkable	Yes	No

	GET	POST
Size limit	About 2000 characters	Practically none
Use for	Searches, filters	Logins, orders, uploads, anything with side effects
Security	Visible in history and logs	Not in URL (still needs HTTPS)

Built-in validation attributes

Attribute	Applies to	Checks
required	Most inputs, select, textarea	Not empty / selected
minlength / maxlength	Text-like inputs, textarea	Length
min / max	number, range, date, time...	Range
step	number, range, date, time...	Granularity
pattern	text, search, url, tel, email, password	Regular expression (whole value)
type=email / url	input	Format

Styling validation states

```
input:required { border-left: 3px solid #999; }
input:user-invalid { border-color: #b90000; }
input:user-valid { border-color: #0f8a4c; }
.error { color: #b90000; font-size: 0.9em; }
```

Custom validation messages

```
<input id="zip" pattern="[0-9]{5}" required>
<script>
  const zip = document.getElementById('zip');
  zip.addEventListener('invalid', () => zip.setCustomValidity('Enter
```

```
exactly five digits.'));
  zip.addEventListener('input', () => zip.setCustomValidity(''));
</script>
```

Semantic layout and accessibility

Semantic HTML means choosing elements for what they mean, not how they look. It is the foundation of accessibility: screen readers, keyboard navigation, reader modes and search engines all depend on it.

Landmark map

Element	Landmark role	How many per page
<header> (top level)	banner	1
<nav>	navigation	Several; label each
<main>	main	Exactly 1
<aside>	complementary	Several
<footer> (top level)	contentinfo	1
<form> with a name	form	Several
<search>	search	Several
<section> with a name	region	Several

Heading outline

One <h1> per page, then h2 for sections, h3 inside them and so on, never skipping levels. Users of screen readers navigate by headings more than by any other means.

Images

- Informative image: alt describes the content.

- Functional image (in a link or button): alt describes the action.
- Decorative image: alt="" (empty).
- Complex image (chart): short alt plus a full description in text or a linked page.

Keyboard

- Everything clickable must be reachable with Tab and operable with Enter or Space: use <a>, <button> and form controls, not <div onclick>.
- Never remove the focus outline without providing a visible replacement (:focus-visible).
- Provide a skip link to <main>.
- Manage focus in dialogs and after dynamic changes.

Colour and motion

- Text contrast at least 4.5:1 (3:1 for large text).
- Never convey information by colour alone.
- Respect prefers-reduced-motion; avoid flashing content.

ARIA in three rules

- Do not use ARIA if a native element does the job.
- Do not change native semantics unless you must.
- All interactive ARIA controls must be keyboard usable.

Media: images, audio and video

Choosing an image format

Format	Best for	Notes
AVIF	Photos, smallest files	Newest; use with fallback
WebP	Photos and graphics	Widely supported
JPEG	Photos, universal fallback	No transparency
PNG	Screenshots, logos with transparency	Large for photos
SVG	Icons, logos, diagrams	Scales perfectly; can be styled
GIF	Simple animations	Prefer video or animated WebP/AVIF

Responsive image decision

- Same image, different sizes: <img srcset sizes>.
- Different crops or formats: <picture> with <source>.
- High-DPI only: srcset with 1x/2x.
- Always: alt, width, height, and loading="lazy" below the fold.

Audio and video checklist

- Provide MP4 (H.264) plus WebM.
- Add controls.
- Add <track kind="captions">.

- Set poster and preload="metadata".
- For background video: autoplay muted loop playsinline, and pause it for prefers-reduced-motion.
- Provide a transcript.

Embedding third-party media

YouTube, Vimeo and maps are embedded with <iframe>. Always add title, loading="lazy" and only the allow permissions you need. Consider a click-to-load facade to save bandwidth.

SEO essentials in HTML

- Unique, descriptive <title> under 60 characters.
- <meta name="description"> under 160 characters.
- One <h1> matching the page topic; logical heading structure.
- Semantic landmarks so crawlers understand the page.
- Descriptive link text; internal links between related pages.
- alt text on images; descriptive file names.
- <link rel="canonical"> to avoid duplicates; hreflang alternates for translations.
- Structured data with JSON-LD (schema.org) for rich results.
- Fast loading: compressed images, lazy loading, deferred scripts, preconnect for fonts.
- Mobile friendly: the viewport meta tag and responsive CSS.
- Open Graph and Twitter tags for attractive sharing previews.

Migrating old HTML (2, 3.2, 4) to HTML5

Old	New
<!DOCTYPE HTML PUBLIC ...>	<!DOCTYPE html>
<meta http-equiv="Content-Type" content="text/html; charset=utf-8">	<meta charset="utf-8">
<script type="text/javascript">	<script>
<style type="text/css">	<style>
<font size color face>	CSS font-size, color, font-family
	CSS text-align: center / margin: auto
<b> for importance	
<i> for emphasis	
<u>	CSS text-decoration or <ins>
<strike>	<s> or <del>
<tt>	<code>, <kbd>, <samp>
<big>	CSS font-size
	<header>
	<nav>
	<main>
	<aside>
	<footer>

Old	New
	<article>
<table> for layout	CSS grid / flexbox
<frameset> / <frame>	CSS layout; <iframe> if needed
<applet>, <embed> Flash	<video>, <audio>, <canvas>, JavaScript
<a name="x">	id="x" on any element
<acronym>	<abbr>
<dir>, <menu> as list	
align, bgcolor, border, cellpadding, valign, width attributes	CSS
<br clear="all">	CSS clear or flow-root
<img border="0">	img { border: 0 } (default now)
onclick="javascript:... "	addEventListener in a script

Part 14

Glossary and Index

Definitions of terms and an alphabetical index of everything in the book.

Glossary

Term	Definition
Accessibility (a11y)	Designing pages so that people with disabilities can use them, including with screen readers, keyboards, magnifiers and voice control.
ARIA	Accessible Rich Internet Applications: a set of role and aria-* attributes that describe widgets and states to assistive technology.
Attribute	A name=value pair inside an opening tag that configures the element, for example href="page.html".
Block-level element	An element that starts on a new line and fills the available width, such as , <p>, <h1>, <footer>.
Boolean attribute	An attribute whose presence means true and absence means false, such as disabled, checked, required.
Browser	The program that reads HTML, CSS and JavaScript and displays web pages: Chrome, Firefox, Safari, Edge.
Cascade	The CSS mechanism that decides which of several conflicting rules applies, based on importance, specificity and order.
Character reference / entity	A way to write a character by name or number, such as & or ©.
Child / parent / sibling / ancestor / descendant	Family terms describing element nesting in the document tree.
Class	A reusable label applied with the class attribute and targeted in CSS with a dot: .name.
Content model	The rules stating which children an element may contain.

Term	Definition
CSS	Cascading Style Sheets: the language that describes presentation.
Deprecated	Still supported but discouraged; may be removed in future.
DOCTYPE	The declaration at the top of a document (<!DOCTYPE html>) that switches the browser to standards mode.
DOM	Document Object Model: the tree of objects the browser builds from HTML, which JavaScript can read and modify.
Element	An opening tag, its content and its closing tag together (or a void tag alone).
Empty / void element	An element with no content and no closing tag, such as , <img>, <input>.
Flow content	Elements allowed in the body: most elements.
Focus	The state of the element that currently receives keyboard input, moved with Tab.
Fragment	The part of a URL after #, pointing to an element id.
Global attribute	An attribute allowed on every element, such as id, class, style, title, lang, hidden.
HTML	HyperText Markup Language: the language that structures web pages.
HTTP / HTTPS	The protocol browsers use to fetch pages; HTTPS is the encrypted version.
Hyperlink	A reference to another resource that the user can follow, created with <a href>.
Id	A unique identifier for one element, targeted in CSS with # and in links with #.
Inline element	An element that flows within text and takes only the width of its content: , <a>, .

Term	Definition
JavaScript	The programming language of the web, which adds behaviour to pages.
Landmark	A region of the page (banner, navigation, main, contentinfo...) that assistive technology can jump to.
Living Standard	The continuously updated HTML specification maintained by the WHATWG.
MDN	Mozilla Developer Network (developer.mozilla.org), the most complete free web documentation.
Metadata	Data about the document, placed in <head>.
MIME type	A label such as text/html or image/png that identifies the type of a file.
Nesting	Placing elements inside other elements.
Obsolete	Removed from the standard; must not be used.
Phrasing content	Text and inline elements that can appear inside a paragraph.
Pseudo-class / pseudo-element	CSS selectors for states (:hover) or generated parts (::before).
Quirks mode	A compatibility rendering mode triggered by a missing DOCTYPE that imitates 1990s browser bugs.
Rendering	The process of turning HTML and CSS into pixels.
Responsive design	Layouts that adapt to any screen size, using fluid widths, flexible images and media queries.
Screen reader	Software that reads the page aloud or in braille for blind users (NVDA, JAWS, VoiceOver, TalkBack).
Sectioning content	<article>, <aside>, <nav>, <section>: elements that define the scope of headings and footers.
Selector	The part of a CSS rule that chooses which elements to style.
Semantic HTML	Using elements according to their meaning.

Term	Definition
Specificity	The weight of a CSS selector, used by the cascade to resolve conflicts.
Tag	The markup in angle brackets, or , that starts or ends an element.
URL	Uniform Resource Locator: the address of a resource on the web.
UTF-8	The character encoding that supports every language; always use it.
Validator	A tool that checks HTML for errors (validator.w3.org).
Viewport	The visible area of the page in the browser window.
W3C	World Wide Web Consortium, the standards body that published HTML 3.2 to HTML 5.2.
WCAG	Web Content Accessibility Guidelines, the international accessibility standard.
WHATWG	The browser vendor group that maintains the HTML Living Standard.
XHTML	HTML written with XML syntax rules.

Glossary in depth

Each term again, with the places in this book where it matters most, so you can jump from a word you do not know to the chapter that explains it.

Accessibility (a11y)

Definition

Designing pages so that people with disabilities can use them, including with screen readers, keyboards, magnifiers and voice control.

Where to read more

- Related elements (Part 6): see the index
- Search tip: in the HTML edition type 'Accessibility (a11y)' in the search box to list every entry that mentions it.

ARIA

Definition

Accessible Rich Internet Applications: a set of role and aria-* attributes that describe widgets and states to assistive technology.

Where to read more

- Related elements (Part 6): see the index
- Search tip: in the HTML edition type 'ARIA' in the search box to list every entry that mentions it.

Attribute

Definition

A name=value pair inside an opening tag that configures the element, for example href="page.html".

Where to read more

- Related elements (Part 6): <html>
- Search tip: in the HTML edition type 'Attribute' in the search box to list every entry that mentions it.

Block-level element

Definition

An element that starts on a new line and fills the available width, such as , <p>, <h1>, <footer>.

Where to read more

- Related elements (Part 6): , <footer>, <h1>
- Related CSS properties (Part 11): width / height
- Search tip: in the HTML edition type 'Block-level element' in the search box to list every entry that mentions it.

Boolean attribute

Definition

An attribute whose presence means true and absence means false, such as disabled, checked, required.

Where to read more

- Related elements (Part 6): see the index
- Search tip: in the HTML edition type 'Boolean attribute' in the search box to list every entry that mentions it.

Browser

Definition

The program that reads HTML, CSS and JavaScript and displays web pages: Chrome, Firefox, Safari, Edge.

Where to read more

- Related elements (Part 6): <html>
- Search tip: in the HTML edition type 'Browser' in the search box to list every entry that mentions it.

Cascade

Definition

The CSS mechanism that decides which of several conflicting rules applies, based on importance, specificity and order.

Where to read more

- Related elements (Part 6): see the index
- Related CSS properties (Part 11): order
- Search tip: in the HTML edition type 'Cascade' in the search box to list every entry that mentions it.

Character reference / entity

Definition

A way to write a character by name or number, such as & or ©.

Where to read more

- Related elements (Part 6): see the index
- Search tip: in the HTML edition type 'Character reference / entity' in the search box to list every entry that mentions it.

Child / parent / sibling / ancestor / descendant

Definition

Family terms describing element nesting in the document tree.

Where to read more

- Related elements (Part 6): see the index
- Search tip: in the HTML edition type 'Child / parent / sibling / ancestor / descendant' in the search box to list every entry that mentions it.

Class

Definition

A reusable label applied with the class attribute and targeted in CSS with a dot: .name.

Where to read more

- Related elements (Part 6): <label>
- Search tip: in the HTML edition type 'Class' in the search box to list every entry that mentions it.

Content model

Definition

The rules stating which children an element may contain.

Where to read more

- Related elements (Part 6): <content>
- Related CSS properties (Part 11): contain / content-visibility, content
- Search tip: in the HTML edition type 'Content model' in the search box to list every entry that mentions it.

CSS

Definition

Cascading Style Sheets: the language that describes presentation.

Where to read more

- Related elements (Part 6): <style>
- Search tip: in the HTML edition type 'CSS' in the search box to list every entry that mentions it.

Deprecated

Definition

Still supported but discouraged; may be removed in future.

Where to read more

- Related elements (Part 6): see the index
- Search tip: in the HTML edition type 'Deprecated' in the search box to list every entry that mentions it.

DOCTYPE

Definition

The declaration at the top of a document (<!DOCTYPE html>) that switches the browser to standards mode.

Where to read more

- Related elements (Part 6): <html>
- Related CSS properties (Part 11): position / top / right / bottom / left / inset / z-index
- Search tip: in the HTML edition type 'DOCTYPE' in the search box to list every entry that mentions it.

DOM

Definition

Document Object Model: the tree of objects the browser builds from HTML, which JavaScript can read and modify.

Where to read more

- Related elements (Part 6): <html>, <object>
- Search tip: in the HTML edition type 'DOM' in the search box to list every entry that mentions it.

Element

Definition

An opening tag, its content and its closing tag together (or a void tag alone).

Where to read more

- Related elements (Part 6): <content>
- Related CSS properties (Part 11): content
- Search tip: in the HTML edition type 'Element' in the search box to list every entry that mentions it.

Empty / void element

Definition

An element with no content and no closing tag, such as <br>, <img>, <input>.

Where to read more

- Related elements (Part 6): <br>, <content>, <img>, <input>
- Related CSS properties (Part 11): content
- Search tip: in the HTML edition type 'Empty / void element' in the search box to list every entry that mentions it.

Flow content

Definition

Elements allowed in the body: most elements.

Where to read more

- Related elements (Part 6): <body>, <content>
- Related CSS properties (Part 11): content
- Search tip: in the HTML edition type 'Flow content' in the search box to list every entry that mentions it.

Focus

Definition

The state of the element that currently receives keyboard input, moved with Tab.

Where to read more

- Related elements (Part 6): <input>
- Search tip: in the HTML edition type 'Focus' in the search box to list every entry that mentions it.

Fragment

Definition

The part of a URL after #, pointing to an element id.

Where to read more

- Related elements (Part 6): see the index
- Search tip: in the HTML edition type 'Fragment' in the search box to list every entry that mentions it.

Global attribute

Definition

An attribute allowed on every element, such as id, class, style, title, lang, hidden.

Where to read more

- Related elements (Part 6): <style>, <title>
- Search tip: in the HTML edition type 'Global attribute' in the search box to list every entry that mentions it.

HTML

Definition

HyperText Markup Language: the language that structures web pages.

Where to read more

- Related elements (Part 6): <html>
- Search tip: in the HTML edition type 'HTML' in the search box to list every entry that mentions it.

HTTP / HTTPS

Definition

The protocol browsers use to fetch pages; HTTPS is the encrypted version.

Where to read more

- Related elements (Part 6): see the index
- Search tip: in the HTML edition type 'HTTP / HTTPS' in the search box to list every entry that mentions it.

Hyperlink

Definition

A reference to another resource that the user can follow, created with <a href>.

Where to read more

- Related elements (Part 6): see the index
- Search tip: in the HTML edition type 'Hyperlink' in the search box to list every entry that mentions it.

Id

Definition

A unique identifier for one element, targeted in CSS with # and in links with #.

Where to read more

- Related elements (Part 6): see the index
- Search tip: in the HTML edition type 'Id' in the search box to list every entry that mentions it.

Inline element

Definition

An element that flows within text and takes only the width of its content: , <a>, .

Where to read more

- Related elements (Part 6): <content>, ,
- Related CSS properties (Part 11): content, width / height
- Search tip: in the HTML edition type 'Inline element' in the search box to list every entry that mentions it.

JavaScript

Definition

The programming language of the web, which adds behaviour to pages.

Where to read more

- Related elements (Part 6): see the index
- Search tip: in the HTML edition type 'JavaScript' in the search box to list every entry that mentions it.

Landmark

Definition

A region of the page (banner, navigation, main, contentinfo…) that assistive technology can jump to.

Where to read more

- Related elements (Part 6): <main>
- Search tip: in the HTML edition type 'Landmark' in the search box to list every entry that mentions it.

Living Standard

Definition

The continuously updated HTML specification maintained by the WHATWG.

Where to read more

- Related elements (Part 6): <html>
- Search tip: in the HTML edition type 'Living Standard' in the search box to list every entry that mentions it.

MDN

Definition

Mozilla Developer Network (developer.mozilla.org), the most complete free web documentation.

Where to read more

- Related elements (Part 6): see the index
- Search tip: in the HTML edition type 'MDN' in the search box to list every entry that mentions it.

Metadata

Definition

Data about the document, placed in <head>.

Where to read more

- Related elements (Part 6): <data>, <head>
- Search tip: in the HTML edition type 'Metadata' in the search box to list every entry that mentions it.

MIME type

Definition

A label such as text/html or image/png that identifies the type of a file.

Where to read more

- Related elements (Part 6): <html>, <image>, <label>
- Search tip: in the HTML edition type 'MIME type' in the search box to list every entry that mentions it.

Nesting

Definition

Placing elements inside other elements.

Where to read more

- Related elements (Part 6): see the index
- Search tip: in the HTML edition type 'Nesting' in the search box to list every entry that mentions it.

Obsolete

Definition

Removed from the standard; must not be used.

Where to read more

- Related elements (Part 6): see the index
- Search tip: in the HTML edition type 'Obsolete' in the search box to list every entry that mentions it.

Phrasing content

Definition

Text and inline elements that can appear inside a paragraph.

Where to read more

- Related elements (Part 6): <content>
- Related CSS properties (Part 11): content
- Search tip: in the HTML edition type 'Phrasing content' in the search box to list every entry that mentions it.

Pseudo-class / pseudo-element

Definition

CSS selectors for states (:hover) or generated parts (::before).

Where to read more

- Related elements (Part 6): see the index
- Search tip: in the HTML edition type 'Pseudo-class / pseudo-element' in the search box to list every entry that mentions it.

Quirks mode

Definition

A compatibility rendering mode triggered by a missing DOCTYPE that imitates 1990s browser bugs.

Where to read more

- Related elements (Part 6): see the index
- Search tip: in the HTML edition type 'Quirks mode' in the search box to list every entry that mentions it.

Rendering

Definition

The process of turning HTML and CSS into pixels.

Where to read more

- Related elements (Part 6): <html>
- Search tip: in the HTML edition type 'Rendering' in the search box to list every entry that mentions it.

Responsive design

Definition

Layouts that adapt to any screen size, using fluid widths, flexible images and media queries.

Where to read more

- Related elements (Part 6): see the index
- Search tip: in the HTML edition type 'Responsive design' in the search box to list every entry that mentions it.

Screen reader

Definition

Software that reads the page aloud or in braille for blind users (NVDA, JAWS, VoiceOver, TalkBack).

Where to read more

- Related elements (Part 6): see the index
- Search tip: in the HTML edition type 'Screen reader' in the search box to list every entry that mentions it.

Sectioning content

Definition

<article>, <aside>, <nav>, <section>: elements that define the scope of headings and footers.

Where to read more

- Related elements (Part 6): <article>, <aside>, <content>, <nav>, <section>
- Related CSS properties (Part 11): content
- Search tip: in the HTML edition type 'Sectioning content' in the search box to list every entry that mentions it.

Selector

Definition

The part of a CSS rule that chooses which elements to style.

Where to read more

- Related elements (Part 6): <style>
- Search tip: in the HTML edition type 'Selector' in the search box to list every entry that mentions it.

Semantic HTML

Definition

Using elements according to their meaning.

Where to read more

- Related elements (Part 6): <html>
- Search tip: in the HTML edition type 'Semantic HTML' in the search box to list every entry that mentions it.

Specificity

Definition

The weight of a CSS selector, used by the cascade to resolve conflicts.

Where to read more

- Related elements (Part 6): see the index
- Search tip: in the HTML edition type 'Specificity' in the search box to list every entry that mentions it.

Tag

Definition

The markup in angle brackets, or , that starts or ends an element.

Where to read more

- Related elements (Part 6): see the index
- Search tip: in the HTML edition type 'Tag' in the search box to list every entry that mentions it.

URL

Definition

Uniform Resource Locator: the address of a resource on the web.

Where to read more

- Related elements (Part 6): <address>
- Search tip: in the HTML edition type 'URL' in the search box to list every entry that mentions it.

UTF-8

Definition

The character encoding that supports every language; always use it.

Where to read more

- Related elements (Part 6): see the index
- Search tip: in the HTML edition type 'UTF-8' in the search box to list every entry that mentions it.

Validator

Definition

A tool that checks HTML for errors (validator.w3.org).

Where to read more

- Related elements (Part 6): <html>
- Search tip: in the HTML edition type 'Validator' in the search box to list every entry that mentions it.

Viewport

Definition

The visible area of the page in the browser window.

Where to read more

- Related elements (Part 6): <area>
- Search tip: in the HTML edition type 'Viewport' in the search box to list every entry that mentions it.

W3C

Definition

World Wide Web Consortium, the standards body that published HTML 3.2 to HTML 5.2.

Where to read more

- Related elements (Part 6): <body>, <html>
- Search tip: in the HTML edition type 'W3C' in the search box to list every entry that mentions it.

WCAG

Definition

Web Content Accessibility Guidelines, the international accessibility standard.

Where to read more

- Related elements (Part 6): <content>
- Related CSS properties (Part 11): content
- Search tip: in the HTML edition type 'WCAG' in the search box to list every entry that mentions it.

WHATWG

Definition

The browser vendor group that maintains the HTML Living Standard.

Where to read more

- Related elements (Part 6): <html>
- Search tip: in the HTML edition type 'WHATWG' in the search box to list every entry that mentions it.

XHTML

Definition

HTML written with XML syntax rules.

Where to read more

- Related elements (Part 6): <html>
- Search tip: in the HTML edition type 'XHTML' in the search box to list every entry that mentions it.

Alphabetical index

Elements are shown in angle brackets, attributes in plain type, CSS properties with a leading dot-free name marked (CSS). Use your PDF reader's search (Ctrl+F) for anything not listed here.

Term	Where to find it
@font-face (CSS)	Part 11: Fonts and text
@import / @layer / @scope / @property (CSS)	Part 11: Interaction
@media (CSS)	Part 11: Interaction
@page (CSS)	Part 11: Interaction
@supports (CSS)	Part 11: Interaction
<a>	Part 6: Anchor (hyperlink)
<abbr>	Part 6: Abbreviation
abbr	Part 9: attribute on <td>, <th>
accent-color (CSS)	Part 11: Interaction
accept	Part 9: attribute on <form>, <input>
accept-charset	Part 9: attribute on <form>
Accessibility (a11y)	Part 14: glossary
accesskey	Part 4: global attribute
<acronym>	Part 6: Acronym (obsolete)
action	Part 9: attribute on <form>, <isindex>
<address>	Part 6: Contact address

Term	Where to find it
align	Part 9: attribute on <applet>, <caption>, <col>, <colgroup>, , <h1>, <hr>, <iframe>, <img>, <input>, <legend>, <object>, <p>, <spacer>, <table>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>
align-items / align-self / align-content (CSS)	Part 11: Layout
alink	Part 9: attribute on <body>
all (CSS)	Part 11: Interaction
allow	Part 9: attribute on <fencedframe>, <iframe>
allowfullscreen	Part 9: attribute on <iframe>
allowpaymentrequest	Part 9: attribute on <iframe>
alpha	Part 9: attribute on <input>
alt	Part 9: attribute on <applet>, <area>, <image>, <img>, <input>
animation / @keyframes (CSS)	Part 11: Motion
appearance (CSS)	Part 11: Interaction
<applet>	Part 6: Java applet (obsolete)
archive	Part 9: attribute on <applet>, <object>
<area>	Part 6: Image map area
ARIA	Part 14: glossary
aria-*	Part 4: global attribute
aria-label	Part 9: attribute on <svg>
aria-labelledby	Part 9: attribute on <svg>
<article>	Part 6: Self-contained article
as	Part 9: attribute on <link>
<aside>	Part 6: Aside (sidebar / tangential content)

Term	Where to find it
aspect-ratio (CSS)	Part 11: Box model
async	Part 9: attribute on <script>
Attribute	Part 14: glossary
attributionsrc	Part 9: attribute on <a>, <img>, <script>
<audio>	Part 6: Embedded audio
autocapitalize	Part 4: global attribute
autocomplete	Part 9: attribute on <form>, <input>, <select>, <textarea>
autocorrect	Part 4: global attribute
autofocus	Part 4: global attribute
autofocus	Part 9: attribute on <button>, <input>, <keygen>, <select>, <textarea>
autoplay	Part 9: attribute on <audio>, <video>
axis	Part 9: attribute on <td>, <th>
<b>	Part 6: Bring attention to (bold)
background	Part 9: attribute on <body>
background (CSS)	Part 11: Backgrounds
background-color (CSS)	Part 11: Backgrounds
background-image (CSS)	Part 11: Backgrounds
background-size / background-position / background-repeat / background-attachment / background-clip / background-origin (CSS)	Part 11: Backgrounds
balance	Part 9: attribute on <bgsound>

Term	Where to find it
<base>	Part 6: Document base URL
<basefont>	Part 6: Base font (obsolete)
<bdi>	Part 6: Bidirectional isolate
<bdo>	Part 6: Bidirectional text override
behavior	Part 9: attribute on <marquee>
bgcolor	Part 9: attribute on <body>, <col>, <colgroup>, <marquee>, <table>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>
<bgsound>	Part 6: Background sound (non-standard, obsolete)
<big>	Part 6: Bigger text (obsolete)
<blink>	Part 6: Blinking text (non-standard, obsolete)
Block-level element	Part 14: glossary
blocking	Part 9: attribute on <link>, <script>, <style>
<blockquote>	Part 6: Block quotation
<body>	Part 6: Document body
Boolean attribute	Part 14: glossary
border	Part 9: attribute on <frameset>, <img>, <object>, <table>
border (CSS)	Part 11: Box model
border-collapse / border-spacing (CSS)	Part 11: Box model
border-radius (CSS)	Part 11: Box model
bottommargin	Part 9: attribute on <body>
box-shadow (CSS)	Part 11: Box model
box-sizing (CSS)	Part 11: Box model
 	Part 6: Line break
Browser	Part 14: glossary

Term	Where to find it
<button>	Part 6: Button
<canvas>	Part 6: Graphics canvas
<caption>	Part 6: Table caption
capture	Part 9: attribute on <input>
caret-color (CSS)	Part 11: Interaction
Cascade	Part 14: glossary
cellpadding	Part 9: attribute on <table>
cellspacing	Part 9: attribute on <table>
	Part 6: Centred block (obsolete)
challenge	Part 9: attribute on <keygen>
char	Part 9: attribute on <col>, <colgroup>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>
Character reference / entity	Part 14: glossary
charoff	Part 9: attribute on <col>, <colgroup>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>
charset	Part 9: attribute on <a>, <link>, <meta>, <script>
checked	Part 9: attribute on <input>, <menuitem>
Child / parent / sibling / ancestor / descendant	Part 14: glossary
<cite>	Part 6: Citation (title of a work)
cite	Part 9: attribute on <blockquote>, <del>, <ins>, <q>
class	Part 4: global attribute
Class	Part 14: glossary
classid	Part 9: attribute on <object>

Term	Where to find it
clear	Part 9: attribute on
clip-path / mask (CSS)	Part 11: Backgrounds
closedby	Part 9: attribute on <dialog>
<code>	Part 6: Inline code
code	Part 9: attribute on <applet>
codebase	Part 9: attribute on <applet>, <object>
codetype	Part 9: attribute on <object>
<col>	Part 6: Table column
<colgroup>	Part 6: Table column group
color	Part 9: attribute on <basefont>, <font>, <hr>, <link>
color (CSS)	Part 11: Fonts and text
color-scheme (CSS)	Part 11: Interaction
colorspace	Part 9: attribute on <input>
cols	Part 9: attribute on <frameset>, <multicol>, <textarea>
colspan	Part 9: attribute on <td>, <th>
columns / column-count / column-width / column-gap / column-rule / column-span / break-inside (CSS)	Part 11: Layout
command	Part 9: attribute on <button>, <menuitem>
commandfor	Part 9: attribute on <button>
compact	Part 9: attribute on <dir>, <dl>, <menu>, ,

Term	Where to find it
contain / content-visibility (CSS)	Part 11: Layout
container-type / container-name / @container (CSS)	Part 11: Layout
<content>	Part 6: Shadow DOM insertion point (obsolete)
content	Part 9: attribute on <meta>
content (CSS)	Part 11: Fonts and text
Content model	Part 14: glossary
contenteditable	Part 4: global attribute
controls	Part 9: attribute on <audio>, <video>
controlslist	Part 9: attribute on <audio>, <video>
coords	Part 9: attribute on <a>, <area>
counter-reset / counter-increment (CSS)	Part 11: Fonts and text
credentialless	Part 9: attribute on <iframe>
crossorigin	Part 9: attribute on <audio>, <img>, <link>, <script>, <video>
csp	Part 9: attribute on <iframe>
CSS	Part 14: glossary
cursor (CSS)	Part 11: Box model
<data>	Part 6: Machine-readable value
data	Part 9: attribute on <object>
data-*	Part 4: global attribute
<datalist>	Part 6: Predefined options for an input
datetime	Part 9: attribute on <del>, <ins>, <time>

Term	Where to find it
<dd>	Part 6: Description details
declare	Part 9: attribute on <object>
decoding	Part 9: attribute on <img>
default	Part 9: attribute on <menuitem>, <track>
defer	Part 9: attribute on <script>
<del>	Part 6: Deleted text
Deprecated	Part 14: glossary
<details>	Part 6: Disclosure widget
<dfn>	Part 6: Definition term
<dialog>	Part 6: Dialog box
<dir>	Part 6: Directory list (obsolete)
dir	Part 4: global attribute
dir	Part 9: attribute on <bdi>, <bdo>, <html>
direction	Part 9: attribute on <marquee>
direction / unicode-bidi / writing-mode (CSS)	Part 11: Fonts and text
dirname	Part 9: attribute on <input>, <textarea>
disabled	Part 9: attribute on <button>, <fieldset>, <input>, <keygen>, <link>, <menuitem>, <optgroup>, <option>, <select>, <textarea>
disablepictureinpicture	Part 9: attribute on <video>
disableremoteplaybac k	Part 9: attribute on <audio>, <video>
display	Part 9: attribute on <math>
display (CSS)	Part 11: Box model
	Part 6: Generic block container
<dl>	Part 6: Description list

Term	Where to find it
DOCTYPE	Part 14: glossary
DOM	Part 14: glossary
download	Part 9: attribute on <a>, <area>
draggable	Part 4: global attribute
<dt>	Part 6: Description term
Element	Part 14: glossary
elementtiming	Part 9: attribute on <img>
	Part 6: Emphasis
<embed>	Part 6: External content
Empty / void element	Part 14: glossary
enctype	Part 9: attribute on <form>
enterkeyhint	Part 4: global attribute
etc.	Part 9: attribute on <image>
event	Part 9: attribute on <script>
exportparts	Part 4: global attribute
face	Part 9: attribute on <basefont>, <font>
<fencedframe>	Part 6: Fenced frame (experimental)
fetchpriority	Part 9: attribute on <img>, <link>, <script>
field-sizing (CSS)	Part 11: Interaction
<fieldset>	Part 6: Form field group
<figcaption>	Part 6: Figure caption
<figure>	Part 6: Figure with optional caption
fill	Part 9: attribute on <svg>
filter / backdrop-filter (CSS)	Part 11: Backgrounds

Term	Where to find it
flex / flex-grow / flex-shrink / flex-basis (CSS)	Part 11: Layout
flex-direction / flex-wrap / flex-flow (CSS)	Part 11: Layout
float / clear (CSS)	Part 11: Layout
Flow content	Part 14: glossary
Focus	Part 14: glossary
<font>	Part 6: Font (obsolete)
font (CSS)	Part 11: Fonts and text
font-family (CSS)	Part 11: Fonts and text
font-size (CSS)	Part 11: Fonts and text
font-style (CSS)	Part 11: Fonts and text
font-variant / font-variant-numeric / font-feature-settings (CSS)	Part 11: Fonts and text
font-weight (CSS)	Part 11: Fonts and text
<footer>	Part 6: Footer
for	Part 9: attribute on <label>, <output>, <script>
<form>	Part 6: Form
form	Part 9: attribute on <button>, <fieldset>, <input>, <keygen>, <label>, <meter>, <object>, <output>, <select>, <textarea>
formaction	Part 9: attribute on <button>, <input>
formenctype	Part 9: attribute on <button>, <input>
formmethod	Part 9: attribute on <button>, <input>

Term	Where to find it
formnovalidate	Part 9: attribute on <button>, <input>
formtarget	Part 9: attribute on <button>, <input>
Fragment	Part 14: glossary
<frame>	Part 6: Frame (obsolete)
frame	Part 9: attribute on <table>
frameborder	Part 9: attribute on <frame>, <frameset>, <iframe>
<frameset>	Part 6: Frameset (obsolete)
framespacing	Part 9: attribute on <frameset>
gap / row-gap / column-gap (CSS)	Part 11: Layout
Global attribute	Part 14: glossary
grid-auto-flow / grid-auto-rows / grid-auto-columns (CSS)	Part 11: Layout
grid-column / grid-row / grid-column-start etc. (CSS)	Part 11: Layout
grid-template-areas / grid-area (CSS)	Part 11: Layout
grid-template-columns / grid-template-rows (CSS)	Part 11: Layout
gutter	Part 9: attribute on <multicol>
<h1>	Part 6: Headings h1 to h6
<h2>	Part 6: see <h1>
<h3>	Part 6: see <h1>
<h4>	Part 6: see <h1>

Term	Where to find it
<h5>	Part 6: see <h1>
<h6>	Part 6: see <h1>
<head>	Part 6: Document head
<header>	Part 6: Header
headers	Part 9: attribute on <td>, <th>
height	Part 9: attribute on <applet>, <canvas>, <embed>, <fencedframe>, <iframe>, <img>, <input>, <marquee>, <object>, <source>, <spacer>, <svg>, <table>, <td>, <th>, <video>
<hgroup>	Part 6: Heading group
hidden	Part 4: global attribute
high	Part 9: attribute on <meter>
<hr>	Part 6: Thematic break (horizontal rule)
href	Part 9: attribute on <a>, <area>, <base>, <link>
hreflang	Part 9: attribute on <a>, <link>
hspace	Part 9: attribute on <applet>, <img>, <marquee>, <object>
<html>	Part 6: Document root
HTML	Part 14: glossary
HTTP / HTTPS	Part 14: glossary
http-equiv	Part 9: attribute on <meta>
Hyperlink	Part 14: glossary
<i>	Part 6: Idiomatic text (italic)
icon	Part 9: attribute on <menuitem>
id	Part 4: global attribute
id	Part 9: attribute on <input>
Id	Part 14: glossary

Term	Where to find it
<iframe>	Part 6: Inline frame
<image>	Part 6: Image (non-standard alias, obsolete)
imagesizes	Part 9: attribute on <link>
imagesrcset	Part 9: attribute on <link>
<img>	Part 6: Image
incremental	Part 9: attribute on <input>
inert	Part 4: global attribute
Inline element	Part 14: glossary
<input>	Part 6: Input control
inputmode	Part 4: global attribute
inputmode	Part 9: attribute on <input>
<ins>	Part 6: Inserted text
integrity	Part 9: attribute on <link>, <script>
is	Part 4: global attribute
<isindex>	Part 6: Search index prompt (obsolete)
ismap	Part 9: attribute on <img>
itemid, itemprop, itemref, itemscope, itemtype	Part 4: global attribute
itemprop	Part 9: attribute on <meta>
JavaScript	Part 14: glossary
justify-content (CSS)	Part 11: Layout
justify-items / justify-self / place-items / place-content / place-self (CSS)	Part 11: Layout

Term	Where to find it
<kbd>	Part 6: Keyboard input
<keygen>	Part 6: Key-pair generator (obsolete)
keytype	Part 9: attribute on <keygen>
kind	Part 9: attribute on <track>
<label>	Part 6: Form control label
label	Part 9: attribute on <menu>, <menuitem>, <optgroup>, <option>, <track>
Landmark	Part 14: glossary
lang	Part 4: global attribute
lang	Part 9: attribute on <html>
language	Part 9: attribute on <script>
leftmargin	Part 9: attribute on <body>
<legend>	Part 6: Fieldset caption
letter-spacing / word-spacing (CSS)	Part 11: Fonts and text
	Part 6: List item
line-height (CSS)	Part 11: Fonts and text
<link>	Part 6: External resource link
link	Part 9: attribute on <body>
list	Part 9: attribute on <input>
list-style (CSS)	Part 11: Fonts and text
<listing>	Part 6: Listing (obsolete)
Living Standard	Part 14: glossary
loading	Part 9: attribute on <iframe>, <img>
longdesc	Part 9: attribute on <frame>, <iframe>, <img>

Term	Where to find it
loop	Part 9: attribute on <audio>, <bgsound>, <marquee>, <video>
low	Part 9: attribute on <meter>
lowsrc	Part 9: attribute on <img>
<main>	Part 6: Main content
manifest	Part 9: attribute on <html>
<map>	Part 6: Image map
margin (CSS)	Part 11: Box model
marginheight	Part 9: attribute on <frame>, <iframe>
marginwidth	Part 9: attribute on <frame>, <iframe>
<mark>	Part 6: Highlighted (marked) text
<marquee>	Part 6: Scrolling text (obsolete)
<math>	Part 6: MathML root
max	Part 9: attribute on <input>, <meter>, <progress>
maxlength	Part 9: attribute on <input>, <textarea>
MDN	Part 14: glossary
media	Part 9: attribute on <link>, <meta>, <source>, <style>
<menu>	Part 6: Menu (toolbar list)
<menuitem>	Part 6: Menu item (obsolete)
<meta>	Part 6: Metadata
Metadata	Part 14: glossary
<meter>	Part 6: Scalar measurement (gauge)
method	Part 9: attribute on <form>
MIME type	Part 14: glossary

Term	Where to find it
min	Part 9: attribute on <input>, <meter>
min-width / max-width / min-height / max-height (CSS)	Part 11: Box model
minlength	Part 9: attribute on <input>, <textarea>
mix-blend-mode / isolation (CSS)	Part 11: Backgrounds
moz-opaque	Part 9: attribute on <canvas>
mozactionhint	Part 9: attribute on <input>
<multicol>	Part 6: Multi-column text (non-standard, obsolete)
multiple	Part 9: attribute on <input>, <select>
muted	Part 9: attribute on <audio>, <video>
n	Part 9: attribute on <nextid>
name	Part 9: attribute on <a>, <applet>, <button>, <details>, <fieldset>, <form>, <frame>, <iframe>, <img>, <input>, <keygen>, <map>, <meta>, <object>, <output>, <param>, <select>, <slot>, <textarea>
<nav>	Part 6: Navigation section
Nesting	Part 14: glossary
<nextid>	Part 6: Next identifier (HTML 1 editor hint)
<nobr>	Part 6: No line break (non-standard, obsolete)
<noembed>	Part 6: Fallback for embed (obsolete)
<noframes>	Part 6: Fallback for frames (obsolete)
nohref	Part 9: attribute on <area>
nomodule	Part 9: attribute on <script>
nonce	Part 4: global attribute
nonce	Part 9: attribute on <script>, <style>

Term	Where to find it
noresize	Part 9: attribute on <frame>
<noscript>	Part 6: Fallback when scripting is disabled
noshade	Part 9: attribute on <hr>
novalidate	Part 9: attribute on <form>
nowrap	Part 9: attribute on <dd>, <td>, <th>
<object>	Part 6: External object
object	Part 9: attribute on <applet>
object-fit / object-position (CSS)	Part 11: Box model
Obsolete	Part 14: glossary
	Part 6: Ordered list
onbeforeunload	Part 9: attribute on <body>
onhashchange	Part 9: attribute on <body>
onlanguagechange	Part 9: attribute on <body>
onload	Part 9: attribute on <body>
onpopstate	Part 9: attribute on <body>
onresize	Part 9: attribute on <body>
onstorage	Part 9: attribute on <body>
onunload	Part 9: attribute on <body>
opacity (CSS)	Part 11: Box model
open	Part 9: attribute on <details>, <dialog>
<optgroup>	Part 6: Option group
optimum	Part 9: attribute on <meter>
<option>	Part 6: Option
order (CSS)	Part 11: Layout
orient	Part 9: attribute on <input>

Term	Where to find it
outline (CSS)	Part 11: Box model
<output>	Part 6: Calculation or user-action result
overflow / overflow-x / overflow-y (CSS)	Part 11: Box model
overflow-wrap / word-break / hyphens (CSS)	Part 11: Fonts and text
<p>	Part 6: Paragraph
padding (CSS)	Part 11: Box model
<param>	Part 6: Object parameter (deprecated)
part	Part 4: global attribute
pattern	Part 9: attribute on <input>
Phrasing content	Part 14: glossary
<picture>	Part 6: Picture (responsive image container)
ping	Part 9: attribute on <a>, <area>
placeholder	Part 9: attribute on <input>, <textarea>
<plaintext>	Part 6: Plain text (obsolete)
playsinline	Part 9: attribute on <video>
pointer-events (CSS)	Part 11: Interaction
popover	Part 4: global attribute
popovertarget	Part 9: attribute on <button>, <input>
popovertargetaction	Part 9: attribute on <button>, <input>
<portal>	Part 6: Portal (experimental, abandoned)
position / top / right / bottom / left / inset / z-index (CSS)	Part 11: Layout
poster	Part 9: attribute on <video>

Term	Where to find it
<pre>	Part 6: Pre-formatted text
preload	Part 9: attribute on <audio>, <video>
preserveAspectRatio	Part 9: attribute on <svg>
profile	Part 9: attribute on <head>
<progress>	Part 6: Progress indicator
prompt	Part 9: attribute on <isindex>
property	Part 9: attribute on <meta>
Pseudo-class / pseudo-element	Part 14: glossary
<q>	Part 6: Inline quotation
Quirks mode	Part 14: glossary
quotes (CSS)	Part 11: Fonts and text
radiogroup	Part 9: attribute on <menuitem>
<rb>	Part 6: Ruby base (deprecated)
readonly	Part 9: attribute on <input>, <textarea>
referrerpolicy	Part 9: attribute on <a>, <area>, <iframe>, <img>, <link>, <portal>, <script>
rel	Part 9: attribute on <a>, <area>, <form>, <link>
Rendering	Part 14: glossary
required	Part 9: attribute on <input>, <select>, <textarea>
resize (CSS)	Part 11: Box model
Responsive design	Part 14: glossary
results	Part 9: attribute on <input>
rev	Part 9: attribute on <a>, <link>
reversed	Part 9: attribute on

Term	Where to find it
rightmargin	Part 9: attribute on <body>
role	Part 4: global attribute
role	Part 9: attribute on <svg>
rows	Part 9: attribute on <frameset>, <textarea>
rowspan	Part 9: attribute on <td>, <th>
<rp>	Part 6: Ruby fallback parenthesis
<rt>	Part 6: Ruby text (annotation)
<rtc>	Part 6: Ruby text container (deprecated)
<ruby>	Part 6: Ruby annotation
rules	Part 9: attribute on <table>
<s>	Part 6: Strikethrough (no longer accurate)
<samp>	Part 6: Sample output
sandbox	Part 9: attribute on <iframe>
scheme	Part 9: attribute on <meta>
scope	Part 9: attribute on <td>, <th>
scoped	Part 9: attribute on <style>
Screen reader	Part 14: glossary
<script>	Part 6: Script
scroll-behavior / scroll-snap-type / scroll-snap-align / scroll-margin / scroll-padding / overscroll-behavior (CSS)	Part 11: Motion
scrollamount	Part 9: attribute on <marquee>
scrolldelay	Part 9: attribute on <marquee>

Term	Where to find it
scrolling	Part 9: attribute on <frame>, <iframe>
<search>	Part 6: Search section
<section>	Part 6: Generic section
Sectioning content	Part 14: glossary
<select>	Part 6: Drop-down / list box
select	Part 9: attribute on <content>
selected	Part 9: attribute on <option>
<selectedcontent>	Part 6: Selected option display (customisable select)
Selector	Part 14: glossary
Semantic HTML	Part 14: glossary
<shadow>	Part 6: Shadow root insertion point (obsolete)
shadowrootclonable	Part 9: attribute on <template>
shadowrootdelegatesfocus	Part 9: attribute on <template>
shadowrootmode	Part 9: attribute on <template>
shadowrootserializable	Part 9: attribute on <template>
shape	Part 9: attribute on <a>, <area>
size	Part 9: attribute on <basefont>, <font>, <hr>, <input>, <select>, <spacer>
sizes	Part 9: attribute on <img>, <link>, <source>
<slot>	Part 6: Shadow DOM slot
slot	Part 4: global attribute
<small>	Part 6: Side comment (fine print)
<source>	Part 6: Media or image source
<spacer>	Part 6: Spacer (non-standard, obsolete)

Term	Where to find it
	Part 6: Generic inline container
span	Part 9: attribute on <col>, <colgroup>
Specificity	Part 14: glossary
spellcheck	Part 4: global attribute
spellcheck	Part 9: attribute on <textarea>
src	Part 9: attribute on <audio>, <bgsound>, <embed>, <frame>, <iframe>, <image>, <img>, <input>, <portal>, <script>, <source>, <track>, <video>
srcdoc	Part 9: attribute on <iframe>
srclang	Part 9: attribute on <track>
srcset	Part 9: attribute on <img>, <source>
standby	Part 9: attribute on <object>
start	Part 9: attribute on
step	Part 9: attribute on <input>
<strike>	Part 6: Strikethrough (obsolete)
stroke	Part 9: attribute on <svg>
stroke-width	Part 9: attribute on <svg>
	Part 6: Strong importance
<style>	Part 6: Embedded style sheet
style	Part 4: global attribute
<sub>	Part 6: Subscript
<summary>	Part 6: Disclosure summary
summary	Part 9: attribute on <table>
<sup>	Part 6: Superscript
<svg>	Part 6: Scalable Vector Graphics root

Term	Where to find it
tab-size (CSS)	Part 11: Fonts and text
tabindex	Part 4: global attribute
<table>	Part 6: Table
Tag	Part 14: glossary
target	Part 9: attribute on <a>, <area>, <base>, <form>, <link>
<tbody>	Part 6: Table body
<td>	Part 6: Table data cell
<template>	Part 6: Content template
text	Part 9: attribute on <body>
text-align (CSS)	Part 11: Fonts and text
text-decoration (CSS)	Part 11: Fonts and text
text-indent (CSS)	Part 11: Fonts and text
text-overflow (CSS)	Part 11: Fonts and text
text-shadow (CSS)	Part 11: Fonts and text
text-transform (CSS)	Part 11: Fonts and text
<textarea>	Part 6: Multi-line text input
<tfoot>	Part 6: Table footer
<th>	Part 6: Table header cell
<thead>	Part 6: Table header
<time>	Part 6: Date / time
<title>	Part 6: Document title
title	Part 4: global attribute
title	Part 9: attribute on <abbr>, <acronym>, <dfn>, <iframe>, <link>, <style>
topmargin	Part 9: attribute on <body>

Term	Where to find it
touch-action (CSS)	Part 11: Interaction
<tr>	Part 6: Table row
<track>	Part 6: Text track for media
transform / transform-origin / rotate / scale / translate (CSS)	Part 11: Motion
transition / transition-property / -duration / -timing-function / -delay (CSS)	Part 11: Motion
translate	Part 4: global attribute
truespeed	Part 9: attribute on <marquee>
<tt>	Part 6: Teletype text (obsolete)
type	Part 9: attribute on <a>, <area>, <button>, <embed>, <input>, , <link>, <menu>, <menuitem>, <object>, , <param>, <script>, <source>, <spacer>, <style>,
type=button	Part 7: input type
type=checkbox	Part 7: input type
type=color	Part 7: input type
type=date	Part 7: input type
type=datetime-local	Part 7: input type
type=email	Part 7: input type
type=file	Part 7: input type
type=hidden	Part 7: input type
type=image	Part 7: input type
type=month	Part 7: input type

Term	Where to find it
type=number	Part 7: input type
type=password	Part 7: input type
type=radio	Part 7: input type
type=range	Part 7: input type
type=reset	Part 7: input type
type=search	Part 7: input type
type=submit	Part 7: input type
type=tel	Part 7: input type
type=text	Part 7: input type
type=time	Part 7: input type
type=url	Part 7: input type
type=week	Part 7: input type
typemustmatch	Part 9: attribute on <object>
<u>	Part 6: Unarticulated annotation (underline)
	Part 6: Unordered list
URL	Part 14: glossary
usemap	Part 9: attribute on <img>, <input>, <object>
user-select (CSS)	Part 11: Fonts and text
UTF-8	Part 14: glossary
Validator	Part 14: glossary
valign	Part 9: attribute on <col>, <colgroup>, <tbody>, <td>, <tfoot>, <th>, <thead>, <tr>
value	Part 9: attribute on <button>, <data>, <input>, , <meter>, <option>, <param>, <progress>
valuetype	Part 9: attribute on <param>
<var>	Part 6: Variable

Term	Where to find it
version	Part 9: attribute on <html>
vertical-align (CSS)	Part 11: Fonts and text
<video>	Part 6: Embedded video
viewBox	Part 9: attribute on <svg>
Viewport	Part 14: glossary
virtualkeyboardpolicy	Part 4: global attribute
visibility (CSS)	Part 11: Box model
vlink	Part 9: attribute on <body>
volume	Part 9: attribute on <bgsound>
vspace	Part 9: attribute on <applet>, <img>, <marquee>, <object>
W3C	Part 14: glossary
<wbr>	Part 6: Word break opportunity
WCAG	Part 14: glossary
webkitdirectory	Part 9: attribute on <input>
WHATWG	Part 14: glossary
white-space (CSS)	Part 11: Fonts and text
width	Part 9: attribute on <applet>, <canvas>, <col>, <colgroup>, <embed>, <fencedframe>, <hr>, <iframe>, <img>, <input>, <marquee>, <multicol>, <object>, <pre>, <source>, <spacer>, <svg>, <table>, <td>, <th>, <video>
width / height (CSS)	Part 11: Box model
will-change (CSS)	Part 11: Motion
wrap	Part 9: attribute on <pre>, <textarea>
writingsuggestions	Part 4: global attribute
XHTML	Part 14: glossary

Term	Where to find it
xml:lang, xml:base, xml:space	Part 4: global attribute
xmlns	Part 9: attribute on <html>, <math>, <svg>
<xmp>	Part 6: Example text (obsolete)

Part 15

Practice Projects

1125 complete, ready-to-type projects: 45 page types for 25 different businesses, each with full HTML and CSS, a build guide, checklist and exercises.

How to use the projects

Every project is a small but complete website page. Each one gives you: a brief, learning goals, the elements and CSS features it teaches, a step-by-step build guide, the complete index.html and styles.css to type or copy, an explanation table for the important lines, a checklist to verify your result, and three exercises that extend it.

Projects are organised by type (45 types) and each type is repeated for 25 businesses, so you can pick the theme closest to your own idea, or build the same page for several themes to see how the same HTML skeleton changes with different content. Level 1 projects need only Parts 2 and 6 of this book; level 2 add Flexbox and Grid; level 3 add pseudo-classes such as :checked and :target, dialog, counters and a little JavaScript.

Project types

#	Type	Level	Teaches
1	Landing page	1	background, color, padding, border-radius
2	Navigation bar	1	display: flex, justify-content, gap, list-style
3	Price table	1	border-collapse, padding, :nth-child(even), text-align
4	Contact form	1	display: grid, gap, font: inherit, :focus-visible
5	Photo gallery	1	grid-template-columns, auto-fill, aspect-ratio, object-fit

#	Type	Level	Teaches
6	About page	1	max-width, font-family, font-size, border-left
7	Menu list	2	display: flex, justify-content, ::after, order
8	FAQ accordion	2	[open], ::after, content, list-style: none
9	Product card	1	place-items: center, box-shadow, border-radius, overflow: hidden
10	Site footer	1	min-height: 100vh, flex: 1, grid, text-transform
11	Full-screen hero banner	2	background shorthand, linear-gradient, background-size: cover, min-height: 80vh
12	Team page	1	border-radius: 50%, object-fit: cover, border, text-align: center
13	Testimonials section	2	position: relative/absolute, ::before, content, opacity
14	Newsletter sign-up box	1	flex: 1 1 12rem, flex-wrap, .sr-only pattern, border-radius: 999px
15	Sidebar layout	2	grid-template-areas, grid-area, @media (min-width), position: sticky
16	Login form	1	width: min(), box-shadow, :not(), display: flex
17	Vertical timeline	2	position: relative, position: absolute, ::before, border-radius: 50%

#	Type	Level	Teaches
18	Statistics dashboard	2	border-top, text-transform, letter-spacing, border-radius: 999px
19	404 error page	1	place-content: center, clamp(), -webkit-text-stroke, line-height
20	Blog article	2	font-family pairs, clamp(), border-left, border-radius partial
21	Weekly schedule grid	2	border-collapse: separate, border-spacing, :not(:empty), border-radius on cells
22	CV / resume page	2	border-bottom, text-transform, letter-spacing, flex-wrap
23	Event page	1	grid-template-columns: max-content 1fr, gap (two values), border-radius, padding-left
24	Printable invoice	2	justify-content: space-between, colspan, font-variant-numeric, border-top
25	Feature list with icons	1	display: flex, align-items: flex-start, flex: 0 0 3rem, place-items
26	Find-us page with map	2	grid-template-columns: 1fr 1.4fr, aspect-ratio, border: 0, align-items: start
27	CSS-only tabs	3	:checked, ~ combinator, attribute selector, display: none/block
28	Modal dialog	3	::backdrop, backdrop-filter, box-shadow, border-radius

#	Type	Level	Teaches
29	Search bar and results page	2	flex: 1 1 18rem, border-radius (four values), border-right: 0, list-style: none
30	Order progress tracker	3	counter-reset, counter(), ::before/::after, translate
31	Split-screen feature section	2	grid-template-columns: 1fr 1fr, object-fit: cover, align-content: center, clamp()
32	Statistics strip	1	flex-direction: column-reverse, grid auto-fit, font-weight: 800, line-height: 1
33	Breadcrumbs and pagination	1	adjacent sibling +, ::before content, attribute selector, min-width
34	Alert message components	1	border: 1px solid, border-left-width, border-color, background
35	Booking form in three steps	2	fieldset border/radius, legend, display: flex on label, margin-left: auto
36	Video and audio page	2	aspect-ratio: 16 / 9, width: 100%, background, border-radius
37	Product grid with clickable cards	2	position: relative + ::after inset: 0, flex-direction: column, margin-top: auto, transition
38	Light and dark theme switcher	3	custom properties, @media (prefers-color-scheme), [data-theme], color-scheme
39	Printable voucher	2	@media print, display: none, page-break-inside, attr()

#	Type	Level	Teaches
40	Month calendar	3	table-layout: fixed, vertical-align: top, height on td, :last-child
41	Responsive hamburger menu	3	:checked ~, flex-basis: 100%, display: none/block, @media (min-width)
42	Glossary with letter navigation	2	position: sticky, :target, scroll-margin-top, place-items
43	Pricing plans comparison	2	transform: scale(), position: absolute + translate, align-items: start, ::before content
44	Step-by-step how-to page	2	counter-reset/increment, grid-template-columns: 3rem 1fr, grid-row: 1 / 3, grid-column: 2
45	Complete one-page website	3	position: sticky, z-index, scroll-margin-top, grid auto-fit

Business themes

Theme	City	Offers
Cairo Book Shop	Giza	PDF and printed books about web development
Nile Bakery	Cairo	Fresh bread and pastries every morning
Pyramid Fitness	6th of October	Train smarter, feel stronger
Delta Dental Clinic	Mansoura	Gentle care for the whole family
Red Sea Travel	Hurghada	Discover Egypt from desert to reef

Theme	City	Offers
Lotus Language School	Alexandria	Learn English, French and German in small groups
Green Leaf Cafe	Zamalek	Specialty coffee and quiet corners
Sinai Trekking Club	Saint Catherine	Guided mountain walks for every level
Horizon Photography	Maadi	Portraits, weddings and product photography
Papyrus Stationery	Heliopolis	Notebooks, pens and paper made in Egypt
Oasis Plant Nursery	Sheikh Zayed	Indoor plants and gardening advice
Cedar Furniture	Damietta	Solid wood furniture made to order
Byte Repair	Nasr City	Phone and laptop repairs while you wait
Sahara Pet Care	New Cairo	Grooming, boarding and vet visits
Alexandria Sailing School	Alexandria	Learn to sail on the Mediterranean
Habiba Handmade Jewellery	Aswan	Silver and brass pieces inspired by Nubia
Fayoum Pottery Studio	Tunis Village	Wheel throwing and glazing classes
Cleopatra Beauty Salon	Dokki	Hair, nails and skin care
Suez Auto Service	Suez	Honest car servicing and repairs
Luxor Music Academy	Luxor	Oud, piano, guitar and voice lessons
Port Said Seafood	Port Said	Grilled fish straight from the boats

Theme	City	Offers
Delta Kids Library	Tanta	Stories, reading clubs and homework help
Nubian Guest House	Aswan	Colourful rooms on the west bank of the Nile
Ismailia Cycling Store	Ismailia	Bikes, parts and Friday group rides
Minya Coding Club	Minya	Free weekend coding for teenagers

Project type: Landing page

Level 1 | 25 projects, one per theme

Build a one-screen landing page: a coloured hero with the business name, tagline and a call-to-action button, a grid of three cards and a footer.

Project 1: Landing page for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 1 | Files: index.html, styles.css

Brief

Build a one-screen landing page: a coloured hero with the business name, tagline and a call-to-action button, a grid of three cards and a footer.

Learning goals

- Use header, main, section and footer landmarks
- Centre content with max-width and margin auto
- Create a responsive card grid with one line of CSS Grid

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, main, section, h2, ul, li, h3, strong, footer	background, color, padding, border-radius, display: grid, grid-template-columns, repeat(auto-fit, minmax()), gap, max-width

Build guide

1. Create index.html with the standard skeleton and link styles.css.
2. Add the <header class="hero"> with h1, tagline and a link styled as a button.
3. Add <main> with a <section> containing a <ul class="cards"> of three <li class="card"> items.
4. Add the footer with the copyright line.

5. In styles.css set the CSS variables in :root, style the hero, then the grid.
6. Resize the browser: the cards should go from three columns to one.

Project 1: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <h1>Cairo Book Shop</h1>
    <p class="tagline">PDF and printed books about web development</p>
    <a class="btn" href="#offers">See our books</a>
  </header>
  <main>
    <section id="offers">
      <h2>Popular books</h2>
      <ul class="cards">
    <li class="card"><h3>Learn HTML</h3><p>From your first tag to a
complete page</p><strong>120 EGP</strong></li>
    <li class="card"><h3>CSS in Practice</h3><p>Layouts, colours and
typography</p><strong>150 EGP</strong></li>
    <li class="card"><h3>JavaScript Basics</h3><p>Make pages
interactive</p><strong>180 EGP</strong></li>
      </ul>
    </section>
  </main>
  <footer>
    <p>&copy; 2026 Cairo Book Shop, Giza</p>
  </footer>
</body>
</html>
```

Project 1: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(2rem, 5vw, 3rem); }
.tagline { font-size: 1.2rem; opacity: .9; }
.btn { display: inline-block; margin-top: 1rem; padding: .7rem 1.5rem;
 background: #fff; color: var(--brand); border-radius: 999px; text-
decoration: none; font-weight: bold; }
```

```
main { max-width: 60rem; margin: 0 auto; padding: 2rem 1rem; }
.cards { list-style: none; padding: 0; display: grid; gap: 1rem; grid-
template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
footer { text-align: center; padding: 1.5rem; color: var(--muted);
border-top: 1px solid var(--line); }
```

Project 1 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
Cairo Book Shop	The main heading; only one per page.
PDF and printed books about web development	A paragraph of text.
See our books	A link styled as a button; it navigates, so it is a link and not a <button>.
<main>	The unique content of this page; exactly one per page.
<section id="offers">	A thematic group of content, normally with its own heading.
Popular books	Second-level heading for a section.
<ul class="cards">	Unordered (bulleted) list.

Line	What it does
<li class="card"> Learn HTML From your first tag to a com...	Third-level heading, inside an h2 section.
<li class="card"> CSS in Practice Layouts, colours and ty...	One list item.
<li class="card"> JavaScript Basics Make pages interactiv...	Strong importance (bold by default).
<footer>	Footer of the page or of a section.
© 2026 Cairo Book Shop, Giza	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.

Declaration	What it does
color: var(--ink);	Text colour.
background: var(--brand);	Background colour or image.
text-align: center;	Centres inline content such as text.
padding: 4rem 1rem;	Space inside the element between its border and content.
font-size: clamp(2rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-size: 1.2rem;	Size of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
font-weight: bold;	Thickness of the text.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Check your work

- Exactly one h1
- Button link has descriptive text
- Cards wrap on narrow screens
- Footer text is readable (contrast)

Exercises

1. Add a fourth card and check the grid still works.
2. Change the hero to a background image with a dark overlay.
3. Add a <nav> with three links inside the header.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 2: Landing page for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 1 | Files: index.html, styles.css

Brief

Build a one-screen landing page: a coloured hero with the business name, tagline and a call-to-action button, a grid of three cards and a footer.

Learning goals

- Use header, main, section and footer landmarks
- Centre content with max-width and margin auto
- Create a responsive card grid with one line of CSS Grid

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, main, section, h2, ul, li, h3, strong, footer	background, color, padding, border-radius, display: grid, grid-template-columns, repeat(auto-fit, minmax()), gap, max-width

Build guide

1. Create index.html with the standard skeleton and link styles.css.
2. Add the <header class="hero"> with h1, tagline and a link styled as a button.
3. Add <main> with a <section> containing a <ul class="cards"> of three <li class="card"> items.
4. Add the footer with the copyright line.

5. In styles.css set the CSS variables in :root, style the hero, then the grid.
6. Resize the browser: the cards should go from three columns to one.

Project 2: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <h1>Nile Bakery</h1>
    <p class="tagline">Fresh bread and pastries every morning</p>
    <a class="btn" href="#offers">See our pastries</a>
  </header>
  <main>
    <section id="offers">
      <h2>Popular pastries</h2>
      <ul class="cards">
    <li class="card"><h3>Sourdough loaf</h3><p>Slow fermented, crisp
crust</p><strong>60 EGP</strong></li>
    <li class="card"><h3>Croissant</h3><p>Butter, 27 layers</
p><strong>35 EGP</strong></li>
    <li class="card"><h3>Date cookies</h3><p>Traditional maamoul
style</p><strong>80 EGP</strong></li>
      </ul>
    </section>
  </main>
  <footer>
    <p>&copy; 2026 Nile Bakery, Cairo</p>
  </footer>
</body>
</html>
```

Project 2: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(2rem, 5vw, 3rem); }
.tagline { font-size: 1.2rem; opacity: .9; }
.btn { display: inline-block; margin-top: 1rem; padding: .7rem 1.5rem;
 background: #fff; color: var(--brand); border-radius: 999px; text-
decoration: none; font-weight: bold; }
```

```
main { max-width: 60rem; margin: 0 auto; padding: 2rem 1rem; }
.cards { list-style: none; padding: 0; display: grid; gap: 1rem; grid-
template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
footer { text-align: center; padding: 1.5rem; color: var(--muted);
border-top: 1px solid var(--line); }
```

Project 2 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
Nile Bakery	The main heading; only one per page.
Fresh bread and pastries every morning	A paragraph of text.
See our pastries	A link styled as a button; it navigates, so it is a link and not a <button>.
<main>	The unique content of this page; exactly one per page.
<section id="offers">	A thematic group of content, normally with its own heading.
Popular pastries	Second-level heading for a section.
<ul class="cards">	Unordered (bulleted) list.

Line	What it does
<li class="card"> Sourdough loaf Slow fermented, crisp cr...	Third-level heading, inside an h2 section.
<li class="card"> Croissant Butter, 27 layers ...	One list item.
<li class="card"> Date cookies Traditional maamoul style<...	Strong importance (bold by default).
<footer>	Footer of the page or of a section.
© 2026 Nile Bakery, Cairo	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-align: center;	Centres inline content such as text.
padding: 4rem 1rem;	Space inside the element between its border and content.
font-size: clamp(2rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-size: 1.2rem;	Size of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
font-weight: bold;	Thickness of the text.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Check your work

- Exactly one h1
- Button link has descriptive text
- Cards wrap on narrow screens
- Footer text is readable (contrast)

Exercises

1. Add a fourth card and check the grid still works.
2. Change the hero to a background image with a dark overlay.
3. Add a <nav> with three links inside the header.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 3: Landing page for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 1 | Files: index.html, styles.css

Brief

Build a one-screen landing page: a coloured hero with the business name, tagline and a call-to-action button, a grid of three cards and a footer.

Learning goals

- Use header, main, section and footer landmarks
- Centre content with max-width and margin auto
- Create a responsive card grid with one line of CSS Grid

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, main, section, h2, ul, li, h3, strong, footer	background, color, padding, border-radius, display: grid, grid-template-columns, repeat(auto-fit, minmax()), gap, max-width

Build guide

1. Create index.html with the standard skeleton and link styles.css.
2. Add the <header class="hero"> with h1, tagline and a link styled as a button.
3. Add <main> with a <section> containing a <ul class="cards"> of three <li class="card"> items.
4. Add the footer with the copyright line.

5. In styles.css set the CSS variables in :root, style the hero, then the grid.
6. Resize the browser: the cards should go from three columns to one.

Project 3: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <h1>Pyramid Fitness</h1>
    <p class="tagline">Train smarter, feel stronger</p>
    <a class="btn" href="#offers">See our classes</a>
  </header>
  <main>
    <section id="offers">
      <h2>Popular classes</h2>
      <ul class="cards">
    <li class="card"><h3>Morning yoga</h3><p>Flexibility and calm, 60
minutes</p><strong>100 EGP</strong></li>
    <li class="card"><h3>Strength circuit</h3><p>Full body, all
levels</p><strong>120 EGP</strong></li>
    <li class="card"><h3>Spinning</h3><p>High energy cycling</
p><strong>110 EGP</strong></li>
      </ul>
    </section>
  </main>
  <footer>
    <p>&copy; 2026 Pyramid Fitness, 6th of October</p>
  </footer>
</body>
</html>
```

Project 3: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(2rem, 5vw, 3rem); }
.tagline { font-size: 1.2rem; opacity: .9; }
.btn { display: inline-block; margin-top: 1rem; padding: .7rem 1.5rem;
 background: #fff; color: var(--brand); border-radius: 999px; text-
decoration: none; font-weight: bold; }
```

```
main { max-width: 60rem; margin: 0 auto; padding: 2rem 1rem; }
.cards { list-style: none; padding: 0; display: grid; gap: 1rem; grid-
template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
footer { text-align: center; padding: 1.5rem; color: var(--muted);
border-top: 1px solid var(--line); }
```

Project 3 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
Pyramid Fitness	The main heading; only one per page.
Train smarter, feel stronger	A paragraph of text.
See our classes	A link styled as a button; it navigates, so it is a link and not a <button>.
<main>	The unique content of this page; exactly one per page.
<section id="offers">	A thematic group of content, normally with its own heading.
Popular classes	Second-level heading for a section.
<ul class="cards">	Unordered (bulleted) list.

Line	What it does
<li class="card"> Morning yoga Flexibility and calm, 60 m...	Third-level heading, inside an h2 section.
<li class="card"> Strength circuit Full body, all levels<...	One list item.
<li class="card"> Spinning High energy cycling <strong...	Strong importance (bold by default).
<footer>	Footer of the page or of a section.
© 2026 Pyramid Fitness, 6th of October	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.

Declaration	What it does
color: var(--ink);	Text colour.
background: var(--brand);	Background colour or image.
text-align: center;	Centres inline content such as text.
padding: 4rem 1rem;	Space inside the element between its border and content.
font-size: clamp(2rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-size: 1.2rem;	Size of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
font-weight: bold;	Thickness of the text.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Check your work

- Exactly one h1
- Button link has descriptive text
- Cards wrap on narrow screens
- Footer text is readable (contrast)

Exercises

1. Add a fourth card and check the grid still works.
2. Change the hero to a background image with a dark overlay.
3. Add a <nav> with three links inside the header.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 4: Landing page for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 1 | Files: index.html, styles.css

Brief

Build a one-screen landing page: a coloured hero with the business name, tagline and a call-to-action button, a grid of three cards and a footer.

Learning goals

- Use header, main, section and footer landmarks
- Centre content with max-width and margin auto
- Create a responsive card grid with one line of CSS Grid

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, main, section, h2, ul, li, h3, strong, footer	background, color, padding, border-radius, display: grid, grid-template-columns, repeat(auto-fit, minmax()), gap, max-width

Build guide

1. Create index.html with the standard skeleton and link styles.css.
2. Add the <header class="hero"> with h1, tagline and a link styled as a button.
3. Add <main> with a <section> containing a <ul class="cards"> of three <li class="card"> items.
4. Add the footer with the copyright line.

5. In styles.css set the CSS variables in :root, style the hero, then the grid.
6. Resize the browser: the cards should go from three columns to one.

Project 4: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <h1>Delta Dental Clinic</h1>
    <p class="tagline">Gentle care for the whole family</p>
    <a class="btn" href="#offers">See our services</a>
  </header>
  <main>
    <section id="offers">
      <h2>Popular services</h2>
      <ul class="cards">
    <li class="card"><h3>Check-up</h3><p>Examination and cleaning</
p><strong>300 EGP</strong></li>
    <li class="card"><h3>Whitening</h3><p>Brighter smile in one
visit</p><strong>1500 EGP</strong></li>
    <li class="card"><h3>Filling</h3><p>Tooth-coloured composite</
p><strong>600 EGP</strong></li>
      </ul>
    </section>
  </main>
  <footer>
    <p>&copy; 2026 Delta Dental Clinic, Mansoura</p>
  </footer>
</body>
</html>
```

Project 4: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(2rem, 5vw, 3rem); }
.tagline { font-size: 1.2rem; opacity: .9; }
.btn { display: inline-block; margin-top: 1rem; padding: .7rem 1.5rem;
 background: #fff; color: var(--brand); border-radius: 999px; text-
decoration: none; font-weight: bold; }
```

```
main { max-width: 60rem; margin: 0 auto; padding: 2rem 1rem; }
.cards { list-style: none; padding: 0; display: grid; gap: 1rem; grid-
template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
footer { text-align: center; padding: 1.5rem; color: var(--muted);
border-top: 1px solid var(--line); }
```

Project 4 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
Delta Dental Clinic	The main heading; only one per page.
Gentle care for the whole family	A paragraph of text.
See our services	A link styled as a button; it navigates, so it is a link and not a <button>.
<main>	The unique content of this page; exactly one per page.
<section id="offers">	A thematic group of content, normally with its own heading.
Popular services	Second-level heading for a section.
<ul class="cards">	Unordered (bulleted) list.

Line	What it does
<li class="card"> Check-up Examination and cleaning <s...	Third-level heading, inside an h2 section.
<li class="card"> Whitening Brighter smile in one visit<//...	One list item.
<li class="card"> Filling Tooth-coloured composite <st...	Strong importance (bold by default).
<footer>	Footer of the page or of a section.
© 2026 Delta Dental Clinic, Mansoura	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-align: center;	Centres inline content such as text.
padding: 4rem 1rem;	Space inside the element between its border and content.
font-size: clamp(2rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-size: 1.2rem;	Size of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
font-weight: bold;	Thickness of the text.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Check your work

- Exactly one h1
- Button link has descriptive text
- Cards wrap on narrow screens
- Footer text is readable (contrast)

Exercises

1. Add a fourth card and check the grid still works.
2. Change the hero to a background image with a dark overlay.
3. Add a <nav> with three links inside the header.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 5: Landing page for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 1 | Files: index.html, styles.css

Brief

Build a one-screen landing page: a coloured hero with the business name, tagline and a call-to-action button, a grid of three cards and a footer.

Learning goals

- Use header, main, section and footer landmarks
- Centre content with max-width and margin auto
- Create a responsive card grid with one line of CSS Grid

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, main, section, h2, ul, li, h3, strong, footer	background, color, padding, border-radius, display: grid, grid-template-columns, repeat(auto-fit, minmax()), gap, max-width

Build guide

1. Create index.html with the standard skeleton and link styles.css.
2. Add the <header class="hero"> with h1, tagline and a link styled as a button.
3. Add <main> with a <section> containing a <ul class="cards"> of three <li class="card"> items.
4. Add the footer with the copyright line.

5. In styles.css set the CSS variables in :root, style the hero, then the grid.
6. Resize the browser: the cards should go from three columns to one.

Project 5: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <h1>Red Sea Travel</h1>
    <p class="tagline">Discover Egypt from desert to reef</p>
    <a class="btn" href="#offers">See our tours</a>
  </header>
  <main>
    <section id="offers">
      <h2>Popular tours</h2>
      <ul class="cards">
    <li class="card"><h3>Luxor day trip</h3><p>Karnak, Valley of the
Kings</p><strong>1200 EGP</strong></li>
    <li class="card"><h3>Snorkelling</h3><p>Giftun island reefs</
p><strong>700 EGP</strong></li>
    <li class="card"><h3>Desert safari</h3><p>Quad bikes and Bedouin
dinner</p><strong>900 EGP</strong></li>
      </ul>
    </section>
  </main>
  <footer>
    <p>&copy; 2026 Red Sea Travel, Hurghada</p>
  </footer>
</body>
</html>
```

Project 5: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(2rem, 5vw, 3rem); }
.tagline { font-size: 1.2rem; opacity: .9; }
.btn { display: inline-block; margin-top: 1rem; padding: .7rem 1.5rem;
 background: #fff; color: var(--brand); border-radius: 999px; text-
decoration: none; font-weight: bold; }
```

```
main { max-width: 60rem; margin: 0 auto; padding: 2rem 1rem; }
.cards { list-style: none; padding: 0; display: grid; gap: 1rem; grid-
template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
footer { text-align: center; padding: 1.5rem; color: var(--muted);
border-top: 1px solid var(--line); }
```

Project 5 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
Red Sea Travel	The main heading; only one per page.
Discover Egypt from desert to reef	A paragraph of text.
See our tours	A link styled as a button; it navigates, so it is a link and not a <button>.
<main>	The unique content of this page; exactly one per page.
<section id="offers">	A thematic group of content, normally with its own heading.
Popular tours	Second-level heading for a section.
<ul class="cards">	Unordered (bulleted) list.

Line	What it does
<li class="card"> Luxor day trip Karnak, Valley of the Ki...	Third-level heading, inside an h2 section.
<li class="card"> Snorkelling Giftun island reefs <str...	One list item.
<li class="card"> Desert safari Quad bikes and Bedouin di...	Strong importance (bold by default).
<footer>	Footer of the page or of a section.
© 2026 Red Sea Travel, Hurghada	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-align: center;	Centres inline content such as text.
padding: 4rem 1rem;	Space inside the element between its border and content.
font-size: clamp(2rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-size: 1.2rem;	Size of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
font-weight: bold;	Thickness of the text.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Check your work

- Exactly one h1
- Button link has descriptive text
- Cards wrap on narrow screens
- Footer text is readable (contrast)

Exercises

1. Add a fourth card and check the grid still works.
2. Change the hero to a background image with a dark overlay.
3. Add a <nav> with three links inside the header.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 6: Landing page for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Build a one-screen landing page: a coloured hero with the business name, tagline and a call-to-action button, a grid of three cards and a footer.

Learning goals

- Use header, main, section and footer landmarks
- Centre content with max-width and margin auto
- Create a responsive card grid with one line of CSS Grid

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, main, section, h2, ul, li, h3, strong, footer	background, color, padding, border-radius, display: grid, grid-template-columns, repeat(auto-fit, minmax()), gap, max-width

Build guide

1. Create index.html with the standard skeleton and link styles.css.
2. Add the <header class="hero"> with h1, tagline and a link styled as a button.
3. Add <main> with a <section> containing a <ul class="cards"> of three <li class="card"> items.
4. Add the footer with the copyright line.

5. In styles.css set the CSS variables in :root, style the hero, then the grid.
6. Resize the browser: the cards should go from three columns to one.

Project 6: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <h1>Lotus Language School</h1>
    <p class="tagline">Learn English, French and German in small
groups</p>
    <a class="btn" href="#offers">See our courses</a>
  </header>
  <main>
    <section id="offers">
      <h2>Popular courses</h2>
      <ul class="cards">
    <li class="card"><h3>English A1</h3><p>Beginner, 8 weeks</
p><strong>1800 EGP</strong></li>
    <li class="card"><h3>French B1</h3><p>Intermediate conversation</
p><strong>2200 EGP</strong></li>
    <li class="card"><h3>German A2</h3><p>Grammar and speaking</
p><strong>2000 EGP</strong></li>
      </ul>
    </section>
  </main>
  <footer>
    <p>&copy; 2026 Lotus Language School, Alexandria</p>
  </footer>
</body>
</html>
```

Project 6: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(2rem, 5vw, 3rem); }
.tagline { font-size: 1.2rem; opacity: .9; }
.btn { display: inline-block; margin-top: 1rem; padding: .7rem 1.5rem;
 background: #fff; color: var(--brand); border-radius: 999px; text-
```

```
decoration: none; font-weight: bold; }
main { max-width: 60rem; margin: 0 auto; padding: 2rem 1rem; }
.cards { list-style: none; padding: 0; display: grid; gap: 1rem; grid-
template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
footer { text-align: center; padding: 1.5rem; color: var(--muted);
border-top: 1px solid var(--line); }
```

Project 6 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
Lotus Language School	The main heading; only one per page.
<p class="tagline">Learn English, French and German in small groups...	A paragraph of text.
See our courses	A link styled as a button; it navigates, so it is a link and not a <button>.
<main>	The unique content of this page; exactly one per page.
<section id="offers">	A thematic group of content, normally with its own heading.
Popular courses	Second-level heading for a section.
<ul class="cards">	Unordered (bulleted) list.

Line	What it does
<li class="card"> English A1 Beginner, 8 weeks <strong...	Third-level heading, inside an h2 section.
<li class="card"> French B1 Intermediate conversation ...	One list item.
<li class="card"> German A2 Grammar and speaking <stro...	Strong importance (bold by default).
<footer>	Footer of the page or of a section.
© 2026 Lotus Language School, Alexandria	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.

Declaration	What it does
color: var(--ink);	Text colour.
background: var(--brand);	Background colour or image.
text-align: center;	Centres inline content such as text.
padding: 4rem 1rem;	Space inside the element between its border and content.
font-size: clamp(2rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-size: 1.2rem;	Size of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
font-weight: bold;	Thickness of the text.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Check your work

- Exactly one h1
- Button link has descriptive text
- Cards wrap on narrow screens
- Footer text is readable (contrast)

Exercises

1. Add a fourth card and check the grid still works.
2. Change the hero to a background image with a dark overlay.
3. Add a <nav> with three links inside the header.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 7: Landing page for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 1 | Files: index.html, styles.css

Brief

Build a one-screen landing page: a coloured hero with the business name, tagline and a call-to-action button, a grid of three cards and a footer.

Learning goals

- Use header, main, section and footer landmarks
- Centre content with max-width and margin auto
- Create a responsive card grid with one line of CSS Grid

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, main, section, h2, ul, li, h3, strong, footer	background, color, padding, border-radius, display: grid, grid-template-columns, repeat(auto-fit, minmax()), gap, max-width

Build guide

1. Create index.html with the standard skeleton and link styles.css.
2. Add the <header class="hero"> with h1, tagline and a link styled as a button.
3. Add <main> with a <section> containing a <ul class="cards"> of three <li class="card"> items.
4. Add the footer with the copyright line.

5. In styles.css set the CSS variables in :root, style the hero, then the grid.
6. Resize the browser: the cards should go from three columns to one.

Project 7: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <h1>Green Leaf Cafe</h1>
    <p class="tagline">Specialty coffee and quiet corners</p>
    <a class="btn" href="#offers">See our drinks</a>
  </header>
  <main>
    <section id="offers">
      <h2>Popular drinks</h2>
      <ul class="cards">
    <li class="card"><h3>Flat white</h3><p>Double shot, silky milk</
p><strong>55 EGP</strong></li>
    <li class="card"><h3>Cold brew</h3><p>18 hours steeped</
p><strong>60 EGP</strong></li>
    <li class="card"><h3>Hibiscus iced tea</h3><p>Karkade with mint</
p><strong>40 EGP</strong></li>
      </ul>
    </section>
  </main>
  <footer>
    <p>&copy; 2026 Green Leaf Cafe, Zamalek</p>
  </footer>
</body>
</html>
```

Project 7: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(2rem, 5vw, 3rem); }
.tagline { font-size: 1.2rem; opacity: .9; }
.btn { display: inline-block; margin-top: 1rem; padding: .7rem 1.5rem;
 background: #fff; color: var(--brand); border-radius: 999px; text-
decoration: none; font-weight: bold; }
```

```
main { max-width: 60rem; margin: 0 auto; padding: 2rem 1rem; }
.cards { list-style: none; padding: 0; display: grid; gap: 1rem; grid-
template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
footer { text-align: center; padding: 1.5rem; color: var(--muted);
border-top: 1px solid var(--line); }
```

Project 7 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
Green Leaf Cafe	The main heading; only one per page.
Specialty coffee and quiet corners	A paragraph of text.
See our drinks	A link styled as a button; it navigates, so it is a link and not a <button>.
<main>	The unique content of this page; exactly one per page.
<section id="offers">	A thematic group of content, normally with its own heading.
Popular drinks	Second-level heading for a section.
<ul class="cards">	Unordered (bulleted) list.

Line	What it does
<li class="card"> Flat white Double shot, silky milk <...	Third-level heading, inside an h2 section.
<li class="card"> Cold brew 18 hours steeped 6...	One list item.
<li class="card"> Hibiscus iced tea Karkade with mint ...	Strong importance (bold by default).
<footer>	Footer of the page or of a section.
© 2026 Green Leaf Cafe, Zamalek	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.

Declaration	What it does
color: var(--ink);	Text colour.
background: var(--brand);	Background colour or image.
text-align: center;	Centres inline content such as text.
padding: 4rem 1rem;	Space inside the element between its border and content.
font-size: clamp(2rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-size: 1.2rem;	Size of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
font-weight: bold;	Thickness of the text.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Check your work

- Exactly one h1
- Button link has descriptive text
- Cards wrap on narrow screens
- Footer text is readable (contrast)

Exercises

1. Add a fourth card and check the grid still works.
2. Change the hero to a background image with a dark overlay.
3. Add a <nav> with three links inside the header.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 8: Landing page for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 1 | Files: index.html, styles.css

Brief

Build a one-screen landing page: a coloured hero with the business name, tagline and a call-to-action button, a grid of three cards and a footer.

Learning goals

- Use header, main, section and footer landmarks
- Centre content with max-width and margin auto
- Create a responsive card grid with one line of CSS Grid

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, main, section, h2, ul, li, h3, strong, footer	background, color, padding, border-radius, display: grid, grid-template-columns, repeat(auto-fit, minmax()), gap, max-width

Build guide

1. Create index.html with the standard skeleton and link styles.css.
2. Add the <header class="hero"> with h1, tagline and a link styled as a button.
3. Add <main> with a <section> containing a <ul class="cards"> of three <li class="card"> items.
4. Add the footer with the copyright line.

5. In styles.css set the CSS variables in :root, style the hero, then the grid.
6. Resize the browser: the cards should go from three columns to one.

Project 8: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <h1>Sinai Trekking Club</h1>
    <p class="tagline">Guided mountain walks for every level</p>
    <a class="btn" href="#offers">See our hikes</a>
  </header>
  <main>
    <section id="offers">
      <h2>Popular hikes</h2>
      <ul class="cards">
    <li class="card"><h3>Mount Sinai sunrise</h3><p>Night climb, 7
km</p><strong>400 EGP</strong></li>
    <li class="card"><h3>Blue Desert loop</h3><p>Easy day walk</
p><strong>250 EGP</strong></li>
    <li class="card"><h3>Wadi Gnai</h3><p>Palms and pools</
p><strong>300 EGP</strong></li>
      </ul>
    </section>
  </main>
  <footer>
    <p>&copy; 2026 Sinai Trekking Club, Saint Catherine</p>
  </footer>
</body>
</html>
```

Project 8: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(2rem, 5vw, 3rem); }
.tagline { font-size: 1.2rem; opacity: .9; }
.btn { display: inline-block; margin-top: 1rem; padding: .7rem 1.5rem;
 background: #fff; color: var(--brand); border-radius: 999px; text-
decoration: none; font-weight: bold; }
```

```
main { max-width: 60rem; margin: 0 auto; padding: 2rem 1rem; }
.cards { list-style: none; padding: 0; display: grid; gap: 1rem; grid-
template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
footer { text-align: center; padding: 1.5rem; color: var(--muted);
border-top: 1px solid var(--line); }
```

Project 8 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
Sinai Trekking Club	The main heading; only one per page.
Guided mountain walks for every level	A paragraph of text.
See our hikes	A link styled as a button; it navigates, so it is a link and not a <button>.
<main>	The unique content of this page; exactly one per page.
<section id="offers">	A thematic group of content, normally with its own heading.
Popular hikes	Second-level heading for a section.
<ul class="cards">	Unordered (bulleted) list.

Line	What it does
<li class="card"> Mount Sinai sunrise Night climb, 7 km<//...	Third-level heading, inside an h2 section.
<li class="card"> Blue Desert loop Easy day walk <stro...	One list item.
<li class="card"> Wadi Gnai Palms and pools 30...	Strong importance (bold by default).
<footer>	Footer of the page or of a section.
© 2026 Sinai Trekking Club, Saint Catherine	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.

Declaration	What it does
color: var(--ink);	Text colour.
background: var(--brand);	Background colour or image.
text-align: center;	Centres inline content such as text.
padding: 4rem 1rem;	Space inside the element between its border and content.
font-size: clamp(2rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-size: 1.2rem;	Size of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
font-weight: bold;	Thickness of the text.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Check your work

- Exactly one h1
- Button link has descriptive text
- Cards wrap on narrow screens
- Footer text is readable (contrast)

Exercises

1. Add a fourth card and check the grid still works.
2. Change the hero to a background image with a dark overlay.
3. Add a <nav> with three links inside the header.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 9: Landing page for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 1 | Files: index.html, styles.css

Brief

Build a one-screen landing page: a coloured hero with the business name, tagline and a call-to-action button, a grid of three cards and a footer.

Learning goals

- Use header, main, section and footer landmarks
- Centre content with max-width and margin auto
- Create a responsive card grid with one line of CSS Grid

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, main, section, h2, ul, li, h3, strong, footer	background, color, padding, border-radius, display: grid, grid-template-columns, repeat(auto-fit, minmax()), gap, max-width

Build guide

1. Create index.html with the standard skeleton and link styles.css.
2. Add the <header class="hero"> with h1, tagline and a link styled as a button.
3. Add <main> with a <section> containing a <ul class="cards"> of three <li class="card"> items.
4. Add the footer with the copyright line.

5. In styles.css set the CSS variables in :root, style the hero, then the grid.
6. Resize the browser: the cards should go from three columns to one.

Project 9: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <h1>Horizon Photography</h1>
    <p class="tagline">Portraits, weddings and product photography</p>
    <a class="btn" href="#offers">See our sessions</a>
  </header>
  <main>
    <section id="offers">
      <h2>Popular sessions</h2>
      <ul class="cards">
    <li class="card"><h3>Portrait session</h3><p>One hour, 20 edited
photos</p><strong>1200 EGP</strong></li>
    <li class="card"><h3>Wedding day</h3><p>Full coverage, two
photographers</p><strong>15000 EGP</strong></li>
    <li class="card"><h3>Product shoot</h3><p>White background, 10
items</p><strong>900 EGP</strong></li>
      </ul>
    </section>
  </main>
  <footer>
    <p>&copy; 2026 Horizon Photography, Maadi</p>
  </footer>
</body>
</html>
```

Project 9: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(2rem, 5vw, 3rem); }
.tagline { font-size: 1.2rem; opacity: .9; }
.btn { display: inline-block; margin-top: 1rem; padding: .7rem 1.5rem;
 background: #fff; color: var(--brand); border-radius: 999px; text-
decoration: none; font-weight: bold; }
```

```
main { max-width: 60rem; margin: 0 auto; padding: 2rem 1rem; }
.cards { list-style: none; padding: 0; display: grid; gap: 1rem; grid-
template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
footer { text-align: center; padding: 1.5rem; color: var(--muted);
border-top: 1px solid var(--line); }
```

Project 9 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
Horizon Photography	The main heading; only one per page.
Portraits, weddings and product photography	A paragraph of text.
See our sessions	A link styled as a button; it navigates, so it is a link and not a <button>.
<main>	The unique content of this page; exactly one per page.
<section id="offers">	A thematic group of content, normally with its own heading.
Popular sessions	Second-level heading for a section.
<ul class="cards">	Unordered (bulleted) list.

Line	What it does
<li class="card"> Portrait session One hour, 20 edited ph...	Third-level heading, inside an h2 section.
<li class="card"> Wedding day Full coverage, two photogra...	One list item.
<li class="card"> Product shoot White background, 10 item...	Strong importance (bold by default).
<footer>	Footer of the page or of a section.
© 2026 Horizon Photography, Maadi	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
background: var(--brand);	Background colour or image.
text-align: center;	Centres inline content such as text.
padding: 4rem 1rem;	Space inside the element between its border and content.
font-size: clamp(2rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-size: 1.2rem;	Size of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
font-weight: bold;	Thickness of the text.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.

Declaration	What it does
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Check your work

- Exactly one h1
- Button link has descriptive text
- Cards wrap on narrow screens
- Footer text is readable (contrast)

Exercises

1. Add a fourth card and check the grid still works.
2. Change the hero to a background image with a dark overlay.
3. Add a <nav> with three links inside the header.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 10: Landing page for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 1 | Files: index.html, styles.css

Brief

Build a one-screen landing page: a coloured hero with the business name, tagline and a call-to-action button, a grid of three cards and a footer.

Learning goals

- Use header, main, section and footer landmarks
- Centre content with max-width and margin auto
- Create a responsive card grid with one line of CSS Grid

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, main, section, h2, ul, li, h3, strong, footer	background, color, padding, border-radius, display: grid, grid-template-columns, repeat(auto-fit, minmax()), gap, max-width

Build guide

1. Create index.html with the standard skeleton and link styles.css.
2. Add the <header class="hero"> with h1, tagline and a link styled as a button.
3. Add <main> with a <section> containing a <ul class="cards"> of three <li class="card"> items.
4. Add the footer with the copyright line.

5. In styles.css set the CSS variables in :root, style the hero, then the grid.
6. Resize the browser: the cards should go from three columns to one.

Project 10: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <h1>Papyrus Stationery</h1>
    <p class="tagline">Notebooks, pens and paper made in Egypt</p>
    <a class="btn" href="#offers">See our products</a>
  </header>
  <main>
    <section id="offers">
      <h2>Popular products</h2>
      <ul class="cards">
    <li class="card"><h3>Dotted notebook</h3><p>A5, 160 pages</
p><strong>140 EGP</strong></li>
    <li class="card"><h3>Fountain pen</h3><p>Steel nib, refillable</
p><strong>350 EGP</strong></li>
    <li class="card"><h3>Washi tape set</h3><p>Six patterns</
p><strong>90 EGP</strong></li>
      </ul>
    </section>
  </main>
  <footer>
    <p>&copy; 2026 Papyrus Stationery, Heliopolis</p>
  </footer>
</body>
</html>
```

Project 10: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(2rem, 5vw, 3rem); }
.tagline { font-size: 1.2rem; opacity: .9; }
.btn { display: inline-block; margin-top: 1rem; padding: .7rem 1.5rem;
 background: #fff; color: var(--brand); border-radius: 999px; text-
decoration: none; font-weight: bold; }
```

```
main { max-width: 60rem; margin: 0 auto; padding: 2rem 1rem; }
.cards { list-style: none; padding: 0; display: grid; gap: 1rem; grid-
template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
footer { text-align: center; padding: 1.5rem; color: var(--muted);
border-top: 1px solid var(--line); }
```

Project 10 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
Papyrus Stationery	The main heading; only one per page.
Notebooks, pens and paper made in Egypt	A paragraph of text.
See our products	A link styled as a button; it navigates, so it is a link and not a <button>.
<main>	The unique content of this page; exactly one per page.
<section id="offers">	A thematic group of content, normally with its own heading.
Popular products	Second-level heading for a section.

Line	What it does
<ul class="cards">	Unordered (bulleted) list.
<li class="card"> Dotted notebook A5, 160 pages <stron...	Third-level heading, inside an h2 section.
<li class="card"> Fountain pen Steel nib, refillable <...	One list item.
<li class="card"> Washi tape set Six patterns ...	Strong importance (bold by default).
<footer>	Footer of the page or of a section.
© 2026 Papyrus Stationery, Heliopolis	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
background: var(--brand);	Background colour or image.
text-align: center;	Centres inline content such as text.
padding: 4rem 1rem;	Space inside the element between its border and content.
font-size: clamp(2rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-size: 1.2rem;	Size of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
font-weight: bold;	Thickness of the text.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.

Declaration	What it does
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Check your work

- Exactly one h1
- Button link has descriptive text
- Cards wrap on narrow screens
- Footer text is readable (contrast)

Exercises

1. Add a fourth card and check the grid still works.
2. Change the hero to a background image with a dark overlay.
3. Add a <nav> with three links inside the header.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 11: Landing page for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 1 | Files: index.html, styles.css

Brief

Build a one-screen landing page: a coloured hero with the business name, tagline and a call-to-action button, a grid of three cards and a footer.

Learning goals

- Use header, main, section and footer landmarks
- Centre content with max-width and margin auto
- Create a responsive card grid with one line of CSS Grid

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, main, section, h2, ul, li, h3, strong, footer	background, color, padding, border-radius, display: grid, grid-template-columns, repeat(auto-fit, minmax()), gap, max-width

Build guide

1. Create index.html with the standard skeleton and link styles.css.
2. Add the <header class="hero"> with h1, tagline and a link styled as a button.
3. Add <main> with a <section> containing a <ul class="cards"> of three <li class="card"> items.
4. Add the footer with the copyright line.

5. In styles.css set the CSS variables in :root, style the hero, then the grid.
6. Resize the browser: the cards should go from three columns to one.

Project 11: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <h1>Oasis Plant Nursery</h1>
    <p class="tagline">Indoor plants and gardening advice</p>
    <a class="btn" href="#offers">See our plants</a>
  </header>
  <main>
    <section id="offers">
      <h2>Popular plants</h2>
      <ul class="cards">
    <li class="card"><h3>Monstera</h3><p>Large leaves, easy care</
p><strong>250 EGP</strong></li>
    <li class="card"><h3>Snake plant</h3><p>Survives anything</
p><strong>120 EGP</strong></li>
    <li class="card"><h3>Basil pot</h3><p>Kitchen herb</p><strong>45
EGP</strong></li>
      </ul>
    </section>
  </main>
  <footer>
    <p>&copy; 2026 Oasis Plant Nursery, Sheikh Zayed</p>
  </footer>
</body>
</html>
```

Project 11: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(2rem, 5vw, 3rem); }
.tagline { font-size: 1.2rem; opacity: .9; }
.btn { display: inline-block; margin-top: 1rem; padding: .7rem 1.5rem;
 background: #fff; color: var(--brand); border-radius: 999px; text-
decoration: none; font-weight: bold; }
```

```
main { max-width: 60rem; margin: 0 auto; padding: 2rem 1rem; }
.cards { list-style: none; padding: 0; display: grid; gap: 1rem; grid-
template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
footer { text-align: center; padding: 1.5rem; color: var(--muted);
border-top: 1px solid var(--line); }
```

Project 11 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
Oasis Plant Nursery	The main heading; only one per page.
Indoor plants and gardening advice	A paragraph of text.
See our plants	A link styled as a button; it navigates, so it is a link and not a <button>.
<main>	The unique content of this page; exactly one per page.
<section id="offers">	A thematic group of content, normally with its own heading.
Popular plants	Second-level heading for a section.
<ul class="cards">	Unordered (bulleted) list.

Line	What it does
<li class="card"> Monstera Large leaves, easy care <st...	Third-level heading, inside an h2 section.
<li class="card"> Snake plant Survives anything <stron...	One list item.
<li class="card"> Basil pot Kitchen herb 45 EG...	Strong importance (bold by default).
<footer>	Footer of the page or of a section.
© 2026 Oasis Plant Nursery, Sheikh Zayed	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-align: center;	Centres inline content such as text.
padding: 4rem 1rem;	Space inside the element between its border and content.
font-size: clamp(2rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-size: 1.2rem;	Size of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
font-weight: bold;	Thickness of the text.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Check your work

- Exactly one h1
- Button link has descriptive text
- Cards wrap on narrow screens
- Footer text is readable (contrast)

Exercises

1. Add a fourth card and check the grid still works.
2. Change the hero to a background image with a dark overlay.
3. Add a <nav> with three links inside the header.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 12: Landing page for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 1 | Files: index.html, styles.css

Brief

Build a one-screen landing page: a coloured hero with the business name, tagline and a call-to-action button, a grid of three cards and a footer.

Learning goals

- Use header, main, section and footer landmarks
- Centre content with max-width and margin auto
- Create a responsive card grid with one line of CSS Grid

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, main, section, h2, ul, li, h3, strong, footer	background, color, padding, border-radius, display: grid, grid-template-columns, repeat(auto-fit, minmax()), gap, max-width

Build guide

1. Create index.html with the standard skeleton and link styles.css.
2. Add the <header class="hero"> with h1, tagline and a link styled as a button.
3. Add <main> with a <section> containing a <ul class="cards"> of three <li class="card"> items.
4. Add the footer with the copyright line.

5. In styles.css set the CSS variables in :root, style the hero, then the grid.
6. Resize the browser: the cards should go from three columns to one.

Project 12: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <h1>Cedar Furniture</h1>
    <p class="tagline">Solid wood furniture made to order</p>
    <a class="btn" href="#offers">See our pieces</a>
  </header>
  <main>
    <section id="offers">
      <h2>Popular pieces</h2>
      <ul class="cards">
    <li class="card"><h3>Oak dining table</h3><p>Seats six</
p><strong>9500 EGP</strong></li>
    <li class="card"><h3>Bookshelf</h3><p>Five shelves, walnut</
p><strong>4200 EGP</strong></li>
    <li class="card"><h3>Bedside table</h3><p>One drawer</
p><strong>1500 EGP</strong></li>
      </ul>
    </section>
  </main>
  <footer>
    <p>&copy; 2026 Cedar Furniture, Damietta</p>
  </footer>
</body>
</html>
```

Project 12: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(2rem, 5vw, 3rem); }
.tagline { font-size: 1.2rem; opacity: .9; }
.btn { display: inline-block; margin-top: 1rem; padding: .7rem 1.5rem;
 background: #fff; color: var(--brand); border-radius: 999px; text-
decoration: none; font-weight: bold; }
```

```
main { max-width: 60rem; margin: 0 auto; padding: 2rem 1rem; }
.cards { list-style: none; padding: 0; display: grid; gap: 1rem; grid-
template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
footer { text-align: center; padding: 1.5rem; color: var(--muted);
border-top: 1px solid var(--line); }
```

Project 12 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
Cedar Furniture	The main heading; only one per page.
Solid wood furniture made to order	A paragraph of text.
See our pieces	A link styled as a button; it navigates, so it is a link and not a <button>.
<main>	The unique content of this page; exactly one per page.
<section id="offers">	A thematic group of content, normally with its own heading.
Popular pieces	Second-level heading for a section.
<ul class="cards">	Unordered (bulleted) list.

Line	What it does
<li class="card"> Oak dining table Seats six 9...	Third-level heading, inside an h2 section.
<li class="card"> Bookshelf Five shelves, walnut <stro...	One list item.
<li class="card"> Bedside table One drawer 150...	Strong importance (bold by default).
<footer>	Footer of the page or of a section.
© 2026 Cedar Furniture, Damietta	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.

Declaration	What it does
color: var(--ink);	Text colour.
background: var(--brand);	Background colour or image.
text-align: center;	Centres inline content such as text.
padding: 4rem 1rem;	Space inside the element between its border and content.
font-size: clamp(2rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-size: 1.2rem;	Size of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
font-weight: bold;	Thickness of the text.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Check your work

- Exactly one h1
- Button link has descriptive text
- Cards wrap on narrow screens
- Footer text is readable (contrast)

Exercises

1. Add a fourth card and check the grid still works.
2. Change the hero to a background image with a dark overlay.
3. Add a <nav> with three links inside the header.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 13: Landing page for Byte Repair

Theme: Byte Repair (Nasr City) | Level 1 | Files: index.html, styles.css

Brief

Build a one-screen landing page: a coloured hero with the business name, tagline and a call-to-action button, a grid of three cards and a footer.

Learning goals

- Use header, main, section and footer landmarks
- Centre content with max-width and margin auto
- Create a responsive card grid with one line of CSS Grid

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, main, section, h2, ul, li, h3, strong, footer	background, color, padding, border-radius, display: grid, grid-template-columns, repeat(auto-fit, minmax()), gap, max-width

Build guide

1. Create index.html with the standard skeleton and link styles.css.
2. Add the <header class="hero"> with h1, tagline and a link styled as a button.
3. Add <main> with a <section> containing a <ul class="cards"> of three <li class="card"> items.
4. Add the footer with the copyright line.

5. In styles.css set the CSS variables in :root, style the hero, then the grid.
6. Resize the browser: the cards should go from three columns to one.

Project 13: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <h1>Byte Repair</h1>
    <p class="tagline">Phone and laptop repairs while you wait</p>
    <a class="btn" href="#offers">See our repairs</a>
  </header>
  <main>
    <section id="offers">
      <h2>Popular repairs</h2>
      <ul class="cards">
    <li class="card"><h3>Screen replacement</h3><p>Most phones, 1
hour</p><strong>From 800 EGP</strong></li>
    <li class="card"><h3>Battery swap</h3><p>Original cells</
p><strong>From 500 EGP</strong></li>
    <li class="card"><h3>Laptop cleaning</h3><p>Fans and thermal
paste</p><strong>350 EGP</strong></li>
      </ul>
    </section>
  </main>
  <footer>
    <p>&copy; 2026 Byte Repair, Nasr City</p>
  </footer>
</body>
</html>
```

Project 13: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(2rem, 5vw, 3rem); }
.tagline { font-size: 1.2rem; opacity: .9; }
.btn { display: inline-block; margin-top: 1rem; padding: .7rem 1.5rem;
 background: #fff; color: var(--brand); border-radius: 999px; text-
decoration: none; font-weight: bold; }
```

```
main { max-width: 60rem; margin: 0 auto; padding: 2rem 1rem; }
.cards { list-style: none; padding: 0; display: grid; gap: 1rem; grid-
template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
footer { text-align: center; padding: 1.5rem; color: var(--muted);
border-top: 1px solid var(--line); }
```

Project 13 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
Byte Repair	The main heading; only one per page.
Phone and laptop repairs while you wait	A paragraph of text.
See our repairs	A link styled as a button; it navigates, so it is a link and not a <button>.
<main>	The unique content of this page; exactly one per page.
<section id="offers">	A thematic group of content, normally with its own heading.
Popular repairs	Second-level heading for a section.
<ul class="cards">	Unordered (bulleted) list.

Line	What it does
<li class="card"> Screen replacement Most phones, 1 hour<...	Third-level heading, inside an h2 section.
<li class="card"> Battery swap Original cells ...	One list item.
<li class="card"> Laptop cleaning Fans and thermal paste<...	Strong importance (bold by default).
<footer>	Footer of the page or of a section.
© 2026 Byte Repair, Nasr City	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.

Declaration	What it does
color: var(--ink);	Text colour.
background: var(--brand);	Background colour or image.
text-align: center;	Centres inline content such as text.
padding: 4rem 1rem;	Space inside the element between its border and content.
font-size: clamp(2rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-size: 1.2rem;	Size of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
font-weight: bold;	Thickness of the text.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Check your work

- Exactly one h1
- Button link has descriptive text
- Cards wrap on narrow screens
- Footer text is readable (contrast)

Exercises

1. Add a fourth card and check the grid still works.
2. Change the hero to a background image with a dark overlay.
3. Add a <nav> with three links inside the header.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 14: Landing page for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 1 | Files: index.html, styles.css

Brief

Build a one-screen landing page: a coloured hero with the business name, tagline and a call-to-action button, a grid of three cards and a footer.

Learning goals

- Use header, main, section and footer landmarks
- Centre content with max-width and margin auto
- Create a responsive card grid with one line of CSS Grid

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, main, section, h2, ul, li, h3, strong, footer	background, color, padding, border-radius, display: grid, grid-template-columns, repeat(auto-fit, minmax()), gap, max-width

Build guide

1. Create index.html with the standard skeleton and link styles.css.
2. Add the <header class="hero"> with h1, tagline and a link styled as a button.
3. Add <main> with a <section> containing a <ul class="cards"> of three <li class="card"> items.
4. Add the footer with the copyright line.

5. In styles.css set the CSS variables in :root, style the hero, then the grid.
6. Resize the browser: the cards should go from three columns to one.

Project 14: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <h1>Sahara Pet Care</h1>
    <p class="tagline">Grooming, boarding and vet visits</p>
    <a class="btn" href="#offers">See our services</a>
  </header>
  <main>
    <section id="offers">
      <h2>Popular services</h2>
      <ul class="cards">
    <li class="card"><h3>Full grooming</h3><p>Bath, cut and nails</
p><strong>400 EGP</strong></li>
    <li class="card"><h3>Day boarding</h3><p>Play and rest</
p><strong>250 EGP</strong></li>
    <li class="card"><h3>Vaccination</h3><p>Annual boosters</
p><strong>300 EGP</strong></li>
      </ul>
    </section>
  </main>
  <footer>
    <p>&copy; 2026 Sahara Pet Care, New Cairo</p>
  </footer>
</body>
</html>
```

Project 14: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(2rem, 5vw, 3rem); }
.tagline { font-size: 1.2rem; opacity: .9; }
.btn { display: inline-block; margin-top: 1rem; padding: .7rem 1.5rem;
 background: #fff; color: var(--brand); border-radius: 999px; text-
decoration: none; font-weight: bold; }
```

```
main { max-width: 60rem; margin: 0 auto; padding: 2rem 1rem; }
.cards { list-style: none; padding: 0; display: grid; gap: 1rem; grid-
template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
footer { text-align: center; padding: 1.5rem; color: var(--muted);
border-top: 1px solid var(--line); }
```

Project 14 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
Sahara Pet Care	The main heading; only one per page.
Grooming, boarding and vet visits	A paragraph of text.
See our services	A link styled as a button; it navigates, so it is a link and not a <button>.
<main>	The unique content of this page; exactly one per page.
<section id="offers">	A thematic group of content, normally with its own heading.
Popular services	Second-level heading for a section.
<ul class="cards">	Unordered (bulleted) list.

Line	What it does
<li class="card"> Full grooming Bath, cut and nails <s...	Third-level heading, inside an h2 section.
<li class="card"> Day boarding Play and rest 2...	One list item.
<li class="card"> Vaccination Annual boosters ...	Strong importance (bold by default).
<footer>	Footer of the page or of a section.
© 2026 Sahara Pet Care, New Cairo	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-align: center;	Centres inline content such as text.
padding: 4rem 1rem;	Space inside the element between its border and content.
font-size: clamp(2rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-size: 1.2rem;	Size of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
font-weight: bold;	Thickness of the text.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Check your work

- Exactly one h1
- Button link has descriptive text
- Cards wrap on narrow screens
- Footer text is readable (contrast)

Exercises

1. Add a fourth card and check the grid still works.
2. Change the hero to a background image with a dark overlay.
3. Add a <nav> with three links inside the header.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 15: Landing page for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Build a one-screen landing page: a coloured hero with the business name, tagline and a call-to-action button, a grid of three cards and a footer.

Learning goals

- Use header, main, section and footer landmarks
- Centre content with max-width and margin auto
- Create a responsive card grid with one line of CSS Grid

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, main, section, h2, ul, li, h3, strong, footer	background, color, padding, border-radius, display: grid, grid-template-columns, repeat(auto-fit, minmax()), gap, max-width

Build guide

1. Create index.html with the standard skeleton and link styles.css.
2. Add the <header class="hero"> with h1, tagline and a link styled as a button.
3. Add <main> with a <section> containing a <ul class="cards"> of three <li class="card"> items.
4. Add the footer with the copyright line.

5. In styles.css set the CSS variables in :root, style the hero, then the grid.
6. Resize the browser: the cards should go from three columns to one.

Project 15: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <h1>Alexandria Sailing School</h1>
    <p class="tagline">Learn to sail on the Mediterranean</p>
    <a class="btn" href="#offers">See our lessons</a>
  </header>
  <main>
    <section id="offers">
      <h2>Popular lessons</h2>
      <ul class="cards">
    <li class="card"><h3>Taster session</h3><p>Two hours on the
water</p><strong>500 EGP</strong></li>
    <li class="card"><h3>Beginner course</h3><p>Five sessions</
p><strong>2200 EGP</strong></li>
    <li class="card"><h3>Racing clinic</h3><p>Tactics and trim</
p><strong>1800 EGP</strong></li>
      </ul>
    </section>
  </main>
  <footer>
    <p>&copy; 2026 Alexandria Sailing School, Alexandria</p>
  </footer>
</body>
</html>
```

Project 15: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(2rem, 5vw, 3rem); }
.tagline { font-size: 1.2rem; opacity: .9; }
.btn { display: inline-block; margin-top: 1rem; padding: .7rem 1.5rem;
 background: #fff; color: var(--brand); border-radius: 999px; text-
decoration: none; font-weight: bold; }
```

```
main { max-width: 60rem; margin: 0 auto; padding: 2rem 1rem; }
.cards { list-style: none; padding: 0; display: grid; gap: 1rem; grid-
template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
footer { text-align: center; padding: 1.5rem; color: var(--muted);
border-top: 1px solid var(--line); }
```

Project 15 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
Alexandria Sailing School	The main heading; only one per page.
Learn to sail on the Mediterranean	A paragraph of text.
See our lessons	A link styled as a button; it navigates, so it is a link and not a <button>.
<main>	The unique content of this page; exactly one per page.
<section id="offers">	A thematic group of content, normally with its own heading.
Popular lessons	Second-level heading for a section.
<ul class="cards">	Unordered (bulleted) list.

Line	What it does
<li class="card"> Taster session Two hours on the water<//...	Third-level heading, inside an h2 section.
<li class="card"> Beginner course Five sessions <stron...	One list item.
<li class="card"> Racing clinic Tactics and trim <stro...	Strong importance (bold by default).
<footer>	Footer of the page or of a section.
© 2026 Alexandria Sailing School, Alexandria	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.

Declaration	What it does
color: var(--ink);	Text colour.
background: var(--brand);	Background colour or image.
text-align: center;	Centres inline content such as text.
padding: 4rem 1rem;	Space inside the element between its border and content.
font-size: clamp(2rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-size: 1.2rem;	Size of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
font-weight: bold;	Thickness of the text.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Check your work

- Exactly one h1
- Button link has descriptive text
- Cards wrap on narrow screens
- Footer text is readable (contrast)

Exercises

1. Add a fourth card and check the grid still works.
2. Change the hero to a background image with a dark overlay.
3. Add a <nav> with three links inside the header.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 16: Landing page for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Build a one-screen landing page: a coloured hero with the business name, tagline and a call-to-action button, a grid of three cards and a footer.

Learning goals

- Use header, main, section and footer landmarks
- Centre content with max-width and margin auto
- Create a responsive card grid with one line of CSS Grid

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, main, section, h2, ul, li, h3, strong, footer	background, color, padding, border-radius, display: grid, grid-template-columns, repeat(auto-fit, minmax()), gap, max-width

Build guide

1. Create index.html with the standard skeleton and link styles.css.
2. Add the <header class="hero"> with h1, tagline and a link styled as a button.
3. Add <main> with a <section> containing a <ul class="cards"> of three <li class="card"> items.
4. Add the footer with the copyright line.

5. In styles.css set the CSS variables in :root, style the hero, then the grid.
6. Resize the browser: the cards should go from three columns to one.

Project 16: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <h1>Habiba Handmade Jewellery</h1>
    <p class="tagline">Silver and brass pieces inspired by Nubia</p>
    <a class="btn" href="#offers">See our items</a>
  </header>
  <main>
    <section id="offers">
      <h2>Popular items</h2>
      <ul class="cards">
    <li class="card"><h3>Lotus pendant</h3><p>Sterling silver</
p><strong>650 EGP</strong></li>
    <li class="card"><h3>Brass cuff</h3><p>Hand engraved</
p><strong>420 EGP</strong></li>
    <li class="card"><h3>Bead earrings</h3><p>Recycled glass</
p><strong>180 EGP</strong></li>
      </ul>
    </section>
  </main>
  <footer>
    <p>&copy; 2026 Habiba Handmade Jewellery, Aswan</p>
  </footer>
</body>
</html>
```

Project 16: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(2rem, 5vw, 3rem); }
.tagline { font-size: 1.2rem; opacity: .9; }
.btn { display: inline-block; margin-top: 1rem; padding: .7rem 1.5rem;
 background: #fff; color: var(--brand); border-radius: 999px; text-
decoration: none; font-weight: bold; }
```

```
main { max-width: 60rem; margin: 0 auto; padding: 2rem 1rem; }
.cards { list-style: none; padding: 0; display: grid; gap: 1rem; grid-
template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
footer { text-align: center; padding: 1.5rem; color: var(--muted);
border-top: 1px solid var(--line); }
```

Project 16 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
Habiba Handmade Jewellery	The main heading; only one per page.
Silver and brass pieces inspired by Nubia	A paragraph of text.
See our items	A link styled as a button; it navigates, so it is a link and not a <button>.
<main>	The unique content of this page; exactly one per page.
<section id="offers">	A thematic group of content, normally with its own heading.
Popular items	Second-level heading for a section.
<ul class="cards">	Unordered (bulleted) list.

Line	What it does
<li class="card"> Lotus pendant Sterling silver <stron...	Third-level heading, inside an h2 section.
<li class="card"> Brass cuff Hand engraved 420...	One list item.
<li class="card"> Bead earrings Recycled glass <strong...	Strong importance (bold by default).
<footer>	Footer of the page or of a section.
© 2026 Habiba Handmade Jewellery, Aswan	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.

Declaration	What it does
color: var(--ink);	Text colour.
background: var(--brand);	Background colour or image.
text-align: center;	Centres inline content such as text.
padding: 4rem 1rem;	Space inside the element between its border and content.
font-size: clamp(2rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-size: 1.2rem;	Size of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
font-weight: bold;	Thickness of the text.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Check your work

- Exactly one h1
- Button link has descriptive text
- Cards wrap on narrow screens
- Footer text is readable (contrast)

Exercises

1. Add a fourth card and check the grid still works.
2. Change the hero to a background image with a dark overlay.
3. Add a <nav> with three links inside the header.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 17: Landing page for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 1 | Files: index.html, styles.css

Brief

Build a one-screen landing page: a coloured hero with the business name, tagline and a call-to-action button, a grid of three cards and a footer.

Learning goals

- Use header, main, section and footer landmarks
- Centre content with max-width and margin auto
- Create a responsive card grid with one line of CSS Grid

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, main, section, h2, ul, li, h3, strong, footer	background, color, padding, border-radius, display: grid, grid-template-columns, repeat(auto-fit, minmax()), gap, max-width

Build guide

1. Create index.html with the standard skeleton and link styles.css.
2. Add the <header class="hero"> with h1, tagline and a link styled as a button.
3. Add <main> with a <section> containing a <ul class="cards"> of three <li class="card"> items.
4. Add the footer with the copyright line.

5. In styles.css set the CSS variables in :root, style the hero, then the grid.
6. Resize the browser: the cards should go from three columns to one.

Project 17: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <h1>Fayoum Pottery Studio</h1>
    <p class="tagline">Wheel throwing and glazing classes</p>
    <a class="btn" href="#offers">See our workshops</a>
  </header>
  <main>
    <section id="offers">
      <h2>Popular workshops</h2>
      <ul class="cards">
    <li class="card"><h3>Intro to the wheel</h3><p>Three hours, take
home a bowl</p><strong>450 EGP</strong></li>
    <li class="card"><h3>Glazing day</h3><p>Colour your pieces</
p><strong>300 EGP</strong></li>
    <li class="card"><h3>Kids clay class</h3><p>Ages 6 to 12</
p><strong>200 EGP</strong></li>
      </ul>
    </section>
  </main>
  <footer>
    <p>&copy; 2026 Fayoum Pottery Studio, Tunis Village</p>
  </footer>
</body>
</html>
```

Project 17: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(2rem, 5vw, 3rem); }
.tagline { font-size: 1.2rem; opacity: .9; }
.btn { display: inline-block; margin-top: 1rem; padding: .7rem 1.5rem;
 background: #fff; color: var(--brand); border-radius: 999px; text-
decoration: none; font-weight: bold; }
```

```
main { max-width: 60rem; margin: 0 auto; padding: 2rem 1rem; }
.cards { list-style: none; padding: 0; display: grid; gap: 1rem; grid-
template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
footer { text-align: center; padding: 1.5rem; color: var(--muted);
border-top: 1px solid var(--line); }
```

Project 17 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
Fayoum Pottery Studio	The main heading; only one per page.
Wheel throwing and glazing classes	A paragraph of text.
See our workshops	A link styled as a button; it navigates, so it is a link and not a <button>.
<main>	The unique content of this page; exactly one per page.
<section id="offers">	A thematic group of content, normally with its own heading.
Popular workshops	Second-level heading for a section.

Line	What it does
<ul class="cards">	Unordered (bulleted) list.
<li class="card"> Intro to the wheel Three hours, take ho...	Third-level heading, inside an h2 section.
<li class="card"> Glazing day Colour your pieces <stro...	One list item.
<li class="card"> Kids clay class Ages 6 to 12 <strong...	Strong importance (bold by default).
<footer>	Footer of the page or of a section.
© 2026 Fayoum Pottery Studio, Tunis Village	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
background: var(--brand);	Background colour or image.
text-align: center;	Centres inline content such as text.
padding: 4rem 1rem;	Space inside the element between its border and content.
font-size: clamp(2rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-size: 1.2rem;	Size of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
font-weight: bold;	Thickness of the text.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.

Declaration	What it does
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Check your work

- Exactly one h1
- Button link has descriptive text
- Cards wrap on narrow screens
- Footer text is readable (contrast)

Exercises

1. Add a fourth card and check the grid still works.
2. Change the hero to a background image with a dark overlay.
3. Add a <nav> with three links inside the header.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 18: Landing page for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 1 | Files: index.html, styles.css

Brief

Build a one-screen landing page: a coloured hero with the business name, tagline and a call-to-action button, a grid of three cards and a footer.

Learning goals

- Use header, main, section and footer landmarks
- Centre content with max-width and margin auto
- Create a responsive card grid with one line of CSS Grid

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, main, section, h2, ul, li, h3, strong, footer	background, color, padding, border-radius, display: grid, grid-template-columns, repeat(auto-fit, minmax()), gap, max-width

Build guide

1. Create index.html with the standard skeleton and link styles.css.
2. Add the <header class="hero"> with h1, tagline and a link styled as a button.
3. Add <main> with a <section> containing a <ul class="cards"> of three <li class="card"> items.
4. Add the footer with the copyright line.

5. In styles.css set the CSS variables in :root, style the hero, then the grid.
6. Resize the browser: the cards should go from three columns to one.

Project 18: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <h1>Cleopatra Beauty Salon</h1>
    <p class="tagline">Hair, nails and skin care</p>
    <a class="btn" href="#offers">See our treatments</a>
  </header>
  <main>
    <section id="offers">
      <h2>Popular treatments</h2>
      <ul class="cards">
    <li class="card"><h3>Haircut and blow-dry</h3><p>Consultation
included</p><strong>350 EGP</strong></li>
    <li class="card"><h3>Manicure</h3><p>Classic or gel</
p><strong>200 EGP</strong></li>
    <li class="card"><h3>Facial</h3><p>Deep cleanse, 60 minutes</
p><strong>600 EGP</strong></li>
      </ul>
    </section>
  </main>
  <footer>
    <p>&copy; 2026 Cleopatra Beauty Salon, Dokki</p>
  </footer>
</body>
</html>
```

Project 18: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(2rem, 5vw, 3rem); }
.tagline { font-size: 1.2rem; opacity: .9; }
.btn { display: inline-block; margin-top: 1rem; padding: .7rem 1.5rem;
 background: #fff; color: var(--brand); border-radius: 999px; text-
decoration: none; font-weight: bold; }
```

```
main { max-width: 60rem; margin: 0 auto; padding: 2rem 1rem; }
.cards { list-style: none; padding: 0; display: grid; gap: 1rem; grid-
template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
footer { text-align: center; padding: 1.5rem; color: var(--muted);
border-top: 1px solid var(--line); }
```

Project 18 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
Cleopatra Beauty Salon	The main heading; only one per page.
Hair, nails and skin care	A paragraph of text.
See our treatments	A link styled as a button; it navigates, so it is a link and not a <button>.
<main>	The unique content of this page; exactly one per page.
<section id="offers">	A thematic group of content, normally with its own heading.
Popular treatments	Second-level heading for a section.
<ul class="cards">	Unordered (bulleted) list.

Line	What it does
<li class="card"> Haircut and blow-dry Consultation inclu...	Third-level heading, inside an h2 section.
<li class="card"> Manicure Classic or gel 200 ...	One list item.
<li class="card"> Facial Deep cleanse, 60 minutes <str...	Strong importance (bold by default).
<footer>	Footer of the page or of a section.
© 2026 Cleopatra Beauty Salon, Dokki	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-align: center;	Centres inline content such as text.
padding: 4rem 1rem;	Space inside the element between its border and content.
font-size: clamp(2rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-size: 1.2rem;	Size of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
font-weight: bold;	Thickness of the text.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Check your work

- Exactly one h1
- Button link has descriptive text
- Cards wrap on narrow screens
- Footer text is readable (contrast)

Exercises

1. Add a fourth card and check the grid still works.
2. Change the hero to a background image with a dark overlay.
3. Add a <nav> with three links inside the header.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 19: Landing page for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 1 | Files: index.html, styles.css

Brief

Build a one-screen landing page: a coloured hero with the business name, tagline and a call-to-action button, a grid of three cards and a footer.

Learning goals

- Use header, main, section and footer landmarks
- Centre content with max-width and margin auto
- Create a responsive card grid with one line of CSS Grid

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, main, section, h2, ul, li, h3, strong, footer	background, color, padding, border-radius, display: grid, grid-template-columns, repeat(auto-fit, minmax()), gap, max-width

Build guide

1. Create index.html with the standard skeleton and link styles.css.
2. Add the <header class="hero"> with h1, tagline and a link styled as a button.
3. Add <main> with a <section> containing a <ul class="cards"> of three <li class="card"> items.
4. Add the footer with the copyright line.

5. In styles.css set the CSS variables in :root, style the hero, then the grid.
6. Resize the browser: the cards should go from three columns to one.

Project 19: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <h1>Suez Auto Service</h1>
    <p class="tagline">Honest car servicing and repairs</p>
    <a class="btn" href="#offers">See our services</a>
  </header>
  <main>
    <section id="offers">
      <h2>Popular services</h2>
      <ul class="cards">
    <li class="card"><h3>Oil change</h3><p>Filter included</
p><strong>600 EGP</strong></li>
    <li class="card"><h3>Brake pads</h3><p>Front axle</p><strong>1400
EGP</strong></li>
    <li class="card"><h3>Air conditioning</h3><p>Recharge and check</
p><strong>900 EGP</strong></li>
      </ul>
    </section>
  </main>
  <footer>
    <p>&copy; 2026 Suez Auto Service, Suez</p>
  </footer>
</body>
</html>
```

Project 19: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(2rem, 5vw, 3rem); }
.tagline { font-size: 1.2rem; opacity: .9; }
.btn { display: inline-block; margin-top: 1rem; padding: .7rem 1.5rem;
 background: #fff; color: var(--brand); border-radius: 999px; text-
decoration: none; font-weight: bold; }
```

```
main { max-width: 60rem; margin: 0 auto; padding: 2rem 1rem; }
.cards { list-style: none; padding: 0; display: grid; gap: 1rem; grid-
template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
footer { text-align: center; padding: 1.5rem; color: var(--muted);
border-top: 1px solid var(--line); }
```

Project 19 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
Suez Auto Service	The main heading; only one per page.
Honest car servicing and repairs	A paragraph of text.
See our services	A link styled as a button; it navigates, so it is a link and not a <button>.
<main>	The unique content of this page; exactly one per page.
<section id="offers">	A thematic group of content, normally with its own heading.
Popular services	Second-level heading for a section.
<ul class="cards">	Unordered (bulleted) list.

Line	What it does
<li class="card"> Oil change Filter included 6...	Third-level heading, inside an h2 section.
<li class="card"> Brake pads Front axle 1400 E...	One list item.
<li class="card"> Air conditioning Recharge and check ...	Strong importance (bold by default).
<footer>	Footer of the page or of a section.
© 2026 Suez Auto Service, Suez	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-align: center;	Centres inline content such as text.
padding: 4rem 1rem;	Space inside the element between its border and content.
font-size: clamp(2rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-size: 1.2rem;	Size of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
font-weight: bold;	Thickness of the text.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Check your work

- Exactly one h1
- Button link has descriptive text
- Cards wrap on narrow screens
- Footer text is readable (contrast)

Exercises

1. Add a fourth card and check the grid still works.
2. Change the hero to a background image with a dark overlay.
3. Add a <nav> with three links inside the header.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 20: Landing page for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 1 | Files: index.html, styles.css

Brief

Build a one-screen landing page: a coloured hero with the business name, tagline and a call-to-action button, a grid of three cards and a footer.

Learning goals

- Use header, main, section and footer landmarks
- Centre content with max-width and margin auto
- Create a responsive card grid with one line of CSS Grid

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, main, section, h2, ul, li, h3, strong, footer	background, color, padding, border-radius, display: grid, grid-template-columns, repeat(auto-fit, minmax()), gap, max-width

Build guide

1. Create index.html with the standard skeleton and link styles.css.
2. Add the <header class="hero"> with h1, tagline and a link styled as a button.
3. Add <main> with a <section> containing a <ul class="cards"> of three <li class="card"> items.
4. Add the footer with the copyright line.

5. In styles.css set the CSS variables in :root, style the hero, then the grid.
6. Resize the browser: the cards should go from three columns to one.

Project 20: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <h1>Luxor Music Academy</h1>
    <p class="tagline">Oud, piano, guitar and voice lessons</p>
    <a class="btn" href="#offers">See our courses</a>
  </header>
  <main>
    <section id="offers">
      <h2>Popular courses</h2>
      <ul class="cards">
    <li class="card"><h3>Oud for beginners</h3><p>Eight weekly
lessons</p><strong>1600 EGP</strong></li>
    <li class="card"><h3>Piano grade 1</h3><p>Theory and practice</
p><strong>1800 EGP</strong></li>
    <li class="card"><h3>Guitar chords</h3><p>Play songs in a month</
p><strong>1400 EGP</strong></li>
      </ul>
    </section>
  </main>
  <footer>
    <p>&copy; 2026 Luxor Music Academy, Luxor</p>
  </footer>
</body>
</html>
```

Project 20: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(2rem, 5vw, 3rem); }
.tagline { font-size: 1.2rem; opacity: .9; }
.btn { display: inline-block; margin-top: 1rem; padding: .7rem 1.5rem;
 background: #fff; color: var(--brand); border-radius: 999px; text-
decoration: none; font-weight: bold; }
```

```
main { max-width: 60rem; margin: 0 auto; padding: 2rem 1rem; }
.cards { list-style: none; padding: 0; display: grid; gap: 1rem; grid-
template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
footer { text-align: center; padding: 1.5rem; color: var(--muted);
border-top: 1px solid var(--line); }
```

Project 20 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
Luxor Music Academy	The main heading; only one per page.
Oud, piano, guitar and voice lessons	A paragraph of text.
See our courses	A link styled as a button; it navigates, so it is a link and not a <button>.
<main>	The unique content of this page; exactly one per page.
<section id="offers">	A thematic group of content, normally with its own heading.
Popular courses	Second-level heading for a section.
<ul class="cards">	Unordered (bulleted) list.

Line	What it does
<li class="card"> Oud for beginners Eight weekly lessons<...	Third-level heading, inside an h2 section.
<li class="card"> Piano grade 1 Theory and practice <s...	One list item.
<li class="card"> Guitar chords Play songs in a month ...	Strong importance (bold by default).
<footer>	Footer of the page or of a section.
© 2026 Luxor Music Academy, Luxor	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-align: center;	Centres inline content such as text.
padding: 4rem 1rem;	Space inside the element between its border and content.
font-size: clamp(2rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-size: 1.2rem;	Size of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
font-weight: bold;	Thickness of the text.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Check your work

- Exactly one h1
- Button link has descriptive text
- Cards wrap on narrow screens
- Footer text is readable (contrast)

Exercises

1. Add a fourth card and check the grid still works.
2. Change the hero to a background image with a dark overlay.
3. Add a <nav> with three links inside the header.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 21: Landing page for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 1 | Files: index.html, styles.css

Brief

Build a one-screen landing page: a coloured hero with the business name, tagline and a call-to-action button, a grid of three cards and a footer.

Learning goals

- Use header, main, section and footer landmarks
- Centre content with max-width and margin auto
- Create a responsive card grid with one line of CSS Grid

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, main, section, h2, ul, li, h3, strong, footer	background, color, padding, border-radius, display: grid, grid-template-columns, repeat(auto-fit, minmax()), gap, max-width

Build guide

1. Create index.html with the standard skeleton and link styles.css.
2. Add the <header class="hero"> with h1, tagline and a link styled as a button.
3. Add <main> with a <section> containing a <ul class="cards"> of three <li class="card"> items.
4. Add the footer with the copyright line.

5. In styles.css set the CSS variables in :root, style the hero, then the grid.
6. Resize the browser: the cards should go from three columns to one.

Project 21: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <h1>Port Said Seafood</h1>
    <p class="tagline">Grilled fish straight from the boats</p>
    <a class="btn" href="#offers">See our dishes</a>
  </header>
  <main>
    <section id="offers">
      <h2>Popular dishes</h2>
      <ul class="cards">
    <li class="card"><h3>Grilled sea bass</h3><p>With rice and salad</
p><strong>320 EGP</strong></li>
    <li class="card"><h3>Shrimp tagine</h3><p>Tomato and garlic</
p><strong>280 EGP</strong></li>
    <li class="card"><h3>Calamari</h3><p>Fried, with tahini</
p><strong>190 EGP</strong></li>
      </ul>
    </section>
  </main>
  <footer>
    <p>&copy; 2026 Port Said Seafood, Port Said</p>
  </footer>
</body>
</html>
```

Project 21: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(2rem, 5vw, 3rem); }
.tagline { font-size: 1.2rem; opacity: .9; }
.btn { display: inline-block; margin-top: 1rem; padding: .7rem 1.5rem;
 background: #fff; color: var(--brand); border-radius: 999px; text-
decoration: none; font-weight: bold; }
```

```
main { max-width: 60rem; margin: 0 auto; padding: 2rem 1rem; }
.cards { list-style: none; padding: 0; display: grid; gap: 1rem; grid-
template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
footer { text-align: center; padding: 1.5rem; color: var(--muted);
border-top: 1px solid var(--line); }
```

Project 21 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
Port Said Seafood	The main heading; only one per page.
Grilled fish straight from the boats	A paragraph of text.
See our dishes	A link styled as a button; it navigates, so it is a link and not a <button>.
<main>	The unique content of this page; exactly one per page.
<section id="offers">	A thematic group of content, normally with its own heading.
Popular dishes	Second-level heading for a section.
<ul class="cards">	Unordered (bulleted) list.

Line	What it does
<li class="card"> Grilled sea bass With rice and salad</p...	Third-level heading, inside an h2 section.
<li class="card"> Shrimp tagine Tomato and garlic <str...	One list item.
<li class="card"> Calamari Fried, with tahini ...	Strong importance (bold by default).
<footer>	Footer of the page or of a section.
© 2026 Port Said Seafood, Port Said	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-align: center;	Centres inline content such as text.
padding: 4rem 1rem;	Space inside the element between its border and content.
font-size: clamp(2rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-size: 1.2rem;	Size of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
font-weight: bold;	Thickness of the text.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Check your work

- Exactly one h1
- Button link has descriptive text
- Cards wrap on narrow screens
- Footer text is readable (contrast)

Exercises

1. Add a fourth card and check the grid still works.
2. Change the hero to a background image with a dark overlay.
3. Add a <nav> with three links inside the header.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 22: Landing page for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 1 | Files: index.html, styles.css

Brief

Build a one-screen landing page: a coloured hero with the business name, tagline and a call-to-action button, a grid of three cards and a footer.

Learning goals

- Use header, main, section and footer landmarks
- Centre content with max-width and margin auto
- Create a responsive card grid with one line of CSS Grid

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, main, section, h2, ul, li, h3, strong, footer	background, color, padding, border-radius, display: grid, grid-template-columns, repeat(auto-fit, minmax()), gap, max-width

Build guide

1. Create index.html with the standard skeleton and link styles.css.
2. Add the <header class="hero"> with h1, tagline and a link styled as a button.
3. Add <main> with a <section> containing a <ul class="cards"> of three <li class="card"> items.
4. Add the footer with the copyright line.

5. In styles.css set the CSS variables in :root, style the hero, then the grid.
6. Resize the browser: the cards should go from three columns to one.

Project 22: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <h1>Delta Kids Library</h1>
    <p class="tagline">Stories, reading clubs and homework help</p>
    <a class="btn" href="#offers">See our programmes</a>
  </header>
  <main>
    <section id="offers">
      <h2>Popular programmes</h2>
      <ul class="cards">
    <li class="card"><h3>Story hour</h3><p>Ages 3 to 6, Saturdays</
p><strong>Free</strong></li>
    <li class="card"><h3>Reading club</h3><p>Ages 7 to 11</
p><strong>50 EGP per month</strong></li>
    <li class="card"><h3>Homework help</h3><p>Weekday afternoons</
p><strong>Free</strong></li>
      </ul>
    </section>
  </main>
  <footer>
    <p>&copy; 2026 Delta Kids Library, Tanta</p>
  </footer>
</body>
</html>
```

Project 22: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(2rem, 5vw, 3rem); }
.tagline { font-size: 1.2rem; opacity: .9; }
.btn { display: inline-block; margin-top: 1rem; padding: .7rem 1.5rem;
 background: #fff; color: var(--brand); border-radius: 999px; text-
decoration: none; font-weight: bold; }
```

```
main { max-width: 60rem; margin: 0 auto; padding: 2rem 1rem; }
.cards { list-style: none; padding: 0; display: grid; gap: 1rem; grid-
template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
footer { text-align: center; padding: 1.5rem; color: var(--muted);
border-top: 1px solid var(--line); }
```

Project 22 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
Delta Kids Library	The main heading; only one per page.
Stories, reading clubs and homework help	A paragraph of text.
See our programmes	A link styled as a button; it navigates, so it is a link and not a <button>.
<main>	The unique content of this page; exactly one per page.
<section id="offers">	A thematic group of content, normally with its own heading.
Popular programmes	Second-level heading for a section.
<ul class="cards">	Unordered (bulleted) list.

Line	What it does
<li class="card"> Story hour Ages 3 to 6, Saturdays <s...	Third-level heading, inside an h2 section.
<li class="card"> Reading club Ages 7 to 11 50...	One list item.
<li class="card"> Home work help Weekday afternoons <st...	Strong importance (bold by default).
<footer>	Footer of the page or of a section.
© 2026 Delta Kids Library, Tanta	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.

Declaration	What it does
color: var(--ink);	Text colour.
background: var(--brand);	Background colour or image.
text-align: center;	Centres inline content such as text.
padding: 4rem 1rem;	Space inside the element between its border and content.
font-size: clamp(2rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-size: 1.2rem;	Size of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
font-weight: bold;	Thickness of the text.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Check your work

- Exactly one h1
- Button link has descriptive text
- Cards wrap on narrow screens
- Footer text is readable (contrast)

Exercises

1. Add a fourth card and check the grid still works.
2. Change the hero to a background image with a dark overlay.
3. Add a <nav> with three links inside the header.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 23: Landing page for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Build a one-screen landing page: a coloured hero with the business name, tagline and a call-to-action button, a grid of three cards and a footer.

Learning goals

- Use header, main, section and footer landmarks
- Centre content with max-width and margin auto
- Create a responsive card grid with one line of CSS Grid

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, main, section, h2, ul, li, h3, strong, footer	background, color, padding, border-radius, display: grid, grid-template-columns, repeat(auto-fit, minmax()), gap, max-width

Build guide

1. Create index.html with the standard skeleton and link styles.css.
2. Add the <header class="hero"> with h1, tagline and a link styled as a button.
3. Add <main> with a <section> containing a <ul class="cards"> of three <li class="card"> items.
4. Add the footer with the copyright line.

5. In styles.css set the CSS variables in :root, style the hero, then the grid.
6. Resize the browser: the cards should go from three columns to one.

Project 23: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <h1>Nubian Guest House</h1>
    <p class="tagline">Colourful rooms on the west bank of the Nile</
p>
    <a class="btn" href="#offers">See our rooms</a>
  </header>
  <main>
    <section id="offers">
      <h2>Popular rooms</h2>
      <ul class="cards">
    <li class="card"><h3>Garden room</h3><p>Double bed, shared
terrace</p><strong>900 EGP</strong></li>
    <li class="card"><h3>Nile view suite</h3><p>Balcony and
breakfast</p><strong>1800 EGP</strong></li>
    <li class="card"><h3>Family room</h3><p>Sleeps four</
p><strong>1500 EGP</strong></li>
      </ul>
    </section>
  </main>
  <footer>
    <p>&copy; 2026 Nubian Guest House, Aswan</p>
  </footer>
</body>
</html>
```

Project 23: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(2rem, 5vw, 3rem); }
.tagline { font-size: 1.2rem; opacity: .9; }
.btn { display: inline-block; margin-top: 1rem; padding: .7rem 1.5rem;
 background: #fff; color: var(--brand); border-radius: 999px; text-
```

```
decoration: none; font-weight: bold; }
main { max-width: 60rem; margin: 0 auto; padding: 2rem 1rem; }
.cards { list-style: none; padding: 0; display: grid; gap: 1rem; grid-
template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
footer { text-align: center; padding: 1.5rem; color: var(--muted);
border-top: 1px solid var(--line); }
```

Project 23 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
Nubian Guest House	The main heading; only one per page.
Colourful rooms on the west bank of the Nile	A paragraph of text.
See our rooms	A link styled as a button; it navigates, so it is a link and not a <button>.
<main>	The unique content of this page; exactly one per page.
<section id="offers">	A thematic group of content, normally with its own heading.
Popular rooms	Second-level heading for a section.
<ul class="cards">	Unordered (bulleted) list.

Line	What it does
<li class="card"> Garden room Double bed, shared terrace<...	Third-level heading, inside an h2 section.
<li class="card"> Nile view suite Balcony and breakfast<//...	One list item.
<li class="card"> Family room Sleeps four 1500...	Strong importance (bold by default).
<footer>	Footer of the page or of a section.
© 2026 Nubian Guest House, Aswan	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.

Declaration	What it does
color: var(--ink);	Text colour.
background: var(--brand);	Background colour or image.
text-align: center;	Centres inline content such as text.
padding: 4rem 1rem;	Space inside the element between its border and content.
font-size: clamp(2rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-size: 1.2rem;	Size of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
font-weight: bold;	Thickness of the text.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Check your work

- Exactly one h1
- Button link has descriptive text
- Cards wrap on narrow screens
- Footer text is readable (contrast)

Exercises

1. Add a fourth card and check the grid still works.
2. Change the hero to a background image with a dark overlay.
3. Add a <nav> with three links inside the header.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 24: Landing page for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 1 | Files: index.html, styles.css

Brief

Build a one-screen landing page: a coloured hero with the business name, tagline and a call-to-action button, a grid of three cards and a footer.

Learning goals

- Use header, main, section and footer landmarks
- Centre content with max-width and margin auto
- Create a responsive card grid with one line of CSS Grid

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, main, section, h2, ul, li, h3, strong, footer	background, color, padding, border-radius, display: grid, grid-template-columns, repeat(auto-fit, minmax()), gap, max-width

Build guide

1. Create index.html with the standard skeleton and link styles.css.
2. Add the <header class="hero"> with h1, tagline and a link styled as a button.
3. Add <main> with a <section> containing a <ul class="cards"> of three <li class="card"> items.
4. Add the footer with the copyright line.

5. In styles.css set the CSS variables in :root, style the hero, then the grid.
6. Resize the browser: the cards should go from three columns to one.

Project 24: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <h1>Ismailia Cycling Store</h1>
    <p class="tagline">Bikes, parts and Friday group rides</p>
    <a class="btn" href="#offers">See our bikes</a>
  </header>
  <main>
    <section id="offers">
      <h2>Popular bikes</h2>
      <ul class="cards">
    <li class="card"><h3>City bike</h3><p>Seven gears, basket</
p><strong>6500 EGP</strong></li>
    <li class="card"><h3>Mountain bike</h3><p>Front suspension</
p><strong>11000 EGP</strong></li>
    <li class="card"><h3>Kids bike</h3><p>20 inch wheels</
p><strong>3200 EGP</strong></li>
      </ul>
    </section>
  </main>
  <footer>
    <p>&copy; 2026 Ismailia Cycling Store, Ismailia</p>
  </footer>
</body>
</html>
```

Project 24: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(2rem, 5vw, 3rem); }
.tagline { font-size: 1.2rem; opacity: .9; }
.btn { display: inline-block; margin-top: 1rem; padding: .7rem 1.5rem;
 background: #fff; color: var(--brand); border-radius: 999px; text-
decoration: none; font-weight: bold; }
```

```
main { max-width: 60rem; margin: 0 auto; padding: 2rem 1rem; }
.cards { list-style: none; padding: 0; display: grid; gap: 1rem; grid-
template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
footer { text-align: center; padding: 1.5rem; color: var(--muted);
border-top: 1px solid var(--line); }
```

Project 24 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
Ismailia Cycling Store	The main heading; only one per page.
Bikes, parts and Friday group rides	A paragraph of text.
See our bikes	A link styled as a button; it navigates, so it is a link and not a <button>.
<main>	The unique content of this page; exactly one per page.
<section id="offers">	A thematic group of content, normally with its own heading.
Popular bikes	Second-level heading for a section.
<ul class="cards">	Unordered (bulleted) list.

Line	What it does
<li class="card"> City bike Seven gears, basket <stron...	Third-level heading, inside an h2 section.
<li class="card"> Mountain bike Front suspension <stro...	One list item.
<li class="card"> Kids bike 20 inch wheels 320...	Strong importance (bold by default).
<footer>	Footer of the page or of a section.
© 2026 Ismailia Cycling Store, Ismailia	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.

Declaration	What it does
color: var(--ink);	Text colour.
background: var(--brand);	Background colour or image.
text-align: center;	Centres inline content such as text.
padding: 4rem 1rem;	Space inside the element between its border and content.
font-size: clamp(2rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-size: 1.2rem;	Size of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
font-weight: bold;	Thickness of the text.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Check your work

- Exactly one h1
- Button link has descriptive text
- Cards wrap on narrow screens
- Footer text is readable (contrast)

Exercises

1. Add a fourth card and check the grid still works.
2. Change the hero to a background image with a dark overlay.
3. Add a <nav> with three links inside the header.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 25: Landing page for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 1 | Files: index.html, styles.css

Brief

Build a one-screen landing page: a coloured hero with the business name, tagline and a call-to-action button, a grid of three cards and a footer.

Learning goals

- Use header, main, section and footer landmarks
- Centre content with max-width and margin auto
- Create a responsive card grid with one line of CSS Grid

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, main, section, h2, ul, li, h3, strong, footer	background, color, padding, border-radius, display: grid, grid-template-columns, repeat(auto-fit, minmax()), gap, max-width

Build guide

1. Create index.html with the standard skeleton and link styles.css.
2. Add the <header class="hero"> with h1, tagline and a link styled as a button.
3. Add <main> with a <section> containing a <ul class="cards"> of three <li class="card"> items.
4. Add the footer with the copyright line.

5. In styles.css set the CSS variables in :root, style the hero, then the grid.
6. Resize the browser: the cards should go from three columns to one.

Project 25: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <h1>Minya Coding Club</h1>
    <p class="tagline">Free weekend coding for teenagers</p>
    <a class="btn" href="#offers">See our workshops</a>
  </header>
  <main>
    <section id="offers">
      <h2>Popular workshops</h2>
      <ul class="cards">
    <li class="card"><h3>HTML weekend</h3><p>Build your first page</
p><strong>Free</strong></li>
    <li class="card"><h3>CSS art</h3><p>Draw with code</
p><strong>Free</strong></li>
    <li class="card"><h3>Scratch games</h3><p>Ages 10 to 13</
p><strong>Free</strong></li>
      </ul>
    </section>
  </main>
  <footer>
    <p>&copy; 2026 Minya Coding Club, Minya</p>
  </footer>
</body>
</html>
```

Project 25: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(2rem, 5vw, 3rem); }
.tagline { font-size: 1.2rem; opacity: .9; }
.btn { display: inline-block; margin-top: 1rem; padding: .7rem 1.5rem;
 background: #fff; color: var(--brand); border-radius: 999px; text-
decoration: none; font-weight: bold; }
```

```
main { max-width: 60rem; margin: 0 auto; padding: 2rem 1rem; }
.cards { list-style: none; padding: 0; display: grid; gap: 1rem; grid-
template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
footer { text-align: center; padding: 1.5rem; color: var(--muted);
border-top: 1px solid var(--line); }
```

Project 25 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
Minya Coding Club	The main heading; only one per page.
Free weekend coding for teenagers	A paragraph of text.
See our workshops	A link styled as a button; it navigates, so it is a link and not a <button>.
<main>	The unique content of this page; exactly one per page.
<section id="offers">	A thematic group of content, normally with its own heading.
Popular workshops	Second-level heading for a section.
<ul class="cards">	Unordered (bulleted) list.

Line	What it does
<li class="card"> HTML weekend Build your first page <...	Third-level heading, inside an h2 section.
<li class="card"> CSS art Draw with code Free<...	One list item.
<li class="card"> Scratch games Ages 10 to 13 ...	Strong importance (bold by default).
<footer>	Footer of the page or of a section.
© 2026 Minya Coding Club, Minya	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.

Declaration	What it does
color: var(--ink);	Text colour.
background: var(--brand);	Background colour or image.
text-align: center;	Centres inline content such as text.
padding: 4rem 1rem;	Space inside the element between its border and content.
font-size: clamp(2rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-size: 1.2rem;	Size of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
font-weight: bold;	Thickness of the text.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Check your work

- Exactly one h1
- Button link has descriptive text
- Cards wrap on narrow screens
- Footer text is readable (contrast)

Exercises

1. Add a fourth card and check the grid still works.
2. Change the hero to a background image with a dark overlay.
3. Add a <nav> with three links inside the header.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Navigation bar

Level 1 | 25 projects, one per theme

Build a horizontal navigation bar from an unordered list, with a logo on the left, links on the right and a highlighted current page.

Project 26: Navigation bar for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 1 | Files: index.html, styles.css

Brief

Build a horizontal navigation bar from an unordered list, with a logo on the left, links on the right and a highlighted current page.

Learning goals

- Turn a list into a horizontal menu with Flexbox
- Mark the current page with aria-current
- Style hover and keyboard focus states

Elements and CSS used

HTML elements	CSS features
header, a, nav, ul, li, main, h1, p	display: flex, justify-content, gap, list-style, text-decoration, :hover, :focus-visible, attribute selector

Build guide

1. Write the header with a logo link and a <nav> containing a <ul> of links.
2. Add aria-current="page" to the link for the current page.
3. Make the header a flex container with space-between.
4. Remove list bullets and padding; make the list itself a flex row.
5. Give each link padding and a hover/focus background.
6. Tab through the links with the keyboard and confirm the focus style is visible.

Project 26: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Navigation</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="site-header">
    <a class="logo" href="index.html">Cairo Book Shop</a>
    <nav aria-label="Main">
      <ul class="nav">
        <li><a href="index.html" aria-current="page">Home</a></li>
        <li><a href="books.html">Books</a></li>
        <li><a href="about.html">About</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main>
    <h1>Welcome to Cairo Book Shop</h1>
    <p>PDF and printed books about web development.</p>
  </main>
</body>
</html>
```

Project 26: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.site-header { display: flex; flex-wrap: wrap; align-items: center;
justify-content: space-between; gap: 1rem; padding: .75rem 1.5rem;
background: var(--brand); }
.logo { color: #fff; font-weight: bold; font-size: 1.25rem; text-
decoration: none; }
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { display: block; padding: .5rem .9rem; color: #fff; text-
decoration: none; border-radius: 6px; }
.nav a:hover, .nav a:focus-visible { background: rgb(255 255 255 /
20%); }
.nav a[aria-current="page"] { background: rgb(0 0 0 / 25%); }
main { padding: 2rem 1.5rem; }
```

Project 26 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - Navigation</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
<ul class="nav">	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Books	One list item.
<main>	The unique content of this page; exactly one per page.
Welcome to Cairo Book Shop	The main heading; only one per page.
PDF and printed books about web development.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
gap: 1rem;	Space between grid or flex items without extra margins.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.

Declaration	What it does
font-weight: bold;	Thickness of the text.
font-size: 1.25rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
.nav a:hover, .nav a:focus-visible {	Applies while the pointer is over the element.
.nav a[aria-current="page"] {	Attribute selector: styles the current page or step.

Check your work

- Links are inside <nav> with an aria-label
- Bullets removed
- Current page visibly different
- Focus visible with keyboard

Exercises

1. Make the menu wrap into two rows on narrow screens.
2. Add a dropdown sub-menu with :hover and :focus-within.
3. Make the header sticky.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza

Field	Value
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 27: Navigation bar for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 1 | Files: index.html, styles.css

Brief

Build a horizontal navigation bar from an unordered list, with a logo on the left, links on the right and a highlighted current page.

Learning goals

- Turn a list into a horizontal menu with Flexbox
- Mark the current page with aria-current
- Style hover and keyboard focus states

Elements and CSS used

HTML elements	CSS features
header, a, nav, ul, li, main, h1, p	display: flex, justify-content, gap, list-style, text-decoration, :hover, :focus-visible, attribute selector

Build guide

1. Write the header with a logo link and a <nav> containing a <ul> of links.
2. Add aria-current="page" to the link for the current page.
3. Make the header a flex container with space-between.
4. Remove list bullets and padding; make the list itself a flex row.
5. Give each link padding and a hover/focus background.
6. Tab through the links with the keyboard and confirm the focus style is visible.

Project 27: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - Navigation</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="site-header">
    <a class="logo" href="index.html">Nile Bakery</a>
    <nav aria-label="Main">
      <ul class="nav">
        <li><a href="index.html" aria-current="page">Home</a></li>
        <li><a href="pastries.html">Pastries</a></li>
        <li><a href="about.html">About</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main>
    <h1>Welcome to Nile Bakery</h1>
    <p>Fresh bread and pastries every morning.</p>
  </main>
</body>
</html>
```

Project 27: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.site-header { display: flex; flex-wrap: wrap; align-items: center;
justify-content: space-between; gap: 1rem; padding: .75rem 1.5rem;
background: var(--brand); }
.logo { color: #fff; font-weight: bold; font-size: 1.25rem; text-
decoration: none; }
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { display: block; padding: .5rem .9rem; color: #fff; text-
decoration: none; border-radius: 6px; }
.nav a:hover, .nav a:focus-visible { background: rgb(255 255 255 /
20%); }
.nav a[aria-current="page"] { background: rgb(0 0 0 / 25%); }
main { padding: 2rem 1.5rem; }
```

Project 27 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - Navigation</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
<ul class="nav">	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Pastries	One list item.
<main>	The unique content of this page; exactly one per page.
Welcome to Nile Bakery	The main heading; only one per page.
Fresh bread and pastries every morning.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
gap: 1rem;	Space between grid or flex items without extra margins.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.

Declaration	What it does
font-weight: bold;	Thickness of the text.
font-size: 1.25rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
.nav a:hover, .nav a:focus-visible {	Applies while the pointer is over the element.
.nav a[aria-current="page"] {	Attribute selector: styles the current page or step.

Check your work

- Links are inside <nav> with an aria-label
- Bullets removed
- Current page visibly different
- Focus visible with keyboard

Exercises

1. Make the menu wrap into two rows on narrow screens.
2. Add a dropdown sub-menu with :hover and :focus-within.
3. Make the header sticky.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo

Field	Value
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 28: Navigation bar for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 1 | Files: index.html, styles.css

Brief

Build a horizontal navigation bar from an unordered list, with a logo on the left, links on the right and a highlighted current page.

Learning goals

- Turn a list into a horizontal menu with Flexbox
- Mark the current page with aria-current
- Style hover and keyboard focus states

Elements and CSS used

HTML elements	CSS features
header, a, nav, ul, li, main, h1, p	display: flex, justify-content, gap, list-style, text-decoration, :hover, :focus-visible, attribute selector

Build guide

1. Write the header with a logo link and a <nav> containing a <ul> of links.
2. Add aria-current="page" to the link for the current page.
3. Make the header a flex container with space-between.
4. Remove list bullets and padding; make the list itself a flex row.
5. Give each link padding and a hover/focus background.

6. Tab through the links with the keyboard and confirm the focus style is visible.

Project 28: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - Navigation</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="site-header">
    <a class="logo" href="index.html">Pyramid Fitness</a>
    <nav aria-label="Main">
      <ul class="nav">
        <li><a href="index.html" aria-current="page">Home</a></li>
        <li><a href="classes.html">Classes</a></li>
        <li><a href="about.html">About</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main>
    <h1>Welcome to Pyramid Fitness</h1>
    <p>Train smarter, feel stronger.</p>
  </main>
</body>
</html>
```

Project 28: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.site-header { display: flex; flex-wrap: wrap; align-items: center;
justify-content: space-between; gap: 1rem; padding: .75rem 1.5rem;
background: var(--brand); }
.logo { color: #fff; font-weight: bold; font-size: 1.25rem; text-
decoration: none; }
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { display: block; padding: .5rem .9rem; color: #fff; text-
decoration: none; border-radius: 6px; }
.nav a:hover, .nav a:focus-visible { background: rgb(255 255 255 /
20%); }
.nav a[aria-current="page"] { background: rgb(0 0 0 / 25%); }
main { padding: 2rem 1.5rem; }
```

Project 28 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - Navigation</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
<ul class="nav">	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Classes	One list item.
<main>	The unique content of this page; exactly one per page.
Welcome to Pyramid Fitness	The main heading; only one per page.
Train smarter, feel stronger.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
gap: 1rem;	Space between grid or flex items without extra margins.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.

Declaration	What it does
font-weight: bold;	Thickness of the text.
font-size: 1.25rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
.nav a:hover, .nav a:focus-visible {	Applies while the pointer is over the element.
.nav a[aria-current="page"] {	Attribute selector: styles the current page or step.

Check your work

- Links are inside <nav> with an aria-label
- Bullets removed
- Current page visibly different
- Focus visible with keyboard

Exercises

1. Make the menu wrap into two rows on narrow screens.
2. Add a dropdown sub-menu with :hover and :focus-within.
3. Make the header sticky.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October

Field	Value
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 29: Navigation bar for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 1 | Files: index.html, styles.css

Brief

Build a horizontal navigation bar from an unordered list, with a logo on the left, links on the right and a highlighted current page.

Learning goals

- Turn a list into a horizontal menu with Flexbox
- Mark the current page with aria-current
- Style hover and keyboard focus states

Elements and CSS used

HTML elements	CSS features
header, a, nav, ul, li, main, h1, p	display: flex, justify-content, gap, list-style, text-decoration, :hover, :focus-visible, attribute selector

Build guide

1. Write the header with a logo link and a <nav> containing a <ul> of links.
2. Add aria-current="page" to the link for the current page.
3. Make the header a flex container with space-between.
4. Remove list bullets and padding; make the list itself a flex row.
5. Give each link padding and a hover/focus background.
6. Tab through the links with the keyboard and confirm the focus style is visible.

Project 29: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - Navigation</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="site-header">
    <a class="logo" href="index.html">Delta Dental Clinic</a>
    <nav aria-label="Main">
      <ul class="nav">
        <li><a href="index.html" aria-current="page">Home</a></li>
        <li><a href="services.html">Services</a></li>
        <li><a href="about.html">About</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main>
    <h1>Welcome to Delta Dental Clinic</h1>
    <p>Gentle care for the whole family.</p>
  </main>
</body>
</html>
```

Project 29: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.site-header { display: flex; flex-wrap: wrap; align-items: center;
justify-content: space-between; gap: 1rem; padding: .75rem 1.5rem;
background: var(--brand); }
.logo { color: #fff; font-weight: bold; font-size: 1.25rem; text-
decoration: none; }
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { display: block; padding: .5rem .9rem; color: #fff; text-
decoration: none; border-radius: 6px; }
.nav a:hover, .nav a:focus-visible { background: rgb(255 255 255 /
20%); }
.nav a[aria-current="page"] { background: rgb(0 0 0 / 25%); }
main { padding: 2rem 1.5rem; }
```

Project 29 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - Navigation</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
<ul class="nav">	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Services	One list item.
<main>	The unique content of this page; exactly one per page.
Welcome to Delta Dental Clinic	The main heading; only one per page.
Gentle care for the whole family.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
gap: 1rem;	Space between grid or flex items without extra margins.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.

Declaration	What it does
font-weight: bold;	Thickness of the text.
font-size: 1.25rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
.nav a:hover, .nav a:focus-visible {	Applies while the pointer is over the element.
.nav a[aria-current="page"] {	Attribute selector: styles the current page or step.

Check your work

- Links are inside <nav> with an aria-label
- Bullets removed
- Current page visibly different
- Focus visible with keyboard

Exercises

1. Make the menu wrap into two rows on narrow screens.
2. Add a dropdown sub-menu with :hover and :focus-within.
3. Make the header sticky.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura

Field	Value
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 30: Navigation bar for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 1 | Files: index.html, styles.css

Brief

Build a horizontal navigation bar from an unordered list, with a logo on the left, links on the right and a highlighted current page.

Learning goals

- Turn a list into a horizontal menu with Flexbox
- Mark the current page with aria-current
- Style hover and keyboard focus states

Elements and CSS used

HTML elements	CSS features
header, a, nav, ul, li, main, h1, p	display: flex, justify-content, gap, list-style, text-decoration, :hover, :focus-visible, attribute selector

Build guide

1. Write the header with a logo link and a <nav> containing a <ul> of links.
2. Add aria-current="page" to the link for the current page.
3. Make the header a flex container with space-between.
4. Remove list bullets and padding; make the list itself a flex row.
5. Give each link padding and a hover/focus background.
6. Tab through the links with the keyboard and confirm the focus style is visible.

Project 30: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - Navigation</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="site-header">
    <a class="logo" href="index.html">Red Sea Travel</a>
    <nav aria-label="Main">
      <ul class="nav">
        <li><a href="index.html" aria-current="page">Home</a></li>
        <li><a href="tours.html">Tours</a></li>
        <li><a href="about.html">About</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main>
    <h1>Welcome to Red Sea Travel</h1>
    <p>Discover Egypt from desert to reef.</p>
  </main>
</body>
</html>
```

Project 30: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.site-header { display: flex; flex-wrap: wrap; align-items: center;
justify-content: space-between; gap: 1rem; padding: .75rem 1.5rem;
background: var(--brand); }
.logo { color: #fff; font-weight: bold; font-size: 1.25rem; text-
decoration: none; }
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { display: block; padding: .5rem .9rem; color: #fff; text-
decoration: none; border-radius: 6px; }
.nav a:hover, .nav a:focus-visible { background: rgb(255 255 255 /
20%); }
.nav a[aria-current="page"] { background: rgb(0 0 0 / 25%); }
main { padding: 2rem 1.5rem; }
```

Project 30 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - Navigation</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
<ul class="nav">	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Tours	One list item.
<main>	The unique content of this page; exactly one per page.
Welcome to Red Sea Travel	The main heading; only one per page.
Discover Egypt from desert to reef.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
gap: 1rem;	Space between grid or flex items without extra margins.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.

Declaration	What it does
font-weight: bold;	Thickness of the text.
font-size: 1.25rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
.nav a:hover, .nav a:focus-visible {	Applies while the pointer is over the element.
.nav a[aria-current="page"] {	Attribute selector: styles the current page or step.

Check your work

- Links are inside <nav> with an aria-label
- Bullets removed
- Current page visibly different
- Focus visible with keyboard

Exercises

1. Make the menu wrap into two rows on narrow screens.
2. Add a dropdown sub-menu with :hover and :focus-within.
3. Make the header sticky.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada

Field	Value
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 31: Navigation bar for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Build a horizontal navigation bar from an unordered list, with a logo on the left, links on the right and a highlighted current page.

Learning goals

- Turn a list into a horizontal menu with Flexbox
- Mark the current page with aria-current
- Style hover and keyboard focus states

Elements and CSS used

HTML elements	CSS features
header, a, nav, ul, li, main, h1, p	display: flex, justify-content, gap, list-style, text-decoration, :hover, :focus-visible, attribute selector

Build guide

1. Write the header with a logo link and a <nav> containing a <ul> of links.
2. Add aria-current="page" to the link for the current page.
3. Make the header a flex container with space-between.
4. Remove list bullets and padding; make the list itself a flex row.
5. Give each link padding and a hover/focus background.

6. Tab through the links with the keyboard and confirm the focus style is visible.

Project 31: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - Navigation</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="site-header">
    <a class="logo" href="index.html">Lotus Language School</a>
    <nav aria-label="Main">
      <ul class="nav">
        <li><a href="index.html" aria-current="page">Home</a></li>
        <li><a href="courses.html">Courses</a></li>
        <li><a href="about.html">About</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main>
    <h1>Welcome to Lotus Language School</h1>
    <p>Learn English, French and German in small groups.</p>
  </main>
</body>
</html>
```

Project 31: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.site-header { display: flex; flex-wrap: wrap; align-items: center;
justify-content: space-between; gap: 1rem; padding: .75rem 1.5rem;
background: var(--brand); }
.logo { color: #fff; font-weight: bold; font-size: 1.25rem; text-
decoration: none; }
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { display: block; padding: .5rem .9rem; color: #fff; text-
decoration: none; border-radius: 6px; }
.nav a:hover, .nav a:focus-visible { background: rgb(255 255 255 /
20%); }
.nav a[aria-current="page"] { background: rgb(0 0 0 / 25%); }
main { padding: 2rem 1.5rem; }
```

Project 31 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - Navigation</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
<ul class="nav">	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Courses	One list item.
<main>	The unique content of this page; exactly one per page.
Welcome to Lotus Language School	The main heading; only one per page.
Learn English, French and German in small groups.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
gap: 1rem;	Space between grid or flex items without extra margins.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.

Declaration	What it does
font-weight: bold;	Thickness of the text.
font-size: 1.25rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
.nav a:hover, .nav a:focus-visible {	Applies while the pointer is over the element.
.nav a[aria-current="page"] {	Attribute selector: styles the current page or step.

Check your work

- Links are inside <nav> with an aria-label
- Bullets removed
- Current page visibly different
- Focus visible with keyboard

Exercises

1. Make the menu wrap into two rows on narrow screens.
2. Add a dropdown sub-menu with :hover and :focus-within.
3. Make the header sticky.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria

Field	Value
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 32: Navigation bar for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 1 | Files: index.html, styles.css

Brief

Build a horizontal navigation bar from an unordered list, with a logo on the left, links on the right and a highlighted current page.

Learning goals

- Turn a list into a horizontal menu with Flexbox
- Mark the current page with aria-current
- Style hover and keyboard focus states

Elements and CSS used

HTML elements	CSS features
header, a, nav, ul, li, main, h1, p	display: flex, justify-content, gap, list-style, text-decoration, :hover, :focus-visible, attribute selector

Build guide

1. Write the header with a logo link and a <nav> containing a <ul> of links.
2. Add aria-current="page" to the link for the current page.
3. Make the header a flex container with space-between.
4. Remove list bullets and padding; make the list itself a flex row.
5. Give each link padding and a hover/focus background.
6. Tab through the links with the keyboard and confirm the focus style is visible.

Project 32: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - Navigation</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="site-header">
    <a class="logo" href="index.html">Green Leaf Cafe</a>
    <nav aria-label="Main">
      <ul class="nav">
        <li><a href="index.html" aria-current="page">Home</a></li>
        <li><a href="drinks.html">Drinks</a></li>
        <li><a href="about.html">About</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main>
    <h1>Welcome to Green Leaf Cafe</h1>
    <p>Specialty coffee and quiet corners.</p>
  </main>
</body>
</html>
```

Project 32: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.site-header { display: flex; flex-wrap: wrap; align-items: center;
justify-content: space-between; gap: 1rem; padding: .75rem 1.5rem;
background: var(--brand); }
.logo { color: #fff; font-weight: bold; font-size: 1.25rem; text-
decoration: none; }
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { display: block; padding: .5rem .9rem; color: #fff; text-
decoration: none; border-radius: 6px; }
.nav a:hover, .nav a:focus-visible { background: rgb(255 255 255 /
20%); }
.nav a[aria-current="page"] { background: rgb(0 0 0 / 25%); }
main { padding: 2rem 1.5rem; }
```

Project 32 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - Navigation</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
<ul class="nav">	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Drinks	One list item.
<main>	The unique content of this page; exactly one per page.
Welcome to Green Leaf Cafe	The main heading; only one per page.
Specialty coffee and quiet corners.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
gap: 1rem;	Space between grid or flex items without extra margins.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.

Declaration	What it does
font-weight: bold;	Thickness of the text.
font-size: 1.25rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
.nav a:hover, .nav a:focus-visible {	Applies while the pointer is over the element.
.nav a[aria-current="page"] {	Attribute selector: styles the current page or step.

Check your work

- Links are inside <nav> with an aria-label
- Bullets removed
- Current page visibly different
- Focus visible with keyboard

Exercises

1. Make the menu wrap into two rows on narrow screens.
2. Add a dropdown sub-menu with :hover and :focus-within.
3. Make the header sticky.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek

Field	Value
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 33: Navigation bar for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 1 | Files: index.html, styles.css

Brief

Build a horizontal navigation bar from an unordered list, with a logo on the left, links on the right and a highlighted current page.

Learning goals

- Turn a list into a horizontal menu with Flexbox
- Mark the current page with aria-current
- Style hover and keyboard focus states

Elements and CSS used

HTML elements	CSS features
header, a, nav, ul, li, main, h1, p	display: flex, justify-content, gap, list-style, text-decoration, :hover, :focus-visible, attribute selector

Build guide

1. Write the header with a logo link and a <nav> containing a <ul> of links.
2. Add aria-current="page" to the link for the current page.
3. Make the header a flex container with space-between.
4. Remove list bullets and padding; make the list itself a flex row.
5. Give each link padding and a hover/focus background.

6. Tab through the links with the keyboard and confirm the focus style is visible.

Project 33: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - Navigation</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="site-header">
    <a class="logo" href="index.html">Sinai Trekking Club</a>
    <nav aria-label="Main">
      <ul class="nav">
        <li><a href="index.html" aria-current="page">Home</a></li>
        <li><a href="hikes.html">Hikes</a></li>
        <li><a href="about.html">About</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main>
    <h1>Welcome to Sinai Trekking Club</h1>
    <p>Guided mountain walks for every level.</p>
  </main>
</body>
</html>
```

Project 33: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.site-header { display: flex; flex-wrap: wrap; align-items: center;
justify-content: space-between; gap: 1rem; padding: .75rem 1.5rem;
background: var(--brand); }
.logo { color: #fff; font-weight: bold; font-size: 1.25rem; text-
decoration: none; }
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { display: block; padding: .5rem .9rem; color: #fff; text-
decoration: none; border-radius: 6px; }
.nav a:hover, .nav a:focus-visible { background: rgb(255 255 255 /
20%); }
.nav a[aria-current="page"] { background: rgb(0 0 0 / 25%); }
main { padding: 2rem 1.5rem; }
```

Project 33 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - Navigation</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
<ul class="nav">	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Hikes	One list item.
<main>	The unique content of this page; exactly one per page.
Welcome to Sinai Trekking Club	The main heading; only one per page.
Guided mountain walks for every level.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
gap: 1rem;	Space between grid or flex items without extra margins.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.

Declaration	What it does
font-weight: bold;	Thickness of the text.
font-size: 1.25rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
.nav a:hover, .nav a:focus-visible {	Applies while the pointer is over the element.
.nav a[aria-current="page"] {	Attribute selector: styles the current page or step.

Check your work

- Links are inside <nav> with an aria-label
- Bullets removed
- Current page visibly different
- Focus visible with keyboard

Exercises

1. Make the menu wrap into two rows on narrow screens.
2. Add a dropdown sub-menu with :hover and :focus-within.
3. Make the header sticky.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine

Field	Value
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 34: Navigation bar for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 1 | Files: index.html, styles.css

Brief

Build a horizontal navigation bar from an unordered list, with a logo on the left, links on the right and a highlighted current page.

Learning goals

- Turn a list into a horizontal menu with Flexbox
- Mark the current page with aria-current
- Style hover and keyboard focus states

Elements and CSS used

HTML elements	CSS features
header, a, nav, ul, li, main, h1, p	display: flex, justify-content, gap, list-style, text-decoration, :hover, :focus-visible, attribute selector

Build guide

1. Write the header with a logo link and a <nav> containing a <ul> of links.
2. Add aria-current="page" to the link for the current page.
3. Make the header a flex container with space-between.
4. Remove list bullets and padding; make the list itself a flex row.
5. Give each link padding and a hover/focus background.
6. Tab through the links with the keyboard and confirm the focus style is visible.

Project 34: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - Navigation</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="site-header">
    <a class="logo" href="index.html">Horizon Photography</a>
    <nav aria-label="Main">
      <ul class="nav">
        <li><a href="index.html" aria-current="page">Home</a></li>
        <li><a href="sessions.html">Sessions</a></li>
        <li><a href="about.html">About</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main>
    <h1>Welcome to Horizon Photography</h1>
    <p>Portraits, weddings and product photography.</p>
  </main>
</body>
</html>
```

Project 34: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.site-header { display: flex; flex-wrap: wrap; align-items: center;
justify-content: space-between; gap: 1rem; padding: .75rem 1.5rem;
background: var(--brand); }
.logo { color: #fff; font-weight: bold; font-size: 1.25rem; text-
decoration: none; }
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { display: block; padding: .5rem .9rem; color: #fff; text-
decoration: none; border-radius: 6px; }
.nav a:hover, .nav a:focus-visible { background: rgb(255 255 255 /
20%); }
.nav a[aria-current="page"] { background: rgb(0 0 0 / 25%); }
main { padding: 2rem 1.5rem; }
```

Project 34 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - Navigation</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
<ul class="nav">	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Sessions	One list item.
<main>	The unique content of this page; exactly one per page.
Welcome to Horizon Photography	The main heading; only one per page.
Portraits, weddings and product photography.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
gap: 1rem;	Space between grid or flex items without extra margins.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.

Declaration	What it does
font-weight: bold;	Thickness of the text.
font-size: 1.25rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
.nav a:hover, .nav a:focus-visible {	Applies while the pointer is over the element.
.nav a[aria-current="page"] {	Attribute selector: styles the current page or step.

Check your work

- Links are inside <nav> with an aria-label
- Bullets removed
- Current page visibly different
- Focus visible with keyboard

Exercises

1. Make the menu wrap into two rows on narrow screens.
2. Add a dropdown sub-menu with :hover and :focus-within.
3. Make the header sticky.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi

Field	Value
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 35: Navigation bar for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 1 | Files: index.html, styles.css

Brief

Build a horizontal navigation bar from an unordered list, with a logo on the left, links on the right and a highlighted current page.

Learning goals

- Turn a list into a horizontal menu with Flexbox
- Mark the current page with aria-current
- Style hover and keyboard focus states

Elements and CSS used

HTML elements	CSS features
header, a, nav, ul, li, main, h1, p	display: flex, justify-content, gap, list-style, text-decoration, :hover, :focus-visible, attribute selector

Build guide

1. Write the header with a logo link and a <nav> containing a <ul> of links.
2. Add aria-current="page" to the link for the current page.
3. Make the header a flex container with space-between.
4. Remove list bullets and padding; make the list itself a flex row.
5. Give each link padding and a hover/focus background.
6. Tab through the links with the keyboard and confirm the focus style is visible.

Project 35: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - Navigation</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="site-header">
    <a class="logo" href="index.html">Papyrus Stationery</a>
    <nav aria-label="Main">
      <ul class="nav">
        <li><a href="index.html" aria-current="page">Home</a></li>
        <li><a href="products.html">Products</a></li>
        <li><a href="about.html">About</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main>
    <h1>Welcome to Papyrus Stationery</h1>
    <p>Notebooks, pens and paper made in Egypt.</p>
  </main>
</body>
</html>
```

Project 35: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.site-header { display: flex; flex-wrap: wrap; align-items: center;
justify-content: space-between; gap: 1rem; padding: .75rem 1.5rem;
background: var(--brand); }
.logo { color: #fff; font-weight: bold; font-size: 1.25rem; text-
decoration: none; }
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { display: block; padding: .5rem .9rem; color: #fff; text-
decoration: none; border-radius: 6px; }
.nav a:hover, .nav a:focus-visible { background: rgb(255 255 255 /
20%); }
.nav a[aria-current="page"] { background: rgb(0 0 0 / 25%); }
main { padding: 2rem 1.5rem; }
```

Project 35 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - Navigation</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
<ul class="nav">	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Products	One list item.
<main>	The unique content of this page; exactly one per page.
Welcome to Papyrus Stationery	The main heading; only one per page.
Notebooks, pens and paper made in Egypt.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
gap: 1rem;	Space between grid or flex items without extra margins.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.

Declaration	What it does
font-weight: bold;	Thickness of the text.
font-size: 1.25rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
.nav a:hover, .nav a:focus-visible {	Applies while the pointer is over the element.
.nav a[aria-current="page"] {	Attribute selector: styles the current page or step.

Check your work

- Links are inside <nav> with an aria-label
- Bullets removed
- Current page visibly different
- Focus visible with keyboard

Exercises

1. Make the menu wrap into two rows on narrow screens.
2. Add a dropdown sub-menu with :hover and :focus-within.
3. Make the header sticky.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis

Field	Value
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 36: Navigation bar for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 1 | Files: index.html, styles.css

Brief

Build a horizontal navigation bar from an unordered list, with a logo on the left, links on the right and a highlighted current page.

Learning goals

- Turn a list into a horizontal menu with Flexbox
- Mark the current page with aria-current
- Style hover and keyboard focus states

Elements and CSS used

HTML elements	CSS features
header, a, nav, ul, li, main, h1, p	display: flex, justify-content, gap, list-style, text-decoration, :hover, :focus-visible, attribute selector

Build guide

1. Write the header with a logo link and a <nav> containing a <ul> of links.
2. Add aria-current="page" to the link for the current page.
3. Make the header a flex container with space-between.
4. Remove list bullets and padding; make the list itself a flex row.
5. Give each link padding and a hover/focus background.

6. Tab through the links with the keyboard and confirm the focus style is visible.

Project 36: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - Navigation</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="site-header">
    <a class="logo" href="index.html">Oasis Plant Nursery</a>
    <nav aria-label="Main">
      <ul class="nav">
        <li><a href="index.html" aria-current="page">Home</a></li>
        <li><a href="plants.html">Plants</a></li>
        <li><a href="about.html">About</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main>
    <h1>Welcome to Oasis Plant Nursery</h1>
    <p>Indoor plants and gardening advice.</p>
  </main>
</body>
</html>
```

Project 36: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.site-header { display: flex; flex-wrap: wrap; align-items: center;
justify-content: space-between; gap: 1rem; padding: .75rem 1.5rem;
background: var(--brand); }
.logo { color: #fff; font-weight: bold; font-size: 1.25rem; text-
decoration: none; }
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { display: block; padding: .5rem .9rem; color: #fff; text-
decoration: none; border-radius: 6px; }
.nav a:hover, .nav a:focus-visible { background: rgb(255 255 255 /
20%); }
.nav a[aria-current="page"] { background: rgb(0 0 0 / 25%); }
main { padding: 2rem 1.5rem; }
```

Project 36 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - Navigation</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
<ul class="nav">	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Plants	One list item.
<main>	The unique content of this page; exactly one per page.
Welcome to Oasis Plant Nursery	The main heading; only one per page.
Indoor plants and gardening advice.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
gap: 1rem;	Space between grid or flex items without extra margins.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.

Declaration	What it does
font-weight: bold;	Thickness of the text.
font-size: 1.25rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
.nav a:hover, .nav a:focus-visible {	Applies while the pointer is over the element.
.nav a[aria-current="page"] {	Attribute selector: styles the current page or step.

Check your work

- Links are inside <nav> with an aria-label
- Bullets removed
- Current page visibly different
- Focus visible with keyboard

Exercises

1. Make the menu wrap into two rows on narrow screens.
2. Add a dropdown sub-menu with :hover and :focus-within.
3. Make the header sticky.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed

Field	Value
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 37: Navigation bar for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 1 | Files: index.html, styles.css

Brief

Build a horizontal navigation bar from an unordered list, with a logo on the left, links on the right and a highlighted current page.

Learning goals

- Turn a list into a horizontal menu with Flexbox
- Mark the current page with aria-current
- Style hover and keyboard focus states

Elements and CSS used

HTML elements	CSS features
header, a, nav, ul, li, main, h1, p	display: flex, justify-content, gap, list-style, text-decoration, :hover, :focus-visible, attribute selector

Build guide

1. Write the header with a logo link and a <nav> containing a <ul> of links.
2. Add aria-current="page" to the link for the current page.
3. Make the header a flex container with space-between.
4. Remove list bullets and padding; make the list itself a flex row.
5. Give each link padding and a hover/focus background.
6. Tab through the links with the keyboard and confirm the focus style is visible.

Project 37: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - Navigation</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="site-header">
    <a class="logo" href="index.html">Cedar Furniture</a>
    <nav aria-label="Main">
      <ul class="nav">
        <li><a href="index.html" aria-current="page">Home</a></li>
        <li><a href="pieces.html">Pieces</a></li>
        <li><a href="about.html">About</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main>
    <h1>Welcome to Cedar Furniture</h1>
    <p>Solid wood furniture made to order.</p>
  </main>
</body>
</html>
```

Project 37: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.site-header { display: flex; flex-wrap: wrap; align-items: center;
justify-content: space-between; gap: 1rem; padding: .75rem 1.5rem;
background: var(--brand); }
.logo { color: #fff; font-weight: bold; font-size: 1.25rem; text-
decoration: none; }
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { display: block; padding: .5rem .9rem; color: #fff; text-
decoration: none; border-radius: 6px; }
.nav a:hover, .nav a:focus-visible { background: rgb(255 255 255 /
20%); }
.nav a[aria-current="page"] { background: rgb(0 0 0 / 25%); }
main { padding: 2rem 1.5rem; }
```

Project 37 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - Navigation</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
<ul class="nav">	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Pieces	One list item.
<main>	The unique content of this page; exactly one per page.
Welcome to Cedar Furniture	The main heading; only one per page.
Solid wood furniture made to order.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
gap: 1rem;	Space between grid or flex items without extra margins.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.

Declaration	What it does
font-weight: bold;	Thickness of the text.
font-size: 1.25rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
.nav a:hover, .nav a:focus-visible {	Applies while the pointer is over the element.
.nav a[aria-current="page"] {	Attribute selector: styles the current page or step.

Check your work

- Links are inside <nav> with an aria-label
- Bullets removed
- Current page visibly different
- Focus visible with keyboard

Exercises

1. Make the menu wrap into two rows on narrow screens.
2. Add a dropdown sub-menu with :hover and :focus-within.
3. Make the header sticky.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta

Field	Value
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 38: Navigation bar for Byte Repair

Theme: Byte Repair (Nasr City) | Level 1 | Files: index.html, styles.css

Brief

Build a horizontal navigation bar from an unordered list, with a logo on the left, links on the right and a highlighted current page.

Learning goals

- Turn a list into a horizontal menu with Flexbox
- Mark the current page with aria-current
- Style hover and keyboard focus states

Elements and CSS used

HTML elements	CSS features
header, a, nav, ul, li, main, h1, p	display: flex, justify-content, gap, list-style, text-decoration, :hover, :focus-visible, attribute selector

Build guide

1. Write the header with a logo link and a <nav> containing a <ul> of links.
2. Add aria-current="page" to the link for the current page.
3. Make the header a flex container with space-between.
4. Remove list bullets and padding; make the list itself a flex row.
5. Give each link padding and a hover/focus background.
6. Tab through the links with the keyboard and confirm the focus style is visible.

Project 38: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - Navigation</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="site-header">
    <a class="logo" href="index.html">Byte Repair</a>
    <nav aria-label="Main">
      <ul class="nav">
        <li><a href="index.html" aria-current="page">Home</a></li>
        <li><a href="repairs.html">Repairs</a></li>
        <li><a href="about.html">About</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main>
    <h1>Welcome to Byte Repair</h1>
    <p>Phone and laptop repairs while you wait.</p>
  </main>
</body>
</html>
```

Project 38: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.site-header { display: flex; flex-wrap: wrap; align-items: center;
justify-content: space-between; gap: 1rem; padding: .75rem 1.5rem;
background: var(--brand); }
.logo { color: #fff; font-weight: bold; font-size: 1.25rem; text-
decoration: none; }
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { display: block; padding: .5rem .9rem; color: #fff; text-
decoration: none; border-radius: 6px; }
.nav a:hover, .nav a:focus-visible { background: rgb(255 255 255 /
20%); }
.nav a[aria-current="page"] { background: rgb(0 0 0 / 25%); }
main { padding: 2rem 1.5rem; }
```

Project 38 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - Navigation</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
<ul class="nav">	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Repairs	One list item.
<main>	The unique content of this page; exactly one per page.
Welcome to Byte Repair	The main heading; only one per page.
Phone and laptop repairs while you wait.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
gap: 1rem;	Space between grid or flex items without extra margins.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.

Declaration	What it does
font-weight: bold;	Thickness of the text.
font-size: 1.25rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
.nav a:hover, .nav a:focus-visible {	Applies while the pointer is over the element.
.nav a[aria-current="page"] {	Attribute selector: styles the current page or step.

Check your work

- Links are inside <nav> with an aria-label
- Bullets removed
- Current page visibly different
- Focus visible with keyboard

Exercises

1. Make the menu wrap into two rows on narrow screens.
2. Add a dropdown sub-menu with :hover and :focus-within.
3. Make the header sticky.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City

Field	Value
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 39: Navigation bar for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 1 | Files: index.html, styles.css

Brief

Build a horizontal navigation bar from an unordered list, with a logo on the left, links on the right and a highlighted current page.

Learning goals

- Turn a list into a horizontal menu with Flexbox
- Mark the current page with aria-current
- Style hover and keyboard focus states

Elements and CSS used

HTML elements	CSS features
header, a, nav, ul, li, main, h1, p	display: flex, justify-content, gap, list-style, text-decoration, :hover, :focus-visible, attribute selector

Build guide

1. Write the header with a logo link and a <nav> containing a <ul> of links.
2. Add aria-current="page" to the link for the current page.
3. Make the header a flex container with space-between.
4. Remove list bullets and padding; make the list itself a flex row.
5. Give each link padding and a hover/focus background.
6. Tab through the links with the keyboard and confirm the focus style is visible.

Project 39: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - Navigation</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="site-header">
    <a class="logo" href="index.html">Sahara Pet Care</a>
    <nav aria-label="Main">
      <ul class="nav">
        <li><a href="index.html" aria-current="page">Home</a></li>
        <li><a href="services.html">Services</a></li>
        <li><a href="about.html">About</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main>
    <h1>Welcome to Sahara Pet Care</h1>
    <p>Grooming, boarding and vet visits.</p>
  </main>
</body>
</html>
```

Project 39: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.site-header { display: flex; flex-wrap: wrap; align-items: center;
justify-content: space-between; gap: 1rem; padding: .75rem 1.5rem;
background: var(--brand); }
.logo { color: #fff; font-weight: bold; font-size: 1.25rem; text-
decoration: none; }
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { display: block; padding: .5rem .9rem; color: #fff; text-
decoration: none; border-radius: 6px; }
.nav a:hover, .nav a:focus-visible { background: rgb(255 255 255 /
20%); }
.nav a[aria-current="page"] { background: rgb(0 0 0 / 25%); }
main { padding: 2rem 1.5rem; }
```

Project 39 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - Navigation</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
<ul class="nav">	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Services	One list item.
<main>	The unique content of this page; exactly one per page.
Welcome to Sahara Pet Care	The main heading; only one per page.
Grooming, boarding and vet visits.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
gap: 1rem;	Space between grid or flex items without extra margins.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.

Declaration	What it does
font-weight: bold;	Thickness of the text.
font-size: 1.25rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
.nav a:hover, .nav a:focus-visible {	Applies while the pointer is over the element.
.nav a[aria-current="page"] {	Attribute selector: styles the current page or step.

Check your work

- Links are inside <nav> with an aria-label
- Bullets removed
- Current page visibly different
- Focus visible with keyboard

Exercises

1. Make the menu wrap into two rows on narrow screens.
2. Add a dropdown sub-menu with :hover and :focus-within.
3. Make the header sticky.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo

Field	Value
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 40: Navigation bar for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Build a horizontal navigation bar from an unordered list, with a logo on the left, links on the right and a highlighted current page.

Learning goals

- Turn a list into a horizontal menu with Flexbox
- Mark the current page with aria-current
- Style hover and keyboard focus states

Elements and CSS used

HTML elements	CSS features
header, a, nav, ul, li, main, h1, p	display: flex, justify-content, gap, list-style, text-decoration, :hover, :focus-visible, attribute selector

Build guide

1. Write the header with a logo link and a <nav> containing a <ul> of links.
2. Add aria-current="page" to the link for the current page.
3. Make the header a flex container with space-between.
4. Remove list bullets and padding; make the list itself a flex row.
5. Give each link padding and a hover/focus background.

6. Tab through the links with the keyboard and confirm the focus style is visible.

Project 40: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - Navigation</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="site-header">
    <a class="logo" href="index.html">Alexandria Sailing School</a>
    <nav aria-label="Main">
      <ul class="nav">
        <li><a href="index.html" aria-current="page">Home</a></li>
        <li><a href="lessons.html">Lessons</a></li>
        <li><a href="about.html">About</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main>
    <h1>Welcome to Alexandria Sailing School</h1>
    <p>Learn to sail on the Mediterranean.</p>
  </main>
</body>
</html>
```

Project 40: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.site-header { display: flex; flex-wrap: wrap; align-items: center;
justify-content: space-between; gap: 1rem; padding: .75rem 1.5rem;
background: var(--brand); }
.logo { color: #fff; font-weight: bold; font-size: 1.25rem; text-
decoration: none; }
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { display: block; padding: .5rem .9rem; color: #fff; text-
decoration: none; border-radius: 6px; }
.nav a:hover, .nav a:focus-visible { background: rgb(255 255 255 /
20%); }
.nav a[aria-current="page"] { background: rgb(0 0 0 / 25%); }
main { padding: 2rem 1.5rem; }
```

Project 40 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - Navigation</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
<ul class="nav">	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Lessons	One list item.
<main>	The unique content of this page; exactly one per page.
Welcome to Alexandria Sailing School	The main heading; only one per page.
Learn to sail on the Mediterranean.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
gap: 1rem;	Space between grid or flex items without extra margins.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.

Declaration	What it does
font-weight: bold;	Thickness of the text.
font-size: 1.25rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
.nav a:hover, .nav a:focus-visible {	Applies while the pointer is over the element.
.nav a[aria-current="page"] {	Attribute selector: styles the current page or step.

Check your work

- Links are inside <nav> with an aria-label
- Bullets removed
- Current page visibly different
- Focus visible with keyboard

Exercises

1. Make the menu wrap into two rows on narrow screens.
2. Add a dropdown sub-menu with :hover and :focus-within.
3. Make the header sticky.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria

Field	Value
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 41: Navigation bar for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Build a horizontal navigation bar from an unordered list, with a logo on the left, links on the right and a highlighted current page.

Learning goals

- Turn a list into a horizontal menu with Flexbox
- Mark the current page with aria-current
- Style hover and keyboard focus states

Elements and CSS used

HTML elements	CSS features
header, a, nav, ul, li, main, h1, p	display: flex, justify-content, gap, list-style, text-decoration, :hover, :focus-visible, attribute selector

Build guide

1. Write the header with a logo link and a <nav> containing a <ul> of links.
2. Add aria-current="page" to the link for the current page.
3. Make the header a flex container with space-between.
4. Remove list bullets and padding; make the list itself a flex row.
5. Give each link padding and a hover/focus background.

6. Tab through the links with the keyboard and confirm the focus style is visible.

Project 41: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - Navigation</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="site-header">
    <a class="logo" href="index.html">Habiba Handmade Jewellery</a>
    <nav aria-label="Main">
      <ul class="nav">
        <li><a href="index.html" aria-current="page">Home</a></li>
        <li><a href="items.html">Items</a></li>
        <li><a href="about.html">About</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main>
    <h1>Welcome to Habiba Handmade Jewellery</h1>
    <p>Silver and brass pieces inspired by Nubia.</p>
  </main>
</body>
</html>
```

Project 41: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.site-header { display: flex; flex-wrap: wrap; align-items: center;
justify-content: space-between; gap: 1rem; padding: .75rem 1.5rem;
background: var(--brand); }
.logo { color: #fff; font-weight: bold; font-size: 1.25rem; text-
decoration: none; }
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { display: block; padding: .5rem .9rem; color: #fff; text-
decoration: none; border-radius: 6px; }
.nav a:hover, .nav a:focus-visible { background: rgb(255 255 255 /
20%); }
.nav a[aria-current="page"] { background: rgb(0 0 0 / 25%); }
main { padding: 2rem 1.5rem; }
```

Project 41 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - Navigation</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
<ul class="nav">	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Items	One list item.
<main>	The unique content of this page; exactly one per page.
Welcome to Habiba Handmade Jewellery	The main heading; only one per page.
Silver and brass pieces inspired by Nubia.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
gap: 1rem;	Space between grid or flex items without extra margins.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.

Declaration	What it does
font-weight: bold;	Thickness of the text.
font-size: 1.25rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
.nav a:hover, .nav a:focus-visible {	Applies while the pointer is over the element.
.nav a[aria-current="page"] {	Attribute selector: styles the current page or step.

Check your work

- Links are inside <nav> with an aria-label
- Bullets removed
- Current page visibly different
- Focus visible with keyboard

Exercises

1. Make the menu wrap into two rows on narrow screens.
2. Add a dropdown sub-menu with :hover and :focus-within.
3. Make the header sticky.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan

Field	Value
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 42: Navigation bar for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 1 | Files: index.html, styles.css

Brief

Build a horizontal navigation bar from an unordered list, with a logo on the left, links on the right and a highlighted current page.

Learning goals

- Turn a list into a horizontal menu with Flexbox
- Mark the current page with aria-current
- Style hover and keyboard focus states

Elements and CSS used

HTML elements	CSS features
header, a, nav, ul, li, main, h1, p	display: flex, justify-content, gap, list-style, text-decoration, :hover, :focus-visible, attribute selector

Build guide

1. Write the header with a logo link and a <nav> containing a <ul> of links.
2. Add aria-current="page" to the link for the current page.
3. Make the header a flex container with space-between.
4. Remove list bullets and padding; make the list itself a flex row.
5. Give each link padding and a hover/focus background.

6. Tab through the links with the keyboard and confirm the focus style is visible.

Project 42: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - Navigation</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="site-header">
    <a class="logo" href="index.html">Fayoum Pottery Studio</a>
    <nav aria-label="Main">
      <ul class="nav">
        <li><a href="index.html" aria-current="page">Home</a></li>
        <li><a href="workshops.html">Workshops</a></li>
        <li><a href="about.html">About</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main>
    <h1>Welcome to Fayoum Pottery Studio</h1>
    <p>Wheel throwing and glazing classes.</p>
  </main>
</body>
</html>
```

Project 42: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.site-header { display: flex; flex-wrap: wrap; align-items: center;
justify-content: space-between; gap: 1rem; padding: .75rem 1.5rem;
background: var(--brand); }
.logo { color: #fff; font-weight: bold; font-size: 1.25rem; text-
decoration: none; }
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { display: block; padding: .5rem .9rem; color: #fff; text-
decoration: none; border-radius: 6px; }
.nav a:hover, .nav a:focus-visible { background: rgb(255 255 255 /
20%); }
.nav a[aria-current="page"] { background: rgb(0 0 0 / 25%); }
main { padding: 2rem 1.5rem; }
```

Project 42 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - Navigation</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
<ul class="nav">	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Workshops	One list item.
<main>	The unique content of this page; exactly one per page.
Welcome to Fayoum Pottery Studio	The main heading; only one per page.
Wheel throwing and glazing classes.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
gap: 1rem;	Space between grid or flex items without extra margins.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.

Declaration	What it does
font-weight: bold;	Thickness of the text.
font-size: 1.25rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
.nav a:hover, .nav a:focus-visible {	Applies while the pointer is over the element.
.nav a[aria-current="page"] {	Attribute selector: styles the current page or step.

Check your work

- Links are inside <nav> with an aria-label
- Bullets removed
- Current page visibly different
- Focus visible with keyboard

Exercises

1. Make the menu wrap into two rows on narrow screens.
2. Add a dropdown sub-menu with :hover and :focus-within.
3. Make the header sticky.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village

Field	Value
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 43: Navigation bar for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 1 | Files: index.html, styles.css

Brief

Build a horizontal navigation bar from an unordered list, with a logo on the left, links on the right and a highlighted current page.

Learning goals

- Turn a list into a horizontal menu with Flexbox
- Mark the current page with aria-current
- Style hover and keyboard focus states

Elements and CSS used

HTML elements	CSS features
header, a, nav, ul, li, main, h1, p	display: flex, justify-content, gap, list-style, text-decoration, :hover, :focus-visible, attribute selector

Build guide

1. Write the header with a logo link and a <nav> containing a <ul> of links.
2. Add aria-current="page" to the link for the current page.
3. Make the header a flex container with space-between.
4. Remove list bullets and padding; make the list itself a flex row.
5. Give each link padding and a hover/focus background.

6. Tab through the links with the keyboard and confirm the focus style is visible.

Project 43: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - Navigation</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="site-header">
    <a class="logo" href="index.html">Cleopatra Beauty Salon</a>
    <nav aria-label="Main">
      <ul class="nav">
        <li><a href="index.html" aria-current="page">Home</a></li>
        <li><a href="treatments.html">Treatments</a></li>
        <li><a href="about.html">About</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main>
    <h1>Welcome to Cleopatra Beauty Salon</h1>
    <p>Hair, nails and skin care.</p>
  </main>
</body>
</html>
```

Project 43: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.site-header { display: flex; flex-wrap: wrap; align-items: center;
justify-content: space-between; gap: 1rem; padding: .75rem 1.5rem;
background: var(--brand); }
.logo { color: #fff; font-weight: bold; font-size: 1.25rem; text-
decoration: none; }
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { display: block; padding: .5rem .9rem; color: #fff; text-
decoration: none; border-radius: 6px; }
.nav a:hover, .nav a:focus-visible { background: rgb(255 255 255 /
20%); }
.nav a[aria-current="page"] { background: rgb(0 0 0 / 25%); }
main { padding: 2rem 1.5rem; }
```

Project 43 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - Navigation</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
<ul class="nav">	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Treatments	One list item.
<main>	The unique content of this page; exactly one per page.
Welcome to Cleopatra Beauty Salon	The main heading; only one per page.
Hair, nails and skin care.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
gap: 1rem;	Space between grid or flex items without extra margins.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.

Declaration	What it does
font-weight: bold;	Thickness of the text.
font-size: 1.25rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
.nav a:hover, .nav a:focus-visible {	Applies while the pointer is over the element.
.nav a[aria-current="page"] {	Attribute selector: styles the current page or step.

Check your work

- Links are inside <nav> with an aria-label
- Bullets removed
- Current page visibly different
- Focus visible with keyboard

Exercises

1. Make the menu wrap into two rows on narrow screens.
2. Add a dropdown sub-menu with :hover and :focus-within.
3. Make the header sticky.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki

Field	Value
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 44: Navigation bar for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 1 | Files: index.html, styles.css

Brief

Build a horizontal navigation bar from an unordered list, with a logo on the left, links on the right and a highlighted current page.

Learning goals

- Turn a list into a horizontal menu with Flexbox
- Mark the current page with aria-current
- Style hover and keyboard focus states

Elements and CSS used

HTML elements	CSS features
header, a, nav, ul, li, main, h1, p	display: flex, justify-content, gap, list-style, text-decoration, :hover, :focus-visible, attribute selector

Build guide

1. Write the header with a logo link and a <nav> containing a <ul> of links.
2. Add aria-current="page" to the link for the current page.
3. Make the header a flex container with space-between.
4. Remove list bullets and padding; make the list itself a flex row.
5. Give each link padding and a hover/focus background.
6. Tab through the links with the keyboard and confirm the focus style is visible.

Project 44: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - Navigation</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="site-header">
    <a class="logo" href="index.html">Suez Auto Service</a>
    <nav aria-label="Main">
      <ul class="nav">
        <li><a href="index.html" aria-current="page">Home</a></li>
        <li><a href="services.html">Services</a></li>
        <li><a href="about.html">About</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main>
    <h1>Welcome to Suez Auto Service</h1>
    <p>Honest car servicing and repairs.</p>
  </main>
</body>
</html>
```

Project 44: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.site-header { display: flex; flex-wrap: wrap; align-items: center;
justify-content: space-between; gap: 1rem; padding: .75rem 1.5rem;
background: var(--brand); }
.logo { color: #fff; font-weight: bold; font-size: 1.25rem; text-
decoration: none; }
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { display: block; padding: .5rem .9rem; color: #fff; text-
decoration: none; border-radius: 6px; }
.nav a:hover, .nav a:focus-visible { background: rgb(255 255 255 /
20%); }
.nav a[aria-current="page"] { background: rgb(0 0 0 / 25%); }
main { padding: 2rem 1.5rem; }
```

Project 44 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - Navigation</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
<ul class="nav">	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Services	One list item.
<main>	The unique content of this page; exactly one per page.
Welcome to Suez Auto Service	The main heading; only one per page.
Honest car servicing and repairs.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
gap: 1rem;	Space between grid or flex items without extra margins.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.

Declaration	What it does
font-weight: bold;	Thickness of the text.
font-size: 1.25rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
.nav a:hover, .nav a:focus-visible {	Applies while the pointer is over the element.
.nav a[aria-current="page"] {	Attribute selector: styles the current page or step.

Check your work

- Links are inside <nav> with an aria-label
- Bullets removed
- Current page visibly different
- Focus visible with keyboard

Exercises

1. Make the menu wrap into two rows on narrow screens.
2. Add a dropdown sub-menu with :hover and :focus-within.
3. Make the header sticky.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez

Field	Value
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 45: Navigation bar for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 1 | Files: index.html, styles.css

Brief

Build a horizontal navigation bar from an unordered list, with a logo on the left, links on the right and a highlighted current page.

Learning goals

- Turn a list into a horizontal menu with Flexbox
- Mark the current page with aria-current
- Style hover and keyboard focus states

Elements and CSS used

HTML elements	CSS features
header, a, nav, ul, li, main, h1, p	display: flex, justify-content, gap, list-style, text-decoration, :hover, :focus-visible, attribute selector

Build guide

1. Write the header with a logo link and a <nav> containing a <ul> of links.
2. Add aria-current="page" to the link for the current page.
3. Make the header a flex container with space-between.
4. Remove list bullets and padding; make the list itself a flex row.
5. Give each link padding and a hover/focus background.
6. Tab through the links with the keyboard and confirm the focus style is visible.

Project 45: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - Navigation</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="site-header">
    <a class="logo" href="index.html">Luxor Music Academy</a>
    <nav aria-label="Main">
      <ul class="nav">
        <li><a href="index.html" aria-current="page">Home</a></li>
        <li><a href="courses.html">Courses</a></li>
        <li><a href="about.html">About</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main>
    <h1>Welcome to Luxor Music Academy</h1>
    <p>Oud, piano, guitar and voice lessons.</p>
  </main>
</body>
</html>
```

Project 45: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.site-header { display: flex; flex-wrap: wrap; align-items: center;
justify-content: space-between; gap: 1rem; padding: .75rem 1.5rem;
background: var(--brand); }
.logo { color: #fff; font-weight: bold; font-size: 1.25rem; text-
decoration: none; }
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { display: block; padding: .5rem .9rem; color: #fff; text-
decoration: none; border-radius: 6px; }
.nav a:hover, .nav a:focus-visible { background: rgb(255 255 255 /
20%); }
.nav a[aria-current="page"] { background: rgb(0 0 0 / 25%); }
main { padding: 2rem 1.5rem; }
```

Project 45 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - Navigation</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
<ul class="nav">	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Courses	One list item.
<main>	The unique content of this page; exactly one per page.
Welcome to Luxor Music Academy	The main heading; only one per page.
Oud, piano, guitar and voice lessons.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
gap: 1rem;	Space between grid or flex items without extra margins.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.

Declaration	What it does
font-weight: bold;	Thickness of the text.
font-size: 1.25rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
.nav a:hover, .nav a:focus-visible {	Applies while the pointer is over the element.
.nav a[aria-current="page"] {	Attribute selector: styles the current page or step.

Check your work

- Links are inside <nav> with an aria-label
- Bullets removed
- Current page visibly different
- Focus visible with keyboard

Exercises

1. Make the menu wrap into two rows on narrow screens.
2. Add a dropdown sub-menu with :hover and :focus-within.
3. Make the header sticky.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor

Field	Value
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 46: Navigation bar for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 1 | Files: index.html, styles.css

Brief

Build a horizontal navigation bar from an unordered list, with a logo on the left, links on the right and a highlighted current page.

Learning goals

- Turn a list into a horizontal menu with Flexbox
- Mark the current page with aria-current
- Style hover and keyboard focus states

Elements and CSS used

HTML elements	CSS features
header, a, nav, ul, li, main, h1, p	display: flex, justify-content, gap, list-style, text-decoration, :hover, :focus-visible, attribute selector

Build guide

1. Write the header with a logo link and a <nav> containing a <ul> of links.
2. Add aria-current="page" to the link for the current page.
3. Make the header a flex container with space-between.
4. Remove list bullets and padding; make the list itself a flex row.
5. Give each link padding and a hover/focus background.
6. Tab through the links with the keyboard and confirm the focus style is visible.

Project 46: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - Navigation</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="site-header">
    <a class="logo" href="index.html">Port Said Seafood</a>
    <nav aria-label="Main">
      <ul class="nav">
        <li><a href="index.html" aria-current="page">Home</a></li>
        <li><a href="dishes.html">Dishes</a></li>
        <li><a href="about.html">About</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main>
    <h1>Welcome to Port Said Seafood</h1>
    <p>Grilled fish straight from the boats.</p>
  </main>
</body>
</html>
```

Project 46: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.site-header { display: flex; flex-wrap: wrap; align-items: center;
justify-content: space-between; gap: 1rem; padding: .75rem 1.5rem;
background: var(--brand); }
.logo { color: #fff; font-weight: bold; font-size: 1.25rem; text-
decoration: none; }
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { display: block; padding: .5rem .9rem; color: #fff; text-
decoration: none; border-radius: 6px; }
.nav a:hover, .nav a:focus-visible { background: rgb(255 255 255 /
20%); }
.nav a[aria-current="page"] { background: rgb(0 0 0 / 25%); }
main { padding: 2rem 1.5rem; }
```

Project 46 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - Navigation</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
<ul class="nav">	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Dishes	One list item.
<main>	The unique content of this page; exactly one per page.
Welcome to Port Said Seafood	The main heading; only one per page.
Grilled fish straight from the boats.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
gap: 1rem;	Space between grid or flex items without extra margins.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.

Declaration	What it does
font-weight: bold;	Thickness of the text.
font-size: 1.25rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
.nav a:hover, .nav a:focus-visible {	Applies while the pointer is over the element.
.nav a[aria-current="page"] {	Attribute selector: styles the current page or step.

Check your work

- Links are inside <nav> with an aria-label
- Bullets removed
- Current page visibly different
- Focus visible with keyboard

Exercises

1. Make the menu wrap into two rows on narrow screens.
2. Add a dropdown sub-menu with :hover and :focus-within.
3. Make the header sticky.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said

Field	Value
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 47: Navigation bar for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 1 | Files: index.html, styles.css

Brief

Build a horizontal navigation bar from an unordered list, with a logo on the left, links on the right and a highlighted current page.

Learning goals

- Turn a list into a horizontal menu with Flexbox
- Mark the current page with aria-current
- Style hover and keyboard focus states

Elements and CSS used

HTML elements	CSS features
header, a, nav, ul, li, main, h1, p	display: flex, justify-content, gap, list-style, text-decoration, :hover, :focus-visible, attribute selector

Build guide

1. Write the header with a logo link and a <nav> containing a <ul> of links.
2. Add aria-current="page" to the link for the current page.
3. Make the header a flex container with space-between.
4. Remove list bullets and padding; make the list itself a flex row.
5. Give each link padding and a hover/focus background.
6. Tab through the links with the keyboard and confirm the focus style is visible.

Project 47: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - Navigation</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="site-header">
    <a class="logo" href="index.html">Delta Kids Library</a>
    <nav aria-label="Main">
      <ul class="nav">
        <li><a href="index.html" aria-current="page">Home</a></li>
        <li><a href="programmes.html">Programmes</a></li>
        <li><a href="about.html">About</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main>
    <h1>Welcome to Delta Kids Library</h1>
    <p>Stories, reading clubs and homework help.</p>
  </main>
</body>
</html>
```

Project 47: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.site-header { display: flex; flex-wrap: wrap; align-items: center;
justify-content: space-between; gap: 1rem; padding: .75rem 1.5rem;
background: var(--brand); }
.logo { color: #fff; font-weight: bold; font-size: 1.25rem; text-
decoration: none; }
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { display: block; padding: .5rem .9rem; color: #fff; text-
decoration: none; border-radius: 6px; }
.nav a:hover, .nav a:focus-visible { background: rgb(255 255 255 /
20%); }
.nav a[aria-current="page"] { background: rgb(0 0 0 / 25%); }
main { padding: 2rem 1.5rem; }
```

Project 47 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - Navigation</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
<ul class="nav">	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Programmes	One list item.
<main>	The unique content of this page; exactly one per page.
Welcome to Delta Kids Library	The main heading; only one per page.
Stories, reading clubs and homework help.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
gap: 1rem;	Space between grid or flex items without extra margins.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.

Declaration	What it does
font-weight: bold;	Thickness of the text.
font-size: 1.25rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
.nav a:hover, .nav a:focus-visible {	Applies while the pointer is over the element.
.nav a[aria-current="page"] {	Attribute selector: styles the current page or step.

Check your work

- Links are inside <nav> with an aria-label
- Bullets removed
- Current page visibly different
- Focus visible with keyboard

Exercises

1. Make the menu wrap into two rows on narrow screens.
2. Add a dropdown sub-menu with :hover and :focus-within.
3. Make the header sticky.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta

Field	Value
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 48: Navigation bar for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Build a horizontal navigation bar from an unordered list, with a logo on the left, links on the right and a highlighted current page.

Learning goals

- Turn a list into a horizontal menu with Flexbox
- Mark the current page with aria-current
- Style hover and keyboard focus states

Elements and CSS used

HTML elements	CSS features
header, a, nav, ul, li, main, h1, p	display: flex, justify-content, gap, list-style, text-decoration, :hover, :focus-visible, attribute selector

Build guide

1. Write the header with a logo link and a <nav> containing a <ul> of links.
2. Add aria-current="page" to the link for the current page.
3. Make the header a flex container with space-between.
4. Remove list bullets and padding; make the list itself a flex row.
5. Give each link padding and a hover/focus background.
6. Tab through the links with the keyboard and confirm the focus style is visible.

Project 48: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - Navigation</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="site-header">
    <a class="logo" href="index.html">Nubian Guest House</a>
    <nav aria-label="Main">
      <ul class="nav">
        <li><a href="index.html" aria-current="page">Home</a></li>
        <li><a href="rooms.html">Rooms</a></li>
        <li><a href="about.html">About</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main>
    <h1>Welcome to Nubian Guest House</h1>
    <p>Colourful rooms on the west bank of the Nile.</p>
  </main>
</body>
</html>
```

Project 48: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.site-header { display: flex; flex-wrap: wrap; align-items: center;
justify-content: space-between; gap: 1rem; padding: .75rem 1.5rem;
background: var(--brand); }
.logo { color: #fff; font-weight: bold; font-size: 1.25rem; text-
decoration: none; }
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { display: block; padding: .5rem .9rem; color: #fff; text-
decoration: none; border-radius: 6px; }
.nav a:hover, .nav a:focus-visible { background: rgb(255 255 255 /
20%); }
.nav a[aria-current="page"] { background: rgb(0 0 0 / 25%); }
main { padding: 2rem 1.5rem; }
```

Project 48 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - Navigation</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
<ul class="nav">	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Rooms	One list item.
<main>	The unique content of this page; exactly one per page.
Welcome to Nubian Guest House	The main heading; only one per page.
Colourful rooms on the west bank of the Nile.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
gap: 1rem;	Space between grid or flex items without extra margins.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.

Declaration	What it does
font-weight: bold;	Thickness of the text.
font-size: 1.25rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
.nav a:hover, .nav a:focus-visible {	Applies while the pointer is over the element.
.nav a[aria-current="page"] {	Attribute selector: styles the current page or step.

Check your work

- Links are inside <nav> with an aria-label
- Bullets removed
- Current page visibly different
- Focus visible with keyboard

Exercises

1. Make the menu wrap into two rows on narrow screens.
2. Add a dropdown sub-menu with :hover and :focus-within.
3. Make the header sticky.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan

Field	Value
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 49: Navigation bar for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 1 | Files: index.html, styles.css

Brief

Build a horizontal navigation bar from an unordered list, with a logo on the left, links on the right and a highlighted current page.

Learning goals

- Turn a list into a horizontal menu with Flexbox
- Mark the current page with aria-current
- Style hover and keyboard focus states

Elements and CSS used

HTML elements	CSS features
header, a, nav, ul, li, main, h1, p	display: flex, justify-content, gap, list-style, text-decoration, :hover, :focus-visible, attribute selector

Build guide

1. Write the header with a logo link and a <nav> containing a <ul> of links.
2. Add aria-current="page" to the link for the current page.
3. Make the header a flex container with space-between.
4. Remove list bullets and padding; make the list itself a flex row.
5. Give each link padding and a hover/focus background.

6. Tab through the links with the keyboard and confirm the focus style is visible.

Project 49: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - Navigation</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="site-header">
    <a class="logo" href="index.html">Ismailia Cycling Store</a>
    <nav aria-label="Main">
      <ul class="nav">
        <li><a href="index.html" aria-current="page">Home</a></li>
        <li><a href="bikes.html">Bikes</a></li>
        <li><a href="about.html">About</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main>
    <h1>Welcome to Ismailia Cycling Store</h1>
    <p>Bikes, parts and Friday group rides.</p>
  </main>
</body>
</html>
```

Project 49: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.site-header { display: flex; flex-wrap: wrap; align-items: center;
justify-content: space-between; gap: 1rem; padding: .75rem 1.5rem;
background: var(--brand); }
.logo { color: #fff; font-weight: bold; font-size: 1.25rem; text-
decoration: none; }
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { display: block; padding: .5rem .9rem; color: #fff; text-
decoration: none; border-radius: 6px; }
.nav a:hover, .nav a:focus-visible { background: rgb(255 255 255 /
20%); }
.nav a[aria-current="page"] { background: rgb(0 0 0 / 25%); }
main { padding: 2rem 1.5rem; }
```

Project 49 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - Navigation</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
<ul class="nav">	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Bikes	One list item.
<main>	The unique content of this page; exactly one per page.
Welcome to Ismailia Cycling Store	The main heading; only one per page.
Bikes, parts and Friday group rides.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
gap: 1rem;	Space between grid or flex items without extra margins.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.

Declaration	What it does
font-weight: bold;	Thickness of the text.
font-size: 1.25rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
.nav a:hover, .nav a:focus-visible {	Applies while the pointer is over the element.
.nav a[aria-current="page"] {	Attribute selector: styles the current page or step.

Check your work

- Links are inside <nav> with an aria-label
- Bullets removed
- Current page visibly different
- Focus visible with keyboard

Exercises

1. Make the menu wrap into two rows on narrow screens.
2. Add a dropdown sub-menu with :hover and :focus-within.
3. Make the header sticky.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia

Field	Value
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 50: Navigation bar for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 1 | Files: index.html, styles.css

Brief

Build a horizontal navigation bar from an unordered list, with a logo on the left, links on the right and a highlighted current page.

Learning goals

- Turn a list into a horizontal menu with Flexbox
- Mark the current page with aria-current
- Style hover and keyboard focus states

Elements and CSS used

HTML elements	CSS features
header, a, nav, ul, li, main, h1, p	display: flex, justify-content, gap, list-style, text-decoration, :hover, :focus-visible, attribute selector

Build guide

1. Write the header with a logo link and a <nav> containing a <ul> of links.
2. Add aria-current="page" to the link for the current page.
3. Make the header a flex container with space-between.
4. Remove list bullets and padding; make the list itself a flex row.
5. Give each link padding and a hover/focus background.
6. Tab through the links with the keyboard and confirm the focus style is visible.

Project 50: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - Navigation</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="site-header">
    <a class="logo" href="index.html">Minya Coding Club</a>
    <nav aria-label="Main">
      <ul class="nav">
        <li><a href="index.html" aria-current="page">Home</a></li>
        <li><a href="workshops.html">Workshops</a></li>
        <li><a href="about.html">About</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main>
    <h1>Welcome to Minya Coding Club</h1>
    <p>Free weekend coding for teenagers.</p>
  </main>
</body>
</html>
```

Project 50: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.site-header { display: flex; flex-wrap: wrap; align-items: center;
justify-content: space-between; gap: 1rem; padding: .75rem 1.5rem;
background: var(--brand); }
.logo { color: #fff; font-weight: bold; font-size: 1.25rem; text-
decoration: none; }
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { display: block; padding: .5rem .9rem; color: #fff; text-
decoration: none; border-radius: 6px; }
.nav a:hover, .nav a:focus-visible { background: rgb(255 255 255 /
20%); }
.nav a[aria-current="page"] { background: rgb(0 0 0 / 25%); }
main { padding: 2rem 1.5rem; }
```

Project 50 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - Navigation</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
<ul class="nav">	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Workshops	One list item.
<main>	The unique content of this page; exactly one per page.
Welcome to Minya Coding Club	The main heading; only one per page.
Free weekend coding for teenagers.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
gap: 1rem;	Space between grid or flex items without extra margins.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.

Declaration	What it does
font-weight: bold;	Thickness of the text.
font-size: 1.25rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
.nav a:hover, .nav a:focus-visible {	Applies while the pointer is over the element.
.nav a[aria-current="page"] {	Attribute selector: styles the current page or step.

Check your work

- Links are inside <nav> with an aria-label
- Bullets removed
- Current page visibly different
- Focus visible with keyboard

Exercises

1. Make the menu wrap into two rows on narrow screens.
2. Add a dropdown sub-menu with :hover and :focus-within.
3. Make the header sticky.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya

Field	Value
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Price table

Level 1 | 25 projects, one per theme

Present the four main offers in an accessible data table with a caption, column and row headers, zebra stripes and a scroll wrapper for phones.

Project 51: Price table for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 1 | Files: index.html, styles.css

Brief

Present the four main offers in an accessible data table with a caption, column and row headers, zebra stripes and a scroll wrapper for phones.

Learning goals

- Structure a table with caption, thead, tbody, th scope
- Collapse borders and stripe rows
- Keep tables usable on small screens

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, div	border-collapse, padding, :nth-child(even), text-align, overflow-x, white-space

Build guide

1. Write the table markup with a caption and a thead row of th scope="col".
2. Add one tbody row per offer; the first cell is th scope="row".
3. Wrap the table in .
4. Collapse borders, add padding and a bottom border to cells.
5. Colour the header row and stripe the even rows.
6. Right-align the price column and stop it wrapping.

Project 51: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Prices</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cairo Book Shop price list</h1>
    <div class="table-wrapper">
      <table>
        <caption>Books and prices, 2026</caption>
        <thead>
          <tr><th scope="col">Book</th><th scope="col">Description</
th><th scope="col">Price</th></tr>
        </thead>
        <tbody>
        <tr><th scope="row">Learn HTML</th><td>From your first tag to
a complete page</td><td class="num">120 EGP</td></tr>
        <tr><th scope="row">CSS in Practice</th><td>Layouts, colours
and typography</td><td class="num">150 EGP</td></tr>
        <tr><th scope="row">JavaScript Basics</th><td>Make pages
interactive</td><td class="num">180 EGP</td></tr>
        <tr><th scope="row">Web Accessibility</th><td>Pages everyone
can use</td><td class="num">95 EGP</td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 51: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 50rem; margin: 2rem auto; padding: 0 1rem; }
.table-wrapper { overflow-x: auto; }
table { width: 100%; border-collapse: collapse; }
caption { text-align: left; padding: .5rem 0; color: var(--muted); }
th, td { padding: .75rem 1rem; text-align: left; border-bottom: 1px
solid var(--line); }
```

```
thead th { background: var(--brand); color: #fff; }
tbody tr:nth-child(even) { background: var(--accent); }
tbody th { font-weight: 600; }
.num { text-align: right; font-variant-numeric: tabular-nums; white-
space: nowrap; }
```

Project 51 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - Prices</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cairo Book Shop price list	The main heading; only one per page.
	Generic block container for grouping and layout.
<table>	Tabular data in rows and columns.
<caption>Books and prices, 2026</caption>	Title of the table.
<thead>	Group of header rows.
<tr><th scope="col">Book</th><th scope="col">Description</th><th sc...	A table row.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">Learn HTML</th><td>From your first tag to a com...	Header cell for a row.
<tr><th scope="row">CSS in Practice</th><td>Layouts, colours and ty...	A header cell.
<tr><th scope="row">JavaScript Basics</th><td>Make pages interactiv...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
background: var(--brand);	Background colour or image.
tbody tr:nth-child(even) {	Every second element: zebra striping.
font-weight: 600;	Thickness of the text.
text-align: right;	Right-aligns inline content, typical for numbers.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Every header cell has scope
- Caption describes the table
- Table scrolls instead of overflowing on a phone
- Numbers right-aligned

Exercises

1. Add a tfoot row with a total.
2. Highlight a row on hover.
3. Make the header row sticky with position: sticky.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 52: Price table for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 1 | Files: index.html, styles.css

Brief

Present the four main offers in an accessible data table with a caption, column and row headers, zebra stripes and a scroll wrapper for phones.

Learning goals

- Structure a table with caption, thead, tbody, th scope
- Collapse borders and stripe rows
- Keep tables usable on small screens

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, div	border-collapse, padding, :nth-child(even), text-align, overflow-x, white-space

Build guide

1. Write the table markup with a caption and a thead row of th scope="col".
2. Add one tbody row per offer; the first cell is th scope="row".
3. Wrap the table in .
4. Collapse borders, add padding and a bottom border to cells.
5. Colour the header row and stripe the even rows.
6. Right-align the price column and stop it wrapping.

Project 52: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - Prices</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Nile Bakery price list</h1>
    <div class="table-wrapper">
      <table>
        <caption>Pastries and prices, 2026</caption>
        <thead>
          <tr><th scope="col">Pastry</th><th scope="col">Description</
th><th scope="col">Price</th></tr>
        </thead>
        <tbody>
        <tr><th scope="row">Sourdough loaf</th><td>Slow fermented,
crisp crust</td><td class="num">60 EGP</td></tr>
        <tr><th scope="row">Croissant</th><td>Butter, 27 layers</
td><td class="num">35 EGP</td></tr>
        <tr><th scope="row">Date cookies</th><td>Traditional maamoul
style</td><td class="num">80 EGP</td></tr>
        <tr><th scope="row">Baklava box</th><td>Pistachio and honey</
td><td class="num">220 EGP</td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 52: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 50rem; margin: 2rem auto; padding: 0 1rem; }
.table-wrapper { overflow-x: auto; }
table { width: 100%; border-collapse: collapse; }
caption { text-align: left; padding: .5rem 0; color: var(--muted); }
th, td { padding: .75rem 1rem; text-align: left; border-bottom: 1px
solid var(--line); }
```

```
thead th { background: var(--brand); color: #fff; }
tbody tr:nth-child(even) { background: var(--accent); }
tbody th { font-weight: 600; }
.num { text-align: right; font-variant-numeric: tabular-nums; white-
space: nowrap; }
```

Project 52 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - Prices</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Nile Bakery price list	The main heading; only one per page.
	Generic block container for grouping and layout.
<table>	Tabular data in rows and columns.
<caption>Pastries and prices, 2026</caption>	Title of the table.
<thead>	Group of header rows.
<tr><th scope="col">Pastry</th><th scope="col">Description</th><th ...	A table row.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">Sourdough loaf</th><td>Slow fermented, crisp cr...	Header cell for a row.
<tr><th scope="row">Croissant</th><td>Butter, 27 layers</td><td cla...	A header cell.
<tr><th scope="row">Date cookies</th><td>Traditional maamoul style<...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
background: var(--brand);	Background colour or image.
tbody tr:nth-child(even) {	Every second element: zebra striping.
font-weight: 600;	Thickness of the text.
text-align: right;	Right-aligns inline content, typical for numbers.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Every header cell has scope
- Caption describes the table
- Table scrolls instead of overflowing on a phone
- Numbers right-aligned

Exercises

1. Add a tfoot row with a total.
2. Highlight a row on hover.
3. Make the header row sticky with position: sticky.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 53: Price table for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 1 | Files: index.html, styles.css

Brief

Present the four main offers in an accessible data table with a caption, column and row headers, zebra stripes and a scroll wrapper for phones.

Learning goals

- Structure a table with caption, thead, tbody, th scope
- Collapse borders and stripe rows
- Keep tables usable on small screens

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, div	border-collapse, padding, :nth-child(even), text-align, overflow-x, white-space

Build guide

1. Write the table markup with a caption and a thead row of th scope="col".
2. Add one tbody row per offer; the first cell is th scope="row".
3. Wrap the table in .
4. Collapse borders, add padding and a bottom border to cells.
5. Colour the header row and stripe the even rows.

6. Right-align the price column and stop it wrapping.

Project 53: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - Prices</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Pyramid Fitness price list</h1>
    <div class="table-wrapper">
      <table>
        <caption>Classes and prices, 2026</caption>
        <thead>
          <tr><th scope="col">Class</th><th scope="col">Description</
th><th scope="col">Price</th></tr>
        </thead>
        <tbody>
        <tr><th scope="row">Morning yoga</th><td>Flexibility and calm,
 60 minutes</td><td class="num">100 EGP</td></tr>
        <tr><th scope="row">Strength circuit</th><td>Full body, all
levels</td><td class="num">120 EGP</td></tr>
        <tr><th scope="row">Spinning</th><td>High energy cycling</
td><td class="num">110 EGP</td></tr>
        <tr><th scope="row">Personal training</th><td>One to one
coaching</td><td class="num">350 EGP</td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 53: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 50rem; margin: 2rem auto; padding: 0 1rem; }
.table-wrapper { overflow-x: auto; }
table { width: 100%; border-collapse: collapse; }
caption { text-align: left; padding: .5rem 0; color: var(--muted); }
th, td { padding: .75rem 1rem; text-align: left; border-bottom: 1px
solid var(--line); }
```

```
thead th { background: var(--brand); color: #fff; }
tbody tr:nth-child(even) { background: var(--accent); }
tbody th { font-weight: 600; }
.num { text-align: right; font-variant-numeric: tabular-nums; white-
space: nowrap; }
```

Project 53 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - Prices</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Pyramid Fitness price list	The main heading; only one per page.
	Generic block container for grouping and layout.
<table>	Tabular data in rows and columns.
<caption>Classes and prices, 2026</caption>	Title of the table.
<thead>	Group of header rows.
<tr><th scope="col">Class</th><th scope="col">Description</th><th s...	A table row.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">Morning yoga</th><td>Flexibility and calm, 60 m...	Header cell for a row.
<tr><th scope="row">Strength circuit</th><td>Full body, all levels<...	A header cell.
<tr><th scope="row">Spinning</th><td>High energy cycling</td><td cl...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
background: var(--brand);	Background colour or image.
tbody tr:nth-child(even) {	Every second element: zebra striping.
font-weight: 600;	Thickness of the text.
text-align: right;	Right-aligns inline content, typical for numbers.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Every header cell has scope
- Caption describes the table
- Table scrolls instead of overflowing on a phone
- Numbers right-aligned

Exercises

1. Add a tfoot row with a total.
2. Highlight a row on hover.
3. Make the header row sticky with position: sticky.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 54: Price table for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 1 | Files: index.html, styles.css

Brief

Present the four main offers in an accessible data table with a caption, column and row headers, zebra stripes and a scroll wrapper for phones.

Learning goals

- Structure a table with caption, thead, tbody, th scope
- Collapse borders and stripe rows
- Keep tables usable on small screens

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, div	border-collapse, padding, :nth-child(even), text-align, overflow-x, white-space

Build guide

1. Write the table markup with a caption and a thead row of th scope="col".
2. Add one tbody row per offer; the first cell is th scope="row".
3. Wrap the table in .
4. Collapse borders, add padding and a bottom border to cells.
5. Colour the header row and stripe the even rows.
6. Right-align the price column and stop it wrapping.

Project 54: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - Prices</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Delta Dental Clinic price list</h1>
    <div class="table-wrapper">
      <table>
        <caption>Services and prices, 2026</caption>
        <thead>
          <tr><th scope="col">Service</th><th
scope="col">Description</th><th scope="col">Price</th></tr>
        </thead>
        <tbody>
        <tr><th scope="row">Check-up</th><td>Examination and
cleaning</td><td class="num">300 EGP</td></tr>
        <tr><th scope="row">Whitening</th><td>Brighter smile in one
visit</td><td class="num">1500 EGP</td></tr>
        <tr><th scope="row">Filling</th><td>Tooth-coloured composite</
td><td class="num">600 EGP</td></tr>
        <tr><th scope="row">Braces consultation</th><td>Plan your
treatment</td><td class="num">Free</td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 54: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 50rem; margin: 2rem auto; padding: 0 1rem; }
.table-wrapper { overflow-x: auto; }
table { width: 100%; border-collapse: collapse; }
caption { text-align: left; padding: .5rem 0; color: var(--muted); }
th, td { padding: .75rem 1rem; text-align: left; border-bottom: 1px
solid var(--line); }
```

```
thead th { background: var(--brand); color: #fff; }
tbody tr:nth-child(even) { background: var(--accent); }
tbody th { font-weight: 600; }
.num { text-align: right; font-variant-numeric: tabular-nums; white-
space: nowrap; }
```

Project 54 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - Prices</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Delta Dental Clinic price list	The main heading; only one per page.
	Generic block container for grouping and layout.
<table>	Tabular data in rows and columns.
<caption>Services and prices, 2026</caption>	Title of the table.
<thead>	Group of header rows.
<tr><th scope="col">Service</th><th scope="col">Description</th><th...	A table row.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">Check-up</th><td>Examination and cleaning</td><...	Header cell for a row.
<tr><th scope="row">Whitening</th><td>Brighter smile in one visit<//...	A header cell.
<tr><th scope="row">Filling</th><td>Tooth-coloured composite</td><t...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
background: var(--brand);	Background colour or image.
tbody tr:nth-child(even) {	Every second element: zebra striping.
font-weight: 600;	Thickness of the text.
text-align: right;	Right-aligns inline content, typical for numbers.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Every header cell has scope
- Caption describes the table
- Table scrolls instead of overflowing on a phone
- Numbers right-aligned

Exercises

1. Add a tfoot row with a total.
2. Highlight a row on hover.
3. Make the header row sticky with position: sticky.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 55: Price table for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 1 | Files: index.html, styles.css

Brief

Present the four main offers in an accessible data table with a caption, column and row headers, zebra stripes and a scroll wrapper for phones.

Learning goals

- Structure a table with caption, thead, tbody, th scope
- Collapse borders and stripe rows
- Keep tables usable on small screens

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, div	border-collapse, padding, :nth-child(even), text-align, overflow-x, white-space

Build guide

1. Write the table markup with a caption and a thead row of th scope="col".
2. Add one tbody row per offer; the first cell is th scope="row".
3. Wrap the table in .
4. Collapse borders, add padding and a bottom border to cells.
5. Colour the header row and stripe the even rows.
6. Right-align the price column and stop it wrapping.

Project 55: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - Prices</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Red Sea Travel price list</h1>
    <div class="table-wrapper">
      <table>
        <caption>Tours and prices, 2026</caption>
        <thead>
          <tr><th scope="col">Tour</th><th scope="col">Description</
th><th scope="col">Price</th></tr>
        </thead>
        <tbody>
        <tr><th scope="row">Luxor day trip</th><td>Karnak, Valley of
the Kings</td><td class="num">1200 EGP</td></tr>
        <tr><th scope="row">Snorkelling</th><td>Giftun island reefs</
td><td class="num">700 EGP</td></tr>
        <tr><th scope="row">Desert safari</th><td>Quad bikes and
Bedouin dinner</td><td class="num">900 EGP</td></tr>
        <tr><th scope="row">Nile cruise</th><td>Three nights Aswan to
Luxor</td><td class="num">6500 EGP</td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 55: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 50rem; margin: 2rem auto; padding: 0 1rem; }
.table-wrapper { overflow-x: auto; }
table { width: 100%; border-collapse: collapse; }
caption { text-align: left; padding: .5rem 0; color: var(--muted); }
th, td { padding: .75rem 1rem; text-align: left; border-bottom: 1px
solid var(--line); }
```

```
thead th { background: var(--brand); color: #fff; }
tbody tr:nth-child(even) { background: var(--accent); }
tbody th { font-weight: 600; }
.num { text-align: right; font-variant-numeric: tabular-nums; white-
space: nowrap; }
```

Project 55 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - Prices</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Red Sea Travel price list	The main heading; only one per page.
	Generic block container for grouping and layout.
<table>	Tabular data in rows and columns.
<caption>Tours and prices, 2026</caption>	Title of the table.
<thead>	Group of header rows.
<tr><th scope="col">Tour</th><th scope="col">Description</th><th sc...	A table row.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">Luxor day trip</th><td>Karnak, Valley of the Ki...	Header cell for a row.
<tr><th scope="row">Snorkelling</th><td>Giftun island reefs</td><td...	A header cell.
<tr><th scope="row">Desert safari</th><td>Quad bikes and Bedouin di...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
background: var(--brand);	Background colour or image.
tbody tr:nth-child(even) {	Every second element: zebra striping.
font-weight: 600;	Thickness of the text.
text-align: right;	Right-aligns inline content, typical for numbers.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Every header cell has scope
- Caption describes the table
- Table scrolls instead of overflowing on a phone
- Numbers right-aligned

Exercises

1. Add a tfoot row with a total.
2. Highlight a row on hover.
3. Make the header row sticky with position: sticky.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 56: Price table for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Present the four main offers in an accessible data table with a caption, column and row headers, zebra stripes and a scroll wrapper for phones.

Learning goals

- Structure a table with caption, thead, tbody, th scope
- Collapse borders and stripe rows
- Keep tables usable on small screens

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, div	border-collapse, padding, :nth-child(even), text-align, overflow-x, white-space

Build guide

1. Write the table markup with a caption and a thead row of th scope="col".
2. Add one tbody row per offer; the first cell is th scope="row".
3. Wrap the table in .
4. Collapse borders, add padding and a bottom border to cells.
5. Colour the header row and stripe the even rows.

6. Right-align the price column and stop it wrapping.

Project 56: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - Prices</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Lotus Language School price list</h1>
    <div class="table-wrapper">
      <table>
        <caption>Courses and prices, 2026</caption>
        <thead>
          <tr><th scope="col">Course</th><th scope="col">Description</
th><th scope="col">Price</th></tr>
        </thead>
        <tbody>
        <tr><th scope="row">English A1</th><td>Beginner, 8 weeks</
td><td class="num">1800 EGP</td></tr>
        <tr><th scope="row">French B1</th><td>Intermediate
conversation</td><td class="num">2200 EGP</td></tr>
        <tr><th scope="row">German A2</th><td>Grammar and speaking</
td><td class="num">2000 EGP</td></tr>
        <tr><th scope="row">IELTS preparation</th><td>Exam
strategies</td><td class="num">3000 EGP</td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 56: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 50rem; margin: 2rem auto; padding: 0 1rem; }
.table-wrapper { overflow-x: auto; }
table { width: 100%; border-collapse: collapse; }
caption { text-align: left; padding: .5rem 0; color: var(--muted); }
th, td { padding: .75rem 1rem; text-align: left; border-bottom: 1px
solid var(--line); }
```

```
thead th { background: var(--brand); color: #fff; }
tbody tr:nth-child(even) { background: var(--accent); }
tbody th { font-weight: 600; }
.num { text-align: right; font-variant-numeric: tabular-nums; white-
space: nowrap; }
```

Project 56 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - Prices</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Lotus Language School price list	The main heading; only one per page.
	Generic block container for grouping and layout.
<table>	Tabular data in rows and columns.
<caption>Courses and prices, 2026</caption>	Title of the table.
<thead>	Group of header rows.
<tr><th scope="col">Course</th><th scope="col">Description</th><th ...	A table row.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">English A1</th><td>Beginner, 8 weeks</td><td cl...	Header cell for a row.
<tr><th scope="row">French B1</th><td>Intermediate conversation</td...	A header cell.
<tr><th scope="row">German A2</th><td>Grammar and speaking</td><td ...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
background: var(--brand);	Background colour or image.
tbody tr:nth-child(even) {	Every second element: zebra striping.
font-weight: 600;	Thickness of the text.
text-align: right;	Right-aligns inline content, typical for numbers.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Every header cell has scope
- Caption describes the table
- Table scrolls instead of overflowing on a phone
- Numbers right-aligned

Exercises

1. Add a tfoot row with a total.
2. Highlight a row on hover.
3. Make the header row sticky with position: sticky.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 57: Price table for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 1 | Files: index.html, styles.css

Brief

Present the four main offers in an accessible data table with a caption, column and row headers, zebra stripes and a scroll wrapper for phones.

Learning goals

- Structure a table with caption, thead, tbody, th scope
- Collapse borders and stripe rows
- Keep tables usable on small screens

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, div	border-collapse, padding, :nth-child(even), text-align, overflow-x, white-space

Build guide

1. Write the table markup with a caption and a thead row of th scope="col".
2. Add one tbody row per offer; the first cell is th scope="row".
3. Wrap the table in .
4. Collapse borders, add padding and a bottom border to cells.
5. Colour the header row and stripe the even rows.
6. Right-align the price column and stop it wrapping.

Project 57: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - Prices</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Green Leaf Cafe price list</h1>
    <div class="table-wrapper">
      <table>
        <caption>Drinks and prices, 2026</caption>
        <thead>
          <tr><th scope="col">Drink</th><th scope="col">Description</
th><th scope="col">Price</th></tr>
        </thead>
        <tbody>
        <tr><th scope="row">Flat white</th><td>Double shot, silky
milk</td><td class="num">55 EGP</td></tr>
        <tr><th scope="row">Cold brew</th><td>18 hours steeped</
td><td class="num">60 EGP</td></tr>
        <tr><th scope="row">Hibiscus iced tea</th><td>Karkade with
mint</td><td class="num">40 EGP</td></tr>
        <tr><th scope="row">Cheesecake</th><td>Baked, with berries</
td><td class="num">75 EGP</td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 57: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 50rem; margin: 2rem auto; padding: 0 1rem; }
.table-wrapper { overflow-x: auto; }
table { width: 100%; border-collapse: collapse; }
caption { text-align: left; padding: .5rem 0; color: var(--muted); }
th, td { padding: .75rem 1rem; text-align: left; border-bottom: 1px
solid var(--line); }
```

```
thead th { background: var(--brand); color: #fff; }
tbody tr:nth-child(even) { background: var(--accent); }
tbody th { font-weight: 600; }
.num { text-align: right; font-variant-numeric: tabular-nums; white-
space: nowrap; }
```

Project 57 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - Prices</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Green Leaf Cafe price list	The main heading; only one per page.
	Generic block container for grouping and layout.
<table>	Tabular data in rows and columns.
<caption>Drinks and prices, 2026</caption>	Title of the table.
<thead>	Group of header rows.
<tr><th scope="col">Drink</th><th scope="col">Description</th><th s...	A table row.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">Flat white</th><td>Double shot, silky milk</td>...	Header cell for a row.
<tr><th scope="row">Cold brew</th><td>18 hours steeped</td><td clas...	A header cell.
<tr><th scope="row">Hibiscus iced tea</th><td>Karkade with mint</td...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
background: var(--brand);	Background colour or image.
tbody tr:nth-child(even) {	Every second element: zebra striping.
font-weight: 600;	Thickness of the text.
text-align: right;	Right-aligns inline content, typical for numbers.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Every header cell has scope
- Caption describes the table
- Table scrolls instead of overflowing on a phone
- Numbers right-aligned

Exercises

1. Add a tfoot row with a total.
2. Highlight a row on hover.
3. Make the header row sticky with position: sticky.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 58: Price table for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 1 | Files: index.html, styles.css

Brief

Present the four main offers in an accessible data table with a caption, column and row headers, zebra stripes and a scroll wrapper for phones.

Learning goals

- Structure a table with caption, thead, tbody, th scope
- Collapse borders and stripe rows
- Keep tables usable on small screens

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, div	border-collapse, padding, :nth-child(even), text-align, overflow-x, white-space

Build guide

1. Write the table markup with a caption and a thead row of th scope="col".
2. Add one tbody row per offer; the first cell is th scope="row".
3. Wrap the table in .
4. Collapse borders, add padding and a bottom border to cells.
5. Colour the header row and stripe the even rows.

6. Right-align the price column and stop it wrapping.

Project 58: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - Prices</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Sinai Trekking Club price list</h1>
    <div class="table-wrapper">
      <table>
        <caption>Hikes and prices, 2026</caption>
        <thead>
          <tr><th scope="col">Hike</th><th scope="col">Description</
th><th scope="col">Price</th></tr>
        </thead>
        <tbody>
        <tr><th scope="row">Mount Sinai sunrise</th><td>Night climb,
7 km</td><td class="num">400 EGP</td></tr>
        <tr><th scope="row">Blue Desert loop</th><td>Easy day walk</
td><td class="num">250 EGP</td></tr>
        <tr><th scope="row">Wadi Gnai</th><td>Palms and pools</td><td
class="num">300 EGP</td></tr>
        <tr><th scope="row">Three-day traverse</th><td>Camping under
stars</td><td class="num">1900 EGP</td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 58: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 50rem; margin: 2rem auto; padding: 0 1rem; }
.table-wrapper { overflow-x: auto; }
table { width: 100%; border-collapse: collapse; }
caption { text-align: left; padding: .5rem 0; color: var(--muted); }
th, td { padding: .75rem 1rem; text-align: left; border-bottom: 1px
solid var(--line); }
```

```
thead th { background: var(--brand); color: #fff; }
tbody tr:nth-child(even) { background: var(--accent); }
tbody th { font-weight: 600; }
.num { text-align: right; font-variant-numeric: tabular-nums; white-
space: nowrap; }
```

Project 58 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - Prices</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Sinai Trekking Club price list	The main heading; only one per page.
	Generic block container for grouping and layout.
<table>	Tabular data in rows and columns.
<caption>Hikes and prices, 2026</caption>	Title of the table.
<thead>	Group of header rows.
<tr><th scope="col">Hike</th><th scope="col">Description</th><th sc...	A table row.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">Mount Sinai sunrise</th><td>Night climb, 7 km<//...	Header cell for a row.
<tr><th scope="row">Blue Desert loop</th><td>Easy day walk</td><td ...	A header cell.
<tr><th scope="row">Wadi Gnai</th><td>Palms and pools</td><td class...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
background: var(--brand);	Background colour or image.
tbody tr:nth-child(even) {	Every second element: zebra striping.
font-weight: 600;	Thickness of the text.
text-align: right;	Right-aligns inline content, typical for numbers.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Every header cell has scope
- Caption describes the table
- Table scrolls instead of overflowing on a phone
- Numbers right-aligned

Exercises

1. Add a tfoot row with a total.
2. Highlight a row on hover.
3. Make the header row sticky with position: sticky.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 59: Price table for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 1 | Files: index.html, styles.css

Brief

Present the four main offers in an accessible data table with a caption, column and row headers, zebra stripes and a scroll wrapper for phones.

Learning goals

- Structure a table with caption, thead, tbody, th scope
- Collapse borders and stripe rows
- Keep tables usable on small screens

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, div	border-collapse, padding, :nth-child(even), text-align, overflow-x, white-space

Build guide

1. Write the table markup with a caption and a thead row of th scope="col".
2. Add one tbody row per offer; the first cell is th scope="row".
3. Wrap the table in .
4. Collapse borders, add padding and a bottom border to cells.
5. Colour the header row and stripe the even rows.
6. Right-align the price column and stop it wrapping.

Project 59: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - Prices</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Horizon Photography price list</h1>
    <div class="table-wrapper">
      <table>
        <caption>Sessions and prices, 2026</caption>
        <thead>
          <tr><th scope="col">Session</th><th
scope="col">Description</th><th scope="col">Price</th></tr>
        </thead>
        <tbody>
        <tr><th scope="row">Portrait session</th><td>One hour, 20
edited photos</td><td class="num">1200 EGP</td></tr>
        <tr><th scope="row">Wedding day</th><td>Full coverage, two
photographers</td><td class="num">15000 EGP</td></tr>
        <tr><th scope="row">Product shoot</th><td>White background,
10 items</td><td class="num">900 EGP</td></tr>
        <tr><th scope="row">Family session</th><td>Outdoor, golden
hour</td><td class="num">1500 EGP</td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 59: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 50rem; margin: 2rem auto; padding: 0 1rem; }
.table-wrapper { overflow-x: auto; }
table { width: 100%; border-collapse: collapse; }
caption { text-align: left; padding: .5rem 0; color: var(--muted); }
th, td { padding: .75rem 1rem; text-align: left; border-bottom: 1px
solid var(--line); }
```

```
thead th { background: var(--brand); color: #fff; }
tbody tr:nth-child(even) { background: var(--accent); }
tbody th { font-weight: 600; }
.num { text-align: right; font-variant-numeric: tabular-nums; white-
space: nowrap; }
```

Project 59 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - Prices</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Horizon Photography price list	The main heading; only one per page.
	Generic block container for grouping and layout.
<table>	Tabular data in rows and columns.
<caption>Sessions and prices, 2026</caption>	Title of the table.
<thead>	Group of header rows.
<tr><th scope="col">Session</th><th scope="col">Description</th><th...	A table row.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">Portrait session</th><td>One hour, 20 edited ph...	Header cell for a row.
<tr><th scope="row">Wedding day</th><td>Full coverage, two photogra...	A header cell.
<tr><th scope="row">Product shoot</th><td>White background, 10 item...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
background: var(--brand);	Background colour or image.
tbody tr:nth-child(even) {	Every second element: zebra striping.
font-weight: 600;	Thickness of the text.
text-align: right;	Right-aligns inline content, typical for numbers.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Every header cell has scope
- Caption describes the table
- Table scrolls instead of overflowing on a phone
- Numbers right-aligned

Exercises

1. Add a tfoot row with a total.
2. Highlight a row on hover.

3. Make the header row sticky with position: sticky.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 60: Price table for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 1 | Files: index.html, styles.css

Brief

Present the four main offers in an accessible data table with a caption, column and row headers, zebra stripes and a scroll wrapper for phones.

Learning goals

- Structure a table with caption, thead, tbody, th scope
- Collapse borders and stripe rows
- Keep tables usable on small screens

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, div	border-collapse, padding, :nth-child(even), text-align, overflow-x, white-space

Build guide

1. Write the table markup with a caption and a thead row of th scope="col".
2. Add one tbody row per offer; the first cell is th scope="row".
3. Wrap the table in .
4. Collapse borders, add padding and a bottom border to cells.
5. Colour the header row and stripe the even rows.
6. Right-align the price column and stop it wrapping.

Project 60: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - Prices</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Papyrus Stationery price list</h1>
    <div class="table-wrapper">
      <table>
        <caption>Products and prices, 2026</caption>
        <thead>
          <tr><th scope="col">Product</th><th
scope="col">Description</th><th scope="col">Price</th></tr>
        </thead>
        <tbody>
        <tr><th scope="row">Dotted notebook</th><td>A5, 160 pages</
td><td class="num">140 EGP</td></tr>
        <tr><th scope="row">Fountain pen</th><td>Steel nib,
refillable</td><td class="num">350 EGP</td></tr>
        <tr><th scope="row">Washi tape set</th><td>Six patterns</
td><td class="num">90 EGP</td></tr>
        <tr><th scope="row">Desk planner</th><td>Weekly, undated</
td><td class="num">110 EGP</td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 60: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 50rem; margin: 2rem auto; padding: 0 1rem; }
.table-wrapper { overflow-x: auto; }
table { width: 100%; border-collapse: collapse; }
caption { text-align: left; padding: .5rem 0; color: var(--muted); }
th, td { padding: .75rem 1rem; text-align: left; border-bottom: 1px
solid var(--line); }
```

```
thead th { background: var(--brand); color: #fff; }
tbody tr:nth-child(even) { background: var(--accent); }
tbody th { font-weight: 600; }
.num { text-align: right; font-variant-numeric: tabular-nums; white-
space: nowrap; }
```

Project 60 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - Prices</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Papyrus Stationery price list	The main heading; only one per page.
	Generic block container for grouping and layout.
<table>	Tabular data in rows and columns.
<caption>Products and prices, 2026</caption>	Title of the table.
<thead>	Group of header rows.
<tr><th scope="col">Product</th><th scope="col">Description</th><th...	A table row.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">Dotted notebook</th><td>A5, 160 pages</td><td c...	Header cell for a row.
<tr><th scope="row">Fountain pen</th><td>Steel nib, refillable</td>...	A header cell.
<tr><th scope="row">Washi tape set</th><td>Six patterns</td><td cla...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
background: var(--brand);	Background colour or image.
tbody tr:nth-child(even) {	Every second element: zebra striping.
font-weight: 600;	Thickness of the text.
text-align: right;	Right-aligns inline content, typical for numbers.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Every header cell has scope
- Caption describes the table
- Table scrolls instead of overflowing on a phone
- Numbers right-aligned

Exercises

1. Add a tfoot row with a total.
2. Highlight a row on hover.
3. Make the header row sticky with position: sticky.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 61: Price table for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 1 | Files: index.html, styles.css

Brief

Present the four main offers in an accessible data table with a caption, column and row headers, zebra stripes and a scroll wrapper for phones.

Learning goals

- Structure a table with caption, thead, tbody, th scope
- Collapse borders and stripe rows
- Keep tables usable on small screens

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, div	border-collapse, padding, :nth-child(even), text-align, overflow-x, white-space

Build guide

1. Write the table markup with a caption and a thead row of th scope="col".
2. Add one tbody row per offer; the first cell is th scope="row".
3. Wrap the table in .
4. Collapse borders, add padding and a bottom border to cells.
5. Colour the header row and stripe the even rows.

6. Right-align the price column and stop it wrapping.

Project 61: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - Prices</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Oasis Plant Nursery price list</h1>
    <div class="table-wrapper">
      <table>
        <caption>Plants and prices, 2026</caption>
        <thead>
          <tr><th scope="col">Plant</th><th scope="col">Description</
th><th scope="col">Price</th></tr>
        </thead>
        <tbody>
        <tr><th scope="row">Monstera</th><td>Large leaves, easy care</
td><td class="num">250 EGP</td></tr>
        <tr><th scope="row">Snake plant</th><td>Survives anything</
td><td class="num">120 EGP</td></tr>
        <tr><th scope="row">Basil pot</th><td>Kitchen herb</td><td
class="num">45 EGP</td></tr>
        <tr><th scope="row">Olive tree</th><td>Balcony sized</td><td
class="num">600 EGP</td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 61: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 50rem; margin: 2rem auto; padding: 0 1rem; }
.table-wrapper { overflow-x: auto; }
table { width: 100%; border-collapse: collapse; }
caption { text-align: left; padding: .5rem 0; color: var(--muted); }
th, td { padding: .75rem 1rem; text-align: left; border-bottom: 1px
solid var(--line); }
```

```
thead th { background: var(--brand); color: #fff; }
tbody tr:nth-child(even) { background: var(--accent); }
tbody th { font-weight: 600; }
.num { text-align: right; font-variant-numeric: tabular-nums; white-
space: nowrap; }
```

Project 61 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - Prices</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Oasis Plant Nursery price list	The main heading; only one per page.
	Generic block container for grouping and layout.
<table>	Tabular data in rows and columns.
<caption>Plants and prices, 2026</caption>	Title of the table.
<thead>	Group of header rows.
<tr><th scope="col">Plant</th><th scope="col">Description</th><th s...	A table row.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">Monstera</th><td>Large leaves, easy care</td><t...	Header cell for a row.
<tr><th scope="row">Snake plant</th><td>Survives anything</td><td c...	A header cell.
<tr><th scope="row">Basil pot</th><td>Kitchen herb</td><td class="n...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
background: var(--brand);	Background colour or image.
tbody tr:nth-child(even) {	Every second element: zebra striping.
font-weight: 600;	Thickness of the text.
text-align: right;	Right-aligns inline content, typical for numbers.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Every header cell has scope
- Caption describes the table
- Table scrolls instead of overflowing on a phone
- Numbers right-aligned

Exercises

1. Add a tfoot row with a total.
2. Highlight a row on hover.
3. Make the header row sticky with position: sticky.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 62: Price table for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 1 | Files: index.html, styles.css

Brief

Present the four main offers in an accessible data table with a caption, column and row headers, zebra stripes and a scroll wrapper for phones.

Learning goals

- Structure a table with caption, thead, tbody, th scope
- Collapse borders and stripe rows
- Keep tables usable on small screens

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, div	border-collapse, padding, :nth-child(even), text-align, overflow-x, white-space

Build guide

1. Write the table markup with a caption and a thead row of th scope="col".
2. Add one tbody row per offer; the first cell is th scope="row".
3. Wrap the table in .
4. Collapse borders, add padding and a bottom border to cells.
5. Colour the header row and stripe the even rows.
6. Right-align the price column and stop it wrapping.

Project 62: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - Prices</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cedar Furniture price list</h1>
    <div class="table-wrapper">
      <table>
        <caption>Pieces and prices, 2026</caption>
        <thead>
          <tr><th scope="col">Piece</th><th scope="col">Description</
th><th scope="col">Price</th></tr>
        </thead>
        <tbody>
        <tr><th scope="row">Oak dining table</th><td>Seats six</
td><td class="num">9500 EGP</td></tr>
        <tr><th scope="row">Bookshelf</th><td>Five shelves, walnut</
td><td class="num">4200 EGP</td></tr>
        <tr><th scope="row">Bedside table</th><td>One drawer</td><td
class="num">1500 EGP</td></tr>
        <tr><th scope="row">Coffee table</th><td>Round, ash wood</
td><td class="num">2800 EGP</td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 62: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 50rem; margin: 2rem auto; padding: 0 1rem; }
.table-wrapper { overflow-x: auto; }
table { width: 100%; border-collapse: collapse; }
caption { text-align: left; padding: .5rem 0; color: var(--muted); }
th, td { padding: .75rem 1rem; text-align: left; border-bottom: 1px
solid var(--line); }
```

```
thead th { background: var(--brand); color: #fff; }
tbody tr:nth-child(even) { background: var(--accent); }
tbody th { font-weight: 600; }
.num { text-align: right; font-variant-numeric: tabular-nums; white-
space: nowrap; }
```

Project 62 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - Prices</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cedar Furniture price list	The main heading; only one per page.
	Generic block container for grouping and layout.
<table>	Tabular data in rows and columns.
<caption>Pieces and prices, 2026</caption>	Title of the table.
<thead>	Group of header rows.
<tr><th scope="col">Piece</th><th scope="col">Description</th><th s...	A table row.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">Oak dining table</th><td>Seats six</td><td clas...	Header cell for a row.
<tr><th scope="row">Books helf</th><td>Five shelves, walnut</td><td ...	A header cell.
<tr><th scope="row">Bedside table</th><td>One drawer</td><td class=...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
background: var(--brand);	Background colour or image.
tbody tr:nth-child(even) {	Every second element: zebra striping.
font-weight: 600;	Thickness of the text.
text-align: right;	Right-aligns inline content, typical for numbers.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Every header cell has scope
- Caption describes the table
- Table scrolls instead of overflowing on a phone
- Numbers right-aligned

Exercises

1. Add a tfoot row with a total.
2. Highlight a row on hover.
3. Make the header row sticky with position: sticky.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 63: Price table for Byte Repair

Theme: Byte Repair (Nasr City) | Level 1 | Files: index.html, styles.css

Brief

Present the four main offers in an accessible data table with a caption, column and row headers, zebra stripes and a scroll wrapper for phones.

Learning goals

- Structure a table with caption, thead, tbody, th scope
- Collapse borders and stripe rows
- Keep tables usable on small screens

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, div	border-collapse, padding, :nth-child(even), text-align, overflow-x, white-space

Build guide

1. Write the table markup with a caption and a thead row of th scope="col".
2. Add one tbody row per offer; the first cell is th scope="row".
3. Wrap the table in .
4. Collapse borders, add padding and a bottom border to cells.
5. Colour the header row and stripe the even rows.
6. Right-align the price column and stop it wrapping.

Project 63: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - Prices</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Byte Repair price list</h1>
    <div class="table-wrapper">
      <table>
        <caption>Repairs and prices, 2026</caption>
        <thead>
          <tr><th scope="col">Repair</th><th scope="col">Description</
th><th scope="col">Price</th></tr>
        </thead>
        <tbody>
        <tr><th scope="row">Screen replacement</th><td>Most phones, 1
hour</td><td class="num">From 800 EGP</td></tr>
        <tr><th scope="row">Battery swap</th><td>Original cells</
td><td class="num">From 500 EGP</td></tr>
        <tr><th scope="row">Laptop cleaning</th><td>Fans and thermal
paste</td><td class="num">350 EGP</td></tr>
        <tr><th scope="row">Data recovery</th><td>Drives and cards</
td><td class="num">From 1200 EGP</td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 63: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 50rem; margin: 2rem auto; padding: 0 1rem; }
.table-wrapper { overflow-x: auto; }
table { width: 100%; border-collapse: collapse; }
caption { text-align: left; padding: .5rem 0; color: var(--muted); }
th, td { padding: .75rem 1rem; text-align: left; border-bottom: 1px
solid var(--line); }
```

```
thead th { background: var(--brand); color: #fff; }
tbody tr:nth-child(even) { background: var(--accent); }
tbody th { font-weight: 600; }
.num { text-align: right; font-variant-numeric: tabular-nums; white-
space: nowrap; }
```

Project 63 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - Prices</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Byte Repair price list	The main heading; only one per page.
	Generic block container for grouping and layout.
<table>	Tabular data in rows and columns.
<caption>Repairs and prices, 2026</caption>	Title of the table.
<thead>	Group of header rows.
<tr><th scope="col">Repair</th><th scope="col">Description</th><th ...	A table row.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">Screen replacement</th><td>Most phones, 1 hour<...	Header cell for a row.
<tr><th scope="row">Battery swap</th><td>Original cells</td><td cla...	A header cell.
<tr><th scope="row">Laptop cleaning</th><td>Fans and thermal paste<...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
background: var(--brand);	Background colour or image.
tbody tr:nth-child(even) {	Every second element: zebra striping.
font-weight: 600;	Thickness of the text.
text-align: right;	Right-aligns inline content, typical for numbers.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Every header cell has scope
- Caption describes the table
- Table scrolls instead of overflowing on a phone
- Numbers right-aligned

Exercises

1. Add a tfoot row with a total.
2. Highlight a row on hover.
3. Make the header row sticky with position: sticky.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 64: Price table for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 1 | Files: index.html, styles.css

Brief

Present the four main offers in an accessible data table with a caption, column and row headers, zebra stripes and a scroll wrapper for phones.

Learning goals

- Structure a table with caption, thead, tbody, th scope
- Collapse borders and stripe rows
- Keep tables usable on small screens

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, div	border-collapse, padding, :nth-child(even), text-align, overflow-x, white-space

Build guide

1. Write the table markup with a caption and a thead row of th scope="col".
2. Add one tbody row per offer; the first cell is th scope="row".
3. Wrap the table in .
4. Collapse borders, add padding and a bottom border to cells.
5. Colour the header row and stripe the even rows.
6. Right-align the price column and stop it wrapping.

Project 64: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - Prices</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Sahara Pet Care price list</h1>
    <div class="table-wrapper">
      <table>
        <caption>Services and prices, 2026</caption>
        <thead>
          <tr><th scope="col">Service</th><th
scope="col">Description</th><th scope="col">Price</th></tr>
        </thead>
        <tbody>
        <tr><th scope="row">Full grooming</th><td>Bath, cut and
nails</td><td class="num">400 EGP</td></tr>
        <tr><th scope="row">Day boarding</th><td>Play and rest</
td><td class="num">250 EGP</td></tr>
        <tr><th scope="row">Vaccination</th><td>Annual boosters</
td><td class="num">300 EGP</td></tr>
        <tr><th scope="row">Dog walking</th><td>30 minutes</td><td
class="num">100 EGP</td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 64: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 50rem; margin: 2rem auto; padding: 0 1rem; }
.table-wrapper { overflow-x: auto; }
table { width: 100%; border-collapse: collapse; }
caption { text-align: left; padding: .5rem 0; color: var(--muted); }
th, td { padding: .75rem 1rem; text-align: left; border-bottom: 1px
solid var(--line); }
```

```
thead th { background: var(--brand); color: #fff; }
tbody tr:nth-child(even) { background: var(--accent); }
tbody th { font-weight: 600; }
.num { text-align: right; font-variant-numeric: tabular-nums; white-
space: nowrap; }
```

Project 64 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - Prices</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Sahara Pet Care price list	The main heading; only one per page.
	Generic block container for grouping and layout.
<table>	Tabular data in rows and columns.
<caption>Services and prices, 2026</caption>	Title of the table.
<thead>	Group of header rows.
<tr><th scope="col">Service</th><th scope="col">Description</th><th...	A table row.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">Full grooming</th><td>Bath, cut and nails</td><...	Header cell for a row.
<tr><th scope="row">Day boarding</th><td>Play and rest</td><td clas...	A header cell.
<tr><th scope="row">Vaccination</th><td>Annual boosters</td><td cla...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
background: var(--brand);	Background colour or image.
tbody tr:nth-child(even) {	Every second element: zebra striping.
font-weight: 600;	Thickness of the text.
text-align: right;	Right-aligns inline content, typical for numbers.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Every header cell has scope
- Caption describes the table
- Table scrolls instead of overflowing on a phone
- Numbers right-aligned

Exercises

1. Add a tfoot row with a total.
2. Highlight a row on hover.
3. Make the header row sticky with position: sticky.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 65: Price table for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Present the four main offers in an accessible data table with a caption, column and row headers, zebra stripes and a scroll wrapper for phones.

Learning goals

- Structure a table with caption, thead, tbody, th scope
- Collapse borders and stripe rows
- Keep tables usable on small screens

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, div	border-collapse, padding, :nth-child(even), text-align, overflow-x, white-space

Build guide

1. Write the table markup with a caption and a thead row of th scope="col".
2. Add one tbody row per offer; the first cell is th scope="row".
3. Wrap the table in .
4. Collapse borders, add padding and a bottom border to cells.
5. Colour the header row and stripe the even rows.

6. Right-align the price column and stop it wrapping.

Project 65: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - Prices</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Alexandria Sailing School price list</h1>
    <div class="table-wrapper">
      <table>
        <caption>Lessons and prices, 2026</caption>
        <thead>
          <tr><th scope="col">Lesson</th><th scope="col">Description</
th><th scope="col">Price</th></tr>
        </thead>
        <tbody>
        <tr><th scope="row">Taster session</th><td>Two hours on the
water</td><td class="num">500 EGP</td></tr>
        <tr><th scope="row">Beginner course</th><td>Five sessions</
td><td class="num">2200 EGP</td></tr>
        <tr><th scope="row">Racing clinic</th><td>Tactics and trim</
td><td class="num">1800 EGP</td></tr>
        <tr><th scope="row">Private lesson</th><td>One to one</td><td
class="num">900 EGP</td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 65: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 50rem; margin: 2rem auto; padding: 0 1rem; }
.table-wrapper { overflow-x: auto; }
table { width: 100%; border-collapse: collapse; }
caption { text-align: left; padding: .5rem 0; color: var(--muted); }
th, td { padding: .75rem 1rem; text-align: left; border-bottom: 1px
solid var(--line); }
```

```
thead th { background: var(--brand); color: #fff; }
tbody tr:nth-child(even) { background: var(--accent); }
tbody th { font-weight: 600; }
.num { text-align: right; font-variant-numeric: tabular-nums; white-
space: nowrap; }
```

Project 65 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - Prices</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Alexandria Sailing School price list	The main heading; only one per page.
	Generic block container for grouping and layout.
<table>	Tabular data in rows and columns.
<caption>Lessons and prices, 2026</caption>	Title of the table.
<thead>	Group of header rows.
<tr><th scope="col">Lesson</th><th scope="col">Description</th><th ...	A table row.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">Taster session</th><td>Two hours on the water<//...	Header cell for a row.
<tr><th scope="row">Beginner course</th><td>Five sessions</td><td c...	A header cell.
<tr><th scope="row">Racing clinic</th><td>Tactics and trim</td><td ...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
background: var(--brand);	Background colour or image.
tbody tr:nth-child(even) {	Every second element: zebra striping.
font-weight: 600;	Thickness of the text.
text-align: right;	Right-aligns inline content, typical for numbers.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Every header cell has scope
- Caption describes the table
- Table scrolls instead of overflowing on a phone
- Numbers right-aligned

Exercises

1. Add a tfoot row with a total.
2. Highlight a row on hover.
3. Make the header row sticky with position: sticky.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 66: Price table for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Present the four main offers in an accessible data table with a caption, column and row headers, zebra stripes and a scroll wrapper for phones.

Learning goals

- Structure a table with caption, thead, tbody, th scope
- Collapse borders and stripe rows
- Keep tables usable on small screens

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, div	border-collapse, padding, :nth-child(even), text-align, overflow-x, white-space

Build guide

1. Write the table markup with a caption and a thead row of th scope="col".
2. Add one tbody row per offer; the first cell is th scope="row".
3. Wrap the table in .
4. Collapse borders, add padding and a bottom border to cells.
5. Colour the header row and stripe the even rows.

6. Right-align the price column and stop it wrapping.

Project 66: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - Prices</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Habiba Handmade Jewellery price list</h1>
    <div class="table-wrapper">
      <table>
        <caption>Items and prices, 2026</caption>
        <thead>
          <tr><th scope="col">Item</th><th scope="col">Description</
th><th scope="col">Price</th></tr>
        </thead>
        <tbody>
        <tr><th scope="row">Lotus pendant</th><td>Sterling silver</
td><td class="num">650 EGP</td></tr>
        <tr><th scope="row">Brass cuff</th><td>Hand engraved</td><td
class="num">420 EGP</td></tr>
        <tr><th scope="row">Bead earrings</th><td>Recycled glass</
td><td class="num">180 EGP</td></tr>
        <tr><th scope="row">Ankh ring</th><td>Adjustable</td><td
class="num">300 EGP</td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 66: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 50rem; margin: 2rem auto; padding: 0 1rem; }
.table-wrapper { overflow-x: auto; }
table { width: 100%; border-collapse: collapse; }
caption { text-align: left; padding: .5rem 0; color: var(--muted); }
th, td { padding: .75rem 1rem; text-align: left; border-bottom: 1px
solid var(--line); }
```

```
thead th { background: var(--brand); color: #fff; }
tbody tr:nth-child(even) { background: var(--accent); }
tbody th { font-weight: 600; }
.num { text-align: right; font-variant-numeric: tabular-nums; white-
space: nowrap; }
```

Project 66 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - Prices</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Habiba Handmade Jewellery price list	The main heading; only one per page.
	Generic block container for grouping and layout.
<table>	Tabular data in rows and columns.
<caption>Items and prices, 2026</caption>	Title of the table.
<thead>	Group of header rows.
<tr><th scope="col">Item</th><th scope="col">Description</th><th sc...	A table row.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">Lotus pendant</th><td>Sterling silver</td><td c...	Header cell for a row.
<tr><th scope="row">Brass cuff</th><td>Hand engraved</td><td class=...	A header cell.
<tr><th scope="row">Bead earrings</th><td>Recycled glass</td><td cl...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
background: var(--brand);	Background colour or image.
tbody tr:nth-child(even) {	Every second element: zebra striping.
font-weight: 600;	Thickness of the text.
text-align: right;	Right-aligns inline content, typical for numbers.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Every header cell has scope
- Caption describes the table
- Table scrolls instead of overflowing on a phone
- Numbers right-aligned

Exercises

1. Add a tfoot row with a total.
2. Highlight a row on hover.
3. Make the header row sticky with position: sticky.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 67: Price table for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 1 | Files: index.html, styles.css

Brief

Present the four main offers in an accessible data table with a caption, column and row headers, zebra stripes and a scroll wrapper for phones.

Learning goals

- Structure a table with caption, thead, tbody, th scope
- Collapse borders and stripe rows
- Keep tables usable on small screens

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, div	border-collapse, padding, :nth-child(even), text-align, overflow-x, white-space

Build guide

1. Write the table markup with a caption and a thead row of th scope="col".
2. Add one tbody row per offer; the first cell is th scope="row".
3. Wrap the table in .
4. Collapse borders, add padding and a bottom border to cells.
5. Colour the header row and stripe the even rows.

6. Right-align the price column and stop it wrapping.

Project 67: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - Prices</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Fayoum Pottery Studio price list</h1>
    <div class="table-wrapper">
      <table>
        <caption>Workshops and prices, 2026</caption>
        <thead>
          <tr><th scope="col">Workshop</th><th
scope="col">Description</th><th scope="col">Price</th></tr>
        </thead>
        <tbody>
        <tr><th scope="row">Intro to the wheel</th><td>Three hours,
take home a bowl</td><td class="num">450 EGP</td></tr>
        <tr><th scope="row">Glazing day</th><td>Colour your pieces</
td><td class="num">300 EGP</td></tr>
        <tr><th scope="row">Kids clay class</th><td>Ages 6 to 12</
td><td class="num">200 EGP</td></tr>
        <tr><th scope="row">Weekend retreat</th><td>Two days with
meals</td><td class="num">2500 EGP</td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 67: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 50rem; margin: 2rem auto; padding: 0 1rem; }
.table-wrapper { overflow-x: auto; }
table { width: 100%; border-collapse: collapse; }
caption { text-align: left; padding: .5rem 0; color: var(--muted); }
th, td { padding: .75rem 1rem; text-align: left; border-bottom: 1px
solid var(--line); }
```

```
thead th { background: var(--brand); color: #fff; }
tbody tr:nth-child(even) { background: var(--accent); }
tbody th { font-weight: 600; }
.num { text-align: right; font-variant-numeric: tabular-nums; white-
space: nowrap; }
```

Project 67 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - Prices</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Fayoum Pottery Studio price list	The main heading; only one per page.
	Generic block container for grouping and layout.
<table>	Tabular data in rows and columns.
<caption>Workshops and prices, 2026</caption>	Title of the table.
<thead>	Group of header rows.
<tr><th scope="col">Workshop</th><th scope="col">Description</th><t...	A table row.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">Intro to the wheel</th><td>Three hours, take ho...	Header cell for a row.
<tr><th scope="row">Glazing day</th><td>Colour your pieces</td><td ...	A header cell.
<tr><th scope="row">Kids clay class</th><td>Ages 6 to 12</td><td cl...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
background: var(--brand);	Background colour or image.
tbody tr:nth-child(even) {	Every second element: zebra striping.
font-weight: 600;	Thickness of the text.
text-align: right;	Right-aligns inline content, typical for numbers.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Every header cell has scope
- Caption describes the table
- Table scrolls instead of overflowing on a phone
- Numbers right-aligned

Exercises

1. Add a tfoot row with a total.
2. Highlight a row on hover.
3. Make the header row sticky with position: sticky.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 68: Price table for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 1 | Files: index.html, styles.css

Brief

Present the four main offers in an accessible data table with a caption, column and row headers, zebra stripes and a scroll wrapper for phones.

Learning goals

- Structure a table with caption, thead, tbody, th scope
- Collapse borders and stripe rows
- Keep tables usable on small screens

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, div	border-collapse, padding, :nth-child(even), text-align, overflow-x, white-space

Build guide

1. Write the table markup with a caption and a thead row of th scope="col".
2. Add one tbody row per offer; the first cell is th scope="row".
3. Wrap the table in .
4. Collapse borders, add padding and a bottom border to cells.
5. Colour the header row and stripe the even rows.

6. Right-align the price column and stop it wrapping.

Project 68: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - Prices</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cleopatra Beauty Salon price list</h1>
    <div class="table-wrapper">
      <table>
        <caption>Treatments and prices, 2026</caption>
        <thead>
          <tr><th scope="col">Treatment</th><th
scope="col">Description</th><th scope="col">Price</th></tr>
        </thead>
        <tbody>
        <tr><th scope="row">Haircut and blow-dry</th><td>Consultation
included</td><td class="num">350 EGP</td></tr>
        <tr><th scope="row">Manicure</th><td>Classic or gel</td><td
class="num">200 EGP</td></tr>
        <tr><th scope="row">Facial</th><td>Deep cleanse, 60 minutes</
td><td class="num">600 EGP</td></tr>
        <tr><th scope="row">Bridal package</th><td>Hair, make-up and
nails</td><td class="num">4500 EGP</td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 68: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 50rem; margin: 2rem auto; padding: 0 1rem; }
.table-wrapper { overflow-x: auto; }
table { width: 100%; border-collapse: collapse; }
caption { text-align: left; padding: .5rem 0; color: var(--muted); }
th, td { padding: .75rem 1rem; text-align: left; border-bottom: 1px
solid var(--line); }
```

```
thead th { background: var(--brand); color: #fff; }
tbody tr:nth-child(even) { background: var(--accent); }
tbody th { font-weight: 600; }
.num { text-align: right; font-variant-numeric: tabular-nums; white-
space: nowrap; }
```

Project 68 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - Prices</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cleopatra Beauty Salon price list	The main heading; only one per page.
	Generic block container for grouping and layout.
<table>	Tabular data in rows and columns.
<caption>Treatments and prices, 2026</caption>	Title of the table.
<thead>	Group of header rows.
<tr><th scope="col">Treatment</th><th scope="col">Description</th><...	A table row.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">Haircut and blow-dry</th><td>Consultation inclu...	Header cell for a row.
<tr><th scope="row">Manicure</th><td>Classic or gel</td><td class="...	A header cell.
<tr><th scope="row">Facial</th><td>Deep cleanse, 60 minutes</td><td...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
background: var(--brand);	Background colour or image.
tbody tr:nth-child(even) {	Every second element: zebra striping.
font-weight: 600;	Thickness of the text.
text-align: right;	Right-aligns inline content, typical for numbers.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Every header cell has scope
- Caption describes the table
- Table scrolls instead of overflowing on a phone
- Numbers right-aligned

Exercises

1. Add a tfoot row with a total.
2. Highlight a row on hover.
3. Make the header row sticky with position: sticky.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 69: Price table for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 1 | Files: index.html, styles.css

Brief

Present the four main offers in an accessible data table with a caption, column and row headers, zebra stripes and a scroll wrapper for phones.

Learning goals

- Structure a table with caption, thead, tbody, th scope
- Collapse borders and stripe rows
- Keep tables usable on small screens

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, div	border-collapse, padding, :nth-child(even), text-align, overflow-x, white-space

Build guide

1. Write the table markup with a caption and a thead row of th scope="col".
2. Add one tbody row per offer; the first cell is th scope="row".
3. Wrap the table in .
4. Collapse borders, add padding and a bottom border to cells.
5. Colour the header row and stripe the even rows.
6. Right-align the price column and stop it wrapping.

Project 69: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - Prices</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Suez Auto Service price list</h1>
    <div class="table-wrapper">
      <table>
        <caption>Services and prices, 2026</caption>
        <thead>
          <tr><th scope="col">Service</th><th
scope="col">Description</th><th scope="col">Price</th></tr>
        </thead>
        <tbody>
        <tr><th scope="row">Oil change</th><td>Filter included</
td><td class="num">600 EGP</td></tr>
        <tr><th scope="row">Brake pads</th><td>Front axle</td><td
class="num">1400 EGP</td></tr>
        <tr><th scope="row">Air conditioning</th><td>Recharge and
check</td><td class="num">900 EGP</td></tr>
        <tr><th scope="row">Pre-purchase inspection</th><td>120 point
check</td><td class="num">750 EGP</td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 69: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 50rem; margin: 2rem auto; padding: 0 1rem; }
.table-wrapper { overflow-x: auto; }
table { width: 100%; border-collapse: collapse; }
caption { text-align: left; padding: .5rem 0; color: var(--muted); }
th, td { padding: .75rem 1rem; text-align: left; border-bottom: 1px
solid var(--line); }
```

```
thead th { background: var(--brand); color: #fff; }
tbody tr:nth-child(even) { background: var(--accent); }
tbody th { font-weight: 600; }
.num { text-align: right; font-variant-numeric: tabular-nums; white-
space: nowrap; }
```

Project 69 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - Prices</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Suez Auto Service price list	The main heading; only one per page.
	Generic block container for grouping and layout.
<table>	Tabular data in rows and columns.
<caption>Services and prices, 2026</caption>	Title of the table.
<thead>	Group of header rows.
<tr><th scope="col">Service</th><th scope="col">Description</th><th...	A table row.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">Oil change</th><td>Filter included</td><td clas...	Header cell for a row.
<tr><th scope="row">Brake pads</th><td>Front axle</td><td class="nu...	A header cell.
<tr><th scope="row">Air conditioning</th><td>Recharge and check</td...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
background: var(--brand);	Background colour or image.
tbody tr:nth-child(even) {	Every second element: zebra striping.
font-weight: 600;	Thickness of the text.
text-align: right;	Right-aligns inline content, typical for numbers.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Every header cell has scope
- Caption describes the table
- Table scrolls instead of overflowing on a phone
- Numbers right-aligned

Exercises

1. Add a tfoot row with a total.
2. Highlight a row on hover.
3. Make the header row sticky with position: sticky.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 70: Price table for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 1 | Files: index.html, styles.css

Brief

Present the four main offers in an accessible data table with a caption, column and row headers, zebra stripes and a scroll wrapper for phones.

Learning goals

- Structure a table with caption, thead, tbody, th scope
- Collapse borders and stripe rows
- Keep tables usable on small screens

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, div	border-collapse, padding, :nth-child(even), text-align, overflow-x, white-space

Build guide

1. Write the table markup with a caption and a thead row of th scope="col".
2. Add one tbody row per offer; the first cell is th scope="row".
3. Wrap the table in .
4. Collapse borders, add padding and a bottom border to cells.
5. Colour the header row and stripe the even rows.
6. Right-align the price column and stop it wrapping.

Project 70: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - Prices</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Luxor Music Academy price list</h1>
    <div class="table-wrapper">
      <table>
        <caption>Courses and prices, 2026</caption>
        <thead>
          <tr><th scope="col">Course</th><th scope="col">Description</
th><th scope="col">Price</th></tr>
        </thead>
        <tbody>
        <tr><th scope="row">Oud for beginners</th><td>Eight weekly
lessons</td><td class="num">1600 EGP</td></tr>
        <tr><th scope="row">Piano grade 1</th><td>Theory and
practice</td><td class="num">1800 EGP</td></tr>
        <tr><th scope="row">Guitar chords</th><td>Play songs in a
month</td><td class="num">1400 EGP</td></tr>
        <tr><th scope="row">Voice coaching</th><td>Breathing and
range</td><td class="num">1500 EGP</td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 70: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 50rem; margin: 2rem auto; padding: 0 1rem; }
.table-wrapper { overflow-x: auto; }
table { width: 100%; border-collapse: collapse; }
caption { text-align: left; padding: .5rem 0; color: var(--muted); }
th, td { padding: .75rem 1rem; text-align: left; border-bottom: 1px
solid var(--line); }
```

```
thead th { background: var(--brand); color: #fff; }
tbody tr:nth-child(even) { background: var(--accent); }
tbody th { font-weight: 600; }
.num { text-align: right; font-variant-numeric: tabular-nums; white-
space: nowrap; }
```

Project 70 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - Prices</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Luxor Music Academy price list	The main heading; only one per page.
	Generic block container for grouping and layout.
<table>	Tabular data in rows and columns.
<caption>Courses and prices, 2026</caption>	Title of the table.
<thead>	Group of header rows.
<tr><th scope="col">Course</th><th scope="col">Description</th><th ...	A table row.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">Oud for beginners</th><td>Eight weekly lessons<...	Header cell for a row.
<tr><th scope="row">Piano grade 1</th><td>Theory and practice</td><...	A header cell.
<tr><th scope="row">Guitar chords</th><td>Play songs in a month</td...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
background: var(--brand);	Background colour or image.
tbody tr:nth-child(even) {	Every second element: zebra striping.
font-weight: 600;	Thickness of the text.
text-align: right;	Right-aligns inline content, typical for numbers.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Every header cell has scope
- Caption describes the table
- Table scrolls instead of overflowing on a phone
- Numbers right-aligned

Exercises

1. Add a tfoot row with a total.
2. Highlight a row on hover.
3. Make the header row sticky with position: sticky.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 71: Price table for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 1 | Files: index.html, styles.css

Brief

Present the four main offers in an accessible data table with a caption, column and row headers, zebra stripes and a scroll wrapper for phones.

Learning goals

- Structure a table with caption, thead, tbody, th scope
- Collapse borders and stripe rows
- Keep tables usable on small screens

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, div	border-collapse, padding, :nth-child(even), text-align, overflow-x, white-space

Build guide

1. Write the table markup with a caption and a thead row of th scope="col".
2. Add one tbody row per offer; the first cell is th scope="row".
3. Wrap the table in .
4. Collapse borders, add padding and a bottom border to cells.
5. Colour the header row and stripe the even rows.
6. Right-align the price column and stop it wrapping.

Project 71: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - Prices</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Port Said Seafood price list</h1>
    <div class="table-wrapper">
      <table>
        <caption>Dishes and prices, 2026</caption>
        <thead>
          <tr><th scope="col">Dish</th><th scope="col">Description</
th><th scope="col">Price</th></tr>
        </thead>
        <tbody>
        <tr><th scope="row">Grilled sea bass</th><td>With rice and
salad</td><td class="num">320 EGP</td></tr>
        <tr><th scope="row">Shrimp tagine</th><td>Tomato and garlic</
td><td class="num">280 EGP</td></tr>
        <tr><th scope="row">Calamari</th><td>Fried, with tahini</
td><td class="num">190 EGP</td></tr>
        <tr><th scope="row">Fish soup</th><td>Daily catch</td><td
class="num">120 EGP</td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 71: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 50rem; margin: 2rem auto; padding: 0 1rem; }
.table-wrapper { overflow-x: auto; }
table { width: 100%; border-collapse: collapse; }
caption { text-align: left; padding: .5rem 0; color: var(--muted); }
th, td { padding: .75rem 1rem; text-align: left; border-bottom: 1px
solid var(--line); }
```

```
thead th { background: var(--brand); color: #fff; }
tbody tr:nth-child(even) { background: var(--accent); }
tbody th { font-weight: 600; }
.num { text-align: right; font-variant-numeric: tabular-nums; white-
space: nowrap; }
```

Project 71 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - Prices</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Port Said Seafood price list	The main heading; only one per page.
	Generic block container for grouping and layout.
<table>	Tabular data in rows and columns.
<caption>Dishes and prices, 2026</caption>	Title of the table.
<thead>	Group of header rows.
<tr><th scope="col">Dish</th><th scope="col">Description</th><th sc...	A table row.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">Grilled sea bass</th><td>With rice and salad</t...	Header cell for a row.
<tr><th scope="row">Shrimp tagine</th><td>Tomato and garlic</td><td...	A header cell.
<tr><th scope="row">Calamari</th><td>Fried, with tahini</td><td cla...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
background: var(--brand);	Background colour or image.
tbody tr:nth-child(even) {	Every second element: zebra striping.
font-weight: 600;	Thickness of the text.
text-align: right;	Right-aligns inline content, typical for numbers.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Every header cell has scope
- Caption describes the table
- Table scrolls instead of overflowing on a phone
- Numbers right-aligned

Exercises

1. Add a tfoot row with a total.
2. Highlight a row on hover.
3. Make the header row sticky with position: sticky.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 72: Price table for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 1 | Files: index.html, styles.css

Brief

Present the four main offers in an accessible data table with a caption, column and row headers, zebra stripes and a scroll wrapper for phones.

Learning goals

- Structure a table with caption, thead, tbody, th scope
- Collapse borders and stripe rows
- Keep tables usable on small screens

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, div	border-collapse, padding, :nth-child(even), text-align, overflow-x, white-space

Build guide

1. Write the table markup with a caption and a thead row of th scope="col".
2. Add one tbody row per offer; the first cell is th scope="row".
3. Wrap the table in .
4. Collapse borders, add padding and a bottom border to cells.
5. Colour the header row and stripe the even rows.
6. Right-align the price column and stop it wrapping.

Project 72: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - Prices</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Delta Kids Library price list</h1>
    <div class="table-wrapper">
      <table>
        <caption>Programmes and prices, 2026</caption>
        <thead>
          <tr><th scope="col">Programme</th><th
scope="col">Description</th><th scope="col">Price</th></tr>
        </thead>
        <tbody>
        <tr><th scope="row">Story hour</th><td>Ages 3 to 6,
Saturdays</td><td class="num">Free</td></tr>
        <tr><th scope="row">Reading club</th><td>Ages 7 to 11</td><td
class="num">50 EGP per month</td></tr>
        <tr><th scope="row">Homework help</th><td>Weekday afternoons</
td><td class="num">Free</td></tr>
        <tr><th scope="row">Summer challenge</th><td>Read ten books</
td><td class="num">Free</td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 72: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 50rem; margin: 2rem auto; padding: 0 1rem; }
.table-wrapper { overflow-x: auto; }
table { width: 100%; border-collapse: collapse; }
caption { text-align: left; padding: .5rem 0; color: var(--muted); }
th, td { padding: .75rem 1rem; text-align: left; border-bottom: 1px
solid var(--line); }
```

```
thead th { background: var(--brand); color: #fff; }
tbody tr:nth-child(even) { background: var(--accent); }
tbody th { font-weight: 600; }
.num { text-align: right; font-variant-numeric: tabular-nums; white-
space: nowrap; }
```

Project 72 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - Prices</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Delta Kids Library price list	The main heading; only one per page.
	Generic block container for grouping and layout.
<table>	Tabular data in rows and columns.
<caption>Programmes and prices, 2026</caption>	Title of the table.
<thead>	Group of header rows.
<tr><th scope="col">Programme</th><th scope="col">Description</th><...	A table row.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">Story hour</th><td>Ages 3 to 6, Saturdays</td><...	Header cell for a row.
<tr><th scope="row">Reading club</th><td>Ages 7 to 11</td><td class...	A header cell.
<tr><th scope="row">Homework help</th><td>Weekday afternoons</td><t...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
background: var(--brand);	Background colour or image.
tbody tr:nth-child(even) {	Every second element: zebra striping.
font-weight: 600;	Thickness of the text.
text-align: right;	Right-aligns inline content, typical for numbers.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Every header cell has scope
- Caption describes the table
- Table scrolls instead of overflowing on a phone
- Numbers right-aligned

Exercises

1. Add a tfoot row with a total.
2. Highlight a row on hover.
3. Make the header row sticky with position: sticky.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 73: Price table for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Present the four main offers in an accessible data table with a caption, column and row headers, zebra stripes and a scroll wrapper for phones.

Learning goals

- Structure a table with caption, thead, tbody, th scope
- Collapse borders and stripe rows
- Keep tables usable on small screens

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, div	border-collapse, padding, :nth-child(even), text-align, overflow-x, white-space

Build guide

1. Write the table markup with a caption and a thead row of th scope="col".
2. Add one tbody row per offer; the first cell is th scope="row".
3. Wrap the table in .
4. Collapse borders, add padding and a bottom border to cells.
5. Colour the header row and stripe the even rows.
6. Right-align the price column and stop it wrapping.

Project 73: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - Prices</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Nubian Guest House price list</h1>
    <div class="table-wrapper">
      <table>
        <caption>Rooms and prices, 2026</caption>
        <thead>
          <tr><th scope="col">Room</th><th scope="col">Description</
th><th scope="col">Price</th></tr>
        </thead>
        <tbody>
        <tr><th scope="row">Garden room</th><td>Double bed, shared
terrace</td><td class="num">900 EGP</td></tr>
        <tr><th scope="row">Nile view suite</th><td>Balcony and
breakfast</td><td class="num">1800 EGP</td></tr>
        <tr><th scope="row">Family room</th><td>Sleeps four</td><td
class="num">1500 EGP</td></tr>
        <tr><th scope="row">Rooftop dorm</th><td>Budget beds</td><td
class="num">300 EGP</td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 73: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 50rem; margin: 2rem auto; padding: 0 1rem; }
.table-wrapper { overflow-x: auto; }
table { width: 100%; border-collapse: collapse; }
caption { text-align: left; padding: .5rem 0; color: var(--muted); }
th, td { padding: .75rem 1rem; text-align: left; border-bottom: 1px
solid var(--line); }
```

```
thead th { background: var(--brand); color: #fff; }
tbody tr:nth-child(even) { background: var(--accent); }
tbody th { font-weight: 600; }
.num { text-align: right; font-variant-numeric: tabular-nums; white-
space: nowrap; }
```

Project 73 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - Prices</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Nubian Guest House price list	The main heading; only one per page.
	Generic block container for grouping and layout.
<table>	Tabular data in rows and columns.
<caption>Rooms and prices, 2026</caption>	Title of the table.
<thead>	Group of header rows.
<tr><th scope="col">Room</th><th scope="col">Description</th><th sc...	A table row.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">Garden room</th><td>Double bed, shared terrace<...	Header cell for a row.
<tr><th scope="row">Nile view suite</th><td>Balcony and breakfast<//...	A header cell.
<tr><th scope="row">Family room</th><td>Sleeps four</td><td class="...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
background: var(--brand);	Background colour or image.
tbody tr:nth-child(even) {	Every second element: zebra striping.
font-weight: 600;	Thickness of the text.
text-align: right;	Right-aligns inline content, typical for numbers.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Every header cell has scope
- Caption describes the table
- Table scrolls instead of overflowing on a phone
- Numbers right-aligned

Exercises

1. Add a tfoot row with a total.
2. Highlight a row on hover.
3. Make the header row sticky with position: sticky.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 74: Price table for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 1 | Files: index.html, styles.css

Brief

Present the four main offers in an accessible data table with a caption, column and row headers, zebra stripes and a scroll wrapper for phones.

Learning goals

- Structure a table with caption, thead, tbody, th scope
- Collapse borders and stripe rows
- Keep tables usable on small screens

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, div	border-collapse, padding, :nth-child(even), text-align, overflow-x, white-space

Build guide

1. Write the table markup with a caption and a thead row of th scope="col".
2. Add one tbody row per offer; the first cell is th scope="row".
3. Wrap the table in .
4. Collapse borders, add padding and a bottom border to cells.
5. Colour the header row and stripe the even rows.

6. Right-align the price column and stop it wrapping.

Project 74: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - Prices</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Ismailia Cycling Store price list</h1>
    <div class="table-wrapper">
      <table>
        <caption>Bikes and prices, 2026</caption>
        <thead>
          <tr><th scope="col">Bike</th><th scope="col">Description</
th><th scope="col">Price</th></tr>
        </thead>
        <tbody>
        <tr><th scope="row">City bike</th><td>Seven gears, basket</
td><td class="num">6500 EGP</td></tr>
        <tr><th scope="row">Mountain bike</th><td>Front suspension</
td><td class="num">11000 EGP</td></tr>
        <tr><th scope="row">Kids bike</th><td>20 inch wheels</td><td
class="num">3200 EGP</td></tr>
        <tr><th scope="row">Tune-up</th><td>Brakes, gears and true
wheels</td><td class="num">250 EGP</td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 74: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 50rem; margin: 2rem auto; padding: 0 1rem; }
.table-wrapper { overflow-x: auto; }
table { width: 100%; border-collapse: collapse; }
caption { text-align: left; padding: .5rem 0; color: var(--muted); }
th, td { padding: .75rem 1rem; text-align: left; border-bottom: 1px
solid var(--line); }
```

```
thead th { background: var(--brand); color: #fff; }
tbody tr:nth-child(even) { background: var(--accent); }
tbody th { font-weight: 600; }
.num { text-align: right; font-variant-numeric: tabular-nums; white-
space: nowrap; }
```

Project 74 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - Prices</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Ismailia Cycling Store price list	The main heading; only one per page.
	Generic block container for grouping and layout.
<table>	Tabular data in rows and columns.
<caption>Bikes and prices, 2026</caption>	Title of the table.
<thead>	Group of header rows.
<tr><th scope="col">Bike</th><th scope="col">Description</th><th sc...	A table row.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">City bike</th><td>Seven gears, basket</td><td c...	Header cell for a row.
<tr><th scope="row">Mountain bike</th><td>Front suspension</td><td ...	A header cell.
<tr><th scope="row">Kids bike</th><td>20 inch wheels</td><td class=...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
background: var(--brand);	Background colour or image.
tbody tr:nth-child(even) {	Every second element: zebra striping.
font-weight: 600;	Thickness of the text.
text-align: right;	Right-aligns inline content, typical for numbers.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Every header cell has scope
- Caption describes the table
- Table scrolls instead of overflowing on a phone
- Numbers right-aligned

Exercises

1. Add a tfoot row with a total.
2. Highlight a row on hover.
3. Make the header row sticky with position: sticky.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 75: Price table for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 1 | Files: index.html, styles.css

Brief

Present the four main offers in an accessible data table with a caption, column and row headers, zebra stripes and a scroll wrapper for phones.

Learning goals

- Structure a table with caption, thead, tbody, th scope
- Collapse borders and stripe rows
- Keep tables usable on small screens

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, div	border-collapse, padding, :nth-child(even), text-align, overflow-x, white-space

Build guide

1. Write the table markup with a caption and a thead row of th scope="col".
2. Add one tbody row per offer; the first cell is th scope="row".
3. Wrap the table in .
4. Collapse borders, add padding and a bottom border to cells.
5. Colour the header row and stripe the even rows.
6. Right-align the price column and stop it wrapping.

Project 75: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - Prices</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Minya Coding Club price list</h1>
    <div class="table-wrapper">
      <table>
        <caption>Workshops and prices, 2026</caption>
        <thead>
          <tr><th scope="col">Workshop</th><th
scope="col">Description</th><th scope="col">Price</th></tr>
        </thead>
        <tbody>
        <tr><th scope="row">HTML weekend</th><td>Build your first
page</td><td class="num">Free</td></tr>
        <tr><th scope="row">CSS art</th><td>Draw with code</td><td
class="num">Free</td></tr>
        <tr><th scope="row">Scratch games</th><td>Ages 10 to 13</
td><td class="num">Free</td></tr>
        <tr><th scope="row">Hackathon</th><td>48 hours, teams of
four</td><td class="num">Free</td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 75: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 50rem; margin: 2rem auto; padding: 0 1rem; }
.table-wrapper { overflow-x: auto; }
table { width: 100%; border-collapse: collapse; }
caption { text-align: left; padding: .5rem 0; color: var(--muted); }
th, td { padding: .75rem 1rem; text-align: left; border-bottom: 1px
solid var(--line); }
```

```
thead th { background: var(--brand); color: #fff; }
tbody tr:nth-child(even) { background: var(--accent); }
tbody th { font-weight: 600; }
.num { text-align: right; font-variant-numeric: tabular-nums; white-
space: nowrap; }
```

Project 75 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - Prices</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Minya Coding Club price list	The main heading; only one per page.
	Generic block container for grouping and layout.
<table>	Tabular data in rows and columns.
<caption>Workshops and prices, 2026</caption>	Title of the table.
<thead>	Group of header rows.
<tr><th scope="col">Workshop</th><th scope="col">Description</th><t...	A table row.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">HTML weekend</th><td>Build your first page</td>...	Header cell for a row.
<tr><th scope="row">CSS art</th><td>Draw with code</td><td class="n...	A header cell.
<tr><th scope="row">Scratch games</th><td>Ages 10 to 13</td><td cla...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
background: var(--brand);	Background colour or image.
tbody tr:nth-child(even) {	Every second element: zebra striping.
font-weight: 600;	Thickness of the text.
text-align: right;	Right-aligns inline content, typical for numbers.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Every header cell has scope
- Caption describes the table
- Table scrolls instead of overflowing on a phone
- Numbers right-aligned

Exercises

1. Add a tfoot row with a total.
2. Highlight a row on hover.
3. Make the header row sticky with position: sticky.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Contact form

Level 1 | 25 projects, one per theme

Build a contact form with text, email, select and textarea controls, proper labels, built-in validation and a styled submit button.

Project 76: Contact form for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 1 | Files: index.html, styles.css

Brief

Build a contact form with text, email, select and textarea controls, proper labels, built-in validation and a styled submit button.

Learning goals

- Connect every label to its control with for/id
- Use input types and required for free validation
- Style focus and invalid states

Elements and CSS used

HTML elements	CSS features
form, label, input, select, option, textarea, button, address, a	display: grid, gap, font: inherit, :focus-visible, :user-invalid, border-radius

Build guide

1. Create the form with action and method.
2. Add one .row per field: a label followed by its control; match for and id.
3. Use type="email", required and minlength.
4. Add the select with one option per offer.
5. Style with Grid gaps; make controls full width and inherit the page font.
6. Submit the empty form and watch the browser's validation messages.

Project 76: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Contact</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Contact Cairo Book Shop</h1>
    <form action="/contact" method="post" class="form">
      <div class="row">
        <label for="name">Your name</label>
        <input id="name" name="name" type="text" required
autocomplete="name">
      </div>
      <div class="row">
        <label for="email">Email</label>
        <input id="email" name="email" type="email" required
autocomplete="email">
      </div>
      <div class="row">
        <label for="topic">Topic</label>
        <select id="topic" name="topic">
    <option>Learn HTML</option>
    <option>CSS in Practice</option>
    <option>JavaScript Basics</option>
    <option>Web Accessibility</option>
          <option>Something else</option>
        </select>
      </div>
      <div class="row">
        <label for="msg">Message</label>
        <textarea id="msg" name="message" rows="5" required
minlength="10"></textarea>
      </div>
      <button type="submit">Send message</button>
    </form>
    <address>Cairo Book Shop, Giza &middot; <a href="mailto:
hello@bookshop.example">hello@bookshop.example</a></address>
  </main>
</body>
</html>
```

Project 76: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.form { display: grid; gap: 1rem; }
.row { display: grid; gap: .3rem; }
label { font-weight: 600; }
input, select, textarea, button { font: inherit; }
input, select, textarea { padding: .6rem .8rem; border: 1px solid
#bbb; border-radius: 8px; width: 100%; }
input:focus-visible, select:focus-visible, textarea:focus-visible {
outline: 3px solid #ffbf47; border-color: var(--brand); }
input:user-invalid, textarea:user-invalid { border-color: #c00; }
button { justify-self: start; padding: .7rem 1.4rem; background: var(-
-brand); color: #fff; border: 0; border-radius: 999px; cursor:
pointer; }
address { margin-top: 2rem; font-style: normal; color: var(--muted); }
```

Project 76 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - Contact</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Contact Cairo Book Shop	The main heading; only one per page.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
	Generic block container for grouping and layout.
<label for="name">Your name</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="name" name="name" type="text" required autocomplete="name">	A form control; its type decides what it looks like.

Line	What it does
<input id="email" name="email" type="email" required autocomplete="...	Email field: validated automatically and shows the @ keyboard on phones.
<select id="topic" name="topic">	Drop-down list.
<option>Learn HTML</option>	One choice in a select or datalist.
<textarea id="msg" name="message" rows="5" required minlength="10">...	Multi-line text field.
<button type="submit">Send message</button>	A clickable button; inside a form it submits by default.
<address>Cairo Book Shop, Giza · <a href="mailto:hello@books...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
font-weight: 600;	Thickness of the text.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
width: 100%;	Fills the container width.
input:focus-visible, select:focus-visible, textarea:focus-visible {	Applies when the element is focused by keyboard; keeps focus rings visible.
border-color: var(--brand);	The line around the element: width, style and colour.
input:user-invalid, textarea:user-invalid {	A field the user has edited that fails validation.
background: var(--brand);	Background colour or image.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Clicking a label focuses its control
- Empty submit is blocked
- Focus ring visible
- Address is real contact info, not italic

Exercises

1. Add a checkbox for newsletter consent.
2. Put name and email side by side on wide screens.
3. Add a pattern attribute for an Egyptian phone number.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 77: Contact form for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 1 | Files: index.html, styles.css

Brief

Build a contact form with text, email, select and textarea controls, proper labels, built-in validation and a styled submit button.

Learning goals

- Connect every label to its control with for/id
- Use input types and required for free validation
- Style focus and invalid states

Elements and CSS used

HTML elements	CSS features
form, label, input, select, option, textarea, button, address, a	display: grid, gap, font: inherit, :focus-visible, :user-invalid, border-radius

Build guide

1. Create the form with action and method.
2. Add one .row per field: a label followed by its control; match for and id.
3. Use type="email", required and minlength.
4. Add the select with one option per offer.
5. Style with Grid gaps; make controls full width and inherit the page font.
6. Submit the empty form and watch the browser's validation messages.

Project 77: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - Contact</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Contact Nile Bakery</h1>
    <form action="/contact" method="post" class="form">
      <div class="row">
        <label for="name">Your name</label>
        <input id="name" name="name" type="text" required
autocomplete="name">
      </div>
      <div class="row">
        <label for="email">Email</label>
        <input id="email" name="email" type="email" required
autocomplete="email">
      </div>
      <div class="row">
        <label for="topic">Topic</label>
        <select id="topic" name="topic">
    <option>Sourdough loaf</option>
    <option>Croissant</option>
    <option>Date cookies</option>
    <option>Baklava box</option>
          <option>Something else</option>
        </select>
      </div>
      <div class="row">
        <label for="msg">Message</label>
        <textarea id="msg" name="message" rows="5" required
minlength="10"></textarea>
      </div>
      <button type="submit">Send message</button>
    </form>
    <address>Nile Bakery, Cairo &middot; <a href="mailto:hello@bakery.
example">hello@bakery.example</a></address>
  </main>
</body>
</html>
```

Project 77: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.form { display: grid; gap: 1rem; }
.row { display: grid; gap: .3rem; }
label { font-weight: 600; }
input, select, textarea, button { font: inherit; }
input, select, textarea { padding: .6rem .8rem; border: 1px solid
#bbb; border-radius: 8px; width: 100%; }
input:focus-visible, select:focus-visible, textarea:focus-visible {
outline: 3px solid #ffbf47; border-color: var(--brand); }
input:user-invalid, textarea:user-invalid { border-color: #c00; }
button { justify-self: start; padding: .7rem 1.4rem; background: var(-
-brand); color: #fff; border: 0; border-radius: 999px; cursor:
pointer; }
address { margin-top: 2rem; font-style: normal; color: var(--muted); }
```

Project 77 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - Contact</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Contact Nile Bakery	The main heading; only one per page.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
	Generic block container for grouping and layout.
<label for="name">Your name</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="name" name="name" type="text" required autocomplete="name">	A form control; its type decides what it looks like.

Line	What it does
<input id="email" name="email" type="email" required autocomplete="...	Email field: validated automatically and shows the @ keyboard on phones.
<select id="topic" name="topic">	Drop-down list.
<option>Sourdough loaf</option>	One choice in a select or datalist.
<textarea id="msg" name="message" rows="5" required minlength="10">...	Multi-line text field.
<button type="submit">Send message</button>	A clickable button; inside a form it submits by default.
<address>Nile Bakery, Cairo · <a href="mailto:hello@bakery.e...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
font-weight: 600;	Thickness of the text.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
width: 100%;	Fills the container width.
input:focus-visible, select:focus-visible, textarea:focus-visible {	Applies when the element is focused by keyboard; keeps focus rings visible.
border-color: var(--brand);	The line around the element: width, style and colour.
input:user-invalid, textarea:user-invalid {	A field the user has edited that fails validation.
background: var(--brand);	Background colour or image.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Clicking a label focuses its control
- Empty submit is blocked
- Focus ring visible
- Address is real contact info, not italic

Exercises

1. Add a checkbox for newsletter consent.
2. Put name and email side by side on wide screens.
3. Add a pattern attribute for an Egyptian phone number.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 78: Contact form for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 1 | Files: index.html, styles.css

Brief

Build a contact form with text, email, select and textarea controls, proper labels, built-in validation and a styled submit button.

Learning goals

- Connect every label to its control with for/id
- Use input types and required for free validation
- Style focus and invalid states

Elements and CSS used

HTML elements	CSS features
form, label, input, select, option, textarea, button, address, a	display: grid, gap, font: inherit, :focus-visible, :user-invalid, border-radius

Build guide

1. Create the form with action and method.
2. Add one .row per field: a label followed by its control; match for and id.
3. Use type="email", required and minlength.
4. Add the select with one option per offer.
5. Style with Grid gaps; make controls full width and inherit the page font.

6. Submit the empty form and watch the browser's validation messages.

Project 78: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - Contact</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Contact Pyramid Fitness</h1>
    <form action="/contact" method="post" class="form">
      <div class="row">
        <label for="name">Your name</label>
        <input id="name" name="name" type="text" required
autocomplete="name">
      </div>
      <div class="row">
        <label for="email">Email</label>
        <input id="email" name="email" type="email" required
autocomplete="email">
      </div>
      <div class="row">
        <label for="topic">Topic</label>
        <select id="topic" name="topic">
    <option>Morning yoga</option>
    <option>Strength circuit</option>
    <option>Spinning</option>
    <option>Personal training</option>
          <option>Something else</option>
        </select>
      </div>
      <div class="row">
        <label for="msg">Message</label>
        <textarea id="msg" name="message" rows="5" required
minlength="10"></textarea>
      </div>
      <button type="submit">Send message</button>
    </form>
    <address>Pyramid Fitness, 6th of October &middot; <a href="mailto:
hello@gym.example">hello@gym.example</a></address>
  </main>
</body>
</html>
```

Project 78: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.form { display: grid; gap: 1rem; }
.row { display: grid; gap: .3rem; }
label { font-weight: 600; }
input, select, textarea, button { font: inherit; }
input, select, textarea { padding: .6rem .8rem; border: 1px solid
#bbb; border-radius: 8px; width: 100%; }
input:focus-visible, select:focus-visible, textarea:focus-visible {
outline: 3px solid #ffbf47; border-color: var(--brand); }
input:user-invalid, textarea:user-invalid { border-color: #c00; }
button { justify-self: start; padding: .7rem 1.4rem; background: var(-
-brand); color: #fff; border: 0; border-radius: 999px; cursor:
pointer; }
address { margin-top: 2rem; font-style: normal; color: var(--muted); }
```

Project 78 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - Contact</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Contact Pyramid Fitness	The main heading; only one per page.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
	Generic block container for grouping and layout.
<label for="name">Your name</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="name" name="name" type="text" required autocomplete="name">	A form control; its type decides what it looks like.

Line	What it does
<input id="email" name="email" type="email" required autocomplete="...	Email field: validated automatically and shows the @ keyboard on phones.
<select id="topic" name="topic">	Drop-down list.
<option>Morning yoga</option>	One choice in a select or datalist.
<textarea id="msg" name="message" rows="5" required minlength="10">...	Multi-line text field.
<button type="submit">Send message</button>	A clickable button; inside a form it submits by default.
<address>Pyramid Fitness, 6th of October · <a href="mailto:h...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
font-weight: 600;	Thickness of the text.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
width: 100%;	Fills the container width.
input:focus-visible, select:focus-visible, textarea:focus-visible {	Applies when the element is focused by keyboard; keeps focus rings visible.
border-color: var(--brand);	The line around the element: width, style and colour.
input:user-invalid, textarea:user-invalid {	A field the user has edited that fails validation.
background: var(--brand);	Background colour or image.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Clicking a label focuses its control
- Empty submit is blocked
- Focus ring visible
- Address is real contact info, not italic

Exercises

1. Add a checkbox for newsletter consent.
2. Put name and email side by side on wide screens.
3. Add a pattern attribute for an Egyptian phone number.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 79: Contact form for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 1 | Files: index.html, styles.css

Brief

Build a contact form with text, email, select and textarea controls, proper labels, built-in validation and a styled submit button.

Learning goals

- Connect every label to its control with for/id
- Use input types and required for free validation
- Style focus and invalid states

Elements and CSS used

HTML elements	CSS features
form, label, input, select, option, textarea, button, address, a	display: grid, gap, font: inherit, :focus-visible, :user-invalid, border-radius

Build guide

1. Create the form with action and method.
2. Add one .row per field: a label followed by its control; match for and id.
3. Use type="email", required and minlength.
4. Add the select with one option per offer.
5. Style with Grid gaps; make controls full width and inherit the page font.
6. Submit the empty form and watch the browser's validation messages.

Project 79: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - Contact</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Contact Delta Dental Clinic</h1>
    <form action="/contact" method="post" class="form">
      <div class="row">
        <label for="name">Your name</label>
        <input id="name" name="name" type="text" required
autocomplete="name">
      </div>
      <div class="row">
        <label for="email">Email</label>
        <input id="email" name="email" type="email" required
autocomplete="email">
      </div>
      <div class="row">
        <label for="topic">Topic</label>
        <select id="topic" name="topic">
    <option>Check-up</option>
    <option>Whitening</option>
    <option>Filling</option>
    <option>Braces consultation</option>
          <option>Something else</option>
        </select>
      </div>
      <div class="row">
        <label for="msg">Message</label>
        <textarea id="msg" name="message" rows="5" required
minlength="10"></textarea>
      </div>
      <button type="submit">Send message</button>
    </form>
    <address>Delta Dental Clinic, Mansoura &middot; <a href="mailto:
hello@clinic.example">hello@clinic.example</a></address>
  </main>
</body>
</html>
```

Project 79: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.form { display: grid; gap: 1rem; }
.row { display: grid; gap: .3rem; }
label { font-weight: 600; }
input, select, textarea, button { font: inherit; }
input, select, textarea { padding: .6rem .8rem; border: 1px solid
#bbb; border-radius: 8px; width: 100%; }
input:focus-visible, select:focus-visible, textarea:focus-visible {
outline: 3px solid #ffbf47; border-color: var(--brand); }
input:user-invalid, textarea:user-invalid { border-color: #c00; }
button { justify-self: start; padding: .7rem 1.4rem; background: var(-
-brand); color: #fff; border: 0; border-radius: 999px; cursor:
pointer; }
address { margin-top: 2rem; font-style: normal; color: var(--muted); }
```

Project 79 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - Contact</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Contact Delta Dental Clinic	The main heading; only one per page.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
	Generic block container for grouping and layout.
<label for="name">Your name</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="name" name="name" type="text" required autocomplete="name">	A form control; its type decides what it looks like.

Line	What it does
<input id="email" name="email" type="email" required autocomplete="...	Email field: validated automatically and shows the @ keyboard on phones.
<select id="topic" name="topic">	Drop-down list.
<option>Check-up</option>	One choice in a select or datalist.
<textarea id="msg" name="message" rows="5" required minlength="10">...	Multi-line text field.
<button type="submit">Send message</button>	A clickable button; inside a form it submits by default.
<address>Delta Dental Clinic, Mansoura · <a href="mailto:hel...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
font-weight: 600;	Thickness of the text.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
width: 100%;	Fills the container width.
input:focus-visible, select:focus-visible, textarea:focus-visible {	Applies when the element is focused by keyboard; keeps focus rings visible.
border-color: var(--brand);	The line around the element: width, style and colour.
input:user-invalid, textarea:user-invalid {	A field the user has edited that fails validation.
background: var(--brand);	Background colour or image.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Clicking a label focuses its control
- Empty submit is blocked
- Focus ring visible
- Address is real contact info, not italic

Exercises

1. Add a checkbox for newsletter consent.
2. Put name and email side by side on wide screens.
3. Add a pattern attribute for an Egyptian phone number.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 80: Contact form for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 1 | Files: index.html, styles.css

Brief

Build a contact form with text, email, select and textarea controls, proper labels, built-in validation and a styled submit button.

Learning goals

- Connect every label to its control with for/id
- Use input types and required for free validation
- Style focus and invalid states

Elements and CSS used

HTML elements	CSS features
form, label, input, select, option, textarea, button, address, a	display: grid, gap, font: inherit, :focus-visible, :user-invalid, border-radius

Build guide

1. Create the form with action and method.
2. Add one .row per field: a label followed by its control; match for and id.
3. Use type="email", required and minlength.
4. Add the select with one option per offer.
5. Style with Grid gaps; make controls full width and inherit the page font.
6. Submit the empty form and watch the browser's validation messages.

Project 80: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - Contact</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Contact Red Sea Travel</h1>
    <form action="/contact" method="post" class="form">
      <div class="row">
        <label for="name">Your name</label>
        <input id="name" name="name" type="text" required
autocomplete="name">
      </div>
      <div class="row">
        <label for="email">Email</label>
        <input id="email" name="email" type="email" required
autocomplete="email">
      </div>
      <div class="row">
        <label for="topic">Topic</label>
        <select id="topic" name="topic">
    <option>Luxor day trip</option>
    <option>Snorkelling</option>
    <option>Desert safari</option>
    <option>Nile cruise</option>
          <option>Something else</option>
        </select>
      </div>
      <div class="row">
        <label for="msg">Message</label>
        <textarea id="msg" name="message" rows="5" required
minlength="10"></textarea>
      </div>
      <button type="submit">Send message</button>
    </form>
    <address>Red Sea Travel, Hurghada &middot; <a href="mailto:
hello@travel.example">hello@travel.example</a></address>
  </main>
</body>
</html>
```

Project 80: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.form { display: grid; gap: 1rem; }
.row { display: grid; gap: .3rem; }
label { font-weight: 600; }
input, select, textarea, button { font: inherit; }
input, select, textarea { padding: .6rem .8rem; border: 1px solid
#bbb; border-radius: 8px; width: 100%; }
input:focus-visible, select:focus-visible, textarea:focus-visible {
outline: 3px solid #ffbf47; border-color: var(--brand); }
input:user-invalid, textarea:user-invalid { border-color: #c00; }
button { justify-self: start; padding: .7rem 1.4rem; background: var(-
-brand); color: #fff; border: 0; border-radius: 999px; cursor:
pointer; }
address { margin-top: 2rem; font-style: normal; color: var(--muted); }
```

Project 80 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - Contact</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Contact Red Sea Travel	The main heading; only one per page.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
	Generic block container for grouping and layout.
<label for="name">Your name</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="name" name="name" type="text" required autocomplete="name">	A form control; its type decides what it looks like.

Line	What it does
<input id="email" name="email" type="email" required autocomplete="...	Email field: validated automatically and shows the @ keyboard on phones.
<select id="topic" name="topic">	Drop-down list.
<option>Luxor day trip</option>	One choice in a select or datalist.
<textarea id="msg" name="message" rows="5" required minlength="10">...	Multi-line text field.
<button type="submit">Send message</button>	A clickable button; inside a form it submits by default.
<address>Red Sea Travel, Hurghada · <a href="mailto:hello@tr...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
font-weight: 600;	Thickness of the text.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
width: 100%;	Fills the container width.
input:focus-visible, select:focus-visible, textarea:focus-visible {	Applies when the element is focused by keyboard; keeps focus rings visible.
border-color: var(--brand);	The line around the element: width, style and colour.
input:user-invalid, textarea:user-invalid {	A field the user has edited that fails validation.
background: var(--brand);	Background colour or image.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Clicking a label focuses its control
- Empty submit is blocked
- Focus ring visible
- Address is real contact info, not italic

Exercises

1. Add a checkbox for newsletter consent.
2. Put name and email side by side on wide screens.
3. Add a pattern attribute for an Egyptian phone number.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 81: Contact form for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Build a contact form with text, email, select and textarea controls, proper labels, built-in validation and a styled submit button.

Learning goals

- Connect every label to its control with for/id
- Use input types and required for free validation
- Style focus and invalid states

Elements and CSS used

HTML elements	CSS features
form, label, input, select, option, textarea, button, address, a	display: grid, gap, font: inherit, :focus-visible, :user-invalid, border-radius

Build guide

1. Create the form with action and method.
2. Add one .row per field: a label followed by its control; match for and id.
3. Use type="email", required and minlength.
4. Add the select with one option per offer.
5. Style with Grid gaps; make controls full width and inherit the page font.

6. Submit the empty form and watch the browser's validation messages.

Project 81: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - Contact</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Contact Lotus Language School</h1>
    <form action="/contact" method="post" class="form">
      <div class="row">
        <label for="name">Your name</label>
        <input id="name" name="name" type="text" required
autocomplete="name">
      </div>
      <div class="row">
        <label for="email">Email</label>
        <input id="email" name="email" type="email" required
autocomplete="email">
      </div>
      <div class="row">
        <label for="topic">Topic</label>
        <select id="topic" name="topic">
    <option>English A1</option>
    <option>French B1</option>
    <option>German A2</option>
    <option>IELTS preparation</option>
          <option>Something else</option>
        </select>
      </div>
      <div class="row">
        <label for="msg">Message</label>
        <textarea id="msg" name="message" rows="5" required
minlength="10"></textarea>
      </div>
      <button type="submit">Send message</button>
    </form>
    <address>Lotus Language School, Alexandria &middot; <a
href="mailto:hello@school.example">hello@school.example</a></address>
  </main>
</body>
</html>
```

Project 81: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.form { display: grid; gap: 1rem; }
.row { display: grid; gap: .3rem; }
label { font-weight: 600; }
input, select, textarea, button { font: inherit; }
input, select, textarea { padding: .6rem .8rem; border: 1px solid
#bbb; border-radius: 8px; width: 100%; }
input:focus-visible, select:focus-visible, textarea:focus-visible {
outline: 3px solid #ffbf47; border-color: var(--brand); }
input:user-invalid, textarea:user-invalid { border-color: #c00; }
button { justify-self: start; padding: .7rem 1.4rem; background: var(-
-brand); color: #fff; border: 0; border-radius: 999px; cursor:
pointer; }
address { margin-top: 2rem; font-style: normal; color: var(--muted); }
```

Project 81 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - Contact</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Contact Lotus Language School	The main heading; only one per page.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
	Generic block container for grouping and layout.
<label for="name">Your name</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="name" name="name" type="text" required autocomplete="name">	A form control; its type decides what it looks like.

Line	What it does
<input id="email" name="email" type="email" required autocomplete="...	Email field: validated automatically and shows the @ keyboard on phones.
<select id="topic" name="topic">	Drop-down list.
<option>English A1</option>	One choice in a select or datalist.
<textarea id="msg" name="message" rows="5" required minlength="10">...	Multi-line text field.
<button type="submit">Send message</button>	A clickable button; inside a form it submits by default.
<address>Lotus Language School, Alexandria · <a href="mailto...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
font-weight: 600;	Thickness of the text.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
width: 100%;	Fills the container width.
input:focus-visible, select:focus-visible, textarea:focus-visible {	Applies when the element is focused by keyboard; keeps focus rings visible.
border-color: var(--brand);	The line around the element: width, style and colour.
input:user-invalid, textarea:user-invalid {	A field the user has edited that fails validation.
background: var(--brand);	Background colour or image.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Clicking a label focuses its control
- Empty submit is blocked
- Focus ring visible
- Address is real contact info, not italic

Exercises

1. Add a checkbox for newsletter consent.
2. Put name and email side by side on wide screens.
3. Add a pattern attribute for an Egyptian phone number.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 82: Contact form for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 1 | Files: index.html, styles.css

Brief

Build a contact form with text, email, select and textarea controls, proper labels, built-in validation and a styled submit button.

Learning goals

- Connect every label to its control with for/id
- Use input types and required for free validation
- Style focus and invalid states

Elements and CSS used

HTML elements	CSS features
form, label, input, select, option, textarea, button, address, a	display: grid, gap, font: inherit, :focus-visible, :user-invalid, border-radius

Build guide

1. Create the form with action and method.
2. Add one .row per field: a label followed by its control; match for and id.
3. Use type="email", required and minlength.
4. Add the select with one option per offer.
5. Style with Grid gaps; make controls full width and inherit the page font.
6. Submit the empty form and watch the browser's validation messages.

Project 82: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - Contact</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Contact Green Leaf Cafe</h1>
    <form action="/contact" method="post" class="form">
      <div class="row">
        <label for="name">Your name</label>
        <input id="name" name="name" type="text" required
autocomplete="name">
      </div>
      <div class="row">
        <label for="email">Email</label>
        <input id="email" name="email" type="email" required
autocomplete="email">
      </div>
      <div class="row">
        <label for="topic">Topic</label>
        <select id="topic" name="topic">
    <option>Flat white</option>
    <option>Cold brew</option>
    <option>Hibiscus iced tea</option>
    <option>Cheesecake</option>
          <option>Something else</option>
        </select>
      </div>
      <div class="row">
        <label for="msg">Message</label>
        <textarea id="msg" name="message" rows="5" required
minlength="10"></textarea>
      </div>
      <button type="submit">Send message</button>
    </form>
    <address>Green Leaf Cafe, Zamalek &middot; <a href="mailto:
hello@cafe.example">hello@cafe.example</a></address>
  </main>
</body>
</html>
```

Project 82: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.form { display: grid; gap: 1rem; }
.row { display: grid; gap: .3rem; }
label { font-weight: 600; }
input, select, textarea, button { font: inherit; }
input, select, textarea { padding: .6rem .8rem; border: 1px solid
#bbb; border-radius: 8px; width: 100%; }
input:focus-visible, select:focus-visible, textarea:focus-visible {
outline: 3px solid #ffbf47; border-color: var(--brand); }
input:user-invalid, textarea:user-invalid { border-color: #c00; }
button { justify-self: start; padding: .7rem 1.4rem; background: var(-
-brand); color: #fff; border: 0; border-radius: 999px; cursor:
pointer; }
address { margin-top: 2rem; font-style: normal; color: var(--muted); }
```

Project 82 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - Contact</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Contact Green Leaf Cafe	The main heading; only one per page.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
	Generic block container for grouping and layout.
<label for="name">Your name</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="name" name="name" type="text" required autocomplete="name">	A form control; its type decides what it looks like.

Line	What it does
<input id="email" name="email" type="email" required autocomplete="...	Email field: validated automatically and shows the @ keyboard on phones.
<select id="topic" name="topic">	Drop-down list.
<option>Flat white</option>	One choice in a select or datalist.
<textarea id="msg" name="message" rows="5" required minlength="10">...	Multi-line text field.
<button type="submit">Send message</button>	A clickable button; inside a form it submits by default.
<address>Green Leaf Cafe, Zamalek · <a href="mailto:hello@ca...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
font-weight: 600;	Thickness of the text.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
width: 100%;	Fills the container width.
input:focus-visible, select:focus-visible, textarea:focus-visible {	Applies when the element is focused by keyboard; keeps focus rings visible.
border-color: var(--brand);	The line around the element: width, style and colour.
input:user-invalid, textarea:user-invalid {	A field the user has edited that fails validation.
background: var(--brand);	Background colour or image.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Clicking a label focuses its control
- Empty submit is blocked
- Focus ring visible
- Address is real contact info, not italic

Exercises

1. Add a checkbox for newsletter consent.
2. Put name and email side by side on wide screens.
3. Add a pattern attribute for an Egyptian phone number.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 83: Contact form for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 1 | Files: index.html, styles.css

Brief

Build a contact form with text, email, select and textarea controls, proper labels, built-in validation and a styled submit button.

Learning goals

- Connect every label to its control with for/id
- Use input types and required for free validation
- Style focus and invalid states

Elements and CSS used

HTML elements	CSS features
form, label, input, select, option, textarea, button, address, a	display: grid, gap, font: inherit, :focus-visible, :user-invalid, border-radius

Build guide

1. Create the form with action and method.
2. Add one .row per field: a label followed by its control; match for and id.
3. Use type="email", required and minlength.
4. Add the select with one option per offer.
5. Style with Grid gaps; make controls full width and inherit the page font.

6. Submit the empty form and watch the browser's validation messages.

Project 83: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - Contact</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Contact Sinai Trekking Club</h1>
    <form action="/contact" method="post" class="form">
      <div class="row">
        <label for="name">Your name</label>
        <input id="name" name="name" type="text" required
autocomplete="name">
      </div>
      <div class="row">
        <label for="email">Email</label>
        <input id="email" name="email" type="email" required
autocomplete="email">
      </div>
      <div class="row">
        <label for="topic">Topic</label>
        <select id="topic" name="topic">
    <option>Mount Sinai sunrise</option>
    <option>Blue Desert loop</option>
    <option>Wadi Gnai</option>
    <option>Three-day traverse</option>
          <option>Something else</option>
        </select>
      </div>
      <div class="row">
        <label for="msg">Message</label>
        <textarea id="msg" name="message" rows="5" required
minlength="10"></textarea>
      </div>
      <button type="submit">Send message</button>
    </form>
    <address>Sinai Trekking Club, Saint Catherine &middot; <a
href="mailto:hello@trekking.example">hello@trekking.example</a></
address>
  </main>
</body>
</html>
```

Project 83: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.form { display: grid; gap: 1rem; }
.row { display: grid; gap: .3rem; }
label { font-weight: 600; }
input, select, textarea, button { font: inherit; }
input, select, textarea { padding: .6rem .8rem; border: 1px solid
#bbb; border-radius: 8px; width: 100%; }
input:focus-visible, select:focus-visible, textarea:focus-visible {
outline: 3px solid #ffbf47; border-color: var(--brand); }
input:user-invalid, textarea:user-invalid { border-color: #c00; }
button { justify-self: start; padding: .7rem 1.4rem; background: var(-
-brand); color: #fff; border: 0; border-radius: 999px; cursor:
pointer; }
address { margin-top: 2rem; font-style: normal; color: var(--muted); }
```

Project 83 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - Contact</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Contact Sinai Trekking Club	The main heading; only one per page.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
	Generic block container for grouping and layout.
<label for="name">Your name</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="name" name="name" type="text" required autocomplete="name">	A form control; its type decides what it looks like.

Line	What it does
<input id="email" name="email" type="email" required autocomplete="...	Email field: validated automatically and shows the @ keyboard on phones.
<select id="topic" name="topic">	Drop-down list.
<option>Mount Sinai sunrise</option>	One choice in a select or datalist.
<textarea id="msg" name="message" rows="5" required minlength="10">...	Multi-line text field.
<button type="submit">Send message</button>	A clickable button; inside a form it submits by default.
<address>Sinai Trekking Club, Saint Catherine · <a href="mai...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
font-weight: 600;	Thickness of the text.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
width: 100%;	Fills the container width.
input:focus-visible, select:focus-visible, textarea:focus-visible {	Applies when the element is focused by keyboard; keeps focus rings visible.
border-color: var(--brand);	The line around the element: width, style and colour.
input:user-invalid, textarea:user-invalid {	A field the user has edited that fails validation.
background: var(--brand);	Background colour or image.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Clicking a label focuses its control
- Empty submit is blocked
- Focus ring visible
- Address is real contact info, not italic

Exercises

1. Add a checkbox for newsletter consent.
2. Put name and email side by side on wide screens.
3. Add a pattern attribute for an Egyptian phone number.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 84: Contact form for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 1 | Files: index.html, styles.css

Brief

Build a contact form with text, email, select and textarea controls, proper labels, built-in validation and a styled submit button.

Learning goals

- Connect every label to its control with for/id
- Use input types and required for free validation
- Style focus and invalid states

Elements and CSS used

HTML elements	CSS features
form, label, input, select, option, textarea, button, address, a	display: grid, gap, font: inherit, :focus-visible, :user-invalid, border-radius

Build guide

1. Create the form with action and method.
2. Add one .row per field: a label followed by its control; match for and id.
3. Use type="email", required and minlength.
4. Add the select with one option per offer.
5. Style with Grid gaps; make controls full width and inherit the page font.
6. Submit the empty form and watch the browser's validation messages.

Project 84: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - Contact</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Contact Horizon Photography</h1>
    <form action="/contact" method="post" class="form">
      <div class="row">
        <label for="name">Your name</label>
        <input id="name" name="name" type="text" required
autocomplete="name">
      </div>
      <div class="row">
        <label for="email">Email</label>
        <input id="email" name="email" type="email" required
autocomplete="email">
      </div>
      <div class="row">
        <label for="topic">Topic</label>
        <select id="topic" name="topic">
    <option>Portrait session</option>
    <option>Wedding day</option>
    <option>Product shoot</option>
    <option>Family session</option>
          <option>Something else</option>
        </select>
      </div>
      <div class="row">
        <label for="msg">Message</label>
        <textarea id="msg" name="message" rows="5" required
minlength="10"></textarea>
      </div>
      <button type="submit">Send message</button>
    </form>
    <address>Horizon Photography, Maadi &middot; <a href="mailto:
hello@photo.example">hello@photo.example</a></address>
  </main>
</body>
</html>
```

Project 84: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.form { display: grid; gap: 1rem; }
.row { display: grid; gap: .3rem; }
label { font-weight: 600; }
input, select, textarea, button { font: inherit; }
input, select, textarea { padding: .6rem .8rem; border: 1px solid
#bbb; border-radius: 8px; width: 100%; }
input:focus-visible, select:focus-visible, textarea:focus-visible {
outline: 3px solid #ffbf47; border-color: var(--brand); }
input:user-invalid, textarea:user-invalid { border-color: #c00; }
button { justify-self: start; padding: .7rem 1.4rem; background: var(-
-brand); color: #fff; border: 0; border-radius: 999px; cursor:
pointer; }
address { margin-top: 2rem; font-style: normal; color: var(--muted); }
```

Project 84 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - Contact</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Contact Horizon Photography	The main heading; only one per page.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
	Generic block container for grouping and layout.
<label for="name">Your name</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="name" name="name" type="text" required autocomplete="name">	A form control; its type decides what it looks like.

Line	What it does
<input id="email" name="email" type="email" required autocomplete="...	Email field: validated automatically and shows the @ keyboard on phones.
<select id="topic" name="topic">	Drop-down list.
<option>Portrait session</option>	One choice in a select or datalist.
<textarea id="msg" name="message" rows="5" required minlength="10">...	Multi-line text field.
<button type="submit">Send message</button>	A clickable button; inside a form it submits by default.
<address>Horizon Photography, Maadi · <a href="mailto:hello@...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
font-weight: 600;	Thickness of the text.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
width: 100%;	Fills the container width.
input:focus-visible, select:focus-visible, textarea:focus-visible {	Applies when the element is focused by keyboard; keeps focus rings visible.
border-color: var(--brand);	The line around the element: width, style and colour.
input:user-invalid, textarea:user-invalid {	A field the user has edited that fails validation.
background: var(--brand);	Background colour or image.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Clicking a label focuses its control
- Empty submit is blocked
- Focus ring visible
- Address is real contact info, not italic

Exercises

1. Add a checkbox for newsletter consent.
2. Put name and email side by side on wide screens.
3. Add a pattern attribute for an Egyptian phone number.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 85: Contact form for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 1 | Files: index.html, styles.css

Brief

Build a contact form with text, email, select and textarea controls, proper labels, built-in validation and a styled submit button.

Learning goals

- Connect every label to its control with for/id
- Use input types and required for free validation
- Style focus and invalid states

Elements and CSS used

HTML elements	CSS features
form, label, input, select, option, textarea, button, address, a	display: grid, gap, font: inherit, :focus-visible, :user-invalid, border-radius

Build guide

1. Create the form with action and method.
2. Add one .row per field: a label followed by its control; match for and id.
3. Use type="email", required and minlength.
4. Add the select with one option per offer.
5. Style with Grid gaps; make controls full width and inherit the page font.
6. Submit the empty form and watch the browser's validation messages.

Project 85: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - Contact</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Contact Papyrus Stationery</h1>
    <form action="/contact" method="post" class="form">
      <div class="row">
        <label for="name">Your name</label>
        <input id="name" name="name" type="text" required
autocomplete="name">
      </div>
      <div class="row">
        <label for="email">Email</label>
        <input id="email" name="email" type="email" required
autocomplete="email">
      </div>
      <div class="row">
        <label for="topic">Topic</label>
        <select id="topic" name="topic">
    <option>Dotted notebook</option>
    <option>Fountain pen</option>
    <option>Washi tape set</option>
    <option>Desk planner</option>
          <option>Something else</option>
        </select>
      </div>
      <div class="row">
        <label for="msg">Message</label>
        <textarea id="msg" name="message" rows="5" required
minlength="10"></textarea>
      </div>
      <button type="submit">Send message</button>
    </form>
    <address>Papyrus Stationery, Heliopolis &middot; <a href="mailto:
hello@stationery.example">hello@stationery.example</a></address>
  </main>
</body>
</html>
```

Project 85: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.form { display: grid; gap: 1rem; }
.row { display: grid; gap: .3rem; }
label { font-weight: 600; }
input, select, textarea, button { font: inherit; }
input, select, textarea { padding: .6rem .8rem; border: 1px solid
#bbb; border-radius: 8px; width: 100%; }
input:focus-visible, select:focus-visible, textarea:focus-visible {
outline: 3px solid #ffbf47; border-color: var(--brand); }
input:user-invalid, textarea:user-invalid { border-color: #c00; }
button { justify-self: start; padding: .7rem 1.4rem; background: var(-
-brand); color: #fff; border: 0; border-radius: 999px; cursor:
pointer; }
address { margin-top: 2rem; font-style: normal; color: var(--muted); }
```

Project 85 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - Contact</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Contact Papyrus Stationery	The main heading; only one per page.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
	Generic block container for grouping and layout.
<label for="name">Your name</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="name" name="name" type="text" required autocomplete="name">	A form control; its type decides what it looks like.

Line	What it does
<input id="email" name="email" type="email" required autocomplete="...	Email field: validated automatically and shows the @ keyboard on phones.
<select id="topic" name="topic">	Drop-down list.
<option>Dotted notebook</option>	One choice in a select or datalist.
<textarea id="msg" name="message" rows="5" required minlength="10">...	Multi-line text field.
<button type="submit">Send message</button>	A clickable button; inside a form it submits by default.
<address>Papyrus Stationery, Heliopolis · <a href="mailto:he...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
font-weight: 600;	Thickness of the text.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
width: 100%;	Fills the container width.
input:focus-visible, select:focus-visible, textarea:focus-visible {	Applies when the element is focused by keyboard; keeps focus rings visible.
border-color: var(--brand);	The line around the element: width, style and colour.
input:user-invalid, textarea:user-invalid {	A field the user has edited that fails validation.
background: var(--brand);	Background colour or image.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Clicking a label focuses its control
- Empty submit is blocked
- Focus ring visible
- Address is real contact info, not italic

Exercises

1. Add a checkbox for newsletter consent.
2. Put name and email side by side on wide screens.
3. Add a pattern attribute for an Egyptian phone number.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 86: Contact form for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 1 | Files: index.html, styles.css

Brief

Build a contact form with text, email, select and textarea controls, proper labels, built-in validation and a styled submit button.

Learning goals

- Connect every label to its control with for/id
- Use input types and required for free validation
- Style focus and invalid states

Elements and CSS used

HTML elements	CSS features
form, label, input, select, option, textarea, button, address, a	display: grid, gap, font: inherit, :focus-visible, :user-invalid, border-radius

Build guide

1. Create the form with action and method.
2. Add one .row per field: a label followed by its control; match for and id.
3. Use type="email", required and minlength.
4. Add the select with one option per offer.
5. Style with Grid gaps; make controls full width and inherit the page font.

6. Submit the empty form and watch the browser's validation messages.

Project 86: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - Contact</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Contact Oasis Plant Nursery</h1>
    <form action="/contact" method="post" class="form">
      <div class="row">
        <label for="name">Your name</label>
        <input id="name" name="name" type="text" required
autocomplete="name">
      </div>
      <div class="row">
        <label for="email">Email</label>
        <input id="email" name="email" type="email" required
autocomplete="email">
      </div>
      <div class="row">
        <label for="topic">Topic</label>
        <select id="topic" name="topic">
    <option>Monstera</option>
    <option>Snake plant</option>
    <option>Basil pot</option>
    <option>Olive tree</option>
          <option>Something else</option>
        </select>
      </div>
      <div class="row">
        <label for="msg">Message</label>
        <textarea id="msg" name="message" rows="5" required
minlength="10"></textarea>
      </div>
      <button type="submit">Send message</button>
    </form>
    <address>Oasis Plant Nursery, Sheikh Zayed &middot; <a
href="mailto:hello@plants.example">hello@plants.example</a></address>
  </main>
</body>
</html>
```

Project 86: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.form { display: grid; gap: 1rem; }
.row { display: grid; gap: .3rem; }
label { font-weight: 600; }
input, select, textarea, button { font: inherit; }
input, select, textarea { padding: .6rem .8rem; border: 1px solid
#bbb; border-radius: 8px; width: 100%; }
input:focus-visible, select:focus-visible, textarea:focus-visible {
outline: 3px solid #ffbf47; border-color: var(--brand); }
input:user-invalid, textarea:user-invalid { border-color: #c00; }
button { justify-self: start; padding: .7rem 1.4rem; background: var(-
-brand); color: #fff; border: 0; border-radius: 999px; cursor:
pointer; }
address { margin-top: 2rem; font-style: normal; color: var(--muted); }
```

Project 86 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - Contact</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Contact Oasis Plant Nursery	The main heading; only one per page.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
	Generic block container for grouping and layout.
<label for="name">Your name</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="name" name="name" type="text" required autocomplete="name">	A form control; its type decides what it looks like.

Line	What it does
<input id="email" name="email" type="email" required autocomplete="...	Email field: validated automatically and shows the @ keyboard on phones.
<select id="topic" name="topic">	Drop-down list.
<option>Monstera</option>	One choice in a select or datalist.
<textarea id="msg" name="message" rows="5" required minlength="10">...	Multi-line text field.
<button type="submit">Send message</button>	A clickable button; inside a form it submits by default.
<address>Oasis Plant Nursery, Sheikh Zayed · <a href="mailto...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
font-weight: 600;	Thickness of the text.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
width: 100%;	Fills the container width.
input:focus-visible, select:focus-visible, textarea:focus-visible {	Applies when the element is focused by keyboard; keeps focus rings visible.
border-color: var(--brand);	The line around the element: width, style and colour.
input:user-invalid, textarea:user-invalid {	A field the user has edited that fails validation.
background: var(--brand);	Background colour or image.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Clicking a label focuses its control
- Empty submit is blocked
- Focus ring visible
- Address is real contact info, not italic

Exercises

1. Add a checkbox for newsletter consent.
2. Put name and email side by side on wide screens.
3. Add a pattern attribute for an Egyptian phone number.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 87: Contact form for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 1 | Files: index.html, styles.css

Brief

Build a contact form with text, email, select and textarea controls, proper labels, built-in validation and a styled submit button.

Learning goals

- Connect every label to its control with for/id
- Use input types and required for free validation
- Style focus and invalid states

Elements and CSS used

HTML elements	CSS features
form, label, input, select, option, textarea, button, address, a	display: grid, gap, font: inherit, :focus-visible, :user-invalid, border-radius

Build guide

1. Create the form with action and method.
2. Add one .row per field: a label followed by its control; match for and id.
3. Use type="email", required and minlength.
4. Add the select with one option per offer.
5. Style with Grid gaps; make controls full width and inherit the page font.
6. Submit the empty form and watch the browser's validation messages.

Project 87: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - Contact</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Contact Cedar Furniture</h1>
    <form action="/contact" method="post" class="form">
      <div class="row">
        <label for="name">Your name</label>
        <input id="name" name="name" type="text" required
autocomplete="name">
      </div>
      <div class="row">
        <label for="email">Email</label>
        <input id="email" name="email" type="email" required
autocomplete="email">
      </div>
      <div class="row">
        <label for="topic">Topic</label>
        <select id="topic" name="topic">
    <option>Oak dining table</option>
    <option>Bookshelf</option>
    <option>Bedside table</option>
    <option>Coffee table</option>
          <option>Something else</option>
        </select>
      </div>
      <div class="row">
        <label for="msg">Message</label>
        <textarea id="msg" name="message" rows="5" required
minlength="10"></textarea>
      </div>
      <button type="submit">Send message</button>
    </form>
    <address>Cedar Furniture, Damietta &middot; <a href="mailto:
hello@furniture.example">hello@furniture.example</a></address>
  </main>
</body>
</html>
```

Project 87: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.form { display: grid; gap: 1rem; }
.row { display: grid; gap: .3rem; }
label { font-weight: 600; }
input, select, textarea, button { font: inherit; }
input, select, textarea { padding: .6rem .8rem; border: 1px solid
#bbb; border-radius: 8px; width: 100%; }
input:focus-visible, select:focus-visible, textarea:focus-visible {
outline: 3px solid #ffbf47; border-color: var(--brand); }
input:user-invalid, textarea:user-invalid { border-color: #c00; }
button { justify-self: start; padding: .7rem 1.4rem; background: var(-
-brand); color: #fff; border: 0; border-radius: 999px; cursor:
pointer; }
address { margin-top: 2rem; font-style: normal; color: var(--muted); }
```

Project 87 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - Contact</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Contact Cedar Furniture	The main heading; only one per page.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
	Generic block container for grouping and layout.
<label for="name">Your name</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="name" name="name" type="text" required autocomplete="name">	A form control; its type decides what it looks like.

Line	What it does
<input id="email" name="email" type="email" required autocomplete="...	Email field: validated automatically and shows the @ keyboard on phones.
<select id="topic" name="topic">	Drop-down list.
<option>Oak dining table</option>	One choice in a select or datalist.
<textarea id="msg" name="message" rows="5" required minlength="10">...	Multi-line text field.
<button type="submit">Send message</button>	A clickable button; inside a form it submits by default.
<address>Cedar Furniture, Damietta · <a href="mailto:hello@f...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
font-weight: 600;	Thickness of the text.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
width: 100%;	Fills the container width.
input:focus-visible, select:focus-visible, textarea:focus-visible {	Applies when the element is focused by keyboard; keeps focus rings visible.
border-color: var(--brand);	The line around the element: width, style and colour.
input:user-invalid, textarea:user-invalid {	A field the user has edited that fails validation.
background: var(--brand);	Background colour or image.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Clicking a label focuses its control
- Empty submit is blocked
- Focus ring visible
- Address is real contact info, not italic

Exercises

1. Add a checkbox for newsletter consent.
2. Put name and email side by side on wide screens.
3. Add a pattern attribute for an Egyptian phone number.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 88: Contact form for Byte Repair

Theme: Byte Repair (Nasr City) | Level 1 | Files: index.html, styles.css

Brief

Build a contact form with text, email, select and textarea controls, proper labels, built-in validation and a styled submit button.

Learning goals

- Connect every label to its control with for/id
- Use input types and required for free validation
- Style focus and invalid states

Elements and CSS used

HTML elements	CSS features
form, label, input, select, option, textarea, button, address, a	display: grid, gap, font: inherit, :focus-visible, :user-invalid, border-radius

Build guide

1. Create the form with action and method.
2. Add one .row per field: a label followed by its control; match for and id.
3. Use type="email", required and minlength.
4. Add the select with one option per offer.
5. Style with Grid gaps; make controls full width and inherit the page font.
6. Submit the empty form and watch the browser's validation messages.

Project 88: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - Contact</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Contact Byte Repair</h1>
    <form action="/contact" method="post" class="form">
      <div class="row">
        <label for="name">Your name</label>
        <input id="name" name="name" type="text" required
autocomplete="name">
      </div>
      <div class="row">
        <label for="email">Email</label>
        <input id="email" name="email" type="email" required
autocomplete="email">
      </div>
      <div class="row">
        <label for="topic">Topic</label>
        <select id="topic" name="topic">
    <option>Screen replacement</option>
    <option>Battery swap</option>
    <option>Laptop cleaning</option>
    <option>Data recovery</option>
          <option>Something else</option>
        </select>
      </div>
      <div class="row">
        <label for="msg">Message</label>
        <textarea id="msg" name="message" rows="5" required
minlength="10"></textarea>
      </div>
      <button type="submit">Send message</button>
    </form>
    <address>Byte Repair, Nasr City &middot; <a href="mailto:
hello@repair.example">hello@repair.example</a></address>
  </main>
</body>
</html>
```

Project 88: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.form { display: grid; gap: 1rem; }
.row { display: grid; gap: .3rem; }
label { font-weight: 600; }
input, select, textarea, button { font: inherit; }
input, select, textarea { padding: .6rem .8rem; border: 1px solid
#bbb; border-radius: 8px; width: 100%; }
input:focus-visible, select:focus-visible, textarea:focus-visible {
outline: 3px solid #ffbf47; border-color: var(--brand); }
input:user-invalid, textarea:user-invalid { border-color: #c00; }
button { justify-self: start; padding: .7rem 1.4rem; background: var(-
-brand); color: #fff; border: 0; border-radius: 999px; cursor:
pointer; }
address { margin-top: 2rem; font-style: normal; color: var(--muted); }
```

Project 88 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - Contact</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Contact Byte Repair	The main heading; only one per page.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
	Generic block container for grouping and layout.
<label for="name">Your name</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="name" name="name" type="text" required autocomplete="name">	A form control; its type decides what it looks like.

Line	What it does
<input id="email" name="email" type="email" required autocomplete="...	Email field: validated automatically and shows the @ keyboard on phones.
<select id="topic" name="topic">	Drop-down list.
<option>Screen replacement</option>	One choice in a select or datalist.
<textarea id="msg" name="message" rows="5" required minlength="10">...	Multi-line text field.
<button type="submit">Send message</button>	A clickable button; inside a form it submits by default.
<address>Byte Repair, Nasr City · <a href="mailto:hello@repa...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
font-weight: 600;	Thickness of the text.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
width: 100%;	Fills the container width.
input:focus-visible, select:focus-visible, textarea:focus-visible {	Applies when the element is focused by keyboard; keeps focus rings visible.
border-color: var(--brand);	The line around the element: width, style and colour.
input:user-invalid, textarea:user-invalid {	A field the user has edited that fails validation.
background: var(--brand);	Background colour or image.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Clicking a label focuses its control
- Empty submit is blocked
- Focus ring visible
- Address is real contact info, not italic

Exercises

1. Add a checkbox for newsletter consent.
2. Put name and email side by side on wide screens.
3. Add a pattern attribute for an Egyptian phone number.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 89: Contact form for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 1 | Files: index.html, styles.css

Brief

Build a contact form with text, email, select and textarea controls, proper labels, built-in validation and a styled submit button.

Learning goals

- Connect every label to its control with for/id
- Use input types and required for free validation
- Style focus and invalid states

Elements and CSS used

HTML elements	CSS features
form, label, input, select, option, textarea, button, address, a	display: grid, gap, font: inherit, :focus-visible, :user-invalid, border-radius

Build guide

1. Create the form with action and method.
2. Add one .row per field: a label followed by its control; match for and id.
3. Use type="email", required and minlength.
4. Add the select with one option per offer.
5. Style with Grid gaps; make controls full width and inherit the page font.
6. Submit the empty form and watch the browser's validation messages.

Project 89: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - Contact</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Contact Sahara Pet Care</h1>
    <form action="/contact" method="post" class="form">
      <div class="row">
        <label for="name">Your name</label>
        <input id="name" name="name" type="text" required
autocomplete="name">
      </div>
      <div class="row">
        <label for="email">Email</label>
        <input id="email" name="email" type="email" required
autocomplete="email">
      </div>
      <div class="row">
        <label for="topic">Topic</label>
        <select id="topic" name="topic">
    <option>Full grooming</option>
    <option>Day boarding</option>
    <option>Vaccination</option>
    <option>Dog walking</option>
          <option>Something else</option>
        </select>
      </div>
      <div class="row">
        <label for="msg">Message</label>
        <textarea id="msg" name="message" rows="5" required
minlength="10"></textarea>
      </div>
      <button type="submit">Send message</button>
    </form>
    <address>Sahara Pet Care, New Cairo &middot; <a href="mailto:
hello@pets.example">hello@pets.example</a></address>
  </main>
</body>
</html>
```

Project 89: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.form { display: grid; gap: 1rem; }
.row { display: grid; gap: .3rem; }
label { font-weight: 600; }
input, select, textarea, button { font: inherit; }
input, select, textarea { padding: .6rem .8rem; border: 1px solid
#bbb; border-radius: 8px; width: 100%; }
input:focus-visible, select:focus-visible, textarea:focus-visible {
outline: 3px solid #ffbf47; border-color: var(--brand); }
input:user-invalid, textarea:user-invalid { border-color: #c00; }
button { justify-self: start; padding: .7rem 1.4rem; background: var(-
-brand); color: #fff; border: 0; border-radius: 999px; cursor:
pointer; }
address { margin-top: 2rem; font-style: normal; color: var(--muted); }
```

Project 89 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - Contact</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Contact Sahara Pet Care	The main heading; only one per page.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
	Generic block container for grouping and layout.
<label for="name">Your name</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="name" name="name" type="text" required autocomplete="name">	A form control; its type decides what it looks like.

Line	What it does
<input id="email" name="email" type="email" required autocomplete="...	Email field: validated automatically and shows the @ keyboard on phones.
<select id="topic" name="topic">	Drop-down list.
<option>Full grooming</option>	One choice in a select or datalist.
<textarea id="msg" name="message" rows="5" required minlength="10">...	Multi-line text field.
<button type="submit">Send message</button>	A clickable button; inside a form it submits by default.
<address>Sahara Pet Care, New Cairo · <a href="mailto:hello@...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
font-weight: 600;	Thickness of the text.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
width: 100%;	Fills the container width.
input:focus-visible, select:focus-visible, textarea:focus-visible {	Applies when the element is focused by keyboard; keeps focus rings visible.
border-color: var(--brand);	The line around the element: width, style and colour.
input:user-invalid, textarea:user-invalid {	A field the user has edited that fails validation.
background: var(--brand);	Background colour or image.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Clicking a label focuses its control
- Empty submit is blocked
- Focus ring visible
- Address is real contact info, not italic

Exercises

1. Add a checkbox for newsletter consent.
2. Put name and email side by side on wide screens.
3. Add a pattern attribute for an Egyptian phone number.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 90: Contact form for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Build a contact form with text, email, select and textarea controls, proper labels, built-in validation and a styled submit button.

Learning goals

- Connect every label to its control with for/id
- Use input types and required for free validation
- Style focus and invalid states

Elements and CSS used

HTML elements	CSS features
form, label, input, select, option, textarea, button, address, a	display: grid, gap, font: inherit, :focus-visible, :user-invalid, border-radius

Build guide

1. Create the form with action and method.
2. Add one .row per field: a label followed by its control; match for and id.
3. Use type="email", required and minlength.
4. Add the select with one option per offer.
5. Style with Grid gaps; make controls full width and inherit the page font.

6. Submit the empty form and watch the browser's validation messages.

Project 90: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - Contact</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Contact Alexandria Sailing School</h1>
    <form action="/contact" method="post" class="form">
      <div class="row">
        <label for="name">Your name</label>
        <input id="name" name="name" type="text" required
autocomplete="name">
      </div>
      <div class="row">
        <label for="email">Email</label>
        <input id="email" name="email" type="email" required
autocomplete="email">
      </div>
      <div class="row">
        <label for="topic">Topic</label>
        <select id="topic" name="topic">
    <option>Taster session</option>
    <option>Beginner course</option>
    <option>Racing clinic</option>
    <option>Private lesson</option>
          <option>Something else</option>
        </select>
      </div>
      <div class="row">
        <label for="msg">Message</label>
        <textarea id="msg" name="message" rows="5" required
minlength="10"></textarea>
      </div>
      <button type="submit">Send message</button>
    </form>
    <address>Alexandria Sailing School, Alexandria &middot; <a
href="mailto:hello@sailing.example">hello@sailing.example</a></
address>
  </main>
</body>
</html>
```

Project 90: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.form { display: grid; gap: 1rem; }
.row { display: grid; gap: .3rem; }
label { font-weight: 600; }
input, select, textarea, button { font: inherit; }
input, select, textarea { padding: .6rem .8rem; border: 1px solid
#bbb; border-radius: 8px; width: 100%; }
input:focus-visible, select:focus-visible, textarea:focus-visible {
outline: 3px solid #ffbf47; border-color: var(--brand); }
input:user-invalid, textarea:user-invalid { border-color: #c00; }
button { justify-self: start; padding: .7rem 1.4rem; background: var(-
-brand); color: #fff; border: 0; border-radius: 999px; cursor:
pointer; }
address { margin-top: 2rem; font-style: normal; color: var(--muted); }
```

Project 90 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - Contact</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Contact Alexandria Sailing School	The main heading; only one per page.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
	Generic block container for grouping and layout.
<label for="name">Your name</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="name" name="name" type="text" required autocomplete="name">	A form control; its type decides what it looks like.

Line	What it does
<input id="email" name="email" type="email" required autocomplete="...	Email field: validated automatically and shows the @ keyboard on phones.
<select id="topic" name="topic">	Drop-down list.
<option>Taster session</option>	One choice in a select or datalist.
<textarea id="msg" name="message" rows="5" required minlength="10">...	Multi-line text field.
<button type="submit">Send message</button>	A clickable button; inside a form it submits by default.
<address>Alexandria Sailing School, Alexandria · <a href="ma...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
font-weight: 600;	Thickness of the text.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
width: 100%;	Fills the container width.
input:focus-visible, select:focus-visible, textarea:focus-visible {	Applies when the element is focused by keyboard; keeps focus rings visible.
border-color: var(--brand);	The line around the element: width, style and colour.
input:user-invalid, textarea:user-invalid {	A field the user has edited that fails validation.
background: var(--brand);	Background colour or image.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Clicking a label focuses its control
- Empty submit is blocked
- Focus ring visible
- Address is real contact info, not italic

Exercises

1. Add a checkbox for newsletter consent.
2. Put name and email side by side on wide screens.
3. Add a pattern attribute for an Egyptian phone number.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 91: Contact form for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Build a contact form with text, email, select and textarea controls, proper labels, built-in validation and a styled submit button.

Learning goals

- Connect every label to its control with for/id
- Use input types and required for free validation
- Style focus and invalid states

Elements and CSS used

HTML elements	CSS features
form, label, input, select, option, textarea, button, address, a	display: grid, gap, font: inherit, :focus-visible, :user-invalid, border-radius

Build guide

1. Create the form with action and method.
2. Add one .row per field: a label followed by its control; match for and id.
3. Use type="email", required and minlength.
4. Add the select with one option per offer.
5. Style with Grid gaps; make controls full width and inherit the page font.

6. Submit the empty form and watch the browser's validation messages.

Project 91: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - Contact</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Contact Habiba Handmade Jewellery</h1>
    <form action="/contact" method="post" class="form">
      <div class="row">
        <label for="name">Your name</label>
        <input id="name" name="name" type="text" required
autocomplete="name">
      </div>
      <div class="row">
        <label for="email">Email</label>
        <input id="email" name="email" type="email" required
autocomplete="email">
      </div>
      <div class="row">
        <label for="topic">Topic</label>
        <select id="topic" name="topic">
    <option>Lotus pendant</option>
    <option>Brass cuff</option>
    <option>Bead earrings</option>
    <option>Ankh ring</option>
          <option>Something else</option>
        </select>
      </div>
      <div class="row">
        <label for="msg">Message</label>
        <textarea id="msg" name="message" rows="5" required
minlength="10"></textarea>
      </div>
      <button type="submit">Send message</button>
    </form>
    <address>Habiba Handmade Jewellery, Aswan &middot; <a
href="mailto:hello@jewellery.example">hello@jewellery.example</a></
address>
  </main>
</body>
</html>
```

Project 91: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.form { display: grid; gap: 1rem; }
.row { display: grid; gap: .3rem; }
label { font-weight: 600; }
input, select, textarea, button { font: inherit; }
input, select, textarea { padding: .6rem .8rem; border: 1px solid
#bbb; border-radius: 8px; width: 100%; }
input:focus-visible, select:focus-visible, textarea:focus-visible {
outline: 3px solid #ffbf47; border-color: var(--brand); }
input:user-invalid, textarea:user-invalid { border-color: #c00; }
button { justify-self: start; padding: .7rem 1.4rem; background: var(-
-brand); color: #fff; border: 0; border-radius: 999px; cursor:
pointer; }
address { margin-top: 2rem; font-style: normal; color: var(--muted); }
```

Project 91 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - Contact</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Contact Habiba Handmade Jewellery	The main heading; only one per page.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
	Generic block container for grouping and layout.
<label for="name">Your name</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="name" name="name" type="text" required autocomplete="name">	A form control; its type decides what it looks like.

Line	What it does
<input id="email" name="email" type="email" required autocomplete="...	Email field: validated automatically and shows the @ keyboard on phones.
<select id="topic" name="topic">	Drop-down list.
<option>Lotus pendant</option>	One choice in a select or datalist.
<textarea id="msg" name="message" rows="5" required minlength="10">...	Multi-line text field.
<button type="submit">Send message</button>	A clickable button; inside a form it submits by default.
<address>Habiba Handmade Jewellery, Aswan · <a href="mailto:...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
font-weight: 600;	Thickness of the text.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
width: 100%;	Fills the container width.
input:focus-visible, select:focus-visible, textarea:focus-visible {	Applies when the element is focused by keyboard; keeps focus rings visible.
border-color: var(--brand);	The line around the element: width, style and colour.
input:user-invalid, textarea:user-invalid {	A field the user has edited that fails validation.
background: var(--brand);	Background colour or image.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Clicking a label focuses its control
- Empty submit is blocked
- Focus ring visible
- Address is real contact info, not italic

Exercises

1. Add a checkbox for newsletter consent.
2. Put name and email side by side on wide screens.
3. Add a pattern attribute for an Egyptian phone number.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 92: Contact form for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 1 | Files: index.html, styles.css

Brief

Build a contact form with text, email, select and textarea controls, proper labels, built-in validation and a styled submit button.

Learning goals

- Connect every label to its control with for/id
- Use input types and required for free validation
- Style focus and invalid states

Elements and CSS used

HTML elements	CSS features
form, label, input, select, option, textarea, button, address, a	display: grid, gap, font: inherit, :focus-visible, :user-invalid, border-radius

Build guide

1. Create the form with action and method.
2. Add one .row per field: a label followed by its control; match for and id.
3. Use type="email", required and minlength.
4. Add the select with one option per offer.
5. Style with Grid gaps; make controls full width and inherit the page font.

6. Submit the empty form and watch the browser's validation messages.

Project 92: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - Contact</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Contact Fayoum Pottery Studio</h1>
    <form action="/contact" method="post" class="form">
      <div class="row">
        <label for="name">Your name</label>
        <input id="name" name="name" type="text" required
autocomplete="name">
      </div>
      <div class="row">
        <label for="email">Email</label>
        <input id="email" name="email" type="email" required
autocomplete="email">
      </div>
      <div class="row">
        <label for="topic">Topic</label>
        <select id="topic" name="topic">
    <option>Intro to the wheel</option>
    <option>Glazing day</option>
    <option>Kids clay class</option>
    <option>Weekend retreat</option>
          <option>Something else</option>
        </select>
      </div>
      <div class="row">
        <label for="msg">Message</label>
        <textarea id="msg" name="message" rows="5" required
minlength="10"></textarea>
      </div>
      <button type="submit">Send message</button>
    </form>
    <address>Fayoum Pottery Studio, Tunis Village &middot; <a
href="mailto:hello@pottery.example">hello@pottery.example</a></
address>
  </main>
</body>
</html>
```

Project 92: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.form { display: grid; gap: 1rem; }
.row { display: grid; gap: .3rem; }
label { font-weight: 600; }
input, select, textarea, button { font: inherit; }
input, select, textarea { padding: .6rem .8rem; border: 1px solid
#bbb; border-radius: 8px; width: 100%; }
input:focus-visible, select:focus-visible, textarea:focus-visible {
outline: 3px solid #ffbf47; border-color: var(--brand); }
input:user-invalid, textarea:user-invalid { border-color: #c00; }
button { justify-self: start; padding: .7rem 1.4rem; background: var(-
-brand); color: #fff; border: 0; border-radius: 999px; cursor:
pointer; }
address { margin-top: 2rem; font-style: normal; color: var(--muted); }
```

Project 92 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - Contact</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Contact Fayoum Pottery Studio	The main heading; only one per page.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
	Generic block container for grouping and layout.
<label for="name">Your name</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="name" name="name" type="text" required autocomplete="name">	A form control; its type decides what it looks like.

Line	What it does
<input id="email" name="email" type="email" required autocomplete="...	Email field: validated automatically and shows the @ keyboard on phones.
<select id="topic" name="topic">	Drop-down list.
<option>Intro to the wheel</option>	One choice in a select or datalist.
<textarea id="msg" name="message" rows="5" required minlength="10">...	Multi-line text field.
<button type="submit">Send message</button>	A clickable button; inside a form it submits by default.
<address>Fayoum Pottery Studio, Tunis Village · <a href="mai...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
font-weight: 600;	Thickness of the text.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
width: 100%;	Fills the container width.
input:focus-visible, select:focus-visible, textarea:focus-visible {	Applies when the element is focused by keyboard; keeps focus rings visible.
border-color: var(--brand);	The line around the element: width, style and colour.
input:user-invalid, textarea:user-invalid {	A field the user has edited that fails validation.
background: var(--brand);	Background colour or image.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Clicking a label focuses its control
- Empty submit is blocked
- Focus ring visible
- Address is real contact info, not italic

Exercises

1. Add a checkbox for newsletter consent.
2. Put name and email side by side on wide screens.
3. Add a pattern attribute for an Egyptian phone number.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 93: Contact form for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 1 | Files: index.html, styles.css

Brief

Build a contact form with text, email, select and textarea controls, proper labels, built-in validation and a styled submit button.

Learning goals

- Connect every label to its control with for/id
- Use input types and required for free validation
- Style focus and invalid states

Elements and CSS used

HTML elements	CSS features
form, label, input, select, option, textarea, button, address, a	display: grid, gap, font: inherit, :focus-visible, :user-invalid, border-radius

Build guide

1. Create the form with action and method.
2. Add one .row per field: a label followed by its control; match for and id.
3. Use type="email", required and minlength.
4. Add the select with one option per offer.
5. Style with Grid gaps; make controls full width and inherit the page font.

6. Submit the empty form and watch the browser's validation messages.

Project 93: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - Contact</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Contact Cleopatra Beauty Salon</h1>
    <form action="/contact" method="post" class="form">
      <div class="row">
        <label for="name">Your name</label>
        <input id="name" name="name" type="text" required
autocomplete="name">
      </div>
      <div class="row">
        <label for="email">Email</label>
        <input id="email" name="email" type="email" required
autocomplete="email">
      </div>
      <div class="row">
        <label for="topic">Topic</label>
        <select id="topic" name="topic">
    <option>Haircut and blow-dry</option>
    <option>Manicure</option>
    <option>Facial</option>
    <option>Bridal package</option>
          <option>Something else</option>
        </select>
      </div>
      <div class="row">
        <label for="msg">Message</label>
        <textarea id="msg" name="message" rows="5" required
minlength="10"></textarea>
      </div>
      <button type="submit">Send message</button>
    </form>
    <address>Cleopatra Beauty Salon, Dokki &middot; <a href="mailto:
hello@salon.example">hello@salon.example</a></address>
  </main>
</body>
</html>
```

Project 93: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.form { display: grid; gap: 1rem; }
.row { display: grid; gap: .3rem; }
label { font-weight: 600; }
input, select, textarea, button { font: inherit; }
input, select, textarea { padding: .6rem .8rem; border: 1px solid
#bbb; border-radius: 8px; width: 100%; }
input:focus-visible, select:focus-visible, textarea:focus-visible {
outline: 3px solid #ffbf47; border-color: var(--brand); }
input:user-invalid, textarea:user-invalid { border-color: #c00; }
button { justify-self: start; padding: .7rem 1.4rem; background: var(-
-brand); color: #fff; border: 0; border-radius: 999px; cursor:
pointer; }
address { margin-top: 2rem; font-style: normal; color: var(--muted); }
```

Project 93 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - Contact</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Contact Cleopatra Beauty Salon	The main heading; only one per page.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
	Generic block container for grouping and layout.
<label for="name">Your name</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="name" name="name" type="text" required autocomplete="name">	A form control; its type decides what it looks like.

Line	What it does
<input id="email" name="email" type="email" required autocomplete="...	Email field: validated automatically and shows the @ keyboard on phones.
<select id="topic" name="topic">	Drop-down list.
<option>Haircut and blow-dry</option>	One choice in a select or datalist.
<textarea id="msg" name="message" rows="5" required minlength="10">...	Multi-line text field.
<button type="submit">Send message</button>	A clickable button; inside a form it submits by default.
<address>Cleopatra Beauty Salon, Dokki · <a href="mailto:hel...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
font-weight: 600;	Thickness of the text.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
width: 100%;	Fills the container width.
input:focus-visible, select:focus-visible, textarea:focus-visible {	Applies when the element is focused by keyboard; keeps focus rings visible.
border-color: var(--brand);	The line around the element: width, style and colour.
input:user-invalid, textarea:user-invalid {	A field the user has edited that fails validation.
background: var(--brand);	Background colour or image.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Clicking a label focuses its control
- Empty submit is blocked
- Focus ring visible
- Address is real contact info, not italic

Exercises

1. Add a checkbox for newsletter consent.
2. Put name and email side by side on wide screens.
3. Add a pattern attribute for an Egyptian phone number.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 94: Contact form for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 1 | Files: index.html, styles.css

Brief

Build a contact form with text, email, select and textarea controls, proper labels, built-in validation and a styled submit button.

Learning goals

- Connect every label to its control with for/id
- Use input types and required for free validation
- Style focus and invalid states

Elements and CSS used

HTML elements	CSS features
form, label, input, select, option, textarea, button, address, a	display: grid, gap, font: inherit, :focus-visible, :user-invalid, border-radius

Build guide

1. Create the form with action and method.
2. Add one .row per field: a label followed by its control; match for and id.
3. Use type="email", required and minlength.
4. Add the select with one option per offer.
5. Style with Grid gaps; make controls full width and inherit the page font.
6. Submit the empty form and watch the browser's validation messages.

Project 94: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - Contact</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Contact Suez Auto Service</h1>
    <form action="/contact" method="post" class="form">
      <div class="row">
        <label for="name">Your name</label>
        <input id="name" name="name" type="text" required
autocomplete="name">
      </div>
      <div class="row">
        <label for="email">Email</label>
        <input id="email" name="email" type="email" required
autocomplete="email">
      </div>
      <div class="row">
        <label for="topic">Topic</label>
        <select id="topic" name="topic">
    <option>Oil change</option>
    <option>Brake pads</option>
    <option>Air conditioning</option>
    <option>Pre-purchase inspection</option>
          <option>Something else</option>
        </select>
      </div>
      <div class="row">
        <label for="msg">Message</label>
        <textarea id="msg" name="message" rows="5" required
minlength="10"></textarea>
      </div>
      <button type="submit">Send message</button>
    </form>
    <address>Suez Auto Service, Suez &middot; <a href="mailto:
hello@auto.example">hello@auto.example</a></address>
  </main>
</body>
</html>
```

Project 94: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.form { display: grid; gap: 1rem; }
.row { display: grid; gap: .3rem; }
label { font-weight: 600; }
input, select, textarea, button { font: inherit; }
input, select, textarea { padding: .6rem .8rem; border: 1px solid
#bbb; border-radius: 8px; width: 100%; }
input:focus-visible, select:focus-visible, textarea:focus-visible {
outline: 3px solid #ffbf47; border-color: var(--brand); }
input:user-invalid, textarea:user-invalid { border-color: #c00; }
button { justify-self: start; padding: .7rem 1.4rem; background: var(-
-brand); color: #fff; border: 0; border-radius: 999px; cursor:
pointer; }
address { margin-top: 2rem; font-style: normal; color: var(--muted); }
```

Project 94 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - Contact</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Contact Suez Auto Service	The main heading; only one per page.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
	Generic block container for grouping and layout.
<label for="name">Your name</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="name" name="name" type="text" required autocomplete="name">	A form control; its type decides what it looks like.

Line	What it does
<input id="email" name="email" type="email" required autocomplete="...	Email field: validated automatically and shows the @ keyboard on phones.
<select id="topic" name="topic">	Drop-down list.
<option>Oil change</option>	One choice in a select or datalist.
<textarea id="msg" name="message" rows="5" required minlength="10">...	Multi-line text field.
<button type="submit">Send message</button>	A clickable button; inside a form it submits by default.
<address>Suez Auto Service, Suez · <a href="mailto:hello@aut...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
font-weight: 600;	Thickness of the text.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
width: 100%;	Fills the container width.
input:focus-visible, select:focus-visible, textarea:focus-visible {	Applies when the element is focused by keyboard; keeps focus rings visible.
border-color: var(--brand);	The line around the element: width, style and colour.
input:user-invalid, textarea:user-invalid {	A field the user has edited that fails validation.
background: var(--brand);	Background colour or image.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Clicking a label focuses its control
- Empty submit is blocked
- Focus ring visible
- Address is real contact info, not italic

Exercises

1. Add a checkbox for newsletter consent.
2. Put name and email side by side on wide screens.
3. Add a pattern attribute for an Egyptian phone number.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 95: Contact form for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 1 | Files: index.html, styles.css

Brief

Build a contact form with text, email, select and textarea controls, proper labels, built-in validation and a styled submit button.

Learning goals

- Connect every label to its control with for/id
- Use input types and required for free validation
- Style focus and invalid states

Elements and CSS used

HTML elements	CSS features
form, label, input, select, option, textarea, button, address, a	display: grid, gap, font: inherit, :focus-visible, :user-invalid, border-radius

Build guide

1. Create the form with action and method.
2. Add one .row per field: a label followed by its control; match for and id.
3. Use type="email", required and minlength.
4. Add the select with one option per offer.
5. Style with Grid gaps; make controls full width and inherit the page font.
6. Submit the empty form and watch the browser's validation messages.

Project 95: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - Contact</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Contact Luxor Music Academy</h1>
    <form action="/contact" method="post" class="form">
      <div class="row">
        <label for="name">Your name</label>
        <input id="name" name="name" type="text" required
autocomplete="name">
      </div>
      <div class="row">
        <label for="email">Email</label>
        <input id="email" name="email" type="email" required
autocomplete="email">
      </div>
      <div class="row">
        <label for="topic">Topic</label>
        <select id="topic" name="topic">
    <option>Oud for beginners</option>
    <option>Piano grade 1</option>
    <option>Guitar chords</option>
    <option>Voice coaching</option>
          <option>Something else</option>
        </select>
      </div>
      <div class="row">
        <label for="msg">Message</label>
        <textarea id="msg" name="message" rows="5" required
minlength="10"></textarea>
      </div>
      <button type="submit">Send message</button>
    </form>
    <address>Luxor Music Academy, Luxor &middot; <a href="mailto:
hello@music.example">hello@music.example</a></address>
  </main>
</body>
</html>
```

Project 95: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.form { display: grid; gap: 1rem; }
.row { display: grid; gap: .3rem; }
label { font-weight: 600; }
input, select, textarea, button { font: inherit; }
input, select, textarea { padding: .6rem .8rem; border: 1px solid
#bbb; border-radius: 8px; width: 100%; }
input:focus-visible, select:focus-visible, textarea:focus-visible {
outline: 3px solid #ffbf47; border-color: var(--brand); }
input:user-invalid, textarea:user-invalid { border-color: #c00; }
button { justify-self: start; padding: .7rem 1.4rem; background: var(-
-brand); color: #fff; border: 0; border-radius: 999px; cursor:
pointer; }
address { margin-top: 2rem; font-style: normal; color: var(--muted); }
```

Project 95 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - Contact</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Contact Luxor Music Academy	The main heading; only one per page.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
	Generic block container for grouping and layout.
<label for="name">Your name</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="name" name="name" type="text" required autocomplete="name">	A form control; its type decides what it looks like.

Line	What it does
<input id="email" name="email" type="email" required autocomplete="...	Email field: validated automatically and shows the @ keyboard on phones.
<select id="topic" name="topic">	Drop-down list.
<option>Oud for beginners</option>	One choice in a select or datalist.
<textarea id="msg" name="message" rows="5" required minlength="10">...	Multi-line text field.
<button type="submit">Send message</button>	A clickable button; inside a form it submits by default.
<address>Luxor Music Academy, Luxor · <a href="mailto:hello@...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
font-weight: 600;	Thickness of the text.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
width: 100%;	Fills the container width.
input:focus-visible, select:focus-visible, textarea:focus-visible {	Applies when the element is focused by keyboard; keeps focus rings visible.
border-color: var(--brand);	The line around the element: width, style and colour.
input:user-invalid, textarea:user-invalid {	A field the user has edited that fails validation.
background: var(--brand);	Background colour or image.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Clicking a label focuses its control
- Empty submit is blocked
- Focus ring visible
- Address is real contact info, not italic

Exercises

1. Add a checkbox for newsletter consent.
2. Put name and email side by side on wide screens.
3. Add a pattern attribute for an Egyptian phone number.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 96: Contact form for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 1 | Files: index.html, styles.css

Brief

Build a contact form with text, email, select and textarea controls, proper labels, built-in validation and a styled submit button.

Learning goals

- Connect every label to its control with for/id
- Use input types and required for free validation
- Style focus and invalid states

Elements and CSS used

HTML elements	CSS features
form, label, input, select, option, textarea, button, address, a	display: grid, gap, font: inherit, :focus-visible, :user-invalid, border-radius

Build guide

1. Create the form with action and method.
2. Add one .row per field: a label followed by its control; match for and id.
3. Use type="email", required and minlength.
4. Add the select with one option per offer.
5. Style with Grid gaps; make controls full width and inherit the page font.
6. Submit the empty form and watch the browser's validation messages.

Project 96: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - Contact</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Contact Port Said Seafood</h1>
    <form action="/contact" method="post" class="form">
      <div class="row">
        <label for="name">Your name</label>
        <input id="name" name="name" type="text" required
autocomplete="name">
      </div>
      <div class="row">
        <label for="email">Email</label>
        <input id="email" name="email" type="email" required
autocomplete="email">
      </div>
      <div class="row">
        <label for="topic">Topic</label>
        <select id="topic" name="topic">
    <option>Grilled sea bass</option>
    <option>Shrimp tagine</option>
    <option>Calamari</option>
    <option>Fish soup</option>
          <option>Something else</option>
        </select>
      </div>
      <div class="row">
        <label for="msg">Message</label>
        <textarea id="msg" name="message" rows="5" required
minlength="10"></textarea>
      </div>
      <button type="submit">Send message</button>
    </form>
    <address>Port Said Seafood, Port Said &middot; <a href="mailto:
hello@restaurant.example">hello@restaurant.example</a></address>
  </main>
</body>
</html>
```

Project 96: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.form { display: grid; gap: 1rem; }
.row { display: grid; gap: .3rem; }
label { font-weight: 600; }
input, select, textarea, button { font: inherit; }
input, select, textarea { padding: .6rem .8rem; border: 1px solid
#bbb; border-radius: 8px; width: 100%; }
input:focus-visible, select:focus-visible, textarea:focus-visible {
outline: 3px solid #ffbf47; border-color: var(--brand); }
input:user-invalid, textarea:user-invalid { border-color: #c00; }
button { justify-self: start; padding: .7rem 1.4rem; background: var(-
-brand); color: #fff; border: 0; border-radius: 999px; cursor:
pointer; }
address { margin-top: 2rem; font-style: normal; color: var(--muted); }
```

Project 96 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - Contact</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Contact Port Said Seafood	The main heading; only one per page.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
	Generic block container for grouping and layout.
<label for="name">Your name</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="name" name="name" type="text" required autocomplete="name">	A form control; its type decides what it looks like.

Line	What it does
<input id="email" name="email" type="email" required autocomplete="...	Email field: validated automatically and shows the @ keyboard on phones.
<select id="topic" name="topic">	Drop-down list.
<option>Grilled sea bass</option>	One choice in a select or datalist.
<textarea id="msg" name="message" rows="5" required minlength="10">...	Multi-line text field.
<button type="submit">Send message</button>	A clickable button; inside a form it submits by default.
<address>Port Said Seafood, Port Said · <a href="mailto:hell...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
font-weight: 600;	Thickness of the text.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
width: 100%;	Fills the container width.
input:focus-visible, select:focus-visible, textarea:focus-visible {	Applies when the element is focused by keyboard; keeps focus rings visible.
border-color: var(--brand);	The line around the element: width, style and colour.
input:user-invalid, textarea:user-invalid {	A field the user has edited that fails validation.
background: var(--brand);	Background colour or image.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Clicking a label focuses its control
- Empty submit is blocked
- Focus ring visible
- Address is real contact info, not italic

Exercises

1. Add a checkbox for newsletter consent.
2. Put name and email side by side on wide screens.
3. Add a pattern attribute for an Egyptian phone number.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 97: Contact form for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 1 | Files: index.html, styles.css

Brief

Build a contact form with text, email, select and textarea controls, proper labels, built-in validation and a styled submit button.

Learning goals

- Connect every label to its control with for/id
- Use input types and required for free validation
- Style focus and invalid states

Elements and CSS used

HTML elements	CSS features
form, label, input, select, option, textarea, button, address, a	display: grid, gap, font: inherit, :focus-visible, :user-invalid, border-radius

Build guide

1. Create the form with action and method.
2. Add one .row per field: a label followed by its control; match for and id.
3. Use type="email", required and minlength.
4. Add the select with one option per offer.
5. Style with Grid gaps; make controls full width and inherit the page font.
6. Submit the empty form and watch the browser's validation messages.

Project 97: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - Contact</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Contact Delta Kids Library</h1>
    <form action="/contact" method="post" class="form">
      <div class="row">
        <label for="name">Your name</label>
        <input id="name" name="name" type="text" required
autocomplete="name">
      </div>
      <div class="row">
        <label for="email">Email</label>
        <input id="email" name="email" type="email" required
autocomplete="email">
      </div>
      <div class="row">
        <label for="topic">Topic</label>
        <select id="topic" name="topic">
    <option>Story hour</option>
    <option>Reading club</option>
    <option>Homework help</option>
    <option>Summer challenge</option>
          <option>Something else</option>
        </select>
      </div>
      <div class="row">
        <label for="msg">Message</label>
        <textarea id="msg" name="message" rows="5" required
minlength="10"></textarea>
      </div>
      <button type="submit">Send message</button>
    </form>
    <address>Delta Kids Library, Tanta &middot; <a href="mailto:
hello@library.example">hello@library.example</a></address>
  </main>
</body>
</html>
```

Project 97: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.form { display: grid; gap: 1rem; }
.row { display: grid; gap: .3rem; }
label { font-weight: 600; }
input, select, textarea, button { font: inherit; }
input, select, textarea { padding: .6rem .8rem; border: 1px solid
#bbb; border-radius: 8px; width: 100%; }
input:focus-visible, select:focus-visible, textarea:focus-visible {
outline: 3px solid #ffbf47; border-color: var(--brand); }
input:user-invalid, textarea:user-invalid { border-color: #c00; }
button { justify-self: start; padding: .7rem 1.4rem; background: var(-
-brand); color: #fff; border: 0; border-radius: 999px; cursor:
pointer; }
address { margin-top: 2rem; font-style: normal; color: var(--muted); }
```

Project 97 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - Contact</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Contact Delta Kids Library	The main heading; only one per page.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
	Generic block container for grouping and layout.
<label for="name">Your name</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="name" name="name" type="text" required autocomplete="name">	A form control; its type decides what it looks like.

Line	What it does
<input id="email" name="email" type="email" required autocomplete="...	Email field: validated automatically and shows the @ keyboard on phones.
<select id="topic" name="topic">	Drop-down list.
<option>Story hour</option>	One choice in a select or datalist.
<textarea id="msg" name="message" rows="5" required minlength="10">...	Multi-line text field.
<button type="submit">Send message</button>	A clickable button; inside a form it submits by default.
<address>Delta Kids Library, Tanta · <a href="mailto:hello@l...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
font-weight: 600;	Thickness of the text.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
width: 100%;	Fills the container width.
input:focus-visible, select:focus-visible, textarea:focus-visible {	Applies when the element is focused by keyboard; keeps focus rings visible.
border-color: var(--brand);	The line around the element: width, style and colour.
input:user-invalid, textarea:user-invalid {	A field the user has edited that fails validation.
background: var(--brand);	Background colour or image.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Clicking a label focuses its control
- Empty submit is blocked
- Focus ring visible
- Address is real contact info, not italic

Exercises

1. Add a checkbox for newsletter consent.
2. Put name and email side by side on wide screens.
3. Add a pattern attribute for an Egyptian phone number.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 98: Contact form for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Build a contact form with text, email, select and textarea controls, proper labels, built-in validation and a styled submit button.

Learning goals

- Connect every label to its control with for/id
- Use input types and required for free validation
- Style focus and invalid states

Elements and CSS used

HTML elements	CSS features
form, label, input, select, option, textarea, button, address, a	display: grid, gap, font: inherit, :focus-visible, :user-invalid, border-radius

Build guide

1. Create the form with action and method.
2. Add one .row per field: a label followed by its control; match for and id.
3. Use type="email", required and minlength.
4. Add the select with one option per offer.
5. Style with Grid gaps; make controls full width and inherit the page font.
6. Submit the empty form and watch the browser's validation messages.

Project 98: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - Contact</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Contact Nubian Guest House</h1>
    <form action="/contact" method="post" class="form">
      <div class="row">
        <label for="name">Your name</label>
        <input id="name" name="name" type="text" required
autocomplete="name">
      </div>
      <div class="row">
        <label for="email">Email</label>
        <input id="email" name="email" type="email" required
autocomplete="email">
      </div>
      <div class="row">
        <label for="topic">Topic</label>
        <select id="topic" name="topic">
    <option>Garden room</option>
    <option>Nile view suite</option>
    <option>Family room</option>
    <option>Rooftop dorm</option>
          <option>Something else</option>
        </select>
      </div>
      <div class="row">
        <label for="msg">Message</label>
        <textarea id="msg" name="message" rows="5" required
minlength="10"></textarea>
      </div>
      <button type="submit">Send message</button>
    </form>
    <address>Nubian Guest House, Aswan &middot; <a href="mailto:
hello@guesthouse.example">hello@guesthouse.example</a></address>
  </main>
</body>
</html>
```

Project 98: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.form { display: grid; gap: 1rem; }
.row { display: grid; gap: .3rem; }
label { font-weight: 600; }
input, select, textarea, button { font: inherit; }
input, select, textarea { padding: .6rem .8rem; border: 1px solid
#bbb; border-radius: 8px; width: 100%; }
input:focus-visible, select:focus-visible, textarea:focus-visible {
outline: 3px solid #ffbf47; border-color: var(--brand); }
input:user-invalid, textarea:user-invalid { border-color: #c00; }
button { justify-self: start; padding: .7rem 1.4rem; background: var(-
-brand); color: #fff; border: 0; border-radius: 999px; cursor:
pointer; }
address { margin-top: 2rem; font-style: normal; color: var(--muted); }
```

Project 98 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - Contact</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Contact Nubian Guest House	The main heading; only one per page.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
	Generic block container for grouping and layout.
<label for="name">Your name</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="name" name="name" type="text" required autocomplete="name">	A form control; its type decides what it looks like.

Line	What it does
<input id="email" name="email" type="email" required autocomplete="...	Email field: validated automatically and shows the @ keyboard on phones.
<select id="topic" name="topic">	Drop-down list.
<option>Garden room</option>	One choice in a select or datalist.
<textarea id="msg" name="message" rows="5" required minlength="10">...	Multi-line text field.
<button type="submit">Send message</button>	A clickable button; inside a form it submits by default.
<address>Nubian Guest House, Aswan · <a href="mailto:hello@g...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
font-weight: 600;	Thickness of the text.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
width: 100%;	Fills the container width.
input:focus-visible, select:focus-visible, textarea:focus-visible {	Applies when the element is focused by keyboard; keeps focus rings visible.
border-color: var(--brand);	The line around the element: width, style and colour.
input:user-invalid, textarea:user-invalid {	A field the user has edited that fails validation.
background: var(--brand);	Background colour or image.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Clicking a label focuses its control
- Empty submit is blocked
- Focus ring visible
- Address is real contact info, not italic

Exercises

1. Add a checkbox for newsletter consent.
2. Put name and email side by side on wide screens.
3. Add a pattern attribute for an Egyptian phone number.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 99: Contact form for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 1 | Files: index.html, styles.css

Brief

Build a contact form with text, email, select and textarea controls, proper labels, built-in validation and a styled submit button.

Learning goals

- Connect every label to its control with for/id
- Use input types and required for free validation
- Style focus and invalid states

Elements and CSS used

HTML elements	CSS features
form, label, input, select, option, textarea, button, address, a	display: grid, gap, font: inherit, :focus-visible, :user-invalid, border-radius

Build guide

1. Create the form with action and method.
2. Add one .row per field: a label followed by its control; match for and id.
3. Use type="email", required and minlength.
4. Add the select with one option per offer.
5. Style with Grid gaps; make controls full width and inherit the page font.

6. Submit the empty form and watch the browser's validation messages.

Project 99: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - Contact</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Contact Ismailia Cycling Store</h1>
    <form action="/contact" method="post" class="form">
      <div class="row">
        <label for="name">Your name</label>
        <input id="name" name="name" type="text" required
autocomplete="name">
      </div>
      <div class="row">
        <label for="email">Email</label>
        <input id="email" name="email" type="email" required
autocomplete="email">
      </div>
      <div class="row">
        <label for="topic">Topic</label>
        <select id="topic" name="topic">
    <option>City bike</option>
    <option>Mountain bike</option>
    <option>Kids bike</option>
    <option>Tune-up</option>
          <option>Something else</option>
        </select>
      </div>
      <div class="row">
        <label for="msg">Message</label>
        <textarea id="msg" name="message" rows="5" required
minlength="10"></textarea>
      </div>
      <button type="submit">Send message</button>
    </form>
    <address>Ismailia Cycling Store, Ismailia &middot; <a
href="mailto:hello@cycling.example">hello@cycling.example</a></
address>
  </main>
</body>
</html>
```

Project 99: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.form { display: grid; gap: 1rem; }
.row { display: grid; gap: .3rem; }
label { font-weight: 600; }
input, select, textarea, button { font: inherit; }
input, select, textarea { padding: .6rem .8rem; border: 1px solid
#bbb; border-radius: 8px; width: 100%; }
input:focus-visible, select:focus-visible, textarea:focus-visible {
outline: 3px solid #ffbf47; border-color: var(--brand); }
input:user-invalid, textarea:user-invalid { border-color: #c00; }
button { justify-self: start; padding: .7rem 1.4rem; background: var(-
-brand); color: #fff; border: 0; border-radius: 999px; cursor:
pointer; }
address { margin-top: 2rem; font-style: normal; color: var(--muted); }
```

Project 99 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - Contact</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Contact Ismailia Cycling Store	The main heading; only one per page.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
	Generic block container for grouping and layout.
<label for="name">Your name</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="name" name="name" type="text" required autocomplete="name">	A form control; its type decides what it looks like.

Line	What it does
<input id="email" name="email" type="email" required autocomplete="...	Email field: validated automatically and shows the @ keyboard on phones.
<select id="topic" name="topic">	Drop-down list.
<option>City bike</option>	One choice in a select or datalist.
<textarea id="msg" name="message" rows="5" required minlength="10">...	Multi-line text field.
<button type="submit">Send message</button>	A clickable button; inside a form it submits by default.
<address>Ismailia Cycling Store, Ismailia · <a href="mailto:...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
font-weight: 600;	Thickness of the text.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
width: 100%;	Fills the container width.
input:focus-visible, select:focus-visible, textarea:focus-visible {	Applies when the element is focused by keyboard; keeps focus rings visible.
border-color: var(--brand);	The line around the element: width, style and colour.
input:user-invalid, textarea:user-invalid {	A field the user has edited that fails validation.
background: var(--brand);	Background colour or image.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Clicking a label focuses its control
- Empty submit is blocked
- Focus ring visible
- Address is real contact info, not italic

Exercises

1. Add a checkbox for newsletter consent.
2. Put name and email side by side on wide screens.
3. Add a pattern attribute for an Egyptian phone number.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 100: Contact form for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 1 | Files: index.html, styles.css

Brief

Build a contact form with text, email, select and textarea controls, proper labels, built-in validation and a styled submit button.

Learning goals

- Connect every label to its control with for/id
- Use input types and required for free validation
- Style focus and invalid states

Elements and CSS used

HTML elements	CSS features
form, label, input, select, option, textarea, button, address, a	display: grid, gap, font: inherit, :focus-visible, :user-invalid, border-radius

Build guide

1. Create the form with action and method.
2. Add one .row per field: a label followed by its control; match for and id.
3. Use type="email", required and minlength.
4. Add the select with one option per offer.
5. Style with Grid gaps; make controls full width and inherit the page font.
6. Submit the empty form and watch the browser's validation messages.

Project 100: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - Contact</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Contact Minya Coding Club</h1>
    <form action="/contact" method="post" class="form">
      <div class="row">
        <label for="name">Your name</label>
        <input id="name" name="name" type="text" required
autocomplete="name">
      </div>
      <div class="row">
        <label for="email">Email</label>
        <input id="email" name="email" type="email" required
autocomplete="email">
      </div>
      <div class="row">
        <label for="topic">Topic</label>
        <select id="topic" name="topic">
    <option>HTML weekend</option>
    <option>CSS art</option>
    <option>Scratch games</option>
    <option>Hackathon</option>
          <option>Something else</option>
        </select>
      </div>
      <div class="row">
        <label for="msg">Message</label>
        <textarea id="msg" name="message" rows="5" required
minlength="10"></textarea>
      </div>
      <button type="submit">Send message</button>
    </form>
    <address>Minya Coding Club, Minya &middot; <a href="mailto:
hello@coding.example">hello@coding.example</a></address>
  </main>
</body>
</html>
```

Project 100: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.form { display: grid; gap: 1rem; }
.row { display: grid; gap: .3rem; }
label { font-weight: 600; }
input, select, textarea, button { font: inherit; }
input, select, textarea { padding: .6rem .8rem; border: 1px solid
#bbb; border-radius: 8px; width: 100%; }
input:focus-visible, select:focus-visible, textarea:focus-visible {
outline: 3px solid #ffbf47; border-color: var(--brand); }
input:user-invalid, textarea:user-invalid { border-color: #c00; }
button { justify-self: start; padding: .7rem 1.4rem; background: var(-
-brand); color: #fff; border: 0; border-radius: 999px; cursor:
pointer; }
address { margin-top: 2rem; font-style: normal; color: var(--muted); }
```

Project 100 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - Contact</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Contact Minya Coding Club	The main heading; only one per page.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
	Generic block container for grouping and layout.
<label for="name">Your name</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="name" name="name" type="text" required autocomplete="name">	A form control; its type decides what it looks like.

Line	What it does
<input id="email" name="email" type="email" required autocomplete="...	Email field: validated automatically and shows the @ keyboard on phones.
<select id="topic" name="topic">	Drop-down list.
<option>HTML weekend</option>	One choice in a select or datalist.
<textarea id="msg" name="message" rows="5" required minlength="10">...	Multi-line text field.
<button type="submit">Send message</button>	A clickable button; inside a form it submits by default.
<address>Minya Coding Club, Minya · <a href="mailto:hello@co...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
font-weight: 600;	Thickness of the text.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
width: 100%;	Fills the container width.
input:focus-visible, select:focus-visible, textarea:focus-visible {	Applies when the element is focused by keyboard; keeps focus rings visible.
border-color: var(--brand);	The line around the element: width, style and colour.
input:user-invalid, textarea:user-invalid {	A field the user has edited that fails validation.
background: var(--brand);	Background colour or image.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Clicking a label focuses its control
- Empty submit is blocked
- Focus ring visible
- Address is real contact info, not italic

Exercises

1. Add a checkbox for newsletter consent.
2. Put name and email side by side on wide screens.
3. Add a pattern attribute for an Egyptian phone number.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Photo gallery

Level 1 | 25 projects, one per theme

Lay out four captioned photos in a responsive grid using figure and figcaption, with lazy loading and a gentle hover zoom.

Project 101: Photo gallery for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 1 | Files: index.html, styles.css

Brief

Lay out four captioned photos in a responsive grid using figure and figcaption, with lazy loading and a gentle hover zoom.

Learning goals

- Use figure/figcaption for captioned images
- Reserve space with width, height and aspect-ratio
- Crop images consistently with object-fit

Elements and CSS used

HTML elements	CSS features
figure, img, figcaption, div, h1	grid-template-columns, auto-fill, aspect-ratio, object-fit, overflow: hidden, transition, transform

Build guide

1. Create an images folder with four photos (any JPEGs, renamed).
2. Write one <figure> per photo with img and figcaption.
3. Give every img alt text, width, height and loading="lazy".
4. Make .gallery a grid with auto-fill columns.
5. Force a 3:2 shape with aspect-ratio and object-fit: cover.
6. Add the hover zoom with transition and transform.

Project 101: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Gallery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cairo Book Shop gallery</h1>
    <div class="gallery">
      <figure><img src="images/bookshop-1.jpg" alt="Learn HTML"
width="600" height="400" loading="lazy"><figcaption>Learn HTML</
figcaption></figure>
      <figure><img src="images/bookshop-2.jpg" alt="CSS in Practice"
width="600" height="400" loading="lazy"><figcaption>CSS in Practice</
figcaption></figure>
      <figure><img src="images/bookshop-3.jpg" alt="JavaScript
Basics" width="600" height="400"
loading="lazy"><figcaption>JavaScript Basics</figcaption></figure>
      <figure><img src="images/bookshop-4.jpg" alt="Web
Accessibility" width="600" height="400"
loading="lazy"><figcaption>Web Accessibility</figcaption></figure>
    </div>
  </main>
</body>
</html>
```

Project 101: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; }
.gallery { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fill, minmax(16rem, 1fr)); }
figure { margin: 0; background: var(--accent); border-radius: 12px;
overflow: hidden; }
img { display: block; width: 100%; height: auto; aspect-ratio: 3 / 2;
object-fit: cover; }
figcaption { padding: .6rem .9rem; font-size: .95rem; }
figure:hover img { transform: scale(1.03); }
img { transition: transform .3s; }
```

Project 101 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - Gallery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cairo Book Shop gallery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure><img src="images/bookshop-1.jpg" alt="Learn HTML" width="60...	An image; alt describes it, width and height reserve space before it loads.
<figure><img src="images/bookshop-2.jpg" alt="CSS in Practice" widt...	Self-contained media with an optional caption.
<figure><img src="images/bookshop-3.jpg" alt="JavaScript Basics" wi...	Caption for the figure.

Line	What it does
<figure><img src="images/bookshop-4.jpg" alt="Web Accessibility" wi...	Defers loading until the image is near the viewport.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fill, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 12px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
font-size: .95rem;	Size of the text.
figure:hover img {	Applies while the pointer is over the element.
transform: scale(1.03);	Enlarges or shrinks the element visually.
transition: transform .3s;	Animates property changes smoothly, for example on hover.

Check your work

- All images have meaningful alt
- No layout jump while loading
- Grid reflows on narrow screens
- Zoom does not overflow the card

Exercises

1. Make the first image span two columns with grid-column: span 2.
2. Add a lightbox using <dialog>.
3. Use <picture> to serve WebP.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 102: Photo gallery for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 1 | Files: index.html, styles.css

Brief

Lay out four captioned photos in a responsive grid using figure and figcaption, with lazy loading and a gentle hover zoom.

Learning goals

- Use figure/figcaption for captioned images
- Reserve space with width, height and aspect-ratio
- Crop images consistently with object-fit

Elements and CSS used

HTML elements	CSS features
figure, img, figcaption, div, h1	grid-template-columns, auto-fill, aspect-ratio, object-fit, overflow: hidden, transition, transform

Build guide

1. Create an images folder with four photos (any JPEGs, renamed).
2. Write one <figure> per photo with img and figcaption.
3. Give every img alt text, width, height and loading="lazy".
4. Make .gallery a grid with auto-fill columns.
5. Force a 3:2 shape with aspect-ratio and object-fit: cover.
6. Add the hover zoom with transition and transform.

Project 102: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - Gallery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Nile Bakery gallery</h1>
    <div class="gallery">
      <figure><img src="images/bakery-1.jpg" alt="Sourdough loaf"
width="600" height="400" loading="lazy"><figcaption>Sourdough loaf</
figcaption></figure>
      <figure><img src="images/bakery-2.jpg" alt="Croissant"
width="600" height="400" loading="lazy"><figcaption>Croissant</
figcaption></figure>
      <figure><img src="images/bakery-3.jpg" alt="Date cookies"
width="600" height="400" loading="lazy"><figcaption>Date cookies</
figcaption></figure>
      <figure><img src="images/bakery-4.jpg" alt="Baklava box"
width="600" height="400" loading="lazy"><figcaption>Baklava box</
figcaption></figure>
    </div>
  </main>
</body>
</html>
```

Project 102: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; }
.gallery { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fill, minmax(16rem, 1fr)); }
figure { margin: 0; background: var(--accent); border-radius: 12px;
overflow: hidden; }
img { display: block; width: 100%; height: auto; aspect-ratio: 3 / 2;
object-fit: cover; }
figcaption { padding: .6rem .9rem; font-size: .95rem; }
figure:hover img { transform: scale(1.03); }
img { transition: transform .3s; }
```

Project 102 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - Gallery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Nile Bakery gallery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure><img src="images/bakery-1.jpg" alt="Sourdough loaf" width="...	An image; alt describes it, width and height reserve space before it loads.
<figure><img src="images/bakery-2.jpg" alt="Croissant" width="600" ...	Self-contained media with an optional caption.

Line	What it does
<figure><img src="images/bakery-3.jpg" alt="Date cookies" width="60...	Caption for the figure.
<figure><img src="images/bakery-4.jpg" alt="Baklava box" width="600...	Defers loading until the image is near the viewport.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 12px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
font-size: .95rem;	Size of the text.
figure:hover img {	Applies while the pointer is over the element.
transform: scale(1.03);	Enlarges or shrinks the element visually.
transition: transform .3s;	Animates property changes smoothly, for example on hover.

Check your work

- All images have meaningful alt
- No layout jump while loading

- Grid reflows on narrow screens
- Zoom does not overflow the card

Exercises

1. Make the first image span two columns with grid-column: span 2.
2. Add a lightbox using <dialog>.
3. Use <picture> to serve WebP.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 103: Photo gallery for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 1 | Files: index.html, styles.css

Brief

Lay out four captioned photos in a responsive grid using figure and figcaption, with lazy loading and a gentle hover zoom.

Learning goals

- Use figure/figcaption for captioned images
- Reserve space with width, height and aspect-ratio
- Crop images consistently with object-fit

Elements and CSS used

HTML elements	CSS features
figure, img, figcaption, div, h1	grid-template-columns, auto-fill, aspect-ratio, object-fit, overflow: hidden, transition, transform

Build guide

1. Create an images folder with four photos (any JPEGs, renamed).
2. Write one <figure> per photo with img and figcaption.
3. Give every img alt text, width, height and loading="lazy".
4. Make .gallery a grid with auto-fill columns.
5. Force a 3:2 shape with aspect-ratio and object-fit: cover.
6. Add the hover zoom with transition and transform.

Project 103: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - Gallery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Pyramid Fitness gallery</h1>
    <div class="gallery">
      <figure><img src="images/gym-1.jpg" alt="Morning yoga"
width="600" height="400" loading="lazy"><figcaption>Morning yoga</
figcaption></figure>
      <figure><img src="images/gym-2.jpg" alt="Strength circuit"
width="600" height="400" loading="lazy"><figcaption>Strength circuit</
figcaption></figure>
      <figure><img src="images/gym-3.jpg" alt="Spinning" width="600"
height="400" loading="lazy"><figcaption>Spinning</figcaption></figure>
      <figure><img src="images/gym-4.jpg" alt="Personal training"
width="600" height="400" loading="lazy"><figcaption>Personal
training</figcaption></figure>
    </div>
  </main>
</body>
</html>
```

Project 103: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; }
.gallery { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fill, minmax(16rem, 1fr)); }
figure { margin: 0; background: var(--accent); border-radius: 12px;
overflow: hidden; }
img { display: block; width: 100%; height: auto; aspect-ratio: 3 / 2;
object-fit: cover; }
figcaption { padding: .6rem .9rem; font-size: .95rem; }
figure:hover img { transform: scale(1.03); }
img { transition: transform .3s; }
```

Project 103 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - Gallery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Pyramid Fitness gallery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure><img src="images/gym-1.jpg" alt="Morning yoga" width="600" ...	An image; alt describes it, width and height reserve space before it loads.
<figure><img src="images/gym-2.jpg" alt="Strength circuit" width="6...	Self-contained media with an optional caption.

Line	What it does
<figure><img src="images/gym-3.jpg" alt="Spinning" width="600" heig...	Caption for the figure.
<figure><img src="images/gym-4.jpg" alt="Personal training" width="...	Defers loading until the image is near the viewport.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 12px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
font-size: .95rem;	Size of the text.
figure:hover img {	Applies while the pointer is over the element.
transform: scale(1.03);	Enlarges or shrinks the element visually.
transition: transform .3s;	Animates property changes smoothly, for example on hover.

Check your work

- All images have meaningful alt
- No layout jump while loading

- Grid reflows on narrow screens
- Zoom does not overflow the card

Exercises

1. Make the first image span two columns with grid-column: span 2.
2. Add a lightbox using <dialog>.
3. Use <picture> to serve WebP.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 104: Photo gallery for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 1 | Files: index.html, styles.css

Brief

Lay out four captioned photos in a responsive grid using figure and figcaption, with lazy loading and a gentle hover zoom.

Learning goals

- Use figure/figcaption for captioned images
- Reserve space with width, height and aspect-ratio
- Crop images consistently with object-fit

Elements and CSS used

HTML elements	CSS features
figure, img, figcaption, div, h1	grid-template-columns, auto-fill, aspect-ratio, object-fit, overflow: hidden, transition, transform

Build guide

1. Create an images folder with four photos (any JPEGs, renamed).
2. Write one <figure> per photo with img and figcaption.
3. Give every img alt text, width, height and loading="lazy".
4. Make .gallery a grid with auto-fill columns.
5. Force a 3:2 shape with aspect-ratio and object-fit: cover.
6. Add the hover zoom with transition and transform.

Project 104: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - Gallery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Delta Dental Clinic gallery</h1>
    <div class="gallery">
      <figure><img src="images/clinic-1.jpg" alt="Check-up"
width="600" height="400" loading="lazy"><figcaption>Check-up</
figcaption></figure>
      <figure><img src="images/clinic-2.jpg" alt="Whitening"
width="600" height="400" loading="lazy"><figcaption>Whitening</
figcaption></figure>
      <figure><img src="images/clinic-3.jpg" alt="Filling"
width="600" height="400" loading="lazy"><figcaption>Filling</
figcaption></figure>
      <figure><img src="images/clinic-4.jpg" alt="Braces
consultation" width="600" height="400"
loading="lazy"><figcaption>Braces consultation</figcaption></figure>
    </div>
  </main>
</body>
</html>
```

Project 104: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; }
.gallery { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fill, minmax(16rem, 1fr)); }
figure { margin: 0; background: var(--accent); border-radius: 12px;
overflow: hidden; }
img { display: block; width: 100%; height: auto; aspect-ratio: 3 / 2;
object-fit: cover; }
figcaption { padding: .6rem .9rem; font-size: .95rem; }
figure:hover img { transform: scale(1.03); }
img { transition: transform .3s; }
```

Project 104 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - Gallery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Delta Dental Clinic gallery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure><img src="images/clinic-1.jpg" alt="Check-up" width="600" h...	An image; alt describes it, width and height reserve space before it loads.
<figure><img src="images/clinic-2.jpg" alt="Whitening" width="600" ...	Self-contained media with an optional caption.

Line	What it does
<figure><img src="images/clinic-3.jpg" alt="Filling" width="600" he...	Caption for the figure.
<figure><img src="images/clinic-4.jpg" alt="Braces consultation" wi...	Defers loading until the image is near the viewport.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 12px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
font-size: .95rem;	Size of the text.
figure:hover img {	Applies while the pointer is over the element.
transform: scale(1.03);	Enlarges or shrinks the element visually.
transition: transform .3s;	Animates property changes smoothly, for example on hover.

Check your work

- All images have meaningful alt
- No layout jump while loading
- Grid reflows on narrow screens

- Zoom does not overflow the card

Exercises

1. Make the first image span two columns with grid-column: span 2.
2. Add a lightbox using <dialog>.
3. Use <picture> to serve WebP.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 105: Photo gallery for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 1 | Files: index.html, styles.css

Brief

Lay out four captioned photos in a responsive grid using figure and figcaption, with lazy loading and a gentle hover zoom.

Learning goals

- Use figure/figcaption for captioned images
- Reserve space with width, height and aspect-ratio
- Crop images consistently with object-fit

Elements and CSS used

HTML elements	CSS features
figure, img, figcaption, div, h1	grid-template-columns, auto-fill, aspect-ratio, object-fit, overflow: hidden, transition, transform

Build guide

1. Create an images folder with four photos (any JPEGs, renamed).
2. Write one <figure> per photo with img and figcaption.
3. Give every img alt text, width, height and loading="lazy".
4. Make .gallery a grid with auto-fill columns.
5. Force a 3:2 shape with aspect-ratio and object-fit: cover.
6. Add the hover zoom with transition and transform.

Project 105: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - Gallery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Red Sea Travel gallery</h1>
    <div class="gallery">
      <figure><img src="images/travel-1.jpg" alt="Luxor day trip"
width="600" height="400" loading="lazy"><figcaption>Luxor day trip</
figcaption></figure>
      <figure><img src="images/travel-2.jpg" alt="Snorkelling"
width="600" height="400" loading="lazy"><figcaption>Snorkelling</
figcaption></figure>
      <figure><img src="images/travel-3.jpg" alt="Desert safari"
width="600" height="400" loading="lazy"><figcaption>Desert safari</
figcaption></figure>
      <figure><img src="images/travel-4.jpg" alt="Nile cruise"
width="600" height="400" loading="lazy"><figcaption>Nile cruise</
figcaption></figure>
    </div>
  </main>
</body>
</html>
```

Project 105: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; }
.gallery { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fill, minmax(16rem, 1fr)); }
figure { margin: 0; background: var(--accent); border-radius: 12px;
overflow: hidden; }
img { display: block; width: 100%; height: auto; aspect-ratio: 3 / 2;
object-fit: cover; }
figcaption { padding: .6rem .9rem; font-size: .95rem; }
figure:hover img { transform: scale(1.03); }
img { transition: transform .3s; }
```

Project 105 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - Gallery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Red Sea Travel gallery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure><img src="images/travel-1.jpg" alt="Luxor day trip" width="...	An image; alt describes it, width and height reserve space before it loads.
<figure><img src="images/travel-2.jpg" alt="Snorkelling" width="600...	Self-contained media with an optional caption.
<figure><img src="images/travel-3.jpg" alt="Desert safari" width="6...	Caption for the figure.

Line	What it does
<figure><img src="images/travel-4.jpg" alt="Nile cruise" width="600...	Defers loading until the image is near the viewport.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fill, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 12px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
font-size: .95rem;	Size of the text.
figure:hover img {	Applies while the pointer is over the element.
transform: scale(1.03);	Enlarges or shrinks the element visually.
transition: transform .3s;	Animates property changes smoothly, for example on hover.

Check your work

- All images have meaningful alt
- No layout jump while loading
- Grid reflows on narrow screens
- Zoom does not overflow the card

Exercises

1. Make the first image span two columns with grid-column: span 2.
2. Add a lightbox using <dialog>.
3. Use <picture> to serve WebP.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 106: Photo gallery for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Lay out four captioned photos in a responsive grid using figure and figcaption, with lazy loading and a gentle hover zoom.

Learning goals

- Use figure/figcaption for captioned images
- Reserve space with width, height and aspect-ratio
- Crop images consistently with object-fit

Elements and CSS used

HTML elements	CSS features
figure, img, figcaption, div, h1	grid-template-columns, auto-fill, aspect-ratio, object-fit, overflow: hidden, transition, transform

Build guide

1. Create an images folder with four photos (any JPEGs, renamed).
2. Write one <figure> per photo with img and figcaption.
3. Give every img alt text, width, height and loading="lazy".
4. Make .gallery a grid with auto-fill columns.
5. Force a 3:2 shape with aspect-ratio and object-fit: cover.
6. Add the hover zoom with transition and transform.

Project 106: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - Gallery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Lotus Language School gallery</h1>
    <div class="gallery">
      <figure><img src="images/school-1.jpg" alt="English A1"
width="600" height="400" loading="lazy"><figcaption>English A1</
figcaption></figure>
      <figure><img src="images/school-2.jpg" alt="French B1"
width="600" height="400" loading="lazy"><figcaption>French B1</
figcaption></figure>
      <figure><img src="images/school-3.jpg" alt="German A2"
width="600" height="400" loading="lazy"><figcaption>German A2</
figcaption></figure>
      <figure><img src="images/school-4.jpg" alt="IELTS preparation"
width="600" height="400" loading="lazy"><figcaption>IELTS
preparation</figcaption></figure>
    </div>
  </main>
</body>
</html>
```

Project 106: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; }
.gallery { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fill, minmax(16rem, 1fr)); }
figure { margin: 0; background: var(--accent); border-radius: 12px;
overflow: hidden; }
img { display: block; width: 100%; height: auto; aspect-ratio: 3 / 2;
object-fit: cover; }
figcaption { padding: .6rem .9rem; font-size: .95rem; }
figure:hover img { transform: scale(1.03); }
img { transition: transform .3s; }
```

Project 106 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - Gallery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Lotus Language School gallery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure><img src="images/school-1.jpg" alt="English A1" width="600"...	An image; alt describes it, width and height reserve space before it loads.
<figure><img src="images/school-2.jpg" alt="French B1" width="600" ...	Self-contained media with an optional caption.

Line	What it does
<figure><img src="images/school-3.jpg" alt="German A2" width="600" ...	Caption for the figure.
<figure><img src="images/school-4.jpg" alt="IELTS preparation" widt...	Defers loading until the image is near the viewport.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 12px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
font-size: .95rem;	Size of the text.
figure:hover img {	Applies while the pointer is over the element.
transform: scale(1.03);	Enlarges or shrinks the element visually.
transition: transform .3s;	Animates property changes smoothly, for example on hover.

Check your work

- All images have meaningful alt
- No layout jump while loading
- Grid reflows on narrow screens

- Zoom does not overflow the card

Exercises

1. Make the first image span two columns with grid-column: span 2.
2. Add a lightbox using <dialog>.
3. Use <picture> to serve WebP.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 107: Photo gallery for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 1 | Files: index.html, styles.css

Brief

Lay out four captioned photos in a responsive grid using figure and figcaption, with lazy loading and a gentle hover zoom.

Learning goals

- Use figure/figcaption for captioned images
- Reserve space with width, height and aspect-ratio
- Crop images consistently with object-fit

Elements and CSS used

HTML elements	CSS features
figure, img, figcaption, div, h1	grid-template-columns, auto-fill, aspect-ratio, object-fit, overflow: hidden, transition, transform

Build guide

1. Create an images folder with four photos (any JPEGs, renamed).
2. Write one <figure> per photo with img and figcaption.
3. Give every img alt text, width, height and loading="lazy".
4. Make .gallery a grid with auto-fill columns.
5. Force a 3:2 shape with aspect-ratio and object-fit: cover.
6. Add the hover zoom with transition and transform.

Project 107: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - Gallery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Green Leaf Cafe gallery</h1>
    <div class="gallery">
      <figure><img src="images/cafe-1.jpg" alt="Flat white"
width="600" height="400" loading="lazy"><figcaption>Flat white</
figcaption></figure>
      <figure><img src="images/cafe-2.jpg" alt="Cold brew"
width="600" height="400" loading="lazy"><figcaption>Cold brew</
figcaption></figure>
      <figure><img src="images/cafe-3.jpg" alt="Hibiscus iced tea"
width="600" height="400" loading="lazy"><figcaption>Hibiscus iced
tea</figcaption></figure>
      <figure><img src="images/cafe-4.jpg" alt="Cheesecake"
width="600" height="400" loading="lazy"><figcaption>Cheesecake</
figcaption></figure>
    </div>
  </main>
</body>
</html>
```

Project 107: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; }
.gallery { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fill, minmax(16rem, 1fr)); }
figure { margin: 0; background: var(--accent); border-radius: 12px;
overflow: hidden; }
img { display: block; width: 100%; height: auto; aspect-ratio: 3 / 2;
object-fit: cover; }
figcaption { padding: .6rem .9rem; font-size: .95rem; }
figure:hover img { transform: scale(1.03); }
img { transition: transform .3s; }
```

Project 107 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - Gallery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Green Leaf Cafe gallery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure><img src="images/cafe-1.jpg" alt="Flat white" width="600" h...	An image; alt describes it, width and height reserve space before it loads.
<figure><img src="images/cafe-2.jpg" alt="Cold brew" width="600" he...	Self-contained media with an optional caption.

Line	What it does
<figure><img src="images/cafe-3.jpg" alt="Hibiscus iced tea" width=...	Caption for the figure.
<figure><img src="images/cafe-4.jpg" alt="Cheesecake" width="600" h...	Defers loading until the image is near the viewport.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 12px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
font-size: .95rem;	Size of the text.
figure:hover img {	Applies while the pointer is over the element.
transform: scale(1.03);	Enlarges or shrinks the element visually.
transition: transform .3s;	Animates property changes smoothly, for example on hover.

Check your work

- All images have meaningful alt
- No layout jump while loading

- Grid reflows on narrow screens
- Zoom does not overflow the card

Exercises

1. Make the first image span two columns with grid-column: span 2.
2. Add a lightbox using <dialog>.
3. Use <picture> to serve WebP.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 108: Photo gallery for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 1 | Files: index.html, styles.css

Brief

Lay out four captioned photos in a responsive grid using figure and figcaption, with lazy loading and a gentle hover zoom.

Learning goals

- Use figure/figcaption for captioned images
- Reserve space with width, height and aspect-ratio
- Crop images consistently with object-fit

Elements and CSS used

HTML elements	CSS features
figure, img, figcaption, div, h1	grid-template-columns, auto-fill, aspect-ratio, object-fit, overflow: hidden, transition, transform

Build guide

1. Create an images folder with four photos (any JPEGs, renamed).
2. Write one <figure> per photo with img and figcaption.
3. Give every img alt text, width, height and loading="lazy".
4. Make .gallery a grid with auto-fill columns.
5. Force a 3:2 shape with aspect-ratio and object-fit: cover.
6. Add the hover zoom with transition and transform.

Project 108: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - Gallery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Sinai Trekking Club gallery</h1>
    <div class="gallery">
      <figure><img src="images/trekking-1.jpg" alt="Mount Sinai
sunrise" width="600" height="400" loading="lazy"><figcaption>Mount
Sinai sunrise</figcaption></figure>
      <figure><img src="images/trekking-2.jpg" alt="Blue Desert loop"
width="600" height="400" loading="lazy"><figcaption>Blue Desert loop</
figcaption></figure>
      <figure><img src="images/trekking-3.jpg" alt="Wadi Gnai"
width="600" height="400" loading="lazy"><figcaption>Wadi Gnai</
figcaption></figure>
      <figure><img src="images/trekking-4.jpg" alt="Three-day
traverse" width="600" height="400" loading="lazy"><figcaption>Three-
day traverse</figcaption></figure>
    </div>
  </main>
</body>
</html>
```

Project 108: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; }
.gallery { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fill, minmax(16rem, 1fr)); }
figure { margin: 0; background: var(--accent); border-radius: 12px;
overflow: hidden; }
img { display: block; width: 100%; height: auto; aspect-ratio: 3 / 2;
object-fit: cover; }
figcaption { padding: .6rem .9rem; font-size: .95rem; }
figure:hover img { transform: scale(1.03); }
img { transition: transform .3s; }
```

Project 108 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - Gallery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Sinai Trekking Club gallery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure><img src="images/trekking-1.jpg" alt="Mount Sinai sunrise" ...	An image; alt describes it, width and height reserve space before it loads.
<figure><img src="images/trekking-2.jpg" alt="Blue Desert loop" wid...	Self-contained media with an optional caption.
<figure><img src="images/trekking-3.jpg" alt="Wadi Gnai" width="600...	Caption for the figure.

Line	What it does
<figure><img src="images/trekking-4.jpg" alt="Three-day traverse" w...	Defers loading until the image is near the viewport.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fill, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 12px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
font-size: .95rem;	Size of the text.
figure:hover img {	Applies while the pointer is over the element.
transform: scale(1.03);	Enlarges or shrinks the element visually.
transition: transform .3s;	Animates property changes smoothly, for example on hover.

Check your work

- All images have meaningful alt
- No layout jump while loading
- Grid reflows on narrow screens
- Zoom does not overflow the card

Exercises

1. Make the first image span two columns with grid-column: span 2.
2. Add a lightbox using <dialog>.
3. Use <picture> to serve WebP.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 109: Photo gallery for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 1 | Files: index.html, styles.css

Brief

Lay out four captioned photos in a responsive grid using figure and figcaption, with lazy loading and a gentle hover zoom.

Learning goals

- Use figure/figcaption for captioned images
- Reserve space with width, height and aspect-ratio
- Crop images consistently with object-fit

Elements and CSS used

HTML elements	CSS features
figure, img, figcaption, div, h1	grid-template-columns, auto-fill, aspect-ratio, object-fit, overflow: hidden, transition, transform

Build guide

1. Create an images folder with four photos (any JPEGs, renamed).
2. Write one <figure> per photo with img and figcaption.
3. Give every img alt text, width, height and loading="lazy".
4. Make .gallery a grid with auto-fill columns.
5. Force a 3:2 shape with aspect-ratio and object-fit: cover.
6. Add the hover zoom with transition and transform.

Project 109: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - Gallery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Horizon Photography gallery</h1>
    <div class="gallery">
      <figure><img src="images/photo-1.jpg" alt="Portrait session"
width="600" height="400" loading="lazy"><figcaption>Portrait session</
figcaption></figure>
      <figure><img src="images/photo-2.jpg" alt="Wedding day"
width="600" height="400" loading="lazy"><figcaption>Wedding day</
figcaption></figure>
      <figure><img src="images/photo-3.jpg" alt="Product shoot"
width="600" height="400" loading="lazy"><figcaption>Product shoot</
figcaption></figure>
      <figure><img src="images/photo-4.jpg" alt="Family session"
width="600" height="400" loading="lazy"><figcaption>Family session</
figcaption></figure>
    </div>
  </main>
</body>
</html>
```

Project 109: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; }
.gallery { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fill, minmax(16rem, 1fr)); }
figure { margin: 0; background: var(--accent); border-radius: 12px;
overflow: hidden; }
img { display: block; width: 100%; height: auto; aspect-ratio: 3 / 2;
object-fit: cover; }
figcaption { padding: .6rem .9rem; font-size: .95rem; }
figure:hover img { transform: scale(1.03); }
img { transition: transform .3s; }
```

Project 109 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - Gallery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Horizon Photography gallery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure><img src="images/photo-1.jpg" alt="Portrait session" width=...	An image; alt describes it, width and height reserve space before it loads.
<figure><img src="images/photo-2.jpg" alt="Wedding day" width="600"...	Self-contained media with an optional caption.

Line	What it does
<figure><img src="images/photo-3.jpg" alt="Product shoot" width="60...	Caption for the figure.
<figure><img src="images/photo-4.jpg" alt="Family session" width="6...	Defers loading until the image is near the viewport.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 12px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
font-size: .95rem;	Size of the text.
figure:hover img {	Applies while the pointer is over the element.
transform: scale(1.03);	Enlarges or shrinks the element visually.
transition: transform .3s;	Animates property changes smoothly, for example on hover.

Check your work

- All images have meaningful alt
- No layout jump while loading

- Grid reflows on narrow screens
- Zoom does not overflow the card

Exercises

1. Make the first image span two columns with grid-column: span 2.
2. Add a lightbox using <dialog>.
3. Use <picture> to serve WebP.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 110: Photo gallery for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 1 | Files: index.html, styles.css

Brief

Lay out four captioned photos in a responsive grid using figure and figcaption, with lazy loading and a gentle hover zoom.

Learning goals

- Use figure/figcaption for captioned images
- Reserve space with width, height and aspect-ratio
- Crop images consistently with object-fit

Elements and CSS used

HTML elements	CSS features
figure, img, figcaption, div, h1	grid-template-columns, auto-fill, aspect-ratio, object-fit, overflow: hidden, transition, transform

Build guide

1. Create an images folder with four photos (any JPEGs, renamed).
2. Write one <figure> per photo with img and figcaption.
3. Give every img alt text, width, height and loading="lazy".
4. Make .gallery a grid with auto-fill columns.
5. Force a 3:2 shape with aspect-ratio and object-fit: cover.
6. Add the hover zoom with transition and transform.

Project 110: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - Gallery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Papyrus Stationery gallery</h1>
    <div class="gallery">
      <figure><img src="images/stationery-1.jpg" alt="Dotted
notebook" width="600" height="400" loading="lazy"><figcaption>Dotted
notebook</figcaption></figure>
      <figure><img src="images/stationery-2.jpg" alt="Fountain pen"
width="600" height="400" loading="lazy"><figcaption>Fountain pen</
figcaption></figure>
      <figure><img src="images/stationery-3.jpg" alt="Washi tape set"
width="600" height="400" loading="lazy"><figcaption>Washi tape set</
figcaption></figure>
      <figure><img src="images/stationery-4.jpg" alt="Desk planner"
width="600" height="400" loading="lazy"><figcaption>Desk planner</
figcaption></figure>
    </div>
  </main>
</body>
</html>
```

Project 110: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; }
.gallery { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fill, minmax(16rem, 1fr)); }
figure { margin: 0; background: var(--accent); border-radius: 12px;
overflow: hidden; }
img { display: block; width: 100%; height: auto; aspect-ratio: 3 / 2;
object-fit: cover; }
figcaption { padding: .6rem .9rem; font-size: .95rem; }
figure:hover img { transform: scale(1.03); }
img { transition: transform .3s; }
```

Project 110 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - Gallery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Papyrus Stationery gallery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure><img src="images/stationery-1.jpg" alt="Dotted notebook" wi...	An image; alt describes it, width and height reserve space before it loads.
<figure><img src="images/stationery-2.jpg" alt="Fountain pen" width...	Self-contained media with an optional caption.
<figure><img src="images/stationery-3.jpg" alt="Washi tape set" wid...	Caption for the figure.

Line	What it does
<figure><img src="images/stationery-4.jpg" alt="Desk planner" width...	Defers loading until the image is near the viewport.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fill, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 12px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
font-size: .95rem;	Size of the text.
figure:hover img {	Applies while the pointer is over the element.
transform: scale(1.03);	Enlarges or shrinks the element visually.
transition: transform .3s;	Animates property changes smoothly, for example on hover.

Check your work

- All images have meaningful alt
- No layout jump while loading
- Grid reflows on narrow screens
- Zoom does not overflow the card

Exercises

1. Make the first image span two columns with grid-column: span 2.
2. Add a lightbox using <dialog>.
3. Use <picture> to serve WebP.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 111: Photo gallery for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 1 | Files: index.html, styles.css

Brief

Lay out four captioned photos in a responsive grid using figure and figcaption, with lazy loading and a gentle hover zoom.

Learning goals

- Use figure/figcaption for captioned images
- Reserve space with width, height and aspect-ratio
- Crop images consistently with object-fit

Elements and CSS used

HTML elements	CSS features
figure, img, figcaption, div, h1	grid-template-columns, auto-fill, aspect-ratio, object-fit, overflow: hidden, transition, transform

Build guide

1. Create an images folder with four photos (any JPEGs, renamed).
2. Write one <figure> per photo with img and figcaption.
3. Give every img alt text, width, height and loading="lazy".
4. Make .gallery a grid with auto-fill columns.
5. Force a 3:2 shape with aspect-ratio and object-fit: cover.
6. Add the hover zoom with transition and transform.

Project 111: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - Gallery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Oasis Plant Nursery gallery</h1>
    <div class="gallery">
      <figure><img src="images/plants-1.jpg" alt="Monstera"
width="600" height="400" loading="lazy"><figcaption>Monstera</
figcaption></figure>
      <figure><img src="images/plants-2.jpg" alt="Snake plant"
width="600" height="400" loading="lazy"><figcaption>Snake plant</
figcaption></figure>
      <figure><img src="images/plants-3.jpg" alt="Basil pot"
width="600" height="400" loading="lazy"><figcaption>Basil pot</
figcaption></figure>
      <figure><img src="images/plants-4.jpg" alt="Olive tree"
width="600" height="400" loading="lazy"><figcaption>Olive tree</
figcaption></figure>
    </div>
  </main>
</body>
</html>
```

Project 111: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; }
.gallery { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fill, minmax(16rem, 1fr)); }
figure { margin: 0; background: var(--accent); border-radius: 12px;
overflow: hidden; }
img { display: block; width: 100%; height: auto; aspect-ratio: 3 / 2;
object-fit: cover; }
figcaption { padding: .6rem .9rem; font-size: .95rem; }
figure:hover img { transform: scale(1.03); }
img { transition: transform .3s; }
```

Project 111 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - Gallery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Oasis Plant Nursery gallery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure><img src="images/plants-1.jpg" alt="Monstera" width="600" h...	An image; alt describes it, width and height reserve space before it loads.
<figure><img src="images/plants-2.jpg" alt="Snake plant" width="600...	Self-contained media with an optional caption.

Line	What it does
<figure><img src="images/plants-3.jpg" alt="Basil pot" width="600" ...	Caption for the figure.
<figure><img src="images/plants-4.jpg" alt="Olive tree" width="600"...	Defers loading until the image is near the viewport.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 12px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
font-size: .95rem;	Size of the text.
figure:hover img {	Applies while the pointer is over the element.
transform: scale(1.03);	Enlarges or shrinks the element visually.
transition: transform .3s;	Animates property changes smoothly, for example on hover.

Check your work

- All images have meaningful alt
- No layout jump while loading
- Grid reflows on narrow screens

- Zoom does not overflow the card

Exercises

1. Make the first image span two columns with grid-column: span 2.
2. Add a lightbox using <dialog>.
3. Use <picture> to serve WebP.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 112: Photo gallery for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 1 | Files: index.html, styles.css

Brief

Lay out four captioned photos in a responsive grid using figure and figcaption, with lazy loading and a gentle hover zoom.

Learning goals

- Use figure/figcaption for captioned images
- Reserve space with width, height and aspect-ratio
- Crop images consistently with object-fit

Elements and CSS used

HTML elements	CSS features
figure, img, figcaption, div, h1	grid-template-columns, auto-fill, aspect-ratio, object-fit, overflow: hidden, transition, transform

Build guide

1. Create an images folder with four photos (any JPEGs, renamed).
2. Write one <figure> per photo with img and figcaption.
3. Give every img alt text, width, height and loading="lazy".
4. Make .gallery a grid with auto-fill columns.
5. Force a 3:2 shape with aspect-ratio and object-fit: cover.
6. Add the hover zoom with transition and transform.

Project 112: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - Gallery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cedar Furniture gallery</h1>
    <div class="gallery">
      <figure><img src="images/furniture-1.jpg" alt="Oak dining
table" width="600" height="400" loading="lazy"><figcaption>Oak dining
table</figcaption></figure>
      <figure><img src="images/furniture-2.jpg" alt="Bookshelf"
width="600" height="400" loading="lazy"><figcaption>Bookshelf</
figcaption></figure>
      <figure><img src="images/furniture-3.jpg" alt="Bedside table"
width="600" height="400" loading="lazy"><figcaption>Bedside table</
figcaption></figure>
      <figure><img src="images/furniture-4.jpg" alt="Coffee table"
width="600" height="400" loading="lazy"><figcaption>Coffee table</
figcaption></figure>
    </div>
  </main>
</body>
</html>
```

Project 112: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; }
.gallery { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fill, minmax(16rem, 1fr)); }
figure { margin: 0; background: var(--accent); border-radius: 12px;
overflow: hidden; }
img { display: block; width: 100%; height: auto; aspect-ratio: 3 / 2;
object-fit: cover; }
figcaption { padding: .6rem .9rem; font-size: .95rem; }
figure:hover img { transform: scale(1.03); }
img { transition: transform .3s; }
```

Project 112 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - Gallery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cedar Furniture gallery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure><img src="images/furniture-1.jpg" alt="Oak dining table" wi...	An image; alt describes it, width and height reserve space before it loads.
<figure><img src="images/furniture-2.jpg" alt="Bookshelf" width="60...	Self-contained media with an optional caption.
<figure><img src="images/furniture-3.jpg" alt="Bedside table" width...	Caption for the figure.

Line	What it does
<figure><img src="images/furniture-4.jpg" alt="Coffee table" width=...	Defers loading until the image is near the viewport.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fill, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 12px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
font-size: .95rem;	Size of the text.
figure:hover img {	Applies while the pointer is over the element.
transform: scale(1.03);	Enlarges or shrinks the element visually.
transition: transform .3s;	Animates property changes smoothly, for example on hover.

Check your work

- All images have meaningful alt
- No layout jump while loading
- Grid reflows on narrow screens
- Zoom does not overflow the card

Exercises

1. Make the first image span two columns with grid-column: span 2.
2. Add a lightbox using <dialog>.
3. Use <picture> to serve WebP.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 113: Photo gallery for Byte Repair

Theme: Byte Repair (Nasr City) | Level 1 | Files: index.html, styles.css

Brief

Lay out four captioned photos in a responsive grid using figure and figcaption, with lazy loading and a gentle hover zoom.

Learning goals

- Use figure/figcaption for captioned images
- Reserve space with width, height and aspect-ratio
- Crop images consistently with object-fit

Elements and CSS used

HTML elements	CSS features
figure, img, figcaption, div, h1	grid-template-columns, auto-fill, aspect-ratio, object-fit, overflow: hidden, transition, transform

Build guide

1. Create an images folder with four photos (any JPEGs, renamed).
2. Write one <figure> per photo with img and figcaption.
3. Give every img alt text, width, height and loading="lazy".
4. Make .gallery a grid with auto-fill columns.
5. Force a 3:2 shape with aspect-ratio and object-fit: cover.
6. Add the hover zoom with transition and transform.

Project 113: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - Gallery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Byte Repair gallery</h1>
    <div class="gallery">
      <figure><img src="images/repair-1.jpg" alt="Screen replacement"
width="600" height="400" loading="lazy"><figcaption>Screen
replacement</figcaption></figure>
      <figure><img src="images/repair-2.jpg" alt="Battery swap"
width="600" height="400" loading="lazy"><figcaption>Battery swap</
figcaption></figure>
      <figure><img src="images/repair-3.jpg" alt="Laptop cleaning"
width="600" height="400" loading="lazy"><figcaption>Laptop cleaning</
figcaption></figure>
      <figure><img src="images/repair-4.jpg" alt="Data recovery"
width="600" height="400" loading="lazy"><figcaption>Data recovery</
figcaption></figure>
    </div>
  </main>
</body>
</html>
```

Project 113: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; }
.gallery { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fill, minmax(16rem, 1fr)); }
figure { margin: 0; background: var(--accent); border-radius: 12px;
overflow: hidden; }
img { display: block; width: 100%; height: auto; aspect-ratio: 3 / 2;
object-fit: cover; }
figcaption { padding: .6rem .9rem; font-size: .95rem; }
figure:hover img { transform: scale(1.03); }
img { transition: transform .3s; }
```

Project 113 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - Gallery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Byte Repair gallery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure><img src="images/repair-1.jpg" alt="Screen replacement" wid...	An image; alt describes it, width and height reserve space before it loads.
<figure><img src="images/repair-2.jpg" alt="Battery swap" width="60...	Self-contained media with an optional caption.

Line	What it does
<figure><img src="images/repair-3.jpg" alt="Laptop cleaning" width=...	Caption for the figure.
<figure><img src="images/repair-4.jpg" alt="Data recovery" width="6...	Defers loading until the image is near the viewport.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 12px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
font-size: .95rem;	Size of the text.
figure:hover img {	Applies while the pointer is over the element.
transform: scale(1.03);	Enlarges or shrinks the element visually.
transition: transform .3s;	Animates property changes smoothly, for example on hover.

Check your work

- All images have meaningful alt
- No layout jump while loading

- Grid reflows on narrow screens
- Zoom does not overflow the card

Exercises

1. Make the first image span two columns with grid-column: span 2.
2. Add a lightbox using <dialog>.
3. Use <picture> to serve WebP.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 114: Photo gallery for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 1 | Files: index.html, styles.css

Brief

Lay out four captioned photos in a responsive grid using figure and figcaption, with lazy loading and a gentle hover zoom.

Learning goals

- Use figure/figcaption for captioned images
- Reserve space with width, height and aspect-ratio
- Crop images consistently with object-fit

Elements and CSS used

HTML elements	CSS features
figure, img, figcaption, div, h1	grid-template-columns, auto-fill, aspect-ratio, object-fit, overflow: hidden, transition, transform

Build guide

1. Create an images folder with four photos (any JPEGs, renamed).
2. Write one <figure> per photo with img and figcaption.
3. Give every img alt text, width, height and loading="lazy".
4. Make .gallery a grid with auto-fill columns.
5. Force a 3:2 shape with aspect-ratio and object-fit: cover.
6. Add the hover zoom with transition and transform.

Project 114: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - Gallery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Sahara Pet Care gallery</h1>
    <div class="gallery">
      <figure><img src="images/pets-1.jpg" alt="Full grooming"
width="600" height="400" loading="lazy"><figcaption>Full grooming</
figcaption></figure>
      <figure><img src="images/pets-2.jpg" alt="Day boarding"
width="600" height="400" loading="lazy"><figcaption>Day boarding</
figcaption></figure>
      <figure><img src="images/pets-3.jpg" alt="Vaccination"
width="600" height="400" loading="lazy"><figcaption>Vaccination</
figcaption></figure>
      <figure><img src="images/pets-4.jpg" alt="Dog walking"
width="600" height="400" loading="lazy"><figcaption>Dog walking</
figcaption></figure>
    </div>
  </main>
</body>
</html>
```

Project 114: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; }
.gallery { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fill, minmax(16rem, 1fr)); }
figure { margin: 0; background: var(--accent); border-radius: 12px;
overflow: hidden; }
img { display: block; width: 100%; height: auto; aspect-ratio: 3 / 2;
object-fit: cover; }
figcaption { padding: .6rem .9rem; font-size: .95rem; }
figure:hover img { transform: scale(1.03); }
img { transition: transform .3s; }
```

Project 114 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - Gallery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Sahara Pet Care gallery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure><img src="images/pets-1.jpg" alt="Full grooming" width="600...	An image; alt describes it, width and height reserve space before it loads.
<figure><img src="images/pets-2.jpg" alt="Day boarding" width="600"...	Self-contained media with an optional caption.

Line	What it does
<figure><img src="images/pets-3.jpg" alt="Vaccination" width="600" ...	Caption for the figure.
<figure><img src="images/pets-4.jpg" alt="Dog walking" width="600" ...	Defers loading until the image is near the viewport.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 12px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
font-size: .95rem;	Size of the text.
figure:hover img {	Applies while the pointer is over the element.
transform: scale(1.03);	Enlarges or shrinks the element visually.
transition: transform .3s;	Animates property changes smoothly, for example on hover.

Check your work

- All images have meaningful alt
- No layout jump while loading

- Grid reflows on narrow screens
- Zoom does not overflow the card

Exercises

1. Make the first image span two columns with grid-column: span 2.
2. Add a lightbox using <dialog>.
3. Use <picture> to serve WebP.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 115: Photo gallery for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Lay out four captioned photos in a responsive grid using figure and figcaption, with lazy loading and a gentle hover zoom.

Learning goals

- Use figure/figcaption for captioned images
- Reserve space with width, height and aspect-ratio
- Crop images consistently with object-fit

Elements and CSS used

HTML elements	CSS features
figure, img, figcaption, div, h1	grid-template-columns, auto-fill, aspect-ratio, object-fit, overflow: hidden, transition, transform

Build guide

1. Create an images folder with four photos (any JPEGs, renamed).
2. Write one <figure> per photo with img and figcaption.
3. Give every img alt text, width, height and loading="lazy".
4. Make .gallery a grid with auto-fill columns.
5. Force a 3:2 shape with aspect-ratio and object-fit: cover.
6. Add the hover zoom with transition and transform.

Project 115: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - Gallery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Alexandria Sailing School gallery</h1>
    <div class="gallery">
      <figure><img src="images/sailing-1.jpg" alt="Taster session"
width="600" height="400" loading="lazy"><figcaption>Taster session</
figcaption></figure>
      <figure><img src="images/sailing-2.jpg" alt="Beginner course"
width="600" height="400" loading="lazy"><figcaption>Beginner course</
figcaption></figure>
      <figure><img src="images/sailing-3.jpg" alt="Racing clinic"
width="600" height="400" loading="lazy"><figcaption>Racing clinic</
figcaption></figure>
      <figure><img src="images/sailing-4.jpg" alt="Private lesson"
width="600" height="400" loading="lazy"><figcaption>Private lesson</
figcaption></figure>
    </div>
  </main>
</body>
</html>
```

Project 115: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; }
.gallery { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fill, minmax(16rem, 1fr)); }
figure { margin: 0; background: var(--accent); border-radius: 12px;
overflow: hidden; }
img { display: block; width: 100%; height: auto; aspect-ratio: 3 / 2;
object-fit: cover; }
figcaption { padding: .6rem .9rem; font-size: .95rem; }
figure:hover img { transform: scale(1.03); }
img { transition: transform .3s; }
```

Project 115 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - Gallery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Alexandria Sailing School gallery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure><img src="images/sailing-1.jpg" alt="Taster session" width=...	An image; alt describes it, width and height reserve space before it loads.
<figure><img src="images/sailing-2.jpg" alt="Beginner course" width...	Self-contained media with an optional caption.
<figure><img src="images/sailing-3.jpg" alt="Racing clinic" width="...	Caption for the figure.

Line	What it does
<figure><img src="images/sailing-4.jpg" alt="Private lesson" width=...	Defers loading until the image is near the viewport.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fill, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 12px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
font-size: .95rem;	Size of the text.
figure:hover img {	Applies while the pointer is over the element.
transform: scale(1.03);	Enlarges or shrinks the element visually.
transition: transform .3s;	Animates property changes smoothly, for example on hover.

Check your work

- All images have meaningful alt
- No layout jump while loading
- Grid reflows on narrow screens
- Zoom does not overflow the card

Exercises

1. Make the first image span two columns with grid-column: span 2.
2. Add a lightbox using <dialog>.
3. Use <picture> to serve WebP.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 116: Photo gallery for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Lay out four captioned photos in a responsive grid using figure and figcaption, with lazy loading and a gentle hover zoom.

Learning goals

- Use figure/figcaption for captioned images
- Reserve space with width, height and aspect-ratio
- Crop images consistently with object-fit

Elements and CSS used

HTML elements	CSS features
figure, img, figcaption, div, h1	grid-template-columns, auto-fill, aspect-ratio, object-fit, overflow: hidden, transition, transform

Build guide

1. Create an images folder with four photos (any JPEGs, renamed).
2. Write one <figure> per photo with img and figcaption.
3. Give every img alt text, width, height and loading="lazy".
4. Make .gallery a grid with auto-fill columns.
5. Force a 3:2 shape with aspect-ratio and object-fit: cover.
6. Add the hover zoom with transition and transform.

Project 116: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - Gallery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Habiba Handmade Jewellery gallery</h1>
    <div class="gallery">
      <figure><img src="images/jewellery-1.jpg" alt="Lotus pendant"
width="600" height="400" loading="lazy"><figcaption>Lotus pendant</
figcaption></figure>
      <figure><img src="images/jewellery-2.jpg" alt="Brass cuff"
width="600" height="400" loading="lazy"><figcaption>Brass cuff</
figcaption></figure>
      <figure><img src="images/jewellery-3.jpg" alt="Bead earrings"
width="600" height="400" loading="lazy"><figcaption>Bead earrings</
figcaption></figure>
      <figure><img src="images/jewellery-4.jpg" alt="Ankh ring"
width="600" height="400" loading="lazy"><figcaption>Ankh ring</
figcaption></figure>
    </div>
  </main>
</body>
</html>
```

Project 116: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; }
.gallery { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fill, minmax(16rem, 1fr)); }
figure { margin: 0; background: var(--accent); border-radius: 12px;
overflow: hidden; }
img { display: block; width: 100%; height: auto; aspect-ratio: 3 / 2;
object-fit: cover; }
figcaption { padding: .6rem .9rem; font-size: .95rem; }
figure:hover img { transform: scale(1.03); }
img { transition: transform .3s; }
```

Project 116 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - Gallery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Habiba Handmade Jewellery gallery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure><img src="images/jewellery-1.jpg" alt="Lotus pendant" width...	An image; alt describes it, width and height reserve space before it loads.
<figure><img src="images/jewellery-2.jpg" alt="Brass cuff" width="6...	Self-contained media with an optional caption.
<figure><img src="images/jewellery-3.jpg" alt="Bead earrings" width...	Caption for the figure.

Line	What it does
<figure><img src="images/jewellery-4.jpg" alt="Ankh ring" width="60...	Defers loading until the image is near the viewport.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fill, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 12px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
font-size: .95rem;	Size of the text.
figure:hover img {	Applies while the pointer is over the element.
transform: scale(1.03);	Enlarges or shrinks the element visually.
transition: transform .3s;	Animates property changes smoothly, for example on hover.

Check your work

- All images have meaningful alt
- No layout jump while loading
- Grid reflows on narrow screens
- Zoom does not overflow the card

Exercises

1. Make the first image span two columns with grid-column: span 2.
2. Add a lightbox using <dialog>.
3. Use <picture> to serve WebP.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 117: Photo gallery for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 1 | Files: index.html, styles.css

Brief

Lay out four captioned photos in a responsive grid using figure and figcaption, with lazy loading and a gentle hover zoom.

Learning goals

- Use figure/figcaption for captioned images
- Reserve space with width, height and aspect-ratio
- Crop images consistently with object-fit

Elements and CSS used

HTML elements	CSS features
figure, img, figcaption, div, h1	grid-template-columns, auto-fill, aspect-ratio, object-fit, overflow: hidden, transition, transform

Build guide

1. Create an images folder with four photos (any JPEGs, renamed).
2. Write one <figure> per photo with img and figcaption.
3. Give every img alt text, width, height and loading="lazy".
4. Make .gallery a grid with auto-fill columns.
5. Force a 3:2 shape with aspect-ratio and object-fit: cover.
6. Add the hover zoom with transition and transform.

Project 117: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - Gallery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Fayoum Pottery Studio gallery</h1>
    <div class="gallery">
      <figure><img src="images/pottery-1.jpg" alt="Intro to the
wheel" width="600" height="400" loading="lazy"><figcaption>Intro to
the wheel</figcaption></figure>
      <figure><img src="images/pottery-2.jpg" alt="Glazing day"
width="600" height="400" loading="lazy"><figcaption>Glazing day</
figcaption></figure>
      <figure><img src="images/pottery-3.jpg" alt="Kids clay class"
width="600" height="400" loading="lazy"><figcaption>Kids clay class</
figcaption></figure>
      <figure><img src="images/pottery-4.jpg" alt="Weekend retreat"
width="600" height="400" loading="lazy"><figcaption>Weekend retreat</
figcaption></figure>
    </div>
  </main>
</body>
</html>
```

Project 117: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; }
.gallery { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fill, minmax(16rem, 1fr)); }
figure { margin: 0; background: var(--accent); border-radius: 12px;
overflow: hidden; }
img { display: block; width: 100%; height: auto; aspect-ratio: 3 / 2;
object-fit: cover; }
figcaption { padding: .6rem .9rem; font-size: .95rem; }
figure:hover img { transform: scale(1.03); }
img { transition: transform .3s; }
```

Project 117 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - Gallery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Fayoum Pottery Studio gallery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure><img src="images/pottery-1.jpg" alt="Intro to the wheel" wi...	An image; alt describes it, width and height reserve space before it loads.
<figure><img src="images/pottery-2.jpg" alt="Glazing day" width="60...	Self-contained media with an optional caption.
<figure><img src="images/pottery-3.jpg" alt="Kids clay class" width...	Caption for the figure.

Line	What it does
<figure><img src="images/pottery-4.jpg" alt="Weekend retreat" width...	Defers loading until the image is near the viewport.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fill, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 12px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
font-size: .95rem;	Size of the text.
figure:hover img {	Applies while the pointer is over the element.
transform: scale(1.03);	Enlarges or shrinks the element visually.
transition: transform .3s;	Animates property changes smoothly, for example on hover.

Check your work

- All images have meaningful alt
- No layout jump while loading
- Grid reflows on narrow screens
- Zoom does not overflow the card

Exercises

1. Make the first image span two columns with grid-column: span 2.
2. Add a lightbox using <dialog>.
3. Use <picture> to serve WebP.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 118: Photo gallery for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 1 | Files: index.html, styles.css

Brief

Lay out four captioned photos in a responsive grid using figure and figcaption, with lazy loading and a gentle hover zoom.

Learning goals

- Use figure/figcaption for captioned images
- Reserve space with width, height and aspect-ratio
- Crop images consistently with object-fit

Elements and CSS used

HTML elements	CSS features
figure, img, figcaption, div, h1	grid-template-columns, auto-fill, aspect-ratio, object-fit, overflow: hidden, transition, transform

Build guide

1. Create an images folder with four photos (any JPEGs, renamed).
2. Write one <figure> per photo with img and figcaption.
3. Give every img alt text, width, height and loading="lazy".
4. Make .gallery a grid with auto-fill columns.
5. Force a 3:2 shape with aspect-ratio and object-fit: cover.
6. Add the hover zoom with transition and transform.

Project 118: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - Gallery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cleopatra Beauty Salon gallery</h1>
    <div class="gallery">
      <figure><img src="images/salon-1.jpg" alt="Haircut and blow-
dry" width="600" height="400" loading="lazy"><figcaption>Haircut and
blow-dry</figcaption></figure>
      <figure><img src="images/salon-2.jpg" alt="Manicure"
width="600" height="400" loading="lazy"><figcaption>Manicure</
figcaption></figure>
      <figure><img src="images/salon-3.jpg" alt="Facial" width="600"
height="400" loading="lazy"><figcaption>Facial</figcaption></figure>
      <figure><img src="images/salon-4.jpg" alt="Bridal package"
width="600" height="400" loading="lazy"><figcaption>Bridal package</
figcaption></figure>
    </div>
  </main>
</body>
</html>
```

Project 118: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; }
.gallery { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fill, minmax(16rem, 1fr)); }
figure { margin: 0; background: var(--accent); border-radius: 12px;
overflow: hidden; }
img { display: block; width: 100%; height: auto; aspect-ratio: 3 / 2;
object-fit: cover; }
figcaption { padding: .6rem .9rem; font-size: .95rem; }
figure:hover img { transform: scale(1.03); }
img { transition: transform .3s; }
```

Project 118 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - Gallery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cleopatra Beauty Salon gallery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure><img src="images/salon-1.jpg" alt="Haircut and blow-dry" wi...	An image; alt describes it, width and height reserve space before it loads.
<figure><img src="images/salon-2.jpg" alt="Manicure" width="600" he...	Self-contained media with an optional caption.

Line	What it does
<figure><img src="images/salon-3.jpg" alt="Facial" width="600" heig...	Caption for the figure.
<figure><img src="images/salon-4.jpg" alt="Bridal package" width="6...	Defers loading until the image is near the viewport.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 12px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
font-size: .95rem;	Size of the text.
figure:hover img {	Applies while the pointer is over the element.
transform: scale(1.03);	Enlarges or shrinks the element visually.
transition: transform .3s;	Animates property changes smoothly, for example on hover.

Check your work

- All images have meaningful alt
- No layout jump while loading

- Grid reflows on narrow screens
- Zoom does not overflow the card

Exercises

1. Make the first image span two columns with grid-column: span 2.
2. Add a lightbox using <dialog>.
3. Use <picture> to serve WebP.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 119: Photo gallery for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 1 | Files: index.html, styles.css

Brief

Lay out four captioned photos in a responsive grid using figure and figcaption, with lazy loading and a gentle hover zoom.

Learning goals

- Use figure/figcaption for captioned images
- Reserve space with width, height and aspect-ratio
- Crop images consistently with object-fit

Elements and CSS used

HTML elements	CSS features
figure, img, figcaption, div, h1	grid-template-columns, auto-fill, aspect-ratio, object-fit, overflow: hidden, transition, transform

Build guide

1. Create an images folder with four photos (any JPEGs, renamed).
2. Write one <figure> per photo with img and figcaption.
3. Give every img alt text, width, height and loading="lazy".
4. Make .gallery a grid with auto-fill columns.
5. Force a 3:2 shape with aspect-ratio and object-fit: cover.
6. Add the hover zoom with transition and transform.

Project 119: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - Gallery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Suez Auto Service gallery</h1>
    <div class="gallery">
      <figure><img src="images/auto-1.jpg" alt="Oil change"
width="600" height="400" loading="lazy"><figcaption>Oil change</
figcaption></figure>
      <figure><img src="images/auto-2.jpg" alt="Brake pads"
width="600" height="400" loading="lazy"><figcaption>Brake pads</
figcaption></figure>
      <figure><img src="images/auto-3.jpg" alt="Air conditioning"
width="600" height="400" loading="lazy"><figcaption>Air conditioning</
figcaption></figure>
      <figure><img src="images/auto-4.jpg" alt="Pre-purchase
inspection" width="600" height="400" loading="lazy"><figcaption>Pre-
purchase inspection</figcaption></figure>
    </div>
  </main>
</body>
</html>
```

Project 119: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; }
.gallery { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fill, minmax(16rem, 1fr)); }
figure { margin: 0; background: var(--accent); border-radius: 12px;
overflow: hidden; }
img { display: block; width: 100%; height: auto; aspect-ratio: 3 / 2;
object-fit: cover; }
figcaption { padding: .6rem .9rem; font-size: .95rem; }
figure:hover img { transform: scale(1.03); }
img { transition: transform .3s; }
```

Project 119 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - Gallery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Suez Auto Service gallery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure><img src="images/auto-1.jpg" alt="Oil change" width="600" h...	An image; alt describes it, width and height reserve space before it loads.
<figure><img src="images/auto-2.jpg" alt="Brake pads" width="600" h...	Self-contained media with an optional caption.

Line	What it does
<figure><img src="images/auto-3.jpg" alt="Air conditioning" width="...	Caption for the figure.
<figure><img src="images/auto-4.jpg" alt="Pre-purchase inspection" ...	Defers loading until the image is near the viewport.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 12px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
font-size: .95rem;	Size of the text.
figure:hover img {	Applies while the pointer is over the element.
transform: scale(1.03);	Enlarges or shrinks the element visually.
transition: transform .3s;	Animates property changes smoothly, for example on hover.

Check your work

- All images have meaningful alt
- No layout jump while loading

- Grid reflows on narrow screens
- Zoom does not overflow the card

Exercises

1. Make the first image span two columns with grid-column: span 2.
2. Add a lightbox using <dialog>.
3. Use <picture> to serve WebP.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 120: Photo gallery for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 1 | Files: index.html, styles.css

Brief

Lay out four captioned photos in a responsive grid using figure and figcaption, with lazy loading and a gentle hover zoom.

Learning goals

- Use figure/figcaption for captioned images
- Reserve space with width, height and aspect-ratio
- Crop images consistently with object-fit

Elements and CSS used

HTML elements	CSS features
figure, img, figcaption, div, h1	grid-template-columns, auto-fill, aspect-ratio, object-fit, overflow: hidden, transition, transform

Build guide

1. Create an images folder with four photos (any JPEGs, renamed).
2. Write one <figure> per photo with img and figcaption.
3. Give every img alt text, width, height and loading="lazy".
4. Make .gallery a grid with auto-fill columns.
5. Force a 3:2 shape with aspect-ratio and object-fit: cover.
6. Add the hover zoom with transition and transform.

Project 120: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - Gallery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Luxor Music Academy gallery</h1>
    <div class="gallery">
      <figure><img src="images/music-1.jpg" alt="Oud for beginners"
width="600" height="400" loading="lazy"><figcaption>Oud for
beginners</figcaption></figure>
      <figure><img src="images/music-2.jpg" alt="Piano grade 1"
width="600" height="400" loading="lazy"><figcaption>Piano grade 1</
figcaption></figure>
      <figure><img src="images/music-3.jpg" alt="Guitar chords"
width="600" height="400" loading="lazy"><figcaption>Guitar chords</
figcaption></figure>
      <figure><img src="images/music-4.jpg" alt="Voice coaching"
width="600" height="400" loading="lazy"><figcaption>Voice coaching</
figcaption></figure>
    </div>
  </main>
</body>
</html>
```

Project 120: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; }
.gallery { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fill, minmax(16rem, 1fr)); }
figure { margin: 0; background: var(--accent); border-radius: 12px;
overflow: hidden; }
img { display: block; width: 100%; height: auto; aspect-ratio: 3 / 2;
object-fit: cover; }
figcaption { padding: .6rem .9rem; font-size: .95rem; }
figure:hover img { transform: scale(1.03); }
img { transition: transform .3s; }
```

Project 120 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - Gallery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Luxor Music Academy gallery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure><img src="images/music-1.jpg" alt="Oud for beginners" width...	An image; alt describes it, width and height reserve space before it loads.
<figure><img src="images/music-2.jpg" alt="Piano grade 1" width="60...	Self-contained media with an optional caption.

Line	What it does
<figure><img src="images/music-3.jpg" alt="Guitar chords" width="60...	Caption for the figure.
<figure><img src="images/music-4.jpg" alt="Voice coaching" width="6...	Defers loading until the image is near the viewport.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 12px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
font-size: .95rem;	Size of the text.
figure:hover img {	Applies while the pointer is over the element.
transform: scale(1.03);	Enlarges or shrinks the element visually.
transition: transform .3s;	Animates property changes smoothly, for example on hover.

Check your work

- All images have meaningful alt
- No layout jump while loading

- Grid reflows on narrow screens
- Zoom does not overflow the card

Exercises

1. Make the first image span two columns with grid-column: span 2.
2. Add a lightbox using <dialog>.
3. Use <picture> to serve WebP.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 121: Photo gallery for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 1 | Files: index.html, styles.css

Brief

Lay out four captioned photos in a responsive grid using figure and figcaption, with lazy loading and a gentle hover zoom.

Learning goals

- Use figure/figcaption for captioned images
- Reserve space with width, height and aspect-ratio
- Crop images consistently with object-fit

Elements and CSS used

HTML elements	CSS features
figure, img, figcaption, div, h1	grid-template-columns, auto-fill, aspect-ratio, object-fit, overflow: hidden, transition, transform

Build guide

1. Create an images folder with four photos (any JPEGs, renamed).
2. Write one <figure> per photo with img and figcaption.
3. Give every img alt text, width, height and loading="lazy".
4. Make .gallery a grid with auto-fill columns.
5. Force a 3:2 shape with aspect-ratio and object-fit: cover.
6. Add the hover zoom with transition and transform.

Project 121: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - Gallery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Port Said Seafood gallery</h1>
    <div class="gallery">
      <figure><img src="images/restaurant-1.jpg" alt="Grilled sea
bass" width="600" height="400" loading="lazy"><figcaption>Grilled sea
bass</figcaption></figure>
      <figure><img src="images/restaurant-2.jpg" alt="Shrimp tagine"
width="600" height="400" loading="lazy"><figcaption>Shrimp tagine</
figcaption></figure>
      <figure><img src="images/restaurant-3.jpg" alt="Calamari"
width="600" height="400" loading="lazy"><figcaption>Calamari</
figcaption></figure>
      <figure><img src="images/restaurant-4.jpg" alt="Fish soup"
width="600" height="400" loading="lazy"><figcaption>Fish soup</
figcaption></figure>
    </div>
  </main>
</body>
</html>
```

Project 121: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; }
.gallery { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fill, minmax(16rem, 1fr)); }
figure { margin: 0; background: var(--accent); border-radius: 12px;
overflow: hidden; }
img { display: block; width: 100%; height: auto; aspect-ratio: 3 / 2;
object-fit: cover; }
figcaption { padding: .6rem .9rem; font-size: .95rem; }
figure:hover img { transform: scale(1.03); }
img { transition: transform .3s; }
```

Project 121 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - Gallery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Port Said Seafood gallery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure><img src="images/restaurant-1.jpg" alt="Grilled sea bass" w...	An image; alt describes it, width and height reserve space before it loads.
<figure><img src="images/restaurant-2.jpg" alt="Shrimp tagine" widt...	Self-contained media with an optional caption.
<figure><img src="images/restaurant-3.jpg" alt="Calamari" width="60...	Caption for the figure.

Line	What it does
<figure><img src="images/restaurant-4.jpg" alt="Fish soup" width="6...	Defers loading until the image is near the viewport.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fill, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 12px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
font-size: .95rem;	Size of the text.
figure:hover img {	Applies while the pointer is over the element.
transform: scale(1.03);	Enlarges or shrinks the element visually.
transition: transform .3s;	Animates property changes smoothly, for example on hover.

Check your work

- All images have meaningful alt
- No layout jump while loading
- Grid reflows on narrow screens
- Zoom does not overflow the card

Exercises

1. Make the first image span two columns with grid-column: span 2.
2. Add a lightbox using <dialog>.
3. Use <picture> to serve WebP.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 122: Photo gallery for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 1 | Files: index.html, styles.css

Brief

Lay out four captioned photos in a responsive grid using figure and figcaption, with lazy loading and a gentle hover zoom.

Learning goals

- Use figure/figcaption for captioned images
- Reserve space with width, height and aspect-ratio
- Crop images consistently with object-fit

Elements and CSS used

HTML elements	CSS features
figure, img, figcaption, div, h1	grid-template-columns, auto-fill, aspect-ratio, object-fit, overflow: hidden, transition, transform

Build guide

1. Create an images folder with four photos (any JPEGs, renamed).
2. Write one <figure> per photo with img and figcaption.
3. Give every img alt text, width, height and loading="lazy".
4. Make .gallery a grid with auto-fill columns.
5. Force a 3:2 shape with aspect-ratio and object-fit: cover.
6. Add the hover zoom with transition and transform.

Project 122: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - Gallery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Delta Kids Library gallery</h1>
    <div class="gallery">
      <figure><img src="images/library-1.jpg" alt="Story hour"
width="600" height="400" loading="lazy"><figcaption>Story hour</
figcaption></figure>
      <figure><img src="images/library-2.jpg" alt="Reading club"
width="600" height="400" loading="lazy"><figcaption>Reading club</
figcaption></figure>
      <figure><img src="images/library-3.jpg" alt="Homework help"
width="600" height="400" loading="lazy"><figcaption>Homework help</
figcaption></figure>
      <figure><img src="images/library-4.jpg" alt="Summer challenge"
width="600" height="400" loading="lazy"><figcaption>Summer challenge</
figcaption></figure>
    </div>
  </main>
</body>
</html>
```

Project 122: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; }
.gallery { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fill, minmax(16rem, 1fr)); }
figure { margin: 0; background: var(--accent); border-radius: 12px;
overflow: hidden; }
img { display: block; width: 100%; height: auto; aspect-ratio: 3 / 2;
object-fit: cover; }
figcaption { padding: .6rem .9rem; font-size: .95rem; }
figure:hover img { transform: scale(1.03); }
img { transition: transform .3s; }
```

Project 122 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - Gallery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Delta Kids Library gallery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure><img src="images/library-1.jpg" alt="Story hour" width="600...	An image; alt describes it, width and height reserve space before it loads.
<figure><img src="images/library-2.jpg" alt="Reading club" width="6...	Self-contained media with an optional caption.
<figure><img src="images/library-3.jpg" alt="Homework help" width="...	Caption for the figure.

Line	What it does
<figure><img src="images/library-4.jpg" alt="Summer challenge" widt...	Defers loading until the image is near the viewport.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fill, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 12px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
font-size: .95rem;	Size of the text.
figure:hover img {	Applies while the pointer is over the element.
transform: scale(1.03);	Enlarges or shrinks the element visually.
transition: transform .3s;	Animates property changes smoothly, for example on hover.

Check your work

- All images have meaningful alt
- No layout jump while loading
- Grid reflows on narrow screens
- Zoom does not overflow the card

Exercises

1. Make the first image span two columns with grid-column: span 2.
2. Add a lightbox using <dialog>.
3. Use <picture> to serve WebP.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 123: Photo gallery for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Lay out four captioned photos in a responsive grid using figure and figcaption, with lazy loading and a gentle hover zoom.

Learning goals

- Use figure/figcaption for captioned images
- Reserve space with width, height and aspect-ratio
- Crop images consistently with object-fit

Elements and CSS used

HTML elements	CSS features
figure, img, figcaption, div, h1	grid-template-columns, auto-fill, aspect-ratio, object-fit, overflow: hidden, transition, transform

Build guide

1. Create an images folder with four photos (any JPEGs, renamed).
2. Write one <figure> per photo with img and figcaption.
3. Give every img alt text, width, height and loading="lazy".
4. Make .gallery a grid with auto-fill columns.
5. Force a 3:2 shape with aspect-ratio and object-fit: cover.
6. Add the hover zoom with transition and transform.

Project 123: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - Gallery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Nubian Guest House gallery</h1>
    <div class="gallery">
      <figure><img src="images/guesthouse-1.jpg" alt="Garden room"
width="600" height="400" loading="lazy"><figcaption>Garden room</
figcaption></figure>
      <figure><img src="images/guesthouse-2.jpg" alt="Nile view
suite" width="600" height="400" loading="lazy"><figcaption>Nile view
suite</figcaption></figure>
      <figure><img src="images/guesthouse-3.jpg" alt="Family room"
width="600" height="400" loading="lazy"><figcaption>Family room</
figcaption></figure>
      <figure><img src="images/guesthouse-4.jpg" alt="Rooftop dorm"
width="600" height="400" loading="lazy"><figcaption>Rooftop dorm</
figcaption></figure>
    </div>
  </main>
</body>
</html>
```

Project 123: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; }
.gallery { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fill, minmax(16rem, 1fr)); }
figure { margin: 0; background: var(--accent); border-radius: 12px;
overflow: hidden; }
img { display: block; width: 100%; height: auto; aspect-ratio: 3 / 2;
object-fit: cover; }
figcaption { padding: .6rem .9rem; font-size: .95rem; }
figure:hover img { transform: scale(1.03); }
img { transition: transform .3s; }
```

Project 123 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - Gallery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Nubian Guest House gallery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure><img src="images/guesthouse-1.jpg" alt="Garden room" width=...	An image; alt describes it, width and height reserve space before it loads.
<figure><img src="images/guesthouse-2.jpg" alt="Nile view suite" wi...	Self-contained media with an optional caption.
<figure><img src="images/guesthouse-3.jpg" alt="Family room" width=...	Caption for the figure.

Line	What it does
<figure><img src="images/guesthouse-4.jpg" alt="Rooftop dorm" width...	Defers loading until the image is near the viewport.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fill, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 12px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
font-size: .95rem;	Size of the text.
figure:hover img {	Applies while the pointer is over the element.
transform: scale(1.03);	Enlarges or shrinks the element visually.
transition: transform .3s;	Animates property changes smoothly, for example on hover.

Check your work

- All images have meaningful alt
- No layout jump while loading
- Grid reflows on narrow screens
- Zoom does not overflow the card

Exercises

1. Make the first image span two columns with grid-column: span 2.
2. Add a lightbox using <dialog>.
3. Use <picture> to serve WebP.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 124: Photo gallery for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 1 | Files: index.html, styles.css

Brief

Lay out four captioned photos in a responsive grid using figure and figcaption, with lazy loading and a gentle hover zoom.

Learning goals

- Use figure/figcaption for captioned images
- Reserve space with width, height and aspect-ratio
- Crop images consistently with object-fit

Elements and CSS used

HTML elements	CSS features
figure, img, figcaption, div, h1	grid-template-columns, auto-fill, aspect-ratio, object-fit, overflow: hidden, transition, transform

Build guide

1. Create an images folder with four photos (any JPEGs, renamed).
2. Write one <figure> per photo with img and figcaption.
3. Give every img alt text, width, height and loading="lazy".
4. Make .gallery a grid with auto-fill columns.
5. Force a 3:2 shape with aspect-ratio and object-fit: cover.
6. Add the hover zoom with transition and transform.

Project 124: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - Gallery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Ismailia Cycling Store gallery</h1>
    <div class="gallery">
      <figure><img src="images/cycling-1.jpg" alt="City bike"
width="600" height="400" loading="lazy"><figcaption>City bike</
figcaption></figure>
      <figure><img src="images/cycling-2.jpg" alt="Mountain bike"
width="600" height="400" loading="lazy"><figcaption>Mountain bike</
figcaption></figure>
      <figure><img src="images/cycling-3.jpg" alt="Kids bike"
width="600" height="400" loading="lazy"><figcaption>Kids bike</
figcaption></figure>
      <figure><img src="images/cycling-4.jpg" alt="Tune-up"
width="600" height="400" loading="lazy"><figcaption>Tune-up</
figcaption></figure>
    </div>
  </main>
</body>
</html>
```

Project 124: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; }
.gallery { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fill, minmax(16rem, 1fr)); }
figure { margin: 0; background: var(--accent); border-radius: 12px;
overflow: hidden; }
img { display: block; width: 100%; height: auto; aspect-ratio: 3 / 2;
object-fit: cover; }
figcaption { padding: .6rem .9rem; font-size: .95rem; }
figure:hover img { transform: scale(1.03); }
img { transition: transform .3s; }
```

Project 124 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - Gallery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Ismailia Cycling Store gallery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure><img src="images/cycling-1.jpg" alt="City bike" width="600"...	An image; alt describes it, width and height reserve space before it loads.
<figure><img src="images/cycling-2.jpg" alt="Mountain bike" width="...	Self-contained media with an optional caption.
<figure><img src="images/cycling-3.jpg" alt="Kids bike" width="600"...	Caption for the figure.

Line	What it does
<figure><img src="images/cycling-4.jpg" alt="Tune-up" width="600" h...	Defers loading until the image is near the viewport.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fill, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 12px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
font-size: .95rem;	Size of the text.
figure:hover img {	Applies while the pointer is over the element.
transform: scale(1.03);	Enlarges or shrinks the element visually.
transition: transform .3s;	Animates property changes smoothly, for example on hover.

Check your work

- All images have meaningful alt
- No layout jump while loading
- Grid reflows on narrow screens
- Zoom does not overflow the card

Exercises

1. Make the first image span two columns with grid-column: span 2.
2. Add a lightbox using <dialog>.
3. Use <picture> to serve WebP.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 125: Photo gallery for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 1 | Files: index.html, styles.css

Brief

Lay out four captioned photos in a responsive grid using figure and figcaption, with lazy loading and a gentle hover zoom.

Learning goals

- Use figure/figcaption for captioned images
- Reserve space with width, height and aspect-ratio
- Crop images consistently with object-fit

Elements and CSS used

HTML elements	CSS features
figure, img, figcaption, div, h1	grid-template-columns, auto-fill, aspect-ratio, object-fit, overflow: hidden, transition, transform

Build guide

1. Create an images folder with four photos (any JPEGs, renamed).
2. Write one <figure> per photo with img and figcaption.
3. Give every img alt text, width, height and loading="lazy".
4. Make .gallery a grid with auto-fill columns.
5. Force a 3:2 shape with aspect-ratio and object-fit: cover.
6. Add the hover zoom with transition and transform.

Project 125: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - Gallery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Minya Coding Club gallery</h1>
    <div class="gallery">
      <figure><img src="images/coding-1.jpg" alt="HTML weekend"
width="600" height="400" loading="lazy"><figcaption>HTML weekend</
figcaption></figure>
      <figure><img src="images/coding-2.jpg" alt="CSS art"
width="600" height="400" loading="lazy"><figcaption>CSS art</
figcaption></figure>
      <figure><img src="images/coding-3.jpg" alt="Scratch games"
width="600" height="400" loading="lazy"><figcaption>Scratch games</
figcaption></figure>
      <figure><img src="images/coding-4.jpg" alt="Hackathon"
width="600" height="400" loading="lazy"><figcaption>Hackathon</
figcaption></figure>
    </div>
  </main>
</body>
</html>
```

Project 125: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; }
.gallery { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fill, minmax(16rem, 1fr)); }
figure { margin: 0; background: var(--accent); border-radius: 12px;
overflow: hidden; }
img { display: block; width: 100%; height: auto; aspect-ratio: 3 / 2;
object-fit: cover; }
figcaption { padding: .6rem .9rem; font-size: .95rem; }
figure:hover img { transform: scale(1.03); }
img { transition: transform .3s; }
```

Project 125 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - Gallery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Minya Coding Club gallery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure><img src="images/coding-1.jpg" alt="HTML weekend" width="60...	An image; alt describes it, width and height reserve space before it loads.
<figure><img src="images/coding-2.jpg" alt="CSS art" width="600" he...	Self-contained media with an optional caption.

Line	What it does
<figure><img src="images/coding-3.jpg" alt="Scratch games" width="6...	Caption for the figure.
<figure><img src="images/coding-4.jpg" alt="Hackathon" width="600" ...	Defers loading until the image is near the viewport.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 12px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
font-size: .95rem;	Size of the text.
figure:hover img {	Applies while the pointer is over the element.
transform: scale(1.03);	Enlarges or shrinks the element visually.
transition: transform .3s;	Animates property changes smoothly, for example on hover.

Check your work

- All images have meaningful alt
- No layout jump while loading

- Grid reflows on narrow screens
- Zoom does not overflow the card

Exercises

1. Make the first image span two columns with grid-column: span 2.
2. Add a lightbox using <dialog>.
3. Use <picture> to serve WebP.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: About page

Level 1 | 25 projects, one per theme

Write a readable long-form page: lead paragraph, image, headings, a value list with strong keywords and a quotation with attribution.

Project 126: About page for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 1 | Files: index.html, styles.css

Brief

Write a readable long-form page: lead paragraph, image, headings, a value list with strong keywords and a quotation with attribution.

Learning goals

- Choose text elements by meaning (strong, cite, blockquote)
- Set comfortable reading width and line length
- Mix a serif body with sans-serif headings

Elements and CSS used

HTML elements	CSS features
article, h1, h2, p, img, ul, li, strong, blockquote, footer, cite	max-width, font-family, font-size, border-left, font-style

Build guide

1. Write the article content first, without any CSS.
2. Add the image with alt text and dimensions.
3. Mark values with at the start of each list item.
4. Add the quotation with <blockquote>, a <footer> and <cite>.
5. Limit the width to 42rem and set fonts.
6. Style the blockquote with a coloured left border.

Project 126: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>About Cairo Book Shop</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="about">
    <article>
      <h1>About Cairo Book Shop</h1>
      <p class="lead">PDF and printed books about web development, in
the heart of Giza.</p>
      <img src="images/team.jpg" alt="Mohamed Khattab in front of
Cairo Book Shop" width="800" height="500">
      <h2>Our story</h2>
      <p>Cairo Book Shop was founded by <strong>Mohamed Khattab</
strong> with one idea: do a few things and do them well. Today our
small team offers 4 core books and welcomes visitors from all over
Giza.</p>
      <h2>What we value</h2>
      <ul>
        <li><strong>Quality.</strong> Every book is checked twice.</
li>
        <li><strong>Honesty.</strong> Clear prices, no surprises.</li>
        <li><strong>Community.</strong> We support local schools and
clubs.</li>
      </ul>
      <blockquote>
        <p>We treat every visitor like a neighbour, because they
usually are.</p>
        <footer>&mdash; <cite>Mohamed Khattab</cite></footer>
      </blockquote>
    </article>
  </main>
</body>
</html>
```

Project 126: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.about { max-width: 42rem; margin: 2rem auto; padding: 0 1rem; font-
```

```
family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; color: var(--brand); }
.lead { font-size: 1.3rem; color: var(--muted); }
img { max-width: 100%; height: auto; border-radius: 12px; }
li { margin-bottom: .5rem; }
blockquote { margin: 2rem 0; padding: 1rem 1.5rem; border-left: 5px
solid var(--brand); background: var(--accent); }
blockquote p { margin: 0 0 .5rem; font-style: italic; }
```

Project 126 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>About Cairo Book Shop</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="about">	The unique content of this page; exactly one per page.
<article>	A self-contained piece: card, post, product.
About Cairo Book Shop	The main heading; only one per page.
<p class="lead">PDF and printed books about web development, in the...	A paragraph of text.
<img src="images/team.jpg" alt="Mohamed Khattab in front of Cairo B...	An image; alt describes it, width and height reserve space before it loads.
Our story	Second-level heading for a section.

Line	What it does
<p>Cairo Book Shop was founded by Mohamed Khattab ...	Strong importance (bold by default).
	Unordered (bulleted) list.
Quality. Every book is checked twice.	One list item.
<blockquote>	A long quotation from another source.
<footer>— <cite>Mohamed Khattab</cite></footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 42rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.
max-width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
border-left: 5px solid var(--brand);	A thick left border used as an accent stripe.
background: var(--accent);	Background colour or image.

Check your work

- Heading order h1 then h2
- Body line length under 75 characters
- Image responsive
- Quote source in cite

Exercises

1. Add a <details> element with 'Opening hours'.
2. Add a timeline as an ordered list.
3. Add a second column with an <aside> on wide screens.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development

Field	Value
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 127: About page for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 1 | Files: index.html, styles.css

Brief

Write a readable long-form page: lead paragraph, image, headings, a value list with strong keywords and a quotation with attribution.

Learning goals

- Choose text elements by meaning (strong, cite, blockquote)
- Set comfortable reading width and line length
- Mix a serif body with sans-serif headings

Elements and CSS used

HTML elements	CSS features
article, h1, h2, p, img, ul, li, strong, blockquote, footer, cite	max-width, font-family, font-size, border-left, font-style

Build guide

1. Write the article content first, without any CSS.
2. Add the image with alt text and dimensions.
3. Mark values with at the start of each list item.
4. Add the quotation with <blockquote>, a <footer> and <cite>.
5. Limit the width to 42rem and set fonts.
6. Style the blockquote with a coloured left border.

Project 127: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>About Nile Bakery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="about">
    <article>
      <h1>About Nile Bakery</h1>
      <p class="lead">Fresh bread and pastries every morning, in the
heart of Cairo.</p>
      <img src="images/team.jpg" alt="Sara Adel in front of Nile
Bakery" width="800" height="500">
      <h2>Our story</h2>
      <p>Nile Bakery was founded by <strong>Sara Adel</strong> with
one idea: do a few things and do them well. Today our small team
offers 4 core pastries and welcomes visitors from all over Cairo.</p>
      <h2>What we value</h2>
      <ul>
        <li><strong>Quality.</strong> Every pastry is checked twice.</
li>
        <li><strong>Honesty.</strong> Clear prices, no surprises.</li>
        <li><strong>Community.</strong> We support local schools and
clubs.</li>
      </ul>
      <blockquote>
        <p>We treat every visitor like a neighbour, because they
usually are.</p>
        <footer>&mdash; <cite>Sara Adel</cite></footer>
      </blockquote>
    </article>
  </main>
</body>
</html>
```

Project 127: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.about { max-width: 42rem; margin: 2rem auto; padding: 0 1rem; font-
family: Georgia, serif; font-size: 1.1rem; }
```

```
h1, h2 { font-family: system-ui, sans-serif; color: var(--brand); }
.lead { font-size: 1.3rem; color: var(--muted); }
img { max-width: 100%; height: auto; border-radius: 12px; }
li { margin-bottom: .5rem; }
blockquote { margin: 2rem 0; padding: 1rem 1.5rem; border-left: 5px
solid var(--brand); background: var(--accent); }
blockquote p { margin: 0 0 .5rem; font-style: italic; }
```

Project 127 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>About Nile Bakery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="about">	The unique content of this page; exactly one per page.
<article>	A self-contained piece: card, post, product.
About Nile Bakery	The main heading; only one per page.
<p class="lead">Fresh bread and pastries every morning, in the hear...	A paragraph of text.
<img src="images/team.jpg" alt="Sara Adel in front of Nile Bakery" ...	An image; alt describes it, width and height reserve space before it loads.
Our story	Second-level heading for a section.
<p>Nile Bakery was founded by Sara Adel with one i...	Strong importance (bold by default).
	Unordered (bulleted) list.

Line	What it does
Quality. Every pastry is checked twice.	One list item.
<blockquote>	A long quotation from another source.
<footer>— <cite>Sara Adel</cite></footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 42rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.

Declaration	What it does
max-width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
border-left: 5px solid var(--brand);	A thick left border used as an accent stripe.
background: var(--accent);	Background colour or image.

Check your work

- Heading order h1 then h2
- Body line length under 75 characters
- Image responsive
- Quote source in cite

Exercises

1. Add a <details> element with 'Opening hours'.
2. Add a timeline as an ordered list.
3. Add a second column with an <aside> on wide screens.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec

Field	Value
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 128: About page for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 1 | Files: index.html, styles.css

Brief

Write a readable long-form page: lead paragraph, image, headings, a value list with strong keywords and a quotation with attribution.

Learning goals

- Choose text elements by meaning (strong, cite, blockquote)
- Set comfortable reading width and line length
- Mix a serif body with sans-serif headings

Elements and CSS used

HTML elements	CSS features
article, h1, h2, p, img, ul, li, strong, blockquote, footer, cite	max-width, font-family, font-size, border-left, font-style

Build guide

1. Write the article content first, without any CSS.
2. Add the image with alt text and dimensions.
3. Mark values with at the start of each list item.
4. Add the quotation with <blockquote>, a <footer> and <cite>.
5. Limit the width to 42rem and set fonts.
6. Style the blockquote with a coloured left border.

Project 128: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>About Pyramid Fitness</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="about">
    <article>
      <h1>About Pyramid Fitness</h1>
      <p class="lead">Train smarter, feel stronger, in the heart of
6th of October.</p>
      <img src="images/team.jpg" alt="Omar Farouk in front of Pyramid
Fitness" width="800" height="500">
      <h2>Our story</h2>
      <p>Pyramid Fitness was founded by <strong>Omar Farouk</strong>
with one idea: do a few things and do them well. Today our small team
offers 4 core classes and welcomes visitors from all over 6th of
October.</p>
      <h2>What we value</h2>
      <ul>
        <li><strong>Quality.</strong> Every class is checked twice.</
li>
        <li><strong>Honesty.</strong> Clear prices, no surprises.</li>
        <li><strong>Community.</strong> We support local schools and
clubs.</li>
      </ul>
      <blockquote>
        <p>We treat every visitor like a neighbour, because they
usually are.</p>
        <footer>&mdash; <cite>Omar Farouk</cite></footer>
      </blockquote>
    </article>
  </main>
</body>
</html>
```

Project 128: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.about { max-width: 42rem; margin: 2rem auto; padding: 0 1rem; font-
```

```
family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; color: var(--brand); }
.lead { font-size: 1.3rem; color: var(--muted); }
img { max-width: 100%; height: auto; border-radius: 12px; }
li { margin-bottom: .5rem; }
blockquote { margin: 2rem 0; padding: 1rem 1.5rem; border-left: 5px
solid var(--brand); background: var(--accent); }
blockquote p { margin: 0 0 .5rem; font-style: italic; }
```

Project 128 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>About Pyramid Fitness</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="about">	The unique content of this page; exactly one per page.
<article>	A self-contained piece: card, post, product.
About Pyramid Fitness	The main heading; only one per page.
<p class="lead">Train smarter, feel stronger, in the heart of 6th o...	A paragraph of text.
<img src="images/team.jpg" alt="Omar Farouk in front of Pyramid Fit...	An image; alt describes it, width and height reserve space before it loads.
Our story	Second-level heading for a section.
<p>Pyramid Fitness was founded by Omar Farouk with...	Strong importance (bold by default).

Line	What it does
	Unordered (bulleted) list.
Quality. Every class is checked twice.	One list item.
<blockquote>	A long quotation from another source.
<footer>— <cite>Omar Farouk</cite></footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 42rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
font-size: 1.1rem;	Size of the text.
max-width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
border-left: 5px solid var(--brand);	A thick left border used as an accent stripe.
background: var(--accent);	Background colour or image.

Check your work

- Heading order h1 then h2
- Body line length under 75 characters
- Image responsive
- Quote source in cite

Exercises

1. Add a <details> element with 'Opening hours'.
2. Add a timeline as an ordered list.
3. Add a second column with an <aside> on wide screens.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5

Field	Value
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 129: About page for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 1 | Files: index.html, styles.css

Brief

Write a readable long-form page: lead paragraph, image, headings, a value list with strong keywords and a quotation with attribution.

Learning goals

- Choose text elements by meaning (strong, cite, blockquote)
- Set comfortable reading width and line length
- Mix a serif body with sans-serif headings

Elements and CSS used

HTML elements	CSS features
article, h1, h2, p, img, ul, li, strong, blockquote, footer, cite	max-width, font-family, font-size, border-left, font-style

Build guide

1. Write the article content first, without any CSS.
2. Add the image with alt text and dimensions.
3. Mark values with at the start of each list item.
4. Add the quotation with <blockquote>, a <footer> and <cite>.
5. Limit the width to 42rem and set fonts.
6. Style the blockquote with a coloured left border.

Project 129: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>About Delta Dental Clinic</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="about">
    <article>
      <h1>About Delta Dental Clinic</h1>
      <p class="lead">Gentle care for the whole family, in the heart
of Mansoura.</p>
      <img src="images/team.jpg" alt="Dr. Hana Youssef in front of
Delta Dental Clinic" width="800" height="500">
      <h2>Our story</h2>
      <p>Delta Dental Clinic was founded by <strong>Dr. Hana Youssef</
strong> with one idea: do a few things and do them well. Today our
small team offers 4 core services and welcomes visitors from all over
Mansoura.</p>
      <h2>What we value</h2>
      <ul>
        <li><strong>Quality.</strong> Every service is checked twice.
</li>
        <li><strong>Honesty.</strong> Clear prices, no surprises.</li>
        <li><strong>Community.</strong> We support local schools and
clubs.</li>
      </ul>
      <blockquote>
        <p>We treat every visitor like a neighbour, because they
usually are.</p>
        <footer>&mdash; <cite>Dr. Hana Youssef</cite></footer>
      </blockquote>
    </article>
  </main>
</body>
</html>
```

Project 129: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.about { max-width: 42rem; margin: 2rem auto; padding: 0 1rem; font-
```

```
family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; color: var(--brand); }
.lead { font-size: 1.3rem; color: var(--muted); }
img { max-width: 100%; height: auto; border-radius: 12px; }
li { margin-bottom: .5rem; }
blockquote { margin: 2rem 0; padding: 1rem 1.5rem; border-left: 5px
solid var(--brand); background: var(--accent); }
blockquote p { margin: 0 0 .5rem; font-style: italic; }
```

Project 129 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>About Delta Dental Clinic</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="about">	The unique content of this page; exactly one per page.
<article>	A self-contained piece: card, post, product.
About Delta Dental Clinic	The main heading; only one per page.
<p class="lead">Gentle care for the whole family, in the heart of M...	A paragraph of text.
<img src="images/team.jpg" alt="Dr. Hana Youssef in front of Delta ...	An image; alt describes it, width and height reserve space before it loads.
Our story	Second-level heading for a section.
<p>Delta Dental Clinic was founded by Dr. Hana Youssef</str...	Strong importance (bold by default).

Line	What it does
	Unordered (bulleted) list.
Quality. Every service is checked twice.	One list item.
<blockquote>	A long quotation from another source.
<footer>— <cite>Dr. Hana Youssef</cite></footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 42rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
font-size: 1.1rem;	Size of the text.
max-width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
border-left: 5px solid var(--brand);	A thick left border used as an accent stripe.
background: var(--accent);	Background colour or image.

Check your work

- Heading order h1 then h2
- Body line length under 75 characters
- Image responsive
- Quote source in cite

Exercises

1. Add a <details> element with 'Opening hours'.
2. Add a timeline as an ordered list.
3. Add a second column with an <aside> on wide screens.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff

Field	Value
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 130: About page for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 1 | Files: index.html, styles.css

Brief

Write a readable long-form page: lead paragraph, image, headings, a value list with strong keywords and a quotation with attribution.

Learning goals

- Choose text elements by meaning (strong, cite, blockquote)
- Set comfortable reading width and line length
- Mix a serif body with sans-serif headings

Elements and CSS used

HTML elements	CSS features
article, h1, h2, p, img, ul, li, strong, blockquote, footer, cite	max-width, font-family, font-size, border-left, font-style

Build guide

1. Write the article content first, without any CSS.
2. Add the image with alt text and dimensions.
3. Mark values with at the start of each list item.
4. Add the quotation with <blockquote>, a <footer> and <cite>.
5. Limit the width to 42rem and set fonts.
6. Style the blockquote with a coloured left border.

Project 130: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>About Red Sea Travel</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="about">
    <article>
      <h1>About Red Sea Travel</h1>
      <p class="lead">Discover Egypt from desert to reef, in the
heart of Hurghada.</p>
      <img src="images/team.jpg" alt="Laila Mansour in front of Red
Sea Travel" width="800" height="500">
      <h2>Our story</h2>
      <p>Red Sea Travel was founded by <strong>Laila Mansour</strong>
with one idea: do a few things and do them well. Today our small team
offers 4 core tours and welcomes visitors from all over Hurghada.</p>
      <h2>What we value</h2>
      <ul>
        <li><strong>Quality.</strong> Every tour is checked twice.</
li>
        <li><strong>Honesty.</strong> Clear prices, no surprises.</li>
        <li><strong>Community.</strong> We support local schools and
clubs.</li>
      </ul>
      <blockquote>
        <p>We treat every visitor like a neighbour, because they
usually are.</p>
        <footer>&mdash; <cite>Laila Mansour</cite></footer>
      </blockquote>
    </article>
  </main>
</body>
</html>
```

Project 130: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.about { max-width: 42rem; margin: 2rem auto; padding: 0 1rem; font-
family: Georgia, serif; font-size: 1.1rem; }
```

```
h1, h2 { font-family: system-ui, sans-serif; color: var(--brand); }
.lead { font-size: 1.3rem; color: var(--muted); }
img { max-width: 100%; height: auto; border-radius: 12px; }
li { margin-bottom: .5rem; }
blockquote { margin: 2rem 0; padding: 1rem 1.5rem; border-left: 5px
solid var(--brand); background: var(--accent); }
blockquote p { margin: 0 0 .5rem; font-style: italic; }
```

Project 130 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>About Red Sea Travel</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="about">	The unique content of this page; exactly one per page.
<article>	A self-contained piece: card, post, product.
About Red Sea Travel	The main heading; only one per page.
<p class="lead">Discover Egypt from desert to reef, in the heart of...	A paragraph of text.
<img src="images/team.jpg" alt="Laila Mansour in front of Red Sea T...	An image; alt describes it, width and height reserve space before it loads.
Our story	Second-level heading for a section.
<p>Red Sea Travel was founded by Laila Mansour wit...	Strong importance (bold by default).

Line	What it does
	Unordered (bulleted) list.
Quality. Every tour is checked twice.	One list item.
<blockquote>	A long quotation from another source.
<footer>— <cite>Laila Mansour</cite></footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 42rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
font-size: 1.1rem;	Size of the text.
max-width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
border-left: 5px solid var(--brand);	A thick left border used as an accent stripe.
background: var(--accent);	Background colour or image.

Check your work

- Heading order h1 then h2
- Body line length under 75 characters
- Image responsive
- Quote source in cite

Exercises

1. Add a <details> element with 'Opening hours'.
2. Add a timeline as an ordered list.
3. Add a second column with an <aside> on wide screens.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff

Field	Value
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 131: About page for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Write a readable long-form page: lead paragraph, image, headings, a value list with strong keywords and a quotation with attribution.

Learning goals

- Choose text elements by meaning (strong, cite, blockquote)
- Set comfortable reading width and line length
- Mix a serif body with sans-serif headings

Elements and CSS used

HTML elements	CSS features
article, h1, h2, p, img, ul, li, strong, blockquote, footer, cite	max-width, font-family, font-size, border-left, font-style

Build guide

1. Write the article content first, without any CSS.
2. Add the image with alt text and dimensions.
3. Mark values with at the start of each list item.
4. Add the quotation with <blockquote>, a <footer> and <cite>.
5. Limit the width to 42rem and set fonts.
6. Style the blockquote with a coloured left border.

Project 131: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>About Lotus Language School</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="about">
    <article>
      <h1>About Lotus Language School</h1>
      <p class="lead">Learn English, French and German in small
groups, in the heart of Alexandria.</p>
      <img src="images/team.jpg" alt="Nour El Din in front of Lotus
Language School" width="800" height="500">
      <h2>Our story</h2>
      <p>Lotus Language School was founded by <strong>Nour El Din</
strong> with one idea: do a few things and do them well. Today our
small team offers 4 core courses and welcomes visitors from all over
Alexandria.</p>
      <h2>What we value</h2>
      <ul>
        <li><strong>Quality.</strong> Every course is checked twice.</
li>
        <li><strong>Honesty.</strong> Clear prices, no surprises.</li>
        <li><strong>Community.</strong> We support local schools and
clubs.</li>
      </ul>
      <blockquote>
        <p>We treat every visitor like a neighbour, because they
usually are.</p>
        <footer>&mdash; <cite>Nour El Din</cite></footer>
      </blockquote>
    </article>
  </main>
</body>
</html>
```

Project 131: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.about { max-width: 42rem; margin: 2rem auto; padding: 0 1rem; font-
```

```
family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; color: var(--brand); }
.lead { font-size: 1.3rem; color: var(--muted); }
img { max-width: 100%; height: auto; border-radius: 12px; }
li { margin-bottom: .5rem; }
blockquote { margin: 2rem 0; padding: 1rem 1.5rem; border-left: 5px
solid var(--brand); background: var(--accent); }
blockquote p { margin: 0 0 .5rem; font-style: italic; }
```

Project 131 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>About Lotus Language School</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="about">	The unique content of this page; exactly one per page.
<article>	A self-contained piece: card, post, product.
About Lotus Language School	The main heading; only one per page.
<p class="lead">Learn English, French and German in small groups, i...	A paragraph of text.
<img src="images/team.jpg" alt="Nour El Din in front of Lotus Langu...	An image; alt describes it, width and height reserve space before it loads.
Our story	Second-level heading for a section.
<p>Lotus Language School was founded by Nour El Din</strong...	Strong importance (bold by default).

Line	What it does
	Unordered (bulleted) list.
Quality. Every course is checked twice.	One list item.
<blockquote>	A long quotation from another source.
<footer>— <cite>Nour El Din</cite></footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 42rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
font-size: 1.1rem;	Size of the text.
max-width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
border-left: 5px solid var(--brand);	A thick left border used as an accent stripe.
background: var(--accent);	Background colour or image.

Check your work

- Heading order h1 then h2
- Body line length under 75 characters
- Image responsive
- Quote source in cite

Exercises

1. Add a <details> element with 'Opening hours'.
2. Add a timeline as an ordered list.
3. Add a second column with an <aside> on wide screens.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff

Field	Value
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 132: About page for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 1 | Files: index.html, styles.css

Brief

Write a readable long-form page: lead paragraph, image, headings, a value list with strong keywords and a quotation with attribution.

Learning goals

- Choose text elements by meaning (strong, cite, blockquote)
- Set comfortable reading width and line length
- Mix a serif body with sans-serif headings

Elements and CSS used

HTML elements	CSS features
article, h1, h2, p, img, ul, li, strong, blockquote, footer, cite	max-width, font-family, font-size, border-left, font-style

Build guide

1. Write the article content first, without any CSS.
2. Add the image with alt text and dimensions.
3. Mark values with at the start of each list item.
4. Add the quotation with <blockquote>, a <footer> and <cite>.
5. Limit the width to 42rem and set fonts.
6. Style the blockquote with a coloured left border.

Project 132: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>About Green Leaf Cafe</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="about">
    <article>
      <h1>About Green Leaf Cafe</h1>
      <p class="lead">Specialty coffee and quiet corners, in the
heart of Zamalek.</p>
      <img src="images/team.jpg" alt="Karim Said in front of Green
Leaf Cafe" width="800" height="500">
      <h2>Our story</h2>
      <p>Green Leaf Cafe was founded by <strong>Karim Said</strong>
with one idea: do a few things and do them well. Today our small team
offers 4 core drinks and welcomes visitors from all over Zamalek.</p>
      <h2>What we value</h2>
      <ul>
        <li><strong>Quality.</strong> Every drink is checked twice.</
li>
        <li><strong>Honesty.</strong> Clear prices, no surprises.</li>
        <li><strong>Community.</strong> We support local schools and
clubs.</li>
      </ul>
      <blockquote>
        <p>We treat every visitor like a neighbour, because they
usually are.</p>
        <footer>&mdash; <cite>Karim Said</cite></footer>
      </blockquote>
    </article>
  </main>
</body>
</html>
```

Project 132: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.about { max-width: 42rem; margin: 2rem auto; padding: 0 1rem; font-
family: Georgia, serif; font-size: 1.1rem; }
```

```
h1, h2 { font-family: system-ui, sans-serif; color: var(--brand); }
.lead { font-size: 1.3rem; color: var(--muted); }
img { max-width: 100%; height: auto; border-radius: 12px; }
li { margin-bottom: .5rem; }
blockquote { margin: 2rem 0; padding: 1rem 1.5rem; border-left: 5px
solid var(--brand); background: var(--accent); }
blockquote p { margin: 0 0 .5rem; font-style: italic; }
```

Project 132 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>About Green Leaf Cafe</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="about">	The unique content of this page; exactly one per page.
<article>	A self-contained piece: card, post, product.
About Green Leaf Cafe	The main heading; only one per page.
<p class="lead">Specialty coffee and quiet corners, in the heart of...	A paragraph of text.
<img src="images/team.jpg" alt="Karim Said in front of Green Leaf C...	An image; alt describes it, width and height reserve space before it loads.
Our story	Second-level heading for a section.
<p>Green Leaf Cafe was founded by Karim Said with ...	Strong importance (bold by default).

Line	What it does
	Unordered (bulleted) list.
Quality. Every drink is checked twice.	One list item.
<blockquote>	A long quotation from another source.
<footer>— <cite>Karim Said</cite></footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 42rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
font-size: 1.1rem;	Size of the text.
max-width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
border-left: 5px solid var(--brand);	A thick left border used as an accent stripe.
background: var(--accent);	Background colour or image.

Check your work

- Heading order h1 then h2
- Body line length under 75 characters
- Image responsive
- Quote source in cite

Exercises

1. Add a <details> element with 'Opening hours'.
2. Add a timeline as an ordered list.
3. Add a second column with an <aside> on wide screens.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4

Field	Value
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 133: About page for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 1 | Files: index.html, styles.css

Brief

Write a readable long-form page: lead paragraph, image, headings, a value list with strong keywords and a quotation with attribution.

Learning goals

- Choose text elements by meaning (strong, cite, blockquote)
- Set comfortable reading width and line length
- Mix a serif body with sans-serif headings

Elements and CSS used

HTML elements	CSS features
article, h1, h2, p, img, ul, li, strong, blockquote, footer, cite	max-width, font-family, font-size, border-left, font-style

Build guide

1. Write the article content first, without any CSS.
2. Add the image with alt text and dimensions.
3. Mark values with at the start of each list item.
4. Add the quotation with <blockquote>, a <footer> and <cite>.
5. Limit the width to 42rem and set fonts.
6. Style the blockquote with a coloured left border.

Project 133: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>About Sinai Trekking Club</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="about">
    <article>
      <h1>About Sinai Trekking Club</h1>
      <p class="lead">Guided mountain walks for every level, in the
heart of Saint Catherine.</p>
      <img src="images/team.jpg" alt="Yara Hamdy in front of Sinai
Trekking Club" width="800" height="500">
      <h2>Our story</h2>
      <p>Sinai Trekking Club was founded by <strong>Yara Hamdy</
strong> with one idea: do a few things and do them well. Today our
small team offers 4 core hikes and welcomes visitors from all over
Saint Catherine.</p>
      <h2>What we value</h2>
      <ul>
        <li><strong>Quality.</strong> Every hike is checked twice.</
li>
        <li><strong>Honesty.</strong> Clear prices, no surprises.</li>
        <li><strong>Community.</strong> We support local schools and
clubs.</li>
      </ul>
      <blockquote>
        <p>We treat every visitor like a neighbour, because they
usually are.</p>
        <footer>&mdash; <cite>Yara Hamdy</cite></footer>
      </blockquote>
    </article>
  </main>
</body>
</html>
```

Project 133: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.about { max-width: 42rem; margin: 2rem auto; padding: 0 1rem; font-
```

```
family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; color: var(--brand); }
.lead { font-size: 1.3rem; color: var(--muted); }
img { max-width: 100%; height: auto; border-radius: 12px; }
li { margin-bottom: .5rem; }
blockquote { margin: 2rem 0; padding: 1rem 1.5rem; border-left: 5px
solid var(--brand); background: var(--accent); }
blockquote p { margin: 0 0 .5rem; font-style: italic; }
```

Project 133 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>About Sinai Trekking Club</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="about">	The unique content of this page; exactly one per page.
<article>	A self-contained piece: card, post, product.
About Sinai Trekking Club	The main heading; only one per page.
<p class="lead">Guided mountain walks for every level, in the heart...	A paragraph of text.
<img src="images/team.jpg" alt="Yara Hamdy in front of Sinai Trekki...	An image; alt describes it, width and height reserve space before it loads.
Our story	Second-level heading for a section.
<p>Sinai Trekking Club was founded by Yara Hamdy w...	Strong importance (bold by default).

Line	What it does
	Unordered (bulleted) list.
Quality. Every hike is checked twice.	One list item.
<blockquote>	A long quotation from another source.
<footer>— <cite>Yara Hamdy</cite></footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 42rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
font-size: 1.1rem;	Size of the text.
max-width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
border-left: 5px solid var(--brand);	A thick left border used as an accent stripe.
background: var(--accent);	Background colour or image.

Check your work

- Heading order h1 then h2
- Body line length under 75 characters
- Image responsive
- Quote source in cite

Exercises

1. Add a <details> element with 'Opening hours'.
2. Add a timeline as an ordered list.
3. Add a second column with an <aside> on wide screens.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb

Field	Value
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 134: About page for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 1 | Files: index.html, styles.css

Brief

Write a readable long-form page: lead paragraph, image, headings, a value list with strong keywords and a quotation with attribution.

Learning goals

- Choose text elements by meaning (strong, cite, blockquote)
- Set comfortable reading width and line length
- Mix a serif body with sans-serif headings

Elements and CSS used

HTML elements	CSS features
article, h1, h2, p, img, ul, li, strong, blockquote, footer, cite	max-width, font-family, font-size, border-left, font-style

Build guide

1. Write the article content first, without any CSS.
2. Add the image with alt text and dimensions.
3. Mark values with at the start of each list item.
4. Add the quotation with <blockquote>, a <footer> and <cite>.
5. Limit the width to 42rem and set fonts.
6. Style the blockquote with a coloured left border.

Project 134: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>About Horizon Photography</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="about">
    <article>
      <h1>About Horizon Photography</h1>
      <p class="lead">Portraits, weddings and product photography, in
the heart of Maadi.</p>
      <img src="images/team.jpg" alt="Adham Nabil in front of Horizon
Photography" width="800" height="500">
      <h2>Our story</h2>
      <p>Horizon Photography was founded by <strong>Adham Nabil</
strong> with one idea: do a few things and do them well. Today our
small team offers 4 core sessions and welcomes visitors from all over
Maadi.</p>
      <h2>What we value</h2>
      <ul>
        <li><strong>Quality.</strong> Every session is checked twice.
</li>
        <li><strong>Honesty.</strong> Clear prices, no surprises.</li>
        <li><strong>Community.</strong> We support local schools and
clubs.</li>
      </ul>
      <blockquote>
        <p>We treat every visitor like a neighbour, because they
usually are.</p>
        <footer>&mdash; <cite>Adham Nabil</cite></footer>
      </blockquote>
    </article>
  </main>
</body>
</html>
```

Project 134: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.about { max-width: 42rem; margin: 2rem auto; padding: 0 1rem; font-
```

```
family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; color: var(--brand); }
.lead { font-size: 1.3rem; color: var(--muted); }
img { max-width: 100%; height: auto; border-radius: 12px; }
li { margin-bottom: .5rem; }
blockquote { margin: 2rem 0; padding: 1rem 1.5rem; border-left: 5px
solid var(--brand); background: var(--accent); }
blockquote p { margin: 0 0 .5rem; font-style: italic; }
```

Project 134 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>About Horizon Photography</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="about">	The unique content of this page; exactly one per page.
<article>	A self-contained piece: card, post, product.
About Horizon Photography	The main heading; only one per page.
<p class="lead">Portraits, weddings and product photography, in the...	A paragraph of text.
<img src="images/team.jpg" alt="Adham Nabil in front of Horizon Pho...	An image; alt describes it, width and height reserve space before it loads.
Our story	Second-level heading for a section.
<p>Horizon Photography was founded by Adham Nabil ...	Strong importance (bold by default).

Line	What it does
	Unordered (bulleted) list.
Quality. Every session is checked twice.	One list item.
<blockquote>	A long quotation from another source.
<footer>— <cite>Adham Nabil</cite></footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 42rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
font-size: 1.1rem;	Size of the text.
max-width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
border-left: 5px solid var(--brand);	A thick left border used as an accent stripe.
background: var(--accent);	Background colour or image.

Check your work

- Heading order h1 then h2
- Body line length under 75 characters
- Image responsive
- Quote source in cite

Exercises

1. Add a <details> element with 'Opening hours'.
2. Add a timeline as an ordered list.
3. Add a second column with an <aside> on wide screens.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6

Field	Value
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 135: About page for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 1 | Files: index.html, styles.css

Brief

Write a readable long-form page: lead paragraph, image, headings, a value list with strong keywords and a quotation with attribution.

Learning goals

- Choose text elements by meaning (strong, cite, blockquote)
- Set comfortable reading width and line length
- Mix a serif body with sans-serif headings

Elements and CSS used

HTML elements	CSS features
article, h1, h2, p, img, ul, li, strong, blockquote, footer, cite	max-width, font-family, font-size, border-left, font-style

Build guide

1. Write the article content first, without any CSS.
2. Add the image with alt text and dimensions.
3. Mark values with at the start of each list item.
4. Add the quotation with <blockquote>, a <footer> and <cite>.
5. Limit the width to 42rem and set fonts.
6. Style the blockquote with a coloured left border.

Project 135: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>About Papyrus Stationery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="about">
    <article>
      <h1>About Papyrus Stationery</h1>
      <p class="lead">Notebooks, pens and paper made in Egypt, in the
heart of Heliopolis.</p>
      <img src="images/team.jpg" alt="Dina Fathy in front of Papyrus
Stationery" width="800" height="500">
      <h2>Our story</h2>
      <p>Papyrus Stationery was founded by <strong>Dina Fathy</
strong> with one idea: do a few things and do them well. Today our
small team offers 4 core products and welcomes visitors from all over
Heliopolis.</p>
      <h2>What we value</h2>
      <ul>
        <li><strong>Quality.</strong> Every product is checked twice.
</li>
        <li><strong>Honesty.</strong> Clear prices, no surprises.</li>
        <li><strong>Community.</strong> We support local schools and
clubs.</li>
      </ul>
      <blockquote>
        <p>We treat every visitor like a neighbour, because they
usually are.</p>
        <footer>&mdash; <cite>Dina Fathy</cite></footer>
      </blockquote>
    </article>
  </main>
</body>
</html>
```

Project 135: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.about { max-width: 42rem; margin: 2rem auto; padding: 0 1rem; font-
```

```
family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; color: var(--brand); }
.lead { font-size: 1.3rem; color: var(--muted); }
img { max-width: 100%; height: auto; border-radius: 12px; }
li { margin-bottom: .5rem; }
blockquote { margin: 2rem 0; padding: 1rem 1.5rem; border-left: 5px
solid var(--brand); background: var(--accent); }
blockquote p { margin: 0 0 .5rem; font-style: italic; }
```

Project 135 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>About Papyrus Stationery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="about">	The unique content of this page; exactly one per page.
<article>	A self-contained piece: card, post, product.
About Papyrus Stationery	The main heading; only one per page.
<p class="lead">Notebooks, pens and paper made in Egypt, in the hea...	A paragraph of text.
<img src="images/team.jpg" alt="Dina Fathy in front of Papyrus Stat...	An image; alt describes it, width and height reserve space before it loads.
Our story	Second-level heading for a section.
<p>Papyrus Stationery was founded by Dina Fathy wi...	Strong importance (bold by default).

Line	What it does
	Unordered (bulleted) list.
Quality. Every product is checked twice.	One list item.
<blockquote>	A long quotation from another source.
<footer>— <cite>Dina Fathy</cite></footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 42rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
font-size: 1.1rem;	Size of the text.
max-width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
border-left: 5px solid var(--brand);	A thick left border used as an accent stripe.
background: var(--accent);	Background colour or image.

Check your work

- Heading order h1 then h2
- Body line length under 75 characters
- Image responsive
- Quote source in cite

Exercises

1. Add a <details> element with 'Opening hours'.
2. Add a timeline as an ordered list.
3. Add a second column with an <aside> on wide screens.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8

Field	Value
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 136: About page for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 1 | Files: index.html, styles.css

Brief

Write a readable long-form page: lead paragraph, image, headings, a value list with strong keywords and a quotation with attribution.

Learning goals

- Choose text elements by meaning (strong, cite, blockquote)
- Set comfortable reading width and line length
- Mix a serif body with sans-serif headings

Elements and CSS used

HTML elements	CSS features
article, h1, h2, p, img, ul, li, strong, blockquote, footer, cite	max-width, font-family, font-size, border-left, font-style

Build guide

1. Write the article content first, without any CSS.
2. Add the image with alt text and dimensions.
3. Mark values with at the start of each list item.
4. Add the quotation with <blockquote>, a <footer> and <cite>.
5. Limit the width to 42rem and set fonts.
6. Style the blockquote with a coloured left border.

Project 136: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>About Oasis Plant Nursery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="about">
    <article>
      <h1>About Oasis Plant Nursery</h1>
      <p class="lead">Indoor plants and gardening advice, in the
heart of Sheikh Zayed.</p>
      <img src="images/team.jpg" alt="Hossam Ali in front of Oasis
Plant Nursery" width="800" height="500">
      <h2>Our story</h2>
      <p>Oasis Plant Nursery was founded by <strong>Hossam Ali</
strong> with one idea: do a few things and do them well. Today our
small team offers 4 core plants and welcomes visitors from all over
Sheikh Zayed.</p>
      <h2>What we value</h2>
      <ul>
        <li><strong>Quality.</strong> Every plant is checked twice.</
li>
        <li><strong>Honesty.</strong> Clear prices, no surprises.</li>
        <li><strong>Community.</strong> We support local schools and
clubs.</li>
      </ul>
      <blockquote>
        <p>We treat every visitor like a neighbour, because they
usually are.</p>
        <footer>&mdash; <cite>Hossam Ali</cite></footer>
      </blockquote>
    </article>
  </main>
</body>
</html>
```

Project 136: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.about { max-width: 42rem; margin: 2rem auto; padding: 0 1rem; font-
```

```
family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; color: var(--brand); }
.lead { font-size: 1.3rem; color: var(--muted); }
img { max-width: 100%; height: auto; border-radius: 12px; }
li { margin-bottom: .5rem; }
blockquote { margin: 2rem 0; padding: 1rem 1.5rem; border-left: 5px
solid var(--brand); background: var(--accent); }
blockquote p { margin: 0 0 .5rem; font-style: italic; }
```

Project 136 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>About Oasis Plant Nursery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="about">	The unique content of this page; exactly one per page.
<article>	A self-contained piece: card, post, product.
About Oasis Plant Nursery	The main heading; only one per page.
<p class="lead">Indoor plants and gardening advice, in the heart of...	A paragraph of text.
<img src="images/team.jpg" alt="Hossam Ali in front of Oasis Plant ...	An image; alt describes it, width and height reserve space before it loads.
Our story	Second-level heading for a section.
<p>Oasis Plant Nursery was founded by Hossam Ali w...	Strong importance (bold by default).

Line	What it does
	Unordered (bulleted) list.
Quality. Every plant is checked twice.	One list item.
<blockquote>	A long quotation from another source.
<footer>— <cite>Hossam Ali</cite></footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 42rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
font-size: 1.1rem;	Size of the text.
max-width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
border-left: 5px solid var(--brand);	A thick left border used as an accent stripe.
background: var(--accent);	Background colour or image.

Check your work

- Heading order h1 then h2
- Body line length under 75 characters
- Image responsive
- Quote source in cite

Exercises

1. Add a <details> element with 'Opening hours'.
2. Add a timeline as an ordered list.
3. Add a second column with an <aside> on wide screens.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7

Field	Value
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 137: About page for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 1 | Files: index.html, styles.css

Brief

Write a readable long-form page: lead paragraph, image, headings, a value list with strong keywords and a quotation with attribution.

Learning goals

- Choose text elements by meaning (strong, cite, blockquote)
- Set comfortable reading width and line length
- Mix a serif body with sans-serif headings

Elements and CSS used

HTML elements	CSS features
article, h1, h2, p, img, ul, li, strong, blockquote, footer, cite	max-width, font-family, font-size, border-left, font-style

Build guide

1. Write the article content first, without any CSS.
2. Add the image with alt text and dimensions.
3. Mark values with at the start of each list item.
4. Add the quotation with <blockquote>, a <footer> and <cite>.
5. Limit the width to 42rem and set fonts.
6. Style the blockquote with a coloured left border.

Project 137: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>About Cedar Furniture</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="about">
    <article>
      <h1>About Cedar Furniture</h1>
      <p class="lead">Solid wood furniture made to order, in the
heart of Damietta.</p>
      <img src="images/team.jpg" alt="Tarek Lotfy in front of Cedar
Furniture" width="800" height="500">
      <h2>Our story</h2>
      <p>Cedar Furniture was founded by <strong>Tarek Lotfy</strong>
with one idea: do a few things and do them well. Today our small team
offers 4 core pieces and welcomes visitors from all over Damietta.</p>
      <h2>What we value</h2>
      <ul>
        <li><strong>Quality.</strong> Every piece is checked twice.</
li>
        <li><strong>Honesty.</strong> Clear prices, no surprises.</li>
        <li><strong>Community.</strong> We support local schools and
clubs.</li>
      </ul>
      <blockquote>
        <p>We treat every visitor like a neighbour, because they
usually are.</p>
        <footer>&mdash; <cite>Tarek Lotfy</cite></footer>
      </blockquote>
    </article>
  </main>
</body>
</html>
```

Project 137: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.about { max-width: 42rem; margin: 2rem auto; padding: 0 1rem; font-
family: Georgia, serif; font-size: 1.1rem; }
```

```
h1, h2 { font-family: system-ui, sans-serif; color: var(--brand); }
.lead { font-size: 1.3rem; color: var(--muted); }
img { max-width: 100%; height: auto; border-radius: 12px; }
li { margin-bottom: .5rem; }
blockquote { margin: 2rem 0; padding: 1rem 1.5rem; border-left: 5px
solid var(--brand); background: var(--accent); }
blockquote p { margin: 0 0 .5rem; font-style: italic; }
```

Project 137 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>About Cedar Furniture</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="about">	The unique content of this page; exactly one per page.
<article>	A self-contained piece: card, post, product.
About Cedar Furniture	The main heading; only one per page.
<p class="lead">Solid wood furniture made to order, in the heart of...	A paragraph of text.
<img src="images/team.jpg" alt="Tarek Lotfy in front of Cedar Furni...	An image; alt describes it, width and height reserve space before it loads.
Our story	Second-level heading for a section.
<p>Cedar Furniture was founded by Tarek Lotfy with...	Strong importance (bold by default).

Line	What it does
	Unordered (bulleted) list.
Quality. Every piece is checked twice.	One list item.
<blockquote>	A long quotation from another source.
<footer>— <cite>Tarek Lotfy</cite></footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 42rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
font-size: 1.1rem;	Size of the text.
max-width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
border-left: 5px solid var(--brand);	A thick left border used as an accent stripe.
background: var(--accent);	Background colour or image.

Check your work

- Heading order h1 then h2
- Body line length under 75 characters
- Image responsive
- Quote source in cite

Exercises

1. Add a <details> element with 'Opening hours'.
2. Add a timeline as an ordered list.
3. Add a second column with an <aside> on wide screens.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7

Field	Value
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 138: About page for Byte Repair

Theme: Byte Repair (Nasr City) | Level 1 | Files: index.html, styles.css

Brief

Write a readable long-form page: lead paragraph, image, headings, a value list with strong keywords and a quotation with attribution.

Learning goals

- Choose text elements by meaning (strong, cite, blockquote)
- Set comfortable reading width and line length
- Mix a serif body with sans-serif headings

Elements and CSS used

HTML elements	CSS features
article, h1, h2, p, img, ul, li, strong, blockquote, footer, cite	max-width, font-family, font-size, border-left, font-style

Build guide

1. Write the article content first, without any CSS.
2. Add the image with alt text and dimensions.
3. Mark values with at the start of each list item.
4. Add the quotation with <blockquote>, a <footer> and <cite>.
5. Limit the width to 42rem and set fonts.
6. Style the blockquote with a coloured left border.

Project 138: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>About Byte Repair</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="about">
    <article>
      <h1>About Byte Repair</h1>
      <p class="lead">Phone and laptop repairs while you wait, in the
heart of Nasr City.</p>
      <img src="images/team.jpg" alt="Mostafa Gamal in front of Byte
Repair" width="800" height="500">
      <h2>Our story</h2>
      <p>Byte Repair was founded by <strong>Mostafa Gamal</strong>
with one idea: do a few things and do them well. Today our small team
offers 4 core repairs and welcomes visitors from all over Nasr City.</
p>
      <h2>What we value</h2>
      <ul>
        <li><strong>Quality.</strong> Every repair is checked twice.</
li>
        <li><strong>Honesty.</strong> Clear prices, no surprises.</li>
        <li><strong>Community.</strong> We support local schools and
clubs.</li>
      </ul>
      <blockquote>
        <p>We treat every visitor like a neighbour, because they
usually are.</p>
        <footer>&mdash; <cite>Mostafa Gamal</cite></footer>
      </blockquote>
    </article>
  </main>
</body>
</html>
```

Project 138: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.about { max-width: 42rem; margin: 2rem auto; padding: 0 1rem; font-
```

```
family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; color: var(--brand); }
.lead { font-size: 1.3rem; color: var(--muted); }
img { max-width: 100%; height: auto; border-radius: 12px; }
li { margin-bottom: .5rem; }
blockquote { margin: 2rem 0; padding: 1rem 1.5rem; border-left: 5px
solid var(--brand); background: var(--accent); }
blockquote p { margin: 0 0 .5rem; font-style: italic; }
```

Project 138 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>About Byte Repair</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="about">	The unique content of this page; exactly one per page.
<article>	A self-contained piece: card, post, product.
About Byte Repair	The main heading; only one per page.
<p class="lead">Phone and laptop repairs while you wait, in the hea...	A paragraph of text.
<img src="images/team.jpg" alt="Mostafa Gamal in front of Byte Repa...	An image; alt describes it, width and height reserve space before it loads.
Our story	Second-level heading for a section.
<p>Byte Repair was founded by Mostafa Gamal with o...	Strong importance (bold by default).
	Unordered (bulleted) list.

Line	What it does
Quality. Every repair is checked twice.	One list item.
<blockquote>	A long quotation from another source.
<footer>— <cite>Mostafa Gamal</cite></footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 42rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.

Declaration	What it does
max-width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
border-left: 5px solid var(--brand);	A thick left border used as an accent stripe.
background: var(--accent);	Background colour or image.

Check your work

- Heading order h1 then h2
- Body line length under 75 characters
- Image responsive
- Quote source in cite

Exercises

1. Add a <details> element with 'Opening hours'.
2. Add a timeline as an ordered list.
3. Add a second column with an <aside> on wide screens.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff

Field	Value
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 139: About page for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 1 | Files: index.html, styles.css

Brief

Write a readable long-form page: lead paragraph, image, headings, a value list with strong keywords and a quotation with attribution.

Learning goals

- Choose text elements by meaning (strong, cite, blockquote)
- Set comfortable reading width and line length
- Mix a serif body with sans-serif headings

Elements and CSS used

HTML elements	CSS features
article, h1, h2, p, img, ul, li, strong, blockquote, footer, cite	max-width, font-family, font-size, border-left, font-style

Build guide

1. Write the article content first, without any CSS.
2. Add the image with alt text and dimensions.
3. Mark values with at the start of each list item.
4. Add the quotation with <blockquote>, a <footer> and <cite>.
5. Limit the width to 42rem and set fonts.
6. Style the blockquote with a coloured left border.

Project 139: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>About Sahara Pet Care</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="about">
    <article>
      <h1>About Sahara Pet Care</h1>
      <p class="lead">Grooming, boarding and vet visits, in the heart
of New Cairo.</p>
      <img src="images/team.jpg" alt="Rana Ibrahim in front of Sahara
Pet Care" width="800" height="500">
      <h2>Our story</h2>
      <p>Sahara Pet Care was founded by <strong>Rana Ibrahim</strong>
with one idea: do a few things and do them well. Today our small team
offers 4 core services and welcomes visitors from all over New Cairo.
</p>
      <h2>What we value</h2>
      <ul>
        <li><strong>Quality.</strong> Every service is checked twice.
</li>
        <li><strong>Honesty.</strong> Clear prices, no surprises.</li>
        <li><strong>Community.</strong> We support local schools and
clubs.</li>
      </ul>
      <blockquote>
        <p>We treat every visitor like a neighbour, because they
usually are.</p>
        <footer>&mdash; <cite>Rana Ibrahim</cite></footer>
      </blockquote>
    </article>
  </main>
</body>
</html>
```

Project 139: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.about { max-width: 42rem; margin: 2rem auto; padding: 0 1rem; font-
```

```
family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; color: var(--brand); }
.lead { font-size: 1.3rem; color: var(--muted); }
img { max-width: 100%; height: auto; border-radius: 12px; }
li { margin-bottom: .5rem; }
blockquote { margin: 2rem 0; padding: 1rem 1.5rem; border-left: 5px
solid var(--brand); background: var(--accent); }
blockquote p { margin: 0 0 .5rem; font-style: italic; }
```

Project 139 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>About Sahara Pet Care</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="about">	The unique content of this page; exactly one per page.
<article>	A self-contained piece: card, post, product.
About Sahara Pet Care	The main heading; only one per page.
<p class="lead">Grooming, boarding and vet visits, in the heart of ...	A paragraph of text.
<img src="images/team.jpg" alt="Rana Ibrahim in front of Sahara Pet...	An image; alt describes it, width and height reserve space before it loads.
Our story	Second-level heading for a section.
<p>Sahara Pet Care was founded by Rana Ibrahim wit...	Strong importance (bold by default).

Line	What it does
	Unordered (bulleted) list.
Quality. Every service is checked twice.	One list item.
<blockquote>	A long quotation from another source.
<footer>— <cite>Rana Ibrahim</cite></footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 42rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
font-size: 1.1rem;	Size of the text.
max-width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
border-left: 5px solid var(--brand);	A thick left border used as an accent stripe.
background: var(--accent);	Background colour or image.

Check your work

- Heading order h1 then h2
- Body line length under 75 characters
- Image responsive
- Quote source in cite

Exercises

1. Add a <details> element with 'Opening hours'.
2. Add a timeline as an ordered list.
3. Add a second column with an <aside> on wide screens.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed

Field	Value
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 140: About page for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Write a readable long-form page: lead paragraph, image, headings, a value list with strong keywords and a quotation with attribution.

Learning goals

- Choose text elements by meaning (strong, cite, blockquote)
- Set comfortable reading width and line length
- Mix a serif body with sans-serif headings

Elements and CSS used

HTML elements	CSS features
article, h1, h2, p, img, ul, li, strong, blockquote, footer, cite	max-width, font-family, font-size, border-left, font-style

Build guide

1. Write the article content first, without any CSS.
2. Add the image with alt text and dimensions.
3. Mark values with at the start of each list item.
4. Add the quotation with <blockquote>, a <footer> and <cite>.
5. Limit the width to 42rem and set fonts.
6. Style the blockquote with a coloured left border.

Project 140: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>About Alexandria Sailing School</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="about">
    <article>
      <h1>About Alexandria Sailing School</h1>
      <p class="lead">Learn to sail on the Mediterranean, in the
heart of Alexandria.</p>
      <img src="images/team.jpg" alt="Amr Selim in front of
Alexandria Sailing School" width="800" height="500">
      <h2>Our story</h2>
      <p>Alexandria Sailing School was founded by <strong>Amr Selim</
strong> with one idea: do a few things and do them well. Today our
small team offers 4 core lessons and welcomes visitors from all over
Alexandria.</p>
      <h2>What we value</h2>
      <ul>
        <li><strong>Quality.</strong> Every lesson is checked twice.</
li>
        <li><strong>Honesty.</strong> Clear prices, no surprises.</li>
        <li><strong>Community.</strong> We support local schools and
clubs.</li>
      </ul>
      <blockquote>
        <p>We treat every visitor like a neighbour, because they
usually are.</p>
        <footer>&mdash; <cite>Amr Selim</cite></footer>
      </blockquote>
    </article>
  </main>
</body>
</html>
```

Project 140: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.about { max-width: 42rem; margin: 2rem auto; padding: 0 1rem; font-
```

```
family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; color: var(--brand); }
.lead { font-size: 1.3rem; color: var(--muted); }
img { max-width: 100%; height: auto; border-radius: 12px; }
li { margin-bottom: .5rem; }
blockquote { margin: 2rem 0; padding: 1rem 1.5rem; border-left: 5px
solid var(--brand); background: var(--accent); }
blockquote p { margin: 0 0 .5rem; font-style: italic; }
```

Project 140 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>About Alexandria Sailing School</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="about">	The unique content of this page; exactly one per page.
<article>	A self-contained piece: card, post, product.
About Alexandria Sailing School	The main heading; only one per page.
<p class="lead">Learn to sail on the Mediterranean, in the heart of...	A paragraph of text.
<img src="images/team.jpg" alt="Amr Selim in front of Alexandria Sa...	An image; alt describes it, width and height reserve space before it loads.
Our story	Second-level heading for a section.
<p>Alexandria Sailing School was founded by Amr Selim</stro...	Strong importance (bold by default).

Line	What it does
	Unordered (bulleted) list.
Quality. Every lesson is checked twice.	One list item.
<blockquote>	A long quotation from another source.
<footer>— <cite>Amr Selim</cite></footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 42rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
font-size: 1.1rem;	Size of the text.
max-width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
border-left: 5px solid var(--brand);	A thick left border used as an accent stripe.
background: var(--accent);	Background colour or image.

Check your work

- Heading order h1 then h2
- Body line length under 75 characters
- Image responsive
- Quote source in cite

Exercises

1. Add a <details> element with 'Opening hours'.
2. Add a timeline as an ordered list.
3. Add a second column with an <aside> on wide screens.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff

Field	Value
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 141: About page for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Write a readable long-form page: lead paragraph, image, headings, a value list with strong keywords and a quotation with attribution.

Learning goals

- Choose text elements by meaning (strong, cite, blockquote)
- Set comfortable reading width and line length
- Mix a serif body with sans-serif headings

Elements and CSS used

HTML elements	CSS features
article, h1, h2, p, img, ul, li, strong, blockquote, footer, cite	max-width, font-family, font-size, border-left, font-style

Build guide

1. Write the article content first, without any CSS.
2. Add the image with alt text and dimensions.
3. Mark values with at the start of each list item.
4. Add the quotation with <blockquote>, a <footer> and <cite>.
5. Limit the width to 42rem and set fonts.
6. Style the blockquote with a coloured left border.

Project 141: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>About Habiba Handmade Jewellery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="about">
    <article>
      <h1>About Habiba Handmade Jewellery</h1>
      <p class="lead">Silver and brass pieces inspired by Nubia, in
the heart of Aswan.</p>
      <img src="images/team.jpg" alt="Habiba Saleh in front of Habiba
Handmade Jewellery" width="800" height="500">
      <h2>Our story</h2>
      <p>Habiba Handmade Jewellery was founded by <strong>Habiba
Saleh</strong> with one idea: do a few things and do them well. Today
our small team offers 4 core items and welcomes visitors from all
over Aswan.</p>
      <h2>What we value</h2>
      <ul>
        <li><strong>Quality.</strong> Every item is checked twice.</
li>
        <li><strong>Honesty.</strong> Clear prices, no surprises.</li>
        <li><strong>Community.</strong> We support local schools and
clubs.</li>
      </ul>
      <blockquote>
        <p>We treat every visitor like a neighbour, because they
usually are.</p>
        <footer>&mdash; <cite>Habiba Saleh</cite></footer>
      </blockquote>
    </article>
  </main>
</body>
</html>
```

Project 141: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.about { max-width: 42rem; margin: 2rem auto; padding: 0 1rem; font-
```

```
family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; color: var(--brand); }
.lead { font-size: 1.3rem; color: var(--muted); }
img { max-width: 100%; height: auto; border-radius: 12px; }
li { margin-bottom: .5rem; }
blockquote { margin: 2rem 0; padding: 1rem 1.5rem; border-left: 5px
solid var(--brand); background: var(--accent); }
blockquote p { margin: 0 0 .5rem; font-style: italic; }
```

Project 141 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>About Habiba Handmade Jewellery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="about">	The unique content of this page; exactly one per page.
<article>	A self-contained piece: card, post, product.
About Habiba Handmade Jewellery	The main heading; only one per page.
<p class="lead">Silver and brass pieces inspired by Nubia, in the h...	A paragraph of text.
<img src="images/team.jpg" alt="Habiba Saleh in front of Habiba Han...	An image; alt describes it, width and height reserve space before it loads.
Our story	Second-level heading for a section.
<p>Habiba Handmade Jewellery was founded by Habiba Saleh</s...	Strong importance (bold by default).

Line	What it does
	Unordered (bulleted) list.
Quality. Every item is checked twice.	One list item.
<blockquote>	A long quotation from another source.
<footer>— <cite>Habiba Saleh</cite></footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 42rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
font-size: 1.1rem;	Size of the text.
max-width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
border-left: 5px solid var(--brand);	A thick left border used as an accent stripe.
background: var(--accent);	Background colour or image.

Check your work

- Heading order h1 then h2
- Body line length under 75 characters
- Image responsive
- Quote source in cite

Exercises

1. Add a <details> element with 'Opening hours'.
2. Add a timeline as an ordered list.
3. Add a second column with an <aside> on wide screens.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8

Field	Value
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 142: About page for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 1 | Files: index.html, styles.css

Brief

Write a readable long-form page: lead paragraph, image, headings, a value list with strong keywords and a quotation with attribution.

Learning goals

- Choose text elements by meaning (strong, cite, blockquote)
- Set comfortable reading width and line length
- Mix a serif body with sans-serif headings

Elements and CSS used

HTML elements	CSS features
article, h1, h2, p, img, ul, li, strong, blockquote, footer, cite	max-width, font-family, font-size, border-left, font-style

Build guide

1. Write the article content first, without any CSS.
2. Add the image with alt text and dimensions.
3. Mark values with at the start of each list item.
4. Add the quotation with <blockquote>, a <footer> and <cite>.
5. Limit the width to 42rem and set fonts.
6. Style the blockquote with a coloured left border.

Project 142: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>About Fayoum Pottery Studio</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="about">
    <article>
      <h1>About Fayoum Pottery Studio</h1>
      <p class="lead">Wheel throwing and glazing classes, in the
heart of Tunis Village.</p>
      <img src="images/team.jpg" alt="Ahmed Mahmoud in front of
Fayoum Pottery Studio" width="800" height="500">
      <h2>Our story</h2>
      <p>Fayoum Pottery Studio was founded by <strong>Ahmed Mahmoud</
strong> with one idea: do a few things and do them well. Today our
small team offers 4 core workshops and welcomes visitors from all
over Tunis Village.</p>
      <h2>What we value</h2>
      <ul>
        <li><strong>Quality.</strong> Every workshop is checked twice.
</li>
        <li><strong>Honesty.</strong> Clear prices, no surprises.</li>
        <li><strong>Community.</strong> We support local schools and
clubs.</li>
      </ul>
      <blockquote>
        <p>We treat every visitor like a neighbour, because they
usually are.</p>
        <footer>&mdash; <cite>Ahmed Mahmoud</cite></footer>
      </blockquote>
    </article>
  </main>
</body>
</html>
```

Project 142: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.about { max-width: 42rem; margin: 2rem auto; padding: 0 1rem; font-
```

```
family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; color: var(--brand); }
.lead { font-size: 1.3rem; color: var(--muted); }
img { max-width: 100%; height: auto; border-radius: 12px; }
li { margin-bottom: .5rem; }
blockquote { margin: 2rem 0; padding: 1rem 1.5rem; border-left: 5px
solid var(--brand); background: var(--accent); }
blockquote p { margin: 0 0 .5rem; font-style: italic; }
```

Project 142 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>About Fayoum Pottery Studio</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="about">	The unique content of this page; exactly one per page.
<article>	A self-contained piece: card, post, product.
About Fayoum Pottery Studio	The main heading; only one per page.
<p class="lead">Wheel throwing and glazing classes, in the heart of...	A paragraph of text.
<img src="images/team.jpg" alt="Ahmed Mahmoud in front of Fayoum Po...	An image; alt describes it, width and height reserve space before it loads.
Our story	Second-level heading for a section.

Line	What it does
<p>Fayoum Pottery Studio was founded by Ahmed Mahmoud</stro...	Strong importance (bold by default).
	Unordered (bulleted) list.
Quality. Every workshop is checked twice.	One list item.
<blockquote>	A long quotation from another source.
<footer>— <cite>Ahmed Mahmoud</cite></footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 42rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.
max-width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
border-left: 5px solid var(--brand);	A thick left border used as an accent stripe.
background: var(--accent);	Background colour or image.

Check your work

- Heading order h1 then h2
- Body line length under 75 characters
- Image responsive
- Quote source in cite

Exercises

1. Add a <details> element with 'Opening hours'.
2. Add a timeline as an ordered list.
3. Add a second column with an <aside> on wide screens.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes

Field	Value
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 143: About page for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 1 | Files: index.html, styles.css

Brief

Write a readable long-form page: lead paragraph, image, headings, a value list with strong keywords and a quotation with attribution.

Learning goals

- Choose text elements by meaning (strong, cite, blockquote)
- Set comfortable reading width and line length
- Mix a serif body with sans-serif headings

Elements and CSS used

HTML elements	CSS features
article, h1, h2, p, img, ul, li, strong, blockquote, footer, cite	max-width, font-family, font-size, border-left, font-style

Build guide

1. Write the article content first, without any CSS.
2. Add the image with alt text and dimensions.
3. Mark values with at the start of each list item.
4. Add the quotation with <blockquote>, a <footer> and <cite>.
5. Limit the width to 42rem and set fonts.
6. Style the blockquote with a coloured left border.

Project 143: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>About Cleopatra Beauty Salon</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="about">
    <article>
      <h1>About Cleopatra Beauty Salon</h1>
      <p class="lead">Hair, nails and skin care, in the heart of
Dokki.</p>
      <img src="images/team.jpg" alt="Mariam Adel in front of
Cleopatra Beauty Salon" width="800" height="500">
      <h2>Our story</h2>
      <p>Cleopatra Beauty Salon was founded by <strong>Mariam Adel</
strong> with one idea: do a few things and do them well. Today our
small team offers 4 core treatments and welcomes visitors from all
over Dokki.</p>
      <h2>What we value</h2>
      <ul>
        <li><strong>Quality.</strong> Every treatment is checked
twice.</li>
        <li><strong>Honesty.</strong> Clear prices, no surprises.</li>
        <li><strong>Community.</strong> We support local schools and
clubs.</li>
      </ul>
      <blockquote>
        <p>We treat every visitor like a neighbour, because they
usually are.</p>
        <footer>&mdash; <cite>Mariam Adel</cite></footer>
      </blockquote>
    </article>
  </main>
</body>
</html>
```

Project 143: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.about { max-width: 42rem; margin: 2rem auto; padding: 0 1rem; font-
```

```
family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; color: var(--brand); }
.lead { font-size: 1.3rem; color: var(--muted); }
img { max-width: 100%; height: auto; border-radius: 12px; }
li { margin-bottom: .5rem; }
blockquote { margin: 2rem 0; padding: 1rem 1.5rem; border-left: 5px
solid var(--brand); background: var(--accent); }
blockquote p { margin: 0 0 .5rem; font-style: italic; }
```

Project 143 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>About Cleopatra Beauty Salon</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="about">	The unique content of this page; exactly one per page.
<article>	A self-contained piece: card, post, product.
About Cleopatra Beauty Salon	The main heading; only one per page.
Hair, nails and skin care, in the heart of Dokki.	A paragraph of text.
<img src="images/team.jpg" alt="Mariam Adel in front of Cleopatra B...	An image; alt describes it, width and height reserve space before it loads.
Our story	Second-level heading for a section.

Line	What it does
<p>Cleopatra Beauty Salon was founded by Mariam Adel</stron...	Strong importance (bold by default).
	Unordered (bulleted) list.
Quality. Every treatment is checked twice.	One list item.
<blockquote>	A long quotation from another source.
<footer>— <cite>Mariam Adel</cite></footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 42rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.
max-width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
border-left: 5px solid var(--brand);	A thick left border used as an accent stripe.
background: var(--accent);	Background colour or image.

Check your work

- Heading order h1 then h2
- Body line length under 75 characters
- Image responsive
- Quote source in cite

Exercises

1. Add a <details> element with 'Opening hours'.
2. Add a timeline as an ordered list.
3. Add a second column with an <aside> on wide screens.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care

Field	Value
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 144: About page for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 1 | Files: index.html, styles.css

Brief

Write a readable long-form page: lead paragraph, image, headings, a value list with strong keywords and a quotation with attribution.

Learning goals

- Choose text elements by meaning (strong, cite, blockquote)
- Set comfortable reading width and line length
- Mix a serif body with sans-serif headings

Elements and CSS used

HTML elements	CSS features
article, h1, h2, p, img, ul, li, strong, blockquote, footer, cite	max-width, font-family, font-size, border-left, font-style

Build guide

1. Write the article content first, without any CSS.
2. Add the image with alt text and dimensions.
3. Mark values with at the start of each list item.
4. Add the quotation with <blockquote>, a <footer> and <cite>.
5. Limit the width to 42rem and set fonts.
6. Style the blockquote with a coloured left border.

Project 144: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>About Suez Auto Service</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="about">
    <article>
      <h1>About Suez Auto Service</h1>
      <p class="lead">Honest car servicing and repairs, in the heart
of Suez.</p>
      <img src="images/team.jpg" alt="Khaled Nasser in front of Suez
Auto Service" width="800" height="500">
      <h2>Our story</h2>
      <p>Suez Auto Service was founded by <strong>Khaled Nasser</
strong> with one idea: do a few things and do them well. Today our
small team offers 4 core services and welcomes visitors from all over
Suez.</p>
      <h2>What we value</h2>
      <ul>
        <li><strong>Quality.</strong> Every service is checked twice.
</li>
        <li><strong>Honesty.</strong> Clear prices, no surprises.</li>
        <li><strong>Community.</strong> We support local schools and
clubs.</li>
      </ul>
      <blockquote>
        <p>We treat every visitor like a neighbour, because they
usually are.</p>
        <footer>&mdash; <cite>Khaled Nasser</cite></footer>
      </blockquote>
    </article>
  </main>
</body>
</html>
```

Project 144: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.about { max-width: 42rem; margin: 2rem auto; padding: 0 1rem; font-
```

```
family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; color: var(--brand); }
.lead { font-size: 1.3rem; color: var(--muted); }
img { max-width: 100%; height: auto; border-radius: 12px; }
li { margin-bottom: .5rem; }
blockquote { margin: 2rem 0; padding: 1rem 1.5rem; border-left: 5px
solid var(--brand); background: var(--accent); }
blockquote p { margin: 0 0 .5rem; font-style: italic; }
```

Project 144 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>About Suez Auto Service</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="about">	The unique content of this page; exactly one per page.
<article>	A self-contained piece: card, post, product.
About Suez Auto Service	The main heading; only one per page.
<p class="lead">Honest car servicing and repairs, in the heart of S...	A paragraph of text.
<img src="images/team.jpg" alt="Khaled Nasser in front of Suez Auto...	An image; alt describes it, width and height reserve space before it loads.
Our story	Second-level heading for a section.
<p>Suez Auto Service was founded by Khaled Nasser ...	Strong importance (bold by default).

Line	What it does
	Unordered (bulleted) list.
Quality. Every service is checked twice.	One list item.
<blockquote>	A long quotation from another source.
<footer>— <cite>Khaled Nasser</cite></footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 42rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
font-size: 1.1rem;	Size of the text.
max-width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
border-left: 5px solid var(--brand);	A thick left border used as an accent stripe.
background: var(--accent);	Background colour or image.

Check your work

- Heading order h1 then h2
- Body line length under 75 characters
- Image responsive
- Quote source in cite

Exercises

1. Add a <details> element with 'Opening hours'.
2. Add a timeline as an ordered list.
3. Add a second column with an <aside> on wide screens.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb

Field	Value
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 145: About page for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 1 | Files: index.html, styles.css

Brief

Write a readable long-form page: lead paragraph, image, headings, a value list with strong keywords and a quotation with attribution.

Learning goals

- Choose text elements by meaning (strong, cite, blockquote)
- Set comfortable reading width and line length
- Mix a serif body with sans-serif headings

Elements and CSS used

HTML elements	CSS features
article, h1, h2, p, img, ul, li, strong, blockquote, footer, cite	max-width, font-family, font-size, border-left, font-style

Build guide

1. Write the article content first, without any CSS.
2. Add the image with alt text and dimensions.
3. Mark values with at the start of each list item.
4. Add the quotation with <blockquote>, a <footer> and <cite>.
5. Limit the width to 42rem and set fonts.
6. Style the blockquote with a coloured left border.

Project 145: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>About Luxor Music Academy</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="about">
    <article>
      <h1>About Luxor Music Academy</h1>
      <p class="lead">Oud, piano, guitar and voice lessons, in the
heart of Luxor.</p>
      <img src="images/team.jpg" alt="Salma Ragab in front of Luxor
Music Academy" width="800" height="500">
      <h2>Our story</h2>
      <p>Luxor Music Academy was founded by <strong>Salma Ragab</
strong> with one idea: do a few things and do them well. Today our
small team offers 4 core courses and welcomes visitors from all over
Luxor.</p>
      <h2>What we value</h2>
      <ul>
        <li><strong>Quality.</strong> Every course is checked twice.</
li>
        <li><strong>Honesty.</strong> Clear prices, no surprises.</li>
        <li><strong>Community.</strong> We support local schools and
clubs.</li>
      </ul>
      <blockquote>
        <p>We treat every visitor like a neighbour, because they
usually are.</p>
        <footer>&mdash; <cite>Salma Ragab</cite></footer>
      </blockquote>
    </article>
  </main>
</body>
</html>
```

Project 145: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.about { max-width: 42rem; margin: 2rem auto; padding: 0 1rem; font-
```

```
family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; color: var(--brand); }
.lead { font-size: 1.3rem; color: var(--muted); }
img { max-width: 100%; height: auto; border-radius: 12px; }
li { margin-bottom: .5rem; }
blockquote { margin: 2rem 0; padding: 1rem 1.5rem; border-left: 5px
solid var(--brand); background: var(--accent); }
blockquote p { margin: 0 0 .5rem; font-style: italic; }
```

Project 145 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>About Luxor Music Academy</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="about">	The unique content of this page; exactly one per page.
<article>	A self-contained piece: card, post, product.
About Luxor Music Academy	The main heading; only one per page.
<p class="lead">Oud, piano, guitar and voice lessons, in the heart ...	A paragraph of text.
<img src="images/team.jpg" alt="Salma Ragab in front of Luxor Music...	An image; alt describes it, width and height reserve space before it loads.
Our story	Second-level heading for a section.
<p>Luxor Music Academy was founded by Salma Ragab ...	Strong importance (bold by default).

Line	What it does
	Unordered (bulleted) list.
Quality. Every course is checked twice.	One list item.
<blockquote>	A long quotation from another source.
<footer>— <cite>Salma Ragab</cite></footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 42rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
font-size: 1.1rem;	Size of the text.
max-width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
border-left: 5px solid var(--brand);	A thick left border used as an accent stripe.
background: var(--accent);	Background colour or image.

Check your work

- Heading order h1 then h2
- Body line length under 75 characters
- Image responsive
- Quote source in cite

Exercises

1. Add a <details> element with 'Opening hours'.
2. Add a timeline as an ordered list.
3. Add a second column with an <aside> on wide screens.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff

Field	Value
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 146: About page for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 1 | Files: index.html, styles.css

Brief

Write a readable long-form page: lead paragraph, image, headings, a value list with strong keywords and a quotation with attribution.

Learning goals

- Choose text elements by meaning (strong, cite, blockquote)
- Set comfortable reading width and line length
- Mix a serif body with sans-serif headings

Elements and CSS used

HTML elements	CSS features
article, h1, h2, p, img, ul, li, strong, blockquote, footer, cite	max-width, font-family, font-size, border-left, font-style

Build guide

1. Write the article content first, without any CSS.
2. Add the image with alt text and dimensions.
3. Mark values with at the start of each list item.
4. Add the quotation with <blockquote>, a <footer> and <cite>.
5. Limit the width to 42rem and set fonts.
6. Style the blockquote with a coloured left border.

Project 146: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>About Port Said Seafood</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="about">
    <article>
      <h1>About Port Said Seafood</h1>
      <p class="lead">Grilled fish straight from the boats, in the
heart of Port Said.</p>
      <img src="images/team.jpg" alt="Sherif Wahba in front of Port
Said Seafood" width="800" height="500">
      <h2>Our story</h2>
      <p>Port Said Seafood was founded by <strong>Sherif Wahba</
strong> with one idea: do a few things and do them well. Today our
small team offers 4 core dishes and welcomes visitors from all over
Port Said.</p>
      <h2>What we value</h2>
      <ul>
        <li><strong>Quality.</strong> Every dish is checked twice.</
li>
        <li><strong>Honesty.</strong> Clear prices, no surprises.</li>
        <li><strong>Community.</strong> We support local schools and
clubs.</li>
      </ul>
      <blockquote>
        <p>We treat every visitor like a neighbour, because they
usually are.</p>
        <footer>&mdash; <cite>Sherif Wahba</cite></footer>
      </blockquote>
    </article>
  </main>
</body>
</html>
```

Project 146: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.about { max-width: 42rem; margin: 2rem auto; padding: 0 1rem; font-
```

```
family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; color: var(--brand); }
.lead { font-size: 1.3rem; color: var(--muted); }
img { max-width: 100%; height: auto; border-radius: 12px; }
li { margin-bottom: .5rem; }
blockquote { margin: 2rem 0; padding: 1rem 1.5rem; border-left: 5px
solid var(--brand); background: var(--accent); }
blockquote p { margin: 0 0 .5rem; font-style: italic; }
```

Project 146 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>About Port Said Seafood</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="about">	The unique content of this page; exactly one per page.
<article>	A self-contained piece: card, post, product.
About Port Said Seafood	The main heading; only one per page.
<p class="lead">Grilled fish straight from the boats, in the heart ...	A paragraph of text.
<img src="images/team.jpg" alt="Sherif Wahba in front of Port Said ...	An image; alt describes it, width and height reserve space before it loads.
Our story	Second-level heading for a section.
<p>Port Said Seafood was founded by Sherif Wahba w...	Strong importance (bold by default).

Line	What it does
	Unordered (bulleted) list.
Quality. Every dish is checked twice.	One list item.
<blockquote>	A long quotation from another source.
<footer>— <cite>Sherif Wahba</cite></footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 42rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
font-size: 1.1rem;	Size of the text.
max-width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
border-left: 5px solid var(--brand);	A thick left border used as an accent stripe.
background: var(--accent);	Background colour or image.

Check your work

- Heading order h1 then h2
- Body line length under 75 characters
- Image responsive
- Quote source in cite

Exercises

1. Add a <details> element with 'Opening hours'.
2. Add a timeline as an ordered list.
3. Add a second column with an <aside> on wide screens.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff

Field	Value
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 147: About page for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 1 | Files: index.html, styles.css

Brief

Write a readable long-form page: lead paragraph, image, headings, a value list with strong keywords and a quotation with attribution.

Learning goals

- Choose text elements by meaning (strong, cite, blockquote)
- Set comfortable reading width and line length
- Mix a serif body with sans-serif headings

Elements and CSS used

HTML elements	CSS features
article, h1, h2, p, img, ul, li, strong, blockquote, footer, cite	max-width, font-family, font-size, border-left, font-style

Build guide

1. Write the article content first, without any CSS.
2. Add the image with alt text and dimensions.
3. Mark values with at the start of each list item.
4. Add the quotation with <blockquote>, a <footer> and <cite>.
5. Limit the width to 42rem and set fonts.
6. Style the blockquote with a coloured left border.

Project 147: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>About Delta Kids Library</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="about">
    <article>
      <h1>About Delta Kids Library</h1>
      <p class="lead">Stories, reading clubs and homework help, in
the heart of Tanta.</p>
      <img src="images/team.jpg" alt="Ghada Kamel in front of Delta
Kids Library" width="800" height="500">
      <h2>Our story</h2>
      <p>Delta Kids Library was founded by <strong>Ghada Kamel</
strong> with one idea: do a few things and do them well. Today our
small team offers 4 core programmes and welcomes visitors from all
over Tanta.</p>
      <h2>What we value</h2>
      <ul>
        <li><strong>Quality.</strong> Every programme is checked
twice.</li>
        <li><strong>Honesty.</strong> Clear prices, no surprises.</li>
        <li><strong>Community.</strong> We support local schools and
clubs.</li>
      </ul>
      <blockquote>
        <p>We treat every visitor like a neighbour, because they
usually are.</p>
        <footer>&mdash; <cite>Ghada Kamel</cite></footer>
      </blockquote>
    </article>
  </main>
</body>
</html>
```

Project 147: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.about { max-width: 42rem; margin: 2rem auto; padding: 0 1rem; font-
```

```
family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; color: var(--brand); }
.lead { font-size: 1.3rem; color: var(--muted); }
img { max-width: 100%; height: auto; border-radius: 12px; }
li { margin-bottom: .5rem; }
blockquote { margin: 2rem 0; padding: 1rem 1.5rem; border-left: 5px
solid var(--brand); background: var(--accent); }
blockquote p { margin: 0 0 .5rem; font-style: italic; }
```

Project 147 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>About Delta Kids Library</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="about">	The unique content of this page; exactly one per page.
<article>	A self-contained piece: card, post, product.
About Delta Kids Library	The main heading; only one per page.
<p class="lead">Stories, reading clubs and homework help, in the he...	A paragraph of text.
<img src="images/team.jpg" alt="Ghada Kamel in front of Delta Kids ...	An image; alt describes it, width and height reserve space before it loads.
Our story	Second-level heading for a section.
<p>Delta Kids Library was founded by Ghada Kamel w...	Strong importance (bold by default).

Line	What it does
	Unordered (bulleted) list.
Quality. Every programme is checked twice.	One list item.
<blockquote>	A long quotation from another source.
<footer>— <cite>Ghada Kamel</cite></footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 42rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
font-size: 1.1rem;	Size of the text.
max-width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
border-left: 5px solid var(--brand);	A thick left border used as an accent stripe.
background: var(--accent);	Background colour or image.

Check your work

- Heading order h1 then h2
- Body line length under 75 characters
- Image responsive
- Quote source in cite

Exercises

1. Add a <details> element with 'Opening hours'.
2. Add a timeline as an ordered list.
3. Add a second column with an <aside> on wide screens.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed

Field	Value
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 148: About page for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Write a readable long-form page: lead paragraph, image, headings, a value list with strong keywords and a quotation with attribution.

Learning goals

- Choose text elements by meaning (strong, cite, blockquote)
- Set comfortable reading width and line length
- Mix a serif body with sans-serif headings

Elements and CSS used

HTML elements	CSS features
article, h1, h2, p, img, ul, li, strong, blockquote, footer, cite	max-width, font-family, font-size, border-left, font-style

Build guide

1. Write the article content first, without any CSS.
2. Add the image with alt text and dimensions.
3. Mark values with at the start of each list item.
4. Add the quotation with <blockquote>, a <footer> and <cite>.
5. Limit the width to 42rem and set fonts.
6. Style the blockquote with a coloured left border.

Project 148: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>About Nubian Guest House</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="about">
    <article>
      <h1>About Nubian Guest House</h1>
      <p class="lead">Colourful rooms on the west bank of the Nile,
in the heart of Aswan.</p>
      <img src="images/team.jpg" alt="Fatma Hassan in front of Nubian
Guest House" width="800" height="500">
      <h2>Our story</h2>
      <p>Nubian Guest House was founded by <strong>Fatma Hassan</
strong> with one idea: do a few things and do them well. Today our
small team offers 4 core rooms and welcomes visitors from all over
Aswan.</p>
      <h2>What we value</h2>
      <ul>
        <li><strong>Quality.</strong> Every room is checked twice.</
li>
        <li><strong>Honesty.</strong> Clear prices, no surprises.</li>
        <li><strong>Community.</strong> We support local schools and
clubs.</li>
      </ul>
      <blockquote>
        <p>We treat every visitor like a neighbour, because they
usually are.</p>
        <footer>&mdash; <cite>Fatma Hassan</cite></footer>
      </blockquote>
    </article>
  </main>
</body>
</html>
```

Project 148: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.about { max-width: 42rem; margin: 2rem auto; padding: 0 1rem; font-
```

```
family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; color: var(--brand); }
.lead { font-size: 1.3rem; color: var(--muted); }
img { max-width: 100%; height: auto; border-radius: 12px; }
li { margin-bottom: .5rem; }
blockquote { margin: 2rem 0; padding: 1rem 1.5rem; border-left: 5px
solid var(--brand); background: var(--accent); }
blockquote p { margin: 0 0 .5rem; font-style: italic; }
```

Project 148 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>About Nubian Guest House</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="about">	The unique content of this page; exactly one per page.
<article>	A self-contained piece: card, post, product.
About Nubian Guest House	The main heading; only one per page.
<p class="lead">Colourful rooms on the west bank of the Nile, in th...	A paragraph of text.
<img src="images/team.jpg" alt="Fatma Hassan in front of Nubian Gue...	An image; alt describes it, width and height reserve space before it loads.
Our story	Second-level heading for a section.
<p>Nubian Guest House was founded by Fatma Hassan ...	Strong importance (bold by default).

Line	What it does
	Unordered (bulleted) list.
Quality. Every room is checked twice.	One list item.
<blockquote>	A long quotation from another source.
<footer>— <cite>Fatma Hassan</cite></footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 42rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
font-size: 1.1rem;	Size of the text.
max-width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
border-left: 5px solid var(--brand);	A thick left border used as an accent stripe.
background: var(--accent);	Background colour or image.

Check your work

- Heading order h1 then h2
- Body line length under 75 characters
- Image responsive
- Quote source in cite

Exercises

1. Add a <details> element with 'Opening hours'.
2. Add a timeline as an ordered list.
3. Add a second column with an <aside> on wide screens.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb

Field	Value
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 149: About page for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 1 | Files: index.html, styles.css

Brief

Write a readable long-form page: lead paragraph, image, headings, a value list with strong keywords and a quotation with attribution.

Learning goals

- Choose text elements by meaning (strong, cite, blockquote)
- Set comfortable reading width and line length
- Mix a serif body with sans-serif headings

Elements and CSS used

HTML elements	CSS features
article, h1, h2, p, img, ul, li, strong, blockquote, footer, cite	max-width, font-family, font-size, border-left, font-style

Build guide

1. Write the article content first, without any CSS.
2. Add the image with alt text and dimensions.
3. Mark values with at the start of each list item.
4. Add the quotation with <blockquote>, a <footer> and <cite>.
5. Limit the width to 42rem and set fonts.
6. Style the blockquote with a coloured left border.

Project 149: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>About Ismailia Cycling Store</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="about">
    <article>
      <h1>About Ismailia Cycling Store</h1>
      <p class="lead">Bikes, parts and Friday group rides, in the
heart of Ismailia.</p>
      <img src="images/team.jpg" alt="Bassem Adly in front of
Ismailia Cycling Store" width="800" height="500">
      <h2>Our story</h2>
      <p>Ismailia Cycling Store was founded by <strong>Bassem Adly</
strong> with one idea: do a few things and do them well. Today our
small team offers 4 core bikes and welcomes visitors from all over
Ismailia.</p>
      <h2>What we value</h2>
      <ul>
        <li><strong>Quality.</strong> Every bike is checked twice.</
li>
        <li><strong>Honesty.</strong> Clear prices, no surprises.</li>
        <li><strong>Community.</strong> We support local schools and
clubs.</li>
      </ul>
      <blockquote>
        <p>We treat every visitor like a neighbour, because they
usually are.</p>
        <footer>&mdash; <cite>Bassem Adly</cite></footer>
      </blockquote>
    </article>
  </main>
</body>
</html>
```

Project 149: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.about { max-width: 42rem; margin: 2rem auto; padding: 0 1rem; font-
```

```
family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; color: var(--brand); }
.lead { font-size: 1.3rem; color: var(--muted); }
img { max-width: 100%; height: auto; border-radius: 12px; }
li { margin-bottom: .5rem; }
blockquote { margin: 2rem 0; padding: 1rem 1.5rem; border-left: 5px
solid var(--brand); background: var(--accent); }
blockquote p { margin: 0 0 .5rem; font-style: italic; }
```

Project 149 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>About Ismailia Cycling Store</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="about">	The unique content of this page; exactly one per page.
<article>	A self-contained piece: card, post, product.
About Ismailia Cycling Store	The main heading; only one per page.
<p class="lead">Bikes, parts and Friday group rides, in the heart o...	A paragraph of text.
<img src="images/team.jpg" alt="Bassem Adly in front of Ismailia Cy...	An image; alt describes it, width and height reserve space before it loads.
Our story	Second-level heading for a section.
<p>Ismailia Cycling Store was founded by Bassem Adly</stron...	Strong importance (bold by default).

Line	What it does
	Unordered (bulleted) list.
Quality. Every bike is checked twice.	One list item.
<blockquote>	A long quotation from another source.
<footer>— <cite>Bassem Adly</cite></footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 42rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
font-size: 1.1rem;	Size of the text.
max-width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
border-left: 5px solid var(--brand);	A thick left border used as an accent stripe.
background: var(--accent);	Background colour or image.

Check your work

- Heading order h1 then h2
- Body line length under 75 characters
- Image responsive
- Quote source in cite

Exercises

1. Add a <details> element with 'Opening hours'.
2. Add a timeline as an ordered list.
3. Add a second column with an <aside> on wide screens.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2

Field	Value
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 150: About page for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 1 | Files: index.html, styles.css

Brief

Write a readable long-form page: lead paragraph, image, headings, a value list with strong keywords and a quotation with attribution.

Learning goals

- Choose text elements by meaning (strong, cite, blockquote)
- Set comfortable reading width and line length
- Mix a serif body with sans-serif headings

Elements and CSS used

HTML elements	CSS features
article, h1, h2, p, img, ul, li, strong, blockquote, footer, cite	max-width, font-family, font-size, border-left, font-style

Build guide

1. Write the article content first, without any CSS.
2. Add the image with alt text and dimensions.
3. Mark values with at the start of each list item.
4. Add the quotation with <blockquote>, a <footer> and <cite>.
5. Limit the width to 42rem and set fonts.
6. Style the blockquote with a coloured left border.

Project 150: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>About Minya Coding Club</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="about">
    <article>
      <h1>About Minya Coding Club</h1>
      <p class="lead">Free weekend coding for teenagers, in the heart
of Minya.</p>
      <img src="images/team.jpg" alt="Youssef Hany in front of Minya
Coding Club" width="800" height="500">
      <h2>Our story</h2>
      <p>Minya Coding Club was founded by <strong>Youssef Hany</
strong> with one idea: do a few things and do them well. Today our
small team offers 4 core workshops and welcomes visitors from all
over Minya.</p>
      <h2>What we value</h2>
      <ul>
        <li><strong>Quality.</strong> Every workshop is checked twice.
</li>
        <li><strong>Honesty.</strong> Clear prices, no surprises.</li>
        <li><strong>Community.</strong> We support local schools and
clubs.</li>
      </ul>
      <blockquote>
        <p>We treat every visitor like a neighbour, because they
usually are.</p>
        <footer>&mdash; <cite>Youssef Hany</cite></footer>
      </blockquote>
    </article>
  </main>
</body>
</html>
```

Project 150: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.about { max-width: 42rem; margin: 2rem auto; padding: 0 1rem; font-
```

```
family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; color: var(--brand); }
.lead { font-size: 1.3rem; color: var(--muted); }
img { max-width: 100%; height: auto; border-radius: 12px; }
li { margin-bottom: .5rem; }
blockquote { margin: 2rem 0; padding: 1rem 1.5rem; border-left: 5px
solid var(--brand); background: var(--accent); }
blockquote p { margin: 0 0 .5rem; font-style: italic; }
```

Project 150 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>About Minya Coding Club</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="about">	The unique content of this page; exactly one per page.
<article>	A self-contained piece: card, post, product.
About Minya Coding Club	The main heading; only one per page.
<p class="lead">Free weekend coding for teenagers, in the heart of ...	A paragraph of text.
<img src="images/team.jpg" alt="Youssef Hany in front of Minya Codi...	An image; alt describes it, width and height reserve space before it loads.
Our story	Second-level heading for a section.
<p>Minya Coding Club was founded by Youssef Hany w...	Strong importance (bold by default).

Line	What it does
	Unordered (bulleted) list.
Quality. Every workshop is checked twice.	One list item.
<blockquote>	A long quotation from another source.
<footer>— <cite>Youssef Hany</cite></footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 42rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
font-size: 1.1rem;	Size of the text.
max-width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
border-left: 5px solid var(--brand);	A thick left border used as an accent stripe.
background: var(--accent);	Background colour or image.

Check your work

- Heading order h1 then h2
- Body line length under 75 characters
- Image responsive
- Quote source in cite

Exercises

1. Add a <details> element with 'Opening hours'.
2. Add a timeline as an ordered list.
3. Add a second column with an <aside> on wide screens.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff

Field	Value
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Menu list

Level 2 | 25 projects, one per theme

Present offers as a description list where each term shows a name and price joined by dotted leaders, with the description below.

Project 151: Menu list for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 2 | Files: index.html, styles.css

Brief

Present offers as a description list where each term shows a name and price joined by dotted leaders, with the description below.

Learning goals

- Use dl/dt/dd for name-description pairs
- Create dotted price leaders with a flex pseudo-element
- Use the order property

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd, span	display: flex, justify-content, ::after, order, flex: 1, border-bottom: dotted

Build guide

1. Write the <dl>; group each dt/dd pair in a .
2. Put the price in a inside the dt.
3. Make dt a flex row.
4. Add an empty ::after with flex: 1 and a dotted bottom border - this is the leader line.
5. Use order so the leader sits between the name and the price.
6. Add a dashed separator under each item.

Project 151: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cairo Book Shop</h1>
    <p class="sub">Books and prices</p>
    <dl class="menu">
      <div class="item"><dt>Learn HTML <span class="price">120 EGP</
span></dt><dd>From your first tag to a complete page</dd></div>
      <div class="item"><dt>CSS in Practice <span class="price">150
EGP</span></dt><dd>Layouts, colours and typography</dd></div>
      <div class="item"><dt>JavaScript Basics <span class="price">180
EGP</span></dt><dd>Make pages interactive</dd></div>
      <div class="item"><dt>Web Accessibility <span class="price">95
EGP</span></dt><dd>Pages everyone can use</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 151: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
h1 { text-align: center; color: var(--brand); margin-bottom: 0; }
.sub { text-align: center; color: var(--muted); margin-top: 0; }
.menu { margin: 0; }
.item { padding: 1rem 0; border-bottom: 1px dashed var(--line); }
dt { display: flex; justify-content: space-between; font-weight: 700;
font-size: 1.1rem; }
dt::after { content: ""; order: 1; flex: 1; border-bottom: 1px dotted
var(--line); margin: 0 .5rem .35rem; }
.price { order: 2; color: var(--brand); }
dd { margin: .25rem 0 0; color: var(--muted); }
```

Project 151 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - Menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cairo Book Shop	The main heading; only one per page.
Books and prices	A paragraph of text.
<dl class="menu">	Description list of term / description pairs.
<dt>Learn HTML 120 EGP...	A term (name) in a description list.
<dt>CSS in Practice 150 EGP</...	The description of the preceding term.

Line	What it does
<dt>JavaScript Basics 180 EGP...	Generic inline container for styling.
<dt>Web Accessibility 95 EGP<...	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.

Declaration	What it does
border-bottom: 1px dashed var(--line);	A bottom border used as a separator line.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
font-weight: 700;	Thickness of the text.
font-size: 1.1rem;	Size of the text.
dt::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
order: 1;	Changes the visual order of a flex item without changing the source.
flex: 1;	All items share free space equally.
border-bottom: 1px dotted var(--line);	The line around the element: width, style and colour.

Check your work

- Each dt has a dd
- Price stays on the right even for long names
- Leaders do not appear when the name is very long
- Readable on a phone

Exercises

1. Group items under h2 categories.
2. Add a 'chef's choice' badge with a ::before.
3. Print stylesheet: remove colours.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 152: Menu list for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 2 | Files: index.html, styles.css

Brief

Present offers as a description list where each term shows a name and price joined by dotted leaders, with the description below.

Learning goals

- Use dl/dt/dd for name-description pairs
- Create dotted price leaders with a flex pseudo-element
- Use the order property

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd, span	display: flex, justify-content, ::after, order, flex: 1, border-bottom: dotted

Build guide

1. Write the <dl>; group each dt/dd pair in a .
2. Put the price in a inside the dt.
3. Make dt a flex row.
4. Add an empty ::after with flex: 1 and a dotted bottom border - this is the leader line.
5. Use order so the leader sits between the name and the price.
6. Add a dashed separator under each item.

Project 152: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - Menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Nile Bakery</h1>
    <p class="sub">Pastries and prices</p>
    <dl class="menu">
      <div class="item"><dt>Sourdough loaf <span class="price">60
EGP</span></dt><dd>Slow fermented, crisp crust</dd></div>
      <div class="item"><dt>Croissant <span class="price">35 EGP</
span></dt><dd>Butter, 27 layers</dd></div>
      <div class="item"><dt>Date cookies <span class="price">80 EGP</
span></dt><dd>Traditional maamoul style</dd></div>
      <div class="item"><dt>Baklava box <span class="price">220 EGP</
span></dt><dd>Pistachio and honey</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 152: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
h1 { text-align: center; color: var(--brand); margin-bottom: 0; }
.sub { text-align: center; color: var(--muted); margin-top: 0; }
.menu { margin: 0; }
.item { padding: 1rem 0; border-bottom: 1px dashed var(--line); }
dt { display: flex; justify-content: space-between; font-weight: 700;
font-size: 1.1rem; }
dt::after { content: ""; order: 1; flex: 1; border-bottom: 1px dotted
var(--line); margin: 0 .5rem .35rem; }
.price { order: 2; color: var(--brand); }
dd { margin: .25rem 0 0; color: var(--muted); }
```

Project 152 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - Menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Nile Bakery	The main heading; only one per page.
Pastries and prices	A paragraph of text.
<dl class="menu">	Description list of term / description pairs.
<dt>Sourdough loaf 60 EGP</sp...	A term (name) in a description list.
<dt>Croissant 35 EGP<//...	The description of the preceding term.

Line	What it does
<dt>Date cookies 80 EGP</span...	Generic inline container for styling.
<dt>Baklava box 220 EGP</span...	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
text-align: center;	Centres inline content such as text.
border-bottom: 1px dashed var(--line);	A bottom border used as a separator line.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
font-weight: 700;	Thickness of the text.
font-size: 1.1rem;	Size of the text.
dt::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
order: 1;	Changes the visual order of a flex item without changing the source.
flex: 1;	All items share free space equally.
border-bottom: 1px dotted var(--line);	The line around the element: width, style and colour.

Check your work

- Each dt has a dd
- Price stays on the right even for long names
- Leaders do not appear when the name is very long
- Readable on a phone

Exercises

1. Group items under h2 categories.
2. Add a 'chef's choice' badge with a ::before.
3. Print stylesheet: remove colours.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 153: Menu list for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 2 | Files: index.html, styles.css

Brief

Present offers as a description list where each term shows a name and price joined by dotted leaders, with the description below.

Learning goals

- Use dl/dt/dd for name-description pairs
- Create dotted price leaders with a flex pseudo-element
- Use the order property

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd, span	display: flex, justify-content, ::after, order, flex: 1, border-bottom: dotted

Build guide

1. Write the <dl>; group each dt/dd pair in a .
2. Put the price in a inside the dt.
3. Make dt a flex row.
4. Add an empty ::after with flex: 1 and a dotted bottom border - this is the leader line.
5. Use order so the leader sits between the name and the price.
6. Add a dashed separator under each item.

Project 153: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - Menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Pyramid Fitness</h1>
    <p class="sub">Classes and prices</p>
    <dl class="menu">
      <div class="item"><dt>Morning yoga <span class="price">100 EGP</
span></dt><dd>Flexibility and calm, 60 minutes</dd></div>
      <div class="item"><dt>Strength circuit <span class="price">120
EGP</span></dt><dd>Full body, all levels</dd></div>
      <div class="item"><dt>Spinning <span class="price">110 EGP</
span></dt><dd>High energy cycling</dd></div>
      <div class="item"><dt>Personal training <span class="price">350
EGP</span></dt><dd>One to one coaching</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 153: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
h1 { text-align: center; color: var(--brand); margin-bottom: 0; }
.sub { text-align: center; color: var(--muted); margin-top: 0; }
.menu { margin: 0; }
.item { padding: 1rem 0; border-bottom: 1px dashed var(--line); }
dt { display: flex; justify-content: space-between; font-weight: 700;
font-size: 1.1rem; }
dt::after { content: ""; order: 1; flex: 1; border-bottom: 1px dotted
var(--line); margin: 0 .5rem .35rem; }
.price { order: 2; color: var(--brand); }
dd { margin: .25rem 0 0; color: var(--muted); }
```

Project 153 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - Menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Pyramid Fitness	The main heading; only one per page.
Classes and prices	A paragraph of text.
<dl class="menu">	Description list of term / description pairs.
<dt>Morning yoga 100 EGP</spa...	A term (name) in a description list.
<dt>Strength circuit 120 EGP<...	The description of the preceding term.

Line	What it does
<dt>Spinning 110 EGP<//...	Generic inline container for styling.
<dt>Personal training 350 EGP...	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
text-align: center;	Centres inline content such as text.
border-bottom: 1px dashed var(--line);	A bottom border used as a separator line.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
font-weight: 700;	Thickness of the text.
font-size: 1.1rem;	Size of the text.
dt::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
order: 1;	Changes the visual order of a flex item without changing the source.
flex: 1;	All items share free space equally.
border-bottom: 1px dotted var(--line);	The line around the element: width, style and colour.

Check your work

- Each dt has a dd
- Price stays on the right even for long names
- Leaders do not appear when the name is very long
- Readable on a phone

Exercises

1. Group items under h2 categories.
2. Add a 'chef's choice' badge with a ::before.
3. Print stylesheet: remove colours.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 154: Menu list for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 2 | Files: index.html, styles.css

Brief

Present offers as a description list where each term shows a name and price joined by dotted leaders, with the description below.

Learning goals

- Use dl/dt/dd for name-description pairs
- Create dotted price leaders with a flex pseudo-element
- Use the order property

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd, span	display: flex, justify-content, ::after, order, flex: 1, border-bottom: dotted

Build guide

1. Write the <dl>; group each dt/dd pair in a .
2. Put the price in a inside the dt.
3. Make dt a flex row.
4. Add an empty ::after with flex: 1 and a dotted bottom border - this is the leader line.
5. Use order so the leader sits between the name and the price.
6. Add a dashed separator under each item.

Project 154: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - Menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Delta Dental Clinic</h1>
    <p class="sub">Services and prices</p>
    <dl class="menu">
      <div class="item"><dt>Check-up <span class="price">300 EGP</
span></dt><dd>Examination and cleaning</dd></div>
      <div class="item"><dt>Whitening <span class="price">1500 EGP</
span></dt><dd>Brighter smile in one visit</dd></div>
      <div class="item"><dt>Filling <span class="price">600 EGP</
span></dt><dd>Tooth-coloured composite</dd></div>
      <div class="item"><dt>Braces consultation <span
class="price">Free</span></dt><dd>Plan your treatment</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 154: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
h1 { text-align: center; color: var(--brand); margin-bottom: 0; }
.sub { text-align: center; color: var(--muted); margin-top: 0; }
.menu { margin: 0; }
.item { padding: 1rem 0; border-bottom: 1px dashed var(--line); }
dt { display: flex; justify-content: space-between; font-weight: 700;
font-size: 1.1rem; }
dt::after { content: ""; order: 1; flex: 1; border-bottom: 1px dotted
var(--line); margin: 0 .5rem .35rem; }
.price { order: 2; color: var(--brand); }
dd { margin: .25rem 0 0; color: var(--muted); }
```

Project 154 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - Menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Delta Dental Clinic	The main heading; only one per page.
Services and prices	A paragraph of text.
<dl class="menu">	Description list of term / description pairs.
<dt>Check-up 300 EGP<//...	A term (name) in a description list.
<dt>Whitening 1500 EGP...	The description of the preceding term.

Line	What it does
<dt>Filling 600 EGP</d...	Generic inline container for styling.
<dt>Braces consultation Free<...	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
text-align: center;	Centres inline content such as text.
border-bottom: 1px dashed var(--line);	A bottom border used as a separator line.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
font-weight: 700;	Thickness of the text.
font-size: 1.1rem;	Size of the text.
dt::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
order: 1;	Changes the visual order of a flex item without changing the source.
flex: 1;	All items share free space equally.
border-bottom: 1px dotted var(--line);	The line around the element: width, style and colour.

Check your work

- Each dt has a dd
- Price stays on the right even for long names
- Leaders do not appear when the name is very long
- Readable on a phone

Exercises

1. Group items under h2 categories.
2. Add a 'chef's choice' badge with a ::before.
3. Print stylesheet: remove colours.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 155: Menu list for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 2 | Files: index.html, styles.css

Brief

Present offers as a description list where each term shows a name and price joined by dotted leaders, with the description below.

Learning goals

- Use dl/dt/dd for name-description pairs
- Create dotted price leaders with a flex pseudo-element
- Use the order property

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd, span	display: flex, justify-content, ::after, order, flex: 1, border-bottom: dotted

Build guide

1. Write the <dl>; group each dt/dd pair in a .
2. Put the price in a inside the dt.
3. Make dt a flex row.
4. Add an empty ::after with flex: 1 and a dotted bottom border - this is the leader line.
5. Use order so the leader sits between the name and the price.
6. Add a dashed separator under each item.

Project 155: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - Menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Red Sea Travel</h1>
    <p class="sub">Tours and prices</p>
    <dl class="menu">
      <div class="item"><dt>Luxor day trip <span class="price">1200
EGP</span></dt><dd>Karnak, Valley of the Kings</dd></div>
      <div class="item"><dt>Snorkelling <span class="price">700 EGP</
span></dt><dd>Giftun island reefs</dd></div>
      <div class="item"><dt>Desert safari <span class="price">900
EGP</span></dt><dd>Quad bikes and Bedouin dinner</dd></div>
      <div class="item"><dt>Nile cruise <span class="price">6500 EGP</
span></dt><dd>Three nights Aswan to Luxor</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 155: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
h1 { text-align: center; color: var(--brand); margin-bottom: 0; }
.sub { text-align: center; color: var(--muted); margin-top: 0; }
.menu { margin: 0; }
.item { padding: 1rem 0; border-bottom: 1px dashed var(--line); }
dt { display: flex; justify-content: space-between; font-weight: 700;
font-size: 1.1rem; }
dt::after { content: ""; order: 1; flex: 1; border-bottom: 1px dotted
var(--line); margin: 0 .5rem .35rem; }
.price { order: 2; color: var(--brand); }
dd { margin: .25rem 0 0; color: var(--muted); }
```

Project 155 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - Menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Red Sea Travel	The main heading; only one per page.
Tours and prices	A paragraph of text.
<dl class="menu">	Description list of term / description pairs.
<dt>Luxor day trip 1200 EGP</...	A term (name) in a description list.
<dt>Snorkelling 700 EGP</span...	The description of the preceding term.

Line	What it does
<dt>Desert safari 900 EGP</sp...	Generic inline container for styling.
<dt>Nile cruise 6500 EGP</spa...	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
text-align: center;	Centres inline content such as text.
border-bottom: 1px dashed var(--line);	A bottom border used as a separator line.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
font-weight: 700;	Thickness of the text.
font-size: 1.1rem;	Size of the text.
dt::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
order: 1;	Changes the visual order of a flex item without changing the source.
flex: 1;	All items share free space equally.
border-bottom: 1px dotted var(--line);	The line around the element: width, style and colour.

Check your work

- Each dt has a dd
- Price stays on the right even for long names
- Leaders do not appear when the name is very long
- Readable on a phone

Exercises

1. Group items under h2 categories.
2. Add a 'chef's choice' badge with a ::before.
3. Print stylesheet: remove colours.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 156: Menu list for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Present offers as a description list where each term shows a name and price joined by dotted leaders, with the description below.

Learning goals

- Use dl/dt/dd for name-description pairs
- Create dotted price leaders with a flex pseudo-element
- Use the order property

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd, span	display: flex, justify-content, ::after, order, flex: 1, border-bottom: dotted

Build guide

1. Write the <dl>; group each dt/dd pair in a .
2. Put the price in a inside the dt.
3. Make dt a flex row.
4. Add an empty ::after with flex: 1 and a dotted bottom border - this is the leader line.
5. Use order so the leader sits between the name and the price.
6. Add a dashed separator under each item.

Project 156: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - Menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Lotus Language School</h1>
    <p class="sub">Courses and prices</p>
    <dl class="menu">
      <div class="item"><dt>English A1 <span class="price">1800 EGP</
span></dt><dd>Beginner, 8 weeks</dd></div>
      <div class="item"><dt>French B1 <span class="price">2200 EGP</
span></dt><dd>Intermediate conversation</dd></div>
      <div class="item"><dt>German A2 <span class="price">2000 EGP</
span></dt><dd>Grammar and speaking</dd></div>
      <div class="item"><dt>IELTS preparation <span
class="price">3000 EGP</span></dt><dd>Exam strategies</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 156: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
h1 { text-align: center; color: var(--brand); margin-bottom: 0; }
.sub { text-align: center; color: var(--muted); margin-top: 0; }
.menu { margin: 0; }
.item { padding: 1rem 0; border-bottom: 1px dashed var(--line); }
dt { display: flex; justify-content: space-between; font-weight: 700;
font-size: 1.1rem; }
dt::after { content: ""; order: 1; flex: 1; border-bottom: 1px dotted
var(--line); margin: 0 .5rem .35rem; }
.price { order: 2; color: var(--brand); }
dd { margin: .25rem 0 0; color: var(--muted); }
```

Project 156 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - Menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Lotus Language School	The main heading; only one per page.
Courses and prices	A paragraph of text.
<dl class="menu">	Description list of term / description pairs.
<dt>English A1 1800 EGP</span...	A term (name) in a description list.
<dt>French B1 2200 EGP...	The description of the preceding term.

Line	What it does
<dt>German A2 2000 EGP...	Generic inline container for styling.
<dt>IELTS preparation 3000 EG...	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.

Declaration	What it does
border-bottom: 1px dashed var(--line);	A bottom border used as a separator line.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
font-weight: 700;	Thickness of the text.
font-size: 1.1rem;	Size of the text.
dt::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
order: 1;	Changes the visual order of a flex item without changing the source.
flex: 1;	All items share free space equally.
border-bottom: 1px dotted var(--line);	The line around the element: width, style and colour.

Check your work

- Each dt has a dd
- Price stays on the right even for long names
- Leaders do not appear when the name is very long
- Readable on a phone

Exercises

1. Group items under h2 categories.
2. Add a 'chef's choice' badge with a ::before.
3. Print stylesheet: remove colours.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 157: Menu list for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 2 | Files: index.html, styles.css

Brief

Present offers as a description list where each term shows a name and price joined by dotted leaders, with the description below.

Learning goals

- Use dl/dt/dd for name-description pairs
- Create dotted price leaders with a flex pseudo-element
- Use the order property

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd, span	display: flex, justify-content, ::after, order, flex: 1, border-bottom: dotted

Build guide

1. Write the <dl>; group each dt/dd pair in a .
2. Put the price in a inside the dt.
3. Make dt a flex row.
4. Add an empty ::after with flex: 1 and a dotted bottom border - this is the leader line.
5. Use order so the leader sits between the name and the price.
6. Add a dashed separator under each item.

Project 157: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - Menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Green Leaf Cafe</h1>
    <p class="sub">Drinks and prices</p>
    <dl class="menu">
      <div class="item"><dt>Flat white <span class="price">55 EGP</
span></dt><dd>Double shot, silky milk</dd></div>
      <div class="item"><dt>Cold brew <span class="price">60 EGP</
span></dt><dd>18 hours steeped</dd></div>
      <div class="item"><dt>Hibiscus iced tea <span class="price">40
EGP</span></dt><dd>Karkade with mint</dd></div>
      <div class="item"><dt>Cheesecake <span class="price">75 EGP</
span></dt><dd>Baked, with berries</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 157: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
h1 { text-align: center; color: var(--brand); margin-bottom: 0; }
.sub { text-align: center; color: var(--muted); margin-top: 0; }
.menu { margin: 0; }
.item { padding: 1rem 0; border-bottom: 1px dashed var(--line); }
dt { display: flex; justify-content: space-between; font-weight: 700;
font-size: 1.1rem; }
dt::after { content: ""; order: 1; flex: 1; border-bottom: 1px dotted
var(--line); margin: 0 .5rem .35rem; }
.price { order: 2; color: var(--brand); }
dd { margin: .25rem 0 0; color: var(--muted); }
```

Project 157 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - Menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Green Leaf Cafe	The main heading; only one per page.
Drinks and prices	A paragraph of text.
<dl class="menu">	Description list of term / description pairs.
<dt>Flat white 55 EGP<...	A term (name) in a description list.
<dt>Cold brew 60 EGP</...	The description of the preceding term.

Line	What it does
<dt>Hibiscus iced tea 40 EGP<...	Generic inline container for styling.
<dt>Cheesecake 75 EGP<...	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
text-align: center;	Centres inline content such as text.
border-bottom: 1px dashed var(--line);	A bottom border used as a separator line.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
font-weight: 700;	Thickness of the text.
font-size: 1.1rem;	Size of the text.
dt::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
order: 1;	Changes the visual order of a flex item without changing the source.
flex: 1;	All items share free space equally.
border-bottom: 1px dotted var(--line);	The line around the element: width, style and colour.

Check your work

- Each dt has a dd
- Price stays on the right even for long names
- Leaders do not appear when the name is very long
- Readable on a phone

Exercises

1. Group items under h2 categories.
2. Add a 'chef's choice' badge with a ::before.
3. Print stylesheet: remove colours.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 158: Menu list for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 2 | Files: index.html, styles.css

Brief

Present offers as a description list where each term shows a name and price joined by dotted leaders, with the description below.

Learning goals

- Use dl/dt/dd for name-description pairs
- Create dotted price leaders with a flex pseudo-element
- Use the order property

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd, span	display: flex, justify-content, ::after, order, flex: 1, border-bottom: dotted

Build guide

1. Write the <dl>; group each dt/dd pair in a .
2. Put the price in a inside the dt.
3. Make dt a flex row.
4. Add an empty ::after with flex: 1 and a dotted bottom border - this is the leader line.
5. Use order so the leader sits between the name and the price.
6. Add a dashed separator under each item.

Project 158: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - Menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Sinai Trekking Club</h1>
    <p class="sub">Hikes and prices</p>
    <dl class="menu">
      <div class="item"><dt>Mount Sinai sunrise <span
class="price">400 EGP</span></dt><dd>Night climb, 7 km</dd></div>
      <div class="item"><dt>Blue Desert loop <span class="price">250
EGP</span></dt><dd>Easy day walk</dd></div>
      <div class="item"><dt>Wadi Gnai <span class="price">300 EGP</
span></dt><dd>Palms and pools</dd></div>
      <div class="item"><dt>Three-day traverse <span
class="price">1900 EGP</span></dt><dd>Camping under stars</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 158: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
h1 { text-align: center; color: var(--brand); margin-bottom: 0; }
.sub { text-align: center; color: var(--muted); margin-top: 0; }
.menu { margin: 0; }
.item { padding: 1rem 0; border-bottom: 1px dashed var(--line); }
dt { display: flex; justify-content: space-between; font-weight: 700;
font-size: 1.1rem; }
dt::after { content: ""; order: 1; flex: 1; border-bottom: 1px dotted
var(--line); margin: 0 .5rem .35rem; }
.price { order: 2; color: var(--brand); }
dd { margin: .25rem 0 0; color: var(--muted); }
```

Project 158 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - Menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Sinai Trekking Club	The main heading; only one per page.
Hikes and prices	A paragraph of text.
<dl class="menu">	Description list of term / description pairs.
<dt>Mount Sinai sunrise 400 E...	A term (name) in a description list.
<dt>Blue Desert loop 250 EGP<...	The description of the preceding term.

Line	What it does
<dt>Wadi Gnai 300 EGP<...	Generic inline container for styling.
<dt>Three-day traverse 1900 E...	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
text-align: center;	Centres inline content such as text.
border-bottom: 1px dashed var(--line);	A bottom border used as a separator line.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
font-weight: 700;	Thickness of the text.
font-size: 1.1rem;	Size of the text.
dt::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
order: 1;	Changes the visual order of a flex item without changing the source.
flex: 1;	All items share free space equally.
border-bottom: 1px dotted var(--line);	The line around the element: width, style and colour.

Check your work

- Each dt has a dd
- Price stays on the right even for long names
- Leaders do not appear when the name is very long
- Readable on a phone

Exercises

1. Group items under h2 categories.
2. Add a 'chef's choice' badge with a ::before.
3. Print stylesheet: remove colours.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 159: Menu list for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 2 | Files: index.html, styles.css

Brief

Present offers as a description list where each term shows a name and price joined by dotted leaders, with the description below.

Learning goals

- Use dl/dt/dd for name-description pairs
- Create dotted price leaders with a flex pseudo-element
- Use the order property

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd, span	display: flex, justify-content, ::after, order, flex: 1, border-bottom: dotted

Build guide

1. Write the <dl>; group each dt/dd pair in a .
2. Put the price in a inside the dt.
3. Make dt a flex row.
4. Add an empty ::after with flex: 1 and a dotted bottom border - this is the leader line.
5. Use order so the leader sits between the name and the price.
6. Add a dashed separator under each item.

Project 159: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - Menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Horizon Photography</h1>
    <p class="sub">Sessions and prices</p>
    <dl class="menu">
      <div class="item"><dt>Portrait session <span class="price">1200
EGP</span></dt><dd>One hour, 20 edited photos</dd></div>
      <div class="item"><dt>Wedding day <span class="price">15000
EGP</span></dt><dd>Full coverage, two photographers</dd></div>
      <div class="item"><dt>Product shoot <span class="price">900
EGP</span></dt><dd>White background, 10 items</dd></div>
      <div class="item"><dt>Family session <span class="price">1500
EGP</span></dt><dd>Outdoor, golden hour</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 159: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
h1 { text-align: center; color: var(--brand); margin-bottom: 0; }
.sub { text-align: center; color: var(--muted); margin-top: 0; }
.menu { margin: 0; }
.item { padding: 1rem 0; border-bottom: 1px dashed var(--line); }
dt { display: flex; justify-content: space-between; font-weight: 700;
font-size: 1.1rem; }
dt::after { content: ""; order: 1; flex: 1; border-bottom: 1px dotted
var(--line); margin: 0 .5rem .35rem; }
.price { order: 2; color: var(--brand); }
dd { margin: .25rem 0 0; color: var(--muted); }
```

Project 159 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - Menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Horizon Photography	The main heading; only one per page.
Sessions and prices	A paragraph of text.
<dl class="menu">	Description list of term / description pairs.
<dt>Portrait session 1200 EGP...	A term (name) in a description list.
<dt>Wedding day 15000 EGP</sp...	The description of the preceding term.

Line	What it does
<dt>Product shoot 900 EGP</sp...	Generic inline container for styling.
<dt>Family session 1500 EGP</...	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
text-align: center;	Centres inline content such as text.
border-bottom: 1px dashed var(--line);	A bottom border used as a separator line.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
font-weight: 700;	Thickness of the text.
font-size: 1.1rem;	Size of the text.
dt::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
order: 1;	Changes the visual order of a flex item without changing the source.
flex: 1;	All items share free space equally.
border-bottom: 1px dotted var(--line);	The line around the element: width, style and colour.

Check your work

- Each dt has a dd
- Price stays on the right even for long names
- Leaders do not appear when the name is very long
- Readable on a phone

Exercises

1. Group items under h2 categories.
2. Add a 'chef's choice' badge with a ::before.
3. Print stylesheet: remove colours.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 160: Menu list for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 2 | Files: index.html, styles.css

Brief

Present offers as a description list where each term shows a name and price joined by dotted leaders, with the description below.

Learning goals

- Use dl/dt/dd for name-description pairs
- Create dotted price leaders with a flex pseudo-element
- Use the order property

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd, span	display: flex, justify-content, ::after, order, flex: 1, border-bottom: dotted

Build guide

1. Write the <dl>; group each dt/dd pair in a .
2. Put the price in a inside the dt.
3. Make dt a flex row.
4. Add an empty ::after with flex: 1 and a dotted bottom border - this is the leader line.
5. Use order so the leader sits between the name and the price.
6. Add a dashed separator under each item.

Project 160: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - Menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Papyrus Stationery</h1>
    <p class="sub">Products and prices</p>
    <dl class="menu">
      <div class="item"><dt>Dotted notebook <span class="price">140
EGP</span></dt><dd>A5, 160 pages</dd></div>
      <div class="item"><dt>Fountain pen <span class="price">350 EGP</
span></dt><dd>Steel nib, refillable</dd></div>
      <div class="item"><dt>Washi tape set <span class="price">90
EGP</span></dt><dd>Six patterns</dd></div>
      <div class="item"><dt>Desk planner <span class="price">110 EGP</
span></dt><dd>Weekly, undated</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 160: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
h1 { text-align: center; color: var(--brand); margin-bottom: 0; }
.sub { text-align: center; color: var(--muted); margin-top: 0; }
.menu { margin: 0; }
.item { padding: 1rem 0; border-bottom: 1px dashed var(--line); }
dt { display: flex; justify-content: space-between; font-weight: 700;
font-size: 1.1rem; }
dt::after { content: ""; order: 1; flex: 1; border-bottom: 1px dotted
var(--line); margin: 0 .5rem .35rem; }
.price { order: 2; color: var(--brand); }
dd { margin: .25rem 0 0; color: var(--muted); }
```

Project 160 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - Menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Papyrus Stationery	The main heading; only one per page.
Products and prices	A paragraph of text.
<dl class="menu">	Description list of term / description pairs.
<dt>Dotted notebook 140 EGP</...	A term (name) in a description list.
<dt>Fountain pen 350 EGP</spa...	The description of the preceding term.

Line	What it does
<dt>Washi tape set 90 EGP</sp...	Generic inline container for styling.
<dt>Desk planner 110 EGP</spa...	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
text-align: center;	Centres inline content such as text.
border-bottom: 1px dashed var(--line);	A bottom border used as a separator line.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
font-weight: 700;	Thickness of the text.
font-size: 1.1rem;	Size of the text.
dt::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
order: 1;	Changes the visual order of a flex item without changing the source.
flex: 1;	All items share free space equally.
border-bottom: 1px dotted var(--line);	The line around the element: width, style and colour.

Check your work

- Each dt has a dd
- Price stays on the right even for long names
- Leaders do not appear when the name is very long
- Readable on a phone

Exercises

1. Group items under h2 categories.
2. Add a 'chef's choice' badge with a ::before.
3. Print stylesheet: remove colours.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 161: Menu list for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 2 | Files: index.html, styles.css

Brief

Present offers as a description list where each term shows a name and price joined by dotted leaders, with the description below.

Learning goals

- Use dl/dt/dd for name-description pairs
- Create dotted price leaders with a flex pseudo-element
- Use the order property

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd, span	display: flex, justify-content, ::after, order, flex: 1, border-bottom: dotted

Build guide

1. Write the <dl>; group each dt/dd pair in a .
2. Put the price in a inside the dt.
3. Make dt a flex row.
4. Add an empty ::after with flex: 1 and a dotted bottom border - this is the leader line.
5. Use order so the leader sits between the name and the price.
6. Add a dashed separator under each item.

Project 161: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - Menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Oasis Plant Nursery</h1>
    <p class="sub">Plants and prices</p>
    <dl class="menu">
      <div class="item"><dt>Monstera <span class="price">250 EGP</
span></dt><dd>Large leaves, easy care</dd></div>
      <div class="item"><dt>Snake plant <span class="price">120 EGP</
span></dt><dd>Survives anything</dd></div>
      <div class="item"><dt>Basil pot <span class="price">45 EGP</
span></dt><dd>Kitchen herb</dd></div>
      <div class="item"><dt>Olive tree <span class="price">600 EGP</
span></dt><dd>Balcony sized</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 161: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
h1 { text-align: center; color: var(--brand); margin-bottom: 0; }
.sub { text-align: center; color: var(--muted); margin-top: 0; }
.menu { margin: 0; }
.item { padding: 1rem 0; border-bottom: 1px dashed var(--line); }
dt { display: flex; justify-content: space-between; font-weight: 700;
font-size: 1.1rem; }
dt::after { content: ""; order: 1; flex: 1; border-bottom: 1px dotted
var(--line); margin: 0 .5rem .35rem; }
.price { order: 2; color: var(--brand); }
dd { margin: .25rem 0 0; color: var(--muted); }
```

Project 161 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - Menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Oasis Plant Nursery	The main heading; only one per page.
Plants and prices	A paragraph of text.
<dl class="menu">	Description list of term / description pairs.
<dt>Monstera 250 EGP<//...	A term (name) in a description list.
<dt>Snake plant 120 EGP</span...	The description of the preceding term.

Line	What it does
<dt>Basil pot 45 EGP<//...	Generic inline container for styling.
<dt>Olive tree 600 EGP...	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.

Declaration	What it does
border-bottom: 1px dashed var(--line);	A bottom border used as a separator line.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
font-weight: 700;	Thickness of the text.
font-size: 1.1rem;	Size of the text.
dt::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
order: 1;	Changes the visual order of a flex item without changing the source.
flex: 1;	All items share free space equally.
border-bottom: 1px dotted var(--line);	The line around the element: width, style and colour.

Check your work

- Each dt has a dd
- Price stays on the right even for long names
- Leaders do not appear when the name is very long
- Readable on a phone

Exercises

1. Group items under h2 categories.
2. Add a 'chef's choice' badge with a ::before.
3. Print stylesheet: remove colours.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 162: Menu list for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 2 | Files: index.html, styles.css

Brief

Present offers as a description list where each term shows a name and price joined by dotted leaders, with the description below.

Learning goals

- Use dl/dt/dd for name-description pairs
- Create dotted price leaders with a flex pseudo-element
- Use the order property

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd, span	display: flex, justify-content, ::after, order, flex: 1, border-bottom: dotted

Build guide

1. Write the <dl>; group each dt/dd pair in a .
2. Put the price in a inside the dt.
3. Make dt a flex row.
4. Add an empty ::after with flex: 1 and a dotted bottom border - this is the leader line.
5. Use order so the leader sits between the name and the price.
6. Add a dashed separator under each item.

Project 162: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - Menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cedar Furniture</h1>
    <p class="sub">Pieces and prices</p>
    <dl class="menu">
      <div class="item"><dt>Oak dining table <span class="price">9500
EGP</span></dt><dd>Seats six</dd></div>
      <div class="item"><dt>Bookshelf <span class="price">4200 EGP</
span></dt><dd>Five shelves, walnut</dd></div>
      <div class="item"><dt>Bedside table <span class="price">1500
EGP</span></dt><dd>One drawer</dd></div>
      <div class="item"><dt>Coffee table <span class="price">2800
EGP</span></dt><dd>Round, ash wood</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 162: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
h1 { text-align: center; color: var(--brand); margin-bottom: 0; }
.sub { text-align: center; color: var(--muted); margin-top: 0; }
.menu { margin: 0; }
.item { padding: 1rem 0; border-bottom: 1px dashed var(--line); }
dt { display: flex; justify-content: space-between; font-weight: 700;
font-size: 1.1rem; }
dt::after { content: ""; order: 1; flex: 1; border-bottom: 1px dotted
var(--line); margin: 0 .5rem .35rem; }
.price { order: 2; color: var(--brand); }
dd { margin: .25rem 0 0; color: var(--muted); }
```

Project 162 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - Menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cedar Furniture	The main heading; only one per page.
Pieces and prices	A paragraph of text.
<dl class="menu">	Description list of term / description pairs.
<dt>Oak dining table 9500 EGP...	A term (name) in a description list.
<dt>Bookshelf 4200 EGP...	The description of the preceding term.

Line	What it does
<dt>Bedside table 1500 EGP</s...	Generic inline container for styling.
<dt>Coffee table 2800 EGP</sp...	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
text-align: center;	Centres inline content such as text.
border-bottom: 1px dashed var(--line);	A bottom border used as a separator line.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
font-weight: 700;	Thickness of the text.
font-size: 1.1rem;	Size of the text.
dt::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
order: 1;	Changes the visual order of a flex item without changing the source.
flex: 1;	All items share free space equally.
border-bottom: 1px dotted var(--line);	The line around the element: width, style and colour.

Check your work

- Each dt has a dd
- Price stays on the right even for long names
- Leaders do not appear when the name is very long
- Readable on a phone

Exercises

1. Group items under h2 categories.
2. Add a 'chef's choice' badge with a ::before.
3. Print stylesheet: remove colours.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 163: Menu list for Byte Repair

Theme: Byte Repair (Nasr City) | Level 2 | Files: index.html, styles.css

Brief

Present offers as a description list where each term shows a name and price joined by dotted leaders, with the description below.

Learning goals

- Use dl/dt/dd for name-description pairs
- Create dotted price leaders with a flex pseudo-element
- Use the order property

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd, span	display: flex, justify-content, ::after, order, flex: 1, border-bottom: dotted

Build guide

1. Write the <dl>; group each dt/dd pair in a .
2. Put the price in a inside the dt.
3. Make dt a flex row.
4. Add an empty ::after with flex: 1 and a dotted bottom border - this is the leader line.
5. Use order so the leader sits between the name and the price.
6. Add a dashed separator under each item.

Project 163: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - Menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Byte Repair</h1>
    <p class="sub">Repairs and prices</p>
    <dl class="menu">
      <div class="item"><dt>Screen replacement <span
class="price">From 800 EGP</span></dt><dd>Most phones, 1 hour</dd></
div>
      <div class="item"><dt>Battery swap <span class="price">From 500
EGP</span></dt><dd>Original cells</dd></div>
      <div class="item"><dt>Laptop cleaning <span class="price">350
EGP</span></dt><dd>Fans and thermal paste</dd></div>
      <div class="item"><dt>Data recovery <span class="price">From
1200 EGP</span></dt><dd>Drives and cards</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 163: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
h1 { text-align: center; color: var(--brand); margin-bottom: 0; }
.sub { text-align: center; color: var(--muted); margin-top: 0; }
.menu { margin: 0; }
.item { padding: 1rem 0; border-bottom: 1px dashed var(--line); }
dt { display: flex; justify-content: space-between; font-weight: 700;
font-size: 1.1rem; }
dt::after { content: ""; order: 1; flex: 1; border-bottom: 1px dotted
var(--line); margin: 0 .5rem .35rem; }
.price { order: 2; color: var(--brand); }
dd { margin: .25rem 0 0; color: var(--muted); }
```

Project 163 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - Menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Byte Repair	The main heading; only one per page.
Repairs and prices	A paragraph of text.
<dl class="menu">	Description list of term / description pairs.
<dt>Screen replacement From 8...	A term (name) in a description list.
<dt>Battery swap From 500 EGP...	The description of the preceding term.

Line	What it does
<dt>Laptop cleaning 350 EGP<//...	Generic inline container for styling.
<dt>Data recovery From 1200 E...	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.

Declaration	What it does
border-bottom: 1px dashed var(--line);	A bottom border used as a separator line.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
font-weight: 700;	Thickness of the text.
font-size: 1.1rem;	Size of the text.
dt::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
order: 1;	Changes the visual order of a flex item without changing the source.
flex: 1;	All items share free space equally.
border-bottom: 1px dotted var(--line);	The line around the element: width, style and colour.

Check your work

- Each dt has a dd
- Price stays on the right even for long names
- Leaders do not appear when the name is very long
- Readable on a phone

Exercises

1. Group items under h2 categories.
2. Add a 'chef's choice' badge with a ::before.
3. Print stylesheet: remove colours.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 164: Menu list for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 2 | Files: index.html, styles.css

Brief

Present offers as a description list where each term shows a name and price joined by dotted leaders, with the description below.

Learning goals

- Use dl/dt/dd for name-description pairs
- Create dotted price leaders with a flex pseudo-element
- Use the order property

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd, span	display: flex, justify-content, ::after, order, flex: 1, border-bottom: dotted

Build guide

1. Write the <dl>; group each dt/dd pair in a .
2. Put the price in a inside the dt.
3. Make dt a flex row.
4. Add an empty ::after with flex: 1 and a dotted bottom border - this is the leader line.
5. Use order so the leader sits between the name and the price.
6. Add a dashed separator under each item.

Project 164: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - Menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Sahara Pet Care</h1>
    <p class="sub">Services and prices</p>
    <dl class="menu">
      <div class="item"><dt>Full grooming <span class="price">400
EGP</span></dt><dd>Bath, cut and nails</dd></div>
      <div class="item"><dt>Day boarding <span class="price">250 EGP</
span></dt><dd>Play and rest</dd></div>
      <div class="item"><dt>Vaccination <span class="price">300 EGP</
span></dt><dd>Annual boosters</dd></div>
      <div class="item"><dt>Dog walking <span class="price">100 EGP</
span></dt><dd>30 minutes</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 164: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
h1 { text-align: center; color: var(--brand); margin-bottom: 0; }
.sub { text-align: center; color: var(--muted); margin-top: 0; }
.menu { margin: 0; }
.item { padding: 1rem 0; border-bottom: 1px dashed var(--line); }
dt { display: flex; justify-content: space-between; font-weight: 700;
font-size: 1.1rem; }
dt::after { content: ""; order: 1; flex: 1; border-bottom: 1px dotted
var(--line); margin: 0 .5rem .35rem; }
.price { order: 2; color: var(--brand); }
dd { margin: .25rem 0 0; color: var(--muted); }
```

Project 164 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - Menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Sahara Pet Care	The main heading; only one per page.
Services and prices	A paragraph of text.
<dl class="menu">	Description list of term / description pairs.
<dt>Full grooming 400 EGP</sp...	A term (name) in a description list.
<dt>Day boarding 250 EGP</spa...	The description of the preceding term.

Line	What it does
<dt>Vaccination 300 EGP</span...	Generic inline container for styling.
<dt>Dog walking 100 EGP</span...	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
text-align: center;	Centres inline content such as text.
border-bottom: 1px dashed var(--line);	A bottom border used as a separator line.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
font-weight: 700;	Thickness of the text.
font-size: 1.1rem;	Size of the text.
dt::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
order: 1;	Changes the visual order of a flex item without changing the source.
flex: 1;	All items share free space equally.
border-bottom: 1px dotted var(--line);	The line around the element: width, style and colour.

Check your work

- Each dt has a dd
- Price stays on the right even for long names
- Leaders do not appear when the name is very long
- Readable on a phone

Exercises

1. Group items under h2 categories.
2. Add a 'chef's choice' badge with a ::before.
3. Print stylesheet: remove colours.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 165: Menu list for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Present offers as a description list where each term shows a name and price joined by dotted leaders, with the description below.

Learning goals

- Use dl/dt/dd for name-description pairs
- Create dotted price leaders with a flex pseudo-element
- Use the order property

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd, span	display: flex, justify-content, ::after, order, flex: 1, border-bottom: dotted

Build guide

1. Write the <dl>; group each dt/dd pair in a .
2. Put the price in a inside the dt.
3. Make dt a flex row.
4. Add an empty ::after with flex: 1 and a dotted bottom border - this is the leader line.
5. Use order so the leader sits between the name and the price.
6. Add a dashed separator under each item.

Project 165: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - Menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Alexandria Sailing School</h1>
    <p class="sub">Lessons and prices</p>
    <dl class="menu">
      <div class="item"><dt>Taster session <span class="price">500
EGP</span></dt><dd>Two hours on the water</dd></div>
      <div class="item"><dt>Beginner course <span class="price">2200
EGP</span></dt><dd>Five sessions</dd></div>
      <div class="item"><dt>Racing clinic <span class="price">1800
EGP</span></dt><dd>Tactics and trim</dd></div>
      <div class="item"><dt>Private lesson <span class="price">900
EGP</span></dt><dd>One to one</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 165: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
h1 { text-align: center; color: var(--brand); margin-bottom: 0; }
.sub { text-align: center; color: var(--muted); margin-top: 0; }
.menu { margin: 0; }
.item { padding: 1rem 0; border-bottom: 1px dashed var(--line); }
dt { display: flex; justify-content: space-between; font-weight: 700;
font-size: 1.1rem; }
dt::after { content: ""; order: 1; flex: 1; border-bottom: 1px dotted
var(--line); margin: 0 .5rem .35rem; }
.price { order: 2; color: var(--brand); }
dd { margin: .25rem 0 0; color: var(--muted); }
```

Project 165 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - Menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Alexandria Sailing School	The main heading; only one per page.
Lessons and prices	A paragraph of text.
<dl class="menu">	Description list of term / description pairs.
<dt>Taster session 500 EGP</s...	A term (name) in a description list.
<dt>Beginner course 2200 EGP<...	The description of the preceding term.

Line	What it does
<dt>Racing clinic 1800 EGP</s...	Generic inline container for styling.
<dt>Private lesson 900 EGP</s...	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
text-align: center;	Centres inline content such as text.
border-bottom: 1px dashed var(--line);	A bottom border used as a separator line.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
font-weight: 700;	Thickness of the text.
font-size: 1.1rem;	Size of the text.
dt::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
order: 1;	Changes the visual order of a flex item without changing the source.
flex: 1;	All items share free space equally.
border-bottom: 1px dotted var(--line);	The line around the element: width, style and colour.

Check your work

- Each dt has a dd
- Price stays on the right even for long names
- Leaders do not appear when the name is very long
- Readable on a phone

Exercises

1. Group items under h2 categories.
2. Add a 'chef's choice' badge with a ::before.
3. Print stylesheet: remove colours.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 166: Menu list for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Present offers as a description list where each term shows a name and price joined by dotted leaders, with the description below.

Learning goals

- Use dl/dt/dd for name-description pairs
- Create dotted price leaders with a flex pseudo-element
- Use the order property

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd, span	display: flex, justify-content, ::after, order, flex: 1, border-bottom: dotted

Build guide

1. Write the <dl>; group each dt/dd pair in a .
2. Put the price in a inside the dt.
3. Make dt a flex row.
4. Add an empty ::after with flex: 1 and a dotted bottom border - this is the leader line.
5. Use order so the leader sits between the name and the price.
6. Add a dashed separator under each item.

Project 166: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - Menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Habiba Handmade Jewellery</h1>
    <p class="sub">Items and prices</p>
    <dl class="menu">
      <div class="item"><dt>Lotus pendant <span class="price">650
EGP</span></dt><dd>Sterling silver</dd></div>
      <div class="item"><dt>Brass cuff <span class="price">420 EGP</
span></dt><dd>Hand engraved</dd></div>
      <div class="item"><dt>Bead earrings <span class="price">180
EGP</span></dt><dd>Recycled glass</dd></div>
      <div class="item"><dt>Ankh ring <span class="price">300 EGP</
span></dt><dd>Adjustable</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 166: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
h1 { text-align: center; color: var(--brand); margin-bottom: 0; }
.sub { text-align: center; color: var(--muted); margin-top: 0; }
.menu { margin: 0; }
.item { padding: 1rem 0; border-bottom: 1px dashed var(--line); }
dt { display: flex; justify-content: space-between; font-weight: 700;
font-size: 1.1rem; }
dt::after { content: ""; order: 1; flex: 1; border-bottom: 1px dotted
var(--line); margin: 0 .5rem .35rem; }
.price { order: 2; color: var(--brand); }
dd { margin: .25rem 0 0; color: var(--muted); }
```

Project 166 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - Menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Habiba Handmade Jewellery	The main heading; only one per page.
Items and prices	A paragraph of text.
<dl class="menu">	Description list of term / description pairs.
<dt>Lotus pendant 650 EGP</sp...	A term (name) in a description list.
<dt>Brass cuff 420 EGP...	The description of the preceding term.

Line	What it does
<dt>Bead earrings 180 EGP</sp...	Generic inline container for styling.
<dt>Ankh ring 300 EGP<...	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.

Declaration	What it does
border-bottom: 1px dashed var(--line);	A bottom border used as a separator line.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
font-weight: 700;	Thickness of the text.
font-size: 1.1rem;	Size of the text.
dt::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
order: 1;	Changes the visual order of a flex item without changing the source.
flex: 1;	All items share free space equally.
border-bottom: 1px dotted var(--line);	The line around the element: width, style and colour.

Check your work

- Each dt has a dd
- Price stays on the right even for long names
- Leaders do not appear when the name is very long
- Readable on a phone

Exercises

1. Group items under h2 categories.
2. Add a 'chef's choice' badge with a ::before.
3. Print stylesheet: remove colours.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 167: Menu list for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 2 | Files: index.html, styles.css

Brief

Present offers as a description list where each term shows a name and price joined by dotted leaders, with the description below.

Learning goals

- Use dl/dt/dd for name-description pairs
- Create dotted price leaders with a flex pseudo-element
- Use the order property

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd, span	display: flex, justify-content, ::after, order, flex: 1, border-bottom: dotted

Build guide

1. Write the <dl>; group each dt/dd pair in a .
2. Put the price in a inside the dt.
3. Make dt a flex row.
4. Add an empty ::after with flex: 1 and a dotted bottom border - this is the leader line.
5. Use order so the leader sits between the name and the price.
6. Add a dashed separator under each item.

Project 167: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - Menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Fayoum Pottery Studio</h1>
    <p class="sub">Workshops and prices</p>
    <dl class="menu">
      <div class="item"><dt>Intro to the wheel <span
class="price">450 EGP</span></dt><dd>Three hours, take home a bowl</
dd></div>
      <div class="item"><dt>Glazing day <span class="price">300 EGP</
span></dt><dd>Colour your pieces</dd></div>
      <div class="item"><dt>Kids clay class <span class="price">200
EGP</span></dt><dd>Ages 6 to 12</dd></div>
      <div class="item"><dt>Weekend retreat <span class="price">2500
EGP</span></dt><dd>Two days with meals</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 167: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
h1 { text-align: center; color: var(--brand); margin-bottom: 0; }
.sub { text-align: center; color: var(--muted); margin-top: 0; }
.menu { margin: 0; }
.item { padding: 1rem 0; border-bottom: 1px dashed var(--line); }
dt { display: flex; justify-content: space-between; font-weight: 700;
font-size: 1.1rem; }
dt::after { content: ""; order: 1; flex: 1; border-bottom: 1px dotted
var(--line); margin: 0 .5rem .35rem; }
.price { order: 2; color: var(--brand); }
dd { margin: .25rem 0 0; color: var(--muted); }
```

Project 167 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - Menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Fayoum Pottery Studio	The main heading; only one per page.
Workshops and prices	A paragraph of text.
<dl class="menu">	Description list of term / description pairs.
<dt>Intro to the wheel 450 EG...	A term (name) in a description list.
<dt>Glazing day 300 EGP</span...	The description of the preceding term.

Line	What it does
<dt>Kids clay class 200 EGP<//...	Generic inline container for styling.
<dt>Weekend retreat 2500 EGP<...	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.

Declaration	What it does
border-bottom: 1px dashed var(--line);	A bottom border used as a separator line.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
font-weight: 700;	Thickness of the text.
font-size: 1.1rem;	Size of the text.
dt::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
order: 1;	Changes the visual order of a flex item without changing the source.
flex: 1;	All items share free space equally.
border-bottom: 1px dotted var(--line);	The line around the element: width, style and colour.

Check your work

- Each dt has a dd
- Price stays on the right even for long names
- Leaders do not appear when the name is very long
- Readable on a phone

Exercises

1. Group items under h2 categories.
2. Add a 'chef's choice' badge with a ::before.
3. Print stylesheet: remove colours.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 168: Menu list for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 2 | Files: index.html, styles.css

Brief

Present offers as a description list where each term shows a name and price joined by dotted leaders, with the description below.

Learning goals

- Use dl/dt/dd for name-description pairs
- Create dotted price leaders with a flex pseudo-element
- Use the order property

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd, span	display: flex, justify-content, ::after, order, flex: 1, border-bottom: dotted

Build guide

1. Write the <dl>; group each dt/dd pair in a .
2. Put the price in a inside the dt.
3. Make dt a flex row.
4. Add an empty ::after with flex: 1 and a dotted bottom border - this is the leader line.
5. Use order so the leader sits between the name and the price.
6. Add a dashed separator under each item.

Project 168: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - Menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cleopatra Beauty Salon</h1>
    <p class="sub">Treatments and prices</p>
    <dl class="menu">
      <div class="item"><dt>Haircut and blow-dry <span
class="price">350 EGP</span></dt><dd>Consultation included</dd></div>
      <div class="item"><dt>Manicure <span class="price">200 EGP</
span></dt><dd>Classic or gel</dd></div>
      <div class="item"><dt>Facial <span class="price">600 EGP</
span></dt><dd>Deep cleanse, 60 minutes</dd></div>
      <div class="item"><dt>Bridal package <span class="price">4500
EGP</span></dt><dd>Hair, make-up and nails</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 168: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
h1 { text-align: center; color: var(--brand); margin-bottom: 0; }
.sub { text-align: center; color: var(--muted); margin-top: 0; }
.menu { margin: 0; }
.item { padding: 1rem 0; border-bottom: 1px dashed var(--line); }
dt { display: flex; justify-content: space-between; font-weight: 700;
font-size: 1.1rem; }
dt::after { content: ""; order: 1; flex: 1; border-bottom: 1px dotted
var(--line); margin: 0 .5rem .35rem; }
.price { order: 2; color: var(--brand); }
dd { margin: .25rem 0 0; color: var(--muted); }
```

Project 168 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - Menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cleopatra Beauty Salon	The main heading; only one per page.
Treatments and prices	A paragraph of text.
<dl class="menu">	Description list of term / description pairs.
<dt>Haircut and blow-dry 350 ...	A term (name) in a description list.
<dt>Manicure 200 EGP<//...	The description of the preceding term.

Line	What it does
<dt>Facial 600 EGP</dt...	Generic inline container for styling.
<dt>Bridal package 4500 EGP</...	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.

Declaration	What it does
border-bottom: 1px dashed var(--line);	A bottom border used as a separator line.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
font-weight: 700;	Thickness of the text.
font-size: 1.1rem;	Size of the text.
dt::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
order: 1;	Changes the visual order of a flex item without changing the source.
flex: 1;	All items share free space equally.
border-bottom: 1px dotted var(--line);	The line around the element: width, style and colour.

Check your work

- Each dt has a dd
- Price stays on the right even for long names
- Leaders do not appear when the name is very long
- Readable on a phone

Exercises

1. Group items under h2 categories.
2. Add a 'chef's choice' badge with a ::before.
3. Print stylesheet: remove colours.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 169: Menu list for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 2 | Files: index.html, styles.css

Brief

Present offers as a description list where each term shows a name and price joined by dotted leaders, with the description below.

Learning goals

- Use dl/dt/dd for name-description pairs
- Create dotted price leaders with a flex pseudo-element
- Use the order property

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd, span	display: flex, justify-content, ::after, order, flex: 1, border-bottom: dotted

Build guide

1. Write the <dl>; group each dt/dd pair in a .
2. Put the price in a inside the dt.
3. Make dt a flex row.
4. Add an empty ::after with flex: 1 and a dotted bottom border - this is the leader line.
5. Use order so the leader sits between the name and the price.
6. Add a dashed separator under each item.

Project 169: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - Menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Suez Auto Service</h1>
    <p class="sub">Services and prices</p>
    <dl class="menu">
      <div class="item"><dt>Oil change <span class="price">600 EGP</
span></dt><dd>Filter included</dd></div>
      <div class="item"><dt>Brake pads <span class="price">1400 EGP</
span></dt><dd>Front axle</dd></div>
      <div class="item"><dt>Air conditioning <span class="price">900
EGP</span></dt><dd>Recharge and check</dd></div>
      <div class="item"><dt>Pre-purchase inspection <span
class="price">750 EGP</span></dt><dd>120 point check</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 169: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
h1 { text-align: center; color: var(--brand); margin-bottom: 0; }
.sub { text-align: center; color: var(--muted); margin-top: 0; }
.menu { margin: 0; }
.item { padding: 1rem 0; border-bottom: 1px dashed var(--line); }
dt { display: flex; justify-content: space-between; font-weight: 700;
font-size: 1.1rem; }
dt::after { content: ""; order: 1; flex: 1; border-bottom: 1px dotted
var(--line); margin: 0 .5rem .35rem; }
.price { order: 2; color: var(--brand); }
dd { margin: .25rem 0 0; color: var(--muted); }
```

Project 169 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - Menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Suez Auto Service	The main heading; only one per page.
Services and prices	A paragraph of text.
<dl class="menu">	Description list of term / description pairs.
<dt>Oil change 600 EGP...	A term (name) in a description list.
<dt>Brake pads 1400 EGP</span...	The description of the preceding term.

Line	What it does
<dt>Air conditioning 900 EGP<...	Generic inline container for styling.
<dt>Pre-purchase inspection 7...	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.

Declaration	What it does
border-bottom: 1px dashed var(--line);	A bottom border used as a separator line.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
font-weight: 700;	Thickness of the text.
font-size: 1.1rem;	Size of the text.
dt::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
order: 1;	Changes the visual order of a flex item without changing the source.
flex: 1;	All items share free space equally.
border-bottom: 1px dotted var(--line);	The line around the element: width, style and colour.

Check your work

- Each dt has a dd
- Price stays on the right even for long names
- Leaders do not appear when the name is very long
- Readable on a phone

Exercises

1. Group items under h2 categories.
2. Add a 'chef's choice' badge with a ::before.
3. Print stylesheet: remove colours.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 170: Menu list for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 2 | Files: index.html, styles.css

Brief

Present offers as a description list where each term shows a name and price joined by dotted leaders, with the description below.

Learning goals

- Use dl/dt/dd for name-description pairs
- Create dotted price leaders with a flex pseudo-element
- Use the order property

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd, span	display: flex, justify-content, ::after, order, flex: 1, border-bottom: dotted

Build guide

1. Write the <dl>; group each dt/dd pair in a .
2. Put the price in a inside the dt.
3. Make dt a flex row.
4. Add an empty ::after with flex: 1 and a dotted bottom border - this is the leader line.
5. Use order so the leader sits between the name and the price.
6. Add a dashed separator under each item.

Project 170: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - Menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Luxor Music Academy</h1>
    <p class="sub">Courses and prices</p>
    <dl class="menu">
      <div class="item"><dt>Oud for beginners <span
class="price">1600 EGP</span></dt><dd>Eight weekly lessons</dd></div>
      <div class="item"><dt>Piano grade 1 <span class="price">1800
EGP</span></dt><dd>Theory and practice</dd></div>
      <div class="item"><dt>Guitar chords <span class="price">1400
EGP</span></dt><dd>Play songs in a month</dd></div>
      <div class="item"><dt>Voice coaching <span class="price">1500
EGP</span></dt><dd>Breathing and range</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 170: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
h1 { text-align: center; color: var(--brand); margin-bottom: 0; }
.sub { text-align: center; color: var(--muted); margin-top: 0; }
.menu { margin: 0; }
.item { padding: 1rem 0; border-bottom: 1px dashed var(--line); }
dt { display: flex; justify-content: space-between; font-weight: 700;
font-size: 1.1rem; }
dt::after { content: ""; order: 1; flex: 1; border-bottom: 1px dotted
var(--line); margin: 0 .5rem .35rem; }
.price { order: 2; color: var(--brand); }
dd { margin: .25rem 0 0; color: var(--muted); }
```

Project 170 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - Menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Luxor Music Academy	The main heading; only one per page.
Courses and prices	A paragraph of text.
<dl class="menu">	Description list of term / description pairs.
<dt>Oud for beginners 1600 EG...	A term (name) in a description list.
<dt>Piano grade 1 1800 EGP</s...	The description of the preceding term.

Line	What it does
<dt>Guitar chords 1400 EGP</s...	Generic inline container for styling.
<dt>Voice coaching 1500 EGP<//...	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.

Declaration	What it does
border-bottom: 1px dashed var(--line);	A bottom border used as a separator line.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
font-weight: 700;	Thickness of the text.
font-size: 1.1rem;	Size of the text.
dt::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
order: 1;	Changes the visual order of a flex item without changing the source.
flex: 1;	All items share free space equally.
border-bottom: 1px dotted var(--line);	The line around the element: width, style and colour.

Check your work

- Each dt has a dd
- Price stays on the right even for long names
- Leaders do not appear when the name is very long
- Readable on a phone

Exercises

1. Group items under h2 categories.
2. Add a 'chef's choice' badge with a ::before.
3. Print stylesheet: remove colours.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 171: Menu list for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 2 | Files: index.html, styles.css

Brief

Present offers as a description list where each term shows a name and price joined by dotted leaders, with the description below.

Learning goals

- Use dl/dt/dd for name-description pairs
- Create dotted price leaders with a flex pseudo-element
- Use the order property

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd, span	display: flex, justify-content, ::after, order, flex: 1, border-bottom: dotted

Build guide

1. Write the <dl>; group each dt/dd pair in a .
2. Put the price in a inside the dt.
3. Make dt a flex row.
4. Add an empty ::after with flex: 1 and a dotted bottom border - this is the leader line.
5. Use order so the leader sits between the name and the price.
6. Add a dashed separator under each item.

Project 171: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - Menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Port Said Seafood</h1>
    <p class="sub">Dishes and prices</p>
    <dl class="menu">
      <div class="item"><dt>Grilled sea bass <span class="price">320
EGP</span></dt><dd>With rice and salad</dd></div>
      <div class="item"><dt>Shrimp tagine <span class="price">280
EGP</span></dt><dd>Tomato and garlic</dd></div>
      <div class="item"><dt>Calamari <span class="price">190 EGP</
span></dt><dd>Fried, with tahini</dd></div>
      <div class="item"><dt>Fish soup <span class="price">120 EGP</
span></dt><dd>Daily catch</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 171: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
h1 { text-align: center; color: var(--brand); margin-bottom: 0; }
.sub { text-align: center; color: var(--muted); margin-top: 0; }
.menu { margin: 0; }
.item { padding: 1rem 0; border-bottom: 1px dashed var(--line); }
dt { display: flex; justify-content: space-between; font-weight: 700;
font-size: 1.1rem; }
dt::after { content: ""; order: 1; flex: 1; border-bottom: 1px dotted
var(--line); margin: 0 .5rem .35rem; }
.price { order: 2; color: var(--brand); }
dd { margin: .25rem 0 0; color: var(--muted); }
```

Project 171 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - Menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Port Said Seafood	The main heading; only one per page.
Dishes and prices	A paragraph of text.
<dl class="menu">	Description list of term / description pairs.
<dt>Grilled sea bass 320 EGP<...	A term (name) in a description list.
<dt>Shrimp tagine 280 EGP</sp...	The description of the preceding term.

Line	What it does
<dt>Calamari 190 EGP<//...	Generic inline container for styling.
<dt>Fish soup 120 EGP<...	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
text-align: center;	Centres inline content such as text.
border-bottom: 1px dashed var(--line);	A bottom border used as a separator line.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
font-weight: 700;	Thickness of the text.
font-size: 1.1rem;	Size of the text.
dt::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
order: 1;	Changes the visual order of a flex item without changing the source.
flex: 1;	All items share free space equally.
border-bottom: 1px dotted var(--line);	The line around the element: width, style and colour.

Check your work

- Each dt has a dd
- Price stays on the right even for long names
- Leaders do not appear when the name is very long
- Readable on a phone

Exercises

1. Group items under h2 categories.
2. Add a 'chef's choice' badge with a ::before.
3. Print stylesheet: remove colours.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 172: Menu list for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 2 | Files: index.html, styles.css

Brief

Present offers as a description list where each term shows a name and price joined by dotted leaders, with the description below.

Learning goals

- Use dl/dt/dd for name-description pairs
- Create dotted price leaders with a flex pseudo-element
- Use the order property

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd, span	display: flex, justify-content, ::after, order, flex: 1, border-bottom: dotted

Build guide

1. Write the <dl>; group each dt/dd pair in a .
2. Put the price in a inside the dt.
3. Make dt a flex row.
4. Add an empty ::after with flex: 1 and a dotted bottom border - this is the leader line.
5. Use order so the leader sits between the name and the price.
6. Add a dashed separator under each item.

Project 172: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - Menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Delta Kids Library</h1>
    <p class="sub">Programmes and prices</p>
    <dl class="menu">
      <div class="item"><dt>Story hour <span class="price">Free</
span></dt><dd>Ages 3 to 6, Saturdays</dd></div>
      <div class="item"><dt>Reading club <span class="price">50 EGP
per month</span></dt><dd>Ages 7 to 11</dd></div>
      <div class="item"><dt>Homework help <span class="price">Free</
span></dt><dd>Weekday afternoons</dd></div>
      <div class="item"><dt>Summer challenge <span
class="price">Free</span></dt><dd>Read ten books</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 172: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
h1 { text-align: center; color: var(--brand); margin-bottom: 0; }
.sub { text-align: center; color: var(--muted); margin-top: 0; }
.menu { margin: 0; }
.item { padding: 1rem 0; border-bottom: 1px dashed var(--line); }
dt { display: flex; justify-content: space-between; font-weight: 700;
font-size: 1.1rem; }
dt::after { content: ""; order: 1; flex: 1; border-bottom: 1px dotted
var(--line); margin: 0 .5rem .35rem; }
.price { order: 2; color: var(--brand); }
dd { margin: .25rem 0 0; color: var(--muted); }
```

Project 172 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - Menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Delta Kids Library	The main heading; only one per page.
Programmes and prices	A paragraph of text.
<dl class="menu">	Description list of term / description pairs.
<dt>Story hour Free</d...	A term (name) in a description list.
<dt>Reading club 50 EGP per m...	The description of the preceding term.

Line	What it does
<dt>Homework help Free...	Generic inline container for styling.
<dt>Summer challenge Free</sp...	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
text-align: center;	Centres inline content such as text.
border-bottom: 1px dashed var(--line);	A bottom border used as a separator line.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
font-weight: 700;	Thickness of the text.
font-size: 1.1rem;	Size of the text.
dt::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
order: 1;	Changes the visual order of a flex item without changing the source.
flex: 1;	All items share free space equally.
border-bottom: 1px dotted var(--line);	The line around the element: width, style and colour.

Check your work

- Each dt has a dd
- Price stays on the right even for long names
- Leaders do not appear when the name is very long
- Readable on a phone

Exercises

1. Group items under h2 categories.
2. Add a 'chef's choice' badge with a ::before.
3. Print stylesheet: remove colours.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 173: Menu list for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Present offers as a description list where each term shows a name and price joined by dotted leaders, with the description below.

Learning goals

- Use dl/dt/dd for name-description pairs
- Create dotted price leaders with a flex pseudo-element
- Use the order property

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd, span	display: flex, justify-content, ::after, order, flex: 1, border-bottom: dotted

Build guide

1. Write the <dl>; group each dt/dd pair in a .
2. Put the price in a inside the dt.
3. Make dt a flex row.
4. Add an empty ::after with flex: 1 and a dotted bottom border - this is the leader line.
5. Use order so the leader sits between the name and the price.
6. Add a dashed separator under each item.

Project 173: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - Menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Nubian Guest House</h1>
    <p class="sub">Rooms and prices</p>
    <dl class="menu">
      <div class="item"><dt>Garden room <span class="price">900 EGP</
span></dt><dd>Double bed, shared terrace</dd></div>
      <div class="item"><dt>Nile view suite <span class="price">1800
EGP</span></dt><dd>Balcony and breakfast</dd></div>
      <div class="item"><dt>Family room <span class="price">1500 EGP</
span></dt><dd>Sleeps four</dd></div>
      <div class="item"><dt>Rooftop dorm <span class="price">300 EGP</
span></dt><dd>Budget beds</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 173: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
h1 { text-align: center; color: var(--brand); margin-bottom: 0; }
.sub { text-align: center; color: var(--muted); margin-top: 0; }
.menu { margin: 0; }
.item { padding: 1rem 0; border-bottom: 1px dashed var(--line); }
dt { display: flex; justify-content: space-between; font-weight: 700;
font-size: 1.1rem; }
dt::after { content: ""; order: 1; flex: 1; border-bottom: 1px dotted
var(--line); margin: 0 .5rem .35rem; }
.price { order: 2; color: var(--brand); }
dd { margin: .25rem 0 0; color: var(--muted); }
```

Project 173 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - Menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Nubian Guest House	The main heading; only one per page.
Rooms and prices	A paragraph of text.
<dl class="menu">	Description list of term / description pairs.
<dt>Garden room 900 EGP</span...	A term (name) in a description list.
<dt>Nile view suite 1800 EGP<...	The description of the preceding term.

Line	What it does
<dt>Family room 1500 EGP</spa...	Generic inline container for styling.
<dt>Rooftop dorm 300 EGP</spa...	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
border-bottom: 1px dashed var(--line);	A bottom border used as a separator line.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
font-weight: 700;	Thickness of the text.
font-size: 1.1rem;	Size of the text.
dt::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
order: 1;	Changes the visual order of a flex item without changing the source.
flex: 1;	All items share free space equally.
border-bottom: 1px dotted var(--line);	The line around the element: width, style and colour.

Check your work

- Each dt has a dd
- Price stays on the right even for long names
- Leaders do not appear when the name is very long
- Readable on a phone

Exercises

1. Group items under h2 categories.

2. Add a 'chef's choice' badge with a ::before.
3. Print stylesheet: remove colours.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 174: Menu list for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 2 | Files: index.html, styles.css

Brief

Present offers as a description list where each term shows a name and price joined by dotted leaders, with the description below.

Learning goals

- Use dl/dt/dd for name-description pairs
- Create dotted price leaders with a flex pseudo-element
- Use the order property

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd, span	display: flex, justify-content, ::after, order, flex: 1, border-bottom: dotted

Build guide

1. Write the <dl>; group each dt/dd pair in a .
2. Put the price in a inside the dt.
3. Make dt a flex row.
4. Add an empty ::after with flex: 1 and a dotted bottom border - this is the leader line.
5. Use order so the leader sits between the name and the price.
6. Add a dashed separator under each item.

Project 174: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - Menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Ismailia Cycling Store</h1>
    <p class="sub">Bikes and prices</p>
    <dl class="menu">
      <div class="item"><dt>City bike <span class="price">6500 EGP</
span></dt><dd>Seven gears, basket</dd></div>
      <div class="item"><dt>Mountain bike <span class="price">11000
EGP</span></dt><dd>Front suspension</dd></div>
      <div class="item"><dt>Kids bike <span class="price">3200 EGP</
span></dt><dd>20 inch wheels</dd></div>
      <div class="item"><dt>Tune-up <span class="price">250 EGP</
span></dt><dd>Brakes, gears and true wheels</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 174: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
h1 { text-align: center; color: var(--brand); margin-bottom: 0; }
.sub { text-align: center; color: var(--muted); margin-top: 0; }
.menu { margin: 0; }
.item { padding: 1rem 0; border-bottom: 1px dashed var(--line); }
dt { display: flex; justify-content: space-between; font-weight: 700;
font-size: 1.1rem; }
dt::after { content: ""; order: 1; flex: 1; border-bottom: 1px dotted
var(--line); margin: 0 .5rem .35rem; }
.price { order: 2; color: var(--brand); }
dd { margin: .25rem 0 0; color: var(--muted); }
```

Project 174 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - Menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Ismailia Cycling Store	The main heading; only one per page.
Bikes and prices	A paragraph of text.
<dl class="menu">	Description list of term / description pairs.
<dt>City bike 6500 EGP...	A term (name) in a description list.
<dt>Mountain bike 11000 EGP</...	The description of the preceding term.

Line	What it does
<dt>Kids bike 3200 EGP...	Generic inline container for styling.
<dt>Tune-up 250 EGP</d...	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
text-align: center;	Centres inline content such as text.
border-bottom: 1px dashed var(--line);	A bottom border used as a separator line.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
font-weight: 700;	Thickness of the text.
font-size: 1.1rem;	Size of the text.
dt::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
order: 1;	Changes the visual order of a flex item without changing the source.
flex: 1;	All items share free space equally.
border-bottom: 1px dotted var(--line);	The line around the element: width, style and colour.

Check your work

- Each dt has a dd
- Price stays on the right even for long names
- Leaders do not appear when the name is very long
- Readable on a phone

Exercises

1. Group items under h2 categories.
2. Add a 'chef's choice' badge with a ::before.
3. Print stylesheet: remove colours.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 175: Menu list for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 2 | Files: index.html, styles.css

Brief

Present offers as a description list where each term shows a name and price joined by dotted leaders, with the description below.

Learning goals

- Use dl/dt/dd for name-description pairs
- Create dotted price leaders with a flex pseudo-element
- Use the order property

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd, span	display: flex, justify-content, ::after, order, flex: 1, border-bottom: dotted

Build guide

1. Write the <dl>; group each dt/dd pair in a .
2. Put the price in a inside the dt.
3. Make dt a flex row.
4. Add an empty ::after with flex: 1 and a dotted bottom border - this is the leader line.
5. Use order so the leader sits between the name and the price.
6. Add a dashed separator under each item.

Project 175: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - Menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Minya Coding Club</h1>
    <p class="sub">Workshops and prices</p>
    <dl class="menu">
      <div class="item"><dt>HTML weekend <span class="price">Free</
span></dt><dd>Build your first page</dd></div>
      <div class="item"><dt>CSS art <span class="price">Free</span></
dt><dd>Draw with code</dd></div>
      <div class="item"><dt>Scratch games <span class="price">Free</
span></dt><dd>Ages 10 to 13</dd></div>
      <div class="item"><dt>Hackathon <span class="price">Free</
span></dt><dd>48 hours, teams of four</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 175: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
h1 { text-align: center; color: var(--brand); margin-bottom: 0; }
.sub { text-align: center; color: var(--muted); margin-top: 0; }
.menu { margin: 0; }
.item { padding: 1rem 0; border-bottom: 1px dashed var(--line); }
dt { display: flex; justify-content: space-between; font-weight: 700;
font-size: 1.1rem; }
dt::after { content: ""; order: 1; flex: 1; border-bottom: 1px dotted
var(--line); margin: 0 .5rem .35rem; }
.price { order: 2; color: var(--brand); }
dd { margin: .25rem 0 0; color: var(--muted); }
```

Project 175 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - Menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Minya Coding Club	The main heading; only one per page.
Workshops and prices	A paragraph of text.
<dl class="menu">	Description list of term / description pairs.
<dt>HTML weekend Free<...	A term (name) in a description list.
<dt>CSS art Free </dt><...	The description of the preceding term.

Line	What it does
<dt>Scratch games Free...	Generic inline container for styling.
<dt>Hackathon Free</dt...	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
text-align: center;	Centres inline content such as text.
border-bottom: 1px dashed var(--line);	A bottom border used as a separator line.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
font-weight: 700;	Thickness of the text.
font-size: 1.1rem;	Size of the text.
dt::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
order: 1;	Changes the visual order of a flex item without changing the source.
flex: 1;	All items share free space equally.
border-bottom: 1px dotted var(--line);	The line around the element: width, style and colour.

Check your work

- Each dt has a dd
- Price stays on the right even for long names
- Leaders do not appear when the name is very long
- Readable on a phone

Exercises

1. Group items under h2 categories.
2. Add a 'chef's choice' badge with a ::before.
3. Print stylesheet: remove colours.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: FAQ accordion

Level 2 | 25 projects, one per theme

Build an accordion of questions and answers with no JavaScript using details and summary, with a custom plus/minus indicator.

Project 176: FAQ accordion for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 2 | Files: index.html, styles.css

Brief

Build an accordion of questions and answers with no JavaScript using details and summary, with a custom plus/minus indicator.

Learning goals

- Use details/summary for native disclosure
- Style the open state with the [open] attribute selector
- Replace the default marker

Elements and CSS used

HTML elements	CSS features
details, summary, p, h1	[open], ::after, content, list-style: none, cursor: pointer, border-radius

Build guide

1. Write one <details> per question; the question goes in <summary>.
2. Add open to the first one so it starts expanded.
3. Remove the default triangle marker.
4. Add a plus sign with summary::after and a minus when open.
5. Give the open summary a background and border.
6. Click and use the keyboard (Tab, Enter) to test.

Project 176: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - FAQ</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Frequently asked questions</h1>
    <details open>
      <summary>How do I book a book?</summary>
      <p>Use the contact form or call us. Popular books fill up
quickly.</p>
    </details>
    <details>
      <summary>Where are you located?</summary>
      <p>We are in Giza. Parking is available nearby.</p>
    </details>
    <details>
      <summary>Do you offer discounts?</summary>
      <p>Students and groups of four or more get 10 percent off.</p>
    </details>
    <details>
      <summary>Can I cancel?</summary>
      <p>Yes, up to 24 hours before, free of charge.</p>
    </details>
  </main>
</body>
</html>
```

Project 176: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
details { border: 1px solid var(--line); border-radius: 10px; margin-
bottom: .75rem; background: #fff; }
summary { padding: .9rem 1.1rem; cursor: pointer; font-weight: 600;
list-style: none; display: flex; justify-content: space-between; }
summary::-webkit-details-marker { display: none; }
summary::after { content: "+"; color: var(--brand); font-size: 1.3rem;
 line-height: 1; }
```

```
details[open] summary::after { content: "\2212"; }
details[open] summary { border-bottom: 1px solid var(--line);
background: var(--accent); }
details p { padding: 0 1.1rem 1rem; margin: .75rem 0 0; }
```

Project 176 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - FAQ</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Frequently asked questions	The main heading; only one per page.
<details open>	Disclosure widget that can be opened and closed.
<summary>How do I book a book?</summary>	The always-visible heading of a details element.
Use the contact form or call us. Popular books fill up quickly.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
background: #fff;	Background colour or image.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-weight: 600;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
display: none;	Removes the element from rendering completely.
summary::after {	Generated content inserted after the element's content.
content: "+";	The text or empty string for a pseudo-element.
font-size: 1.3rem;	Size of the text.
details[open] summary::after {	Attribute selector: a details or dialog that is open.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.

Check your work

- Summary is the first child
- Works with keyboard
- Only summary is clickable, not the answer
- Indicator changes when open

Exercises

1. Use the name attribute so only one item can be open at once.
2. Animate the opening with interpolate-size or a max-height transition.
3. Add a search box that filters questions with JavaScript.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 177: FAQ accordion for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 2 | Files: index.html, styles.css

Brief

Build an accordion of questions and answers with no JavaScript using details and summary, with a custom plus/minus indicator.

Learning goals

- Use details/summary for native disclosure
- Style the open state with the [open] attribute selector
- Replace the default marker

Elements and CSS used

HTML elements	CSS features
details, summary, p, h1	[open], ::after, content, list-style: none, cursor: pointer, border-radius

Build guide

1. Write one <details> per question; the question goes in <summary>.
2. Add open to the first one so it starts expanded.
3. Remove the default triangle marker.
4. Add a plus sign with summary::after and a minus when open.
5. Give the open summary a background and border.
6. Click and use the keyboard (Tab, Enter) to test.

Project 177: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - FAQ</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Frequently asked questions</h1>
    <details open>
      <summary>How do I book a pastry?</summary>
      <p>Use the contact form or call us. Popular pastries fill up
quickly.</p>
    </details>
    <details>
      <summary>Where are you located?</summary>
      <p>We are in Cairo. Parking is available nearby.</p>
    </details>
    <details>
      <summary>Do you offer discounts?</summary>
      <p>Students and groups of four or more get 10 percent off.</p>
    </details>
    <details>
      <summary>Can I cancel?</summary>
      <p>Yes, up to 24 hours before, free of charge.</p>
    </details>
  </main>
</body>
</html>
```

Project 177: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
details { border: 1px solid var(--line); border-radius: 10px; margin-
bottom: .75rem; background: #fff; }
summary { padding: .9rem 1.1rem; cursor: pointer; font-weight: 600;
list-style: none; display: flex; justify-content: space-between; }
summary::-webkit-details-marker { display: none; }
summary::after { content: "+"; color: var(--brand); font-size: 1.3rem;
 line-height: 1; }
```

```
details[open] summary::after { content: "\2212"; }
details[open] summary { border-bottom: 1px solid var(--line);
background: var(--accent); }
details p { padding: 0 1.1rem 1rem; margin: .75rem 0 0; }
```

Project 177 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - FAQ</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Frequently asked questions	The main heading; only one per page.
<details open>	Disclosure widget that can be opened and closed.
<summary>How do I book a pastry?</summary>	The always-visible heading of a details element.
<p>Use the contact form or call us. Popular pastries fill up quickl...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
background: #fff;	Background colour or image.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-weight: 600;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
display: none;	Removes the element from rendering completely.
summary::after {	Generated content inserted after the element's content.
content: "+";	The text or empty string for a pseudo-element.
font-size: 1.3rem;	Size of the text.
details[open] summary::after {	Attribute selector: a details or dialog that is open.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.

Check your work

- Summary is the first child
- Works with keyboard
- Only summary is clickable, not the answer
- Indicator changes when open

Exercises

1. Use the name attribute so only one item can be open at once.
2. Animate the opening with interpolate-size or a max-height transition.
3. Add a search box that filters questions with JavaScript.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 178: FAQ accordion for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 2 | Files: index.html, styles.css

Brief

Build an accordion of questions and answers with no JavaScript using details and summary, with a custom plus/minus indicator.

Learning goals

- Use details/summary for native disclosure
- Style the open state with the [open] attribute selector
- Replace the default marker

Elements and CSS used

HTML elements	CSS features
details, summary, p, h1	[open], ::after, content, list-style: none, cursor: pointer, border-radius

Build guide

1. Write one <details> per question; the question goes in <summary>.
2. Add open to the first one so it starts expanded.
3. Remove the default triangle marker.
4. Add a plus sign with summary::after and a minus when open.
5. Give the open summary a background and border.
6. Click and use the keyboard (Tab, Enter) to test.

Project 178: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - FAQ</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Frequently asked questions</h1>
    <details open>
      <summary>How do I book a class?</summary>
      <p>Use the contact form or call us. Popular classes fill up
quickly.</p>
    </details>
    <details>
      <summary>Where are you located?</summary>
      <p>We are in 6th of October. Parking is available nearby.</p>
    </details>
    <details>
      <summary>Do you offer discounts?</summary>
      <p>Students and groups of four or more get 10 percent off.</p>
    </details>
    <details>
      <summary>Can I cancel?</summary>
      <p>Yes, up to 24 hours before, free of charge.</p>
    </details>
  </main>
</body>
</html>
```

Project 178: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
details { border: 1px solid var(--line); border-radius: 10px; margin-
bottom: .75rem; background: #fff; }
summary { padding: .9rem 1.1rem; cursor: pointer; font-weight: 600;
list-style: none; display: flex; justify-content: space-between; }
summary::-webkit-details-marker { display: none; }
summary::after { content: "+"; color: var(--brand); font-size: 1.3rem;
 line-height: 1; }
```

```
details[open] summary::after { content: "\2212"; }
details[open] summary { border-bottom: 1px solid var(--line);
background: var(--accent); }
details p { padding: 0 1.1rem 1rem; margin: .75rem 0 0; }
```

Project 178 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - FAQ</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Frequently asked questions	The main heading; only one per page.
<details open>	Disclosure widget that can be opened and closed.
<summary>How do I book a class?</summary>	The always-visible heading of a details element.
<p>Use the contact form or call us. Popular classes fill up quickly...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
background: #fff;	Background colour or image.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-weight: 600;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
display: none;	Removes the element from rendering completely.
summary::after {	Generated content inserted after the element's content.
content: "+";	The text or empty string for a pseudo-element.
font-size: 1.3rem;	Size of the text.
details[open] summary::after {	Attribute selector: a details or dialog that is open.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.

Check your work

- Summary is the first child
- Works with keyboard
- Only summary is clickable, not the answer
- Indicator changes when open

Exercises

1. Use the name attribute so only one item can be open at once.
2. Animate the opening with interpolate-size or a max-height transition.
3. Add a search box that filters questions with JavaScript.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 179: FAQ accordion for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 2 | Files: index.html, styles.css

Brief

Build an accordion of questions and answers with no JavaScript using details and summary, with a custom plus/minus indicator.

Learning goals

- Use details/summary for native disclosure
- Style the open state with the [open] attribute selector
- Replace the default marker

Elements and CSS used

HTML elements	CSS features
details, summary, p, h1	[open], ::after, content, list-style: none, cursor: pointer, border-radius

Build guide

1. Write one <details> per question; the question goes in <summary>.
2. Add open to the first one so it starts expanded.
3. Remove the default triangle marker.
4. Add a plus sign with summary::after and a minus when open.
5. Give the open summary a background and border.
6. Click and use the keyboard (Tab, Enter) to test.

Project 179: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - FAQ</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Frequently asked questions</h1>
    <details open>
      <summary>How do I book a service?</summary>
      <p>Use the contact form or call us. Popular services fill up
quickly.</p>
    </details>
    <details>
      <summary>Where are you located?</summary>
      <p>We are in Mansoura. Parking is available nearby.</p>
    </details>
    <details>
      <summary>Do you offer discounts?</summary>
      <p>Students and groups of four or more get 10 percent off.</p>
    </details>
    <details>
      <summary>Can I cancel?</summary>
      <p>Yes, up to 24 hours before, free of charge.</p>
    </details>
  </main>
</body>
</html>
```

Project 179: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
details { border: 1px solid var(--line); border-radius: 10px; margin-
bottom: .75rem; background: #fff; }
summary { padding: .9rem 1.1rem; cursor: pointer; font-weight: 600;
list-style: none; display: flex; justify-content: space-between; }
summary::-webkit-details-marker { display: none; }
summary::after { content: "+"; color: var(--brand); font-size: 1.3rem;
 line-height: 1; }
```

```
details[open] summary::after { content: "\2212"; }
details[open] summary { border-bottom: 1px solid var(--line);
background: var(--accent); }
details p { padding: 0 1.1rem 1rem; margin: .75rem 0 0; }
```

Project 179 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - FAQ</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Frequently asked questions	The main heading; only one per page.
<details open>	Disclosure widget that can be opened and closed.
<summary>How do I book a service?</summary>	The always-visible heading of a details element.
<p>Use the contact form or call us. Popular services fill up quickl...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
background: #fff;	Background colour or image.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-weight: 600;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
display: none;	Removes the element from rendering completely.
summary::after {	Generated content inserted after the element's content.
content: "+";	The text or empty string for a pseudo-element.
font-size: 1.3rem;	Size of the text.
details[open] summary::after {	Attribute selector: a details or dialog that is open.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.

Check your work

- Summary is the first child
- Works with keyboard
- Only summary is clickable, not the answer
- Indicator changes when open

Exercises

1. Use the name attribute so only one item can be open at once.
2. Animate the opening with interpolate-size or a max-height transition.
3. Add a search box that filters questions with JavaScript.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 180: FAQ accordion for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 2 | Files: index.html, styles.css

Brief

Build an accordion of questions and answers with no JavaScript using details and summary, with a custom plus/minus indicator.

Learning goals

- Use details/summary for native disclosure
- Style the open state with the [open] attribute selector
- Replace the default marker

Elements and CSS used

HTML elements	CSS features
details, summary, p, h1	[open], ::after, content, list-style: none, cursor: pointer, border-radius

Build guide

1. Write one <details> per question; the question goes in <summary>.
2. Add open to the first one so it starts expanded.
3. Remove the default triangle marker.
4. Add a plus sign with summary::after and a minus when open.
5. Give the open summary a background and border.
6. Click and use the keyboard (Tab, Enter) to test.

Project 180: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - FAQ</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Frequently asked questions</h1>
    <details open>
      <summary>How do I book a tour?</summary>
      <p>Use the contact form or call us. Popular tours fill up
quickly.</p>
    </details>
    <details>
      <summary>Where are you located?</summary>
      <p>We are in Hurghada. Parking is available nearby.</p>
    </details>
    <details>
      <summary>Do you offer discounts?</summary>
      <p>Students and groups of four or more get 10 percent off.</p>
    </details>
    <details>
      <summary>Can I cancel?</summary>
      <p>Yes, up to 24 hours before, free of charge.</p>
    </details>
  </main>
</body>
</html>
```

Project 180: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
details { border: 1px solid var(--line); border-radius: 10px; margin-
bottom: .75rem; background: #fff; }
summary { padding: .9rem 1.1rem; cursor: pointer; font-weight: 600;
list-style: none; display: flex; justify-content: space-between; }
summary::-webkit-details-marker { display: none; }
summary::after { content: "+"; color: var(--brand); font-size: 1.3rem;
 line-height: 1; }
```

```
details[open] summary::after { content: "\2212"; }
details[open] summary { border-bottom: 1px solid var(--line);
background: var(--accent); }
details p { padding: 0 1.1rem 1rem; margin: .75rem 0 0; }
```

Project 180 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - FAQ</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Frequently asked questions	The main heading; only one per page.
<details open>	Disclosure widget that can be opened and closed.
<summary>How do I book a tour?</summary>	The always-visible heading of a details element.
Use the contact form or call us. Popular tours fill up quickly.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
background: #fff;	Background colour or image.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-weight: 600;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
display: none;	Removes the element from rendering completely.
summary::after {	Generated content inserted after the element's content.
content: "+";	The text or empty string for a pseudo-element.
font-size: 1.3rem;	Size of the text.
details[open] summary::after {	Attribute selector: a details or dialog that is open.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.

Check your work

- Summary is the first child
- Works with keyboard
- Only summary is clickable, not the answer
- Indicator changes when open

Exercises

1. Use the name attribute so only one item can be open at once.
2. Animate the opening with interpolate-size or a max-height transition.
3. Add a search box that filters questions with JavaScript.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 181: FAQ accordion for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Build an accordion of questions and answers with no JavaScript using details and summary, with a custom plus/minus indicator.

Learning goals

- Use details/summary for native disclosure
- Style the open state with the [open] attribute selector
- Replace the default marker

Elements and CSS used

HTML elements	CSS features
details, summary, p, h1	[open], ::after, content, list-style: none, cursor: pointer, border-radius

Build guide

1. Write one <details> per question; the question goes in <summary>.
2. Add open to the first one so it starts expanded.
3. Remove the default triangle marker.
4. Add a plus sign with summary::after and a minus when open.
5. Give the open summary a background and border.
6. Click and use the keyboard (Tab, Enter) to test.

Project 181: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - FAQ</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Frequently asked questions</h1>
    <details open>
      <summary>How do I book a course?</summary>
      <p>Use the contact form or call us. Popular courses fill up
quickly.</p>
    </details>
    <details>
      <summary>Where are you located?</summary>
      <p>We are in Alexandria. Parking is available nearby.</p>
    </details>
    <details>
      <summary>Do you offer discounts?</summary>
      <p>Students and groups of four or more get 10 percent off.</p>
    </details>
    <details>
      <summary>Can I cancel?</summary>
      <p>Yes, up to 24 hours before, free of charge.</p>
    </details>
  </main>
</body>
</html>
```

Project 181: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
details { border: 1px solid var(--line); border-radius: 10px; margin-
bottom: .75rem; background: #fff; }
summary { padding: .9rem 1.1rem; cursor: pointer; font-weight: 600;
list-style: none; display: flex; justify-content: space-between; }
summary::-webkit-details-marker { display: none; }
summary::after { content: "+"; color: var(--brand); font-size: 1.3rem;
 line-height: 1; }
```

```
details[open] summary::after { content: "\2212"; }
details[open] summary { border-bottom: 1px solid var(--line);
background: var(--accent); }
details p { padding: 0 1.1rem 1rem; margin: .75rem 0 0; }
```

Project 181 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - FAQ</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Frequently asked questions	The main heading; only one per page.
<details open>	Disclosure widget that can be opened and closed.
<summary>How do I book a course?</summary>	The always-visible heading of a details element.
<p>Use the contact form or call us. Popular courses fill up quickly...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
background: #fff;	Background colour or image.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-weight: 600;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
display: none;	Removes the element from rendering completely.
summary::after {	Generated content inserted after the element's content.
content: "+";	The text or empty string for a pseudo-element.
font-size: 1.3rem;	Size of the text.
details[open] summary::after {	Attribute selector: a details or dialog that is open.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.

Check your work

- Summary is the first child
- Works with keyboard
- Only summary is clickable, not the answer
- Indicator changes when open

Exercises

1. Use the name attribute so only one item can be open at once.
2. Animate the opening with interpolate-size or a max-height transition.
3. Add a search box that filters questions with JavaScript.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 182: FAQ accordion for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 2 | Files: index.html, styles.css

Brief

Build an accordion of questions and answers with no JavaScript using details and summary, with a custom plus/minus indicator.

Learning goals

- Use details/summary for native disclosure
- Style the open state with the [open] attribute selector
- Replace the default marker

Elements and CSS used

HTML elements	CSS features
details, summary, p, h1	[open], ::after, content, list-style: none, cursor: pointer, border-radius

Build guide

1. Write one <details> per question; the question goes in <summary>.
2. Add open to the first one so it starts expanded.
3. Remove the default triangle marker.
4. Add a plus sign with summary::after and a minus when open.
5. Give the open summary a background and border.
6. Click and use the keyboard (Tab, Enter) to test.

Project 182: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - FAQ</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Frequently asked questions</h1>
    <details open>
      <summary>How do I book a drink?</summary>
      <p>Use the contact form or call us. Popular drinks fill up
quickly.</p>
    </details>
    <details>
      <summary>Where are you located?</summary>
      <p>We are in Zamalek. Parking is available nearby.</p>
    </details>
    <details>
      <summary>Do you offer discounts?</summary>
      <p>Students and groups of four or more get 10 percent off.</p>
    </details>
    <details>
      <summary>Can I cancel?</summary>
      <p>Yes, up to 24 hours before, free of charge.</p>
    </details>
  </main>
</body>
</html>
```

Project 182: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
details { border: 1px solid var(--line); border-radius: 10px; margin-
bottom: .75rem; background: #fff; }
summary { padding: .9rem 1.1rem; cursor: pointer; font-weight: 600;
list-style: none; display: flex; justify-content: space-between; }
summary::-webkit-details-marker { display: none; }
summary::after { content: "+"; color: var(--brand); font-size: 1.3rem;
 line-height: 1; }
```

```
details[open] summary::after { content: "\2212"; }
details[open] summary { border-bottom: 1px solid var(--line);
background: var(--accent); }
details p { padding: 0 1.1rem 1rem; margin: .75rem 0 0; }
```

Project 182 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - FAQ</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Frequently asked questions	The main heading; only one per page.
<details open>	Disclosure widget that can be opened and closed.
<summary>How do I book a drink?</summary>	The always-visible heading of a details element.
<p>Use the contact form or call us. Popular drinks fill up quickly....	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
background: #fff;	Background colour or image.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-weight: 600;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
display: none;	Removes the element from rendering completely.
summary::after {	Generated content inserted after the element's content.
content: "+";	The text or empty string for a pseudo-element.
font-size: 1.3rem;	Size of the text.
details[open] summary::after {	Attribute selector: a details or dialog that is open.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.

Check your work

- Summary is the first child
- Works with keyboard
- Only summary is clickable, not the answer
- Indicator changes when open

Exercises

1. Use the name attribute so only one item can be open at once.
2. Animate the opening with interpolate-size or a max-height transition.
3. Add a search box that filters questions with JavaScript.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 183: FAQ accordion for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 2 | Files: index.html, styles.css

Brief

Build an accordion of questions and answers with no JavaScript using details and summary, with a custom plus/minus indicator.

Learning goals

- Use details/summary for native disclosure
- Style the open state with the [open] attribute selector
- Replace the default marker

Elements and CSS used

HTML elements	CSS features
details, summary, p, h1	[open], ::after, content, list-style: none, cursor: pointer, border-radius

Build guide

1. Write one <details> per question; the question goes in <summary>.
2. Add open to the first one so it starts expanded.
3. Remove the default triangle marker.
4. Add a plus sign with summary::after and a minus when open.
5. Give the open summary a background and border.
6. Click and use the keyboard (Tab, Enter) to test.

Project 183: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - FAQ</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Frequently asked questions</h1>
    <details open>
      <summary>How do I book a hike?</summary>
      <p>Use the contact form or call us. Popular hikes fill up
quickly.</p>
    </details>
    <details>
      <summary>Where are you located?</summary>
      <p>We are in Saint Catherine. Parking is available nearby.</p>
    </details>
    <details>
      <summary>Do you offer discounts?</summary>
      <p>Students and groups of four or more get 10 percent off.</p>
    </details>
    <details>
      <summary>Can I cancel?</summary>
      <p>Yes, up to 24 hours before, free of charge.</p>
    </details>
  </main>
</body>
</html>
```

Project 183: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
details { border: 1px solid var(--line); border-radius: 10px; margin-
bottom: .75rem; background: #fff; }
summary { padding: .9rem 1.1rem; cursor: pointer; font-weight: 600;
list-style: none; display: flex; justify-content: space-between; }
summary::-webkit-details-marker { display: none; }
summary::after { content: "+"; color: var(--brand); font-size: 1.3rem;
 line-height: 1; }
```

```
details[open] summary::after { content: "\2212"; }
details[open] summary { border-bottom: 1px solid var(--line);
background: var(--accent); }
details p { padding: 0 1.1rem 1rem; margin: .75rem 0 0; }
```

Project 183 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - FAQ</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Frequently asked questions	The main heading; only one per page.
<details open>	Disclosure widget that can be opened and closed.
<summary>How do I book a hike?</summary>	The always-visible heading of a details element.
Use the contact form or call us. Popular hikes fill up quickly.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
background: #fff;	Background colour or image.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-weight: 600;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
display: none;	Removes the element from rendering completely.
summary::after {	Generated content inserted after the element's content.
content: "+";	The text or empty string for a pseudo-element.
font-size: 1.3rem;	Size of the text.
details[open] summary::after {	Attribute selector: a details or dialog that is open.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.

Check your work

- Summary is the first child
- Works with keyboard
- Only summary is clickable, not the answer
- Indicator changes when open

Exercises

1. Use the name attribute so only one item can be open at once.
2. Animate the opening with interpolate-size or a max-height transition.
3. Add a search box that filters questions with JavaScript.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 184: FAQ accordion for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 2 | Files: index.html, styles.css

Brief

Build an accordion of questions and answers with no JavaScript using details and summary, with a custom plus/minus indicator.

Learning goals

- Use details/summary for native disclosure
- Style the open state with the [open] attribute selector
- Replace the default marker

Elements and CSS used

HTML elements	CSS features
details, summary, p, h1	[open], ::after, content, list-style: none, cursor: pointer, border-radius

Build guide

1. Write one <details> per question; the question goes in <summary>.
2. Add open to the first one so it starts expanded.
3. Remove the default triangle marker.
4. Add a plus sign with summary::after and a minus when open.
5. Give the open summary a background and border.
6. Click and use the keyboard (Tab, Enter) to test.

Project 184: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - FAQ</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Frequently asked questions</h1>
    <details open>
      <summary>How do I book a session?</summary>
      <p>Use the contact form or call us. Popular sessions fill up
quickly.</p>
    </details>
    <details>
      <summary>Where are you located?</summary>
      <p>We are in Maadi. Parking is available nearby.</p>
    </details>
    <details>
      <summary>Do you offer discounts?</summary>
      <p>Students and groups of four or more get 10 percent off.</p>
    </details>
    <details>
      <summary>Can I cancel?</summary>
      <p>Yes, up to 24 hours before, free of charge.</p>
    </details>
  </main>
</body>
</html>
```

Project 184: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
details { border: 1px solid var(--line); border-radius: 10px; margin-
bottom: .75rem; background: #fff; }
summary { padding: .9rem 1.1rem; cursor: pointer; font-weight: 600;
list-style: none; display: flex; justify-content: space-between; }
summary::-webkit-details-marker { display: none; }
summary::after { content: "+"; color: var(--brand); font-size: 1.3rem;
 line-height: 1; }
```

```
details[open] summary::after { content: "\2212"; }
details[open] summary { border-bottom: 1px solid var(--line);
background: var(--accent); }
details p { padding: 0 1.1rem 1rem; margin: .75rem 0 0; }
```

Project 184 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - FAQ</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Frequently asked questions	The main heading; only one per page.
<details open>	Disclosure widget that can be opened and closed.
<summary>How do I book a session?</summary>	The always-visible heading of a details element.
<p>Use the contact form or call us. Popular sessions fill up quickl...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
background: #fff;	Background colour or image.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-weight: 600;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
display: none;	Removes the element from rendering completely.
summary::after {	Generated content inserted after the element's content.
content: "+";	The text or empty string for a pseudo-element.
font-size: 1.3rem;	Size of the text.
details[open] summary::after {	Attribute selector: a details or dialog that is open.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.

Check your work

- Summary is the first child
- Works with keyboard
- Only summary is clickable, not the answer
- Indicator changes when open

Exercises

1. Use the name attribute so only one item can be open at once.
2. Animate the opening with interpolate-size or a max-height transition.
3. Add a search box that filters questions with JavaScript.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 185: FAQ accordion for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 2 | Files: index.html, styles.css

Brief

Build an accordion of questions and answers with no JavaScript using details and summary, with a custom plus/minus indicator.

Learning goals

- Use details/summary for native disclosure
- Style the open state with the [open] attribute selector
- Replace the default marker

Elements and CSS used

HTML elements	CSS features
details, summary, p, h1	[open], ::after, content, list-style: none, cursor: pointer, border-radius

Build guide

1. Write one <details> per question; the question goes in <summary>.
2. Add open to the first one so it starts expanded.
3. Remove the default triangle marker.
4. Add a plus sign with summary::after and a minus when open.
5. Give the open summary a background and border.
6. Click and use the keyboard (Tab, Enter) to test.

Project 185: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - FAQ</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Frequently asked questions</h1>
    <details open>
      <summary>How do I book a product?</summary>
      <p>Use the contact form or call us. Popular products fill up
quickly.</p>
    </details>
    <details>
      <summary>Where are you located?</summary>
      <p>We are in Heliopolis. Parking is available nearby.</p>
    </details>
    <details>
      <summary>Do you offer discounts?</summary>
      <p>Students and groups of four or more get 10 percent off.</p>
    </details>
    <details>
      <summary>Can I cancel?</summary>
      <p>Yes, up to 24 hours before, free of charge.</p>
    </details>
  </main>
</body>
</html>
```

Project 185: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
details { border: 1px solid var(--line); border-radius: 10px; margin-
bottom: .75rem; background: #fff; }
summary { padding: .9rem 1.1rem; cursor: pointer; font-weight: 600;
list-style: none; display: flex; justify-content: space-between; }
summary::-webkit-details-marker { display: none; }
summary::after { content: "+"; color: var(--brand); font-size: 1.3rem;
 line-height: 1; }
```

```
details[open] summary::after { content: "\2212"; }
details[open] summary { border-bottom: 1px solid var(--line);
background: var(--accent); }
details p { padding: 0 1.1rem 1rem; margin: .75rem 0 0; }
```

Project 185 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - FAQ</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Frequently asked questions	The main heading; only one per page.
<details open>	Disclosure widget that can be opened and closed.
<summary>How do I book a product?</summary>	The always-visible heading of a details element.
<p>Use the contact form or call us. Popular products fill up quickl...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
background: #fff;	Background colour or image.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-weight: 600;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
display: none;	Removes the element from rendering completely.
summary::after {	Generated content inserted after the element's content.
content: "+";	The text or empty string for a pseudo-element.
font-size: 1.3rem;	Size of the text.
details[open] summary::after {	Attribute selector: a details or dialog that is open.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.

Check your work

- Summary is the first child
- Works with keyboard
- Only summary is clickable, not the answer
- Indicator changes when open

Exercises

1. Use the name attribute so only one item can be open at once.
2. Animate the opening with interpolate-size or a max-height transition.
3. Add a search box that filters questions with JavaScript.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 186: FAQ accordion for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 2 | Files: index.html, styles.css

Brief

Build an accordion of questions and answers with no JavaScript using details and summary, with a custom plus/minus indicator.

Learning goals

- Use details/summary for native disclosure
- Style the open state with the [open] attribute selector
- Replace the default marker

Elements and CSS used

HTML elements	CSS features
details, summary, p, h1	[open], ::after, content, list-style: none, cursor: pointer, border-radius

Build guide

1. Write one <details> per question; the question goes in <summary>.
2. Add open to the first one so it starts expanded.
3. Remove the default triangle marker.
4. Add a plus sign with summary::after and a minus when open.
5. Give the open summary a background and border.
6. Click and use the keyboard (Tab, Enter) to test.

Project 186: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - FAQ</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Frequently asked questions</h1>
    <details open>
      <summary>How do I book a plant?</summary>
      <p>Use the contact form or call us. Popular plants fill up
quickly.</p>
    </details>
    <details>
      <summary>Where are you located?</summary>
      <p>We are in Sheikh Zayed. Parking is available nearby.</p>
    </details>
    <details>
      <summary>Do you offer discounts?</summary>
      <p>Students and groups of four or more get 10 percent off.</p>
    </details>
    <details>
      <summary>Can I cancel?</summary>
      <p>Yes, up to 24 hours before, free of charge.</p>
    </details>
  </main>
</body>
</html>
```

Project 186: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
details { border: 1px solid var(--line); border-radius: 10px; margin-
bottom: .75rem; background: #fff; }
summary { padding: .9rem 1.1rem; cursor: pointer; font-weight: 600;
list-style: none; display: flex; justify-content: space-between; }
summary::-webkit-details-marker { display: none; }
summary::after { content: "+"; color: var(--brand); font-size: 1.3rem;
 line-height: 1; }
```

```
details[open] summary::after { content: "\2212"; }
details[open] summary { border-bottom: 1px solid var(--line);
background: var(--accent); }
details p { padding: 0 1.1rem 1rem; margin: .75rem 0 0; }
```

Project 186 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - FAQ</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Frequently asked questions	The main heading; only one per page.
<details open>	Disclosure widget that can be opened and closed.
<summary>How do I book a plant?</summary>	The always-visible heading of a details element.
<p>Use the contact form or call us. Popular plants fill up quickly....	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
background: #fff;	Background colour or image.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-weight: 600;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
display: none;	Removes the element from rendering completely.
summary::after {	Generated content inserted after the element's content.
content: "+";	The text or empty string for a pseudo-element.
font-size: 1.3rem;	Size of the text.
details[open] summary::after {	Attribute selector: a details or dialog that is open.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.

Check your work

- Summary is the first child
- Works with keyboard
- Only summary is clickable, not the answer
- Indicator changes when open

Exercises

1. Use the name attribute so only one item can be open at once.
2. Animate the opening with interpolate-size or a max-height transition.
3. Add a search box that filters questions with JavaScript.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 187: FAQ accordion for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 2 | Files: index.html, styles.css

Brief

Build an accordion of questions and answers with no JavaScript using details and summary, with a custom plus/minus indicator.

Learning goals

- Use details/summary for native disclosure
- Style the open state with the [open] attribute selector
- Replace the default marker

Elements and CSS used

HTML elements	CSS features
details, summary, p, h1	[open], ::after, content, list-style: none, cursor: pointer, border-radius

Build guide

1. Write one <details> per question; the question goes in <summary>.
2. Add open to the first one so it starts expanded.
3. Remove the default triangle marker.
4. Add a plus sign with summary::after and a minus when open.
5. Give the open summary a background and border.
6. Click and use the keyboard (Tab, Enter) to test.

Project 187: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - FAQ</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Frequently asked questions</h1>
    <details open>
      <summary>How do I book a piece?</summary>
      <p>Use the contact form or call us. Popular pieces fill up
quickly.</p>
    </details>
    <details>
      <summary>Where are you located?</summary>
      <p>We are in Damietta. Parking is available nearby.</p>
    </details>
    <details>
      <summary>Do you offer discounts?</summary>
      <p>Students and groups of four or more get 10 percent off.</p>
    </details>
    <details>
      <summary>Can I cancel?</summary>
      <p>Yes, up to 24 hours before, free of charge.</p>
    </details>
  </main>
</body>
</html>
```

Project 187: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
details { border: 1px solid var(--line); border-radius: 10px; margin-
bottom: .75rem; background: #fff; }
summary { padding: .9rem 1.1rem; cursor: pointer; font-weight: 600;
list-style: none; display: flex; justify-content: space-between; }
summary::-webkit-details-marker { display: none; }
summary::after { content: "+"; color: var(--brand); font-size: 1.3rem;
 line-height: 1; }
```

```
details[open] summary::after { content: "\2212"; }
details[open] summary { border-bottom: 1px solid var(--line);
background: var(--accent); }
details p { padding: 0 1.1rem 1rem; margin: .75rem 0 0; }
```

Project 187 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - FAQ</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Frequently asked questions	The main heading; only one per page.
<details open>	Disclosure widget that can be opened and closed.
<summary>How do I book a piece?</summary>	The always-visible heading of a details element.
<p>Use the contact form or call us. Popular pieces fill up quickly....	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
background: #fff;	Background colour or image.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-weight: 600;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
display: none;	Removes the element from rendering completely.
summary::after {	Generated content inserted after the element's content.
content: "+";	The text or empty string for a pseudo-element.
font-size: 1.3rem;	Size of the text.
details[open] summary::after {	Attribute selector: a details or dialog that is open.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.

Check your work

- Summary is the first child
- Works with keyboard
- Only summary is clickable, not the answer
- Indicator changes when open

Exercises

1. Use the name attribute so only one item can be open at once.
2. Animate the opening with interpolate-size or a max-height transition.
3. Add a search box that filters questions with JavaScript.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 188: FAQ accordion for Byte Repair

Theme: Byte Repair (Nasr City) | Level 2 | Files: index.html, styles.css

Brief

Build an accordion of questions and answers with no JavaScript using details and summary, with a custom plus/minus indicator.

Learning goals

- Use details/summary for native disclosure
- Style the open state with the [open] attribute selector
- Replace the default marker

Elements and CSS used

HTML elements	CSS features
details, summary, p, h1	[open], ::after, content, list-style: none, cursor: pointer, border-radius

Build guide

1. Write one <details> per question; the question goes in <summary>.
2. Add open to the first one so it starts expanded.
3. Remove the default triangle marker.
4. Add a plus sign with summary::after and a minus when open.
5. Give the open summary a background and border.
6. Click and use the keyboard (Tab, Enter) to test.

Project 188: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - FAQ</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Frequently asked questions</h1>
    <details open>
      <summary>How do I book a repair?</summary>
      <p>Use the contact form or call us. Popular repairs fill up
quickly.</p>
    </details>
    <details>
      <summary>Where are you located?</summary>
      <p>We are in Nasr City. Parking is available nearby.</p>
    </details>
    <details>
      <summary>Do you offer discounts?</summary>
      <p>Students and groups of four or more get 10 percent off.</p>
    </details>
    <details>
      <summary>Can I cancel?</summary>
      <p>Yes, up to 24 hours before, free of charge.</p>
    </details>
  </main>
</body>
</html>
```

Project 188: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
details { border: 1px solid var(--line); border-radius: 10px; margin-
bottom: .75rem; background: #fff; }
summary { padding: .9rem 1.1rem; cursor: pointer; font-weight: 600;
list-style: none; display: flex; justify-content: space-between; }
summary::-webkit-details-marker { display: none; }
summary::after { content: "+"; color: var(--brand); font-size: 1.3rem;
 line-height: 1; }
```

```
details[open] summary::after { content: "\2212"; }
details[open] summary { border-bottom: 1px solid var(--line);
background: var(--accent); }
details p { padding: 0 1.1rem 1rem; margin: .75rem 0 0; }
```

Project 188 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - FAQ</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Frequently asked questions	The main heading; only one per page.
<details open>	Disclosure widget that can be opened and closed.
<summary>How do I book a repair?</summary>	The always-visible heading of a details element.
<p>Use the contact form or call us. Popular repairs fill up quickly...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
background: #fff;	Background colour or image.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-weight: 600;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
display: none;	Removes the element from rendering completely.
summary::after {	Generated content inserted after the element's content.
content: "+";	The text or empty string for a pseudo-element.
font-size: 1.3rem;	Size of the text.
details[open] summary::after {	Attribute selector: a details or dialog that is open.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.

Check your work

- Summary is the first child
- Works with keyboard
- Only summary is clickable, not the answer
- Indicator changes when open

Exercises

1. Use the name attribute so only one item can be open at once.
2. Animate the opening with interpolate-size or a max-height transition.
3. Add a search box that filters questions with JavaScript.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 189: FAQ accordion for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 2 | Files: index.html, styles.css

Brief

Build an accordion of questions and answers with no JavaScript using details and summary, with a custom plus/minus indicator.

Learning goals

- Use details/summary for native disclosure
- Style the open state with the [open] attribute selector
- Replace the default marker

Elements and CSS used

HTML elements	CSS features
details, summary, p, h1	[open], ::after, content, list-style: none, cursor: pointer, border-radius

Build guide

1. Write one <details> per question; the question goes in <summary>.
2. Add open to the first one so it starts expanded.
3. Remove the default triangle marker.
4. Add a plus sign with summary::after and a minus when open.
5. Give the open summary a background and border.
6. Click and use the keyboard (Tab, Enter) to test.

Project 189: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - FAQ</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Frequently asked questions</h1>
    <details open>
      <summary>How do I book a service?</summary>
      <p>Use the contact form or call us. Popular services fill up
quickly.</p>
    </details>
    <details>
      <summary>Where are you located?</summary>
      <p>We are in New Cairo. Parking is available nearby.</p>
    </details>
    <details>
      <summary>Do you offer discounts?</summary>
      <p>Students and groups of four or more get 10 percent off.</p>
    </details>
    <details>
      <summary>Can I cancel?</summary>
      <p>Yes, up to 24 hours before, free of charge.</p>
    </details>
  </main>
</body>
</html>
```

Project 189: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
details { border: 1px solid var(--line); border-radius: 10px; margin-
bottom: .75rem; background: #fff; }
summary { padding: .9rem 1.1rem; cursor: pointer; font-weight: 600;
list-style: none; display: flex; justify-content: space-between; }
summary::-webkit-details-marker { display: none; }
summary::after { content: "+"; color: var(--brand); font-size: 1.3rem;
 line-height: 1; }
```

```
details[open] summary::after { content: "\2212"; }
details[open] summary { border-bottom: 1px solid var(--line);
background: var(--accent); }
details p { padding: 0 1.1rem 1rem; margin: .75rem 0 0; }
```

Project 189 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - FAQ</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Frequently asked questions	The main heading; only one per page.
<details open>	Disclosure widget that can be opened and closed.
<summary>How do I book a service?</summary>	The always-visible heading of a details element.
<p>Use the contact form or call us. Popular services fill up quickl...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
background: #fff;	Background colour or image.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-weight: 600;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
display: none;	Removes the element from rendering completely.
summary::after {	Generated content inserted after the element's content.
content: "+";	The text or empty string for a pseudo-element.
font-size: 1.3rem;	Size of the text.
details[open] summary::after {	Attribute selector: a details or dialog that is open.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.

Check your work

- Summary is the first child
- Works with keyboard
- Only summary is clickable, not the answer
- Indicator changes when open

Exercises

1. Use the name attribute so only one item can be open at once.
2. Animate the opening with interpolate-size or a max-height transition.
3. Add a search box that filters questions with JavaScript.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 190: FAQ accordion for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Build an accordion of questions and answers with no JavaScript using details and summary, with a custom plus/minus indicator.

Learning goals

- Use details/summary for native disclosure
- Style the open state with the [open] attribute selector
- Replace the default marker

Elements and CSS used

HTML elements	CSS features
details, summary, p, h1	[open], ::after, content, list-style: none, cursor: pointer, border-radius

Build guide

1. Write one <details> per question; the question goes in <summary>.
2. Add open to the first one so it starts expanded.
3. Remove the default triangle marker.
4. Add a plus sign with summary::after and a minus when open.
5. Give the open summary a background and border.
6. Click and use the keyboard (Tab, Enter) to test.

Project 190: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - FAQ</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Frequently asked questions</h1>
    <details open>
      <summary>How do I book a lesson?</summary>
      <p>Use the contact form or call us. Popular lessons fill up
quickly.</p>
    </details>
    <details>
      <summary>Where are you located?</summary>
      <p>We are in Alexandria. Parking is available nearby.</p>
    </details>
    <details>
      <summary>Do you offer discounts?</summary>
      <p>Students and groups of four or more get 10 percent off.</p>
    </details>
    <details>
      <summary>Can I cancel?</summary>
      <p>Yes, up to 24 hours before, free of charge.</p>
    </details>
  </main>
</body>
</html>
```

Project 190: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
details { border: 1px solid var(--line); border-radius: 10px; margin-
bottom: .75rem; background: #fff; }
summary { padding: .9rem 1.1rem; cursor: pointer; font-weight: 600;
list-style: none; display: flex; justify-content: space-between; }
summary::-webkit-details-marker { display: none; }
summary::after { content: "+"; color: var(--brand); font-size: 1.3rem;
 line-height: 1; }
```

```
details[open] summary::after { content: "\2212"; }
details[open] summary { border-bottom: 1px solid var(--line);
background: var(--accent); }
details p { padding: 0 1.1rem 1rem; margin: .75rem 0 0; }
```

Project 190 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - FAQ</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Frequently asked questions	The main heading; only one per page.
<details open>	Disclosure widget that can be opened and closed.
<summary>How do I book a lesson?</summary>	The always-visible heading of a details element.
<p>Use the contact form or call us. Popular lessons fill up quickly...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
background: #fff;	Background colour or image.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-weight: 600;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
display: none;	Removes the element from rendering completely.
summary::after {	Generated content inserted after the element's content.
content: "+";	The text or empty string for a pseudo-element.
font-size: 1.3rem;	Size of the text.
details[open] summary::after {	Attribute selector: a details or dialog that is open.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.

Check your work

- Summary is the first child
- Works with keyboard
- Only summary is clickable, not the answer
- Indicator changes when open

Exercises

1. Use the name attribute so only one item can be open at once.
2. Animate the opening with interpolate-size or a max-height transition.
3. Add a search box that filters questions with JavaScript.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 191: FAQ accordion for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Build an accordion of questions and answers with no JavaScript using details and summary, with a custom plus/minus indicator.

Learning goals

- Use details/summary for native disclosure
- Style the open state with the [open] attribute selector
- Replace the default marker

Elements and CSS used

HTML elements	CSS features
details, summary, p, h1	[open], ::after, content, list-style: none, cursor: pointer, border-radius

Build guide

1. Write one <details> per question; the question goes in <summary>.
2. Add open to the first one so it starts expanded.
3. Remove the default triangle marker.
4. Add a plus sign with summary::after and a minus when open.
5. Give the open summary a background and border.
6. Click and use the keyboard (Tab, Enter) to test.

Project 191: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - FAQ</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Frequently asked questions</h1>
    <details open>
      <summary>How do I book a item?</summary>
      <p>Use the contact form or call us. Popular items fill up
quickly.</p>
    </details>
    <details>
      <summary>Where are you located?</summary>
      <p>We are in Aswan. Parking is available nearby.</p>
    </details>
    <details>
      <summary>Do you offer discounts?</summary>
      <p>Students and groups of four or more get 10 percent off.</p>
    </details>
    <details>
      <summary>Can I cancel?</summary>
      <p>Yes, up to 24 hours before, free of charge.</p>
    </details>
  </main>
</body>
</html>
```

Project 191: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
details { border: 1px solid var(--line); border-radius: 10px; margin-
bottom: .75rem; background: #fff; }
summary { padding: .9rem 1.1rem; cursor: pointer; font-weight: 600;
list-style: none; display: flex; justify-content: space-between; }
summary::-webkit-details-marker { display: none; }
summary::after { content: "+"; color: var(--brand); font-size: 1.3rem;
 line-height: 1; }
```

```
details[open] summary::after { content: "\2212"; }
details[open] summary { border-bottom: 1px solid var(--line);
background: var(--accent); }
details p { padding: 0 1.1rem 1rem; margin: .75rem 0 0; }
```

Project 191 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - FAQ</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Frequently asked questions	The main heading; only one per page.
<details open>	Disclosure widget that can be opened and closed.
<summary>How do I book a item?</summary>	The always-visible heading of a details element.
Use the contact form or call us. Popular items fill up quickly.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
background: #fff;	Background colour or image.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-weight: 600;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
display: none;	Removes the element from rendering completely.
summary::after {	Generated content inserted after the element's content.
content: "+";	The text or empty string for a pseudo-element.
font-size: 1.3rem;	Size of the text.
details[open] summary::after {	Attribute selector: a details or dialog that is open.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.

Check your work

- Summary is the first child
- Works with keyboard
- Only summary is clickable, not the answer
- Indicator changes when open

Exercises

1. Use the name attribute so only one item can be open at once.
2. Animate the opening with interpolate-size or a max-height transition.
3. Add a search box that filters questions with JavaScript.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 192: FAQ accordion for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 2 | Files: index.html, styles.css

Brief

Build an accordion of questions and answers with no JavaScript using details and summary, with a custom plus/minus indicator.

Learning goals

- Use details/summary for native disclosure
- Style the open state with the [open] attribute selector
- Replace the default marker

Elements and CSS used

HTML elements	CSS features
details, summary, p, h1	[open], ::after, content, list-style: none, cursor: pointer, border-radius

Build guide

1. Write one <details> per question; the question goes in <summary>.
2. Add open to the first one so it starts expanded.
3. Remove the default triangle marker.
4. Add a plus sign with summary::after and a minus when open.
5. Give the open summary a background and border.
6. Click and use the keyboard (Tab, Enter) to test.

Project 192: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - FAQ</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Frequently asked questions</h1>
    <details open>
      <summary>How do I book a workshop?</summary>
      <p>Use the contact form or call us. Popular workshops fill up
quickly.</p>
    </details>
    <details>
      <summary>Where are you located?</summary>
      <p>We are in Tunis Village. Parking is available nearby.</p>
    </details>
    <details>
      <summary>Do you offer discounts?</summary>
      <p>Students and groups of four or more get 10 percent off.</p>
    </details>
    <details>
      <summary>Can I cancel?</summary>
      <p>Yes, up to 24 hours before, free of charge.</p>
    </details>
  </main>
</body>
</html>
```

Project 192: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
details { border: 1px solid var(--line); border-radius: 10px; margin-
bottom: .75rem; background: #fff; }
summary { padding: .9rem 1.1rem; cursor: pointer; font-weight: 600;
list-style: none; display: flex; justify-content: space-between; }
summary::-webkit-details-marker { display: none; }
summary::after { content: "+"; color: var(--brand); font-size: 1.3rem;
 line-height: 1; }
```

```
details[open] summary::after { content: "\2212"; }
details[open] summary { border-bottom: 1px solid var(--line);
background: var(--accent); }
details p { padding: 0 1.1rem 1rem; margin: .75rem 0 0; }
```

Project 192 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - FAQ</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Frequently asked questions	The main heading; only one per page.
<details open>	Disclosure widget that can be opened and closed.
<summary>How do I book a workshop?</summary>	The always-visible heading of a details element.
<p>Use the contact form or call us. Popular workshops fill up quick...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
background: #fff;	Background colour or image.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-weight: 600;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
display: none;	Removes the element from rendering completely.
summary::after {	Generated content inserted after the element's content.
content: "+";	The text or empty string for a pseudo-element.
font-size: 1.3rem;	Size of the text.
details[open] summary::after {	Attribute selector: a details or dialog that is open.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.

Check your work

- Summary is the first child
- Works with keyboard
- Only summary is clickable, not the answer
- Indicator changes when open

Exercises

1. Use the name attribute so only one item can be open at once.
2. Animate the opening with interpolate-size or a max-height transition.
3. Add a search box that filters questions with JavaScript.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 193: FAQ accordion for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 2 | Files: index.html, styles.css

Brief

Build an accordion of questions and answers with no JavaScript using details and summary, with a custom plus/minus indicator.

Learning goals

- Use details/summary for native disclosure
- Style the open state with the [open] attribute selector
- Replace the default marker

Elements and CSS used

HTML elements	CSS features
details, summary, p, h1	[open], ::after, content, list-style: none, cursor: pointer, border-radius

Build guide

1. Write one <details> per question; the question goes in <summary>.
2. Add open to the first one so it starts expanded.
3. Remove the default triangle marker.
4. Add a plus sign with summary::after and a minus when open.
5. Give the open summary a background and border.
6. Click and use the keyboard (Tab, Enter) to test.

Project 193: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - FAQ</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Frequently asked questions</h1>
    <details open>
      <summary>How do I book a treatment?</summary>
      <p>Use the contact form or call us. Popular treatments fill up
quickly.</p>
    </details>
    <details>
      <summary>Where are you located?</summary>
      <p>We are in Dokki. Parking is available nearby.</p>
    </details>
    <details>
      <summary>Do you offer discounts?</summary>
      <p>Students and groups of four or more get 10 percent off.</p>
    </details>
    <details>
      <summary>Can I cancel?</summary>
      <p>Yes, up to 24 hours before, free of charge.</p>
    </details>
  </main>
</body>
</html>
```

Project 193: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
details { border: 1px solid var(--line); border-radius: 10px; margin-
bottom: .75rem; background: #fff; }
summary { padding: .9rem 1.1rem; cursor: pointer; font-weight: 600;
list-style: none; display: flex; justify-content: space-between; }
summary::-webkit-details-marker { display: none; }
summary::after { content: "+"; color: var(--brand); font-size: 1.3rem;
 line-height: 1; }
```

```
details[open] summary::after { content: "\2212"; }
details[open] summary { border-bottom: 1px solid var(--line);
background: var(--accent); }
details p { padding: 0 1.1rem 1rem; margin: .75rem 0 0; }
```

Project 193 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - FAQ</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Frequently asked questions	The main heading; only one per page.
<details open>	Disclosure widget that can be opened and closed.
<summary>How do I book a treatment?</summary>	The always-visible heading of a details element.
<p>Use the contact form or call us. Popular treatments fill up quic...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
background: #fff;	Background colour or image.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-weight: 600;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
display: none;	Removes the element from rendering completely.
summary::after {	Generated content inserted after the element's content.
content: "+";	The text or empty string for a pseudo-element.
font-size: 1.3rem;	Size of the text.
details[open] summary::after {	Attribute selector: a details or dialog that is open.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.

Check your work

- Summary is the first child
- Works with keyboard
- Only summary is clickable, not the answer
- Indicator changes when open

Exercises

1. Use the name attribute so only one item can be open at once.
2. Animate the opening with interpolate-size or a max-height transition.
3. Add a search box that filters questions with JavaScript.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 194: FAQ accordion for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 2 | Files: index.html, styles.css

Brief

Build an accordion of questions and answers with no JavaScript using details and summary, with a custom plus/minus indicator.

Learning goals

- Use details/summary for native disclosure
- Style the open state with the [open] attribute selector
- Replace the default marker

Elements and CSS used

HTML elements	CSS features
details, summary, p, h1	[open], ::after, content, list-style: none, cursor: pointer, border-radius

Build guide

1. Write one <details> per question; the question goes in <summary>.
2. Add open to the first one so it starts expanded.
3. Remove the default triangle marker.
4. Add a plus sign with summary::after and a minus when open.
5. Give the open summary a background and border.
6. Click and use the keyboard (Tab, Enter) to test.

Project 194: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - FAQ</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Frequently asked questions</h1>
    <details open>
      <summary>How do I book a service?</summary>
      <p>Use the contact form or call us. Popular services fill up
quickly.</p>
    </details>
    <details>
      <summary>Where are you located?</summary>
      <p>We are in Suez. Parking is available nearby.</p>
    </details>
    <details>
      <summary>Do you offer discounts?</summary>
      <p>Students and groups of four or more get 10 percent off.</p>
    </details>
    <details>
      <summary>Can I cancel?</summary>
      <p>Yes, up to 24 hours before, free of charge.</p>
    </details>
  </main>
</body>
</html>
```

Project 194: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
details { border: 1px solid var(--line); border-radius: 10px; margin-
bottom: .75rem; background: #fff; }
summary { padding: .9rem 1.1rem; cursor: pointer; font-weight: 600;
list-style: none; display: flex; justify-content: space-between; }
summary::-webkit-details-marker { display: none; }
summary::after { content: "+"; color: var(--brand); font-size: 1.3rem;
 line-height: 1; }
```

```
details[open] summary::after { content: "\2212"; }
details[open] summary { border-bottom: 1px solid var(--line);
background: var(--accent); }
details p { padding: 0 1.1rem 1rem; margin: .75rem 0 0; }
```

Project 194 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - FAQ</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Frequently asked questions	The main heading; only one per page.
<details open>	Disclosure widget that can be opened and closed.
<summary>How do I book a service?</summary>	The always-visible heading of a details element.
<p>Use the contact form or call us. Popular services fill up quickl...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
background: #fff;	Background colour or image.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-weight: 600;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
display: none;	Removes the element from rendering completely.
summary::after {	Generated content inserted after the element's content.
content: "+";	The text or empty string for a pseudo-element.
font-size: 1.3rem;	Size of the text.
details[open] summary::after {	Attribute selector: a details or dialog that is open.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.

Check your work

- Summary is the first child
- Works with keyboard
- Only summary is clickable, not the answer
- Indicator changes when open

Exercises

1. Use the name attribute so only one item can be open at once.
2. Animate the opening with interpolate-size or a max-height transition.
3. Add a search box that filters questions with JavaScript.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 195: FAQ accordion for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 2 | Files: index.html, styles.css

Brief

Build an accordion of questions and answers with no JavaScript using details and summary, with a custom plus/minus indicator.

Learning goals

- Use details/summary for native disclosure
- Style the open state with the [open] attribute selector
- Replace the default marker

Elements and CSS used

HTML elements	CSS features
details, summary, p, h1	[open], ::after, content, list-style: none, cursor: pointer, border-radius

Build guide

1. Write one <details> per question; the question goes in <summary>.
2. Add open to the first one so it starts expanded.
3. Remove the default triangle marker.
4. Add a plus sign with summary::after and a minus when open.
5. Give the open summary a background and border.
6. Click and use the keyboard (Tab, Enter) to test.

Project 195: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - FAQ</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Frequently asked questions</h1>
    <details open>
      <summary>How do I book a course?</summary>
      <p>Use the contact form or call us. Popular courses fill up
quickly.</p>
    </details>
    <details>
      <summary>Where are you located?</summary>
      <p>We are in Luxor. Parking is available nearby.</p>
    </details>
    <details>
      <summary>Do you offer discounts?</summary>
      <p>Students and groups of four or more get 10 percent off.</p>
    </details>
    <details>
      <summary>Can I cancel?</summary>
      <p>Yes, up to 24 hours before, free of charge.</p>
    </details>
  </main>
</body>
</html>
```

Project 195: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
details { border: 1px solid var(--line); border-radius: 10px; margin-
bottom: .75rem; background: #fff; }
summary { padding: .9rem 1.1rem; cursor: pointer; font-weight: 600;
list-style: none; display: flex; justify-content: space-between; }
summary::-webkit-details-marker { display: none; }
summary::after { content: "+"; color: var(--brand); font-size: 1.3rem;
 line-height: 1; }
```

```
details[open] summary::after { content: "\2212"; }
details[open] summary { border-bottom: 1px solid var(--line);
background: var(--accent); }
details p { padding: 0 1.1rem 1rem; margin: .75rem 0 0; }
```

Project 195 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - FAQ</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Frequently asked questions	The main heading; only one per page.
<details open>	Disclosure widget that can be opened and closed.
<summary>How do I book a course?</summary>	The always-visible heading of a details element.
<p>Use the contact form or call us. Popular courses fill up quickly...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
background: #fff;	Background colour or image.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-weight: 600;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
display: none;	Removes the element from rendering completely.
summary::after {	Generated content inserted after the element's content.
content: "+";	The text or empty string for a pseudo-element.
font-size: 1.3rem;	Size of the text.
details[open] summary::after {	Attribute selector: a details or dialog that is open.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.

Check your work

- Summary is the first child
- Works with keyboard
- Only summary is clickable, not the answer
- Indicator changes when open

Exercises

1. Use the name attribute so only one item can be open at once.
2. Animate the opening with interpolate-size or a max-height transition.
3. Add a search box that filters questions with JavaScript.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 196: FAQ accordion for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 2 | Files: index.html, styles.css

Brief

Build an accordion of questions and answers with no JavaScript using details and summary, with a custom plus/minus indicator.

Learning goals

- Use details/summary for native disclosure
- Style the open state with the [open] attribute selector
- Replace the default marker

Elements and CSS used

HTML elements	CSS features
details, summary, p, h1	[open], ::after, content, list-style: none, cursor: pointer, border-radius

Build guide

1. Write one <details> per question; the question goes in <summary>.
2. Add open to the first one so it starts expanded.
3. Remove the default triangle marker.
4. Add a plus sign with summary::after and a minus when open.
5. Give the open summary a background and border.
6. Click and use the keyboard (Tab, Enter) to test.

Project 196: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - FAQ</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Frequently asked questions</h1>
    <details open>
      <summary>How do I book a dish?</summary>
      <p>Use the contact form or call us. Popular dishes fill up
quickly.</p>
    </details>
    <details>
      <summary>Where are you located?</summary>
      <p>We are in Port Said. Parking is available nearby.</p>
    </details>
    <details>
      <summary>Do you offer discounts?</summary>
      <p>Students and groups of four or more get 10 percent off.</p>
    </details>
    <details>
      <summary>Can I cancel?</summary>
      <p>Yes, up to 24 hours before, free of charge.</p>
    </details>
  </main>
</body>
</html>
```

Project 196: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
details { border: 1px solid var(--line); border-radius: 10px; margin-
bottom: .75rem; background: #fff; }
summary { padding: .9rem 1.1rem; cursor: pointer; font-weight: 600;
list-style: none; display: flex; justify-content: space-between; }
summary::-webkit-details-marker { display: none; }
summary::after { content: "+"; color: var(--brand); font-size: 1.3rem;
 line-height: 1; }
```

```
details[open] summary::after { content: "\2212"; }
details[open] summary { border-bottom: 1px solid var(--line);
background: var(--accent); }
details p { padding: 0 1.1rem 1rem; margin: .75rem 0 0; }
```

Project 196 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - FAQ</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Frequently asked questions	The main heading; only one per page.
<details open>	Disclosure widget that can be opened and closed.
<summary>How do I book a dish?</summary>	The always-visible heading of a details element.
<p>Use the contact form or call us. Popular dishes fill up quickly....	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
background: #fff;	Background colour or image.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-weight: 600;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
display: none;	Removes the element from rendering completely.
summary::after {	Generated content inserted after the element's content.
content: "+";	The text or empty string for a pseudo-element.
font-size: 1.3rem;	Size of the text.
details[open] summary::after {	Attribute selector: a details or dialog that is open.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.

Check your work

- Summary is the first child
- Works with keyboard
- Only summary is clickable, not the answer
- Indicator changes when open

Exercises

1. Use the name attribute so only one item can be open at once.
2. Animate the opening with interpolate-size or a max-height transition.
3. Add a search box that filters questions with JavaScript.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 197: FAQ accordion for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 2 | Files: index.html, styles.css

Brief

Build an accordion of questions and answers with no JavaScript using details and summary, with a custom plus/minus indicator.

Learning goals

- Use details/summary for native disclosure
- Style the open state with the [open] attribute selector
- Replace the default marker

Elements and CSS used

HTML elements	CSS features
details, summary, p, h1	[open], ::after, content, list-style: none, cursor: pointer, border-radius

Build guide

1. Write one <details> per question; the question goes in <summary>.
2. Add open to the first one so it starts expanded.
3. Remove the default triangle marker.
4. Add a plus sign with summary::after and a minus when open.
5. Give the open summary a background and border.
6. Click and use the keyboard (Tab, Enter) to test.

Project 197: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - FAQ</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Frequently asked questions</h1>
    <details open>
      <summary>How do I book a programme?</summary>
      <p>Use the contact form or call us. Popular programmes fill up
quickly.</p>
    </details>
    <details>
      <summary>Where are you located?</summary>
      <p>We are in Tanta. Parking is available nearby.</p>
    </details>
    <details>
      <summary>Do you offer discounts?</summary>
      <p>Students and groups of four or more get 10 percent off.</p>
    </details>
    <details>
      <summary>Can I cancel?</summary>
      <p>Yes, up to 24 hours before, free of charge.</p>
    </details>
  </main>
</body>
</html>
```

Project 197: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
details { border: 1px solid var(--line); border-radius: 10px; margin-
bottom: .75rem; background: #fff; }
summary { padding: .9rem 1.1rem; cursor: pointer; font-weight: 600;
list-style: none; display: flex; justify-content: space-between; }
summary::-webkit-details-marker { display: none; }
summary::after { content: "+"; color: var(--brand); font-size: 1.3rem;
 line-height: 1; }
```

```
details[open] summary::after { content: "\2212"; }
details[open] summary { border-bottom: 1px solid var(--line);
background: var(--accent); }
details p { padding: 0 1.1rem 1rem; margin: .75rem 0 0; }
```

Project 197 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - FAQ</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Frequently asked questions	The main heading; only one per page.
<details open>	Disclosure widget that can be opened and closed.
<summary>How do I book a programme?</summary>	The always-visible heading of a details element.
<p>Use the contact form or call us. Popular programmes fill up quic...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
background: #fff;	Background colour or image.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-weight: 600;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
display: none;	Removes the element from rendering completely.
summary::after {	Generated content inserted after the element's content.
content: "+";	The text or empty string for a pseudo-element.
font-size: 1.3rem;	Size of the text.
details[open] summary::after {	Attribute selector: a details or dialog that is open.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.

Check your work

- Summary is the first child
- Works with keyboard
- Only summary is clickable, not the answer
- Indicator changes when open

Exercises

1. Use the name attribute so only one item can be open at once.
2. Animate the opening with interpolate-size or a max-height transition.
3. Add a search box that filters questions with JavaScript.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 198: FAQ accordion for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Build an accordion of questions and answers with no JavaScript using details and summary, with a custom plus/minus indicator.

Learning goals

- Use details/summary for native disclosure
- Style the open state with the [open] attribute selector
- Replace the default marker

Elements and CSS used

HTML elements	CSS features
details, summary, p, h1	[open], ::after, content, list-style: none, cursor: pointer, border-radius

Build guide

1. Write one <details> per question; the question goes in <summary>.
2. Add open to the first one so it starts expanded.
3. Remove the default triangle marker.
4. Add a plus sign with summary::after and a minus when open.
5. Give the open summary a background and border.
6. Click and use the keyboard (Tab, Enter) to test.

Project 198: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - FAQ</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Frequently asked questions</h1>
    <details open>
      <summary>How do I book a room?</summary>
      <p>Use the contact form or call us. Popular rooms fill up
quickly.</p>
    </details>
    <details>
      <summary>Where are you located?</summary>
      <p>We are in Aswan. Parking is available nearby.</p>
    </details>
    <details>
      <summary>Do you offer discounts?</summary>
      <p>Students and groups of four or more get 10 percent off.</p>
    </details>
    <details>
      <summary>Can I cancel?</summary>
      <p>Yes, up to 24 hours before, free of charge.</p>
    </details>
  </main>
</body>
</html>
```

Project 198: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
details { border: 1px solid var(--line); border-radius: 10px; margin-
bottom: .75rem; background: #fff; }
summary { padding: .9rem 1.1rem; cursor: pointer; font-weight: 600;
list-style: none; display: flex; justify-content: space-between; }
summary::-webkit-details-marker { display: none; }
summary::after { content: "+"; color: var(--brand); font-size: 1.3rem;
 line-height: 1; }
```

```
details[open] summary::after { content: "\2212"; }
details[open] summary { border-bottom: 1px solid var(--line);
background: var(--accent); }
details p { padding: 0 1.1rem 1rem; margin: .75rem 0 0; }
```

Project 198 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - FAQ</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Frequently asked questions	The main heading; only one per page.
<details open>	Disclosure widget that can be opened and closed.
<summary>How do I book a room?</summary>	The always-visible heading of a details element.
Use the contact form or call us. Popular rooms fill up quickly.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
background: #fff;	Background colour or image.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-weight: 600;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
display: none;	Removes the element from rendering completely.
summary::after {	Generated content inserted after the element's content.
content: "+";	The text or empty string for a pseudo-element.
font-size: 1.3rem;	Size of the text.
details[open] summary::after {	Attribute selector: a details or dialog that is open.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.

Check your work

- Summary is the first child
- Works with keyboard
- Only summary is clickable, not the answer
- Indicator changes when open

Exercises

1. Use the name attribute so only one item can be open at once.
2. Animate the opening with interpolate-size or a max-height transition.
3. Add a search box that filters questions with JavaScript.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 199: FAQ accordion for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 2 | Files: index.html, styles.css

Brief

Build an accordion of questions and answers with no JavaScript using details and summary, with a custom plus/minus indicator.

Learning goals

- Use details/summary for native disclosure
- Style the open state with the [open] attribute selector
- Replace the default marker

Elements and CSS used

HTML elements	CSS features
details, summary, p, h1	[open], ::after, content, list-style: none, cursor: pointer, border-radius

Build guide

1. Write one <details> per question; the question goes in <summary>.
2. Add open to the first one so it starts expanded.
3. Remove the default triangle marker.
4. Add a plus sign with summary::after and a minus when open.
5. Give the open summary a background and border.
6. Click and use the keyboard (Tab, Enter) to test.

Project 199: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - FAQ</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Frequently asked questions</h1>
    <details open>
      <summary>How do I book a bike?</summary>
      <p>Use the contact form or call us. Popular bikes fill up
quickly.</p>
    </details>
    <details>
      <summary>Where are you located?</summary>
      <p>We are in Ismailia. Parking is available nearby.</p>
    </details>
    <details>
      <summary>Do you offer discounts?</summary>
      <p>Students and groups of four or more get 10 percent off.</p>
    </details>
    <details>
      <summary>Can I cancel?</summary>
      <p>Yes, up to 24 hours before, free of charge.</p>
    </details>
  </main>
</body>
</html>
```

Project 199: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
details { border: 1px solid var(--line); border-radius: 10px; margin-
bottom: .75rem; background: #fff; }
summary { padding: .9rem 1.1rem; cursor: pointer; font-weight: 600;
list-style: none; display: flex; justify-content: space-between; }
summary::-webkit-details-marker { display: none; }
summary::after { content: "+"; color: var(--brand); font-size: 1.3rem;
 line-height: 1; }
```

```
details[open] summary::after { content: "\2212"; }
details[open] summary { border-bottom: 1px solid var(--line);
background: var(--accent); }
details p { padding: 0 1.1rem 1rem; margin: .75rem 0 0; }
```

Project 199 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - FAQ</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Frequently asked questions	The main heading; only one per page.
<details open>	Disclosure widget that can be opened and closed.
<summary>How do I book a bike?</summary>	The always-visible heading of a details element.
Use the contact form or call us. Popular bikes fill up quickly.	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
background: #fff;	Background colour or image.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-weight: 600;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
display: none;	Removes the element from rendering completely.
summary::after {	Generated content inserted after the element's content.
content: "+";	The text or empty string for a pseudo-element.
font-size: 1.3rem;	Size of the text.
details[open] summary::after {	Attribute selector: a details or dialog that is open.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.

Check your work

- Summary is the first child
- Works with keyboard
- Only summary is clickable, not the answer
- Indicator changes when open

Exercises

1. Use the name attribute so only one item can be open at once.
2. Animate the opening with interpolate-size or a max-height transition.
3. Add a search box that filters questions with JavaScript.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 200: FAQ accordion for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 2 | Files: index.html, styles.css

Brief

Build an accordion of questions and answers with no JavaScript using details and summary, with a custom plus/minus indicator.

Learning goals

- Use details/summary for native disclosure
- Style the open state with the [open] attribute selector
- Replace the default marker

Elements and CSS used

HTML elements	CSS features
details, summary, p, h1	[open], ::after, content, list-style: none, cursor: pointer, border-radius

Build guide

1. Write one <details> per question; the question goes in <summary>.
2. Add open to the first one so it starts expanded.
3. Remove the default triangle marker.
4. Add a plus sign with summary::after and a minus when open.
5. Give the open summary a background and border.
6. Click and use the keyboard (Tab, Enter) to test.

Project 200: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - FAQ</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Frequently asked questions</h1>
    <details open>
      <summary>How do I book a workshop?</summary>
      <p>Use the contact form or call us. Popular workshops fill up
quickly.</p>
    </details>
    <details>
      <summary>Where are you located?</summary>
      <p>We are in Minya. Parking is available nearby.</p>
    </details>
    <details>
      <summary>Do you offer discounts?</summary>
      <p>Students and groups of four or more get 10 percent off.</p>
    </details>
    <details>
      <summary>Can I cancel?</summary>
      <p>Yes, up to 24 hours before, free of charge.</p>
    </details>
  </main>
</body>
</html>
```

Project 200: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
details { border: 1px solid var(--line); border-radius: 10px; margin-
bottom: .75rem; background: #fff; }
summary { padding: .9rem 1.1rem; cursor: pointer; font-weight: 600;
list-style: none; display: flex; justify-content: space-between; }
summary::-webkit-details-marker { display: none; }
summary::after { content: "+"; color: var(--brand); font-size: 1.3rem;
 line-height: 1; }
```

```
details[open] summary::after { content: "\2212"; }
details[open] summary { border-bottom: 1px solid var(--line);
background: var(--accent); }
details p { padding: 0 1.1rem 1rem; margin: .75rem 0 0; }
```

Project 200 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - FAQ</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Frequently asked questions	The main heading; only one per page.
<details open>	Disclosure widget that can be opened and closed.
<summary>How do I book a workshop?</summary>	The always-visible heading of a details element.
<p>Use the contact form or call us. Popular workshops fill up quick...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
background: #fff;	Background colour or image.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-weight: 600;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
display: none;	Removes the element from rendering completely.
summary::after {	Generated content inserted after the element's content.
content: "+";	The text or empty string for a pseudo-element.
font-size: 1.3rem;	Size of the text.
details[open] summary::after {	Attribute selector: a details or dialog that is open.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.

Check your work

- Summary is the first child
- Works with keyboard
- Only summary is clickable, not the answer
- Indicator changes when open

Exercises

1. Use the name attribute so only one item can be open at once.
2. Animate the opening with interpolate-size or a max-height transition.
3. Add a search box that filters questions with JavaScript.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Product card

Level 1 | 25 projects, one per theme

Design a single product card: image on top, small uppercase label, title, description, price and a full-width button, centred on the page.

Project 201: Product card for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 1 | Files: index.html, styles.css

Brief

Design a single product card: image on top, small uppercase label, title, description, price and a full-width button, centred on the page.

Learning goals

- Centre a component with display: grid and place-items
- Build a shadowed card with rounded corners
- Use text-transform and letter-spacing for labels

Elements and CSS used

HTML elements	CSS features
article, img, div, p, h1, a	place-items: center, box-shadow, border-radius, overflow: hidden, text-transform, letter-spacing, filter

Build guide

1. Write the article with the image first, then a .body div.
2. Add the kicker, title, description, price and button.
3. Centre the card in main with grid and place-items.
4. Round the card corners; hide overflow so the image follows the rounding.
5. Add a soft box shadow.
6. Darken the button slightly on hover with filter.

Project 201: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Learn HTML - Cairo Book Shop</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="card">
      <img src="images/bookshop-1.jpg" alt="Learn HTML" width="600"
height="400">
      <div class="body">
        <p class="kicker">Book</p>
        <h1>Learn HTML</h1>
        <p>From your first tag to a complete page.</p>
        <p class="price">120 EGP</p>
        <a class="btn" href="book.html">Book now</a>
      </div>
    </article>
  </main>
</body>
</html>
```

Project 201: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.card { max-width: 22rem; background: #fff; border-radius: 16px;
overflow: hidden; box-shadow: 0 10px 30px rgb(0 0 0 / 12%); }
.card img { display: block; width: 100%; height: auto; }
.body { padding: 1.25rem; }
.kicker { text-transform: uppercase; letter-spacing: .08em; font-size:
 .75rem; color: var(--muted); margin: 0; }
h1 { margin: .25rem 0 .5rem; font-size: 1.4rem; }
.price { font-size: 1.3rem; font-weight: 700; color: var(--brand); }
.btn { display: block; text-align: center; padding: .7rem; background:
 var(--brand); color: #fff; border-radius: 10px; text-decoration:
none; }
.btn:hover { filter: brightness(.9); }
```

Project 201 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Learn HTML - Cairo Book Shop</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/bookshop-1.jpg" alt="Learn HTML" width="600" heigh...	An image; alt describes it, width and height reserve space before it loads.
	Generic block container for grouping and layout.
Book	A paragraph of text.
Learn HTML	The main heading; only one per page.
Book now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
max-width: 22rem;	Limits how wide the element can grow, keeping lines readable.
border-radius: 16px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.

Declaration	What it does
box-shadow: 0 10px 30px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
font-size: .75rem;	Size of the text.
font-weight: 700;	Thickness of the text.
text-align: center;	Centres inline content such as text.
border-radius: 10px;	The line around the element: width, style and colour.
text-decoration: none;	Removes the underline from links.
.btn:hover {	Applies while the pointer is over the element.
filter: brightness(.9);	Darkens or brightens the element; a cheap hover effect.

Check your work

- Image corners rounded with the card
- Card is centred vertically and horizontally
- Button is full width
- Text contrast passes

Exercises

1. Turn it into a grid of four cards.
2. Add a 'sold out' ribbon positioned absolutely.
3. Make the image and text side by side above 600px.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 202: Product card for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 1 | Files: index.html, styles.css

Brief

Design a single product card: image on top, small uppercase label, title, description, price and a full-width button, centred on the page.

Learning goals

- Centre a component with display: grid and place-items
- Build a shadowed card with rounded corners
- Use text-transform and letter-spacing for labels

Elements and CSS used

HTML elements	CSS features
article, img, div, p, h1, a	place-items: center, box-shadow, border-radius, overflow: hidden, text-transform, letter-spacing, filter

Build guide

1. Write the article with the image first, then a .body div.
2. Add the kicker, title, description, price and button.
3. Centre the card in main with grid and place-items.
4. Round the card corners; hide overflow so the image follows the rounding.
5. Add a soft box shadow.
6. Darken the button slightly on hover with filter.

Project 202: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sourdough loaf - Nile Bakery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="card">
      <img src="images/bakery-1.jpg" alt="Sourdough loaf" width="600"
height="400">
      <div class="body">
        <p class="kicker">Pastry</p>
        <h1>Sourdough loaf</h1>
        <p>Slow fermented, crisp crust.</p>
        <p class="price">60 EGP</p>
        <a class="btn" href="book.html">Book now</a>
      </div>
    </article>
  </main>
</body>
</html>
```

Project 202: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.card { max-width: 22rem; background: #fff; border-radius: 16px;
overflow: hidden; box-shadow: 0 10px 30px rgb(0 0 0 / 12%); }
.card img { display: block; width: 100%; height: auto; }
.body { padding: 1.25rem; }
.kicker { text-transform: uppercase; letter-spacing: .08em; font-size:
 .75rem; color: var(--muted); margin: 0; }
h1 { margin: .25rem 0 .5rem; font-size: 1.4rem; }
.price { font-size: 1.3rem; font-weight: 700; color: var(--brand); }
.btn { display: block; text-align: center; padding: .7rem; background:
 var(--brand); color: #fff; border-radius: 10px; text-decoration:
none; }
.btn:hover { filter: brightness(.9); }
```

Project 202 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sourdough loaf - Nile Bakery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/bakery-1.jpg" alt="Sourdough loaf" width="600" hei...	An image; alt describes it, width and height reserve space before it loads.
	Generic block container for grouping and layout.
Pastry	A paragraph of text.
Sourdough loaf	The main heading; only one per page.
Book now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
max-width: 22rem;	Limits how wide the element can grow, keeping lines readable.
border-radius: 16px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.

Declaration	What it does
box-shadow: 0 10px 30px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
font-size: .75rem;	Size of the text.
font-weight: 700;	Thickness of the text.
text-align: center;	Centres inline content such as text.
border-radius: 10px;	The line around the element: width, style and colour.
text-decoration: none;	Removes the underline from links.
.btn:hover {	Applies while the pointer is over the element.
filter: brightness(.9);	Darkens or brightens the element; a cheap hover effect.

Check your work

- Image corners rounded with the card
- Card is centred vertically and horizontally
- Button is full width
- Text contrast passes

Exercises

1. Turn it into a grid of four cards.
2. Add a 'sold out' ribbon positioned absolutely.
3. Make the image and text side by side above 600px.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 203: Product card for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 1 | Files: index.html, styles.css

Brief

Design a single product card: image on top, small uppercase label, title, description, price and a full-width button, centred on the page.

Learning goals

- Centre a component with display: grid and place-items
- Build a shadowed card with rounded corners
- Use text-transform and letter-spacing for labels

Elements and CSS used

HTML elements	CSS features
article, img, div, p, h1, a	place-items: center, box-shadow, border-radius, overflow: hidden, text-transform, letter-spacing, filter

Build guide

1. Write the article with the image first, then a .body div.
2. Add the kicker, title, description, price and button.
3. Centre the card in main with grid and place-items.
4. Round the card corners; hide overflow so the image follows the rounding.
5. Add a soft box shadow.
6. Darken the button slightly on hover with filter.

Project 203: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Morning yoga - Pyramid Fitness</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="card">
      <img src="images/gym-1.jpg" alt="Morning yoga" width="600"
height="400">
      <div class="body">
        <p class="kicker">Class</p>
        <h1>Morning yoga</h1>
        <p>Flexibility and calm, 60 minutes.</p>
        <p class="price">100 EGP</p>
        <a class="btn" href="book.html">Book now</a>
      </div>
    </article>
  </main>
</body>
</html>
```

Project 203: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.card { max-width: 22rem; background: #fff; border-radius: 16px;
overflow: hidden; box-shadow: 0 10px 30px rgb(0 0 0 / 12%); }
.card img { display: block; width: 100%; height: auto; }
.body { padding: 1.25rem; }
.kicker { text-transform: uppercase; letter-spacing: .08em; font-size:
 .75rem; color: var(--muted); margin: 0; }
h1 { margin: .25rem 0 .5rem; font-size: 1.4rem; }
.price { font-size: 1.3rem; font-weight: 700; color: var(--brand); }
.btn { display: block; text-align: center; padding: .7rem; background:
 var(--brand); color: #fff; border-radius: 10px; text-decoration:
none; }
.btn:hover { filter: brightness(.9); }
```

Project 203 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Morning yoga - Pyramid Fitness</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/gym-1.jpg" alt="Morning yoga" width="600" height="...	An image; alt describes it, width and height reserve space before it loads.
	Generic block container for grouping and layout.
Class	A paragraph of text.
Morning yoga	The main heading; only one per page.
Book now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
max-width: 22rem;	Limits how wide the element can grow, keeping lines readable.
border-radius: 16px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
box-shadow: 0 10px 30px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.

Declaration	What it does
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
font-size: .75rem;	Size of the text.
font-weight: 700;	Thickness of the text.
text-align: center;	Centres inline content such as text.
border-radius: 10px;	The line around the element: width, style and colour.
text-decoration: none;	Removes the underline from links.
.btn:hover {	Applies while the pointer is over the element.
filter: brightness(.9);	Darkens or brightens the element; a cheap hover effect.

Check your work

- Image corners rounded with the card
- Card is centred vertically and horizontally
- Button is full width
- Text contrast passes

Exercises

1. Turn it into a grid of four cards.
2. Add a 'sold out' ribbon positioned absolutely.

3. Make the image and text side by side above 600px.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 204: Product card for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 1 | Files: index.html, styles.css

Brief

Design a single product card: image on top, small uppercase label, title, description, price and a full-width button, centred on the page.

Learning goals

- Centre a component with display: grid and place-items
- Build a shadowed card with rounded corners
- Use text-transform and letter-spacing for labels

Elements and CSS used

HTML elements	CSS features
article, img, div, p, h1, a	place-items: center, box-shadow, border-radius, overflow: hidden, text-transform, letter-spacing, filter

Build guide

1. Write the article with the image first, then a .body div.
2. Add the kicker, title, description, price and button.
3. Centre the card in main with grid and place-items.
4. Round the card corners; hide overflow so the image follows the rounding.
5. Add a soft box shadow.
6. Darken the button slightly on hover with filter.

Project 204: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Check-up - Delta Dental Clinic</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="card">
      <img src="images/clinic-1.jpg" alt="Check-up" width="600"
height="400">
      <div class="body">
        <p class="kicker">Service</p>
        <h1>Check-up</h1>
        <p>Examination and cleaning.</p>
        <p class="price">300 EGP</p>
        <a class="btn" href="book.html">Book now</a>
      </div>
    </article>
  </main>
</body>
</html>
```

Project 204: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.card { max-width: 22rem; background: #fff; border-radius: 16px;
overflow: hidden; box-shadow: 0 10px 30px rgb(0 0 0 / 12%); }
.card img { display: block; width: 100%; height: auto; }
.body { padding: 1.25rem; }
.kicker { text-transform: uppercase; letter-spacing: .08em; font-size:
 .75rem; color: var(--muted); margin: 0; }
h1 { margin: .25rem 0 .5rem; font-size: 1.4rem; }
.price { font-size: 1.3rem; font-weight: 700; color: var(--brand); }
.btn { display: block; text-align: center; padding: .7rem; background:
 var(--brand); color: #fff; border-radius: 10px; text-decoration:
none; }
.btn:hover { filter: brightness(.9); }
```

Project 204 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Check-up - Delta Dental Clinic</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/clinic-1.jpg" alt="Check-up" width="600" height="4...	An image; alt describes it, width and height reserve space before it loads.
	Generic block container for grouping and layout.
Service	A paragraph of text.
Check-up	The main heading; only one per page.
Book now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
max-width: 22rem;	Limits how wide the element can grow, keeping lines readable.
border-radius: 16px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.

Declaration	What it does
box-shadow: 0 10px 30px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
font-size: .75rem;	Size of the text.
font-weight: 700;	Thickness of the text.
text-align: center;	Centres inline content such as text.
border-radius: 10px;	The line around the element: width, style and colour.
text-decoration: none;	Removes the underline from links.
.btn:hover {	Applies while the pointer is over the element.
filter: brightness(.9);	Darkens or brightens the element; a cheap hover effect.

Check your work

- Image corners rounded with the card
- Card is centred vertically and horizontally
- Button is full width
- Text contrast passes

Exercises

1. Turn it into a grid of four cards.
2. Add a 'sold out' ribbon positioned absolutely.
3. Make the image and text side by side above 600px.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 205: Product card for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 1 | Files: index.html, styles.css

Brief

Design a single product card: image on top, small uppercase label, title, description, price and a full-width button, centred on the page.

Learning goals

- Centre a component with display: grid and place-items
- Build a shadowed card with rounded corners
- Use text-transform and letter-spacing for labels

Elements and CSS used

HTML elements	CSS features
article, img, div, p, h1, a	place-items: center, box-shadow, border-radius, overflow: hidden, text-transform, letter-spacing, filter

Build guide

1. Write the article with the image first, then a .body div.
2. Add the kicker, title, description, price and button.
3. Centre the card in main with grid and place-items.
4. Round the card corners; hide overflow so the image follows the rounding.
5. Add a soft box shadow.
6. Darken the button slightly on hover with filter.

Project 205: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor day trip - Red Sea Travel</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="card">
      <img src="images/travel-1.jpg" alt="Luxor day trip" width="600"
height="400">
      <div class="body">
        <p class="kicker">Tour</p>
        <h1>Luxor day trip</h1>
        <p>Karnak, Valley of the Kings.</p>
        <p class="price">1200 EGP</p>
        <a class="btn" href="book.html">Book now</a>
      </div>
    </article>
  </main>
</body>
</html>
```

Project 205: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.card { max-width: 22rem; background: #fff; border-radius: 16px;
overflow: hidden; box-shadow: 0 10px 30px rgb(0 0 0 / 12%); }
.card img { display: block; width: 100%; height: auto; }
.body { padding: 1.25rem; }
.kicker { text-transform: uppercase; letter-spacing: .08em; font-size:
 .75rem; color: var(--muted); margin: 0; }
h1 { margin: .25rem 0 .5rem; font-size: 1.4rem; }
.price { font-size: 1.3rem; font-weight: 700; color: var(--brand); }
.btn { display: block; text-align: center; padding: .7rem; background:
 var(--brand); color: #fff; border-radius: 10px; text-decoration:
none; }
.btn:hover { filter: brightness(.9); }
```

Project 205 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor day trip - Red Sea Travel</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/travel-1.jpg" alt="Luxor day trip" width="600" hei...	An image; alt describes it, width and height reserve space before it loads.
	Generic block container for grouping and layout.
Tour	A paragraph of text.
Luxor day trip	The main heading; only one per page.
Book now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
max-width: 22rem;	Limits how wide the element can grow, keeping lines readable.
border-radius: 16px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.

Declaration	What it does
box-shadow: 0 10px 30px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
font-size: .75rem;	Size of the text.
font-weight: 700;	Thickness of the text.
text-align: center;	Centres inline content such as text.
border-radius: 10px;	The line around the element: width, style and colour.
text-decoration: none;	Removes the underline from links.
.btn:hover {	Applies while the pointer is over the element.
filter: brightness(.9);	Darkens or brightens the element; a cheap hover effect.

Check your work

- Image corners rounded with the card
- Card is centred vertically and horizontally
- Button is full width
- Text contrast passes

Exercises

1. Turn it into a grid of four cards.
2. Add a 'sold out' ribbon positioned absolutely.
3. Make the image and text side by side above 600px.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 206: Product card for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Design a single product card: image on top, small uppercase label, title, description, price and a full-width button, centred on the page.

Learning goals

- Centre a component with display: grid and place-items
- Build a shadowed card with rounded corners
- Use text-transform and letter-spacing for labels

Elements and CSS used

HTML elements	CSS features
article, img, div, p, h1, a	place-items: center, box-shadow, border-radius, overflow: hidden, text-transform, letter-spacing, filter

Build guide

1. Write the article with the image first, then a .body div.
2. Add the kicker, title, description, price and button.
3. Centre the card in main with grid and place-items.
4. Round the card corners; hide overflow so the image follows the rounding.
5. Add a soft box shadow.
6. Darken the button slightly on hover with filter.

Project 206: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>English A1 - Lotus Language School</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="card">
      <img src="images/school-1.jpg" alt="English A1" width="600"
height="400">
      <div class="body">
        <p class="kicker">Course</p>
        <h1>English A1</h1>
        <p>Beginner, 8 weeks.</p>
        <p class="price">1800 EGP</p>
        <a class="btn" href="book.html">Book now</a>
      </div>
    </article>
  </main>
</body>
</html>
```

Project 206: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.card { max-width: 22rem; background: #fff; border-radius: 16px;
overflow: hidden; box-shadow: 0 10px 30px rgb(0 0 0 / 12%); }
.card img { display: block; width: 100%; height: auto; }
.body { padding: 1.25rem; }
.kicker { text-transform: uppercase; letter-spacing: .08em; font-size:
 .75rem; color: var(--muted); margin: 0; }
h1 { margin: .25rem 0 .5rem; font-size: 1.4rem; }
.price { font-size: 1.3rem; font-weight: 700; color: var(--brand); }
.btn { display: block; text-align: center; padding: .7rem; background:
 var(--brand); color: #fff; border-radius: 10px; text-decoration:
none; }
.btn:hover { filter: brightness(.9); }
```

Project 206 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>English A1 - Lotus Language School</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/school-1.jpg" alt="English A1" width="600" height=...	An image; alt describes it, width and height reserve space before it loads.
	Generic block container for grouping and layout.
Course	A paragraph of text.
English A1	The main heading; only one per page.
Book now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
max-width: 22rem;	Limits how wide the element can grow, keeping lines readable.
border-radius: 16px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.

Declaration	What it does
box-shadow: 0 10px 30px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
font-size: .75rem;	Size of the text.
font-weight: 700;	Thickness of the text.
text-align: center;	Centres inline content such as text.
border-radius: 10px;	The line around the element: width, style and colour.
text-decoration: none;	Removes the underline from links.
.btn:hover {	Applies while the pointer is over the element.
filter: brightness(.9);	Darkens or brightens the element; a cheap hover effect.

Check your work

- Image corners rounded with the card
- Card is centred vertically and horizontally
- Button is full width
- Text contrast passes

Exercises

1. Turn it into a grid of four cards.
2. Add a 'sold out' ribbon positioned absolutely.
3. Make the image and text side by side above 600px.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 207: Product card for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 1 | Files: index.html, styles.css

Brief

Design a single product card: image on top, small uppercase label, title, description, price and a full-width button, centred on the page.

Learning goals

- Centre a component with display: grid and place-items
- Build a shadowed card with rounded corners
- Use text-transform and letter-spacing for labels

Elements and CSS used

HTML elements	CSS features
article, img, div, p, h1, a	place-items: center, box-shadow, border-radius, overflow: hidden, text-transform, letter-spacing, filter

Build guide

1. Write the article with the image first, then a .body div.
2. Add the kicker, title, description, price and button.
3. Centre the card in main with grid and place-items.
4. Round the card corners; hide overflow so the image follows the rounding.
5. Add a soft box shadow.
6. Darken the button slightly on hover with filter.

Project 207: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Flat white - Green Leaf Cafe</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="card">
      <img src="images/cafe-1.jpg" alt="Flat white" width="600"
height="400">
      <div class="body">
        <p class="kicker">Drink</p>
        <h1>Flat white</h1>
        <p>Double shot, silky milk.</p>
        <p class="price">55 EGP</p>
        <a class="btn" href="book.html">Book now</a>
      </div>
    </article>
  </main>
</body>
</html>
```

Project 207: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.card { max-width: 22rem; background: #fff; border-radius: 16px;
overflow: hidden; box-shadow: 0 10px 30px rgb(0 0 0 / 12%); }
.card img { display: block; width: 100%; height: auto; }
.body { padding: 1.25rem; }
.kicker { text-transform: uppercase; letter-spacing: .08em; font-size:
 .75rem; color: var(--muted); margin: 0; }
h1 { margin: .25rem 0 .5rem; font-size: 1.4rem; }
.price { font-size: 1.3rem; font-weight: 700; color: var(--brand); }
.btn { display: block; text-align: center; padding: .7rem; background:
 var(--brand); color: #fff; border-radius: 10px; text-decoration:
none; }
.btn:hover { filter: brightness(.9); }
```

Project 207 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Flat white - Green Leaf Cafe</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/cafe-1.jpg" alt="Flat white" width="600" height="4...	An image; alt describes it, width and height reserve space before it loads.
	Generic block container for grouping and layout.
Drink	A paragraph of text.
Flat white	The main heading; only one per page.
Book now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
max-width: 22rem;	Limits how wide the element can grow, keeping lines readable.
border-radius: 16px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
box-shadow: 0 10px 30px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.

Declaration	What it does
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
font-size: .75rem;	Size of the text.
font-weight: 700;	Thickness of the text.
text-align: center;	Centres inline content such as text.
border-radius: 10px;	The line around the element: width, style and colour.
text-decoration: none;	Removes the underline from links.
.btn:hover {	Applies while the pointer is over the element.
filter: brightness(.9);	Darkens or brightens the element; a cheap hover effect.

Check your work

- Image corners rounded with the card
- Card is centred vertically and horizontally
- Button is full width
- Text contrast passes

Exercises

1. Turn it into a grid of four cards.
2. Add a 'sold out' ribbon positioned absolutely.

3. Make the image and text side by side above 600px.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 208: Product card for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 1 | Files: index.html, styles.css

Brief

Design a single product card: image on top, small uppercase label, title, description, price and a full-width button, centred on the page.

Learning goals

- Centre a component with display: grid and place-items
- Build a shadowed card with rounded corners
- Use text-transform and letter-spacing for labels

Elements and CSS used

HTML elements	CSS features
article, img, div, p, h1, a	place-items: center, box-shadow, border-radius, overflow: hidden, text-transform, letter-spacing, filter

Build guide

1. Write the article with the image first, then a .body div.
2. Add the kicker, title, description, price and button.
3. Centre the card in main with grid and place-items.
4. Round the card corners; hide overflow so the image follows the rounding.
5. Add a soft box shadow.
6. Darken the button slightly on hover with filter.

Project 208: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Mount Sinai sunrise - Sinai Trekking Club</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="card">
      <img src="images/trekking-1.jpg" alt="Mount Sinai sunrise"
width="600" height="400">
      <div class="body">
        <p class="kicker">Hike</p>
        <h1>Mount Sinai sunrise</h1>
        <p>Night climb, 7 km.</p>
        <p class="price">400 EGP</p>
        <a class="btn" href="book.html">Book now</a>
      </div>
    </article>
  </main>
</body>
</html>
```

Project 208: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.card { max-width: 22rem; background: #fff; border-radius: 16px;
overflow: hidden; box-shadow: 0 10px 30px rgb(0 0 0 / 12%); }
.card img { display: block; width: 100%; height: auto; }
.body { padding: 1.25rem; }
.kicker { text-transform: uppercase; letter-spacing: .08em; font-size:
 .75rem; color: var(--muted); margin: 0; }
h1 { margin: .25rem 0 .5rem; font-size: 1.4rem; }
.price { font-size: 1.3rem; font-weight: 700; color: var(--brand); }
.btn { display: block; text-align: center; padding: .7rem; background:
 var(--brand); color: #fff; border-radius: 10px; text-decoration:
none; }
.btn:hover { filter: brightness(.9); }
```

Project 208 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Mount Sinai sunrise - Sinai Trekking Club</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/trekking-1.jpg" alt="Mount Sinai sunrise" width="6...	An image; alt describes it, width and height reserve space before it loads.
	Generic block container for grouping and layout.
Hike	A paragraph of text.
Mount Sinai sunrise	The main heading; only one per page.
Book now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
max-width: 22rem;	Limits how wide the element can grow, keeping lines readable.
border-radius: 16px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.

Declaration	What it does
box-shadow: 0 10px 30px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
font-size: .75rem;	Size of the text.
font-weight: 700;	Thickness of the text.
text-align: center;	Centres inline content such as text.
border-radius: 10px;	The line around the element: width, style and colour.
text-decoration: none;	Removes the underline from links.
.btn:hover {	Applies while the pointer is over the element.
filter: brightness(.9);	Darkens or brightens the element; a cheap hover effect.

Check your work

- Image corners rounded with the card
- Card is centred vertically and horizontally
- Button is full width
- Text contrast passes

Exercises

1. Turn it into a grid of four cards.
2. Add a 'sold out' ribbon positioned absolutely.
3. Make the image and text side by side above 600px.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 209: Product card for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 1 | Files: index.html, styles.css

Brief

Design a single product card: image on top, small uppercase label, title, description, price and a full-width button, centred on the page.

Learning goals

- Centre a component with display: grid and place-items
- Build a shadowed card with rounded corners
- Use text-transform and letter-spacing for labels

Elements and CSS used

HTML elements	CSS features
article, img, div, p, h1, a	place-items: center, box-shadow, border-radius, overflow: hidden, text-transform, letter-spacing, filter

Build guide

1. Write the article with the image first, then a .body div.
2. Add the kicker, title, description, price and button.
3. Centre the card in main with grid and place-items.
4. Round the card corners; hide overflow so the image follows the rounding.
5. Add a soft box shadow.
6. Darken the button slightly on hover with filter.

Project 209: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Portrait session - Horizon Photography</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="card">
      <img src="images/photo-1.jpg" alt="Portrait session"
width="600" height="400">
      <div class="body">
        <p class="kicker">Session</p>
        <h1>Portrait session</h1>
        <p>One hour, 20 edited photos.</p>
        <p class="price">1200 EGP</p>
        <a class="btn" href="book.html">Book now</a>
      </div>
    </article>
  </main>
</body>
</html>
```

Project 209: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.card { max-width: 22rem; background: #fff; border-radius: 16px;
overflow: hidden; box-shadow: 0 10px 30px rgb(0 0 0 / 12%); }
.card img { display: block; width: 100%; height: auto; }
.body { padding: 1.25rem; }
.kicker { text-transform: uppercase; letter-spacing: .08em; font-size:
 .75rem; color: var(--muted); margin: 0; }
h1 { margin: .25rem 0 .5rem; font-size: 1.4rem; }
.price { font-size: 1.3rem; font-weight: 700; color: var(--brand); }
.btn { display: block; text-align: center; padding: .7rem; background:
 var(--brand); color: #fff; border-radius: 10px; text-decoration:
none; }
.btn:hover { filter: brightness(.9); }
```

Project 209 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Portrait session - Horizon Photography</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/photo-1.jpg" alt="Portrait session" width="600" he...	An image; alt describes it, width and height reserve space before it loads.
	Generic block container for grouping and layout.
Session	A paragraph of text.
Portrait session	The main heading; only one per page.
Book now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
max-width: 22rem;	Limits how wide the element can grow, keeping lines readable.
border-radius: 16px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.

Declaration	What it does
box-shadow: 0 10px 30px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
font-size: .75rem;	Size of the text.
font-weight: 700;	Thickness of the text.
text-align: center;	Centres inline content such as text.
border-radius: 10px;	The line around the element: width, style and colour.
text-decoration: none;	Removes the underline from links.
.btn:hover {	Applies while the pointer is over the element.
filter: brightness(.9);	Darkens or brightens the element; a cheap hover effect.

Check your work

- Image corners rounded with the card
- Card is centred vertically and horizontally
- Button is full width
- Text contrast passes

Exercises

1. Turn it into a grid of four cards.
2. Add a 'sold out' ribbon positioned absolutely.
3. Make the image and text side by side above 600px.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 210: Product card for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 1 | Files: index.html, styles.css

Brief

Design a single product card: image on top, small uppercase label, title, description, price and a full-width button, centred on the page.

Learning goals

- Centre a component with display: grid and place-items
- Build a shadowed card with rounded corners
- Use text-transform and letter-spacing for labels

Elements and CSS used

HTML elements	CSS features
article, img, div, p, h1, a	place-items: center, box-shadow, border-radius, overflow: hidden, text-transform, letter-spacing, filter

Build guide

1. Write the article with the image first, then a .body div.
2. Add the kicker, title, description, price and button.
3. Centre the card in main with grid and place-items.
4. Round the card corners; hide overflow so the image follows the rounding.
5. Add a soft box shadow.
6. Darken the button slightly on hover with filter.

Project 210: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Dotted notebook - Papyrus Stationery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="card">
      <img src="images/stationery-1.jpg" alt="Dotted notebook"
width="600" height="400">
      <div class="body">
        <p class="kicker">Product</p>
        <h1>Dotted notebook</h1>
        <p>A5, 160 pages.</p>
        <p class="price">140 EGP</p>
        <a class="btn" href="book.html">Book now</a>
      </div>
    </article>
  </main>
</body>
</html>
```

Project 210: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.card { max-width: 22rem; background: #fff; border-radius: 16px;
overflow: hidden; box-shadow: 0 10px 30px rgb(0 0 0 / 12%); }
.card img { display: block; width: 100%; height: auto; }
.body { padding: 1.25rem; }
.kicker { text-transform: uppercase; letter-spacing: .08em; font-size:
 .75rem; color: var(--muted); margin: 0; }
h1 { margin: .25rem 0 .5rem; font-size: 1.4rem; }
.price { font-size: 1.3rem; font-weight: 700; color: var(--brand); }
.btn { display: block; text-align: center; padding: .7rem; background:
 var(--brand); color: #fff; border-radius: 10px; text-decoration:
none; }
.btn:hover { filter: brightness(.9); }
```

Project 210 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Dotted notebook - Papyrus Stationery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/stationery-1.jpg" alt="Dotted notebook" width="600...	An image; alt describes it, width and height reserve space before it loads.
	Generic block container for grouping and layout.
Product	A paragraph of text.
Dotted notebook	The main heading; only one per page.
Book now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
max-width: 22rem;	Limits how wide the element can grow, keeping lines readable.
border-radius: 16px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.

Declaration	What it does
box-shadow: 0 10px 30px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
font-size: .75rem;	Size of the text.
font-weight: 700;	Thickness of the text.
text-align: center;	Centres inline content such as text.
border-radius: 10px;	The line around the element: width, style and colour.
text-decoration: none;	Removes the underline from links.
.btn:hover {	Applies while the pointer is over the element.
filter: brightness(.9);	Darkens or brightens the element; a cheap hover effect.

Check your work

- Image corners rounded with the card
- Card is centred vertically and horizontally
- Button is full width
- Text contrast passes

Exercises

1. Turn it into a grid of four cards.
2. Add a 'sold out' ribbon positioned absolutely.
3. Make the image and text side by side above 600px.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 211: Product card for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 1 | Files: index.html, styles.css

Brief

Design a single product card: image on top, small uppercase label, title, description, price and a full-width button, centred on the page.

Learning goals

- Centre a component with display: grid and place-items
- Build a shadowed card with rounded corners
- Use text-transform and letter-spacing for labels

Elements and CSS used

HTML elements	CSS features
article, img, div, p, h1, a	place-items: center, box-shadow, border-radius, overflow: hidden, text-transform, letter-spacing, filter

Build guide

1. Write the article with the image first, then a .body div.
2. Add the kicker, title, description, price and button.
3. Centre the card in main with grid and place-items.
4. Round the card corners; hide overflow so the image follows the rounding.
5. Add a soft box shadow.
6. Darken the button slightly on hover with filter.

Project 211: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Monstera - Oasis Plant Nursery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="card">
      <img src="images/plants-1.jpg" alt="Monstera" width="600"
height="400">
      <div class="body">
        <p class="kicker">Plant</p>
        <h1>Monstera</h1>
        <p>Large leaves, easy care.</p>
        <p class="price">250 EGP</p>
        <a class="btn" href="book.html">Book now</a>
      </div>
    </article>
  </main>
</body>
</html>
```

Project 211: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.card { max-width: 22rem; background: #fff; border-radius: 16px;
overflow: hidden; box-shadow: 0 10px 30px rgb(0 0 0 / 12%); }
.card img { display: block; width: 100%; height: auto; }
.body { padding: 1.25rem; }
.kicker { text-transform: uppercase; letter-spacing: .08em; font-size:
 .75rem; color: var(--muted); margin: 0; }
h1 { margin: .25rem 0 .5rem; font-size: 1.4rem; }
.price { font-size: 1.3rem; font-weight: 700; color: var(--brand); }
.btn { display: block; text-align: center; padding: .7rem; background:
 var(--brand); color: #fff; border-radius: 10px; text-decoration:
none; }
.btn:hover { filter: brightness(.9); }
```

Project 211 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Monstera - Oasis Plant Nursery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/plants-1.jpg" alt="Monstera" width="600" height="4...	An image; alt describes it, width and height reserve space before it loads.
	Generic block container for grouping and layout.
Plant	A paragraph of text.
Monstera	The main heading; only one per page.
Book now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
max-width: 22rem;	Limits how wide the element can grow, keeping lines readable.
border-radius: 16px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.

Declaration	What it does
box-shadow: 0 10px 30px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
font-size: .75rem;	Size of the text.
font-weight: 700;	Thickness of the text.
text-align: center;	Centres inline content such as text.
border-radius: 10px;	The line around the element: width, style and colour.
text-decoration: none;	Removes the underline from links.
.btn:hover {	Applies while the pointer is over the element.
filter: brightness(.9);	Darkens or brightens the element; a cheap hover effect.

Check your work

- Image corners rounded with the card
- Card is centred vertically and horizontally
- Button is full width
- Text contrast passes

Exercises

1. Turn it into a grid of four cards.
2. Add a 'sold out' ribbon positioned absolutely.
3. Make the image and text side by side above 600px.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 212: Product card for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 1 | Files: index.html, styles.css

Brief

Design a single product card: image on top, small uppercase label, title, description, price and a full-width button, centred on the page.

Learning goals

- Centre a component with display: grid and place-items
- Build a shadowed card with rounded corners
- Use text-transform and letter-spacing for labels

Elements and CSS used

HTML elements	CSS features
article, img, div, p, h1, a	place-items: center, box-shadow, border-radius, overflow: hidden, text-transform, letter-spacing, filter

Build guide

1. Write the article with the image first, then a .body div.
2. Add the kicker, title, description, price and button.
3. Centre the card in main with grid and place-items.
4. Round the card corners; hide overflow so the image follows the rounding.
5. Add a soft box shadow.
6. Darken the button slightly on hover with filter.

Project 212: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oak dining table - Cedar Furniture</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="card">
      <img src="images/furniture-1.jpg" alt="Oak dining table"
width="600" height="400">
      <div class="body">
        <p class="kicker">Piece</p>
        <h1>Oak dining table</h1>
        <p>Seats six.</p>
        <p class="price">9500 EGP</p>
        <a class="btn" href="book.html">Book now</a>
      </div>
    </article>
  </main>
</body>
</html>
```

Project 212: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.card { max-width: 22rem; background: #fff; border-radius: 16px;
overflow: hidden; box-shadow: 0 10px 30px rgb(0 0 0 / 12%); }
.card img { display: block; width: 100%; height: auto; }
.body { padding: 1.25rem; }
.kicker { text-transform: uppercase; letter-spacing: .08em; font-size:
 .75rem; color: var(--muted); margin: 0; }
h1 { margin: .25rem 0 .5rem; font-size: 1.4rem; }
.price { font-size: 1.3rem; font-weight: 700; color: var(--brand); }
.btn { display: block; text-align: center; padding: .7rem; background:
 var(--brand); color: #fff; border-radius: 10px; text-decoration:
none; }
.btn:hover { filter: brightness(.9); }
```

Project 212 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oak dining table - Cedar Furniture</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/furniture-1.jpg" alt="Oak dining table" width="600...	An image; alt describes it, width and height reserve space before it loads.
	Generic block container for grouping and layout.
Piece	A paragraph of text.
Oak dining table	The main heading; only one per page.
Book now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
max-width: 22rem;	Limits how wide the element can grow, keeping lines readable.
border-radius: 16px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.

Declaration	What it does
box-shadow: 0 10px 30px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
font-size: .75rem;	Size of the text.
font-weight: 700;	Thickness of the text.
text-align: center;	Centres inline content such as text.
border-radius: 10px;	The line around the element: width, style and colour.
text-decoration: none;	Removes the underline from links.
.btn:hover {	Applies while the pointer is over the element.
filter: brightness(.9);	Darkens or brightens the element; a cheap hover effect.

Check your work

- Image corners rounded with the card
- Card is centred vertically and horizontally
- Button is full width
- Text contrast passes

Exercises

1. Turn it into a grid of four cards.
2. Add a 'sold out' ribbon positioned absolutely.
3. Make the image and text side by side above 600px.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 213: Product card for Byte Repair

Theme: Byte Repair (Nasr City) | Level 1 | Files: index.html, styles.css

Brief

Design a single product card: image on top, small uppercase label, title, description, price and a full-width button, centred on the page.

Learning goals

- Centre a component with display: grid and place-items
- Build a shadowed card with rounded corners
- Use text-transform and letter-spacing for labels

Elements and CSS used

HTML elements	CSS features
article, img, div, p, h1, a	place-items: center, box-shadow, border-radius, overflow: hidden, text-transform, letter-spacing, filter

Build guide

1. Write the article with the image first, then a .body div.
2. Add the kicker, title, description, price and button.
3. Centre the card in main with grid and place-items.
4. Round the card corners; hide overflow so the image follows the rounding.
5. Add a soft box shadow.
6. Darken the button slightly on hover with filter.

Project 213: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Screen replacement - Byte Repair</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="card">
      <img src="images/repair-1.jpg" alt="Screen replacement"
width="600" height="400">
      <div class="body">
        <p class="kicker">Repair</p>
        <h1>Screen replacement</h1>
        <p>Most phones, 1 hour.</p>
        <p class="price">From 800 EGP</p>
        <a class="btn" href="book.html">Book now</a>
      </div>
    </article>
  </main>
</body>
</html>
```

Project 213: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.card { max-width: 22rem; background: #fff; border-radius: 16px;
overflow: hidden; box-shadow: 0 10px 30px rgb(0 0 0 / 12%); }
.card img { display: block; width: 100%; height: auto; }
.body { padding: 1.25rem; }
.kicker { text-transform: uppercase; letter-spacing: .08em; font-size:
 .75rem; color: var(--muted); margin: 0; }
h1 { margin: .25rem 0 .5rem; font-size: 1.4rem; }
.price { font-size: 1.3rem; font-weight: 700; color: var(--brand); }
.btn { display: block; text-align: center; padding: .7rem; background:
 var(--brand); color: #fff; border-radius: 10px; text-decoration:
none; }
.btn:hover { filter: brightness(.9); }
```

Project 213 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Screen replacement - Byte Repair</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/repair-1.jpg" alt="Screen replacement" width="600"...	An image; alt describes it, width and height reserve space before it loads.
	Generic block container for grouping and layout.
Repair	A paragraph of text.
Screen replacement	The main heading; only one per page.

Line	What it does
Book now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.

Declaration	What it does
max-width: 22rem;	Limits how wide the element can grow, keeping lines readable.
border-radius: 16px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
box-shadow: 0 10px 30px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
font-size: .75rem;	Size of the text.
font-weight: 700;	Thickness of the text.
text-align: center;	Centres inline content such as text.
border-radius: 10px;	The line around the element: width, style and colour.
text-decoration: none;	Removes the underline from links.
.btn:hover {	Applies while the pointer is over the element.
filter: brightness(.9);	Darkens or brightens the element; a cheap hover effect.

Check your work

- Image corners rounded with the card

- Card is centred vertically and horizontally
- Button is full width
- Text contrast passes

Exercises

1. Turn it into a grid of four cards.
2. Add a 'sold out' ribbon positioned absolutely.
3. Make the image and text side by side above 600px.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 214: Product card for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 1 | Files: index.html, styles.css

Brief

Design a single product card: image on top, small uppercase label, title, description, price and a full-width button, centred on the page.

Learning goals

- Centre a component with display: grid and place-items
- Build a shadowed card with rounded corners
- Use text-transform and letter-spacing for labels

Elements and CSS used

HTML elements	CSS features
article, img, div, p, h1, a	place-items: center, box-shadow, border-radius, overflow: hidden, text-transform, letter-spacing, filter

Build guide

1. Write the article with the image first, then a .body div.
2. Add the kicker, title, description, price and button.
3. Centre the card in main with grid and place-items.
4. Round the card corners; hide overflow so the image follows the rounding.
5. Add a soft box shadow.
6. Darken the button slightly on hover with filter.

Project 214: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Full grooming - Sahara Pet Care</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="card">
      <img src="images/pets-1.jpg" alt="Full grooming" width="600"
height="400">
      <div class="body">
        <p class="kicker">Service</p>
        <h1>Full grooming</h1>
        <p>Bath, cut and nails.</p>
        <p class="price">400 EGP</p>
        <a class="btn" href="book.html">Book now</a>
      </div>
    </article>
  </main>
</body>
</html>
```

Project 214: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.card { max-width: 22rem; background: #fff; border-radius: 16px;
overflow: hidden; box-shadow: 0 10px 30px rgb(0 0 0 / 12%); }
.card img { display: block; width: 100%; height: auto; }
.body { padding: 1.25rem; }
.kicker { text-transform: uppercase; letter-spacing: .08em; font-size:
 .75rem; color: var(--muted); margin: 0; }
h1 { margin: .25rem 0 .5rem; font-size: 1.4rem; }
.price { font-size: 1.3rem; font-weight: 700; color: var(--brand); }
.btn { display: block; text-align: center; padding: .7rem; background:
 var(--brand); color: #fff; border-radius: 10px; text-decoration:
none; }
.btn:hover { filter: brightness(.9); }
```

Project 214 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Full grooming - Sahara Pet Care</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/pets-1.jpg" alt="Full grooming" width="600" height...	An image; alt describes it, width and height reserve space before it loads.
	Generic block container for grouping and layout.
Service	A paragraph of text.
Full grooming	The main heading; only one per page.
Book now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
max-width: 22rem;	Limits how wide the element can grow, keeping lines readable.
border-radius: 16px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.

Declaration	What it does
box-shadow: 0 10px 30px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
font-size: .75rem;	Size of the text.
font-weight: 700;	Thickness of the text.
text-align: center;	Centres inline content such as text.
border-radius: 10px;	The line around the element: width, style and colour.
text-decoration: none;	Removes the underline from links.
.btn:hover {	Applies while the pointer is over the element.
filter: brightness(.9);	Darkens or brightens the element; a cheap hover effect.

Check your work

- Image corners rounded with the card
- Card is centred vertically and horizontally
- Button is full width
- Text contrast passes

Exercises

1. Turn it into a grid of four cards.
2. Add a 'sold out' ribbon positioned absolutely.
3. Make the image and text side by side above 600px.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 215: Product card for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Design a single product card: image on top, small uppercase label, title, description, price and a full-width button, centred on the page.

Learning goals

- Centre a component with display: grid and place-items
- Build a shadowed card with rounded corners
- Use text-transform and letter-spacing for labels

Elements and CSS used

HTML elements	CSS features
article, img, div, p, h1, a	place-items: center, box-shadow, border-radius, overflow: hidden, text-transform, letter-spacing, filter

Build guide

1. Write the article with the image first, then a .body div.
2. Add the kicker, title, description, price and button.
3. Centre the card in main with grid and place-items.
4. Round the card corners; hide overflow so the image follows the rounding.
5. Add a soft box shadow.
6. Darken the button slightly on hover with filter.

Project 215: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Taster session - Alexandria Sailing School</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="card">
      <img src="images/sailing-1.jpg" alt="Taster session"
width="600" height="400">
      <div class="body">
        <p class="kicker">Lesson</p>
        <h1>Taster session</h1>
        <p>Two hours on the water.</p>
        <p class="price">500 EGP</p>
        <a class="btn" href="book.html">Book now</a>
      </div>
    </article>
  </main>
</body>
</html>
```

Project 215: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.card { max-width: 22rem; background: #fff; border-radius: 16px;
overflow: hidden; box-shadow: 0 10px 30px rgb(0 0 0 / 12%); }
.card img { display: block; width: 100%; height: auto; }
.body { padding: 1.25rem; }
.kicker { text-transform: uppercase; letter-spacing: .08em; font-size:
 .75rem; color: var(--muted); margin: 0; }
h1 { margin: .25rem 0 .5rem; font-size: 1.4rem; }
.price { font-size: 1.3rem; font-weight: 700; color: var(--brand); }
.btn { display: block; text-align: center; padding: .7rem; background:
 var(--brand); color: #fff; border-radius: 10px; text-decoration:
none; }
.btn:hover { filter: brightness(.9); }
```

Project 215 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Taster session - Alexandria Sailing School</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/sailing-1.jpg" alt="Taster session" width="600" he...	An image; alt describes it, width and height reserve space before it loads.
	Generic block container for grouping and layout.
Lesson	A paragraph of text.
Taster session	The main heading; only one per page.

Line	What it does
Book now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.

Declaration	What it does
max-width: 22rem;	Limits how wide the element can grow, keeping lines readable.
border-radius: 16px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
box-shadow: 0 10px 30px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
font-size: .75rem;	Size of the text.
font-weight: 700;	Thickness of the text.
text-align: center;	Centres inline content such as text.
border-radius: 10px;	The line around the element: width, style and colour.
text-decoration: none;	Removes the underline from links.
.btn:hover {	Applies while the pointer is over the element.
filter: brightness(.9);	Darkens or brightens the element; a cheap hover effect.

Check your work

- Image corners rounded with the card

- Card is centred vertically and horizontally
- Button is full width
- Text contrast passes

Exercises

1. Turn it into a grid of four cards.
2. Add a 'sold out' ribbon positioned absolutely.
3. Make the image and text side by side above 600px.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 216: Product card for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Design a single product card: image on top, small uppercase label, title, description, price and a full-width button, centred on the page.

Learning goals

- Centre a component with display: grid and place-items
- Build a shadowed card with rounded corners
- Use text-transform and letter-spacing for labels

Elements and CSS used

HTML elements	CSS features
article, img, div, p, h1, a	place-items: center, box-shadow, border-radius, overflow: hidden, text-transform, letter-spacing, filter

Build guide

1. Write the article with the image first, then a .body div.
2. Add the kicker, title, description, price and button.
3. Centre the card in main with grid and place-items.
4. Round the card corners; hide overflow so the image follows the rounding.
5. Add a soft box shadow.
6. Darken the button slightly on hover with filter.

Project 216: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus pendant - Habiba Handmade Jewellery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="card">
      <img src="images/jewellery-1.jpg" alt="Lotus pendant"
width="600" height="400">
      <div class="body">
        <p class="kicker">Item</p>
        <h1>Lotus pendant</h1>
        <p>Sterling silver.</p>
        <p class="price">650 EGP</p>
        <a class="btn" href="book.html">Book now</a>
      </div>
    </article>
  </main>
</body>
</html>
```

Project 216: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.card { max-width: 22rem; background: #fff; border-radius: 16px;
overflow: hidden; box-shadow: 0 10px 30px rgb(0 0 0 / 12%); }
.card img { display: block; width: 100%; height: auto; }
.body { padding: 1.25rem; }
.kicker { text-transform: uppercase; letter-spacing: .08em; font-size:
 .75rem; color: var(--muted); margin: 0; }
h1 { margin: .25rem 0 .5rem; font-size: 1.4rem; }
.price { font-size: 1.3rem; font-weight: 700; color: var(--brand); }
.btn { display: block; text-align: center; padding: .7rem; background:
 var(--brand); color: #fff; border-radius: 10px; text-decoration:
none; }
.btn:hover { filter: brightness(.9); }
```

Project 216 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus pendant - Habiba Handmade Jewellery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/jewellery-1.jpg" alt="Lotus pendant" width="600" h...	An image; alt describes it, width and height reserve space before it loads.
	Generic block container for grouping and layout.
Item	A paragraph of text.
Lotus pendant	The main heading; only one per page.
Book now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
max-width: 22rem;	Limits how wide the element can grow, keeping lines readable.
border-radius: 16px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.

Declaration	What it does
box-shadow: 0 10px 30px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
font-size: .75rem;	Size of the text.
font-weight: 700;	Thickness of the text.
text-align: center;	Centres inline content such as text.
border-radius: 10px;	The line around the element: width, style and colour.
text-decoration: none;	Removes the underline from links.
.btn:hover {	Applies while the pointer is over the element.
filter: brightness(.9);	Darkens or brightens the element; a cheap hover effect.

Check your work

- Image corners rounded with the card
- Card is centred vertically and horizontally
- Button is full width
- Text contrast passes

Exercises

1. Turn it into a grid of four cards.
2. Add a 'sold out' ribbon positioned absolutely.
3. Make the image and text side by side above 600px.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 217: Product card for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 1 | Files: index.html, styles.css

Brief

Design a single product card: image on top, small uppercase label, title, description, price and a full-width button, centred on the page.

Learning goals

- Centre a component with display: grid and place-items
- Build a shadowed card with rounded corners
- Use text-transform and letter-spacing for labels

Elements and CSS used

HTML elements	CSS features
article, img, div, p, h1, a	place-items: center, box-shadow, border-radius, overflow: hidden, text-transform, letter-spacing, filter

Build guide

1. Write the article with the image first, then a .body div.
2. Add the kicker, title, description, price and button.
3. Centre the card in main with grid and place-items.
4. Round the card corners; hide overflow so the image follows the rounding.
5. Add a soft box shadow.
6. Darken the button slightly on hover with filter.

Project 217: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Intro to the wheel - Fayoum Pottery Studio</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="card">
      <img src="images/pottery-1.jpg" alt="Intro to the wheel"
width="600" height="400">
      <div class="body">
        <p class="kicker">Workshop</p>
        <h1>Intro to the wheel</h1>
        <p>Three hours, take home a bowl.</p>
        <p class="price">450 EGP</p>
        <a class="btn" href="book.html">Book now</a>
      </div>
    </article>
  </main>
</body>
</html>
```

Project 217: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.card { max-width: 22rem; background: #fff; border-radius: 16px;
overflow: hidden; box-shadow: 0 10px 30px rgb(0 0 0 / 12%); }
.card img { display: block; width: 100%; height: auto; }
.body { padding: 1.25rem; }
.kicker { text-transform: uppercase; letter-spacing: .08em; font-size:
 .75rem; color: var(--muted); margin: 0; }
h1 { margin: .25rem 0 .5rem; font-size: 1.4rem; }
.price { font-size: 1.3rem; font-weight: 700; color: var(--brand); }
.btn { display: block; text-align: center; padding: .7rem; background:
 var(--brand); color: #fff; border-radius: 10px; text-decoration:
none; }
.btn:hover { filter: brightness(.9); }
```

Project 217 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Intro to the wheel - Fayoum Pottery Studio</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/pottery-1.jpg" alt="Intro to the wheel" width="600...	An image; alt describes it, width and height reserve space before it loads.
	Generic block container for grouping and layout.
Workshop	A paragraph of text.
Intro to the wheel	The main heading; only one per page.
Book now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
max-width: 22rem;	Limits how wide the element can grow, keeping lines readable.
border-radius: 16px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.

Declaration	What it does
box-shadow: 0 10px 30px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
font-size: .75rem;	Size of the text.
font-weight: 700;	Thickness of the text.
text-align: center;	Centres inline content such as text.
border-radius: 10px;	The line around the element: width, style and colour.
text-decoration: none;	Removes the underline from links.
.btn:hover {	Applies while the pointer is over the element.
filter: brightness(.9);	Darkens or brightens the element; a cheap hover effect.

Check your work

- Image corners rounded with the card
- Card is centred vertically and horizontally
- Button is full width
- Text contrast passes

Exercises

1. Turn it into a grid of four cards.
2. Add a 'sold out' ribbon positioned absolutely.
3. Make the image and text side by side above 600px.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 218: Product card for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 1 | Files: index.html, styles.css

Brief

Design a single product card: image on top, small uppercase label, title, description, price and a full-width button, centred on the page.

Learning goals

- Centre a component with display: grid and place-items
- Build a shadowed card with rounded corners
- Use text-transform and letter-spacing for labels

Elements and CSS used

HTML elements	CSS features
article, img, div, p, h1, a	place-items: center, box-shadow, border-radius, overflow: hidden, text-transform, letter-spacing, filter

Build guide

1. Write the article with the image first, then a .body div.
2. Add the kicker, title, description, price and button.
3. Centre the card in main with grid and place-items.
4. Round the card corners; hide overflow so the image follows the rounding.
5. Add a soft box shadow.
6. Darken the button slightly on hover with filter.

Project 218: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Haircut and blow-dry - Cleopatra Beauty Salon</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="card">
      <img src="images/salon-1.jpg" alt="Haircut and blow-dry"
width="600" height="400">
      <div class="body">
        <p class="kicker">Treatment</p>
        <h1>Haircut and blow-dry</h1>
        <p>Consultation included.</p>
        <p class="price">350 EGP</p>
        <a class="btn" href="book.html">Book now</a>
      </div>
    </article>
  </main>
</body>
</html>
```

Project 218: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.card { max-width: 22rem; background: #fff; border-radius: 16px;
overflow: hidden; box-shadow: 0 10px 30px rgb(0 0 0 / 12%); }
.card img { display: block; width: 100%; height: auto; }
.body { padding: 1.25rem; }
.kicker { text-transform: uppercase; letter-spacing: .08em; font-size:
 .75rem; color: var(--muted); margin: 0; }
h1 { margin: .25rem 0 .5rem; font-size: 1.4rem; }
.price { font-size: 1.3rem; font-weight: 700; color: var(--brand); }
.btn { display: block; text-align: center; padding: .7rem; background:
 var(--brand); color: #fff; border-radius: 10px; text-decoration:
none; }
.btn:hover { filter: brightness(.9); }
```

Project 218 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Haircut and blow-dry - Cleopatra Beauty Salon</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/salon-1.jpg" alt="Haircut and blow-dry" width="600...	An image; alt describes it, width and height reserve space before it loads.
	Generic block container for grouping and layout.
Treatment	A paragraph of text.
Haircut and blow-dry	The main heading; only one per page.

Line	What it does
Book now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.

Declaration	What it does
max-width: 22rem;	Limits how wide the element can grow, keeping lines readable.
border-radius: 16px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
box-shadow: 0 10px 30px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
font-size: .75rem;	Size of the text.
font-weight: 700;	Thickness of the text.
text-align: center;	Centres inline content such as text.
border-radius: 10px;	The line around the element: width, style and colour.
text-decoration: none;	Removes the underline from links.
.btn:hover {	Applies while the pointer is over the element.
filter: brightness(.9);	Darkens or brightens the element; a cheap hover effect.

Check your work

- Image corners rounded with the card

- Card is centred vertically and horizontally
- Button is full width
- Text contrast passes

Exercises

1. Turn it into a grid of four cards.
2. Add a 'sold out' ribbon positioned absolutely.
3. Make the image and text side by side above 600px.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 219: Product card for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 1 | Files: index.html, styles.css

Brief

Design a single product card: image on top, small uppercase label, title, description, price and a full-width button, centred on the page.

Learning goals

- Centre a component with display: grid and place-items
- Build a shadowed card with rounded corners
- Use text-transform and letter-spacing for labels

Elements and CSS used

HTML elements	CSS features
article, img, div, p, h1, a	place-items: center, box-shadow, border-radius, overflow: hidden, text-transform, letter-spacing, filter

Build guide

1. Write the article with the image first, then a .body div.
2. Add the kicker, title, description, price and button.
3. Centre the card in main with grid and place-items.
4. Round the card corners; hide overflow so the image follows the rounding.
5. Add a soft box shadow.
6. Darken the button slightly on hover with filter.

Project 219: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oil change - Suez Auto Service</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="card">
      <img src="images/auto-1.jpg" alt="Oil change" width="600"
height="400">
      <div class="body">
        <p class="kicker">Service</p>
        <h1>Oil change</h1>
        <p>Filter included.</p>
        <p class="price">600 EGP</p>
        <a class="btn" href="book.html">Book now</a>
      </div>
    </article>
  </main>
</body>
</html>
```

Project 219: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.card { max-width: 22rem; background: #fff; border-radius: 16px;
overflow: hidden; box-shadow: 0 10px 30px rgb(0 0 0 / 12%); }
.card img { display: block; width: 100%; height: auto; }
.body { padding: 1.25rem; }
.kicker { text-transform: uppercase; letter-spacing: .08em; font-size:
 .75rem; color: var(--muted); margin: 0; }
h1 { margin: .25rem 0 .5rem; font-size: 1.4rem; }
.price { font-size: 1.3rem; font-weight: 700; color: var(--brand); }
.btn { display: block; text-align: center; padding: .7rem; background:
 var(--brand); color: #fff; border-radius: 10px; text-decoration:
none; }
.btn:hover { filter: brightness(.9); }
```

Project 219 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oil change - Suez Auto Service</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/auto-1.jpg" alt="Oil change" width="600" height="4...	An image; alt describes it, width and height reserve space before it loads.
	Generic block container for grouping and layout.
Service	A paragraph of text.
Oil change	The main heading; only one per page.
Book now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
max-width: 22rem;	Limits how wide the element can grow, keeping lines readable.
border-radius: 16px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.

Declaration	What it does
box-shadow: 0 10px 30px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
font-size: .75rem;	Size of the text.
font-weight: 700;	Thickness of the text.
text-align: center;	Centres inline content such as text.
border-radius: 10px;	The line around the element: width, style and colour.
text-decoration: none;	Removes the underline from links.
.btn:hover {	Applies while the pointer is over the element.
filter: brightness(.9);	Darkens or brightens the element; a cheap hover effect.

Check your work

- Image corners rounded with the card
- Card is centred vertically and horizontally
- Button is full width
- Text contrast passes

Exercises

1. Turn it into a grid of four cards.
2. Add a 'sold out' ribbon positioned absolutely.
3. Make the image and text side by side above 600px.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 220: Product card for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 1 | Files: index.html, styles.css

Brief

Design a single product card: image on top, small uppercase label, title, description, price and a full-width button, centred on the page.

Learning goals

- Centre a component with display: grid and place-items
- Build a shadowed card with rounded corners
- Use text-transform and letter-spacing for labels

Elements and CSS used

HTML elements	CSS features
article, img, div, p, h1, a	place-items: center, box-shadow, border-radius, overflow: hidden, text-transform, letter-spacing, filter

Build guide

1. Write the article with the image first, then a .body div.
2. Add the kicker, title, description, price and button.
3. Centre the card in main with grid and place-items.
4. Round the card corners; hide overflow so the image follows the rounding.
5. Add a soft box shadow.
6. Darken the button slightly on hover with filter.

Project 220: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oud for beginners - Luxor Music Academy</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="card">
      <img src="images/music-1.jpg" alt="Oud for beginners"
width="600" height="400">
      <div class="body">
        <p class="kicker">Course</p>
        <h1>Oud for beginners</h1>
        <p>Eight weekly lessons.</p>
        <p class="price">1600 EGP</p>
        <a class="btn" href="book.html">Book now</a>
      </div>
    </article>
  </main>
</body>
</html>
```

Project 220: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.card { max-width: 22rem; background: #fff; border-radius: 16px;
overflow: hidden; box-shadow: 0 10px 30px rgb(0 0 0 / 12%); }
.card img { display: block; width: 100%; height: auto; }
.body { padding: 1.25rem; }
.kicker { text-transform: uppercase; letter-spacing: .08em; font-size:
 .75rem; color: var(--muted); margin: 0; }
h1 { margin: .25rem 0 .5rem; font-size: 1.4rem; }
.price { font-size: 1.3rem; font-weight: 700; color: var(--brand); }
.btn { display: block; text-align: center; padding: .7rem; background:
 var(--brand); color: #fff; border-radius: 10px; text-decoration:
none; }
.btn:hover { filter: brightness(.9); }
```

Project 220 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oud for beginners - Luxor Music Academy</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/music-1.jpg" alt="Oud for beginners" width="600" h...	An image; alt describes it, width and height reserve space before it loads.
	Generic block container for grouping and layout.
Course	A paragraph of text.
Oud for beginners	The main heading; only one per page.
Book now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
max-width: 22rem;	Limits how wide the element can grow, keeping lines readable.
border-radius: 16px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.

Declaration	What it does
box-shadow: 0 10px 30px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
font-size: .75rem;	Size of the text.
font-weight: 700;	Thickness of the text.
text-align: center;	Centres inline content such as text.
border-radius: 10px;	The line around the element: width, style and colour.
text-decoration: none;	Removes the underline from links.
.btn:hover {	Applies while the pointer is over the element.
filter: brightness(.9);	Darkens or brightens the element; a cheap hover effect.

Check your work

- Image corners rounded with the card
- Card is centred vertically and horizontally
- Button is full width
- Text contrast passes

Exercises

1. Turn it into a grid of four cards.
2. Add a 'sold out' ribbon positioned absolutely.
3. Make the image and text side by side above 600px.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 221: Product card for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 1 | Files: index.html, styles.css

Brief

Design a single product card: image on top, small uppercase label, title, description, price and a full-width button, centred on the page.

Learning goals

- Centre a component with display: grid and place-items
- Build a shadowed card with rounded corners
- Use text-transform and letter-spacing for labels

Elements and CSS used

HTML elements	CSS features
article, img, div, p, h1, a	place-items: center, box-shadow, border-radius, overflow: hidden, text-transform, letter-spacing, filter

Build guide

1. Write the article with the image first, then a .body div.
2. Add the kicker, title, description, price and button.
3. Centre the card in main with grid and place-items.
4. Round the card corners; hide overflow so the image follows the rounding.
5. Add a soft box shadow.
6. Darken the button slightly on hover with filter.

Project 221: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Grilled sea bass - Port Said Seafood</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="card">
      <img src="images/restaurant-1.jpg" alt="Grilled sea bass"
width="600" height="400">
      <div class="body">
        <p class="kicker">Dish</p>
        <h1>Grilled sea bass</h1>
        <p>With rice and salad.</p>
        <p class="price">320 EGP</p>
        <a class="btn" href="book.html">Book now</a>
      </div>
    </article>
  </main>
</body>
</html>
```

Project 221: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.card { max-width: 22rem; background: #fff; border-radius: 16px;
overflow: hidden; box-shadow: 0 10px 30px rgb(0 0 0 / 12%); }
.card img { display: block; width: 100%; height: auto; }
.body { padding: 1.25rem; }
.kicker { text-transform: uppercase; letter-spacing: .08em; font-size:
 .75rem; color: var(--muted); margin: 0; }
h1 { margin: .25rem 0 .5rem; font-size: 1.4rem; }
.price { font-size: 1.3rem; font-weight: 700; color: var(--brand); }
.btn { display: block; text-align: center; padding: .7rem; background:
 var(--brand); color: #fff; border-radius: 10px; text-decoration:
none; }
.btn:hover { filter: brightness(.9); }
```

Project 221 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Grilled sea bass - Port Said Seafood</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/restaurant-1.jpg" alt="Grilled sea bass" width="60...	An image; alt describes it, width and height reserve space before it loads.
	Generic block container for grouping and layout.
Dish	A paragraph of text.
Grilled sea bass	The main heading; only one per page.
Book now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
max-width: 22rem;	Limits how wide the element can grow, keeping lines readable.
border-radius: 16px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.

Declaration	What it does
box-shadow: 0 10px 30px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
font-size: .75rem;	Size of the text.
font-weight: 700;	Thickness of the text.
text-align: center;	Centres inline content such as text.
border-radius: 10px;	The line around the element: width, style and colour.
text-decoration: none;	Removes the underline from links.
.btn:hover {	Applies while the pointer is over the element.
filter: brightness(.9);	Darkens or brightens the element; a cheap hover effect.

Check your work

- Image corners rounded with the card
- Card is centred vertically and horizontally
- Button is full width
- Text contrast passes

Exercises

1. Turn it into a grid of four cards.
2. Add a 'sold out' ribbon positioned absolutely.
3. Make the image and text side by side above 600px.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 222: Product card for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 1 | Files: index.html, styles.css

Brief

Design a single product card: image on top, small uppercase label, title, description, price and a full-width button, centred on the page.

Learning goals

- Centre a component with display: grid and place-items
- Build a shadowed card with rounded corners
- Use text-transform and letter-spacing for labels

Elements and CSS used

HTML elements	CSS features
article, img, div, p, h1, a	place-items: center, box-shadow, border-radius, overflow: hidden, text-transform, letter-spacing, filter

Build guide

1. Write the article with the image first, then a .body div.
2. Add the kicker, title, description, price and button.
3. Centre the card in main with grid and place-items.
4. Round the card corners; hide overflow so the image follows the rounding.
5. Add a soft box shadow.
6. Darken the button slightly on hover with filter.

Project 222: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Story hour - Delta Kids Library</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="card">
      <img src="images/library-1.jpg" alt="Story hour" width="600"
height="400">
      <div class="body">
        <p class="kicker">Programme</p>
        <h1>Story hour</h1>
        <p>Ages 3 to 6, Saturdays.</p>
        <p class="price">Free</p>
        <a class="btn" href="book.html">Book now</a>
      </div>
    </article>
  </main>
</body>
</html>
```

Project 222: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.card { max-width: 22rem; background: #fff; border-radius: 16px;
overflow: hidden; box-shadow: 0 10px 30px rgb(0 0 0 / 12%); }
.card img { display: block; width: 100%; height: auto; }
.body { padding: 1.25rem; }
.kicker { text-transform: uppercase; letter-spacing: .08em; font-size:
 .75rem; color: var(--muted); margin: 0; }
h1 { margin: .25rem 0 .5rem; font-size: 1.4rem; }
.price { font-size: 1.3rem; font-weight: 700; color: var(--brand); }
.btn { display: block; text-align: center; padding: .7rem; background:
 var(--brand); color: #fff; border-radius: 10px; text-decoration:
none; }
.btn:hover { filter: brightness(.9); }
```

Project 222 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Story hour - Delta Kids Library</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/library-1.jpg" alt="Story hour" width="600" height...	An image; alt describes it, width and height reserve space before it loads.
	Generic block container for grouping and layout.
Programme	A paragraph of text.
Story hour	The main heading; only one per page.
Book now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
max-width: 22rem;	Limits how wide the element can grow, keeping lines readable.
border-radius: 16px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.

Declaration	What it does
box-shadow: 0 10px 30px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
font-size: .75rem;	Size of the text.
font-weight: 700;	Thickness of the text.
text-align: center;	Centres inline content such as text.
border-radius: 10px;	The line around the element: width, style and colour.
text-decoration: none;	Removes the underline from links.
.btn:hover {	Applies while the pointer is over the element.
filter: brightness(.9);	Darkens or brightens the element; a cheap hover effect.

Check your work

- Image corners rounded with the card
- Card is centred vertically and horizontally
- Button is full width
- Text contrast passes

Exercises

1. Turn it into a grid of four cards.
2. Add a 'sold out' ribbon positioned absolutely.
3. Make the image and text side by side above 600px.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 223: Product card for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Design a single product card: image on top, small uppercase label, title, description, price and a full-width button, centred on the page.

Learning goals

- Centre a component with display: grid and place-items
- Build a shadowed card with rounded corners
- Use text-transform and letter-spacing for labels

Elements and CSS used

HTML elements	CSS features
article, img, div, p, h1, a	place-items: center, box-shadow, border-radius, overflow: hidden, text-transform, letter-spacing, filter

Build guide

1. Write the article with the image first, then a .body div.
2. Add the kicker, title, description, price and button.
3. Centre the card in main with grid and place-items.
4. Round the card corners; hide overflow so the image follows the rounding.
5. Add a soft box shadow.
6. Darken the button slightly on hover with filter.

Project 223: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Garden room - Nubian Guest House</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="card">
      <img src="images/guesthouse-1.jpg" alt="Garden room"
width="600" height="400">
      <div class="body">
        <p class="kicker">Room</p>
        <h1>Garden room</h1>
        <p>Double bed, shared terrace.</p>
        <p class="price">900 EGP</p>
        <a class="btn" href="book.html">Book now</a>
      </div>
    </article>
  </main>
</body>
</html>
```

Project 223: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.card { max-width: 22rem; background: #fff; border-radius: 16px;
overflow: hidden; box-shadow: 0 10px 30px rgb(0 0 0 / 12%); }
.card img { display: block; width: 100%; height: auto; }
.body { padding: 1.25rem; }
.kicker { text-transform: uppercase; letter-spacing: .08em; font-size:
 .75rem; color: var(--muted); margin: 0; }
h1 { margin: .25rem 0 .5rem; font-size: 1.4rem; }
.price { font-size: 1.3rem; font-weight: 700; color: var(--brand); }
.btn { display: block; text-align: center; padding: .7rem; background:
 var(--brand); color: #fff; border-radius: 10px; text-decoration:
none; }
.btn:hover { filter: brightness(.9); }
```

Project 223 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Garden room - Nubian Guest House</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/guesthouse-1.jpg" alt="Garden room" width="600" he...	An image; alt describes it, width and height reserve space before it loads.
	Generic block container for grouping and layout.
Room	A paragraph of text.
Garden room	The main heading; only one per page.
Book now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
max-width: 22rem;	Limits how wide the element can grow, keeping lines readable.
border-radius: 16px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
box-shadow: 0 10px 30px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.

Declaration	What it does
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
font-size: .75rem;	Size of the text.
font-weight: 700;	Thickness of the text.
text-align: center;	Centres inline content such as text.
border-radius: 10px;	The line around the element: width, style and colour.
text-decoration: none;	Removes the underline from links.
.btn:hover {	Applies while the pointer is over the element.
filter: brightness(.9);	Darkens or brightens the element; a cheap hover effect.

Check your work

- Image corners rounded with the card
- Card is centred vertically and horizontally
- Button is full width
- Text contrast passes

Exercises

1. Turn it into a grid of four cards.
2. Add a 'sold out' ribbon positioned absolutely.

3. Make the image and text side by side above 600px.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 224: Product card for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 1 | Files: index.html, styles.css

Brief

Design a single product card: image on top, small uppercase label, title, description, price and a full-width button, centred on the page.

Learning goals

- Centre a component with display: grid and place-items
- Build a shadowed card with rounded corners
- Use text-transform and letter-spacing for labels

Elements and CSS used

HTML elements	CSS features
article, img, div, p, h1, a	place-items: center, box-shadow, border-radius, overflow: hidden, text-transform, letter-spacing, filter

Build guide

1. Write the article with the image first, then a .body div.
2. Add the kicker, title, description, price and button.
3. Centre the card in main with grid and place-items.
4. Round the card corners; hide overflow so the image follows the rounding.
5. Add a soft box shadow.
6. Darken the button slightly on hover with filter.

Project 224: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>City bike - Ismailia Cycling Store</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="card">
      <img src="images/cycling-1.jpg" alt="City bike" width="600"
height="400">
      <div class="body">
        <p class="kicker">Bike</p>
        <h1>City bike</h1>
        <p>Seven gears, basket.</p>
        <p class="price">6500 EGP</p>
        <a class="btn" href="book.html">Book now</a>
      </div>
    </article>
  </main>
</body>
</html>
```

Project 224: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.card { max-width: 22rem; background: #fff; border-radius: 16px;
overflow: hidden; box-shadow: 0 10px 30px rgb(0 0 0 / 12%); }
.card img { display: block; width: 100%; height: auto; }
.body { padding: 1.25rem; }
.kicker { text-transform: uppercase; letter-spacing: .08em; font-size:
 .75rem; color: var(--muted); margin: 0; }
h1 { margin: .25rem 0 .5rem; font-size: 1.4rem; }
.price { font-size: 1.3rem; font-weight: 700; color: var(--brand); }
.btn { display: block; text-align: center; padding: .7rem; background:
 var(--brand); color: #fff; border-radius: 10px; text-decoration:
none; }
.btn:hover { filter: brightness(.9); }
```

Project 224 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>City bike - Ismailia Cycling Store</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/cycling-1.jpg" alt="City bike" width="600" height=...	An image; alt describes it, width and height reserve space before it loads.
	Generic block container for grouping and layout.
Bike	A paragraph of text.
City bike	The main heading; only one per page.
Book now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
max-width: 22rem;	Limits how wide the element can grow, keeping lines readable.
border-radius: 16px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.

Declaration	What it does
box-shadow: 0 10px 30px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
font-size: .75rem;	Size of the text.
font-weight: 700;	Thickness of the text.
text-align: center;	Centres inline content such as text.
border-radius: 10px;	The line around the element: width, style and colour.
text-decoration: none;	Removes the underline from links.
.btn:hover {	Applies while the pointer is over the element.
filter: brightness(.9);	Darkens or brightens the element; a cheap hover effect.

Check your work

- Image corners rounded with the card
- Card is centred vertically and horizontally
- Button is full width
- Text contrast passes

Exercises

1. Turn it into a grid of four cards.
2. Add a 'sold out' ribbon positioned absolutely.
3. Make the image and text side by side above 600px.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 225: Product card for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 1 | Files: index.html, styles.css

Brief

Design a single product card: image on top, small uppercase label, title, description, price and a full-width button, centred on the page.

Learning goals

- Centre a component with display: grid and place-items
- Build a shadowed card with rounded corners
- Use text-transform and letter-spacing for labels

Elements and CSS used

HTML elements	CSS features
article, img, div, p, h1, a	place-items: center, box-shadow, border-radius, overflow: hidden, text-transform, letter-spacing, filter

Build guide

1. Write the article with the image first, then a .body div.
2. Add the kicker, title, description, price and button.
3. Centre the card in main with grid and place-items.
4. Round the card corners; hide overflow so the image follows the rounding.
5. Add a soft box shadow.
6. Darken the button slightly on hover with filter.

Project 225: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>HTML weekend - Minya Coding Club</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="card">
      <img src="images/coding-1.jpg" alt="HTML weekend" width="600"
height="400">
      <div class="body">
        <p class="kicker">Workshop</p>
        <h1>HTML weekend</h1>
        <p>Build your first page.</p>
        <p class="price">Free</p>
        <a class="btn" href="book.html">Book now</a>
      </div>
    </article>
  </main>
</body>
</html>
```

Project 225: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.card { max-width: 22rem; background: #fff; border-radius: 16px;
overflow: hidden; box-shadow: 0 10px 30px rgb(0 0 0 / 12%); }
.card img { display: block; width: 100%; height: auto; }
.body { padding: 1.25rem; }
.kicker { text-transform: uppercase; letter-spacing: .08em; font-size:
 .75rem; color: var(--muted); margin: 0; }
h1 { margin: .25rem 0 .5rem; font-size: 1.4rem; }
.price { font-size: 1.3rem; font-weight: 700; color: var(--brand); }
.btn { display: block; text-align: center; padding: .7rem; background:
 var(--brand); color: #fff; border-radius: 10px; text-decoration:
none; }
.btn:hover { filter: brightness(.9); }
```

Project 225 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>HTML weekend - Minya Coding Club</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/coding-1.jpg" alt="HTML weekend" width="600" heigh...	An image; alt describes it, width and height reserve space before it loads.
	Generic block container for grouping and layout.
Workshop	A paragraph of text.
HTML weekend	The main heading; only one per page.
Book now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
max-width: 22rem;	Limits how wide the element can grow, keeping lines readable.
border-radius: 16px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.

Declaration	What it does
box-shadow: 0 10px 30px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
display: block;	Element starts on a new line and fills the width (used on links and images).
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
font-size: .75rem;	Size of the text.
font-weight: 700;	Thickness of the text.
text-align: center;	Centres inline content such as text.
border-radius: 10px;	The line around the element: width, style and colour.
text-decoration: none;	Removes the underline from links.
.btn:hover {	Applies while the pointer is over the element.
filter: brightness(.9);	Darkens or brightens the element; a cheap hover effect.

Check your work

- Image corners rounded with the card
- Card is centred vertically and horizontally
- Button is full width
- Text contrast passes

Exercises

1. Turn it into a grid of four cards.
2. Add a 'sold out' ribbon positioned absolutely.
3. Make the image and text side by side above 600px.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Site footer

Level 1 | 25 projects, one per theme

Build a three-column footer (about, links, contact) that stays at the bottom of short pages, with a legal line underneath.

Project 226: Site footer for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 1 | Files: index.html, styles.css

Brief

Build a three-column footer (about, links, contact) that stays at the bottom of short pages, with a legal line underneath.

Learning goals

- Make a sticky footer with flex column body
- Use address for contact details
- Lay out columns with auto-fit grid

Elements and CSS used

HTML elements	CSS features
footer, section, nav, h2, ul, li, a, address, br, p	min-height: 100vh, flex: 1, grid, text-transform, border-top, font-size

Build guide

1. Write main content followed by <footer class="site-footer">.
2. Inside, add a .cols div with three blocks: section, nav, section.
3. Add the legal paragraph after .cols.
4. Make body a flex column with min-height 100vh and main flex: 1 - this pushes the footer down.
5. Grid the columns.
6. Style headings small and uppercase; reset list styles.

Project 226: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cairo Book Shop</h1>
    <p>Scroll down to see the footer.</p>
  </main>
  <footer class="site-footer">
    <div class="cols">
      <section>
        <h2>Cairo Book Shop</h2>
        <p>PDF and printed books about web development.</p>
      </section>
      <nav aria-label="Footer">
        <h2>Books</h2>
        <ul>
    <li><a href="#">Learn HTML</a></li>
    <li><a href="#">CSS in Practice</a></li>
    <li><a href="#">JavaScript Basics</a></li>
    <li><a href="#">Web Accessibility</a></li>
        </ul>
      </nav>
      <section>
        <h2>Contact</h2>
        <address>Giza, Egypt<br><a href="mailto:hello@bookshop.
example">hello@bookshop.example</a><br><a href="tel:+20100000000">+20
100 000 0000</a></address>
      </section>
    </div>
    <p class="legal">&copy; 2026 Cairo Book Shop &middot; <a
href="privacy.html">Privacy</a> &middot; <a href="#top">Back to top</
a></p>
  </footer>
</body>
</html>
```

Project 226: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
body { min-height: 100vh; display: flex; flex-direction: column; }
main { flex: 1; padding: 2rem 1rem; }
.site-footer { background: #1b2431; color: #d5dbe5; padding: 2.5rem
1rem 1rem; }
.cols { max-width: 60rem; margin: 0 auto; display: grid; gap: 2rem;
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.site-footer h2 { color: #fff; font-size: 1rem; text-transform:
uppercase; letter-spacing: .06em; margin: 0 0 .75rem; }
.site-footer ul { list-style: none; padding: 0; margin: 0; }
.site-footer li { margin-bottom: .4rem; }
.site-footer a { color: #fff; }
address { font-style: normal; line-height: 1.8; }
.legal { max-width: 60rem; margin: 2rem auto 0; padding-top: 1rem;
border-top: 1px solid #334155; font-size: .85rem; text-align: center;
}
```

Project 226 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cairo Book Shop	The main heading; only one per page.
Scroll down to see the footer.	A paragraph of text.
<footer class="site-footer">	Footer of the page or of a section.
	Generic block container for grouping and layout.
<section>	A thematic group of content, normally with its own heading.
Cairo Book Shop	Second-level heading for a section.
<nav aria-label="Footer">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.

Line	What it does
Learn HTML	A hyperlink; href gives the destination.
CSS in Practice	One list item.
<address>Giza, Egypt <a href="mailto:hello@bookshop.example">hel...	Contact information for the page or article.
<p class="legal">© 2026 Cairo Book Shop · <a href="priv...	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
flex: 1;	All items share free space equally.
padding: 2rem 1rem;	Space inside the element between its border and content.
background: #1b2431;	Background colour or image.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
font-size: 1rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .06em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid #334155;	A top border used as an accent or separator.
text-align: center;	Centres inline content such as text.

Check your work

- Footer sits at the bottom even with little content

- Links are readable on the dark background
- address not italic
- Columns stack on phones

Exercises

1. Add social media icons as SVG links.
2. Add a newsletter form in a fourth column.
3. Make the 'Back to top' link smooth-scroll with scroll-behavior.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 227: Site footer for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 1 | Files: index.html, styles.css

Brief

Build a three-column footer (about, links, contact) that stays at the bottom of short pages, with a legal line underneath.

Learning goals

- Make a sticky footer with flex column body
- Use address for contact details
- Lay out columns with auto-fit grid

Elements and CSS used

HTML elements	CSS features
footer, section, nav, h2, ul, li, a, address, br, p	min-height: 100vh, flex: 1, grid, text-transform, border-top, font-size

Build guide

1. Write main content followed by <footer class="site-footer">.
2. Inside, add a .cols div with three blocks: section, nav, section.
3. Add the legal paragraph after .cols.
4. Make body a flex column with min-height 100vh and main flex: 1 - this pushes the footer down.
5. Grid the columns.
6. Style headings small and uppercase; reset list styles.

Project 227: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Nile Bakery</h1>
    <p>Scroll down to see the footer.</p>
  </main>
  <footer class="site-footer">
    <div class="cols">
      <section>
        <h2>Nile Bakery</h2>
        <p>Fresh bread and pastries every morning.</p>
      </section>
      <nav aria-label="Footer">
        <h2>Pastries</h2>
        <ul>
    <li><a href="#">Sourdough loaf</a></li>
    <li><a href="#">Croissant</a></li>
    <li><a href="#">Date cookies</a></li>
    <li><a href="#">Baklava box</a></li>
        </ul>
      </nav>
      <section>
        <h2>Contact</h2>
        <address>Cairo, Egypt<br><a href="mailto:hello@bakery.
example">hello@bakery.example</a><br><a href="tel:+20100000000">+20
100 000 0000</a></address>
      </section>
    </div>
    <p class="legal">&copy; 2026 Nile Bakery &middot; <a
href="privacy.html">Privacy</a> &middot; <a href="#top">Back to top</
a></p>
  </footer>
</body>
</html>
```

Project 227: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
body { min-height: 100vh; display: flex; flex-direction: column; }
main { flex: 1; padding: 2rem 1rem; }
.site-footer { background: #1b2431; color: #d5dbe5; padding: 2.5rem
1rem 1rem; }
.cols { max-width: 60rem; margin: 0 auto; display: grid; gap: 2rem;
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.site-footer h2 { color: #fff; font-size: 1rem; text-transform:
uppercase; letter-spacing: .06em; margin: 0 0 .75rem; }
.site-footer ul { list-style: none; padding: 0; margin: 0; }
.site-footer li { margin-bottom: .4rem; }
.site-footer a { color: #fff; }
address { font-style: normal; line-height: 1.8; }
.legal { max-width: 60rem; margin: 2rem auto 0; padding-top: 1rem;
border-top: 1px solid #334155; font-size: .85rem; text-align: center;
}
```

Project 227 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Nile Bakery	The main heading; only one per page.
Scroll down to see the footer.	A paragraph of text.
<footer class="site-footer">	Footer of the page or of a section.
	Generic block container for grouping and layout.
<section>	A thematic group of content, normally with its own heading.
Nile Bakery	Second-level heading for a section.
<nav aria-label="Footer">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.

Line	What it does
Sourdough loaf	A hyperlink; href gives the destination.
Croissant	One list item.
<address>Cairo, Egypt <a href="mailto:hello@bakery.example">hell...	Contact information for the page or article.
<p class="legal">© 2026 Nile Bakery · <a href="privacy....	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
flex: 1;	All items share free space equally.
padding: 2rem 1rem;	Space inside the element between its border and content.
background: #1b2431;	Background colour or image.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
font-size: 1rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .06em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid #334155;	A top border used as an accent or separator.
text-align: center;	Centres inline content such as text.

Check your work

- Footer sits at the bottom even with little content

- Links are readable on the dark background
- address not italic
- Columns stack on phones

Exercises

1. Add social media icons as SVG links.
2. Add a newsletter form in a fourth column.
3. Make the 'Back to top' link smooth-scroll with scroll-behavior.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 228: Site footer for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 1 | Files: index.html, styles.css

Brief

Build a three-column footer (about, links, contact) that stays at the bottom of short pages, with a legal line underneath.

Learning goals

- Make a sticky footer with flex column body
- Use address for contact details
- Lay out columns with auto-fit grid

Elements and CSS used

HTML elements	CSS features
footer, section, nav, h2, ul, li, a, address, br, p	min-height: 100vh, flex: 1, grid, text-transform, border-top, font-size

Build guide

1. Write main content followed by <footer class="site-footer">.
2. Inside, add a .cols div with three blocks: section, nav, section.
3. Add the legal paragraph after .cols.
4. Make body a flex column with min-height 100vh and main flex: 1 - this pushes the footer down.
5. Grid the columns.
6. Style headings small and uppercase; reset list styles.

Project 228: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Pyramid Fitness</h1>
    <p>Scroll down to see the footer.</p>
  </main>
  <footer class="site-footer">
    <div class="cols">
      <section>
        <h2>Pyramid Fitness</h2>
        <p>Train smarter, feel stronger.</p>
      </section>
      <nav aria-label="Footer">
        <h2>Classes</h2>
        <ul>
    <li><a href="#">Morning yoga</a></li>
    <li><a href="#">Strength circuit</a></li>
    <li><a href="#">Spinning</a></li>
    <li><a href="#">Personal training</a></li>
        </ul>
      </nav>
      <section>
        <h2>Contact</h2>
        <address>6th of October, Egypt<br><a href="mailto:hello@gym.
example">hello@gym.example</a><br><a href="tel:+20100000000">+20 100
000 0000</a></address>
      </section>
    </div>
    <p class="legal">&copy; 2026 Pyramid Fitness &middot; <a
href="privacy.html">Privacy</a> &middot; <a href="#top">Back to top</
a></p>
  </footer>
</body>
</html>
```

Project 228: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
body { min-height: 100vh; display: flex; flex-direction: column; }
main { flex: 1; padding: 2rem 1rem; }
.site-footer { background: #1b2431; color: #d5dbe5; padding: 2.5rem
1rem 1rem; }
.cols { max-width: 60rem; margin: 0 auto; display: grid; gap: 2rem;
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.site-footer h2 { color: #fff; font-size: 1rem; text-transform:
uppercase; letter-spacing: .06em; margin: 0 0 .75rem; }
.site-footer ul { list-style: none; padding: 0; margin: 0; }
.site-footer li { margin-bottom: .4rem; }
.site-footer a { color: #fff; }
address { font-style: normal; line-height: 1.8; }
.legal { max-width: 60rem; margin: 2rem auto 0; padding-top: 1rem;
border-top: 1px solid #334155; font-size: .85rem; text-align: center;
}
```

Project 228 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Pyramid Fitness	The main heading; only one per page.
Scroll down to see the footer.	A paragraph of text.
<footer class="site-footer">	Footer of the page or of a section.
	Generic block container for grouping and layout.
<section>	A thematic group of content, normally with its own heading.
Pyramid Fitness	Second-level heading for a section.
<nav aria-label="Footer">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.

Line	What it does
Morning yoga	A hyperlink; href gives the destination.
Strength circuit	One list item.
<address>6th of October, Egypt <a href="mailto:hello@gym.example...	Contact information for the page or article.
<p class="legal">© 2026 Pyramid Fitness · <a href="priv...	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
flex: 1;	All items share free space equally.
padding: 2rem 1rem;	Space inside the element between its border and content.
background: #1b2431;	Background colour or image.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
font-size: 1rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .06em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid #334155;	A top border used as an accent or separator.
text-align: center;	Centres inline content such as text.

Check your work

- Footer sits at the bottom even with little content

- Links are readable on the dark background
- address not italic
- Columns stack on phones

Exercises

1. Add social media icons as SVG links.
2. Add a newsletter form in a fourth column.
3. Make the 'Back to top' link smooth-scroll with scroll-behavior.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 229: Site footer for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 1 | Files: index.html, styles.css

Brief

Build a three-column footer (about, links, contact) that stays at the bottom of short pages, with a legal line underneath.

Learning goals

- Make a sticky footer with flex column body
- Use address for contact details
- Lay out columns with auto-fit grid

Elements and CSS used

HTML elements	CSS features
footer, section, nav, h2, ul, li, a, address, br, p	min-height: 100vh, flex: 1, grid, text-transform, border-top, font-size

Build guide

1. Write main content followed by <footer class="site-footer">.
2. Inside, add a .cols div with three blocks: section, nav, section.
3. Add the legal paragraph after .cols.
4. Make body a flex column with min-height 100vh and main flex: 1 - this pushes the footer down.
5. Grid the columns.
6. Style headings small and uppercase; reset list styles.

Project 229: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Delta Dental Clinic</h1>
    <p>Scroll down to see the footer.</p>
  </main>
  <footer class="site-footer">
    <div class="cols">
      <section>
        <h2>Delta Dental Clinic</h2>
        <p>Gentle care for the whole family.</p>
      </section>
      <nav aria-label="Footer">
        <h2>Services</h2>
        <ul>
    <li><a href="#">Check-up</a></li>
    <li><a href="#">Whitening</a></li>
    <li><a href="#">Filling</a></li>
    <li><a href="#">Braces consultation</a></li>
        </ul>
      </nav>
      <section>
        <h2>Contact</h2>
        <address>Mansoura, Egypt<br><a href="mailto:hello@clinic.
example">hello@clinic.example</a><br><a href="tel:+20100000000">+20
100 000 0000</a></address>
      </section>
    </div>
    <p class="legal">&copy; 2026 Delta Dental Clinic &middot; <a
href="privacy.html">Privacy</a> &middot; <a href="#top">Back to top</
a></p>
  </footer>
</body>
</html>
```

Project 229: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
body { min-height: 100vh; display: flex; flex-direction: column; }
main { flex: 1; padding: 2rem 1rem; }
.site-footer { background: #1b2431; color: #d5dbe5; padding: 2.5rem
1rem 1rem; }
.cols { max-width: 60rem; margin: 0 auto; display: grid; gap: 2rem;
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.site-footer h2 { color: #fff; font-size: 1rem; text-transform:
uppercase; letter-spacing: .06em; margin: 0 0 .75rem; }
.site-footer ul { list-style: none; padding: 0; margin: 0; }
.site-footer li { margin-bottom: .4rem; }
.site-footer a { color: #fff; }
address { font-style: normal; line-height: 1.8; }
.legal { max-width: 60rem; margin: 2rem auto 0; padding-top: 1rem;
border-top: 1px solid #334155; font-size: .85rem; text-align: center;
}
```

Project 229 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Delta Dental Clinic	The main heading; only one per page.
Scroll down to see the footer.	A paragraph of text.
<footer class="site-footer">	Footer of the page or of a section.
	Generic block container for grouping and layout.
<section>	A thematic group of content, normally with its own heading.
Delta Dental Clinic	Second-level heading for a section.
<nav aria-label="Footer">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.

Line	What it does
Check-up	A hyperlink; href gives the destination.
Whitening	One list item.
<address>Mansoura, Egypt <a href="mailto:hello@clinic.example">h...	Contact information for the page or article.
<p class="legal">© 2026 Delta Dental Clinic · <a href="...	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
flex: 1;	All items share free space equally.
padding: 2rem 1rem;	Space inside the element between its border and content.
background: #1b2431;	Background colour or image.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
font-size: 1rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .06em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid #334155;	A top border used as an accent or separator.
text-align: center;	Centres inline content such as text.

Check your work

- Footer sits at the bottom even with little content

- Links are readable on the dark background
- address not italic
- Columns stack on phones

Exercises

1. Add social media icons as SVG links.
2. Add a newsletter form in a fourth column.
3. Make the 'Back to top' link smooth-scroll with scroll-behavior.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 230: Site footer for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 1 | Files: index.html, styles.css

Brief

Build a three-column footer (about, links, contact) that stays at the bottom of short pages, with a legal line underneath.

Learning goals

- Make a sticky footer with flex column body
- Use address for contact details
- Lay out columns with auto-fit grid

Elements and CSS used

HTML elements	CSS features
footer, section, nav, h2, ul, li, a, address, br, p	min-height: 100vh, flex: 1, grid, text-transform, border-top, font-size

Build guide

1. Write main content followed by <footer class="site-footer">.
2. Inside, add a .cols div with three blocks: section, nav, section.
3. Add the legal paragraph after .cols.
4. Make body a flex column with min-height 100vh and main flex: 1 - this pushes the footer down.
5. Grid the columns.
6. Style headings small and uppercase; reset list styles.

Project 230: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Red Sea Travel</h1>
    <p>Scroll down to see the footer.</p>
  </main>
  <footer class="site-footer">
    <div class="cols">
      <section>
        <h2>Red Sea Travel</h2>
        <p>Discover Egypt from desert to reef.</p>
      </section>
      <nav aria-label="Footer">
        <h2>Tours</h2>
        <ul>
    <li><a href="#">Luxor day trip</a></li>
    <li><a href="#">Snorkelling</a></li>
    <li><a href="#">Desert safari</a></li>
    <li><a href="#">Nile cruise</a></li>
        </ul>
      </nav>
      <section>
        <h2>Contact</h2>
        <address>Hurghada, Egypt<br><a href="mailto:hello@travel.
example">hello@travel.example</a><br><a href="tel:+20100000000">+20
100 000 0000</a></address>
      </section>
    </div>
    <p class="legal">&copy; 2026 Red Sea Travel &middot; <a
href="privacy.html">Privacy</a> &middot; <a href="#top">Back to top</
a></p>
  </footer>
</body>
</html>
```

Project 230: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
body { min-height: 100vh; display: flex; flex-direction: column; }
main { flex: 1; padding: 2rem 1rem; }
.site-footer { background: #1b2431; color: #d5dbe5; padding: 2.5rem
1rem 1rem; }
.cols { max-width: 60rem; margin: 0 auto; display: grid; gap: 2rem;
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.site-footer h2 { color: #fff; font-size: 1rem; text-transform:
uppercase; letter-spacing: .06em; margin: 0 0 .75rem; }
.site-footer ul { list-style: none; padding: 0; margin: 0; }
.site-footer li { margin-bottom: .4rem; }
.site-footer a { color: #fff; }
address { font-style: normal; line-height: 1.8; }
.legal { max-width: 60rem; margin: 2rem auto 0; padding-top: 1rem;
border-top: 1px solid #334155; font-size: .85rem; text-align: center;
}
```

Project 230 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Red Sea Travel	The main heading; only one per page.
Scroll down to see the footer.	A paragraph of text.
<footer class="site-footer">	Footer of the page or of a section.
	Generic block container for grouping and layout.
<section>	A thematic group of content, normally with its own heading.
Red Sea Travel	Second-level heading for a section.
<nav aria-label="Footer">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.

Line	What it does
Luxor day trip	A hyperlink; href gives the destination.
Snorkelling 	One list item.
<address>Hurghada, Egypt <a href="mailto:hello@travel.example">h...	Contact information for the page or article.
<p class="legal">© 2026 Red Sea Travel · <a href="priva...	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
flex: 1;	All items share free space equally.
padding: 2rem 1rem;	Space inside the element between its border and content.
background: #1b2431;	Background colour or image.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
font-size: 1rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .06em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid #334155;	A top border used as an accent or separator.
text-align: center;	Centres inline content such as text.

Check your work

- Footer sits at the bottom even with little content

- Links are readable on the dark background
- address not italic
- Columns stack on phones

Exercises

1. Add social media icons as SVG links.
2. Add a newsletter form in a fourth column.
3. Make the 'Back to top' link smooth-scroll with scroll-behavior.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 231: Site footer for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Build a three-column footer (about, links, contact) that stays at the bottom of short pages, with a legal line underneath.

Learning goals

- Make a sticky footer with flex column body
- Use address for contact details
- Lay out columns with auto-fit grid

Elements and CSS used

HTML elements	CSS features
footer, section, nav, h2, ul, li, a, address, br, p	min-height: 100vh, flex: 1, grid, text-transform, border-top, font-size

Build guide

1. Write main content followed by <footer class="site-footer">.
2. Inside, add a .cols div with three blocks: section, nav, section.
3. Add the legal paragraph after .cols.
4. Make body a flex column with min-height 100vh and main flex: 1 - this pushes the footer down.
5. Grid the columns.
6. Style headings small and uppercase; reset list styles.

Project 231: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Lotus Language School</h1>
    <p>Scroll down to see the footer.</p>
  </main>
  <footer class="site-footer">
    <div class="cols">
      <section>
        <h2>Lotus Language School</h2>
        <p>Learn English, French and German in small groups.</p>
      </section>
      <nav aria-label="Footer">
        <h2>Courses</h2>
        <ul>
    <li><a href="#">English A1</a></li>
    <li><a href="#">French B1</a></li>
    <li><a href="#">German A2</a></li>
    <li><a href="#">IELTS preparation</a></li>
        </ul>
      </nav>
      <section>
        <h2>Contact</h2>
        <address>Alexandria, Egypt<br><a href="mailto:hello@school.
example">hello@school.example</a><br><a href="tel:+20100000000">+20
100 000 0000</a></address>
      </section>
    </div>
    <p class="legal">&copy; 2026 Lotus Language School &middot; <a
href="privacy.html">Privacy</a> &middot; <a href="#top">Back to top</
a></p>
  </footer>
</body>
</html>
```

Project 231: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
body { min-height: 100vh; display: flex; flex-direction: column; }
main { flex: 1; padding: 2rem 1rem; }
.site-footer { background: #1b2431; color: #d5dbe5; padding: 2.5rem
1rem 1rem; }
.cols { max-width: 60rem; margin: 0 auto; display: grid; gap: 2rem;
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.site-footer h2 { color: #fff; font-size: 1rem; text-transform:
uppercase; letter-spacing: .06em; margin: 0 0 .75rem; }
.site-footer ul { list-style: none; padding: 0; margin: 0; }
.site-footer li { margin-bottom: .4rem; }
.site-footer a { color: #fff; }
address { font-style: normal; line-height: 1.8; }
.legal { max-width: 60rem; margin: 2rem auto 0; padding-top: 1rem;
border-top: 1px solid #334155; font-size: .85rem; text-align: center;
}
```

Project 231 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Lotus Language School	The main heading; only one per page.
Scroll down to see the footer.	A paragraph of text.
<footer class="site-footer">	Footer of the page or of a section.
	Generic block container for grouping and layout.
<section>	A thematic group of content, normally with its own heading.
Lotus Language School	Second-level heading for a section.
<nav aria-label="Footer">	A block of navigation links; aria-label names it for screen readers.

Line	What it does
	Unordered (bulleted) list.
English A1	A hyperlink; href gives the destination.
French B1	One list item.
<address>Alexandria, Egypt <a href="mailto:hello@school.example"...	Contact information for the page or article.
<p class="legal">© 2026 Lotus Language School · <a href...	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
flex: 1;	All items share free space equally.
padding: 2rem 1rem;	Space inside the element between its border and content.
background: #1b2431;	Background colour or image.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
font-size: 1rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .06em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid #334155;	A top border used as an accent or separator.
text-align: center;	Centres inline content such as text.

Check your work

- Footer sits at the bottom even with little content

- Links are readable on the dark background
- address not italic
- Columns stack on phones

Exercises

1. Add social media icons as SVG links.
2. Add a newsletter form in a fourth column.
3. Make the 'Back to top' link smooth-scroll with scroll-behavior.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 232: Site footer for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 1 | Files: index.html, styles.css

Brief

Build a three-column footer (about, links, contact) that stays at the bottom of short pages, with a legal line underneath.

Learning goals

- Make a sticky footer with flex column body
- Use address for contact details
- Lay out columns with auto-fit grid

Elements and CSS used

HTML elements	CSS features
footer, section, nav, h2, ul, li, a, address, br, p	min-height: 100vh, flex: 1, grid, text-transform, border-top, font-size

Build guide

1. Write main content followed by <footer class="site-footer">.
2. Inside, add a .cols div with three blocks: section, nav, section.
3. Add the legal paragraph after .cols.
4. Make body a flex column with min-height 100vh and main flex: 1 - this pushes the footer down.
5. Grid the columns.
6. Style headings small and uppercase; reset list styles.

Project 232: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Green Leaf Cafe</h1>
    <p>Scroll down to see the footer.</p>
  </main>
  <footer class="site-footer">
    <div class="cols">
      <section>
        <h2>Green Leaf Cafe</h2>
        <p>Specialty coffee and quiet corners.</p>
      </section>
      <nav aria-label="Footer">
        <h2>Drinks</h2>
        <ul>
    <li><a href="#">Flat white</a></li>
    <li><a href="#">Cold brew</a></li>
    <li><a href="#">Hibiscus iced tea</a></li>
    <li><a href="#">Cheesecake</a></li>
        </ul>
      </nav>
      <section>
        <h2>Contact</h2>
        <address>Zamalek, Egypt<br><a href="mailto:hello@cafe.
example">hello@cafe.example</a><br><a href="tel:+20100000000">+20 100
000 0000</a></address>
      </section>
    </div>
    <p class="legal">&copy; 2026 Green Leaf Cafe &middot; <a
href="privacy.html">Privacy</a> &middot; <a href="#top">Back to top</
a></p>
  </footer>
</body>
</html>
```

Project 232: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
body { min-height: 100vh; display: flex; flex-direction: column; }
main { flex: 1; padding: 2rem 1rem; }
.site-footer { background: #1b2431; color: #d5dbe5; padding: 2.5rem
1rem 1rem; }
.cols { max-width: 60rem; margin: 0 auto; display: grid; gap: 2rem;
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.site-footer h2 { color: #fff; font-size: 1rem; text-transform:
uppercase; letter-spacing: .06em; margin: 0 0 .75rem; }
.site-footer ul { list-style: none; padding: 0; margin: 0; }
.site-footer li { margin-bottom: .4rem; }
.site-footer a { color: #fff; }
address { font-style: normal; line-height: 1.8; }
.legal { max-width: 60rem; margin: 2rem auto 0; padding-top: 1rem;
border-top: 1px solid #334155; font-size: .85rem; text-align: center;
}
```

Project 232 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Green Leaf Cafe	The main heading; only one per page.
Scroll down to see the footer.	A paragraph of text.
<footer class="site-footer">	Footer of the page or of a section.
	Generic block container for grouping and layout.
<section>	A thematic group of content, normally with its own heading.
Green Leaf Cafe	Second-level heading for a section.
<nav aria-label="Footer">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.

Line	What it does
Flat white	A hyperlink; href gives the destination.
Cold brew	One list item.
<address>Zamalek, Egypt <a href="mailto:hello@cafe.example">hell...	Contact information for the page or article.
<p class="legal">© 2026 Green Leaf Cafe · <a href="priv...	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
flex: 1;	All items share free space equally.
padding: 2rem 1rem;	Space inside the element between its border and content.
background: #1b2431;	Background colour or image.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
font-size: 1rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .06em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid #334155;	A top border used as an accent or separator.
text-align: center;	Centres inline content such as text.

Check your work

- Footer sits at the bottom even with little content

- Links are readable on the dark background
- address not italic
- Columns stack on phones

Exercises

1. Add social media icons as SVG links.
2. Add a newsletter form in a fourth column.
3. Make the 'Back to top' link smooth-scroll with scroll-behavior.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 233: Site footer for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 1 | Files: index.html, styles.css

Brief

Build a three-column footer (about, links, contact) that stays at the bottom of short pages, with a legal line underneath.

Learning goals

- Make a sticky footer with flex column body
- Use address for contact details
- Lay out columns with auto-fit grid

Elements and CSS used

HTML elements	CSS features
footer, section, nav, h2, ul, li, a, address, br, p	min-height: 100vh, flex: 1, grid, text-transform, border-top, font-size

Build guide

1. Write main content followed by <footer class="site-footer">.
2. Inside, add a .cols div with three blocks: section, nav, section.
3. Add the legal paragraph after .cols.
4. Make body a flex column with min-height 100vh and main flex: 1 - this pushes the footer down.
5. Grid the columns.
6. Style headings small and uppercase; reset list styles.

Project 233: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Sinai Trekking Club</h1>
    <p>Scroll down to see the footer.</p>
  </main>
  <footer class="site-footer">
    <div class="cols">
      <section>
        <h2>Sinai Trekking Club</h2>
        <p>Guided mountain walks for every level.</p>
      </section>
      <nav aria-label="Footer">
        <h2>Hikes</h2>
        <ul>
    <li><a href="#">Mount Sinai sunrise</a></li>
    <li><a href="#">Blue Desert loop</a></li>
    <li><a href="#">Wadi Gnai</a></li>
    <li><a href="#">Three-day traverse</a></li>
        </ul>
      </nav>
      <section>
        <h2>Contact</h2>
        <address>Saint Catherine, Egypt<br><a href="mailto:
hello@trekking.example">hello@trekking.example</a><br><a href="tel:
+20100000000">+20 100 000 0000</a></address>
      </section>
    </div>
    <p class="legal">&copy; 2026 Sinai Trekking Club &middot; <a
href="privacy.html">Privacy</a> &middot; <a href="#top">Back to top</
a></p>
  </footer>
</body>
</html>
```

Project 233: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
body { min-height: 100vh; display: flex; flex-direction: column; }
main { flex: 1; padding: 2rem 1rem; }
.site-footer { background: #1b2431; color: #d5dbe5; padding: 2.5rem
1rem 1rem; }
.cols { max-width: 60rem; margin: 0 auto; display: grid; gap: 2rem;
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.site-footer h2 { color: #fff; font-size: 1rem; text-transform:
uppercase; letter-spacing: .06em; margin: 0 0 .75rem; }
.site-footer ul { list-style: none; padding: 0; margin: 0; }
.site-footer li { margin-bottom: .4rem; }
.site-footer a { color: #fff; }
address { font-style: normal; line-height: 1.8; }
.legal { max-width: 60rem; margin: 2rem auto 0; padding-top: 1rem;
border-top: 1px solid #334155; font-size: .85rem; text-align: center;
}
```

Project 233 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Sinai Trekking Club	The main heading; only one per page.
Scroll down to see the footer.	A paragraph of text.
<footer class="site-footer">	Footer of the page or of a section.
	Generic block container for grouping and layout.
<section>	A thematic group of content, normally with its own heading.
Sinai Trekking Club	Second-level heading for a section.
<nav aria-label="Footer">	A block of navigation links; aria-label names it for screen readers.

Line	What it does
	Unordered (bulleted) list.
Mount Sinai sunrise	A hyperlink; href gives the destination.
Blue Desert loop	One list item.
<address>Saint Catherine, Egypt <a href="mailto:hello@trekking.e...	Contact information for the page or article.
<p class="legal">© 2026 Sinai Trekking Club · <a href="...	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
flex: 1;	All items share free space equally.
padding: 2rem 1rem;	Space inside the element between its border and content.
background: #1b2431;	Background colour or image.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
font-size: 1rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .06em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid #334155;	A top border used as an accent or separator.
text-align: center;	Centres inline content such as text.

Check your work

- Footer sits at the bottom even with little content

- Links are readable on the dark background
- address not italic
- Columns stack on phones

Exercises

1. Add social media icons as SVG links.
2. Add a newsletter form in a fourth column.
3. Make the 'Back to top' link smooth-scroll with scroll-behavior.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 234: Site footer for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 1 | Files: index.html, styles.css

Brief

Build a three-column footer (about, links, contact) that stays at the bottom of short pages, with a legal line underneath.

Learning goals

- Make a sticky footer with flex column body
- Use address for contact details
- Lay out columns with auto-fit grid

Elements and CSS used

HTML elements	CSS features
footer, section, nav, h2, ul, li, a, address, br, p	min-height: 100vh, flex: 1, grid, text-transform, border-top, font-size

Build guide

1. Write main content followed by <footer class="site-footer">.
2. Inside, add a .cols div with three blocks: section, nav, section.
3. Add the legal paragraph after .cols.
4. Make body a flex column with min-height 100vh and main flex: 1 - this pushes the footer down.
5. Grid the columns.
6. Style headings small and uppercase; reset list styles.

Project 234: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Horizon Photography</h1>
    <p>Scroll down to see the footer.</p>
  </main>
  <footer class="site-footer">
    <div class="cols">
      <section>
        <h2>Horizon Photography</h2>
        <p>Portraits, weddings and product photography.</p>
      </section>
      <nav aria-label="Footer">
        <h2>Sessions</h2>
        <ul>
    <li><a href="#">Portrait session</a></li>
    <li><a href="#">Wedding day</a></li>
    <li><a href="#">Product shoot</a></li>
    <li><a href="#">Family session</a></li>
        </ul>
      </nav>
      <section>
        <h2>Contact</h2>
        <address>Maadi, Egypt<br><a href="mailto:hello@photo.
example">hello@photo.example</a><br><a href="tel:+20100000000">+20
100 000 0000</a></address>
      </section>
    </div>
    <p class="legal">&copy; 2026 Horizon Photography &middot; <a
href="privacy.html">Privacy</a> &middot; <a href="#top">Back to top</
a></p>
  </footer>
</body>
</html>
```

Project 234: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
body { min-height: 100vh; display: flex; flex-direction: column; }
main { flex: 1; padding: 2rem 1rem; }
.site-footer { background: #1b2431; color: #d5dbe5; padding: 2.5rem
1rem 1rem; }
.cols { max-width: 60rem; margin: 0 auto; display: grid; gap: 2rem;
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.site-footer h2 { color: #fff; font-size: 1rem; text-transform:
uppercase; letter-spacing: .06em; margin: 0 0 .75rem; }
.site-footer ul { list-style: none; padding: 0; margin: 0; }
.site-footer li { margin-bottom: .4rem; }
.site-footer a { color: #fff; }
address { font-style: normal; line-height: 1.8; }
.legal { max-width: 60rem; margin: 2rem auto 0; padding-top: 1rem;
border-top: 1px solid #334155; font-size: .85rem; text-align: center;
}
```

Project 234 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Horizon Photography	The main heading; only one per page.
Scroll down to see the footer.	A paragraph of text.
<footer class="site-footer">	Footer of the page or of a section.
	Generic block container for grouping and layout.
<section>	A thematic group of content, normally with its own heading.
Horizon Photography	Second-level heading for a section.
<nav aria-label="Footer">	A block of navigation links; aria-label names it for screen readers.

Line	What it does
	Unordered (bulleted) list.
Portrait session	A hyperlink; href gives the destination.
Wedding day	One list item.
<address>Maadi, Egypt <a href="mailto:hello@photo.example">hello...	Contact information for the page or article.
<p class="legal">© 2026 Horizon Photography · <a href="...	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
flex: 1;	All items share free space equally.
padding: 2rem 1rem;	Space inside the element between its border and content.
background: #1b2431;	Background colour or image.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
font-size: 1rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .06em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid #334155;	A top border used as an accent or separator.
text-align: center;	Centres inline content such as text.

Check your work

- Footer sits at the bottom even with little content

- Links are readable on the dark background
- address not italic
- Columns stack on phones

Exercises

1. Add social media icons as SVG links.
2. Add a newsletter form in a fourth column.
3. Make the 'Back to top' link smooth-scroll with scroll-behavior.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 235: Site footer for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 1 | Files: index.html, styles.css

Brief

Build a three-column footer (about, links, contact) that stays at the bottom of short pages, with a legal line underneath.

Learning goals

- Make a sticky footer with flex column body
- Use address for contact details
- Lay out columns with auto-fit grid

Elements and CSS used

HTML elements	CSS features
footer, section, nav, h2, ul, li, a, address, br, p	min-height: 100vh, flex: 1, grid, text-transform, border-top, font-size

Build guide

1. Write main content followed by <footer class="site-footer">.
2. Inside, add a .cols div with three blocks: section, nav, section.
3. Add the legal paragraph after .cols.
4. Make body a flex column with min-height 100vh and main flex: 1 - this pushes the footer down.
5. Grid the columns.
6. Style headings small and uppercase; reset list styles.

Project 235: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Papyrus Stationery</h1>
    <p>Scroll down to see the footer.</p>
  </main>
  <footer class="site-footer">
    <div class="cols">
      <section>
        <h2>Papyrus Stationery</h2>
        <p>Notebooks, pens and paper made in Egypt.</p>
      </section>
      <nav aria-label="Footer">
        <h2>Products</h2>
        <ul>
    <li><a href="#">Dotted notebook</a></li>
    <li><a href="#">Fountain pen</a></li>
    <li><a href="#">Washi tape set</a></li>
    <li><a href="#">Desk planner</a></li>
        </ul>
      </nav>
      <section>
        <h2>Contact</h2>
        <address>Heliopolis, Egypt<br><a href="mailto:
hello@stationery.example">hello@stationery.example</a><br><a
href="tel:+20100000000">+20 100 000 0000</a></address>
      </section>
    </div>
    <p class="legal">&copy; 2026 Papyrus Stationery &middot; <a
href="privacy.html">Privacy</a> &middot; <a href="#top">Back to top</
a></p>
  </footer>
</body>
</html>
```

Project 235: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
body { min-height: 100vh; display: flex; flex-direction: column; }
main { flex: 1; padding: 2rem 1rem; }
.site-footer { background: #1b2431; color: #d5dbe5; padding: 2.5rem
1rem 1rem; }
.cols { max-width: 60rem; margin: 0 auto; display: grid; gap: 2rem;
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.site-footer h2 { color: #fff; font-size: 1rem; text-transform:
uppercase; letter-spacing: .06em; margin: 0 0 .75rem; }
.site-footer ul { list-style: none; padding: 0; margin: 0; }
.site-footer li { margin-bottom: .4rem; }
.site-footer a { color: #fff; }
address { font-style: normal; line-height: 1.8; }
.legal { max-width: 60rem; margin: 2rem auto 0; padding-top: 1rem;
border-top: 1px solid #334155; font-size: .85rem; text-align: center;
}
```

Project 235 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Papyrus Stationery	The main heading; only one per page.
Scroll down to see the footer.	A paragraph of text.
<footer class="site-footer">	Footer of the page or of a section.
	Generic block container for grouping and layout.
<section>	A thematic group of content, normally with its own heading.
Papyrus Stationery	Second-level heading for a section.
<nav aria-label="Footer">	A block of navigation links; aria-label names it for screen readers.

Line	What it does
	Unordered (bulleted) list.
Dotted notebook	A hyperlink; href gives the destination.
Fountain pen	One list item.
<address>Heliopolis, Egypt <a href="mailto:hello@stationery.exam...	Contact information for the page or article.
<p class="legal">© 2026 Papyrus Stationery · <a href="p...	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
flex: 1;	All items share free space equally.
padding: 2rem 1rem;	Space inside the element between its border and content.
background: #1b2431;	Background colour or image.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
font-size: 1rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .06em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid #334155;	A top border used as an accent or separator.
text-align: center;	Centres inline content such as text.

Check your work

- Footer sits at the bottom even with little content

- Links are readable on the dark background
- address not italic
- Columns stack on phones

Exercises

1. Add social media icons as SVG links.
2. Add a newsletter form in a fourth column.
3. Make the 'Back to top' link smooth-scroll with scroll-behavior.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 236: Site footer for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 1 | Files: index.html, styles.css

Brief

Build a three-column footer (about, links, contact) that stays at the bottom of short pages, with a legal line underneath.

Learning goals

- Make a sticky footer with flex column body
- Use address for contact details
- Lay out columns with auto-fit grid

Elements and CSS used

HTML elements	CSS features
footer, section, nav, h2, ul, li, a, address, br, p	min-height: 100vh, flex: 1, grid, text-transform, border-top, font-size

Build guide

1. Write main content followed by <footer class="site-footer">.
2. Inside, add a .cols div with three blocks: section, nav, section.
3. Add the legal paragraph after .cols.
4. Make body a flex column with min-height 100vh and main flex: 1 - this pushes the footer down.
5. Grid the columns.
6. Style headings small and uppercase; reset list styles.

Project 236: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Oasis Plant Nursery</h1>
    <p>Scroll down to see the footer.</p>
  </main>
  <footer class="site-footer">
    <div class="cols">
      <section>
        <h2>Oasis Plant Nursery</h2>
        <p>Indoor plants and gardening advice.</p>
      </section>
      <nav aria-label="Footer">
        <h2>Plants</h2>
        <ul>
    <li><a href="#">Monstera</a></li>
    <li><a href="#">Snake plant</a></li>
    <li><a href="#">Basil pot</a></li>
    <li><a href="#">Olive tree</a></li>
        </ul>
      </nav>
      <section>
        <h2>Contact</h2>
        <address>Sheikh Zayed, Egypt<br><a href="mailto:hello@plants.
example">hello@plants.example</a><br><a href="tel:+20100000000">+20
100 000 0000</a></address>
      </section>
    </div>
    <p class="legal">&copy; 2026 Oasis Plant Nursery &middot; <a
href="privacy.html">Privacy</a> &middot; <a href="#top">Back to top</
a></p>
  </footer>
</body>
</html>
```

Project 236: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
body { min-height: 100vh; display: flex; flex-direction: column; }
main { flex: 1; padding: 2rem 1rem; }
.site-footer { background: #1b2431; color: #d5dbe5; padding: 2.5rem
1rem 1rem; }
.cols { max-width: 60rem; margin: 0 auto; display: grid; gap: 2rem;
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.site-footer h2 { color: #fff; font-size: 1rem; text-transform:
uppercase; letter-spacing: .06em; margin: 0 0 .75rem; }
.site-footer ul { list-style: none; padding: 0; margin: 0; }
.site-footer li { margin-bottom: .4rem; }
.site-footer a { color: #fff; }
address { font-style: normal; line-height: 1.8; }
.legal { max-width: 60rem; margin: 2rem auto 0; padding-top: 1rem;
border-top: 1px solid #334155; font-size: .85rem; text-align: center;
}
```

Project 236 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Oasis Plant Nursery	The main heading; only one per page.
Scroll down to see the footer.	A paragraph of text.
<footer class="site-footer">	Footer of the page or of a section.
	Generic block container for grouping and layout.
<section>	A thematic group of content, normally with its own heading.
Oasis Plant Nursery	Second-level heading for a section.
<nav aria-label="Footer">	A block of navigation links; aria-label names it for screen readers.

Line	What it does
	Unordered (bulleted) list.
Monstera	A hyperlink; href gives the destination.
Snake plant	One list item.
<address>Sheikh Zayed, Egypt <a href="mailto:hello@plants.exampl...	Contact information for the page or article.
<p class="legal">© 2026 Oasis Plant Nursery · <a href="...	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
flex: 1;	All items share free space equally.
padding: 2rem 1rem;	Space inside the element between its border and content.
background: #1b2431;	Background colour or image.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
font-size: 1rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .06em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid #334155;	A top border used as an accent or separator.
text-align: center;	Centres inline content such as text.

Check your work

- Footer sits at the bottom even with little content

- Links are readable on the dark background
- address not italic
- Columns stack on phones

Exercises

1. Add social media icons as SVG links.
2. Add a newsletter form in a fourth column.
3. Make the 'Back to top' link smooth-scroll with scroll-behavior.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 237: Site footer for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 1 | Files: index.html, styles.css

Brief

Build a three-column footer (about, links, contact) that stays at the bottom of short pages, with a legal line underneath.

Learning goals

- Make a sticky footer with flex column body
- Use address for contact details
- Lay out columns with auto-fit grid

Elements and CSS used

HTML elements	CSS features
footer, section, nav, h2, ul, li, a, address, br, p	min-height: 100vh, flex: 1, grid, text-transform, border-top, font-size

Build guide

1. Write main content followed by <footer class="site-footer">.
2. Inside, add a .cols div with three blocks: section, nav, section.
3. Add the legal paragraph after .cols.
4. Make body a flex column with min-height 100vh and main flex: 1 - this pushes the footer down.
5. Grid the columns.
6. Style headings small and uppercase; reset list styles.

Project 237: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cedar Furniture</h1>
    <p>Scroll down to see the footer.</p>
  </main>
  <footer class="site-footer">
    <div class="cols">
      <section>
        <h2>Cedar Furniture</h2>
        <p>Solid wood furniture made to order.</p>
      </section>
      <nav aria-label="Footer">
        <h2>Pieces</h2>
        <ul>
    <li><a href="#">Oak dining table</a></li>
    <li><a href="#">Bookshelf</a></li>
    <li><a href="#">Bedside table</a></li>
    <li><a href="#">Coffee table</a></li>
        </ul>
      </nav>
      <section>
        <h2>Contact</h2>
        <address>Damietta, Egypt<br><a href="mailto:hello@furniture.
example">hello@furniture.example</a><br><a href="tel:
+20100000000">+20 100 000 0000</a></address>
      </section>
    </div>
    <p class="legal">&copy; 2026 Cedar Furniture &middot; <a
href="privacy.html">Privacy</a> &middot; <a href="#top">Back to top</
a></p>
  </footer>
</body>
</html>
```

Project 237: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
body { min-height: 100vh; display: flex; flex-direction: column; }
main { flex: 1; padding: 2rem 1rem; }
.site-footer { background: #1b2431; color: #d5dbe5; padding: 2.5rem
1rem 1rem; }
.cols { max-width: 60rem; margin: 0 auto; display: grid; gap: 2rem;
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.site-footer h2 { color: #fff; font-size: 1rem; text-transform:
uppercase; letter-spacing: .06em; margin: 0 0 .75rem; }
.site-footer ul { list-style: none; padding: 0; margin: 0; }
.site-footer li { margin-bottom: .4rem; }
.site-footer a { color: #fff; }
address { font-style: normal; line-height: 1.8; }
.legal { max-width: 60rem; margin: 2rem auto 0; padding-top: 1rem;
border-top: 1px solid #334155; font-size: .85rem; text-align: center;
}
```

Project 237 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cedar Furniture	The main heading; only one per page.
Scroll down to see the footer.	A paragraph of text.
<footer class="site-footer">	Footer of the page or of a section.
	Generic block container for grouping and layout.
<section>	A thematic group of content, normally with its own heading.
Cedar Furniture	Second-level heading for a section.
<nav aria-label="Footer">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.

Line	What it does
Oak dining table	A hyperlink; href gives the destination.
Bookshelf	One list item.
<address>Damietta, Egypt <a href="mailto:hello@furniture.example...	Contact information for the page or article.
<p class="legal">© 2026 Cedar Furniture · <a href="priv...	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
flex: 1;	All items share free space equally.
padding: 2rem 1rem;	Space inside the element between its border and content.
background: #1b2431;	Background colour or image.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
font-size: 1rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .06em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid #334155;	A top border used as an accent or separator.
text-align: center;	Centres inline content such as text.

Check your work

- Footer sits at the bottom even with little content

- Links are readable on the dark background
- address not italic
- Columns stack on phones

Exercises

1. Add social media icons as SVG links.
2. Add a newsletter form in a fourth column.
3. Make the 'Back to top' link smooth-scroll with scroll-behavior.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 238: Site footer for Byte Repair

Theme: Byte Repair (Nasr City) | Level 1 | Files: index.html, styles.css

Brief

Build a three-column footer (about, links, contact) that stays at the bottom of short pages, with a legal line underneath.

Learning goals

- Make a sticky footer with flex column body
- Use address for contact details
- Lay out columns with auto-fit grid

Elements and CSS used

HTML elements	CSS features
footer, section, nav, h2, ul, li, a, address, br, p	min-height: 100vh, flex: 1, grid, text-transform, border-top, font-size

Build guide

1. Write main content followed by <footer class="site-footer">.
2. Inside, add a .cols div with three blocks: section, nav, section.
3. Add the legal paragraph after .cols.
4. Make body a flex column with min-height 100vh and main flex: 1 - this pushes the footer down.
5. Grid the columns.
6. Style headings small and uppercase; reset list styles.

Project 238: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Byte Repair</h1>
    <p>Scroll down to see the footer.</p>
  </main>
  <footer class="site-footer">
    <div class="cols">
      <section>
        <h2>Byte Repair</h2>
        <p>Phone and laptop repairs while you wait.</p>
      </section>
      <nav aria-label="Footer">
        <h2>Repairs</h2>
        <ul>
    <li><a href="#">Screen replacement</a></li>
    <li><a href="#">Battery swap</a></li>
    <li><a href="#">Laptop cleaning</a></li>
    <li><a href="#">Data recovery</a></li>
        </ul>
      </nav>
      <section>
        <h2>Contact</h2>
        <address>Nasr City, Egypt<br><a href="mailto:hello@repair.
example">hello@repair.example</a><br><a href="tel:+20100000000">+20
100 000 0000</a></address>
      </section>
    </div>
    <p class="legal">&copy; 2026 Byte Repair &middot; <a
href="privacy.html">Privacy</a> &middot; <a href="#top">Back to top</
a></p>
  </footer>
</body>
</html>
```

Project 238: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
body { min-height: 100vh; display: flex; flex-direction: column; }
main { flex: 1; padding: 2rem 1rem; }
.site-footer { background: #1b2431; color: #d5dbe5; padding: 2.5rem
1rem 1rem; }
.cols { max-width: 60rem; margin: 0 auto; display: grid; gap: 2rem;
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.site-footer h2 { color: #fff; font-size: 1rem; text-transform:
uppercase; letter-spacing: .06em; margin: 0 0 .75rem; }
.site-footer ul { list-style: none; padding: 0; margin: 0; }
.site-footer li { margin-bottom: .4rem; }
.site-footer a { color: #fff; }
address { font-style: normal; line-height: 1.8; }
.legal { max-width: 60rem; margin: 2rem auto 0; padding-top: 1rem;
border-top: 1px solid #334155; font-size: .85rem; text-align: center;
}
```

Project 238 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Byte Repair	The main heading; only one per page.
Scroll down to see the footer.	A paragraph of text.
<footer class="site-footer">	Footer of the page or of a section.
	Generic block container for grouping and layout.
<section>	A thematic group of content, normally with its own heading.
Byte Repair	Second-level heading for a section.
<nav aria-label="Footer">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.

Line	What it does
Screen replacement	A hyperlink; href gives the destination.
Battery swap	One list item.
<address>Nasr City, Egypt <a href="mailto:hello@repair.example">...	Contact information for the page or article.
<p class="legal">© 2026 Byte Repair · <a href="privacy....	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
flex: 1;	All items share free space equally.
padding: 2rem 1rem;	Space inside the element between its border and content.
background: #1b2431;	Background colour or image.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
font-size: 1rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .06em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid #334155;	A top border used as an accent or separator.
text-align: center;	Centres inline content such as text.

Check your work

- Footer sits at the bottom even with little content

- Links are readable on the dark background
- address not italic
- Columns stack on phones

Exercises

1. Add social media icons as SVG links.
2. Add a newsletter form in a fourth column.
3. Make the 'Back to top' link smooth-scroll with scroll-behavior.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 239: Site footer for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 1 | Files: index.html, styles.css

Brief

Build a three-column footer (about, links, contact) that stays at the bottom of short pages, with a legal line underneath.

Learning goals

- Make a sticky footer with flex column body
- Use address for contact details
- Lay out columns with auto-fit grid

Elements and CSS used

HTML elements	CSS features
footer, section, nav, h2, ul, li, a, address, br, p	min-height: 100vh, flex: 1, grid, text-transform, border-top, font-size

Build guide

1. Write main content followed by <footer class="site-footer">.
2. Inside, add a .cols div with three blocks: section, nav, section.
3. Add the legal paragraph after .cols.
4. Make body a flex column with min-height 100vh and main flex: 1 - this pushes the footer down.
5. Grid the columns.
6. Style headings small and uppercase; reset list styles.

Project 239: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Sahara Pet Care</h1>
    <p>Scroll down to see the footer.</p>
  </main>
  <footer class="site-footer">
    <div class="cols">
      <section>
        <h2>Sahara Pet Care</h2>
        <p>Grooming, boarding and vet visits.</p>
      </section>
      <nav aria-label="Footer">
        <h2>Services</h2>
        <ul>
    <li><a href="#">Full grooming</a></li>
    <li><a href="#">Day boarding</a></li>
    <li><a href="#">Vaccination</a></li>
    <li><a href="#">Dog walking</a></li>
        </ul>
      </nav>
      <section>
        <h2>Contact</h2>
        <address>New Cairo, Egypt<br><a href="mailto:hello@pets.
example">hello@pets.example</a><br><a href="tel:+20100000000">+20 100
000 0000</a></address>
      </section>
    </div>
    <p class="legal">&copy; 2026 Sahara Pet Care &middot; <a
href="privacy.html">Privacy</a> &middot; <a href="#top">Back to top</
a></p>
  </footer>
</body>
</html>
```

Project 239: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
body { min-height: 100vh; display: flex; flex-direction: column; }
main { flex: 1; padding: 2rem 1rem; }
.site-footer { background: #1b2431; color: #d5dbe5; padding: 2.5rem
1rem 1rem; }
.cols { max-width: 60rem; margin: 0 auto; display: grid; gap: 2rem;
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.site-footer h2 { color: #fff; font-size: 1rem; text-transform:
uppercase; letter-spacing: .06em; margin: 0 0 .75rem; }
.site-footer ul { list-style: none; padding: 0; margin: 0; }
.site-footer li { margin-bottom: .4rem; }
.site-footer a { color: #fff; }
address { font-style: normal; line-height: 1.8; }
.legal { max-width: 60rem; margin: 2rem auto 0; padding-top: 1rem;
border-top: 1px solid #334155; font-size: .85rem; text-align: center;
}
```

Project 239 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Sahara Pet Care	The main heading; only one per page.
Scroll down to see the footer.	A paragraph of text.
<footer class="site-footer">	Footer of the page or of a section.
	Generic block container for grouping and layout.
<section>	A thematic group of content, normally with its own heading.
Sahara Pet Care	Second-level heading for a section.
<nav aria-label="Footer">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.

Line	What it does
Full grooming	A hyperlink; href gives the destination.
Day boarding	One list item.
<address>New Cairo, Egypt <a href="mailto:hello@pets.example">he...	Contact information for the page or article.
<p class="legal">© 2026 Sahara Pet Care · <a href="priv...	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
flex: 1;	All items share free space equally.
padding: 2rem 1rem;	Space inside the element between its border and content.
background: #1b2431;	Background colour or image.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
font-size: 1rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .06em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid #334155;	A top border used as an accent or separator.
text-align: center;	Centres inline content such as text.

Check your work

- Footer sits at the bottom even with little content

- Links are readable on the dark background
- address not italic
- Columns stack on phones

Exercises

1. Add social media icons as SVG links.
2. Add a newsletter form in a fourth column.
3. Make the 'Back to top' link smooth-scroll with scroll-behavior.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 240: Site footer for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Build a three-column footer (about, links, contact) that stays at the bottom of short pages, with a legal line underneath.

Learning goals

- Make a sticky footer with flex column body
- Use address for contact details
- Lay out columns with auto-fit grid

Elements and CSS used

HTML elements	CSS features
footer, section, nav, h2, ul, li, a, address, br, p	min-height: 100vh, flex: 1, grid, text-transform, border-top, font-size

Build guide

1. Write main content followed by <footer class="site-footer">.
2. Inside, add a .cols div with three blocks: section, nav, section.
3. Add the legal paragraph after .cols.
4. Make body a flex column with min-height 100vh and main flex: 1 - this pushes the footer down.
5. Grid the columns.
6. Style headings small and uppercase; reset list styles.

Project 240: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Alexandria Sailing School</h1>
    <p>Scroll down to see the footer.</p>
  </main>
  <footer class="site-footer">
    <div class="cols">
      <section>
        <h2>Alexandria Sailing School</h2>
        <p>Learn to sail on the Mediterranean.</p>
      </section>
      <nav aria-label="Footer">
        <h2>Lessons</h2>
        <ul>
    <li><a href="#">Taster session</a></li>
    <li><a href="#">Beginner course</a></li>
    <li><a href="#">Racing clinic</a></li>
    <li><a href="#">Private lesson</a></li>
        </ul>
      </nav>
      <section>
        <h2>Contact</h2>
        <address>Alexandria, Egypt<br><a href="mailto:hello@sailing.
example">hello@sailing.example</a><br><a href="tel:+20100000000">+20
100 000 0000</a></address>
      </section>
    </div>
    <p class="legal">&copy; 2026 Alexandria Sailing School &middot;
<a href="privacy.html">Privacy</a> &middot; <a href="#top">Back to
top</a></p>
  </footer>
</body>
</html>
```

Project 240: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
body { min-height: 100vh; display: flex; flex-direction: column; }
main { flex: 1; padding: 2rem 1rem; }
.site-footer { background: #1b2431; color: #d5dbe5; padding: 2.5rem
1rem 1rem; }
.cols { max-width: 60rem; margin: 0 auto; display: grid; gap: 2rem;
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.site-footer h2 { color: #fff; font-size: 1rem; text-transform:
uppercase; letter-spacing: .06em; margin: 0 0 .75rem; }
.site-footer ul { list-style: none; padding: 0; margin: 0; }
.site-footer li { margin-bottom: .4rem; }
.site-footer a { color: #fff; }
address { font-style: normal; line-height: 1.8; }
.legal { max-width: 60rem; margin: 2rem auto 0; padding-top: 1rem;
border-top: 1px solid #334155; font-size: .85rem; text-align: center;
}
```

Project 240 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Alexandria Sailing School	The main heading; only one per page.
Scroll down to see the footer.	A paragraph of text.
<footer class="site-footer">	Footer of the page or of a section.
	Generic block container for grouping and layout.
<section>	A thematic group of content, normally with its own heading.
Alexandria Sailing School	Second-level heading for a section.
<nav aria-label="Footer">	A block of navigation links; aria-label names it for screen readers.

Line	What it does
	Unordered (bulleted) list.
Taster session	A hyperlink; href gives the destination.
Beginner course	One list item.
<address>Alexandria, Egypt <a href="mailto:hello@sailing.example...	Contact information for the page or article.
<p class="legal">© 2026 Alexandria Sailing School · <a ...	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
flex: 1;	All items share free space equally.
padding: 2rem 1rem;	Space inside the element between its border and content.
background: #1b2431;	Background colour or image.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
font-size: 1rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .06em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid #334155;	A top border used as an accent or separator.
text-align: center;	Centres inline content such as text.

Check your work

- Footer sits at the bottom even with little content

- Links are readable on the dark background
- address not italic
- Columns stack on phones

Exercises

1. Add social media icons as SVG links.
2. Add a newsletter form in a fourth column.
3. Make the 'Back to top' link smooth-scroll with scroll-behavior.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 241: Site footer for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Build a three-column footer (about, links, contact) that stays at the bottom of short pages, with a legal line underneath.

Learning goals

- Make a sticky footer with flex column body
- Use address for contact details
- Lay out columns with auto-fit grid

Elements and CSS used

HTML elements	CSS features
footer, section, nav, h2, ul, li, a, address, br, p	min-height: 100vh, flex: 1, grid, text-transform, border-top, font-size

Build guide

1. Write main content followed by <footer class="site-footer">.
2. Inside, add a .cols div with three blocks: section, nav, section.
3. Add the legal paragraph after .cols.
4. Make body a flex column with min-height 100vh and main flex: 1 - this pushes the footer down.
5. Grid the columns.
6. Style headings small and uppercase; reset list styles.

Project 241: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Habiba Handmade Jewellery</h1>
    <p>Scroll down to see the footer.</p>
  </main>
  <footer class="site-footer">
    <div class="cols">
      <section>
        <h2>Habiba Handmade Jewellery</h2>
        <p>Silver and brass pieces inspired by Nubia.</p>
      </section>
      <nav aria-label="Footer">
        <h2>Items</h2>
        <ul>
    <li><a href="#">Lotus pendant</a></li>
    <li><a href="#">Brass cuff</a></li>
    <li><a href="#">Bead earrings</a></li>
    <li><a href="#">Ankh ring</a></li>
        </ul>
      </nav>
      <section>
        <h2>Contact</h2>
        <address>Aswan, Egypt<br><a href="mailto:hello@jewellery.
example">hello@jewellery.example</a><br><a href="tel:
+20100000000">+20 100 000 0000</a></address>
      </section>
    </div>
    <p class="legal">&copy; 2026 Habiba Handmade Jewellery &middot;
<a href="privacy.html">Privacy</a> &middot; <a href="#top">Back to
top</a></p>
  </footer>
</body>
</html>
```

Project 241: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
body { min-height: 100vh; display: flex; flex-direction: column; }
main { flex: 1; padding: 2rem 1rem; }
.site-footer { background: #1b2431; color: #d5dbe5; padding: 2.5rem
1rem 1rem; }
.cols { max-width: 60rem; margin: 0 auto; display: grid; gap: 2rem;
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.site-footer h2 { color: #fff; font-size: 1rem; text-transform:
uppercase; letter-spacing: .06em; margin: 0 0 .75rem; }
.site-footer ul { list-style: none; padding: 0; margin: 0; }
.site-footer li { margin-bottom: .4rem; }
.site-footer a { color: #fff; }
address { font-style: normal; line-height: 1.8; }
.legal { max-width: 60rem; margin: 2rem auto 0; padding-top: 1rem;
border-top: 1px solid #334155; font-size: .85rem; text-align: center;
}
```

Project 241 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Habiba Handmade Jewellery	The main heading; only one per page.
Scroll down to see the footer.	A paragraph of text.
<footer class="site-footer">	Footer of the page or of a section.
	Generic block container for grouping and layout.
<section>	A thematic group of content, normally with its own heading.
Habiba Handmade Jewellery	Second-level heading for a section.
<nav aria-label="Footer">	A block of navigation links; aria-label names it for screen readers.

Line	What it does
	Unordered (bulleted) list.
Lotus pendant	A hyperlink; href gives the destination.
Brass cuff	One list item.
<address>Aswan, Egypt <a href="mailto:hello@jewellery.example">h...	Contact information for the page or article.
<p class="legal">© 2026 Habiba Handmade Jewellery · <a ...	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
flex: 1;	All items share free space equally.
padding: 2rem 1rem;	Space inside the element between its border and content.
background: #1b2431;	Background colour or image.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
font-size: 1rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .06em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid #334155;	A top border used as an accent or separator.
text-align: center;	Centres inline content such as text.

Check your work

- Footer sits at the bottom even with little content

- Links are readable on the dark background
- address not italic
- Columns stack on phones

Exercises

1. Add social media icons as SVG links.
2. Add a newsletter form in a fourth column.
3. Make the 'Back to top' link smooth-scroll with scroll-behavior.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 242: Site footer for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 1 | Files: index.html, styles.css

Brief

Build a three-column footer (about, links, contact) that stays at the bottom of short pages, with a legal line underneath.

Learning goals

- Make a sticky footer with flex column body
- Use address for contact details
- Lay out columns with auto-fit grid

Elements and CSS used

HTML elements	CSS features
footer, section, nav, h2, ul, li, a, address, br, p	min-height: 100vh, flex: 1, grid, text-transform, border-top, font-size

Build guide

1. Write main content followed by <footer class="site-footer">.
2. Inside, add a .cols div with three blocks: section, nav, section.
3. Add the legal paragraph after .cols.
4. Make body a flex column with min-height 100vh and main flex: 1 - this pushes the footer down.
5. Grid the columns.
6. Style headings small and uppercase; reset list styles.

Project 242: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Fayoum Pottery Studio</h1>
    <p>Scroll down to see the footer.</p>
  </main>
  <footer class="site-footer">
    <div class="cols">
      <section>
        <h2>Fayoum Pottery Studio</h2>
        <p>Wheel throwing and glazing classes.</p>
      </section>
      <nav aria-label="Footer">
        <h2>Workshops</h2>
        <ul>
    <li><a href="#">Intro to the wheel</a></li>
    <li><a href="#">Glazing day</a></li>
    <li><a href="#">Kids clay class</a></li>
    <li><a href="#">Weekend retreat</a></li>
        </ul>
      </nav>
      <section>
        <h2>Contact</h2>
        <address>Tunis Village, Egypt<br><a href="mailto:
hello@pottery.example">hello@pottery.example</a><br><a href="tel:
+20100000000">+20 100 000 0000</a></address>
      </section>
    </div>
    <p class="legal">&copy; 2026 Fayoum Pottery Studio &middot; <a
href="privacy.html">Privacy</a> &middot; <a href="#top">Back to top</
a></p>
  </footer>
</body>
</html>
```

Project 242: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
body { min-height: 100vh; display: flex; flex-direction: column; }
main { flex: 1; padding: 2rem 1rem; }
.site-footer { background: #1b2431; color: #d5dbe5; padding: 2.5rem
1rem 1rem; }
.cols { max-width: 60rem; margin: 0 auto; display: grid; gap: 2rem;
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.site-footer h2 { color: #fff; font-size: 1rem; text-transform:
uppercase; letter-spacing: .06em; margin: 0 0 .75rem; }
.site-footer ul { list-style: none; padding: 0; margin: 0; }
.site-footer li { margin-bottom: .4rem; }
.site-footer a { color: #fff; }
address { font-style: normal; line-height: 1.8; }
.legal { max-width: 60rem; margin: 2rem auto 0; padding-top: 1rem;
border-top: 1px solid #334155; font-size: .85rem; text-align: center;
}
```

Project 242 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Fayoum Pottery Studio	The main heading; only one per page.
Scroll down to see the footer.	A paragraph of text.
<footer class="site-footer">	Footer of the page or of a section.
	Generic block container for grouping and layout.
<section>	A thematic group of content, normally with its own heading.
Fayoum Pottery Studio	Second-level heading for a section.
<nav aria-label="Footer">	A block of navigation links; aria-label names it for screen readers.

Line	What it does
	Unordered (bulleted) list.
Intro to the wheel	A hyperlink; href gives the destination.
Glazing day	One list item.
<address>Tunis Village, Egypt <a href="mailto:hello@pottery.exam...	Contact information for the page or article.
<p class="legal">© 2026 Fayoum Pottery Studio · <a href...	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
flex: 1;	All items share free space equally.
padding: 2rem 1rem;	Space inside the element between its border and content.
background: #1b2431;	Background colour or image.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
font-size: 1rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .06em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid #334155;	A top border used as an accent or separator.
text-align: center;	Centres inline content such as text.

Check your work

- Footer sits at the bottom even with little content

- Links are readable on the dark background
- address not italic
- Columns stack on phones

Exercises

1. Add social media icons as SVG links.
2. Add a newsletter form in a fourth column.
3. Make the 'Back to top' link smooth-scroll with scroll-behavior.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 243: Site footer for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 1 | Files: index.html, styles.css

Brief

Build a three-column footer (about, links, contact) that stays at the bottom of short pages, with a legal line underneath.

Learning goals

- Make a sticky footer with flex column body
- Use address for contact details
- Lay out columns with auto-fit grid

Elements and CSS used

HTML elements	CSS features
footer, section, nav, h2, ul, li, a, address, br, p	min-height: 100vh, flex: 1, grid, text-transform, border-top, font-size

Build guide

1. Write main content followed by <footer class="site-footer">.
2. Inside, add a .cols div with three blocks: section, nav, section.
3. Add the legal paragraph after .cols.
4. Make body a flex column with min-height 100vh and main flex: 1 - this pushes the footer down.
5. Grid the columns.
6. Style headings small and uppercase; reset list styles.

Project 243: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cleopatra Beauty Salon</h1>
    <p>Scroll down to see the footer.</p>
  </main>
  <footer class="site-footer">
    <div class="cols">
      <section>
        <h2>Cleopatra Beauty Salon</h2>
        <p>Hair, nails and skin care.</p>
      </section>
      <nav aria-label="Footer">
        <h2>Treatments</h2>
        <ul>
    <li><a href="#">Haircut and blow-dry</a></li>
    <li><a href="#">Manicure</a></li>
    <li><a href="#">Facial</a></li>
    <li><a href="#">Bridal package</a></li>
        </ul>
      </nav>
      <section>
        <h2>Contact</h2>
        <address>Dokki, Egypt<br><a href="mailto:hello@salon.
example">hello@salon.example</a><br><a href="tel:+20100000000">+20
100 000 0000</a></address>
      </section>
    </div>
    <p class="legal">&copy; 2026 Cleopatra Beauty Salon &middot; <a
href="privacy.html">Privacy</a> &middot; <a href="#top">Back to top</
a></p>
  </footer>
</body>
</html>
```

Project 243: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
body { min-height: 100vh; display: flex; flex-direction: column; }
main { flex: 1; padding: 2rem 1rem; }
.site-footer { background: #1b2431; color: #d5dbe5; padding: 2.5rem
1rem 1rem; }
.cols { max-width: 60rem; margin: 0 auto; display: grid; gap: 2rem;
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.site-footer h2 { color: #fff; font-size: 1rem; text-transform:
uppercase; letter-spacing: .06em; margin: 0 0 .75rem; }
.site-footer ul { list-style: none; padding: 0; margin: 0; }
.site-footer li { margin-bottom: .4rem; }
.site-footer a { color: #fff; }
address { font-style: normal; line-height: 1.8; }
.legal { max-width: 60rem; margin: 2rem auto 0; padding-top: 1rem;
border-top: 1px solid #334155; font-size: .85rem; text-align: center;
}
```

Project 243 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cleopatra Beauty Salon	The main heading; only one per page.
Scroll down to see the footer.	A paragraph of text.
<footer class="site-footer">	Footer of the page or of a section.
	Generic block container for grouping and layout.
<section>	A thematic group of content, normally with its own heading.
Cleopatra Beauty Salon	Second-level heading for a section.
<nav aria-label="Footer">	A block of navigation links; aria-label names it for screen readers.

Line	What it does
	Unordered (bulleted) list.
Haircut and blow-dry	A hyperlink; href gives the destination.
Manicure	One list item.
<address>Dokki, Egypt <a href="mailto:hello@salon.example">hello...	Contact information for the page or article.
<p class="legal">© 2026 Cleopatra Beauty Salon · <a hre...	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
flex: 1;	All items share free space equally.
padding: 2rem 1rem;	Space inside the element between its border and content.
background: #1b2431;	Background colour or image.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
font-size: 1rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .06em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid #334155;	A top border used as an accent or separator.
text-align: center;	Centres inline content such as text.

Check your work

- Footer sits at the bottom even with little content

- Links are readable on the dark background
- address not italic
- Columns stack on phones

Exercises

1. Add social media icons as SVG links.
2. Add a newsletter form in a fourth column.
3. Make the 'Back to top' link smooth-scroll with scroll-behavior.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 244: Site footer for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 1 | Files: index.html, styles.css

Brief

Build a three-column footer (about, links, contact) that stays at the bottom of short pages, with a legal line underneath.

Learning goals

- Make a sticky footer with flex column body
- Use address for contact details
- Lay out columns with auto-fit grid

Elements and CSS used

HTML elements	CSS features
footer, section, nav, h2, ul, li, a, address, br, p	min-height: 100vh, flex: 1, grid, text-transform, border-top, font-size

Build guide

1. Write main content followed by <footer class="site-footer">.
2. Inside, add a .cols div with three blocks: section, nav, section.
3. Add the legal paragraph after .cols.
4. Make body a flex column with min-height 100vh and main flex: 1 - this pushes the footer down.
5. Grid the columns.
6. Style headings small and uppercase; reset list styles.

Project 244: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Suez Auto Service</h1>
    <p>Scroll down to see the footer.</p>
  </main>
  <footer class="site-footer">
    <div class="cols">
      <section>
        <h2>Suez Auto Service</h2>
        <p>Honest car servicing and repairs.</p>
      </section>
      <nav aria-label="Footer">
        <h2>Services</h2>
        <ul>
    <li><a href="#">Oil change</a></li>
    <li><a href="#">Brake pads</a></li>
    <li><a href="#">Air conditioning</a></li>
    <li><a href="#">Pre-purchase inspection</a></li>
        </ul>
      </nav>
      <section>
        <h2>Contact</h2>
        <address>Suez, Egypt<br><a href="mailto:hello@auto.
example">hello@auto.example</a><br><a href="tel:+20100000000">+20 100
000 0000</a></address>
      </section>
    </div>
    <p class="legal">&copy; 2026 Suez Auto Service &middot; <a
href="privacy.html">Privacy</a> &middot; <a href="#top">Back to top</
a></p>
  </footer>
</body>
</html>
```

Project 244: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
body { min-height: 100vh; display: flex; flex-direction: column; }
main { flex: 1; padding: 2rem 1rem; }
.site-footer { background: #1b2431; color: #d5dbe5; padding: 2.5rem
1rem 1rem; }
.cols { max-width: 60rem; margin: 0 auto; display: grid; gap: 2rem;
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.site-footer h2 { color: #fff; font-size: 1rem; text-transform:
uppercase; letter-spacing: .06em; margin: 0 0 .75rem; }
.site-footer ul { list-style: none; padding: 0; margin: 0; }
.site-footer li { margin-bottom: .4rem; }
.site-footer a { color: #fff; }
address { font-style: normal; line-height: 1.8; }
.legal { max-width: 60rem; margin: 2rem auto 0; padding-top: 1rem;
border-top: 1px solid #334155; font-size: .85rem; text-align: center;
}
```

Project 244 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Suez Auto Service	The main heading; only one per page.
Scroll down to see the footer.	A paragraph of text.
<footer class="site-footer">	Footer of the page or of a section.
	Generic block container for grouping and layout.
<section>	A thematic group of content, normally with its own heading.
Suez Auto Service	Second-level heading for a section.
<nav aria-label="Footer">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.

Line	What it does
Oil change	A hyperlink; href gives the destination.
Brake pads	One list item.
<address>Suez, Egypt <a href="mailto:hello@auto.example">hello@a...	Contact information for the page or article.
<p class="legal">© 2026 Suez Auto Service · <a href="pr...	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
flex: 1;	All items share free space equally.
padding: 2rem 1rem;	Space inside the element between its border and content.
background: #1b2431;	Background colour or image.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
font-size: 1rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .06em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid #334155;	A top border used as an accent or separator.
text-align: center;	Centres inline content such as text.

Check your work

- Footer sits at the bottom even with little content

- Links are readable on the dark background
- address not italic
- Columns stack on phones

Exercises

1. Add social media icons as SVG links.
2. Add a newsletter form in a fourth column.
3. Make the 'Back to top' link smooth-scroll with scroll-behavior.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 245: Site footer for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 1 | Files: index.html, styles.css

Brief

Build a three-column footer (about, links, contact) that stays at the bottom of short pages, with a legal line underneath.

Learning goals

- Make a sticky footer with flex column body
- Use address for contact details
- Lay out columns with auto-fit grid

Elements and CSS used

HTML elements	CSS features
footer, section, nav, h2, ul, li, a, address, br, p	min-height: 100vh, flex: 1, grid, text-transform, border-top, font-size

Build guide

1. Write main content followed by <footer class="site-footer">.
2. Inside, add a .cols div with three blocks: section, nav, section.
3. Add the legal paragraph after .cols.
4. Make body a flex column with min-height 100vh and main flex: 1 - this pushes the footer down.
5. Grid the columns.
6. Style headings small and uppercase; reset list styles.

Project 245: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Luxor Music Academy</h1>
    <p>Scroll down to see the footer.</p>
  </main>
  <footer class="site-footer">
    <div class="cols">
      <section>
        <h2>Luxor Music Academy</h2>
        <p>Oud, piano, guitar and voice lessons.</p>
      </section>
      <nav aria-label="Footer">
        <h2>Courses</h2>
        <ul>
    <li><a href="#">Oud for beginners</a></li>
    <li><a href="#">Piano grade 1</a></li>
    <li><a href="#">Guitar chords</a></li>
    <li><a href="#">Voice coaching</a></li>
        </ul>
      </nav>
      <section>
        <h2>Contact</h2>
        <address>Luxor, Egypt<br><a href="mailto:hello@music.
example">hello@music.example</a><br><a href="tel:+20100000000">+20
100 000 0000</a></address>
      </section>
    </div>
    <p class="legal">&copy; 2026 Luxor Music Academy &middot; <a
href="privacy.html">Privacy</a> &middot; <a href="#top">Back to top</
a></p>
  </footer>
</body>
</html>
```

Project 245: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
body { min-height: 100vh; display: flex; flex-direction: column; }
main { flex: 1; padding: 2rem 1rem; }
.site-footer { background: #1b2431; color: #d5dbe5; padding: 2.5rem
1rem 1rem; }
.cols { max-width: 60rem; margin: 0 auto; display: grid; gap: 2rem;
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.site-footer h2 { color: #fff; font-size: 1rem; text-transform:
uppercase; letter-spacing: .06em; margin: 0 0 .75rem; }
.site-footer ul { list-style: none; padding: 0; margin: 0; }
.site-footer li { margin-bottom: .4rem; }
.site-footer a { color: #fff; }
address { font-style: normal; line-height: 1.8; }
.legal { max-width: 60rem; margin: 2rem auto 0; padding-top: 1rem;
border-top: 1px solid #334155; font-size: .85rem; text-align: center;
}
```

Project 245 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Luxor Music Academy	The main heading; only one per page.
Scroll down to see the footer.	A paragraph of text.
<footer class="site-footer">	Footer of the page or of a section.
	Generic block container for grouping and layout.
<section>	A thematic group of content, normally with its own heading.
Luxor Music Academy	Second-level heading for a section.
<nav aria-label="Footer">	A block of navigation links; aria-label names it for screen readers.

Line	What it does
	Unordered (bulleted) list.
Oud for beginners	A hyperlink; href gives the destination.
Piano grade 1	One list item.
<address>Luxor, Egypt <a href="mailto:hello@music.example">hello...	Contact information for the page or article.
<p class="legal">© 2026 Luxor Music Academy · <a href="...	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
flex: 1;	All items share free space equally.
padding: 2rem 1rem;	Space inside the element between its border and content.
background: #1b2431;	Background colour or image.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
font-size: 1rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .06em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid #334155;	A top border used as an accent or separator.
text-align: center;	Centres inline content such as text.

Check your work

- Footer sits at the bottom even with little content

- Links are readable on the dark background
- address not italic
- Columns stack on phones

Exercises

1. Add social media icons as SVG links.
2. Add a newsletter form in a fourth column.
3. Make the 'Back to top' link smooth-scroll with scroll-behavior.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 246: Site footer for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 1 | Files: index.html, styles.css

Brief

Build a three-column footer (about, links, contact) that stays at the bottom of short pages, with a legal line underneath.

Learning goals

- Make a sticky footer with flex column body
- Use address for contact details
- Lay out columns with auto-fit grid

Elements and CSS used

HTML elements	CSS features
footer, section, nav, h2, ul, li, a, address, br, p	min-height: 100vh, flex: 1, grid, text-transform, border-top, font-size

Build guide

1. Write main content followed by <footer class="site-footer">.
2. Inside, add a .cols div with three blocks: section, nav, section.
3. Add the legal paragraph after .cols.
4. Make body a flex column with min-height 100vh and main flex: 1 - this pushes the footer down.
5. Grid the columns.
6. Style headings small and uppercase; reset list styles.

Project 246: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Port Said Seafood</h1>
    <p>Scroll down to see the footer.</p>
  </main>
  <footer class="site-footer">
    <div class="cols">
      <section>
        <h2>Port Said Seafood</h2>
        <p>Grilled fish straight from the boats.</p>
      </section>
      <nav aria-label="Footer">
        <h2>Dishes</h2>
        <ul>
    <li><a href="#">Grilled sea bass</a></li>
    <li><a href="#">Shrimp tagine</a></li>
    <li><a href="#">Calamari</a></li>
    <li><a href="#">Fish soup</a></li>
        </ul>
      </nav>
      <section>
        <h2>Contact</h2>
        <address>Port Said, Egypt<br><a href="mailto:hello@restaurant.
example">hello@restaurant.example</a><br><a href="tel:
+20100000000">+20 100 000 0000</a></address>
      </section>
    </div>
    <p class="legal">&copy; 2026 Port Said Seafood &middot; <a
href="privacy.html">Privacy</a> &middot; <a href="#top">Back to top</
a></p>
  </footer>
</body>
</html>
```

Project 246: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
body { min-height: 100vh; display: flex; flex-direction: column; }
main { flex: 1; padding: 2rem 1rem; }
.site-footer { background: #1b2431; color: #d5dbe5; padding: 2.5rem
1rem 1rem; }
.cols { max-width: 60rem; margin: 0 auto; display: grid; gap: 2rem;
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.site-footer h2 { color: #fff; font-size: 1rem; text-transform:
uppercase; letter-spacing: .06em; margin: 0 0 .75rem; }
.site-footer ul { list-style: none; padding: 0; margin: 0; }
.site-footer li { margin-bottom: .4rem; }
.site-footer a { color: #fff; }
address { font-style: normal; line-height: 1.8; }
.legal { max-width: 60rem; margin: 2rem auto 0; padding-top: 1rem;
border-top: 1px solid #334155; font-size: .85rem; text-align: center;
}
```

Project 246 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Port Said Seafood	The main heading; only one per page.
Scroll down to see the footer.	A paragraph of text.
<footer class="site-footer">	Footer of the page or of a section.
	Generic block container for grouping and layout.
<section>	A thematic group of content, normally with its own heading.
Port Said Seafood	Second-level heading for a section.
<nav aria-label="Footer">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.

Line	What it does
Grilled sea bass	A hyperlink; href gives the destination.
Shrimp tagine	One list item.
<address>Port Said, Egypt <a href="mailto:hello@restaurant.examp...	Contact information for the page or article.
<p class="legal">© 2026 Port Said Seafood · <a href="pr...	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
flex: 1;	All items share free space equally.
padding: 2rem 1rem;	Space inside the element between its border and content.
background: #1b2431;	Background colour or image.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
font-size: 1rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .06em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid #334155;	A top border used as an accent or separator.
text-align: center;	Centres inline content such as text.

Check your work

- Footer sits at the bottom even with little content

- Links are readable on the dark background
- address not italic
- Columns stack on phones

Exercises

1. Add social media icons as SVG links.
2. Add a newsletter form in a fourth column.
3. Make the 'Back to top' link smooth-scroll with scroll-behavior.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 247: Site footer for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 1 | Files: index.html, styles.css

Brief

Build a three-column footer (about, links, contact) that stays at the bottom of short pages, with a legal line underneath.

Learning goals

- Make a sticky footer with flex column body
- Use address for contact details
- Lay out columns with auto-fit grid

Elements and CSS used

HTML elements	CSS features
footer, section, nav, h2, ul, li, a, address, br, p	min-height: 100vh, flex: 1, grid, text-transform, border-top, font-size

Build guide

1. Write main content followed by <footer class="site-footer">.
2. Inside, add a .cols div with three blocks: section, nav, section.
3. Add the legal paragraph after .cols.
4. Make body a flex column with min-height 100vh and main flex: 1 - this pushes the footer down.
5. Grid the columns.
6. Style headings small and uppercase; reset list styles.

Project 247: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Delta Kids Library</h1>
    <p>Scroll down to see the footer.</p>
  </main>
  <footer class="site-footer">
    <div class="cols">
      <section>
        <h2>Delta Kids Library</h2>
        <p>Stories, reading clubs and homework help.</p>
      </section>
      <nav aria-label="Footer">
        <h2>Programmes</h2>
        <ul>
    <li><a href="#">Story hour</a></li>
    <li><a href="#">Reading club</a></li>
    <li><a href="#">Homework help</a></li>
    <li><a href="#">Summer challenge</a></li>
        </ul>
      </nav>
      <section>
        <h2>Contact</h2>
        <address>Tanta, Egypt<br><a href="mailto:hello@library.
example">hello@library.example</a><br><a href="tel:+20100000000">+20
100 000 0000</a></address>
      </section>
    </div>
    <p class="legal">&copy; 2026 Delta Kids Library &middot; <a
href="privacy.html">Privacy</a> &middot; <a href="#top">Back to top</
a></p>
  </footer>
</body>
</html>
```

Project 247: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
body { min-height: 100vh; display: flex; flex-direction: column; }
main { flex: 1; padding: 2rem 1rem; }
.site-footer { background: #1b2431; color: #d5dbe5; padding: 2.5rem
1rem 1rem; }
.cols { max-width: 60rem; margin: 0 auto; display: grid; gap: 2rem;
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.site-footer h2 { color: #fff; font-size: 1rem; text-transform:
uppercase; letter-spacing: .06em; margin: 0 0 .75rem; }
.site-footer ul { list-style: none; padding: 0; margin: 0; }
.site-footer li { margin-bottom: .4rem; }
.site-footer a { color: #fff; }
address { font-style: normal; line-height: 1.8; }
.legal { max-width: 60rem; margin: 2rem auto 0; padding-top: 1rem;
border-top: 1px solid #334155; font-size: .85rem; text-align: center;
}
```

Project 247 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Delta Kids Library	The main heading; only one per page.
Scroll down to see the footer.	A paragraph of text.
<footer class="site-footer">	Footer of the page or of a section.
	Generic block container for grouping and layout.
<section>	A thematic group of content, normally with its own heading.
Delta Kids Library	Second-level heading for a section.
<nav aria-label="Footer">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.

Line	What it does
Story hour	A hyperlink; href gives the destination.
Reading club	One list item.
<address>Tanta, Egypt <a href="mailto:hello@library.example">hel...	Contact information for the page or article.
<p class="legal">© 2026 Delta Kids Library · <a href="p...	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
flex: 1;	All items share free space equally.
padding: 2rem 1rem;	Space inside the element between its border and content.
background: #1b2431;	Background colour or image.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
font-size: 1rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .06em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid #334155;	A top border used as an accent or separator.
text-align: center;	Centres inline content such as text.

Check your work

- Footer sits at the bottom even with little content

- Links are readable on the dark background
- address not italic
- Columns stack on phones

Exercises

1. Add social media icons as SVG links.
2. Add a newsletter form in a fourth column.
3. Make the 'Back to top' link smooth-scroll with scroll-behavior.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 248: Site footer for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Build a three-column footer (about, links, contact) that stays at the bottom of short pages, with a legal line underneath.

Learning goals

- Make a sticky footer with flex column body
- Use address for contact details
- Lay out columns with auto-fit grid

Elements and CSS used

HTML elements	CSS features
footer, section, nav, h2, ul, li, a, address, br, p	min-height: 100vh, flex: 1, grid, text-transform, border-top, font-size

Build guide

1. Write main content followed by <footer class="site-footer">.
2. Inside, add a .cols div with three blocks: section, nav, section.
3. Add the legal paragraph after .cols.
4. Make body a flex column with min-height 100vh and main flex: 1 - this pushes the footer down.
5. Grid the columns.
6. Style headings small and uppercase; reset list styles.

Project 248: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Nubian Guest House</h1>
    <p>Scroll down to see the footer.</p>
  </main>
  <footer class="site-footer">
    <div class="cols">
      <section>
        <h2>Nubian Guest House</h2>
        <p>Colourful rooms on the west bank of the Nile.</p>
      </section>
      <nav aria-label="Footer">
        <h2>Rooms</h2>
        <ul>
    <li><a href="#">Garden room</a></li>
    <li><a href="#">Nile view suite</a></li>
    <li><a href="#">Family room</a></li>
    <li><a href="#">Rooftop dorm</a></li>
        </ul>
      </nav>
      <section>
        <h2>Contact</h2>
        <address>Aswan, Egypt<br><a href="mailto:hello@guesthouse.
example">hello@guesthouse.example</a><br><a href="tel:
+20100000000">+20 100 000 0000</a></address>
      </section>
    </div>
    <p class="legal">&copy; 2026 Nubian Guest House &middot; <a
href="privacy.html">Privacy</a> &middot; <a href="#top">Back to top</
a></p>
  </footer>
</body>
</html>
```

Project 248: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
body { min-height: 100vh; display: flex; flex-direction: column; }
main { flex: 1; padding: 2rem 1rem; }
.site-footer { background: #1b2431; color: #d5dbe5; padding: 2.5rem
1rem 1rem; }
.cols { max-width: 60rem; margin: 0 auto; display: grid; gap: 2rem;
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.site-footer h2 { color: #fff; font-size: 1rem; text-transform:
uppercase; letter-spacing: .06em; margin: 0 0 .75rem; }
.site-footer ul { list-style: none; padding: 0; margin: 0; }
.site-footer li { margin-bottom: .4rem; }
.site-footer a { color: #fff; }
address { font-style: normal; line-height: 1.8; }
.legal { max-width: 60rem; margin: 2rem auto 0; padding-top: 1rem;
border-top: 1px solid #334155; font-size: .85rem; text-align: center;
}
```

Project 248 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Nubian Guest House	The main heading; only one per page.
Scroll down to see the footer.	A paragraph of text.
<footer class="site-footer">	Footer of the page or of a section.
	Generic block container for grouping and layout.
<section>	A thematic group of content, normally with its own heading.
Nubian Guest House	Second-level heading for a section.
<nav aria-label="Footer">	A block of navigation links; aria-label names it for screen readers.

Line	What it does
	Unordered (bulleted) list.
Garden room	A hyperlink; href gives the destination.
Nile view suite	One list item.
<address>Aswan, Egypt <a href="mailto:hello@guesthouse.example">...	Contact information for the page or article.
<p class="legal">© 2026 Nubian Guest House · <a href="p...	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
flex: 1;	All items share free space equally.
padding: 2rem 1rem;	Space inside the element between its border and content.
background: #1b2431;	Background colour or image.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
font-size: 1rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .06em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid #334155;	A top border used as an accent or separator.
text-align: center;	Centres inline content such as text.

Check your work

- Footer sits at the bottom even with little content

- Links are readable on the dark background
- address not italic
- Columns stack on phones

Exercises

1. Add social media icons as SVG links.
2. Add a newsletter form in a fourth column.
3. Make the 'Back to top' link smooth-scroll with scroll-behavior.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 249: Site footer for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 1 | Files: index.html, styles.css

Brief

Build a three-column footer (about, links, contact) that stays at the bottom of short pages, with a legal line underneath.

Learning goals

- Make a sticky footer with flex column body
- Use address for contact details
- Lay out columns with auto-fit grid

Elements and CSS used

HTML elements	CSS features
footer, section, nav, h2, ul, li, a, address, br, p	min-height: 100vh, flex: 1, grid, text-transform, border-top, font-size

Build guide

1. Write main content followed by <footer class="site-footer">.
2. Inside, add a .cols div with three blocks: section, nav, section.
3. Add the legal paragraph after .cols.
4. Make body a flex column with min-height 100vh and main flex: 1 - this pushes the footer down.
5. Grid the columns.
6. Style headings small and uppercase; reset list styles.

Project 249: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Ismailia Cycling Store</h1>
    <p>Scroll down to see the footer.</p>
  </main>
  <footer class="site-footer">
    <div class="cols">
      <section>
        <h2>Ismailia Cycling Store</h2>
        <p>Bikes, parts and Friday group rides.</p>
      </section>
      <nav aria-label="Footer">
        <h2>Bikes</h2>
        <ul>
    <li><a href="#">City bike</a></li>
    <li><a href="#">Mountain bike</a></li>
    <li><a href="#">Kids bike</a></li>
    <li><a href="#">Tune-up</a></li>
        </ul>
      </nav>
      <section>
        <h2>Contact</h2>
        <address>Ismailia, Egypt<br><a href="mailto:hello@cycling.
example">hello@cycling.example</a><br><a href="tel:+20100000000">+20
100 000 0000</a></address>
      </section>
    </div>
    <p class="legal">&copy; 2026 Ismailia Cycling Store &middot; <a
href="privacy.html">Privacy</a> &middot; <a href="#top">Back to top</
a></p>
  </footer>
</body>
</html>
```

Project 249: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
body { min-height: 100vh; display: flex; flex-direction: column; }
main { flex: 1; padding: 2rem 1rem; }
.site-footer { background: #1b2431; color: #d5dbe5; padding: 2.5rem
1rem 1rem; }
.cols { max-width: 60rem; margin: 0 auto; display: grid; gap: 2rem;
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.site-footer h2 { color: #fff; font-size: 1rem; text-transform:
uppercase; letter-spacing: .06em; margin: 0 0 .75rem; }
.site-footer ul { list-style: none; padding: 0; margin: 0; }
.site-footer li { margin-bottom: .4rem; }
.site-footer a { color: #fff; }
address { font-style: normal; line-height: 1.8; }
.legal { max-width: 60rem; margin: 2rem auto 0; padding-top: 1rem;
border-top: 1px solid #334155; font-size: .85rem; text-align: center;
}
```

Project 249 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Ismailia Cycling Store	The main heading; only one per page.
Scroll down to see the footer.	A paragraph of text.
<footer class="site-footer">	Footer of the page or of a section.
	Generic block container for grouping and layout.
<section>	A thematic group of content, normally with its own heading.
Ismailia Cycling Store	Second-level heading for a section.
<nav aria-label="Footer">	A block of navigation links; aria-label names it for screen readers.

Line	What it does
	Unordered (bulleted) list.
City bike	A hyperlink; href gives the destination.
Mountain bike	One list item.
<address>Ismailia, Egypt <a href="mailto:hello@cycling.example">...	Contact information for the page or article.
<p class="legal">© 2026 Ismailia Cycling Store · <a hre...	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
flex: 1;	All items share free space equally.
padding: 2rem 1rem;	Space inside the element between its border and content.
background: #1b2431;	Background colour or image.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
font-size: 1rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .06em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid #334155;	A top border used as an accent or separator.
text-align: center;	Centres inline content such as text.

Check your work

- Footer sits at the bottom even with little content

- Links are readable on the dark background
- address not italic
- Columns stack on phones

Exercises

1. Add social media icons as SVG links.
2. Add a newsletter form in a fourth column.
3. Make the 'Back to top' link smooth-scroll with scroll-behavior.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 250: Site footer for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 1 | Files: index.html, styles.css

Brief

Build a three-column footer (about, links, contact) that stays at the bottom of short pages, with a legal line underneath.

Learning goals

- Make a sticky footer with flex column body
- Use address for contact details
- Lay out columns with auto-fit grid

Elements and CSS used

HTML elements	CSS features
footer, section, nav, h2, ul, li, a, address, br, p	min-height: 100vh, flex: 1, grid, text-transform, border-top, font-size

Build guide

1. Write main content followed by <footer class="site-footer">.
2. Inside, add a .cols div with three blocks: section, nav, section.
3. Add the legal paragraph after .cols.
4. Make body a flex column with min-height 100vh and main flex: 1 - this pushes the footer down.
5. Grid the columns.
6. Style headings small and uppercase; reset list styles.

Project 250: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Minya Coding Club</h1>
    <p>Scroll down to see the footer.</p>
  </main>
  <footer class="site-footer">
    <div class="cols">
      <section>
        <h2>Minya Coding Club</h2>
        <p>Free weekend coding for teenagers.</p>
      </section>
      <nav aria-label="Footer">
        <h2>Workshops</h2>
        <ul>
    <li><a href="#">HTML weekend</a></li>
    <li><a href="#">CSS art</a></li>
    <li><a href="#">Scratch games</a></li>
    <li><a href="#">Hackathon</a></li>
        </ul>
      </nav>
      <section>
        <h2>Contact</h2>
        <address>Minya, Egypt<br><a href="mailto:hello@coding.
example">hello@coding.example</a><br><a href="tel:+20100000000">+20
100 000 0000</a></address>
      </section>
    </div>
    <p class="legal">&copy; 2026 Minya Coding Club &middot; <a
href="privacy.html">Privacy</a> &middot; <a href="#top">Back to top</
a></p>
  </footer>
</body>
</html>
```

Project 250: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
body { min-height: 100vh; display: flex; flex-direction: column; }
main { flex: 1; padding: 2rem 1rem; }
.site-footer { background: #1b2431; color: #d5dbe5; padding: 2.5rem
1rem 1rem; }
.cols { max-width: 60rem; margin: 0 auto; display: grid; gap: 2rem;
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr)); }
.site-footer h2 { color: #fff; font-size: 1rem; text-transform:
uppercase; letter-spacing: .06em; margin: 0 0 .75rem; }
.site-footer ul { list-style: none; padding: 0; margin: 0; }
.site-footer li { margin-bottom: .4rem; }
.site-footer a { color: #fff; }
address { font-style: normal; line-height: 1.8; }
.legal { max-width: 60rem; margin: 2rem auto 0; padding-top: 1rem;
border-top: 1px solid #334155; font-size: .85rem; text-align: center;
}
```

Project 250 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Minya Coding Club	The main heading; only one per page.
Scroll down to see the footer.	A paragraph of text.
<footer class="site-footer">	Footer of the page or of a section.
	Generic block container for grouping and layout.
<section>	A thematic group of content, normally with its own heading.
Minya Coding Club	Second-level heading for a section.
<nav aria-label="Footer">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.

Line	What it does
HTML weekend	A hyperlink; href gives the destination.
CSS art	One list item.
<address>Minya, Egypt <a href="mailto:hello@coding.example">hell...	Contact information for the page or article.
<p class="legal">© 2026 Minya Coding Club · <a href="pr...	Character entity for the copyright sign.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
flex: 1;	All items share free space equally.
padding: 2rem 1rem;	Space inside the element between its border and content.
background: #1b2431;	Background colour or image.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(14rem, 1fr));	Defines the columns of the grid.
font-size: 1rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .06em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid #334155;	A top border used as an accent or separator.
text-align: center;	Centres inline content such as text.

Check your work

- Footer sits at the bottom even with little content

- Links are readable on the dark background
- address not italic
- Columns stack on phones

Exercises

1. Add social media icons as SVG links.
2. Add a newsletter form in a fourth column.
3. Make the 'Back to top' link smooth-scroll with scroll-behavior.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Full-screen hero banner

Level 2 | 25 projects, one per theme

Build a hero section that fills most of the screen with a background photo, a dark overlay for contrast, centred text and a button.

Project 251: Full-screen hero banner for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 2 | Files: index.html, styles.css

Brief

Build a hero section that fills most of the screen with a background photo, a dark overlay for contrast, centred text and a button.

Learning goals

- Layer a gradient overlay over a background image
- Size with viewport units
- Scale headings fluidly with clamp()

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, a, main, h2	background shorthand, linear-gradient, background-size: cover, min-height: 80vh, place-items, clamp(), text-shadow

Build guide

1. Save a wide photo as images/hero.jpg.
2. Write the header with a .content block.
3. Set min-height: 80vh and centre with grid/place-items.
4. Set the background with a linear-gradient overlay first, then the image.
5. Use clamp() for the h1 size.
6. Check text contrast; darken the overlay if needed.

Project 251: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <div class="content">
      <h1>Cairo Book Shop</h1>
      <p>PDF and printed books about web development.</p>
      <a class="btn" href="#more">Learn more</a>
    </div>
  </header>
  <main id="more">
    <h2>Why choose us</h2>
    <p>Founded in Giza by Mohamed Khattab, we offer books that people
come back for.</p>
  </main>
</body>
</html>
```

Project 251: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero {
  min-height: 80vh; display: grid; place-items: center; text-align:
center; color: #fff; padding: 2rem 1rem;
  background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)),
url("images/hero.jpg") center / cover no-repeat;
}
.hero h1 { font-size: clamp(2.2rem, 6vw, 4rem); margin: 0; text-
shadow: 0 2px 8px rgb(0 0 0 / 40%); }
.hero p { font-size: 1.25rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
main { max-width: 50rem; margin: 0 auto; padding: 3rem 1rem; }
```

Project 251 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
	Generic block container for grouping and layout.
Cairo Book Shop	The main heading; only one per page.
PDF and printed books about web development.	A paragraph of text.
Learn more	A link styled as a button; it navigates, so it is a link and not a <button>.
<main id="more">	The unique content of this page; exactly one per page.
Why choose us	Second-level heading for a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 80vh; display: grid; place-items: center; text-align: c...	Space inside the element between its border and content.
background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)), ur...	A gradient (here often used as a translucent overlay over an image).
font-size: clamp(2.2rem, 6vw, 4rem);	A fluid value between a minimum and a maximum, based on the middle expression.
text-shadow: 0 2px 8px rgb(0 0 0 / 40%);	Shadow behind text to improve contrast over images.
font-size: 1.25rem;	Size of the text.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
background: var(--brand);	Background colour or image.

Declaration	What it does
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.

Check your work

- Text readable over any part of the image
- Image covers without distortion
- Heading scales between phone and desktop
- Button reachable by keyboard

Exercises

1. Add a second button with an outline style.
2. Add a scroll-down arrow animated with @keyframes.
3. Use <picture> in the HTML instead of a CSS background for better loading.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea

Field	Value
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 252: Full-screen hero banner for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 2 | Files: index.html, styles.css

Brief

Build a hero section that fills most of the screen with a background photo, a dark overlay for contrast, centred text and a button.

Learning goals

- Layer a gradient overlay over a background image
- Size with viewport units
- Scale headings fluidly with clamp()

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, a, main, h2	background shorthand, linear-gradient, background-size: cover, min-height: 80vh, place-items, clamp(), text-shadow

Build guide

1. Save a wide photo as images/hero.jpg.
2. Write the header with a .content block.
3. Set min-height: 80vh and centre with grid/place-items.
4. Set the background with a linear-gradient overlay first, then the image.
5. Use clamp() for the h1 size.
6. Check text contrast; darken the overlay if needed.

Project 252: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <div class="content">
      <h1>Nile Bakery</h1>
      <p>Fresh bread and pastries every morning.</p>
      <a class="btn" href="#more">Learn more</a>
    </div>
  </header>
  <main id="more">
    <h2>Why choose us</h2>
    <p>Founded in Cairo by Sara Adel, we offer pastries that people
come back for.</p>
  </main>
</body>
</html>
```

Project 252: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero {
  min-height: 80vh; display: grid; place-items: center; text-align:
center; color: #fff; padding: 2rem 1rem;
  background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)),
url("images/hero.jpg") center / cover no-repeat;
}
.hero h1 { font-size: clamp(2.2rem, 6vw, 4rem); margin: 0; text-
shadow: 0 2px 8px rgb(0 0 0 / 40%); }
.hero p { font-size: 1.25rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
main { max-width: 50rem; margin: 0 auto; padding: 3rem 1rem; }
```

Project 252 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
	Generic block container for grouping and layout.
Nile Bakery	The main heading; only one per page.
Fresh bread and pastries every morning.	A paragraph of text.
Learn more	A link styled as a button; it navigates, so it is a link and not a <button>.
<main id="more">	The unique content of this page; exactly one per page.
Why choose us	Second-level heading for a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 80vh; display: grid; place-items: center; text-align: c...	Space inside the element between its border and content.
background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)), ur...	A gradient (here often used as a translucent overlay over an image).
font-size: clamp(2.2rem, 6vw, 4rem);	A fluid value between a minimum and a maximum, based on the middle expression.
text-shadow: 0 2px 8px rgb(0 0 0 / 40%);	Shadow behind text to improve contrast over images.
font-size: 1.25rem;	Size of the text.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
background: var(--brand);	Background colour or image.

Declaration	What it does
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.

Check your work

- Text readable over any part of the image
- Image covers without distortion
- Heading scales between phone and desktop
- Button reachable by keyboard

Exercises

1. Add a second button with an outline style.
2. Add a scroll-down arrow animated with @keyframes.
3. Use <picture> in the HTML instead of a CSS background for better loading.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec

Field	Value
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 253: Full-screen hero banner for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 2 | Files: index.html, styles.css

Brief

Build a hero section that fills most of the screen with a background photo, a dark overlay for contrast, centred text and a button.

Learning goals

- Layer a gradient overlay over a background image
- Size with viewport units
- Scale headings fluidly with clamp()

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, a, main, h2	background shorthand, linear-gradient, background-size: cover, min-height: 80vh, place-items, clamp(), text-shadow

Build guide

1. Save a wide photo as images/hero.jpg.
2. Write the header with a .content block.
3. Set min-height: 80vh and centre with grid/place-items.
4. Set the background with a linear-gradient overlay first, then the image.
5. Use clamp() for the h1 size.
6. Check text contrast; darken the overlay if needed.

Project 253: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <div class="content">
      <h1>Pyramid Fitness</h1>
      <p>Train smarter, feel stronger.</p>
      <a class="btn" href="#more">Learn more</a>
    </div>
  </header>
  <main id="more">
    <h2>Why choose us</h2>
    <p>Founded in 6th of October by Omar Farouk, we offer classes
that people come back for.</p>
  </main>
</body>
</html>
```

Project 253: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero {
  min-height: 80vh; display: grid; place-items: center; text-align:
center; color: #fff; padding: 2rem 1rem;
  background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)),
url("images/hero.jpg") center / cover no-repeat;
}
.hero h1 { font-size: clamp(2.2rem, 6vw, 4rem); margin: 0; text-
shadow: 0 2px 8px rgb(0 0 0 / 40%); }
.hero p { font-size: 1.25rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
main { max-width: 50rem; margin: 0 auto; padding: 3rem 1rem; }
```

Project 253 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
	Generic block container for grouping and layout.
Pyramid Fitness	The main heading; only one per page.
Train smarter, feel stronger.	A paragraph of text.
Learn more	A link styled as a button; it navigates, so it is a link and not a <button>.
<main id="more">	The unique content of this page; exactly one per page.
Why choose us	Second-level heading for a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 80vh; display: grid; place-items: center; text-align: c...	Space inside the element between its border and content.
background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)), ur...	A gradient (here often used as a translucent overlay over an image).
font-size: clamp(2.2rem, 6vw, 4rem);	A fluid value between a minimum and a maximum, based on the middle expression.
text-shadow: 0 2px 8px rgb(0 0 0 / 40%);	Shadow behind text to improve contrast over images.
font-size: 1.25rem;	Size of the text.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
background: var(--brand);	Background colour or image.

Declaration	What it does
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.

Check your work

- Text readable over any part of the image
- Image covers without distortion
- Heading scales between phone and desktop
- Button reachable by keyboard

Exercises

1. Add a second button with an outline style.
2. Add a scroll-down arrow animated with @keyframes.
3. Use <picture> in the HTML instead of a CSS background for better loading.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5

Field	Value
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 254: Full-screen hero banner for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 2 | Files: index.html, styles.css

Brief

Build a hero section that fills most of the screen with a background photo, a dark overlay for contrast, centred text and a button.

Learning goals

- Layer a gradient overlay over a background image
- Size with viewport units
- Scale headings fluidly with clamp()

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, a, main, h2	background shorthand, linear-gradient, background-size: cover, min-height: 80vh, place-items, clamp(), text-shadow

Build guide

1. Save a wide photo as images/hero.jpg.
2. Write the header with a .content block.
3. Set min-height: 80vh and centre with grid/place-items.
4. Set the background with a linear-gradient overlay first, then the image.
5. Use clamp() for the h1 size.
6. Check text contrast; darken the overlay if needed.

Project 254: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <div class="content">
      <h1>Delta Dental Clinic</h1>
      <p>Gentle care for the whole family.</p>
      <a class="btn" href="#more">Learn more</a>
    </div>
  </header>
  <main id="more">
    <h2>Why choose us</h2>
    <p>Founded in Mansoura by Dr. Hana Youssef, we offer services
that people come back for.</p>
  </main>
</body>
</html>
```

Project 254: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero {
  min-height: 80vh; display: grid; place-items: center; text-align:
center; color: #fff; padding: 2rem 1rem;
  background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)),
url("images/hero.jpg") center / cover no-repeat;
}
.hero h1 { font-size: clamp(2.2rem, 6vw, 4rem); margin: 0; text-
shadow: 0 2px 8px rgb(0 0 0 / 40%); }
.hero p { font-size: 1.25rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
main { max-width: 50rem; margin: 0 auto; padding: 3rem 1rem; }
```

Project 254 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
	Generic block container for grouping and layout.
Delta Dental Clinic	The main heading; only one per page.
Gentle care for the whole family.	A paragraph of text.
Learn more	A link styled as a button; it navigates, so it is a link and not a <button>.
<main id="more">	The unique content of this page; exactly one per page.
Why choose us	Second-level heading for a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 80vh; display: grid; place-items: center; text-align: c...	Space inside the element between its border and content.
background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)), ur...	A gradient (here often used as a translucent overlay over an image).
font-size: clamp(2.2rem, 6vw, 4rem);	A fluid value between a minimum and a maximum, based on the middle expression.
text-shadow: 0 2px 8px rgb(0 0 0 / 40%);	Shadow behind text to improve contrast over images.
font-size: 1.25rem;	Size of the text.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
background: var(--brand);	Background colour or image.

Declaration	What it does
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.

Check your work

- Text readable over any part of the image
- Image covers without distortion
- Heading scales between phone and desktop
- Button reachable by keyboard

Exercises

1. Add a second button with an outline style.
2. Add a scroll-down arrow animated with @keyframes.
3. Use <picture> in the HTML instead of a CSS background for better loading.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff

Field	Value
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 255: Full-screen hero banner for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 2 | Files: index.html, styles.css

Brief

Build a hero section that fills most of the screen with a background photo, a dark overlay for contrast, centred text and a button.

Learning goals

- Layer a gradient overlay over a background image
- Size with viewport units
- Scale headings fluidly with clamp()

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, a, main, h2	background shorthand, linear-gradient, background-size: cover, min-height: 80vh, place-items, clamp(), text-shadow

Build guide

1. Save a wide photo as images/hero.jpg.
2. Write the header with a .content block.
3. Set min-height: 80vh and centre with grid/place-items.
4. Set the background with a linear-gradient overlay first, then the image.
5. Use clamp() for the h1 size.
6. Check text contrast; darken the overlay if needed.

Project 255: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <div class="content">
      <h1>Red Sea Travel</h1>
      <p>Discover Egypt from desert to reef.</p>
      <a class="btn" href="#more">Learn more</a>
    </div>
  </header>
  <main id="more">
    <h2>Why choose us</h2>
    <p>Founded in Hurghada by Laila Mansour, we offer tours that
people come back for.</p>
  </main>
</body>
</html>
```

Project 255: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero {
  min-height: 80vh; display: grid; place-items: center; text-align:
center; color: #fff; padding: 2rem 1rem;
  background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)),
url("images/hero.jpg") center / cover no-repeat;
}
.hero h1 { font-size: clamp(2.2rem, 6vw, 4rem); margin: 0; text-
shadow: 0 2px 8px rgb(0 0 0 / 40%); }
.hero p { font-size: 1.25rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
main { max-width: 50rem; margin: 0 auto; padding: 3rem 1rem; }
```

Project 255 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
	Generic block container for grouping and layout.
Red Sea Travel	The main heading; only one per page.
Discover Egypt from desert to reef.	A paragraph of text.
Learn more	A link styled as a button; it navigates, so it is a link and not a <button>.
<main id="more">	The unique content of this page; exactly one per page.
Why choose us	Second-level heading for a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 80vh; display: grid; place-items: center; text-align: c...	Space inside the element between its border and content.
background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)), ur...	A gradient (here often used as a translucent overlay over an image).
font-size: clamp(2.2rem, 6vw, 4rem);	A fluid value between a minimum and a maximum, based on the middle expression.
text-shadow: 0 2px 8px rgb(0 0 0 / 40%);	Shadow behind text to improve contrast over images.
font-size: 1.25rem;	Size of the text.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
background: var(--brand);	Background colour or image.

Declaration	What it does
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.

Check your work

- Text readable over any part of the image
- Image covers without distortion
- Heading scales between phone and desktop
- Button reachable by keyboard

Exercises

1. Add a second button with an outline style.
2. Add a scroll-down arrow animated with @keyframes.
3. Use <picture> in the HTML instead of a CSS background for better loading.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff

Field	Value
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 256: Full-screen hero banner for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Build a hero section that fills most of the screen with a background photo, a dark overlay for contrast, centred text and a button.

Learning goals

- Layer a gradient overlay over a background image
- Size with viewport units
- Scale headings fluidly with clamp()

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, a, main, h2	background shorthand, linear-gradient, background-size: cover, min-height: 80vh, place-items, clamp(), text-shadow

Build guide

1. Save a wide photo as images/hero.jpg.
2. Write the header with a .content block.
3. Set min-height: 80vh and centre with grid/place-items.
4. Set the background with a linear-gradient overlay first, then the image.
5. Use clamp() for the h1 size.

6. Check text contrast; darken the overlay if needed.

Project 256: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <div class="content">
      <h1>Lotus Language School</h1>
      <p>Learn English, French and German in small groups.</p>
      <a class="btn" href="#more">Learn more</a>
    </div>
  </header>
  <main id="more">
    <h2>Why choose us</h2>
    <p>Founded in Alexandria by Nour El Din, we offer courses that
people come back for.</p>
  </main>
</body>
</html>
```

Project 256: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero {
  min-height: 80vh; display: grid; place-items: center; text-align:
center; color: #fff; padding: 2rem 1rem;
  background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)),
url("images/hero.jpg") center / cover no-repeat;
}
.hero h1 { font-size: clamp(2.2rem, 6vw, 4rem); margin: 0; text-
shadow: 0 2px 8px rgb(0 0 0 / 40%); }
.hero p { font-size: 1.25rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
main { max-width: 50rem; margin: 0 auto; padding: 3rem 1rem; }
```

Project 256 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
	Generic block container for grouping and layout.
Lotus Language School	The main heading; only one per page.
Learn English, French and German in small groups.	A paragraph of text.
Learn more	A link styled as a button; it navigates, so it is a link and not a <button>.
<main id="more">	The unique content of this page; exactly one per page.
Why choose us	Second-level heading for a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 80vh; display: grid; place-items: center; text-align: c...	Space inside the element between its border and content.
background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)), ur...	A gradient (here often used as a translucent overlay over an image).
font-size: clamp(2.2rem, 6vw, 4rem);	A fluid value between a minimum and a maximum, based on the middle expression.
text-shadow: 0 2px 8px rgb(0 0 0 / 40%);	Shadow behind text to improve contrast over images.
font-size: 1.25rem;	Size of the text.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
background: var(--brand);	Background colour or image.

Declaration	What it does
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.

Check your work

- Text readable over any part of the image
- Image covers without distortion
- Heading scales between phone and desktop
- Button reachable by keyboard

Exercises

1. Add a second button with an outline style.
2. Add a scroll-down arrow animated with @keyframes.
3. Use <picture> in the HTML instead of a CSS background for better loading.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff

Field	Value
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 257: Full-screen hero banner for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 2 | Files: index.html, styles.css

Brief

Build a hero section that fills most of the screen with a background photo, a dark overlay for contrast, centred text and a button.

Learning goals

- Layer a gradient overlay over a background image
- Size with viewport units
- Scale headings fluidly with clamp()

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, a, main, h2	background shorthand, linear-gradient, background-size: cover, min-height: 80vh, place-items, clamp(), text-shadow

Build guide

1. Save a wide photo as images/hero.jpg.
2. Write the header with a .content block.
3. Set min-height: 80vh and centre with grid/place-items.
4. Set the background with a linear-gradient overlay first, then the image.
5. Use clamp() for the h1 size.
6. Check text contrast; darken the overlay if needed.

Project 257: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <div class="content">
      <h1>Green Leaf Cafe</h1>
      <p>Specialty coffee and quiet corners.</p>
      <a class="btn" href="#more">Learn more</a>
    </div>
  </header>
  <main id="more">
    <h2>Why choose us</h2>
    <p>Founded in Zamalek by Karim Said, we offer drinks that people
come back for.</p>
  </main>
</body>
</html>
```

Project 257: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero {
  min-height: 80vh; display: grid; place-items: center; text-align:
center; color: #fff; padding: 2rem 1rem;
  background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)),
url("images/hero.jpg") center / cover no-repeat;
}
.hero h1 { font-size: clamp(2.2rem, 6vw, 4rem); margin: 0; text-
shadow: 0 2px 8px rgb(0 0 0 / 40%); }
.hero p { font-size: 1.25rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
main { max-width: 50rem; margin: 0 auto; padding: 3rem 1rem; }
```

Project 257 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
	Generic block container for grouping and layout.
Green Leaf Cafe	The main heading; only one per page.
Specialty coffee and quiet corners.	A paragraph of text.
Learn more	A link styled as a button; it navigates, so it is a link and not a <button>.
<main id="more">	The unique content of this page; exactly one per page.
Why choose us	Second-level heading for a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 80vh; display: grid; place-items: center; text-align: c...	Space inside the element between its border and content.
background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)), ur...	A gradient (here often used as a translucent overlay over an image).
font-size: clamp(2.2rem, 6vw, 4rem);	A fluid value between a minimum and a maximum, based on the middle expression.
text-shadow: 0 2px 8px rgb(0 0 0 / 40%);	Shadow behind text to improve contrast over images.
font-size: 1.25rem;	Size of the text.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
background: var(--brand);	Background colour or image.

Declaration	What it does
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.

Check your work

- Text readable over any part of the image
- Image covers without distortion
- Heading scales between phone and desktop
- Button reachable by keyboard

Exercises

1. Add a second button with an outline style.
2. Add a scroll-down arrow animated with @keyframes.
3. Use <picture> in the HTML instead of a CSS background for better loading.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4

Field	Value
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 258: Full-screen hero banner for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 2 | Files: index.html, styles.css

Brief

Build a hero section that fills most of the screen with a background photo, a dark overlay for contrast, centred text and a button.

Learning goals

- Layer a gradient overlay over a background image
- Size with viewport units
- Scale headings fluidly with clamp()

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, a, main, h2	background shorthand, linear-gradient, background-size: cover, min-height: 80vh, place-items, clamp(), text-shadow

Build guide

1. Save a wide photo as images/hero.jpg.
2. Write the header with a .content block.
3. Set min-height: 80vh and centre with grid/place-items.
4. Set the background with a linear-gradient overlay first, then the image.
5. Use clamp() for the h1 size.
6. Check text contrast; darken the overlay if needed.

Project 258: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <div class="content">
      <h1>Sinai Trekking Club</h1>
      <p>Guided mountain walks for every level.</p>
      <a class="btn" href="#more">Learn more</a>
    </div>
  </header>
  <main id="more">
    <h2>Why choose us</h2>
    <p>Founded in Saint Catherine by Yara Hamdy, we offer hikes that
people come back for.</p>
  </main>
</body>
</html>
```

Project 258: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero {
  min-height: 80vh; display: grid; place-items: center; text-align:
center; color: #fff; padding: 2rem 1rem;
  background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)),
url("images/hero.jpg") center / cover no-repeat;
}
.hero h1 { font-size: clamp(2.2rem, 6vw, 4rem); margin: 0; text-
shadow: 0 2px 8px rgb(0 0 0 / 40%); }
.hero p { font-size: 1.25rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
main { max-width: 50rem; margin: 0 auto; padding: 3rem 1rem; }
```

Project 258 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
	Generic block container for grouping and layout.
Sinai Trekking Club	The main heading; only one per page.
Guided mountain walks for every level.	A paragraph of text.
Learn more	A link styled as a button; it navigates, so it is a link and not a <button>.
<main id="more">	The unique content of this page; exactly one per page.
Why choose us	Second-level heading for a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 80vh; display: grid; place-items: center; text-align: c...	Space inside the element between its border and content.
background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)), ur...	A gradient (here often used as a translucent overlay over an image).
font-size: clamp(2.2rem, 6vw, 4rem);	A fluid value between a minimum and a maximum, based on the middle expression.
text-shadow: 0 2px 8px rgb(0 0 0 / 40%);	Shadow behind text to improve contrast over images.
font-size: 1.25rem;	Size of the text.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
background: var(--brand);	Background colour or image.

Declaration	What it does
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.

Check your work

- Text readable over any part of the image
- Image covers without distortion
- Heading scales between phone and desktop
- Button reachable by keyboard

Exercises

1. Add a second button with an outline style.
2. Add a scroll-down arrow animated with @keyframes.
3. Use <picture> in the HTML instead of a CSS background for better loading.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb

Field	Value
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 259: Full-screen hero banner for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 2 | Files: index.html, styles.css

Brief

Build a hero section that fills most of the screen with a background photo, a dark overlay for contrast, centred text and a button.

Learning goals

- Layer a gradient overlay over a background image
- Size with viewport units
- Scale headings fluidly with clamp()

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, a, main, h2	background shorthand, linear-gradient, background-size: cover, min-height: 80vh, place-items, clamp(), text-shadow

Build guide

1. Save a wide photo as images/hero.jpg.
2. Write the header with a .content block.
3. Set min-height: 80vh and centre with grid/place-items.
4. Set the background with a linear-gradient overlay first, then the image.
5. Use clamp() for the h1 size.

6. Check text contrast; darken the overlay if needed.

Project 259: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <div class="content">
      <h1>Horizon Photography</h1>
      <p>Portraits, weddings and product photography.</p>
      <a class="btn" href="#more">Learn more</a>
    </div>
  </header>
  <main id="more">
    <h2>Why choose us</h2>
    <p>Founded in Maadi by Adham Nabil, we offer sessions that people
come back for.</p>
  </main>
</body>
</html>
```

Project 259: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero {
  min-height: 80vh; display: grid; place-items: center; text-align:
center; color: #fff; padding: 2rem 1rem;
  background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)),
url("images/hero.jpg") center / cover no-repeat;
}
.hero h1 { font-size: clamp(2.2rem, 6vw, 4rem); margin: 0; text-
shadow: 0 2px 8px rgb(0 0 0 / 40%); }
.hero p { font-size: 1.25rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
main { max-width: 50rem; margin: 0 auto; padding: 3rem 1rem; }
```

Project 259 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
	Generic block container for grouping and layout.
Horizon Photography	The main heading; only one per page.
Portraits, weddings and product photography.	A paragraph of text.
Learn more	A link styled as a button; it navigates, so it is a link and not a <button>.
<main id="more">	The unique content of this page; exactly one per page.
Why choose us	Second-level heading for a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 80vh; display: grid; place-items: center; text-align: c...	Space inside the element between its border and content.
background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)), ur...	A gradient (here often used as a translucent overlay over an image).
font-size: clamp(2.2rem, 6vw, 4rem);	A fluid value between a minimum and a maximum, based on the middle expression.
text-shadow: 0 2px 8px rgb(0 0 0 / 40%);	Shadow behind text to improve contrast over images.
font-size: 1.25rem;	Size of the text.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
background: var(--brand);	Background colour or image.

Declaration	What it does
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.

Check your work

- Text readable over any part of the image
- Image covers without distortion
- Heading scales between phone and desktop
- Button reachable by keyboard

Exercises

1. Add a second button with an outline style.
2. Add a scroll-down arrow animated with @keyframes.
3. Use <picture> in the HTML instead of a CSS background for better loading.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6

Field	Value
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 260: Full-screen hero banner for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 2 | Files: index.html, styles.css

Brief

Build a hero section that fills most of the screen with a background photo, a dark overlay for contrast, centred text and a button.

Learning goals

- Layer a gradient overlay over a background image
- Size with viewport units
- Scale headings fluidly with clamp()

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, a, main, h2	background shorthand, linear-gradient, background-size: cover, min-height: 80vh, place-items, clamp(), text-shadow

Build guide

1. Save a wide photo as images/hero.jpg.
2. Write the header with a .content block.
3. Set min-height: 80vh and centre with grid/place-items.
4. Set the background with a linear-gradient overlay first, then the image.
5. Use clamp() for the h1 size.
6. Check text contrast; darken the overlay if needed.

Project 260: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <div class="content">
      <h1>Papyrus Stationery</h1>
      <p>Notebooks, pens and paper made in Egypt.</p>
      <a class="btn" href="#more">Learn more</a>
    </div>
  </header>
  <main id="more">
    <h2>Why choose us</h2>
    <p>Founded in Heliopolis by Dina Fathy, we offer products that
people come back for.</p>
  </main>
</body>
</html>
```

Project 260: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero {
  min-height: 80vh; display: grid; place-items: center; text-align:
center; color: #fff; padding: 2rem 1rem;
  background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)),
url("images/hero.jpg") center / cover no-repeat;
}
.hero h1 { font-size: clamp(2.2rem, 6vw, 4rem); margin: 0; text-
shadow: 0 2px 8px rgb(0 0 0 / 40%); }
.hero p { font-size: 1.25rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
main { max-width: 50rem; margin: 0 auto; padding: 3rem 1rem; }
```

Project 260 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
	Generic block container for grouping and layout.
Papyrus Stationery	The main heading; only one per page.
Notebooks, pens and paper made in Egypt.	A paragraph of text.
Learn more	A link styled as a button; it navigates, so it is a link and not a <button>.
<main id="more">	The unique content of this page; exactly one per page.
Why choose us	Second-level heading for a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 80vh; display: grid; place-items: center; text-align: c...	Space inside the element between its border and content.
background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)), ur...	A gradient (here often used as a translucent overlay over an image).
font-size: clamp(2.2rem, 6vw, 4rem);	A fluid value between a minimum and a maximum, based on the middle expression.
text-shadow: 0 2px 8px rgb(0 0 0 / 40%);	Shadow behind text to improve contrast over images.
font-size: 1.25rem;	Size of the text.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
background: var(--brand);	Background colour or image.

Declaration	What it does
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.

Check your work

- Text readable over any part of the image
- Image covers without distortion
- Heading scales between phone and desktop
- Button reachable by keyboard

Exercises

1. Add a second button with an outline style.
2. Add a scroll-down arrow animated with @keyframes.
3. Use <picture> in the HTML instead of a CSS background for better loading.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8

Field	Value
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 261: Full-screen hero banner for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 2 | Files: index.html, styles.css

Brief

Build a hero section that fills most of the screen with a background photo, a dark overlay for contrast, centred text and a button.

Learning goals

- Layer a gradient overlay over a background image
- Size with viewport units
- Scale headings fluidly with clamp()

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, a, main, h2	background shorthand, linear-gradient, background-size: cover, min-height: 80vh, place-items, clamp(), text-shadow

Build guide

1. Save a wide photo as images/hero.jpg.
2. Write the header with a .content block.
3. Set min-height: 80vh and centre with grid/place-items.
4. Set the background with a linear-gradient overlay first, then the image.
5. Use clamp() for the h1 size.
6. Check text contrast; darken the overlay if needed.

Project 261: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <div class="content">
      <h1>Oasis Plant Nursery</h1>
      <p>Indoor plants and gardening advice.</p>
      <a class="btn" href="#more">Learn more</a>
    </div>
  </header>
  <main id="more">
    <h2>Why choose us</h2>
    <p>Founded in Sheikh Zayed by Hossam Ali, we offer plants that
people come back for.</p>
  </main>
</body>
</html>
```

Project 261: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero {
  min-height: 80vh; display: grid; place-items: center; text-align:
center; color: #fff; padding: 2rem 1rem;
  background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)),
url("images/hero.jpg") center / cover no-repeat;
}
.hero h1 { font-size: clamp(2.2rem, 6vw, 4rem); margin: 0; text-
shadow: 0 2px 8px rgb(0 0 0 / 40%); }
.hero p { font-size: 1.25rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
main { max-width: 50rem; margin: 0 auto; padding: 3rem 1rem; }
```

Project 261 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
	Generic block container for grouping and layout.
Oasis Plant Nursery	The main heading; only one per page.
Indoor plants and gardening advice.	A paragraph of text.
Learn more	A link styled as a button; it navigates, so it is a link and not a <button>.
<main id="more">	The unique content of this page; exactly one per page.
Why choose us	Second-level heading for a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 80vh; display: grid; place-items: center; text-align: c...	Space inside the element between its border and content.
background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)), ur...	A gradient (here often used as a translucent overlay over an image).
font-size: clamp(2.2rem, 6vw, 4rem);	A fluid value between a minimum and a maximum, based on the middle expression.
text-shadow: 0 2px 8px rgb(0 0 0 / 40%);	Shadow behind text to improve contrast over images.
font-size: 1.25rem;	Size of the text.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
background: var(--brand);	Background colour or image.

Declaration	What it does
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.

Check your work

- Text readable over any part of the image
- Image covers without distortion
- Heading scales between phone and desktop
- Button reachable by keyboard

Exercises

1. Add a second button with an outline style.
2. Add a scroll-down arrow animated with @keyframes.
3. Use <picture> in the HTML instead of a CSS background for better loading.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7

Field	Value
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 262: Full-screen hero banner for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 2 | Files: index.html, styles.css

Brief

Build a hero section that fills most of the screen with a background photo, a dark overlay for contrast, centred text and a button.

Learning goals

- Layer a gradient overlay over a background image
- Size with viewport units
- Scale headings fluidly with clamp()

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, a, main, h2	background shorthand, linear-gradient, background-size: cover, min-height: 80vh, place-items, clamp(), text-shadow

Build guide

1. Save a wide photo as images/hero.jpg.
2. Write the header with a .content block.
3. Set min-height: 80vh and centre with grid/place-items.
4. Set the background with a linear-gradient overlay first, then the image.
5. Use clamp() for the h1 size.
6. Check text contrast; darken the overlay if needed.

Project 262: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <div class="content">
      <h1>Cedar Furniture</h1>
      <p>Solid wood furniture made to order.</p>
      <a class="btn" href="#more">Learn more</a>
    </div>
  </header>
  <main id="more">
    <h2>Why choose us</h2>
    <p>Founded in Damietta by Tarek Lotfy, we offer pieces that
people come back for.</p>
  </main>
</body>
</html>
```

Project 262: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero {
  min-height: 80vh; display: grid; place-items: center; text-align:
center; color: #fff; padding: 2rem 1rem;
  background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)),
url("images/hero.jpg") center / cover no-repeat;
}
.hero h1 { font-size: clamp(2.2rem, 6vw, 4rem); margin: 0; text-
shadow: 0 2px 8px rgb(0 0 0 / 40%); }
.hero p { font-size: 1.25rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
main { max-width: 50rem; margin: 0 auto; padding: 3rem 1rem; }
```

Project 262 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
	Generic block container for grouping and layout.
Cedar Furniture	The main heading; only one per page.
Solid wood furniture made to order.	A paragraph of text.
Learn more	A link styled as a button; it navigates, so it is a link and not a <button>.
<main id="more">	The unique content of this page; exactly one per page.
Why choose us	Second-level heading for a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 80vh; display: grid; place-items: center; text-align: c...	Space inside the element between its border and content.
background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)), ur...	A gradient (here often used as a translucent overlay over an image).
font-size: clamp(2.2rem, 6vw, 4rem);	A fluid value between a minimum and a maximum, based on the middle expression.
text-shadow: 0 2px 8px rgb(0 0 0 / 40%);	Shadow behind text to improve contrast over images.
font-size: 1.25rem;	Size of the text.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
background: var(--brand);	Background colour or image.

Declaration	What it does
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.

Check your work

- Text readable over any part of the image
- Image covers without distortion
- Heading scales between phone and desktop
- Button reachable by keyboard

Exercises

1. Add a second button with an outline style.
2. Add a scroll-down arrow animated with @keyframes.
3. Use <picture> in the HTML instead of a CSS background for better loading.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7

Field	Value
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 263: Full-screen hero banner for Byte Repair

Theme: Byte Repair (Nasr City) | Level 2 | Files: index.html, styles.css

Brief

Build a hero section that fills most of the screen with a background photo, a dark overlay for contrast, centred text and a button.

Learning goals

- Layer a gradient overlay over a background image
- Size with viewport units
- Scale headings fluidly with clamp()

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, a, main, h2	background shorthand, linear-gradient, background-size: cover, min-height: 80vh, place-items, clamp(), text-shadow

Build guide

1. Save a wide photo as images/hero.jpg.
2. Write the header with a .content block.
3. Set min-height: 80vh and centre with grid/place-items.
4. Set the background with a linear-gradient overlay first, then the image.
5. Use clamp() for the h1 size.
6. Check text contrast; darken the overlay if needed.

Project 263: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <div class="content">
      <h1>Byte Repair</h1>
      <p>Phone and laptop repairs while you wait.</p>
      <a class="btn" href="#more">Learn more</a>
    </div>
  </header>
  <main id="more">
    <h2>Why choose us</h2>
    <p>Founded in Nasr City by Mostafa Gamal, we offer repairs that
people come back for.</p>
  </main>
</body>
</html>
```

Project 263: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero {
  min-height: 80vh; display: grid; place-items: center; text-align:
center; color: #fff; padding: 2rem 1rem;
  background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)),
url("images/hero.jpg") center / cover no-repeat;
}
.hero h1 { font-size: clamp(2.2rem, 6vw, 4rem); margin: 0; text-
shadow: 0 2px 8px rgb(0 0 0 / 40%); }
.hero p { font-size: 1.25rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
main { max-width: 50rem; margin: 0 auto; padding: 3rem 1rem; }
```

Project 263 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
	Generic block container for grouping and layout.
Byte Repair	The main heading; only one per page.
Phone and laptop repairs while you wait.	A paragraph of text.
Learn more	A link styled as a button; it navigates, so it is a link and not a <button>.
<main id="more">	The unique content of this page; exactly one per page.
Why choose us	Second-level heading for a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 80vh; display: grid; place-items: center; text-align: c...	Space inside the element between its border and content.
background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)), ur...	A gradient (here often used as a translucent overlay over an image).
font-size: clamp(2.2rem, 6vw, 4rem);	A fluid value between a minimum and a maximum, based on the middle expression.
text-shadow: 0 2px 8px rgb(0 0 0 / 40%);	Shadow behind text to improve contrast over images.
font-size: 1.25rem;	Size of the text.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
background: var(--brand);	Background colour or image.

Declaration	What it does
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.

Check your work

- Text readable over any part of the image
- Image covers without distortion
- Heading scales between phone and desktop
- Button reachable by keyboard

Exercises

1. Add a second button with an outline style.
2. Add a scroll-down arrow animated with @keyframes.
3. Use <picture> in the HTML instead of a CSS background for better loading.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff

Field	Value
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 264: Full-screen hero banner for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 2 | Files: index.html, styles.css

Brief

Build a hero section that fills most of the screen with a background photo, a dark overlay for contrast, centred text and a button.

Learning goals

- Layer a gradient overlay over a background image
- Size with viewport units
- Scale headings fluidly with clamp()

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, a, main, h2	background shorthand, linear-gradient, background-size: cover, min-height: 80vh, place-items, clamp(), text-shadow

Build guide

1. Save a wide photo as images/hero.jpg.
2. Write the header with a .content block.
3. Set min-height: 80vh and centre with grid/place-items.
4. Set the background with a linear-gradient overlay first, then the image.
5. Use clamp() for the h1 size.
6. Check text contrast; darken the overlay if needed.

Project 264: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <div class="content">
      <h1>Sahara Pet Care</h1>
      <p>Grooming, boarding and vet visits.</p>
      <a class="btn" href="#more">Learn more</a>
    </div>
  </header>
  <main id="more">
    <h2>Why choose us</h2>
    <p>Founded in New Cairo by Rana Ibrahim, we offer services that
people come back for.</p>
  </main>
</body>
</html>
```

Project 264: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero {
  min-height: 80vh; display: grid; place-items: center; text-align:
center; color: #fff; padding: 2rem 1rem;
  background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)),
url("images/hero.jpg") center / cover no-repeat;
}
.hero h1 { font-size: clamp(2.2rem, 6vw, 4rem); margin: 0; text-
shadow: 0 2px 8px rgb(0 0 0 / 40%); }
.hero p { font-size: 1.25rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
main { max-width: 50rem; margin: 0 auto; padding: 3rem 1rem; }
```

Project 264 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
	Generic block container for grouping and layout.
Sahara Pet Care	The main heading; only one per page.
Grooming, boarding and vet visits.	A paragraph of text.
Learn more	A link styled as a button; it navigates, so it is a link and not a <button>.
<main id="more">	The unique content of this page; exactly one per page.
Why choose us	Second-level heading for a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 80vh; display: grid; place-items: center; text-align: c...	Space inside the element between its border and content.
background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)), ur...	A gradient (here often used as a translucent overlay over an image).
font-size: clamp(2.2rem, 6vw, 4rem);	A fluid value between a minimum and a maximum, based on the middle expression.
text-shadow: 0 2px 8px rgb(0 0 0 / 40%);	Shadow behind text to improve contrast over images.
font-size: 1.25rem;	Size of the text.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
background: var(--brand);	Background colour or image.

Declaration	What it does
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.

Check your work

- Text readable over any part of the image
- Image covers without distortion
- Heading scales between phone and desktop
- Button reachable by keyboard

Exercises

1. Add a second button with an outline style.
2. Add a scroll-down arrow animated with @keyframes.
3. Use <picture> in the HTML instead of a CSS background for better loading.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed

Field	Value
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 265: Full-screen hero banner for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Build a hero section that fills most of the screen with a background photo, a dark overlay for contrast, centred text and a button.

Learning goals

- Layer a gradient overlay over a background image
- Size with viewport units
- Scale headings fluidly with clamp()

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, a, main, h2	background shorthand, linear-gradient, background-size: cover, min-height: 80vh, place-items, clamp(), text-shadow

Build guide

1. Save a wide photo as images/hero.jpg.
2. Write the header with a .content block.
3. Set min-height: 80vh and centre with grid/place-items.
4. Set the background with a linear-gradient overlay first, then the image.
5. Use clamp() for the h1 size.

6. Check text contrast; darken the overlay if needed.

Project 265: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <div class="content">
      <h1>Alexandria Sailing School</h1>
      <p>Learn to sail on the Mediterranean.</p>
      <a class="btn" href="#more">Learn more</a>
    </div>
  </header>
  <main id="more">
    <h2>Why choose us</h2>
    <p>Founded in Alexandria by Amr Selim, we offer lessons that
people come back for.</p>
  </main>
</body>
</html>
```

Project 265: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero {
  min-height: 80vh; display: grid; place-items: center; text-align:
center; color: #fff; padding: 2rem 1rem;
  background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)),
url("images/hero.jpg") center / cover no-repeat;
}
.hero h1 { font-size: clamp(2.2rem, 6vw, 4rem); margin: 0; text-
shadow: 0 2px 8px rgb(0 0 0 / 40%); }
.hero p { font-size: 1.25rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
main { max-width: 50rem; margin: 0 auto; padding: 3rem 1rem; }
```

Project 265 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
	Generic block container for grouping and layout.
Alexandria Sailing School	The main heading; only one per page.
Learn to sail on the Mediterranean.	A paragraph of text.
Learn more	A link styled as a button; it navigates, so it is a link and not a <button>.
<main id="more">	The unique content of this page; exactly one per page.
Why choose us	Second-level heading for a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 80vh; display: grid; place-items: center; text-align: c...	Space inside the element between its border and content.
background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)), ur...	A gradient (here often used as a translucent overlay over an image).
font-size: clamp(2.2rem, 6vw, 4rem);	A fluid value between a minimum and a maximum, based on the middle expression.
text-shadow: 0 2px 8px rgb(0 0 0 / 40%);	Shadow behind text to improve contrast over images.
font-size: 1.25rem;	Size of the text.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
background: var(--brand);	Background colour or image.

Declaration	What it does
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.

Check your work

- Text readable over any part of the image
- Image covers without distortion
- Heading scales between phone and desktop
- Button reachable by keyboard

Exercises

1. Add a second button with an outline style.
2. Add a scroll-down arrow animated with @keyframes.
3. Use <picture> in the HTML instead of a CSS background for better loading.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff

Field	Value
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 266: Full-screen hero banner for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Build a hero section that fills most of the screen with a background photo, a dark overlay for contrast, centred text and a button.

Learning goals

- Layer a gradient overlay over a background image
- Size with viewport units
- Scale headings fluidly with clamp()

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, a, main, h2	background shorthand, linear-gradient, background-size: cover, min-height: 80vh, place-items, clamp(), text-shadow

Build guide

1. Save a wide photo as images/hero.jpg.
2. Write the header with a .content block.
3. Set min-height: 80vh and centre with grid/place-items.
4. Set the background with a linear-gradient overlay first, then the image.
5. Use clamp() for the h1 size.

6. Check text contrast; darken the overlay if needed.

Project 266: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <div class="content">
      <h1>Habiba Handmade Jewellery</h1>
      <p>Silver and brass pieces inspired by Nubia.</p>
      <a class="btn" href="#more">Learn more</a>
    </div>
  </header>
  <main id="more">
    <h2>Why choose us</h2>
    <p>Founded in Aswan by Habiba Saleh, we offer items that people
come back for.</p>
  </main>
</body>
</html>
```

Project 266: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero {
  min-height: 80vh; display: grid; place-items: center; text-align:
center; color: #fff; padding: 2rem 1rem;
  background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)),
url("images/hero.jpg") center / cover no-repeat;
}
.hero h1 { font-size: clamp(2.2rem, 6vw, 4rem); margin: 0; text-
shadow: 0 2px 8px rgb(0 0 0 / 40%); }
.hero p { font-size: 1.25rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
main { max-width: 50rem; margin: 0 auto; padding: 3rem 1rem; }
```

Project 266 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
	Generic block container for grouping and layout.
Habiba Handmade Jewellery	The main heading; only one per page.
Silver and brass pieces inspired by Nubia.	A paragraph of text.
Learn more	A link styled as a button; it navigates, so it is a link and not a <button>.
<main id="more">	The unique content of this page; exactly one per page.
Why choose us	Second-level heading for a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 80vh; display: grid; place-items: center; text-align: c...	Space inside the element between its border and content.
background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)), ur...	A gradient (here often used as a translucent overlay over an image).
font-size: clamp(2.2rem, 6vw, 4rem);	A fluid value between a minimum and a maximum, based on the middle expression.
text-shadow: 0 2px 8px rgb(0 0 0 / 40%);	Shadow behind text to improve contrast over images.
font-size: 1.25rem;	Size of the text.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
background: var(--brand);	Background colour or image.

Declaration	What it does
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.

Check your work

- Text readable over any part of the image
- Image covers without distortion
- Heading scales between phone and desktop
- Button reachable by keyboard

Exercises

1. Add a second button with an outline style.
2. Add a scroll-down arrow animated with @keyframes.
3. Use <picture> in the HTML instead of a CSS background for better loading.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8

Field	Value
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 267: Full-screen hero banner for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 2 | Files: index.html, styles.css

Brief

Build a hero section that fills most of the screen with a background photo, a dark overlay for contrast, centred text and a button.

Learning goals

- Layer a gradient overlay over a background image
- Size with viewport units
- Scale headings fluidly with clamp()

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, a, main, h2	background shorthand, linear-gradient, background-size: cover, min-height: 80vh, place-items, clamp(), text-shadow

Build guide

1. Save a wide photo as images/hero.jpg.
2. Write the header with a .content block.
3. Set min-height: 80vh and centre with grid/place-items.
4. Set the background with a linear-gradient overlay first, then the image.
5. Use clamp() for the h1 size.

6. Check text contrast; darken the overlay if needed.

Project 267: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <div class="content">
      <h1>Fayoum Pottery Studio</h1>
      <p>Wheel throwing and glazing classes.</p>
      <a class="btn" href="#more">Learn more</a>
    </div>
  </header>
  <main id="more">
    <h2>Why choose us</h2>
    <p>Founded in Tunis Village by Ahmed Mahmoud, we offer workshops
that people come back for.</p>
  </main>
</body>
</html>
```

Project 267: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero {
  min-height: 80vh; display: grid; place-items: center; text-align:
center; color: #fff; padding: 2rem 1rem;
  background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)),
url("images/hero.jpg") center / cover no-repeat;
}
.hero h1 { font-size: clamp(2.2rem, 6vw, 4rem); margin: 0; text-
shadow: 0 2px 8px rgb(0 0 0 / 40%); }
.hero p { font-size: 1.25rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
main { max-width: 50rem; margin: 0 auto; padding: 3rem 1rem; }
```

Project 267 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
	Generic block container for grouping and layout.
Fayoum Pottery Studio	The main heading; only one per page.
Wheel throwing and glazing classes.	A paragraph of text.
Learn more	A link styled as a button; it navigates, so it is a link and not a <button>.
<main id="more">	The unique content of this page; exactly one per page.
Why choose us	Second-level heading for a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 80vh; display: grid; place-items: center; text-align: c...	Space inside the element between its border and content.
background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)), ur...	A gradient (here often used as a translucent overlay over an image).
font-size: clamp(2.2rem, 6vw, 4rem);	A fluid value between a minimum and a maximum, based on the middle expression.
text-shadow: 0 2px 8px rgb(0 0 0 / 40%);	Shadow behind text to improve contrast over images.
font-size: 1.25rem;	Size of the text.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
background: var(--brand);	Background colour or image.

Declaration	What it does
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.

Check your work

- Text readable over any part of the image
- Image covers without distortion
- Heading scales between phone and desktop
- Button reachable by keyboard

Exercises

1. Add a second button with an outline style.
2. Add a scroll-down arrow animated with @keyframes.
3. Use <picture> in the HTML instead of a CSS background for better loading.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed

Field	Value
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 268: Full-screen hero banner for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 2 | Files: index.html, styles.css

Brief

Build a hero section that fills most of the screen with a background photo, a dark overlay for contrast, centred text and a button.

Learning goals

- Layer a gradient overlay over a background image
- Size with viewport units
- Scale headings fluidly with clamp()

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, a, main, h2	background shorthand, linear-gradient, background-size: cover, min-height: 80vh, place-items, clamp(), text-shadow

Build guide

1. Save a wide photo as images/hero.jpg.
2. Write the header with a .content block.
3. Set min-height: 80vh and centre with grid/place-items.
4. Set the background with a linear-gradient overlay first, then the image.
5. Use clamp() for the h1 size.

6. Check text contrast; darken the overlay if needed.

Project 268: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <div class="content">
      <h1>Cleopatra Beauty Salon</h1>
      <p>Hair, nails and skin care.</p>
      <a class="btn" href="#more">Learn more</a>
    </div>
  </header>
  <main id="more">
    <h2>Why choose us</h2>
    <p>Founded in Dokki by Mariam Adel, we offer treatments that
people come back for.</p>
  </main>
</body>
</html>
```

Project 268: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero {
  min-height: 80vh; display: grid; place-items: center; text-align:
center; color: #fff; padding: 2rem 1rem;
  background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)),
url("images/hero.jpg") center / cover no-repeat;
}
.hero h1 { font-size: clamp(2.2rem, 6vw, 4rem); margin: 0; text-
shadow: 0 2px 8px rgb(0 0 0 / 40%); }
.hero p { font-size: 1.25rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
main { max-width: 50rem; margin: 0 auto; padding: 3rem 1rem; }
```

Project 268 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
	Generic block container for grouping and layout.
Cleopatra Beauty Salon	The main heading; only one per page.
Hair, nails and skin care.	A paragraph of text.
Learn more	A link styled as a button; it navigates, so it is a link and not a <button>.
<main id="more">	The unique content of this page; exactly one per page.
Why choose us	Second-level heading for a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 80vh; display: grid; place-items: center; text-align: c...	Space inside the element between its border and content.
background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)), ur...	A gradient (here often used as a translucent overlay over an image).
font-size: clamp(2.2rem, 6vw, 4rem);	A fluid value between a minimum and a maximum, based on the middle expression.
text-shadow: 0 2px 8px rgb(0 0 0 / 40%);	Shadow behind text to improve contrast over images.
font-size: 1.25rem;	Size of the text.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
background: var(--brand);	Background colour or image.

Declaration	What it does
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.

Check your work

- Text readable over any part of the image
- Image covers without distortion
- Heading scales between phone and desktop
- Button reachable by keyboard

Exercises

1. Add a second button with an outline style.
2. Add a scroll-down arrow animated with @keyframes.
3. Use <picture> in the HTML instead of a CSS background for better loading.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8

Field	Value
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 269: Full-screen hero banner for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 2 | Files: index.html, styles.css

Brief

Build a hero section that fills most of the screen with a background photo, a dark overlay for contrast, centred text and a button.

Learning goals

- Layer a gradient overlay over a background image
- Size with viewport units
- Scale headings fluidly with clamp()

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, a, main, h2	background shorthand, linear-gradient, background-size: cover, min-height: 80vh, place-items, clamp(), text-shadow

Build guide

1. Save a wide photo as images/hero.jpg.
2. Write the header with a .content block.
3. Set min-height: 80vh and centre with grid/place-items.
4. Set the background with a linear-gradient overlay first, then the image.
5. Use clamp() for the h1 size.
6. Check text contrast; darken the overlay if needed.

Project 269: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <div class="content">
      <h1>Suez Auto Service</h1>
      <p>Honest car servicing and repairs.</p>
      <a class="btn" href="#more">Learn more</a>
    </div>
  </header>
  <main id="more">
    <h2>Why choose us</h2>
    <p>Founded in Suez by Khaled Nasser, we offer services that
people come back for.</p>
  </main>
</body>
</html>
```

Project 269: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero {
  min-height: 80vh; display: grid; place-items: center; text-align:
center; color: #fff; padding: 2rem 1rem;
  background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)),
url("images/hero.jpg") center / cover no-repeat;
}
.hero h1 { font-size: clamp(2.2rem, 6vw, 4rem); margin: 0; text-
shadow: 0 2px 8px rgb(0 0 0 / 40%); }
.hero p { font-size: 1.25rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
main { max-width: 50rem; margin: 0 auto; padding: 3rem 1rem; }
```

Project 269 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
	Generic block container for grouping and layout.
Suez Auto Service	The main heading; only one per page.
Honest car servicing and repairs.	A paragraph of text.
Learn more	A link styled as a button; it navigates, so it is a link and not a <button>.
<main id="more">	The unique content of this page; exactly one per page.
Why choose us	Second-level heading for a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 80vh; display: grid; place-items: center; text-align: c...	Space inside the element between its border and content.
background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)), ur...	A gradient (here often used as a translucent overlay over an image).
font-size: clamp(2.2rem, 6vw, 4rem);	A fluid value between a minimum and a maximum, based on the middle expression.
text-shadow: 0 2px 8px rgb(0 0 0 / 40%);	Shadow behind text to improve contrast over images.
font-size: 1.25rem;	Size of the text.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
background: var(--brand);	Background colour or image.

Declaration	What it does
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.

Check your work

- Text readable over any part of the image
- Image covers without distortion
- Heading scales between phone and desktop
- Button reachable by keyboard

Exercises

1. Add a second button with an outline style.
2. Add a scroll-down arrow animated with @keyframes.
3. Use <picture> in the HTML instead of a CSS background for better loading.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb

Field	Value
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 270: Full-screen hero banner for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 2 | Files: index.html, styles.css

Brief

Build a hero section that fills most of the screen with a background photo, a dark overlay for contrast, centred text and a button.

Learning goals

- Layer a gradient overlay over a background image
- Size with viewport units
- Scale headings fluidly with clamp()

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, a, main, h2	background shorthand, linear-gradient, background-size: cover, min-height: 80vh, place-items, clamp(), text-shadow

Build guide

1. Save a wide photo as images/hero.jpg.
2. Write the header with a .content block.
3. Set min-height: 80vh and centre with grid/place-items.
4. Set the background with a linear-gradient overlay first, then the image.
5. Use clamp() for the h1 size.

6. Check text contrast; darken the overlay if needed.

Project 270: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <div class="content">
      <h1>Luxor Music Academy</h1>
      <p>Oud, piano, guitar and voice lessons.</p>
      <a class="btn" href="#more">Learn more</a>
    </div>
  </header>
  <main id="more">
    <h2>Why choose us</h2>
    <p>Founded in Luxor by Salma Ragab, we offer courses that people
come back for.</p>
  </main>
</body>
</html>
```

Project 270: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero {
  min-height: 80vh; display: grid; place-items: center; text-align:
center; color: #fff; padding: 2rem 1rem;
  background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)),
url("images/hero.jpg") center / cover no-repeat;
}
.hero h1 { font-size: clamp(2.2rem, 6vw, 4rem); margin: 0; text-
shadow: 0 2px 8px rgb(0 0 0 / 40%); }
.hero p { font-size: 1.25rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
main { max-width: 50rem; margin: 0 auto; padding: 3rem 1rem; }
```

Project 270 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
	Generic block container for grouping and layout.
Luxor Music Academy	The main heading; only one per page.
Oud, piano, guitar and voice lessons.	A paragraph of text.
Learn more	A link styled as a button; it navigates, so it is a link and not a <button>.
<main id="more">	The unique content of this page; exactly one per page.
Why choose us	Second-level heading for a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 80vh; display: grid; place-items: center; text-align: c...	Space inside the element between its border and content.
background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)), ur...	A gradient (here often used as a translucent overlay over an image).
font-size: clamp(2.2rem, 6vw, 4rem);	A fluid value between a minimum and a maximum, based on the middle expression.
text-shadow: 0 2px 8px rgb(0 0 0 / 40%);	Shadow behind text to improve contrast over images.
font-size: 1.25rem;	Size of the text.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
background: var(--brand);	Background colour or image.

Declaration	What it does
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.

Check your work

- Text readable over any part of the image
- Image covers without distortion
- Heading scales between phone and desktop
- Button reachable by keyboard

Exercises

1. Add a second button with an outline style.
2. Add a scroll-down arrow animated with @keyframes.
3. Use <picture> in the HTML instead of a CSS background for better loading.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff

Field	Value
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 271: Full-screen hero banner for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 2 | Files: index.html, styles.css

Brief

Build a hero section that fills most of the screen with a background photo, a dark overlay for contrast, centred text and a button.

Learning goals

- Layer a gradient overlay over a background image
- Size with viewport units
- Scale headings fluidly with clamp()

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, a, main, h2	background shorthand, linear-gradient, background-size: cover, min-height: 80vh, place-items, clamp(), text-shadow

Build guide

1. Save a wide photo as images/hero.jpg.
2. Write the header with a .content block.
3. Set min-height: 80vh and centre with grid/place-items.
4. Set the background with a linear-gradient overlay first, then the image.
5. Use clamp() for the h1 size.
6. Check text contrast; darken the overlay if needed.

Project 271: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <div class="content">
      <h1>Port Said Seafood</h1>
      <p>Grilled fish straight from the boats.</p>
      <a class="btn" href="#more">Learn more</a>
    </div>
  </header>
  <main id="more">
    <h2>Why choose us</h2>
    <p>Founded in Port Said by Sherif Wahba, we offer dishes that
people come back for.</p>
  </main>
</body>
</html>
```

Project 271: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero {
  min-height: 80vh; display: grid; place-items: center; text-align:
center; color: #fff; padding: 2rem 1rem;
  background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)),
url("images/hero.jpg") center / cover no-repeat;
}
.hero h1 { font-size: clamp(2.2rem, 6vw, 4rem); margin: 0; text-
shadow: 0 2px 8px rgb(0 0 0 / 40%); }
.hero p { font-size: 1.25rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
main { max-width: 50rem; margin: 0 auto; padding: 3rem 1rem; }
```

Project 271 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
	Generic block container for grouping and layout.
Port Said Seafood	The main heading; only one per page.
Grilled fish straight from the boats.	A paragraph of text.
Learn more	A link styled as a button; it navigates, so it is a link and not a <button>.
<main id="more">	The unique content of this page; exactly one per page.
Why choose us	Second-level heading for a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 80vh; display: grid; place-items: center; text-align: c...	Space inside the element between its border and content.
background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)), ur...	A gradient (here often used as a translucent overlay over an image).
font-size: clamp(2.2rem, 6vw, 4rem);	A fluid value between a minimum and a maximum, based on the middle expression.
text-shadow: 0 2px 8px rgb(0 0 0 / 40%);	Shadow behind text to improve contrast over images.
font-size: 1.25rem;	Size of the text.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
background: var(--brand);	Background colour or image.

Declaration	What it does
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.

Check your work

- Text readable over any part of the image
- Image covers without distortion
- Heading scales between phone and desktop
- Button reachable by keyboard

Exercises

1. Add a second button with an outline style.
2. Add a scroll-down arrow animated with @keyframes.
3. Use <picture> in the HTML instead of a CSS background for better loading.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff

Field	Value
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 272: Full-screen hero banner for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 2 | Files: index.html, styles.css

Brief

Build a hero section that fills most of the screen with a background photo, a dark overlay for contrast, centred text and a button.

Learning goals

- Layer a gradient overlay over a background image
- Size with viewport units
- Scale headings fluidly with clamp()

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, a, main, h2	background shorthand, linear-gradient, background-size: cover, min-height: 80vh, place-items, clamp(), text-shadow

Build guide

1. Save a wide photo as images/hero.jpg.
2. Write the header with a .content block.
3. Set min-height: 80vh and centre with grid/place-items.
4. Set the background with a linear-gradient overlay first, then the image.
5. Use clamp() for the h1 size.
6. Check text contrast; darken the overlay if needed.

Project 272: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <div class="content">
      <h1>Delta Kids Library</h1>
      <p>Stories, reading clubs and homework help.</p>
      <a class="btn" href="#more">Learn more</a>
    </div>
  </header>
  <main id="more">
    <h2>Why choose us</h2>
    <p>Founded in Tanta by Ghada Kamel, we offer programmes that
people come back for.</p>
  </main>
</body>
</html>
```

Project 272: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero {
  min-height: 80vh; display: grid; place-items: center; text-align:
center; color: #fff; padding: 2rem 1rem;
  background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)),
url("images/hero.jpg") center / cover no-repeat;
}
.hero h1 { font-size: clamp(2.2rem, 6vw, 4rem); margin: 0; text-
shadow: 0 2px 8px rgb(0 0 0 / 40%); }
.hero p { font-size: 1.25rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
main { max-width: 50rem; margin: 0 auto; padding: 3rem 1rem; }
```

Project 272 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
	Generic block container for grouping and layout.
Delta Kids Library	The main heading; only one per page.
Stories, reading clubs and homework help.	A paragraph of text.
Learn more	A link styled as a button; it navigates, so it is a link and not a <button>.
<main id="more">	The unique content of this page; exactly one per page.
Why choose us	Second-level heading for a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 80vh; display: grid; place-items: center; text-align: c...	Space inside the element between its border and content.
background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)), ur...	A gradient (here often used as a translucent overlay over an image).
font-size: clamp(2.2rem, 6vw, 4rem);	A fluid value between a minimum and a maximum, based on the middle expression.
text-shadow: 0 2px 8px rgb(0 0 0 / 40%);	Shadow behind text to improve contrast over images.
font-size: 1.25rem;	Size of the text.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
background: var(--brand);	Background colour or image.

Declaration	What it does
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.

Check your work

- Text readable over any part of the image
- Image covers without distortion
- Heading scales between phone and desktop
- Button reachable by keyboard

Exercises

1. Add a second button with an outline style.
2. Add a scroll-down arrow animated with @keyframes.
3. Use <picture> in the HTML instead of a CSS background for better loading.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed

Field	Value
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 273: Full-screen hero banner for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Build a hero section that fills most of the screen with a background photo, a dark overlay for contrast, centred text and a button.

Learning goals

- Layer a gradient overlay over a background image
- Size with viewport units
- Scale headings fluidly with clamp()

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, a, main, h2	background shorthand, linear-gradient, background-size: cover, min-height: 80vh, place-items, clamp(), text-shadow

Build guide

1. Save a wide photo as images/hero.jpg.
2. Write the header with a .content block.
3. Set min-height: 80vh and centre with grid/place-items.
4. Set the background with a linear-gradient overlay first, then the image.
5. Use clamp() for the h1 size.

6. Check text contrast; darken the overlay if needed.

Project 273: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <div class="content">
      <h1>Nubian Guest House</h1>
      <p>Colourful rooms on the west bank of the Nile.</p>
      <a class="btn" href="#more">Learn more</a>
    </div>
  </header>
  <main id="more">
    <h2>Why choose us</h2>
    <p>Founded in Aswan by Fatma Hassan, we offer rooms that people
come back for.</p>
  </main>
</body>
</html>
```

Project 273: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero {
  min-height: 80vh; display: grid; place-items: center; text-align:
center; color: #fff; padding: 2rem 1rem;
  background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)),
url("images/hero.jpg") center / cover no-repeat;
}
.hero h1 { font-size: clamp(2.2rem, 6vw, 4rem); margin: 0; text-
shadow: 0 2px 8px rgb(0 0 0 / 40%); }
.hero p { font-size: 1.25rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
main { max-width: 50rem; margin: 0 auto; padding: 3rem 1rem; }
```

Project 273 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
	Generic block container for grouping and layout.
Nubian Guest House	The main heading; only one per page.
Colourful rooms on the west bank of the Nile.	A paragraph of text.
Learn more	A link styled as a button; it navigates, so it is a link and not a <button>.
<main id="more">	The unique content of this page; exactly one per page.
Why choose us	Second-level heading for a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 80vh; display: grid; place-items: center; text-align: c...	Space inside the element between its border and content.
background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)), ur...	A gradient (here often used as a translucent overlay over an image).
font-size: clamp(2.2rem, 6vw, 4rem);	A fluid value between a minimum and a maximum, based on the middle expression.
text-shadow: 0 2px 8px rgb(0 0 0 / 40%);	Shadow behind text to improve contrast over images.
font-size: 1.25rem;	Size of the text.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
background: var(--brand);	Background colour or image.

Declaration	What it does
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.

Check your work

- Text readable over any part of the image
- Image covers without distortion
- Heading scales between phone and desktop
- Button reachable by keyboard

Exercises

1. Add a second button with an outline style.
2. Add a scroll-down arrow animated with @keyframes.
3. Use <picture> in the HTML instead of a CSS background for better loading.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb

Field	Value
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 274: Full-screen hero banner for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 2 | Files: index.html, styles.css

Brief

Build a hero section that fills most of the screen with a background photo, a dark overlay for contrast, centred text and a button.

Learning goals

- Layer a gradient overlay over a background image
- Size with viewport units
- Scale headings fluidly with clamp()

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, a, main, h2	background shorthand, linear-gradient, background-size: cover, min-height: 80vh, place-items, clamp(), text-shadow

Build guide

1. Save a wide photo as images/hero.jpg.
2. Write the header with a .content block.
3. Set min-height: 80vh and centre with grid/place-items.
4. Set the background with a linear-gradient overlay first, then the image.
5. Use clamp() for the h1 size.

6. Check text contrast; darken the overlay if needed.

Project 274: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <div class="content">
      <h1>Ismailia Cycling Store</h1>
      <p>Bikes, parts and Friday group rides.</p>
      <a class="btn" href="#more">Learn more</a>
    </div>
  </header>
  <main id="more">
    <h2>Why choose us</h2>
    <p>Founded in Ismailia by Bassem Adly, we offer bikes that people
come back for.</p>
  </main>
</body>
</html>
```

Project 274: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero {
  min-height: 80vh; display: grid; place-items: center; text-align:
center; color: #fff; padding: 2rem 1rem;
  background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)),
url("images/hero.jpg") center / cover no-repeat;
}
.hero h1 { font-size: clamp(2.2rem, 6vw, 4rem); margin: 0; text-
shadow: 0 2px 8px rgb(0 0 0 / 40%); }
.hero p { font-size: 1.25rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
main { max-width: 50rem; margin: 0 auto; padding: 3rem 1rem; }
```

Project 274 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
	Generic block container for grouping and layout.
Ismailia Cycling Store	The main heading; only one per page.
Bikes, parts and Friday group rides.	A paragraph of text.
Learn more	A link styled as a button; it navigates, so it is a link and not a <button>.
<main id="more">	The unique content of this page; exactly one per page.
Why choose us	Second-level heading for a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 80vh; display: grid; place-items: center; text-align: c...	Space inside the element between its border and content.
background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)), ur...	A gradient (here often used as a translucent overlay over an image).
font-size: clamp(2.2rem, 6vw, 4rem);	A fluid value between a minimum and a maximum, based on the middle expression.
text-shadow: 0 2px 8px rgb(0 0 0 / 40%);	Shadow behind text to improve contrast over images.
font-size: 1.25rem;	Size of the text.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
background: var(--brand);	Background colour or image.

Declaration	What it does
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.

Check your work

- Text readable over any part of the image
- Image covers without distortion
- Heading scales between phone and desktop
- Button reachable by keyboard

Exercises

1. Add a second button with an outline style.
2. Add a scroll-down arrow animated with @keyframes.
3. Use <picture> in the HTML instead of a CSS background for better loading.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2

Field	Value
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 275: Full-screen hero banner for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 2 | Files: index.html, styles.css

Brief

Build a hero section that fills most of the screen with a background photo, a dark overlay for contrast, centred text and a button.

Learning goals

- Layer a gradient overlay over a background image
- Size with viewport units
- Scale headings fluidly with clamp()

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, a, main, h2	background shorthand, linear-gradient, background-size: cover, min-height: 80vh, place-items, clamp(), text-shadow

Build guide

1. Save a wide photo as images/hero.jpg.
2. Write the header with a .content block.
3. Set min-height: 80vh and centre with grid/place-items.
4. Set the background with a linear-gradient overlay first, then the image.
5. Use clamp() for the h1 size.
6. Check text contrast; darken the overlay if needed.

Project 275: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="hero">
    <div class="content">
      <h1>Minya Coding Club</h1>
      <p>Free weekend coding for teenagers.</p>
      <a class="btn" href="#more">Learn more</a>
    </div>
  </header>
  <main id="more">
    <h2>Why choose us</h2>
    <p>Founded in Minya by Youssef Hany, we offer workshops that
people come back for.</p>
  </main>
</body>
</html>
```

Project 275: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.hero {
  min-height: 80vh; display: grid; place-items: center; text-align:
center; color: #fff; padding: 2rem 1rem;
  background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)),
url("images/hero.jpg") center / cover no-repeat;
}
.hero h1 { font-size: clamp(2.2rem, 6vw, 4rem); margin: 0; text-
shadow: 0 2px 8px rgb(0 0 0 / 40%); }
.hero p { font-size: 1.25rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
main { max-width: 50rem; margin: 0 auto; padding: 3rem 1rem; }
```

Project 275 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="hero">	Introductory content: logo, title, navigation.
	Generic block container for grouping and layout.
Minya Coding Club	The main heading; only one per page.
Free weekend coding for teenagers.	A paragraph of text.
Learn more	A link styled as a button; it navigates, so it is a link and not a <button>.
<main id="more">	The unique content of this page; exactly one per page.
Why choose us	Second-level heading for a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 80vh; display: grid; place-items: center; text-align: c...	Space inside the element between its border and content.
background: linear-gradient(rgb(0 0 0 / 45%), rgb(0 0 0 / 45%)), ur...	A gradient (here often used as a translucent overlay over an image).
font-size: clamp(2.2rem, 6vw, 4rem);	A fluid value between a minimum and a maximum, based on the middle expression.
text-shadow: 0 2px 8px rgb(0 0 0 / 40%);	Shadow behind text to improve contrast over images.
font-size: 1.25rem;	Size of the text.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
background: var(--brand);	Background colour or image.

Declaration	What it does
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.

Check your work

- Text readable over any part of the image
- Image covers without distortion
- Heading scales between phone and desktop
- Button reachable by keyboard

Exercises

1. Add a second button with an outline style.
2. Add a scroll-down arrow animated with @keyframes.
3. Use <picture> in the HTML instead of a CSS background for better loading.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff

Field	Value
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Team page

Level 1 | 25 projects, one per theme

Show four team members with circular photos, names and roles in a centred responsive grid.

Project 276: Team page for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 1 | Files: index.html, styles.css

Brief

Show four team members with circular photos, names and roles in a centred responsive grid.

Learning goals

- Make circular avatars with border-radius: 50% and object-fit
- Use decorative empty alt when the name is next to the photo
- Centre text in a grid

Elements and CSS used

HTML elements	CSS features
ul, li, img, h2, p	border-radius: 50%, object-fit: cover, border, text-align: center, grid

Build guide

1. Write a <ul class="team"> with one <li> per person.
2. Add square photos with alt="" (the name follows as text).
3. Add h2 for the name and p for the role.
4. Grid the list with auto-fit.
5. Make the images 9rem circles with object-fit: cover.
6. Add a coloured ring with border.

Project 276: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Team</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Meet the team</h1>
    <ul class="team">
      <li class="member"><img src="images/person-1.jpg" alt=""
width="200" height="200"><h2>Mohamed Khattab</h2><p>Founder</p></li>
      <li class="member"><img src="images/person-2.jpg" alt=""
width="200" height="200"><h2>Nadia Fawzy</h2><p>Manager</p></li>
      <li class="member"><img src="images/person-3.jpg" alt=""
width="200" height="200"><h2>Ali Hassan</h2><p>Specialist</p></li>
      <li class="member"><img src="images/person-4.jpg" alt=""
width="200" height="200"><h2>Mona Zaki</h2><p>Customer care</p></li>
    </ul>
  </main>
</body>
</html>
```

Project 276: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; text-
align: center; }
.team { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr)); }
.member img { width: 9rem; height: 9rem; border-radius: 50%; object-
fit: cover; border: 4px solid var(--accent); }
.member h2 { font-size: 1.05rem; margin: .75rem 0 .1rem; }
.member p { margin: 0; color: var(--muted); }
```

Project 276 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - Team</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Meet the team	The main heading; only one per page.
<ul class="team">	Unordered (bulleted) list.
<li class="member"><img src="images/person-1.jpg" alt="" width="200...	Second-level heading for a section.
<li class="member"><img src="images/person-2.jpg" alt="" width="200...	A paragraph of text.
<li class="member"><img src="images/person-3.jpg" alt="" width="200...	One list item.

Line	What it does
<li class="member"><img src="images/person-4.jpg" alt="" width="200...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr));	Defines the columns of the grid.
border-radius: 50%;	Turns a square into a circle.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
border: 4px solid var(--accent);	Changes the visual order of a flex item without changing the source.
font-size: 1.05rem;	Size of the text.

Check your work

- Photos are perfect circles even if the source is not square
- Names are headings
- Grid wraps
- Alt is empty because the name is visible text

Exercises

1. Add a short bio with <details>.
2. Add social links under each name.
3. Add a hover effect that lifts the card.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab

Field	Value
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 277: Team page for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 1 | Files: index.html, styles.css

Brief

Show four team members with circular photos, names and roles in a centred responsive grid.

Learning goals

- Make circular avatars with border-radius: 50% and object-fit
- Use decorative empty alt when the name is next to the photo
- Centre text in a grid

Elements and CSS used

HTML elements	CSS features
ul, li, img, h2, p	border-radius: 50%, object-fit: cover, border, text-align: center, grid

Build guide

1. Write a <ul class="team"> with one <li> per person.
2. Add square photos with alt="" (the name follows as text).
3. Add h2 for the name and p for the role.
4. Grid the list with auto-fit.
5. Make the images 9rem circles with object-fit: cover.
6. Add a coloured ring with border.

Project 277: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - Team</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Meet the team</h1>
    <ul class="team">
      <li class="member"><img src="images/person-1.jpg" alt=""
width="200" height="200"><h2>Sara Adel</h2><p>Founder</p></li>
      <li class="member"><img src="images/person-2.jpg" alt=""
width="200" height="200"><h2>Nadia Fawzy</h2><p>Manager</p></li>
      <li class="member"><img src="images/person-3.jpg" alt=""
width="200" height="200"><h2>Ali Hassan</h2><p>Specialist</p></li>
      <li class="member"><img src="images/person-4.jpg" alt=""
width="200" height="200"><h2>Mona Zaki</h2><p>Customer care</p></li>
    </ul>
  </main>
</body>
</html>
```

Project 277: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; text-
align: center; }
.team { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr)); }
.member img { width: 9rem; height: 9rem; border-radius: 50%; object-
fit: cover; border: 4px solid var(--accent); }
.member h2 { font-size: 1.05rem; margin: .75rem 0 .1rem; }
.member p { margin: 0; color: var(--muted); }
```

Project 277 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - Team</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Meet the team	The main heading; only one per page.
<ul class="team">	Unordered (bulleted) list.
<li class="member"><img src="images/person-1.jpg" alt="" width="200...	Second-level heading for a section.
<li class="member"><img src="images/person-2.jpg" alt="" width="200...	A paragraph of text.
<li class="member"><img src="images/person-3.jpg" alt="" width="200...	One list item.

Line	What it does
<li class="member"><img src="images/person-4.jpg" alt="" width="200...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr));	Defines the columns of the grid.
border-radius: 50%;	Turns a square into a circle.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
border: 4px solid var(--accent);	Changes the visual order of a flex item without changing the source.
font-size: 1.05rem;	Size of the text.

Check your work

- Photos are perfect circles even if the source is not square
- Names are headings
- Grid wraps
- Alt is empty because the name is visible text

Exercises

1. Add a short bio with <details>.
2. Add social links under each name.
3. Add a hover effect that lifts the card.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel

Field	Value
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 278: Team page for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 1 | Files: index.html, styles.css

Brief

Show four team members with circular photos, names and roles in a centred responsive grid.

Learning goals

- Make circular avatars with border-radius: 50% and object-fit
- Use decorative empty alt when the name is next to the photo
- Centre text in a grid

Elements and CSS used

HTML elements	CSS features
ul, li, img, h2, p	border-radius: 50%, object-fit: cover, border, text-align: center, grid

Build guide

1. Write a <ul class="team"> with one <li> per person.
2. Add square photos with alt="" (the name follows as text).
3. Add h2 for the name and p for the role.
4. Grid the list with auto-fit.
5. Make the images 9rem circles with object-fit: cover.
6. Add a coloured ring with border.

Project 278: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - Team</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Meet the team</h1>
    <ul class="team">
      <li class="member"><img src="images/person-1.jpg" alt=""
width="200" height="200"><h2>Omar Farouk</h2><p>Founder</p></li>
      <li class="member"><img src="images/person-2.jpg" alt=""
width="200" height="200"><h2>Nadia Fawzy</h2><p>Manager</p></li>
      <li class="member"><img src="images/person-3.jpg" alt=""
width="200" height="200"><h2>Ali Hassan</h2><p>Specialist</p></li>
      <li class="member"><img src="images/person-4.jpg" alt=""
width="200" height="200"><h2>Mona Zaki</h2><p>Customer care</p></li>
    </ul>
  </main>
</body>
</html>
```

Project 278: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; text-
align: center; }
.team { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr)); }
.member img { width: 9rem; height: 9rem; border-radius: 50%; object-
fit: cover; border: 4px solid var(--accent); }
.member h2 { font-size: 1.05rem; margin: .75rem 0 .1rem; }
.member p { margin: 0; color: var(--muted); }
```

Project 278 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - Team</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Meet the team	The main heading; only one per page.
<ul class="team">	Unordered (bulleted) list.
<li class="member"><img src="images/person-1.jpg" alt="" width="200...	Second-level heading for a section.
<li class="member"><img src="images/person-2.jpg" alt="" width="200...	A paragraph of text.
<li class="member"><img src="images/person-3.jpg" alt="" width="200...	One list item.

Line	What it does
<li class="member"><img src="images/person-4.jpg" alt="" width="200...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr));	Defines the columns of the grid.
border-radius: 50%;	Turns a square into a circle.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
border: 4px solid var(--accent);	Changes the visual order of a flex item without changing the source.
font-size: 1.05rem;	Size of the text.

Check your work

- Photos are perfect circles even if the source is not square
- Names are headings
- Grid wraps
- Alt is empty because the name is visible text

Exercises

1. Add a short bio with <details>.
2. Add social links under each name.
3. Add a hover effect that lifts the card.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk

Field	Value
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 279: Team page for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 1 | Files: index.html, styles.css

Brief

Show four team members with circular photos, names and roles in a centred responsive grid.

Learning goals

- Make circular avatars with border-radius: 50% and object-fit
- Use decorative empty alt when the name is next to the photo
- Centre text in a grid

Elements and CSS used

HTML elements	CSS features
ul, li, img, h2, p	border-radius: 50%, object-fit: cover, border, text-align: center, grid

Build guide

1. Write a <ul class="team"> with one <li> per person.
2. Add square photos with alt="" (the name follows as text).
3. Add h2 for the name and p for the role.
4. Grid the list with auto-fit.
5. Make the images 9rem circles with object-fit: cover.
6. Add a coloured ring with border.

Project 279: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - Team</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Meet the team</h1>
    <ul class="team">
      <li class="member"><img src="images/person-1.jpg" alt="" 
width="200" height="200"><h2>Dr. Hana Youssef</h2><p>Founder</p></li>
      <li class="member"><img src="images/person-2.jpg" alt="" 
width="200" height="200"><h2>Nadia Fawzy</h2><p>Manager</p></li>
      <li class="member"><img src="images/person-3.jpg" alt="" 
width="200" height="200"><h2>Ali Hassan</h2><p>Specialist</p></li>
      <li class="member"><img src="images/person-4.jpg" alt="" 
width="200" height="200"><h2>Mona Zaki</h2><p>Customer care</p></li>
    </ul>
  </main>
</body>
</html>
```

Project 279: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted: 
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; text-
align: center; }
.team { list-style: none; padding: 0; display: grid; gap: 1.5rem; 
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr)); }
.member img { width: 9rem; height: 9rem; border-radius: 50%; object-
fit: cover; border: 4px solid var(--accent); }
.member h2 { font-size: 1.05rem; margin: .75rem 0 .1rem; }
.member p { margin: 0; color: var(--muted); }
```

Project 279 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - Team</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Meet the team	The main heading; only one per page.
<ul class="team">	Unordered (bulleted) list.
<li class="member"><img src="images/person-1.jpg" alt="" width="200...	Second-level heading for a section.
<li class="member"><img src="images/person-2.jpg" alt="" width="200...	A paragraph of text.
<li class="member"><img src="images/person-3.jpg" alt="" width="200...	One list item.

Line	What it does
<li class="member"><img src="images/person-4.jpg" alt="" width="200...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr));	Defines the columns of the grid.
border-radius: 50%;	Turns a square into a circle.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
border: 4px solid var(--accent);	Changes the visual order of a flex item without changing the source.
font-size: 1.05rem;	Size of the text.

Check your work

- Photos are perfect circles even if the source is not square
- Names are headings
- Grid wraps
- Alt is empty because the name is visible text

Exercises

1. Add a short bio with <details>.
2. Add social links under each name.
3. Add a hover effect that lifts the card.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef

Field	Value
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 280: Team page for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 1 | Files: index.html, styles.css

Brief

Show four team members with circular photos, names and roles in a centred responsive grid.

Learning goals

- Make circular avatars with border-radius: 50% and object-fit
- Use decorative empty alt when the name is next to the photo
- Centre text in a grid

Elements and CSS used

HTML elements	CSS features
ul, li, img, h2, p	border-radius: 50%, object-fit: cover, border, text-align: center, grid

Build guide

1. Write a <ul class="team"> with one <li> per person.
2. Add square photos with alt="" (the name follows as text).
3. Add h2 for the name and p for the role.
4. Grid the list with auto-fit.
5. Make the images 9rem circles with object-fit: cover.
6. Add a coloured ring with border.

Project 280: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - Team</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Meet the team</h1>
    <ul class="team">
      <li class="member"><img src="images/person-1.jpg" alt="" 
width="200" height="200"><h2>Laila Mansour</h2><p>Founder</p></li>
      <li class="member"><img src="images/person-2.jpg" alt="" 
width="200" height="200"><h2>Nadia Fawzy</h2><p>Manager</p></li>
      <li class="member"><img src="images/person-3.jpg" alt="" 
width="200" height="200"><h2>Ali Hassan</h2><p>Specialist</p></li>
      <li class="member"><img src="images/person-4.jpg" alt="" 
width="200" height="200"><h2>Mona Zaki</h2><p>Customer care</p></li>
    </ul>
  </main>
</body>
</html>
```

Project 280: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted: 
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; text-
align: center; }
.team { list-style: none; padding: 0; display: grid; gap: 1.5rem; 
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr)); }
.member img { width: 9rem; height: 9rem; border-radius: 50%; object-
fit: cover; border: 4px solid var(--accent); }
.member h2 { font-size: 1.05rem; margin: .75rem 0 .1rem; }
.member p { margin: 0; color: var(--muted); }
```

Project 280 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - Team</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Meet the team	The main heading; only one per page.
<ul class="team">	Unordered (bulleted) list.
<li class="member"><img src="images/person-1.jpg" alt="" width="200...	Second-level heading for a section.
<li class="member"><img src="images/person-2.jpg" alt="" width="200...	A paragraph of text.
<li class="member"><img src="images/person-3.jpg" alt="" width="200...	One list item.

Line	What it does
<li class="member"><img src="images/person-4.jpg" alt="" width="200...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr));	Defines the columns of the grid.
border-radius: 50%;	Turns a square into a circle.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
border: 4px solid var(--accent);	Changes the visual order of a flex item without changing the source.
font-size: 1.05rem;	Size of the text.

Check your work

- Photos are perfect circles even if the source is not square
- Names are headings
- Grid wraps
- Alt is empty because the name is visible text

Exercises

1. Add a short bio with <details>.
2. Add social links under each name.
3. Add a hover effect that lifts the card.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour

Field	Value
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 281: Team page for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Show four team members with circular photos, names and roles in a centred responsive grid.

Learning goals

- Make circular avatars with border-radius: 50% and object-fit
- Use decorative empty alt when the name is next to the photo
- Centre text in a grid

Elements and CSS used

HTML elements	CSS features
ul, li, img, h2, p	border-radius: 50%, object-fit: cover, border, text-align: center, grid

Build guide

1. Write a <ul class="team"> with one <li> per person.
2. Add square photos with alt="" (the name follows as text).
3. Add h2 for the name and p for the role.
4. Grid the list with auto-fit.
5. Make the images 9rem circles with object-fit: cover.
6. Add a coloured ring with border.

Project 281: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - Team</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Meet the team</h1>
    <ul class="team">
      <li class="member"><img src="images/person-1.jpg" alt=""
width="200" height="200"><h2>Nour El Din</h2><p>Founder</p></li>
      <li class="member"><img src="images/person-2.jpg" alt=""
width="200" height="200"><h2>Nadia Fawzy</h2><p>Manager</p></li>
      <li class="member"><img src="images/person-3.jpg" alt=""
width="200" height="200"><h2>Ali Hassan</h2><p>Specialist</p></li>
      <li class="member"><img src="images/person-4.jpg" alt=""
width="200" height="200"><h2>Mona Zaki</h2><p>Customer care</p></li>
    </ul>
  </main>
</body>
</html>
```

Project 281: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; text-
align: center; }
.team { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr)); }
.member img { width: 9rem; height: 9rem; border-radius: 50%; object-
fit: cover; border: 4px solid var(--accent); }
.member h2 { font-size: 1.05rem; margin: .75rem 0 .1rem; }
.member p { margin: 0; color: var(--muted); }
```

Project 281 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - Team</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Meet the team	The main heading; only one per page.
<ul class="team">	Unordered (bulleted) list.
<li class="member"><img src="images/person-1.jpg" alt="" width="200...	Second-level heading for a section.
<li class="member"><img src="images/person-2.jpg" alt="" width="200...	A paragraph of text.
<li class="member"><img src="images/person-3.jpg" alt="" width="200...	One list item.

Line	What it does
<li class="member"><img src="images/person-4.jpg" alt="" width="200...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr));	Defines the columns of the grid.
border-radius: 50%;	Turns a square into a circle.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
border: 4px solid var(--accent);	Changes the visual order of a flex item without changing the source.
font-size: 1.05rem;	Size of the text.

Check your work

- Photos are perfect circles even if the source is not square
- Names are headings
- Grid wraps
- Alt is empty because the name is visible text

Exercises

1. Add a short bio with <details>.
2. Add social links under each name.
3. Add a hover effect that lifts the card.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din

Field	Value
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 282: Team page for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 1 | Files: index.html, styles.css

Brief

Show four team members with circular photos, names and roles in a centred responsive grid.

Learning goals

- Make circular avatars with border-radius: 50% and object-fit
- Use decorative empty alt when the name is next to the photo
- Centre text in a grid

Elements and CSS used

HTML elements	CSS features
ul, li, img, h2, p	border-radius: 50%, object-fit: cover, border, text-align: center, grid

Build guide

1. Write a <ul class="team"> with one <li> per person.
2. Add square photos with alt="" (the name follows as text).
3. Add h2 for the name and p for the role.
4. Grid the list with auto-fit.
5. Make the images 9rem circles with object-fit: cover.
6. Add a coloured ring with border.

Project 282: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - Team</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Meet the team</h1>
    <ul class="team">
      <li class="member"><img src="images/person-1.jpg" alt=""
width="200" height="200"><h2>Karim Said</h2><p>Founder</p></li>
      <li class="member"><img src="images/person-2.jpg" alt=""
width="200" height="200"><h2>Nadia Fawzy</h2><p>Manager</p></li>
      <li class="member"><img src="images/person-3.jpg" alt=""
width="200" height="200"><h2>Ali Hassan</h2><p>Specialist</p></li>
      <li class="member"><img src="images/person-4.jpg" alt=""
width="200" height="200"><h2>Mona Zaki</h2><p>Customer care</p></li>
    </ul>
  </main>
</body>
</html>
```

Project 282: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; text-
align: center; }
.team { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr)); }
.member img { width: 9rem; height: 9rem; border-radius: 50%; object-
fit: cover; border: 4px solid var(--accent); }
.member h2 { font-size: 1.05rem; margin: .75rem 0 .1rem; }
.member p { margin: 0; color: var(--muted); }
```

Project 282 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - Team</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Meet the team	The main heading; only one per page.
<ul class="team">	Unordered (bulleted) list.
<li class="member"><img src="images/person-1.jpg" alt="" width="200...	Second-level heading for a section.
<li class="member"><img src="images/person-2.jpg" alt="" width="200...	A paragraph of text.
<li class="member"><img src="images/person-3.jpg" alt="" width="200...	One list item.

Line	What it does
<li class="member"><img src="images/person-4.jpg" alt="" width="200...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr));	Defines the columns of the grid.
border-radius: 50%;	Turns a square into a circle.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
border: 4px solid var(--accent);	Changes the visual order of a flex item without changing the source.
font-size: 1.05rem;	Size of the text.

Check your work

- Photos are perfect circles even if the source is not square
- Names are headings
- Grid wraps
- Alt is empty because the name is visible text

Exercises

1. Add a short bio with <details>.
2. Add social links under each name.
3. Add a hover effect that lifts the card.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said

Field	Value
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 283: Team page for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 1 | Files: index.html, styles.css

Brief

Show four team members with circular photos, names and roles in a centred responsive grid.

Learning goals

- Make circular avatars with border-radius: 50% and object-fit
- Use decorative empty alt when the name is next to the photo
- Centre text in a grid

Elements and CSS used

HTML elements	CSS features
ul, li, img, h2, p	border-radius: 50%, object-fit: cover, border, text-align: center, grid

Build guide

1. Write a <ul class="team"> with one <li> per person.
2. Add square photos with alt="" (the name follows as text).
3. Add h2 for the name and p for the role.
4. Grid the list with auto-fit.
5. Make the images 9rem circles with object-fit: cover.
6. Add a coloured ring with border.

Project 283: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - Team</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Meet the team</h1>
    <ul class="team">
      <li class="member"><img src="images/person-1.jpg" alt=""
width="200" height="200"><h2>Yara Hamdy</h2><p>Founder</p></li>
      <li class="member"><img src="images/person-2.jpg" alt=""
width="200" height="200"><h2>Nadia Fawzy</h2><p>Manager</p></li>
      <li class="member"><img src="images/person-3.jpg" alt=""
width="200" height="200"><h2>Ali Hassan</h2><p>Specialist</p></li>
      <li class="member"><img src="images/person-4.jpg" alt=""
width="200" height="200"><h2>Mona Zaki</h2><p>Customer care</p></li>
    </ul>
  </main>
</body>
</html>
```

Project 283: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; text-
align: center; }
.team { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr)); }
.member img { width: 9rem; height: 9rem; border-radius: 50%; object-
fit: cover; border: 4px solid var(--accent); }
.member h2 { font-size: 1.05rem; margin: .75rem 0 .1rem; }
.member p { margin: 0; color: var(--muted); }
```

Project 283 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - Team</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Meet the team	The main heading; only one per page.
<ul class="team">	Unordered (bulleted) list.
<li class="member"><img src="images/person-1.jpg" alt="" width="200...	Second-level heading for a section.
<li class="member"><img src="images/person-2.jpg" alt="" width="200...	A paragraph of text.
<li class="member"><img src="images/person-3.jpg" alt="" width="200...	One list item.

Line	What it does
<li class="member"><img src="images/person-4.jpg" alt="" width="200...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr));	Defines the columns of the grid.
border-radius: 50%;	Turns a square into a circle.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
border: 4px solid var(--accent);	Changes the visual order of a flex item without changing the source.
font-size: 1.05rem;	Size of the text.

Check your work

- Photos are perfect circles even if the source is not square
- Names are headings
- Grid wraps
- Alt is empty because the name is visible text

Exercises

1. Add a short bio with <details>.
2. Add social links under each name.
3. Add a hover effect that lifts the card.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy

Field	Value
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 284: Team page for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 1 | Files: index.html, styles.css

Brief

Show four team members with circular photos, names and roles in a centred responsive grid.

Learning goals

- Make circular avatars with border-radius: 50% and object-fit
- Use decorative empty alt when the name is next to the photo
- Centre text in a grid

Elements and CSS used

HTML elements	CSS features
ul, li, img, h2, p	border-radius: 50%, object-fit: cover, border, text-align: center, grid

Build guide

1. Write a <ul class="team"> with one <li> per person.
2. Add square photos with alt="" (the name follows as text).
3. Add h2 for the name and p for the role.
4. Grid the list with auto-fit.
5. Make the images 9rem circles with object-fit: cover.
6. Add a coloured ring with border.

Project 284: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - Team</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Meet the team</h1>
    <ul class="team">
      <li class="member"><img src="images/person-1.jpg" alt="" 
width="200" height="200"><h2>Adham Nabil</h2><p>Founder</p></li>
      <li class="member"><img src="images/person-2.jpg" alt="" 
width="200" height="200"><h2>Nadia Fawzy</h2><p>Manager</p></li>
      <li class="member"><img src="images/person-3.jpg" alt="" 
width="200" height="200"><h2>Ali Hassan</h2><p>Specialist</p></li>
      <li class="member"><img src="images/person-4.jpg" alt="" 
width="200" height="200"><h2>Mona Zaki</h2><p>Customer care</p></li>
    </ul>
  </main>
</body>
</html>
```

Project 284: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted: 
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; text-
align: center; }
.team { list-style: none; padding: 0; display: grid; gap: 1.5rem; 
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr)); }
.member img { width: 9rem; height: 9rem; border-radius: 50%; object-
fit: cover; border: 4px solid var(--accent); }
.member h2 { font-size: 1.05rem; margin: .75rem 0 .1rem; }
.member p { margin: 0; color: var(--muted); }
```

Project 284 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - Team</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Meet the team	The main heading; only one per page.
<ul class="team">	Unordered (bulleted) list.
<li class="member"><img src="images/person-1.jpg" alt="" width="200...	Second-level heading for a section.
<li class="member"><img src="images/person-2.jpg" alt="" width="200...	A paragraph of text.
<li class="member"><img src="images/person-3.jpg" alt="" width="200...	One list item.

Line	What it does
<li class="member"><img src="images/person-4.jpg" alt="" width="200...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr));	Defines the columns of the grid.
border-radius: 50%;	Turns a square into a circle.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
border: 4px solid var(--accent);	Changes the visual order of a flex item without changing the source.
font-size: 1.05rem;	Size of the text.

Check your work

- Photos are perfect circles even if the source is not square
- Names are headings
- Grid wraps
- Alt is empty because the name is visible text

Exercises

1. Add a short bio with <details>.
2. Add social links under each name.
3. Add a hover effect that lifts the card.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil

Field	Value
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 285: Team page for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 1 | Files: index.html, styles.css

Brief

Show four team members with circular photos, names and roles in a centred responsive grid.

Learning goals

- Make circular avatars with border-radius: 50% and object-fit
- Use decorative empty alt when the name is next to the photo
- Centre text in a grid

Elements and CSS used

HTML elements	CSS features
ul, li, img, h2, p	border-radius: 50%, object-fit: cover, border, text-align: center, grid

Build guide

1. Write a <ul class="team"> with one <li> per person.
2. Add square photos with alt="" (the name follows as text).
3. Add h2 for the name and p for the role.
4. Grid the list with auto-fit.
5. Make the images 9rem circles with object-fit: cover.
6. Add a coloured ring with border.

Project 285: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - Team</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Meet the team</h1>
    <ul class="team">
      <li class="member"><img src="images/person-1.jpg" alt=""
width="200" height="200"><h2>Dina Fathy</h2><p>Founder</p></li>
      <li class="member"><img src="images/person-2.jpg" alt=""
width="200" height="200"><h2>Nadia Fawzy</h2><p>Manager</p></li>
      <li class="member"><img src="images/person-3.jpg" alt=""
width="200" height="200"><h2>Ali Hassan</h2><p>Specialist</p></li>
      <li class="member"><img src="images/person-4.jpg" alt=""
width="200" height="200"><h2>Mona Zaki</h2><p>Customer care</p></li>
    </ul>
  </main>
</body>
</html>
```

Project 285: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; text-
align: center; }
.team { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr)); }
.member img { width: 9rem; height: 9rem; border-radius: 50%; object-
fit: cover; border: 4px solid var(--accent); }
.member h2 { font-size: 1.05rem; margin: .75rem 0 .1rem; }
.member p { margin: 0; color: var(--muted); }
```

Project 285 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - Team</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Meet the team	The main heading; only one per page.
<ul class="team">	Unordered (bulleted) list.
<li class="member"><img src="images/person-1.jpg" alt="" width="200...	Second-level heading for a section.
<li class="member"><img src="images/person-2.jpg" alt="" width="200...	A paragraph of text.
<li class="member"><img src="images/person-3.jpg" alt="" width="200...	One list item.

Line	What it does
<li class="member"><img src="images/person-4.jpg" alt="" width="200...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr));	Defines the columns of the grid.
border-radius: 50%;	Turns a square into a circle.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
border: 4px solid var(--accent);	Changes the visual order of a flex item without changing the source.
font-size: 1.05rem;	Size of the text.

Check your work

- Photos are perfect circles even if the source is not square
- Names are headings
- Grid wraps
- Alt is empty because the name is visible text

Exercises

1. Add a short bio with <details>.
2. Add social links under each name.
3. Add a hover effect that lifts the card.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy

Field	Value
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 286: Team page for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 1 | Files: index.html, styles.css

Brief

Show four team members with circular photos, names and roles in a centred responsive grid.

Learning goals

- Make circular avatars with border-radius: 50% and object-fit
- Use decorative empty alt when the name is next to the photo
- Centre text in a grid

Elements and CSS used

HTML elements	CSS features
ul, li, img, h2, p	border-radius: 50%, object-fit: cover, border, text-align: center, grid

Build guide

1. Write a <ul class="team"> with one <li> per person.
2. Add square photos with alt="" (the name follows as text).
3. Add h2 for the name and p for the role.
4. Grid the list with auto-fit.
5. Make the images 9rem circles with object-fit: cover.
6. Add a coloured ring with border.

Project 286: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - Team</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Meet the team</h1>
    <ul class="team">
      <li class="member"><img src="images/person-1.jpg" alt=""
width="200" height="200"><h2>Hossam Ali</h2><p>Founder</p></li>
      <li class="member"><img src="images/person-2.jpg" alt=""
width="200" height="200"><h2>Nadia Fawzy</h2><p>Manager</p></li>
      <li class="member"><img src="images/person-3.jpg" alt=""
width="200" height="200"><h2>Ali Hassan</h2><p>Specialist</p></li>
      <li class="member"><img src="images/person-4.jpg" alt=""
width="200" height="200"><h2>Mona Zaki</h2><p>Customer care</p></li>
    </ul>
  </main>
</body>
</html>
```

Project 286: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; text-
align: center; }
.team { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr)); }
.member img { width: 9rem; height: 9rem; border-radius: 50%; object-
fit: cover; border: 4px solid var(--accent); }
.member h2 { font-size: 1.05rem; margin: .75rem 0 .1rem; }
.member p { margin: 0; color: var(--muted); }
```

Project 286 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - Team</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Meet the team	The main heading; only one per page.
<ul class="team">	Unordered (bulleted) list.
<li class="member"><img src="images/person-1.jpg" alt="" width="200...	Second-level heading for a section.
<li class="member"><img src="images/person-2.jpg" alt="" width="200...	A paragraph of text.
<li class="member"><img src="images/person-3.jpg" alt="" width="200...	One list item.

Line	What it does
<li class="member"><img src="images/person-4.jpg" alt="" width="200...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr));	Defines the columns of the grid.
border-radius: 50%;	Turns a square into a circle.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
border: 4px solid var(--accent);	Changes the visual order of a flex item without changing the source.
font-size: 1.05rem;	Size of the text.

Check your work

- Photos are perfect circles even if the source is not square
- Names are headings
- Grid wraps
- Alt is empty because the name is visible text

Exercises

1. Add a short bio with <details>.
2. Add social links under each name.
3. Add a hover effect that lifts the card.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali

Field	Value
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 287: Team page for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 1 | Files: index.html, styles.css

Brief

Show four team members with circular photos, names and roles in a centred responsive grid.

Learning goals

- Make circular avatars with border-radius: 50% and object-fit
- Use decorative empty alt when the name is next to the photo
- Centre text in a grid

Elements and CSS used

HTML elements	CSS features
ul, li, img, h2, p	border-radius: 50%, object-fit: cover, border, text-align: center, grid

Build guide

1. Write a <ul class="team"> with one <li> per person.
2. Add square photos with alt="" (the name follows as text).
3. Add h2 for the name and p for the role.
4. Grid the list with auto-fit.
5. Make the images 9rem circles with object-fit: cover.
6. Add a coloured ring with border.

Project 287: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - Team</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Meet the team</h1>
    <ul class="team">
      <li class="member"><img src="images/person-1.jpg" alt=""
width="200" height="200"><h2>Tarek Lotfy</h2><p>Founder</p></li>
      <li class="member"><img src="images/person-2.jpg" alt=""
width="200" height="200"><h2>Nadia Fawzy</h2><p>Manager</p></li>
      <li class="member"><img src="images/person-3.jpg" alt=""
width="200" height="200"><h2>Ali Hassan</h2><p>Specialist</p></li>
      <li class="member"><img src="images/person-4.jpg" alt=""
width="200" height="200"><h2>Mona Zaki</h2><p>Customer care</p></li>
    </ul>
  </main>
</body>
</html>
```

Project 287: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; text-
align: center; }
.team { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr)); }
.member img { width: 9rem; height: 9rem; border-radius: 50%; object-
fit: cover; border: 4px solid var(--accent); }
.member h2 { font-size: 1.05rem; margin: .75rem 0 .1rem; }
.member p { margin: 0; color: var(--muted); }
```

Project 287 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - Team</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Meet the team	The main heading; only one per page.
<ul class="team">	Unordered (bulleted) list.
<li class="member"><img src="images/person-1.jpg" alt="" width="200...	Second-level heading for a section.
<li class="member"><img src="images/person-2.jpg" alt="" width="200...	A paragraph of text.
<li class="member"><img src="images/person-3.jpg" alt="" width="200...	One list item.

Line	What it does
<li class="member"><img src="images/person-4.jpg" alt="" width="200...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr));	Defines the columns of the grid.
border-radius: 50%;	Turns a square into a circle.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
border: 4px solid var(--accent);	Changes the visual order of a flex item without changing the source.
font-size: 1.05rem;	Size of the text.

Check your work

- Photos are perfect circles even if the source is not square
- Names are headings
- Grid wraps
- Alt is empty because the name is visible text

Exercises

1. Add a short bio with <details>.
2. Add social links under each name.
3. Add a hover effect that lifts the card.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy

Field	Value
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 288: Team page for Byte Repair

Theme: Byte Repair (Nasr City) | Level 1 | Files: index.html, styles.css

Brief

Show four team members with circular photos, names and roles in a centred responsive grid.

Learning goals

- Make circular avatars with border-radius: 50% and object-fit
- Use decorative empty alt when the name is next to the photo
- Centre text in a grid

Elements and CSS used

HTML elements	CSS features
ul, li, img, h2, p	border-radius: 50%, object-fit: cover, border, text-align: center, grid

Build guide

1. Write a <ul class="team"> with one <li> per person.
2. Add square photos with alt="" (the name follows as text).
3. Add h2 for the name and p for the role.
4. Grid the list with auto-fit.
5. Make the images 9rem circles with object-fit: cover.
6. Add a coloured ring with border.

Project 288: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - Team</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Meet the team</h1>
    <ul class="team">
      <li class="member"><img src="images/person-1.jpg" alt=""
width="200" height="200"><h2>Mostafa Gamal</h2><p>Founder</p></li>
      <li class="member"><img src="images/person-2.jpg" alt=""
width="200" height="200"><h2>Nadia Fawzy</h2><p>Manager</p></li>
      <li class="member"><img src="images/person-3.jpg" alt=""
width="200" height="200"><h2>Ali Hassan</h2><p>Specialist</p></li>
      <li class="member"><img src="images/person-4.jpg" alt=""
width="200" height="200"><h2>Mona Zaki</h2><p>Customer care</p></li>
    </ul>
  </main>
</body>
</html>
```

Project 288: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; text-
align: center; }
.team { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr)); }
.member img { width: 9rem; height: 9rem; border-radius: 50%; object-
fit: cover; border: 4px solid var(--accent); }
.member h2 { font-size: 1.05rem; margin: .75rem 0 .1rem; }
.member p { margin: 0; color: var(--muted); }
```

Project 288 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - Team</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Meet the team	The main heading; only one per page.
<ul class="team">	Unordered (bulleted) list.
<li class="member"><img src="images/person-1.jpg" alt="" width="200...	Second-level heading for a section.
<li class="member"><img src="images/person-2.jpg" alt="" width="200...	A paragraph of text.
<li class="member"><img src="images/person-3.jpg" alt="" width="200...	One list item.

Line	What it does
<li class="member"><img src="images/person-4.jpg" alt="" width="200...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr));	Defines the columns of the grid.
border-radius: 50%;	Turns a square into a circle.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
border: 4px solid var(--accent);	Changes the visual order of a flex item without changing the source.
font-size: 1.05rem;	Size of the text.

Check your work

- Photos are perfect circles even if the source is not square
- Names are headings
- Grid wraps
- Alt is empty because the name is visible text

Exercises

1. Add a short bio with <details>.
2. Add social links under each name.
3. Add a hover effect that lifts the card.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal

Field	Value
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 289: Team page for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 1 | Files: index.html, styles.css

Brief

Show four team members with circular photos, names and roles in a centred responsive grid.

Learning goals

- Make circular avatars with border-radius: 50% and object-fit
- Use decorative empty alt when the name is next to the photo
- Centre text in a grid

Elements and CSS used

HTML elements	CSS features
ul, li, img, h2, p	border-radius: 50%, object-fit: cover, border, text-align: center, grid

Build guide

1. Write a <ul class="team"> with one <li> per person.
2. Add square photos with alt="" (the name follows as text).
3. Add h2 for the name and p for the role.
4. Grid the list with auto-fit.
5. Make the images 9rem circles with object-fit: cover.
6. Add a coloured ring with border.

Project 289: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - Team</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Meet the team</h1>
    <ul class="team">
      <li class="member"><img src="images/person-1.jpg" alt=""
width="200" height="200"><h2>Rana Ibrahim</h2><p>Founder</p></li>
      <li class="member"><img src="images/person-2.jpg" alt=""
width="200" height="200"><h2>Nadia Fawzy</h2><p>Manager</p></li>
      <li class="member"><img src="images/person-3.jpg" alt=""
width="200" height="200"><h2>Ali Hassan</h2><p>Specialist</p></li>
      <li class="member"><img src="images/person-4.jpg" alt=""
width="200" height="200"><h2>Mona Zaki</h2><p>Customer care</p></li>
    </ul>
  </main>
</body>
</html>
```

Project 289: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; text-
align: center; }
.team { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr)); }
.member img { width: 9rem; height: 9rem; border-radius: 50%; object-
fit: cover; border: 4px solid var(--accent); }
.member h2 { font-size: 1.05rem; margin: .75rem 0 .1rem; }
.member p { margin: 0; color: var(--muted); }
```

Project 289 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - Team</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Meet the team	The main heading; only one per page.
<ul class="team">	Unordered (bulleted) list.
<li class="member"><img src="images/person-1.jpg" alt="" width="200...	Second-level heading for a section.
<li class="member"><img src="images/person-2.jpg" alt="" width="200...	A paragraph of text.
<li class="member"><img src="images/person-3.jpg" alt="" width="200...	One list item.

Line	What it does
<li class="member"><img src="images/person-4.jpg" alt="" width="200...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr));	Defines the columns of the grid.
border-radius: 50%;	Turns a square into a circle.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
border: 4px solid var(--accent);	Changes the visual order of a flex item without changing the source.
font-size: 1.05rem;	Size of the text.

Check your work

- Photos are perfect circles even if the source is not square
- Names are headings
- Grid wraps
- Alt is empty because the name is visible text

Exercises

1. Add a short bio with <details>.
2. Add social links under each name.
3. Add a hover effect that lifts the card.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim

Field	Value
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 290: Team page for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Show four team members with circular photos, names and roles in a centred responsive grid.

Learning goals

- Make circular avatars with border-radius: 50% and object-fit
- Use decorative empty alt when the name is next to the photo
- Centre text in a grid

Elements and CSS used

HTML elements	CSS features
ul, li, img, h2, p	border-radius: 50%, object-fit: cover, border, text-align: center, grid

Build guide

1. Write a <ul class="team"> with one <li> per person.
2. Add square photos with alt="" (the name follows as text).
3. Add h2 for the name and p for the role.
4. Grid the list with auto-fit.
5. Make the images 9rem circles with object-fit: cover.
6. Add a coloured ring with border.

Project 290: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - Team</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Meet the team</h1>
    <ul class="team">
      <li class="member"><img src="images/person-1.jpg" alt=""
width="200" height="200"><h2>Amr Selim</h2><p>Founder</p></li>
      <li class="member"><img src="images/person-2.jpg" alt=""
width="200" height="200"><h2>Nadia Fawzy</h2><p>Manager</p></li>
      <li class="member"><img src="images/person-3.jpg" alt=""
width="200" height="200"><h2>Ali Hassan</h2><p>Specialist</p></li>
      <li class="member"><img src="images/person-4.jpg" alt=""
width="200" height="200"><h2>Mona Zaki</h2><p>Customer care</p></li>
    </ul>
  </main>
</body>
</html>
```

Project 290: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; text-
align: center; }
.team { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr)); }
.member img { width: 9rem; height: 9rem; border-radius: 50%; object-
fit: cover; border: 4px solid var(--accent); }
.member h2 { font-size: 1.05rem; margin: .75rem 0 .1rem; }
.member p { margin: 0; color: var(--muted); }
```

Project 290 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - Team</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Meet the team	The main heading; only one per page.
<ul class="team">	Unordered (bulleted) list.
<li class="member"><img src="images/person-1.jpg" alt="" width="200...	Second-level heading for a section.
<li class="member"><img src="images/person-2.jpg" alt="" width="200...	A paragraph of text.
<li class="member"><img src="images/person-3.jpg" alt="" width="200...	One list item.

Line	What it does
<li class="member"><img src="images/person-4.jpg" alt="" width="200...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr));	Defines the columns of the grid.
border-radius: 50%;	Turns a square into a circle.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
border: 4px solid var(--accent);	Changes the visual order of a flex item without changing the source.
font-size: 1.05rem;	Size of the text.

Check your work

- Photos are perfect circles even if the source is not square
- Names are headings
- Grid wraps
- Alt is empty because the name is visible text

Exercises

1. Add a short bio with <details>.
2. Add social links under each name.
3. Add a hover effect that lifts the card.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim

Field	Value
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 291: Team page for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Show four team members with circular photos, names and roles in a centred responsive grid.

Learning goals

- Make circular avatars with border-radius: 50% and object-fit
- Use decorative empty alt when the name is next to the photo
- Centre text in a grid

Elements and CSS used

HTML elements	CSS features
ul, li, img, h2, p	border-radius: 50%, object-fit: cover, border, text-align: center, grid

Build guide

1. Write a <ul class="team"> with one <li> per person.
2. Add square photos with alt="" (the name follows as text).
3. Add h2 for the name and p for the role.
4. Grid the list with auto-fit.
5. Make the images 9rem circles with object-fit: cover.
6. Add a coloured ring with border.

Project 291: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - Team</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Meet the team</h1>
    <ul class="team">
      <li class="member"><img src="images/person-1.jpg" alt=""
width="200" height="200"><h2>Habiba Saleh</h2><p>Founder</p></li>
      <li class="member"><img src="images/person-2.jpg" alt=""
width="200" height="200"><h2>Nadia Fawzy</h2><p>Manager</p></li>
      <li class="member"><img src="images/person-3.jpg" alt=""
width="200" height="200"><h2>Ali Hassan</h2><p>Specialist</p></li>
      <li class="member"><img src="images/person-4.jpg" alt=""
width="200" height="200"><h2>Mona Zaki</h2><p>Customer care</p></li>
    </ul>
  </main>
</body>
</html>
```

Project 291: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; text-
align: center; }
.team { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr)); }
.member img { width: 9rem; height: 9rem; border-radius: 50%; object-
fit: cover; border: 4px solid var(--accent); }
.member h2 { font-size: 1.05rem; margin: .75rem 0 .1rem; }
.member p { margin: 0; color: var(--muted); }
```

Project 291 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - Team</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Meet the team	The main heading; only one per page.
<ul class="team">	Unordered (bulleted) list.
<li class="member"><img src="images/person-1.jpg" alt="" width="200...	Second-level heading for a section.
<li class="member"><img src="images/person-2.jpg" alt="" width="200...	A paragraph of text.
<li class="member"><img src="images/person-3.jpg" alt="" width="200...	One list item.

Line	What it does
<li class="member"><img src="images/person-4.jpg" alt="" width="200...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr));	Defines the columns of the grid.
border-radius: 50%;	Turns a square into a circle.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
border: 4px solid var(--accent);	Changes the visual order of a flex item without changing the source.
font-size: 1.05rem;	Size of the text.

Check your work

- Photos are perfect circles even if the source is not square
- Names are headings
- Grid wraps
- Alt is empty because the name is visible text

Exercises

1. Add a short bio with <details>.
2. Add social links under each name.
3. Add a hover effect that lifts the card.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh

Field	Value
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 292: Team page for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 1 | Files: index.html, styles.css

Brief

Show four team members with circular photos, names and roles in a centred responsive grid.

Learning goals

- Make circular avatars with border-radius: 50% and object-fit
- Use decorative empty alt when the name is next to the photo
- Centre text in a grid

Elements and CSS used

HTML elements	CSS features
ul, li, img, h2, p	border-radius: 50%, object-fit: cover, border, text-align: center, grid

Build guide

1. Write a <ul class="team"> with one <li> per person.
2. Add square photos with alt="" (the name follows as text).
3. Add h2 for the name and p for the role.
4. Grid the list with auto-fit.
5. Make the images 9rem circles with object-fit: cover.
6. Add a coloured ring with border.

Project 292: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - Team</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Meet the team</h1>
    <ul class="team">
      <li class="member"><img src="images/person-1.jpg" alt="" 
width="200" height="200"><h2>Ahmed Mahmoud</h2><p>Founder</p></li>
      <li class="member"><img src="images/person-2.jpg" alt="" 
width="200" height="200"><h2>Nadia Fawzy</h2><p>Manager</p></li>
      <li class="member"><img src="images/person-3.jpg" alt="" 
width="200" height="200"><h2>Ali Hassan</h2><p>Specialist</p></li>
      <li class="member"><img src="images/person-4.jpg" alt="" 
width="200" height="200"><h2>Mona Zaki</h2><p>Customer care</p></li>
    </ul>
  </main>
</body>
</html>
```

Project 292: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted: 
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; text-
align: center; }
.team { list-style: none; padding: 0; display: grid; gap: 1.5rem; 
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr)); }
.member img { width: 9rem; height: 9rem; border-radius: 50%; object-
fit: cover; border: 4px solid var(--accent); }
.member h2 { font-size: 1.05rem; margin: .75rem 0 .1rem; }
.member p { margin: 0; color: var(--muted); }
```

Project 292 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - Team</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Meet the team	The main heading; only one per page.
<ul class="team">	Unordered (bulleted) list.
<li class="member"><img src="images/person-1.jpg" alt="" width="200...	Second-level heading for a section.
<li class="member"><img src="images/person-2.jpg" alt="" width="200...	A paragraph of text.
<li class="member"><img src="images/person-3.jpg" alt="" width="200...	One list item.

Line	What it does
<li class="member"><img src="images/person-4.jpg" alt="" width="200...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr));	Defines the columns of the grid.
border-radius: 50%;	Turns a square into a circle.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
border: 4px solid var(--accent);	Changes the visual order of a flex item without changing the source.
font-size: 1.05rem;	Size of the text.

Check your work

- Photos are perfect circles even if the source is not square
- Names are headings
- Grid wraps
- Alt is empty because the name is visible text

Exercises

1. Add a short bio with <details>.
2. Add social links under each name.
3. Add a hover effect that lifts the card.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud

Field	Value
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 293: Team page for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 1 | Files: index.html, styles.css

Brief

Show four team members with circular photos, names and roles in a centred responsive grid.

Learning goals

- Make circular avatars with border-radius: 50% and object-fit
- Use decorative empty alt when the name is next to the photo
- Centre text in a grid

Elements and CSS used

HTML elements	CSS features
ul, li, img, h2, p	border-radius: 50%, object-fit: cover, border, text-align: center, grid

Build guide

1. Write a <ul class="team"> with one <li> per person.
2. Add square photos with alt="" (the name follows as text).
3. Add h2 for the name and p for the role.
4. Grid the list with auto-fit.
5. Make the images 9rem circles with object-fit: cover.
6. Add a coloured ring with border.

Project 293: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - Team</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Meet the team</h1>
    <ul class="team">
      <li class="member"><img src="images/person-1.jpg" alt=""
width="200" height="200"><h2>Mariam Adel</h2><p>Founder</p></li>
      <li class="member"><img src="images/person-2.jpg" alt=""
width="200" height="200"><h2>Nadia Fawzy</h2><p>Manager</p></li>
      <li class="member"><img src="images/person-3.jpg" alt=""
width="200" height="200"><h2>Ali Hassan</h2><p>Specialist</p></li>
      <li class="member"><img src="images/person-4.jpg" alt=""
width="200" height="200"><h2>Mona Zaki</h2><p>Customer care</p></li>
    </ul>
  </main>
</body>
</html>
```

Project 293: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; text-
align: center; }
.team { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr)); }
.member img { width: 9rem; height: 9rem; border-radius: 50%; object-
fit: cover; border: 4px solid var(--accent); }
.member h2 { font-size: 1.05rem; margin: .75rem 0 .1rem; }
.member p { margin: 0; color: var(--muted); }
```

Project 293 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - Team</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Meet the team	The main heading; only one per page.
<ul class="team">	Unordered (bulleted) list.
<li class="member"><img src="images/person-1.jpg" alt="" width="200...	Second-level heading for a section.
<li class="member"><img src="images/person-2.jpg" alt="" width="200...	A paragraph of text.
<li class="member"><img src="images/person-3.jpg" alt="" width="200...	One list item.

Line	What it does
<li class="member"><img src="images/person-4.jpg" alt="" width="200...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr));	Defines the columns of the grid.
border-radius: 50%;	Turns a square into a circle.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
border: 4px solid var(--accent);	Changes the visual order of a flex item without changing the source.
font-size: 1.05rem;	Size of the text.

Check your work

- Photos are perfect circles even if the source is not square
- Names are headings
- Grid wraps
- Alt is empty because the name is visible text

Exercises

1. Add a short bio with <details>.
2. Add social links under each name.
3. Add a hover effect that lifts the card.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel

Field	Value
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 294: Team page for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 1 | Files: index.html, styles.css

Brief

Show four team members with circular photos, names and roles in a centred responsive grid.

Learning goals

- Make circular avatars with border-radius: 50% and object-fit
- Use decorative empty alt when the name is next to the photo
- Centre text in a grid

Elements and CSS used

HTML elements	CSS features
ul, li, img, h2, p	border-radius: 50%, object-fit: cover, border, text-align: center, grid

Build guide

1. Write a <ul class="team"> with one <li> per person.
2. Add square photos with alt="" (the name follows as text).
3. Add h2 for the name and p for the role.
4. Grid the list with auto-fit.
5. Make the images 9rem circles with object-fit: cover.
6. Add a coloured ring with border.

Project 294: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - Team</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Meet the team</h1>
    <ul class="team">
      <li class="member"><img src="images/person-1.jpg" alt=""
width="200" height="200"><h2>Khaled Nasser</h2><p>Founder</p></li>
      <li class="member"><img src="images/person-2.jpg" alt=""
width="200" height="200"><h2>Nadia Fawzy</h2><p>Manager</p></li>
      <li class="member"><img src="images/person-3.jpg" alt=""
width="200" height="200"><h2>Ali Hassan</h2><p>Specialist</p></li>
      <li class="member"><img src="images/person-4.jpg" alt=""
width="200" height="200"><h2>Mona Zaki</h2><p>Customer care</p></li>
    </ul>
  </main>
</body>
</html>
```

Project 294: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; text-
align: center; }
.team { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr)); }
.member img { width: 9rem; height: 9rem; border-radius: 50%; object-
fit: cover; border: 4px solid var(--accent); }
.member h2 { font-size: 1.05rem; margin: .75rem 0 .1rem; }
.member p { margin: 0; color: var(--muted); }
```

Project 294 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - Team</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Meet the team	The main heading; only one per page.
<ul class="team">	Unordered (bulleted) list.
<li class="member"><img src="images/person-1.jpg" alt="" width="200...	Second-level heading for a section.
<li class="member"><img src="images/person-2.jpg" alt="" width="200...	A paragraph of text.
<li class="member"><img src="images/person-3.jpg" alt="" width="200...	One list item.

Line	What it does
<li class="member"><img src="images/person-4.jpg" alt="" width="200...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr));	Defines the columns of the grid.
border-radius: 50%;	Turns a square into a circle.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
border: 4px solid var(--accent);	Changes the visual order of a flex item without changing the source.
font-size: 1.05rem;	Size of the text.

Check your work

- Photos are perfect circles even if the source is not square
- Names are headings
- Grid wraps
- Alt is empty because the name is visible text

Exercises

1. Add a short bio with <details>.
2. Add social links under each name.
3. Add a hover effect that lifts the card.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser

Field	Value
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 295: Team page for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 1 | Files: index.html, styles.css

Brief

Show four team members with circular photos, names and roles in a centred responsive grid.

Learning goals

- Make circular avatars with border-radius: 50% and object-fit
- Use decorative empty alt when the name is next to the photo
- Centre text in a grid

Elements and CSS used

HTML elements	CSS features
ul, li, img, h2, p	border-radius: 50%, object-fit: cover, border, text-align: center, grid

Build guide

1. Write a <ul class="team"> with one <li> per person.
2. Add square photos with alt="" (the name follows as text).
3. Add h2 for the name and p for the role.
4. Grid the list with auto-fit.
5. Make the images 9rem circles with object-fit: cover.
6. Add a coloured ring with border.

Project 295: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - Team</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Meet the team</h1>
    <ul class="team">
      <li class="member"><img src="images/person-1.jpg" alt=""
width="200" height="200"><h2>Salma Ragab</h2><p>Founder</p></li>
      <li class="member"><img src="images/person-2.jpg" alt=""
width="200" height="200"><h2>Nadia Fawzy</h2><p>Manager</p></li>
      <li class="member"><img src="images/person-3.jpg" alt=""
width="200" height="200"><h2>Ali Hassan</h2><p>Specialist</p></li>
      <li class="member"><img src="images/person-4.jpg" alt=""
width="200" height="200"><h2>Mona Zaki</h2><p>Customer care</p></li>
    </ul>
  </main>
</body>
</html>
```

Project 295: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; text-
align: center; }
.team { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr)); }
.member img { width: 9rem; height: 9rem; border-radius: 50%; object-
fit: cover; border: 4px solid var(--accent); }
.member h2 { font-size: 1.05rem; margin: .75rem 0 .1rem; }
.member p { margin: 0; color: var(--muted); }
```

Project 295 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - Team</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Meet the team	The main heading; only one per page.
<ul class="team">	Unordered (bulleted) list.
<li class="member"><img src="images/person-1.jpg" alt="" width="200...	Second-level heading for a section.
<li class="member"><img src="images/person-2.jpg" alt="" width="200...	A paragraph of text.
<li class="member"><img src="images/person-3.jpg" alt="" width="200...	One list item.

Line	What it does
<li class="member"><img src="images/person-4.jpg" alt="" width="200...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr));	Defines the columns of the grid.
border-radius: 50%;	Turns a square into a circle.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
border: 4px solid var(--accent);	Changes the visual order of a flex item without changing the source.
font-size: 1.05rem;	Size of the text.

Check your work

- Photos are perfect circles even if the source is not square
- Names are headings
- Grid wraps
- Alt is empty because the name is visible text

Exercises

1. Add a short bio with <details>.
2. Add social links under each name.
3. Add a hover effect that lifts the card.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab

Field	Value
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 296: Team page for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 1 | Files: index.html, styles.css

Brief

Show four team members with circular photos, names and roles in a centred responsive grid.

Learning goals

- Make circular avatars with border-radius: 50% and object-fit
- Use decorative empty alt when the name is next to the photo
- Centre text in a grid

Elements and CSS used

HTML elements	CSS features
ul, li, img, h2, p	border-radius: 50%, object-fit: cover, border, text-align: center, grid

Build guide

1. Write a <ul class="team"> with one <li> per person.
2. Add square photos with alt="" (the name follows as text).
3. Add h2 for the name and p for the role.
4. Grid the list with auto-fit.
5. Make the images 9rem circles with object-fit: cover.
6. Add a coloured ring with border.

Project 296: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - Team</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Meet the team</h1>
    <ul class="team">
      <li class="member"><img src="images/person-1.jpg" alt=""
width="200" height="200"><h2>Sherif Wahba</h2><p>Founder</p></li>
      <li class="member"><img src="images/person-2.jpg" alt=""
width="200" height="200"><h2>Nadia Fawzy</h2><p>Manager</p></li>
      <li class="member"><img src="images/person-3.jpg" alt=""
width="200" height="200"><h2>Ali Hassan</h2><p>Specialist</p></li>
      <li class="member"><img src="images/person-4.jpg" alt=""
width="200" height="200"><h2>Mona Zaki</h2><p>Customer care</p></li>
    </ul>
  </main>
</body>
</html>
```

Project 296: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; text-
align: center; }
.team { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr)); }
.member img { width: 9rem; height: 9rem; border-radius: 50%; object-
fit: cover; border: 4px solid var(--accent); }
.member h2 { font-size: 1.05rem; margin: .75rem 0 .1rem; }
.member p { margin: 0; color: var(--muted); }
```

Project 296 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - Team</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Meet the team	The main heading; only one per page.
<ul class="team">	Unordered (bulleted) list.
<li class="member"><img src="images/person-1.jpg" alt="" width="200...	Second-level heading for a section.
<li class="member"><img src="images/person-2.jpg" alt="" width="200...	A paragraph of text.
<li class="member"><img src="images/person-3.jpg" alt="" width="200...	One list item.

Line	What it does
<li class="member"><img src="images/person-4.jpg" alt="" width="200...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr));	Defines the columns of the grid.
border-radius: 50%;	Turns a square into a circle.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
border: 4px solid var(--accent);	Changes the visual order of a flex item without changing the source.
font-size: 1.05rem;	Size of the text.

Check your work

- Photos are perfect circles even if the source is not square
- Names are headings
- Grid wraps
- Alt is empty because the name is visible text

Exercises

1. Add a short bio with <details>.
2. Add social links under each name.
3. Add a hover effect that lifts the card.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba

Field	Value
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 297: Team page for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 1 | Files: index.html, styles.css

Brief

Show four team members with circular photos, names and roles in a centred responsive grid.

Learning goals

- Make circular avatars with border-radius: 50% and object-fit
- Use decorative empty alt when the name is next to the photo
- Centre text in a grid

Elements and CSS used

HTML elements	CSS features
ul, li, img, h2, p	border-radius: 50%, object-fit: cover, border, text-align: center, grid

Build guide

1. Write a <ul class="team"> with one <li> per person.
2. Add square photos with alt="" (the name follows as text).
3. Add h2 for the name and p for the role.
4. Grid the list with auto-fit.
5. Make the images 9rem circles with object-fit: cover.
6. Add a coloured ring with border.

Project 297: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - Team</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Meet the team</h1>
    <ul class="team">
      <li class="member"><img src="images/person-1.jpg" alt=""
width="200" height="200"><h2>Ghada Kamel</h2><p>Founder</p></li>
      <li class="member"><img src="images/person-2.jpg" alt=""
width="200" height="200"><h2>Nadia Fawzy</h2><p>Manager</p></li>
      <li class="member"><img src="images/person-3.jpg" alt=""
width="200" height="200"><h2>Ali Hassan</h2><p>Specialist</p></li>
      <li class="member"><img src="images/person-4.jpg" alt=""
width="200" height="200"><h2>Mona Zaki</h2><p>Customer care</p></li>
    </ul>
  </main>
</body>
</html>
```

Project 297: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; text-
align: center; }
.team { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr)); }
.member img { width: 9rem; height: 9rem; border-radius: 50%; object-
fit: cover; border: 4px solid var(--accent); }
.member h2 { font-size: 1.05rem; margin: .75rem 0 .1rem; }
.member p { margin: 0; color: var(--muted); }
```

Project 297 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - Team</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Meet the team	The main heading; only one per page.
<ul class="team">	Unordered (bulleted) list.
<li class="member"><img src="images/person-1.jpg" alt="" width="200...	Second-level heading for a section.
<li class="member"><img src="images/person-2.jpg" alt="" width="200...	A paragraph of text.
<li class="member"><img src="images/person-3.jpg" alt="" width="200...	One list item.

Line	What it does
<li class="member"><img src="images/person-4.jpg" alt="" width="200...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr));	Defines the columns of the grid.
border-radius: 50%;	Turns a square into a circle.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
border: 4px solid var(--accent);	Changes the visual order of a flex item without changing the source.
font-size: 1.05rem;	Size of the text.

Check your work

- Photos are perfect circles even if the source is not square
- Names are headings
- Grid wraps
- Alt is empty because the name is visible text

Exercises

1. Add a short bio with <details>.
2. Add social links under each name.
3. Add a hover effect that lifts the card.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel

Field	Value
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 298: Team page for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Show four team members with circular photos, names and roles in a centred responsive grid.

Learning goals

- Make circular avatars with border-radius: 50% and object-fit
- Use decorative empty alt when the name is next to the photo
- Centre text in a grid

Elements and CSS used

HTML elements	CSS features
ul, li, img, h2, p	border-radius: 50%, object-fit: cover, border, text-align: center, grid

Build guide

1. Write a <ul class="team"> with one <li> per person.
2. Add square photos with alt="" (the name follows as text).
3. Add h2 for the name and p for the role.
4. Grid the list with auto-fit.
5. Make the images 9rem circles with object-fit: cover.
6. Add a coloured ring with border.

Project 298: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - Team</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Meet the team</h1>
    <ul class="team">
      <li class="member"><img src="images/person-1.jpg" alt=""
width="200" height="200"><h2>Fatma Hassan</h2><p>Founder</p></li>
      <li class="member"><img src="images/person-2.jpg" alt=""
width="200" height="200"><h2>Nadia Fawzy</h2><p>Manager</p></li>
      <li class="member"><img src="images/person-3.jpg" alt=""
width="200" height="200"><h2>Ali Hassan</h2><p>Specialist</p></li>
      <li class="member"><img src="images/person-4.jpg" alt=""
width="200" height="200"><h2>Mona Zaki</h2><p>Customer care</p></li>
    </ul>
  </main>
</body>
</html>
```

Project 298: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; text-
align: center; }
.team { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr)); }
.member img { width: 9rem; height: 9rem; border-radius: 50%; object-
fit: cover; border: 4px solid var(--accent); }
.member h2 { font-size: 1.05rem; margin: .75rem 0 .1rem; }
.member p { margin: 0; color: var(--muted); }
```

Project 298 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - Team</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Meet the team	The main heading; only one per page.
<ul class="team">	Unordered (bulleted) list.
<li class="member"><img src="images/person-1.jpg" alt="" width="200...	Second-level heading for a section.
<li class="member"><img src="images/person-2.jpg" alt="" width="200...	A paragraph of text.
<li class="member"><img src="images/person-3.jpg" alt="" width="200...	One list item.

Line	What it does
<li class="member"><img src="images/person-4.jpg" alt="" width="200...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr));	Defines the columns of the grid.
border-radius: 50%;	Turns a square into a circle.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
border: 4px solid var(--accent);	Changes the visual order of a flex item without changing the source.
font-size: 1.05rem;	Size of the text.

Check your work

- Photos are perfect circles even if the source is not square
- Names are headings
- Grid wraps
- Alt is empty because the name is visible text

Exercises

1. Add a short bio with <details>.
2. Add social links under each name.
3. Add a hover effect that lifts the card.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan

Field	Value
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 299: Team page for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 1 | Files: index.html, styles.css

Brief

Show four team members with circular photos, names and roles in a centred responsive grid.

Learning goals

- Make circular avatars with border-radius: 50% and object-fit
- Use decorative empty alt when the name is next to the photo
- Centre text in a grid

Elements and CSS used

HTML elements	CSS features
ul, li, img, h2, p	border-radius: 50%, object-fit: cover, border, text-align: center, grid

Build guide

1. Write a <ul class="team"> with one <li> per person.
2. Add square photos with alt="" (the name follows as text).
3. Add h2 for the name and p for the role.
4. Grid the list with auto-fit.
5. Make the images 9rem circles with object-fit: cover.
6. Add a coloured ring with border.

Project 299: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - Team</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Meet the team</h1>
    <ul class="team">
      <li class="member"><img src="images/person-1.jpg" alt=""
width="200" height="200"><h2>Bassem Adly</h2><p>Founder</p></li>
      <li class="member"><img src="images/person-2.jpg" alt=""
width="200" height="200"><h2>Nadia Fawzy</h2><p>Manager</p></li>
      <li class="member"><img src="images/person-3.jpg" alt=""
width="200" height="200"><h2>Ali Hassan</h2><p>Specialist</p></li>
      <li class="member"><img src="images/person-4.jpg" alt=""
width="200" height="200"><h2>Mona Zaki</h2><p>Customer care</p></li>
    </ul>
  </main>
</body>
</html>
```

Project 299: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; text-
align: center; }
.team { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr)); }
.member img { width: 9rem; height: 9rem; border-radius: 50%; object-
fit: cover; border: 4px solid var(--accent); }
.member h2 { font-size: 1.05rem; margin: .75rem 0 .1rem; }
.member p { margin: 0; color: var(--muted); }
```

Project 299 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - Team</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Meet the team	The main heading; only one per page.
<ul class="team">	Unordered (bulleted) list.
<li class="member"><img src="images/person-1.jpg" alt="" width="200...	Second-level heading for a section.
<li class="member"><img src="images/person-2.jpg" alt="" width="200...	A paragraph of text.
<li class="member"><img src="images/person-3.jpg" alt="" width="200...	One list item.

Line	What it does
<li class="member"><img src="images/person-4.jpg" alt="" width="200...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr));	Defines the columns of the grid.
border-radius: 50%;	Turns a square into a circle.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
border: 4px solid var(--accent);	Changes the visual order of a flex item without changing the source.
font-size: 1.05rem;	Size of the text.

Check your work

- Photos are perfect circles even if the source is not square
- Names are headings
- Grid wraps
- Alt is empty because the name is visible text

Exercises

1. Add a short bio with <details>.
2. Add social links under each name.
3. Add a hover effect that lifts the card.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly

Field	Value
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 300: Team page for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 1 | Files: index.html, styles.css

Brief

Show four team members with circular photos, names and roles in a centred responsive grid.

Learning goals

- Make circular avatars with border-radius: 50% and object-fit
- Use decorative empty alt when the name is next to the photo
- Centre text in a grid

Elements and CSS used

HTML elements	CSS features
ul, li, img, h2, p	border-radius: 50%, object-fit: cover, border, text-align: center, grid

Build guide

1. Write a <ul class="team"> with one <li> per person.
2. Add square photos with alt="" (the name follows as text).
3. Add h2 for the name and p for the role.
4. Grid the list with auto-fit.
5. Make the images 9rem circles with object-fit: cover.
6. Add a coloured ring with border.

Project 300: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - Team</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Meet the team</h1>
    <ul class="team">
      <li class="member"><img src="images/person-1.jpg" alt="" 
width="200" height="200"><h2>Youssef Hany</h2><p>Founder</p></li>
      <li class="member"><img src="images/person-2.jpg" alt="" 
width="200" height="200"><h2>Nadia Fawzy</h2><p>Manager</p></li>
      <li class="member"><img src="images/person-3.jpg" alt="" 
width="200" height="200"><h2>Ali Hassan</h2><p>Specialist</p></li>
      <li class="member"><img src="images/person-4.jpg" alt="" 
width="200" height="200"><h2>Mona Zaki</h2><p>Customer care</p></li>
    </ul>
  </main>
</body>
</html>
```

Project 300: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted: 
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; text-
align: center; }
.team { list-style: none; padding: 0; display: grid; gap: 1.5rem; 
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr)); }
.member img { width: 9rem; height: 9rem; border-radius: 50%; object-
fit: cover; border: 4px solid var(--accent); }
.member h2 { font-size: 1.05rem; margin: .75rem 0 .1rem; }
.member p { margin: 0; color: var(--muted); }
```

Project 300 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - Team</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Meet the team	The main heading; only one per page.
<ul class="team">	Unordered (bulleted) list.
<li class="member"><img src="images/person-1.jpg" alt="" width="200...	Second-level heading for a section.
<li class="member"><img src="images/person-2.jpg" alt="" width="200...	A paragraph of text.
<li class="member"><img src="images/person-3.jpg" alt="" width="200...	One list item.

Line	What it does
<li class="member"><img src="images/person-4.jpg" alt="" width="200...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(11rem, 1fr));	Defines the columns of the grid.
border-radius: 50%;	Turns a square into a circle.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
border: 4px solid var(--accent);	Changes the visual order of a flex item without changing the source.
font-size: 1.05rem;	Size of the text.

Check your work

- Photos are perfect circles even if the source is not square
- Names are headings
- Grid wraps
- Alt is empty because the name is visible text

Exercises

1. Add a short bio with <details>.
2. Add social links under each name.
3. Add a hover effect that lifts the card.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany

Field	Value
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Testimonials section

Level 2 | 25 projects, one per theme

Show three customer quotes as cards with a large decorative quotation mark, the customer's name and a star rating.

Project 301: Testimonials section for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 2 | Files: index.html, styles.css

Brief

Show three customer quotes as cards with a large decorative quotation mark, the customer's name and a star rating.

Learning goals

- Mark up quotes correctly with figure, blockquote and figcaption
- Position a decorative ::before
- Label icon-only content with aria-label

Elements and CSS used

HTML elements	CSS features
figure, blockquote, p, figcaption, span	position: relative/absolute, ::before, content, opacity, font-style, grid

Build guide

1. Write one <figure> per review: blockquote with the text, figcaption with the name.
2. Add the stars in a span with an aria-label.
3. Grid the figures.
4. Set figure position: relative.
5. Add the big quotation mark with ::before positioned absolutely.
6. Colour the stars.

Project 301: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Reviews</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What customers say about Cairo Book Shop</h1>
    <div class="quotes">
      <figure>
        <blockquote><p>The best book experience in Giza.</p></
blockquote>
        <figcaption>Heba M. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>Friendly staff and fair prices.</p></
blockquote>
        <figcaption>Ziad K. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>I recommend them to everyone.</p></blockquote>
        <figcaption>Rania S. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
    </div>
  </main>
</body>
</html>
```

Project 301: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.quotes { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(16rem, 1fr)); }
figure { margin: 0; padding: 1.5rem; background: var(--accent);
border-radius: 14px; position: relative; }
figure::before { content: "\201C"; position: absolute; top: -.2em;
```

```
left: .4rem; font-size: 5rem; color: var(--brand); opacity: .25; font-
family: Georgia, serif; }
blockquote { margin: 0 0 1rem; font-size: 1.1rem; font-style: italic;
}
figcaption { font-weight: 600; }
.stars { color: #f59e0b; margin-left: .5rem; }
```

Project 301 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - Reviews</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What customers say about Cairo Book Shop	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure>	Self-contained media with an optional caption.
<blockquote> The best book experience in Giza. </blockquote>	A paragraph of text.
<figcaption>Heba M. <span class="stars" aria-label="5 out of 5 star...	Caption for the figure.

Line	What it does
<blockquote> Friendly staff and fair prices. </blockquote>	A long quotation from another source.
<figcaption>Ziad K. <span class="stars" aria-label="5 out of 5 star...	Generic inline container for styling.
<figcaption>Rania S. <span class="stars" aria-label="5 out of 5 sta...	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 14px;	Rounds the corners.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "\201C";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
font-size: 5rem;	Size of the text.
opacity: .25;	Transparency from 0 (invisible) to 1 (solid).
font-weight: 600;	Thickness of the text.

Check your work

- Attribution is outside the blockquote
- Stars have a text alternative
- Quote mark does not overlap text badly
- Cards equal height

Exercises

1. Add photos of the customers.
2. Turn the section into a horizontal scroll-snap carousel.
3. Add schema.org Review microdata.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 302: Testimonials section for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 2 | Files: index.html, styles.css

Brief

Show three customer quotes as cards with a large decorative quotation mark, the customer's name and a star rating.

Learning goals

- Mark up quotes correctly with figure, blockquote and figcaption
- Position a decorative ::before
- Label icon-only content with aria-label

Elements and CSS used

HTML elements	CSS features
figure, blockquote, p, figcaption, span	position: relative/absolute, ::before, content, opacity, font-style, grid

Build guide

1. Write one <figure> per review: blockquote with the text, figcaption with the name.
2. Add the stars in a span with an aria-label.
3. Grid the figures.
4. Set figure position: relative.
5. Add the big quotation mark with ::before positioned absolutely.
6. Colour the stars.

Project 302: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - Reviews</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What customers say about Nile Bakery</h1>
    <div class="quotes">
      <figure>
        <blockquote><p>The best pastry experience in Cairo.</p></
blockquote>
        <figcaption>Heba M. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>Friendly staff and fair prices.</p></
blockquote>
        <figcaption>Ziad K. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>I recommend them to everyone.</p></blockquote>
        <figcaption>Rania S. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
    </div>
  </main>
</body>
</html>
```

Project 302: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.quotes { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(16rem, 1fr)); }
figure { margin: 0; padding: 1.5rem; background: var(--accent);
border-radius: 14px; position: relative; }
figure::before { content: "\201C"; position: absolute; top: -.2em;
```

```
left: .4rem; font-size: 5rem; color: var(--brand); opacity: .25; font-
family: Georgia, serif; }
blockquote { margin: 0 0 1rem; font-size: 1.1rem; font-style: italic;
}
figcaption { font-weight: 600; }
.stars { color: #f59e0b; margin-left: .5rem; }
```

Project 302 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - Reviews</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What customers say about Nile Bakery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure>	Self-contained media with an optional caption.
<blockquote> The best pastry experience in Cairo. </blockquote>	A paragraph of text.
<figcaption>Heba M. <span class="stars" aria-label="5 out of 5 star...	Caption for the figure.

Line	What it does
<blockquote> Friendly staff and fair prices. </blockquote>	A long quotation from another source.
<figcaption>Ziad K. <span class="stars" aria-label="5 out of 5 star...	Generic inline container for styling.
<figcaption>Rania S. <span class="stars" aria-label="5 out of 5 sta...	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 14px;	Rounds the corners.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "\201C";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
font-size: 5rem;	Size of the text.
opacity: .25;	Transparency from 0 (invisible) to 1 (solid).
font-weight: 600;	Thickness of the text.

Check your work

- Attribution is outside the blockquote
- Stars have a text alternative
- Quote mark does not overlap text badly
- Cards equal height

Exercises

1. Add photos of the customers.
2. Turn the section into a horizontal scroll-snap carousel.
3. Add schema.org Review microdata.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 303: Testimonials section for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 2 | Files: index.html, styles.css

Brief

Show three customer quotes as cards with a large decorative quotation mark, the customer's name and a star rating.

Learning goals

- Mark up quotes correctly with figure, blockquote and figcaption
- Position a decorative ::before
- Label icon-only content with aria-label

Elements and CSS used

HTML elements	CSS features
figure, blockquote, p, figcaption, span	position: relative/absolute, ::before, content, opacity, font-style, grid

Build guide

1. Write one <figure> per review: blockquote with the text, figcaption with the name.
2. Add the stars in a span with an aria-label.
3. Grid the figures.
4. Set figure position: relative.
5. Add the big quotation mark with ::before positioned absolutely.
6. Colour the stars.

Project 303: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - Reviews</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What customers say about Pyramid Fitness</h1>
    <div class="quotes">
      <figure>
        <blockquote><p>The best class experience in 6th of October.</
p></blockquote>
        <figcaption>Heba M. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>Friendly staff and fair prices.</p></
blockquote>
        <figcaption>Ziad K. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>I recommend them to everyone.</p></blockquote>
        <figcaption>Rania S. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
    </div>
  </main>
</body>
</html>
```

Project 303: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.quotes { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(16rem, 1fr)); }
figure { margin: 0; padding: 1.5rem; background: var(--accent);
border-radius: 14px; position: relative; }
figure::before { content: "\201C"; position: absolute; top: -.2em;
```

```
left: .4rem; font-size: 5rem; color: var(--brand); opacity: .25; font-
family: Georgia, serif; }
blockquote { margin: 0 0 1rem; font-size: 1.1rem; font-style: italic;
}
figcaption { font-weight: 600; }
.stars { color: #f59e0b; margin-left: .5rem; }
```

Project 303 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - Reviews</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What customers say about Pyramid Fitness	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure>	Self-contained media with an optional caption.
<blockquote> The best class experience in 6th of October. </bl...	A paragraph of text.
<figcaption>Heba M. <span class="stars" aria-label="5 out of 5 star...	Caption for the figure.

Line	What it does
<blockquote> Friendly staff and fair prices. </blockquote>	A long quotation from another source.
<figcaption>Ziad K. <span class="stars" aria-label="5 out of 5 star...	Generic inline container for styling.
<figcaption>Rania S. <span class="stars" aria-label="5 out of 5 sta...	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 14px;	Rounds the corners.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "\201C";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
font-size: 5rem;	Size of the text.
opacity: .25;	Transparency from 0 (invisible) to 1 (solid).
font-weight: 600;	Thickness of the text.

Check your work

- Attribution is outside the blockquote
- Stars have a text alternative
- Quote mark does not overlap text badly
- Cards equal height

Exercises

1. Add photos of the customers.
2. Turn the section into a horizontal scroll-snap carousel.
3. Add schema.org Review microdata.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 304: Testimonials section for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 2 | Files: index.html, styles.css

Brief

Show three customer quotes as cards with a large decorative quotation mark, the customer's name and a star rating.

Learning goals

- Mark up quotes correctly with figure, blockquote and figcaption
- Position a decorative ::before
- Label icon-only content with aria-label

Elements and CSS used

HTML elements	CSS features
figure, blockquote, p, figcaption, span	position: relative/absolute, ::before, content, opacity, font-style, grid

Build guide

1. Write one <figure> per review: blockquote with the text, figcaption with the name.
2. Add the stars in a span with an aria-label.
3. Grid the figures.
4. Set figure position: relative.
5. Add the big quotation mark with ::before positioned absolutely.
6. Colour the stars.

Project 304: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - Reviews</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What customers say about Delta Dental Clinic</h1>
    <div class="quotes">
      <figure>
        <blockquote><p>The best service experience in Mansoura.</p></
blockquote>
        <figcaption>Heba M. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>Friendly staff and fair prices.</p></
blockquote>
        <figcaption>Ziad K. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>I recommend them to everyone.</p></blockquote>
        <figcaption>Rania S. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
    </div>
  </main>
</body>
</html>
```

Project 304: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.quotes { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(16rem, 1fr)); }
figure { margin: 0; padding: 1.5rem; background: var(--accent);
border-radius: 14px; position: relative; }
figure::before { content: "\201C"; position: absolute; top: -.2em;
```

```
left: .4rem; font-size: 5rem; color: var(--brand); opacity: .25; font-
family: Georgia, serif; }
blockquote { margin: 0 0 1rem; font-size: 1.1rem; font-style: italic;
}
figcaption { font-weight: 600; }
.stars { color: #f59e0b; margin-left: .5rem; }
```

Project 304 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - Reviews</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What customers say about Delta Dental Clinic	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure>	Self-contained media with an optional caption.
<blockquote> The best service experience in Mansoura. </blockq...	A paragraph of text.
<figcaption>Heba M. <span class="stars" aria-label="5 out of 5 star...	Caption for the figure.

Line	What it does
<blockquote> Friendly staff and fair prices. </blockquote>	A long quotation from another source.
<figcaption>Ziad K. <span class="stars" aria-label="5 out of 5 star...	Generic inline container for styling.
<figcaption>Rania S. <span class="stars" aria-label="5 out of 5 sta...	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 14px;	Rounds the corners.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "\201C";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
font-size: 5rem;	Size of the text.
opacity: .25;	Transparency from 0 (invisible) to 1 (solid).
font-weight: 600;	Thickness of the text.

Check your work

- Attribution is outside the blockquote
- Stars have a text alternative
- Quote mark does not overlap text badly
- Cards equal height

Exercises

1. Add photos of the customers.
2. Turn the section into a horizontal scroll-snap carousel.
3. Add schema.org Review microdata.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 305: Testimonials section for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 2 | Files: index.html, styles.css

Brief

Show three customer quotes as cards with a large decorative quotation mark, the customer's name and a star rating.

Learning goals

- Mark up quotes correctly with figure, blockquote and figcaption
- Position a decorative ::before
- Label icon-only content with aria-label

Elements and CSS used

HTML elements	CSS features
figure, blockquote, p, figcaption, span	position: relative/absolute, ::before, content, opacity, font-style, grid

Build guide

1. Write one <figure> per review: blockquote with the text, figcaption with the name.
2. Add the stars in a span with an aria-label.
3. Grid the figures.
4. Set figure position: relative.
5. Add the big quotation mark with ::before positioned absolutely.
6. Colour the stars.

Project 305: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - Reviews</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What customers say about Red Sea Travel</h1>
    <div class="quotes">
      <figure>
        <blockquote><p>The best tour experience in Hurghada.</p></
blockquote>
        <figcaption>Heba M. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>Friendly staff and fair prices.</p></
blockquote>
        <figcaption>Ziad K. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>I recommend them to everyone.</p></blockquote>
        <figcaption>Rania S. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
    </div>
  </main>
</body>
</html>
```

Project 305: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.quotes { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(16rem, 1fr)); }
figure { margin: 0; padding: 1.5rem; background: var(--accent);
border-radius: 14px; position: relative; }
figure::before { content: "\201C"; position: absolute; top: -.2em;
```

```
left: .4rem; font-size: 5rem; color: var(--brand); opacity: .25; font-
family: Georgia, serif; }
blockquote { margin: 0 0 1rem; font-size: 1.1rem; font-style: italic;
}
figcaption { font-weight: 600; }
.stars { color: #f59e0b; margin-left: .5rem; }
```

Project 305 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - Reviews</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What customers say about Red Sea Travel	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure>	Self-contained media with an optional caption.
<blockquote> The best tour experience in Hurghada. </blockquote>	A paragraph of text.
<figcaption>Heba M. <span class="stars" aria-label="5 out of 5 star...	Caption for the figure.

Line	What it does
<blockquote> Friendly staff and fair prices. </blockquote>	A long quotation from another source.
<figcaption>Ziad K. <span class="stars" aria-label="5 out of 5 star...	Generic inline container for styling.
<figcaption>Rania S. <span class="stars" aria-label="5 out of 5 sta...	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 14px;	Rounds the corners.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "\201C";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
font-size: 5rem;	Size of the text.
opacity: .25;	Transparency from 0 (invisible) to 1 (solid).
font-weight: 600;	Thickness of the text.

Check your work

- Attribution is outside the blockquote
- Stars have a text alternative
- Quote mark does not overlap text badly
- Cards equal height

Exercises

1. Add photos of the customers.
2. Turn the section into a horizontal scroll-snap carousel.
3. Add schema.org Review microdata.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 306: Testimonials section for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Show three customer quotes as cards with a large decorative quotation mark, the customer's name and a star rating.

Learning goals

- Mark up quotes correctly with figure, blockquote and figcaption
- Position a decorative ::before
- Label icon-only content with aria-label

Elements and CSS used

HTML elements	CSS features
figure, blockquote, p, figcaption, span	position: relative/absolute, ::before, content, opacity, font-style, grid

Build guide

1. Write one <figure> per review: blockquote with the text, figcaption with the name.
2. Add the stars in a span with an aria-label.
3. Grid the figures.
4. Set figure position: relative.
5. Add the big quotation mark with ::before positioned absolutely.

6. Colour the stars.

Project 306: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - Reviews</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What customers say about Lotus Language School</h1>
    <div class="quotes">
      <figure>
        <blockquote><p>The best course experience in Alexandria.</p></
blockquote>
        <figcaption>Heba M. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>Friendly staff and fair prices.</p></
blockquote>
        <figcaption>Ziad K. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>I recommend them to everyone.</p></blockquote>
        <figcaption>Rania S. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
    </div>
  </main>
</body>
</html>
```

Project 306: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.quotes { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(16rem, 1fr)); }
figure { margin: 0; padding: 1.5rem; background: var(--accent);
border-radius: 14px; position: relative; }
figure::before { content: "\201C"; position: absolute; top: -.2em;
```

```
left: .4rem; font-size: 5rem; color: var(--brand); opacity: .25; font-
family: Georgia, serif; }
blockquote { margin: 0 0 1rem; font-size: 1.1rem; font-style: italic;
}
figcaption { font-weight: 600; }
.stars { color: #f59e0b; margin-left: .5rem; }
```

Project 306 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - Reviews</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What customers say about Lotus Language School	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure>	Self-contained media with an optional caption.
<blockquote> The best course experience in Alexandria. </block...	A paragraph of text.
<figcaption>Heba M. <span class="stars" aria-label="5 out of 5 star...	Caption for the figure.

Line	What it does
<blockquote> Friendly staff and fair prices. </blockquote>	A long quotation from another source.
<figcaption>Ziad K. <span class="stars" aria-label="5 out of 5 star...	Generic inline container for styling.
<figcaption>Rania S. <span class="stars" aria-label="5 out of 5 sta...	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 14px;	Rounds the corners.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "\201C";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
font-size: 5rem;	Size of the text.
opacity: .25;	Transparency from 0 (invisible) to 1 (solid).
font-weight: 600;	Thickness of the text.

Check your work

- Attribution is outside the blockquote
- Stars have a text alternative
- Quote mark does not overlap text badly
- Cards equal height

Exercises

1. Add photos of the customers.
2. Turn the section into a horizontal scroll-snap carousel.
3. Add schema.org Review microdata.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 307: Testimonials section for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 2 | Files: index.html, styles.css

Brief

Show three customer quotes as cards with a large decorative quotation mark, the customer's name and a star rating.

Learning goals

- Mark up quotes correctly with figure, blockquote and figcaption
- Position a decorative ::before
- Label icon-only content with aria-label

Elements and CSS used

HTML elements	CSS features
figure, blockquote, p, figcaption, span	position: relative/absolute, ::before, content, opacity, font-style, grid

Build guide

1. Write one <figure> per review: blockquote with the text, figcaption with the name.
2. Add the stars in a span with an aria-label.
3. Grid the figures.
4. Set figure position: relative.
5. Add the big quotation mark with ::before positioned absolutely.
6. Colour the stars.

Project 307: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - Reviews</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What customers say about Green Leaf Cafe</h1>
    <div class="quotes">
      <figure>
        <blockquote><p>The best drink experience in Zamalek.</p></
blockquote>
        <figcaption>Heba M. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>Friendly staff and fair prices.</p></
blockquote>
        <figcaption>Ziad K. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>I recommend them to everyone.</p></blockquote>
        <figcaption>Rania S. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
    </div>
  </main>
</body>
</html>
```

Project 307: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.quotes { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(16rem, 1fr)); }
figure { margin: 0; padding: 1.5rem; background: var(--accent);
border-radius: 14px; position: relative; }
figure::before { content: "\201C"; position: absolute; top: -.2em;
```

```
left: .4rem; font-size: 5rem; color: var(--brand); opacity: .25; font-
family: Georgia, serif; }
blockquote { margin: 0 0 1rem; font-size: 1.1rem; font-style: italic;
}
figcaption { font-weight: 600; }
.stars { color: #f59e0b; margin-left: .5rem; }
```

Project 307 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - Reviews</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What customers say about Green Leaf Cafe	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure>	Self-contained media with an optional caption.
<blockquote> The best drink experience in Zamalek. </blockquote>	A paragraph of text.
<figcaption>Heba M. <span class="stars" aria-label="5 out of 5 star...	Caption for the figure.

Line	What it does
<blockquote> Friendly staff and fair prices. </blockquote>	A long quotation from another source.
<figcaption>Ziad K. <span class="stars" aria-label="5 out of 5 star...	Generic inline container for styling.
<figcaption>Rania S. <span class="stars" aria-label="5 out of 5 sta...	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 14px;	Rounds the corners.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "\201C";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
font-size: 5rem;	Size of the text.
opacity: .25;	Transparency from 0 (invisible) to 1 (solid).
font-weight: 600;	Thickness of the text.

Check your work

- Attribution is outside the blockquote
- Stars have a text alternative
- Quote mark does not overlap text badly
- Cards equal height

Exercises

1. Add photos of the customers.
2. Turn the section into a horizontal scroll-snap carousel.
3. Add schema.org Review microdata.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 308: Testimonials section for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 2 | Files: index.html, styles.css

Brief

Show three customer quotes as cards with a large decorative quotation mark, the customer's name and a star rating.

Learning goals

- Mark up quotes correctly with figure, blockquote and figcaption
- Position a decorative ::before
- Label icon-only content with aria-label

Elements and CSS used

HTML elements	CSS features
figure, blockquote, p, figcaption, span	position: relative/absolute, ::before, content, opacity, font-style, grid

Build guide

1. Write one <figure> per review: blockquote with the text, figcaption with the name.
2. Add the stars in a span with an aria-label.
3. Grid the figures.
4. Set figure position: relative.
5. Add the big quotation mark with ::before positioned absolutely.
6. Colour the stars.

Project 308: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - Reviews</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What customers say about Sinai Trekking Club</h1>
    <div class="quotes">
      <figure>
        <blockquote><p>The best hike experience in Saint Catherine.</
p></blockquote>
        <figcaption>Heba M. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>Friendly staff and fair prices.</p></
blockquote>
        <figcaption>Ziad K. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>I recommend them to everyone.</p></blockquote>
        <figcaption>Rania S. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
    </div>
  </main>
</body>
</html>
```

Project 308: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.quotes { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(16rem, 1fr)); }
figure { margin: 0; padding: 1.5rem; background: var(--accent);
border-radius: 14px; position: relative; }
figure::before { content: "\201C"; position: absolute; top: -.2em;
```

```
left: .4rem; font-size: 5rem; color: var(--brand); opacity: .25; font-
family: Georgia, serif; }
blockquote { margin: 0 0 1rem; font-size: 1.1rem; font-style: italic;
}
figcaption { font-weight: 600; }
.stars { color: #f59e0b; margin-left: .5rem; }
```

Project 308 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - Reviews</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What customers say about Sinai Trekking Club	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure>	Self-contained media with an optional caption.
<blockquote> The best hike experience in Saint Catherine. </bl...	A paragraph of text.
<figcaption>Heba M. <span class="stars" aria-label="5 out of 5 star...	Caption for the figure.

Line	What it does
<blockquote> Friendly staff and fair prices. </blockquote>	A long quotation from another source.
<figcaption>Ziad K. <span class="stars" aria-label="5 out of 5 star...	Generic inline container for styling.
<figcaption>Rania S. <span class="stars" aria-label="5 out of 5 sta...	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 14px;	Rounds the corners.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "\201C";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
font-size: 5rem;	Size of the text.
opacity: .25;	Transparency from 0 (invisible) to 1 (solid).
font-weight: 600;	Thickness of the text.

Check your work

- Attribution is outside the blockquote
- Stars have a text alternative
- Quote mark does not overlap text badly
- Cards equal height

Exercises

1. Add photos of the customers.
2. Turn the section into a horizontal scroll-snap carousel.
3. Add schema.org Review microdata.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 309: Testimonials section for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 2 | Files: index.html, styles.css

Brief

Show three customer quotes as cards with a large decorative quotation mark, the customer's name and a star rating.

Learning goals

- Mark up quotes correctly with figure, blockquote and figcaption
- Position a decorative ::before
- Label icon-only content with aria-label

Elements and CSS used

HTML elements	CSS features
figure, blockquote, p, figcaption, span	position: relative/absolute, ::before, content, opacity, font-style, grid

Build guide

1. Write one <figure> per review: blockquote with the text, figcaption with the name.
2. Add the stars in a span with an aria-label.
3. Grid the figures.
4. Set figure position: relative.
5. Add the big quotation mark with ::before positioned absolutely.
6. Colour the stars.

Project 309: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - Reviews</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What customers say about Horizon Photography</h1>
    <div class="quotes">
      <figure>
        <blockquote><p>The best session experience in Maadi.</p></
blockquote>
        <figcaption>Heba M. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>Friendly staff and fair prices.</p></
blockquote>
        <figcaption>Ziad K. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>I recommend them to everyone.</p></blockquote>
        <figcaption>Rania S. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
    </div>
  </main>
</body>
</html>
```

Project 309: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.quotes { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(16rem, 1fr)); }
figure { margin: 0; padding: 1.5rem; background: var(--accent);
border-radius: 14px; position: relative; }
figure::before { content: "\201C"; position: absolute; top: -.2em;
```

```
left: .4rem; font-size: 5rem; color: var(--brand); opacity: .25; font-
family: Georgia, serif; }
blockquote { margin: 0 0 1rem; font-size: 1.1rem; font-style: italic;
}
figcaption { font-weight: 600; }
.stars { color: #f59e0b; margin-left: .5rem; }
```

Project 309 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - Reviews</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What customers say about Horizon Photography	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure>	Self-contained media with an optional caption.
<blockquote> The best session experience in Maadi. </blockquote>	A paragraph of text.
<figcaption>Heba M. <span class="stars" aria-label="5 out of 5 star...	Caption for the figure.

Line	What it does
<blockquote> Friendly staff and fair prices. </blockquote>	A long quotation from another source.
<figcaption>Ziad K. <span class="stars" aria-label="5 out of 5 star...	Generic inline container for styling.
<figcaption>Rania S. <span class="stars" aria-label="5 out of 5 sta...	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 14px;	Rounds the corners.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "\201C";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
font-size: 5rem;	Size of the text.
opacity: .25;	Transparency from 0 (invisible) to 1 (solid).
font-weight: 600;	Thickness of the text.

Check your work

- Attribution is outside the blockquote
- Stars have a text alternative
- Quote mark does not overlap text badly
- Cards equal height

Exercises

1. Add photos of the customers.
2. Turn the section into a horizontal scroll-snap carousel.
3. Add schema.org Review microdata.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 310: Testimonials section for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 2 | Files: index.html, styles.css

Brief

Show three customer quotes as cards with a large decorative quotation mark, the customer's name and a star rating.

Learning goals

- Mark up quotes correctly with figure, blockquote and figcaption
- Position a decorative ::before
- Label icon-only content with aria-label

Elements and CSS used

HTML elements	CSS features
figure, blockquote, p, figcaption, span	position: relative/absolute, ::before, content, opacity, font-style, grid

Build guide

1. Write one <figure> per review: blockquote with the text, figcaption with the name.
2. Add the stars in a span with an aria-label.
3. Grid the figures.
4. Set figure position: relative.
5. Add the big quotation mark with ::before positioned absolutely.
6. Colour the stars.

Project 310: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - Reviews</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What customers say about Papyrus Stationery</h1>
    <div class="quotes">
      <figure>
        <blockquote><p>The best product experience in Heliopolis.</
p></blockquote>
        <figcaption>Heba M. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>Friendly staff and fair prices.</p></
blockquote>
        <figcaption>Ziad K. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>I recommend them to everyone.</p></blockquote>
        <figcaption>Rania S. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
    </div>
  </main>
</body>
</html>
```

Project 310: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.quotes { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(16rem, 1fr)); }
figure { margin: 0; padding: 1.5rem; background: var(--accent);
border-radius: 14px; position: relative; }
figure::before { content: "\201C"; position: absolute; top: -.2em;
```

```
left: .4rem; font-size: 5rem; color: var(--brand); opacity: .25; font-
family: Georgia, serif; }
blockquote { margin: 0 0 1rem; font-size: 1.1rem; font-style: italic;
}
figcaption { font-weight: 600; }
.stars { color: #f59e0b; margin-left: .5rem; }
```

Project 310 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - Reviews</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What customers say about Papyrus Stationery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure>	Self-contained media with an optional caption.
<blockquote> The best product experience in Heliopolis. </bloc...	A paragraph of text.
<figcaption>Heba M. <span class="stars" aria-label="5 out of 5 star...	Caption for the figure.

Line	What it does
<blockquote> Friendly staff and fair prices. </blockquote>	A long quotation from another source.
<figcaption>Ziad K. <span class="stars" aria-label="5 out of 5 star...	Generic inline container for styling.
<figcaption>Rania S. <span class="stars" aria-label="5 out of 5 sta...	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 14px;	Rounds the corners.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "\201C";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
font-size: 5rem;	Size of the text.
opacity: .25;	Transparency from 0 (invisible) to 1 (solid).
font-weight: 600;	Thickness of the text.

Check your work

- Attribution is outside the blockquote
- Stars have a text alternative
- Quote mark does not overlap text badly
- Cards equal height

Exercises

1. Add photos of the customers.
2. Turn the section into a horizontal scroll-snap carousel.
3. Add schema.org Review microdata.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 311: Testimonials section for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 2 | Files: index.html, styles.css

Brief

Show three customer quotes as cards with a large decorative quotation mark, the customer's name and a star rating.

Learning goals

- Mark up quotes correctly with figure, blockquote and figcaption
- Position a decorative ::before
- Label icon-only content with aria-label

Elements and CSS used

HTML elements	CSS features
figure, blockquote, p, figcaption, span	position: relative/absolute, ::before, content, opacity, font-style, grid

Build guide

1. Write one <figure> per review: blockquote with the text, figcaption with the name.
2. Add the stars in a span with an aria-label.
3. Grid the figures.
4. Set figure position: relative.
5. Add the big quotation mark with ::before positioned absolutely.
6. Colour the stars.

Project 311: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - Reviews</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What customers say about Oasis Plant Nursery</h1>
    <div class="quotes">
      <figure>
        <blockquote><p>The best plant experience in Sheikh Zayed.</
p></blockquote>
        <figcaption>Heba M. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>Friendly staff and fair prices.</p></
blockquote>
        <figcaption>Ziad K. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>I recommend them to everyone.</p></blockquote>
        <figcaption>Rania S. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
    </div>
  </main>
</body>
</html>
```

Project 311: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.quotes { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(16rem, 1fr)); }
figure { margin: 0; padding: 1.5rem; background: var(--accent);
border-radius: 14px; position: relative; }
figure::before { content: "\201C"; position: absolute; top: -.2em;
```

```
left: .4rem; font-size: 5rem; color: var(--brand); opacity: .25; font-
family: Georgia, serif; }
blockquote { margin: 0 0 1rem; font-size: 1.1rem; font-style: italic;
}
figcaption { font-weight: 600; }
.stars { color: #f59e0b; margin-left: .5rem; }
```

Project 311 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - Reviews</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What customers say about Oasis Plant Nursery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure>	Self-contained media with an optional caption.
<blockquote> The best plant experience in Sheikh Zayed. </bloc...	A paragraph of text.
<figcaption>Heba M. <span class="stars" aria-label="5 out of 5 star...	Caption for the figure.

Line	What it does
<blockquote> Friendly staff and fair prices. </blockquote>	A long quotation from another source.
<figcaption>Ziad K. <span class="stars" aria-label="5 out of 5 star...	Generic inline container for styling.
<figcaption>Rania S. <span class="stars" aria-label="5 out of 5 sta...	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 14px;	Rounds the corners.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "\201C";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
font-size: 5rem;	Size of the text.
opacity: .25;	Transparency from 0 (invisible) to 1 (solid).
font-weight: 600;	Thickness of the text.

Check your work

- Attribution is outside the blockquote
- Stars have a text alternative
- Quote mark does not overlap text badly
- Cards equal height

Exercises

1. Add photos of the customers.
2. Turn the section into a horizontal scroll-snap carousel.
3. Add schema.org Review microdata.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 312: Testimonials section for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 2 | Files: index.html, styles.css

Brief

Show three customer quotes as cards with a large decorative quotation mark, the customer's name and a star rating.

Learning goals

- Mark up quotes correctly with figure, blockquote and figcaption
- Position a decorative ::before
- Label icon-only content with aria-label

Elements and CSS used

HTML elements	CSS features
figure, blockquote, p, figcaption, span	position: relative/absolute, ::before, content, opacity, font-style, grid

Build guide

1. Write one <figure> per review: blockquote with the text, figcaption with the name.
2. Add the stars in a span with an aria-label.
3. Grid the figures.
4. Set figure position: relative.
5. Add the big quotation mark with ::before positioned absolutely.
6. Colour the stars.

Project 312: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - Reviews</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What customers say about Cedar Furniture</h1>
    <div class="quotes">
      <figure>
        <blockquote><p>The best piece experience in Damietta.</p></
blockquote>
        <figcaption>Heba M. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>Friendly staff and fair prices.</p></
blockquote>
        <figcaption>Ziad K. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>I recommend them to everyone.</p></blockquote>
        <figcaption>Rania S. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
    </div>
  </main>
</body>
</html>
```

Project 312: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.quotes { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(16rem, 1fr)); }
figure { margin: 0; padding: 1.5rem; background: var(--accent);
border-radius: 14px; position: relative; }
figure::before { content: "\201C"; position: absolute; top: -.2em;
```

```
left: .4rem; font-size: 5rem; color: var(--brand); opacity: .25; font-
family: Georgia, serif; }
blockquote { margin: 0 0 1rem; font-size: 1.1rem; font-style: italic;
}
figcaption { font-weight: 600; }
.stars { color: #f59e0b; margin-left: .5rem; }
```

Project 312 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - Reviews</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What customers say about Cedar Furniture	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure>	Self-contained media with an optional caption.
<blockquote> The best piece experience in Damietta. </blockquote>	A paragraph of text.
<figcaption>Heba M. <span class="stars" aria-label="5 out of 5 star...	Caption for the figure.

Line	What it does
<blockquote> Friendly staff and fair prices. </blockquote>	A long quotation from another source.
<figcaption>Ziad K. <span class="stars" aria-label="5 out of 5 star...	Generic inline container for styling.
<figcaption>Rania S. <span class="stars" aria-label="5 out of 5 sta...	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 14px;	Rounds the corners.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "\201C";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
font-size: 5rem;	Size of the text.
opacity: .25;	Transparency from 0 (invisible) to 1 (solid).
font-weight: 600;	Thickness of the text.

Check your work

- Attribution is outside the blockquote
- Stars have a text alternative
- Quote mark does not overlap text badly
- Cards equal height

Exercises

1. Add photos of the customers.
2. Turn the section into a horizontal scroll-snap carousel.
3. Add schema.org Review microdata.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 313: Testimonials section for Byte Repair

Theme: Byte Repair (Nasr City) | Level 2 | Files: index.html, styles.css

Brief

Show three customer quotes as cards with a large decorative quotation mark, the customer's name and a star rating.

Learning goals

- Mark up quotes correctly with figure, blockquote and figcaption
- Position a decorative ::before
- Label icon-only content with aria-label

Elements and CSS used

HTML elements	CSS features
figure, blockquote, p, figcaption, span	position: relative/absolute, ::before, content, opacity, font-style, grid

Build guide

1. Write one <figure> per review: blockquote with the text, figcaption with the name.
2. Add the stars in a span with an aria-label.
3. Grid the figures.
4. Set figure position: relative.
5. Add the big quotation mark with ::before positioned absolutely.
6. Colour the stars.

Project 313: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - Reviews</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What customers say about Byte Repair</h1>
    <div class="quotes">
      <figure>
        <blockquote><p>The best repair experience in Nasr City.</p></
blockquote>
        <figcaption>Heba M. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>Friendly staff and fair prices.</p></
blockquote>
        <figcaption>Ziad K. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>I recommend them to everyone.</p></blockquote>
        <figcaption>Rania S. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
    </div>
  </main>
</body>
</html>
```

Project 313: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.quotes { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(16rem, 1fr)); }
figure { margin: 0; padding: 1.5rem; background: var(--accent);
border-radius: 14px; position: relative; }
figure::before { content: "\201C"; position: absolute; top: -.2em;
```

```
left: .4rem; font-size: 5rem; color: var(--brand); opacity: .25; font-
family: Georgia, serif; }
blockquote { margin: 0 0 1rem; font-size: 1.1rem; font-style: italic;
}
figcaption { font-weight: 600; }
.stars { color: #f59e0b; margin-left: .5rem; }
```

Project 313 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - Reviews</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What customers say about Byte Repair	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure>	Self-contained media with an optional caption.
<blockquote> The best repair experience in Nasr City. </blockq...	A paragraph of text.
<figcaption>Heba M. <span class="stars" aria-label="5 out of 5 star...	Caption for the figure.

Line	What it does
<blockquote> Friendly staff and fair prices. </blockquote>	A long quotation from another source.
<figcaption>Ziad K. <span class="stars" aria-label="5 out of 5 star...	Generic inline container for styling.
<figcaption>Rania S. <span class="stars" aria-label="5 out of 5 sta...	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 14px;	Rounds the corners.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "\201C";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
font-size: 5rem;	Size of the text.
opacity: .25;	Transparency from 0 (invisible) to 1 (solid).
font-weight: 600;	Thickness of the text.

Check your work

- Attribution is outside the blockquote
- Stars have a text alternative
- Quote mark does not overlap text badly
- Cards equal height

Exercises

1. Add photos of the customers.
2. Turn the section into a horizontal scroll-snap carousel.
3. Add schema.org Review microdata.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 314: Testimonials section for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 2 | Files: index.html, styles.css

Brief

Show three customer quotes as cards with a large decorative quotation mark, the customer's name and a star rating.

Learning goals

- Mark up quotes correctly with figure, blockquote and figcaption
- Position a decorative ::before
- Label icon-only content with aria-label

Elements and CSS used

HTML elements	CSS features
figure, blockquote, p, figcaption, span	position: relative/absolute, ::before, content, opacity, font-style, grid

Build guide

1. Write one <figure> per review: blockquote with the text, figcaption with the name.
2. Add the stars in a span with an aria-label.
3. Grid the figures.
4. Set figure position: relative.
5. Add the big quotation mark with ::before positioned absolutely.
6. Colour the stars.

Project 314: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - Reviews</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What customers say about Sahara Pet Care</h1>
    <div class="quotes">
      <figure>
        <blockquote><p>The best service experience in New Cairo.</p></
blockquote>
        <figcaption>Heba M. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>Friendly staff and fair prices.</p></
blockquote>
        <figcaption>Ziad K. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>I recommend them to everyone.</p></blockquote>
        <figcaption>Rania S. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
    </div>
  </main>
</body>
</html>
```

Project 314: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.quotes { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(16rem, 1fr)); }
figure { margin: 0; padding: 1.5rem; background: var(--accent);
border-radius: 14px; position: relative; }
figure::before { content: "\201C"; position: absolute; top: -.2em;
```

```
left: .4rem; font-size: 5rem; color: var(--brand); opacity: .25; font-
family: Georgia, serif; }
blockquote { margin: 0 0 1rem; font-size: 1.1rem; font-style: italic;
}
figcaption { font-weight: 600; }
.stars { color: #f59e0b; margin-left: .5rem; }
```

Project 314 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - Reviews</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What customers say about Sahara Pet Care	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure>	Self-contained media with an optional caption.
<blockquote> The best service experience in New Cairo. </block...	A paragraph of text.
<figcaption>Heba M. <span class="stars" aria-label="5 out of 5 star...	Caption for the figure.

Line	What it does
<blockquote> Friendly staff and fair prices. </blockquote>	A long quotation from another source.
<figcaption>Ziad K. <span class="stars" aria-label="5 out of 5 star...	Generic inline container for styling.
<figcaption>Rania S. <span class="stars" aria-label="5 out of 5 sta...	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 14px;	Rounds the corners.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "\201C";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
font-size: 5rem;	Size of the text.
opacity: .25;	Transparency from 0 (invisible) to 1 (solid).
font-weight: 600;	Thickness of the text.

Check your work

- Attribution is outside the blockquote
- Stars have a text alternative
- Quote mark does not overlap text badly
- Cards equal height

Exercises

1. Add photos of the customers.
2. Turn the section into a horizontal scroll-snap carousel.
3. Add schema.org Review microdata.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 315: Testimonials section for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Show three customer quotes as cards with a large decorative quotation mark, the customer's name and a star rating.

Learning goals

- Mark up quotes correctly with figure, blockquote and figcaption
- Position a decorative ::before
- Label icon-only content with aria-label

Elements and CSS used

HTML elements	CSS features
figure, blockquote, p, figcaption, span	position: relative/absolute, ::before, content, opacity, font-style, grid

Build guide

1. Write one <figure> per review: blockquote with the text, figcaption with the name.
2. Add the stars in a span with an aria-label.
3. Grid the figures.
4. Set figure position: relative.
5. Add the big quotation mark with ::before positioned absolutely.

6. Colour the stars.

Project 315: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - Reviews</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What customers say about Alexandria Sailing School</h1>
    <div class="quotes">
      <figure>
        <blockquote><p>The best lesson experience in Alexandria.</p></
blockquote>
        <figcaption>Heba M. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>Friendly staff and fair prices.</p></
blockquote>
        <figcaption>Ziad K. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>I recommend them to everyone.</p></blockquote>
        <figcaption>Rania S. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
    </div>
  </main>
</body>
</html>
```

Project 315: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.quotes { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(16rem, 1fr)); }
figure { margin: 0; padding: 1.5rem; background: var(--accent);
border-radius: 14px; position: relative; }
figure::before { content: "\201C"; position: absolute; top: -.2em;
```

```
left: .4rem; font-size: 5rem; color: var(--brand); opacity: .25; font-
family: Georgia, serif; }
blockquote { margin: 0 0 1rem; font-size: 1.1rem; font-style: italic;
}
figcaption { font-weight: 600; }
.stars { color: #f59e0b; margin-left: .5rem; }
```

Project 315 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - Reviews</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What customers say about Alexandria Sailing School	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure>	Self-contained media with an optional caption.
<blockquote> The best lesson experience in Alexandria. </block...	A paragraph of text.
<figcaption>Heba M. <span class="stars" aria-label="5 out of 5 star...	Caption for the figure.

Line	What it does
<blockquote> Friendly staff and fair prices. </blockquote>	A long quotation from another source.
<figcaption>Ziad K. <span class="stars" aria-label="5 out of 5 star...	Generic inline container for styling.
<figcaption>Rania S. <span class="stars" aria-label="5 out of 5 sta...	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 14px;	Rounds the corners.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "\201C";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
font-size: 5rem;	Size of the text.
opacity: .25;	Transparency from 0 (invisible) to 1 (solid).
font-weight: 600;	Thickness of the text.

Check your work

- Attribution is outside the blockquote
- Stars have a text alternative
- Quote mark does not overlap text badly
- Cards equal height

Exercises

1. Add photos of the customers.
2. Turn the section into a horizontal scroll-snap carousel.
3. Add schema.org Review microdata.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 316: Testimonials section for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Show three customer quotes as cards with a large decorative quotation mark, the customer's name and a star rating.

Learning goals

- Mark up quotes correctly with figure, blockquote and figcaption
- Position a decorative ::before
- Label icon-only content with aria-label

Elements and CSS used

HTML elements	CSS features
figure, blockquote, p, figcaption, span	position: relative/absolute, ::before, content, opacity, font-style, grid

Build guide

1. Write one <figure> per review: blockquote with the text, figcaption with the name.
2. Add the stars in a span with an aria-label.
3. Grid the figures.
4. Set figure position: relative.
5. Add the big quotation mark with ::before positioned absolutely.

6. Colour the stars.

Project 316: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - Reviews</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What customers say about Habiba Handmade Jewellery</h1>
    <div class="quotes">
      <figure>
        <blockquote><p>The best item experience in Aswan.</p></
blockquote>
        <figcaption>Heba M. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>Friendly staff and fair prices.</p></
blockquote>
        <figcaption>Ziad K. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>I recommend them to everyone.</p></blockquote>
        <figcaption>Rania S. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
    </div>
  </main>
</body>
</html>
```

Project 316: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.quotes { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(16rem, 1fr)); }
figure { margin: 0; padding: 1.5rem; background: var(--accent);
border-radius: 14px; position: relative; }
figure::before { content: "\201C"; position: absolute; top: -.2em;
```

```
left: .4rem; font-size: 5rem; color: var(--brand); opacity: .25; font-
family: Georgia, serif; }
blockquote { margin: 0 0 1rem; font-size: 1.1rem; font-style: italic;
}
figcaption { font-weight: 600; }
.stars { color: #f59e0b; margin-left: .5rem; }
```

Project 316 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - Reviews</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What customers say about Habiba Handmade Jewellery	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure>	Self-contained media with an optional caption.
<blockquote> The best item experience in Aswan. </blockquote>	A paragraph of text.
<figcaption>Heba M. <span class="stars" aria-label="5 out of 5 star...	Caption for the figure.

Line	What it does
<blockquote> Friendly staff and fair prices. </blockquote>	A long quotation from another source.
<figcaption>Ziad K. <span class="stars" aria-label="5 out of 5 star...	Generic inline container for styling.
<figcaption>Rania S. <span class="stars" aria-label="5 out of 5 sta...	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 14px;	Rounds the corners.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "\201C";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
font-size: 5rem;	Size of the text.
opacity: .25;	Transparency from 0 (invisible) to 1 (solid).
font-weight: 600;	Thickness of the text.

Check your work

- Attribution is outside the blockquote
- Stars have a text alternative
- Quote mark does not overlap text badly
- Cards equal height

Exercises

1. Add photos of the customers.
2. Turn the section into a horizontal scroll-snap carousel.
3. Add schema.org Review microdata.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 317: Testimonials section for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 2 | Files: index.html, styles.css

Brief

Show three customer quotes as cards with a large decorative quotation mark, the customer's name and a star rating.

Learning goals

- Mark up quotes correctly with figure, blockquote and figcaption
- Position a decorative ::before
- Label icon-only content with aria-label

Elements and CSS used

HTML elements	CSS features
figure, blockquote, p, figcaption, span	position: relative/absolute, ::before, content, opacity, font-style, grid

Build guide

1. Write one <figure> per review: blockquote with the text, figcaption with the name.
2. Add the stars in a span with an aria-label.
3. Grid the figures.
4. Set figure position: relative.
5. Add the big quotation mark with ::before positioned absolutely.

6. Colour the stars.

Project 317: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - Reviews</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What customers say about Fayoum Pottery Studio</h1>
    <div class="quotes">
      <figure>
        <blockquote><p>The best workshop experience in Tunis Village.
</p></blockquote>
        <figcaption>Heba M. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>Friendly staff and fair prices.</p></
blockquote>
        <figcaption>Ziad K. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>I recommend them to everyone.</p></blockquote>
        <figcaption>Rania S. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
    </div>
  </main>
</body>
</html>
```

Project 317: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.quotes { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(16rem, 1fr)); }
figure { margin: 0; padding: 1.5rem; background: var(--accent);
border-radius: 14px; position: relative; }
figure::before { content: "\201C"; position: absolute; top: -.2em;
```

```
left: .4rem; font-size: 5rem; color: var(--brand); opacity: .25; font-
family: Georgia, serif; }
blockquote { margin: 0 0 1rem; font-size: 1.1rem; font-style: italic;
}
figcaption { font-weight: 600; }
.stars { color: #f59e0b; margin-left: .5rem; }
```

Project 317 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - Reviews</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What customers say about Fayoum Pottery Studio	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure>	Self-contained media with an optional caption.
<blockquote> The best workshop experience in Tunis Village. </...	A paragraph of text.
<figcaption>Heba M. <span class="stars" aria-label="5 out of 5 star...	Caption for the figure.

Line	What it does
<blockquote> Friendly staff and fair prices. </blockquote>	A long quotation from another source.
<figcaption>Ziad K. <span class="stars" aria-label="5 out of 5 star...	Generic inline container for styling.
<figcaption>Rania S. <span class="stars" aria-label="5 out of 5 sta...	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 14px;	Rounds the corners.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "\201C";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
font-size: 5rem;	Size of the text.
opacity: .25;	Transparency from 0 (invisible) to 1 (solid).
font-weight: 600;	Thickness of the text.

Check your work

- Attribution is outside the blockquote
- Stars have a text alternative
- Quote mark does not overlap text badly
- Cards equal height

Exercises

1. Add photos of the customers.
2. Turn the section into a horizontal scroll-snap carousel.
3. Add schema.org Review microdata.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 318: Testimonials section for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 2 | Files: index.html, styles.css

Brief

Show three customer quotes as cards with a large decorative quotation mark, the customer's name and a star rating.

Learning goals

- Mark up quotes correctly with figure, blockquote and figcaption
- Position a decorative ::before
- Label icon-only content with aria-label

Elements and CSS used

HTML elements	CSS features
figure, blockquote, p, figcaption, span	position: relative/absolute, ::before, content, opacity, font-style, grid

Build guide

1. Write one <figure> per review: blockquote with the text, figcaption with the name.
2. Add the stars in a span with an aria-label.
3. Grid the figures.
4. Set figure position: relative.
5. Add the big quotation mark with ::before positioned absolutely.

6. Colour the stars.

Project 318: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - Reviews</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What customers say about Cleopatra Beauty Salon</h1>
    <div class="quotes">
      <figure>
        <blockquote><p>The best treatment experience in Dokki.</p></
blockquote>
        <figcaption>Heba M. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>Friendly staff and fair prices.</p></
blockquote>
        <figcaption>Ziad K. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>I recommend them to everyone.</p></blockquote>
        <figcaption>Rania S. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
    </div>
  </main>
</body>
</html>
```

Project 318: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.quotes { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(16rem, 1fr)); }
figure { margin: 0; padding: 1.5rem; background: var(--accent);
border-radius: 14px; position: relative; }
figure::before { content: "\201C"; position: absolute; top: -.2em;
```

```
left: .4rem; font-size: 5rem; color: var(--brand); opacity: .25; font-
family: Georgia, serif; }
blockquote { margin: 0 0 1rem; font-size: 1.1rem; font-style: italic;
}
figcaption { font-weight: 600; }
.stars { color: #f59e0b; margin-left: .5rem; }
```

Project 318 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - Reviews</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What customers say about Cleopatra Beauty Salon	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure>	Self-contained media with an optional caption.
<blockquote> The best treatment experience in Dokki. </blockqu...	A paragraph of text.
<figcaption>Heba M. <span class="stars" aria-label="5 out of 5 star...	Caption for the figure.

Line	What it does
<blockquote> Friendly staff and fair prices. </blockquote>	A long quotation from another source.
<figcaption>Ziad K. <span class="stars" aria-label="5 out of 5 star...	Generic inline container for styling.
<figcaption>Rania S. <span class="stars" aria-label="5 out of 5 sta...	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 14px;	Rounds the corners.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "\201C";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
font-size: 5rem;	Size of the text.
opacity: .25;	Transparency from 0 (invisible) to 1 (solid).
font-weight: 600;	Thickness of the text.

Check your work

- Attribution is outside the blockquote
- Stars have a text alternative
- Quote mark does not overlap text badly
- Cards equal height

Exercises

1. Add photos of the customers.
2. Turn the section into a horizontal scroll-snap carousel.
3. Add schema.org Review microdata.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 319: Testimonials section for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 2 | Files: index.html, styles.css

Brief

Show three customer quotes as cards with a large decorative quotation mark, the customer's name and a star rating.

Learning goals

- Mark up quotes correctly with figure, blockquote and figcaption
- Position a decorative ::before
- Label icon-only content with aria-label

Elements and CSS used

HTML elements	CSS features
figure, blockquote, p, figcaption, span	position: relative/absolute, ::before, content, opacity, font-style, grid

Build guide

1. Write one <figure> per review: blockquote with the text, figcaption with the name.
2. Add the stars in a span with an aria-label.
3. Grid the figures.
4. Set figure position: relative.
5. Add the big quotation mark with ::before positioned absolutely.
6. Colour the stars.

Project 319: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - Reviews</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What customers say about Suez Auto Service</h1>
    <div class="quotes">
      <figure>
        <blockquote><p>The best service experience in Suez.</p></
blockquote>
        <figcaption>Heba M. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>Friendly staff and fair prices.</p></
blockquote>
        <figcaption>Ziad K. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>I recommend them to everyone.</p></blockquote>
        <figcaption>Rania S. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
    </div>
  </main>
</body>
</html>
```

Project 319: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.quotes { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(16rem, 1fr)); }
figure { margin: 0; padding: 1.5rem; background: var(--accent);
border-radius: 14px; position: relative; }
figure::before { content: "\201C"; position: absolute; top: -.2em;
```

```
left: .4rem; font-size: 5rem; color: var(--brand); opacity: .25; font-
family: Georgia, serif; }
blockquote { margin: 0 0 1rem; font-size: 1.1rem; font-style: italic;
}
figcaption { font-weight: 600; }
.stars { color: #f59e0b; margin-left: .5rem; }
```

Project 319 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - Reviews</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What customers say about Suez Auto Service	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure>	Self-contained media with an optional caption.
<blockquote> The best service experience in Suez. </blockquote>	A paragraph of text.
<figcaption>Heba M. <span class="stars" aria-label="5 out of 5 star...	Caption for the figure.

Line	What it does
<blockquote> Friendly staff and fair prices. </blockquote>	A long quotation from another source.
<figcaption>Ziad K. <span class="stars" aria-label="5 out of 5 star...	Generic inline container for styling.
<figcaption>Rania S. <span class="stars" aria-label="5 out of 5 sta...	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 14px;	Rounds the corners.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "\201C";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
font-size: 5rem;	Size of the text.
opacity: .25;	Transparency from 0 (invisible) to 1 (solid).
font-weight: 600;	Thickness of the text.

Check your work

- Attribution is outside the blockquote
- Stars have a text alternative
- Quote mark does not overlap text badly
- Cards equal height

Exercises

1. Add photos of the customers.
2. Turn the section into a horizontal scroll-snap carousel.
3. Add schema.org Review microdata.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 320: Testimonials section for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 2 | Files: index.html, styles.css

Brief

Show three customer quotes as cards with a large decorative quotation mark, the customer's name and a star rating.

Learning goals

- Mark up quotes correctly with figure, blockquote and figcaption
- Position a decorative ::before
- Label icon-only content with aria-label

Elements and CSS used

HTML elements	CSS features
figure, blockquote, p, figcaption, span	position: relative/absolute, ::before, content, opacity, font-style, grid

Build guide

1. Write one <figure> per review: blockquote with the text, figcaption with the name.
2. Add the stars in a span with an aria-label.
3. Grid the figures.
4. Set figure position: relative.
5. Add the big quotation mark with ::before positioned absolutely.
6. Colour the stars.

Project 320: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - Reviews</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What customers say about Luxor Music Academy</h1>
    <div class="quotes">
      <figure>
        <blockquote><p>The best course experience in Luxor.</p></
blockquote>
        <figcaption>Heba M. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>Friendly staff and fair prices.</p></
blockquote>
        <figcaption>Ziad K. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>I recommend them to everyone.</p></blockquote>
        <figcaption>Rania S. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
    </div>
  </main>
</body>
</html>
```

Project 320: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.quotes { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(16rem, 1fr)); }
figure { margin: 0; padding: 1.5rem; background: var(--accent);
border-radius: 14px; position: relative; }
figure::before { content: "\201C"; position: absolute; top: -.2em;
```

```
left: .4rem; font-size: 5rem; color: var(--brand); opacity: .25; font-
family: Georgia, serif; }
blockquote { margin: 0 0 1rem; font-size: 1.1rem; font-style: italic;
}
figcaption { font-weight: 600; }
.stars { color: #f59e0b; margin-left: .5rem; }
```

Project 320 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - Reviews</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What customers say about Luxor Music Academy	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure>	Self-contained media with an optional caption.
<blockquote> The best course experience in Luxor. </blockquote>	A paragraph of text.
<figcaption>Heba M. <span class="stars" aria-label="5 out of 5 star...	Caption for the figure.

Line	What it does
<blockquote> Friendly staff and fair prices. </blockquote>	A long quotation from another source.
<figcaption>Ziad K. <span class="stars" aria-label="5 out of 5 star...	Generic inline container for styling.
<figcaption>Rania S. <span class="stars" aria-label="5 out of 5 sta...	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 14px;	Rounds the corners.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "\201C";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
font-size: 5rem;	Size of the text.
opacity: .25;	Transparency from 0 (invisible) to 1 (solid).
font-weight: 600;	Thickness of the text.

Check your work

- Attribution is outside the blockquote
- Stars have a text alternative
- Quote mark does not overlap text badly
- Cards equal height

Exercises

1. Add photos of the customers.
2. Turn the section into a horizontal scroll-snap carousel.
3. Add schema.org Review microdata.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 321: Testimonials section for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 2 | Files: index.html, styles.css

Brief

Show three customer quotes as cards with a large decorative quotation mark, the customer's name and a star rating.

Learning goals

- Mark up quotes correctly with figure, blockquote and figcaption
- Position a decorative ::before
- Label icon-only content with aria-label

Elements and CSS used

HTML elements	CSS features
figure, blockquote, p, figcaption, span	position: relative/absolute, ::before, content, opacity, font-style, grid

Build guide

1. Write one <figure> per review: blockquote with the text, figcaption with the name.
2. Add the stars in a span with an aria-label.
3. Grid the figures.
4. Set figure position: relative.
5. Add the big quotation mark with ::before positioned absolutely.
6. Colour the stars.

Project 321: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - Reviews</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What customers say about Port Said Seafood</h1>
    <div class="quotes">
      <figure>
        <blockquote><p>The best dish experience in Port Said.</p></
blockquote>
        <figcaption>Heba M. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>Friendly staff and fair prices.</p></
blockquote>
        <figcaption>Ziad K. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>I recommend them to everyone.</p></blockquote>
        <figcaption>Rania S. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
    </div>
  </main>
</body>
</html>
```

Project 321: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.quotes { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(16rem, 1fr)); }
figure { margin: 0; padding: 1.5rem; background: var(--accent);
border-radius: 14px; position: relative; }
figure::before { content: "\201C"; position: absolute; top: -.2em;
```

```
left: .4rem; font-size: 5rem; color: var(--brand); opacity: .25; font-
family: Georgia, serif; }
blockquote { margin: 0 0 1rem; font-size: 1.1rem; font-style: italic;
}
figcaption { font-weight: 600; }
.stars { color: #f59e0b; margin-left: .5rem; }
```

Project 321 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - Reviews</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What customers say about Port Said Seafood	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure>	Self-contained media with an optional caption.
<blockquote> The best dish experience in Port Said. </blockquote>	A paragraph of text.
<figcaption>Heba M. <span class="stars" aria-label="5 out of 5 star...	Caption for the figure.

Line	What it does
<blockquote> Friendly staff and fair prices. </blockquote>	A long quotation from another source.
<figcaption>Ziad K. <span class="stars" aria-label="5 out of 5 star...	Generic inline container for styling.
<figcaption>Rania S. <span class="stars" aria-label="5 out of 5 sta...	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 14px;	Rounds the corners.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "\201C";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
font-size: 5rem;	Size of the text.
opacity: .25;	Transparency from 0 (invisible) to 1 (solid).
font-weight: 600;	Thickness of the text.

Check your work

- Attribution is outside the blockquote
- Stars have a text alternative
- Quote mark does not overlap text badly
- Cards equal height

Exercises

1. Add photos of the customers.
2. Turn the section into a horizontal scroll-snap carousel.
3. Add schema.org Review microdata.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 322: Testimonials section for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 2 | Files: index.html, styles.css

Brief

Show three customer quotes as cards with a large decorative quotation mark, the customer's name and a star rating.

Learning goals

- Mark up quotes correctly with figure, blockquote and figcaption
- Position a decorative ::before
- Label icon-only content with aria-label

Elements and CSS used

HTML elements	CSS features
figure, blockquote, p, figcaption, span	position: relative/absolute, ::before, content, opacity, font-style, grid

Build guide

1. Write one <figure> per review: blockquote with the text, figcaption with the name.
2. Add the stars in a span with an aria-label.
3. Grid the figures.
4. Set figure position: relative.
5. Add the big quotation mark with ::before positioned absolutely.
6. Colour the stars.

Project 322: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - Reviews</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What customers say about Delta Kids Library</h1>
    <div class="quotes">
      <figure>
        <blockquote><p>The best programme experience in Tanta.</p></
blockquote>
        <figcaption>Heba M. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>Friendly staff and fair prices.</p></
blockquote>
        <figcaption>Ziad K. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>I recommend them to everyone.</p></blockquote>
        <figcaption>Rania S. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
    </div>
  </main>
</body>
</html>
```

Project 322: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.quotes { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(16rem, 1fr)); }
figure { margin: 0; padding: 1.5rem; background: var(--accent);
border-radius: 14px; position: relative; }
figure::before { content: "\201C"; position: absolute; top: -.2em;
```

```
left: .4rem; font-size: 5rem; color: var(--brand); opacity: .25; font-
family: Georgia, serif; }
blockquote { margin: 0 0 1rem; font-size: 1.1rem; font-style: italic;
}
figcaption { font-weight: 600; }
.stars { color: #f59e0b; margin-left: .5rem; }
```

Project 322 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - Reviews</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What customers say about Delta Kids Library	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure>	Self-contained media with an optional caption.
<blockquote> The best programme experience in Tanta. </blockqu...	A paragraph of text.
<figcaption>Heba M. <span class="stars" aria-label="5 out of 5 star...	Caption for the figure.

Line	What it does
<blockquote> Friendly staff and fair prices. </blockquote>	A long quotation from another source.
<figcaption>Ziad K. <span class="stars" aria-label="5 out of 5 star...	Generic inline container for styling.
<figcaption>Rania S. <span class="stars" aria-label="5 out of 5 sta...	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 14px;	Rounds the corners.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "\201C";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
font-size: 5rem;	Size of the text.
opacity: .25;	Transparency from 0 (invisible) to 1 (solid).
font-weight: 600;	Thickness of the text.

Check your work

- Attribution is outside the blockquote
- Stars have a text alternative
- Quote mark does not overlap text badly
- Cards equal height

Exercises

1. Add photos of the customers.
2. Turn the section into a horizontal scroll-snap carousel.
3. Add schema.org Review microdata.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 323: Testimonials section for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Show three customer quotes as cards with a large decorative quotation mark, the customer's name and a star rating.

Learning goals

- Mark up quotes correctly with figure, blockquote and figcaption
- Position a decorative ::before
- Label icon-only content with aria-label

Elements and CSS used

HTML elements	CSS features
figure, blockquote, p, figcaption, span	position: relative/absolute, ::before, content, opacity, font-style, grid

Build guide

1. Write one <figure> per review: blockquote with the text, figcaption with the name.
2. Add the stars in a span with an aria-label.
3. Grid the figures.
4. Set figure position: relative.
5. Add the big quotation mark with ::before positioned absolutely.
6. Colour the stars.

Project 323: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - Reviews</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What customers say about Nubian Guest House</h1>
    <div class="quotes">
      <figure>
        <blockquote><p>The best room experience in Aswan.</p></
blockquote>
        <figcaption>Heba M. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>Friendly staff and fair prices.</p></
blockquote>
        <figcaption>Ziad K. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>I recommend them to everyone.</p></blockquote>
        <figcaption>Rania S. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
    </div>
  </main>
</body>
</html>
```

Project 323: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.quotes { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(16rem, 1fr)); }
figure { margin: 0; padding: 1.5rem; background: var(--accent);
border-radius: 14px; position: relative; }
figure::before { content: "\201C"; position: absolute; top: -.2em;
```

```
left: .4rem; font-size: 5rem; color: var(--brand); opacity: .25; font-
family: Georgia, serif; }
blockquote { margin: 0 0 1rem; font-size: 1.1rem; font-style: italic;
}
figcaption { font-weight: 600; }
.stars { color: #f59e0b; margin-left: .5rem; }
```

Project 323 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - Reviews</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What customers say about Nubian Guest House	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure>	Self-contained media with an optional caption.
<blockquote> The best room experience in Aswan. </blockquote>	A paragraph of text.
<figcaption>Heba M. <span class="stars" aria-label="5 out of 5 star...	Caption for the figure.

Line	What it does
<blockquote> Friendly staff and fair prices. </blockquote>	A long quotation from another source.
<figcaption>Ziad K. <span class="stars" aria-label="5 out of 5 star...	Generic inline container for styling.
<figcaption>Rania S. <span class="stars" aria-label="5 out of 5 sta...	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 14px;	Rounds the corners.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "\201C";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
font-size: 5rem;	Size of the text.
opacity: .25;	Transparency from 0 (invisible) to 1 (solid).
font-weight: 600;	Thickness of the text.

Check your work

- Attribution is outside the blockquote
- Stars have a text alternative
- Quote mark does not overlap text badly
- Cards equal height

Exercises

1. Add photos of the customers.
2. Turn the section into a horizontal scroll-snap carousel.
3. Add schema.org Review microdata.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 324: Testimonials section for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 2 | Files: index.html, styles.css

Brief

Show three customer quotes as cards with a large decorative quotation mark, the customer's name and a star rating.

Learning goals

- Mark up quotes correctly with figure, blockquote and figcaption
- Position a decorative ::before
- Label icon-only content with aria-label

Elements and CSS used

HTML elements	CSS features
figure, blockquote, p, figcaption, span	position: relative/absolute, ::before, content, opacity, font-style, grid

Build guide

1. Write one <figure> per review: blockquote with the text, figcaption with the name.
2. Add the stars in a span with an aria-label.
3. Grid the figures.
4. Set figure position: relative.
5. Add the big quotation mark with ::before positioned absolutely.

6. Colour the stars.

Project 324: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - Reviews</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What customers say about Ismailia Cycling Store</h1>
    <div class="quotes">
      <figure>
        <blockquote><p>The best bike experience in Ismailia.</p></
blockquote>
        <figcaption>Heba M. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>Friendly staff and fair prices.</p></
blockquote>
        <figcaption>Ziad K. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>I recommend them to everyone.</p></blockquote>
        <figcaption>Rania S. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
    </div>
  </main>
</body>
</html>
```

Project 324: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.quotes { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(16rem, 1fr)); }
figure { margin: 0; padding: 1.5rem; background: var(--accent);
border-radius: 14px; position: relative; }
figure::before { content: "\201C"; position: absolute; top: -.2em;
```

```
left: .4rem; font-size: 5rem; color: var(--brand); opacity: .25; font-
family: Georgia, serif; }
blockquote { margin: 0 0 1rem; font-size: 1.1rem; font-style: italic;
}
figcaption { font-weight: 600; }
.stars { color: #f59e0b; margin-left: .5rem; }
```

Project 324 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - Reviews</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What customers say about Ismailia Cycling Store	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure>	Self-contained media with an optional caption.
<blockquote> The best bike experience in Ismailia. </blockquote>	A paragraph of text.
<figcaption>Heba M. <span class="stars" aria-label="5 out of 5 star...	Caption for the figure.

Line	What it does
<blockquote> Friendly staff and fair prices. </blockquote>	A long quotation from another source.
<figcaption>Ziad K. <span class="stars" aria-label="5 out of 5 star...	Generic inline container for styling.
<figcaption>Rania S. <span class="stars" aria-label="5 out of 5 sta...	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 14px;	Rounds the corners.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "\201C";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
font-size: 5rem;	Size of the text.
opacity: .25;	Transparency from 0 (invisible) to 1 (solid).
font-weight: 600;	Thickness of the text.

Check your work

- Attribution is outside the blockquote
- Stars have a text alternative
- Quote mark does not overlap text badly
- Cards equal height

Exercises

1. Add photos of the customers.
2. Turn the section into a horizontal scroll-snap carousel.
3. Add schema.org Review microdata.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 325: Testimonials section for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 2 | Files: index.html, styles.css

Brief

Show three customer quotes as cards with a large decorative quotation mark, the customer's name and a star rating.

Learning goals

- Mark up quotes correctly with figure, blockquote and figcaption
- Position a decorative ::before
- Label icon-only content with aria-label

Elements and CSS used

HTML elements	CSS features
figure, blockquote, p, figcaption, span	position: relative/absolute, ::before, content, opacity, font-style, grid

Build guide

1. Write one <figure> per review: blockquote with the text, figcaption with the name.
2. Add the stars in a span with an aria-label.
3. Grid the figures.
4. Set figure position: relative.
5. Add the big quotation mark with ::before positioned absolutely.
6. Colour the stars.

Project 325: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - Reviews</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What customers say about Minya Coding Club</h1>
    <div class="quotes">
      <figure>
        <blockquote><p>The best workshop experience in Minya.</p></
blockquote>
        <figcaption>Heba M. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>Friendly staff and fair prices.</p></
blockquote>
        <figcaption>Ziad K. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
      <figure>
        <blockquote><p>I recommend them to everyone.</p></blockquote>
        <figcaption>Rania S. <span class="stars" aria-label="5 out of
5 stars">&#9733;&#9733;&#9733;&#9733;&#9733;</span></figcaption>
      </figure>
    </div>
  </main>
</body>
</html>
```

Project 325: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.quotes { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(16rem, 1fr)); }
figure { margin: 0; padding: 1.5rem; background: var(--accent);
border-radius: 14px; position: relative; }
figure::before { content: "\201C"; position: absolute; top: -.2em;
```

```
left: .4rem; font-size: 5rem; color: var(--brand); opacity: .25; font-
family: Georgia, serif; }
blockquote { margin: 0 0 1rem; font-size: 1.1rem; font-style: italic;
}
figcaption { font-weight: 600; }
.stars { color: #f59e0b; margin-left: .5rem; }
```

Project 325 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - Reviews</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What customers say about Minya Coding Club	The main heading; only one per page.
	Generic block container for grouping and layout.
<figure>	Self-contained media with an optional caption.
<blockquote> The best workshop experience in Minya. </blockquote>	A paragraph of text.
<figcaption>Heba M. <span class="stars" aria-label="5 out of 5 star...	Caption for the figure.

Line	What it does
<blockquote> Friendly staff and fair prices. </blockquote>	A long quotation from another source.
<figcaption>Ziad K. <span class="stars" aria-label="5 out of 5 star...	Generic inline container for styling.
<figcaption>Rania S. <span class="stars" aria-label="5 out of 5 sta...	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(16rem, 1fr));	Defines the columns of the grid.
background: var(--accent);	Background colour or image.
border-radius: 14px;	Rounds the corners.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "\201C";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
font-size: 5rem;	Size of the text.
opacity: .25;	Transparency from 0 (invisible) to 1 (solid).
font-weight: 600;	Thickness of the text.

Check your work

- Attribution is outside the blockquote
- Stars have a text alternative
- Quote mark does not overlap text badly
- Cards equal height

Exercises

1. Add photos of the customers.
2. Turn the section into a horizontal scroll-snap carousel.
3. Add schema.org Review microdata.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Newsletter sign-up box

Level 1 | 25 projects, one per theme

Create a centred sign-up card with a single email field and button on one line, a visually hidden label and a privacy note.

Project 326: Newsletter sign-up box for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 1 | Files: index.html, styles.css

Brief

Create a centred sign-up card with a single email field and button on one line, a visually hidden label and a privacy note.

Learning goals

- Hide a label visually but keep it for screen readers
- Put input and button on one line with Flexbox and let them wrap
- Use placeholder correctly (hint, not label)

Elements and CSS used

HTML elements	CSS features
section, form, label, input, button, p, a	flex: 1 1 12rem, flex-wrap, .sr-only pattern, border-radius: 999px, place-items

Build guide

1. Write the section with heading, text, form and note.
2. Add a label with class sr-only before the input.
3. Use type="email" and required.
4. Make the form a flex row that wraps.
5. Give the input flex: 1 1 12rem so it grows but wraps below 12rem.
6. Centre the card on a coloured page.

Project 326: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Newsletter</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <section class="signup">
      <h1>Get Cairo Book Shop news</h1>
      <p>New books, offers and events. One email a month, no spam.</p>
      <form action="/subscribe" method="post">
        <label for="email" class="sr-only">Email address</label>
        <input id="email" name="email" type="email"
placeholder="you@example.com" required autocomplete="email">
        <button type="submit">Subscribe</button>
      </form>
      <p class="small">By subscribing you agree to our <a
href="privacy.html">privacy policy</a>.</p>
    </section>
  </main>
</body>
</html>
```

Project 326: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center; padding:
 1rem; background: var(--brand); }
.signup { background: #fff; padding: 2.5rem; border-radius: 18px; max-
width: 30rem; text-align: center; }
form { display: flex; gap: .5rem; flex-wrap: wrap; }
input { flex: 1 1 12rem; padding: .8rem 1rem; border: 1px solid #bbb;
border-radius: 999px; font: inherit; }
button { padding: .8rem 1.4rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
.small { font-size: .8rem; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 326 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - Newsletter</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<section class="signup">	A thematic group of content, normally with its own heading.
Get Cairo Book Shop news	The main heading; only one per page.
New books, offers and events. One email a month, no spam.	A paragraph of text.
<form action="/subscribe" method="post">	A form; action is where the data goes, method how it is sent.
<label for="email" class="sr-only">Email address</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="email" name="email" type="email" placeholder="you@exampl...	Email field: validated automatically and shows the @ keyboard on phones.
<button type="submit">Subscribe</button>	A clickable button; inside a form it submits by default.
<p class="small">By subscribing you agree to our <a href="privacy.h...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.

Declaration	What it does
padding: 1rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.
border-radius: 18px;	Rounds the corners.
max-width: 30rem;	Limits how wide the element can grow, keeping lines readable.
text-align: center;	Centres inline content such as text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .5rem;	Space between grid or flex items without extra margins.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
flex: 1 1 12rem;	The item can grow and shrink from the given basis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	The line around the element: width, style and colour.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-size: .8rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Screen reader announces 'Email address'
- Placeholder disappears when typing; label does not
- Button wraps under the input on very narrow screens
- Contrast of white card on brand colour

Exercises

1. Add a success message with the :valid state.
2. Add a checkbox for consent.
3. Animate the card entrance with @keyframes.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea

Field	Value
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 327: Newsletter sign-up box for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 1 | Files: index.html, styles.css

Brief

Create a centred sign-up card with a single email field and button on one line, a visually hidden label and a privacy note.

Learning goals

- Hide a label visually but keep it for screen readers
- Put input and button on one line with Flexbox and let them wrap
- Use placeholder correctly (hint, not label)

Elements and CSS used

HTML elements	CSS features
section, form, label, input, button, p, a	flex: 1 1 12rem, flex-wrap, .sr-only pattern, border-radius: 999px, place-items

Build guide

1. Write the section with heading, text, form and note.
2. Add a label with class sr-only before the input.
3. Use type="email" and required.
4. Make the form a flex row that wraps.
5. Give the input flex: 1 1 12rem so it grows but wraps below 12rem.
6. Centre the card on a coloured page.

Project 327: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - Newsletter</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <section class="signup">
      <h1>Get Nile Bakery news</h1>
      <p>New pastries, offers and events. One email a month, no spam.
</p>
      <form action="/subscribe" method="post">
        <label for="email" class="sr-only">Email address</label>
        <input id="email" name="email" type="email"
placeholder="you@example.com" required autocomplete="email">
        <button type="submit">Subscribe</button>
      </form>
      <p class="small">By subscribing you agree to our <a
href="privacy.html">privacy policy</a>.</p>
    </section>
  </main>
</body>
</html>
```

Project 327: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center; padding:
 1rem; background: var(--brand); }
.signup { background: #fff; padding: 2.5rem; border-radius: 18px; max-
width: 30rem; text-align: center; }
form { display: flex; gap: .5rem; flex-wrap: wrap; }
input { flex: 1 1 12rem; padding: .8rem 1rem; border: 1px solid #bbb;
border-radius: 999px; font: inherit; }
button { padding: .8rem 1.4rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
.small { font-size: .8rem; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 327 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - Newsletter</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<section class="signup">	A thematic group of content, normally with its own heading.
Get Nile Bakery news	The main heading; only one per page.
New pastries, offers and events. One email a month, no spam.	A paragraph of text.
<form action="/subscribe" method="post">	A form; action is where the data goes, method how it is sent.
<label for="email" class="sr-only">Email address</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="email" name="email" type="email" placeholder="you@exampl...	Email field: validated automatically and shows the @ keyboard on phones.
<button type="submit">Subscribe</button>	A clickable button; inside a form it submits by default.
<p class="small">By subscribing you agree to our <a href="privacy.h...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.

Declaration	What it does
padding: 1rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.
border-radius: 18px;	Rounds the corners.
max-width: 30rem;	Limits how wide the element can grow, keeping lines readable.
text-align: center;	Centres inline content such as text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .5rem;	Space between grid or flex items without extra margins.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
flex: 1 1 12rem;	The item can grow and shrink from the given basis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	The line around the element: width, style and colour.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-size: .8rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Screen reader announces 'Email address'
- Placeholder disappears when typing; label does not
- Button wraps under the input on very narrow screens
- Contrast of white card on brand colour

Exercises

1. Add a success message with the :valid state.
2. Add a checkbox for consent.
3. Animate the card entrance with @keyframes.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec

Field	Value
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 328: Newsletter sign-up box for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 1 | Files: index.html, styles.css

Brief

Create a centred sign-up card with a single email field and button on one line, a visually hidden label and a privacy note.

Learning goals

- Hide a label visually but keep it for screen readers
- Put input and button on one line with Flexbox and let them wrap
- Use placeholder correctly (hint, not label)

Elements and CSS used

HTML elements	CSS features
section, form, label, input, button, p, a	flex: 1 1 12rem, flex-wrap, .sr-only pattern, border-radius: 999px, place-items

Build guide

1. Write the section with heading, text, form and note.
2. Add a label with class sr-only before the input.
3. Use type="email" and required.
4. Make the form a flex row that wraps.
5. Give the input flex: 1 1 12rem so it grows but wraps below 12rem.

6. Centre the card on a coloured page.

Project 328: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - Newsletter</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <section class="signup">
      <h1>Get Pyramid Fitness news</h1>
      <p>New classes, offers and events. One email a month, no spam.</
p>
      <form action="/subscribe" method="post">
        <label for="email" class="sr-only">Email address</label>
        <input id="email" name="email" type="email"
placeholder="you@example.com" required autocomplete="email">
        <button type="submit">Subscribe</button>
      </form>
      <p class="small">By subscribing you agree to our <a
href="privacy.html">privacy policy</a>.</p>
    </section>
  </main>
</body>
</html>
```

Project 328: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center; padding:
 1rem; background: var(--brand); }
.signup { background: #fff; padding: 2.5rem; border-radius: 18px; max-
width: 30rem; text-align: center; }
form { display: flex; gap: .5rem; flex-wrap: wrap; }
input { flex: 1 1 12rem; padding: .8rem 1rem; border: 1px solid #bbb;
border-radius: 999px; font: inherit; }
button { padding: .8rem 1.4rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
.small { font-size: .8rem; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 328 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - Newsletter</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<section class="signup">	A thematic group of content, normally with its own heading.
Get Pyramid Fitness news	The main heading; only one per page.
New classes, offers and events. One email a month, no spam.	A paragraph of text.
<form action="/subscribe" method="post">	A form; action is where the data goes, method how it is sent.
<label for="email" class="sr-only">Email address</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="email" name="email" type="email" placeholder="you@exampl...	Email field: validated automatically and shows the @ keyboard on phones.
<button type="submit">Subscribe</button>	A clickable button; inside a form it submits by default.
<p class="small">By subscribing you agree to our <a href="privacy.h...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.

Declaration	What it does
padding: 1rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.
border-radius: 18px;	Rounds the corners.
max-width: 30rem;	Limits how wide the element can grow, keeping lines readable.
text-align: center;	Centres inline content such as text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .5rem;	Space between grid or flex items without extra margins.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
flex: 1 1 12rem;	The item can grow and shrink from the given basis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	The line around the element: width, style and colour.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-size: .8rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Screen reader announces 'Email address'
- Placeholder disappears when typing; label does not
- Button wraps under the input on very narrow screens
- Contrast of white card on brand colour

Exercises

1. Add a success message with the :valid state.
2. Add a checkbox for consent.
3. Animate the card entrance with @keyframes.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5

Field	Value
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 329: Newsletter sign-up box for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 1 | Files: index.html, styles.css

Brief

Create a centred sign-up card with a single email field and button on one line, a visually hidden label and a privacy note.

Learning goals

- Hide a label visually but keep it for screen readers
- Put input and button on one line with Flexbox and let them wrap
- Use placeholder correctly (hint, not label)

Elements and CSS used

HTML elements	CSS features
section, form, label, input, button, p, a	flex: 1 1 12rem, flex-wrap, .sr-only pattern, border-radius: 999px, place-items

Build guide

1. Write the section with heading, text, form and note.
2. Add a label with class sr-only before the input.
3. Use type="email" and required.
4. Make the form a flex row that wraps.
5. Give the input flex: 1 1 12rem so it grows but wraps below 12rem.
6. Centre the card on a coloured page.

Project 329: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - Newsletter</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <section class="signup">
      <h1>Get Delta Dental Clinic news</h1>
      <p>New services, offers and events. One email a month, no spam.
</p>
      <form action="/subscribe" method="post">
        <label for="email" class="sr-only">Email address</label>
        <input id="email" name="email" type="email"
placeholder="you@example.com" required autocomplete="email">
        <button type="submit">Subscribe</button>
      </form>
      <p class="small">By subscribing you agree to our <a
href="privacy.html">privacy policy</a>.</p>
    </section>
  </main>
</body>
</html>
```

Project 329: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center; padding:
 1rem; background: var(--brand); }
.signup { background: #fff; padding: 2.5rem; border-radius: 18px; max-
width: 30rem; text-align: center; }
form { display: flex; gap: .5rem; flex-wrap: wrap; }
input { flex: 1 1 12rem; padding: .8rem 1rem; border: 1px solid #bbb;
border-radius: 999px; font: inherit; }
button { padding: .8rem 1.4rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
.small { font-size: .8rem; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 329 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - Newsletter</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<section class="signup">	A thematic group of content, normally with its own heading.
Get Delta Dental Clinic news	The main heading; only one per page.
New services, offers and events. One email a month, no spam.	A paragraph of text.
<form action="/subscribe" method="post">	A form; action is where the data goes, method how it is sent.
<label for="email" class="sr-only">Email address</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="email" name="email" type="email" placeholder="you@exampl...	Email field: validated automatically and shows the @ keyboard on phones.
<button type="submit">Subscribe</button>	A clickable button; inside a form it submits by default.
<p class="small">By subscribing you agree to our <a href="privacy.h...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.

Declaration	What it does
padding: 1rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.
border-radius: 18px;	Rounds the corners.
max-width: 30rem;	Limits how wide the element can grow, keeping lines readable.
text-align: center;	Centres inline content such as text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .5rem;	Space between grid or flex items without extra margins.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
flex: 1 1 12rem;	The item can grow and shrink from the given basis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	The line around the element: width, style and colour.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-size: .8rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Screen reader announces 'Email address'
- Placeholder disappears when typing; label does not
- Button wraps under the input on very narrow screens
- Contrast of white card on brand colour

Exercises

1. Add a success message with the :valid state.
2. Add a checkbox for consent.
3. Animate the card entrance with @keyframes.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff

Field	Value
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 330: Newsletter sign-up box for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 1 | Files: index.html, styles.css

Brief

Create a centred sign-up card with a single email field and button on one line, a visually hidden label and a privacy note.

Learning goals

- Hide a label visually but keep it for screen readers
- Put input and button on one line with Flexbox and let them wrap
- Use placeholder correctly (hint, not label)

Elements and CSS used

HTML elements	CSS features
section, form, label, input, button, p, a	flex: 1 1 12rem, flex-wrap, .sr-only pattern, border-radius: 999px, place-items

Build guide

1. Write the section with heading, text, form and note.
2. Add a label with class sr-only before the input.
3. Use type="email" and required.
4. Make the form a flex row that wraps.
5. Give the input flex: 1 1 12rem so it grows but wraps below 12rem.
6. Centre the card on a coloured page.

Project 330: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - Newsletter</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <section class="signup">
      <h1>Get Red Sea Travel news</h1>
      <p>New tours, offers and events. One email a month, no spam.</p>
      <form action="/subscribe" method="post">
        <label for="email" class="sr-only">Email address</label>
        <input id="email" name="email" type="email"
placeholder="you@example.com" required autocomplete="email">
        <button type="submit">Subscribe</button>
      </form>
      <p class="small">By subscribing you agree to our <a
href="privacy.html">privacy policy</a>.</p>
    </section>
  </main>
</body>
</html>
```

Project 330: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center; padding:
 1rem; background: var(--brand); }
.signup { background: #fff; padding: 2.5rem; border-radius: 18px; max-
width: 30rem; text-align: center; }
form { display: flex; gap: .5rem; flex-wrap: wrap; }
input { flex: 1 1 12rem; padding: .8rem 1rem; border: 1px solid #bbb;
border-radius: 999px; font: inherit; }
button { padding: .8rem 1.4rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
.small { font-size: .8rem; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 330 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - Newsletter</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<section class="signup">	A thematic group of content, normally with its own heading.
Get Red Sea Travel news	The main heading; only one per page.
New tours, offers and events. One email a month, no spam.	A paragraph of text.
<form action="/subscribe" method="post">	A form; action is where the data goes, method how it is sent.
<label for="email" class="sr-only">Email address</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="email" name="email" type="email" placeholder="you@exampl...	Email field: validated automatically and shows the @ keyboard on phones.
<button type="submit">Subscribe</button>	A clickable button; inside a form it submits by default.
<p class="small">By subscribing you agree to our <a href="privacy.h...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.

Declaration	What it does
padding: 1rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.
border-radius: 18px;	Rounds the corners.
max-width: 30rem;	Limits how wide the element can grow, keeping lines readable.
text-align: center;	Centres inline content such as text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .5rem;	Space between grid or flex items without extra margins.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
flex: 1 1 12rem;	The item can grow and shrink from the given basis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	The line around the element: width, style and colour.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-size: .8rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Screen reader announces 'Email address'
- Placeholder disappears when typing; label does not
- Button wraps under the input on very narrow screens
- Contrast of white card on brand colour

Exercises

1. Add a success message with the :valid state.
2. Add a checkbox for consent.
3. Animate the card entrance with @keyframes.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff

Field	Value
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 331: Newsletter sign-up box for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Create a centred sign-up card with a single email field and button on one line, a visually hidden label and a privacy note.

Learning goals

- Hide a label visually but keep it for screen readers
- Put input and button on one line with Flexbox and let them wrap
- Use placeholder correctly (hint, not label)

Elements and CSS used

HTML elements	CSS features
section, form, label, input, button, p, a	flex: 1 1 12rem, flex-wrap, .sr-only pattern, border-radius: 999px, place-items

Build guide

1. Write the section with heading, text, form and note.
2. Add a label with class sr-only before the input.
3. Use type="email" and required.
4. Make the form a flex row that wraps.
5. Give the input flex: 1 1 12rem so it grows but wraps below 12rem.

6. Centre the card on a coloured page.

Project 331: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - Newsletter</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <section class="signup">
      <h1>Get Lotus Language School news</h1>
      <p>New courses, offers and events. One email a month, no spam.</
p>
      <form action="/subscribe" method="post">
        <label for="email" class="sr-only">Email address</label>
        <input id="email" name="email" type="email"
placeholder="you@example.com" required autocomplete="email">
        <button type="submit">Subscribe</button>
      </form>
      <p class="small">By subscribing you agree to our <a
href="privacy.html">privacy policy</a>.</p>
    </section>
  </main>
</body>
</html>
```

Project 331: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center; padding:
 1rem; background: var(--brand); }
.signup { background: #fff; padding: 2.5rem; border-radius: 18px; max-
width: 30rem; text-align: center; }
form { display: flex; gap: .5rem; flex-wrap: wrap; }
input { flex: 1 1 12rem; padding: .8rem 1rem; border: 1px solid #bbb;
border-radius: 999px; font: inherit; }
button { padding: .8rem 1.4rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
.small { font-size: .8rem; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 331 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - Newsletter</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<section class="signup">	A thematic group of content, normally with its own heading.
Get Lotus Language School news	The main heading; only one per page.
New courses, offers and events. One email a month, no spam.	A paragraph of text.
<form action="/subscribe" method="post">	A form; action is where the data goes, method how it is sent.
<label for="email" class="sr-only">Email address</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="email" name="email" type="email" placeholder="you@exampl...	Email field: validated automatically and shows the @ keyboard on phones.
<button type="submit">Subscribe</button>	A clickable button; inside a form it submits by default.
<p class="small">By subscribing you agree to our <a href="privacy.h...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.

Declaration	What it does
padding: 1rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.
border-radius: 18px;	Rounds the corners.
max-width: 30rem;	Limits how wide the element can grow, keeping lines readable.
text-align: center;	Centres inline content such as text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .5rem;	Space between grid or flex items without extra margins.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
flex: 1 1 12rem;	The item can grow and shrink from the given basis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	The line around the element: width, style and colour.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-size: .8rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Screen reader announces 'Email address'
- Placeholder disappears when typing; label does not
- Button wraps under the input on very narrow screens
- Contrast of white card on brand colour

Exercises

1. Add a success message with the :valid state.
2. Add a checkbox for consent.
3. Animate the card entrance with @keyframes.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff

Field	Value
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 332: Newsletter sign-up box for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 1 | Files: index.html, styles.css

Brief

Create a centred sign-up card with a single email field and button on one line, a visually hidden label and a privacy note.

Learning goals

- Hide a label visually but keep it for screen readers
- Put input and button on one line with Flexbox and let them wrap
- Use placeholder correctly (hint, not label)

Elements and CSS used

HTML elements	CSS features
section, form, label, input, button, p, a	flex: 1 1 12rem, flex-wrap, .sr-only pattern, border-radius: 999px, place-items

Build guide

1. Write the section with heading, text, form and note.
2. Add a label with class sr-only before the input.
3. Use type="email" and required.
4. Make the form a flex row that wraps.
5. Give the input flex: 1 1 12rem so it grows but wraps below 12rem.
6. Centre the card on a coloured page.

Project 332: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - Newsletter</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <section class="signup">
      <h1>Get Green Leaf Cafe news</h1>
      <p>New drinks, offers and events. One email a month, no spam.</
p>
      <form action="/subscribe" method="post">
        <label for="email" class="sr-only">Email address</label>
        <input id="email" name="email" type="email"
placeholder="you@example.com" required autocomplete="email">
        <button type="submit">Subscribe</button>
      </form>
      <p class="small">By subscribing you agree to our <a
href="privacy.html">privacy policy</a>.</p>
    </section>
  </main>
</body>
</html>
```

Project 332: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center; padding:
 1rem; background: var(--brand); }
.signup { background: #fff; padding: 2.5rem; border-radius: 18px; max-
width: 30rem; text-align: center; }
form { display: flex; gap: .5rem; flex-wrap: wrap; }
input { flex: 1 1 12rem; padding: .8rem 1rem; border: 1px solid #bbb;
border-radius: 999px; font: inherit; }
button { padding: .8rem 1.4rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
.small { font-size: .8rem; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 332 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - Newsletter</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<section class="signup">	A thematic group of content, normally with its own heading.
Get Green Leaf Cafe news	The main heading; only one per page.
New drinks, offers and events. One email a month, no spam.	A paragraph of text.
<form action="/subscribe" method="post">	A form; action is where the data goes, method how it is sent.
<label for="email" class="sr-only">Email address</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="email" name="email" type="email" placeholder="you@exampl...	Email field: validated automatically and shows the @ keyboard on phones.
<button type="submit">Subscribe</button>	A clickable button; inside a form it submits by default.
<p class="small">By subscribing you agree to our <a href="privacy.h...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.

Declaration	What it does
padding: 1rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.
border-radius: 18px;	Rounds the corners.
max-width: 30rem;	Limits how wide the element can grow, keeping lines readable.
text-align: center;	Centres inline content such as text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .5rem;	Space between grid or flex items without extra margins.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
flex: 1 1 12rem;	The item can grow and shrink from the given basis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	The line around the element: width, style and colour.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-size: .8rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Screen reader announces 'Email address'
- Placeholder disappears when typing; label does not
- Button wraps under the input on very narrow screens
- Contrast of white card on brand colour

Exercises

1. Add a success message with the :valid state.
2. Add a checkbox for consent.
3. Animate the card entrance with @keyframes.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4

Field	Value
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 333: Newsletter sign-up box for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 1 | Files: index.html, styles.css

Brief

Create a centred sign-up card with a single email field and button on one line, a visually hidden label and a privacy note.

Learning goals

- Hide a label visually but keep it for screen readers
- Put input and button on one line with Flexbox and let them wrap
- Use placeholder correctly (hint, not label)

Elements and CSS used

HTML elements	CSS features
section, form, label, input, button, p, a	flex: 1 1 12rem, flex-wrap, .sr-only pattern, border-radius: 999px, place-items

Build guide

1. Write the section with heading, text, form and note.
2. Add a label with class sr-only before the input.
3. Use type="email" and required.
4. Make the form a flex row that wraps.
5. Give the input flex: 1 1 12rem so it grows but wraps below 12rem.

6. Centre the card on a coloured page.

Project 333: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - Newsletter</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <section class="signup">
      <h1>Get Sinai Trekking Club news</h1>
      <p>New hikes, offers and events. One email a month, no spam.</p>
      <form action="/subscribe" method="post">
        <label for="email" class="sr-only">Email address</label>
        <input id="email" name="email" type="email"
placeholder="you@example.com" required autocomplete="email">
        <button type="submit">Subscribe</button>
      </form>
      <p class="small">By subscribing you agree to our <a
href="privacy.html">privacy policy</a>.</p>
    </section>
  </main>
</body>
</html>
```

Project 333: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center; padding:
 1rem; background: var(--brand); }
.signup { background: #fff; padding: 2.5rem; border-radius: 18px; max-
width: 30rem; text-align: center; }
form { display: flex; gap: .5rem; flex-wrap: wrap; }
input { flex: 1 1 12rem; padding: .8rem 1rem; border: 1px solid #bbb;
border-radius: 999px; font: inherit; }
button { padding: .8rem 1.4rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
.small { font-size: .8rem; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 333 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - Newsletter</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<section class="signup">	A thematic group of content, normally with its own heading.
Get Sinai Trekking Club news	The main heading; only one per page.
New hikes, offers and events. One email a month, no spam.	A paragraph of text.
<form action="/subscribe" method="post">	A form; action is where the data goes, method how it is sent.
<label for="email" class="sr-only">Email address</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="email" name="email" type="email" placeholder="you@exampl...	Email field: validated automatically and shows the @ keyboard on phones.
<button type="submit">Subscribe</button>	A clickable button; inside a form it submits by default.
<p class="small">By subscribing you agree to our <a href="privacy.h...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.

Declaration	What it does
padding: 1rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.
border-radius: 18px;	Rounds the corners.
max-width: 30rem;	Limits how wide the element can grow, keeping lines readable.
text-align: center;	Centres inline content such as text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .5rem;	Space between grid or flex items without extra margins.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
flex: 1 1 12rem;	The item can grow and shrink from the given basis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	The line around the element: width, style and colour.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-size: .8rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Screen reader announces 'Email address'
- Placeholder disappears when typing; label does not
- Button wraps under the input on very narrow screens
- Contrast of white card on brand colour

Exercises

1. Add a success message with the :valid state.
2. Add a checkbox for consent.
3. Animate the card entrance with @keyframes.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb

Field	Value
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 334: Newsletter sign-up box for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 1 | Files: index.html, styles.css

Brief

Create a centred sign-up card with a single email field and button on one line, a visually hidden label and a privacy note.

Learning goals

- Hide a label visually but keep it for screen readers
- Put input and button on one line with Flexbox and let them wrap
- Use placeholder correctly (hint, not label)

Elements and CSS used

HTML elements	CSS features
section, form, label, input, button, p, a	flex: 1 1 12rem, flex-wrap, .sr-only pattern, border-radius: 999px, place-items

Build guide

1. Write the section with heading, text, form and note.
2. Add a label with class sr-only before the input.
3. Use type="email" and required.
4. Make the form a flex row that wraps.
5. Give the input flex: 1 1 12rem so it grows but wraps below 12rem.
6. Centre the card on a coloured page.

Project 334: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - Newsletter</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <section class="signup">
      <h1>Get Horizon Photography news</h1>
      <p>New sessions, offers and events. One email a month, no spam.
</p>
      <form action="/subscribe" method="post">
        <label for="email" class="sr-only">Email address</label>
        <input id="email" name="email" type="email"
placeholder="you@example.com" required autocomplete="email">
        <button type="submit">Subscribe</button>
      </form>
      <p class="small">By subscribing you agree to our <a
href="privacy.html">privacy policy</a>.</p>
    </section>
  </main>
</body>
</html>
```

Project 334: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center; padding:
 1rem; background: var(--brand); }
.signup { background: #fff; padding: 2.5rem; border-radius: 18px; max-
width: 30rem; text-align: center; }
form { display: flex; gap: .5rem; flex-wrap: wrap; }
input { flex: 1 1 12rem; padding: .8rem 1rem; border: 1px solid #bbb;
border-radius: 999px; font: inherit; }
button { padding: .8rem 1.4rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
.small { font-size: .8rem; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 334 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - Newsletter</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<section class="signup">	A thematic group of content, normally with its own heading.
Get Horizon Photography news	The main heading; only one per page.
New sessions, offers and events. One email a month, no spam.	A paragraph of text.
<form action="/subscribe" method="post">	A form; action is where the data goes, method how it is sent.
<label for="email" class="sr-only">Email address</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="email" name="email" type="email" placeholder="you@exampl...	Email field: validated automatically and shows the @ keyboard on phones.
<button type="submit">Subscribe</button>	A clickable button; inside a form it submits by default.
<p class="small">By subscribing you agree to our <a href="privacy.h...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.

Declaration	What it does
padding: 1rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.
border-radius: 18px;	Rounds the corners.
max-width: 30rem;	Limits how wide the element can grow, keeping lines readable.
text-align: center;	Centres inline content such as text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .5rem;	Space between grid or flex items without extra margins.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
flex: 1 1 12rem;	The item can grow and shrink from the given basis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	The line around the element: width, style and colour.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-size: .8rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Screen reader announces 'Email address'
- Placeholder disappears when typing; label does not
- Button wraps under the input on very narrow screens
- Contrast of white card on brand colour

Exercises

1. Add a success message with the :valid state.
2. Add a checkbox for consent.
3. Animate the card entrance with @keyframes.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6

Field	Value
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 335: Newsletter sign-up box for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 1 | Files: index.html, styles.css

Brief

Create a centred sign-up card with a single email field and button on one line, a visually hidden label and a privacy note.

Learning goals

- Hide a label visually but keep it for screen readers
- Put input and button on one line with Flexbox and let them wrap
- Use placeholder correctly (hint, not label)

Elements and CSS used

HTML elements	CSS features
section, form, label, input, button, p, a	flex: 1 1 12rem, flex-wrap, .sr-only pattern, border-radius: 999px, place-items

Build guide

1. Write the section with heading, text, form and note.
2. Add a label with class sr-only before the input.
3. Use type="email" and required.
4. Make the form a flex row that wraps.
5. Give the input flex: 1 1 12rem so it grows but wraps below 12rem.
6. Centre the card on a coloured page.

Project 335: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - Newsletter</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <section class="signup">
      <h1>Get Papyrus Stationery news</h1>
      <p>New products, offers and events. One email a month, no spam.
</p>
      <form action="/subscribe" method="post">
        <label for="email" class="sr-only">Email address</label>
        <input id="email" name="email" type="email"
placeholder="you@example.com" required autocomplete="email">
        <button type="submit">Subscribe</button>
      </form>
      <p class="small">By subscribing you agree to our <a
href="privacy.html">privacy policy</a>.</p>
    </section>
  </main>
</body>
</html>
```

Project 335: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center; padding:
 1rem; background: var(--brand); }
.signup { background: #fff; padding: 2.5rem; border-radius: 18px; max-
width: 30rem; text-align: center; }
form { display: flex; gap: .5rem; flex-wrap: wrap; }
input { flex: 1 1 12rem; padding: .8rem 1rem; border: 1px solid #bbb;
border-radius: 999px; font: inherit; }
button { padding: .8rem 1.4rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
.small { font-size: .8rem; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 335 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - Newsletter</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<section class="signup">	A thematic group of content, normally with its own heading.
Get Papyrus Stationery news	The main heading; only one per page.
New products, offers and events. One email a month, no spam.	A paragraph of text.
<form action="/subscribe" method="post">	A form; action is where the data goes, method how it is sent.
<label for="email" class="sr-only">Email address</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="email" name="email" type="email" placeholder="you@exampl...	Email field: validated automatically and shows the @ keyboard on phones.
<button type="submit">Subscribe</button>	A clickable button; inside a form it submits by default.
<p class="small">By subscribing you agree to our <a href="privacy.h...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.

Declaration	What it does
padding: 1rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.
border-radius: 18px;	Rounds the corners.
max-width: 30rem;	Limits how wide the element can grow, keeping lines readable.
text-align: center;	Centres inline content such as text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .5rem;	Space between grid or flex items without extra margins.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
flex: 1 1 12rem;	The item can grow and shrink from the given basis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	The line around the element: width, style and colour.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-size: .8rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Screen reader announces 'Email address'
- Placeholder disappears when typing; label does not
- Button wraps under the input on very narrow screens
- Contrast of white card on brand colour

Exercises

1. Add a success message with the :valid state.
2. Add a checkbox for consent.
3. Animate the card entrance with @keyframes.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8

Field	Value
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 336: Newsletter sign-up box for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 1 | Files: index.html, styles.css

Brief

Create a centred sign-up card with a single email field and button on one line, a visually hidden label and a privacy note.

Learning goals

- Hide a label visually but keep it for screen readers
- Put input and button on one line with Flexbox and let them wrap
- Use placeholder correctly (hint, not label)

Elements and CSS used

HTML elements	CSS features
section, form, label, input, button, p, a	flex: 1 1 12rem, flex-wrap, .sr-only pattern, border-radius: 999px, place-items

Build guide

1. Write the section with heading, text, form and note.
2. Add a label with class sr-only before the input.
3. Use type="email" and required.
4. Make the form a flex row that wraps.
5. Give the input flex: 1 1 12rem so it grows but wraps below 12rem.

6. Centre the card on a coloured page.

Project 336: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - Newsletter</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <section class="signup">
      <h1>Get Oasis Plant Nursery news</h1>
      <p>New plants, offers and events. One email a month, no spam.</
p>
      <form action="/subscribe" method="post">
        <label for="email" class="sr-only">Email address</label>
        <input id="email" name="email" type="email"
placeholder="you@example.com" required autocomplete="email">
        <button type="submit">Subscribe</button>
      </form>
      <p class="small">By subscribing you agree to our <a
href="privacy.html">privacy policy</a>.</p>
    </section>
  </main>
</body>
</html>
```

Project 336: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center; padding:
 1rem; background: var(--brand); }
.signup { background: #fff; padding: 2.5rem; border-radius: 18px; max-
width: 30rem; text-align: center; }
form { display: flex; gap: .5rem; flex-wrap: wrap; }
input { flex: 1 1 12rem; padding: .8rem 1rem; border: 1px solid #bbb;
border-radius: 999px; font: inherit; }
button { padding: .8rem 1.4rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
.small { font-size: .8rem; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 336 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - Newsletter</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<section class="signup">	A thematic group of content, normally with its own heading.
Get Oasis Plant Nursery news	The main heading; only one per page.
New plants, offers and events. One email a month, no spam.	A paragraph of text.
<form action="/subscribe" method="post">	A form; action is where the data goes, method how it is sent.
<label for="email" class="sr-only">Email address</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="email" name="email" type="email" placeholder="you@exampl...	Email field: validated automatically and shows the @ keyboard on phones.
<button type="submit">Subscribe</button>	A clickable button; inside a form it submits by default.
<p class="small">By subscribing you agree to our <a href="privacy.h...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.

Declaration	What it does
padding: 1rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.
border-radius: 18px;	Rounds the corners.
max-width: 30rem;	Limits how wide the element can grow, keeping lines readable.
text-align: center;	Centres inline content such as text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .5rem;	Space between grid or flex items without extra margins.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
flex: 1 1 12rem;	The item can grow and shrink from the given basis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	The line around the element: width, style and colour.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-size: .8rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Screen reader announces 'Email address'
- Placeholder disappears when typing; label does not
- Button wraps under the input on very narrow screens
- Contrast of white card on brand colour

Exercises

1. Add a success message with the :valid state.
2. Add a checkbox for consent.
3. Animate the card entrance with @keyframes.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7

Field	Value
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 337: Newsletter sign-up box for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 1 | Files: index.html, styles.css

Brief

Create a centred sign-up card with a single email field and button on one line, a visually hidden label and a privacy note.

Learning goals

- Hide a label visually but keep it for screen readers
- Put input and button on one line with Flexbox and let them wrap
- Use placeholder correctly (hint, not label)

Elements and CSS used

HTML elements	CSS features
section, form, label, input, button, p, a	flex: 1 1 12rem, flex-wrap, .sr-only pattern, border-radius: 999px, place-items

Build guide

1. Write the section with heading, text, form and note.
2. Add a label with class sr-only before the input.
3. Use type="email" and required.
4. Make the form a flex row that wraps.
5. Give the input flex: 1 1 12rem so it grows but wraps below 12rem.
6. Centre the card on a coloured page.

Project 337: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - Newsletter</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <section class="signup">
      <h1>Get Cedar Furniture news</h1>
      <p>New pieces, offers and events. One email a month, no spam.</
p>
      <form action="/subscribe" method="post">
        <label for="email" class="sr-only">Email address</label>
        <input id="email" name="email" type="email"
placeholder="you@example.com" required autocomplete="email">
        <button type="submit">Subscribe</button>
      </form>
      <p class="small">By subscribing you agree to our <a
href="privacy.html">privacy policy</a>.</p>
    </section>
  </main>
</body>
</html>
```

Project 337: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center; padding:
 1rem; background: var(--brand); }
.signup { background: #fff; padding: 2.5rem; border-radius: 18px; max-
width: 30rem; text-align: center; }
form { display: flex; gap: .5rem; flex-wrap: wrap; }
input { flex: 1 1 12rem; padding: .8rem 1rem; border: 1px solid #bbb;
border-radius: 999px; font: inherit; }
button { padding: .8rem 1.4rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
.small { font-size: .8rem; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 337 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - Newsletter</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<section class="signup">	A thematic group of content, normally with its own heading.
Get Cedar Furniture news	The main heading; only one per page.
New pieces, offers and events. One email a month, no spam.	A paragraph of text.
<form action="/subscribe" method="post">	A form; action is where the data goes, method how it is sent.
<label for="email" class="sr-only">Email address</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="email" name="email" type="email" placeholder="you@exampl...	Email field: validated automatically and shows the @ keyboard on phones.
<button type="submit">Subscribe</button>	A clickable button; inside a form it submits by default.
<p class="small">By subscribing you agree to our <a href="privacy.h...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.

Declaration	What it does
padding: 1rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.
border-radius: 18px;	Rounds the corners.
max-width: 30rem;	Limits how wide the element can grow, keeping lines readable.
text-align: center;	Centres inline content such as text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .5rem;	Space between grid or flex items without extra margins.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
flex: 1 1 12rem;	The item can grow and shrink from the given basis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	The line around the element: width, style and colour.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-size: .8rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Screen reader announces 'Email address'
- Placeholder disappears when typing; label does not
- Button wraps under the input on very narrow screens
- Contrast of white card on brand colour

Exercises

1. Add a success message with the :valid state.
2. Add a checkbox for consent.
3. Animate the card entrance with @keyframes.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7

Field	Value
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 338: Newsletter sign-up box for Byte Repair

Theme: Byte Repair (Nasr City) | Level 1 | Files: index.html, styles.css

Brief

Create a centred sign-up card with a single email field and button on one line, a visually hidden label and a privacy note.

Learning goals

- Hide a label visually but keep it for screen readers
- Put input and button on one line with Flexbox and let them wrap
- Use placeholder correctly (hint, not label)

Elements and CSS used

HTML elements	CSS features
section, form, label, input, button, p, a	flex: 1 1 12rem, flex-wrap, .sr-only pattern, border-radius: 999px, place-items

Build guide

1. Write the section with heading, text, form and note.
2. Add a label with class sr-only before the input.
3. Use type="email" and required.
4. Make the form a flex row that wraps.
5. Give the input flex: 1 1 12rem so it grows but wraps below 12rem.
6. Centre the card on a coloured page.

Project 338: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - Newsletter</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <section class="signup">
      <h1>Get Byte Repair news</h1>
      <p>New repairs, offers and events. One email a month, no spam.</
p>
      <form action="/subscribe" method="post">
        <label for="email" class="sr-only">Email address</label>
        <input id="email" name="email" type="email"
placeholder="you@example.com" required autocomplete="email">
        <button type="submit">Subscribe</button>
      </form>
      <p class="small">By subscribing you agree to our <a
href="privacy.html">privacy policy</a>.</p>
    </section>
  </main>
</body>
</html>
```

Project 338: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center; padding:
 1rem; background: var(--brand); }
.signup { background: #fff; padding: 2.5rem; border-radius: 18px; max-
width: 30rem; text-align: center; }
form { display: flex; gap: .5rem; flex-wrap: wrap; }
input { flex: 1 1 12rem; padding: .8rem 1rem; border: 1px solid #bbb;
border-radius: 999px; font: inherit; }
button { padding: .8rem 1.4rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
.small { font-size: .8rem; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 338 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - Newsletter</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<section class="signup">	A thematic group of content, normally with its own heading.
Get Byte Repair news	The main heading; only one per page.
New repairs, offers and events. One email a month, no spam.	A paragraph of text.
<form action="/subscribe" method="post">	A form; action is where the data goes, method how it is sent.
<label for="email" class="sr-only">Email address</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="email" name="email" type="email" placeholder="you@exampl...	Email field: validated automatically and shows the @ keyboard on phones.
<button type="submit">Subscribe</button>	A clickable button; inside a form it submits by default.
<p class="small">By subscribing you agree to our <a href="privacy.h...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.

Declaration	What it does
padding: 1rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.
border-radius: 18px;	Rounds the corners.
max-width: 30rem;	Limits how wide the element can grow, keeping lines readable.
text-align: center;	Centres inline content such as text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .5rem;	Space between grid or flex items without extra margins.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
flex: 1 1 12rem;	The item can grow and shrink from the given basis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	The line around the element: width, style and colour.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-size: .8rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Screen reader announces 'Email address'
- Placeholder disappears when typing; label does not
- Button wraps under the input on very narrow screens
- Contrast of white card on brand colour

Exercises

1. Add a success message with the :valid state.
2. Add a checkbox for consent.
3. Animate the card entrance with @keyframes.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff

Field	Value
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 339: Newsletter sign-up box for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 1 | Files: index.html, styles.css

Brief

Create a centred sign-up card with a single email field and button on one line, a visually hidden label and a privacy note.

Learning goals

- Hide a label visually but keep it for screen readers
- Put input and button on one line with Flexbox and let them wrap
- Use placeholder correctly (hint, not label)

Elements and CSS used

HTML elements	CSS features
section, form, label, input, button, p, a	flex: 1 1 12rem, flex-wrap, .sr-only pattern, border-radius: 999px, place-items

Build guide

1. Write the section with heading, text, form and note.
2. Add a label with class sr-only before the input.
3. Use type="email" and required.
4. Make the form a flex row that wraps.
5. Give the input flex: 1 1 12rem so it grows but wraps below 12rem.
6. Centre the card on a coloured page.

Project 339: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - Newsletter</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <section class="signup">
      <h1>Get Sahara Pet Care news</h1>
      <p>New services, offers and events. One email a month, no spam.
</p>
      <form action="/subscribe" method="post">
        <label for="email" class="sr-only">Email address</label>
        <input id="email" name="email" type="email"
placeholder="you@example.com" required autocomplete="email">
        <button type="submit">Subscribe</button>
      </form>
      <p class="small">By subscribing you agree to our <a
href="privacy.html">privacy policy</a>.</p>
    </section>
  </main>
</body>
</html>
```

Project 339: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center; padding:
 1rem; background: var(--brand); }
.signup { background: #fff; padding: 2.5rem; border-radius: 18px; max-
width: 30rem; text-align: center; }
form { display: flex; gap: .5rem; flex-wrap: wrap; }
input { flex: 1 1 12rem; padding: .8rem 1rem; border: 1px solid #bbb;
border-radius: 999px; font: inherit; }
button { padding: .8rem 1.4rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
.small { font-size: .8rem; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 339 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - Newsletter</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<section class="signup">	A thematic group of content, normally with its own heading.
Get Sahara Pet Care news	The main heading; only one per page.
New services, offers and events. One email a month, no spam.	A paragraph of text.
<form action="/subscribe" method="post">	A form; action is where the data goes, method how it is sent.
<label for="email" class="sr-only">Email address</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="email" name="email" type="email" placeholder="you@exampl...	Email field: validated automatically and shows the @ keyboard on phones.
<button type="submit">Subscribe</button>	A clickable button; inside a form it submits by default.
<p class="small">By subscribing you agree to our <a href="privacy.h...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.

Declaration	What it does
padding: 1rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.
border-radius: 18px;	Rounds the corners.
max-width: 30rem;	Limits how wide the element can grow, keeping lines readable.
text-align: center;	Centres inline content such as text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .5rem;	Space between grid or flex items without extra margins.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
flex: 1 1 12rem;	The item can grow and shrink from the given basis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	The line around the element: width, style and colour.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-size: .8rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Screen reader announces 'Email address'
- Placeholder disappears when typing; label does not
- Button wraps under the input on very narrow screens
- Contrast of white card on brand colour

Exercises

1. Add a success message with the :valid state.
2. Add a checkbox for consent.
3. Animate the card entrance with @keyframes.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed

Field	Value
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 340: Newsletter sign-up box for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Create a centred sign-up card with a single email field and button on one line, a visually hidden label and a privacy note.

Learning goals

- Hide a label visually but keep it for screen readers
- Put input and button on one line with Flexbox and let them wrap
- Use placeholder correctly (hint, not label)

Elements and CSS used

HTML elements	CSS features
section, form, label, input, button, p, a	flex: 1 1 12rem, flex-wrap, .sr-only pattern, border-radius: 999px, place-items

Build guide

1. Write the section with heading, text, form and note.
2. Add a label with class sr-only before the input.
3. Use type="email" and required.
4. Make the form a flex row that wraps.
5. Give the input flex: 1 1 12rem so it grows but wraps below 12rem.

6. Centre the card on a coloured page.

Project 340: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - Newsletter</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <section class="signup">
      <h1>Get Alexandria Sailing School news</h1>
      <p>New lessons, offers and events. One email a month, no spam.</
p>
      <form action="/subscribe" method="post">
        <label for="email" class="sr-only">Email address</label>
        <input id="email" name="email" type="email"
placeholder="you@example.com" required autocomplete="email">
        <button type="submit">Subscribe</button>
      </form>
      <p class="small">By subscribing you agree to our <a
href="privacy.html">privacy policy</a>.</p>
    </section>
  </main>
</body>
</html>
```

Project 340: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center; padding:
 1rem; background: var(--brand); }
.signup { background: #fff; padding: 2.5rem; border-radius: 18px; max-
width: 30rem; text-align: center; }
form { display: flex; gap: .5rem; flex-wrap: wrap; }
input { flex: 1 1 12rem; padding: .8rem 1rem; border: 1px solid #bbb;
border-radius: 999px; font: inherit; }
button { padding: .8rem 1.4rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
.small { font-size: .8rem; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 340 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - Newsletter</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<section class="signup">	A thematic group of content, normally with its own heading.
Get Alexandria Sailing School news	The main heading; only one per page.
New lessons, offers and events. One email a month, no spam.	A paragraph of text.
<form action="/subscribe" method="post">	A form; action is where the data goes, method how it is sent.
<label for="email" class="sr-only">Email address</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="email" name="email" type="email" placeholder="you@exampl...	Email field: validated automatically and shows the @ keyboard on phones.
<button type="submit">Subscribe</button>	A clickable button; inside a form it submits by default.
<p class="small">By subscribing you agree to our <a href="privacy.h...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.

Declaration	What it does
padding: 1rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.
border-radius: 18px;	Rounds the corners.
max-width: 30rem;	Limits how wide the element can grow, keeping lines readable.
text-align: center;	Centres inline content such as text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .5rem;	Space between grid or flex items without extra margins.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
flex: 1 1 12rem;	The item can grow and shrink from the given basis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	The line around the element: width, style and colour.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-size: .8rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Screen reader announces 'Email address'
- Placeholder disappears when typing; label does not
- Button wraps under the input on very narrow screens
- Contrast of white card on brand colour

Exercises

1. Add a success message with the :valid state.
2. Add a checkbox for consent.
3. Animate the card entrance with @keyframes.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff

Field	Value
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 341: Newsletter sign-up box for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Create a centred sign-up card with a single email field and button on one line, a visually hidden label and a privacy note.

Learning goals

- Hide a label visually but keep it for screen readers
- Put input and button on one line with Flexbox and let them wrap
- Use placeholder correctly (hint, not label)

Elements and CSS used

HTML elements	CSS features
section, form, label, input, button, p, a	flex: 1 1 12rem, flex-wrap, .sr-only pattern, border-radius: 999px, place-items

Build guide

1. Write the section with heading, text, form and note.
2. Add a label with class sr-only before the input.
3. Use type="email" and required.
4. Make the form a flex row that wraps.
5. Give the input flex: 1 1 12rem so it grows but wraps below 12rem.

6. Centre the card on a coloured page.

Project 341: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - Newsletter</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <section class="signup">
      <h1>Get Habiba Handmade Jewellery news</h1>
      <p>New items, offers and events. One email a month, no spam.</p>
      <form action="/subscribe" method="post">
        <label for="email" class="sr-only">Email address</label>
        <input id="email" name="email" type="email"
placeholder="you@example.com" required autocomplete="email">
        <button type="submit">Subscribe</button>
      </form>
      <p class="small">By subscribing you agree to our <a
href="privacy.html">privacy policy</a>.</p>
    </section>
  </main>
</body>
</html>
```

Project 341: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center; padding:
 1rem; background: var(--brand); }
.signup { background: #fff; padding: 2.5rem; border-radius: 18px; max-
width: 30rem; text-align: center; }
form { display: flex; gap: .5rem; flex-wrap: wrap; }
input { flex: 1 1 12rem; padding: .8rem 1rem; border: 1px solid #bbb;
border-radius: 999px; font: inherit; }
button { padding: .8rem 1.4rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
.small { font-size: .8rem; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 341 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - Newsletter</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<section class="signup">	A thematic group of content, normally with its own heading.
Get Habiba Handmade Jewellery news	The main heading; only one per page.
New items, offers and events. One email a month, no spam.	A paragraph of text.
<form action="/subscribe" method="post">	A form; action is where the data goes, method how it is sent.
<label for="email" class="sr-only">Email address</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="email" name="email" type="email" placeholder="you@exampl...	Email field: validated automatically and shows the @ keyboard on phones.
<button type="submit">Subscribe</button>	A clickable button; inside a form it submits by default.
<p class="small">By subscribing you agree to our <a href="privacy.h...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.

Declaration	What it does
padding: 1rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.
border-radius: 18px;	Rounds the corners.
max-width: 30rem;	Limits how wide the element can grow, keeping lines readable.
text-align: center;	Centres inline content such as text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .5rem;	Space between grid or flex items without extra margins.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
flex: 1 1 12rem;	The item can grow and shrink from the given basis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	The line around the element: width, style and colour.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-size: .8rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Screen reader announces 'Email address'
- Placeholder disappears when typing; label does not
- Button wraps under the input on very narrow screens
- Contrast of white card on brand colour

Exercises

1. Add a success message with the :valid state.
2. Add a checkbox for consent.
3. Animate the card entrance with @keyframes.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8

Field	Value
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 342: Newsletter sign-up box for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 1 | Files: index.html, styles.css

Brief

Create a centred sign-up card with a single email field and button on one line, a visually hidden label and a privacy note.

Learning goals

- Hide a label visually but keep it for screen readers
- Put input and button on one line with Flexbox and let them wrap
- Use placeholder correctly (hint, not label)

Elements and CSS used

HTML elements	CSS features
section, form, label, input, button, p, a	flex: 1 1 12rem, flex-wrap, .sr-only pattern, border-radius: 999px, place-items

Build guide

1. Write the section with heading, text, form and note.
2. Add a label with class sr-only before the input.
3. Use type="email" and required.
4. Make the form a flex row that wraps.
5. Give the input flex: 1 1 12rem so it grows but wraps below 12rem.

6. Centre the card on a coloured page.

Project 342: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - Newsletter</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <section class="signup">
      <h1>Get Fayoum Pottery Studio news</h1>
      <p>New workshops, offers and events. One email a month, no spam.
</p>
      <form action="/subscribe" method="post">
        <label for="email" class="sr-only">Email address</label>
        <input id="email" name="email" type="email"
placeholder="you@example.com" required autocomplete="email">
        <button type="submit">Subscribe</button>
      </form>
      <p class="small">By subscribing you agree to our <a
href="privacy.html">privacy policy</a>.</p>
    </section>
  </main>
</body>
</html>
```

Project 342: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center; padding:
 1rem; background: var(--brand); }
.signup { background: #fff; padding: 2.5rem; border-radius: 18px; max-
width: 30rem; text-align: center; }
form { display: flex; gap: .5rem; flex-wrap: wrap; }
input { flex: 1 1 12rem; padding: .8rem 1rem; border: 1px solid #bbb;
border-radius: 999px; font: inherit; }
button { padding: .8rem 1.4rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
.small { font-size: .8rem; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 342 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - Newsletter</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<section class="signup">	A thematic group of content, normally with its own heading.
Get Fayoum Pottery Studio news	The main heading; only one per page.
New workshops, offers and events. One email a month, no spam.	A paragraph of text.
<form action="/subscribe" method="post">	A form; action is where the data goes, method how it is sent.
<label for="email" class="sr-only">Email address</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="email" name="email" type="email" placeholder="you@exampl...	Email field: validated automatically and shows the @ keyboard on phones.
<button type="submit">Subscribe</button>	A clickable button; inside a form it submits by default.
<p class="small">By subscribing you agree to our <a href="privacy.h...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.

Declaration	What it does
padding: 1rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.
border-radius: 18px;	Rounds the corners.
max-width: 30rem;	Limits how wide the element can grow, keeping lines readable.
text-align: center;	Centres inline content such as text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .5rem;	Space between grid or flex items without extra margins.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
flex: 1 1 12rem;	The item can grow and shrink from the given basis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	The line around the element: width, style and colour.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-size: .8rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Screen reader announces 'Email address'
- Placeholder disappears when typing; label does not
- Button wraps under the input on very narrow screens
- Contrast of white card on brand colour

Exercises

1. Add a success message with the :valid state.
2. Add a checkbox for consent.
3. Animate the card entrance with @keyframes.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed

Field	Value
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 343: Newsletter sign-up box for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 1 | Files: index.html, styles.css

Brief

Create a centred sign-up card with a single email field and button on one line, a visually hidden label and a privacy note.

Learning goals

- Hide a label visually but keep it for screen readers
- Put input and button on one line with Flexbox and let them wrap
- Use placeholder correctly (hint, not label)

Elements and CSS used

HTML elements	CSS features
section, form, label, input, button, p, a	flex: 1 1 12rem, flex-wrap, .sr-only pattern, border-radius: 999px, place-items

Build guide

1. Write the section with heading, text, form and note.
2. Add a label with class sr-only before the input.
3. Use type="email" and required.
4. Make the form a flex row that wraps.
5. Give the input flex: 1 1 12rem so it grows but wraps below 12rem.

6. Centre the card on a coloured page.

Project 343: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - Newsletter</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <section class="signup">
      <h1>Get Cleopatra Beauty Salon news</h1>
      <p>New treatments, offers and events. One email a month, no
spam.</p>
      <form action="/subscribe" method="post">
        <label for="email" class="sr-only">Email address</label>
        <input id="email" name="email" type="email"
placeholder="you@example.com" required autocomplete="email">
        <button type="submit">Subscribe</button>
      </form>
      <p class="small">By subscribing you agree to our <a
href="privacy.html">privacy policy</a>.</p>
    </section>
  </main>
</body>
</html>
```

Project 343: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center; padding:
 1rem; background: var(--brand); }
.signup { background: #fff; padding: 2.5rem; border-radius: 18px; max-
width: 30rem; text-align: center; }
form { display: flex; gap: .5rem; flex-wrap: wrap; }
input { flex: 1 1 12rem; padding: .8rem 1rem; border: 1px solid #bbb;
border-radius: 999px; font: inherit; }
button { padding: .8rem 1.4rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
.small { font-size: .8rem; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 343 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - Newsletter</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<section class="signup">	A thematic group of content, normally with its own heading.
Get Cleopatra Beauty Salon news	The main heading; only one per page.
New treatments, offers and events. One email a month, no spam.	A paragraph of text.
<form action="/subscribe" method="post">	A form; action is where the data goes, method how it is sent.
<label for="email" class="sr-only">Email address</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="email" name="email" type="email" placeholder="you@exampl...	Email field: validated automatically and shows the @ keyboard on phones.
<button type="submit">Subscribe</button>	A clickable button; inside a form it submits by default.
<p class="small">By subscribing you agree to our <a href="privacy.h...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.

Declaration	What it does
padding: 1rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.
border-radius: 18px;	Rounds the corners.
max-width: 30rem;	Limits how wide the element can grow, keeping lines readable.
text-align: center;	Centres inline content such as text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .5rem;	Space between grid or flex items without extra margins.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
flex: 1 1 12rem;	The item can grow and shrink from the given basis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	The line around the element: width, style and colour.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-size: .8rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Screen reader announces 'Email address'
- Placeholder disappears when typing; label does not
- Button wraps under the input on very narrow screens
- Contrast of white card on brand colour

Exercises

1. Add a success message with the :valid state.
2. Add a checkbox for consent.
3. Animate the card entrance with @keyframes.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8

Field	Value
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 344: Newsletter sign-up box for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 1 | Files: index.html, styles.css

Brief

Create a centred sign-up card with a single email field and button on one line, a visually hidden label and a privacy note.

Learning goals

- Hide a label visually but keep it for screen readers
- Put input and button on one line with Flexbox and let them wrap
- Use placeholder correctly (hint, not label)

Elements and CSS used

HTML elements	CSS features
section, form, label, input, button, p, a	flex: 1 1 12rem, flex-wrap, .sr-only pattern, border-radius: 999px, place-items

Build guide

1. Write the section with heading, text, form and note.
2. Add a label with class sr-only before the input.
3. Use type="email" and required.
4. Make the form a flex row that wraps.
5. Give the input flex: 1 1 12rem so it grows but wraps below 12rem.
6. Centre the card on a coloured page.

Project 344: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - Newsletter</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <section class="signup">
      <h1>Get Suez Auto Service news</h1>
      <p>New services, offers and events. One email a month, no spam.
</p>
      <form action="/subscribe" method="post">
        <label for="email" class="sr-only">Email address</label>
        <input id="email" name="email" type="email"
placeholder="you@example.com" required autocomplete="email">
        <button type="submit">Subscribe</button>
      </form>
      <p class="small">By subscribing you agree to our <a
href="privacy.html">privacy policy</a>.</p>
    </section>
  </main>
</body>
</html>
```

Project 344: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center; padding:
 1rem; background: var(--brand); }
.signup { background: #fff; padding: 2.5rem; border-radius: 18px; max-
width: 30rem; text-align: center; }
form { display: flex; gap: .5rem; flex-wrap: wrap; }
input { flex: 1 1 12rem; padding: .8rem 1rem; border: 1px solid #bbb;
border-radius: 999px; font: inherit; }
button { padding: .8rem 1.4rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
.small { font-size: .8rem; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 344 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - Newsletter</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<section class="signup">	A thematic group of content, normally with its own heading.
Get Suez Auto Service news	The main heading; only one per page.
New services, offers and events. One email a month, no spam.	A paragraph of text.
<form action="/subscribe" method="post">	A form; action is where the data goes, method how it is sent.
<label for="email" class="sr-only">Email address</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="email" name="email" type="email" placeholder="you@exampl...	Email field: validated automatically and shows the @ keyboard on phones.
<button type="submit">Subscribe</button>	A clickable button; inside a form it submits by default.
<p class="small">By subscribing you agree to our <a href="privacy.h...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.

Declaration	What it does
padding: 1rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.
border-radius: 18px;	Rounds the corners.
max-width: 30rem;	Limits how wide the element can grow, keeping lines readable.
text-align: center;	Centres inline content such as text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .5rem;	Space between grid or flex items without extra margins.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
flex: 1 1 12rem;	The item can grow and shrink from the given basis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	The line around the element: width, style and colour.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-size: .8rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Screen reader announces 'Email address'
- Placeholder disappears when typing; label does not
- Button wraps under the input on very narrow screens
- Contrast of white card on brand colour

Exercises

1. Add a success message with the :valid state.
2. Add a checkbox for consent.
3. Animate the card entrance with @keyframes.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb

Field	Value
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 345: Newsletter sign-up box for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 1 | Files: index.html, styles.css

Brief

Create a centred sign-up card with a single email field and button on one line, a visually hidden label and a privacy note.

Learning goals

- Hide a label visually but keep it for screen readers
- Put input and button on one line with Flexbox and let them wrap
- Use placeholder correctly (hint, not label)

Elements and CSS used

HTML elements	CSS features
section, form, label, input, button, p, a	flex: 1 1 12rem, flex-wrap, .sr-only pattern, border-radius: 999px, place-items

Build guide

1. Write the section with heading, text, form and note.
2. Add a label with class sr-only before the input.
3. Use type="email" and required.
4. Make the form a flex row that wraps.
5. Give the input flex: 1 1 12rem so it grows but wraps below 12rem.
6. Centre the card on a coloured page.

Project 345: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - Newsletter</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <section class="signup">
      <h1>Get Luxor Music Academy news</h1>
      <p>New courses, offers and events. One email a month, no spam.</
p>
      <form action="/subscribe" method="post">
        <label for="email" class="sr-only">Email address</label>
        <input id="email" name="email" type="email"
placeholder="you@example.com" required autocomplete="email">
        <button type="submit">Subscribe</button>
      </form>
      <p class="small">By subscribing you agree to our <a
href="privacy.html">privacy policy</a>.</p>
    </section>
  </main>
</body>
</html>
```

Project 345: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center; padding:
 1rem; background: var(--brand); }
.signup { background: #fff; padding: 2.5rem; border-radius: 18px; max-
width: 30rem; text-align: center; }
form { display: flex; gap: .5rem; flex-wrap: wrap; }
input { flex: 1 1 12rem; padding: .8rem 1rem; border: 1px solid #bbb;
border-radius: 999px; font: inherit; }
button { padding: .8rem 1.4rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
.small { font-size: .8rem; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 345 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - Newsletter</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<section class="signup">	A thematic group of content, normally with its own heading.
Get Luxor Music Academy news	The main heading; only one per page.
New courses, offers and events. One email a month, no spam.	A paragraph of text.
<form action="/subscribe" method="post">	A form; action is where the data goes, method how it is sent.
<label for="email" class="sr-only">Email address</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="email" name="email" type="email" placeholder="you@exampl...	Email field: validated automatically and shows the @ keyboard on phones.
<button type="submit">Subscribe</button>	A clickable button; inside a form it submits by default.
<p class="small">By subscribing you agree to our <a href="privacy.h...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.

Declaration	What it does
padding: 1rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.
border-radius: 18px;	Rounds the corners.
max-width: 30rem;	Limits how wide the element can grow, keeping lines readable.
text-align: center;	Centres inline content such as text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .5rem;	Space between grid or flex items without extra margins.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
flex: 1 1 12rem;	The item can grow and shrink from the given basis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	The line around the element: width, style and colour.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-size: .8rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Screen reader announces 'Email address'
- Placeholder disappears when typing; label does not
- Button wraps under the input on very narrow screens
- Contrast of white card on brand colour

Exercises

1. Add a success message with the :valid state.
2. Add a checkbox for consent.
3. Animate the card entrance with @keyframes.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff

Field	Value
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 346: Newsletter sign-up box for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 1 | Files: index.html, styles.css

Brief

Create a centred sign-up card with a single email field and button on one line, a visually hidden label and a privacy note.

Learning goals

- Hide a label visually but keep it for screen readers
- Put input and button on one line with Flexbox and let them wrap
- Use placeholder correctly (hint, not label)

Elements and CSS used

HTML elements	CSS features
section, form, label, input, button, p, a	flex: 1 1 12rem, flex-wrap, .sr-only pattern, border-radius: 999px, place-items

Build guide

1. Write the section with heading, text, form and note.
2. Add a label with class sr-only before the input.
3. Use type="email" and required.
4. Make the form a flex row that wraps.
5. Give the input flex: 1 1 12rem so it grows but wraps below 12rem.
6. Centre the card on a coloured page.

Project 346: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - Newsletter</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <section class="signup">
      <h1>Get Port Said Seafood news</h1>
      <p>New dishes, offers and events. One email a month, no spam.</
p>
      <form action="/subscribe" method="post">
        <label for="email" class="sr-only">Email address</label>
        <input id="email" name="email" type="email"
placeholder="you@example.com" required autocomplete="email">
        <button type="submit">Subscribe</button>
      </form>
      <p class="small">By subscribing you agree to our <a
href="privacy.html">privacy policy</a>.</p>
    </section>
  </main>
</body>
</html>
```

Project 346: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center; padding:
 1rem; background: var(--brand); }
.signup { background: #fff; padding: 2.5rem; border-radius: 18px; max-
width: 30rem; text-align: center; }
form { display: flex; gap: .5rem; flex-wrap: wrap; }
input { flex: 1 1 12rem; padding: .8rem 1rem; border: 1px solid #bbb;
border-radius: 999px; font: inherit; }
button { padding: .8rem 1.4rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
.small { font-size: .8rem; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 346 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - Newsletter</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<section class="signup">	A thematic group of content, normally with its own heading.
Get Port Said Seafood news	The main heading; only one per page.
New dishes, offers and events. One email a month, no spam.	A paragraph of text.
<form action="/subscribe" method="post">	A form; action is where the data goes, method how it is sent.
<label for="email" class="sr-only">Email address</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="email" name="email" type="email" placeholder="you@exampl...	Email field: validated automatically and shows the @ keyboard on phones.
<button type="submit">Subscribe</button>	A clickable button; inside a form it submits by default.
<p class="small">By subscribing you agree to our <a href="privacy.h...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.

Declaration	What it does
padding: 1rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.
border-radius: 18px;	Rounds the corners.
max-width: 30rem;	Limits how wide the element can grow, keeping lines readable.
text-align: center;	Centres inline content such as text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .5rem;	Space between grid or flex items without extra margins.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
flex: 1 1 12rem;	The item can grow and shrink from the given basis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	The line around the element: width, style and colour.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-size: .8rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Screen reader announces 'Email address'
- Placeholder disappears when typing; label does not
- Button wraps under the input on very narrow screens
- Contrast of white card on brand colour

Exercises

1. Add a success message with the :valid state.
2. Add a checkbox for consent.
3. Animate the card entrance with @keyframes.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff

Field	Value
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 347: Newsletter sign-up box for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 1 | Files: index.html, styles.css

Brief

Create a centred sign-up card with a single email field and button on one line, a visually hidden label and a privacy note.

Learning goals

- Hide a label visually but keep it for screen readers
- Put input and button on one line with Flexbox and let them wrap
- Use placeholder correctly (hint, not label)

Elements and CSS used

HTML elements	CSS features
section, form, label, input, button, p, a	flex: 1 1 12rem, flex-wrap, .sr-only pattern, border-radius: 999px, place-items

Build guide

1. Write the section with heading, text, form and note.
2. Add a label with class sr-only before the input.
3. Use type="email" and required.
4. Make the form a flex row that wraps.
5. Give the input flex: 1 1 12rem so it grows but wraps below 12rem.
6. Centre the card on a coloured page.

Project 347: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - Newsletter</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <section class="signup">
      <h1>Get Delta Kids Library news</h1>
      <p>New programmes, offers and events. One email a month, no
spam.</p>
      <form action="/subscribe" method="post">
        <label for="email" class="sr-only">Email address</label>
        <input id="email" name="email" type="email"
placeholder="you@example.com" required autocomplete="email">
        <button type="submit">Subscribe</button>
      </form>
      <p class="small">By subscribing you agree to our <a
href="privacy.html">privacy policy</a>.</p>
    </section>
  </main>
</body>
</html>
```

Project 347: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center; padding:
 1rem; background: var(--brand); }
.signup { background: #fff; padding: 2.5rem; border-radius: 18px; max-
width: 30rem; text-align: center; }
form { display: flex; gap: .5rem; flex-wrap: wrap; }
input { flex: 1 1 12rem; padding: .8rem 1rem; border: 1px solid #bbb;
border-radius: 999px; font: inherit; }
button { padding: .8rem 1.4rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
.small { font-size: .8rem; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 347 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - Newsletter</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<section class="signup">	A thematic group of content, normally with its own heading.
Get Delta Kids Library news	The main heading; only one per page.
New programmes, offers and events. One email a month, no spam.	A paragraph of text.
<form action="/subscribe" method="post">	A form; action is where the data goes, method how it is sent.
<label for="email" class="sr-only">Email address</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="email" name="email" type="email" placeholder="you@exampl...	Email field: validated automatically and shows the @ keyboard on phones.
<button type="submit">Subscribe</button>	A clickable button; inside a form it submits by default.
<p class="small">By subscribing you agree to our <a href="privacy.h...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.

Declaration	What it does
padding: 1rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.
border-radius: 18px;	Rounds the corners.
max-width: 30rem;	Limits how wide the element can grow, keeping lines readable.
text-align: center;	Centres inline content such as text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .5rem;	Space between grid or flex items without extra margins.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
flex: 1 1 12rem;	The item can grow and shrink from the given basis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	The line around the element: width, style and colour.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-size: .8rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Screen reader announces 'Email address'
- Placeholder disappears when typing; label does not
- Button wraps under the input on very narrow screens
- Contrast of white card on brand colour

Exercises

1. Add a success message with the :valid state.
2. Add a checkbox for consent.
3. Animate the card entrance with @keyframes.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed

Field	Value
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 348: Newsletter sign-up box for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Create a centred sign-up card with a single email field and button on one line, a visually hidden label and a privacy note.

Learning goals

- Hide a label visually but keep it for screen readers
- Put input and button on one line with Flexbox and let them wrap
- Use placeholder correctly (hint, not label)

Elements and CSS used

HTML elements	CSS features
section, form, label, input, button, p, a	flex: 1 1 12rem, flex-wrap, .sr-only pattern, border-radius: 999px, place-items

Build guide

1. Write the section with heading, text, form and note.
2. Add a label with class sr-only before the input.
3. Use type="email" and required.
4. Make the form a flex row that wraps.
5. Give the input flex: 1 1 12rem so it grows but wraps below 12rem.
6. Centre the card on a coloured page.

Project 348: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - Newsletter</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <section class="signup">
      <h1>Get Nubian Guest House news</h1>
      <p>New rooms, offers and events. One email a month, no spam.</p>
      <form action="/subscribe" method="post">
        <label for="email" class="sr-only">Email address</label>
        <input id="email" name="email" type="email"
placeholder="you@example.com" required autocomplete="email">
        <button type="submit">Subscribe</button>
      </form>
      <p class="small">By subscribing you agree to our <a
href="privacy.html">privacy policy</a>.</p>
    </section>
  </main>
</body>
</html>
```

Project 348: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center; padding:
 1rem; background: var(--brand); }
.signup { background: #fff; padding: 2.5rem; border-radius: 18px; max-
width: 30rem; text-align: center; }
form { display: flex; gap: .5rem; flex-wrap: wrap; }
input { flex: 1 1 12rem; padding: .8rem 1rem; border: 1px solid #bbb;
border-radius: 999px; font: inherit; }
button { padding: .8rem 1.4rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
.small { font-size: .8rem; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 348 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - Newsletter</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<section class="signup">	A thematic group of content, normally with its own heading.
Get Nubian Guest House news	The main heading; only one per page.
New rooms, offers and events. One email a month, no spam.	A paragraph of text.
<form action="/subscribe" method="post">	A form; action is where the data goes, method how it is sent.
<label for="email" class="sr-only">Email address</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="email" name="email" type="email" placeholder="you@exampl...	Email field: validated automatically and shows the @ keyboard on phones.
<button type="submit">Subscribe</button>	A clickable button; inside a form it submits by default.
<p class="small">By subscribing you agree to our <a href="privacy.h...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.

Declaration	What it does
padding: 1rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.
border-radius: 18px;	Rounds the corners.
max-width: 30rem;	Limits how wide the element can grow, keeping lines readable.
text-align: center;	Centres inline content such as text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .5rem;	Space between grid or flex items without extra margins.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
flex: 1 1 12rem;	The item can grow and shrink from the given basis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	The line around the element: width, style and colour.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-size: .8rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Screen reader announces 'Email address'
- Placeholder disappears when typing; label does not
- Button wraps under the input on very narrow screens
- Contrast of white card on brand colour

Exercises

1. Add a success message with the :valid state.
2. Add a checkbox for consent.
3. Animate the card entrance with @keyframes.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb

Field	Value
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 349: Newsletter sign-up box for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 1 | Files: index.html, styles.css

Brief

Create a centred sign-up card with a single email field and button on one line, a visually hidden label and a privacy note.

Learning goals

- Hide a label visually but keep it for screen readers
- Put input and button on one line with Flexbox and let them wrap
- Use placeholder correctly (hint, not label)

Elements and CSS used

HTML elements	CSS features
section, form, label, input, button, p, a	flex: 1 1 12rem, flex-wrap, .sr-only pattern, border-radius: 999px, place-items

Build guide

1. Write the section with heading, text, form and note.
2. Add a label with class sr-only before the input.
3. Use type="email" and required.
4. Make the form a flex row that wraps.
5. Give the input flex: 1 1 12rem so it grows but wraps below 12rem.

6. Centre the card on a coloured page.

Project 349: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - Newsletter</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <section class="signup">
      <h1>Get Ismailia Cycling Store news</h1>
      <p>New bikes, offers and events. One email a month, no spam.</p>
      <form action="/subscribe" method="post">
        <label for="email" class="sr-only">Email address</label>
        <input id="email" name="email" type="email"
placeholder="you@example.com" required autocomplete="email">
        <button type="submit">Subscribe</button>
      </form>
      <p class="small">By subscribing you agree to our <a
href="privacy.html">privacy policy</a>.</p>
    </section>
  </main>
</body>
</html>
```

Project 349: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center; padding:
 1rem; background: var(--brand); }
.signup { background: #fff; padding: 2.5rem; border-radius: 18px; max-
width: 30rem; text-align: center; }
form { display: flex; gap: .5rem; flex-wrap: wrap; }
input { flex: 1 1 12rem; padding: .8rem 1rem; border: 1px solid #bbb;
border-radius: 999px; font: inherit; }
button { padding: .8rem 1.4rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
.small { font-size: .8rem; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 349 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - Newsletter</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<section class="signup">	A thematic group of content, normally with its own heading.
Get Ismailia Cycling Store news	The main heading; only one per page.
New bikes, offers and events. One email a month, no spam.	A paragraph of text.
<form action="/subscribe" method="post">	A form; action is where the data goes, method how it is sent.
<label for="email" class="sr-only">Email address</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="email" name="email" type="email" placeholder="you@exampl...	Email field: validated automatically and shows the @ keyboard on phones.
<button type="submit">Subscribe</button>	A clickable button; inside a form it submits by default.
<p class="small">By subscribing you agree to our <a href="privacy.h...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.

Declaration	What it does
padding: 1rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.
border-radius: 18px;	Rounds the corners.
max-width: 30rem;	Limits how wide the element can grow, keeping lines readable.
text-align: center;	Centres inline content such as text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .5rem;	Space between grid or flex items without extra margins.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
flex: 1 1 12rem;	The item can grow and shrink from the given basis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	The line around the element: width, style and colour.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-size: .8rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Screen reader announces 'Email address'
- Placeholder disappears when typing; label does not
- Button wraps under the input on very narrow screens
- Contrast of white card on brand colour

Exercises

1. Add a success message with the :valid state.
2. Add a checkbox for consent.
3. Animate the card entrance with @keyframes.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2

Field	Value
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 350: Newsletter sign-up box for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 1 | Files: index.html, styles.css

Brief

Create a centred sign-up card with a single email field and button on one line, a visually hidden label and a privacy note.

Learning goals

- Hide a label visually but keep it for screen readers
- Put input and button on one line with Flexbox and let them wrap
- Use placeholder correctly (hint, not label)

Elements and CSS used

HTML elements	CSS features
section, form, label, input, button, p, a	flex: 1 1 12rem, flex-wrap, .sr-only pattern, border-radius: 999px, place-items

Build guide

1. Write the section with heading, text, form and note.
2. Add a label with class sr-only before the input.
3. Use type="email" and required.
4. Make the form a flex row that wraps.
5. Give the input flex: 1 1 12rem so it grows but wraps below 12rem.
6. Centre the card on a coloured page.

Project 350: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - Newsletter</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <section class="signup">
      <h1>Get Minya Coding Club news</h1>
      <p>New workshops, offers and events. One email a month, no spam.
</p>
      <form action="/subscribe" method="post">
        <label for="email" class="sr-only">Email address</label>
        <input id="email" name="email" type="email"
placeholder="you@example.com" required autocomplete="email">
        <button type="submit">Subscribe</button>
      </form>
      <p class="small">By subscribing you agree to our <a
href="privacy.html">privacy policy</a>.</p>
    </section>
  </main>
</body>
</html>
```

Project 350: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center; padding:
 1rem; background: var(--brand); }
.signup { background: #fff; padding: 2.5rem; border-radius: 18px; max-
width: 30rem; text-align: center; }
form { display: flex; gap: .5rem; flex-wrap: wrap; }
input { flex: 1 1 12rem; padding: .8rem 1rem; border: 1px solid #bbb;
border-radius: 999px; font: inherit; }
button { padding: .8rem 1.4rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
.small { font-size: .8rem; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 350 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - Newsletter</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<section class="signup">	A thematic group of content, normally with its own heading.
Get Minya Coding Club news	The main heading; only one per page.
New workshops, offers and events. One email a month, no spam.	A paragraph of text.
<form action="/subscribe" method="post">	A form; action is where the data goes, method how it is sent.
<label for="email" class="sr-only">Email address</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="email" name="email" type="email" placeholder="you@exampl...	Email field: validated automatically and shows the @ keyboard on phones.
<button type="submit">Subscribe</button>	A clickable button; inside a form it submits by default.
<p class="small">By subscribing you agree to our <a href="privacy.h...	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.

Declaration	What it does
padding: 1rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.
border-radius: 18px;	Rounds the corners.
max-width: 30rem;	Limits how wide the element can grow, keeping lines readable.
text-align: center;	Centres inline content such as text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .5rem;	Space between grid or flex items without extra margins.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
flex: 1 1 12rem;	The item can grow and shrink from the given basis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	The line around the element: width, style and colour.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
font-size: .8rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Screen reader announces 'Email address'
- Placeholder disappears when typing; label does not
- Button wraps under the input on very narrow screens
- Contrast of white card on brand colour

Exercises

1. Add a success message with the :valid state.
2. Add a checkbox for consent.
3. Animate the card entrance with @keyframes.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff

Field	Value
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Sidebar layout

Level 2 | 25 projects, one per theme

Build a documentation-style page: header, left sidebar of section links, content and footer, using named grid areas that rearrange at 800px.

Project 351: Sidebar layout for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 2 | Files: index.html, styles.css

Brief

Build a documentation-style page: header, left sidebar of section links, content and footer, using named grid areas that rearrange at 800px.

Learning goals

- Use grid-template-areas for whole-page layout
- Change the areas in a media query
- Make the sidebar sticky on wide screens

Elements and CSS used

HTML elements	CSS features
div, header, nav, ul, li, a, main, section, footer	grid-template-areas, grid-area, @media (min-width), position: sticky, align-self: start

Build guide

1. Write the four regions inside a .layout div.
2. Give each region a grid-area name.
3. Mobile first: one column, areas stacked.
4. At 800px switch to two columns with side and content side by side.
5. Turn the sidebar link list into a column on desktop.
6. Make the sidebar sticky.

Project 351: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Guide</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <div class="layout">
    <header class="top"><h1>Cairo Book Shop guide</h1></header>
    <nav class="side" aria-label="Sections">
      <ul>
    <li><a href="#sLearn HTML">Learn HTML</a></li>
    <li><a href="#sCSS in Practice">CSS in Practice</a></li>
    <li><a href="#sJavaScript Basics">JavaScript Basics</a></li>
    <li><a href="#sWeb Accessibility">Web Accessibility</a></li>
      </ul>
    </nav>
    <main class="content">
      <section id="sLearn HTML"><h2>Learn HTML</h2><p>From your first
tag to a complete page. Price: 120 EGP.</p></section>
      <section id="sCSS in Practice"><h2>CSS in Practice</
h2><p>Layouts, colours and typography. Price: 150 EGP.</p></section>
      <section id="sJavaScript Basics"><h2>JavaScript Basics</
h2><p>Make pages interactive. Price: 180 EGP.</p></section>
      <section id="sWeb Accessibility"><h2>Web Accessibility</
h2><p>Pages everyone can use. Price: 95 EGP.</p></section>
    </main>
    <footer class="bottom">&copy; 2026 Cairo Book Shop</footer>
  </div>
</body>
</html>
```

Project 351: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.layout { min-height: 100vh; display: grid; grid-template-rows: auto
1fr auto; grid-template-columns: 1fr; grid-template-areas: "top"
"side" "content" "bottom"; }
.top { grid-area: top; background: var(--brand); color: #fff; padding:
 1rem 1.5rem; }
.top h1 { margin: 0; font-size: 1.3rem; }
```

```
.side { grid-area: side; background: var(--accent); padding: 1rem; }
.side ul { list-style: none; margin: 0; padding: 0; display: flex;
flex-wrap: wrap; gap: .5rem; }
.side a { display: block; padding: .4rem .7rem; border-radius: 6px;
text-decoration: none; color: var(--ink); background: #fff; }
.content { grid-area: content; padding: 1.5rem; max-width: 50rem; }
.bottom { grid-area: bottom; padding: 1rem 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
@media (min-width: 800px) {
  .layout { grid-template-columns: 16rem 1fr; grid-template-areas:
"top top" "side content" "bottom bottom"; }
  .side ul { flex-direction: column; }
  .side { position: sticky; top: 0; align-self: start; height: 100vh;
}
}
```

Project 351 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - Guide</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
	Generic block container for grouping and layout.
<header class="top"> Cairo Book Shop guide </header>	Introductory content: logo, title, navigation.
<nav class="side" aria-label="Sections">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Learn HTML	A hyperlink; href gives the destination.
CSS in Practice	One list item.
<main class="content">	The unique content of this page; exactly one per page.

Line	What it does
<section id="sLearn HTML"><h2>Learn HTML</h2><p>From your first tag...	A thematic group of content, normally with its own heading.
<section id="sCSS in Practice"><h2>CSS in Practice</h2><p>Layouts, ...	Second-level heading for a section.
<section id="sJavaScript Basics"><h2>JavaScript Basics</h2><p>Make ...	A paragraph of text.
<footer class="bottom">© 2026 Cairo Book Shop</footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
grid-template-areas: "top" "side" "content" "bottom";	Names regions of the grid so children can be placed by name.
grid-area: top;	Places a child into a named area.
background: var(--brand);	Background colour or image.
padding: 1rem 1.5rem;	Space inside the element between its border and content.
font-size: 1.3rem;	Size of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
@media (min-width: 800px) {	Applies from the given width upwards (mobile-first breakpoint).
flex-direction: column;	Stacks flex items vertically.

Declaration	What it does
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.

Check your work

- Areas string has equal columns per row
- Anchor links jump to sections
- Sticky sidebar does not cover the footer
- Mobile shows links as a wrapped row

Exercises

1. Highlight the current section link with :target.
2. Add a right column for 'on this page'.
3. Collapse the sidebar with a checkbox toggle.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 352: Sidebar layout for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 2 | Files: index.html, styles.css

Brief

Build a documentation-style page: header, left sidebar of section links, content and footer, using named grid areas that rearrange at 800px.

Learning goals

- Use grid-template-areas for whole-page layout
- Change the areas in a media query
- Make the sidebar sticky on wide screens

Elements and CSS used

HTML elements	CSS features
div, header, nav, ul, li, a, main, section, footer	grid-template-areas, grid-area, @media (min-width), position: sticky, align-self: start

Build guide

1. Write the four regions inside a .layout div.
2. Give each region a grid-area name.
3. Mobile first: one column, areas stacked.
4. At 800px switch to two columns with side and content side by side.
5. Turn the sidebar link list into a column on desktop.
6. Make the sidebar sticky.

Project 352: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - Guide</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <div class="layout">
    <header class="top"><h1>Nile Bakery guide</h1></header>
    <nav class="side" aria-label="Sections">
      <ul>
    <li><a href="#sSourdough loaf">Sourdough loaf</a></li>
    <li><a href="#sCroissant">Croissant</a></li>
    <li><a href="#sDate cookies">Date cookies</a></li>
    <li><a href="#sBaklava box">Baklava box</a></li>
      </ul>
    </nav>
    <main class="content">
      <section id="sSourdough loaf"><h2>Sourdough loaf</h2><p>Slow
fermented, crisp crust. Price: 60 EGP.</p></section>
      <section id="sCroissant"><h2>Croissant</h2><p>Butter, 27 layers.
 Price: 35 EGP.</p></section>
      <section id="sDate cookies"><h2>Date cookies</h2><p>Traditional
maamoul style. Price: 80 EGP.</p></section>
      <section id="sBaklava box"><h2>Baklava box</h2><p>Pistachio and
honey. Price: 220 EGP.</p></section>
    </main>
    <footer class="bottom">&copy; 2026 Nile Bakery</footer>
  </div>
</body>
</html>
```

Project 352: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.layout { min-height: 100vh; display: grid; grid-template-rows: auto
1fr auto; grid-template-columns: 1fr; grid-template-areas: "top"
"side" "content" "bottom"; }
.top { grid-area: top; background: var(--brand); color: #fff; padding:
 1rem 1.5rem; }
.top h1 { margin: 0; font-size: 1.3rem; }
```

```
.side { grid-area: side; background: var(--accent); padding: 1rem; }
.side ul { list-style: none; margin: 0; padding: 0; display: flex;
flex-wrap: wrap; gap: .5rem; }
.side a { display: block; padding: .4rem .7rem; border-radius: 6px;
text-decoration: none; color: var(--ink); background: #fff; }
.content { grid-area: content; padding: 1.5rem; max-width: 50rem; }
.bottom { grid-area: bottom; padding: 1rem 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
@media (min-width: 800px) {
  .layout { grid-template-columns: 16rem 1fr; grid-template-areas:
"top top" "side content" "bottom bottom"; }
  .side ul { flex-direction: column; }
  .side { position: sticky; top: 0; align-self: start; height: 100vh;
}
}
```

Project 352 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - Guide</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
	Generic block container for grouping and layout.
<header class="top"> Nile Bakery guide </header>	Introductory content: logo, title, navigation.
<nav class="side" aria-label="Sections">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Sourdough loaf	A hyperlink; href gives the destination.
Croissant	One list item.
<main class="content">	The unique content of this page; exactly one per page.

Line	What it does
<section id="sSourdough loaf"><h2>Sourdough loaf</h2><p>Slow fermen...	A thematic group of content, normally with its own heading.
<section id="sCroissant"><h2>Croissant</h2><p>Butter, 27 layers. Pr...	Second-level heading for a section.
<section id="sDate cookies"><h2>Date cookies</h2><p>Traditional maa...	A paragraph of text.
<footer class="bottom">© 2026 Nile Bakery</footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
grid-template-areas: "top" "side" "content" "bottom";	Names regions of the grid so children can be placed by name.
grid-area: top;	Places a child into a named area.
background: var(--brand);	Background colour or image.
padding: 1rem 1.5rem;	Space inside the element between its border and content.
font-size: 1.3rem;	Size of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
@media (min-width: 800px) {	Applies from the given width upwards (mobile-first breakpoint).
flex-direction: column;	Stacks flex items vertically.

Declaration	What it does
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.

Check your work

- Areas string has equal columns per row
- Anchor links jump to sections
- Sticky sidebar does not cover the footer
- Mobile shows links as a wrapped row

Exercises

1. Highlight the current section link with :target.
2. Add a right column for 'on this page'.
3. Collapse the sidebar with a checkbox toggle.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 353: Sidebar layout for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 2 | Files: index.html, styles.css

Brief

Build a documentation-style page: header, left sidebar of section links, content and footer, using named grid areas that rearrange at 800px.

Learning goals

- Use grid-template-areas for whole-page layout
- Change the areas in a media query
- Make the sidebar sticky on wide screens

Elements and CSS used

HTML elements	CSS features
div, header, nav, ul, li, a, main, section, footer	grid-template-areas, grid-area, @media (min-width), position: sticky, align-self: start

Build guide

1. Write the four regions inside a .layout div.
2. Give each region a grid-area name.
3. Mobile first: one column, areas stacked.
4. At 800px switch to two columns with side and content side by side.
5. Turn the sidebar link list into a column on desktop.
6. Make the sidebar sticky.

Project 353: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - Guide</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <div class="layout">
    <header class="top"><h1>Pyramid Fitness guide</h1></header>
    <nav class="side" aria-label="Sections">
      <ul>
    <li><a href="#sMorning yoga">Morning yoga</a></li>
    <li><a href="#sStrength circuit">Strength circuit</a></li>
    <li><a href="#sSpinning">Spinning</a></li>
    <li><a href="#sPersonal training">Personal training</a></li>
      </ul>
    </nav>
    <main class="content">
      <section id="sMorning yoga"><h2>Morning yoga</h2><p>Flexibility
and calm, 60 minutes. Price: 100 EGP.</p></section>
      <section id="sStrength circuit"><h2>Strength circuit</
h2><p>Full body, all levels. Price: 120 EGP.</p></section>
      <section id="sSpinning"><h2>Spinning</h2><p>High energy cycling.
 Price: 110 EGP.</p></section>
      <section id="sPersonal training"><h2>Personal training</
h2><p>One to one coaching. Price: 350 EGP.</p></section>
    </main>
    <footer class="bottom">&copy; 2026 Pyramid Fitness</footer>
  </div>
</body>
</html>
```

Project 353: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.layout { min-height: 100vh; display: grid; grid-template-rows: auto
1fr auto; grid-template-columns: 1fr; grid-template-areas: "top"
"side" "content" "bottom"; }
.top { grid-area: top; background: var(--brand); color: #fff; padding:
 1rem 1.5rem; }
.top h1 { margin: 0; font-size: 1.3rem; }
```

```
.side { grid-area: side; background: var(--accent); padding: 1rem; }
.side ul { list-style: none; margin: 0; padding: 0; display: flex;
flex-wrap: wrap; gap: .5rem; }
.side a { display: block; padding: .4rem .7rem; border-radius: 6px;
text-decoration: none; color: var(--ink); background: #fff; }
.content { grid-area: content; padding: 1.5rem; max-width: 50rem; }
.bottom { grid-area: bottom; padding: 1rem 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
@media (min-width: 800px) {
  .layout { grid-template-columns: 16rem 1fr; grid-template-areas:
"top top" "side content" "bottom bottom"; }
  .side ul { flex-direction: column; }
  .side { position: sticky; top: 0; align-self: start; height: 100vh;
}
}
```

Project 353 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - Guide</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
	Generic block container for grouping and layout.
<header class="top"> Pyramid Fitness guide </header>	Introductory content: logo, title, navigation.
<nav class="side" aria-label="Sections">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Morning yoga	A hyperlink; href gives the destination.
Strength circuit	One list item.

Line	What it does
<main class="content">	The unique content of this page; exactly one per page.
<section id="sMorning yoga"><h2>Morning yoga</h2><p>Flexibility and...	A thematic group of content, normally with its own heading.
<section id="sStrength circuit"><h2>Strength circuit</h2><p>Full bo...	Second-level heading for a section.
<section id="sSpinning"><h2>Spinning</h2><p>High energy cycling. Pr...	A paragraph of text.
<footer class="bottom">© 2026 Pyramid Fitness</footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
grid-template-areas: "top" "side" "content" "bottom";	Names regions of the grid so children can be placed by name.
grid-area: top;	Places a child into a named area.
background: var(--brand);	Background colour or image.
padding: 1rem 1.5rem;	Space inside the element between its border and content.
font-size: 1.3rem;	Size of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Declaration	What it does
@media (min-width: 800px) {	Applies from the given width upwards (mobile-first breakpoint).
flex-direction: column;	Stacks flex items vertically.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.

Check your work

- Areas string has equal columns per row
- Anchor links jump to sections
- Sticky sidebar does not cover the footer
- Mobile shows links as a wrapped row

Exercises

1. Highlight the current section link with :target.
2. Add a right column for 'on this page'.
3. Collapse the sidebar with a checkbox toggle.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 354: Sidebar layout for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 2 | Files: index.html, styles.css

Brief

Build a documentation-style page: header, left sidebar of section links, content and footer, using named grid areas that rearrange at 800px.

Learning goals

- Use grid-template-areas for whole-page layout
- Change the areas in a media query
- Make the sidebar sticky on wide screens

Elements and CSS used

HTML elements	CSS features
div, header, nav, ul, li, a, main, section, footer	grid-template-areas, grid-area, @media (min-width), position: sticky, align-self: start

Build guide

1. Write the four regions inside a .layout div.
2. Give each region a grid-area name.
3. Mobile first: one column, areas stacked.
4. At 800px switch to two columns with side and content side by side.
5. Turn the sidebar link list into a column on desktop.
6. Make the sidebar sticky.

Project 354: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - Guide</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <div class="layout">
    <header class="top"><h1>Delta Dental Clinic guide</h1></header>
    <nav class="side" aria-label="Sections">
      <ul>
    <li><a href="#sCheck-up">Check-up</a></li>
    <li><a href="#sWhitening">Whitening</a></li>
    <li><a href="#sFilling">Filling</a></li>
    <li><a href="#sBraces consultation">Braces consultation</a></li>
      </ul>
    </nav>
    <main class="content">
      <section id="sCheck-up"><h2>Check-up</h2><p>Examination and
cleaning. Price: 300 EGP.</p></section>
      <section id="sWhitening"><h2>Whitening</h2><p>Brighter smile in
one visit. Price: 1500 EGP.</p></section>
      <section id="sFilling"><h2>Filling</h2><p>Tooth-coloured
composite. Price: 600 EGP.</p></section>
      <section id="sBraces consultation"><h2>Braces consultation</
h2><p>Plan your treatment. Price: Free.</p></section>
    </main>
    <footer class="bottom">&copy; 2026 Delta Dental Clinic</footer>
  </div>
</body>
</html>
```

Project 354: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.layout { min-height: 100vh; display: grid; grid-template-rows: auto
1fr auto; grid-template-columns: 1fr; grid-template-areas: "top"
"side" "content" "bottom"; }
.top { grid-area: top; background: var(--brand); color: #fff; padding:
 1rem 1.5rem; }
.top h1 { margin: 0; font-size: 1.3rem; }
```

```
.side { grid-area: side; background: var(--accent); padding: 1rem; }
.side ul { list-style: none; margin: 0; padding: 0; display: flex;
flex-wrap: wrap; gap: .5rem; }
.side a { display: block; padding: .4rem .7rem; border-radius: 6px;
text-decoration: none; color: var(--ink); background: #fff; }
.content { grid-area: content; padding: 1.5rem; max-width: 50rem; }
.bottom { grid-area: bottom; padding: 1rem 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
@media (min-width: 800px) {
  .layout { grid-template-columns: 16rem 1fr; grid-template-areas:
"top top" "side content" "bottom bottom"; }
  .side ul { flex-direction: column; }
  .side { position: sticky; top: 0; align-self: start; height: 100vh;
}
}
```

Project 354 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - Guide</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
	Generic block container for grouping and layout.
<header class="top"> Delta Dental Clinic guide </header>	Introductory content: logo, title, navigation.
<nav class="side" aria-label="Sections">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Check-up	A hyperlink; href gives the destination.
Whitening	One list item.
<main class="content">	The unique content of this page; exactly one per page.

Line	What it does
<section id="sCheck-up"><h2>Check-up</h2><p>Examination and cleanin...	A thematic group of content, normally with its own heading.
<section id="sWhitening"><h2>Whitening</h2><p>Brighter smile in one...	Second-level heading for a section.
<section id="sFilling"><h2>Filling</h2><p>Tooth-coloured composite....	A paragraph of text.
<footer class="bottom">© 2026 Delta Dental Clinic</footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
grid-template-areas: "top" "side" "content" "bottom";	Names regions of the grid so children can be placed by name.
grid-area: top;	Places a child into a named area.
background: var(--brand);	Background colour or image.
padding: 1rem 1.5rem;	Space inside the element between its border and content.
font-size: 1.3rem;	Size of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
@media (min-width: 800px) {	Applies from the given width upwards (mobile-first breakpoint).
flex-direction: column;	Stacks flex items vertically.

Declaration	What it does
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.

Check your work

- Areas string has equal columns per row
- Anchor links jump to sections
- Sticky sidebar does not cover the footer
- Mobile shows links as a wrapped row

Exercises

1. Highlight the current section link with :target.
2. Add a right column for 'on this page'.
3. Collapse the sidebar with a checkbox toggle.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 355: Sidebar layout for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 2 | Files: index.html, styles.css

Brief

Build a documentation-style page: header, left sidebar of section links, content and footer, using named grid areas that rearrange at 800px.

Learning goals

- Use grid-template-areas for whole-page layout
- Change the areas in a media query
- Make the sidebar sticky on wide screens

Elements and CSS used

HTML elements	CSS features
div, header, nav, ul, li, a, main, section, footer	grid-template-areas, grid-area, @media (min-width), position: sticky, align-self: start

Build guide

1. Write the four regions inside a .layout div.
2. Give each region a grid-area name.
3. Mobile first: one column, areas stacked.
4. At 800px switch to two columns with side and content side by side.
5. Turn the sidebar link list into a column on desktop.
6. Make the sidebar sticky.

Project 355: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - Guide</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <div class="layout">
    <header class="top"><h1>Red Sea Travel guide</h1></header>
    <nav class="side" aria-label="Sections">
      <ul>
    <li><a href="#sLuxor day trip">Luxor day trip</a></li>
    <li><a href="#sSnorkelling">Snorkelling</a></li>
    <li><a href="#sDesert safari">Desert safari</a></li>
    <li><a href="#sNile cruise">Nile cruise</a></li>
      </ul>
    </nav>
    <main class="content">
      <section id="sLuxor day trip"><h2>Luxor day trip</h2><p>Karnak,
Valley of the Kings. Price: 1200 EGP.</p></section>
      <section id="sSnorkelling"><h2>Snorkelling</h2><p>Giftun island
reefs. Price: 700 EGP.</p></section>
      <section id="sDesert safari"><h2>Desert safari</h2><p>Quad
bikes and Bedouin dinner. Price: 900 EGP.</p></section>
      <section id="sNile cruise"><h2>Nile cruise</h2><p>Three nights
Aswan to Luxor. Price: 6500 EGP.</p></section>
    </main>
    <footer class="bottom">&copy; 2026 Red Sea Travel</footer>
  </div>
</body>
</html>
```

Project 355: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.layout { min-height: 100vh; display: grid; grid-template-rows: auto
1fr auto; grid-template-columns: 1fr; grid-template-areas: "top"
"side" "content" "bottom"; }
.top { grid-area: top; background: var(--brand); color: #fff; padding:
 1rem 1.5rem; }
.top h1 { margin: 0; font-size: 1.3rem; }
```

```
.side { grid-area: side; background: var(--accent); padding: 1rem; }
.side ul { list-style: none; margin: 0; padding: 0; display: flex;
flex-wrap: wrap; gap: .5rem; }
.side a { display: block; padding: .4rem .7rem; border-radius: 6px;
text-decoration: none; color: var(--ink); background: #fff; }
.content { grid-area: content; padding: 1.5rem; max-width: 50rem; }
.bottom { grid-area: bottom; padding: 1rem 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
@media (min-width: 800px) {
  .layout { grid-template-columns: 16rem 1fr; grid-template-areas:
"top top" "side content" "bottom bottom"; }
  .side ul { flex-direction: column; }
  .side { position: sticky; top: 0; align-self: start; height: 100vh;
}
}
```

Project 355 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - Guide</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
	Generic block container for grouping and layout.
<header class="top"> Red Sea Travel guide </header>	Introductory content: logo, title, navigation.
<nav class="side" aria-label="Sections">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Luxor day trip	A hyperlink; href gives the destination.
Snorkelling	One list item.
<main class="content">	The unique content of this page; exactly one per page.

Line	What it does
<section id="sLuxor day trip"><h2>Luxor day trip</h2><p>Karnak, Val...	A thematic group of content, normally with its own heading.
<section id="sSnorkelling"><h2>Snorkelling</h2><p>Giftun island ree...	Second-level heading for a section.
<section id="sDesert safari"><h2>Desert safari</h2><p>Quad bikes an...	A paragraph of text.
<footer class="bottom">© 2026 Red Sea Travel</footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
grid-template-areas: "top" "side" "content" "bottom";	Names regions of the grid so children can be placed by name.
grid-area: top;	Places a child into a named area.
background: var(--brand);	Background colour or image.
padding: 1rem 1.5rem;	Space inside the element between its border and content.
font-size: 1.3rem;	Size of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
@media (min-width: 800px) {	Applies from the given width upwards (mobile-first breakpoint).
flex-direction: column;	Stacks flex items vertically.

Declaration	What it does
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.

Check your work

- Areas string has equal columns per row
- Anchor links jump to sections
- Sticky sidebar does not cover the footer
- Mobile shows links as a wrapped row

Exercises

1. Highlight the current section link with :target.
2. Add a right column for 'on this page'.
3. Collapse the sidebar with a checkbox toggle.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 356: Sidebar layout for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Build a documentation-style page: header, left sidebar of section links, content and footer, using named grid areas that rearrange at 800px.

Learning goals

- Use grid-template-areas for whole-page layout
- Change the areas in a media query
- Make the sidebar sticky on wide screens

Elements and CSS used

HTML elements	CSS features
div, header, nav, ul, li, a, main, section, footer	grid-template-areas, grid-area, @media (min-width), position: sticky, align-self: start

Build guide

1. Write the four regions inside a .layout div.
2. Give each region a grid-area name.
3. Mobile first: one column, areas stacked.
4. At 800px switch to two columns with side and content side by side.
5. Turn the sidebar link list into a column on desktop.
6. Make the sidebar sticky.

Project 356: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - Guide</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <div class="layout">
    <header class="top"><h1>Lotus Language School guide</h1></header>
    <nav class="side" aria-label="Sections">
      <ul>
    <li><a href="#sEnglish A1">English A1</a></li>
    <li><a href="#sFrench B1">French B1</a></li>
    <li><a href="#sGerman A2">German A2</a></li>
    <li><a href="#sIELTS preparation">IELTS preparation</a></li>
      </ul>
    </nav>
    <main class="content">
      <section id="sEnglish A1"><h2>English A1</h2><p>Beginner, 8
weeks. Price: 1800 EGP.</p></section>
      <section id="sFrench B1"><h2>French B1</h2><p>Intermediate
conversation. Price: 2200 EGP.</p></section>
      <section id="sGerman A2"><h2>German A2</h2><p>Grammar and
speaking. Price: 2000 EGP.</p></section>
      <section id="sIELTS preparation"><h2>IELTS preparation</
h2><p>Exam strategies. Price: 3000 EGP.</p></section>
    </main>
    <footer class="bottom">&copy; 2026 Lotus Language School</footer>
  </div>
</body>
</html>
```

Project 356: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.layout { min-height: 100vh; display: grid; grid-template-rows: auto
1fr auto; grid-template-columns: 1fr; grid-template-areas: "top"
"side" "content" "bottom"; }
.top { grid-area: top; background: var(--brand); color: #fff; padding:
 1rem 1.5rem; }
.top h1 { margin: 0; font-size: 1.3rem; }
```

```
.side { grid-area: side; background: var(--accent); padding: 1rem; }
.side ul { list-style: none; margin: 0; padding: 0; display: flex;
flex-wrap: wrap; gap: .5rem; }
.side a { display: block; padding: .4rem .7rem; border-radius: 6px;
text-decoration: none; color: var(--ink); background: #fff; }
.content { grid-area: content; padding: 1.5rem; max-width: 50rem; }
.bottom { grid-area: bottom; padding: 1rem 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
@media (min-width: 800px) {
  .layout { grid-template-columns: 16rem 1fr; grid-template-areas:
"top top" "side content" "bottom bottom"; }
  .side ul { flex-direction: column; }
  .side { position: sticky; top: 0; align-self: start; height: 100vh;
}
}
```

Project 356 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - Guide</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
	Generic block container for grouping and layout.
<header class="top"> Lotus Language School guide </header>	Introductory content: logo, title, navigation.
<nav class="side" aria-label="Sections">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
English A1	A hyperlink; href gives the destination.
French B1	One list item.
<main class="content">	The unique content of this page; exactly one per page.

Line	What it does
<section id="sEnglish A1"><h2>English A1</h2><p>Beginner, 8 weeks. ...	A thematic group of content, normally with its own heading.
<section id="sFrench B1"><h2>French B1</h2><p>Intermediate conversa...	Second-level heading for a section.
<section id="sGerman A2"><h2>German A2</h2><p>Grammar and speaking....	A paragraph of text.
<footer class="bottom">© 2026 Lotus Language School</footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
grid-template-areas: "top" "side" "content" "bottom";	Names regions of the grid so children can be placed by name.
grid-area: top;	Places a child into a named area.
background: var(--brand);	Background colour or image.
padding: 1rem 1.5rem;	Space inside the element between its border and content.
font-size: 1.3rem;	Size of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Declaration	What it does
@media (min-width: 800px) {	Applies from the given width upwards (mobile-first breakpoint).
flex-direction: column;	Stacks flex items vertically.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.

Check your work

- Areas string has equal columns per row
- Anchor links jump to sections
- Sticky sidebar does not cover the footer
- Mobile shows links as a wrapped row

Exercises

1. Highlight the current section link with :target.
2. Add a right column for 'on this page'.
3. Collapse the sidebar with a checkbox toggle.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 357: Sidebar layout for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 2 | Files: index.html, styles.css

Brief

Build a documentation-style page: header, left sidebar of section links, content and footer, using named grid areas that rearrange at 800px.

Learning goals

- Use grid-template-areas for whole-page layout
- Change the areas in a media query
- Make the sidebar sticky on wide screens

Elements and CSS used

HTML elements	CSS features
div, header, nav, ul, li, a, main, section, footer	grid-template-areas, grid-area, @media (min-width), position: sticky, align-self: start

Build guide

1. Write the four regions inside a .layout div.
2. Give each region a grid-area name.
3. Mobile first: one column, areas stacked.
4. At 800px switch to two columns with side and content side by side.
5. Turn the sidebar link list into a column on desktop.
6. Make the sidebar sticky.

Project 357: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - Guide</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <div class="layout">
    <header class="top"><h1>Green Leaf Cafe guide</h1></header>
    <nav class="side" aria-label="Sections">
      <ul>
    <li><a href="#sFlat white">Flat white</a></li>
    <li><a href="#sCold brew">Cold brew</a></li>
    <li><a href="#sHibiscus iced tea">Hibiscus iced tea</a></li>
    <li><a href="#sCheesecake">Cheesecake</a></li>
      </ul>
    </nav>
    <main class="content">
      <section id="sFlat white"><h2>Flat white</h2><p>Double shot,
silky milk. Price: 55 EGP.</p></section>
      <section id="sCold brew"><h2>Cold brew</h2><p>18 hours steeped.
Price: 60 EGP.</p></section>
      <section id="sHibiscus iced tea"><h2>Hibiscus iced tea</
h2><p>Karkade with mint. Price: 40 EGP.</p></section>
      <section id="sCheesecake"><h2>Cheesecake</h2><p>Baked, with
berries. Price: 75 EGP.</p></section>
    </main>
    <footer class="bottom">&copy; 2026 Green Leaf Cafe</footer>
  </div>
</body>
</html>
```

Project 357: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.layout { min-height: 100vh; display: grid; grid-template-rows: auto
1fr auto; grid-template-columns: 1fr; grid-template-areas: "top"
"side" "content" "bottom"; }
.top { grid-area: top; background: var(--brand); color: #fff; padding:
 1rem 1.5rem; }
.top h1 { margin: 0; font-size: 1.3rem; }
```

```
.side { grid-area: side; background: var(--accent); padding: 1rem; }
.side ul { list-style: none; margin: 0; padding: 0; display: flex;
flex-wrap: wrap; gap: .5rem; }
.side a { display: block; padding: .4rem .7rem; border-radius: 6px;
text-decoration: none; color: var(--ink); background: #fff; }
.content { grid-area: content; padding: 1.5rem; max-width: 50rem; }
.bottom { grid-area: bottom; padding: 1rem 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
@media (min-width: 800px) {
  .layout { grid-template-columns: 16rem 1fr; grid-template-areas:
"top top" "side content" "bottom bottom"; }
  .side ul { flex-direction: column; }
  .side { position: sticky; top: 0; align-self: start; height: 100vh;
}
}
```

Project 357 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - Guide</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
	Generic block container for grouping and layout.
<header class="top"> Green Leaf Cafe guide </header>	Introductory content: logo, title, navigation.
<nav class="side" aria-label="Sections">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Flat white	A hyperlink; href gives the destination.
Cold brew	One list item.
<main class="content">	The unique content of this page; exactly one per page.

Line	What it does
<section id="sFlat white"><h2>Flat white</h2><p>Double shot, silky ...	A thematic group of content, normally with its own heading.
<section id="sCold brew"><h2>Cold brew</h2><p>18 hours steeped. Pri...	Second-level heading for a section.
<section id="sHibiscus iced tea"><h2>Hibiscus iced tea</h2><p>Karka...	A paragraph of text.
<footer class="bottom">© 2026 Green Leaf Cafe</footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.

Declaration	What it does
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
grid-template-areas: "top" "side" "content" "bottom";	Names regions of the grid so children can be placed by name.
grid-area: top;	Places a child into a named area.
background: var(--brand);	Background colour or image.
padding: 1rem 1.5rem;	Space inside the element between its border and content.
font-size: 1.3rem;	Size of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
@media (min-width: 800px) {	Applies from the given width upwards (mobile-first breakpoint).

Declaration	What it does
flex-direction: column;	Stacks flex items vertically.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.

Check your work

- Areas string has equal columns per row
- Anchor links jump to sections
- Sticky sidebar does not cover the footer
- Mobile shows links as a wrapped row

Exercises

1. Highlight the current section link with :target.
2. Add a right column for 'on this page'.
3. Collapse the sidebar with a checkbox toggle.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 358: Sidebar layout for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 2 | Files: index.html, styles.css

Brief

Build a documentation-style page: header, left sidebar of section links, content and footer, using named grid areas that rearrange at 800px.

Learning goals

- Use grid-template-areas for whole-page layout
- Change the areas in a media query
- Make the sidebar sticky on wide screens

Elements and CSS used

HTML elements	CSS features
div, header, nav, ul, li, a, main, section, footer	grid-template-areas, grid-area, @media (min-width), position: sticky, align-self: start

Build guide

1. Write the four regions inside a .layout div.
2. Give each region a grid-area name.
3. Mobile first: one column, areas stacked.
4. At 800px switch to two columns with side and content side by side.
5. Turn the sidebar link list into a column on desktop.
6. Make the sidebar sticky.

Project 358: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - Guide</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <div class="layout">
    <header class="top"><h1>Sinai Trekking Club guide</h1></header>
    <nav class="side" aria-label="Sections">
      <ul>
    <li><a href="#sMount Sinai sunrise">Mount Sinai sunrise</a></li>
    <li><a href="#sBlue Desert loop">Blue Desert loop</a></li>
    <li><a href="#sWadi Gnai">Wadi Gnai</a></li>
    <li><a href="#sThree-day traverse">Three-day traverse</a></li>
      </ul>
    </nav>
    <main class="content">
      <section id="sMount Sinai sunrise"><h2>Mount Sinai sunrise</
h2><p>Night climb, 7 km. Price: 400 EGP.</p></section>
      <section id="sBlue Desert loop"><h2>Blue Desert loop</
h2><p>Easy day walk. Price: 250 EGP.</p></section>
      <section id="sWadi Gnai"><h2>Wadi Gnai</h2><p>Palms and pools.
Price: 300 EGP.</p></section>
      <section id="sThree-day traverse"><h2>Three-day traverse</
h2><p>Camping under stars. Price: 1900 EGP.</p></section>
    </main>
    <footer class="bottom">&copy; 2026 Sinai Trekking Club</footer>
  </div>
</body>
</html>
```

Project 358: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.layout { min-height: 100vh; display: grid; grid-template-rows: auto
1fr auto; grid-template-columns: 1fr; grid-template-areas: "top"
"side" "content" "bottom"; }
.top { grid-area: top; background: var(--brand); color: #fff; padding:
 1rem 1.5rem; }
.top h1 { margin: 0; font-size: 1.3rem; }
```

```
.side { grid-area: side; background: var(--accent); padding: 1rem; }
.side ul { list-style: none; margin: 0; padding: 0; display: flex;
flex-wrap: wrap; gap: .5rem; }
.side a { display: block; padding: .4rem .7rem; border-radius: 6px;
text-decoration: none; color: var(--ink); background: #fff; }
.content { grid-area: content; padding: 1.5rem; max-width: 50rem; }
.bottom { grid-area: bottom; padding: 1rem 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
@media (min-width: 800px) {
  .layout { grid-template-columns: 16rem 1fr; grid-template-areas:
"top top" "side content" "bottom bottom"; }
  .side ul { flex-direction: column; }
  .side { position: sticky; top: 0; align-self: start; height: 100vh;
}
}
```

Project 358 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - Guide</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
	Generic block container for grouping and layout.
<header class="top"> Sinai Trekking Club guide </header>	Introductory content: logo, title, navigation.
<nav class="side" aria-label="Sections">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Mount Sinai sunrise	A hyperlink; href gives the destination.
Blue Desert loop	One list item.

Line	What it does
<main class="content">	The unique content of this page; exactly one per page.
<section id="sMount Sinai sunrise"><h2>Mount Sinai sunrise</h2><p>N...	A thematic group of content, normally with its own heading.
<section id="sBlue Desert loop"><h2>Blue Desert loop</h2><p>Easy da...	Second-level heading for a section.
<section id="sWadi Gnai"><h2>Wadi Gnai</h2><p>Palms and pools. Pric...	A paragraph of text.
<footer class="bottom">© 2026 Sinai Trekking Club</footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
grid-template-areas: "top" "side" "content" "bottom";	Names regions of the grid so children can be placed by name.
grid-area: top;	Places a child into a named area.
background: var(--brand);	Background colour or image.
padding: 1rem 1.5rem;	Space inside the element between its border and content.
font-size: 1.3rem;	Size of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Declaration	What it does
@media (min-width: 800px) {	Applies from the given width upwards (mobile-first breakpoint).
flex-direction: column;	Stacks flex items vertically.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.

Check your work

- Areas string has equal columns per row
- Anchor links jump to sections
- Sticky sidebar does not cover the footer
- Mobile shows links as a wrapped row

Exercises

1. Highlight the current section link with :target.
2. Add a right column for 'on this page'.
3. Collapse the sidebar with a checkbox toggle.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 359: Sidebar layout for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 2 | Files: index.html, styles.css

Brief

Build a documentation-style page: header, left sidebar of section links, content and footer, using named grid areas that rearrange at 800px.

Learning goals

- Use grid-template-areas for whole-page layout
- Change the areas in a media query
- Make the sidebar sticky on wide screens

Elements and CSS used

HTML elements	CSS features
div, header, nav, ul, li, a, main, section, footer	grid-template-areas, grid-area, @media (min-width), position: sticky, align-self: start

Build guide

1. Write the four regions inside a .layout div.
2. Give each region a grid-area name.
3. Mobile first: one column, areas stacked.
4. At 800px switch to two columns with side and content side by side.
5. Turn the sidebar link list into a column on desktop.
6. Make the sidebar sticky.

Project 359: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - Guide</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <div class="layout">
    <header class="top"><h1>Horizon Photography guide</h1></header>
    <nav class="side" aria-label="Sections">
      <ul>
    <li><a href="#sPortrait session">Portrait session</a></li>
    <li><a href="#sWedding day">Wedding day</a></li>
    <li><a href="#sProduct shoot">Product shoot</a></li>
    <li><a href="#sFamily session">Family session</a></li>
      </ul>
    </nav>
    <main class="content">
      <section id="sPortrait session"><h2>Portrait session</h2><p>One
hour, 20 edited photos. Price: 1200 EGP.</p></section>
      <section id="sWedding day"><h2>Wedding day</h2><p>Full coverage,
 two photographers. Price: 15000 EGP.</p></section>
      <section id="sProduct shoot"><h2>Product shoot</h2><p>White
background, 10 items. Price: 900 EGP.</p></section>
      <section id="sFamily session"><h2>Family session</h2><p>Outdoor,
 golden hour. Price: 1500 EGP.</p></section>
    </main>
    <footer class="bottom">&copy; 2026 Horizon Photography</footer>
  </div>
</body>
</html>
```

Project 359: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.layout { min-height: 100vh; display: grid; grid-template-rows: auto
1fr auto; grid-template-columns: 1fr; grid-template-areas: "top"
"side" "content" "bottom"; }
.top { grid-area: top; background: var(--brand); color: #fff; padding:
 1rem 1.5rem; }
.top h1 { margin: 0; font-size: 1.3rem; }
```

```
.side { grid-area: side; background: var(--accent); padding: 1rem; }
.side ul { list-style: none; margin: 0; padding: 0; display: flex;
flex-wrap: wrap; gap: .5rem; }
.side a { display: block; padding: .4rem .7rem; border-radius: 6px;
text-decoration: none; color: var(--ink); background: #fff; }
.content { grid-area: content; padding: 1.5rem; max-width: 50rem; }
.bottom { grid-area: bottom; padding: 1rem 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
@media (min-width: 800px) {
  .layout { grid-template-columns: 16rem 1fr; grid-template-areas:
"top top" "side content" "bottom bottom"; }
  .side ul { flex-direction: column; }
  .side { position: sticky; top: 0; align-self: start; height: 100vh;
}
}
```

Project 359 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - Guide</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
	Generic block container for grouping and layout.
<header class="top"> Horizon Photography guide </header>	Introductory content: logo, title, navigation.
<nav class="side" aria-label="Sections">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Portrait session	A hyperlink; href gives the destination.
Wedding day	One list item.

Line	What it does
<main class="content">	The unique content of this page; exactly one per page.
<section id="sPortrait session"><h2>Portrait session</h2><p>One hou...	A thematic group of content, normally with its own heading.
<section id="sWedding day"><h2>Wedding day</h2><p>Full coverage, tw...	Second-level heading for a section.
<section id="sProduct shoot"><h2>Product shoot</h2><p>White backgro...	A paragraph of text.
<footer class="bottom">© 2026 Horizon Photography</footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
grid-template-areas: "top" "side" "content" "bottom";	Names regions of the grid so children can be placed by name.
grid-area: top;	Places a child into a named area.
background: var(--brand);	Background colour or image.
padding: 1rem 1.5rem;	Space inside the element between its border and content.
font-size: 1.3rem;	Size of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Declaration	What it does
@media (min-width: 800px) {	Applies from the given width upwards (mobile-first breakpoint).
flex-direction: column;	Stacks flex items vertically.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.

Check your work

- Areas string has equal columns per row
- Anchor links jump to sections
- Sticky sidebar does not cover the footer
- Mobile shows links as a wrapped row

Exercises

1. Highlight the current section link with :target.
2. Add a right column for 'on this page'.
3. Collapse the sidebar with a checkbox toggle.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 360: Sidebar layout for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 2 | Files: index.html, styles.css

Brief

Build a documentation-style page: header, left sidebar of section links, content and footer, using named grid areas that rearrange at 800px.

Learning goals

- Use grid-template-areas for whole-page layout
- Change the areas in a media query
- Make the sidebar sticky on wide screens

Elements and CSS used

HTML elements	CSS features
div, header, nav, ul, li, a, main, section, footer	grid-template-areas, grid-area, @media (min-width), position: sticky, align-self: start

Build guide

1. Write the four regions inside a .layout div.
2. Give each region a grid-area name.
3. Mobile first: one column, areas stacked.
4. At 800px switch to two columns with side and content side by side.
5. Turn the sidebar link list into a column on desktop.
6. Make the sidebar sticky.

Project 360: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - Guide</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <div class="layout">
    <header class="top"><h1>Papyrus Stationery guide</h1></header>
    <nav class="side" aria-label="Sections">
      <ul>
    <li><a href="#sDotted notebook">Dotted notebook</a></li>
    <li><a href="#sFountain pen">Fountain pen</a></li>
    <li><a href="#sWashi tape set">Washi tape set</a></li>
    <li><a href="#sDesk planner">Desk planner</a></li>
      </ul>
    </nav>
    <main class="content">
      <section id="sDotted notebook"><h2>Dotted notebook</h2><p>A5,
160 pages. Price: 140 EGP.</p></section>
      <section id="sFountain pen"><h2>Fountain pen</h2><p>Steel nib,
refillable. Price: 350 EGP.</p></section>
      <section id="sWashi tape set"><h2>Washi tape set</h2><p>Six
patterns. Price: 90 EGP.</p></section>
      <section id="sDesk planner"><h2>Desk planner</h2><p>Weekly,
undated. Price: 110 EGP.</p></section>
    </main>
    <footer class="bottom">&copy; 2026 Papyrus Stationery</footer>
  </div>
</body>
</html>
```

Project 360: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.layout { min-height: 100vh; display: grid; grid-template-rows: auto
1fr auto; grid-template-columns: 1fr; grid-template-areas: "top"
"side" "content" "bottom"; }
.top { grid-area: top; background: var(--brand); color: #fff; padding:
 1rem 1.5rem; }
.top h1 { margin: 0; font-size: 1.3rem; }
```

```
.side { grid-area: side; background: var(--accent); padding: 1rem; }
.side ul { list-style: none; margin: 0; padding: 0; display: flex;
flex-wrap: wrap; gap: .5rem; }
.side a { display: block; padding: .4rem .7rem; border-radius: 6px;
text-decoration: none; color: var(--ink); background: #fff; }
.content { grid-area: content; padding: 1.5rem; max-width: 50rem; }
.bottom { grid-area: bottom; padding: 1rem 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
@media (min-width: 800px) {
  .layout { grid-template-columns: 16rem 1fr; grid-template-areas:
"top top" "side content" "bottom bottom"; }
  .side ul { flex-direction: column; }
  .side { position: sticky; top: 0; align-self: start; height: 100vh;
}
}
```

Project 360 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - Guide</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
	Generic block container for grouping and layout.
<header class="top"> Papyrus Stationery guide </header>	Introductory content: logo, title, navigation.
<nav class="side" aria-label="Sections">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Dotted notebook	A hyperlink; href gives the destination.
Fountain pen	One list item.

Line	What it does
<main class="content">	The unique content of this page; exactly one per page.
<section id="sDotted notebook"><h2>Dotted notebook</h2><p>A5, 160 p...	A thematic group of content, normally with its own heading.
<section id="sFountain pen"><h2>Fountain pen</h2><p>Steel nib, refi...	Second-level heading for a section.
<section id="sWashi tape set"><h2>Washi tape set</h2><p>Six pattern...	A paragraph of text.
<footer class="bottom">© 2026 Papyrus Stationery</footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
grid-template-areas: "top" "side" "content" "bottom";	Names regions of the grid so children can be placed by name.
grid-area: top;	Places a child into a named area.
background: var(--brand);	Background colour or image.
padding: 1rem 1.5rem;	Space inside the element between its border and content.
font-size: 1.3rem;	Size of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Declaration	What it does
@media (min-width: 800px) {	Applies from the given width upwards (mobile-first breakpoint).
flex-direction: column;	Stacks flex items vertically.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.

Check your work

- Areas string has equal columns per row
- Anchor links jump to sections
- Sticky sidebar does not cover the footer
- Mobile shows links as a wrapped row

Exercises

1. Highlight the current section link with :target.
2. Add a right column for 'on this page'.
3. Collapse the sidebar with a checkbox toggle.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 361: Sidebar layout for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 2 | Files: index.html, styles.css

Brief

Build a documentation-style page: header, left sidebar of section links, content and footer, using named grid areas that rearrange at 800px.

Learning goals

- Use grid-template-areas for whole-page layout
- Change the areas in a media query
- Make the sidebar sticky on wide screens

Elements and CSS used

HTML elements	CSS features
div, header, nav, ul, li, a, main, section, footer	grid-template-areas, grid-area, @media (min-width), position: sticky, align-self: start

Build guide

1. Write the four regions inside a .layout div.
2. Give each region a grid-area name.
3. Mobile first: one column, areas stacked.
4. At 800px switch to two columns with side and content side by side.
5. Turn the sidebar link list into a column on desktop.
6. Make the sidebar sticky.

Project 361: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - Guide</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <div class="layout">
    <header class="top"><h1>Oasis Plant Nursery guide</h1></header>
    <nav class="side" aria-label="Sections">
      <ul>
    <li><a href="#sMonstera">Monstera</a></li>
    <li><a href="#sSnake plant">Snake plant</a></li>
    <li><a href="#sBasil pot">Basil pot</a></li>
    <li><a href="#sOlive tree">Olive tree</a></li>
      </ul>
    </nav>
    <main class="content">
      <section id="sMonstera"><h2>Monstera</h2><p>Large leaves, easy
care. Price: 250 EGP.</p></section>
      <section id="sSnake plant"><h2>Snake plant</h2><p>Survives
anything. Price: 120 EGP.</p></section>
      <section id="sBasil pot"><h2>Basil pot</h2><p>Kitchen herb.
Price: 45 EGP.</p></section>
      <section id="sOlive tree"><h2>Olive tree</h2><p>Balcony sized.
Price: 600 EGP.</p></section>
    </main>
    <footer class="bottom">&copy; 2026 Oasis Plant Nursery</footer>
  </div>
</body>
</html>
```

Project 361: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.layout { min-height: 100vh; display: grid; grid-template-rows: auto
1fr auto; grid-template-columns: 1fr; grid-template-areas: "top"
"side" "content" "bottom"; }
.top { grid-area: top; background: var(--brand); color: #fff; padding:
 1rem 1.5rem; }
.top h1 { margin: 0; font-size: 1.3rem; }
```

```
.side { grid-area: side; background: var(--accent); padding: 1rem; }
.side ul { list-style: none; margin: 0; padding: 0; display: flex;
flex-wrap: wrap; gap: .5rem; }
.side a { display: block; padding: .4rem .7rem; border-radius: 6px;
text-decoration: none; color: var(--ink); background: #fff; }
.content { grid-area: content; padding: 1.5rem; max-width: 50rem; }
.bottom { grid-area: bottom; padding: 1rem 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
@media (min-width: 800px) {
  .layout { grid-template-columns: 16rem 1fr; grid-template-areas:
"top top" "side content" "bottom bottom"; }
  .side ul { flex-direction: column; }
  .side { position: sticky; top: 0; align-self: start; height: 100vh;
}
}
```

Project 361 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - Guide</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
	Generic block container for grouping and layout.
<header class="top"> Oasis Plant Nursery guide </header>	Introductory content: logo, title, navigation.
<nav class="side" aria-label="Sections">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Monstera	A hyperlink; href gives the destination.
Snake plant	One list item.
<main class="content">	The unique content of this page; exactly one per page.

Line	What it does
<section id="sMonstera"><h2>Monstera</h2><p>Large leaves, easy care...	A thematic group of content, normally with its own heading.
<section id="sSnake plant"><h2>Snake plant</h2><p>Survives anything...	Second-level heading for a section.
<section id="sBasil pot"><h2>Basil pot</h2><p>Kitchen herb. Price: ...	A paragraph of text.
<footer class="bottom">© 2026 Oasis Plant Nursery</footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.

Declaration	What it does
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
grid-template-areas: "top" "side" "content" "bottom";	Names regions of the grid so children can be placed by name.
grid-area: top;	Places a child into a named area.
background: var(--brand);	Background colour or image.
padding: 1rem 1.5rem;	Space inside the element between its border and content.
font-size: 1.3rem;	Size of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
@media (min-width: 800px) {	Applies from the given width upwards (mobile-first breakpoint).

Declaration	What it does
flex-direction: column;	Stacks flex items vertically.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.

Check your work

- Areas string has equal columns per row
- Anchor links jump to sections
- Sticky sidebar does not cover the footer
- Mobile shows links as a wrapped row

Exercises

1. Highlight the current section link with :target.
2. Add a right column for 'on this page'.
3. Collapse the sidebar with a checkbox toggle.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 362: Sidebar layout for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 2 | Files: index.html, styles.css

Brief

Build a documentation-style page: header, left sidebar of section links, content and footer, using named grid areas that rearrange at 800px.

Learning goals

- Use grid-template-areas for whole-page layout
- Change the areas in a media query
- Make the sidebar sticky on wide screens

Elements and CSS used

HTML elements	CSS features
div, header, nav, ul, li, a, main, section, footer	grid-template-areas, grid-area, @media (min-width), position: sticky, align-self: start

Build guide

1. Write the four regions inside a .layout div.
2. Give each region a grid-area name.
3. Mobile first: one column, areas stacked.
4. At 800px switch to two columns with side and content side by side.
5. Turn the sidebar link list into a column on desktop.
6. Make the sidebar sticky.

Project 362: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - Guide</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <div class="layout">
    <header class="top"><h1>Cedar Furniture guide</h1></header>
    <nav class="side" aria-label="Sections">
      <ul>
    <li><a href="#sOak dining table">Oak dining table</a></li>
    <li><a href="#sBookshelf">Bookshelf</a></li>
    <li><a href="#sBedside table">Bedside table</a></li>
    <li><a href="#sCoffee table">Coffee table</a></li>
      </ul>
    </nav>
    <main class="content">
      <section id="sOak dining table"><h2>Oak dining table</
h2><p>Seats six. Price: 9500 EGP.</p></section>
      <section id="sBookshelf"><h2>Bookshelf</h2><p>Five shelves,
walnut. Price: 4200 EGP.</p></section>
      <section id="sBedside table"><h2>Bedside table</h2><p>One
drawer. Price: 1500 EGP.</p></section>
      <section id="sCoffee table"><h2>Coffee table</h2><p>Round, ash
wood. Price: 2800 EGP.</p></section>
    </main>
    <footer class="bottom">&copy; 2026 Cedar Furniture</footer>
  </div>
</body>
</html>
```

Project 362: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.layout { min-height: 100vh; display: grid; grid-template-rows: auto
1fr auto; grid-template-columns: 1fr; grid-template-areas: "top"
"side" "content" "bottom"; }
.top { grid-area: top; background: var(--brand); color: #fff; padding:
 1rem 1.5rem; }
.top h1 { margin: 0; font-size: 1.3rem; }
```

```
.side { grid-area: side; background: var(--accent); padding: 1rem; }
.side ul { list-style: none; margin: 0; padding: 0; display: flex;
flex-wrap: wrap; gap: .5rem; }
.side a { display: block; padding: .4rem .7rem; border-radius: 6px;
text-decoration: none; color: var(--ink); background: #fff; }
.content { grid-area: content; padding: 1.5rem; max-width: 50rem; }
.bottom { grid-area: bottom; padding: 1rem 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
@media (min-width: 800px) {
  .layout { grid-template-columns: 16rem 1fr; grid-template-areas:
"top top" "side content" "bottom bottom"; }
  .side ul { flex-direction: column; }
  .side { position: sticky; top: 0; align-self: start; height: 100vh;
}
}
```

Project 362 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - Guide</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
	Generic block container for grouping and layout.
<header class="top"> Cedar Furniture guide </header>	Introductory content: logo, title, navigation.
<nav class="side" aria-label="Sections">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Oak dining table	A hyperlink; href gives the destination.
Bookshelf	One list item.

Line	What it does
<main class="content">	The unique content of this page; exactly one per page.
<section id="sOak dining table"><h2>Oak dining table</h2><p>Seats s...	A thematic group of content, normally with its own heading.
<section id="sBookshelf"><h2>Bookshelf</h2><p>Five shelves, walnut....	Second-level heading for a section.
<section id="sBedside table"><h2>Bedside table</h2><p>One drawer. P...	A paragraph of text.
<footer class="bottom">© 2026 Cedar Furniture</footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
grid-template-areas: "top" "side" "content" "bottom";	Names regions of the grid so children can be placed by name.
grid-area: top;	Places a child into a named area.
background: var(--brand);	Background colour or image.
padding: 1rem 1.5rem;	Space inside the element between its border and content.
font-size: 1.3rem;	Size of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Declaration	What it does
@media (min-width: 800px) {	Applies from the given width upwards (mobile-first breakpoint).
flex-direction: column;	Stacks flex items vertically.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.

Check your work

- Areas string has equal columns per row
- Anchor links jump to sections
- Sticky sidebar does not cover the footer
- Mobile shows links as a wrapped row

Exercises

1. Highlight the current section link with :target.
2. Add a right column for 'on this page'.
3. Collapse the sidebar with a checkbox toggle.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 363: Sidebar layout for Byte Repair

Theme: Byte Repair (Nasr City) | Level 2 | Files: index.html, styles.css

Brief

Build a documentation-style page: header, left sidebar of section links, content and footer, using named grid areas that rearrange at 800px.

Learning goals

- Use grid-template-areas for whole-page layout
- Change the areas in a media query
- Make the sidebar sticky on wide screens

Elements and CSS used

HTML elements	CSS features
div, header, nav, ul, li, a, main, section, footer	grid-template-areas, grid-area, @media (min-width), position: sticky, align-self: start

Build guide

1. Write the four regions inside a .layout div.
2. Give each region a grid-area name.
3. Mobile first: one column, areas stacked.
4. At 800px switch to two columns with side and content side by side.
5. Turn the sidebar link list into a column on desktop.
6. Make the sidebar sticky.

Project 363: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - Guide</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <div class="layout">
    <header class="top"><h1>Byte Repair guide</h1></header>
    <nav class="side" aria-label="Sections">
      <ul>
    <li><a href="#sScreen replacement">Screen replacement</a></li>
    <li><a href="#sBattery swap">Battery swap</a></li>
    <li><a href="#sLaptop cleaning">Laptop cleaning</a></li>
    <li><a href="#sData recovery">Data recovery</a></li>
      </ul>
    </nav>
    <main class="content">
      <section id="sScreen replacement"><h2>Screen replacement</
h2><p>Most phones, 1 hour. Price: From 800 EGP.</p></section>
      <section id="sBattery swap"><h2>Battery swap</h2><p>Original
cells. Price: From 500 EGP.</p></section>
      <section id="sLaptop cleaning"><h2>Laptop cleaning</h2><p>Fans
and thermal paste. Price: 350 EGP.</p></section>
      <section id="sData recovery"><h2>Data recovery</h2><p>Drives
and cards. Price: From 1200 EGP.</p></section>
    </main>
    <footer class="bottom">&copy; 2026 Byte Repair</footer>
  </div>
</body>
</html>
```

Project 363: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.layout { min-height: 100vh; display: grid; grid-template-rows: auto
1fr auto; grid-template-columns: 1fr; grid-template-areas: "top"
"side" "content" "bottom"; }
.top { grid-area: top; background: var(--brand); color: #fff; padding:
 1rem 1.5rem; }
.top h1 { margin: 0; font-size: 1.3rem; }
```

```
.side { grid-area: side; background: var(--accent); padding: 1rem; }
.side ul { list-style: none; margin: 0; padding: 0; display: flex;
flex-wrap: wrap; gap: .5rem; }
.side a { display: block; padding: .4rem .7rem; border-radius: 6px;
text-decoration: none; color: var(--ink); background: #fff; }
.content { grid-area: content; padding: 1.5rem; max-width: 50rem; }
.bottom { grid-area: bottom; padding: 1rem 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
@media (min-width: 800px) {
  .layout { grid-template-columns: 16rem 1fr; grid-template-areas:
"top top" "side content" "bottom bottom"; }
  .side ul { flex-direction: column; }
  .side { position: sticky; top: 0; align-self: start; height: 100vh;
}
}
```

Project 363 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - Guide</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
	Generic block container for grouping and layout.
<header class="top"> Byte Repair guide </header>	Introductory content: logo, title, navigation.
<nav class="side" aria-label="Sections">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Screen replacement	A hyperlink; href gives the destination.
Battery swap	One list item.

Line	What it does
<main class="content">	The unique content of this page; exactly one per page.
<section id="sScreen replacement"><h2>Screen replacement</h2><p>Mos...	A thematic group of content, normally with its own heading.
<section id="sBattery swap"><h2>Battery swap</h2><p>Original cells....	Second-level heading for a section.
<section id="sLaptop cleaning"><h2>Laptop cleaning</h2><p>Fans and ...	A paragraph of text.
<footer class="bottom">© 2026 Byte Repair</footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
grid-template-areas: "top" "side" "content" "bottom";	Names regions of the grid so children can be placed by name.
grid-area: top;	Places a child into a named area.
background: var(--brand);	Background colour or image.
padding: 1rem 1.5rem;	Space inside the element between its border and content.
font-size: 1.3rem;	Size of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Declaration	What it does
@media (min-width: 800px) {	Applies from the given width upwards (mobile-first breakpoint).
flex-direction: column;	Stacks flex items vertically.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.

Check your work

- Areas string has equal columns per row
- Anchor links jump to sections
- Sticky sidebar does not cover the footer
- Mobile shows links as a wrapped row

Exercises

1. Highlight the current section link with :target.
2. Add a right column for 'on this page'.
3. Collapse the sidebar with a checkbox toggle.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 364: Sidebar layout for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 2 | Files: index.html, styles.css

Brief

Build a documentation-style page: header, left sidebar of section links, content and footer, using named grid areas that rearrange at 800px.

Learning goals

- Use grid-template-areas for whole-page layout
- Change the areas in a media query
- Make the sidebar sticky on wide screens

Elements and CSS used

HTML elements	CSS features
div, header, nav, ul, li, a, main, section, footer	grid-template-areas, grid-area, @media (min-width), position: sticky, align-self: start

Build guide

1. Write the four regions inside a .layout div.
2. Give each region a grid-area name.
3. Mobile first: one column, areas stacked.
4. At 800px switch to two columns with side and content side by side.
5. Turn the sidebar link list into a column on desktop.
6. Make the sidebar sticky.

Project 364: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - Guide</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <div class="layout">
    <header class="top"><h1>Sahara Pet Care guide</h1></header>
    <nav class="side" aria-label="Sections">
      <ul>
    <li><a href="#sFull grooming">Full grooming</a></li>
    <li><a href="#sDay boarding">Day boarding</a></li>
    <li><a href="#sVaccination">Vaccination</a></li>
    <li><a href="#sDog walking">Dog walking</a></li>
      </ul>
    </nav>
    <main class="content">
      <section id="sFull grooming"><h2>Full grooming</h2><p>Bath, cut
and nails. Price: 400 EGP.</p></section>
      <section id="sDay boarding"><h2>Day boarding</h2><p>Play and
rest. Price: 250 EGP.</p></section>
      <section id="sVaccination"><h2>Vaccination</h2><p>Annual
boosters. Price: 300 EGP.</p></section>
      <section id="sDog walking"><h2>Dog walking</h2><p>30 minutes.
Price: 100 EGP.</p></section>
    </main>
    <footer class="bottom">&copy; 2026 Sahara Pet Care</footer>
  </div>
</body>
</html>
```

Project 364: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.layout { min-height: 100vh; display: grid; grid-template-rows: auto
1fr auto; grid-template-columns: 1fr; grid-template-areas: "top"
"side" "content" "bottom"; }
.top { grid-area: top; background: var(--brand); color: #fff; padding:
 1rem 1.5rem; }
.top h1 { margin: 0; font-size: 1.3rem; }
```

```
.side { grid-area: side; background: var(--accent); padding: 1rem; }
.side ul { list-style: none; margin: 0; padding: 0; display: flex;
flex-wrap: wrap; gap: .5rem; }
.side a { display: block; padding: .4rem .7rem; border-radius: 6px;
text-decoration: none; color: var(--ink); background: #fff; }
.content { grid-area: content; padding: 1.5rem; max-width: 50rem; }
.bottom { grid-area: bottom; padding: 1rem 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
@media (min-width: 800px) {
  .layout { grid-template-columns: 16rem 1fr; grid-template-areas:
"top top" "side content" "bottom bottom"; }
  .side ul { flex-direction: column; }
  .side { position: sticky; top: 0; align-self: start; height: 100vh;
}
}
```

Project 364 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - Guide</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
	Generic block container for grouping and layout.
<header class="top"> Sahara Pet Care guide </header>	Introductory content: logo, title, navigation.
<nav class="side" aria-label="Sections">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Full grooming	A hyperlink; href gives the destination.
Day boarding	One list item.

Line	What it does
<main class="content">	The unique content of this page; exactly one per page.
<section id="sFull grooming"><h2>Full grooming</h2><p>Bath, cut and...	A thematic group of content, normally with its own heading.
<section id="sDay boarding"><h2>Day boarding</h2><p>Play and rest. ...	Second-level heading for a section.
<section id="sVaccination"><h2>Vaccination</h2><p>Annual boosters. ...	A paragraph of text.
<footer class="bottom">© 2026 Sahara Pet Care</footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
grid-template-areas: "top" "side" "content" "bottom";	Names regions of the grid so children can be placed by name.
grid-area: top;	Places a child into a named area.
background: var(--brand);	Background colour or image.
padding: 1rem 1.5rem;	Space inside the element between its border and content.
font-size: 1.3rem;	Size of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Declaration	What it does
@media (min-width: 800px) {	Applies from the given width upwards (mobile-first breakpoint).
flex-direction: column;	Stacks flex items vertically.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.

Check your work

- Areas string has equal columns per row
- Anchor links jump to sections
- Sticky sidebar does not cover the footer
- Mobile shows links as a wrapped row

Exercises

1. Highlight the current section link with :target.
2. Add a right column for 'on this page'.
3. Collapse the sidebar with a checkbox toggle.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 365: Sidebar layout for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Build a documentation-style page: header, left sidebar of section links, content and footer, using named grid areas that rearrange at 800px.

Learning goals

- Use grid-template-areas for whole-page layout
- Change the areas in a media query
- Make the sidebar sticky on wide screens

Elements and CSS used

HTML elements	CSS features
div, header, nav, ul, li, a, main, section, footer	grid-template-areas, grid-area, @media (min-width), position: sticky, align-self: start

Build guide

1. Write the four regions inside a .layout div.
2. Give each region a grid-area name.
3. Mobile first: one column, areas stacked.
4. At 800px switch to two columns with side and content side by side.
5. Turn the sidebar link list into a column on desktop.
6. Make the sidebar sticky.

Project 365: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - Guide</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <div class="layout">
    <header class="top"><h1>Alexandria Sailing School guide</h1></
header>
    <nav class="side" aria-label="Sections">
      <ul>
    <li><a href="#sTaster session">Taster session</a></li>
    <li><a href="#sBeginner course">Beginner course</a></li>
    <li><a href="#sRacing clinic">Racing clinic</a></li>
    <li><a href="#sPrivate lesson">Private lesson</a></li>
      </ul>
    </nav>
    <main class="content">
      <section id="sTaster session"><h2>Taster session</h2><p>Two
hours on the water. Price: 500 EGP.</p></section>
      <section id="sBeginner course"><h2>Beginner course</h2><p>Five
sessions. Price: 2200 EGP.</p></section>
      <section id="sRacing clinic"><h2>Racing clinic</h2><p>Tactics
and trim. Price: 1800 EGP.</p></section>
      <section id="sPrivate lesson"><h2>Private lesson</h2><p>One to
one. Price: 900 EGP.</p></section>
    </main>
    <footer class="bottom">&copy; 2026 Alexandria Sailing School</
footer>
  </div>
</body>
</html>
```

Project 365: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.layout { min-height: 100vh; display: grid; grid-template-rows: auto
1fr auto; grid-template-columns: 1fr; grid-template-areas: "top"
"side" "content" "bottom"; }
.top { grid-area: top; background: var(--brand); color: #fff; padding:
```

```
 1rem 1.5rem; }
.top h1 { margin: 0; font-size: 1.3rem; }
.side { grid-area: side; background: var(--accent); padding: 1rem; }
.side ul { list-style: none; margin: 0; padding: 0; display: flex;
flex-wrap: wrap; gap: .5rem; }
.side a { display: block; padding: .4rem .7rem; border-radius: 6px;
text-decoration: none; color: var(--ink); background: #fff; }
.content { grid-area: content; padding: 1.5rem; max-width: 50rem; }
.bottom { grid-area: bottom; padding: 1rem 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
@media (min-width: 800px) {
  .layout { grid-template-columns: 16rem 1fr; grid-template-areas:
"top top" "side content" "bottom bottom"; }
  .side ul { flex-direction: column; }
  .side { position: sticky; top: 0; align-self: start; height: 100vh;
}
}
```

Project 365 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - Guide</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
	Generic block container for grouping and layout.
<header class="top"> Alexandria Sailing School guide </header>	Introductory content: logo, title, navigation.
<nav class="side" aria-label="Sections">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Taster session	A hyperlink; href gives the destination.
Beginner course	One list item.

Line	What it does
<main class="content">	The unique content of this page; exactly one per page.
<section id="sTaster session"><h2>Taster session</h2><p>Two hours o...	A thematic group of content, normally with its own heading.
<section id="sBeginner course"><h2>Beginner course</h2><p>Five sess...	Second-level heading for a section.
<section id="sRacing clinic"><h2>Racing clinic</h2><p>Tactics and t...	A paragraph of text.
<footer class="bottom">© 2026 Alexandria Sailing School</footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
grid-template-areas: "top" "side" "content" "bottom";	Names regions of the grid so children can be placed by name.
grid-area: top;	Places a child into a named area.
background: var(--brand);	Background colour or image.
padding: 1rem 1.5rem;	Space inside the element between its border and content.
font-size: 1.3rem;	Size of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Declaration	What it does
@media (min-width: 800px) {	Applies from the given width upwards (mobile-first breakpoint).
flex-direction: column;	Stacks flex items vertically.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.

Check your work

- Areas string has equal columns per row
- Anchor links jump to sections
- Sticky sidebar does not cover the footer
- Mobile shows links as a wrapped row

Exercises

1. Highlight the current section link with :target.
2. Add a right column for 'on this page'.
3. Collapse the sidebar with a checkbox toggle.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 366: Sidebar layout for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Build a documentation-style page: header, left sidebar of section links, content and footer, using named grid areas that rearrange at 800px.

Learning goals

- Use grid-template-areas for whole-page layout
- Change the areas in a media query
- Make the sidebar sticky on wide screens

Elements and CSS used

HTML elements	CSS features
div, header, nav, ul, li, a, main, section, footer	grid-template-areas, grid-area, @media (min-width), position: sticky, align-self: start

Build guide

1. Write the four regions inside a .layout div.
2. Give each region a grid-area name.
3. Mobile first: one column, areas stacked.
4. At 800px switch to two columns with side and content side by side.
5. Turn the sidebar link list into a column on desktop.
6. Make the sidebar sticky.

Project 366: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - Guide</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <div class="layout">
    <header class="top"><h1>Habiba Handmade Jewellery guide</h1></
header>
    <nav class="side" aria-label="Sections">
      <ul>
    <li><a href="#sLotus pendant">Lotus pendant</a></li>
    <li><a href="#sBrass cuff">Brass cuff</a></li>
    <li><a href="#sBead earrings">Bead earrings</a></li>
    <li><a href="#sAnkh ring">Ankh ring</a></li>
      </ul>
    </nav>
    <main class="content">
      <section id="sLotus pendant"><h2>Lotus pendant</h2><p>Sterling
silver. Price: 650 EGP.</p></section>
      <section id="sBrass cuff"><h2>Brass cuff</h2><p>Hand engraved.
Price: 420 EGP.</p></section>
      <section id="sBead earrings"><h2>Bead earrings</h2><p>Recycled
glass. Price: 180 EGP.</p></section>
      <section id="sAnkh ring"><h2>Ankh ring</h2><p>Adjustable. Price:
 300 EGP.</p></section>
    </main>
    <footer class="bottom">&copy; 2026 Habiba Handmade Jewellery</
footer>
  </div>
</body>
</html>
```

Project 366: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.layout { min-height: 100vh; display: grid; grid-template-rows: auto
1fr auto; grid-template-columns: 1fr; grid-template-areas: "top"
"side" "content" "bottom"; }
.top { grid-area: top; background: var(--brand); color: #fff; padding:
```

```
 1rem 1.5rem; }
.top h1 { margin: 0; font-size: 1.3rem; }
.side { grid-area: side; background: var(--accent); padding: 1rem; }
.side ul { list-style: none; margin: 0; padding: 0; display: flex;
flex-wrap: wrap; gap: .5rem; }
.side a { display: block; padding: .4rem .7rem; border-radius: 6px;
text-decoration: none; color: var(--ink); background: #fff; }
.content { grid-area: content; padding: 1.5rem; max-width: 50rem; }
.bottom { grid-area: bottom; padding: 1rem 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
@media (min-width: 800px) {
  .layout { grid-template-columns: 16rem 1fr; grid-template-areas:
"top top" "side content" "bottom bottom"; }
  .side ul { flex-direction: column; }
  .side { position: sticky; top: 0; align-self: start; height: 100vh;
}
}
```

Project 366 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - Guide</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
	Generic block container for grouping and layout.
<header class="top"> Habiba Handmade Jewellery guide </header>	Introductory content: logo, title, navigation.
<nav class="side" aria-label="Sections">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Lotus pendant	A hyperlink; href gives the destination.
Brass cuff	One list item.

Line	What it does
<main class="content">	The unique content of this page; exactly one per page.
<section id="sLotus pendant"><h2>Lotus pendant</h2><p>Sterling silv...	A thematic group of content, normally with its own heading.
<section id="sBrass cuff"><h2>Brass cuff</h2><p>Hand engraved. Pric...	Second-level heading for a section.
<section id="sBead earrings"><h2>Bead earrings</h2><p>Recycled glas...	A paragraph of text.
<footer class="bottom">© 2026 Habiba Handmade Jewellery</footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.

Declaration	What it does
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
grid-template-areas: "top" "side" "content" "bottom";	Names regions of the grid so children can be placed by name.
grid-area: top;	Places a child into a named area.
background: var(--brand);	Background colour or image.
padding: 1rem 1.5rem;	Space inside the element between its border and content.
font-size: 1.3rem;	Size of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
border-top: 1px solid var(--line);	A top border used as an accent or separator.
@media (min-width: 800px) {	Applies from the given width upwards (mobile-first breakpoint).
flex-direction: column;	Stacks flex items vertically.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.

Check your work

- Areas string has equal columns per row
- Anchor links jump to sections
- Sticky sidebar does not cover the footer
- Mobile shows links as a wrapped row

Exercises

1. Highlight the current section link with :target.
2. Add a right column for 'on this page'.
3. Collapse the sidebar with a checkbox toggle.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8

Field	Value
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 367: Sidebar layout for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 2 | Files: index.html, styles.css

Brief

Build a documentation-style page: header, left sidebar of section links, content and footer, using named grid areas that rearrange at 800px.

Learning goals

- Use grid-template-areas for whole-page layout
- Change the areas in a media query
- Make the sidebar sticky on wide screens

Elements and CSS used

HTML elements	CSS features
div, header, nav, ul, li, a, main, section, footer	grid-template-areas, grid-area, @media (min-width), position: sticky, align-self: start

Build guide

1. Write the four regions inside a .layout div.
2. Give each region a grid-area name.
3. Mobile first: one column, areas stacked.
4. At 800px switch to two columns with side and content side by side.
5. Turn the sidebar link list into a column on desktop.
6. Make the sidebar sticky.

Project 367: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - Guide</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <div class="layout">
    <header class="top"><h1>Fayoum Pottery Studio guide</h1></header>
    <nav class="side" aria-label="Sections">
      <ul>
    <li><a href="#sIntro to the wheel">Intro to the wheel</a></li>
    <li><a href="#sGlazing day">Glazing day</a></li>
    <li><a href="#sKids clay class">Kids clay class</a></li>
    <li><a href="#sWeekend retreat">Weekend retreat</a></li>
      </ul>
    </nav>
    <main class="content">
      <section id="sIntro to the wheel"><h2>Intro to the wheel</
h2><p>Three hours, take home a bowl. Price: 450 EGP.</p></section>
      <section id="sGlazing day"><h2>Glazing day</h2><p>Colour your
pieces. Price: 300 EGP.</p></section>
      <section id="sKids clay class"><h2>Kids clay class</h2><p>Ages
6 to 12. Price: 200 EGP.</p></section>
      <section id="sWeekend retreat"><h2>Weekend retreat</h2><p>Two
days with meals. Price: 2500 EGP.</p></section>
    </main>
    <footer class="bottom">&copy; 2026 Fayoum Pottery Studio</footer>
  </div>
</body>
</html>
```

Project 367: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.layout { min-height: 100vh; display: grid; grid-template-rows: auto
1fr auto; grid-template-columns: 1fr; grid-template-areas: "top"
"side" "content" "bottom"; }
.top { grid-area: top; background: var(--brand); color: #fff; padding:
 1rem 1.5rem; }
.top h1 { margin: 0; font-size: 1.3rem; }
```

```
.side { grid-area: side; background: var(--accent); padding: 1rem; }
.side ul { list-style: none; margin: 0; padding: 0; display: flex;
flex-wrap: wrap; gap: .5rem; }
.side a { display: block; padding: .4rem .7rem; border-radius: 6px;
text-decoration: none; color: var(--ink); background: #fff; }
.content { grid-area: content; padding: 1.5rem; max-width: 50rem; }
.bottom { grid-area: bottom; padding: 1rem 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
@media (min-width: 800px) {
  .layout { grid-template-columns: 16rem 1fr; grid-template-areas:
"top top" "side content" "bottom bottom"; }
  .side ul { flex-direction: column; }
  .side { position: sticky; top: 0; align-self: start; height: 100vh;
}
}
```

Project 367 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - Guide</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
	Generic block container for grouping and layout.
<header class="top"> Fayoum Pottery Studio guide </header>	Introductory content: logo, title, navigation.
<nav class="side" aria-label="Sections">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Intro to the wheel	A hyperlink; href gives the destination.
Glazing day	One list item.

Line	What it does
<main class="content">	The unique content of this page; exactly one per page.
<section id="sIntro to the wheel"><h2>Intro to the wheel</h2><p>Thr...	A thematic group of content, normally with its own heading.
<section id="sGlazing day"><h2>Glazing day</h2><p>Colour your piece...	Second-level heading for a section.
<section id="sKids clay class"><h2>Kids clay class</h2><p>Ages 6 to...	A paragraph of text.
<footer class="bottom">© 2026 Fayoum Pottery Studio</footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
grid-template-areas: "top" "side" "content" "bottom";	Names regions of the grid so children can be placed by name.
grid-area: top;	Places a child into a named area.
background: var(--brand);	Background colour or image.
padding: 1rem 1.5rem;	Space inside the element between its border and content.
font-size: 1.3rem;	Size of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Declaration	What it does
@media (min-width: 800px) {	Applies from the given width upwards (mobile-first breakpoint).
flex-direction: column;	Stacks flex items vertically.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.

Check your work

- Areas string has equal columns per row
- Anchor links jump to sections
- Sticky sidebar does not cover the footer
- Mobile shows links as a wrapped row

Exercises

1. Highlight the current section link with :target.
2. Add a right column for 'on this page'.
3. Collapse the sidebar with a checkbox toggle.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 368: Sidebar layout for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 2 | Files: index.html, styles.css

Brief

Build a documentation-style page: header, left sidebar of section links, content and footer, using named grid areas that rearrange at 800px.

Learning goals

- Use grid-template-areas for whole-page layout
- Change the areas in a media query
- Make the sidebar sticky on wide screens

Elements and CSS used

HTML elements	CSS features
div, header, nav, ul, li, a, main, section, footer	grid-template-areas, grid-area, @media (min-width), position: sticky, align-self: start

Build guide

1. Write the four regions inside a .layout div.
2. Give each region a grid-area name.
3. Mobile first: one column, areas stacked.
4. At 800px switch to two columns with side and content side by side.
5. Turn the sidebar link list into a column on desktop.
6. Make the sidebar sticky.

Project 368: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - Guide</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <div class="layout">
    <header class="top"><h1>Cleopatra Beauty Salon guide</h1></header>
    <nav class="side" aria-label="Sections">
      <ul>
    <li><a href="#sHaircut and blow-dry">Haircut and blow-dry</a></li>
    <li><a href="#sManicure">Manicure</a></li>
    <li><a href="#sFacial">Facial</a></li>
    <li><a href="#sBridal package">Bridal package</a></li>
      </ul>
    </nav>
    <main class="content">
      <section id="sHaircut and blow-dry"><h2>Haircut and blow-dry</
h2><p>Consultation included. Price: 350 EGP.</p></section>
      <section id="sManicure"><h2>Manicure</h2><p>Classic or gel.
Price: 200 EGP.</p></section>
      <section id="sFacial"><h2>Facial</h2><p>Deep cleanse, 60
minutes. Price: 600 EGP.</p></section>
      <section id="sBridal package"><h2>Bridal package</h2><p>Hair,
make-up and nails. Price: 4500 EGP.</p></section>
    </main>
    <footer class="bottom">&copy; 2026 Cleopatra Beauty Salon</footer>
  </div>
</body>
</html>
```

Project 368: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.layout { min-height: 100vh; display: grid; grid-template-rows: auto
1fr auto; grid-template-columns: 1fr; grid-template-areas: "top"
"side" "content" "bottom"; }
.top { grid-area: top; background: var(--brand); color: #fff; padding:
 1rem 1.5rem; }
.top h1 { margin: 0; font-size: 1.3rem; }
```

```
.side { grid-area: side; background: var(--accent); padding: 1rem; }
.side ul { list-style: none; margin: 0; padding: 0; display: flex;
flex-wrap: wrap; gap: .5rem; }
.side a { display: block; padding: .4rem .7rem; border-radius: 6px;
text-decoration: none; color: var(--ink); background: #fff; }
.content { grid-area: content; padding: 1.5rem; max-width: 50rem; }
.bottom { grid-area: bottom; padding: 1rem 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
@media (min-width: 800px) {
  .layout { grid-template-columns: 16rem 1fr; grid-template-areas:
"top top" "side content" "bottom bottom"; }
  .side ul { flex-direction: column; }
  .side { position: sticky; top: 0; align-self: start; height: 100vh;
}
}
```

Project 368 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - Guide</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
	Generic block container for grouping and layout.
<header class="top"> Cleopatra Beauty Salon guide </header>	Introductory content: logo, title, navigation.
<nav class="side" aria-label="Sections">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Haircut and blow-dry	A hyperlink; href gives the destination.
Manicure	One list item.

Line	What it does
<main class="content">	The unique content of this page; exactly one per page.
<section id="sHaircut and blow-dry"> Haircut and blow-dry <p...	A thematic group of content, normally with its own heading.
<section id="sManicure"><h2>Manicure</h2><p>Classic or gel. Price: ...	Second-level heading for a section.
<section id="sFacial"><h2>Facial</h2><p>Deep cleanse, 60 minutes. P...	A paragraph of text.
<footer class="bottom">© 2026 Cleopatra Beauty Salon</footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
grid-template-areas: "top" "side" "content" "bottom";	Names regions of the grid so children can be placed by name.
grid-area: top;	Places a child into a named area.
background: var(--brand);	Background colour or image.
padding: 1rem 1.5rem;	Space inside the element between its border and content.
font-size: 1.3rem;	Size of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Declaration	What it does
@media (min-width: 800px) {	Applies from the given width upwards (mobile-first breakpoint).
flex-direction: column;	Stacks flex items vertically.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.

Check your work

- Areas string has equal columns per row
- Anchor links jump to sections
- Sticky sidebar does not cover the footer
- Mobile shows links as a wrapped row

Exercises

1. Highlight the current section link with :target.
2. Add a right column for 'on this page'.
3. Collapse the sidebar with a checkbox toggle.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 369: Sidebar layout for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 2 | Files: index.html, styles.css

Brief

Build a documentation-style page: header, left sidebar of section links, content and footer, using named grid areas that rearrange at 800px.

Learning goals

- Use grid-template-areas for whole-page layout
- Change the areas in a media query
- Make the sidebar sticky on wide screens

Elements and CSS used

HTML elements	CSS features
div, header, nav, ul, li, a, main, section, footer	grid-template-areas, grid-area, @media (min-width), position: sticky, align-self: start

Build guide

1. Write the four regions inside a .layout div.
2. Give each region a grid-area name.
3. Mobile first: one column, areas stacked.
4. At 800px switch to two columns with side and content side by side.
5. Turn the sidebar link list into a column on desktop.
6. Make the sidebar sticky.

Project 369: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - Guide</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <div class="layout">
    <header class="top"><h1>Suez Auto Service guide</h1></header>
    <nav class="side" aria-label="Sections">
      <ul>
    <li><a href="#sOil change">Oil change</a></li>
    <li><a href="#sBrake pads">Brake pads</a></li>
    <li><a href="#sAir conditioning">Air conditioning</a></li>
    <li><a href="#sPre-purchase inspection">Pre-purchase inspection</
a></li>
      </ul>
    </nav>
    <main class="content">
      <section id="sOil change"><h2>Oil change</h2><p>Filter included.
 Price: 600 EGP.</p></section>
      <section id="sBrake pads"><h2>Brake pads</h2><p>Front axle.
Price: 1400 EGP.</p></section>
      <section id="sAir conditioning"><h2>Air conditioning</
h2><p>Recharge and check. Price: 900 EGP.</p></section>
      <section id="sPre-purchase inspection"><h2>Pre-purchase
inspection</h2><p>120 point check. Price: 750 EGP.</p></section>
    </main>
    <footer class="bottom">&copy; 2026 Suez Auto Service</footer>
  </div>
</body>
</html>
```

Project 369: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.layout { min-height: 100vh; display: grid; grid-template-rows: auto
1fr auto; grid-template-columns: 1fr; grid-template-areas: "top"
"side" "content" "bottom"; }
.top { grid-area: top; background: var(--brand); color: #fff; padding:
 1rem 1.5rem; }
```

```
.top h1 { margin: 0; font-size: 1.3rem; }
.side { grid-area: side; background: var(--accent); padding: 1rem; }
.side ul { list-style: none; margin: 0; padding: 0; display: flex;
flex-wrap: wrap; gap: .5rem; }
.side a { display: block; padding: .4rem .7rem; border-radius: 6px;
text-decoration: none; color: var(--ink); background: #fff; }
.content { grid-area: content; padding: 1.5rem; max-width: 50rem; }
.bottom { grid-area: bottom; padding: 1rem 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
@media (min-width: 800px) {
  .layout { grid-template-columns: 16rem 1fr; grid-template-areas:
"top top" "side content" "bottom bottom"; }
  .side ul { flex-direction: column; }
  .side { position: sticky; top: 0; align-self: start; height: 100vh;
}
}
```

Project 369 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - Guide</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
	Generic block container for grouping and layout.
<header class="top"> Suez Auto Service guide </header>	Introductory content: logo, title, navigation.
<nav class="side" aria-label="Sections">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Oil change	A hyperlink; href gives the destination.
Brake pads	One list item.
<main class="content">	The unique content of this page; exactly one per page.

Line	What it does
<section id="sOil change"><h2>Oil change</h2><p>Filter included. Pr...	A thematic group of content, normally with its own heading.
<section id="sBrake pads"><h2>Brake pads</h2><p>Front axle. Price: ...	Second-level heading for a section.
<section id="sAir conditioning"><h2>Air conditioning</h2><p>Recharg...	A paragraph of text.
<footer class="bottom">© 2026 Suez Auto Service</footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.

Declaration	What it does
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
grid-template-areas: "top" "side" "content" "bottom";	Names regions of the grid so children can be placed by name.
grid-area: top;	Places a child into a named area.
background: var(--brand);	Background colour or image.
padding: 1rem 1.5rem;	Space inside the element between its border and content.
font-size: 1.3rem;	Size of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
@media (min-width: 800px) {	Applies from the given width upwards (mobile-first breakpoint).

Declaration	What it does
flex-direction: column;	Stacks flex items vertically.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.

Check your work

- Areas string has equal columns per row
- Anchor links jump to sections
- Sticky sidebar does not cover the footer
- Mobile shows links as a wrapped row

Exercises

1. Highlight the current section link with :target.
2. Add a right column for 'on this page'.
3. Collapse the sidebar with a checkbox toggle.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 370: Sidebar layout for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 2 | Files: index.html, styles.css

Brief

Build a documentation-style page: header, left sidebar of section links, content and footer, using named grid areas that rearrange at 800px.

Learning goals

- Use grid-template-areas for whole-page layout
- Change the areas in a media query
- Make the sidebar sticky on wide screens

Elements and CSS used

HTML elements	CSS features
div, header, nav, ul, li, a, main, section, footer	grid-template-areas, grid-area, @media (min-width), position: sticky, align-self: start

Build guide

1. Write the four regions inside a .layout div.
2. Give each region a grid-area name.
3. Mobile first: one column, areas stacked.
4. At 800px switch to two columns with side and content side by side.
5. Turn the sidebar link list into a column on desktop.
6. Make the sidebar sticky.

Project 370: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - Guide</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <div class="layout">
    <header class="top"><h1>Luxor Music Academy guide</h1></header>
    <nav class="side" aria-label="Sections">
      <ul>
    <li><a href="#sOud for beginners">Oud for beginners</a></li>
    <li><a href="#sPiano grade 1">Piano grade 1</a></li>
    <li><a href="#sGuitar chords">Guitar chords</a></li>
    <li><a href="#sVoice coaching">Voice coaching</a></li>
      </ul>
    </nav>
    <main class="content">
      <section id="sOud for beginners"><h2>Oud for beginners</
h2><p>Eight weekly lessons. Price: 1600 EGP.</p></section>
      <section id="sPiano grade 1"><h2>Piano grade 1</h2><p>Theory
and practice. Price: 1800 EGP.</p></section>
      <section id="sGuitar chords"><h2>Guitar chords</h2><p>Play
songs in a month. Price: 1400 EGP.</p></section>
      <section id="sVoice coaching"><h2>Voice coaching</
h2><p>Breathing and range. Price: 1500 EGP.</p></section>
    </main>
    <footer class="bottom">&copy; 2026 Luxor Music Academy</footer>
  </div>
</body>
</html>
```

Project 370: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.layout { min-height: 100vh; display: grid; grid-template-rows: auto
1fr auto; grid-template-columns: 1fr; grid-template-areas: "top"
"side" "content" "bottom"; }
.top { grid-area: top; background: var(--brand); color: #fff; padding:
 1rem 1.5rem; }
.top h1 { margin: 0; font-size: 1.3rem; }
```

```
.side { grid-area: side; background: var(--accent); padding: 1rem; }
.side ul { list-style: none; margin: 0; padding: 0; display: flex;
flex-wrap: wrap; gap: .5rem; }
.side a { display: block; padding: .4rem .7rem; border-radius: 6px;
text-decoration: none; color: var(--ink); background: #fff; }
.content { grid-area: content; padding: 1.5rem; max-width: 50rem; }
.bottom { grid-area: bottom; padding: 1rem 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
@media (min-width: 800px) {
  .layout { grid-template-columns: 16rem 1fr; grid-template-areas:
"top top" "side content" "bottom bottom"; }
  .side ul { flex-direction: column; }
  .side { position: sticky; top: 0; align-self: start; height: 100vh;
}
}
```

Project 370 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - Guide</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
	Generic block container for grouping and layout.
<header class="top"> Luxor Music Academy guide </header>	Introductory content: logo, title, navigation.
<nav class="side" aria-label="Sections">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Oud for beginners	A hyperlink; href gives the destination.
Piano grade 1	One list item.

Line	What it does
<main class="content">	The unique content of this page; exactly one per page.
<section id="sOud for beginners"><h2>Oud for beginners</h2><p>Eight...	A thematic group of content, normally with its own heading.
<section id="sPiano grade 1"><h2>Piano grade 1</h2><p>Theory and pr...	Second-level heading for a section.
<section id="sGuitar chords"><h2>Guitar chords</h2><p>Play songs in...	A paragraph of text.
<footer class="bottom">© 2026 Luxor Music Academy</footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
grid-template-areas: "top" "side" "content" "bottom";	Names regions of the grid so children can be placed by name.
grid-area: top;	Places a child into a named area.
background: var(--brand);	Background colour or image.
padding: 1rem 1.5rem;	Space inside the element between its border and content.
font-size: 1.3rem;	Size of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Declaration	What it does
@media (min-width: 800px) {	Applies from the given width upwards (mobile-first breakpoint).
flex-direction: column;	Stacks flex items vertically.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.

Check your work

- Areas string has equal columns per row
- Anchor links jump to sections
- Sticky sidebar does not cover the footer
- Mobile shows links as a wrapped row

Exercises

1. Highlight the current section link with :target.
2. Add a right column for 'on this page'.
3. Collapse the sidebar with a checkbox toggle.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 371: Sidebar layout for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 2 | Files: index.html, styles.css

Brief

Build a documentation-style page: header, left sidebar of section links, content and footer, using named grid areas that rearrange at 800px.

Learning goals

- Use grid-template-areas for whole-page layout
- Change the areas in a media query
- Make the sidebar sticky on wide screens

Elements and CSS used

HTML elements	CSS features
div, header, nav, ul, li, a, main, section, footer	grid-template-areas, grid-area, @media (min-width), position: sticky, align-self: start

Build guide

1. Write the four regions inside a .layout div.
2. Give each region a grid-area name.
3. Mobile first: one column, areas stacked.
4. At 800px switch to two columns with side and content side by side.
5. Turn the sidebar link list into a column on desktop.
6. Make the sidebar sticky.

Project 371: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - Guide</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <div class="layout">
    <header class="top"><h1>Port Said Seafood guide</h1></header>
    <nav class="side" aria-label="Sections">
      <ul>
    <li><a href="#sGrilled sea bass">Grilled sea bass</a></li>
    <li><a href="#sShrimp tagine">Shrimp tagine</a></li>
    <li><a href="#sCalamari">Calamari</a></li>
    <li><a href="#sFish soup">Fish soup</a></li>
      </ul>
    </nav>
    <main class="content">
      <section id="sGrilled sea bass"><h2>Grilled sea bass</
h2><p>With rice and salad. Price: 320 EGP.</p></section>
      <section id="sShrimp tagine"><h2>Shrimp tagine</h2><p>Tomato
and garlic. Price: 280 EGP.</p></section>
      <section id="sCalamari"><h2>Calamari</h2><p>Fried, with tahini.
Price: 190 EGP.</p></section>
      <section id="sFish soup"><h2>Fish soup</h2><p>Daily catch.
Price: 120 EGP.</p></section>
    </main>
    <footer class="bottom">&copy; 2026 Port Said Seafood</footer>
  </div>
</body>
</html>
```

Project 371: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.layout { min-height: 100vh; display: grid; grid-template-rows: auto
1fr auto; grid-template-columns: 1fr; grid-template-areas: "top"
"side" "content" "bottom"; }
.top { grid-area: top; background: var(--brand); color: #fff; padding:
 1rem 1.5rem; }
.top h1 { margin: 0; font-size: 1.3rem; }
```

```
.side { grid-area: side; background: var(--accent); padding: 1rem; }
.side ul { list-style: none; margin: 0; padding: 0; display: flex;
flex-wrap: wrap; gap: .5rem; }
.side a { display: block; padding: .4rem .7rem; border-radius: 6px;
text-decoration: none; color: var(--ink); background: #fff; }
.content { grid-area: content; padding: 1.5rem; max-width: 50rem; }
.bottom { grid-area: bottom; padding: 1rem 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
@media (min-width: 800px) {
  .layout { grid-template-columns: 16rem 1fr; grid-template-areas:
"top top" "side content" "bottom bottom"; }
  .side ul { flex-direction: column; }
  .side { position: sticky; top: 0; align-self: start; height: 100vh;
}
}
```

Project 371 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - Guide</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
	Generic block container for grouping and layout.
<header class="top"> Port Said Seafood guide </header>	Introductory content: logo, title, navigation.
<nav class="side" aria-label="Sections">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Grilled sea bass	A hyperlink; href gives the destination.
Shrimp tagine	One list item.

Line	What it does
<main class="content">	The unique content of this page; exactly one per page.
<section id="sGrilled sea bass"><h2>Grilled sea bass</h2><p>With ri...	A thematic group of content, normally with its own heading.
<section id="sShrimp tagine"><h2>Shrimp tagine</h2><p>Tomato and ga...	Second-level heading for a section.
<section id="sCalamari"><h2>Calamari</h2><p>Fried, with tahini. Pri...	A paragraph of text.
<footer class="bottom">© 2026 Port Said Seafood</footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
grid-template-areas: "top" "side" "content" "bottom";	Names regions of the grid so children can be placed by name.
grid-area: top;	Places a child into a named area.
background: var(--brand);	Background colour or image.
padding: 1rem 1.5rem;	Space inside the element between its border and content.
font-size: 1.3rem;	Size of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Declaration	What it does
@media (min-width: 800px) {	Applies from the given width upwards (mobile-first breakpoint).
flex-direction: column;	Stacks flex items vertically.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.

Check your work

- Areas string has equal columns per row
- Anchor links jump to sections
- Sticky sidebar does not cover the footer
- Mobile shows links as a wrapped row

Exercises

1. Highlight the current section link with :target.
2. Add a right column for 'on this page'.
3. Collapse the sidebar with a checkbox toggle.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 372: Sidebar layout for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 2 | Files: index.html, styles.css

Brief

Build a documentation-style page: header, left sidebar of section links, content and footer, using named grid areas that rearrange at 800px.

Learning goals

- Use grid-template-areas for whole-page layout
- Change the areas in a media query
- Make the sidebar sticky on wide screens

Elements and CSS used

HTML elements	CSS features
div, header, nav, ul, li, a, main, section, footer	grid-template-areas, grid-area, @media (min-width), position: sticky, align-self: start

Build guide

1. Write the four regions inside a .layout div.
2. Give each region a grid-area name.
3. Mobile first: one column, areas stacked.
4. At 800px switch to two columns with side and content side by side.
5. Turn the sidebar link list into a column on desktop.
6. Make the sidebar sticky.

Project 372: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - Guide</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <div class="layout">
    <header class="top"><h1>Delta Kids Library guide</h1></header>
    <nav class="side" aria-label="Sections">
      <ul>
    <li><a href="#sStory hour">Story hour</a></li>
    <li><a href="#sReading club">Reading club</a></li>
    <li><a href="#sHomework help">Homework help</a></li>
    <li><a href="#sSummer challenge">Summer challenge</a></li>
      </ul>
    </nav>
    <main class="content">
      <section id="sStory hour"><h2>Story hour</h2><p>Ages 3 to 6,
Saturdays. Price: Free.</p></section>
      <section id="sReading club"><h2>Reading club</h2><p>Ages 7 to
11. Price: 50 EGP per month.</p></section>
      <section id="sHomework help"><h2>Homework help</h2><p>Weekday
afternoons. Price: Free.</p></section>
      <section id="sSummer challenge"><h2>Summer challenge</
h2><p>Read ten books. Price: Free.</p></section>
    </main>
    <footer class="bottom">&copy; 2026 Delta Kids Library</footer>
  </div>
</body>
</html>
```

Project 372: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.layout { min-height: 100vh; display: grid; grid-template-rows: auto
1fr auto; grid-template-columns: 1fr; grid-template-areas: "top"
"side" "content" "bottom"; }
.top { grid-area: top; background: var(--brand); color: #fff; padding:
 1rem 1.5rem; }
.top h1 { margin: 0; font-size: 1.3rem; }
```

```
.side { grid-area: side; background: var(--accent); padding: 1rem; }
.side ul { list-style: none; margin: 0; padding: 0; display: flex;
flex-wrap: wrap; gap: .5rem; }
.side a { display: block; padding: .4rem .7rem; border-radius: 6px;
text-decoration: none; color: var(--ink); background: #fff; }
.content { grid-area: content; padding: 1.5rem; max-width: 50rem; }
.bottom { grid-area: bottom; padding: 1rem 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
@media (min-width: 800px) {
  .layout { grid-template-columns: 16rem 1fr; grid-template-areas:
"top top" "side content" "bottom bottom"; }
  .side ul { flex-direction: column; }
  .side { position: sticky; top: 0; align-self: start; height: 100vh;
}
}
```

Project 372 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - Guide</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
	Generic block container for grouping and layout.
<header class="top"> Delta Kids Library guide </header>	Introductory content: logo, title, navigation.
<nav class="side" aria-label="Sections">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Story hour	A hyperlink; href gives the destination.
Reading club	One list item.
<main class="content">	The unique content of this page; exactly one per page.

Line	What it does
<section id="sStory hour"><h2>Story hour</h2><p>Ages 3 to 6, Saturd...	A thematic group of content, normally with its own heading.
<section id="sReading club"><h2>Reading club</h2><p>Ages 7 to 11. P...	Second-level heading for a section.
<section id="sHomework help"><h2>Homework help</h2><p>Weekday after...	A paragraph of text.
<footer class="bottom">© 2026 Delta Kids Library</footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
grid-template-areas: "top" "side" "content" "bottom";	Names regions of the grid so children can be placed by name.
grid-area: top;	Places a child into a named area.
background: var(--brand);	Background colour or image.
padding: 1rem 1.5rem;	Space inside the element between its border and content.
font-size: 1.3rem;	Size of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Declaration	What it does
@media (min-width: 800px) {	Applies from the given width upwards (mobile-first breakpoint).
flex-direction: column;	Stacks flex items vertically.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.

Check your work

- Areas string has equal columns per row
- Anchor links jump to sections
- Sticky sidebar does not cover the footer
- Mobile shows links as a wrapped row

Exercises

1. Highlight the current section link with :target.
2. Add a right column for 'on this page'.
3. Collapse the sidebar with a checkbox toggle.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 373: Sidebar layout for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Build a documentation-style page: header, left sidebar of section links, content and footer, using named grid areas that rearrange at 800px.

Learning goals

- Use grid-template-areas for whole-page layout
- Change the areas in a media query
- Make the sidebar sticky on wide screens

Elements and CSS used

HTML elements	CSS features
div, header, nav, ul, li, a, main, section, footer	grid-template-areas, grid-area, @media (min-width), position: sticky, align-self: start

Build guide

1. Write the four regions inside a .layout div.
2. Give each region a grid-area name.
3. Mobile first: one column, areas stacked.
4. At 800px switch to two columns with side and content side by side.
5. Turn the sidebar link list into a column on desktop.
6. Make the sidebar sticky.

Project 373: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - Guide</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <div class="layout">
    <header class="top"><h1>Nubian Guest House guide</h1></header>
    <nav class="side" aria-label="Sections">
      <ul>
    <li><a href="#sGarden room">Garden room</a></li>
    <li><a href="#sNile view suite">Nile view suite</a></li>
    <li><a href="#sFamily room">Family room</a></li>
    <li><a href="#sRooftop dorm">Rooftop dorm</a></li>
      </ul>
    </nav>
    <main class="content">
      <section id="sGarden room"><h2>Garden room</h2><p>Double bed,
shared terrace. Price: 900 EGP.</p></section>
      <section id="sNile view suite"><h2>Nile view suite</
h2><p>Balcony and breakfast. Price: 1800 EGP.</p></section>
      <section id="sFamily room"><h2>Family room</h2><p>Sleeps four.
Price: 1500 EGP.</p></section>
      <section id="sRooftop dorm"><h2>Rooftop dorm</h2><p>Budget beds.
 Price: 300 EGP.</p></section>
    </main>
    <footer class="bottom">&copy; 2026 Nubian Guest House</footer>
  </div>
</body>
</html>
```

Project 373: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.layout { min-height: 100vh; display: grid; grid-template-rows: auto
1fr auto; grid-template-columns: 1fr; grid-template-areas: "top"
"side" "content" "bottom"; }
.top { grid-area: top; background: var(--brand); color: #fff; padding:
 1rem 1.5rem; }
.top h1 { margin: 0; font-size: 1.3rem; }
```

```
.side { grid-area: side; background: var(--accent); padding: 1rem; }
.side ul { list-style: none; margin: 0; padding: 0; display: flex;
flex-wrap: wrap; gap: .5rem; }
.side a { display: block; padding: .4rem .7rem; border-radius: 6px;
text-decoration: none; color: var(--ink); background: #fff; }
.content { grid-area: content; padding: 1.5rem; max-width: 50rem; }
.bottom { grid-area: bottom; padding: 1rem 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
@media (min-width: 800px) {
  .layout { grid-template-columns: 16rem 1fr; grid-template-areas:
"top top" "side content" "bottom bottom"; }
  .side ul { flex-direction: column; }
  .side { position: sticky; top: 0; align-self: start; height: 100vh;
}
}
```

Project 373 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - Guide</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
	Generic block container for grouping and layout.
<header class="top"> Nubian Guest House guide </header>	Introductory content: logo, title, navigation.
<nav class="side" aria-label="Sections">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Garden room	A hyperlink; href gives the destination.
Nile view suite	One list item.

Line	What it does
<main class="content">	The unique content of this page; exactly one per page.
<section id="sGarden room"><h2>Garden room</h2><p>Double bed, share...	A thematic group of content, normally with its own heading.
<section id="sNile view suite"><h2>Nile view suite</h2><p>Balcony a...	Second-level heading for a section.
<section id="sFamily room"><h2>Family room</h2><p>Sleeps four. Pric...	A paragraph of text.
<footer class="bottom">© 2026 Nubian Guest House</footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
grid-template-areas: "top" "side" "content" "bottom";	Names regions of the grid so children can be placed by name.
grid-area: top;	Places a child into a named area.
background: var(--brand);	Background colour or image.
padding: 1rem 1.5rem;	Space inside the element between its border and content.
font-size: 1.3rem;	Size of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.
border-top: 1px solid var(--line);	A top border used as an accent or separator.

Declaration	What it does
@media (min-width: 800px) {	Applies from the given width upwards (mobile-first breakpoint).
flex-direction: column;	Stacks flex items vertically.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.

Check your work

- Areas string has equal columns per row
- Anchor links jump to sections
- Sticky sidebar does not cover the footer
- Mobile shows links as a wrapped row

Exercises

1. Highlight the current section link with :target.
2. Add a right column for 'on this page'.
3. Collapse the sidebar with a checkbox toggle.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 374: Sidebar layout for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 2 | Files: index.html, styles.css

Brief

Build a documentation-style page: header, left sidebar of section links, content and footer, using named grid areas that rearrange at 800px.

Learning goals

- Use grid-template-areas for whole-page layout
- Change the areas in a media query
- Make the sidebar sticky on wide screens

Elements and CSS used

HTML elements	CSS features
div, header, nav, ul, li, a, main, section, footer	grid-template-areas, grid-area, @media (min-width), position: sticky, align-self: start

Build guide

1. Write the four regions inside a .layout div.
2. Give each region a grid-area name.
3. Mobile first: one column, areas stacked.
4. At 800px switch to two columns with side and content side by side.
5. Turn the sidebar link list into a column on desktop.
6. Make the sidebar sticky.

Project 374: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - Guide</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <div class="layout">
    <header class="top"><h1>Ismailia Cycling Store guide</h1></header>
    <nav class="side" aria-label="Sections">
      <ul>
    <li><a href="#sCity bike">City bike</a></li>
    <li><a href="#sMountain bike">Mountain bike</a></li>
    <li><a href="#sKids bike">Kids bike</a></li>
    <li><a href="#sTune-up">Tune-up</a></li>
      </ul>
    </nav>
    <main class="content">
      <section id="sCity bike"><h2>City bike</h2><p>Seven gears,
basket. Price: 6500 EGP.</p></section>
      <section id="sMountain bike"><h2>Mountain bike</h2><p>Front
suspension. Price: 11000 EGP.</p></section>
      <section id="sKids bike"><h2>Kids bike</h2><p>20 inch wheels.
Price: 3200 EGP.</p></section>
      <section id="sTune-up"><h2>Tune-up</h2><p>Brakes, gears and
true wheels. Price: 250 EGP.</p></section>
    </main>
    <footer class="bottom">&copy; 2026 Ismailia Cycling Store</footer>
  </div>
</body>
</html>
```

Project 374: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.layout { min-height: 100vh; display: grid; grid-template-rows: auto
1fr auto; grid-template-columns: 1fr; grid-template-areas: "top"
"side" "content" "bottom"; }
.top { grid-area: top; background: var(--brand); color: #fff; padding:
 1rem 1.5rem; }
.top h1 { margin: 0; font-size: 1.3rem; }
```

```
.side { grid-area: side; background: var(--accent); padding: 1rem; }
.side ul { list-style: none; margin: 0; padding: 0; display: flex;
flex-wrap: wrap; gap: .5rem; }
.side a { display: block; padding: .4rem .7rem; border-radius: 6px;
text-decoration: none; color: var(--ink); background: #fff; }
.content { grid-area: content; padding: 1.5rem; max-width: 50rem; }
.bottom { grid-area: bottom; padding: 1rem 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
@media (min-width: 800px) {
  .layout { grid-template-columns: 16rem 1fr; grid-template-areas:
"top top" "side content" "bottom bottom"; }
  .side ul { flex-direction: column; }
  .side { position: sticky; top: 0; align-self: start; height: 100vh;
}
}
```

Project 374 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - Guide</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
	Generic block container for grouping and layout.
<header class="top"> Ismailia Cycling Store guide </header>	Introductory content: logo, title, navigation.
<nav class="side" aria-label="Sections">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
City bike	A hyperlink; href gives the destination.
Mountain bike	One list item.

Line	What it does
<main class="content">	The unique content of this page; exactly one per page.
<section id="sCity bike"><h2>City bike</h2><p>Seven gears, basket. ...	A thematic group of content, normally with its own heading.
<section id="sMountain bike"><h2>Mountain bike</h2><p>Front suspens...	Second-level heading for a section.
<section id="sKids bike"><h2>Kids bike</h2><p>20 inch wheels. Price...	A paragraph of text.
<footer class="bottom">© 2026 Ismailia Cycling Store</footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.

Declaration	What it does
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
grid-template-areas: "top" "side" "content" "bottom";	Names regions of the grid so children can be placed by name.
grid-area: top;	Places a child into a named area.
background: var(--brand);	Background colour or image.
padding: 1rem 1.5rem;	Space inside the element between its border and content.
font-size: 1.3rem;	Size of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
border-top: 1px solid var(--line);	A top border used as an accent or separator.
@media (min-width: 800px) {	Applies from the given width upwards (mobile-first breakpoint).
flex-direction: column;	Stacks flex items vertically.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.

Check your work

- Areas string has equal columns per row
- Anchor links jump to sections
- Sticky sidebar does not cover the footer
- Mobile shows links as a wrapped row

Exercises

1. Highlight the current section link with :target.
2. Add a right column for 'on this page'.
3. Collapse the sidebar with a checkbox toggle.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2

Field	Value
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 375: Sidebar layout for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 2 | Files: index.html, styles.css

Brief

Build a documentation-style page: header, left sidebar of section links, content and footer, using named grid areas that rearrange at 800px.

Learning goals

- Use grid-template-areas for whole-page layout
- Change the areas in a media query
- Make the sidebar sticky on wide screens

Elements and CSS used

HTML elements	CSS features
div, header, nav, ul, li, a, main, section, footer	grid-template-areas, grid-area, @media (min-width), position: sticky, align-self: start

Build guide

1. Write the four regions inside a .layout div.
2. Give each region a grid-area name.
3. Mobile first: one column, areas stacked.
4. At 800px switch to two columns with side and content side by side.
5. Turn the sidebar link list into a column on desktop.
6. Make the sidebar sticky.

Project 375: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - Guide</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <div class="layout">
    <header class="top"><h1>Minya Coding Club guide</h1></header>
    <nav class="side" aria-label="Sections">
      <ul>
    <li><a href="#sHTML weekend">HTML weekend</a></li>
    <li><a href="#sCSS art">CSS art</a></li>
    <li><a href="#sScratch games">Scratch games</a></li>
    <li><a href="#sHackathon">Hackathon</a></li>
      </ul>
    </nav>
    <main class="content">
      <section id="sHTML weekend"><h2>HTML weekend</h2><p>Build your
first page. Price: Free.</p></section>
      <section id="sCSS art"><h2>CSS art</h2><p>Draw with code. Price:
 Free.</p></section>
      <section id="sScratch games"><h2>Scratch games</h2><p>Ages 10
to 13. Price: Free.</p></section>
      <section id="sHackathon"><h2>Hackathon</h2><p>48 hours, teams
of four. Price: Free.</p></section>
    </main>
    <footer class="bottom">&copy; 2026 Minya Coding Club</footer>
  </div>
</body>
</html>
```

Project 375: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.layout { min-height: 100vh; display: grid; grid-template-rows: auto
1fr auto; grid-template-columns: 1fr; grid-template-areas: "top"
"side" "content" "bottom"; }
.top { grid-area: top; background: var(--brand); color: #fff; padding:
 1rem 1.5rem; }
.top h1 { margin: 0; font-size: 1.3rem; }
```

```
.side { grid-area: side; background: var(--accent); padding: 1rem; }
.side ul { list-style: none; margin: 0; padding: 0; display: flex;
flex-wrap: wrap; gap: .5rem; }
.side a { display: block; padding: .4rem .7rem; border-radius: 6px;
text-decoration: none; color: var(--ink); background: #fff; }
.content { grid-area: content; padding: 1.5rem; max-width: 50rem; }
.bottom { grid-area: bottom; padding: 1rem 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
@media (min-width: 800px) {
  .layout { grid-template-columns: 16rem 1fr; grid-template-areas:
"top top" "side content" "bottom bottom"; }
  .side ul { flex-direction: column; }
  .side { position: sticky; top: 0; align-self: start; height: 100vh;
}
}
```

Project 375 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - Guide</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
	Generic block container for grouping and layout.
<header class="top"> Minya Coding Club guide </header>	Introductory content: logo, title, navigation.
<nav class="side" aria-label="Sections">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
HTML weekend	A hyperlink; href gives the destination.
CSS art	One list item.

Line	What it does
<main class="content">	The unique content of this page; exactly one per page.
<section id="sHTML weekend"><h2>HTML weekend</h2><p>Build your firs...	A thematic group of content, normally with its own heading.
<section id="sCSS art"><h2>CSS art</h2><p>Draw with code. Price: Fr...	Second-level heading for a section.
<section id="sScratch games"><h2>Scratch games</h2><p>Ages 10 to 13...	A paragraph of text.
<footer class="bottom">© 2026 Minya Coding Club</footer>	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.

Declaration	What it does
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
grid-template-areas: "top" "side" "content" "bottom";	Names regions of the grid so children can be placed by name.
grid-area: top;	Places a child into a named area.
background: var(--brand);	Background colour or image.
padding: 1rem 1.5rem;	Space inside the element between its border and content.
font-size: 1.3rem;	Size of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
max-width: 50rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
border-top: 1px solid var(--line);	A top border used as an accent or separator.
@media (min-width: 800px) {	Applies from the given width upwards (mobile-first breakpoint).
flex-direction: column;	Stacks flex items vertically.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.

Check your work

- Areas string has equal columns per row
- Anchor links jump to sections
- Sticky sidebar does not cover the footer
- Mobile shows links as a wrapped row

Exercises

1. Highlight the current section link with :target.
2. Add a right column for 'on this page'.
3. Collapse the sidebar with a checkbox toggle.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff

Field	Value
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Login form

Level 1 | 25 projects, one per theme

Build a compact sign-in card with email, password, remember-me checkbox and a link, using the correct autocomplete tokens so password managers work.

Project 376: Login form for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 1 | Files: index.html, styles.css

Brief

Build a compact sign-in card with email, password, remember-me checkbox and a link, using the correct autocomplete tokens so password managers work.

Learning goals

- Use autocomplete="username" and "current-password"
- Wrap a checkbox in its label
- Size a card with min()

Elements and CSS used

HTML elements	CSS features
form, h1, label, input, button, p, a	width: min(), box-shadow, :not(), display: flex, align-items

Build guide

1. Write the form with labels before each input.
2. Add autocomplete tokens and minlength on the password.
3. Wrap the checkbox inside its label.
4. Make the form a grid with small gaps.
5. Exclude the checkbox from the input styling with :not([type=checkbox]).
6. Centre the card.

Project 376: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Sign in</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <form class="login" action="/login" method="post">
      <h1>Sign in to Cairo Book Shop</h1>
      <label for="user">Email</label>
      <input id="user" name="email" type="email" required
autocomplete="username">
      <label for="pass">Password</label>
      <input id="pass" name="password" type="password" required
minlength="8" autocomplete="current-password">
      <label class="check"><input type="checkbox" name="remember">
Remember me</label>
      <button type="submit">Sign in</button>
      <p><a href="forgot.html">Forgot your password?</a></p>
    </form>
  </main>
</body>
</html>
```

Project 376: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.login { width: min(100%, 22rem); background: #fff; padding: 2rem;
border-radius: 14px; box-shadow: 0 8px 24px rgb(0 0 0 / 10%); display:
 grid; gap: .4rem; }
h1 { font-size: 1.3rem; margin: 0 0 1rem; text-align: center; }
label { font-weight: 600; font-size: .9rem; }
input:not([type="checkbox"]) { padding: .65rem .8rem; border: 1px
solid #bbb; border-radius: 8px; font: inherit; margin-bottom: .6rem; }
.check { display: flex; align-items: center; gap: .4rem; font-weight:
400; }
button { margin-top: .5rem; padding: .75rem; border: 0; border-radius:
 8px; background: var(--brand); color: #fff; font: inherit; cursor:
```

```
pointer; }
p { text-align: center; font-size: .9rem; }
```

Project 376 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - Sign in</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<form class="login" action="/login" method="post">	A form; action is where the data goes, method how it is sent.
Sign in to Cairo Book Shop	The main heading; only one per page.
<label for="user">Email</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="user" name="email" type="email" required autocomplete="u...	Email field: validated automatically and shows the @ keyboard on phones.
<input id="pass" name="password" type="password" required minlength...	Password field: characters are hidden.

Line	What it does
<label class="check"><input type="checkbox" name="remember"> Rememb...	Checkbox: on or off.
<button type="submit">Sign in</button>	A clickable button; inside a form it submits by default.
Forgot your password?	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.

Declaration	What it does
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
width: min(100%, 22rem);	Uses the smaller of the listed values.
border-radius: 14px;	Rounds the corners.
box-shadow: 0 8px 24px rgb(0 0 0 / 10%);	Soft shadow that lifts the element from the page.
gap: .4rem;	Space between grid or flex items without extra margins.
font-size: 1.3rem;	Size of the text.
text-align: center;	Centres inline content such as text.
font-weight: 600;	Thickness of the text.
input:not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
border: 0;	Removes the default border (for example on an iframe or button).
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Browser offers to save the password
- Checkbox label is clickable
- Card never wider than 22rem
- Password minimum length enforced

Exercises

1. Add a show/hide password button.
2. Add a 'Sign in with...' divider using ::before/::after lines.
3. Show a friendly error message region with aria-live.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 377: Login form for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 1 | Files: index.html, styles.css

Brief

Build a compact sign-in card with email, password, remember-me checkbox and a link, using the correct autocomplete tokens so password managers work.

Learning goals

- Use autocomplete="username" and "current-password"
- Wrap a checkbox in its label
- Size a card with min()

Elements and CSS used

HTML elements	CSS features
form, h1, label, input, button, p, a	width: min(), box-shadow, :not(), display: flex, align-items

Build guide

1. Write the form with labels before each input.
2. Add autocomplete tokens and minlength on the password.
3. Wrap the checkbox inside its label.
4. Make the form a grid with small gaps.
5. Exclude the checkbox from the input styling with :not([type=checkbox]).
6. Centre the card.

Project 377: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - Sign in</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <form class="login" action="/login" method="post">
      <h1>Sign in to Nile Bakery</h1>
      <label for="user">Email</label>
      <input id="user" name="email" type="email" required
autocomplete="username">
      <label for="pass">Password</label>
      <input id="pass" name="password" type="password" required
minlength="8" autocomplete="current-password">
      <label class="check"><input type="checkbox" name="remember">
Remember me</label>
      <button type="submit">Sign in</button>
      <p><a href="forgot.html">Forgot your password?</a></p>
    </form>
  </main>
</body>
</html>
```

Project 377: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.login { width: min(100%, 22rem); background: #fff; padding: 2rem;
border-radius: 14px; box-shadow: 0 8px 24px rgb(0 0 0 / 10%); display:
 grid; gap: .4rem; }
h1 { font-size: 1.3rem; margin: 0 0 1rem; text-align: center; }
label { font-weight: 600; font-size: .9rem; }
input:not([type="checkbox"]) { padding: .65rem .8rem; border: 1px
solid #bbb; border-radius: 8px; font: inherit; margin-bottom: .6rem; }
.check { display: flex; align-items: center; gap: .4rem; font-weight:
400; }
button { margin-top: .5rem; padding: .75rem; border: 0; border-radius:
 8px; background: var(--brand); color: #fff; font: inherit; cursor:
```

```
pointer; }
p { text-align: center; font-size: .9rem; }
```

Project 377 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - Sign in</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<form class="login" action="/login" method="post">	A form; action is where the data goes, method how it is sent.
Sign in to Nile Bakery	The main heading; only one per page.
<label for="user">Email</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="user" name="email" type="email" required autocomplete="u...	Email field: validated automatically and shows the @ keyboard on phones.
<input id="pass" name="password" type="password" required minlength...	Password field: characters are hidden.

Line	What it does
<label class="check"><input type="checkbox" name="remember"> Rememb...	Checkbox: on or off.
<button type="submit">Sign in</button>	A clickable button; inside a form it submits by default.
Forgot your password?	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.

Declaration	What it does
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
width: min(100%, 22rem);	Uses the smaller of the listed values.
border-radius: 14px;	Rounds the corners.
box-shadow: 0 8px 24px rgb(0 0 0 / 10%);	Soft shadow that lifts the element from the page.
gap: .4rem;	Space between grid or flex items without extra margins.
font-size: 1.3rem;	Size of the text.
text-align: center;	Centres inline content such as text.
font-weight: 600;	Thickness of the text.
input:not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
border: 0;	Removes the default border (for example on an iframe or button).
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Browser offers to save the password
- Checkbox label is clickable
- Card never wider than 22rem
- Password minimum length enforced

Exercises

1. Add a show/hide password button.
2. Add a 'Sign in with...' divider using ::before/::after lines.
3. Show a friendly error message region with aria-live.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 378: Login form for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 1 | Files: index.html, styles.css

Brief

Build a compact sign-in card with email, password, remember-me checkbox and a link, using the correct autocomplete tokens so password managers work.

Learning goals

- Use autocomplete="username" and "current-password"
- Wrap a checkbox in its label
- Size a card with min()

Elements and CSS used

HTML elements	CSS features
form, h1, label, input, button, p, a	width: min(), box-shadow, :not(), display: flex, align-items

Build guide

1. Write the form with labels before each input.
2. Add autocomplete tokens and minlength on the password.
3. Wrap the checkbox inside its label.
4. Make the form a grid with small gaps.
5. Exclude the checkbox from the input styling with :not([type=checkbox]).
6. Centre the card.

Project 378: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - Sign in</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <form class="login" action="/login" method="post">
      <h1>Sign in to Pyramid Fitness</h1>
      <label for="user">Email</label>
      <input id="user" name="email" type="email" required
autocomplete="username">
      <label for="pass">Password</label>
      <input id="pass" name="password" type="password" required
minlength="8" autocomplete="current-password">
      <label class="check"><input type="checkbox" name="remember">
Remember me</label>
      <button type="submit">Sign in</button>
      <p><a href="forgot.html">Forgot your password?</a></p>
    </form>
  </main>
</body>
</html>
```

Project 378: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.login { width: min(100%, 22rem); background: #fff; padding: 2rem;
border-radius: 14px; box-shadow: 0 8px 24px rgb(0 0 0 / 10%); display:
 grid; gap: .4rem; }
h1 { font-size: 1.3rem; margin: 0 0 1rem; text-align: center; }
label { font-weight: 600; font-size: .9rem; }
input:not([type="checkbox"]) { padding: .65rem .8rem; border: 1px
solid #bbb; border-radius: 8px; font: inherit; margin-bottom: .6rem; }
.check { display: flex; align-items: center; gap: .4rem; font-weight:
400; }
button { margin-top: .5rem; padding: .75rem; border: 0; border-radius:
 8px; background: var(--brand); color: #fff; font: inherit; cursor:
```

```
pointer; }
p { text-align: center; font-size: .9rem; }
```

Project 378 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - Sign in</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<form class="login" action="/login" method="post">	A form; action is where the data goes, method how it is sent.
Sign in to Pyramid Fitness	The main heading; only one per page.
<label for="user">Email</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="user" name="email" type="email" required autocomplete="u...	Email field: validated automatically and shows the @ keyboard on phones.
<input id="pass" name="password" type="password" required minlength...	Password field: characters are hidden.

Line	What it does
<label class="check"><input type="checkbox" name="remember"> Rememb...	Checkbox: on or off.
<button type="submit">Sign in</button>	A clickable button; inside a form it submits by default.
Forgot your password?	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.

Declaration	What it does
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
width: min(100%, 22rem);	Uses the smaller of the listed values.
border-radius: 14px;	Rounds the corners.
box-shadow: 0 8px 24px rgb(0 0 0 / 10%);	Soft shadow that lifts the element from the page.
gap: .4rem;	Space between grid or flex items without extra margins.
font-size: 1.3rem;	Size of the text.
text-align: center;	Centres inline content such as text.
font-weight: 600;	Thickness of the text.
input:not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
border: 0;	Removes the default border (for example on an iframe or button).
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Browser offers to save the password
- Checkbox label is clickable
- Card never wider than 22rem
- Password minimum length enforced

Exercises

1. Add a show/hide password button.
2. Add a 'Sign in with...' divider using ::before/::after lines.
3. Show a friendly error message region with aria-live.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 379: Login form for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 1 | Files: index.html, styles.css

Brief

Build a compact sign-in card with email, password, remember-me checkbox and a link, using the correct autocomplete tokens so password managers work.

Learning goals

- Use autocomplete="username" and "current-password"
- Wrap a checkbox in its label
- Size a card with min()

Elements and CSS used

HTML elements	CSS features
form, h1, label, input, button, p, a	width: min(), box-shadow, :not(), display: flex, align-items

Build guide

1. Write the form with labels before each input.
2. Add autocomplete tokens and minlength on the password.
3. Wrap the checkbox inside its label.
4. Make the form a grid with small gaps.
5. Exclude the checkbox from the input styling with :not([type=checkbox]).
6. Centre the card.

Project 379: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - Sign in</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <form class="login" action="/login" method="post">
      <h1>Sign in to Delta Dental Clinic</h1>
      <label for="user">Email</label>
      <input id="user" name="email" type="email" required
autocomplete="username">
      <label for="pass">Password</label>
      <input id="pass" name="password" type="password" required
minlength="8" autocomplete="current-password">
      <label class="check"><input type="checkbox" name="remember">
Remember me</label>
      <button type="submit">Sign in</button>
      <p><a href="forgot.html">Forgot your password?</a></p>
    </form>
  </main>
</body>
</html>
```

Project 379: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.login { width: min(100%, 22rem); background: #fff; padding: 2rem;
border-radius: 14px; box-shadow: 0 8px 24px rgb(0 0 0 / 10%); display:
 grid; gap: .4rem; }
h1 { font-size: 1.3rem; margin: 0 0 1rem; text-align: center; }
label { font-weight: 600; font-size: .9rem; }
input:not([type="checkbox"]) { padding: .65rem .8rem; border: 1px
solid #bbb; border-radius: 8px; font: inherit; margin-bottom: .6rem; }
.check { display: flex; align-items: center; gap: .4rem; font-weight:
400; }
button { margin-top: .5rem; padding: .75rem; border: 0; border-radius:
 8px; background: var(--brand); color: #fff; font: inherit; cursor:
```

```
pointer; }
p { text-align: center; font-size: .9rem; }
```

Project 379 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - Sign in</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<form class="login" action="/login" method="post">	A form; action is where the data goes, method how it is sent.
Sign in to Delta Dental Clinic	The main heading; only one per page.
<label for="user">Email</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="user" name="email" type="email" required autocomplete="u...	Email field: validated automatically and shows the @ keyboard on phones.
<input id="pass" name="password" type="password" required minlength...	Password field: characters are hidden.

Line	What it does
<label class="check"><input type="checkbox" name="remember"> Rememb...	Checkbox: on or off.
<button type="submit">Sign in</button>	A clickable button; inside a form it submits by default.
Forgot your password?	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.

Declaration	What it does
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
width: min(100%, 22rem);	Uses the smaller of the listed values.
border-radius: 14px;	Rounds the corners.
box-shadow: 0 8px 24px rgb(0 0 0 / 10%);	Soft shadow that lifts the element from the page.
gap: .4rem;	Space between grid or flex items without extra margins.
font-size: 1.3rem;	Size of the text.
text-align: center;	Centres inline content such as text.
font-weight: 600;	Thickness of the text.
input:not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
border: 0;	Removes the default border (for example on an iframe or button).
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Browser offers to save the password
- Checkbox label is clickable
- Card never wider than 22rem
- Password minimum length enforced

Exercises

1. Add a show/hide password button.
2. Add a 'Sign in with...' divider using ::before/::after lines.
3. Show a friendly error message region with aria-live.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 380: Login form for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 1 | Files: index.html, styles.css

Brief

Build a compact sign-in card with email, password, remember-me checkbox and a link, using the correct autocomplete tokens so password managers work.

Learning goals

- Use autocomplete="username" and "current-password"
- Wrap a checkbox in its label
- Size a card with min()

Elements and CSS used

HTML elements	CSS features
form, h1, label, input, button, p, a	width: min(), box-shadow, :not(), display: flex, align-items

Build guide

1. Write the form with labels before each input.
2. Add autocomplete tokens and minlength on the password.
3. Wrap the checkbox inside its label.
4. Make the form a grid with small gaps.
5. Exclude the checkbox from the input styling with :not([type=checkbox]).
6. Centre the card.

Project 380: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - Sign in</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <form class="login" action="/login" method="post">
      <h1>Sign in to Red Sea Travel</h1>
      <label for="user">Email</label>
      <input id="user" name="email" type="email" required
autocomplete="username">
      <label for="pass">Password</label>
      <input id="pass" name="password" type="password" required
minlength="8" autocomplete="current-password">
      <label class="check"><input type="checkbox" name="remember">
Remember me</label>
      <button type="submit">Sign in</button>
      <p><a href="forgot.html">Forgot your password?</a></p>
    </form>
  </main>
</body>
</html>
```

Project 380: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.login { width: min(100%, 22rem); background: #fff; padding: 2rem;
border-radius: 14px; box-shadow: 0 8px 24px rgb(0 0 0 / 10%); display:
 grid; gap: .4rem; }
h1 { font-size: 1.3rem; margin: 0 0 1rem; text-align: center; }
label { font-weight: 600; font-size: .9rem; }
input:not([type="checkbox"]) { padding: .65rem .8rem; border: 1px
solid #bbb; border-radius: 8px; font: inherit; margin-bottom: .6rem; }
.check { display: flex; align-items: center; gap: .4rem; font-weight:
400; }
button { margin-top: .5rem; padding: .75rem; border: 0; border-radius:
 8px; background: var(--brand); color: #fff; font: inherit; cursor:
```

```
pointer; }
p { text-align: center; font-size: .9rem; }
```

Project 380 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - Sign in</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<form class="login" action="/login" method="post">	A form; action is where the data goes, method how it is sent.
Sign in to Red Sea Travel	The main heading; only one per page.
<label for="user">Email</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="user" name="email" type="email" required autocomplete="u...	Email field: validated automatically and shows the @ keyboard on phones.
<input id="pass" name="password" type="password" required minlength...	Password field: characters are hidden.

Line	What it does
<label class="check"><input type="checkbox" name="remember"> Rememb...	Checkbox: on or off.
<button type="submit">Sign in</button>	A clickable button; inside a form it submits by default.
Forgot your password?	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.

Declaration	What it does
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
width: min(100%, 22rem);	Uses the smaller of the listed values.
border-radius: 14px;	Rounds the corners.
box-shadow: 0 8px 24px rgb(0 0 0 / 10%);	Soft shadow that lifts the element from the page.
gap: .4rem;	Space between grid or flex items without extra margins.
font-size: 1.3rem;	Size of the text.
text-align: center;	Centres inline content such as text.
font-weight: 600;	Thickness of the text.
input:not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
border: 0;	Removes the default border (for example on an iframe or button).
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Browser offers to save the password
- Checkbox label is clickable
- Card never wider than 22rem
- Password minimum length enforced

Exercises

1. Add a show/hide password button.
2. Add a 'Sign in with...' divider using ::before/::after lines.
3. Show a friendly error message region with aria-live.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 381: Login form for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Build a compact sign-in card with email, password, remember-me checkbox and a link, using the correct autocomplete tokens so password managers work.

Learning goals

- Use autocomplete="username" and "current-password"
- Wrap a checkbox in its label
- Size a card with min()

Elements and CSS used

HTML elements	CSS features
form, h1, label, input, button, p, a	width: min(), box-shadow, :not(), display: flex, align-items

Build guide

1. Write the form with labels before each input.
2. Add autocomplete tokens and minlength on the password.
3. Wrap the checkbox inside its label.
4. Make the form a grid with small gaps.
5. Exclude the checkbox from the input styling with :not([type=checkbox]).
6. Centre the card.

Project 381: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - Sign in</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <form class="login" action="/login" method="post">
      <h1>Sign in to Lotus Language School</h1>
      <label for="user">Email</label>
      <input id="user" name="email" type="email" required
autocomplete="username">
      <label for="pass">Password</label>
      <input id="pass" name="password" type="password" required
minlength="8" autocomplete="current-password">
      <label class="check"><input type="checkbox" name="remember">
Remember me</label>
      <button type="submit">Sign in</button>
      <p><a href="forgot.html">Forgot your password?</a></p>
    </form>
  </main>
</body>
</html>
```

Project 381: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.login { width: min(100%, 22rem); background: #fff; padding: 2rem;
border-radius: 14px; box-shadow: 0 8px 24px rgb(0 0 0 / 10%); display:
 grid; gap: .4rem; }
h1 { font-size: 1.3rem; margin: 0 0 1rem; text-align: center; }
label { font-weight: 600; font-size: .9rem; }
input:not([type="checkbox"]) { padding: .65rem .8rem; border: 1px
solid #bbb; border-radius: 8px; font: inherit; margin-bottom: .6rem; }
.check { display: flex; align-items: center; gap: .4rem; font-weight:
400; }
button { margin-top: .5rem; padding: .75rem; border: 0; border-radius:
 8px; background: var(--brand); color: #fff; font: inherit; cursor:
```

```
pointer; }
p { text-align: center; font-size: .9rem; }
```

Project 381 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - Sign in</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<form class="login" action="/login" method="post">	A form; action is where the data goes, method how it is sent.
Sign in to Lotus Language School	The main heading; only one per page.
<label for="user">Email</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="user" name="email" type="email" required autocomplete="u...	Email field: validated automatically and shows the @ keyboard on phones.
<input id="pass" name="password" type="password" required minlength...	Password field: characters are hidden.

Line	What it does
<label class="check"><input type="checkbox" name="remember"> Rememb...	Checkbox: on or off.
<button type="submit">Sign in</button>	A clickable button; inside a form it submits by default.
Forgot your password?	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.

Declaration	What it does
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
width: min(100%, 22rem);	Uses the smaller of the listed values.
border-radius: 14px;	Rounds the corners.
box-shadow: 0 8px 24px rgb(0 0 0 / 10%);	Soft shadow that lifts the element from the page.
gap: .4rem;	Space between grid or flex items without extra margins.
font-size: 1.3rem;	Size of the text.
text-align: center;	Centres inline content such as text.
font-weight: 600;	Thickness of the text.
input:not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
border: 0;	Removes the default border (for example on an iframe or button).
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Browser offers to save the password
- Checkbox label is clickable
- Card never wider than 22rem
- Password minimum length enforced

Exercises

1. Add a show/hide password button.
2. Add a 'Sign in with...' divider using ::before/::after lines.
3. Show a friendly error message region with aria-live.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 382: Login form for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 1 | Files: index.html, styles.css

Brief

Build a compact sign-in card with email, password, remember-me checkbox and a link, using the correct autocomplete tokens so password managers work.

Learning goals

- Use autocomplete="username" and "current-password"
- Wrap a checkbox in its label
- Size a card with min()

Elements and CSS used

HTML elements	CSS features
form, h1, label, input, button, p, a	width: min(), box-shadow, :not(), display: flex, align-items

Build guide

1. Write the form with labels before each input.
2. Add autocomplete tokens and minlength on the password.
3. Wrap the checkbox inside its label.
4. Make the form a grid with small gaps.
5. Exclude the checkbox from the input styling with :not([type=checkbox]).
6. Centre the card.

Project 382: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - Sign in</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <form class="login" action="/login" method="post">
      <h1>Sign in to Green Leaf Cafe</h1>
      <label for="user">Email</label>
      <input id="user" name="email" type="email" required
autocomplete="username">
      <label for="pass">Password</label>
      <input id="pass" name="password" type="password" required
minlength="8" autocomplete="current-password">
      <label class="check"><input type="checkbox" name="remember">
Remember me</label>
      <button type="submit">Sign in</button>
      <p><a href="forgot.html">Forgot your password?</a></p>
    </form>
  </main>
</body>
</html>
```

Project 382: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.login { width: min(100%, 22rem); background: #fff; padding: 2rem;
border-radius: 14px; box-shadow: 0 8px 24px rgb(0 0 0 / 10%); display:
 grid; gap: .4rem; }
h1 { font-size: 1.3rem; margin: 0 0 1rem; text-align: center; }
label { font-weight: 600; font-size: .9rem; }
input:not([type="checkbox"]) { padding: .65rem .8rem; border: 1px
solid #bbb; border-radius: 8px; font: inherit; margin-bottom: .6rem; }
.check { display: flex; align-items: center; gap: .4rem; font-weight:
400; }
button { margin-top: .5rem; padding: .75rem; border: 0; border-radius:
 8px; background: var(--brand); color: #fff; font: inherit; cursor:
```

```
pointer; }
p { text-align: center; font-size: .9rem; }
```

Project 382 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - Sign in</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<form class="login" action="/login" method="post">	A form; action is where the data goes, method how it is sent.
Sign in to Green Leaf Cafe	The main heading; only one per page.
<label for="user">Email</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="user" name="email" type="email" required autocomplete="u...	Email field: validated automatically and shows the @ keyboard on phones.
<input id="pass" name="password" type="password" required minlength...	Password field: characters are hidden.

Line	What it does
<label class="check"><input type="checkbox" name="remember"> Rememb...	Checkbox: on or off.
<button type="submit">Sign in</button>	A clickable button; inside a form it submits by default.
Forgot your password?	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.

Declaration	What it does
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
width: min(100%, 22rem);	Uses the smaller of the listed values.
border-radius: 14px;	Rounds the corners.
box-shadow: 0 8px 24px rgb(0 0 0 / 10%);	Soft shadow that lifts the element from the page.
gap: .4rem;	Space between grid or flex items without extra margins.
font-size: 1.3rem;	Size of the text.
text-align: center;	Centres inline content such as text.
font-weight: 600;	Thickness of the text.
input:not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
border: 0;	Removes the default border (for example on an iframe or button).
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Browser offers to save the password
- Checkbox label is clickable
- Card never wider than 22rem
- Password minimum length enforced

Exercises

1. Add a show/hide password button.
2. Add a 'Sign in with...' divider using ::before/::after lines.
3. Show a friendly error message region with aria-live.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 383: Login form for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 1 | Files: index.html, styles.css

Brief

Build a compact sign-in card with email, password, remember-me checkbox and a link, using the correct autocomplete tokens so password managers work.

Learning goals

- Use autocomplete="username" and "current-password"
- Wrap a checkbox in its label
- Size a card with min()

Elements and CSS used

HTML elements	CSS features
form, h1, label, input, button, p, a	width: min(), box-shadow, :not(), display: flex, align-items

Build guide

1. Write the form with labels before each input.
2. Add autocomplete tokens and minlength on the password.
3. Wrap the checkbox inside its label.
4. Make the form a grid with small gaps.
5. Exclude the checkbox from the input styling with :not([type=checkbox]).
6. Centre the card.

Project 383: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - Sign in</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <form class="login" action="/login" method="post">
      <h1>Sign in to Sinai Trekking Club</h1>
      <label for="user">Email</label>
      <input id="user" name="email" type="email" required
autocomplete="username">
      <label for="pass">Password</label>
      <input id="pass" name="password" type="password" required
minlength="8" autocomplete="current-password">
      <label class="check"><input type="checkbox" name="remember">
Remember me</label>
      <button type="submit">Sign in</button>
      <p><a href="forgot.html">Forgot your password?</a></p>
    </form>
  </main>
</body>
</html>
```

Project 383: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.login { width: min(100%, 22rem); background: #fff; padding: 2rem;
border-radius: 14px; box-shadow: 0 8px 24px rgb(0 0 0 / 10%); display:
 grid; gap: .4rem; }
h1 { font-size: 1.3rem; margin: 0 0 1rem; text-align: center; }
label { font-weight: 600; font-size: .9rem; }
input:not([type="checkbox"]) { padding: .65rem .8rem; border: 1px
solid #bbb; border-radius: 8px; font: inherit; margin-bottom: .6rem; }
.check { display: flex; align-items: center; gap: .4rem; font-weight:
400; }
button { margin-top: .5rem; padding: .75rem; border: 0; border-radius:
 8px; background: var(--brand); color: #fff; font: inherit; cursor:
```

```
pointer; }
p { text-align: center; font-size: .9rem; }
```

Project 383 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - Sign in</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<form class="login" action="/login" method="post">	A form; action is where the data goes, method how it is sent.
Sign in to Sinai Trekking Club	The main heading; only one per page.
<label for="user">Email</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="user" name="email" type="email" required autocomplete="u...	Email field: validated automatically and shows the @ keyboard on phones.
<input id="pass" name="password" type="password" required minlength...	Password field: characters are hidden.

Line	What it does
<label class="check"><input type="checkbox" name="remember"> Rememb...	Checkbox: on or off.
<button type="submit">Sign in</button>	A clickable button; inside a form it submits by default.
Forgot your password?	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.

Declaration	What it does
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
width: min(100%, 22rem);	Uses the smaller of the listed values.
border-radius: 14px;	Rounds the corners.
box-shadow: 0 8px 24px rgb(0 0 0 / 10%);	Soft shadow that lifts the element from the page.
gap: .4rem;	Space between grid or flex items without extra margins.
font-size: 1.3rem;	Size of the text.
text-align: center;	Centres inline content such as text.
font-weight: 600;	Thickness of the text.
input:not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
border: 0;	Removes the default border (for example on an iframe or button).
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Browser offers to save the password
- Checkbox label is clickable
- Card never wider than 22rem
- Password minimum length enforced

Exercises

1. Add a show/hide password button.
2. Add a 'Sign in with…' divider using ::before/::after lines.
3. Show a friendly error message region with aria-live.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 384: Login form for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 1 | Files: index.html, styles.css

Brief

Build a compact sign-in card with email, password, remember-me checkbox and a link, using the correct autocomplete tokens so password managers work.

Learning goals

- Use autocomplete="username" and "current-password"
- Wrap a checkbox in its label
- Size a card with min()

Elements and CSS used

HTML elements	CSS features
form, h1, label, input, button, p, a	width: min(), box-shadow, :not(), display: flex, align-items

Build guide

1. Write the form with labels before each input.
2. Add autocomplete tokens and minlength on the password.
3. Wrap the checkbox inside its label.
4. Make the form a grid with small gaps.
5. Exclude the checkbox from the input styling with :not([type=checkbox]).
6. Centre the card.

Project 384: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - Sign in</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <form class="login" action="/login" method="post">
      <h1>Sign in to Horizon Photography</h1>
      <label for="user">Email</label>
      <input id="user" name="email" type="email" required
autocomplete="username">
      <label for="pass">Password</label>
      <input id="pass" name="password" type="password" required
minlength="8" autocomplete="current-password">
      <label class="check"><input type="checkbox" name="remember">
Remember me</label>
      <button type="submit">Sign in</button>
      <p><a href="forgot.html">Forgot your password?</a></p>
    </form>
  </main>
</body>
</html>
```

Project 384: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.login { width: min(100%, 22rem); background: #fff; padding: 2rem;
border-radius: 14px; box-shadow: 0 8px 24px rgb(0 0 0 / 10%); display:
 grid; gap: .4rem; }
h1 { font-size: 1.3rem; margin: 0 0 1rem; text-align: center; }
label { font-weight: 600; font-size: .9rem; }
input:not([type="checkbox"]) { padding: .65rem .8rem; border: 1px
solid #bbb; border-radius: 8px; font: inherit; margin-bottom: .6rem; }
.check { display: flex; align-items: center; gap: .4rem; font-weight:
400; }
button { margin-top: .5rem; padding: .75rem; border: 0; border-radius:
 8px; background: var(--brand); color: #fff; font: inherit; cursor:
```

```
pointer; }
p { text-align: center; font-size: .9rem; }
```

Project 384 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - Sign in</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<form class="login" action="/login" method="post">	A form; action is where the data goes, method how it is sent.
Sign in to Horizon Photography	The main heading; only one per page.
<label for="user">Email</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="user" name="email" type="email" required autocomplete="u...	Email field: validated automatically and shows the @ keyboard on phones.
<input id="pass" name="password" type="password" required minlength...	Password field: characters are hidden.

Line	What it does
<label class="check"><input type="checkbox" name="remember"> Rememb...	Checkbox: on or off.
<button type="submit">Sign in</button>	A clickable button; inside a form it submits by default.
Forgot your password?	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.

Declaration	What it does
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
width: min(100%, 22rem);	Uses the smaller of the listed values.
border-radius: 14px;	Rounds the corners.
box-shadow: 0 8px 24px rgb(0 0 0 / 10%);	Soft shadow that lifts the element from the page.
gap: .4rem;	Space between grid or flex items without extra margins.
font-size: 1.3rem;	Size of the text.
text-align: center;	Centres inline content such as text.
font-weight: 600;	Thickness of the text.
input:not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
border: 0;	Removes the default border (for example on an iframe or button).
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Browser offers to save the password
- Checkbox label is clickable
- Card never wider than 22rem
- Password minimum length enforced

Exercises

1. Add a show/hide password button.
2. Add a 'Sign in with...' divider using ::before/::after lines.
3. Show a friendly error message region with aria-live.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 385: Login form for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 1 | Files: index.html, styles.css

Brief

Build a compact sign-in card with email, password, remember-me checkbox and a link, using the correct autocomplete tokens so password managers work.

Learning goals

- Use autocomplete="username" and "current-password"
- Wrap a checkbox in its label
- Size a card with min()

Elements and CSS used

HTML elements	CSS features
form, h1, label, input, button, p, a	width: min(), box-shadow, :not(), display: flex, align-items

Build guide

1. Write the form with labels before each input.
2. Add autocomplete tokens and minlength on the password.
3. Wrap the checkbox inside its label.
4. Make the form a grid with small gaps.
5. Exclude the checkbox from the input styling with :not([type=checkbox]).
6. Centre the card.

Project 385: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - Sign in</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <form class="login" action="/login" method="post">
      <h1>Sign in to Papyrus Stationery</h1>
      <label for="user">Email</label>
      <input id="user" name="email" type="email" required
autocomplete="username">
      <label for="pass">Password</label>
      <input id="pass" name="password" type="password" required
minlength="8" autocomplete="current-password">
      <label class="check"><input type="checkbox" name="remember">
Remember me</label>
      <button type="submit">Sign in</button>
      <p><a href="forgot.html">Forgot your password?</a></p>
    </form>
  </main>
</body>
</html>
```

Project 385: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.login { width: min(100%, 22rem); background: #fff; padding: 2rem;
border-radius: 14px; box-shadow: 0 8px 24px rgb(0 0 0 / 10%); display:
 grid; gap: .4rem; }
h1 { font-size: 1.3rem; margin: 0 0 1rem; text-align: center; }
label { font-weight: 600; font-size: .9rem; }
input:not([type="checkbox"]) { padding: .65rem .8rem; border: 1px
solid #bbb; border-radius: 8px; font: inherit; margin-bottom: .6rem; }
.check { display: flex; align-items: center; gap: .4rem; font-weight:
400; }
button { margin-top: .5rem; padding: .75rem; border: 0; border-radius:
 8px; background: var(--brand); color: #fff; font: inherit; cursor:
```

```
pointer; }
p { text-align: center; font-size: .9rem; }
```

Project 385 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - Sign in</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<form class="login" action="/login" method="post">	A form; action is where the data goes, method how it is sent.
Sign in to Papyrus Stationery	The main heading; only one per page.
<label for="user">Email</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="user" name="email" type="email" required autocomplete="u...	Email field: validated automatically and shows the @ keyboard on phones.
<input id="pass" name="password" type="password" required minlength...	Password field: characters are hidden.

Line	What it does
<label class="check"><input type="checkbox" name="remember"> Rememb...	Checkbox: on or off.
<button type="submit">Sign in</button>	A clickable button; inside a form it submits by default.
Forgot your password?	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.

Declaration	What it does
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
width: min(100%, 22rem);	Uses the smaller of the listed values.
border-radius: 14px;	Rounds the corners.
box-shadow: 0 8px 24px rgb(0 0 0 / 10%);	Soft shadow that lifts the element from the page.
gap: .4rem;	Space between grid or flex items without extra margins.
font-size: 1.3rem;	Size of the text.
text-align: center;	Centres inline content such as text.
font-weight: 600;	Thickness of the text.
input:not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
border: 0;	Removes the default border (for example on an iframe or button).
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Browser offers to save the password
- Checkbox label is clickable
- Card never wider than 22rem
- Password minimum length enforced

Exercises

1. Add a show/hide password button.
2. Add a 'Sign in with...' divider using ::before/::after lines.
3. Show a friendly error message region with aria-live.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 386: Login form for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 1 | Files: index.html, styles.css

Brief

Build a compact sign-in card with email, password, remember-me checkbox and a link, using the correct autocomplete tokens so password managers work.

Learning goals

- Use autocomplete="username" and "current-password"
- Wrap a checkbox in its label
- Size a card with min()

Elements and CSS used

HTML elements	CSS features
form, h1, label, input, button, p, a	width: min(), box-shadow, :not(), display: flex, align-items

Build guide

1. Write the form with labels before each input.
2. Add autocomplete tokens and minlength on the password.
3. Wrap the checkbox inside its label.
4. Make the form a grid with small gaps.
5. Exclude the checkbox from the input styling with :not([type=checkbox]).
6. Centre the card.

Project 386: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - Sign in</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <form class="login" action="/login" method="post">
      <h1>Sign in to Oasis Plant Nursery</h1>
      <label for="user">Email</label>
      <input id="user" name="email" type="email" required
autocomplete="username">
      <label for="pass">Password</label>
      <input id="pass" name="password" type="password" required
minlength="8" autocomplete="current-password">
      <label class="check"><input type="checkbox" name="remember">
Remember me</label>
      <button type="submit">Sign in</button>
      <p><a href="forgot.html">Forgot your password?</a></p>
    </form>
  </main>
</body>
</html>
```

Project 386: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.login { width: min(100%, 22rem); background: #fff; padding: 2rem;
border-radius: 14px; box-shadow: 0 8px 24px rgb(0 0 0 / 10%); display:
 grid; gap: .4rem; }
h1 { font-size: 1.3rem; margin: 0 0 1rem; text-align: center; }
label { font-weight: 600; font-size: .9rem; }
input:not([type="checkbox"]) { padding: .65rem .8rem; border: 1px
solid #bbb; border-radius: 8px; font: inherit; margin-bottom: .6rem; }
.check { display: flex; align-items: center; gap: .4rem; font-weight:
400; }
button { margin-top: .5rem; padding: .75rem; border: 0; border-radius:
 8px; background: var(--brand); color: #fff; font: inherit; cursor:
```

```
pointer; }
p { text-align: center; font-size: .9rem; }
```

Project 386 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - Sign in</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<form class="login" action="/login" method="post">	A form; action is where the data goes, method how it is sent.
Sign in to Oasis Plant Nursery	The main heading; only one per page.
<label for="user">Email</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="user" name="email" type="email" required autocomplete="u...	Email field: validated automatically and shows the @ keyboard on phones.
<input id="pass" name="password" type="password" required minlength...	Password field: characters are hidden.

Line	What it does
<label class="check"><input type="checkbox" name="remember"> Rememb...	Checkbox: on or off.
<button type="submit">Sign in</button>	A clickable button; inside a form it submits by default.
Forgot your password?	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.

Declaration	What it does
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
width: min(100%, 22rem);	Uses the smaller of the listed values.
border-radius: 14px;	Rounds the corners.
box-shadow: 0 8px 24px rgb(0 0 0 / 10%);	Soft shadow that lifts the element from the page.
gap: .4rem;	Space between grid or flex items without extra margins.
font-size: 1.3rem;	Size of the text.
text-align: center;	Centres inline content such as text.
font-weight: 600;	Thickness of the text.
input:not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
border: 0;	Removes the default border (for example on an iframe or button).
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Browser offers to save the password
- Checkbox label is clickable
- Card never wider than 22rem
- Password minimum length enforced

Exercises

1. Add a show/hide password button.
2. Add a 'Sign in with...' divider using ::before/::after lines.
3. Show a friendly error message region with aria-live.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 387: Login form for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 1 | Files: index.html, styles.css

Brief

Build a compact sign-in card with email, password, remember-me checkbox and a link, using the correct autocomplete tokens so password managers work.

Learning goals

- Use autocomplete="username" and "current-password"
- Wrap a checkbox in its label
- Size a card with min()

Elements and CSS used

HTML elements	CSS features
form, h1, label, input, button, p, a	width: min(), box-shadow, :not(), display: flex, align-items

Build guide

1. Write the form with labels before each input.
2. Add autocomplete tokens and minlength on the password.
3. Wrap the checkbox inside its label.
4. Make the form a grid with small gaps.
5. Exclude the checkbox from the input styling with :not([type=checkbox]).
6. Centre the card.

Project 387: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - Sign in</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <form class="login" action="/login" method="post">
      <h1>Sign in to Cedar Furniture</h1>
      <label for="user">Email</label>
      <input id="user" name="email" type="email" required
autocomplete="username">
      <label for="pass">Password</label>
      <input id="pass" name="password" type="password" required
minlength="8" autocomplete="current-password">
      <label class="check"><input type="checkbox" name="remember">
Remember me</label>
      <button type="submit">Sign in</button>
      <p><a href="forgot.html">Forgot your password?</a></p>
    </form>
  </main>
</body>
</html>
```

Project 387: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.login { width: min(100%, 22rem); background: #fff; padding: 2rem;
border-radius: 14px; box-shadow: 0 8px 24px rgb(0 0 0 / 10%); display:
 grid; gap: .4rem; }
h1 { font-size: 1.3rem; margin: 0 0 1rem; text-align: center; }
label { font-weight: 600; font-size: .9rem; }
input:not([type="checkbox"]) { padding: .65rem .8rem; border: 1px
solid #bbb; border-radius: 8px; font: inherit; margin-bottom: .6rem; }
.check { display: flex; align-items: center; gap: .4rem; font-weight:
400; }
button { margin-top: .5rem; padding: .75rem; border: 0; border-radius:
 8px; background: var(--brand); color: #fff; font: inherit; cursor:
```

```
pointer; }
p { text-align: center; font-size: .9rem; }
```

Project 387 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - Sign in</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<form class="login" action="/login" method="post">	A form; action is where the data goes, method how it is sent.
Sign in to Cedar Furniture	The main heading; only one per page.
<label for="user">Email</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="user" name="email" type="email" required autocomplete="u...	Email field: validated automatically and shows the @ keyboard on phones.
<input id="pass" name="password" type="password" required minlength...	Password field: characters are hidden.

Line	What it does
<label class="check"><input type="checkbox" name="remember"> Rememb...	Checkbox: on or off.
<button type="submit">Sign in</button>	A clickable button; inside a form it submits by default.
Forgot your password?	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.

Declaration	What it does
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
width: min(100%, 22rem);	Uses the smaller of the listed values.
border-radius: 14px;	Rounds the corners.
box-shadow: 0 8px 24px rgb(0 0 0 / 10%);	Soft shadow that lifts the element from the page.
gap: .4rem;	Space between grid or flex items without extra margins.
font-size: 1.3rem;	Size of the text.
text-align: center;	Centres inline content such as text.
font-weight: 600;	Thickness of the text.
input:not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
border: 0;	Removes the default border (for example on an iframe or button).
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Browser offers to save the password
- Checkbox label is clickable
- Card never wider than 22rem
- Password minimum length enforced

Exercises

1. Add a show/hide password button.
2. Add a 'Sign in with...' divider using ::before/::after lines.
3. Show a friendly error message region with aria-live.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 388: Login form for Byte Repair

Theme: Byte Repair (Nasr City) | Level 1 | Files: index.html, styles.css

Brief

Build a compact sign-in card with email, password, remember-me checkbox and a link, using the correct autocomplete tokens so password managers work.

Learning goals

- Use autocomplete="username" and "current-password"
- Wrap a checkbox in its label
- Size a card with min()

Elements and CSS used

HTML elements	CSS features
form, h1, label, input, button, p, a	width: min(), box-shadow, :not(), display: flex, align-items

Build guide

1. Write the form with labels before each input.
2. Add autocomplete tokens and minlength on the password.
3. Wrap the checkbox inside its label.
4. Make the form a grid with small gaps.
5. Exclude the checkbox from the input styling with :not([type=checkbox]).
6. Centre the card.

Project 388: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - Sign in</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <form class="login" action="/login" method="post">
      <h1>Sign in to Byte Repair</h1>
      <label for="user">Email</label>
      <input id="user" name="email" type="email" required
autocomplete="username">
      <label for="pass">Password</label>
      <input id="pass" name="password" type="password" required
minlength="8" autocomplete="current-password">
      <label class="check"><input type="checkbox" name="remember">
Remember me</label>
      <button type="submit">Sign in</button>
      <p><a href="forgot.html">Forgot your password?</a></p>
    </form>
  </main>
</body>
</html>
```

Project 388: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.login { width: min(100%, 22rem); background: #fff; padding: 2rem;
border-radius: 14px; box-shadow: 0 8px 24px rgb(0 0 0 / 10%); display:
 grid; gap: .4rem; }
h1 { font-size: 1.3rem; margin: 0 0 1rem; text-align: center; }
label { font-weight: 600; font-size: .9rem; }
input:not([type="checkbox"]) { padding: .65rem .8rem; border: 1px
solid #bbb; border-radius: 8px; font: inherit; margin-bottom: .6rem; }
.check { display: flex; align-items: center; gap: .4rem; font-weight:
400; }
button { margin-top: .5rem; padding: .75rem; border: 0; border-radius:
 8px; background: var(--brand); color: #fff; font: inherit; cursor:
```

```
pointer; }
p { text-align: center; font-size: .9rem; }
```

Project 388 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - Sign in</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<form class="login" action="/login" method="post">	A form; action is where the data goes, method how it is sent.
Sign in to Byte Repair	The main heading; only one per page.
<label for="user">Email</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="user" name="email" type="email" required autocomplete="u...	Email field: validated automatically and shows the @ keyboard on phones.
<input id="pass" name="password" type="password" required minlength...	Password field: characters are hidden.

Line	What it does
<label class="check"><input type="checkbox" name="remember"> Rememb...	Checkbox: on or off.
<button type="submit">Sign in</button>	A clickable button; inside a form it submits by default.
Forgot your password?	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.

Declaration	What it does
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
width: min(100%, 22rem);	Uses the smaller of the listed values.
border-radius: 14px;	Rounds the corners.
box-shadow: 0 8px 24px rgb(0 0 0 / 10%);	Soft shadow that lifts the element from the page.
gap: .4rem;	Space between grid or flex items without extra margins.
font-size: 1.3rem;	Size of the text.
text-align: center;	Centres inline content such as text.
font-weight: 600;	Thickness of the text.
input:not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
border: 0;	Removes the default border (for example on an iframe or button).
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Browser offers to save the password
- Checkbox label is clickable
- Card never wider than 22rem
- Password minimum length enforced

Exercises

1. Add a show/hide password button.
2. Add a 'Sign in with...' divider using ::before/::after lines.
3. Show a friendly error message region with aria-live.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 389: Login form for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 1 | Files: index.html, styles.css

Brief

Build a compact sign-in card with email, password, remember-me checkbox and a link, using the correct autocomplete tokens so password managers work.

Learning goals

- Use autocomplete="username" and "current-password"
- Wrap a checkbox in its label
- Size a card with min()

Elements and CSS used

HTML elements	CSS features
form, h1, label, input, button, p, a	width: min(), box-shadow, :not(), display: flex, align-items

Build guide

1. Write the form with labels before each input.
2. Add autocomplete tokens and minlength on the password.
3. Wrap the checkbox inside its label.
4. Make the form a grid with small gaps.
5. Exclude the checkbox from the input styling with :not([type=checkbox]).
6. Centre the card.

Project 389: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - Sign in</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <form class="login" action="/login" method="post">
      <h1>Sign in to Sahara Pet Care</h1>
      <label for="user">Email</label>
      <input id="user" name="email" type="email" required
autocomplete="username">
      <label for="pass">Password</label>
      <input id="pass" name="password" type="password" required
minlength="8" autocomplete="current-password">
      <label class="check"><input type="checkbox" name="remember">
Remember me</label>
      <button type="submit">Sign in</button>
      <p><a href="forgot.html">Forgot your password?</a></p>
    </form>
  </main>
</body>
</html>
```

Project 389: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.login { width: min(100%, 22rem); background: #fff; padding: 2rem;
border-radius: 14px; box-shadow: 0 8px 24px rgb(0 0 0 / 10%); display:
 grid; gap: .4rem; }
h1 { font-size: 1.3rem; margin: 0 0 1rem; text-align: center; }
label { font-weight: 600; font-size: .9rem; }
input:not([type="checkbox"]) { padding: .65rem .8rem; border: 1px
solid #bbb; border-radius: 8px; font: inherit; margin-bottom: .6rem; }
.check { display: flex; align-items: center; gap: .4rem; font-weight:
400; }
button { margin-top: .5rem; padding: .75rem; border: 0; border-radius:
 8px; background: var(--brand); color: #fff; font: inherit; cursor:
```

```
pointer; }
p { text-align: center; font-size: .9rem; }
```

Project 389 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - Sign in</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<form class="login" action="/login" method="post">	A form; action is where the data goes, method how it is sent.
Sign in to Sahara Pet Care	The main heading; only one per page.
<label for="user">Email</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="user" name="email" type="email" required autocomplete="u...	Email field: validated automatically and shows the @ keyboard on phones.
<input id="pass" name="password" type="password" required minlength...	Password field: characters are hidden.

Line	What it does
<label class="check"><input type="checkbox" name="remember"> Rememb...	Checkbox: on or off.
<button type="submit">Sign in</button>	A clickable button; inside a form it submits by default.
Forgot your password?	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.

Declaration	What it does
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
width: min(100%, 22rem);	Uses the smaller of the listed values.
border-radius: 14px;	Rounds the corners.
box-shadow: 0 8px 24px rgb(0 0 0 / 10%);	Soft shadow that lifts the element from the page.
gap: .4rem;	Space between grid or flex items without extra margins.
font-size: 1.3rem;	Size of the text.
text-align: center;	Centres inline content such as text.
font-weight: 600;	Thickness of the text.
input:not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
border: 0;	Removes the default border (for example on an iframe or button).
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Browser offers to save the password
- Checkbox label is clickable
- Card never wider than 22rem
- Password minimum length enforced

Exercises

1. Add a show/hide password button.
2. Add a 'Sign in with...' divider using ::before/::after lines.
3. Show a friendly error message region with aria-live.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 390: Login form for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Build a compact sign-in card with email, password, remember-me checkbox and a link, using the correct autocomplete tokens so password managers work.

Learning goals

- Use autocomplete="username" and "current-password"
- Wrap a checkbox in its label
- Size a card with min()

Elements and CSS used

HTML elements	CSS features
form, h1, label, input, button, p, a	width: min(), box-shadow, :not(), display: flex, align-items

Build guide

1. Write the form with labels before each input.
2. Add autocomplete tokens and minlength on the password.
3. Wrap the checkbox inside its label.
4. Make the form a grid with small gaps.
5. Exclude the checkbox from the input styling with :not([type=checkbox]).
6. Centre the card.

Project 390: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - Sign in</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <form class="login" action="/login" method="post">
      <h1>Sign in to Alexandria Sailing School</h1>
      <label for="user">Email</label>
      <input id="user" name="email" type="email" required
autocomplete="username">
      <label for="pass">Password</label>
      <input id="pass" name="password" type="password" required
minlength="8" autocomplete="current-password">
      <label class="check"><input type="checkbox" name="remember">
Remember me</label>
      <button type="submit">Sign in</button>
      <p><a href="forgot.html">Forgot your password?</a></p>
    </form>
  </main>
</body>
</html>
```

Project 390: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.login { width: min(100%, 22rem); background: #fff; padding: 2rem;
border-radius: 14px; box-shadow: 0 8px 24px rgb(0 0 0 / 10%); display:
 grid; gap: .4rem; }
h1 { font-size: 1.3rem; margin: 0 0 1rem; text-align: center; }
label { font-weight: 600; font-size: .9rem; }
input:not([type="checkbox"]) { padding: .65rem .8rem; border: 1px
solid #bbb; border-radius: 8px; font: inherit; margin-bottom: .6rem; }
.check { display: flex; align-items: center; gap: .4rem; font-weight:
400; }
button { margin-top: .5rem; padding: .75rem; border: 0; border-radius:
 8px; background: var(--brand); color: #fff; font: inherit; cursor:
```

```
pointer; }
p { text-align: center; font-size: .9rem; }
```

Project 390 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - Sign in</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<form class="login" action="/login" method="post">	A form; action is where the data goes, method how it is sent.
Sign in to Alexandria Sailing School	The main heading; only one per page.
<label for="user">Email</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="user" name="email" type="email" required autocomplete="u...	Email field: validated automatically and shows the @ keyboard on phones.
<input id="pass" name="password" type="password" required minlength...	Password field: characters are hidden.

Line	What it does
<label class="check"><input type="checkbox" name="remember"> Rememb...	Checkbox: on or off.
<button type="submit">Sign in</button>	A clickable button; inside a form it submits by default.
Forgot your password?	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.

Declaration	What it does
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
width: min(100%, 22rem);	Uses the smaller of the listed values.
border-radius: 14px;	Rounds the corners.
box-shadow: 0 8px 24px rgb(0 0 0 / 10%);	Soft shadow that lifts the element from the page.
gap: .4rem;	Space between grid or flex items without extra margins.
font-size: 1.3rem;	Size of the text.
text-align: center;	Centres inline content such as text.
font-weight: 600;	Thickness of the text.
input:not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
border: 0;	Removes the default border (for example on an iframe or button).
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Browser offers to save the password
- Checkbox label is clickable
- Card never wider than 22rem
- Password minimum length enforced

Exercises

1. Add a show/hide password button.
2. Add a 'Sign in with...' divider using ::before/::after lines.
3. Show a friendly error message region with aria-live.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 391: Login form for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Build a compact sign-in card with email, password, remember-me checkbox and a link, using the correct autocomplete tokens so password managers work.

Learning goals

- Use autocomplete="username" and "current-password"
- Wrap a checkbox in its label
- Size a card with min()

Elements and CSS used

HTML elements	CSS features
form, h1, label, input, button, p, a	width: min(), box-shadow, :not(), display: flex, align-items

Build guide

1. Write the form with labels before each input.
2. Add autocomplete tokens and minlength on the password.
3. Wrap the checkbox inside its label.
4. Make the form a grid with small gaps.
5. Exclude the checkbox from the input styling with :not([type=checkbox]).
6. Centre the card.

Project 391: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - Sign in</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <form class="login" action="/login" method="post">
      <h1>Sign in to Habiba Handmade Jewellery</h1>
      <label for="user">Email</label>
      <input id="user" name="email" type="email" required
autocomplete="username">
      <label for="pass">Password</label>
      <input id="pass" name="password" type="password" required
minlength="8" autocomplete="current-password">
      <label class="check"><input type="checkbox" name="remember">
Remember me</label>
      <button type="submit">Sign in</button>
      <p><a href="forgot.html">Forgot your password?</a></p>
    </form>
  </main>
</body>
</html>
```

Project 391: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.login { width: min(100%, 22rem); background: #fff; padding: 2rem;
border-radius: 14px; box-shadow: 0 8px 24px rgb(0 0 0 / 10%); display:
 grid; gap: .4rem; }
h1 { font-size: 1.3rem; margin: 0 0 1rem; text-align: center; }
label { font-weight: 600; font-size: .9rem; }
input:not([type="checkbox"]) { padding: .65rem .8rem; border: 1px
solid #bbb; border-radius: 8px; font: inherit; margin-bottom: .6rem; }
.check { display: flex; align-items: center; gap: .4rem; font-weight:
400; }
button { margin-top: .5rem; padding: .75rem; border: 0; border-radius:
 8px; background: var(--brand); color: #fff; font: inherit; cursor:
```

```
pointer; }
p { text-align: center; font-size: .9rem; }
```

Project 391 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - Sign in</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<form class="login" action="/login" method="post">	A form; action is where the data goes, method how it is sent.
Sign in to Habiba Handmade Jewellery	The main heading; only one per page.
<label for="user">Email</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="user" name="email" type="email" required autocomplete="u...	Email field: validated automatically and shows the @ keyboard on phones.
<input id="pass" name="password" type="password" required minlength...	Password field: characters are hidden.

Line	What it does
<label class="check"><input type="checkbox" name="remember"> Rememb...	Checkbox: on or off.
<button type="submit">Sign in</button>	A clickable button; inside a form it submits by default.
Forgot your password?	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.

Declaration	What it does
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
width: min(100%, 22rem);	Uses the smaller of the listed values.
border-radius: 14px;	Rounds the corners.
box-shadow: 0 8px 24px rgb(0 0 0 / 10%);	Soft shadow that lifts the element from the page.
gap: .4rem;	Space between grid or flex items without extra margins.
font-size: 1.3rem;	Size of the text.
text-align: center;	Centres inline content such as text.
font-weight: 600;	Thickness of the text.
input:not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
border: 0;	Removes the default border (for example on an iframe or button).
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Browser offers to save the password
- Checkbox label is clickable
- Card never wider than 22rem
- Password minimum length enforced

Exercises

1. Add a show/hide password button.
2. Add a 'Sign in with...' divider using ::before/::after lines.
3. Show a friendly error message region with aria-live.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 392: Login form for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 1 | Files: index.html, styles.css

Brief

Build a compact sign-in card with email, password, remember-me checkbox and a link, using the correct autocomplete tokens so password managers work.

Learning goals

- Use autocomplete="username" and "current-password"
- Wrap a checkbox in its label
- Size a card with min()

Elements and CSS used

HTML elements	CSS features
form, h1, label, input, button, p, a	width: min(), box-shadow, :not(), display: flex, align-items

Build guide

1. Write the form with labels before each input.
2. Add autocomplete tokens and minlength on the password.
3. Wrap the checkbox inside its label.
4. Make the form a grid with small gaps.
5. Exclude the checkbox from the input styling with :not([type=checkbox]).
6. Centre the card.

Project 392: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - Sign in</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <form class="login" action="/login" method="post">
      <h1>Sign in to Fayoum Pottery Studio</h1>
      <label for="user">Email</label>
      <input id="user" name="email" type="email" required
autocomplete="username">
      <label for="pass">Password</label>
      <input id="pass" name="password" type="password" required
minlength="8" autocomplete="current-password">
      <label class="check"><input type="checkbox" name="remember">
Remember me</label>
      <button type="submit">Sign in</button>
      <p><a href="forgot.html">Forgot your password?</a></p>
    </form>
  </main>
</body>
</html>
```

Project 392: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.login { width: min(100%, 22rem); background: #fff; padding: 2rem;
border-radius: 14px; box-shadow: 0 8px 24px rgb(0 0 0 / 10%); display:
 grid; gap: .4rem; }
h1 { font-size: 1.3rem; margin: 0 0 1rem; text-align: center; }
label { font-weight: 600; font-size: .9rem; }
input:not([type="checkbox"]) { padding: .65rem .8rem; border: 1px
solid #bbb; border-radius: 8px; font: inherit; margin-bottom: .6rem; }
.check { display: flex; align-items: center; gap: .4rem; font-weight:
400; }
button { margin-top: .5rem; padding: .75rem; border: 0; border-radius:
 8px; background: var(--brand); color: #fff; font: inherit; cursor:
```

```
pointer; }
p { text-align: center; font-size: .9rem; }
```

Project 392 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - Sign in</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<form class="login" action="/login" method="post">	A form; action is where the data goes, method how it is sent.
Sign in to Fayoum Pottery Studio	The main heading; only one per page.
<label for="user">Email</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="user" name="email" type="email" required autocomplete="u...	Email field: validated automatically and shows the @ keyboard on phones.
<input id="pass" name="password" type="password" required minlength...	Password field: characters are hidden.

Line	What it does
<label class="check"><input type="checkbox" name="remember"> Rememb...	Checkbox: on or off.
<button type="submit">Sign in</button>	A clickable button; inside a form it submits by default.
Forgot your password?	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.

Declaration	What it does
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
width: min(100%, 22rem);	Uses the smaller of the listed values.
border-radius: 14px;	Rounds the corners.
box-shadow: 0 8px 24px rgb(0 0 0 / 10%);	Soft shadow that lifts the element from the page.
gap: .4rem;	Space between grid or flex items without extra margins.
font-size: 1.3rem;	Size of the text.
text-align: center;	Centres inline content such as text.
font-weight: 600;	Thickness of the text.
input:not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
border: 0;	Removes the default border (for example on an iframe or button).
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Browser offers to save the password
- Checkbox label is clickable
- Card never wider than 22rem
- Password minimum length enforced

Exercises

1. Add a show/hide password button.
2. Add a 'Sign in with...' divider using ::before/::after lines.
3. Show a friendly error message region with aria-live.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 393: Login form for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 1 | Files: index.html, styles.css

Brief

Build a compact sign-in card with email, password, remember-me checkbox and a link, using the correct autocomplete tokens so password managers work.

Learning goals

- Use autocomplete="username" and "current-password"
- Wrap a checkbox in its label
- Size a card with min()

Elements and CSS used

HTML elements	CSS features
form, h1, label, input, button, p, a	width: min(), box-shadow, :not(), display: flex, align-items

Build guide

1. Write the form with labels before each input.
2. Add autocomplete tokens and minlength on the password.
3. Wrap the checkbox inside its label.
4. Make the form a grid with small gaps.
5. Exclude the checkbox from the input styling with :not([type=checkbox]).
6. Centre the card.

Project 393: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - Sign in</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <form class="login" action="/login" method="post">
      <h1>Sign in to Cleopatra Beauty Salon</h1>
      <label for="user">Email</label>
      <input id="user" name="email" type="email" required
autocomplete="username">
      <label for="pass">Password</label>
      <input id="pass" name="password" type="password" required
minlength="8" autocomplete="current-password">
      <label class="check"><input type="checkbox" name="remember">
Remember me</label>
      <button type="submit">Sign in</button>
      <p><a href="forgot.html">Forgot your password?</a></p>
    </form>
  </main>
</body>
</html>
```

Project 393: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.login { width: min(100%, 22rem); background: #fff; padding: 2rem;
border-radius: 14px; box-shadow: 0 8px 24px rgb(0 0 0 / 10%); display:
 grid; gap: .4rem; }
h1 { font-size: 1.3rem; margin: 0 0 1rem; text-align: center; }
label { font-weight: 600; font-size: .9rem; }
input:not([type="checkbox"]) { padding: .65rem .8rem; border: 1px
solid #bbb; border-radius: 8px; font: inherit; margin-bottom: .6rem; }
.check { display: flex; align-items: center; gap: .4rem; font-weight:
400; }
button { margin-top: .5rem; padding: .75rem; border: 0; border-radius:
 8px; background: var(--brand); color: #fff; font: inherit; cursor:
```

```
pointer; }
p { text-align: center; font-size: .9rem; }
```

Project 393 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - Sign in</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<form class="login" action="/login" method="post">	A form; action is where the data goes, method how it is sent.
Sign in to Cleopatra Beauty Salon	The main heading; only one per page.
<label for="user">Email</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="user" name="email" type="email" required autocomplete="u...	Email field: validated automatically and shows the @ keyboard on phones.
<input id="pass" name="password" type="password" required minlength...	Password field: characters are hidden.

Line	What it does
<label class="check"><input type="checkbox" name="remember"> Rememb...	Checkbox: on or off.
<button type="submit">Sign in</button>	A clickable button; inside a form it submits by default.
Forgot your password?	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.

Declaration	What it does
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
width: min(100%, 22rem);	Uses the smaller of the listed values.
border-radius: 14px;	Rounds the corners.
box-shadow: 0 8px 24px rgb(0 0 0 / 10%);	Soft shadow that lifts the element from the page.
gap: .4rem;	Space between grid or flex items without extra margins.
font-size: 1.3rem;	Size of the text.
text-align: center;	Centres inline content such as text.
font-weight: 600;	Thickness of the text.
input:not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
border: 0;	Removes the default border (for example on an iframe or button).
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Browser offers to save the password
- Checkbox label is clickable
- Card never wider than 22rem
- Password minimum length enforced

Exercises

1. Add a show/hide password button.
2. Add a 'Sign in with...' divider using ::before/::after lines.
3. Show a friendly error message region with aria-live.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 394: Login form for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 1 | Files: index.html, styles.css

Brief

Build a compact sign-in card with email, password, remember-me checkbox and a link, using the correct autocomplete tokens so password managers work.

Learning goals

- Use autocomplete="username" and "current-password"
- Wrap a checkbox in its label
- Size a card with min()

Elements and CSS used

HTML elements	CSS features
form, h1, label, input, button, p, a	width: min(), box-shadow, :not(), display: flex, align-items

Build guide

1. Write the form with labels before each input.
2. Add autocomplete tokens and minlength on the password.
3. Wrap the checkbox inside its label.
4. Make the form a grid with small gaps.
5. Exclude the checkbox from the input styling with :not([type=checkbox]).
6. Centre the card.

Project 394: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - Sign in</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <form class="login" action="/login" method="post">
      <h1>Sign in to Suez Auto Service</h1>
      <label for="user">Email</label>
      <input id="user" name="email" type="email" required
autocomplete="username">
      <label for="pass">Password</label>
      <input id="pass" name="password" type="password" required
minlength="8" autocomplete="current-password">
      <label class="check"><input type="checkbox" name="remember">
Remember me</label>
      <button type="submit">Sign in</button>
      <p><a href="forgot.html">Forgot your password?</a></p>
    </form>
  </main>
</body>
</html>
```

Project 394: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.login { width: min(100%, 22rem); background: #fff; padding: 2rem;
border-radius: 14px; box-shadow: 0 8px 24px rgb(0 0 0 / 10%); display:
 grid; gap: .4rem; }
h1 { font-size: 1.3rem; margin: 0 0 1rem; text-align: center; }
label { font-weight: 600; font-size: .9rem; }
input:not([type="checkbox"]) { padding: .65rem .8rem; border: 1px
solid #bbb; border-radius: 8px; font: inherit; margin-bottom: .6rem; }
.check { display: flex; align-items: center; gap: .4rem; font-weight:
400; }
button { margin-top: .5rem; padding: .75rem; border: 0; border-radius:
 8px; background: var(--brand); color: #fff; font: inherit; cursor:
```

```
pointer; }
p { text-align: center; font-size: .9rem; }
```

Project 394 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - Sign in</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<form class="login" action="/login" method="post">	A form; action is where the data goes, method how it is sent.
Sign in to Suez Auto Service	The main heading; only one per page.
<label for="user">Email</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="user" name="email" type="email" required autocomplete="u...	Email field: validated automatically and shows the @ keyboard on phones.
<input id="pass" name="password" type="password" required minlength...	Password field: characters are hidden.

Line	What it does
<label class="check"><input type="checkbox" name="remember"> Rememb...	Checkbox: on or off.
<button type="submit">Sign in</button>	A clickable button; inside a form it submits by default.
Forgot your password?	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.

Declaration	What it does
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
width: min(100%, 22rem);	Uses the smaller of the listed values.
border-radius: 14px;	Rounds the corners.
box-shadow: 0 8px 24px rgb(0 0 0 / 10%);	Soft shadow that lifts the element from the page.
gap: .4rem;	Space between grid or flex items without extra margins.
font-size: 1.3rem;	Size of the text.
text-align: center;	Centres inline content such as text.
font-weight: 600;	Thickness of the text.
input:not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
border: 0;	Removes the default border (for example on an iframe or button).
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Browser offers to save the password
- Checkbox label is clickable
- Card never wider than 22rem
- Password minimum length enforced

Exercises

1. Add a show/hide password button.
2. Add a 'Sign in with...' divider using ::before/::after lines.
3. Show a friendly error message region with aria-live.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 395: Login form for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 1 | Files: index.html, styles.css

Brief

Build a compact sign-in card with email, password, remember-me checkbox and a link, using the correct autocomplete tokens so password managers work.

Learning goals

- Use autocomplete="username" and "current-password"
- Wrap a checkbox in its label
- Size a card with min()

Elements and CSS used

HTML elements	CSS features
form, h1, label, input, button, p, a	width: min(), box-shadow, :not(), display: flex, align-items

Build guide

1. Write the form with labels before each input.
2. Add autocomplete tokens and minlength on the password.
3. Wrap the checkbox inside its label.
4. Make the form a grid with small gaps.
5. Exclude the checkbox from the input styling with :not([type=checkbox]).
6. Centre the card.

Project 395: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - Sign in</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <form class="login" action="/login" method="post">
      <h1>Sign in to Luxor Music Academy</h1>
      <label for="user">Email</label>
      <input id="user" name="email" type="email" required
autocomplete="username">
      <label for="pass">Password</label>
      <input id="pass" name="password" type="password" required
minlength="8" autocomplete="current-password">
      <label class="check"><input type="checkbox" name="remember">
Remember me</label>
      <button type="submit">Sign in</button>
      <p><a href="forgot.html">Forgot your password?</a></p>
    </form>
  </main>
</body>
</html>
```

Project 395: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.login { width: min(100%, 22rem); background: #fff; padding: 2rem;
border-radius: 14px; box-shadow: 0 8px 24px rgb(0 0 0 / 10%); display:
 grid; gap: .4rem; }
h1 { font-size: 1.3rem; margin: 0 0 1rem; text-align: center; }
label { font-weight: 600; font-size: .9rem; }
input:not([type="checkbox"]) { padding: .65rem .8rem; border: 1px
solid #bbb; border-radius: 8px; font: inherit; margin-bottom: .6rem; }
.check { display: flex; align-items: center; gap: .4rem; font-weight:
400; }
button { margin-top: .5rem; padding: .75rem; border: 0; border-radius:
 8px; background: var(--brand); color: #fff; font: inherit; cursor:
```

```
pointer; }
p { text-align: center; font-size: .9rem; }
```

Project 395 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - Sign in</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<form class="login" action="/login" method="post">	A form; action is where the data goes, method how it is sent.
Sign in to Luxor Music Academy	The main heading; only one per page.
<label for="user">Email</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="user" name="email" type="email" required autocomplete="u...	Email field: validated automatically and shows the @ keyboard on phones.
<input id="pass" name="password" type="password" required minlength...	Password field: characters are hidden.

Line	What it does
<label class="check"><input type="checkbox" name="remember"> Rememb...	Checkbox: on or off.
<button type="submit">Sign in</button>	A clickable button; inside a form it submits by default.
Forgot your password?	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.

Declaration	What it does
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
width: min(100%, 22rem);	Uses the smaller of the listed values.
border-radius: 14px;	Rounds the corners.
box-shadow: 0 8px 24px rgb(0 0 0 / 10%);	Soft shadow that lifts the element from the page.
gap: .4rem;	Space between grid or flex items without extra margins.
font-size: 1.3rem;	Size of the text.
text-align: center;	Centres inline content such as text.
font-weight: 600;	Thickness of the text.
input:not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
border: 0;	Removes the default border (for example on an iframe or button).
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Browser offers to save the password
- Checkbox label is clickable
- Card never wider than 22rem
- Password minimum length enforced

Exercises

1. Add a show/hide password button.
2. Add a 'Sign in with...' divider using ::before/::after lines.
3. Show a friendly error message region with aria-live.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 396: Login form for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 1 | Files: index.html, styles.css

Brief

Build a compact sign-in card with email, password, remember-me checkbox and a link, using the correct autocomplete tokens so password managers work.

Learning goals

- Use autocomplete="username" and "current-password"
- Wrap a checkbox in its label
- Size a card with min()

Elements and CSS used

HTML elements	CSS features
form, h1, label, input, button, p, a	width: min(), box-shadow, :not(), display: flex, align-items

Build guide

1. Write the form with labels before each input.
2. Add autocomplete tokens and minlength on the password.
3. Wrap the checkbox inside its label.
4. Make the form a grid with small gaps.
5. Exclude the checkbox from the input styling with :not([type=checkbox]).
6. Centre the card.

Project 396: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - Sign in</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <form class="login" action="/login" method="post">
      <h1>Sign in to Port Said Seafood</h1>
      <label for="user">Email</label>
      <input id="user" name="email" type="email" required
autocomplete="username">
      <label for="pass">Password</label>
      <input id="pass" name="password" type="password" required
minlength="8" autocomplete="current-password">
      <label class="check"><input type="checkbox" name="remember">
Remember me</label>
      <button type="submit">Sign in</button>
      <p><a href="forgot.html">Forgot your password?</a></p>
    </form>
  </main>
</body>
</html>
```

Project 396: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.login { width: min(100%, 22rem); background: #fff; padding: 2rem;
border-radius: 14px; box-shadow: 0 8px 24px rgb(0 0 0 / 10%); display:
 grid; gap: .4rem; }
h1 { font-size: 1.3rem; margin: 0 0 1rem; text-align: center; }
label { font-weight: 600; font-size: .9rem; }
input:not([type="checkbox"]) { padding: .65rem .8rem; border: 1px
solid #bbb; border-radius: 8px; font: inherit; margin-bottom: .6rem; }
.check { display: flex; align-items: center; gap: .4rem; font-weight:
400; }
button { margin-top: .5rem; padding: .75rem; border: 0; border-radius:
 8px; background: var(--brand); color: #fff; font: inherit; cursor:
```

```
pointer; }
p { text-align: center; font-size: .9rem; }
```

Project 396 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - Sign in</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<form class="login" action="/login" method="post">	A form; action is where the data goes, method how it is sent.
Sign in to Port Said Seafood	The main heading; only one per page.
<label for="user">Email</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="user" name="email" type="email" required autocomplete="u...	Email field: validated automatically and shows the @ keyboard on phones.
<input id="pass" name="password" type="password" required minlength...	Password field: characters are hidden.

Line	What it does
<label class="check"><input type="checkbox" name="remember"> Rememb...	Checkbox: on or off.
<button type="submit">Sign in</button>	A clickable button; inside a form it submits by default.
Forgot your password?	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.

Declaration	What it does
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
width: min(100%, 22rem);	Uses the smaller of the listed values.
border-radius: 14px;	Rounds the corners.
box-shadow: 0 8px 24px rgb(0 0 0 / 10%);	Soft shadow that lifts the element from the page.
gap: .4rem;	Space between grid or flex items without extra margins.
font-size: 1.3rem;	Size of the text.
text-align: center;	Centres inline content such as text.
font-weight: 600;	Thickness of the text.
input:not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
border: 0;	Removes the default border (for example on an iframe or button).
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Browser offers to save the password
- Checkbox label is clickable
- Card never wider than 22rem
- Password minimum length enforced

Exercises

1. Add a show/hide password button.
2. Add a 'Sign in with...' divider using ::before/::after lines.
3. Show a friendly error message region with aria-live.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 397: Login form for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 1 | Files: index.html, styles.css

Brief

Build a compact sign-in card with email, password, remember-me checkbox and a link, using the correct autocomplete tokens so password managers work.

Learning goals

- Use autocomplete="username" and "current-password"
- Wrap a checkbox in its label
- Size a card with min()

Elements and CSS used

HTML elements	CSS features
form, h1, label, input, button, p, a	width: min(), box-shadow, :not(), display: flex, align-items

Build guide

1. Write the form with labels before each input.
2. Add autocomplete tokens and minlength on the password.
3. Wrap the checkbox inside its label.
4. Make the form a grid with small gaps.
5. Exclude the checkbox from the input styling with :not([type=checkbox]).
6. Centre the card.

Project 397: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - Sign in</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <form class="login" action="/login" method="post">
      <h1>Sign in to Delta Kids Library</h1>
      <label for="user">Email</label>
      <input id="user" name="email" type="email" required
autocomplete="username">
      <label for="pass">Password</label>
      <input id="pass" name="password" type="password" required
minlength="8" autocomplete="current-password">
      <label class="check"><input type="checkbox" name="remember">
Remember me</label>
      <button type="submit">Sign in</button>
      <p><a href="forgot.html">Forgot your password?</a></p>
    </form>
  </main>
</body>
</html>
```

Project 397: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.login { width: min(100%, 22rem); background: #fff; padding: 2rem;
border-radius: 14px; box-shadow: 0 8px 24px rgb(0 0 0 / 10%); display:
 grid; gap: .4rem; }
h1 { font-size: 1.3rem; margin: 0 0 1rem; text-align: center; }
label { font-weight: 600; font-size: .9rem; }
input:not([type="checkbox"]) { padding: .65rem .8rem; border: 1px
solid #bbb; border-radius: 8px; font: inherit; margin-bottom: .6rem; }
.check { display: flex; align-items: center; gap: .4rem; font-weight:
400; }
button { margin-top: .5rem; padding: .75rem; border: 0; border-radius:
 8px; background: var(--brand); color: #fff; font: inherit; cursor:
```

```
pointer; }
p { text-align: center; font-size: .9rem; }
```

Project 397 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - Sign in</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<form class="login" action="/login" method="post">	A form; action is where the data goes, method how it is sent.
Sign in to Delta Kids Library	The main heading; only one per page.
<label for="user">Email</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="user" name="email" type="email" required autocomplete="u...	Email field: validated automatically and shows the @ keyboard on phones.
<input id="pass" name="password" type="password" required minlength...	Password field: characters are hidden.

Line	What it does
<label class="check"><input type="checkbox" name="remember"> Rememb...	Checkbox: on or off.
<button type="submit">Sign in</button>	A clickable button; inside a form it submits by default.
Forgot your password?	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.

Declaration	What it does
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
width: min(100%, 22rem);	Uses the smaller of the listed values.
border-radius: 14px;	Rounds the corners.
box-shadow: 0 8px 24px rgb(0 0 0 / 10%);	Soft shadow that lifts the element from the page.
gap: .4rem;	Space between grid or flex items without extra margins.
font-size: 1.3rem;	Size of the text.
text-align: center;	Centres inline content such as text.
font-weight: 600;	Thickness of the text.
input:not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
border: 0;	Removes the default border (for example on an iframe or button).
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Browser offers to save the password
- Checkbox label is clickable
- Card never wider than 22rem
- Password minimum length enforced

Exercises

1. Add a show/hide password button.
2. Add a 'Sign in with...' divider using ::before/::after lines.
3. Show a friendly error message region with aria-live.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 398: Login form for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Build a compact sign-in card with email, password, remember-me checkbox and a link, using the correct autocomplete tokens so password managers work.

Learning goals

- Use autocomplete="username" and "current-password"
- Wrap a checkbox in its label
- Size a card with min()

Elements and CSS used

HTML elements	CSS features
form, h1, label, input, button, p, a	width: min(), box-shadow, :not(), display: flex, align-items

Build guide

1. Write the form with labels before each input.
2. Add autocomplete tokens and minlength on the password.
3. Wrap the checkbox inside its label.
4. Make the form a grid with small gaps.
5. Exclude the checkbox from the input styling with :not([type=checkbox]).
6. Centre the card.

Project 398: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - Sign in</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <form class="login" action="/login" method="post">
      <h1>Sign in to Nubian Guest House</h1>
      <label for="user">Email</label>
      <input id="user" name="email" type="email" required
autocomplete="username">
      <label for="pass">Password</label>
      <input id="pass" name="password" type="password" required
minlength="8" autocomplete="current-password">
      <label class="check"><input type="checkbox" name="remember">
Remember me</label>
      <button type="submit">Sign in</button>
      <p><a href="forgot.html">Forgot your password?</a></p>
    </form>
  </main>
</body>
</html>
```

Project 398: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.login { width: min(100%, 22rem); background: #fff; padding: 2rem;
border-radius: 14px; box-shadow: 0 8px 24px rgb(0 0 0 / 10%); display:
 grid; gap: .4rem; }
h1 { font-size: 1.3rem; margin: 0 0 1rem; text-align: center; }
label { font-weight: 600; font-size: .9rem; }
input:not([type="checkbox"]) { padding: .65rem .8rem; border: 1px
solid #bbb; border-radius: 8px; font: inherit; margin-bottom: .6rem; }
.check { display: flex; align-items: center; gap: .4rem; font-weight:
400; }
button { margin-top: .5rem; padding: .75rem; border: 0; border-radius:
 8px; background: var(--brand); color: #fff; font: inherit; cursor:
```

```
pointer; }
p { text-align: center; font-size: .9rem; }
```

Project 398 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - Sign in</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<form class="login" action="/login" method="post">	A form; action is where the data goes, method how it is sent.
Sign in to Nubian Guest House	The main heading; only one per page.
<label for="user">Email</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="user" name="email" type="email" required autocomplete="u...	Email field: validated automatically and shows the @ keyboard on phones.
<input id="pass" name="password" type="password" required minlength...	Password field: characters are hidden.

Line	What it does
<label class="check"><input type="checkbox" name="remember"> Rememb...	Checkbox: on or off.
<button type="submit">Sign in</button>	A clickable button; inside a form it submits by default.
Forgot your password?	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.

Declaration	What it does
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
width: min(100%, 22rem);	Uses the smaller of the listed values.
border-radius: 14px;	Rounds the corners.
box-shadow: 0 8px 24px rgb(0 0 0 / 10%);	Soft shadow that lifts the element from the page.
gap: .4rem;	Space between grid or flex items without extra margins.
font-size: 1.3rem;	Size of the text.
text-align: center;	Centres inline content such as text.
font-weight: 600;	Thickness of the text.
input:not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
border: 0;	Removes the default border (for example on an iframe or button).
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Browser offers to save the password
- Checkbox label is clickable
- Card never wider than 22rem
- Password minimum length enforced

Exercises

1. Add a show/hide password button.
2. Add a 'Sign in with...' divider using ::before/::after lines.
3. Show a friendly error message region with aria-live.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 399: Login form for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 1 | Files: index.html, styles.css

Brief

Build a compact sign-in card with email, password, remember-me checkbox and a link, using the correct autocomplete tokens so password managers work.

Learning goals

- Use autocomplete="username" and "current-password"
- Wrap a checkbox in its label
- Size a card with min()

Elements and CSS used

HTML elements	CSS features
form, h1, label, input, button, p, a	width: min(), box-shadow, :not(), display: flex, align-items

Build guide

1. Write the form with labels before each input.
2. Add autocomplete tokens and minlength on the password.
3. Wrap the checkbox inside its label.
4. Make the form a grid with small gaps.
5. Exclude the checkbox from the input styling with :not([type=checkbox]).
6. Centre the card.

Project 399: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - Sign in</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <form class="login" action="/login" method="post">
      <h1>Sign in to Ismailia Cycling Store</h1>
      <label for="user">Email</label>
      <input id="user" name="email" type="email" required
autocomplete="username">
      <label for="pass">Password</label>
      <input id="pass" name="password" type="password" required
minlength="8" autocomplete="current-password">
      <label class="check"><input type="checkbox" name="remember">
Remember me</label>
      <button type="submit">Sign in</button>
      <p><a href="forgot.html">Forgot your password?</a></p>
    </form>
  </main>
</body>
</html>
```

Project 399: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.login { width: min(100%, 22rem); background: #fff; padding: 2rem;
border-radius: 14px; box-shadow: 0 8px 24px rgb(0 0 0 / 10%); display:
 grid; gap: .4rem; }
h1 { font-size: 1.3rem; margin: 0 0 1rem; text-align: center; }
label { font-weight: 600; font-size: .9rem; }
input:not([type="checkbox"]) { padding: .65rem .8rem; border: 1px
solid #bbb; border-radius: 8px; font: inherit; margin-bottom: .6rem; }
.check { display: flex; align-items: center; gap: .4rem; font-weight:
400; }
button { margin-top: .5rem; padding: .75rem; border: 0; border-radius:
 8px; background: var(--brand); color: #fff; font: inherit; cursor:
```

```
pointer; }
p { text-align: center; font-size: .9rem; }
```

Project 399 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - Sign in</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<form class="login" action="/login" method="post">	A form; action is where the data goes, method how it is sent.
Sign in to Ismailia Cycling Store	The main heading; only one per page.
<label for="user">Email</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="user" name="email" type="email" required autocomplete="u...	Email field: validated automatically and shows the @ keyboard on phones.
<input id="pass" name="password" type="password" required minlength...	Password field: characters are hidden.

Line	What it does
<label class="check"><input type="checkbox" name="remember"> Rememb...	Checkbox: on or off.
<button type="submit">Sign in</button>	A clickable button; inside a form it submits by default.
Forgot your password?	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.

Declaration	What it does
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
width: min(100%, 22rem);	Uses the smaller of the listed values.
border-radius: 14px;	Rounds the corners.
box-shadow: 0 8px 24px rgb(0 0 0 / 10%);	Soft shadow that lifts the element from the page.
gap: .4rem;	Space between grid or flex items without extra margins.
font-size: 1.3rem;	Size of the text.
text-align: center;	Centres inline content such as text.
font-weight: 600;	Thickness of the text.
input:not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
border: 0;	Removes the default border (for example on an iframe or button).
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Browser offers to save the password
- Checkbox label is clickable
- Card never wider than 22rem
- Password minimum length enforced

Exercises

1. Add a show/hide password button.
2. Add a 'Sign in with...' divider using ::before/::after lines.
3. Show a friendly error message region with aria-live.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 400: Login form for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 1 | Files: index.html, styles.css

Brief

Build a compact sign-in card with email, password, remember-me checkbox and a link, using the correct autocomplete tokens so password managers work.

Learning goals

- Use autocomplete="username" and "current-password"
- Wrap a checkbox in its label
- Size a card with min()

Elements and CSS used

HTML elements	CSS features
form, h1, label, input, button, p, a	width: min(), box-shadow, :not(), display: flex, align-items

Build guide

1. Write the form with labels before each input.
2. Add autocomplete tokens and minlength on the password.
3. Wrap the checkbox inside its label.
4. Make the form a grid with small gaps.
5. Exclude the checkbox from the input styling with :not([type=checkbox]).
6. Centre the card.

Project 400: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - Sign in</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <form class="login" action="/login" method="post">
      <h1>Sign in to Minya Coding Club</h1>
      <label for="user">Email</label>
      <input id="user" name="email" type="email" required
autocomplete="username">
      <label for="pass">Password</label>
      <input id="pass" name="password" type="password" required
minlength="8" autocomplete="current-password">
      <label class="check"><input type="checkbox" name="remember">
Remember me</label>
      <button type="submit">Sign in</button>
      <p><a href="forgot.html">Forgot your password?</a></p>
    </form>
  </main>
</body>
</html>
```

Project 400: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { min-height: 100vh; display: grid; place-items: center;
background: var(--accent); padding: 1rem; }
.login { width: min(100%, 22rem); background: #fff; padding: 2rem;
border-radius: 14px; box-shadow: 0 8px 24px rgb(0 0 0 / 10%); display:
 grid; gap: .4rem; }
h1 { font-size: 1.3rem; margin: 0 0 1rem; text-align: center; }
label { font-weight: 600; font-size: .9rem; }
input:not([type="checkbox"]) { padding: .65rem .8rem; border: 1px
solid #bbb; border-radius: 8px; font: inherit; margin-bottom: .6rem; }
.check { display: flex; align-items: center; gap: .4rem; font-weight:
400; }
button { margin-top: .5rem; padding: .75rem; border: 0; border-radius:
 8px; background: var(--brand); color: #fff; font: inherit; cursor:
```

```
pointer; }
p { text-align: center; font-size: .9rem; }
```

Project 400 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - Sign in</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<form class="login" action="/login" method="post">	A form; action is where the data goes, method how it is sent.
Sign in to Minya Coding Club	The main heading; only one per page.
<label for="user">Email</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="user" name="email" type="email" required autocomplete="u...	Email field: validated automatically and shows the @ keyboard on phones.
<input id="pass" name="password" type="password" required minlength...	Password field: characters are hidden.

Line	What it does
<label class="check"><input type="checkbox" name="remember"> Rememb...	Checkbox: on or off.
<button type="submit">Sign in</button>	A clickable button; inside a form it submits by default.
Forgot your password?	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.

Declaration	What it does
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--accent);	Background colour or image.
padding: 1rem;	Space inside the element between its border and content.
width: min(100%, 22rem);	Uses the smaller of the listed values.
border-radius: 14px;	Rounds the corners.
box-shadow: 0 8px 24px rgb(0 0 0 / 10%);	Soft shadow that lifts the element from the page.
gap: .4rem;	Space between grid or flex items without extra margins.
font-size: 1.3rem;	Size of the text.
text-align: center;	Centres inline content such as text.
font-weight: 600;	Thickness of the text.
input:not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
border: 0;	Removes the default border (for example on an iframe or button).
cursor: pointer;	Shows the hand cursor to indicate something clickable.

Check your work

- Browser offers to save the password
- Checkbox label is clickable
- Card never wider than 22rem
- Password minimum length enforced

Exercises

1. Add a show/hide password button.
2. Add a 'Sign in with...' divider using ::before/::after lines.
3. Show a friendly error message region with aria-live.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Vertical timeline

Level 2 | 25 projects, one per theme

Show the business history as an ordered list drawn as a vertical timeline with a line and dots, using only pseudo-elements.

Project 401: Vertical timeline for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 2 | Files: index.html, styles.css

Brief

Show the business history as an ordered list drawn as a vertical timeline with a line and dots, using only pseudo-elements.

Learning goals

- Use <ol> and <time> for dated events
- Draw a line and markers with ::before
- Combine relative and absolute positioning

Elements and CSS used

HTML elements	CSS features
ol, li, time, p	position: relative, position: absolute, ::before, border-radius: 50%, box-shadow ring

Build guide

1. Write an <ol class="timeline"> with a <time> and <p> per event.
2. Remove bullets and add left padding for the line.
3. Draw the vertical line with .timeline::before.
4. Draw a dot per item with li::before positioned to the left.
5. Style the year.
6. Check the datetime attributes are valid.

Project 401: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - History</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Our history</h1>
    <ol class="timeline">
      <li><time datetime="2018">2018</time><p>Mohamed Khattab opens
Cairo Book Shop in Giza.</p></li>
      <li><time datetime="2020">2020</time><p>Online ordering
launched.</p></li>
      <li><time datetime="2023">2023</time><p>Second location and new
books.</p></li>
      <li><time datetime="2026">2026</time><p>This website goes live.
</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 401: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.timeline { list-style: none; padding: 0 0 0 2rem; margin: 0;
position: relative; }
.timeline::before { content: ""; position: absolute; left: .55rem;
top: .3rem; bottom: .3rem; width: 3px; background: var(--line); }
.timeline li { position: relative; padding-bottom: 1.5rem; }
.timeline li::before { content: ""; position: absolute; left: -1.
85rem; top: .35rem; width: 1rem; height: 1rem; border-radius: 50%;
background: var(--brand); border: 3px solid #fff; box-shadow: 0 0 0
2px var(--brand); }
time { font-weight: 700; color: var(--brand); }
.timeline p { margin: .2rem 0 0; }
```

Project 401 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - History</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Our history	The main heading; only one per page.
<ol class="timeline">	Ordered (numbered) list; the order matters.
<time datetime="2018">2018</time><p>Mohamed Khattab opens Cairo...	A paragraph of text.
<time datetime="2020">2020</time><p>Online ordering launched.<//...	One list item.
<time datetime="2023">2023</time><p>Second location and new boo...	A date or time; datetime holds the machine-readable value.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: var(--line);	Background colour or image.

Declaration	What it does
border-radius: 50%;	Turns a square into a circle.
border: 3px solid #fff;	Changes the visual order of a flex item without changing the source.
box-shadow: 0 0 0 2px var(--brand);	Soft shadow that lifts the element from the page.
font-weight: 700;	Thickness of the text.

Check your work

- Events in chronological order
- Line runs from first dot to last
- Dots centred on the line
- Works when text wraps

Exercises

1. Alternate items left and right on wide screens.
2. Animate dots appearing with animation-timeline: view().
3. Add images to some events.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 402: Vertical timeline for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 2 | Files: index.html, styles.css

Brief

Show the business history as an ordered list drawn as a vertical timeline with a line and dots, using only pseudo-elements.

Learning goals

- Use <ol> and <time> for dated events
- Draw a line and markers with ::before
- Combine relative and absolute positioning

Elements and CSS used

HTML elements	CSS features
ol, li, time, p	position: relative, position: absolute, ::before, border-radius: 50%, box-shadow ring

Build guide

1. Write an <ol class="timeline"> with a <time> and <p> per event.
2. Remove bullets and add left padding for the line.
3. Draw the vertical line with .timeline::before.
4. Draw a dot per item with li::before positioned to the left.
5. Style the year.
6. Check the datetime attributes are valid.

Project 402: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - History</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Our history</h1>
    <ol class="timeline">
      <li><time datetime="2018">2018</time><p>Sara Adel opens Nile
Bakery in Cairo.</p></li>
      <li><time datetime="2020">2020</time><p>Online ordering
launched.</p></li>
      <li><time datetime="2023">2023</time><p>Second location and new
pastries.</p></li>
      <li><time datetime="2026">2026</time><p>This website goes live.
</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 402: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.timeline { list-style: none; padding: 0 0 0 2rem; margin: 0;
position: relative; }
.timeline::before { content: ""; position: absolute; left: .55rem;
top: .3rem; bottom: .3rem; width: 3px; background: var(--line); }
.timeline li { position: relative; padding-bottom: 1.5rem; }
.timeline li::before { content: ""; position: absolute; left: -1.
85rem; top: .35rem; width: 1rem; height: 1rem; border-radius: 50%;
background: var(--brand); border: 3px solid #fff; box-shadow: 0 0 0
2px var(--brand); }
time { font-weight: 700; color: var(--brand); }
.timeline p { margin: .2rem 0 0; }
```

Project 402 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - History</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Our history	The main heading; only one per page.
<ol class="timeline">	Ordered (numbered) list; the order matters.
<time datetime="2018">2018</time><p>Sara Adel opens Nile Bakery...	A paragraph of text.
<time datetime="2020">2020</time><p>Online ordering launched.</...	One list item.
<time datetime="2023">2023</time><p>Second location and new pas...	A date or time; datetime holds the machine-readable value.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: var(--line);	Background colour or image.

Declaration	What it does
border-radius: 50%;	Turns a square into a circle.
border: 3px solid #fff;	Changes the visual order of a flex item without changing the source.
box-shadow: 0 0 0 2px var(--brand);	Soft shadow that lifts the element from the page.
font-weight: 700;	Thickness of the text.

Check your work

- Events in chronological order
- Line runs from first dot to last
- Dots centred on the line
- Works when text wraps

Exercises

1. Alternate items left and right on wide screens.
2. Animate dots appearing with animation-timeline: view().
3. Add images to some events.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 403: Vertical timeline for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 2 | Files: index.html, styles.css

Brief

Show the business history as an ordered list drawn as a vertical timeline with a line and dots, using only pseudo-elements.

Learning goals

- Use <ol> and <time> for dated events
- Draw a line and markers with ::before
- Combine relative and absolute positioning

Elements and CSS used

HTML elements	CSS features
ol, li, time, p	position: relative, position: absolute, ::before, border-radius: 50%, box-shadow ring

Build guide

1. Write an <ol class="timeline"> with a <time> and <p> per event.
2. Remove bullets and add left padding for the line.
3. Draw the vertical line with .timeline::before.
4. Draw a dot per item with li::before positioned to the left.
5. Style the year.
6. Check the datetime attributes are valid.

Project 403: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - History</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Our history</h1>
    <ol class="timeline">
      <li><time datetime="2018">2018</time><p>Omar Farouk opens
Pyramid Fitness in 6th of October.</p></li>
      <li><time datetime="2020">2020</time><p>Online ordering
launched.</p></li>
      <li><time datetime="2023">2023</time><p>Second location and new
classes.</p></li>
      <li><time datetime="2026">2026</time><p>This website goes live.
</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 403: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.timeline { list-style: none; padding: 0 0 0 2rem; margin: 0;
position: relative; }
.timeline::before { content: ""; position: absolute; left: .55rem;
top: .3rem; bottom: .3rem; width: 3px; background: var(--line); }
.timeline li { position: relative; padding-bottom: 1.5rem; }
.timeline li::before { content: ""; position: absolute; left: -1.
85rem; top: .35rem; width: 1rem; height: 1rem; border-radius: 50%;
background: var(--brand); border: 3px solid #fff; box-shadow: 0 0 0
2px var(--brand); }
time { font-weight: 700; color: var(--brand); }
.timeline p { margin: .2rem 0 0; }
```

Project 403 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - History</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Our history	The main heading; only one per page.
<ol class="timeline">	Ordered (numbered) list; the order matters.
<time datetime="2018"> 2018</time><p>Omar Farouk opens Pyramid F...	A paragraph of text.
<time datetime="2020"> 2020</time><p>Online ordering launched.</...	One list item.
<time datetime="2023"> 2023</time><p>Second location and new cla...	A date or time; datetime holds the machine-readable value.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: var(--line);	Background colour or image.

Declaration	What it does
border-radius: 50%;	Turns a square into a circle.
border: 3px solid #fff;	Changes the visual order of a flex item without changing the source.
box-shadow: 0 0 0 2px var(--brand);	Soft shadow that lifts the element from the page.
font-weight: 700;	Thickness of the text.

Check your work

- Events in chronological order
- Line runs from first dot to last
- Dots centred on the line
- Works when text wraps

Exercises

1. Alternate items left and right on wide screens.
2. Animate dots appearing with animation-timeline: view().
3. Add images to some events.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 404: Vertical timeline for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 2 | Files: index.html, styles.css

Brief

Show the business history as an ordered list drawn as a vertical timeline with a line and dots, using only pseudo-elements.

Learning goals

- Use <ol> and <time> for dated events
- Draw a line and markers with ::before
- Combine relative and absolute positioning

Elements and CSS used

HTML elements	CSS features
ol, li, time, p	position: relative, position: absolute, ::before, border-radius: 50%, box-shadow ring

Build guide

1. Write an <ol class="timeline"> with a <time> and <p> per event.
2. Remove bullets and add left padding for the line.
3. Draw the vertical line with .timeline::before.
4. Draw a dot per item with li::before positioned to the left.
5. Style the year.
6. Check the datetime attributes are valid.

Project 404: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - History</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Our history</h1>
    <ol class="timeline">
      <li><time datetime="2018">2018</time><p>Dr. Hana Youssef opens
Delta Dental Clinic in Mansoura.</p></li>
      <li><time datetime="2020">2020</time><p>Online ordering
launched.</p></li>
      <li><time datetime="2023">2023</time><p>Second location and new
services.</p></li>
      <li><time datetime="2026">2026</time><p>This website goes live.
</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 404: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.timeline { list-style: none; padding: 0 0 0 2rem; margin: 0;
position: relative; }
.timeline::before { content: ""; position: absolute; left: .55rem;
top: .3rem; bottom: .3rem; width: 3px; background: var(--line); }
.timeline li { position: relative; padding-bottom: 1.5rem; }
.timeline li::before { content: ""; position: absolute; left: -1.
85rem; top: .35rem; width: 1rem; height: 1rem; border-radius: 50%;
background: var(--brand); border: 3px solid #fff; box-shadow: 0 0 0
2px var(--brand); }
time { font-weight: 700; color: var(--brand); }
.timeline p { margin: .2rem 0 0; }
```

Project 404 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - History</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Our history	The main heading; only one per page.
<ol class="timeline">	Ordered (numbered) list; the order matters.
<time datetime="2018"> 2018</time><p>Dr. Hana Youssef opens Delt...	A paragraph of text.
<time datetime="2020"> 2020</time><p>Online ordering launched.<//...	One list item.
<time datetime="2023"> 2023</time><p>Second location and new ser...	A date or time; datetime holds the machine-readable value.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: var(--line);	Background colour or image.

Declaration	What it does
border-radius: 50%;	Turns a square into a circle.
border: 3px solid #fff;	Changes the visual order of a flex item without changing the source.
box-shadow: 0 0 0 2px var(--brand);	Soft shadow that lifts the element from the page.
font-weight: 700;	Thickness of the text.

Check your work

- Events in chronological order
- Line runs from first dot to last
- Dots centred on the line
- Works when text wraps

Exercises

1. Alternate items left and right on wide screens.
2. Animate dots appearing with animation-timeline: view().
3. Add images to some events.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 405: Vertical timeline for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 2 | Files: index.html, styles.css

Brief

Show the business history as an ordered list drawn as a vertical timeline with a line and dots, using only pseudo-elements.

Learning goals

- Use <ol> and <time> for dated events
- Draw a line and markers with ::before
- Combine relative and absolute positioning

Elements and CSS used

HTML elements	CSS features
ol, li, time, p	position: relative, position: absolute, ::before, border-radius: 50%, box-shadow ring

Build guide

1. Write an <ol class="timeline"> with a <time> and <p> per event.
2. Remove bullets and add left padding for the line.
3. Draw the vertical line with .timeline::before.
4. Draw a dot per item with li::before positioned to the left.
5. Style the year.
6. Check the datetime attributes are valid.

Project 405: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - History</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Our history</h1>
    <ol class="timeline">
      <li><time datetime="2018">2018</time><p>Laila Mansour opens Red
Sea Travel in Hurghada.</p></li>
      <li><time datetime="2020">2020</time><p>Online ordering
launched.</p></li>
      <li><time datetime="2023">2023</time><p>Second location and new
tours.</p></li>
      <li><time datetime="2026">2026</time><p>This website goes live.
</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 405: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.timeline { list-style: none; padding: 0 0 0 2rem; margin: 0;
position: relative; }
.timeline::before { content: ""; position: absolute; left: .55rem;
top: .3rem; bottom: .3rem; width: 3px; background: var(--line); }
.timeline li { position: relative; padding-bottom: 1.5rem; }
.timeline li::before { content: ""; position: absolute; left: -1.
85rem; top: .35rem; width: 1rem; height: 1rem; border-radius: 50%;
background: var(--brand); border: 3px solid #fff; box-shadow: 0 0 0
2px var(--brand); }
time { font-weight: 700; color: var(--brand); }
.timeline p { margin: .2rem 0 0; }
```

Project 405 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - History</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Our history	The main heading; only one per page.
<ol class="timeline">	Ordered (numbered) list; the order matters.
<time datetime="2018"> 2018</time><p>Laila Mansour opens Red Sea...	A paragraph of text.
<time datetime="2020"> 2020</time><p>Online ordering launched.<//...	One list item.
<time datetime="2023"> 2023</time><p>Second location and new tou...	A date or time; datetime holds the machine-readable value.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: var(--line);	Background colour or image.

Declaration	What it does
border-radius: 50%;	Turns a square into a circle.
border: 3px solid #fff;	Changes the visual order of a flex item without changing the source.
box-shadow: 0 0 0 2px var(--brand);	Soft shadow that lifts the element from the page.
font-weight: 700;	Thickness of the text.

Check your work

- Events in chronological order
- Line runs from first dot to last
- Dots centred on the line
- Works when text wraps

Exercises

1. Alternate items left and right on wide screens.
2. Animate dots appearing with animation-timeline: view().
3. Add images to some events.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 406: Vertical timeline for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Show the business history as an ordered list drawn as a vertical timeline with a line and dots, using only pseudo-elements.

Learning goals

- Use <ol> and <time> for dated events
- Draw a line and markers with ::before
- Combine relative and absolute positioning

Elements and CSS used

HTML elements	CSS features
ol, li, time, p	position: relative, position: absolute, ::before, border-radius: 50%, box-shadow ring

Build guide

1. Write an <ol class="timeline"> with a <time> and <p> per event.
2. Remove bullets and add left padding for the line.
3. Draw the vertical line with .timeline::before.
4. Draw a dot per item with li::before positioned to the left.
5. Style the year.
6. Check the datetime attributes are valid.

Project 406: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - History</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Our history</h1>
    <ol class="timeline">
      <li><time datetime="2018">2018</time><p>Nour El Din opens Lotus
Language School in Alexandria.</p></li>
      <li><time datetime="2020">2020</time><p>Online ordering
launched.</p></li>
      <li><time datetime="2023">2023</time><p>Second location and new
courses.</p></li>
      <li><time datetime="2026">2026</time><p>This website goes live.
</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 406: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.timeline { list-style: none; padding: 0 0 0 2rem; margin: 0;
position: relative; }
.timeline::before { content: ""; position: absolute; left: .55rem;
top: .3rem; bottom: .3rem; width: 3px; background: var(--line); }
.timeline li { position: relative; padding-bottom: 1.5rem; }
.timeline li::before { content: ""; position: absolute; left: -1.
85rem; top: .35rem; width: 1rem; height: 1rem; border-radius: 50%;
background: var(--brand); border: 3px solid #fff; box-shadow: 0 0 0
2px var(--brand); }
time { font-weight: 700; color: var(--brand); }
.timeline p { margin: .2rem 0 0; }
```

Project 406 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - History</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Our history	The main heading; only one per page.
<ol class="timeline">	Ordered (numbered) list; the order matters.
<time datetime="2018">2018</time><p>Nour El Din opens Lotus Lan...	A paragraph of text.
<time datetime="2020">2020</time><p>Online ordering launched.</...	One list item.
<time datetime="2023">2023</time><p>Second location and new cou...	A date or time; datetime holds the machine-readable value.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: var(--line);	Background colour or image.

Declaration	What it does
border-radius: 50%;	Turns a square into a circle.
border: 3px solid #fff;	Changes the visual order of a flex item without changing the source.
box-shadow: 0 0 0 2px var(--brand);	Soft shadow that lifts the element from the page.
font-weight: 700;	Thickness of the text.

Check your work

- Events in chronological order
- Line runs from first dot to last
- Dots centred on the line
- Works when text wraps

Exercises

1. Alternate items left and right on wide screens.
2. Animate dots appearing with animation-timeline: view().
3. Add images to some events.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 407: Vertical timeline for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 2 | Files: index.html, styles.css

Brief

Show the business history as an ordered list drawn as a vertical timeline with a line and dots, using only pseudo-elements.

Learning goals

- Use <ol> and <time> for dated events
- Draw a line and markers with ::before
- Combine relative and absolute positioning

Elements and CSS used

HTML elements	CSS features
ol, li, time, p	position: relative, position: absolute, ::before, border-radius: 50%, box-shadow ring

Build guide

1. Write an <ol class="timeline"> with a <time> and <p> per event.
2. Remove bullets and add left padding for the line.
3. Draw the vertical line with .timeline::before.
4. Draw a dot per item with li::before positioned to the left.
5. Style the year.
6. Check the datetime attributes are valid.

Project 407: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - History</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Our history</h1>
    <ol class="timeline">
      <li><time datetime="2018">2018</time><p>Karim Said opens Green
Leaf Cafe in Zamalek.</p></li>
      <li><time datetime="2020">2020</time><p>Online ordering
launched.</p></li>
      <li><time datetime="2023">2023</time><p>Second location and new
drinks.</p></li>
      <li><time datetime="2026">2026</time><p>This website goes live.
</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 407: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.timeline { list-style: none; padding: 0 0 0 2rem; margin: 0;
position: relative; }
.timeline::before { content: ""; position: absolute; left: .55rem;
top: .3rem; bottom: .3rem; width: 3px; background: var(--line); }
.timeline li { position: relative; padding-bottom: 1.5rem; }
.timeline li::before { content: ""; position: absolute; left: -1.
85rem; top: .35rem; width: 1rem; height: 1rem; border-radius: 50%;
background: var(--brand); border: 3px solid #fff; box-shadow: 0 0 0
2px var(--brand); }
time { font-weight: 700; color: var(--brand); }
.timeline p { margin: .2rem 0 0; }
```

Project 407 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - History</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Our history	The main heading; only one per page.
<ol class="timeline">	Ordered (numbered) list; the order matters.
<time datetime="2018">2018</time><p>Karim Said opens Green Leaf...	A paragraph of text.
<time datetime="2020">2020</time><p>Online ordering launched.<//...	One list item.
<time datetime="2023">2023</time><p>Second location and new dri...	A date or time; datetime holds the machine-readable value.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: var(--line);	Background colour or image.

Declaration	What it does
border-radius: 50%;	Turns a square into a circle.
border: 3px solid #fff;	Changes the visual order of a flex item without changing the source.
box-shadow: 0 0 0 2px var(--brand);	Soft shadow that lifts the element from the page.
font-weight: 700;	Thickness of the text.

Check your work

- Events in chronological order
- Line runs from first dot to last
- Dots centred on the line
- Works when text wraps

Exercises

1. Alternate items left and right on wide screens.
2. Animate dots appearing with animation-timeline: view().
3. Add images to some events.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 408: Vertical timeline for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 2 | Files: index.html, styles.css

Brief

Show the business history as an ordered list drawn as a vertical timeline with a line and dots, using only pseudo-elements.

Learning goals

- Use <ol> and <time> for dated events
- Draw a line and markers with ::before
- Combine relative and absolute positioning

Elements and CSS used

HTML elements	CSS features
ol, li, time, p	position: relative, position: absolute, ::before, border-radius: 50%, box-shadow ring

Build guide

1. Write an <ol class="timeline"> with a <time> and <p> per event.
2. Remove bullets and add left padding for the line.
3. Draw the vertical line with .timeline::before.
4. Draw a dot per item with li::before positioned to the left.
5. Style the year.
6. Check the datetime attributes are valid.

Project 408: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - History</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Our history</h1>
    <ol class="timeline">
      <li><time datetime="2018">2018</time><p>Yara Hamdy opens Sinai
Trekking Club in Saint Catherine.</p></li>
      <li><time datetime="2020">2020</time><p>Online ordering
launched.</p></li>
      <li><time datetime="2023">2023</time><p>Second location and new
hikes.</p></li>
      <li><time datetime="2026">2026</time><p>This website goes live.
</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 408: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.timeline { list-style: none; padding: 0 0 0 2rem; margin: 0;
position: relative; }
.timeline::before { content: ""; position: absolute; left: .55rem;
top: .3rem; bottom: .3rem; width: 3px; background: var(--line); }
.timeline li { position: relative; padding-bottom: 1.5rem; }
.timeline li::before { content: ""; position: absolute; left: -1.
85rem; top: .35rem; width: 1rem; height: 1rem; border-radius: 50%;
background: var(--brand); border: 3px solid #fff; box-shadow: 0 0 0
2px var(--brand); }
time { font-weight: 700; color: var(--brand); }
.timeline p { margin: .2rem 0 0; }
```

Project 408 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - History</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Our history	The main heading; only one per page.
<ol class="timeline">	Ordered (numbered) list; the order matters.
<time datetime="2018"> 2018</time><p>Yara Hamdy opens Sinai Trek...	A paragraph of text.
<time datetime="2020"> 2020</time><p>Online ordering launched.<//...	One list item.
<time datetime="2023"> 2023</time><p>Second location and new hik...	A date or time; datetime holds the machine-readable value.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: var(--line);	Background colour or image.

Declaration	What it does
border-radius: 50%;	Turns a square into a circle.
border: 3px solid #fff;	Changes the visual order of a flex item without changing the source.
box-shadow: 0 0 0 2px var(--brand);	Soft shadow that lifts the element from the page.
font-weight: 700;	Thickness of the text.

Check your work

- Events in chronological order
- Line runs from first dot to last
- Dots centred on the line
- Works when text wraps

Exercises

1. Alternate items left and right on wide screens.
2. Animate dots appearing with animation-timeline: view().
3. Add images to some events.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb

Field	Value
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 409: Vertical timeline for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 2 | Files: index.html, styles.css

Brief

Show the business history as an ordered list drawn as a vertical timeline with a line and dots, using only pseudo-elements.

Learning goals

- Use <ol> and <time> for dated events
- Draw a line and markers with ::before
- Combine relative and absolute positioning

Elements and CSS used

HTML elements	CSS features
ol, li, time, p	position: relative, position: absolute, ::before, border-radius: 50%, box-shadow ring

Build guide

1. Write an <ol class="timeline"> with a <time> and <p> per event.
2. Remove bullets and add left padding for the line.
3. Draw the vertical line with .timeline::before.
4. Draw a dot per item with li::before positioned to the left.
5. Style the year.
6. Check the datetime attributes are valid.

Project 409: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - History</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Our history</h1>
    <ol class="timeline">
      <li><time datetime="2018">2018</time><p>Adham Nabil opens
Horizon Photography in Maadi.</p></li>
      <li><time datetime="2020">2020</time><p>Online ordering
launched.</p></li>
      <li><time datetime="2023">2023</time><p>Second location and new
sessions.</p></li>
      <li><time datetime="2026">2026</time><p>This website goes live.
</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 409: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.timeline { list-style: none; padding: 0 0 0 2rem; margin: 0;
position: relative; }
.timeline::before { content: ""; position: absolute; left: .55rem;
top: .3rem; bottom: .3rem; width: 3px; background: var(--line); }
.timeline li { position: relative; padding-bottom: 1.5rem; }
.timeline li::before { content: ""; position: absolute; left: -1.
85rem; top: .35rem; width: 1rem; height: 1rem; border-radius: 50%;
background: var(--brand); border: 3px solid #fff; box-shadow: 0 0 0
2px var(--brand); }
time { font-weight: 700; color: var(--brand); }
.timeline p { margin: .2rem 0 0; }
```

Project 409 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - History</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Our history	The main heading; only one per page.
<ol class="timeline">	Ordered (numbered) list; the order matters.
<time datetime="2018">2018</time><p>Adham Nabil opens Horizon P...	A paragraph of text.
<time datetime="2020">2020</time><p>Online ordering launched.<//...	One list item.
<time datetime="2023">2023</time><p>Second location and new ses...	A date or time; datetime holds the machine-readable value.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: var(--line);	Background colour or image.

Declaration	What it does
border-radius: 50%;	Turns a square into a circle.
border: 3px solid #fff;	Changes the visual order of a flex item without changing the source.
box-shadow: 0 0 0 2px var(--brand);	Soft shadow that lifts the element from the page.
font-weight: 700;	Thickness of the text.

Check your work

- Events in chronological order
- Line runs from first dot to last
- Dots centred on the line
- Works when text wraps

Exercises

1. Alternate items left and right on wide screens.
2. Animate dots appearing with animation-timeline: view().
3. Add images to some events.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 410: Vertical timeline for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 2 | Files: index.html, styles.css

Brief

Show the business history as an ordered list drawn as a vertical timeline with a line and dots, using only pseudo-elements.

Learning goals

- Use <ol> and <time> for dated events
- Draw a line and markers with ::before
- Combine relative and absolute positioning

Elements and CSS used

HTML elements	CSS features
ol, li, time, p	position: relative, position: absolute, ::before, border-radius: 50%, box-shadow ring

Build guide

1. Write an <ol class="timeline"> with a <time> and <p> per event.
2. Remove bullets and add left padding for the line.
3. Draw the vertical line with .timeline::before.
4. Draw a dot per item with li::before positioned to the left.
5. Style the year.
6. Check the datetime attributes are valid.

Project 410: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - History</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Our history</h1>
    <ol class="timeline">
      <li><time datetime="2018">2018</time><p>Dina Fathy opens
Papyrus Stationery in Heliopolis.</p></li>
      <li><time datetime="2020">2020</time><p>Online ordering
launched.</p></li>
      <li><time datetime="2023">2023</time><p>Second location and new
products.</p></li>
      <li><time datetime="2026">2026</time><p>This website goes live.
</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 410: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.timeline { list-style: none; padding: 0 0 0 2rem; margin: 0;
position: relative; }
.timeline::before { content: ""; position: absolute; left: .55rem;
top: .3rem; bottom: .3rem; width: 3px; background: var(--line); }
.timeline li { position: relative; padding-bottom: 1.5rem; }
.timeline li::before { content: ""; position: absolute; left: -1.
85rem; top: .35rem; width: 1rem; height: 1rem; border-radius: 50%;
background: var(--brand); border: 3px solid #fff; box-shadow: 0 0 0
2px var(--brand); }
time { font-weight: 700; color: var(--brand); }
.timeline p { margin: .2rem 0 0; }
```

Project 410 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - History</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Our history	The main heading; only one per page.
<ol class="timeline">	Ordered (numbered) list; the order matters.
<time datetime="2018">2018</time><p>Dina Fathy opens Papyrus St...	A paragraph of text.
<time datetime="2020">2020</time><p>Online ordering launched.</...	One list item.
<time datetime="2023">2023</time><p>Second location and new pro...	A date or time; datetime holds the machine-readable value.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: var(--line);	Background colour or image.

Declaration	What it does
border-radius: 50%;	Turns a square into a circle.
border: 3px solid #fff;	Changes the visual order of a flex item without changing the source.
box-shadow: 0 0 0 2px var(--brand);	Soft shadow that lifts the element from the page.
font-weight: 700;	Thickness of the text.

Check your work

- Events in chronological order
- Line runs from first dot to last
- Dots centred on the line
- Works when text wraps

Exercises

1. Alternate items left and right on wide screens.
2. Animate dots appearing with animation-timeline: view().
3. Add images to some events.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 411: Vertical timeline for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 2 | Files: index.html, styles.css

Brief

Show the business history as an ordered list drawn as a vertical timeline with a line and dots, using only pseudo-elements.

Learning goals

- Use <ol> and <time> for dated events
- Draw a line and markers with ::before
- Combine relative and absolute positioning

Elements and CSS used

HTML elements	CSS features
ol, li, time, p	position: relative, position: absolute, ::before, border-radius: 50%, box-shadow ring

Build guide

1. Write an <ol class="timeline"> with a <time> and <p> per event.
2. Remove bullets and add left padding for the line.
3. Draw the vertical line with .timeline::before.
4. Draw a dot per item with li::before positioned to the left.
5. Style the year.
6. Check the datetime attributes are valid.

Project 411: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - History</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Our history</h1>
    <ol class="timeline">
      <li><time datetime="2018">2018</time><p>Hossam Ali opens Oasis
Plant Nursery in Sheikh Zayed.</p></li>
      <li><time datetime="2020">2020</time><p>Online ordering
launched.</p></li>
      <li><time datetime="2023">2023</time><p>Second location and new
plants.</p></li>
      <li><time datetime="2026">2026</time><p>This website goes live.
</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 411: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.timeline { list-style: none; padding: 0 0 0 2rem; margin: 0;
position: relative; }
.timeline::before { content: ""; position: absolute; left: .55rem;
top: .3rem; bottom: .3rem; width: 3px; background: var(--line); }
.timeline li { position: relative; padding-bottom: 1.5rem; }
.timeline li::before { content: ""; position: absolute; left: -1.
85rem; top: .35rem; width: 1rem; height: 1rem; border-radius: 50%;
background: var(--brand); border: 3px solid #fff; box-shadow: 0 0 0
2px var(--brand); }
time { font-weight: 700; color: var(--brand); }
.timeline p { margin: .2rem 0 0; }
```

Project 411 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - History</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Our history	The main heading; only one per page.
<ol class="timeline">	Ordered (numbered) list; the order matters.
<time datetime="2018">2018</time><p>Hossam Ali opens Oasis Plan...	A paragraph of text.
<time datetime="2020">2020</time><p>Online ordering launched.</...	One list item.
<time datetime="2023">2023</time><p>Second location and new pla...	A date or time; datetime holds the machine-readable value.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: var(--line);	Background colour or image.

Declaration	What it does
border-radius: 50%;	Turns a square into a circle.
border: 3px solid #fff;	Changes the visual order of a flex item without changing the source.
box-shadow: 0 0 0 2px var(--brand);	Soft shadow that lifts the element from the page.
font-weight: 700;	Thickness of the text.

Check your work

- Events in chronological order
- Line runs from first dot to last
- Dots centred on the line
- Works when text wraps

Exercises

1. Alternate items left and right on wide screens.
2. Animate dots appearing with animation-timeline: view().
3. Add images to some events.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 412: Vertical timeline for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 2 | Files: index.html, styles.css

Brief

Show the business history as an ordered list drawn as a vertical timeline with a line and dots, using only pseudo-elements.

Learning goals

- Use <ol> and <time> for dated events
- Draw a line and markers with ::before
- Combine relative and absolute positioning

Elements and CSS used

HTML elements	CSS features
ol, li, time, p	position: relative, position: absolute, ::before, border-radius: 50%, box-shadow ring

Build guide

1. Write an <ol class="timeline"> with a <time> and <p> per event.
2. Remove bullets and add left padding for the line.
3. Draw the vertical line with .timeline::before.
4. Draw a dot per item with li::before positioned to the left.
5. Style the year.
6. Check the datetime attributes are valid.

Project 412: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - History</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Our history</h1>
    <ol class="timeline">
      <li><time datetime="2018">2018</time><p>Tarek Lotfy opens Cedar
Furniture in Damietta.</p></li>
      <li><time datetime="2020">2020</time><p>Online ordering
launched.</p></li>
      <li><time datetime="2023">2023</time><p>Second location and new
pieces.</p></li>
      <li><time datetime="2026">2026</time><p>This website goes live.
</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 412: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.timeline { list-style: none; padding: 0 0 0 2rem; margin: 0;
position: relative; }
.timeline::before { content: ""; position: absolute; left: .55rem;
top: .3rem; bottom: .3rem; width: 3px; background: var(--line); }
.timeline li { position: relative; padding-bottom: 1.5rem; }
.timeline li::before { content: ""; position: absolute; left: -1.
85rem; top: .35rem; width: 1rem; height: 1rem; border-radius: 50%;
background: var(--brand); border: 3px solid #fff; box-shadow: 0 0 0
2px var(--brand); }
time { font-weight: 700; color: var(--brand); }
.timeline p { margin: .2rem 0 0; }
```

Project 412 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - History</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Our history	The main heading; only one per page.
<ol class="timeline">	Ordered (numbered) list; the order matters.
<time datetime="2018">2018</time><p>Tarek Lotfy opens Cedar Fur...	A paragraph of text.
<time datetime="2020">2020</time><p>Online ordering launched.<//...	One list item.
<time datetime="2023">2023</time><p>Second location and new pie...	A date or time; datetime holds the machine-readable value.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: var(--line);	Background colour or image.

Declaration	What it does
border-radius: 50%;	Turns a square into a circle.
border: 3px solid #fff;	Changes the visual order of a flex item without changing the source.
box-shadow: 0 0 0 2px var(--brand);	Soft shadow that lifts the element from the page.
font-weight: 700;	Thickness of the text.

Check your work

- Events in chronological order
- Line runs from first dot to last
- Dots centred on the line
- Works when text wraps

Exercises

1. Alternate items left and right on wide screens.
2. Animate dots appearing with animation-timeline: view().
3. Add images to some events.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 413: Vertical timeline for Byte Repair

Theme: Byte Repair (Nasr City) | Level 2 | Files: index.html, styles.css

Brief

Show the business history as an ordered list drawn as a vertical timeline with a line and dots, using only pseudo-elements.

Learning goals

- Use <ol> and <time> for dated events
- Draw a line and markers with ::before
- Combine relative and absolute positioning

Elements and CSS used

HTML elements	CSS features
ol, li, time, p	position: relative, position: absolute, ::before, border-radius: 50%, box-shadow ring

Build guide

1. Write an <ol class="timeline"> with a <time> and <p> per event.
2. Remove bullets and add left padding for the line.
3. Draw the vertical line with .timeline::before.
4. Draw a dot per item with li::before positioned to the left.
5. Style the year.
6. Check the datetime attributes are valid.

Project 413: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - History</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Our history</h1>
    <ol class="timeline">
      <li><time datetime="2018">2018</time><p>Mostafa Gamal opens
Byte Repair in Nasr City.</p></li>
      <li><time datetime="2020">2020</time><p>Online ordering
launched.</p></li>
      <li><time datetime="2023">2023</time><p>Second location and new
repairs.</p></li>
      <li><time datetime="2026">2026</time><p>This website goes live.
</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 413: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.timeline { list-style: none; padding: 0 0 0 2rem; margin: 0;
position: relative; }
.timeline::before { content: ""; position: absolute; left: .55rem;
top: .3rem; bottom: .3rem; width: 3px; background: var(--line); }
.timeline li { position: relative; padding-bottom: 1.5rem; }
.timeline li::before { content: ""; position: absolute; left: -1.
85rem; top: .35rem; width: 1rem; height: 1rem; border-radius: 50%;
background: var(--brand); border: 3px solid #fff; box-shadow: 0 0 0
2px var(--brand); }
time { font-weight: 700; color: var(--brand); }
.timeline p { margin: .2rem 0 0; }
```

Project 413 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - History</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Our history	The main heading; only one per page.
<ol class="timeline">	Ordered (numbered) list; the order matters.
<time datetime="2018">2018</time><p>Mostafa Gamal opens Byte Re...	A paragraph of text.
<time datetime="2020">2020</time><p>Online ordering launched.<//...	One list item.
<time datetime="2023">2023</time><p>Second location and new rep...	A date or time; datetime holds the machine-readable value.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: var(--line);	Background colour or image.

Declaration	What it does
border-radius: 50%;	Turns a square into a circle.
border: 3px solid #fff;	Changes the visual order of a flex item without changing the source.
box-shadow: 0 0 0 2px var(--brand);	Soft shadow that lifts the element from the page.
font-weight: 700;	Thickness of the text.

Check your work

- Events in chronological order
- Line runs from first dot to last
- Dots centred on the line
- Works when text wraps

Exercises

1. Alternate items left and right on wide screens.
2. Animate dots appearing with animation-timeline: view().
3. Add images to some events.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff

Field	Value
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 414: Vertical timeline for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 2 | Files: index.html, styles.css

Brief

Show the business history as an ordered list drawn as a vertical timeline with a line and dots, using only pseudo-elements.

Learning goals

- Use <ol> and <time> for dated events
- Draw a line and markers with ::before
- Combine relative and absolute positioning

Elements and CSS used

HTML elements	CSS features
ol, li, time, p	position: relative, position: absolute, ::before, border-radius: 50%, box-shadow ring

Build guide

1. Write an <ol class="timeline"> with a <time> and <p> per event.
2. Remove bullets and add left padding for the line.
3. Draw the vertical line with .timeline::before.
4. Draw a dot per item with li::before positioned to the left.
5. Style the year.
6. Check the datetime attributes are valid.

Project 414: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - History</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Our history</h1>
    <ol class="timeline">
      <li><time datetime="2018">2018</time><p>Rana Ibrahim opens
Sahara Pet Care in New Cairo.</p></li>
      <li><time datetime="2020">2020</time><p>Online ordering
launched.</p></li>
      <li><time datetime="2023">2023</time><p>Second location and new
services.</p></li>
      <li><time datetime="2026">2026</time><p>This website goes live.
</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 414: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.timeline { list-style: none; padding: 0 0 0 2rem; margin: 0;
position: relative; }
.timeline::before { content: ""; position: absolute; left: .55rem;
top: .3rem; bottom: .3rem; width: 3px; background: var(--line); }
.timeline li { position: relative; padding-bottom: 1.5rem; }
.timeline li::before { content: ""; position: absolute; left: -1.
85rem; top: .35rem; width: 1rem; height: 1rem; border-radius: 50%;
background: var(--brand); border: 3px solid #fff; box-shadow: 0 0 0
2px var(--brand); }
time { font-weight: 700; color: var(--brand); }
.timeline p { margin: .2rem 0 0; }
```

Project 414 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - History</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Our history	The main heading; only one per page.
<ol class="timeline">	Ordered (numbered) list; the order matters.
<time datetime="2018">2018</time><p>Rana Ibrahim opens Sahara P...	A paragraph of text.
<time datetime="2020">2020</time><p>Online ordering launched.<//...	One list item.
<time datetime="2023">2023</time><p>Second location and new ser...	A date or time; datetime holds the machine-readable value.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: var(--line);	Background colour or image.

Declaration	What it does
border-radius: 50%;	Turns a square into a circle.
border: 3px solid #fff;	Changes the visual order of a flex item without changing the source.
box-shadow: 0 0 0 2px var(--brand);	Soft shadow that lifts the element from the page.
font-weight: 700;	Thickness of the text.

Check your work

- Events in chronological order
- Line runs from first dot to last
- Dots centred on the line
- Works when text wraps

Exercises

1. Alternate items left and right on wide screens.
2. Animate dots appearing with animation-timeline: view().
3. Add images to some events.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 415: Vertical timeline for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Show the business history as an ordered list drawn as a vertical timeline with a line and dots, using only pseudo-elements.

Learning goals

- Use <ol> and <time> for dated events
- Draw a line and markers with ::before
- Combine relative and absolute positioning

Elements and CSS used

HTML elements	CSS features
ol, li, time, p	position: relative, position: absolute, ::before, border-radius: 50%, box-shadow ring

Build guide

1. Write an <ol class="timeline"> with a <time> and <p> per event.
2. Remove bullets and add left padding for the line.
3. Draw the vertical line with .timeline::before.
4. Draw a dot per item with li::before positioned to the left.
5. Style the year.
6. Check the datetime attributes are valid.

Project 415: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - History</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Our history</h1>
    <ol class="timeline">
      <li><time datetime="2018">2018</time><p>Amr Selim opens
Alexandria Sailing School in Alexandria.</p></li>
      <li><time datetime="2020">2020</time><p>Online ordering
launched.</p></li>
      <li><time datetime="2023">2023</time><p>Second location and new
lessons.</p></li>
      <li><time datetime="2026">2026</time><p>This website goes live.
</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 415: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.timeline { list-style: none; padding: 0 0 0 2rem; margin: 0;
position: relative; }
.timeline::before { content: ""; position: absolute; left: .55rem;
top: .3rem; bottom: .3rem; width: 3px; background: var(--line); }
.timeline li { position: relative; padding-bottom: 1.5rem; }
.timeline li::before { content: ""; position: absolute; left: -1.
85rem; top: .35rem; width: 1rem; height: 1rem; border-radius: 50%;
background: var(--brand); border: 3px solid #fff; box-shadow: 0 0 0
2px var(--brand); }
time { font-weight: 700; color: var(--brand); }
.timeline p { margin: .2rem 0 0; }
```

Project 415 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - History</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Our history	The main heading; only one per page.
<ol class="timeline">	Ordered (numbered) list; the order matters.
<time datetime="2018">2018</time><p>Amr Selim opens Alexandria ...	A paragraph of text.
<time datetime="2020">2020</time><p>Online ordering launched.<//...	One list item.
<time datetime="2023">2023</time><p>Second location and new les...	A date or time; datetime holds the machine-readable value.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: var(--line);	Background colour or image.

Declaration	What it does
border-radius: 50%;	Turns a square into a circle.
border: 3px solid #fff;	Changes the visual order of a flex item without changing the source.
box-shadow: 0 0 0 2px var(--brand);	Soft shadow that lifts the element from the page.
font-weight: 700;	Thickness of the text.

Check your work

- Events in chronological order
- Line runs from first dot to last
- Dots centred on the line
- Works when text wraps

Exercises

1. Alternate items left and right on wide screens.
2. Animate dots appearing with animation-timeline: view().
3. Add images to some events.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 416: Vertical timeline for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Show the business history as an ordered list drawn as a vertical timeline with a line and dots, using only pseudo-elements.

Learning goals

- Use <ol> and <time> for dated events
- Draw a line and markers with ::before
- Combine relative and absolute positioning

Elements and CSS used

HTML elements	CSS features
ol, li, time, p	position: relative, position: absolute, ::before, border-radius: 50%, box-shadow ring

Build guide

1. Write an <ol class="timeline"> with a <time> and <p> per event.
2. Remove bullets and add left padding for the line.
3. Draw the vertical line with .timeline::before.
4. Draw a dot per item with li::before positioned to the left.
5. Style the year.

6. Check the datetime attributes are valid.

Project 416: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - History</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Our history</h1>
    <ol class="timeline">
      <li><time datetime="2018">2018</time><p>Habiba Saleh opens
Habiba Handmade Jewellery in Aswan.</p></li>
      <li><time datetime="2020">2020</time><p>Online ordering
launched.</p></li>
      <li><time datetime="2023">2023</time><p>Second location and new
items.</p></li>
      <li><time datetime="2026">2026</time><p>This website goes live.
</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 416: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.timeline { list-style: none; padding: 0 0 0 2rem; margin: 0;
position: relative; }
.timeline::before { content: ""; position: absolute; left: .55rem;
top: .3rem; bottom: .3rem; width: 3px; background: var(--line); }
.timeline li { position: relative; padding-bottom: 1.5rem; }
.timeline li::before { content: ""; position: absolute; left: -1.
85rem; top: .35rem; width: 1rem; height: 1rem; border-radius: 50%;
background: var(--brand); border: 3px solid #fff; box-shadow: 0 0 0
2px var(--brand); }
time { font-weight: 700; color: var(--brand); }
.timeline p { margin: .2rem 0 0; }
```

Project 416 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - History</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Our history	The main heading; only one per page.
<ol class="timeline">	Ordered (numbered) list; the order matters.
<time datetime="2018">2018</time><p>Habiba Saleh opens Habiba H...	A paragraph of text.
<time datetime="2020">2020</time><p>Online ordering launched.<//...	One list item.
<time datetime="2023">2023</time><p>Second location and new ite...	A date or time; datetime holds the machine-readable value.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: var(--line);	Background colour or image.

Declaration	What it does
border-radius: 50%;	Turns a square into a circle.
border: 3px solid #fff;	Changes the visual order of a flex item without changing the source.
box-shadow: 0 0 0 2px var(--brand);	Soft shadow that lifts the element from the page.
font-weight: 700;	Thickness of the text.

Check your work

- Events in chronological order
- Line runs from first dot to last
- Dots centred on the line
- Works when text wraps

Exercises

1. Alternate items left and right on wide screens.
2. Animate dots appearing with animation-timeline: view().
3. Add images to some events.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 417: Vertical timeline for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 2 | Files: index.html, styles.css

Brief

Show the business history as an ordered list drawn as a vertical timeline with a line and dots, using only pseudo-elements.

Learning goals

- Use <ol> and <time> for dated events
- Draw a line and markers with ::before
- Combine relative and absolute positioning

Elements and CSS used

HTML elements	CSS features
ol, li, time, p	position: relative, position: absolute, ::before, border-radius: 50%, box-shadow ring

Build guide

1. Write an <ol class="timeline"> with a <time> and <p> per event.
2. Remove bullets and add left padding for the line.
3. Draw the vertical line with .timeline::before.
4. Draw a dot per item with li::before positioned to the left.
5. Style the year.
6. Check the datetime attributes are valid.

Project 417: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - History</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Our history</h1>
    <ol class="timeline">
      <li><time datetime="2018">2018</time><p>Ahmed Mahmoud opens
Fayoum Pottery Studio in Tunis Village.</p></li>
      <li><time datetime="2020">2020</time><p>Online ordering
launched.</p></li>
      <li><time datetime="2023">2023</time><p>Second location and new
workshops.</p></li>
      <li><time datetime="2026">2026</time><p>This website goes live.
</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 417: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.timeline { list-style: none; padding: 0 0 0 2rem; margin: 0;
position: relative; }
.timeline::before { content: ""; position: absolute; left: .55rem;
top: .3rem; bottom: .3rem; width: 3px; background: var(--line); }
.timeline li { position: relative; padding-bottom: 1.5rem; }
.timeline li::before { content: ""; position: absolute; left: -1.
85rem; top: .35rem; width: 1rem; height: 1rem; border-radius: 50%;
background: var(--brand); border: 3px solid #fff; box-shadow: 0 0 0
2px var(--brand); }
time { font-weight: 700; color: var(--brand); }
.timeline p { margin: .2rem 0 0; }
```

Project 417 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - History</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Our history	The main heading; only one per page.
<ol class="timeline">	Ordered (numbered) list; the order matters.
<time datetime="2018">2018</time><p>Ahmed Mahmoud opens Fayoum ...	A paragraph of text.
<time datetime="2020">2020</time><p>Online ordering launched.<//...	One list item.
<time datetime="2023">2023</time><p>Second location and new wor...	A date or time; datetime holds the machine-readable value.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: var(--line);	Background colour or image.

Declaration	What it does
border-radius: 50%;	Turns a square into a circle.
border: 3px solid #fff;	Changes the visual order of a flex item without changing the source.
box-shadow: 0 0 0 2px var(--brand);	Soft shadow that lifts the element from the page.
font-weight: 700;	Thickness of the text.

Check your work

- Events in chronological order
- Line runs from first dot to last
- Dots centred on the line
- Works when text wraps

Exercises

1. Alternate items left and right on wide screens.
2. Animate dots appearing with animation-timeline: view().
3. Add images to some events.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 418: Vertical timeline for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 2 | Files: index.html, styles.css

Brief

Show the business history as an ordered list drawn as a vertical timeline with a line and dots, using only pseudo-elements.

Learning goals

- Use <ol> and <time> for dated events
- Draw a line and markers with ::before
- Combine relative and absolute positioning

Elements and CSS used

HTML elements	CSS features
ol, li, time, p	position: relative, position: absolute, ::before, border-radius: 50%, box-shadow ring

Build guide

1. Write an <ol class="timeline"> with a <time> and <p> per event.
2. Remove bullets and add left padding for the line.
3. Draw the vertical line with .timeline::before.
4. Draw a dot per item with li::before positioned to the left.
5. Style the year.
6. Check the datetime attributes are valid.

Project 418: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - History</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Our history</h1>
    <ol class="timeline">
      <li><time datetime="2018">2018</time><p>Mariam Adel opens
Cleopatra Beauty Salon in Dokki.</p></li>
      <li><time datetime="2020">2020</time><p>Online ordering
launched.</p></li>
      <li><time datetime="2023">2023</time><p>Second location and new
treatments.</p></li>
      <li><time datetime="2026">2026</time><p>This website goes live.
</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 418: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.timeline { list-style: none; padding: 0 0 0 2rem; margin: 0;
position: relative; }
.timeline::before { content: ""; position: absolute; left: .55rem;
top: .3rem; bottom: .3rem; width: 3px; background: var(--line); }
.timeline li { position: relative; padding-bottom: 1.5rem; }
.timeline li::before { content: ""; position: absolute; left: -1.
85rem; top: .35rem; width: 1rem; height: 1rem; border-radius: 50%;
background: var(--brand); border: 3px solid #fff; box-shadow: 0 0 0
2px var(--brand); }
time { font-weight: 700; color: var(--brand); }
.timeline p { margin: .2rem 0 0; }
```

Project 418 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - History</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Our history	The main heading; only one per page.
<ol class="timeline">	Ordered (numbered) list; the order matters.
<time datetime="2018"> 2018</time><p>Mariam Adel opens Cleopatra...	A paragraph of text.
<time datetime="2020"> 2020</time><p>Online ordering launched.<//...	One list item.
<time datetime="2023"> 2023</time><p>Second location and new tre...	A date or time; datetime holds the machine-readable value.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: var(--line);	Background colour or image.

Declaration	What it does
border-radius: 50%;	Turns a square into a circle.
border: 3px solid #fff;	Changes the visual order of a flex item without changing the source.
box-shadow: 0 0 0 2px var(--brand);	Soft shadow that lifts the element from the page.
font-weight: 700;	Thickness of the text.

Check your work

- Events in chronological order
- Line runs from first dot to last
- Dots centred on the line
- Works when text wraps

Exercises

1. Alternate items left and right on wide screens.
2. Animate dots appearing with animation-timeline: view().
3. Add images to some events.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 419: Vertical timeline for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 2 | Files: index.html, styles.css

Brief

Show the business history as an ordered list drawn as a vertical timeline with a line and dots, using only pseudo-elements.

Learning goals

- Use <ol> and <time> for dated events
- Draw a line and markers with ::before
- Combine relative and absolute positioning

Elements and CSS used

HTML elements	CSS features
ol, li, time, p	position: relative, position: absolute, ::before, border-radius: 50%, box-shadow ring

Build guide

1. Write an <ol class="timeline"> with a <time> and <p> per event.
2. Remove bullets and add left padding for the line.
3. Draw the vertical line with .timeline::before.
4. Draw a dot per item with li::before positioned to the left.
5. Style the year.
6. Check the datetime attributes are valid.

Project 419: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - History</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Our history</h1>
    <ol class="timeline">
      <li><time datetime="2018">2018</time><p>Khaled Nasser opens
Suez Auto Service in Suez.</p></li>
      <li><time datetime="2020">2020</time><p>Online ordering
launched.</p></li>
      <li><time datetime="2023">2023</time><p>Second location and new
services.</p></li>
      <li><time datetime="2026">2026</time><p>This website goes live.
</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 419: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.timeline { list-style: none; padding: 0 0 0 2rem; margin: 0;
position: relative; }
.timeline::before { content: ""; position: absolute; left: .55rem;
top: .3rem; bottom: .3rem; width: 3px; background: var(--line); }
.timeline li { position: relative; padding-bottom: 1.5rem; }
.timeline li::before { content: ""; position: absolute; left: -1.
85rem; top: .35rem; width: 1rem; height: 1rem; border-radius: 50%;
background: var(--brand); border: 3px solid #fff; box-shadow: 0 0 0
2px var(--brand); }
time { font-weight: 700; color: var(--brand); }
.timeline p { margin: .2rem 0 0; }
```

Project 419 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - History</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Our history	The main heading; only one per page.
<ol class="timeline">	Ordered (numbered) list; the order matters.
<time datetime="2018"> 2018</time><p>Khaled Nasser opens Suez Au...	A paragraph of text.
<time datetime="2020"> 2020</time><p>Online ordering launched.<//...	One list item.
<time datetime="2023"> 2023</time><p>Second location and new ser...	A date or time; datetime holds the machine-readable value.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: var(--line);	Background colour or image.

Declaration	What it does
border-radius: 50%;	Turns a square into a circle.
border: 3px solid #fff;	Changes the visual order of a flex item without changing the source.
box-shadow: 0 0 0 2px var(--brand);	Soft shadow that lifts the element from the page.
font-weight: 700;	Thickness of the text.

Check your work

- Events in chronological order
- Line runs from first dot to last
- Dots centred on the line
- Works when text wraps

Exercises

1. Alternate items left and right on wide screens.
2. Animate dots appearing with animation-timeline: view().
3. Add images to some events.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb

Field	Value
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 420: Vertical timeline for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 2 | Files: index.html, styles.css

Brief

Show the business history as an ordered list drawn as a vertical timeline with a line and dots, using only pseudo-elements.

Learning goals

- Use <ol> and <time> for dated events
- Draw a line and markers with ::before
- Combine relative and absolute positioning

Elements and CSS used

HTML elements	CSS features
ol, li, time, p	position: relative, position: absolute, ::before, border-radius: 50%, box-shadow ring

Build guide

1. Write an <ol class="timeline"> with a <time> and <p> per event.
2. Remove bullets and add left padding for the line.
3. Draw the vertical line with .timeline::before.
4. Draw a dot per item with li::before positioned to the left.
5. Style the year.
6. Check the datetime attributes are valid.

Project 420: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - History</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Our history</h1>
    <ol class="timeline">
      <li><time datetime="2018">2018</time><p>Salma Ragab opens Luxor
Music Academy in Luxor.</p></li>
      <li><time datetime="2020">2020</time><p>Online ordering
launched.</p></li>
      <li><time datetime="2023">2023</time><p>Second location and new
courses.</p></li>
      <li><time datetime="2026">2026</time><p>This website goes live.
</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 420: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.timeline { list-style: none; padding: 0 0 0 2rem; margin: 0;
position: relative; }
.timeline::before { content: ""; position: absolute; left: .55rem;
top: .3rem; bottom: .3rem; width: 3px; background: var(--line); }
.timeline li { position: relative; padding-bottom: 1.5rem; }
.timeline li::before { content: ""; position: absolute; left: -1.
85rem; top: .35rem; width: 1rem; height: 1rem; border-radius: 50%;
background: var(--brand); border: 3px solid #fff; box-shadow: 0 0 0
2px var(--brand); }
time { font-weight: 700; color: var(--brand); }
.timeline p { margin: .2rem 0 0; }
```

Project 420 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - History</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Our history	The main heading; only one per page.
<ol class="timeline">	Ordered (numbered) list; the order matters.
<time datetime="2018"> 2018</time><p>Salma Ragab opens Luxor Mus...	A paragraph of text.
<time datetime="2020"> 2020</time><p>Online ordering launched.<//...	One list item.
<time datetime="2023"> 2023</time><p>Second location and new cou...	A date or time; datetime holds the machine-readable value.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: var(--line);	Background colour or image.

Declaration	What it does
border-radius: 50%;	Turns a square into a circle.
border: 3px solid #fff;	Changes the visual order of a flex item without changing the source.
box-shadow: 0 0 0 2px var(--brand);	Soft shadow that lifts the element from the page.
font-weight: 700;	Thickness of the text.

Check your work

- Events in chronological order
- Line runs from first dot to last
- Dots centred on the line
- Works when text wraps

Exercises

1. Alternate items left and right on wide screens.
2. Animate dots appearing with animation-timeline: view().
3. Add images to some events.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff

Field	Value
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 421: Vertical timeline for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 2 | Files: index.html, styles.css

Brief

Show the business history as an ordered list drawn as a vertical timeline with a line and dots, using only pseudo-elements.

Learning goals

- Use <ol> and <time> for dated events
- Draw a line and markers with ::before
- Combine relative and absolute positioning

Elements and CSS used

HTML elements	CSS features
ol, li, time, p	position: relative, position: absolute, ::before, border-radius: 50%, box-shadow ring

Build guide

1. Write an <ol class="timeline"> with a <time> and <p> per event.
2. Remove bullets and add left padding for the line.
3. Draw the vertical line with .timeline::before.
4. Draw a dot per item with li::before positioned to the left.
5. Style the year.
6. Check the datetime attributes are valid.

Project 421: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - History</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Our history</h1>
    <ol class="timeline">
      <li><time datetime="2018">2018</time><p>Sherif Wahba opens Port
Said Seafood in Port Said.</p></li>
      <li><time datetime="2020">2020</time><p>Online ordering
launched.</p></li>
      <li><time datetime="2023">2023</time><p>Second location and new
dishes.</p></li>
      <li><time datetime="2026">2026</time><p>This website goes live.
</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 421: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.timeline { list-style: none; padding: 0 0 0 2rem; margin: 0;
position: relative; }
.timeline::before { content: ""; position: absolute; left: .55rem;
top: .3rem; bottom: .3rem; width: 3px; background: var(--line); }
.timeline li { position: relative; padding-bottom: 1.5rem; }
.timeline li::before { content: ""; position: absolute; left: -1.
85rem; top: .35rem; width: 1rem; height: 1rem; border-radius: 50%;
background: var(--brand); border: 3px solid #fff; box-shadow: 0 0 0
2px var(--brand); }
time { font-weight: 700; color: var(--brand); }
.timeline p { margin: .2rem 0 0; }
```

Project 421 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - History</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Our history	The main heading; only one per page.
<ol class="timeline">	Ordered (numbered) list; the order matters.
<time datetime="2018"> 2018</time><p>Sherif Wahba opens Port Sai...	A paragraph of text.
<time datetime="2020"> 2020</time><p>Online ordering launched.<//...	One list item.
<time datetime="2023"> 2023</time><p>Second location and new dis...	A date or time; datetime holds the machine-readable value.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: var(--line);	Background colour or image.

Declaration	What it does
border-radius: 50%;	Turns a square into a circle.
border: 3px solid #fff;	Changes the visual order of a flex item without changing the source.
box-shadow: 0 0 0 2px var(--brand);	Soft shadow that lifts the element from the page.
font-weight: 700;	Thickness of the text.

Check your work

- Events in chronological order
- Line runs from first dot to last
- Dots centred on the line
- Works when text wraps

Exercises

1. Alternate items left and right on wide screens.
2. Animate dots appearing with animation-timeline: view().
3. Add images to some events.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 422: Vertical timeline for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 2 | Files: index.html, styles.css

Brief

Show the business history as an ordered list drawn as a vertical timeline with a line and dots, using only pseudo-elements.

Learning goals

- Use <ol> and <time> for dated events
- Draw a line and markers with ::before
- Combine relative and absolute positioning

Elements and CSS used

HTML elements	CSS features
ol, li, time, p	position: relative, position: absolute, ::before, border-radius: 50%, box-shadow ring

Build guide

1. Write an <ol class="timeline"> with a <time> and <p> per event.
2. Remove bullets and add left padding for the line.
3. Draw the vertical line with .timeline::before.
4. Draw a dot per item with li::before positioned to the left.
5. Style the year.
6. Check the datetime attributes are valid.

Project 422: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - History</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Our history</h1>
    <ol class="timeline">
      <li><time datetime="2018">2018</time><p>Ghada Kamel opens Delta
Kids Library in Tanta.</p></li>
      <li><time datetime="2020">2020</time><p>Online ordering
launched.</p></li>
      <li><time datetime="2023">2023</time><p>Second location and new
programmes.</p></li>
      <li><time datetime="2026">2026</time><p>This website goes live.
</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 422: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.timeline { list-style: none; padding: 0 0 0 2rem; margin: 0;
position: relative; }
.timeline::before { content: ""; position: absolute; left: .55rem;
top: .3rem; bottom: .3rem; width: 3px; background: var(--line); }
.timeline li { position: relative; padding-bottom: 1.5rem; }
.timeline li::before { content: ""; position: absolute; left: -1.
85rem; top: .35rem; width: 1rem; height: 1rem; border-radius: 50%;
background: var(--brand); border: 3px solid #fff; box-shadow: 0 0 0
2px var(--brand); }
time { font-weight: 700; color: var(--brand); }
.timeline p { margin: .2rem 0 0; }
```

Project 422 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - History</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Our history	The main heading; only one per page.
<ol class="timeline">	Ordered (numbered) list; the order matters.
<time datetime="2018"> 2018</time><p>Ghada Kamel opens Delta Kid...	A paragraph of text.
<time datetime="2020"> 2020</time><p>Online ordering launched.<//...	One list item.
<time datetime="2023"> 2023</time><p>Second location and new pro...	A date or time; datetime holds the machine-readable value.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: var(--line);	Background colour or image.

Declaration	What it does
border-radius: 50%;	Turns a square into a circle.
border: 3px solid #fff;	Changes the visual order of a flex item without changing the source.
box-shadow: 0 0 0 2px var(--brand);	Soft shadow that lifts the element from the page.
font-weight: 700;	Thickness of the text.

Check your work

- Events in chronological order
- Line runs from first dot to last
- Dots centred on the line
- Works when text wraps

Exercises

1. Alternate items left and right on wide screens.
2. Animate dots appearing with animation-timeline: view().
3. Add images to some events.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 423: Vertical timeline for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Show the business history as an ordered list drawn as a vertical timeline with a line and dots, using only pseudo-elements.

Learning goals

- Use <ol> and <time> for dated events
- Draw a line and markers with ::before
- Combine relative and absolute positioning

Elements and CSS used

HTML elements	CSS features
ol, li, time, p	position: relative, position: absolute, ::before, border-radius: 50%, box-shadow ring

Build guide

1. Write an <ol class="timeline"> with a <time> and <p> per event.
2. Remove bullets and add left padding for the line.
3. Draw the vertical line with .timeline::before.
4. Draw a dot per item with li::before positioned to the left.
5. Style the year.
6. Check the datetime attributes are valid.

Project 423: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - History</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Our history</h1>
    <ol class="timeline">
      <li><time datetime="2018">2018</time><p>Fatma Hassan opens
Nubian Guest House in Aswan.</p></li>
      <li><time datetime="2020">2020</time><p>Online ordering
launched.</p></li>
      <li><time datetime="2023">2023</time><p>Second location and new
rooms.</p></li>
      <li><time datetime="2026">2026</time><p>This website goes live.
</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 423: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.timeline { list-style: none; padding: 0 0 0 2rem; margin: 0;
position: relative; }
.timeline::before { content: ""; position: absolute; left: .55rem;
top: .3rem; bottom: .3rem; width: 3px; background: var(--line); }
.timeline li { position: relative; padding-bottom: 1.5rem; }
.timeline li::before { content: ""; position: absolute; left: -1.
85rem; top: .35rem; width: 1rem; height: 1rem; border-radius: 50%;
background: var(--brand); border: 3px solid #fff; box-shadow: 0 0 0
2px var(--brand); }
time { font-weight: 700; color: var(--brand); }
.timeline p { margin: .2rem 0 0; }
```

Project 423 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - History</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Our history	The main heading; only one per page.
<ol class="timeline">	Ordered (numbered) list; the order matters.
<time datetime="2018">2018</time><p>Fatma Hassan opens Nubian G...	A paragraph of text.
<time datetime="2020">2020</time><p>Online ordering launched.</...	One list item.
<time datetime="2023">2023</time><p>Second location and new roo...	A date or time; datetime holds the machine-readable value.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: var(--line);	Background colour or image.

Declaration	What it does
border-radius: 50%;	Turns a square into a circle.
border: 3px solid #fff;	Changes the visual order of a flex item without changing the source.
box-shadow: 0 0 0 2px var(--brand);	Soft shadow that lifts the element from the page.
font-weight: 700;	Thickness of the text.

Check your work

- Events in chronological order
- Line runs from first dot to last
- Dots centred on the line
- Works when text wraps

Exercises

1. Alternate items left and right on wide screens.
2. Animate dots appearing with animation-timeline: view().
3. Add images to some events.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 424: Vertical timeline for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 2 | Files: index.html, styles.css

Brief

Show the business history as an ordered list drawn as a vertical timeline with a line and dots, using only pseudo-elements.

Learning goals

- Use <ol> and <time> for dated events
- Draw a line and markers with ::before
- Combine relative and absolute positioning

Elements and CSS used

HTML elements	CSS features
ol, li, time, p	position: relative, position: absolute, ::before, border-radius: 50%, box-shadow ring

Build guide

1. Write an <ol class="timeline"> with a <time> and <p> per event.
2. Remove bullets and add left padding for the line.
3. Draw the vertical line with .timeline::before.
4. Draw a dot per item with li::before positioned to the left.
5. Style the year.
6. Check the datetime attributes are valid.

Project 424: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - History</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Our history</h1>
    <ol class="timeline">
      <li><time datetime="2018">2018</time><p>Bassem Adly opens
Ismailia Cycling Store in Ismailia.</p></li>
      <li><time datetime="2020">2020</time><p>Online ordering
launched.</p></li>
      <li><time datetime="2023">2023</time><p>Second location and new
bikes.</p></li>
      <li><time datetime="2026">2026</time><p>This website goes live.
</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 424: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.timeline { list-style: none; padding: 0 0 0 2rem; margin: 0;
position: relative; }
.timeline::before { content: ""; position: absolute; left: .55rem;
top: .3rem; bottom: .3rem; width: 3px; background: var(--line); }
.timeline li { position: relative; padding-bottom: 1.5rem; }
.timeline li::before { content: ""; position: absolute; left: -1.
85rem; top: .35rem; width: 1rem; height: 1rem; border-radius: 50%;
background: var(--brand); border: 3px solid #fff; box-shadow: 0 0 0
2px var(--brand); }
time { font-weight: 700; color: var(--brand); }
.timeline p { margin: .2rem 0 0; }
```

Project 424 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - History</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Our history	The main heading; only one per page.
<ol class="timeline">	Ordered (numbered) list; the order matters.
<time datetime="2018">2018</time><p>Bassem Adly opens Ismailia ...	A paragraph of text.
<time datetime="2020">2020</time><p>Online ordering launched.<//...	One list item.
<time datetime="2023">2023</time><p>Second location and new bik...	A date or time; datetime holds the machine-readable value.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: var(--line);	Background colour or image.

Declaration	What it does
border-radius: 50%;	Turns a square into a circle.
border: 3px solid #fff;	Changes the visual order of a flex item without changing the source.
box-shadow: 0 0 0 2px var(--brand);	Soft shadow that lifts the element from the page.
font-weight: 700;	Thickness of the text.

Check your work

- Events in chronological order
- Line runs from first dot to last
- Dots centred on the line
- Works when text wraps

Exercises

1. Alternate items left and right on wide screens.
2. Animate dots appearing with animation-timeline: view().
3. Add images to some events.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 425: Vertical timeline for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 2 | Files: index.html, styles.css

Brief

Show the business history as an ordered list drawn as a vertical timeline with a line and dots, using only pseudo-elements.

Learning goals

- Use <ol> and <time> for dated events
- Draw a line and markers with ::before
- Combine relative and absolute positioning

Elements and CSS used

HTML elements	CSS features
ol, li, time, p	position: relative, position: absolute, ::before, border-radius: 50%, box-shadow ring

Build guide

1. Write an <ol class="timeline"> with a <time> and <p> per event.
2. Remove bullets and add left padding for the line.
3. Draw the vertical line with .timeline::before.
4. Draw a dot per item with li::before positioned to the left.
5. Style the year.
6. Check the datetime attributes are valid.

Project 425: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - History</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Our history</h1>
    <ol class="timeline">
      <li><time datetime="2018">2018</time><p>Youssef Hany opens
Minya Coding Club in Minya.</p></li>
      <li><time datetime="2020">2020</time><p>Online ordering
launched.</p></li>
      <li><time datetime="2023">2023</time><p>Second location and new
workshops.</p></li>
      <li><time datetime="2026">2026</time><p>This website goes live.
</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 425: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.timeline { list-style: none; padding: 0 0 0 2rem; margin: 0;
position: relative; }
.timeline::before { content: ""; position: absolute; left: .55rem;
top: .3rem; bottom: .3rem; width: 3px; background: var(--line); }
.timeline li { position: relative; padding-bottom: 1.5rem; }
.timeline li::before { content: ""; position: absolute; left: -1.
85rem; top: .35rem; width: 1rem; height: 1rem; border-radius: 50%;
background: var(--brand); border: 3px solid #fff; box-shadow: 0 0 0
2px var(--brand); }
time { font-weight: 700; color: var(--brand); }
.timeline p { margin: .2rem 0 0; }
```

Project 425 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - History</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Our history	The main heading; only one per page.
<ol class="timeline">	Ordered (numbered) list; the order matters.
<time datetime="2018"> 2018</time><p>Youssef Hany opens Minya Co...	A paragraph of text.
<time datetime="2020"> 2020</time><p>Online ordering launched.<//...	One list item.
<time datetime="2023"> 2023</time><p>Second location and new wor...	A date or time; datetime holds the machine-readable value.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: var(--line);	Background colour or image.

Declaration	What it does
border-radius: 50%;	Turns a square into a circle.
border: 3px solid #fff;	Changes the visual order of a flex item without changing the source.
box-shadow: 0 0 0 2px var(--brand);	Soft shadow that lifts the element from the page.
font-weight: 700;	Thickness of the text.

Check your work

- Events in chronological order
- Line runs from first dot to last
- Dots centred on the line
- Works when text wraps

Exercises

1. Alternate items left and right on wide screens.
2. Animate dots appearing with animation-timeline: view().
3. Add images to some events.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Statistics dashboard

Level 2 | 25 projects, one per theme

Build an admin-style dashboard: four statistic cards with a coloured top border and a panel containing a recent-orders table with status badges.

Project 426: Statistics dashboard for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 2 | Files: index.html, styles.css

Brief

Build an admin-style dashboard: four statistic cards with a coloured top border and a panel containing a recent-orders table with status badges.

Learning goals

- Present numbers in cards with small uppercase labels
- Create pill-shaped status badges
- Combine grid cards and a table

Elements and CSS used

HTML elements	CSS features
article, h2, p, section, table, thead, tbody, span	border-top, text-transform, letter-spacing, border-radius: 999px, grid auto-fit

Build guide

1. Write four .stat articles inside .stats.
2. Add the panel with a small table.
3. Wrap statuses in .
4. Grid the cards.
5. Style the badges as pills with soft background colours.
6. Give the page a light grey background so white panels stand out.

Project 426: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Dashboard</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cairo Book Shop dashboard</h1>
    <div class="stats">
      <article class="stat"><h2>Visitors today</h2><p class="value">1,
284</p></article>
      <article class="stat"><h2>Books sold</h2><p class="value">57</
p></article>
      <article class="stat"><h2>Revenue</h2><p class="value">18,450
EGP</p></article>
      <article class="stat"><h2>Rating</h2><p class="value">4.8 / 5</
p></article>
    </div>
    <section class="panel">
      <h2>Recent orders</h2>
      <table>
        <thead><tr><th>Order</th><th>Book</th><th>Status</th></tr></
thead>
        <tbody>
          <tr><td>#1041</td><td>Learn HTML</td><td><span class="badge
ok">Paid</span></td></tr>
          <tr><td>#1040</td><td>CSS in Practice</td><td><span
class="badge wait">Pending</span></td></tr>
          <tr><td>#1039</td><td>JavaScript Basics</td><td><span
class="badge ok">Paid</span></td></tr>
        </tbody>
      </table>
    </section>
  </main>
</body>
</html>
```

Project 426: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
body { background: #f3f4f6; }
main { max-width: 64rem; margin: 0 auto; padding: 1.5rem 1rem; }
.stats { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(12rem, 1fr)); }
.stat { background: #fff; padding: 1rem 1.25rem; border-radius: 12px;
border-top: 4px solid var(--brand); }
.stat h2 { font-size: .85rem; color: var(--muted); margin: 0; text-
transform: uppercase; letter-spacing: .05em; }
.value { font-size: 1.8rem; font-weight: 700; margin: .25rem 0 0; }
.panel { background: #fff; border-radius: 12px; padding: 1.25rem;
margin-top: 1.5rem; }
table { width: 100%; border-collapse: collapse; }
th, td { text-align: left; padding: .6rem; border-bottom: 1px solid
var(--line); }
.badge { padding: .15rem .6rem; border-radius: 999px; font-size: .
8rem; font-weight: 600; }
.ok { background: #dcfce7; color: #166534; }
.wait { background: #fef9c3; color: #854d0e; }
```

Project 426 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - Dashboard</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cairo Book Shop dashboard	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="stat"> Visitors today 1,284...	A self-contained piece: card, post, product.
<article class="stat"> Books sold 57 </a...	Second-level heading for a section.

Line	What it does
<article class="stat"> Revenue <p class="value">18,450 EGP<//...	A paragraph of text.
<section class="panel">	A thematic group of content, normally with its own heading.
<table>	Tabular data in rows and columns.
<thead><tr><th>Order</th><th>Book</th><th>Status</th></tr></thead>	Group of header rows.
<tbody>	Group of data rows.
<tr><td>#1041</td><td>Learn HTML</td><td>Pai...	A table row.
<tr><td>#1040</td><td>CSS in Practice</td><td><span class="badge wa...	A data cell.
<tr><td>#1039</td><td>JavaScript Basics</td><td><span class="badge ...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.

Declaration	What it does
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
background: #f3f4f6;	Background colour or image.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
padding: 1.5rem 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(12rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 4px solid var(--brand);	A top border used as an accent or separator.
font-size: .85rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.

Declaration	What it does
letter-spacing: .05em;	Adds space between letters; useful for small capitals.
font-weight: 700;	Thickness of the text.
border-radius: 12px;	The line around the element: width, style and colour.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
border-radius: 999px;	Fully rounded pill shape.

Check your work

- Stat labels are headings
- Table has header cells
- Badge colours pass contrast
- Cards wrap on phones

Exercises

1. Add a simple bar chart made of divs with widths in percent.
2. Add a sidebar navigation.
3. Add a dark theme with prefers-color-scheme.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza

Field	Value
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 427: Statistics dashboard for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 2 | Files: index.html, styles.css

Brief

Build an admin-style dashboard: four statistic cards with a coloured top border and a panel containing a recent-orders table with status badges.

Learning goals

- Present numbers in cards with small uppercase labels
- Create pill-shaped status badges
- Combine grid cards and a table

Elements and CSS used

HTML elements	CSS features
article, h2, p, section, table, thead, tbody, span	border-top, text-transform, letter-spacing, border-radius: 999px, grid auto-fit

Build guide

1. Write four .stat articles inside .stats.
2. Add the panel with a small table.
3. Wrap statuses in .
4. Grid the cards.
5. Style the badges as pills with soft background colours.
6. Give the page a light grey background so white panels stand out.

Project 427: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - Dashboard</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Nile Bakery dashboard</h1>
    <div class="stats">
      <article class="stat"><h2>Visitors today</h2><p class="value">1,
284</p></article>
      <article class="stat"><h2>Pastries sold</h2><p
class="value">57</p></article>
      <article class="stat"><h2>Revenue</h2><p class="value">18,450
EGP</p></article>
      <article class="stat"><h2>Rating</h2><p class="value">4.8 / 5</
p></article>
    </div>
    <section class="panel">
      <h2>Recent orders</h2>
      <table>
        <thead><tr><th>Order</th><th>Pastry</th><th>Status</th></tr></
thead>
        <tbody>
          <tr><td>#1041</td><td>Sourdough loaf</td><td><span
class="badge ok">Paid</span></td></tr>
          <tr><td>#1040</td><td>Croissant</td><td><span class="badge
wait">Pending</span></td></tr>
          <tr><td>#1039</td><td>Date cookies</td><td><span
class="badge ok">Paid</span></td></tr>
        </tbody>
      </table>
    </section>
  </main>
</body>
</html>
```

Project 427: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
body { background: #f3f4f6; }
main { max-width: 64rem; margin: 0 auto; padding: 1.5rem 1rem; }
.stats { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(12rem, 1fr)); }
.stat { background: #fff; padding: 1rem 1.25rem; border-radius: 12px;
border-top: 4px solid var(--brand); }
.stat h2 { font-size: .85rem; color: var(--muted); margin: 0; text-
transform: uppercase; letter-spacing: .05em; }
.value { font-size: 1.8rem; font-weight: 700; margin: .25rem 0 0; }
.panel { background: #fff; border-radius: 12px; padding: 1.25rem;
margin-top: 1.5rem; }
table { width: 100%; border-collapse: collapse; }
th, td { text-align: left; padding: .6rem; border-bottom: 1px solid
var(--line); }
.badge { padding: .15rem .6rem; border-radius: 999px; font-size: .
8rem; font-weight: 600; }
.ok { background: #dcfce7; color: #166534; }
.wait { background: #fef9c3; color: #854d0e; }
```

Project 427 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - Dashboard</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Nile Bakery dashboard	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="stat"> Visitors today 1,284...	A self-contained piece: card, post, product.
<article class="stat"> Pastries sold 57 ...	Second-level heading for a section.

Line	What it does
<article class="stat"> Revenue <p class="value">18,450 EGP<//...	A paragraph of text.
<section class="panel">	A thematic group of content, normally with its own heading.
<table>	Tabular data in rows and columns.
<thead><tr><th>Order</th><th>Pastry</th><th>Status</th></tr></thead>	Group of header rows.
<tbody>	Group of data rows.
<tr><td>#1041</td><td>Sourdough loaf</td><td><span class="badge ok"...	A table row.
<tr><td>#1040</td><td>Croissant</td><td>Pe...	A data cell.
<tr><td>#1039</td><td>Date cookies</td><td>P...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.

Declaration	What it does
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
background: #f3f4f6;	Background colour or image.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
padding: 1.5rem 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(12rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 4px solid var(--brand);	A top border used as an accent or separator.
font-size: .85rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.

Declaration	What it does
font-weight: 700;	Thickness of the text.
border-radius: 12px;	The line around the element: width, style and colour.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
border-radius: 999px;	Fully rounded pill shape.

Check your work

- Stat labels are headings
- Table has header cells
- Badge colours pass contrast
- Cards wrap on phones

Exercises

1. Add a simple bar chart made of divs with widths in percent.
2. Add a sidebar navigation.
3. Add a dark theme with prefers-color-scheme.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d

Field	Value
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 428: Statistics dashboard for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 2 | Files: index.html, styles.css

Brief

Build an admin-style dashboard: four statistic cards with a coloured top border and a panel containing a recent-orders table with status badges.

Learning goals

- Present numbers in cards with small uppercase labels
- Create pill-shaped status badges
- Combine grid cards and a table

Elements and CSS used

HTML elements	CSS features
article, h2, p, section, table, thead, tbody, span	border-top, text-transform, letter-spacing, border-radius: 999px, grid auto-fit

Build guide

1. Write four .stat articles inside .stats.
2. Add the panel with a small table.
3. Wrap statuses in .
4. Grid the cards.
5. Style the badges as pills with soft background colours.
6. Give the page a light grey background so white panels stand out.

Project 428: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - Dashboard</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Pyramid Fitness dashboard</h1>
    <div class="stats">
      <article class="stat"><h2>Visitors today</h2><p class="value">1,
284</p></article>
      <article class="stat"><h2>Classes sold</h2><p class="value">57</
p></article>
      <article class="stat"><h2>Revenue</h2><p class="value">18,450
EGP</p></article>
      <article class="stat"><h2>Rating</h2><p class="value">4.8 / 5</
p></article>
    </div>
    <section class="panel">
      <h2>Recent orders</h2>
      <table>
        <thead><tr><th>Order</th><th>Class</th><th>Status</th></tr></
thead>
        <tbody>
          <tr><td>#1041</td><td>Morning yoga</td><td><span
class="badge ok">Paid</span></td></tr>
          <tr><td>#1040</td><td>Strength circuit</td><td><span
class="badge wait">Pending</span></td></tr>
          <tr><td>#1039</td><td>Spinning</td><td><span class="badge
ok">Paid</span></td></tr>
        </tbody>
      </table>
    </section>
  </main>
</body>
</html>
```

Project 428: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
body { background: #f3f4f6; }
main { max-width: 64rem; margin: 0 auto; padding: 1.5rem 1rem; }
.stats { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(12rem, 1fr)); }
.stat { background: #fff; padding: 1rem 1.25rem; border-radius: 12px;
border-top: 4px solid var(--brand); }
.stat h2 { font-size: .85rem; color: var(--muted); margin: 0; text-
transform: uppercase; letter-spacing: .05em; }
.value { font-size: 1.8rem; font-weight: 700; margin: .25rem 0 0; }
.panel { background: #fff; border-radius: 12px; padding: 1.25rem;
margin-top: 1.5rem; }
table { width: 100%; border-collapse: collapse; }
th, td { text-align: left; padding: .6rem; border-bottom: 1px solid
var(--line); }
.badge { padding: .15rem .6rem; border-radius: 999px; font-size: .
8rem; font-weight: 600; }
.ok { background: #dcfce7; color: #166534; }
.wait { background: #fef9c3; color: #854d0e; }
```

Project 428 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - Dashboard</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Pyramid Fitness dashboard	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="stat"> Visitors today 1,284...	A self-contained piece: card, post, product.
<article class="stat"> Classes sold 57 <...	Second-level heading for a section.

Line	What it does
<article class="stat"> Revenue <p class="value">18,450 EGP<//...	A paragraph of text.
<section class="panel">	A thematic group of content, normally with its own heading.
<table>	Tabular data in rows and columns.
<thead><tr><th>Order</th><th>Class</th><th>Status</th></tr></thead>	Group of header rows.
<tbody>	Group of data rows.
<tr><td>#1041</td><td>Morning yoga</td><td>P...	A table row.
<tr><td>#1040</td><td>Strength circuit</td><td><span class="badge w...	A data cell.
<tr><td>#1039</td><td>Spinning</td><td>Paid<...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.

Declaration	What it does
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
background: #f3f4f6;	Background colour or image.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
padding: 1.5rem 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(12rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 4px solid var(--brand);	A top border used as an accent or separator.
font-size: .85rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.

Declaration	What it does
font-weight: 700;	Thickness of the text.
border-radius: 12px;	The line around the element: width, style and colour.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
border-radius: 999px;	Fully rounded pill shape.

Check your work

- Stat labels are headings
- Table has header cells
- Badge colours pass contrast
- Cards wrap on phones

Exercises

1. Add a simple bar chart made of divs with widths in percent.
2. Add a sidebar navigation.
3. Add a dark theme with prefers-color-scheme.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e

Field	Value
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 429: Statistics dashboard for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 2 | Files: index.html, styles.css

Brief

Build an admin-style dashboard: four statistic cards with a coloured top border and a panel containing a recent-orders table with status badges.

Learning goals

- Present numbers in cards with small uppercase labels
- Create pill-shaped status badges
- Combine grid cards and a table

Elements and CSS used

HTML elements	CSS features
article, h2, p, section, table, thead, tbody, span	border-top, text-transform, letter-spacing, border-radius: 999px, grid auto-fit

Build guide

1. Write four .stat articles inside .stats.
2. Add the panel with a small table.
3. Wrap statuses in .
4. Grid the cards.
5. Style the badges as pills with soft background colours.
6. Give the page a light grey background so white panels stand out.

Project 429: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - Dashboard</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Delta Dental Clinic dashboard</h1>
    <div class="stats">
      <article class="stat"><h2>Visitors today</h2><p class="value">1,
284</p></article>
      <article class="stat"><h2>Services sold</h2><p
class="value">57</p></article>
      <article class="stat"><h2>Revenue</h2><p class="value">18,450
EGP</p></article>
      <article class="stat"><h2>Rating</h2><p class="value">4.8 / 5</
p></article>
    </div>
    <section class="panel">
      <h2>Recent orders</h2>
      <table>
        <thead><tr><th>Order</th><th>Service</th><th>Status</th></
tr></thead>
        <tbody>
          <tr><td>#1041</td><td>Check-up</td><td><span class="badge
ok">Paid</span></td></tr>
          <tr><td>#1040</td><td>Whitening</td><td><span class="badge
wait">Pending</span></td></tr>
          <tr><td>#1039</td><td>Filling</td><td><span class="badge
ok">Paid</span></td></tr>
        </tbody>
      </table>
    </section>
  </main>
</body>
</html>
```

Project 429: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
body { background: #f3f4f6; }
main { max-width: 64rem; margin: 0 auto; padding: 1.5rem 1rem; }
.stats { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(12rem, 1fr)); }
.stat { background: #fff; padding: 1rem 1.25rem; border-radius: 12px;
border-top: 4px solid var(--brand); }
.stat h2 { font-size: .85rem; color: var(--muted); margin: 0; text-
transform: uppercase; letter-spacing: .05em; }
.value { font-size: 1.8rem; font-weight: 700; margin: .25rem 0 0; }
.panel { background: #fff; border-radius: 12px; padding: 1.25rem;
margin-top: 1.5rem; }
table { width: 100%; border-collapse: collapse; }
th, td { text-align: left; padding: .6rem; border-bottom: 1px solid
var(--line); }
.badge { padding: .15rem .6rem; border-radius: 999px; font-size: .
8rem; font-weight: 600; }
.ok { background: #dcfce7; color: #166534; }
.wait { background: #fef9c3; color: #854d0e; }
```

Project 429 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - Dashboard</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Delta Dental Clinic dashboard	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="stat"> Visitors today 1,284...	A self-contained piece: card, post, product.
<article class="stat"> Services sold 57 ...	Second-level heading for a section.

Line	What it does
<article class="stat"> Revenue <p class="value">18,450 EGP<//...	A paragraph of text.
<section class="panel">	A thematic group of content, normally with its own heading.
<table>	Tabular data in rows and columns.
<thead><tr><th>Order</th><th>Service</th><th>Status</th></tr></thead>	Group of header rows.
<tbody>	Group of data rows.
<tr><td>#1041</td><td>Check-up</td><td>Paid<...	A table row.
<tr><td>#1040</td><td>Whitening</td><td>Pe...	A data cell.
<tr><td>#1039</td><td>Filling</td><td>Paid<//...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.

Declaration	What it does
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
background: #f3f4f6;	Background colour or image.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
padding: 1.5rem 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(12rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 4px solid var(--brand);	A top border used as an accent or separator.
font-size: .85rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.

Declaration	What it does
font-weight: 700;	Thickness of the text.
border-radius: 12px;	The line around the element: width, style and colour.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
border-radius: 999px;	Fully rounded pill shape.

Check your work

- Stat labels are headings
- Table has header cells
- Badge colours pass contrast
- Cards wrap on phones

Exercises

1. Add a simple bar chart made of divs with widths in percent.
2. Add a sidebar navigation.
3. Add a dark theme with prefers-color-scheme.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8

Field	Value
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 430: Statistics dashboard for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 2 | Files: index.html, styles.css

Brief

Build an admin-style dashboard: four statistic cards with a coloured top border and a panel containing a recent-orders table with status badges.

Learning goals

- Present numbers in cards with small uppercase labels
- Create pill-shaped status badges
- Combine grid cards and a table

Elements and CSS used

HTML elements	CSS features
article, h2, p, section, table, thead, tbody, span	border-top, text-transform, letter-spacing, border-radius: 999px, grid auto-fit

Build guide

1. Write four .stat articles inside .stats.
2. Add the panel with a small table.
3. Wrap statuses in .
4. Grid the cards.
5. Style the badges as pills with soft background colours.
6. Give the page a light grey background so white panels stand out.

Project 430: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - Dashboard</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Red Sea Travel dashboard</h1>
    <div class="stats">
      <article class="stat"><h2>Visitors today</h2><p class="value">1,
284</p></article>
      <article class="stat"><h2>Tours sold</h2><p class="value">57</
p></article>
      <article class="stat"><h2>Revenue</h2><p class="value">18,450
EGP</p></article>
      <article class="stat"><h2>Rating</h2><p class="value">4.8 / 5</
p></article>
    </div>
    <section class="panel">
      <h2>Recent orders</h2>
      <table>
        <thead><tr><th>Order</th><th>Tour</th><th>Status</th></tr></
thead>
        <tbody>
          <tr><td>#1041</td><td>Luxor day trip</td><td><span
class="badge ok">Paid</span></td></tr>
          <tr><td>#1040</td><td>Snorkelling</td><td><span
class="badge wait">Pending</span></td></tr>
          <tr><td>#1039</td><td>Desert safari</td><td><span
class="badge ok">Paid</span></td></tr>
        </tbody>
      </table>
    </section>
  </main>
</body>
</html>
```

Project 430: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
body { background: #f3f4f6; }
main { max-width: 64rem; margin: 0 auto; padding: 1.5rem 1rem; }
.stats { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(12rem, 1fr)); }
.stat { background: #fff; padding: 1rem 1.25rem; border-radius: 12px;
border-top: 4px solid var(--brand); }
.stat h2 { font-size: .85rem; color: var(--muted); margin: 0; text-
transform: uppercase; letter-spacing: .05em; }
.value { font-size: 1.8rem; font-weight: 700; margin: .25rem 0 0; }
.panel { background: #fff; border-radius: 12px; padding: 1.25rem;
margin-top: 1.5rem; }
table { width: 100%; border-collapse: collapse; }
th, td { text-align: left; padding: .6rem; border-bottom: 1px solid
var(--line); }
.badge { padding: .15rem .6rem; border-radius: 999px; font-size: .
8rem; font-weight: 600; }
.ok { background: #dcfce7; color: #166534; }
.wait { background: #fef9c3; color: #854d0e; }
```

Project 430 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - Dashboard</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Red Sea Travel dashboard	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="stat"> Visitors today 1,284...	A self-contained piece: card, post, product.
<article class="stat"> Tours sold 57 </a...	Second-level heading for a section.

Line	What it does
<article class="stat"> Revenue <p class="value">18,450 EGP<//...	A paragraph of text.
<section class="panel">	A thematic group of content, normally with its own heading.
<table>	Tabular data in rows and columns.
<thead><tr><th>Order</th><th>Tour</th><th>Status</th></tr></thead>	Group of header rows.
<tbody>	Group of data rows.
<tr><td>#1041</td><td>Luxor day trip</td><td><span class="badge ok"...	A table row.
<tr><td>#1040</td><td>Snorkelling</td><td>...	A data cell.
<tr><td>#1039</td><td>Desert safari</td><td>...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.

Declaration	What it does
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
background: #f3f4f6;	Background colour or image.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
padding: 1.5rem 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(12rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 4px solid var(--brand);	A top border used as an accent or separator.
font-size: .85rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.

Declaration	What it does
font-weight: 700;	Thickness of the text.
border-radius: 12px;	The line around the element: width, style and colour.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
border-radius: 999px;	Fully rounded pill shape.

Check your work

- Stat labels are headings
- Table has header cells
- Badge colours pass contrast
- Cards wrap on phones

Exercises

1. Add a simple bar chart made of divs with widths in percent.
2. Add a sidebar navigation.
3. Add a dark theme with prefers-color-scheme.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1

Field	Value
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 431: Statistics dashboard for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Build an admin-style dashboard: four statistic cards with a coloured top border and a panel containing a recent-orders table with status badges.

Learning goals

- Present numbers in cards with small uppercase labels
- Create pill-shaped status badges
- Combine grid cards and a table

Elements and CSS used

HTML elements	CSS features
article, h2, p, section, table, thead, tbody, span	border-top, text-transform, letter-spacing, border-radius: 999px, grid auto-fit

Build guide

1. Write four .stat articles inside .stats.
2. Add the panel with a small table.
3. Wrap statuses in .
4. Grid the cards.
5. Style the badges as pills with soft background colours.

6. Give the page a light grey background so white panels stand out.

Project 431: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - Dashboard</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Lotus Language School dashboard</h1>
    <div class="stats">
      <article class="stat"><h2>Visitors today</h2><p class="value">1,
284</p></article>
      <article class="stat"><h2>Courses sold</h2><p class="value">57</
p></article>
      <article class="stat"><h2>Revenue</h2><p class="value">18,450
EGP</p></article>
      <article class="stat"><h2>Rating</h2><p class="value">4.8 / 5</
p></article>
    </div>
    <section class="panel">
      <h2>Recent orders</h2>
      <table>
        <thead><tr><th>Order</th><th>Course</th><th>Status</th></tr></
thead>
        <tbody>
          <tr><td>#1041</td><td>English A1</td><td><span class="badge
ok">Paid</span></td></tr>
          <tr><td>#1040</td><td>French B1</td><td><span class="badge
wait">Pending</span></td></tr>
          <tr><td>#1039</td><td>German A2</td><td><span class="badge
ok">Paid</span></td></tr>
        </tbody>
      </table>
    </section>
  </main>
</body>
</html>
```

Project 431: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
body { background: #f3f4f6; }
main { max-width: 64rem; margin: 0 auto; padding: 1.5rem 1rem; }
.stats { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(12rem, 1fr)); }
.stat { background: #fff; padding: 1rem 1.25rem; border-radius: 12px;
border-top: 4px solid var(--brand); }
.stat h2 { font-size: .85rem; color: var(--muted); margin: 0; text-
transform: uppercase; letter-spacing: .05em; }
.value { font-size: 1.8rem; font-weight: 700; margin: .25rem 0 0; }
.panel { background: #fff; border-radius: 12px; padding: 1.25rem;
margin-top: 1.5rem; }
table { width: 100%; border-collapse: collapse; }
th, td { text-align: left; padding: .6rem; border-bottom: 1px solid
var(--line); }
.badge { padding: .15rem .6rem; border-radius: 999px; font-size: .
8rem; font-weight: 600; }
.ok { background: #dcfce7; color: #166534; }
.wait { background: #fef9c3; color: #854d0e; }
```

Project 431 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - Dashboard</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Lotus Language School dashboard	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="stat"> Visitors today 1,284...	A self-contained piece: card, post, product.
<article class="stat"> Courses sold 57 <...	Second-level heading for a section.

Line	What it does
<article class="stat"> Revenue <p class="value">18,450 EGP<//...	A paragraph of text.
<section class="panel">	A thematic group of content, normally with its own heading.
<table>	Tabular data in rows and columns.
<thead><tr><th>Order</th><th>Course</th><th>Status</th></tr></thead>	Group of header rows.
<tbody>	Group of data rows.
<tr><td>#1041</td><td>English A1</td><td>Pai...	A table row.
<tr><td>#1040</td><td>French B1</td><td>Pe...	A data cell.
<tr><td>#1039</td><td>German A2</td><td>Paid...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.

Declaration	What it does
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
background: #f3f4f6;	Background colour or image.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
padding: 1.5rem 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(12rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 4px solid var(--brand);	A top border used as an accent or separator.
font-size: .85rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.

Declaration	What it does
font-weight: 700;	Thickness of the text.
border-radius: 12px;	The line around the element: width, style and colour.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
border-radius: 999px;	Fully rounded pill shape.

Check your work

- Stat labels are headings
- Table has header cells
- Badge colours pass contrast
- Cards wrap on phones

Exercises

1. Add a simple bar chart made of divs with widths in percent.
2. Add a sidebar navigation.
3. Add a dark theme with prefers-color-scheme.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed

Field	Value
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 432: Statistics dashboard for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 2 | Files: index.html, styles.css

Brief

Build an admin-style dashboard: four statistic cards with a coloured top border and a panel containing a recent-orders table with status badges.

Learning goals

- Present numbers in cards with small uppercase labels
- Create pill-shaped status badges
- Combine grid cards and a table

Elements and CSS used

HTML elements	CSS features
article, h2, p, section, table, thead, tbody, span	border-top, text-transform, letter-spacing, border-radius: 999px, grid auto-fit

Build guide

1. Write four .stat articles inside .stats.
2. Add the panel with a small table.
3. Wrap statuses in .
4. Grid the cards.
5. Style the badges as pills with soft background colours.
6. Give the page a light grey background so white panels stand out.

Project 432: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - Dashboard</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Green Leaf Cafe dashboard</h1>
    <div class="stats">
      <article class="stat"><h2>Visitors today</h2><p class="value">1,
284</p></article>
      <article class="stat"><h2>Drinks sold</h2><p class="value">57</
p></article>
      <article class="stat"><h2>Revenue</h2><p class="value">18,450
EGP</p></article>
      <article class="stat"><h2>Rating</h2><p class="value">4.8 / 5</
p></article>
    </div>
    <section class="panel">
      <h2>Recent orders</h2>
      <table>
        <thead><tr><th>Order</th><th>Drink</th><th>Status</th></tr></
thead>
        <tbody>
          <tr><td>#1041</td><td>Flat white</td><td><span class="badge
ok">Paid</span></td></tr>
          <tr><td>#1040</td><td>Cold brew</td><td><span class="badge
wait">Pending</span></td></tr>
          <tr><td>#1039</td><td>Hibiscus iced tea</td><td><span
class="badge ok">Paid</span></td></tr>
        </tbody>
      </table>
    </section>
  </main>
</body>
</html>
```

Project 432: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
body { background: #f3f4f6; }
main { max-width: 64rem; margin: 0 auto; padding: 1.5rem 1rem; }
.stats { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(12rem, 1fr)); }
.stat { background: #fff; padding: 1rem 1.25rem; border-radius: 12px;
border-top: 4px solid var(--brand); }
.stat h2 { font-size: .85rem; color: var(--muted); margin: 0; text-
transform: uppercase; letter-spacing: .05em; }
.value { font-size: 1.8rem; font-weight: 700; margin: .25rem 0 0; }
.panel { background: #fff; border-radius: 12px; padding: 1.25rem;
margin-top: 1.5rem; }
table { width: 100%; border-collapse: collapse; }
th, td { text-align: left; padding: .6rem; border-bottom: 1px solid
var(--line); }
.badge { padding: .15rem .6rem; border-radius: 999px; font-size: .
8rem; font-weight: 600; }
.ok { background: #dcfce7; color: #166534; }
.wait { background: #fef9c3; color: #854d0e; }
```

Project 432 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - Dashboard</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Green Leaf Cafe dashboard	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="stat"> Visitors today 1,284...	A self-contained piece: card, post, product.
<article class="stat"> Drinks sold 57 </...	Second-level heading for a section.

Line	What it does
<article class="stat"> Revenue <p class="value">18,450 EGP<//...	A paragraph of text.
<section class="panel">	A thematic group of content, normally with its own heading.
<table>	Tabular data in rows and columns.
<thead><tr><th>Order</th><th>Drink</th><th>Status</th></tr></thead>	Group of header rows.
<tbody>	Group of data rows.
<tr><td>#1041</td><td>Flat white</td><td>Pai...	A table row.
<tr><td>#1040</td><td>Cold brew</td><td>Pe...	A data cell.
<tr><td>#1039</td><td>Hibiscus iced tea</td><td><span class="badge ...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.

Declaration	What it does
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
background: #f3f4f6;	Background colour or image.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
padding: 1.5rem 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(12rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 4px solid var(--brand);	A top border used as an accent or separator.
font-size: .85rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.

Declaration	What it does
font-weight: 700;	Thickness of the text.
border-radius: 12px;	The line around the element: width, style and colour.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
border-radius: 999px;	Fully rounded pill shape.

Check your work

- Stat labels are headings
- Table has header cells
- Badge colours pass contrast
- Cards wrap on phones

Exercises

1. Add a simple bar chart made of divs with widths in percent.
2. Add a sidebar navigation.
3. Add a dark theme with prefers-color-scheme.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534

Field	Value
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 433: Statistics dashboard for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 2 | Files: index.html, styles.css

Brief

Build an admin-style dashboard: four statistic cards with a coloured top border and a panel containing a recent-orders table with status badges.

Learning goals

- Present numbers in cards with small uppercase labels
- Create pill-shaped status badges
- Combine grid cards and a table

Elements and CSS used

HTML elements	CSS features
article, h2, p, section, table, thead, tbody, span	border-top, text-transform, letter-spacing, border-radius: 999px, grid auto-fit

Build guide

1. Write four .stat articles inside .stats.
2. Add the panel with a small table.
3. Wrap statuses in .
4. Grid the cards.
5. Style the badges as pills with soft background colours.

6. Give the page a light grey background so white panels stand out.

Project 433: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - Dashboard</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Sinai Trekking Club dashboard</h1>
    <div class="stats">
      <article class="stat"><h2>Visitors today</h2><p class="value">1,
284</p></article>
      <article class="stat"><h2>Hikes sold</h2><p class="value">57</
p></article>
      <article class="stat"><h2>Revenue</h2><p class="value">18,450
EGP</p></article>
      <article class="stat"><h2>Rating</h2><p class="value">4.8 / 5</
p></article>
    </div>
    <section class="panel">
      <h2>Recent orders</h2>
      <table>
        <thead><tr><th>Order</th><th>Hike</th><th>Status</th></tr></
thead>
        <tbody>
          <tr><td>#1041</td><td>Mount Sinai sunrise</td><td><span
class="badge ok">Paid</span></td></tr>
          <tr><td>#1040</td><td>Blue Desert loop</td><td><span
class="badge wait">Pending</span></td></tr>
          <tr><td>#1039</td><td>Wadi Gnai</td><td><span class="badge
ok">Paid</span></td></tr>
        </tbody>
      </table>
    </section>
  </main>
</body>
</html>
```

Project 433: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
body { background: #f3f4f6; }
main { max-width: 64rem; margin: 0 auto; padding: 1.5rem 1rem; }
.stats { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(12rem, 1fr)); }
.stat { background: #fff; padding: 1rem 1.25rem; border-radius: 12px;
border-top: 4px solid var(--brand); }
.stat h2 { font-size: .85rem; color: var(--muted); margin: 0; text-
transform: uppercase; letter-spacing: .05em; }
.value { font-size: 1.8rem; font-weight: 700; margin: .25rem 0 0; }
.panel { background: #fff; border-radius: 12px; padding: 1.25rem;
margin-top: 1.5rem; }
table { width: 100%; border-collapse: collapse; }
th, td { text-align: left; padding: .6rem; border-bottom: 1px solid
var(--line); }
.badge { padding: .15rem .6rem; border-radius: 999px; font-size: .
8rem; font-weight: 600; }
.ok { background: #dcfce7; color: #166534; }
.wait { background: #fef9c3; color: #854d0e; }
```

Project 433 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - Dashboard</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Sinai Trekking Club dashboard	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="stat"> Visitors today 1,284...	A self-contained piece: card, post, product.
<article class="stat"> Hikes sold 57 </a...	Second-level heading for a section.

Line	What it does
<article class="stat"> Revenue <p class="value">18,450 EGP<//...	A paragraph of text.
<section class="panel">	A thematic group of content, normally with its own heading.
<table>	Tabular data in rows and columns.
<thead><tr><th>Order</th><th>Hike</th><th>Status</th></tr></thead>	Group of header rows.
<tbody>	Group of data rows.
<tr><td>#1041</td><td>Mount Sinai sunrise</td><td><span class="badg...	A table row.
<tr><td>#1040</td><td>Blue Desert loop</td><td><span class="badge w...	A data cell.
<tr><td>#1039</td><td>Wadi Gnai</td><td>Paid...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.

Declaration	What it does
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
background: #f3f4f6;	Background colour or image.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
padding: 1.5rem 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(12rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 4px solid var(--brand);	A top border used as an accent or separator.
font-size: .85rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.

Declaration	What it does
letter-spacing: .05em;	Adds space between letters; useful for small capitals.
font-weight: 700;	Thickness of the text.
border-radius: 12px;	The line around the element: width, style and colour.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
border-radius: 999px;	Fully rounded pill shape.

Check your work

- Stat labels are headings
- Table has header cells
- Badge colours pass contrast
- Cards wrap on phones

Exercises

1. Add a simple bar chart made of divs with widths in percent.
2. Add a sidebar navigation.
3. Add a dark theme with prefers-color-scheme.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine

Field	Value
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 434: Statistics dashboard for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 2 | Files: index.html, styles.css

Brief

Build an admin-style dashboard: four statistic cards with a coloured top border and a panel containing a recent-orders table with status badges.

Learning goals

- Present numbers in cards with small uppercase labels
- Create pill-shaped status badges
- Combine grid cards and a table

Elements and CSS used

HTML elements	CSS features
article, h2, p, section, table, thead, tbody, span	border-top, text-transform, letter-spacing, border-radius: 999px, grid auto-fit

Build guide

1. Write four .stat articles inside .stats.
2. Add the panel with a small table.
3. Wrap statuses in .
4. Grid the cards.
5. Style the badges as pills with soft background colours.
6. Give the page a light grey background so white panels stand out.

Project 434: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - Dashboard</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Horizon Photography dashboard</h1>
    <div class="stats">
      <article class="stat"><h2>Visitors today</h2><p class="value">1,
284</p></article>
      <article class="stat"><h2>Sessions sold</h2><p
class="value">57</p></article>
      <article class="stat"><h2>Revenue</h2><p class="value">18,450
EGP</p></article>
      <article class="stat"><h2>Rating</h2><p class="value">4.8 / 5</
p></article>
    </div>
    <section class="panel">
      <h2>Recent orders</h2>
      <table>
        <thead><tr><th>Order</th><th>Session</th><th>Status</th></
tr></thead>
        <tbody>
          <tr><td>#1041</td><td>Portrait session</td><td><span
class="badge ok">Paid</span></td></tr>
          <tr><td>#1040</td><td>Wedding day</td><td><span
class="badge wait">Pending</span></td></tr>
          <tr><td>#1039</td><td>Product shoot</td><td><span
class="badge ok">Paid</span></td></tr>
        </tbody>
      </table>
    </section>
  </main>
</body>
</html>
```

Project 434: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
body { background: #f3f4f6; }
main { max-width: 64rem; margin: 0 auto; padding: 1.5rem 1rem; }
.stats { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(12rem, 1fr)); }
.stat { background: #fff; padding: 1rem 1.25rem; border-radius: 12px;
border-top: 4px solid var(--brand); }
.stat h2 { font-size: .85rem; color: var(--muted); margin: 0; text-
transform: uppercase; letter-spacing: .05em; }
.value { font-size: 1.8rem; font-weight: 700; margin: .25rem 0 0; }
.panel { background: #fff; border-radius: 12px; padding: 1.25rem;
margin-top: 1.5rem; }
table { width: 100%; border-collapse: collapse; }
th, td { text-align: left; padding: .6rem; border-bottom: 1px solid
var(--line); }
.badge { padding: .15rem .6rem; border-radius: 999px; font-size: .
8rem; font-weight: 600; }
.ok { background: #dcfce7; color: #166534; }
.wait { background: #fef9c3; color: #854d0e; }
```

Project 434 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - Dashboard</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Horizon Photography dashboard	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="stat"> Visitors today 1,284...	A self-contained piece: card, post, product.
<article class="stat"> Sessions sold 57 ...	Second-level heading for a section.

Line	What it does
<article class="stat"> Revenue <p class="value">18,450 EGP<//...	A paragraph of text.
<section class="panel">	A thematic group of content, normally with its own heading.
<table>	Tabular data in rows and columns.
<thead><tr><th>Order</th><th>Session</th><th>Status</th></tr></thead>	Group of header rows.
<tbody>	Group of data rows.
<tr><td>#1041</td><td>Portrait session</td><td><span class="badge o...	A table row.
<tr><td>#1040</td><td>Wedding day</td><td>...	A data cell.
<tr><td>#1039</td><td>Product shoot</td><td>...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.

Declaration	What it does
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
background: #f3f4f6;	Background colour or image.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
padding: 1.5rem 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(12rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 4px solid var(--brand);	A top border used as an accent or separator.
font-size: .85rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.

Declaration	What it does
font-weight: 700;	Thickness of the text.
border-radius: 12px;	The line around the element: width, style and colour.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
border-radius: 999px;	Fully rounded pill shape.

Check your work

- Stat labels are headings
- Table has header cells
- Badge colours pass contrast
- Cards wrap on phones

Exercises

1. Add a simple bar chart made of divs with widths in percent.
2. Add a sidebar navigation.
3. Add a dark theme with prefers-color-scheme.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827

Field	Value
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 435: Statistics dashboard for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 2 | Files: index.html, styles.css

Brief

Build an admin-style dashboard: four statistic cards with a coloured top border and a panel containing a recent-orders table with status badges.

Learning goals

- Present numbers in cards with small uppercase labels
- Create pill-shaped status badges
- Combine grid cards and a table

Elements and CSS used

HTML elements	CSS features
article, h2, p, section, table, thead, tbody, span	border-top, text-transform, letter-spacing, border-radius: 999px, grid auto-fit

Build guide

1. Write four .stat articles inside .stats.
2. Add the panel with a small table.
3. Wrap statuses in .
4. Grid the cards.
5. Style the badges as pills with soft background colours.
6. Give the page a light grey background so white panels stand out.

Project 435: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - Dashboard</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Papyrus Stationery dashboard</h1>
    <div class="stats">
      <article class="stat"><h2>Visitors today</h2><p class="value">1,
284</p></article>
      <article class="stat"><h2>Products sold</h2><p
class="value">57</p></article>
      <article class="stat"><h2>Revenue</h2><p class="value">18,450
EGP</p></article>
      <article class="stat"><h2>Rating</h2><p class="value">4.8 / 5</
p></article>
    </div>
    <section class="panel">
      <h2>Recent orders</h2>
      <table>
        <thead><tr><th>Order</th><th>Product</th><th>Status</th></
tr></thead>
        <tbody>
          <tr><td>#1041</td><td>Dotted notebook</td><td><span
class="badge ok">Paid</span></td></tr>
          <tr><td>#1040</td><td>Fountain pen</td><td><span
class="badge wait">Pending</span></td></tr>
          <tr><td>#1039</td><td>Washi tape set</td><td><span
class="badge ok">Paid</span></td></tr>
        </tbody>
      </table>
    </section>
  </main>
</body>
</html>
```

Project 435: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
body { background: #f3f4f6; }
main { max-width: 64rem; margin: 0 auto; padding: 1.5rem 1rem; }
.stats { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(12rem, 1fr)); }
.stat { background: #fff; padding: 1rem 1.25rem; border-radius: 12px;
border-top: 4px solid var(--brand); }
.stat h2 { font-size: .85rem; color: var(--muted); margin: 0; text-
transform: uppercase; letter-spacing: .05em; }
.value { font-size: 1.8rem; font-weight: 700; margin: .25rem 0 0; }
.panel { background: #fff; border-radius: 12px; padding: 1.25rem;
margin-top: 1.5rem; }
table { width: 100%; border-collapse: collapse; }
th, td { text-align: left; padding: .6rem; border-bottom: 1px solid
var(--line); }
.badge { padding: .15rem .6rem; border-radius: 999px; font-size: .
8rem; font-weight: 600; }
.ok { background: #dcfce7; color: #166534; }
.wait { background: #fef9c3; color: #854d0e; }
```

Project 435 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - Dashboard</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Papyrus Stationery dashboard	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="stat"> Visitors today 1,284...	A self-contained piece: card, post, product.
<article class="stat"> Products sold 57 ...	Second-level heading for a section.

Line	What it does
<article class="stat"> Revenue <p class="value">18,450 EGP<//...	A paragraph of text.
<section class="panel">	A thematic group of content, normally with its own heading.
<table>	Tabular data in rows and columns.
<thead><tr><th>Order</th><th>Product</th><th>Status</th></tr></thead>	Group of header rows.
<tbody>	Group of data rows.
<tr><td>#1041</td><td>Dotted notebook</td><td><span class="badge ok...	A table row.
<tr><td>#1040</td><td>Fountain pen</td><td><span class="badge wait"...	A data cell.
<tr><td>#1039</td><td>Washi tape set</td><td><span class="badge ok"...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.

Declaration	What it does
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
background: #f3f4f6;	Background colour or image.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
padding: 1.5rem 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(12rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 4px solid var(--brand);	A top border used as an accent or separator.
font-size: .85rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.

Declaration	What it does
font-weight: 700;	Thickness of the text.
border-radius: 12px;	The line around the element: width, style and colour.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
border-radius: 999px;	Fully rounded pill shape.

Check your work

- Stat labels are headings
- Table has header cells
- Badge colours pass contrast
- Cards wrap on phones

Exercises

1. Add a simple bar chart made of divs with widths in percent.
2. Add a sidebar navigation.
3. Add a dark theme with prefers-color-scheme.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d

Field	Value
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 436: Statistics dashboard for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 2 | Files: index.html, styles.css

Brief

Build an admin-style dashboard: four statistic cards with a coloured top border and a panel containing a recent-orders table with status badges.

Learning goals

- Present numbers in cards with small uppercase labels
- Create pill-shaped status badges
- Combine grid cards and a table

Elements and CSS used

HTML elements	CSS features
article, h2, p, section, table, thead, tbody, span	border-top, text-transform, letter-spacing, border-radius: 999px, grid auto-fit

Build guide

1. Write four .stat articles inside .stats.
2. Add the panel with a small table.
3. Wrap statuses in .
4. Grid the cards.
5. Style the badges as pills with soft background colours.

6. Give the page a light grey background so white panels stand out.

Project 436: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - Dashboard</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Oasis Plant Nursery dashboard</h1>
    <div class="stats">
      <article class="stat"><h2>Visitors today</h2><p class="value">1,
284</p></article>
      <article class="stat"><h2>Plants sold</h2><p class="value">57</
p></article>
      <article class="stat"><h2>Revenue</h2><p class="value">18,450
EGP</p></article>
      <article class="stat"><h2>Rating</h2><p class="value">4.8 / 5</
p></article>
    </div>
    <section class="panel">
      <h2>Recent orders</h2>
      <table>
        <thead><tr><th>Order</th><th>Plant</th><th>Status</th></tr></
thead>
        <tbody>
          <tr><td>#1041</td><td>Monstera</td><td><span class="badge
ok">Paid</span></td></tr>
          <tr><td>#1040</td><td>Snake plant</td><td><span
class="badge wait">Pending</span></td></tr>
          <tr><td>#1039</td><td>Basil pot</td><td><span class="badge
ok">Paid</span></td></tr>
        </tbody>
      </table>
    </section>
  </main>
</body>
</html>
```

Project 436: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
body { background: #f3f4f6; }
main { max-width: 64rem; margin: 0 auto; padding: 1.5rem 1rem; }
.stats { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(12rem, 1fr)); }
.stat { background: #fff; padding: 1rem 1.25rem; border-radius: 12px;
border-top: 4px solid var(--brand); }
.stat h2 { font-size: .85rem; color: var(--muted); margin: 0; text-
transform: uppercase; letter-spacing: .05em; }
.value { font-size: 1.8rem; font-weight: 700; margin: .25rem 0 0; }
.panel { background: #fff; border-radius: 12px; padding: 1.25rem;
margin-top: 1.5rem; }
table { width: 100%; border-collapse: collapse; }
th, td { text-align: left; padding: .6rem; border-bottom: 1px solid
var(--line); }
.badge { padding: .15rem .6rem; border-radius: 999px; font-size: .
8rem; font-weight: 600; }
.ok { background: #dcfce7; color: #166534; }
.wait { background: #fef9c3; color: #854d0e; }
```

Project 436 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - Dashboard</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Oasis Plant Nursery dashboard	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="stat"> Visitors today 1,284...	A self-contained piece: card, post, product.
<article class="stat"> Plants sold 57 </...	Second-level heading for a section.

Line	What it does
<article class="stat"> Revenue <p class="value">18,450 EGP<//...	A paragraph of text.
<section class="panel">	A thematic group of content, normally with its own heading.
<table>	Tabular data in rows and columns.
<thead><tr><th>Order</th><th>Plant</th><th>Status</th></tr></thead>	Group of header rows.
<tbody>	Group of data rows.
<tr><td>#1041</td><td>Monstera</td><td>Paid<...	A table row.
<tr><td>#1040</td><td>Snake plant</td><td>...	A data cell.
<tr><td>#1039</td><td>Basil pot</td><td>Paid...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.

Declaration	What it does
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
background: #f3f4f6;	Background colour or image.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
padding: 1.5rem 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(12rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 4px solid var(--brand);	A top border used as an accent or separator.
font-size: .85rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.

Declaration	What it does
font-weight: 700;	Thickness of the text.
border-radius: 12px;	The line around the element: width, style and colour.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
border-radius: 999px;	Fully rounded pill shape.

Check your work

- Stat labels are headings
- Table has header cells
- Badge colours pass contrast
- Cards wrap on phones

Exercises

1. Add a simple bar chart made of divs with widths in percent.
2. Add a sidebar navigation.
3. Add a dark theme with prefers-color-scheme.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d

Field	Value
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 437: Statistics dashboard for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 2 | Files: index.html, styles.css

Brief

Build an admin-style dashboard: four statistic cards with a coloured top border and a panel containing a recent-orders table with status badges.

Learning goals

- Present numbers in cards with small uppercase labels
- Create pill-shaped status badges
- Combine grid cards and a table

Elements and CSS used

HTML elements	CSS features
article, h2, p, section, table, thead, tbody, span	border-top, text-transform, letter-spacing, border-radius: 999px, grid auto-fit

Build guide

1. Write four .stat articles inside .stats.
2. Add the panel with a small table.
3. Wrap statuses in .
4. Grid the cards.
5. Style the badges as pills with soft background colours.
6. Give the page a light grey background so white panels stand out.

Project 437: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - Dashboard</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cedar Furniture dashboard</h1>
    <div class="stats">
      <article class="stat"><h2>Visitors today</h2><p class="value">1,
284</p></article>
      <article class="stat"><h2>Pieces sold</h2><p class="value">57</
p></article>
      <article class="stat"><h2>Revenue</h2><p class="value">18,450
EGP</p></article>
      <article class="stat"><h2>Rating</h2><p class="value">4.8 / 5</
p></article>
    </div>
    <section class="panel">
      <h2>Recent orders</h2>
      <table>
        <thead><tr><th>Order</th><th>Piece</th><th>Status</th></tr></
thead>
        <tbody>
          <tr><td>#1041</td><td>Oak dining table</td><td><span
class="badge ok">Paid</span></td></tr>
          <tr><td>#1040</td><td>Bookshelf</td><td><span class="badge
wait">Pending</span></td></tr>
          <tr><td>#1039</td><td>Bedside table</td><td><span
class="badge ok">Paid</span></td></tr>
        </tbody>
      </table>
    </section>
  </main>
</body>
</html>
```

Project 437: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
body { background: #f3f4f6; }
main { max-width: 64rem; margin: 0 auto; padding: 1.5rem 1rem; }
.stats { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(12rem, 1fr)); }
.stat { background: #fff; padding: 1rem 1.25rem; border-radius: 12px;
border-top: 4px solid var(--brand); }
.stat h2 { font-size: .85rem; color: var(--muted); margin: 0; text-
transform: uppercase; letter-spacing: .05em; }
.value { font-size: 1.8rem; font-weight: 700; margin: .25rem 0 0; }
.panel { background: #fff; border-radius: 12px; padding: 1.25rem;
margin-top: 1.5rem; }
table { width: 100%; border-collapse: collapse; }
th, td { text-align: left; padding: .6rem; border-bottom: 1px solid
var(--line); }
.badge { padding: .15rem .6rem; border-radius: 999px; font-size: .
8rem; font-weight: 600; }
.ok { background: #dcfce7; color: #166534; }
.wait { background: #fef9c3; color: #854d0e; }
```

Project 437 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - Dashboard</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cedar Furniture dashboard	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="stat"> Visitors today 1,284...	A self-contained piece: card, post, product.
<article class="stat"> Pieces sold 57 </...	Second-level heading for a section.

Line	What it does
<article class="stat"> Revenue <p class="value">18,450 EGP<//...	A paragraph of text.
<section class="panel">	A thematic group of content, normally with its own heading.
<table>	Tabular data in rows and columns.
<thead><tr><th>Order</th><th>Piece</th><th>Status</th></tr></thead>	Group of header rows.
<tbody>	Group of data rows.
<tr><td>#1041</td><td>Oak dining table</td><td><span class="badge o...	A table row.
<tr><td>#1040</td><td>Bookshelf</td><td>Pe...	A data cell.
<tr><td>#1039</td><td>Bedside table</td><td>...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.

Declaration	What it does
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
background: #f3f4f6;	Background colour or image.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
padding: 1.5rem 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(12rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 4px solid var(--brand);	A top border used as an accent or separator.
font-size: .85rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.

Declaration	What it does
font-weight: 700;	Thickness of the text.
border-radius: 12px;	The line around the element: width, style and colour.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
border-radius: 999px;	Fully rounded pill shape.

Check your work

- Stat labels are headings
- Table has header cells
- Badge colours pass contrast
- Cards wrap on phones

Exercises

1. Add a simple bar chart made of divs with widths in percent.
2. Add a sidebar navigation.
3. Add a dark theme with prefers-color-scheme.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f

Field	Value
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 438: Statistics dashboard for Byte Repair

Theme: Byte Repair (Nasr City) | Level 2 | Files: index.html, styles.css

Brief

Build an admin-style dashboard: four statistic cards with a coloured top border and a panel containing a recent-orders table with status badges.

Learning goals

- Present numbers in cards with small uppercase labels
- Create pill-shaped status badges
- Combine grid cards and a table

Elements and CSS used

HTML elements	CSS features
article, h2, p, section, table, thead, tbody, span	border-top, text-transform, letter-spacing, border-radius: 999px, grid auto-fit

Build guide

1. Write four .stat articles inside .stats.
2. Add the panel with a small table.
3. Wrap statuses in .
4. Grid the cards.
5. Style the badges as pills with soft background colours.
6. Give the page a light grey background so white panels stand out.

Project 438: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - Dashboard</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Byte Repair dashboard</h1>
    <div class="stats">
      <article class="stat"><h2>Visitors today</h2><p class="value">1,
284</p></article>
      <article class="stat"><h2>Repairs sold</h2><p class="value">57</
p></article>
      <article class="stat"><h2>Revenue</h2><p class="value">18,450
EGP</p></article>
      <article class="stat"><h2>Rating</h2><p class="value">4.8 / 5</
p></article>
    </div>
    <section class="panel">
      <h2>Recent orders</h2>
      <table>
        <thead><tr><th>Order</th><th>Repair</th><th>Status</th></tr></
thead>
        <tbody>
          <tr><td>#1041</td><td>Screen replacement</td><td><span
class="badge ok">Paid</span></td></tr>
          <tr><td>#1040</td><td>Battery swap</td><td><span
class="badge wait">Pending</span></td></tr>
          <tr><td>#1039</td><td>Laptop cleaning</td><td><span
class="badge ok">Paid</span></td></tr>
        </tbody>
      </table>
    </section>
  </main>
</body>
</html>
```

Project 438: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
body { background: #f3f4f6; }
main { max-width: 64rem; margin: 0 auto; padding: 1.5rem 1rem; }
.stats { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(12rem, 1fr)); }
.stat { background: #fff; padding: 1rem 1.25rem; border-radius: 12px;
border-top: 4px solid var(--brand); }
.stat h2 { font-size: .85rem; color: var(--muted); margin: 0; text-
transform: uppercase; letter-spacing: .05em; }
.value { font-size: 1.8rem; font-weight: 700; margin: .25rem 0 0; }
.panel { background: #fff; border-radius: 12px; padding: 1.25rem;
margin-top: 1.5rem; }
table { width: 100%; border-collapse: collapse; }
th, td { text-align: left; padding: .6rem; border-bottom: 1px solid
var(--line); }
.badge { padding: .15rem .6rem; border-radius: 999px; font-size: .
8rem; font-weight: 600; }
.ok { background: #dcfce7; color: #166534; }
.wait { background: #fef9c3; color: #854d0e; }
```

Project 438 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - Dashboard</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Byte Repair dashboard	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="stat"> Visitors today 1,284...	A self-contained piece: card, post, product.
<article class="stat"> Repairs sold 57 <...	Second-level heading for a section.

Line	What it does
<article class="stat"> Revenue <p class="value">18,450 EGP<//...	A paragraph of text.
<section class="panel">	A thematic group of content, normally with its own heading.
<table>	Tabular data in rows and columns.
<thead><tr><th>Order</th><th>Repair</th><th>Status</th></tr></thead>	Group of header rows.
<tbody>	Group of data rows.
<tr><td>#1041</td><td>Screen replacement</td><td><span class="badge...	A table row.
<tr><td>#1040</td><td>Battery swap</td><td><span class="badge wait"...	A data cell.
<tr><td>#1039</td><td>Laptop cleaning</td><td><span class="badge ok...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.

Declaration	What it does
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
background: #f3f4f6;	Background colour or image.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
padding: 1.5rem 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(12rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 4px solid var(--brand);	A top border used as an accent or separator.
font-size: .85rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.

Declaration	What it does
letter-spacing: .05em;	Adds space between letters; useful for small capitals.
font-weight: 700;	Thickness of the text.
border-radius: 12px;	The line around the element: width, style and colour.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
border-radius: 999px;	Fully rounded pill shape.

Check your work

- Stat labels are headings
- Table has header cells
- Badge colours pass contrast
- Cards wrap on phones

Exercises

1. Add a simple bar chart made of divs with widths in percent.
2. Add a sidebar navigation.
3. Add a dark theme with prefers-color-scheme.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City

Field	Value
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 439: Statistics dashboard for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 2 | Files: index.html, styles.css

Brief

Build an admin-style dashboard: four statistic cards with a coloured top border and a panel containing a recent-orders table with status badges.

Learning goals

- Present numbers in cards with small uppercase labels
- Create pill-shaped status badges
- Combine grid cards and a table

Elements and CSS used

HTML elements	CSS features
article, h2, p, section, table, thead, tbody, span	border-top, text-transform, letter-spacing, border-radius: 999px, grid auto-fit

Build guide

1. Write four .stat articles inside .stats.
2. Add the panel with a small table.
3. Wrap statuses in .
4. Grid the cards.
5. Style the badges as pills with soft background colours.
6. Give the page a light grey background so white panels stand out.

Project 439: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - Dashboard</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Sahara Pet Care dashboard</h1>
    <div class="stats">
      <article class="stat"><h2>Visitors today</h2><p class="value">1,
284</p></article>
      <article class="stat"><h2>Services sold</h2><p
class="value">57</p></article>
      <article class="stat"><h2>Revenue</h2><p class="value">18,450
EGP</p></article>
      <article class="stat"><h2>Rating</h2><p class="value">4.8 / 5</
p></article>
    </div>
    <section class="panel">
      <h2>Recent orders</h2>
      <table>
        <thead><tr><th>Order</th><th>Service</th><th>Status</th></
tr></thead>
        <tbody>
          <tr><td>#1041</td><td>Full grooming</td><td><span
class="badge ok">Paid</span></td></tr>
          <tr><td>#1040</td><td>Day boarding</td><td><span
class="badge wait">Pending</span></td></tr>
          <tr><td>#1039</td><td>Vaccination</td><td><span
class="badge ok">Paid</span></td></tr>
        </tbody>
      </table>
    </section>
  </main>
</body>
</html>
```

Project 439: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
body { background: #f3f4f6; }
main { max-width: 64rem; margin: 0 auto; padding: 1.5rem 1rem; }
.stats { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(12rem, 1fr)); }
.stat { background: #fff; padding: 1rem 1.25rem; border-radius: 12px;
border-top: 4px solid var(--brand); }
.stat h2 { font-size: .85rem; color: var(--muted); margin: 0; text-
transform: uppercase; letter-spacing: .05em; }
.value { font-size: 1.8rem; font-weight: 700; margin: .25rem 0 0; }
.panel { background: #fff; border-radius: 12px; padding: 1.25rem;
margin-top: 1.5rem; }
table { width: 100%; border-collapse: collapse; }
th, td { text-align: left; padding: .6rem; border-bottom: 1px solid
var(--line); }
.badge { padding: .15rem .6rem; border-radius: 999px; font-size: .
8rem; font-weight: 600; }
.ok { background: #dcfce7; color: #166534; }
.wait { background: #fef9c3; color: #854d0e; }
```

Project 439 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - Dashboard</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Sahara Pet Care dashboard	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="stat"> Visitors today 1,284...	A self-contained piece: card, post, product.
<article class="stat"> Services sold 57 ...	Second-level heading for a section.

Line	What it does
<article class="stat"> Revenue <p class="value">18,450 EGP<//...	A paragraph of text.
<section class="panel">	A thematic group of content, normally with its own heading.
<table>	Tabular data in rows and columns.
<thead><tr><th>Order</th><th>Service</th><th>Status</th></tr></thead>	Group of header rows.
<tbody>	Group of data rows.
<tr><td>#1041</td><td>Full grooming</td><td>...	A table row.
<tr><td>#1040</td><td>Day boarding</td><td><span class="badge wait"...	A data cell.
<tr><td>#1039</td><td>Vaccination</td><td>Pa...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.

Declaration	What it does
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
background: #f3f4f6;	Background colour or image.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
padding: 1.5rem 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(12rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 4px solid var(--brand);	A top border used as an accent or separator.
font-size: .85rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.

Declaration	What it does
font-weight: 700;	Thickness of the text.
border-radius: 12px;	The line around the element: width, style and colour.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
border-radius: 999px;	Fully rounded pill shape.

Check your work

- Stat labels are headings
- Table has header cells
- Badge colours pass contrast
- Cards wrap on phones

Exercises

1. Add a simple bar chart made of divs with widths in percent.
2. Add a sidebar navigation.
3. Add a dark theme with prefers-color-scheme.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c

Field	Value
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 440: Statistics dashboard for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Build an admin-style dashboard: four statistic cards with a coloured top border and a panel containing a recent-orders table with status badges.

Learning goals

- Present numbers in cards with small uppercase labels
- Create pill-shaped status badges
- Combine grid cards and a table

Elements and CSS used

HTML elements	CSS features
article, h2, p, section, table, thead, tbody, span	border-top, text-transform, letter-spacing, border-radius: 999px, grid auto-fit

Build guide

1. Write four .stat articles inside .stats.
2. Add the panel with a small table.
3. Wrap statuses in .
4. Grid the cards.
5. Style the badges as pills with soft background colours.

6. Give the page a light grey background so white panels stand out.

Project 440: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - Dashboard</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Alexandria Sailing School dashboard</h1>
    <div class="stats">
      <article class="stat"><h2>Visitors today</h2><p class="value">1,
284</p></article>
      <article class="stat"><h2>Lessons sold</h2><p class="value">57</
p></article>
      <article class="stat"><h2>Revenue</h2><p class="value">18,450
EGP</p></article>
      <article class="stat"><h2>Rating</h2><p class="value">4.8 / 5</
p></article>
    </div>
    <section class="panel">
      <h2>Recent orders</h2>
      <table>
        <thead><tr><th>Order</th><th>Lesson</th><th>Status</th></tr></
thead>
        <tbody>
          <tr><td>#1041</td><td>Taster session</td><td><span
class="badge ok">Paid</span></td></tr>
          <tr><td>#1040</td><td>Beginner course</td><td><span
class="badge wait">Pending</span></td></tr>
          <tr><td>#1039</td><td>Racing clinic</td><td><span
class="badge ok">Paid</span></td></tr>
        </tbody>
      </table>
    </section>
  </main>
</body>
</html>
```

Project 440: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
body { background: #f3f4f6; }
main { max-width: 64rem; margin: 0 auto; padding: 1.5rem 1rem; }
.stats { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(12rem, 1fr)); }
.stat { background: #fff; padding: 1rem 1.25rem; border-radius: 12px;
border-top: 4px solid var(--brand); }
.stat h2 { font-size: .85rem; color: var(--muted); margin: 0; text-
transform: uppercase; letter-spacing: .05em; }
.value { font-size: 1.8rem; font-weight: 700; margin: .25rem 0 0; }
.panel { background: #fff; border-radius: 12px; padding: 1.25rem;
margin-top: 1.5rem; }
table { width: 100%; border-collapse: collapse; }
th, td { text-align: left; padding: .6rem; border-bottom: 1px solid
var(--line); }
.badge { padding: .15rem .6rem; border-radius: 999px; font-size: .
8rem; font-weight: 600; }
.ok { background: #dcfce7; color: #166534; }
.wait { background: #fef9c3; color: #854d0e; }
```

Project 440 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - Dashboard</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Alexandria Sailing School dashboard	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="stat"> Visitors today 1,284...	A self-contained piece: card, post, product.
<article class="stat"> Lessons sold 57 <...	Second-level heading for a section.

Line	What it does
<article class="stat"> Revenue <p class="value">18,450 EGP<//...	A paragraph of text.
<section class="panel">	A thematic group of content, normally with its own heading.
<table>	Tabular data in rows and columns.
<thead><tr><th>Order</th><th>Lesson</th><th>Status</th></tr></thead>	Group of header rows.
<tbody>	Group of data rows.
<tr><td>#1041</td><td>Taster session</td><td><span class="badge ok"...	A table row.
<tr><td>#1040</td><td>Beginner course</td><td><span class="badge wa...	A data cell.
<tr><td>#1039</td><td>Racing clinic</td><td>...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.

Declaration	What it does
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
background: #f3f4f6;	Background colour or image.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
padding: 1.5rem 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(12rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 4px solid var(--brand);	A top border used as an accent or separator.
font-size: .85rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.

Declaration	What it does
font-weight: 700;	Thickness of the text.
border-radius: 12px;	The line around the element: width, style and colour.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
border-radius: 999px;	Fully rounded pill shape.

Check your work

- Stat labels are headings
- Table has header cells
- Badge colours pass contrast
- Cards wrap on phones

Exercises

1. Add a simple bar chart made of divs with widths in percent.
2. Add a sidebar navigation.
3. Add a dark theme with prefers-color-scheme.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af

Field	Value
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 441: Statistics dashboard for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Build an admin-style dashboard: four statistic cards with a coloured top border and a panel containing a recent-orders table with status badges.

Learning goals

- Present numbers in cards with small uppercase labels
- Create pill-shaped status badges
- Combine grid cards and a table

Elements and CSS used

HTML elements	CSS features
article, h2, p, section, table, thead, tbody, span	border-top, text-transform, letter-spacing, border-radius: 999px, grid auto-fit

Build guide

1. Write four .stat articles inside .stats.
2. Add the panel with a small table.
3. Wrap statuses in .
4. Grid the cards.
5. Style the badges as pills with soft background colours.

6. Give the page a light grey background so white panels stand out.

Project 441: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - Dashboard</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Habiba Handmade Jewellery dashboard</h1>
    <div class="stats">
      <article class="stat"><h2>Visitors today</h2><p class="value">1,
284</p></article>
      <article class="stat"><h2>Items sold</h2><p class="value">57</
p></article>
      <article class="stat"><h2>Revenue</h2><p class="value">18,450
EGP</p></article>
      <article class="stat"><h2>Rating</h2><p class="value">4.8 / 5</
p></article>
    </div>
    <section class="panel">
      <h2>Recent orders</h2>
      <table>
        <thead><tr><th>Order</th><th>Item</th><th>Status</th></tr></
thead>
        <tbody>
          <tr><td>#1041</td><td>Lotus pendant</td><td><span
class="badge ok">Paid</span></td></tr>
          <tr><td>#1040</td><td>Brass cuff</td><td><span class="badge
wait">Pending</span></td></tr>
          <tr><td>#1039</td><td>Bead earrings</td><td><span
class="badge ok">Paid</span></td></tr>
        </tbody>
      </table>
    </section>
  </main>
</body>
</html>
```

Project 441: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
body { background: #f3f4f6; }
main { max-width: 64rem; margin: 0 auto; padding: 1.5rem 1rem; }
.stats { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(12rem, 1fr)); }
.stat { background: #fff; padding: 1rem 1.25rem; border-radius: 12px;
border-top: 4px solid var(--brand); }
.stat h2 { font-size: .85rem; color: var(--muted); margin: 0; text-
transform: uppercase; letter-spacing: .05em; }
.value { font-size: 1.8rem; font-weight: 700; margin: .25rem 0 0; }
.panel { background: #fff; border-radius: 12px; padding: 1.25rem;
margin-top: 1.5rem; }
table { width: 100%; border-collapse: collapse; }
th, td { text-align: left; padding: .6rem; border-bottom: 1px solid
var(--line); }
.badge { padding: .15rem .6rem; border-radius: 999px; font-size: .
8rem; font-weight: 600; }
.ok { background: #dcfce7; color: #166534; }
.wait { background: #fef9c3; color: #854d0e; }
```

Project 441 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - Dashboard</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Habiba Handmade Jewellery dashboard	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="stat"> Visitors today 1,284...	A self-contained piece: card, post, product.
<article class="stat"> Items sold 57 </a...	Second-level heading for a section.

Line	What it does
<article class="stat"> Revenue <p class="value">18,450 EGP<//...	A paragraph of text.
<section class="panel">	A thematic group of content, normally with its own heading.
<table>	Tabular data in rows and columns.
<thead><tr><th>Order</th><th>Item</th><th>Status</th></tr></thead>	Group of header rows.
<tbody>	Group of data rows.
<tr><td>#1041</td><td>Lotus pendant</td><td>...	A table row.
<tr><td>#1040</td><td>Brass cuff</td><td>P...	A data cell.
<tr><td>#1039</td><td>Bead earrings</td><td>...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.

Declaration	What it does
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
background: #f3f4f6;	Background colour or image.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
padding: 1.5rem 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(12rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 4px solid var(--brand);	A top border used as an accent or separator.
font-size: .85rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.

Declaration	What it does
font-weight: 700;	Thickness of the text.
border-radius: 12px;	The line around the element: width, style and colour.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
border-radius: 999px;	Fully rounded pill shape.

Check your work

- Stat labels are headings
- Table has header cells
- Badge colours pass contrast
- Cards wrap on phones

Exercises

1. Add a simple bar chart made of divs with widths in percent.
2. Add a sidebar navigation.
3. Add a dark theme with prefers-color-scheme.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207

Field	Value
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 442: Statistics dashboard for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 2 | Files: index.html, styles.css

Brief

Build an admin-style dashboard: four statistic cards with a coloured top border and a panel containing a recent-orders table with status badges.

Learning goals

- Present numbers in cards with small uppercase labels
- Create pill-shaped status badges
- Combine grid cards and a table

Elements and CSS used

HTML elements	CSS features
article, h2, p, section, table, thead, tbody, span	border-top, text-transform, letter-spacing, border-radius: 999px, grid auto-fit

Build guide

1. Write four .stat articles inside .stats.
2. Add the panel with a small table.
3. Wrap statuses in .
4. Grid the cards.
5. Style the badges as pills with soft background colours.

6. Give the page a light grey background so white panels stand out.

Project 442: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - Dashboard</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Fayoum Pottery Studio dashboard</h1>
    <div class="stats">
      <article class="stat"><h2>Visitors today</h2><p class="value">1,
284</p></article>
      <article class="stat"><h2>Workshops sold</h2><p
class="value">57</p></article>
      <article class="stat"><h2>Revenue</h2><p class="value">18,450
EGP</p></article>
      <article class="stat"><h2>Rating</h2><p class="value">4.8 / 5</
p></article>
    </div>
    <section class="panel">
      <h2>Recent orders</h2>
      <table>
        <thead><tr><th>Order</th><th>Workshop</th><th>Status</th></
tr></thead>
        <tbody>
          <tr><td>#1041</td><td>Intro to the wheel</td><td><span
class="badge ok">Paid</span></td></tr>
          <tr><td>#1040</td><td>Glazing day</td><td><span
class="badge wait">Pending</span></td></tr>
          <tr><td>#1039</td><td>Kids clay class</td><td><span
class="badge ok">Paid</span></td></tr>
        </tbody>
      </table>
    </section>
  </main>
</body>
</html>
```

Project 442: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
body { background: #f3f4f6; }
main { max-width: 64rem; margin: 0 auto; padding: 1.5rem 1rem; }
.stats { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(12rem, 1fr)); }
.stat { background: #fff; padding: 1rem 1.25rem; border-radius: 12px;
border-top: 4px solid var(--brand); }
.stat h2 { font-size: .85rem; color: var(--muted); margin: 0; text-
transform: uppercase; letter-spacing: .05em; }
.value { font-size: 1.8rem; font-weight: 700; margin: .25rem 0 0; }
.panel { background: #fff; border-radius: 12px; padding: 1.25rem;
margin-top: 1.5rem; }
table { width: 100%; border-collapse: collapse; }
th, td { text-align: left; padding: .6rem; border-bottom: 1px solid
var(--line); }
.badge { padding: .15rem .6rem; border-radius: 999px; font-size: .
8rem; font-weight: 600; }
.ok { background: #dcfce7; color: #166534; }
.wait { background: #fef9c3; color: #854d0e; }
```

Project 442 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - Dashboard</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Fayoum Pottery Studio dashboard	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="stat"> Visitors today <p class="value">1,284...	A self-contained piece: card, post, product.
<article class="stat"> Workshops sold <p class="value">57</p...	Second-level heading for a section.

Line	What it does
<article class="stat"> Revenue <p class="value">18,450 EGP<//...	A paragraph of text.
<section class="panel">	A thematic group of content, normally with its own heading.
<table>	Tabular data in rows and columns.
<thead><tr><th>Order</th><th>Workshop</th><th>Status</th></tr></thead>	Group of header rows.
<tbody>	Group of data rows.
<tr><td>#1041</td><td>Intro to the wheel</td><td><span class="badge...	A table row.
<tr><td>#1040</td><td>Glazing day</td><td>...	A data cell.
<tr><td>#1039</td><td>Kids clay class</td><td><span class="badge ok...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.

Declaration	What it does
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
background: #f3f4f6;	Background colour or image.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
padding: 1.5rem 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(12rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 4px solid var(--brand);	A top border used as an accent or separator.
font-size: .85rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.

Declaration	What it does
font-weight: 700;	Thickness of the text.
border-radius: 12px;	The line around the element: width, style and colour.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
border-radius: 999px;	Fully rounded pill shape.

Check your work

- Stat labels are headings
- Table has header cells
- Badge colours pass contrast
- Cards wrap on phones

Exercises

1. Add a simple bar chart made of divs with widths in percent.
2. Add a sidebar navigation.
3. Add a dark theme with prefers-color-scheme.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412

Field	Value
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 443: Statistics dashboard for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 2 | Files: index.html, styles.css

Brief

Build an admin-style dashboard: four statistic cards with a coloured top border and a panel containing a recent-orders table with status badges.

Learning goals

- Present numbers in cards with small uppercase labels
- Create pill-shaped status badges
- Combine grid cards and a table

Elements and CSS used

HTML elements	CSS features
article, h2, p, section, table, thead, tbody, span	border-top, text-transform, letter-spacing, border-radius: 999px, grid auto-fit

Build guide

1. Write four .stat articles inside .stats.
2. Add the panel with a small table.
3. Wrap statuses in .
4. Grid the cards.
5. Style the badges as pills with soft background colours.

6. Give the page a light grey background so white panels stand out.

Project 443: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - Dashboard</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cleopatra Beauty Salon dashboard</h1>
    <div class="stats">
      <article class="stat"><h2>Visitors today</h2><p class="value">1,
284</p></article>
      <article class="stat"><h2>Treatments sold</h2><p
class="value">57</p></article>
      <article class="stat"><h2>Revenue</h2><p class="value">18,450
EGP</p></article>
      <article class="stat"><h2>Rating</h2><p class="value">4.8 / 5</
p></article>
    </div>
    <section class="panel">
      <h2>Recent orders</h2>
      <table>
        <thead><tr><th>Order</th><th>Treatment</th><th>Status</th></
tr></thead>
        <tbody>
          <tr><td>#1041</td><td>Haircut and blow-dry</td><td><span
class="badge ok">Paid</span></td></tr>
          <tr><td>#1040</td><td>Manicure</td><td><span class="badge
wait">Pending</span></td></tr>
          <tr><td>#1039</td><td>Facial</td><td><span class="badge
ok">Paid</span></td></tr>
        </tbody>
      </table>
    </section>
  </main>
</body>
</html>
```

Project 443: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
body { background: #f3f4f6; }
main { max-width: 64rem; margin: 0 auto; padding: 1.5rem 1rem; }
.stats { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(12rem, 1fr)); }
.stat { background: #fff; padding: 1rem 1.25rem; border-radius: 12px;
border-top: 4px solid var(--brand); }
.stat h2 { font-size: .85rem; color: var(--muted); margin: 0; text-
transform: uppercase; letter-spacing: .05em; }
.value { font-size: 1.8rem; font-weight: 700; margin: .25rem 0 0; }
.panel { background: #fff; border-radius: 12px; padding: 1.25rem;
margin-top: 1.5rem; }
table { width: 100%; border-collapse: collapse; }
th, td { text-align: left; padding: .6rem; border-bottom: 1px solid
var(--line); }
.badge { padding: .15rem .6rem; border-radius: 999px; font-size: .
8rem; font-weight: 600; }
.ok { background: #dcfce7; color: #166534; }
.wait { background: #fef9c3; color: #854d0e; }
```

Project 443 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - Dashboard</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cleopatra Beauty Salon dashboard	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="stat"> Visitors today <p class="value">1,284...	A self-contained piece: card, post, product.
<article class="stat"> Treatments sold <p class="value">57<//...	Second-level heading for a section.

Line	What it does
<article class="stat"> Revenue <p class="value">18,450 EGP<//...	A paragraph of text.
<section class="panel">	A thematic group of content, normally with its own heading.
<table>	Tabular data in rows and columns.
<thead><tr><th>Order</th><th>Treatment</th><th>Status</th></tr></th...	Group of header rows.
<tbody>	Group of data rows.
<tr><td>#1041</td><td>Haircut and blow-dry</td><td><span class="bad...	A table row.
<tr><td>#1040</td><td>Manicure</td><td>Pen...	A data cell.
<tr><td>#1039</td><td>Facial</td><td>Paid</s...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.

Declaration	What it does
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
background: #f3f4f6;	Background colour or image.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
padding: 1.5rem 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(12rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 4px solid var(--brand);	A top border used as an accent or separator.
font-size: .85rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.

Declaration	What it does
font-weight: 700;	Thickness of the text.
border-radius: 12px;	The line around the element: width, style and colour.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
border-radius: 999px;	Fully rounded pill shape.

Check your work

- Stat labels are headings
- Table has header cells
- Badge colours pass contrast
- Cards wrap on phones

Exercises

1. Add a simple bar chart made of divs with widths in percent.
2. Add a sidebar navigation.
3. Add a dark theme with prefers-color-scheme.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777

Field	Value
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 444: Statistics dashboard for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 2 | Files: index.html, styles.css

Brief

Build an admin-style dashboard: four statistic cards with a coloured top border and a panel containing a recent-orders table with status badges.

Learning goals

- Present numbers in cards with small uppercase labels
- Create pill-shaped status badges
- Combine grid cards and a table

Elements and CSS used

HTML elements	CSS features
article, h2, p, section, table, thead, tbody, span	border-top, text-transform, letter-spacing, border-radius: 999px, grid auto-fit

Build guide

1. Write four .stat articles inside .stats.
2. Add the panel with a small table.
3. Wrap statuses in .
4. Grid the cards.
5. Style the badges as pills with soft background colours.
6. Give the page a light grey background so white panels stand out.

Project 444: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - Dashboard</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Suez Auto Service dashboard</h1>
    <div class="stats">
      <article class="stat"><h2>Visitors today</h2><p class="value">1,
284</p></article>
      <article class="stat"><h2>Services sold</h2><p
class="value">57</p></article>
      <article class="stat"><h2>Revenue</h2><p class="value">18,450
EGP</p></article>
      <article class="stat"><h2>Rating</h2><p class="value">4.8 / 5</
p></article>
    </div>
    <section class="panel">
      <h2>Recent orders</h2>
      <table>
        <thead><tr><th>Order</th><th>Service</th><th>Status</th></
tr></thead>
        <tbody>
          <tr><td>#1041</td><td>Oil change</td><td><span class="badge
ok">Paid</span></td></tr>
          <tr><td>#1040</td><td>Brake pads</td><td><span class="badge
wait">Pending</span></td></tr>
          <tr><td>#1039</td><td>Air conditioning</td><td><span
class="badge ok">Paid</span></td></tr>
        </tbody>
      </table>
    </section>
  </main>
</body>
</html>
```

Project 444: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
body { background: #f3f4f6; }
main { max-width: 64rem; margin: 0 auto; padding: 1.5rem 1rem; }
.stats { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(12rem, 1fr)); }
.stat { background: #fff; padding: 1rem 1.25rem; border-radius: 12px;
border-top: 4px solid var(--brand); }
.stat h2 { font-size: .85rem; color: var(--muted); margin: 0; text-
transform: uppercase; letter-spacing: .05em; }
.value { font-size: 1.8rem; font-weight: 700; margin: .25rem 0 0; }
.panel { background: #fff; border-radius: 12px; padding: 1.25rem;
margin-top: 1.5rem; }
table { width: 100%; border-collapse: collapse; }
th, td { text-align: left; padding: .6rem; border-bottom: 1px solid
var(--line); }
.badge { padding: .15rem .6rem; border-radius: 999px; font-size: .
8rem; font-weight: 600; }
.ok { background: #dcfce7; color: #166534; }
.wait { background: #fef9c3; color: #854d0e; }
```

Project 444 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - Dashboard</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Suez Auto Service dashboard	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="stat"> Visitors today 1,284...	A self-contained piece: card, post, product.
<article class="stat"> Services sold 57 ...	Second-level heading for a section.

Line	What it does
<article class="stat"> Revenue <p class="value">18,450 EGP<//...	A paragraph of text.
<section class="panel">	A thematic group of content, normally with its own heading.
<table>	Tabular data in rows and columns.
<thead><tr><th>Order</th><th>Service</th><th>Status</th></tr></thead>	Group of header rows.
<tbody>	Group of data rows.
<tr><td>#1041</td><td>Oil change</td><td>Pai...	A table row.
<tr><td>#1040</td><td>Brake pads</td><td>P...	A data cell.
<tr><td>#1039</td><td>Air conditioning</td><td><span class="badge o...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.

Declaration	What it does
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
background: #f3f4f6;	Background colour or image.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
padding: 1.5rem 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(12rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 4px solid var(--brand);	A top border used as an accent or separator.
font-size: .85rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.

Declaration	What it does
font-weight: 700;	Thickness of the text.
border-radius: 12px;	The line around the element: width, style and colour.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
border-radius: 999px;	Fully rounded pill shape.

Check your work

- Stat labels are headings
- Table has header cells
- Badge colours pass contrast
- Cards wrap on phones

Exercises

1. Add a simple bar chart made of divs with widths in percent.
2. Add a sidebar navigation.
3. Add a dark theme with prefers-color-scheme.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151

Field	Value
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 445: Statistics dashboard for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 2 | Files: index.html, styles.css

Brief

Build an admin-style dashboard: four statistic cards with a coloured top border and a panel containing a recent-orders table with status badges.

Learning goals

- Present numbers in cards with small uppercase labels
- Create pill-shaped status badges
- Combine grid cards and a table

Elements and CSS used

HTML elements	CSS features
article, h2, p, section, table, thead, tbody, span	border-top, text-transform, letter-spacing, border-radius: 999px, grid auto-fit

Build guide

1. Write four .stat articles inside .stats.
2. Add the panel with a small table.
3. Wrap statuses in .
4. Grid the cards.
5. Style the badges as pills with soft background colours.
6. Give the page a light grey background so white panels stand out.

Project 445: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - Dashboard</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Luxor Music Academy dashboard</h1>
    <div class="stats">
      <article class="stat"><h2>Visitors today</h2><p class="value">1,
284</p></article>
      <article class="stat"><h2>Courses sold</h2><p class="value">57</
p></article>
      <article class="stat"><h2>Revenue</h2><p class="value">18,450
EGP</p></article>
      <article class="stat"><h2>Rating</h2><p class="value">4.8 / 5</
p></article>
    </div>
    <section class="panel">
      <h2>Recent orders</h2>
      <table>
        <thead><tr><th>Order</th><th>Course</th><th>Status</th></tr></
thead>
        <tbody>
          <tr><td>#1041</td><td>Oud for beginners</td><td><span
class="badge ok">Paid</span></td></tr>
          <tr><td>#1040</td><td>Piano grade 1</td><td><span
class="badge wait">Pending</span></td></tr>
          <tr><td>#1039</td><td>Guitar chords</td><td><span
class="badge ok">Paid</span></td></tr>
        </tbody>
      </table>
    </section>
  </main>
</body>
</html>
```

Project 445: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
body { background: #f3f4f6; }
main { max-width: 64rem; margin: 0 auto; padding: 1.5rem 1rem; }
.stats { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(12rem, 1fr)); }
.stat { background: #fff; padding: 1rem 1.25rem; border-radius: 12px;
border-top: 4px solid var(--brand); }
.stat h2 { font-size: .85rem; color: var(--muted); margin: 0; text-
transform: uppercase; letter-spacing: .05em; }
.value { font-size: 1.8rem; font-weight: 700; margin: .25rem 0 0; }
.panel { background: #fff; border-radius: 12px; padding: 1.25rem;
margin-top: 1.5rem; }
table { width: 100%; border-collapse: collapse; }
th, td { text-align: left; padding: .6rem; border-bottom: 1px solid
var(--line); }
.badge { padding: .15rem .6rem; border-radius: 999px; font-size: .
8rem; font-weight: 600; }
.ok { background: #dcfce7; color: #166534; }
.wait { background: #fef9c3; color: #854d0e; }
```

Project 445 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - Dashboard</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Luxor Music Academy dashboard	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="stat"> Visitors today 1,284...	A self-contained piece: card, post, product.
<article class="stat"> Courses sold 57 <...	Second-level heading for a section.

Line	What it does
<article class="stat"> Revenue <p class="value">18,450 EGP<//...	A paragraph of text.
<section class="panel">	A thematic group of content, normally with its own heading.
<table>	Tabular data in rows and columns.
<thead><tr><th>Order</th><th>Course</th><th>Status</th></tr></thead>	Group of header rows.
<tbody>	Group of data rows.
<tr><td>#1041</td><td>Oud for beginners</td><td><span class="badge ...	A table row.
<tr><td>#1040</td><td>Piano grade 1</td><td><span class="badge wait...	A data cell.
<tr><td>#1039</td><td>Guitar chords</td><td>...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.

Declaration	What it does
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
background: #f3f4f6;	Background colour or image.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
padding: 1.5rem 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(12rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 4px solid var(--brand);	A top border used as an accent or separator.
font-size: .85rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.

Declaration	What it does
font-weight: 700;	Thickness of the text.
border-radius: 12px;	The line around the element: width, style and colour.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
border-radius: 999px;	Fully rounded pill shape.

Check your work

- Stat labels are headings
- Table has header cells
- Badge colours pass contrast
- Cards wrap on phones

Exercises

1. Add a simple bar chart made of divs with widths in percent.
2. Add a sidebar navigation.
3. Add a dark theme with prefers-color-scheme.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95

Field	Value
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 446: Statistics dashboard for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 2 | Files: index.html, styles.css

Brief

Build an admin-style dashboard: four statistic cards with a coloured top border and a panel containing a recent-orders table with status badges.

Learning goals

- Present numbers in cards with small uppercase labels
- Create pill-shaped status badges
- Combine grid cards and a table

Elements and CSS used

HTML elements	CSS features
article, h2, p, section, table, thead, tbody, span	border-top, text-transform, letter-spacing, border-radius: 999px, grid auto-fit

Build guide

1. Write four .stat articles inside .stats.
2. Add the panel with a small table.
3. Wrap statuses in .
4. Grid the cards.
5. Style the badges as pills with soft background colours.
6. Give the page a light grey background so white panels stand out.

Project 446: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - Dashboard</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Port Said Seafood dashboard</h1>
    <div class="stats">
      <article class="stat"><h2>Visitors today</h2><p class="value">1,
284</p></article>
      <article class="stat"><h2>Dishes sold</h2><p class="value">57</
p></article>
      <article class="stat"><h2>Revenue</h2><p class="value">18,450
EGP</p></article>
      <article class="stat"><h2>Rating</h2><p class="value">4.8 / 5</
p></article>
    </div>
    <section class="panel">
      <h2>Recent orders</h2>
      <table>
        <thead><tr><th>Order</th><th>Dish</th><th>Status</th></tr></
thead>
        <tbody>
          <tr><td>#1041</td><td>Grilled sea bass</td><td><span
class="badge ok">Paid</span></td></tr>
          <tr><td>#1040</td><td>Shrimp tagine</td><td><span
class="badge wait">Pending</span></td></tr>
          <tr><td>#1039</td><td>Calamari</td><td><span class="badge
ok">Paid</span></td></tr>
        </tbody>
      </table>
    </section>
  </main>
</body>
</html>
```

Project 446: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
body { background: #f3f4f6; }
main { max-width: 64rem; margin: 0 auto; padding: 1.5rem 1rem; }
.stats { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(12rem, 1fr)); }
.stat { background: #fff; padding: 1rem 1.25rem; border-radius: 12px;
border-top: 4px solid var(--brand); }
.stat h2 { font-size: .85rem; color: var(--muted); margin: 0; text-
transform: uppercase; letter-spacing: .05em; }
.value { font-size: 1.8rem; font-weight: 700; margin: .25rem 0 0; }
.panel { background: #fff; border-radius: 12px; padding: 1.25rem;
margin-top: 1.5rem; }
table { width: 100%; border-collapse: collapse; }
th, td { text-align: left; padding: .6rem; border-bottom: 1px solid
var(--line); }
.badge { padding: .15rem .6rem; border-radius: 999px; font-size: .
8rem; font-weight: 600; }
.ok { background: #dcfce7; color: #166534; }
.wait { background: #fef9c3; color: #854d0e; }
```

Project 446 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - Dashboard</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Port Said Seafood dashboard	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="stat"> Visitors today 1,284...	A self-contained piece: card, post, product.
<article class="stat"> Dishes sold 57 </...	Second-level heading for a section.

Line	What it does
<article class="stat"> Revenue <p class="value">18,450 EGP<//...	A paragraph of text.
<section class="panel">	A thematic group of content, normally with its own heading.
<table>	Tabular data in rows and columns.
<thead><tr><th>Order</th><th>Dish</th><th>Status</th></tr></thead>	Group of header rows.
<tbody>	Group of data rows.
<tr><td>#1041</td><td>Grilled sea bass</td><td><span class="badge o...	A table row.
<tr><td>#1040</td><td>Shrimp tagine</td><td><span class="badge wait...	A data cell.
<tr><td>#1039</td><td>Calamari</td><td>Paid<...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.

Declaration	What it does
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
background: #f3f4f6;	Background colour or image.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
padding: 1.5rem 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(12rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 4px solid var(--brand);	A top border used as an accent or separator.
font-size: .85rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.

Declaration	What it does
font-weight: 700;	Thickness of the text.
border-radius: 12px;	The line around the element: width, style and colour.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
border-radius: 999px;	Fully rounded pill shape.

Check your work

- Stat labels are headings
- Table has header cells
- Badge colours pass contrast
- Cards wrap on phones

Exercises

1. Add a simple bar chart made of divs with widths in percent.
2. Add a sidebar navigation.
3. Add a dark theme with prefers-color-scheme.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490

Field	Value
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 447: Statistics dashboard for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 2 | Files: index.html, styles.css

Brief

Build an admin-style dashboard: four statistic cards with a coloured top border and a panel containing a recent-orders table with status badges.

Learning goals

- Present numbers in cards with small uppercase labels
- Create pill-shaped status badges
- Combine grid cards and a table

Elements and CSS used

HTML elements	CSS features
article, h2, p, section, table, thead, tbody, span	border-top, text-transform, letter-spacing, border-radius: 999px, grid auto-fit

Build guide

1. Write four .stat articles inside .stats.
2. Add the panel with a small table.
3. Wrap statuses in .
4. Grid the cards.
5. Style the badges as pills with soft background colours.
6. Give the page a light grey background so white panels stand out.

Project 447: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - Dashboard</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Delta Kids Library dashboard</h1>
    <div class="stats">
      <article class="stat"><h2>Visitors today</h2><p class="value">1,
284</p></article>
      <article class="stat"><h2>Programmes sold</h2><p
class="value">57</p></article>
      <article class="stat"><h2>Revenue</h2><p class="value">18,450
EGP</p></article>
      <article class="stat"><h2>Rating</h2><p class="value">4.8 / 5</
p></article>
    </div>
    <section class="panel">
      <h2>Recent orders</h2>
      <table>
        <thead><tr><th>Order</th><th>Programme</th><th>Status</th></
tr></thead>
        <tbody>
          <tr><td>#1041</td><td>Story hour</td><td><span class="badge
ok">Paid</span></td></tr>
          <tr><td>#1040</td><td>Reading club</td><td><span
class="badge wait">Pending</span></td></tr>
          <tr><td>#1039</td><td>Homework help</td><td><span
class="badge ok">Paid</span></td></tr>
        </tbody>
      </table>
    </section>
  </main>
</body>
</html>
```

Project 447: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
body { background: #f3f4f6; }
main { max-width: 64rem; margin: 0 auto; padding: 1.5rem 1rem; }
.stats { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(12rem, 1fr)); }
.stat { background: #fff; padding: 1rem 1.25rem; border-radius: 12px;
border-top: 4px solid var(--brand); }
.stat h2 { font-size: .85rem; color: var(--muted); margin: 0; text-
transform: uppercase; letter-spacing: .05em; }
.value { font-size: 1.8rem; font-weight: 700; margin: .25rem 0 0; }
.panel { background: #fff; border-radius: 12px; padding: 1.25rem;
margin-top: 1.5rem; }
table { width: 100%; border-collapse: collapse; }
th, td { text-align: left; padding: .6rem; border-bottom: 1px solid
var(--line); }
.badge { padding: .15rem .6rem; border-radius: 999px; font-size: .
8rem; font-weight: 600; }
.ok { background: #dcfce7; color: #166534; }
.wait { background: #fef9c3; color: #854d0e; }
```

Project 447 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - Dashboard</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Delta Kids Library dashboard	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="stat"> Visitors today <p class="value">1,284...	A self-contained piece: card, post, product.
<article class="stat"> Programmes sold <p class="value">57<//...	Second-level heading for a section.

Line	What it does
<article class="stat"> Revenue <p class="value">18,450 EGP<//...	A paragraph of text.
<section class="panel">	A thematic group of content, normally with its own heading.
<table>	Tabular data in rows and columns.
<thead><tr><th>Order</th><th>Programme</th><th>Status</th></tr></th...	Group of header rows.
<tbody>	Group of data rows.
<tr><td>#1041</td><td>Story hour</td><td>Pai...	A table row.
<tr><td>#1040</td><td>Reading club</td><td><span class="badge wait"...	A data cell.
<tr><td>#1039</td><td>Homework help</td><td>...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.

Declaration	What it does
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
background: #f3f4f6;	Background colour or image.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
padding: 1.5rem 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(12rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 4px solid var(--brand);	A top border used as an accent or separator.
font-size: .85rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.

Declaration	What it does
font-weight: 700;	Thickness of the text.
border-radius: 12px;	The line around the element: width, style and colour.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
border-radius: 999px;	Fully rounded pill shape.

Check your work

- Stat labels are headings
- Table has header cells
- Badge colours pass contrast
- Cards wrap on phones

Exercises

1. Add a simple bar chart made of divs with widths in percent.
2. Add a sidebar navigation.
3. Add a dark theme with prefers-color-scheme.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c

Field	Value
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 448: Statistics dashboard for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Build an admin-style dashboard: four statistic cards with a coloured top border and a panel containing a recent-orders table with status badges.

Learning goals

- Present numbers in cards with small uppercase labels
- Create pill-shaped status badges
- Combine grid cards and a table

Elements and CSS used

HTML elements	CSS features
article, h2, p, section, table, thead, tbody, span	border-top, text-transform, letter-spacing, border-radius: 999px, grid auto-fit

Build guide

1. Write four .stat articles inside .stats.
2. Add the panel with a small table.
3. Wrap statuses in .
4. Grid the cards.
5. Style the badges as pills with soft background colours.
6. Give the page a light grey background so white panels stand out.

Project 448: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - Dashboard</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Nubian Guest House dashboard</h1>
    <div class="stats">
      <article class="stat"><h2>Visitors today</h2><p class="value">1,
284</p></article>
      <article class="stat"><h2>Rooms sold</h2><p class="value">57</
p></article>
      <article class="stat"><h2>Revenue</h2><p class="value">18,450
EGP</p></article>
      <article class="stat"><h2>Rating</h2><p class="value">4.8 / 5</
p></article>
    </div>
    <section class="panel">
      <h2>Recent orders</h2>
      <table>
        <thead><tr><th>Order</th><th>Room</th><th>Status</th></tr></
thead>
        <tbody>
          <tr><td>#1041</td><td>Garden room</td><td><span
class="badge ok">Paid</span></td></tr>
          <tr><td>#1040</td><td>Nile view suite</td><td><span
class="badge wait">Pending</span></td></tr>
          <tr><td>#1039</td><td>Family room</td><td><span
class="badge ok">Paid</span></td></tr>
        </tbody>
      </table>
    </section>
  </main>
</body>
</html>
```

Project 448: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
body { background: #f3f4f6; }
main { max-width: 64rem; margin: 0 auto; padding: 1.5rem 1rem; }
.stats { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(12rem, 1fr)); }
.stat { background: #fff; padding: 1rem 1.25rem; border-radius: 12px;
border-top: 4px solid var(--brand); }
.stat h2 { font-size: .85rem; color: var(--muted); margin: 0; text-
transform: uppercase; letter-spacing: .05em; }
.value { font-size: 1.8rem; font-weight: 700; margin: .25rem 0 0; }
.panel { background: #fff; border-radius: 12px; padding: 1.25rem;
margin-top: 1.5rem; }
table { width: 100%; border-collapse: collapse; }
th, td { text-align: left; padding: .6rem; border-bottom: 1px solid
var(--line); }
.badge { padding: .15rem .6rem; border-radius: 999px; font-size: .
8rem; font-weight: 600; }
.ok { background: #dcfce7; color: #166534; }
.wait { background: #fef9c3; color: #854d0e; }
```

Project 448 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - Dashboard</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Nubian Guest House dashboard	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="stat"> Visitors today 1,284...	A self-contained piece: card, post, product.
<article class="stat"> Rooms sold 57 </a...	Second-level heading for a section.

Line	What it does
<article class="stat"> Revenue <p class="value">18,450 EGP<//...	A paragraph of text.
<section class="panel">	A thematic group of content, normally with its own heading.
<table>	Tabular data in rows and columns.
<thead><tr><th>Order</th><th>Room</th><th>Status</th></tr></thead>	Group of header rows.
<tbody>	Group of data rows.
<tr><td>#1041</td><td>Garden room</td><td>Pa...	A table row.
<tr><td>#1040</td><td>Nile view suite</td><td><span class="badge wa...	A data cell.
<tr><td>#1039</td><td>Family room</td><td>Pa...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.

Declaration	What it does
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
background: #f3f4f6;	Background colour or image.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
padding: 1.5rem 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(12rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 4px solid var(--brand);	A top border used as an accent or separator.
font-size: .85rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.

Declaration	What it does
font-weight: 700;	Thickness of the text.
border-radius: 12px;	The line around the element: width, style and colour.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
border-radius: 999px;	Fully rounded pill shape.

Check your work

- Stat labels are headings
- Table has header cells
- Badge colours pass contrast
- Cards wrap on phones

Exercises

1. Add a simple bar chart made of divs with widths in percent.
2. Add a sidebar navigation.
3. Add a dark theme with prefers-color-scheme.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309

Field	Value
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 449: Statistics dashboard for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 2 | Files: index.html, styles.css

Brief

Build an admin-style dashboard: four statistic cards with a coloured top border and a panel containing a recent-orders table with status badges.

Learning goals

- Present numbers in cards with small uppercase labels
- Create pill-shaped status badges
- Combine grid cards and a table

Elements and CSS used

HTML elements	CSS features
article, h2, p, section, table, thead, tbody, span	border-top, text-transform, letter-spacing, border-radius: 999px, grid auto-fit

Build guide

1. Write four .stat articles inside .stats.
2. Add the panel with a small table.
3. Wrap statuses in .
4. Grid the cards.
5. Style the badges as pills with soft background colours.

6. Give the page a light grey background so white panels stand out.

Project 449: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - Dashboard</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Ismailia Cycling Store dashboard</h1>
    <div class="stats">
      <article class="stat"><h2>Visitors today</h2><p class="value">1,
284</p></article>
      <article class="stat"><h2>Bikes sold</h2><p class="value">57</
p></article>
      <article class="stat"><h2>Revenue</h2><p class="value">18,450
EGP</p></article>
      <article class="stat"><h2>Rating</h2><p class="value">4.8 / 5</
p></article>
    </div>
    <section class="panel">
      <h2>Recent orders</h2>
      <table>
        <thead><tr><th>Order</th><th>Bike</th><th>Status</th></tr></
thead>
        <tbody>
          <tr><td>#1041</td><td>City bike</td><td><span class="badge
ok">Paid</span></td></tr>
          <tr><td>#1040</td><td>Mountain bike</td><td><span
class="badge wait">Pending</span></td></tr>
          <tr><td>#1039</td><td>Kids bike</td><td><span class="badge
ok">Paid</span></td></tr>
        </tbody>
      </table>
    </section>
  </main>
</body>
</html>
```

Project 449: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
body { background: #f3f4f6; }
main { max-width: 64rem; margin: 0 auto; padding: 1.5rem 1rem; }
.stats { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(12rem, 1fr)); }
.stat { background: #fff; padding: 1rem 1.25rem; border-radius: 12px;
border-top: 4px solid var(--brand); }
.stat h2 { font-size: .85rem; color: var(--muted); margin: 0; text-
transform: uppercase; letter-spacing: .05em; }
.value { font-size: 1.8rem; font-weight: 700; margin: .25rem 0 0; }
.panel { background: #fff; border-radius: 12px; padding: 1.25rem;
margin-top: 1.5rem; }
table { width: 100%; border-collapse: collapse; }
th, td { text-align: left; padding: .6rem; border-bottom: 1px solid
var(--line); }
.badge { padding: .15rem .6rem; border-radius: 999px; font-size: .
8rem; font-weight: 600; }
.ok { background: #dcfce7; color: #166534; }
.wait { background: #fef9c3; color: #854d0e; }
```

Project 449 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - Dashboard</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Ismailia Cycling Store dashboard	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="stat"> Visitors today 1,284...	A self-contained piece: card, post, product.
<article class="stat"> Bikes sold 57 </a...	Second-level heading for a section.

Line	What it does
<article class="stat"> Revenue <p class="value">18,450 EGP<//...	A paragraph of text.
<section class="panel">	A thematic group of content, normally with its own heading.
<table>	Tabular data in rows and columns.
<thead><tr><th>Order</th><th>Bike</th><th>Status</th></tr></thead>	Group of header rows.
<tbody>	Group of data rows.
<tr><td>#1041</td><td>City bike</td><td>Paid...	A table row.
<tr><td>#1040</td><td>Mountain bike</td><td><span class="badge wait...	A data cell.
<tr><td>#1039</td><td>Kids bike</td><td>Paid...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.

Declaration	What it does
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
background: #f3f4f6;	Background colour or image.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
padding: 1.5rem 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(12rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 4px solid var(--brand);	A top border used as an accent or separator.
font-size: .85rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.

Declaration	What it does
font-weight: 700;	Thickness of the text.
border-radius: 12px;	The line around the element: width, style and colour.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
border-radius: 999px;	Fully rounded pill shape.

Check your work

- Stat labels are headings
- Table has header cells
- Badge colours pass contrast
- Cards wrap on phones

Exercises

1. Add a simple bar chart made of divs with widths in percent.
2. Add a sidebar navigation.
3. Add a dark theme with prefers-color-scheme.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626

Field	Value
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 450: Statistics dashboard for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 2 | Files: index.html, styles.css

Brief

Build an admin-style dashboard: four statistic cards with a coloured top border and a panel containing a recent-orders table with status badges.

Learning goals

- Present numbers in cards with small uppercase labels
- Create pill-shaped status badges
- Combine grid cards and a table

Elements and CSS used

HTML elements	CSS features
article, h2, p, section, table, thead, tbody, span	border-top, text-transform, letter-spacing, border-radius: 999px, grid auto-fit

Build guide

1. Write four .stat articles inside .stats.
2. Add the panel with a small table.
3. Wrap statuses in .
4. Grid the cards.
5. Style the badges as pills with soft background colours.
6. Give the page a light grey background so white panels stand out.

Project 450: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - Dashboard</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Minya Coding Club dashboard</h1>
    <div class="stats">
      <article class="stat"><h2>Visitors today</h2><p class="value">1,
284</p></article>
      <article class="stat"><h2>Workshops sold</h2><p
class="value">57</p></article>
      <article class="stat"><h2>Revenue</h2><p class="value">18,450
EGP</p></article>
      <article class="stat"><h2>Rating</h2><p class="value">4.8 / 5</
p></article>
    </div>
    <section class="panel">
      <h2>Recent orders</h2>
      <table>
        <thead><tr><th>Order</th><th>Workshop</th><th>Status</th></
tr></thead>
        <tbody>
          <tr><td>#1041</td><td>HTML weekend</td><td><span
class="badge ok">Paid</span></td></tr>
          <tr><td>#1040</td><td>CSS art</td><td><span class="badge
wait">Pending</span></td></tr>
          <tr><td>#1039</td><td>Scratch games</td><td><span
class="badge ok">Paid</span></td></tr>
        </tbody>
      </table>
    </section>
  </main>
</body>
</html>
```

Project 450: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
body { background: #f3f4f6; }
main { max-width: 64rem; margin: 0 auto; padding: 1.5rem 1rem; }
.stats { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(12rem, 1fr)); }
.stat { background: #fff; padding: 1rem 1.25rem; border-radius: 12px;
border-top: 4px solid var(--brand); }
.stat h2 { font-size: .85rem; color: var(--muted); margin: 0; text-
transform: uppercase; letter-spacing: .05em; }
.value { font-size: 1.8rem; font-weight: 700; margin: .25rem 0 0; }
.panel { background: #fff; border-radius: 12px; padding: 1.25rem;
margin-top: 1.5rem; }
table { width: 100%; border-collapse: collapse; }
th, td { text-align: left; padding: .6rem; border-bottom: 1px solid
var(--line); }
.badge { padding: .15rem .6rem; border-radius: 999px; font-size: .
8rem; font-weight: 600; }
.ok { background: #dcfce7; color: #166534; }
.wait { background: #fef9c3; color: #854d0e; }
```

Project 450 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - Dashboard</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Minya Coding Club dashboard	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="stat"> Visitors today <p class="value">1,284...	A self-contained piece: card, post, product.
<article class="stat"> Workshops sold <p class="value">57</p...	Second-level heading for a section.

Line	What it does
<article class="stat"> Revenue <p class="value">18,450 EGP<//...	A paragraph of text.
<section class="panel">	A thematic group of content, normally with its own heading.
<table>	Tabular data in rows and columns.
<thead><tr><th>Order</th><th>Workshop</th><th>Status</th></tr></thead>	Group of header rows.
<tbody>	Group of data rows.
<tr><td>#1041</td><td>HTML weekend</td><td>P...	A table row.
<tr><td>#1040</td><td>CSS art</td><td>Pend...	A data cell.
<tr><td>#1039</td><td>Scratch games</td><td>...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.

Declaration	What it does
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
background: #f3f4f6;	Background colour or image.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
padding: 1.5rem 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(12rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	Rounds the corners.
border-top: 4px solid var(--brand);	A top border used as an accent or separator.
font-size: .85rem;	Size of the text.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.

Declaration	What it does
font-weight: 700;	Thickness of the text.
border-radius: 12px;	The line around the element: width, style and colour.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
border-radius: 999px;	Fully rounded pill shape.

Check your work

- Stat labels are headings
- Table has header cells
- Badge colours pass contrast
- Cards wrap on phones

Exercises

1. Add a simple bar chart made of divs with widths in percent.
2. Add a sidebar navigation.
3. Add a dark theme with prefers-color-scheme.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb

Field	Value
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: 404 error page

Level 1 | 25 projects, one per theme

Design a friendly 'page not found' screen with a huge outlined 404, helpful links and a search box.

Project 451: 404 error page for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 1 | Files: index.html, styles.css

Brief

Design a friendly 'page not found' screen with a huge outlined 404, helpful links and a search box.

Learning goals

- Centre a block with place-content
- Use huge fluid type with clamp()
- Provide useful next steps on error pages

Elements and CSS used

HTML elements	CSS features
main, p, h1, ul, li, a, form, label, input, button	place-content: center, clamp(), -webkit-text-stroke, line-height, flex-wrap

Build guide

1. Write the page: code, heading, links and search form.
2. Set role="search" on the form.
3. Centre everything with grid and place-content.
4. Make the 404 huge with clamp() and outline it with text-stroke.
5. Lay out links and the form horizontally with wrapping.
6. Name the file 404.html and configure your host to use it.

Project 451: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Page not found - Cairo Book Shop</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="nf">
    <p class="code">404</p>
    <h1>We can't find that page</h1>
    <p>The link may be old or the address mistyped. Try one of these
instead:</p>
    <ul>
      <li><a href="index.html">Cairo Book Shop home</a></li>
      <li><a href="books.html">All books</a></li>
      <li><a href="contact.html">Contact us</a></li>
    </ul>
    <form action="/search" role="search">
      <label for="q">Search the site</label>
      <input id="q" name="q" type="search">
      <button>Search</button>
    </form>
  </main>
</body>
</html>
```

Project 451: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.nf { min-height: 100vh; display: grid; place-content: center; text-
align: center; padding: 2rem 1rem; }
.code { font-size: clamp(5rem, 20vw, 10rem); font-weight: 800; color:
var(--accent); -webkit-text-stroke: 2px var(--brand); margin: 0; line-
height: 1; }
h1 { margin: 0 0 .5rem; }
ul { list-style: none; padding: 0; display: flex; gap: 1rem; justify-
content: center; flex-wrap: wrap; }
form { margin-top: 1.5rem; display: flex; gap: .5rem; justify-content:
 center; flex-wrap: wrap; align-items: center; }
input { padding: .6rem; border: 1px solid #bbb; border-radius: 8px; }
button { padding: .6rem 1rem; border: 0; border-radius: 8px;
```

```
  background: var(--brand); color: #fff; }
```

Project 451 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Page not found - Cairo Book Shop</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="nf">	The unique content of this page; exactly one per page.
404	A paragraph of text.
We can't find that page	The main heading; only one per page.
	Unordered (bulleted) list.
Cairo Book Shop home	A hyperlink; href gives the destination.
All books	One list item.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q">Search the site</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="q" name="q" type="search">	Search field.
<button>Search</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-content: center;	Centres the whole grid content in the container.
text-align: center;	Centres inline content such as text.
padding: 2rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
font-size: clamp(5rem, 20vw, 10rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
justify-content: center;	Centres items along the main axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: center;	The text or empty string for a pseudo-element.
align-items: center;	Centres items on the cross axis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 8px;	The line around the element: width, style and colour.
background: var(--brand);	Background colour or image.

Check your work

- The h1 says what happened in plain words
- Links go to real pages
- Search input has a label
- Looks fine at 320px wide

Exercises

1. Add an illustration as inline SVG.
2. Animate the 404 with a subtle float.
3. Add a 'report broken link' mailto with the current URL from JavaScript.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 452: 404 error page for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 1 | Files: index.html, styles.css

Brief

Design a friendly 'page not found' screen with a huge outlined 404, helpful links and a search box.

Learning goals

- Centre a block with place-content
- Use huge fluid type with clamp()
- Provide useful next steps on error pages

Elements and CSS used

HTML elements	CSS features
main, p, h1, ul, li, a, form, label, input, button	place-content: center, clamp(), -webkit-text-stroke, line-height, flex-wrap

Build guide

1. Write the page: code, heading, links and search form.
2. Set role="search" on the form.
3. Centre everything with grid and place-content.
4. Make the 404 huge with clamp() and outline it with text-stroke.
5. Lay out links and the form horizontally with wrapping.
6. Name the file 404.html and configure your host to use it.

Project 452: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Page not found - Nile Bakery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="nf">
    <p class="code">404</p>
    <h1>We can't find that page</h1>
    <p>The link may be old or the address mistyped. Try one of these
instead:</p>
    <ul>
      <li><a href="index.html">Nile Bakery home</a></li>
      <li><a href="pastries.html">All pastries</a></li>
      <li><a href="contact.html">Contact us</a></li>
    </ul>
    <form action="/search" role="search">
      <label for="q">Search the site</label>
      <input id="q" name="q" type="search">
      <button>Search</button>
    </form>
  </main>
</body>
</html>
```

Project 452: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.nf { min-height: 100vh; display: grid; place-content: center; text-
align: center; padding: 2rem 1rem; }
.code { font-size: clamp(5rem, 20vw, 10rem); font-weight: 800; color:
var(--accent); -webkit-text-stroke: 2px var(--brand); margin: 0; line-
height: 1; }
h1 { margin: 0 0 .5rem; }
ul { list-style: none; padding: 0; display: flex; gap: 1rem; justify-
content: center; flex-wrap: wrap; }
form { margin-top: 1.5rem; display: flex; gap: .5rem; justify-content:
 center; flex-wrap: wrap; align-items: center; }
input { padding: .6rem; border: 1px solid #bbb; border-radius: 8px; }
button { padding: .6rem 1rem; border: 0; border-radius: 8px;
```

```
  background: var(--brand); color: #fff; }
```

Project 452 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Page not found - Nile Bakery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="nf">	The unique content of this page; exactly one per page.
404	A paragraph of text.
We can't find that page	The main heading; only one per page.
	Unordered (bulleted) list.
Nile Bakery home	A hyperlink; href gives the destination.
All pastries	One list item.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.

Line	What it does
<label for="q">Search the site</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search">	Search field.
<button>Search</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-content: center;	Centres the whole grid content in the container.
text-align: center;	Centres inline content such as text.

Declaration	What it does
padding: 2rem 1rem;	Space inside the element between its border and content.
font-size: clamp(5rem, 20vw, 10rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
justify-content: center;	Centres items along the main axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: center;	The text or empty string for a pseudo-element.
align-items: center;	Centres items on the cross axis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 8px;	The line around the element: width, style and colour.
background: var(--brand);	Background colour or image.

Check your work

- The h1 says what happened in plain words
- Links go to real pages

- Search input has a label
- Looks fine at 320px wide

Exercises

1. Add an illustration as inline SVG.
2. Animate the 404 with a subtle float.
3. Add a 'report broken link' mailto with the current URL from JavaScript.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 453: 404 error page for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 1 | Files: index.html, styles.css

Brief

Design a friendly 'page not found' screen with a huge outlined 404, helpful links and a search box.

Learning goals

- Centre a block with place-content
- Use huge fluid type with clamp()
- Provide useful next steps on error pages

Elements and CSS used

HTML elements	CSS features
main, p, h1, ul, li, a, form, label, input, button	place-content: center, clamp(), -webkit-text-stroke, line-height, flex-wrap

Build guide

1. Write the page: code, heading, links and search form.
2. Set role="search" on the form.
3. Centre everything with grid and place-content.
4. Make the 404 huge with clamp() and outline it with text-stroke.
5. Lay out links and the form horizontally with wrapping.
6. Name the file 404.html and configure your host to use it.

Project 453: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Page not found - Pyramid Fitness</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="nf">
    <p class="code">404</p>
    <h1>We can't find that page</h1>
    <p>The link may be old or the address mistyped. Try one of these
instead:</p>
    <ul>
      <li><a href="index.html">Pyramid Fitness home</a></li>
      <li><a href="classes.html">All classes</a></li>
      <li><a href="contact.html">Contact us</a></li>
    </ul>
    <form action="/search" role="search">
      <label for="q">Search the site</label>
      <input id="q" name="q" type="search">
      <button>Search</button>
    </form>
  </main>
</body>
</html>
```

Project 453: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.nf { min-height: 100vh; display: grid; place-content: center; text-
align: center; padding: 2rem 1rem; }
.code { font-size: clamp(5rem, 20vw, 10rem); font-weight: 800; color:
var(--accent); -webkit-text-stroke: 2px var(--brand); margin: 0; line-
height: 1; }
h1 { margin: 0 0 .5rem; }
ul { list-style: none; padding: 0; display: flex; gap: 1rem; justify-
content: center; flex-wrap: wrap; }
form { margin-top: 1.5rem; display: flex; gap: .5rem; justify-content:
 center; flex-wrap: wrap; align-items: center; }
input { padding: .6rem; border: 1px solid #bbb; border-radius: 8px; }
button { padding: .6rem 1rem; border: 0; border-radius: 8px;
```

```
  background: var(--brand); color: #fff; }
```

Project 453 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Page not found - Pyramid Fitness</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="nf">	The unique content of this page; exactly one per page.
404	A paragraph of text.
We can't find that page	The main heading; only one per page.
	Unordered (bulleted) list.
Pyramid Fitness home	A hyperlink; href gives the destination.
All classes	One list item.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.

Line	What it does
<label for="q">Search the site</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search">	Search field.
<button>Search</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-content: center;	Centres the whole grid content in the container.
text-align: center;	Centres inline content such as text.

Declaration	What it does
padding: 2rem 1rem;	Space inside the element between its border and content.
font-size: clamp(5rem, 20vw, 10rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
justify-content: center;	Centres items along the main axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: center;	The text or empty string for a pseudo-element.
align-items: center;	Centres items on the cross axis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 8px;	The line around the element: width, style and colour.
background: var(--brand);	Background colour or image.

Check your work

- The h1 says what happened in plain words
- Links go to real pages

- Search input has a label
- Looks fine at 320px wide

Exercises

1. Add an illustration as inline SVG.
2. Animate the 404 with a subtle float.
3. Add a 'report broken link' mailto with the current URL from JavaScript.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 454: 404 error page for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 1 | Files: index.html, styles.css

Brief

Design a friendly 'page not found' screen with a huge outlined 404, helpful links and a search box.

Learning goals

- Centre a block with place-content
- Use huge fluid type with clamp()
- Provide useful next steps on error pages

Elements and CSS used

HTML elements	CSS features
main, p, h1, ul, li, a, form, label, input, button	place-content: center, clamp(), -webkit-text-stroke, line-height, flex-wrap

Build guide

1. Write the page: code, heading, links and search form.
2. Set role="search" on the form.
3. Centre everything with grid and place-content.
4. Make the 404 huge with clamp() and outline it with text-stroke.
5. Lay out links and the form horizontally with wrapping.
6. Name the file 404.html and configure your host to use it.

Project 454: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Page not found - Delta Dental Clinic</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="nf">
    <p class="code">404</p>
    <h1>We can't find that page</h1>
    <p>The link may be old or the address mistyped. Try one of these
instead:</p>
    <ul>
      <li><a href="index.html">Delta Dental Clinic home</a></li>
      <li><a href="services.html">All services</a></li>
      <li><a href="contact.html">Contact us</a></li>
    </ul>
    <form action="/search" role="search">
      <label for="q">Search the site</label>
      <input id="q" name="q" type="search">
      <button>Search</button>
    </form>
  </main>
</body>
</html>
```

Project 454: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.nf { min-height: 100vh; display: grid; place-content: center; text-
align: center; padding: 2rem 1rem; }
.code { font-size: clamp(5rem, 20vw, 10rem); font-weight: 800; color:
var(--accent); -webkit-text-stroke: 2px var(--brand); margin: 0; line-
height: 1; }
h1 { margin: 0 0 .5rem; }
ul { list-style: none; padding: 0; display: flex; gap: 1rem; justify-
content: center; flex-wrap: wrap; }
form { margin-top: 1.5rem; display: flex; gap: .5rem; justify-content:
 center; flex-wrap: wrap; align-items: center; }
input { padding: .6rem; border: 1px solid #bbb; border-radius: 8px; }
button { padding: .6rem 1rem; border: 0; border-radius: 8px;
```

```
  background: var(--brand); color: #fff; }
```

Project 454 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Page not found - Delta Dental Clinic</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="nf">	The unique content of this page; exactly one per page.
404	A paragraph of text.
We can't find that page	The main heading; only one per page.
	Unordered (bulleted) list.
Delta Dental Clinic home	A hyperlink; href gives the destination.
All services	One list item.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.

Line	What it does
<label for="q">Search the site</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search">	Search field.
<button>Search</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-content: center;	Centres the whole grid content in the container.
text-align: center;	Centres inline content such as text.

Declaration	What it does
padding: 2rem 1rem;	Space inside the element between its border and content.
font-size: clamp(5rem, 20vw, 10rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
justify-content: center;	Centres items along the main axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: center;	The text or empty string for a pseudo-element.
align-items: center;	Centres items on the cross axis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 8px;	The line around the element: width, style and colour.
background: var(--brand);	Background colour or image.

Check your work

- The h1 says what happened in plain words
- Links go to real pages

- Search input has a label
- Looks fine at 320px wide

Exercises

1. Add an illustration as inline SVG.
2. Animate the 404 with a subtle float.
3. Add a 'report broken link' mailto with the current URL from JavaScript.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 455: 404 error page for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 1 | Files: index.html, styles.css

Brief

Design a friendly 'page not found' screen with a huge outlined 404, helpful links and a search box.

Learning goals

- Centre a block with place-content
- Use huge fluid type with clamp()
- Provide useful next steps on error pages

Elements and CSS used

HTML elements	CSS features
main, p, h1, ul, li, a, form, label, input, button	place-content: center, clamp(), -webkit-text-stroke, line-height, flex-wrap

Build guide

1. Write the page: code, heading, links and search form.
2. Set role="search" on the form.
3. Centre everything with grid and place-content.
4. Make the 404 huge with clamp() and outline it with text-stroke.
5. Lay out links and the form horizontally with wrapping.
6. Name the file 404.html and configure your host to use it.

Project 455: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Page not found - Red Sea Travel</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="nf">
    <p class="code">404</p>
    <h1>We can't find that page</h1>
    <p>The link may be old or the address mistyped. Try one of these
instead:</p>
    <ul>
      <li><a href="index.html">Red Sea Travel home</a></li>
      <li><a href="tours.html">All tours</a></li>
      <li><a href="contact.html">Contact us</a></li>
    </ul>
    <form action="/search" role="search">
      <label for="q">Search the site</label>
      <input id="q" name="q" type="search">
      <button>Search</button>
    </form>
  </main>
</body>
</html>
```

Project 455: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.nf { min-height: 100vh; display: grid; place-content: center; text-
align: center; padding: 2rem 1rem; }
.code { font-size: clamp(5rem, 20vw, 10rem); font-weight: 800; color:
var(--accent); -webkit-text-stroke: 2px var(--brand); margin: 0; line-
height: 1; }
h1 { margin: 0 0 .5rem; }
ul { list-style: none; padding: 0; display: flex; gap: 1rem; justify-
content: center; flex-wrap: wrap; }
form { margin-top: 1.5rem; display: flex; gap: .5rem; justify-content:
 center; flex-wrap: wrap; align-items: center; }
input { padding: .6rem; border: 1px solid #bbb; border-radius: 8px; }
button { padding: .6rem 1rem; border: 0; border-radius: 8px;
```

```
  background: var(--brand); color: #fff; }
```

Project 455 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Page not found - Red Sea Travel</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="nf">	The unique content of this page; exactly one per page.
404	A paragraph of text.
We can't find that page	The main heading; only one per page.
	Unordered (bulleted) list.
Red Sea Travel home	A hyperlink; href gives the destination.
All tours	One list item.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q">Search the site</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="q" name="q" type="search">	Search field.
<button>Search</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-content: center;	Centres the whole grid content in the container.
text-align: center;	Centres inline content such as text.
padding: 2rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
font-size: clamp(5rem, 20vw, 10rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
justify-content: center;	Centres items along the main axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: center;	The text or empty string for a pseudo-element.
align-items: center;	Centres items on the cross axis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 8px;	The line around the element: width, style and colour.
background: var(--brand);	Background colour or image.

Check your work

- The h1 says what happened in plain words
- Links go to real pages
- Search input has a label
- Looks fine at 320px wide

Exercises

1. Add an illustration as inline SVG.
2. Animate the 404 with a subtle float.
3. Add a 'report broken link' mailto with the current URL from JavaScript.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 456: 404 error page for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Design a friendly 'page not found' screen with a huge outlined 404, helpful links and a search box.

Learning goals

- Centre a block with place-content
- Use huge fluid type with clamp()
- Provide useful next steps on error pages

Elements and CSS used

HTML elements	CSS features
main, p, h1, ul, li, a, form, label, input, button	place-content: center, clamp(), -webkit-text-stroke, line-height, flex-wrap

Build guide

1. Write the page: code, heading, links and search form.
2. Set role="search" on the form.
3. Centre everything with grid and place-content.
4. Make the 404 huge with clamp() and outline it with text-stroke.
5. Lay out links and the form horizontally with wrapping.
6. Name the file 404.html and configure your host to use it.

Project 456: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Page not found - Lotus Language School</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="nf">
    <p class="code">404</p>
    <h1>We can't find that page</h1>
    <p>The link may be old or the address mistyped. Try one of these
instead:</p>
    <ul>
      <li><a href="index.html">Lotus Language School home</a></li>
      <li><a href="courses.html">All courses</a></li>
      <li><a href="contact.html">Contact us</a></li>
    </ul>
    <form action="/search" role="search">
      <label for="q">Search the site</label>
      <input id="q" name="q" type="search">
      <button>Search</button>
    </form>
  </main>
</body>
</html>
```

Project 456: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.nf { min-height: 100vh; display: grid; place-content: center; text-
align: center; padding: 2rem 1rem; }
.code { font-size: clamp(5rem, 20vw, 10rem); font-weight: 800; color:
var(--accent); -webkit-text-stroke: 2px var(--brand); margin: 0; line-
height: 1; }
h1 { margin: 0 0 .5rem; }
ul { list-style: none; padding: 0; display: flex; gap: 1rem; justify-
content: center; flex-wrap: wrap; }
form { margin-top: 1.5rem; display: flex; gap: .5rem; justify-content:
 center; flex-wrap: wrap; align-items: center; }
input { padding: .6rem; border: 1px solid #bbb; border-radius: 8px; }
button { padding: .6rem 1rem; border: 0; border-radius: 8px;
```

```
  background: var(--brand); color: #fff; }
```

Project 456 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Page not found - Lotus Language School</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="nf">	The unique content of this page; exactly one per page.
404	A paragraph of text.
We can't find that page	The main heading; only one per page.
	Unordered (bulleted) list.
Lotus Language School home	A hyperlink; href gives the destination.
All courses	One list item.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.

Line	What it does
<label for="q">Search the site</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search">	Search field.
<button>Search</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-content: center;	Centres the whole grid content in the container.
text-align: center;	Centres inline content such as text.

Declaration	What it does
padding: 2rem 1rem;	Space inside the element between its border and content.
font-size: clamp(5rem, 20vw, 10rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
justify-content: center;	Centres items along the main axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: center;	The text or empty string for a pseudo-element.
align-items: center;	Centres items on the cross axis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 8px;	The line around the element: width, style and colour.
background: var(--brand);	Background colour or image.

Check your work

- The h1 says what happened in plain words
- Links go to real pages

- Search input has a label
- Looks fine at 320px wide

Exercises

1. Add an illustration as inline SVG.
2. Animate the 404 with a subtle float.
3. Add a 'report broken link' mailto with the current URL from JavaScript.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 457: 404 error page for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 1 | Files: index.html, styles.css

Brief

Design a friendly 'page not found' screen with a huge outlined 404, helpful links and a search box.

Learning goals

- Centre a block with place-content
- Use huge fluid type with clamp()
- Provide useful next steps on error pages

Elements and CSS used

HTML elements	CSS features
main, p, h1, ul, li, a, form, label, input, button	place-content: center, clamp(), -webkit-text-stroke, line-height, flex-wrap

Build guide

1. Write the page: code, heading, links and search form.
2. Set role="search" on the form.
3. Centre everything with grid and place-content.
4. Make the 404 huge with clamp() and outline it with text-stroke.
5. Lay out links and the form horizontally with wrapping.
6. Name the file 404.html and configure your host to use it.

Project 457: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Page not found - Green Leaf Cafe</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="nf">
    <p class="code">404</p>
    <h1>We can't find that page</h1>
    <p>The link may be old or the address mistyped. Try one of these
instead:</p>
    <ul>
      <li><a href="index.html">Green Leaf Cafe home</a></li>
      <li><a href="drinks.html">All drinks</a></li>
      <li><a href="contact.html">Contact us</a></li>
    </ul>
    <form action="/search" role="search">
      <label for="q">Search the site</label>
      <input id="q" name="q" type="search">
      <button>Search</button>
    </form>
  </main>
</body>
</html>
```

Project 457: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.nf { min-height: 100vh; display: grid; place-content: center; text-
align: center; padding: 2rem 1rem; }
.code { font-size: clamp(5rem, 20vw, 10rem); font-weight: 800; color:
var(--accent); -webkit-text-stroke: 2px var(--brand); margin: 0; line-
height: 1; }
h1 { margin: 0 0 .5rem; }
ul { list-style: none; padding: 0; display: flex; gap: 1rem; justify-
content: center; flex-wrap: wrap; }
form { margin-top: 1.5rem; display: flex; gap: .5rem; justify-content:
 center; flex-wrap: wrap; align-items: center; }
input { padding: .6rem; border: 1px solid #bbb; border-radius: 8px; }
button { padding: .6rem 1rem; border: 0; border-radius: 8px;
```

```
  background: var(--brand); color: #fff; }
```

Project 457 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Page not found - Green Leaf Cafe</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="nf">	The unique content of this page; exactly one per page.
404	A paragraph of text.
We can't find that page	The main heading; only one per page.
	Unordered (bulleted) list.
Green Leaf Cafe home	A hyperlink; href gives the destination.
All drinks	One list item.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q">Search the site</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="q" name="q" type="search">	Search field.
<button>Search</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-content: center;	Centres the whole grid content in the container.
text-align: center;	Centres inline content such as text.
padding: 2rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
font-size: clamp(5rem, 20vw, 10rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
justify-content: center;	Centres items along the main axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: center;	The text or empty string for a pseudo-element.
align-items: center;	Centres items on the cross axis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 8px;	The line around the element: width, style and colour.
background: var(--brand);	Background colour or image.

Check your work

- The h1 says what happened in plain words
- Links go to real pages
- Search input has a label
- Looks fine at 320px wide

Exercises

1. Add an illustration as inline SVG.
2. Animate the 404 with a subtle float.
3. Add a 'report broken link' mailto with the current URL from JavaScript.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 458: 404 error page for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 1 | Files: index.html, styles.css

Brief

Design a friendly 'page not found' screen with a huge outlined 404, helpful links and a search box.

Learning goals

- Centre a block with place-content
- Use huge fluid type with clamp()
- Provide useful next steps on error pages

Elements and CSS used

HTML elements	CSS features
main, p, h1, ul, li, a, form, label, input, button	place-content: center, clamp(), -webkit-text-stroke, line-height, flex-wrap

Build guide

1. Write the page: code, heading, links and search form.
2. Set role="search" on the form.
3. Centre everything with grid and place-content.
4. Make the 404 huge with clamp() and outline it with text-stroke.
5. Lay out links and the form horizontally with wrapping.
6. Name the file 404.html and configure your host to use it.

Project 458: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Page not found - Sinai Trekking Club</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="nf">
    <p class="code">404</p>
    <h1>We can't find that page</h1>
    <p>The link may be old or the address mistyped. Try one of these
instead:</p>
    <ul>
      <li><a href="index.html">Sinai Trekking Club home</a></li>
      <li><a href="hikes.html">All hikes</a></li>
      <li><a href="contact.html">Contact us</a></li>
    </ul>
    <form action="/search" role="search">
      <label for="q">Search the site</label>
      <input id="q" name="q" type="search">
      <button>Search</button>
    </form>
  </main>
</body>
</html>
```

Project 458: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.nf { min-height: 100vh; display: grid; place-content: center; text-
align: center; padding: 2rem 1rem; }
.code { font-size: clamp(5rem, 20vw, 10rem); font-weight: 800; color:
var(--accent); -webkit-text-stroke: 2px var(--brand); margin: 0; line-
height: 1; }
h1 { margin: 0 0 .5rem; }
ul { list-style: none; padding: 0; display: flex; gap: 1rem; justify-
content: center; flex-wrap: wrap; }
form { margin-top: 1.5rem; display: flex; gap: .5rem; justify-content:
 center; flex-wrap: wrap; align-items: center; }
input { padding: .6rem; border: 1px solid #bbb; border-radius: 8px; }
button { padding: .6rem 1rem; border: 0; border-radius: 8px;
```

```
  background: var(--brand); color: #fff; }
```

Project 458 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Page not found - Sinai Trekking Club</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="nf">	The unique content of this page; exactly one per page.
404	A paragraph of text.
We can't find that page	The main heading; only one per page.
	Unordered (bulleted) list.
Sinai Trekking Club home	A hyperlink; href gives the destination.
All hikes	One list item.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q">Search the site</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="q" name="q" type="search">	Search field.
<button>Search</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-content: center;	Centres the whole grid content in the container.
text-align: center;	Centres inline content such as text.
padding: 2rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
font-size: clamp(5rem, 20vw, 10rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
justify-content: center;	Centres items along the main axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: center;	The text or empty string for a pseudo-element.
align-items: center;	Centres items on the cross axis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 8px;	The line around the element: width, style and colour.
background: var(--brand);	Background colour or image.

Check your work

- The h1 says what happened in plain words
- Links go to real pages
- Search input has a label
- Looks fine at 320px wide

Exercises

1. Add an illustration as inline SVG.
2. Animate the 404 with a subtle float.
3. Add a 'report broken link' mailto with the current URL from JavaScript.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 459: 404 error page for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 1 | Files: index.html, styles.css

Brief

Design a friendly 'page not found' screen with a huge outlined 404, helpful links and a search box.

Learning goals

- Centre a block with place-content
- Use huge fluid type with clamp()
- Provide useful next steps on error pages

Elements and CSS used

HTML elements	CSS features
main, p, h1, ul, li, a, form, label, input, button	place-content: center, clamp(), -webkit-text-stroke, line-height, flex-wrap

Build guide

1. Write the page: code, heading, links and search form.
2. Set role="search" on the form.
3. Centre everything with grid and place-content.
4. Make the 404 huge with clamp() and outline it with text-stroke.
5. Lay out links and the form horizontally with wrapping.
6. Name the file 404.html and configure your host to use it.

Project 459: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Page not found - Horizon Photography</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="nf">
    <p class="code">404</p>
    <h1>We can't find that page</h1>
    <p>The link may be old or the address mistyped. Try one of these
instead:</p>
    <ul>
      <li><a href="index.html">Horizon Photography home</a></li>
      <li><a href="sessions.html">All sessions</a></li>
      <li><a href="contact.html">Contact us</a></li>
    </ul>
    <form action="/search" role="search">
      <label for="q">Search the site</label>
      <input id="q" name="q" type="search">
      <button>Search</button>
    </form>
  </main>
</body>
</html>
```

Project 459: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.nf { min-height: 100vh; display: grid; place-content: center; text-
align: center; padding: 2rem 1rem; }
.code { font-size: clamp(5rem, 20vw, 10rem); font-weight: 800; color:
var(--accent); -webkit-text-stroke: 2px var(--brand); margin: 0; line-
height: 1; }
h1 { margin: 0 0 .5rem; }
ul { list-style: none; padding: 0; display: flex; gap: 1rem; justify-
content: center; flex-wrap: wrap; }
form { margin-top: 1.5rem; display: flex; gap: .5rem; justify-content:
 center; flex-wrap: wrap; align-items: center; }
input { padding: .6rem; border: 1px solid #bbb; border-radius: 8px; }
button { padding: .6rem 1rem; border: 0; border-radius: 8px;
```

```
  background: var(--brand); color: #fff; }
```

Project 459 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Page not found - Horizon Photography</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="nf">	The unique content of this page; exactly one per page.
404	A paragraph of text.
We can't find that page	The main heading; only one per page.
	Unordered (bulleted) list.
Horizon Photography home	A hyperlink; href gives the destination.
All sessions	One list item.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.

Line	What it does
<label for="q">Search the site</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search">	Search field.
<button>Search</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-content: center;	Centres the whole grid content in the container.
text-align: center;	Centres inline content such as text.

Declaration	What it does
padding: 2rem 1rem;	Space inside the element between its border and content.
font-size: clamp(5rem, 20vw, 10rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
justify-content: center;	Centres items along the main axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: center;	The text or empty string for a pseudo-element.
align-items: center;	Centres items on the cross axis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 8px;	The line around the element: width, style and colour.
background: var(--brand);	Background colour or image.

Check your work

- The h1 says what happened in plain words
- Links go to real pages

- Search input has a label
- Looks fine at 320px wide

Exercises

1. Add an illustration as inline SVG.
2. Animate the 404 with a subtle float.
3. Add a 'report broken link' mailto with the current URL from JavaScript.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 460: 404 error page for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 1 | Files: index.html, styles.css

Brief

Design a friendly 'page not found' screen with a huge outlined 404, helpful links and a search box.

Learning goals

- Centre a block with place-content
- Use huge fluid type with clamp()
- Provide useful next steps on error pages

Elements and CSS used

HTML elements	CSS features
main, p, h1, ul, li, a, form, label, input, button	place-content: center, clamp(), -webkit-text-stroke, line-height, flex-wrap

Build guide

1. Write the page: code, heading, links and search form.
2. Set role="search" on the form.
3. Centre everything with grid and place-content.
4. Make the 404 huge with clamp() and outline it with text-stroke.
5. Lay out links and the form horizontally with wrapping.
6. Name the file 404.html and configure your host to use it.

Project 460: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Page not found - Papyrus Stationery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="nf">
    <p class="code">404</p>
    <h1>We can't find that page</h1>
    <p>The link may be old or the address mistyped. Try one of these
instead:</p>
    <ul>
      <li><a href="index.html">Papyrus Stationery home</a></li>
      <li><a href="products.html">All products</a></li>
      <li><a href="contact.html">Contact us</a></li>
    </ul>
    <form action="/search" role="search">
      <label for="q">Search the site</label>
      <input id="q" name="q" type="search">
      <button>Search</button>
    </form>
  </main>
</body>
</html>
```

Project 460: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.nf { min-height: 100vh; display: grid; place-content: center; text-
align: center; padding: 2rem 1rem; }
.code { font-size: clamp(5rem, 20vw, 10rem); font-weight: 800; color:
var(--accent); -webkit-text-stroke: 2px var(--brand); margin: 0; line-
height: 1; }
h1 { margin: 0 0 .5rem; }
ul { list-style: none; padding: 0; display: flex; gap: 1rem; justify-
content: center; flex-wrap: wrap; }
form { margin-top: 1.5rem; display: flex; gap: .5rem; justify-content:
 center; flex-wrap: wrap; align-items: center; }
input { padding: .6rem; border: 1px solid #bbb; border-radius: 8px; }
button { padding: .6rem 1rem; border: 0; border-radius: 8px;
```

```
  background: var(--brand); color: #fff; }
```

Project 460 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Page not found - Papyrus Stationery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="nf">	The unique content of this page; exactly one per page.
404	A paragraph of text.
We can't find that page	The main heading; only one per page.
	Unordered (bulleted) list.
Papyrus Stationery home	A hyperlink; href gives the destination.
All products	One list item.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.

Line	What it does
<label for="q">Search the site</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search">	Search field.
<button>Search</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-content: center;	Centres the whole grid content in the container.
text-align: center;	Centres inline content such as text.

Declaration	What it does
padding: 2rem 1rem;	Space inside the element between its border and content.
font-size: clamp(5rem, 20vw, 10rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
justify-content: center;	Centres items along the main axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: center;	The text or empty string for a pseudo-element.
align-items: center;	Centres items on the cross axis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 8px;	The line around the element: width, style and colour.
background: var(--brand);	Background colour or image.

Check your work

- The h1 says what happened in plain words
- Links go to real pages

- Search input has a label
- Looks fine at 320px wide

Exercises

1. Add an illustration as inline SVG.
2. Animate the 404 with a subtle float.
3. Add a 'report broken link' mailto with the current URL from JavaScript.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 461: 404 error page for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 1 | Files: index.html, styles.css

Brief

Design a friendly 'page not found' screen with a huge outlined 404, helpful links and a search box.

Learning goals

- Centre a block with place-content
- Use huge fluid type with clamp()
- Provide useful next steps on error pages

Elements and CSS used

HTML elements	CSS features
main, p, h1, ul, li, a, form, label, input, button	place-content: center, clamp(), -webkit-text-stroke, line-height, flex-wrap

Build guide

1. Write the page: code, heading, links and search form.
2. Set role="search" on the form.
3. Centre everything with grid and place-content.
4. Make the 404 huge with clamp() and outline it with text-stroke.
5. Lay out links and the form horizontally with wrapping.
6. Name the file 404.html and configure your host to use it.

Project 461: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Page not found - Oasis Plant Nursery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="nf">
    <p class="code">404</p>
    <h1>We can't find that page</h1>
    <p>The link may be old or the address mistyped. Try one of these
instead:</p>
    <ul>
      <li><a href="index.html">Oasis Plant Nursery home</a></li>
      <li><a href="plants.html">All plants</a></li>
      <li><a href="contact.html">Contact us</a></li>
    </ul>
    <form action="/search" role="search">
      <label for="q">Search the site</label>
      <input id="q" name="q" type="search">
      <button>Search</button>
    </form>
  </main>
</body>
</html>
```

Project 461: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.nf { min-height: 100vh; display: grid; place-content: center; text-
align: center; padding: 2rem 1rem; }
.code { font-size: clamp(5rem, 20vw, 10rem); font-weight: 800; color:
var(--accent); -webkit-text-stroke: 2px var(--brand); margin: 0; line-
height: 1; }
h1 { margin: 0 0 .5rem; }
ul { list-style: none; padding: 0; display: flex; gap: 1rem; justify-
content: center; flex-wrap: wrap; }
form { margin-top: 1.5rem; display: flex; gap: .5rem; justify-content:
 center; flex-wrap: wrap; align-items: center; }
input { padding: .6rem; border: 1px solid #bbb; border-radius: 8px; }
button { padding: .6rem 1rem; border: 0; border-radius: 8px;
```

```
  background: var(--brand); color: #fff; }
```

Project 461 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Page not found - Oasis Plant Nursery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="nf">	The unique content of this page; exactly one per page.
404	A paragraph of text.
We can't find that page	The main heading; only one per page.
	Unordered (bulleted) list.
Oasis Plant Nursery home	A hyperlink; href gives the destination.
All plants	One list item.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q">Search the site</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="q" name="q" type="search">	Search field.
<button>Search</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-content: center;	Centres the whole grid content in the container.
text-align: center;	Centres inline content such as text.
padding: 2rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
font-size: clamp(5rem, 20vw, 10rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
justify-content: center;	Centres items along the main axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: center;	The text or empty string for a pseudo-element.
align-items: center;	Centres items on the cross axis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 8px;	The line around the element: width, style and colour.
background: var(--brand);	Background colour or image.

Check your work

- The h1 says what happened in plain words
- Links go to real pages
- Search input has a label
- Looks fine at 320px wide

Exercises

1. Add an illustration as inline SVG.
2. Animate the 404 with a subtle float.
3. Add a 'report broken link' mailto with the current URL from JavaScript.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 462: 404 error page for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 1 | Files: index.html, styles.css

Brief

Design a friendly 'page not found' screen with a huge outlined 404, helpful links and a search box.

Learning goals

- Centre a block with place-content
- Use huge fluid type with clamp()
- Provide useful next steps on error pages

Elements and CSS used

HTML elements	CSS features
main, p, h1, ul, li, a, form, label, input, button	place-content: center, clamp(), -webkit-text-stroke, line-height, flex-wrap

Build guide

1. Write the page: code, heading, links and search form.
2. Set role="search" on the form.
3. Centre everything with grid and place-content.
4. Make the 404 huge with clamp() and outline it with text-stroke.
5. Lay out links and the form horizontally with wrapping.
6. Name the file 404.html and configure your host to use it.

Project 462: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Page not found - Cedar Furniture</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="nf">
    <p class="code">404</p>
    <h1>We can't find that page</h1>
    <p>The link may be old or the address mistyped. Try one of these
instead:</p>
    <ul>
      <li><a href="index.html">Cedar Furniture home</a></li>
      <li><a href="pieces.html">All pieces</a></li>
      <li><a href="contact.html">Contact us</a></li>
    </ul>
    <form action="/search" role="search">
      <label for="q">Search the site</label>
      <input id="q" name="q" type="search">
      <button>Search</button>
    </form>
  </main>
</body>
</html>
```

Project 462: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.nf { min-height: 100vh; display: grid; place-content: center; text-
align: center; padding: 2rem 1rem; }
.code { font-size: clamp(5rem, 20vw, 10rem); font-weight: 800; color:
var(--accent); -webkit-text-stroke: 2px var(--brand); margin: 0; line-
height: 1; }
h1 { margin: 0 0 .5rem; }
ul { list-style: none; padding: 0; display: flex; gap: 1rem; justify-
content: center; flex-wrap: wrap; }
form { margin-top: 1.5rem; display: flex; gap: .5rem; justify-content:
 center; flex-wrap: wrap; align-items: center; }
input { padding: .6rem; border: 1px solid #bbb; border-radius: 8px; }
button { padding: .6rem 1rem; border: 0; border-radius: 8px;
```

```
  background: var(--brand); color: #fff; }
```

Project 462 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Page not found - Cedar Furniture</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="nf">	The unique content of this page; exactly one per page.
404	A paragraph of text.
We can't find that page	The main heading; only one per page.
	Unordered (bulleted) list.
Cedar Furniture home	A hyperlink; href gives the destination.
All pieces	One list item.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.

Line	What it does
<label for="q">Search the site</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search">	Search field.
<button>Search</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-content: center;	Centres the whole grid content in the container.
text-align: center;	Centres inline content such as text.

Declaration	What it does
padding: 2rem 1rem;	Space inside the element between its border and content.
font-size: clamp(5rem, 20vw, 10rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
justify-content: center;	Centres items along the main axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: center;	The text or empty string for a pseudo-element.
align-items: center;	Centres items on the cross axis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 8px;	The line around the element: width, style and colour.
background: var(--brand);	Background colour or image.

Check your work

- The h1 says what happened in plain words
- Links go to real pages

- Search input has a label
- Looks fine at 320px wide

Exercises

1. Add an illustration as inline SVG.
2. Animate the 404 with a subtle float.
3. Add a 'report broken link' mailto with the current URL from JavaScript.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 463: 404 error page for Byte Repair

Theme: Byte Repair (Nasr City) | Level 1 | Files: index.html, styles.css

Brief

Design a friendly 'page not found' screen with a huge outlined 404, helpful links and a search box.

Learning goals

- Centre a block with place-content
- Use huge fluid type with clamp()
- Provide useful next steps on error pages

Elements and CSS used

HTML elements	CSS features
main, p, h1, ul, li, a, form, label, input, button	place-content: center, clamp(), -webkit-text-stroke, line-height, flex-wrap

Build guide

1. Write the page: code, heading, links and search form.
2. Set role="search" on the form.
3. Centre everything with grid and place-content.
4. Make the 404 huge with clamp() and outline it with text-stroke.
5. Lay out links and the form horizontally with wrapping.
6. Name the file 404.html and configure your host to use it.

Project 463: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Page not found - Byte Repair</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="nf">
    <p class="code">404</p>
    <h1>We can't find that page</h1>
    <p>The link may be old or the address mistyped. Try one of these
instead:</p>
    <ul>
      <li><a href="index.html">Byte Repair home</a></li>
      <li><a href="repairs.html">All repairs</a></li>
      <li><a href="contact.html">Contact us</a></li>
    </ul>
    <form action="/search" role="search">
      <label for="q">Search the site</label>
      <input id="q" name="q" type="search">
      <button>Search</button>
    </form>
  </main>
</body>
</html>
```

Project 463: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.nf { min-height: 100vh; display: grid; place-content: center; text-
align: center; padding: 2rem 1rem; }
.code { font-size: clamp(5rem, 20vw, 10rem); font-weight: 800; color:
var(--accent); -webkit-text-stroke: 2px var(--brand); margin: 0; line-
height: 1; }
h1 { margin: 0 0 .5rem; }
ul { list-style: none; padding: 0; display: flex; gap: 1rem; justify-
content: center; flex-wrap: wrap; }
form { margin-top: 1.5rem; display: flex; gap: .5rem; justify-content:
 center; flex-wrap: wrap; align-items: center; }
input { padding: .6rem; border: 1px solid #bbb; border-radius: 8px; }
button { padding: .6rem 1rem; border: 0; border-radius: 8px;
```

```
  background: var(--brand); color: #fff; }
```

Project 463 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Page not found - Byte Repair</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="nf">	The unique content of this page; exactly one per page.
404	A paragraph of text.
We can't find that page	The main heading; only one per page.
	Unordered (bulleted) list.
Byte Repair home	A hyperlink; href gives the destination.
All repairs	One list item.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.

Line	What it does
<label for="q">Search the site</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search">	Search field.
<button>Search</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-content: center;	Centres the whole grid content in the container.
text-align: center;	Centres inline content such as text.

Declaration	What it does
padding: 2rem 1rem;	Space inside the element between its border and content.
font-size: clamp(5rem, 20vw, 10rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
justify-content: center;	Centres items along the main axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: center;	The text or empty string for a pseudo-element.
align-items: center;	Centres items on the cross axis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 8px;	The line around the element: width, style and colour.
background: var(--brand);	Background colour or image.

Check your work

- The h1 says what happened in plain words
- Links go to real pages

- Search input has a label
- Looks fine at 320px wide

Exercises

1. Add an illustration as inline SVG.
2. Animate the 404 with a subtle float.
3. Add a 'report broken link' mailto with the current URL from JavaScript.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 464: 404 error page for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 1 | Files: index.html, styles.css

Brief

Design a friendly 'page not found' screen with a huge outlined 404, helpful links and a search box.

Learning goals

- Centre a block with place-content
- Use huge fluid type with clamp()
- Provide useful next steps on error pages

Elements and CSS used

HTML elements	CSS features
main, p, h1, ul, li, a, form, label, input, button	place-content: center, clamp(), -webkit-text-stroke, line-height, flex-wrap

Build guide

1. Write the page: code, heading, links and search form.
2. Set role="search" on the form.
3. Centre everything with grid and place-content.
4. Make the 404 huge with clamp() and outline it with text-stroke.
5. Lay out links and the form horizontally with wrapping.
6. Name the file 404.html and configure your host to use it.

Project 464: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Page not found - Sahara Pet Care</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="nf">
    <p class="code">404</p>
    <h1>We can't find that page</h1>
    <p>The link may be old or the address mistyped. Try one of these
instead:</p>
    <ul>
      <li><a href="index.html">Sahara Pet Care home</a></li>
      <li><a href="services.html">All services</a></li>
      <li><a href="contact.html">Contact us</a></li>
    </ul>
    <form action="/search" role="search">
      <label for="q">Search the site</label>
      <input id="q" name="q" type="search">
      <button>Search</button>
    </form>
  </main>
</body>
</html>
```

Project 464: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.nf { min-height: 100vh; display: grid; place-content: center; text-
align: center; padding: 2rem 1rem; }
.code { font-size: clamp(5rem, 20vw, 10rem); font-weight: 800; color:
var(--accent); -webkit-text-stroke: 2px var(--brand); margin: 0; line-
height: 1; }
h1 { margin: 0 0 .5rem; }
ul { list-style: none; padding: 0; display: flex; gap: 1rem; justify-
content: center; flex-wrap: wrap; }
form { margin-top: 1.5rem; display: flex; gap: .5rem; justify-content:
 center; flex-wrap: wrap; align-items: center; }
input { padding: .6rem; border: 1px solid #bbb; border-radius: 8px; }
button { padding: .6rem 1rem; border: 0; border-radius: 8px;
```

```
  background: var(--brand); color: #fff; }
```

Project 464 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Page not found - Sahara Pet Care</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="nf">	The unique content of this page; exactly one per page.
404	A paragraph of text.
We can't find that page	The main heading; only one per page.
	Unordered (bulleted) list.
Sahara Pet Care home	A hyperlink; href gives the destination.
All services	One list item.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.

Line	What it does
<label for="q">Search the site</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search">	Search field.
<button>Search</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-content: center;	Centres the whole grid content in the container.
text-align: center;	Centres inline content such as text.

Declaration	What it does
padding: 2rem 1rem;	Space inside the element between its border and content.
font-size: clamp(5rem, 20vw, 10rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
justify-content: center;	Centres items along the main axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: center;	The text or empty string for a pseudo-element.
align-items: center;	Centres items on the cross axis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 8px;	The line around the element: width, style and colour.
background: var(--brand);	Background colour or image.

Check your work

- The h1 says what happened in plain words
- Links go to real pages

- Search input has a label
- Looks fine at 320px wide

Exercises

1. Add an illustration as inline SVG.
2. Animate the 404 with a subtle float.
3. Add a 'report broken link' mailto with the current URL from JavaScript.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 465: 404 error page for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Design a friendly 'page not found' screen with a huge outlined 404, helpful links and a search box.

Learning goals

- Centre a block with place-content
- Use huge fluid type with clamp()
- Provide useful next steps on error pages

Elements and CSS used

HTML elements	CSS features
main, p, h1, ul, li, a, form, label, input, button	place-content: center, clamp(), -webkit-text-stroke, line-height, flex-wrap

Build guide

1. Write the page: code, heading, links and search form.
2. Set role="search" on the form.
3. Centre everything with grid and place-content.
4. Make the 404 huge with clamp() and outline it with text-stroke.
5. Lay out links and the form horizontally with wrapping.
6. Name the file 404.html and configure your host to use it.

Project 465: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Page not found - Alexandria Sailing School</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="nf">
    <p class="code">404</p>
    <h1>We can't find that page</h1>
    <p>The link may be old or the address mistyped. Try one of these
instead:</p>
    <ul>
      <li><a href="index.html">Alexandria Sailing School home</a></li>
      <li><a href="lessons.html">All lessons</a></li>
      <li><a href="contact.html">Contact us</a></li>
    </ul>
    <form action="/search" role="search">
      <label for="q">Search the site</label>
      <input id="q" name="q" type="search">
      <button>Search</button>
    </form>
  </main>
</body>
</html>
```

Project 465: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.nf { min-height: 100vh; display: grid; place-content: center; text-
align: center; padding: 2rem 1rem; }
.code { font-size: clamp(5rem, 20vw, 10rem); font-weight: 800; color:
var(--accent); -webkit-text-stroke: 2px var(--brand); margin: 0; line-
height: 1; }
h1 { margin: 0 0 .5rem; }
ul { list-style: none; padding: 0; display: flex; gap: 1rem; justify-
content: center; flex-wrap: wrap; }
form { margin-top: 1.5rem; display: flex; gap: .5rem; justify-content:
 center; flex-wrap: wrap; align-items: center; }
input { padding: .6rem; border: 1px solid #bbb; border-radius: 8px; }
button { padding: .6rem 1rem; border: 0; border-radius: 8px;
```

```
  background: var(--brand); color: #fff; }
```

Project 465 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Page not found - Alexandria Sailing School</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="nf">	The unique content of this page; exactly one per page.
404	A paragraph of text.
We can't find that page	The main heading; only one per page.
	Unordered (bulleted) list.
Alexandria Sailing School home	A hyperlink; href gives the destination.
All lessons	One list item.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.

Line	What it does
<label for="q">Search the site</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search">	Search field.
<button>Search</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-content: center;	Centres the whole grid content in the container.
text-align: center;	Centres inline content such as text.

Declaration	What it does
padding: 2rem 1rem;	Space inside the element between its border and content.
font-size: clamp(5rem, 20vw, 10rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
justify-content: center;	Centres items along the main axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: center;	The text or empty string for a pseudo-element.
align-items: center;	Centres items on the cross axis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 8px;	The line around the element: width, style and colour.
background: var(--brand);	Background colour or image.

Check your work

- The h1 says what happened in plain words
- Links go to real pages

- Search input has a label
- Looks fine at 320px wide

Exercises

1. Add an illustration as inline SVG.
2. Animate the 404 with a subtle float.
3. Add a 'report broken link' mailto with the current URL from JavaScript.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 466: 404 error page for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Design a friendly 'page not found' screen with a huge outlined 404, helpful links and a search box.

Learning goals

- Centre a block with place-content
- Use huge fluid type with clamp()
- Provide useful next steps on error pages

Elements and CSS used

HTML elements	CSS features
main, p, h1, ul, li, a, form, label, input, button	place-content: center, clamp(), -webkit-text-stroke, line-height, flex-wrap

Build guide

1. Write the page: code, heading, links and search form.
2. Set role="search" on the form.
3. Centre everything with grid and place-content.
4. Make the 404 huge with clamp() and outline it with text-stroke.
5. Lay out links and the form horizontally with wrapping.
6. Name the file 404.html and configure your host to use it.

Project 466: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Page not found - Habiba Handmade Jewellery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="nf">
    <p class="code">404</p>
    <h1>We can't find that page</h1>
    <p>The link may be old or the address mistyped. Try one of these
instead:</p>
    <ul>
      <li><a href="index.html">Habiba Handmade Jewellery home</a></li>
      <li><a href="items.html">All items</a></li>
      <li><a href="contact.html">Contact us</a></li>
    </ul>
    <form action="/search" role="search">
      <label for="q">Search the site</label>
      <input id="q" name="q" type="search">
      <button>Search</button>
    </form>
  </main>
</body>
</html>
```

Project 466: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.nf { min-height: 100vh; display: grid; place-content: center; text-
align: center; padding: 2rem 1rem; }
.code { font-size: clamp(5rem, 20vw, 10rem); font-weight: 800; color:
var(--accent); -webkit-text-stroke: 2px var(--brand); margin: 0; line-
height: 1; }
h1 { margin: 0 0 .5rem; }
ul { list-style: none; padding: 0; display: flex; gap: 1rem; justify-
content: center; flex-wrap: wrap; }
form { margin-top: 1.5rem; display: flex; gap: .5rem; justify-content:
 center; flex-wrap: wrap; align-items: center; }
input { padding: .6rem; border: 1px solid #bbb; border-radius: 8px; }
button { padding: .6rem 1rem; border: 0; border-radius: 8px;
```

```
  background: var(--brand); color: #fff; }
```

Project 466 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Page not found - Habiba Handmade Jewellery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="nf">	The unique content of this page; exactly one per page.
404	A paragraph of text.
We can't find that page	The main heading; only one per page.
	Unordered (bulleted) list.
Habiba Handmade Jewellery home	A hyperlink; href gives the destination.
All items	One list item.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.

Line	What it does
<label for="q">Search the site</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search">	Search field.
<button>Search</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-content: center;	Centres the whole grid content in the container.
text-align: center;	Centres inline content such as text.

Declaration	What it does
padding: 2rem 1rem;	Space inside the element between its border and content.
font-size: clamp(5rem, 20vw, 10rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
justify-content: center;	Centres items along the main axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: center;	The text or empty string for a pseudo-element.
align-items: center;	Centres items on the cross axis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 8px;	The line around the element: width, style and colour.
background: var(--brand);	Background colour or image.

Check your work

- The h1 says what happened in plain words
- Links go to real pages

- Search input has a label
- Looks fine at 320px wide

Exercises

1. Add an illustration as inline SVG.
2. Animate the 404 with a subtle float.
3. Add a 'report broken link' mailto with the current URL from JavaScript.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 467: 404 error page for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 1 | Files: index.html, styles.css

Brief

Design a friendly 'page not found' screen with a huge outlined 404, helpful links and a search box.

Learning goals

- Centre a block with place-content
- Use huge fluid type with clamp()
- Provide useful next steps on error pages

Elements and CSS used

HTML elements	CSS features
main, p, h1, ul, li, a, form, label, input, button	place-content: center, clamp(), -webkit-text-stroke, line-height, flex-wrap

Build guide

1. Write the page: code, heading, links and search form.
2. Set role="search" on the form.
3. Centre everything with grid and place-content.
4. Make the 404 huge with clamp() and outline it with text-stroke.
5. Lay out links and the form horizontally with wrapping.
6. Name the file 404.html and configure your host to use it.

Project 467: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Page not found - Fayoum Pottery Studio</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="nf">
    <p class="code">404</p>
    <h1>We can't find that page</h1>
    <p>The link may be old or the address mistyped. Try one of these
instead:</p>
    <ul>
      <li><a href="index.html">Fayoum Pottery Studio home</a></li>
      <li><a href="workshops.html">All workshops</a></li>
      <li><a href="contact.html">Contact us</a></li>
    </ul>
    <form action="/search" role="search">
      <label for="q">Search the site</label>
      <input id="q" name="q" type="search">
      <button>Search</button>
    </form>
  </main>
</body>
</html>
```

Project 467: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.nf { min-height: 100vh; display: grid; place-content: center; text-
align: center; padding: 2rem 1rem; }
.code { font-size: clamp(5rem, 20vw, 10rem); font-weight: 800; color:
var(--accent); -webkit-text-stroke: 2px var(--brand); margin: 0; line-
height: 1; }
h1 { margin: 0 0 .5rem; }
ul { list-style: none; padding: 0; display: flex; gap: 1rem; justify-
content: center; flex-wrap: wrap; }
form { margin-top: 1.5rem; display: flex; gap: .5rem; justify-content:
 center; flex-wrap: wrap; align-items: center; }
input { padding: .6rem; border: 1px solid #bbb; border-radius: 8px; }
button { padding: .6rem 1rem; border: 0; border-radius: 8px;
```

```
  background: var(--brand); color: #fff; }
```

Project 467 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Page not found - Fayoum Pottery Studio</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="nf">	The unique content of this page; exactly one per page.
404	A paragraph of text.
We can't find that page	The main heading; only one per page.
	Unordered (bulleted) list.
Fayoum Pottery Studio home	A hyperlink; href gives the destination.
All workshops	One list item.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.

Line	What it does
<label for="q">Search the site</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search">	Search field.
<button>Search</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-content: center;	Centres the whole grid content in the container.
text-align: center;	Centres inline content such as text.

Declaration	What it does
padding: 2rem 1rem;	Space inside the element between its border and content.
font-size: clamp(5rem, 20vw, 10rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
justify-content: center;	Centres items along the main axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: center;	The text or empty string for a pseudo-element.
align-items: center;	Centres items on the cross axis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 8px;	The line around the element: width, style and colour.
background: var(--brand);	Background colour or image.

Check your work

- The h1 says what happened in plain words
- Links go to real pages

- Search input has a label
- Looks fine at 320px wide

Exercises

1. Add an illustration as inline SVG.
2. Animate the 404 with a subtle float.
3. Add a 'report broken link' mailto with the current URL from JavaScript.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 468: 404 error page for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 1 | Files: index.html, styles.css

Brief

Design a friendly 'page not found' screen with a huge outlined 404, helpful links and a search box.

Learning goals

- Centre a block with place-content
- Use huge fluid type with clamp()
- Provide useful next steps on error pages

Elements and CSS used

HTML elements	CSS features
main, p, h1, ul, li, a, form, label, input, button	place-content: center, clamp(), -webkit-text-stroke, line-height, flex-wrap

Build guide

1. Write the page: code, heading, links and search form.
2. Set role="search" on the form.
3. Centre everything with grid and place-content.
4. Make the 404 huge with clamp() and outline it with text-stroke.
5. Lay out links and the form horizontally with wrapping.
6. Name the file 404.html and configure your host to use it.

Project 468: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Page not found - Cleopatra Beauty Salon</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="nf">
    <p class="code">404</p>
    <h1>We can't find that page</h1>
    <p>The link may be old or the address mistyped. Try one of these
instead:</p>
    <ul>
      <li><a href="index.html">Cleopatra Beauty Salon home</a></li>
      <li><a href="treatments.html">All treatments</a></li>
      <li><a href="contact.html">Contact us</a></li>
    </ul>
    <form action="/search" role="search">
      <label for="q">Search the site</label>
      <input id="q" name="q" type="search">
      <button>Search</button>
    </form>
  </main>
</body>
</html>
```

Project 468: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.nf { min-height: 100vh; display: grid; place-content: center; text-
align: center; padding: 2rem 1rem; }
.code { font-size: clamp(5rem, 20vw, 10rem); font-weight: 800; color:
var(--accent); -webkit-text-stroke: 2px var(--brand); margin: 0; line-
height: 1; }
h1 { margin: 0 0 .5rem; }
ul { list-style: none; padding: 0; display: flex; gap: 1rem; justify-
content: center; flex-wrap: wrap; }
form { margin-top: 1.5rem; display: flex; gap: .5rem; justify-content:
 center; flex-wrap: wrap; align-items: center; }
input { padding: .6rem; border: 1px solid #bbb; border-radius: 8px; }
button { padding: .6rem 1rem; border: 0; border-radius: 8px;
```

```
  background: var(--brand); color: #fff; }
```

Project 468 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Page not found - Cleopatra Beauty Salon</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="nf">	The unique content of this page; exactly one per page.
404	A paragraph of text.
We can't find that page	The main heading; only one per page.
	Unordered (bulleted) list.
Cleopatra Beauty Salon home	A hyperlink; href gives the destination.
All treatments	One list item.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.

Line	What it does
<label for="q">Search the site</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search">	Search field.
<button>Search</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-content: center;	Centres the whole grid content in the container.
text-align: center;	Centres inline content such as text.

Declaration	What it does
padding: 2rem 1rem;	Space inside the element between its border and content.
font-size: clamp(5rem, 20vw, 10rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
justify-content: center;	Centres items along the main axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: center;	The text or empty string for a pseudo-element.
align-items: center;	Centres items on the cross axis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 8px;	The line around the element: width, style and colour.
background: var(--brand);	Background colour or image.

Check your work

- The h1 says what happened in plain words
- Links go to real pages

- Search input has a label
- Looks fine at 320px wide

Exercises

1. Add an illustration as inline SVG.
2. Animate the 404 with a subtle float.
3. Add a 'report broken link' mailto with the current URL from JavaScript.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 469: 404 error page for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 1 | Files: index.html, styles.css

Brief

Design a friendly 'page not found' screen with a huge outlined 404, helpful links and a search box.

Learning goals

- Centre a block with place-content
- Use huge fluid type with clamp()
- Provide useful next steps on error pages

Elements and CSS used

HTML elements	CSS features
main, p, h1, ul, li, a, form, label, input, button	place-content: center, clamp(), -webkit-text-stroke, line-height, flex-wrap

Build guide

1. Write the page: code, heading, links and search form.
2. Set role="search" on the form.
3. Centre everything with grid and place-content.
4. Make the 404 huge with clamp() and outline it with text-stroke.
5. Lay out links and the form horizontally with wrapping.
6. Name the file 404.html and configure your host to use it.

Project 469: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Page not found - Suez Auto Service</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="nf">
    <p class="code">404</p>
    <h1>We can't find that page</h1>
    <p>The link may be old or the address mistyped. Try one of these
instead:</p>
    <ul>
      <li><a href="index.html">Suez Auto Service home</a></li>
      <li><a href="services.html">All services</a></li>
      <li><a href="contact.html">Contact us</a></li>
    </ul>
    <form action="/search" role="search">
      <label for="q">Search the site</label>
      <input id="q" name="q" type="search">
      <button>Search</button>
    </form>
  </main>
</body>
</html>
```

Project 469: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.nf { min-height: 100vh; display: grid; place-content: center; text-
align: center; padding: 2rem 1rem; }
.code { font-size: clamp(5rem, 20vw, 10rem); font-weight: 800; color:
var(--accent); -webkit-text-stroke: 2px var(--brand); margin: 0; line-
height: 1; }
h1 { margin: 0 0 .5rem; }
ul { list-style: none; padding: 0; display: flex; gap: 1rem; justify-
content: center; flex-wrap: wrap; }
form { margin-top: 1.5rem; display: flex; gap: .5rem; justify-content:
 center; flex-wrap: wrap; align-items: center; }
input { padding: .6rem; border: 1px solid #bbb; border-radius: 8px; }
button { padding: .6rem 1rem; border: 0; border-radius: 8px;
```

```
  background: var(--brand); color: #fff; }
```

Project 469 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Page not found - Suez Auto Service</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="nf">	The unique content of this page; exactly one per page.
404	A paragraph of text.
We can't find that page	The main heading; only one per page.
	Unordered (bulleted) list.
Suez Auto Service home	A hyperlink; href gives the destination.
All services	One list item.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.

Line	What it does
<label for="q">Search the site</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search">	Search field.
<button>Search</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-content: center;	Centres the whole grid content in the container.
text-align: center;	Centres inline content such as text.

Declaration	What it does
padding: 2rem 1rem;	Space inside the element between its border and content.
font-size: clamp(5rem, 20vw, 10rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
justify-content: center;	Centres items along the main axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: center;	The text or empty string for a pseudo-element.
align-items: center;	Centres items on the cross axis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 8px;	The line around the element: width, style and colour.
background: var(--brand);	Background colour or image.

Check your work

- The h1 says what happened in plain words
- Links go to real pages

- Search input has a label
- Looks fine at 320px wide

Exercises

1. Add an illustration as inline SVG.
2. Animate the 404 with a subtle float.
3. Add a 'report broken link' mailto with the current URL from JavaScript.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 470: 404 error page for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 1 | Files: index.html, styles.css

Brief

Design a friendly 'page not found' screen with a huge outlined 404, helpful links and a search box.

Learning goals

- Centre a block with place-content
- Use huge fluid type with clamp()
- Provide useful next steps on error pages

Elements and CSS used

HTML elements	CSS features
main, p, h1, ul, li, a, form, label, input, button	place-content: center, clamp(), -webkit-text-stroke, line-height, flex-wrap

Build guide

1. Write the page: code, heading, links and search form.
2. Set role="search" on the form.
3. Centre everything with grid and place-content.
4. Make the 404 huge with clamp() and outline it with text-stroke.
5. Lay out links and the form horizontally with wrapping.
6. Name the file 404.html and configure your host to use it.

Project 470: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Page not found - Luxor Music Academy</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="nf">
    <p class="code">404</p>
    <h1>We can't find that page</h1>
    <p>The link may be old or the address mistyped. Try one of these
instead:</p>
    <ul>
      <li><a href="index.html">Luxor Music Academy home</a></li>
      <li><a href="courses.html">All courses</a></li>
      <li><a href="contact.html">Contact us</a></li>
    </ul>
    <form action="/search" role="search">
      <label for="q">Search the site</label>
      <input id="q" name="q" type="search">
      <button>Search</button>
    </form>
  </main>
</body>
</html>
```

Project 470: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.nf { min-height: 100vh; display: grid; place-content: center; text-
align: center; padding: 2rem 1rem; }
.code { font-size: clamp(5rem, 20vw, 10rem); font-weight: 800; color:
var(--accent); -webkit-text-stroke: 2px var(--brand); margin: 0; line-
height: 1; }
h1 { margin: 0 0 .5rem; }
ul { list-style: none; padding: 0; display: flex; gap: 1rem; justify-
content: center; flex-wrap: wrap; }
form { margin-top: 1.5rem; display: flex; gap: .5rem; justify-content:
 center; flex-wrap: wrap; align-items: center; }
input { padding: .6rem; border: 1px solid #bbb; border-radius: 8px; }
button { padding: .6rem 1rem; border: 0; border-radius: 8px;
```

```
  background: var(--brand); color: #fff; }
```

Project 470 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Page not found - Luxor Music Academy</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="nf">	The unique content of this page; exactly one per page.
404	A paragraph of text.
We can't find that page	The main heading; only one per page.
	Unordered (bulleted) list.
Luxor Music Academy home	A hyperlink; href gives the destination.
All courses	One list item.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.

Line	What it does
<label for="q">Search the site</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search">	Search field.
<button>Search</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-content: center;	Centres the whole grid content in the container.
text-align: center;	Centres inline content such as text.

Declaration	What it does
padding: 2rem 1rem;	Space inside the element between its border and content.
font-size: clamp(5rem, 20vw, 10rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
justify-content: center;	Centres items along the main axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: center;	The text or empty string for a pseudo-element.
align-items: center;	Centres items on the cross axis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 8px;	The line around the element: width, style and colour.
background: var(--brand);	Background colour or image.

Check your work

- The h1 says what happened in plain words
- Links go to real pages

- Search input has a label
- Looks fine at 320px wide

Exercises

1. Add an illustration as inline SVG.
2. Animate the 404 with a subtle float.
3. Add a 'report broken link' mailto with the current URL from JavaScript.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 471: 404 error page for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 1 | Files: index.html, styles.css

Brief

Design a friendly 'page not found' screen with a huge outlined 404, helpful links and a search box.

Learning goals

- Centre a block with place-content
- Use huge fluid type with clamp()
- Provide useful next steps on error pages

Elements and CSS used

HTML elements	CSS features
main, p, h1, ul, li, a, form, label, input, button	place-content: center, clamp(), -webkit-text-stroke, line-height, flex-wrap

Build guide

1. Write the page: code, heading, links and search form.
2. Set role="search" on the form.
3. Centre everything with grid and place-content.
4. Make the 404 huge with clamp() and outline it with text-stroke.
5. Lay out links and the form horizontally with wrapping.
6. Name the file 404.html and configure your host to use it.

Project 471: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Page not found - Port Said Seafood</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="nf">
    <p class="code">404</p>
    <h1>We can't find that page</h1>
    <p>The link may be old or the address mistyped. Try one of these
instead:</p>
    <ul>
      <li><a href="index.html">Port Said Seafood home</a></li>
      <li><a href="dishes.html">All dishes</a></li>
      <li><a href="contact.html">Contact us</a></li>
    </ul>
    <form action="/search" role="search">
      <label for="q">Search the site</label>
      <input id="q" name="q" type="search">
      <button>Search</button>
    </form>
  </main>
</body>
</html>
```

Project 471: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.nf { min-height: 100vh; display: grid; place-content: center; text-
align: center; padding: 2rem 1rem; }
.code { font-size: clamp(5rem, 20vw, 10rem); font-weight: 800; color:
var(--accent); -webkit-text-stroke: 2px var(--brand); margin: 0; line-
height: 1; }
h1 { margin: 0 0 .5rem; }
ul { list-style: none; padding: 0; display: flex; gap: 1rem; justify-
content: center; flex-wrap: wrap; }
form { margin-top: 1.5rem; display: flex; gap: .5rem; justify-content:
 center; flex-wrap: wrap; align-items: center; }
input { padding: .6rem; border: 1px solid #bbb; border-radius: 8px; }
button { padding: .6rem 1rem; border: 0; border-radius: 8px;
```

```
  background: var(--brand); color: #fff; }
```

Project 471 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Page not found - Port Said Seafood</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="nf">	The unique content of this page; exactly one per page.
404	A paragraph of text.
We can't find that page	The main heading; only one per page.
	Unordered (bulleted) list.
Port Said Seafood home	A hyperlink; href gives the destination.
All dishes	One list item.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.

Line	What it does
<label for="q">Search the site</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search">	Search field.
<button>Search</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-content: center;	Centres the whole grid content in the container.
text-align: center;	Centres inline content such as text.

Declaration	What it does
padding: 2rem 1rem;	Space inside the element between its border and content.
font-size: clamp(5rem, 20vw, 10rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
justify-content: center;	Centres items along the main axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: center;	The text or empty string for a pseudo-element.
align-items: center;	Centres items on the cross axis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 8px;	The line around the element: width, style and colour.
background: var(--brand);	Background colour or image.

Check your work

- The h1 says what happened in plain words
- Links go to real pages

- Search input has a label
- Looks fine at 320px wide

Exercises

1. Add an illustration as inline SVG.
2. Animate the 404 with a subtle float.
3. Add a 'report broken link' mailto with the current URL from JavaScript.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 472: 404 error page for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 1 | Files: index.html, styles.css

Brief

Design a friendly 'page not found' screen with a huge outlined 404, helpful links and a search box.

Learning goals

- Centre a block with place-content
- Use huge fluid type with clamp()
- Provide useful next steps on error pages

Elements and CSS used

HTML elements	CSS features
main, p, h1, ul, li, a, form, label, input, button	place-content: center, clamp(), -webkit-text-stroke, line-height, flex-wrap

Build guide

1. Write the page: code, heading, links and search form.
2. Set role="search" on the form.
3. Centre everything with grid and place-content.
4. Make the 404 huge with clamp() and outline it with text-stroke.
5. Lay out links and the form horizontally with wrapping.
6. Name the file 404.html and configure your host to use it.

Project 472: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Page not found - Delta Kids Library</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="nf">
    <p class="code">404</p>
    <h1>We can't find that page</h1>
    <p>The link may be old or the address mistyped. Try one of these
instead:</p>
    <ul>
      <li><a href="index.html">Delta Kids Library home</a></li>
      <li><a href="programmes.html">All programmes</a></li>
      <li><a href="contact.html">Contact us</a></li>
    </ul>
    <form action="/search" role="search">
      <label for="q">Search the site</label>
      <input id="q" name="q" type="search">
      <button>Search</button>
    </form>
  </main>
</body>
</html>
```

Project 472: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.nf { min-height: 100vh; display: grid; place-content: center; text-
align: center; padding: 2rem 1rem; }
.code { font-size: clamp(5rem, 20vw, 10rem); font-weight: 800; color:
var(--accent); -webkit-text-stroke: 2px var(--brand); margin: 0; line-
height: 1; }
h1 { margin: 0 0 .5rem; }
ul { list-style: none; padding: 0; display: flex; gap: 1rem; justify-
content: center; flex-wrap: wrap; }
form { margin-top: 1.5rem; display: flex; gap: .5rem; justify-content:
 center; flex-wrap: wrap; align-items: center; }
input { padding: .6rem; border: 1px solid #bbb; border-radius: 8px; }
button { padding: .6rem 1rem; border: 0; border-radius: 8px;
```

```
  background: var(--brand); color: #fff; }
```

Project 472 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Page not found - Delta Kids Library</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="nf">	The unique content of this page; exactly one per page.
404	A paragraph of text.
We can't find that page	The main heading; only one per page.
	Unordered (bulleted) list.
Delta Kids Library home	A hyperlink; href gives the destination.
All programmes	One list item.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.

Line	What it does
<label for="q">Search the site</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search">	Search field.
<button>Search</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-content: center;	Centres the whole grid content in the container.
text-align: center;	Centres inline content such as text.

Declaration	What it does
padding: 2rem 1rem;	Space inside the element between its border and content.
font-size: clamp(5rem, 20vw, 10rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
justify-content: center;	Centres items along the main axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: center;	The text or empty string for a pseudo-element.
align-items: center;	Centres items on the cross axis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 8px;	The line around the element: width, style and colour.
background: var(--brand);	Background colour or image.

Check your work

- The h1 says what happened in plain words
- Links go to real pages

- Search input has a label
- Looks fine at 320px wide

Exercises

1. Add an illustration as inline SVG.
2. Animate the 404 with a subtle float.
3. Add a 'report broken link' mailto with the current URL from JavaScript.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 473: 404 error page for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Design a friendly 'page not found' screen with a huge outlined 404, helpful links and a search box.

Learning goals

- Centre a block with place-content
- Use huge fluid type with clamp()
- Provide useful next steps on error pages

Elements and CSS used

HTML elements	CSS features
main, p, h1, ul, li, a, form, label, input, button	place-content: center, clamp(), -webkit-text-stroke, line-height, flex-wrap

Build guide

1. Write the page: code, heading, links and search form.
2. Set role="search" on the form.
3. Centre everything with grid and place-content.
4. Make the 404 huge with clamp() and outline it with text-stroke.
5. Lay out links and the form horizontally with wrapping.
6. Name the file 404.html and configure your host to use it.

Project 473: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Page not found - Nubian Guest House</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="nf">
    <p class="code">404</p>
    <h1>We can't find that page</h1>
    <p>The link may be old or the address mistyped. Try one of these
instead:</p>
    <ul>
      <li><a href="index.html">Nubian Guest House home</a></li>
      <li><a href="rooms.html">All rooms</a></li>
      <li><a href="contact.html">Contact us</a></li>
    </ul>
    <form action="/search" role="search">
      <label for="q">Search the site</label>
      <input id="q" name="q" type="search">
      <button>Search</button>
    </form>
  </main>
</body>
</html>
```

Project 473: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.nf { min-height: 100vh; display: grid; place-content: center; text-
align: center; padding: 2rem 1rem; }
.code { font-size: clamp(5rem, 20vw, 10rem); font-weight: 800; color:
var(--accent); -webkit-text-stroke: 2px var(--brand); margin: 0; line-
height: 1; }
h1 { margin: 0 0 .5rem; }
ul { list-style: none; padding: 0; display: flex; gap: 1rem; justify-
content: center; flex-wrap: wrap; }
form { margin-top: 1.5rem; display: flex; gap: .5rem; justify-content:
 center; flex-wrap: wrap; align-items: center; }
input { padding: .6rem; border: 1px solid #bbb; border-radius: 8px; }
button { padding: .6rem 1rem; border: 0; border-radius: 8px;
```

```
  background: var(--brand); color: #fff; }
```

Project 473 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Page not found - Nubian Guest House</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="nf">	The unique content of this page; exactly one per page.
404	A paragraph of text.
We can't find that page	The main heading; only one per page.
	Unordered (bulleted) list.
Nubian Guest House home	A hyperlink; href gives the destination.
All rooms	One list item.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q">Search the site</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="q" name="q" type="search">	Search field.
<button>Search</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-content: center;	Centres the whole grid content in the container.
text-align: center;	Centres inline content such as text.
padding: 2rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
font-size: clamp(5rem, 20vw, 10rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
justify-content: center;	Centres items along the main axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: center;	The text or empty string for a pseudo-element.
align-items: center;	Centres items on the cross axis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 8px;	The line around the element: width, style and colour.
background: var(--brand);	Background colour or image.

Check your work

- The h1 says what happened in plain words
- Links go to real pages
- Search input has a label
- Looks fine at 320px wide

Exercises

1. Add an illustration as inline SVG.
2. Animate the 404 with a subtle float.
3. Add a 'report broken link' mailto with the current URL from JavaScript.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 474: 404 error page for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 1 | Files: index.html, styles.css

Brief

Design a friendly 'page not found' screen with a huge outlined 404, helpful links and a search box.

Learning goals

- Centre a block with place-content
- Use huge fluid type with clamp()
- Provide useful next steps on error pages

Elements and CSS used

HTML elements	CSS features
main, p, h1, ul, li, a, form, label, input, button	place-content: center, clamp(), -webkit-text-stroke, line-height, flex-wrap

Build guide

1. Write the page: code, heading, links and search form.
2. Set role="search" on the form.
3. Centre everything with grid and place-content.
4. Make the 404 huge with clamp() and outline it with text-stroke.
5. Lay out links and the form horizontally with wrapping.
6. Name the file 404.html and configure your host to use it.

Project 474: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Page not found - Ismailia Cycling Store</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="nf">
    <p class="code">404</p>
    <h1>We can't find that page</h1>
    <p>The link may be old or the address mistyped. Try one of these
instead:</p>
    <ul>
      <li><a href="index.html">Ismailia Cycling Store home</a></li>
      <li><a href="bikes.html">All bikes</a></li>
      <li><a href="contact.html">Contact us</a></li>
    </ul>
    <form action="/search" role="search">
      <label for="q">Search the site</label>
      <input id="q" name="q" type="search">
      <button>Search</button>
    </form>
  </main>
</body>
</html>
```

Project 474: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.nf { min-height: 100vh; display: grid; place-content: center; text-
align: center; padding: 2rem 1rem; }
.code { font-size: clamp(5rem, 20vw, 10rem); font-weight: 800; color:
var(--accent); -webkit-text-stroke: 2px var(--brand); margin: 0; line-
height: 1; }
h1 { margin: 0 0 .5rem; }
ul { list-style: none; padding: 0; display: flex; gap: 1rem; justify-
content: center; flex-wrap: wrap; }
form { margin-top: 1.5rem; display: flex; gap: .5rem; justify-content:
 center; flex-wrap: wrap; align-items: center; }
input { padding: .6rem; border: 1px solid #bbb; border-radius: 8px; }
button { padding: .6rem 1rem; border: 0; border-radius: 8px;
```

```
  background: var(--brand); color: #fff; }
```

Project 474 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Page not found - Ismailia Cycling Store</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="nf">	The unique content of this page; exactly one per page.
404	A paragraph of text.
We can't find that page	The main heading; only one per page.
	Unordered (bulleted) list.
Ismailia Cycling Store home	A hyperlink; href gives the destination.
All bikes	One list item.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q">Search the site</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<input id="q" name="q" type="search">	Search field.
<button>Search</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-content: center;	Centres the whole grid content in the container.
text-align: center;	Centres inline content such as text.
padding: 2rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
font-size: clamp(5rem, 20vw, 10rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
justify-content: center;	Centres items along the main axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: center;	The text or empty string for a pseudo-element.
align-items: center;	Centres items on the cross axis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 8px;	The line around the element: width, style and colour.
background: var(--brand);	Background colour or image.

Check your work

- The h1 says what happened in plain words
- Links go to real pages
- Search input has a label
- Looks fine at 320px wide

Exercises

1. Add an illustration as inline SVG.
2. Animate the 404 with a subtle float.
3. Add a 'report broken link' mailto with the current URL from JavaScript.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 475: 404 error page for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 1 | Files: index.html, styles.css

Brief

Design a friendly 'page not found' screen with a huge outlined 404, helpful links and a search box.

Learning goals

- Centre a block with place-content
- Use huge fluid type with clamp()
- Provide useful next steps on error pages

Elements and CSS used

HTML elements	CSS features
main, p, h1, ul, li, a, form, label, input, button	place-content: center, clamp(), -webkit-text-stroke, line-height, flex-wrap

Build guide

1. Write the page: code, heading, links and search form.
2. Set role="search" on the form.
3. Centre everything with grid and place-content.
4. Make the 404 huge with clamp() and outline it with text-stroke.
5. Lay out links and the form horizontally with wrapping.
6. Name the file 404.html and configure your host to use it.

Project 475: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Page not found - Minya Coding Club</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="nf">
    <p class="code">404</p>
    <h1>We can't find that page</h1>
    <p>The link may be old or the address mistyped. Try one of these
instead:</p>
    <ul>
      <li><a href="index.html">Minya Coding Club home</a></li>
      <li><a href="workshops.html">All workshops</a></li>
      <li><a href="contact.html">Contact us</a></li>
    </ul>
    <form action="/search" role="search">
      <label for="q">Search the site</label>
      <input id="q" name="q" type="search">
      <button>Search</button>
    </form>
  </main>
</body>
</html>
```

Project 475: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.nf { min-height: 100vh; display: grid; place-content: center; text-
align: center; padding: 2rem 1rem; }
.code { font-size: clamp(5rem, 20vw, 10rem); font-weight: 800; color:
var(--accent); -webkit-text-stroke: 2px var(--brand); margin: 0; line-
height: 1; }
h1 { margin: 0 0 .5rem; }
ul { list-style: none; padding: 0; display: flex; gap: 1rem; justify-
content: center; flex-wrap: wrap; }
form { margin-top: 1.5rem; display: flex; gap: .5rem; justify-content:
 center; flex-wrap: wrap; align-items: center; }
input { padding: .6rem; border: 1px solid #bbb; border-radius: 8px; }
button { padding: .6rem 1rem; border: 0; border-radius: 8px;
```

```
  background: var(--brand); color: #fff; }
```

Project 475 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Page not found - Minya Coding Club</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="nf">	The unique content of this page; exactly one per page.
404	A paragraph of text.
We can't find that page	The main heading; only one per page.
	Unordered (bulleted) list.
Minya Coding Club home	A hyperlink; href gives the destination.
All workshops	One list item.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.

Line	What it does
<label for="q">Search the site</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search">	Search field.
<button>Search</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
place-content: center;	Centres the whole grid content in the container.
text-align: center;	Centres inline content such as text.

Declaration	What it does
padding: 2rem 1rem;	Space inside the element between its border and content.
font-size: clamp(5rem, 20vw, 10rem);	A fluid value between a minimum and a maximum, based on the middle expression.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
justify-content: center;	Centres items along the main axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: center;	The text or empty string for a pseudo-element.
align-items: center;	Centres items on the cross axis.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-radius: 8px;	Rounds the corners.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 8px;	The line around the element: width, style and colour.
background: var(--brand);	Background colour or image.

Check your work

- The h1 says what happened in plain words
- Links go to real pages

- Search input has a label
- Looks fine at 320px wide

Exercises

1. Add an illustration as inline SVG.
2. Animate the 404 with a subtle float.
3. Add a 'report broken link' mailto with the current URL from JavaScript.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Blog article

Level 2 | 25 projects, one per theme

Write a full blog post with article header metadata, lead paragraph, hero figure, sections, a callout aside and tags in the footer.

Project 476: Blog article for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 2 | Files: index.html, styles.css

Brief

Write a full blog post with article header metadata, lead paragraph, hero figure, sections, a callout aside and tags in the footer.

Learning goals

- Use article, header, footer, aside and time inside a post
- Set up readable long-form typography
- Style a callout and tag pills

Elements and CSS used

HTML elements	CSS features
article, header, time, h1, p, figure, img, figcaption, h2, aside, strong, footer, a	font-family pairs, clamp(), border-left, border-radius partial, display: inline-block

Build guide

1. Write the article structure with header (meta, h1, lead).
2. Add the figure with caption.
3. Write two or three h2 sections.
4. Add the callout aside and the tag footer.
5. Set serif body / sans headings and a 44rem measure.
6. Style the callout and tags.

Project 476: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Why we love Learn HTML - Cairo Book Shop blog</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="post">
      <header>
        <p class="meta"><time datetime="2026-09-01">1 September 2026</
time> &middot; by Mohamed Khattab &middot; 4 min read</p>
        <h1>Why we love Learn HTML</h1>
        <p class="lead">From your first tag to a complete page. Here
is the story behind one of our favourite books.</p>
      </header>
      <figure>
        <img src="images/bookshop-1.jpg" alt="Learn HTML"
width="1200" height="700">
        <figcaption>Learn HTML, photographed in Giza.</figcaption>
      </figure>
      <h2>How it started</h2>
      <p>When Cairo Book Shop opened, Learn HTML was not on the list.
A customer asked for it, we tried, and it has been our best seller
ever since.</p>
      <h2>What makes it special</h2>
      <p>Three things: care, time and good ingredients. We never rush
a book.</p>
      <aside class="callout"><strong>Tip:</strong> Ask for it early
in the day, it sells out by the afternoon.</aside>
      <h2>Try it yourself</h2>
      <p>Learn HTML is available now for 120 EGP. <a href="books.
html">See all books</a>.</p>
      <footer class="tags">Tags: <a href="#">bookshop</a> <a
href="#">news</a></footer>
    </article>
  </main>
</body>
</html>
```

Project 476: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.post { font-family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; line-height: 1.2; }
h1 { font-size: clamp(1.8rem, 4vw, 2.6rem); margin: .2rem 0 .5rem; }
.meta { color: var(--muted); font-family: system-ui, sans-serif; font-
size: .9rem; }
.lead { font-size: 1.25rem; color: var(--muted); }
figure { margin: 2rem 0; }
img { width: 100%; height: auto; border-radius: 12px; }
figcaption { font-size: .9rem; color: var(--muted); font-family:
system-ui, sans-serif; margin-top: .4rem; }
.callout { background: var(--accent); border-left: 4px solid var(--
brand); padding: 1rem 1.25rem; margin: 1.5rem 0; border-radius: 0
10px 10px 0; }
.tags { margin-top: 2rem; padding-top: 1rem; border-top: 1px solid
var(--line); font-family: system-ui, sans-serif; font-size: .9rem; }
.tags a { display: inline-block; background: var(--accent); padding: .
1rem .6rem; border-radius: 999px; text-decoration: none; color: var(--
ink); margin-right: .3rem; }
```

Project 476 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Why we love Learn HTML - Cairo Book Shop blog</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="post">	A self-contained piece: card, post, product.
<header>	Introductory content: logo, title, navigation.
<p class="meta"><time datetime="2026-09-01">1 September 2026</time>...	A paragraph of text.
Why we love Learn HTML	The main heading; only one per page.
<figure>	Self-contained media with an optional caption.

Line	What it does
<img src="images/bookshop-1.jpg" alt="Learn HTML" width="1200" heig...	An image; alt describes it, width and height reserve space before it loads.
<figcaption>Learn HTML, photographed in Giza.</figcaption>	Caption for the figure.
How it started	Second-level heading for a section.
<aside class="callout">Tip: Ask for it early in th...	Content related to, but separate from, the main content.
<p>Learn HTML is available now for 120 EGP. <a href="books.html">Se...	A hyperlink; href gives the destination.
<footer class="tags">Tags: bookshop <a href="#">new...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.

Declaration	What it does
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.
font-size: clamp(1.8rem, 4vw, 2.6rem);	A fluid value between a minimum and a maximum, based on the middle expression.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
background: var(--accent);	Background colour or image.
border-left: 4px solid var(--brand);	A thick left border used as an accent stripe.
border-radius: 0 10px 10px 0;	The line around the element: width, style and colour.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Date has a datetime attribute
- One h1, then h2s
- Figure caption present
- Line length comfortable

Exercises

1. Add a table of contents generated from the h2 ids.
2. Add an author box with an image.
3. Add 'related posts' cards at the end.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 477: Blog article for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 2 | Files: index.html, styles.css

Brief

Write a full blog post with article header metadata, lead paragraph, hero figure, sections, a callout aside and tags in the footer.

Learning goals

- Use article, header, footer, aside and time inside a post
- Set up readable long-form typography
- Style a callout and tag pills

Elements and CSS used

HTML elements	CSS features
article, header, time, h1, p, figure, img, figcaption, h2, aside, strong, footer, a	font-family pairs, clamp(), border-left, border-radius partial, display: inline-block

Build guide

1. Write the article structure with header (meta, h1, lead).
2. Add the figure with caption.
3. Write two or three h2 sections.
4. Add the callout aside and the tag footer.
5. Set serif body / sans headings and a 44rem measure.
6. Style the callout and tags.

Project 477: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Why we love Sourdough loaf - Nile Bakery blog</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="post">
      <header>
        <p class="meta"><time datetime="2026-09-01">1 September 2026</
time> &middot; by Sara Adel &middot; 4 min read</p>
        <h1>Why we love Sourdough loaf</h1>
        <p class="lead">Slow fermented, crisp crust. Here is the
story behind one of our favourite pastries.</p>
      </header>
      <figure>
        <img src="images/bakery-1.jpg" alt="Sourdough loaf"
width="1200" height="700">
        <figcaption>Sourdough loaf, photographed in Cairo.</
figcaption>
      </figure>
      <h2>How it started</h2>
      <p>When Nile Bakery opened, Sourdough loaf was not on the list.
A customer asked for it, we tried, and it has been our best seller
ever since.</p>
      <h2>What makes it special</h2>
      <p>Three things: care, time and good ingredients. We never rush
a pastry.</p>
      <aside class="callout"><strong>Tip:</strong> Ask for it early
in the day, it sells out by the afternoon.</aside>
      <h2>Try it yourself</h2>
      <p>Sourdough loaf is available now for 60 EGP. <a
href="pastries.html">See all pastries</a>.</p>
      <footer class="tags">Tags: <a href="#">bakery</a> <a
href="#">news</a></footer>
    </article>
  </main>
</body>
</html>
```

Project 477: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
```

```
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.post { font-family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; line-height: 1.2; }
h1 { font-size: clamp(1.8rem, 4vw, 2.6rem); margin: .2rem 0 .5rem; }
.meta { color: var(--muted); font-family: system-ui, sans-serif; font-
size: .9rem; }
.lead { font-size: 1.25rem; color: var(--muted); }
figure { margin: 2rem 0; }
img { width: 100%; height: auto; border-radius: 12px; }
figcaption { font-size: .9rem; color: var(--muted); font-family:
system-ui, sans-serif; margin-top: .4rem; }
.callout { background: var(--accent); border-left: 4px solid var(--
brand); padding: 1rem 1.25rem; margin: 1.5rem 0; border-radius: 0
10px 10px 0; }
.tags { margin-top: 2rem; padding-top: 1rem; border-top: 1px solid
var(--line); font-family: system-ui, sans-serif; font-size: .9rem; }
.tags a { display: inline-block; background: var(--accent); padding: .
1rem .6rem; border-radius: 999px; text-decoration: none; color: var(--
ink); margin-right: .3rem; }
```

Project 477 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Why we love Sourdough loaf - Nile Bakery blog</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="post">	A self-contained piece: card, post, product.
<header>	Introductory content: logo, title, navigation.
<p class="meta"><time datetime="2026-09-01">1 September 2026</time>...	A paragraph of text.
Why we love Sourdough loaf	The main heading; only one per page.
<figure>	Self-contained media with an optional caption.

Line	What it does
<img src="images/bakery-1.jpg" alt="Sourdough loaf" width="1200" he...	An image; alt describes it, width and height reserve space before it loads.
<figcaption>Sourdough loaf, photographed in Cairo.</figcaption>	Caption for the figure.
How it started	Second-level heading for a section.
<aside class="callout">Tip: Ask for it early in th...	Content related to, but separate from, the main content.
<p>Sourdough loaf is available now for 60 EGP. <a href="pastries.ht...	A hyperlink; href gives the destination.
<footer class="tags">Tags: bakery <a href="#">news<...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.

Declaration	What it does
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.
font-size: clamp(1.8rem, 4vw, 2.6rem);	A fluid value between a minimum and a maximum, based on the middle expression.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
background: var(--accent);	Background colour or image.
border-left: 4px solid var(--brand);	A thick left border used as an accent stripe.
border-radius: 0 10px 10px 0;	The line around the element: width, style and colour.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Date has a datetime attribute
- One h1, then h2s
- Figure caption present
- Line length comfortable

Exercises

1. Add a table of contents generated from the h2 ids.
2. Add an author box with an image.
3. Add 'related posts' cards at the end.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 478: Blog article for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 2 | Files: index.html, styles.css

Brief

Write a full blog post with article header metadata, lead paragraph, hero figure, sections, a callout aside and tags in the footer.

Learning goals

- Use article, header, footer, aside and time inside a post
- Set up readable long-form typography
- Style a callout and tag pills

Elements and CSS used

HTML elements	CSS features
article, header, time, h1, p, figure, img, figcaption, h2, aside, strong, footer, a	font-family pairs, clamp(), border-left, border-radius partial, display: inline-block

Build guide

1. Write the article structure with header (meta, h1, lead).
2. Add the figure with caption.
3. Write two or three h2 sections.
4. Add the callout aside and the tag footer.
5. Set serif body / sans headings and a 44rem measure.
6. Style the callout and tags.

Project 478: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Why we love Morning yoga - Pyramid Fitness blog</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="post">
      <header>
        <p class="meta"><time datetime="2026-09-01">1 September 2026</
time> &middot; by Omar Farouk &middot; 4 min read</p>
        <h1>Why we love Morning yoga</h1>
        <p class="lead">Flexibility and calm, 60 minutes. Here is the
story behind one of our favourite classes.</p>
      </header>
      <figure>
        <img src="images/gym-1.jpg" alt="Morning yoga" width="1200"
height="700">
        <figcaption>Morning yoga, photographed in 6th of October.</
figcaption>
      </figure>
      <h2>How it started</h2>
      <p>When Pyramid Fitness opened, Morning yoga was not on the
list. A customer asked for it, we tried, and it has been our best
seller ever since.</p>
      <h2>What makes it special</h2>
      <p>Three things: care, time and good ingredients. We never rush
a class.</p>
      <aside class="callout"><strong>Tip:</strong> Ask for it early
in the day, it sells out by the afternoon.</aside>
      <h2>Try it yourself</h2>
      <p>Morning yoga is available now for 100 EGP. <a href="classes.
html">See all classes</a>.</p>
      <footer class="tags">Tags: <a href="#">gym</a> <a
href="#">news</a></footer>
    </article>
  </main>
</body>
</html>
```

Project 478: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
```

```
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.post { font-family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; line-height: 1.2; }
h1 { font-size: clamp(1.8rem, 4vw, 2.6rem); margin: .2rem 0 .5rem; }
.meta { color: var(--muted); font-family: system-ui, sans-serif; font-
size: .9rem; }
.lead { font-size: 1.25rem; color: var(--muted); }
figure { margin: 2rem 0; }
img { width: 100%; height: auto; border-radius: 12px; }
figcaption { font-size: .9rem; color: var(--muted); font-family:
system-ui, sans-serif; margin-top: .4rem; }
.callout { background: var(--accent); border-left: 4px solid var(--
brand); padding: 1rem 1.25rem; margin: 1.5rem 0; border-radius: 0
10px 10px 0; }
.tags { margin-top: 2rem; padding-top: 1rem; border-top: 1px solid
var(--line); font-family: system-ui, sans-serif; font-size: .9rem; }
.tags a { display: inline-block; background: var(--accent); padding: .
1rem .6rem; border-radius: 999px; text-decoration: none; color: var(--
ink); margin-right: .3rem; }
```

Project 478 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Why we love Morning yoga - Pyramid Fitness blog</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="post">	A self-contained piece: card, post, product.
<header>	Introductory content: logo, title, navigation.
<p class="meta"><time datetime="2026-09-01">1 September 2026</time>...	A paragraph of text.
Why we love Morning yoga	The main heading; only one per page.
<figure>	Self-contained media with an optional caption.
<img src="images/gym-1.jpg" alt="Morning yoga" width="1200" height=...	An image; alt describes it, width and height reserve space before it loads.

Line	What it does
<figcaption>Morning yoga, photographed in 6th of October.</figcaption>	Caption for the figure.
How it started	Second-level heading for a section.
<aside class="callout">Tip: Ask for it early in th...	Content related to, but separate from, the main content.
<p>Morning yoga is available now for 100 EGP. <a href="classes.html...	A hyperlink; href gives the destination.
<footer class="tags">Tags: gym news...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.

Declaration	What it does
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.
font-size: clamp(1.8rem, 4vw, 2.6rem);	A fluid value between a minimum and a maximum, based on the middle expression.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
background: var(--accent);	Background colour or image.
border-left: 4px solid var(--brand);	A thick left border used as an accent stripe.
border-radius: 0 10px 10px 0;	The line around the element: width, style and colour.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Date has a datetime attribute
- One h1, then h2s
- Figure caption present

- Line length comfortable

Exercises

1. Add a table of contents generated from the h2 ids.
2. Add an author box with an image.
3. Add 'related posts' cards at the end.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 479: Blog article for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 2 | Files: index.html, styles.css

Brief

Write a full blog post with article header metadata, lead paragraph, hero figure, sections, a callout aside and tags in the footer.

Learning goals

- Use article, header, footer, aside and time inside a post
- Set up readable long-form typography
- Style a callout and tag pills

Elements and CSS used

HTML elements	CSS features
article, header, time, h1, p, figure, img, figcaption, h2, aside, strong, footer, a	font-family pairs, clamp(), border-left, border-radius partial, display: inline-block

Build guide

1. Write the article structure with header (meta, h1, lead).
2. Add the figure with caption.
3. Write two or three h2 sections.
4. Add the callout aside and the tag footer.
5. Set serif body / sans headings and a 44rem measure.
6. Style the callout and tags.

Project 479: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Why we love Check-up - Delta Dental Clinic blog</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="post">
      <header>
        <p class="meta"><time datetime="2026-09-01">1 September 2026</
time> &middot; by Dr. Hana Youssef &middot; 4 min read</p>
        <h1>Why we love Check-up</h1>
        <p class="lead">Examination and cleaning. Here is the story
behind one of our favourite services.</p>
      </header>
      <figure>
        <img src="images/clinic-1.jpg" alt="Check-up" width="1200"
height="700">
        <figcaption>Check-up, photographed in Mansoura.</figcaption>
      </figure>
      <h2>How it started</h2>
      <p>When Delta Dental Clinic opened, Check-up was not on the
list. A customer asked for it, we tried, and it has been our best
seller ever since.</p>
      <h2>What makes it special</h2>
      <p>Three things: care, time and good ingredients. We never rush
a service.</p>
      <aside class="callout"><strong>Tip:</strong> Ask for it early
in the day, it sells out by the afternoon.</aside>
      <h2>Try it yourself</h2>
      <p>Check-up is available now for 300 EGP. <a href="services.
html">See all services</a>.</p>
      <footer class="tags">Tags: <a href="#">clinic</a> <a
href="#">news</a></footer>
    </article>
  </main>
</body>
</html>
```

Project 479: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.post { font-family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; line-height: 1.2; }
h1 { font-size: clamp(1.8rem, 4vw, 2.6rem); margin: .2rem 0 .5rem; }
.meta { color: var(--muted); font-family: system-ui, sans-serif; font-
size: .9rem; }
.lead { font-size: 1.25rem; color: var(--muted); }
figure { margin: 2rem 0; }
img { width: 100%; height: auto; border-radius: 12px; }
figcaption { font-size: .9rem; color: var(--muted); font-family:
system-ui, sans-serif; margin-top: .4rem; }
.callout { background: var(--accent); border-left: 4px solid var(--
brand); padding: 1rem 1.25rem; margin: 1.5rem 0; border-radius: 0
10px 10px 0; }
.tags { margin-top: 2rem; padding-top: 1rem; border-top: 1px solid
var(--line); font-family: system-ui, sans-serif; font-size: .9rem; }
.tags a { display: inline-block; background: var(--accent); padding: .
1rem .6rem; border-radius: 999px; text-decoration: none; color: var(--
ink); margin-right: .3rem; }
```

Project 479 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Why we love Check-up - Delta Dental Clinic blog</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="post">	A self-contained piece: card, post, product.
<header>	Introductory content: logo, title, navigation.
<p class="meta"><time datetime="2026-09-01">1 September 2026</time>...	A paragraph of text.
Why we love Check-up	The main heading; only one per page.
<figure>	Self-contained media with an optional caption.

Line	What it does
<img src="images/clinic-1.jpg" alt="Check-up" width="1200" height="...	An image; alt describes it, width and height reserve space before it loads.
<figcaption>Check-up, photographed in Mansoura.</figcaption>	Caption for the figure.
How it started	Second-level heading for a section.
<aside class="callout">Tip: Ask for it early in th...	Content related to, but separate from, the main content.
<p>Check-up is available now for 300 EGP. <a href="services.html">S...	A hyperlink; href gives the destination.
<footer class="tags">Tags: clinic <a href="#">news<...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.

Declaration	What it does
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.
font-size: clamp(1.8rem, 4vw, 2.6rem);	A fluid value between a minimum and a maximum, based on the middle expression.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
background: var(--accent);	Background colour or image.
border-left: 4px solid var(--brand);	A thick left border used as an accent stripe.
border-radius: 0 10px 10px 0;	The line around the element: width, style and colour.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Date has a datetime attribute
- One h1, then h2s
- Figure caption present
- Line length comfortable

Exercises

1. Add a table of contents generated from the h2 ids.
2. Add an author box with an image.
3. Add 'related posts' cards at the end.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 480: Blog article for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 2 | Files: index.html, styles.css

Brief

Write a full blog post with article header metadata, lead paragraph, hero figure, sections, a callout aside and tags in the footer.

Learning goals

- Use article, header, footer, aside and time inside a post
- Set up readable long-form typography
- Style a callout and tag pills

Elements and CSS used

HTML elements	CSS features
article, header, time, h1, p, figure, img, figcaption, h2, aside, strong, footer, a	font-family pairs, clamp(), border-left, border-radius partial, display: inline-block

Build guide

1. Write the article structure with header (meta, h1, lead).
2. Add the figure with caption.
3. Write two or three h2 sections.
4. Add the callout aside and the tag footer.
5. Set serif body / sans headings and a 44rem measure.
6. Style the callout and tags.

Project 480: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Why we love Luxor day trip - Red Sea Travel blog</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="post">
      <header>
        <p class="meta"><time datetime="2026-09-01">1 September 2026</
time> &middot; by Laila Mansour &middot; 4 min read</p>
        <h1>Why we love Luxor day trip</h1>
        <p class="lead">Karnak, Valley of the Kings. Here is the
story behind one of our favourite tours.</p>
      </header>
      <figure>
        <img src="images/travel-1.jpg" alt="Luxor day trip"
width="1200" height="700">
        <figcaption>Luxor day trip, photographed in Hurghada.</
figcaption>
      </figure>
      <h2>How it started</h2>
      <p>When Red Sea Travel opened, Luxor day trip was not on the
list. A customer asked for it, we tried, and it has been our best
seller ever since.</p>
      <h2>What makes it special</h2>
      <p>Three things: care, time and good ingredients. We never rush
a tour.</p>
      <aside class="callout"><strong>Tip:</strong> Ask for it early
in the day, it sells out by the afternoon.</aside>
      <h2>Try it yourself</h2>
      <p>Luxor day trip is available now for 1200 EGP. <a href="tours.
html">See all tours</a>.</p>
      <footer class="tags">Tags: <a href="#">travel</a> <a
href="#">news</a></footer>
    </article>
  </main>
</body>
</html>
```

Project 480: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
```

```
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.post { font-family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; line-height: 1.2; }
h1 { font-size: clamp(1.8rem, 4vw, 2.6rem); margin: .2rem 0 .5rem; }
.meta { color: var(--muted); font-family: system-ui, sans-serif; font-
size: .9rem; }
.lead { font-size: 1.25rem; color: var(--muted); }
figure { margin: 2rem 0; }
img { width: 100%; height: auto; border-radius: 12px; }
figcaption { font-size: .9rem; color: var(--muted); font-family:
system-ui, sans-serif; margin-top: .4rem; }
.callout { background: var(--accent); border-left: 4px solid var(--
brand); padding: 1rem 1.25rem; margin: 1.5rem 0; border-radius: 0
10px 10px 0; }
.tags { margin-top: 2rem; padding-top: 1rem; border-top: 1px solid
var(--line); font-family: system-ui, sans-serif; font-size: .9rem; }
.tags a { display: inline-block; background: var(--accent); padding: .
1rem .6rem; border-radius: 999px; text-decoration: none; color: var(--
ink); margin-right: .3rem; }
```

Project 480 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Why we love Luxor day trip - Red Sea Travel blog</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="post">	A self-contained piece: card, post, product.
<header>	Introductory content: logo, title, navigation.
<p class="meta"><time datetime="2026-09-01">1 September 2026</time>...	A paragraph of text.
Why we love Luxor day trip	The main heading; only one per page.
<figure>	Self-contained media with an optional caption.

Line	What it does
<img src="images/travel-1.jpg" alt="Luxor day trip" width="1200" he...	An image; alt describes it, width and height reserve space before it loads.
<figcaption>Luxor day trip, photographed in Hurghada.</figcaption>	Caption for the figure.
How it started	Second-level heading for a section.
<aside class="callout">Tip: Ask for it early in th...	Content related to, but separate from, the main content.
<p>Luxor day trip is available now for 1200 EGP. <a href="tours.htm...	A hyperlink; href gives the destination.
<footer class="tags">Tags: travel <a href="#">news<...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.

Declaration	What it does
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.
font-size: clamp(1.8rem, 4vw, 2.6rem);	A fluid value between a minimum and a maximum, based on the middle expression.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
background: var(--accent);	Background colour or image.
border-left: 4px solid var(--brand);	A thick left border used as an accent stripe.
border-radius: 0 10px 10px 0;	The line around the element: width, style and colour.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Date has a datetime attribute
- One h1, then h2s
- Figure caption present
- Line length comfortable

Exercises

1. Add a table of contents generated from the h2 ids.
2. Add an author box with an image.
3. Add 'related posts' cards at the end.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 481: Blog article for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Write a full blog post with article header metadata, lead paragraph, hero figure, sections, a callout aside and tags in the footer.

Learning goals

- Use article, header, footer, aside and time inside a post
- Set up readable long-form typography
- Style a callout and tag pills

Elements and CSS used

HTML elements	CSS features
article, header, time, h1, p, figure, img, figcaption, h2, aside, strong, footer, a	font-family pairs, clamp(), border-left, border-radius partial, display: inline-block

Build guide

1. Write the article structure with header (meta, h1, lead).
2. Add the figure with caption.
3. Write two or three h2 sections.
4. Add the callout aside and the tag footer.
5. Set serif body / sans headings and a 44rem measure.
6. Style the callout and tags.

Project 481: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Why we love English A1 - Lotus Language School blog</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="post">
      <header>
        <p class="meta"><time datetime="2026-09-01">1 September 2026</
time> &middot; by Nour El Din &middot; 4 min read</p>
        <h1>Why we love English A1</h1>
        <p class="lead">Beginner, 8 weeks. Here is the story behind
one of our favourite courses.</p>
      </header>
      <figure>
        <img src="images/school-1.jpg" alt="English A1" width="1200"
height="700">
        <figcaption>English A1, photographed in Alexandria.</
figcaption>
      </figure>
      <h2>How it started</h2>
      <p>When Lotus Language School opened, English A1 was not on the
list. A customer asked for it, we tried, and it has been our best
seller ever since.</p>
      <h2>What makes it special</h2>
      <p>Three things: care, time and good ingredients. We never rush
a course.</p>
      <aside class="callout"><strong>Tip:</strong> Ask for it early
in the day, it sells out by the afternoon.</aside>
      <h2>Try it yourself</h2>
      <p>English A1 is available now for 1800 EGP. <a href="courses.
html">See all courses</a>.</p>
      <footer class="tags">Tags: <a href="#">school</a> <a
href="#">news</a></footer>
    </article>
  </main>
</body>
</html>
```

Project 481: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
```

```
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.post { font-family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; line-height: 1.2; }
h1 { font-size: clamp(1.8rem, 4vw, 2.6rem); margin: .2rem 0 .5rem; }
.meta { color: var(--muted); font-family: system-ui, sans-serif; font-
size: .9rem; }
.lead { font-size: 1.25rem; color: var(--muted); }
figure { margin: 2rem 0; }
img { width: 100%; height: auto; border-radius: 12px; }
figcaption { font-size: .9rem; color: var(--muted); font-family:
system-ui, sans-serif; margin-top: .4rem; }
.callout { background: var(--accent); border-left: 4px solid var(--
brand); padding: 1rem 1.25rem; margin: 1.5rem 0; border-radius: 0
10px 10px 0; }
.tags { margin-top: 2rem; padding-top: 1rem; border-top: 1px solid
var(--line); font-family: system-ui, sans-serif; font-size: .9rem; }
.tags a { display: inline-block; background: var(--accent); padding: .
1rem .6rem; border-radius: 999px; text-decoration: none; color: var(--
ink); margin-right: .3rem; }
```

Project 481 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Why we love English A1 - Lotus Language School blog</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="post">	A self-contained piece: card, post, product.
<header>	Introductory content: logo, title, navigation.
<p class="meta"><time datetime="2026-09-01">1 September 2026</time>...	A paragraph of text.
Why we love English A1	The main heading; only one per page.
<figure>	Self-contained media with an optional caption.

Line	What it does
<img src="images/school-1.jpg" alt="English A1" width="1200" height...	An image; alt describes it, width and height reserve space before it loads.
<figcaption>English A1, photographed in Alexandria.</figcaption>	Caption for the figure.
How it started	Second-level heading for a section.
<aside class="callout">Tip: Ask for it early in th...	Content related to, but separate from, the main content.
<p>English A1 is available now for 1800 EGP. <a href="courses.html"...	A hyperlink; href gives the destination.
<footer class="tags">Tags: school <a href="#">news<...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.

Declaration	What it does
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.
font-size: clamp(1.8rem, 4vw, 2.6rem);	A fluid value between a minimum and a maximum, based on the middle expression.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
background: var(--accent);	Background colour or image.
border-left: 4px solid var(--brand);	A thick left border used as an accent stripe.
border-radius: 0 10px 10px 0;	The line around the element: width, style and colour.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Date has a datetime attribute
- One h1, then h2s
- Figure caption present
- Line length comfortable

Exercises

1. Add a table of contents generated from the h2 ids.
2. Add an author box with an image.
3. Add 'related posts' cards at the end.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 482: Blog article for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 2 | Files: index.html, styles.css

Brief

Write a full blog post with article header metadata, lead paragraph, hero figure, sections, a callout aside and tags in the footer.

Learning goals

- Use article, header, footer, aside and time inside a post
- Set up readable long-form typography
- Style a callout and tag pills

Elements and CSS used

HTML elements	CSS features
article, header, time, h1, p, figure, img, figcaption, h2, aside, strong, footer, a	font-family pairs, clamp(), border-left, border-radius partial, display: inline-block

Build guide

1. Write the article structure with header (meta, h1, lead).
2. Add the figure with caption.
3. Write two or three h2 sections.
4. Add the callout aside and the tag footer.
5. Set serif body / sans headings and a 44rem measure.
6. Style the callout and tags.

Project 482: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Why we love Flat white - Green Leaf Cafe blog</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="post">
      <header>
        <p class="meta"><time datetime="2026-09-01">1 September 2026</
time> &middot; by Karim Said &middot; 4 min read</p>
        <h1>Why we love Flat white</h1>
        <p class="lead">Double shot, silky milk. Here is the story
behind one of our favourite drinks.</p>
      </header>
      <figure>
        <img src="images/cafe-1.jpg" alt="Flat white" width="1200"
height="700">
        <figcaption>Flat white, photographed in Zamalek.</figcaption>
      </figure>
      <h2>How it started</h2>
      <p>When Green Leaf Cafe opened, Flat white was not on the list.
A customer asked for it, we tried, and it has been our best seller
ever since.</p>
      <h2>What makes it special</h2>
      <p>Three things: care, time and good ingredients. We never rush
a drink.</p>
      <aside class="callout"><strong>Tip:</strong> Ask for it early
in the day, it sells out by the afternoon.</aside>
      <h2>Try it yourself</h2>
      <p>Flat white is available now for 55 EGP. <a href="drinks.
html">See all drinks</a>.</p>
      <footer class="tags">Tags: <a href="#">cafe</a> <a
href="#">news</a></footer>
    </article>
  </main>
</body>
</html>
```

Project 482: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.post { font-family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; line-height: 1.2; }
h1 { font-size: clamp(1.8rem, 4vw, 2.6rem); margin: .2rem 0 .5rem; }
.meta { color: var(--muted); font-family: system-ui, sans-serif; font-
size: .9rem; }
.lead { font-size: 1.25rem; color: var(--muted); }
figure { margin: 2rem 0; }
img { width: 100%; height: auto; border-radius: 12px; }
figcaption { font-size: .9rem; color: var(--muted); font-family:
system-ui, sans-serif; margin-top: .4rem; }
.callout { background: var(--accent); border-left: 4px solid var(--
brand); padding: 1rem 1.25rem; margin: 1.5rem 0; border-radius: 0
10px 10px 0; }
.tags { margin-top: 2rem; padding-top: 1rem; border-top: 1px solid
var(--line); font-family: system-ui, sans-serif; font-size: .9rem; }
.tags a { display: inline-block; background: var(--accent); padding: .
1rem .6rem; border-radius: 999px; text-decoration: none; color: var(--
ink); margin-right: .3rem; }
```

Project 482 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Why we love Flat white - Green Leaf Cafe blog</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="post">	A self-contained piece: card, post, product.
<header>	Introductory content: logo, title, navigation.
<p class="meta"><time datetime="2026-09-01">1 September 2026</time>...	A paragraph of text.
Why we love Flat white	The main heading; only one per page.
<figure>	Self-contained media with an optional caption.
<img src="images/cafe-1.jpg" alt="Flat white" width="1200" height="...	An image; alt describes it, width and height reserve space before it loads.

Line	What it does
<figcaption>Flat white, photographed in Zamalek.</figcaption>	Caption for the figure.
How it started	Second-level heading for a section.
<aside class="callout">Tip: Ask for it early in th...	Content related to, but separate from, the main content.
<p>Flat white is available now for 55 EGP. <a href="drinks.html">Se...	A hyperlink; href gives the destination.
<footer class="tags">Tags: cafe <a href="#">news</a...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.

Declaration	What it does
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.
font-size: clamp(1.8rem, 4vw, 2.6rem);	A fluid value between a minimum and a maximum, based on the middle expression.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
background: var(--accent);	Background colour or image.
border-left: 4px solid var(--brand);	A thick left border used as an accent stripe.
border-radius: 0 10px 10px 0;	The line around the element: width, style and colour.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Date has a datetime attribute
- One h1, then h2s
- Figure caption present

- Line length comfortable

Exercises

1. Add a table of contents generated from the h2 ids.
2. Add an author box with an image.
3. Add 'related posts' cards at the end.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 483: Blog article for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 2 | Files: index.html, styles.css

Brief

Write a full blog post with article header metadata, lead paragraph, hero figure, sections, a callout aside and tags in the footer.

Learning goals

- Use article, header, footer, aside and time inside a post
- Set up readable long-form typography
- Style a callout and tag pills

Elements and CSS used

HTML elements	CSS features
article, header, time, h1, p, figure, img, figcaption, h2, aside, strong, footer, a	font-family pairs, clamp(), border-left, border-radius partial, display: inline-block

Build guide

1. Write the article structure with header (meta, h1, lead).
2. Add the figure with caption.
3. Write two or three h2 sections.
4. Add the callout aside and the tag footer.
5. Set serif body / sans headings and a 44rem measure.
6. Style the callout and tags.

Project 483: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Why we love Mount Sinai sunrise - Sinai Trekking Club blog</
title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="post">
      <header>
        <p class="meta"><time datetime="2026-09-01">1 September 2026</
time> &middot; by Yara Hamdy &middot; 4 min read</p>
        <h1>Why we love Mount Sinai sunrise</h1>
        <p class="lead">Night climb, 7 km. Here is the story behind
one of our favourite hikes.</p>
      </header>
      <figure>
        <img src="images/trekking-1.jpg" alt="Mount Sinai sunrise"
width="1200" height="700">
        <figcaption>Mount Sinai sunrise, photographed in Saint
Catherine.</figcaption>
      </figure>
      <h2>How it started</h2>
      <p>When Sinai Trekking Club opened, Mount Sinai sunrise was not
on the list. A customer asked for it, we tried, and it has been our
best seller ever since.</p>
      <h2>What makes it special</h2>
      <p>Three things: care, time and good ingredients. We never rush
a hike.</p>
      <aside class="callout"><strong>Tip:</strong> Ask for it early
in the day, it sells out by the afternoon.</aside>
      <h2>Try it yourself</h2>
      <p>Mount Sinai sunrise is available now for 400 EGP. <a
href="hikes.html">See all hikes</a>.</p>
      <footer class="tags">Tags: <a href="#">trekking</a> <a
href="#">news</a></footer>
    </article>
  </main>
</body>
</html>
```

Project 483: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
```

```
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.post { font-family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; line-height: 1.2; }
h1 { font-size: clamp(1.8rem, 4vw, 2.6rem); margin: .2rem 0 .5rem; }
.meta { color: var(--muted); font-family: system-ui, sans-serif; font-
size: .9rem; }
.lead { font-size: 1.25rem; color: var(--muted); }
figure { margin: 2rem 0; }
img { width: 100%; height: auto; border-radius: 12px; }
figcaption { font-size: .9rem; color: var(--muted); font-family:
system-ui, sans-serif; margin-top: .4rem; }
.callout { background: var(--accent); border-left: 4px solid var(--
brand); padding: 1rem 1.25rem; margin: 1.5rem 0; border-radius: 0
10px 10px 0; }
.tags { margin-top: 2rem; padding-top: 1rem; border-top: 1px solid
var(--line); font-family: system-ui, sans-serif; font-size: .9rem; }
.tags a { display: inline-block; background: var(--accent); padding: .
1rem .6rem; border-radius: 999px; text-decoration: none; color: var(--
ink); margin-right: .3rem; }
```

Project 483 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Why we love Mount Sinai sunrise - Sinai Trekking Club blog</...	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="post">	A self-contained piece: card, post, product.
<header>	Introductory content: logo, title, navigation.
<p class="meta"><time datetime="2026-09-01">1 September 2026</time>...	A paragraph of text.
Why we love Mount Sinai sunrise	The main heading; only one per page.
<figure>	Self-contained media with an optional caption.

Line	What it does
<img src="images/trekking-1.jpg" alt="Mount Sinai sunrise" width="1...	An image; alt describes it, width and height reserve space before it loads.
<figcaption>Mount Sinai sunrise, photographed in Saint Catherine.</...	Caption for the figure.
How it started	Second-level heading for a section.
<aside class="callout">Tip: Ask for it early in th...	Content related to, but separate from, the main content.
<p>Mount Sinai sunrise is available now for 400 EGP. <a href="hikes...	A hyperlink; href gives the destination.
<footer class="tags">Tags: trekking <a href="#">new...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.

Declaration	What it does
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.
font-size: clamp(1.8rem, 4vw, 2.6rem);	A fluid value between a minimum and a maximum, based on the middle expression.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
background: var(--accent);	Background colour or image.
border-left: 4px solid var(--brand);	A thick left border used as an accent stripe.
border-radius: 0 10px 10px 0;	The line around the element: width, style and colour.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Date has a datetime attribute
- One h1, then h2s
- Figure caption present
- Line length comfortable

Exercises

1. Add a table of contents generated from the h2 ids.
2. Add an author box with an image.
3. Add 'related posts' cards at the end.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 484: Blog article for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 2 | Files: index.html, styles.css

Brief

Write a full blog post with article header metadata, lead paragraph, hero figure, sections, a callout aside and tags in the footer.

Learning goals

- Use article, header, footer, aside and time inside a post
- Set up readable long-form typography
- Style a callout and tag pills

Elements and CSS used

HTML elements	CSS features
article, header, time, h1, p, figure, img, figcaption, h2, aside, strong, footer, a	font-family pairs, clamp(), border-left, border-radius partial, display: inline-block

Build guide

1. Write the article structure with header (meta, h1, lead).
2. Add the figure with caption.
3. Write two or three h2 sections.
4. Add the callout aside and the tag footer.
5. Set serif body / sans headings and a 44rem measure.
6. Style the callout and tags.

Project 484: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Why we love Portrait session - Horizon Photography blog</
title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="post">
      <header>
        <p class="meta"><time datetime="2026-09-01">1 September 2026</
time> &middot; by Adham Nabil &middot; 4 min read</p>
        <h1>Why we love Portrait session</h1>
        <p class="lead">One hour, 20 edited photos. Here is the story
behind one of our favourite sessions.</p>
      </header>
      <figure>
        <img src="images/photo-1.jpg" alt="Portrait session"
width="1200" height="700">
        <figcaption>Portrait session, photographed in Maadi.</
figcaption>
      </figure>
      <h2>How it started</h2>
      <p>When Horizon Photography opened, Portrait session was not on
the list. A customer asked for it, we tried, and it has been our best
seller ever since.</p>
      <h2>What makes it special</h2>
      <p>Three things: care, time and good ingredients. We never rush
a session.</p>
      <aside class="callout"><strong>Tip:</strong> Ask for it early
in the day, it sells out by the afternoon.</aside>
      <h2>Try it yourself</h2>
      <p>Portrait session is available now for 1200 EGP. <a
href="sessions.html">See all sessions</a>.</p>
      <footer class="tags">Tags: <a href="#">photo</a> <a
href="#">news</a></footer>
    </article>
  </main>
</body>
</html>
```

Project 484: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
```

```
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.post { font-family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; line-height: 1.2; }
h1 { font-size: clamp(1.8rem, 4vw, 2.6rem); margin: .2rem 0 .5rem; }
.meta { color: var(--muted); font-family: system-ui, sans-serif; font-
size: .9rem; }
.lead { font-size: 1.25rem; color: var(--muted); }
figure { margin: 2rem 0; }
img { width: 100%; height: auto; border-radius: 12px; }
figcaption { font-size: .9rem; color: var(--muted); font-family:
system-ui, sans-serif; margin-top: .4rem; }
.callout { background: var(--accent); border-left: 4px solid var(--
brand); padding: 1rem 1.25rem; margin: 1.5rem 0; border-radius: 0
10px 10px 0; }
.tags { margin-top: 2rem; padding-top: 1rem; border-top: 1px solid
var(--line); font-family: system-ui, sans-serif; font-size: .9rem; }
.tags a { display: inline-block; background: var(--accent); padding: .
1rem .6rem; border-radius: 999px; text-decoration: none; color: var(--
ink); margin-right: .3rem; }
```

Project 484 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Why we love Portrait session - Horizon Photography blog</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="post">	A self-contained piece: card, post, product.
<header>	Introductory content: logo, title, navigation.
<p class="meta"><time datetime="2026-09-01">1 September 2026</time>...	A paragraph of text.
Why we love Portrait session	The main heading; only one per page.
<figure>	Self-contained media with an optional caption.

Line	What it does
<img src="images/photo-1.jpg" alt="Portrait session" width="1200" h...	An image; alt describes it, width and height reserve space before it loads.
<figcaption>Portrait session, photographed in Maadi.</figcaption>	Caption for the figure.
How it started	Second-level heading for a section.
<aside class="callout">Tip: Ask for it early in th...	Content related to, but separate from, the main content.
<p>Portrait session is available now for 1200 EGP. <a href="session...	A hyperlink; href gives the destination.
<footer class="tags">Tags: photo <a href="#">news</...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.

Declaration	What it does
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.
font-size: clamp(1.8rem, 4vw, 2.6rem);	A fluid value between a minimum and a maximum, based on the middle expression.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
background: var(--accent);	Background colour or image.
border-left: 4px solid var(--brand);	A thick left border used as an accent stripe.
border-radius: 0 10px 10px 0;	The line around the element: width, style and colour.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Date has a datetime attribute
- One h1, then h2s
- Figure caption present
- Line length comfortable

Exercises

1. Add a table of contents generated from the h2 ids.
2. Add an author box with an image.
3. Add 'related posts' cards at the end.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 485: Blog article for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 2 | Files: index.html, styles.css

Brief

Write a full blog post with article header metadata, lead paragraph, hero figure, sections, a callout aside and tags in the footer.

Learning goals

- Use article, header, footer, aside and time inside a post
- Set up readable long-form typography
- Style a callout and tag pills

Elements and CSS used

HTML elements	CSS features
article, header, time, h1, p, figure, img, figcaption, h2, aside, strong, footer, a	font-family pairs, clamp(), border-left, border-radius partial, display: inline-block

Build guide

1. Write the article structure with header (meta, h1, lead).
2. Add the figure with caption.
3. Write two or three h2 sections.
4. Add the callout aside and the tag footer.
5. Set serif body / sans headings and a 44rem measure.
6. Style the callout and tags.

Project 485: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Why we love Dotted notebook - Papyrus Stationery blog</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="post">
      <header>
        <p class="meta"><time datetime="2026-09-01">1 September 2026</
time> &middot; by Dina Fathy &middot; 4 min read</p>
        <h1>Why we love Dotted notebook</h1>
        <p class="lead">A5, 160 pages. Here is the story behind one
of our favourite products.</p>
      </header>
      <figure>
        <img src="images/stationery-1.jpg" alt="Dotted notebook"
width="1200" height="700">
        <figcaption>Dotted notebook, photographed in Heliopolis.</
figcaption>
      </figure>
      <h2>How it started</h2>
      <p>When Papyrus Stationery opened, Dotted notebook was not on
the list. A customer asked for it, we tried, and it has been our best
seller ever since.</p>
      <h2>What makes it special</h2>
      <p>Three things: care, time and good ingredients. We never rush
a product.</p>
      <aside class="callout"><strong>Tip:</strong> Ask for it early
in the day, it sells out by the afternoon.</aside>
      <h2>Try it yourself</h2>
      <p>Dotted notebook is available now for 140 EGP. <a
href="products.html">See all products</a>.</p>
      <footer class="tags">Tags: <a href="#">stationery</a> <a
href="#">news</a></footer>
    </article>
  </main>
</body>
</html>
```

Project 485: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
```

```
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.post { font-family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; line-height: 1.2; }
h1 { font-size: clamp(1.8rem, 4vw, 2.6rem); margin: .2rem 0 .5rem; }
.meta { color: var(--muted); font-family: system-ui, sans-serif; font-
size: .9rem; }
.lead { font-size: 1.25rem; color: var(--muted); }
figure { margin: 2rem 0; }
img { width: 100%; height: auto; border-radius: 12px; }
figcaption { font-size: .9rem; color: var(--muted); font-family:
system-ui, sans-serif; margin-top: .4rem; }
.callout { background: var(--accent); border-left: 4px solid var(--
brand); padding: 1rem 1.25rem; margin: 1.5rem 0; border-radius: 0
10px 10px 0; }
.tags { margin-top: 2rem; padding-top: 1rem; border-top: 1px solid
var(--line); font-family: system-ui, sans-serif; font-size: .9rem; }
.tags a { display: inline-block; background: var(--accent); padding: .
1rem .6rem; border-radius: 999px; text-decoration: none; color: var(--
ink); margin-right: .3rem; }
```

Project 485 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Why we love Dotted notebook - Papyrus Stationery blog</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="post">	A self-contained piece: card, post, product.
<header>	Introductory content: logo, title, navigation.
<p class="meta"><time datetime="2026-09-01">1 September 2026</time>...	A paragraph of text.
Why we love Dotted notebook	The main heading; only one per page.
<figure>	Self-contained media with an optional caption.

Line	What it does
<img src="images/stationery-1.jpg" alt="Dotted notebook" width="120...	An image; alt describes it, width and height reserve space before it loads.
<figcaption>Dotted notebook, photographed in Heliopolis.</figcaption>	Caption for the figure.
How it started	Second-level heading for a section.
<aside class="callout">Tip: Ask for it early in th...	Content related to, but separate from, the main content.
<p>Dotted notebook is available now for 140 EGP. <a href="products....	A hyperlink; href gives the destination.
<footer class="tags">Tags: stationery <a href="#">n...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.

Declaration	What it does
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.
font-size: clamp(1.8rem, 4vw, 2.6rem);	A fluid value between a minimum and a maximum, based on the middle expression.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
background: var(--accent);	Background colour or image.
border-left: 4px solid var(--brand);	A thick left border used as an accent stripe.
border-radius: 0 10px 10px 0;	The line around the element: width, style and colour.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Date has a datetime attribute
- One h1, then h2s
- Figure caption present
- Line length comfortable

Exercises

1. Add a table of contents generated from the h2 ids.
2. Add an author box with an image.
3. Add 'related posts' cards at the end.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 486: Blog article for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 2 | Files: index.html, styles.css

Brief

Write a full blog post with article header metadata, lead paragraph, hero figure, sections, a callout aside and tags in the footer.

Learning goals

- Use article, header, footer, aside and time inside a post
- Set up readable long-form typography
- Style a callout and tag pills

Elements and CSS used

HTML elements	CSS features
article, header, time, h1, p, figure, img, figcaption, h2, aside, strong, footer, a	font-family pairs, clamp(), border-left, border-radius partial, display: inline-block

Build guide

1. Write the article structure with header (meta, h1, lead).
2. Add the figure with caption.
3. Write two or three h2 sections.
4. Add the callout aside and the tag footer.
5. Set serif body / sans headings and a 44rem measure.
6. Style the callout and tags.

Project 486: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Why we love Monstera - Oasis Plant Nursery blog</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="post">
      <header>
        <p class="meta"><time datetime="2026-09-01">1 September 2026</
time> &middot; by Hossam Ali &middot; 4 min read</p>
        <h1>Why we love Monstera</h1>
        <p class="lead">Large leaves, easy care. Here is the story
behind one of our favourite plants.</p>
      </header>
      <figure>
        <img src="images/plants-1.jpg" alt="Monstera" width="1200"
height="700">
        <figcaption>Monstera, photographed in Sheikh Zayed.</
figcaption>
      </figure>
      <h2>How it started</h2>
      <p>When Oasis Plant Nursery opened, Monstera was not on the
list. A customer asked for it, we tried, and it has been our best
seller ever since.</p>
      <h2>What makes it special</h2>
      <p>Three things: care, time and good ingredients. We never rush
a plant.</p>
      <aside class="callout"><strong>Tip:</strong> Ask for it early
in the day, it sells out by the afternoon.</aside>
      <h2>Try it yourself</h2>
      <p>Monstera is available now for 250 EGP. <a href="plants.
html">See all plants</a>.</p>
      <footer class="tags">Tags: <a href="#">plants</a> <a
href="#">news</a></footer>
    </article>
  </main>
</body>
</html>
```

Project 486: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
```

```
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.post { font-family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; line-height: 1.2; }
h1 { font-size: clamp(1.8rem, 4vw, 2.6rem); margin: .2rem 0 .5rem; }
.meta { color: var(--muted); font-family: system-ui, sans-serif; font-
size: .9rem; }
.lead { font-size: 1.25rem; color: var(--muted); }
figure { margin: 2rem 0; }
img { width: 100%; height: auto; border-radius: 12px; }
figcaption { font-size: .9rem; color: var(--muted); font-family:
system-ui, sans-serif; margin-top: .4rem; }
.callout { background: var(--accent); border-left: 4px solid var(--
brand); padding: 1rem 1.25rem; margin: 1.5rem 0; border-radius: 0
10px 10px 0; }
.tags { margin-top: 2rem; padding-top: 1rem; border-top: 1px solid
var(--line); font-family: system-ui, sans-serif; font-size: .9rem; }
.tags a { display: inline-block; background: var(--accent); padding: .
1rem .6rem; border-radius: 999px; text-decoration: none; color: var(--
ink); margin-right: .3rem; }
```

Project 486 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Why we love Monstera - Oasis Plant Nursery blog</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="post">	A self-contained piece: card, post, product.
<header>	Introductory content: logo, title, navigation.
<p class="meta"><time datetime="2026-09-01">1 September 2026</time>...	A paragraph of text.
Why we love Monstera	The main heading; only one per page.
<figure>	Self-contained media with an optional caption.

Line	What it does
<img src="images/plants-1.jpg" alt="Monstera" width="1200" height="...	An image; alt describes it, width and height reserve space before it loads.
<figcaption>Monstera, photographed in Sheikh Zayed.</figcaption>	Caption for the figure.
How it started	Second-level heading for a section.
<aside class="callout">Tip: Ask for it early in th...	Content related to, but separate from, the main content.
<p>Monstera is available now for 250 EGP. <a href="plants.html">See...	A hyperlink; href gives the destination.
<footer class="tags">Tags: plants <a href="#">news<...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.

Declaration	What it does
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.
font-size: clamp(1.8rem, 4vw, 2.6rem);	A fluid value between a minimum and a maximum, based on the middle expression.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
background: var(--accent);	Background colour or image.
border-left: 4px solid var(--brand);	A thick left border used as an accent stripe.
border-radius: 0 10px 10px 0;	The line around the element: width, style and colour.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Date has a datetime attribute
- One h1, then h2s
- Figure caption present
- Line length comfortable

Exercises

1. Add a table of contents generated from the h2 ids.
2. Add an author box with an image.
3. Add 'related posts' cards at the end.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 487: Blog article for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 2 | Files: index.html, styles.css

Brief

Write a full blog post with article header metadata, lead paragraph, hero figure, sections, a callout aside and tags in the footer.

Learning goals

- Use article, header, footer, aside and time inside a post
- Set up readable long-form typography
- Style a callout and tag pills

Elements and CSS used

HTML elements	CSS features
article, header, time, h1, p, figure, img, figcaption, h2, aside, strong, footer, a	font-family pairs, clamp(), border-left, border-radius partial, display: inline-block

Build guide

1. Write the article structure with header (meta, h1, lead).
2. Add the figure with caption.
3. Write two or three h2 sections.
4. Add the callout aside and the tag footer.
5. Set serif body / sans headings and a 44rem measure.
6. Style the callout and tags.

Project 487: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Why we love Oak dining table - Cedar Furniture blog</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="post">
      <header>
        <p class="meta"><time datetime="2026-09-01">1 September 2026</
time> &middot; by Tarek Lotfy &middot; 4 min read</p>
        <h1>Why we love Oak dining table</h1>
        <p class="lead">Seats six. Here is the story behind one of
our favourite pieces.</p>
      </header>
      <figure>
        <img src="images/furniture-1.jpg" alt="Oak dining table"
width="1200" height="700">
        <figcaption>Oak dining table, photographed in Damietta.</
figcaption>
      </figure>
      <h2>How it started</h2>
      <p>When Cedar Furniture opened, Oak dining table was not on the
list. A customer asked for it, we tried, and it has been our best
seller ever since.</p>
      <h2>What makes it special</h2>
      <p>Three things: care, time and good ingredients. We never rush
a piece.</p>
      <aside class="callout"><strong>Tip:</strong> Ask for it early
in the day, it sells out by the afternoon.</aside>
      <h2>Try it yourself</h2>
      <p>Oak dining table is available now for 9500 EGP. <a
href="pieces.html">See all pieces</a>.</p>
      <footer class="tags">Tags: <a href="#">furniture</a> <a
href="#">news</a></footer>
    </article>
  </main>
</body>
</html>
```

Project 487: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
```

```
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.post { font-family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; line-height: 1.2; }
h1 { font-size: clamp(1.8rem, 4vw, 2.6rem); margin: .2rem 0 .5rem; }
.meta { color: var(--muted); font-family: system-ui, sans-serif; font-
size: .9rem; }
.lead { font-size: 1.25rem; color: var(--muted); }
figure { margin: 2rem 0; }
img { width: 100%; height: auto; border-radius: 12px; }
figcaption { font-size: .9rem; color: var(--muted); font-family:
system-ui, sans-serif; margin-top: .4rem; }
.callout { background: var(--accent); border-left: 4px solid var(--
brand); padding: 1rem 1.25rem; margin: 1.5rem 0; border-radius: 0
10px 10px 0; }
.tags { margin-top: 2rem; padding-top: 1rem; border-top: 1px solid
var(--line); font-family: system-ui, sans-serif; font-size: .9rem; }
.tags a { display: inline-block; background: var(--accent); padding: .
1rem .6rem; border-radius: 999px; text-decoration: none; color: var(--
ink); margin-right: .3rem; }
```

Project 487 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Why we love Oak dining table - Cedar Furniture blog</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="post">	A self-contained piece: card, post, product.
<header>	Introductory content: logo, title, navigation.
<p class="meta"><time datetime="2026-09-01">1 September 2026</time>...	A paragraph of text.
Why we love Oak dining table	The main heading; only one per page.
<figure>	Self-contained media with an optional caption.

Line	What it does
<img src="images/furniture-1.jpg" alt="Oak dining table" width="120...	An image; alt describes it, width and height reserve space before it loads.
<figcaption>Oak dining table, photographed in Damietta.</figcaption>	Caption for the figure.
How it started	Second-level heading for a section.
<aside class="callout">Tip: Ask for it early in th...	Content related to, but separate from, the main content.
<p>Oak dining table is available now for 9500 EGP. <a href="pieces....	A hyperlink; href gives the destination.
<footer class="tags">Tags: furniture <a href="#">ne...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.

Declaration	What it does
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.
font-size: clamp(1.8rem, 4vw, 2.6rem);	A fluid value between a minimum and a maximum, based on the middle expression.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
background: var(--accent);	Background colour or image.
border-left: 4px solid var(--brand);	A thick left border used as an accent stripe.
border-radius: 0 10px 10px 0;	The line around the element: width, style and colour.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Date has a datetime attribute
- One h1, then h2s
- Figure caption present
- Line length comfortable

Exercises

1. Add a table of contents generated from the h2 ids.
2. Add an author box with an image.
3. Add 'related posts' cards at the end.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 488: Blog article for Byte Repair

Theme: Byte Repair (Nasr City) | Level 2 | Files: index.html, styles.css

Brief

Write a full blog post with article header metadata, lead paragraph, hero figure, sections, a callout aside and tags in the footer.

Learning goals

- Use article, header, footer, aside and time inside a post
- Set up readable long-form typography
- Style a callout and tag pills

Elements and CSS used

HTML elements	CSS features
article, header, time, h1, p, figure, img, figcaption, h2, aside, strong, footer, a	font-family pairs, clamp(), border-left, border-radius partial, display: inline-block

Build guide

1. Write the article structure with header (meta, h1, lead).
2. Add the figure with caption.
3. Write two or three h2 sections.
4. Add the callout aside and the tag footer.
5. Set serif body / sans headings and a 44rem measure.
6. Style the callout and tags.

Project 488: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Why we love Screen replacement - Byte Repair blog</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="post">
      <header>
        <p class="meta"><time datetime="2026-09-01">1 September 2026</
time> &middot; by Mostafa Gamal &middot; 4 min read</p>
        <h1>Why we love Screen replacement</h1>
        <p class="lead">Most phones, 1 hour. Here is the story behind
one of our favourite repairs.</p>
      </header>
      <figure>
        <img src="images/repair-1.jpg" alt="Screen replacement"
width="1200" height="700">
        <figcaption>Screen replacement, photographed in Nasr City.</
figcaption>
      </figure>
      <h2>How it started</h2>
      <p>When Byte Repair opened, Screen replacement was not on the
list. A customer asked for it, we tried, and it has been our best
seller ever since.</p>
      <h2>What makes it special</h2>
      <p>Three things: care, time and good ingredients. We never rush
a repair.</p>
      <aside class="callout"><strong>Tip:</strong> Ask for it early
in the day, it sells out by the afternoon.</aside>
      <h2>Try it yourself</h2>
      <p>Screen replacement is available now for From 800 EGP. <a
href="repairs.html">See all repairs</a>.</p>
      <footer class="tags">Tags: <a href="#">repair</a> <a
href="#">news</a></footer>
    </article>
  </main>
</body>
</html>
```

Project 488: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
```

```
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.post { font-family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; line-height: 1.2; }
h1 { font-size: clamp(1.8rem, 4vw, 2.6rem); margin: .2rem 0 .5rem; }
.meta { color: var(--muted); font-family: system-ui, sans-serif; font-
size: .9rem; }
.lead { font-size: 1.25rem; color: var(--muted); }
figure { margin: 2rem 0; }
img { width: 100%; height: auto; border-radius: 12px; }
figcaption { font-size: .9rem; color: var(--muted); font-family:
system-ui, sans-serif; margin-top: .4rem; }
.callout { background: var(--accent); border-left: 4px solid var(--
brand); padding: 1rem 1.25rem; margin: 1.5rem 0; border-radius: 0
10px 10px 0; }
.tags { margin-top: 2rem; padding-top: 1rem; border-top: 1px solid
var(--line); font-family: system-ui, sans-serif; font-size: .9rem; }
.tags a { display: inline-block; background: var(--accent); padding: .
1rem .6rem; border-radius: 999px; text-decoration: none; color: var(--
ink); margin-right: .3rem; }
```

Project 488 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Why we love Screen replacement - Byte Repair blog</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="post">	A self-contained piece: card, post, product.
<header>	Introductory content: logo, title, navigation.
<p class="meta"><time datetime="2026-09-01">1 September 2026</time>...	A paragraph of text.
Why we love Screen replacement	The main heading; only one per page.
<figure>	Self-contained media with an optional caption.

Line	What it does
<img src="images/repair-1.jpg" alt="Screen replacement" width="1200...	An image; alt describes it, width and height reserve space before it loads.
<figcaption>Screen replacement, photographed in Nasr City.</figcapt...	Caption for the figure.
How it started	Second-level heading for a section.
<aside class="callout">Tip: Ask for it early in th...	Content related to, but separate from, the main content.
<p>Screen replacement is available now for From 800 EGP. <a href="r...	A hyperlink; href gives the destination.
<footer class="tags">Tags: repair <a href="#">news<...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.

Declaration	What it does
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.
font-size: clamp(1.8rem, 4vw, 2.6rem);	A fluid value between a minimum and a maximum, based on the middle expression.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
background: var(--accent);	Background colour or image.
border-left: 4px solid var(--brand);	A thick left border used as an accent stripe.
border-radius: 0 10px 10px 0;	The line around the element: width, style and colour.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Date has a datetime attribute
- One h1, then h2s
- Figure caption present
- Line length comfortable

Exercises

1. Add a table of contents generated from the h2 ids.
2. Add an author box with an image.
3. Add 'related posts' cards at the end.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 489: Blog article for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 2 | Files: index.html, styles.css

Brief

Write a full blog post with article header metadata, lead paragraph, hero figure, sections, a callout aside and tags in the footer.

Learning goals

- Use article, header, footer, aside and time inside a post
- Set up readable long-form typography
- Style a callout and tag pills

Elements and CSS used

HTML elements	CSS features
article, header, time, h1, p, figure, img, figcaption, h2, aside, strong, footer, a	font-family pairs, clamp(), border-left, border-radius partial, display: inline-block

Build guide

1. Write the article structure with header (meta, h1, lead).
2. Add the figure with caption.
3. Write two or three h2 sections.
4. Add the callout aside and the tag footer.
5. Set serif body / sans headings and a 44rem measure.
6. Style the callout and tags.

Project 489: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Why we love Full grooming - Sahara Pet Care blog</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="post">
      <header>
        <p class="meta"><time datetime="2026-09-01">1 September 2026</
time> &middot; by Rana Ibrahim &middot; 4 min read</p>
        <h1>Why we love Full grooming</h1>
        <p class="lead">Bath, cut and nails. Here is the story behind
one of our favourite services.</p>
      </header>
      <figure>
        <img src="images/pets-1.jpg" alt="Full grooming" width="1200"
height="700">
        <figcaption>Full grooming, photographed in New Cairo.</
figcaption>
      </figure>
      <h2>How it started</h2>
      <p>When Sahara Pet Care opened, Full grooming was not on the
list. A customer asked for it, we tried, and it has been our best
seller ever since.</p>
      <h2>What makes it special</h2>
      <p>Three things: care, time and good ingredients. We never rush
a service.</p>
      <aside class="callout"><strong>Tip:</strong> Ask for it early
in the day, it sells out by the afternoon.</aside>
      <h2>Try it yourself</h2>
      <p>Full grooming is available now for 400 EGP. <a
href="services.html">See all services</a>.</p>
      <footer class="tags">Tags: <a href="#">pets</a> <a
href="#">news</a></footer>
    </article>
  </main>
</body>
</html>
```

Project 489: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
```

```
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.post { font-family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; line-height: 1.2; }
h1 { font-size: clamp(1.8rem, 4vw, 2.6rem); margin: .2rem 0 .5rem; }
.meta { color: var(--muted); font-family: system-ui, sans-serif; font-
size: .9rem; }
.lead { font-size: 1.25rem; color: var(--muted); }
figure { margin: 2rem 0; }
img { width: 100%; height: auto; border-radius: 12px; }
figcaption { font-size: .9rem; color: var(--muted); font-family:
system-ui, sans-serif; margin-top: .4rem; }
.callout { background: var(--accent); border-left: 4px solid var(--
brand); padding: 1rem 1.25rem; margin: 1.5rem 0; border-radius: 0
10px 10px 0; }
.tags { margin-top: 2rem; padding-top: 1rem; border-top: 1px solid
var(--line); font-family: system-ui, sans-serif; font-size: .9rem; }
.tags a { display: inline-block; background: var(--accent); padding: .
1rem .6rem; border-radius: 999px; text-decoration: none; color: var(--
ink); margin-right: .3rem; }
```

Project 489 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Why we love Full grooming - Sahara Pet Care blog</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="post">	A self-contained piece: card, post, product.
<header>	Introductory content: logo, title, navigation.
<p class="meta"><time datetime="2026-09-01">1 September 2026</time>...	A paragraph of text.
Why we love Full grooming	The main heading; only one per page.
<figure>	Self-contained media with an optional caption.
<img src="images/pets-1.jpg" alt="Full grooming" width="1200" heigh...	An image; alt describes it, width and height reserve space before it loads.

Line	What it does
<figcaption>Full grooming, photographed in New Cairo.</figcaption>	Caption for the figure.
How it started	Second-level heading for a section.
<aside class="callout">Tip: Ask for it early in th...	Content related to, but separate from, the main content.
<p>Full grooming is available now for 400 EGP. <a href="services.ht...	A hyperlink; href gives the destination.
<footer class="tags">Tags: pets <a href="#">news</a...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.

Declaration	What it does
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.
font-size: clamp(1.8rem, 4vw, 2.6rem);	A fluid value between a minimum and a maximum, based on the middle expression.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
background: var(--accent);	Background colour or image.
border-left: 4px solid var(--brand);	A thick left border used as an accent stripe.
border-radius: 0 10px 10px 0;	The line around the element: width, style and colour.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Date has a datetime attribute
- One h1, then h2s
- Figure caption present

- Line length comfortable

Exercises

1. Add a table of contents generated from the h2 ids.
2. Add an author box with an image.
3. Add 'related posts' cards at the end.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 490: Blog article for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Write a full blog post with article header metadata, lead paragraph, hero figure, sections, a callout aside and tags in the footer.

Learning goals

- Use article, header, footer, aside and time inside a post
- Set up readable long-form typography
- Style a callout and tag pills

Elements and CSS used

HTML elements	CSS features
article, header, time, h1, p, figure, img, figcaption, h2, aside, strong, footer, a	font-family pairs, clamp(), border-left, border-radius partial, display: inline-block

Build guide

1. Write the article structure with header (meta, h1, lead).
2. Add the figure with caption.
3. Write two or three h2 sections.
4. Add the callout aside and the tag footer.
5. Set serif body / sans headings and a 44rem measure.
6. Style the callout and tags.

Project 490: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Why we love Taster session - Alexandria Sailing School blog</
title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="post">
      <header>
        <p class="meta"><time datetime="2026-09-01">1 September 2026</
time> &middot; by Amr Selim &middot; 4 min read</p>
        <h1>Why we love Taster session</h1>
        <p class="lead">Two hours on the water. Here is the story
behind one of our favourite lessons.</p>
      </header>
      <figure>
        <img src="images/sailing-1.jpg" alt="Taster session"
width="1200" height="700">
        <figcaption>Taster session, photographed in Alexandria.</
figcaption>
      </figure>
      <h2>How it started</h2>
      <p>When Alexandria Sailing School opened, Taster session was
not on the list. A customer asked for it, we tried, and it has been
our best seller ever since.</p>
      <h2>What makes it special</h2>
      <p>Three things: care, time and good ingredients. We never rush
a lesson.</p>
      <aside class="callout"><strong>Tip:</strong> Ask for it early
in the day, it sells out by the afternoon.</aside>
      <h2>Try it yourself</h2>
      <p>Taster session is available now for 500 EGP. <a
href="lessons.html">See all lessons</a>.</p>
      <footer class="tags">Tags: <a href="#">sailing</a> <a
href="#">news</a></footer>
    </article>
  </main>
</body>
</html>
```

Project 490: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
```

```
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.post { font-family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; line-height: 1.2; }
h1 { font-size: clamp(1.8rem, 4vw, 2.6rem); margin: .2rem 0 .5rem; }
.meta { color: var(--muted); font-family: system-ui, sans-serif; font-
size: .9rem; }
.lead { font-size: 1.25rem; color: var(--muted); }
figure { margin: 2rem 0; }
img { width: 100%; height: auto; border-radius: 12px; }
figcaption { font-size: .9rem; color: var(--muted); font-family:
system-ui, sans-serif; margin-top: .4rem; }
.callout { background: var(--accent); border-left: 4px solid var(--
brand); padding: 1rem 1.25rem; margin: 1.5rem 0; border-radius: 0
10px 10px 0; }
.tags { margin-top: 2rem; padding-top: 1rem; border-top: 1px solid
var(--line); font-family: system-ui, sans-serif; font-size: .9rem; }
.tags a { display: inline-block; background: var(--accent); padding: .
1rem .6rem; border-radius: 999px; text-decoration: none; color: var(--
ink); margin-right: .3rem; }
```

Project 490 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Why we love Taster session - Alexandria Sailing School blog<...	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="post">	A self-contained piece: card, post, product.
<header>	Introductory content: logo, title, navigation.
<p class="meta"><time datetime="2026-09-01">1 September 2026</time>...	A paragraph of text.
Why we love Taster session	The main heading; only one per page.
<figure>	Self-contained media with an optional caption.

Line	What it does
<img src="images/sailing-1.jpg" alt="Taster session" width="1200" h...	An image; alt describes it, width and height reserve space before it loads.
<figcaption>Taster session, photographed in Alexandria.</figcaption>	Caption for the figure.
How it started	Second-level heading for a section.
<aside class="callout">Tip: Ask for it early in th...	Content related to, but separate from, the main content.
<p>Taster session is available now for 500 EGP. <a href="lessons.ht...	A hyperlink; href gives the destination.
<footer class="tags">Tags: sailing <a href="#">news...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.

Declaration	What it does
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.
font-size: clamp(1.8rem, 4vw, 2.6rem);	A fluid value between a minimum and a maximum, based on the middle expression.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
background: var(--accent);	Background colour or image.
border-left: 4px solid var(--brand);	A thick left border used as an accent stripe.
border-radius: 0 10px 10px 0;	The line around the element: width, style and colour.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Date has a datetime attribute
- One h1, then h2s
- Figure caption present
- Line length comfortable

Exercises

1. Add a table of contents generated from the h2 ids.
2. Add an author box with an image.
3. Add 'related posts' cards at the end.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 491: Blog article for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Write a full blog post with article header metadata, lead paragraph, hero figure, sections, a callout aside and tags in the footer.

Learning goals

- Use article, header, footer, aside and time inside a post
- Set up readable long-form typography
- Style a callout and tag pills

Elements and CSS used

HTML elements	CSS features
article, header, time, h1, p, figure, img, figcaption, h2, aside, strong, footer, a	font-family pairs, clamp(), border-left, border-radius partial, display: inline-block

Build guide

1. Write the article structure with header (meta, h1, lead).
2. Add the figure with caption.
3. Write two or three h2 sections.
4. Add the callout aside and the tag footer.
5. Set serif body / sans headings and a 44rem measure.
6. Style the callout and tags.

Project 491: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Why we love Lotus pendant - Habiba Handmade Jewellery blog</
title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="post">
      <header>
        <p class="meta"><time datetime="2026-09-01">1 September 2026</
time> &middot; by Habiba Saleh &middot; 4 min read</p>
        <h1>Why we love Lotus pendant</h1>
        <p class="lead">Sterling silver. Here is the story behind one
of our favourite items.</p>
      </header>
      <figure>
        <img src="images/jewellery-1.jpg" alt="Lotus pendant"
width="1200" height="700">
        <figcaption>Lotus pendant, photographed in Aswan.</figcaption>
      </figure>
      <h2>How it started</h2>
      <p>When Habiba Handmade Jewellery opened, Lotus pendant was not
on the list. A customer asked for it, we tried, and it has been our
best seller ever since.</p>
      <h2>What makes it special</h2>
      <p>Three things: care, time and good ingredients. We never rush
a item.</p>
      <aside class="callout"><strong>Tip:</strong> Ask for it early
in the day, it sells out by the afternoon.</aside>
      <h2>Try it yourself</h2>
      <p>Lotus pendant is available now for 650 EGP. <a href="items.
html">See all items</a>.</p>
      <footer class="tags">Tags: <a href="#">jewellery</a> <a
href="#">news</a></footer>
    </article>
  </main>
</body>
</html>
```

Project 491: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
```

```
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.post { font-family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; line-height: 1.2; }
h1 { font-size: clamp(1.8rem, 4vw, 2.6rem); margin: .2rem 0 .5rem; }
.meta { color: var(--muted); font-family: system-ui, sans-serif; font-
size: .9rem; }
.lead { font-size: 1.25rem; color: var(--muted); }
figure { margin: 2rem 0; }
img { width: 100%; height: auto; border-radius: 12px; }
figcaption { font-size: .9rem; color: var(--muted); font-family:
system-ui, sans-serif; margin-top: .4rem; }
.callout { background: var(--accent); border-left: 4px solid var(--
brand); padding: 1rem 1.25rem; margin: 1.5rem 0; border-radius: 0
10px 10px 0; }
.tags { margin-top: 2rem; padding-top: 1rem; border-top: 1px solid
var(--line); font-family: system-ui, sans-serif; font-size: .9rem; }
.tags a { display: inline-block; background: var(--accent); padding: .
1rem .6rem; border-radius: 999px; text-decoration: none; color: var(--
ink); margin-right: .3rem; }
```

Project 491 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Why we love Lotus pendant - Habiba Handmade Jewellery blog<//...	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="post">	A self-contained piece: card, post, product.
<header>	Introductory content: logo, title, navigation.
<p class="meta"><time datetime="2026-09-01">1 September 2026</time>...	A paragraph of text.
Why we love Lotus pendant	The main heading; only one per page.
<figure>	Self-contained media with an optional caption.

Line	What it does
<img src="images/jewellery-1.jpg" alt="Lotus pendant" width="1200" ...	An image; alt describes it, width and height reserve space before it loads.
<figcaption>Lotus pendant, photographed in Aswan.</figcaption>	Caption for the figure.
How it started	Second-level heading for a section.
<aside class="callout">Tip: Ask for it early in th...	Content related to, but separate from, the main content.
<p>Lotus pendant is available now for 650 EGP. <a href="items.html"...	A hyperlink; href gives the destination.
<footer class="tags">Tags: jewellery <a href="#">ne...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.

Declaration	What it does
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.
font-size: clamp(1.8rem, 4vw, 2.6rem);	A fluid value between a minimum and a maximum, based on the middle expression.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
background: var(--accent);	Background colour or image.
border-left: 4px solid var(--brand);	A thick left border used as an accent stripe.
border-radius: 0 10px 10px 0;	The line around the element: width, style and colour.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Date has a datetime attribute
- One h1, then h2s
- Figure caption present
- Line length comfortable

Exercises

1. Add a table of contents generated from the h2 ids.
2. Add an author box with an image.
3. Add 'related posts' cards at the end.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 492: Blog article for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 2 | Files: index.html, styles.css

Brief

Write a full blog post with article header metadata, lead paragraph, hero figure, sections, a callout aside and tags in the footer.

Learning goals

- Use article, header, footer, aside and time inside a post
- Set up readable long-form typography
- Style a callout and tag pills

Elements and CSS used

HTML elements	CSS features
article, header, time, h1, p, figure, img, figcaption, h2, aside, strong, footer, a	font-family pairs, clamp(), border-left, border-radius partial, display: inline-block

Build guide

1. Write the article structure with header (meta, h1, lead).
2. Add the figure with caption.
3. Write two or three h2 sections.
4. Add the callout aside and the tag footer.
5. Set serif body / sans headings and a 44rem measure.
6. Style the callout and tags.

Project 492: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Why we love Intro to the wheel - Fayoum Pottery Studio blog</
title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="post">
      <header>
        <p class="meta"><time datetime="2026-09-01">1 September 2026</
time> &middot; by Ahmed Mahmoud &middot; 4 min read</p>
        <h1>Why we love Intro to the wheel</h1>
        <p class="lead">Three hours, take home a bowl. Here is the
story behind one of our favourite workshops.</p>
      </header>
      <figure>
        <img src="images/pottery-1.jpg" alt="Intro to the wheel"
width="1200" height="700">
        <figcaption>Intro to the wheel, photographed in Tunis Village.
</figcaption>
      </figure>
      <h2>How it started</h2>
      <p>When Fayoum Pottery Studio opened, Intro to the wheel was
not on the list. A customer asked for it, we tried, and it has been
our best seller ever since.</p>
      <h2>What makes it special</h2>
      <p>Three things: care, time and good ingredients. We never rush
a workshop.</p>
      <aside class="callout"><strong>Tip:</strong> Ask for it early
in the day, it sells out by the afternoon.</aside>
      <h2>Try it yourself</h2>
      <p>Intro to the wheel is available now for 450 EGP. <a
href="workshops.html">See all workshops</a>.</p>
      <footer class="tags">Tags: <a href="#">pottery</a> <a
href="#">news</a></footer>
    </article>
  </main>
</body>
</html>
```

Project 492: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
```

```
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.post { font-family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; line-height: 1.2; }
h1 { font-size: clamp(1.8rem, 4vw, 2.6rem); margin: .2rem 0 .5rem; }
.meta { color: var(--muted); font-family: system-ui, sans-serif; font-
size: .9rem; }
.lead { font-size: 1.25rem; color: var(--muted); }
figure { margin: 2rem 0; }
img { width: 100%; height: auto; border-radius: 12px; }
figcaption { font-size: .9rem; color: var(--muted); font-family:
system-ui, sans-serif; margin-top: .4rem; }
.callout { background: var(--accent); border-left: 4px solid var(--
brand); padding: 1rem 1.25rem; margin: 1.5rem 0; border-radius: 0
10px 10px 0; }
.tags { margin-top: 2rem; padding-top: 1rem; border-top: 1px solid
var(--line); font-family: system-ui, sans-serif; font-size: .9rem; }
.tags a { display: inline-block; background: var(--accent); padding: .
1rem .6rem; border-radius: 999px; text-decoration: none; color: var(--
ink); margin-right: .3rem; }
```

Project 492 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Why we love Intro to the wheel - Fayoum Pottery Studio blog<...	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="post">	A self-contained piece: card, post, product.
<header>	Introductory content: logo, title, navigation.
<p class="meta"><time datetime="2026-09-01">1 September 2026</time>...	A paragraph of text.
Why we love Intro to the wheel	The main heading; only one per page.
<figure>	Self-contained media with an optional caption.

Line	What it does
<img src="images/pottery-1.jpg" alt="Intro to the wheel" width="120...	An image; alt describes it, width and height reserve space before it loads.
<figcaption>Intro to the wheel, photographed in Tunis Village.</fig...	Caption for the figure.
How it started	Second-level heading for a section.
<aside class="callout">Tip: Ask for it early in th...	Content related to, but separate from, the main content.
<p>Intro to the wheel is available now for 450 EGP. <a href="worksh...	A hyperlink; href gives the destination.
<footer class="tags">Tags: pottery <a href="#">news...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.

Declaration	What it does
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.
font-size: clamp(1.8rem, 4vw, 2.6rem);	A fluid value between a minimum and a maximum, based on the middle expression.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
background: var(--accent);	Background colour or image.
border-left: 4px solid var(--brand);	A thick left border used as an accent stripe.
border-radius: 0 10px 10px 0;	The line around the element: width, style and colour.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Date has a datetime attribute
- One h1, then h2s
- Figure caption present
- Line length comfortable

Exercises

1. Add a table of contents generated from the h2 ids.
2. Add an author box with an image.
3. Add 'related posts' cards at the end.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 493: Blog article for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 2 | Files: index.html, styles.css

Brief

Write a full blog post with article header metadata, lead paragraph, hero figure, sections, a callout aside and tags in the footer.

Learning goals

- Use article, header, footer, aside and time inside a post
- Set up readable long-form typography
- Style a callout and tag pills

Elements and CSS used

HTML elements	CSS features
article, header, time, h1, p, figure, img, figcaption, h2, aside, strong, footer, a	font-family pairs, clamp(), border-left, border-radius partial, display: inline-block

Build guide

1. Write the article structure with header (meta, h1, lead).
2. Add the figure with caption.
3. Write two or three h2 sections.
4. Add the callout aside and the tag footer.
5. Set serif body / sans headings and a 44rem measure.
6. Style the callout and tags.

Project 493: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Why we love Haircut and blow-dry - Cleopatra Beauty Salon
blog</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="post">
      <header>
        <p class="meta"><time datetime="2026-09-01">1 September 2026</
time> &middot; by Mariam Adel &middot; 4 min read</p>
        <h1>Why we love Haircut and blow-dry</h1>
        <p class="lead">Consultation included. Here is the story
behind one of our favourite treatments.</p>
      </header>
      <figure>
        <img src="images/salon-1.jpg" alt="Haircut and blow-dry"
width="1200" height="700">
        <figcaption>Haircut and blow-dry, photographed in Dokki.</
figcaption>
      </figure>
      <h2>How it started</h2>
      <p>When Cleopatra Beauty Salon opened, Haircut and blow-dry was
not on the list. A customer asked for it, we tried, and it has been
our best seller ever since.</p>
      <h2>What makes it special</h2>
      <p>Three things: care, time and good ingredients. We never rush
a treatment.</p>
      <aside class="callout"><strong>Tip:</strong> Ask for it early
in the day, it sells out by the afternoon.</aside>
      <h2>Try it yourself</h2>
      <p>Haircut and blow-dry is available now for 350 EGP. <a
href="treatments.html">See all treatments</a>.</p>
      <footer class="tags">Tags: <a href="#">salon</a> <a
href="#">news</a></footer>
    </article>
  </main>
</body>
</html>
```

Project 493: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
```

```
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.post { font-family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; line-height: 1.2; }
h1 { font-size: clamp(1.8rem, 4vw, 2.6rem); margin: .2rem 0 .5rem; }
.meta { color: var(--muted); font-family: system-ui, sans-serif; font-
size: .9rem; }
.lead { font-size: 1.25rem; color: var(--muted); }
figure { margin: 2rem 0; }
img { width: 100%; height: auto; border-radius: 12px; }
figcaption { font-size: .9rem; color: var(--muted); font-family:
system-ui, sans-serif; margin-top: .4rem; }
.callout { background: var(--accent); border-left: 4px solid var(--
brand); padding: 1rem 1.25rem; margin: 1.5rem 0; border-radius: 0
10px 10px 0; }
.tags { margin-top: 2rem; padding-top: 1rem; border-top: 1px solid
var(--line); font-family: system-ui, sans-serif; font-size: .9rem; }
.tags a { display: inline-block; background: var(--accent); padding: .
1rem .6rem; border-radius: 999px; text-decoration: none; color: var(--
ink); margin-right: .3rem; }
```

Project 493 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Why we love Haircut and blow-dry - Cleopatra Beauty Salon bl...	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="post">	A self-contained piece: card, post, product.
<header>	Introductory content: logo, title, navigation.
<p class="meta"><time datetime="2026-09-01">1 September 2026</time>...	A paragraph of text.
Why we love Haircut and blow-dry	The main heading; only one per page.
<figure>	Self-contained media with an optional caption.

Line	What it does
<img src="images/salon-1.jpg" alt="Haircut and blow-dry" width="120...	An image; alt describes it, width and height reserve space before it loads.
<figcaption>Haircut and blow-dry, photographed in Dokki.</figcaption>	Caption for the figure.
How it started	Second-level heading for a section.
<aside class="callout">Tip: Ask for it early in th...	Content related to, but separate from, the main content.
<p>Haircut and blow-dry is available now for 350 EGP. <a href="trea...	A hyperlink; href gives the destination.
<footer class="tags">Tags: salon <a href="#">news</...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.

Declaration	What it does
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.
font-size: clamp(1.8rem, 4vw, 2.6rem);	A fluid value between a minimum and a maximum, based on the middle expression.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
background: var(--accent);	Background colour or image.
border-left: 4px solid var(--brand);	A thick left border used as an accent stripe.
border-radius: 0 10px 10px 0;	The line around the element: width, style and colour.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Date has a datetime attribute
- One h1, then h2s
- Figure caption present
- Line length comfortable

Exercises

1. Add a table of contents generated from the h2 ids.
2. Add an author box with an image.
3. Add 'related posts' cards at the end.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 494: Blog article for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 2 | Files: index.html, styles.css

Brief

Write a full blog post with article header metadata, lead paragraph, hero figure, sections, a callout aside and tags in the footer.

Learning goals

- Use article, header, footer, aside and time inside a post
- Set up readable long-form typography
- Style a callout and tag pills

Elements and CSS used

HTML elements	CSS features
article, header, time, h1, p, figure, img, figcaption, h2, aside, strong, footer, a	font-family pairs, clamp(), border-left, border-radius partial, display: inline-block

Build guide

1. Write the article structure with header (meta, h1, lead).
2. Add the figure with caption.
3. Write two or three h2 sections.
4. Add the callout aside and the tag footer.
5. Set serif body / sans headings and a 44rem measure.
6. Style the callout and tags.

Project 494: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Why we love Oil change - Suez Auto Service blog</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="post">
      <header>
        <p class="meta"><time datetime="2026-09-01">1 September 2026</
time> &middot; by Khaled Nasser &middot; 4 min read</p>
        <h1>Why we love Oil change</h1>
        <p class="lead">Filter included. Here is the story behind one
of our favourite services.</p>
      </header>
      <figure>
        <img src="images/auto-1.jpg" alt="Oil change" width="1200"
height="700">
        <figcaption>Oil change, photographed in Suez.</figcaption>
      </figure>
      <h2>How it started</h2>
      <p>When Suez Auto Service opened, Oil change was not on the
list. A customer asked for it, we tried, and it has been our best
seller ever since.</p>
      <h2>What makes it special</h2>
      <p>Three things: care, time and good ingredients. We never rush
a service.</p>
      <aside class="callout"><strong>Tip:</strong> Ask for it early
in the day, it sells out by the afternoon.</aside>
      <h2>Try it yourself</h2>
      <p>Oil change is available now for 600 EGP. <a href="services.
html">See all services</a>.</p>
      <footer class="tags">Tags: <a href="#">auto</a> <a
href="#">news</a></footer>
    </article>
  </main>
</body>
</html>
```

Project 494: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.post { font-family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; line-height: 1.2; }
h1 { font-size: clamp(1.8rem, 4vw, 2.6rem); margin: .2rem 0 .5rem; }
.meta { color: var(--muted); font-family: system-ui, sans-serif; font-
size: .9rem; }
.lead { font-size: 1.25rem; color: var(--muted); }
figure { margin: 2rem 0; }
img { width: 100%; height: auto; border-radius: 12px; }
figcaption { font-size: .9rem; color: var(--muted); font-family:
system-ui, sans-serif; margin-top: .4rem; }
.callout { background: var(--accent); border-left: 4px solid var(--
brand); padding: 1rem 1.25rem; margin: 1.5rem 0; border-radius: 0
10px 10px 0; }
.tags { margin-top: 2rem; padding-top: 1rem; border-top: 1px solid
var(--line); font-family: system-ui, sans-serif; font-size: .9rem; }
.tags a { display: inline-block; background: var(--accent); padding: .
1rem .6rem; border-radius: 999px; text-decoration: none; color: var(--
ink); margin-right: .3rem; }
```

Project 494 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Why we love Oil change - Suez Auto Service blog</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="post">	A self-contained piece: card, post, product.
<header>	Introductory content: logo, title, navigation.
<p class="meta"><time datetime="2026-09-01">1 September 2026</time>...	A paragraph of text.
Why we love Oil change	The main heading; only one per page.
<figure>	Self-contained media with an optional caption.
<img src="images/auto-1.jpg" alt="Oil change" width="1200" height="...	An image; alt describes it, width and height reserve space before it loads.

Line	What it does
<figcaption>Oil change, photographed in Suez.</figcaption>	Caption for the figure.
How it started	Second-level heading for a section.
<aside class="callout">Tip: Ask for it early in th...	Content related to, but separate from, the main content.
<p>Oil change is available now for 600 EGP. <a href="services.html"...	A hyperlink; href gives the destination.
<footer class="tags">Tags: auto <a href="#">news</a...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.

Declaration	What it does
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.
font-size: clamp(1.8rem, 4vw, 2.6rem);	A fluid value between a minimum and a maximum, based on the middle expression.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
background: var(--accent);	Background colour or image.
border-left: 4px solid var(--brand);	A thick left border used as an accent stripe.
border-radius: 0 10px 10px 0;	The line around the element: width, style and colour.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Date has a datetime attribute
- One h1, then h2s
- Figure caption present

- Line length comfortable

Exercises

1. Add a table of contents generated from the h2 ids.
2. Add an author box with an image.
3. Add 'related posts' cards at the end.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 495: Blog article for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 2 | Files: index.html, styles.css

Brief

Write a full blog post with article header metadata, lead paragraph, hero figure, sections, a callout aside and tags in the footer.

Learning goals

- Use article, header, footer, aside and time inside a post
- Set up readable long-form typography
- Style a callout and tag pills

Elements and CSS used

HTML elements	CSS features
article, header, time, h1, p, figure, img, figcaption, h2, aside, strong, footer, a	font-family pairs, clamp(), border-left, border-radius partial, display: inline-block

Build guide

1. Write the article structure with header (meta, h1, lead).
2. Add the figure with caption.
3. Write two or three h2 sections.
4. Add the callout aside and the tag footer.
5. Set serif body / sans headings and a 44rem measure.
6. Style the callout and tags.

Project 495: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Why we love Oud for beginners - Luxor Music Academy blog</
title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="post">
      <header>
        <p class="meta"><time datetime="2026-09-01">1 September 2026</
time> &middot; by Salma Ragab &middot; 4 min read</p>
        <h1>Why we love Oud for beginners</h1>
        <p class="lead">Eight weekly lessons. Here is the story
behind one of our favourite courses.</p>
      </header>
      <figure>
        <img src="images/music-1.jpg" alt="Oud for beginners"
width="1200" height="700">
        <figcaption>Oud for beginners, photographed in Luxor.</
figcaption>
      </figure>
      <h2>How it started</h2>
      <p>When Luxor Music Academy opened, Oud for beginners was not
on the list. A customer asked for it, we tried, and it has been our
best seller ever since.</p>
      <h2>What makes it special</h2>
      <p>Three things: care, time and good ingredients. We never rush
a course.</p>
      <aside class="callout"><strong>Tip:</strong> Ask for it early
in the day, it sells out by the afternoon.</aside>
      <h2>Try it yourself</h2>
      <p>Oud for beginners is available now for 1600 EGP. <a
href="courses.html">See all courses</a>.</p>
      <footer class="tags">Tags: <a href="#">music</a> <a
href="#">news</a></footer>
    </article>
  </main>
</body>
</html>
```

Project 495: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
```

```
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.post { font-family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; line-height: 1.2; }
h1 { font-size: clamp(1.8rem, 4vw, 2.6rem); margin: .2rem 0 .5rem; }
.meta { color: var(--muted); font-family: system-ui, sans-serif; font-
size: .9rem; }
.lead { font-size: 1.25rem; color: var(--muted); }
figure { margin: 2rem 0; }
img { width: 100%; height: auto; border-radius: 12px; }
figcaption { font-size: .9rem; color: var(--muted); font-family:
system-ui, sans-serif; margin-top: .4rem; }
.callout { background: var(--accent); border-left: 4px solid var(--
brand); padding: 1rem 1.25rem; margin: 1.5rem 0; border-radius: 0
10px 10px 0; }
.tags { margin-top: 2rem; padding-top: 1rem; border-top: 1px solid
var(--line); font-family: system-ui, sans-serif; font-size: .9rem; }
.tags a { display: inline-block; background: var(--accent); padding: .
1rem .6rem; border-radius: 999px; text-decoration: none; color: var(--
ink); margin-right: .3rem; }
```

Project 495 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Why we love Oud for beginners - Luxor Music Academy blog</ti...	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="post">	A self-contained piece: card, post, product.
<header>	Introductory content: logo, title, navigation.
<p class="meta"><time datetime="2026-09-01">1 September 2026</time>...	A paragraph of text.
Why we love Oud for beginners	The main heading; only one per page.
<figure>	Self-contained media with an optional caption.

Line	What it does
<img src="images/music-1.jpg" alt="Oud for beginners" width="1200" ...	An image; alt describes it, width and height reserve space before it loads.
<figcaption>Oud for beginners, photographed in Luxor.</figcaption>	Caption for the figure.
How it started	Second-level heading for a section.
<aside class="callout">Tip: Ask for it early in th...	Content related to, but separate from, the main content.
<p>Oud for beginners is available now for 1600 EGP. <a href="course...	A hyperlink; href gives the destination.
<footer class="tags">Tags: music <a href="#">news</...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.

Declaration	What it does
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.
font-size: clamp(1.8rem, 4vw, 2.6rem);	A fluid value between a minimum and a maximum, based on the middle expression.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
background: var(--accent);	Background colour or image.
border-left: 4px solid var(--brand);	A thick left border used as an accent stripe.
border-radius: 0 10px 10px 0;	The line around the element: width, style and colour.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Date has a datetime attribute
- One h1, then h2s
- Figure caption present
- Line length comfortable

Exercises

1. Add a table of contents generated from the h2 ids.
2. Add an author box with an image.
3. Add 'related posts' cards at the end.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 496: Blog article for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 2 | Files: index.html, styles.css

Brief

Write a full blog post with article header metadata, lead paragraph, hero figure, sections, a callout aside and tags in the footer.

Learning goals

- Use article, header, footer, aside and time inside a post
- Set up readable long-form typography
- Style a callout and tag pills

Elements and CSS used

HTML elements	CSS features
article, header, time, h1, p, figure, img, figcaption, h2, aside, strong, footer, a	font-family pairs, clamp(), border-left, border-radius partial, display: inline-block

Build guide

1. Write the article structure with header (meta, h1, lead).
2. Add the figure with caption.
3. Write two or three h2 sections.
4. Add the callout aside and the tag footer.
5. Set serif body / sans headings and a 44rem measure.
6. Style the callout and tags.

Project 496: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Why we love Grilled sea bass - Port Said Seafood blog</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="post">
      <header>
        <p class="meta"><time datetime="2026-09-01">1 September 2026</
time> &middot; by Sherif Wahba &middot; 4 min read</p>
        <h1>Why we love Grilled sea bass</h1>
        <p class="lead">With rice and salad. Here is the story behind
one of our favourite dishes.</p>
      </header>
      <figure>
        <img src="images/restaurant-1.jpg" alt="Grilled sea bass"
width="1200" height="700">
        <figcaption>Grilled sea bass, photographed in Port Said.</
figcaption>
      </figure>
      <h2>How it started</h2>
      <p>When Port Said Seafood opened, Grilled sea bass was not on
the list. A customer asked for it, we tried, and it has been our best
seller ever since.</p>
      <h2>What makes it special</h2>
      <p>Three things: care, time and good ingredients. We never rush
a dish.</p>
      <aside class="callout"><strong>Tip:</strong> Ask for it early
in the day, it sells out by the afternoon.</aside>
      <h2>Try it yourself</h2>
      <p>Grilled sea bass is available now for 320 EGP. <a
href="dishes.html">See all dishes</a>.</p>
      <footer class="tags">Tags: <a href="#">restaurant</a> <a
href="#">news</a></footer>
    </article>
  </main>
</body>
</html>
```

Project 496: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
```

```
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.post { font-family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; line-height: 1.2; }
h1 { font-size: clamp(1.8rem, 4vw, 2.6rem); margin: .2rem 0 .5rem; }
.meta { color: var(--muted); font-family: system-ui, sans-serif; font-
size: .9rem; }
.lead { font-size: 1.25rem; color: var(--muted); }
figure { margin: 2rem 0; }
img { width: 100%; height: auto; border-radius: 12px; }
figcaption { font-size: .9rem; color: var(--muted); font-family:
system-ui, sans-serif; margin-top: .4rem; }
.callout { background: var(--accent); border-left: 4px solid var(--
brand); padding: 1rem 1.25rem; margin: 1.5rem 0; border-radius: 0
10px 10px 0; }
.tags { margin-top: 2rem; padding-top: 1rem; border-top: 1px solid
var(--line); font-family: system-ui, sans-serif; font-size: .9rem; }
.tags a { display: inline-block; background: var(--accent); padding: .
1rem .6rem; border-radius: 999px; text-decoration: none; color: var(--
ink); margin-right: .3rem; }
```

Project 496 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Why we love Grilled sea bass - Port Said Seafood blog</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="post">	A self-contained piece: card, post, product.
<header>	Introductory content: logo, title, navigation.
<p class="meta"><time datetime="2026-09-01">1 September 2026</time>...	A paragraph of text.
Why we love Grilled sea bass	The main heading; only one per page.
<figure>	Self-contained media with an optional caption.

Line	What it does
<img src="images/restaurant-1.jpg" alt="Grilled sea bass" width="12...	An image; alt describes it, width and height reserve space before it loads.
<figcaption>Grilled sea bass, photographed in Port Said.</figcaption>	Caption for the figure.
How it started	Second-level heading for a section.
<aside class="callout">Tip: Ask for it early in th...	Content related to, but separate from, the main content.
<p>Grilled sea bass is available now for 320 EGP. <a href="dishes.h...	A hyperlink; href gives the destination.
<footer class="tags">Tags: restaurant <a href="#">n...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.

Declaration	What it does
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.
font-size: clamp(1.8rem, 4vw, 2.6rem);	A fluid value between a minimum and a maximum, based on the middle expression.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
background: var(--accent);	Background colour or image.
border-left: 4px solid var(--brand);	A thick left border used as an accent stripe.
border-radius: 0 10px 10px 0;	The line around the element: width, style and colour.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Date has a datetime attribute
- One h1, then h2s
- Figure caption present
- Line length comfortable

Exercises

1. Add a table of contents generated from the h2 ids.
2. Add an author box with an image.
3. Add 'related posts' cards at the end.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 497: Blog article for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 2 | Files: index.html, styles.css

Brief

Write a full blog post with article header metadata, lead paragraph, hero figure, sections, a callout aside and tags in the footer.

Learning goals

- Use article, header, footer, aside and time inside a post
- Set up readable long-form typography
- Style a callout and tag pills

Elements and CSS used

HTML elements	CSS features
article, header, time, h1, p, figure, img, figcaption, h2, aside, strong, footer, a	font-family pairs, clamp(), border-left, border-radius partial, display: inline-block

Build guide

1. Write the article structure with header (meta, h1, lead).
2. Add the figure with caption.
3. Write two or three h2 sections.
4. Add the callout aside and the tag footer.
5. Set serif body / sans headings and a 44rem measure.
6. Style the callout and tags.

Project 497: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Why we love Story hour - Delta Kids Library blog</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="post">
      <header>
        <p class="meta"><time datetime="2026-09-01">1 September 2026</
time> &middot; by Ghada Kamel &middot; 4 min read</p>
        <h1>Why we love Story hour</h1>
        <p class="lead">Ages 3 to 6, Saturdays. Here is the story
behind one of our favourite programmes.</p>
      </header>
      <figure>
        <img src="images/library-1.jpg" alt="Story hour" width="1200"
height="700">
        <figcaption>Story hour, photographed in Tanta.</figcaption>
      </figure>
      <h2>How it started</h2>
      <p>When Delta Kids Library opened, Story hour was not on the
list. A customer asked for it, we tried, and it has been our best
seller ever since.</p>
      <h2>What makes it special</h2>
      <p>Three things: care, time and good ingredients. We never rush
a programme.</p>
      <aside class="callout"><strong>Tip:</strong> Ask for it early
in the day, it sells out by the afternoon.</aside>
      <h2>Try it yourself</h2>
      <p>Story hour is available now for Free. <a href="programmes.
html">See all programmes</a>.</p>
      <footer class="tags">Tags: <a href="#">library</a> <a
href="#">news</a></footer>
    </article>
  </main>
</body>
</html>
```

Project 497: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.post { font-family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; line-height: 1.2; }
h1 { font-size: clamp(1.8rem, 4vw, 2.6rem); margin: .2rem 0 .5rem; }
.meta { color: var(--muted); font-family: system-ui, sans-serif; font-
size: .9rem; }
.lead { font-size: 1.25rem; color: var(--muted); }
figure { margin: 2rem 0; }
img { width: 100%; height: auto; border-radius: 12px; }
figcaption { font-size: .9rem; color: var(--muted); font-family:
system-ui, sans-serif; margin-top: .4rem; }
.callout { background: var(--accent); border-left: 4px solid var(--
brand); padding: 1rem 1.25rem; margin: 1.5rem 0; border-radius: 0
10px 10px 0; }
.tags { margin-top: 2rem; padding-top: 1rem; border-top: 1px solid
var(--line); font-family: system-ui, sans-serif; font-size: .9rem; }
.tags a { display: inline-block; background: var(--accent); padding: .
1rem .6rem; border-radius: 999px; text-decoration: none; color: var(--
ink); margin-right: .3rem; }
```

Project 497 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Why we love Story hour - Delta Kids Library blog</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="post">	A self-contained piece: card, post, product.
<header>	Introductory content: logo, title, navigation.
<p class="meta"><time datetime="2026-09-01">1 September 2026</time>...	A paragraph of text.
Why we love Story hour	The main heading; only one per page.
<figure>	Self-contained media with an optional caption.

Line	What it does
<img src="images/library-1.jpg" alt="Story hour" width="1200" heigh...	An image; alt describes it, width and height reserve space before it loads.
<figcaption>Story hour, photographed in Tanta.</figcaption>	Caption for the figure.
How it started	Second-level heading for a section.
<aside class="callout">Tip: Ask for it early in th...	Content related to, but separate from, the main content.
<p>Story hour is available now for Free. <a href="programmes.html">...	A hyperlink; href gives the destination.
<footer class="tags">Tags: library <a href="#">news...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.

Declaration	What it does
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.
font-size: clamp(1.8rem, 4vw, 2.6rem);	A fluid value between a minimum and a maximum, based on the middle expression.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
background: var(--accent);	Background colour or image.
border-left: 4px solid var(--brand);	A thick left border used as an accent stripe.
border-radius: 0 10px 10px 0;	The line around the element: width, style and colour.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Date has a datetime attribute
- One h1, then h2s
- Figure caption present
- Line length comfortable

Exercises

1. Add a table of contents generated from the h2 ids.
2. Add an author box with an image.
3. Add 'related posts' cards at the end.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 498: Blog article for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Write a full blog post with article header metadata, lead paragraph, hero figure, sections, a callout aside and tags in the footer.

Learning goals

- Use article, header, footer, aside and time inside a post
- Set up readable long-form typography
- Style a callout and tag pills

Elements and CSS used

HTML elements	CSS features
article, header, time, h1, p, figure, img, figcaption, h2, aside, strong, footer, a	font-family pairs, clamp(), border-left, border-radius partial, display: inline-block

Build guide

1. Write the article structure with header (meta, h1, lead).
2. Add the figure with caption.
3. Write two or three h2 sections.
4. Add the callout aside and the tag footer.
5. Set serif body / sans headings and a 44rem measure.
6. Style the callout and tags.

Project 498: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Why we love Garden room - Nubian Guest House blog</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="post">
      <header>
        <p class="meta"><time datetime="2026-09-01">1 September 2026</
time> &middot; by Fatma Hassan &middot; 4 min read</p>
        <h1>Why we love Garden room</h1>
        <p class="lead">Double bed, shared terrace. Here is the story
behind one of our favourite rooms.</p>
      </header>
      <figure>
        <img src="images/guesthouse-1.jpg" alt="Garden room"
width="1200" height="700">
        <figcaption>Garden room, photographed in Aswan.</figcaption>
      </figure>
      <h2>How it started</h2>
      <p>When Nubian Guest House opened, Garden room was not on the
list. A customer asked for it, we tried, and it has been our best
seller ever since.</p>
      <h2>What makes it special</h2>
      <p>Three things: care, time and good ingredients. We never rush
a room.</p>
      <aside class="callout"><strong>Tip:</strong> Ask for it early
in the day, it sells out by the afternoon.</aside>
      <h2>Try it yourself</h2>
      <p>Garden room is available now for 900 EGP. <a href="rooms.
html">See all rooms</a>.</p>
      <footer class="tags">Tags: <a href="#">guesthouse</a> <a
href="#">news</a></footer>
    </article>
  </main>
</body>
</html>
```

Project 498: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.post { font-family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; line-height: 1.2; }
h1 { font-size: clamp(1.8rem, 4vw, 2.6rem); margin: .2rem 0 .5rem; }
.meta { color: var(--muted); font-family: system-ui, sans-serif; font-
size: .9rem; }
.lead { font-size: 1.25rem; color: var(--muted); }
figure { margin: 2rem 0; }
img { width: 100%; height: auto; border-radius: 12px; }
figcaption { font-size: .9rem; color: var(--muted); font-family:
system-ui, sans-serif; margin-top: .4rem; }
.callout { background: var(--accent); border-left: 4px solid var(--
brand); padding: 1rem 1.25rem; margin: 1.5rem 0; border-radius: 0
10px 10px 0; }
.tags { margin-top: 2rem; padding-top: 1rem; border-top: 1px solid
var(--line); font-family: system-ui, sans-serif; font-size: .9rem; }
.tags a { display: inline-block; background: var(--accent); padding: .
1rem .6rem; border-radius: 999px; text-decoration: none; color: var(--
ink); margin-right: .3rem; }
```

Project 498 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Why we love Garden room - Nubian Guest House blog</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="post">	A self-contained piece: card, post, product.
<header>	Introductory content: logo, title, navigation.
<p class="meta"><time datetime="2026-09-01">1 September 2026</time>...	A paragraph of text.
Why we love Garden room	The main heading; only one per page.
<figure>	Self-contained media with an optional caption.
<img src="images/guesthouse-1.jpg" alt="Garden room" width="1200" h...	An image; alt describes it, width and height reserve space before it loads.

Line	What it does
<figcaption>Garden room, photographed in Aswan.</figcaption>	Caption for the figure.
How it started	Second-level heading for a section.
<aside class="callout">Tip: Ask for it early in th...	Content related to, but separate from, the main content.
<p>Garden room is available now for 900 EGP. <a href="rooms.html">S...	A hyperlink; href gives the destination.
<footer class="tags">Tags: guesthouse <a href="#">n...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.

Declaration	What it does
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.
font-size: clamp(1.8rem, 4vw, 2.6rem);	A fluid value between a minimum and a maximum, based on the middle expression.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
background: var(--accent);	Background colour or image.
border-left: 4px solid var(--brand);	A thick left border used as an accent stripe.
border-radius: 0 10px 10px 0;	The line around the element: width, style and colour.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Date has a datetime attribute
- One h1, then h2s
- Figure caption present

- Line length comfortable

Exercises

1. Add a table of contents generated from the h2 ids.
2. Add an author box with an image.
3. Add 'related posts' cards at the end.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 499: Blog article for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 2 | Files: index.html, styles.css

Brief

Write a full blog post with article header metadata, lead paragraph, hero figure, sections, a callout aside and tags in the footer.

Learning goals

- Use article, header, footer, aside and time inside a post
- Set up readable long-form typography
- Style a callout and tag pills

Elements and CSS used

HTML elements	CSS features
article, header, time, h1, p, figure, img, figcaption, h2, aside, strong, footer, a	font-family pairs, clamp(), border-left, border-radius partial, display: inline-block

Build guide

1. Write the article structure with header (meta, h1, lead).
2. Add the figure with caption.
3. Write two or three h2 sections.
4. Add the callout aside and the tag footer.
5. Set serif body / sans headings and a 44rem measure.
6. Style the callout and tags.

Project 499: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Why we love City bike - Ismailia Cycling Store blog</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="post">
      <header>
        <p class="meta"><time datetime="2026-09-01">1 September 2026</
time> &middot; by Bassem Adly &middot; 4 min read</p>
        <h1>Why we love City bike</h1>
        <p class="lead">Seven gears, basket. Here is the story behind
one of our favourite bikes.</p>
      </header>
      <figure>
        <img src="images/cycling-1.jpg" alt="City bike" width="1200"
height="700">
        <figcaption>City bike, photographed in Ismailia.</figcaption>
      </figure>
      <h2>How it started</h2>
      <p>When Ismailia Cycling Store opened, City bike was not on the
list. A customer asked for it, we tried, and it has been our best
seller ever since.</p>
      <h2>What makes it special</h2>
      <p>Three things: care, time and good ingredients. We never rush
a bike.</p>
      <aside class="callout"><strong>Tip:</strong> Ask for it early
in the day, it sells out by the afternoon.</aside>
      <h2>Try it yourself</h2>
      <p>City bike is available now for 6500 EGP. <a href="bikes.
html">See all bikes</a>.</p>
      <footer class="tags">Tags: <a href="#">cycling</a> <a
href="#">news</a></footer>
    </article>
  </main>
</body>
</html>
```

Project 499: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.post { font-family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; line-height: 1.2; }
h1 { font-size: clamp(1.8rem, 4vw, 2.6rem); margin: .2rem 0 .5rem; }
.meta { color: var(--muted); font-family: system-ui, sans-serif; font-
size: .9rem; }
.lead { font-size: 1.25rem; color: var(--muted); }
figure { margin: 2rem 0; }
img { width: 100%; height: auto; border-radius: 12px; }
figcaption { font-size: .9rem; color: var(--muted); font-family:
system-ui, sans-serif; margin-top: .4rem; }
.callout { background: var(--accent); border-left: 4px solid var(--
brand); padding: 1rem 1.25rem; margin: 1.5rem 0; border-radius: 0
10px 10px 0; }
.tags { margin-top: 2rem; padding-top: 1rem; border-top: 1px solid
var(--line); font-family: system-ui, sans-serif; font-size: .9rem; }
.tags a { display: inline-block; background: var(--accent); padding: .
1rem .6rem; border-radius: 999px; text-decoration: none; color: var(--
ink); margin-right: .3rem; }
```

Project 499 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Why we love City bike - Ismailia Cycling Store blog</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="post">	A self-contained piece: card, post, product.
<header>	Introductory content: logo, title, navigation.
<p class="meta"><time datetime="2026-09-01">1 September 2026</time>...	A paragraph of text.
Why we love City bike	The main heading; only one per page.
<figure>	Self-contained media with an optional caption.

Line	What it does
<img src="images/cycling-1.jpg" alt="City bike" width="1200" height...	An image; alt describes it, width and height reserve space before it loads.
<figcaption>City bike, photographed in Ismailia.</figcaption>	Caption for the figure.
How it started	Second-level heading for a section.
<aside class="callout">Tip: Ask for it early in th...	Content related to, but separate from, the main content.
<p>City bike is available now for 6500 EGP. <a href="bikes.html">Se...	A hyperlink; href gives the destination.
<footer class="tags">Tags: cycling <a href="#">news...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.

Declaration	What it does
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.
font-size: clamp(1.8rem, 4vw, 2.6rem);	A fluid value between a minimum and a maximum, based on the middle expression.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
background: var(--accent);	Background colour or image.
border-left: 4px solid var(--brand);	A thick left border used as an accent stripe.
border-radius: 0 10px 10px 0;	The line around the element: width, style and colour.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Date has a datetime attribute
- One h1, then h2s
- Figure caption present
- Line length comfortable

Exercises

1. Add a table of contents generated from the h2 ids.
2. Add an author box with an image.
3. Add 'related posts' cards at the end.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 500: Blog article for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 2 | Files: index.html, styles.css

Brief

Write a full blog post with article header metadata, lead paragraph, hero figure, sections, a callout aside and tags in the footer.

Learning goals

- Use article, header, footer, aside and time inside a post
- Set up readable long-form typography
- Style a callout and tag pills

Elements and CSS used

HTML elements	CSS features
article, header, time, h1, p, figure, img, figcaption, h2, aside, strong, footer, a	font-family pairs, clamp(), border-left, border-radius partial, display: inline-block

Build guide

1. Write the article structure with header (meta, h1, lead).
2. Add the figure with caption.
3. Write two or three h2 sections.
4. Add the callout aside and the tag footer.
5. Set serif body / sans headings and a 44rem measure.
6. Style the callout and tags.

Project 500: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Why we love HTML weekend - Minya Coding Club blog</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="post">
      <header>
        <p class="meta"><time datetime="2026-09-01">1 September 2026</
time> &middot; by Youssef Hany &middot; 4 min read</p>
        <h1>Why we love HTML weekend</h1>
        <p class="lead">Build your first page. Here is the story
behind one of our favourite workshops.</p>
      </header>
      <figure>
        <img src="images/coding-1.jpg" alt="HTML weekend"
width="1200" height="700">
        <figcaption>HTML weekend, photographed in Minya.</figcaption>
      </figure>
      <h2>How it started</h2>
      <p>When Minya Coding Club opened, HTML weekend was not on the
list. A customer asked for it, we tried, and it has been our best
seller ever since.</p>
      <h2>What makes it special</h2>
      <p>Three things: care, time and good ingredients. We never rush
a workshop.</p>
      <aside class="callout"><strong>Tip:</strong> Ask for it early
in the day, it sells out by the afternoon.</aside>
      <h2>Try it yourself</h2>
      <p>HTML weekend is available now for Free. <a href="workshops.
html">See all workshops</a>.</p>
      <footer class="tags">Tags: <a href="#">coding</a> <a
href="#">news</a></footer>
    </article>
  </main>
</body>
</html>
```

Project 500: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.post { font-family: Georgia, serif; font-size: 1.1rem; }
h1, h2 { font-family: system-ui, sans-serif; line-height: 1.2; }
h1 { font-size: clamp(1.8rem, 4vw, 2.6rem); margin: .2rem 0 .5rem; }
.meta { color: var(--muted); font-family: system-ui, sans-serif; font-
size: .9rem; }
.lead { font-size: 1.25rem; color: var(--muted); }
figure { margin: 2rem 0; }
img { width: 100%; height: auto; border-radius: 12px; }
figcaption { font-size: .9rem; color: var(--muted); font-family:
system-ui, sans-serif; margin-top: .4rem; }
.callout { background: var(--accent); border-left: 4px solid var(--
brand); padding: 1rem 1.25rem; margin: 1.5rem 0; border-radius: 0
10px 10px 0; }
.tags { margin-top: 2rem; padding-top: 1rem; border-top: 1px solid
var(--line); font-family: system-ui, sans-serif; font-size: .9rem; }
.tags a { display: inline-block; background: var(--accent); padding: .
1rem .6rem; border-radius: 999px; text-decoration: none; color: var(--
ink); margin-right: .3rem; }
```

Project 500 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Why we love HTML weekend - Minya Coding Club blog</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="post">	A self-contained piece: card, post, product.
<header>	Introductory content: logo, title, navigation.
<p class="meta"><time datetime="2026-09-01">1 September 2026</time>...	A paragraph of text.
Why we love HTML weekend	The main heading; only one per page.
<figure>	Self-contained media with an optional caption.

Line	What it does
<img src="images/coding-1.jpg" alt="HTML weekend" width="1200" heig...	An image; alt describes it, width and height reserve space before it loads.
<figcaption>HTML weekend, photographed in Minya.</figcaption>	Caption for the figure.
How it started	Second-level heading for a section.
<aside class="callout">Tip: Ask for it early in th...	Content related to, but separate from, the main content.
<p>HTML weekend is available now for Free. <a href="workshops.html"...	A hyperlink; href gives the destination.
<footer class="tags">Tags: coding <a href="#">news<...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.

Declaration	What it does
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.1rem;	Size of the text.
font-size: clamp(1.8rem, 4vw, 2.6rem);	A fluid value between a minimum and a maximum, based on the middle expression.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
border-radius: 12px;	Rounds the corners.
background: var(--accent);	Background colour or image.
border-left: 4px solid var(--brand);	A thick left border used as an accent stripe.
border-radius: 0 10px 10px 0;	The line around the element: width, style and colour.
border-top: 1px solid var(--line);	A top border used as an accent or separator.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Date has a datetime attribute
- One h1, then h2s
- Figure caption present
- Line length comfortable

Exercises

1. Add a table of contents generated from the h2 ids.
2. Add an author box with an image.
3. Add 'related posts' cards at the end.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Weekly schedule grid

Level 2 | 25 projects, one per theme

Build a timetable as a table with separate, rounded cells where booked slots are highlighted with :not(:empty).

Project 501: Weekly schedule grid for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 2 | Files: index.html, styles.css

Brief

Build a timetable as a table with separate, rounded cells where booked slots are highlighted with :not(:empty).

Learning goals

- Use the separate border model with border-spacing
- Highlight cells based on content with :empty
- Keep a wide table scrollable

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td	border-collapse: separate, border-spacing, :not(:empty), border-radius on cells, min-width

Build guide

1. Write the header row with the days.
2. Write one row per time slot; the first cell is th scope="row".
3. Leave empty <td></td> for free slots.
4. Use border-collapse: separate and border-spacing so cells look like tiles.
5. Style non-empty cells with :not(:empty).
6. Wrap for horizontal scrolling.

Project 501: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Weekly schedule</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Weekly schedule</h1>
    <div class="wrap">
      <table class="schedule">
        <caption>Books by day and time</caption>
        <thead><tr><th scope="col">Time</th><th scope="col">Sat</
th><th scope="col">Sun</th><th scope="col">Mon</th><th
scope="col">Tue</th><th scope="col">Wed</th></tr></thead>
        <tbody>
          <tr><th scope="row">9:00</th><td>Learn HTML</td><td></
td><td>Learn HTML</td><td></td><td>Learn HTML</td></tr>
          <tr><th scope="row">11:00</th><td></td><td>CSS in Practice</
td><td></td><td>CSS in Practice</td><td></td></tr>
          <tr><th scope="row">13:00</th><td>JavaScript Basics</
td><td></td><td>JavaScript Basics</td><td></td><td>JavaScript Basics</
td></tr>
          <tr><th scope="row">15:00</th><td></td><td>Web
Accessibility</td><td></td><td>Web Accessibility</td><td></td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 501: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.wrap { overflow-x: auto; }
.schedule { border-collapse: separate; border-spacing: 4px; width:
100%; min-width: 36rem; }
.schedule th { background: var(--brand); color: #fff; padding: .5rem;
border-radius: 6px; }
```

```
.schedule tbody th { background: var(--accent); color: var(--ink); }
.schedule td { padding: .6rem; border-radius: 6px; text-align: center;
 background: #f6f6f6; min-height: 3rem; }
.schedule td:not(:empty) { background: var(--accent); font-weight:
600; border: 2px solid var(--brand); }
```

Project 501 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - Weekly schedule</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Weekly schedule	The main heading; only one per page.
	Generic block container for grouping and layout.
<table class="schedule">	Tabular data in rows and columns.
<caption>Books by day and time</caption>	Title of the table.
<thead><tr><th scope="col">Time</th><th scope="col">Sat</th><th sco...	Group of header rows.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">9:00</th><td>Learn HTML</td><td></td><td>Learn ...	A table row.
<tr><th scope="row">11:00</th><td></td><td>CSS in Practice</td><td>...	Header cell for a row.
<tr><th scope="row">13:00</th><td>JavaScript Basics</td><td></td><td><t...	A header cell.
<tr><th scope="row">15:00</th><td></td><td>Web Accessibility</td><td><t...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
border-collapse: separate;	Keeps each cell's border separate so cells look like tiles.
border-spacing: 4px;	Gap between cells in the separate border model.
width: 100%;	Fills the container width.
background: var(--brand);	Background colour or image.
border-radius: 6px;	Rounds the corners.
border-radius: 6px;	The line around the element: width, style and colour.
text-align: center;	Centres inline content such as text.
.schedule td:not(:empty) {	Excludes elements from a selector.
font-weight: 600;	Thickness of the text.
border: 2px solid var(--brand);	Changes the visual order of a flex item without changing the source.

Check your work

- Every cell exists even if empty
- Row and column headers have scope
- Tiles have rounded corners
- Table scrolls on narrow screens

Exercises

1. Add rowspan for a two-hour slot.

2. Colour by category with classes.
3. Make the time column sticky with position: sticky; left: 0.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 502: Weekly schedule grid for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 2 | Files: index.html, styles.css

Brief

Build a timetable as a table with separate, rounded cells where booked slots are highlighted with :not(:empty).

Learning goals

- Use the separate border model with border-spacing
- Highlight cells based on content with :empty
- Keep a wide table scrollable

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td	border-collapse: separate, border-spacing, :not(:empty), border-radius on cells, min-width

Build guide

1. Write the header row with the days.
2. Write one row per time slot; the first cell is th scope="row".
3. Leave empty <td></td> for free slots.
4. Use border-collapse: separate and border-spacing so cells look like tiles.
5. Style non-empty cells with :not(:empty).
6. Wrap for horizontal scrolling.

Project 502: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - Weekly schedule</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Weekly schedule</h1>
    <div class="wrap">
      <table class="schedule">
        <caption>Pastries by day and time</caption>
        <thead><tr><th scope="col">Time</th><th scope="col">Sat</
th><th scope="col">Sun</th><th scope="col">Mon</th><th
scope="col">Tue</th><th scope="col">Wed</th></tr></thead>
        <tbody>
          <tr><th scope="row">9:00</th><td>Sourdough loaf</td><td></
td><td>Sourdough loaf</td><td></td><td>Sourdough loaf</td></tr>
          <tr><th scope="row">11:00</th><td></td><td>Croissant</
td><td></td><td>Croissant</td><td></td></tr>
          <tr><th scope="row">13:00</th><td>Date cookies</td><td></
td><td>Date cookies</td><td></td><td>Date cookies</td></tr>
          <tr><th scope="row">15:00</th><td></td><td>Baklava box</
td><td></td><td>Baklava box</td><td></td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 502: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.wrap { overflow-x: auto; }
.schedule { border-collapse: separate; border-spacing: 4px; width:
100%; min-width: 36rem; }
.schedule th { background: var(--brand); color: #fff; padding: .5rem;
border-radius: 6px; }
.schedule tbody th { background: var(--accent); color: var(--ink); }
```

```
.schedule td { padding: .6rem; border-radius: 6px; text-align: center;
 background: #f6f6f6; min-height: 3rem; }
.schedule td:not(:empty) { background: var(--accent); font-weight:
600; border: 2px solid var(--brand); }
```

Project 502 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - Weekly schedule</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Weekly schedule	The main heading; only one per page.
	Generic block container for grouping and layout.
<table class="schedule">	Tabular data in rows and columns.
<caption>Pastries by day and time</caption>	Title of the table.
<thead><tr><th scope="col">Time</th><th scope="col">Sat</th><th sco...	Group of header rows.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">9:00</th><td>Sourdough loaf</td><td></td><td>So...	A table row.
<tr><th scope="row">11:00</th><td></td><td>Croissant</td><td></td><...	Header cell for a row.
<tr><th scope="row">13:00</th><td>Date cookies</td><td></td><td>Dat...	A header cell.
<tr><th scope="row">15:00</th><td></td><td>Baklava box</td><td></td...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
border-collapse: separate;	Keeps each cell's border separate so cells look like tiles.
border-spacing: 4px;	Gap between cells in the separate border model.
width: 100%;	Fills the container width.
background: var(--brand);	Background colour or image.
border-radius: 6px;	Rounds the corners.
border-radius: 6px;	The line around the element: width, style and colour.
text-align: center;	Centres inline content such as text.
.schedule td:not(:empty) {	Excludes elements from a selector.
font-weight: 600;	Thickness of the text.
border: 2px solid var(--brand);	Changes the visual order of a flex item without changing the source.

Check your work

- Every cell exists even if empty
- Row and column headers have scope
- Tiles have rounded corners
- Table scrolls on narrow screens

Exercises

1. Add rowspan for a two-hour slot.

2. Colour by category with classes.
3. Make the time column sticky with position: sticky; left: 0.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 503: Weekly schedule grid for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 2 | Files: index.html, styles.css

Brief

Build a timetable as a table with separate, rounded cells where booked slots are highlighted with :not(:empty).

Learning goals

- Use the separate border model with border-spacing
- Highlight cells based on content with :empty
- Keep a wide table scrollable

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td	border-collapse: separate, border-spacing, :not(:empty), border-radius on cells, min-width

Build guide

1. Write the header row with the days.
2. Write one row per time slot; the first cell is th scope="row".
3. Leave empty <td></td> for free slots.
4. Use border-collapse: separate and border-spacing so cells look like tiles.
5. Style non-empty cells with :not(:empty).
6. Wrap for horizontal scrolling.

Project 503: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - Weekly schedule</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Weekly schedule</h1>
    <div class="wrap">
      <table class="schedule">
        <caption>Classes by day and time</caption>
        <thead><tr><th scope="col">Time</th><th scope="col">Sat</
th><th scope="col">Sun</th><th scope="col">Mon</th><th
scope="col">Tue</th><th scope="col">Wed</th></tr></thead>
        <tbody>
          <tr><th scope="row">9:00</th><td>Morning yoga</td><td></
td><td>Morning yoga</td><td></td><td>Morning yoga</td></tr>
          <tr><th scope="row">11:00</th><td></td><td>Strength
circuit</td><td></td><td>Strength circuit</td><td></td></tr>
          <tr><th scope="row">13:00</th><td>Spinning</td><td></
td><td>Spinning</td><td></td><td>Spinning</td></tr>
          <tr><th scope="row">15:00</th><td></td><td>Personal
training</td><td></td><td>Personal training</td><td></td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 503: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.wrap { overflow-x: auto; }
.schedule { border-collapse: separate; border-spacing: 4px; width:
100%; min-width: 36rem; }
.schedule th { background: var(--brand); color: #fff; padding: .5rem;
border-radius: 6px; }
.schedule tbody th { background: var(--accent); color: var(--ink); }
```

```
.schedule td { padding: .6rem; border-radius: 6px; text-align: center;
 background: #f6f6f6; min-height: 3rem; }
.schedule td:not(:empty) { background: var(--accent); font-weight:
600; border: 2px solid var(--brand); }
```

Project 503 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - Weekly schedule</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Weekly schedule	The main heading; only one per page.
	Generic block container for grouping and layout.
<table class="schedule">	Tabular data in rows and columns.
<caption>Classes by day and time</caption>	Title of the table.
<thead><tr><th scope="col">Time</th><th scope="col">Sat</th><th sco...	Group of header rows.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">9:00</th><td>Morning yoga</td><td></td><td>Morn...	A table row.
<tr><th scope="row">11:00</th><td></td><td>Strength circuit</td><td...	Header cell for a row.
<tr><th scope="row">13:00</th><td>Spinning</td><td></td><td>Spinnin...	A header cell.
<tr><th scope="row">15:00</th><td></td><td>Personal training</td><t...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
border-collapse: separate;	Keeps each cell's border separate so cells look like tiles.
border-spacing: 4px;	Gap between cells in the separate border model.
width: 100%;	Fills the container width.
background: var(--brand);	Background colour or image.
border-radius: 6px;	Rounds the corners.
border-radius: 6px;	The line around the element: width, style and colour.
text-align: center;	Centres inline content such as text.
.schedule td:not(:empty) {	Excludes elements from a selector.
font-weight: 600;	Thickness of the text.
border: 2px solid var(--brand);	Changes the visual order of a flex item without changing the source.

Check your work

- Every cell exists even if empty
- Row and column headers have scope
- Tiles have rounded corners
- Table scrolls on narrow screens

Exercises

1. Add rowspan for a two-hour slot.

2. Colour by category with classes.
3. Make the time column sticky with position: sticky; left: 0.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 504: Weekly schedule grid for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 2 | Files: index.html, styles.css

Brief

Build a timetable as a table with separate, rounded cells where booked slots are highlighted with :not(:empty).

Learning goals

- Use the separate border model with border-spacing
- Highlight cells based on content with :empty
- Keep a wide table scrollable

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td	border-collapse: separate, border-spacing, :not(:empty), border-radius on cells, min-width

Build guide

1. Write the header row with the days.
2. Write one row per time slot; the first cell is th scope="row".
3. Leave empty <td></td> for free slots.
4. Use border-collapse: separate and border-spacing so cells look like tiles.
5. Style non-empty cells with :not(:empty).
6. Wrap for horizontal scrolling.

Project 504: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - Weekly schedule</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Weekly schedule</h1>
    <div class="wrap">
      <table class="schedule">
        <caption>Services by day and time</caption>
        <thead><tr><th scope="col">Time</th><th scope="col">Sat</
th><th scope="col">Sun</th><th scope="col">Mon</th><th
scope="col">Tue</th><th scope="col">Wed</th></tr></thead>
        <tbody>
          <tr><th scope="row">9:00</th><td>Check-up</td><td></
td><td>Check-up</td><td></td><td>Check-up</td></tr>
          <tr><th scope="row">11:00</th><td></td><td>Whitening</
td><td></td><td>Whitening</td><td></td></tr>
          <tr><th scope="row">13:00</th><td>Filling</td><td></
td><td>Filling</td><td></td><td>Filling</td></tr>
          <tr><th scope="row">15:00</th><td></td><td>Braces
consultation</td><td></td><td>Braces consultation</td><td></td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 504: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.wrap { overflow-x: auto; }
.schedule { border-collapse: separate; border-spacing: 4px; width:
100%; min-width: 36rem; }
.schedule th { background: var(--brand); color: #fff; padding: .5rem;
border-radius: 6px; }
.schedule tbody th { background: var(--accent); color: var(--ink); }
```

```
.schedule td { padding: .6rem; border-radius: 6px; text-align: center;
 background: #f6f6f6; min-height: 3rem; }
.schedule td:not(:empty) { background: var(--accent); font-weight:
600; border: 2px solid var(--brand); }
```

Project 504 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - Weekly schedule</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Weekly schedule	The main heading; only one per page.
	Generic block container for grouping and layout.
<table class="schedule">	Tabular data in rows and columns.
<caption>Services by day and time</caption>	Title of the table.
<thead><tr><th scope="col">Time</th><th scope="col">Sat</th><th sco...	Group of header rows.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">9:00</th><td>Check-up</td><td></td><td>Check-up...	A table row.
<tr><th scope="row">11:00</th><td></td><td>Whitening</td><td></td><...	Header cell for a row.
<tr><th scope="row">13:00</th><td>Filling</td><td></td><td>Filling<...	A header cell.
<tr><th scope="row">15:00</th><td></td><td>Braces consultation</td>...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
border-collapse: separate;	Keeps each cell's border separate so cells look like tiles.
border-spacing: 4px;	Gap between cells in the separate border model.
width: 100%;	Fills the container width.
background: var(--brand);	Background colour or image.
border-radius: 6px;	Rounds the corners.
border-radius: 6px;	The line around the element: width, style and colour.
text-align: center;	Centres inline content such as text.
.schedule td:not(:empty) {	Excludes elements from a selector.
font-weight: 600;	Thickness of the text.
border: 2px solid var(--brand);	Changes the visual order of a flex item without changing the source.

Check your work

- Every cell exists even if empty
- Row and column headers have scope
- Tiles have rounded corners
- Table scrolls on narrow screens

Exercises

1. Add rowspan for a two-hour slot.

2. Colour by category with classes.
3. Make the time column sticky with position: sticky; left: 0.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 505: Weekly schedule grid for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 2 | Files: index.html, styles.css

Brief

Build a timetable as a table with separate, rounded cells where booked slots are highlighted with :not(:empty).

Learning goals

- Use the separate border model with border-spacing
- Highlight cells based on content with :empty
- Keep a wide table scrollable

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td	border-collapse: separate, border-spacing, :not(:empty), border-radius on cells, min-width

Build guide

1. Write the header row with the days.
2. Write one row per time slot; the first cell is th scope="row".
3. Leave empty <td></td> for free slots.
4. Use border-collapse: separate and border-spacing so cells look like tiles.
5. Style non-empty cells with :not(:empty).
6. Wrap for horizontal scrolling.

Project 505: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - Weekly schedule</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Weekly schedule</h1>
    <div class="wrap">
      <table class="schedule">
        <caption>Tours by day and time</caption>
        <thead><tr><th scope="col">Time</th><th scope="col">Sat</
th><th scope="col">Sun</th><th scope="col">Mon</th><th
scope="col">Tue</th><th scope="col">Wed</th></tr></thead>
        <tbody>
          <tr><th scope="row">9:00</th><td>Luxor day trip</td><td></
td><td>Luxor day trip</td><td></td><td>Luxor day trip</td></tr>
          <tr><th scope="row">11:00</th><td></td><td>Snorkelling</
td><td></td><td>Snorkelling</td><td></td></tr>
          <tr><th scope="row">13:00</th><td>Desert safari</td><td></
td><td>Desert safari</td><td></td><td>Desert safari</td></tr>
          <tr><th scope="row">15:00</th><td></td><td>Nile cruise</
td><td></td><td>Nile cruise</td><td></td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 505: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.wrap { overflow-x: auto; }
.schedule { border-collapse: separate; border-spacing: 4px; width:
100%; min-width: 36rem; }
.schedule th { background: var(--brand); color: #fff; padding: .5rem;
border-radius: 6px; }
.schedule tbody th { background: var(--accent); color: var(--ink); }
```

```
.schedule td { padding: .6rem; border-radius: 6px; text-align: center;
 background: #f6f6f6; min-height: 3rem; }
.schedule td:not(:empty) { background: var(--accent); font-weight:
600; border: 2px solid var(--brand); }
```

Project 505 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - Weekly schedule</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Weekly schedule	The main heading; only one per page.
	Generic block container for grouping and layout.
<table class="schedule">	Tabular data in rows and columns.
<caption>Tours by day and time</caption>	Title of the table.
<thead><tr><th scope="col">Time</th><th scope="col">Sat</th><th sco...	Group of header rows.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">9:00</th><td>Luxor day trip</td><td></td><td>Lu...	A table row.
<tr><th scope="row">11:00</th><td></td><td>Snorkelling</td><td></td...	Header cell for a row.
<tr><th scope="row">13:00</th><td>Desert safari</td><td></td><td>De...	A header cell.
<tr><th scope="row">15:00</th><td></td><td>Nile cruise</td><td></td...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
border-collapse: separate;	Keeps each cell's border separate so cells look like tiles.
border-spacing: 4px;	Gap between cells in the separate border model.
width: 100%;	Fills the container width.
background: var(--brand);	Background colour or image.
border-radius: 6px;	Rounds the corners.
border-radius: 6px;	The line around the element: width, style and colour.
text-align: center;	Centres inline content such as text.
.schedule td:not(:empty) {	Excludes elements from a selector.
font-weight: 600;	Thickness of the text.
border: 2px solid var(--brand);	Changes the visual order of a flex item without changing the source.

Check your work

- Every cell exists even if empty
- Row and column headers have scope
- Tiles have rounded corners
- Table scrolls on narrow screens

Exercises

1. Add rowspan for a two-hour slot.

2. Colour by category with classes.
3. Make the time column sticky with position: sticky; left: 0.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 506: Weekly schedule grid for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Build a timetable as a table with separate, rounded cells where booked slots are highlighted with :not(:empty).

Learning goals

- Use the separate border model with border-spacing
- Highlight cells based on content with :empty
- Keep a wide table scrollable

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td	border-collapse: separate, border-spacing, :not(:empty), border-radius on cells, min-width

Build guide

1. Write the header row with the days.
2. Write one row per time slot; the first cell is th scope="row".
3. Leave empty <td></td> for free slots.
4. Use border-collapse: separate and border-spacing so cells look like tiles.
5. Style non-empty cells with :not(:empty).

6. Wrap for horizontal scrolling.

Project 506: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - Weekly schedule</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Weekly schedule</h1>
    <div class="wrap">
      <table class="schedule">
        <caption>Courses by day and time</caption>
        <thead><tr><th scope="col">Time</th><th scope="col">Sat</
th><th scope="col">Sun</th><th scope="col">Mon</th><th
scope="col">Tue</th><th scope="col">Wed</th></tr></thead>
        <tbody>
          <tr><th scope="row">9:00</th><td>English A1</td><td></
td><td>English A1</td><td></td><td>English A1</td></tr>
          <tr><th scope="row">11:00</th><td></td><td>French B1</
td><td></td><td>French B1</td><td></td></tr>
          <tr><th scope="row">13:00</th><td>German A2</td><td></
td><td>German A2</td><td></td><td>German A2</td></tr>
          <tr><th scope="row">15:00</th><td></td><td>IELTS
preparation</td><td></td><td>IELTS preparation</td><td></td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 506: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.wrap { overflow-x: auto; }
.schedule { border-collapse: separate; border-spacing: 4px; width:
100%; min-width: 36rem; }
.schedule th { background: var(--brand); color: #fff; padding: .5rem;
border-radius: 6px; }
.schedule tbody th { background: var(--accent); color: var(--ink); }
```

```
.schedule td { padding: .6rem; border-radius: 6px; text-align: center;
 background: #f6f6f6; min-height: 3rem; }
.schedule td:not(:empty) { background: var(--accent); font-weight:
600; border: 2px solid var(--brand); }
```

Project 506 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - Weekly schedule</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Weekly schedule	The main heading; only one per page.
	Generic block container for grouping and layout.
<table class="schedule">	Tabular data in rows and columns.
<caption>Courses by day and time</caption>	Title of the table.
<thead><tr><th scope="col">Time</th><th scope="col">Sat</th><th sco...	Group of header rows.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">9:00</th><td>English A1</td><td></td><td>Englis...	A table row.
<tr><th scope="row">11:00</th><td></td><td>French B1</td><td></td><...	Header cell for a row.
<tr><th scope="row">13:00</th><td>German A2</td><td></td><td>German...	A header cell.
<tr><th scope="row">15:00</th><td></td><td>IELTS preparation</td><t...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
border-collapse: separate;	Keeps each cell's border separate so cells look like tiles.
border-spacing: 4px;	Gap between cells in the separate border model.
width: 100%;	Fills the container width.
background: var(--brand);	Background colour or image.
border-radius: 6px;	Rounds the corners.
border-radius: 6px;	The line around the element: width, style and colour.
text-align: center;	Centres inline content such as text.
.schedule td:not(:empty) {	Excludes elements from a selector.
font-weight: 600;	Thickness of the text.
border: 2px solid var(--brand);	Changes the visual order of a flex item without changing the source.

Check your work

- Every cell exists even if empty
- Row and column headers have scope
- Tiles have rounded corners
- Table scrolls on narrow screens

Exercises

1. Add rowspan for a two-hour slot.

2. Colour by category with classes.
3. Make the time column sticky with position: sticky; left: 0.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 507: Weekly schedule grid for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 2 | Files: index.html, styles.css

Brief

Build a timetable as a table with separate, rounded cells where booked slots are highlighted with :not(:empty).

Learning goals

- Use the separate border model with border-spacing
- Highlight cells based on content with :empty
- Keep a wide table scrollable

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td	border-collapse: separate, border-spacing, :not(:empty), border-radius on cells, min-width

Build guide

1. Write the header row with the days.
2. Write one row per time slot; the first cell is th scope="row".
3. Leave empty <td></td> for free slots.
4. Use border-collapse: separate and border-spacing so cells look like tiles.
5. Style non-empty cells with :not(:empty).
6. Wrap for horizontal scrolling.

Project 507: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - Weekly schedule</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Weekly schedule</h1>
    <div class="wrap">
      <table class="schedule">
        <caption>Drinks by day and time</caption>
        <thead><tr><th scope="col">Time</th><th scope="col">Sat</
th><th scope="col">Sun</th><th scope="col">Mon</th><th
scope="col">Tue</th><th scope="col">Wed</th></tr></thead>
        <tbody>
          <tr><th scope="row">9:00</th><td>Flat white</td><td></
td><td>Flat white</td><td></td><td>Flat white</td></tr>
          <tr><th scope="row">11:00</th><td></td><td>Cold brew</
td><td></td><td>Cold brew</td><td></td></tr>
          <tr><th scope="row">13:00</th><td>Hibiscus iced tea</
td><td></td><td>Hibiscus iced tea</td><td></td><td>Hibiscus iced tea</
td></tr>
          <tr><th scope="row">15:00</th><td></td><td>Cheesecake</
td><td></td><td>Cheesecake</td><td></td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 507: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.wrap { overflow-x: auto; }
.schedule { border-collapse: separate; border-spacing: 4px; width:
100%; min-width: 36rem; }
.schedule th { background: var(--brand); color: #fff; padding: .5rem;
border-radius: 6px; }
```

```
.schedule tbody th { background: var(--accent); color: var(--ink); }
.schedule td { padding: .6rem; border-radius: 6px; text-align: center;
 background: #f6f6f6; min-height: 3rem; }
.schedule td:not(:empty) { background: var(--accent); font-weight:
600; border: 2px solid var(--brand); }
```

Project 507 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - Weekly schedule</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Weekly schedule	The main heading; only one per page.
	Generic block container for grouping and layout.
<table class="schedule">	Tabular data in rows and columns.
<caption>Drinks by day and time</caption>	Title of the table.
<thead><tr><th scope="col">Time</th><th scope="col">Sat</th><th sco...	Group of header rows.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">9:00</th><td>Flat white</td><td></td><td>Flat w...	A table row.
<tr><th scope="row">11:00</th><td></td><td>Cold brew</td><td></td><...	Header cell for a row.
<tr><th scope="row">13:00</th><td>Hibiscus iced tea</td><td></td><t...	A header cell.
<tr><th scope="row">15:00</th><td></td><td>Cheese cake</td><td></td>...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
border-collapse: separate;	Keeps each cell's border separate so cells look like tiles.
border-spacing: 4px;	Gap between cells in the separate border model.
width: 100%;	Fills the container width.
background: var(--brand);	Background colour or image.
border-radius: 6px;	Rounds the corners.
border-radius: 6px;	The line around the element: width, style and colour.
text-align: center;	Centres inline content such as text.
.schedule td:not(:empty) {	Excludes elements from a selector.
font-weight: 600;	Thickness of the text.
border: 2px solid var(--brand);	Changes the visual order of a flex item without changing the source.

Check your work

- Every cell exists even if empty
- Row and column headers have scope
- Tiles have rounded corners
- Table scrolls on narrow screens

Exercises

1. Add rowspan for a two-hour slot.

2. Colour by category with classes.
3. Make the time column sticky with position: sticky; left: 0.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 508: Weekly schedule grid for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 2 | Files: index.html, styles.css

Brief

Build a timetable as a table with separate, rounded cells where booked slots are highlighted with :not(:empty).

Learning goals

- Use the separate border model with border-spacing
- Highlight cells based on content with :empty
- Keep a wide table scrollable

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td	border-collapse: separate, border-spacing, :not(:empty), border-radius on cells, min-width

Build guide

1. Write the header row with the days.
2. Write one row per time slot; the first cell is th scope="row".
3. Leave empty <td></td> for free slots.
4. Use border-collapse: separate and border-spacing so cells look like tiles.
5. Style non-empty cells with :not(:empty).
6. Wrap for horizontal scrolling.

Project 508: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - Weekly schedule</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Weekly schedule</h1>
    <div class="wrap">
      <table class="schedule">
        <caption>Hikes by day and time</caption>
        <thead><tr><th scope="col">Time</th><th scope="col">Sat</
th><th scope="col">Sun</th><th scope="col">Mon</th><th
scope="col">Tue</th><th scope="col">Wed</th></tr></thead>
        <tbody>
          <tr><th scope="row">9:00</th><td>Mount Sinai sunrise</
td><td></td><td>Mount Sinai sunrise</td><td></td><td>Mount Sinai
sunrise</td></tr>
          <tr><th scope="row">11:00</th><td></td><td>Blue Desert
loop</td><td></td><td>Blue Desert loop</td><td></td></tr>
          <tr><th scope="row">13:00</th><td>Wadi Gnai</td><td></
td><td>Wadi Gnai</td><td></td><td>Wadi Gnai</td></tr>
          <tr><th scope="row">15:00</th><td></td><td>Three-day
traverse</td><td></td><td>Three-day traverse</td><td></td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 508: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.wrap { overflow-x: auto; }
.schedule { border-collapse: separate; border-spacing: 4px; width:
100%; min-width: 36rem; }
.schedule th { background: var(--brand); color: #fff; padding: .5rem;
border-radius: 6px; }
```

```
.schedule tbody th { background: var(--accent); color: var(--ink); }
.schedule td { padding: .6rem; border-radius: 6px; text-align: center;
 background: #f6f6f6; min-height: 3rem; }
.schedule td:not(:empty) { background: var(--accent); font-weight:
600; border: 2px solid var(--brand); }
```

Project 508 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - Weekly schedule</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Weekly schedule	The main heading; only one per page.
	Generic block container for grouping and layout.
<table class="schedule">	Tabular data in rows and columns.
<caption>Hikes by day and time</caption>	Title of the table.
<thead><tr><th scope="col">Time</th><th scope="col">Sat</th><th sco...	Group of header rows.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">9:00</th><td>Mount Sinai sunrise</td><td></td><...	A table row.
<tr><th scope="row">11:00</th><td></td><td>Blue Desert loop</td><td...	Header cell for a row.
<tr><th scope="row">13:00</th><td>Wadi Gnai</td><td></td><td>Wadi G...	A header cell.
<tr><th scope="row">15:00</th><td></td><td>Three-day traverse</td><...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
border-collapse: separate;	Keeps each cell's border separate so cells look like tiles.
border-spacing: 4px;	Gap between cells in the separate border model.
width: 100%;	Fills the container width.
background: var(--brand);	Background colour or image.
border-radius: 6px;	Rounds the corners.
border-radius: 6px;	The line around the element: width, style and colour.
text-align: center;	Centres inline content such as text.
.schedule td:not(:empty) {	Excludes elements from a selector.
font-weight: 600;	Thickness of the text.
border: 2px solid var(--brand);	Changes the visual order of a flex item without changing the source.

Check your work

- Every cell exists even if empty
- Row and column headers have scope
- Tiles have rounded corners
- Table scrolls on narrow screens

Exercises

1. Add rowspan for a two-hour slot.

2. Colour by category with classes.
3. Make the time column sticky with position: sticky; left: 0.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 509: Weekly schedule grid for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 2 | Files: index.html, styles.css

Brief

Build a timetable as a table with separate, rounded cells where booked slots are highlighted with :not(:empty).

Learning goals

- Use the separate border model with border-spacing
- Highlight cells based on content with :empty
- Keep a wide table scrollable

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td	border-collapse: separate, border-spacing, :not(:empty), border-radius on cells, min-width

Build guide

1. Write the header row with the days.
2. Write one row per time slot; the first cell is th scope="row".
3. Leave empty <td></td> for free slots.
4. Use border-collapse: separate and border-spacing so cells look like tiles.
5. Style non-empty cells with :not(:empty).
6. Wrap for horizontal scrolling.

Project 509: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - Weekly schedule</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Weekly schedule</h1>
    <div class="wrap">
      <table class="schedule">
        <caption>Sessions by day and time</caption>
        <thead><tr><th scope="col">Time</th><th scope="col">Sat</
th><th scope="col">Sun</th><th scope="col">Mon</th><th
scope="col">Tue</th><th scope="col">Wed</th></tr></thead>
        <tbody>
          <tr><th scope="row">9:00</th><td>Portrait session</td><td></
td><td>Portrait session</td><td></td><td>Portrait session</td></tr>
          <tr><th scope="row">11:00</th><td></td><td>Wedding day</
td><td></td><td>Wedding day</td><td></td></tr>
          <tr><th scope="row">13:00</th><td>Product shoot</td><td></
td><td>Product shoot</td><td></td><td>Product shoot</td></tr>
          <tr><th scope="row">15:00</th><td></td><td>Family session</
td><td></td><td>Family session</td><td></td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 509: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.wrap { overflow-x: auto; }
.schedule { border-collapse: separate; border-spacing: 4px; width:
100%; min-width: 36rem; }
.schedule th { background: var(--brand); color: #fff; padding: .5rem;
border-radius: 6px; }
.schedule tbody th { background: var(--accent); color: var(--ink); }
```

```
.schedule td { padding: .6rem; border-radius: 6px; text-align: center;
 background: #f6f6f6; min-height: 3rem; }
.schedule td:not(:empty) { background: var(--accent); font-weight:
600; border: 2px solid var(--brand); }
```

Project 509 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - Weekly schedule</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Weekly schedule	The main heading; only one per page.
	Generic block container for grouping and layout.
<table class="schedule">	Tabular data in rows and columns.
<caption>Sessions by day and time</caption>	Title of the table.
<thead><tr><th scope="col">Time</th><th scope="col">Sat</th><th sco...	Group of header rows.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">9:00</th><td>Portrait session</td><td></td><td>...	A table row.
<tr><th scope="row">11:00</th><td></td><td>Wedding day</td><td></td...	Header cell for a row.
<tr><th scope="row">13:00</th><td>Product shoot</td><td></td><td>Pr...	A header cell.
<tr><th scope="row">15:00</th><td></td><td>Family session</td><td><...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
border-collapse: separate;	Keeps each cell's border separate so cells look like tiles.
border-spacing: 4px;	Gap between cells in the separate border model.
width: 100%;	Fills the container width.
background: var(--brand);	Background colour or image.
border-radius: 6px;	Rounds the corners.
border-radius: 6px;	The line around the element: width, style and colour.
text-align: center;	Centres inline content such as text.
.schedule td:not(:empty) {	Excludes elements from a selector.
font-weight: 600;	Thickness of the text.
border: 2px solid var(--brand);	Changes the visual order of a flex item without changing the source.

Check your work

- Every cell exists even if empty
- Row and column headers have scope
- Tiles have rounded corners
- Table scrolls on narrow screens

Exercises

1. Add rowspan for a two-hour slot.

2. Colour by category with classes.
3. Make the time column sticky with position: sticky; left: 0.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 510: Weekly schedule grid for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 2 | Files: index.html, styles.css

Brief

Build a timetable as a table with separate, rounded cells where booked slots are highlighted with :not(:empty).

Learning goals

- Use the separate border model with border-spacing
- Highlight cells based on content with :empty
- Keep a wide table scrollable

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td	border-collapse: separate, border-spacing, :not(:empty), border-radius on cells, min-width

Build guide

1. Write the header row with the days.
2. Write one row per time slot; the first cell is th scope="row".
3. Leave empty <td></td> for free slots.
4. Use border-collapse: separate and border-spacing so cells look like tiles.
5. Style non-empty cells with :not(:empty).
6. Wrap for horizontal scrolling.

Project 510: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - Weekly schedule</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Weekly schedule</h1>
    <div class="wrap">
      <table class="schedule">
        <caption>Products by day and time</caption>
        <thead><tr><th scope="col">Time</th><th scope="col">Sat</
th><th scope="col">Sun</th><th scope="col">Mon</th><th
scope="col">Tue</th><th scope="col">Wed</th></tr></thead>
        <tbody>
          <tr><th scope="row">9:00</th><td>Dotted notebook</td><td></
td><td>Dotted notebook</td><td></td><td>Dotted notebook</td></tr>
          <tr><th scope="row">11:00</th><td></td><td>Fountain pen</
td><td></td><td>Fountain pen</td><td></td></tr>
          <tr><th scope="row">13:00</th><td>Washi tape set</td><td></
td><td>Washi tape set</td><td></td><td>Washi tape set</td></tr>
          <tr><th scope="row">15:00</th><td></td><td>Desk planner</
td><td></td><td>Desk planner</td><td></td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 510: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.wrap { overflow-x: auto; }
.schedule { border-collapse: separate; border-spacing: 4px; width:
100%; min-width: 36rem; }
.schedule th { background: var(--brand); color: #fff; padding: .5rem;
border-radius: 6px; }
.schedule tbody th { background: var(--accent); color: var(--ink); }
```

```
.schedule td { padding: .6rem; border-radius: 6px; text-align: center;
 background: #f6f6f6; min-height: 3rem; }
.schedule td:not(:empty) { background: var(--accent); font-weight:
600; border: 2px solid var(--brand); }
```

Project 510 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - Weekly schedule</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Weekly schedule	The main heading; only one per page.
	Generic block container for grouping and layout.
<table class="schedule">	Tabular data in rows and columns.
<caption>Products by day and time</caption>	Title of the table.
<thead><tr><th scope="col">Time</th><th scope="col">Sat</th><th sco...	Group of header rows.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">9:00</th><td>Dotted notebook</td><td></td><td>D...	A table row.
<tr><th scope="row">11:00</th><td></td><td>Fountain pen</td><td></t...	Header cell for a row.
<tr><th scope="row">13:00</th><td>Washi tape set</td><td></td><td>W...	A header cell.
<tr><th scope="row">15:00</th><td></td><td>Desk planner</td><td></t...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
border-collapse: separate;	Keeps each cell's border separate so cells look like tiles.
border-spacing: 4px;	Gap between cells in the separate border model.
width: 100%;	Fills the container width.
background: var(--brand);	Background colour or image.
border-radius: 6px;	Rounds the corners.
border-radius: 6px;	The line around the element: width, style and colour.
text-align: center;	Centres inline content such as text.
.schedule td:not(:empty) {	Excludes elements from a selector.
font-weight: 600;	Thickness of the text.
border: 2px solid var(--brand);	Changes the visual order of a flex item without changing the source.

Check your work

- Every cell exists even if empty
- Row and column headers have scope
- Tiles have rounded corners
- Table scrolls on narrow screens

Exercises

1. Add rowspan for a two-hour slot.

2. Colour by category with classes.
3. Make the time column sticky with position: sticky; left: 0.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 511: Weekly schedule grid for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 2 | Files: index.html, styles.css

Brief

Build a timetable as a table with separate, rounded cells where booked slots are highlighted with :not(:empty).

Learning goals

- Use the separate border model with border-spacing
- Highlight cells based on content with :empty
- Keep a wide table scrollable

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td	border-collapse: separate, border-spacing, :not(:empty), border-radius on cells, min-width

Build guide

1. Write the header row with the days.
2. Write one row per time slot; the first cell is th scope="row".
3. Leave empty <td></td> for free slots.
4. Use border-collapse: separate and border-spacing so cells look like tiles.
5. Style non-empty cells with :not(:empty).
6. Wrap for horizontal scrolling.

Project 511: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - Weekly schedule</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Weekly schedule</h1>
    <div class="wrap">
      <table class="schedule">
        <caption>Plants by day and time</caption>
        <thead><tr><th scope="col">Time</th><th scope="col">Sat</
th><th scope="col">Sun</th><th scope="col">Mon</th><th
scope="col">Tue</th><th scope="col">Wed</th></tr></thead>
        <tbody>
          <tr><th scope="row">9:00</th><td>Monstera</td><td></
td><td>Monstera</td><td></td><td>Monstera</td></tr>
          <tr><th scope="row">11:00</th><td></td><td>Snake plant</
td><td></td><td>Snake plant</td><td></td></tr>
          <tr><th scope="row">13:00</th><td>Basil pot</td><td></
td><td>Basil pot</td><td></td><td>Basil pot</td></tr>
          <tr><th scope="row">15:00</th><td></td><td>Olive tree</
td><td></td><td>Olive tree</td><td></td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 511: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.wrap { overflow-x: auto; }
.schedule { border-collapse: separate; border-spacing: 4px; width:
100%; min-width: 36rem; }
.schedule th { background: var(--brand); color: #fff; padding: .5rem;
border-radius: 6px; }
.schedule tbody th { background: var(--accent); color: var(--ink); }
```

```
.schedule td { padding: .6rem; border-radius: 6px; text-align: center;
 background: #f6f6f6; min-height: 3rem; }
.schedule td:not(:empty) { background: var(--accent); font-weight:
600; border: 2px solid var(--brand); }
```

Project 511 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - Weekly schedule</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Weekly schedule	The main heading; only one per page.
	Generic block container for grouping and layout.
<table class="schedule">	Tabular data in rows and columns.
<caption>Plants by day and time</caption>	Title of the table.
<thead><tr><th scope="col">Time</th><th scope="col">Sat</th><th sco...	Group of header rows.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">9:00</th><td>Monstera</td><td></td><td>Monstera...	A table row.
<tr><th scope="row">11:00</th><td></td><td>Snake plant</td><td></td...	Header cell for a row.
<tr><th scope="row">13:00</th><td>Basil pot</td><td></td><td>Basil...	A header cell.
<tr><th scope="row">15:00</th><td></td><td>Olive tree</td><td></td>...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
border-collapse: separate;	Keeps each cell's border separate so cells look like tiles.
border-spacing: 4px;	Gap between cells in the separate border model.
width: 100%;	Fills the container width.
background: var(--brand);	Background colour or image.
border-radius: 6px;	Rounds the corners.
border-radius: 6px;	The line around the element: width, style and colour.
text-align: center;	Centres inline content such as text.
.schedule td:not(:empty) {	Excludes elements from a selector.
font-weight: 600;	Thickness of the text.
border: 2px solid var(--brand);	Changes the visual order of a flex item without changing the source.

Check your work

- Every cell exists even if empty
- Row and column headers have scope
- Tiles have rounded corners
- Table scrolls on narrow screens

Exercises

1. Add rowspan for a two-hour slot.

2. Colour by category with classes.
3. Make the time column sticky with position: sticky; left: 0.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 512: Weekly schedule grid for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 2 | Files: index.html, styles.css

Brief

Build a timetable as a table with separate, rounded cells where booked slots are highlighted with :not(:empty).

Learning goals

- Use the separate border model with border-spacing
- Highlight cells based on content with :empty
- Keep a wide table scrollable

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td	border-collapse: separate, border-spacing, :not(:empty), border-radius on cells, min-width

Build guide

1. Write the header row with the days.
2. Write one row per time slot; the first cell is th scope="row".
3. Leave empty <td></td> for free slots.
4. Use border-collapse: separate and border-spacing so cells look like tiles.
5. Style non-empty cells with :not(:empty).
6. Wrap for horizontal scrolling.

Project 512: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - Weekly schedule</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Weekly schedule</h1>
    <div class="wrap">
      <table class="schedule">
        <caption>Pieces by day and time</caption>
        <thead><tr><th scope="col">Time</th><th scope="col">Sat</
th><th scope="col">Sun</th><th scope="col">Mon</th><th
scope="col">Tue</th><th scope="col">Wed</th></tr></thead>
        <tbody>
          <tr><th scope="row">9:00</th><td>Oak dining table</td><td></
td><td>Oak dining table</td><td></td><td>Oak dining table</td></tr>
          <tr><th scope="row">11:00</th><td></td><td>Bookshelf</
td><td></td><td>Bookshelf</td><td></td></tr>
          <tr><th scope="row">13:00</th><td>Bedside table</td><td></
td><td>Bedside table</td><td></td><td>Bedside table</td></tr>
          <tr><th scope="row">15:00</th><td></td><td>Coffee table</
td><td></td><td>Coffee table</td><td></td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 512: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.wrap { overflow-x: auto; }
.schedule { border-collapse: separate; border-spacing: 4px; width:
100%; min-width: 36rem; }
.schedule th { background: var(--brand); color: #fff; padding: .5rem;
border-radius: 6px; }
.schedule tbody th { background: var(--accent); color: var(--ink); }
```

```
.schedule td { padding: .6rem; border-radius: 6px; text-align: center;
 background: #f6f6f6; min-height: 3rem; }
.schedule td:not(:empty) { background: var(--accent); font-weight:
600; border: 2px solid var(--brand); }
```

Project 512 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - Weekly schedule</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Weekly schedule	The main heading; only one per page.
	Generic block container for grouping and layout.
<table class="schedule">	Tabular data in rows and columns.
<caption>Pieces by day and time</caption>	Title of the table.
<thead><tr><th scope="col">Time</th><th scope="col">Sat</th><th sco...	Group of header rows.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">9:00</th><td>Oak dining table</td><td></td><td>...	A table row.
<tr><th scope="row">11:00</th><td></td><td>Bookshelf</td><td></td><...	Header cell for a row.
<tr><th scope="row">13:00</th><td>Bedside table</td><td></td><td>Be...	A header cell.
<tr><th scope="row">15:00</th><td></td><td>Coffee table</td><td></t...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
border-collapse: separate;	Keeps each cell's border separate so cells look like tiles.
border-spacing: 4px;	Gap between cells in the separate border model.
width: 100%;	Fills the container width.
background: var(--brand);	Background colour or image.
border-radius: 6px;	Rounds the corners.
border-radius: 6px;	The line around the element: width, style and colour.
text-align: center;	Centres inline content such as text.
.schedule td:not(:empty) {	Excludes elements from a selector.
font-weight: 600;	Thickness of the text.
border: 2px solid var(--brand);	Changes the visual order of a flex item without changing the source.

Check your work

- Every cell exists even if empty
- Row and column headers have scope
- Tiles have rounded corners
- Table scrolls on narrow screens

Exercises

1. Add rowspan for a two-hour slot.

2. Colour by category with classes.
3. Make the time column sticky with position: sticky; left: 0.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 513: Weekly schedule grid for Byte Repair

Theme: Byte Repair (Nasr City) | Level 2 | Files: index.html, styles.css

Brief

Build a timetable as a table with separate, rounded cells where booked slots are highlighted with :not(:empty).

Learning goals

- Use the separate border model with border-spacing
- Highlight cells based on content with :empty
- Keep a wide table scrollable

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td	border-collapse: separate, border-spacing, :not(:empty), border-radius on cells, min-width

Build guide

1. Write the header row with the days.
2. Write one row per time slot; the first cell is th scope="row".
3. Leave empty <td></td> for free slots.
4. Use border-collapse: separate and border-spacing so cells look like tiles.
5. Style non-empty cells with :not(:empty).
6. Wrap for horizontal scrolling.

Project 513: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - Weekly schedule</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Weekly schedule</h1>
    <div class="wrap">
      <table class="schedule">
        <caption>Repairs by day and time</caption>
        <thead><tr><th scope="col">Time</th><th scope="col">Sat</
th><th scope="col">Sun</th><th scope="col">Mon</th><th
scope="col">Tue</th><th scope="col">Wed</th></tr></thead>
        <tbody>
          <tr><th scope="row">9:00</th><td>Screen replacement</
td><td></td><td>Screen replacement</td><td></td><td>Screen
replacement</td></tr>
          <tr><th scope="row">11:00</th><td></td><td>Battery swap</
td><td></td><td>Battery swap</td><td></td></tr>
          <tr><th scope="row">13:00</th><td>Laptop cleaning</td><td></
td><td>Laptop cleaning</td><td></td><td>Laptop cleaning</td></tr>
          <tr><th scope="row">15:00</th><td></td><td>Data recovery</
td><td></td><td>Data recovery</td><td></td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 513: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.wrap { overflow-x: auto; }
.schedule { border-collapse: separate; border-spacing: 4px; width:
100%; min-width: 36rem; }
.schedule th { background: var(--brand); color: #fff; padding: .5rem;
border-radius: 6px; }
```

```
.schedule tbody th { background: var(--accent); color: var(--ink); }
.schedule td { padding: .6rem; border-radius: 6px; text-align: center;
 background: #f6f6f6; min-height: 3rem; }
.schedule td:not(:empty) { background: var(--accent); font-weight:
600; border: 2px solid var(--brand); }
```

Project 513 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - Weekly schedule</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Weekly schedule	The main heading; only one per page.
	Generic block container for grouping and layout.
<table class="schedule">	Tabular data in rows and columns.
<caption>Repairs by day and time</caption>	Title of the table.
<thead><tr><th scope="col">Time</th><th scope="col">Sat</th><th sco...	Group of header rows.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">9:00</th><td>Screen replacement</td><td></td><t...	A table row.
<tr><th scope="row">11:00</th><td></td><td>Battery swap</td><td></t...	Header cell for a row.
<tr><th scope="row">13:00</th><td>Laptop cleaning</td><td></td><td>...	A header cell.
<tr><th scope="row">15:00</th><td></td><td>Data recovery</td><td></...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
border-collapse: separate;	Keeps each cell's border separate so cells look like tiles.
border-spacing: 4px;	Gap between cells in the separate border model.
width: 100%;	Fills the container width.
background: var(--brand);	Background colour or image.
border-radius: 6px;	Rounds the corners.
border-radius: 6px;	The line around the element: width, style and colour.
text-align: center;	Centres inline content such as text.
.schedule td:not(:empty) {	Excludes elements from a selector.
font-weight: 600;	Thickness of the text.
border: 2px solid var(--brand);	Changes the visual order of a flex item without changing the source.

Check your work

- Every cell exists even if empty
- Row and column headers have scope
- Tiles have rounded corners
- Table scrolls on narrow screens

Exercises

1. Add rowspan for a two-hour slot.

2. Colour by category with classes.
3. Make the time column sticky with position: sticky; left: 0.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 514: Weekly schedule grid for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 2 | Files: index.html, styles.css

Brief

Build a timetable as a table with separate, rounded cells where booked slots are highlighted with :not(:empty).

Learning goals

- Use the separate border model with border-spacing
- Highlight cells based on content with :empty
- Keep a wide table scrollable

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td	border-collapse: separate, border-spacing, :not(:empty), border-radius on cells, min-width

Build guide

1. Write the header row with the days.
2. Write one row per time slot; the first cell is th scope="row".
3. Leave empty <td></td> for free slots.
4. Use border-collapse: separate and border-spacing so cells look like tiles.
5. Style non-empty cells with :not(:empty).
6. Wrap for horizontal scrolling.

Project 514: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - Weekly schedule</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Weekly schedule</h1>
    <div class="wrap">
      <table class="schedule">
        <caption>Services by day and time</caption>
        <thead><tr><th scope="col">Time</th><th scope="col">Sat</
th><th scope="col">Sun</th><th scope="col">Mon</th><th
scope="col">Tue</th><th scope="col">Wed</th></tr></thead>
        <tbody>
          <tr><th scope="row">9:00</th><td>Full grooming</td><td></
td><td>Full grooming</td><td></td><td>Full grooming</td></tr>
          <tr><th scope="row">11:00</th><td></td><td>Day boarding</
td><td></td><td>Day boarding</td><td></td></tr>
          <tr><th scope="row">13:00</th><td>Vaccination</td><td></
td><td>Vaccination</td><td></td><td>Vaccination</td></tr>
          <tr><th scope="row">15:00</th><td></td><td>Dog walking</
td><td></td><td>Dog walking</td><td></td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 514: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.wrap { overflow-x: auto; }
.schedule { border-collapse: separate; border-spacing: 4px; width:
100%; min-width: 36rem; }
.schedule th { background: var(--brand); color: #fff; padding: .5rem;
border-radius: 6px; }
.schedule tbody th { background: var(--accent); color: var(--ink); }
```

```
.schedule td { padding: .6rem; border-radius: 6px; text-align: center;
 background: #f6f6f6; min-height: 3rem; }
.schedule td:not(:empty) { background: var(--accent); font-weight:
600; border: 2px solid var(--brand); }
```

Project 514 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - Weekly schedule</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Weekly schedule	The main heading; only one per page.
	Generic block container for grouping and layout.
<table class="schedule">	Tabular data in rows and columns.
<caption>Services by day and time</caption>	Title of the table.
<thead><tr><th scope="col">Time</th><th scope="col">Sat</th><th sco...	Group of header rows.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">9:00</th><td>Full grooming</td><td></td><td>Ful...	A table row.
<tr><th scope="row">11:00</th><td></td><td>Day boarding</td><td></t...	Header cell for a row.
<tr><th scope="row">13:00</th><td>Vaccination</td><td></td><td>Vacc...	A header cell.
<tr><th scope="row">15:00</th><td></td><td>Dog walking</td><td></td...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
border-collapse: separate;	Keeps each cell's border separate so cells look like tiles.
border-spacing: 4px;	Gap between cells in the separate border model.
width: 100%;	Fills the container width.
background: var(--brand);	Background colour or image.
border-radius: 6px;	Rounds the corners.
border-radius: 6px;	The line around the element: width, style and colour.
text-align: center;	Centres inline content such as text.
.schedule td:not(:empty) {	Excludes elements from a selector.
font-weight: 600;	Thickness of the text.
border: 2px solid var(--brand);	Changes the visual order of a flex item without changing the source.

Check your work

- Every cell exists even if empty
- Row and column headers have scope
- Tiles have rounded corners
- Table scrolls on narrow screens

Exercises

1. Add rowspan for a two-hour slot.

2. Colour by category with classes.
3. Make the time column sticky with position: sticky; left: 0.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 515: Weekly schedule grid for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Build a timetable as a table with separate, rounded cells where booked slots are highlighted with :not(:empty).

Learning goals

- Use the separate border model with border-spacing
- Highlight cells based on content with :empty
- Keep a wide table scrollable

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td	border-collapse: separate, border-spacing, :not(:empty), border-radius on cells, min-width

Build guide

1. Write the header row with the days.
2. Write one row per time slot; the first cell is th scope="row".
3. Leave empty <td></td> for free slots.
4. Use border-collapse: separate and border-spacing so cells look like tiles.
5. Style non-empty cells with :not(:empty).

6. Wrap for horizontal scrolling.

Project 515: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - Weekly schedule</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Weekly schedule</h1>
    <div class="wrap">
      <table class="schedule">
        <caption>Lessons by day and time</caption>
        <thead><tr><th scope="col">Time</th><th scope="col">Sat</
th><th scope="col">Sun</th><th scope="col">Mon</th><th
scope="col">Tue</th><th scope="col">Wed</th></tr></thead>
        <tbody>
          <tr><th scope="row">9:00</th><td>Taster session</td><td></
td><td>Taster session</td><td></td><td>Taster session</td></tr>
          <tr><th scope="row">11:00</th><td></td><td>Beginner course</
td><td></td><td>Beginner course</td><td></td></tr>
          <tr><th scope="row">13:00</th><td>Racing clinic</td><td></
td><td>Racing clinic</td><td></td><td>Racing clinic</td></tr>
          <tr><th scope="row">15:00</th><td></td><td>Private lesson</
td><td></td><td>Private lesson</td><td></td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 515: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.wrap { overflow-x: auto; }
.schedule { border-collapse: separate; border-spacing: 4px; width:
100%; min-width: 36rem; }
.schedule th { background: var(--brand); color: #fff; padding: .5rem;
border-radius: 6px; }
.schedule tbody th { background: var(--accent); color: var(--ink); }
```

```
.schedule td { padding: .6rem; border-radius: 6px; text-align: center;
 background: #f6f6f6; min-height: 3rem; }
.schedule td:not(:empty) { background: var(--accent); font-weight:
600; border: 2px solid var(--brand); }
```

Project 515 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - Weekly schedule</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Weekly schedule	The main heading; only one per page.
	Generic block container for grouping and layout.
<table class="schedule">	Tabular data in rows and columns.
<caption>Lessons by day and time</caption>	Title of the table.
<thead><tr><th scope="col">Time</th><th scope="col">Sat</th><th sco...	Group of header rows.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">9:00</th><td>Taster session</td><td></td><td>Ta...	A table row.
<tr><th scope="row">11:00</th><td></td><td>Beginner course</td><td>...	Header cell for a row.
<tr><th scope="row">13:00</th><td>Racing clinic</td><td></td><td>Ra...	A header cell.
<tr><th scope="row">15:00</th><td></td><td>Private lesson</td><td><...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
border-collapse: separate;	Keeps each cell's border separate so cells look like tiles.
border-spacing: 4px;	Gap between cells in the separate border model.
width: 100%;	Fills the container width.
background: var(--brand);	Background colour or image.
border-radius: 6px;	Rounds the corners.
border-radius: 6px;	The line around the element: width, style and colour.
text-align: center;	Centres inline content such as text.
.schedule td:not(:empty) {	Excludes elements from a selector.
font-weight: 600;	Thickness of the text.
border: 2px solid var(--brand);	Changes the visual order of a flex item without changing the source.

Check your work

- Every cell exists even if empty
- Row and column headers have scope
- Tiles have rounded corners
- Table scrolls on narrow screens

Exercises

1. Add rowspan for a two-hour slot.

2. Colour by category with classes.
3. Make the time column sticky with position: sticky; left: 0.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 516: Weekly schedule grid for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Build a timetable as a table with separate, rounded cells where booked slots are highlighted with :not(:empty).

Learning goals

- Use the separate border model with border-spacing
- Highlight cells based on content with :empty
- Keep a wide table scrollable

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td	border-collapse: separate, border-spacing, :not(:empty), border-radius on cells, min-width

Build guide

1. Write the header row with the days.
2. Write one row per time slot; the first cell is th scope="row".
3. Leave empty <td></td> for free slots.
4. Use border-collapse: separate and border-spacing so cells look like tiles.
5. Style non-empty cells with :not(:empty).

6. Wrap for horizontal scrolling.

Project 516: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - Weekly schedule</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Weekly schedule</h1>
    <div class="wrap">
      <table class="schedule">
        <caption>Items by day and time</caption>
        <thead><tr><th scope="col">Time</th><th scope="col">Sat</
th><th scope="col">Sun</th><th scope="col">Mon</th><th
scope="col">Tue</th><th scope="col">Wed</th></tr></thead>
        <tbody>
          <tr><th scope="row">9:00</th><td>Lotus pendant</td><td></
td><td>Lotus pendant</td><td></td><td>Lotus pendant</td></tr>
          <tr><th scope="row">11:00</th><td></td><td>Brass cuff</
td><td></td><td>Brass cuff</td><td></td></tr>
          <tr><th scope="row">13:00</th><td>Bead earrings</td><td></
td><td>Bead earrings</td><td></td><td>Bead earrings</td></tr>
          <tr><th scope="row">15:00</th><td></td><td>Ankh ring</
td><td></td><td>Ankh ring</td><td></td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 516: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.wrap { overflow-x: auto; }
.schedule { border-collapse: separate; border-spacing: 4px; width:
100%; min-width: 36rem; }
.schedule th { background: var(--brand); color: #fff; padding: .5rem;
border-radius: 6px; }
.schedule tbody th { background: var(--accent); color: var(--ink); }
```

```
.schedule td { padding: .6rem; border-radius: 6px; text-align: center;
 background: #f6f6f6; min-height: 3rem; }
.schedule td:not(:empty) { background: var(--accent); font-weight:
600; border: 2px solid var(--brand); }
```

Project 516 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - Weekly schedule</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Weekly schedule	The main heading; only one per page.
	Generic block container for grouping and layout.
<table class="schedule">	Tabular data in rows and columns.
<caption>Items by day and time</caption>	Title of the table.
<thead><tr><th scope="col">Time</th><th scope="col">Sat</th><th sco...	Group of header rows.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">9:00</th><td>Lotus pendant</td><td></td><td>Lot...	A table row.
<tr><th scope="row">11:00</th><td></td><td>Brass cuff</td><td></td>...	Header cell for a row.
<tr><th scope="row">13:00</th><td>Bead earrings</td><td></td><td>Be...	A header cell.
<tr><th scope="row">15:00</th><td></td><td>Ankh ring</td><td></td><...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
border-collapse: separate;	Keeps each cell's border separate so cells look like tiles.
border-spacing: 4px;	Gap between cells in the separate border model.
width: 100%;	Fills the container width.
background: var(--brand);	Background colour or image.
border-radius: 6px;	Rounds the corners.
border-radius: 6px;	The line around the element: width, style and colour.
text-align: center;	Centres inline content such as text.
.schedule td:not(:empty) {	Excludes elements from a selector.
font-weight: 600;	Thickness of the text.
border: 2px solid var(--brand);	Changes the visual order of a flex item without changing the source.

Check your work

- Every cell exists even if empty
- Row and column headers have scope
- Tiles have rounded corners
- Table scrolls on narrow screens

Exercises

1. Add rowspan for a two-hour slot.

2. Colour by category with classes.
3. Make the time column sticky with position: sticky; left: 0.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 517: Weekly schedule grid for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 2 | Files: index.html, styles.css

Brief

Build a timetable as a table with separate, rounded cells where booked slots are highlighted with :not(:empty).

Learning goals

- Use the separate border model with border-spacing
- Highlight cells based on content with :empty
- Keep a wide table scrollable

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td	border-collapse: separate, border-spacing, :not(:empty), border-radius on cells, min-width

Build guide

1. Write the header row with the days.
2. Write one row per time slot; the first cell is th scope="row".
3. Leave empty <td></td> for free slots.
4. Use border-collapse: separate and border-spacing so cells look like tiles.
5. Style non-empty cells with :not(:empty).
6. Wrap for horizontal scrolling.

Project 517: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - Weekly schedule</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Weekly schedule</h1>
    <div class="wrap">
      <table class="schedule">
        <caption>Workshops by day and time</caption>
        <thead><tr><th scope="col">Time</th><th scope="col">Sat</
th><th scope="col">Sun</th><th scope="col">Mon</th><th
scope="col">Tue</th><th scope="col">Wed</th></tr></thead>
        <tbody>
          <tr><th scope="row">9:00</th><td>Intro to the wheel</
td><td></td><td>Intro to the wheel</td><td></td><td>Intro to the
wheel</td></tr>
          <tr><th scope="row">11:00</th><td></td><td>Glazing day</
td><td></td><td>Glazing day</td><td></td></tr>
          <tr><th scope="row">13:00</th><td>Kids clay class</td><td></
td><td>Kids clay class</td><td></td><td>Kids clay class</td></tr>
          <tr><th scope="row">15:00</th><td></td><td>Weekend retreat</
td><td></td><td>Weekend retreat</td><td></td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 517: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.wrap { overflow-x: auto; }
.schedule { border-collapse: separate; border-spacing: 4px; width:
100%; min-width: 36rem; }
.schedule th { background: var(--brand); color: #fff; padding: .5rem;
border-radius: 6px; }
```

```
.schedule tbody th { background: var(--accent); color: var(--ink); }
.schedule td { padding: .6rem; border-radius: 6px; text-align: center;
 background: #f6f6f6; min-height: 3rem; }
.schedule td:not(:empty) { background: var(--accent); font-weight:
600; border: 2px solid var(--brand); }
```

Project 517 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - Weekly schedule</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Weekly schedule	The main heading; only one per page.
	Generic block container for grouping and layout.
<table class="schedule">	Tabular data in rows and columns.
<caption>Workshops by day and time</caption>	Title of the table.
<thead><tr><th scope="col">Time</th><th scope="col">Sat</th><th sco...	Group of header rows.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">9:00</th><td>Intro to the wheel</td><td></td><t...	A table row.
<tr><th scope="row">11:00</th><td></td><td>Glazing day</td><td></td...	Header cell for a row.
<tr><th scope="row">13:00</th><td>Kids clay class</td><td></td><td>...	A header cell.
<tr><th scope="row">15:00</th><td></td><td>Weekend retreat</td><td>...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
border-collapse: separate;	Keeps each cell's border separate so cells look like tiles.
border-spacing: 4px;	Gap between cells in the separate border model.
width: 100%;	Fills the container width.
background: var(--brand);	Background colour or image.
border-radius: 6px;	Rounds the corners.
border-radius: 6px;	The line around the element: width, style and colour.
text-align: center;	Centres inline content such as text.
.schedule td:not(:empty) {	Excludes elements from a selector.
font-weight: 600;	Thickness of the text.
border: 2px solid var(--brand);	Changes the visual order of a flex item without changing the source.

Check your work

- Every cell exists even if empty
- Row and column headers have scope
- Tiles have rounded corners
- Table scrolls on narrow screens

Exercises

1. Add rowspan for a two-hour slot.

2. Colour by category with classes.
3. Make the time column sticky with position: sticky; left: 0.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 518: Weekly schedule grid for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 2 | Files: index.html, styles.css

Brief

Build a timetable as a table with separate, rounded cells where booked slots are highlighted with :not(:empty).

Learning goals

- Use the separate border model with border-spacing
- Highlight cells based on content with :empty
- Keep a wide table scrollable

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td	border-collapse: separate, border-spacing, :not(:empty), border-radius on cells, min-width

Build guide

1. Write the header row with the days.
2. Write one row per time slot; the first cell is th scope="row".
3. Leave empty <td></td> for free slots.
4. Use border-collapse: separate and border-spacing so cells look like tiles.
5. Style non-empty cells with :not(:empty).

6. Wrap for horizontal scrolling.

Project 518: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - Weekly schedule</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Weekly schedule</h1>
    <div class="wrap">
      <table class="schedule">
        <caption>Treatments by day and time</caption>
        <thead><tr><th scope="col">Time</th><th scope="col">Sat</
th><th scope="col">Sun</th><th scope="col">Mon</th><th
scope="col">Tue</th><th scope="col">Wed</th></tr></thead>
        <tbody>
          <tr><th scope="row">9:00</th><td>Haircut and blow-dry</
td><td></td><td>Haircut and blow-dry</td><td></td><td>Haircut and
blow-dry</td></tr>
          <tr><th scope="row">11:00</th><td></td><td>Manicure</
td><td></td><td>Manicure</td><td></td></tr>
          <tr><th scope="row">13:00</th><td>Facial</td><td></
td><td>Facial</td><td></td><td>Facial</td></tr>
          <tr><th scope="row">15:00</th><td></td><td>Bridal package</
td><td></td><td>Bridal package</td><td></td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 518: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.wrap { overflow-x: auto; }
.schedule { border-collapse: separate; border-spacing: 4px; width:
100%; min-width: 36rem; }
.schedule th { background: var(--brand); color: #fff; padding: .5rem;
border-radius: 6px; }
```

```
.schedule tbody th { background: var(--accent); color: var(--ink); }
.schedule td { padding: .6rem; border-radius: 6px; text-align: center;
 background: #f6f6f6; min-height: 3rem; }
.schedule td:not(:empty) { background: var(--accent); font-weight:
600; border: 2px solid var(--brand); }
```

Project 518 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - Weekly schedule</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Weekly schedule	The main heading; only one per page.
	Generic block container for grouping and layout.
<table class="schedule">	Tabular data in rows and columns.
<caption>Treatments by day and time</caption>	Title of the table.
<thead><tr><th scope="col">Time</th><th scope="col">Sat</th><th sco...	Group of header rows.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">9:00</th><td>Haircut and blow-dry</td><td></td>...	A table row.
<tr><th scope="row">11:00</th><td></td><td>Manicure</td><td></td><t...	Header cell for a row.
<tr><th scope="row">13:00</th><td>Facial</td><td></td><td>Facial</t...	A header cell.
<tr><th scope="row">15:00</th><td></td><td>Bridal package</td><td><...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
border-collapse: separate;	Keeps each cell's border separate so cells look like tiles.
border-spacing: 4px;	Gap between cells in the separate border model.
width: 100%;	Fills the container width.
background: var(--brand);	Background colour or image.
border-radius: 6px;	Rounds the corners.
border-radius: 6px;	The line around the element: width, style and colour.
text-align: center;	Centres inline content such as text.
.schedule td:not(:empty) {	Excludes elements from a selector.
font-weight: 600;	Thickness of the text.
border: 2px solid var(--brand);	Changes the visual order of a flex item without changing the source.

Check your work

- Every cell exists even if empty
- Row and column headers have scope
- Tiles have rounded corners
- Table scrolls on narrow screens

Exercises

1. Add rowspan for a two-hour slot.

2. Colour by category with classes.
3. Make the time column sticky with position: sticky; left: 0.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 519: Weekly schedule grid for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 2 | Files: index.html, styles.css

Brief

Build a timetable as a table with separate, rounded cells where booked slots are highlighted with :not(:empty).

Learning goals

- Use the separate border model with border-spacing
- Highlight cells based on content with :empty
- Keep a wide table scrollable

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td	border-collapse: separate, border-spacing, :not(:empty), border-radius on cells, min-width

Build guide

1. Write the header row with the days.
2. Write one row per time slot; the first cell is th scope="row".
3. Leave empty <td></td> for free slots.
4. Use border-collapse: separate and border-spacing so cells look like tiles.
5. Style non-empty cells with :not(:empty).
6. Wrap for horizontal scrolling.

Project 519: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - Weekly schedule</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Weekly schedule</h1>
    <div class="wrap">
      <table class="schedule">
        <caption>Services by day and time</caption>
        <thead><tr><th scope="col">Time</th><th scope="col">Sat</
th><th scope="col">Sun</th><th scope="col">Mon</th><th
scope="col">Tue</th><th scope="col">Wed</th></tr></thead>
        <tbody>
          <tr><th scope="row">9:00</th><td>Oil change</td><td></
td><td>Oil change</td><td></td><td>Oil change</td></tr>
          <tr><th scope="row">11:00</th><td></td><td>Brake pads</
td><td></td><td>Brake pads</td><td></td></tr>
          <tr><th scope="row">13:00</th><td>Air conditioning</
td><td></td><td>Air conditioning</td><td></td><td>Air conditioning</
td></tr>
          <tr><th scope="row">15:00</th><td></td><td>Pre-purchase
inspection</td><td></td><td>Pre-purchase inspection</td><td></td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 519: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.wrap { overflow-x: auto; }
.schedule { border-collapse: separate; border-spacing: 4px; width:
100%; min-width: 36rem; }
.schedule th { background: var(--brand); color: #fff; padding: .5rem;
border-radius: 6px; }
```

```
.schedule tbody th { background: var(--accent); color: var(--ink); }
.schedule td { padding: .6rem; border-radius: 6px; text-align: center;
 background: #f6f6f6; min-height: 3rem; }
.schedule td:not(:empty) { background: var(--accent); font-weight:
600; border: 2px solid var(--brand); }
```

Project 519 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - Weekly schedule</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Weekly schedule	The main heading; only one per page.
	Generic block container for grouping and layout.
<table class="schedule">	Tabular data in rows and columns.
<caption>Services by day and time</caption>	Title of the table.
<thead><tr><th scope="col">Time</th><th scope="col">Sat</th><th sco...	Group of header rows.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">9:00</th><td>Oil change</td><td></td><td>Oil ch...	A table row.
<tr><th scope="row">11:00</th><td></td><td>Brake pads</td><td></td>...	Header cell for a row.
<tr><th scope="row">13:00</th><td>Air conditioning</td><td></td><td...	A header cell.
<tr><th scope="row">15:00</th><td></td><td>Pre-purchase inspection<...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
border-collapse: separate;	Keeps each cell's border separate so cells look like tiles.
border-spacing: 4px;	Gap between cells in the separate border model.
width: 100%;	Fills the container width.
background: var(--brand);	Background colour or image.
border-radius: 6px;	Rounds the corners.
border-radius: 6px;	The line around the element: width, style and colour.
text-align: center;	Centres inline content such as text.
.schedule td:not(:empty) {	Excludes elements from a selector.
font-weight: 600;	Thickness of the text.
border: 2px solid var(--brand);	Changes the visual order of a flex item without changing the source.

Check your work

- Every cell exists even if empty
- Row and column headers have scope
- Tiles have rounded corners
- Table scrolls on narrow screens

Exercises

1. Add rowspan for a two-hour slot.

2. Colour by category with classes.
3. Make the time column sticky with position: sticky; left: 0.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 520: Weekly schedule grid for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 2 | Files: index.html, styles.css

Brief

Build a timetable as a table with separate, rounded cells where booked slots are highlighted with :not(:empty).

Learning goals

- Use the separate border model with border-spacing
- Highlight cells based on content with :empty
- Keep a wide table scrollable

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td	border-collapse: separate, border-spacing, :not(:empty), border-radius on cells, min-width

Build guide

1. Write the header row with the days.
2. Write one row per time slot; the first cell is th scope="row".
3. Leave empty <td></td> for free slots.
4. Use border-collapse: separate and border-spacing so cells look like tiles.
5. Style non-empty cells with :not(:empty).
6. Wrap for horizontal scrolling.

Project 520: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - Weekly schedule</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Weekly schedule</h1>
    <div class="wrap">
      <table class="schedule">
        <caption>Courses by day and time</caption>
        <thead><tr><th scope="col">Time</th><th scope="col">Sat</
th><th scope="col">Sun</th><th scope="col">Mon</th><th
scope="col">Tue</th><th scope="col">Wed</th></tr></thead>
        <tbody>
          <tr><th scope="row">9:00</th><td>Oud for beginners</
td><td></td><td>Oud for beginners</td><td></td><td>Oud for beginners</
td></tr>
          <tr><th scope="row">11:00</th><td></td><td>Piano grade 1</
td><td></td><td>Piano grade 1</td><td></td></tr>
          <tr><th scope="row">13:00</th><td>Guitar chords</td><td></
td><td>Guitar chords</td><td></td><td>Guitar chords</td></tr>
          <tr><th scope="row">15:00</th><td></td><td>Voice coaching</
td><td></td><td>Voice coaching</td><td></td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 520: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.wrap { overflow-x: auto; }
.schedule { border-collapse: separate; border-spacing: 4px; width:
100%; min-width: 36rem; }
.schedule th { background: var(--brand); color: #fff; padding: .5rem;
border-radius: 6px; }
```

```
.schedule tbody th { background: var(--accent); color: var(--ink); }
.schedule td { padding: .6rem; border-radius: 6px; text-align: center;
 background: #f6f6f6; min-height: 3rem; }
.schedule td:not(:empty) { background: var(--accent); font-weight:
600; border: 2px solid var(--brand); }
```

Project 520 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - Weekly schedule</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Weekly schedule	The main heading; only one per page.
	Generic block container for grouping and layout.
<table class="schedule">	Tabular data in rows and columns.
<caption>Courses by day and time</caption>	Title of the table.
<thead><tr><th scope="col">Time</th><th scope="col">Sat</th><th sco...	Group of header rows.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">9:00</th><td>Oud for beginners</td><td></td><td...	A table row.
<tr><th scope="row">11:00</th><td></td><td>Piano grade 1</td><td></...	Header cell for a row.
<tr><th scope="row">13:00</th><td>Guitar chords</td><td></td><td>Gu...	A header cell.
<tr><th scope="row">15:00</th><td></td><td>Voice coaching</td><td><...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
border-collapse: separate;	Keeps each cell's border separate so cells look like tiles.
border-spacing: 4px;	Gap between cells in the separate border model.
width: 100%;	Fills the container width.
background: var(--brand);	Background colour or image.
border-radius: 6px;	Rounds the corners.
border-radius: 6px;	The line around the element: width, style and colour.
text-align: center;	Centres inline content such as text.
.schedule td:not(:empty) {	Excludes elements from a selector.
font-weight: 600;	Thickness of the text.
border: 2px solid var(--brand);	Changes the visual order of a flex item without changing the source.

Check your work

- Every cell exists even if empty
- Row and column headers have scope
- Tiles have rounded corners
- Table scrolls on narrow screens

Exercises

1. Add rowspan for a two-hour slot.

2. Colour by category with classes.
3. Make the time column sticky with position: sticky; left: 0.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 521: Weekly schedule grid for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 2 | Files: index.html, styles.css

Brief

Build a timetable as a table with separate, rounded cells where booked slots are highlighted with :not(:empty).

Learning goals

- Use the separate border model with border-spacing
- Highlight cells based on content with :empty
- Keep a wide table scrollable

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td	border-collapse: separate, border-spacing, :not(:empty), border-radius on cells, min-width

Build guide

1. Write the header row with the days.
2. Write one row per time slot; the first cell is th scope="row".
3. Leave empty <td></td> for free slots.
4. Use border-collapse: separate and border-spacing so cells look like tiles.
5. Style non-empty cells with :not(:empty).
6. Wrap for horizontal scrolling.

Project 521: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - Weekly schedule</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Weekly schedule</h1>
    <div class="wrap">
      <table class="schedule">
        <caption>Dishes by day and time</caption>
        <thead><tr><th scope="col">Time</th><th scope="col">Sat</
th><th scope="col">Sun</th><th scope="col">Mon</th><th
scope="col">Tue</th><th scope="col">Wed</th></tr></thead>
        <tbody>
          <tr><th scope="row">9:00</th><td>Grilled sea bass</td><td></
td><td>Grilled sea bass</td><td></td><td>Grilled sea bass</td></tr>
          <tr><th scope="row">11:00</th><td></td><td>Shrimp tagine</
td><td></td><td>Shrimp tagine</td><td></td></tr>
          <tr><th scope="row">13:00</th><td>Calamari</td><td></
td><td>Calamari</td><td></td><td>Calamari</td></tr>
          <tr><th scope="row">15:00</th><td></td><td>Fish soup</
td><td></td><td>Fish soup</td><td></td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 521: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.wrap { overflow-x: auto; }
.schedule { border-collapse: separate; border-spacing: 4px; width:
100%; min-width: 36rem; }
.schedule th { background: var(--brand); color: #fff; padding: .5rem;
border-radius: 6px; }
.schedule tbody th { background: var(--accent); color: var(--ink); }
```

```
.schedule td { padding: .6rem; border-radius: 6px; text-align: center;
 background: #f6f6f6; min-height: 3rem; }
.schedule td:not(:empty) { background: var(--accent); font-weight:
600; border: 2px solid var(--brand); }
```

Project 521 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - Weekly schedule</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Weekly schedule	The main heading; only one per page.
	Generic block container for grouping and layout.
<table class="schedule">	Tabular data in rows and columns.
<caption>Dishes by day and time</caption>	Title of the table.
<thead><tr><th scope="col">Time</th><th scope="col">Sat</th><th sco...	Group of header rows.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">9:00</th><td>Grilled sea bass</td><td></td><td>...	A table row.
<tr><th scope="row">11:00</th><td></td><td>Shrimp tagine</td><td></...	Header cell for a row.
<tr><th scope="row">13:00</th><td>Calamari</td><td></td><td>Calamar...	A header cell.
<tr><th scope="row">15:00</th><td></td><td>Fish soup</td><td></td><...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
border-collapse: separate;	Keeps each cell's border separate so cells look like tiles.
border-spacing: 4px;	Gap between cells in the separate border model.
width: 100%;	Fills the container width.
background: var(--brand);	Background colour or image.
border-radius: 6px;	Rounds the corners.
border-radius: 6px;	The line around the element: width, style and colour.
text-align: center;	Centres inline content such as text.
.schedule td:not(:empty) {	Excludes elements from a selector.
font-weight: 600;	Thickness of the text.
border: 2px solid var(--brand);	Changes the visual order of a flex item without changing the source.

Check your work

- Every cell exists even if empty
- Row and column headers have scope
- Tiles have rounded corners
- Table scrolls on narrow screens

Exercises

1. Add rowspan for a two-hour slot.

2. Colour by category with classes.
3. Make the time column sticky with position: sticky; left: 0.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 522: Weekly schedule grid for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 2 | Files: index.html, styles.css

Brief

Build a timetable as a table with separate, rounded cells where booked slots are highlighted with :not(:empty).

Learning goals

- Use the separate border model with border-spacing
- Highlight cells based on content with :empty
- Keep a wide table scrollable

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td	border-collapse: separate, border-spacing, :not(:empty), border-radius on cells, min-width

Build guide

1. Write the header row with the days.
2. Write one row per time slot; the first cell is th scope="row".
3. Leave empty <td></td> for free slots.
4. Use border-collapse: separate and border-spacing so cells look like tiles.
5. Style non-empty cells with :not(:empty).
6. Wrap for horizontal scrolling.

Project 522: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - Weekly schedule</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Weekly schedule</h1>
    <div class="wrap">
      <table class="schedule">
        <caption>Programmes by day and time</caption>
        <thead><tr><th scope="col">Time</th><th scope="col">Sat</
th><th scope="col">Sun</th><th scope="col">Mon</th><th
scope="col">Tue</th><th scope="col">Wed</th></tr></thead>
        <tbody>
          <tr><th scope="row">9:00</th><td>Story hour</td><td></
td><td>Story hour</td><td></td><td>Story hour</td></tr>
          <tr><th scope="row">11:00</th><td></td><td>Reading club</
td><td></td><td>Reading club</td><td></td></tr>
          <tr><th scope="row">13:00</th><td>Homework help</td><td></
td><td>Homework help</td><td></td><td>Homework help</td></tr>
          <tr><th scope="row">15:00</th><td></td><td>Summer
challenge</td><td></td><td>Summer challenge</td><td></td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 522: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.wrap { overflow-x: auto; }
.schedule { border-collapse: separate; border-spacing: 4px; width:
100%; min-width: 36rem; }
.schedule th { background: var(--brand); color: #fff; padding: .5rem;
border-radius: 6px; }
.schedule tbody th { background: var(--accent); color: var(--ink); }
```

```
.schedule td { padding: .6rem; border-radius: 6px; text-align: center;
 background: #f6f6f6; min-height: 3rem; }
.schedule td:not(:empty) { background: var(--accent); font-weight:
600; border: 2px solid var(--brand); }
```

Project 522 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - Weekly schedule</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Weekly schedule	The main heading; only one per page.
	Generic block container for grouping and layout.
<table class="schedule">	Tabular data in rows and columns.
<caption>Programmes by day and time</caption>	Title of the table.
<thead><tr><th scope="col">Time</th><th scope="col">Sat</th><th sco...	Group of header rows.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">9:00</th><td>Story hour</td><td></td><td>Story ...	A table row.
<tr><th scope="row">11:00</th><td></td><td>Reading club</td><td></t...	Header cell for a row.
<tr><th scope="row">13:00</th><td>Homework help</td><td></td><td>Ho...	A header cell.
<tr><th scope="row">15:00</th><td></td><td>Summer challenge</td><td...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
border-collapse: separate;	Keeps each cell's border separate so cells look like tiles.
border-spacing: 4px;	Gap between cells in the separate border model.
width: 100%;	Fills the container width.
background: var(--brand);	Background colour or image.
border-radius: 6px;	Rounds the corners.
border-radius: 6px;	The line around the element: width, style and colour.
text-align: center;	Centres inline content such as text.
.schedule td:not(:empty) {	Excludes elements from a selector.
font-weight: 600;	Thickness of the text.
border: 2px solid var(--brand);	Changes the visual order of a flex item without changing the source.

Check your work

- Every cell exists even if empty
- Row and column headers have scope
- Tiles have rounded corners
- Table scrolls on narrow screens

Exercises

1. Add rowspan for a two-hour slot.

2. Colour by category with classes.
3. Make the time column sticky with position: sticky; left: 0.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 523: Weekly schedule grid for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Build a timetable as a table with separate, rounded cells where booked slots are highlighted with :not(:empty).

Learning goals

- Use the separate border model with border-spacing
- Highlight cells based on content with :empty
- Keep a wide table scrollable

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td	border-collapse: separate, border-spacing, :not(:empty), border-radius on cells, min-width

Build guide

1. Write the header row with the days.
2. Write one row per time slot; the first cell is th scope="row".
3. Leave empty <td></td> for free slots.
4. Use border-collapse: separate and border-spacing so cells look like tiles.
5. Style non-empty cells with :not(:empty).
6. Wrap for horizontal scrolling.

Project 523: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - Weekly schedule</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Weekly schedule</h1>
    <div class="wrap">
      <table class="schedule">
        <caption>Rooms by day and time</caption>
        <thead><tr><th scope="col">Time</th><th scope="col">Sat</
th><th scope="col">Sun</th><th scope="col">Mon</th><th
scope="col">Tue</th><th scope="col">Wed</th></tr></thead>
        <tbody>
          <tr><th scope="row">9:00</th><td>Garden room</td><td></
td><td>Garden room</td><td></td><td>Garden room</td></tr>
          <tr><th scope="row">11:00</th><td></td><td>Nile view suite</
td><td></td><td>Nile view suite</td><td></td></tr>
          <tr><th scope="row">13:00</th><td>Family room</td><td></
td><td>Family room</td><td></td><td>Family room</td></tr>
          <tr><th scope="row">15:00</th><td></td><td>Rooftop dorm</
td><td></td><td>Rooftop dorm</td><td></td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 523: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.wrap { overflow-x: auto; }
.schedule { border-collapse: separate; border-spacing: 4px; width:
100%; min-width: 36rem; }
.schedule th { background: var(--brand); color: #fff; padding: .5rem;
border-radius: 6px; }
.schedule tbody th { background: var(--accent); color: var(--ink); }
```

```
.schedule td { padding: .6rem; border-radius: 6px; text-align: center;
 background: #f6f6f6; min-height: 3rem; }
.schedule td:not(:empty) { background: var(--accent); font-weight:
600; border: 2px solid var(--brand); }
```

Project 523 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - Weekly schedule</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Weekly schedule	The main heading; only one per page.
	Generic block container for grouping and layout.
<table class="schedule">	Tabular data in rows and columns.
<caption>Rooms by day and time</caption>	Title of the table.
<thead><tr><th scope="col">Time</th><th scope="col">Sat</th><th sco...	Group of header rows.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">9:00</th><td>Garden room</td><td></td><td>Garde...	A table row.
<tr><th scope="row">11:00</th><td></td><td>Nile view suite</td><td>...	Header cell for a row.
<tr><th scope="row">13:00</th><td>Family room</td><td></td><td>Fami...	A header cell.
<tr><th scope="row">15:00</th><td></td><td>Rooftop dorm</td><td></t...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
border-collapse: separate;	Keeps each cell's border separate so cells look like tiles.
border-spacing: 4px;	Gap between cells in the separate border model.
width: 100%;	Fills the container width.
background: var(--brand);	Background colour or image.
border-radius: 6px;	Rounds the corners.
border-radius: 6px;	The line around the element: width, style and colour.
text-align: center;	Centres inline content such as text.
.schedule td:not(:empty) {	Excludes elements from a selector.
font-weight: 600;	Thickness of the text.
border: 2px solid var(--brand);	Changes the visual order of a flex item without changing the source.

Check your work

- Every cell exists even if empty
- Row and column headers have scope
- Tiles have rounded corners
- Table scrolls on narrow screens

Exercises

1. Add rowspan for a two-hour slot.

2. Colour by category with classes.
3. Make the time column sticky with position: sticky; left: 0.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 524: Weekly schedule grid for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 2 | Files: index.html, styles.css

Brief

Build a timetable as a table with separate, rounded cells where booked slots are highlighted with :not(:empty).

Learning goals

- Use the separate border model with border-spacing
- Highlight cells based on content with :empty
- Keep a wide table scrollable

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td	border-collapse: separate, border-spacing, :not(:empty), border-radius on cells, min-width

Build guide

1. Write the header row with the days.
2. Write one row per time slot; the first cell is th scope="row".
3. Leave empty <td></td> for free slots.
4. Use border-collapse: separate and border-spacing so cells look like tiles.
5. Style non-empty cells with :not(:empty).
6. Wrap for horizontal scrolling.

Project 524: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - Weekly schedule</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Weekly schedule</h1>
    <div class="wrap">
      <table class="schedule">
        <caption>Bikes by day and time</caption>
        <thead><tr><th scope="col">Time</th><th scope="col">Sat</
th><th scope="col">Sun</th><th scope="col">Mon</th><th
scope="col">Tue</th><th scope="col">Wed</th></tr></thead>
        <tbody>
          <tr><th scope="row">9:00</th><td>City bike</td><td></
td><td>City bike</td><td></td><td>City bike</td></tr>
          <tr><th scope="row">11:00</th><td></td><td>Mountain bike</
td><td></td><td>Mountain bike</td><td></td></tr>
          <tr><th scope="row">13:00</th><td>Kids bike</td><td></
td><td>Kids bike</td><td></td><td>Kids bike</td></tr>
          <tr><th scope="row">15:00</th><td></td><td>Tune-up</
td><td></td><td>Tune-up</td><td></td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 524: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.wrap { overflow-x: auto; }
.schedule { border-collapse: separate; border-spacing: 4px; width:
100%; min-width: 36rem; }
.schedule th { background: var(--brand); color: #fff; padding: .5rem;
border-radius: 6px; }
.schedule tbody th { background: var(--accent); color: var(--ink); }
```

```
.schedule td { padding: .6rem; border-radius: 6px; text-align: center;
 background: #f6f6f6; min-height: 3rem; }
.schedule td:not(:empty) { background: var(--accent); font-weight:
600; border: 2px solid var(--brand); }
```

Project 524 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - Weekly schedule</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Weekly schedule	The main heading; only one per page.
	Generic block container for grouping and layout.
<table class="schedule">	Tabular data in rows and columns.
<caption>Bikes by day and time</caption>	Title of the table.
<thead><tr><th scope="col">Time</th><th scope="col">Sat</th><th sco...	Group of header rows.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">9:00</th><td>City bike</td><td></td><td>City bi...	A table row.
<tr><th scope="row">11:00</th><td></td><td>Mountain bike</td><td></...	Header cell for a row.
<tr><th scope="row">13:00</th><td>Kids bike</td><td></td><td>Kids b...	A header cell.
<tr><th scope="row">15:00</th><td></td><td>Tune-up</td><td></td><td...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
border-collapse: separate;	Keeps each cell's border separate so cells look like tiles.
border-spacing: 4px;	Gap between cells in the separate border model.
width: 100%;	Fills the container width.
background: var(--brand);	Background colour or image.
border-radius: 6px;	Rounds the corners.
border-radius: 6px;	The line around the element: width, style and colour.
text-align: center;	Centres inline content such as text.
.schedule td:not(:empty) {	Excludes elements from a selector.
font-weight: 600;	Thickness of the text.
border: 2px solid var(--brand);	Changes the visual order of a flex item without changing the source.

Check your work

- Every cell exists even if empty
- Row and column headers have scope
- Tiles have rounded corners
- Table scrolls on narrow screens

Exercises

1. Add rowspan for a two-hour slot.

2. Colour by category with classes.
3. Make the time column sticky with position: sticky; left: 0.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 525: Weekly schedule grid for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 2 | Files: index.html, styles.css

Brief

Build a timetable as a table with separate, rounded cells where booked slots are highlighted with :not(:empty).

Learning goals

- Use the separate border model with border-spacing
- Highlight cells based on content with :empty
- Keep a wide table scrollable

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td	border-collapse: separate, border-spacing, :not(:empty), border-radius on cells, min-width

Build guide

1. Write the header row with the days.
2. Write one row per time slot; the first cell is th scope="row".
3. Leave empty <td></td> for free slots.
4. Use border-collapse: separate and border-spacing so cells look like tiles.
5. Style non-empty cells with :not(:empty).
6. Wrap for horizontal scrolling.

Project 525: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - Weekly schedule</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Weekly schedule</h1>
    <div class="wrap">
      <table class="schedule">
        <caption>Workshops by day and time</caption>
        <thead><tr><th scope="col">Time</th><th scope="col">Sat</
th><th scope="col">Sun</th><th scope="col">Mon</th><th
scope="col">Tue</th><th scope="col">Wed</th></tr></thead>
        <tbody>
          <tr><th scope="row">9:00</th><td>HTML weekend</td><td></
td><td>HTML weekend</td><td></td><td>HTML weekend</td></tr>
          <tr><th scope="row">11:00</th><td></td><td>CSS art</
td><td></td><td>CSS art</td><td></td></tr>
          <tr><th scope="row">13:00</th><td>Scratch games</td><td></
td><td>Scratch games</td><td></td><td>Scratch games</td></tr>
          <tr><th scope="row">15:00</th><td></td><td>Hackathon</
td><td></td><td>Hackathon</td><td></td></tr>
        </tbody>
      </table>
    </div>
  </main>
</body>
</html>
```

Project 525: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 2rem auto; padding: 0 1rem; }
.wrap { overflow-x: auto; }
.schedule { border-collapse: separate; border-spacing: 4px; width:
100%; min-width: 36rem; }
.schedule th { background: var(--brand); color: #fff; padding: .5rem;
border-radius: 6px; }
.schedule tbody th { background: var(--accent); color: var(--ink); }
```

```
.schedule td { padding: .6rem; border-radius: 6px; text-align: center;
 background: #f6f6f6; min-height: 3rem; }
.schedule td:not(:empty) { background: var(--accent); font-weight:
600; border: 2px solid var(--brand); }
```

Project 525 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - Weekly schedule</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Weekly schedule	The main heading; only one per page.
	Generic block container for grouping and layout.
<table class="schedule">	Tabular data in rows and columns.
<caption>Workshops by day and time</caption>	Title of the table.
<thead><tr><th scope="col">Time</th><th scope="col">Sat</th><th sco...	Group of header rows.
<tbody>	Group of data rows.

Line	What it does
<tr><th scope="row">9:00</th><td>HTML weekend</td><td></td><td>HTML...	A table row.
<tr><th scope="row">11:00</th><td></td><td>CSS art</td><td></td><td...	Header cell for a row.
<tr><th scope="row">13:00</th><td>Scratch games</td><td></td><td>Sc...	A header cell.
<tr><th scope="row">15:00</th><td></td><td>Hackathon</td><td></td><...	A data cell.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
overflow-x: auto;	Adds a horizontal scrollbar only when needed (responsive tables).
border-collapse: separate;	Keeps each cell's border separate so cells look like tiles.
border-spacing: 4px;	Gap between cells in the separate border model.
width: 100%;	Fills the container width.
background: var(--brand);	Background colour or image.
border-radius: 6px;	Rounds the corners.
border-radius: 6px;	The line around the element: width, style and colour.
text-align: center;	Centres inline content such as text.
.schedule td:not(:empty) {	Excludes elements from a selector.
font-weight: 600;	Thickness of the text.
border: 2px solid var(--brand);	Changes the visual order of a flex item without changing the source.

Check your work

- Every cell exists even if empty
- Row and column headers have scope
- Tiles have rounded corners
- Table scrolls on narrow screens

Exercises

1. Add rowspan for a two-hour slot.

2. Colour by category with classes.
3. Make the time column sticky with position: sticky; left: 0.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: CV / resume page

Level 2 | 25 projects, one per theme

Lay out a one-page CV with header, experience entries using article and time, and a skills list as pills, with a print stylesheet.

Project 526: CV / resume page for Mohamed Khattab

Theme: Cairo Book Shop (Giza) | Level 2 | Files: index.html, styles.css

Brief

Lay out a one-page CV with header, experience entries using article and time, and a skills list as pills, with a print stylesheet.

Learning goals

- Structure a CV semantically
- Style skill tags with Flexbox wrapping
- Add @media print rules

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, section, article, h3, time, ul, li	border-bottom, text-transform, letter-spacing, flex-wrap, @media print

Build guide

1. Write the header with name, role and contact links.
2. Add an Experience section with one article per job.
3. Use <time> for the years.
4. Add a Skills list.
5. Style section headings small and uppercase.
6. Print preview (Ctrl+P) and adjust the print rules.

Project 526: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Mohamed Khattab - CV</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="cv">
    <header>
      <h1>Mohamed Khattab</h1>
      <p class="role">Founder, Cairo Book Shop &middot; Giza</p>
      <p class="links"><a href="mailto:bookshop@example.com">Email</
a> &middot; <a href="tel:+20100000000">Phone</a> &middot; <a
href="https://example.com">Website</a></p>
    </header>
    <section>
      <h2>Experience</h2>
      <article>
        <h3>Founder, Cairo Book Shop</h3>
        <p class="when"><time datetime="2018">2018</time> - present</
p>
        <ul><li>Grew the business to 4 core books.</li><li>Built a
loyal customer base in Giza.</li></ul>
      </article>
      <article>
        <h3>Assistant manager, Local Company</h3>
        <p class="when"><time datetime="2014">2014</time> - <time
datetime="2018">2018</time></p>
        <ul><li>Managed a team of six.</li></ul>
      </article>
    </section>
    <section>
      <h2>Skills</h2>
      <ul class="skills"><li>Customer service</li><li>Planning</
li><li>HTML and CSS</li><li>Arabic and English</li></ul>
    </section>
  </main>
</body>
</html>
```

Project 526: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.cv { max-width: 46rem; margin: 2rem auto; padding: 0 1rem; }
header { border-bottom: 3px solid var(--brand); padding-bottom: 1rem;
margin-bottom: 1.5rem; }
h1 { margin: 0; }
.role { margin: .2rem 0; color: var(--muted); }
h2 { color: var(--brand); text-transform: uppercase; font-size: 1rem;
letter-spacing: .08em; margin-top: 1.5rem; }
h3 { margin: 1rem 0 0; }
.when { margin: 0; color: var(--muted); font-size: .9rem; }
.skills { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .5rem; }
.skills li { background: var(--accent); padding: .3rem .8rem; border-
radius: 999px; }
@media print { a { color: inherit; text-decoration: none; } .cv { max-
width: none; } }
```

Project 526 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Mohamed Khattab - CV</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="cv">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Mohamed Khattab	The main heading; only one per page.
Founder, Cairo Book Shop · Giza	A paragraph of text.
Email &m...	A hyperlink; href gives the destination.
<section>	A thematic group of content, normally with its own heading.
Experience	Second-level heading for a section.
<article>	A self-contained piece: card, post, product.

Line	What it does
Founder, Cairo Book Shop	Third-level heading, inside an h2 section.
<time date time="2018">2018</time> - present	A date or time; datetime holds the machine-readable value.
Grew the business to 4 core books. Built a loyal cu...	Unordered (bulleted) list.
Managed a team of six.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
font-size: 1rem;	Size of the text.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
@media print { a { color: inherit; text-decoration: none; } .cv { m...	Removes the underline from links.

Check your work

- Contact links work (mailto, tel)
- Jobs in reverse chronological order
- Skills wrap
- Prints on one page without colours

Exercises

1. Add a two-column layout for print with CSS columns.
2. Add an Education section.
3. Add a downloadable PDF link.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 527: CV / resume page for Sara Adel

Theme: Nile Bakery (Cairo) | Level 2 | Files: index.html, styles.css

Brief

Lay out a one-page CV with header, experience entries using article and time, and a skills list as pills, with a print stylesheet.

Learning goals

- Structure a CV semantically
- Style skill tags with Flexbox wrapping
- Add @media print rules

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, section, article, h3, time, ul, li	border-bottom, text-transform, letter-spacing, flex-wrap, @media print

Build guide

1. Write the header with name, role and contact links.
2. Add an Experience section with one article per job.
3. Use <time> for the years.
4. Add a Skills list.
5. Style section headings small and uppercase.
6. Print preview (Ctrl+P) and adjust the print rules.

Project 527: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sara Adel - CV</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="cv">
    <header>
      <h1>Sara Adel</h1>
      <p class="role">Founder, Nile Bakery &middot; Cairo</p>
      <p class="links"><a href="mailto:bakery@example.com">Email</a>
&middot; <a href="tel:+20100000000">Phone</a> &middot; <a href="https:
//example.com">Website</a></p>
    </header>
    <section>
      <h2>Experience</h2>
      <article>
        <h3>Founder, Nile Bakery</h3>
        <p class="when"><time datetime="2018">2018</time> - present</
p>
        <ul><li>Grew the business to 4 core pastries.</li><li>Built a
loyal customer base in Cairo.</li></ul>
      </article>
      <article>
        <h3>Assistant manager, Local Company</h3>
        <p class="when"><time datetime="2014">2014</time> - <time
datetime="2018">2018</time></p>
        <ul><li>Managed a team of six.</li></ul>
      </article>
    </section>
    <section>
      <h2>Skills</h2>
      <ul class="skills"><li>Customer service</li><li>Planning</
li><li>HTML and CSS</li><li>Arabic and English</li></ul>
    </section>
  </main>
</body>
</html>
```

Project 527: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.cv { max-width: 46rem; margin: 2rem auto; padding: 0 1rem; }
header { border-bottom: 3px solid var(--brand); padding-bottom: 1rem;
margin-bottom: 1.5rem; }
h1 { margin: 0; }
.role { margin: .2rem 0; color: var(--muted); }
h2 { color: var(--brand); text-transform: uppercase; font-size: 1rem;
letter-spacing: .08em; margin-top: 1.5rem; }
h3 { margin: 1rem 0 0; }
.when { margin: 0; color: var(--muted); font-size: .9rem; }
.skills { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .5rem; }
.skills li { background: var(--accent); padding: .3rem .8rem; border-
radius: 999px; }
@media print { a { color: inherit; text-decoration: none; } .cv { max-
width: none; } }
```

Project 527 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sara Adel - CV</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="cv">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Sara Adel	The main heading; only one per page.
Founder, Nile Bakery · Cairo	A paragraph of text.
Email &mid...	A hyperlink; href gives the destination.
<section>	A thematic group of content, normally with its own heading.
Experience	Second-level heading for a section.
<article>	A self-contained piece: card, post, product.

Line	What it does
Founder, Nile Bakery	Third-level heading, inside an h2 section.
<time date time="2018">2018</time> - present	A date or time; datetime holds the machine-readable value.
Grew the business to 4 core pastries. Built a loyal...	Unordered (bulleted) list.
Managed a team of six.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
font-size: 1rem;	Size of the text.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
@media print { a { color: inherit; text-decoration: none; } .cv { m...	Removes the underline from links.

Check your work

- Contact links work (mailto, tel)
- Jobs in reverse chronological order
- Skills wrap
- Prints on one page without colours

Exercises

1. Add a two-column layout for print with CSS columns.
2. Add an Education section.
3. Add a downloadable PDF link.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 528: CV / resume page for Omar Farouk

Theme: Pyramid Fitness (6th of October) | Level 2 | Files: index.html, styles.css

Brief

Lay out a one-page CV with header, experience entries using article and time, and a skills list as pills, with a print stylesheet.

Learning goals

- Structure a CV semantically
- Style skill tags with Flexbox wrapping
- Add @media print rules

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, section, article, h3, time, ul, li	border-bottom, text-transform, letter-spacing, flex-wrap, @media print

Build guide

1. Write the header with name, role and contact links.
2. Add an Experience section with one article per job.
3. Use <time> for the years.
4. Add a Skills list.
5. Style section headings small and uppercase.
6. Print preview (Ctrl+P) and adjust the print rules.

Project 528: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Omar Farouk - CV</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="cv">
    <header>
      <h1>Omar Farouk</h1>
      <p class="role">Founder, Pyramid Fitness &middot; 6th of
October</p>
      <p class="links"><a href="mailto:gym@example.com">Email</a>
&middot; <a href="tel:+20100000000">Phone</a> &middot; <a href="https:
//example.com">Website</a></p>
    </header>
    <section>
      <h2>Experience</h2>
      <article>
        <h3>Founder, Pyramid Fitness</h3>
        <p class="when"><time datetime="2018">2018</time> - present</
p>
        <ul><li>Grew the business to 4 core classes.</li><li>Built a
loyal customer base in 6th of October.</li></ul>
      </article>
      <article>
        <h3>Assistant manager, Local Company</h3>
        <p class="when"><time datetime="2014">2014</time> - <time
datetime="2018">2018</time></p>
        <ul><li>Managed a team of six.</li></ul>
      </article>
    </section>
    <section>
      <h2>Skills</h2>
      <ul class="skills"><li>Customer service</li><li>Planning</
li><li>HTML and CSS</li><li>Arabic and English</li></ul>
    </section>
  </main>
</body>
</html>
```

Project 528: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
```

```
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.cv { max-width: 46rem; margin: 2rem auto; padding: 0 1rem; }
header { border-bottom: 3px solid var(--brand); padding-bottom: 1rem;
margin-bottom: 1.5rem; }
h1 { margin: 0; }
.role { margin: .2rem 0; color: var(--muted); }
h2 { color: var(--brand); text-transform: uppercase; font-size: 1rem;
letter-spacing: .08em; margin-top: 1.5rem; }
h3 { margin: 1rem 0 0; }
.when { margin: 0; color: var(--muted); font-size: .9rem; }
.skills { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .5rem; }
.skills li { background: var(--accent); padding: .3rem .8rem; border-
radius: 999px; }
@media print { a { color: inherit; text-decoration: none; } .cv { max-
width: none; } }
```

Project 528 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Omar Farouk - CV</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="cv">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Omar Farouk	The main heading; only one per page.
Founder, Pyramid Fitness · 6th of October	A paragraph of text.
Email &middot...	A hyperlink; href gives the destination.
<section>	A thematic group of content, normally with its own heading.
Experience	Second-level heading for a section.
<article>	A self-contained piece: card, post, product.

Line	What it does
Founder, Pyramid Fitness	Third-level heading, inside an h2 section.
<time date time="2018">2018</time> - present	A date or time; datetime holds the machine-readable value.
Grew the business to 4 core classes. Built a loyal ...	Unordered (bulleted) list.
Managed a team of six.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
font-size: 1rem;	Size of the text.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
@media print { a { color: inherit; text-decoration: none; } .cv { m...	Removes the underline from links.

Check your work

- Contact links work (mailto, tel)
- Jobs in reverse chronological order
- Skills wrap
- Prints on one page without colours

Exercises

1. Add a two-column layout for print with CSS columns.
2. Add an Education section.
3. Add a downloadable PDF link.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 529: CV / resume page for Dr. Hana Youssef

Theme: Delta Dental Clinic (Mansoura) | Level 2 | Files: index.html, styles.css

Brief

Lay out a one-page CV with header, experience entries using article and time, and a skills list as pills, with a print stylesheet.

Learning goals

- Structure a CV semantically
- Style skill tags with Flexbox wrapping
- Add @media print rules

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, section, article, h3, time, ul, li	border-bottom, text-transform, letter-spacing, flex-wrap, @media print

Build guide

1. Write the header with name, role and contact links.
2. Add an Experience section with one article per job.
3. Use <time> for the years.
4. Add a Skills list.
5. Style section headings small and uppercase.
6. Print preview (Ctrl+P) and adjust the print rules.

Project 529: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Dr. Hana Youssef - CV</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="cv">
    <header>
      <h1>Dr. Hana Youssef</h1>
      <p class="role">Founder, Delta Dental Clinic &middot; Mansoura</
p>
      <p class="links"><a href="mailto:clinic@example.com">Email</a>
&middot; <a href="tel:+20100000000">Phone</a> &middot; <a href="https:
//example.com">Website</a></p>
    </header>
    <section>
      <h2>Experience</h2>
      <article>
        <h3>Founder, Delta Dental Clinic</h3>
        <p class="when"><time datetime="2018">2018</time> - present</
p>
        <ul><li>Grew the business to 4 core services.</li><li>Built a
loyal customer base in Mansoura.</li></ul>
      </article>
      <article>
        <h3>Assistant manager, Local Company</h3>
        <p class="when"><time datetime="2014">2014</time> - <time
datetime="2018">2018</time></p>
        <ul><li>Managed a team of six.</li></ul>
      </article>
    </section>
    <section>
      <h2>Skills</h2>
      <ul class="skills"><li>Customer service</li><li>Planning</
li><li>HTML and CSS</li><li>Arabic and English</li></ul>
    </section>
  </main>
</body>
</html>
```

Project 529: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
```

```
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.cv { max-width: 46rem; margin: 2rem auto; padding: 0 1rem; }
header { border-bottom: 3px solid var(--brand); padding-bottom: 1rem;
margin-bottom: 1.5rem; }
h1 { margin: 0; }
.role { margin: .2rem 0; color: var(--muted); }
h2 { color: var(--brand); text-transform: uppercase; font-size: 1rem;
letter-spacing: .08em; margin-top: 1.5rem; }
h3 { margin: 1rem 0 0; }
.when { margin: 0; color: var(--muted); font-size: .9rem; }
.skills { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .5rem; }
.skills li { background: var(--accent); padding: .3rem .8rem; border-
radius: 999px; }
@media print { a { color: inherit; text-decoration: none; } .cv { max-
width: none; } }
```

Project 529 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Dr. Hana Youssef - CV</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="cv">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Dr. Hana Youssef	The main heading; only one per page.
Founder, Delta Dental Clinic · Mansoura	A paragraph of text.
Email &mid...	A hyperlink; href gives the destination.
<section>	A thematic group of content, normally with its own heading.
Experience	Second-level heading for a section.
<article>	A self-contained piece: card, post, product.

Line	What it does
Founder, Delta Dental Clinic	Third-level heading, inside an h2 section.
<time date time="2018">2018</time> - present	A date or time; datetime holds the machine-readable value.
Grew the business to 4 core services. Built a loyal...	Unordered (bulleted) list.
Managed a team of six.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
font-size: 1rem;	Size of the text.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
@media print { a { color: inherit; text-decoration: none; } .cv { m...	Removes the underline from links.

Check your work

- Contact links work (mailto, tel)
- Jobs in reverse chronological order
- Skills wrap
- Prints on one page without colours

Exercises

1. Add a two-column layout for print with CSS columns.
2. Add an Education section.
3. Add a downloadable PDF link.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 530: CV / resume page for Laila Mansour

Theme: Red Sea Travel (Hurghada) | Level 2 | Files: index.html, styles.css

Brief

Lay out a one-page CV with header, experience entries using article and time, and a skills list as pills, with a print stylesheet.

Learning goals

- Structure a CV semantically
- Style skill tags with Flexbox wrapping
- Add @media print rules

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, section, article, h3, time, ul, li	border-bottom, text-transform, letter-spacing, flex-wrap, @media print

Build guide

1. Write the header with name, role and contact links.
2. Add an Experience section with one article per job.
3. Use <time> for the years.
4. Add a Skills list.
5. Style section headings small and uppercase.
6. Print preview (Ctrl+P) and adjust the print rules.

Project 530: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Laila Mansour - CV</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="cv">
    <header>
      <h1>Laila Mansour</h1>
      <p class="role">Founder, Red Sea Travel &middot; Hurghada</p>
      <p class="links"><a href="mailto:travel@example.com">Email</a>
&middot; <a href="tel:+20100000000">Phone</a> &middot; <a href="https:
//example.com">Website</a></p>
    </header>
    <section>
      <h2>Experience</h2>
      <article>
        <h3>Founder, Red Sea Travel</h3>
        <p class="when"><time datetime="2018">2018</time> - present</
p>
        <ul><li>Grew the business to 4 core tours.</li><li>Built a
loyal customer base in Hurghada.</li></ul>
      </article>
      <article>
        <h3>Assistant manager, Local Company</h3>
        <p class="when"><time datetime="2014">2014</time> - <time
datetime="2018">2018</time></p>
        <ul><li>Managed a team of six.</li></ul>
      </article>
    </section>
    <section>
      <h2>Skills</h2>
      <ul class="skills"><li>Customer service</li><li>Planning</
li><li>HTML and CSS</li><li>Arabic and English</li></ul>
    </section>
  </main>
</body>
</html>
```

Project 530: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.cv { max-width: 46rem; margin: 2rem auto; padding: 0 1rem; }
header { border-bottom: 3px solid var(--brand); padding-bottom: 1rem;
margin-bottom: 1.5rem; }
h1 { margin: 0; }
.role { margin: .2rem 0; color: var(--muted); }
h2 { color: var(--brand); text-transform: uppercase; font-size: 1rem;
letter-spacing: .08em; margin-top: 1.5rem; }
h3 { margin: 1rem 0 0; }
.when { margin: 0; color: var(--muted); font-size: .9rem; }
.skills { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .5rem; }
.skills li { background: var(--accent); padding: .3rem .8rem; border-
radius: 999px; }
@media print { a { color: inherit; text-decoration: none; } .cv { max-
width: none; } }
```

Project 530 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Laila Mansour - CV</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="cv">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Laila Mansour	The main heading; only one per page.
Founder, Red Sea Travel · Hurghada	A paragraph of text.
Email &mid...	A hyperlink; href gives the destination.
<section>	A thematic group of content, normally with its own heading.
Experience	Second-level heading for a section.
<article>	A self-contained piece: card, post, product.

Line	What it does
Founder, Red Sea Travel	Third-level heading, inside an h2 section.
<time date time="2018">2018</time> - present	A date or time; datetime holds the machine-readable value.
Grew the business to 4 core tours. Built a loyal cu...	Unordered (bulleted) list.
Managed a team of six.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
font-size: 1rem;	Size of the text.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
@media print { a { color: inherit; text-decoration: none; } .cv { m...	Removes the underline from links.

Check your work

- Contact links work (mailto, tel)
- Jobs in reverse chronological order
- Skills wrap
- Prints on one page without colours

Exercises

1. Add a two-column layout for print with CSS columns.
2. Add an Education section.
3. Add a downloadable PDF link.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 531: CV / resume page for Nour El Din

Theme: Lotus Language School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Lay out a one-page CV with header, experience entries using article and time, and a skills list as pills, with a print stylesheet.

Learning goals

- Structure a CV semantically
- Style skill tags with Flexbox wrapping
- Add @media print rules

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, section, article, h3, time, ul, li	border-bottom, text-transform, letter-spacing, flex-wrap, @media print

Build guide

1. Write the header with name, role and contact links.
2. Add an Experience section with one article per job.
3. Use <time> for the years.
4. Add a Skills list.
5. Style section headings small and uppercase.
6. Print preview (Ctrl+P) and adjust the print rules.

Project 531: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nour El Din - CV</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="cv">
    <header>
      <h1>Nour El Din</h1>
      <p class="role">Founder, Lotus Language School &middot;
Alexandria</p>
      <p class="links"><a href="mailto:school@example.com">Email</a>
&middot; <a href="tel:+20100000000">Phone</a> &middot; <a href="https:
//example.com">Website</a></p>
    </header>
    <section>
      <h2>Experience</h2>
      <article>
        <h3>Founder, Lotus Language School</h3>
        <p class="when"><time datetime="2018">2018</time> - present</
p>
        <ul><li>Grew the business to 4 core courses.</li><li>Built a
loyal customer base in Alexandria.</li></ul>
      </article>
      <article>
        <h3>Assistant manager, Local Company</h3>
        <p class="when"><time datetime="2014">2014</time> - <time
datetime="2018">2018</time></p>
        <ul><li>Managed a team of six.</li></ul>
      </article>
    </section>
    <section>
      <h2>Skills</h2>
      <ul class="skills"><li>Customer service</li><li>Planning</
li><li>HTML and CSS</li><li>Arabic and English</li></ul>
    </section>
  </main>
</body>
</html>
```

Project 531: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
```

```
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.cv { max-width: 46rem; margin: 2rem auto; padding: 0 1rem; }
header { border-bottom: 3px solid var(--brand); padding-bottom: 1rem;
margin-bottom: 1.5rem; }
h1 { margin: 0; }
.role { margin: .2rem 0; color: var(--muted); }
h2 { color: var(--brand); text-transform: uppercase; font-size: 1rem;
letter-spacing: .08em; margin-top: 1.5rem; }
h3 { margin: 1rem 0 0; }
.when { margin: 0; color: var(--muted); font-size: .9rem; }
.skills { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .5rem; }
.skills li { background: var(--accent); padding: .3rem .8rem; border-
radius: 999px; }
@media print { a { color: inherit; text-decoration: none; } .cv { max-
width: none; } }
```

Project 531 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nour El Din - CV</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="cv">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Nour El Din	The main heading; only one per page.
Founder, Lotus Language School · Alexandria	A paragraph of text.
Email &mid...	A hyperlink; href gives the destination.
<section>	A thematic group of content, normally with its own heading.
Experience	Second-level heading for a section.
<article>	A self-contained piece: card, post, product.

Line	What it does
Founder, Lotus Language School	Third-level heading, inside an h2 section.
<time date time="2018">2018</time> - present	A date or time; datetime holds the machine-readable value.
Grew the business to 4 core courses. Built a loyal ...	Unordered (bulleted) list.
Managed a team of six.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
font-size: 1rem;	Size of the text.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
@media print { a { color: inherit; text-decoration: none; } .cv { m...	Removes the underline from links.

Check your work

- Contact links work (mailto, tel)
- Jobs in reverse chronological order
- Skills wrap
- Prints on one page without colours

Exercises

1. Add a two-column layout for print with CSS columns.
2. Add an Education section.
3. Add a downloadable PDF link.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 532: CV / resume page for Karim Said

Theme: Green Leaf Cafe (Zamalek) | Level 2 | Files: index.html, styles.css

Brief

Lay out a one-page CV with header, experience entries using article and time, and a skills list as pills, with a print stylesheet.

Learning goals

- Structure a CV semantically
- Style skill tags with Flexbox wrapping
- Add @media print rules

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, section, article, h3, time, ul, li	border-bottom, text-transform, letter-spacing, flex-wrap, @media print

Build guide

1. Write the header with name, role and contact links.
2. Add an Experience section with one article per job.
3. Use <time> for the years.
4. Add a Skills list.
5. Style section headings small and uppercase.
6. Print preview (Ctrl+P) and adjust the print rules.

Project 532: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Karim Said - CV</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="cv">
    <header>
      <h1>Karim Said</h1>
      <p class="role">Founder, Green Leaf Cafe &middot; Zamalek</p>
      <p class="links"><a href="mailto:cafe@example.com">Email</a>
&middot; <a href="tel:+20100000000">Phone</a> &middot; <a href="https:
//example.com">Website</a></p>
    </header>
    <section>
      <h2>Experience</h2>
      <article>
        <h3>Founder, Green Leaf Cafe</h3>
        <p class="when"><time datetime="2018">2018</time> - present</
p>
        <ul><li>Grew the business to 4 core drinks.</li><li>Built a
loyal customer base in Zamalek.</li></ul>
      </article>
      <article>
        <h3>Assistant manager, Local Company</h3>
        <p class="when"><time datetime="2014">2014</time> - <time
datetime="2018">2018</time></p>
        <ul><li>Managed a team of six.</li></ul>
      </article>
    </section>
    <section>
      <h2>Skills</h2>
      <ul class="skills"><li>Customer service</li><li>Planning</
li><li>HTML and CSS</li><li>Arabic and English</li></ul>
    </section>
  </main>
</body>
</html>
```

Project 532: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.cv { max-width: 46rem; margin: 2rem auto; padding: 0 1rem; }
header { border-bottom: 3px solid var(--brand); padding-bottom: 1rem;
margin-bottom: 1.5rem; }
h1 { margin: 0; }
.role { margin: .2rem 0; color: var(--muted); }
h2 { color: var(--brand); text-transform: uppercase; font-size: 1rem;
letter-spacing: .08em; margin-top: 1.5rem; }
h3 { margin: 1rem 0 0; }
.when { margin: 0; color: var(--muted); font-size: .9rem; }
.skills { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .5rem; }
.skills li { background: var(--accent); padding: .3rem .8rem; border-
radius: 999px; }
@media print { a { color: inherit; text-decoration: none; } .cv { max-
width: none; } }
```

Project 532 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Karim Said - CV</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="cv">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Karim Said	The main heading; only one per page.
Founder, Green Leaf Cafe · Zamalek	A paragraph of text.
Email &middo...	A hyperlink; href gives the destination.
<section>	A thematic group of content, normally with its own heading.
Experience	Second-level heading for a section.
<article>	A self-contained piece: card, post, product.

Line	What it does
Founder, Green Leaf Cafe	Third-level heading, inside an h2 section.
<time date time="2018">2018</time> - present	A date or time; datetime holds the machine-readable value.
Grew the business to 4 core drinks. Built a loyal c...	Unordered (bulleted) list.
Managed a team of six.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
font-size: 1rem;	Size of the text.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
@media print { a { color: inherit; text-decoration: none; } .cv { m...	Removes the underline from links.

Check your work

- Contact links work (mailto, tel)
- Jobs in reverse chronological order
- Skills wrap
- Prints on one page without colours

Exercises

1. Add a two-column layout for print with CSS columns.
2. Add an Education section.
3. Add a downloadable PDF link.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 533: CV / resume page for Yara Hamdy

Theme: Sinai Trekking Club (Saint Catherine) | Level 2 | Files: index.html, styles.css

Brief

Lay out a one-page CV with header, experience entries using article and time, and a skills list as pills, with a print stylesheet.

Learning goals

- Structure a CV semantically
- Style skill tags with Flexbox wrapping
- Add @media print rules

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, section, article, h3, time, ul, li	border-bottom, text-transform, letter-spacing, flex-wrap, @media print

Build guide

1. Write the header with name, role and contact links.
2. Add an Experience section with one article per job.
3. Use <time> for the years.
4. Add a Skills list.
5. Style section headings small and uppercase.
6. Print preview (Ctrl+P) and adjust the print rules.

Project 533: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Yara Hamdy - CV</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="cv">
    <header>
      <h1>Yara Hamdy</h1>
      <p class="role">Founder, Sinai Trekking Club &middot; Saint
Catherine</p>
      <p class="links"><a href="mailto:trekking@example.com">Email</
a> &middot; <a href="tel:+20100000000">Phone</a> &middot; <a
href="https://example.com">Website</a></p>
    </header>
    <section>
      <h2>Experience</h2>
      <article>
        <h3>Founder, Sinai Trekking Club</h3>
        <p class="when"><time datetime="2018">2018</time> - present</
p>
        <ul><li>Grew the business to 4 core hikes.</li><li>Built a
loyal customer base in Saint Catherine.</li></ul>
      </article>
      <article>
        <h3>Assistant manager, Local Company</h3>
        <p class="when"><time datetime="2014">2014</time> - <time
datetime="2018">2018</time></p>
        <ul><li>Managed a team of six.</li></ul>
      </article>
    </section>
    <section>
      <h2>Skills</h2>
      <ul class="skills"><li>Customer service</li><li>Planning</
li><li>HTML and CSS</li><li>Arabic and English</li></ul>
    </section>
  </main>
</body>
</html>
```

Project 533: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
```

```
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.cv { max-width: 46rem; margin: 2rem auto; padding: 0 1rem; }
header { border-bottom: 3px solid var(--brand); padding-bottom: 1rem;
margin-bottom: 1.5rem; }
h1 { margin: 0; }
.role { margin: .2rem 0; color: var(--muted); }
h2 { color: var(--brand); text-transform: uppercase; font-size: 1rem;
letter-spacing: .08em; margin-top: 1.5rem; }
h3 { margin: 1rem 0 0; }
.when { margin: 0; color: var(--muted); font-size: .9rem; }
.skills { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .5rem; }
.skills li { background: var(--accent); padding: .3rem .8rem; border-
radius: 999px; }
@media print { a { color: inherit; text-decoration: none; } .cv { max-
width: none; } }
```

Project 533 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Yara Hamdy - CV</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="cv">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Yara Hamdy	The main heading; only one per page.
<p class="role">Founder, Sinai Trekking Club · Saint Catheri...	A paragraph of text.
<p class="links">Email &m...	A hyperlink; href gives the destination.
<section>	A thematic group of content, normally with its own heading.
Experience	Second-level heading for a section.
<article>	A self-contained piece: card, post, product.

Line	What it does
Founder, Sinai Trekking Club	Third-level heading, inside an h2 section.
<time date time="2018">2018</time> - present	A date or time; datetime holds the machine-readable value.
Grew the business to 4 core hikes. Built a loyal cu...	Unordered (bulleted) list.
Managed a team of six.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
font-size: 1rem;	Size of the text.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
@media print { a { color: inherit; text-decoration: none; } .cv { m...	Removes the underline from links.

Check your work

- Contact links work (mailto, tel)
- Jobs in reverse chronological order
- Skills wrap
- Prints on one page without colours

Exercises

1. Add a two-column layout for print with CSS columns.
2. Add an Education section.
3. Add a downloadable PDF link.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 534: CV / resume page for Adham Nabil

Theme: Horizon Photography (Maadi) | Level 2 | Files: index.html, styles.css

Brief

Lay out a one-page CV with header, experience entries using article and time, and a skills list as pills, with a print stylesheet.

Learning goals

- Structure a CV semantically
- Style skill tags with Flexbox wrapping
- Add @media print rules

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, section, article, h3, time, ul, li	border-bottom, text-transform, letter-spacing, flex-wrap, @media print

Build guide

1. Write the header with name, role and contact links.
2. Add an Experience section with one article per job.
3. Use <time> for the years.
4. Add a Skills list.
5. Style section headings small and uppercase.
6. Print preview (Ctrl+P) and adjust the print rules.

Project 534: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Adham Nabil - CV</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="cv">
    <header>
      <h1>Adham Nabil</h1>
      <p class="role">Founder, Horizon Photography &middot; Maadi</p>
      <p class="links"><a href="mailto:photo@example.com">Email</a>
&middot; <a href="tel:+20100000000">Phone</a> &middot; <a href="https:
//example.com">Website</a></p>
    </header>
    <section>
      <h2>Experience</h2>
      <article>
        <h3>Founder, Horizon Photography</h3>
        <p class="when"><time datetime="2018">2018</time> - present</
p>
        <ul><li>Grew the business to 4 core sessions.</li><li>Built a
loyal customer base in Maadi.</li></ul>
      </article>
      <article>
        <h3>Assistant manager, Local Company</h3>
        <p class="when"><time datetime="2014">2014</time> - <time
datetime="2018">2018</time></p>
        <ul><li>Managed a team of six.</li></ul>
      </article>
    </section>
    <section>
      <h2>Skills</h2>
      <ul class="skills"><li>Customer service</li><li>Planning</
li><li>HTML and CSS</li><li>Arabic and English</li></ul>
    </section>
  </main>
</body>
</html>
```

Project 534: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.cv { max-width: 46rem; margin: 2rem auto; padding: 0 1rem; }
header { border-bottom: 3px solid var(--brand); padding-bottom: 1rem;
margin-bottom: 1.5rem; }
h1 { margin: 0; }
.role { margin: .2rem 0; color: var(--muted); }
h2 { color: var(--brand); text-transform: uppercase; font-size: 1rem;
letter-spacing: .08em; margin-top: 1.5rem; }
h3 { margin: 1rem 0 0; }
.when { margin: 0; color: var(--muted); font-size: .9rem; }
.skills { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .5rem; }
.skills li { background: var(--accent); padding: .3rem .8rem; border-
radius: 999px; }
@media print { a { color: inherit; text-decoration: none; } .cv { max-
width: none; } }
```

Project 534 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Adham Nabil - CV</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="cv">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Adham Nabil	The main heading; only one per page.
Founder, Horizon Photography · Maadi	A paragraph of text.
Email &midd...	A hyperlink; href gives the destination.
<section>	A thematic group of content, normally with its own heading.
Experience	Second-level heading for a section.
<article>	A self-contained piece: card, post, product.

Line	What it does
Founder, Horizon Photography	Third-level heading, inside an h2 section.
<time date time="2018">2018</time> - present	A date or time; datetime holds the machine-readable value.
Grew the business to 4 core sessions. Built a loyal...	Unordered (bulleted) list.
Managed a team of six.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
font-size: 1rem;	Size of the text.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
@media print { a { color: inherit; text-decoration: none; } .cv { m...	Removes the underline from links.

Check your work

- Contact links work (mailto, tel)
- Jobs in reverse chronological order
- Skills wrap
- Prints on one page without colours

Exercises

1. Add a two-column layout for print with CSS columns.
2. Add an Education section.
3. Add a downloadable PDF link.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 535: CV / resume page for Dina Fathy

Theme: Papyrus Stationery (Heliopolis) | Level 2 | Files: index.html, styles.css

Brief

Lay out a one-page CV with header, experience entries using article and time, and a skills list as pills, with a print stylesheet.

Learning goals

- Structure a CV semantically
- Style skill tags with Flexbox wrapping
- Add @media print rules

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, section, article, h3, time, ul, li	border-bottom, text-transform, letter-spacing, flex-wrap, @media print

Build guide

1. Write the header with name, role and contact links.
2. Add an Experience section with one article per job.
3. Use <time> for the years.
4. Add a Skills list.
5. Style section headings small and uppercase.
6. Print preview (Ctrl+P) and adjust the print rules.

Project 535: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Dina Fathy - CV</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="cv">
    <header>
      <h1>Dina Fathy</h1>
      <p class="role">Founder, Papyrus Stationery &middot;
Heliopolis</p>
      <p class="links"><a href="mailto:stationery@example.com">Email</
a> &middot; <a href="tel:+20100000000">Phone</a> &middot; <a
href="https://example.com">Website</a></p>
    </header>
    <section>
      <h2>Experience</h2>
      <article>
        <h3>Founder, Papyrus Stationery</h3>
        <p class="when"><time datetime="2018">2018</time> - present</
p>
        <ul><li>Grew the business to 4 core products.</li><li>Built a
loyal customer base in Heliopolis.</li></ul>
      </article>
      <article>
        <h3>Assistant manager, Local Company</h3>
        <p class="when"><time datetime="2014">2014</time> - <time
datetime="2018">2018</time></p>
        <ul><li>Managed a team of six.</li></ul>
      </article>
    </section>
    <section>
      <h2>Skills</h2>
      <ul class="skills"><li>Customer service</li><li>Planning</
li><li>HTML and CSS</li><li>Arabic and English</li></ul>
    </section>
  </main>
</body>
</html>
```

Project 535: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
```

```
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.cv { max-width: 46rem; margin: 2rem auto; padding: 0 1rem; }
header { border-bottom: 3px solid var(--brand); padding-bottom: 1rem;
margin-bottom: 1.5rem; }
h1 { margin: 0; }
.role { margin: .2rem 0; color: var(--muted); }
h2 { color: var(--brand); text-transform: uppercase; font-size: 1rem;
letter-spacing: .08em; margin-top: 1.5rem; }
h3 { margin: 1rem 0 0; }
.when { margin: 0; color: var(--muted); font-size: .9rem; }
.skills { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .5rem; }
.skills li { background: var(--accent); padding: .3rem .8rem; border-
radius: 999px; }
@media print { a { color: inherit; text-decoration: none; } .cv { max-
width: none; } }
```

Project 535 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Dina Fathy - CV</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="cv">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Dina Fathy	The main heading; only one per page.
Founder, Papyrus Stationery · Heliopolis	A paragraph of text.
Email ...	A hyperlink; href gives the destination.
<section>	A thematic group of content, normally with its own heading.
Experience	Second-level heading for a section.
<article>	A self-contained piece: card, post, product.

Line	What it does
Founder, Papyrus Stationery	Third-level heading, inside an h2 section.
<time date time="2018">2018</time> - present	A date or time; datetime holds the machine-readable value.
Grew the business to 4 core products. Built a loyal...	Unordered (bulleted) list.
Managed a team of six.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
font-size: 1rem;	Size of the text.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
@media print { a { color: inherit; text-decoration: none; } .cv { m...	Removes the underline from links.

Check your work

- Contact links work (mailto, tel)
- Jobs in reverse chronological order
- Skills wrap
- Prints on one page without colours

Exercises

1. Add a two-column layout for print with CSS columns.
2. Add an Education section.
3. Add a downloadable PDF link.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 536: CV / resume page for Hossam Ali

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 2 | Files: index.html, styles.css

Brief

Lay out a one-page CV with header, experience entries using article and time, and a skills list as pills, with a print stylesheet.

Learning goals

- Structure a CV semantically
- Style skill tags with Flexbox wrapping
- Add @media print rules

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, section, article, h3, time, ul, li	border-bottom, text-transform, letter-spacing, flex-wrap, @media print

Build guide

1. Write the header with name, role and contact links.
2. Add an Experience section with one article per job.
3. Use <time> for the years.
4. Add a Skills list.
5. Style section headings small and uppercase.
6. Print preview (Ctrl+P) and adjust the print rules.

Project 536: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Hossam Ali - CV</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="cv">
    <header>
      <h1>Hossam Ali</h1>
      <p class="role">Founder, Oasis Plant Nursery &middot; Sheikh
Zayed</p>
      <p class="links"><a href="mailto:plants@example.com">Email</a>
&middot; <a href="tel:+20100000000">Phone</a> &middot; <a href="https:
//example.com">Website</a></p>
    </header>
    <section>
      <h2>Experience</h2>
      <article>
        <h3>Founder, Oasis Plant Nursery</h3>
        <p class="when"><time datetime="2018">2018</time> - present</
p>
        <ul><li>Grew the business to 4 core plants.</li><li>Built a
loyal customer base in Sheikh Zayed.</li></ul>
      </article>
      <article>
        <h3>Assistant manager, Local Company</h3>
        <p class="when"><time datetime="2014">2014</time> - <time
datetime="2018">2018</time></p>
        <ul><li>Managed a team of six.</li></ul>
      </article>
    </section>
    <section>
      <h2>Skills</h2>
      <ul class="skills"><li>Customer service</li><li>Planning</
li><li>HTML and CSS</li><li>Arabic and English</li></ul>
    </section>
  </main>
</body>
</html>
```

Project 536: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
```

```
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.cv { max-width: 46rem; margin: 2rem auto; padding: 0 1rem; }
header { border-bottom: 3px solid var(--brand); padding-bottom: 1rem;
margin-bottom: 1.5rem; }
h1 { margin: 0; }
.role { margin: .2rem 0; color: var(--muted); }
h2 { color: var(--brand); text-transform: uppercase; font-size: 1rem;
letter-spacing: .08em; margin-top: 1.5rem; }
h3 { margin: 1rem 0 0; }
.when { margin: 0; color: var(--muted); font-size: .9rem; }
.skills { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .5rem; }
.skills li { background: var(--accent); padding: .3rem .8rem; border-
radius: 999px; }
@media print { a { color: inherit; text-decoration: none; } .cv { max-
width: none; } }
```

Project 536 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Hossam Ali - CV</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="cv">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Hossam Ali	The main heading; only one per page.
Founder, Oasis Plant Nursery · Sheikh Zayed	A paragraph of text.
Email &mid...	A hyperlink; href gives the destination.
<section>	A thematic group of content, normally with its own heading.
Experience	Second-level heading for a section.
<article>	A self-contained piece: card, post, product.

Line	What it does
Founder, Oasis Plant Nursery	Third-level heading, inside an h2 section.
<time date time="2018">2018</time> - present	A date or time; datetime holds the machine-readable value.
Grew the business to 4 core plants. Built a loyal c...	Unordered (bulleted) list.
Managed a team of six.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
font-size: 1rem;	Size of the text.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
@media print { a { color: inherit; text-decoration: none; } .cv { m...	Removes the underline from links.

Check your work

- Contact links work (mailto, tel)
- Jobs in reverse chronological order
- Skills wrap
- Prints on one page without colours

Exercises

1. Add a two-column layout for print with CSS columns.
2. Add an Education section.
3. Add a downloadable PDF link.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 537: CV / resume page for Tarek Lotfy

Theme: Cedar Furniture (Damietta) | Level 2 | Files: index.html, styles.css

Brief

Lay out a one-page CV with header, experience entries using article and time, and a skills list as pills, with a print stylesheet.

Learning goals

- Structure a CV semantically
- Style skill tags with Flexbox wrapping
- Add @media print rules

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, section, article, h3, time, ul, li	border-bottom, text-transform, letter-spacing, flex-wrap, @media print

Build guide

1. Write the header with name, role and contact links.
2. Add an Experience section with one article per job.
3. Use <time> for the years.
4. Add a Skills list.
5. Style section headings small and uppercase.
6. Print preview (Ctrl+P) and adjust the print rules.

Project 537: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Tarek Lotfy - CV</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="cv">
    <header>
      <h1>Tarek Lotfy</h1>
      <p class="role">Founder, Cedar Furniture &middot; Damietta</p>
      <p class="links"><a href="mailto:furniture@example.com">Email</
a> &middot; <a href="tel:+20100000000">Phone</a> &middot; <a
href="https://example.com">Website</a></p>
    </header>
    <section>
      <h2>Experience</h2>
      <article>
        <h3>Founder, Cedar Furniture</h3>
        <p class="when"><time datetime="2018">2018</time> - present</
p>
        <ul><li>Grew the business to 4 core pieces.</li><li>Built a
loyal customer base in Damietta.</li></ul>
      </article>
      <article>
        <h3>Assistant manager, Local Company</h3>
        <p class="when"><time datetime="2014">2014</time> - <time
datetime="2018">2018</time></p>
        <ul><li>Managed a team of six.</li></ul>
      </article>
    </section>
    <section>
      <h2>Skills</h2>
      <ul class="skills"><li>Customer service</li><li>Planning</
li><li>HTML and CSS</li><li>Arabic and English</li></ul>
    </section>
  </main>
</body>
</html>
```

Project 537: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.cv { max-width: 46rem; margin: 2rem auto; padding: 0 1rem; }
header { border-bottom: 3px solid var(--brand); padding-bottom: 1rem;
margin-bottom: 1.5rem; }
h1 { margin: 0; }
.role { margin: .2rem 0; color: var(--muted); }
h2 { color: var(--brand); text-transform: uppercase; font-size: 1rem;
letter-spacing: .08em; margin-top: 1.5rem; }
h3 { margin: 1rem 0 0; }
.when { margin: 0; color: var(--muted); font-size: .9rem; }
.skills { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .5rem; }
.skills li { background: var(--accent); padding: .3rem .8rem; border-
radius: 999px; }
@media print { a { color: inherit; text-decoration: none; } .cv { max-
width: none; } }
```

Project 537 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Tarek Lotfy - CV</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="cv">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Tarek Lotfy	The main heading; only one per page.
Founder, Cedar Furniture · Damietta	A paragraph of text.
Email &...	A hyperlink; href gives the destination.
<section>	A thematic group of content, normally with its own heading.
Experience	Second-level heading for a section.
<article>	A self-contained piece: card, post, product.

Line	What it does
Founder, Cedar Furniture	Third-level heading, inside an h2 section.
<time date time="2018">2018</time> - present	A date or time; datetime holds the machine-readable value.
Grew the business to 4 core pieces. Built a loyal c...	Unordered (bulleted) list.
Managed a team of six.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
font-size: 1rem;	Size of the text.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
@media print { a { color: inherit; text-decoration: none; } .cv { m...	Removes the underline from links.

Check your work

- Contact links work (mailto, tel)
- Jobs in reverse chronological order
- Skills wrap
- Prints on one page without colours

Exercises

1. Add a two-column layout for print with CSS columns.
2. Add an Education section.
3. Add a downloadable PDF link.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 538: CV / resume page for Mostafa Gamal

Theme: Byte Repair (Nasr City) | Level 2 | Files: index.html, styles.css

Brief

Lay out a one-page CV with header, experience entries using article and time, and a skills list as pills, with a print stylesheet.

Learning goals

- Structure a CV semantically
- Style skill tags with Flexbox wrapping
- Add @media print rules

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, section, article, h3, time, ul, li	border-bottom, text-transform, letter-spacing, flex-wrap, @media print

Build guide

1. Write the header with name, role and contact links.
2. Add an Experience section with one article per job.
3. Use <time> for the years.
4. Add a Skills list.
5. Style section headings small and uppercase.
6. Print preview (Ctrl+P) and adjust the print rules.

Project 538: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Mostafa Gamal - CV</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="cv">
    <header>
      <h1>Mostafa Gamal</h1>
      <p class="role">Founder, Byte Repair &middot; Nasr City</p>
      <p class="links"><a href="mailto:repair@example.com">Email</a>
&middot; <a href="tel:+20100000000">Phone</a> &middot; <a href="https:
//example.com">Website</a></p>
    </header>
    <section>
      <h2>Experience</h2>
      <article>
        <h3>Founder, Byte Repair</h3>
        <p class="when"><time datetime="2018">2018</time> - present</
p>
        <ul><li>Grew the business to 4 core repairs.</li><li>Built a
loyal customer base in Nasr City.</li></ul>
      </article>
      <article>
        <h3>Assistant manager, Local Company</h3>
        <p class="when"><time datetime="2014">2014</time> - <time
datetime="2018">2018</time></p>
        <ul><li>Managed a team of six.</li></ul>
      </article>
    </section>
    <section>
      <h2>Skills</h2>
      <ul class="skills"><li>Customer service</li><li>Planning</
li><li>HTML and CSS</li><li>Arabic and English</li></ul>
    </section>
  </main>
</body>
</html>
```

Project 538: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.cv { max-width: 46rem; margin: 2rem auto; padding: 0 1rem; }
header { border-bottom: 3px solid var(--brand); padding-bottom: 1rem;
margin-bottom: 1.5rem; }
h1 { margin: 0; }
.role { margin: .2rem 0; color: var(--muted); }
h2 { color: var(--brand); text-transform: uppercase; font-size: 1rem;
letter-spacing: .08em; margin-top: 1.5rem; }
h3 { margin: 1rem 0 0; }
.when { margin: 0; color: var(--muted); font-size: .9rem; }
.skills { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .5rem; }
.skills li { background: var(--accent); padding: .3rem .8rem; border-
radius: 999px; }
@media print { a { color: inherit; text-decoration: none; } .cv { max-
width: none; } }
```

Project 538 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Mostafa Gamal - CV</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="cv">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Mostafa Gamal	The main heading; only one per page.
Founder, Byte Repair · Nasr City	A paragraph of text.
Email &mid...	A hyperlink; href gives the destination.
<section>	A thematic group of content, normally with its own heading.
Experience	Second-level heading for a section.
<article>	A self-contained piece: card, post, product.

Line	What it does
Founder, Byte Repair	Third-level heading, inside an h2 section.
<time date time="2018">2018</time> - present	A date or time; datetime holds the machine-readable value.
Grew the business to 4 core repairs. Built a loyal ...	Unordered (bulleted) list.
Managed a team of six.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
font-size: 1rem;	Size of the text.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
@media print { a { color: inherit; text-decoration: none; } .cv { m...	Removes the underline from links.

Check your work

- Contact links work (mailto, tel)
- Jobs in reverse chronological order
- Skills wrap
- Prints on one page without colours

Exercises

1. Add a two-column layout for print with CSS columns.
2. Add an Education section.
3. Add a downloadable PDF link.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 539: CV / resume page for Rana Ibrahim

Theme: Sahara Pet Care (New Cairo) | Level 2 | Files: index.html, styles.css

Brief

Lay out a one-page CV with header, experience entries using article and time, and a skills list as pills, with a print stylesheet.

Learning goals

- Structure a CV semantically
- Style skill tags with Flexbox wrapping
- Add @media print rules

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, section, article, h3, time, ul, li	border-bottom, text-transform, letter-spacing, flex-wrap, @media print

Build guide

1. Write the header with name, role and contact links.
2. Add an Experience section with one article per job.
3. Use <time> for the years.
4. Add a Skills list.
5. Style section headings small and uppercase.
6. Print preview (Ctrl+P) and adjust the print rules.

Project 539: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Rana Ibrahim - CV</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="cv">
    <header>
      <h1>Rana Ibrahim</h1>
      <p class="role">Founder, Sahara Pet Care &middot; New Cairo</p>
      <p class="links"><a href="mailto:pets@example.com">Email</a>
&middot; <a href="tel:+20100000000">Phone</a> &middot; <a href="https:
//example.com">Website</a></p>
    </header>
    <section>
      <h2>Experience</h2>
      <article>
        <h3>Founder, Sahara Pet Care</h3>
        <p class="when"><time datetime="2018">2018</time> - present</
p>
        <ul><li>Grew the business to 4 core services.</li><li>Built a
loyal customer base in New Cairo.</li></ul>
      </article>
      <article>
        <h3>Assistant manager, Local Company</h3>
        <p class="when"><time datetime="2014">2014</time> - <time
datetime="2018">2018</time></p>
        <ul><li>Managed a team of six.</li></ul>
      </article>
    </section>
    <section>
      <h2>Skills</h2>
      <ul class="skills"><li>Customer service</li><li>Planning</
li><li>HTML and CSS</li><li>Arabic and English</li></ul>
    </section>
  </main>
</body>
</html>
```

Project 539: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.cv { max-width: 46rem; margin: 2rem auto; padding: 0 1rem; }
header { border-bottom: 3px solid var(--brand); padding-bottom: 1rem;
margin-bottom: 1.5rem; }
h1 { margin: 0; }
.role { margin: .2rem 0; color: var(--muted); }
h2 { color: var(--brand); text-transform: uppercase; font-size: 1rem;
letter-spacing: .08em; margin-top: 1.5rem; }
h3 { margin: 1rem 0 0; }
.when { margin: 0; color: var(--muted); font-size: .9rem; }
.skills { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .5rem; }
.skills li { background: var(--accent); padding: .3rem .8rem; border-
radius: 999px; }
@media print { a { color: inherit; text-decoration: none; } .cv { max-
width: none; } }
```

Project 539 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Rana Ibrahim - CV</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="cv">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Rana Ibrahim	The main heading; only one per page.
Founder, Sahara Pet Care · New Cairo	A paragraph of text.
Email &middo...	A hyperlink; href gives the destination.
<section>	A thematic group of content, normally with its own heading.
Experience	Second-level heading for a section.
<article>	A self-contained piece: card, post, product.

Line	What it does
Founder, Sahara Pet Care	Third-level heading, inside an h2 section.
<time date time="2018">2018</time> - present	A date or time; datetime holds the machine-readable value.
Grew the business to 4 core services. Built a loyal...	Unordered (bulleted) list.
Managed a team of six.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
font-size: 1rem;	Size of the text.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
@media print { a { color: inherit; text-decoration: none; } .cv { m...	Removes the underline from links.

Check your work

- Contact links work (mailto, tel)
- Jobs in reverse chronological order
- Skills wrap
- Prints on one page without colours

Exercises

1. Add a two-column layout for print with CSS columns.
2. Add an Education section.
3. Add a downloadable PDF link.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 540: CV / resume page for Amr Selim

Theme: Alexandria Sailing School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Lay out a one-page CV with header, experience entries using article and time, and a skills list as pills, with a print stylesheet.

Learning goals

- Structure a CV semantically
- Style skill tags with Flexbox wrapping
- Add @media print rules

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, section, article, h3, time, ul, li	border-bottom, text-transform, letter-spacing, flex-wrap, @media print

Build guide

1. Write the header with name, role and contact links.
2. Add an Experience section with one article per job.
3. Use <time> for the years.
4. Add a Skills list.
5. Style section headings small and uppercase.
6. Print preview (Ctrl+P) and adjust the print rules.

Project 540: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Amr Selim - CV</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="cv">
    <header>
      <h1>Amr Selim</h1>
      <p class="role">Founder, Alexandria Sailing School &middot;
Alexandria</p>
      <p class="links"><a href="mailto:sailing@example.com">Email</a>
&middot; <a href="tel:+20100000000">Phone</a> &middot; <a href="https:
//example.com">Website</a></p>
    </header>
    <section>
      <h2>Experience</h2>
      <article>
        <h3>Founder, Alexandria Sailing School</h3>
        <p class="when"><time datetime="2018">2018</time> - present</
p>
        <ul><li>Grew the business to 4 core lessons.</li><li>Built a
loyal customer base in Alexandria.</li></ul>
      </article>
      <article>
        <h3>Assistant manager, Local Company</h3>
        <p class="when"><time datetime="2014">2014</time> - <time
datetime="2018">2018</time></p>
        <ul><li>Managed a team of six.</li></ul>
      </article>
    </section>
    <section>
      <h2>Skills</h2>
      <ul class="skills"><li>Customer service</li><li>Planning</
li><li>HTML and CSS</li><li>Arabic and English</li></ul>
    </section>
  </main>
</body>
</html>
```

Project 540: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
```

```
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.cv { max-width: 46rem; margin: 2rem auto; padding: 0 1rem; }
header { border-bottom: 3px solid var(--brand); padding-bottom: 1rem;
margin-bottom: 1.5rem; }
h1 { margin: 0; }
.role { margin: .2rem 0; color: var(--muted); }
h2 { color: var(--brand); text-transform: uppercase; font-size: 1rem;
letter-spacing: .08em; margin-top: 1.5rem; }
h3 { margin: 1rem 0 0; }
.when { margin: 0; color: var(--muted); font-size: .9rem; }
.skills { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .5rem; }
.skills li { background: var(--accent); padding: .3rem .8rem; border-
radius: 999px; }
@media print { a { color: inherit; text-decoration: none; } .cv { max-
width: none; } }
```

Project 540 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Amr Selim - CV</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="cv">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Amr Selim	The main heading; only one per page.
<p class="role">Founder, Alexandria Sailing School · Alexand...	A paragraph of text.
<p class="links">Email &mi...	A hyperlink; href gives the destination.
<section>	A thematic group of content, normally with its own heading.
Experience	Second-level heading for a section.
<article>	A self-contained piece: card, post, product.

Line	What it does
Founder, Alexandria Sailing School	Third-level heading, inside an h2 section.
<time date time="2018">2018</time> - present	A date or time; datetime holds the machine-readable value.
Grew the business to 4 core lessons. Built a loyal ...	Unordered (bulleted) list.
Managed a team of six.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
font-size: 1rem;	Size of the text.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
@media print { a { color: inherit; text-decoration: none; } .cv { m...	Removes the underline from links.

Check your work

- Contact links work (mailto, tel)
- Jobs in reverse chronological order
- Skills wrap
- Prints on one page without colours

Exercises

1. Add a two-column layout for print with CSS columns.
2. Add an Education section.
3. Add a downloadable PDF link.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 541: CV / resume page for Habiba Saleh

Theme: Habiba Handmade Jewellery (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Lay out a one-page CV with header, experience entries using article and time, and a skills list as pills, with a print stylesheet.

Learning goals

- Structure a CV semantically
- Style skill tags with Flexbox wrapping
- Add @media print rules

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, section, article, h3, time, ul, li	border-bottom, text-transform, letter-spacing, flex-wrap, @media print

Build guide

1. Write the header with name, role and contact links.
2. Add an Experience section with one article per job.
3. Use <time> for the years.
4. Add a Skills list.
5. Style section headings small and uppercase.
6. Print preview (Ctrl+P) and adjust the print rules.

Project 541: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Saleh - CV</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="cv">
    <header>
      <h1>Habiba Saleh</h1>
      <p class="role">Founder, Habiba Handmade Jewellery &middot;
Aswan</p>
      <p class="links"><a href="mailto:jewellery@example.com">Email</
a> &middot; <a href="tel:+20100000000">Phone</a> &middot; <a
href="https://example.com">Website</a></p>
    </header>
    <section>
      <h2>Experience</h2>
      <article>
        <h3>Founder, Habiba Handmade Jewellery</h3>
        <p class="when"><time datetime="2018">2018</time> - present</
p>
        <ul><li>Grew the business to 4 core items.</li><li>Built a
loyal customer base in Aswan.</li></ul>
      </article>
      <article>
        <h3>Assistant manager, Local Company</h3>
        <p class="when"><time datetime="2014">2014</time> - <time
datetime="2018">2018</time></p>
        <ul><li>Managed a team of six.</li></ul>
      </article>
    </section>
    <section>
      <h2>Skills</h2>
      <ul class="skills"><li>Customer service</li><li>Planning</
li><li>HTML and CSS</li><li>Arabic and English</li></ul>
    </section>
  </main>
</body>
</html>
```

Project 541: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
```

```
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.cv { max-width: 46rem; margin: 2rem auto; padding: 0 1rem; }
header { border-bottom: 3px solid var(--brand); padding-bottom: 1rem;
margin-bottom: 1.5rem; }
h1 { margin: 0; }
.role { margin: .2rem 0; color: var(--muted); }
h2 { color: var(--brand); text-transform: uppercase; font-size: 1rem;
letter-spacing: .08em; margin-top: 1.5rem; }
h3 { margin: 1rem 0 0; }
.when { margin: 0; color: var(--muted); font-size: .9rem; }
.skills { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .5rem; }
.skills li { background: var(--accent); padding: .3rem .8rem; border-
radius: 999px; }
@media print { a { color: inherit; text-decoration: none; } .cv { max-
width: none; } }
```

Project 541 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Saleh - CV</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="cv">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Habiba Saleh	The main heading; only one per page.
Founder, Habiba Handmade Jewellery · Aswan	A paragraph of text.
Email &...	A hyperlink; href gives the destination.
<section>	A thematic group of content, normally with its own heading.
Experience	Second-level heading for a section.
<article>	A self-contained piece: card, post, product.

Line	What it does
Founder, Habiba Handmade Jewellery	Third-level heading, inside an h2 section.
<time date time="2018">2018</time> - present	A date or time; datetime holds the machine-readable value.
Grew the business to 4 core items. Built a loyal cu...	Unordered (bulleted) list.
Managed a team of six.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
font-size: 1rem;	Size of the text.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
@media print { a { color: inherit; text-decoration: none; } .cv { m...	Removes the underline from links.

Check your work

- Contact links work (mailto, tel)
- Jobs in reverse chronological order
- Skills wrap
- Prints on one page without colours

Exercises

1. Add a two-column layout for print with CSS columns.
2. Add an Education section.
3. Add a downloadable PDF link.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 542: CV / resume page for Ahmed Mahmoud

Theme: Fayoum Pottery Studio (Tunis Village) | Level 2 | Files: index.html, styles.css

Brief

Lay out a one-page CV with header, experience entries using article and time, and a skills list as pills, with a print stylesheet.

Learning goals

- Structure a CV semantically
- Style skill tags with Flexbox wrapping
- Add @media print rules

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, section, article, h3, time, ul, li	border-bottom, text-transform, letter-spacing, flex-wrap, @media print

Build guide

1. Write the header with name, role and contact links.
2. Add an Experience section with one article per job.
3. Use <time> for the years.
4. Add a Skills list.
5. Style section headings small and uppercase.
6. Print preview (Ctrl+P) and adjust the print rules.

Project 542: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ahmed Mahmoud - CV</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="cv">
    <header>
      <h1>Ahmed Mahmoud</h1>
      <p class="role">Founder, Fayoum Pottery Studio &middot; Tunis
Village</p>
      <p class="links"><a href="mailto:pottery@example.com">Email</a>
&middot; <a href="tel:+20100000000">Phone</a> &middot; <a href="https:
//example.com">Website</a></p>
    </header>
    <section>
      <h2>Experience</h2>
      <article>
        <h3>Founder, Fayoum Pottery Studio</h3>
        <p class="when"><time datetime="2018">2018</time> - present</
p>
        <ul><li>Grew the business to 4 core workshops.</li><li>Built
a loyal customer base in Tunis Village.</li></ul>
      </article>
      <article>
        <h3>Assistant manager, Local Company</h3>
        <p class="when"><time datetime="2014">2014</time> - <time
datetime="2018">2018</time></p>
        <ul><li>Managed a team of six.</li></ul>
      </article>
    </section>
    <section>
      <h2>Skills</h2>
      <ul class="skills"><li>Customer service</li><li>Planning</
li><li>HTML and CSS</li><li>Arabic and English</li></ul>
    </section>
  </main>
</body>
</html>
```

Project 542: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
```

```
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.cv { max-width: 46rem; margin: 2rem auto; padding: 0 1rem; }
header { border-bottom: 3px solid var(--brand); padding-bottom: 1rem;
margin-bottom: 1.5rem; }
h1 { margin: 0; }
.role { margin: .2rem 0; color: var(--muted); }
h2 { color: var(--brand); text-transform: uppercase; font-size: 1rem;
letter-spacing: .08em; margin-top: 1.5rem; }
h3 { margin: 1rem 0 0; }
.when { margin: 0; color: var(--muted); font-size: .9rem; }
.skills { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .5rem; }
.skills li { background: var(--accent); padding: .3rem .8rem; border-
radius: 999px; }
@media print { a { color: inherit; text-decoration: none; } .cv { max-
width: none; } }
```

Project 542 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ahmed Mahmoud - CV</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="cv">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Ahmed Mahmoud	The main heading; only one per page.
<p class="role">Founder, Fayoum Pottery Studio · Tunis Villa...	A paragraph of text.
<p class="links">Email &mi...	A hyperlink; href gives the destination.
<section>	A thematic group of content, normally with its own heading.
Experience	Second-level heading for a section.
<article>	A self-contained piece: card, post, product.

Line	What it does
Founder, Fayoum Pottery Studio	Third-level heading, inside an h2 section.
<time date time="2018">2018</time> - present	A date or time; datetime holds the machine-readable value.
Grew the business to 4 core workshops. Built a loya...	Unordered (bulleted) list.
Managed a team of six.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
font-size: 1rem;	Size of the text.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
@media print { a { color: inherit; text-decoration: none; } .cv { m...	Removes the underline from links.

Check your work

- Contact links work (mailto, tel)
- Jobs in reverse chronological order
- Skills wrap
- Prints on one page without colours

Exercises

1. Add a two-column layout for print with CSS columns.
2. Add an Education section.
3. Add a downloadable PDF link.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 543: CV / resume page for Mariam Adel

Theme: Cleopatra Beauty Salon (Dokki) | Level 2 | Files: index.html, styles.css

Brief

Lay out a one-page CV with header, experience entries using article and time, and a skills list as pills, with a print stylesheet.

Learning goals

- Structure a CV semantically
- Style skill tags with Flexbox wrapping
- Add @media print rules

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, section, article, h3, time, ul, li	border-bottom, text-transform, letter-spacing, flex-wrap, @media print

Build guide

1. Write the header with name, role and contact links.
2. Add an Experience section with one article per job.
3. Use <time> for the years.
4. Add a Skills list.
5. Style section headings small and uppercase.
6. Print preview (Ctrl+P) and adjust the print rules.

Project 543: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Mariam Adel - CV</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="cv">
    <header>
      <h1>Mariam Adel</h1>
      <p class="role">Founder, Cleopatra Beauty Salon &middot; Dokki</
p>
      <p class="links"><a href="mailto:salon@example.com">Email</a>
&middot; <a href="tel:+20100000000">Phone</a> &middot; <a href="https:
//example.com">Website</a></p>
    </header>
    <section>
      <h2>Experience</h2>
      <article>
        <h3>Founder, Cleopatra Beauty Salon</h3>
        <p class="when"><time datetime="2018">2018</time> - present</
p>
        <ul><li>Grew the business to 4 core treatments.</li><li>Built
a loyal customer base in Dokki.</li></ul>
      </article>
      <article>
        <h3>Assistant manager, Local Company</h3>
        <p class="when"><time datetime="2014">2014</time> - <time
datetime="2018">2018</time></p>
        <ul><li>Managed a team of six.</li></ul>
      </article>
    </section>
    <section>
      <h2>Skills</h2>
      <ul class="skills"><li>Customer service</li><li>Planning</
li><li>HTML and CSS</li><li>Arabic and English</li></ul>
    </section>
  </main>
</body>
</html>
```

Project 543: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
```

```
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.cv { max-width: 46rem; margin: 2rem auto; padding: 0 1rem; }
header { border-bottom: 3px solid var(--brand); padding-bottom: 1rem;
margin-bottom: 1.5rem; }
h1 { margin: 0; }
.role { margin: .2rem 0; color: var(--muted); }
h2 { color: var(--brand); text-transform: uppercase; font-size: 1rem;
letter-spacing: .08em; margin-top: 1.5rem; }
h3 { margin: 1rem 0 0; }
.when { margin: 0; color: var(--muted); font-size: .9rem; }
.skills { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .5rem; }
.skills li { background: var(--accent); padding: .3rem .8rem; border-
radius: 999px; }
@media print { a { color: inherit; text-decoration: none; } .cv { max-
width: none; } }
```

Project 543 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Mariam Adel - CV</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="cv">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Mariam Adel	The main heading; only one per page.
Founder, Cleopatra Beauty Salon · Dokki	A paragraph of text.
Email &midd...	A hyperlink; href gives the destination.
<section>	A thematic group of content, normally with its own heading.
Experience	Second-level heading for a section.
<article>	A self-contained piece: card, post, product.

Line	What it does
Founder, Cleopatra Beauty Salon	Third-level heading, inside an h2 section.
<time date time="2018">2018</time> - present	A date or time; datetime holds the machine-readable value.
Grew the business to 4 core treatments. Built a loy...	Unordered (bulleted) list.
Managed a team of six.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
font-size: 1rem;	Size of the text.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
@media print { a { color: inherit; text-decoration: none; } .cv { m...	Removes the underline from links.

Check your work

- Contact links work (mailto, tel)
- Jobs in reverse chronological order
- Skills wrap
- Prints on one page without colours

Exercises

1. Add a two-column layout for print with CSS columns.
2. Add an Education section.
3. Add a downloadable PDF link.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 544: CV / resume page for Khaled Nasser

Theme: Suez Auto Service (Suez) | Level 2 | Files: index.html, styles.css

Brief

Lay out a one-page CV with header, experience entries using article and time, and a skills list as pills, with a print stylesheet.

Learning goals

- Structure a CV semantically
- Style skill tags with Flexbox wrapping
- Add @media print rules

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, section, article, h3, time, ul, li	border-bottom, text-transform, letter-spacing, flex-wrap, @media print

Build guide

1. Write the header with name, role and contact links.
2. Add an Experience section with one article per job.
3. Use <time> for the years.
4. Add a Skills list.
5. Style section headings small and uppercase.
6. Print preview (Ctrl+P) and adjust the print rules.

Project 544: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Khaled Nasser - CV</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="cv">
    <header>
      <h1>Khaled Nasser</h1>
      <p class="role">Founder, Suez Auto Service &middot; Suez</p>
      <p class="links"><a href="mailto:auto@example.com">Email</a>
&middot; <a href="tel:+20100000000">Phone</a> &middot; <a href="https:
//example.com">Website</a></p>
    </header>
    <section>
      <h2>Experience</h2>
      <article>
        <h3>Founder, Suez Auto Service</h3>
        <p class="when"><time datetime="2018">2018</time> - present</
p>
        <ul><li>Grew the business to 4 core services.</li><li>Built a
loyal customer base in Suez.</li></ul>
      </article>
      <article>
        <h3>Assistant manager, Local Company</h3>
        <p class="when"><time datetime="2014">2014</time> - <time
datetime="2018">2018</time></p>
        <ul><li>Managed a team of six.</li></ul>
      </article>
    </section>
    <section>
      <h2>Skills</h2>
      <ul class="skills"><li>Customer service</li><li>Planning</
li><li>HTML and CSS</li><li>Arabic and English</li></ul>
    </section>
  </main>
</body>
</html>
```

Project 544: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.cv { max-width: 46rem; margin: 2rem auto; padding: 0 1rem; }
header { border-bottom: 3px solid var(--brand); padding-bottom: 1rem;
margin-bottom: 1.5rem; }
h1 { margin: 0; }
.role { margin: .2rem 0; color: var(--muted); }
h2 { color: var(--brand); text-transform: uppercase; font-size: 1rem;
letter-spacing: .08em; margin-top: 1.5rem; }
h3 { margin: 1rem 0 0; }
.when { margin: 0; color: var(--muted); font-size: .9rem; }
.skills { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .5rem; }
.skills li { background: var(--accent); padding: .3rem .8rem; border-
radius: 999px; }
@media print { a { color: inherit; text-decoration: none; } .cv { max-
width: none; } }
```

Project 544 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Khaled Nasser - CV</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="cv">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Khaled Nasser	The main heading; only one per page.
Founder, Suez Auto Service · Suez	A paragraph of text.
Email &middo...	A hyperlink; href gives the destination.
<section>	A thematic group of content, normally with its own heading.
Experience	Second-level heading for a section.
<article>	A self-contained piece: card, post, product.

Line	What it does
Founder, Suez Auto Service	Third-level heading, inside an h2 section.
<time date time="2018">2018</time> - present	A date or time; datetime holds the machine-readable value.
Grew the business to 4 core services. Built a loyal...	Unordered (bulleted) list.
Managed a team of six.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
font-size: 1rem;	Size of the text.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
@media print { a { color: inherit; text-decoration: none; } .cv { m...	Removes the underline from links.

Check your work

- Contact links work (mailto, tel)
- Jobs in reverse chronological order
- Skills wrap
- Prints on one page without colours

Exercises

1. Add a two-column layout for print with CSS columns.
2. Add an Education section.
3. Add a downloadable PDF link.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 545: CV / resume page for Salma Ragab

Theme: Luxor Music Academy (Luxor) | Level 2 | Files: index.html, styles.css

Brief

Lay out a one-page CV with header, experience entries using article and time, and a skills list as pills, with a print stylesheet.

Learning goals

- Structure a CV semantically
- Style skill tags with Flexbox wrapping
- Add @media print rules

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, section, article, h3, time, ul, li	border-bottom, text-transform, letter-spacing, flex-wrap, @media print

Build guide

1. Write the header with name, role and contact links.
2. Add an Experience section with one article per job.
3. Use <time> for the years.
4. Add a Skills list.
5. Style section headings small and uppercase.
6. Print preview (Ctrl+P) and adjust the print rules.

Project 545: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Salma Ragab - CV</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="cv">
    <header>
      <h1>Salma Ragab</h1>
      <p class="role">Founder, Luxor Music Academy &middot; Luxor</p>
      <p class="links"><a href="mailto:music@example.com">Email</a>
&middot; <a href="tel:+20100000000">Phone</a> &middot; <a href="https:
//example.com">Website</a></p>
    </header>
    <section>
      <h2>Experience</h2>
      <article>
        <h3>Founder, Luxor Music Academy</h3>
        <p class="when"><time datetime="2018">2018</time> - present</
p>
        <ul><li>Grew the business to 4 core courses.</li><li>Built a
loyal customer base in Luxor.</li></ul>
      </article>
      <article>
        <h3>Assistant manager, Local Company</h3>
        <p class="when"><time datetime="2014">2014</time> - <time
datetime="2018">2018</time></p>
        <ul><li>Managed a team of six.</li></ul>
      </article>
    </section>
    <section>
      <h2>Skills</h2>
      <ul class="skills"><li>Customer service</li><li>Planning</
li><li>HTML and CSS</li><li>Arabic and English</li></ul>
    </section>
  </main>
</body>
</html>
```

Project 545: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.cv { max-width: 46rem; margin: 2rem auto; padding: 0 1rem; }
header { border-bottom: 3px solid var(--brand); padding-bottom: 1rem;
margin-bottom: 1.5rem; }
h1 { margin: 0; }
.role { margin: .2rem 0; color: var(--muted); }
h2 { color: var(--brand); text-transform: uppercase; font-size: 1rem;
letter-spacing: .08em; margin-top: 1.5rem; }
h3 { margin: 1rem 0 0; }
.when { margin: 0; color: var(--muted); font-size: .9rem; }
.skills { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .5rem; }
.skills li { background: var(--accent); padding: .3rem .8rem; border-
radius: 999px; }
@media print { a { color: inherit; text-decoration: none; } .cv { max-
width: none; } }
```

Project 545 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Salma Ragab - CV</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="cv">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Salma Ragab	The main heading; only one per page.
Founder, Luxor Music Academy · Luxor	A paragraph of text.
Email &midd...	A hyperlink; href gives the destination.
<section>	A thematic group of content, normally with its own heading.
Experience	Second-level heading for a section.
<article>	A self-contained piece: card, post, product.

Line	What it does
Founder, Luxor Music Academy	Third-level heading, inside an h2 section.
<time date time="2018">2018</time> - present	A date or time; datetime holds the machine-readable value.
Grew the business to 4 core courses. Built a loyal ...	Unordered (bulleted) list.
Managed a team of six.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
font-size: 1rem;	Size of the text.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
@media print { a { color: inherit; text-decoration: none; } .cv { m...	Removes the underline from links.

Check your work

- Contact links work (mailto, tel)
- Jobs in reverse chronological order
- Skills wrap
- Prints on one page without colours

Exercises

1. Add a two-column layout for print with CSS columns.
2. Add an Education section.
3. Add a downloadable PDF link.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 546: CV / resume page for Sherif Wahba

Theme: Port Said Seafood (Port Said) | Level 2 | Files: index.html, styles.css

Brief

Lay out a one-page CV with header, experience entries using article and time, and a skills list as pills, with a print stylesheet.

Learning goals

- Structure a CV semantically
- Style skill tags with Flexbox wrapping
- Add @media print rules

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, section, article, h3, time, ul, li	border-bottom, text-transform, letter-spacing, flex-wrap, @media print

Build guide

1. Write the header with name, role and contact links.
2. Add an Experience section with one article per job.
3. Use <time> for the years.
4. Add a Skills list.
5. Style section headings small and uppercase.
6. Print preview (Ctrl+P) and adjust the print rules.

Project 546: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sherif Wahba - CV</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="cv">
    <header>
      <h1>Sherif Wahba</h1>
      <p class="role">Founder, Port Said Seafood &middot; Port Said</
p>
      <p class="links"><a href="mailto:restaurant@example.com">Email</
a> &middot; <a href="tel:+20100000000">Phone</a> &middot; <a
href="https://example.com">Website</a></p>
    </header>
    <section>
      <h2>Experience</h2>
      <article>
        <h3>Founder, Port Said Seafood</h3>
        <p class="when"><time datetime="2018">2018</time> - present</
p>
        <ul><li>Grew the business to 4 core dishes.</li><li>Built a
loyal customer base in Port Said.</li></ul>
      </article>
      <article>
        <h3>Assistant manager, Local Company</h3>
        <p class="when"><time datetime="2014">2014</time> - <time
datetime="2018">2018</time></p>
        <ul><li>Managed a team of six.</li></ul>
      </article>
    </section>
    <section>
      <h2>Skills</h2>
      <ul class="skills"><li>Customer service</li><li>Planning</
li><li>HTML and CSS</li><li>Arabic and English</li></ul>
    </section>
  </main>
</body>
</html>
```

Project 546: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
```

```
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.cv { max-width: 46rem; margin: 2rem auto; padding: 0 1rem; }
header { border-bottom: 3px solid var(--brand); padding-bottom: 1rem;
margin-bottom: 1.5rem; }
h1 { margin: 0; }
.role { margin: .2rem 0; color: var(--muted); }
h2 { color: var(--brand); text-transform: uppercase; font-size: 1rem;
letter-spacing: .08em; margin-top: 1.5rem; }
h3 { margin: 1rem 0 0; }
.when { margin: 0; color: var(--muted); font-size: .9rem; }
.skills { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .5rem; }
.skills li { background: var(--accent); padding: .3rem .8rem; border-
radius: 999px; }
@media print { a { color: inherit; text-decoration: none; } .cv { max-
width: none; } }
```

Project 546 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sherif Wahba - CV</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="cv">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Sherif Wahba	The main heading; only one per page.
Founder, Port Said Seafood · Port Said	A paragraph of text.
Email ...	A hyperlink; href gives the destination.
<section>	A thematic group of content, normally with its own heading.
Experience	Second-level heading for a section.
<article>	A self-contained piece: card, post, product.

Line	What it does
Founder, Port Said Seafood	Third-level heading, inside an h2 section.
<time date time="2018">2018</time> - present	A date or time; datetime holds the machine-readable value.
Grew the business to 4 core dishes. Built a loyal c...	Unordered (bulleted) list.
Managed a team of six.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
font-size: 1rem;	Size of the text.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
@media print { a { color: inherit; text-decoration: none; } .cv { m...	Removes the underline from links.

Check your work

- Contact links work (mailto, tel)
- Jobs in reverse chronological order
- Skills wrap
- Prints on one page without colours

Exercises

1. Add a two-column layout for print with CSS columns.
2. Add an Education section.
3. Add a downloadable PDF link.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 547: CV / resume page for Ghada Kamel

Theme: Delta Kids Library (Tanta) | Level 2 | Files: index.html, styles.css

Brief

Lay out a one-page CV with header, experience entries using article and time, and a skills list as pills, with a print stylesheet.

Learning goals

- Structure a CV semantically
- Style skill tags with Flexbox wrapping
- Add @media print rules

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, section, article, h3, time, ul, li	border-bottom, text-transform, letter-spacing, flex-wrap, @media print

Build guide

1. Write the header with name, role and contact links.
2. Add an Experience section with one article per job.
3. Use <time> for the years.
4. Add a Skills list.
5. Style section headings small and uppercase.
6. Print preview (Ctrl+P) and adjust the print rules.

Project 547: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ghada Kamel - CV</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="cv">
    <header>
      <h1>Ghada Kamel</h1>
      <p class="role">Founder, Delta Kids Library &middot; Tanta</p>
      <p class="links"><a href="mailto:library@example.com">Email</a>
&middot; <a href="tel:+20100000000">Phone</a> &middot; <a href="https:
//example.com">Website</a></p>
    </header>
    <section>
      <h2>Experience</h2>
      <article>
        <h3>Founder, Delta Kids Library</h3>
        <p class="when"><time datetime="2018">2018</time> - present</
p>
        <ul><li>Grew the business to 4 core programmes.</li><li>Built
a loyal customer base in Tanta.</li></ul>
      </article>
      <article>
        <h3>Assistant manager, Local Company</h3>
        <p class="when"><time datetime="2014">2014</time> - <time
datetime="2018">2018</time></p>
        <ul><li>Managed a team of six.</li></ul>
      </article>
    </section>
    <section>
      <h2>Skills</h2>
      <ul class="skills"><li>Customer service</li><li>Planning</
li><li>HTML and CSS</li><li>Arabic and English</li></ul>
    </section>
  </main>
</body>
</html>
```

Project 547: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.cv { max-width: 46rem; margin: 2rem auto; padding: 0 1rem; }
header { border-bottom: 3px solid var(--brand); padding-bottom: 1rem;
margin-bottom: 1.5rem; }
h1 { margin: 0; }
.role { margin: .2rem 0; color: var(--muted); }
h2 { color: var(--brand); text-transform: uppercase; font-size: 1rem;
letter-spacing: .08em; margin-top: 1.5rem; }
h3 { margin: 1rem 0 0; }
.when { margin: 0; color: var(--muted); font-size: .9rem; }
.skills { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .5rem; }
.skills li { background: var(--accent); padding: .3rem .8rem; border-
radius: 999px; }
@media print { a { color: inherit; text-decoration: none; } .cv { max-
width: none; } }
```

Project 547 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ghada Kamel - CV</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="cv">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Ghada Kamel	The main heading; only one per page.
Founder, Delta Kids Library · Tanta	A paragraph of text.
Email &mi...	A hyperlink; href gives the destination.
<section>	A thematic group of content, normally with its own heading.
Experience	Second-level heading for a section.
<article>	A self-contained piece: card, post, product.

Line	What it does
Founder, Delta Kids Library	Third-level heading, inside an h2 section.
<time date time="2018">2018</time> - present	A date or time; datetime holds the machine-readable value.
Grew the business to 4 core programmes. Built a loy...	Unordered (bulleted) list.
Managed a team of six.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
font-size: 1rem;	Size of the text.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
@media print { a { color: inherit; text-decoration: none; } .cv { m...	Removes the underline from links.

Check your work

- Contact links work (mailto, tel)
- Jobs in reverse chronological order
- Skills wrap
- Prints on one page without colours

Exercises

1. Add a two-column layout for print with CSS columns.
2. Add an Education section.
3. Add a downloadable PDF link.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 548: CV / resume page for Fatma Hassan

Theme: Nubian Guest House (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Lay out a one-page CV with header, experience entries using article and time, and a skills list as pills, with a print stylesheet.

Learning goals

- Structure a CV semantically
- Style skill tags with Flexbox wrapping
- Add @media print rules

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, section, article, h3, time, ul, li	border-bottom, text-transform, letter-spacing, flex-wrap, @media print

Build guide

1. Write the header with name, role and contact links.
2. Add an Experience section with one article per job.
3. Use <time> for the years.
4. Add a Skills list.
5. Style section headings small and uppercase.
6. Print preview (Ctrl+P) and adjust the print rules.

Project 548: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fatma Hassan - CV</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="cv">
    <header>
      <h1>Fatma Hassan</h1>
      <p class="role">Founder, Nubian Guest House &middot; Aswan</p>
      <p class="links"><a href="mailto:guesthouse@example.com">Email</
a> &middot; <a href="tel:+20100000000">Phone</a> &middot; <a
href="https://example.com">Website</a></p>
    </header>
    <section>
      <h2>Experience</h2>
      <article>
        <h3>Founder, Nubian Guest House</h3>
        <p class="when"><time datetime="2018">2018</time> - present</
p>
        <ul><li>Grew the business to 4 core rooms.</li><li>Built a
loyal customer base in Aswan.</li></ul>
      </article>
      <article>
        <h3>Assistant manager, Local Company</h3>
        <p class="when"><time datetime="2014">2014</time> - <time
datetime="2018">2018</time></p>
        <ul><li>Managed a team of six.</li></ul>
      </article>
    </section>
    <section>
      <h2>Skills</h2>
      <ul class="skills"><li>Customer service</li><li>Planning</
li><li>HTML and CSS</li><li>Arabic and English</li></ul>
    </section>
  </main>
</body>
</html>
```

Project 548: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.cv { max-width: 46rem; margin: 2rem auto; padding: 0 1rem; }
header { border-bottom: 3px solid var(--brand); padding-bottom: 1rem;
margin-bottom: 1.5rem; }
h1 { margin: 0; }
.role { margin: .2rem 0; color: var(--muted); }
h2 { color: var(--brand); text-transform: uppercase; font-size: 1rem;
letter-spacing: .08em; margin-top: 1.5rem; }
h3 { margin: 1rem 0 0; }
.when { margin: 0; color: var(--muted); font-size: .9rem; }
.skills { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .5rem; }
.skills li { background: var(--accent); padding: .3rem .8rem; border-
radius: 999px; }
@media print { a { color: inherit; text-decoration: none; } .cv { max-
width: none; } }
```

Project 548 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fatma Hassan - CV</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="cv">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Fatma Hassan	The main heading; only one per page.
Founder, Nubian Guest House · Aswan	A paragraph of text.
Email ...	A hyperlink; href gives the destination.
<section>	A thematic group of content, normally with its own heading.
Experience	Second-level heading for a section.
<article>	A self-contained piece: card, post, product.

Line	What it does
Founder, Nubian Guest House	Third-level heading, inside an h2 section.
<time date time="2018">2018</time> - present	A date or time; datetime holds the machine-readable value.
Grew the business to 4 core rooms. Built a loyal cu...	Unordered (bulleted) list.
Managed a team of six.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
font-size: 1rem;	Size of the text.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
@media print { a { color: inherit; text-decoration: none; } .cv { m...	Removes the underline from links.

Check your work

- Contact links work (mailto, tel)
- Jobs in reverse chronological order
- Skills wrap
- Prints on one page without colours

Exercises

1. Add a two-column layout for print with CSS columns.
2. Add an Education section.
3. Add a downloadable PDF link.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 549: CV / resume page for Bassem Adly

Theme: Ismailia Cycling Store (Ismailia) | Level 2 | Files: index.html, styles.css

Brief

Lay out a one-page CV with header, experience entries using article and time, and a skills list as pills, with a print stylesheet.

Learning goals

- Structure a CV semantically
- Style skill tags with Flexbox wrapping
- Add @media print rules

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, section, article, h3, time, ul, li	border-bottom, text-transform, letter-spacing, flex-wrap, @media print

Build guide

1. Write the header with name, role and contact links.
2. Add an Experience section with one article per job.
3. Use <time> for the years.
4. Add a Skills list.
5. Style section headings small and uppercase.
6. Print preview (Ctrl+P) and adjust the print rules.

Project 549: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Bassem Adly - CV</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="cv">
    <header>
      <h1>Bassem Adly</h1>
      <p class="role">Founder, Ismailia Cycling Store &middot;
Ismailia</p>
      <p class="links"><a href="mailto:cycling@example.com">Email</a>
&middot; <a href="tel:+20100000000">Phone</a> &middot; <a href="https:
//example.com">Website</a></p>
    </header>
    <section>
      <h2>Experience</h2>
      <article>
        <h3>Founder, Ismailia Cycling Store</h3>
        <p class="when"><time datetime="2018">2018</time> - present</
p>
        <ul><li>Grew the business to 4 core bikes.</li><li>Built a
loyal customer base in Ismailia.</li></ul>
      </article>
      <article>
        <h3>Assistant manager, Local Company</h3>
        <p class="when"><time datetime="2014">2014</time> - <time
datetime="2018">2018</time></p>
        <ul><li>Managed a team of six.</li></ul>
      </article>
    </section>
    <section>
      <h2>Skills</h2>
      <ul class="skills"><li>Customer service</li><li>Planning</
li><li>HTML and CSS</li><li>Arabic and English</li></ul>
    </section>
  </main>
</body>
</html>
```

Project 549: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
```

```
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.cv { max-width: 46rem; margin: 2rem auto; padding: 0 1rem; }
header { border-bottom: 3px solid var(--brand); padding-bottom: 1rem;
margin-bottom: 1.5rem; }
h1 { margin: 0; }
.role { margin: .2rem 0; color: var(--muted); }
h2 { color: var(--brand); text-transform: uppercase; font-size: 1rem;
letter-spacing: .08em; margin-top: 1.5rem; }
h3 { margin: 1rem 0 0; }
.when { margin: 0; color: var(--muted); font-size: .9rem; }
.skills { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .5rem; }
.skills li { background: var(--accent); padding: .3rem .8rem; border-
radius: 999px; }
@media print { a { color: inherit; text-decoration: none; } .cv { max-
width: none; } }
```

Project 549 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Bassem Adly - CV</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="cv">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Bassem Adly	The main heading; only one per page.
Founder, Ismailia Cycling Store · Ismailia	A paragraph of text.
Email &mi...	A hyperlink; href gives the destination.
<section>	A thematic group of content, normally with its own heading.
Experience	Second-level heading for a section.
<article>	A self-contained piece: card, post, product.

Line	What it does
Founder, Ismailia Cycling Store	Third-level heading, inside an h2 section.
<time date time="2018">2018</time> - present	A date or time; datetime holds the machine-readable value.
Grew the business to 4 core bikes. Built a loyal cu...	Unordered (bulleted) list.
Managed a team of six.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
font-size: 1rem;	Size of the text.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
@media print { a { color: inherit; text-decoration: none; } .cv { m...	Removes the underline from links.

Check your work

- Contact links work (mailto, tel)
- Jobs in reverse chronological order
- Skills wrap
- Prints on one page without colours

Exercises

1. Add a two-column layout for print with CSS columns.
2. Add an Education section.
3. Add a downloadable PDF link.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 550: CV / resume page for Youssef Hany

Theme: Minya Coding Club (Minya) | Level 2 | Files: index.html, styles.css

Brief

Lay out a one-page CV with header, experience entries using article and time, and a skills list as pills, with a print stylesheet.

Learning goals

- Structure a CV semantically
- Style skill tags with Flexbox wrapping
- Add @media print rules

Elements and CSS used

HTML elements	CSS features
header, h1, p, a, section, article, h3, time, ul, li	border-bottom, text-transform, letter-spacing, flex-wrap, @media print

Build guide

1. Write the header with name, role and contact links.
2. Add an Experience section with one article per job.
3. Use <time> for the years.
4. Add a Skills list.
5. Style section headings small and uppercase.
6. Print preview (Ctrl+P) and adjust the print rules.

Project 550: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Youssef Hany - CV</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="cv">
    <header>
      <h1>Youssef Hany</h1>
      <p class="role">Founder, Minya Coding Club &middot; Minya</p>
      <p class="links"><a href="mailto:coding@example.com">Email</a>
&middot; <a href="tel:+20100000000">Phone</a> &middot; <a href="https:
//example.com">Website</a></p>
    </header>
    <section>
      <h2>Experience</h2>
      <article>
        <h3>Founder, Minya Coding Club</h3>
        <p class="when"><time datetime="2018">2018</time> - present</
p>
        <ul><li>Grew the business to 4 core workshops.</li><li>Built
a loyal customer base in Minya.</li></ul>
      </article>
      <article>
        <h3>Assistant manager, Local Company</h3>
        <p class="when"><time datetime="2014">2014</time> - <time
datetime="2018">2018</time></p>
        <ul><li>Managed a team of six.</li></ul>
      </article>
    </section>
    <section>
      <h2>Skills</h2>
      <ul class="skills"><li>Customer service</li><li>Planning</
li><li>HTML and CSS</li><li>Arabic and English</li></ul>
    </section>
  </main>
</body>
</html>
```

Project 550: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
```

```
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.cv { max-width: 46rem; margin: 2rem auto; padding: 0 1rem; }
header { border-bottom: 3px solid var(--brand); padding-bottom: 1rem;
margin-bottom: 1.5rem; }
h1 { margin: 0; }
.role { margin: .2rem 0; color: var(--muted); }
h2 { color: var(--brand); text-transform: uppercase; font-size: 1rem;
letter-spacing: .08em; margin-top: 1.5rem; }
h3 { margin: 1rem 0 0; }
.when { margin: 0; color: var(--muted); font-size: .9rem; }
.skills { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .5rem; }
.skills li { background: var(--accent); padding: .3rem .8rem; border-
radius: 999px; }
@media print { a { color: inherit; text-decoration: none; } .cv { max-
width: none; } }
```

Project 550 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Youssef Hany - CV</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="cv">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Youssef Hany	The main heading; only one per page.
Founder, Minya Coding Club · Minya	A paragraph of text.
Email &mid...	A hyperlink; href gives the destination.
<section>	A thematic group of content, normally with its own heading.
Experience	Second-level heading for a section.
<article>	A self-contained piece: card, post, product.

Line	What it does
Founder, Minya Coding Club	Third-level heading, inside an h2 section.
<time date time="2018">2018</time> - present	A date or time; datetime holds the machine-readable value.
Grew the business to 4 core workshops. Built a loya...	Unordered (bulleted) list.
Managed a team of six.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
font-size: 1rem;	Size of the text.
letter-spacing: .08em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
@media print { a { color: inherit; text-decoration: none; } .cv { m...	Removes the underline from links.

Check your work

- Contact links work (mailto, tel)
- Jobs in reverse chronological order
- Skills wrap
- Prints on one page without colours

Exercises

1. Add a two-column layout for print with CSS columns.
2. Add an Education section.
3. Add a downloadable PDF link.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Event page

Level 1 | 25 projects, one per theme

Announce an event with a machine-readable date, key facts in a two-column description list, a numbered programme and a register button.

Project 551: Event page for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 1 | Files: index.html, styles.css

Brief

Announce an event with a machine-readable date, key facts in a two-column description list, a numbered programme and a register button.

Learning goals

- Use <time> with a full datetime
- Lay out dl as a two-column grid
- Use ol for a sequence

Elements and CSS used

HTML elements	CSS features
article, time, h1, p, dl, dt, dd, h2, ol, li, b, a	grid-template-columns: max-content 1fr, gap (two values), border-radius, padding-left

Build guide

1. Write the date first with <time datetime="2026-10-15T18:00">.
2. Add heading and lead.
3. Add the facts list and programme.
4. Grid the dl: dt in the first column, dd in the second.
5. Style the button.
6. Validate the datetime format.

Project 551: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop open day</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="event">
      <p class="date"><time datetime="2026-10-15T18:00">Thursday 15
October 2026, 18:00</time></p>
      <h1>Cairo Book Shop open day</h1>
      <p class="lead">Come and try our books for free, meet Mohamed
Khattab and enjoy live music.</p>
      <dl class="facts">
        <dt>Where</dt><dd>Cairo Book Shop, Giza</dd>
        <dt>Price</dt><dd>Free, registration required</dd>
        <dt>Duration</dt><dd>3 hours</dd>
      </dl>
      <h2>Programme</h2>
      <ol>
        <li><b>18:00</b> Doors open</li>
        <li><b>18:30</b> Welcome talk</li>
        <li><b>19:00</b> Try the books</li>
        <li><b>20:30</b> Prize draw</li>
      </ol>
      <a class="btn" href="register.html">Register now</a>
    </article>
  </main>
</body>
</html>
```

Project 551: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.date { color: var(--brand); font-weight: 700; margin: 0; }
h1 { margin: .2rem 0; }
.lead { font-size: 1.2rem; }
.facts { display: grid; grid-template-columns: max-content 1fr; gap: .
4rem 1.5rem; background: var(--accent); padding: 1rem 1.25rem; border-
```

```
radius: 10px; }
dt { font-weight: 700; }
dd { margin: 0; }
ol { padding-left: 1.2rem; }
ol li { margin-bottom: .4rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 551 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop open day</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="event">	A self-contained piece: card, post, product.
<p class="date"><time datetime="2026-10-15T18:00">Thursday 15 Octob...	A paragraph of text.
Cairo Book Shop open day	The main heading; only one per page.
<dl class="facts">	Description list of term / description pairs.
<dt>Where</dt><dd>Cairo Book Shop, Giza</dd>	A term (name) in a description list.
<dt>Price</dt><dd>Free, registration required</dd>	The description of the preceding term.
Programme	Second-level heading for a section.

Line	What it does
	Ordered (numbered) list; the order matters.
18:00 Doors open	One list item.
18:30 Welcome talk	Keyword or name drawn to attention without extra importance.
Register now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
font-weight: 700;	Thickness of the text.
font-size: 1.2rem;	Size of the text.
display: grid;	Turns the element into a grid container.
grid-template-columns: max-content 1fr;	Defines the columns of the grid.
gap: .4rem 1.5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 10px;	Rounds the corners.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- datetime is ISO format
- dt/dd pairs align
- Programme is an ordered list
- Button text is an action

Exercises

1. Add an 'Add to calendar' .ics link.
2. Add a map with an iframe.
3. Add a countdown with JavaScript.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 552: Event page for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 1 | Files: index.html, styles.css

Brief

Announce an event with a machine-readable date, key facts in a two-column description list, a numbered programme and a register button.

Learning goals

- Use <time> with a full datetime
- Lay out dl as a two-column grid
- Use ol for a sequence

Elements and CSS used

HTML elements	CSS features
article, time, h1, p, dl, dt, dd, h2, ol, li, b, a	grid-template-columns: max-content 1fr, gap (two values), border-radius, padding-left

Build guide

1. Write the date first with <time datetime="2026-10-15T18:00">.
2. Add heading and lead.
3. Add the facts list and programme.
4. Grid the dl: dt in the first column, dd in the second.
5. Style the button.
6. Validate the datetime format.

Project 552: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery open day</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="event">
      <p class="date"><time datetime="2026-10-15T18:00">Thursday 15
October 2026, 18:00</time></p>
      <h1>Nile Bakery open day</h1>
      <p class="lead">Come and try our pastries for free, meet Sara
Adel and enjoy live music.</p>
      <dl class="facts">
        <dt>Where</dt><dd>Nile Bakery, Cairo</dd>
        <dt>Price</dt><dd>Free, registration required</dd>
        <dt>Duration</dt><dd>3 hours</dd>
      </dl>
      <h2>Programme</h2>
      <ol>
        <li><b>18:00</b> Doors open</li>
        <li><b>18:30</b> Welcome talk</li>
        <li><b>19:00</b> Try the pastries</li>
        <li><b>20:30</b> Prize draw</li>
      </ol>
      <a class="btn" href="register.html">Register now</a>
    </article>
  </main>
</body>
</html>
```

Project 552: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.date { color: var(--brand); font-weight: 700; margin: 0; }
h1 { margin: .2rem 0; }
.lead { font-size: 1.2rem; }
.facts { display: grid; grid-template-columns: max-content 1fr; gap: .
4rem 1.5rem; background: var(--accent); padding: 1rem 1.25rem; border-
```

```
radius: 10px; }
dt { font-weight: 700; }
dd { margin: 0; }
ol { padding-left: 1.2rem; }
ol li { margin-bottom: .4rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 552 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery open day</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="event">	A self-contained piece: card, post, product.
<p class="date"><time datetime="2026-10-15T18:00">Thursday 15 Octob...	A paragraph of text.
Nile Bakery open day	The main heading; only one per page.
<dl class="facts">	Description list of term / description pairs.
<dt>Where</dt><dd>Nile Bakery, Cairo</dd>	A term (name) in a description list.
<dt>Price</dt><dd>Free, registration required</dd>	The description of the preceding term.
Programme	Second-level heading for a section.

Line	What it does
	Ordered (numbered) list; the order matters.
18:00 Doors open	One list item.
18:30 Welcome talk	Keyword or name drawn to attention without extra importance.
Register now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
font-weight: 700;	Thickness of the text.
font-size: 1.2rem;	Size of the text.
display: grid;	Turns the element into a grid container.
grid-template-columns: max-content 1fr;	Defines the columns of the grid.
gap: .4rem 1.5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 10px;	Rounds the corners.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- datetime is ISO format
- dt/dd pairs align
- Programme is an ordered list
- Button text is an action

Exercises

1. Add an 'Add to calendar' .ics link.
2. Add a map with an iframe.
3. Add a countdown with JavaScript.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 553: Event page for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 1 | Files: index.html, styles.css

Brief

Announce an event with a machine-readable date, key facts in a two-column description list, a numbered programme and a register button.

Learning goals

- Use <time> with a full datetime
- Lay out dl as a two-column grid
- Use ol for a sequence

Elements and CSS used

HTML elements	CSS features
article, time, h1, p, dl, dt, dd, h2, ol, li, b, a	grid-template-columns: max-content 1fr, gap (two values), border-radius, padding-left

Build guide

1. Write the date first with <time datetime="2026-10-15T18:00">.
2. Add heading and lead.
3. Add the facts list and programme.
4. Grid the dl: dt in the first column, dd in the second.
5. Style the button.
6. Validate the datetime format.

Project 553: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness open day</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="event">
      <p class="date"><time datetime="2026-10-15T18:00">Thursday 15
October 2026, 18:00</time></p>
      <h1>Pyramid Fitness open day</h1>
      <p class="lead">Come and try our classes for free, meet Omar
Farouk and enjoy live music.</p>
      <dl class="facts">
        <dt>Where</dt><dd>Pyramid Fitness, 6th of October</dd>
        <dt>Price</dt><dd>Free, registration required</dd>
        <dt>Duration</dt><dd>3 hours</dd>
      </dl>
      <h2>Programme</h2>
      <ol>
        <li><b>18:00</b> Doors open</li>
        <li><b>18:30</b> Welcome talk</li>
        <li><b>19:00</b> Try the classes</li>
        <li><b>20:30</b> Prize draw</li>
      </ol>
      <a class="btn" href="register.html">Register now</a>
    </article>
  </main>
</body>
</html>
```

Project 553: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.date { color: var(--brand); font-weight: 700; margin: 0; }
h1 { margin: .2rem 0; }
.lead { font-size: 1.2rem; }
.facts { display: grid; grid-template-columns: max-content 1fr; gap: .
4rem 1.5rem; background: var(--accent); padding: 1rem 1.25rem; border-
```

```
radius: 10px; }
dt { font-weight: 700; }
dd { margin: 0; }
ol { padding-left: 1.2rem; }
ol li { margin-bottom: .4rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 553 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness open day</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="event">	A self-contained piece: card, post, product.
<p class="date"><time datetime="2026-10-15T18:00">Thursday 15 Octob...	A paragraph of text.
Pyramid Fitness open day	The main heading; only one per page.
<dl class="facts">	Description list of term / description pairs.
<dt>Where</dt><dd>Pyramid Fitness, 6th of October</dd>	A term (name) in a description list.
<dt>Price</dt><dd>Free, registration required</dd>	The description of the preceding term.
Programme	Second-level heading for a section.

Line	What it does
	Ordered (numbered) list; the order matters.
18:00 Doors open	One list item.
18:30 Welcome talk	Keyword or name drawn to attention without extra importance.
Register now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
font-weight: 700;	Thickness of the text.
font-size: 1.2rem;	Size of the text.
display: grid;	Turns the element into a grid container.
grid-template-columns: max-content 1fr;	Defines the columns of the grid.
gap: .4rem 1.5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 10px;	Rounds the corners.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- datetime is ISO format
- dt/dd pairs align
- Programme is an ordered list
- Button text is an action

Exercises

1. Add an 'Add to calendar' .ics link.
2. Add a map with an iframe.
3. Add a countdown with JavaScript.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 554: Event page for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 1 | Files: index.html, styles.css

Brief

Announce an event with a machine-readable date, key facts in a two-column description list, a numbered programme and a register button.

Learning goals

- Use <time> with a full datetime
- Lay out dl as a two-column grid
- Use ol for a sequence

Elements and CSS used

HTML elements	CSS features
article, time, h1, p, dl, dt, dd, h2, ol, li, b, a	grid-template-columns: max-content 1fr, gap (two values), border-radius, padding-left

Build guide

1. Write the date first with <time datetime="2026-10-15T18:00">.
2. Add heading and lead.
3. Add the facts list and programme.
4. Grid the dl: dt in the first column, dd in the second.
5. Style the button.
6. Validate the datetime format.

Project 554: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic open day</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="event">
      <p class="date"><time datetime="2026-10-15T18:00">Thursday 15
October 2026, 18:00</time></p>
      <h1>Delta Dental Clinic open day</h1>
      <p class="lead">Come and try our services for free, meet Dr.
Hana Youssef and enjoy live music.</p>
      <dl class="facts">
        <dt>Where</dt><dd>Delta Dental Clinic, Mansoura</dd>
        <dt>Price</dt><dd>Free, registration required</dd>
        <dt>Duration</dt><dd>3 hours</dd>
      </dl>
      <h2>Programme</h2>
      <ol>
        <li><b>18:00</b> Doors open</li>
        <li><b>18:30</b> Welcome talk</li>
        <li><b>19:00</b> Try the services</li>
        <li><b>20:30</b> Prize draw</li>
      </ol>
      <a class="btn" href="register.html">Register now</a>
    </article>
  </main>
</body>
</html>
```

Project 554: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.date { color: var(--brand); font-weight: 700; margin: 0; }
h1 { margin: .2rem 0; }
.lead { font-size: 1.2rem; }
.facts { display: grid; grid-template-columns: max-content 1fr; gap: .
4rem 1.5rem; background: var(--accent); padding: 1rem 1.25rem; border-
```

```
radius: 10px; }
dt { font-weight: 700; }
dd { margin: 0; }
ol { padding-left: 1.2rem; }
ol li { margin-bottom: .4rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 554 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic open day</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="event">	A self-contained piece: card, post, product.
<p class="date"><time datetime="2026-10-15T18:00">Thursday 15 Octob...	A paragraph of text.
Delta Dental Clinic open day	The main heading; only one per page.
<dl class="facts">	Description list of term / description pairs.
<dt>Where</dt><dd>Delta Dental Clinic, Mansoura</dd>	A term (name) in a description list.
<dt>Price</dt><dd>Free, registration required</dd>	The description of the preceding term.
Programme	Second-level heading for a section.

Line	What it does
	Ordered (numbered) list; the order matters.
18:00 Doors open	One list item.
18:30 Welcome talk	Keyword or name drawn to attention without extra importance.
Register now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
font-weight: 700;	Thickness of the text.
font-size: 1.2rem;	Size of the text.
display: grid;	Turns the element into a grid container.
grid-template-columns: max-content 1fr;	Defines the columns of the grid.
gap: .4rem 1.5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 10px;	Rounds the corners.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- datetime is ISO format
- dt/dd pairs align
- Programme is an ordered list
- Button text is an action

Exercises

1. Add an 'Add to calendar' .ics link.
2. Add a map with an iframe.
3. Add a countdown with JavaScript.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 555: Event page for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 1 | Files: index.html, styles.css

Brief

Announce an event with a machine-readable date, key facts in a two-column description list, a numbered programme and a register button.

Learning goals

- Use <time> with a full datetime
- Lay out dl as a two-column grid
- Use ol for a sequence

Elements and CSS used

HTML elements	CSS features
article, time, h1, p, dl, dt, dd, h2, ol, li, b, a	grid-template-columns: max-content 1fr, gap (two values), border-radius, padding-left

Build guide

1. Write the date first with <time datetime="2026-10-15T18:00">.
2. Add heading and lead.
3. Add the facts list and programme.
4. Grid the dl: dt in the first column, dd in the second.
5. Style the button.
6. Validate the datetime format.

Project 555: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel open day</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="event">
      <p class="date"><time datetime="2026-10-15T18:00">Thursday 15
October 2026, 18:00</time></p>
      <h1>Red Sea Travel open day</h1>
      <p class="lead">Come and try our tours for free, meet Laila
Mansour and enjoy live music.</p>
      <dl class="facts">
        <dt>Where</dt><dd>Red Sea Travel, Hurghada</dd>
        <dt>Price</dt><dd>Free, registration required</dd>
        <dt>Duration</dt><dd>3 hours</dd>
      </dl>
      <h2>Programme</h2>
      <ol>
        <li><b>18:00</b> Doors open</li>
        <li><b>18:30</b> Welcome talk</li>
        <li><b>19:00</b> Try the tours</li>
        <li><b>20:30</b> Prize draw</li>
      </ol>
      <a class="btn" href="register.html">Register now</a>
    </article>
  </main>
</body>
</html>
```

Project 555: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.date { color: var(--brand); font-weight: 700; margin: 0; }
h1 { margin: .2rem 0; }
.lead { font-size: 1.2rem; }
.facts { display: grid; grid-template-columns: max-content 1fr; gap: .
4rem 1.5rem; background: var(--accent); padding: 1rem 1.25rem; border-
```

```
radius: 10px; }
dt { font-weight: 700; }
dd { margin: 0; }
ol { padding-left: 1.2rem; }
ol li { margin-bottom: .4rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 555 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel open day</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="event">	A self-contained piece: card, post, product.
<p class="date"><time datetime="2026-10-15T18:00">Thursday 15 Octob...	A paragraph of text.
Red Sea Travel open day	The main heading; only one per page.
<dl class="facts">	Description list of term / description pairs.
<dt>Where</dt><dd>Red Sea Travel, Hurghada</dd>	A term (name) in a description list.
<dt>Price</dt><dd>Free, registration required</dd>	The description of the preceding term.
Programme	Second-level heading for a section.

Line	What it does
	Ordered (numbered) list; the order matters.
18:00 Doors open	One list item.
18:30 Welcome talk	Keyword or name drawn to attention without extra importance.
Register now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
font-weight: 700;	Thickness of the text.
font-size: 1.2rem;	Size of the text.
display: grid;	Turns the element into a grid container.
grid-template-columns: max-content 1fr;	Defines the columns of the grid.
gap: .4rem 1.5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 10px;	Rounds the corners.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- datetime is ISO format
- dt/dd pairs align
- Programme is an ordered list
- Button text is an action

Exercises

1. Add an 'Add to calendar' .ics link.
2. Add a map with an iframe.
3. Add a countdown with JavaScript.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 556: Event page for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Announce an event with a machine-readable date, key facts in a two-column description list, a numbered programme and a register button.

Learning goals

- Use <time> with a full datetime
- Lay out dl as a two-column grid
- Use ol for a sequence

Elements and CSS used

HTML elements	CSS features
article, time, h1, p, dl, dt, dd, h2, ol, li, b, a	grid-template-columns: max-content 1fr, gap (two values), border-radius, padding-left

Build guide

1. Write the date first with <time datetime="2026-10-15T18:00">.
2. Add heading and lead.
3. Add the facts list and programme.
4. Grid the dl: dt in the first column, dd in the second.
5. Style the button.
6. Validate the datetime format.

Project 556: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School open day</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="event">
      <p class="date"><time datetime="2026-10-15T18:00">Thursday 15
October 2026, 18:00</time></p>
      <h1>Lotus Language School open day</h1>
      <p class="lead">Come and try our courses for free, meet Nour El
Din and enjoy live music.</p>
      <dl class="facts">
        <dt>Where</dt><dd>Lotus Language School, Alexandria</dd>
        <dt>Price</dt><dd>Free, registration required</dd>
        <dt>Duration</dt><dd>3 hours</dd>
      </dl>
      <h2>Programme</h2>
      <ol>
        <li><b>18:00</b> Doors open</li>
        <li><b>18:30</b> Welcome talk</li>
        <li><b>19:00</b> Try the courses</li>
        <li><b>20:30</b> Prize draw</li>
      </ol>
      <a class="btn" href="register.html">Register now</a>
    </article>
  </main>
</body>
</html>
```

Project 556: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.date { color: var(--brand); font-weight: 700; margin: 0; }
h1 { margin: .2rem 0; }
.lead { font-size: 1.2rem; }
.facts { display: grid; grid-template-columns: max-content 1fr; gap: .
4rem 1.5rem; background: var(--accent); padding: 1rem 1.25rem; border-
```

```
radius: 10px; }
dt { font-weight: 700; }
dd { margin: 0; }
ol { padding-left: 1.2rem; }
ol li { margin-bottom: .4rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 556 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School open day</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="event">	A self-contained piece: card, post, product.
<p class="date"><time datetime="2026-10-15T18:00">Thursday 15 Octob...	A paragraph of text.
Lotus Language School open day	The main heading; only one per page.
<dl class="facts">	Description list of term / description pairs.
<dt>Where</dt><dd>Lotus Language School, Alexandria</dd>	A term (name) in a description list.
<dt>Price</dt><dd>Free, registration required</dd>	The description of the preceding term.
Programme	Second-level heading for a section.

Line	What it does
	Ordered (numbered) list; the order matters.
18:00 Doors open	One list item.
18:30 Welcome talk	Keyword or name drawn to attention without extra importance.
Register now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
font-weight: 700;	Thickness of the text.
font-size: 1.2rem;	Size of the text.
display: grid;	Turns the element into a grid container.
grid-template-columns: max-content 1fr;	Defines the columns of the grid.
gap: .4rem 1.5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 10px;	Rounds the corners.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- datetime is ISO format
- dt/dd pairs align
- Programme is an ordered list
- Button text is an action

Exercises

1. Add an 'Add to calendar' .ics link.
2. Add a map with an iframe.
3. Add a countdown with JavaScript.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 557: Event page for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 1 | Files: index.html, styles.css

Brief

Announce an event with a machine-readable date, key facts in a two-column description list, a numbered programme and a register button.

Learning goals

- Use <time> with a full datetime
- Lay out dl as a two-column grid
- Use ol for a sequence

Elements and CSS used

HTML elements	CSS features
article, time, h1, p, dl, dt, dd, h2, ol, li, b, a	grid-template-columns: max-content 1fr, gap (two values), border-radius, padding-left

Build guide

1. Write the date first with <time datetime="2026-10-15T18:00">.
2. Add heading and lead.
3. Add the facts list and programme.
4. Grid the dl: dt in the first column, dd in the second.
5. Style the button.
6. Validate the datetime format.

Project 557: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe open day</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="event">
      <p class="date"><time datetime="2026-10-15T18:00">Thursday 15
October 2026, 18:00</time></p>
      <h1>Green Leaf Cafe open day</h1>
      <p class="lead">Come and try our drinks for free, meet Karim
Said and enjoy live music.</p>
      <dl class="facts">
        <dt>Where</dt><dd>Green Leaf Cafe, Zamalek</dd>
        <dt>Price</dt><dd>Free, registration required</dd>
        <dt>Duration</dt><dd>3 hours</dd>
      </dl>
      <h2>Programme</h2>
      <ol>
        <li><b>18:00</b> Doors open</li>
        <li><b>18:30</b> Welcome talk</li>
        <li><b>19:00</b> Try the drinks</li>
        <li><b>20:30</b> Prize draw</li>
      </ol>
      <a class="btn" href="register.html">Register now</a>
    </article>
  </main>
</body>
</html>
```

Project 557: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.date { color: var(--brand); font-weight: 700; margin: 0; }
h1 { margin: .2rem 0; }
.lead { font-size: 1.2rem; }
.facts { display: grid; grid-template-columns: max-content 1fr; gap: .
4rem 1.5rem; background: var(--accent); padding: 1rem 1.25rem; border-
```

```
radius: 10px; }
dt { font-weight: 700; }
dd { margin: 0; }
ol { padding-left: 1.2rem; }
ol li { margin-bottom: .4rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 557 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe open day</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="event">	A self-contained piece: card, post, product.
<p class="date"><time datetime="2026-10-15T18:00">Thursday 15 Octob...	A paragraph of text.
Green Leaf Cafe open day	The main heading; only one per page.
<dl class="facts">	Description list of term / description pairs.
<dt>Where</dt><dd>Green Leaf Cafe, Zamalek</dd>	A term (name) in a description list.
<dt>Price</dt><dd>Free, registration required</dd>	The description of the preceding term.
Programme	Second-level heading for a section.

Line	What it does
	Ordered (numbered) list; the order matters.
18:00 Doors open	One list item.
18:30 Welcome talk	Keyword or name drawn to attention without extra importance.
Register now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
font-weight: 700;	Thickness of the text.
font-size: 1.2rem;	Size of the text.
display: grid;	Turns the element into a grid container.
grid-template-columns: max-content 1fr;	Defines the columns of the grid.
gap: .4rem 1.5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 10px;	Rounds the corners.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- datetime is ISO format
- dt/dd pairs align
- Programme is an ordered list
- Button text is an action

Exercises

1. Add an 'Add to calendar' .ics link.
2. Add a map with an iframe.
3. Add a countdown with JavaScript.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 558: Event page for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 1 | Files: index.html, styles.css

Brief

Announce an event with a machine-readable date, key facts in a two-column description list, a numbered programme and a register button.

Learning goals

- Use <time> with a full datetime
- Lay out dl as a two-column grid
- Use ol for a sequence

Elements and CSS used

HTML elements	CSS features
article, time, h1, p, dl, dt, dd, h2, ol, li, b, a	grid-template-columns: max-content 1fr, gap (two values), border-radius, padding-left

Build guide

1. Write the date first with <time datetime="2026-10-15T18:00">.
2. Add heading and lead.
3. Add the facts list and programme.
4. Grid the dl: dt in the first column, dd in the second.
5. Style the button.
6. Validate the datetime format.

Project 558: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club open day</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="event">
      <p class="date"><time datetime="2026-10-15T18:00">Thursday 15
October 2026, 18:00</time></p>
      <h1>Sinai Trekking Club open day</h1>
      <p class="lead">Come and try our hikes for free, meet Yara
Hamdy and enjoy live music.</p>
      <dl class="facts">
        <dt>Where</dt><dd>Sinai Trekking Club, Saint Catherine</dd>
        <dt>Price</dt><dd>Free, registration required</dd>
        <dt>Duration</dt><dd>3 hours</dd>
      </dl>
      <h2>Programme</h2>
      <ol>
        <li><b>18:00</b> Doors open</li>
        <li><b>18:30</b> Welcome talk</li>
        <li><b>19:00</b> Try the hikes</li>
        <li><b>20:30</b> Prize draw</li>
      </ol>
      <a class="btn" href="register.html">Register now</a>
    </article>
  </main>
</body>
</html>
```

Project 558: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.date { color: var(--brand); font-weight: 700; margin: 0; }
h1 { margin: .2rem 0; }
.lead { font-size: 1.2rem; }
.facts { display: grid; grid-template-columns: max-content 1fr; gap: .
4rem 1.5rem; background: var(--accent); padding: 1rem 1.25rem; border-
```

```
radius: 10px; }
dt { font-weight: 700; }
dd { margin: 0; }
ol { padding-left: 1.2rem; }
ol li { margin-bottom: .4rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 558 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club open day</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="event">	A self-contained piece: card, post, product.
<p class="date"><time datetime="2026-10-15T18:00">Thursday 15 Octob...	A paragraph of text.
Sinai Trekking Club open day	The main heading; only one per page.
<dl class="facts">	Description list of term / description pairs.
<dt>Where</dt><dd>Sinai Trekking Club, Saint Catherine</dd>	A term (name) in a description list.
<dt>Price</dt><dd>Free, registration required</dd>	The description of the preceding term.
Programme	Second-level heading for a section.

Line	What it does
	Ordered (numbered) list; the order matters.
18:00 Doors open	One list item.
18:30 Welcome talk	Keyword or name drawn to attention without extra importance.
Register now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
font-weight: 700;	Thickness of the text.
font-size: 1.2rem;	Size of the text.
display: grid;	Turns the element into a grid container.
grid-template-columns: max-content 1fr;	Defines the columns of the grid.
gap: .4rem 1.5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 10px;	Rounds the corners.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- datetime is ISO format
- dt/dd pairs align
- Programme is an ordered list
- Button text is an action

Exercises

1. Add an 'Add to calendar' .ics link.
2. Add a map with an iframe.
3. Add a countdown with JavaScript.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 559: Event page for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 1 | Files: index.html, styles.css

Brief

Announce an event with a machine-readable date, key facts in a two-column description list, a numbered programme and a register button.

Learning goals

- Use <time> with a full datetime
- Lay out dl as a two-column grid
- Use ol for a sequence

Elements and CSS used

HTML elements	CSS features
article, time, h1, p, dl, dt, dd, h2, ol, li, b, a	grid-template-columns: max-content 1fr, gap (two values), border-radius, padding-left

Build guide

1. Write the date first with <time datetime="2026-10-15T18:00">.
2. Add heading and lead.
3. Add the facts list and programme.
4. Grid the dl: dt in the first column, dd in the second.
5. Style the button.
6. Validate the datetime format.

Project 559: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography open day</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="event">
      <p class="date"><time datetime="2026-10-15T18:00">Thursday 15
October 2026, 18:00</time></p>
      <h1>Horizon Photography open day</h1>
      <p class="lead">Come and try our sessions for free, meet Adham
Nabil and enjoy live music.</p>
      <dl class="facts">
        <dt>Where</dt><dd>Horizon Photography, Maadi</dd>
        <dt>Price</dt><dd>Free, registration required</dd>
        <dt>Duration</dt><dd>3 hours</dd>
      </dl>
      <h2>Programme</h2>
      <ol>
        <li><b>18:00</b> Doors open</li>
        <li><b>18:30</b> Welcome talk</li>
        <li><b>19:00</b> Try the sessions</li>
        <li><b>20:30</b> Prize draw</li>
      </ol>
      <a class="btn" href="register.html">Register now</a>
    </article>
  </main>
</body>
</html>
```

Project 559: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.date { color: var(--brand); font-weight: 700; margin: 0; }
h1 { margin: .2rem 0; }
.lead { font-size: 1.2rem; }
.facts { display: grid; grid-template-columns: max-content 1fr; gap: .
4rem 1.5rem; background: var(--accent); padding: 1rem 1.25rem; border-
```

```
radius: 10px; }
dt { font-weight: 700; }
dd { margin: 0; }
ol { padding-left: 1.2rem; }
ol li { margin-bottom: .4rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 559 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography open day</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="event">	A self-contained piece: card, post, product.
<p class="date"><time datetime="2026-10-15T18:00">Thursday 15 Octob...	A paragraph of text.
Horizon Photography open day	The main heading; only one per page.
<dl class="facts">	Description list of term / description pairs.
<dt>Where</dt><dd>Horizon Photography, Maadi</dd>	A term (name) in a description list.
<dt>Price</dt><dd>Free, registration required</dd>	The description of the preceding term.
Programme	Second-level heading for a section.

Line	What it does
	Ordered (numbered) list; the order matters.
18:00 Doors open	One list item.
18:30 Welcome talk	Keyword or name drawn to attention without extra importance.
Register now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
font-weight: 700;	Thickness of the text.
font-size: 1.2rem;	Size of the text.
display: grid;	Turns the element into a grid container.
grid-template-columns: max-content 1fr;	Defines the columns of the grid.
gap: .4rem 1.5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 10px;	Rounds the corners.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- datetime is ISO format
- dt/dd pairs align
- Programme is an ordered list
- Button text is an action

Exercises

1. Add an 'Add to calendar' .ics link.
2. Add a map with an iframe.
3. Add a countdown with JavaScript.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 560: Event page for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 1 | Files: index.html, styles.css

Brief

Announce an event with a machine-readable date, key facts in a two-column description list, a numbered programme and a register button.

Learning goals

- Use <time> with a full datetime
- Lay out dl as a two-column grid
- Use ol for a sequence

Elements and CSS used

HTML elements	CSS features
article, time, h1, p, dl, dt, dd, h2, ol, li, b, a	grid-template-columns: max-content 1fr, gap (two values), border-radius, padding-left

Build guide

1. Write the date first with <time datetime="2026-10-15T18:00">.
2. Add heading and lead.
3. Add the facts list and programme.
4. Grid the dl: dt in the first column, dd in the second.
5. Style the button.
6. Validate the datetime format.

Project 560: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery open day</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="event">
      <p class="date"><time datetime="2026-10-15T18:00">Thursday 15
October 2026, 18:00</time></p>
      <h1>Papyrus Stationery open day</h1>
      <p class="lead">Come and try our products for free, meet Dina
Fathy and enjoy live music.</p>
      <dl class="facts">
        <dt>Where</dt><dd>Papyrus Stationery, Heliopolis</dd>
        <dt>Price</dt><dd>Free, registration required</dd>
        <dt>Duration</dt><dd>3 hours</dd>
      </dl>
      <h2>Programme</h2>
      <ol>
        <li><b>18:00</b> Doors open</li>
        <li><b>18:30</b> Welcome talk</li>
        <li><b>19:00</b> Try the products</li>
        <li><b>20:30</b> Prize draw</li>
      </ol>
      <a class="btn" href="register.html">Register now</a>
    </article>
  </main>
</body>
</html>
```

Project 560: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.date { color: var(--brand); font-weight: 700; margin: 0; }
h1 { margin: .2rem 0; }
.lead { font-size: 1.2rem; }
.facts { display: grid; grid-template-columns: max-content 1fr; gap: .
4rem 1.5rem; background: var(--accent); padding: 1rem 1.25rem; border-
```

```
radius: 10px; }
dt { font-weight: 700; }
dd { margin: 0; }
ol { padding-left: 1.2rem; }
ol li { margin-bottom: .4rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 560 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery open day</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="event">	A self-contained piece: card, post, product.
<p class="date"><time datetime="2026-10-15T18:00">Thursday 15 Octob...	A paragraph of text.
Papyrus Stationery open day	The main heading; only one per page.
<dl class="facts">	Description list of term / description pairs.
<dt>Where</dt><dd>Papyrus Stationery, Heliopolis</dd>	A term (name) in a description list.
<dt>Price</dt><dd>Free, registration required</dd>	The description of the preceding term.
Programme	Second-level heading for a section.

Line	What it does
	Ordered (numbered) list; the order matters.
18:00 Doors open	One list item.
18:30 Welcome talk	Keyword or name drawn to attention without extra importance.
Register now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
font-weight: 700;	Thickness of the text.
font-size: 1.2rem;	Size of the text.
display: grid;	Turns the element into a grid container.
grid-template-columns: max-content 1fr;	Defines the columns of the grid.
gap: .4rem 1.5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 10px;	Rounds the corners.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- datetime is ISO format
- dt/dd pairs align
- Programme is an ordered list
- Button text is an action

Exercises

1. Add an 'Add to calendar' .ics link.
2. Add a map with an iframe.
3. Add a countdown with JavaScript.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 561: Event page for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 1 | Files: index.html, styles.css

Brief

Announce an event with a machine-readable date, key facts in a two-column description list, a numbered programme and a register button.

Learning goals

- Use <time> with a full datetime
- Lay out dl as a two-column grid
- Use ol for a sequence

Elements and CSS used

HTML elements	CSS features
article, time, h1, p, dl, dt, dd, h2, ol, li, b, a	grid-template-columns: max-content 1fr, gap (two values), border-radius, padding-left

Build guide

1. Write the date first with <time datetime="2026-10-15T18:00">.
2. Add heading and lead.
3. Add the facts list and programme.
4. Grid the dl: dt in the first column, dd in the second.
5. Style the button.
6. Validate the datetime format.

Project 561: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery open day</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="event">
      <p class="date"><time datetime="2026-10-15T18:00">Thursday 15
October 2026, 18:00</time></p>
      <h1>Oasis Plant Nursery open day</h1>
      <p class="lead">Come and try our plants for free, meet Hossam
Ali and enjoy live music.</p>
      <dl class="facts">
        <dt>Where</dt><dd>Oasis Plant Nursery, Sheikh Zayed</dd>
        <dt>Price</dt><dd>Free, registration required</dd>
        <dt>Duration</dt><dd>3 hours</dd>
      </dl>
      <h2>Programme</h2>
      <ol>
        <li><b>18:00</b> Doors open</li>
        <li><b>18:30</b> Welcome talk</li>
        <li><b>19:00</b> Try the plants</li>
        <li><b>20:30</b> Prize draw</li>
      </ol>
      <a class="btn" href="register.html">Register now</a>
    </article>
  </main>
</body>
</html>
```

Project 561: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.date { color: var(--brand); font-weight: 700; margin: 0; }
h1 { margin: .2rem 0; }
.lead { font-size: 1.2rem; }
.facts { display: grid; grid-template-columns: max-content 1fr; gap: .
4rem 1.5rem; background: var(--accent); padding: 1rem 1.25rem; border-
```

```
radius: 10px; }
dt { font-weight: 700; }
dd { margin: 0; }
ol { padding-left: 1.2rem; }
ol li { margin-bottom: .4rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 561 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery open day</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="event">	A self-contained piece: card, post, product.
<p class="date"><time datetime="2026-10-15T18:00">Thursday 15 Octob...	A paragraph of text.
Oasis Plant Nursery open day	The main heading; only one per page.
<dl class="facts">	Description list of term / description pairs.
<dt>Where</dt><dd>Oasis Plant Nursery, Sheikh Zayed</dd>	A term (name) in a description list.
<dt>Price</dt><dd>Free, registration required</dd>	The description of the preceding term.
Programme	Second-level heading for a section.

Line	What it does
	Ordered (numbered) list; the order matters.
18:00 Doors open	One list item.
18:30 Welcome talk	Keyword or name drawn to attention without extra importance.
Register now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
font-weight: 700;	Thickness of the text.
font-size: 1.2rem;	Size of the text.
display: grid;	Turns the element into a grid container.
grid-template-columns: max-content 1fr;	Defines the columns of the grid.
gap: .4rem 1.5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 10px;	Rounds the corners.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- datetime is ISO format
- dt/dd pairs align
- Programme is an ordered list
- Button text is an action

Exercises

1. Add an 'Add to calendar' .ics link.
2. Add a map with an iframe.
3. Add a countdown with JavaScript.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 562: Event page for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 1 | Files: index.html, styles.css

Brief

Announce an event with a machine-readable date, key facts in a two-column description list, a numbered programme and a register button.

Learning goals

- Use <time> with a full datetime
- Lay out dl as a two-column grid
- Use ol for a sequence

Elements and CSS used

HTML elements	CSS features
article, time, h1, p, dl, dt, dd, h2, ol, li, b, a	grid-template-columns: max-content 1fr, gap (two values), border-radius, padding-left

Build guide

1. Write the date first with <time datetime="2026-10-15T18:00">.
2. Add heading and lead.
3. Add the facts list and programme.
4. Grid the dl: dt in the first column, dd in the second.
5. Style the button.
6. Validate the datetime format.

Project 562: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture open day</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="event">
      <p class="date"><time datetime="2026-10-15T18:00">Thursday 15
October 2026, 18:00</time></p>
      <h1>Cedar Furniture open day</h1>
      <p class="lead">Come and try our pieces for free, meet Tarek
Lotfy and enjoy live music.</p>
      <dl class="facts">
        <dt>Where</dt><dd>Cedar Furniture, Damietta</dd>
        <dt>Price</dt><dd>Free, registration required</dd>
        <dt>Duration</dt><dd>3 hours</dd>
      </dl>
      <h2>Programme</h2>
      <ol>
        <li><b>18:00</b> Doors open</li>
        <li><b>18:30</b> Welcome talk</li>
        <li><b>19:00</b> Try the pieces</li>
        <li><b>20:30</b> Prize draw</li>
      </ol>
      <a class="btn" href="register.html">Register now</a>
    </article>
  </main>
</body>
</html>
```

Project 562: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.date { color: var(--brand); font-weight: 700; margin: 0; }
h1 { margin: .2rem 0; }
.lead { font-size: 1.2rem; }
.facts { display: grid; grid-template-columns: max-content 1fr; gap: .
4rem 1.5rem; background: var(--accent); padding: 1rem 1.25rem; border-
```

```
radius: 10px; }
dt { font-weight: 700; }
dd { margin: 0; }
ol { padding-left: 1.2rem; }
ol li { margin-bottom: .4rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 562 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture open day</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="event">	A self-contained piece: card, post, product.
<p class="date"><time datetime="2026-10-15T18:00">Thursday 15 Octob...	A paragraph of text.
Cedar Furniture open day	The main heading; only one per page.
<dl class="facts">	Description list of term / description pairs.
<dt>Where</dt><dd>Cedar Furniture, Damietta</dd>	A term (name) in a description list.
<dt>Price</dt><dd>Free, registration required</dd>	The description of the preceding term.
Programme	Second-level heading for a section.

Line	What it does
	Ordered (numbered) list; the order matters.
18:00 Doors open	One list item.
18:30 Welcome talk	Keyword or name drawn to attention without extra importance.
Register now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
font-weight: 700;	Thickness of the text.
font-size: 1.2rem;	Size of the text.
display: grid;	Turns the element into a grid container.
grid-template-columns: max-content 1fr;	Defines the columns of the grid.
gap: .4rem 1.5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 10px;	Rounds the corners.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- datetime is ISO format
- dt/dd pairs align
- Programme is an ordered list
- Button text is an action

Exercises

1. Add an 'Add to calendar' .ics link.
2. Add a map with an iframe.
3. Add a countdown with JavaScript.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 563: Event page for Byte Repair

Theme: Byte Repair (Nasr City) | Level 1 | Files: index.html, styles.css

Brief

Announce an event with a machine-readable date, key facts in a two-column description list, a numbered programme and a register button.

Learning goals

- Use <time> with a full datetime
- Lay out dl as a two-column grid
- Use ol for a sequence

Elements and CSS used

HTML elements	CSS features
article, time, h1, p, dl, dt, dd, h2, ol, li, b, a	grid-template-columns: max-content 1fr, gap (two values), border-radius, padding-left

Build guide

1. Write the date first with <time datetime="2026-10-15T18:00">.
2. Add heading and lead.
3. Add the facts list and programme.
4. Grid the dl: dt in the first column, dd in the second.
5. Style the button.
6. Validate the datetime format.

Project 563: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair open day</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="event">
      <p class="date"><time datetime="2026-10-15T18:00">Thursday 15
October 2026, 18:00</time></p>
      <h1>Byte Repair open day</h1>
      <p class="lead">Come and try our repairs for free, meet Mostafa
Gamal and enjoy live music.</p>
      <dl class="facts">
        <dt>Where</dt><dd>Byte Repair, Nasr City</dd>
        <dt>Price</dt><dd>Free, registration required</dd>
        <dt>Duration</dt><dd>3 hours</dd>
      </dl>
      <h2>Programme</h2>
      <ol>
        <li><b>18:00</b> Doors open</li>
        <li><b>18:30</b> Welcome talk</li>
        <li><b>19:00</b> Try the repairs</li>
        <li><b>20:30</b> Prize draw</li>
      </ol>
      <a class="btn" href="register.html">Register now</a>
    </article>
  </main>
</body>
</html>
```

Project 563: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.date { color: var(--brand); font-weight: 700; margin: 0; }
h1 { margin: .2rem 0; }
.lead { font-size: 1.2rem; }
.facts { display: grid; grid-template-columns: max-content 1fr; gap: .
4rem 1.5rem; background: var(--accent); padding: 1rem 1.25rem; border-
```

```
radius: 10px; }
dt { font-weight: 700; }
dd { margin: 0; }
ol { padding-left: 1.2rem; }
ol li { margin-bottom: .4rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 563 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair open day</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="event">	A self-contained piece: card, post, product.
<p class="date"><time datetime="2026-10-15T18:00">Thursday 15 Octob...	A paragraph of text.
Byte Repair open day	The main heading; only one per page.
<dl class="facts">	Description list of term / description pairs.
<dt>Where</dt><dd>Byte Repair, Nasr City</dd>	A term (name) in a description list.
<dt>Price</dt><dd>Free, registration required</dd>	The description of the preceding term.
Programme	Second-level heading for a section.

Line	What it does
	Ordered (numbered) list; the order matters.
18:00 Doors open	One list item.
18:30 Welcome talk	Keyword or name drawn to attention without extra importance.
Register now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
font-weight: 700;	Thickness of the text.
font-size: 1.2rem;	Size of the text.
display: grid;	Turns the element into a grid container.
grid-template-columns: max-content 1fr;	Defines the columns of the grid.
gap: .4rem 1.5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 10px;	Rounds the corners.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- datetime is ISO format
- dt/dd pairs align
- Programme is an ordered list
- Button text is an action

Exercises

1. Add an 'Add to calendar' .ics link.
2. Add a map with an iframe.
3. Add a countdown with JavaScript.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 564: Event page for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 1 | Files: index.html, styles.css

Brief

Announce an event with a machine-readable date, key facts in a two-column description list, a numbered programme and a register button.

Learning goals

- Use <time> with a full datetime
- Lay out dl as a two-column grid
- Use ol for a sequence

Elements and CSS used

HTML elements	CSS features
article, time, h1, p, dl, dt, dd, h2, ol, li, b, a	grid-template-columns: max-content 1fr, gap (two values), border-radius, padding-left

Build guide

1. Write the date first with <time datetime="2026-10-15T18:00">.
2. Add heading and lead.
3. Add the facts list and programme.
4. Grid the dl: dt in the first column, dd in the second.
5. Style the button.
6. Validate the datetime format.

Project 564: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care open day</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="event">
      <p class="date"><time datetime="2026-10-15T18:00">Thursday 15
October 2026, 18:00</time></p>
      <h1>Sahara Pet Care open day</h1>
      <p class="lead">Come and try our services for free, meet Rana
Ibrahim and enjoy live music.</p>
      <dl class="facts">
        <dt>Where</dt><dd>Sahara Pet Care, New Cairo</dd>
        <dt>Price</dt><dd>Free, registration required</dd>
        <dt>Duration</dt><dd>3 hours</dd>
      </dl>
      <h2>Programme</h2>
      <ol>
        <li><b>18:00</b> Doors open</li>
        <li><b>18:30</b> Welcome talk</li>
        <li><b>19:00</b> Try the services</li>
        <li><b>20:30</b> Prize draw</li>
      </ol>
      <a class="btn" href="register.html">Register now</a>
    </article>
  </main>
</body>
</html>
```

Project 564: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.date { color: var(--brand); font-weight: 700; margin: 0; }
h1 { margin: .2rem 0; }
.lead { font-size: 1.2rem; }
.facts { display: grid; grid-template-columns: max-content 1fr; gap: .
4rem 1.5rem; background: var(--accent); padding: 1rem 1.25rem; border-
```

```
radius: 10px; }
dt { font-weight: 700; }
dd { margin: 0; }
ol { padding-left: 1.2rem; }
ol li { margin-bottom: .4rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 564 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care open day</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="event">	A self-contained piece: card, post, product.
<p class="date"><time datetime="2026-10-15T18:00">Thursday 15 Octob...	A paragraph of text.
Sahara Pet Care open day	The main heading; only one per page.
<dl class="facts">	Description list of term / description pairs.
<dt>Where</dt><dd>Sahara Pet Care, New Cairo</dd>	A term (name) in a description list.
<dt>Price</dt><dd>Free, registration required</dd>	The description of the preceding term.
Programme	Second-level heading for a section.

Line	What it does
	Ordered (numbered) list; the order matters.
18:00 Doors open	One list item.
18:30 Welcome talk	Keyword or name drawn to attention without extra importance.
Register now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
font-weight: 700;	Thickness of the text.
font-size: 1.2rem;	Size of the text.
display: grid;	Turns the element into a grid container.
grid-template-columns: max-content 1fr;	Defines the columns of the grid.
gap: .4rem 1.5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 10px;	Rounds the corners.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- datetime is ISO format
- dt/dd pairs align
- Programme is an ordered list
- Button text is an action

Exercises

1. Add an 'Add to calendar' .ics link.
2. Add a map with an iframe.
3. Add a countdown with JavaScript.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 565: Event page for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Announce an event with a machine-readable date, key facts in a two-column description list, a numbered programme and a register button.

Learning goals

- Use <time> with a full datetime
- Lay out dl as a two-column grid
- Use ol for a sequence

Elements and CSS used

HTML elements	CSS features
article, time, h1, p, dl, dt, dd, h2, ol, li, b, a	grid-template-columns: max-content 1fr, gap (two values), border-radius, padding-left

Build guide

1. Write the date first with <time datetime="2026-10-15T18:00">.
2. Add heading and lead.
3. Add the facts list and programme.
4. Grid the dl: dt in the first column, dd in the second.
5. Style the button.
6. Validate the datetime format.

Project 565: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School open day</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="event">
      <p class="date"><time datetime="2026-10-15T18:00">Thursday 15
October 2026, 18:00</time></p>
      <h1>Alexandria Sailing School open day</h1>
      <p class="lead">Come and try our lessons for free, meet Amr
Selim and enjoy live music.</p>
      <dl class="facts">
        <dt>Where</dt><dd>Alexandria Sailing School, Alexandria</dd>
        <dt>Price</dt><dd>Free, registration required</dd>
        <dt>Duration</dt><dd>3 hours</dd>
      </dl>
      <h2>Programme</h2>
      <ol>
        <li><b>18:00</b> Doors open</li>
        <li><b>18:30</b> Welcome talk</li>
        <li><b>19:00</b> Try the lessons</li>
        <li><b>20:30</b> Prize draw</li>
      </ol>
      <a class="btn" href="register.html">Register now</a>
    </article>
  </main>
</body>
</html>
```

Project 565: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.date { color: var(--brand); font-weight: 700; margin: 0; }
h1 { margin: .2rem 0; }
.lead { font-size: 1.2rem; }
.facts { display: grid; grid-template-columns: max-content 1fr; gap: .
4rem 1.5rem; background: var(--accent); padding: 1rem 1.25rem; border-
```

```
radius: 10px; }
dt { font-weight: 700; }
dd { margin: 0; }
ol { padding-left: 1.2rem; }
ol li { margin-bottom: .4rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 565 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School open day</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="event">	A self-contained piece: card, post, product.
<p class="date"><time datetime="2026-10-15T18:00">Thursday 15 Octob...	A paragraph of text.
Alexandria Sailing School open day	The main heading; only one per page.
<dl class="facts">	Description list of term / description pairs.
<dt>Where</dt><dd>Alexandria Sailing School, Alexandria</dd>	A term (name) in a description list.
<dt>Price</dt><dd>Free, registration required</dd>	The description of the preceding term.
Programme	Second-level heading for a section.

Line	What it does
	Ordered (numbered) list; the order matters.
18:00 Doors open	One list item.
18:30 Welcome talk	Keyword or name drawn to attention without extra importance.
Register now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
font-weight: 700;	Thickness of the text.
font-size: 1.2rem;	Size of the text.
display: grid;	Turns the element into a grid container.
grid-template-columns: max-content 1fr;	Defines the columns of the grid.
gap: .4rem 1.5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 10px;	Rounds the corners.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- datetime is ISO format
- dt/dd pairs align
- Programme is an ordered list
- Button text is an action

Exercises

1. Add an 'Add to calendar' .ics link.
2. Add a map with an iframe.
3. Add a countdown with JavaScript.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 566: Event page for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Announce an event with a machine-readable date, key facts in a two-column description list, a numbered programme and a register button.

Learning goals

- Use <time> with a full datetime
- Lay out dl as a two-column grid
- Use ol for a sequence

Elements and CSS used

HTML elements	CSS features
article, time, h1, p, dl, dt, dd, h2, ol, li, b, a	grid-template-columns: max-content 1fr, gap (two values), border-radius, padding-left

Build guide

1. Write the date first with <time datetime="2026-10-15T18:00">.
2. Add heading and lead.
3. Add the facts list and programme.
4. Grid the dl: dt in the first column, dd in the second.
5. Style the button.
6. Validate the datetime format.

Project 566: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery open day</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="event">
      <p class="date"><time datetime="2026-10-15T18:00">Thursday 15
October 2026, 18:00</time></p>
      <h1>Habiba Handmade Jewellery open day</h1>
      <p class="lead">Come and try our items for free, meet Habiba
Saleh and enjoy live music.</p>
      <dl class="facts">
        <dt>Where</dt><dd>Habiba Handmade Jewellery, Aswan</dd>
        <dt>Price</dt><dd>Free, registration required</dd>
        <dt>Duration</dt><dd>3 hours</dd>
      </dl>
      <h2>Programme</h2>
      <ol>
        <li><b>18:00</b> Doors open</li>
        <li><b>18:30</b> Welcome talk</li>
        <li><b>19:00</b> Try the items</li>
        <li><b>20:30</b> Prize draw</li>
      </ol>
      <a class="btn" href="register.html">Register now</a>
    </article>
  </main>
</body>
</html>
```

Project 566: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.date { color: var(--brand); font-weight: 700; margin: 0; }
h1 { margin: .2rem 0; }
.lead { font-size: 1.2rem; }
.facts { display: grid; grid-template-columns: max-content 1fr; gap: .
4rem 1.5rem; background: var(--accent); padding: 1rem 1.25rem; border-
```

```
radius: 10px; }
dt { font-weight: 700; }
dd { margin: 0; }
ol { padding-left: 1.2rem; }
ol li { margin-bottom: .4rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 566 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery open day</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="event">	A self-contained piece: card, post, product.
<p class="date"><time datetime="2026-10-15T18:00">Thursday 15 Octob...	A paragraph of text.
Habiba Handmade Jewellery open day	The main heading; only one per page.
<dl class="facts">	Description list of term / description pairs.
<dt>Where</dt><dd>Habiba Handmade Jewellery, Aswan</dd>	A term (name) in a description list.
<dt>Price</dt><dd>Free, registration required</dd>	The description of the preceding term.
Programme	Second-level heading for a section.

Line	What it does
	Ordered (numbered) list; the order matters.
18:00 Doors open	One list item.
18:30 Welcome talk	Keyword or name drawn to attention without extra importance.
Register now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
font-weight: 700;	Thickness of the text.
font-size: 1.2rem;	Size of the text.
display: grid;	Turns the element into a grid container.
grid-template-columns: max-content 1fr;	Defines the columns of the grid.
gap: .4rem 1.5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 10px;	Rounds the corners.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- datetime is ISO format
- dt/dd pairs align
- Programme is an ordered list
- Button text is an action

Exercises

1. Add an 'Add to calendar' .ics link.
2. Add a map with an iframe.
3. Add a countdown with JavaScript.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 567: Event page for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 1 | Files: index.html, styles.css

Brief

Announce an event with a machine-readable date, key facts in a two-column description list, a numbered programme and a register button.

Learning goals

- Use <time> with a full datetime
- Lay out dl as a two-column grid
- Use ol for a sequence

Elements and CSS used

HTML elements	CSS features
article, time, h1, p, dl, dt, dd, h2, ol, li, b, a	grid-template-columns: max-content 1fr, gap (two values), border-radius, padding-left

Build guide

1. Write the date first with <time datetime="2026-10-15T18:00">.
2. Add heading and lead.
3. Add the facts list and programme.
4. Grid the dl: dt in the first column, dd in the second.
5. Style the button.
6. Validate the datetime format.

Project 567: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio open day</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="event">
      <p class="date"><time datetime="2026-10-15T18:00">Thursday 15
October 2026, 18:00</time></p>
      <h1>Fayoum Pottery Studio open day</h1>
      <p class="lead">Come and try our workshops for free, meet Ahmed
Mahmoud and enjoy live music.</p>
      <dl class="facts">
        <dt>Where</dt><dd>Fayoum Pottery Studio, Tunis Village</dd>
        <dt>Price</dt><dd>Free, registration required</dd>
        <dt>Duration</dt><dd>3 hours</dd>
      </dl>
      <h2>Programme</h2>
      <ol>
        <li><b>18:00</b> Doors open</li>
        <li><b>18:30</b> Welcome talk</li>
        <li><b>19:00</b> Try the workshops</li>
        <li><b>20:30</b> Prize draw</li>
      </ol>
      <a class="btn" href="register.html">Register now</a>
    </article>
  </main>
</body>
</html>
```

Project 567: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.date { color: var(--brand); font-weight: 700; margin: 0; }
h1 { margin: .2rem 0; }
.lead { font-size: 1.2rem; }
.facts { display: grid; grid-template-columns: max-content 1fr; gap: .
4rem 1.5rem; background: var(--accent); padding: 1rem 1.25rem; border-
```

```
radius: 10px; }
dt { font-weight: 700; }
dd { margin: 0; }
ol { padding-left: 1.2rem; }
ol li { margin-bottom: .4rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 567 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio open day</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="event">	A self-contained piece: card, post, product.
<p class="date"><time datetime="2026-10-15T18:00">Thursday 15 Octob...	A paragraph of text.
Fayoum Pottery Studio open day	The main heading; only one per page.
<dl class="facts">	Description list of term / description pairs.
<dt>Where</dt><dd>Fayoum Pottery Studio, Tunis Village</dd>	A term (name) in a description list.
<dt>Price</dt><dd>Free, registration required</dd>	The description of the preceding term.
Programme	Second-level heading for a section.

Line	What it does
	Ordered (numbered) list; the order matters.
18:00 Doors open	One list item.
18:30 Welcome talk	Keyword or name drawn to attention without extra importance.
Register now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
font-weight: 700;	Thickness of the text.
font-size: 1.2rem;	Size of the text.
display: grid;	Turns the element into a grid container.
grid-template-columns: max-content 1fr;	Defines the columns of the grid.
gap: .4rem 1.5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 10px;	Rounds the corners.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- datetime is ISO format
- dt/dd pairs align
- Programme is an ordered list
- Button text is an action

Exercises

1. Add an 'Add to calendar' .ics link.
2. Add a map with an iframe.
3. Add a countdown with JavaScript.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 568: Event page for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 1 | Files: index.html, styles.css

Brief

Announce an event with a machine-readable date, key facts in a two-column description list, a numbered programme and a register button.

Learning goals

- Use <time> with a full datetime
- Lay out dl as a two-column grid
- Use ol for a sequence

Elements and CSS used

HTML elements	CSS features
article, time, h1, p, dl, dt, dd, h2, ol, li, b, a	grid-template-columns: max-content 1fr, gap (two values), border-radius, padding-left

Build guide

1. Write the date first with <time datetime="2026-10-15T18:00">.
2. Add heading and lead.
3. Add the facts list and programme.
4. Grid the dl: dt in the first column, dd in the second.
5. Style the button.
6. Validate the datetime format.

Project 568: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon open day</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="event">
      <p class="date"><time datetime="2026-10-15T18:00">Thursday 15
October 2026, 18:00</time></p>
      <h1>Cleopatra Beauty Salon open day</h1>
      <p class="lead">Come and try our treatments for free, meet
Mariam Adel and enjoy live music.</p>
      <dl class="facts">
        <dt>Where</dt><dd>Cleopatra Beauty Salon, Dokki</dd>
        <dt>Price</dt><dd>Free, registration required</dd>
        <dt>Duration</dt><dd>3 hours</dd>
      </dl>
      <h2>Programme</h2>
      <ol>
        <li><b>18:00</b> Doors open</li>
        <li><b>18:30</b> Welcome talk</li>
        <li><b>19:00</b> Try the treatments</li>
        <li><b>20:30</b> Prize draw</li>
      </ol>
      <a class="btn" href="register.html">Register now</a>
    </article>
  </main>
</body>
</html>
```

Project 568: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.date { color: var(--brand); font-weight: 700; margin: 0; }
h1 { margin: .2rem 0; }
.lead { font-size: 1.2rem; }
.facts { display: grid; grid-template-columns: max-content 1fr; gap: .
4rem 1.5rem; background: var(--accent); padding: 1rem 1.25rem; border-
```

```
radius: 10px; }
dt { font-weight: 700; }
dd { margin: 0; }
ol { padding-left: 1.2rem; }
ol li { margin-bottom: .4rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 568 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon open day</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="event">	A self-contained piece: card, post, product.
<p class="date"><time datetime="2026-10-15T18:00">Thursday 15 Octob...	A paragraph of text.
Cleopatra Beauty Salon open day	The main heading; only one per page.
<dl class="facts">	Description list of term / description pairs.
<dt>Where</dt><dd>Cleopatra Beauty Salon, Dokki</dd>	A term (name) in a description list.
<dt>Price</dt><dd>Free, registration required</dd>	The description of the preceding term.
Programme	Second-level heading for a section.

Line	What it does
	Ordered (numbered) list; the order matters.
18:00 Doors open	One list item.
18:30 Welcome talk	Keyword or name drawn to attention without extra importance.
Register now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
font-weight: 700;	Thickness of the text.
font-size: 1.2rem;	Size of the text.
display: grid;	Turns the element into a grid container.
grid-template-columns: max-content 1fr;	Defines the columns of the grid.
gap: .4rem 1.5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 10px;	Rounds the corners.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- datetime is ISO format
- dt/dd pairs align
- Programme is an ordered list
- Button text is an action

Exercises

1. Add an 'Add to calendar' .ics link.
2. Add a map with an iframe.
3. Add a countdown with JavaScript.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 569: Event page for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 1 | Files: index.html, styles.css

Brief

Announce an event with a machine-readable date, key facts in a two-column description list, a numbered programme and a register button.

Learning goals

- Use <time> with a full datetime
- Lay out dl as a two-column grid
- Use ol for a sequence

Elements and CSS used

HTML elements	CSS features
article, time, h1, p, dl, dt, dd, h2, ol, li, b, a	grid-template-columns: max-content 1fr, gap (two values), border-radius, padding-left

Build guide

1. Write the date first with <time datetime="2026-10-15T18:00">.
2. Add heading and lead.
3. Add the facts list and programme.
4. Grid the dl: dt in the first column, dd in the second.
5. Style the button.
6. Validate the datetime format.

Project 569: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service open day</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="event">
      <p class="date"><time datetime="2026-10-15T18:00">Thursday 15
October 2026, 18:00</time></p>
      <h1>Suez Auto Service open day</h1>
      <p class="lead">Come and try our services for free, meet Khaled
Nasser and enjoy live music.</p>
      <dl class="facts">
        <dt>Where</dt><dd>Suez Auto Service, Suez</dd>
        <dt>Price</dt><dd>Free, registration required</dd>
        <dt>Duration</dt><dd>3 hours</dd>
      </dl>
      <h2>Programme</h2>
      <ol>
        <li><b>18:00</b> Doors open</li>
        <li><b>18:30</b> Welcome talk</li>
        <li><b>19:00</b> Try the services</li>
        <li><b>20:30</b> Prize draw</li>
      </ol>
      <a class="btn" href="register.html">Register now</a>
    </article>
  </main>
</body>
</html>
```

Project 569: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.date { color: var(--brand); font-weight: 700; margin: 0; }
h1 { margin: .2rem 0; }
.lead { font-size: 1.2rem; }
.facts { display: grid; grid-template-columns: max-content 1fr; gap: .
4rem 1.5rem; background: var(--accent); padding: 1rem 1.25rem; border-
```

```
radius: 10px; }
dt { font-weight: 700; }
dd { margin: 0; }
ol { padding-left: 1.2rem; }
ol li { margin-bottom: .4rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 569 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service open day</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="event">	A self-contained piece: card, post, product.
<p class="date"><time datetime="2026-10-15T18:00">Thursday 15 Octob...	A paragraph of text.
Suez Auto Service open day	The main heading; only one per page.
<dl class="facts">	Description list of term / description pairs.
<dt>Where</dt><dd>Suez Auto Service, Suez</dd>	A term (name) in a description list.
<dt>Price</dt><dd>Free, registration required</dd>	The description of the preceding term.
Programme	Second-level heading for a section.

Line	What it does
	Ordered (numbered) list; the order matters.
18:00 Doors open	One list item.
18:30 Welcome talk	Keyword or name drawn to attention without extra importance.
Register now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
font-weight: 700;	Thickness of the text.
font-size: 1.2rem;	Size of the text.
display: grid;	Turns the element into a grid container.
grid-template-columns: max-content 1fr;	Defines the columns of the grid.
gap: .4rem 1.5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 10px;	Rounds the corners.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- datetime is ISO format
- dt/dd pairs align
- Programme is an ordered list
- Button text is an action

Exercises

1. Add an 'Add to calendar' .ics link.
2. Add a map with an iframe.
3. Add a countdown with JavaScript.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 570: Event page for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 1 | Files: index.html, styles.css

Brief

Announce an event with a machine-readable date, key facts in a two-column description list, a numbered programme and a register button.

Learning goals

- Use <time> with a full datetime
- Lay out dl as a two-column grid
- Use ol for a sequence

Elements and CSS used

HTML elements	CSS features
article, time, h1, p, dl, dt, dd, h2, ol, li, b, a	grid-template-columns: max-content 1fr, gap (two values), border-radius, padding-left

Build guide

1. Write the date first with <time datetime="2026-10-15T18:00">.
2. Add heading and lead.
3. Add the facts list and programme.
4. Grid the dl: dt in the first column, dd in the second.
5. Style the button.
6. Validate the datetime format.

Project 570: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy open day</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="event">
      <p class="date"><time datetime="2026-10-15T18:00">Thursday 15
October 2026, 18:00</time></p>
      <h1>Luxor Music Academy open day</h1>
      <p class="lead">Come and try our courses for free, meet Salma
Ragab and enjoy live music.</p>
      <dl class="facts">
        <dt>Where</dt><dd>Luxor Music Academy, Luxor</dd>
        <dt>Price</dt><dd>Free, registration required</dd>
        <dt>Duration</dt><dd>3 hours</dd>
      </dl>
      <h2>Programme</h2>
      <ol>
        <li><b>18:00</b> Doors open</li>
        <li><b>18:30</b> Welcome talk</li>
        <li><b>19:00</b> Try the courses</li>
        <li><b>20:30</b> Prize draw</li>
      </ol>
      <a class="btn" href="register.html">Register now</a>
    </article>
  </main>
</body>
</html>
```

Project 570: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.date { color: var(--brand); font-weight: 700; margin: 0; }
h1 { margin: .2rem 0; }
.lead { font-size: 1.2rem; }
.facts { display: grid; grid-template-columns: max-content 1fr; gap: .
4rem 1.5rem; background: var(--accent); padding: 1rem 1.25rem; border-
```

```
radius: 10px; }
dt { font-weight: 700; }
dd { margin: 0; }
ol { padding-left: 1.2rem; }
ol li { margin-bottom: .4rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 570 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy open day</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="event">	A self-contained piece: card, post, product.
<p class="date"><time datetime="2026-10-15T18:00">Thursday 15 Octob...	A paragraph of text.
Luxor Music Academy open day	The main heading; only one per page.
<dl class="facts">	Description list of term / description pairs.
<dt>Where</dt><dd>Luxor Music Academy, Luxor</dd>	A term (name) in a description list.
<dt>Price</dt><dd>Free, registration required</dd>	The description of the preceding term.
Programme	Second-level heading for a section.

Line	What it does
	Ordered (numbered) list; the order matters.
18:00 Doors open	One list item.
18:30 Welcome talk	Keyword or name drawn to attention without extra importance.
Register now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
font-weight: 700;	Thickness of the text.
font-size: 1.2rem;	Size of the text.
display: grid;	Turns the element into a grid container.
grid-template-columns: max-content 1fr;	Defines the columns of the grid.
gap: .4rem 1.5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 10px;	Rounds the corners.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- datetime is ISO format
- dt/dd pairs align
- Programme is an ordered list
- Button text is an action

Exercises

1. Add an 'Add to calendar' .ics link.
2. Add a map with an iframe.
3. Add a countdown with JavaScript.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 571: Event page for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 1 | Files: index.html, styles.css

Brief

Announce an event with a machine-readable date, key facts in a two-column description list, a numbered programme and a register button.

Learning goals

- Use <time> with a full datetime
- Lay out dl as a two-column grid
- Use ol for a sequence

Elements and CSS used

HTML elements	CSS features
article, time, h1, p, dl, dt, dd, h2, ol, li, b, a	grid-template-columns: max-content 1fr, gap (two values), border-radius, padding-left

Build guide

1. Write the date first with <time datetime="2026-10-15T18:00">.
2. Add heading and lead.
3. Add the facts list and programme.
4. Grid the dl: dt in the first column, dd in the second.
5. Style the button.
6. Validate the datetime format.

Project 571: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood open day</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="event">
      <p class="date"><time datetime="2026-10-15T18:00">Thursday 15
October 2026, 18:00</time></p>
      <h1>Port Said Seafood open day</h1>
      <p class="lead">Come and try our dishes for free, meet Sherif
Wahba and enjoy live music.</p>
      <dl class="facts">
        <dt>Where</dt><dd>Port Said Seafood, Port Said</dd>
        <dt>Price</dt><dd>Free, registration required</dd>
        <dt>Duration</dt><dd>3 hours</dd>
      </dl>
      <h2>Programme</h2>
      <ol>
        <li><b>18:00</b> Doors open</li>
        <li><b>18:30</b> Welcome talk</li>
        <li><b>19:00</b> Try the dishes</li>
        <li><b>20:30</b> Prize draw</li>
      </ol>
      <a class="btn" href="register.html">Register now</a>
    </article>
  </main>
</body>
</html>
```

Project 571: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.date { color: var(--brand); font-weight: 700; margin: 0; }
h1 { margin: .2rem 0; }
.lead { font-size: 1.2rem; }
.facts { display: grid; grid-template-columns: max-content 1fr; gap: .
4rem 1.5rem; background: var(--accent); padding: 1rem 1.25rem; border-
```

```
radius: 10px; }
dt { font-weight: 700; }
dd { margin: 0; }
ol { padding-left: 1.2rem; }
ol li { margin-bottom: .4rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 571 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood open day</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="event">	A self-contained piece: card, post, product.
<p class="date"><time datetime="2026-10-15T18:00">Thursday 15 Octob...	A paragraph of text.
Port Said Seafood open day	The main heading; only one per page.
<dl class="facts">	Description list of term / description pairs.
<dt>Where</dt><dd>Port Said Seafood, Port Said</dd>	A term (name) in a description list.
<dt>Price</dt><dd>Free, registration required</dd>	The description of the preceding term.
Programme	Second-level heading for a section.

Line	What it does
	Ordered (numbered) list; the order matters.
18:00 Doors open	One list item.
18:30 Welcome talk	Keyword or name drawn to attention without extra importance.
Register now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
font-weight: 700;	Thickness of the text.
font-size: 1.2rem;	Size of the text.
display: grid;	Turns the element into a grid container.
grid-template-columns: max-content 1fr;	Defines the columns of the grid.
gap: .4rem 1.5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 10px;	Rounds the corners.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- datetime is ISO format
- dt/dd pairs align
- Programme is an ordered list
- Button text is an action

Exercises

1. Add an 'Add to calendar' .ics link.
2. Add a map with an iframe.
3. Add a countdown with JavaScript.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 572: Event page for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 1 | Files: index.html, styles.css

Brief

Announce an event with a machine-readable date, key facts in a two-column description list, a numbered programme and a register button.

Learning goals

- Use <time> with a full datetime
- Lay out dl as a two-column grid
- Use ol for a sequence

Elements and CSS used

HTML elements	CSS features
article, time, h1, p, dl, dt, dd, h2, ol, li, b, a	grid-template-columns: max-content 1fr, gap (two values), border-radius, padding-left

Build guide

1. Write the date first with <time datetime="2026-10-15T18:00">.
2. Add heading and lead.
3. Add the facts list and programme.
4. Grid the dl: dt in the first column, dd in the second.
5. Style the button.
6. Validate the datetime format.

Project 572: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library open day</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="event">
      <p class="date"><time datetime="2026-10-15T18:00">Thursday 15
October 2026, 18:00</time></p>
      <h1>Delta Kids Library open day</h1>
      <p class="lead">Come and try our programmes for free, meet
Ghada Kamel and enjoy live music.</p>
      <dl class="facts">
        <dt>Where</dt><dd>Delta Kids Library, Tanta</dd>
        <dt>Price</dt><dd>Free, registration required</dd>
        <dt>Duration</dt><dd>3 hours</dd>
      </dl>
      <h2>Programme</h2>
      <ol>
        <li><b>18:00</b> Doors open</li>
        <li><b>18:30</b> Welcome talk</li>
        <li><b>19:00</b> Try the programmes</li>
        <li><b>20:30</b> Prize draw</li>
      </ol>
      <a class="btn" href="register.html">Register now</a>
    </article>
  </main>
</body>
</html>
```

Project 572: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.date { color: var(--brand); font-weight: 700; margin: 0; }
h1 { margin: .2rem 0; }
.lead { font-size: 1.2rem; }
.facts { display: grid; grid-template-columns: max-content 1fr; gap: .
4rem 1.5rem; background: var(--accent); padding: 1rem 1.25rem; border-
```

```
radius: 10px; }
dt { font-weight: 700; }
dd { margin: 0; }
ol { padding-left: 1.2rem; }
ol li { margin-bottom: .4rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 572 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library open day</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="event">	A self-contained piece: card, post, product.
<p class="date"><time datetime="2026-10-15T18:00">Thursday 15 Octob...	A paragraph of text.
Delta Kids Library open day	The main heading; only one per page.
<dl class="facts">	Description list of term / description pairs.
<dt>Where</dt><dd>Delta Kids Library, Tanta</dd>	A term (name) in a description list.
<dt>Price</dt><dd>Free, registration required</dd>	The description of the preceding term.
Programme	Second-level heading for a section.

Line	What it does
	Ordered (numbered) list; the order matters.
18:00 Doors open	One list item.
18:30 Welcome talk	Keyword or name drawn to attention without extra importance.
Register now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
font-weight: 700;	Thickness of the text.
font-size: 1.2rem;	Size of the text.
display: grid;	Turns the element into a grid container.
grid-template-columns: max-content 1fr;	Defines the columns of the grid.
gap: .4rem 1.5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 10px;	Rounds the corners.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- datetime is ISO format
- dt/dd pairs align
- Programme is an ordered list
- Button text is an action

Exercises

1. Add an 'Add to calendar' .ics link.
2. Add a map with an iframe.
3. Add a countdown with JavaScript.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 573: Event page for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Announce an event with a machine-readable date, key facts in a two-column description list, a numbered programme and a register button.

Learning goals

- Use <time> with a full datetime
- Lay out dl as a two-column grid
- Use ol for a sequence

Elements and CSS used

HTML elements	CSS features
article, time, h1, p, dl, dt, dd, h2, ol, li, b, a	grid-template-columns: max-content 1fr, gap (two values), border-radius, padding-left

Build guide

1. Write the date first with <time datetime="2026-10-15T18:00">.
2. Add heading and lead.
3. Add the facts list and programme.
4. Grid the dl: dt in the first column, dd in the second.
5. Style the button.
6. Validate the datetime format.

Project 573: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House open day</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="event">
      <p class="date"><time datetime="2026-10-15T18:00">Thursday 15
October 2026, 18:00</time></p>
      <h1>Nubian Guest House open day</h1>
      <p class="lead">Come and try our rooms for free, meet Fatma
Hassan and enjoy live music.</p>
      <dl class="facts">
        <dt>Where</dt><dd>Nubian Guest House, Aswan</dd>
        <dt>Price</dt><dd>Free, registration required</dd>
        <dt>Duration</dt><dd>3 hours</dd>
      </dl>
      <h2>Programme</h2>
      <ol>
        <li><b>18:00</b> Doors open</li>
        <li><b>18:30</b> Welcome talk</li>
        <li><b>19:00</b> Try the rooms</li>
        <li><b>20:30</b> Prize draw</li>
      </ol>
      <a class="btn" href="register.html">Register now</a>
    </article>
  </main>
</body>
</html>
```

Project 573: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.date { color: var(--brand); font-weight: 700; margin: 0; }
h1 { margin: .2rem 0; }
.lead { font-size: 1.2rem; }
.facts { display: grid; grid-template-columns: max-content 1fr; gap: .
4rem 1.5rem; background: var(--accent); padding: 1rem 1.25rem; border-
```

```
radius: 10px; }
dt { font-weight: 700; }
dd { margin: 0; }
ol { padding-left: 1.2rem; }
ol li { margin-bottom: .4rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 573 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House open day</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="event">	A self-contained piece: card, post, product.
<p class="date"><time datetime="2026-10-15T18:00">Thursday 15 Octob...	A paragraph of text.
Nubian Guest House open day	The main heading; only one per page.
<dl class="facts">	Description list of term / description pairs.
<dt>Where</dt><dd>Nubian Guest House, Aswan</dd>	A term (name) in a description list.
<dt>Price</dt><dd>Free, registration required</dd>	The description of the preceding term.
Programme	Second-level heading for a section.

Line	What it does
	Ordered (numbered) list; the order matters.
18:00 Doors open	One list item.
18:30 Welcome talk	Keyword or name drawn to attention without extra importance.
Register now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
font-weight: 700;	Thickness of the text.
font-size: 1.2rem;	Size of the text.
display: grid;	Turns the element into a grid container.
grid-template-columns: max-content 1fr;	Defines the columns of the grid.
gap: .4rem 1.5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 10px;	Rounds the corners.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- datetime is ISO format
- dt/dd pairs align
- Programme is an ordered list
- Button text is an action

Exercises

1. Add an 'Add to calendar' .ics link.
2. Add a map with an iframe.
3. Add a countdown with JavaScript.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 574: Event page for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 1 | Files: index.html, styles.css

Brief

Announce an event with a machine-readable date, key facts in a two-column description list, a numbered programme and a register button.

Learning goals

- Use <time> with a full datetime
- Lay out dl as a two-column grid
- Use ol for a sequence

Elements and CSS used

HTML elements	CSS features
article, time, h1, p, dl, dt, dd, h2, ol, li, b, a	grid-template-columns: max-content 1fr, gap (two values), border-radius, padding-left

Build guide

1. Write the date first with <time datetime="2026-10-15T18:00">.
2. Add heading and lead.
3. Add the facts list and programme.
4. Grid the dl: dt in the first column, dd in the second.
5. Style the button.
6. Validate the datetime format.

Project 574: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store open day</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="event">
      <p class="date"><time datetime="2026-10-15T18:00">Thursday 15
October 2026, 18:00</time></p>
      <h1>Ismailia Cycling Store open day</h1>
      <p class="lead">Come and try our bikes for free, meet Bassem
Adly and enjoy live music.</p>
      <dl class="facts">
        <dt>Where</dt><dd>Ismailia Cycling Store, Ismailia</dd>
        <dt>Price</dt><dd>Free, registration required</dd>
        <dt>Duration</dt><dd>3 hours</dd>
      </dl>
      <h2>Programme</h2>
      <ol>
        <li><b>18:00</b> Doors open</li>
        <li><b>18:30</b> Welcome talk</li>
        <li><b>19:00</b> Try the bikes</li>
        <li><b>20:30</b> Prize draw</li>
      </ol>
      <a class="btn" href="register.html">Register now</a>
    </article>
  </main>
</body>
</html>
```

Project 574: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.date { color: var(--brand); font-weight: 700; margin: 0; }
h1 { margin: .2rem 0; }
.lead { font-size: 1.2rem; }
.facts { display: grid; grid-template-columns: max-content 1fr; gap: .
4rem 1.5rem; background: var(--accent); padding: 1rem 1.25rem; border-
```

```
radius: 10px; }
dt { font-weight: 700; }
dd { margin: 0; }
ol { padding-left: 1.2rem; }
ol li { margin-bottom: .4rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 574 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store open day</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="event">	A self-contained piece: card, post, product.
<p class="date"><time datetime="2026-10-15T18:00">Thursday 15 Octob...	A paragraph of text.
Ismailia Cycling Store open day	The main heading; only one per page.
<dl class="facts">	Description list of term / description pairs.
<dt>Where</dt><dd>Ismailia Cycling Store, Ismailia</dd>	A term (name) in a description list.
<dt>Price</dt><dd>Free, registration required</dd>	The description of the preceding term.
Programme	Second-level heading for a section.

Line	What it does
	Ordered (numbered) list; the order matters.
18:00 Doors open	One list item.
18:30 Welcome talk	Keyword or name drawn to attention without extra importance.
Register now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
font-weight: 700;	Thickness of the text.
font-size: 1.2rem;	Size of the text.
display: grid;	Turns the element into a grid container.
grid-template-columns: max-content 1fr;	Defines the columns of the grid.
gap: .4rem 1.5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 10px;	Rounds the corners.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- datetime is ISO format
- dt/dd pairs align
- Programme is an ordered list
- Button text is an action

Exercises

1. Add an 'Add to calendar' .ics link.
2. Add a map with an iframe.
3. Add a countdown with JavaScript.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 575: Event page for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 1 | Files: index.html, styles.css

Brief

Announce an event with a machine-readable date, key facts in a two-column description list, a numbered programme and a register button.

Learning goals

- Use <time> with a full datetime
- Lay out dl as a two-column grid
- Use ol for a sequence

Elements and CSS used

HTML elements	CSS features
article, time, h1, p, dl, dt, dd, h2, ol, li, b, a	grid-template-columns: max-content 1fr, gap (two values), border-radius, padding-left

Build guide

1. Write the date first with <time datetime="2026-10-15T18:00">.
2. Add heading and lead.
3. Add the facts list and programme.
4. Grid the dl: dt in the first column, dd in the second.
5. Style the button.
6. Validate the datetime format.

Project 575: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club open day</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="event">
      <p class="date"><time datetime="2026-10-15T18:00">Thursday 15
October 2026, 18:00</time></p>
      <h1>Minya Coding Club open day</h1>
      <p class="lead">Come and try our workshops for free, meet
Youssef Hany and enjoy live music.</p>
      <dl class="facts">
        <dt>Where</dt><dd>Minya Coding Club, Minya</dd>
        <dt>Price</dt><dd>Free, registration required</dd>
        <dt>Duration</dt><dd>3 hours</dd>
      </dl>
      <h2>Programme</h2>
      <ol>
        <li><b>18:00</b> Doors open</li>
        <li><b>18:30</b> Welcome talk</li>
        <li><b>19:00</b> Try the workshops</li>
        <li><b>20:30</b> Prize draw</li>
      </ol>
      <a class="btn" href="register.html">Register now</a>
    </article>
  </main>
</body>
</html>
```

Project 575: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.date { color: var(--brand); font-weight: 700; margin: 0; }
h1 { margin: .2rem 0; }
.lead { font-size: 1.2rem; }
.facts { display: grid; grid-template-columns: max-content 1fr; gap: .
4rem 1.5rem; background: var(--accent); padding: 1rem 1.25rem; border-
```

```
radius: 10px; }
dt { font-weight: 700; }
dd { margin: 0; }
ol { padding-left: 1.2rem; }
ol li { margin-bottom: .4rem; }
.btn { display: inline-block; padding: .8rem 1.6rem; background: var(-
-brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 575 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club open day</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="event">	A self-contained piece: card, post, product.
<p class="date"><time datetime="2026-10-15T18:00">Thursday 15 Octob...	A paragraph of text.
Minya Coding Club open day	The main heading; only one per page.
<dl class="facts">	Description list of term / description pairs.
<dt>Where</dt><dd>Minya Coding Club, Minya</dd>	A term (name) in a description list.
<dt>Price</dt><dd>Free, registration required</dd>	The description of the preceding term.
Programme	Second-level heading for a section.

Line	What it does
	Ordered (numbered) list; the order matters.
18:00 Doors open	One list item.
18:30 Welcome talk	Keyword or name drawn to attention without extra importance.
Register now	A link styled as a button; it navigates, so it is a link and not a <button>.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
font-weight: 700;	Thickness of the text.
font-size: 1.2rem;	Size of the text.
display: grid;	Turns the element into a grid container.
grid-template-columns: max-content 1fr;	Defines the columns of the grid.
gap: .4rem 1.5rem;	Space between grid or flex items without extra margins.
background: var(--accent);	Background colour or image.
border-radius: 10px;	Rounds the corners.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- datetime is ISO format
- dt/dd pairs align
- Programme is an ordered list
- Button text is an action

Exercises

1. Add an 'Add to calendar' .ics link.
2. Add a map with an iframe.
3. Add a countdown with JavaScript.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Printable invoice

Level 2 | 25 projects, one per theme

Create a clean invoice with a header row, a table using tfoot and colspan for the total, right-aligned numbers and print styles.

Project 576: Printable invoice for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 2 | Files: index.html, styles.css

Brief

Create a clean invoice with a header row, a table using tfoot and colspan for the total, right-aligned numbers and print styles.

Learning goals

- Use tfoot and colspan
- Align numbers with tabular figures
- Design for print

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, b, time, table, thead, tbody, tfoot, th, td	justify-content: space-between, colspan, font-variant-numeric, border-top, @media print

Build guide

1. Write the header with two blocks: seller and invoice metadata.
2. Write the table with thead, tbody and a tfoot total row using colspan="2".
3. Add class n to numeric cells.
4. Flex the header with space-between.
5. Right-align .n cells.
6. Print preview and remove the border in @media print.

Project 576: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Invoice 2026-041 - Cairo Book Shop</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="invoice">
    <header>
      <div><h1>Cairo Book Shop</h1><p>Giza, Egypt</p></div>
      <div class="meta"><p><b>Invoice</b> 2026-041</p><p><b>Date</b>
<time datetime="2026-09-11">11 Sep 2026</time></p></div>
    </header>
    <p><b>Bill to:</b> Customer name, Giza</p>
    <table>
      <thead><tr><th>Item</th><th class="n">Qty</th><th
class="n">Price</th></tr></thead>
      <tbody>
        <tr><td>Learn HTML</td><td class="n">1</td><td class="n">120
EGP</td></tr>
        <tr><td>CSS in Practice</td><td class="n">1</td><td
class="n">150 EGP</td></tr>
        <tr><td>JavaScript Basics</td><td class="n">1</td><td
class="n">180 EGP</td></tr>
      </tbody>
      <tfoot><tr><th colspan="2">Total</th><td class="n">see items</
td></tr></tfoot>
    </table>
    <p class="thanks">Thank you for your business.</p>
  </main>
</body>
</html>
```

Project 576: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.invoice { max-width: 46rem; margin: 2rem auto; padding: 2rem; border:
 1px solid var(--line); }
header { display: flex; justify-content: space-between; flex-wrap:
wrap; gap: 1rem; border-bottom: 3px solid var(--brand); padding-
bottom: 1rem; }
```

```
h1 { margin: 0; color: var(--brand); }
.meta p { margin: .1rem 0; text-align: right; }
table { width: 100%; border-collapse: collapse; margin-top: 1.5rem; }
th, td { padding: .6rem; border-bottom: 1px solid var(--line); text-
align: left; }
.n { text-align: right; font-variant-numeric: tabular-nums; }
tfoot th, tfoot td { font-weight: 700; border-top: 2px solid var(--
ink); border-bottom: 0; }
.thanks { margin-top: 2rem; color: var(--muted); font-style: italic; }
@media print { .invoice { border: 0; margin: 0; max-width: none; } }
```

Project 576 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Invoice 2026-041 - Cairo Book Shop</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="invoice">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Cairo Book Shop Giza, Egypt	The main heading; only one per page.
Invoice 2026-041 Date <tim...	A paragraph of text.
Bill to: Customer name, Giza	Keyword or name drawn to attention without extra importance.
<table>	Tabular data in rows and columns.
<thead><tr><th>Item</th><th class="n">Qty</th><th class="n">Price<//...	Group of header rows.

Line	What it does
<tbody>	Group of data rows.
<tr><td>Learn HTML</td><td class="n">1</td><td class="n">120 EGP</t...	A table row.
<tr><td>CSS in Practice</td><td class="n">1</td><td class="n">150 E...	A data cell.
<tfoot><tr><th colspan="2">Total</th><td class="n">see items</td><//...	Group of footer rows (totals).

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 2rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: 1rem;	Space between grid or flex items without extra margins.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-align: right;	Right-aligns inline content, typical for numbers.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	The line around the element: width, style and colour.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
font-weight: 700;	Thickness of the text.
border-top: 2px solid var(--ink);	A top border used as an accent or separator.

Declaration	What it does
@media print { .invoice { border: 0; margin: 0; max-width: none; } }	Removes the default border (for example on an iframe or button).

Check your work

- Numbers right-aligned
- Total row in tfoot
- Fits on one printed page
- Date has datetime

Exercises

1. Calculate the total with JavaScript.
2. Add a logo image.
3. Add a QR code image for payment.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 577: Printable invoice for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 2 | Files: index.html, styles.css

Brief

Create a clean invoice with a header row, a table using tfoot and colspan for the total, right-aligned numbers and print styles.

Learning goals

- Use tfoot and colspan
- Align numbers with tabular figures
- Design for print

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, b, time, table, thead, tbody, tfoot, th, td	justify-content: space-between, colspan, font-variant-numeric, border-top, @media print

Build guide

1. Write the header with two blocks: seller and invoice metadata.
2. Write the table with thead, tbody and a tfoot total row using colspan="2".
3. Add class n to numeric cells.
4. Flex the header with space-between.
5. Right-align .n cells.
6. Print preview and remove the border in @media print.

Project 577: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Invoice 2026-041 - Nile Bakery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="invoice">
    <header>
      <div><h1>Nile Bakery</h1><p>Cairo, Egypt</p></div>
      <div class="meta"><p><b>Invoice</b> 2026-041</p><p><b>Date</b>
<time datetime="2026-09-11">11 Sep 2026</time></p></div>
    </header>
    <p><b>Bill to:</b> Customer name, Cairo</p>
    <table>
      <thead><tr><th>Item</th><th class="n">Qty</th><th
class="n">Price</th></tr></thead>
      <tbody>
        <tr><td>Sourdough loaf</td><td class="n">1</td><td
class="n">60 EGP</td></tr>
        <tr><td>Croissant</td><td class="n">1</td><td class="n">35
EGP</td></tr>
        <tr><td>Date cookies</td><td class="n">1</td><td class="n">80
EGP</td></tr>
      </tbody>
      <tfoot><tr><th colspan="2">Total</th><td class="n">see items</
td></tr></tfoot>
    </table>
    <p class="thanks">Thank you for your business.</p>
  </main>
</body>
</html>
```

Project 577: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.invoice { max-width: 46rem; margin: 2rem auto; padding: 2rem; border:
 1px solid var(--line); }
header { display: flex; justify-content: space-between; flex-wrap:
wrap; gap: 1rem; border-bottom: 3px solid var(--brand); padding-
bottom: 1rem; }
```

```
h1 { margin: 0; color: var(--brand); }
.meta p { margin: .1rem 0; text-align: right; }
table { width: 100%; border-collapse: collapse; margin-top: 1.5rem; }
th, td { padding: .6rem; border-bottom: 1px solid var(--line); text-
align: left; }
.n { text-align: right; font-variant-numeric: tabular-nums; }
tfoot th, tfoot td { font-weight: 700; border-top: 2px solid var(--
ink); border-bottom: 0; }
.thanks { margin-top: 2rem; color: var(--muted); font-style: italic; }
@media print { .invoice { border: 0; margin: 0; max-width: none; } }
```

Project 577 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Invoice 2026-041 - Nile Bakery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="invoice">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Nile Bakery Cairo, Egypt	The main heading; only one per page.
Invoice 2026-041 Date <tim...	A paragraph of text.
Bill to: Customer name, Cairo	Keyword or name drawn to attention without extra importance.
<table>	Tabular data in rows and columns.
<thead><tr><th>Item</th><th class="n">Qty</th><th class="n">Price<//...	Group of header rows.

Line	What it does
<tbody>	Group of data rows.
<tr><td>Sourdough loaf</td><td class="n">1</td><td class="n">60 EGP...	A table row.
<tr><td>Croissant</td><td class="n">1</td><td class="n">35 EGP</td>...	A data cell.
<tfoot><tr><th colspan="2">Total</th><td class="n">see items</td><//...	Group of footer rows (totals).

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 2rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: 1rem;	Space between grid or flex items without extra margins.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-align: right;	Right-aligns inline content, typical for numbers.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	The line around the element: width, style and colour.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
font-weight: 700;	Thickness of the text.
border-top: 2px solid var(--ink);	A top border used as an accent or separator.

Declaration	What it does
@media print { .invoice { border: 0; margin: 0; max-width: none; } }	Removes the default border (for example on an iframe or button).

Check your work

- Numbers right-aligned
- Total row in tfoot
- Fits on one printed page
- Date has datetime

Exercises

1. Calculate the total with JavaScript.
2. Add a logo image.
3. Add a QR code image for payment.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 578: Printable invoice for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 2 | Files: index.html, styles.css

Brief

Create a clean invoice with a header row, a table using tfoot and colspan for the total, right-aligned numbers and print styles.

Learning goals

- Use tfoot and colspan
- Align numbers with tabular figures
- Design for print

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, b, time, table, thead, tbody, tfoot, th, td	justify-content: space-between, colspan, font-variant-numeric, border-top, @media print

Build guide

1. Write the header with two blocks: seller and invoice metadata.
2. Write the table with thead, tbody and a tfoot total row using colspan="2".
3. Add class n to numeric cells.
4. Flex the header with space-between.
5. Right-align .n cells.
6. Print preview and remove the border in @media print.

Project 578: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Invoice 2026-041 - Pyramid Fitness</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="invoice">
    <header>
      <div><h1>Pyramid Fitness</h1><p>6th of October, Egypt</p></div>
      <div class="meta"><p><b>Invoice</b> 2026-041</p><p><b>Date</b>
<time datetime="2026-09-11">11 Sep 2026</time></p></div>
    </header>
    <p><b>Bill to:</b> Customer name, 6th of October</p>
    <table>
      <thead><tr><th>Item</th><th class="n">Qty</th><th
class="n">Price</th></tr></thead>
      <tbody>
        <tr><td>Morning yoga</td><td class="n">1</td><td
class="n">100 EGP</td></tr>
        <tr><td>Strength circuit</td><td class="n">1</td><td
class="n">120 EGP</td></tr>
        <tr><td>Spinning</td><td class="n">1</td><td class="n">110
EGP</td></tr>
      </tbody>
      <tfoot><tr><th colspan="2">Total</th><td class="n">see items</
td></tr></tfoot>
    </table>
    <p class="thanks">Thank you for your business.</p>
  </main>
</body>
</html>
```

Project 578: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.invoice { max-width: 46rem; margin: 2rem auto; padding: 2rem; border:
 1px solid var(--line); }
header { display: flex; justify-content: space-between; flex-wrap:
wrap; gap: 1rem; border-bottom: 3px solid var(--brand); padding-
bottom: 1rem; }
```

```
h1 { margin: 0; color: var(--brand); }
.meta p { margin: .1rem 0; text-align: right; }
table { width: 100%; border-collapse: collapse; margin-top: 1.5rem; }
th, td { padding: .6rem; border-bottom: 1px solid var(--line); text-
align: left; }
.n { text-align: right; font-variant-numeric: tabular-nums; }
tfoot th, tfoot td { font-weight: 700; border-top: 2px solid var(--
ink); border-bottom: 0; }
.thanks { margin-top: 2rem; color: var(--muted); font-style: italic; }
@media print { .invoice { border: 0; margin: 0; max-width: none; } }
```

Project 578 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Invoice 2026-041 - Pyramid Fitness</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="invoice">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Pyramid Fitness 6th of October, Egypt	The main heading; only one per page.
Invoice 2026-041 Date <tim...	A paragraph of text.
Bill to: Customer name, 6th of October	Keyword or name drawn to attention without extra importance.
<table>	Tabular data in rows and columns.
<thead><tr><th>Item</th><th class="n">Qty</th><th class="n">Price<//...	Group of header rows.

Line	What it does
<tbody>	Group of data rows.
<tr><td>Morning yoga</td><td class="n">1</td><td class="n">100 EGP<...	A table row.
<tr><td>Strength circuit</td><td class="n">1</td><td class="n">120 ...	A data cell.
<tfoot><tr><th colspan="2">Total</th><td class="n">see items</td><//...	Group of footer rows (totals).

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 2rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: 1rem;	Space between grid or flex items without extra margins.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-align: right;	Right-aligns inline content, typical for numbers.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	The line around the element: width, style and colour.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
font-weight: 700;	Thickness of the text.
border-top: 2px solid var(--ink);	A top border used as an accent or separator.

Declaration	What it does
@media print { .invoice { border: 0; margin: 0; max-width: none; } }	Removes the default border (for example on an iframe or button).

Check your work

- Numbers right-aligned
- Total row in tfoot
- Fits on one printed page
- Date has datetime

Exercises

1. Calculate the total with JavaScript.
2. Add a logo image.
3. Add a QR code image for payment.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 579: Printable invoice for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 2 | Files: index.html, styles.css

Brief

Create a clean invoice with a header row, a table using tfoot and colspan for the total, right-aligned numbers and print styles.

Learning goals

- Use tfoot and colspan
- Align numbers with tabular figures
- Design for print

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, b, time, table, thead, tbody, tfoot, th, td	justify-content: space-between, colspan, font-variant-numeric, border-top, @media print

Build guide

1. Write the header with two blocks: seller and invoice metadata.
2. Write the table with thead, tbody and a tfoot total row using colspan="2".
3. Add class n to numeric cells.
4. Flex the header with space-between.
5. Right-align .n cells.
6. Print preview and remove the border in @media print.

Project 579: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Invoice 2026-041 - Delta Dental Clinic</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="invoice">
    <header>
      <div><h1>Delta Dental Clinic</h1><p>Mansoura, Egypt</p></div>
      <div class="meta"><p><b>Invoice</b> 2026-041</p><p><b>Date</b>
<time datetime="2026-09-11">11 Sep 2026</time></p></div>
    </header>
    <p><b>Bill to:</b> Customer name, Mansoura</p>
    <table>
      <thead><tr><th>Item</th><th class="n">Qty</th><th
class="n">Price</th></tr></thead>
      <tbody>
        <tr><td>Check-up</td><td class="n">1</td><td class="n">300
EGP</td></tr>
        <tr><td>Whitening</td><td class="n">1</td><td class="n">1500
EGP</td></tr>
        <tr><td>Filling</td><td class="n">1</td><td class="n">600
EGP</td></tr>
      </tbody>
      <tfoot><tr><th colspan="2">Total</th><td class="n">see items</
td></tr></tfoot>
    </table>
    <p class="thanks">Thank you for your business.</p>
  </main>
</body>
</html>
```

Project 579: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.invoice { max-width: 46rem; margin: 2rem auto; padding: 2rem; border:
 1px solid var(--line); }
header { display: flex; justify-content: space-between; flex-wrap:
wrap; gap: 1rem; border-bottom: 3px solid var(--brand); padding-
bottom: 1rem; }
```

```
h1 { margin: 0; color: var(--brand); }
.meta p { margin: .1rem 0; text-align: right; }
table { width: 100%; border-collapse: collapse; margin-top: 1.5rem; }
th, td { padding: .6rem; border-bottom: 1px solid var(--line); text-
align: left; }
.n { text-align: right; font-variant-numeric: tabular-nums; }
tfoot th, tfoot td { font-weight: 700; border-top: 2px solid var(--
ink); border-bottom: 0; }
.thanks { margin-top: 2rem; color: var(--muted); font-style: italic; }
@media print { .invoice { border: 0; margin: 0; max-width: none; } }
```

Project 579 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Invoice 2026-041 - Delta Dental Clinic</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="invoice">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Delta Dental Clinic Mansoura, Egypt	The main heading; only one per page.
Invoice 2026-041 Date <tim...	A paragraph of text.
Bill to: Customer name, Mansoura	Keyword or name drawn to attention without extra importance.
<table>	Tabular data in rows and columns.
<thead><tr><th>Item</th><th class="n">Qty</th><th class="n">Price<//...	Group of header rows.

Line	What it does
<tbody>	Group of data rows.
<tr><td>Check-up</td><td class="n">1</td><td class="n">300 EGP</td>...	A table row.
<tr><td>Whitening</td><td class="n">1</td><td class="n">1500 EGP</t...	A data cell.
<tfoot><tr><th colspan="2">Total</th><td class="n">see items</td><//...	Group of footer rows (totals).

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 2rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: 1rem;	Space between grid or flex items without extra margins.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-align: right;	Right-aligns inline content, typical for numbers.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	The line around the element: width, style and colour.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
font-weight: 700;	Thickness of the text.
border-top: 2px solid var(--ink);	A top border used as an accent or separator.

Declaration	What it does
@media print { .invoice { border: 0; margin: 0; max-width: none; } }	Removes the default border (for example on an iframe or button).

Check your work

- Numbers right-aligned
- Total row in tfoot
- Fits on one printed page
- Date has datetime

Exercises

1. Calculate the total with JavaScript.
2. Add a logo image.
3. Add a QR code image for payment.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 580: Printable invoice for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 2 | Files: index.html, styles.css

Brief

Create a clean invoice with a header row, a table using tfoot and colspan for the total, right-aligned numbers and print styles.

Learning goals

- Use tfoot and colspan
- Align numbers with tabular figures
- Design for print

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, b, time, table, thead, tbody, tfoot, th, td	justify-content: space-between, colspan, font-variant-numeric, border-top, @media print

Build guide

1. Write the header with two blocks: seller and invoice metadata.
2. Write the table with thead, tbody and a tfoot total row using colspan="2".
3. Add class n to numeric cells.
4. Flex the header with space-between.
5. Right-align .n cells.
6. Print preview and remove the border in @media print.

Project 580: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Invoice 2026-041 - Red Sea Travel</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="invoice">
    <header>
      <div><h1>Red Sea Travel</h1><p>Hurghada, Egypt</p></div>
      <div class="meta"><p><b>Invoice</b> 2026-041</p><p><b>Date</b>
<time datetime="2026-09-11">11 Sep 2026</time></p></div>
    </header>
    <p><b>Bill to:</b> Customer name, Hurghada</p>
    <table>
      <thead><tr><th>Item</th><th class="n">Qty</th><th
class="n">Price</th></tr></thead>
      <tbody>
        <tr><td>Luxor day trip</td><td class="n">1</td><td
class="n">1200 EGP</td></tr>
        <tr><td>Snorkelling</td><td class="n">1</td><td class="n">700
EGP</td></tr>
        <tr><td>Desert safari</td><td class="n">1</td><td
class="n">900 EGP</td></tr>
      </tbody>
      <tfoot><tr><th colspan="2">Total</th><td class="n">see items</
td></tr></tfoot>
    </table>
    <p class="thanks">Thank you for your business.</p>
  </main>
</body>
</html>
```

Project 580: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.invoice { max-width: 46rem; margin: 2rem auto; padding: 2rem; border:
 1px solid var(--line); }
header { display: flex; justify-content: space-between; flex-wrap:
wrap; gap: 1rem; border-bottom: 3px solid var(--brand); padding-
bottom: 1rem; }
```

```
h1 { margin: 0; color: var(--brand); }
.meta p { margin: .1rem 0; text-align: right; }
table { width: 100%; border-collapse: collapse; margin-top: 1.5rem; }
th, td { padding: .6rem; border-bottom: 1px solid var(--line); text-
align: left; }
.n { text-align: right; font-variant-numeric: tabular-nums; }
tfoot th, tfoot td { font-weight: 700; border-top: 2px solid var(--
ink); border-bottom: 0; }
.thanks { margin-top: 2rem; color: var(--muted); font-style: italic; }
@media print { .invoice { border: 0; margin: 0; max-width: none; } }
```

Project 580 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Invoice 2026-041 - Red Sea Travel</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="invoice">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Red Sea Travel Hurghada, Egypt	The main heading; only one per page.
Invoice 2026-041 Date <tim...	A paragraph of text.
Bill to: Customer name, Hurghada	Keyword or name drawn to attention without extra importance.
<table>	Tabular data in rows and columns.
<thead><tr><th>Item</th><th class="n">Qty</th><th class="n">Price<//...	Group of header rows.

Line	What it does
<tbody>	Group of data rows.
<tr><td>Luxor day trip</td><td class="n">1</td><td class="n">1200 E...	A table row.
<tr><td>Snorkelling</td><td class="n">1</td><td class="n">700 EGP<//...	A data cell.
<tfoot><tr><th colspan="2">Total</th><td class="n">see items</td><//...	Group of footer rows (totals).

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 2rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: 1rem;	Space between grid or flex items without extra margins.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-align: right;	Right-aligns inline content, typical for numbers.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	The line around the element: width, style and colour.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
font-weight: 700;	Thickness of the text.
border-top: 2px solid var(--ink);	A top border used as an accent or separator.

Declaration	What it does
@media print { .invoice { border: 0; margin: 0; max-width: none; } }	Removes the default border (for example on an iframe or button).

Check your work

- Numbers right-aligned
- Total row in tfoot
- Fits on one printed page
- Date has datetime

Exercises

1. Calculate the total with JavaScript.
2. Add a logo image.
3. Add a QR code image for payment.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 581: Printable invoice for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Create a clean invoice with a header row, a table using tfoot and colspan for the total, right-aligned numbers and print styles.

Learning goals

- Use tfoot and colspan
- Align numbers with tabular figures
- Design for print

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, b, time, table, thead, tbody, tfoot, th, td	justify-content: space-between, colspan, font-variant-numeric, border-top, @media print

Build guide

1. Write the header with two blocks: seller and invoice metadata.
2. Write the table with thead, tbody and a tfoot total row using colspan="2".
3. Add class n to numeric cells.
4. Flex the header with space-between.
5. Right-align .n cells.
6. Print preview and remove the border in @media print.

Project 581: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Invoice 2026-041 - Lotus Language School</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="invoice">
    <header>
      <div><h1>Lotus Language School</h1><p>Alexandria, Egypt</p></
div>
      <div class="meta"><p><b>Invoice</b> 2026-041</p><p><b>Date</b>
<time datetime="2026-09-11">11 Sep 2026</time></p></div>
    </header>
    <p><b>Bill to:</b> Customer name, Alexandria</p>
    <table>
      <thead><tr><th>Item</th><th class="n">Qty</th><th
class="n">Price</th></tr></thead>
      <tbody>
        <tr><td>English A1</td><td class="n">1</td><td class="n">1800
EGP</td></tr>
        <tr><td>French B1</td><td class="n">1</td><td class="n">2200
EGP</td></tr>
        <tr><td>German A2</td><td class="n">1</td><td class="n">2000
EGP</td></tr>
      </tbody>
      <tfoot><tr><th colspan="2">Total</th><td class="n">see items</
td></tr></tfoot>
    </table>
    <p class="thanks">Thank you for your business.</p>
  </main>
</body>
</html>
```

Project 581: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.invoice { max-width: 46rem; margin: 2rem auto; padding: 2rem; border:
 1px solid var(--line); }
header { display: flex; justify-content: space-between; flex-wrap:
wrap; gap: 1rem; border-bottom: 3px solid var(--brand); padding-
```

```
bottom: 1rem; }
h1 { margin: 0; color: var(--brand); }
.meta p { margin: .1rem 0; text-align: right; }
table { width: 100%; border-collapse: collapse; margin-top: 1.5rem; }
th, td { padding: .6rem; border-bottom: 1px solid var(--line); text-
align: left; }
.n { text-align: right; font-variant-numeric: tabular-nums; }
tfoot th, tfoot td { font-weight: 700; border-top: 2px solid var(--
ink); border-bottom: 0; }
.thanks { margin-top: 2rem; color: var(--muted); font-style: italic; }
@media print { .invoice { border: 0; margin: 0; max-width: none; } }
```

Project 581 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Invoice 2026-041 - Lotus Language School</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="invoice">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Lotus Language School Alexandria, Egypt	The main heading; only one per page.
Invoice 2026-041 Date <tim...	A paragraph of text.
Bill to: Customer name, Alexandria	Keyword or name drawn to attention without extra importance.
<table>	Tabular data in rows and columns.
<thead><tr><th>Item</th><th class="n">Qty</th><th class="n">Price<//...	Group of header rows.

Line	What it does
<tbody>	Group of data rows.
<tr><td>English A1</td><td class="n">1</td><td class="n">1800 EGP<//...	A table row.
<tr><td>French B1</td><td class="n">1</td><td class="n">2200 EGP</t...	A data cell.
<tfoot><tr><th colspan="2">Total</th><td class="n">see items</td><//...	Group of footer rows (totals).

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 2rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: 1rem;	Space between grid or flex items without extra margins.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-align: right;	Right-aligns inline content, typical for numbers.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	The line around the element: width, style and colour.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
font-weight: 700;	Thickness of the text.
border-top: 2px solid var(--ink);	A top border used as an accent or separator.

Declaration	What it does
@media print { .invoice { border: 0; margin: 0; max-width: none; } }	Removes the default border (for example on an iframe or button).

Check your work

- Numbers right-aligned
- Total row in tfoot
- Fits on one printed page
- Date has datetime

Exercises

1. Calculate the total with JavaScript.
2. Add a logo image.
3. Add a QR code image for payment.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 582: Printable invoice for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 2 | Files: index.html, styles.css

Brief

Create a clean invoice with a header row, a table using tfoot and colspan for the total, right-aligned numbers and print styles.

Learning goals

- Use tfoot and colspan
- Align numbers with tabular figures
- Design for print

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, b, time, table, thead, tbody, tfoot, th, td	justify-content: space-between, colspan, font-variant-numeric, border-top, @media print

Build guide

1. Write the header with two blocks: seller and invoice metadata.
2. Write the table with thead, tbody and a tfoot total row using colspan="2".
3. Add class n to numeric cells.
4. Flex the header with space-between.
5. Right-align .n cells.
6. Print preview and remove the border in @media print.

Project 582: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Invoice 2026-041 - Green Leaf Cafe</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="invoice">
    <header>
      <div><h1>Green Leaf Cafe</h1><p>Zamalek, Egypt</p></div>
      <div class="meta"><p><b>Invoice</b> 2026-041</p><p><b>Date</b>
<time datetime="2026-09-11">11 Sep 2026</time></p></div>
    </header>
    <p><b>Bill to:</b> Customer name, Zamalek</p>
    <table>
      <thead><tr><th>Item</th><th class="n">Qty</th><th
class="n">Price</th></tr></thead>
      <tbody>
        <tr><td>Flat white</td><td class="n">1</td><td class="n">55
EGP</td></tr>
        <tr><td>Cold brew</td><td class="n">1</td><td class="n">60
EGP</td></tr>
        <tr><td>Hibiscus iced tea</td><td class="n">1</td><td
class="n">40 EGP</td></tr>
      </tbody>
      <tfoot><tr><th colspan="2">Total</th><td class="n">see items</
td></tr></tfoot>
    </table>
    <p class="thanks">Thank you for your business.</p>
  </main>
</body>
</html>
```

Project 582: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.invoice { max-width: 46rem; margin: 2rem auto; padding: 2rem; border:
 1px solid var(--line); }
header { display: flex; justify-content: space-between; flex-wrap:
wrap; gap: 1rem; border-bottom: 3px solid var(--brand); padding-
bottom: 1rem; }
```

```
h1 { margin: 0; color: var(--brand); }
.meta p { margin: .1rem 0; text-align: right; }
table { width: 100%; border-collapse: collapse; margin-top: 1.5rem; }
th, td { padding: .6rem; border-bottom: 1px solid var(--line); text-
align: left; }
.n { text-align: right; font-variant-numeric: tabular-nums; }
tfoot th, tfoot td { font-weight: 700; border-top: 2px solid var(--
ink); border-bottom: 0; }
.thanks { margin-top: 2rem; color: var(--muted); font-style: italic; }
@media print { .invoice { border: 0; margin: 0; max-width: none; } }
```

Project 582 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Invoice 2026-041 - Green Leaf Cafe</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="invoice">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Green Leaf Cafe Zamalek, Egypt	The main heading; only one per page.
Invoice 2026-041 Date <tim...	A paragraph of text.
Bill to: Customer name, Zamalek	Keyword or name drawn to attention without extra importance.
<table>	Tabular data in rows and columns.
<thead><tr><th>Item</th><th class="n">Qty</th><th class="n">Price<//...	Group of header rows.

Line	What it does
<tbody>	Group of data rows.
<tr><td>Flat white</td><td class="n">1</td><td class="n">55 EGP</td...	A table row.
<tr><td>Cold brew</td><td class="n">1</td><td class="n">60 EGP</td>...	A data cell.
<tfoot><tr><th colspan="2">Total</th><td class="n">see items</td><//...	Group of footer rows (totals).

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 2rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: 1rem;	Space between grid or flex items without extra margins.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-align: right;	Right-aligns inline content, typical for numbers.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	The line around the element: width, style and colour.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
font-weight: 700;	Thickness of the text.
border-top: 2px solid var(--ink);	A top border used as an accent or separator.

Declaration	What it does
@media print { .invoice { border: 0; margin: 0; max-width: none; } }	Removes the default border (for example on an iframe or button).

Check your work

- Numbers right-aligned
- Total row in tfoot
- Fits on one printed page
- Date has datetime

Exercises

1. Calculate the total with JavaScript.
2. Add a logo image.
3. Add a QR code image for payment.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 583: Printable invoice for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 2 | Files: index.html, styles.css

Brief

Create a clean invoice with a header row, a table using tfoot and colspan for the total, right-aligned numbers and print styles.

Learning goals

- Use tfoot and colspan
- Align numbers with tabular figures
- Design for print

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, b, time, table, thead, tbody, tfoot, th, td	justify-content: space-between, colspan, font-variant-numeric, border-top, @media print

Build guide

1. Write the header with two blocks: seller and invoice metadata.
2. Write the table with thead, tbody and a tfoot total row using colspan="2".
3. Add class n to numeric cells.
4. Flex the header with space-between.
5. Right-align .n cells.
6. Print preview and remove the border in @media print.

Project 583: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Invoice 2026-041 - Sinai Trekking Club</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="invoice">
    <header>
      <div><h1>Sinai Trekking Club</h1><p>Saint Catherine, Egypt</p></
div>
      <div class="meta"><p><b>Invoice</b> 2026-041</p><p><b>Date</b>
<time datetime="2026-09-11">11 Sep 2026</time></p></div>
    </header>
    <p><b>Bill to:</b> Customer name, Saint Catherine</p>
    <table>
      <thead><tr><th>Item</th><th class="n">Qty</th><th
class="n">Price</th></tr></thead>
      <tbody>
        <tr><td>Mount Sinai sunrise</td><td class="n">1</td><td
class="n">400 EGP</td></tr>
        <tr><td>Blue Desert loop</td><td class="n">1</td><td
class="n">250 EGP</td></tr>
        <tr><td>Wadi Gnai</td><td class="n">1</td><td class="n">300
EGP</td></tr>
      </tbody>
      <tfoot><tr><th colspan="2">Total</th><td class="n">see items</
td></tr></tfoot>
    </table>
    <p class="thanks">Thank you for your business.</p>
  </main>
</body>
</html>
```

Project 583: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.invoice { max-width: 46rem; margin: 2rem auto; padding: 2rem; border:
 1px solid var(--line); }
header { display: flex; justify-content: space-between; flex-wrap:
wrap; gap: 1rem; border-bottom: 3px solid var(--brand); padding-
```

```
bottom: 1rem; }
h1 { margin: 0; color: var(--brand); }
.meta p { margin: .1rem 0; text-align: right; }
table { width: 100%; border-collapse: collapse; margin-top: 1.5rem; }
th, td { padding: .6rem; border-bottom: 1px solid var(--line); text-
align: left; }
.n { text-align: right; font-variant-numeric: tabular-nums; }
tfoot th, tfoot td { font-weight: 700; border-top: 2px solid var(--
ink); border-bottom: 0; }
.thanks { margin-top: 2rem; color: var(--muted); font-style: italic; }
@media print { .invoice { border: 0; margin: 0; max-width: none; } }
```

Project 583 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Invoice 2026-041 - Sinai Trekking Club</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="invoice">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Sinai Trekking Club Saint Catherine, Egypt	The main heading; only one per page.
Invoice 2026-041 Date <tim...	A paragraph of text.
Bill to: Customer name, Saint Catherine	Keyword or name drawn to attention without extra importance.
<table>	Tabular data in rows and columns.
<thead><tr><th>Item</th><th class="n">Qty</th><th class="n">Price<//...	Group of header rows.

Line	What it does
<tbody>	Group of data rows.
<tr><td>Mount Sinai sunrise</td><td class="n">1</td><td class="n">4...	A table row.
<tr><td>Blue Desert loop</td><td class="n">1</td><td class="n">250 ...	A data cell.
<tfoot><tr><th colspan="2">Total</th><td class="n">see items</td><//...	Group of footer rows (totals).

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 2rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: 1rem;	Space between grid or flex items without extra margins.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-align: right;	Right-aligns inline content, typical for numbers.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	The line around the element: width, style and colour.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
font-weight: 700;	Thickness of the text.
border-top: 2px solid var(--ink);	A top border used as an accent or separator.

Declaration	What it does
@media print { .invoice { border: 0; margin: 0; max-width: none; } }	Removes the default border (for example on an iframe or button).

Check your work

- Numbers right-aligned
- Total row in tfoot
- Fits on one printed page
- Date has datetime

Exercises

1. Calculate the total with JavaScript.
2. Add a logo image.
3. Add a QR code image for payment.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 584: Printable invoice for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 2 | Files: index.html, styles.css

Brief

Create a clean invoice with a header row, a table using tfoot and colspan for the total, right-aligned numbers and print styles.

Learning goals

- Use tfoot and colspan
- Align numbers with tabular figures
- Design for print

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, b, time, table, thead, tbody, tfoot, th, td	justify-content: space-between, colspan, font-variant-numeric, border-top, @media print

Build guide

1. Write the header with two blocks: seller and invoice metadata.
2. Write the table with thead, tbody and a tfoot total row using colspan="2".
3. Add class n to numeric cells.
4. Flex the header with space-between.
5. Right-align .n cells.
6. Print preview and remove the border in @media print.

Project 584: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Invoice 2026-041 - Horizon Photography</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="invoice">
    <header>
      <div><h1>Horizon Photography</h1><p>Maadi, Egypt</p></div>
      <div class="meta"><p><b>Invoice</b> 2026-041</p><p><b>Date</b>
<time datetime="2026-09-11">11 Sep 2026</time></p></div>
    </header>
    <p><b>Bill to:</b> Customer name, Maadi</p>
    <table>
      <thead><tr><th>Item</th><th class="n">Qty</th><th
class="n">Price</th></tr></thead>
      <tbody>
        <tr><td>Portrait session</td><td class="n">1</td><td
class="n">1200 EGP</td></tr>
        <tr><td>Wedding day</td><td class="n">1</td><td
class="n">15000 EGP</td></tr>
        <tr><td>Product shoot</td><td class="n">1</td><td
class="n">900 EGP</td></tr>
      </tbody>
      <tfoot><tr><th colspan="2">Total</th><td class="n">see items</
td></tr></tfoot>
    </table>
    <p class="thanks">Thank you for your business.</p>
  </main>
</body>
</html>
```

Project 584: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.invoice { max-width: 46rem; margin: 2rem auto; padding: 2rem; border:
 1px solid var(--line); }
header { display: flex; justify-content: space-between; flex-wrap:
wrap; gap: 1rem; border-bottom: 3px solid var(--brand); padding-
bottom: 1rem; }
```

```
h1 { margin: 0; color: var(--brand); }
.meta p { margin: .1rem 0; text-align: right; }
table { width: 100%; border-collapse: collapse; margin-top: 1.5rem; }
th, td { padding: .6rem; border-bottom: 1px solid var(--line); text-
align: left; }
.n { text-align: right; font-variant-numeric: tabular-nums; }
tfoot th, tfoot td { font-weight: 700; border-top: 2px solid var(--
ink); border-bottom: 0; }
.thanks { margin-top: 2rem; color: var(--muted); font-style: italic; }
@media print { .invoice { border: 0; margin: 0; max-width: none; } }
```

Project 584 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Invoice 2026-041 - Horizon Photography</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="invoice">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Horizon Photography Maadi, Egypt	The main heading; only one per page.
Invoice 2026-041 Date <tim...	A paragraph of text.
Bill to: Customer name, Maadi	Keyword or name drawn to attention without extra importance.
<table>	Tabular data in rows and columns.
<thead><tr><th>Item</th><th class="n">Qty</th><th class="n">Price<//...	Group of header rows.

Line	What it does
<tbody>	Group of data rows.
<tr><td>Portrait session</td><td class="n">1</td><td class="n">1200...	A table row.
<tr><td>Wedding day</td><td class="n">1</td><td class="n">15000 EGP...	A data cell.
<tfoot><tr><th colspan="2">Total</th><td class="n">see items</td><//...	Group of footer rows (totals).

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 2rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: 1rem;	Space between grid or flex items without extra margins.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-align: right;	Right-aligns inline content, typical for numbers.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	The line around the element: width, style and colour.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
font-weight: 700;	Thickness of the text.
border-top: 2px solid var(--ink);	A top border used as an accent or separator.

Declaration	What it does
@media print { .invoice { border: 0; margin: 0; max-width: none; } }	Removes the default border (for example on an iframe or button).

Check your work

- Numbers right-aligned
- Total row in tfoot
- Fits on one printed page
- Date has datetime

Exercises

1. Calculate the total with JavaScript.
2. Add a logo image.
3. Add a QR code image for payment.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 585: Printable invoice for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 2 | Files: index.html, styles.css

Brief

Create a clean invoice with a header row, a table using tfoot and colspan for the total, right-aligned numbers and print styles.

Learning goals

- Use tfoot and colspan
- Align numbers with tabular figures
- Design for print

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, b, time, table, thead, tbody, tfoot, th, td	justify-content: space-between, colspan, font-variant-numeric, border-top, @media print

Build guide

1. Write the header with two blocks: seller and invoice metadata.
2. Write the table with thead, tbody and a tfoot total row using colspan="2".
3. Add class n to numeric cells.
4. Flex the header with space-between.
5. Right-align .n cells.
6. Print preview and remove the border in @media print.

Project 585: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Invoice 2026-041 - Papyrus Stationery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="invoice">
    <header>
      <div><h1>Papyrus Stationery</h1><p>Heliopolis, Egypt</p></div>
      <div class="meta"><p><b>Invoice</b> 2026-041</p><p><b>Date</b>
<time datetime="2026-09-11">11 Sep 2026</time></p></div>
    </header>
    <p><b>Bill to:</b> Customer name, Heliopolis</p>
    <table>
      <thead><tr><th>Item</th><th class="n">Qty</th><th
class="n">Price</th></tr></thead>
      <tbody>
        <tr><td>Dotted notebook</td><td class="n">1</td><td
class="n">140 EGP</td></tr>
        <tr><td>Fountain pen</td><td class="n">1</td><td
class="n">350 EGP</td></tr>
        <tr><td>Washi tape set</td><td class="n">1</td><td
class="n">90 EGP</td></tr>
      </tbody>
      <tfoot><tr><th colspan="2">Total</th><td class="n">see items</
td></tr></tfoot>
    </table>
    <p class="thanks">Thank you for your business.</p>
  </main>
</body>
</html>
```

Project 585: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.invoice { max-width: 46rem; margin: 2rem auto; padding: 2rem; border:
 1px solid var(--line); }
header { display: flex; justify-content: space-between; flex-wrap:
wrap; gap: 1rem; border-bottom: 3px solid var(--brand); padding-
bottom: 1rem; }
```

```
h1 { margin: 0; color: var(--brand); }
.meta p { margin: .1rem 0; text-align: right; }
table { width: 100%; border-collapse: collapse; margin-top: 1.5rem; }
th, td { padding: .6rem; border-bottom: 1px solid var(--line); text-
align: left; }
.n { text-align: right; font-variant-numeric: tabular-nums; }
tfoot th, tfoot td { font-weight: 700; border-top: 2px solid var(--
ink); border-bottom: 0; }
.thanks { margin-top: 2rem; color: var(--muted); font-style: italic; }
@media print { .invoice { border: 0; margin: 0; max-width: none; } }
```

Project 585 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Invoice 2026-041 - Papyrus Stationery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="invoice">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Papyrus Stationery Heliopolis, Egypt	The main heading; only one per page.
Invoice 2026-041 Date <tim...	A paragraph of text.
Bill to: Customer name, Heliopolis	Keyword or name drawn to attention without extra importance.
<table>	Tabular data in rows and columns.
<thead><tr><th>Item</th><th class="n">Qty</th><th class="n">Price<//...	Group of header rows.

Line	What it does
<tbody>	Group of data rows.
<tr><td>Dotted notebook</td><td class="n">1</td><td class="n">140 E...	A table row.
<tr><td>Fountain pen</td><td class="n">1</td><td class="n">350 EGP<...	A data cell.
<tfoot><tr><th colspan="2">Total</th><td class="n">see items</td><//...	Group of footer rows (totals).

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 2rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: 1rem;	Space between grid or flex items without extra margins.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-align: right;	Right-aligns inline content, typical for numbers.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	The line around the element: width, style and colour.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
font-weight: 700;	Thickness of the text.
border-top: 2px solid var(--ink);	A top border used as an accent or separator.

Declaration	What it does
@media print { .invoice { border: 0; margin: 0; max-width: none; } }	Removes the default border (for example on an iframe or button).

Check your work

- Numbers right-aligned
- Total row in tfoot
- Fits on one printed page
- Date has datetime

Exercises

1. Calculate the total with JavaScript.
2. Add a logo image.
3. Add a QR code image for payment.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 586: Printable invoice for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 2 | Files: index.html, styles.css

Brief

Create a clean invoice with a header row, a table using tfoot and colspan for the total, right-aligned numbers and print styles.

Learning goals

- Use tfoot and colspan
- Align numbers with tabular figures
- Design for print

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, b, time, table, thead, tbody, tfoot, th, td	justify-content: space-between, colspan, font-variant-numeric, border-top, @media print

Build guide

1. Write the header with two blocks: seller and invoice metadata.
2. Write the table with thead, tbody and a tfoot total row using colspan="2".
3. Add class n to numeric cells.
4. Flex the header with space-between.
5. Right-align .n cells.
6. Print preview and remove the border in @media print.

Project 586: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Invoice 2026-041 - Oasis Plant Nursery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="invoice">
    <header>
      <div><h1>Oasis Plant Nursery</h1><p>Sheikh Zayed, Egypt</p></
div>
      <div class="meta"><p><b>Invoice</b> 2026-041</p><p><b>Date</b>
<time datetime="2026-09-11">11 Sep 2026</time></p></div>
    </header>
    <p><b>Bill to:</b> Customer name, Sheikh Zayed</p>
    <table>
      <thead><tr><th>Item</th><th class="n">Qty</th><th
class="n">Price</th></tr></thead>
      <tbody>
        <tr><td>Monstera</td><td class="n">1</td><td class="n">250
EGP</td></tr>
        <tr><td>Snake plant</td><td class="n">1</td><td class="n">120
EGP</td></tr>
        <tr><td>Basil pot</td><td class="n">1</td><td class="n">45
EGP</td></tr>
      </tbody>
      <tfoot><tr><th colspan="2">Total</th><td class="n">see items</
td></tr></tfoot>
    </table>
    <p class="thanks">Thank you for your business.</p>
  </main>
</body>
</html>
```

Project 586: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.invoice { max-width: 46rem; margin: 2rem auto; padding: 2rem; border:
 1px solid var(--line); }
header { display: flex; justify-content: space-between; flex-wrap:
wrap; gap: 1rem; border-bottom: 3px solid var(--brand); padding-
```

```
bottom: 1rem; }
h1 { margin: 0; color: var(--brand); }
.meta p { margin: .1rem 0; text-align: right; }
table { width: 100%; border-collapse: collapse; margin-top: 1.5rem; }
th, td { padding: .6rem; border-bottom: 1px solid var(--line); text-
align: left; }
.n { text-align: right; font-variant-numeric: tabular-nums; }
tfoot th, tfoot td { font-weight: 700; border-top: 2px solid var(--
ink); border-bottom: 0; }
.thanks { margin-top: 2rem; color: var(--muted); font-style: italic; }
@media print { .invoice { border: 0; margin: 0; max-width: none; } }
```

Project 586 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Invoice 2026-041 - Oasis Plant Nursery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="invoice">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Oasis Plant Nursery Sheikh Zayed, Egypt	The main heading; only one per page.
Invoice 2026-041 Date <tim...	A paragraph of text.
Bill to: Customer name, Sheikh Zayed	Keyword or name drawn to attention without extra importance.
<table>	Tabular data in rows and columns.
<thead><tr><th>Item</th><th class="n">Qty</th><th class="n">Price<//...	Group of header rows.

Line	What it does
<tbody>	Group of data rows.
<tr><td>Monstera</td><td class="n">1</td><td class="n">250 EGP</td>...	A table row.
<tr><td>Snake plant</td><td class="n">1</td><td class="n">120 EGP<//...	A data cell.
<tfoot><tr><th colspan="2">Total</th><td class="n">see items</td><//...	Group of footer rows (totals).

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 2rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: 1rem;	Space between grid or flex items without extra margins.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-align: right;	Right-aligns inline content, typical for numbers.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	The line around the element: width, style and colour.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
font-weight: 700;	Thickness of the text.
border-top: 2px solid var(--ink);	A top border used as an accent or separator.

Declaration	What it does
@media print { .invoice { border: 0; margin: 0; max-width: none; } }	Removes the default border (for example on an iframe or button).

Check your work

- Numbers right-aligned
- Total row in tfoot
- Fits on one printed page
- Date has datetime

Exercises

1. Calculate the total with JavaScript.
2. Add a logo image.
3. Add a QR code image for payment.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 587: Printable invoice for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 2 | Files: index.html, styles.css

Brief

Create a clean invoice with a header row, a table using tfoot and colspan for the total, right-aligned numbers and print styles.

Learning goals

- Use tfoot and colspan
- Align numbers with tabular figures
- Design for print

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, b, time, table, thead, tbody, tfoot, th, td	justify-content: space-between, colspan, font-variant-numeric, border-top, @media print

Build guide

1. Write the header with two blocks: seller and invoice metadata.
2. Write the table with thead, tbody and a tfoot total row using colspan="2".
3. Add class n to numeric cells.
4. Flex the header with space-between.
5. Right-align .n cells.
6. Print preview and remove the border in @media print.

Project 587: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Invoice 2026-041 - Cedar Furniture</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="invoice">
    <header>
      <div><h1>Cedar Furniture</h1><p>Damietta, Egypt</p></div>
      <div class="meta"><p><b>Invoice</b> 2026-041</p><p><b>Date</b>
<time datetime="2026-09-11">11 Sep 2026</time></p></div>
    </header>
    <p><b>Bill to:</b> Customer name, Damietta</p>
    <table>
      <thead><tr><th>Item</th><th class="n">Qty</th><th
class="n">Price</th></tr></thead>
      <tbody>
        <tr><td>Oak dining table</td><td class="n">1</td><td
class="n">9500 EGP</td></tr>
        <tr><td>Bookshelf</td><td class="n">1</td><td class="n">4200
EGP</td></tr>
        <tr><td>Bedside table</td><td class="n">1</td><td
class="n">1500 EGP</td></tr>
      </tbody>
      <tfoot><tr><th colspan="2">Total</th><td class="n">see items</
td></tr></tfoot>
    </table>
    <p class="thanks">Thank you for your business.</p>
  </main>
</body>
</html>
```

Project 587: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.invoice { max-width: 46rem; margin: 2rem auto; padding: 2rem; border:
 1px solid var(--line); }
header { display: flex; justify-content: space-between; flex-wrap:
wrap; gap: 1rem; border-bottom: 3px solid var(--brand); padding-
bottom: 1rem; }
```

```
h1 { margin: 0; color: var(--brand); }
.meta p { margin: .1rem 0; text-align: right; }
table { width: 100%; border-collapse: collapse; margin-top: 1.5rem; }
th, td { padding: .6rem; border-bottom: 1px solid var(--line); text-
align: left; }
.n { text-align: right; font-variant-numeric: tabular-nums; }
tfoot th, tfoot td { font-weight: 700; border-top: 2px solid var(--
ink); border-bottom: 0; }
.thanks { margin-top: 2rem; color: var(--muted); font-style: italic; }
@media print { .invoice { border: 0; margin: 0; max-width: none; } }
```

Project 587 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Invoice 2026-041 - Cedar Furniture</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="invoice">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Cedar Furniture Damietta, Egypt	The main heading; only one per page.
Invoice 2026-041 Date <tim...	A paragraph of text.
Bill to: Customer name, Damietta	Keyword or name drawn to attention without extra importance.
<table>	Tabular data in rows and columns.
<thead><tr><th>Item</th><th class="n">Qty</th><th class="n">Price<//...	Group of header rows.

Line	What it does
<tbody>	Group of data rows.
<tr><td>Oak dining table</td><td class="n">1</td><td class="n">9500...	A table row.
<tr><td>Bookshelf</td><td class="n">1</td><td class="n">4200 EGP</t...	A data cell.
<tfoot><tr><th colspan="2">Total</th><td class="n">see items</td><//...	Group of footer rows (totals).

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 2rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: 1rem;	Space between grid or flex items without extra margins.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-align: right;	Right-aligns inline content, typical for numbers.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	The line around the element: width, style and colour.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
font-weight: 700;	Thickness of the text.
border-top: 2px solid var(--ink);	A top border used as an accent or separator.

Declaration	What it does
@media print { .invoice { border: 0; margin: 0; max-width: none; } }	Removes the default border (for example on an iframe or button).

Check your work

- Numbers right-aligned
- Total row in tfoot
- Fits on one printed page
- Date has datetime

Exercises

1. Calculate the total with JavaScript.
2. Add a logo image.
3. Add a QR code image for payment.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 588: Printable invoice for Byte Repair

Theme: Byte Repair (Nasr City) | Level 2 | Files: index.html, styles.css

Brief

Create a clean invoice with a header row, a table using tfoot and colspan for the total, right-aligned numbers and print styles.

Learning goals

- Use tfoot and colspan
- Align numbers with tabular figures
- Design for print

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, b, time, table, thead, tbody, tfoot, th, td	justify-content: space-between, colspan, font-variant-numeric, border-top, @media print

Build guide

1. Write the header with two blocks: seller and invoice metadata.
2. Write the table with thead, tbody and a tfoot total row using colspan="2".
3. Add class n to numeric cells.
4. Flex the header with space-between.
5. Right-align .n cells.
6. Print preview and remove the border in @media print.

Project 588: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Invoice 2026-041 - Byte Repair</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="invoice">
    <header>
      <div><h1>Byte Repair</h1><p>Nasr City, Egypt</p></div>
      <div class="meta"><p><b>Invoice</b> 2026-041</p><p><b>Date</b>
<time datetime="2026-09-11">11 Sep 2026</time></p></div>
    </header>
    <p><b>Bill to:</b> Customer name, Nasr City</p>
    <table>
      <thead><tr><th>Item</th><th class="n">Qty</th><th
class="n">Price</th></tr></thead>
      <tbody>
        <tr><td>Screen replacement</td><td class="n">1</td><td
class="n">From 800 EGP</td></tr>
        <tr><td>Battery swap</td><td class="n">1</td><td
class="n">From 500 EGP</td></tr>
        <tr><td>Laptop cleaning</td><td class="n">1</td><td
class="n">350 EGP</td></tr>
      </tbody>
      <tfoot><tr><th colspan="2">Total</th><td class="n">see items</
td></tr></tfoot>
    </table>
    <p class="thanks">Thank you for your business.</p>
  </main>
</body>
</html>
```

Project 588: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.invoice { max-width: 46rem; margin: 2rem auto; padding: 2rem; border:
 1px solid var(--line); }
header { display: flex; justify-content: space-between; flex-wrap:
wrap; gap: 1rem; border-bottom: 3px solid var(--brand); padding-
bottom: 1rem; }
```

```
h1 { margin: 0; color: var(--brand); }
.meta p { margin: .1rem 0; text-align: right; }
table { width: 100%; border-collapse: collapse; margin-top: 1.5rem; }
th, td { padding: .6rem; border-bottom: 1px solid var(--line); text-
align: left; }
.n { text-align: right; font-variant-numeric: tabular-nums; }
tfoot th, tfoot td { font-weight: 700; border-top: 2px solid var(--
ink); border-bottom: 0; }
.thanks { margin-top: 2rem; color: var(--muted); font-style: italic; }
@media print { .invoice { border: 0; margin: 0; max-width: none; } }
```

Project 588 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Invoice 2026-041 - Byte Repair</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="invoice">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Byte Repair Nasr City, Egypt	The main heading; only one per page.
Invoice 2026-041 Date <tim...	A paragraph of text.
Bill to: Customer name, Nasr City	Keyword or name drawn to attention without extra importance.
<table>	Tabular data in rows and columns.
<thead><tr><th>Item</th><th class="n">Qty</th><th class="n">Price<//...	Group of header rows.

Line	What it does
<tbody>	Group of data rows.
<tr><td>Screen replacement</td><td class="n">1</td><td class="n">Fr...	A table row.
<tr><td>Battery swap</td><td class="n">1</td><td class="n">From 500...	A data cell.
<tfoot><tr><th colspan="2">Total</th><td class="n">see items</td><//...	Group of footer rows (totals).

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 2rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: 1rem;	Space between grid or flex items without extra margins.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-align: right;	Right-aligns inline content, typical for numbers.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	The line around the element: width, style and colour.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
font-weight: 700;	Thickness of the text.
border-top: 2px solid var(--ink);	A top border used as an accent or separator.

Declaration	What it does
@media print { .invoice { border: 0; margin: 0; max-width: none; } }	Removes the default border (for example on an iframe or button).

Check your work

- Numbers right-aligned
- Total row in tfoot
- Fits on one printed page
- Date has datetime

Exercises

1. Calculate the total with JavaScript.
2. Add a logo image.
3. Add a QR code image for payment.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 589: Printable invoice for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 2 | Files: index.html, styles.css

Brief

Create a clean invoice with a header row, a table using tfoot and colspan for the total, right-aligned numbers and print styles.

Learning goals

- Use tfoot and colspan
- Align numbers with tabular figures
- Design for print

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, b, time, table, thead, tbody, tfoot, th, td	justify-content: space-between, colspan, font-variant-numeric, border-top, @media print

Build guide

1. Write the header with two blocks: seller and invoice metadata.
2. Write the table with thead, tbody and a tfoot total row using colspan="2".
3. Add class n to numeric cells.
4. Flex the header with space-between.
5. Right-align .n cells.
6. Print preview and remove the border in @media print.

Project 589: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Invoice 2026-041 - Sahara Pet Care</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="invoice">
    <header>
      <div><h1>Sahara Pet Care</h1><p>New Cairo, Egypt</p></div>
      <div class="meta"><p><b>Invoice</b> 2026-041</p><p><b>Date</b>
<time datetime="2026-09-11">11 Sep 2026</time></p></div>
    </header>
    <p><b>Bill to:</b> Customer name, New Cairo</p>
    <table>
      <thead><tr><th>Item</th><th class="n">Qty</th><th
class="n">Price</th></tr></thead>
      <tbody>
        <tr><td>Full grooming</td><td class="n">1</td><td
class="n">400 EGP</td></tr>
        <tr><td>Day boarding</td><td class="n">1</td><td
class="n">250 EGP</td></tr>
        <tr><td>Vaccination</td><td class="n">1</td><td class="n">300
EGP</td></tr>
      </tbody>
      <tfoot><tr><th colspan="2">Total</th><td class="n">see items</
td></tr></tfoot>
    </table>
    <p class="thanks">Thank you for your business.</p>
  </main>
</body>
</html>
```

Project 589: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.invoice { max-width: 46rem; margin: 2rem auto; padding: 2rem; border:
 1px solid var(--line); }
header { display: flex; justify-content: space-between; flex-wrap:
wrap; gap: 1rem; border-bottom: 3px solid var(--brand); padding-
bottom: 1rem; }
```

```
h1 { margin: 0; color: var(--brand); }
.meta p { margin: .1rem 0; text-align: right; }
table { width: 100%; border-collapse: collapse; margin-top: 1.5rem; }
th, td { padding: .6rem; border-bottom: 1px solid var(--line); text-
align: left; }
.n { text-align: right; font-variant-numeric: tabular-nums; }
tfoot th, tfoot td { font-weight: 700; border-top: 2px solid var(--
ink); border-bottom: 0; }
.thanks { margin-top: 2rem; color: var(--muted); font-style: italic; }
@media print { .invoice { border: 0; margin: 0; max-width: none; } }
```

Project 589 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Invoice 2026-041 - Sahara Pet Care</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="invoice">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Sahara Pet Care New Cairo, Egypt	The main heading; only one per page.
Invoice 2026-041 Date <tim...	A paragraph of text.
Bill to: Customer name, New Cairo	Keyword or name drawn to attention without extra importance.
<table>	Tabular data in rows and columns.
<thead><tr><th>Item</th><th class="n">Qty</th><th class="n">Price<//...	Group of header rows.

Line	What it does
<tbody>	Group of data rows.
<tr><td>Full grooming</td><td class="n">1</td><td class="n">400 EGP...	A table row.
<tr><td>Day boarding</td><td class="n">1</td><td class="n">250 EGP<...	A data cell.
<tfoot><tr><th colspan="2">Total</th><td class="n">see items</td><//...	Group of footer rows (totals).

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 2rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: 1rem;	Space between grid or flex items without extra margins.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-align: right;	Right-aligns inline content, typical for numbers.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	The line around the element: width, style and colour.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
font-weight: 700;	Thickness of the text.
border-top: 2px solid var(--ink);	A top border used as an accent or separator.

Declaration	What it does
@media print { .invoice { border: 0; margin: 0; max-width: none; } }	Removes the default border (for example on an iframe or button).

Check your work

- Numbers right-aligned
- Total row in tfoot
- Fits on one printed page
- Date has datetime

Exercises

1. Calculate the total with JavaScript.
2. Add a logo image.
3. Add a QR code image for payment.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 590: Printable invoice for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Create a clean invoice with a header row, a table using tfoot and colspan for the total, right-aligned numbers and print styles.

Learning goals

- Use tfoot and colspan
- Align numbers with tabular figures
- Design for print

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, b, time, table, thead, tbody, tfoot, th, td	justify-content: space-between, colspan, font-variant-numeric, border-top, @media print

Build guide

1. Write the header with two blocks: seller and invoice metadata.
2. Write the table with thead, tbody and a tfoot total row using colspan="2".
3. Add class n to numeric cells.
4. Flex the header with space-between.
5. Right-align .n cells.
6. Print preview and remove the border in @media print.

Project 590: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Invoice 2026-041 - Alexandria Sailing School</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="invoice">
    <header>
      <div><h1>Alexandria Sailing School</h1><p>Alexandria, Egypt</
p></div>
      <div class="meta"><p><b>Invoice</b> 2026-041</p><p><b>Date</b>
<time datetime="2026-09-11">11 Sep 2026</time></p></div>
    </header>
    <p><b>Bill to:</b> Customer name, Alexandria</p>
    <table>
      <thead><tr><th>Item</th><th class="n">Qty</th><th
class="n">Price</th></tr></thead>
      <tbody>
        <tr><td>Taster session</td><td class="n">1</td><td
class="n">500 EGP</td></tr>
        <tr><td>Beginner course</td><td class="n">1</td><td
class="n">2200 EGP</td></tr>
        <tr><td>Racing clinic</td><td class="n">1</td><td
class="n">1800 EGP</td></tr>
      </tbody>
      <tfoot><tr><th colspan="2">Total</th><td class="n">see items</
td></tr></tfoot>
    </table>
    <p class="thanks">Thank you for your business.</p>
  </main>
</body>
</html>
```

Project 590: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.invoice { max-width: 46rem; margin: 2rem auto; padding: 2rem; border:
 1px solid var(--line); }
header { display: flex; justify-content: space-between; flex-wrap:
wrap; gap: 1rem; border-bottom: 3px solid var(--brand); padding-
```

```
bottom: 1rem; }
h1 { margin: 0; color: var(--brand); }
.meta p { margin: .1rem 0; text-align: right; }
table { width: 100%; border-collapse: collapse; margin-top: 1.5rem; }
th, td { padding: .6rem; border-bottom: 1px solid var(--line); text-
align: left; }
.n { text-align: right; font-variant-numeric: tabular-nums; }
tfoot th, tfoot td { font-weight: 700; border-top: 2px solid var(--
ink); border-bottom: 0; }
.thanks { margin-top: 2rem; color: var(--muted); font-style: italic; }
@media print { .invoice { border: 0; margin: 0; max-width: none; } }
```

Project 590 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Invoice 2026-041 - Alexandria Sailing School</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="invoice">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Alexandria Sailing School Alexandria, Egypt	The main heading; only one per page.
Invoice 2026-041 Date <tim...	A paragraph of text.
Bill to: Customer name, Alexandria	Keyword or name drawn to attention without extra importance.
<table>	Tabular data in rows and columns.

Line	What it does
<thead><tr><th>Item</th><th class="n">Qty</th><th class="n">Price<//...	Group of header rows.
<tbody>	Group of data rows.
<tr><td>Taster session</td><td class="n">1</td><td class="n">500 EG...	A table row.
<tr><td>Beginner course</td><td class="n">1</td><td class="n">2200 ...	A data cell.
<tfoot><tr><th colspan="2">Total</th><td class="n">see items</td><//...	Group of footer rows (totals).

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 2rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: 1rem;	Space between grid or flex items without extra margins.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-align: right;	Right-aligns inline content, typical for numbers.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	The line around the element: width, style and colour.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
font-weight: 700;	Thickness of the text.

Declaration	What it does
border-top: 2px solid var(--ink);	A top border used as an accent or separator.
@media print { .invoice { border: 0; margin: 0; max-width: none; } }	Removes the default border (for example on an iframe or button).

Check your work

- Numbers right-aligned
- Total row in tfoot
- Fits on one printed page
- Date has datetime

Exercises

1. Calculate the total with JavaScript.
2. Add a logo image.
3. Add a QR code image for payment.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 591: Printable invoice for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Create a clean invoice with a header row, a table using tfoot and colspan for the total, right-aligned numbers and print styles.

Learning goals

- Use tfoot and colspan
- Align numbers with tabular figures
- Design for print

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, b, time, table, thead, tbody, tfoot, th, td	justify-content: space-between, colspan, font-variant-numeric, border-top, @media print

Build guide

1. Write the header with two blocks: seller and invoice metadata.
2. Write the table with thead, tbody and a tfoot total row using colspan="2".
3. Add class n to numeric cells.
4. Flex the header with space-between.
5. Right-align .n cells.

6. Print preview and remove the border in @media print.

Project 591: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Invoice 2026-041 - Habiba Handmade Jewellery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="invoice">
    <header>
      <div><h1>Habiba Handmade Jewellery</h1><p>Aswan, Egypt</p></div>
      <div class="meta"><p><b>Invoice</b> 2026-041</p><p><b>Date</b>
<time datetime="2026-09-11">11 Sep 2026</time></p></div>
    </header>
    <p><b>Bill to:</b> Customer name, Aswan</p>
    <table>
      <thead><tr><th>Item</th><th class="n">Qty</th><th
class="n">Price</th></tr></thead>
      <tbody>
        <tr><td>Lotus pendant</td><td class="n">1</td><td
class="n">650 EGP</td></tr>
        <tr><td>Brass cuff</td><td class="n">1</td><td class="n">420
EGP</td></tr>
        <tr><td>Bead earrings</td><td class="n">1</td><td
class="n">180 EGP</td></tr>
      </tbody>
      <tfoot><tr><th colspan="2">Total</th><td class="n">see items</
td></tr></tfoot>
    </table>
    <p class="thanks">Thank you for your business.</p>
  </main>
</body>
</html>
```

Project 591: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.invoice { max-width: 46rem; margin: 2rem auto; padding: 2rem; border:
 1px solid var(--line); }
header { display: flex; justify-content: space-between; flex-wrap:
wrap; gap: 1rem; border-bottom: 3px solid var(--brand); padding-
bottom: 1rem; }
```

```
h1 { margin: 0; color: var(--brand); }
.meta p { margin: .1rem 0; text-align: right; }
table { width: 100%; border-collapse: collapse; margin-top: 1.5rem; }
th, td { padding: .6rem; border-bottom: 1px solid var(--line); text-
align: left; }
.n { text-align: right; font-variant-numeric: tabular-nums; }
tfoot th, tfoot td { font-weight: 700; border-top: 2px solid var(--
ink); border-bottom: 0; }
.thanks { margin-top: 2rem; color: var(--muted); font-style: italic; }
@media print { .invoice { border: 0; margin: 0; max-width: none; } }
```

Project 591 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Invoice 2026-041 - Habiba Handmade Jewellery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="invoice">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Habiba Handmade Jewellery Aswan, Egypt	The main heading; only one per page.
Invoice 2026-041 Date <tim...	A paragraph of text.
Bill to: Customer name, Aswan	Keyword or name drawn to attention without extra importance.
<table>	Tabular data in rows and columns.

Line	What it does
<thead><tr><th>Item</th><th class="n">Qty</th><th class="n">Price<//...	Group of header rows.
<tbody>	Group of data rows.
<tr><td>Lotus pendant</td><td class="n">1</td><td class="n">650 EGP...	A table row.
<tr><td>Brass cuff</td><td class="n">1</td><td class="n">420 EGP</t...	A data cell.
<tfoot><tr><th colspan="2">Total</th><td class="n">see items</td><//...	Group of footer rows (totals).

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 2rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: 1rem;	Space between grid or flex items without extra margins.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-align: right;	Right-aligns inline content, typical for numbers.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	The line around the element: width, style and colour.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
font-weight: 700;	Thickness of the text.

Declaration	What it does
border-top: 2px solid var(--ink);	A top border used as an accent or separator.
@media print { .invoice { border: 0; margin: 0; max-width: none; } }	Removes the default border (for example on an iframe or button).

Check your work

- Numbers right-aligned
- Total row in tfoot
- Fits on one printed page
- Date has datetime

Exercises

1. Calculate the total with JavaScript.
2. Add a logo image.
3. Add a QR code image for payment.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 592: Printable invoice for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 2 | Files: index.html, styles.css

Brief

Create a clean invoice with a header row, a table using tfoot and colspan for the total, right-aligned numbers and print styles.

Learning goals

- Use tfoot and colspan
- Align numbers with tabular figures
- Design for print

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, b, time, table, thead, tbody, tfoot, th, td	justify-content: space-between, colspan, font-variant-numeric, border-top, @media print

Build guide

1. Write the header with two blocks: seller and invoice metadata.
2. Write the table with thead, tbody and a tfoot total row using colspan="2".
3. Add class n to numeric cells.
4. Flex the header with space-between.
5. Right-align .n cells.
6. Print preview and remove the border in @media print.

Project 592: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Invoice 2026-041 - Fayoum Pottery Studio</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="invoice">
    <header>
      <div><h1>Fayoum Pottery Studio</h1><p>Tunis Village, Egypt</p></
div>
      <div class="meta"><p><b>Invoice</b> 2026-041</p><p><b>Date</b>
<time datetime="2026-09-11">11 Sep 2026</time></p></div>
    </header>
    <p><b>Bill to:</b> Customer name, Tunis Village</p>
    <table>
      <thead><tr><th>Item</th><th class="n">Qty</th><th
class="n">Price</th></tr></thead>
      <tbody>
        <tr><td>Intro to the wheel</td><td class="n">1</td><td
class="n">450 EGP</td></tr>
        <tr><td>Glazing day</td><td class="n">1</td><td class="n">300
EGP</td></tr>
        <tr><td>Kids clay class</td><td class="n">1</td><td
class="n">200 EGP</td></tr>
      </tbody>
      <tfoot><tr><th colspan="2">Total</th><td class="n">see items</
td></tr></tfoot>
    </table>
    <p class="thanks">Thank you for your business.</p>
  </main>
</body>
</html>
```

Project 592: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.invoice { max-width: 46rem; margin: 2rem auto; padding: 2rem; border:
 1px solid var(--line); }
header { display: flex; justify-content: space-between; flex-wrap:
wrap; gap: 1rem; border-bottom: 3px solid var(--brand); padding-
```

```
bottom: 1rem; }
h1 { margin: 0; color: var(--brand); }
.meta p { margin: .1rem 0; text-align: right; }
table { width: 100%; border-collapse: collapse; margin-top: 1.5rem; }
th, td { padding: .6rem; border-bottom: 1px solid var(--line); text-
align: left; }
.n { text-align: right; font-variant-numeric: tabular-nums; }
tfoot th, tfoot td { font-weight: 700; border-top: 2px solid var(--
ink); border-bottom: 0; }
.thanks { margin-top: 2rem; color: var(--muted); font-style: italic; }
@media print { .invoice { border: 0; margin: 0; max-width: none; } }
```

Project 592 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Invoice 2026-041 - Fayoum Pottery Studio</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="invoice">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Fayoum Pottery Studio Tunis Village, Egypt	The main heading; only one per page.
Invoice 2026-041 Date <tim...	A paragraph of text.
Bill to: Customer name, Tunis Village	Keyword or name drawn to attention without extra importance.
<table>	Tabular data in rows and columns.
<thead><tr><th>Item</th><th class="n">Qty</th><th class="n">Price<//...	Group of header rows.

Line	What it does
<tbody>	Group of data rows.
<tr><td>Intro to the wheel</td><td class="n">1</td><td class="n">45...	A table row.
<tr><td>Glazing day</td><td class="n">1</td><td class="n">300 EGP<//...	A data cell.
<tfoot><tr><th colspan="2">Total</th><td class="n">see items</td><//...	Group of footer rows (totals).

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 2rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: 1rem;	Space between grid or flex items without extra margins.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-align: right;	Right-aligns inline content, typical for numbers.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	The line around the element: width, style and colour.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
font-weight: 700;	Thickness of the text.
border-top: 2px solid var(--ink);	A top border used as an accent or separator.

Declaration	What it does
@media print { .invoice { border: 0; margin: 0; max-width: none; } }	Removes the default border (for example on an iframe or button).

Check your work

- Numbers right-aligned
- Total row in tfoot
- Fits on one printed page
- Date has datetime

Exercises

1. Calculate the total with JavaScript.
2. Add a logo image.
3. Add a QR code image for payment.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 593: Printable invoice for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 2 | Files: index.html, styles.css

Brief

Create a clean invoice with a header row, a table using tfoot and colspan for the total, right-aligned numbers and print styles.

Learning goals

- Use tfoot and colspan
- Align numbers with tabular figures
- Design for print

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, b, time, table, thead, tbody, tfoot, th, td	justify-content: space-between, colspan, font-variant-numeric, border-top, @media print

Build guide

1. Write the header with two blocks: seller and invoice metadata.
2. Write the table with thead, tbody and a tfoot total row using colspan="2".
3. Add class n to numeric cells.
4. Flex the header with space-between.
5. Right-align .n cells.
6. Print preview and remove the border in @media print.

Project 593: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Invoice 2026-041 - Cleopatra Beauty Salon</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="invoice">
    <header>
      <div><h1>Cleopatra Beauty Salon</h1><p>Dokki, Egypt</p></div>
      <div class="meta"><p><b>Invoice</b> 2026-041</p><p><b>Date</b>
<time datetime="2026-09-11">11 Sep 2026</time></p></div>
    </header>
    <p><b>Bill to:</b> Customer name, Dokki</p>
    <table>
      <thead><tr><th>Item</th><th class="n">Qty</th><th
class="n">Price</th></tr></thead>
      <tbody>
        <tr><td>Haircut and blow-dry</td><td class="n">1</td><td
class="n">350 EGP</td></tr>
        <tr><td>Manicure</td><td class="n">1</td><td class="n">200
EGP</td></tr>
        <tr><td>Facial</td><td class="n">1</td><td class="n">600 EGP</
td></tr>
      </tbody>
      <tfoot><tr><th colspan="2">Total</th><td class="n">see items</
td></tr></tfoot>
    </table>
    <p class="thanks">Thank you for your business.</p>
  </main>
</body>
</html>
```

Project 593: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.invoice { max-width: 46rem; margin: 2rem auto; padding: 2rem; border:
 1px solid var(--line); }
header { display: flex; justify-content: space-between; flex-wrap:
wrap; gap: 1rem; border-bottom: 3px solid var(--brand); padding-
bottom: 1rem; }
```

```
h1 { margin: 0; color: var(--brand); }
.meta p { margin: .1rem 0; text-align: right; }
table { width: 100%; border-collapse: collapse; margin-top: 1.5rem; }
th, td { padding: .6rem; border-bottom: 1px solid var(--line); text-
align: left; }
.n { text-align: right; font-variant-numeric: tabular-nums; }
tfoot th, tfoot td { font-weight: 700; border-top: 2px solid var(--
ink); border-bottom: 0; }
.thanks { margin-top: 2rem; color: var(--muted); font-style: italic; }
@media print { .invoice { border: 0; margin: 0; max-width: none; } }
```

Project 593 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Invoice 2026-041 - Cleopatra Beauty Salon</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="invoice">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Cleopatra Beauty Salon Dokki, Egypt	The main heading; only one per page.
Invoice 2026-041 Date <tim...	A paragraph of text.
Bill to: Customer name, Dokki	Keyword or name drawn to attention without extra importance.
<table>	Tabular data in rows and columns.

Line	What it does
<thead><tr><th>Item</th><th class="n">Qty</th><th class="n">Price<//...	Group of header rows.
<tbody>	Group of data rows.
<tr><td>Haircut and blow-dry</td><td class="n">1</td><td class="n">...	A table row.
<tr><td>Manicure</td><td class="n">1</td><td class="n">200 EGP</td>...	A data cell.
<tfoot><tr><th colspan="2">Total</th><td class="n">see items</td><//...	Group of footer rows (totals).

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 2rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: 1rem;	Space between grid or flex items without extra margins.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-align: right;	Right-aligns inline content, typical for numbers.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	The line around the element: width, style and colour.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
font-weight: 700;	Thickness of the text.

Declaration	What it does
border-top: 2px solid var(--ink);	A top border used as an accent or separator.
@media print { .invoice { border: 0; margin: 0; max-width: none; } }	Removes the default border (for example on an iframe or button).

Check your work

- Numbers right-aligned
- Total row in tfoot
- Fits on one printed page
- Date has datetime

Exercises

1. Calculate the total with JavaScript.
2. Add a logo image.
3. Add a QR code image for payment.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 594: Printable invoice for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 2 | Files: index.html, styles.css

Brief

Create a clean invoice with a header row, a table using tfoot and colspan for the total, right-aligned numbers and print styles.

Learning goals

- Use tfoot and colspan
- Align numbers with tabular figures
- Design for print

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, b, time, table, thead, tbody, tfoot, th, td	justify-content: space-between, colspan, font-variant-numeric, border-top, @media print

Build guide

1. Write the header with two blocks: seller and invoice metadata.
2. Write the table with thead, tbody and a tfoot total row using colspan="2".
3. Add class n to numeric cells.
4. Flex the header with space-between.
5. Right-align .n cells.
6. Print preview and remove the border in @media print.

Project 594: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Invoice 2026-041 - Suez Auto Service</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="invoice">
    <header>
      <div><h1>Suez Auto Service</h1><p>Suez, Egypt</p></div>
      <div class="meta"><p><b>Invoice</b> 2026-041</p><p><b>Date</b>
<time datetime="2026-09-11">11 Sep 2026</time></p></div>
    </header>
    <p><b>Bill to:</b> Customer name, Suez</p>
    <table>
      <thead><tr><th>Item</th><th class="n">Qty</th><th
class="n">Price</th></tr></thead>
      <tbody>
        <tr><td>Oil change</td><td class="n">1</td><td class="n">600
EGP</td></tr>
        <tr><td>Brake pads</td><td class="n">1</td><td class="n">1400
EGP</td></tr>
        <tr><td>Air conditioning</td><td class="n">1</td><td
class="n">900 EGP</td></tr>
      </tbody>
      <tfoot><tr><th colspan="2">Total</th><td class="n">see items</
td></tr></tfoot>
    </table>
    <p class="thanks">Thank you for your business.</p>
  </main>
</body>
</html>
```

Project 594: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.invoice { max-width: 46rem; margin: 2rem auto; padding: 2rem; border:
 1px solid var(--line); }
header { display: flex; justify-content: space-between; flex-wrap:
wrap; gap: 1rem; border-bottom: 3px solid var(--brand); padding-
bottom: 1rem; }
```

```
h1 { margin: 0; color: var(--brand); }
.meta p { margin: .1rem 0; text-align: right; }
table { width: 100%; border-collapse: collapse; margin-top: 1.5rem; }
th, td { padding: .6rem; border-bottom: 1px solid var(--line); text-
align: left; }
.n { text-align: right; font-variant-numeric: tabular-nums; }
tfoot th, tfoot td { font-weight: 700; border-top: 2px solid var(--
ink); border-bottom: 0; }
.thanks { margin-top: 2rem; color: var(--muted); font-style: italic; }
@media print { .invoice { border: 0; margin: 0; max-width: none; } }
```

Project 594 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Invoice 2026-041 - Suez Auto Service</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="invoice">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Suez Auto Service Suez, Egypt	The main heading; only one per page.
Invoice 2026-041 Date <tim...	A paragraph of text.
Bill to: Customer name, Suez	Keyword or name drawn to attention without extra importance.
<table>	Tabular data in rows and columns.
<thead><tr><th>Item</th><th class="n">Qty</th><th class="n">Price<//...	Group of header rows.

Line	What it does
<tbody>	Group of data rows.
<tr><td>Oil change</td><td class="n">1</td><td class="n">600 EGP</t...	A table row.
<tr><td>Brake pads</td><td class="n">1</td><td class="n">1400 EGP<//...	A data cell.
<tfoot><tr><th colspan="2">Total</th><td class="n">see items</td><//...	Group of footer rows (totals).

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 2rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: 1rem;	Space between grid or flex items without extra margins.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-align: right;	Right-aligns inline content, typical for numbers.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	The line around the element: width, style and colour.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
font-weight: 700;	Thickness of the text.
border-top: 2px solid var(--ink);	A top border used as an accent or separator.

Declaration	What it does
@media print { .invoice { border: 0; margin: 0; max-width: none; } }	Removes the default border (for example on an iframe or button).

Check your work

- Numbers right-aligned
- Total row in tfoot
- Fits on one printed page
- Date has datetime

Exercises

1. Calculate the total with JavaScript.
2. Add a logo image.
3. Add a QR code image for payment.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 595: Printable invoice for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 2 | Files: index.html, styles.css

Brief

Create a clean invoice with a header row, a table using tfoot and colspan for the total, right-aligned numbers and print styles.

Learning goals

- Use tfoot and colspan
- Align numbers with tabular figures
- Design for print

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, b, time, table, thead, tbody, tfoot, th, td	justify-content: space-between, colspan, font-variant-numeric, border-top, @media print

Build guide

1. Write the header with two blocks: seller and invoice metadata.
2. Write the table with thead, tbody and a tfoot total row using colspan="2".
3. Add class n to numeric cells.
4. Flex the header with space-between.
5. Right-align .n cells.
6. Print preview and remove the border in @media print.

Project 595: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Invoice 2026-041 - Luxor Music Academy</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="invoice">
    <header>
      <div><h1>Luxor Music Academy</h1><p>Luxor, Egypt</p></div>
      <div class="meta"><p><b>Invoice</b> 2026-041</p><p><b>Date</b>
<time datetime="2026-09-11">11 Sep 2026</time></p></div>
    </header>
    <p><b>Bill to:</b> Customer name, Luxor</p>
    <table>
      <thead><tr><th>Item</th><th class="n">Qty</th><th
class="n">Price</th></tr></thead>
      <tbody>
        <tr><td>Oud for beginners</td><td class="n">1</td><td
class="n">1600 EGP</td></tr>
        <tr><td>Piano grade 1</td><td class="n">1</td><td
class="n">1800 EGP</td></tr>
        <tr><td>Guitar chords</td><td class="n">1</td><td
class="n">1400 EGP</td></tr>
      </tbody>
      <tfoot><tr><th colspan="2">Total</th><td class="n">see items</
td></tr></tfoot>
    </table>
    <p class="thanks">Thank you for your business.</p>
  </main>
</body>
</html>
```

Project 595: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.invoice { max-width: 46rem; margin: 2rem auto; padding: 2rem; border:
 1px solid var(--line); }
header { display: flex; justify-content: space-between; flex-wrap:
wrap; gap: 1rem; border-bottom: 3px solid var(--brand); padding-
bottom: 1rem; }
```

```
h1 { margin: 0; color: var(--brand); }
.meta p { margin: .1rem 0; text-align: right; }
table { width: 100%; border-collapse: collapse; margin-top: 1.5rem; }
th, td { padding: .6rem; border-bottom: 1px solid var(--line); text-
align: left; }
.n { text-align: right; font-variant-numeric: tabular-nums; }
tfoot th, tfoot td { font-weight: 700; border-top: 2px solid var(--
ink); border-bottom: 0; }
.thanks { margin-top: 2rem; color: var(--muted); font-style: italic; }
@media print { .invoice { border: 0; margin: 0; max-width: none; } }
```

Project 595 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Invoice 2026-041 - Luxor Music Academy</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="invoice">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Luxor Music Academy Luxor, Egypt	The main heading; only one per page.
Invoice 2026-041 Date <tim...	A paragraph of text.
Bill to: Customer name, Luxor	Keyword or name drawn to attention without extra importance.
<table>	Tabular data in rows and columns.
<thead><tr><th>Item</th><th class="n">Qty</th><th class="n">Price<//...	Group of header rows.

Line	What it does
<tbody>	Group of data rows.
<tr><td>Oud for beginners</td><td class="n">1</td><td class="n">160...	A table row.
<tr><td>Piano grade 1</td><td class="n">1</td><td class="n">1800 EG...	A data cell.
<tfoot><tr><th colspan="2">Total</th><td class="n">see items</td><//...	Group of footer rows (totals).

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 2rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: 1rem;	Space between grid or flex items without extra margins.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-align: right;	Right-aligns inline content, typical for numbers.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	The line around the element: width, style and colour.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
font-weight: 700;	Thickness of the text.
border-top: 2px solid var(--ink);	A top border used as an accent or separator.

Declaration	What it does
@media print { .invoice { border: 0; margin: 0; max-width: none; } }	Removes the default border (for example on an iframe or button).

Check your work

- Numbers right-aligned
- Total row in tfoot
- Fits on one printed page
- Date has datetime

Exercises

1. Calculate the total with JavaScript.
2. Add a logo image.
3. Add a QR code image for payment.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 596: Printable invoice for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 2 | Files: index.html, styles.css

Brief

Create a clean invoice with a header row, a table using tfoot and colspan for the total, right-aligned numbers and print styles.

Learning goals

- Use tfoot and colspan
- Align numbers with tabular figures
- Design for print

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, b, time, table, thead, tbody, tfoot, th, td	justify-content: space-between, colspan, font-variant-numeric, border-top, @media print

Build guide

1. Write the header with two blocks: seller and invoice metadata.
2. Write the table with thead, tbody and a tfoot total row using colspan="2".
3. Add class n to numeric cells.
4. Flex the header with space-between.
5. Right-align .n cells.
6. Print preview and remove the border in @media print.

Project 596: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Invoice 2026-041 - Port Said Seafood</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="invoice">
    <header>
      <div><h1>Port Said Seafood</h1><p>Port Said, Egypt</p></div>
      <div class="meta"><p><b>Invoice</b> 2026-041</p><p><b>Date</b>
<time datetime="2026-09-11">11 Sep 2026</time></p></div>
    </header>
    <p><b>Bill to:</b> Customer name, Port Said</p>
    <table>
      <thead><tr><th>Item</th><th class="n">Qty</th><th
class="n">Price</th></tr></thead>
      <tbody>
        <tr><td>Grilled sea bass</td><td class="n">1</td><td
class="n">320 EGP</td></tr>
        <tr><td>Shrimp tagine</td><td class="n">1</td><td
class="n">280 EGP</td></tr>
        <tr><td>Calamari</td><td class="n">1</td><td class="n">190
EGP</td></tr>
      </tbody>
      <tfoot><tr><th colspan="2">Total</th><td class="n">see items</
td></tr></tfoot>
    </table>
    <p class="thanks">Thank you for your business.</p>
  </main>
</body>
</html>
```

Project 596: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.invoice { max-width: 46rem; margin: 2rem auto; padding: 2rem; border:
 1px solid var(--line); }
header { display: flex; justify-content: space-between; flex-wrap:
wrap; gap: 1rem; border-bottom: 3px solid var(--brand); padding-
bottom: 1rem; }
```

```
h1 { margin: 0; color: var(--brand); }
.meta p { margin: .1rem 0; text-align: right; }
table { width: 100%; border-collapse: collapse; margin-top: 1.5rem; }
th, td { padding: .6rem; border-bottom: 1px solid var(--line); text-
align: left; }
.n { text-align: right; font-variant-numeric: tabular-nums; }
tfoot th, tfoot td { font-weight: 700; border-top: 2px solid var(--
ink); border-bottom: 0; }
.thanks { margin-top: 2rem; color: var(--muted); font-style: italic; }
@media print { .invoice { border: 0; margin: 0; max-width: none; } }
```

Project 596 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Invoice 2026-041 - Port Said Seafood</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="invoice">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Port Said Seafood Port Said, Egypt	The main heading; only one per page.
Invoice 2026-041 Date <tim...	A paragraph of text.
Bill to: Customer name, Port Said	Keyword or name drawn to attention without extra importance.
<table>	Tabular data in rows and columns.
<thead><tr><th>Item</th><th class="n">Qty</th><th class="n">Price<//...	Group of header rows.

Line	What it does
<tbody>	Group of data rows.
<tr><td>Grilled sea bass</td><td class="n">1</td><td class="n">320 ...	A table row.
<tr><td>Shrimp tagine</td><td class="n">1</td><td class="n">280 EGP...	A data cell.
<tfoot><tr><th colspan="2">Total</th><td class="n">see items</td><//...	Group of footer rows (totals).

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 2rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: 1rem;	Space between grid or flex items without extra margins.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-align: right;	Right-aligns inline content, typical for numbers.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	The line around the element: width, style and colour.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
font-weight: 700;	Thickness of the text.
border-top: 2px solid var(--ink);	A top border used as an accent or separator.

Declaration	What it does
@media print { .invoice { border: 0; margin: 0; max-width: none; } }	Removes the default border (for example on an iframe or button).

Check your work

- Numbers right-aligned
- Total row in tfoot
- Fits on one printed page
- Date has datetime

Exercises

1. Calculate the total with JavaScript.
2. Add a logo image.
3. Add a QR code image for payment.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 597: Printable invoice for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 2 | Files: index.html, styles.css

Brief

Create a clean invoice with a header row, a table using tfoot and colspan for the total, right-aligned numbers and print styles.

Learning goals

- Use tfoot and colspan
- Align numbers with tabular figures
- Design for print

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, b, time, table, thead, tbody, tfoot, th, td	justify-content: space-between, colspan, font-variant-numeric, border-top, @media print

Build guide

1. Write the header with two blocks: seller and invoice metadata.
2. Write the table with thead, tbody and a tfoot total row using colspan="2".
3. Add class n to numeric cells.
4. Flex the header with space-between.
5. Right-align .n cells.
6. Print preview and remove the border in @media print.

Project 597: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Invoice 2026-041 - Delta Kids Library</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="invoice">
    <header>
      <div><h1>Delta Kids Library</h1><p>Tanta, Egypt</p></div>
      <div class="meta"><p><b>Invoice</b> 2026-041</p><p><b>Date</b>
<time datetime="2026-09-11">11 Sep 2026</time></p></div>
    </header>
    <p><b>Bill to:</b> Customer name, Tanta</p>
    <table>
      <thead><tr><th>Item</th><th class="n">Qty</th><th
class="n">Price</th></tr></thead>
      <tbody>
        <tr><td>Story hour</td><td class="n">1</td><td
class="n">Free</td></tr>
        <tr><td>Reading club</td><td class="n">1</td><td class="n">50
EGP per month</td></tr>
        <tr><td>Homework help</td><td class="n">1</td><td
class="n">Free</td></tr>
      </tbody>
      <tfoot><tr><th colspan="2">Total</th><td class="n">see items</
td></tr></tfoot>
    </table>
    <p class="thanks">Thank you for your business.</p>
  </main>
</body>
</html>
```

Project 597: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.invoice { max-width: 46rem; margin: 2rem auto; padding: 2rem; border:
 1px solid var(--line); }
header { display: flex; justify-content: space-between; flex-wrap:
wrap; gap: 1rem; border-bottom: 3px solid var(--brand); padding-
bottom: 1rem; }
```

```
h1 { margin: 0; color: var(--brand); }
.meta p { margin: .1rem 0; text-align: right; }
table { width: 100%; border-collapse: collapse; margin-top: 1.5rem; }
th, td { padding: .6rem; border-bottom: 1px solid var(--line); text-
align: left; }
.n { text-align: right; font-variant-numeric: tabular-nums; }
tfoot th, tfoot td { font-weight: 700; border-top: 2px solid var(--
ink); border-bottom: 0; }
.thanks { margin-top: 2rem; color: var(--muted); font-style: italic; }
@media print { .invoice { border: 0; margin: 0; max-width: none; } }
```

Project 597 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Invoice 2026-041 - Delta Kids Library</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="invoice">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Delta Kids Library Tanta, Egypt	The main heading; only one per page.
Invoice 2026-041 Date <tim...	A paragraph of text.
Bill to: Customer name, Tanta	Keyword or name drawn to attention without extra importance.
<table>	Tabular data in rows and columns.
<thead><tr><th>Item</th><th class="n">Qty</th><th class="n">Price<//...	Group of header rows.

Line	What it does
<tbody>	Group of data rows.
<tr><td>Story hour</td><td class="n">1</td><td class="n">Free</td><...	A table row.
<tr><td>Reading club</td><td class="n">1</td><td class="n">50 EGP p...	A data cell.
<tfoot><tr><th colspan="2">Total</th><td class="n">see items</td><//...	Group of footer rows (totals).

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 2rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: 1rem;	Space between grid or flex items without extra margins.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-align: right;	Right-aligns inline content, typical for numbers.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	The line around the element: width, style and colour.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
font-weight: 700;	Thickness of the text.
border-top: 2px solid var(--ink);	A top border used as an accent or separator.

Declaration	What it does
@media print { .invoice { border: 0; margin: 0; max-width: none; } }	Removes the default border (for example on an iframe or button).

Check your work

- Numbers right-aligned
- Total row in tfoot
- Fits on one printed page
- Date has datetime

Exercises

1. Calculate the total with JavaScript.
2. Add a logo image.
3. Add a QR code image for payment.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 598: Printable invoice for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Create a clean invoice with a header row, a table using tfoot and colspan for the total, right-aligned numbers and print styles.

Learning goals

- Use tfoot and colspan
- Align numbers with tabular figures
- Design for print

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, b, time, table, thead, tbody, tfoot, th, td	justify-content: space-between, colspan, font-variant-numeric, border-top, @media print

Build guide

1. Write the header with two blocks: seller and invoice metadata.
2. Write the table with thead, tbody and a tfoot total row using colspan="2".
3. Add class n to numeric cells.
4. Flex the header with space-between.
5. Right-align .n cells.
6. Print preview and remove the border in @media print.

Project 598: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Invoice 2026-041 - Nubian Guest House</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="invoice">
    <header>
      <div><h1>Nubian Guest House</h1><p>Aswan, Egypt</p></div>
      <div class="meta"><p><b>Invoice</b> 2026-041</p><p><b>Date</b>
<time datetime="2026-09-11">11 Sep 2026</time></p></div>
    </header>
    <p><b>Bill to:</b> Customer name, Aswan</p>
    <table>
      <thead><tr><th>Item</th><th class="n">Qty</th><th
class="n">Price</th></tr></thead>
      <tbody>
        <tr><td>Garden room</td><td class="n">1</td><td class="n">900
EGP</td></tr>
        <tr><td>Nile view suite</td><td class="n">1</td><td
class="n">1800 EGP</td></tr>
        <tr><td>Family room</td><td class="n">1</td><td
class="n">1500 EGP</td></tr>
      </tbody>
      <tfoot><tr><th colspan="2">Total</th><td class="n">see items</
td></tr></tfoot>
    </table>
    <p class="thanks">Thank you for your business.</p>
  </main>
</body>
</html>
```

Project 598: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.invoice { max-width: 46rem; margin: 2rem auto; padding: 2rem; border:
 1px solid var(--line); }
header { display: flex; justify-content: space-between; flex-wrap:
wrap; gap: 1rem; border-bottom: 3px solid var(--brand); padding-
bottom: 1rem; }
```

```
h1 { margin: 0; color: var(--brand); }
.meta p { margin: .1rem 0; text-align: right; }
table { width: 100%; border-collapse: collapse; margin-top: 1.5rem; }
th, td { padding: .6rem; border-bottom: 1px solid var(--line); text-
align: left; }
.n { text-align: right; font-variant-numeric: tabular-nums; }
tfoot th, tfoot td { font-weight: 700; border-top: 2px solid var(--
ink); border-bottom: 0; }
.thanks { margin-top: 2rem; color: var(--muted); font-style: italic; }
@media print { .invoice { border: 0; margin: 0; max-width: none; } }
```

Project 598 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Invoice 2026-041 - Nubian Guest House</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="invoice">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Nubian Guest House Aswan, Egypt	The main heading; only one per page.
Invoice 2026-041 Date <tim...	A paragraph of text.
Bill to: Customer name, Aswan	Keyword or name drawn to attention without extra importance.
<table>	Tabular data in rows and columns.
<thead><tr><th>Item</th><th class="n">Qty</th><th class="n">Price<//...	Group of header rows.

Line	What it does
<tbody>	Group of data rows.
<tr><td>Garden room</td><td class="n">1</td><td class="n">900 EGP<//...	A table row.
<tr><td>Nile view suite</td><td class="n">1</td><td class="n">1800 ...	A data cell.
<tfoot><tr><th colspan="2">Total</th><td class="n">see items</td><//...	Group of footer rows (totals).

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 2rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: 1rem;	Space between grid or flex items without extra margins.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-align: right;	Right-aligns inline content, typical for numbers.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	The line around the element: width, style and colour.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
font-weight: 700;	Thickness of the text.
border-top: 2px solid var(--ink);	A top border used as an accent or separator.

Declaration	What it does
@media print { .invoice { border: 0; margin: 0; max-width: none; } }	Removes the default border (for example on an iframe or button).

Check your work

- Numbers right-aligned
- Total row in tfoot
- Fits on one printed page
- Date has datetime

Exercises

1. Calculate the total with JavaScript.
2. Add a logo image.
3. Add a QR code image for payment.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 599: Printable invoice for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 2 | Files: index.html, styles.css

Brief

Create a clean invoice with a header row, a table using tfoot and colspan for the total, right-aligned numbers and print styles.

Learning goals

- Use tfoot and colspan
- Align numbers with tabular figures
- Design for print

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, b, time, table, thead, tbody, tfoot, th, td	justify-content: space-between, colspan, font-variant-numeric, border-top, @media print

Build guide

1. Write the header with two blocks: seller and invoice metadata.
2. Write the table with thead, tbody and a tfoot total row using colspan="2".
3. Add class n to numeric cells.
4. Flex the header with space-between.
5. Right-align .n cells.
6. Print preview and remove the border in @media print.

Project 599: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Invoice 2026-041 - Ismailia Cycling Store</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="invoice">
    <header>
      <div><h1>Ismailia Cycling Store</h1><p>Ismailia, Egypt</p></div>
      <div class="meta"><p><b>Invoice</b> 2026-041</p><p><b>Date</b>
<time datetime="2026-09-11">11 Sep 2026</time></p></div>
    </header>
    <p><b>Bill to:</b> Customer name, Ismailia</p>
    <table>
      <thead><tr><th>Item</th><th class="n">Qty</th><th
class="n">Price</th></tr></thead>
      <tbody>
        <tr><td>City bike</td><td class="n">1</td><td class="n">6500
EGP</td></tr>
        <tr><td>Mountain bike</td><td class="n">1</td><td
class="n">11000 EGP</td></tr>
        <tr><td>Kids bike</td><td class="n">1</td><td class="n">3200
EGP</td></tr>
      </tbody>
      <tfoot><tr><th colspan="2">Total</th><td class="n">see items</
td></tr></tfoot>
    </table>
    <p class="thanks">Thank you for your business.</p>
  </main>
</body>
</html>
```

Project 599: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.invoice { max-width: 46rem; margin: 2rem auto; padding: 2rem; border:
 1px solid var(--line); }
header { display: flex; justify-content: space-between; flex-wrap:
wrap; gap: 1rem; border-bottom: 3px solid var(--brand); padding-
bottom: 1rem; }
```

```
h1 { margin: 0; color: var(--brand); }
.meta p { margin: .1rem 0; text-align: right; }
table { width: 100%; border-collapse: collapse; margin-top: 1.5rem; }
th, td { padding: .6rem; border-bottom: 1px solid var(--line); text-
align: left; }
.n { text-align: right; font-variant-numeric: tabular-nums; }
tfoot th, tfoot td { font-weight: 700; border-top: 2px solid var(--
ink); border-bottom: 0; }
.thanks { margin-top: 2rem; color: var(--muted); font-style: italic; }
@media print { .invoice { border: 0; margin: 0; max-width: none; } }
```

Project 599 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Invoice 2026-041 - Ismailia Cycling Store</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="invoice">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Ismailia Cycling Store Ismailia, Egypt	The main heading; only one per page.
Invoice 2026-041 Date <tim...	A paragraph of text.
Bill to: Customer name, Ismailia	Keyword or name drawn to attention without extra importance.
<table>	Tabular data in rows and columns.
<thead><tr><th>Item</th><th class="n">Qty</th><th class="n">Price<//...	Group of header rows.

Line	What it does
<tbody>	Group of data rows.
<tr><td>City bike</td><td class="n">1</td><td class="n">6500 EGP</t...	A table row.
<tr><td>Mountain bike</td><td class="n">1</td><td class="n">11000 E...	A data cell.
<tfoot><tr><th colspan="2">Total</th><td class="n">see items</td><//...	Group of footer rows (totals).

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 2rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: 1rem;	Space between grid or flex items without extra margins.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-align: right;	Right-aligns inline content, typical for numbers.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	The line around the element: width, style and colour.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
font-weight: 700;	Thickness of the text.
border-top: 2px solid var(--ink);	A top border used as an accent or separator.

Declaration	What it does
@media print { .invoice { border: 0; margin: 0; max-width: none; } }	Removes the default border (for example on an iframe or button).

Check your work

- Numbers right-aligned
- Total row in tfoot
- Fits on one printed page
- Date has datetime

Exercises

1. Calculate the total with JavaScript.
2. Add a logo image.
3. Add a QR code image for payment.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 600: Printable invoice for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 2 | Files: index.html, styles.css

Brief

Create a clean invoice with a header row, a table using tfoot and colspan for the total, right-aligned numbers and print styles.

Learning goals

- Use tfoot and colspan
- Align numbers with tabular figures
- Design for print

Elements and CSS used

HTML elements	CSS features
header, div, h1, p, b, time, table, thead, tbody, tfoot, th, td	justify-content: space-between, colspan, font-variant-numeric, border-top, @media print

Build guide

1. Write the header with two blocks: seller and invoice metadata.
2. Write the table with thead, tbody and a tfoot total row using colspan="2".
3. Add class n to numeric cells.
4. Flex the header with space-between.
5. Right-align .n cells.
6. Print preview and remove the border in @media print.

Project 600: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Invoice 2026-041 - Minya Coding Club</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="invoice">
    <header>
      <div><h1>Minya Coding Club</h1><p>Minya, Egypt</p></div>
      <div class="meta"><p><b>Invoice</b> 2026-041</p><p><b>Date</b>
<time datetime="2026-09-11">11 Sep 2026</time></p></div>
    </header>
    <p><b>Bill to:</b> Customer name, Minya</p>
    <table>
      <thead><tr><th>Item</th><th class="n">Qty</th><th
class="n">Price</th></tr></thead>
      <tbody>
        <tr><td>HTML weekend</td><td class="n">1</td><td
class="n">Free</td></tr>
        <tr><td>CSS art</td><td class="n">1</td><td class="n">Free</
td></tr>
        <tr><td>Scratch games</td><td class="n">1</td><td
class="n">Free</td></tr>
      </tbody>
      <tfoot><tr><th colspan="2">Total</th><td class="n">see items</
td></tr></tfoot>
    </table>
    <p class="thanks">Thank you for your business.</p>
  </main>
</body>
</html>
```

Project 600: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.invoice { max-width: 46rem; margin: 2rem auto; padding: 2rem; border:
 1px solid var(--line); }
header { display: flex; justify-content: space-between; flex-wrap:
wrap; gap: 1rem; border-bottom: 3px solid var(--brand); padding-
bottom: 1rem; }
```

```
h1 { margin: 0; color: var(--brand); }
.meta p { margin: .1rem 0; text-align: right; }
table { width: 100%; border-collapse: collapse; margin-top: 1.5rem; }
th, td { padding: .6rem; border-bottom: 1px solid var(--line); text-
align: left; }
.n { text-align: right; font-variant-numeric: tabular-nums; }
tfoot th, tfoot td { font-weight: 700; border-top: 2px solid var(--
ink); border-bottom: 0; }
.thanks { margin-top: 2rem; color: var(--muted); font-style: italic; }
@media print { .invoice { border: 0; margin: 0; max-width: none; } }
```

Project 600 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Invoice 2026-041 - Minya Coding Club</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="invoice">	The unique content of this page; exactly one per page.
<header>	Introductory content: logo, title, navigation.
Minya Coding Club Minya, Egypt	The main heading; only one per page.
Invoice 2026-041 Date <tim...	A paragraph of text.
Bill to: Customer name, Minya	Keyword or name drawn to attention without extra importance.
<table>	Tabular data in rows and columns.
<thead><tr><th>Item</th><th class="n">Qty</th><th class="n">Price<//...	Group of header rows.

Line	What it does
<tbody>	Group of data rows.
<tr><td>HTML weekend</td><td class="n">1</td><td class="n">Free</td...	A table row.
<tr><td>CSS art</td><td class="n">1</td><td class="n">Free</td></tr>	A data cell.
<tfoot><tr><th colspan="2">Total</th><td class="n">see items</td><//...	Group of footer rows (totals).

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
max-width: 46rem;	Limits how wide the element can grow, keeping lines readable.
padding: 2rem;	Space inside the element between its border and content.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: flex;	Turns the element into a flex container (one-dimensional layout).
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: 1rem;	Space between grid or flex items without extra margins.
border-bottom: 3px solid var(--brand);	A bottom border used as a separator line.
text-align: right;	Right-aligns inline content, typical for numbers.
width: 100%;	Fills the container width.
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
border-bottom: 1px solid var(--line);	The line around the element: width, style and colour.
font-variant-numeric: tabular-nums;	Makes all digits the same width so columns of numbers line up.
font-weight: 700;	Thickness of the text.
border-top: 2px solid var(--ink);	A top border used as an accent or separator.

Declaration	What it does
@media print { .invoice { border: 0; margin: 0; max-width: none; } }	Removes the default border (for example on an iframe or button).

Check your work

- Numbers right-aligned
- Total row in tfoot
- Fits on one printed page
- Date has datetime

Exercises

1. Calculate the total with JavaScript.
2. Add a logo image.
3. Add a QR code image for payment.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Feature list with icons

Level 1 | 25 projects, one per theme

Present four features as a two-column list where each item is a media object: an icon box on the left and text on the right.

Project 601: Feature list with icons for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 1 | Files: index.html, styles.css

Brief

Present four features as a two-column list where each item is a media object: an icon box on the left and text on the right.

Learning goals

- Build the media object pattern with Flexbox
- Hide decorative icons from screen readers
- Use flex: 0 0 for fixed-size boxes

Elements and CSS used

HTML elements	CSS features
ul, li, span, div, h2, p	display: flex, align-items: flex-start, flex: 0 0 3rem, place-items, grid auto-fit

Build guide

1. Write the list; each li has an icon span and a div with h2 and p.
2. Add aria-hidden="true" to the icon.
3. Make li a flex row.
4. Fix the icon size with flex: 0 0 3rem and centre the glyph.
5. Grid the list into two columns when wide.
6. Check the text wraps under itself, not under the icon.

Project 601: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Features</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What we offer</h1>
    <ul class="features">
      <li><span class="icon" aria-hidden="true">&#10004;</
span><div><h2>Learn HTML</h2><p>From your first tag to a complete
page.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9733;</
span><div><h2>CSS in Practice</h2><p>Layouts, colours and typography.
</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9829;</
span><div><h2>JavaScript Basics</h2><p>Make pages interactive.</p></
div></li>
      <li><span class="icon" aria-hidden="true">&#9992;</
span><div><h2>Web Accessibility</h2><p>Pages everyone can use.</p></
div></li>
    </ul>
  </main>
</body>
</html>
```

Project 601: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.features { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr)); }
.features li { display: flex; gap: 1rem; align-items: flex-start; }
.icon { flex: 0 0 3rem; height: 3rem; display: grid; place-items:
center; background: var(--brand); color: #fff; border-radius: 12px;
font-size: 1.4rem; }
.features h2 { margin: 0 0 .25rem; font-size: 1.1rem; }
.features p { margin: 0; color: var(--muted); }
```

Project 601 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - Features</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What we offer	The main heading; only one per page.
<ul class="features">	Unordered (bulleted) list.
✔ <h2>L...	Second-level heading for a section.
★ <h2>CS...	A paragraph of text.
♥ <h2>Ja...	One list item.

Line	What it does
✈ <h2>We...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex: 0 0 3rem;	Fixed size: never grows or shrinks.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--brand);	Background colour or image.
border-radius: 12px;	Rounds the corners.
font-size: 1.4rem;	Size of the text.

Check your work

- Icons hidden from assistive tech
- Text does not wrap under the icon
- Two columns on desktop, one on mobile
- Headings are h2

Exercises

1. Replace the glyphs with inline SVG icons.
2. Add a hover effect on the icon box.
3. Make the icon box a circle.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza

Field	Value
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 602: Feature list with icons for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 1 | Files: index.html, styles.css

Brief

Present four features as a two-column list where each item is a media object: an icon box on the left and text on the right.

Learning goals

- Build the media object pattern with Flexbox
- Hide decorative icons from screen readers
- Use flex: 0 0 for fixed-size boxes

Elements and CSS used

HTML elements	CSS features
ul, li, span, div, h2, p	display: flex, align-items: flex-start, flex: 0 0 3rem, place-items, grid auto-fit

Build guide

1. Write the list; each li has an icon span and a div with h2 and p.
2. Add aria-hidden="true" to the icon.
3. Make li a flex row.
4. Fix the icon size with flex: 0 0 3rem and centre the glyph.
5. Grid the list into two columns when wide.
6. Check the text wraps under itself, not under the icon.

Project 602: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - Features</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What we offer</h1>
    <ul class="features">
      <li><span class="icon" aria-hidden="true">&#10004;</
span><div><h2>Sourdough loaf</h2><p>Slow fermented, crisp crust.</p></
div></li>
      <li><span class="icon" aria-hidden="true">&#9733;</
span><div><h2>Croissant</h2><p>Butter, 27 layers.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9829;</
span><div><h2>Date cookies</h2><p>Traditional maamoul style.</p></
div></li>
      <li><span class="icon" aria-hidden="true">&#9992;</
span><div><h2>Baklava box</h2><p>Pistachio and honey.</p></div></li>
    </ul>
  </main>
</body>
</html>
```

Project 602: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.features { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr)); }
.features li { display: flex; gap: 1rem; align-items: flex-start; }
.icon { flex: 0 0 3rem; height: 3rem; display: grid; place-items:
center; background: var(--brand); color: #fff; border-radius: 12px;
font-size: 1.4rem; }
.features h2 { margin: 0 0 .25rem; font-size: 1.1rem; }
.features p { margin: 0; color: var(--muted); }
```

Project 602 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - Features</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What we offer	The main heading; only one per page.
<ul class="features">	Unordered (bulleted) list.
✔ <h2>S...	Second-level heading for a section.
★ <h2>Cr...	A paragraph of text.
♥ <h2>Da...	One list item.

Line	What it does
✈ <h2>Ba...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex: 0 0 3rem;	Fixed size: never grows or shrinks.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--brand);	Background colour or image.
border-radius: 12px;	Rounds the corners.
font-size: 1.4rem;	Size of the text.

Check your work

- Icons hidden from assistive tech
- Text does not wrap under the icon
- Two columns on desktop, one on mobile
- Headings are h2

Exercises

1. Replace the glyphs with inline SVG icons.
2. Add a hover effect on the icon box.
3. Make the icon box a circle.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo

Field	Value
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 603: Feature list with icons for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 1 | Files: index.html, styles.css

Brief

Present four features as a two-column list where each item is a media object: an icon box on the left and text on the right.

Learning goals

- Build the media object pattern with Flexbox
- Hide decorative icons from screen readers
- Use flex: 0 0 for fixed-size boxes

Elements and CSS used

HTML elements	CSS features
ul, li, span, div, h2, p	display: flex, align-items: flex-start, flex: 0 0 3rem, place-items, grid auto-fit

Build guide

1. Write the list; each li has an icon span and a div with h2 and p.
2. Add aria-hidden="true" to the icon.
3. Make li a flex row.
4. Fix the icon size with flex: 0 0 3rem and centre the glyph.
5. Grid the list into two columns when wide.
6. Check the text wraps under itself, not under the icon.

Project 603: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - Features</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What we offer</h1>
    <ul class="features">
      <li><span class="icon" aria-hidden="true">&#10004;</
span><div><h2>Morning yoga</h2><p>Flexibility and calm, 60 minutes.</
p></div></li>
      <li><span class="icon" aria-hidden="true">&#9733;</
span><div><h2>Strength circuit</h2><p>Full body, all levels.</p></
div></li>
      <li><span class="icon" aria-hidden="true">&#9829;</
span><div><h2>Spinning</h2><p>High energy cycling.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9992;</
span><div><h2>Personal training</h2><p>One to one coaching.</p></
div></li>
    </ul>
  </main>
</body>
</html>
```

Project 603: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.features { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr)); }
.features li { display: flex; gap: 1rem; align-items: flex-start; }
.icon { flex: 0 0 3rem; height: 3rem; display: grid; place-items:
center; background: var(--brand); color: #fff; border-radius: 12px;
font-size: 1.4rem; }
.features h2 { margin: 0 0 .25rem; font-size: 1.1rem; }
.features p { margin: 0; color: var(--muted); }
```

Project 603 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - Features</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What we offer	The main heading; only one per page.
<ul class="features">	Unordered (bulleted) list.
✔ <h2>M...	Second-level heading for a section.
★ <h2>St...	A paragraph of text.
♥ <h2>Sp...	One list item.

Line	What it does
✈ <h2>Pe...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex: 0 0 3rem;	Fixed size: never grows or shrinks.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--brand);	Background colour or image.
border-radius: 12px;	Rounds the corners.
font-size: 1.4rem;	Size of the text.

Check your work

- Icons hidden from assistive tech
- Text does not wrap under the icon
- Two columns on desktop, one on mobile
- Headings are h2

Exercises

1. Replace the glyphs with inline SVG icons.
2. Add a hover effect on the icon box.
3. Make the icon box a circle.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October

Field	Value
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 604: Feature list with icons for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 1 | Files: index.html, styles.css

Brief

Present four features as a two-column list where each item is a media object: an icon box on the left and text on the right.

Learning goals

- Build the media object pattern with Flexbox
- Hide decorative icons from screen readers
- Use flex: 0 0 for fixed-size boxes

Elements and CSS used

HTML elements	CSS features
ul, li, span, div, h2, p	display: flex, align-items: flex-start, flex: 0 0 3rem, place-items, grid auto-fit

Build guide

1. Write the list; each li has an icon span and a div with h2 and p.
2. Add aria-hidden="true" to the icon.
3. Make li a flex row.
4. Fix the icon size with flex: 0 0 3rem and centre the glyph.
5. Grid the list into two columns when wide.
6. Check the text wraps under itself, not under the icon.

Project 604: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - Features</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What we offer</h1>
    <ul class="features">
      <li><span class="icon" aria-hidden="true">&#10004;</
span><div><h2>Check-up</h2><p>Examination and cleaning.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9733;</
span><div><h2>Whitening</h2><p>Brighter smile in one visit.</p></
div></li>
      <li><span class="icon" aria-hidden="true">&#9829;</
span><div><h2>Filling</h2><p>Tooth-coloured composite.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9992;</
span><div><h2>Braces consultation</h2><p>Plan your treatment.</p></
div></li>
    </ul>
  </main>
</body>
</html>
```

Project 604: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.features { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr)); }
.features li { display: flex; gap: 1rem; align-items: flex-start; }
.icon { flex: 0 0 3rem; height: 3rem; display: grid; place-items:
center; background: var(--brand); color: #fff; border-radius: 12px;
font-size: 1.4rem; }
.features h2 { margin: 0 0 .25rem; font-size: 1.1rem; }
.features p { margin: 0; color: var(--muted); }
```

Project 604 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - Features</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What we offer	The main heading; only one per page.
<ul class="features">	Unordered (bulleted) list.
✔ <h2>C...	Second-level heading for a section.
★ <h2>Wh...	A paragraph of text.
♥ <h2>Fi...	One list item.

Line	What it does
✈ <h2>Br...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex: 0 0 3rem;	Fixed size: never grows or shrinks.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--brand);	Background colour or image.
border-radius: 12px;	Rounds the corners.
font-size: 1.4rem;	Size of the text.

Check your work

- Icons hidden from assistive tech
- Text does not wrap under the icon
- Two columns on desktop, one on mobile
- Headings are h2

Exercises

1. Replace the glyphs with inline SVG icons.
2. Add a hover effect on the icon box.
3. Make the icon box a circle.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura

Field	Value
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 605: Feature list with icons for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 1 | Files: index.html, styles.css

Brief

Present four features as a two-column list where each item is a media object: an icon box on the left and text on the right.

Learning goals

- Build the media object pattern with Flexbox
- Hide decorative icons from screen readers
- Use flex: 0 0 for fixed-size boxes

Elements and CSS used

HTML elements	CSS features
ul, li, span, div, h2, p	display: flex, align-items: flex-start, flex: 0 0 3rem, place-items, grid auto-fit

Build guide

1. Write the list; each li has an icon span and a div with h2 and p.
2. Add aria-hidden="true" to the icon.
3. Make li a flex row.
4. Fix the icon size with flex: 0 0 3rem and centre the glyph.
5. Grid the list into two columns when wide.
6. Check the text wraps under itself, not under the icon.

Project 605: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - Features</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What we offer</h1>
    <ul class="features">
      <li><span class="icon" aria-hidden="true">&#10004;</
span><div><h2>Luxor day trip</h2><p>Karnak, Valley of the Kings.</p></
div></li>
      <li><span class="icon" aria-hidden="true">&#9733;</
span><div><h2>Snorkelling</h2><p>Giftun island reefs.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9829;</
span><div><h2>Desert safari</h2><p>Quad bikes and Bedouin dinner.</
p></div></li>
      <li><span class="icon" aria-hidden="true">&#9992;</
span><div><h2>Nile cruise</h2><p>Three nights Aswan to Luxor.</p></
div></li>
    </ul>
  </main>
</body>
</html>
```

Project 605: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.features { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr)); }
.features li { display: flex; gap: 1rem; align-items: flex-start; }
.icon { flex: 0 0 3rem; height: 3rem; display: grid; place-items:
center; background: var(--brand); color: #fff; border-radius: 12px;
font-size: 1.4rem; }
.features h2 { margin: 0 0 .25rem; font-size: 1.1rem; }
.features p { margin: 0; color: var(--muted); }
```

Project 605 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - Features</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What we offer	The main heading; only one per page.
<ul class="features">	Unordered (bulleted) list.
✔ <h2>L...	Second-level heading for a section.
★ <h2>Sn...	A paragraph of text.
♥ <h2>De...	One list item.

Line	What it does
✈ <h2>Ni...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex: 0 0 3rem;	Fixed size: never grows or shrinks.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--brand);	Background colour or image.
border-radius: 12px;	Rounds the corners.
font-size: 1.4rem;	Size of the text.

Check your work

- Icons hidden from assistive tech
- Text does not wrap under the icon
- Two columns on desktop, one on mobile
- Headings are h2

Exercises

1. Replace the glyphs with inline SVG icons.
2. Add a hover effect on the icon box.
3. Make the icon box a circle.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada

Field	Value
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 606: Feature list with icons for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Present four features as a two-column list where each item is a media object: an icon box on the left and text on the right.

Learning goals

- Build the media object pattern with Flexbox
- Hide decorative icons from screen readers
- Use flex: 0 0 for fixed-size boxes

Elements and CSS used

HTML elements	CSS features
ul, li, span, div, h2, p	display: flex, align-items: flex-start, flex: 0 0 3rem, place-items, grid auto-fit

Build guide

1. Write the list; each li has an icon span and a div with h2 and p.
2. Add aria-hidden="true" to the icon.
3. Make li a flex row.
4. Fix the icon size with flex: 0 0 3rem and centre the glyph.
5. Grid the list into two columns when wide.
6. Check the text wraps under itself, not under the icon.

Project 606: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - Features</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What we offer</h1>
    <ul class="features">
      <li><span class="icon" aria-hidden="true">&#10004;</
span><div><h2>English A1</h2><p>Beginner, 8 weeks.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9733;</
span><div><h2>French B1</h2><p>Intermediate conversation.</p></div></
li>
      <li><span class="icon" aria-hidden="true">&#9829;</
span><div><h2>German A2</h2><p>Grammar and speaking.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9992;</
span><div><h2>IELTS preparation</h2><p>Exam strategies.</p></div></li>
    </ul>
  </main>
</body>
</html>
```

Project 606: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.features { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr)); }
.features li { display: flex; gap: 1rem; align-items: flex-start; }
.icon { flex: 0 0 3rem; height: 3rem; display: grid; place-items:
center; background: var(--brand); color: #fff; border-radius: 12px;
font-size: 1.4rem; }
.features h2 { margin: 0 0 .25rem; font-size: 1.1rem; }
.features p { margin: 0; color: var(--muted); }
```

Project 606 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - Features</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What we offer	The main heading; only one per page.
<ul class="features">	Unordered (bulleted) list.
✔ <h2>E...	Second-level heading for a section.
★ <h2>Fr...	A paragraph of text.
♥ <h2>Ge...	One list item.

Line	What it does
✈ <h2>IE...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex: 0 0 3rem;	Fixed size: never grows or shrinks.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--brand);	Background colour or image.
border-radius: 12px;	Rounds the corners.
font-size: 1.4rem;	Size of the text.

Check your work

- Icons hidden from assistive tech
- Text does not wrap under the icon
- Two columns on desktop, one on mobile
- Headings are h2

Exercises

1. Replace the glyphs with inline SVG icons.
2. Add a hover effect on the icon box.
3. Make the icon box a circle.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria

Field	Value
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 607: Feature list with icons for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 1 | Files: index.html, styles.css

Brief

Present four features as a two-column list where each item is a media object: an icon box on the left and text on the right.

Learning goals

- Build the media object pattern with Flexbox
- Hide decorative icons from screen readers
- Use flex: 0 0 for fixed-size boxes

Elements and CSS used

HTML elements	CSS features
ul, li, span, div, h2, p	display: flex, align-items: flex-start, flex: 0 0 3rem, place-items, grid auto-fit

Build guide

1. Write the list; each li has an icon span and a div with h2 and p.
2. Add aria-hidden="true" to the icon.
3. Make li a flex row.
4. Fix the icon size with flex: 0 0 3rem and centre the glyph.
5. Grid the list into two columns when wide.
6. Check the text wraps under itself, not under the icon.

Project 607: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - Features</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What we offer</h1>
    <ul class="features">
      <li><span class="icon" aria-hidden="true">&#10004;</
span><div><h2>Flat white</h2><p>Double shot, silky milk.</p></div></
li>
      <li><span class="icon" aria-hidden="true">&#9733;</
span><div><h2>Cold brew</h2><p>18 hours steeped.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9829;</
span><div><h2>Hibiscus iced tea</h2><p>Karkade with mint.</p></div></
li>
      <li><span class="icon" aria-hidden="true">&#9992;</
span><div><h2>Cheesecake</h2><p>Baked, with berries.</p></div></li>
    </ul>
  </main>
</body>
</html>
```

Project 607: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.features { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr)); }
.features li { display: flex; gap: 1rem; align-items: flex-start; }
.icon { flex: 0 0 3rem; height: 3rem; display: grid; place-items:
center; background: var(--brand); color: #fff; border-radius: 12px;
font-size: 1.4rem; }
.features h2 { margin: 0 0 .25rem; font-size: 1.1rem; }
.features p { margin: 0; color: var(--muted); }
```

Project 607 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - Features</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What we offer	The main heading; only one per page.
<ul class="features">	Unordered (bulleted) list.
✔ <h2>F...	Second-level heading for a section.
★ <h2>Co...	A paragraph of text.
♥ <h2>Hi...	One list item.

Line	What it does
✈ <h2>Ch...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex: 0 0 3rem;	Fixed size: never grows or shrinks.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--brand);	Background colour or image.
border-radius: 12px;	Rounds the corners.
font-size: 1.4rem;	Size of the text.

Check your work

- Icons hidden from assistive tech
- Text does not wrap under the icon
- Two columns on desktop, one on mobile
- Headings are h2

Exercises

1. Replace the glyphs with inline SVG icons.
2. Add a hover effect on the icon box.
3. Make the icon box a circle.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek

Field	Value
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 608: Feature list with icons for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 1 | Files: index.html, styles.css

Brief

Present four features as a two-column list where each item is a media object: an icon box on the left and text on the right.

Learning goals

- Build the media object pattern with Flexbox
- Hide decorative icons from screen readers
- Use flex: 0 0 for fixed-size boxes

Elements and CSS used

HTML elements	CSS features
ul, li, span, div, h2, p	display: flex, align-items: flex-start, flex: 0 0 3rem, place-items, grid auto-fit

Build guide

1. Write the list; each li has an icon span and a div with h2 and p.
2. Add aria-hidden="true" to the icon.
3. Make li a flex row.
4. Fix the icon size with flex: 0 0 3rem and centre the glyph.
5. Grid the list into two columns when wide.
6. Check the text wraps under itself, not under the icon.

Project 608: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - Features</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What we offer</h1>
    <ul class="features">
      <li><span class="icon" aria-hidden="true">&#10004;</
span><div><h2>Mount Sinai sunrise</h2><p>Night climb, 7 km.</p></
div></li>
      <li><span class="icon" aria-hidden="true">&#9733;</
span><div><h2>Blue Desert loop</h2><p>Easy day walk.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9829;</
span><div><h2>Wadi Gnai</h2><p>Palms and pools.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9992;</
span><div><h2>Three-day traverse</h2><p>Camping under stars.</p></
div></li>
    </ul>
  </main>
</body>
</html>
```

Project 608: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.features { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr)); }
.features li { display: flex; gap: 1rem; align-items: flex-start; }
.icon { flex: 0 0 3rem; height: 3rem; display: grid; place-items:
center; background: var(--brand); color: #fff; border-radius: 12px;
font-size: 1.4rem; }
.features h2 { margin: 0 0 .25rem; font-size: 1.1rem; }
.features p { margin: 0; color: var(--muted); }
```

Project 608 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - Features</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What we offer	The main heading; only one per page.
<ul class="features">	Unordered (bulleted) list.
✔ <h2>M...	Second-level heading for a section.
★ <h2>Bl...	A paragraph of text.
♥ <h2>Wa...	One list item.

Line	What it does
✈ <h2>Th...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex: 0 0 3rem;	Fixed size: never grows or shrinks.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--brand);	Background colour or image.
border-radius: 12px;	Rounds the corners.
font-size: 1.4rem;	Size of the text.

Check your work

- Icons hidden from assistive tech
- Text does not wrap under the icon
- Two columns on desktop, one on mobile
- Headings are h2

Exercises

1. Replace the glyphs with inline SVG icons.
2. Add a hover effect on the icon box.
3. Make the icon box a circle.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine

Field	Value
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 609: Feature list with icons for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 1 | Files: index.html, styles.css

Brief

Present four features as a two-column list where each item is a media object: an icon box on the left and text on the right.

Learning goals

- Build the media object pattern with Flexbox
- Hide decorative icons from screen readers
- Use flex: 0 0 for fixed-size boxes

Elements and CSS used

HTML elements	CSS features
ul, li, span, div, h2, p	display: flex, align-items: flex-start, flex: 0 0 3rem, place-items, grid auto-fit

Build guide

1. Write the list; each li has an icon span and a div with h2 and p.
2. Add aria-hidden="true" to the icon.
3. Make li a flex row.
4. Fix the icon size with flex: 0 0 3rem and centre the glyph.
5. Grid the list into two columns when wide.
6. Check the text wraps under itself, not under the icon.

Project 609: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - Features</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What we offer</h1>
    <ul class="features">
      <li><span class="icon" aria-hidden="true">&#10004;</
span><div><h2>Portrait session</h2><p>One hour, 20 edited photos.</
p></div></li>
      <li><span class="icon" aria-hidden="true">&#9733;</
span><div><h2>Wedding day</h2><p>Full coverage, two photographers.</
p></div></li>
      <li><span class="icon" aria-hidden="true">&#9829;</
span><div><h2>Product shoot</h2><p>White background, 10 items.</p></
div></li>
      <li><span class="icon" aria-hidden="true">&#9992;</
span><div><h2>Family session</h2><p>Outdoor, golden hour.</p></div></
li>
    </ul>
  </main>
</body>
</html>
```

Project 609: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.features { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr)); }
.features li { display: flex; gap: 1rem; align-items: flex-start; }
.icon { flex: 0 0 3rem; height: 3rem; display: grid; place-items:
center; background: var(--brand); color: #fff; border-radius: 12px;
font-size: 1.4rem; }
.features h2 { margin: 0 0 .25rem; font-size: 1.1rem; }
.features p { margin: 0; color: var(--muted); }
```

Project 609 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - Features</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What we offer	The main heading; only one per page.
<ul class="features">	Unordered (bulleted) list.
✔ <h2>P...	Second-level heading for a section.
★ <h2>We...	A paragraph of text.
♥ <h2>Pr...	One list item.

Line	What it does
✈ <h2>Fa...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex: 0 0 3rem;	Fixed size: never grows or shrinks.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--brand);	Background colour or image.
border-radius: 12px;	Rounds the corners.
font-size: 1.4rem;	Size of the text.

Check your work

- Icons hidden from assistive tech
- Text does not wrap under the icon
- Two columns on desktop, one on mobile
- Headings are h2

Exercises

1. Replace the glyphs with inline SVG icons.
2. Add a hover effect on the icon box.
3. Make the icon box a circle.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi

Field	Value
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 610: Feature list with icons for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 1 | Files: index.html, styles.css

Brief

Present four features as a two-column list where each item is a media object: an icon box on the left and text on the right.

Learning goals

- Build the media object pattern with Flexbox
- Hide decorative icons from screen readers
- Use flex: 0 0 for fixed-size boxes

Elements and CSS used

HTML elements	CSS features
ul, li, span, div, h2, p	display: flex, align-items: flex-start, flex: 0 0 3rem, place-items, grid auto-fit

Build guide

1. Write the list; each li has an icon span and a div with h2 and p.
2. Add aria-hidden="true" to the icon.
3. Make li a flex row.
4. Fix the icon size with flex: 0 0 3rem and centre the glyph.
5. Grid the list into two columns when wide.
6. Check the text wraps under itself, not under the icon.

Project 610: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - Features</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What we offer</h1>
    <ul class="features">
      <li><span class="icon" aria-hidden="true">&#10004;</
span><div><h2>Dotted notebook</h2><p>A5, 160 pages.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9733;</
span><div><h2>Fountain pen</h2><p>Steel nib, refillable.</p></div></
li>
      <li><span class="icon" aria-hidden="true">&#9829;</
span><div><h2>Washi tape set</h2><p>Six patterns.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9992;</
span><div><h2>Desk planner</h2><p>Weekly, undated.</p></div></li>
    </ul>
  </main>
</body>
</html>
```

Project 610: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.features { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr)); }
.features li { display: flex; gap: 1rem; align-items: flex-start; }
.icon { flex: 0 0 3rem; height: 3rem; display: grid; place-items:
center; background: var(--brand); color: #fff; border-radius: 12px;
font-size: 1.4rem; }
.features h2 { margin: 0 0 .25rem; font-size: 1.1rem; }
.features p { margin: 0; color: var(--muted); }
```

Project 610 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - Features</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What we offer	The main heading; only one per page.
<ul class="features">	Unordered (bulleted) list.
✔ <h2>D...	Second-level heading for a section.
★ <h2>Fo...	A paragraph of text.
♥ <h2>Wa...	One list item.

Line	What it does
✈ <h2>De...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex: 0 0 3rem;	Fixed size: never grows or shrinks.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--brand);	Background colour or image.
border-radius: 12px;	Rounds the corners.
font-size: 1.4rem;	Size of the text.

Check your work

- Icons hidden from assistive tech
- Text does not wrap under the icon
- Two columns on desktop, one on mobile
- Headings are h2

Exercises

1. Replace the glyphs with inline SVG icons.
2. Add a hover effect on the icon box.
3. Make the icon box a circle.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis

Field	Value
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 611: Feature list with icons for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 1 | Files: index.html, styles.css

Brief

Present four features as a two-column list where each item is a media object: an icon box on the left and text on the right.

Learning goals

- Build the media object pattern with Flexbox
- Hide decorative icons from screen readers
- Use flex: 0 0 for fixed-size boxes

Elements and CSS used

HTML elements	CSS features
ul, li, span, div, h2, p	display: flex, align-items: flex-start, flex: 0 0 3rem, place-items, grid auto-fit

Build guide

1. Write the list; each li has an icon span and a div with h2 and p.
2. Add aria-hidden="true" to the icon.
3. Make li a flex row.
4. Fix the icon size with flex: 0 0 3rem and centre the glyph.
5. Grid the list into two columns when wide.
6. Check the text wraps under itself, not under the icon.

Project 611: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - Features</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What we offer</h1>
    <ul class="features">
      <li><span class="icon" aria-hidden="true">&#10004;</
span><div><h2>Monstera</h2><p>Large leaves, easy care.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9733;</
span><div><h2>Snake plant</h2><p>Survives anything.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9829;</
span><div><h2>Basil pot</h2><p>Kitchen herb.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9992;</
span><div><h2>Olive tree</h2><p>Balcony sized.</p></div></li>
    </ul>
  </main>
</body>
</html>
```

Project 611: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.features { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr)); }
.features li { display: flex; gap: 1rem; align-items: flex-start; }
.icon { flex: 0 0 3rem; height: 3rem; display: grid; place-items:
center; background: var(--brand); color: #fff; border-radius: 12px;
font-size: 1.4rem; }
.features h2 { margin: 0 0 .25rem; font-size: 1.1rem; }
.features p { margin: 0; color: var(--muted); }
```

Project 611 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - Features</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What we offer	The main heading; only one per page.
<ul class="features">	Unordered (bulleted) list.
✔ <h2>M...	Second-level heading for a section.
★ <h2>Sn...	A paragraph of text.
♥ <h2>Ba...	One list item.

Line	What it does
✈ <h2>Ol...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex: 0 0 3rem;	Fixed size: never grows or shrinks.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--brand);	Background colour or image.
border-radius: 12px;	Rounds the corners.
font-size: 1.4rem;	Size of the text.

Check your work

- Icons hidden from assistive tech
- Text does not wrap under the icon
- Two columns on desktop, one on mobile
- Headings are h2

Exercises

1. Replace the glyphs with inline SVG icons.
2. Add a hover effect on the icon box.
3. Make the icon box a circle.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed

Field	Value
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 612: Feature list with icons for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 1 | Files: index.html, styles.css

Brief

Present four features as a two-column list where each item is a media object: an icon box on the left and text on the right.

Learning goals

- Build the media object pattern with Flexbox
- Hide decorative icons from screen readers
- Use flex: 0 0 for fixed-size boxes

Elements and CSS used

HTML elements	CSS features
ul, li, span, div, h2, p	display: flex, align-items: flex-start, flex: 0 0 3rem, place-items, grid auto-fit

Build guide

1. Write the list; each li has an icon span and a div with h2 and p.
2. Add aria-hidden="true" to the icon.
3. Make li a flex row.
4. Fix the icon size with flex: 0 0 3rem and centre the glyph.
5. Grid the list into two columns when wide.
6. Check the text wraps under itself, not under the icon.

Project 612: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - Features</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What we offer</h1>
    <ul class="features">
      <li><span class="icon" aria-hidden="true">&#10004;</
span><div><h2>Oak dining table</h2><p>Seats six.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9733;</
span><div><h2>Bookshelf</h2><p>Five shelves, walnut.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9829;</
span><div><h2>Bedside table</h2><p>One drawer.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9992;</
span><div><h2>Coffee table</h2><p>Round, ash wood.</p></div></li>
    </ul>
  </main>
</body>
</html>
```

Project 612: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.features { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr)); }
.features li { display: flex; gap: 1rem; align-items: flex-start; }
.icon { flex: 0 0 3rem; height: 3rem; display: grid; place-items:
center; background: var(--brand); color: #fff; border-radius: 12px;
font-size: 1.4rem; }
.features h2 { margin: 0 0 .25rem; font-size: 1.1rem; }
.features p { margin: 0; color: var(--muted); }
```

Project 612 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - Features</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What we offer	The main heading; only one per page.
<ul class="features">	Unordered (bulleted) list.
✔ <h2>O...	Second-level heading for a section.
★ <h2>Bo...	A paragraph of text.
♥ <h2>Be...	One list item.

Line	What it does
✈ <h2>Co...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex: 0 0 3rem;	Fixed size: never grows or shrinks.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--brand);	Background colour or image.
border-radius: 12px;	Rounds the corners.
font-size: 1.4rem;	Size of the text.

Check your work

- Icons hidden from assistive tech
- Text does not wrap under the icon
- Two columns on desktop, one on mobile
- Headings are h2

Exercises

1. Replace the glyphs with inline SVG icons.
2. Add a hover effect on the icon box.
3. Make the icon box a circle.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta

Field	Value
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 613: Feature list with icons for Byte Repair

Theme: Byte Repair (Nasr City) | Level 1 | Files: index.html, styles.css

Brief

Present four features as a two-column list where each item is a media object: an icon box on the left and text on the right.

Learning goals

- Build the media object pattern with Flexbox
- Hide decorative icons from screen readers
- Use flex: 0 0 for fixed-size boxes

Elements and CSS used

HTML elements	CSS features
ul, li, span, div, h2, p	display: flex, align-items: flex-start, flex: 0 0 3rem, place-items, grid auto-fit

Build guide

1. Write the list; each li has an icon span and a div with h2 and p.
2. Add aria-hidden="true" to the icon.
3. Make li a flex row.
4. Fix the icon size with flex: 0 0 3rem and centre the glyph.
5. Grid the list into two columns when wide.
6. Check the text wraps under itself, not under the icon.

Project 613: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - Features</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What we offer</h1>
    <ul class="features">
      <li><span class="icon" aria-hidden="true">&#10004;</
span><div><h2>Screen replacement</h2><p>Most phones, 1 hour.</p></
div></li>
      <li><span class="icon" aria-hidden="true">&#9733;</
span><div><h2>Battery swap</h2><p>Original cells.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9829;</
span><div><h2>Laptop cleaning</h2><p>Fans and thermal paste.</p></
div></li>
      <li><span class="icon" aria-hidden="true">&#9992;</
span><div><h2>Data recovery</h2><p>Drives and cards.</p></div></li>
    </ul>
  </main>
</body>
</html>
```

Project 613: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.features { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr)); }
.features li { display: flex; gap: 1rem; align-items: flex-start; }
.icon { flex: 0 0 3rem; height: 3rem; display: grid; place-items:
center; background: var(--brand); color: #fff; border-radius: 12px;
font-size: 1.4rem; }
.features h2 { margin: 0 0 .25rem; font-size: 1.1rem; }
.features p { margin: 0; color: var(--muted); }
```

Project 613 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - Features</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What we offer	The main heading; only one per page.
<ul class="features">	Unordered (bulleted) list.
✔ <h2>S...	Second-level heading for a section.
★ <h2>Ba...	A paragraph of text.
♥ <h2>La...	One list item.

Line	What it does
✈ <h2>Da...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex: 0 0 3rem;	Fixed size: never grows or shrinks.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--brand);	Background colour or image.
border-radius: 12px;	Rounds the corners.
font-size: 1.4rem;	Size of the text.

Check your work

- Icons hidden from assistive tech
- Text does not wrap under the icon
- Two columns on desktop, one on mobile
- Headings are h2

Exercises

1. Replace the glyphs with inline SVG icons.
2. Add a hover effect on the icon box.
3. Make the icon box a circle.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City

Field	Value
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 614: Feature list with icons for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 1 | Files: index.html, styles.css

Brief

Present four features as a two-column list where each item is a media object: an icon box on the left and text on the right.

Learning goals

- Build the media object pattern with Flexbox
- Hide decorative icons from screen readers
- Use flex: 0 0 for fixed-size boxes

Elements and CSS used

HTML elements	CSS features
ul, li, span, div, h2, p	display: flex, align-items: flex-start, flex: 0 0 3rem, place-items, grid auto-fit

Build guide

1. Write the list; each li has an icon span and a div with h2 and p.
2. Add aria-hidden="true" to the icon.
3. Make li a flex row.
4. Fix the icon size with flex: 0 0 3rem and centre the glyph.
5. Grid the list into two columns when wide.
6. Check the text wraps under itself, not under the icon.

Project 614: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - Features</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What we offer</h1>
    <ul class="features">
      <li><span class="icon" aria-hidden="true">&#10004;</
span><div><h2>Full grooming</h2><p>Bath, cut and nails.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9733;</
span><div><h2>Day boarding</h2><p>Play and rest.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9829;</
span><div><h2>Vaccination</h2><p>Annual boosters.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9992;</
span><div><h2>Dog walking</h2><p>30 minutes.</p></div></li>
    </ul>
  </main>
</body>
</html>
```

Project 614: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.features { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr)); }
.features li { display: flex; gap: 1rem; align-items: flex-start; }
.icon { flex: 0 0 3rem; height: 3rem; display: grid; place-items:
center; background: var(--brand); color: #fff; border-radius: 12px;
font-size: 1.4rem; }
.features h2 { margin: 0 0 .25rem; font-size: 1.1rem; }
.features p { margin: 0; color: var(--muted); }
```

Project 614 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - Features</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What we offer	The main heading; only one per page.
<ul class="features">	Unordered (bulleted) list.
✔ <h2>F...	Second-level heading for a section.
★ <h2>Da...	A paragraph of text.
♥ <h2>Va...	One list item.

Line	What it does
✈ <h2>Do...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex: 0 0 3rem;	Fixed size: never grows or shrinks.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--brand);	Background colour or image.
border-radius: 12px;	Rounds the corners.
font-size: 1.4rem;	Size of the text.

Check your work

- Icons hidden from assistive tech
- Text does not wrap under the icon
- Two columns on desktop, one on mobile
- Headings are h2

Exercises

1. Replace the glyphs with inline SVG icons.
2. Add a hover effect on the icon box.
3. Make the icon box a circle.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo

Field	Value
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 615: Feature list with icons for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Present four features as a two-column list where each item is a media object: an icon box on the left and text on the right.

Learning goals

- Build the media object pattern with Flexbox
- Hide decorative icons from screen readers
- Use flex: 0 0 for fixed-size boxes

Elements and CSS used

HTML elements	CSS features
ul, li, span, div, h2, p	display: flex, align-items: flex-start, flex: 0 0 3rem, place-items, grid auto-fit

Build guide

1. Write the list; each li has an icon span and a div with h2 and p.
2. Add aria-hidden="true" to the icon.
3. Make li a flex row.
4. Fix the icon size with flex: 0 0 3rem and centre the glyph.
5. Grid the list into two columns when wide.
6. Check the text wraps under itself, not under the icon.

Project 615: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - Features</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What we offer</h1>
    <ul class="features">
      <li><span class="icon" aria-hidden="true">&#10004;</
span><div><h2>Taster session</h2><p>Two hours on the water.</p></
div></li>
      <li><span class="icon" aria-hidden="true">&#9733;</
span><div><h2>Beginner course</h2><p>Five sessions.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9829;</
span><div><h2>Racing clinic</h2><p>Tactics and trim.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9992;</
span><div><h2>Private lesson</h2><p>One to one.</p></div></li>
    </ul>
  </main>
</body>
</html>
```

Project 615: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.features { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr)); }
.features li { display: flex; gap: 1rem; align-items: flex-start; }
.icon { flex: 0 0 3rem; height: 3rem; display: grid; place-items:
center; background: var(--brand); color: #fff; border-radius: 12px;
font-size: 1.4rem; }
.features h2 { margin: 0 0 .25rem; font-size: 1.1rem; }
.features p { margin: 0; color: var(--muted); }
```

Project 615 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - Features</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What we offer	The main heading; only one per page.
<ul class="features">	Unordered (bulleted) list.
✔ <h2>T...	Second-level heading for a section.
★ <h2>Be...	A paragraph of text.
♥ <h2>Ra...	One list item.

Line	What it does
✈ <h2>Pr...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex: 0 0 3rem;	Fixed size: never grows or shrinks.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--brand);	Background colour or image.
border-radius: 12px;	Rounds the corners.
font-size: 1.4rem;	Size of the text.

Check your work

- Icons hidden from assistive tech
- Text does not wrap under the icon
- Two columns on desktop, one on mobile
- Headings are h2

Exercises

1. Replace the glyphs with inline SVG icons.
2. Add a hover effect on the icon box.
3. Make the icon box a circle.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria

Field	Value
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 616: Feature list with icons for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Present four features as a two-column list where each item is a media object: an icon box on the left and text on the right.

Learning goals

- Build the media object pattern with Flexbox
- Hide decorative icons from screen readers
- Use flex: 0 0 for fixed-size boxes

Elements and CSS used

HTML elements	CSS features
ul, li, span, div, h2, p	display: flex, align-items: flex-start, flex: 0 0 3rem, place-items, grid auto-fit

Build guide

1. Write the list; each li has an icon span and a div with h2 and p.
2. Add aria-hidden="true" to the icon.
3. Make li a flex row.
4. Fix the icon size with flex: 0 0 3rem and centre the glyph.
5. Grid the list into two columns when wide.
6. Check the text wraps under itself, not under the icon.

Project 616: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - Features</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What we offer</h1>
    <ul class="features">
      <li><span class="icon" aria-hidden="true">&#10004;</
span><div><h2>Lotus pendant</h2><p>Sterling silver.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9733;</
span><div><h2>Brass cuff</h2><p>Hand engraved.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9829;</
span><div><h2>Bead earrings</h2><p>Recycled glass.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9992;</
span><div><h2>Ankh ring</h2><p>Adjustable.</p></div></li>
    </ul>
  </main>
</body>
</html>
```

Project 616: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.features { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr)); }
.features li { display: flex; gap: 1rem; align-items: flex-start; }
.icon { flex: 0 0 3rem; height: 3rem; display: grid; place-items:
center; background: var(--brand); color: #fff; border-radius: 12px;
font-size: 1.4rem; }
.features h2 { margin: 0 0 .25rem; font-size: 1.1rem; }
.features p { margin: 0; color: var(--muted); }
```

Project 616 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - Features</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What we offer	The main heading; only one per page.
<ul class="features">	Unordered (bulleted) list.
✔ <h2>L...	Second-level heading for a section.
★ <h2>Br...	A paragraph of text.
♥ <h2>Be...	One list item.

Line	What it does
✈ <h2>An...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex: 0 0 3rem;	Fixed size: never grows or shrinks.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--brand);	Background colour or image.
border-radius: 12px;	Rounds the corners.
font-size: 1.4rem;	Size of the text.

Check your work

- Icons hidden from assistive tech
- Text does not wrap under the icon
- Two columns on desktop, one on mobile
- Headings are h2

Exercises

1. Replace the glyphs with inline SVG icons.
2. Add a hover effect on the icon box.
3. Make the icon box a circle.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan

Field	Value
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 617: Feature list with icons for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 1 | Files: index.html, styles.css

Brief

Present four features as a two-column list where each item is a media object: an icon box on the left and text on the right.

Learning goals

- Build the media object pattern with Flexbox
- Hide decorative icons from screen readers
- Use flex: 0 0 for fixed-size boxes

Elements and CSS used

HTML elements	CSS features
ul, li, span, div, h2, p	display: flex, align-items: flex-start, flex: 0 0 3rem, place-items, grid auto-fit

Build guide

1. Write the list; each li has an icon span and a div with h2 and p.
2. Add aria-hidden="true" to the icon.
3. Make li a flex row.
4. Fix the icon size with flex: 0 0 3rem and centre the glyph.
5. Grid the list into two columns when wide.
6. Check the text wraps under itself, not under the icon.

Project 617: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - Features</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What we offer</h1>
    <ul class="features">
      <li><span class="icon" aria-hidden="true">&#10004;</
span><div><h2>Intro to the wheel</h2><p>Three hours, take home a bowl.
</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9733;</
span><div><h2>Glazing day</h2><p>Colour your pieces.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9829;</
span><div><h2>Kids clay class</h2><p>Ages 6 to 12.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9992;</
span><div><h2>Weekend retreat</h2><p>Two days with meals.</p></div></
li>
    </ul>
  </main>
</body>
</html>
```

Project 617: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.features { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr)); }
.features li { display: flex; gap: 1rem; align-items: flex-start; }
.icon { flex: 0 0 3rem; height: 3rem; display: grid; place-items:
center; background: var(--brand); color: #fff; border-radius: 12px;
font-size: 1.4rem; }
.features h2 { margin: 0 0 .25rem; font-size: 1.1rem; }
.features p { margin: 0; color: var(--muted); }
```

Project 617 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - Features</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What we offer	The main heading; only one per page.
<ul class="features">	Unordered (bulleted) list.
✔ <h2>I...	Second-level heading for a section.
★ <h2>Gl...	A paragraph of text.
♥ <h2>Ki...	One list item.

Line	What it does
✈ <h2>We...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex: 0 0 3rem;	Fixed size: never grows or shrinks.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--brand);	Background colour or image.
border-radius: 12px;	Rounds the corners.
font-size: 1.4rem;	Size of the text.

Check your work

- Icons hidden from assistive tech
- Text does not wrap under the icon
- Two columns on desktop, one on mobile
- Headings are h2

Exercises

1. Replace the glyphs with inline SVG icons.
2. Add a hover effect on the icon box.
3. Make the icon box a circle.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village

Field	Value
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 618: Feature list with icons for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 1 | Files: index.html, styles.css

Brief

Present four features as a two-column list where each item is a media object: an icon box on the left and text on the right.

Learning goals

- Build the media object pattern with Flexbox
- Hide decorative icons from screen readers
- Use flex: 0 0 for fixed-size boxes

Elements and CSS used

HTML elements	CSS features
ul, li, span, div, h2, p	display: flex, align-items: flex-start, flex: 0 0 3rem, place-items, grid auto-fit

Build guide

1. Write the list; each li has an icon span and a div with h2 and p.
2. Add aria-hidden="true" to the icon.
3. Make li a flex row.
4. Fix the icon size with flex: 0 0 3rem and centre the glyph.
5. Grid the list into two columns when wide.
6. Check the text wraps under itself, not under the icon.

Project 618: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - Features</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What we offer</h1>
    <ul class="features">
      <li><span class="icon" aria-hidden="true">&#10004;</
span><div><h2>Haircut and blow-dry</h2><p>Consultation included.</p></
div></li>
      <li><span class="icon" aria-hidden="true">&#9733;</
span><div><h2>Manicure</h2><p>Classic or gel.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9829;</
span><div><h2>Facial</h2><p>Deep cleanse, 60 minutes.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9992;</
span><div><h2>Bridal package</h2><p>Hair, make-up and nails.</p></
div></li>
    </ul>
  </main>
</body>
</html>
```

Project 618: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.features { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr)); }
.features li { display: flex; gap: 1rem; align-items: flex-start; }
.icon { flex: 0 0 3rem; height: 3rem; display: grid; place-items:
center; background: var(--brand); color: #fff; border-radius: 12px;
font-size: 1.4rem; }
.features h2 { margin: 0 0 .25rem; font-size: 1.1rem; }
.features p { margin: 0; color: var(--muted); }
```

Project 618 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - Features</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What we offer	The main heading; only one per page.
<ul class="features">	Unordered (bulleted) list.
✔ <h2>H...	Second-level heading for a section.
★ <h2>Ma...	A paragraph of text.
♥ <h2>Fa...	One list item.

Line	What it does
✈ <h2>Br...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex: 0 0 3rem;	Fixed size: never grows or shrinks.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--brand);	Background colour or image.
border-radius: 12px;	Rounds the corners.
font-size: 1.4rem;	Size of the text.

Check your work

- Icons hidden from assistive tech
- Text does not wrap under the icon
- Two columns on desktop, one on mobile
- Headings are h2

Exercises

1. Replace the glyphs with inline SVG icons.
2. Add a hover effect on the icon box.
3. Make the icon box a circle.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki

Field	Value
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 619: Feature list with icons for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 1 | Files: index.html, styles.css

Brief

Present four features as a two-column list where each item is a media object: an icon box on the left and text on the right.

Learning goals

- Build the media object pattern with Flexbox
- Hide decorative icons from screen readers
- Use flex: 0 0 for fixed-size boxes

Elements and CSS used

HTML elements	CSS features
ul, li, span, div, h2, p	display: flex, align-items: flex-start, flex: 0 0 3rem, place-items, grid auto-fit

Build guide

1. Write the list; each li has an icon span and a div with h2 and p.
2. Add aria-hidden="true" to the icon.
3. Make li a flex row.
4. Fix the icon size with flex: 0 0 3rem and centre the glyph.
5. Grid the list into two columns when wide.
6. Check the text wraps under itself, not under the icon.

Project 619: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - Features</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What we offer</h1>
    <ul class="features">
      <li><span class="icon" aria-hidden="true">&#10004;</
span><div><h2>Oil change</h2><p>Filter included.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9733;</
span><div><h2>Brake pads</h2><p>Front axle.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9829;</
span><div><h2>Air conditioning</h2><p>Recharge and check.</p></div></
li>
      <li><span class="icon" aria-hidden="true">&#9992;</
span><div><h2>Pre-purchase inspection</h2><p>120 point check.</p></
div></li>
    </ul>
  </main>
</body>
</html>
```

Project 619: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.features { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr)); }
.features li { display: flex; gap: 1rem; align-items: flex-start; }
.icon { flex: 0 0 3rem; height: 3rem; display: grid; place-items:
center; background: var(--brand); color: #fff; border-radius: 12px;
font-size: 1.4rem; }
.features h2 { margin: 0 0 .25rem; font-size: 1.1rem; }
.features p { margin: 0; color: var(--muted); }
```

Project 619 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - Features</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What we offer	The main heading; only one per page.
<ul class="features">	Unordered (bulleted) list.
✔ <h2>O...	Second-level heading for a section.
★ <h2>Br...	A paragraph of text.
♥ <h2>Ai...	One list item.

Line	What it does
✈ <h2>Pr...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex: 0 0 3rem;	Fixed size: never grows or shrinks.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--brand);	Background colour or image.
border-radius: 12px;	Rounds the corners.
font-size: 1.4rem;	Size of the text.

Check your work

- Icons hidden from assistive tech
- Text does not wrap under the icon
- Two columns on desktop, one on mobile
- Headings are h2

Exercises

1. Replace the glyphs with inline SVG icons.
2. Add a hover effect on the icon box.
3. Make the icon box a circle.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez

Field	Value
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 620: Feature list with icons for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 1 | Files: index.html, styles.css

Brief

Present four features as a two-column list where each item is a media object: an icon box on the left and text on the right.

Learning goals

- Build the media object pattern with Flexbox
- Hide decorative icons from screen readers
- Use flex: 0 0 for fixed-size boxes

Elements and CSS used

HTML elements	CSS features
ul, li, span, div, h2, p	display: flex, align-items: flex-start, flex: 0 0 3rem, place-items, grid auto-fit

Build guide

1. Write the list; each li has an icon span and a div with h2 and p.
2. Add aria-hidden="true" to the icon.
3. Make li a flex row.
4. Fix the icon size with flex: 0 0 3rem and centre the glyph.
5. Grid the list into two columns when wide.
6. Check the text wraps under itself, not under the icon.

Project 620: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - Features</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What we offer</h1>
    <ul class="features">
      <li><span class="icon" aria-hidden="true">&#10004;</
span><div><h2>Oud for beginners</h2><p>Eight weekly lessons.</p></
div></li>
      <li><span class="icon" aria-hidden="true">&#9733;</
span><div><h2>Piano grade 1</h2><p>Theory and practice.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9829;</
span><div><h2>Guitar chords</h2><p>Play songs in a month.</p></div></
li>
      <li><span class="icon" aria-hidden="true">&#9992;</
span><div><h2>Voice coaching</h2><p>Breathing and range.</p></div></
li>
    </ul>
  </main>
</body>
</html>
```

Project 620: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.features { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr)); }
.features li { display: flex; gap: 1rem; align-items: flex-start; }
.icon { flex: 0 0 3rem; height: 3rem; display: grid; place-items:
center; background: var(--brand); color: #fff; border-radius: 12px;
font-size: 1.4rem; }
.features h2 { margin: 0 0 .25rem; font-size: 1.1rem; }
.features p { margin: 0; color: var(--muted); }
```

Project 620 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - Features</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What we offer	The main heading; only one per page.
<ul class="features">	Unordered (bulleted) list.
✔ <h2>O...	Second-level heading for a section.
★ <h2>Pi...	A paragraph of text.
♥ <h2>Gu...	One list item.

Line	What it does
✈ <h2>Vo...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex: 0 0 3rem;	Fixed size: never grows or shrinks.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--brand);	Background colour or image.
border-radius: 12px;	Rounds the corners.
font-size: 1.4rem;	Size of the text.

Check your work

- Icons hidden from assistive tech
- Text does not wrap under the icon
- Two columns on desktop, one on mobile
- Headings are h2

Exercises

1. Replace the glyphs with inline SVG icons.
2. Add a hover effect on the icon box.
3. Make the icon box a circle.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor

Field	Value
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 621: Feature list with icons for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 1 | Files: index.html, styles.css

Brief

Present four features as a two-column list where each item is a media object: an icon box on the left and text on the right.

Learning goals

- Build the media object pattern with Flexbox
- Hide decorative icons from screen readers
- Use flex: 0 0 for fixed-size boxes

Elements and CSS used

HTML elements	CSS features
ul, li, span, div, h2, p	display: flex, align-items: flex-start, flex: 0 0 3rem, place-items, grid auto-fit

Build guide

1. Write the list; each li has an icon span and a div with h2 and p.
2. Add aria-hidden="true" to the icon.
3. Make li a flex row.
4. Fix the icon size with flex: 0 0 3rem and centre the glyph.
5. Grid the list into two columns when wide.
6. Check the text wraps under itself, not under the icon.

Project 621: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - Features</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What we offer</h1>
    <ul class="features">
      <li><span class="icon" aria-hidden="true">&#10004;</
span><div><h2>Grilled sea bass</h2><p>With rice and salad.</p></div></
li>
      <li><span class="icon" aria-hidden="true">&#9733;</
span><div><h2>Shrimp tagine</h2><p>Tomato and garlic.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9829;</
span><div><h2>Calamari</h2><p>Fried, with tahini.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9992;</
span><div><h2>Fish soup</h2><p>Daily catch.</p></div></li>
    </ul>
  </main>
</body>
</html>
```

Project 621: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.features { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr)); }
.features li { display: flex; gap: 1rem; align-items: flex-start; }
.icon { flex: 0 0 3rem; height: 3rem; display: grid; place-items:
center; background: var(--brand); color: #fff; border-radius: 12px;
font-size: 1.4rem; }
.features h2 { margin: 0 0 .25rem; font-size: 1.1rem; }
.features p { margin: 0; color: var(--muted); }
```

Project 621 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - Features</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What we offer	The main heading; only one per page.
<ul class="features">	Unordered (bulleted) list.
✔ <h2>G...	Second-level heading for a section.
★ <h2>Sh...	A paragraph of text.
♥ <h2>Ca...	One list item.

Line	What it does
✈ <h2>Fi...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex: 0 0 3rem;	Fixed size: never grows or shrinks.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--brand);	Background colour or image.
border-radius: 12px;	Rounds the corners.
font-size: 1.4rem;	Size of the text.

Check your work

- Icons hidden from assistive tech
- Text does not wrap under the icon
- Two columns on desktop, one on mobile
- Headings are h2

Exercises

1. Replace the glyphs with inline SVG icons.
2. Add a hover effect on the icon box.
3. Make the icon box a circle.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said

Field	Value
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 622: Feature list with icons for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 1 | Files: index.html, styles.css

Brief

Present four features as a two-column list where each item is a media object: an icon box on the left and text on the right.

Learning goals

- Build the media object pattern with Flexbox
- Hide decorative icons from screen readers
- Use flex: 0 0 for fixed-size boxes

Elements and CSS used

HTML elements	CSS features
ul, li, span, div, h2, p	display: flex, align-items: flex-start, flex: 0 0 3rem, place-items, grid auto-fit

Build guide

1. Write the list; each li has an icon span and a div with h2 and p.
2. Add aria-hidden="true" to the icon.
3. Make li a flex row.
4. Fix the icon size with flex: 0 0 3rem and centre the glyph.
5. Grid the list into two columns when wide.
6. Check the text wraps under itself, not under the icon.

Project 622: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - Features</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What we offer</h1>
    <ul class="features">
      <li><span class="icon" aria-hidden="true">&#10004;</
span><div><h2>Story hour</h2><p>Ages 3 to 6, Saturdays.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9733;</
span><div><h2>Reading club</h2><p>Ages 7 to 11.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9829;</
span><div><h2>Homework help</h2><p>Weekday afternoons.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9992;</
span><div><h2>Summer challenge</h2><p>Read ten books.</p></div></li>
    </ul>
  </main>
</body>
</html>
```

Project 622: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.features { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr)); }
.features li { display: flex; gap: 1rem; align-items: flex-start; }
.icon { flex: 0 0 3rem; height: 3rem; display: grid; place-items:
center; background: var(--brand); color: #fff; border-radius: 12px;
font-size: 1.4rem; }
.features h2 { margin: 0 0 .25rem; font-size: 1.1rem; }
.features p { margin: 0; color: var(--muted); }
```

Project 622 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - Features</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What we offer	The main heading; only one per page.
<ul class="features">	Unordered (bulleted) list.
✔ <h2>S...	Second-level heading for a section.
★ <h2>Re...	A paragraph of text.
♥ <h2>Ho...	One list item.

Line	What it does
✈ <h2>Su...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex: 0 0 3rem;	Fixed size: never grows or shrinks.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--brand);	Background colour or image.
border-radius: 12px;	Rounds the corners.
font-size: 1.4rem;	Size of the text.

Check your work

- Icons hidden from assistive tech
- Text does not wrap under the icon
- Two columns on desktop, one on mobile
- Headings are h2

Exercises

1. Replace the glyphs with inline SVG icons.
2. Add a hover effect on the icon box.
3. Make the icon box a circle.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta

Field	Value
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 623: Feature list with icons for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Present four features as a two-column list where each item is a media object: an icon box on the left and text on the right.

Learning goals

- Build the media object pattern with Flexbox
- Hide decorative icons from screen readers
- Use flex: 0 0 for fixed-size boxes

Elements and CSS used

HTML elements	CSS features
ul, li, span, div, h2, p	display: flex, align-items: flex-start, flex: 0 0 3rem, place-items, grid auto-fit

Build guide

1. Write the list; each li has an icon span and a div with h2 and p.
2. Add aria-hidden="true" to the icon.
3. Make li a flex row.
4. Fix the icon size with flex: 0 0 3rem and centre the glyph.
5. Grid the list into two columns when wide.
6. Check the text wraps under itself, not under the icon.

Project 623: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - Features</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What we offer</h1>
    <ul class="features">
      <li><span class="icon" aria-hidden="true">&#10004;</
span><div><h2>Garden room</h2><p>Double bed, shared terrace.</p></
div></li>
      <li><span class="icon" aria-hidden="true">&#9733;</
span><div><h2>Nile view suite</h2><p>Balcony and breakfast.</p></
div></li>
      <li><span class="icon" aria-hidden="true">&#9829;</
span><div><h2>Family room</h2><p>Sleeps four.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9992;</
span><div><h2>Rooftop dorm</h2><p>Budget beds.</p></div></li>
    </ul>
  </main>
</body>
</html>
```

Project 623: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.features { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr)); }
.features li { display: flex; gap: 1rem; align-items: flex-start; }
.icon { flex: 0 0 3rem; height: 3rem; display: grid; place-items:
center; background: var(--brand); color: #fff; border-radius: 12px;
font-size: 1.4rem; }
.features h2 { margin: 0 0 .25rem; font-size: 1.1rem; }
.features p { margin: 0; color: var(--muted); }
```

Project 623 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - Features</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What we offer	The main heading; only one per page.
<ul class="features">	Unordered (bulleted) list.
✔ <h2>G...	Second-level heading for a section.
★ <h2>Ni...	A paragraph of text.
♥ <h2>Fa...	One list item.

Line	What it does
✈ <h2>Ro...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex: 0 0 3rem;	Fixed size: never grows or shrinks.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--brand);	Background colour or image.
border-radius: 12px;	Rounds the corners.
font-size: 1.4rem;	Size of the text.

Check your work

- Icons hidden from assistive tech
- Text does not wrap under the icon
- Two columns on desktop, one on mobile
- Headings are h2

Exercises

1. Replace the glyphs with inline SVG icons.
2. Add a hover effect on the icon box.
3. Make the icon box a circle.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan

Field	Value
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 624: Feature list with icons for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 1 | Files: index.html, styles.css

Brief

Present four features as a two-column list where each item is a media object: an icon box on the left and text on the right.

Learning goals

- Build the media object pattern with Flexbox
- Hide decorative icons from screen readers
- Use flex: 0 0 for fixed-size boxes

Elements and CSS used

HTML elements	CSS features
ul, li, span, div, h2, p	display: flex, align-items: flex-start, flex: 0 0 3rem, place-items, grid auto-fit

Build guide

1. Write the list; each li has an icon span and a div with h2 and p.
2. Add aria-hidden="true" to the icon.
3. Make li a flex row.
4. Fix the icon size with flex: 0 0 3rem and centre the glyph.
5. Grid the list into two columns when wide.
6. Check the text wraps under itself, not under the icon.

Project 624: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - Features</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What we offer</h1>
    <ul class="features">
      <li><span class="icon" aria-hidden="true">&#10004;</
span><div><h2>City bike</h2><p>Seven gears, basket.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9733;</
span><div><h2>Mountain bike</h2><p>Front suspension.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9829;</
span><div><h2>Kids bike</h2><p>20 inch wheels.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9992;</
span><div><h2>Tune-up</h2><p>Brakes, gears and true wheels.</p></
div></li>
    </ul>
  </main>
</body>
</html>
```

Project 624: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.features { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr)); }
.features li { display: flex; gap: 1rem; align-items: flex-start; }
.icon { flex: 0 0 3rem; height: 3rem; display: grid; place-items:
center; background: var(--brand); color: #fff; border-radius: 12px;
font-size: 1.4rem; }
.features h2 { margin: 0 0 .25rem; font-size: 1.1rem; }
.features p { margin: 0; color: var(--muted); }
```

Project 624 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - Features</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What we offer	The main heading; only one per page.
<ul class="features">	Unordered (bulleted) list.
✔ <h2>C...	Second-level heading for a section.
★ <h2>Mo...	A paragraph of text.
♥ <h2>Ki...	One list item.

Line	What it does
✈ <h2>Tu...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex: 0 0 3rem;	Fixed size: never grows or shrinks.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--brand);	Background colour or image.
border-radius: 12px;	Rounds the corners.
font-size: 1.4rem;	Size of the text.

Check your work

- Icons hidden from assistive tech
- Text does not wrap under the icon
- Two columns on desktop, one on mobile
- Headings are h2

Exercises

1. Replace the glyphs with inline SVG icons.
2. Add a hover effect on the icon box.
3. Make the icon box a circle.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia

Field	Value
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 625: Feature list with icons for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 1 | Files: index.html, styles.css

Brief

Present four features as a two-column list where each item is a media object: an icon box on the left and text on the right.

Learning goals

- Build the media object pattern with Flexbox
- Hide decorative icons from screen readers
- Use flex: 0 0 for fixed-size boxes

Elements and CSS used

HTML elements	CSS features
ul, li, span, div, h2, p	display: flex, align-items: flex-start, flex: 0 0 3rem, place-items, grid auto-fit

Build guide

1. Write the list; each li has an icon span and a div with h2 and p.
2. Add aria-hidden="true" to the icon.
3. Make li a flex row.
4. Fix the icon size with flex: 0 0 3rem and centre the glyph.
5. Grid the list into two columns when wide.
6. Check the text wraps under itself, not under the icon.

Project 625: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - Features</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>What we offer</h1>
    <ul class="features">
      <li><span class="icon" aria-hidden="true">&#10004;</
span><div><h2>HTML weekend</h2><p>Build your first page.</p></div></
li>
      <li><span class="icon" aria-hidden="true">&#9733;</
span><div><h2>CSS art</h2><p>Draw with code.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9829;</
span><div><h2>Scratch games</h2><p>Ages 10 to 13.</p></div></li>
      <li><span class="icon" aria-hidden="true">&#9992;</
span><div><h2>Hackathon</h2><p>48 hours, teams of four.</p></div></li>
    </ul>
  </main>
</body>
</html>
```

Project 625: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.features { list-style: none; padding: 0; display: grid; gap: 1.5rem;
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr)); }
.features li { display: flex; gap: 1rem; align-items: flex-start; }
.icon { flex: 0 0 3rem; height: 3rem; display: grid; place-items:
center; background: var(--brand); color: #fff; border-radius: 12px;
font-size: 1.4rem; }
.features h2 { margin: 0 0 .25rem; font-size: 1.1rem; }
.features p { margin: 0; color: var(--muted); }
```

Project 625 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - Features</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
What we offer	The main heading; only one per page.
<ul class="features">	Unordered (bulleted) list.
✔ <h2>H...	Second-level heading for a section.
★ <h2>CS...	A paragraph of text.
♥ <h2>Sc...	One list item.

Line	What it does
✈ <h2>Ha...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.

Declaration	What it does
grid-template-columns: repeat(auto-fit, minmax(20rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex: 0 0 3rem;	Fixed size: never grows or shrinks.
place-items: center;	Centres items horizontally and vertically in a grid.
background: var(--brand);	Background colour or image.
border-radius: 12px;	Rounds the corners.
font-size: 1.4rem;	Size of the text.

Check your work

- Icons hidden from assistive tech
- Text does not wrap under the icon
- Two columns on desktop, one on mobile
- Headings are h2

Exercises

1. Replace the glyphs with inline SVG icons.
2. Add a hover effect on the icon box.
3. Make the icon box a circle.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya

Field	Value
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Find-us page with map

Level 2 | 25 projects, one per theme

Combine an address block, an opening-hours table and an embedded map iframe in a two-column responsive layout.

Project 626: Find-us page with map for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 2 | Files: index.html, styles.css

Brief

Combine an address block, an opening-hours table and an embedded map iframe in a two-column responsive layout.

Learning goals

- Embed a third-party map with iframe and title
- Use address correctly
- Give the iframe a responsive aspect ratio

Elements and CSS used

HTML elements	CSS features
section, h1, address, strong, br, a, h2, table, tr, th, td, iframe	grid-template-columns: 1fr 1.4fr, aspect-ratio, border: 0, align-items: start, @media

Build guide

1. Write the info section with address and hours table.
2. Add the iframe with a descriptive title and loading="lazy".
3. Single column by default.
4. Two columns above 760px.
5. Make the map fill its column with width 100% and aspect-ratio.
6. Remove the iframe border.

Project 626: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Find us</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="find">
    <section class="info">
      <h1>Find Cairo Book Shop</h1>
      <address>
        <strong>Cairo Book Shop</strong><br>
        12 Example Street<br>
        Giza, Egypt<br>
        <a href="tel:+20100000000">+20 100 000 0000</a>
      </address>
      <h2>Opening hours</h2>
      <table>
        <tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:
00</td></tr>
        <tr><th scope="row">Friday</th><td>14:00 - 22:00</td></tr>
      </table>
    </section>
    <iframe class="map" src="https://www.openstreetmap.org/export/
embed.html?bbox=31.20%2C30.02%2C31.24%2C30.06&amp;layer=mapnik"
title="Map showing Cairo Book Shop in Giza" loading="lazy"></iframe>
  </main>
</body>
</html>
```

Project 626: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.find { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; display:
 grid; gap: 2rem; grid-template-columns: 1fr; }
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4fr;
align-items: start; } }
address { font-style: normal; line-height: 1.8; margin-bottom: 1.5rem;
 }
table { border-collapse: collapse; }
th, td { text-align: left; padding: .4rem .8rem .4rem 0; }
```

```
.map { width: 100%; aspect-ratio: 4 / 3; border: 0; border-radius:
12px; }
```

Project 626 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - Find us</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="find">	The unique content of this page; exactly one per page.
<section class="info">	A thematic group of content, normally with its own heading.
Find Cairo Book Shop	The main heading; only one per page.
<address>	Contact information for the page or article.
Cairo Book Shop 	Strong importance (bold by default).
+20 100 000 0000	A hyperlink; href gives the destination.
Opening hours	Second-level heading for a section.
<table>	Tabular data in rows and columns.

Line	What it does
<tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:00</td><...	A table row.
<tr><th scope="row">Friday </th><td>14:00 - 22:00</td></tr>	Header cell for a row.
<iframe class="map" src="https://www.openstreetmap.org/export/embed...	Embeds another page; title describes it for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: 1fr;	Defines the columns of the grid.
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4f...	Aligns items to the start of the cross axis (no stretching).
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
width: 100%;	Fills the container width.
aspect-ratio: 4 / 3;	Keeps a fixed width-to-height ratio, reserving space before media loads.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.

Check your work

- iframe has a title
- Address uses <address> without italic
- Map keeps its shape on resize
- Phone link works on mobile

Exercises

1. Add a 'Get directions' link to a maps URL.
2. Add a contact form under the address.
3. Use <details> for a public transport section.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 627: Find-us page with map for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 2 | Files: index.html, styles.css

Brief

Combine an address block, an opening-hours table and an embedded map iframe in a two-column responsive layout.

Learning goals

- Embed a third-party map with iframe and title
- Use address correctly
- Give the iframe a responsive aspect ratio

Elements and CSS used

HTML elements	CSS features
section, h1, address, strong, br, a, h2, table, tr, th, td, iframe	grid-template-columns: 1fr 1.4fr, aspect-ratio, border: 0, align-items: start, @media

Build guide

1. Write the info section with address and hours table.
2. Add the iframe with a descriptive title and loading="lazy".
3. Single column by default.
4. Two columns above 760px.
5. Make the map fill its column with width 100% and aspect-ratio.
6. Remove the iframe border.

Project 627: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - Find us</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="find">
    <section class="info">
      <h1>Find Nile Bakery</h1>
      <address>
        <strong>Nile Bakery</strong><br>
        12 Example Street<br>
        Cairo, Egypt<br>
        <a href="tel:+20100000000">+20 100 000 0000</a>
      </address>
      <h2>Opening hours</h2>
      <table>
        <tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:
00</td></tr>
        <tr><th scope="row">Friday</th><td>14:00 - 22:00</td></tr>
      </table>
    </section>
    <iframe class="map" src="https://www.openstreetmap.org/export/
embed.html?bbox=31.20%2C30.02%2C31.24%2C30.06&amp;layer=mapnik"
title="Map showing Nile Bakery in Cairo" loading="lazy"></iframe>
  </main>
</body>
</html>
```

Project 627: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.find { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; display:
 grid; gap: 2rem; grid-template-columns: 1fr; }
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4fr;
align-items: start; } }
address { font-style: normal; line-height: 1.8; margin-bottom: 1.5rem;
 }
table { border-collapse: collapse; }
th, td { text-align: left; padding: .4rem .8rem .4rem 0; }
```

```
.map { width: 100%; aspect-ratio: 4 / 3; border: 0; border-radius:
12px; }
```

Project 627 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - Find us</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="find">	The unique content of this page; exactly one per page.
<section class="info">	A thematic group of content, normally with its own heading.
Find Nile Bakery	The main heading; only one per page.
<address>	Contact information for the page or article.
Nile Bakery 	Strong importance (bold by default).
+20 100 000 0000	A hyperlink; href gives the destination.
Opening hours	Second-level heading for a section.
<table>	Tabular data in rows and columns.

Line	What it does
<tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:00</td><...	A table row.
<tr><th scope="row">Friday </th><td>14:00 - 22:00</td></tr>	Header cell for a row.
<iframe class="map" src="https://www.openstreetmap.org/export/embed...	Embeds another page; title describes it for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: 1fr;	Defines the columns of the grid.
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4f...	Aligns items to the start of the cross axis (no stretching).
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
width: 100%;	Fills the container width.
aspect-ratio: 4 / 3;	Keeps a fixed width-to-height ratio, reserving space before media loads.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.

Check your work

- iframe has a title
- Address uses <address> without italic
- Map keeps its shape on resize
- Phone link works on mobile

Exercises

1. Add a 'Get directions' link to a maps URL.
2. Add a contact form under the address.
3. Use <details> for a public transport section.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 628: Find-us page with map for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 2 | Files: index.html, styles.css

Brief

Combine an address block, an opening-hours table and an embedded map iframe in a two-column responsive layout.

Learning goals

- Embed a third-party map with iframe and title
- Use address correctly
- Give the iframe a responsive aspect ratio

Elements and CSS used

HTML elements	CSS features
section, h1, address, strong, br, a, h2, table, tr, th, td, iframe	grid-template-columns: 1fr 1.4fr, aspect-ratio, border: 0, align-items: start, @media

Build guide

1. Write the info section with address and hours table.
2. Add the iframe with a descriptive title and loading="lazy".
3. Single column by default.
4. Two columns above 760px.
5. Make the map fill its column with width 100% and aspect-ratio.
6. Remove the iframe border.

Project 628: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - Find us</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="find">
    <section class="info">
      <h1>Find Pyramid Fitness</h1>
      <address>
        <strong>Pyramid Fitness</strong><br>
        12 Example Street<br>
        6th of October, Egypt<br>
        <a href="tel:+20100000000">+20 100 000 0000</a>
      </address>
      <h2>Opening hours</h2>
      <table>
        <tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:
00</td></tr>
        <tr><th scope="row">Friday</th><td>14:00 - 22:00</td></tr>
      </table>
    </section>
    <iframe class="map" src="https://www.openstreetmap.org/export/
embed.html?bbox=31.20%2C30.02%2C31.24%2C30.06&amp;layer=mapnik"
title="Map showing Pyramid Fitness in 6th of October"
loading="lazy"></iframe>
  </main>
</body>
</html>
```

Project 628: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.find { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; display:
 grid; gap: 2rem; grid-template-columns: 1fr; }
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4fr;
align-items: start; } }
address { font-style: normal; line-height: 1.8; margin-bottom: 1.5rem;
 }
table { border-collapse: collapse; }
```

```
th, td { text-align: left; padding: .4rem .8rem .4rem 0; }
.map { width: 100%; aspect-ratio: 4 / 3; border: 0; border-radius:
12px; }
```

Project 628 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - Find us</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="find">	The unique content of this page; exactly one per page.
<section class="info">	A thematic group of content, normally with its own heading.
Find Pyramid Fitness	The main heading; only one per page.
<address>	Contact information for the page or article.
Pyramid Fitness 	Strong importance (bold by default).
+20 100 000 0000	A hyperlink; href gives the destination.
Opening hours	Second-level heading for a section.
<table>	Tabular data in rows and columns.

Line	What it does
<tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:00</td><...	A table row.
<tr><th scope="row">Friday </th><td>14:00 - 22:00</td></tr>	Header cell for a row.
<iframe class="map" src="https://www.openstreetmap.org/export/embed...	Embeds another page; title describes it for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: 1fr;	Defines the columns of the grid.
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4f...	Aligns items to the start of the cross axis (no stretching).
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
width: 100%;	Fills the container width.
aspect-ratio: 4 / 3;	Keeps a fixed width-to-height ratio, reserving space before media loads.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.

Check your work

- iframe has a title
- Address uses <address> without italic
- Map keeps its shape on resize
- Phone link works on mobile

Exercises

1. Add a 'Get directions' link to a maps URL.
2. Add a contact form under the address.
3. Use <details> for a public transport section.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 629: Find-us page with map for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 2 | Files: index.html, styles.css

Brief

Combine an address block, an opening-hours table and an embedded map iframe in a two-column responsive layout.

Learning goals

- Embed a third-party map with iframe and title
- Use address correctly
- Give the iframe a responsive aspect ratio

Elements and CSS used

HTML elements	CSS features
section, h1, address, strong, br, a, h2, table, tr, th, td, iframe	grid-template-columns: 1fr 1.4fr, aspect-ratio, border: 0, align-items: start, @media

Build guide

1. Write the info section with address and hours table.
2. Add the iframe with a descriptive title and loading="lazy".
3. Single column by default.
4. Two columns above 760px.
5. Make the map fill its column with width 100% and aspect-ratio.
6. Remove the iframe border.

Project 629: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - Find us</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="find">
    <section class="info">
      <h1>Find Delta Dental Clinic</h1>
      <address>
        <strong>Delta Dental Clinic</strong><br>
        12 Example Street<br>
        Mansoura, Egypt<br>
        <a href="tel:+20100000000">+20 100 000 0000</a>
      </address>
      <h2>Opening hours</h2>
      <table>
        <tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:
00</td></tr>
        <tr><th scope="row">Friday</th><td>14:00 - 22:00</td></tr>
      </table>
    </section>
    <iframe class="map" src="https://www.openstreetmap.org/export/
embed.html?bbox=31.20%2C30.02%2C31.24%2C30.06&amp;layer=mapnik"
title="Map showing Delta Dental Clinic in Mansoura" loading="lazy"></
iframe>
  </main>
</body>
</html>
```

Project 629: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.find { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; display:
 grid; gap: 2rem; grid-template-columns: 1fr; }
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4fr;
align-items: start; } }
address { font-style: normal; line-height: 1.8; margin-bottom: 1.5rem;
 }
table { border-collapse: collapse; }
```

```
th, td { text-align: left; padding: .4rem .8rem .4rem 0; }
.map { width: 100%; aspect-ratio: 4 / 3; border: 0; border-radius:
12px; }
```

Project 629 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - Find us</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="find">	The unique content of this page; exactly one per page.
<section class="info">	A thematic group of content, normally with its own heading.
Find Delta Dental Clinic	The main heading; only one per page.
<address>	Contact information for the page or article.
Delta Dental Clinic 	Strong importance (bold by default).
+20 100 000 0000	A hyperlink; href gives the destination.
Opening hours	Second-level heading for a section.
<table>	Tabular data in rows and columns.

Line	What it does
<tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:00</td><...	A table row.
<tr><th scope="row">Friday </th><td>14:00 - 22:00</td></tr>	Header cell for a row.
<iframe class="map" src="https://www.openstreetmap.org/export/embed...	Embeds another page; title describes it for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: 1fr;	Defines the columns of the grid.
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4f...	Aligns items to the start of the cross axis (no stretching).
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
width: 100%;	Fills the container width.
aspect-ratio: 4 / 3;	Keeps a fixed width-to-height ratio, reserving space before media loads.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.

Check your work

- iframe has a title
- Address uses <address> without italic
- Map keeps its shape on resize
- Phone link works on mobile

Exercises

1. Add a 'Get directions' link to a maps URL.
2. Add a contact form under the address.
3. Use <details> for a public transport section.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 630: Find-us page with map for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 2 | Files: index.html, styles.css

Brief

Combine an address block, an opening-hours table and an embedded map iframe in a two-column responsive layout.

Learning goals

- Embed a third-party map with iframe and title
- Use address correctly
- Give the iframe a responsive aspect ratio

Elements and CSS used

HTML elements	CSS features
section, h1, address, strong, br, a, h2, table, tr, th, td, iframe	grid-template-columns: 1fr 1.4fr, aspect-ratio, border: 0, align-items: start, @media

Build guide

1. Write the info section with address and hours table.
2. Add the iframe with a descriptive title and loading="lazy".
3. Single column by default.
4. Two columns above 760px.
5. Make the map fill its column with width 100% and aspect-ratio.
6. Remove the iframe border.

Project 630: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - Find us</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="find">
    <section class="info">
      <h1>Find Red Sea Travel</h1>
      <address>
        <strong>Red Sea Travel</strong><br>
        12 Example Street<br>
        Hurghada, Egypt<br>
        <a href="tel:+20100000000">+20 100 000 0000</a>
      </address>
      <h2>Opening hours</h2>
      <table>
        <tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:
00</td></tr>
        <tr><th scope="row">Friday</th><td>14:00 - 22:00</td></tr>
      </table>
    </section>
    <iframe class="map" src="https://www.openstreetmap.org/export/
embed.html?bbox=31.20%2C30.02%2C31.24%2C30.06&amp;layer=mapnik"
title="Map showing Red Sea Travel in Hurghada" loading="lazy"></
iframe>
  </main>
</body>
</html>
```

Project 630: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.find { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; display:
 grid; gap: 2rem; grid-template-columns: 1fr; }
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4fr;
align-items: start; } }
address { font-style: normal; line-height: 1.8; margin-bottom: 1.5rem;
 }
table { border-collapse: collapse; }
```

```
th, td { text-align: left; padding: .4rem .8rem .4rem 0; }
.map { width: 100%; aspect-ratio: 4 / 3; border: 0; border-radius:
12px; }
```

Project 630 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - Find us</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="find">	The unique content of this page; exactly one per page.
<section class="info">	A thematic group of content, normally with its own heading.
Find Red Sea Travel	The main heading; only one per page.
<address>	Contact information for the page or article.
Red Sea Travel 	Strong importance (bold by default).
+20 100 000 0000	A hyperlink; href gives the destination.
Opening hours	Second-level heading for a section.
<table>	Tabular data in rows and columns.

Line	What it does
<tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:00</td><...	A table row.
<tr><th scope="row">Friday </th><td>14:00 - 22:00</td></tr>	Header cell for a row.
<iframe class="map" src="https://www.openstreetmap.org/export/embed...	Embeds another page; title describes it for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: 1fr;	Defines the columns of the grid.
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4f...	Aligns items to the start of the cross axis (no stretching).
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
width: 100%;	Fills the container width.
aspect-ratio: 4 / 3;	Keeps a fixed width-to-height ratio, reserving space before media loads.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.

Check your work

- iframe has a title
- Address uses <address> without italic
- Map keeps its shape on resize
- Phone link works on mobile

Exercises

1. Add a 'Get directions' link to a maps URL.
2. Add a contact form under the address.
3. Use <details> for a public transport section.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 631: Find-us page with map for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Combine an address block, an opening-hours table and an embedded map iframe in a two-column responsive layout.

Learning goals

- Embed a third-party map with iframe and title
- Use address correctly
- Give the iframe a responsive aspect ratio

Elements and CSS used

HTML elements	CSS features
section, h1, address, strong, br, a, h2, table, tr, th, td, iframe	grid-template-columns: 1fr 1.4fr, aspect-ratio, border: 0, align-items: start, @media

Build guide

1. Write the info section with address and hours table.
2. Add the iframe with a descriptive title and loading="lazy".
3. Single column by default.
4. Two columns above 760px.
5. Make the map fill its column with width 100% and aspect-ratio.
6. Remove the iframe border.

Project 631: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - Find us</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="find">
    <section class="info">
      <h1>Find Lotus Language School</h1>
      <address>
        <strong>Lotus Language School</strong><br>
        12 Example Street<br>
        Alexandria, Egypt<br>
        <a href="tel:+20100000000">+20 100 000 0000</a>
      </address>
      <h2>Opening hours</h2>
      <table>
        <tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:
00</td></tr>
        <tr><th scope="row">Friday</th><td>14:00 - 22:00</td></tr>
      </table>
    </section>
    <iframe class="map" src="https://www.openstreetmap.org/export/
embed.html?bbox=31.20%2C30.02%2C31.24%2C30.06&amp;layer=mapnik"
title="Map showing Lotus Language School in Alexandria"
loading="lazy"></iframe>
  </main>
</body>
</html>
```

Project 631: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.find { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; display:
 grid; gap: 2rem; grid-template-columns: 1fr; }
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4fr;
align-items: start; } }
address { font-style: normal; line-height: 1.8; margin-bottom: 1.5rem;
 }
table { border-collapse: collapse; }
```

```
th, td { text-align: left; padding: .4rem .8rem .4rem 0; }
.map { width: 100%; aspect-ratio: 4 / 3; border: 0; border-radius:
12px; }
```

Project 631 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - Find us</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="find">	The unique content of this page; exactly one per page.
<section class="info">	A thematic group of content, normally with its own heading.
Find Lotus Language School	The main heading; only one per page.
<address>	Contact information for the page or article.
Lotus Language School 	Strong importance (bold by default).
+20 100 000 0000	A hyperlink; href gives the destination.
Opening hours	Second-level heading for a section.
<table>	Tabular data in rows and columns.

Line	What it does
<tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:00</td><...	A table row.
<tr><th scope="row">Friday </th><td>14:00 - 22:00</td></tr>	Header cell for a row.
<iframe class="map" src="https://www.openstreetmap.org/export/embed...	Embeds another page; title describes it for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: 1fr;	Defines the columns of the grid.
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4f...	Aligns items to the start of the cross axis (no stretching).
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
width: 100%;	Fills the container width.
aspect-ratio: 4 / 3;	Keeps a fixed width-to-height ratio, reserving space before media loads.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.

Check your work

- iframe has a title
- Address uses <address> without italic
- Map keeps its shape on resize
- Phone link works on mobile

Exercises

1. Add a 'Get directions' link to a maps URL.
2. Add a contact form under the address.
3. Use <details> for a public transport section.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 632: Find-us page with map for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 2 | Files: index.html, styles.css

Brief

Combine an address block, an opening-hours table and an embedded map iframe in a two-column responsive layout.

Learning goals

- Embed a third-party map with iframe and title
- Use address correctly
- Give the iframe a responsive aspect ratio

Elements and CSS used

HTML elements	CSS features
section, h1, address, strong, br, a, h2, table, tr, th, td, iframe	grid-template-columns: 1fr 1.4fr, aspect-ratio, border: 0, align-items: start, @media

Build guide

1. Write the info section with address and hours table.
2. Add the iframe with a descriptive title and loading="lazy".
3. Single column by default.
4. Two columns above 760px.
5. Make the map fill its column with width 100% and aspect-ratio.
6. Remove the iframe border.

Project 632: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - Find us</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="find">
    <section class="info">
      <h1>Find Green Leaf Cafe</h1>
      <address>
        <strong>Green Leaf Cafe</strong><br>
        12 Example Street<br>
        Zamalek, Egypt<br>
        <a href="tel:+20100000000">+20 100 000 0000</a>
      </address>
      <h2>Opening hours</h2>
      <table>
        <tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:
00</td></tr>
        <tr><th scope="row">Friday</th><td>14:00 - 22:00</td></tr>
      </table>
    </section>
    <iframe class="map" src="https://www.openstreetmap.org/export/
embed.html?bbox=31.20%2C30.02%2C31.24%2C30.06&amp;layer=mapnik"
title="Map showing Green Leaf Cafe in Zamalek" loading="lazy"></
iframe>
  </main>
</body>
</html>
```

Project 632: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.find { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; display:
 grid; gap: 2rem; grid-template-columns: 1fr; }
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4fr;
align-items: start; } }
address { font-style: normal; line-height: 1.8; margin-bottom: 1.5rem;
 }
table { border-collapse: collapse; }
```

```
th, td { text-align: left; padding: .4rem .8rem .4rem 0; }
.map { width: 100%; aspect-ratio: 4 / 3; border: 0; border-radius:
12px; }
```

Project 632 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - Find us</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="find">	The unique content of this page; exactly one per page.
<section class="info">	A thematic group of content, normally with its own heading.
Find Green Leaf Cafe	The main heading; only one per page.
<address>	Contact information for the page or article.
Green Leaf Cafe 	Strong importance (bold by default).
+20 100 000 0000	A hyperlink; href gives the destination.
Opening hours	Second-level heading for a section.
<table>	Tabular data in rows and columns.

Line	What it does
<tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:00</td><...	A table row.
<tr><th scope="row">Friday </th><td>14:00 - 22:00</td></tr>	Header cell for a row.
<iframe class="map" src="https://www.openstreetmap.org/export/embed...	Embeds another page; title describes it for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: 1fr;	Defines the columns of the grid.
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4f...	Aligns items to the start of the cross axis (no stretching).
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
width: 100%;	Fills the container width.
aspect-ratio: 4 / 3;	Keeps a fixed width-to-height ratio, reserving space before media loads.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.

Check your work

- iframe has a title
- Address uses <address> without italic
- Map keeps its shape on resize
- Phone link works on mobile

Exercises

1. Add a 'Get directions' link to a maps URL.
2. Add a contact form under the address.
3. Use <details> for a public transport section.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 633: Find-us page with map for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 2 | Files: index.html, styles.css

Brief

Combine an address block, an opening-hours table and an embedded map iframe in a two-column responsive layout.

Learning goals

- Embed a third-party map with iframe and title
- Use address correctly
- Give the iframe a responsive aspect ratio

Elements and CSS used

HTML elements	CSS features
section, h1, address, strong, br, a, h2, table, tr, th, td, iframe	grid-template-columns: 1fr 1.4fr, aspect-ratio, border: 0, align-items: start, @media

Build guide

1. Write the info section with address and hours table.
2. Add the iframe with a descriptive title and loading="lazy".
3. Single column by default.
4. Two columns above 760px.
5. Make the map fill its column with width 100% and aspect-ratio.
6. Remove the iframe border.

Project 633: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - Find us</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="find">
    <section class="info">
      <h1>Find Sinai Trekking Club</h1>
      <address>
        <strong>Sinai Trekking Club</strong><br>
        12 Example Street<br>
        Saint Catherine, Egypt<br>
        <a href="tel:+20100000000">+20 100 000 0000</a>
      </address>
      <h2>Opening hours</h2>
      <table>
        <tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:
00</td></tr>
        <tr><th scope="row">Friday</th><td>14:00 - 22:00</td></tr>
      </table>
    </section>
    <iframe class="map" src="https://www.openstreetmap.org/export/
embed.html?bbox=31.20%2C30.02%2C31.24%2C30.06&amp;layer=mapnik"
title="Map showing Sinai Trekking Club in Saint Catherine"
loading="lazy"></iframe>
  </main>
</body>
</html>
```

Project 633: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.find { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; display:
 grid; gap: 2rem; grid-template-columns: 1fr; }
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4fr;
align-items: start; } }
address { font-style: normal; line-height: 1.8; margin-bottom: 1.5rem;
 }
table { border-collapse: collapse; }
```

```
th, td { text-align: left; padding: .4rem .8rem .4rem 0; }
.map { width: 100%; aspect-ratio: 4 / 3; border: 0; border-radius:
12px; }
```

Project 633 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - Find us</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="find">	The unique content of this page; exactly one per page.
<section class="info">	A thematic group of content, normally with its own heading.
Find Sinai Trekking Club	The main heading; only one per page.
<address>	Contact information for the page or article.
Sinai Trekking Club 	Strong importance (bold by default).
+20 100 000 0000	A hyperlink; href gives the destination.
Opening hours	Second-level heading for a section.
<table>	Tabular data in rows and columns.

Line	What it does
<tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:00</td><...	A table row.
<tr><th scope="row">Friday </th><td>14:00 - 22:00</td></tr>	Header cell for a row.
<iframe class="map" src="https://www.openstreetmap.org/export/embed...	Embeds another page; title describes it for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: 1fr;	Defines the columns of the grid.
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4f...	Aligns items to the start of the cross axis (no stretching).
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
width: 100%;	Fills the container width.
aspect-ratio: 4 / 3;	Keeps a fixed width-to-height ratio, reserving space before media loads.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.

Check your work

- iframe has a title
- Address uses <address> without italic
- Map keeps its shape on resize
- Phone link works on mobile

Exercises

1. Add a 'Get directions' link to a maps URL.
2. Add a contact form under the address.
3. Use <details> for a public transport section.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 634: Find-us page with map for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 2 | Files: index.html, styles.css

Brief

Combine an address block, an opening-hours table and an embedded map iframe in a two-column responsive layout.

Learning goals

- Embed a third-party map with iframe and title
- Use address correctly
- Give the iframe a responsive aspect ratio

Elements and CSS used

HTML elements	CSS features
section, h1, address, strong, br, a, h2, table, tr, th, td, iframe	grid-template-columns: 1fr 1.4fr, aspect-ratio, border: 0, align-items: start, @media

Build guide

1. Write the info section with address and hours table.
2. Add the iframe with a descriptive title and loading="lazy".
3. Single column by default.
4. Two columns above 760px.
5. Make the map fill its column with width 100% and aspect-ratio.
6. Remove the iframe border.

Project 634: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - Find us</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="find">
    <section class="info">
      <h1>Find Horizon Photography</h1>
      <address>
        <strong>Horizon Photography</strong><br>
        12 Example Street<br>
        Maadi, Egypt<br>
        <a href="tel:+20100000000">+20 100 000 0000</a>
      </address>
      <h2>Opening hours</h2>
      <table>
        <tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:
00</td></tr>
        <tr><th scope="row">Friday</th><td>14:00 - 22:00</td></tr>
      </table>
    </section>
    <iframe class="map" src="https://www.openstreetmap.org/export/
embed.html?bbox=31.20%2C30.02%2C31.24%2C30.06&amp;layer=mapnik"
title="Map showing Horizon Photography in Maadi" loading="lazy"></
iframe>
  </main>
</body>
</html>
```

Project 634: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.find { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; display:
 grid; gap: 2rem; grid-template-columns: 1fr; }
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4fr;
align-items: start; } }
address { font-style: normal; line-height: 1.8; margin-bottom: 1.5rem;
 }
table { border-collapse: collapse; }
```

```
th, td { text-align: left; padding: .4rem .8rem .4rem 0; }
.map { width: 100%; aspect-ratio: 4 / 3; border: 0; border-radius:
12px; }
```

Project 634 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - Find us</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="find">	The unique content of this page; exactly one per page.
<section class="info">	A thematic group of content, normally with its own heading.
Find Horizon Photography	The main heading; only one per page.
<address>	Contact information for the page or article.
Horizon Photography 	Strong importance (bold by default).
+20 100 000 0000	A hyperlink; href gives the destination.
Opening hours	Second-level heading for a section.
<table>	Tabular data in rows and columns.

Line	What it does
<tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:00</td><...	A table row.
<tr><th scope="row">Friday </th><td>14:00 - 22:00</td></tr>	Header cell for a row.
<iframe class="map" src="https://www.openstreetmap.org/export/embed...	Embeds another page; title describes it for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: 1fr;	Defines the columns of the grid.
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4f...	Aligns items to the start of the cross axis (no stretching).
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
width: 100%;	Fills the container width.
aspect-ratio: 4 / 3;	Keeps a fixed width-to-height ratio, reserving space before media loads.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.

Check your work

- iframe has a title
- Address uses <address> without italic
- Map keeps its shape on resize
- Phone link works on mobile

Exercises

1. Add a 'Get directions' link to a maps URL.
2. Add a contact form under the address.
3. Use <details> for a public transport section.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 635: Find-us page with map for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 2 | Files: index.html, styles.css

Brief

Combine an address block, an opening-hours table and an embedded map iframe in a two-column responsive layout.

Learning goals

- Embed a third-party map with iframe and title
- Use address correctly
- Give the iframe a responsive aspect ratio

Elements and CSS used

HTML elements	CSS features
section, h1, address, strong, br, a, h2, table, tr, th, td, iframe	grid-template-columns: 1fr 1.4fr, aspect-ratio, border: 0, align-items: start, @media

Build guide

1. Write the info section with address and hours table.
2. Add the iframe with a descriptive title and loading="lazy".
3. Single column by default.
4. Two columns above 760px.
5. Make the map fill its column with width 100% and aspect-ratio.
6. Remove the iframe border.

Project 635: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - Find us</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="find">
    <section class="info">
      <h1>Find Papyrus Stationery</h1>
      <address>
        <strong>Papyrus Stationery</strong><br>
        12 Example Street<br>
        Heliopolis, Egypt<br>
        <a href="tel:+20100000000">+20 100 000 0000</a>
      </address>
      <h2>Opening hours</h2>
      <table>
        <tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:
00</td></tr>
        <tr><th scope="row">Friday</th><td>14:00 - 22:00</td></tr>
      </table>
    </section>
    <iframe class="map" src="https://www.openstreetmap.org/export/
embed.html?bbox=31.20%2C30.02%2C31.24%2C30.06&amp;layer=mapnik"
title="Map showing Papyrus Stationery in Heliopolis" loading="lazy"></
iframe>
  </main>
</body>
</html>
```

Project 635: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.find { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; display:
 grid; gap: 2rem; grid-template-columns: 1fr; }
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4fr;
align-items: start; } }
address { font-style: normal; line-height: 1.8; margin-bottom: 1.5rem;
 }
table { border-collapse: collapse; }
```

```
th, td { text-align: left; padding: .4rem .8rem .4rem 0; }
.map { width: 100%; aspect-ratio: 4 / 3; border: 0; border-radius:
12px; }
```

Project 635 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - Find us</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="find">	The unique content of this page; exactly one per page.
<section class="info">	A thematic group of content, normally with its own heading.
Find Papyrus Stationery	The main heading; only one per page.
<address>	Contact information for the page or article.
Papyrus Stationery 	Strong importance (bold by default).
+20 100 000 0000	A hyperlink; href gives the destination.
Opening hours	Second-level heading for a section.
<table>	Tabular data in rows and columns.

Line	What it does
<tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:00</td><...	A table row.
<tr><th scope="row">Friday </th><td>14:00 - 22:00</td></tr>	Header cell for a row.
<iframe class="map" src="https://www.openstreetmap.org/export/embed...	Embeds another page; title describes it for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: 1fr;	Defines the columns of the grid.
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4f...	Aligns items to the start of the cross axis (no stretching).
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
width: 100%;	Fills the container width.
aspect-ratio: 4 / 3;	Keeps a fixed width-to-height ratio, reserving space before media loads.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.

Check your work

- iframe has a title
- Address uses <address> without italic
- Map keeps its shape on resize
- Phone link works on mobile

Exercises

1. Add a 'Get directions' link to a maps URL.
2. Add a contact form under the address.
3. Use <details> for a public transport section.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 636: Find-us page with map for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 2 | Files: index.html, styles.css

Brief

Combine an address block, an opening-hours table and an embedded map iframe in a two-column responsive layout.

Learning goals

- Embed a third-party map with iframe and title
- Use address correctly
- Give the iframe a responsive aspect ratio

Elements and CSS used

HTML elements	CSS features
section, h1, address, strong, br, a, h2, table, tr, th, td, iframe	grid-template-columns: 1fr 1.4fr, aspect-ratio, border: 0, align-items: start, @media

Build guide

1. Write the info section with address and hours table.
2. Add the iframe with a descriptive title and loading="lazy".
3. Single column by default.
4. Two columns above 760px.
5. Make the map fill its column with width 100% and aspect-ratio.
6. Remove the iframe border.

Project 636: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - Find us</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="find">
    <section class="info">
      <h1>Find Oasis Plant Nursery</h1>
      <address>
        <strong>Oasis Plant Nursery</strong><br>
        12 Example Street<br>
        Sheikh Zayed, Egypt<br>
        <a href="tel:+20100000000">+20 100 000 0000</a>
      </address>
      <h2>Opening hours</h2>
      <table>
        <tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:
00</td></tr>
        <tr><th scope="row">Friday</th><td>14:00 - 22:00</td></tr>
      </table>
    </section>
    <iframe class="map" src="https://www.openstreetmap.org/export/
embed.html?bbox=31.20%2C30.02%2C31.24%2C30.06&amp;layer=mapnik"
title="Map showing Oasis Plant Nursery in Sheikh Zayed"
loading="lazy"></iframe>
  </main>
</body>
</html>
```

Project 636: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.find { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; display:
 grid; gap: 2rem; grid-template-columns: 1fr; }
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4fr;
align-items: start; } }
address { font-style: normal; line-height: 1.8; margin-bottom: 1.5rem;
 }
table { border-collapse: collapse; }
```

```
th, td { text-align: left; padding: .4rem .8rem .4rem 0; }
.map { width: 100%; aspect-ratio: 4 / 3; border: 0; border-radius:
12px; }
```

Project 636 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - Find us</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="find">	The unique content of this page; exactly one per page.
<section class="info">	A thematic group of content, normally with its own heading.
Find Oasis Plant Nursery	The main heading; only one per page.
<address>	Contact information for the page or article.
Oasis Plant Nursery 	Strong importance (bold by default).
+20 100 000 0000	A hyperlink; href gives the destination.
Opening hours	Second-level heading for a section.
<table>	Tabular data in rows and columns.

Line	What it does
<tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:00</td><...	A table row.
<tr><th scope="row">Friday </th><td>14:00 - 22:00</td></tr>	Header cell for a row.
<iframe class="map" src="https://www.openstreetmap.org/export/embed...	Embeds another page; title describes it for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: 1fr;	Defines the columns of the grid.
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4f...	Aligns items to the start of the cross axis (no stretching).
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
width: 100%;	Fills the container width.
aspect-ratio: 4 / 3;	Keeps a fixed width-to-height ratio, reserving space before media loads.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.

Check your work

- iframe has a title
- Address uses <address> without italic
- Map keeps its shape on resize
- Phone link works on mobile

Exercises

1. Add a 'Get directions' link to a maps URL.
2. Add a contact form under the address.
3. Use <details> for a public transport section.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 637: Find-us page with map for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 2 | Files: index.html, styles.css

Brief

Combine an address block, an opening-hours table and an embedded map iframe in a two-column responsive layout.

Learning goals

- Embed a third-party map with iframe and title
- Use address correctly
- Give the iframe a responsive aspect ratio

Elements and CSS used

HTML elements	CSS features
section, h1, address, strong, br, a, h2, table, tr, th, td, iframe	grid-template-columns: 1fr 1.4fr, aspect-ratio, border: 0, align-items: start, @media

Build guide

1. Write the info section with address and hours table.
2. Add the iframe with a descriptive title and loading="lazy".
3. Single column by default.
4. Two columns above 760px.
5. Make the map fill its column with width 100% and aspect-ratio.
6. Remove the iframe border.

Project 637: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - Find us</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="find">
    <section class="info">
      <h1>Find Cedar Furniture</h1>
      <address>
        <strong>Cedar Furniture</strong><br>
        12 Example Street<br>
        Damietta, Egypt<br>
        <a href="tel:+20100000000">+20 100 000 0000</a>
      </address>
      <h2>Opening hours</h2>
      <table>
        <tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:
00</td></tr>
        <tr><th scope="row">Friday</th><td>14:00 - 22:00</td></tr>
      </table>
    </section>
    <iframe class="map" src="https://www.openstreetmap.org/export/
embed.html?bbox=31.20%2C30.02%2C31.24%2C30.06&amp;layer=mapnik"
title="Map showing Cedar Furniture in Damietta" loading="lazy"></
iframe>
  </main>
</body>
</html>
```

Project 637: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.find { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; display:
 grid; gap: 2rem; grid-template-columns: 1fr; }
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4fr;
align-items: start; } }
address { font-style: normal; line-height: 1.8; margin-bottom: 1.5rem;
 }
table { border-collapse: collapse; }
```

```
th, td { text-align: left; padding: .4rem .8rem .4rem 0; }
.map { width: 100%; aspect-ratio: 4 / 3; border: 0; border-radius:
12px; }
```

Project 637 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - Find us</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="find">	The unique content of this page; exactly one per page.
<section class="info">	A thematic group of content, normally with its own heading.
Find Cedar Furniture	The main heading; only one per page.
<address>	Contact information for the page or article.
Cedar Furniture 	Strong importance (bold by default).
+20 100 000 0000	A hyperlink; href gives the destination.
Opening hours	Second-level heading for a section.
<table>	Tabular data in rows and columns.

Line	What it does
<tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:00</td><...	A table row.
<tr><th scope="row">Friday </th><td>14:00 - 22:00</td></tr>	Header cell for a row.
<iframe class="map" src="https://www.openstreetmap.org/export/embed...	Embeds another page; title describes it for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: 1fr;	Defines the columns of the grid.
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4f...	Aligns items to the start of the cross axis (no stretching).
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
width: 100%;	Fills the container width.
aspect-ratio: 4 / 3;	Keeps a fixed width-to-height ratio, reserving space before media loads.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.

Check your work

- iframe has a title
- Address uses <address> without italic
- Map keeps its shape on resize
- Phone link works on mobile

Exercises

1. Add a 'Get directions' link to a maps URL.
2. Add a contact form under the address.
3. Use <details> for a public transport section.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 638: Find-us page with map for Byte Repair

Theme: Byte Repair (Nasr City) | Level 2 | Files: index.html, styles.css

Brief

Combine an address block, an opening-hours table and an embedded map iframe in a two-column responsive layout.

Learning goals

- Embed a third-party map with iframe and title
- Use address correctly
- Give the iframe a responsive aspect ratio

Elements and CSS used

HTML elements	CSS features
section, h1, address, strong, br, a, h2, table, tr, th, td, iframe	grid-template-columns: 1fr 1.4fr, aspect-ratio, border: 0, align-items: start, @media

Build guide

1. Write the info section with address and hours table.
2. Add the iframe with a descriptive title and loading="lazy".
3. Single column by default.
4. Two columns above 760px.
5. Make the map fill its column with width 100% and aspect-ratio.
6. Remove the iframe border.

Project 638: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - Find us</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="find">
    <section class="info">
      <h1>Find Byte Repair</h1>
      <address>
        <strong>Byte Repair</strong><br>
        12 Example Street<br>
        Nasr City, Egypt<br>
        <a href="tel:+20100000000">+20 100 000 0000</a>
      </address>
      <h2>Opening hours</h2>
      <table>
        <tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:
00</td></tr>
        <tr><th scope="row">Friday</th><td>14:00 - 22:00</td></tr>
      </table>
    </section>
    <iframe class="map" src="https://www.openstreetmap.org/export/
embed.html?bbox=31.20%2C30.02%2C31.24%2C30.06&amp;layer=mapnik"
title="Map showing Byte Repair in Nasr City" loading="lazy"></iframe>
  </main>
</body>
</html>
```

Project 638: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.find { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; display:
 grid; gap: 2rem; grid-template-columns: 1fr; }
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4fr;
align-items: start; } }
address { font-style: normal; line-height: 1.8; margin-bottom: 1.5rem;
 }
table { border-collapse: collapse; }
th, td { text-align: left; padding: .4rem .8rem .4rem 0; }
```

```
.map { width: 100%; aspect-ratio: 4 / 3; border: 0; border-radius:
12px; }
```

Project 638 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - Find us</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="find">	The unique content of this page; exactly one per page.
<section class="info">	A thematic group of content, normally with its own heading.
Find Byte Repair	The main heading; only one per page.
<address>	Contact information for the page or article.
Byte Repair 	Strong importance (bold by default).
+20 100 000 0000	A hyperlink; href gives the destination.
Opening hours	Second-level heading for a section.
<table>	Tabular data in rows and columns.

Line	What it does
<tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:00</td><...	A table row.
<tr><th scope="row">Friday </th><td>14:00 - 22:00</td></tr>	Header cell for a row.
<iframe class="map" src="https://www.openstreetmap.org/export/embed...	Embeds another page; title describes it for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: 1fr;	Defines the columns of the grid.
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4f...	Aligns items to the start of the cross axis (no stretching).
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
width: 100%;	Fills the container width.
aspect-ratio: 4 / 3;	Keeps a fixed width-to-height ratio, reserving space before media loads.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.

Check your work

- iframe has a title
- Address uses <address> without italic
- Map keeps its shape on resize
- Phone link works on mobile

Exercises

1. Add a 'Get directions' link to a maps URL.
2. Add a contact form under the address.
3. Use <details> for a public transport section.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 639: Find-us page with map for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 2 | Files: index.html, styles.css

Brief

Combine an address block, an opening-hours table and an embedded map iframe in a two-column responsive layout.

Learning goals

- Embed a third-party map with iframe and title
- Use address correctly
- Give the iframe a responsive aspect ratio

Elements and CSS used

HTML elements	CSS features
section, h1, address, strong, br, a, h2, table, tr, th, td, iframe	grid-template-columns: 1fr 1.4fr, aspect-ratio, border: 0, align-items: start, @media

Build guide

1. Write the info section with address and hours table.
2. Add the iframe with a descriptive title and loading="lazy".
3. Single column by default.
4. Two columns above 760px.
5. Make the map fill its column with width 100% and aspect-ratio.
6. Remove the iframe border.

Project 639: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - Find us</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="find">
    <section class="info">
      <h1>Find Sahara Pet Care</h1>
      <address>
        <strong>Sahara Pet Care</strong><br>
        12 Example Street<br>
        New Cairo, Egypt<br>
        <a href="tel:+20100000000">+20 100 000 0000</a>
      </address>
      <h2>Opening hours</h2>
      <table>
        <tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:
00</td></tr>
        <tr><th scope="row">Friday</th><td>14:00 - 22:00</td></tr>
      </table>
    </section>
    <iframe class="map" src="https://www.openstreetmap.org/export/
embed.html?bbox=31.20%2C30.02%2C31.24%2C30.06&amp;layer=mapnik"
title="Map showing Sahara Pet Care in New Cairo" loading="lazy"></
iframe>
  </main>
</body>
</html>
```

Project 639: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.find { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; display:
 grid; gap: 2rem; grid-template-columns: 1fr; }
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4fr;
align-items: start; } }
address { font-style: normal; line-height: 1.8; margin-bottom: 1.5rem;
 }
table { border-collapse: collapse; }
```

```
th, td { text-align: left; padding: .4rem .8rem .4rem 0; }
.map { width: 100%; aspect-ratio: 4 / 3; border: 0; border-radius:
12px; }
```

Project 639 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - Find us</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="find">	The unique content of this page; exactly one per page.
<section class="info">	A thematic group of content, normally with its own heading.
Find Sahara Pet Care	The main heading; only one per page.
<address>	Contact information for the page or article.
Sahara Pet Care 	Strong importance (bold by default).
+20 100 000 0000	A hyperlink; href gives the destination.
Opening hours	Second-level heading for a section.
<table>	Tabular data in rows and columns.

Line	What it does
<tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:00</td><...	A table row.
<tr><th scope="row">Friday </th><td>14:00 - 22:00</td></tr>	Header cell for a row.
<iframe class="map" src="https://www.openstreetmap.org/export/embed...	Embeds another page; title describes it for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: 1fr;	Defines the columns of the grid.
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4f...	Aligns items to the start of the cross axis (no stretching).
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
width: 100%;	Fills the container width.
aspect-ratio: 4 / 3;	Keeps a fixed width-to-height ratio, reserving space before media loads.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.

Check your work

- iframe has a title
- Address uses <address> without italic
- Map keeps its shape on resize
- Phone link works on mobile

Exercises

1. Add a 'Get directions' link to a maps URL.
2. Add a contact form under the address.
3. Use <details> for a public transport section.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 640: Find-us page with map for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Combine an address block, an opening-hours table and an embedded map iframe in a two-column responsive layout.

Learning goals

- Embed a third-party map with iframe and title
- Use address correctly
- Give the iframe a responsive aspect ratio

Elements and CSS used

HTML elements	CSS features
section, h1, address, strong, br, a, h2, table, tr, th, td, iframe	grid-template-columns: 1fr 1.4fr, aspect-ratio, border: 0, align-items: start, @media

Build guide

1. Write the info section with address and hours table.
2. Add the iframe with a descriptive title and loading="lazy".
3. Single column by default.
4. Two columns above 760px.
5. Make the map fill its column with width 100% and aspect-ratio.
6. Remove the iframe border.

Project 640: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - Find us</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="find">
    <section class="info">
      <h1>Find Alexandria Sailing School</h1>
      <address>
        <strong>Alexandria Sailing School</strong><br>
        12 Example Street<br>
        Alexandria, Egypt<br>
        <a href="tel:+20100000000">+20 100 000 0000</a>
      </address>
      <h2>Opening hours</h2>
      <table>
        <tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:
00</td></tr>
        <tr><th scope="row">Friday</th><td>14:00 - 22:00</td></tr>
      </table>
    </section>
    <iframe class="map" src="https://www.openstreetmap.org/export/
embed.html?bbox=31.20%2C30.02%2C31.24%2C30.06&amp;layer=mapnik"
title="Map showing Alexandria Sailing School in Alexandria"
loading="lazy"></iframe>
  </main>
</body>
</html>
```

Project 640: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.find { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; display:
 grid; gap: 2rem; grid-template-columns: 1fr; }
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4fr;
align-items: start; } }
address { font-style: normal; line-height: 1.8; margin-bottom: 1.5rem;
 }
table { border-collapse: collapse; }
```

```
th, td { text-align: left; padding: .4rem .8rem .4rem 0; }
.map { width: 100%; aspect-ratio: 4 / 3; border: 0; border-radius:
12px; }
```

Project 640 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - Find us</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="find">	The unique content of this page; exactly one per page.
<section class="info">	A thematic group of content, normally with its own heading.
Find Alexandria Sailing School	The main heading; only one per page.
<address>	Contact information for the page or article.
Alexandria Sailing School 	Strong importance (bold by default).
+20 100 000 0000	A hyperlink; href gives the destination.
Opening hours	Second-level heading for a section.
<table>	Tabular data in rows and columns.

Line	What it does
<tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:00</td><...	A table row.
<tr><th scope="row">Friday </th><td>14:00 - 22:00</td></tr>	Header cell for a row.
<iframe class="map" src="https://www.openstreetmap.org/export/embed...	Embeds another page; title describes it for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: 1fr;	Defines the columns of the grid.
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4f...	Aligns items to the start of the cross axis (no stretching).
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
width: 100%;	Fills the container width.
aspect-ratio: 4 / 3;	Keeps a fixed width-to-height ratio, reserving space before media loads.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.

Check your work

- iframe has a title
- Address uses <address> without italic
- Map keeps its shape on resize
- Phone link works on mobile

Exercises

1. Add a 'Get directions' link to a maps URL.
2. Add a contact form under the address.
3. Use <details> for a public transport section.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 641: Find-us page with map for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Combine an address block, an opening-hours table and an embedded map iframe in a two-column responsive layout.

Learning goals

- Embed a third-party map with iframe and title
- Use address correctly
- Give the iframe a responsive aspect ratio

Elements and CSS used

HTML elements	CSS features
section, h1, address, strong, br, a, h2, table, tr, th, td, iframe	grid-template-columns: 1fr 1.4fr, aspect-ratio, border: 0, align-items: start, @media

Build guide

1. Write the info section with address and hours table.
2. Add the iframe with a descriptive title and loading="lazy".
3. Single column by default.
4. Two columns above 760px.
5. Make the map fill its column with width 100% and aspect-ratio.
6. Remove the iframe border.

Project 641: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - Find us</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="find">
    <section class="info">
      <h1>Find Habiba Handmade Jewellery</h1>
      <address>
        <strong>Habiba Handmade Jewellery</strong><br>
        12 Example Street<br>
        Aswan, Egypt<br>
        <a href="tel:+20100000000">+20 100 000 0000</a>
      </address>
      <h2>Opening hours</h2>
      <table>
        <tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:
00</td></tr>
        <tr><th scope="row">Friday</th><td>14:00 - 22:00</td></tr>
      </table>
    </section>
    <iframe class="map" src="https://www.openstreetmap.org/export/
embed.html?bbox=31.20%2C30.02%2C31.24%2C30.06&amp;layer=mapnik"
title="Map showing Habiba Handmade Jewellery in Aswan"
loading="lazy"></iframe>
  </main>
</body>
</html>
```

Project 641: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.find { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; display:
 grid; gap: 2rem; grid-template-columns: 1fr; }
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4fr;
align-items: start; } }
address { font-style: normal; line-height: 1.8; margin-bottom: 1.5rem;
 }
table { border-collapse: collapse; }
```

```
th, td { text-align: left; padding: .4rem .8rem .4rem 0; }
.map { width: 100%; aspect-ratio: 4 / 3; border: 0; border-radius:
12px; }
```

Project 641 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - Find us</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="find">	The unique content of this page; exactly one per page.
<section class="info">	A thematic group of content, normally with its own heading.
Find Habiba Handmade Jewellery	The main heading; only one per page.
<address>	Contact information for the page or article.
Habiba Handmade Jewellery 	Strong importance (bold by default).
+20 100 000 0000	A hyperlink; href gives the destination.
Opening hours	Second-level heading for a section.
<table>	Tabular data in rows and columns.

Line	What it does
<tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:00</td><...	A table row.
<tr><th scope="row">Friday </th><td>14:00 - 22:00</td></tr>	Header cell for a row.
<iframe class="map" src="https://www.openstreetmap.org/export/embed...	Embeds another page; title describes it for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: 1fr;	Defines the columns of the grid.
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4f...	Aligns items to the start of the cross axis (no stretching).
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
width: 100%;	Fills the container width.
aspect-ratio: 4 / 3;	Keeps a fixed width-to-height ratio, reserving space before media loads.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.

Check your work

- iframe has a title
- Address uses <address> without italic
- Map keeps its shape on resize
- Phone link works on mobile

Exercises

1. Add a 'Get directions' link to a maps URL.
2. Add a contact form under the address.
3. Use <details> for a public transport section.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 642: Find-us page with map for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 2 | Files: index.html, styles.css

Brief

Combine an address block, an opening-hours table and an embedded map iframe in a two-column responsive layout.

Learning goals

- Embed a third-party map with iframe and title
- Use address correctly
- Give the iframe a responsive aspect ratio

Elements and CSS used

HTML elements	CSS features
section, h1, address, strong, br, a, h2, table, tr, th, td, iframe	grid-template-columns: 1fr 1.4fr, aspect-ratio, border: 0, align-items: start, @media

Build guide

1. Write the info section with address and hours table.
2. Add the iframe with a descriptive title and loading="lazy".
3. Single column by default.
4. Two columns above 760px.
5. Make the map fill its column with width 100% and aspect-ratio.
6. Remove the iframe border.

Project 642: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - Find us</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="find">
    <section class="info">
      <h1>Find Fayoum Pottery Studio</h1>
      <address>
        <strong>Fayoum Pottery Studio</strong><br>
        12 Example Street<br>
        Tunis Village, Egypt<br>
        <a href="tel:+20100000000">+20 100 000 0000</a>
      </address>
      <h2>Opening hours</h2>
      <table>
        <tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:
00</td></tr>
        <tr><th scope="row">Friday</th><td>14:00 - 22:00</td></tr>
      </table>
    </section>
    <iframe class="map" src="https://www.openstreetmap.org/export/
embed.html?bbox=31.20%2C30.02%2C31.24%2C30.06&amp;layer=mapnik"
title="Map showing Fayoum Pottery Studio in Tunis Village"
loading="lazy"></iframe>
  </main>
</body>
</html>
```

Project 642: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.find { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; display:
 grid; gap: 2rem; grid-template-columns: 1fr; }
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4fr;
align-items: start; } }
address { font-style: normal; line-height: 1.8; margin-bottom: 1.5rem;
 }
table { border-collapse: collapse; }
```

```
th, td { text-align: left; padding: .4rem .8rem .4rem 0; }
.map { width: 100%; aspect-ratio: 4 / 3; border: 0; border-radius:
12px; }
```

Project 642 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - Find us</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="find">	The unique content of this page; exactly one per page.
<section class="info">	A thematic group of content, normally with its own heading.
Find Fayoum Pottery Studio	The main heading; only one per page.
<address>	Contact information for the page or article.
Fayoum Pottery Studio 	Strong importance (bold by default).
+20 100 000 0000	A hyperlink; href gives the destination.
Opening hours	Second-level heading for a section.
<table>	Tabular data in rows and columns.

Line	What it does
<tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:00</td><...	A table row.
<tr><th scope="row">Friday </th><td>14:00 - 22:00</td></tr>	Header cell for a row.
<iframe class="map" src="https://www.openstreetmap.org/export/embed...	Embeds another page; title describes it for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: 1fr;	Defines the columns of the grid.
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4f...	Aligns items to the start of the cross axis (no stretching).
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
width: 100%;	Fills the container width.
aspect-ratio: 4 / 3;	Keeps a fixed width-to-height ratio, reserving space before media loads.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.

Check your work

- iframe has a title
- Address uses <address> without italic
- Map keeps its shape on resize
- Phone link works on mobile

Exercises

1. Add a 'Get directions' link to a maps URL.
2. Add a contact form under the address.
3. Use <details> for a public transport section.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 643: Find-us page with map for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 2 | Files: index.html, styles.css

Brief

Combine an address block, an opening-hours table and an embedded map iframe in a two-column responsive layout.

Learning goals

- Embed a third-party map with iframe and title
- Use address correctly
- Give the iframe a responsive aspect ratio

Elements and CSS used

HTML elements	CSS features
section, h1, address, strong, br, a, h2, table, tr, th, td, iframe	grid-template-columns: 1fr 1.4fr, aspect-ratio, border: 0, align-items: start, @media

Build guide

1. Write the info section with address and hours table.
2. Add the iframe with a descriptive title and loading="lazy".
3. Single column by default.
4. Two columns above 760px.
5. Make the map fill its column with width 100% and aspect-ratio.
6. Remove the iframe border.

Project 643: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - Find us</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="find">
    <section class="info">
      <h1>Find Cleopatra Beauty Salon</h1>
      <address>
        <strong>Cleopatra Beauty Salon</strong><br>
        12 Example Street<br>
        Dokki, Egypt<br>
        <a href="tel:+20100000000">+20 100 000 0000</a>
      </address>
      <h2>Opening hours</h2>
      <table>
        <tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:
00</td></tr>
        <tr><th scope="row">Friday</th><td>14:00 - 22:00</td></tr>
      </table>
    </section>
    <iframe class="map" src="https://www.openstreetmap.org/export/
embed.html?bbox=31.20%2C30.02%2C31.24%2C30.06&amp;layer=mapnik"
title="Map showing Cleopatra Beauty Salon in Dokki" loading="lazy"></
iframe>
  </main>
</body>
</html>
```

Project 643: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.find { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; display:
 grid; gap: 2rem; grid-template-columns: 1fr; }
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4fr;
align-items: start; } }
address { font-style: normal; line-height: 1.8; margin-bottom: 1.5rem;
 }
table { border-collapse: collapse; }
```

```
th, td { text-align: left; padding: .4rem .8rem .4rem 0; }
.map { width: 100%; aspect-ratio: 4 / 3; border: 0; border-radius:
12px; }
```

Project 643 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - Find us</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="find">	The unique content of this page; exactly one per page.
<section class="info">	A thematic group of content, normally with its own heading.
Find Cleopatra Beauty Salon	The main heading; only one per page.
<address>	Contact information for the page or article.
Cleopatra Beauty Salon 	Strong importance (bold by default).
+20 100 000 0000	A hyperlink; href gives the destination.
Opening hours	Second-level heading for a section.
<table>	Tabular data in rows and columns.

Line	What it does
<tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:00</td><...	A table row.
<tr><th scope="row">Friday </th><td>14:00 - 22:00</td></tr>	Header cell for a row.
<iframe class="map" src="https://www.openstreetmap.org/export/embed...	Embeds another page; title describes it for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: 1fr;	Defines the columns of the grid.
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4f...	Aligns items to the start of the cross axis (no stretching).
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
width: 100%;	Fills the container width.
aspect-ratio: 4 / 3;	Keeps a fixed width-to-height ratio, reserving space before media loads.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.

Check your work

- iframe has a title
- Address uses <address> without italic
- Map keeps its shape on resize
- Phone link works on mobile

Exercises

1. Add a 'Get directions' link to a maps URL.
2. Add a contact form under the address.
3. Use <details> for a public transport section.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 644: Find-us page with map for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 2 | Files: index.html, styles.css

Brief

Combine an address block, an opening-hours table and an embedded map iframe in a two-column responsive layout.

Learning goals

- Embed a third-party map with iframe and title
- Use address correctly
- Give the iframe a responsive aspect ratio

Elements and CSS used

HTML elements	CSS features
section, h1, address, strong, br, a, h2, table, tr, th, td, iframe	grid-template-columns: 1fr 1.4fr, aspect-ratio, border: 0, align-items: start, @media

Build guide

1. Write the info section with address and hours table.
2. Add the iframe with a descriptive title and loading="lazy".
3. Single column by default.
4. Two columns above 760px.
5. Make the map fill its column with width 100% and aspect-ratio.
6. Remove the iframe border.

Project 644: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - Find us</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="find">
    <section class="info">
      <h1>Find Suez Auto Service</h1>
      <address>
        <strong>Suez Auto Service</strong><br>
        12 Example Street<br>
        Suez, Egypt<br>
        <a href="tel:+20100000000">+20 100 000 0000</a>
      </address>
      <h2>Opening hours</h2>
      <table>
        <tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:
00</td></tr>
        <tr><th scope="row">Friday</th><td>14:00 - 22:00</td></tr>
      </table>
    </section>
    <iframe class="map" src="https://www.openstreetmap.org/export/
embed.html?bbox=31.20%2C30.02%2C31.24%2C30.06&amp;layer=mapnik"
title="Map showing Suez Auto Service in Suez" loading="lazy"></iframe>
  </main>
</body>
</html>
```

Project 644: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.find { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; display:
 grid; gap: 2rem; grid-template-columns: 1fr; }
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4fr;
align-items: start; } }
address { font-style: normal; line-height: 1.8; margin-bottom: 1.5rem;
 }
table { border-collapse: collapse; }
th, td { text-align: left; padding: .4rem .8rem .4rem 0; }
```

```
.map { width: 100%; aspect-ratio: 4 / 3; border: 0; border-radius:
12px; }
```

Project 644 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - Find us</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="find">	The unique content of this page; exactly one per page.
<section class="info">	A thematic group of content, normally with its own heading.
Find Suez Auto Service	The main heading; only one per page.
<address>	Contact information for the page or article.
Suez Auto Service 	Strong importance (bold by default).
+20 100 000 0000	A hyperlink; href gives the destination.
Opening hours	Second-level heading for a section.
<table>	Tabular data in rows and columns.

Line	What it does
<tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:00</td><...	A table row.
<tr><th scope="row">Friday </th><td>14:00 - 22:00</td></tr>	Header cell for a row.
<iframe class="map" src="https://www.openstreetmap.org/export/embed...	Embeds another page; title describes it for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: 1fr;	Defines the columns of the grid.
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4f...	Aligns items to the start of the cross axis (no stretching).
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
width: 100%;	Fills the container width.
aspect-ratio: 4 / 3;	Keeps a fixed width-to-height ratio, reserving space before media loads.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.

Check your work

- iframe has a title
- Address uses <address> without italic
- Map keeps its shape on resize
- Phone link works on mobile

Exercises

1. Add a 'Get directions' link to a maps URL.
2. Add a contact form under the address.
3. Use <details> for a public transport section.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 645: Find-us page with map for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 2 | Files: index.html, styles.css

Brief

Combine an address block, an opening-hours table and an embedded map iframe in a two-column responsive layout.

Learning goals

- Embed a third-party map with iframe and title
- Use address correctly
- Give the iframe a responsive aspect ratio

Elements and CSS used

HTML elements	CSS features
section, h1, address, strong, br, a, h2, table, tr, th, td, iframe	grid-template-columns: 1fr 1.4fr, aspect-ratio, border: 0, align-items: start, @media

Build guide

1. Write the info section with address and hours table.
2. Add the iframe with a descriptive title and loading="lazy".
3. Single column by default.
4. Two columns above 760px.
5. Make the map fill its column with width 100% and aspect-ratio.
6. Remove the iframe border.

Project 645: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - Find us</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="find">
    <section class="info">
      <h1>Find Luxor Music Academy</h1>
      <address>
        <strong>Luxor Music Academy</strong><br>
        12 Example Street<br>
        Luxor, Egypt<br>
        <a href="tel:+20100000000">+20 100 000 0000</a>
      </address>
      <h2>Opening hours</h2>
      <table>
        <tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:
00</td></tr>
        <tr><th scope="row">Friday</th><td>14:00 - 22:00</td></tr>
      </table>
    </section>
    <iframe class="map" src="https://www.openstreetmap.org/export/
embed.html?bbox=31.20%2C30.02%2C31.24%2C30.06&amp;layer=mapnik"
title="Map showing Luxor Music Academy in Luxor" loading="lazy"></
iframe>
  </main>
</body>
</html>
```

Project 645: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.find { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; display:
 grid; gap: 2rem; grid-template-columns: 1fr; }
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4fr;
align-items: start; } }
address { font-style: normal; line-height: 1.8; margin-bottom: 1.5rem;
 }
table { border-collapse: collapse; }
```

```
th, td { text-align: left; padding: .4rem .8rem .4rem 0; }
.map { width: 100%; aspect-ratio: 4 / 3; border: 0; border-radius:
12px; }
```

Project 645 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - Find us</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="find">	The unique content of this page; exactly one per page.
<section class="info">	A thematic group of content, normally with its own heading.
Find Luxor Music Academy	The main heading; only one per page.
<address>	Contact information for the page or article.
Luxor Music Academy 	Strong importance (bold by default).
+20 100 000 0000	A hyperlink; href gives the destination.
Opening hours	Second-level heading for a section.
<table>	Tabular data in rows and columns.

Line	What it does
<tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:00</td><...	A table row.
<tr><th scope="row">Friday </th><td>14:00 - 22:00</td></tr>	Header cell for a row.
<iframe class="map" src="https://www.openstreetmap.org/export/embed...	Embeds another page; title describes it for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: 1fr;	Defines the columns of the grid.
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4f...	Aligns items to the start of the cross axis (no stretching).
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
width: 100%;	Fills the container width.
aspect-ratio: 4 / 3;	Keeps a fixed width-to-height ratio, reserving space before media loads.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.

Check your work

- iframe has a title
- Address uses <address> without italic
- Map keeps its shape on resize
- Phone link works on mobile

Exercises

1. Add a 'Get directions' link to a maps URL.
2. Add a contact form under the address.
3. Use <details> for a public transport section.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 646: Find-us page with map for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 2 | Files: index.html, styles.css

Brief

Combine an address block, an opening-hours table and an embedded map iframe in a two-column responsive layout.

Learning goals

- Embed a third-party map with iframe and title
- Use address correctly
- Give the iframe a responsive aspect ratio

Elements and CSS used

HTML elements	CSS features
section, h1, address, strong, br, a, h2, table, tr, th, td, iframe	grid-template-columns: 1fr 1.4fr, aspect-ratio, border: 0, align-items: start, @media

Build guide

1. Write the info section with address and hours table.
2. Add the iframe with a descriptive title and loading="lazy".
3. Single column by default.
4. Two columns above 760px.
5. Make the map fill its column with width 100% and aspect-ratio.
6. Remove the iframe border.

Project 646: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - Find us</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="find">
    <section class="info">
      <h1>Find Port Said Seafood</h1>
      <address>
        <strong>Port Said Seafood</strong><br>
        12 Example Street<br>
        Port Said, Egypt<br>
        <a href="tel:+20100000000">+20 100 000 0000</a>
      </address>
      <h2>Opening hours</h2>
      <table>
        <tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:
00</td></tr>
        <tr><th scope="row">Friday</th><td>14:00 - 22:00</td></tr>
      </table>
    </section>
    <iframe class="map" src="https://www.openstreetmap.org/export/
embed.html?bbox=31.20%2C30.02%2C31.24%2C30.06&amp;layer=mapnik"
title="Map showing Port Said Seafood in Port Said" loading="lazy"></
iframe>
  </main>
</body>
</html>
```

Project 646: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.find { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; display:
 grid; gap: 2rem; grid-template-columns: 1fr; }
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4fr;
align-items: start; } }
address { font-style: normal; line-height: 1.8; margin-bottom: 1.5rem;
 }
table { border-collapse: collapse; }
```

```
th, td { text-align: left; padding: .4rem .8rem .4rem 0; }
.map { width: 100%; aspect-ratio: 4 / 3; border: 0; border-radius:
12px; }
```

Project 646 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - Find us</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="find">	The unique content of this page; exactly one per page.
<section class="info">	A thematic group of content, normally with its own heading.
Find Port Said Seafood	The main heading; only one per page.
<address>	Contact information for the page or article.
Port Said Seafood 	Strong importance (bold by default).
+20 100 000 0000	A hyperlink; href gives the destination.
Opening hours	Second-level heading for a section.
<table>	Tabular data in rows and columns.

Line	What it does
<tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:00</td><...	A table row.
<tr><th scope="row">Friday </th><td>14:00 - 22:00</td></tr>	Header cell for a row.
<iframe class="map" src="https://www.openstreetmap.org/export/embed...	Embeds another page; title describes it for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: 1fr;	Defines the columns of the grid.
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4f...	Aligns items to the start of the cross axis (no stretching).
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
width: 100%;	Fills the container width.
aspect-ratio: 4 / 3;	Keeps a fixed width-to-height ratio, reserving space before media loads.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.

Check your work

- iframe has a title
- Address uses <address> without italic
- Map keeps its shape on resize
- Phone link works on mobile

Exercises

1. Add a 'Get directions' link to a maps URL.
2. Add a contact form under the address.
3. Use <details> for a public transport section.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 647: Find-us page with map for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 2 | Files: index.html, styles.css

Brief

Combine an address block, an opening-hours table and an embedded map iframe in a two-column responsive layout.

Learning goals

- Embed a third-party map with iframe and title
- Use address correctly
- Give the iframe a responsive aspect ratio

Elements and CSS used

HTML elements	CSS features
section, h1, address, strong, br, a, h2, table, tr, th, td, iframe	grid-template-columns: 1fr 1.4fr, aspect-ratio, border: 0, align-items: start, @media

Build guide

1. Write the info section with address and hours table.
2. Add the iframe with a descriptive title and loading="lazy".
3. Single column by default.
4. Two columns above 760px.
5. Make the map fill its column with width 100% and aspect-ratio.
6. Remove the iframe border.

Project 647: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - Find us</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="find">
    <section class="info">
      <h1>Find Delta Kids Library</h1>
      <address>
        <strong>Delta Kids Library</strong><br>
        12 Example Street<br>
        Tanta, Egypt<br>
        <a href="tel:+20100000000">+20 100 000 0000</a>
      </address>
      <h2>Opening hours</h2>
      <table>
        <tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:
00</td></tr>
        <tr><th scope="row">Friday</th><td>14:00 - 22:00</td></tr>
      </table>
    </section>
    <iframe class="map" src="https://www.openstreetmap.org/export/
embed.html?bbox=31.20%2C30.02%2C31.24%2C30.06&amp;layer=mapnik"
title="Map showing Delta Kids Library in Tanta" loading="lazy"></
iframe>
  </main>
</body>
</html>
```

Project 647: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.find { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; display:
 grid; gap: 2rem; grid-template-columns: 1fr; }
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4fr;
align-items: start; } }
address { font-style: normal; line-height: 1.8; margin-bottom: 1.5rem;
 }
table { border-collapse: collapse; }
```

```
th, td { text-align: left; padding: .4rem .8rem .4rem 0; }
.map { width: 100%; aspect-ratio: 4 / 3; border: 0; border-radius:
12px; }
```

Project 647 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - Find us</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="find">	The unique content of this page; exactly one per page.
<section class="info">	A thematic group of content, normally with its own heading.
Find Delta Kids Library	The main heading; only one per page.
<address>	Contact information for the page or article.
Delta Kids Library 	Strong importance (bold by default).
+20 100 000 0000	A hyperlink; href gives the destination.
Opening hours	Second-level heading for a section.
<table>	Tabular data in rows and columns.

Line	What it does
<tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:00</td><...	A table row.
<tr><th scope="row">Friday </th><td>14:00 - 22:00</td></tr>	Header cell for a row.
<iframe class="map" src="https://www.openstreetmap.org/export/embed...	Embeds another page; title describes it for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: 1fr;	Defines the columns of the grid.
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4f...	Aligns items to the start of the cross axis (no stretching).
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
width: 100%;	Fills the container width.
aspect-ratio: 4 / 3;	Keeps a fixed width-to-height ratio, reserving space before media loads.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.

Check your work

- iframe has a title
- Address uses <address> without italic
- Map keeps its shape on resize
- Phone link works on mobile

Exercises

1. Add a 'Get directions' link to a maps URL.
2. Add a contact form under the address.
3. Use <details> for a public transport section.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 648: Find-us page with map for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Combine an address block, an opening-hours table and an embedded map iframe in a two-column responsive layout.

Learning goals

- Embed a third-party map with iframe and title
- Use address correctly
- Give the iframe a responsive aspect ratio

Elements and CSS used

HTML elements	CSS features
section, h1, address, strong, br, a, h2, table, tr, th, td, iframe	grid-template-columns: 1fr 1.4fr, aspect-ratio, border: 0, align-items: start, @media

Build guide

1. Write the info section with address and hours table.
2. Add the iframe with a descriptive title and loading="lazy".
3. Single column by default.
4. Two columns above 760px.
5. Make the map fill its column with width 100% and aspect-ratio.
6. Remove the iframe border.

Project 648: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - Find us</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="find">
    <section class="info">
      <h1>Find Nubian Guest House</h1>
      <address>
        <strong>Nubian Guest House</strong><br>
        12 Example Street<br>
        Aswan, Egypt<br>
        <a href="tel:+20100000000">+20 100 000 0000</a>
      </address>
      <h2>Opening hours</h2>
      <table>
        <tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:
00</td></tr>
        <tr><th scope="row">Friday</th><td>14:00 - 22:00</td></tr>
      </table>
    </section>
    <iframe class="map" src="https://www.openstreetmap.org/export/
embed.html?bbox=31.20%2C30.02%2C31.24%2C30.06&amp;layer=mapnik"
title="Map showing Nubian Guest House in Aswan" loading="lazy"></
iframe>
  </main>
</body>
</html>
```

Project 648: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.find { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; display:
 grid; gap: 2rem; grid-template-columns: 1fr; }
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4fr;
align-items: start; } }
address { font-style: normal; line-height: 1.8; margin-bottom: 1.5rem;
 }
table { border-collapse: collapse; }
```

```
th, td { text-align: left; padding: .4rem .8rem .4rem 0; }
.map { width: 100%; aspect-ratio: 4 / 3; border: 0; border-radius:
12px; }
```

Project 648 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - Find us</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="find">	The unique content of this page; exactly one per page.
<section class="info">	A thematic group of content, normally with its own heading.
Find Nubian Guest House	The main heading; only one per page.
<address>	Contact information for the page or article.
Nubian Guest House 	Strong importance (bold by default).
+20 100 000 0000	A hyperlink; href gives the destination.
Opening hours	Second-level heading for a section.
<table>	Tabular data in rows and columns.

Line	What it does
<tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:00</td><...	A table row.
<tr><th scope="row">Friday </th><td>14:00 - 22:00</td></tr>	Header cell for a row.
<iframe class="map" src="https://www.openstreetmap.org/export/embed...	Embeds another page; title describes it for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: 1fr;	Defines the columns of the grid.
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4f...	Aligns items to the start of the cross axis (no stretching).
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
width: 100%;	Fills the container width.
aspect-ratio: 4 / 3;	Keeps a fixed width-to-height ratio, reserving space before media loads.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.

Check your work

- iframe has a title
- Address uses <address> without italic
- Map keeps its shape on resize
- Phone link works on mobile

Exercises

1. Add a 'Get directions' link to a maps URL.
2. Add a contact form under the address.
3. Use <details> for a public transport section.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 649: Find-us page with map for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 2 | Files: index.html, styles.css

Brief

Combine an address block, an opening-hours table and an embedded map iframe in a two-column responsive layout.

Learning goals

- Embed a third-party map with iframe and title
- Use address correctly
- Give the iframe a responsive aspect ratio

Elements and CSS used

HTML elements	CSS features
section, h1, address, strong, br, a, h2, table, tr, th, td, iframe	grid-template-columns: 1fr 1.4fr, aspect-ratio, border: 0, align-items: start, @media

Build guide

1. Write the info section with address and hours table.
2. Add the iframe with a descriptive title and loading="lazy".
3. Single column by default.
4. Two columns above 760px.
5. Make the map fill its column with width 100% and aspect-ratio.
6. Remove the iframe border.

Project 649: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - Find us</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="find">
    <section class="info">
      <h1>Find Ismailia Cycling Store</h1>
      <address>
        <strong>Ismailia Cycling Store</strong><br>
        12 Example Street<br>
        Ismailia, Egypt<br>
        <a href="tel:+20100000000">+20 100 000 0000</a>
      </address>
      <h2>Opening hours</h2>
      <table>
        <tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:
00</td></tr>
        <tr><th scope="row">Friday</th><td>14:00 - 22:00</td></tr>
      </table>
    </section>
    <iframe class="map" src="https://www.openstreetmap.org/export/
embed.html?bbox=31.20%2C30.02%2C31.24%2C30.06&amp;layer=mapnik"
title="Map showing Ismailia Cycling Store in Ismailia"
loading="lazy"></iframe>
  </main>
</body>
</html>
```

Project 649: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.find { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; display:
 grid; gap: 2rem; grid-template-columns: 1fr; }
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4fr;
align-items: start; } }
address { font-style: normal; line-height: 1.8; margin-bottom: 1.5rem;
 }
table { border-collapse: collapse; }
```

```
th, td { text-align: left; padding: .4rem .8rem .4rem 0; }
.map { width: 100%; aspect-ratio: 4 / 3; border: 0; border-radius:
12px; }
```

Project 649 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - Find us</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="find">	The unique content of this page; exactly one per page.
<section class="info">	A thematic group of content, normally with its own heading.
Find Ismailia Cycling Store	The main heading; only one per page.
<address>	Contact information for the page or article.
Ismailia Cycling Store 	Strong importance (bold by default).
+20 100 000 0000	A hyperlink; href gives the destination.
Opening hours	Second-level heading for a section.
<table>	Tabular data in rows and columns.

Line	What it does
<tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:00</td><...	A table row.
<tr><th scope="row">Friday </th><td>14:00 - 22:00</td></tr>	Header cell for a row.
<iframe class="map" src="https://www.openstreetmap.org/export/embed...	Embeds another page; title describes it for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: 1fr;	Defines the columns of the grid.
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4f...	Aligns items to the start of the cross axis (no stretching).
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
width: 100%;	Fills the container width.
aspect-ratio: 4 / 3;	Keeps a fixed width-to-height ratio, reserving space before media loads.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.

Check your work

- iframe has a title
- Address uses <address> without italic
- Map keeps its shape on resize
- Phone link works on mobile

Exercises

1. Add a 'Get directions' link to a maps URL.
2. Add a contact form under the address.
3. Use <details> for a public transport section.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 650: Find-us page with map for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 2 | Files: index.html, styles.css

Brief

Combine an address block, an opening-hours table and an embedded map iframe in a two-column responsive layout.

Learning goals

- Embed a third-party map with iframe and title
- Use address correctly
- Give the iframe a responsive aspect ratio

Elements and CSS used

HTML elements	CSS features
section, h1, address, strong, br, a, h2, table, tr, th, td, iframe	grid-template-columns: 1fr 1.4fr, aspect-ratio, border: 0, align-items: start, @media

Build guide

1. Write the info section with address and hours table.
2. Add the iframe with a descriptive title and loading="lazy".
3. Single column by default.
4. Two columns above 760px.
5. Make the map fill its column with width 100% and aspect-ratio.
6. Remove the iframe border.

Project 650: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - Find us</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="find">
    <section class="info">
      <h1>Find Minya Coding Club</h1>
      <address>
        <strong>Minya Coding Club</strong><br>
        12 Example Street<br>
        Minya, Egypt<br>
        <a href="tel:+20100000000">+20 100 000 0000</a>
      </address>
      <h2>Opening hours</h2>
      <table>
        <tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:
00</td></tr>
        <tr><th scope="row">Friday</th><td>14:00 - 22:00</td></tr>
      </table>
    </section>
    <iframe class="map" src="https://www.openstreetmap.org/export/
embed.html?bbox=31.20%2C30.02%2C31.24%2C30.06&amp;layer=mapnik"
title="Map showing Minya Coding Club in Minya" loading="lazy"></
iframe>
  </main>
</body>
</html>
```

Project 650: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.find { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; display:
 grid; gap: 2rem; grid-template-columns: 1fr; }
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4fr;
align-items: start; } }
address { font-style: normal; line-height: 1.8; margin-bottom: 1.5rem;
 }
table { border-collapse: collapse; }
```

```
th, td { text-align: left; padding: .4rem .8rem .4rem 0; }
.map { width: 100%; aspect-ratio: 4 / 3; border: 0; border-radius:
12px; }
```

Project 650 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - Find us</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="find">	The unique content of this page; exactly one per page.
<section class="info">	A thematic group of content, normally with its own heading.
Find Minya Coding Club	The main heading; only one per page.
<address>	Contact information for the page or article.
Minya Coding Club 	Strong importance (bold by default).
+20 100 000 0000	A hyperlink; href gives the destination.
Opening hours	Second-level heading for a section.
<table>	Tabular data in rows and columns.

Line	What it does
<tr><th scope="row">Saturday - Thursday</th><td>10:00 - 22:00</td><...	A table row.
<tr><th scope="row">Friday </th><td>14:00 - 22:00</td></tr>	Header cell for a row.
<iframe class="map" src="https://www.openstreetmap.org/export/embed...	Embeds another page; title describes it for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 2rem;	Space between grid or flex items without extra margins.
grid-template-columns: 1fr;	Defines the columns of the grid.
@media (min-width: 760px) { .find { grid-template-columns: 1fr 1.4f...	Aligns items to the start of the cross axis (no stretching).
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
width: 100%;	Fills the container width.
aspect-ratio: 4 / 3;	Keeps a fixed width-to-height ratio, reserving space before media loads.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.

Check your work

- iframe has a title
- Address uses <address> without italic
- Map keeps its shape on resize
- Phone link works on mobile

Exercises

1. Add a 'Get directions' link to a maps URL.
2. Add a contact form under the address.
3. Use <details> for a public transport section.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: CSS-only tabs

Level 3 | 25 projects, one per theme

Build a tabbed interface without JavaScript using hidden radio buttons, labels as tabs and the :checked ~ sibling selector to show panels.

Project 651: CSS-only tabs for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 3 | Files: index.html, styles.css

Brief

Build a tabbed interface without JavaScript using hidden radio buttons, labels as tabs and the :checked ~ sibling selector to show panels.

Learning goals

- Use the :checked pseudo-class with the general sibling combinator
- Style labels as tabs
- Understand the limits of CSS-only widgets

Elements and CSS used

HTML elements	CSS features
input type=radio, label, div, section, h2, p	:checked, ~ combinator, attribute selector, display: none/block, opacity: 0 hiding

Build guide

1. Put three radio inputs with the same name first inside .tabs.
2. Add a .tablist of labels pointing at the radios.
3. Add three panels.
4. Hide the radios visually but keep them focusable.
5. Show the panel matching the checked radio with :checked ~ .panels #pN.
6. Highlight the active label the same way.

Project 651: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Compare</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="tabs">
    <input type="radio" name="tab" id="t0" checked>
    <input type="radio" name="tab" id="t1">
    <input type="radio" name="tab" id="t2">
    <div class="tablist"><label for="t0">Learn HTML</label><label
for="t1">CSS in Practice</label><label for="t2">JavaScript Basics</
label></div>
    <div class="panels">
      <section class="panel" id="p0"><h2>Learn HTML</h2><p>From your
first tag to a complete page. Price: 120 EGP.</p></section>
      <section class="panel" id="p1"><h2>CSS in Practice</
h2><p>Layouts, colours and typography. Price: 150 EGP.</p></section>
      <section class="panel" id="p2"><h2>JavaScript Basics</
h2><p>Make pages interactive. Price: 180 EGP.</p></section>
    </div>
  </main>
</body>
</html>
```

Project 651: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.tabs { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.tabs > input { position: absolute; opacity: 0; pointer-events: none;
}
.tablist { display: flex; border-bottom: 2px solid var(--line); }
.tablist label { padding: .7rem 1rem; cursor: pointer; color: var(--
muted); border-bottom: 3px solid transparent; margin-bottom: -2px; }
.tabs > input:focus-visible + .tablist label { outline: 2px solid var(
--brand); }
.panel { display: none; padding: 1.25rem 0; }
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist label[
for="t1"], #t2:checked ~ .tablist label[for="t2"] { color: var(--
brand); border-color: var(--brand); font-weight: 600; }
```

```
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~ .
panels #p2 { display: block; }
```

Project 651 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - Compare</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="tabs">	The unique content of this page; exactly one per page.
<input type="radio" name="tab" id="t0" checked>	Radio button: one choice from a group sharing the same name.
<input type="radio" name="tab" id="t1">	A form control; its type decides what it looks like.
<label for="t0">Learn HTML</label><label for="...	Text label for a control; for matches the control's id, or the label wraps the control.
	Generic block container for grouping and layout.
<section class="panel" id="p0"><h2>Learn HTML</h2><p>From your firs...	A thematic group of content, normally with its own heading.

Line	What it does
<section class="panel" id="p1"><h2>CSS in Practice</h2><p>Layouts, ...	Second-level heading for a section.
<section class="panel" id="p2"><h2>JavaScript Basics</h2><p>Make pa...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
opacity: 0;	Transparency from 0 (invisible) to 1 (solid).
pointer-events: none;	The element ignores mouse clicks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
border-bottom: 2px solid var(--line);	A bottom border used as a separator line.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border-bottom: 3px solid transparent;	The line around the element: width, style and colour.
.tabs > input:focus-visible + .tablist label {	Applies when the element is focused by keyboard; keeps focus rings visible.
display: none;	Removes the element from rendering completely.
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist labe...	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
font-weight: 600;	Thickness of the text.
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~...	General sibling combinator: later siblings of the matched element.
display: block;	Element starts on a new line and fills the width (used on links and images).

Check your work

- Arrow keys switch tabs (radio behaviour)
- First tab open by default

- Only one panel visible
- Radios are before the labels and panels in the source

Exercises

1. Add a fourth tab.
2. Add a slide-in animation on the active panel.
3. Rebuild it with buttons and JavaScript plus role=tablist for full accessibility.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 652: CSS-only tabs for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 3 | Files: index.html, styles.css

Brief

Build a tabbed interface without JavaScript using hidden radio buttons, labels as tabs and the :checked ~ sibling selector to show panels.

Learning goals

- Use the :checked pseudo-class with the general sibling combinator
- Style labels as tabs
- Understand the limits of CSS-only widgets

Elements and CSS used

HTML elements	CSS features
input type=radio, label, div, section, h2, p	:checked, ~ combinator, attribute selector, display: none/block, opacity: 0 hiding

Build guide

1. Put three radio inputs with the same name first inside .tabs.
2. Add a .tablist of labels pointing at the radios.
3. Add three panels.
4. Hide the radios visually but keep them focusable.
5. Show the panel matching the checked radio with :checked ~ .panels #pN.
6. Highlight the active label the same way.

Project 652: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - Compare</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="tabs">
    <input type="radio" name="tab" id="t0" checked>
    <input type="radio" name="tab" id="t1">
    <input type="radio" name="tab" id="t2">
    <div class="tablist"><label for="t0">Sourdough loaf</label><label
for="t1">Croissant</label><label for="t2">Date cookies</label></div>
    <div class="panels">
      <section class="panel" id="p0"><h2>Sourdough loaf</h2><p>Slow
fermented, crisp crust. Price: 60 EGP.</p></section>
      <section class="panel" id="p1"><h2>Croissant</h2><p>Butter, 27
layers. Price: 35 EGP.</p></section>
      <section class="panel" id="p2"><h2>Date cookies</
h2><p>Traditional maamoul style. Price: 80 EGP.</p></section>
    </div>
  </main>
</body>
</html>
```

Project 652: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.tabs { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.tabs > input { position: absolute; opacity: 0; pointer-events: none;
}
.tablist { display: flex; border-bottom: 2px solid var(--line); }
.tablist label { padding: .7rem 1rem; cursor: pointer; color: var(--
muted); border-bottom: 3px solid transparent; margin-bottom: -2px; }
.tabs > input:focus-visible + .tablist label { outline: 2px solid var(
--brand); }
.panel { display: none; padding: 1.25rem 0; }
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist label[
for="t1"], #t2:checked ~ .tablist label[for="t2"] { color: var(--
brand); border-color: var(--brand); font-weight: 600; }
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~ .
```

```
panels #p2 { display: block; }
```

Project 652 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - Compare</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="tabs">	The unique content of this page; exactly one per page.
<input type="radio" name="tab" id="t0" checked>	Radio button: one choice from a group sharing the same name.
<input type="radio" name="tab" id="t1">	A form control; its type decides what it looks like.
<label for="t0">Sourdough loaf</label><label f...	Text label for a control; for matches the control's id, or the label wraps the control.
	Generic block container for grouping and layout.
<section class="panel" id="p0"><h2>Sourdough loaf</h2><p>Slow ferme...	A thematic group of content, normally with its own heading.

Line	What it does
<section class="panel" id="p1"><h2>Croissant</h2><p>Butter, 27 laye...	Second-level heading for a section.
<section class="panel" id="p2"><h2>Date cookies</h2><p>Traditional ...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
opacity: 0;	Transparency from 0 (invisible) to 1 (solid).
pointer-events: none;	The element ignores mouse clicks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
border-bottom: 2px solid var(--line);	A bottom border used as a separator line.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border-bottom: 3px solid transparent;	The line around the element: width, style and colour.
.tabs > input:focus-visible + .tablist label {	Applies when the element is focused by keyboard; keeps focus rings visible.
display: none;	Removes the element from rendering completely.
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist labe...	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
font-weight: 600;	Thickness of the text.
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~...	General sibling combinator: later siblings of the matched element.
display: block;	Element starts on a new line and fills the width (used on links and images).

Check your work

- Arrow keys switch tabs (radio behaviour)
- First tab open by default

- Only one panel visible
- Radios are before the labels and panels in the source

Exercises

1. Add a fourth tab.
2. Add a slide-in animation on the active panel.
3. Rebuild it with buttons and JavaScript plus role=tablist for full accessibility.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 653: CSS-only tabs for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 3 | Files: index.html, styles.css

Brief

Build a tabbed interface without JavaScript using hidden radio buttons, labels as tabs and the :checked ~ sibling selector to show panels.

Learning goals

- Use the :checked pseudo-class with the general sibling combinator
- Style labels as tabs
- Understand the limits of CSS-only widgets

Elements and CSS used

HTML elements	CSS features
input type=radio, label, div, section, h2, p	:checked, ~ combinator, attribute selector, display: none/block, opacity: 0 hiding

Build guide

1. Put three radio inputs with the same name first inside .tabs.
2. Add a .tablist of labels pointing at the radios.
3. Add three panels.
4. Hide the radios visually but keep them focusable.
5. Show the panel matching the checked radio with :checked ~ .panels #pN.

6. Highlight the active label the same way.

Project 653: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - Compare</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="tabs">
    <input type="radio" name="tab" id="t0" checked>
    <input type="radio" name="tab" id="t1">
    <input type="radio" name="tab" id="t2">
    <div class="tablist"><label for="t0">Morning yoga</label><label
for="t1">Strength circuit</label><label for="t2">Spinning</label></
div>
    <div class="panels">
      <section class="panel" id="p0"><h2>Morning yoga</
h2><p>Flexibility and calm, 60 minutes. Price: 100 EGP.</p></section>
      <section class="panel" id="p1"><h2>Strength circuit</h2><p>Full
body, all levels. Price: 120 EGP.</p></section>
      <section class="panel" id="p2"><h2>Spinning</h2><p>High energy
cycling. Price: 110 EGP.</p></section>
    </div>
  </main>
</body>
</html>
```

Project 653: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.tabs { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.tabs > input { position: absolute; opacity: 0; pointer-events: none;
}
.tablist { display: flex; border-bottom: 2px solid var(--line); }
.tablist label { padding: .7rem 1rem; cursor: pointer; color: var(--
muted); border-bottom: 3px solid transparent; margin-bottom: -2px; }
.tabs > input:focus-visible + .tablist label { outline: 2px solid var(
--brand); }
.panel { display: none; padding: 1.25rem 0; }
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist label[
for="t1"], #t2:checked ~ .tablist label[for="t2"] { color: var(--
brand); border-color: var(--brand); font-weight: 600; }
```

```
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~ .
panels #p2 { display: block; }
```

Project 653 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - Compare</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="tabs">	The unique content of this page; exactly one per page.
<input type="radio" name="tab" id="t0" checked>	Radio button: one choice from a group sharing the same name.
<input type="radio" name="tab" id="t1">	A form control; its type decides what it looks like.
<label for="t0">Morning yoga</label><label for...	Text label for a control; for matches the control's id, or the label wraps the control.
	Generic block container for grouping and layout.
<section class="panel" id="p0"><h2>Morning yoga</h2><p>Flexibility ...	A thematic group of content, normally with its own heading.

Line	What it does
<section class="panel" id="p1"><h2>Strength circuit</h2><p>Full bod...	Second-level heading for a section.
<section class="panel" id="p2"><h2>Spinning</h2><p>High energy cycl...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
opacity: 0;	Transparency from 0 (invisible) to 1 (solid).
pointer-events: none;	The element ignores mouse clicks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
border-bottom: 2px solid var(--line);	A bottom border used as a separator line.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border-bottom: 3px solid transparent;	The line around the element: width, style and colour.
.tabs > input:focus-visible + .tablist label {	Applies when the element is focused by keyboard; keeps focus rings visible.
display: none;	Removes the element from rendering completely.
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist labe...	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
font-weight: 600;	Thickness of the text.
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~...	General sibling combinator: later siblings of the matched element.
display: block;	Element starts on a new line and fills the width (used on links and images).

Check your work

- Arrow keys switch tabs (radio behaviour)
- First tab open by default

- Only one panel visible
- Radios are before the labels and panels in the source

Exercises

1. Add a fourth tab.
2. Add a slide-in animation on the active panel.
3. Rebuild it with buttons and JavaScript plus role=tablist for full accessibility.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 654: CSS-only tabs for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 3 | Files: index.html, styles.css

Brief

Build a tabbed interface without JavaScript using hidden radio buttons, labels as tabs and the :checked ~ sibling selector to show panels.

Learning goals

- Use the :checked pseudo-class with the general sibling combinator
- Style labels as tabs
- Understand the limits of CSS-only widgets

Elements and CSS used

HTML elements	CSS features
input type=radio, label, div, section, h2, p	:checked, ~ combinator, attribute selector, display: none/block, opacity: 0 hiding

Build guide

1. Put three radio inputs with the same name first inside .tabs.
2. Add a .tablist of labels pointing at the radios.
3. Add three panels.
4. Hide the radios visually but keep them focusable.
5. Show the panel matching the checked radio with :checked ~ .panels #pN.
6. Highlight the active label the same way.

Project 654: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - Compare</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="tabs">
    <input type="radio" name="tab" id="t0" checked>
    <input type="radio" name="tab" id="t1">
    <input type="radio" name="tab" id="t2">
    <div class="tablist"><label for="t0">Check-up</label><label
for="t1">Whitening</label><label for="t2">Filling</label></div>
    <div class="panels">
      <section class="panel" id="p0"><h2>Check-up</h2><p>Examination
and cleaning. Price: 300 EGP.</p></section>
      <section class="panel" id="p1"><h2>Whitening</h2><p>Brighter
smile in one visit. Price: 1500 EGP.</p></section>
      <section class="panel" id="p2"><h2>Filling</h2><p>Tooth-
coloured composite. Price: 600 EGP.</p></section>
    </div>
  </main>
</body>
</html>
```

Project 654: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.tabs { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.tabs > input { position: absolute; opacity: 0; pointer-events: none;
}
.tablist { display: flex; border-bottom: 2px solid var(--line); }
.tablist label { padding: .7rem 1rem; cursor: pointer; color: var(--
muted); border-bottom: 3px solid transparent; margin-bottom: -2px; }
.tabs > input:focus-visible + .tablist label { outline: 2px solid var(
--brand); }
.panel { display: none; padding: 1.25rem 0; }
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist label[
for="t1"], #t2:checked ~ .tablist label[for="t2"] { color: var(--
brand); border-color: var(--brand); font-weight: 600; }
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~ .
```

```
panels #p2 { display: block; }
```

Project 654 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - Compare</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="tabs">	The unique content of this page; exactly one per page.
<input type="radio" name="tab" id="t0" checked>	Radio button: one choice from a group sharing the same name.
<input type="radio" name="tab" id="t1">	A form control; its type decides what it looks like.
<label for="t0">Check-up</label><label for="t1...	Text label for a control; for matches the control's id, or the label wraps the control.
	Generic block container for grouping and layout.
<section class="panel" id="p0"><h2>Check-up</h2><p>Examination and ...	A thematic group of content, normally with its own heading.

Line	What it does
<section class="panel" id="p1"><h2>Whitening</h2><p> Brighter smile ...	Second-level heading for a section.
<section class="panel" id="p2"><h2>Filling</h2><p>Tooth-coloured co...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
opacity: 0;	Transparency from 0 (invisible) to 1 (solid).
pointer-events: none;	The element ignores mouse clicks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
border-bottom: 2px solid var(--line);	A bottom border used as a separator line.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border-bottom: 3px solid transparent;	The line around the element: width, style and colour.
.tabs > input:focus-visible + .tablist label {	Applies when the element is focused by keyboard; keeps focus rings visible.
display: none;	Removes the element from rendering completely.
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist labe...	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
font-weight: 600;	Thickness of the text.
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~...	General sibling combinator: later siblings of the matched element.
display: block;	Element starts on a new line and fills the width (used on links and images).

Check your work

- Arrow keys switch tabs (radio behaviour)
- First tab open by default

- Only one panel visible
- Radios are before the labels and panels in the source

Exercises

1. Add a fourth tab.
2. Add a slide-in animation on the active panel.
3. Rebuild it with buttons and JavaScript plus role=tablist for full accessibility.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 655: CSS-only tabs for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 3 | Files: index.html, styles.css

Brief

Build a tabbed interface without JavaScript using hidden radio buttons, labels as tabs and the :checked ~ sibling selector to show panels.

Learning goals

- Use the :checked pseudo-class with the general sibling combinator
- Style labels as tabs
- Understand the limits of CSS-only widgets

Elements and CSS used

HTML elements	CSS features
input type=radio, label, div, section, h2, p	:checked, ~ combinator, attribute selector, display: none/block, opacity: 0 hiding

Build guide

1. Put three radio inputs with the same name first inside .tabs.
2. Add a .tablist of labels pointing at the radios.
3. Add three panels.
4. Hide the radios visually but keep them focusable.
5. Show the panel matching the checked radio with :checked ~ .panels #pN.
6. Highlight the active label the same way.

Project 655: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - Compare</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="tabs">
    <input type="radio" name="tab" id="t0" checked>
    <input type="radio" name="tab" id="t1">
    <input type="radio" name="tab" id="t2">
    <div class="tablist"><label for="t0">Luxor day trip</label><label
for="t1">Snorkelling</label><label for="t2">Desert safari</label></
div>
    <div class="panels">
      <section class="panel" id="p0"><h2>Luxor day trip</h2><p>Karnak,
 Valley of the Kings. Price: 1200 EGP.</p></section>
      <section class="panel" id="p1"><h2>Snorkelling</h2><p>Giftun
island reefs. Price: 700 EGP.</p></section>
      <section class="panel" id="p2"><h2>Desert safari</h2><p>Quad
bikes and Bedouin dinner. Price: 900 EGP.</p></section>
    </div>
  </main>
</body>
</html>
```

Project 655: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.tabs { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.tabs > input { position: absolute; opacity: 0; pointer-events: none;
}
.tablist { display: flex; border-bottom: 2px solid var(--line); }
.tablist label { padding: .7rem 1rem; cursor: pointer; color: var(--
muted); border-bottom: 3px solid transparent; margin-bottom: -2px; }
.tabs > input:focus-visible + .tablist label { outline: 2px solid var(
--brand); }
.panel { display: none; padding: 1.25rem 0; }
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist label[
for="t1"], #t2:checked ~ .tablist label[for="t2"] { color: var(--
brand); border-color: var(--brand); font-weight: 600; }
```

```
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~ .
panels #p2 { display: block; }
```

Project 655 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - Compare</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="tabs">	The unique content of this page; exactly one per page.
<input type="radio" name="tab" id="t0" checked>	Radio button: one choice from a group sharing the same name.
<input type="radio" name="tab" id="t1">	A form control; its type decides what it looks like.
<label for="t0">Luxor day trip</label><label f...	Text label for a control; for matches the control's id, or the label wraps the control.
	Generic block container for grouping and layout.
<section class="panel" id="p0"><h2>Luxor day trip</h2><p>Karnak, Va...	A thematic group of content, normally with its own heading.

Line	What it does
<section class="panel" id="p1"><h2>Snorkelling</h2><p>Giftun island...	Second-level heading for a section.
<section class="panel" id="p2"><h2>Desert safari</h2><p>Quad bikes ...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
opacity: 0;	Transparency from 0 (invisible) to 1 (solid).
pointer-events: none;	The element ignores mouse clicks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
border-bottom: 2px solid var(--line);	A bottom border used as a separator line.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border-bottom: 3px solid transparent;	The line around the element: width, style and colour.
.tabs > input:focus-visible + .tablist label {	Applies when the element is focused by keyboard; keeps focus rings visible.
display: none;	Removes the element from rendering completely.
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist labe...	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
font-weight: 600;	Thickness of the text.
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~...	General sibling combinator: later siblings of the matched element.
display: block;	Element starts on a new line and fills the width (used on links and images).

Check your work

- Arrow keys switch tabs (radio behaviour)
- First tab open by default

- Only one panel visible
- Radios are before the labels and panels in the source

Exercises

1. Add a fourth tab.
2. Add a slide-in animation on the active panel.
3. Rebuild it with buttons and JavaScript plus role=tablist for full accessibility.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 656: CSS-only tabs for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 3 | Files: index.html, styles.css

Brief

Build a tabbed interface without JavaScript using hidden radio buttons, labels as tabs and the :checked ~ sibling selector to show panels.

Learning goals

- Use the :checked pseudo-class with the general sibling combinator
- Style labels as tabs
- Understand the limits of CSS-only widgets

Elements and CSS used

HTML elements	CSS features
input type=radio, label, div, section, h2, p	:checked, ~ combinator, attribute selector, display: none/block, opacity: 0 hiding

Build guide

1. Put three radio inputs with the same name first inside .tabs.
2. Add a .tablist of labels pointing at the radios.
3. Add three panels.
4. Hide the radios visually but keep them focusable.
5. Show the panel matching the checked radio with :checked ~ .panels #pN.

6. Highlight the active label the same way.

Project 656: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - Compare</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="tabs">
    <input type="radio" name="tab" id="t0" checked>
    <input type="radio" name="tab" id="t1">
    <input type="radio" name="tab" id="t2">
    <div class="tablist"><label for="t0">English A1</label><label
for="t1">French B1</label><label for="t2">German A2</label></div>
    <div class="panels">
      <section class="panel" id="p0"><h2>English A1</h2><p>Beginner,
8 weeks. Price: 1800 EGP.</p></section>
      <section class="panel" id="p1"><h2>French B1</
h2><p>Intermediate conversation. Price: 2200 EGP.</p></section>
      <section class="panel" id="p2"><h2>German A2</h2><p>Grammar and
speaking. Price: 2000 EGP.</p></section>
    </div>
  </main>
</body>
</html>
```

Project 656: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.tabs { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.tabs > input { position: absolute; opacity: 0; pointer-events: none;
}
.tablist { display: flex; border-bottom: 2px solid var(--line); }
.tablist label { padding: .7rem 1rem; cursor: pointer; color: var(--
muted); border-bottom: 3px solid transparent; margin-bottom: -2px; }
.tabs > input:focus-visible + .tablist label { outline: 2px solid var(
--brand); }
.panel { display: none; padding: 1.25rem 0; }
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist label[
for="t1"], #t2:checked ~ .tablist label[for="t2"] { color: var(--
brand); border-color: var(--brand); font-weight: 600; }
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~ .
```

```
panels #p2 { display: block; }
```

Project 656 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - Compare</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="tabs">	The unique content of this page; exactly one per page.
<input type="radio" name="tab" id="t0" checked>	Radio button: one choice from a group sharing the same name.
<input type="radio" name="tab" id="t1">	A form control; its type decides what it looks like.
<label for="t0">English A1</label><label for="...	Text label for a control; for matches the control's id, or the label wraps the control.
	Generic block container for grouping and layout.
<section class="panel" id="p0"><h2>English A1</h2><p>Beginner, 8 we...	A thematic group of content, normally with its own heading.

Line	What it does
<section class="panel" id="p1"><h2>French B1</h2><p>Intermediate co...	Second-level heading for a section.
<section class="panel" id="p2"><h2>German A2</h2><p>Grammar and spe...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
opacity: 0;	Transparency from 0 (invisible) to 1 (solid).
pointer-events: none;	The element ignores mouse clicks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
border-bottom: 2px solid var(--line);	A bottom border used as a separator line.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border-bottom: 3px solid transparent;	The line around the element: width, style and colour.
.tabs > input:focus-visible + .tablist label {	Applies when the element is focused by keyboard; keeps focus rings visible.
display: none;	Removes the element from rendering completely.
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist labe...	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
font-weight: 600;	Thickness of the text.
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~...	General sibling combinator: later siblings of the matched element.
display: block;	Element starts on a new line and fills the width (used on links and images).

Check your work

- Arrow keys switch tabs (radio behaviour)
- First tab open by default

- Only one panel visible
- Radios are before the labels and panels in the source

Exercises

1. Add a fourth tab.
2. Add a slide-in animation on the active panel.
3. Rebuild it with buttons and JavaScript plus role=tablist for full accessibility.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 657: CSS-only tabs for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 3 | Files: index.html, styles.css

Brief

Build a tabbed interface without JavaScript using hidden radio buttons, labels as tabs and the :checked ~ sibling selector to show panels.

Learning goals

- Use the :checked pseudo-class with the general sibling combinator
- Style labels as tabs
- Understand the limits of CSS-only widgets

Elements and CSS used

HTML elements	CSS features
input type=radio, label, div, section, h2, p	:checked, ~ combinator, attribute selector, display: none/block, opacity: 0 hiding

Build guide

1. Put three radio inputs with the same name first inside .tabs.
2. Add a .tablist of labels pointing at the radios.
3. Add three panels.
4. Hide the radios visually but keep them focusable.
5. Show the panel matching the checked radio with :checked ~ .panels #pN.
6. Highlight the active label the same way.

Project 657: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - Compare</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="tabs">
    <input type="radio" name="tab" id="t0" checked>
    <input type="radio" name="tab" id="t1">
    <input type="radio" name="tab" id="t2">
    <div class="tablist"><label for="t0">Flat white</label><label
for="t1">Cold brew</label><label for="t2">Hibiscus iced tea</label></
div>
    <div class="panels">
      <section class="panel" id="p0"><h2>Flat white</h2><p>Double
shot, silky milk. Price: 55 EGP.</p></section>
      <section class="panel" id="p1"><h2>Cold brew</h2><p>18 hours
steeped. Price: 60 EGP.</p></section>
      <section class="panel" id="p2"><h2>Hibiscus iced tea</
h2><p>Karkade with mint. Price: 40 EGP.</p></section>
    </div>
  </main>
</body>
</html>
```

Project 657: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.tabs { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.tabs > input { position: absolute; opacity: 0; pointer-events: none;
}
.tablist { display: flex; border-bottom: 2px solid var(--line); }
.tablist label { padding: .7rem 1rem; cursor: pointer; color: var(--
muted); border-bottom: 3px solid transparent; margin-bottom: -2px; }
.tabs > input:focus-visible + .tablist label { outline: 2px solid var(
--brand); }
.panel { display: none; padding: 1.25rem 0; }
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist label[
for="t1"], #t2:checked ~ .tablist label[for="t2"] { color: var(--
brand); border-color: var(--brand); font-weight: 600; }
```

```
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~ .
panels #p2 { display: block; }
```

Project 657 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - Compare</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="tabs">	The unique content of this page; exactly one per page.
<input type="radio" name="tab" id="t0" checked>	Radio button: one choice from a group sharing the same name.
<input type="radio" name="tab" id="t1">	A form control; its type decides what it looks like.
<label for="t0">Flat white</label><label for="...	Text label for a control; for matches the control's id, or the label wraps the control.
	Generic block container for grouping and layout.
<section class="panel" id="p0"><h2>Flat white</h2><p>Double shot, s...	A thematic group of content, normally with its own heading.

Line	What it does
<section class="panel" id="p1"><h2>Cold brew</h2><p>18 hours steepe...	Second-level heading for a section.
<section class="panel" id="p2"><h2>Hibiscus iced tea</h2><p>Karkade...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
opacity: 0;	Transparency from 0 (invisible) to 1 (solid).
pointer-events: none;	The element ignores mouse clicks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
border-bottom: 2px solid var(--line);	A bottom border used as a separator line.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border-bottom: 3px solid transparent;	The line around the element: width, style and colour.
.tabs > input:focus-visible + .tablist label {	Applies when the element is focused by keyboard; keeps focus rings visible.
display: none;	Removes the element from rendering completely.
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist labe...	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
font-weight: 600;	Thickness of the text.
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~...	General sibling combinator: later siblings of the matched element.
display: block;	Element starts on a new line and fills the width (used on links and images).

Check your work

- Arrow keys switch tabs (radio behaviour)
- First tab open by default

- Only one panel visible
- Radios are before the labels and panels in the source

Exercises

1. Add a fourth tab.
2. Add a slide-in animation on the active panel.
3. Rebuild it with buttons and JavaScript plus role=tablist for full accessibility.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 658: CSS-only tabs for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 3 | Files: index.html, styles.css

Brief

Build a tabbed interface without JavaScript using hidden radio buttons, labels as tabs and the :checked ~ sibling selector to show panels.

Learning goals

- Use the :checked pseudo-class with the general sibling combinator
- Style labels as tabs
- Understand the limits of CSS-only widgets

Elements and CSS used

HTML elements	CSS features
input type=radio, label, div, section, h2, p	:checked, ~ combinator, attribute selector, display: none/block, opacity: 0 hiding

Build guide

1. Put three radio inputs with the same name first inside .tabs.
2. Add a .tablist of labels pointing at the radios.
3. Add three panels.
4. Hide the radios visually but keep them focusable.
5. Show the panel matching the checked radio with :checked ~ .panels #pN.

6. Highlight the active label the same way.

Project 658: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - Compare</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="tabs">
    <input type="radio" name="tab" id="t0" checked>
    <input type="radio" name="tab" id="t1">
    <input type="radio" name="tab" id="t2">
    <div class="tablist"><label for="t0">Mount Sinai sunrise</
label><label for="t1">Blue Desert loop</label><label for="t2">Wadi
Gnai</label></div>
    <div class="panels">
      <section class="panel" id="p0"><h2>Mount Sinai sunrise</
h2><p>Night climb, 7 km. Price: 400 EGP.</p></section>
      <section class="panel" id="p1"><h2>Blue Desert loop</h2><p>Easy
day walk. Price: 250 EGP.</p></section>
      <section class="panel" id="p2"><h2>Wadi Gnai</h2><p>Palms and
pools. Price: 300 EGP.</p></section>
    </div>
  </main>
</body>
</html>
```

Project 658: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.tabs { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.tabs > input { position: absolute; opacity: 0; pointer-events: none;
}
.tablist { display: flex; border-bottom: 2px solid var(--line); }
.tablist label { padding: .7rem 1rem; cursor: pointer; color: var(--
muted); border-bottom: 3px solid transparent; margin-bottom: -2px; }
.tabs > input:focus-visible + .tablist label { outline: 2px solid var(
--brand); }
.panel { display: none; padding: 1.25rem 0; }
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist label[
for="t1"], #t2:checked ~ .tablist label[for="t2"] { color: var(--
brand); border-color: var(--brand); font-weight: 600; }
```

```
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~ .
panels #p2 { display: block; }
```

Project 658 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - Compare</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="tabs">	The unique content of this page; exactly one per page.
<input type="radio" name="tab" id="t0" checked>	Radio button: one choice from a group sharing the same name.
<input type="radio" name="tab" id="t1">	A form control; its type decides what it looks like.
<label for="t0">Mount Sinai sunrise</label><la...	Text label for a control; for matches the control's id, or the label wraps the control.
	Generic block container for grouping and layout.
<section class="panel" id="p0"><h2>Mount Sinai sunrise</h2><p>Night...	A thematic group of content, normally with its own heading.

Line	What it does
<section class="panel" id="p1"><h2>Blue Desert loop</h2><p>Easy day...	Second-level heading for a section.
<section class="panel" id="p2"><h2>Wadi Gnai</h2><p>Palms and pools...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
opacity: 0;	Transparency from 0 (invisible) to 1 (solid).
pointer-events: none;	The element ignores mouse clicks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
border-bottom: 2px solid var(--line);	A bottom border used as a separator line.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border-bottom: 3px solid transparent;	The line around the element: width, style and colour.
.tabs > input:focus-visible + .tablist label {	Applies when the element is focused by keyboard; keeps focus rings visible.
display: none;	Removes the element from rendering completely.
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist labe...	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
font-weight: 600;	Thickness of the text.
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~...	General sibling combinator: later siblings of the matched element.
display: block;	Element starts on a new line and fills the width (used on links and images).

Check your work

- Arrow keys switch tabs (radio behaviour)
- First tab open by default

- Only one panel visible
- Radios are before the labels and panels in the source

Exercises

1. Add a fourth tab.
2. Add a slide-in animation on the active panel.
3. Rebuild it with buttons and JavaScript plus role=tablist for full accessibility.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 659: CSS-only tabs for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 3 | Files: index.html, styles.css

Brief

Build a tabbed interface without JavaScript using hidden radio buttons, labels as tabs and the :checked ~ sibling selector to show panels.

Learning goals

- Use the :checked pseudo-class with the general sibling combinator
- Style labels as tabs
- Understand the limits of CSS-only widgets

Elements and CSS used

HTML elements	CSS features
input type=radio, label, div, section, h2, p	:checked, ~ combinator, attribute selector, display: none/block, opacity: 0 hiding

Build guide

1. Put three radio inputs with the same name first inside .tabs.
2. Add a .tablist of labels pointing at the radios.
3. Add three panels.
4. Hide the radios visually but keep them focusable.
5. Show the panel matching the checked radio with :checked ~ .panels #pN.
6. Highlight the active label the same way.

Project 659: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - Compare</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="tabs">
    <input type="radio" name="tab" id="t0" checked>
    <input type="radio" name="tab" id="t1">
    <input type="radio" name="tab" id="t2">
    <div class="tablist"><label for="t0">Portrait session</
label><label for="t1">Wedding day</label><label for="t2">Product
shoot</label></div>
    <div class="panels">
      <section class="panel" id="p0"><h2>Portrait session</h2><p>One
hour, 20 edited photos. Price: 1200 EGP.</p></section>
      <section class="panel" id="p1"><h2>Wedding day</h2><p>Full
coverage, two photographers. Price: 15000 EGP.</p></section>
      <section class="panel" id="p2"><h2>Product shoot</h2><p>White
background, 10 items. Price: 900 EGP.</p></section>
    </div>
  </main>
</body>
</html>
```

Project 659: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.tabs { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.tabs > input { position: absolute; opacity: 0; pointer-events: none;
}
.tablist { display: flex; border-bottom: 2px solid var(--line); }
.tablist label { padding: .7rem 1rem; cursor: pointer; color: var(--
muted); border-bottom: 3px solid transparent; margin-bottom: -2px; }
.tabs > input:focus-visible + .tablist label { outline: 2px solid var(
--brand); }
.panel { display: none; padding: 1.25rem 0; }
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist label[
for="t1"], #t2:checked ~ .tablist label[for="t2"] { color: var(--
brand); border-color: var(--brand); font-weight: 600; }
```

```
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~ .
panels #p2 { display: block; }
```

Project 659 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - Compare</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="tabs">	The unique content of this page; exactly one per page.
<input type="radio" name="tab" id="t0" checked>	Radio button: one choice from a group sharing the same name.
<input type="radio" name="tab" id="t1">	A form control; its type decides what it looks like.
<label for="t0">Portrait session</label><label...	Text label for a control; for matches the control's id, or the label wraps the control.
	Generic block container for grouping and layout.
<section class="panel" id="p0"><h2>Portrait session</h2><p>One hour...	A thematic group of content, normally with its own heading.

Line	What it does
<section class="panel" id="p1"><h2>Wedding day</h2><p>Full coverage...	Second-level heading for a section.
<section class="panel" id="p2"><h2>Product shoot</h2><p>White backg...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
opacity: 0;	Transparency from 0 (invisible) to 1 (solid).
pointer-events: none;	The element ignores mouse clicks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
border-bottom: 2px solid var(--line);	A bottom border used as a separator line.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border-bottom: 3px solid transparent;	The line around the element: width, style and colour.
.tabs > input:focus-visible + .tablist label {	Applies when the element is focused by keyboard; keeps focus rings visible.
display: none;	Removes the element from rendering completely.
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist labe...	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
font-weight: 600;	Thickness of the text.
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~...	General sibling combinator: later siblings of the matched element.
display: block;	Element starts on a new line and fills the width (used on links and images).

Check your work

- Arrow keys switch tabs (radio behaviour)
- First tab open by default

- Only one panel visible
- Radios are before the labels and panels in the source

Exercises

1. Add a fourth tab.
2. Add a slide-in animation on the active panel.
3. Rebuild it with buttons and JavaScript plus role=tablist for full accessibility.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 660: CSS-only tabs for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 3 | Files: index.html, styles.css

Brief

Build a tabbed interface without JavaScript using hidden radio buttons, labels as tabs and the :checked ~ sibling selector to show panels.

Learning goals

- Use the :checked pseudo-class with the general sibling combinator
- Style labels as tabs
- Understand the limits of CSS-only widgets

Elements and CSS used

HTML elements	CSS features
input type=radio, label, div, section, h2, p	:checked, ~ combinator, attribute selector, display: none/block, opacity: 0 hiding

Build guide

1. Put three radio inputs with the same name first inside .tabs.
2. Add a .tablist of labels pointing at the radios.
3. Add three panels.
4. Hide the radios visually but keep them focusable.
5. Show the panel matching the checked radio with :checked ~ .panels #pN.
6. Highlight the active label the same way.

Project 660: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - Compare</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="tabs">
    <input type="radio" name="tab" id="t0" checked>
    <input type="radio" name="tab" id="t1">
    <input type="radio" name="tab" id="t2">
    <div class="tablist"><label for="t0">Dotted notebook</
label><label for="t1">Fountain pen</label><label for="t2">Washi tape
set</label></div>
    <div class="panels">
      <section class="panel" id="p0"><h2>Dotted notebook</h2><p>A5,
160 pages. Price: 140 EGP.</p></section>
      <section class="panel" id="p1"><h2>Fountain pen</h2><p>Steel
nib, refillable. Price: 350 EGP.</p></section>
      <section class="panel" id="p2"><h2>Washi tape set</h2><p>Six
patterns. Price: 90 EGP.</p></section>
    </div>
  </main>
</body>
</html>
```

Project 660: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.tabs { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.tabs > input { position: absolute; opacity: 0; pointer-events: none;
}
.tablist { display: flex; border-bottom: 2px solid var(--line); }
.tablist label { padding: .7rem 1rem; cursor: pointer; color: var(--
muted); border-bottom: 3px solid transparent; margin-bottom: -2px; }
.tabs > input:focus-visible + .tablist label { outline: 2px solid var(
--brand); }
.panel { display: none; padding: 1.25rem 0; }
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist label[
for="t1"], #t2:checked ~ .tablist label[for="t2"] { color: var(--
brand); border-color: var(--brand); font-weight: 600; }
```

```
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~ .
panels #p2 { display: block; }
```

Project 660 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - Compare</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="tabs">	The unique content of this page; exactly one per page.
<input type="radio" name="tab" id="t0" checked>	Radio button: one choice from a group sharing the same name.
<input type="radio" name="tab" id="t1">	A form control; its type decides what it looks like.
<label for="t0">Dotted notebook</label><label ...	Text label for a control; for matches the control's id, or the label wraps the control.
	Generic block container for grouping and layout.
<section class="panel" id="p0"><h2>Dotted notebook</h2><p>A5, 160 p...	A thematic group of content, normally with its own heading.

Line	What it does
<section class="panel" id="p1"><h2>Fountain pen</h2><p>Steel nib, r...	Second-level heading for a section.
<section class="panel" id="p2"><h2>Washi tape set</h2><p>Six patter...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
opacity: 0;	Transparency from 0 (invisible) to 1 (solid).
pointer-events: none;	The element ignores mouse clicks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
border-bottom: 2px solid var(--line);	A bottom border used as a separator line.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border-bottom: 3px solid transparent;	The line around the element: width, style and colour.
.tabs > input:focus-visible + .tablist label {	Applies when the element is focused by keyboard; keeps focus rings visible.
display: none;	Removes the element from rendering completely.
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist labe...	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
font-weight: 600;	Thickness of the text.
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~...	General sibling combinator: later siblings of the matched element.
display: block;	Element starts on a new line and fills the width (used on links and images).

Check your work

- Arrow keys switch tabs (radio behaviour)
- First tab open by default

- Only one panel visible
- Radios are before the labels and panels in the source

Exercises

1. Add a fourth tab.
2. Add a slide-in animation on the active panel.
3. Rebuild it with buttons and JavaScript plus role=tablist for full accessibility.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 661: CSS-only tabs for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 3 | Files: index.html, styles.css

Brief

Build a tabbed interface without JavaScript using hidden radio buttons, labels as tabs and the :checked ~ sibling selector to show panels.

Learning goals

- Use the :checked pseudo-class with the general sibling combinator
- Style labels as tabs
- Understand the limits of CSS-only widgets

Elements and CSS used

HTML elements	CSS features
input type=radio, label, div, section, h2, p	:checked, ~ combinator, attribute selector, display: none/block, opacity: 0 hiding

Build guide

1. Put three radio inputs with the same name first inside .tabs.
2. Add a .tablist of labels pointing at the radios.
3. Add three panels.
4. Hide the radios visually but keep them focusable.
5. Show the panel matching the checked radio with :checked ~ .panels #pN.

6. Highlight the active label the same way.

Project 661: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - Compare</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="tabs">
    <input type="radio" name="tab" id="t0" checked>
    <input type="radio" name="tab" id="t1">
    <input type="radio" name="tab" id="t2">
    <div class="tablist"><label for="t0">Monstera</label><label
for="t1">Snake plant</label><label for="t2">Basil pot</label></div>
    <div class="panels">
      <section class="panel" id="p0"><h2>Monstera</h2><p>Large leaves,
 easy care. Price: 250 EGP.</p></section>
      <section class="panel" id="p1"><h2>Snake plant</h2><p>Survives
anything. Price: 120 EGP.</p></section>
      <section class="panel" id="p2"><h2>Basil pot</h2><p>Kitchen
herb. Price: 45 EGP.</p></section>
    </div>
  </main>
</body>
</html>
```

Project 661: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.tabs { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.tabs > input { position: absolute; opacity: 0; pointer-events: none;
}
.tablist { display: flex; border-bottom: 2px solid var(--line); }
.tablist label { padding: .7rem 1rem; cursor: pointer; color: var(--
muted); border-bottom: 3px solid transparent; margin-bottom: -2px; }
.tabs > input:focus-visible + .tablist label { outline: 2px solid var(
--brand); }
.panel { display: none; padding: 1.25rem 0; }
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist label[
for="t1"], #t2:checked ~ .tablist label[for="t2"] { color: var(--
brand); border-color: var(--brand); font-weight: 600; }
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~ .
```

```
panels #p2 { display: block; }
```

Project 661 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - Compare</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="tabs">	The unique content of this page; exactly one per page.
<input type="radio" name="tab" id="t0" checked>	Radio button: one choice from a group sharing the same name.
<input type="radio" name="tab" id="t1">	A form control; its type decides what it looks like.
<label for="t0">Monstera</label><label for="t1...	Text label for a control; for matches the control's id, or the label wraps the control.
	Generic block container for grouping and layout.
<section class="panel" id="p0"><h2>Monstera</h2><p>Large leaves, ea...	A thematic group of content, normally with its own heading.

Line	What it does
<section class="panel" id="p1"><h2>Snake plant</h2><p>Survives anyt...	Second-level heading for a section.
<section class="panel" id="p2"><h2>Basil pot</h2><p>Kitchen herb. P...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
opacity: 0;	Transparency from 0 (invisible) to 1 (solid).
pointer-events: none;	The element ignores mouse clicks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
border-bottom: 2px solid var(--line);	A bottom border used as a separator line.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border-bottom: 3px solid transparent;	The line around the element: width, style and colour.
.tabs > input:focus-visible + .tablist label {	Applies when the element is focused by keyboard; keeps focus rings visible.
display: none;	Removes the element from rendering completely.
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist labe...	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
font-weight: 600;	Thickness of the text.
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~...	General sibling combinator: later siblings of the matched element.
display: block;	Element starts on a new line and fills the width (used on links and images).

Check your work

- Arrow keys switch tabs (radio behaviour)
- First tab open by default

- Only one panel visible
- Radios are before the labels and panels in the source

Exercises

1. Add a fourth tab.
2. Add a slide-in animation on the active panel.
3. Rebuild it with buttons and JavaScript plus role=tablist for full accessibility.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 662: CSS-only tabs for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 3 | Files: index.html, styles.css

Brief

Build a tabbed interface without JavaScript using hidden radio buttons, labels as tabs and the :checked ~ sibling selector to show panels.

Learning goals

- Use the :checked pseudo-class with the general sibling combinator
- Style labels as tabs
- Understand the limits of CSS-only widgets

Elements and CSS used

HTML elements	CSS features
input type=radio, label, div, section, h2, p	:checked, ~ combinator, attribute selector, display: none/block, opacity: 0 hiding

Build guide

1. Put three radio inputs with the same name first inside .tabs.
2. Add a .tablist of labels pointing at the radios.
3. Add three panels.
4. Hide the radios visually but keep them focusable.
5. Show the panel matching the checked radio with :checked ~ .panels #pN.
6. Highlight the active label the same way.

Project 662: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - Compare</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="tabs">
    <input type="radio" name="tab" id="t0" checked>
    <input type="radio" name="tab" id="t1">
    <input type="radio" name="tab" id="t2">
    <div class="tablist"><label for="t0">Oak dining table</
label><label for="t1">Bookshelf</label><label for="t2">Bedside table</
label></div>
    <div class="panels">
      <section class="panel" id="p0"><h2>Oak dining table</
h2><p>Seats six. Price: 9500 EGP.</p></section>
      <section class="panel" id="p1"><h2>Bookshelf</h2><p>Five
shelves, walnut. Price: 4200 EGP.</p></section>
      <section class="panel" id="p2"><h2>Bedside table</h2><p>One
drawer. Price: 1500 EGP.</p></section>
    </div>
  </main>
</body>
</html>
```

Project 662: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.tabs { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.tabs > input { position: absolute; opacity: 0; pointer-events: none;
}
.tablist { display: flex; border-bottom: 2px solid var(--line); }
.tablist label { padding: .7rem 1rem; cursor: pointer; color: var(--
muted); border-bottom: 3px solid transparent; margin-bottom: -2px; }
.tabs > input:focus-visible + .tablist label { outline: 2px solid var(
--brand); }
.panel { display: none; padding: 1.25rem 0; }
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist label[
for="t1"], #t2:checked ~ .tablist label[for="t2"] { color: var(--
brand); border-color: var(--brand); font-weight: 600; }
```

```
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~ .
panels #p2 { display: block; }
```

Project 662 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - Compare</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="tabs">	The unique content of this page; exactly one per page.
<input type="radio" name="tab" id="t0" checked>	Radio button: one choice from a group sharing the same name.
<input type="radio" name="tab" id="t1">	A form control; its type decides what it looks like.
<label for="t0">Oak dining table</label><label...	Text label for a control; for matches the control's id, or the label wraps the control.
	Generic block container for grouping and layout.
<section class="panel" id="p0"><h2>Oak dining table</h2><p>Seats si...	A thematic group of content, normally with its own heading.

Line	What it does
<section class="panel" id="p1"><h2>Bookshelf</h2><p>Five shelves, w...	Second-level heading for a section.
<section class="panel" id="p2"><h2>Bedside table</h2><p>One drawer....	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
opacity: 0;	Transparency from 0 (invisible) to 1 (solid).
pointer-events: none;	The element ignores mouse clicks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
border-bottom: 2px solid var(--line);	A bottom border used as a separator line.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border-bottom: 3px solid transparent;	The line around the element: width, style and colour.
.tabs > input:focus-visible + .tablist label {	Applies when the element is focused by keyboard; keeps focus rings visible.
display: none;	Removes the element from rendering completely.
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist labe...	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
font-weight: 600;	Thickness of the text.
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~...	General sibling combinator: later siblings of the matched element.
display: block;	Element starts on a new line and fills the width (used on links and images).

Check your work

- Arrow keys switch tabs (radio behaviour)
- First tab open by default

- Only one panel visible
- Radios are before the labels and panels in the source

Exercises

1. Add a fourth tab.
2. Add a slide-in animation on the active panel.
3. Rebuild it with buttons and JavaScript plus role=tablist for full accessibility.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 663: CSS-only tabs for Byte Repair

Theme: Byte Repair (Nasr City) | Level 3 | Files: index.html, styles.css

Brief

Build a tabbed interface without JavaScript using hidden radio buttons, labels as tabs and the :checked ~ sibling selector to show panels.

Learning goals

- Use the :checked pseudo-class with the general sibling combinator
- Style labels as tabs
- Understand the limits of CSS-only widgets

Elements and CSS used

HTML elements	CSS features
input type=radio, label, div, section, h2, p	:checked, ~ combinator, attribute selector, display: none/block, opacity: 0 hiding

Build guide

1. Put three radio inputs with the same name first inside .tabs.
2. Add a .tablist of labels pointing at the radios.
3. Add three panels.
4. Hide the radios visually but keep them focusable.
5. Show the panel matching the checked radio with :checked ~ .panels #pN.
6. Highlight the active label the same way.

Project 663: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - Compare</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="tabs">
    <input type="radio" name="tab" id="t0" checked>
    <input type="radio" name="tab" id="t1">
    <input type="radio" name="tab" id="t2">
    <div class="tablist"><label for="t0">Screen replacement</
label><label for="t1">Battery swap</label><label for="t2">Laptop
cleaning</label></div>
    <div class="panels">
      <section class="panel" id="p0"><h2>Screen replacement</
h2><p>Most phones, 1 hour. Price: From 800 EGP.</p></section>
      <section class="panel" id="p1"><h2>Battery swap</h2><p>Original
cells. Price: From 500 EGP.</p></section>
      <section class="panel" id="p2"><h2>Laptop cleaning</h2><p>Fans
and thermal paste. Price: 350 EGP.</p></section>
    </div>
  </main>
</body>
</html>
```

Project 663: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.tabs { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.tabs > input { position: absolute; opacity: 0; pointer-events: none;
}
.tablist { display: flex; border-bottom: 2px solid var(--line); }
.tablist label { padding: .7rem 1rem; cursor: pointer; color: var(--
muted); border-bottom: 3px solid transparent; margin-bottom: -2px; }
.tabs > input:focus-visible + .tablist label { outline: 2px solid var(
--brand); }
.panel { display: none; padding: 1.25rem 0; }
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist label[
for="t1"], #t2:checked ~ .tablist label[for="t2"] { color: var(--
brand); border-color: var(--brand); font-weight: 600; }
```

```
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~ .
panels #p2 { display: block; }
```

Project 663 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - Compare</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="tabs">	The unique content of this page; exactly one per page.
<input type="radio" name="tab" id="t0" checked>	Radio button: one choice from a group sharing the same name.
<input type="radio" name="tab" id="t1">	A form control; its type decides what it looks like.
<label for="t0">Screen replacement</label><lab...	Text label for a control; for matches the control's id, or the label wraps the control.
	Generic block container for grouping and layout.
<section class="panel" id="p0"><h2>Screen replacement</h2><p>Most p...	A thematic group of content, normally with its own heading.

Line	What it does
<section class="panel" id="p1"><h2>Battery swap</h2><p>Original cel...	Second-level heading for a section.
<section class="panel" id="p2"><h2>Laptop cleaning</h2><p>Fans and ...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
opacity: 0;	Transparency from 0 (invisible) to 1 (solid).
pointer-events: none;	The element ignores mouse clicks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
border-bottom: 2px solid var(--line);	A bottom border used as a separator line.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border-bottom: 3px solid transparent;	The line around the element: width, style and colour.
.tabs > input:focus-visible + .tablist label {	Applies when the element is focused by keyboard; keeps focus rings visible.
display: none;	Removes the element from rendering completely.
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist labe...	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
font-weight: 600;	Thickness of the text.
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~...	General sibling combinator: later siblings of the matched element.
display: block;	Element starts on a new line and fills the width (used on links and images).

Check your work

- Arrow keys switch tabs (radio behaviour)
- First tab open by default

- Only one panel visible
- Radios are before the labels and panels in the source

Exercises

1. Add a fourth tab.
2. Add a slide-in animation on the active panel.
3. Rebuild it with buttons and JavaScript plus role=tablist for full accessibility.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 664: CSS-only tabs for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 3 | Files: index.html, styles.css

Brief

Build a tabbed interface without JavaScript using hidden radio buttons, labels as tabs and the :checked ~ sibling selector to show panels.

Learning goals

- Use the :checked pseudo-class with the general sibling combinator
- Style labels as tabs
- Understand the limits of CSS-only widgets

Elements and CSS used

HTML elements	CSS features
input type=radio, label, div, section, h2, p	:checked, ~ combinator, attribute selector, display: none/block, opacity: 0 hiding

Build guide

1. Put three radio inputs with the same name first inside .tabs.
2. Add a .tablist of labels pointing at the radios.
3. Add three panels.
4. Hide the radios visually but keep them focusable.
5. Show the panel matching the checked radio with :checked ~ .panels #pN.
6. Highlight the active label the same way.

Project 664: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - Compare</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="tabs">
    <input type="radio" name="tab" id="t0" checked>
    <input type="radio" name="tab" id="t1">
    <input type="radio" name="tab" id="t2">
    <div class="tablist"><label for="t0">Full grooming</label><label
for="t1">Day boarding</label><label for="t2">Vaccination</label></div>
    <div class="panels">
      <section class="panel" id="p0"><h2>Full grooming</h2><p>Bath,
cut and nails. Price: 400 EGP.</p></section>
      <section class="panel" id="p1"><h2>Day boarding</h2><p>Play and
rest. Price: 250 EGP.</p></section>
      <section class="panel" id="p2"><h2>Vaccination</h2><p>Annual
boosters. Price: 300 EGP.</p></section>
    </div>
  </main>
</body>
</html>
```

Project 664: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.tabs { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.tabs > input { position: absolute; opacity: 0; pointer-events: none;
}
.tablist { display: flex; border-bottom: 2px solid var(--line); }
.tablist label { padding: .7rem 1rem; cursor: pointer; color: var(--
muted); border-bottom: 3px solid transparent; margin-bottom: -2px; }
.tabs > input:focus-visible + .tablist label { outline: 2px solid var(
--brand); }
.panel { display: none; padding: 1.25rem 0; }
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist label[
for="t1"], #t2:checked ~ .tablist label[for="t2"] { color: var(--
brand); border-color: var(--brand); font-weight: 600; }
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~ .
```

```
panels #p2 { display: block; }
```

Project 664 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - Compare</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="tabs">	The unique content of this page; exactly one per page.
<input type="radio" name="tab" id="t0" checked>	Radio button: one choice from a group sharing the same name.
<input type="radio" name="tab" id="t1">	A form control; its type decides what it looks like.
<label for="t0">Full grooming</label><label fo...	Text label for a control; for matches the control's id, or the label wraps the control.
	Generic block container for grouping and layout.
<section class="panel" id="p0"><h2>Full grooming</h2><p>Bath, cut a...	A thematic group of content, normally with its own heading.

Line	What it does
<section class="panel" id="p1"><h2>Day boarding</h2><p>Play and res...	Second-level heading for a section.
<section class="panel" id="p2"><h2>Vaccination</h2><p>Annual booste...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
opacity: 0;	Transparency from 0 (invisible) to 1 (solid).
pointer-events: none;	The element ignores mouse clicks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
border-bottom: 2px solid var(--line);	A bottom border used as a separator line.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border-bottom: 3px solid transparent;	The line around the element: width, style and colour.
.tabs > input:focus-visible + .tablist label {	Applies when the element is focused by keyboard; keeps focus rings visible.
display: none;	Removes the element from rendering completely.
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist labe...	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
font-weight: 600;	Thickness of the text.
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~...	General sibling combinator: later siblings of the matched element.
display: block;	Element starts on a new line and fills the width (used on links and images).

Check your work

- Arrow keys switch tabs (radio behaviour)
- First tab open by default

- Only one panel visible
- Radios are before the labels and panels in the source

Exercises

1. Add a fourth tab.
2. Add a slide-in animation on the active panel.
3. Rebuild it with buttons and JavaScript plus role=tablist for full accessibility.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 665: CSS-only tabs for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 3 | Files: index.html, styles.css

Brief

Build a tabbed interface without JavaScript using hidden radio buttons, labels as tabs and the :checked ~ sibling selector to show panels.

Learning goals

- Use the :checked pseudo-class with the general sibling combinator
- Style labels as tabs
- Understand the limits of CSS-only widgets

Elements and CSS used

HTML elements	CSS features
input type=radio, label, div, section, h2, p	:checked, ~ combinator, attribute selector, display: none/block, opacity: 0 hiding

Build guide

1. Put three radio inputs with the same name first inside .tabs.
2. Add a .tablist of labels pointing at the radios.
3. Add three panels.
4. Hide the radios visually but keep them focusable.
5. Show the panel matching the checked radio with :checked ~ .panels #pN.

6. Highlight the active label the same way.

Project 665: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - Compare</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="tabs">
    <input type="radio" name="tab" id="t0" checked>
    <input type="radio" name="tab" id="t1">
    <input type="radio" name="tab" id="t2">
    <div class="tablist"><label for="t0">Taster session</label><label
for="t1">Beginner course</label><label for="t2">Racing clinic</
label></div>
    <div class="panels">
      <section class="panel" id="p0"><h2>Taster session</h2><p>Two
hours on the water. Price: 500 EGP.</p></section>
      <section class="panel" id="p1"><h2>Beginner course</h2><p>Five
sessions. Price: 2200 EGP.</p></section>
      <section class="panel" id="p2"><h2>Racing clinic</h2><p>Tactics
and trim. Price: 1800 EGP.</p></section>
    </div>
  </main>
</body>
</html>
```

Project 665: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.tabs { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.tabs > input { position: absolute; opacity: 0; pointer-events: none;
}
.tablist { display: flex; border-bottom: 2px solid var(--line); }
.tablist label { padding: .7rem 1rem; cursor: pointer; color: var(--
muted); border-bottom: 3px solid transparent; margin-bottom: -2px; }
.tabs > input:focus-visible + .tablist label { outline: 2px solid var(
--brand); }
.panel { display: none; padding: 1.25rem 0; }
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist label[
for="t1"], #t2:checked ~ .tablist label[for="t2"] { color: var(--
brand); border-color: var(--brand); font-weight: 600; }
```

```
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~ .
panels #p2 { display: block; }
```

Project 665 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - Compare</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="tabs">	The unique content of this page; exactly one per page.
<input type="radio" name="tab" id="t0" checked>	Radio button: one choice from a group sharing the same name.
<input type="radio" name="tab" id="t1">	A form control; its type decides what it looks like.
<label for="t0">Taster session</label><label f...	Text label for a control; for matches the control's id, or the label wraps the control.
	Generic block container for grouping and layout.
<section class="panel" id="p0"><h2>Taster session</h2><p>Two hours ...	A thematic group of content, normally with its own heading.

Line	What it does
<section class="panel" id="p1"><h2>Beginner course</h2><p>Five sess...	Second-level heading for a section.
<section class="panel" id="p2"><h2>Racing clinic</h2><p>Tactics and...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
opacity: 0;	Transparency from 0 (invisible) to 1 (solid).
pointer-events: none;	The element ignores mouse clicks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
border-bottom: 2px solid var(--line);	A bottom border used as a separator line.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border-bottom: 3px solid transparent;	The line around the element: width, style and colour.
.tabs > input:focus-visible + .tablist label {	Applies when the element is focused by keyboard; keeps focus rings visible.
display: none;	Removes the element from rendering completely.
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist labe...	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
font-weight: 600;	Thickness of the text.
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~...	General sibling combinator: later siblings of the matched element.
display: block;	Element starts on a new line and fills the width (used on links and images).

Check your work

- Arrow keys switch tabs (radio behaviour)
- First tab open by default

- Only one panel visible
- Radios are before the labels and panels in the source

Exercises

1. Add a fourth tab.
2. Add a slide-in animation on the active panel.
3. Rebuild it with buttons and JavaScript plus role=tablist for full accessibility.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 666: CSS-only tabs for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 3 | Files: index.html, styles.css

Brief

Build a tabbed interface without JavaScript using hidden radio buttons, labels as tabs and the :checked ~ sibling selector to show panels.

Learning goals

- Use the :checked pseudo-class with the general sibling combinator
- Style labels as tabs
- Understand the limits of CSS-only widgets

Elements and CSS used

HTML elements	CSS features
input type=radio, label, div, section, h2, p	:checked, ~ combinator, attribute selector, display: none/block, opacity: 0 hiding

Build guide

1. Put three radio inputs with the same name first inside .tabs.
2. Add a .tablist of labels pointing at the radios.
3. Add three panels.
4. Hide the radios visually but keep them focusable.
5. Show the panel matching the checked radio with :checked ~ .panels #pN.

6. Highlight the active label the same way.

Project 666: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - Compare</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="tabs">
    <input type="radio" name="tab" id="t0" checked>
    <input type="radio" name="tab" id="t1">
    <input type="radio" name="tab" id="t2">
    <div class="tablist"><label for="t0">Lotus pendant</label><label
for="t1">Brass cuff</label><label for="t2">Bead earrings</label></div>
    <div class="panels">
      <section class="panel" id="p0"><h2>Lotus pendant</
h2><p>Sterling silver. Price: 650 EGP.</p></section>
      <section class="panel" id="p1"><h2>Brass cuff</h2><p>Hand
engraved. Price: 420 EGP.</p></section>
      <section class="panel" id="p2"><h2>Bead earrings</
h2><p>Recycled glass. Price: 180 EGP.</p></section>
    </div>
  </main>
</body>
</html>
```

Project 666: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.tabs { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.tabs > input { position: absolute; opacity: 0; pointer-events: none;
}
.tablist { display: flex; border-bottom: 2px solid var(--line); }
.tablist label { padding: .7rem 1rem; cursor: pointer; color: var(--
muted); border-bottom: 3px solid transparent; margin-bottom: -2px; }
.tabs > input:focus-visible + .tablist label { outline: 2px solid var(
--brand); }
.panel { display: none; padding: 1.25rem 0; }
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist label[
for="t1"], #t2:checked ~ .tablist label[for="t2"] { color: var(--
brand); border-color: var(--brand); font-weight: 600; }
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~ .
```

```
panels #p2 { display: block; }
```

Project 666 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - Compare</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="tabs">	The unique content of this page; exactly one per page.
<input type="radio" name="tab" id="t0" checked>	Radio button: one choice from a group sharing the same name.
<input type="radio" name="tab" id="t1">	A form control; its type decides what it looks like.
<label for="t0">Lotus pendant</label><label fo...	Text label for a control; for matches the control's id, or the label wraps the control.
	Generic block container for grouping and layout.
<section class="panel" id="p0"><h2>Lotus pendant</h2><p>Sterling si...	A thematic group of content, normally with its own heading.

Line	What it does
<section class="panel" id="p1"><h2>Brass cuff</h2><p>Hand engraved....	Second-level heading for a section.
<section class="panel" id="p2"><h2>Bead earrings</h2><p>Recycled gl...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
opacity: 0;	Transparency from 0 (invisible) to 1 (solid).
pointer-events: none;	The element ignores mouse clicks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
border-bottom: 2px solid var(--line);	A bottom border used as a separator line.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border-bottom: 3px solid transparent;	The line around the element: width, style and colour.
.tabs > input:focus-visible + .tablist label {	Applies when the element is focused by keyboard; keeps focus rings visible.
display: none;	Removes the element from rendering completely.
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist labe...	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
font-weight: 600;	Thickness of the text.
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~...	General sibling combinator: later siblings of the matched element.
display: block;	Element starts on a new line and fills the width (used on links and images).

Check your work

- Arrow keys switch tabs (radio behaviour)
- First tab open by default

- Only one panel visible
- Radios are before the labels and panels in the source

Exercises

1. Add a fourth tab.
2. Add a slide-in animation on the active panel.
3. Rebuild it with buttons and JavaScript plus role=tablist for full accessibility.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 667: CSS-only tabs for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 3 | Files: index.html, styles.css

Brief

Build a tabbed interface without JavaScript using hidden radio buttons, labels as tabs and the :checked ~ sibling selector to show panels.

Learning goals

- Use the :checked pseudo-class with the general sibling combinator
- Style labels as tabs
- Understand the limits of CSS-only widgets

Elements and CSS used

HTML elements	CSS features
input type=radio, label, div, section, h2, p	:checked, ~ combinator, attribute selector, display: none/block, opacity: 0 hiding

Build guide

1. Put three radio inputs with the same name first inside .tabs.
2. Add a .tablist of labels pointing at the radios.
3. Add three panels.
4. Hide the radios visually but keep them focusable.
5. Show the panel matching the checked radio with :checked ~ .panels #pN.

6. Highlight the active label the same way.

Project 667: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - Compare</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="tabs">
    <input type="radio" name="tab" id="t0" checked>
    <input type="radio" name="tab" id="t1">
    <input type="radio" name="tab" id="t2">
    <div class="tablist"><label for="t0">Intro to the wheel</
label><label for="t1">Glazing day</label><label for="t2">Kids clay
class</label></div>
    <div class="panels">
      <section class="panel" id="p0"><h2>Intro to the wheel</
h2><p>Three hours, take home a bowl. Price: 450 EGP.</p></section>
      <section class="panel" id="p1"><h2>Glazing day</h2><p>Colour
your pieces. Price: 300 EGP.</p></section>
      <section class="panel" id="p2"><h2>Kids clay class</h2><p>Ages
6 to 12. Price: 200 EGP.</p></section>
    </div>
  </main>
</body>
</html>
```

Project 667: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.tabs { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.tabs > input { position: absolute; opacity: 0; pointer-events: none;
}
.tablist { display: flex; border-bottom: 2px solid var(--line); }
.tablist label { padding: .7rem 1rem; cursor: pointer; color: var(--
muted); border-bottom: 3px solid transparent; margin-bottom: -2px; }
.tabs > input:focus-visible + .tablist label { outline: 2px solid var(
--brand); }
.panel { display: none; padding: 1.25rem 0; }
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist label[
for="t1"], #t2:checked ~ .tablist label[for="t2"] { color: var(--
brand); border-color: var(--brand); font-weight: 600; }
```

```
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~ .
panels #p2 { display: block; }
```

Project 667 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - Compare</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="tabs">	The unique content of this page; exactly one per page.
<input type="radio" name="tab" id="t0" checked>	Radio button: one choice from a group sharing the same name.
<input type="radio" name="tab" id="t1">	A form control; its type decides what it looks like.
<label for="t0">Intro to the wheel</label><lab...	Text label for a control; for matches the control's id, or the label wraps the control.
	Generic block container for grouping and layout.
<section class="panel" id="p0"><h2>Intro to the wheel</h2><p>Three ...	A thematic group of content, normally with its own heading.

Line	What it does
<section class="panel" id="p1"><h2>Glazing day</h2><p>Colour your p...	Second-level heading for a section.
<section class="panel" id="p2"><h2>Kids clay class</h2><p>Ages 6 to...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
opacity: 0;	Transparency from 0 (invisible) to 1 (solid).
pointer-events: none;	The element ignores mouse clicks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
border-bottom: 2px solid var(--line);	A bottom border used as a separator line.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border-bottom: 3px solid transparent;	The line around the element: width, style and colour.
.tabs > input:focus-visible + .tablist label {	Applies when the element is focused by keyboard; keeps focus rings visible.
display: none;	Removes the element from rendering completely.
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist labe...	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
font-weight: 600;	Thickness of the text.
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~...	General sibling combinator: later siblings of the matched element.
display: block;	Element starts on a new line and fills the width (used on links and images).

Check your work

- Arrow keys switch tabs (radio behaviour)
- First tab open by default

- Only one panel visible
- Radios are before the labels and panels in the source

Exercises

1. Add a fourth tab.
2. Add a slide-in animation on the active panel.
3. Rebuild it with buttons and JavaScript plus role=tablist for full accessibility.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 668: CSS-only tabs for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 3 | Files: index.html, styles.css

Brief

Build a tabbed interface without JavaScript using hidden radio buttons, labels as tabs and the :checked ~ sibling selector to show panels.

Learning goals

- Use the :checked pseudo-class with the general sibling combinator
- Style labels as tabs
- Understand the limits of CSS-only widgets

Elements and CSS used

HTML elements	CSS features
input type=radio, label, div, section, h2, p	:checked, ~ combinator, attribute selector, display: none/block, opacity: 0 hiding

Build guide

1. Put three radio inputs with the same name first inside .tabs.
2. Add a .tablist of labels pointing at the radios.
3. Add three panels.
4. Hide the radios visually but keep them focusable.
5. Show the panel matching the checked radio with :checked ~ .panels #pN.

6. Highlight the active label the same way.

Project 668: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - Compare</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="tabs">
    <input type="radio" name="tab" id="t0" checked>
    <input type="radio" name="tab" id="t1">
    <input type="radio" name="tab" id="t2">
    <div class="tablist"><label for="t0">Haircut and blow-dry</
label><label for="t1">Manicure</label><label for="t2">Facial</label></
div>
    <div class="panels">
      <section class="panel" id="p0"><h2>Haircut and blow-dry</
h2><p>Consultation included. Price: 350 EGP.</p></section>
      <section class="panel" id="p1"><h2>Manicure</h2><p>Classic or
gel. Price: 200 EGP.</p></section>
      <section class="panel" id="p2"><h2>Facial</h2><p>Deep cleanse,
60 minutes. Price: 600 EGP.</p></section>
    </div>
  </main>
</body>
</html>
```

Project 668: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.tabs { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.tabs > input { position: absolute; opacity: 0; pointer-events: none;
}
.tablist { display: flex; border-bottom: 2px solid var(--line); }
.tablist label { padding: .7rem 1rem; cursor: pointer; color: var(--
muted); border-bottom: 3px solid transparent; margin-bottom: -2px; }
.tabs > input:focus-visible + .tablist label { outline: 2px solid var(
--brand); }
.panel { display: none; padding: 1.25rem 0; }
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist label[
for="t1"], #t2:checked ~ .tablist label[for="t2"] { color: var(--
brand); border-color: var(--brand); font-weight: 600; }
```

```
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~ .
panels #p2 { display: block; }
```

Project 668 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - Compare</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="tabs">	The unique content of this page; exactly one per page.
<input type="radio" name="tab" id="t0" checked>	Radio button: one choice from a group sharing the same name.
<input type="radio" name="tab" id="t1">	A form control; its type decides what it looks like.
<label for="t0">Haircut and blow-dry</label><l...	Text label for a control; for matches the control's id, or the label wraps the control.
	Generic block container for grouping and layout.
<section class="panel" id="p0"><h2>Haircut and blow-dry</h2><p>Cons...	A thematic group of content, normally with its own heading.

Line	What it does
<section class="panel" id="p1"><h2>Manicure</h2><p>Classic or gel. ...	Second-level heading for a section.
<section class="panel" id="p2"><h2>Facial</h2><p>Deep cleanse, 60 m...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
opacity: 0;	Transparency from 0 (invisible) to 1 (solid).
pointer-events: none;	The element ignores mouse clicks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
border-bottom: 2px solid var(--line);	A bottom border used as a separator line.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border-bottom: 3px solid transparent;	The line around the element: width, style and colour.
.tabs > input:focus-visible + .tablist label {	Applies when the element is focused by keyboard; keeps focus rings visible.
display: none;	Removes the element from rendering completely.
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist labe...	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
font-weight: 600;	Thickness of the text.
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~...	General sibling combinator: later siblings of the matched element.
display: block;	Element starts on a new line and fills the width (used on links and images).

Check your work

- Arrow keys switch tabs (radio behaviour)
- First tab open by default

- Only one panel visible
- Radios are before the labels and panels in the source

Exercises

1. Add a fourth tab.
2. Add a slide-in animation on the active panel.
3. Rebuild it with buttons and JavaScript plus role=tablist for full accessibility.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 669: CSS-only tabs for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 3 | Files: index.html, styles.css

Brief

Build a tabbed interface without JavaScript using hidden radio buttons, labels as tabs and the :checked ~ sibling selector to show panels.

Learning goals

- Use the :checked pseudo-class with the general sibling combinator
- Style labels as tabs
- Understand the limits of CSS-only widgets

Elements and CSS used

HTML elements	CSS features
input type=radio, label, div, section, h2, p	:checked, ~ combinator, attribute selector, display: none/block, opacity: 0 hiding

Build guide

1. Put three radio inputs with the same name first inside .tabs.
2. Add a .tablist of labels pointing at the radios.
3. Add three panels.
4. Hide the radios visually but keep them focusable.
5. Show the panel matching the checked radio with :checked ~ .panels #pN.
6. Highlight the active label the same way.

Project 669: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - Compare</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="tabs">
    <input type="radio" name="tab" id="t0" checked>
    <input type="radio" name="tab" id="t1">
    <input type="radio" name="tab" id="t2">
    <div class="tablist"><label for="t0">Oil change</label><label
for="t1">Brake pads</label><label for="t2">Air conditioning</label></
div>
    <div class="panels">
      <section class="panel" id="p0"><h2>Oil change</h2><p>Filter
included. Price: 600 EGP.</p></section>
      <section class="panel" id="p1"><h2>Brake pads</h2><p>Front axle.
 Price: 1400 EGP.</p></section>
      <section class="panel" id="p2"><h2>Air conditioning</
h2><p>Recharge and check. Price: 900 EGP.</p></section>
    </div>
  </main>
</body>
</html>
```

Project 669: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.tabs { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.tabs > input { position: absolute; opacity: 0; pointer-events: none;
}
.tablist { display: flex; border-bottom: 2px solid var(--line); }
.tablist label { padding: .7rem 1rem; cursor: pointer; color: var(--
muted); border-bottom: 3px solid transparent; margin-bottom: -2px; }
.tabs > input:focus-visible + .tablist label { outline: 2px solid var(
--brand); }
.panel { display: none; padding: 1.25rem 0; }
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist label[
for="t1"], #t2:checked ~ .tablist label[for="t2"] { color: var(--
brand); border-color: var(--brand); font-weight: 600; }
```

```
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~ .
panels #p2 { display: block; }
```

Project 669 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - Compare</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="tabs">	The unique content of this page; exactly one per page.
<input type="radio" name="tab" id="t0" checked>	Radio button: one choice from a group sharing the same name.
<input type="radio" name="tab" id="t1">	A form control; its type decides what it looks like.
<label for="t0">Oil change</label><label for="...	Text label for a control; for matches the control's id, or the label wraps the control.
	Generic block container for grouping and layout.
<section class="panel" id="p0"><h2>Oil change</h2><p>Filter include...	A thematic group of content, normally with its own heading.

Line	What it does
<section class="panel" id="p1"><h2>Brake pads</h2><p>Front axle. Pr...	Second-level heading for a section.
<section class="panel" id="p2"><h2>Air conditioning</h2><p>Recharge...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
opacity: 0;	Transparency from 0 (invisible) to 1 (solid).
pointer-events: none;	The element ignores mouse clicks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
border-bottom: 2px solid var(--line);	A bottom border used as a separator line.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border-bottom: 3px solid transparent;	The line around the element: width, style and colour.
.tabs > input:focus-visible + .tablist label {	Applies when the element is focused by keyboard; keeps focus rings visible.
display: none;	Removes the element from rendering completely.
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist labe...	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
font-weight: 600;	Thickness of the text.
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~...	General sibling combinator: later siblings of the matched element.
display: block;	Element starts on a new line and fills the width (used on links and images).

Check your work

- Arrow keys switch tabs (radio behaviour)
- First tab open by default

- Only one panel visible
- Radios are before the labels and panels in the source

Exercises

1. Add a fourth tab.
2. Add a slide-in animation on the active panel.
3. Rebuild it with buttons and JavaScript plus role=tablist for full accessibility.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 670: CSS-only tabs for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 3 | Files: index.html, styles.css

Brief

Build a tabbed interface without JavaScript using hidden radio buttons, labels as tabs and the :checked ~ sibling selector to show panels.

Learning goals

- Use the :checked pseudo-class with the general sibling combinator
- Style labels as tabs
- Understand the limits of CSS-only widgets

Elements and CSS used

HTML elements	CSS features
input type=radio, label, div, section, h2, p	:checked, ~ combinator, attribute selector, display: none/block, opacity: 0 hiding

Build guide

1. Put three radio inputs with the same name first inside .tabs.
2. Add a .tablist of labels pointing at the radios.
3. Add three panels.
4. Hide the radios visually but keep them focusable.
5. Show the panel matching the checked radio with :checked ~ .panels #pN.
6. Highlight the active label the same way.

Project 670: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - Compare</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="tabs">
    <input type="radio" name="tab" id="t0" checked>
    <input type="radio" name="tab" id="t1">
    <input type="radio" name="tab" id="t2">
    <div class="tablist"><label for="t0">Oud for beginners</
label><label for="t1">Piano grade 1</label><label for="t2">Guitar
chords</label></div>
    <div class="panels">
      <section class="panel" id="p0"><h2>Oud for beginners</
h2><p>Eight weekly lessons. Price: 1600 EGP.</p></section>
      <section class="panel" id="p1"><h2>Piano grade 1</h2><p>Theory
and practice. Price: 1800 EGP.</p></section>
      <section class="panel" id="p2"><h2>Guitar chords</h2><p>Play
songs in a month. Price: 1400 EGP.</p></section>
    </div>
  </main>
</body>
</html>
```

Project 670: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.tabs { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.tabs > input { position: absolute; opacity: 0; pointer-events: none;
}
.tablist { display: flex; border-bottom: 2px solid var(--line); }
.tablist label { padding: .7rem 1rem; cursor: pointer; color: var(--
muted); border-bottom: 3px solid transparent; margin-bottom: -2px; }
.tabs > input:focus-visible + .tablist label { outline: 2px solid var(
--brand); }
.panel { display: none; padding: 1.25rem 0; }
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist label[
for="t1"], #t2:checked ~ .tablist label[for="t2"] { color: var(--
brand); border-color: var(--brand); font-weight: 600; }
```

```
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~ .
panels #p2 { display: block; }
```

Project 670 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - Compare</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="tabs">	The unique content of this page; exactly one per page.
<input type="radio" name="tab" id="t0" checked>	Radio button: one choice from a group sharing the same name.
<input type="radio" name="tab" id="t1">	A form control; its type decides what it looks like.
<label for="t0">Oud for beginners</label><labe...	Text label for a control; for matches the control's id, or the label wraps the control.
	Generic block container for grouping and layout.
<section class="panel" id="p0"><h2>Oud for beginners</h2><p>Eight w...	A thematic group of content, normally with its own heading.

Line	What it does
<section class="panel" id="p1"><h2>Piano grade 1</h2><p>Theory and ...	Second-level heading for a section.
<section class="panel" id="p2"><h2>Guitar chords</h2><p>Play songs ...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
opacity: 0;	Transparency from 0 (invisible) to 1 (solid).
pointer-events: none;	The element ignores mouse clicks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
border-bottom: 2px solid var(--line);	A bottom border used as a separator line.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border-bottom: 3px solid transparent;	The line around the element: width, style and colour.
.tabs > input:focus-visible + .tablist label {	Applies when the element is focused by keyboard; keeps focus rings visible.
display: none;	Removes the element from rendering completely.
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist labe...	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
font-weight: 600;	Thickness of the text.
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~...	General sibling combinator: later siblings of the matched element.
display: block;	Element starts on a new line and fills the width (used on links and images).

Check your work

- Arrow keys switch tabs (radio behaviour)
- First tab open by default

- Only one panel visible
- Radios are before the labels and panels in the source

Exercises

1. Add a fourth tab.
2. Add a slide-in animation on the active panel.
3. Rebuild it with buttons and JavaScript plus role=tablist for full accessibility.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 671: CSS-only tabs for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 3 | Files: index.html, styles.css

Brief

Build a tabbed interface without JavaScript using hidden radio buttons, labels as tabs and the :checked ~ sibling selector to show panels.

Learning goals

- Use the :checked pseudo-class with the general sibling combinator
- Style labels as tabs
- Understand the limits of CSS-only widgets

Elements and CSS used

HTML elements	CSS features
input type=radio, label, div, section, h2, p	:checked, ~ combinator, attribute selector, display: none/block, opacity: 0 hiding

Build guide

1. Put three radio inputs with the same name first inside .tabs.
2. Add a .tablist of labels pointing at the radios.
3. Add three panels.
4. Hide the radios visually but keep them focusable.
5. Show the panel matching the checked radio with :checked ~ .panels #pN.
6. Highlight the active label the same way.

Project 671: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - Compare</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="tabs">
    <input type="radio" name="tab" id="t0" checked>
    <input type="radio" name="tab" id="t1">
    <input type="radio" name="tab" id="t2">
    <div class="tablist"><label for="t0">Grilled sea bass</
label><label for="t1">Shrimp tagine</label><label for="t2">Calamari</
label></div>
    <div class="panels">
      <section class="panel" id="p0"><h2>Grilled sea bass</h2><p>With
rice and salad. Price: 320 EGP.</p></section>
      <section class="panel" id="p1"><h2>Shrimp tagine</h2><p>Tomato
and garlic. Price: 280 EGP.</p></section>
      <section class="panel" id="p2"><h2>Calamari</h2><p>Fried, with
tahini. Price: 190 EGP.</p></section>
    </div>
  </main>
</body>
</html>
```

Project 671: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.tabs { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.tabs > input { position: absolute; opacity: 0; pointer-events: none;
}
.tablist { display: flex; border-bottom: 2px solid var(--line); }
.tablist label { padding: .7rem 1rem; cursor: pointer; color: var(--
muted); border-bottom: 3px solid transparent; margin-bottom: -2px; }
.tabs > input:focus-visible + .tablist label { outline: 2px solid var(
--brand); }
.panel { display: none; padding: 1.25rem 0; }
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist label[
for="t1"], #t2:checked ~ .tablist label[for="t2"] { color: var(--
brand); border-color: var(--brand); font-weight: 600; }
```

```
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~ .
panels #p2 { display: block; }
```

Project 671 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - Compare</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="tabs">	The unique content of this page; exactly one per page.
<input type="radio" name="tab" id="t0" checked>	Radio button: one choice from a group sharing the same name.
<input type="radio" name="tab" id="t1">	A form control; its type decides what it looks like.
<label for="t0">Grilled sea bass</label><label...	Text label for a control; for matches the control's id, or the label wraps the control.
	Generic block container for grouping and layout.
<section class="panel" id="p0"><h2>Grilled sea bass</h2><p>With ric...	A thematic group of content, normally with its own heading.

Line	What it does
<section class="panel" id="p1"><h2>Shrimp tagine</h2><p>Tomato and ...	Second-level heading for a section.
<section class="panel" id="p2"><h2>Calamari</h2><p>Fried, with tahi...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
opacity: 0;	Transparency from 0 (invisible) to 1 (solid).
pointer-events: none;	The element ignores mouse clicks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
border-bottom: 2px solid var(--line);	A bottom border used as a separator line.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border-bottom: 3px solid transparent;	The line around the element: width, style and colour.
.tabs > input:focus-visible + .tablist label {	Applies when the element is focused by keyboard; keeps focus rings visible.
display: none;	Removes the element from rendering completely.
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist labe...	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
font-weight: 600;	Thickness of the text.
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~...	General sibling combinator: later siblings of the matched element.
display: block;	Element starts on a new line and fills the width (used on links and images).

Check your work

- Arrow keys switch tabs (radio behaviour)
- First tab open by default

- Only one panel visible
- Radios are before the labels and panels in the source

Exercises

1. Add a fourth tab.
2. Add a slide-in animation on the active panel.
3. Rebuild it with buttons and JavaScript plus role=tablist for full accessibility.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 672: CSS-only tabs for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 3 | Files: index.html, styles.css

Brief

Build a tabbed interface without JavaScript using hidden radio buttons, labels as tabs and the :checked ~ sibling selector to show panels.

Learning goals

- Use the :checked pseudo-class with the general sibling combinator
- Style labels as tabs
- Understand the limits of CSS-only widgets

Elements and CSS used

HTML elements	CSS features
input type=radio, label, div, section, h2, p	:checked, ~ combinator, attribute selector, display: none/block, opacity: 0 hiding

Build guide

1. Put three radio inputs with the same name first inside .tabs.
2. Add a .tablist of labels pointing at the radios.
3. Add three panels.
4. Hide the radios visually but keep them focusable.
5. Show the panel matching the checked radio with :checked ~ .panels #pN.
6. Highlight the active label the same way.

Project 672: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - Compare</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="tabs">
    <input type="radio" name="tab" id="t0" checked>
    <input type="radio" name="tab" id="t1">
    <input type="radio" name="tab" id="t2">
    <div class="tablist"><label for="t0">Story hour</label><label
for="t1">Reading club</label><label for="t2">Homework help</label></
div>
    <div class="panels">
      <section class="panel" id="p0"><h2>Story hour</h2><p>Ages 3 to
6, Saturdays. Price: Free.</p></section>
      <section class="panel" id="p1"><h2>Reading club</h2><p>Ages 7
to 11. Price: 50 EGP per month.</p></section>
      <section class="panel" id="p2"><h2>Homework help</h2><p>Weekday
afternoons. Price: Free.</p></section>
    </div>
  </main>
</body>
</html>
```

Project 672: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.tabs { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.tabs > input { position: absolute; opacity: 0; pointer-events: none;
}
.tablist { display: flex; border-bottom: 2px solid var(--line); }
.tablist label { padding: .7rem 1rem; cursor: pointer; color: var(--
muted); border-bottom: 3px solid transparent; margin-bottom: -2px; }
.tabs > input:focus-visible + .tablist label { outline: 2px solid var(
--brand); }
.panel { display: none; padding: 1.25rem 0; }
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist label[
for="t1"], #t2:checked ~ .tablist label[for="t2"] { color: var(--
brand); border-color: var(--brand); font-weight: 600; }
```

```
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~ .
panels #p2 { display: block; }
```

Project 672 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - Compare</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="tabs">	The unique content of this page; exactly one per page.
<input type="radio" name="tab" id="t0" checked>	Radio button: one choice from a group sharing the same name.
<input type="radio" name="tab" id="t1">	A form control; its type decides what it looks like.
<label for="t0">Story hour</label><label for="...	Text label for a control; for matches the control's id, or the label wraps the control.
	Generic block container for grouping and layout.
<section class="panel" id="p0"><h2>Story hour</h2><p>Ages 3 to 6, S...	A thematic group of content, normally with its own heading.

Line	What it does
<section class="panel" id="p1"><h2>Reading club</h2><p>Ages 7 to 11...	Second-level heading for a section.
<section class="panel" id="p2"><h2>Homework help</h2><p>Weekday aft...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
opacity: 0;	Transparency from 0 (invisible) to 1 (solid).
pointer-events: none;	The element ignores mouse clicks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
border-bottom: 2px solid var(--line);	A bottom border used as a separator line.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border-bottom: 3px solid transparent;	The line around the element: width, style and colour.
.tabs > input:focus-visible + .tablist label {	Applies when the element is focused by keyboard; keeps focus rings visible.
display: none;	Removes the element from rendering completely.
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist labe...	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
font-weight: 600;	Thickness of the text.
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~...	General sibling combinator: later siblings of the matched element.
display: block;	Element starts on a new line and fills the width (used on links and images).

Check your work

- Arrow keys switch tabs (radio behaviour)
- First tab open by default

- Only one panel visible
- Radios are before the labels and panels in the source

Exercises

1. Add a fourth tab.
2. Add a slide-in animation on the active panel.
3. Rebuild it with buttons and JavaScript plus role=tablist for full accessibility.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 673: CSS-only tabs for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 3 | Files: index.html, styles.css

Brief

Build a tabbed interface without JavaScript using hidden radio buttons, labels as tabs and the :checked ~ sibling selector to show panels.

Learning goals

- Use the :checked pseudo-class with the general sibling combinator
- Style labels as tabs
- Understand the limits of CSS-only widgets

Elements and CSS used

HTML elements	CSS features
input type=radio, label, div, section, h2, p	:checked, ~ combinator, attribute selector, display: none/block, opacity: 0 hiding

Build guide

1. Put three radio inputs with the same name first inside .tabs.
2. Add a .tablist of labels pointing at the radios.
3. Add three panels.
4. Hide the radios visually but keep them focusable.
5. Show the panel matching the checked radio with :checked ~ .panels #pN.
6. Highlight the active label the same way.

Project 673: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - Compare</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="tabs">
    <input type="radio" name="tab" id="t0" checked>
    <input type="radio" name="tab" id="t1">
    <input type="radio" name="tab" id="t2">
    <div class="tablist"><label for="t0">Garden room</label><label
for="t1">Nile view suite</label><label for="t2">Family room</label></
div>
    <div class="panels">
      <section class="panel" id="p0"><h2>Garden room</h2><p>Double
bed, shared terrace. Price: 900 EGP.</p></section>
      <section class="panel" id="p1"><h2>Nile view suite</
h2><p>Balcony and breakfast. Price: 1800 EGP.</p></section>
      <section class="panel" id="p2"><h2>Family room</h2><p>Sleeps
four. Price: 1500 EGP.</p></section>
    </div>
  </main>
</body>
</html>
```

Project 673: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.tabs { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.tabs > input { position: absolute; opacity: 0; pointer-events: none;
}
.tablist { display: flex; border-bottom: 2px solid var(--line); }
.tablist label { padding: .7rem 1rem; cursor: pointer; color: var(--
muted); border-bottom: 3px solid transparent; margin-bottom: -2px; }
.tabs > input:focus-visible + .tablist label { outline: 2px solid var(
--brand); }
.panel { display: none; padding: 1.25rem 0; }
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist label[
for="t1"], #t2:checked ~ .tablist label[for="t2"] { color: var(--
brand); border-color: var(--brand); font-weight: 600; }
```

```
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~ .
panels #p2 { display: block; }
```

Project 673 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - Compare</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="tabs">	The unique content of this page; exactly one per page.
<input type="radio" name="tab" id="t0" checked>	Radio button: one choice from a group sharing the same name.
<input type="radio" name="tab" id="t1">	A form control; its type decides what it looks like.
<label for="t0">Garden room</label><label for=...	Text label for a control; for matches the control's id, or the label wraps the control.
	Generic block container for grouping and layout.
<section class="panel" id="p0"><h2>Garden room</h2><p>Double bed, s...	A thematic group of content, normally with its own heading.

Line	What it does
<section class="panel" id="p1"><h2>Nile view suite</h2><p>Balcony a...	Second-level heading for a section.
<section class="panel" id="p2"><h2>Family room</h2><p>Sleeps four. ...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
opacity: 0;	Transparency from 0 (invisible) to 1 (solid).
pointer-events: none;	The element ignores mouse clicks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
border-bottom: 2px solid var(--line);	A bottom border used as a separator line.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border-bottom: 3px solid transparent;	The line around the element: width, style and colour.
.tabs > input:focus-visible + .tablist label {	Applies when the element is focused by keyboard; keeps focus rings visible.
display: none;	Removes the element from rendering completely.
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist labe...	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
font-weight: 600;	Thickness of the text.
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~...	General sibling combinator: later siblings of the matched element.
display: block;	Element starts on a new line and fills the width (used on links and images).

Check your work

- Arrow keys switch tabs (radio behaviour)
- First tab open by default

- Only one panel visible
- Radios are before the labels and panels in the source

Exercises

1. Add a fourth tab.
2. Add a slide-in animation on the active panel.
3. Rebuild it with buttons and JavaScript plus role=tablist for full accessibility.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 674: CSS-only tabs for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 3 | Files: index.html, styles.css

Brief

Build a tabbed interface without JavaScript using hidden radio buttons, labels as tabs and the :checked ~ sibling selector to show panels.

Learning goals

- Use the :checked pseudo-class with the general sibling combinator
- Style labels as tabs
- Understand the limits of CSS-only widgets

Elements and CSS used

HTML elements	CSS features
input type=radio, label, div, section, h2, p	:checked, ~ combinator, attribute selector, display: none/block, opacity: 0 hiding

Build guide

1. Put three radio inputs with the same name first inside .tabs.
2. Add a .tablist of labels pointing at the radios.
3. Add three panels.
4. Hide the radios visually but keep them focusable.
5. Show the panel matching the checked radio with :checked ~ .panels #pN.

6. Highlight the active label the same way.

Project 674: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - Compare</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="tabs">
    <input type="radio" name="tab" id="t0" checked>
    <input type="radio" name="tab" id="t1">
    <input type="radio" name="tab" id="t2">
    <div class="tablist"><label for="t0">City bike</label><label
for="t1">Mountain bike</label><label for="t2">Kids bike</label></div>
    <div class="panels">
      <section class="panel" id="p0"><h2>City bike</h2><p>Seven gears,
 basket. Price: 6500 EGP.</p></section>
      <section class="panel" id="p1"><h2>Mountain bike</h2><p>Front
suspension. Price: 11000 EGP.</p></section>
      <section class="panel" id="p2"><h2>Kids bike</h2><p>20 inch
wheels. Price: 3200 EGP.</p></section>
    </div>
  </main>
</body>
</html>
```

Project 674: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.tabs { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.tabs > input { position: absolute; opacity: 0; pointer-events: none;
}
.tablist { display: flex; border-bottom: 2px solid var(--line); }
.tablist label { padding: .7rem 1rem; cursor: pointer; color: var(--
muted); border-bottom: 3px solid transparent; margin-bottom: -2px; }
.tabs > input:focus-visible + .tablist label { outline: 2px solid var(
--brand); }
.panel { display: none; padding: 1.25rem 0; }
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist label[
for="t1"], #t2:checked ~ .tablist label[for="t2"] { color: var(--
brand); border-color: var(--brand); font-weight: 600; }
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~ .
```

```
panels #p2 { display: block; }
```

Project 674 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - Compare</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="tabs">	The unique content of this page; exactly one per page.
<input type="radio" name="tab" id="t0" checked>	Radio button: one choice from a group sharing the same name.
<input type="radio" name="tab" id="t1">	A form control; its type decides what it looks like.
<label for="t0">City bike</label><label for="t...	Text label for a control; for matches the control's id, or the label wraps the control.
	Generic block container for grouping and layout.
<section class="panel" id="p0"><h2>City bike</h2><p>Seven gears, ba...	A thematic group of content, normally with its own heading.

Line	What it does
<section class="panel" id="p1"><h2>Mountain bike</h2><p>Front suspe...	Second-level heading for a section.
<section class="panel" id="p2"><h2>Kids bike</h2><p>20 inch wheels....	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
opacity: 0;	Transparency from 0 (invisible) to 1 (solid).
pointer-events: none;	The element ignores mouse clicks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
border-bottom: 2px solid var(--line);	A bottom border used as a separator line.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border-bottom: 3px solid transparent;	The line around the element: width, style and colour.
.tabs > input:focus-visible + .tablist label {	Applies when the element is focused by keyboard; keeps focus rings visible.
display: none;	Removes the element from rendering completely.
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist labe...	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
font-weight: 600;	Thickness of the text.
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~...	General sibling combinator: later siblings of the matched element.
display: block;	Element starts on a new line and fills the width (used on links and images).

Check your work

- Arrow keys switch tabs (radio behaviour)
- First tab open by default

- Only one panel visible
- Radios are before the labels and panels in the source

Exercises

1. Add a fourth tab.
2. Add a slide-in animation on the active panel.
3. Rebuild it with buttons and JavaScript plus role=tablist for full accessibility.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 675: CSS-only tabs for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 3 | Files: index.html, styles.css

Brief

Build a tabbed interface without JavaScript using hidden radio buttons, labels as tabs and the :checked ~ sibling selector to show panels.

Learning goals

- Use the :checked pseudo-class with the general sibling combinator
- Style labels as tabs
- Understand the limits of CSS-only widgets

Elements and CSS used

HTML elements	CSS features
input type=radio, label, div, section, h2, p	:checked, ~ combinator, attribute selector, display: none/block, opacity: 0 hiding

Build guide

1. Put three radio inputs with the same name first inside .tabs.
2. Add a .tablist of labels pointing at the radios.
3. Add three panels.
4. Hide the radios visually but keep them focusable.
5. Show the panel matching the checked radio with :checked ~ .panels #pN.
6. Highlight the active label the same way.

Project 675: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - Compare</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="tabs">
    <input type="radio" name="tab" id="t0" checked>
    <input type="radio" name="tab" id="t1">
    <input type="radio" name="tab" id="t2">
    <div class="tablist"><label for="t0">HTML weekend</label><label
for="t1">CSS art</label><label for="t2">Scratch games</label></div>
    <div class="panels">
      <section class="panel" id="p0"><h2>HTML weekend</h2><p>Build
your first page. Price: Free.</p></section>
      <section class="panel" id="p1"><h2>CSS art</h2><p>Draw with
code. Price: Free.</p></section>
      <section class="panel" id="p2"><h2>Scratch games</h2><p>Ages 10
to 13. Price: Free.</p></section>
    </div>
  </main>
</body>
</html>
```

Project 675: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.tabs { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.tabs > input { position: absolute; opacity: 0; pointer-events: none;
}
.tablist { display: flex; border-bottom: 2px solid var(--line); }
.tablist label { padding: .7rem 1rem; cursor: pointer; color: var(--
muted); border-bottom: 3px solid transparent; margin-bottom: -2px; }
.tabs > input:focus-visible + .tablist label { outline: 2px solid var(
--brand); }
.panel { display: none; padding: 1.25rem 0; }
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist label[
for="t1"], #t2:checked ~ .tablist label[for="t2"] { color: var(--
brand); border-color: var(--brand); font-weight: 600; }
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~ .
```

```
panels #p2 { display: block; }
```

Project 675 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - Compare</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="tabs">	The unique content of this page; exactly one per page.
<input type="radio" name="tab" id="t0" checked>	Radio button: one choice from a group sharing the same name.
<input type="radio" name="tab" id="t1">	A form control; its type decides what it looks like.
<label for="t0">HTML weekend</label><label for...	Text label for a control; for matches the control's id, or the label wraps the control.
	Generic block container for grouping and layout.
<section class="panel" id="p0"><h2>HTML weekend</h2><p>Build your f...	A thematic group of content, normally with its own heading.

Line	What it does
<section class="panel" id="p1"><h2>CSS art</h2><p>Draw with code. P...	Second-level heading for a section.
<section class="panel" id="p2"><h2>Scratch games</h2><p>Ages 10 to ...	A paragraph of text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
opacity: 0;	Transparency from 0 (invisible) to 1 (solid).
pointer-events: none;	The element ignores mouse clicks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
border-bottom: 2px solid var(--line);	A bottom border used as a separator line.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border-bottom: 3px solid transparent;	The line around the element: width, style and colour.
.tabs > input:focus-visible + .tablist label {	Applies when the element is focused by keyboard; keeps focus rings visible.
display: none;	Removes the element from rendering completely.
#t0:checked ~ .tablist label[for="t0"], #t1:checked ~ .tablist labe...	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
font-weight: 600;	Thickness of the text.
#t0:checked ~ .panels #p0, #t1:checked ~ .panels #p1, #t2:checked ~...	General sibling combinator: later siblings of the matched element.
display: block;	Element starts on a new line and fills the width (used on links and images).

Check your work

- Arrow keys switch tabs (radio behaviour)
- First tab open by default

- Only one panel visible
- Radios are before the labels and panels in the source

Exercises

1. Add a fourth tab.
2. Add a slide-in animation on the active panel.
3. Rebuild it with buttons and JavaScript plus role=tablist for full accessibility.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Modal dialog

Level 3 | 25 projects, one per theme

Show a promotional pop-up using the native dialog element, opened with two lines of JavaScript, closed by a form with method=dialog, with a blurred backdrop.

Project 676: Modal dialog for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 3 | Files: index.html, styles.css

Brief

Show a promotional pop-up using the native dialog element, opened with two lines of JavaScript, closed by a form with method=dialog, with a blurred backdrop.

Learning goals

- Use <dialog> and showModal()
- Close a dialog with method="dialog"
- Style ::backdrop

Elements and CSS used

HTML elements	CSS features
button, dialog, form method=dialog, h2, p, strong, script	::backdrop, backdrop-filter, box-shadow, border-radius

Build guide

1. Write the page with an open button and a <dialog>.
2. Inside the dialog, wrap the content in <form method="dialog"> with a close button.
3. Add the script that calls showModal() on click.
4. Remove the default border and round the dialog.
5. Style ::backdrop.
6. Test: Escape closes it; focus is trapped inside.

Project 676: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Offer</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cairo Book Shop</h1>
    <p>PDF and printed books about web development.</p>
    <button type="button" id="open">See this week's offer</button>
    <dialog id="offer">
      <form method="dialog">
        <h2>This week only</h2>
        <p><strong>Learn HTML</strong> for 120 EGP: 20 percent off
with the code WEB20.</p>
        <button value="close">Close</button>
      </form>
    </dialog>
  </main>
  <script>
    const dlg = document.getElementById('offer');
    document.getElementById('open').addEventListener('click', () =>
dlg.showModal());
  </script>
</body>
</html>
```

Project 676: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 3rem auto; padding: 0 1rem; }
button { padding: .7rem 1.3rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
dialog { border: 0; border-radius: 16px; padding: 2rem; max-width:
26rem; box-shadow: 0 20px 60px rgb(0 0 0 / 30%); }
dialog::backdrop { background: rgb(0 0 0 / 50%); backdrop-filter:
blur(2px); }
dialog h2 { margin-top: 0; color: var(--brand); }
```

Project 676 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - Offer</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cairo Book Shop	The main heading; only one per page.
PDF and printed books about web development.	A paragraph of text.
<button type="button" id="open">See this week's offer</button>	A clickable button; inside a form it submits by default.
<dialog id="offer">	A dialog box; showModal() opens it as a modal.
<form method="dialog">	A form; action is where the data goes, method how it is sent.
This week only	Second-level heading for a section.

Line	What it does
<p>Learn HTML for 120 EGP: 20 percent off with the...	Strong importance (bold by default).
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
background: var(--brand);	Background colour or image.
font: inherit;	Makes form controls use the page font instead of the browser default.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 16px;	Rounds the corners.
box-shadow: 0 20px 60px rgb(0 0 0 / 30%);	Soft shadow that lifts the element from the page.
dialog::backdrop {	The dimmed layer behind a modal dialog.
backdrop-filter: blur(2px);	Blurs or filters whatever is behind the element.

Check your work

- Escape key closes
- Focus moves into the dialog
- Background is not clickable
- Close button visible

Exercises

1. Open the dialog automatically after 5 seconds, once per visit (localStorage).
2. Animate the entrance with @starting-style.
3. Add a form inside and read the returnValue.

Theme data for this project

Field	Value
Business	Cairo Book Shop

Field	Value
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 677: Modal dialog for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 3 | Files: index.html, styles.css

Brief

Show a promotional pop-up using the native dialog element, opened with two lines of JavaScript, closed by a form with method=dialog, with a blurred backdrop.

Learning goals

- Use <dialog> and showModal()
- Close a dialog with method="dialog"
- Style ::backdrop

Elements and CSS used

HTML elements	CSS features
button, dialog, form method=dialog, h2, p, strong, script	::backdrop, backdrop-filter, box-shadow, border-radius

Build guide

1. Write the page with an open button and a <dialog>.
2. Inside the dialog, wrap the content in <form method="dialog"> with a close button.
3. Add the script that calls showModal() on click.
4. Remove the default border and round the dialog.
5. Style ::backdrop.
6. Test: Escape closes it; focus is trapped inside.

Project 677: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - Offer</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Nile Bakery</h1>
    <p>Fresh bread and pastries every morning.</p>
    <button type="button" id="open">See this week's offer</button>
    <dialog id="offer">
      <form method="dialog">
        <h2>This week only</h2>
        <p><strong>Sourdough loaf</strong> for 60 EGP: 20 percent off
with the code WEB20.</p>
        <button value="close">Close</button>
      </form>
    </dialog>
  </main>
  <script>
    const dlg = document.getElementById('offer');
    document.getElementById('open').addEventListener('click', () =>
dlg.showModal());
  </script>
</body>
</html>
```

Project 677: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 3rem auto; padding: 0 1rem; }
button { padding: .7rem 1.3rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
dialog { border: 0; border-radius: 16px; padding: 2rem; max-width:
26rem; box-shadow: 0 20px 60px rgb(0 0 0 / 30%); }
dialog::backdrop { background: rgb(0 0 0 / 50%); backdrop-filter:
blur(2px); }
dialog h2 { margin-top: 0; color: var(--brand); }
```

Project 677 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - Offer</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Nile Bakery	The main heading; only one per page.
Fresh bread and pastries every morning.	A paragraph of text.
<button type="button" id="open">See this week's offer</button>	A clickable button; inside a form it submits by default.
<dialog id="offer">	A dialog box; showModal() opens it as a modal.
<form method="dialog">	A form; action is where the data goes, method how it is sent.
This week only	Second-level heading for a section.

Line	What it does
<p>Sourdough loaf for 60 EGP: 20 percent off with ...	Strong importance (bold by default).
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
background: var(--brand);	Background colour or image.
font: inherit;	Makes form controls use the page font instead of the browser default.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 16px;	Rounds the corners.
box-shadow: 0 20px 60px rgb(0 0 0 / 30%);	Soft shadow that lifts the element from the page.
dialog::backdrop {	The dimmed layer behind a modal dialog.
backdrop-filter: blur(2px);	Blurs or filters whatever is behind the element.

Check your work

- Escape key closes
- Focus moves into the dialog
- Background is not clickable
- Close button visible

Exercises

1. Open the dialog automatically after 5 seconds, once per visit (localStorage).
2. Animate the entrance with @starting-style.
3. Add a form inside and read the returnValue.

Theme data for this project

Field	Value
Business	Nile Bakery

Field	Value
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 678: Modal dialog for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 3 | Files: index.html, styles.css

Brief

Show a promotional pop-up using the native dialog element, opened with two lines of JavaScript, closed by a form with method=dialog, with a blurred backdrop.

Learning goals

- Use <dialog> and showModal()
- Close a dialog with method="dialog"
- Style ::backdrop

Elements and CSS used

HTML elements	CSS features
button, dialog, form method=dialog, h2, p, strong, script	::backdrop, backdrop-filter, box-shadow, border-radius

Build guide

1. Write the page with an open button and a <dialog>.
2. Inside the dialog, wrap the content in <form method="dialog"> with a close button.
3. Add the script that calls showModal() on click.
4. Remove the default border and round the dialog.
5. Style ::backdrop.
6. Test: Escape closes it; focus is trapped inside.

Project 678: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - Offer</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Pyramid Fitness</h1>
    <p>Train smarter, feel stronger.</p>
    <button type="button" id="open">See this week's offer</button>
    <dialog id="offer">
      <form method="dialog">
        <h2>This week only</h2>
        <p><strong>Morning yoga</strong> for 100 EGP: 20 percent off
with the code WEB20.</p>
        <button value="close">Close</button>
      </form>
    </dialog>
  </main>
  <script>
    const dlg = document.getElementById('offer');
    document.getElementById('open').addEventListener('click', () =>
dlg.showModal());
  </script>
</body>
</html>
```

Project 678: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 3rem auto; padding: 0 1rem; }
button { padding: .7rem 1.3rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
dialog { border: 0; border-radius: 16px; padding: 2rem; max-width:
26rem; box-shadow: 0 20px 60px rgb(0 0 0 / 30%); }
dialog::backdrop { background: rgb(0 0 0 / 50%); backdrop-filter:
blur(2px); }
dialog h2 { margin-top: 0; color: var(--brand); }
```

Project 678 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - Offer</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Pyramid Fitness	The main heading; only one per page.
Train smarter, feel stronger.	A paragraph of text.
<button type="button" id="open">See this week's offer</button>	A clickable button; inside a form it submits by default.
<dialog id="offer">	A dialog box; showModal() opens it as a modal.
<form method="dialog">	A form; action is where the data goes, method how it is sent.
This week only	Second-level heading for a section.

Line	What it does
<p>Morning yoga for 100 EGP: 20 percent off with t...	Strong importance (bold by default).
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
background: var(--brand);	Background colour or image.
font: inherit;	Makes form controls use the page font instead of the browser default.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 16px;	Rounds the corners.
box-shadow: 0 20px 60px rgb(0 0 0 / 30%);	Soft shadow that lifts the element from the page.
dialog::backdrop {	The dimmed layer behind a modal dialog.
backdrop-filter: blur(2px);	Blurs or filters whatever is behind the element.

Check your work

- Escape key closes
- Focus moves into the dialog
- Background is not clickable
- Close button visible

Exercises

1. Open the dialog automatically after 5 seconds, once per visit (localStorage).
2. Animate the entrance with @starting-style.
3. Add a form inside and read the returnValue.

Theme data for this project

Field	Value
Business	Pyramid Fitness

Field	Value
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 679: Modal dialog for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 3 | Files: index.html, styles.css

Brief

Show a promotional pop-up using the native dialog element, opened with two lines of JavaScript, closed by a form with method=dialog, with a blurred backdrop.

Learning goals

- Use <dialog> and showModal()
- Close a dialog with method="dialog"
- Style ::backdrop

Elements and CSS used

HTML elements	CSS features
button, dialog, form method=dialog, h2, p, strong, script	::backdrop, backdrop-filter, box-shadow, border-radius

Build guide

1. Write the page with an open button and a <dialog>.
2. Inside the dialog, wrap the content in <form method="dialog"> with a close button.
3. Add the script that calls showModal() on click.
4. Remove the default border and round the dialog.
5. Style ::backdrop.
6. Test: Escape closes it; focus is trapped inside.

Project 679: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - Offer</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Delta Dental Clinic</h1>
    <p>Gentle care for the whole family.</p>
    <button type="button" id="open">See this week's offer</button>
    <dialog id="offer">
      <form method="dialog">
        <h2>This week only</h2>
        <p><strong>Check-up</strong> for 300 EGP: 20 percent off with
the code WEB20.</p>
        <button value="close">Close</button>
      </form>
    </dialog>
  </main>
  <script>
    const dlg = document.getElementById('offer');
    document.getElementById('open').addEventListener('click', () =>
dlg.showModal());
  </script>
</body>
</html>
```

Project 679: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 3rem auto; padding: 0 1rem; }
button { padding: .7rem 1.3rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
dialog { border: 0; border-radius: 16px; padding: 2rem; max-width:
26rem; box-shadow: 0 20px 60px rgb(0 0 0 / 30%); }
dialog::backdrop { background: rgb(0 0 0 / 50%); backdrop-filter:
blur(2px); }
dialog h2 { margin-top: 0; color: var(--brand); }
```

Project 679 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - Offer</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Delta Dental Clinic	The main heading; only one per page.
Gentle care for the whole family.	A paragraph of text.
<button type="button" id="open">See this week's offer</button>	A clickable button; inside a form it submits by default.
<dialog id="offer">	A dialog box; showModal() opens it as a modal.
<form method="dialog">	A form; action is where the data goes, method how it is sent.
This week only	Second-level heading for a section.

Line	What it does
<p>Check-up for 300 EGP: 20 percent off with the c...	Strong importance (bold by default).
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
background: var(--brand);	Background colour or image.
font: inherit;	Makes form controls use the page font instead of the browser default.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 16px;	Rounds the corners.
box-shadow: 0 20px 60px rgb(0 0 0 / 30%);	Soft shadow that lifts the element from the page.
dialog::backdrop {	The dimmed layer behind a modal dialog.
backdrop-filter: blur(2px);	Blurs or filters whatever is behind the element.

Check your work

- Escape key closes
- Focus moves into the dialog
- Background is not clickable
- Close button visible

Exercises

1. Open the dialog automatically after 5 seconds, once per visit (localStorage).
2. Animate the entrance with @starting-style.
3. Add a form inside and read the returnValue.

Theme data for this project

Field	Value
Business	Delta Dental Clinic

Field	Value
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 680: Modal dialog for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 3 | Files: index.html, styles.css

Brief

Show a promotional pop-up using the native dialog element, opened with two lines of JavaScript, closed by a form with method=dialog, with a blurred backdrop.

Learning goals

- Use <dialog> and showModal()
- Close a dialog with method="dialog"
- Style ::backdrop

Elements and CSS used

HTML elements	CSS features
button, dialog, form method=dialog, h2, p, strong, script	::backdrop, backdrop-filter, box-shadow, border-radius

Build guide

1. Write the page with an open button and a <dialog>.
2. Inside the dialog, wrap the content in <form method="dialog"> with a close button.
3. Add the script that calls showModal() on click.
4. Remove the default border and round the dialog.
5. Style ::backdrop.
6. Test: Escape closes it; focus is trapped inside.

Project 680: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - Offer</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Red Sea Travel</h1>
    <p>Discover Egypt from desert to reef.</p>
    <button type="button" id="open">See this week's offer</button>
    <dialog id="offer">
      <form method="dialog">
        <h2>This week only</h2>
        <p><strong>Luxor day trip</strong> for 1200 EGP: 20 percent
off with the code WEB20.</p>
        <button value="close">Close</button>
      </form>
    </dialog>
  </main>
  <script>
    const dlg = document.getElementById('offer');
    document.getElementById('open').addEventListener('click', () =>
dlg.showModal());
  </script>
</body>
</html>
```

Project 680: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 3rem auto; padding: 0 1rem; }
button { padding: .7rem 1.3rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
dialog { border: 0; border-radius: 16px; padding: 2rem; max-width:
26rem; box-shadow: 0 20px 60px rgb(0 0 0 / 30%); }
dialog::backdrop { background: rgb(0 0 0 / 50%); backdrop-filter:
blur(2px); }
dialog h2 { margin-top: 0; color: var(--brand); }
```

Project 680 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - Offer</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Red Sea Travel	The main heading; only one per page.
Discover Egypt from desert to reef.	A paragraph of text.
<button type="button" id="open">See this week's offer</button>	A clickable button; inside a form it submits by default.
<dialog id="offer">	A dialog box; showModal() opens it as a modal.
<form method="dialog">	A form; action is where the data goes, method how it is sent.
This week only	Second-level heading for a section.

Line	What it does
<p>Luxor day trip for 1200 EGP: 20 percent off wit...	Strong importance (bold by default).
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
background: var(--brand);	Background colour or image.
font: inherit;	Makes form controls use the page font instead of the browser default.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 16px;	Rounds the corners.
box-shadow: 0 20px 60px rgb(0 0 0 / 30%);	Soft shadow that lifts the element from the page.
dialog::backdrop {	The dimmed layer behind a modal dialog.
backdrop-filter: blur(2px);	Blurs or filters whatever is behind the element.

Check your work

- Escape key closes
- Focus moves into the dialog
- Background is not clickable
- Close button visible

Exercises

1. Open the dialog automatically after 5 seconds, once per visit (localStorage).
2. Animate the entrance with @starting-style.
3. Add a form inside and read the returnValue.

Theme data for this project

Field	Value
Business	Red Sea Travel

Field	Value
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 681: Modal dialog for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 3 | Files: index.html, styles.css

Brief

Show a promotional pop-up using the native dialog element, opened with two lines of JavaScript, closed by a form with method=dialog, with a blurred backdrop.

Learning goals

- Use <dialog> and showModal()
- Close a dialog with method="dialog"
- Style ::backdrop

Elements and CSS used

HTML elements	CSS features
button, dialog, form method=dialog, h2, p, strong, script	::backdrop, backdrop-filter, box-shadow, border-radius

Build guide

1. Write the page with an open button and a <dialog>.
2. Inside the dialog, wrap the content in <form method="dialog"> with a close button.
3. Add the script that calls showModal() on click.
4. Remove the default border and round the dialog.
5. Style ::backdrop.
6. Test: Escape closes it; focus is trapped inside.

Project 681: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - Offer</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Lotus Language School</h1>
    <p>Learn English, French and German in small groups.</p>
    <button type="button" id="open">See this week's offer</button>
    <dialog id="offer">
      <form method="dialog">
        <h2>This week only</h2>
        <p><strong>English A1</strong> for 1800 EGP: 20 percent off
with the code WEB20.</p>
        <button value="close">Close</button>
      </form>
    </dialog>
  </main>
  <script>
    const dlg = document.getElementById('offer');
    document.getElementById('open').addEventListener('click', () =>
dlg.showModal());
  </script>
</body>
</html>
```

Project 681: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 3rem auto; padding: 0 1rem; }
button { padding: .7rem 1.3rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
dialog { border: 0; border-radius: 16px; padding: 2rem; max-width:
26rem; box-shadow: 0 20px 60px rgb(0 0 0 / 30%); }
dialog::backdrop { background: rgb(0 0 0 / 50%); backdrop-filter:
blur(2px); }
dialog h2 { margin-top: 0; color: var(--brand); }
```

Project 681 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - Offer</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Lotus Language School	The main heading; only one per page.
Learn English, French and German in small groups.	A paragraph of text.
<button type="button" id="open">See this week's offer</button>	A clickable button; inside a form it submits by default.
<dialog id="offer">	A dialog box; showModal() opens it as a modal.
<form method="dialog">	A form; action is where the data goes, method how it is sent.
This week only	Second-level heading for a section.

Line	What it does
<p>English A1 for 1800 EGP: 20 percent off with th...	Strong importance (bold by default).
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
background: var(--brand);	Background colour or image.
font: inherit;	Makes form controls use the page font instead of the browser default.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 16px;	Rounds the corners.
box-shadow: 0 20px 60px rgb(0 0 0 / 30%);	Soft shadow that lifts the element from the page.
dialog::backdrop {	The dimmed layer behind a modal dialog.
backdrop-filter: blur(2px);	Blurs or filters whatever is behind the element.

Check your work

- Escape key closes
- Focus moves into the dialog
- Background is not clickable
- Close button visible

Exercises

1. Open the dialog automatically after 5 seconds, once per visit (localStorage).
2. Animate the entrance with @starting-style.
3. Add a form inside and read the returnValue.

Theme data for this project

Field	Value
Business	Lotus Language School

Field	Value
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 682: Modal dialog for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 3 | Files: index.html, styles.css

Brief

Show a promotional pop-up using the native dialog element, opened with two lines of JavaScript, closed by a form with method=dialog, with a blurred backdrop.

Learning goals

- Use <dialog> and showModal()
- Close a dialog with method="dialog"
- Style ::backdrop

Elements and CSS used

HTML elements	CSS features
button, dialog, form method=dialog, h2, p, strong, script	::backdrop, backdrop-filter, box-shadow, border-radius

Build guide

1. Write the page with an open button and a <dialog>.
2. Inside the dialog, wrap the content in <form method="dialog"> with a close button.
3. Add the script that calls showModal() on click.
4. Remove the default border and round the dialog.
5. Style ::backdrop.
6. Test: Escape closes it; focus is trapped inside.

Project 682: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - Offer</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Green Leaf Cafe</h1>
    <p>Specialty coffee and quiet corners.</p>
    <button type="button" id="open">See this week's offer</button>
    <dialog id="offer">
      <form method="dialog">
        <h2>This week only</h2>
        <p><strong>Flat white</strong> for 55 EGP: 20 percent off
with the code WEB20.</p>
        <button value="close">Close</button>
      </form>
    </dialog>
  </main>
  <script>
    const dlg = document.getElementById('offer');
    document.getElementById('open').addEventListener('click', () =>
dlg.showModal());
  </script>
</body>
</html>
```

Project 682: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 3rem auto; padding: 0 1rem; }
button { padding: .7rem 1.3rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
dialog { border: 0; border-radius: 16px; padding: 2rem; max-width:
26rem; box-shadow: 0 20px 60px rgb(0 0 0 / 30%); }
dialog::backdrop { background: rgb(0 0 0 / 50%); backdrop-filter:
blur(2px); }
dialog h2 { margin-top: 0; color: var(--brand); }
```

Project 682 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - Offer</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Green Leaf Cafe	The main heading; only one per page.
Specialty coffee and quiet corners.	A paragraph of text.
<button type="button" id="open">See this week's offer</button>	A clickable button; inside a form it submits by default.
<dialog id="offer">	A dialog box; showModal() opens it as a modal.
<form method="dialog">	A form; action is where the data goes, method how it is sent.
This week only	Second-level heading for a section.

Line	What it does
<p>Flat white for 55 EGP: 20 percent off with the ...	Strong importance (bold by default).
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
background: var(--brand);	Background colour or image.
font: inherit;	Makes form controls use the page font instead of the browser default.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 16px;	Rounds the corners.
box-shadow: 0 20px 60px rgb(0 0 0 / 30%);	Soft shadow that lifts the element from the page.
dialog::backdrop {	The dimmed layer behind a modal dialog.
backdrop-filter: blur(2px);	Blurs or filters whatever is behind the element.

Check your work

- Escape key closes
- Focus moves into the dialog
- Background is not clickable
- Close button visible

Exercises

1. Open the dialog automatically after 5 seconds, once per visit (localStorage).
2. Animate the entrance with @starting-style.
3. Add a form inside and read the returnValue.

Theme data for this project

Field	Value
Business	Green Leaf Cafe

Field	Value
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 683: Modal dialog for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 3 | Files: index.html, styles.css

Brief

Show a promotional pop-up using the native dialog element, opened with two lines of JavaScript, closed by a form with method=dialog, with a blurred backdrop.

Learning goals

- Use <dialog> and showModal()
- Close a dialog with method="dialog"
- Style ::backdrop

Elements and CSS used

HTML elements	CSS features
button, dialog, form method=dialog, h2, p, strong, script	::backdrop, backdrop-filter, box-shadow, border-radius

Build guide

1. Write the page with an open button and a <dialog>.
2. Inside the dialog, wrap the content in <form method="dialog"> with a close button.
3. Add the script that calls showModal() on click.
4. Remove the default border and round the dialog.
5. Style ::backdrop.
6. Test: Escape closes it; focus is trapped inside.

Project 683: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - Offer</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Sinai Trekking Club</h1>
    <p>Guided mountain walks for every level.</p>
    <button type="button" id="open">See this week's offer</button>
    <dialog id="offer">
      <form method="dialog">
        <h2>This week only</h2>
        <p><strong>Mount Sinai sunrise</strong> for 400 EGP: 20
percent off with the code WEB20.</p>
        <button value="close">Close</button>
      </form>
    </dialog>
  </main>
  <script>
    const dlg = document.getElementById('offer');
    document.getElementById('open').addEventListener('click', () =>
dlg.showModal());
  </script>
</body>
</html>
```

Project 683: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 3rem auto; padding: 0 1rem; }
button { padding: .7rem 1.3rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
dialog { border: 0; border-radius: 16px; padding: 2rem; max-width:
26rem; box-shadow: 0 20px 60px rgb(0 0 0 / 30%); }
dialog::backdrop { background: rgb(0 0 0 / 50%); backdrop-filter:
blur(2px); }
dialog h2 { margin-top: 0; color: var(--brand); }
```

Project 683 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - Offer</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Sinai Trekking Club	The main heading; only one per page.
Guided mountain walks for every level.	A paragraph of text.
<button type="button" id="open">See this week's offer</button>	A clickable button; inside a form it submits by default.
<dialog id="offer">	A dialog box; showModal() opens it as a modal.
<form method="dialog">	A form; action is where the data goes, method how it is sent.
This week only	Second-level heading for a section.

Line	What it does
<p>Mount Sinai sunrise for 400 EGP: 20 percent off...	Strong importance (bold by default).
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
background: var(--brand);	Background colour or image.
font: inherit;	Makes form controls use the page font instead of the browser default.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 16px;	Rounds the corners.
box-shadow: 0 20px 60px rgb(0 0 0 / 30%);	Soft shadow that lifts the element from the page.
dialog::backdrop {	The dimmed layer behind a modal dialog.
backdrop-filter: blur(2px);	Blurs or filters whatever is behind the element.

Check your work

- Escape key closes
- Focus moves into the dialog
- Background is not clickable
- Close button visible

Exercises

1. Open the dialog automatically after 5 seconds, once per visit (localStorage).
2. Animate the entrance with @starting-style.
3. Add a form inside and read the returnValue.

Theme data for this project

Field	Value
Business	Sinai Trekking Club

Field	Value
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 684: Modal dialog for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 3 | Files: index.html, styles.css

Brief

Show a promotional pop-up using the native dialog element, opened with two lines of JavaScript, closed by a form with method=dialog, with a blurred backdrop.

Learning goals

- Use <dialog> and showModal()
- Close a dialog with method="dialog"
- Style ::backdrop

Elements and CSS used

HTML elements	CSS features
button, dialog, form method=dialog, h2, p, strong, script	::backdrop, backdrop-filter, box-shadow, border-radius

Build guide

1. Write the page with an open button and a <dialog>.
2. Inside the dialog, wrap the content in <form method="dialog"> with a close button.
3. Add the script that calls showModal() on click.
4. Remove the default border and round the dialog.
5. Style ::backdrop.
6. Test: Escape closes it; focus is trapped inside.

Project 684: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - Offer</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Horizon Photography</h1>
    <p>Portraits, weddings and product photography.</p>
    <button type="button" id="open">See this week's offer</button>
    <dialog id="offer">
      <form method="dialog">
        <h2>This week only</h2>
        <p><strong>Portrait session</strong> for 1200 EGP: 20 percent
off with the code WEB20.</p>
        <button value="close">Close</button>
      </form>
    </dialog>
  </main>
  <script>
    const dlg = document.getElementById('offer');
    document.getElementById('open').addEventListener('click', () =>
dlg.showModal());
  </script>
</body>
</html>
```

Project 684: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 3rem auto; padding: 0 1rem; }
button { padding: .7rem 1.3rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
dialog { border: 0; border-radius: 16px; padding: 2rem; max-width:
26rem; box-shadow: 0 20px 60px rgb(0 0 0 / 30%); }
dialog::backdrop { background: rgb(0 0 0 / 50%); backdrop-filter:
blur(2px); }
dialog h2 { margin-top: 0; color: var(--brand); }
```

Project 684 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - Offer</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Horizon Photography	The main heading; only one per page.
Portraits, weddings and product photography.	A paragraph of text.
<button type="button" id="open">See this week's offer</button>	A clickable button; inside a form it submits by default.
<dialog id="offer">	A dialog box; showModal() opens it as a modal.
<form method="dialog">	A form; action is where the data goes, method how it is sent.
This week only	Second-level heading for a section.

Line	What it does
<p>Portrait session for 1200 EGP: 20 percent off w...	Strong importance (bold by default).
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
background: var(--brand);	Background colour or image.
font: inherit;	Makes form controls use the page font instead of the browser default.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 16px;	Rounds the corners.
box-shadow: 0 20px 60px rgb(0 0 0 / 30%);	Soft shadow that lifts the element from the page.
dialog::backdrop {	The dimmed layer behind a modal dialog.
backdrop-filter: blur(2px);	Blurs or filters whatever is behind the element.

Check your work

- Escape key closes
- Focus moves into the dialog
- Background is not clickable
- Close button visible

Exercises

1. Open the dialog automatically after 5 seconds, once per visit (localStorage).
2. Animate the entrance with @starting-style.
3. Add a form inside and read the returnValue.

Theme data for this project

Field	Value
Business	Horizon Photography

Field	Value
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 685: Modal dialog for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 3 | Files: index.html, styles.css

Brief

Show a promotional pop-up using the native dialog element, opened with two lines of JavaScript, closed by a form with method=dialog, with a blurred backdrop.

Learning goals

- Use <dialog> and showModal()
- Close a dialog with method="dialog"
- Style ::backdrop

Elements and CSS used

HTML elements	CSS features
button, dialog, form method=dialog, h2, p, strong, script	::backdrop, backdrop-filter, box-shadow, border-radius

Build guide

1. Write the page with an open button and a <dialog>.
2. Inside the dialog, wrap the content in <form method="dialog"> with a close button.
3. Add the script that calls showModal() on click.
4. Remove the default border and round the dialog.
5. Style ::backdrop.
6. Test: Escape closes it; focus is trapped inside.

Project 685: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - Offer</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Papyrus Stationery</h1>
    <p>Notebooks, pens and paper made in Egypt.</p>
    <button type="button" id="open">See this week's offer</button>
    <dialog id="offer">
      <form method="dialog">
        <h2>This week only</h2>
        <p><strong>Dotted notebook</strong> for 140 EGP: 20 percent
off with the code WEB20.</p>
        <button value="close">Close</button>
      </form>
    </dialog>
  </main>
  <script>
    const dlg = document.getElementById('offer');
    document.getElementById('open').addEventListener('click', () =>
dlg.showModal());
  </script>
</body>
</html>
```

Project 685: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 3rem auto; padding: 0 1rem; }
button { padding: .7rem 1.3rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
dialog { border: 0; border-radius: 16px; padding: 2rem; max-width:
26rem; box-shadow: 0 20px 60px rgb(0 0 0 / 30%); }
dialog::backdrop { background: rgb(0 0 0 / 50%); backdrop-filter:
blur(2px); }
dialog h2 { margin-top: 0; color: var(--brand); }
```

Project 685 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - Offer</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Papyrus Stationery	The main heading; only one per page.
Notebooks, pens and paper made in Egypt.	A paragraph of text.
<button type="button" id="open">See this week's offer</button>	A clickable button; inside a form it submits by default.
<dialog id="offer">	A dialog box; showModal() opens it as a modal.
<form method="dialog">	A form; action is where the data goes, method how it is sent.
This week only	Second-level heading for a section.

Line	What it does
<p>Dotted notebook for 140 EGP: 20 percent off wit...	Strong importance (bold by default).
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
background: var(--brand);	Background colour or image.
font: inherit;	Makes form controls use the page font instead of the browser default.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 16px;	Rounds the corners.
box-shadow: 0 20px 60px rgb(0 0 0 / 30%);	Soft shadow that lifts the element from the page.
dialog::backdrop {	The dimmed layer behind a modal dialog.
backdrop-filter: blur(2px);	Blurs or filters whatever is behind the element.

Check your work

- Escape key closes
- Focus moves into the dialog
- Background is not clickable
- Close button visible

Exercises

1. Open the dialog automatically after 5 seconds, once per visit (localStorage).
2. Animate the entrance with @starting-style.
3. Add a form inside and read the returnValue.

Theme data for this project

Field	Value
Business	Papyrus Stationery

Field	Value
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 686: Modal dialog for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 3 | Files: index.html, styles.css

Brief

Show a promotional pop-up using the native dialog element, opened with two lines of JavaScript, closed by a form with method=dialog, with a blurred backdrop.

Learning goals

- Use <dialog> and showModal()
- Close a dialog with method="dialog"
- Style ::backdrop

Elements and CSS used

HTML elements	CSS features
button, dialog, form method=dialog, h2, p, strong, script	::backdrop, backdrop-filter, box-shadow, border-radius

Build guide

1. Write the page with an open button and a <dialog>.
2. Inside the dialog, wrap the content in <form method="dialog"> with a close button.
3. Add the script that calls showModal() on click.
4. Remove the default border and round the dialog.
5. Style ::backdrop.
6. Test: Escape closes it; focus is trapped inside.

Project 686: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - Offer</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Oasis Plant Nursery</h1>
    <p>Indoor plants and gardening advice.</p>
    <button type="button" id="open">See this week's offer</button>
    <dialog id="offer">
      <form method="dialog">
        <h2>This week only</h2>
        <p><strong>Monstera</strong> for 250 EGP: 20 percent off with
the code WEB20.</p>
        <button value="close">Close</button>
      </form>
    </dialog>
  </main>
  <script>
    const dlg = document.getElementById('offer');
    document.getElementById('open').addEventListener('click', () =>
dlg.showModal());
  </script>
</body>
</html>
```

Project 686: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 3rem auto; padding: 0 1rem; }
button { padding: .7rem 1.3rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
dialog { border: 0; border-radius: 16px; padding: 2rem; max-width:
26rem; box-shadow: 0 20px 60px rgb(0 0 0 / 30%); }
dialog::backdrop { background: rgb(0 0 0 / 50%); backdrop-filter:
blur(2px); }
dialog h2 { margin-top: 0; color: var(--brand); }
```

Project 686 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - Offer</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Oasis Plant Nursery	The main heading; only one per page.
Indoor plants and gardening advice.	A paragraph of text.
<button type="button" id="open">See this week's offer</button>	A clickable button; inside a form it submits by default.
<dialog id="offer">	A dialog box; showModal() opens it as a modal.
<form method="dialog">	A form; action is where the data goes, method how it is sent.
This week only	Second-level heading for a section.

Line	What it does
<p>Monstera for 250 EGP: 20 percent off with the c...	Strong importance (bold by default).
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
background: var(--brand);	Background colour or image.
font: inherit;	Makes form controls use the page font instead of the browser default.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 16px;	Rounds the corners.
box-shadow: 0 20px 60px rgb(0 0 0 / 30%);	Soft shadow that lifts the element from the page.
dialog::backdrop {	The dimmed layer behind a modal dialog.
backdrop-filter: blur(2px);	Blurs or filters whatever is behind the element.

Check your work

- Escape key closes
- Focus moves into the dialog
- Background is not clickable
- Close button visible

Exercises

1. Open the dialog automatically after 5 seconds, once per visit (localStorage).
2. Animate the entrance with @starting-style.
3. Add a form inside and read the returnValue.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery

Field	Value
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 687: Modal dialog for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 3 | Files: index.html, styles.css

Brief

Show a promotional pop-up using the native dialog element, opened with two lines of JavaScript, closed by a form with method=dialog, with a blurred backdrop.

Learning goals

- Use <dialog> and showModal()
- Close a dialog with method="dialog"
- Style ::backdrop

Elements and CSS used

HTML elements	CSS features
button, dialog, form method=dialog, h2, p, strong, script	::backdrop, backdrop-filter, box-shadow, border-radius

Build guide

1. Write the page with an open button and a <dialog>.
2. Inside the dialog, wrap the content in <form method="dialog"> with a close button.
3. Add the script that calls showModal() on click.
4. Remove the default border and round the dialog.
5. Style ::backdrop.
6. Test: Escape closes it; focus is trapped inside.

Project 687: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - Offer</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cedar Furniture</h1>
    <p>Solid wood furniture made to order.</p>
    <button type="button" id="open">See this week's offer</button>
    <dialog id="offer">
      <form method="dialog">
        <h2>This week only</h2>
        <p><strong>Oak dining table</strong> for 9500 EGP: 20 percent
off with the code WEB20.</p>
        <button value="close">Close</button>
      </form>
    </dialog>
  </main>
  <script>
    const dlg = document.getElementById('offer');
    document.getElementById('open').addEventListener('click', () =>
dlg.showModal());
  </script>
</body>
</html>
```

Project 687: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 3rem auto; padding: 0 1rem; }
button { padding: .7rem 1.3rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
dialog { border: 0; border-radius: 16px; padding: 2rem; max-width:
26rem; box-shadow: 0 20px 60px rgb(0 0 0 / 30%); }
dialog::backdrop { background: rgb(0 0 0 / 50%); backdrop-filter:
blur(2px); }
dialog h2 { margin-top: 0; color: var(--brand); }
```

Project 687 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - Offer</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cedar Furniture	The main heading; only one per page.
Solid wood furniture made to order.	A paragraph of text.
<button type="button" id="open">See this week's offer</button>	A clickable button; inside a form it submits by default.
<dialog id="offer">	A dialog box; showModal() opens it as a modal.
<form method="dialog">	A form; action is where the data goes, method how it is sent.
This week only	Second-level heading for a section.

Line	What it does
<p>Oak dining table for 9500 EGP: 20 percent off w…	Strong importance (bold by default).
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
background: var(--brand);	Background colour or image.
font: inherit;	Makes form controls use the page font instead of the browser default.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 16px;	Rounds the corners.
box-shadow: 0 20px 60px rgb(0 0 0 / 30%);	Soft shadow that lifts the element from the page.
dialog::backdrop {	The dimmed layer behind a modal dialog.
backdrop-filter: blur(2px);	Blurs or filters whatever is behind the element.

Check your work

- Escape key closes
- Focus moves into the dialog
- Background is not clickable
- Close button visible

Exercises

1. Open the dialog automatically after 5 seconds, once per visit (localStorage).
2. Animate the entrance with @starting-style.
3. Add a form inside and read the returnValue.

Theme data for this project

Field	Value
Business	Cedar Furniture

Field	Value
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 688: Modal dialog for Byte Repair

Theme: Byte Repair (Nasr City) | Level 3 | Files: index.html, styles.css

Brief

Show a promotional pop-up using the native dialog element, opened with two lines of JavaScript, closed by a form with method=dialog, with a blurred backdrop.

Learning goals

- Use <dialog> and showModal()
- Close a dialog with method="dialog"
- Style ::backdrop

Elements and CSS used

HTML elements	CSS features
button, dialog, form method=dialog, h2, p, strong, script	::backdrop, backdrop-filter, box-shadow, border-radius

Build guide

1. Write the page with an open button and a <dialog>.
2. Inside the dialog, wrap the content in <form method="dialog"> with a close button.
3. Add the script that calls showModal() on click.
4. Remove the default border and round the dialog.
5. Style ::backdrop.
6. Test: Escape closes it; focus is trapped inside.

Project 688: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - Offer</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Byte Repair</h1>
    <p>Phone and laptop repairs while you wait.</p>
    <button type="button" id="open">See this week's offer</button>
    <dialog id="offer">
      <form method="dialog">
        <h2>This week only</h2>
        <p><strong>Screen replacement</strong> for From 800 EGP: 20
percent off with the code WEB20.</p>
        <button value="close">Close</button>
      </form>
    </dialog>
  </main>
  <script>
    const dlg = document.getElementById('offer');
    document.getElementById('open').addEventListener('click', () =>
dlg.showModal());
  </script>
</body>
</html>
```

Project 688: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 3rem auto; padding: 0 1rem; }
button { padding: .7rem 1.3rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
dialog { border: 0; border-radius: 16px; padding: 2rem; max-width:
26rem; box-shadow: 0 20px 60px rgb(0 0 0 / 30%); }
dialog::backdrop { background: rgb(0 0 0 / 50%); backdrop-filter:
blur(2px); }
dialog h2 { margin-top: 0; color: var(--brand); }
```

Project 688 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - Offer</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Byte Repair	The main heading; only one per page.
Phone and laptop repairs while you wait.	A paragraph of text.
<button type="button" id="open">See this week's offer</button>	A clickable button; inside a form it submits by default.
<dialog id="offer">	A dialog box; showModal() opens it as a modal.
<form method="dialog">	A form; action is where the data goes, method how it is sent.
This week only	Second-level heading for a section.

Line	What it does
<p>Screen replacement for From 800 EGP: 20 percent...	Strong importance (bold by default).
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
background: var(--brand);	Background colour or image.
font: inherit;	Makes form controls use the page font instead of the browser default.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 16px;	Rounds the corners.
box-shadow: 0 20px 60px rgb(0 0 0 / 30%);	Soft shadow that lifts the element from the page.
dialog::backdrop {	The dimmed layer behind a modal dialog.
backdrop-filter: blur(2px);	Blurs or filters whatever is behind the element.

Check your work

- Escape key closes
- Focus moves into the dialog
- Background is not clickable
- Close button visible

Exercises

1. Open the dialog automatically after 5 seconds, once per visit (localStorage).
2. Animate the entrance with @starting-style.
3. Add a form inside and read the returnValue.

Theme data for this project

Field	Value
Business	Byte Repair

Field	Value
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 689: Modal dialog for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 3 | Files: index.html, styles.css

Brief

Show a promotional pop-up using the native dialog element, opened with two lines of JavaScript, closed by a form with method=dialog, with a blurred backdrop.

Learning goals

- Use <dialog> and showModal()
- Close a dialog with method="dialog"
- Style ::backdrop

Elements and CSS used

HTML elements	CSS features
button, dialog, form method=dialog, h2, p, strong, script	::backdrop, backdrop-filter, box-shadow, border-radius

Build guide

1. Write the page with an open button and a <dialog>.
2. Inside the dialog, wrap the content in <form method="dialog"> with a close button.
3. Add the script that calls showModal() on click.
4. Remove the default border and round the dialog.
5. Style ::backdrop.
6. Test: Escape closes it; focus is trapped inside.

Project 689: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - Offer</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Sahara Pet Care</h1>
    <p>Grooming, boarding and vet visits.</p>
    <button type="button" id="open">See this week's offer</button>
    <dialog id="offer">
      <form method="dialog">
        <h2>This week only</h2>
        <p><strong>Full grooming</strong> for 400 EGP: 20 percent off
with the code WEB20.</p>
        <button value="close">Close</button>
      </form>
    </dialog>
  </main>
  <script>
    const dlg = document.getElementById('offer');
    document.getElementById('open').addEventListener('click', () =>
dlg.showModal());
  </script>
</body>
</html>
```

Project 689: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 3rem auto; padding: 0 1rem; }
button { padding: .7rem 1.3rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
dialog { border: 0; border-radius: 16px; padding: 2rem; max-width:
26rem; box-shadow: 0 20px 60px rgb(0 0 0 / 30%); }
dialog::backdrop { background: rgb(0 0 0 / 50%); backdrop-filter:
blur(2px); }
dialog h2 { margin-top: 0; color: var(--brand); }
```

Project 689 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - Offer</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Sahara Pet Care	The main heading; only one per page.
Grooming, boarding and vet visits.	A paragraph of text.
<button type="button" id="open">See this week's offer</button>	A clickable button; inside a form it submits by default.
<dialog id="offer">	A dialog box; showModal() opens it as a modal.
<form method="dialog">	A form; action is where the data goes, method how it is sent.
This week only	Second-level heading for a section.

Line	What it does
<p>Full grooming for 400 EGP: 20 percent off with ...	Strong importance (bold by default).
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
background: var(--brand);	Background colour or image.
font: inherit;	Makes form controls use the page font instead of the browser default.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 16px;	Rounds the corners.
box-shadow: 0 20px 60px rgb(0 0 0 / 30%);	Soft shadow that lifts the element from the page.
dialog::backdrop {	The dimmed layer behind a modal dialog.
backdrop-filter: blur(2px);	Blurs or filters whatever is behind the element.

Check your work

- Escape key closes
- Focus moves into the dialog
- Background is not clickable
- Close button visible

Exercises

1. Open the dialog automatically after 5 seconds, once per visit (localStorage).
2. Animate the entrance with @starting-style.
3. Add a form inside and read the returnValue.

Theme data for this project

Field	Value
Business	Sahara Pet Care

Field	Value
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 690: Modal dialog for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 3 | Files: index.html, styles.css

Brief

Show a promotional pop-up using the native dialog element, opened with two lines of JavaScript, closed by a form with method=dialog, with a blurred backdrop.

Learning goals

- Use <dialog> and showModal()
- Close a dialog with method="dialog"
- Style ::backdrop

Elements and CSS used

HTML elements	CSS features
button, dialog, form method=dialog, h2, p, strong, script	::backdrop, backdrop-filter, box-shadow, border-radius

Build guide

1. Write the page with an open button and a <dialog>.
2. Inside the dialog, wrap the content in <form method="dialog"> with a close button.
3. Add the script that calls showModal() on click.
4. Remove the default border and round the dialog.
5. Style ::backdrop.
6. Test: Escape closes it; focus is trapped inside.

Project 690: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - Offer</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Alexandria Sailing School</h1>
    <p>Learn to sail on the Mediterranean.</p>
    <button type="button" id="open">See this week's offer</button>
    <dialog id="offer">
      <form method="dialog">
        <h2>This week only</h2>
        <p><strong>Taster session</strong> for 500 EGP: 20 percent
off with the code WEB20.</p>
        <button value="close">Close</button>
      </form>
    </dialog>
  </main>
  <script>
    const dlg = document.getElementById('offer');
    document.getElementById('open').addEventListener('click', () =>
dlg.showModal());
  </script>
</body>
</html>
```

Project 690: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 3rem auto; padding: 0 1rem; }
button { padding: .7rem 1.3rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
dialog { border: 0; border-radius: 16px; padding: 2rem; max-width:
26rem; box-shadow: 0 20px 60px rgb(0 0 0 / 30%); }
dialog::backdrop { background: rgb(0 0 0 / 50%); backdrop-filter:
blur(2px); }
dialog h2 { margin-top: 0; color: var(--brand); }
```

Project 690 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - Offer</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Alexandria Sailing School	The main heading; only one per page.
Learn to sail on the Mediterranean.	A paragraph of text.
<button type="button" id="open">See this week's offer</button>	A clickable button; inside a form it submits by default.
<dialog id="offer">	A dialog box; showModal() opens it as a modal.
<form method="dialog">	A form; action is where the data goes, method how it is sent.
This week only	Second-level heading for a section.

Line	What it does
<p>Taster session for 500 EGP: 20 percent off with...	Strong importance (bold by default).
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
background: var(--brand);	Background colour or image.
font: inherit;	Makes form controls use the page font instead of the browser default.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 16px;	Rounds the corners.
box-shadow: 0 20px 60px rgb(0 0 0 / 30%);	Soft shadow that lifts the element from the page.
dialog::backdrop {	The dimmed layer behind a modal dialog.
backdrop-filter: blur(2px);	Blurs or filters whatever is behind the element.

Check your work

- Escape key closes
- Focus moves into the dialog
- Background is not clickable
- Close button visible

Exercises

1. Open the dialog automatically after 5 seconds, once per visit (localStorage).
2. Animate the entrance with @starting-style.
3. Add a form inside and read the returnValue.

Theme data for this project

Field	Value
Business	Alexandria Sailing School

Field	Value
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 691: Modal dialog for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 3 | Files: index.html, styles.css

Brief

Show a promotional pop-up using the native dialog element, opened with two lines of JavaScript, closed by a form with method=dialog, with a blurred backdrop.

Learning goals

- Use <dialog> and showModal()
- Close a dialog with method="dialog"
- Style ::backdrop

Elements and CSS used

HTML elements	CSS features
button, dialog, form method=dialog, h2, p, strong, script	::backdrop, backdrop-filter, box-shadow, border-radius

Build guide

1. Write the page with an open button and a <dialog>.
2. Inside the dialog, wrap the content in <form method="dialog"> with a close button.
3. Add the script that calls showModal() on click.
4. Remove the default border and round the dialog.
5. Style ::backdrop.
6. Test: Escape closes it; focus is trapped inside.

Project 691: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - Offer</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Habiba Handmade Jewellery</h1>
    <p>Silver and brass pieces inspired by Nubia.</p>
    <button type="button" id="open">See this week's offer</button>
    <dialog id="offer">
      <form method="dialog">
        <h2>This week only</h2>
        <p><strong>Lotus pendant</strong> for 650 EGP: 20 percent off
with the code WEB20.</p>
        <button value="close">Close</button>
      </form>
    </dialog>
  </main>
  <script>
    const dlg = document.getElementById('offer');
    document.getElementById('open').addEventListener('click', () =>
dlg.showModal());
  </script>
</body>
</html>
```

Project 691: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 3rem auto; padding: 0 1rem; }
button { padding: .7rem 1.3rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
dialog { border: 0; border-radius: 16px; padding: 2rem; max-width:
26rem; box-shadow: 0 20px 60px rgb(0 0 0 / 30%); }
dialog::backdrop { background: rgb(0 0 0 / 50%); backdrop-filter:
blur(2px); }
dialog h2 { margin-top: 0; color: var(--brand); }
```

Project 691 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - Offer</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Habiba Handmade Jewellery	The main heading; only one per page.
Silver and brass pieces inspired by Nubia.	A paragraph of text.
<button type="button" id="open">See this week's offer</button>	A clickable button; inside a form it submits by default.
<dialog id="offer">	A dialog box; showModal() opens it as a modal.
<form method="dialog">	A form; action is where the data goes, method how it is sent.
This week only	Second-level heading for a section.

Line	What it does
<p>Lotus pendant for 650 EGP: 20 percent off with ...	Strong importance (bold by default).
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
background: var(--brand);	Background colour or image.
font: inherit;	Makes form controls use the page font instead of the browser default.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 16px;	Rounds the corners.
box-shadow: 0 20px 60px rgb(0 0 0 / 30%);	Soft shadow that lifts the element from the page.
dialog::backdrop {	The dimmed layer behind a modal dialog.
backdrop-filter: blur(2px);	Blurs or filters whatever is behind the element.

Check your work

- Escape key closes
- Focus moves into the dialog
- Background is not clickable
- Close button visible

Exercises

1. Open the dialog automatically after 5 seconds, once per visit (localStorage).
2. Animate the entrance with @starting-style.
3. Add a form inside and read the returnValue.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery

Field	Value
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 692: Modal dialog for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 3 | Files: index.html, styles.css

Brief

Show a promotional pop-up using the native dialog element, opened with two lines of JavaScript, closed by a form with method=dialog, with a blurred backdrop.

Learning goals

- Use <dialog> and showModal()
- Close a dialog with method="dialog"
- Style ::backdrop

Elements and CSS used

HTML elements	CSS features
button, dialog, form method=dialog, h2, p, strong, script	::backdrop, backdrop-filter, box-shadow, border-radius

Build guide

1. Write the page with an open button and a <dialog>.
2. Inside the dialog, wrap the content in <form method="dialog"> with a close button.
3. Add the script that calls showModal() on click.
4. Remove the default border and round the dialog.
5. Style ::backdrop.
6. Test: Escape closes it; focus is trapped inside.

Project 692: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - Offer</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Fayoum Pottery Studio</h1>
    <p>Wheel throwing and glazing classes.</p>
    <button type="button" id="open">See this week's offer</button>
    <dialog id="offer">
      <form method="dialog">
        <h2>This week only</h2>
        <p><strong>Intro to the wheel</strong> for 450 EGP: 20
percent off with the code WEB20.</p>
        <button value="close">Close</button>
      </form>
    </dialog>
  </main>
  <script>
    const dlg = document.getElementById('offer');
    document.getElementById('open').addEventListener('click', () =>
dlg.showModal());
  </script>
</body>
</html>
```

Project 692: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 3rem auto; padding: 0 1rem; }
button { padding: .7rem 1.3rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
dialog { border: 0; border-radius: 16px; padding: 2rem; max-width:
26rem; box-shadow: 0 20px 60px rgb(0 0 0 / 30%); }
dialog::backdrop { background: rgb(0 0 0 / 50%); backdrop-filter:
blur(2px); }
dialog h2 { margin-top: 0; color: var(--brand); }
```

Project 692 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - Offer</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Fayoum Pottery Studio	The main heading; only one per page.
Wheel throwing and glazing classes.	A paragraph of text.
<button type="button" id="open">See this week's offer</button>	A clickable button; inside a form it submits by default.
<dialog id="offer">	A dialog box; showModal() opens it as a modal.
<form method="dialog">	A form; action is where the data goes, method how it is sent.
This week only	Second-level heading for a section.

Line	What it does
<p>Intro to the wheel for 450 EGP: 20 percent off ...	Strong importance (bold by default).
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
background: var(--brand);	Background colour or image.
font: inherit;	Makes form controls use the page font instead of the browser default.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 16px;	Rounds the corners.
box-shadow: 0 20px 60px rgb(0 0 0 / 30%);	Soft shadow that lifts the element from the page.
dialog::backdrop {	The dimmed layer behind a modal dialog.
backdrop-filter: blur(2px);	Blurs or filters whatever is behind the element.

Check your work

- Escape key closes
- Focus moves into the dialog
- Background is not clickable
- Close button visible

Exercises

1. Open the dialog automatically after 5 seconds, once per visit (localStorage).
2. Animate the entrance with @starting-style.
3. Add a form inside and read the returnValue.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio

Field	Value
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 693: Modal dialog for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 3 | Files: index.html, styles.css

Brief

Show a promotional pop-up using the native dialog element, opened with two lines of JavaScript, closed by a form with method=dialog, with a blurred backdrop.

Learning goals

- Use <dialog> and showModal()
- Close a dialog with method="dialog"
- Style ::backdrop

Elements and CSS used

HTML elements	CSS features
button, dialog, form method=dialog, h2, p, strong, script	::backdrop, backdrop-filter, box-shadow, border-radius

Build guide

1. Write the page with an open button and a <dialog>.
2. Inside the dialog, wrap the content in <form method="dialog"> with a close button.
3. Add the script that calls showModal() on click.
4. Remove the default border and round the dialog.
5. Style ::backdrop.
6. Test: Escape closes it; focus is trapped inside.

Project 693: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - Offer</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cleopatra Beauty Salon</h1>
    <p>Hair, nails and skin care.</p>
    <button type="button" id="open">See this week's offer</button>
    <dialog id="offer">
      <form method="dialog">
        <h2>This week only</h2>
        <p><strong>Haircut and blow-dry</strong> for 350 EGP: 20
percent off with the code WEB20.</p>
        <button value="close">Close</button>
      </form>
    </dialog>
  </main>
  <script>
    const dlg = document.getElementById('offer');
    document.getElementById('open').addEventListener('click', () =>
dlg.showModal());
  </script>
</body>
</html>
```

Project 693: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 3rem auto; padding: 0 1rem; }
button { padding: .7rem 1.3rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
dialog { border: 0; border-radius: 16px; padding: 2rem; max-width:
26rem; box-shadow: 0 20px 60px rgb(0 0 0 / 30%); }
dialog::backdrop { background: rgb(0 0 0 / 50%); backdrop-filter:
blur(2px); }
dialog h2 { margin-top: 0; color: var(--brand); }
```

Project 693 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - Offer</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cleopatra Beauty Salon	The main heading; only one per page.
Hair, nails and skin care.	A paragraph of text.
<button type="button" id="open">See this week's offer</button>	A clickable button; inside a form it submits by default.
<dialog id="offer">	A dialog box; showModal() opens it as a modal.
<form method="dialog">	A form; action is where the data goes, method how it is sent.
This week only	Second-level heading for a section.

Line	What it does
<p>Haircut and blow-dry for 350 EGP: 20 percent of...	Strong importance (bold by default).
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
background: var(--brand);	Background colour or image.
font: inherit;	Makes form controls use the page font instead of the browser default.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 16px;	Rounds the corners.
box-shadow: 0 20px 60px rgb(0 0 0 / 30%);	Soft shadow that lifts the element from the page.
dialog::backdrop {	The dimmed layer behind a modal dialog.
backdrop-filter: blur(2px);	Blurs or filters whatever is behind the element.

Check your work

- Escape key closes
- Focus moves into the dialog
- Background is not clickable
- Close button visible

Exercises

1. Open the dialog automatically after 5 seconds, once per visit (localStorage).
2. Animate the entrance with @starting-style.
3. Add a form inside and read the returnValue.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon

Field	Value
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 694: Modal dialog for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 3 | Files: index.html, styles.css

Brief

Show a promotional pop-up using the native dialog element, opened with two lines of JavaScript, closed by a form with method=dialog, with a blurred backdrop.

Learning goals

- Use <dialog> and showModal()
- Close a dialog with method="dialog"
- Style ::backdrop

Elements and CSS used

HTML elements	CSS features
button, dialog, form method=dialog, h2, p, strong, script	::backdrop, backdrop-filter, box-shadow, border-radius

Build guide

1. Write the page with an open button and a <dialog>.
2. Inside the dialog, wrap the content in <form method="dialog"> with a close button.
3. Add the script that calls showModal() on click.
4. Remove the default border and round the dialog.
5. Style ::backdrop.
6. Test: Escape closes it; focus is trapped inside.

Project 694: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - Offer</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Suez Auto Service</h1>
    <p>Honest car servicing and repairs.</p>
    <button type="button" id="open">See this week's offer</button>
    <dialog id="offer">
      <form method="dialog">
        <h2>This week only</h2>
        <p><strong>Oil change</strong> for 600 EGP: 20 percent off
with the code WEB20.</p>
        <button value="close">Close</button>
      </form>
    </dialog>
  </main>
  <script>
    const dlg = document.getElementById('offer');
    document.getElementById('open').addEventListener('click', () =>
dlg.showModal());
  </script>
</body>
</html>
```

Project 694: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 3rem auto; padding: 0 1rem; }
button { padding: .7rem 1.3rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
dialog { border: 0; border-radius: 16px; padding: 2rem; max-width:
26rem; box-shadow: 0 20px 60px rgb(0 0 0 / 30%); }
dialog::backdrop { background: rgb(0 0 0 / 50%); backdrop-filter:
blur(2px); }
dialog h2 { margin-top: 0; color: var(--brand); }
```

Project 694 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - Offer</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Suez Auto Service	The main heading; only one per page.
Honest car servicing and repairs.	A paragraph of text.
<button type="button" id="open">See this week's offer</button>	A clickable button; inside a form it submits by default.
<dialog id="offer">	A dialog box; showModal() opens it as a modal.
<form method="dialog">	A form; action is where the data goes, method how it is sent.
This week only	Second-level heading for a section.

Line	What it does
<p>Oil change for 600 EGP: 20 percent off with the...	Strong importance (bold by default).
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
background: var(--brand);	Background colour or image.
font: inherit;	Makes form controls use the page font instead of the browser default.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 16px;	Rounds the corners.
box-shadow: 0 20px 60px rgb(0 0 0 / 30%);	Soft shadow that lifts the element from the page.
dialog::backdrop {	The dimmed layer behind a modal dialog.
backdrop-filter: blur(2px);	Blurs or filters whatever is behind the element.

Check your work

- Escape key closes
- Focus moves into the dialog
- Background is not clickable
- Close button visible

Exercises

1. Open the dialog automatically after 5 seconds, once per visit (localStorage).
2. Animate the entrance with @starting-style.
3. Add a form inside and read the returnValue.

Theme data for this project

Field	Value
Business	Suez Auto Service

Field	Value
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 695: Modal dialog for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 3 | Files: index.html, styles.css

Brief

Show a promotional pop-up using the native dialog element, opened with two lines of JavaScript, closed by a form with method=dialog, with a blurred backdrop.

Learning goals

- Use <dialog> and showModal()
- Close a dialog with method="dialog"
- Style ::backdrop

Elements and CSS used

HTML elements	CSS features
button, dialog, form method=dialog, h2, p, strong, script	::backdrop, backdrop-filter, box-shadow, border-radius

Build guide

1. Write the page with an open button and a <dialog>.
2. Inside the dialog, wrap the content in <form method="dialog"> with a close button.
3. Add the script that calls showModal() on click.
4. Remove the default border and round the dialog.
5. Style ::backdrop.
6. Test: Escape closes it; focus is trapped inside.

Project 695: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - Offer</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Luxor Music Academy</h1>
    <p>Oud, piano, guitar and voice lessons.</p>
    <button type="button" id="open">See this week's offer</button>
    <dialog id="offer">
      <form method="dialog">
        <h2>This week only</h2>
        <p><strong>Oud for beginners</strong> for 1600 EGP: 20
percent off with the code WEB20.</p>
        <button value="close">Close</button>
      </form>
    </dialog>
  </main>
  <script>
    const dlg = document.getElementById('offer');
    document.getElementById('open').addEventListener('click', () =>
dlg.showModal());
  </script>
</body>
</html>
```

Project 695: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 3rem auto; padding: 0 1rem; }
button { padding: .7rem 1.3rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
dialog { border: 0; border-radius: 16px; padding: 2rem; max-width:
26rem; box-shadow: 0 20px 60px rgb(0 0 0 / 30%); }
dialog::backdrop { background: rgb(0 0 0 / 50%); backdrop-filter:
blur(2px); }
dialog h2 { margin-top: 0; color: var(--brand); }
```

Project 695 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - Offer</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Luxor Music Academy	The main heading; only one per page.
Oud, piano, guitar and voice lessons.	A paragraph of text.
<button type="button" id="open">See this week's offer</button>	A clickable button; inside a form it submits by default.
<dialog id="offer">	A dialog box; showModal() opens it as a modal.
<form method="dialog">	A form; action is where the data goes, method how it is sent.
This week only	Second-level heading for a section.

Line	What it does
<p>Oud for beginners for 1600 EGP: 20 percent off ...	Strong importance (bold by default).
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
background: var(--brand);	Background colour or image.
font: inherit;	Makes form controls use the page font instead of the browser default.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 16px;	Rounds the corners.
box-shadow: 0 20px 60px rgb(0 0 0 / 30%);	Soft shadow that lifts the element from the page.
dialog::backdrop {	The dimmed layer behind a modal dialog.
backdrop-filter: blur(2px);	Blurs or filters whatever is behind the element.

Check your work

- Escape key closes
- Focus moves into the dialog
- Background is not clickable
- Close button visible

Exercises

1. Open the dialog automatically after 5 seconds, once per visit (localStorage).
2. Animate the entrance with @starting-style.
3. Add a form inside and read the returnValue.

Theme data for this project

Field	Value
Business	Luxor Music Academy

Field	Value
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 696: Modal dialog for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 3 | Files: index.html, styles.css

Brief

Show a promotional pop-up using the native dialog element, opened with two lines of JavaScript, closed by a form with method=dialog, with a blurred backdrop.

Learning goals

- Use <dialog> and showModal()
- Close a dialog with method="dialog"
- Style ::backdrop

Elements and CSS used

HTML elements	CSS features
button, dialog, form method=dialog, h2, p, strong, script	::backdrop, backdrop-filter, box-shadow, border-radius

Build guide

1. Write the page with an open button and a <dialog>.
2. Inside the dialog, wrap the content in <form method="dialog"> with a close button.
3. Add the script that calls showModal() on click.
4. Remove the default border and round the dialog.
5. Style ::backdrop.
6. Test: Escape closes it; focus is trapped inside.

Project 696: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - Offer</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Port Said Seafood</h1>
    <p>Grilled fish straight from the boats.</p>
    <button type="button" id="open">See this week's offer</button>
    <dialog id="offer">
      <form method="dialog">
        <h2>This week only</h2>
        <p><strong>Grilled sea bass</strong> for 320 EGP: 20 percent
off with the code WEB20.</p>
        <button value="close">Close</button>
      </form>
    </dialog>
  </main>
  <script>
    const dlg = document.getElementById('offer');
    document.getElementById('open').addEventListener('click', () =>
dlg.showModal());
  </script>
</body>
</html>
```

Project 696: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 3rem auto; padding: 0 1rem; }
button { padding: .7rem 1.3rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
dialog { border: 0; border-radius: 16px; padding: 2rem; max-width:
26rem; box-shadow: 0 20px 60px rgb(0 0 0 / 30%); }
dialog::backdrop { background: rgb(0 0 0 / 50%); backdrop-filter:
blur(2px); }
dialog h2 { margin-top: 0; color: var(--brand); }
```

Project 696 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - Offer</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Port Said Seafood	The main heading; only one per page.
Grilled fish straight from the boats.	A paragraph of text.
<button type="button" id="open">See this week's offer</button>	A clickable button; inside a form it submits by default.
<dialog id="offer">	A dialog box; showModal() opens it as a modal.
<form method="dialog">	A form; action is where the data goes, method how it is sent.
This week only	Second-level heading for a section.

Line	What it does
<p>Grilled sea bass for 320 EGP: 20 percent off wi...	Strong importance (bold by default).
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
background: var(--brand);	Background colour or image.
font: inherit;	Makes form controls use the page font instead of the browser default.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 16px;	Rounds the corners.
box-shadow: 0 20px 60px rgb(0 0 0 / 30%);	Soft shadow that lifts the element from the page.
dialog::backdrop {	The dimmed layer behind a modal dialog.
backdrop-filter: blur(2px);	Blurs or filters whatever is behind the element.

Check your work

- Escape key closes
- Focus moves into the dialog
- Background is not clickable
- Close button visible

Exercises

1. Open the dialog automatically after 5 seconds, once per visit (localStorage).
2. Animate the entrance with @starting-style.
3. Add a form inside and read the returnValue.

Theme data for this project

Field	Value
Business	Port Said Seafood

Field	Value
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 697: Modal dialog for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 3 | Files: index.html, styles.css

Brief

Show a promotional pop-up using the native dialog element, opened with two lines of JavaScript, closed by a form with method=dialog, with a blurred backdrop.

Learning goals

- Use <dialog> and showModal()
- Close a dialog with method="dialog"
- Style ::backdrop

Elements and CSS used

HTML elements	CSS features
button, dialog, form method=dialog, h2, p, strong, script	::backdrop, backdrop-filter, box-shadow, border-radius

Build guide

1. Write the page with an open button and a <dialog>.
2. Inside the dialog, wrap the content in <form method="dialog"> with a close button.
3. Add the script that calls showModal() on click.
4. Remove the default border and round the dialog.
5. Style ::backdrop.
6. Test: Escape closes it; focus is trapped inside.

Project 697: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - Offer</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Delta Kids Library</h1>
    <p>Stories, reading clubs and homework help.</p>
    <button type="button" id="open">See this week's offer</button>
    <dialog id="offer">
      <form method="dialog">
        <h2>This week only</h2>
        <p><strong>Story hour</strong> for Free: 20 percent off with
the code WEB20.</p>
        <button value="close">Close</button>
      </form>
    </dialog>
  </main>
  <script>
    const dlg = document.getElementById('offer');
    document.getElementById('open').addEventListener('click', () =>
dlg.showModal());
  </script>
</body>
</html>
```

Project 697: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 3rem auto; padding: 0 1rem; }
button { padding: .7rem 1.3rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
dialog { border: 0; border-radius: 16px; padding: 2rem; max-width:
26rem; box-shadow: 0 20px 60px rgb(0 0 0 / 30%); }
dialog::backdrop { background: rgb(0 0 0 / 50%); backdrop-filter:
blur(2px); }
dialog h2 { margin-top: 0; color: var(--brand); }
```

Project 697 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - Offer</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Delta Kids Library	The main heading; only one per page.
Stories, reading clubs and homework help.	A paragraph of text.
<button type="button" id="open">See this week's offer</button>	A clickable button; inside a form it submits by default.
<dialog id="offer">	A dialog box; showModal() opens it as a modal.
<form method="dialog">	A form; action is where the data goes, method how it is sent.
This week only	Second-level heading for a section.

Line	What it does
<p>Story hour for Free: 20 percent off with the co...	Strong importance (bold by default).
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
background: var(--brand);	Background colour or image.
font: inherit;	Makes form controls use the page font instead of the browser default.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 16px;	Rounds the corners.
box-shadow: 0 20px 60px rgb(0 0 0 / 30%);	Soft shadow that lifts the element from the page.
dialog::backdrop {	The dimmed layer behind a modal dialog.
backdrop-filter: blur(2px);	Blurs or filters whatever is behind the element.

Check your work

- Escape key closes
- Focus moves into the dialog
- Background is not clickable
- Close button visible

Exercises

1. Open the dialog automatically after 5 seconds, once per visit (localStorage).
2. Animate the entrance with @starting-style.
3. Add a form inside and read the returnValue.

Theme data for this project

Field	Value
Business	Delta Kids Library

Field	Value
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 698: Modal dialog for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 3 | Files: index.html, styles.css

Brief

Show a promotional pop-up using the native dialog element, opened with two lines of JavaScript, closed by a form with method=dialog, with a blurred backdrop.

Learning goals

- Use <dialog> and showModal()
- Close a dialog with method="dialog"
- Style ::backdrop

Elements and CSS used

HTML elements	CSS features
button, dialog, form method=dialog, h2, p, strong, script	::backdrop, backdrop-filter, box-shadow, border-radius

Build guide

1. Write the page with an open button and a <dialog>.
2. Inside the dialog, wrap the content in <form method="dialog"> with a close button.
3. Add the script that calls showModal() on click.
4. Remove the default border and round the dialog.
5. Style ::backdrop.
6. Test: Escape closes it; focus is trapped inside.

Project 698: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - Offer</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Nubian Guest House</h1>
    <p>Colourful rooms on the west bank of the Nile.</p>
    <button type="button" id="open">See this week's offer</button>
    <dialog id="offer">
      <form method="dialog">
        <h2>This week only</h2>
        <p><strong>Garden room</strong> for 900 EGP: 20 percent off
with the code WEB20.</p>
        <button value="close">Close</button>
      </form>
    </dialog>
  </main>
  <script>
    const dlg = document.getElementById('offer');
    document.getElementById('open').addEventListener('click', () =>
dlg.showModal());
  </script>
</body>
</html>
```

Project 698: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 3rem auto; padding: 0 1rem; }
button { padding: .7rem 1.3rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
dialog { border: 0; border-radius: 16px; padding: 2rem; max-width:
26rem; box-shadow: 0 20px 60px rgb(0 0 0 / 30%); }
dialog::backdrop { background: rgb(0 0 0 / 50%); backdrop-filter:
blur(2px); }
dialog h2 { margin-top: 0; color: var(--brand); }
```

Project 698 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - Offer</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Nubian Guest House	The main heading; only one per page.
Colourful rooms on the west bank of the Nile.	A paragraph of text.
<button type="button" id="open">See this week's offer</button>	A clickable button; inside a form it submits by default.
<dialog id="offer">	A dialog box; showModal() opens it as a modal.
<form method="dialog">	A form; action is where the data goes, method how it is sent.
This week only	Second-level heading for a section.

Line	What it does
<p>Garden room for 900 EGP: 20 percent off with th...	Strong importance (bold by default).
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
background: var(--brand);	Background colour or image.
font: inherit;	Makes form controls use the page font instead of the browser default.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 16px;	Rounds the corners.
box-shadow: 0 20px 60px rgb(0 0 0 / 30%);	Soft shadow that lifts the element from the page.
dialog::backdrop {	The dimmed layer behind a modal dialog.
backdrop-filter: blur(2px);	Blurs or filters whatever is behind the element.

Check your work

- Escape key closes
- Focus moves into the dialog
- Background is not clickable
- Close button visible

Exercises

1. Open the dialog automatically after 5 seconds, once per visit (localStorage).
2. Animate the entrance with @starting-style.
3. Add a form inside and read the returnValue.

Theme data for this project

Field	Value
Business	Nubian Guest House

Field	Value
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 699: Modal dialog for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 3 | Files: index.html, styles.css

Brief

Show a promotional pop-up using the native dialog element, opened with two lines of JavaScript, closed by a form with method=dialog, with a blurred backdrop.

Learning goals

- Use <dialog> and showModal()
- Close a dialog with method="dialog"
- Style ::backdrop

Elements and CSS used

HTML elements	CSS features
button, dialog, form method=dialog, h2, p, strong, script	::backdrop, backdrop-filter, box-shadow, border-radius

Build guide

1. Write the page with an open button and a <dialog>.
2. Inside the dialog, wrap the content in <form method="dialog"> with a close button.
3. Add the script that calls showModal() on click.
4. Remove the default border and round the dialog.
5. Style ::backdrop.
6. Test: Escape closes it; focus is trapped inside.

Project 699: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - Offer</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Ismailia Cycling Store</h1>
    <p>Bikes, parts and Friday group rides.</p>
    <button type="button" id="open">See this week's offer</button>
    <dialog id="offer">
      <form method="dialog">
        <h2>This week only</h2>
        <p><strong>City bike</strong> for 6500 EGP: 20 percent off
with the code WEB20.</p>
        <button value="close">Close</button>
      </form>
    </dialog>
  </main>
  <script>
    const dlg = document.getElementById('offer');
    document.getElementById('open').addEventListener('click', () =>
dlg.showModal());
  </script>
</body>
</html>
```

Project 699: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 3rem auto; padding: 0 1rem; }
button { padding: .7rem 1.3rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
dialog { border: 0; border-radius: 16px; padding: 2rem; max-width:
26rem; box-shadow: 0 20px 60px rgb(0 0 0 / 30%); }
dialog::backdrop { background: rgb(0 0 0 / 50%); backdrop-filter:
blur(2px); }
dialog h2 { margin-top: 0; color: var(--brand); }
```

Project 699 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - Offer</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Ismailia Cycling Store	The main heading; only one per page.
Bikes, parts and Friday group rides.	A paragraph of text.
<button type="button" id="open">See this week's offer</button>	A clickable button; inside a form it submits by default.
<dialog id="offer">	A dialog box; showModal() opens it as a modal.
<form method="dialog">	A form; action is where the data goes, method how it is sent.
This week only	Second-level heading for a section.

Line	What it does
<p>City bike for 6500 EGP: 20 percent off with the...	Strong importance (bold by default).
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
background: var(--brand);	Background colour or image.
font: inherit;	Makes form controls use the page font instead of the browser default.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 16px;	Rounds the corners.
box-shadow: 0 20px 60px rgb(0 0 0 / 30%);	Soft shadow that lifts the element from the page.
dialog::backdrop {	The dimmed layer behind a modal dialog.
backdrop-filter: blur(2px);	Blurs or filters whatever is behind the element.

Check your work

- Escape key closes
- Focus moves into the dialog
- Background is not clickable
- Close button visible

Exercises

1. Open the dialog automatically after 5 seconds, once per visit (localStorage).
2. Animate the entrance with @starting-style.
3. Add a form inside and read the returnValue.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store

Field	Value
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 700: Modal dialog for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 3 | Files: index.html, styles.css

Brief

Show a promotional pop-up using the native dialog element, opened with two lines of JavaScript, closed by a form with method=dialog, with a blurred backdrop.

Learning goals

- Use <dialog> and showModal()
- Close a dialog with method="dialog"
- Style ::backdrop

Elements and CSS used

HTML elements	CSS features
button, dialog, form method=dialog, h2, p, strong, script	::backdrop, backdrop-filter, box-shadow, border-radius

Build guide

1. Write the page with an open button and a <dialog>.
2. Inside the dialog, wrap the content in <form method="dialog"> with a close button.
3. Add the script that calls showModal() on click.
4. Remove the default border and round the dialog.
5. Style ::backdrop.
6. Test: Escape closes it; focus is trapped inside.

Project 700: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - Offer</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Minya Coding Club</h1>
    <p>Free weekend coding for teenagers.</p>
    <button type="button" id="open">See this week's offer</button>
    <dialog id="offer">
      <form method="dialog">
        <h2>This week only</h2>
        <p><strong>HTML weekend</strong> for Free: 20 percent off
with the code WEB20.</p>
        <button value="close">Close</button>
      </form>
    </dialog>
  </main>
  <script>
    const dlg = document.getElementById('offer');
    document.getElementById('open').addEventListener('click', () =>
dlg.showModal());
  </script>
</body>
</html>
```

Project 700: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 3rem auto; padding: 0 1rem; }
button { padding: .7rem 1.3rem; border: 0; border-radius: 999px;
background: var(--brand); color: #fff; font: inherit; cursor: pointer;
 }
dialog { border: 0; border-radius: 16px; padding: 2rem; max-width:
26rem; box-shadow: 0 20px 60px rgb(0 0 0 / 30%); }
dialog::backdrop { background: rgb(0 0 0 / 50%); backdrop-filter:
blur(2px); }
dialog h2 { margin-top: 0; color: var(--brand); }
```

Project 700 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - Offer</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Minya Coding Club	The main heading; only one per page.
Free weekend coding for teenagers.	A paragraph of text.
<button type="button" id="open">See this week's offer</button>	A clickable button; inside a form it submits by default.
<dialog id="offer">	A dialog box; showModal() opens it as a modal.
<form method="dialog">	A form; action is where the data goes, method how it is sent.
This week only	Second-level heading for a section.

Line	What it does
<p>HTML weekend for Free: 20 percent off with the …	Strong importance (bold by default).
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
background: var(--brand);	Background colour or image.
font: inherit;	Makes form controls use the page font instead of the browser default.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 16px;	Rounds the corners.
box-shadow: 0 20px 60px rgb(0 0 0 / 30%);	Soft shadow that lifts the element from the page.
dialog::backdrop {	The dimmed layer behind a modal dialog.
backdrop-filter: blur(2px);	Blurs or filters whatever is behind the element.

Check your work

- Escape key closes
- Focus moves into the dialog
- Background is not clickable
- Close button visible

Exercises

1. Open the dialog automatically after 5 seconds, once per visit (localStorage).
2. Animate the entrance with @starting-style.
3. Add a form inside and read the returnValue.

Theme data for this project

Field	Value
Business	Minya Coding Club

Field	Value
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Search bar and results page

Level 2 | 25 projects, one per theme

Build a header search box with datalist suggestions and a joined input/button pair, plus a results list styled like a search engine.

Project 701: Search bar and results page for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 2 | Files: index.html, styles.css

Brief

Build a header search box with datalist suggestions and a joined input/button pair, plus a results list styled like a search engine.

Learning goals

- Use the search element, type=search and datalist
- Join an input and button with asymmetric border-radius
- Present results as an ordered list

Elements and CSS used

HTML elements	CSS features
search, form, label, input type=search, datalist, option, button, ol, li, a, q	flex: 1 1 18rem, border-radius (four values), border-right: 0, list-style: none

Build guide

1. Write the header with logo and <search> containing the form.
2. Add a datalist with one option per offer and link it with list=.
3. Add the results list.
4. Flex the bar; let the search area grow.
5. Round only the outer corners of input and button.

6. Style the results.

Project 701: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Search</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="bar">
    <a class="logo" href="index.html">Cairo Book Shop</a>
    <search>
      <form action="/search" role="search">
        <label for="q" class="sr-only">Search books</label>
        <input id="q" name="q" type="search" placeholder="Search
books" list="suggest" autocomplete="off">
        <datalist id="suggest">
    <option value="Learn HTML">
    <option value="CSS in Practice">
    <option value="JavaScript Basics">
    <option value="Web Accessibility">
        </datalist>
        <button>Go</button>
      </form>
    </search>
  </header>
  <main>
    <h1>Search results</h1>
    <p>3 results for <q>book</q></p>
    <ol class="results">
    <li><a href="#">Learn HTML</a><p>From your first tag to a
complete page.</p></li>
    <li><a href="#">CSS in Practice</a><p>Layouts, colours and
typography.</p></li>
    <li><a href="#">JavaScript Basics</a><p>Make pages interactive.</
p></li>
    </ol>
  </main>
</body>
</html>
```

Project 701: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
```

```
height: 1.6; color: var(--ink); }
.bar { display: flex; gap: 1rem; align-items: center; padding: .75rem
1.5rem; background: var(--accent); flex-wrap: wrap; }
.logo { font-weight: 700; text-decoration: none; color: var(--brand);
}
search { flex: 1 1 18rem; }
form { display: flex; }
input { flex: 1; padding: .6rem .9rem; border: 1px solid #bbb; border-
right: 0; border-radius: 999px 0 0 999px; font: inherit; }
button { padding: .6rem 1rem; border: 0; border-radius: 0 999px 999px
0; background: var(--brand); color: #fff; font: inherit; }
main { max-width: 40rem; margin: 1.5rem auto; padding: 0 1rem; }
.results { list-style: none; padding: 0; }
.results li { padding: 1rem 0; border-bottom: 1px solid var(--line); }
.results a { font-size: 1.1rem; font-weight: 600; }
.results p { margin: .2rem 0 0; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 701 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - Search</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="bar">	Introductory content: logo, title, navigation.
<search>	Container for search functionality.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q" class="sr-only">Search books</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search" placeholder="Search books" lis...	Search field.
<datalist id="suggest">	Suggestions for an input linked with the list attribute.
<option value="Learn HTML">	One choice in a select or datalist.

Line	What it does
<button>Go</button>	A clickable button; inside a form it submits by default.
<main>	The unique content of this page; exactly one per page.
Search results	The main heading; only one per page.
3 results for <q>book</q>	A paragraph of text.
<ol class="results">	Ordered (numbered) list; the order matters.
Learn HTML From your first tag to a complete ...	A hyperlink; href gives the destination.
CSS in Practice Layouts, colours and typograp...	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
align-items: center;	Centres items on the cross axis.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--accent);	Background colour or image.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
font-weight: 700;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
flex: 1 1 18rem;	The item can grow and shrink from the given basis.
flex: 1;	All items share free space equally.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-right: 0;	The line around the element: width, style and colour.
border-radius: 999px 0 0 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).

Declaration	What it does
border-radius: 0 999px 999px 0;	Rounds the corners.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-size: 1.1rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Typing shows suggestions
- Label exists (hidden)
- Button attached to input visually
- Results are links with descriptions

Exercises

1. Highlight the matched word in results with <mark>.
2. Add filters with checkboxes in an aside.
3. Add 'no results' state styling.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 702: Search bar and results page for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 2 | Files: index.html, styles.css

Brief

Build a header search box with datalist suggestions and a joined input/button pair, plus a results list styled like a search engine.

Learning goals

- Use the search element, type=search and datalist
- Join an input and button with asymmetric border-radius
- Present results as an ordered list

Elements and CSS used

HTML elements	CSS features
search, form, label, input type=search, datalist, option, button, ol, li, a, q	flex: 1 1 18rem, border-radius (four values), border-right: 0, list-style: none

Build guide

1. Write the header with logo and <search> containing the form.
2. Add a datalist with one option per offer and link it with list=.
3. Add the results list.
4. Flex the bar; let the search area grow.
5. Round only the outer corners of input and button.
6. Style the results.

Project 702: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - Search</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="bar">
    <a class="logo" href="index.html">Nile Bakery</a>
    <search>
      <form action="/search" role="search">
        <label for="q" class="sr-only">Search pastries</label>
        <input id="q" name="q" type="search" placeholder="Search
pastries" list="suggest" autocomplete="off">
        <datalist id="suggest">
    <option value="Sourdough loaf">
    <option value="Croissant">
    <option value="Date cookies">
    <option value="Baklava box">
        </datalist>
        <button>Go</button>
      </form>
    </search>
  </header>
  <main>
    <h1>Search results</h1>
    <p>3 results for <q>pastry</q></p>
    <ol class="results">
    <li><a href="#">Sourdough loaf</a><p>Slow fermented, crisp crust.
</p></li>
    <li><a href="#">Croissant</a><p>Butter, 27 layers.</p></li>
    <li><a href="#">Date cookies</a><p>Traditional maamoul style.</
p></li>
    </ol>
  </main>
</body>
</html>
```

Project 702: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
.bar { display: flex; gap: 1rem; align-items: center; padding: .75rem
1.5rem; background: var(--accent); flex-wrap: wrap; }
.logo { font-weight: 700; text-decoration: none; color: var(--brand);
}
search { flex: 1 1 18rem; }
form { display: flex; }
input { flex: 1; padding: .6rem .9rem; border: 1px solid #bbb; border-
right: 0; border-radius: 999px 0 0 999px; font: inherit; }
button { padding: .6rem 1rem; border: 0; border-radius: 0 999px 999px
0; background: var(--brand); color: #fff; font: inherit; }
main { max-width: 40rem; margin: 1.5rem auto; padding: 0 1rem; }
.results { list-style: none; padding: 0; }
.results li { padding: 1rem 0; border-bottom: 1px solid var(--line); }
.results a { font-size: 1.1rem; font-weight: 600; }
.results p { margin: .2rem 0 0; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 702 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - Search</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="bar">	Introductory content: logo, title, navigation.
<search>	Container for search functionality.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q" class="sr-only">Search pastries</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search" placeholder="Search pastries" ...	Search field.
<datalist id="suggest">	Suggestions for an input linked with the list attribute.
<option value="Sourdough loaf">	One choice in a select or datalist.

Line	What it does
<button>Go</button>	A clickable button; inside a form it submits by default.
<main>	The unique content of this page; exactly one per page.
Search results	The main heading; only one per page.
3 results for <q>pastry</q>	A paragraph of text.
<ol class="results">	Ordered (numbered) list; the order matters.
Sourdough loaf Slow fermented, crisp crust.</...	A hyperlink; href gives the destination.
Croissant Butter, 27 layers.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
align-items: center;	Centres items on the cross axis.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--accent);	Background colour or image.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
font-weight: 700;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
flex: 1 1 18rem;	The item can grow and shrink from the given basis.
flex: 1;	All items share free space equally.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-right: 0;	The line around the element: width, style and colour.
border-radius: 999px 0 0 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).

Declaration	What it does
border-radius: 0 999px 999px 0;	Rounds the corners.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-size: 1.1rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Typing shows suggestions
- Label exists (hidden)
- Button attached to input visually
- Results are links with descriptions

Exercises

1. Highlight the matched word in results with <mark>.
2. Add filters with checkboxes in an aside.
3. Add 'no results' state styling.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 703: Search bar and results page for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 2 | Files: index.html, styles.css

Brief

Build a header search box with datalist suggestions and a joined input/button pair, plus a results list styled like a search engine.

Learning goals

- Use the search element, type=search and datalist
- Join an input and button with asymmetric border-radius
- Present results as an ordered list

Elements and CSS used

HTML elements	CSS features
search, form, label, input type=search, datalist, option, button, ol, li, a, q	flex: 1 1 18rem, border-radius (four values), border-right: 0, list-style: none

Build guide

1. Write the header with logo and <search> containing the form.
2. Add a datalist with one option per offer and link it with list=.
3. Add the results list.
4. Flex the bar; let the search area grow.
5. Round only the outer corners of input and button.

6. Style the results.

Project 703: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - Search</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="bar">
    <a class="logo" href="index.html">Pyramid Fitness</a>
    <search>
      <form action="/search" role="search">
        <label for="q" class="sr-only">Search classes</label>
        <input id="q" name="q" type="search" placeholder="Search
classes" list="suggest" autocomplete="off">
        <datalist id="suggest">
    <option value="Morning yoga">
    <option value="Strength circuit">
    <option value="Spinning">
    <option value="Personal training">
        </datalist>
        <button>Go</button>
      </form>
    </search>
  </header>
  <main>
    <h1>Search results</h1>
    <p>3 results for <q>class</q></p>
    <ol class="results">
    <li><a href="#">Morning yoga</a><p>Flexibility and calm, 60
minutes.</p></li>
    <li><a href="#">Strength circuit</a><p>Full body, all levels.</
p></li>
    <li><a href="#">Spinning</a><p>High energy cycling.</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 703: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
.bar { display: flex; gap: 1rem; align-items: center; padding: .75rem
1.5rem; background: var(--accent); flex-wrap: wrap; }
.logo { font-weight: 700; text-decoration: none; color: var(--brand);
}
search { flex: 1 1 18rem; }
form { display: flex; }
input { flex: 1; padding: .6rem .9rem; border: 1px solid #bbb; border-
right: 0; border-radius: 999px 0 0 999px; font: inherit; }
button { padding: .6rem 1rem; border: 0; border-radius: 0 999px 999px
0; background: var(--brand); color: #fff; font: inherit; }
main { max-width: 40rem; margin: 1.5rem auto; padding: 0 1rem; }
.results { list-style: none; padding: 0; }
.results li { padding: 1rem 0; border-bottom: 1px solid var(--line); }
.results a { font-size: 1.1rem; font-weight: 600; }
.results p { margin: .2rem 0 0; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 703 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - Search</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="bar">	Introductory content: logo, title, navigation.
<search>	Container for search functionality.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q" class="sr-only">Search classes</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search" placeholder="Search classes" l...	Search field.
<datalist id="suggest">	Suggestions for an input linked with the list attribute.
<option value="Morning yoga">	One choice in a select or datalist.

Line	What it does
<button>Go</button>	A clickable button; inside a form it submits by default.
<main>	The unique content of this page; exactly one per page.
Search results	The main heading; only one per page.
3 results for <q>class</q>	A paragraph of text.
<ol class="results">	Ordered (numbered) list; the order matters.
Morning yoga Flexibility and calm, 60 minutes...	A hyperlink; href gives the destination.
Strength circuit Full body, all levels.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
align-items: center;	Centres items on the cross axis.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--accent);	Background colour or image.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
font-weight: 700;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
flex: 1 1 18rem;	The item can grow and shrink from the given basis.
flex: 1;	All items share free space equally.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-right: 0;	The line around the element: width, style and colour.
border-radius: 999px 0 0 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).

Declaration	What it does
border-radius: 0 999px 999px 0;	Rounds the corners.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-size: 1.1rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Typing shows suggestions
- Label exists (hidden)
- Button attached to input visually
- Results are links with descriptions

Exercises

1. Highlight the matched word in results with <mark>.
2. Add filters with checkboxes in an aside.
3. Add 'no results' state styling.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 704: Search bar and results page for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 2 | Files: index.html, styles.css

Brief

Build a header search box with datalist suggestions and a joined input/button pair, plus a results list styled like a search engine.

Learning goals

- Use the search element, type=search and datalist
- Join an input and button with asymmetric border-radius
- Present results as an ordered list

Elements and CSS used

HTML elements	CSS features
search, form, label, input type=search, datalist, option, button, ol, li, a, q	flex: 1 1 18rem, border-radius (four values), border-right: 0, list-style: none

Build guide

1. Write the header with logo and <search> containing the form.
2. Add a datalist with one option per offer and link it with list=.
3. Add the results list.
4. Flex the bar; let the search area grow.
5. Round only the outer corners of input and button.

6. Style the results.

Project 704: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - Search</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="bar">
    <a class="logo" href="index.html">Delta Dental Clinic</a>
    <search>
      <form action="/search" role="search">
        <label for="q" class="sr-only">Search services</label>
        <input id="q" name="q" type="search" placeholder="Search
services" list="suggest" autocomplete="off">
        <datalist id="suggest">
    <option value="Check-up">
    <option value="Whitening">
    <option value="Filling">
    <option value="Braces consultation">
        </datalist>
        <button>Go</button>
      </form>
    </search>
  </header>
  <main>
    <h1>Search results</h1>
    <p>3 results for <q>service</q></p>
    <ol class="results">
    <li><a href="#">Check-up</a><p>Examination and cleaning.</p></li>
    <li><a href="#">Whitening</a><p>Brighter smile in one visit.</p></
li>
    <li><a href="#">Filling</a><p>Tooth-coloured composite.</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 704: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.bar { display: flex; gap: 1rem; align-items: center; padding: .75rem
```

```
1.5rem; background: var(--accent); flex-wrap: wrap; }
.logo { font-weight: 700; text-decoration: none; color: var(--brand);
}
search { flex: 1 1 18rem; }
form { display: flex; }
input { flex: 1; padding: .6rem .9rem; border: 1px solid #bbb; border-
right: 0; border-radius: 999px 0 0 999px; font: inherit; }
button { padding: .6rem 1rem; border: 0; border-radius: 0 999px 999px
0; background: var(--brand); color: #fff; font: inherit; }
main { max-width: 40rem; margin: 1.5rem auto; padding: 0 1rem; }
.results { list-style: none; padding: 0; }
.results li { padding: 1rem 0; border-bottom: 1px solid var(--line); }
.results a { font-size: 1.1rem; font-weight: 600; }
.results p { margin: .2rem 0 0; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 704 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - Search</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="bar">	Introductory content: logo, title, navigation.
<search>	Container for search functionality.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q" class="sr-only">Search services</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search" placeholder="Search services" ...	Search field.
<datalist id="suggest">	Suggestions for an input linked with the list attribute.
<option value="Check-up">	One choice in a select or datalist.

Line	What it does
<button>Go</button>	A clickable button; inside a form it submits by default.
<main>	The unique content of this page; exactly one per page.
Search results	The main heading; only one per page.
3 results for <q>service</q>	A paragraph of text.
<ol class="results">	Ordered (numbered) list; the order matters.
Check-up Examination and cleaning.	A hyperlink; href gives the destination.
Whitening Brighter smile in one visit.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
align-items: center;	Centres items on the cross axis.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--accent);	Background colour or image.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
font-weight: 700;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
flex: 1 1 18rem;	The item can grow and shrink from the given basis.
flex: 1;	All items share free space equally.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-right: 0;	The line around the element: width, style and colour.
border-radius: 999px 0 0 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).

Declaration	What it does
border-radius: 0 999px 999px 0;	Rounds the corners.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-size: 1.1rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Typing shows suggestions
- Label exists (hidden)
- Button attached to input visually
- Results are links with descriptions

Exercises

1. Highlight the matched word in results with <mark>.
2. Add filters with checkboxes in an aside.
3. Add 'no results' state styling.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 705: Search bar and results page for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 2 | Files: index.html, styles.css

Brief

Build a header search box with datalist suggestions and a joined input/button pair, plus a results list styled like a search engine.

Learning goals

- Use the search element, type=search and datalist
- Join an input and button with asymmetric border-radius
- Present results as an ordered list

Elements and CSS used

HTML elements	CSS features
search, form, label, input type=search, datalist, option, button, ol, li, a, q	flex: 1 1 18rem, border-radius (four values), border-right: 0, list-style: none

Build guide

1. Write the header with logo and <search> containing the form.
2. Add a datalist with one option per offer and link it with list=.
3. Add the results list.
4. Flex the bar; let the search area grow.
5. Round only the outer corners of input and button.
6. Style the results.

Project 705: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - Search</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="bar">
    <a class="logo" href="index.html">Red Sea Travel</a>
    <search>
      <form action="/search" role="search">
        <label for="q" class="sr-only">Search tours</label>
        <input id="q" name="q" type="search" placeholder="Search
tours" list="suggest" autocomplete="off">
        <datalist id="suggest">
    <option value="Luxor day trip">
    <option value="Snorkelling">
    <option value="Desert safari">
    <option value="Nile cruise">
        </datalist>
        <button>Go</button>
      </form>
    </search>
  </header>
  <main>
    <h1>Search results</h1>
    <p>3 results for <q>tour</q></p>
    <ol class="results">
    <li><a href="#">Luxor day trip</a><p>Karnak, Valley of the Kings.
</p></li>
    <li><a href="#">Snorkelling</a><p>Giftun island reefs.</p></li>
    <li><a href="#">Desert safari</a><p>Quad bikes and Bedouin dinner.
</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 705: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
.bar { display: flex; gap: 1rem; align-items: center; padding: .75rem
1.5rem; background: var(--accent); flex-wrap: wrap; }
.logo { font-weight: 700; text-decoration: none; color: var(--brand);
}
search { flex: 1 1 18rem; }
form { display: flex; }
input { flex: 1; padding: .6rem .9rem; border: 1px solid #bbb; border-
right: 0; border-radius: 999px 0 0 999px; font: inherit; }
button { padding: .6rem 1rem; border: 0; border-radius: 0 999px 999px
0; background: var(--brand); color: #fff; font: inherit; }
main { max-width: 40rem; margin: 1.5rem auto; padding: 0 1rem; }
.results { list-style: none; padding: 0; }
.results li { padding: 1rem 0; border-bottom: 1px solid var(--line); }
.results a { font-size: 1.1rem; font-weight: 600; }
.results p { margin: .2rem 0 0; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 705 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - Search</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="bar">	Introductory content: logo, title, navigation.
<search>	Container for search functionality.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q" class="sr-only">Search tours</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search" placeholder="Search tours" lis...	Search field.
<datalist id="suggest">	Suggestions for an input linked with the list attribute.
<option value="Luxor day trip">	One choice in a select or datalist.

Line	What it does
<button>Go</button>	A clickable button; inside a form it submits by default.
<main>	The unique content of this page; exactly one per page.
Search results	The main heading; only one per page.
3 results for <q>tour</q>	A paragraph of text.
<ol class="results">	Ordered (numbered) list; the order matters.
Luxor day trip Karnak, Valley of the Kings.<//...	A hyperlink; href gives the destination.
Snorkelling Giftun island reefs.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
align-items: center;	Centres items on the cross axis.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--accent);	Background colour or image.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
font-weight: 700;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
flex: 1 1 18rem;	The item can grow and shrink from the given basis.
flex: 1;	All items share free space equally.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-right: 0;	The line around the element: width, style and colour.
border-radius: 999px 0 0 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).

Declaration	What it does
border-radius: 0 999px 999px 0;	Rounds the corners.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-size: 1.1rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Typing shows suggestions
- Label exists (hidden)
- Button attached to input visually
- Results are links with descriptions

Exercises

1. Highlight the matched word in results with <mark>.
2. Add filters with checkboxes in an aside.
3. Add 'no results' state styling.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 706: Search bar and results page for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Build a header search box with datalist suggestions and a joined input/button pair, plus a results list styled like a search engine.

Learning goals

- Use the search element, type=search and datalist
- Join an input and button with asymmetric border-radius
- Present results as an ordered list

Elements and CSS used

HTML elements	CSS features
search, form, label, input type=search, datalist, option, button, ol, li, a, q	flex: 1 1 18rem, border-radius (four values), border-right: 0, list-style: none

Build guide

1. Write the header with logo and <search> containing the form.
2. Add a datalist with one option per offer and link it with list=.
3. Add the results list.
4. Flex the bar; let the search area grow.
5. Round only the outer corners of input and button.

6. Style the results.

Project 706: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - Search</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="bar">
    <a class="logo" href="index.html">Lotus Language School</a>
    <search>
      <form action="/search" role="search">
        <label for="q" class="sr-only">Search courses</label>
        <input id="q" name="q" type="search" placeholder="Search
courses" list="suggest" autocomplete="off">
        <datalist id="suggest">
    <option value="English A1">
    <option value="French B1">
    <option value="German A2">
    <option value="IELTS preparation">
        </datalist>
        <button>Go</button>
      </form>
    </search>
  </header>
  <main>
    <h1>Search results</h1>
    <p>3 results for <q>course</q></p>
    <ol class="results">
    <li><a href="#">English A1</a><p>Beginner, 8 weeks.</p></li>
    <li><a href="#">French B1</a><p>Intermediate conversation.</p></
li>
    <li><a href="#">German A2</a><p>Grammar and speaking.</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 706: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.bar { display: flex; gap: 1rem; align-items: center; padding: .75rem
```

```
1.5rem; background: var(--accent); flex-wrap: wrap; }
.logo { font-weight: 700; text-decoration: none; color: var(--brand);
}
search { flex: 1 1 18rem; }
form { display: flex; }
input { flex: 1; padding: .6rem .9rem; border: 1px solid #bbb; border-
right: 0; border-radius: 999px 0 0 999px; font: inherit; }
button { padding: .6rem 1rem; border: 0; border-radius: 0 999px 999px
0; background: var(--brand); color: #fff; font: inherit; }
main { max-width: 40rem; margin: 1.5rem auto; padding: 0 1rem; }
.results { list-style: none; padding: 0; }
.results li { padding: 1rem 0; border-bottom: 1px solid var(--line); }
.results a { font-size: 1.1rem; font-weight: 600; }
.results p { margin: .2rem 0 0; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 706 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - Search</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="bar">	Introductory content: logo, title, navigation.
<search>	Container for search functionality.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q" class="sr-only">Search courses</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search" placeholder="Search courses" l...	Search field.
<datalist id="suggest">	Suggestions for an input linked with the list attribute.
<option value="English A1">	One choice in a select or datalist.

Line	What it does
<button>Go</button>	A clickable button; inside a form it submits by default.
<main>	The unique content of this page; exactly one per page.
Search results	The main heading; only one per page.
3 results for <q>course</q>	A paragraph of text.
<ol class="results">	Ordered (numbered) list; the order matters.
English A1 Beginner, 8 weeks.	A hyperlink; href gives the destination.
French B1 Intermediate conversation.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
align-items: center;	Centres items on the cross axis.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--accent);	Background colour or image.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
font-weight: 700;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
flex: 1 1 18rem;	The item can grow and shrink from the given basis.
flex: 1;	All items share free space equally.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-right: 0;	The line around the element: width, style and colour.
border-radius: 999px 0 0 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).

Declaration	What it does
border-radius: 0 999px 999px 0;	Rounds the corners.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-size: 1.1rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Typing shows suggestions
- Label exists (hidden)
- Button attached to input visually
- Results are links with descriptions

Exercises

1. Highlight the matched word in results with <mark>.
2. Add filters with checkboxes in an aside.
3. Add 'no results' state styling.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 707: Search bar and results page for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 2 | Files: index.html, styles.css

Brief

Build a header search box with datalist suggestions and a joined input/button pair, plus a results list styled like a search engine.

Learning goals

- Use the search element, type=search and datalist
- Join an input and button with asymmetric border-radius
- Present results as an ordered list

Elements and CSS used

HTML elements	CSS features
search, form, label, input type=search, datalist, option, button, ol, li, a, q	flex: 1 1 18rem, border-radius (four values), border-right: 0, list-style: none

Build guide

1. Write the header with logo and <search> containing the form.
2. Add a datalist with one option per offer and link it with list=.
3. Add the results list.
4. Flex the bar; let the search area grow.
5. Round only the outer corners of input and button.

6. Style the results.

Project 707: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - Search</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="bar">
    <a class="logo" href="index.html">Green Leaf Cafe</a>
    <search>
      <form action="/search" role="search">
        <label for="q" class="sr-only">Search drinks</label>
        <input id="q" name="q" type="search" placeholder="Search
drinks" list="suggest" autocomplete="off">
        <datalist id="suggest">
    <option value="Flat white">
    <option value="Cold brew">
    <option value="Hibiscus iced tea">
    <option value="Cheesecake">
        </datalist>
        <button>Go</button>
      </form>
    </search>
  </header>
  <main>
    <h1>Search results</h1>
    <p>3 results for <q>drink</q></p>
    <ol class="results">
    <li><a href="#">Flat white</a><p>Double shot, silky milk.</p></li>
    <li><a href="#">Cold brew</a><p>18 hours steeped.</p></li>
    <li><a href="#">Hibiscus iced tea</a><p>Karkade with mint.</p></
li>
    </ol>
  </main>
</body>
</html>
```

Project 707: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.bar { display: flex; gap: 1rem; align-items: center; padding: .75rem
```

```
1.5rem; background: var(--accent); flex-wrap: wrap; }
.logo { font-weight: 700; text-decoration: none; color: var(--brand);
}
search { flex: 1 1 18rem; }
form { display: flex; }
input { flex: 1; padding: .6rem .9rem; border: 1px solid #bbb; border-
right: 0; border-radius: 999px 0 0 999px; font: inherit; }
button { padding: .6rem 1rem; border: 0; border-radius: 0 999px 999px
0; background: var(--brand); color: #fff; font: inherit; }
main { max-width: 40rem; margin: 1.5rem auto; padding: 0 1rem; }
.results { list-style: none; padding: 0; }
.results li { padding: 1rem 0; border-bottom: 1px solid var(--line); }
.results a { font-size: 1.1rem; font-weight: 600; }
.results p { margin: .2rem 0 0; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 707 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - Search</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="bar">	Introductory content: logo, title, navigation.
<search>	Container for search functionality.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q" class="sr-only">Search drinks</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search" placeholder="Search drinks" li...	Search field.
<datalist id="suggest">	Suggestions for an input linked with the list attribute.
<option value="Flat white">	One choice in a select or datalist.

Line	What it does
<button>Go</button>	A clickable button; inside a form it submits by default.
<main>	The unique content of this page; exactly one per page.
Search results	The main heading; only one per page.
3 results for <q>drink</q>	A paragraph of text.
<ol class="results">	Ordered (numbered) list; the order matters.
Flat white Double shot, silky milk.	A hyperlink; href gives the destination.
Cold brew 18 hours steeped.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
align-items: center;	Centres items on the cross axis.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--accent);	Background colour or image.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
font-weight: 700;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
flex: 1 1 18rem;	The item can grow and shrink from the given basis.
flex: 1;	All items share free space equally.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-right: 0;	The line around the element: width, style and colour.
border-radius: 999px 0 0 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).

Declaration	What it does
border-radius: 0 999px 999px 0;	Rounds the corners.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-size: 1.1rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Typing shows suggestions
- Label exists (hidden)
- Button attached to input visually
- Results are links with descriptions

Exercises

1. Highlight the matched word in results with <mark>.
2. Add filters with checkboxes in an aside.
3. Add 'no results' state styling.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 708: Search bar and results page for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 2 | Files: index.html, styles.css

Brief

Build a header search box with datalist suggestions and a joined input/button pair, plus a results list styled like a search engine.

Learning goals

- Use the search element, type=search and datalist
- Join an input and button with asymmetric border-radius
- Present results as an ordered list

Elements and CSS used

HTML elements	CSS features
search, form, label, input type=search, datalist, option, button, ol, li, a, q	flex: 1 1 18rem, border-radius (four values), border-right: 0, list-style: none

Build guide

1. Write the header with logo and <search> containing the form.
2. Add a datalist with one option per offer and link it with list=.
3. Add the results list.
4. Flex the bar; let the search area grow.
5. Round only the outer corners of input and button.

6. Style the results.

Project 708: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - Search</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="bar">
    <a class="logo" href="index.html">Sinai Trekking Club</a>
    <search>
      <form action="/search" role="search">
        <label for="q" class="sr-only">Search hikes</label>
        <input id="q" name="q" type="search" placeholder="Search
hikes" list="suggest" autocomplete="off">
        <datalist id="suggest">
    <option value="Mount Sinai sunrise">
    <option value="Blue Desert loop">
    <option value="Wadi Gnai">
    <option value="Three-day traverse">
        </datalist>
        <button>Go</button>
      </form>
    </search>
  </header>
  <main>
    <h1>Search results</h1>
    <p>3 results for <q>hike</q></p>
    <ol class="results">
    <li><a href="#">Mount Sinai sunrise</a><p>Night climb, 7 km.</p></
li>
    <li><a href="#">Blue Desert loop</a><p>Easy day walk.</p></li>
    <li><a href="#">Wadi Gnai</a><p>Palms and pools.</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 708: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.bar { display: flex; gap: 1rem; align-items: center; padding: .75rem
```

```
1.5rem; background: var(--accent); flex-wrap: wrap; }
.logo { font-weight: 700; text-decoration: none; color: var(--brand);
}
search { flex: 1 1 18rem; }
form { display: flex; }
input { flex: 1; padding: .6rem .9rem; border: 1px solid #bbb; border-
right: 0; border-radius: 999px 0 0 999px; font: inherit; }
button { padding: .6rem 1rem; border: 0; border-radius: 0 999px 999px
0; background: var(--brand); color: #fff; font: inherit; }
main { max-width: 40rem; margin: 1.5rem auto; padding: 0 1rem; }
.results { list-style: none; padding: 0; }
.results li { padding: 1rem 0; border-bottom: 1px solid var(--line); }
.results a { font-size: 1.1rem; font-weight: 600; }
.results p { margin: .2rem 0 0; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 708 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - Search</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="bar">	Introductory content: logo, title, navigation.
<search>	Container for search functionality.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q" class="sr-only">Search hikes</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search" placeholder="Search hikes" lis...	Search field.
<datalist id="suggest">	Suggestions for an input linked with the list attribute.
<option value="Mount Sinai sunrise">	One choice in a select or datalist.

Line	What it does
<button>Go</button>	A clickable button; inside a form it submits by default.
<main>	The unique content of this page; exactly one per page.
Search results	The main heading; only one per page.
3 results for <q>hike</q>	A paragraph of text.
<ol class="results">	Ordered (numbered) list; the order matters.
Mount Sinai sunrise Night climb, 7 km.	A hyperlink; href gives the destination.
Blue Desert loop Easy day walk.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
align-items: center;	Centres items on the cross axis.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--accent);	Background colour or image.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
font-weight: 700;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
flex: 1 1 18rem;	The item can grow and shrink from the given basis.
flex: 1;	All items share free space equally.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-right: 0;	The line around the element: width, style and colour.
border-radius: 999px 0 0 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).

Declaration	What it does
border-radius: 0 999px 999px 0;	Rounds the corners.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-size: 1.1rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Typing shows suggestions
- Label exists (hidden)
- Button attached to input visually
- Results are links with descriptions

Exercises

1. Highlight the matched word in results with <mark>.
2. Add filters with checkboxes in an aside.
3. Add 'no results' state styling.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 709: Search bar and results page for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 2 | Files: index.html, styles.css

Brief

Build a header search box with datalist suggestions and a joined input/button pair, plus a results list styled like a search engine.

Learning goals

- Use the search element, type=search and datalist
- Join an input and button with asymmetric border-radius
- Present results as an ordered list

Elements and CSS used

HTML elements	CSS features
search, form, label, input type=search, datalist, option, button, ol, li, a, q	flex: 1 1 18rem, border-radius (four values), border-right: 0, list-style: none

Build guide

1. Write the header with logo and <search> containing the form.
2. Add a datalist with one option per offer and link it with list=.
3. Add the results list.
4. Flex the bar; let the search area grow.
5. Round only the outer corners of input and button.

6. Style the results.

Project 709: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - Search</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="bar">
    <a class="logo" href="index.html">Horizon Photography</a>
    <search>
      <form action="/search" role="search">
        <label for="q" class="sr-only">Search sessions</label>
        <input id="q" name="q" type="search" placeholder="Search
sessions" list="suggest" autocomplete="off">
        <datalist id="suggest">
    <option value="Portrait session">
    <option value="Wedding day">
    <option value="Product shoot">
    <option value="Family session">
        </datalist>
        <button>Go</button>
      </form>
    </search>
  </header>
  <main>
    <h1>Search results</h1>
    <p>3 results for <q>session</q></p>
    <ol class="results">
    <li><a href="#">Portrait session</a><p>One hour, 20 edited photos.
</p></li>
    <li><a href="#">Wedding day</a><p>Full coverage, two
photographers.</p></li>
    <li><a href="#">Product shoot</a><p>White background, 10 items.</
p></li>
    </ol>
  </main>
</body>
</html>
```

Project 709: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
```

```
height: 1.6; color: var(--ink); }
.bar { display: flex; gap: 1rem; align-items: center; padding: .75rem
1.5rem; background: var(--accent); flex-wrap: wrap; }
.logo { font-weight: 700; text-decoration: none; color: var(--brand);
}
search { flex: 1 1 18rem; }
form { display: flex; }
input { flex: 1; padding: .6rem .9rem; border: 1px solid #bbb; border-
right: 0; border-radius: 999px 0 0 999px; font: inherit; }
button { padding: .6rem 1rem; border: 0; border-radius: 0 999px 999px
0; background: var(--brand); color: #fff; font: inherit; }
main { max-width: 40rem; margin: 1.5rem auto; padding: 0 1rem; }
.results { list-style: none; padding: 0; }
.results li { padding: 1rem 0; border-bottom: 1px solid var(--line); }
.results a { font-size: 1.1rem; font-weight: 600; }
.results p { margin: .2rem 0 0; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 709 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - Search</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="bar">	Introductory content: logo, title, navigation.
<search>	Container for search functionality.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q" class="sr-only">Search sessions</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search" placeholder="Search sessions" ...	Search field.
<datalist id="suggest">	Suggestions for an input linked with the list attribute.
<option value="Portrait session">	One choice in a select or datalist.

Line	What it does
<button>Go</button>	A clickable button; inside a form it submits by default.
<main>	The unique content of this page; exactly one per page.
Search results	The main heading; only one per page.
3 results for <q>session</q>	A paragraph of text.
<ol class="results">	Ordered (numbered) list; the order matters.
Portrait session One hour, 20 edited photos.<...	A hyperlink; href gives the destination.
Wedding day Full coverage, two photographers....	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
align-items: center;	Centres items on the cross axis.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--accent);	Background colour or image.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
font-weight: 700;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
flex: 1 1 18rem;	The item can grow and shrink from the given basis.
flex: 1;	All items share free space equally.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-right: 0;	The line around the element: width, style and colour.
border-radius: 999px 0 0 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).

Declaration	What it does
border-radius: 0 999px 999px 0;	Rounds the corners.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-size: 1.1rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Typing shows suggestions
- Label exists (hidden)
- Button attached to input visually
- Results are links with descriptions

Exercises

1. Highlight the matched word in results with <mark>.
2. Add filters with checkboxes in an aside.
3. Add 'no results' state styling.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 710: Search bar and results page for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 2 | Files: index.html, styles.css

Brief

Build a header search box with datalist suggestions and a joined input/button pair, plus a results list styled like a search engine.

Learning goals

- Use the search element, type=search and datalist
- Join an input and button with asymmetric border-radius
- Present results as an ordered list

Elements and CSS used

HTML elements	CSS features
search, form, label, input type=search, datalist, option, button, ol, li, a, q	flex: 1 1 18rem, border-radius (four values), border-right: 0, list-style: none

Build guide

1. Write the header with logo and <search> containing the form.
2. Add a datalist with one option per offer and link it with list=.
3. Add the results list.
4. Flex the bar; let the search area grow.
5. Round only the outer corners of input and button.

6. Style the results.

Project 710: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - Search</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="bar">
    <a class="logo" href="index.html">Papyrus Stationery</a>
    <search>
      <form action="/search" role="search">
        <label for="q" class="sr-only">Search products</label>
        <input id="q" name="q" type="search" placeholder="Search
products" list="suggest" autocomplete="off">
        <datalist id="suggest">
    <option value="Dotted notebook">
    <option value="Fountain pen">
    <option value="Washi tape set">
    <option value="Desk planner">
        </datalist>
        <button>Go</button>
      </form>
    </search>
  </header>
  <main>
    <h1>Search results</h1>
    <p>3 results for <q>product</q></p>
    <ol class="results">
    <li><a href="#">Dotted notebook</a><p>A5, 160 pages.</p></li>
    <li><a href="#">Fountain pen</a><p>Steel nib, refillable.</p></li>
    <li><a href="#">Washi tape set</a><p>Six patterns.</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 710: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.bar { display: flex; gap: 1rem; align-items: center; padding: .75rem
1.5rem; background: var(--accent); flex-wrap: wrap; }
```

```
.logo { font-weight: 700; text-decoration: none; color: var(--brand);
}
search { flex: 1 1 18rem; }
form { display: flex; }
input { flex: 1; padding: .6rem .9rem; border: 1px solid #bbb; border-
right: 0; border-radius: 999px 0 0 999px; font: inherit; }
button { padding: .6rem 1rem; border: 0; border-radius: 0 999px 999px
0; background: var(--brand); color: #fff; font: inherit; }
main { max-width: 40rem; margin: 1.5rem auto; padding: 0 1rem; }
.results { list-style: none; padding: 0; }
.results li { padding: 1rem 0; border-bottom: 1px solid var(--line); }
.results a { font-size: 1.1rem; font-weight: 600; }
.results p { margin: .2rem 0 0; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 710 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - Search</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="bar">	Introductory content: logo, title, navigation.
<search>	Container for search functionality.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q" class="sr-only">Search products</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search" placeholder="Search products" ...	Search field.
<datalist id="suggest">	Suggestions for an input linked with the list attribute.
<option value="Dotted notebook">	One choice in a select or datalist.

Line	What it does
<button>Go</button>	A clickable button; inside a form it submits by default.
<main>	The unique content of this page; exactly one per page.
Search results	The main heading; only one per page.
3 results for <q>product</q>	A paragraph of text.
<ol class="results">	Ordered (numbered) list; the order matters.
Dotted notebook A5, 160 pages.	A hyperlink; href gives the destination.
Fountain pen Steel nib, refillable.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
align-items: center;	Centres items on the cross axis.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--accent);	Background colour or image.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
font-weight: 700;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
flex: 1 1 18rem;	The item can grow and shrink from the given basis.
flex: 1;	All items share free space equally.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-right: 0;	The line around the element: width, style and colour.
border-radius: 999px 0 0 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).

Declaration	What it does
border-radius: 0 999px 999px 0;	Rounds the corners.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-size: 1.1rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Typing shows suggestions
- Label exists (hidden)
- Button attached to input visually
- Results are links with descriptions

Exercises

1. Highlight the matched word in results with <mark>.
2. Add filters with checkboxes in an aside.
3. Add 'no results' state styling.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 711: Search bar and results page for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 2 | Files: index.html, styles.css

Brief

Build a header search box with datalist suggestions and a joined input/button pair, plus a results list styled like a search engine.

Learning goals

- Use the search element, type=search and datalist
- Join an input and button with asymmetric border-radius
- Present results as an ordered list

Elements and CSS used

HTML elements	CSS features
search, form, label, input type=search, datalist, option, button, ol, li, a, q	flex: 1 1 18rem, border-radius (four values), border-right: 0, list-style: none

Build guide

1. Write the header with logo and <search> containing the form.
2. Add a datalist with one option per offer and link it with list=.
3. Add the results list.
4. Flex the bar; let the search area grow.
5. Round only the outer corners of input and button.

6. Style the results.

Project 711: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - Search</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="bar">
    <a class="logo" href="index.html">Oasis Plant Nursery</a>
    <search>
      <form action="/search" role="search">
        <label for="q" class="sr-only">Search plants</label>
        <input id="q" name="q" type="search" placeholder="Search
plants" list="suggest" autocomplete="off">
        <datalist id="suggest">
    <option value="Monstera">
    <option value="Snake plant">
    <option value="Basil pot">
    <option value="Olive tree">
        </datalist>
        <button>Go</button>
      </form>
    </search>
  </header>
  <main>
    <h1>Search results</h1>
    <p>3 results for <q>plant</q></p>
    <ol class="results">
    <li><a href="#">Monstera</a><p>Large leaves, easy care.</p></li>
    <li><a href="#">Snake plant</a><p>Survives anything.</p></li>
    <li><a href="#">Basil pot</a><p>Kitchen herb.</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 711: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.bar { display: flex; gap: 1rem; align-items: center; padding: .75rem
1.5rem; background: var(--accent); flex-wrap: wrap; }
```

```
.logo { font-weight: 700; text-decoration: none; color: var(--brand);
}
search { flex: 1 1 18rem; }
form { display: flex; }
input { flex: 1; padding: .6rem .9rem; border: 1px solid #bbb; border-
right: 0; border-radius: 999px 0 0 999px; font: inherit; }
button { padding: .6rem 1rem; border: 0; border-radius: 0 999px 999px
0; background: var(--brand); color: #fff; font: inherit; }
main { max-width: 40rem; margin: 1.5rem auto; padding: 0 1rem; }
.results { list-style: none; padding: 0; }
.results li { padding: 1rem 0; border-bottom: 1px solid var(--line); }
.results a { font-size: 1.1rem; font-weight: 600; }
.results p { margin: .2rem 0 0; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 711 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - Search</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="bar">	Introductory content: logo, title, navigation.
<search>	Container for search functionality.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q" class="sr-only">Search plants</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search" placeholder="Search plants" li...	Search field.
<datalist id="suggest">	Suggestions for an input linked with the list attribute.
<option value="Monstera">	One choice in a select or datalist.

Line	What it does
<button>Go</button>	A clickable button; inside a form it submits by default.
<main>	The unique content of this page; exactly one per page.
Search results	The main heading; only one per page.
3 results for <q>plant</q>	A paragraph of text.
<ol class="results">	Ordered (numbered) list; the order matters.
Monstera Large leaves, easy care.	A hyperlink; href gives the destination.
Snake plant Survives anything.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
align-items: center;	Centres items on the cross axis.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--accent);	Background colour or image.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
font-weight: 700;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
flex: 1 1 18rem;	The item can grow and shrink from the given basis.
flex: 1;	All items share free space equally.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-right: 0;	The line around the element: width, style and colour.
border-radius: 999px 0 0 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).

Declaration	What it does
border-radius: 0 999px 999px 0;	Rounds the corners.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-size: 1.1rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Typing shows suggestions
- Label exists (hidden)
- Button attached to input visually
- Results are links with descriptions

Exercises

1. Highlight the matched word in results with <mark>.
2. Add filters with checkboxes in an aside.
3. Add 'no results' state styling.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 712: Search bar and results page for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 2 | Files: index.html, styles.css

Brief

Build a header search box with datalist suggestions and a joined input/button pair, plus a results list styled like a search engine.

Learning goals

- Use the search element, type=search and datalist
- Join an input and button with asymmetric border-radius
- Present results as an ordered list

Elements and CSS used

HTML elements	CSS features
search, form, label, input type=search, datalist, option, button, ol, li, a, q	flex: 1 1 18rem, border-radius (four values), border-right: 0, list-style: none

Build guide

1. Write the header with logo and <search> containing the form.
2. Add a datalist with one option per offer and link it with list=.
3. Add the results list.
4. Flex the bar; let the search area grow.
5. Round only the outer corners of input and button.

6. Style the results.

Project 712: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - Search</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="bar">
    <a class="logo" href="index.html">Cedar Furniture</a>
    <search>
      <form action="/search" role="search">
        <label for="q" class="sr-only">Search pieces</label>
        <input id="q" name="q" type="search" placeholder="Search
pieces" list="suggest" autocomplete="off">
        <datalist id="suggest">
    <option value="Oak dining table">
    <option value="Bookshelf">
    <option value="Bedside table">
    <option value="Coffee table">
        </datalist>
        <button>Go</button>
      </form>
    </search>
  </header>
  <main>
    <h1>Search results</h1>
    <p>3 results for <q>piece</q></p>
    <ol class="results">
    <li><a href="#">Oak dining table</a><p>Seats six.</p></li>
    <li><a href="#">Bookshelf</a><p>Five shelves, walnut.</p></li>
    <li><a href="#">Bedside table</a><p>One drawer.</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 712: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.bar { display: flex; gap: 1rem; align-items: center; padding: .75rem
1.5rem; background: var(--accent); flex-wrap: wrap; }
```

```
.logo { font-weight: 700; text-decoration: none; color: var(--brand);
}
search { flex: 1 1 18rem; }
form { display: flex; }
input { flex: 1; padding: .6rem .9rem; border: 1px solid #bbb; border-
right: 0; border-radius: 999px 0 0 999px; font: inherit; }
button { padding: .6rem 1rem; border: 0; border-radius: 0 999px 999px
0; background: var(--brand); color: #fff; font: inherit; }
main { max-width: 40rem; margin: 1.5rem auto; padding: 0 1rem; }
.results { list-style: none; padding: 0; }
.results li { padding: 1rem 0; border-bottom: 1px solid var(--line); }
.results a { font-size: 1.1rem; font-weight: 600; }
.results p { margin: .2rem 0 0; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 712 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - Search</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="bar">	Introductory content: logo, title, navigation.
<search>	Container for search functionality.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q" class="sr-only">Search pieces</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search" placeholder="Search pieces" li...	Search field.
<datalist id="suggest">	Suggestions for an input linked with the list attribute.
<option value="Oak dining table">	One choice in a select or datalist.

Line	What it does
<button>Go</button>	A clickable button; inside a form it submits by default.
<main>	The unique content of this page; exactly one per page.
Search results	The main heading; only one per page.
3 results for <q>piece</q>	A paragraph of text.
<ol class="results">	Ordered (numbered) list; the order matters.
Oak dining table Seats six.	A hyperlink; href gives the destination.
Bookshelf Five shelves, walnut.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
align-items: center;	Centres items on the cross axis.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--accent);	Background colour or image.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
font-weight: 700;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
flex: 1 1 18rem;	The item can grow and shrink from the given basis.
flex: 1;	All items share free space equally.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-right: 0;	The line around the element: width, style and colour.
border-radius: 999px 0 0 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).

Declaration	What it does
border-radius: 0 999px 999px 0;	Rounds the corners.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-size: 1.1rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Typing shows suggestions
- Label exists (hidden)
- Button attached to input visually
- Results are links with descriptions

Exercises

1. Highlight the matched word in results with <mark>.
2. Add filters with checkboxes in an aside.
3. Add 'no results' state styling.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 713: Search bar and results page for Byte Repair

Theme: Byte Repair (Nasr City) | Level 2 | Files: index.html, styles.css

Brief

Build a header search box with datalist suggestions and a joined input/button pair, plus a results list styled like a search engine.

Learning goals

- Use the search element, type=search and datalist
- Join an input and button with asymmetric border-radius
- Present results as an ordered list

Elements and CSS used

HTML elements	CSS features
search, form, label, input type=search, datalist, option, button, ol, li, a, q	flex: 1 1 18rem, border-radius (four values), border-right: 0, list-style: none

Build guide

1. Write the header with logo and <search> containing the form.
2. Add a datalist with one option per offer and link it with list=.
3. Add the results list.
4. Flex the bar; let the search area grow.
5. Round only the outer corners of input and button.
6. Style the results.

Project 713: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - Search</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="bar">
    <a class="logo" href="index.html">Byte Repair</a>
    <search>
      <form action="/search" role="search">
        <label for="q" class="sr-only">Search repairs</label>
        <input id="q" name="q" type="search" placeholder="Search
repairs" list="suggest" autocomplete="off">
        <datalist id="suggest">
    <option value="Screen replacement">
    <option value="Battery swap">
    <option value="Laptop cleaning">
    <option value="Data recovery">
        </datalist>
        <button>Go</button>
      </form>
    </search>
  </header>
  <main>
    <h1>Search results</h1>
    <p>3 results for <q>repair</q></p>
    <ol class="results">
    <li><a href="#">Screen replacement</a><p>Most phones, 1 hour.</
p></li>
    <li><a href="#">Battery swap</a><p>Original cells.</p></li>
    <li><a href="#">Laptop cleaning</a><p>Fans and thermal paste.</
p></li>
    </ol>
  </main>
</body>
</html>
```

Project 713: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
.bar { display: flex; gap: 1rem; align-items: center; padding: .75rem
1.5rem; background: var(--accent); flex-wrap: wrap; }
.logo { font-weight: 700; text-decoration: none; color: var(--brand);
}
search { flex: 1 1 18rem; }
form { display: flex; }
input { flex: 1; padding: .6rem .9rem; border: 1px solid #bbb; border-
right: 0; border-radius: 999px 0 0 999px; font: inherit; }
button { padding: .6rem 1rem; border: 0; border-radius: 0 999px 999px
0; background: var(--brand); color: #fff; font: inherit; }
main { max-width: 40rem; margin: 1.5rem auto; padding: 0 1rem; }
.results { list-style: none; padding: 0; }
.results li { padding: 1rem 0; border-bottom: 1px solid var(--line); }
.results a { font-size: 1.1rem; font-weight: 600; }
.results p { margin: .2rem 0 0; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 713 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - Search</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="bar">	Introductory content: logo, title, navigation.
<search>	Container for search functionality.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q" class="sr-only">Search repairs</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search" placeholder="Search repairs" l...	Search field.
<datalist id="suggest">	Suggestions for an input linked with the list attribute.
<option value="Screen replacement">	One choice in a select or datalist.

Line	What it does
<button>Go</button>	A clickable button; inside a form it submits by default.
<main>	The unique content of this page; exactly one per page.
Search results	The main heading; only one per page.
3 results for <q>repair</q>	A paragraph of text.
<ol class="results">	Ordered (numbered) list; the order matters.
Screen replacement Most phones, 1 hour.	A hyperlink; href gives the destination.
Battery swap Original cells.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
align-items: center;	Centres items on the cross axis.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--accent);	Background colour or image.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
font-weight: 700;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
flex: 1 1 18rem;	The item can grow and shrink from the given basis.
flex: 1;	All items share free space equally.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-right: 0;	The line around the element: width, style and colour.
border-radius: 999px 0 0 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).

Declaration	What it does
border-radius: 0 999px 999px 0;	Rounds the corners.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-size: 1.1rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Typing shows suggestions
- Label exists (hidden)
- Button attached to input visually
- Results are links with descriptions

Exercises

1. Highlight the matched word in results with <mark>.
2. Add filters with checkboxes in an aside.
3. Add 'no results' state styling.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 714: Search bar and results page for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 2 | Files: index.html, styles.css

Brief

Build a header search box with datalist suggestions and a joined input/button pair, plus a results list styled like a search engine.

Learning goals

- Use the search element, type=search and datalist
- Join an input and button with asymmetric border-radius
- Present results as an ordered list

Elements and CSS used

HTML elements	CSS features
search, form, label, input type=search, datalist, option, button, ol, li, a, q	flex: 1 1 18rem, border-radius (four values), border-right: 0, list-style: none

Build guide

1. Write the header with logo and <search> containing the form.
2. Add a datalist with one option per offer and link it with list=.
3. Add the results list.
4. Flex the bar; let the search area grow.
5. Round only the outer corners of input and button.

6. Style the results.

Project 714: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - Search</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="bar">
    <a class="logo" href="index.html">Sahara Pet Care</a>
    <search>
      <form action="/search" role="search">
        <label for="q" class="sr-only">Search services</label>
        <input id="q" name="q" type="search" placeholder="Search
services" list="suggest" autocomplete="off">
        <datalist id="suggest">
    <option value="Full grooming">
    <option value="Day boarding">
    <option value="Vaccination">
    <option value="Dog walking">
        </datalist>
        <button>Go</button>
      </form>
    </search>
  </header>
  <main>
    <h1>Search results</h1>
    <p>3 results for <q>service</q></p>
    <ol class="results">
    <li><a href="#">Full grooming</a><p>Bath, cut and nails.</p></li>
    <li><a href="#">Day boarding</a><p>Play and rest.</p></li>
    <li><a href="#">Vaccination</a><p>Annual boosters.</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 714: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.bar { display: flex; gap: 1rem; align-items: center; padding: .75rem
1.5rem; background: var(--accent); flex-wrap: wrap; }
```

```
.logo { font-weight: 700; text-decoration: none; color: var(--brand);
}
search { flex: 1 1 18rem; }
form { display: flex; }
input { flex: 1; padding: .6rem .9rem; border: 1px solid #bbb; border-
right: 0; border-radius: 999px 0 0 999px; font: inherit; }
button { padding: .6rem 1rem; border: 0; border-radius: 0 999px 999px
0; background: var(--brand); color: #fff; font: inherit; }
main { max-width: 40rem; margin: 1.5rem auto; padding: 0 1rem; }
.results { list-style: none; padding: 0; }
.results li { padding: 1rem 0; border-bottom: 1px solid var(--line); }
.results a { font-size: 1.1rem; font-weight: 600; }
.results p { margin: .2rem 0 0; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 714 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - Search</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="bar">	Introductory content: logo, title, navigation.
<search>	Container for search functionality.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q" class="sr-only">Search services</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search" placeholder="Search services" ...	Search field.
<datalist id="suggest">	Suggestions for an input linked with the list attribute.
<option value="Full grooming">	One choice in a select or datalist.

Line	What it does
<button>Go</button>	A clickable button; inside a form it submits by default.
<main>	The unique content of this page; exactly one per page.
Search results	The main heading; only one per page.
3 results for <q>service</q>	A paragraph of text.
<ol class="results">	Ordered (numbered) list; the order matters.
Full grooming Bath, cut and nails.	A hyperlink; href gives the destination.
Day boarding Play and rest.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
align-items: center;	Centres items on the cross axis.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--accent);	Background colour or image.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
font-weight: 700;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
flex: 1 1 18rem;	The item can grow and shrink from the given basis.
flex: 1;	All items share free space equally.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-right: 0;	The line around the element: width, style and colour.
border-radius: 999px 0 0 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).

Declaration	What it does
border-radius: 0 999px 999px 0;	Rounds the corners.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-size: 1.1rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Typing shows suggestions
- Label exists (hidden)
- Button attached to input visually
- Results are links with descriptions

Exercises

1. Highlight the matched word in results with <mark>.
2. Add filters with checkboxes in an aside.
3. Add 'no results' state styling.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 715: Search bar and results page for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Build a header search box with datalist suggestions and a joined input/button pair, plus a results list styled like a search engine.

Learning goals

- Use the search element, type=search and datalist
- Join an input and button with asymmetric border-radius
- Present results as an ordered list

Elements and CSS used

HTML elements	CSS features
search, form, label, input type=search, datalist, option, button, ol, li, a, q	flex: 1 1 18rem, border-radius (four values), border-right: 0, list-style: none

Build guide

1. Write the header with logo and <search> containing the form.
2. Add a datalist with one option per offer and link it with list=.
3. Add the results list.
4. Flex the bar; let the search area grow.
5. Round only the outer corners of input and button.

6. Style the results.

Project 715: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - Search</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="bar">
    <a class="logo" href="index.html">Alexandria Sailing School</a>
    <search>
      <form action="/search" role="search">
        <label for="q" class="sr-only">Search lessons</label>
        <input id="q" name="q" type="search" placeholder="Search
lessons" list="suggest" autocomplete="off">
        <datalist id="suggest">
    <option value="Taster session">
    <option value="Beginner course">
    <option value="Racing clinic">
    <option value="Private lesson">
        </datalist>
        <button>Go</button>
      </form>
    </search>
  </header>
  <main>
    <h1>Search results</h1>
    <p>3 results for <q>lesson</q></p>
    <ol class="results">
    <li><a href="#">Taster session</a><p>Two hours on the water.</p></
li>
    <li><a href="#">Beginner course</a><p>Five sessions.</p></li>
    <li><a href="#">Racing clinic</a><p>Tactics and trim.</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 715: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.bar { display: flex; gap: 1rem; align-items: center; padding: .75rem
```

```
1.5rem; background: var(--accent); flex-wrap: wrap; }
.logo { font-weight: 700; text-decoration: none; color: var(--brand);
}
search { flex: 1 1 18rem; }
form { display: flex; }
input { flex: 1; padding: .6rem .9rem; border: 1px solid #bbb; border-
right: 0; border-radius: 999px 0 0 999px; font: inherit; }
button { padding: .6rem 1rem; border: 0; border-radius: 0 999px 999px
0; background: var(--brand); color: #fff; font: inherit; }
main { max-width: 40rem; margin: 1.5rem auto; padding: 0 1rem; }
.results { list-style: none; padding: 0; }
.results li { padding: 1rem 0; border-bottom: 1px solid var(--line); }
.results a { font-size: 1.1rem; font-weight: 600; }
.results p { margin: .2rem 0 0; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 715 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - Search</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="bar">	Introductory content: logo, title, navigation.
<search>	Container for search functionality.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q" class="sr-only">Search lessons</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search" placeholder="Search lessons" l...	Search field.
<datalist id="suggest">	Suggestions for an input linked with the list attribute.
<option value="Taster session">	One choice in a select or datalist.

Line	What it does
<button>Go</button>	A clickable button; inside a form it submits by default.
<main>	The unique content of this page; exactly one per page.
Search results	The main heading; only one per page.
3 results for <q>lesson</q>	A paragraph of text.
<ol class="results">	Ordered (numbered) list; the order matters.
Taster session Two hours on the water.	A hyperlink; href gives the destination.
Beginner course Five sessions.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
align-items: center;	Centres items on the cross axis.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--accent);	Background colour or image.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
font-weight: 700;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
flex: 1 1 18rem;	The item can grow and shrink from the given basis.
flex: 1;	All items share free space equally.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-right: 0;	The line around the element: width, style and colour.
border-radius: 999px 0 0 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).

Declaration	What it does
border-radius: 0 999px 999px 0;	Rounds the corners.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-size: 1.1rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Typing shows suggestions
- Label exists (hidden)
- Button attached to input visually
- Results are links with descriptions

Exercises

1. Highlight the matched word in results with <mark>.
2. Add filters with checkboxes in an aside.
3. Add 'no results' state styling.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 716: Search bar and results page for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Build a header search box with datalist suggestions and a joined input/button pair, plus a results list styled like a search engine.

Learning goals

- Use the search element, type=search and datalist
- Join an input and button with asymmetric border-radius
- Present results as an ordered list

Elements and CSS used

HTML elements	CSS features
search, form, label, input type=search, datalist, option, button, ol, li, a, q	flex: 1 1 18rem, border-radius (four values), border-right: 0, list-style: none

Build guide

1. Write the header with logo and <search> containing the form.
2. Add a datalist with one option per offer and link it with list=.
3. Add the results list.
4. Flex the bar; let the search area grow.
5. Round only the outer corners of input and button.

6. Style the results.

Project 716: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - Search</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="bar">
    <a class="logo" href="index.html">Habiba Handmade Jewellery</a>
    <search>
      <form action="/search" role="search">
        <label for="q" class="sr-only">Search items</label>
        <input id="q" name="q" type="search" placeholder="Search
items" list="suggest" autocomplete="off">
        <datalist id="suggest">
    <option value="Lotus pendant">
    <option value="Brass cuff">
    <option value="Bead earrings">
    <option value="Ankh ring">
        </datalist>
        <button>Go</button>
      </form>
    </search>
  </header>
  <main>
    <h1>Search results</h1>
    <p>3 results for <q>item</q></p>
    <ol class="results">
    <li><a href="#">Lotus pendant</a><p>Sterling silver.</p></li>
    <li><a href="#">Brass cuff</a><p>Hand engraved.</p></li>
    <li><a href="#">Bead earrings</a><p>Recycled glass.</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 716: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.bar { display: flex; gap: 1rem; align-items: center; padding: .75rem
1.5rem; background: var(--accent); flex-wrap: wrap; }
```

```
.logo { font-weight: 700; text-decoration: none; color: var(--brand);
}
search { flex: 1 1 18rem; }
form { display: flex; }
input { flex: 1; padding: .6rem .9rem; border: 1px solid #bbb; border-
right: 0; border-radius: 999px 0 0 999px; font: inherit; }
button { padding: .6rem 1rem; border: 0; border-radius: 0 999px 999px
0; background: var(--brand); color: #fff; font: inherit; }
main { max-width: 40rem; margin: 1.5rem auto; padding: 0 1rem; }
.results { list-style: none; padding: 0; }
.results li { padding: 1rem 0; border-bottom: 1px solid var(--line); }
.results a { font-size: 1.1rem; font-weight: 600; }
.results p { margin: .2rem 0 0; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 716 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - Search</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="bar">	Introductory content: logo, title, navigation.
<search>	Container for search functionality.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q" class="sr-only">Search items</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search" placeholder="Search items" lis...	Search field.
<datalist id="suggest">	Suggestions for an input linked with the list attribute.
<option value="Lotus pendant">	One choice in a select or datalist.

Line	What it does
<button>Go</button>	A clickable button; inside a form it submits by default.
<main>	The unique content of this page; exactly one per page.
Search results	The main heading; only one per page.
3 results for <q>item</q>	A paragraph of text.
<ol class="results">	Ordered (numbered) list; the order matters.
Lotus pendant Sterling silver.	A hyperlink; href gives the destination.
Brass cuff Hand engraved.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
align-items: center;	Centres items on the cross axis.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--accent);	Background colour or image.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
font-weight: 700;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
flex: 1 1 18rem;	The item can grow and shrink from the given basis.
flex: 1;	All items share free space equally.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-right: 0;	The line around the element: width, style and colour.
border-radius: 999px 0 0 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).

Declaration	What it does
border-radius: 0 999px 999px 0;	Rounds the corners.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-size: 1.1rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Typing shows suggestions
- Label exists (hidden)
- Button attached to input visually
- Results are links with descriptions

Exercises

1. Highlight the matched word in results with <mark>.
2. Add filters with checkboxes in an aside.
3. Add 'no results' state styling.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 717: Search bar and results page for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 2 | Files: index.html, styles.css

Brief

Build a header search box with datalist suggestions and a joined input/button pair, plus a results list styled like a search engine.

Learning goals

- Use the search element, type=search and datalist
- Join an input and button with asymmetric border-radius
- Present results as an ordered list

Elements and CSS used

HTML elements	CSS features
search, form, label, input type=search, datalist, option, button, ol, li, a, q	flex: 1 1 18rem, border-radius (four values), border-right: 0, list-style: none

Build guide

1. Write the header with logo and <search> containing the form.
2. Add a datalist with one option per offer and link it with list=.
3. Add the results list.
4. Flex the bar; let the search area grow.
5. Round only the outer corners of input and button.

6. Style the results.

Project 717: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - Search</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="bar">
    <a class="logo" href="index.html">Fayoum Pottery Studio</a>
    <search>
      <form action="/search" role="search">
        <label for="q" class="sr-only">Search workshops</label>
        <input id="q" name="q" type="search" placeholder="Search
workshops" list="suggest" autocomplete="off">
        <datalist id="suggest">
    <option value="Intro to the wheel">
    <option value="Glazing day">
    <option value="Kids clay class">
    <option value="Weekend retreat">
        </datalist>
        <button>Go</button>
      </form>
    </search>
  </header>
  <main>
    <h1>Search results</h1>
    <p>3 results for <q>workshop</q></p>
    <ol class="results">
    <li><a href="#">Intro to the wheel</a><p>Three hours, take home a
bowl.</p></li>
    <li><a href="#">Glazing day</a><p>Colour your pieces.</p></li>
    <li><a href="#">Kids clay class</a><p>Ages 6 to 12.</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 717: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.bar { display: flex; gap: 1rem; align-items: center; padding: .75rem
```

```
1.5rem; background: var(--accent); flex-wrap: wrap; }
.logo { font-weight: 700; text-decoration: none; color: var(--brand);
}
search { flex: 1 1 18rem; }
form { display: flex; }
input { flex: 1; padding: .6rem .9rem; border: 1px solid #bbb; border-
right: 0; border-radius: 999px 0 0 999px; font: inherit; }
button { padding: .6rem 1rem; border: 0; border-radius: 0 999px 999px
0; background: var(--brand); color: #fff; font: inherit; }
main { max-width: 40rem; margin: 1.5rem auto; padding: 0 1rem; }
.results { list-style: none; padding: 0; }
.results li { padding: 1rem 0; border-bottom: 1px solid var(--line); }
.results a { font-size: 1.1rem; font-weight: 600; }
.results p { margin: .2rem 0 0; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 717 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - Search</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="bar">	Introductory content: logo, title, navigation.
<search>	Container for search functionality.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q" class="sr-only">Search workshops</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search" placeholder="Search workshops"...	Search field.
<datalist id="suggest">	Suggestions for an input linked with the list attribute.
<option value="Intro to the wheel">	One choice in a select or datalist.

Line	What it does
<button>Go</button>	A clickable button; inside a form it submits by default.
<main>	The unique content of this page; exactly one per page.
Search results	The main heading; only one per page.
3 results for <q>workshop</q>	A paragraph of text.
<ol class="results">	Ordered (numbered) list; the order matters.
Intro to the wheel Three hours, take home a b...	A hyperlink; href gives the destination.
Glazing day Colour your pieces.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
align-items: center;	Centres items on the cross axis.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--accent);	Background colour or image.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
font-weight: 700;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
flex: 1 1 18rem;	The item can grow and shrink from the given basis.
flex: 1;	All items share free space equally.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-right: 0;	The line around the element: width, style and colour.
border-radius: 999px 0 0 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).

Declaration	What it does
border-radius: 0 999px 999px 0;	Rounds the corners.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-size: 1.1rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Typing shows suggestions
- Label exists (hidden)
- Button attached to input visually
- Results are links with descriptions

Exercises

1. Highlight the matched word in results with <mark>.
2. Add filters with checkboxes in an aside.
3. Add 'no results' state styling.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 718: Search bar and results page for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 2 | Files: index.html, styles.css

Brief

Build a header search box with datalist suggestions and a joined input/button pair, plus a results list styled like a search engine.

Learning goals

- Use the search element, type=search and datalist
- Join an input and button with asymmetric border-radius
- Present results as an ordered list

Elements and CSS used

HTML elements	CSS features
search, form, label, input type=search, datalist, option, button, ol, li, a, q	flex: 1 1 18rem, border-radius (four values), border-right: 0, list-style: none

Build guide

1. Write the header with logo and <search> containing the form.
2. Add a datalist with one option per offer and link it with list=.
3. Add the results list.
4. Flex the bar; let the search area grow.
5. Round only the outer corners of input and button.

6. Style the results.

Project 718: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - Search</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="bar">
    <a class="logo" href="index.html">Cleopatra Beauty Salon</a>
    <search>
      <form action="/search" role="search">
        <label for="q" class="sr-only">Search treatments</label>
        <input id="q" name="q" type="search" placeholder="Search
treatments" list="suggest" autocomplete="off">
        <datalist id="suggest">
    <option value="Haircut and blow-dry">
    <option value="Manicure">
    <option value="Facial">
    <option value="Bridal package">
        </datalist>
        <button>Go</button>
      </form>
    </search>
  </header>
  <main>
    <h1>Search results</h1>
    <p>3 results for <q>treatment</q></p>
    <ol class="results">
    <li><a href="#">Haircut and blow-dry</a><p>Consultation included.
</p></li>
    <li><a href="#">Manicure</a><p>Classic or gel.</p></li>
    <li><a href="#">Facial</a><p>Deep cleanse, 60 minutes.</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 718: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.bar { display: flex; gap: 1rem; align-items: center; padding: .75rem
```

```
1.5rem; background: var(--accent); flex-wrap: wrap; }
.logo { font-weight: 700; text-decoration: none; color: var(--brand);
}
search { flex: 1 1 18rem; }
form { display: flex; }
input { flex: 1; padding: .6rem .9rem; border: 1px solid #bbb; border-
right: 0; border-radius: 999px 0 0 999px; font: inherit; }
button { padding: .6rem 1rem; border: 0; border-radius: 0 999px 999px
0; background: var(--brand); color: #fff; font: inherit; }
main { max-width: 40rem; margin: 1.5rem auto; padding: 0 1rem; }
.results { list-style: none; padding: 0; }
.results li { padding: 1rem 0; border-bottom: 1px solid var(--line); }
.results a { font-size: 1.1rem; font-weight: 600; }
.results p { margin: .2rem 0 0; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 718 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - Search</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="bar">	Introductory content: logo, title, navigation.
<search>	Container for search functionality.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q" class="sr-only">Search treatments</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search" placeholder="Search treatments...	Search field.
<datalist id="suggest">	Suggestions for an input linked with the list attribute.
<option value="Haircut and blow-dry">	One choice in a select or datalist.

Line	What it does
<button>Go</button>	A clickable button; inside a form it submits by default.
<main>	The unique content of this page; exactly one per page.
Search results	The main heading; only one per page.
3 results for <q>treatment</q>	A paragraph of text.
<ol class="results">	Ordered (numbered) list; the order matters.
Haircut and blow-dry Consultation included.<//...	A hyperlink; href gives the destination.
Manicure Classic or gel.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
align-items: center;	Centres items on the cross axis.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--accent);	Background colour or image.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
font-weight: 700;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
flex: 1 1 18rem;	The item can grow and shrink from the given basis.
flex: 1;	All items share free space equally.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-right: 0;	The line around the element: width, style and colour.
border-radius: 999px 0 0 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).

Declaration	What it does
border-radius: 0 999px 999px 0;	Rounds the corners.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-size: 1.1rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Typing shows suggestions
- Label exists (hidden)
- Button attached to input visually
- Results are links with descriptions

Exercises

1. Highlight the matched word in results with <mark>.
2. Add filters with checkboxes in an aside.
3. Add 'no results' state styling.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 719: Search bar and results page for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 2 | Files: index.html, styles.css

Brief

Build a header search box with datalist suggestions and a joined input/button pair, plus a results list styled like a search engine.

Learning goals

- Use the search element, type=search and datalist
- Join an input and button with asymmetric border-radius
- Present results as an ordered list

Elements and CSS used

HTML elements	CSS features
search, form, label, input type=search, datalist, option, button, ol, li, a, q	flex: 1 1 18rem, border-radius (four values), border-right: 0, list-style: none

Build guide

1. Write the header with logo and <search> containing the form.
2. Add a datalist with one option per offer and link it with list=.
3. Add the results list.
4. Flex the bar; let the search area grow.
5. Round only the outer corners of input and button.

6. Style the results.

Project 719: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - Search</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="bar">
    <a class="logo" href="index.html">Suez Auto Service</a>
    <search>
      <form action="/search" role="search">
        <label for="q" class="sr-only">Search services</label>
        <input id="q" name="q" type="search" placeholder="Search
services" list="suggest" autocomplete="off">
        <datalist id="suggest">
    <option value="Oil change">
    <option value="Brake pads">
    <option value="Air conditioning">
    <option value="Pre-purchase inspection">
        </datalist>
        <button>Go</button>
      </form>
    </search>
  </header>
  <main>
    <h1>Search results</h1>
    <p>3 results for <q>service</q></p>
    <ol class="results">
    <li><a href="#">Oil change</a><p>Filter included.</p></li>
    <li><a href="#">Brake pads</a><p>Front axle.</p></li>
    <li><a href="#">Air conditioning</a><p>Recharge and check.</p></
li>
    </ol>
  </main>
</body>
</html>
```

Project 719: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.bar { display: flex; gap: 1rem; align-items: center; padding: .75rem
```

```
1.5rem; background: var(--accent); flex-wrap: wrap; }
.logo { font-weight: 700; text-decoration: none; color: var(--brand);
}
search { flex: 1 1 18rem; }
form { display: flex; }
input { flex: 1; padding: .6rem .9rem; border: 1px solid #bbb; border-
right: 0; border-radius: 999px 0 0 999px; font: inherit; }
button { padding: .6rem 1rem; border: 0; border-radius: 0 999px 999px
0; background: var(--brand); color: #fff; font: inherit; }
main { max-width: 40rem; margin: 1.5rem auto; padding: 0 1rem; }
.results { list-style: none; padding: 0; }
.results li { padding: 1rem 0; border-bottom: 1px solid var(--line); }
.results a { font-size: 1.1rem; font-weight: 600; }
.results p { margin: .2rem 0 0; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 719 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - Search</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="bar">	Introductory content: logo, title, navigation.
<search>	Container for search functionality.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q" class="sr-only">Search services</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search" placeholder="Search services" ...	Search field.
<datalist id="suggest">	Suggestions for an input linked with the list attribute.
<option value="Oil change">	One choice in a select or datalist.

Line	What it does
<button>Go</button>	A clickable button; inside a form it submits by default.
<main>	The unique content of this page; exactly one per page.
Search results	The main heading; only one per page.
3 results for <q>service</q>	A paragraph of text.
<ol class="results">	Ordered (numbered) list; the order matters.
Oil change Filter included.	A hyperlink; href gives the destination.
Brake pads Front axle.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
align-items: center;	Centres items on the cross axis.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--accent);	Background colour or image.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
font-weight: 700;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
flex: 1 1 18rem;	The item can grow and shrink from the given basis.
flex: 1;	All items share free space equally.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-right: 0;	The line around the element: width, style and colour.
border-radius: 999px 0 0 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).

Declaration	What it does
border-radius: 0 999px 999px 0;	Rounds the corners.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-size: 1.1rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Typing shows suggestions
- Label exists (hidden)
- Button attached to input visually
- Results are links with descriptions

Exercises

1. Highlight the matched word in results with <mark>.
2. Add filters with checkboxes in an aside.
3. Add 'no results' state styling.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 720: Search bar and results page for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 2 | Files: index.html, styles.css

Brief

Build a header search box with datalist suggestions and a joined input/button pair, plus a results list styled like a search engine.

Learning goals

- Use the search element, type=search and datalist
- Join an input and button with asymmetric border-radius
- Present results as an ordered list

Elements and CSS used

HTML elements	CSS features
search, form, label, input type=search, datalist, option, button, ol, li, a, q	flex: 1 1 18rem, border-radius (four values), border-right: 0, list-style: none

Build guide

1. Write the header with logo and <search> containing the form.
2. Add a datalist with one option per offer and link it with list=.
3. Add the results list.
4. Flex the bar; let the search area grow.
5. Round only the outer corners of input and button.

6. Style the results.

Project 720: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - Search</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="bar">
    <a class="logo" href="index.html">Luxor Music Academy</a>
    <search>
      <form action="/search" role="search">
        <label for="q" class="sr-only">Search courses</label>
        <input id="q" name="q" type="search" placeholder="Search
courses" list="suggest" autocomplete="off">
        <datalist id="suggest">
    <option value="Oud for beginners">
    <option value="Piano grade 1">
    <option value="Guitar chords">
    <option value="Voice coaching">
        </datalist>
        <button>Go</button>
      </form>
    </search>
  </header>
  <main>
    <h1>Search results</h1>
    <p>3 results for <q>course</q></p>
    <ol class="results">
    <li><a href="#">Oud for beginners</a><p>Eight weekly lessons.</
p></li>
    <li><a href="#">Piano grade 1</a><p>Theory and practice.</p></li>
    <li><a href="#">Guitar chords</a><p>Play songs in a month.</p></
li>
    </ol>
  </main>
</body>
</html>
```

Project 720: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
.bar { display: flex; gap: 1rem; align-items: center; padding: .75rem
1.5rem; background: var(--accent); flex-wrap: wrap; }
.logo { font-weight: 700; text-decoration: none; color: var(--brand);
}
search { flex: 1 1 18rem; }
form { display: flex; }
input { flex: 1; padding: .6rem .9rem; border: 1px solid #bbb; border-
right: 0; border-radius: 999px 0 0 999px; font: inherit; }
button { padding: .6rem 1rem; border: 0; border-radius: 0 999px 999px
0; background: var(--brand); color: #fff; font: inherit; }
main { max-width: 40rem; margin: 1.5rem auto; padding: 0 1rem; }
.results { list-style: none; padding: 0; }
.results li { padding: 1rem 0; border-bottom: 1px solid var(--line); }
.results a { font-size: 1.1rem; font-weight: 600; }
.results p { margin: .2rem 0 0; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 720 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - Search</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="bar">	Introductory content: logo, title, navigation.
<search>	Container for search functionality.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q" class="sr-only">Search courses</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search" placeholder="Search courses" l...	Search field.
<datalist id="suggest">	Suggestions for an input linked with the list attribute.
<option value="Oud for beginners">	One choice in a select or datalist.

Line	What it does
<button>Go</button>	A clickable button; inside a form it submits by default.
<main>	The unique content of this page; exactly one per page.
Search results	The main heading; only one per page.
3 results for <q>course</q>	A paragraph of text.
<ol class="results">	Ordered (numbered) list; the order matters.
Oud for beginners Eight weekly lessons.	A hyperlink; href gives the destination.
Piano grade 1 Theory and practice.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
align-items: center;	Centres items on the cross axis.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--accent);	Background colour or image.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
font-weight: 700;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
flex: 1 1 18rem;	The item can grow and shrink from the given basis.
flex: 1;	All items share free space equally.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-right: 0;	The line around the element: width, style and colour.
border-radius: 999px 0 0 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).

Declaration	What it does
border-radius: 0 999px 999px 0;	Rounds the corners.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-size: 1.1rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Typing shows suggestions
- Label exists (hidden)
- Button attached to input visually
- Results are links with descriptions

Exercises

1. Highlight the matched word in results with <mark>.
2. Add filters with checkboxes in an aside.
3. Add 'no results' state styling.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 721: Search bar and results page for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 2 | Files: index.html, styles.css

Brief

Build a header search box with datalist suggestions and a joined input/button pair, plus a results list styled like a search engine.

Learning goals

- Use the search element, type=search and datalist
- Join an input and button with asymmetric border-radius
- Present results as an ordered list

Elements and CSS used

HTML elements	CSS features
search, form, label, input type=search, datalist, option, button, ol, li, a, q	flex: 1 1 18rem, border-radius (four values), border-right: 0, list-style: none

Build guide

1. Write the header with logo and <search> containing the form.
2. Add a datalist with one option per offer and link it with list=.
3. Add the results list.
4. Flex the bar; let the search area grow.
5. Round only the outer corners of input and button.

6. Style the results.

Project 721: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - Search</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="bar">
    <a class="logo" href="index.html">Port Said Seafood</a>
    <search>
      <form action="/search" role="search">
        <label for="q" class="sr-only">Search dishes</label>
        <input id="q" name="q" type="search" placeholder="Search
dishes" list="suggest" autocomplete="off">
        <datalist id="suggest">
    <option value="Grilled sea bass">
    <option value="Shrimp tagine">
    <option value="Calamari">
    <option value="Fish soup">
        </datalist>
        <button>Go</button>
      </form>
    </search>
  </header>
  <main>
    <h1>Search results</h1>
    <p>3 results for <q>dish</q></p>
    <ol class="results">
    <li><a href="#">Grilled sea bass</a><p>With rice and salad.</p></
li>
    <li><a href="#">Shrimp tagine</a><p>Tomato and garlic.</p></li>
    <li><a href="#">Calamari</a><p>Fried, with tahini.</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 721: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.bar { display: flex; gap: 1rem; align-items: center; padding: .75rem
```

```
1.5rem; background: var(--accent); flex-wrap: wrap; }
.logo { font-weight: 700; text-decoration: none; color: var(--brand);
}
search { flex: 1 1 18rem; }
form { display: flex; }
input { flex: 1; padding: .6rem .9rem; border: 1px solid #bbb; border-
right: 0; border-radius: 999px 0 0 999px; font: inherit; }
button { padding: .6rem 1rem; border: 0; border-radius: 0 999px 999px
0; background: var(--brand); color: #fff; font: inherit; }
main { max-width: 40rem; margin: 1.5rem auto; padding: 0 1rem; }
.results { list-style: none; padding: 0; }
.results li { padding: 1rem 0; border-bottom: 1px solid var(--line); }
.results a { font-size: 1.1rem; font-weight: 600; }
.results p { margin: .2rem 0 0; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 721 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - Search</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="bar">	Introductory content: logo, title, navigation.
<search>	Container for search functionality.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q" class="sr-only">Search dishes</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search" placeholder="Search dishes" li...	Search field.
<datalist id="suggest">	Suggestions for an input linked with the list attribute.
<option value="Grilled sea bass">	One choice in a select or datalist.

Line	What it does
<button>Go</button>	A clickable button; inside a form it submits by default.
<main>	The unique content of this page; exactly one per page.
Search results	The main heading; only one per page.
3 results for <q>dish</q>	A paragraph of text.
<ol class="results">	Ordered (numbered) list; the order matters.
Grilled sea bass With rice and salad.	A hyperlink; href gives the destination.
Shrimp tagine Tomato and garlic.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
align-items: center;	Centres items on the cross axis.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--accent);	Background colour or image.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
font-weight: 700;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
flex: 1 1 18rem;	The item can grow and shrink from the given basis.
flex: 1;	All items share free space equally.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-right: 0;	The line around the element: width, style and colour.
border-radius: 999px 0 0 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).

Declaration	What it does
border-radius: 0 999px 999px 0;	Rounds the corners.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-size: 1.1rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Typing shows suggestions
- Label exists (hidden)
- Button attached to input visually
- Results are links with descriptions

Exercises

1. Highlight the matched word in results with <mark>.
2. Add filters with checkboxes in an aside.
3. Add 'no results' state styling.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 722: Search bar and results page for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 2 | Files: index.html, styles.css

Brief

Build a header search box with datalist suggestions and a joined input/button pair, plus a results list styled like a search engine.

Learning goals

- Use the search element, type=search and datalist
- Join an input and button with asymmetric border-radius
- Present results as an ordered list

Elements and CSS used

HTML elements	CSS features
search, form, label, input type=search, datalist, option, button, ol, li, a, q	flex: 1 1 18rem, border-radius (four values), border-right: 0, list-style: none

Build guide

1. Write the header with logo and <search> containing the form.
2. Add a datalist with one option per offer and link it with list=.
3. Add the results list.
4. Flex the bar; let the search area grow.
5. Round only the outer corners of input and button.

6. Style the results.

Project 722: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - Search</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="bar">
    <a class="logo" href="index.html">Delta Kids Library</a>
    <search>
      <form action="/search" role="search">
        <label for="q" class="sr-only">Search programmes</label>
        <input id="q" name="q" type="search" placeholder="Search
programmes" list="suggest" autocomplete="off">
        <datalist id="suggest">
    <option value="Story hour">
    <option value="Reading club">
    <option value="Homework help">
    <option value="Summer challenge">
        </datalist>
        <button>Go</button>
      </form>
    </search>
  </header>
  <main>
    <h1>Search results</h1>
    <p>3 results for <q>programme</q></p>
    <ol class="results">
    <li><a href="#">Story hour</a><p>Ages 3 to 6, Saturdays.</p></li>
    <li><a href="#">Reading club</a><p>Ages 7 to 11.</p></li>
    <li><a href="#">Homework help</a><p>Weekday afternoons.</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 722: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.bar { display: flex; gap: 1rem; align-items: center; padding: .75rem
1.5rem; background: var(--accent); flex-wrap: wrap; }
```

```
.logo { font-weight: 700; text-decoration: none; color: var(--brand);
}
search { flex: 1 1 18rem; }
form { display: flex; }
input { flex: 1; padding: .6rem .9rem; border: 1px solid #bbb; border-
right: 0; border-radius: 999px 0 0 999px; font: inherit; }
button { padding: .6rem 1rem; border: 0; border-radius: 0 999px 999px
0; background: var(--brand); color: #fff; font: inherit; }
main { max-width: 40rem; margin: 1.5rem auto; padding: 0 1rem; }
.results { list-style: none; padding: 0; }
.results li { padding: 1rem 0; border-bottom: 1px solid var(--line); }
.results a { font-size: 1.1rem; font-weight: 600; }
.results p { margin: .2rem 0 0; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 722 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - Search</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="bar">	Introductory content: logo, title, navigation.
<search>	Container for search functionality.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q" class="sr-only">Search programmes</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search" placeholder="Search programmes...	Search field.
<datalist id="suggest">	Suggestions for an input linked with the list attribute.
<option value="Story hour">	One choice in a select or datalist.

Line	What it does
<button>Go</button>	A clickable button; inside a form it submits by default.
<main>	The unique content of this page; exactly one per page.
Search results	The main heading; only one per page.
3 results for <q>programme</q>	A paragraph of text.
<ol class="results">	Ordered (numbered) list; the order matters.
Story hour Ages 3 to 6, Saturdays.	A hyperlink; href gives the destination.
Reading club Ages 7 to 11.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
align-items: center;	Centres items on the cross axis.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--accent);	Background colour or image.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
font-weight: 700;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
flex: 1 1 18rem;	The item can grow and shrink from the given basis.
flex: 1;	All items share free space equally.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-right: 0;	The line around the element: width, style and colour.
border-radius: 999px 0 0 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).

Declaration	What it does
border-radius: 0 999px 999px 0;	Rounds the corners.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-size: 1.1rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Typing shows suggestions
- Label exists (hidden)
- Button attached to input visually
- Results are links with descriptions

Exercises

1. Highlight the matched word in results with <mark>.
2. Add filters with checkboxes in an aside.
3. Add 'no results' state styling.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 723: Search bar and results page for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Build a header search box with datalist suggestions and a joined input/button pair, plus a results list styled like a search engine.

Learning goals

- Use the search element, type=search and datalist
- Join an input and button with asymmetric border-radius
- Present results as an ordered list

Elements and CSS used

HTML elements	CSS features
search, form, label, input type=search, datalist, option, button, ol, li, a, q	flex: 1 1 18rem, border-radius (four values), border-right: 0, list-style: none

Build guide

1. Write the header with logo and <search> containing the form.
2. Add a datalist with one option per offer and link it with list=.
3. Add the results list.
4. Flex the bar; let the search area grow.
5. Round only the outer corners of input and button.

6. Style the results.

Project 723: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - Search</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="bar">
    <a class="logo" href="index.html">Nubian Guest House</a>
    <search>
      <form action="/search" role="search">
        <label for="q" class="sr-only">Search rooms</label>
        <input id="q" name="q" type="search" placeholder="Search
rooms" list="suggest" autocomplete="off">
        <datalist id="suggest">
    <option value="Garden room">
    <option value="Nile view suite">
    <option value="Family room">
    <option value="Rooftop dorm">
        </datalist>
        <button>Go</button>
      </form>
    </search>
  </header>
  <main>
    <h1>Search results</h1>
    <p>3 results for <q>room</q></p>
    <ol class="results">
    <li><a href="#">Garden room</a><p>Double bed, shared terrace.</
p></li>
    <li><a href="#">Nile view suite</a><p>Balcony and breakfast.</p></
li>
    <li><a href="#">Family room</a><p>Sleeps four.</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 723: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
```

```
.bar { display: flex; gap: 1rem; align-items: center; padding: .75rem
1.5rem; background: var(--accent); flex-wrap: wrap; }
.logo { font-weight: 700; text-decoration: none; color: var(--brand);
}
search { flex: 1 1 18rem; }
form { display: flex; }
input { flex: 1; padding: .6rem .9rem; border: 1px solid #bbb; border-
right: 0; border-radius: 999px 0 0 999px; font: inherit; }
button { padding: .6rem 1rem; border: 0; border-radius: 0 999px 999px
0; background: var(--brand); color: #fff; font: inherit; }
main { max-width: 40rem; margin: 1.5rem auto; padding: 0 1rem; }
.results { list-style: none; padding: 0; }
.results li { padding: 1rem 0; border-bottom: 1px solid var(--line); }
.results a { font-size: 1.1rem; font-weight: 600; }
.results p { margin: .2rem 0 0; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 723 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - Search</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="bar">	Introductory content: logo, title, navigation.
<search>	Container for search functionality.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q" class="sr-only">Search rooms</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search" placeholder="Search rooms" lis...	Search field.
<datalist id="suggest">	Suggestions for an input linked with the list attribute.
<option value="Garden room">	One choice in a select or datalist.

Line	What it does
<button>Go</button>	A clickable button; inside a form it submits by default.
<main>	The unique content of this page; exactly one per page.
Search results	The main heading; only one per page.
3 results for <q>room</q>	A paragraph of text.
<ol class="results">	Ordered (numbered) list; the order matters.
Garden room Double bed, shared terrace.	A hyperlink; href gives the destination.
Nile view suite Balcony and breakfast.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
align-items: center;	Centres items on the cross axis.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--accent);	Background colour or image.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
font-weight: 700;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
flex: 1 1 18rem;	The item can grow and shrink from the given basis.
flex: 1;	All items share free space equally.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-right: 0;	The line around the element: width, style and colour.
border-radius: 999px 0 0 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).

Declaration	What it does
border-radius: 0 999px 999px 0;	Rounds the corners.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-size: 1.1rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Typing shows suggestions
- Label exists (hidden)
- Button attached to input visually
- Results are links with descriptions

Exercises

1. Highlight the matched word in results with <mark>.
2. Add filters with checkboxes in an aside.
3. Add 'no results' state styling.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 724: Search bar and results page for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 2 | Files: index.html, styles.css

Brief

Build a header search box with datalist suggestions and a joined input/button pair, plus a results list styled like a search engine.

Learning goals

- Use the search element, type=search and datalist
- Join an input and button with asymmetric border-radius
- Present results as an ordered list

Elements and CSS used

HTML elements	CSS features
search, form, label, input type=search, datalist, option, button, ol, li, a, q	flex: 1 1 18rem, border-radius (four values), border-right: 0, list-style: none

Build guide

1. Write the header with logo and <search> containing the form.
2. Add a datalist with one option per offer and link it with list=.
3. Add the results list.
4. Flex the bar; let the search area grow.
5. Round only the outer corners of input and button.

6. Style the results.

Project 724: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - Search</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="bar">
    <a class="logo" href="index.html">Ismailia Cycling Store</a>
    <search>
      <form action="/search" role="search">
        <label for="q" class="sr-only">Search bikes</label>
        <input id="q" name="q" type="search" placeholder="Search
bikes" list="suggest" autocomplete="off">
        <datalist id="suggest">
    <option value="City bike">
    <option value="Mountain bike">
    <option value="Kids bike">
    <option value="Tune-up">
        </datalist>
        <button>Go</button>
      </form>
    </search>
  </header>
  <main>
    <h1>Search results</h1>
    <p>3 results for <q>bike</q></p>
    <ol class="results">
    <li><a href="#">City bike</a><p>Seven gears, basket.</p></li>
    <li><a href="#">Mountain bike</a><p>Front suspension.</p></li>
    <li><a href="#">Kids bike</a><p>20 inch wheels.</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 724: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.bar { display: flex; gap: 1rem; align-items: center; padding: .75rem
1.5rem; background: var(--accent); flex-wrap: wrap; }
```

```
.logo { font-weight: 700; text-decoration: none; color: var(--brand);
}
search { flex: 1 1 18rem; }
form { display: flex; }
input { flex: 1; padding: .6rem .9rem; border: 1px solid #bbb; border-
right: 0; border-radius: 999px 0 0 999px; font: inherit; }
button { padding: .6rem 1rem; border: 0; border-radius: 0 999px 999px
0; background: var(--brand); color: #fff; font: inherit; }
main { max-width: 40rem; margin: 1.5rem auto; padding: 0 1rem; }
.results { list-style: none; padding: 0; }
.results li { padding: 1rem 0; border-bottom: 1px solid var(--line); }
.results a { font-size: 1.1rem; font-weight: 600; }
.results p { margin: .2rem 0 0; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 724 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - Search</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="bar">	Introductory content: logo, title, navigation.
<search>	Container for search functionality.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q" class="sr-only">Search bikes</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search" placeholder="Search bikes" lis...	Search field.
<datalist id="suggest">	Suggestions for an input linked with the list attribute.
<option value="City bike">	One choice in a select or datalist.

Line	What it does
<button>Go</button>	A clickable button; inside a form it submits by default.
<main>	The unique content of this page; exactly one per page.
Search results	The main heading; only one per page.
3 results for <q>bike</q>	A paragraph of text.
<ol class="results">	Ordered (numbered) list; the order matters.
City bike Seven gears, basket.	A hyperlink; href gives the destination.
Mountain bike Front suspension.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
align-items: center;	Centres items on the cross axis.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--accent);	Background colour or image.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
font-weight: 700;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
flex: 1 1 18rem;	The item can grow and shrink from the given basis.
flex: 1;	All items share free space equally.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-right: 0;	The line around the element: width, style and colour.
border-radius: 999px 0 0 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).

Declaration	What it does
border-radius: 0 999px 999px 0;	Rounds the corners.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-size: 1.1rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Typing shows suggestions
- Label exists (hidden)
- Button attached to input visually
- Results are links with descriptions

Exercises

1. Highlight the matched word in results with <mark>.
2. Add filters with checkboxes in an aside.
3. Add 'no results' state styling.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 725: Search bar and results page for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 2 | Files: index.html, styles.css

Brief

Build a header search box with datalist suggestions and a joined input/button pair, plus a results list styled like a search engine.

Learning goals

- Use the search element, type=search and datalist
- Join an input and button with asymmetric border-radius
- Present results as an ordered list

Elements and CSS used

HTML elements	CSS features
search, form, label, input type=search, datalist, option, button, ol, li, a, q	flex: 1 1 18rem, border-radius (four values), border-right: 0, list-style: none

Build guide

1. Write the header with logo and <search> containing the form.
2. Add a datalist with one option per offer and link it with list=.
3. Add the results list.
4. Flex the bar; let the search area grow.
5. Round only the outer corners of input and button.

6. Style the results.

Project 725: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - Search</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="bar">
    <a class="logo" href="index.html">Minya Coding Club</a>
    <search>
      <form action="/search" role="search">
        <label for="q" class="sr-only">Search workshops</label>
        <input id="q" name="q" type="search" placeholder="Search
workshops" list="suggest" autocomplete="off">
        <datalist id="suggest">
    <option value="HTML weekend">
    <option value="CSS art">
    <option value="Scratch games">
    <option value="Hackathon">
        </datalist>
        <button>Go</button>
      </form>
    </search>
  </header>
  <main>
    <h1>Search results</h1>
    <p>3 results for <q>workshop</q></p>
    <ol class="results">
    <li><a href="#">HTML weekend</a><p>Build your first page.</p></li>
    <li><a href="#">CSS art</a><p>Draw with code.</p></li>
    <li><a href="#">Scratch games</a><p>Ages 10 to 13.</p></li>
    </ol>
  </main>
</body>
</html>
```

Project 725: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.bar { display: flex; gap: 1rem; align-items: center; padding: .75rem
1.5rem; background: var(--accent); flex-wrap: wrap; }
```

```
.logo { font-weight: 700; text-decoration: none; color: var(--brand);
}
search { flex: 1 1 18rem; }
form { display: flex; }
input { flex: 1; padding: .6rem .9rem; border: 1px solid #bbb; border-
right: 0; border-radius: 999px 0 0 999px; font: inherit; }
button { padding: .6rem 1rem; border: 0; border-radius: 0 999px 999px
0; background: var(--brand); color: #fff; font: inherit; }
main { max-width: 40rem; margin: 1.5rem auto; padding: 0 1rem; }
.results { list-style: none; padding: 0; }
.results li { padding: 1rem 0; border-bottom: 1px solid var(--line); }
.results a { font-size: 1.1rem; font-weight: 600; }
.results p { margin: .2rem 0 0; color: var(--muted); }
.sr-only { position: absolute; width: 1px; height: 1px; overflow:
hidden; clip: rect(0 0 0 0); white-space: nowrap; }
```

Project 725 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - Search</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="bar">	Introductory content: logo, title, navigation.
<search>	Container for search functionality.
<form action="/search" role="search">	A form; action is where the data goes, method how it is sent.
<label for="q" class="sr-only">Search workshops</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<input id="q" name="q" type="search" placeholder="Search workshops"...	Search field.
<datalist id="suggest">	Suggestions for an input linked with the list attribute.
<option value="HTML weekend">	One choice in a select or datalist.

Line	What it does
<button>Go</button>	A clickable button; inside a form it submits by default.
<main>	The unique content of this page; exactly one per page.
Search results	The main heading; only one per page.
3 results for <q>workshop</q>	A paragraph of text.
<ol class="results">	Ordered (numbered) list; the order matters.
HTML weekend Build your first page.	A hyperlink; href gives the destination.
CSS art Draw with code.	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
align-items: center;	Centres items on the cross axis.
padding: .75rem 1.5rem;	Space inside the element between its border and content.
background: var(--accent);	Background colour or image.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
font-weight: 700;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
flex: 1 1 18rem;	The item can grow and shrink from the given basis.
flex: 1;	All items share free space equally.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
border-right: 0;	The line around the element: width, style and colour.
border-radius: 999px 0 0 999px;	Fully rounded pill shape.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).

Declaration	What it does
border-radius: 0 999px 999px 0;	Rounds the corners.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-size: 1.1rem;	Size of the text.
.sr-only {	Visually hidden but still read by screen readers.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
clip: rect(0 0 0 0);	Part of the screen-reader-only pattern: clips the box to nothing.
white-space: nowrap;	Prevents text from wrapping to a new line.

Check your work

- Typing shows suggestions
- Label exists (hidden)
- Button attached to input visually
- Results are links with descriptions

Exercises

1. Highlight the matched word in results with <mark>.
2. Add filters with checkboxes in an aside.
3. Add 'no results' state styling.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Order progress tracker

Level 3 | 25 projects, one per theme

Show order status as a numbered step indicator built with CSS counters and pseudo-elements, plus native progress and meter elements.

Project 726: Order progress tracker for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 3 | Files: index.html, styles.css

Brief

Show order status as a numbered step indicator built with CSS counters and pseudo-elements, plus native progress and meter elements.

Learning goals

- Use counter-reset and counter-increment
- Use progress and meter
- Build connector lines with ::after

Elements and CSS used

HTML elements	CSS features
ol, li, progress, meter, label, strong	counter-reset, counter(), ::before/::after, translate, accent-color, z-index

Build guide

1. Write the ol with classes done/current and aria-current="step".
2. Add progress and meter elements with values.
3. Flex the list; each li gets equal width.
4. Number the circles with counters in ::before.
5. Draw connector lines with ::after.
6. Colour completed steps and the progress bar with accent-color.

Project 726: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Order status</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Your order</h1>
    <p>Order 1042: <strong>Learn HTML</strong></p>
    <ol class="steps">
      <li class="done">Received</li>
      <li class="done">Prepared</li>
      <li class="current" aria-current="step">On the way</li>
      <li>Delivered</li>
    </ol>
    <label for="p">Progress</label>
    <progress id="p" value="3" max="4">75%</progress>
    <h2>Rating so far</h2>
    <meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.
8 out of 5</meter> 4.8 / 5
  </main>
</body>
</html>
```

Project 726: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.steps { list-style: none; padding: 0; display: flex; counter-reset:
step; margin: 1.5rem 0; }
.steps li { flex: 1; text-align: center; position: relative; padding-
top: 2.4rem; font-size: .9rem; color: var(--muted); }
.steps li::before { counter-increment: step; content: counter(step);
position: absolute; top: 0; left: 50%; translate: -50% 0; width: 2rem;
 height: 2rem; border-radius: 50%; background: var(--line); color:
#fff; display: grid; place-items: center; font-weight: 700; }
.steps li::after { content: ""; position: absolute; top: 1rem; left: -
50%; width: 100%; height: 3px; background: var(--line); z-index: -1; }
.steps li:first-child::after { display: none; }
.steps .done::before, .steps .done::after, .steps .current::before {
```

```
  background: var(--brand); }
  .steps .current { color: var(--brand); font-weight: 700; }
  progress { width: 100%; height: 1rem; accent-color: var(--brand); }
  meter { width: 12rem; }
```

Project 726 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - Order status</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Your order	The main heading; only one per page.
Order 1042: Learn HTML	A paragraph of text.
<ol class="steps">	Ordered (numbered) list; the order matters.
<li class="done">Received	One list item.
<li class="current" aria-current="step">On the way	Tells assistive technology which item is the current page or step.
<label for="p">Progress</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<progress id="p" value="3" max="4">75%</progress>	Progress of a task.
Rating so far	Second-level heading for a section.
<meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.8...	A measurement within a known range.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
counter-reset: step;	Starts a CSS counter.
flex: 1;	All items share free space equally.
text-align: center;	Centres inline content such as text.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
font-size: .9rem;	Size of the text.
counter-increment: step;	Adds one to the counter for each matching element.
content: counter(step);	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
border-radius: 50%;	Turns a square into a circle.
background: var(--line);	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 700;	Thickness of the text.
.steps li::after {	Generated content inserted after the element's content.
width: 100%;	Fills the container width.
z-index: -1;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
.steps li:first-child::after {	The first child of its parent.
display: none;	Removes the element from rendering completely.
accent-color: var(--brand);	Colours native checkboxes, radios, progress and range controls.

Check your work

- Numbers generated by CSS, not typed
- Lines sit behind circles
- Current step announced with aria-current
- Progress has a label

Exercises

1. Animate the progress bar value with a transition on width (custom bar).
2. Make the tracker vertical on narrow screens.
3. Add estimated times under each step.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 727: Order progress tracker for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 3 | Files: index.html, styles.css

Brief

Show order status as a numbered step indicator built with CSS counters and pseudo-elements, plus native progress and meter elements.

Learning goals

- Use counter-reset and counter-increment
- Use progress and meter
- Build connector lines with ::after

Elements and CSS used

HTML elements	CSS features
ol, li, progress, meter, label, strong	counter-reset, counter(), ::before/::after, translate, accent-color, z-index

Build guide

1. Write the ol with classes done/current and aria-current="step".
2. Add progress and meter elements with values.
3. Flex the list; each li gets equal width.
4. Number the circles with counters in ::before.
5. Draw connector lines with ::after.
6. Colour completed steps and the progress bar with accent-color.

Project 727: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - Order status</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Your order</h1>
    <p>Order 1042: <strong>Sourdough loaf</strong></p>
    <ol class="steps">
      <li class="done">Received</li>
      <li class="done">Prepared</li>
      <li class="current" aria-current="step">On the way</li>
      <li>Delivered</li>
    </ol>
    <label for="p">Progress</label>
    <progress id="p" value="3" max="4">75%</progress>
    <h2>Rating so far</h2>
    <meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.
8 out of 5</meter> 4.8 / 5
  </main>
</body>
</html>
```

Project 727: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.steps { list-style: none; padding: 0; display: flex; counter-reset:
step; margin: 1.5rem 0; }
.steps li { flex: 1; text-align: center; position: relative; padding-
top: 2.4rem; font-size: .9rem; color: var(--muted); }
.steps li::before { counter-increment: step; content: counter(step);
position: absolute; top: 0; left: 50%; translate: -50% 0; width: 2rem;
 height: 2rem; border-radius: 50%; background: var(--line); color:
#fff; display: grid; place-items: center; font-weight: 700; }
.steps li::after { content: ""; position: absolute; top: 1rem; left: -
50%; width: 100%; height: 3px; background: var(--line); z-index: -1; }
.steps li:first-child::after { display: none; }
.steps .done::before, .steps .done::after, .steps .current::before {
```

```
  background: var(--brand); }
  .steps .current { color: var(--brand); font-weight: 700; }
  progress { width: 100%; height: 1rem; accent-color: var(--brand); }
  meter { width: 12rem; }
```

Project 727 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - Order status</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Your order	The main heading; only one per page.
Order 1042: Sourdough loaf	A paragraph of text.
<ol class="steps">	Ordered (numbered) list; the order matters.
<li class="done">Received	One list item.
<li class="current" aria-current="step">On the way	Tells assistive technology which item is the current page or step.
<label for="p">Progress</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<progress id="p" value="3" max="4">75%</progress>	Progress of a task.
Rating so far	Second-level heading for a section.
<meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.8...	A measurement within a known range.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
counter-reset: step;	Starts a CSS counter.
flex: 1;	All items share free space equally.
text-align: center;	Centres inline content such as text.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
font-size: .9rem;	Size of the text.
counter-increment: step;	Adds one to the counter for each matching element.
content: counter(step);	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
border-radius: 50%;	Turns a square into a circle.
background: var(--line);	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 700;	Thickness of the text.
.steps li::after {	Generated content inserted after the element's content.
width: 100%;	Fills the container width.
z-index: -1;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
.steps li:first-child::after {	The first child of its parent.
display: none;	Removes the element from rendering completely.
accent-color: var(--brand);	Colours native checkboxes, radios, progress and range controls.

Check your work

- Numbers generated by CSS, not typed
- Lines sit behind circles
- Current step announced with aria-current
- Progress has a label

Exercises

1. Animate the progress bar value with a transition on width (custom bar).
2. Make the tracker vertical on narrow screens.
3. Add estimated times under each step.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 728: Order progress tracker for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 3 | Files: index.html, styles.css

Brief

Show order status as a numbered step indicator built with CSS counters and pseudo-elements, plus native progress and meter elements.

Learning goals

- Use counter-reset and counter-increment
- Use progress and meter
- Build connector lines with ::after

Elements and CSS used

HTML elements	CSS features
ol, li, progress, meter, label, strong	counter-reset, counter(), ::before/::after, translate, accent-color, z-index

Build guide

1. Write the ol with classes done/current and aria-current="step".
2. Add progress and meter elements with values.
3. Flex the list; each li gets equal width.
4. Number the circles with counters in ::before.
5. Draw connector lines with ::after.
6. Colour completed steps and the progress bar with accent-color.

Project 728: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - Order status</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Your order</h1>
    <p>Order 1042: <strong>Morning yoga</strong></p>
    <ol class="steps">
      <li class="done">Received</li>
      <li class="done">Prepared</li>
      <li class="current" aria-current="step">On the way</li>
      <li>Delivered</li>
    </ol>
    <label for="p">Progress</label>
    <progress id="p" value="3" max="4">75%</progress>
    <h2>Rating so far</h2>
    <meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.
8 out of 5</meter> 4.8 / 5
  </main>
</body>
</html>
```

Project 728: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.steps { list-style: none; padding: 0; display: flex; counter-reset:
step; margin: 1.5rem 0; }
.steps li { flex: 1; text-align: center; position: relative; padding-
top: 2.4rem; font-size: .9rem; color: var(--muted); }
.steps li::before { counter-increment: step; content: counter(step);
position: absolute; top: 0; left: 50%; translate: -50% 0; width: 2rem;
 height: 2rem; border-radius: 50%; background: var(--line); color:
#fff; display: grid; place-items: center; font-weight: 700; }
.steps li::after { content: ""; position: absolute; top: 1rem; left: -
50%; width: 100%; height: 3px; background: var(--line); z-index: -1; }
.steps li:first-child::after { display: none; }
.steps .done::before, .steps .done::after, .steps .current::before {
```

```
  background: var(--brand); }
  .steps .current { color: var(--brand); font-weight: 700; }
  progress { width: 100%; height: 1rem; accent-color: var(--brand); }
  meter { width: 12rem; }
```

Project 728 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - Order status</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Your order	The main heading; only one per page.
Order 1042: Morning yoga	A paragraph of text.
<ol class="steps">	Ordered (numbered) list; the order matters.
<li class="done">Received	One list item.
<li class="current" aria-current="step">On the way	Tells assistive technology which item is the current page or step.
<label for="p">Progress</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<progress id="p" value="3" max="4">75%</progress>	Progress of a task.
Rating so far	Second-level heading for a section.
<meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.8...	A measurement within a known range.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
counter-reset: step;	Starts a CSS counter.
flex: 1;	All items share free space equally.
text-align: center;	Centres inline content such as text.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
font-size: .9rem;	Size of the text.
counter-increment: step;	Adds one to the counter for each matching element.
content: counter(step);	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
border-radius: 50%;	Turns a square into a circle.
background: var(--line);	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 700;	Thickness of the text.
.steps li::after {	Generated content inserted after the element's content.
width: 100%;	Fills the container width.
z-index: -1;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
.steps li:first-child::after {	The first child of its parent.
display: none;	Removes the element from rendering completely.
accent-color: var(--brand);	Colours native checkboxes, radios, progress and range controls.

Check your work

- Numbers generated by CSS, not typed
- Lines sit behind circles
- Current step announced with aria-current
- Progress has a label

Exercises

1. Animate the progress bar value with a transition on width (custom bar).
2. Make the tracker vertical on narrow screens.
3. Add estimated times under each step.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 729: Order progress tracker for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 3 | Files: index.html, styles.css

Brief

Show order status as a numbered step indicator built with CSS counters and pseudo-elements, plus native progress and meter elements.

Learning goals

- Use counter-reset and counter-increment
- Use progress and meter
- Build connector lines with ::after

Elements and CSS used

HTML elements	CSS features
ol, li, progress, meter, label, strong	counter-reset, counter(), ::before/::after, translate, accent-color, z-index

Build guide

1. Write the ol with classes done/current and aria-current="step".
2. Add progress and meter elements with values.
3. Flex the list; each li gets equal width.
4. Number the circles with counters in ::before.
5. Draw connector lines with ::after.
6. Colour completed steps and the progress bar with accent-color.

Project 729: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - Order status</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Your order</h1>
    <p>Order 1042: <strong>Check-up</strong></p>
    <ol class="steps">
      <li class="done">Received</li>
      <li class="done">Prepared</li>
      <li class="current" aria-current="step">On the way</li>
      <li>Delivered</li>
    </ol>
    <label for="p">Progress</label>
    <progress id="p" value="3" max="4">75%</progress>
    <h2>Rating so far</h2>
    <meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.
8 out of 5</meter> 4.8 / 5
  </main>
</body>
</html>
```

Project 729: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.steps { list-style: none; padding: 0; display: flex; counter-reset:
step; margin: 1.5rem 0; }
.steps li { flex: 1; text-align: center; position: relative; padding-
top: 2.4rem; font-size: .9rem; color: var(--muted); }
.steps li::before { counter-increment: step; content: counter(step);
position: absolute; top: 0; left: 50%; translate: -50% 0; width: 2rem;
 height: 2rem; border-radius: 50%; background: var(--line); color:
#fff; display: grid; place-items: center; font-weight: 700; }
.steps li::after { content: ""; position: absolute; top: 1rem; left: -
50%; width: 100%; height: 3px; background: var(--line); z-index: -1; }
.steps li:first-child::after { display: none; }
.steps .done::before, .steps .done::after, .steps .current::before {
```

```
  background: var(--brand); }
  .steps .current { color: var(--brand); font-weight: 700; }
  progress { width: 100%; height: 1rem; accent-color: var(--brand); }
  meter { width: 12rem; }
```

Project 729 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - Order status</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Your order	The main heading; only one per page.
Order 1042: Check-up	A paragraph of text.
<ol class="steps">	Ordered (numbered) list; the order matters.
<li class="done">Received	One list item.
<li class="current" aria-current="step">On the way	Tells assistive technology which item is the current page or step.
<label for="p">Progress</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<progress id="p" value="3" max="4">75%</progress>	Progress of a task.
Rating so far	Second-level heading for a section.
<meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.8...	A measurement within a known range.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
counter-reset: step;	Starts a CSS counter.
flex: 1;	All items share free space equally.
text-align: center;	Centres inline content such as text.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
font-size: .9rem;	Size of the text.
counter-increment: step;	Adds one to the counter for each matching element.
content: counter(step);	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
border-radius: 50%;	Turns a square into a circle.
background: var(--line);	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 700;	Thickness of the text.
.steps li::after {	Generated content inserted after the element's content.
width: 100%;	Fills the container width.
z-index: -1;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
.steps li:first-child::after {	The first child of its parent.
display: none;	Removes the element from rendering completely.
accent-color: var(--brand);	Colours native checkboxes, radios, progress and range controls.

Check your work

- Numbers generated by CSS, not typed
- Lines sit behind circles
- Current step announced with aria-current
- Progress has a label

Exercises

1. Animate the progress bar value with a transition on width (custom bar).
2. Make the tracker vertical on narrow screens.
3. Add estimated times under each step.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 730: Order progress tracker for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 3 | Files: index.html, styles.css

Brief

Show order status as a numbered step indicator built with CSS counters and pseudo-elements, plus native progress and meter elements.

Learning goals

- Use counter-reset and counter-increment
- Use progress and meter
- Build connector lines with ::after

Elements and CSS used

HTML elements	CSS features
ol, li, progress, meter, label, strong	counter-reset, counter(), ::before/::after, translate, accent-color, z-index

Build guide

1. Write the ol with classes done/current and aria-current="step".
2. Add progress and meter elements with values.
3. Flex the list; each li gets equal width.
4. Number the circles with counters in ::before.
5. Draw connector lines with ::after.
6. Colour completed steps and the progress bar with accent-color.

Project 730: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - Order status</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Your order</h1>
    <p>Order 1042: <strong>Luxor day trip</strong></p>
    <ol class="steps">
      <li class="done">Received</li>
      <li class="done">Prepared</li>
      <li class="current" aria-current="step">On the way</li>
      <li>Delivered</li>
    </ol>
    <label for="p">Progress</label>
    <progress id="p" value="3" max="4">75%</progress>
    <h2>Rating so far</h2>
    <meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.
8 out of 5</meter> 4.8 / 5
  </main>
</body>
</html>
```

Project 730: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.steps { list-style: none; padding: 0; display: flex; counter-reset:
step; margin: 1.5rem 0; }
.steps li { flex: 1; text-align: center; position: relative; padding-
top: 2.4rem; font-size: .9rem; color: var(--muted); }
.steps li::before { counter-increment: step; content: counter(step);
position: absolute; top: 0; left: 50%; translate: -50% 0; width: 2rem;
 height: 2rem; border-radius: 50%; background: var(--line); color:
#fff; display: grid; place-items: center; font-weight: 700; }
.steps li::after { content: ""; position: absolute; top: 1rem; left: -
50%; width: 100%; height: 3px; background: var(--line); z-index: -1; }
.steps li:first-child::after { display: none; }
.steps .done::before, .steps .done::after, .steps .current::before {
```

```
  background: var(--brand); }
  .steps .current { color: var(--brand); font-weight: 700; }
  progress { width: 100%; height: 1rem; accent-color: var(--brand); }
  meter { width: 12rem; }
```

Project 730 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - Order status</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Your order	The main heading; only one per page.
Order 1042: Luxor day trip	A paragraph of text.
<ol class="steps">	Ordered (numbered) list; the order matters.
<li class="done">Received	One list item.
<li class="current" aria-current="step">On the way	Tells assistive technology which item is the current page or step.
<label for="p">Progress</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<progress id="p" value="3" max="4">75%</progress>	Progress of a task.
Rating so far	Second-level heading for a section.
<meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.8...	A measurement within a known range.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
counter-reset: step;	Starts a CSS counter.
flex: 1;	All items share free space equally.
text-align: center;	Centres inline content such as text.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
font-size: .9rem;	Size of the text.
counter-increment: step;	Adds one to the counter for each matching element.
content: counter(step);	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
border-radius: 50%;	Turns a square into a circle.
background: var(--line);	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 700;	Thickness of the text.
.steps li::after {	Generated content inserted after the element's content.
width: 100%;	Fills the container width.
z-index: -1;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
.steps li:first-child::after {	The first child of its parent.
display: none;	Removes the element from rendering completely.
accent-color: var(--brand);	Colours native checkboxes, radios, progress and range controls.

Check your work

- Numbers generated by CSS, not typed
- Lines sit behind circles
- Current step announced with aria-current
- Progress has a label

Exercises

1. Animate the progress bar value with a transition on width (custom bar).
2. Make the tracker vertical on narrow screens.
3. Add estimated times under each step.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 731: Order progress tracker for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 3 | Files: index.html, styles.css

Brief

Show order status as a numbered step indicator built with CSS counters and pseudo-elements, plus native progress and meter elements.

Learning goals

- Use counter-reset and counter-increment
- Use progress and meter
- Build connector lines with ::after

Elements and CSS used

HTML elements	CSS features
ol, li, progress, meter, label, strong	counter-reset, counter(), ::before/::after, translate, accent-color, z-index

Build guide

1. Write the ol with classes done/current and aria-current="step".
2. Add progress and meter elements with values.
3. Flex the list; each li gets equal width.
4. Number the circles with counters in ::before.
5. Draw connector lines with ::after.

6. Colour completed steps and the progress bar with accent-color.

Project 731: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - Order status</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Your order</h1>
    <p>Order 1042: <strong>English A1</strong></p>
    <ol class="steps">
      <li class="done">Received</li>
      <li class="done">Prepared</li>
      <li class="current" aria-current="step">On the way</li>
      <li>Delivered</li>
    </ol>
    <label for="p">Progress</label>
    <progress id="p" value="3" max="4">75%</progress>
    <h2>Rating so far</h2>
    <meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.
8 out of 5</meter> 4.8 / 5
  </main>
</body>
</html>
```

Project 731: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.steps { list-style: none; padding: 0; display: flex; counter-reset:
step; margin: 1.5rem 0; }
.steps li { flex: 1; text-align: center; position: relative; padding-
top: 2.4rem; font-size: .9rem; color: var(--muted); }
.steps li::before { counter-increment: step; content: counter(step);
position: absolute; top: 0; left: 50%; translate: -50% 0; width: 2rem;
 height: 2rem; border-radius: 50%; background: var(--line); color:
#fff; display: grid; place-items: center; font-weight: 700; }
.steps li::after { content: ""; position: absolute; top: 1rem; left: -
50%; width: 100%; height: 3px; background: var(--line); z-index: -1; }
.steps li:first-child::after { display: none; }
.steps .done::before, .steps .done::after, .steps .current::before {
```

```
  background: var(--brand); }
  .steps .current { color: var(--brand); font-weight: 700; }
  progress { width: 100%; height: 1rem; accent-color: var(--brand); }
  meter { width: 12rem; }
```

Project 731 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - Order status</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Your order	The main heading; only one per page.
Order 1042: English A1	A paragraph of text.
<ol class="steps">	Ordered (numbered) list; the order matters.
<li class="done">Received	One list item.
<li class="current" aria-current="step">On the way	Tells assistive technology which item is the current page or step.
<label for="p">Progress</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<progress id="p" value="3" max="4">75%</progress>	Progress of a task.
Rating so far	Second-level heading for a section.
<meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.8...	A measurement within a known range.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
counter-reset: step;	Starts a CSS counter.
flex: 1;	All items share free space equally.
text-align: center;	Centres inline content such as text.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
font-size: .9rem;	Size of the text.
counter-increment: step;	Adds one to the counter for each matching element.
content: counter(step);	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
border-radius: 50%;	Turns a square into a circle.
background: var(--line);	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 700;	Thickness of the text.
.steps li::after {	Generated content inserted after the element's content.
width: 100%;	Fills the container width.
z-index: -1;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
.steps li:first-child::after {	The first child of its parent.
display: none;	Removes the element from rendering completely.
accent-color: var(--brand);	Colours native checkboxes, radios, progress and range controls.

Check your work

- Numbers generated by CSS, not typed
- Lines sit behind circles
- Current step announced with aria-current
- Progress has a label

Exercises

1. Animate the progress bar value with a transition on width (custom bar).
2. Make the tracker vertical on narrow screens.
3. Add estimated times under each step.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 732: Order progress tracker for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 3 | Files: index.html, styles.css

Brief

Show order status as a numbered step indicator built with CSS counters and pseudo-elements, plus native progress and meter elements.

Learning goals

- Use counter-reset and counter-increment
- Use progress and meter
- Build connector lines with ::after

Elements and CSS used

HTML elements	CSS features
ol, li, progress, meter, label, strong	counter-reset, counter(), ::before/::after, translate, accent-color, z-index

Build guide

1. Write the ol with classes done/current and aria-current="step".
2. Add progress and meter elements with values.
3. Flex the list; each li gets equal width.
4. Number the circles with counters in ::before.
5. Draw connector lines with ::after.
6. Colour completed steps and the progress bar with accent-color.

Project 732: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - Order status</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Your order</h1>
    <p>Order 1042: <strong>Flat white</strong></p>
    <ol class="steps">
      <li class="done">Received</li>
      <li class="done">Prepared</li>
      <li class="current" aria-current="step">On the way</li>
      <li>Delivered</li>
    </ol>
    <label for="p">Progress</label>
    <progress id="p" value="3" max="4">75%</progress>
    <h2>Rating so far</h2>
    <meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.
8 out of 5</meter> 4.8 / 5
  </main>
</body>
</html>
```

Project 732: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.steps { list-style: none; padding: 0; display: flex; counter-reset:
step; margin: 1.5rem 0; }
.steps li { flex: 1; text-align: center; position: relative; padding-
top: 2.4rem; font-size: .9rem; color: var(--muted); }
.steps li::before { counter-increment: step; content: counter(step);
position: absolute; top: 0; left: 50%; translate: -50% 0; width: 2rem;
 height: 2rem; border-radius: 50%; background: var(--line); color:
#fff; display: grid; place-items: center; font-weight: 700; }
.steps li::after { content: ""; position: absolute; top: 1rem; left: -
50%; width: 100%; height: 3px; background: var(--line); z-index: -1; }
.steps li:first-child::after { display: none; }
.steps .done::before, .steps .done::after, .steps .current::before {
```

```
  background: var(--brand); }
  .steps .current { color: var(--brand); font-weight: 700; }
  progress { width: 100%; height: 1rem; accent-color: var(--brand); }
  meter { width: 12rem; }
```

Project 732 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - Order status</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Your order	The main heading; only one per page.
Order 1042: Flat white	A paragraph of text.
<ol class="steps">	Ordered (numbered) list; the order matters.
<li class="done">Received	One list item.
<li class="current" aria-current="step">On the way	Tells assistive technology which item is the current page or step.
<label for="p">Progress</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<progress id="p" value="3" max="4">75%</progress>	Progress of a task.
Rating so far	Second-level heading for a section.
<meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.8...	A measurement within a known range.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
counter-reset: step;	Starts a CSS counter.
flex: 1;	All items share free space equally.
text-align: center;	Centres inline content such as text.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
font-size: .9rem;	Size of the text.
counter-increment: step;	Adds one to the counter for each matching element.
content: counter(step);	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
border-radius: 50%;	Turns a square into a circle.
background: var(--line);	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 700;	Thickness of the text.
.steps li::after {	Generated content inserted after the element's content.
width: 100%;	Fills the container width.
z-index: -1;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
.steps li:first-child::after {	The first child of its parent.
display: none;	Removes the element from rendering completely.
accent-color: var(--brand);	Colours native checkboxes, radios, progress and range controls.

Check your work

- Numbers generated by CSS, not typed
- Lines sit behind circles
- Current step announced with aria-current
- Progress has a label

Exercises

1. Animate the progress bar value with a transition on width (custom bar).
2. Make the tracker vertical on narrow screens.
3. Add estimated times under each step.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 733: Order progress tracker for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 3 | Files: index.html, styles.css

Brief

Show order status as a numbered step indicator built with CSS counters and pseudo-elements, plus native progress and meter elements.

Learning goals

- Use counter-reset and counter-increment
- Use progress and meter
- Build connector lines with ::after

Elements and CSS used

HTML elements	CSS features
ol, li, progress, meter, label, strong	counter-reset, counter(), ::before/::after, translate, accent-color, z-index

Build guide

1. Write the ol with classes done/current and aria-current="step".
2. Add progress and meter elements with values.
3. Flex the list; each li gets equal width.
4. Number the circles with counters in ::before.
5. Draw connector lines with ::after.

6. Colour completed steps and the progress bar with accent-color.

Project 733: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - Order status</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Your order</h1>
    <p>Order 1042: <strong>Mount Sinai sunrise</strong></p>
    <ol class="steps">
      <li class="done">Received</li>
      <li class="done">Prepared</li>
      <li class="current" aria-current="step">On the way</li>
      <li>Delivered</li>
    </ol>
    <label for="p">Progress</label>
    <progress id="p" value="3" max="4">75%</progress>
    <h2>Rating so far</h2>
    <meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.
8 out of 5</meter> 4.8 / 5
  </main>
</body>
</html>
```

Project 733: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.steps { list-style: none; padding: 0; display: flex; counter-reset:
step; margin: 1.5rem 0; }
.steps li { flex: 1; text-align: center; position: relative; padding-
top: 2.4rem; font-size: .9rem; color: var(--muted); }
.steps li::before { counter-increment: step; content: counter(step);
position: absolute; top: 0; left: 50%; translate: -50% 0; width: 2rem;
 height: 2rem; border-radius: 50%; background: var(--line); color:
#fff; display: grid; place-items: center; font-weight: 700; }
.steps li::after { content: ""; position: absolute; top: 1rem; left: -
50%; width: 100%; height: 3px; background: var(--line); z-index: -1; }
.steps li:first-child::after { display: none; }
.steps .done::before, .steps .done::after, .steps .current::before {
```

```
  background: var(--brand); }
  .steps .current { color: var(--brand); font-weight: 700; }
  progress { width: 100%; height: 1rem; accent-color: var(--brand); }
  meter { width: 12rem; }
```

Project 733 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - Order status</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Your order	The main heading; only one per page.
Order 1042: Mount Sinai sunrise	A paragraph of text.
<ol class="steps">	Ordered (numbered) list; the order matters.
<li class="done">Received	One list item.
<li class="current" aria-current="step">On the way	Tells assistive technology which item is the current page or step.
<label for="p">Progress</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<progress id="p" value="3" max="4">75%</progress>	Progress of a task.
Rating so far	Second-level heading for a section.
<meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.8...	A measurement within a known range.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
counter-reset: step;	Starts a CSS counter.
flex: 1;	All items share free space equally.
text-align: center;	Centres inline content such as text.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
font-size: .9rem;	Size of the text.
counter-increment: step;	Adds one to the counter for each matching element.
content: counter(step);	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
border-radius: 50%;	Turns a square into a circle.
background: var(--line);	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 700;	Thickness of the text.
.steps li::after {	Generated content inserted after the element's content.
width: 100%;	Fills the container width.
z-index: -1;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
.steps li:first-child::after {	The first child of its parent.
display: none;	Removes the element from rendering completely.
accent-color: var(--brand);	Colours native checkboxes, radios, progress and range controls.

Check your work

- Numbers generated by CSS, not typed
- Lines sit behind circles
- Current step announced with aria-current
- Progress has a label

Exercises

1. Animate the progress bar value with a transition on width (custom bar).
2. Make the tracker vertical on narrow screens.
3. Add estimated times under each step.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 734: Order progress tracker for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 3 | Files: index.html, styles.css

Brief

Show order status as a numbered step indicator built with CSS counters and pseudo-elements, plus native progress and meter elements.

Learning goals

- Use counter-reset and counter-increment
- Use progress and meter
- Build connector lines with ::after

Elements and CSS used

HTML elements	CSS features
ol, li, progress, meter, label, strong	counter-reset, counter(), ::before/::after, translate, accent-color, z-index

Build guide

1. Write the ol with classes done/current and aria-current="step".
2. Add progress and meter elements with values.
3. Flex the list; each li gets equal width.
4. Number the circles with counters in ::before.
5. Draw connector lines with ::after.

6. Colour completed steps and the progress bar with accent-color.

Project 734: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - Order status</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Your order</h1>
    <p>Order 1042: <strong>Portrait session</strong></p>
    <ol class="steps">
      <li class="done">Received</li>
      <li class="done">Prepared</li>
      <li class="current" aria-current="step">On the way</li>
      <li>Delivered</li>
    </ol>
    <label for="p">Progress</label>
    <progress id="p" value="3" max="4">75%</progress>
    <h2>Rating so far</h2>
    <meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.
8 out of 5</meter> 4.8 / 5
  </main>
</body>
</html>
```

Project 734: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.steps { list-style: none; padding: 0; display: flex; counter-reset:
step; margin: 1.5rem 0; }
.steps li { flex: 1; text-align: center; position: relative; padding-
top: 2.4rem; font-size: .9rem; color: var(--muted); }
.steps li::before { counter-increment: step; content: counter(step);
position: absolute; top: 0; left: 50%; translate: -50% 0; width: 2rem;
 height: 2rem; border-radius: 50%; background: var(--line); color:
#fff; display: grid; place-items: center; font-weight: 700; }
.steps li::after { content: ""; position: absolute; top: 1rem; left: -
50%; width: 100%; height: 3px; background: var(--line); z-index: -1; }
.steps li:first-child::after { display: none; }
.steps .done::before, .steps .done::after, .steps .current::before {
```

```
  background: var(--brand); }
  .steps .current { color: var(--brand); font-weight: 700; }
  progress { width: 100%; height: 1rem; accent-color: var(--brand); }
  meter { width: 12rem; }
```

Project 734 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - Order status</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Your order	The main heading; only one per page.
Order 1042: Portrait session	A paragraph of text.
<ol class="steps">	Ordered (numbered) list; the order matters.
<li class="done">Received	One list item.
<li class="current" aria-current="step">On the way	Tells assistive technology which item is the current page or step.
<label for="p">Progress</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<progress id="p" value="3" max="4">75%</progress>	Progress of a task.
Rating so far	Second-level heading for a section.
<meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.8...	A measurement within a known range.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
counter-reset: step;	Starts a CSS counter.
flex: 1;	All items share free space equally.
text-align: center;	Centres inline content such as text.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
font-size: .9rem;	Size of the text.
counter-increment: step;	Adds one to the counter for each matching element.
content: counter(step);	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
border-radius: 50%;	Turns a square into a circle.
background: var(--line);	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 700;	Thickness of the text.
.steps li::after {	Generated content inserted after the element's content.
width: 100%;	Fills the container width.
z-index: -1;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
.steps li:first-child::after {	The first child of its parent.
display: none;	Removes the element from rendering completely.
accent-color: var(--brand);	Colours native checkboxes, radios, progress and range controls.

Check your work

- Numbers generated by CSS, not typed
- Lines sit behind circles
- Current step announced with aria-current
- Progress has a label

Exercises

1. Animate the progress bar value with a transition on width (custom bar).
2. Make the tracker vertical on narrow screens.
3. Add estimated times under each step.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 735: Order progress tracker for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 3 | Files: index.html, styles.css

Brief

Show order status as a numbered step indicator built with CSS counters and pseudo-elements, plus native progress and meter elements.

Learning goals

- Use counter-reset and counter-increment
- Use progress and meter
- Build connector lines with ::after

Elements and CSS used

HTML elements	CSS features
ol, li, progress, meter, label, strong	counter-reset, counter(), ::before/::after, translate, accent-color, z-index

Build guide

1. Write the ol with classes done/current and aria-current="step".
2. Add progress and meter elements with values.
3. Flex the list; each li gets equal width.
4. Number the circles with counters in ::before.
5. Draw connector lines with ::after.
6. Colour completed steps and the progress bar with accent-color.

Project 735: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - Order status</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Your order</h1>
    <p>Order 1042: <strong>Dotted notebook</strong></p>
    <ol class="steps">
      <li class="done">Received</li>
      <li class="done">Prepared</li>
      <li class="current" aria-current="step">On the way</li>
      <li>Delivered</li>
    </ol>
    <label for="p">Progress</label>
    <progress id="p" value="3" max="4">75%</progress>
    <h2>Rating so far</h2>
    <meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.
8 out of 5</meter> 4.8 / 5
  </main>
</body>
</html>
```

Project 735: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.steps { list-style: none; padding: 0; display: flex; counter-reset:
step; margin: 1.5rem 0; }
.steps li { flex: 1; text-align: center; position: relative; padding-
top: 2.4rem; font-size: .9rem; color: var(--muted); }
.steps li::before { counter-increment: step; content: counter(step);
position: absolute; top: 0; left: 50%; translate: -50% 0; width: 2rem;
 height: 2rem; border-radius: 50%; background: var(--line); color:
#fff; display: grid; place-items: center; font-weight: 700; }
.steps li::after { content: ""; position: absolute; top: 1rem; left: -
50%; width: 100%; height: 3px; background: var(--line); z-index: -1; }
.steps li:first-child::after { display: none; }
.steps .done::before, .steps .done::after, .steps .current::before {
```

```
  background: var(--brand); }
  .steps .current { color: var(--brand); font-weight: 700; }
  progress { width: 100%; height: 1rem; accent-color: var(--brand); }
  meter { width: 12rem; }
```

Project 735 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - Order status</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Your order	The main heading; only one per page.
Order 1042: Dotted notebook	A paragraph of text.
<ol class="steps">	Ordered (numbered) list; the order matters.
<li class="done">Received	One list item.
<li class="current" aria-current="step">On the way	Tells assistive technology which item is the current page or step.
<label for="p">Progress</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<progress id="p" value="3" max="4">75%</progress>	Progress of a task.
Rating so far	Second-level heading for a section.
<meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.8...	A measurement within a known range.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
counter-reset: step;	Starts a CSS counter.
flex: 1;	All items share free space equally.
text-align: center;	Centres inline content such as text.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
font-size: .9rem;	Size of the text.
counter-increment: step;	Adds one to the counter for each matching element.
content: counter(step);	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
border-radius: 50%;	Turns a square into a circle.
background: var(--line);	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 700;	Thickness of the text.
.steps li::after {	Generated content inserted after the element's content.
width: 100%;	Fills the container width.
z-index: -1;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
.steps li:first-child::after {	The first child of its parent.
display: none;	Removes the element from rendering completely.
accent-color: var(--brand);	Colours native checkboxes, radios, progress and range controls.

Check your work

- Numbers generated by CSS, not typed
- Lines sit behind circles
- Current step announced with aria-current
- Progress has a label

Exercises

1. Animate the progress bar value with a transition on width (custom bar).
2. Make the tracker vertical on narrow screens.
3. Add estimated times under each step.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 736: Order progress tracker for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 3 | Files: index.html, styles.css

Brief

Show order status as a numbered step indicator built with CSS counters and pseudo-elements, plus native progress and meter elements.

Learning goals

- Use counter-reset and counter-increment
- Use progress and meter
- Build connector lines with ::after

Elements and CSS used

HTML elements	CSS features
ol, li, progress, meter, label, strong	counter-reset, counter(), ::before/::after, translate, accent-color, z-index

Build guide

1. Write the ol with classes done/current and aria-current="step".
2. Add progress and meter elements with values.
3. Flex the list; each li gets equal width.
4. Number the circles with counters in ::before.
5. Draw connector lines with ::after.
6. Colour completed steps and the progress bar with accent-color.

Project 736: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - Order status</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Your order</h1>
    <p>Order 1042: <strong>Monstera</strong></p>
    <ol class="steps">
      <li class="done">Received</li>
      <li class="done">Prepared</li>
      <li class="current" aria-current="step">On the way</li>
      <li>Delivered</li>
    </ol>
    <label for="p">Progress</label>
    <progress id="p" value="3" max="4">75%</progress>
    <h2>Rating so far</h2>
    <meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.
8 out of 5</meter> 4.8 / 5
  </main>
</body>
</html>
```

Project 736: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.steps { list-style: none; padding: 0; display: flex; counter-reset:
step; margin: 1.5rem 0; }
.steps li { flex: 1; text-align: center; position: relative; padding-
top: 2.4rem; font-size: .9rem; color: var(--muted); }
.steps li::before { counter-increment: step; content: counter(step);
position: absolute; top: 0; left: 50%; translate: -50% 0; width: 2rem;
 height: 2rem; border-radius: 50%; background: var(--line); color:
#fff; display: grid; place-items: center; font-weight: 700; }
.steps li::after { content: ""; position: absolute; top: 1rem; left: -
50%; width: 100%; height: 3px; background: var(--line); z-index: -1; }
.steps li:first-child::after { display: none; }
.steps .done::before, .steps .done::after, .steps .current::before {
```

```
  background: var(--brand); }
  .steps .current { color: var(--brand); font-weight: 700; }
  progress { width: 100%; height: 1rem; accent-color: var(--brand); }
  meter { width: 12rem; }
```

Project 736 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - Order status</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Your order	The main heading; only one per page.
Order 1042: Monstera	A paragraph of text.
<ol class="steps">	Ordered (numbered) list; the order matters.
<li class="done">Received	One list item.
<li class="current" aria-current="step">On the way	Tells assistive technology which item is the current page or step.
<label for="p">Progress</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<progress id="p" value="3" max="4">75%</progress>	Progress of a task.
Rating so far	Second-level heading for a section.
<meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.8...	A measurement within a known range.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
counter-reset: step;	Starts a CSS counter.
flex: 1;	All items share free space equally.
text-align: center;	Centres inline content such as text.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
font-size: .9rem;	Size of the text.
counter-increment: step;	Adds one to the counter for each matching element.
content: counter(step);	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
border-radius: 50%;	Turns a square into a circle.
background: var(--line);	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 700;	Thickness of the text.
.steps li::after {	Generated content inserted after the element's content.
width: 100%;	Fills the container width.
z-index: -1;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
.steps li:first-child::after {	The first child of its parent.
display: none;	Removes the element from rendering completely.
accent-color: var(--brand);	Colours native checkboxes, radios, progress and range controls.

Check your work

- Numbers generated by CSS, not typed
- Lines sit behind circles
- Current step announced with aria-current
- Progress has a label

Exercises

1. Animate the progress bar value with a transition on width (custom bar).
2. Make the tracker vertical on narrow screens.
3. Add estimated times under each step.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 737: Order progress tracker for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 3 | Files: index.html, styles.css

Brief

Show order status as a numbered step indicator built with CSS counters and pseudo-elements, plus native progress and meter elements.

Learning goals

- Use counter-reset and counter-increment
- Use progress and meter
- Build connector lines with ::after

Elements and CSS used

HTML elements	CSS features
ol, li, progress, meter, label, strong	counter-reset, counter(), ::before/::after, translate, accent-color, z-index

Build guide

1. Write the ol with classes done/current and aria-current="step".
2. Add progress and meter elements with values.
3. Flex the list; each li gets equal width.
4. Number the circles with counters in ::before.
5. Draw connector lines with ::after.
6. Colour completed steps and the progress bar with accent-color.

Project 737: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - Order status</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Your order</h1>
    <p>Order 1042: <strong>Oak dining table</strong></p>
    <ol class="steps">
      <li class="done">Received</li>
      <li class="done">Prepared</li>
      <li class="current" aria-current="step">On the way</li>
      <li>Delivered</li>
    </ol>
    <label for="p">Progress</label>
    <progress id="p" value="3" max="4">75%</progress>
    <h2>Rating so far</h2>
    <meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.
8 out of 5</meter> 4.8 / 5
  </main>
</body>
</html>
```

Project 737: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.steps { list-style: none; padding: 0; display: flex; counter-reset:
step; margin: 1.5rem 0; }
.steps li { flex: 1; text-align: center; position: relative; padding-
top: 2.4rem; font-size: .9rem; color: var(--muted); }
.steps li::before { counter-increment: step; content: counter(step);
position: absolute; top: 0; left: 50%; translate: -50% 0; width: 2rem;
 height: 2rem; border-radius: 50%; background: var(--line); color:
#fff; display: grid; place-items: center; font-weight: 700; }
.steps li::after { content: ""; position: absolute; top: 1rem; left: -
50%; width: 100%; height: 3px; background: var(--line); z-index: -1; }
.steps li:first-child::after { display: none; }
.steps .done::before, .steps .done::after, .steps .current::before {
```

```
  background: var(--brand); }
  .steps .current { color: var(--brand); font-weight: 700; }
  progress { width: 100%; height: 1rem; accent-color: var(--brand); }
  meter { width: 12rem; }
```

Project 737 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - Order status</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Your order	The main heading; only one per page.
Order 1042: Oak dining table	A paragraph of text.
<ol class="steps">	Ordered (numbered) list; the order matters.
<li class="done">Received	One list item.
<li class="current" aria-current="step">On the way	Tells assistive technology which item is the current page or step.
<label for="p">Progress</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<progress id="p" value="3" max="4">75%</progress>	Progress of a task.
Rating so far	Second-level heading for a section.
<meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.8...	A measurement within a known range.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
counter-reset: step;	Starts a CSS counter.
flex: 1;	All items share free space equally.
text-align: center;	Centres inline content such as text.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
font-size: .9rem;	Size of the text.
counter-increment: step;	Adds one to the counter for each matching element.
content: counter(step);	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
border-radius: 50%;	Turns a square into a circle.
background: var(--line);	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 700;	Thickness of the text.
.steps li::after {	Generated content inserted after the element's content.
width: 100%;	Fills the container width.
z-index: -1;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
.steps li:first-child::after {	The first child of its parent.
display: none;	Removes the element from rendering completely.
accent-color: var(--brand);	Colours native checkboxes, radios, progress and range controls.

Check your work

- Numbers generated by CSS, not typed
- Lines sit behind circles
- Current step announced with aria-current
- Progress has a label

Exercises

1. Animate the progress bar value with a transition on width (custom bar).
2. Make the tracker vertical on narrow screens.
3. Add estimated times under each step.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 738: Order progress tracker for Byte Repair

Theme: Byte Repair (Nasr City) | Level 3 | Files: index.html, styles.css

Brief

Show order status as a numbered step indicator built with CSS counters and pseudo-elements, plus native progress and meter elements.

Learning goals

- Use counter-reset and counter-increment
- Use progress and meter
- Build connector lines with ::after

Elements and CSS used

HTML elements	CSS features
ol, li, progress, meter, label, strong	counter-reset, counter(), ::before/::after, translate, accent-color, z-index

Build guide

1. Write the ol with classes done/current and aria-current="step".
2. Add progress and meter elements with values.
3. Flex the list; each li gets equal width.
4. Number the circles with counters in ::before.
5. Draw connector lines with ::after.
6. Colour completed steps and the progress bar with accent-color.

Project 738: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - Order status</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Your order</h1>
    <p>Order 1042: <strong>Screen replacement</strong></p>
    <ol class="steps">
      <li class="done">Received</li>
      <li class="done">Prepared</li>
      <li class="current" aria-current="step">On the way</li>
      <li>Delivered</li>
    </ol>
    <label for="p">Progress</label>
    <progress id="p" value="3" max="4">75%</progress>
    <h2>Rating so far</h2>
    <meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.
8 out of 5</meter> 4.8 / 5
  </main>
</body>
</html>
```

Project 738: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.steps { list-style: none; padding: 0; display: flex; counter-reset:
step; margin: 1.5rem 0; }
.steps li { flex: 1; text-align: center; position: relative; padding-
top: 2.4rem; font-size: .9rem; color: var(--muted); }
.steps li::before { counter-increment: step; content: counter(step);
position: absolute; top: 0; left: 50%; translate: -50% 0; width: 2rem;
 height: 2rem; border-radius: 50%; background: var(--line); color:
#fff; display: grid; place-items: center; font-weight: 700; }
.steps li::after { content: ""; position: absolute; top: 1rem; left: -
50%; width: 100%; height: 3px; background: var(--line); z-index: -1; }
.steps li:first-child::after { display: none; }
.steps .done::before, .steps .done::after, .steps .current::before {
```

```
  background: var(--brand); }
  .steps .current { color: var(--brand); font-weight: 700; }
  progress { width: 100%; height: 1rem; accent-color: var(--brand); }
  meter { width: 12rem; }
```

Project 738 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - Order status</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Your order	The main heading; only one per page.
Order 1042: Screen replacement	A paragraph of text.
<ol class="steps">	Ordered (numbered) list; the order matters.
<li class="done">Received	One list item.
<li class="current" aria-current="step">On the way	Tells assistive technology which item is the current page or step.
<label for="p">Progress</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<progress id="p" value="3" max="4">75%</progress>	Progress of a task.
Rating so far	Second-level heading for a section.
<meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.8...	A measurement within a known range.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
counter-reset: step;	Starts a CSS counter.
flex: 1;	All items share free space equally.
text-align: center;	Centres inline content such as text.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
font-size: .9rem;	Size of the text.
counter-increment: step;	Adds one to the counter for each matching element.
content: counter(step);	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
border-radius: 50%;	Turns a square into a circle.
background: var(--line);	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 700;	Thickness of the text.
.steps li::after {	Generated content inserted after the element's content.
width: 100%;	Fills the container width.
z-index: -1;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
.steps li:first-child::after {	The first child of its parent.
display: none;	Removes the element from rendering completely.
accent-color: var(--brand);	Colours native checkboxes, radios, progress and range controls.

Check your work

- Numbers generated by CSS, not typed
- Lines sit behind circles
- Current step announced with aria-current
- Progress has a label

Exercises

1. Animate the progress bar value with a transition on width (custom bar).
2. Make the tracker vertical on narrow screens.
3. Add estimated times under each step.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 739: Order progress tracker for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 3 | Files: index.html, styles.css

Brief

Show order status as a numbered step indicator built with CSS counters and pseudo-elements, plus native progress and meter elements.

Learning goals

- Use counter-reset and counter-increment
- Use progress and meter
- Build connector lines with ::after

Elements and CSS used

HTML elements	CSS features
ol, li, progress, meter, label, strong	counter-reset, counter(), ::before/::after, translate, accent-color, z-index

Build guide

1. Write the ol with classes done/current and aria-current="step".
2. Add progress and meter elements with values.
3. Flex the list; each li gets equal width.
4. Number the circles with counters in ::before.
5. Draw connector lines with ::after.
6. Colour completed steps and the progress bar with accent-color.

Project 739: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - Order status</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Your order</h1>
    <p>Order 1042: <strong>Full grooming</strong></p>
    <ol class="steps">
      <li class="done">Received</li>
      <li class="done">Prepared</li>
      <li class="current" aria-current="step">On the way</li>
      <li>Delivered</li>
    </ol>
    <label for="p">Progress</label>
    <progress id="p" value="3" max="4">75%</progress>
    <h2>Rating so far</h2>
    <meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.
8 out of 5</meter> 4.8 / 5
  </main>
</body>
</html>
```

Project 739: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.steps { list-style: none; padding: 0; display: flex; counter-reset:
step; margin: 1.5rem 0; }
.steps li { flex: 1; text-align: center; position: relative; padding-
top: 2.4rem; font-size: .9rem; color: var(--muted); }
.steps li::before { counter-increment: step; content: counter(step);
position: absolute; top: 0; left: 50%; translate: -50% 0; width: 2rem;
 height: 2rem; border-radius: 50%; background: var(--line); color:
#fff; display: grid; place-items: center; font-weight: 700; }
.steps li::after { content: ""; position: absolute; top: 1rem; left: -
50%; width: 100%; height: 3px; background: var(--line); z-index: -1; }
.steps li:first-child::after { display: none; }
.steps .done::before, .steps .done::after, .steps .current::before {
```

```
  background: var(--brand); }
  .steps .current { color: var(--brand); font-weight: 700; }
  progress { width: 100%; height: 1rem; accent-color: var(--brand); }
  meter { width: 12rem; }
```

Project 739 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - Order status</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Your order	The main heading; only one per page.
Order 1042: Full grooming	A paragraph of text.
<ol class="steps">	Ordered (numbered) list; the order matters.
<li class="done">Received	One list item.
<li class="current" aria-current="step">On the way	Tells assistive technology which item is the current page or step.
<label for="p">Progress</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<progress id="p" value="3" max="4">75%</progress>	Progress of a task.
Rating so far	Second-level heading for a section.
<meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.8...	A measurement within a known range.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
counter-reset: step;	Starts a CSS counter.
flex: 1;	All items share free space equally.
text-align: center;	Centres inline content such as text.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
font-size: .9rem;	Size of the text.
counter-increment: step;	Adds one to the counter for each matching element.
content: counter(step);	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
border-radius: 50%;	Turns a square into a circle.
background: var(--line);	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 700;	Thickness of the text.
.steps li::after {	Generated content inserted after the element's content.
width: 100%;	Fills the container width.
z-index: -1;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
.steps li:first-child::after {	The first child of its parent.
display: none;	Removes the element from rendering completely.
accent-color: var(--brand);	Colours native checkboxes, radios, progress and range controls.

Check your work

- Numbers generated by CSS, not typed
- Lines sit behind circles
- Current step announced with aria-current
- Progress has a label

Exercises

1. Animate the progress bar value with a transition on width (custom bar).
2. Make the tracker vertical on narrow screens.
3. Add estimated times under each step.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 740: Order progress tracker for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 3 | Files: index.html, styles.css

Brief

Show order status as a numbered step indicator built with CSS counters and pseudo-elements, plus native progress and meter elements.

Learning goals

- Use counter-reset and counter-increment
- Use progress and meter
- Build connector lines with ::after

Elements and CSS used

HTML elements	CSS features
ol, li, progress, meter, label, strong	counter-reset, counter(), ::before/::after, translate, accent-color, z-index

Build guide

1. Write the ol with classes done/current and aria-current="step".
2. Add progress and meter elements with values.
3. Flex the list; each li gets equal width.
4. Number the circles with counters in ::before.
5. Draw connector lines with ::after.

6. Colour completed steps and the progress bar with accent-color.

Project 740: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - Order status</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Your order</h1>
    <p>Order 1042: <strong>Taster session</strong></p>
    <ol class="steps">
      <li class="done">Received</li>
      <li class="done">Prepared</li>
      <li class="current" aria-current="step">On the way</li>
      <li>Delivered</li>
    </ol>
    <label for="p">Progress</label>
    <progress id="p" value="3" max="4">75%</progress>
    <h2>Rating so far</h2>
    <meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.
8 out of 5</meter> 4.8 / 5
  </main>
</body>
</html>
```

Project 740: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.steps { list-style: none; padding: 0; display: flex; counter-reset:
step; margin: 1.5rem 0; }
.steps li { flex: 1; text-align: center; position: relative; padding-
top: 2.4rem; font-size: .9rem; color: var(--muted); }
.steps li::before { counter-increment: step; content: counter(step);
position: absolute; top: 0; left: 50%; translate: -50% 0; width: 2rem;
 height: 2rem; border-radius: 50%; background: var(--line); color:
#fff; display: grid; place-items: center; font-weight: 700; }
.steps li::after { content: ""; position: absolute; top: 1rem; left: -
50%; width: 100%; height: 3px; background: var(--line); z-index: -1; }
.steps li:first-child::after { display: none; }
.steps .done::before, .steps .done::after, .steps .current::before {
```

```
  background: var(--brand); }
  .steps .current { color: var(--brand); font-weight: 700; }
  progress { width: 100%; height: 1rem; accent-color: var(--brand); }
  meter { width: 12rem; }
```

Project 740 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - Order status</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Your order	The main heading; only one per page.
Order 1042: Taster session	A paragraph of text.
<ol class="steps">	Ordered (numbered) list; the order matters.
<li class="done">Received	One list item.
<li class="current" aria-current="step">On the way	Tells assistive technology which item is the current page or step.
<label for="p">Progress</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<progress id="p" value="3" max="4">75%</progress>	Progress of a task.
Rating so far	Second-level heading for a section.
<meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.8...	A measurement within a known range.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
counter-reset: step;	Starts a CSS counter.
flex: 1;	All items share free space equally.
text-align: center;	Centres inline content such as text.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
font-size: .9rem;	Size of the text.
counter-increment: step;	Adds one to the counter for each matching element.
content: counter(step);	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
border-radius: 50%;	Turns a square into a circle.
background: var(--line);	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 700;	Thickness of the text.
.steps li::after {	Generated content inserted after the element's content.
width: 100%;	Fills the container width.
z-index: -1;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
.steps li:first-child::after {	The first child of its parent.
display: none;	Removes the element from rendering completely.
accent-color: var(--brand);	Colours native checkboxes, radios, progress and range controls.

Check your work

- Numbers generated by CSS, not typed
- Lines sit behind circles
- Current step announced with aria-current
- Progress has a label

Exercises

1. Animate the progress bar value with a transition on width (custom bar).
2. Make the tracker vertical on narrow screens.
3. Add estimated times under each step.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 741: Order progress tracker for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 3 | Files: index.html, styles.css

Brief

Show order status as a numbered step indicator built with CSS counters and pseudo-elements, plus native progress and meter elements.

Learning goals

- Use counter-reset and counter-increment
- Use progress and meter
- Build connector lines with ::after

Elements and CSS used

HTML elements	CSS features
ol, li, progress, meter, label, strong	counter-reset, counter(), ::before/::after, translate, accent-color, z-index

Build guide

1. Write the ol with classes done/current and aria-current="step".
2. Add progress and meter elements with values.
3. Flex the list; each li gets equal width.
4. Number the circles with counters in ::before.
5. Draw connector lines with ::after.

6. Colour completed steps and the progress bar with accent-color.

Project 741: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - Order status</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Your order</h1>
    <p>Order 1042: <strong>Lotus pendant</strong></p>
    <ol class="steps">
      <li class="done">Received</li>
      <li class="done">Prepared</li>
      <li class="current" aria-current="step">On the way</li>
      <li>Delivered</li>
    </ol>
    <label for="p">Progress</label>
    <progress id="p" value="3" max="4">75%</progress>
    <h2>Rating so far</h2>
    <meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.
8 out of 5</meter> 4.8 / 5
  </main>
</body>
</html>
```

Project 741: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.steps { list-style: none; padding: 0; display: flex; counter-reset:
step; margin: 1.5rem 0; }
.steps li { flex: 1; text-align: center; position: relative; padding-
top: 2.4rem; font-size: .9rem; color: var(--muted); }
.steps li::before { counter-increment: step; content: counter(step);
position: absolute; top: 0; left: 50%; translate: -50% 0; width: 2rem;
 height: 2rem; border-radius: 50%; background: var(--line); color:
#fff; display: grid; place-items: center; font-weight: 700; }
.steps li::after { content: ""; position: absolute; top: 1rem; left: -
50%; width: 100%; height: 3px; background: var(--line); z-index: -1; }
.steps li:first-child::after { display: none; }
.steps .done::before, .steps .done::after, .steps .current::before {
```

```
  background: var(--brand); }
  .steps .current { color: var(--brand); font-weight: 700; }
  progress { width: 100%; height: 1rem; accent-color: var(--brand); }
  meter { width: 12rem; }
```

Project 741 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - Order status</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Your order	The main heading; only one per page.
Order 1042: Lotus pendant	A paragraph of text.
<ol class="steps">	Ordered (numbered) list; the order matters.
<li class="done">Received	One list item.
<li class="current" aria-current="step">On the way	Tells assistive technology which item is the current page or step.

Line	What it does
<label for="p">Progress</label>	Text label for a control; for matches the control's id, or the label wraps the control.
<progress id="p" value="3" max="4">75%</progress>	Progress of a task.
Rating so far	Second-level heading for a section.
<meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.8...	A measurement within a known range.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.

Declaration	What it does
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
counter-reset: step;	Starts a CSS counter.
flex: 1;	All items share free space equally.
text-align: center;	Centres inline content such as text.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
font-size: .9rem;	Size of the text.
counter-increment: step;	Adds one to the counter for each matching element.
content: counter(step);	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
border-radius: 50%;	Turns a square into a circle.
background: var(--line);	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 700;	Thickness of the text.
.steps li::after {	Generated content inserted after the element's content.
width: 100%;	Fills the container width.

Declaration	What it does
z-index: -1;	Stacking order for positioned elements; higher is on top.
.steps li:first-child::after {	The first child of its parent.
display: none;	Removes the element from rendering completely.
accent-color: var(--brand);	Colours native checkboxes, radios, progress and range controls.

Check your work

- Numbers generated by CSS, not typed
- Lines sit behind circles
- Current step announced with aria-current
- Progress has a label

Exercises

1. Animate the progress bar value with a transition on width (custom bar).
2. Make the tracker vertical on narrow screens.
3. Add estimated times under each step.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8

Field	Value
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 742: Order progress tracker for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 3 | Files: index.html, styles.css

Brief

Show order status as a numbered step indicator built with CSS counters and pseudo-elements, plus native progress and meter elements.

Learning goals

- Use counter-reset and counter-increment
- Use progress and meter
- Build connector lines with ::after

Elements and CSS used

HTML elements	CSS features
ol, li, progress, meter, label, strong	counter-reset, counter(), ::before/::after, translate, accent-color, z-index

Build guide

1. Write the ol with classes done/current and aria-current="step".
2. Add progress and meter elements with values.
3. Flex the list; each li gets equal width.
4. Number the circles with counters in ::before.
5. Draw connector lines with ::after.

6. Colour completed steps and the progress bar with accent-color.

Project 742: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - Order status</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Your order</h1>
    <p>Order 1042: <strong>Intro to the wheel</strong></p>
    <ol class="steps">
      <li class="done">Received</li>
      <li class="done">Prepared</li>
      <li class="current" aria-current="step">On the way</li>
      <li>Delivered</li>
    </ol>
    <label for="p">Progress</label>
    <progress id="p" value="3" max="4">75%</progress>
    <h2>Rating so far</h2>
    <meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.
8 out of 5</meter> 4.8 / 5
  </main>
</body>
</html>
```

Project 742: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.steps { list-style: none; padding: 0; display: flex; counter-reset:
step; margin: 1.5rem 0; }
.steps li { flex: 1; text-align: center; position: relative; padding-
top: 2.4rem; font-size: .9rem; color: var(--muted); }
.steps li::before { counter-increment: step; content: counter(step);
position: absolute; top: 0; left: 50%; translate: -50% 0; width: 2rem;
 height: 2rem; border-radius: 50%; background: var(--line); color:
#fff; display: grid; place-items: center; font-weight: 700; }
.steps li::after { content: ""; position: absolute; top: 1rem; left: -
50%; width: 100%; height: 3px; background: var(--line); z-index: -1; }
.steps li:first-child::after { display: none; }
.steps .done::before, .steps .done::after, .steps .current::before {
```

```
  background: var(--brand); }
  .steps .current { color: var(--brand); font-weight: 700; }
  progress { width: 100%; height: 1rem; accent-color: var(--brand); }
  meter { width: 12rem; }
```

Project 742 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - Order status</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Your order	The main heading; only one per page.
Order 1042: Intro to the wheel	A paragraph of text.
<ol class="steps">	Ordered (numbered) list; the order matters.
<li class="done">Received	One list item.
<li class="current" aria-current="step">On the way	Tells assistive technology which item is the current page or step.
<label for="p">Progress</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<progress id="p" value="3" max="4">75%</progress>	Progress of a task.
Rating so far	Second-level heading for a section.
<meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.8...	A measurement within a known range.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
counter-reset: step;	Starts a CSS counter.
flex: 1;	All items share free space equally.
text-align: center;	Centres inline content such as text.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
font-size: .9rem;	Size of the text.
counter-increment: step;	Adds one to the counter for each matching element.
content: counter(step);	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
border-radius: 50%;	Turns a square into a circle.
background: var(--line);	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 700;	Thickness of the text.
.steps li::after {	Generated content inserted after the element's content.
width: 100%;	Fills the container width.
z-index: -1;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
.steps li:first-child::after {	The first child of its parent.
display: none;	Removes the element from rendering completely.
accent-color: var(--brand);	Colours native checkboxes, radios, progress and range controls.

Check your work

- Numbers generated by CSS, not typed
- Lines sit behind circles
- Current step announced with aria-current
- Progress has a label

Exercises

1. Animate the progress bar value with a transition on width (custom bar).
2. Make the tracker vertical on narrow screens.
3. Add estimated times under each step.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 743: Order progress tracker for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 3 | Files: index.html, styles.css

Brief

Show order status as a numbered step indicator built with CSS counters and pseudo-elements, plus native progress and meter elements.

Learning goals

- Use counter-reset and counter-increment
- Use progress and meter
- Build connector lines with ::after

Elements and CSS used

HTML elements	CSS features
ol, li, progress, meter, label, strong	counter-reset, counter(), ::before/::after, translate, accent-color, z-index

Build guide

1. Write the ol with classes done/current and aria-current="step".
2. Add progress and meter elements with values.
3. Flex the list; each li gets equal width.
4. Number the circles with counters in ::before.
5. Draw connector lines with ::after.

6. Colour completed steps and the progress bar with accent-color.

Project 743: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - Order status</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Your order</h1>
    <p>Order 1042: <strong>Haircut and blow-dry</strong></p>
    <ol class="steps">
      <li class="done">Received</li>
      <li class="done">Prepared</li>
      <li class="current" aria-current="step">On the way</li>
      <li>Delivered</li>
    </ol>
    <label for="p">Progress</label>
    <progress id="p" value="3" max="4">75%</progress>
    <h2>Rating so far</h2>
    <meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.
8 out of 5</meter> 4.8 / 5
  </main>
</body>
</html>
```

Project 743: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.steps { list-style: none; padding: 0; display: flex; counter-reset:
step; margin: 1.5rem 0; }
.steps li { flex: 1; text-align: center; position: relative; padding-
top: 2.4rem; font-size: .9rem; color: var(--muted); }
.steps li::before { counter-increment: step; content: counter(step);
position: absolute; top: 0; left: 50%; translate: -50% 0; width: 2rem;
 height: 2rem; border-radius: 50%; background: var(--line); color:
#fff; display: grid; place-items: center; font-weight: 700; }
.steps li::after { content: ""; position: absolute; top: 1rem; left: -
50%; width: 100%; height: 3px; background: var(--line); z-index: -1; }
.steps li:first-child::after { display: none; }
.steps .done::before, .steps .done::after, .steps .current::before {
```

```
  background: var(--brand); }
  .steps .current { color: var(--brand); font-weight: 700; }
  progress { width: 100%; height: 1rem; accent-color: var(--brand); }
  meter { width: 12rem; }
```

Project 743 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - Order status</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Your order	The main heading; only one per page.
Order 1042: Haircut and blow-dry	A paragraph of text.
<ol class="steps">	Ordered (numbered) list; the order matters.
<li class="done">Received	One list item.
<li class="current" aria-current="step">On the way	Tells assistive technology which item is the current page or step.
<label for="p">Progress</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<progress id="p" value="3" max="4">75%</progress>	Progress of a task.
Rating so far	Second-level heading for a section.
<meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.8...	A measurement within a known range.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
counter-reset: step;	Starts a CSS counter.
flex: 1;	All items share free space equally.
text-align: center;	Centres inline content such as text.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
font-size: .9rem;	Size of the text.
counter-increment: step;	Adds one to the counter for each matching element.
content: counter(step);	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
border-radius: 50%;	Turns a square into a circle.
background: var(--line);	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 700;	Thickness of the text.
.steps li::after {	Generated content inserted after the element's content.
width: 100%;	Fills the container width.
z-index: -1;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
.steps li:first-child::after {	The first child of its parent.
display: none;	Removes the element from rendering completely.
accent-color: var(--brand);	Colours native checkboxes, radios, progress and range controls.

Check your work

- Numbers generated by CSS, not typed
- Lines sit behind circles
- Current step announced with aria-current
- Progress has a label

Exercises

1. Animate the progress bar value with a transition on width (custom bar).
2. Make the tracker vertical on narrow screens.
3. Add estimated times under each step.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 744: Order progress tracker for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 3 | Files: index.html, styles.css

Brief

Show order status as a numbered step indicator built with CSS counters and pseudo-elements, plus native progress and meter elements.

Learning goals

- Use counter-reset and counter-increment
- Use progress and meter
- Build connector lines with ::after

Elements and CSS used

HTML elements	CSS features
ol, li, progress, meter, label, strong	counter-reset, counter(), ::before/::after, translate, accent-color, z-index

Build guide

1. Write the ol with classes done/current and aria-current="step".
2. Add progress and meter elements with values.
3. Flex the list; each li gets equal width.
4. Number the circles with counters in ::before.
5. Draw connector lines with ::after.
6. Colour completed steps and the progress bar with accent-color.

Project 744: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - Order status</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Your order</h1>
    <p>Order 1042: <strong>Oil change</strong></p>
    <ol class="steps">
      <li class="done">Received</li>
      <li class="done">Prepared</li>
      <li class="current" aria-current="step">On the way</li>
      <li>Delivered</li>
    </ol>
    <label for="p">Progress</label>
    <progress id="p" value="3" max="4">75%</progress>
    <h2>Rating so far</h2>
    <meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.
8 out of 5</meter> 4.8 / 5
  </main>
</body>
</html>
```

Project 744: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.steps { list-style: none; padding: 0; display: flex; counter-reset:
step; margin: 1.5rem 0; }
.steps li { flex: 1; text-align: center; position: relative; padding-
top: 2.4rem; font-size: .9rem; color: var(--muted); }
.steps li::before { counter-increment: step; content: counter(step);
position: absolute; top: 0; left: 50%; translate: -50% 0; width: 2rem;
 height: 2rem; border-radius: 50%; background: var(--line); color:
#fff; display: grid; place-items: center; font-weight: 700; }
.steps li::after { content: ""; position: absolute; top: 1rem; left: -
50%; width: 100%; height: 3px; background: var(--line); z-index: -1; }
.steps li:first-child::after { display: none; }
.steps .done::before, .steps .done::after, .steps .current::before {
```

```
  background: var(--brand); }
  .steps .current { color: var(--brand); font-weight: 700; }
  progress { width: 100%; height: 1rem; accent-color: var(--brand); }
  meter { width: 12rem; }
```

Project 744 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - Order status</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Your order	The main heading; only one per page.
Order 1042: Oil change	A paragraph of text.
<ol class="steps">	Ordered (numbered) list; the order matters.
<li class="done">Received	One list item.
<li class="current" aria-current="step">On the way	Tells assistive technology which item is the current page or step.
<label for="p">Progress</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<progress id="p" value="3" max="4">75%</progress>	Progress of a task.
Rating so far	Second-level heading for a section.
<meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.8...	A measurement within a known range.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
counter-reset: step;	Starts a CSS counter.
flex: 1;	All items share free space equally.
text-align: center;	Centres inline content such as text.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
font-size: .9rem;	Size of the text.
counter-increment: step;	Adds one to the counter for each matching element.
content: counter(step);	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
border-radius: 50%;	Turns a square into a circle.
background: var(--line);	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 700;	Thickness of the text.
.steps li::after {	Generated content inserted after the element's content.
width: 100%;	Fills the container width.
z-index: -1;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
.steps li:first-child::after {	The first child of its parent.
display: none;	Removes the element from rendering completely.
accent-color: var(--brand);	Colours native checkboxes, radios, progress and range controls.

Check your work

- Numbers generated by CSS, not typed
- Lines sit behind circles
- Current step announced with aria-current
- Progress has a label

Exercises

1. Animate the progress bar value with a transition on width (custom bar).
2. Make the tracker vertical on narrow screens.
3. Add estimated times under each step.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 745: Order progress tracker for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 3 | Files: index.html, styles.css

Brief

Show order status as a numbered step indicator built with CSS counters and pseudo-elements, plus native progress and meter elements.

Learning goals

- Use counter-reset and counter-increment
- Use progress and meter
- Build connector lines with ::after

Elements and CSS used

HTML elements	CSS features
ol, li, progress, meter, label, strong	counter-reset, counter(), ::before/::after, translate, accent-color, z-index

Build guide

1. Write the ol with classes done/current and aria-current="step".
2. Add progress and meter elements with values.
3. Flex the list; each li gets equal width.
4. Number the circles with counters in ::before.
5. Draw connector lines with ::after.

6. Colour completed steps and the progress bar with accent-color.

Project 745: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - Order status</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Your order</h1>
    <p>Order 1042: <strong>Oud for beginners</strong></p>
    <ol class="steps">
      <li class="done">Received</li>
      <li class="done">Prepared</li>
      <li class="current" aria-current="step">On the way</li>
      <li>Delivered</li>
    </ol>
    <label for="p">Progress</label>
    <progress id="p" value="3" max="4">75%</progress>
    <h2>Rating so far</h2>
    <meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.
8 out of 5</meter> 4.8 / 5
  </main>
</body>
</html>
```

Project 745: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.steps { list-style: none; padding: 0; display: flex; counter-reset:
step; margin: 1.5rem 0; }
.steps li { flex: 1; text-align: center; position: relative; padding-
top: 2.4rem; font-size: .9rem; color: var(--muted); }
.steps li::before { counter-increment: step; content: counter(step);
position: absolute; top: 0; left: 50%; translate: -50% 0; width: 2rem;
 height: 2rem; border-radius: 50%; background: var(--line); color:
#fff; display: grid; place-items: center; font-weight: 700; }
.steps li::after { content: ""; position: absolute; top: 1rem; left: -
50%; width: 100%; height: 3px; background: var(--line); z-index: -1; }
.steps li:first-child::after { display: none; }
.steps .done::before, .steps .done::after, .steps .current::before {
```

```
  background: var(--brand); }
  .steps .current { color: var(--brand); font-weight: 700; }
  progress { width: 100%; height: 1rem; accent-color: var(--brand); }
  meter { width: 12rem; }
```

Project 745 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - Order status</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Your order	The main heading; only one per page.
Order 1042: Oud for beginners	A paragraph of text.
<ol class="steps">	Ordered (numbered) list; the order matters.
<li class="done">Received	One list item.
<li class="current" aria-current="step">On the way	Tells assistive technology which item is the current page or step.
<label for="p">Progress</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<progress id="p" value="3" max="4">75%</progress>	Progress of a task.
Rating so far	Second-level heading for a section.
<meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.8...	A measurement within a known range.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
counter-reset: step;	Starts a CSS counter.
flex: 1;	All items share free space equally.
text-align: center;	Centres inline content such as text.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
font-size: .9rem;	Size of the text.
counter-increment: step;	Adds one to the counter for each matching element.
content: counter(step);	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
border-radius: 50%;	Turns a square into a circle.
background: var(--line);	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 700;	Thickness of the text.
.steps li::after {	Generated content inserted after the element's content.
width: 100%;	Fills the container width.
z-index: -1;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
.steps li:first-child::after {	The first child of its parent.
display: none;	Removes the element from rendering completely.
accent-color: var(--brand);	Colours native checkboxes, radios, progress and range controls.

Check your work

- Numbers generated by CSS, not typed
- Lines sit behind circles
- Current step announced with aria-current
- Progress has a label

Exercises

1. Animate the progress bar value with a transition on width (custom bar).
2. Make the tracker vertical on narrow screens.
3. Add estimated times under each step.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 746: Order progress tracker for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 3 | Files: index.html, styles.css

Brief

Show order status as a numbered step indicator built with CSS counters and pseudo-elements, plus native progress and meter elements.

Learning goals

- Use counter-reset and counter-increment
- Use progress and meter
- Build connector lines with ::after

Elements and CSS used

HTML elements	CSS features
ol, li, progress, meter, label, strong	counter-reset, counter(), ::before/::after, translate, accent-color, z-index

Build guide

1. Write the ol with classes done/current and aria-current="step".
2. Add progress and meter elements with values.
3. Flex the list; each li gets equal width.
4. Number the circles with counters in ::before.
5. Draw connector lines with ::after.
6. Colour completed steps and the progress bar with accent-color.

Project 746: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - Order status</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Your order</h1>
    <p>Order 1042: <strong>Grilled sea bass</strong></p>
    <ol class="steps">
      <li class="done">Received</li>
      <li class="done">Prepared</li>
      <li class="current" aria-current="step">On the way</li>
      <li>Delivered</li>
    </ol>
    <label for="p">Progress</label>
    <progress id="p" value="3" max="4">75%</progress>
    <h2>Rating so far</h2>
    <meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.
8 out of 5</meter> 4.8 / 5
  </main>
</body>
</html>
```

Project 746: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.steps { list-style: none; padding: 0; display: flex; counter-reset:
step; margin: 1.5rem 0; }
.steps li { flex: 1; text-align: center; position: relative; padding-
top: 2.4rem; font-size: .9rem; color: var(--muted); }
.steps li::before { counter-increment: step; content: counter(step);
position: absolute; top: 0; left: 50%; translate: -50% 0; width: 2rem;
 height: 2rem; border-radius: 50%; background: var(--line); color:
#fff; display: grid; place-items: center; font-weight: 700; }
.steps li::after { content: ""; position: absolute; top: 1rem; left: -
50%; width: 100%; height: 3px; background: var(--line); z-index: -1; }
.steps li:first-child::after { display: none; }
.steps .done::before, .steps .done::after, .steps .current::before {
```

```
  background: var(--brand); }
  .steps .current { color: var(--brand); font-weight: 700; }
  progress { width: 100%; height: 1rem; accent-color: var(--brand); }
  meter { width: 12rem; }
```

Project 746 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - Order status</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Your order	The main heading; only one per page.
Order 1042: Grilled sea bass	A paragraph of text.
<ol class="steps">	Ordered (numbered) list; the order matters.
<li class="done">Received	One list item.
<li class="current" aria-current="step">On the way	Tells assistive technology which item is the current page or step.
<label for="p">Progress</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<progress id="p" value="3" max="4">75%</progress>	Progress of a task.
Rating so far	Second-level heading for a section.
<meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.8...	A measurement within a known range.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
counter-reset: step;	Starts a CSS counter.
flex: 1;	All items share free space equally.
text-align: center;	Centres inline content such as text.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
font-size: .9rem;	Size of the text.
counter-increment: step;	Adds one to the counter for each matching element.
content: counter(step);	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
border-radius: 50%;	Turns a square into a circle.
background: var(--line);	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 700;	Thickness of the text.
.steps li::after {	Generated content inserted after the element's content.
width: 100%;	Fills the container width.
z-index: -1;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
.steps li:first-child::after {	The first child of its parent.
display: none;	Removes the element from rendering completely.
accent-color: var(--brand);	Colours native checkboxes, radios, progress and range controls.

Check your work

- Numbers generated by CSS, not typed
- Lines sit behind circles
- Current step announced with aria-current
- Progress has a label

Exercises

1. Animate the progress bar value with a transition on width (custom bar).
2. Make the tracker vertical on narrow screens.
3. Add estimated times under each step.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 747: Order progress tracker for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 3 | Files: index.html, styles.css

Brief

Show order status as a numbered step indicator built with CSS counters and pseudo-elements, plus native progress and meter elements.

Learning goals

- Use counter-reset and counter-increment
- Use progress and meter
- Build connector lines with ::after

Elements and CSS used

HTML elements	CSS features
ol, li, progress, meter, label, strong	counter-reset, counter(), ::before/::after, translate, accent-color, z-index

Build guide

1. Write the ol with classes done/current and aria-current="step".
2. Add progress and meter elements with values.
3. Flex the list; each li gets equal width.
4. Number the circles with counters in ::before.
5. Draw connector lines with ::after.
6. Colour completed steps and the progress bar with accent-color.

Project 747: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - Order status</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Your order</h1>
    <p>Order 1042: <strong>Story hour</strong></p>
    <ol class="steps">
      <li class="done">Received</li>
      <li class="done">Prepared</li>
      <li class="current" aria-current="step">On the way</li>
      <li>Delivered</li>
    </ol>
    <label for="p">Progress</label>
    <progress id="p" value="3" max="4">75%</progress>
    <h2>Rating so far</h2>
    <meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.
8 out of 5</meter> 4.8 / 5
  </main>
</body>
</html>
```

Project 747: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.steps { list-style: none; padding: 0; display: flex; counter-reset:
step; margin: 1.5rem 0; }
.steps li { flex: 1; text-align: center; position: relative; padding-
top: 2.4rem; font-size: .9rem; color: var(--muted); }
.steps li::before { counter-increment: step; content: counter(step);
position: absolute; top: 0; left: 50%; translate: -50% 0; width: 2rem;
 height: 2rem; border-radius: 50%; background: var(--line); color:
#fff; display: grid; place-items: center; font-weight: 700; }
.steps li::after { content: ""; position: absolute; top: 1rem; left: -
50%; width: 100%; height: 3px; background: var(--line); z-index: -1; }
.steps li:first-child::after { display: none; }
.steps .done::before, .steps .done::after, .steps .current::before {
```

```
  background: var(--brand); }
  .steps .current { color: var(--brand); font-weight: 700; }
  progress { width: 100%; height: 1rem; accent-color: var(--brand); }
  meter { width: 12rem; }
```

Project 747 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - Order status</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Your order	The main heading; only one per page.
Order 1042: Story hour	A paragraph of text.
<ol class="steps">	Ordered (numbered) list; the order matters.
<li class="done">Received	One list item.
<li class="current" aria-current="step">On the way	Tells assistive technology which item is the current page or step.
<label for="p">Progress</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<progress id="p" value="3" max="4">75%</progress>	Progress of a task.
Rating so far	Second-level heading for a section.
<meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.8...	A measurement within a known range.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
counter-reset: step;	Starts a CSS counter.
flex: 1;	All items share free space equally.
text-align: center;	Centres inline content such as text.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
font-size: .9rem;	Size of the text.
counter-increment: step;	Adds one to the counter for each matching element.
content: counter(step);	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
border-radius: 50%;	Turns a square into a circle.
background: var(--line);	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 700;	Thickness of the text.
.steps li::after {	Generated content inserted after the element's content.
width: 100%;	Fills the container width.
z-index: -1;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
.steps li:first-child::after {	The first child of its parent.
display: none;	Removes the element from rendering completely.
accent-color: var(--brand);	Colours native checkboxes, radios, progress and range controls.

Check your work

- Numbers generated by CSS, not typed
- Lines sit behind circles
- Current step announced with aria-current
- Progress has a label

Exercises

1. Animate the progress bar value with a transition on width (custom bar).
2. Make the tracker vertical on narrow screens.
3. Add estimated times under each step.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 748: Order progress tracker for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 3 | Files: index.html, styles.css

Brief

Show order status as a numbered step indicator built with CSS counters and pseudo-elements, plus native progress and meter elements.

Learning goals

- Use counter-reset and counter-increment
- Use progress and meter
- Build connector lines with ::after

Elements and CSS used

HTML elements	CSS features
ol, li, progress, meter, label, strong	counter-reset, counter(), ::before/::after, translate, accent-color, z-index

Build guide

1. Write the ol with classes done/current and aria-current="step".
2. Add progress and meter elements with values.
3. Flex the list; each li gets equal width.
4. Number the circles with counters in ::before.
5. Draw connector lines with ::after.

6. Colour completed steps and the progress bar with accent-color.

Project 748: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - Order status</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Your order</h1>
    <p>Order 1042: <strong>Garden room</strong></p>
    <ol class="steps">
      <li class="done">Received</li>
      <li class="done">Prepared</li>
      <li class="current" aria-current="step">On the way</li>
      <li>Delivered</li>
    </ol>
    <label for="p">Progress</label>
    <progress id="p" value="3" max="4">75%</progress>
    <h2>Rating so far</h2>
    <meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.
8 out of 5</meter> 4.8 / 5
  </main>
</body>
</html>
```

Project 748: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.steps { list-style: none; padding: 0; display: flex; counter-reset:
step; margin: 1.5rem 0; }
.steps li { flex: 1; text-align: center; position: relative; padding-
top: 2.4rem; font-size: .9rem; color: var(--muted); }
.steps li::before { counter-increment: step; content: counter(step);
position: absolute; top: 0; left: 50%; translate: -50% 0; width: 2rem;
 height: 2rem; border-radius: 50%; background: var(--line); color:
#fff; display: grid; place-items: center; font-weight: 700; }
.steps li::after { content: ""; position: absolute; top: 1rem; left: -
50%; width: 100%; height: 3px; background: var(--line); z-index: -1; }
.steps li:first-child::after { display: none; }
.steps .done::before, .steps .done::after, .steps .current::before {
```

```
  background: var(--brand); }
  .steps .current { color: var(--brand); font-weight: 700; }
  progress { width: 100%; height: 1rem; accent-color: var(--brand); }
  meter { width: 12rem; }
```

Project 748 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - Order status</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Your order	The main heading; only one per page.
Order 1042: Garden room	A paragraph of text.
<ol class="steps">	Ordered (numbered) list; the order matters.
<li class="done">Received	One list item.
<li class="current" aria-current="step">On the way	Tells assistive technology which item is the current page or step.
<label for="p">Progress</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<progress id="p" value="3" max="4">75%</progress>	Progress of a task.
Rating so far	Second-level heading for a section.
<meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.8...	A measurement within a known range.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
counter-reset: step;	Starts a CSS counter.
flex: 1;	All items share free space equally.
text-align: center;	Centres inline content such as text.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
font-size: .9rem;	Size of the text.
counter-increment: step;	Adds one to the counter for each matching element.
content: counter(step);	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
border-radius: 50%;	Turns a square into a circle.
background: var(--line);	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 700;	Thickness of the text.
.steps li::after {	Generated content inserted after the element's content.
width: 100%;	Fills the container width.
z-index: -1;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
.steps li:first-child::after {	The first child of its parent.
display: none;	Removes the element from rendering completely.
accent-color: var(--brand);	Colours native checkboxes, radios, progress and range controls.

Check your work

- Numbers generated by CSS, not typed
- Lines sit behind circles
- Current step announced with aria-current
- Progress has a label

Exercises

1. Animate the progress bar value with a transition on width (custom bar).
2. Make the tracker vertical on narrow screens.
3. Add estimated times under each step.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 749: Order progress tracker for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 3 | Files: index.html, styles.css

Brief

Show order status as a numbered step indicator built with CSS counters and pseudo-elements, plus native progress and meter elements.

Learning goals

- Use counter-reset and counter-increment
- Use progress and meter
- Build connector lines with ::after

Elements and CSS used

HTML elements	CSS features
ol, li, progress, meter, label, strong	counter-reset, counter(), ::before/::after, translate, accent-color, z-index

Build guide

1. Write the ol with classes done/current and aria-current="step".
2. Add progress and meter elements with values.
3. Flex the list; each li gets equal width.
4. Number the circles with counters in ::before.
5. Draw connector lines with ::after.

6. Colour completed steps and the progress bar with accent-color.

Project 749: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - Order status</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Your order</h1>
    <p>Order 1042: <strong>City bike</strong></p>
    <ol class="steps">
      <li class="done">Received</li>
      <li class="done">Prepared</li>
      <li class="current" aria-current="step">On the way</li>
      <li>Delivered</li>
    </ol>
    <label for="p">Progress</label>
    <progress id="p" value="3" max="4">75%</progress>
    <h2>Rating so far</h2>
    <meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.
8 out of 5</meter> 4.8 / 5
  </main>
</body>
</html>
```

Project 749: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.steps { list-style: none; padding: 0; display: flex; counter-reset:
step; margin: 1.5rem 0; }
.steps li { flex: 1; text-align: center; position: relative; padding-
top: 2.4rem; font-size: .9rem; color: var(--muted); }
.steps li::before { counter-increment: step; content: counter(step);
position: absolute; top: 0; left: 50%; translate: -50% 0; width: 2rem;
 height: 2rem; border-radius: 50%; background: var(--line); color:
#fff; display: grid; place-items: center; font-weight: 700; }
.steps li::after { content: ""; position: absolute; top: 1rem; left: -
50%; width: 100%; height: 3px; background: var(--line); z-index: -1; }
.steps li:first-child::after { display: none; }
.steps .done::before, .steps .done::after, .steps .current::before {
```

```
  background: var(--brand); }
  .steps .current { color: var(--brand); font-weight: 700; }
  progress { width: 100%; height: 1rem; accent-color: var(--brand); }
  meter { width: 12rem; }
```

Project 749 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - Order status</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Your order	The main heading; only one per page.
Order 1042: City bike	A paragraph of text.
<ol class="steps">	Ordered (numbered) list; the order matters.
<li class="done">Received	One list item.
<li class="current" aria-current="step">On the way	Tells assistive technology which item is the current page or step.
<label for="p">Progress</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<progress id="p" value="3" max="4">75%</progress>	Progress of a task.
Rating so far	Second-level heading for a section.
<meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.8...	A measurement within a known range.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
counter-reset: step;	Starts a CSS counter.
flex: 1;	All items share free space equally.
text-align: center;	Centres inline content such as text.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
font-size: .9rem;	Size of the text.
counter-increment: step;	Adds one to the counter for each matching element.
content: counter(step);	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
border-radius: 50%;	Turns a square into a circle.
background: var(--line);	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 700;	Thickness of the text.
.steps li::after {	Generated content inserted after the element's content.
width: 100%;	Fills the container width.
z-index: -1;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
.steps li:first-child::after {	The first child of its parent.
display: none;	Removes the element from rendering completely.
accent-color: var(--brand);	Colours native checkboxes, radios, progress and range controls.

Check your work

- Numbers generated by CSS, not typed
- Lines sit behind circles
- Current step announced with aria-current
- Progress has a label

Exercises

1. Animate the progress bar value with a transition on width (custom bar).
2. Make the tracker vertical on narrow screens.
3. Add estimated times under each step.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 750: Order progress tracker for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 3 | Files: index.html, styles.css

Brief

Show order status as a numbered step indicator built with CSS counters and pseudo-elements, plus native progress and meter elements.

Learning goals

- Use counter-reset and counter-increment
- Use progress and meter
- Build connector lines with ::after

Elements and CSS used

HTML elements	CSS features
ol, li, progress, meter, label, strong	counter-reset, counter(), ::before/::after, translate, accent-color, z-index

Build guide

1. Write the ol with classes done/current and aria-current="step".
2. Add progress and meter elements with values.
3. Flex the list; each li gets equal width.
4. Number the circles with counters in ::before.
5. Draw connector lines with ::after.
6. Colour completed steps and the progress bar with accent-color.

Project 750: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - Order status</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Your order</h1>
    <p>Order 1042: <strong>HTML weekend</strong></p>
    <ol class="steps">
      <li class="done">Received</li>
      <li class="done">Prepared</li>
      <li class="current" aria-current="step">On the way</li>
      <li>Delivered</li>
    </ol>
    <label for="p">Progress</label>
    <progress id="p" value="3" max="4">75%</progress>
    <h2>Rating so far</h2>
    <meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.
8 out of 5</meter> 4.8 / 5
  </main>
</body>
</html>
```

Project 750: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.steps { list-style: none; padding: 0; display: flex; counter-reset:
step; margin: 1.5rem 0; }
.steps li { flex: 1; text-align: center; position: relative; padding-
top: 2.4rem; font-size: .9rem; color: var(--muted); }
.steps li::before { counter-increment: step; content: counter(step);
position: absolute; top: 0; left: 50%; translate: -50% 0; width: 2rem;
 height: 2rem; border-radius: 50%; background: var(--line); color:
#fff; display: grid; place-items: center; font-weight: 700; }
.steps li::after { content: ""; position: absolute; top: 1rem; left: -
50%; width: 100%; height: 3px; background: var(--line); z-index: -1; }
.steps li:first-child::after { display: none; }
.steps .done::before, .steps .done::after, .steps .current::before {
```

```
  background: var(--brand); }
  .steps .current { color: var(--brand); font-weight: 700; }
  progress { width: 100%; height: 1rem; accent-color: var(--brand); }
  meter { width: 12rem; }
```

Project 750 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - Order status</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Your order	The main heading; only one per page.
Order 1042: HTML weekend	A paragraph of text.
<ol class="steps">	Ordered (numbered) list; the order matters.
<li class="done">Received	One list item.
<li class="current" aria-current="step">On the way	Tells assistive technology which item is the current page or step.
<label for="p">Progress</label>	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<progress id="p" value="3" max="4">75%</progress>	Progress of a task.
Rating so far	Second-level heading for a section.
<meter value="4.8" min="0" max="5" low="2" high="4" optimum="5">4.8...	A measurement within a known range.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
counter-reset: step;	Starts a CSS counter.
flex: 1;	All items share free space equally.
text-align: center;	Centres inline content such as text.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
font-size: .9rem;	Size of the text.
counter-increment: step;	Adds one to the counter for each matching element.
content: counter(step);	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
border-radius: 50%;	Turns a square into a circle.
background: var(--line);	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 700;	Thickness of the text.
.steps li::after {	Generated content inserted after the element's content.
width: 100%;	Fills the container width.
z-index: -1;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
.steps li:first-child::after {	The first child of its parent.
display: none;	Removes the element from rendering completely.
accent-color: var(--brand);	Colours native checkboxes, radios, progress and range controls.

Check your work

- Numbers generated by CSS, not typed
- Lines sit behind circles
- Current step announced with aria-current
- Progress has a label

Exercises

1. Animate the progress bar value with a transition on width (custom bar).
2. Make the tracker vertical on narrow screens.
3. Add estimated times under each step.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Split-screen feature section

Level 2 | 25 projects, one per theme

Create a full-height section with text on one half and a photo filling the other half, stacking on small screens.

Project 751: Split-screen feature section for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 2 | Files: index.html, styles.css

Brief

Create a full-height section with text on one half and a photo filling the other half, stacking on small screens.

Learning goals

- Fill a grid cell with an image using object-fit
- Vertically centre content with align-content
- Use clamp() for fluid padding

Elements and CSS used

HTML elements	CSS features
main, div, p, h1, strong, ul, li, a, img	grid-template-columns: 1fr 1fr, object-fit: cover, align-content: center, clamp(), ::before content

Build guide

1. Write the text block and the image as the two children of .split.
2. Grid with one column by default, two above 800px.
3. Give the image height 100% and object-fit: cover.
4. Centre the text vertically with align-content.
5. Add tick marks to the list with ::before.
6. Use clamp() for padding.

Project 751: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Learn HTML</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="split">
    <div class="text">
      <p class="kicker">Book of the month</p>
      <h1>Learn HTML</h1>
      <p>From your first tag to a complete page. Available now at
Cairo Book Shop in Giza for <strong>120 EGP</strong>.</p>
      <ul class="ticks">
        <li>Made with care</li>
        <li>Satisfaction guaranteed</li>
        <li>Ask us anything</li>
      </ul>
      <a class="btn" href="contact.html">Ask about it</a>
    </div>
    <img src="images/bookshop-1.jpg" alt="Learn HTML" width="900"
height="900">
  </main>
</body>
</html>
```

Project 751: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.split { min-height: 100vh; display: grid; grid-template-columns: 1fr;
 }
.text { padding: clamp(1.5rem, 5vw, 4rem); display: grid; align-
content: center; gap: 1rem; }
img { width: 100%; height: 100%; object-fit: cover; }
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr;
} }
.kicker { text-transform: uppercase; letter-spacing: .1em; color: var(
--brand); font-weight: 700; margin: 0; }
h1 { margin: 0; font-size: clamp(2rem, 4vw, 3rem); }
.ticks { list-style: none; padding: 0; margin: 0; }
.ticks li::before { content: "\2713 "; color: var(--brand); font-
```

```
weight: 700; }
.btn { justify-self: start; padding: .8rem 1.6rem; background: var(--
brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 751 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - Learn HTML</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="split">	The unique content of this page; exactly one per page.
	Generic block container for grouping and layout.
Book of the month	A paragraph of text.
Learn HTML	The main heading; only one per page.
From your first tag to a complete page. Available now at Cairo B...	Strong importance (bold by default).
<ul class="ticks">	Unordered (bulleted) list.
Made with care	One list item.
Ask about it	A link styled as a button; it navigates, so it is a link and not a <button>.

Line	What it does
<img src="images/bookshop-1.jpg" alt="Learn HTML" width="900" heigh...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
padding: clamp(1.5rem, 5vw, 4rem);	Space inside the element between its border and content.
align-content: center;	Centres the lines of a multi-line flex or grid container.

Declaration	What it does
gap: 1rem;	Space between grid or flex items without extra margins.
width: 100%;	Fills the container width.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr...	Applies from the given width upwards (mobile-first breakpoint).
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .1em;	Adds space between letters; useful for small capitals.
font-weight: 700;	Thickness of the text.
font-size: clamp(2rem, 4vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
list-style: none;	Removes bullets or numbers from a list.
content: "\2713 ";	The text or empty string for a pseudo-element.
background: var(--brand);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Image never distorts
- Text stays readable width
- Stacks on mobile with image below
- Button aligned left, not stretched

Exercises

1. Swap the sides with order or direction: rtl.
2. Add a second split section with the image on the left.
3. Use a background video instead of the image.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 752: Split-screen feature section for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 2 | Files: index.html, styles.css

Brief

Create a full-height section with text on one half and a photo filling the other half, stacking on small screens.

Learning goals

- Fill a grid cell with an image using object-fit
- Vertically centre content with align-content
- Use clamp() for fluid padding

Elements and CSS used

HTML elements	CSS features
main, div, p, h1, strong, ul, li, a, img	grid-template-columns: 1fr 1fr, object-fit: cover, align-content: center, clamp(), ::before content

Build guide

1. Write the text block and the image as the two children of .split.
2. Grid with one column by default, two above 800px.
3. Give the image height 100% and object-fit: cover.
4. Centre the text vertically with align-content.
5. Add tick marks to the list with ::before.
6. Use clamp() for padding.

Project 752: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - Sourdough loaf</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="split">
    <div class="text">
      <p class="kicker">Pastry of the month</p>
      <h1>Sourdough loaf</h1>
      <p>Slow fermented, crisp crust. Available now at Nile Bakery in
Cairo for <strong>60 EGP</strong>.</p>
      <ul class="ticks">
        <li>Made with care</li>
        <li>Satisfaction guaranteed</li>
        <li>Ask us anything</li>
      </ul>
      <a class="btn" href="contact.html">Ask about it</a>
    </div>
    <img src="images/bakery-1.jpg" alt="Sourdough loaf" width="900"
height="900">
  </main>
</body>
</html>
```

Project 752: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.split { min-height: 100vh; display: grid; grid-template-columns: 1fr;
 }
.text { padding: clamp(1.5rem, 5vw, 4rem); display: grid; align-
content: center; gap: 1rem; }
img { width: 100%; height: 100%; object-fit: cover; }
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr;
} }
.kicker { text-transform: uppercase; letter-spacing: .1em; color: var(
--brand); font-weight: 700; margin: 0; }
h1 { margin: 0; font-size: clamp(2rem, 4vw, 3rem); }
.ticks { list-style: none; padding: 0; margin: 0; }
.ticks li::before { content: "\2713 "; color: var(--brand); font-
```

```
weight: 700; }
.btn { justify-self: start; padding: .8rem 1.6rem; background: var(--
brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 752 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - Sourdough loaf</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="split">	The unique content of this page; exactly one per page.
	Generic block container for grouping and layout.
Pastry of the month	A paragraph of text.
Sourdough loaf	The main heading; only one per page.
Slow fermented, crisp crust. Available now at Nile Bakery in Cai...	Strong importance (bold by default).
<ul class="ticks">	Unordered (bulleted) list.
Made with care	One list item.
Ask about it	A link styled as a button; it navigates, so it is a link and not a <button>.

Line	What it does
<img src="images/bakery-1.jpg" alt="Sourdough loaf" width="900" hei...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
padding: clamp(1.5rem, 5vw, 4rem);	Space inside the element between its border and content.
align-content: center;	Centres the lines of a multi-line flex or grid container.

Declaration	What it does
gap: 1rem;	Space between grid or flex items without extra margins.
width: 100%;	Fills the container width.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr...	Applies from the given width upwards (mobile-first breakpoint).
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .1em;	Adds space between letters; useful for small capitals.
font-weight: 700;	Thickness of the text.
font-size: clamp(2rem, 4vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
list-style: none;	Removes bullets or numbers from a list.
content: "\2713 ";	The text or empty string for a pseudo-element.
background: var(--brand);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Image never distorts
- Text stays readable width
- Stacks on mobile with image below
- Button aligned left, not stretched

Exercises

1. Swap the sides with order or direction: rtl.
2. Add a second split section with the image on the left.
3. Use a background video instead of the image.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 753: Split-screen feature section for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 2 | Files: index.html, styles.css

Brief

Create a full-height section with text on one half and a photo filling the other half, stacking on small screens.

Learning goals

- Fill a grid cell with an image using object-fit
- Vertically centre content with align-content
- Use clamp() for fluid padding

Elements and CSS used

HTML elements	CSS features
main, div, p, h1, strong, ul, li, a, img	grid-template-columns: 1fr 1fr, object-fit: cover, align-content: center, clamp(), ::before content

Build guide

1. Write the text block and the image as the two children of .split.
2. Grid with one column by default, two above 800px.
3. Give the image height 100% and object-fit: cover.
4. Centre the text vertically with align-content.
5. Add tick marks to the list with ::before.
6. Use clamp() for padding.

Project 753: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - Morning yoga</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="split">
    <div class="text">
      <p class="kicker">Class of the month</p>
      <h1>Morning yoga</h1>
      <p>Flexibility and calm, 60 minutes. Available now at Pyramid
Fitness in 6th of October for <strong>100 EGP</strong>.</p>
      <ul class="ticks">
        <li>Made with care</li>
        <li>Satisfaction guaranteed</li>
        <li>Ask us anything</li>
      </ul>
      <a class="btn" href="contact.html">Ask about it</a>
    </div>
    <img src="images/gym-1.jpg" alt="Morning yoga" width="900"
height="900">
  </main>
</body>
</html>
```

Project 753: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.split { min-height: 100vh; display: grid; grid-template-columns: 1fr;
 }
.text { padding: clamp(1.5rem, 5vw, 4rem); display: grid; align-
content: center; gap: 1rem; }
img { width: 100%; height: 100%; object-fit: cover; }
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr;
} }
.kicker { text-transform: uppercase; letter-spacing: .1em; color: var(
--brand); font-weight: 700; margin: 0; }
h1 { margin: 0; font-size: clamp(2rem, 4vw, 3rem); }
.ticks { list-style: none; padding: 0; margin: 0; }
.ticks li::before { content: "\2713 "; color: var(--brand); font-
```

```
weight: 700; }
.btn { justify-self: start; padding: .8rem 1.6rem; background: var(--
brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 753 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - Morning yoga</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="split">	The unique content of this page; exactly one per page.
	Generic block container for grouping and layout.
Class of the month	A paragraph of text.
Morning yoga	The main heading; only one per page.
Flexibility and calm, 60 minutes. Available now at Pyramid Fitne...	Strong importance (bold by default).
<ul class="ticks">	Unordered (bulleted) list.
Made with care	One list item.
Ask about it	A link styled as a button; it navigates, so it is a link and not a <button>.

Line	What it does
<img src="images/gym-1.jpg" alt="Morning yoga" width="900" height="...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
padding: clamp(1.5rem, 5vw, 4rem);	Space inside the element between its border and content.
align-content: center;	Centres the lines of a multi-line flex or grid container.

Declaration	What it does
gap: 1rem;	Space between grid or flex items without extra margins.
width: 100%;	Fills the container width.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr...	Applies from the given width upwards (mobile-first breakpoint).
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .1em;	Adds space between letters; useful for small capitals.
font-weight: 700;	Thickness of the text.
font-size: clamp(2rem, 4vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
list-style: none;	Removes bullets or numbers from a list.
content: "\2713 ";	The text or empty string for a pseudo-element.
background: var(--brand);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Image never distorts
- Text stays readable width
- Stacks on mobile with image below
- Button aligned left, not stretched

Exercises

1. Swap the sides with order or direction: rtl.
2. Add a second split section with the image on the left.
3. Use a background video instead of the image.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 754: Split-screen feature section for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 2 | Files: index.html, styles.css

Brief

Create a full-height section with text on one half and a photo filling the other half, stacking on small screens.

Learning goals

- Fill a grid cell with an image using object-fit
- Vertically centre content with align-content
- Use clamp() for fluid padding

Elements and CSS used

HTML elements	CSS features
main, div, p, h1, strong, ul, li, a, img	grid-template-columns: 1fr 1fr, object-fit: cover, align-content: center, clamp(), ::before content

Build guide

1. Write the text block and the image as the two children of .split.
2. Grid with one column by default, two above 800px.
3. Give the image height 100% and object-fit: cover.
4. Centre the text vertically with align-content.
5. Add tick marks to the list with ::before.
6. Use clamp() for padding.

Project 754: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - Check-up</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="split">
    <div class="text">
      <p class="kicker">Service of the month</p>
      <h1>Check-up</h1>
      <p>Examination and cleaning. Available now at Delta Dental
Clinic in Mansoura for <strong>300 EGP</strong>.</p>
      <ul class="ticks">
        <li>Made with care</li>
        <li>Satisfaction guaranteed</li>
        <li>Ask us anything</li>
      </ul>
      <a class="btn" href="contact.html">Ask about it</a>
    </div>
    <img src="images/clinic-1.jpg" alt="Check-up" width="900"
height="900">
  </main>
</body>
</html>
```

Project 754: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.split { min-height: 100vh; display: grid; grid-template-columns: 1fr;
 }
.text { padding: clamp(1.5rem, 5vw, 4rem); display: grid; align-
content: center; gap: 1rem; }
img { width: 100%; height: 100%; object-fit: cover; }
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr;
} }
.kicker { text-transform: uppercase; letter-spacing: .1em; color: var(
--brand); font-weight: 700; margin: 0; }
h1 { margin: 0; font-size: clamp(2rem, 4vw, 3rem); }
.ticks { list-style: none; padding: 0; margin: 0; }
.ticks li::before { content: "\2713 "; color: var(--brand); font-
```

```
weight: 700; }
.btn { justify-self: start; padding: .8rem 1.6rem; background: var(--
brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 754 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - Check-up</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="split">	The unique content of this page; exactly one per page.
	Generic block container for grouping and layout.
Service of the month	A paragraph of text.
Check-up	The main heading; only one per page.
Examination and cleaning. Available now at Delta Dental Clinic i...	Strong importance (bold by default).
<ul class="ticks">	Unordered (bulleted) list.
Made with care	One list item.
Ask about it	A link styled as a button; it navigates, so it is a link and not a <button>.

Line	What it does
<img src="images/clinic-1.jpg" alt="Check-up" width="900" height="9...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
padding: clamp(1.5rem, 5vw, 4rem);	Space inside the element between its border and content.
align-content: center;	Centres the lines of a multi-line flex or grid container.

Declaration	What it does
gap: 1rem;	Space between grid or flex items without extra margins.
width: 100%;	Fills the container width.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr...	Applies from the given width upwards (mobile-first breakpoint).
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .1em;	Adds space between letters; useful for small capitals.
font-weight: 700;	Thickness of the text.
font-size: clamp(2rem, 4vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
list-style: none;	Removes bullets or numbers from a list.
content: "\2713 ";	The text or empty string for a pseudo-element.
background: var(--brand);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Image never distorts
- Text stays readable width
- Stacks on mobile with image below
- Button aligned left, not stretched

Exercises

1. Swap the sides with order or direction: rtl.
2. Add a second split section with the image on the left.
3. Use a background video instead of the image.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 755: Split-screen feature section for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 2 | Files: index.html, styles.css

Brief

Create a full-height section with text on one half and a photo filling the other half, stacking on small screens.

Learning goals

- Fill a grid cell with an image using object-fit
- Vertically centre content with align-content
- Use clamp() for fluid padding

Elements and CSS used

HTML elements	CSS features
main, div, p, h1, strong, ul, li, a, img	grid-template-columns: 1fr 1fr, object-fit: cover, align-content: center, clamp(), ::before content

Build guide

1. Write the text block and the image as the two children of .split.
2. Grid with one column by default, two above 800px.
3. Give the image height 100% and object-fit: cover.
4. Centre the text vertically with align-content.
5. Add tick marks to the list with ::before.
6. Use clamp() for padding.

Project 755: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - Luxor day trip</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="split">
    <div class="text">
      <p class="kicker">Tour of the month</p>
      <h1>Luxor day trip</h1>
      <p>Karnak, Valley of the Kings. Available now at Red Sea Travel
in Hurghada for <strong>1200 EGP</strong>.</p>
      <ul class="ticks">
        <li>Made with care</li>
        <li>Satisfaction guaranteed</li>
        <li>Ask us anything</li>
      </ul>
      <a class="btn" href="contact.html">Ask about it</a>
    </div>
    <img src="images/travel-1.jpg" alt="Luxor day trip" width="900"
height="900">
  </main>
</body>
</html>
```

Project 755: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.split { min-height: 100vh; display: grid; grid-template-columns: 1fr;
 }
.text { padding: clamp(1.5rem, 5vw, 4rem); display: grid; align-
content: center; gap: 1rem; }
img { width: 100%; height: 100%; object-fit: cover; }
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr;
} }
.kicker { text-transform: uppercase; letter-spacing: .1em; color: var(
--brand); font-weight: 700; margin: 0; }
h1 { margin: 0; font-size: clamp(2rem, 4vw, 3rem); }
.ticks { list-style: none; padding: 0; margin: 0; }
.ticks li::before { content: "\2713 "; color: var(--brand); font-
```

```
weight: 700; }
.btn { justify-self: start; padding: .8rem 1.6rem; background: var(--
brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 755 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - Luxor day trip</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="split">	The unique content of this page; exactly one per page.
	Generic block container for grouping and layout.
Tour of the month	A paragraph of text.
Luxor day trip	The main heading; only one per page.
Karnak, Valley of the Kings. Available now at Red Sea Travel in ...	Strong importance (bold by default).
<ul class="ticks">	Unordered (bulleted) list.
Made with care	One list item.
Ask about it	A link styled as a button; it navigates, so it is a link and not a <button>.

Line	What it does
<img src="images/travel-1.jpg" alt="Luxor day trip" width="900" hei...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
padding: clamp(1.5rem, 5vw, 4rem);	Space inside the element between its border and content.
align-content: center;	Centres the lines of a multi-line flex or grid container.

Declaration	What it does
gap: 1rem;	Space between grid or flex items without extra margins.
width: 100%;	Fills the container width.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr...	Applies from the given width upwards (mobile-first breakpoint).
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .1em;	Adds space between letters; useful for small capitals.
font-weight: 700;	Thickness of the text.
font-size: clamp(2rem, 4vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
list-style: none;	Removes bullets or numbers from a list.
content: "\2713 ";	The text or empty string for a pseudo-element.
background: var(--brand);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Image never distorts
- Text stays readable width
- Stacks on mobile with image below
- Button aligned left, not stretched

Exercises

1. Swap the sides with order or direction: rtl.
2. Add a second split section with the image on the left.
3. Use a background video instead of the image.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 756: Split-screen feature section for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Create a full-height section with text on one half and a photo filling the other half, stacking on small screens.

Learning goals

- Fill a grid cell with an image using object-fit
- Vertically centre content with align-content
- Use clamp() for fluid padding

Elements and CSS used

HTML elements	CSS features
main, div, p, h1, strong, ul, li, a, img	grid-template-columns: 1fr 1fr, object-fit: cover, align-content: center, clamp(), ::before content

Build guide

1. Write the text block and the image as the two children of .split.
2. Grid with one column by default, two above 800px.
3. Give the image height 100% and object-fit: cover.
4. Centre the text vertically with align-content.
5. Add tick marks to the list with ::before.
6. Use clamp() for padding.

Project 756: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - English A1</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="split">
    <div class="text">
      <p class="kicker">Course of the month</p>
      <h1>English A1</h1>
      <p>Beginner, 8 weeks. Available now at Lotus Language School in
Alexandria for <strong>1800 EGP</strong>.</p>
      <ul class="ticks">
        <li>Made with care</li>
        <li>Satisfaction guaranteed</li>
        <li>Ask us anything</li>
      </ul>
      <a class="btn" href="contact.html">Ask about it</a>
    </div>
    <img src="images/school-1.jpg" alt="English A1" width="900"
height="900">
  </main>
</body>
</html>
```

Project 756: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.split { min-height: 100vh; display: grid; grid-template-columns: 1fr;
 }
.text { padding: clamp(1.5rem, 5vw, 4rem); display: grid; align-
content: center; gap: 1rem; }
img { width: 100%; height: 100%; object-fit: cover; }
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr;
} }
.kicker { text-transform: uppercase; letter-spacing: .1em; color: var(
--brand); font-weight: 700; margin: 0; }
h1 { margin: 0; font-size: clamp(2rem, 4vw, 3rem); }
.ticks { list-style: none; padding: 0; margin: 0; }
.ticks li::before { content: "\2713 "; color: var(--brand); font-
```

```
weight: 700; }
.btn { justify-self: start; padding: .8rem 1.6rem; background: var(--
brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 756 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - English A1</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="split">	The unique content of this page; exactly one per page.
	Generic block container for grouping and layout.
Course of the month	A paragraph of text.
English A1	The main heading; only one per page.
Beginner, 8 weeks. Available now at Lotus Language School in Ale...	Strong importance (bold by default).
<ul class="ticks">	Unordered (bulleted) list.
Made with care	One list item.
Ask about it	A link styled as a button; it navigates, so it is a link and not a <button>.

Line	What it does
<img src="images/school-1.jpg" alt="English A1" width="900" height=...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
padding: clamp(1.5rem, 5vw, 4rem);	Space inside the element between its border and content.
align-content: center;	Centres the lines of a multi-line flex or grid container.

Declaration	What it does
gap: 1rem;	Space between grid or flex items without extra margins.
width: 100%;	Fills the container width.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr...	Applies from the given width upwards (mobile-first breakpoint).
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .1em;	Adds space between letters; useful for small capitals.
font-weight: 700;	Thickness of the text.
font-size: clamp(2rem, 4vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
list-style: none;	Removes bullets or numbers from a list.
content: "\2713 ";	The text or empty string for a pseudo-element.
background: var(--brand);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Image never distorts
- Text stays readable width
- Stacks on mobile with image below
- Button aligned left, not stretched

Exercises

1. Swap the sides with order or direction: rtl.
2. Add a second split section with the image on the left.
3. Use a background video instead of the image.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 757: Split-screen feature section for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 2 | Files: index.html, styles.css

Brief

Create a full-height section with text on one half and a photo filling the other half, stacking on small screens.

Learning goals

- Fill a grid cell with an image using object-fit
- Vertically centre content with align-content
- Use clamp() for fluid padding

Elements and CSS used

HTML elements	CSS features
main, div, p, h1, strong, ul, li, a, img	grid-template-columns: 1fr 1fr, object-fit: cover, align-content: center, clamp(), ::before content

Build guide

1. Write the text block and the image as the two children of .split.
2. Grid with one column by default, two above 800px.
3. Give the image height 100% and object-fit: cover.
4. Centre the text vertically with align-content.
5. Add tick marks to the list with ::before.
6. Use clamp() for padding.

Project 757: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - Flat white</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="split">
    <div class="text">
      <p class="kicker">Drink of the month</p>
      <h1>Flat white</h1>
      <p>Double shot, silky milk. Available now at Green Leaf Cafe in
Zamalek for <strong>55 EGP</strong>.</p>
      <ul class="ticks">
        <li>Made with care</li>
        <li>Satisfaction guaranteed</li>
        <li>Ask us anything</li>
      </ul>
      <a class="btn" href="contact.html">Ask about it</a>
    </div>
    <img src="images/cafe-1.jpg" alt="Flat white" width="900"
height="900">
  </main>
</body>
</html>
```

Project 757: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.split { min-height: 100vh; display: grid; grid-template-columns: 1fr;
 }
.text { padding: clamp(1.5rem, 5vw, 4rem); display: grid; align-
content: center; gap: 1rem; }
img { width: 100%; height: 100%; object-fit: cover; }
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr;
} }
.kicker { text-transform: uppercase; letter-spacing: .1em; color: var(
--brand); font-weight: 700; margin: 0; }
h1 { margin: 0; font-size: clamp(2rem, 4vw, 3rem); }
.ticks { list-style: none; padding: 0; margin: 0; }
.ticks li::before { content: "\2713 "; color: var(--brand); font-
```

```
weight: 700; }
.btn { justify-self: start; padding: .8rem 1.6rem; background: var(--
brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 757 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - Flat white</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="split">	The unique content of this page; exactly one per page.
	Generic block container for grouping and layout.
Drink of the month	A paragraph of text.
Flat white	The main heading; only one per page.
Double shot, silky milk. Available now at Green Leaf Cafe in Zam...	Strong importance (bold by default).
<ul class="ticks">	Unordered (bulleted) list.
Made with care	One list item.
Ask about it	A link styled as a button; it navigates, so it is a link and not a <button>.

Line	What it does
<img src="images/cafe-1.jpg" alt="Flat white" width="900" height="9...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
padding: clamp(1.5rem, 5vw, 4rem);	Space inside the element between its border and content.
align-content: center;	Centres the lines of a multi-line flex or grid container.

Declaration	What it does
gap: 1rem;	Space between grid or flex items without extra margins.
width: 100%;	Fills the container width.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr...	Applies from the given width upwards (mobile-first breakpoint).
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .1em;	Adds space between letters; useful for small capitals.
font-weight: 700;	Thickness of the text.
font-size: clamp(2rem, 4vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
list-style: none;	Removes bullets or numbers from a list.
content: "\2713 ";	The text or empty string for a pseudo-element.
background: var(--brand);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Image never distorts
- Text stays readable width
- Stacks on mobile with image below
- Button aligned left, not stretched

Exercises

1. Swap the sides with order or direction: rtl.
2. Add a second split section with the image on the left.
3. Use a background video instead of the image.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 758: Split-screen feature section for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 2 | Files: index.html, styles.css

Brief

Create a full-height section with text on one half and a photo filling the other half, stacking on small screens.

Learning goals

- Fill a grid cell with an image using object-fit
- Vertically centre content with align-content
- Use clamp() for fluid padding

Elements and CSS used

HTML elements	CSS features
main, div, p, h1, strong, ul, li, a, img	grid-template-columns: 1fr 1fr, object-fit: cover, align-content: center, clamp(), ::before content

Build guide

1. Write the text block and the image as the two children of .split.
2. Grid with one column by default, two above 800px.
3. Give the image height 100% and object-fit: cover.
4. Centre the text vertically with align-content.
5. Add tick marks to the list with ::before.
6. Use clamp() for padding.

Project 758: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - Mount Sinai sunrise</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="split">
    <div class="text">
      <p class="kicker">Hike of the month</p>
      <h1>Mount Sinai sunrise</h1>
      <p>Night climb, 7 km. Available now at Sinai Trekking Club in
Saint Catherine for <strong>400 EGP</strong>.</p>
      <ul class="ticks">
        <li>Made with care</li>
        <li>Satisfaction guaranteed</li>
        <li>Ask us anything</li>
      </ul>
      <a class="btn" href="contact.html">Ask about it</a>
    </div>
    <img src="images/trekking-1.jpg" alt="Mount Sinai sunrise"
width="900" height="900">
  </main>
</body>
</html>
```

Project 758: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.split { min-height: 100vh; display: grid; grid-template-columns: 1fr;
 }
.text { padding: clamp(1.5rem, 5vw, 4rem); display: grid; align-
content: center; gap: 1rem; }
img { width: 100%; height: 100%; object-fit: cover; }
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr;
} }
.kicker { text-transform: uppercase; letter-spacing: .1em; color: var(
--brand); font-weight: 700; margin: 0; }
h1 { margin: 0; font-size: clamp(2rem, 4vw, 3rem); }
.ticks { list-style: none; padding: 0; margin: 0; }
.ticks li::before { content: "\2713 "; color: var(--brand); font-
```

```
weight: 700; }
.btn { justify-self: start; padding: .8rem 1.6rem; background: var(--
brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 758 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - Mount Sinai sunrise</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="split">	The unique content of this page; exactly one per page.
	Generic block container for grouping and layout.
Hike of the month	A paragraph of text.
Mount Sinai sunrise	The main heading; only one per page.
Night climb, 7 km. Available now at Sinai Trekking Club in Saint...	Strong importance (bold by default).
<ul class="ticks">	Unordered (bulleted) list.
Made with care	One list item.

Line	What it does
Ask about it	A link styled as a button; it navigates, so it is a link and not a <button>.
<img src="images/trekking-1.jpg" alt="Mount Sinai sunrise" width="9...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
padding: clamp(1.5rem, 5vw, 4rem);	Space inside the element between its border and content.

Declaration	What it does
align-content: center;	Centres the lines of a multi-line flex or grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
width: 100%;	Fills the container width.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr...	Applies from the given width upwards (mobile-first breakpoint).
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .1em;	Adds space between letters; useful for small capitals.
font-weight: 700;	Thickness of the text.
font-size: clamp(2rem, 4vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
list-style: none;	Removes bullets or numbers from a list.
content: "\2713 ";	The text or empty string for a pseudo-element.
background: var(--brand);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Image never distorts
- Text stays readable width
- Stacks on mobile with image below

- Button aligned left, not stretched

Exercises

1. Swap the sides with order or direction: rtl.
2. Add a second split section with the image on the left.
3. Use a background video instead of the image.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 759: Split-screen feature section for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 2 | Files: index.html, styles.css

Brief

Create a full-height section with text on one half and a photo filling the other half, stacking on small screens.

Learning goals

- Fill a grid cell with an image using object-fit
- Vertically centre content with align-content
- Use clamp() for fluid padding

Elements and CSS used

HTML elements	CSS features
main, div, p, h1, strong, ul, li, a, img	grid-template-columns: 1fr 1fr, object-fit: cover, align-content: center, clamp(), ::before content

Build guide

1. Write the text block and the image as the two children of .split.
2. Grid with one column by default, two above 800px.
3. Give the image height 100% and object-fit: cover.
4. Centre the text vertically with align-content.
5. Add tick marks to the list with ::before.
6. Use clamp() for padding.

Project 759: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - Portrait session</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="split">
    <div class="text">
      <p class="kicker">Session of the month</p>
      <h1>Portrait session</h1>
      <p>One hour, 20 edited photos. Available now at Horizon
Photography in Maadi for <strong>1200 EGP</strong>.</p>
      <ul class="ticks">
        <li>Made with care</li>
        <li>Satisfaction guaranteed</li>
        <li>Ask us anything</li>
      </ul>
      <a class="btn" href="contact.html">Ask about it</a>
    </div>
    <img src="images/photo-1.jpg" alt="Portrait session" width="900"
height="900">
  </main>
</body>
</html>
```

Project 759: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.split { min-height: 100vh; display: grid; grid-template-columns: 1fr;
 }
.text { padding: clamp(1.5rem, 5vw, 4rem); display: grid; align-
content: center; gap: 1rem; }
img { width: 100%; height: 100%; object-fit: cover; }
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr;
} }
.kicker { text-transform: uppercase; letter-spacing: .1em; color: var(
--brand); font-weight: 700; margin: 0; }
h1 { margin: 0; font-size: clamp(2rem, 4vw, 3rem); }
.ticks { list-style: none; padding: 0; margin: 0; }
.ticks li::before { content: "\2713 "; color: var(--brand); font-
```

```
weight: 700; }
.btn { justify-self: start; padding: .8rem 1.6rem; background: var(--
brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 759 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - Portrait session</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="split">	The unique content of this page; exactly one per page.
	Generic block container for grouping and layout.
Session of the month	A paragraph of text.
Portrait session	The main heading; only one per page.
One hour, 20 edited photos. Available now at Horizon Photography...	Strong importance (bold by default).
<ul class="ticks">	Unordered (bulleted) list.
Made with care	One list item.
Ask about it	A link styled as a button; it navigates, so it is a link and not a <button>.

Line	What it does
<img src="images/photo-1.jpg" alt="Portrait session" width="900" he...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
padding: clamp(1.5rem, 5vw, 4rem);	Space inside the element between its border and content.
align-content: center;	Centres the lines of a multi-line flex or grid container.

Declaration	What it does
gap: 1rem;	Space between grid or flex items without extra margins.
width: 100%;	Fills the container width.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr...	Applies from the given width upwards (mobile-first breakpoint).
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .1em;	Adds space between letters; useful for small capitals.
font-weight: 700;	Thickness of the text.
font-size: clamp(2rem, 4vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
list-style: none;	Removes bullets or numbers from a list.
content: "\2713 ";	The text or empty string for a pseudo-element.
background: var(--brand);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Image never distorts
- Text stays readable width
- Stacks on mobile with image below
- Button aligned left, not stretched

Exercises

1. Swap the sides with order or direction: rtl.
2. Add a second split section with the image on the left.
3. Use a background video instead of the image.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 760: Split-screen feature section for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 2 | Files: index.html, styles.css

Brief

Create a full-height section with text on one half and a photo filling the other half, stacking on small screens.

Learning goals

- Fill a grid cell with an image using object-fit
- Vertically centre content with align-content
- Use clamp() for fluid padding

Elements and CSS used

HTML elements	CSS features
main, div, p, h1, strong, ul, li, a, img	grid-template-columns: 1fr 1fr, object-fit: cover, align-content: center, clamp(), ::before content

Build guide

1. Write the text block and the image as the two children of .split.
2. Grid with one column by default, two above 800px.
3. Give the image height 100% and object-fit: cover.
4. Centre the text vertically with align-content.
5. Add tick marks to the list with ::before.
6. Use clamp() for padding.

Project 760: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - Dotted notebook</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="split">
    <div class="text">
      <p class="kicker">Product of the month</p>
      <h1>Dotted notebook</h1>
      <p>A5, 160 pages. Available now at Papyrus Stationery in
Heliopolis for <strong>140 EGP</strong>.</p>
      <ul class="ticks">
        <li>Made with care</li>
        <li>Satisfaction guaranteed</li>
        <li>Ask us anything</li>
      </ul>
      <a class="btn" href="contact.html">Ask about it</a>
    </div>
    <img src="images/stationery-1.jpg" alt="Dotted notebook"
width="900" height="900">
  </main>
</body>
</html>
```

Project 760: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.split { min-height: 100vh; display: grid; grid-template-columns: 1fr;
 }
.text { padding: clamp(1.5rem, 5vw, 4rem); display: grid; align-
content: center; gap: 1rem; }
img { width: 100%; height: 100%; object-fit: cover; }
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr;
} }
.kicker { text-transform: uppercase; letter-spacing: .1em; color: var(
--brand); font-weight: 700; margin: 0; }
h1 { margin: 0; font-size: clamp(2rem, 4vw, 3rem); }
.ticks { list-style: none; padding: 0; margin: 0; }
.ticks li::before { content: "\2713 "; color: var(--brand); font-
```

```
weight: 700; }
.btn { justify-self: start; padding: .8rem 1.6rem; background: var(--
brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 760 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - Dotted notebook</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="split">	The unique content of this page; exactly one per page.
	Generic block container for grouping and layout.
Product of the month	A paragraph of text.
Dotted notebook	The main heading; only one per page.
A5, 160 pages. Available now at Papyrus Stationery in Heliopolis...	Strong importance (bold by default).
<ul class="ticks">	Unordered (bulleted) list.
Made with care	One list item.
Ask about it	A link styled as a button; it navigates, so it is a link and not a <button>.

Line	What it does
<img src="images/stationery-1.jpg" alt="Dotted notebook" width="900...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
padding: clamp(1.5rem, 5vw, 4rem);	Space inside the element between its border and content.
align-content: center;	Centres the lines of a multi-line flex or grid container.

Declaration	What it does
gap: 1rem;	Space between grid or flex items without extra margins.
width: 100%;	Fills the container width.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr...	Applies from the given width upwards (mobile-first breakpoint).
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .1em;	Adds space between letters; useful for small capitals.
font-weight: 700;	Thickness of the text.
font-size: clamp(2rem, 4vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
list-style: none;	Removes bullets or numbers from a list.
content: "\2713 ";	The text or empty string for a pseudo-element.
background: var(--brand);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Image never distorts
- Text stays readable width
- Stacks on mobile with image below
- Button aligned left, not stretched

Exercises

1. Swap the sides with order or direction: rtl.
2. Add a second split section with the image on the left.
3. Use a background video instead of the image.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 761: Split-screen feature section for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 2 | Files: index.html, styles.css

Brief

Create a full-height section with text on one half and a photo filling the other half, stacking on small screens.

Learning goals

- Fill a grid cell with an image using object-fit
- Vertically centre content with align-content
- Use clamp() for fluid padding

Elements and CSS used

HTML elements	CSS features
main, div, p, h1, strong, ul, li, a, img	grid-template-columns: 1fr 1fr, object-fit: cover, align-content: center, clamp(), ::before content

Build guide

1. Write the text block and the image as the two children of .split.
2. Grid with one column by default, two above 800px.
3. Give the image height 100% and object-fit: cover.
4. Centre the text vertically with align-content.
5. Add tick marks to the list with ::before.
6. Use clamp() for padding.

Project 761: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - Monstera</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="split">
    <div class="text">
      <p class="kicker">Plant of the month</p>
      <h1>Monstera</h1>
      <p>Large leaves, easy care. Available now at Oasis Plant
Nursery in Sheikh Zayed for <strong>250 EGP</strong>.</p>
      <ul class="ticks">
        <li>Made with care</li>
        <li>Satisfaction guaranteed</li>
        <li>Ask us anything</li>
      </ul>
      <a class="btn" href="contact.html">Ask about it</a>
    </div>
    <img src="images/plants-1.jpg" alt="Monstera" width="900"
height="900">
  </main>
</body>
</html>
```

Project 761: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.split { min-height: 100vh; display: grid; grid-template-columns: 1fr;
 }
.text { padding: clamp(1.5rem, 5vw, 4rem); display: grid; align-
content: center; gap: 1rem; }
img { width: 100%; height: 100%; object-fit: cover; }
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr;
} }
.kicker { text-transform: uppercase; letter-spacing: .1em; color: var(
--brand); font-weight: 700; margin: 0; }
h1 { margin: 0; font-size: clamp(2rem, 4vw, 3rem); }
.ticks { list-style: none; padding: 0; margin: 0; }
.ticks li::before { content: "\2713 "; color: var(--brand); font-
```

```
weight: 700; }
.btn { justify-self: start; padding: .8rem 1.6rem; background: var(--
brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 761 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - Monstera</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="split">	The unique content of this page; exactly one per page.
	Generic block container for grouping and layout.
Plant of the month	A paragraph of text.
Monstera	The main heading; only one per page.
Large leaves, easy care. Available now at Oasis Plant Nursery in...	Strong importance (bold by default).
<ul class="ticks">	Unordered (bulleted) list.
Made with care	One list item.
Ask about it	A link styled as a button; it navigates, so it is a link and not a <button>.

Line	What it does
<img src="images/plants-1.jpg" alt="Monstera" width="900" height="9...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
padding: clamp(1.5rem, 5vw, 4rem);	Space inside the element between its border and content.
align-content: center;	Centres the lines of a multi-line flex or grid container.

Declaration	What it does
gap: 1rem;	Space between grid or flex items without extra margins.
width: 100%;	Fills the container width.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr...	Applies from the given width upwards (mobile-first breakpoint).
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .1em;	Adds space between letters; useful for small capitals.
font-weight: 700;	Thickness of the text.
font-size: clamp(2rem, 4vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
list-style: none;	Removes bullets or numbers from a list.
content: "\2713 ";	The text or empty string for a pseudo-element.
background: var(--brand);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Image never distorts
- Text stays readable width
- Stacks on mobile with image below
- Button aligned left, not stretched

Exercises

1. Swap the sides with order or direction: rtl.
2. Add a second split section with the image on the left.
3. Use a background video instead of the image.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 762: Split-screen feature section for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 2 | Files: index.html, styles.css

Brief

Create a full-height section with text on one half and a photo filling the other half, stacking on small screens.

Learning goals

- Fill a grid cell with an image using object-fit
- Vertically centre content with align-content
- Use clamp() for fluid padding

Elements and CSS used

HTML elements	CSS features
main, div, p, h1, strong, ul, li, a, img	grid-template-columns: 1fr 1fr, object-fit: cover, align-content: center, clamp(), ::before content

Build guide

1. Write the text block and the image as the two children of .split.
2. Grid with one column by default, two above 800px.
3. Give the image height 100% and object-fit: cover.
4. Centre the text vertically with align-content.
5. Add tick marks to the list with ::before.
6. Use clamp() for padding.

Project 762: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - Oak dining table</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="split">
    <div class="text">
      <p class="kicker">Piece of the month</p>
      <h1>Oak dining table</h1>
      <p>Seats six. Available now at Cedar Furniture in Damietta for
<strong>9500 EGP</strong>.</p>
      <ul class="ticks">
        <li>Made with care</li>
        <li>Satisfaction guaranteed</li>
        <li>Ask us anything</li>
      </ul>
      <a class="btn" href="contact.html">Ask about it</a>
    </div>
    <img src="images/furniture-1.jpg" alt="Oak dining table"
width="900" height="900">
  </main>
</body>
</html>
```

Project 762: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.split { min-height: 100vh; display: grid; grid-template-columns: 1fr;
 }
.text { padding: clamp(1.5rem, 5vw, 4rem); display: grid; align-
content: center; gap: 1rem; }
img { width: 100%; height: 100%; object-fit: cover; }
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr;
} }
.kicker { text-transform: uppercase; letter-spacing: .1em; color: var(
--brand); font-weight: 700; margin: 0; }
h1 { margin: 0; font-size: clamp(2rem, 4vw, 3rem); }
.ticks { list-style: none; padding: 0; margin: 0; }
.ticks li::before { content: "\2713 "; color: var(--brand); font-
```

```
weight: 700; }
.btn { justify-self: start; padding: .8rem 1.6rem; background: var(--
brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 762 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - Oak dining table</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="split">	The unique content of this page; exactly one per page.
	Generic block container for grouping and layout.
Piece of the month	A paragraph of text.
Oak dining table	The main heading; only one per page.
Seats six. Available now at Cedar Furniture in Damietta for <str...	Strong importance (bold by default).
<ul class="ticks">	Unordered (bulleted) list.
Made with care	One list item.
Ask about it	A link styled as a button; it navigates, so it is a link and not a <button>.

Line	What it does
<img src="images/furniture-1.jpg" alt="Oak dining table" width="900...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
padding: clamp(1.5rem, 5vw, 4rem);	Space inside the element between its border and content.
align-content: center;	Centres the lines of a multi-line flex or grid container.

Declaration	What it does
gap: 1rem;	Space between grid or flex items without extra margins.
width: 100%;	Fills the container width.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr...	Applies from the given width upwards (mobile-first breakpoint).
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .1em;	Adds space between letters; useful for small capitals.
font-weight: 700;	Thickness of the text.
font-size: clamp(2rem, 4vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
list-style: none;	Removes bullets or numbers from a list.
content: "\2713 ";	The text or empty string for a pseudo-element.
background: var(--brand);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Image never distorts
- Text stays readable width
- Stacks on mobile with image below
- Button aligned left, not stretched

Exercises

1. Swap the sides with order or direction: rtl.
2. Add a second split section with the image on the left.
3. Use a background video instead of the image.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 763: Split-screen feature section for Byte Repair

Theme: Byte Repair (Nasr City) | Level 2 | Files: index.html, styles.css

Brief

Create a full-height section with text on one half and a photo filling the other half, stacking on small screens.

Learning goals

- Fill a grid cell with an image using object-fit
- Vertically centre content with align-content
- Use clamp() for fluid padding

Elements and CSS used

HTML elements	CSS features
main, div, p, h1, strong, ul, li, a, img	grid-template-columns: 1fr 1fr, object-fit: cover, align-content: center, clamp(), ::before content

Build guide

1. Write the text block and the image as the two children of .split.
2. Grid with one column by default, two above 800px.
3. Give the image height 100% and object-fit: cover.
4. Centre the text vertically with align-content.
5. Add tick marks to the list with ::before.
6. Use clamp() for padding.

Project 763: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - Screen replacement</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="split">
    <div class="text">
      <p class="kicker">Repair of the month</p>
      <h1>Screen replacement</h1>
      <p>Most phones, 1 hour. Available now at Byte Repair in Nasr
City for <strong>From 800 EGP</strong>.</p>
      <ul class="ticks">
        <li>Made with care</li>
        <li>Satisfaction guaranteed</li>
        <li>Ask us anything</li>
      </ul>
      <a class="btn" href="contact.html">Ask about it</a>
    </div>
    <img src="images/repair-1.jpg" alt="Screen replacement"
width="900" height="900">
  </main>
</body>
</html>
```

Project 763: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.split { min-height: 100vh; display: grid; grid-template-columns: 1fr;
 }
.text { padding: clamp(1.5rem, 5vw, 4rem); display: grid; align-
content: center; gap: 1rem; }
img { width: 100%; height: 100%; object-fit: cover; }
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr;
} }
.kicker { text-transform: uppercase; letter-spacing: .1em; color: var(
--brand); font-weight: 700; margin: 0; }
h1 { margin: 0; font-size: clamp(2rem, 4vw, 3rem); }
.ticks { list-style: none; padding: 0; margin: 0; }
.ticks li::before { content: "\2713 "; color: var(--brand); font-
```

```
weight: 700; }
.btn { justify-self: start; padding: .8rem 1.6rem; background: var(--
brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 763 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - Screen replacement</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="split">	The unique content of this page; exactly one per page.
	Generic block container for grouping and layout.
Repair of the month	A paragraph of text.
Screen replacement	The main heading; only one per page.
Most phones, 1 hour. Available now at Byte Repair in Nasr City f...	Strong importance (bold by default).
<ul class="ticks">	Unordered (bulleted) list.
Made with care	One list item.

Line	What it does
Ask about it	A link styled as a button; it navigates, so it is a link and not a <button>.
<img src="images/repair-1.jpg" alt="Screen replacement" width="900"...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
padding: clamp(1.5rem, 5vw, 4rem);	Space inside the element between its border and content.

Declaration	What it does
align-content: center;	Centres the lines of a multi-line flex or grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
width: 100%;	Fills the container width.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr...	Applies from the given width upwards (mobile-first breakpoint).
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .1em;	Adds space between letters; useful for small capitals.
font-weight: 700;	Thickness of the text.
font-size: clamp(2rem, 4vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
list-style: none;	Removes bullets or numbers from a list.
content: "\2713 ";	The text or empty string for a pseudo-element.
background: var(--brand);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Image never distorts
- Text stays readable width
- Stacks on mobile with image below

- Button aligned left, not stretched

Exercises

1. Swap the sides with order or direction: rtl.
2. Add a second split section with the image on the left.
3. Use a background video instead of the image.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 764: Split-screen feature section for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 2 | Files: index.html, styles.css

Brief

Create a full-height section with text on one half and a photo filling the other half, stacking on small screens.

Learning goals

- Fill a grid cell with an image using object-fit
- Vertically centre content with align-content
- Use clamp() for fluid padding

Elements and CSS used

HTML elements	CSS features
main, div, p, h1, strong, ul, li, a, img	grid-template-columns: 1fr 1fr, object-fit: cover, align-content: center, clamp(), ::before content

Build guide

1. Write the text block and the image as the two children of .split.
2. Grid with one column by default, two above 800px.
3. Give the image height 100% and object-fit: cover.
4. Centre the text vertically with align-content.
5. Add tick marks to the list with ::before.
6. Use clamp() for padding.

Project 764: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - Full grooming</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="split">
    <div class="text">
      <p class="kicker">Service of the month</p>
      <h1>Full grooming</h1>
      <p>Bath, cut and nails. Available now at Sahara Pet Care in New
Cairo for <strong>400 EGP</strong>.</p>
      <ul class="ticks">
        <li>Made with care</li>
        <li>Satisfaction guaranteed</li>
        <li>Ask us anything</li>
      </ul>
      <a class="btn" href="contact.html">Ask about it</a>
    </div>
    <img src="images/pets-1.jpg" alt="Full grooming" width="900"
height="900">
  </main>
</body>
</html>
```

Project 764: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.split { min-height: 100vh; display: grid; grid-template-columns: 1fr;
 }
.text { padding: clamp(1.5rem, 5vw, 4rem); display: grid; align-
content: center; gap: 1rem; }
img { width: 100%; height: 100%; object-fit: cover; }
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr;
} }
.kicker { text-transform: uppercase; letter-spacing: .1em; color: var(
--brand); font-weight: 700; margin: 0; }
h1 { margin: 0; font-size: clamp(2rem, 4vw, 3rem); }
.ticks { list-style: none; padding: 0; margin: 0; }
.ticks li::before { content: "\2713 "; color: var(--brand); font-
```

```
weight: 700; }
.btn { justify-self: start; padding: .8rem 1.6rem; background: var(--
brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 764 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - Full grooming</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="split">	The unique content of this page; exactly one per page.
	Generic block container for grouping and layout.
Service of the month	A paragraph of text.
Full grooming	The main heading; only one per page.
Bath, cut and nails. Available now at Sahara Pet Care in New Cai...	Strong importance (bold by default).
<ul class="ticks">	Unordered (bulleted) list.
Made with care	One list item.
Ask about it	A link styled as a button; it navigates, so it is a link and not a <button>.

Line	What it does
<img src="images/pets-1.jpg" alt="Full grooming" width="900" height...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
padding: clamp(1.5rem, 5vw, 4rem);	Space inside the element between its border and content.
align-content: center;	Centres the lines of a multi-line flex or grid container.

Declaration	What it does
gap: 1rem;	Space between grid or flex items without extra margins.
width: 100%;	Fills the container width.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr...	Applies from the given width upwards (mobile-first breakpoint).
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .1em;	Adds space between letters; useful for small capitals.
font-weight: 700;	Thickness of the text.
font-size: clamp(2rem, 4vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
list-style: none;	Removes bullets or numbers from a list.
content: "\2713 ";	The text or empty string for a pseudo-element.
background: var(--brand);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Image never distorts
- Text stays readable width
- Stacks on mobile with image below
- Button aligned left, not stretched

Exercises

1. Swap the sides with order or direction: rtl.
2. Add a second split section with the image on the left.
3. Use a background video instead of the image.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 765: Split-screen feature section for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Create a full-height section with text on one half and a photo filling the other half, stacking on small screens.

Learning goals

- Fill a grid cell with an image using object-fit
- Vertically centre content with align-content
- Use clamp() for fluid padding

Elements and CSS used

HTML elements	CSS features
main, div, p, h1, strong, ul, li, a, img	grid-template-columns: 1fr 1fr, object-fit: cover, align-content: center, clamp(), ::before content

Build guide

1. Write the text block and the image as the two children of .split.
2. Grid with one column by default, two above 800px.
3. Give the image height 100% and object-fit: cover.
4. Centre the text vertically with align-content.
5. Add tick marks to the list with ::before.
6. Use clamp() for padding.

Project 765: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - Taster session</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="split">
    <div class="text">
      <p class="kicker">Lesson of the month</p>
      <h1>Taster session</h1>
      <p>Two hours on the water. Available now at Alexandria Sailing
School in Alexandria for <strong>500 EGP</strong>.</p>
      <ul class="ticks">
        <li>Made with care</li>
        <li>Satisfaction guaranteed</li>
        <li>Ask us anything</li>
      </ul>
      <a class="btn" href="contact.html">Ask about it</a>
    </div>
    <img src="images/sailing-1.jpg" alt="Taster session" width="900"
height="900">
  </main>
</body>
</html>
```

Project 765: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.split { min-height: 100vh; display: grid; grid-template-columns: 1fr;
 }
.text { padding: clamp(1.5rem, 5vw, 4rem); display: grid; align-
content: center; gap: 1rem; }
img { width: 100%; height: 100%; object-fit: cover; }
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr;
} }
.kicker { text-transform: uppercase; letter-spacing: .1em; color: var(
--brand); font-weight: 700; margin: 0; }
h1 { margin: 0; font-size: clamp(2rem, 4vw, 3rem); }
.ticks { list-style: none; padding: 0; margin: 0; }
.ticks li::before { content: "\2713 "; color: var(--brand); font-
```

```
weight: 700; }
.btn { justify-self: start; padding: .8rem 1.6rem; background: var(--
brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 765 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - Taster session</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="split">	The unique content of this page; exactly one per page.
	Generic block container for grouping and layout.
Lesson of the month	A paragraph of text.
Taster session	The main heading; only one per page.
Two hours on the water. Available now at Alexandria Sailing Scho...	Strong importance (bold by default).
<ul class="ticks">	Unordered (bulleted) list.
Made with care	One list item.
Ask about it	A link styled as a button; it navigates, so it is a link and not a <button>.

Line	What it does
<img src="images/sailing-1.jpg" alt="Taster session" width="900" he...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
padding: clamp(1.5rem, 5vw, 4rem);	Space inside the element between its border and content.
align-content: center;	Centres the lines of a multi-line flex or grid container.

Declaration	What it does
gap: 1rem;	Space between grid or flex items without extra margins.
width: 100%;	Fills the container width.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr...	Applies from the given width upwards (mobile-first breakpoint).
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .1em;	Adds space between letters; useful for small capitals.
font-weight: 700;	Thickness of the text.
font-size: clamp(2rem, 4vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
list-style: none;	Removes bullets or numbers from a list.
content: "\2713 ";	The text or empty string for a pseudo-element.
background: var(--brand);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Image never distorts
- Text stays readable width
- Stacks on mobile with image below
- Button aligned left, not stretched

Exercises

1. Swap the sides with order or direction: rtl.
2. Add a second split section with the image on the left.
3. Use a background video instead of the image.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 766: Split-screen feature section for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Create a full-height section with text on one half and a photo filling the other half, stacking on small screens.

Learning goals

- Fill a grid cell with an image using object-fit
- Vertically centre content with align-content
- Use clamp() for fluid padding

Elements and CSS used

HTML elements	CSS features
main, div, p, h1, strong, ul, li, a, img	grid-template-columns: 1fr 1fr, object-fit: cover, align-content: center, clamp(), ::before content

Build guide

1. Write the text block and the image as the two children of .split.
2. Grid with one column by default, two above 800px.
3. Give the image height 100% and object-fit: cover.
4. Centre the text vertically with align-content.
5. Add tick marks to the list with ::before.
6. Use clamp() for padding.

Project 766: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - Lotus pendant</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="split">
    <div class="text">
      <p class="kicker">Item of the month</p>
      <h1>Lotus pendant</h1>
      <p>Sterling silver. Available now at Habiba Handmade Jewellery
in Aswan for <strong>650 EGP</strong>.</p>
      <ul class="ticks">
        <li>Made with care</li>
        <li>Satisfaction guaranteed</li>
        <li>Ask us anything</li>
      </ul>
      <a class="btn" href="contact.html">Ask about it</a>
    </div>
    <img src="images/jewellery-1.jpg" alt="Lotus pendant" width="900"
height="900">
  </main>
</body>
</html>
```

Project 766: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.split { min-height: 100vh; display: grid; grid-template-columns: 1fr;
 }
.text { padding: clamp(1.5rem, 5vw, 4rem); display: grid; align-
content: center; gap: 1rem; }
img { width: 100%; height: 100%; object-fit: cover; }
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr;
} }
.kicker { text-transform: uppercase; letter-spacing: .1em; color: var(
--brand); font-weight: 700; margin: 0; }
h1 { margin: 0; font-size: clamp(2rem, 4vw, 3rem); }
.ticks { list-style: none; padding: 0; margin: 0; }
.ticks li::before { content: "\2713 "; color: var(--brand); font-
```

```
weight: 700; }
.btn { justify-self: start; padding: .8rem 1.6rem; background: var(--
brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 766 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - Lotus pendant</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="split">	The unique content of this page; exactly one per page.
	Generic block container for grouping and layout.
Item of the month	A paragraph of text.
Lotus pendant	The main heading; only one per page.
Sterling silver. Available now at Habiba Handmade Jewellery in A...	Strong importance (bold by default).
<ul class="ticks">	Unordered (bulleted) list.
Made with care	One list item.

Line	What it does
Ask about it	A link styled as a button; it navigates, so it is a link and not a <button>.
<img src="images/jewellery-1.jpg" alt="Lotus pendant" width="900" h...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
padding: clamp(1.5rem, 5vw, 4rem);	Space inside the element between its border and content.

Declaration	What it does
align-content: center;	Centres the lines of a multi-line flex or grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
width: 100%;	Fills the container width.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr...	Applies from the given width upwards (mobile-first breakpoint).
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .1em;	Adds space between letters; useful for small capitals.
font-weight: 700;	Thickness of the text.
font-size: clamp(2rem, 4vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
list-style: none;	Removes bullets or numbers from a list.
content: "\2713 ";	The text or empty string for a pseudo-element.
background: var(--brand);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Image never distorts
- Text stays readable width
- Stacks on mobile with image below

- Button aligned left, not stretched

Exercises

1. Swap the sides with order or direction: rtl.
2. Add a second split section with the image on the left.
3. Use a background video instead of the image.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 767: Split-screen feature section for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 2 | Files: index.html, styles.css

Brief

Create a full-height section with text on one half and a photo filling the other half, stacking on small screens.

Learning goals

- Fill a grid cell with an image using object-fit
- Vertically centre content with align-content
- Use clamp() for fluid padding

Elements and CSS used

HTML elements	CSS features
main, div, p, h1, strong, ul, li, a, img	grid-template-columns: 1fr 1fr, object-fit: cover, align-content: center, clamp(), ::before content

Build guide

1. Write the text block and the image as the two children of .split.
2. Grid with one column by default, two above 800px.
3. Give the image height 100% and object-fit: cover.
4. Centre the text vertically with align-content.
5. Add tick marks to the list with ::before.
6. Use clamp() for padding.

Project 767: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - Intro to the wheel</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="split">
    <div class="text">
      <p class="kicker">Workshop of the month</p>
      <h1>Intro to the wheel</h1>
      <p>Three hours, take home a bowl. Available now at Fayoum
Pottery Studio in Tunis Village for <strong>450 EGP</strong>.</p>
      <ul class="ticks">
        <li>Made with care</li>
        <li>Satisfaction guaranteed</li>
        <li>Ask us anything</li>
      </ul>
      <a class="btn" href="contact.html">Ask about it</a>
    </div>
    <img src="images/pottery-1.jpg" alt="Intro to the wheel"
width="900" height="900">
  </main>
</body>
</html>
```

Project 767: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.split { min-height: 100vh; display: grid; grid-template-columns: 1fr;
 }
.text { padding: clamp(1.5rem, 5vw, 4rem); display: grid; align-
content: center; gap: 1rem; }
img { width: 100%; height: 100%; object-fit: cover; }
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr;
} }
.kicker { text-transform: uppercase; letter-spacing: .1em; color: var(
--brand); font-weight: 700; margin: 0; }
h1 { margin: 0; font-size: clamp(2rem, 4vw, 3rem); }
.ticks { list-style: none; padding: 0; margin: 0; }
.ticks li::before { content: "\2713 "; color: var(--brand); font-
```

```
weight: 700; }
.btn { justify-self: start; padding: .8rem 1.6rem; background: var(--
brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 767 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - Intro to the wheel</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="split">	The unique content of this page; exactly one per page.
	Generic block container for grouping and layout.
Workshop of the month	A paragraph of text.
Intro to the wheel	The main heading; only one per page.
Three hours, take home a bowl. Available now at Fayoum Pottery S...	Strong importance (bold by default).
<ul class="ticks">	Unordered (bulleted) list.
Made with care	One list item.
Ask about it	A link styled as a button; it navigates, so it is a link and not a <button>.

Line	What it does
<img src="images/pottery-1.jpg" alt="Intro to the wheel" width="900...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
padding: clamp(1.5rem, 5vw, 4rem);	Space inside the element between its border and content.
align-content: center;	Centres the lines of a multi-line flex or grid container.

Declaration	What it does
gap: 1rem;	Space between grid or flex items without extra margins.
width: 100%;	Fills the container width.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr...	Applies from the given width upwards (mobile-first breakpoint).
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .1em;	Adds space between letters; useful for small capitals.
font-weight: 700;	Thickness of the text.
font-size: clamp(2rem, 4vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
list-style: none;	Removes bullets or numbers from a list.
content: "\2713 ";	The text or empty string for a pseudo-element.
background: var(--brand);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Image never distorts
- Text stays readable width
- Stacks on mobile with image below
- Button aligned left, not stretched

Exercises

1. Swap the sides with order or direction: rtl.
2. Add a second split section with the image on the left.
3. Use a background video instead of the image.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 768: Split-screen feature section for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 2 | Files: index.html, styles.css

Brief

Create a full-height section with text on one half and a photo filling the other half, stacking on small screens.

Learning goals

- Fill a grid cell with an image using object-fit
- Vertically centre content with align-content
- Use clamp() for fluid padding

Elements and CSS used

HTML elements	CSS features
main, div, p, h1, strong, ul, li, a, img	grid-template-columns: 1fr 1fr, object-fit: cover, align-content: center, clamp(), ::before content

Build guide

1. Write the text block and the image as the two children of .split.
2. Grid with one column by default, two above 800px.
3. Give the image height 100% and object-fit: cover.
4. Centre the text vertically with align-content.
5. Add tick marks to the list with ::before.
6. Use clamp() for padding.

Project 768: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - Haircut and blow-dry</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="split">
    <div class="text">
      <p class="kicker">Treatment of the month</p>
      <h1>Haircut and blow-dry</h1>
      <p>Consultation included. Available now at Cleopatra Beauty
Salon in Dokki for <strong>350 EGP</strong>.</p>
      <ul class="ticks">
        <li>Made with care</li>
        <li>Satisfaction guaranteed</li>
        <li>Ask us anything</li>
      </ul>
      <a class="btn" href="contact.html">Ask about it</a>
    </div>
    <img src="images/salon-1.jpg" alt="Haircut and blow-dry"
width="900" height="900">
  </main>
</body>
</html>
```

Project 768: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.split { min-height: 100vh; display: grid; grid-template-columns: 1fr;
 }
.text { padding: clamp(1.5rem, 5vw, 4rem); display: grid; align-
content: center; gap: 1rem; }
img { width: 100%; height: 100%; object-fit: cover; }
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr;
} }
.kicker { text-transform: uppercase; letter-spacing: .1em; color: var(
--brand); font-weight: 700; margin: 0; }
h1 { margin: 0; font-size: clamp(2rem, 4vw, 3rem); }
.ticks { list-style: none; padding: 0; margin: 0; }
.ticks li::before { content: "\2713 "; color: var(--brand); font-
```

```
weight: 700; }
.btn { justify-self: start; padding: .8rem 1.6rem; background: var(--
brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 768 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - Haircut and blow-dry</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="split">	The unique content of this page; exactly one per page.
	Generic block container for grouping and layout.
Treatment of the month	A paragraph of text.
Haircut and blow-dry	The main heading; only one per page.
Consultation included. Available now at Cleopatra Beauty Salon i...	Strong importance (bold by default).
<ul class="ticks">	Unordered (bulleted) list.
Made with care	One list item.

Line	What it does
Ask about it	A link styled as a button; it navigates, so it is a link and not a <button>.
<img src="images/salon-1.jpg" alt="Haircut and blow-dry" width="900...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
padding: clamp(1.5rem, 5vw, 4rem);	Space inside the element between its border and content.

Declaration	What it does
align-content: center;	Centres the lines of a multi-line flex or grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
width: 100%;	Fills the container width.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr...	Applies from the given width upwards (mobile-first breakpoint).
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .1em;	Adds space between letters; useful for small capitals.
font-weight: 700;	Thickness of the text.
font-size: clamp(2rem, 4vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
list-style: none;	Removes bullets or numbers from a list.
content: "\2713 ";	The text or empty string for a pseudo-element.
background: var(--brand);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Image never distorts
- Text stays readable width
- Stacks on mobile with image below

- Button aligned left, not stretched

Exercises

1. Swap the sides with order or direction: rtl.
2. Add a second split section with the image on the left.
3. Use a background video instead of the image.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 769: Split-screen feature section for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 2 | Files: index.html, styles.css

Brief

Create a full-height section with text on one half and a photo filling the other half, stacking on small screens.

Learning goals

- Fill a grid cell with an image using object-fit
- Vertically centre content with align-content
- Use clamp() for fluid padding

Elements and CSS used

HTML elements	CSS features
main, div, p, h1, strong, ul, li, a, img	grid-template-columns: 1fr 1fr, object-fit: cover, align-content: center, clamp(), ::before content

Build guide

1. Write the text block and the image as the two children of .split.
2. Grid with one column by default, two above 800px.
3. Give the image height 100% and object-fit: cover.
4. Centre the text vertically with align-content.
5. Add tick marks to the list with ::before.
6. Use clamp() for padding.

Project 769: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - Oil change</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="split">
    <div class="text">
      <p class="kicker">Service of the month</p>
      <h1>Oil change</h1>
      <p>Filter included. Available now at Suez Auto Service in Suez
for <strong>600 EGP</strong>.</p>
      <ul class="ticks">
        <li>Made with care</li>
        <li>Satisfaction guaranteed</li>
        <li>Ask us anything</li>
      </ul>
      <a class="btn" href="contact.html">Ask about it</a>
    </div>
    <img src="images/auto-1.jpg" alt="Oil change" width="900"
height="900">
  </main>
</body>
</html>
```

Project 769: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.split { min-height: 100vh; display: grid; grid-template-columns: 1fr;
 }
.text { padding: clamp(1.5rem, 5vw, 4rem); display: grid; align-
content: center; gap: 1rem; }
img { width: 100%; height: 100%; object-fit: cover; }
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr;
} }
.kicker { text-transform: uppercase; letter-spacing: .1em; color: var(
--brand); font-weight: 700; margin: 0; }
h1 { margin: 0; font-size: clamp(2rem, 4vw, 3rem); }
.ticks { list-style: none; padding: 0; margin: 0; }
.ticks li::before { content: "\2713 "; color: var(--brand); font-
```

```
weight: 700; }
.btn { justify-self: start; padding: .8rem 1.6rem; background: var(--
brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 769 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - Oil change</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="split">	The unique content of this page; exactly one per page.
	Generic block container for grouping and layout.
Service of the month	A paragraph of text.
Oil change	The main heading; only one per page.
Filter included. Available now at Suez Auto Service in Suez for ...	Strong importance (bold by default).
<ul class="ticks">	Unordered (bulleted) list.
Made with care	One list item.
Ask about it	A link styled as a button; it navigates, so it is a link and not a <button>.

Line	What it does
<img src="images/auto-1.jpg" alt="Oil change" width="900" height="9...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
padding: clamp(1.5rem, 5vw, 4rem);	Space inside the element between its border and content.
align-content: center;	Centres the lines of a multi-line flex or grid container.

Declaration	What it does
gap: 1rem;	Space between grid or flex items without extra margins.
width: 100%;	Fills the container width.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr...	Applies from the given width upwards (mobile-first breakpoint).
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .1em;	Adds space between letters; useful for small capitals.
font-weight: 700;	Thickness of the text.
font-size: clamp(2rem, 4vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
list-style: none;	Removes bullets or numbers from a list.
content: "\2713 ";	The text or empty string for a pseudo-element.
background: var(--brand);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Image never distorts
- Text stays readable width
- Stacks on mobile with image below
- Button aligned left, not stretched

Exercises

1. Swap the sides with order or direction: rtl.
2. Add a second split section with the image on the left.
3. Use a background video instead of the image.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 770: Split-screen feature section for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 2 | Files: index.html, styles.css

Brief

Create a full-height section with text on one half and a photo filling the other half, stacking on small screens.

Learning goals

- Fill a grid cell with an image using object-fit
- Vertically centre content with align-content
- Use clamp() for fluid padding

Elements and CSS used

HTML elements	CSS features
main, div, p, h1, strong, ul, li, a, img	grid-template-columns: 1fr 1fr, object-fit: cover, align-content: center, clamp(), ::before content

Build guide

1. Write the text block and the image as the two children of .split.
2. Grid with one column by default, two above 800px.
3. Give the image height 100% and object-fit: cover.
4. Centre the text vertically with align-content.
5. Add tick marks to the list with ::before.
6. Use clamp() for padding.

Project 770: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - Oud for beginners</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="split">
    <div class="text">
      <p class="kicker">Course of the month</p>
      <h1>Oud for beginners</h1>
      <p>Eight weekly lessons. Available now at Luxor Music Academy
in Luxor for <strong>1600 EGP</strong>.</p>
      <ul class="ticks">
        <li>Made with care</li>
        <li>Satisfaction guaranteed</li>
        <li>Ask us anything</li>
      </ul>
      <a class="btn" href="contact.html">Ask about it</a>
    </div>
    <img src="images/music-1.jpg" alt="Oud for beginners" width="900"
height="900">
  </main>
</body>
</html>
```

Project 770: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.split { min-height: 100vh; display: grid; grid-template-columns: 1fr;
 }
.text { padding: clamp(1.5rem, 5vw, 4rem); display: grid; align-
content: center; gap: 1rem; }
img { width: 100%; height: 100%; object-fit: cover; }
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr;
} }
.kicker { text-transform: uppercase; letter-spacing: .1em; color: var(
--brand); font-weight: 700; margin: 0; }
h1 { margin: 0; font-size: clamp(2rem, 4vw, 3rem); }
.ticks { list-style: none; padding: 0; margin: 0; }
.ticks li::before { content: "\2713 "; color: var(--brand); font-
```

```
weight: 700; }
.btn { justify-self: start; padding: .8rem 1.6rem; background: var(--
brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 770 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - Oud for beginners</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="split">	The unique content of this page; exactly one per page.
	Generic block container for grouping and layout.
Course of the month	A paragraph of text.
Oud for beginners	The main heading; only one per page.
Eight weekly lessons. Available now at Luxor Music Academy in Lu...	Strong importance (bold by default).
<ul class="ticks">	Unordered (bulleted) list.
Made with care	One list item.
Ask about it	A link styled as a button; it navigates, so it is a link and not a <button>.

Line	What it does
<img src="images/music-1.jpg" alt="Oud for beginners" width="900" h...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
padding: clamp(1.5rem, 5vw, 4rem);	Space inside the element between its border and content.
align-content: center;	Centres the lines of a multi-line flex or grid container.

Declaration	What it does
gap: 1rem;	Space between grid or flex items without extra margins.
width: 100%;	Fills the container width.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr...	Applies from the given width upwards (mobile-first breakpoint).
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .1em;	Adds space between letters; useful for small capitals.
font-weight: 700;	Thickness of the text.
font-size: clamp(2rem, 4vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
list-style: none;	Removes bullets or numbers from a list.
content: "\2713 ";	The text or empty string for a pseudo-element.
background: var(--brand);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Image never distorts
- Text stays readable width
- Stacks on mobile with image below
- Button aligned left, not stretched

Exercises

1. Swap the sides with order or direction: rtl.
2. Add a second split section with the image on the left.
3. Use a background video instead of the image.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 771: Split-screen feature section for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 2 | Files: index.html, styles.css

Brief

Create a full-height section with text on one half and a photo filling the other half, stacking on small screens.

Learning goals

- Fill a grid cell with an image using object-fit
- Vertically centre content with align-content
- Use clamp() for fluid padding

Elements and CSS used

HTML elements	CSS features
main, div, p, h1, strong, ul, li, a, img	grid-template-columns: 1fr 1fr, object-fit: cover, align-content: center, clamp(), ::before content

Build guide

1. Write the text block and the image as the two children of .split.
2. Grid with one column by default, two above 800px.
3. Give the image height 100% and object-fit: cover.
4. Centre the text vertically with align-content.
5. Add tick marks to the list with ::before.
6. Use clamp() for padding.

Project 771: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - Grilled sea bass</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="split">
    <div class="text">
      <p class="kicker">Dish of the month</p>
      <h1>Grilled sea bass</h1>
      <p>With rice and salad. Available now at Port Said Seafood in
Port Said for <strong>320 EGP</strong>.</p>
      <ul class="ticks">
        <li>Made with care</li>
        <li>Satisfaction guaranteed</li>
        <li>Ask us anything</li>
      </ul>
      <a class="btn" href="contact.html">Ask about it</a>
    </div>
    <img src="images/restaurant-1.jpg" alt="Grilled sea bass"
width="900" height="900">
  </main>
</body>
</html>
```

Project 771: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.split { min-height: 100vh; display: grid; grid-template-columns: 1fr;
 }
.text { padding: clamp(1.5rem, 5vw, 4rem); display: grid; align-
content: center; gap: 1rem; }
img { width: 100%; height: 100%; object-fit: cover; }
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr;
} }
.kicker { text-transform: uppercase; letter-spacing: .1em; color: var(
--brand); font-weight: 700; margin: 0; }
h1 { margin: 0; font-size: clamp(2rem, 4vw, 3rem); }
.ticks { list-style: none; padding: 0; margin: 0; }
.ticks li::before { content: "\2713 "; color: var(--brand); font-
```

```
weight: 700; }
.btn { justify-self: start; padding: .8rem 1.6rem; background: var(--
brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 771 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - Grilled sea bass</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="split">	The unique content of this page; exactly one per page.
	Generic block container for grouping and layout.
Dish of the month	A paragraph of text.
Grilled sea bass	The main heading; only one per page.
With rice and salad. Available now at Port Said Seafood in Port ...	Strong importance (bold by default).
<ul class="ticks">	Unordered (bulleted) list.
Made with care	One list item.
Ask about it	A link styled as a button; it navigates, so it is a link and not a <button>.

Line	What it does
<img src="images/restaurant-1.jpg" alt="Grilled sea bass" width="90...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
padding: clamp(1.5rem, 5vw, 4rem);	Space inside the element between its border and content.
align-content: center;	Centres the lines of a multi-line flex or grid container.

Declaration	What it does
gap: 1rem;	Space between grid or flex items without extra margins.
width: 100%;	Fills the container width.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr...	Applies from the given width upwards (mobile-first breakpoint).
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .1em;	Adds space between letters; useful for small capitals.
font-weight: 700;	Thickness of the text.
font-size: clamp(2rem, 4vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
list-style: none;	Removes bullets or numbers from a list.
content: "\2713 ";	The text or empty string for a pseudo-element.
background: var(--brand);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Image never distorts
- Text stays readable width
- Stacks on mobile with image below
- Button aligned left, not stretched

Exercises

1. Swap the sides with order or direction: rtl.
2. Add a second split section with the image on the left.
3. Use a background video instead of the image.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 772: Split-screen feature section for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 2 | Files: index.html, styles.css

Brief

Create a full-height section with text on one half and a photo filling the other half, stacking on small screens.

Learning goals

- Fill a grid cell with an image using object-fit
- Vertically centre content with align-content
- Use clamp() for fluid padding

Elements and CSS used

HTML elements	CSS features
main, div, p, h1, strong, ul, li, a, img	grid-template-columns: 1fr 1fr, object-fit: cover, align-content: center, clamp(), ::before content

Build guide

1. Write the text block and the image as the two children of .split.
2. Grid with one column by default, two above 800px.
3. Give the image height 100% and object-fit: cover.
4. Centre the text vertically with align-content.
5. Add tick marks to the list with ::before.
6. Use clamp() for padding.

Project 772: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - Story hour</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="split">
    <div class="text">
      <p class="kicker">Programme of the month</p>
      <h1>Story hour</h1>
      <p>Ages 3 to 6, Saturdays. Available now at Delta Kids Library
in Tanta for <strong>Free</strong>.</p>
      <ul class="ticks">
        <li>Made with care</li>
        <li>Satisfaction guaranteed</li>
        <li>Ask us anything</li>
      </ul>
      <a class="btn" href="contact.html">Ask about it</a>
    </div>
    <img src="images/library-1.jpg" alt="Story hour" width="900"
height="900">
  </main>
</body>
</html>
```

Project 772: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.split { min-height: 100vh; display: grid; grid-template-columns: 1fr;
 }
.text { padding: clamp(1.5rem, 5vw, 4rem); display: grid; align-
content: center; gap: 1rem; }
img { width: 100%; height: 100%; object-fit: cover; }
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr;
} }
.kicker { text-transform: uppercase; letter-spacing: .1em; color: var(
--brand); font-weight: 700; margin: 0; }
h1 { margin: 0; font-size: clamp(2rem, 4vw, 3rem); }
.ticks { list-style: none; padding: 0; margin: 0; }
.ticks li::before { content: "\2713 "; color: var(--brand); font-
```

```
weight: 700; }
.btn { justify-self: start; padding: .8rem 1.6rem; background: var(--
brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 772 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - Story hour</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="split">	The unique content of this page; exactly one per page.
	Generic block container for grouping and layout.
Programme of the month	A paragraph of text.
Story hour	The main heading; only one per page.
Ages 3 to 6, Saturdays. Available now at Delta Kids Library in T...	Strong importance (bold by default).
<ul class="ticks">	Unordered (bulleted) list.
Made with care	One list item.

Line	What it does
Ask about it	A link styled as a button; it navigates, so it is a link and not a <button>.
<img src="images/library-1.jpg" alt="Story hour" width="900" height...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
padding: clamp(1.5rem, 5vw, 4rem);	Space inside the element between its border and content.

Declaration	What it does
align-content: center;	Centres the lines of a multi-line flex or grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
width: 100%;	Fills the container width.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr...	Applies from the given width upwards (mobile-first breakpoint).
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .1em;	Adds space between letters; useful for small capitals.
font-weight: 700;	Thickness of the text.
font-size: clamp(2rem, 4vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
list-style: none;	Removes bullets or numbers from a list.
content: "\2713 ";	The text or empty string for a pseudo-element.
background: var(--brand);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Image never distorts
- Text stays readable width
- Stacks on mobile with image below

- Button aligned left, not stretched

Exercises

1. Swap the sides with order or direction: rtl.
2. Add a second split section with the image on the left.
3. Use a background video instead of the image.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 773: Split-screen feature section for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Create a full-height section with text on one half and a photo filling the other half, stacking on small screens.

Learning goals

- Fill a grid cell with an image using object-fit
- Vertically centre content with align-content
- Use clamp() for fluid padding

Elements and CSS used

HTML elements	CSS features
main, div, p, h1, strong, ul, li, a, img	grid-template-columns: 1fr 1fr, object-fit: cover, align-content: center, clamp(), ::before content

Build guide

1. Write the text block and the image as the two children of .split.
2. Grid with one column by default, two above 800px.
3. Give the image height 100% and object-fit: cover.
4. Centre the text vertically with align-content.
5. Add tick marks to the list with ::before.
6. Use clamp() for padding.

Project 773: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - Garden room</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="split">
    <div class="text">
      <p class="kicker">Room of the month</p>
      <h1>Garden room</h1>
      <p>Double bed, shared terrace. Available now at Nubian Guest
House in Aswan for <strong>900 EGP</strong>.</p>
      <ul class="ticks">
        <li>Made with care</li>
        <li>Satisfaction guaranteed</li>
        <li>Ask us anything</li>
      </ul>
      <a class="btn" href="contact.html">Ask about it</a>
    </div>
    <img src="images/guesthouse-1.jpg" alt="Garden room" width="900"
height="900">
  </main>
</body>
</html>
```

Project 773: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.split { min-height: 100vh; display: grid; grid-template-columns: 1fr;
 }
.text { padding: clamp(1.5rem, 5vw, 4rem); display: grid; align-
content: center; gap: 1rem; }
img { width: 100%; height: 100%; object-fit: cover; }
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr;
} }
.kicker { text-transform: uppercase; letter-spacing: .1em; color: var(
--brand); font-weight: 700; margin: 0; }
h1 { margin: 0; font-size: clamp(2rem, 4vw, 3rem); }
.ticks { list-style: none; padding: 0; margin: 0; }
.ticks li::before { content: "\2713 "; color: var(--brand); font-
```

```
weight: 700; }
.btn { justify-self: start; padding: .8rem 1.6rem; background: var(--
brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 773 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - Garden room</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="split">	The unique content of this page; exactly one per page.
	Generic block container for grouping and layout.
Room of the month	A paragraph of text.
Garden room	The main heading; only one per page.
Double bed, shared terrace. Available now at Nubian Guest House ...	Strong importance (bold by default).
<ul class="ticks">	Unordered (bulleted) list.
Made with care	One list item.
Ask about it	A link styled as a button; it navigates, so it is a link and not a <button>.

Line	What it does
<img src="images/guesthouse-1.jpg" alt="Garden room" width="900" he...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
padding: clamp(1.5rem, 5vw, 4rem);	Space inside the element between its border and content.
align-content: center;	Centres the lines of a multi-line flex or grid container.

Declaration	What it does
gap: 1rem;	Space between grid or flex items without extra margins.
width: 100%;	Fills the container width.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr...	Applies from the given width upwards (mobile-first breakpoint).
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .1em;	Adds space between letters; useful for small capitals.
font-weight: 700;	Thickness of the text.
font-size: clamp(2rem, 4vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
list-style: none;	Removes bullets or numbers from a list.
content: "\2713 ";	The text or empty string for a pseudo-element.
background: var(--brand);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Image never distorts
- Text stays readable width
- Stacks on mobile with image below
- Button aligned left, not stretched

Exercises

1. Swap the sides with order or direction: rtl.
2. Add a second split section with the image on the left.
3. Use a background video instead of the image.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 774: Split-screen feature section for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 2 | Files: index.html, styles.css

Brief

Create a full-height section with text on one half and a photo filling the other half, stacking on small screens.

Learning goals

- Fill a grid cell with an image using object-fit
- Vertically centre content with align-content
- Use clamp() for fluid padding

Elements and CSS used

HTML elements	CSS features
main, div, p, h1, strong, ul, li, a, img	grid-template-columns: 1fr 1fr, object-fit: cover, align-content: center, clamp(), ::before content

Build guide

1. Write the text block and the image as the two children of .split.
2. Grid with one column by default, two above 800px.
3. Give the image height 100% and object-fit: cover.
4. Centre the text vertically with align-content.
5. Add tick marks to the list with ::before.
6. Use clamp() for padding.

Project 774: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - City bike</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="split">
    <div class="text">
      <p class="kicker">Bike of the month</p>
      <h1>City bike</h1>
      <p>Seven gears, basket. Available now at Ismailia Cycling Store
in Ismailia for <strong>6500 EGP</strong>.</p>
      <ul class="ticks">
        <li>Made with care</li>
        <li>Satisfaction guaranteed</li>
        <li>Ask us anything</li>
      </ul>
      <a class="btn" href="contact.html">Ask about it</a>
    </div>
    <img src="images/cycling-1.jpg" alt="City bike" width="900"
height="900">
  </main>
</body>
</html>
```

Project 774: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.split { min-height: 100vh; display: grid; grid-template-columns: 1fr;
 }
.text { padding: clamp(1.5rem, 5vw, 4rem); display: grid; align-
content: center; gap: 1rem; }
img { width: 100%; height: 100%; object-fit: cover; }
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr;
} }
.kicker { text-transform: uppercase; letter-spacing: .1em; color: var(
--brand); font-weight: 700; margin: 0; }
h1 { margin: 0; font-size: clamp(2rem, 4vw, 3rem); }
.ticks { list-style: none; padding: 0; margin: 0; }
.ticks li::before { content: "\2713 "; color: var(--brand); font-
```

```
weight: 700; }
.btn { justify-self: start; padding: .8rem 1.6rem; background: var(--
brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 774 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - City bike</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="split">	The unique content of this page; exactly one per page.
	Generic block container for grouping and layout.
Bike of the month	A paragraph of text.
City bike	The main heading; only one per page.
Seven gears, basket. Available now at Ismailia Cycling Store in ...	Strong importance (bold by default).
<ul class="ticks">	Unordered (bulleted) list.
Made with care	One list item.
Ask about it	A link styled as a button; it navigates, so it is a link and not a <button>.

Line	What it does
<img src="images/cycling-1.jpg" alt="City bike" width="900" height=...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
padding: clamp(1.5rem, 5vw, 4rem);	Space inside the element between its border and content.
align-content: center;	Centres the lines of a multi-line flex or grid container.

Declaration	What it does
gap: 1rem;	Space between grid or flex items without extra margins.
width: 100%;	Fills the container width.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr...	Applies from the given width upwards (mobile-first breakpoint).
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .1em;	Adds space between letters; useful for small capitals.
font-weight: 700;	Thickness of the text.
font-size: clamp(2rem, 4vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
list-style: none;	Removes bullets or numbers from a list.
content: "\2713 ";	The text or empty string for a pseudo-element.
background: var(--brand);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Image never distorts
- Text stays readable width
- Stacks on mobile with image below
- Button aligned left, not stretched

Exercises

1. Swap the sides with order or direction: rtl.
2. Add a second split section with the image on the left.
3. Use a background video instead of the image.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 775: Split-screen feature section for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 2 | Files: index.html, styles.css

Brief

Create a full-height section with text on one half and a photo filling the other half, stacking on small screens.

Learning goals

- Fill a grid cell with an image using object-fit
- Vertically centre content with align-content
- Use clamp() for fluid padding

Elements and CSS used

HTML elements	CSS features
main, div, p, h1, strong, ul, li, a, img	grid-template-columns: 1fr 1fr, object-fit: cover, align-content: center, clamp(), ::before content

Build guide

1. Write the text block and the image as the two children of .split.
2. Grid with one column by default, two above 800px.
3. Give the image height 100% and object-fit: cover.
4. Centre the text vertically with align-content.
5. Add tick marks to the list with ::before.
6. Use clamp() for padding.

Project 775: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - HTML weekend</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main class="split">
    <div class="text">
      <p class="kicker">Workshop of the month</p>
      <h1>HTML weekend</h1>
      <p>Build your first page. Available now at Minya Coding Club in
Minya for <strong>Free</strong>.</p>
      <ul class="ticks">
        <li>Made with care</li>
        <li>Satisfaction guaranteed</li>
        <li>Ask us anything</li>
      </ul>
      <a class="btn" href="contact.html">Ask about it</a>
    </div>
    <img src="images/coding-1.jpg" alt="HTML weekend" width="900"
height="900">
  </main>
</body>
</html>
```

Project 775: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.split { min-height: 100vh; display: grid; grid-template-columns: 1fr;
 }
.text { padding: clamp(1.5rem, 5vw, 4rem); display: grid; align-
content: center; gap: 1rem; }
img { width: 100%; height: 100%; object-fit: cover; }
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr;
} }
.kicker { text-transform: uppercase; letter-spacing: .1em; color: var(
--brand); font-weight: 700; margin: 0; }
h1 { margin: 0; font-size: clamp(2rem, 4vw, 3rem); }
.ticks { list-style: none; padding: 0; margin: 0; }
.ticks li::before { content: "\2713 "; color: var(--brand); font-
```

```
weight: 700; }
.btn { justify-self: start; padding: .8rem 1.6rem; background: var(--
brand); color: #fff; border-radius: 999px; text-decoration: none; }
```

Project 775 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - HTML weekend</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main class="split">	The unique content of this page; exactly one per page.
	Generic block container for grouping and layout.
Workshop of the month	A paragraph of text.
HTML weekend	The main heading; only one per page.
Build your first page. Available now at Minya Coding Club in Min...	Strong importance (bold by default).
<ul class="ticks">	Unordered (bulleted) list.
Made with care	One list item.
Ask about it	A link styled as a button; it navigates, so it is a link and not a <button>.

Line	What it does
<img src="images/coding-1.jpg" alt="HTML weekend" width="900" heigh...	An image; alt describes it, width and height reserve space before it loads.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
min-height: 100vh;	At least as tall as the viewport.
display: grid;	Turns the element into a grid container.
grid-template-columns: 1fr;	Defines the columns of the grid.
padding: clamp(1.5rem, 5vw, 4rem);	Space inside the element between its border and content.
align-content: center;	Centres the lines of a multi-line flex or grid container.

Declaration	What it does
gap: 1rem;	Space between grid or flex items without extra margins.
width: 100%;	Fills the container width.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
@media (min-width: 800px) { .split { grid-template-columns: 1fr 1fr...	Applies from the given width upwards (mobile-first breakpoint).
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .1em;	Adds space between letters; useful for small capitals.
font-weight: 700;	Thickness of the text.
font-size: clamp(2rem, 4vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
list-style: none;	Removes bullets or numbers from a list.
content: "\2713 ";	The text or empty string for a pseudo-element.
background: var(--brand);	Background colour or image.
border-radius: 999px;	Fully rounded pill shape.
text-decoration: none;	Removes the underline from links.

Check your work

- Image never distorts
- Text stays readable width
- Stacks on mobile with image below
- Button aligned left, not stretched

Exercises

1. Swap the sides with order or direction: rtl.
2. Add a second split section with the image on the left.
3. Use a background video instead of the image.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Statistics strip

Level 1 | 25 projects, one per theme

Show four key numbers in coloured tiles where the big number appears above its label, using flex-direction: column-reverse on a dl.

Project 776: Statistics strip for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 1 | Files: index.html, styles.css

Brief

Show four key numbers in coloured tiles where the big number appears above its label, using flex-direction: column-reverse on a dl.

Learning goals

- Use dl for label/value pairs
- Reverse visual order without changing source order
- Size big numbers with line-height 1

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd	flex-direction: column-reverse, grid auto-fit, font-weight: 800, line-height: 1, opacity

Build guide

1. Write the dl with a div per pair.
2. Grid the dl.
3. Make each div a flex column-reverse so the number shows first.
4. Style dd large and bold.
5. Colour the tiles.
6. Check the reading order in a screen reader stays label then value.

Project 776: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - In numbers</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cairo Book Shop in numbers</h1>
    <dl class="numbers">
      <div><dt>Years open</dt><dd>8</dd></div>
      <div><dt>Happy customers</dt><dd>12,000+</dd></div>
      <div><dt>Books</dt><dd>4</dd></div>
      <div><dt>Average rating</dt><dd>4.8</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 776: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 3rem auto; padding: 0 1rem; text-
align: center; }
.numbers { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fit, minmax(10rem, 1fr)); margin: 0; }
.numbers div { background: var(--brand); color: #fff; padding: 1.5rem
1rem; border-radius: 14px; display: flex; flex-direction: column-
reverse; }
dd { margin: 0; font-size: 2.5rem; font-weight: 800; line-height: 1; }
dt { margin-top: .5rem; opacity: .9; }
```

Project 776 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - In numbers</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cairo Book Shop in numbers	The main heading; only one per page.
<dl class="numbers">	Description list of term / description pairs.
<dt>Years open</dt><dd>8</dd>	A term (name) in a description list.
<dt>Happy customers</dt><dd>12,000+</dd>	The description of the preceding term.
<dt>Books</dt><dd>4</dd>	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(10rem, 1fr));	Defines the columns of the grid.
background: var(--brand);	Background colour or image.
border-radius: 14px;	Rounds the corners.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-direction: column-reverse;	Stacks flex items vertically.
font-size: 2.5rem;	Size of the text.
font-weight: 800;	Thickness of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).

Check your work

- dt before dd in source
- Numbers visually above labels
- Tiles equal height
- White text contrast on brand colour

Exercises

1. Animate the numbers counting up with JavaScript.
2. Add small icons.
3. Add a subtle gradient to the tiles.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 777: Statistics strip for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 1 | Files: index.html, styles.css

Brief

Show four key numbers in coloured tiles where the big number appears above its label, using flex-direction: column-reverse on a dl.

Learning goals

- Use dl for label/value pairs
- Reverse visual order without changing source order
- Size big numbers with line-height 1

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd	flex-direction: column-reverse, grid auto-fit, font-weight: 800, line-height: 1, opacity

Build guide

1. Write the dl with a div per pair.
2. Grid the dl.
3. Make each div a flex column-reverse so the number shows first.
4. Style dd large and bold.
5. Colour the tiles.
6. Check the reading order in a screen reader stays label then value.

Project 777: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - In numbers</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Nile Bakery in numbers</h1>
    <dl class="numbers">
      <div><dt>Years open</dt><dd>8</dd></div>
      <div><dt>Happy customers</dt><dd>12,000+</dd></div>
      <div><dt>Pastries</dt><dd>4</dd></div>
      <div><dt>Average rating</dt><dd>4.8</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 777: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 3rem auto; padding: 0 1rem; text-
align: center; }
.numbers { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fit, minmax(10rem, 1fr)); margin: 0; }
.numbers div { background: var(--brand); color: #fff; padding: 1.5rem
1rem; border-radius: 14px; display: flex; flex-direction: column-
reverse; }
dd { margin: 0; font-size: 2.5rem; font-weight: 800; line-height: 1; }
dt { margin-top: .5rem; opacity: .9; }
```

Project 777 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - In numbers</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Nile Bakery in numbers	The main heading; only one per page.
<dl class="numbers">	Description list of term / description pairs.
<dt>Years open</dt><dd>8</dd>	A term (name) in a description list.
<dt>Happy customers</dt><dd>12,000+</dd>	The description of the preceding term.
<dt>Pastries</dt><dd>4</dd>	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(10rem, 1fr));	Defines the columns of the grid.
background: var(--brand);	Background colour or image.
border-radius: 14px;	Rounds the corners.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-direction: column-reverse;	Stacks flex items vertically.
font-size: 2.5rem;	Size of the text.
font-weight: 800;	Thickness of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).

Check your work

- dt before dd in source
- Numbers visually above labels
- Tiles equal height
- White text contrast on brand colour

Exercises

1. Animate the numbers counting up with JavaScript.
2. Add small icons.
3. Add a subtle gradient to the tiles.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 778: Statistics strip for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 1 | Files: index.html, styles.css

Brief

Show four key numbers in coloured tiles where the big number appears above its label, using flex-direction: column-reverse on a dl.

Learning goals

- Use dl for label/value pairs
- Reverse visual order without changing source order
- Size big numbers with line-height 1

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd	flex-direction: column-reverse, grid auto-fit, font-weight: 800, line-height: 1, opacity

Build guide

1. Write the dl with a div per pair.
2. Grid the dl.
3. Make each div a flex column-reverse so the number shows first.
4. Style dd large and bold.
5. Colour the tiles.
6. Check the reading order in a screen reader stays label then value.

Project 778: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - In numbers</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Pyramid Fitness in numbers</h1>
    <dl class="numbers">
      <div><dt>Years open</dt><dd>8</dd></div>
      <div><dt>Happy customers</dt><dd>12,000+</dd></div>
      <div><dt>Classes</dt><dd>4</dd></div>
      <div><dt>Average rating</dt><dd>4.8</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 778: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 3rem auto; padding: 0 1rem; text-
align: center; }
.numbers { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fit, minmax(10rem, 1fr)); margin: 0; }
.numbers div { background: var(--brand); color: #fff; padding: 1.5rem
1rem; border-radius: 14px; display: flex; flex-direction: column-
reverse; }
dd { margin: 0; font-size: 2.5rem; font-weight: 800; line-height: 1; }
dt { margin-top: .5rem; opacity: .9; }
```

Project 778 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - In numbers</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Pyramid Fitness in numbers	The main heading; only one per page.
<dl class="numbers">	Description list of term / description pairs.
<dt>Years open</dt><dd>8</dd>	A term (name) in a description list.
<dt>Happy customers</dt><dd>12,000+</dd>	The description of the preceding term.
<dt>Classes</dt><dd>4</dd>	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(10rem, 1fr));	Defines the columns of the grid.
background: var(--brand);	Background colour or image.
border-radius: 14px;	Rounds the corners.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-direction: column-reverse;	Stacks flex items vertically.
font-size: 2.5rem;	Size of the text.
font-weight: 800;	Thickness of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).

Check your work

- dt before dd in source
- Numbers visually above labels
- Tiles equal height
- White text contrast on brand colour

Exercises

1. Animate the numbers counting up with JavaScript.
2. Add small icons.
3. Add a subtle gradient to the tiles.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 779: Statistics strip for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 1 | Files: index.html, styles.css

Brief

Show four key numbers in coloured tiles where the big number appears above its label, using flex-direction: column-reverse on a dl.

Learning goals

- Use dl for label/value pairs
- Reverse visual order without changing source order
- Size big numbers with line-height 1

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd	flex-direction: column-reverse, grid auto-fit, font-weight: 800, line-height: 1, opacity

Build guide

1. Write the dl with a div per pair.
2. Grid the dl.
3. Make each div a flex column-reverse so the number shows first.
4. Style dd large and bold.
5. Colour the tiles.
6. Check the reading order in a screen reader stays label then value.

Project 779: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - In numbers</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Delta Dental Clinic in numbers</h1>
    <dl class="numbers">
      <div><dt>Years open</dt><dd>8</dd></div>
      <div><dt>Happy customers</dt><dd>12,000+</dd></div>
      <div><dt>Services</dt><dd>4</dd></div>
      <div><dt>Average rating</dt><dd>4.8</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 779: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 3rem auto; padding: 0 1rem; text-
align: center; }
.numbers { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fit, minmax(10rem, 1fr)); margin: 0; }
.numbers div { background: var(--brand); color: #fff; padding: 1.5rem
1rem; border-radius: 14px; display: flex; flex-direction: column-
reverse; }
dd { margin: 0; font-size: 2.5rem; font-weight: 800; line-height: 1; }
dt { margin-top: .5rem; opacity: .9; }
```

Project 779 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - In numbers</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Delta Dental Clinic in numbers	The main heading; only one per page.
<dl class="numbers">	Description list of term / description pairs.
<dt>Years open</dt><dd>8</dd>	A term (name) in a description list.
<dt>Happy customers</dt><dd>12,000+</dd>	The description of the preceding term.
<dt>Services</dt><dd>4</dd>	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(10rem, 1fr));	Defines the columns of the grid.
background: var(--brand);	Background colour or image.
border-radius: 14px;	Rounds the corners.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-direction: column-reverse;	Stacks flex items vertically.
font-size: 2.5rem;	Size of the text.
font-weight: 800;	Thickness of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).

Check your work

- dt before dd in source
- Numbers visually above labels
- Tiles equal height
- White text contrast on brand colour

Exercises

1. Animate the numbers counting up with JavaScript.
2. Add small icons.
3. Add a subtle gradient to the tiles.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 780: Statistics strip for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 1 | Files: index.html, styles.css

Brief

Show four key numbers in coloured tiles where the big number appears above its label, using flex-direction: column-reverse on a dl.

Learning goals

- Use dl for label/value pairs
- Reverse visual order without changing source order
- Size big numbers with line-height 1

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd	flex-direction: column-reverse, grid auto-fit, font-weight: 800, line-height: 1, opacity

Build guide

1. Write the dl with a div per pair.
2. Grid the dl.
3. Make each div a flex column-reverse so the number shows first.
4. Style dd large and bold.
5. Colour the tiles.
6. Check the reading order in a screen reader stays label then value.

Project 780: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - In numbers</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Red Sea Travel in numbers</h1>
    <dl class="numbers">
      <div><dt>Years open</dt><dd>8</dd></div>
      <div><dt>Happy customers</dt><dd>12,000+</dd></div>
      <div><dt>Tours</dt><dd>4</dd></div>
      <div><dt>Average rating</dt><dd>4.8</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 780: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 3rem auto; padding: 0 1rem; text-
align: center; }
.numbers { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fit, minmax(10rem, 1fr)); margin: 0; }
.numbers div { background: var(--brand); color: #fff; padding: 1.5rem
1rem; border-radius: 14px; display: flex; flex-direction: column-
reverse; }
dd { margin: 0; font-size: 2.5rem; font-weight: 800; line-height: 1; }
dt { margin-top: .5rem; opacity: .9; }
```

Project 780 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - In numbers</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Red Sea Travel in numbers	The main heading; only one per page.
<dl class="numbers">	Description list of term / description pairs.
<dt>Years open</dt><dd>8</dd>	A term (name) in a description list.
<dt>Happy customers</dt><dd>12,000+</dd>	The description of the preceding term.
<dt>Tours</dt><dd>4</dd>	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(10rem, 1fr));	Defines the columns of the grid.
background: var(--brand);	Background colour or image.
border-radius: 14px;	Rounds the corners.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-direction: column-reverse;	Stacks flex items vertically.
font-size: 2.5rem;	Size of the text.
font-weight: 800;	Thickness of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).

Check your work

- dt before dd in source
- Numbers visually above labels
- Tiles equal height
- White text contrast on brand colour

Exercises

1. Animate the numbers counting up with JavaScript.
2. Add small icons.
3. Add a subtle gradient to the tiles.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 781: Statistics strip for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Show four key numbers in coloured tiles where the big number appears above its label, using flex-direction: column-reverse on a dl.

Learning goals

- Use dl for label/value pairs
- Reverse visual order without changing source order
- Size big numbers with line-height 1

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd	flex-direction: column-reverse, grid auto-fit, font-weight: 800, line-height: 1, opacity

Build guide

1. Write the dl with a div per pair.
2. Grid the dl.
3. Make each div a flex column-reverse so the number shows first.
4. Style dd large and bold.
5. Colour the tiles.
6. Check the reading order in a screen reader stays label then value.

Project 781: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - In numbers</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Lotus Language School in numbers</h1>
    <dl class="numbers">
      <div><dt>Years open</dt><dd>8</dd></div>
      <div><dt>Happy customers</dt><dd>12,000+</dd></div>
      <div><dt>Courses</dt><dd>4</dd></div>
      <div><dt>Average rating</dt><dd>4.8</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 781: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 3rem auto; padding: 0 1rem; text-
align: center; }
.numbers { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fit, minmax(10rem, 1fr)); margin: 0; }
.numbers div { background: var(--brand); color: #fff; padding: 1.5rem
1rem; border-radius: 14px; display: flex; flex-direction: column-
reverse; }
dd { margin: 0; font-size: 2.5rem; font-weight: 800; line-height: 1; }
dt { margin-top: .5rem; opacity: .9; }
```

Project 781 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - In numbers</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Lotus Language School in numbers	The main heading; only one per page.
<dl class="numbers">	Description list of term / description pairs.
<dt>Years open</dt><dd>8</dd>	A term (name) in a description list.
<dt>Happy customers</dt><dd>12,000+</dd>	The description of the preceding term.
<dt>Courses</dt><dd>4</dd>	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(10rem, 1fr));	Defines the columns of the grid.
background: var(--brand);	Background colour or image.
border-radius: 14px;	Rounds the corners.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-direction: column-reverse;	Stacks flex items vertically.
font-size: 2.5rem;	Size of the text.
font-weight: 800;	Thickness of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).

Check your work

- dt before dd in source
- Numbers visually above labels
- Tiles equal height
- White text contrast on brand colour

Exercises

1. Animate the numbers counting up with JavaScript.
2. Add small icons.
3. Add a subtle gradient to the tiles.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 782: Statistics strip for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 1 | Files: index.html, styles.css

Brief

Show four key numbers in coloured tiles where the big number appears above its label, using flex-direction: column-reverse on a dl.

Learning goals

- Use dl for label/value pairs
- Reverse visual order without changing source order
- Size big numbers with line-height 1

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd	flex-direction: column-reverse, grid auto-fit, font-weight: 800, line-height: 1, opacity

Build guide

1. Write the dl with a div per pair.
2. Grid the dl.
3. Make each div a flex column-reverse so the number shows first.
4. Style dd large and bold.
5. Colour the tiles.
6. Check the reading order in a screen reader stays label then value.

Project 782: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - In numbers</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Green Leaf Cafe in numbers</h1>
    <dl class="numbers">
      <div><dt>Years open</dt><dd>8</dd></div>
      <div><dt>Happy customers</dt><dd>12,000+</dd></div>
      <div><dt>Drinks</dt><dd>4</dd></div>
      <div><dt>Average rating</dt><dd>4.8</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 782: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 3rem auto; padding: 0 1rem; text-
align: center; }
.numbers { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fit, minmax(10rem, 1fr)); margin: 0; }
.numbers div { background: var(--brand); color: #fff; padding: 1.5rem
1rem; border-radius: 14px; display: flex; flex-direction: column-
reverse; }
dd { margin: 0; font-size: 2.5rem; font-weight: 800; line-height: 1; }
dt { margin-top: .5rem; opacity: .9; }
```

Project 782 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - In numbers</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Green Leaf Cafe in numbers	The main heading; only one per page.
<dl class="numbers">	Description list of term / description pairs.
<dt>Years open</dt><dd>8</dd>	A term (name) in a description list.
<dt>Happy customers</dt><dd>12,000+</dd>	The description of the preceding term.
<dt>Drinks</dt><dd>4</dd>	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(10rem, 1fr));	Defines the columns of the grid.
background: var(--brand);	Background colour or image.
border-radius: 14px;	Rounds the corners.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-direction: column-reverse;	Stacks flex items vertically.
font-size: 2.5rem;	Size of the text.
font-weight: 800;	Thickness of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).

Check your work

- dt before dd in source
- Numbers visually above labels
- Tiles equal height
- White text contrast on brand colour

Exercises

1. Animate the numbers counting up with JavaScript.
2. Add small icons.
3. Add a subtle gradient to the tiles.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 783: Statistics strip for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 1 | Files: index.html, styles.css

Brief

Show four key numbers in coloured tiles where the big number appears above its label, using flex-direction: column-reverse on a dl.

Learning goals

- Use dl for label/value pairs
- Reverse visual order without changing source order
- Size big numbers with line-height 1

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd	flex-direction: column-reverse, grid auto-fit, font-weight: 800, line-height: 1, opacity

Build guide

1. Write the dl with a div per pair.
2. Grid the dl.
3. Make each div a flex column-reverse so the number shows first.
4. Style dd large and bold.
5. Colour the tiles.
6. Check the reading order in a screen reader stays label then value.

Project 783: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - In numbers</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Sinai Trekking Club in numbers</h1>
    <dl class="numbers">
      <div><dt>Years open</dt><dd>8</dd></div>
      <div><dt>Happy customers</dt><dd>12,000+</dd></div>
      <div><dt>Hikes</dt><dd>4</dd></div>
      <div><dt>Average rating</dt><dd>4.8</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 783: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 3rem auto; padding: 0 1rem; text-
align: center; }
.numbers { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fit, minmax(10rem, 1fr)); margin: 0; }
.numbers div { background: var(--brand); color: #fff; padding: 1.5rem
1rem; border-radius: 14px; display: flex; flex-direction: column-
reverse; }
dd { margin: 0; font-size: 2.5rem; font-weight: 800; line-height: 1; }
dt { margin-top: .5rem; opacity: .9; }
```

Project 783 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - In numbers</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Sinai Trekking Club in numbers	The main heading; only one per page.
<dl class="numbers">	Description list of term / description pairs.
<dt>Years open</dt><dd>8</dd>	A term (name) in a description list.
<dt>Happy customers</dt><dd>12,000+</dd>	The description of the preceding term.
<dt>Hikes</dt><dd>4</dd>	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(10rem, 1fr));	Defines the columns of the grid.
background: var(--brand);	Background colour or image.
border-radius: 14px;	Rounds the corners.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-direction: column-reverse;	Stacks flex items vertically.
font-size: 2.5rem;	Size of the text.
font-weight: 800;	Thickness of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).

Check your work

- dt before dd in source
- Numbers visually above labels
- Tiles equal height
- White text contrast on brand colour

Exercises

1. Animate the numbers counting up with JavaScript.
2. Add small icons.
3. Add a subtle gradient to the tiles.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 784: Statistics strip for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 1 | Files: index.html, styles.css

Brief

Show four key numbers in coloured tiles where the big number appears above its label, using flex-direction: column-reverse on a dl.

Learning goals

- Use dl for label/value pairs
- Reverse visual order without changing source order
- Size big numbers with line-height 1

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd	flex-direction: column-reverse, grid auto-fit, font-weight: 800, line-height: 1, opacity

Build guide

1. Write the dl with a div per pair.
2. Grid the dl.
3. Make each div a flex column-reverse so the number shows first.
4. Style dd large and bold.
5. Colour the tiles.
6. Check the reading order in a screen reader stays label then value.

Project 784: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - In numbers</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Horizon Photography in numbers</h1>
    <dl class="numbers">
      <div><dt>Years open</dt><dd>8</dd></div>
      <div><dt>Happy customers</dt><dd>12,000+</dd></div>
      <div><dt>Sessions</dt><dd>4</dd></div>
      <div><dt>Average rating</dt><dd>4.8</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 784: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 3rem auto; padding: 0 1rem; text-
align: center; }
.numbers { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fit, minmax(10rem, 1fr)); margin: 0; }
.numbers div { background: var(--brand); color: #fff; padding: 1.5rem
1rem; border-radius: 14px; display: flex; flex-direction: column-
reverse; }
dd { margin: 0; font-size: 2.5rem; font-weight: 800; line-height: 1; }
dt { margin-top: .5rem; opacity: .9; }
```

Project 784 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - In numbers</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Horizon Photography in numbers	The main heading; only one per page.
<dl class="numbers">	Description list of term / description pairs.
<dt>Years open</dt><dd>8</dd>	A term (name) in a description list.
<dt>Happy customers</dt><dd>12,000+</dd>	The description of the preceding term.
<dt>Sessions</dt><dd>4</dd>	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(10rem, 1fr));	Defines the columns of the grid.
background: var(--brand);	Background colour or image.
border-radius: 14px;	Rounds the corners.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-direction: column-reverse;	Stacks flex items vertically.
font-size: 2.5rem;	Size of the text.
font-weight: 800;	Thickness of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).

Check your work

- dt before dd in source
- Numbers visually above labels
- Tiles equal height
- White text contrast on brand colour

Exercises

1. Animate the numbers counting up with JavaScript.
2. Add small icons.
3. Add a subtle gradient to the tiles.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 785: Statistics strip for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 1 | Files: index.html, styles.css

Brief

Show four key numbers in coloured tiles where the big number appears above its label, using flex-direction: column-reverse on a dl.

Learning goals

- Use dl for label/value pairs
- Reverse visual order without changing source order
- Size big numbers with line-height 1

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd	flex-direction: column-reverse, grid auto-fit, font-weight: 800, line-height: 1, opacity

Build guide

1. Write the dl with a div per pair.
2. Grid the dl.
3. Make each div a flex column-reverse so the number shows first.
4. Style dd large and bold.
5. Colour the tiles.
6. Check the reading order in a screen reader stays label then value.

Project 785: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - In numbers</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Papyrus Stationery in numbers</h1>
    <dl class="numbers">
      <div><dt>Years open</dt><dd>8</dd></div>
      <div><dt>Happy customers</dt><dd>12,000+</dd></div>
      <div><dt>Products</dt><dd>4</dd></div>
      <div><dt>Average rating</dt><dd>4.8</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 785: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 3rem auto; padding: 0 1rem; text-
align: center; }
.numbers { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fit, minmax(10rem, 1fr)); margin: 0; }
.numbers div { background: var(--brand); color: #fff; padding: 1.5rem
1rem; border-radius: 14px; display: flex; flex-direction: column-
reverse; }
dd { margin: 0; font-size: 2.5rem; font-weight: 800; line-height: 1; }
dt { margin-top: .5rem; opacity: .9; }
```

Project 785 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - In numbers</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Papyrus Stationery in numbers	The main heading; only one per page.
<dl class="numbers">	Description list of term / description pairs.
<dt>Years open</dt><dd>8</dd>	A term (name) in a description list.
<dt>Happy customers</dt><dd>12,000+</dd>	The description of the preceding term.
<dt>Products</dt><dd>4</dd>	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(10rem, 1fr));	Defines the columns of the grid.
background: var(--brand);	Background colour or image.
border-radius: 14px;	Rounds the corners.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-direction: column-reverse;	Stacks flex items vertically.
font-size: 2.5rem;	Size of the text.
font-weight: 800;	Thickness of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).

Check your work

- dt before dd in source
- Numbers visually above labels
- Tiles equal height
- White text contrast on brand colour

Exercises

1. Animate the numbers counting up with JavaScript.
2. Add small icons.
3. Add a subtle gradient to the tiles.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 786: Statistics strip for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 1 | Files: index.html, styles.css

Brief

Show four key numbers in coloured tiles where the big number appears above its label, using flex-direction: column-reverse on a dl.

Learning goals

- Use dl for label/value pairs
- Reverse visual order without changing source order
- Size big numbers with line-height 1

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd	flex-direction: column-reverse, grid auto-fit, font-weight: 800, line-height: 1, opacity

Build guide

1. Write the dl with a div per pair.
2. Grid the dl.
3. Make each div a flex column-reverse so the number shows first.
4. Style dd large and bold.
5. Colour the tiles.
6. Check the reading order in a screen reader stays label then value.

Project 786: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - In numbers</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Oasis Plant Nursery in numbers</h1>
    <dl class="numbers">
      <div><dt>Years open</dt><dd>8</dd></div>
      <div><dt>Happy customers</dt><dd>12,000+</dd></div>
      <div><dt>Plants</dt><dd>4</dd></div>
      <div><dt>Average rating</dt><dd>4.8</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 786: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 3rem auto; padding: 0 1rem; text-
align: center; }
.numbers { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fit, minmax(10rem, 1fr)); margin: 0; }
.numbers div { background: var(--brand); color: #fff; padding: 1.5rem
1rem; border-radius: 14px; display: flex; flex-direction: column-
reverse; }
dd { margin: 0; font-size: 2.5rem; font-weight: 800; line-height: 1; }
dt { margin-top: .5rem; opacity: .9; }
```

Project 786 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - In numbers</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Oasis Plant Nursery in numbers	The main heading; only one per page.
<dl class="numbers">	Description list of term / description pairs.
<dt>Years open</dt><dd>8</dd>	A term (name) in a description list.
<dt>Happy customers</dt><dd>12,000+</dd>	The description of the preceding term.
<dt>Plants</dt><dd>4</dd>	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(10rem, 1fr));	Defines the columns of the grid.
background: var(--brand);	Background colour or image.
border-radius: 14px;	Rounds the corners.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-direction: column-reverse;	Stacks flex items vertically.
font-size: 2.5rem;	Size of the text.
font-weight: 800;	Thickness of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).

Check your work

- dt before dd in source
- Numbers visually above labels
- Tiles equal height
- White text contrast on brand colour

Exercises

1. Animate the numbers counting up with JavaScript.
2. Add small icons.
3. Add a subtle gradient to the tiles.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 787: Statistics strip for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 1 | Files: index.html, styles.css

Brief

Show four key numbers in coloured tiles where the big number appears above its label, using flex-direction: column-reverse on a dl.

Learning goals

- Use dl for label/value pairs
- Reverse visual order without changing source order
- Size big numbers with line-height 1

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd	flex-direction: column-reverse, grid auto-fit, font-weight: 800, line-height: 1, opacity

Build guide

1. Write the dl with a div per pair.
2. Grid the dl.
3. Make each div a flex column-reverse so the number shows first.
4. Style dd large and bold.
5. Colour the tiles.
6. Check the reading order in a screen reader stays label then value.

Project 787: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - In numbers</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cedar Furniture in numbers</h1>
    <dl class="numbers">
      <div><dt>Years open</dt><dd>8</dd></div>
      <div><dt>Happy customers</dt><dd>12,000+</dd></div>
      <div><dt>Pieces</dt><dd>4</dd></div>
      <div><dt>Average rating</dt><dd>4.8</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 787: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 3rem auto; padding: 0 1rem; text-
align: center; }
.numbers { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fit, minmax(10rem, 1fr)); margin: 0; }
.numbers div { background: var(--brand); color: #fff; padding: 1.5rem
1rem; border-radius: 14px; display: flex; flex-direction: column-
reverse; }
dd { margin: 0; font-size: 2.5rem; font-weight: 800; line-height: 1; }
dt { margin-top: .5rem; opacity: .9; }
```

Project 787 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - In numbers</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cedar Furniture in numbers	The main heading; only one per page.
<dl class="numbers">	Description list of term / description pairs.
<dt>Years open</dt><dd>8</dd>	A term (name) in a description list.
<dt>Happy customers</dt><dd>12,000+</dd>	The description of the preceding term.
<dt>Pieces</dt><dd>4</dd>	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(10rem, 1fr));	Defines the columns of the grid.
background: var(--brand);	Background colour or image.
border-radius: 14px;	Rounds the corners.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-direction: column-reverse;	Stacks flex items vertically.
font-size: 2.5rem;	Size of the text.
font-weight: 800;	Thickness of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).

Check your work

- dt before dd in source
- Numbers visually above labels
- Tiles equal height
- White text contrast on brand colour

Exercises

1. Animate the numbers counting up with JavaScript.
2. Add small icons.
3. Add a subtle gradient to the tiles.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 788: Statistics strip for Byte Repair

Theme: Byte Repair (Nasr City) | Level 1 | Files: index.html, styles.css

Brief

Show four key numbers in coloured tiles where the big number appears above its label, using flex-direction: column-reverse on a dl.

Learning goals

- Use dl for label/value pairs
- Reverse visual order without changing source order
- Size big numbers with line-height 1

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd	flex-direction: column-reverse, grid auto-fit, font-weight: 800, line-height: 1, opacity

Build guide

1. Write the dl with a div per pair.
2. Grid the dl.
3. Make each div a flex column-reverse so the number shows first.
4. Style dd large and bold.
5. Colour the tiles.
6. Check the reading order in a screen reader stays label then value.

Project 788: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - In numbers</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Byte Repair in numbers</h1>
    <dl class="numbers">
      <div><dt>Years open</dt><dd>8</dd></div>
      <div><dt>Happy customers</dt><dd>12,000+</dd></div>
      <div><dt>Repairs</dt><dd>4</dd></div>
      <div><dt>Average rating</dt><dd>4.8</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 788: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 3rem auto; padding: 0 1rem; text-
align: center; }
.numbers { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fit, minmax(10rem, 1fr)); margin: 0; }
.numbers div { background: var(--brand); color: #fff; padding: 1.5rem
1rem; border-radius: 14px; display: flex; flex-direction: column-
reverse; }
dd { margin: 0; font-size: 2.5rem; font-weight: 800; line-height: 1; }
dt { margin-top: .5rem; opacity: .9; }
```

Project 788 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - In numbers</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Byte Repair in numbers	The main heading; only one per page.
<dl class="numbers">	Description list of term / description pairs.
<dt>Years open</dt><dd>8</dd>	A term (name) in a description list.
<dt>Happy customers</dt><dd>12,000+</dd>	The description of the preceding term.
<dt>Repairs</dt><dd>4</dd>	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(10rem, 1fr));	Defines the columns of the grid.
background: var(--brand);	Background colour or image.
border-radius: 14px;	Rounds the corners.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-direction: column-reverse;	Stacks flex items vertically.
font-size: 2.5rem;	Size of the text.
font-weight: 800;	Thickness of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).

Check your work

- dt before dd in source
- Numbers visually above labels
- Tiles equal height
- White text contrast on brand colour

Exercises

1. Animate the numbers counting up with JavaScript.
2. Add small icons.
3. Add a subtle gradient to the tiles.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 789: Statistics strip for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 1 | Files: index.html, styles.css

Brief

Show four key numbers in coloured tiles where the big number appears above its label, using flex-direction: column-reverse on a dl.

Learning goals

- Use dl for label/value pairs
- Reverse visual order without changing source order
- Size big numbers with line-height 1

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd	flex-direction: column-reverse, grid auto-fit, font-weight: 800, line-height: 1, opacity

Build guide

1. Write the dl with a div per pair.
2. Grid the dl.
3. Make each div a flex column-reverse so the number shows first.
4. Style dd large and bold.
5. Colour the tiles.
6. Check the reading order in a screen reader stays label then value.

Project 789: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - In numbers</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Sahara Pet Care in numbers</h1>
    <dl class="numbers">
      <div><dt>Years open</dt><dd>8</dd></div>
      <div><dt>Happy customers</dt><dd>12,000+</dd></div>
      <div><dt>Services</dt><dd>4</dd></div>
      <div><dt>Average rating</dt><dd>4.8</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 789: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 3rem auto; padding: 0 1rem; text-
align: center; }
.numbers { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fit, minmax(10rem, 1fr)); margin: 0; }
.numbers div { background: var(--brand); color: #fff; padding: 1.5rem
1rem; border-radius: 14px; display: flex; flex-direction: column-
reverse; }
dd { margin: 0; font-size: 2.5rem; font-weight: 800; line-height: 1; }
dt { margin-top: .5rem; opacity: .9; }
```

Project 789 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - In numbers</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Sahara Pet Care in numbers	The main heading; only one per page.
<dl class="numbers">	Description list of term / description pairs.
<dt>Years open</dt><dd>8</dd>	A term (name) in a description list.
<dt>Happy customers</dt><dd>12,000+</dd>	The description of the preceding term.
<dt>Services</dt><dd>4</dd>	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(10rem, 1fr));	Defines the columns of the grid.
background: var(--brand);	Background colour or image.
border-radius: 14px;	Rounds the corners.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-direction: column-reverse;	Stacks flex items vertically.
font-size: 2.5rem;	Size of the text.
font-weight: 800;	Thickness of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).

Check your work

- dt before dd in source
- Numbers visually above labels
- Tiles equal height
- White text contrast on brand colour

Exercises

1. Animate the numbers counting up with JavaScript.
2. Add small icons.
3. Add a subtle gradient to the tiles.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 790: Statistics strip for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Show four key numbers in coloured tiles where the big number appears above its label, using flex-direction: column-reverse on a dl.

Learning goals

- Use dl for label/value pairs
- Reverse visual order without changing source order
- Size big numbers with line-height 1

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd	flex-direction: column-reverse, grid auto-fit, font-weight: 800, line-height: 1, opacity

Build guide

1. Write the dl with a div per pair.
2. Grid the dl.
3. Make each div a flex column-reverse so the number shows first.
4. Style dd large and bold.
5. Colour the tiles.
6. Check the reading order in a screen reader stays label then value.

Project 790: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - In numbers</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Alexandria Sailing School in numbers</h1>
    <dl class="numbers">
      <div><dt>Years open</dt><dd>8</dd></div>
      <div><dt>Happy customers</dt><dd>12,000+</dd></div>
      <div><dt>Lessons</dt><dd>4</dd></div>
      <div><dt>Average rating</dt><dd>4.8</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 790: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 3rem auto; padding: 0 1rem; text-
align: center; }
.numbers { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fit, minmax(10rem, 1fr)); margin: 0; }
.numbers div { background: var(--brand); color: #fff; padding: 1.5rem
1rem; border-radius: 14px; display: flex; flex-direction: column-
reverse; }
dd { margin: 0; font-size: 2.5rem; font-weight: 800; line-height: 1; }
dt { margin-top: .5rem; opacity: .9; }
```

Project 790 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - In numbers</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Alexandria Sailing School in numbers	The main heading; only one per page.
<dl class="numbers">	Description list of term / description pairs.
<dt>Years open</dt><dd>8</dd>	A term (name) in a description list.
<dt>Happy customers</dt><dd>12,000+</dd>	The description of the preceding term.
<dt>Lessons</dt><dd>4</dd>	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(10rem, 1fr));	Defines the columns of the grid.
background: var(--brand);	Background colour or image.
border-radius: 14px;	Rounds the corners.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-direction: column-reverse;	Stacks flex items vertically.
font-size: 2.5rem;	Size of the text.
font-weight: 800;	Thickness of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).

Check your work

- dt before dd in source
- Numbers visually above labels
- Tiles equal height
- White text contrast on brand colour

Exercises

1. Animate the numbers counting up with JavaScript.
2. Add small icons.
3. Add a subtle gradient to the tiles.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 791: Statistics strip for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Show four key numbers in coloured tiles where the big number appears above its label, using flex-direction: column-reverse on a dl.

Learning goals

- Use dl for label/value pairs
- Reverse visual order without changing source order
- Size big numbers with line-height 1

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd	flex-direction: column-reverse, grid auto-fit, font-weight: 800, line-height: 1, opacity

Build guide

1. Write the dl with a div per pair.
2. Grid the dl.
3. Make each div a flex column-reverse so the number shows first.
4. Style dd large and bold.
5. Colour the tiles.
6. Check the reading order in a screen reader stays label then value.

Project 791: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - In numbers</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Habiba Handmade Jewellery in numbers</h1>
    <dl class="numbers">
      <div><dt>Years open</dt><dd>8</dd></div>
      <div><dt>Happy customers</dt><dd>12,000+</dd></div>
      <div><dt>Items</dt><dd>4</dd></div>
      <div><dt>Average rating</dt><dd>4.8</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 791: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 3rem auto; padding: 0 1rem; text-
align: center; }
.numbers { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fit, minmax(10rem, 1fr)); margin: 0; }
.numbers div { background: var(--brand); color: #fff; padding: 1.5rem
1rem; border-radius: 14px; display: flex; flex-direction: column-
reverse; }
dd { margin: 0; font-size: 2.5rem; font-weight: 800; line-height: 1; }
dt { margin-top: .5rem; opacity: .9; }
```

Project 791 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - In numbers</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Habiba Handmade Jewellery in numbers	The main heading; only one per page.
<dl class="numbers">	Description list of term / description pairs.
<dt>Years open</dt><dd>8</dd>	A term (name) in a description list.
<dt>Happy customers</dt><dd>12,000+</dd>	The description of the preceding term.
<dt>Items</dt><dd>4</dd>	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(10rem, 1fr));	Defines the columns of the grid.
background: var(--brand);	Background colour or image.
border-radius: 14px;	Rounds the corners.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-direction: column-reverse;	Stacks flex items vertically.
font-size: 2.5rem;	Size of the text.
font-weight: 800;	Thickness of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).

Check your work

- dt before dd in source
- Numbers visually above labels
- Tiles equal height
- White text contrast on brand colour

Exercises

1. Animate the numbers counting up with JavaScript.
2. Add small icons.
3. Add a subtle gradient to the tiles.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 792: Statistics strip for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 1 | Files: index.html, styles.css

Brief

Show four key numbers in coloured tiles where the big number appears above its label, using flex-direction: column-reverse on a dl.

Learning goals

- Use dl for label/value pairs
- Reverse visual order without changing source order
- Size big numbers with line-height 1

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd	flex-direction: column-reverse, grid auto-fit, font-weight: 800, line-height: 1, opacity

Build guide

1. Write the dl with a div per pair.
2. Grid the dl.
3. Make each div a flex column-reverse so the number shows first.
4. Style dd large and bold.
5. Colour the tiles.
6. Check the reading order in a screen reader stays label then value.

Project 792: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - In numbers</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Fayoum Pottery Studio in numbers</h1>
    <dl class="numbers">
      <div><dt>Years open</dt><dd>8</dd></div>
      <div><dt>Happy customers</dt><dd>12,000+</dd></div>
      <div><dt>Workshops</dt><dd>4</dd></div>
      <div><dt>Average rating</dt><dd>4.8</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 792: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 3rem auto; padding: 0 1rem; text-
align: center; }
.numbers { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fit, minmax(10rem, 1fr)); margin: 0; }
.numbers div { background: var(--brand); color: #fff; padding: 1.5rem
1rem; border-radius: 14px; display: flex; flex-direction: column-
reverse; }
dd { margin: 0; font-size: 2.5rem; font-weight: 800; line-height: 1; }
dt { margin-top: .5rem; opacity: .9; }
```

Project 792 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - In numbers</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Fayoum Pottery Studio in numbers	The main heading; only one per page.
<dl class="numbers">	Description list of term / description pairs.
<dt>Years open</dt><dd>8</dd>	A term (name) in a description list.
<dt>Happy customers</dt><dd>12,000+</dd>	The description of the preceding term.
<dt>Workshops</dt><dd>4</dd>	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(10rem, 1fr));	Defines the columns of the grid.
background: var(--brand);	Background colour or image.
border-radius: 14px;	Rounds the corners.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-direction: column-reverse;	Stacks flex items vertically.
font-size: 2.5rem;	Size of the text.
font-weight: 800;	Thickness of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).

Check your work

- dt before dd in source
- Numbers visually above labels
- Tiles equal height
- White text contrast on brand colour

Exercises

1. Animate the numbers counting up with JavaScript.
2. Add small icons.
3. Add a subtle gradient to the tiles.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 793: Statistics strip for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 1 | Files: index.html, styles.css

Brief

Show four key numbers in coloured tiles where the big number appears above its label, using flex-direction: column-reverse on a dl.

Learning goals

- Use dl for label/value pairs
- Reverse visual order without changing source order
- Size big numbers with line-height 1

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd	flex-direction: column-reverse, grid auto-fit, font-weight: 800, line-height: 1, opacity

Build guide

1. Write the dl with a div per pair.
2. Grid the dl.
3. Make each div a flex column-reverse so the number shows first.
4. Style dd large and bold.
5. Colour the tiles.
6. Check the reading order in a screen reader stays label then value.

Project 793: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - In numbers</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cleopatra Beauty Salon in numbers</h1>
    <dl class="numbers">
      <div><dt>Years open</dt><dd>8</dd></div>
      <div><dt>Happy customers</dt><dd>12,000+</dd></div>
      <div><dt>Treatments</dt><dd>4</dd></div>
      <div><dt>Average rating</dt><dd>4.8</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 793: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 3rem auto; padding: 0 1rem; text-
align: center; }
.numbers { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fit, minmax(10rem, 1fr)); margin: 0; }
.numbers div { background: var(--brand); color: #fff; padding: 1.5rem
1rem; border-radius: 14px; display: flex; flex-direction: column-
reverse; }
dd { margin: 0; font-size: 2.5rem; font-weight: 800; line-height: 1; }
dt { margin-top: .5rem; opacity: .9; }
```

Project 793 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - In numbers</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cleopatra Beauty Salon in numbers	The main heading; only one per page.
<dl class="numbers">	Description list of term / description pairs.
<dt>Years open</dt><dd>8</dd>	A term (name) in a description list.
<dt>Happy customers</dt><dd>12,000+</dd>	The description of the preceding term.
<dt>Treatments</dt><dd>4</dd>	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(10rem, 1fr));	Defines the columns of the grid.
background: var(--brand);	Background colour or image.
border-radius: 14px;	Rounds the corners.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-direction: column-reverse;	Stacks flex items vertically.
font-size: 2.5rem;	Size of the text.
font-weight: 800;	Thickness of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).

Check your work

- dt before dd in source
- Numbers visually above labels
- Tiles equal height
- White text contrast on brand colour

Exercises

1. Animate the numbers counting up with JavaScript.
2. Add small icons.
3. Add a subtle gradient to the tiles.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 794: Statistics strip for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 1 | Files: index.html, styles.css

Brief

Show four key numbers in coloured tiles where the big number appears above its label, using flex-direction: column-reverse on a dl.

Learning goals

- Use dl for label/value pairs
- Reverse visual order without changing source order
- Size big numbers with line-height 1

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd	flex-direction: column-reverse, grid auto-fit, font-weight: 800, line-height: 1, opacity

Build guide

1. Write the dl with a div per pair.
2. Grid the dl.
3. Make each div a flex column-reverse so the number shows first.
4. Style dd large and bold.
5. Colour the tiles.
6. Check the reading order in a screen reader stays label then value.

Project 794: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - In numbers</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Suez Auto Service in numbers</h1>
    <dl class="numbers">
      <div><dt>Years open</dt><dd>8</dd></div>
      <div><dt>Happy customers</dt><dd>12,000+</dd></div>
      <div><dt>Services</dt><dd>4</dd></div>
      <div><dt>Average rating</dt><dd>4.8</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 794: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 3rem auto; padding: 0 1rem; text-
align: center; }
.numbers { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fit, minmax(10rem, 1fr)); margin: 0; }
.numbers div { background: var(--brand); color: #fff; padding: 1.5rem
1rem; border-radius: 14px; display: flex; flex-direction: column-
reverse; }
dd { margin: 0; font-size: 2.5rem; font-weight: 800; line-height: 1; }
dt { margin-top: .5rem; opacity: .9; }
```

Project 794 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - In numbers</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Suez Auto Service in numbers	The main heading; only one per page.
<dl class="numbers">	Description list of term / description pairs.
<dt>Years open</dt><dd>8</dd>	A term (name) in a description list.
<dt>Happy customers</dt><dd>12,000+</dd>	The description of the preceding term.
<dt>Services</dt><dd>4</dd>	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(10rem, 1fr));	Defines the columns of the grid.
background: var(--brand);	Background colour or image.
border-radius: 14px;	Rounds the corners.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-direction: column-reverse;	Stacks flex items vertically.
font-size: 2.5rem;	Size of the text.
font-weight: 800;	Thickness of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).

Check your work

- dt before dd in source
- Numbers visually above labels
- Tiles equal height
- White text contrast on brand colour

Exercises

1. Animate the numbers counting up with JavaScript.
2. Add small icons.
3. Add a subtle gradient to the tiles.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 795: Statistics strip for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 1 | Files: index.html, styles.css

Brief

Show four key numbers in coloured tiles where the big number appears above its label, using flex-direction: column-reverse on a dl.

Learning goals

- Use dl for label/value pairs
- Reverse visual order without changing source order
- Size big numbers with line-height 1

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd	flex-direction: column-reverse, grid auto-fit, font-weight: 800, line-height: 1, opacity

Build guide

1. Write the dl with a div per pair.
2. Grid the dl.
3. Make each div a flex column-reverse so the number shows first.
4. Style dd large and bold.
5. Colour the tiles.
6. Check the reading order in a screen reader stays label then value.

Project 795: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - In numbers</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Luxor Music Academy in numbers</h1>
    <dl class="numbers">
      <div><dt>Years open</dt><dd>8</dd></div>
      <div><dt>Happy customers</dt><dd>12,000+</dd></div>
      <div><dt>Courses</dt><dd>4</dd></div>
      <div><dt>Average rating</dt><dd>4.8</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 795: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 3rem auto; padding: 0 1rem; text-
align: center; }
.numbers { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fit, minmax(10rem, 1fr)); margin: 0; }
.numbers div { background: var(--brand); color: #fff; padding: 1.5rem
1rem; border-radius: 14px; display: flex; flex-direction: column-
reverse; }
dd { margin: 0; font-size: 2.5rem; font-weight: 800; line-height: 1; }
dt { margin-top: .5rem; opacity: .9; }
```

Project 795 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - In numbers</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Luxor Music Academy in numbers	The main heading; only one per page.
<dl class="numbers">	Description list of term / description pairs.
<dt>Years open</dt><dd>8</dd>	A term (name) in a description list.
<dt>Happy customers</dt><dd>12,000+</dd>	The description of the preceding term.
<dt>Courses</dt><dd>4</dd>	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(10rem, 1fr));	Defines the columns of the grid.
background: var(--brand);	Background colour or image.
border-radius: 14px;	Rounds the corners.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-direction: column-reverse;	Stacks flex items vertically.
font-size: 2.5rem;	Size of the text.
font-weight: 800;	Thickness of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).

Check your work

- dt before dd in source
- Numbers visually above labels
- Tiles equal height
- White text contrast on brand colour

Exercises

1. Animate the numbers counting up with JavaScript.
2. Add small icons.
3. Add a subtle gradient to the tiles.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 796: Statistics strip for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 1 | Files: index.html, styles.css

Brief

Show four key numbers in coloured tiles where the big number appears above its label, using flex-direction: column-reverse on a dl.

Learning goals

- Use dl for label/value pairs
- Reverse visual order without changing source order
- Size big numbers with line-height 1

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd	flex-direction: column-reverse, grid auto-fit, font-weight: 800, line-height: 1, opacity

Build guide

1. Write the dl with a div per pair.
2. Grid the dl.
3. Make each div a flex column-reverse so the number shows first.
4. Style dd large and bold.
5. Colour the tiles.
6. Check the reading order in a screen reader stays label then value.

Project 796: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - In numbers</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Port Said Seafood in numbers</h1>
    <dl class="numbers">
      <div><dt>Years open</dt><dd>8</dd></div>
      <div><dt>Happy customers</dt><dd>12,000+</dd></div>
      <div><dt>Dishes</dt><dd>4</dd></div>
      <div><dt>Average rating</dt><dd>4.8</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 796: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 3rem auto; padding: 0 1rem; text-
align: center; }
.numbers { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fit, minmax(10rem, 1fr)); margin: 0; }
.numbers div { background: var(--brand); color: #fff; padding: 1.5rem
1rem; border-radius: 14px; display: flex; flex-direction: column-
reverse; }
dd { margin: 0; font-size: 2.5rem; font-weight: 800; line-height: 1; }
dt { margin-top: .5rem; opacity: .9; }
```

Project 796 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - In numbers</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Port Said Seafood in numbers	The main heading; only one per page.
<dl class="numbers">	Description list of term / description pairs.
<dt>Years open</dt><dd>8</dd>	A term (name) in a description list.
<dt>Happy customers</dt><dd>12,000+</dd>	The description of the preceding term.
<dt>Dishes</dt><dd>4</dd>	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(10rem, 1fr));	Defines the columns of the grid.
background: var(--brand);	Background colour or image.
border-radius: 14px;	Rounds the corners.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-direction: column-reverse;	Stacks flex items vertically.
font-size: 2.5rem;	Size of the text.
font-weight: 800;	Thickness of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).

Check your work

- dt before dd in source
- Numbers visually above labels
- Tiles equal height
- White text contrast on brand colour

Exercises

1. Animate the numbers counting up with JavaScript.
2. Add small icons.
3. Add a subtle gradient to the tiles.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 797: Statistics strip for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 1 | Files: index.html, styles.css

Brief

Show four key numbers in coloured tiles where the big number appears above its label, using flex-direction: column-reverse on a dl.

Learning goals

- Use dl for label/value pairs
- Reverse visual order without changing source order
- Size big numbers with line-height 1

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd	flex-direction: column-reverse, grid auto-fit, font-weight: 800, line-height: 1, opacity

Build guide

1. Write the dl with a div per pair.
2. Grid the dl.
3. Make each div a flex column-reverse so the number shows first.
4. Style dd large and bold.
5. Colour the tiles.
6. Check the reading order in a screen reader stays label then value.

Project 797: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - In numbers</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Delta Kids Library in numbers</h1>
    <dl class="numbers">
      <div><dt>Years open</dt><dd>8</dd></div>
      <div><dt>Happy customers</dt><dd>12,000+</dd></div>
      <div><dt>Programmes</dt><dd>4</dd></div>
      <div><dt>Average rating</dt><dd>4.8</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 797: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 3rem auto; padding: 0 1rem; text-
align: center; }
.numbers { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fit, minmax(10rem, 1fr)); margin: 0; }
.numbers div { background: var(--brand); color: #fff; padding: 1.5rem
1rem; border-radius: 14px; display: flex; flex-direction: column-
reverse; }
dd { margin: 0; font-size: 2.5rem; font-weight: 800; line-height: 1; }
dt { margin-top: .5rem; opacity: .9; }
```

Project 797 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - In numbers</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Delta Kids Library in numbers	The main heading; only one per page.
<dl class="numbers">	Description list of term / description pairs.
<dt>Years open</dt><dd>8</dd>	A term (name) in a description list.
<dt>Happy customers</dt><dd>12,000+</dd>	The description of the preceding term.
<dt>Programmes</dt><dd>4</dd>	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(10rem, 1fr));	Defines the columns of the grid.
background: var(--brand);	Background colour or image.
border-radius: 14px;	Rounds the corners.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-direction: column-reverse;	Stacks flex items vertically.
font-size: 2.5rem;	Size of the text.
font-weight: 800;	Thickness of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).

Check your work

- dt before dd in source
- Numbers visually above labels
- Tiles equal height
- White text contrast on brand colour

Exercises

1. Animate the numbers counting up with JavaScript.
2. Add small icons.
3. Add a subtle gradient to the tiles.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 798: Statistics strip for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Show four key numbers in coloured tiles where the big number appears above its label, using flex-direction: column-reverse on a dl.

Learning goals

- Use dl for label/value pairs
- Reverse visual order without changing source order
- Size big numbers with line-height 1

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd	flex-direction: column-reverse, grid auto-fit, font-weight: 800, line-height: 1, opacity

Build guide

1. Write the dl with a div per pair.
2. Grid the dl.
3. Make each div a flex column-reverse so the number shows first.
4. Style dd large and bold.
5. Colour the tiles.
6. Check the reading order in a screen reader stays label then value.

Project 798: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - In numbers</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Nubian Guest House in numbers</h1>
    <dl class="numbers">
      <div><dt>Years open</dt><dd>8</dd></div>
      <div><dt>Happy customers</dt><dd>12,000+</dd></div>
      <div><dt>Rooms</dt><dd>4</dd></div>
      <div><dt>Average rating</dt><dd>4.8</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 798: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 3rem auto; padding: 0 1rem; text-
align: center; }
.numbers { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fit, minmax(10rem, 1fr)); margin: 0; }
.numbers div { background: var(--brand); color: #fff; padding: 1.5rem
1rem; border-radius: 14px; display: flex; flex-direction: column-
reverse; }
dd { margin: 0; font-size: 2.5rem; font-weight: 800; line-height: 1; }
dt { margin-top: .5rem; opacity: .9; }
```

Project 798 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - In numbers</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Nubian Guest House in numbers	The main heading; only one per page.
<dl class="numbers">	Description list of term / description pairs.
<dt>Years open</dt><dd>8</dd>	A term (name) in a description list.
<dt>Happy customers</dt><dd>12,000+</dd>	The description of the preceding term.
<dt>Rooms</dt><dd>4</dd>	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(10rem, 1fr));	Defines the columns of the grid.
background: var(--brand);	Background colour or image.
border-radius: 14px;	Rounds the corners.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-direction: column-reverse;	Stacks flex items vertically.
font-size: 2.5rem;	Size of the text.
font-weight: 800;	Thickness of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).

Check your work

- dt before dd in source
- Numbers visually above labels
- Tiles equal height
- White text contrast on brand colour

Exercises

1. Animate the numbers counting up with JavaScript.
2. Add small icons.
3. Add a subtle gradient to the tiles.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 799: Statistics strip for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 1 | Files: index.html, styles.css

Brief

Show four key numbers in coloured tiles where the big number appears above its label, using flex-direction: column-reverse on a dl.

Learning goals

- Use dl for label/value pairs
- Reverse visual order without changing source order
- Size big numbers with line-height 1

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd	flex-direction: column-reverse, grid auto-fit, font-weight: 800, line-height: 1, opacity

Build guide

1. Write the dl with a div per pair.
2. Grid the dl.
3. Make each div a flex column-reverse so the number shows first.
4. Style dd large and bold.
5. Colour the tiles.
6. Check the reading order in a screen reader stays label then value.

Project 799: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - In numbers</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Ismailia Cycling Store in numbers</h1>
    <dl class="numbers">
      <div><dt>Years open</dt><dd>8</dd></div>
      <div><dt>Happy customers</dt><dd>12,000+</dd></div>
      <div><dt>Bikes</dt><dd>4</dd></div>
      <div><dt>Average rating</dt><dd>4.8</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 799: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 3rem auto; padding: 0 1rem; text-
align: center; }
.numbers { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fit, minmax(10rem, 1fr)); margin: 0; }
.numbers div { background: var(--brand); color: #fff; padding: 1.5rem
1rem; border-radius: 14px; display: flex; flex-direction: column-
reverse; }
dd { margin: 0; font-size: 2.5rem; font-weight: 800; line-height: 1; }
dt { margin-top: .5rem; opacity: .9; }
```

Project 799 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - In numbers</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Ismailia Cycling Store in numbers	The main heading; only one per page.
<dl class="numbers">	Description list of term / description pairs.
<dt>Years open</dt><dd>8</dd>	A term (name) in a description list.
<dt>Happy customers</dt><dd>12,000+</dd>	The description of the preceding term.
<dt>Bikes</dt><dd>4</dd>	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(10rem, 1fr));	Defines the columns of the grid.
background: var(--brand);	Background colour or image.
border-radius: 14px;	Rounds the corners.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-direction: column-reverse;	Stacks flex items vertically.
font-size: 2.5rem;	Size of the text.
font-weight: 800;	Thickness of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).

Check your work

- dt before dd in source
- Numbers visually above labels
- Tiles equal height
- White text contrast on brand colour

Exercises

1. Animate the numbers counting up with JavaScript.
2. Add small icons.
3. Add a subtle gradient to the tiles.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 800: Statistics strip for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 1 | Files: index.html, styles.css

Brief

Show four key numbers in coloured tiles where the big number appears above its label, using flex-direction: column-reverse on a dl.

Learning goals

- Use dl for label/value pairs
- Reverse visual order without changing source order
- Size big numbers with line-height 1

Elements and CSS used

HTML elements	CSS features
dl, div, dt, dd	flex-direction: column-reverse, grid auto-fit, font-weight: 800, line-height: 1, opacity

Build guide

1. Write the dl with a div per pair.
2. Grid the dl.
3. Make each div a flex column-reverse so the number shows first.
4. Style dd large and bold.
5. Colour the tiles.
6. Check the reading order in a screen reader stays label then value.

Project 800: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - In numbers</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Minya Coding Club in numbers</h1>
    <dl class="numbers">
      <div><dt>Years open</dt><dd>8</dd></div>
      <div><dt>Happy customers</dt><dd>12,000+</dd></div>
      <div><dt>Workshops</dt><dd>4</dd></div>
      <div><dt>Average rating</dt><dd>4.8</dd></div>
    </dl>
  </main>
</body>
</html>
```

Project 800: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 60rem; margin: 3rem auto; padding: 0 1rem; text-
align: center; }
.numbers { display: grid; gap: 1rem; grid-template-columns: repeat(
auto-fit, minmax(10rem, 1fr)); margin: 0; }
.numbers div { background: var(--brand); color: #fff; padding: 1.5rem
1rem; border-radius: 14px; display: flex; flex-direction: column-
reverse; }
dd { margin: 0; font-size: 2.5rem; font-weight: 800; line-height: 1; }
dt { margin-top: .5rem; opacity: .9; }
```

Project 800 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - In numbers</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Minya Coding Club in numbers	The main heading; only one per page.
<dl class="numbers">	Description list of term / description pairs.
<dt>Years open</dt><dd>8</dd>	A term (name) in a description list.
<dt>Happy customers</dt><dd>12,000+</dd>	The description of the preceding term.
<dt>Workshops</dt><dd>4</dd>	Generic block container for grouping and layout.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(10rem, 1fr));	Defines the columns of the grid.
background: var(--brand);	Background colour or image.
border-radius: 14px;	Rounds the corners.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-direction: column-reverse;	Stacks flex items vertically.
font-size: 2.5rem;	Size of the text.
font-weight: 800;	Thickness of the text.
opacity: .9;	Transparency from 0 (invisible) to 1 (solid).

Check your work

- dt before dd in source
- Numbers visually above labels
- Tiles equal height
- White text contrast on brand colour

Exercises

1. Animate the numbers counting up with JavaScript.
2. Add small icons.
3. Add a subtle gradient to the tiles.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Breadcrumbs and pagination

Level 1 | 25 projects, one per theme

Add two navigation aids: a breadcrumb trail with CSS-generated separators and a pagination bar with a highlighted current page.

Project 801: Breadcrumbs and pagination for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 1 | Files: index.html, styles.css

Brief

Add two navigation aids: a breadcrumb trail with CSS-generated separators and a pagination bar with a highlighted current page.

Learning goals

- Use nav with aria-label for secondary navigation
- Generate separators with li + li::before
- Style the current item with [aria-current]

Elements and CSS used

HTML elements	CSS features
nav, ol, li, a	adjacent sibling +, ::before content, attribute selector, min-width, border

Build guide

1. Write the breadcrumb ol inside a nav.
2. Mark the last item with aria-current="page" and no link.
3. Write the pager with previous/next arrows labelled.
4. Add separators with li + li::before so the first has none.
5. Style pager links as boxes.
6. Highlight the current page.

Project 801: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Learn HTML - Cairo Book Shop</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav aria-label="Breadcrumb">
      <ol class="crumbs">
        <li><a href="index.html">Home</a></li>
        <li><a href="books.html">Books</a></li>
        <li aria-current="page">Learn HTML</li>
      </ol>
    </nav>
    <h1>Learn HTML</h1>
    <p>From your first tag to a complete page.</p>
    <nav class="pager" aria-label="Pagination">
      <a href="?page=1" aria-label="Previous page">&laquo;</a>
      <a href="?page=1">1</a>
      <a href="?page=2" aria-current="page">2</a>
      <a href="?page=3">3</a>
      <a href="?page=3" aria-label="Next page">&raquo;</a>
    </nav>
  </main>
</body>
</html>
```

Project 801: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.crumbs { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .25rem; font-size: .9rem; }
.crumbs li + li::before { content: "/"; margin: 0 .5rem; color: var(--
muted); }
.crumbs a { color: var(--brand); }
.crumbs [aria-current] { color: var(--muted); }
.pager { display: flex; gap: .25rem; margin-top: 3rem; }
.pager a { min-width: 2.4rem; padding: .5rem; text-align: center;
border: 1px solid var(--line); border-radius: 6px; text-decoration:
```

```
none; color: var(--ink); }
.pager a:hover { background: var(--accent); }
.pager a[aria-current] { background: var(--brand); color: #fff;
border-color: var(--brand); }
```

Project 801 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Learn HTML - Cairo Book Shop</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav aria-label="Breadcrumb">	A block of navigation links; aria-label names it for screen readers.
<ol class="crumbs">	Ordered (numbered) list; the order matters.
Home	A hyperlink; href gives the destination.
Books	One list item.
<li aria-current="page">Learn HTML	Tells assistive technology which item is the current page or step.
Learn HTML	The main heading; only one per page.
From your first tag to a complete page.	A paragraph of text.

Line	What it does
<nav class="pager" aria-label="Pagination">	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.

Declaration	What it does
gap: .25rem;	Space between grid or flex items without extra margins.
font-size: .9rem;	Size of the text.
.crumbs li + li::before {	Adjacent sibling combinator: every li that follows another li.
content: "/";	The text or empty string for a pseudo-element.
.crumbs [aria-current] {	Attribute selector: styles the current page or step.
text-align: center;	Centres inline content such as text.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
.pager a:hover {	Applies while the pointer is over the element.
background: var(--accent);	Background colour or image.
border-color: var(--brand);	The line around the element: width, style and colour.

Check your work

- Both navs have distinct aria-labels
- Separators not in the HTML
- Arrows have aria-label
- Current page not a link in breadcrumb

Exercises

1. Use an SVG chevron as the separator.
2. Add schema.org BreadcrumbList microdata.

3. Collapse middle crumbs on narrow screens.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 802: Breadcrumbs and pagination for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 1 | Files: index.html, styles.css

Brief

Add two navigation aids: a breadcrumb trail with CSS-generated separators and a pagination bar with a highlighted current page.

Learning goals

- Use nav with aria-label for secondary navigation
- Generate separators with li + li::before
- Style the current item with [aria-current]

Elements and CSS used

HTML elements	CSS features
nav, ol, li, a	adjacent sibling +, ::before content, attribute selector, min-width, border

Build guide

1. Write the breadcrumb ol inside a nav.
2. Mark the last item with aria-current="page" and no link.
3. Write the pager with previous/next arrows labelled.
4. Add separators with li + li::before so the first has none.
5. Style pager links as boxes.
6. Highlight the current page.

Project 802: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sourdough loaf - Nile Bakery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav aria-label="Breadcrumb">
      <ol class="crumbs">
        <li><a href="index.html">Home</a></li>
        <li><a href="pastries.html">Pastries</a></li>
        <li aria-current="page">Sourdough loaf</li>
      </ol>
    </nav>
    <h1>Sourdough loaf</h1>
    <p>Slow fermented, crisp crust.</p>
    <nav class="pager" aria-label="Pagination">
      <a href="?page=1" aria-label="Previous page">&laquo;</a>
      <a href="?page=1">1</a>
      <a href="?page=2" aria-current="page">2</a>
      <a href="?page=3">3</a>
      <a href="?page=3" aria-label="Next page">&raquo;</a>
    </nav>
  </main>
</body>
</html>
```

Project 802: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.crumbs { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .25rem; font-size: .9rem; }
.crumbs li + li::before { content: "/"; margin: 0 .5rem; color: var(--
muted); }
.crumbs a { color: var(--brand); }
.crumbs [aria-current] { color: var(--muted); }
.pager { display: flex; gap: .25rem; margin-top: 3rem; }
.pager a { min-width: 2.4rem; padding: .5rem; text-align: center;
border: 1px solid var(--line); border-radius: 6px; text-decoration:
```

```
none; color: var(--ink); }
.pager a:hover { background: var(--accent); }
.pager a[aria-current] { background: var(--brand); color: #fff;
border-color: var(--brand); }
```

Project 802 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sourdough loaf - Nile Bakery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav aria-label="Breadcrumb">	A block of navigation links; aria-label names it for screen readers.
<ol class="crumbs">	Ordered (numbered) list; the order matters.
Home	A hyperlink; href gives the destination.
Pastries	One list item.
<li aria-current="page">Sourdough loaf	Tells assistive technology which item is the current page or step.
Sourdough loaf	The main heading; only one per page.
Slow fermented, crisp crust.	A paragraph of text.

Line	What it does
<nav class="pager" aria-label="Pagination">	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.

Declaration	What it does
gap: .25rem;	Space between grid or flex items without extra margins.
font-size: .9rem;	Size of the text.
.crumbs li + li::before {	Adjacent sibling combinator: every li that follows another li.
content: "/";	The text or empty string for a pseudo-element.
.crumbs [aria-current] {	Attribute selector: styles the current page or step.
text-align: center;	Centres inline content such as text.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
.pager a:hover {	Applies while the pointer is over the element.
background: var(--accent);	Background colour or image.
border-color: var(--brand);	The line around the element: width, style and colour.

Check your work

- Both navs have distinct aria-labels
- Separators not in the HTML
- Arrows have aria-label
- Current page not a link in breadcrumb

Exercises

1. Use an SVG chevron as the separator.
2. Add schema.org BreadcrumbList microdata.

3. Collapse middle crumbs on narrow screens.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 803: Breadcrumbs and pagination for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 1 | Files: index.html, styles.css

Brief

Add two navigation aids: a breadcrumb trail with CSS-generated separators and a pagination bar with a highlighted current page.

Learning goals

- Use nav with aria-label for secondary navigation
- Generate separators with li + li::before
- Style the current item with [aria-current]

Elements and CSS used

HTML elements	CSS features
nav, ol, li, a	adjacent sibling +, ::before content, attribute selector, min-width, border

Build guide

1. Write the breadcrumb ol inside a nav.
2. Mark the last item with aria-current="page" and no link.
3. Write the pager with previous/next arrows labelled.
4. Add separators with li + li::before so the first has none.
5. Style pager links as boxes.
6. Highlight the current page.

Project 803: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Morning yoga - Pyramid Fitness</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav aria-label="Breadcrumb">
      <ol class="crumbs">
        <li><a href="index.html">Home</a></li>
        <li><a href="classes.html">Classes</a></li>
        <li aria-current="page">Morning yoga</li>
      </ol>
    </nav>
    <h1>Morning yoga</h1>
    <p>Flexibility and calm, 60 minutes.</p>
    <nav class="pager" aria-label="Pagination">
      <a href="?page=1" aria-label="Previous page">&laquo;</a>
      <a href="?page=1">1</a>
      <a href="?page=2" aria-current="page">2</a>
      <a href="?page=3">3</a>
      <a href="?page=3" aria-label="Next page">&raquo;</a>
    </nav>
  </main>
</body>
</html>
```

Project 803: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.crumbs { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .25rem; font-size: .9rem; }
.crumbs li + li::before { content: "/"; margin: 0 .5rem; color: var(--
muted); }
.crumbs a { color: var(--brand); }
.crumbs [aria-current] { color: var(--muted); }
.pager { display: flex; gap: .25rem; margin-top: 3rem; }
.pager a { min-width: 2.4rem; padding: .5rem; text-align: center;
border: 1px solid var(--line); border-radius: 6px; text-decoration:
```

```
none; color: var(--ink); }
.pager a:hover { background: var(--accent); }
.pager a[aria-current] { background: var(--brand); color: #fff;
border-color: var(--brand); }
```

Project 803 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Morning yoga - Pyramid Fitness</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav aria-label="Breadcrumb">	A block of navigation links; aria-label names it for screen readers.
<ol class="crumbs">	Ordered (numbered) list; the order matters.
Home	A hyperlink; href gives the destination.
Classes	One list item.
<li aria-current="page">Morning yoga	Tells assistive technology which item is the current page or step.
Morning yoga	The main heading; only one per page.

Line	What it does
Flexibility and calm, 60 minutes.	A paragraph of text.
<nav class="pager" aria-label="Pagination">	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .25rem;	Space between grid or flex items without extra margins.
font-size: .9rem;	Size of the text.
.crumbs li + li::before {	Adjacent sibling combinator: every li that follows another li.
content: "/";	The text or empty string for a pseudo-element.
.crumbs [aria-current] {	Attribute selector: styles the current page or step.
text-align: center;	Centres inline content such as text.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
.pager a:hover {	Applies while the pointer is over the element.
background: var(--accent);	Background colour or image.
border-color: var(--brand);	The line around the element: width, style and colour.

Check your work

- Both navs have distinct aria-labels
- Separators not in the HTML
- Arrows have aria-label
- Current page not a link in breadcrumb

Exercises

1. Use an SVG chevron as the separator.
2. Add schema.org BreadcrumbList microdata.
3. Collapse middle crumbs on narrow screens.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 804: Breadcrumbs and pagination for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 1 | Files: index.html, styles.css

Brief

Add two navigation aids: a breadcrumb trail with CSS-generated separators and a pagination bar with a highlighted current page.

Learning goals

- Use nav with aria-label for secondary navigation
- Generate separators with li + li::before
- Style the current item with [aria-current]

Elements and CSS used

HTML elements	CSS features
nav, ol, li, a	adjacent sibling +, ::before content, attribute selector, min-width, border

Build guide

1. Write the breadcrumb ol inside a nav.
2. Mark the last item with aria-current="page" and no link.
3. Write the pager with previous/next arrows labelled.
4. Add separators with li + li::before so the first has none.
5. Style pager links as boxes.
6. Highlight the current page.

Project 804: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Check-up - Delta Dental Clinic</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav aria-label="Breadcrumb">
      <ol class="crumbs">
        <li><a href="index.html">Home</a></li>
        <li><a href="services.html">Services</a></li>
        <li aria-current="page">Check-up</li>
      </ol>
    </nav>
    <h1>Check-up</h1>
    <p>Examination and cleaning.</p>
    <nav class="pager" aria-label="Pagination">
      <a href="?page=1" aria-label="Previous page">&laquo;</a>
      <a href="?page=1">1</a>
      <a href="?page=2" aria-current="page">2</a>
      <a href="?page=3">3</a>
      <a href="?page=3" aria-label="Next page">&raquo;</a>
    </nav>
  </main>
</body>
</html>
```

Project 804: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.crumbs { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .25rem; font-size: .9rem; }
.crumbs li + li::before { content: "/"; margin: 0 .5rem; color: var(--
muted); }
.crumbs a { color: var(--brand); }
.crumbs [aria-current] { color: var(--muted); }
.pager { display: flex; gap: .25rem; margin-top: 3rem; }
.pager a { min-width: 2.4rem; padding: .5rem; text-align: center;
border: 1px solid var(--line); border-radius: 6px; text-decoration:
```

```
none; color: var(--ink); }
.pager a:hover { background: var(--accent); }
.pager a[aria-current] { background: var(--brand); color: #fff;
border-color: var(--brand); }
```

Project 804 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Check-up - Delta Dental Clinic</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav aria-label="Breadcrumb">	A block of navigation links; aria-label names it for screen readers.
<ol class="crumbs">	Ordered (numbered) list; the order matters.
Home	A hyperlink; href gives the destination.
Services	One list item.
<li aria-current="page">Check-up	Tells assistive technology which item is the current page or step.
Check-up	The main heading; only one per page.
Examination and cleaning.	A paragraph of text.

Line	What it does
<nav class="pager" aria-label="Pagination">	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.

Declaration	What it does
gap: .25rem;	Space between grid or flex items without extra margins.
font-size: .9rem;	Size of the text.
.crumbs li + li::before {	Adjacent sibling combinator: every li that follows another li.
content: "/";	The text or empty string for a pseudo-element.
.crumbs [aria-current] {	Attribute selector: styles the current page or step.
text-align: center;	Centres inline content such as text.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
.pager a:hover {	Applies while the pointer is over the element.
background: var(--accent);	Background colour or image.
border-color: var(--brand);	The line around the element: width, style and colour.

Check your work

- Both navs have distinct aria-labels
- Separators not in the HTML
- Arrows have aria-label
- Current page not a link in breadcrumb

Exercises

1. Use an SVG chevron as the separator.
2. Add schema.org BreadcrumbList microdata.

3. Collapse middle crumbs on narrow screens.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 805: Breadcrumbs and pagination for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 1 | Files: index.html, styles.css

Brief

Add two navigation aids: a breadcrumb trail with CSS-generated separators and a pagination bar with a highlighted current page.

Learning goals

- Use nav with aria-label for secondary navigation
- Generate separators with li + li::before
- Style the current item with [aria-current]

Elements and CSS used

HTML elements	CSS features
nav, ol, li, a	adjacent sibling +, ::before content, attribute selector, min-width, border

Build guide

1. Write the breadcrumb ol inside a nav.
2. Mark the last item with aria-current="page" and no link.
3. Write the pager with previous/next arrows labelled.
4. Add separators with li + li::before so the first has none.
5. Style pager links as boxes.
6. Highlight the current page.

Project 805: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor day trip - Red Sea Travel</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav aria-label="Breadcrumb">
      <ol class="crumbs">
        <li><a href="index.html">Home</a></li>
        <li><a href="tours.html">Tours</a></li>
        <li aria-current="page">Luxor day trip</li>
      </ol>
    </nav>
    <h1>Luxor day trip</h1>
    <p>Karnak, Valley of the Kings.</p>
    <nav class="pager" aria-label="Pagination">
      <a href="?page=1" aria-label="Previous page">&laquo;</a>
      <a href="?page=1">1</a>
      <a href="?page=2" aria-current="page">2</a>
      <a href="?page=3">3</a>
      <a href="?page=3" aria-label="Next page">&raquo;</a>
    </nav>
  </main>
</body>
</html>
```

Project 805: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.crumbs { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .25rem; font-size: .9rem; }
.crumbs li + li::before { content: "/"; margin: 0 .5rem; color: var(--
muted); }
.crumbs a { color: var(--brand); }
.crumbs [aria-current] { color: var(--muted); }
.pager { display: flex; gap: .25rem; margin-top: 3rem; }
.pager a { min-width: 2.4rem; padding: .5rem; text-align: center;
border: 1px solid var(--line); border-radius: 6px; text-decoration:
```

```
none; color: var(--ink); }
.pager a:hover { background: var(--accent); }
.pager a[aria-current] { background: var(--brand); color: #fff;
border-color: var(--brand); }
```

Project 805 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor day trip - Red Sea Travel</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav aria-label="Breadcrumb">	A block of navigation links; aria-label names it for screen readers.
<ol class="crumbs">	Ordered (numbered) list; the order matters.
Home	A hyperlink; href gives the destination.
Tours	One list item.
<li aria-current="page">Luxor day trip	Tells assistive technology which item is the current page or step.
Luxor day trip	The main heading; only one per page.
Karnak, Valley of the Kings.	A paragraph of text.

Line	What it does
<nav class="pager" aria-label="Pagination">	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.

Declaration	What it does
gap: .25rem;	Space between grid or flex items without extra margins.
font-size: .9rem;	Size of the text.
.crumbs li + li::before {	Adjacent sibling combinator: every li that follows another li.
content: "/";	The text or empty string for a pseudo-element.
.crumbs [aria-current] {	Attribute selector: styles the current page or step.
text-align: center;	Centres inline content such as text.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
.pager a:hover {	Applies while the pointer is over the element.
background: var(--accent);	Background colour or image.
border-color: var(--brand);	The line around the element: width, style and colour.

Check your work

- Both navs have distinct aria-labels
- Separators not in the HTML
- Arrows have aria-label
- Current page not a link in breadcrumb

Exercises

1. Use an SVG chevron as the separator.
2. Add schema.org BreadcrumbList microdata.

3. Collapse middle crumbs on narrow screens.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 806: Breadcrumbs and pagination for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Add two navigation aids: a breadcrumb trail with CSS-generated separators and a pagination bar with a highlighted current page.

Learning goals

- Use nav with aria-label for secondary navigation
- Generate separators with li + li::before
- Style the current item with [aria-current]

Elements and CSS used

HTML elements	CSS features
nav, ol, li, a	adjacent sibling +, ::before content, attribute selector, min-width, border

Build guide

1. Write the breadcrumb ol inside a nav.
2. Mark the last item with aria-current="page" and no link.
3. Write the pager with previous/next arrows labelled.
4. Add separators with li + li::before so the first has none.
5. Style pager links as boxes.
6. Highlight the current page.

Project 806: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>English A1 - Lotus Language School</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav aria-label="Breadcrumb">
      <ol class="crumbs">
        <li><a href="index.html">Home</a></li>
        <li><a href="courses.html">Courses</a></li>
        <li aria-current="page">English A1</li>
      </ol>
    </nav>
    <h1>English A1</h1>
    <p>Beginner, 8 weeks.</p>
    <nav class="pager" aria-label="Pagination">
      <a href="?page=1" aria-label="Previous page">&laquo;</a>
      <a href="?page=1">1</a>
      <a href="?page=2" aria-current="page">2</a>
      <a href="?page=3">3</a>
      <a href="?page=3" aria-label="Next page">&raquo;</a>
    </nav>
  </main>
</body>
</html>
```

Project 806: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.crumbs { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .25rem; font-size: .9rem; }
.crumbs li + li::before { content: "/"; margin: 0 .5rem; color: var(--
muted); }
.crumbs a { color: var(--brand); }
.crumbs [aria-current] { color: var(--muted); }
.pager { display: flex; gap: .25rem; margin-top: 3rem; }
.pager a { min-width: 2.4rem; padding: .5rem; text-align: center;
border: 1px solid var(--line); border-radius: 6px; text-decoration:
```

```
none; color: var(--ink); }
.pager a:hover { background: var(--accent); }
.pager a[aria-current] { background: var(--brand); color: #fff;
border-color: var(--brand); }
```

Project 806 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>English A1 - Lotus Language School</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav aria-label="Breadcrumb">	A block of navigation links; aria-label names it for screen readers.
<ol class="crumbs">	Ordered (numbered) list; the order matters.
Home	A hyperlink; href gives the destination.
Courses	One list item.
<li aria-current="page">English A1	Tells assistive technology which item is the current page or step.
English A1	The main heading; only one per page.
Beginner, 8 weeks.	A paragraph of text.

Line	What it does
<nav class="pager" aria-label="Pagination">	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.

Declaration	What it does
gap: .25rem;	Space between grid or flex items without extra margins.
font-size: .9rem;	Size of the text.
.crumbs li + li::before {	Adjacent sibling combinator: every li that follows another li.
content: "/";	The text or empty string for a pseudo-element.
.crumbs [aria-current] {	Attribute selector: styles the current page or step.
text-align: center;	Centres inline content such as text.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
.pager a:hover {	Applies while the pointer is over the element.
background: var(--accent);	Background colour or image.
border-color: var(--brand);	The line around the element: width, style and colour.

Check your work

- Both navs have distinct aria-labels
- Separators not in the HTML
- Arrows have aria-label
- Current page not a link in breadcrumb

Exercises

1. Use an SVG chevron as the separator.
2. Add schema.org BreadcrumbList microdata.

3. Collapse middle crumbs on narrow screens.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 807: Breadcrumbs and pagination for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 1 | Files: index.html, styles.css

Brief

Add two navigation aids: a breadcrumb trail with CSS-generated separators and a pagination bar with a highlighted current page.

Learning goals

- Use nav with aria-label for secondary navigation
- Generate separators with li + li::before
- Style the current item with [aria-current]

Elements and CSS used

HTML elements	CSS features
nav, ol, li, a	adjacent sibling +, ::before content, attribute selector, min-width, border

Build guide

1. Write the breadcrumb ol inside a nav.
2. Mark the last item with aria-current="page" and no link.
3. Write the pager with previous/next arrows labelled.
4. Add separators with li + li::before so the first has none.
5. Style pager links as boxes.
6. Highlight the current page.

Project 807: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Flat white - Green Leaf Cafe</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav aria-label="Breadcrumb">
      <ol class="crumbs">
        <li><a href="index.html">Home</a></li>
        <li><a href="drinks.html">Drinks</a></li>
        <li aria-current="page">Flat white</li>
      </ol>
    </nav>
    <h1>Flat white</h1>
    <p>Double shot, silky milk.</p>
    <nav class="pager" aria-label="Pagination">
      <a href="?page=1" aria-label="Previous page">&laquo;</a>
      <a href="?page=1">1</a>
      <a href="?page=2" aria-current="page">2</a>
      <a href="?page=3">3</a>
      <a href="?page=3" aria-label="Next page">&raquo;</a>
    </nav>
  </main>
</body>
</html>
```

Project 807: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.crumbs { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .25rem; font-size: .9rem; }
.crumbs li + li::before { content: "/"; margin: 0 .5rem; color: var(--
muted); }
.crumbs a { color: var(--brand); }
.crumbs [aria-current] { color: var(--muted); }
.pager { display: flex; gap: .25rem; margin-top: 3rem; }
.pager a { min-width: 2.4rem; padding: .5rem; text-align: center;
border: 1px solid var(--line); border-radius: 6px; text-decoration:
```

```
none; color: var(--ink); }
.pager a:hover { background: var(--accent); }
.pager a[aria-current] { background: var(--brand); color: #fff;
border-color: var(--brand); }
```

Project 807 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Flat white - Green Leaf Cafe</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav aria-label="Breadcrumb">	A block of navigation links; aria-label names it for screen readers.
<ol class="crumbs">	Ordered (numbered) list; the order matters.
Home	A hyperlink; href gives the destination.
Drinks	One list item.
<li aria-current="page">Flat white	Tells assistive technology which item is the current page or step.
Flat white	The main heading; only one per page.
Double shot, silky milk.	A paragraph of text.

Line	What it does
<nav class="pager" aria-label="Pagination">	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.

Declaration	What it does
gap: .25rem;	Space between grid or flex items without extra margins.
font-size: .9rem;	Size of the text.
.crumbs li + li::before {	Adjacent sibling combinator: every li that follows another li.
content: "/";	The text or empty string for a pseudo-element.
.crumbs [aria-current] {	Attribute selector: styles the current page or step.
text-align: center;	Centres inline content such as text.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
.pager a:hover {	Applies while the pointer is over the element.
background: var(--accent);	Background colour or image.
border-color: var(--brand);	The line around the element: width, style and colour.

Check your work

- Both navs have distinct aria-labels
- Separators not in the HTML
- Arrows have aria-label
- Current page not a link in breadcrumb

Exercises

1. Use an SVG chevron as the separator.
2. Add schema.org BreadcrumbList microdata.

3. Collapse middle crumbs on narrow screens.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 808: Breadcrumbs and pagination for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 1 | Files: index.html, styles.css

Brief

Add two navigation aids: a breadcrumb trail with CSS-generated separators and a pagination bar with a highlighted current page.

Learning goals

- Use nav with aria-label for secondary navigation
- Generate separators with li + li::before
- Style the current item with [aria-current]

Elements and CSS used

HTML elements	CSS features
nav, ol, li, a	adjacent sibling +, ::before content, attribute selector, min-width, border

Build guide

1. Write the breadcrumb ol inside a nav.
2. Mark the last item with aria-current="page" and no link.
3. Write the pager with previous/next arrows labelled.
4. Add separators with li + li::before so the first has none.
5. Style pager links as boxes.
6. Highlight the current page.

Project 808: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Mount Sinai sunrise - Sinai Trekking Club</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav aria-label="Breadcrumb">
      <ol class="crumbs">
        <li><a href="index.html">Home</a></li>
        <li><a href="hikes.html">Hikes</a></li>
        <li aria-current="page">Mount Sinai sunrise</li>
      </ol>
    </nav>
    <h1>Mount Sinai sunrise</h1>
    <p>Night climb, 7 km.</p>
    <nav class="pager" aria-label="Pagination">
      <a href="?page=1" aria-label="Previous page">&laquo;</a>
      <a href="?page=1">1</a>
      <a href="?page=2" aria-current="page">2</a>
      <a href="?page=3">3</a>
      <a href="?page=3" aria-label="Next page">&raquo;</a>
    </nav>
  </main>
</body>
</html>
```

Project 808: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.crumbs { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .25rem; font-size: .9rem; }
.crumbs li + li::before { content: "/"; margin: 0 .5rem; color: var(--
muted); }
.crumbs a { color: var(--brand); }
.crumbs [aria-current] { color: var(--muted); }
.pager { display: flex; gap: .25rem; margin-top: 3rem; }
.pager a { min-width: 2.4rem; padding: .5rem; text-align: center;
border: 1px solid var(--line); border-radius: 6px; text-decoration:
```

```
none; color: var(--ink); }
.pager a:hover { background: var(--accent); }
.pager a[aria-current] { background: var(--brand); color: #fff;
border-color: var(--brand); }
```

Project 808 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Mount Sinai sunrise - Sinai Trekking Club</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav aria-label="Breadcrumb">	A block of navigation links; aria-label names it for screen readers.
<ol class="crumbs">	Ordered (numbered) list; the order matters.
Home	A hyperlink; href gives the destination.
Hikes	One list item.
<li aria-current="page">Mount Sinai sunrise	Tells assistive technology which item is the current page or step.
Mount Sinai sunrise	The main heading; only one per page.

Line	What it does
Night climb, 7 km.	A paragraph of text.
<nav class="pager" aria-label="Pagination">	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .25rem;	Space between grid or flex items without extra margins.
font-size: .9rem;	Size of the text.
.crumbs li + li::before {	Adjacent sibling combinator: every li that follows another li.
content: "/";	The text or empty string for a pseudo-element.
.crumbs [aria-current] {	Attribute selector: styles the current page or step.
text-align: center;	Centres inline content such as text.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
.pager a:hover {	Applies while the pointer is over the element.
background: var(--accent);	Background colour or image.
border-color: var(--brand);	The line around the element: width, style and colour.

Check your work

- Both navs have distinct aria-labels
- Separators not in the HTML
- Arrows have aria-label
- Current page not a link in breadcrumb

Exercises

1. Use an SVG chevron as the separator.
2. Add schema.org BreadcrumbList microdata.
3. Collapse middle crumbs on narrow screens.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 809: Breadcrumbs and pagination for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 1 | Files: index.html, styles.css

Brief

Add two navigation aids: a breadcrumb trail with CSS-generated separators and a pagination bar with a highlighted current page.

Learning goals

- Use nav with aria-label for secondary navigation
- Generate separators with li + li::before
- Style the current item with [aria-current]

Elements and CSS used

HTML elements	CSS features
nav, ol, li, a	adjacent sibling +, ::before content, attribute selector, min-width, border

Build guide

1. Write the breadcrumb ol inside a nav.
2. Mark the last item with aria-current="page" and no link.
3. Write the pager with previous/next arrows labelled.
4. Add separators with li + li::before so the first has none.
5. Style pager links as boxes.
6. Highlight the current page.

Project 809: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Portrait session - Horizon Photography</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav aria-label="Breadcrumb">
      <ol class="crumbs">
        <li><a href="index.html">Home</a></li>
        <li><a href="sessions.html">Sessions</a></li>
        <li aria-current="page">Portrait session</li>
      </ol>
    </nav>
    <h1>Portrait session</h1>
    <p>One hour, 20 edited photos.</p>
    <nav class="pager" aria-label="Pagination">
      <a href="?page=1" aria-label="Previous page">&laquo;</a>
      <a href="?page=1">1</a>
      <a href="?page=2" aria-current="page">2</a>
      <a href="?page=3">3</a>
      <a href="?page=3" aria-label="Next page">&raquo;</a>
    </nav>
  </main>
</body>
</html>
```

Project 809: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.crumbs { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .25rem; font-size: .9rem; }
.crumbs li + li::before { content: "/"; margin: 0 .5rem; color: var(--
muted); }
.crumbs a { color: var(--brand); }
.crumbs [aria-current] { color: var(--muted); }
.pager { display: flex; gap: .25rem; margin-top: 3rem; }
.pager a { min-width: 2.4rem; padding: .5rem; text-align: center;
border: 1px solid var(--line); border-radius: 6px; text-decoration:
```

```
none; color: var(--ink); }
.pager a:hover { background: var(--accent); }
.pager a[aria-current] { background: var(--brand); color: #fff;
border-color: var(--brand); }
```

Project 809 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Portrait session - Horizon Photography</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav aria-label="Breadcrumb">	A block of navigation links; aria-label names it for screen readers.
<ol class="crumbs">	Ordered (numbered) list; the order matters.
Home	A hyperlink; href gives the destination.
Sessions	One list item.
<li aria-current="page">Portrait session	Tells assistive technology which item is the current page or step.
Portrait session	The main heading; only one per page.

Line	What it does
One hour, 20 edited photos.	A paragraph of text.
<nav class="pager" aria-label="Pagination">	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .25rem;	Space between grid or flex items without extra margins.
font-size: .9rem;	Size of the text.
.crumbs li + li::before {	Adjacent sibling combinator: every li that follows another li.
content: "/";	The text or empty string for a pseudo-element.
.crumbs [aria-current] {	Attribute selector: styles the current page or step.
text-align: center;	Centres inline content such as text.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
.pager a:hover {	Applies while the pointer is over the element.
background: var(--accent);	Background colour or image.
border-color: var(--brand);	The line around the element: width, style and colour.

Check your work

- Both navs have distinct aria-labels
- Separators not in the HTML
- Arrows have aria-label
- Current page not a link in breadcrumb

Exercises

1. Use an SVG chevron as the separator.
2. Add schema.org BreadcrumbList microdata.
3. Collapse middle crumbs on narrow screens.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 810: Breadcrumbs and pagination for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 1 | Files: index.html, styles.css

Brief

Add two navigation aids: a breadcrumb trail with CSS-generated separators and a pagination bar with a highlighted current page.

Learning goals

- Use nav with aria-label for secondary navigation
- Generate separators with li + li::before
- Style the current item with [aria-current]

Elements and CSS used

HTML elements	CSS features
nav, ol, li, a	adjacent sibling +, ::before content, attribute selector, min-width, border

Build guide

1. Write the breadcrumb ol inside a nav.
2. Mark the last item with aria-current="page" and no link.
3. Write the pager with previous/next arrows labelled.
4. Add separators with li + li::before so the first has none.
5. Style pager links as boxes.
6. Highlight the current page.

Project 810: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Dotted notebook - Papyrus Stationery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav aria-label="Breadcrumb">
      <ol class="crumbs">
        <li><a href="index.html">Home</a></li>
        <li><a href="products.html">Products</a></li>
        <li aria-current="page">Dotted notebook</li>
      </ol>
    </nav>
    <h1>Dotted notebook</h1>
    <p>A5, 160 pages.</p>
    <nav class="pager" aria-label="Pagination">
      <a href="?page=1" aria-label="Previous page">&laquo;</a>
      <a href="?page=1">1</a>
      <a href="?page=2" aria-current="page">2</a>
      <a href="?page=3">3</a>
      <a href="?page=3" aria-label="Next page">&raquo;</a>
    </nav>
  </main>
</body>
</html>
```

Project 810: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.crumbs { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .25rem; font-size: .9rem; }
.crumbs li + li::before { content: "/"; margin: 0 .5rem; color: var(--
muted); }
.crumbs a { color: var(--brand); }
.crumbs [aria-current] { color: var(--muted); }
.pager { display: flex; gap: .25rem; margin-top: 3rem; }
.pager a { min-width: 2.4rem; padding: .5rem; text-align: center;
border: 1px solid var(--line); border-radius: 6px; text-decoration:
```

```
none; color: var(--ink); }
.pager a:hover { background: var(--accent); }
.pager a[aria-current] { background: var(--brand); color: #fff;
border-color: var(--brand); }
```

Project 810 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Dotted notebook - Papyrus Stationery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav aria-label="Breadcrumb">	A block of navigation links; aria-label names it for screen readers.
<ol class="crumbs">	Ordered (numbered) list; the order matters.
Home	A hyperlink; href gives the destination.
Products	One list item.
<li aria-current="page">Dotted notebook	Tells assistive technology which item is the current page or step.
Dotted notebook	The main heading; only one per page.
A5, 160 pages.	A paragraph of text.

Line	What it does
<nav class="pager" aria-label="Pagination">	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.

Declaration	What it does
gap: .25rem;	Space between grid or flex items without extra margins.
font-size: .9rem;	Size of the text.
.crumbs li + li::before {	Adjacent sibling combinator: every li that follows another li.
content: "/";	The text or empty string for a pseudo-element.
.crumbs [aria-current] {	Attribute selector: styles the current page or step.
text-align: center;	Centres inline content such as text.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
.pager a:hover {	Applies while the pointer is over the element.
background: var(--accent);	Background colour or image.
border-color: var(--brand);	The line around the element: width, style and colour.

Check your work

- Both navs have distinct aria-labels
- Separators not in the HTML
- Arrows have aria-label
- Current page not a link in breadcrumb

Exercises

1. Use an SVG chevron as the separator.
2. Add schema.org BreadcrumbList microdata.

3. Collapse middle crumbs on narrow screens.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 811: Breadcrumbs and pagination for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 1 | Files: index.html, styles.css

Brief

Add two navigation aids: a breadcrumb trail with CSS-generated separators and a pagination bar with a highlighted current page.

Learning goals

- Use nav with aria-label for secondary navigation
- Generate separators with li + li::before
- Style the current item with [aria-current]

Elements and CSS used

HTML elements	CSS features
nav, ol, li, a	adjacent sibling +, ::before content, attribute selector, min-width, border

Build guide

1. Write the breadcrumb ol inside a nav.
2. Mark the last item with aria-current="page" and no link.
3. Write the pager with previous/next arrows labelled.
4. Add separators with li + li::before so the first has none.
5. Style pager links as boxes.
6. Highlight the current page.

Project 811: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Monstera - Oasis Plant Nursery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav aria-label="Breadcrumb">
      <ol class="crumbs">
        <li><a href="index.html">Home</a></li>
        <li><a href="plants.html">Plants</a></li>
        <li aria-current="page">Monstera</li>
      </ol>
    </nav>
    <h1>Monstera</h1>
    <p>Large leaves, easy care.</p>
    <nav class="pager" aria-label="Pagination">
      <a href="?page=1" aria-label="Previous page">&laquo;</a>
      <a href="?page=1">1</a>
      <a href="?page=2" aria-current="page">2</a>
      <a href="?page=3">3</a>
      <a href="?page=3" aria-label="Next page">&raquo;</a>
    </nav>
  </main>
</body>
</html>
```

Project 811: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.crumbs { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .25rem; font-size: .9rem; }
.crumbs li + li::before { content: "/"; margin: 0 .5rem; color: var(--
muted); }
.crumbs a { color: var(--brand); }
.crumbs [aria-current] { color: var(--muted); }
.pager { display: flex; gap: .25rem; margin-top: 3rem; }
.pager a { min-width: 2.4rem; padding: .5rem; text-align: center;
border: 1px solid var(--line); border-radius: 6px; text-decoration:
```

```
none; color: var(--ink); }
.pager a:hover { background: var(--accent); }
.pager a[aria-current] { background: var(--brand); color: #fff;
border-color: var(--brand); }
```

Project 811 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Monstera - Oasis Plant Nursery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav aria-label="Breadcrumb">	A block of navigation links; aria-label names it for screen readers.
<ol class="crumbs">	Ordered (numbered) list; the order matters.
Home	A hyperlink; href gives the destination.
Plants	One list item.
<li aria-current="page">Monstera	Tells assistive technology which item is the current page or step.
Monstera	The main heading; only one per page.
Large leaves, easy care.	A paragraph of text.

Line	What it does
<nav class="pager" aria-label="Pagination">	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.

Declaration	What it does
gap: .25rem;	Space between grid or flex items without extra margins.
font-size: .9rem;	Size of the text.
.crumbs li + li::before {	Adjacent sibling combinator: every li that follows another li.
content: "/";	The text or empty string for a pseudo-element.
.crumbs [aria-current] {	Attribute selector: styles the current page or step.
text-align: center;	Centres inline content such as text.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
.pager a:hover {	Applies while the pointer is over the element.
background: var(--accent);	Background colour or image.
border-color: var(--brand);	The line around the element: width, style and colour.

Check your work

- Both navs have distinct aria-labels
- Separators not in the HTML
- Arrows have aria-label
- Current page not a link in breadcrumb

Exercises

1. Use an SVG chevron as the separator.
2. Add schema.org BreadcrumbList microdata.

3. Collapse middle crumbs on narrow screens.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 812: Breadcrumbs and pagination for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 1 | Files: index.html, styles.css

Brief

Add two navigation aids: a breadcrumb trail with CSS-generated separators and a pagination bar with a highlighted current page.

Learning goals

- Use nav with aria-label for secondary navigation
- Generate separators with li + li::before
- Style the current item with [aria-current]

Elements and CSS used

HTML elements	CSS features
nav, ol, li, a	adjacent sibling +, ::before content, attribute selector, min-width, border

Build guide

1. Write the breadcrumb ol inside a nav.
2. Mark the last item with aria-current="page" and no link.
3. Write the pager with previous/next arrows labelled.
4. Add separators with li + li::before so the first has none.
5. Style pager links as boxes.
6. Highlight the current page.

Project 812: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oak dining table - Cedar Furniture</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav aria-label="Breadcrumb">
      <ol class="crumbs">
        <li><a href="index.html">Home</a></li>
        <li><a href="pieces.html">Pieces</a></li>
        <li aria-current="page">Oak dining table</li>
      </ol>
    </nav>
    <h1>Oak dining table</h1>
    <p>Seats six.</p>
    <nav class="pager" aria-label="Pagination">
      <a href="?page=1" aria-label="Previous page">&laquo;</a>
      <a href="?page=1">1</a>
      <a href="?page=2" aria-current="page">2</a>
      <a href="?page=3">3</a>
      <a href="?page=3" aria-label="Next page">&raquo;</a>
    </nav>
  </main>
</body>
</html>
```

Project 812: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.crumbs { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .25rem; font-size: .9rem; }
.crumbs li + li::before { content: "/"; margin: 0 .5rem; color: var(--
muted); }
.crumbs a { color: var(--brand); }
.crumbs [aria-current] { color: var(--muted); }
.pager { display: flex; gap: .25rem; margin-top: 3rem; }
.pager a { min-width: 2.4rem; padding: .5rem; text-align: center;
border: 1px solid var(--line); border-radius: 6px; text-decoration:
```

```
none; color: var(--ink); }
.pager a:hover { background: var(--accent); }
.pager a[aria-current] { background: var(--brand); color: #fff;
border-color: var(--brand); }
```

Project 812 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oak dining table - Cedar Furniture</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav aria-label="Breadcrumb">	A block of navigation links; aria-label names it for screen readers.
<ol class="crumbs">	Ordered (numbered) list; the order matters.
Home	A hyperlink; href gives the destination.
Pieces	One list item.
<li aria-current="page">Oak dining table	Tells assistive technology which item is the current page or step.
Oak dining table	The main heading; only one per page.
Seats six.	A paragraph of text.

Line	What it does
<nav class="pager" aria-label="Pagination">	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.

Declaration	What it does
gap: .25rem;	Space between grid or flex items without extra margins.
font-size: .9rem;	Size of the text.
.crumbs li + li::before {	Adjacent sibling combinator: every li that follows another li.
content: "/";	The text or empty string for a pseudo-element.
.crumbs [aria-current] {	Attribute selector: styles the current page or step.
text-align: center;	Centres inline content such as text.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
.pager a:hover {	Applies while the pointer is over the element.
background: var(--accent);	Background colour or image.
border-color: var(--brand);	The line around the element: width, style and colour.

Check your work

- Both navs have distinct aria-labels
- Separators not in the HTML
- Arrows have aria-label
- Current page not a link in breadcrumb

Exercises

1. Use an SVG chevron as the separator.
2. Add schema.org BreadcrumbList microdata.

3. Collapse middle crumbs on narrow screens.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 813: Breadcrumbs and pagination for Byte Repair

Theme: Byte Repair (Nasr City) | Level 1 | Files: index.html, styles.css

Brief

Add two navigation aids: a breadcrumb trail with CSS-generated separators and a pagination bar with a highlighted current page.

Learning goals

- Use nav with aria-label for secondary navigation
- Generate separators with li + li::before
- Style the current item with [aria-current]

Elements and CSS used

HTML elements	CSS features
nav, ol, li, a	adjacent sibling +, ::before content, attribute selector, min-width, border

Build guide

1. Write the breadcrumb ol inside a nav.
2. Mark the last item with aria-current="page" and no link.
3. Write the pager with previous/next arrows labelled.
4. Add separators with li + li::before so the first has none.
5. Style pager links as boxes.
6. Highlight the current page.

Project 813: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Screen replacement - Byte Repair</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav aria-label="Breadcrumb">
      <ol class="crumbs">
        <li><a href="index.html">Home</a></li>
        <li><a href="repairs.html">Repairs</a></li>
        <li aria-current="page">Screen replacement</li>
      </ol>
    </nav>
    <h1>Screen replacement</h1>
    <p>Most phones, 1 hour.</p>
    <nav class="pager" aria-label="Pagination">
      <a href="?page=1" aria-label="Previous page">&laquo;</a>
      <a href="?page=1">1</a>
      <a href="?page=2" aria-current="page">2</a>
      <a href="?page=3">3</a>
      <a href="?page=3" aria-label="Next page">&raquo;</a>
    </nav>
  </main>
</body>
</html>
```

Project 813: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.crumbs { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .25rem; font-size: .9rem; }
.crumbs li + li::before { content: "/"; margin: 0 .5rem; color: var(--
muted); }
.crumbs a { color: var(--brand); }
.crumbs [aria-current] { color: var(--muted); }
.pager { display: flex; gap: .25rem; margin-top: 3rem; }
.pager a { min-width: 2.4rem; padding: .5rem; text-align: center;
border: 1px solid var(--line); border-radius: 6px; text-decoration:
```

```
none; color: var(--ink); }
.pager a:hover { background: var(--accent); }
.pager a[aria-current] { background: var(--brand); color: #fff;
border-color: var(--brand); }
```

Project 813 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Screen replacement - Byte Repair</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav aria-label="Breadcrumb">	A block of navigation links; aria-label names it for screen readers.
<ol class="crumbs">	Ordered (numbered) list; the order matters.
Home	A hyperlink; href gives the destination.
Repairs	One list item.
<li aria-current="page">Screen replacement	Tells assistive technology which item is the current page or step.
Screen replacement	The main heading; only one per page.

Line	What it does
Most phones, 1 hour.	A paragraph of text.
<nav class="pager" aria-label="Pagination">	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .25rem;	Space between grid or flex items without extra margins.
font-size: .9rem;	Size of the text.
.crumbs li + li::before {	Adjacent sibling combinator: every li that follows another li.
content: "/";	The text or empty string for a pseudo-element.
.crumbs [aria-current] {	Attribute selector: styles the current page or step.
text-align: center;	Centres inline content such as text.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
.pager a:hover {	Applies while the pointer is over the element.
background: var(--accent);	Background colour or image.
border-color: var(--brand);	The line around the element: width, style and colour.

Check your work

- Both navs have distinct aria-labels
- Separators not in the HTML
- Arrows have aria-label
- Current page not a link in breadcrumb

Exercises

1. Use an SVG chevron as the separator.
2. Add schema.org BreadcrumbList microdata.
3. Collapse middle crumbs on narrow screens.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 814: Breadcrumbs and pagination for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 1 | Files: index.html, styles.css

Brief

Add two navigation aids: a breadcrumb trail with CSS-generated separators and a pagination bar with a highlighted current page.

Learning goals

- Use nav with aria-label for secondary navigation
- Generate separators with li + li::before
- Style the current item with [aria-current]

Elements and CSS used

HTML elements	CSS features
nav, ol, li, a	adjacent sibling +, ::before content, attribute selector, min-width, border

Build guide

1. Write the breadcrumb ol inside a nav.
2. Mark the last item with aria-current="page" and no link.
3. Write the pager with previous/next arrows labelled.
4. Add separators with li + li::before so the first has none.
5. Style pager links as boxes.
6. Highlight the current page.

Project 814: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Full grooming - Sahara Pet Care</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav aria-label="Breadcrumb">
      <ol class="crumbs">
        <li><a href="index.html">Home</a></li>
        <li><a href="services.html">Services</a></li>
        <li aria-current="page">Full grooming</li>
      </ol>
    </nav>
    <h1>Full grooming</h1>
    <p>Bath, cut and nails.</p>
    <nav class="pager" aria-label="Pagination">
      <a href="?page=1" aria-label="Previous page">&laquo;</a>
      <a href="?page=1">1</a>
      <a href="?page=2" aria-current="page">2</a>
      <a href="?page=3">3</a>
      <a href="?page=3" aria-label="Next page">&raquo;</a>
    </nav>
  </main>
</body>
</html>
```

Project 814: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.crumbs { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .25rem; font-size: .9rem; }
.crumbs li + li::before { content: "/"; margin: 0 .5rem; color: var(--
muted); }
.crumbs a { color: var(--brand); }
.crumbs [aria-current] { color: var(--muted); }
.pager { display: flex; gap: .25rem; margin-top: 3rem; }
.pager a { min-width: 2.4rem; padding: .5rem; text-align: center;
border: 1px solid var(--line); border-radius: 6px; text-decoration:
```

```
none; color: var(--ink); }
.pager a:hover { background: var(--accent); }
.pager a[aria-current] { background: var(--brand); color: #fff;
border-color: var(--brand); }
```

Project 814 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Full grooming - Sahara Pet Care</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav aria-label="Breadcrumb">	A block of navigation links; aria-label names it for screen readers.
<ol class="crumbs">	Ordered (numbered) list; the order matters.
Home	A hyperlink; href gives the destination.
Services	One list item.
<li aria-current="page">Full grooming	Tells assistive technology which item is the current page or step.
Full grooming	The main heading; only one per page.
Bath, cut and nails.	A paragraph of text.

Line	What it does
<nav class="pager" aria-label="Pagination">	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.

Declaration	What it does
gap: .25rem;	Space between grid or flex items without extra margins.
font-size: .9rem;	Size of the text.
.crumbs li + li::before {	Adjacent sibling combinator: every li that follows another li.
content: "/";	The text or empty string for a pseudo-element.
.crumbs [aria-current] {	Attribute selector: styles the current page or step.
text-align: center;	Centres inline content such as text.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
.pager a:hover {	Applies while the pointer is over the element.
background: var(--accent);	Background colour or image.
border-color: var(--brand);	The line around the element: width, style and colour.

Check your work

- Both navs have distinct aria-labels
- Separators not in the HTML
- Arrows have aria-label
- Current page not a link in breadcrumb

Exercises

1. Use an SVG chevron as the separator.
2. Add schema.org BreadcrumbList microdata.

3. Collapse middle crumbs on narrow screens.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 815: Breadcrumbs and pagination for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Add two navigation aids: a breadcrumb trail with CSS-generated separators and a pagination bar with a highlighted current page.

Learning goals

- Use nav with aria-label for secondary navigation
- Generate separators with li + li::before
- Style the current item with [aria-current]

Elements and CSS used

HTML elements	CSS features
nav, ol, li, a	adjacent sibling +, ::before content, attribute selector, min-width, border

Build guide

1. Write the breadcrumb ol inside a nav.
2. Mark the last item with aria-current="page" and no link.
3. Write the pager with previous/next arrows labelled.
4. Add separators with li + li::before so the first has none.
5. Style pager links as boxes.
6. Highlight the current page.

Project 815: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Taster session - Alexandria Sailing School</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav aria-label="Breadcrumb">
      <ol class="crumbs">
        <li><a href="index.html">Home</a></li>
        <li><a href="lessons.html">Lessons</a></li>
        <li aria-current="page">Taster session</li>
      </ol>
    </nav>
    <h1>Taster session</h1>
    <p>Two hours on the water.</p>
    <nav class="pager" aria-label="Pagination">
      <a href="?page=1" aria-label="Previous page">&laquo;</a>
      <a href="?page=1">1</a>
      <a href="?page=2" aria-current="page">2</a>
      <a href="?page=3">3</a>
      <a href="?page=3" aria-label="Next page">&raquo;</a>
    </nav>
  </main>
</body>
</html>
```

Project 815: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.crumbs { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .25rem; font-size: .9rem; }
.crumbs li + li::before { content: "/"; margin: 0 .5rem; color: var(--
muted); }
.crumbs a { color: var(--brand); }
.crumbs [aria-current] { color: var(--muted); }
.pager { display: flex; gap: .25rem; margin-top: 3rem; }
.pager a { min-width: 2.4rem; padding: .5rem; text-align: center;
border: 1px solid var(--line); border-radius: 6px; text-decoration:
```

```
none; color: var(--ink); }
.pager a:hover { background: var(--accent); }
.pager a[aria-current] { background: var(--brand); color: #fff;
border-color: var(--brand); }
```

Project 815 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Taster session - Alexandria Sailing School</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav aria-label="Breadcrumb">	A block of navigation links; aria-label names it for screen readers.
<ol class="crumbs">	Ordered (numbered) list; the order matters.
Home	A hyperlink; href gives the destination.
Lessons	One list item.
<li aria-current="page">Taster session	Tells assistive technology which item is the current page or step.
Taster session	The main heading; only one per page.

Line	What it does
Two hours on the water.	A paragraph of text.
<nav class="pager" aria-label="Pagination">	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .25rem;	Space between grid or flex items without extra margins.
font-size: .9rem;	Size of the text.
.crumbs li + li::before {	Adjacent sibling combinator: every li that follows another li.
content: "/";	The text or empty string for a pseudo-element.
.crumbs [aria-current] {	Attribute selector: styles the current page or step.
text-align: center;	Centres inline content such as text.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
.pager a:hover {	Applies while the pointer is over the element.
background: var(--accent);	Background colour or image.
border-color: var(--brand);	The line around the element: width, style and colour.

Check your work

- Both navs have distinct aria-labels
- Separators not in the HTML
- Arrows have aria-label
- Current page not a link in breadcrumb

Exercises

1. Use an SVG chevron as the separator.
2. Add schema.org BreadcrumbList microdata.
3. Collapse middle crumbs on narrow screens.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 816: Breadcrumbs and pagination for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Add two navigation aids: a breadcrumb trail with CSS-generated separators and a pagination bar with a highlighted current page.

Learning goals

- Use nav with aria-label for secondary navigation
- Generate separators with li + li::before
- Style the current item with [aria-current]

Elements and CSS used

HTML elements	CSS features
nav, ol, li, a	adjacent sibling +, ::before content, attribute selector, min-width, border

Build guide

1. Write the breadcrumb ol inside a nav.
2. Mark the last item with aria-current="page" and no link.
3. Write the pager with previous/next arrows labelled.
4. Add separators with li + li::before so the first has none.
5. Style pager links as boxes.
6. Highlight the current page.

Project 816: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus pendant - Habiba Handmade Jewellery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav aria-label="Breadcrumb">
      <ol class="crumbs">
        <li><a href="index.html">Home</a></li>
        <li><a href="items.html">Items</a></li>
        <li aria-current="page">Lotus pendant</li>
      </ol>
    </nav>
    <h1>Lotus pendant</h1>
    <p>Sterling silver.</p>
    <nav class="pager" aria-label="Pagination">
      <a href="?page=1" aria-label="Previous page">&laquo;</a>
      <a href="?page=1">1</a>
      <a href="?page=2" aria-current="page">2</a>
      <a href="?page=3">3</a>
      <a href="?page=3" aria-label="Next page">&raquo;</a>
    </nav>
  </main>
</body>
</html>
```

Project 816: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.crumbs { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .25rem; font-size: .9rem; }
.crumbs li + li::before { content: "/"; margin: 0 .5rem; color: var(--
muted); }
.crumbs a { color: var(--brand); }
.crumbs [aria-current] { color: var(--muted); }
.pager { display: flex; gap: .25rem; margin-top: 3rem; }
.pager a { min-width: 2.4rem; padding: .5rem; text-align: center;
border: 1px solid var(--line); border-radius: 6px; text-decoration:
```

```
none; color: var(--ink); }
.pager a:hover { background: var(--accent); }
.pager a[aria-current] { background: var(--brand); color: #fff;
border-color: var(--brand); }
```

Project 816 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus pendant - Habiba Handmade Jewellery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav aria-label="Breadcrumb">	A block of navigation links; aria-label names it for screen readers.
<ol class="crumbs">	Ordered (numbered) list; the order matters.
Home	A hyperlink; href gives the destination.
Items	One list item.
<li aria-current="page">Lotus pendant	Tells assistive technology which item is the current page or step.
Lotus pendant	The main heading; only one per page.
Sterling silver.	A paragraph of text.

Line	What it does
<nav class="pager" aria-label="Pagination">	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.

Declaration	What it does
gap: .25rem;	Space between grid or flex items without extra margins.
font-size: .9rem;	Size of the text.
.crumbs li + li::before {	Adjacent sibling combinator: every li that follows another li.
content: "/";	The text or empty string for a pseudo-element.
.crumbs [aria-current] {	Attribute selector: styles the current page or step.
text-align: center;	Centres inline content such as text.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
.pager a:hover {	Applies while the pointer is over the element.
background: var(--accent);	Background colour or image.
border-color: var(--brand);	The line around the element: width, style and colour.

Check your work

- Both navs have distinct aria-labels
- Separators not in the HTML
- Arrows have aria-label
- Current page not a link in breadcrumb

Exercises

1. Use an SVG chevron as the separator.
2. Add schema.org BreadcrumbList microdata.

3. Collapse middle crumbs on narrow screens.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 817: Breadcrumbs and pagination for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 1 | Files: index.html, styles.css

Brief

Add two navigation aids: a breadcrumb trail with CSS-generated separators and a pagination bar with a highlighted current page.

Learning goals

- Use nav with aria-label for secondary navigation
- Generate separators with li + li::before
- Style the current item with [aria-current]

Elements and CSS used

HTML elements	CSS features
nav, ol, li, a	adjacent sibling +, ::before content, attribute selector, min-width, border

Build guide

1. Write the breadcrumb ol inside a nav.
2. Mark the last item with aria-current="page" and no link.
3. Write the pager with previous/next arrows labelled.
4. Add separators with li + li::before so the first has none.
5. Style pager links as boxes.
6. Highlight the current page.

Project 817: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Intro to the wheel - Fayoum Pottery Studio</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav aria-label="Breadcrumb">
      <ol class="crumbs">
        <li><a href="index.html">Home</a></li>
        <li><a href="workshops.html">Workshops</a></li>
        <li aria-current="page">Intro to the wheel</li>
      </ol>
    </nav>
    <h1>Intro to the wheel</h1>
    <p>Three hours, take home a bowl.</p>
    <nav class="pager" aria-label="Pagination">
      <a href="?page=1" aria-label="Previous page">&laquo;</a>
      <a href="?page=1">1</a>
      <a href="?page=2" aria-current="page">2</a>
      <a href="?page=3">3</a>
      <a href="?page=3" aria-label="Next page">&raquo;</a>
    </nav>
  </main>
</body>
</html>
```

Project 817: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.crumbs { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .25rem; font-size: .9rem; }
.crumbs li + li::before { content: "/"; margin: 0 .5rem; color: var(--
muted); }
.crumbs a { color: var(--brand); }
.crumbs [aria-current] { color: var(--muted); }
.pager { display: flex; gap: .25rem; margin-top: 3rem; }
.pager a { min-width: 2.4rem; padding: .5rem; text-align: center;
border: 1px solid var(--line); border-radius: 6px; text-decoration:
```

```
none; color: var(--ink); }
.pager a:hover { background: var(--accent); }
.pager a[aria-current] { background: var(--brand); color: #fff;
border-color: var(--brand); }
```

Project 817 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Intro to the wheel - Fayoum Pottery Studio</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav aria-label="Breadcrumb">	A block of navigation links; aria-label names it for screen readers.
<ol class="crumbs">	Ordered (numbered) list; the order matters.
Home	A hyperlink; href gives the destination.
Workshops	One list item.
<li aria-current="page">Intro to the wheel	Tells assistive technology which item is the current page or step.
Intro to the wheel	The main heading; only one per page.
Three hours, take home a bowl.	A paragraph of text.

Line	What it does
<nav class="pager" aria-label="Pagination">	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.

Declaration	What it does
gap: .25rem;	Space between grid or flex items without extra margins.
font-size: .9rem;	Size of the text.
.crumbs li + li::before {	Adjacent sibling combinator: every li that follows another li.
content: "/";	The text or empty string for a pseudo-element.
.crumbs [aria-current] {	Attribute selector: styles the current page or step.
text-align: center;	Centres inline content such as text.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
.pager a:hover {	Applies while the pointer is over the element.
background: var(--accent);	Background colour or image.
border-color: var(--brand);	The line around the element: width, style and colour.

Check your work

- Both navs have distinct aria-labels
- Separators not in the HTML
- Arrows have aria-label
- Current page not a link in breadcrumb

Exercises

1. Use an SVG chevron as the separator.
2. Add schema.org BreadcrumbList microdata.

3. Collapse middle crumbs on narrow screens.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 818: Breadcrumbs and pagination for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 1 | Files: index.html, styles.css

Brief

Add two navigation aids: a breadcrumb trail with CSS-generated separators and a pagination bar with a highlighted current page.

Learning goals

- Use nav with aria-label for secondary navigation
- Generate separators with li + li::before
- Style the current item with [aria-current]

Elements and CSS used

HTML elements	CSS features
nav, ol, li, a	adjacent sibling +, ::before content, attribute selector, min-width, border

Build guide

1. Write the breadcrumb ol inside a nav.
2. Mark the last item with aria-current="page" and no link.
3. Write the pager with previous/next arrows labelled.
4. Add separators with li + li::before so the first has none.
5. Style pager links as boxes.
6. Highlight the current page.

Project 818: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Haircut and blow-dry - Cleopatra Beauty Salon</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav aria-label="Breadcrumb">
      <ol class="crumbs">
        <li><a href="index.html">Home</a></li>
        <li><a href="treatments.html">Treatments</a></li>
        <li aria-current="page">Haircut and blow-dry</li>
      </ol>
    </nav>
    <h1>Haircut and blow-dry</h1>
    <p>Consultation included.</p>
    <nav class="pager" aria-label="Pagination">
      <a href="?page=1" aria-label="Previous page">&laquo;</a>
      <a href="?page=1">1</a>
      <a href="?page=2" aria-current="page">2</a>
      <a href="?page=3">3</a>
      <a href="?page=3" aria-label="Next page">&raquo;</a>
    </nav>
  </main>
</body>
</html>
```

Project 818: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.crumbs { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .25rem; font-size: .9rem; }
.crumbs li + li::before { content: "/"; margin: 0 .5rem; color: var(--
muted); }
.crumbs a { color: var(--brand); }
.crumbs [aria-current] { color: var(--muted); }
.pager { display: flex; gap: .25rem; margin-top: 3rem; }
.pager a { min-width: 2.4rem; padding: .5rem; text-align: center;
border: 1px solid var(--line); border-radius: 6px; text-decoration:
```

```
none; color: var(--ink); }
.pager a:hover { background: var(--accent); }
.pager a[aria-current] { background: var(--brand); color: #fff;
border-color: var(--brand); }
```

Project 818 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Haircut and blow-dry - Cleopatra Beauty Salon</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav aria-label="Breadcrumb">	A block of navigation links; aria-label names it for screen readers.
<ol class="crumbs">	Ordered (numbered) list; the order matters.
Home	A hyperlink; href gives the destination.
Treatments	One list item.
<li aria-current="page">Haircut and blow-dry	Tells assistive technology which item is the current page or step.

Line	What it does
Haircut and blow-dry	The main heading; only one per page.
Consultation included.	A paragraph of text.
<nav class="pager" aria-label="Pagination">	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .25rem;	Space between grid or flex items without extra margins.
font-size: .9rem;	Size of the text.
.crumbs li + li::before {	Adjacent sibling combinator: every li that follows another li.
content: "/";	The text or empty string for a pseudo-element.
.crumbs [aria-current] {	Attribute selector: styles the current page or step.
text-align: center;	Centres inline content such as text.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
.pager a:hover {	Applies while the pointer is over the element.
background: var(--accent);	Background colour or image.
border-color: var(--brand);	The line around the element: width, style and colour.

Check your work

- Both navs have distinct aria-labels
- Separators not in the HTML
- Arrows have aria-label
- Current page not a link in breadcrumb

Exercises

1. Use an SVG chevron as the separator.
2. Add schema.org BreadcrumbList microdata.
3. Collapse middle crumbs on narrow screens.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 819: Breadcrumbs and pagination for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 1 | Files: index.html, styles.css

Brief

Add two navigation aids: a breadcrumb trail with CSS-generated separators and a pagination bar with a highlighted current page.

Learning goals

- Use nav with aria-label for secondary navigation
- Generate separators with li + li::before
- Style the current item with [aria-current]

Elements and CSS used

HTML elements	CSS features
nav, ol, li, a	adjacent sibling +, ::before content, attribute selector, min-width, border

Build guide

1. Write the breadcrumb ol inside a nav.
2. Mark the last item with aria-current="page" and no link.
3. Write the pager with previous/next arrows labelled.
4. Add separators with li + li::before so the first has none.
5. Style pager links as boxes.
6. Highlight the current page.

Project 819: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oil change - Suez Auto Service</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav aria-label="Breadcrumb">
      <ol class="crumbs">
        <li><a href="index.html">Home</a></li>
        <li><a href="services.html">Services</a></li>
        <li aria-current="page">Oil change</li>
      </ol>
    </nav>
    <h1>Oil change</h1>
    <p>Filter included.</p>
    <nav class="pager" aria-label="Pagination">
      <a href="?page=1" aria-label="Previous page">&laquo;</a>
      <a href="?page=1">1</a>
      <a href="?page=2" aria-current="page">2</a>
      <a href="?page=3">3</a>
      <a href="?page=3" aria-label="Next page">&raquo;</a>
    </nav>
  </main>
</body>
</html>
```

Project 819: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.crumbs { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .25rem; font-size: .9rem; }
.crumbs li + li::before { content: "/"; margin: 0 .5rem; color: var(--
muted); }
.crumbs a { color: var(--brand); }
.crumbs [aria-current] { color: var(--muted); }
.pager { display: flex; gap: .25rem; margin-top: 3rem; }
.pager a { min-width: 2.4rem; padding: .5rem; text-align: center;
border: 1px solid var(--line); border-radius: 6px; text-decoration:
```

```
none; color: var(--ink); }
.pager a:hover { background: var(--accent); }
.pager a[aria-current] { background: var(--brand); color: #fff;
border-color: var(--brand); }
```

Project 819 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oil change - Suez Auto Service</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav aria-label="Breadcrumb">	A block of navigation links; aria-label names it for screen readers.
<ol class="crumbs">	Ordered (numbered) list; the order matters.
Home	A hyperlink; href gives the destination.
Services	One list item.
<li aria-current="page">Oil change	Tells assistive technology which item is the current page or step.
Oil change	The main heading; only one per page.
Filter included.	A paragraph of text.

Line	What it does
<nav class="pager" aria-label="Pagination">	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.

Declaration	What it does
gap: .25rem;	Space between grid or flex items without extra margins.
font-size: .9rem;	Size of the text.
.crumbs li + li::before {	Adjacent sibling combinator: every li that follows another li.
content: "/";	The text or empty string for a pseudo-element.
.crumbs [aria-current] {	Attribute selector: styles the current page or step.
text-align: center;	Centres inline content such as text.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
.pager a:hover {	Applies while the pointer is over the element.
background: var(--accent);	Background colour or image.
border-color: var(--brand);	The line around the element: width, style and colour.

Check your work

- Both navs have distinct aria-labels
- Separators not in the HTML
- Arrows have aria-label
- Current page not a link in breadcrumb

Exercises

1. Use an SVG chevron as the separator.
2. Add schema.org BreadcrumbList microdata.

3. Collapse middle crumbs on narrow screens.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 820: Breadcrumbs and pagination for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 1 | Files: index.html, styles.css

Brief

Add two navigation aids: a breadcrumb trail with CSS-generated separators and a pagination bar with a highlighted current page.

Learning goals

- Use nav with aria-label for secondary navigation
- Generate separators with li + li::before
- Style the current item with [aria-current]

Elements and CSS used

HTML elements	CSS features
nav, ol, li, a	adjacent sibling +, ::before content, attribute selector, min-width, border

Build guide

1. Write the breadcrumb ol inside a nav.
2. Mark the last item with aria-current="page" and no link.
3. Write the pager with previous/next arrows labelled.
4. Add separators with li + li::before so the first has none.
5. Style pager links as boxes.
6. Highlight the current page.

Project 820: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oud for beginners - Luxor Music Academy</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav aria-label="Breadcrumb">
      <ol class="crumbs">
        <li><a href="index.html">Home</a></li>
        <li><a href="courses.html">Courses</a></li>
        <li aria-current="page">Oud for beginners</li>
      </ol>
    </nav>
    <h1>Oud for beginners</h1>
    <p>Eight weekly lessons.</p>
    <nav class="pager" aria-label="Pagination">
      <a href="?page=1" aria-label="Previous page">&laquo;</a>
      <a href="?page=1">1</a>
      <a href="?page=2" aria-current="page">2</a>
      <a href="?page=3">3</a>
      <a href="?page=3" aria-label="Next page">&raquo;</a>
    </nav>
  </main>
</body>
</html>
```

Project 820: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.crumbs { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .25rem; font-size: .9rem; }
.crumbs li + li::before { content: "/"; margin: 0 .5rem; color: var(--
muted); }
.crumbs a { color: var(--brand); }
.crumbs [aria-current] { color: var(--muted); }
.pager { display: flex; gap: .25rem; margin-top: 3rem; }
.pager a { min-width: 2.4rem; padding: .5rem; text-align: center;
border: 1px solid var(--line); border-radius: 6px; text-decoration:
```

```
none; color: var(--ink); }
.pager a:hover { background: var(--accent); }
.pager a[aria-current] { background: var(--brand); color: #fff;
border-color: var(--brand); }
```

Project 820 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oud for beginners - Luxor Music Academy</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav aria-label="Breadcrumb">	A block of navigation links; aria-label names it for screen readers.
<ol class="crumbs">	Ordered (numbered) list; the order matters.
Home	A hyperlink; href gives the destination.
Courses	One list item.
<li aria-current="page">Oud for beginners	Tells assistive technology which item is the current page or step.
Oud for beginners	The main heading; only one per page.
Eight weekly lessons.	A paragraph of text.

Line	What it does
<nav class="pager" aria-label="Pagination">	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.

Declaration	What it does
gap: .25rem;	Space between grid or flex items without extra margins.
font-size: .9rem;	Size of the text.
.crumbs li + li::before {	Adjacent sibling combinator: every li that follows another li.
content: "/";	The text or empty string for a pseudo-element.
.crumbs [aria-current] {	Attribute selector: styles the current page or step.
text-align: center;	Centres inline content such as text.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
.pager a:hover {	Applies while the pointer is over the element.
background: var(--accent);	Background colour or image.
border-color: var(--brand);	The line around the element: width, style and colour.

Check your work

- Both navs have distinct aria-labels
- Separators not in the HTML
- Arrows have aria-label
- Current page not a link in breadcrumb

Exercises

1. Use an SVG chevron as the separator.
2. Add schema.org BreadcrumbList microdata.

3. Collapse middle crumbs on narrow screens.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 821: Breadcrumbs and pagination for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 1 | Files: index.html, styles.css

Brief

Add two navigation aids: a breadcrumb trail with CSS-generated separators and a pagination bar with a highlighted current page.

Learning goals

- Use nav with aria-label for secondary navigation
- Generate separators with li + li::before
- Style the current item with [aria-current]

Elements and CSS used

HTML elements	CSS features
nav, ol, li, a	adjacent sibling +, ::before content, attribute selector, min-width, border

Build guide

1. Write the breadcrumb ol inside a nav.
2. Mark the last item with aria-current="page" and no link.
3. Write the pager with previous/next arrows labelled.
4. Add separators with li + li::before so the first has none.
5. Style pager links as boxes.
6. Highlight the current page.

Project 821: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Grilled sea bass - Port Said Seafood</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav aria-label="Breadcrumb">
      <ol class="crumbs">
        <li><a href="index.html">Home</a></li>
        <li><a href="dishes.html">Dishes</a></li>
        <li aria-current="page">Grilled sea bass</li>
      </ol>
    </nav>
    <h1>Grilled sea bass</h1>
    <p>With rice and salad.</p>
    <nav class="pager" aria-label="Pagination">
      <a href="?page=1" aria-label="Previous page">&laquo;</a>
      <a href="?page=1">1</a>
      <a href="?page=2" aria-current="page">2</a>
      <a href="?page=3">3</a>
      <a href="?page=3" aria-label="Next page">&raquo;</a>
    </nav>
  </main>
</body>
</html>
```

Project 821: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.crumbs { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .25rem; font-size: .9rem; }
.crumbs li + li::before { content: "/"; margin: 0 .5rem; color: var(--
muted); }
.crumbs a { color: var(--brand); }
.crumbs [aria-current] { color: var(--muted); }
.pager { display: flex; gap: .25rem; margin-top: 3rem; }
.pager a { min-width: 2.4rem; padding: .5rem; text-align: center;
border: 1px solid var(--line); border-radius: 6px; text-decoration:
```

```
none; color: var(--ink); }
.pager a:hover { background: var(--accent); }
.pager a[aria-current] { background: var(--brand); color: #fff;
border-color: var(--brand); }
```

Project 821 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Grilled sea bass - Port Said Seafood</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav aria-label="Breadcrumb">	A block of navigation links; aria-label names it for screen readers.
<ol class="crumbs">	Ordered (numbered) list; the order matters.
Home	A hyperlink; href gives the destination.
Dishes	One list item.
<li aria-current="page">Grilled sea bass	Tells assistive technology which item is the current page or step.
Grilled sea bass	The main heading; only one per page.
With rice and salad.	A paragraph of text.

Line	What it does
<nav class="pager" aria-label="Pagination">	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.

Declaration	What it does
gap: .25rem;	Space between grid or flex items without extra margins.
font-size: .9rem;	Size of the text.
.crumbs li + li::before {	Adjacent sibling combinator: every li that follows another li.
content: "/";	The text or empty string for a pseudo-element.
.crumbs [aria-current] {	Attribute selector: styles the current page or step.
text-align: center;	Centres inline content such as text.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
.pager a:hover {	Applies while the pointer is over the element.
background: var(--accent);	Background colour or image.
border-color: var(--brand);	The line around the element: width, style and colour.

Check your work

- Both navs have distinct aria-labels
- Separators not in the HTML
- Arrows have aria-label
- Current page not a link in breadcrumb

Exercises

1. Use an SVG chevron as the separator.
2. Add schema.org BreadcrumbList microdata.

3. Collapse middle crumbs on narrow screens.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 822: Breadcrumbs and pagination for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 1 | Files: index.html, styles.css

Brief

Add two navigation aids: a breadcrumb trail with CSS-generated separators and a pagination bar with a highlighted current page.

Learning goals

- Use nav with aria-label for secondary navigation
- Generate separators with li + li::before
- Style the current item with [aria-current]

Elements and CSS used

HTML elements	CSS features
nav, ol, li, a	adjacent sibling +, ::before content, attribute selector, min-width, border

Build guide

1. Write the breadcrumb ol inside a nav.
2. Mark the last item with aria-current="page" and no link.
3. Write the pager with previous/next arrows labelled.
4. Add separators with li + li::before so the first has none.
5. Style pager links as boxes.
6. Highlight the current page.

Project 822: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Story hour - Delta Kids Library</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav aria-label="Breadcrumb">
      <ol class="crumbs">
        <li><a href="index.html">Home</a></li>
        <li><a href="programmes.html">Programmes</a></li>
        <li aria-current="page">Story hour</li>
      </ol>
    </nav>
    <h1>Story hour</h1>
    <p>Ages 3 to 6, Saturdays.</p>
    <nav class="pager" aria-label="Pagination">
      <a href="?page=1" aria-label="Previous page">&laquo;</a>
      <a href="?page=1">1</a>
      <a href="?page=2" aria-current="page">2</a>
      <a href="?page=3">3</a>
      <a href="?page=3" aria-label="Next page">&raquo;</a>
    </nav>
  </main>
</body>
</html>
```

Project 822: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.crumbs { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .25rem; font-size: .9rem; }
.crumbs li + li::before { content: "/"; margin: 0 .5rem; color: var(--
muted); }
.crumbs a { color: var(--brand); }
.crumbs [aria-current] { color: var(--muted); }
.pager { display: flex; gap: .25rem; margin-top: 3rem; }
.pager a { min-width: 2.4rem; padding: .5rem; text-align: center;
border: 1px solid var(--line); border-radius: 6px; text-decoration:
```

```
none; color: var(--ink); }
.pager a:hover { background: var(--accent); }
.pager a[aria-current] { background: var(--brand); color: #fff;
border-color: var(--brand); }
```

Project 822 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Story hour - Delta Kids Library</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav aria-label="Breadcrumb">	A block of navigation links; aria-label names it for screen readers.
<ol class="crumbs">	Ordered (numbered) list; the order matters.
Home	A hyperlink; href gives the destination.
Programmes	One list item.
<li aria-current="page">Story hour	Tells assistive technology which item is the current page or step.
Story hour	The main heading; only one per page.
Ages 3 to 6, Saturdays.	A paragraph of text.

Line	What it does
<nav class="pager" aria-label="Pagination">	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.

Declaration	What it does
gap: .25rem;	Space between grid or flex items without extra margins.
font-size: .9rem;	Size of the text.
.crumbs li + li::before {	Adjacent sibling combinator: every li that follows another li.
content: "/";	The text or empty string for a pseudo-element.
.crumbs [aria-current] {	Attribute selector: styles the current page or step.
text-align: center;	Centres inline content such as text.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
.pager a:hover {	Applies while the pointer is over the element.
background: var(--accent);	Background colour or image.
border-color: var(--brand);	The line around the element: width, style and colour.

Check your work

- Both navs have distinct aria-labels
- Separators not in the HTML
- Arrows have aria-label
- Current page not a link in breadcrumb

Exercises

1. Use an SVG chevron as the separator.
2. Add schema.org BreadcrumbList microdata.

3. Collapse middle crumbs on narrow screens.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 823: Breadcrumbs and pagination for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Add two navigation aids: a breadcrumb trail with CSS-generated separators and a pagination bar with a highlighted current page.

Learning goals

- Use nav with aria-label for secondary navigation
- Generate separators with li + li::before
- Style the current item with [aria-current]

Elements and CSS used

HTML elements	CSS features
nav, ol, li, a	adjacent sibling +, ::before content, attribute selector, min-width, border

Build guide

1. Write the breadcrumb ol inside a nav.
2. Mark the last item with aria-current="page" and no link.
3. Write the pager with previous/next arrows labelled.
4. Add separators with li + li::before so the first has none.
5. Style pager links as boxes.
6. Highlight the current page.

Project 823: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Garden room - Nubian Guest House</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav aria-label="Breadcrumb">
      <ol class="crumbs">
        <li><a href="index.html">Home</a></li>
        <li><a href="rooms.html">Rooms</a></li>
        <li aria-current="page">Garden room</li>
      </ol>
    </nav>
    <h1>Garden room</h1>
    <p>Double bed, shared terrace.</p>
    <nav class="pager" aria-label="Pagination">
      <a href="?page=1" aria-label="Previous page">&laquo;</a>
      <a href="?page=1">1</a>
      <a href="?page=2" aria-current="page">2</a>
      <a href="?page=3">3</a>
      <a href="?page=3" aria-label="Next page">&raquo;</a>
    </nav>
  </main>
</body>
</html>
```

Project 823: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.crumbs { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .25rem; font-size: .9rem; }
.crumbs li + li::before { content: "/"; margin: 0 .5rem; color: var(--
muted); }
.crumbs a { color: var(--brand); }
.crumbs [aria-current] { color: var(--muted); }
.pager { display: flex; gap: .25rem; margin-top: 3rem; }
.pager a { min-width: 2.4rem; padding: .5rem; text-align: center;
border: 1px solid var(--line); border-radius: 6px; text-decoration:
```

```
none; color: var(--ink); }
.pager a:hover { background: var(--accent); }
.pager a[aria-current] { background: var(--brand); color: #fff;
border-color: var(--brand); }
```

Project 823 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Garden room - Nubian Guest House</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav aria-label="Breadcrumb">	A block of navigation links; aria-label names it for screen readers.
<ol class="crumbs">	Ordered (numbered) list; the order matters.
Home	A hyperlink; href gives the destination.
Rooms	One list item.
<li aria-current="page">Garden room	Tells assistive technology which item is the current page or step.
Garden room	The main heading; only one per page.

Line	What it does
Double bed, shared terrace.	A paragraph of text.
<nav class="pager" aria-label="Pagination">	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
gap: .25rem;	Space between grid or flex items without extra margins.
font-size: .9rem;	Size of the text.
.crumbs li + li::before {	Adjacent sibling combinator: every li that follows another li.
content: "/";	The text or empty string for a pseudo-element.
.crumbs [aria-current] {	Attribute selector: styles the current page or step.
text-align: center;	Centres inline content such as text.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
.pager a:hover {	Applies while the pointer is over the element.
background: var(--accent);	Background colour or image.
border-color: var(--brand);	The line around the element: width, style and colour.

Check your work

- Both navs have distinct aria-labels
- Separators not in the HTML
- Arrows have aria-label
- Current page not a link in breadcrumb

Exercises

1. Use an SVG chevron as the separator.
2. Add schema.org BreadcrumbList microdata.
3. Collapse middle crumbs on narrow screens.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 824: Breadcrumbs and pagination for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 1 | Files: index.html, styles.css

Brief

Add two navigation aids: a breadcrumb trail with CSS-generated separators and a pagination bar with a highlighted current page.

Learning goals

- Use nav with aria-label for secondary navigation
- Generate separators with li + li::before
- Style the current item with [aria-current]

Elements and CSS used

HTML elements	CSS features
nav, ol, li, a	adjacent sibling +, ::before content, attribute selector, min-width, border

Build guide

1. Write the breadcrumb ol inside a nav.
2. Mark the last item with aria-current="page" and no link.
3. Write the pager with previous/next arrows labelled.
4. Add separators with li + li::before so the first has none.
5. Style pager links as boxes.
6. Highlight the current page.

Project 824: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>City bike - Ismailia Cycling Store</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav aria-label="Breadcrumb">
      <ol class="crumbs">
        <li><a href="index.html">Home</a></li>
        <li><a href="bikes.html">Bikes</a></li>
        <li aria-current="page">City bike</li>
      </ol>
    </nav>
    <h1>City bike</h1>
    <p>Seven gears, basket.</p>
    <nav class="pager" aria-label="Pagination">
      <a href="?page=1" aria-label="Previous page">&laquo;</a>
      <a href="?page=1">1</a>
      <a href="?page=2" aria-current="page">2</a>
      <a href="?page=3">3</a>
      <a href="?page=3" aria-label="Next page">&raquo;</a>
    </nav>
  </main>
</body>
</html>
```

Project 824: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.crumbs { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .25rem; font-size: .9rem; }
.crumbs li + li::before { content: "/"; margin: 0 .5rem; color: var(--
muted); }
.crumbs a { color: var(--brand); }
.crumbs [aria-current] { color: var(--muted); }
.pager { display: flex; gap: .25rem; margin-top: 3rem; }
.pager a { min-width: 2.4rem; padding: .5rem; text-align: center;
border: 1px solid var(--line); border-radius: 6px; text-decoration:
```

```
none; color: var(--ink); }
.pager a:hover { background: var(--accent); }
.pager a[aria-current] { background: var(--brand); color: #fff;
border-color: var(--brand); }
```

Project 824 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>City bike - Ismailia Cycling Store</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav aria-label="Breadcrumb">	A block of navigation links; aria-label names it for screen readers.
<ol class="crumbs">	Ordered (numbered) list; the order matters.
Home	A hyperlink; href gives the destination.
Bikes	One list item.
<li aria-current="page">City bike	Tells assistive technology which item is the current page or step.
City bike	The main heading; only one per page.
Seven gears, basket.	A paragraph of text.

Line	What it does
<nav class="pager" aria-label="Pagination">	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.

Declaration	What it does
gap: .25rem;	Space between grid or flex items without extra margins.
font-size: .9rem;	Size of the text.
.crumbs li + li::before {	Adjacent sibling combinator: every li that follows another li.
content: "/";	The text or empty string for a pseudo-element.
.crumbs [aria-current] {	Attribute selector: styles the current page or step.
text-align: center;	Centres inline content such as text.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
.pager a:hover {	Applies while the pointer is over the element.
background: var(--accent);	Background colour or image.
border-color: var(--brand);	The line around the element: width, style and colour.

Check your work

- Both navs have distinct aria-labels
- Separators not in the HTML
- Arrows have aria-label
- Current page not a link in breadcrumb

Exercises

1. Use an SVG chevron as the separator.
2. Add schema.org BreadcrumbList microdata.

3. Collapse middle crumbs on narrow screens.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 825: Breadcrumbs and pagination for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 1 | Files: index.html, styles.css

Brief

Add two navigation aids: a breadcrumb trail with CSS-generated separators and a pagination bar with a highlighted current page.

Learning goals

- Use nav with aria-label for secondary navigation
- Generate separators with li + li::before
- Style the current item with [aria-current]

Elements and CSS used

HTML elements	CSS features
nav, ol, li, a	adjacent sibling +, ::before content, attribute selector, min-width, border

Build guide

1. Write the breadcrumb ol inside a nav.
2. Mark the last item with aria-current="page" and no link.
3. Write the pager with previous/next arrows labelled.
4. Add separators with li + li::before so the first has none.
5. Style pager links as boxes.
6. Highlight the current page.

Project 825: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>HTML weekend - Minya Coding Club</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav aria-label="Breadcrumb">
      <ol class="crumbs">
        <li><a href="index.html">Home</a></li>
        <li><a href="workshops.html">Workshops</a></li>
        <li aria-current="page">HTML weekend</li>
      </ol>
    </nav>
    <h1>HTML weekend</h1>
    <p>Build your first page.</p>
    <nav class="pager" aria-label="Pagination">
      <a href="?page=1" aria-label="Previous page">&laquo;</a>
      <a href="?page=1">1</a>
      <a href="?page=2" aria-current="page">2</a>
      <a href="?page=3">3</a>
      <a href="?page=3" aria-label="Next page">&raquo;</a>
    </nav>
  </main>
</body>
</html>
```

Project 825: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.crumbs { list-style: none; padding: 0; display: flex; flex-wrap:
wrap; gap: .25rem; font-size: .9rem; }
.crumbs li + li::before { content: "/"; margin: 0 .5rem; color: var(--
muted); }
.crumbs a { color: var(--brand); }
.crumbs [aria-current] { color: var(--muted); }
.pager { display: flex; gap: .25rem; margin-top: 3rem; }
.pager a { min-width: 2.4rem; padding: .5rem; text-align: center;
border: 1px solid var(--line); border-radius: 6px; text-decoration:
```

```
none; color: var(--ink); }
.pager a:hover { background: var(--accent); }
.pager a[aria-current] { background: var(--brand); color: #fff;
border-color: var(--brand); }
```

Project 825 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>HTML weekend - Minya Coding Club</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav aria-label="Breadcrumb">	A block of navigation links; aria-label names it for screen readers.
<ol class="crumbs">	Ordered (numbered) list; the order matters.
Home	A hyperlink; href gives the destination.
Workshops	One list item.
<li aria-current="page">HTML weekend	Tells assistive technology which item is the current page or step.
HTML weekend	The main heading; only one per page.
Build your first page.	A paragraph of text.

Line	What it does
<nav class="pager" aria-label="Pagination">	Accessible name for an element that has no visible text.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
list-style: none;	Removes bullets or numbers from a list.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.

Declaration	What it does
gap: .25rem;	Space between grid or flex items without extra margins.
font-size: .9rem;	Size of the text.
.crumbs li + li::before {	Adjacent sibling combinator: every li that follows another li.
content: "/";	The text or empty string for a pseudo-element.
.crumbs [aria-current] {	Attribute selector: styles the current page or step.
text-align: center;	Centres inline content such as text.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
.pager a:hover {	Applies while the pointer is over the element.
background: var(--accent);	Background colour or image.
border-color: var(--brand);	The line around the element: width, style and colour.

Check your work

- Both navs have distinct aria-labels
- Separators not in the HTML
- Arrows have aria-label
- Current page not a link in breadcrumb

Exercises

1. Use an SVG chevron as the separator.
2. Add schema.org BreadcrumbList microdata.

3. Collapse middle crumbs on narrow screens.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Alert message components

Level 1 | 25 projects, one per theme

Create four message styles (info, success, warning, error) with colour, a thick left border and a text prefix so meaning does not rely on colour alone.

Project 826: Alert message components for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 1 | Files: index.html, styles.css

Brief

Create four message styles (info, success, warning, error) with colour, a thick left border and a text prefix so meaning does not rely on colour alone.

Learning goals

- Build reusable component classes
- Use role=status and role=alert
- Use border shorthand then override one side

Elements and CSS used

HTML elements	CSS features
p, strong	border: 1px solid, border-left-width, border-color, background, class modifiers

Build guide

1. Write four paragraphs with the shared class alert and a modifier class.
2. Prefix each with a strong label.
3. Add role attributes.
4. Style .alert once with padding, radius and a 1px border.
5. Set border-left-width: 6px.
6. Set colours per modifier.

Project 826: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Messages</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Message styles</h1>
    <p class="alert info" role="status"><strong>Info:</strong> Cairo
Book Shop opens at 10:00 on Fridays.</p>
    <p class="alert success" role="status"><strong>Success:</strong>
Your book has been booked.</p>
    <p class="alert warning" role="alert"><strong>Warning:</strong>
Only two books left this week.</p>
    <p class="alert error" role="alert"><strong>Error:</strong> The
email address is not valid.</p>
  </main>
</body>
</html>
```

Project 826: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; display:
grid; gap: 1rem; }
.alert { margin: 0; padding: .9rem 1.1rem; border-radius: 10px;
border: 1px solid; border-left-width: 6px; }
.info    { background: #eff6ff; border-color: #60a5fa; color: #1e3a8a;
 }
.success { background: #f0fdf4; border-color: #4ade80; color: #14532d;
 }
.warning { background: #fffbeb; border-color: #fbbf24; color: #78350f;
 }
.error   { background: #fef2f2; border-color: #f87171; color: #7f1d1d;
 }
```

Project 826 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - Messages</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Message styles	The main heading; only one per page.
<p class="alert info" role="status">Info: Cairo Bo...	A paragraph of text.
<p class="alert success" role="status">Success: Yo...	Strong importance (bold by default).
<p class="alert warning" role="alert">Warning: Onl...	Gives the element an ARIA role for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
border-radius: 10px;	Rounds the corners.
border: 1px solid;	Changes the visual order of a flex item without changing the source.
border-left-width: 6px;	A thick left border used as an accent stripe.
background: #eff6ff;	Background colour or image.
border-color: #60a5fa;	The line around the element: width, style and colour.

Check your work

- Each message has a text label
- Contrast passes for all four
- Shared styles in one rule
- role used correctly

Exercises

1. Add a close button that hides the alert with JavaScript.
2. Add icons with ::before.
3. Add a dark mode variant.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 827: Alert message components for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 1 | Files: index.html, styles.css

Brief

Create four message styles (info, success, warning, error) with colour, a thick left border and a text prefix so meaning does not rely on colour alone.

Learning goals

- Build reusable component classes
- Use role=status and role=alert
- Use border shorthand then override one side

Elements and CSS used

HTML elements	CSS features
p, strong	border: 1px solid, border-left-width, border-color, background, class modifiers

Build guide

1. Write four paragraphs with the shared class alert and a modifier class.
2. Prefix each with a strong label.
3. Add role attributes.
4. Style .alert once with padding, radius and a 1px border.
5. Set border-left-width: 6px.
6. Set colours per modifier.

Project 827: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - Messages</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Message styles</h1>
    <p class="alert info" role="status"><strong>Info:</strong> Nile
Bakery opens at 10:00 on Fridays.</p>
    <p class="alert success" role="status"><strong>Success:</strong>
Your pastry has been booked.</p>
    <p class="alert warning" role="alert"><strong>Warning:</strong>
Only two pastries left this week.</p>
    <p class="alert error" role="alert"><strong>Error:</strong> The
email address is not valid.</p>
  </main>
</body>
</html>
```

Project 827: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; display:
grid; gap: 1rem; }
.alert { margin: 0; padding: .9rem 1.1rem; border-radius: 10px;
border: 1px solid; border-left-width: 6px; }
.info    { background: #eff6ff; border-color: #60a5fa; color: #1e3a8a;
 }
.success { background: #f0fdf4; border-color: #4ade80; color: #14532d;
 }
.warning { background: #fffbeb; border-color: #fbbf24; color: #78350f;
 }
.error   { background: #fef2f2; border-color: #f87171; color: #7f1d1d;
 }
```

Project 827 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - Messages</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Message styles	The main heading; only one per page.
<p class="alert info" role="status">Info: Nile Bak...	A paragraph of text.
<p class="alert success" role="status">Success: Yo...	Strong importance (bold by default).
<p class="alert warning" role="alert">Warning: Onl...	Gives the element an ARIA role for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
border-radius: 10px;	Rounds the corners.
border: 1px solid;	Changes the visual order of a flex item without changing the source.
border-left-width: 6px;	A thick left border used as an accent stripe.
background: #eff6ff;	Background colour or image.
border-color: #60a5fa;	The line around the element: width, style and colour.

Check your work

- Each message has a text label
- Contrast passes for all four
- Shared styles in one rule
- role used correctly

Exercises

1. Add a close button that hides the alert with JavaScript.
2. Add icons with ::before.
3. Add a dark mode variant.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 828: Alert message components for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 1 | Files: index.html, styles.css

Brief

Create four message styles (info, success, warning, error) with colour, a thick left border and a text prefix so meaning does not rely on colour alone.

Learning goals

- Build reusable component classes
- Use role=status and role=alert
- Use border shorthand then override one side

Elements and CSS used

HTML elements	CSS features
p, strong	border: 1px solid, border-left-width, border-color, background, class modifiers

Build guide

1. Write four paragraphs with the shared class alert and a modifier class.
2. Prefix each with a strong label.
3. Add role attributes.
4. Style .alert once with padding, radius and a 1px border.
5. Set border-left-width: 6px.

6. Set colours per modifier.

Project 828: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - Messages</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Message styles</h1>
    <p class="alert info" role="status"><strong>Info:</strong>
Pyramid Fitness opens at 10:00 on Fridays.</p>
    <p class="alert success" role="status"><strong>Success:</strong>
Your class has been booked.</p>
    <p class="alert warning" role="alert"><strong>Warning:</strong>
Only two classes left this week.</p>
    <p class="alert error" role="alert"><strong>Error:</strong> The
email address is not valid.</p>
  </main>
</body>
</html>
```

Project 828: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; display:
grid; gap: 1rem; }
.alert { margin: 0; padding: .9rem 1.1rem; border-radius: 10px;
border: 1px solid; border-left-width: 6px; }
.info    { background: #eff6ff; border-color: #60a5fa; color: #1e3a8a;
 }
.success { background: #f0fdf4; border-color: #4ade80; color: #14532d;
 }
.warning { background: #fffbeb; border-color: #fbbf24; color: #78350f;
 }
.error   { background: #fef2f2; border-color: #f87171; color: #7f1d1d;
 }
```

Project 828 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - Messages</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Message styles	The main heading; only one per page.
<p class="alert info" role="status">Info: Pyramid ...	A paragraph of text.
<p class="alert success" role="status">Success: Yo...	Strong importance (bold by default).
<p class="alert warning" role="alert">Warning: Onl...	Gives the element an ARIA role for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
border-radius: 10px;	Rounds the corners.
border: 1px solid;	Changes the visual order of a flex item without changing the source.
border-left-width: 6px;	A thick left border used as an accent stripe.
background: #eff6ff;	Background colour or image.
border-color: #60a5fa;	The line around the element: width, style and colour.

Check your work

- Each message has a text label
- Contrast passes for all four
- Shared styles in one rule
- role used correctly

Exercises

1. Add a close button that hides the alert with JavaScript.
2. Add icons with ::before.
3. Add a dark mode variant.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 829: Alert message components for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 1 | Files: index.html, styles.css

Brief

Create four message styles (info, success, warning, error) with colour, a thick left border and a text prefix so meaning does not rely on colour alone.

Learning goals

- Build reusable component classes
- Use role=status and role=alert
- Use border shorthand then override one side

Elements and CSS used

HTML elements	CSS features
p, strong	border: 1px solid, border-left-width, border-color, background, class modifiers

Build guide

1. Write four paragraphs with the shared class alert and a modifier class.
2. Prefix each with a strong label.
3. Add role attributes.
4. Style .alert once with padding, radius and a 1px border.
5. Set border-left-width: 6px.
6. Set colours per modifier.

Project 829: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - Messages</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Message styles</h1>
    <p class="alert info" role="status"><strong>Info:</strong> Delta
Dental Clinic opens at 10:00 on Fridays.</p>
    <p class="alert success" role="status"><strong>Success:</strong>
Your service has been booked.</p>
    <p class="alert warning" role="alert"><strong>Warning:</strong>
Only two services left this week.</p>
    <p class="alert error" role="alert"><strong>Error:</strong> The
email address is not valid.</p>
  </main>
</body>
</html>
```

Project 829: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; display:
grid; gap: 1rem; }
.alert { margin: 0; padding: .9rem 1.1rem; border-radius: 10px;
border: 1px solid; border-left-width: 6px; }
.info    { background: #eff6ff; border-color: #60a5fa; color: #1e3a8a;
 }
.success { background: #f0fdf4; border-color: #4ade80; color: #14532d;
 }
.warning { background: #fffbeb; border-color: #fbbf24; color: #78350f;
 }
.error   { background: #fef2f2; border-color: #f87171; color: #7f1d1d;
 }
```

Project 829 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - Messages</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Message styles	The main heading; only one per page.
<p class="alert info" role="status">Info: Delta De...	A paragraph of text.
<p class="alert success" role="status">Success: Yo...	Strong importance (bold by default).
<p class="alert warning" role="alert">Warning: Onl...	Gives the element an ARIA role for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
border-radius: 10px;	Rounds the corners.
border: 1px solid;	Changes the visual order of a flex item without changing the source.
border-left-width: 6px;	A thick left border used as an accent stripe.
background: #eff6ff;	Background colour or image.
border-color: #60a5fa;	The line around the element: width, style and colour.

Check your work

- Each message has a text label
- Contrast passes for all four
- Shared styles in one rule
- role used correctly

Exercises

1. Add a close button that hides the alert with JavaScript.
2. Add icons with ::before.
3. Add a dark mode variant.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 830: Alert message components for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 1 | Files: index.html, styles.css

Brief

Create four message styles (info, success, warning, error) with colour, a thick left border and a text prefix so meaning does not rely on colour alone.

Learning goals

- Build reusable component classes
- Use role=status and role=alert
- Use border shorthand then override one side

Elements and CSS used

HTML elements	CSS features
p, strong	border: 1px solid, border-left-width, border-color, background, class modifiers

Build guide

1. Write four paragraphs with the shared class alert and a modifier class.
2. Prefix each with a strong label.
3. Add role attributes.
4. Style .alert once with padding, radius and a 1px border.
5. Set border-left-width: 6px.
6. Set colours per modifier.

Project 830: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - Messages</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Message styles</h1>
    <p class="alert info" role="status"><strong>Info:</strong> Red
Sea Travel opens at 10:00 on Fridays.</p>
    <p class="alert success" role="status"><strong>Success:</strong>
Your tour has been booked.</p>
    <p class="alert warning" role="alert"><strong>Warning:</strong>
Only two tours left this week.</p>
    <p class="alert error" role="alert"><strong>Error:</strong> The
email address is not valid.</p>
  </main>
</body>
</html>
```

Project 830: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; display:
grid; gap: 1rem; }
.alert { margin: 0; padding: .9rem 1.1rem; border-radius: 10px;
border: 1px solid; border-left-width: 6px; }
.info    { background: #eff6ff; border-color: #60a5fa; color: #1e3a8a;
 }
.success { background: #f0fdf4; border-color: #4ade80; color: #14532d;
 }
.warning { background: #fffbeb; border-color: #fbbf24; color: #78350f;
 }
.error   { background: #fef2f2; border-color: #f87171; color: #7f1d1d;
 }
```

Project 830 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - Messages</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Message styles	The main heading; only one per page.
<p class="alert info" role="status">Info: Red Sea ...	A paragraph of text.
<p class="alert success" role="status">Success: Yo...	Strong importance (bold by default).
<p class="alert warning" role="alert">Warning: Onl...	Gives the element an ARIA role for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
border-radius: 10px;	Rounds the corners.
border: 1px solid;	Changes the visual order of a flex item without changing the source.
border-left-width: 6px;	A thick left border used as an accent stripe.
background: #eff6ff;	Background colour or image.
border-color: #60a5fa;	The line around the element: width, style and colour.

Check your work

- Each message has a text label
- Contrast passes for all four
- Shared styles in one rule
- role used correctly

Exercises

1. Add a close button that hides the alert with JavaScript.
2. Add icons with ::before.
3. Add a dark mode variant.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 831: Alert message components for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Create four message styles (info, success, warning, error) with colour, a thick left border and a text prefix so meaning does not rely on colour alone.

Learning goals

- Build reusable component classes
- Use role=status and role=alert
- Use border shorthand then override one side

Elements and CSS used

HTML elements	CSS features
p, strong	border: 1px solid, border-left-width, border-color, background, class modifiers

Build guide

1. Write four paragraphs with the shared class alert and a modifier class.
2. Prefix each with a strong label.
3. Add role attributes.
4. Style .alert once with padding, radius and a 1px border.
5. Set border-left-width: 6px.

6. Set colours per modifier.

Project 831: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - Messages</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Message styles</h1>
    <p class="alert info" role="status"><strong>Info:</strong> Lotus
Language School opens at 10:00 on Fridays.</p>
    <p class="alert success" role="status"><strong>Success:</strong>
Your course has been booked.</p>
    <p class="alert warning" role="alert"><strong>Warning:</strong>
Only two courses left this week.</p>
    <p class="alert error" role="alert"><strong>Error:</strong> The
email address is not valid.</p>
  </main>
</body>
</html>
```

Project 831: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; display:
grid; gap: 1rem; }
.alert { margin: 0; padding: .9rem 1.1rem; border-radius: 10px;
border: 1px solid; border-left-width: 6px; }
.info    { background: #eff6ff; border-color: #60a5fa; color: #1e3a8a;
 }
.success { background: #f0fdf4; border-color: #4ade80; color: #14532d;
 }
.warning { background: #fffbeb; border-color: #fbbf24; color: #78350f;
 }
.error   { background: #fef2f2; border-color: #f87171; color: #7f1d1d;
 }
```

Project 831 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - Messages</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Message styles	The main heading; only one per page.
<p class="alert info" role="status">Info: Lotus La...	A paragraph of text.
<p class="alert success" role="status">Success: Yo...	Strong importance (bold by default).
<p class="alert warning" role="alert">Warning: Onl...	Gives the element an ARIA role for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
border-radius: 10px;	Rounds the corners.
border: 1px solid;	Changes the visual order of a flex item without changing the source.
border-left-width: 6px;	A thick left border used as an accent stripe.
background: #eff6ff;	Background colour or image.
border-color: #60a5fa;	The line around the element: width, style and colour.

Check your work

- Each message has a text label
- Contrast passes for all four
- Shared styles in one rule
- role used correctly

Exercises

1. Add a close button that hides the alert with JavaScript.
2. Add icons with ::before.
3. Add a dark mode variant.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 832: Alert message components for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 1 | Files: index.html, styles.css

Brief

Create four message styles (info, success, warning, error) with colour, a thick left border and a text prefix so meaning does not rely on colour alone.

Learning goals

- Build reusable component classes
- Use role=status and role=alert
- Use border shorthand then override one side

Elements and CSS used

HTML elements	CSS features
p, strong	border: 1px solid, border-left-width, border-color, background, class modifiers

Build guide

1. Write four paragraphs with the shared class alert and a modifier class.
2. Prefix each with a strong label.
3. Add role attributes.
4. Style .alert once with padding, radius and a 1px border.
5. Set border-left-width: 6px.
6. Set colours per modifier.

Project 832: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - Messages</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Message styles</h1>
    <p class="alert info" role="status"><strong>Info:</strong> Green
Leaf Cafe opens at 10:00 on Fridays.</p>
    <p class="alert success" role="status"><strong>Success:</strong>
Your drink has been booked.</p>
    <p class="alert warning" role="alert"><strong>Warning:</strong>
Only two drinks left this week.</p>
    <p class="alert error" role="alert"><strong>Error:</strong> The
email address is not valid.</p>
  </main>
</body>
</html>
```

Project 832: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; display:
grid; gap: 1rem; }
.alert { margin: 0; padding: .9rem 1.1rem; border-radius: 10px;
border: 1px solid; border-left-width: 6px; }
.info    { background: #eff6ff; border-color: #60a5fa; color: #1e3a8a;
 }
.success { background: #f0fdf4; border-color: #4ade80; color: #14532d;
 }
.warning { background: #fffbeb; border-color: #fbbf24; color: #78350f;
 }
.error   { background: #fef2f2; border-color: #f87171; color: #7f1d1d;
 }
```

Project 832 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - Messages</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Message styles	The main heading; only one per page.
<p class="alert info" role="status">Info: Green Le...	A paragraph of text.
<p class="alert success" role="status">Success: Yo...	Strong importance (bold by default).
<p class="alert warning" role="alert">Warning: Onl...	Gives the element an ARIA role for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
border-radius: 10px;	Rounds the corners.
border: 1px solid;	Changes the visual order of a flex item without changing the source.
border-left-width: 6px;	A thick left border used as an accent stripe.
background: #eff6ff;	Background colour or image.
border-color: #60a5fa;	The line around the element: width, style and colour.

Check your work

- Each message has a text label
- Contrast passes for all four
- Shared styles in one rule
- role used correctly

Exercises

1. Add a close button that hides the alert with JavaScript.
2. Add icons with ::before.
3. Add a dark mode variant.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 833: Alert message components for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 1 | Files: index.html, styles.css

Brief

Create four message styles (info, success, warning, error) with colour, a thick left border and a text prefix so meaning does not rely on colour alone.

Learning goals

- Build reusable component classes
- Use role=status and role=alert
- Use border shorthand then override one side

Elements and CSS used

HTML elements	CSS features
p, strong	border: 1px solid, border-left-width, border-color, background, class modifiers

Build guide

1. Write four paragraphs with the shared class alert and a modifier class.
2. Prefix each with a strong label.
3. Add role attributes.
4. Style .alert once with padding, radius and a 1px border.
5. Set border-left-width: 6px.

6. Set colours per modifier.

Project 833: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - Messages</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Message styles</h1>
    <p class="alert info" role="status"><strong>Info:</strong> Sinai
Trekking Club opens at 10:00 on Fridays.</p>
    <p class="alert success" role="status"><strong>Success:</strong>
Your hike has been booked.</p>
    <p class="alert warning" role="alert"><strong>Warning:</strong>
Only two hikes left this week.</p>
    <p class="alert error" role="alert"><strong>Error:</strong> The
email address is not valid.</p>
  </main>
</body>
</html>
```

Project 833: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; display:
grid; gap: 1rem; }
.alert { margin: 0; padding: .9rem 1.1rem; border-radius: 10px;
border: 1px solid; border-left-width: 6px; }
.info    { background: #eff6ff; border-color: #60a5fa; color: #1e3a8a;
 }
.success { background: #f0fdf4; border-color: #4ade80; color: #14532d;
 }
.warning { background: #fffbeb; border-color: #fbbf24; color: #78350f;
 }
.error   { background: #fef2f2; border-color: #f87171; color: #7f1d1d;
 }
```

Project 833 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - Messages</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Message styles	The main heading; only one per page.
<p class="alert info" role="status">Info: Sinai Tr...	A paragraph of text.
<p class="alert success" role="status">Success: Yo...	Strong importance (bold by default).
<p class="alert warning" role="alert">Warning: Onl...	Gives the element an ARIA role for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
border-radius: 10px;	Rounds the corners.
border: 1px solid;	Changes the visual order of a flex item without changing the source.
border-left-width: 6px;	A thick left border used as an accent stripe.
background: #eff6ff;	Background colour or image.
border-color: #60a5fa;	The line around the element: width, style and colour.

Check your work

- Each message has a text label
- Contrast passes for all four
- Shared styles in one rule
- role used correctly

Exercises

1. Add a close button that hides the alert with JavaScript.
2. Add icons with ::before.
3. Add a dark mode variant.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 834: Alert message components for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 1 | Files: index.html, styles.css

Brief

Create four message styles (info, success, warning, error) with colour, a thick left border and a text prefix so meaning does not rely on colour alone.

Learning goals

- Build reusable component classes
- Use role=status and role=alert
- Use border shorthand then override one side

Elements and CSS used

HTML elements	CSS features
p, strong	border: 1px solid, border-left-width, border-color, background, class modifiers

Build guide

1. Write four paragraphs with the shared class alert and a modifier class.
2. Prefix each with a strong label.
3. Add role attributes.
4. Style .alert once with padding, radius and a 1px border.
5. Set border-left-width: 6px.
6. Set colours per modifier.

Project 834: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - Messages</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Message styles</h1>
    <p class="alert info" role="status"><strong>Info:</strong>
Horizon Photography opens at 10:00 on Fridays.</p>
    <p class="alert success" role="status"><strong>Success:</strong>
Your session has been booked.</p>
    <p class="alert warning" role="alert"><strong>Warning:</strong>
Only two sessions left this week.</p>
    <p class="alert error" role="alert"><strong>Error:</strong> The
email address is not valid.</p>
  </main>
</body>
</html>
```

Project 834: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; display:
grid; gap: 1rem; }
.alert { margin: 0; padding: .9rem 1.1rem; border-radius: 10px;
border: 1px solid; border-left-width: 6px; }
.info    { background: #eff6ff; border-color: #60a5fa; color: #1e3a8a;
 }
.success { background: #f0fdf4; border-color: #4ade80; color: #14532d;
 }
.warning { background: #fffbeb; border-color: #fbbf24; color: #78350f;
 }
.error   { background: #fef2f2; border-color: #f87171; color: #7f1d1d;
 }
```

Project 834 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - Messages</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Message styles	The main heading; only one per page.
<p class="alert info" role="status">Info: Horizon ...	A paragraph of text.
<p class="alert success" role="status">Success: Yo...	Strong importance (bold by default).
<p class="alert warning" role="alert">Warning: Onl...	Gives the element an ARIA role for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
border-radius: 10px;	Rounds the corners.
border: 1px solid;	Changes the visual order of a flex item without changing the source.
border-left-width: 6px;	A thick left border used as an accent stripe.
background: #eff6ff;	Background colour or image.
border-color: #60a5fa;	The line around the element: width, style and colour.

Check your work

- Each message has a text label
- Contrast passes for all four
- Shared styles in one rule
- role used correctly

Exercises

1. Add a close button that hides the alert with JavaScript.
2. Add icons with ::before.
3. Add a dark mode variant.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 835: Alert message components for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 1 | Files: index.html, styles.css

Brief

Create four message styles (info, success, warning, error) with colour, a thick left border and a text prefix so meaning does not rely on colour alone.

Learning goals

- Build reusable component classes
- Use role=status and role=alert
- Use border shorthand then override one side

Elements and CSS used

HTML elements	CSS features
p, strong	border: 1px solid, border-left-width, border-color, background, class modifiers

Build guide

1. Write four paragraphs with the shared class alert and a modifier class.
2. Prefix each with a strong label.
3. Add role attributes.
4. Style .alert once with padding, radius and a 1px border.
5. Set border-left-width: 6px.
6. Set colours per modifier.

Project 835: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - Messages</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Message styles</h1>
    <p class="alert info" role="status"><strong>Info:</strong>
Papyrus Stationery opens at 10:00 on Fridays.</p>
    <p class="alert success" role="status"><strong>Success:</strong>
Your product has been booked.</p>
    <p class="alert warning" role="alert"><strong>Warning:</strong>
Only two products left this week.</p>
    <p class="alert error" role="alert"><strong>Error:</strong> The
email address is not valid.</p>
  </main>
</body>
</html>
```

Project 835: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; display:
grid; gap: 1rem; }
.alert { margin: 0; padding: .9rem 1.1rem; border-radius: 10px;
border: 1px solid; border-left-width: 6px; }
.info    { background: #eff6ff; border-color: #60a5fa; color: #1e3a8a;
 }
.success { background: #f0fdf4; border-color: #4ade80; color: #14532d;
 }
.warning { background: #fffbeb; border-color: #fbbf24; color: #78350f;
 }
.error   { background: #fef2f2; border-color: #f87171; color: #7f1d1d;
 }
```

Project 835 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - Messages</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Message styles	The main heading; only one per page.
<p class="alert info" role="status">Info: Papyrus ...	A paragraph of text.
<p class="alert success" role="status">Success: Yo...	Strong importance (bold by default).
<p class="alert warning" role="alert">Warning: Onl...	Gives the element an ARIA role for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
border-radius: 10px;	Rounds the corners.
border: 1px solid;	Changes the visual order of a flex item without changing the source.
border-left-width: 6px;	A thick left border used as an accent stripe.
background: #eff6ff;	Background colour or image.
border-color: #60a5fa;	The line around the element: width, style and colour.

Check your work

- Each message has a text label
- Contrast passes for all four
- Shared styles in one rule
- role used correctly

Exercises

1. Add a close button that hides the alert with JavaScript.
2. Add icons with ::before.
3. Add a dark mode variant.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 836: Alert message components for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 1 | Files: index.html, styles.css

Brief

Create four message styles (info, success, warning, error) with colour, a thick left border and a text prefix so meaning does not rely on colour alone.

Learning goals

- Build reusable component classes
- Use role=status and role=alert
- Use border shorthand then override one side

Elements and CSS used

HTML elements	CSS features
p, strong	border: 1px solid, border-left-width, border-color, background, class modifiers

Build guide

1. Write four paragraphs with the shared class alert and a modifier class.
2. Prefix each with a strong label.
3. Add role attributes.
4. Style .alert once with padding, radius and a 1px border.
5. Set border-left-width: 6px.

6. Set colours per modifier.

Project 836: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - Messages</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Message styles</h1>
    <p class="alert info" role="status"><strong>Info:</strong> Oasis
Plant Nursery opens at 10:00 on Fridays.</p>
    <p class="alert success" role="status"><strong>Success:</strong>
Your plant has been booked.</p>
    <p class="alert warning" role="alert"><strong>Warning:</strong>
Only two plants left this week.</p>
    <p class="alert error" role="alert"><strong>Error:</strong> The
email address is not valid.</p>
  </main>
</body>
</html>
```

Project 836: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; display:
grid; gap: 1rem; }
.alert { margin: 0; padding: .9rem 1.1rem; border-radius: 10px;
border: 1px solid; border-left-width: 6px; }
.info    { background: #eff6ff; border-color: #60a5fa; color: #1e3a8a;
 }
.success { background: #f0fdf4; border-color: #4ade80; color: #14532d;
 }
.warning { background: #fffbeb; border-color: #fbbf24; color: #78350f;
 }
.error   { background: #fef2f2; border-color: #f87171; color: #7f1d1d;
 }
```

Project 836 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - Messages</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Message styles	The main heading; only one per page.
<p class="alert info" role="status">Info: Oasis Pl...	A paragraph of text.
<p class="alert success" role="status">Success: Yo...	Strong importance (bold by default).
<p class="alert warning" role="alert">Warning: Onl...	Gives the element an ARIA role for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
border-radius: 10px;	Rounds the corners.
border: 1px solid;	Changes the visual order of a flex item without changing the source.
border-left-width: 6px;	A thick left border used as an accent stripe.
background: #eff6ff;	Background colour or image.
border-color: #60a5fa;	The line around the element: width, style and colour.

Check your work

- Each message has a text label
- Contrast passes for all four
- Shared styles in one rule
- role used correctly

Exercises

1. Add a close button that hides the alert with JavaScript.
2. Add icons with ::before.
3. Add a dark mode variant.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 837: Alert message components for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 1 | Files: index.html, styles.css

Brief

Create four message styles (info, success, warning, error) with colour, a thick left border and a text prefix so meaning does not rely on colour alone.

Learning goals

- Build reusable component classes
- Use role=status and role=alert
- Use border shorthand then override one side

Elements and CSS used

HTML elements	CSS features
p, strong	border: 1px solid, border-left-width, border-color, background, class modifiers

Build guide

1. Write four paragraphs with the shared class alert and a modifier class.
2. Prefix each with a strong label.
3. Add role attributes.
4. Style .alert once with padding, radius and a 1px border.
5. Set border-left-width: 6px.
6. Set colours per modifier.

Project 837: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - Messages</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Message styles</h1>
    <p class="alert info" role="status"><strong>Info:</strong> Cedar
Furniture opens at 10:00 on Fridays.</p>
    <p class="alert success" role="status"><strong>Success:</strong>
Your piece has been booked.</p>
    <p class="alert warning" role="alert"><strong>Warning:</strong>
Only two pieces left this week.</p>
    <p class="alert error" role="alert"><strong>Error:</strong> The
email address is not valid.</p>
  </main>
</body>
</html>
```

Project 837: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; display:
grid; gap: 1rem; }
.alert { margin: 0; padding: .9rem 1.1rem; border-radius: 10px;
border: 1px solid; border-left-width: 6px; }
.info    { background: #eff6ff; border-color: #60a5fa; color: #1e3a8a;
 }
.success { background: #f0fdf4; border-color: #4ade80; color: #14532d;
 }
.warning { background: #fffbeb; border-color: #fbbf24; color: #78350f;
 }
.error   { background: #fef2f2; border-color: #f87171; color: #7f1d1d;
 }
```

Project 837 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - Messages</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Message styles	The main heading; only one per page.
<p class="alert info" role="status">Info: Cedar Fu...	A paragraph of text.
<p class="alert success" role="status">Success: Yo...	Strong importance (bold by default).
<p class="alert warning" role="alert">Warning: Onl...	Gives the element an ARIA role for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
border-radius: 10px;	Rounds the corners.
border: 1px solid;	Changes the visual order of a flex item without changing the source.
border-left-width: 6px;	A thick left border used as an accent stripe.
background: #eff6ff;	Background colour or image.
border-color: #60a5fa;	The line around the element: width, style and colour.

Check your work

- Each message has a text label
- Contrast passes for all four
- Shared styles in one rule
- role used correctly

Exercises

1. Add a close button that hides the alert with JavaScript.
2. Add icons with ::before.
3. Add a dark mode variant.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 838: Alert message components for Byte Repair

Theme: Byte Repair (Nasr City) | Level 1 | Files: index.html, styles.css

Brief

Create four message styles (info, success, warning, error) with colour, a thick left border and a text prefix so meaning does not rely on colour alone.

Learning goals

- Build reusable component classes
- Use role=status and role=alert
- Use border shorthand then override one side

Elements and CSS used

HTML elements	CSS features
p, strong	border: 1px solid, border-left-width, border-color, background, class modifiers

Build guide

1. Write four paragraphs with the shared class alert and a modifier class.
2. Prefix each with a strong label.
3. Add role attributes.
4. Style .alert once with padding, radius and a 1px border.
5. Set border-left-width: 6px.
6. Set colours per modifier.

Project 838: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - Messages</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Message styles</h1>
    <p class="alert info" role="status"><strong>Info:</strong> Byte
Repair opens at 10:00 on Fridays.</p>
    <p class="alert success" role="status"><strong>Success:</strong>
Your repair has been booked.</p>
    <p class="alert warning" role="alert"><strong>Warning:</strong>
Only two repairs left this week.</p>
    <p class="alert error" role="alert"><strong>Error:</strong> The
email address is not valid.</p>
  </main>
</body>
</html>
```

Project 838: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; display:
grid; gap: 1rem; }
.alert { margin: 0; padding: .9rem 1.1rem; border-radius: 10px;
border: 1px solid; border-left-width: 6px; }
.info    { background: #eff6ff; border-color: #60a5fa; color: #1e3a8a;
 }
.success { background: #f0fdf4; border-color: #4ade80; color: #14532d;
 }
.warning { background: #fffbeb; border-color: #fbbf24; color: #78350f;
 }
.error   { background: #fef2f2; border-color: #f87171; color: #7f1d1d;
 }
```

Project 838 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - Messages</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Message styles	The main heading; only one per page.
<p class="alert info" role="status">Info: Byte Rep...	A paragraph of text.
<p class="alert success" role="status">Success: Yo...	Strong importance (bold by default).
<p class="alert warning" role="alert">Warning: Onl...	Gives the element an ARIA role for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
border-radius: 10px;	Rounds the corners.
border: 1px solid;	Changes the visual order of a flex item without changing the source.
border-left-width: 6px;	A thick left border used as an accent stripe.
background: #eff6ff;	Background colour or image.
border-color: #60a5fa;	The line around the element: width, style and colour.

Check your work

- Each message has a text label
- Contrast passes for all four
- Shared styles in one rule
- role used correctly

Exercises

1. Add a close button that hides the alert with JavaScript.
2. Add icons with ::before.
3. Add a dark mode variant.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 839: Alert message components for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 1 | Files: index.html, styles.css

Brief

Create four message styles (info, success, warning, error) with colour, a thick left border and a text prefix so meaning does not rely on colour alone.

Learning goals

- Build reusable component classes
- Use role=status and role=alert
- Use border shorthand then override one side

Elements and CSS used

HTML elements	CSS features
p, strong	border: 1px solid, border-left-width, border-color, background, class modifiers

Build guide

1. Write four paragraphs with the shared class alert and a modifier class.
2. Prefix each with a strong label.
3. Add role attributes.
4. Style .alert once with padding, radius and a 1px border.
5. Set border-left-width: 6px.
6. Set colours per modifier.

Project 839: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - Messages</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Message styles</h1>
    <p class="alert info" role="status"><strong>Info:</strong> Sahara
Pet Care opens at 10:00 on Fridays.</p>
    <p class="alert success" role="status"><strong>Success:</strong>
Your service has been booked.</p>
    <p class="alert warning" role="alert"><strong>Warning:</strong>
Only two services left this week.</p>
    <p class="alert error" role="alert"><strong>Error:</strong> The
email address is not valid.</p>
  </main>
</body>
</html>
```

Project 839: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; display:
grid; gap: 1rem; }
.alert { margin: 0; padding: .9rem 1.1rem; border-radius: 10px;
border: 1px solid; border-left-width: 6px; }
.info    { background: #eff6ff; border-color: #60a5fa; color: #1e3a8a;
 }
.success { background: #f0fdf4; border-color: #4ade80; color: #14532d;
 }
.warning { background: #fffbeb; border-color: #fbbf24; color: #78350f;
 }
.error   { background: #fef2f2; border-color: #f87171; color: #7f1d1d;
 }
```

Project 839 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - Messages</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Message styles	The main heading; only one per page.
<p class="alert info" role="status">Info: Sahara P...	A paragraph of text.
<p class="alert success" role="status">Success: Yo...	Strong importance (bold by default).
<p class="alert warning" role="alert">Warning: Onl...	Gives the element an ARIA role for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
border-radius: 10px;	Rounds the corners.
border: 1px solid;	Changes the visual order of a flex item without changing the source.
border-left-width: 6px;	A thick left border used as an accent stripe.
background: #eff6ff;	Background colour or image.
border-color: #60a5fa;	The line around the element: width, style and colour.

Check your work

- Each message has a text label
- Contrast passes for all four
- Shared styles in one rule
- role used correctly

Exercises

1. Add a close button that hides the alert with JavaScript.
2. Add icons with ::before.
3. Add a dark mode variant.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 840: Alert message components for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 1 | Files: index.html, styles.css

Brief

Create four message styles (info, success, warning, error) with colour, a thick left border and a text prefix so meaning does not rely on colour alone.

Learning goals

- Build reusable component classes
- Use role=status and role=alert
- Use border shorthand then override one side

Elements and CSS used

HTML elements	CSS features
p, strong	border: 1px solid, border-left-width, border-color, background, class modifiers

Build guide

1. Write four paragraphs with the shared class alert and a modifier class.
2. Prefix each with a strong label.
3. Add role attributes.
4. Style .alert once with padding, radius and a 1px border.
5. Set border-left-width: 6px.

6. Set colours per modifier.

Project 840: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - Messages</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Message styles</h1>
    <p class="alert info" role="status"><strong>Info:</strong>
Alexandria Sailing School opens at 10:00 on Fridays.</p>
    <p class="alert success" role="status"><strong>Success:</strong>
Your lesson has been booked.</p>
    <p class="alert warning" role="alert"><strong>Warning:</strong>
Only two lessons left this week.</p>
    <p class="alert error" role="alert"><strong>Error:</strong> The
email address is not valid.</p>
  </main>
</body>
</html>
```

Project 840: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; display:
grid; gap: 1rem; }
.alert { margin: 0; padding: .9rem 1.1rem; border-radius: 10px;
border: 1px solid; border-left-width: 6px; }
.info    { background: #eff6ff; border-color: #60a5fa; color: #1e3a8a;
 }
.success { background: #f0fdf4; border-color: #4ade80; color: #14532d;
 }
.warning { background: #fffbeb; border-color: #fbbf24; color: #78350f;
 }
.error   { background: #fef2f2; border-color: #f87171; color: #7f1d1d;
 }
```

Project 840 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - Messages</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Message styles	The main heading; only one per page.
<p class="alert info" role="status">Info: Alexandr...	A paragraph of text.
<p class="alert success" role="status">Success: Yo...	Strong importance (bold by default).
<p class="alert warning" role="alert">Warning: Onl...	Gives the element an ARIA role for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
border-radius: 10px;	Rounds the corners.
border: 1px solid;	Changes the visual order of a flex item without changing the source.
border-left-width: 6px;	A thick left border used as an accent stripe.
background: #eff6ff;	Background colour or image.
border-color: #60a5fa;	The line around the element: width, style and colour.

Check your work

- Each message has a text label
- Contrast passes for all four
- Shared styles in one rule
- role used correctly

Exercises

1. Add a close button that hides the alert with JavaScript.
2. Add icons with ::before.
3. Add a dark mode variant.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 841: Alert message components for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Create four message styles (info, success, warning, error) with colour, a thick left border and a text prefix so meaning does not rely on colour alone.

Learning goals

- Build reusable component classes
- Use role=status and role=alert
- Use border shorthand then override one side

Elements and CSS used

HTML elements	CSS features
p, strong	border: 1px solid, border-left-width, border-color, background, class modifiers

Build guide

1. Write four paragraphs with the shared class alert and a modifier class.
2. Prefix each with a strong label.
3. Add role attributes.
4. Style .alert once with padding, radius and a 1px border.
5. Set border-left-width: 6px.

6. Set colours per modifier.

Project 841: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - Messages</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Message styles</h1>
    <p class="alert info" role="status"><strong>Info:</strong> Habiba
Handmade Jewellery opens at 10:00 on Fridays.</p>
    <p class="alert success" role="status"><strong>Success:</strong>
Your item has been booked.</p>
    <p class="alert warning" role="alert"><strong>Warning:</strong>
Only two items left this week.</p>
    <p class="alert error" role="alert"><strong>Error:</strong> The
email address is not valid.</p>
  </main>
</body>
</html>
```

Project 841: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; display:
grid; gap: 1rem; }
.alert { margin: 0; padding: .9rem 1.1rem; border-radius: 10px;
border: 1px solid; border-left-width: 6px; }
.info    { background: #eff6ff; border-color: #60a5fa; color: #1e3a8a;
 }
.success { background: #f0fdf4; border-color: #4ade80; color: #14532d;
 }
.warning { background: #fffbeb; border-color: #fbbf24; color: #78350f;
 }
.error   { background: #fef2f2; border-color: #f87171; color: #7f1d1d;
 }
```

Project 841 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - Messages</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Message styles	The main heading; only one per page.
<p class="alert info" role="status">Info: Habiba H...	A paragraph of text.
<p class="alert success" role="status">Success: Yo...	Strong importance (bold by default).
<p class="alert warning" role="alert">Warning: Onl...	Gives the element an ARIA role for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
border-radius: 10px;	Rounds the corners.
border: 1px solid;	Changes the visual order of a flex item without changing the source.
border-left-width: 6px;	A thick left border used as an accent stripe.
background: #eff6ff;	Background colour or image.
border-color: #60a5fa;	The line around the element: width, style and colour.

Check your work

- Each message has a text label
- Contrast passes for all four
- Shared styles in one rule
- role used correctly

Exercises

1. Add a close button that hides the alert with JavaScript.
2. Add icons with ::before.
3. Add a dark mode variant.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 842: Alert message components for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 1 | Files: index.html, styles.css

Brief

Create four message styles (info, success, warning, error) with colour, a thick left border and a text prefix so meaning does not rely on colour alone.

Learning goals

- Build reusable component classes
- Use role=status and role=alert
- Use border shorthand then override one side

Elements and CSS used

HTML elements	CSS features
p, strong	border: 1px solid, border-left-width, border-color, background, class modifiers

Build guide

1. Write four paragraphs with the shared class alert and a modifier class.
2. Prefix each with a strong label.
3. Add role attributes.
4. Style .alert once with padding, radius and a 1px border.
5. Set border-left-width: 6px.

6. Set colours per modifier.

Project 842: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - Messages</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Message styles</h1>
    <p class="alert info" role="status"><strong>Info:</strong> Fayoum
Pottery Studio opens at 10:00 on Fridays.</p>
    <p class="alert success" role="status"><strong>Success:</strong>
Your workshop has been booked.</p>
    <p class="alert warning" role="alert"><strong>Warning:</strong>
Only two workshops left this week.</p>
    <p class="alert error" role="alert"><strong>Error:</strong> The
email address is not valid.</p>
  </main>
</body>
</html>
```

Project 842: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; display:
grid; gap: 1rem; }
.alert { margin: 0; padding: .9rem 1.1rem; border-radius: 10px;
border: 1px solid; border-left-width: 6px; }
.info    { background: #eff6ff; border-color: #60a5fa; color: #1e3a8a;
 }
.success { background: #f0fdf4; border-color: #4ade80; color: #14532d;
 }
.warning { background: #fffbeb; border-color: #fbbf24; color: #78350f;
 }
.error   { background: #fef2f2; border-color: #f87171; color: #7f1d1d;
 }
```

Project 842 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - Messages</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Message styles	The main heading; only one per page.
<p class="alert info" role="status">Info: Fayoum P...	A paragraph of text.
<p class="alert success" role="status">Success: Yo...	Strong importance (bold by default).
<p class="alert warning" role="alert">Warning: Onl...	Gives the element an ARIA role for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
border-radius: 10px;	Rounds the corners.
border: 1px solid;	Changes the visual order of a flex item without changing the source.
border-left-width: 6px;	A thick left border used as an accent stripe.
background: #eff6ff;	Background colour or image.
border-color: #60a5fa;	The line around the element: width, style and colour.

Check your work

- Each message has a text label
- Contrast passes for all four
- Shared styles in one rule
- role used correctly

Exercises

1. Add a close button that hides the alert with JavaScript.
2. Add icons with ::before.
3. Add a dark mode variant.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 843: Alert message components for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 1 | Files: index.html, styles.css

Brief

Create four message styles (info, success, warning, error) with colour, a thick left border and a text prefix so meaning does not rely on colour alone.

Learning goals

- Build reusable component classes
- Use role=status and role=alert
- Use border shorthand then override one side

Elements and CSS used

HTML elements	CSS features
p, strong	border: 1px solid, border-left-width, border-color, background, class modifiers

Build guide

1. Write four paragraphs with the shared class alert and a modifier class.
2. Prefix each with a strong label.
3. Add role attributes.
4. Style .alert once with padding, radius and a 1px border.
5. Set border-left-width: 6px.

6. Set colours per modifier.

Project 843: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - Messages</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Message styles</h1>
    <p class="alert info" role="status"><strong>Info:</strong>
Cleopatra Beauty Salon opens at 10:00 on Fridays.</p>
    <p class="alert success" role="status"><strong>Success:</strong>
Your treatment has been booked.</p>
    <p class="alert warning" role="alert"><strong>Warning:</strong>
Only two treatments left this week.</p>
    <p class="alert error" role="alert"><strong>Error:</strong> The
email address is not valid.</p>
  </main>
</body>
</html>
```

Project 843: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; display:
grid; gap: 1rem; }
.alert { margin: 0; padding: .9rem 1.1rem; border-radius: 10px;
border: 1px solid; border-left-width: 6px; }
.info    { background: #eff6ff; border-color: #60a5fa; color: #1e3a8a;
 }
.success { background: #f0fdf4; border-color: #4ade80; color: #14532d;
 }
.warning { background: #fffbeb; border-color: #fbbf24; color: #78350f;
 }
.error   { background: #fef2f2; border-color: #f87171; color: #7f1d1d;
 }
```

Project 843 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - Messages</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Message styles	The main heading; only one per page.
<p class="alert info" role="status">Info: Cleopatr...	A paragraph of text.
<p class="alert success" role="status">Success: Yo...	Strong importance (bold by default).
<p class="alert warning" role="alert">Warning: Onl...	Gives the element an ARIA role for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
border-radius: 10px;	Rounds the corners.
border: 1px solid;	Changes the visual order of a flex item without changing the source.
border-left-width: 6px;	A thick left border used as an accent stripe.
background: #eff6ff;	Background colour or image.
border-color: #60a5fa;	The line around the element: width, style and colour.

Check your work

- Each message has a text label
- Contrast passes for all four
- Shared styles in one rule
- role used correctly

Exercises

1. Add a close button that hides the alert with JavaScript.
2. Add icons with ::before.
3. Add a dark mode variant.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 844: Alert message components for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 1 | Files: index.html, styles.css

Brief

Create four message styles (info, success, warning, error) with colour, a thick left border and a text prefix so meaning does not rely on colour alone.

Learning goals

- Build reusable component classes
- Use role=status and role=alert
- Use border shorthand then override one side

Elements and CSS used

HTML elements	CSS features
p, strong	border: 1px solid, border-left-width, border-color, background, class modifiers

Build guide

1. Write four paragraphs with the shared class alert and a modifier class.
2. Prefix each with a strong label.
3. Add role attributes.
4. Style .alert once with padding, radius and a 1px border.
5. Set border-left-width: 6px.
6. Set colours per modifier.

Project 844: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - Messages</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Message styles</h1>
    <p class="alert info" role="status"><strong>Info:</strong> Suez
Auto Service opens at 10:00 on Fridays.</p>
    <p class="alert success" role="status"><strong>Success:</strong>
Your service has been booked.</p>
    <p class="alert warning" role="alert"><strong>Warning:</strong>
Only two services left this week.</p>
    <p class="alert error" role="alert"><strong>Error:</strong> The
email address is not valid.</p>
  </main>
</body>
</html>
```

Project 844: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; display:
grid; gap: 1rem; }
.alert { margin: 0; padding: .9rem 1.1rem; border-radius: 10px;
border: 1px solid; border-left-width: 6px; }
.info    { background: #eff6ff; border-color: #60a5fa; color: #1e3a8a;
 }
.success { background: #f0fdf4; border-color: #4ade80; color: #14532d;
 }
.warning { background: #fffbeb; border-color: #fbbf24; color: #78350f;
 }
.error   { background: #fef2f2; border-color: #f87171; color: #7f1d1d;
 }
```

Project 844 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - Messages</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Message styles	The main heading; only one per page.
<p class="alert info" role="status">Info: Suez Aut...	A paragraph of text.
<p class="alert success" role="status">Success: Yo...	Strong importance (bold by default).
<p class="alert warning" role="alert">Warning: Onl...	Gives the element an ARIA role for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
border-radius: 10px;	Rounds the corners.
border: 1px solid;	Changes the visual order of a flex item without changing the source.
border-left-width: 6px;	A thick left border used as an accent stripe.
background: #eff6ff;	Background colour or image.
border-color: #60a5fa;	The line around the element: width, style and colour.

Check your work

- Each message has a text label
- Contrast passes for all four
- Shared styles in one rule
- role used correctly

Exercises

1. Add a close button that hides the alert with JavaScript.
2. Add icons with ::before.
3. Add a dark mode variant.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 845: Alert message components for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 1 | Files: index.html, styles.css

Brief

Create four message styles (info, success, warning, error) with colour, a thick left border and a text prefix so meaning does not rely on colour alone.

Learning goals

- Build reusable component classes
- Use role=status and role=alert
- Use border shorthand then override one side

Elements and CSS used

HTML elements	CSS features
p, strong	border: 1px solid, border-left-width, border-color, background, class modifiers

Build guide

1. Write four paragraphs with the shared class alert and a modifier class.
2. Prefix each with a strong label.
3. Add role attributes.
4. Style .alert once with padding, radius and a 1px border.
5. Set border-left-width: 6px.
6. Set colours per modifier.

Project 845: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - Messages</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Message styles</h1>
    <p class="alert info" role="status"><strong>Info:</strong> Luxor
Music Academy opens at 10:00 on Fridays.</p>
    <p class="alert success" role="status"><strong>Success:</strong>
Your course has been booked.</p>
    <p class="alert warning" role="alert"><strong>Warning:</strong>
Only two courses left this week.</p>
    <p class="alert error" role="alert"><strong>Error:</strong> The
email address is not valid.</p>
  </main>
</body>
</html>
```

Project 845: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; display:
grid; gap: 1rem; }
.alert { margin: 0; padding: .9rem 1.1rem; border-radius: 10px;
border: 1px solid; border-left-width: 6px; }
.info    { background: #eff6ff; border-color: #60a5fa; color: #1e3a8a;
 }
.success { background: #f0fdf4; border-color: #4ade80; color: #14532d;
 }
.warning { background: #fffbeb; border-color: #fbbf24; color: #78350f;
 }
.error   { background: #fef2f2; border-color: #f87171; color: #7f1d1d;
 }
```

Project 845 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - Messages</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Message styles	The main heading; only one per page.
<p class="alert info" role="status">Info: Luxor Mu...	A paragraph of text.
<p class="alert success" role="status">Success: Yo...	Strong importance (bold by default).
<p class="alert warning" role="alert">Warning: Onl...	Gives the element an ARIA role for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
border-radius: 10px;	Rounds the corners.
border: 1px solid;	Changes the visual order of a flex item without changing the source.
border-left-width: 6px;	A thick left border used as an accent stripe.
background: #eff6ff;	Background colour or image.
border-color: #60a5fa;	The line around the element: width, style and colour.

Check your work

- Each message has a text label
- Contrast passes for all four
- Shared styles in one rule
- role used correctly

Exercises

1. Add a close button that hides the alert with JavaScript.
2. Add icons with ::before.
3. Add a dark mode variant.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 846: Alert message components for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 1 | Files: index.html, styles.css

Brief

Create four message styles (info, success, warning, error) with colour, a thick left border and a text prefix so meaning does not rely on colour alone.

Learning goals

- Build reusable component classes
- Use role=status and role=alert
- Use border shorthand then override one side

Elements and CSS used

HTML elements	CSS features
p, strong	border: 1px solid, border-left-width, border-color, background, class modifiers

Build guide

1. Write four paragraphs with the shared class alert and a modifier class.
2. Prefix each with a strong label.
3. Add role attributes.
4. Style .alert once with padding, radius and a 1px border.
5. Set border-left-width: 6px.
6. Set colours per modifier.

Project 846: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - Messages</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Message styles</h1>
    <p class="alert info" role="status"><strong>Info:</strong> Port
Said Seafood opens at 10:00 on Fridays.</p>
    <p class="alert success" role="status"><strong>Success:</strong>
Your dish has been booked.</p>
    <p class="alert warning" role="alert"><strong>Warning:</strong>
Only two dishes left this week.</p>
    <p class="alert error" role="alert"><strong>Error:</strong> The
email address is not valid.</p>
  </main>
</body>
</html>
```

Project 846: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; display:
grid; gap: 1rem; }
.alert { margin: 0; padding: .9rem 1.1rem; border-radius: 10px;
border: 1px solid; border-left-width: 6px; }
.info    { background: #eff6ff; border-color: #60a5fa; color: #1e3a8a;
 }
.success { background: #f0fdf4; border-color: #4ade80; color: #14532d;
 }
.warning { background: #fffbeb; border-color: #fbbf24; color: #78350f;
 }
.error   { background: #fef2f2; border-color: #f87171; color: #7f1d1d;
 }
```

Project 846 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - Messages</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Message styles	The main heading; only one per page.
<p class="alert info" role="status">Info: Port Sai...	A paragraph of text.
<p class="alert success" role="status">Success: Yo...	Strong importance (bold by default).
<p class="alert warning" role="alert">Warning: Onl...	Gives the element an ARIA role for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
border-radius: 10px;	Rounds the corners.
border: 1px solid;	Changes the visual order of a flex item without changing the source.
border-left-width: 6px;	A thick left border used as an accent stripe.
background: #eff6ff;	Background colour or image.
border-color: #60a5fa;	The line around the element: width, style and colour.

Check your work

- Each message has a text label
- Contrast passes for all four
- Shared styles in one rule
- role used correctly

Exercises

1. Add a close button that hides the alert with JavaScript.
2. Add icons with ::before.
3. Add a dark mode variant.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 847: Alert message components for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 1 | Files: index.html, styles.css

Brief

Create four message styles (info, success, warning, error) with colour, a thick left border and a text prefix so meaning does not rely on colour alone.

Learning goals

- Build reusable component classes
- Use role=status and role=alert
- Use border shorthand then override one side

Elements and CSS used

HTML elements	CSS features
p, strong	border: 1px solid, border-left-width, border-color, background, class modifiers

Build guide

1. Write four paragraphs with the shared class alert and a modifier class.
2. Prefix each with a strong label.
3. Add role attributes.
4. Style .alert once with padding, radius and a 1px border.
5. Set border-left-width: 6px.
6. Set colours per modifier.

Project 847: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - Messages</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Message styles</h1>
    <p class="alert info" role="status"><strong>Info:</strong> Delta
Kids Library opens at 10:00 on Fridays.</p>
    <p class="alert success" role="status"><strong>Success:</strong>
Your programme has been booked.</p>
    <p class="alert warning" role="alert"><strong>Warning:</strong>
Only two programmes left this week.</p>
    <p class="alert error" role="alert"><strong>Error:</strong> The
email address is not valid.</p>
  </main>
</body>
</html>
```

Project 847: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; display:
grid; gap: 1rem; }
.alert { margin: 0; padding: .9rem 1.1rem; border-radius: 10px;
border: 1px solid; border-left-width: 6px; }
.info    { background: #eff6ff; border-color: #60a5fa; color: #1e3a8a;
 }
.success { background: #f0fdf4; border-color: #4ade80; color: #14532d;
 }
.warning { background: #fffbeb; border-color: #fbbf24; color: #78350f;
 }
.error   { background: #fef2f2; border-color: #f87171; color: #7f1d1d;
 }
```

Project 847 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - Messages</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Message styles	The main heading; only one per page.
<p class="alert info" role="status">Info: Delta Ki...	A paragraph of text.
<p class="alert success" role="status">Success: Yo...	Strong importance (bold by default).
<p class="alert warning" role="alert">Warning: Onl...	Gives the element an ARIA role for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
border-radius: 10px;	Rounds the corners.
border: 1px solid;	Changes the visual order of a flex item without changing the source.
border-left-width: 6px;	A thick left border used as an accent stripe.
background: #eff6ff;	Background colour or image.
border-color: #60a5fa;	The line around the element: width, style and colour.

Check your work

- Each message has a text label
- Contrast passes for all four
- Shared styles in one rule
- role used correctly

Exercises

1. Add a close button that hides the alert with JavaScript.
2. Add icons with ::before.
3. Add a dark mode variant.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 848: Alert message components for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 1 | Files: index.html, styles.css

Brief

Create four message styles (info, success, warning, error) with colour, a thick left border and a text prefix so meaning does not rely on colour alone.

Learning goals

- Build reusable component classes
- Use role=status and role=alert
- Use border shorthand then override one side

Elements and CSS used

HTML elements	CSS features
p, strong	border: 1px solid, border-left-width, border-color, background, class modifiers

Build guide

1. Write four paragraphs with the shared class alert and a modifier class.
2. Prefix each with a strong label.
3. Add role attributes.
4. Style .alert once with padding, radius and a 1px border.
5. Set border-left-width: 6px.
6. Set colours per modifier.

Project 848: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - Messages</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Message styles</h1>
    <p class="alert info" role="status"><strong>Info:</strong> Nubian
Guest House opens at 10:00 on Fridays.</p>
    <p class="alert success" role="status"><strong>Success:</strong>
Your room has been booked.</p>
    <p class="alert warning" role="alert"><strong>Warning:</strong>
Only two rooms left this week.</p>
    <p class="alert error" role="alert"><strong>Error:</strong> The
email address is not valid.</p>
  </main>
</body>
</html>
```

Project 848: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; display:
grid; gap: 1rem; }
.alert { margin: 0; padding: .9rem 1.1rem; border-radius: 10px;
border: 1px solid; border-left-width: 6px; }
.info    { background: #eff6ff; border-color: #60a5fa; color: #1e3a8a;
 }
.success { background: #f0fdf4; border-color: #4ade80; color: #14532d;
 }
.warning { background: #fffbeb; border-color: #fbbf24; color: #78350f;
 }
.error   { background: #fef2f2; border-color: #f87171; color: #7f1d1d;
 }
```

Project 848 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - Messages</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Message styles	The main heading; only one per page.
<p class="alert info" role="status">Info: Nubian G...	A paragraph of text.
<p class="alert success" role="status">Success: Yo...	Strong importance (bold by default).
<p class="alert warning" role="alert">Warning: Onl...	Gives the element an ARIA role for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
border-radius: 10px;	Rounds the corners.
border: 1px solid;	Changes the visual order of a flex item without changing the source.
border-left-width: 6px;	A thick left border used as an accent stripe.
background: #eff6ff;	Background colour or image.
border-color: #60a5fa;	The line around the element: width, style and colour.

Check your work

- Each message has a text label
- Contrast passes for all four
- Shared styles in one rule
- role used correctly

Exercises

1. Add a close button that hides the alert with JavaScript.
2. Add icons with ::before.
3. Add a dark mode variant.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 849: Alert message components for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 1 | Files: index.html, styles.css

Brief

Create four message styles (info, success, warning, error) with colour, a thick left border and a text prefix so meaning does not rely on colour alone.

Learning goals

- Build reusable component classes
- Use role=status and role=alert
- Use border shorthand then override one side

Elements and CSS used

HTML elements	CSS features
p, strong	border: 1px solid, border-left-width, border-color, background, class modifiers

Build guide

1. Write four paragraphs with the shared class alert and a modifier class.
2. Prefix each with a strong label.
3. Add role attributes.
4. Style .alert once with padding, radius and a 1px border.
5. Set border-left-width: 6px.

6. Set colours per modifier.

Project 849: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - Messages</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Message styles</h1>
    <p class="alert info" role="status"><strong>Info:</strong>
Ismailia Cycling Store opens at 10:00 on Fridays.</p>
    <p class="alert success" role="status"><strong>Success:</strong>
Your bike has been booked.</p>
    <p class="alert warning" role="alert"><strong>Warning:</strong>
Only two bikes left this week.</p>
    <p class="alert error" role="alert"><strong>Error:</strong> The
email address is not valid.</p>
  </main>
</body>
</html>
```

Project 849: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; display:
grid; gap: 1rem; }
.alert { margin: 0; padding: .9rem 1.1rem; border-radius: 10px;
border: 1px solid; border-left-width: 6px; }
.info    { background: #eff6ff; border-color: #60a5fa; color: #1e3a8a;
 }
.success { background: #f0fdf4; border-color: #4ade80; color: #14532d;
 }
.warning { background: #fffbeb; border-color: #fbbf24; color: #78350f;
 }
.error   { background: #fef2f2; border-color: #f87171; color: #7f1d1d;
 }
```

Project 849 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - Messages</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Message styles	The main heading; only one per page.
<p class="alert info" role="status">Info: Ismailia...	A paragraph of text.
<p class="alert success" role="status">Success: Yo...	Strong importance (bold by default).
<p class="alert warning" role="alert">Warning: Onl...	Gives the element an ARIA role for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
border-radius: 10px;	Rounds the corners.
border: 1px solid;	Changes the visual order of a flex item without changing the source.
border-left-width: 6px;	A thick left border used as an accent stripe.
background: #eff6ff;	Background colour or image.
border-color: #60a5fa;	The line around the element: width, style and colour.

Check your work

- Each message has a text label
- Contrast passes for all four
- Shared styles in one rule
- role used correctly

Exercises

1. Add a close button that hides the alert with JavaScript.
2. Add icons with ::before.
3. Add a dark mode variant.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 850: Alert message components for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 1 | Files: index.html, styles.css

Brief

Create four message styles (info, success, warning, error) with colour, a thick left border and a text prefix so meaning does not rely on colour alone.

Learning goals

- Build reusable component classes
- Use role=status and role=alert
- Use border shorthand then override one side

Elements and CSS used

HTML elements	CSS features
p, strong	border: 1px solid, border-left-width, border-color, background, class modifiers

Build guide

1. Write four paragraphs with the shared class alert and a modifier class.
2. Prefix each with a strong label.
3. Add role attributes.
4. Style .alert once with padding, radius and a 1px border.
5. Set border-left-width: 6px.
6. Set colours per modifier.

Project 850: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - Messages</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Message styles</h1>
    <p class="alert info" role="status"><strong>Info:</strong> Minya
Coding Club opens at 10:00 on Fridays.</p>
    <p class="alert success" role="status"><strong>Success:</strong>
Your workshop has been booked.</p>
    <p class="alert warning" role="alert"><strong>Warning:</strong>
Only two workshops left this week.</p>
    <p class="alert error" role="alert"><strong>Error:</strong> The
email address is not valid.</p>
  </main>
</body>
</html>
```

Project 850: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; display:
grid; gap: 1rem; }
.alert { margin: 0; padding: .9rem 1.1rem; border-radius: 10px;
border: 1px solid; border-left-width: 6px; }
.info    { background: #eff6ff; border-color: #60a5fa; color: #1e3a8a;
 }
.success { background: #f0fdf4; border-color: #4ade80; color: #14532d;
 }
.warning { background: #fffbeb; border-color: #fbbf24; color: #78350f;
 }
.error   { background: #fef2f2; border-color: #f87171; color: #7f1d1d;
 }
```

Project 850 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - Messages</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Message styles	The main heading; only one per page.
<p class="alert info" role="status">Info: Minya Co...	A paragraph of text.
<p class="alert success" role="status">Success: Yo...	Strong importance (bold by default).
<p class="alert warning" role="alert">Warning: Onl...	Gives the element an ARIA role for assistive technology.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1rem;	Space between grid or flex items without extra margins.
border-radius: 10px;	Rounds the corners.
border: 1px solid;	Changes the visual order of a flex item without changing the source.
border-left-width: 6px;	A thick left border used as an accent stripe.
background: #eff6ff;	Background colour or image.
border-color: #60a5fa;	The line around the element: width, style and colour.

Check your work

- Each message has a text label
- Contrast passes for all four
- Shared styles in one rule
- role used correctly

Exercises

1. Add a close button that hides the alert with JavaScript.
2. Add icons with ::before.
3. Add a dark mode variant.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Booking form in three steps

Level 2 | 25 projects, one per theme

Build a longer form divided into three fieldsets: radio choice with prices, date/time/number inputs, and personal details with a required checkbox.

Project 851: Booking form in three steps for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 2 | Files: index.html, styles.css

Brief

Build a longer form divided into three fieldsets: radio choice with prices, date/time/number inputs, and personal details with a required checkbox.

Learning goals

- Group related controls with fieldset and legend
- Use date, time, number and tel input types with min/max/step
- Use wrapping labels

Elements and CSS used

HTML elements	CSS features
form, fieldset, legend, label, input (radio, date, time, number, text, tel, checkbox), small, button	fieldset border/radius, legend, display: flex on label, margin-left: auto, :not() chains

Build guide

1. Write three fieldsets with legends numbered 1 to 3.
2. Step 1: radio buttons with the same name, each wrapped in a label with the price in <small>.
3. Step 2: date, time and number inputs with limits.
4. Step 3: text, tel and a required checkbox.
5. Grid the form and fieldsets.

6. Push prices right with margin-left: auto.

Project 851: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Booking</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Book a book</h1>
    <form action="/book" method="post" class="wizard">
      <fieldset>
        <legend>1. Choose a book</legend>
    <label><input type="radio" name="item" value="Learn HTML"
required> Learn HTML <small>120 EGP</small></label>
    <label><input type="radio" name="item" value="CSS in Practice"
required> CSS in Practice <small>150 EGP</small></label>
    <label><input type="radio" name="item" value="JavaScript Basics"
required> JavaScript Basics <small>180 EGP</small></label>
    <label><input type="radio" name="item" value="Web Accessibility"
required> Web Accessibility <small>95 EGP</small></label>
      </fieldset>
      <fieldset>
        <legend>2. When</legend>
        <label>Date <input type="date" name="date" required min="2026-
09-11"></label>
        <label>Time <input type="time" name="time" required
step="1800"></label>
        <label>People <input type="number" name="people" min="1"
max="10" value="1"></label>
      </fieldset>
      <fieldset>
        <legend>3. Your details</legend>
        <label>Name <input type="text" name="name" required
autocomplete="name"></label>
        <label>Phone <input type="tel" name="phone" required
autocomplete="tel" inputmode="tel"></label>
        <label><input type="checkbox" name="terms" required> I agree
to the cancellation policy</label>
      </fieldset>
      <button type="submit">Confirm booking</button>
    </form>
  </main>
</body>
</html>
```

Project 851: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.wizard { display: grid; gap: 1.5rem; }
fieldset { border: 1px solid var(--line); border-radius: 12px;
padding: 1rem 1.25rem; display: grid; gap: .6rem; }
legend { font-weight: 700; color: var(--brand); padding: 0 .4rem; }
label { display: flex; align-items: center; gap: .5rem; flex-wrap:
wrap; }
label small { margin-left: auto; color: var(--muted); }
input:not([type="radio"]):not([type="checkbox"]) { padding: .5rem .
7rem; border: 1px solid #bbb; border-radius: 8px; font: inherit; flex:
 1 1 8rem; }
button { justify-self: start; padding: .8rem 1.6rem; border: 0;
border-radius: 999px; background: var(--brand); color: #fff; font:
inherit; }
```

Project 851 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - Booking</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Book a book	The main heading; only one per page.
<form action="/book" method="post" class="wizard">	A form; action is where the data goes, method how it is sent.
<fieldset>	Groups related form controls.
<legend>1. Choose a book</legend>	Caption for the fieldset.
<label><input type="radio" name="item" value="Learn HTML" required>...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="item" value="CSS in Practice" requ...	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="item" value="JavaScript Basics" re...	A form control; its type decides what it looks like.
<label><input type="radio" name="item" value="Web Accessibility" re...	The field must be filled before the form can be submitted.
<label>Date <input type="date" name="date" required min="2026-09-11...	Date picker.
<label>Time <input type="time" name="time" required step="1800"></l...	Time picker.
<label>People <input type="number" name="people" min="1" max="10" v...	Numeric input with min, max and step.
<label>Name <input type="text" name="name" required autocomplete="n...	Tells the browser which saved value to offer (name, email, tel...).
<label>Phone <input type="tel" name="phone" required autocomplete="...	Telephone number; shows the phone keypad on mobiles.
<label><input type="checkbox" name="terms" required> I agree to the...	Checkbox: on or off.
<button type="submit">Confirm booking</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.
font-weight: 700;	Thickness of the text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
input:not([type="radio"]):not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
flex: 1 1 8rem;	The item can grow and shrink from the given basis.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.
background: var(--brand);	Background colour or image.

Check your work

- Radios share one name
- Date min prevents past dates
- Every control labelled
- Checkbox required works

Exercises

1. Show one fieldset at a time with :has() and radio state or JavaScript.
2. Add a summary panel that updates live.
3. Add a progress tracker on top.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 852: Booking form in three steps for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 2 | Files: index.html, styles.css

Brief

Build a longer form divided into three fieldsets: radio choice with prices, date/time/number inputs, and personal details with a required checkbox.

Learning goals

- Group related controls with fieldset and legend
- Use date, time, number and tel input types with min/max/step
- Use wrapping labels

Elements and CSS used

HTML elements	CSS features
form, fieldset, legend, label, input (radio, date, time, number, text, tel, checkbox), small, button	fieldset border/radius, legend, display: flex on label, margin-left: auto, :not() chains

Build guide

1. Write three fieldsets with legends numbered 1 to 3.
2. Step 1: radio buttons with the same name, each wrapped in a label with the price in <small>.
3. Step 2: date, time and number inputs with limits.
4. Step 3: text, tel and a required checkbox.
5. Grid the form and fieldsets.
6. Push prices right with margin-left: auto.

Project 852: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - Booking</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Book a pastry</h1>
    <form action="/book" method="post" class="wizard">
      <fieldset>
        <legend>1. Choose a pastry</legend>
    <label><input type="radio" name="item" value="Sourdough loaf"
required> Sourdough loaf <small>60 EGP</small></label>
    <label><input type="radio" name="item" value="Croissant"
required> Croissant <small>35 EGP</small></label>
    <label><input type="radio" name="item" value="Date cookies"
required> Date cookies <small>80 EGP</small></label>
    <label><input type="radio" name="item" value="Baklava box"
required> Baklava box <small>220 EGP</small></label>
      </fieldset>
      <fieldset>
        <legend>2. When</legend>
        <label>Date <input type="date" name="date" required min="2026-
09-11"></label>
        <label>Time <input type="time" name="time" required
step="1800"></label>
        <label>People <input type="number" name="people" min="1"
max="10" value="1"></label>
      </fieldset>
      <fieldset>
        <legend>3. Your details</legend>
        <label>Name <input type="text" name="name" required
autocomplete="name"></label>
        <label>Phone <input type="tel" name="phone" required
autocomplete="tel" inputmode="tel"></label>
        <label><input type="checkbox" name="terms" required> I agree
to the cancellation policy</label>
      </fieldset>
      <button type="submit">Confirm booking</button>
    </form>
  </main>
</body>
</html>
```

Project 852: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.wizard { display: grid; gap: 1.5rem; }
fieldset { border: 1px solid var(--line); border-radius: 12px;
padding: 1rem 1.25rem; display: grid; gap: .6rem; }
legend { font-weight: 700; color: var(--brand); padding: 0 .4rem; }
label { display: flex; align-items: center; gap: .5rem; flex-wrap:
wrap; }
label small { margin-left: auto; color: var(--muted); }
input:not([type="radio"]):not([type="checkbox"]) { padding: .5rem .
7rem; border: 1px solid #bbb; border-radius: 8px; font: inherit; flex:
 1 1 8rem; }
button { justify-self: start; padding: .8rem 1.6rem; border: 0;
border-radius: 999px; background: var(--brand); color: #fff; font:
inherit; }
```

Project 852 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - Booking</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Book a pastry	The main heading; only one per page.
<form action="/book" method="post" class="wizard">	A form; action is where the data goes, method how it is sent.
<fieldset>	Groups related form controls.
<legend>1. Choose a pastry</legend>	Caption for the fieldset.
<label><input type="radio" name="item" value="Sourdough loaf" requi...	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<label><input type="radio" name="item" value="Croissant" required> ...	Radio button: one choice from a group sharing the same name.
<label><input type="radio" name="item" value="Date cookies" require...	A form control; its type decides what it looks like.
<label><input type="radio" name="item" value="Baklava box" required...	The field must be filled before the form can be submitted.
<label>Date <input type="date" name="date" required min="2026-09-11...	Date picker.
<label>Time <input type="time" name="time" required step="1800"></l...	Time picker.
<label>People <input type="number" name="people" min="1" max="10" v...	Numeric input with min, max and step.
<label>Name <input type="text" name="name" required autocomplete="n...	Tells the browser which saved value to offer (name, email, tel...).
<label>Phone <input type="tel" name="phone" required autocomplete="...	Telephone number; shows the phone keypad on mobiles.
<label><input type="checkbox" name="terms" required> I agree to the...	Checkbox: on or off.
<button type="submit">Confirm booking</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.
font-weight: 700;	Thickness of the text.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
input:not([type="radio"]):not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
flex: 1 1 8rem;	The item can grow and shrink from the given basis.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.
background: var(--brand);	Background colour or image.

Check your work

- Radios share one name
- Date min prevents past dates
- Every control labelled
- Checkbox required works

Exercises

1. Show one fieldset at a time with :has() and radio state or JavaScript.
2. Add a summary panel that updates live.
3. Add a progress tracker on top.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 853: Booking form in three steps for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 2 | Files: index.html, styles.css

Brief

Build a longer form divided into three fieldsets: radio choice with prices, date/time/number inputs, and personal details with a required checkbox.

Learning goals

- Group related controls with fieldset and legend
- Use date, time, number and tel input types with min/max/step
- Use wrapping labels

Elements and CSS used

HTML elements	CSS features
form, fieldset, legend, label, input (radio, date, time, number, text, tel, checkbox), small, button	fieldset border/radius, legend, display: flex on label, margin-left: auto, :not() chains

Build guide

1. Write three fieldsets with legends numbered 1 to 3.
2. Step 1: radio buttons with the same name, each wrapped in a label with the price in <small>.
3. Step 2: date, time and number inputs with limits.
4. Step 3: text, tel and a required checkbox.
5. Grid the form and fieldsets.
6. Push prices right with margin-left: auto.

Project 853: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - Booking</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Book a class</h1>
    <form action="/book" method="post" class="wizard">
      <fieldset>
        <legend>1. Choose a class</legend>
    <label><input type="radio" name="item" value="Morning yoga"
required> Morning yoga <small>100 EGP</small></label>
    <label><input type="radio" name="item" value="Strength circuit"
required> Strength circuit <small>120 EGP</small></label>
    <label><input type="radio" name="item" value="Spinning" required>
Spinning <small>110 EGP</small></label>
    <label><input type="radio" name="item" value="Personal training"
required> Personal training <small>350 EGP</small></label>
      </fieldset>
      <fieldset>
        <legend>2. When</legend>
        <label>Date <input type="date" name="date" required min="2026-
09-11"></label>
        <label>Time <input type="time" name="time" required
step="1800"></label>
        <label>People <input type="number" name="people" min="1"
max="10" value="1"></label>
      </fieldset>
      <fieldset>
        <legend>3. Your details</legend>
        <label>Name <input type="text" name="name" required
autocomplete="name"></label>
        <label>Phone <input type="tel" name="phone" required
autocomplete="tel" inputmode="tel"></label>
        <label><input type="checkbox" name="terms" required> I agree
to the cancellation policy</label>
      </fieldset>
      <button type="submit">Confirm booking</button>
    </form>
  </main>
</body>
</html>
```

Project 853: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.wizard { display: grid; gap: 1.5rem; }
fieldset { border: 1px solid var(--line); border-radius: 12px;
padding: 1rem 1.25rem; display: grid; gap: .6rem; }
legend { font-weight: 700; color: var(--brand); padding: 0 .4rem; }
label { display: flex; align-items: center; gap: .5rem; flex-wrap:
wrap; }
label small { margin-left: auto; color: var(--muted); }
input:not([type="radio"]):not([type="checkbox"]) { padding: .5rem .
7rem; border: 1px solid #bbb; border-radius: 8px; font: inherit; flex:
 1 1 8rem; }
button { justify-self: start; padding: .8rem 1.6rem; border: 0;
border-radius: 999px; background: var(--brand); color: #fff; font:
inherit; }
```

Project 853 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - Booking</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Book a class	The main heading; only one per page.
<form action="/book" method="post" class="wizard">	A form; action is where the data goes, method how it is sent.
<fieldset>	Groups related form controls.
<legend>1. Choose a class</legend>	Caption for the fieldset.
<label><input type="radio" name="item" value="Morning yoga" require...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="item" value="Strength circuit" req...	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="item" value="Spinning" required> S...	A form control; its type decides what it looks like.
<label><input type="radio" name="item" value="Personal training" re...	The field must be filled before the form can be submitted.
<label>Date <input type="date" name="date" required min="2026-09-11...	Date picker.
<label>Time <input type="time" name="time" required step="1800"></l...	Time picker.
<label>People <input type="number" name="people" min="1" max="10" v...	Numeric input with min, max and step.
<label>Name <input type="text" name="name" required autocomplete="n...	Tells the browser which saved value to offer (name, email, tel...).
<label>Phone <input type="tel" name="phone" required autocomplete="...	Telephone number; shows the phone keypad on mobiles.
<label><input type="checkbox" name="terms" required> I agree to the...	Checkbox: on or off.
<button type="submit">Confirm booking</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.
font-weight: 700;	Thickness of the text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
input:not([type="radio"]):not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
flex: 1 1 8rem;	The item can grow and shrink from the given basis.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.
background: var(--brand);	Background colour or image.

Check your work

- Radios share one name
- Date min prevents past dates
- Every control labelled
- Checkbox required works

Exercises

1. Show one fieldset at a time with :has() and radio state or JavaScript.
2. Add a summary panel that updates live.
3. Add a progress tracker on top.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 854: Booking form in three steps for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 2 | Files: index.html, styles.css

Brief

Build a longer form divided into three fieldsets: radio choice with prices, date/time/number inputs, and personal details with a required checkbox.

Learning goals

- Group related controls with fieldset and legend
- Use date, time, number and tel input types with min/max/step
- Use wrapping labels

Elements and CSS used

HTML elements	CSS features
form, fieldset, legend, label, input (radio, date, time, number, text, tel, checkbox), small, button	fieldset border/radius, legend, display: flex on label, margin-left: auto, :not() chains

Build guide

1. Write three fieldsets with legends numbered 1 to 3.
2. Step 1: radio buttons with the same name, each wrapped in a label with the price in <small>.
3. Step 2: date, time and number inputs with limits.
4. Step 3: text, tel and a required checkbox.
5. Grid the form and fieldsets.

6. Push prices right with margin-left: auto.

Project 854: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - Booking</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Book a service</h1>
    <form action="/book" method="post" class="wizard">
      <fieldset>
        <legend>1. Choose a service</legend>
    <label><input type="radio" name="item" value="Check-up" required>
Check-up <small>300 EGP</small></label>
    <label><input type="radio" name="item" value="Whitening"
required> Whitening <small>1500 EGP</small></label>
    <label><input type="radio" name="item" value="Filling" required>
Filling <small>600 EGP</small></label>
    <label><input type="radio" name="item" value="Braces
consultation" required> Braces consultation <small>Free</small></
label>
      </fieldset>
      <fieldset>
        <legend>2. When</legend>
        <label>Date <input type="date" name="date" required min="2026-
09-11"></label>
        <label>Time <input type="time" name="time" required
step="1800"></label>
        <label>People <input type="number" name="people" min="1"
max="10" value="1"></label>
      </fieldset>
      <fieldset>
        <legend>3. Your details</legend>
        <label>Name <input type="text" name="name" required
autocomplete="name"></label>
        <label>Phone <input type="tel" name="phone" required
autocomplete="tel" inputmode="tel"></label>
        <label><input type="checkbox" name="terms" required> I agree
to the cancellation policy</label>
      </fieldset>
      <button type="submit">Confirm booking</button>
    </form>
  </main>
</body>
</html>
```

Project 854: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.wizard { display: grid; gap: 1.5rem; }
fieldset { border: 1px solid var(--line); border-radius: 12px;
padding: 1rem 1.25rem; display: grid; gap: .6rem; }
legend { font-weight: 700; color: var(--brand); padding: 0 .4rem; }
label { display: flex; align-items: center; gap: .5rem; flex-wrap:
wrap; }
label small { margin-left: auto; color: var(--muted); }
input:not([type="radio"]):not([type="checkbox"]) { padding: .5rem .
7rem; border: 1px solid #bbb; border-radius: 8px; font: inherit; flex:
 1 1 8rem; }
button { justify-self: start; padding: .8rem 1.6rem; border: 0;
border-radius: 999px; background: var(--brand); color: #fff; font:
inherit; }
```

Project 854 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - Booking</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Book a service	The main heading; only one per page.
<form action="/book" method="post" class="wizard">	A form; action is where the data goes, method how it is sent.
<fieldset>	Groups related form controls.
<legend>1. Choose a service</legend>	Caption for the fieldset.
<label><input type="radio" name="item" value="Check-up" required> C...	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<label><input type="radio" name="item" value="Whitening" required> ...	Radio button: one choice from a group sharing the same name.
<label><input type="radio" name="item" value="Filling" required> Fi...	A form control; its type decides what it looks like.
<label><input type="radio" name="item" value="Braces consultation" ...	The field must be filled before the form can be submitted.
<label>Date <input type="date" name="date" required min="2026-09-11...	Date picker.
<label>Time <input type="time" name="time" required step="1800"></l...	Time picker.
<label>People <input type="number" name="people" min="1" max="10" v...	Numeric input with min, max and step.
<label>Name <input type="text" name="name" required autocomplete="n...	Tells the browser which saved value to offer (name, email, tel...).
<label>Phone <input type="tel" name="phone" required autocomplete="...	Telephone number; shows the phone keypad on mobiles.
<label><input type="checkbox" name="terms" required> I agree to the...	Checkbox: on or off.
<button type="submit">Confirm booking</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.
font-weight: 700;	Thickness of the text.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
input:not([type="radio"]):not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
flex: 1 1 8rem;	The item can grow and shrink from the given basis.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.
background: var(--brand);	Background colour or image.

Check your work

- Radios share one name
- Date min prevents past dates
- Every control labelled
- Checkbox required works

Exercises

1. Show one fieldset at a time with :has() and radio state or JavaScript.
2. Add a summary panel that updates live.
3. Add a progress tracker on top.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 855: Booking form in three steps for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 2 | Files: index.html, styles.css

Brief

Build a longer form divided into three fieldsets: radio choice with prices, date/time/number inputs, and personal details with a required checkbox.

Learning goals

- Group related controls with fieldset and legend
- Use date, time, number and tel input types with min/max/step
- Use wrapping labels

Elements and CSS used

HTML elements	CSS features
form, fieldset, legend, label, input (radio, date, time, number, text, tel, checkbox), small, button	fieldset border/radius, legend, display: flex on label, margin-left: auto, :not() chains

Build guide

1. Write three fieldsets with legends numbered 1 to 3.
2. Step 1: radio buttons with the same name, each wrapped in a label with the price in <small>.
3. Step 2: date, time and number inputs with limits.
4. Step 3: text, tel and a required checkbox.
5. Grid the form and fieldsets.
6. Push prices right with margin-left: auto.

Project 855: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - Booking</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Book a tour</h1>
    <form action="/book" method="post" class="wizard">
      <fieldset>
        <legend>1. Choose a tour</legend>
    <label><input type="radio" name="item" value="Luxor day trip"
required> Luxor day trip <small>1200 EGP</small></label>
    <label><input type="radio" name="item" value="Snorkelling"
required> Snorkelling <small>700 EGP</small></label>
    <label><input type="radio" name="item" value="Desert safari"
required> Desert safari <small>900 EGP</small></label>
    <label><input type="radio" name="item" value="Nile cruise"
required> Nile cruise <small>6500 EGP</small></label>
      </fieldset>
      <fieldset>
        <legend>2. When</legend>
        <label>Date <input type="date" name="date" required min="2026-
09-11"></label>
        <label>Time <input type="time" name="time" required
step="1800"></label>
        <label>People <input type="number" name="people" min="1"
max="10" value="1"></label>
      </fieldset>
      <fieldset>
        <legend>3. Your details</legend>
        <label>Name <input type="text" name="name" required
autocomplete="name"></label>
        <label>Phone <input type="tel" name="phone" required
autocomplete="tel" inputmode="tel"></label>
        <label><input type="checkbox" name="terms" required> I agree
to the cancellation policy</label>
      </fieldset>
      <button type="submit">Confirm booking</button>
    </form>
  </main>
</body>
</html>
```

Project 855: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.wizard { display: grid; gap: 1.5rem; }
fieldset { border: 1px solid var(--line); border-radius: 12px;
padding: 1rem 1.25rem; display: grid; gap: .6rem; }
legend { font-weight: 700; color: var(--brand); padding: 0 .4rem; }
label { display: flex; align-items: center; gap: .5rem; flex-wrap:
wrap; }
label small { margin-left: auto; color: var(--muted); }
input:not([type="radio"]):not([type="checkbox"]) { padding: .5rem .
7rem; border: 1px solid #bbb; border-radius: 8px; font: inherit; flex:
 1 1 8rem; }
button { justify-self: start; padding: .8rem 1.6rem; border: 0;
border-radius: 999px; background: var(--brand); color: #fff; font:
inherit; }
```

Project 855 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - Booking</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Book a tour	The main heading; only one per page.
<form action="/book" method="post" class="wizard">	A form; action is where the data goes, method how it is sent.
<fieldset>	Groups related form controls.
<legend>1. Choose a tour</legend>	Caption for the fieldset.
<label><input type="radio" name="item" value="Luxor day trip" requi...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="item" value="Snorkelling" required...	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="item" value="Desert safari" requir...	A form control; its type decides what it looks like.
<label><input type="radio" name="item" value="Nile cruise" required...	The field must be filled before the form can be submitted.
<label>Date <input type="date" name="date" required min="2026-09-11...	Date picker.
<label>Time <input type="time" name="time" required step="1800"></l...	Time picker.
<label>People <input type="number" name="people" min="1" max="10" v...	Numeric input with min, max and step.
<label>Name <input type="text" name="name" required autocomplete="n...	Tells the browser which saved value to offer (name, email, tel...).
<label>Phone <input type="tel" name="phone" required autocomplete="...	Telephone number; shows the phone keypad on mobiles.
<label><input type="checkbox" name="terms" required> I agree to the...	Checkbox: on or off.
<button type="submit">Confirm booking</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.
font-weight: 700;	Thickness of the text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
input:not([type="radio"]):not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
flex: 1 1 8rem;	The item can grow and shrink from the given basis.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.
background: var(--brand);	Background colour or image.

Check your work

- Radios share one name
- Date min prevents past dates
- Every control labelled
- Checkbox required works

Exercises

1. Show one fieldset at a time with :has() and radio state or JavaScript.
2. Add a summary panel that updates live.
3. Add a progress tracker on top.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 856: Booking form in three steps for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Build a longer form divided into three fieldsets: radio choice with prices, date/time/number inputs, and personal details with a required checkbox.

Learning goals

- Group related controls with fieldset and legend
- Use date, time, number and tel input types with min/max/step
- Use wrapping labels

Elements and CSS used

HTML elements	CSS features
form, fieldset, legend, label, input (radio, date, time, number, text, tel, checkbox), small, button	fieldset border/radius, legend, display: flex on label, margin-left: auto, :not() chains

Build guide

1. Write three fieldsets with legends numbered 1 to 3.
2. Step 1: radio buttons with the same name, each wrapped in a label with the price in <small>.
3. Step 2: date, time and number inputs with limits.
4. Step 3: text, tel and a required checkbox.
5. Grid the form and fieldsets.

6. Push prices right with margin-left: auto.

Project 856: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - Booking</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Book a course</h1>
    <form action="/book" method="post" class="wizard">
      <fieldset>
        <legend>1. Choose a course</legend>
    <label><input type="radio" name="item" value="English A1"
required> English A1 <small>1800 EGP</small></label>
    <label><input type="radio" name="item" value="French B1"
required> French B1 <small>2200 EGP</small></label>
    <label><input type="radio" name="item" value="German A2"
required> German A2 <small>2000 EGP</small></label>
    <label><input type="radio" name="item" value="IELTS preparation"
required> IELTS preparation <small>3000 EGP</small></label>
      </fieldset>
      <fieldset>
        <legend>2. When</legend>
        <label>Date <input type="date" name="date" required min="2026-
09-11"></label>
        <label>Time <input type="time" name="time" required
step="1800"></label>
        <label>People <input type="number" name="people" min="1"
max="10" value="1"></label>
      </fieldset>
      <fieldset>
        <legend>3. Your details</legend>
        <label>Name <input type="text" name="name" required
autocomplete="name"></label>
        <label>Phone <input type="tel" name="phone" required
autocomplete="tel" inputmode="tel"></label>
        <label><input type="checkbox" name="terms" required> I agree
to the cancellation policy</label>
      </fieldset>
      <button type="submit">Confirm booking</button>
    </form>
  </main>
</body>
</html>
```

Project 856: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.wizard { display: grid; gap: 1.5rem; }
fieldset { border: 1px solid var(--line); border-radius: 12px;
padding: 1rem 1.25rem; display: grid; gap: .6rem; }
legend { font-weight: 700; color: var(--brand); padding: 0 .4rem; }
label { display: flex; align-items: center; gap: .5rem; flex-wrap:
wrap; }
label small { margin-left: auto; color: var(--muted); }
input:not([type="radio"]):not([type="checkbox"]) { padding: .5rem .
7rem; border: 1px solid #bbb; border-radius: 8px; font: inherit; flex:
 1 1 8rem; }
button { justify-self: start; padding: .8rem 1.6rem; border: 0;
border-radius: 999px; background: var(--brand); color: #fff; font:
inherit; }
```

Project 856 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - Booking</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Book a course	The main heading; only one per page.
<form action="/book" method="post" class="wizard">	A form; action is where the data goes, method how it is sent.
<fieldset>	Groups related form controls.
<legend>1. Choose a course</legend>	Caption for the fieldset.
<label><input type="radio" name="item" value="English A1" required>...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="item" value="French B1" required> ...	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="item" value="German A2" required> ...	A form control; its type decides what it looks like.
<label><input type="radio" name="item" value="IELTS preparation" re...	The field must be filled before the form can be submitted.
<label>Date <input type="date" name="date" required min="2026-09-11...	Date picker.
<label>Time <input type="time" name="time" required step="1800"></l...	Time picker.
<label>People <input type="number" name="people" min="1" max="10" v...	Numeric input with min, max and step.
<label>Name <input type="text" name="name" required autocomplete="n...	Tells the browser which saved value to offer (name, email, tel...).
<label>Phone <input type="tel" name="phone" required autocomplete="...	Telephone number; shows the phone keypad on mobiles.
<label><input type="checkbox" name="terms" required> I agree to the...	Checkbox: on or off.
<button type="submit">Confirm booking</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.
font-weight: 700;	Thickness of the text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
input:not([type="radio"]):not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
flex: 1 1 8rem;	The item can grow and shrink from the given basis.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.
background: var(--brand);	Background colour or image.

Check your work

- Radios share one name
- Date min prevents past dates
- Every control labelled
- Checkbox required works

Exercises

1. Show one fieldset at a time with :has() and radio state or JavaScript.
2. Add a summary panel that updates live.
3. Add a progress tracker on top.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 857: Booking form in three steps for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 2 | Files: index.html, styles.css

Brief

Build a longer form divided into three fieldsets: radio choice with prices, date/time/number inputs, and personal details with a required checkbox.

Learning goals

- Group related controls with fieldset and legend
- Use date, time, number and tel input types with min/max/step
- Use wrapping labels

Elements and CSS used

HTML elements	CSS features
form, fieldset, legend, label, input (radio, date, time, number, text, tel, checkbox), small, button	fieldset border/radius, legend, display: flex on label, margin-left: auto, :not() chains

Build guide

1. Write three fieldsets with legends numbered 1 to 3.
2. Step 1: radio buttons with the same name, each wrapped in a label with the price in <small>.
3. Step 2: date, time and number inputs with limits.
4. Step 3: text, tel and a required checkbox.
5. Grid the form and fieldsets.
6. Push prices right with margin-left: auto.

Project 857: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - Booking</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Book a drink</h1>
    <form action="/book" method="post" class="wizard">
      <fieldset>
        <legend>1. Choose a drink</legend>
    <label><input type="radio" name="item" value="Flat white"
required> Flat white <small>55 EGP</small></label>
    <label><input type="radio" name="item" value="Cold brew"
required> Cold brew <small>60 EGP</small></label>
    <label><input type="radio" name="item" value="Hibiscus iced tea"
required> Hibiscus iced tea <small>40 EGP</small></label>
    <label><input type="radio" name="item" value="Cheesecake"
required> Cheesecake <small>75 EGP</small></label>
      </fieldset>
      <fieldset>
        <legend>2. When</legend>
        <label>Date <input type="date" name="date" required min="2026-
09-11"></label>
        <label>Time <input type="time" name="time" required
step="1800"></label>
        <label>People <input type="number" name="people" min="1"
max="10" value="1"></label>
      </fieldset>
      <fieldset>
        <legend>3. Your details</legend>
        <label>Name <input type="text" name="name" required
autocomplete="name"></label>
        <label>Phone <input type="tel" name="phone" required
autocomplete="tel" inputmode="tel"></label>
        <label><input type="checkbox" name="terms" required> I agree
to the cancellation policy</label>
      </fieldset>
      <button type="submit">Confirm booking</button>
    </form>
  </main>
</body>
</html>
```

Project 857: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.wizard { display: grid; gap: 1.5rem; }
fieldset { border: 1px solid var(--line); border-radius: 12px;
padding: 1rem 1.25rem; display: grid; gap: .6rem; }
legend { font-weight: 700; color: var(--brand); padding: 0 .4rem; }
label { display: flex; align-items: center; gap: .5rem; flex-wrap:
wrap; }
label small { margin-left: auto; color: var(--muted); }
input:not([type="radio"]):not([type="checkbox"]) { padding: .5rem .
7rem; border: 1px solid #bbb; border-radius: 8px; font: inherit; flex:
 1 1 8rem; }
button { justify-self: start; padding: .8rem 1.6rem; border: 0;
border-radius: 999px; background: var(--brand); color: #fff; font:
inherit; }
```

Project 857 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - Booking</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Book a drink	The main heading; only one per page.
<form action="/book" method="post" class="wizard">	A form; action is where the data goes, method how it is sent.
<fieldset>	Groups related form controls.
<legend>1. Choose a drink</legend>	Caption for the fieldset.
<label><input type="radio" name="item" value="Flat white" required>...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="item" value="Cold brew" required> ...	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="item" value="Hibiscus iced tea" re...	A form control; its type decides what it looks like.
<label><input type="radio" name="item" value="Cheesecake" required>...	The field must be filled before the form can be submitted.
<label>Date <input type="date" name="date" required min="2026-09-11...	Date picker.
<label>Time <input type="time" name="time" required step="1800"></l...	Time picker.
<label>People <input type="number" name="people" min="1" max="10" v...	Numeric input with min, max and step.
<label>Name <input type="text" name="name" required autocomplete="n...	Tells the browser which saved value to offer (name, email, tel...).
<label>Phone <input type="tel" name="phone" required autocomplete="...	Telephone number; shows the phone keypad on mobiles.
<label><input type="checkbox" name="terms" required> I agree to the...	Checkbox: on or off.
<button type="submit">Confirm booking</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.
font-weight: 700;	Thickness of the text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
input:not([type="radio"]):not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
flex: 1 1 8rem;	The item can grow and shrink from the given basis.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.
background: var(--brand);	Background colour or image.

Check your work

- Radios share one name
- Date min prevents past dates
- Every control labelled
- Checkbox required works

Exercises

1. Show one fieldset at a time with :has() and radio state or JavaScript.
2. Add a summary panel that updates live.
3. Add a progress tracker on top.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 858: Booking form in three steps for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 2 | Files: index.html, styles.css

Brief

Build a longer form divided into three fieldsets: radio choice with prices, date/time/number inputs, and personal details with a required checkbox.

Learning goals

- Group related controls with fieldset and legend
- Use date, time, number and tel input types with min/max/step
- Use wrapping labels

Elements and CSS used

HTML elements	CSS features
form, fieldset, legend, label, input (radio, date, time, number, text, tel, checkbox), small, button	fieldset border/radius, legend, display: flex on label, margin-left: auto, :not() chains

Build guide

1. Write three fieldsets with legends numbered 1 to 3.
2. Step 1: radio buttons with the same name, each wrapped in a label with the price in <small>.
3. Step 2: date, time and number inputs with limits.
4. Step 3: text, tel and a required checkbox.
5. Grid the form and fieldsets.

6. Push prices right with margin-left: auto.

Project 858: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - Booking</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Book a hike</h1>
    <form action="/book" method="post" class="wizard">
      <fieldset>
        <legend>1. Choose a hike</legend>
    <label><input type="radio" name="item" value="Mount Sinai
sunrise" required> Mount Sinai sunrise <small>400 EGP</small></label>
    <label><input type="radio" name="item" value="Blue Desert loop"
required> Blue Desert loop <small>250 EGP</small></label>
    <label><input type="radio" name="item" value="Wadi Gnai"
required> Wadi Gnai <small>300 EGP</small></label>
    <label><input type="radio" name="item" value="Three-day traverse"
required> Three-day traverse <small>1900 EGP</small></label>
      </fieldset>
      <fieldset>
        <legend>2. When</legend>
        <label>Date <input type="date" name="date" required min="2026-
09-11"></label>
        <label>Time <input type="time" name="time" required
step="1800"></label>
        <label>People <input type="number" name="people" min="1"
max="10" value="1"></label>
      </fieldset>
      <fieldset>
        <legend>3. Your details</legend>
        <label>Name <input type="text" name="name" required
autocomplete="name"></label>
        <label>Phone <input type="tel" name="phone" required
autocomplete="tel" inputmode="tel"></label>
        <label><input type="checkbox" name="terms" required> I agree
to the cancellation policy</label>
      </fieldset>
      <button type="submit">Confirm booking</button>
    </form>
  </main>
</body>
</html>
```

Project 858: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.wizard { display: grid; gap: 1.5rem; }
fieldset { border: 1px solid var(--line); border-radius: 12px;
padding: 1rem 1.25rem; display: grid; gap: .6rem; }
legend { font-weight: 700; color: var(--brand); padding: 0 .4rem; }
label { display: flex; align-items: center; gap: .5rem; flex-wrap:
wrap; }
label small { margin-left: auto; color: var(--muted); }
input:not([type="radio"]):not([type="checkbox"]) { padding: .5rem .
7rem; border: 1px solid #bbb; border-radius: 8px; font: inherit; flex:
 1 1 8rem; }
button { justify-self: start; padding: .8rem 1.6rem; border: 0;
border-radius: 999px; background: var(--brand); color: #fff; font:
inherit; }
```

Project 858 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - Booking</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Book a hike	The main heading; only one per page.
<form action="/book" method="post" class="wizard">	A form; action is where the data goes, method how it is sent.
<fieldset>	Groups related form controls.
<legend>1. Choose a hike</legend>	Caption for the fieldset.
<label><input type="radio" name="item" value="Mount Sinai sunrise" ...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="item" value="Blue Desert loop" req...	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="item" value="Wadi Gnai" required> ...	A form control; its type decides what it looks like.
<label><input type="radio" name="item" value="Three-day traverse" r...	The field must be filled before the form can be submitted.
<label>Date <input type="date" name="date" required min="2026-09-11...	Date picker.
<label>Time <input type="time" name="time" required step="1800"></l...	Time picker.
<label>People <input type="number" name="people" min="1" max="10" v...	Numeric input with min, max and step.
<label>Name <input type="text" name="name" required autocomplete="n...	Tells the browser which saved value to offer (name, email, tel...).
<label>Phone <input type="tel" name="phone" required autocomplete="...	Telephone number; shows the phone keypad on mobiles.
<label><input type="checkbox" name="terms" required> I agree to the...	Checkbox: on or off.
<button type="submit">Confirm booking</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.
font-weight: 700;	Thickness of the text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
input:not([type="radio"]):not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
flex: 1 1 8rem;	The item can grow and shrink from the given basis.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.
background: var(--brand);	Background colour or image.

Check your work

- Radios share one name
- Date min prevents past dates
- Every control labelled
- Checkbox required works

Exercises

1. Show one fieldset at a time with :has() and radio state or JavaScript.
2. Add a summary panel that updates live.
3. Add a progress tracker on top.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 859: Booking form in three steps for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 2 | Files: index.html, styles.css

Brief

Build a longer form divided into three fieldsets: radio choice with prices, date/time/number inputs, and personal details with a required checkbox.

Learning goals

- Group related controls with fieldset and legend
- Use date, time, number and tel input types with min/max/step
- Use wrapping labels

Elements and CSS used

HTML elements	CSS features
form, fieldset, legend, label, input (radio, date, time, number, text, tel, checkbox), small, button	fieldset border/radius, legend, display: flex on label, margin-left: auto, :not() chains

Build guide

1. Write three fieldsets with legends numbered 1 to 3.
2. Step 1: radio buttons with the same name, each wrapped in a label with the price in <small>.
3. Step 2: date, time and number inputs with limits.
4. Step 3: text, tel and a required checkbox.
5. Grid the form and fieldsets.

6. Push prices right with margin-left: auto.

Project 859: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - Booking</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Book a session</h1>
    <form action="/book" method="post" class="wizard">
      <fieldset>
        <legend>1. Choose a session</legend>
    <label><input type="radio" name="item" value="Portrait session"
required> Portrait session <small>1200 EGP</small></label>
    <label><input type="radio" name="item" value="Wedding day"
required> Wedding day <small>15000 EGP</small></label>
    <label><input type="radio" name="item" value="Product shoot"
required> Product shoot <small>900 EGP</small></label>
    <label><input type="radio" name="item" value="Family session"
required> Family session <small>1500 EGP</small></label>
      </fieldset>
      <fieldset>
        <legend>2. When</legend>
        <label>Date <input type="date" name="date" required min="2026-
09-11"></label>
        <label>Time <input type="time" name="time" required
step="1800"></label>
        <label>People <input type="number" name="people" min="1"
max="10" value="1"></label>
      </fieldset>
      <fieldset>
        <legend>3. Your details</legend>
        <label>Name <input type="text" name="name" required
autocomplete="name"></label>
        <label>Phone <input type="tel" name="phone" required
autocomplete="tel" inputmode="tel"></label>
        <label><input type="checkbox" name="terms" required> I agree
to the cancellation policy</label>
      </fieldset>
      <button type="submit">Confirm booking</button>
    </form>
  </main>
</body>
</html>
```

Project 859: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.wizard { display: grid; gap: 1.5rem; }
fieldset { border: 1px solid var(--line); border-radius: 12px;
padding: 1rem 1.25rem; display: grid; gap: .6rem; }
legend { font-weight: 700; color: var(--brand); padding: 0 .4rem; }
label { display: flex; align-items: center; gap: .5rem; flex-wrap:
wrap; }
label small { margin-left: auto; color: var(--muted); }
input:not([type="radio"]):not([type="checkbox"]) { padding: .5rem .
7rem; border: 1px solid #bbb; border-radius: 8px; font: inherit; flex:
 1 1 8rem; }
button { justify-self: start; padding: .8rem 1.6rem; border: 0;
border-radius: 999px; background: var(--brand); color: #fff; font:
inherit; }
```

Project 859 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - Booking</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Book a session	The main heading; only one per page.
<form action="/book" method="post" class="wizard">	A form; action is where the data goes, method how it is sent.
<fieldset>	Groups related form controls.
<legend>1. Choose a session</legend>	Caption for the fieldset.
<label><input type="radio" name="item" value="Portrait session" req...	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<label><input type="radio" name="item" value="Wedding day" required...	Radio button: one choice from a group sharing the same name.
<label><input type="radio" name="item" value="Product shoot" requir...	A form control; its type decides what it looks like.
<label><input type="radio" name="item" value="Family session" requi...	The field must be filled before the form can be submitted.
<label>Date <input type="date" name="date" required min="2026-09-11...	Date picker.
<label>Time <input type="time" name="time" required step="1800"></l...	Time picker.
<label>People <input type="number" name="people" min="1" max="10" v...	Numeric input with min, max and step.
<label>Name <input type="text" name="name" required autocomplete="n...	Tells the browser which saved value to offer (name, email, tel...).
<label>Phone <input type="tel" name="phone" required autocomplete="...	Telephone number; shows the phone keypad on mobiles.
<label><input type="checkbox" name="terms" required> I agree to the...	Checkbox: on or off.
<button type="submit">Confirm booking</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.
font-weight: 700;	Thickness of the text.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
input:not([type="radio"]):not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
flex: 1 1 8rem;	The item can grow and shrink from the given basis.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.
background: var(--brand);	Background colour or image.

Check your work

- Radios share one name
- Date min prevents past dates
- Every control labelled
- Checkbox required works

Exercises

1. Show one fieldset at a time with :has() and radio state or JavaScript.
2. Add a summary panel that updates live.
3. Add a progress tracker on top.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 860: Booking form in three steps for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 2 | Files: index.html, styles.css

Brief

Build a longer form divided into three fieldsets: radio choice with prices, date/time/number inputs, and personal details with a required checkbox.

Learning goals

- Group related controls with fieldset and legend
- Use date, time, number and tel input types with min/max/step
- Use wrapping labels

Elements and CSS used

HTML elements	CSS features
form, fieldset, legend, label, input (radio, date, time, number, text, tel, checkbox), small, button	fieldset border/radius, legend, display: flex on label, margin-left: auto, :not() chains

Build guide

1. Write three fieldsets with legends numbered 1 to 3.
2. Step 1: radio buttons with the same name, each wrapped in a label with the price in <small>.
3. Step 2: date, time and number inputs with limits.
4. Step 3: text, tel and a required checkbox.
5. Grid the form and fieldsets.

6. Push prices right with margin-left: auto.

Project 860: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - Booking</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Book a product</h1>
    <form action="/book" method="post" class="wizard">
      <fieldset>
        <legend>1. Choose a product</legend>
    <label><input type="radio" name="item" value="Dotted notebook"
required> Dotted notebook <small>140 EGP</small></label>
    <label><input type="radio" name="item" value="Fountain pen"
required> Fountain pen <small>350 EGP</small></label>
    <label><input type="radio" name="item" value="Washi tape set"
required> Washi tape set <small>90 EGP</small></label>
    <label><input type="radio" name="item" value="Desk planner"
required> Desk planner <small>110 EGP</small></label>
      </fieldset>
      <fieldset>
        <legend>2. When</legend>
        <label>Date <input type="date" name="date" required min="2026-
09-11"></label>
        <label>Time <input type="time" name="time" required
step="1800"></label>
        <label>People <input type="number" name="people" min="1"
max="10" value="1"></label>
      </fieldset>
      <fieldset>
        <legend>3. Your details</legend>
        <label>Name <input type="text" name="name" required
autocomplete="name"></label>
        <label>Phone <input type="tel" name="phone" required
autocomplete="tel" inputmode="tel"></label>
        <label><input type="checkbox" name="terms" required> I agree
to the cancellation policy</label>
      </fieldset>
      <button type="submit">Confirm booking</button>
    </form>
  </main>
</body>
</html>
```

Project 860: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.wizard { display: grid; gap: 1.5rem; }
fieldset { border: 1px solid var(--line); border-radius: 12px;
padding: 1rem 1.25rem; display: grid; gap: .6rem; }
legend { font-weight: 700; color: var(--brand); padding: 0 .4rem; }
label { display: flex; align-items: center; gap: .5rem; flex-wrap:
wrap; }
label small { margin-left: auto; color: var(--muted); }
input:not([type="radio"]):not([type="checkbox"]) { padding: .5rem .
7rem; border: 1px solid #bbb; border-radius: 8px; font: inherit; flex:
 1 1 8rem; }
button { justify-self: start; padding: .8rem 1.6rem; border: 0;
border-radius: 999px; background: var(--brand); color: #fff; font:
inherit; }
```

Project 860 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - Booking</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Book a product	The main heading; only one per page.
<form action="/book" method="post" class="wizard">	A form; action is where the data goes, method how it is sent.
<fieldset>	Groups related form controls.
<legend>1. Choose a product</legend>	Caption for the fieldset.
<label><input type="radio" name="item" value="Dotted notebook" requ...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="item" value="Fountain pen" require...	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="item" value="Washi tape set" requi...	A form control; its type decides what it looks like.
<label><input type="radio" name="item" value="Desk planner" require...	The field must be filled before the form can be submitted.
<label>Date <input type="date" name="date" required min="2026-09-11...	Date picker.
<label>Time <input type="time" name="time" required step="1800"></l...	Time picker.
<label>People <input type="number" name="people" min="1" max="10" v...	Numeric input with min, max and step.
<label>Name <input type="text" name="name" required autocomplete="n...	Tells the browser which saved value to offer (name, email, tel...).
<label>Phone <input type="tel" name="phone" required autocomplete="...	Telephone number; shows the phone keypad on mobiles.
<label><input type="checkbox" name="terms" required> I agree to the...	Checkbox: on or off.
<button type="submit">Confirm booking</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.
font-weight: 700;	Thickness of the text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
input:not([type="radio"]):not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
flex: 1 1 8rem;	The item can grow and shrink from the given basis.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.
background: var(--brand);	Background colour or image.

Check your work

- Radios share one name
- Date min prevents past dates
- Every control labelled
- Checkbox required works

Exercises

1. Show one fieldset at a time with :has() and radio state or JavaScript.
2. Add a summary panel that updates live.
3. Add a progress tracker on top.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 861: Booking form in three steps for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 2 | Files: index.html, styles.css

Brief

Build a longer form divided into three fieldsets: radio choice with prices, date/time/number inputs, and personal details with a required checkbox.

Learning goals

- Group related controls with fieldset and legend
- Use date, time, number and tel input types with min/max/step
- Use wrapping labels

Elements and CSS used

HTML elements	CSS features
form, fieldset, legend, label, input (radio, date, time, number, text, tel, checkbox), small, button	fieldset border/radius, legend, display: flex on label, margin-left: auto, :not() chains

Build guide

1. Write three fieldsets with legends numbered 1 to 3.
2. Step 1: radio buttons with the same name, each wrapped in a label with the price in <small>.
3. Step 2: date, time and number inputs with limits.
4. Step 3: text, tel and a required checkbox.
5. Grid the form and fieldsets.

6. Push prices right with margin-left: auto.

Project 861: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - Booking</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Book a plant</h1>
    <form action="/book" method="post" class="wizard">
      <fieldset>
        <legend>1. Choose a plant</legend>
    <label><input type="radio" name="item" value="Monstera" required>
Monstera <small>250 EGP</small></label>
    <label><input type="radio" name="item" value="Snake plant"
required> Snake plant <small>120 EGP</small></label>
    <label><input type="radio" name="item" value="Basil pot"
required> Basil pot <small>45 EGP</small></label>
    <label><input type="radio" name="item" value="Olive tree"
required> Olive tree <small>600 EGP</small></label>
      </fieldset>
      <fieldset>
        <legend>2. When</legend>
        <label>Date <input type="date" name="date" required min="2026-
09-11"></label>
        <label>Time <input type="time" name="time" required
step="1800"></label>
        <label>People <input type="number" name="people" min="1"
max="10" value="1"></label>
      </fieldset>
      <fieldset>
        <legend>3. Your details</legend>
        <label>Name <input type="text" name="name" required
autocomplete="name"></label>
        <label>Phone <input type="tel" name="phone" required
autocomplete="tel" inputmode="tel"></label>
        <label><input type="checkbox" name="terms" required> I agree
to the cancellation policy</label>
      </fieldset>
      <button type="submit">Confirm booking</button>
    </form>
  </main>
</body>
</html>
```

Project 861: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.wizard { display: grid; gap: 1.5rem; }
fieldset { border: 1px solid var(--line); border-radius: 12px;
padding: 1rem 1.25rem; display: grid; gap: .6rem; }
legend { font-weight: 700; color: var(--brand); padding: 0 .4rem; }
label { display: flex; align-items: center; gap: .5rem; flex-wrap:
wrap; }
label small { margin-left: auto; color: var(--muted); }
input:not([type="radio"]):not([type="checkbox"]) { padding: .5rem .
7rem; border: 1px solid #bbb; border-radius: 8px; font: inherit; flex:
 1 1 8rem; }
button { justify-self: start; padding: .8rem 1.6rem; border: 0;
border-radius: 999px; background: var(--brand); color: #fff; font:
inherit; }
```

Project 861 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - Booking</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Book a plant	The main heading; only one per page.
<form action="/book" method="post" class="wizard">	A form; action is where the data goes, method how it is sent.
<fieldset>	Groups related form controls.
<legend>1. Choose a plant</legend>	Caption for the fieldset.
<label><input type="radio" name="item" value="Monstera" required> M...	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<label><input type="radio" name="item" value="Snake plant" required...	Radio button: one choice from a group sharing the same name.
<label><input type="radio" name="item" value="Basil pot" required> ...	A form control; its type decides what it looks like.
<label><input type="radio" name="item" value="Olive tree" required>...	The field must be filled before the form can be submitted.
<label>Date <input type="date" name="date" required min="2026-09-11...	Date picker.
<label>Time <input type="time" name="time" required step="1800"></l...	Time picker.
<label>People <input type="number" name="people" min="1" max="10" v...	Numeric input with min, max and step.
<label>Name <input type="text" name="name" required autocomplete="n...	Tells the browser which saved value to offer (name, email, tel...).
<label>Phone <input type="tel" name="phone" required autocomplete="...	Telephone number; shows the phone keypad on mobiles.
<label><input type="checkbox" name="terms" required> I agree to the...	Checkbox: on or off.
<button type="submit">Confirm booking</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.
font-weight: 700;	Thickness of the text.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
align-items: center;	Centres items on the cross axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
input:not([type="radio"]):not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
flex: 1 1 8rem;	The item can grow and shrink from the given basis.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.
background: var(--brand);	Background colour or image.

Check your work

- Radios share one name
- Date min prevents past dates
- Every control labelled
- Checkbox required works

Exercises

1. Show one fieldset at a time with :has() and radio state or JavaScript.
2. Add a summary panel that updates live.
3. Add a progress tracker on top.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 862: Booking form in three steps for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 2 | Files: index.html, styles.css

Brief

Build a longer form divided into three fieldsets: radio choice with prices, date/time/number inputs, and personal details with a required checkbox.

Learning goals

- Group related controls with fieldset and legend
- Use date, time, number and tel input types with min/max/step
- Use wrapping labels

Elements and CSS used

HTML elements	CSS features
form, fieldset, legend, label, input (radio, date, time, number, text, tel, checkbox), small, button	fieldset border/radius, legend, display: flex on label, margin-left: auto, :not() chains

Build guide

1. Write three fieldsets with legends numbered 1 to 3.
2. Step 1: radio buttons with the same name, each wrapped in a label with the price in <small>.
3. Step 2: date, time and number inputs with limits.
4. Step 3: text, tel and a required checkbox.
5. Grid the form and fieldsets.

6. Push prices right with margin-left: auto.

Project 862: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - Booking</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Book a piece</h1>
    <form action="/book" method="post" class="wizard">
      <fieldset>
        <legend>1. Choose a piece</legend>
    <label><input type="radio" name="item" value="Oak dining table"
required> Oak dining table <small>9500 EGP</small></label>
    <label><input type="radio" name="item" value="Bookshelf"
required> Bookshelf <small>4200 EGP</small></label>
    <label><input type="radio" name="item" value="Bedside table"
required> Bedside table <small>1500 EGP</small></label>
    <label><input type="radio" name="item" value="Coffee table"
required> Coffee table <small>2800 EGP</small></label>
      </fieldset>
      <fieldset>
        <legend>2. When</legend>
        <label>Date <input type="date" name="date" required min="2026-
09-11"></label>
        <label>Time <input type="time" name="time" required
step="1800"></label>
        <label>People <input type="number" name="people" min="1"
max="10" value="1"></label>
      </fieldset>
      <fieldset>
        <legend>3. Your details</legend>
        <label>Name <input type="text" name="name" required
autocomplete="name"></label>
        <label>Phone <input type="tel" name="phone" required
autocomplete="tel" inputmode="tel"></label>
        <label><input type="checkbox" name="terms" required> I agree
to the cancellation policy</label>
      </fieldset>
      <button type="submit">Confirm booking</button>
    </form>
  </main>
</body>
</html>
```

Project 862: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.wizard { display: grid; gap: 1.5rem; }
fieldset { border: 1px solid var(--line); border-radius: 12px;
padding: 1rem 1.25rem; display: grid; gap: .6rem; }
legend { font-weight: 700; color: var(--brand); padding: 0 .4rem; }
label { display: flex; align-items: center; gap: .5rem; flex-wrap:
wrap; }
label small { margin-left: auto; color: var(--muted); }
input:not([type="radio"]):not([type="checkbox"]) { padding: .5rem .
7rem; border: 1px solid #bbb; border-radius: 8px; font: inherit; flex:
 1 1 8rem; }
button { justify-self: start; padding: .8rem 1.6rem; border: 0;
border-radius: 999px; background: var(--brand); color: #fff; font:
inherit; }
```

Project 862 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - Booking</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Book a piece	The main heading; only one per page.
<form action="/book" method="post" class="wizard">	A form; action is where the data goes, method how it is sent.
<fieldset>	Groups related form controls.
<legend>1. Choose a piece</legend>	Caption for the fieldset.
<label><input type="radio" name="item" value="Oak dining table" req...	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<label><input type="radio" name="item" value="Bookshelf" required> ...	Radio button: one choice from a group sharing the same name.
<label><input type="radio" name="item" value="Bedside table" requir...	A form control; its type decides what it looks like.
<label><input type="radio" name="item" value="Coffee table" require...	The field must be filled before the form can be submitted.
<label>Date <input type="date" name="date" required min="2026-09-11...	Date picker.
<label>Time <input type="time" name="time" required step="1800"></l...	Time picker.
<label>People <input type="number" name="people" min="1" max="10" v...	Numeric input with min, max and step.
<label>Name <input type="text" name="name" required autocomplete="n...	Tells the browser which saved value to offer (name, email, tel...).
<label>Phone <input type="tel" name="phone" required autocomplete="...	Telephone number; shows the phone keypad on mobiles.
<label><input type="checkbox" name="terms" required> I agree to the...	Checkbox: on or off.
<button type="submit">Confirm booking</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.
font-weight: 700;	Thickness of the text.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
input:not([type="radio"]):not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
flex: 1 1 8rem;	The item can grow and shrink from the given basis.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.
background: var(--brand);	Background colour or image.

Check your work

- Radios share one name
- Date min prevents past dates
- Every control labelled
- Checkbox required works

Exercises

1. Show one fieldset at a time with :has() and radio state or JavaScript.
2. Add a summary panel that updates live.
3. Add a progress tracker on top.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 863: Booking form in three steps for Byte Repair

Theme: Byte Repair (Nasr City) | Level 2 | Files: index.html, styles.css

Brief

Build a longer form divided into three fieldsets: radio choice with prices, date/time/number inputs, and personal details with a required checkbox.

Learning goals

- Group related controls with fieldset and legend
- Use date, time, number and tel input types with min/max/step
- Use wrapping labels

Elements and CSS used

HTML elements	CSS features
form, fieldset, legend, label, input (radio, date, time, number, text, tel, checkbox), small, button	fieldset border/radius, legend, display: flex on label, margin-left: auto, :not() chains

Build guide

1. Write three fieldsets with legends numbered 1 to 3.
2. Step 1: radio buttons with the same name, each wrapped in a label with the price in <small>.
3. Step 2: date, time and number inputs with limits.
4. Step 3: text, tel and a required checkbox.
5. Grid the form and fieldsets.
6. Push prices right with margin-left: auto.

Project 863: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - Booking</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Book a repair</h1>
    <form action="/book" method="post" class="wizard">
      <fieldset>
        <legend>1. Choose a repair</legend>
    <label><input type="radio" name="item" value="Screen replacement"
required> Screen replacement <small>From 800 EGP</small></label>
    <label><input type="radio" name="item" value="Battery swap"
required> Battery swap <small>From 500 EGP</small></label>
    <label><input type="radio" name="item" value="Laptop cleaning"
required> Laptop cleaning <small>350 EGP</small></label>
    <label><input type="radio" name="item" value="Data recovery"
required> Data recovery <small>From 1200 EGP</small></label>
      </fieldset>
      <fieldset>
        <legend>2. When</legend>
        <label>Date <input type="date" name="date" required min="2026-
09-11"></label>
        <label>Time <input type="time" name="time" required
step="1800"></label>
        <label>People <input type="number" name="people" min="1"
max="10" value="1"></label>
      </fieldset>
      <fieldset>
        <legend>3. Your details</legend>
        <label>Name <input type="text" name="name" required
autocomplete="name"></label>
        <label>Phone <input type="tel" name="phone" required
autocomplete="tel" inputmode="tel"></label>
        <label><input type="checkbox" name="terms" required> I agree
to the cancellation policy</label>
      </fieldset>
      <button type="submit">Confirm booking</button>
    </form>
  </main>
</body>
</html>
```

Project 863: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.wizard { display: grid; gap: 1.5rem; }
fieldset { border: 1px solid var(--line); border-radius: 12px;
padding: 1rem 1.25rem; display: grid; gap: .6rem; }
legend { font-weight: 700; color: var(--brand); padding: 0 .4rem; }
label { display: flex; align-items: center; gap: .5rem; flex-wrap:
wrap; }
label small { margin-left: auto; color: var(--muted); }
input:not([type="radio"]):not([type="checkbox"]) { padding: .5rem .
7rem; border: 1px solid #bbb; border-radius: 8px; font: inherit; flex:
 1 1 8rem; }
button { justify-self: start; padding: .8rem 1.6rem; border: 0;
border-radius: 999px; background: var(--brand); color: #fff; font:
inherit; }
```

Project 863 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - Booking</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Book a repair	The main heading; only one per page.
<form action="/book" method="post" class="wizard">	A form; action is where the data goes, method how it is sent.
<fieldset>	Groups related form controls.
<legend>1. Choose a repair</legend>	Caption for the fieldset.
<label><input type="radio" name="item" value="Screen replacement" r...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="item" value="Battery swap" require...	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="item" value="Laptop cleaning" requ...	A form control; its type decides what it looks like.
<label><input type="radio" name="item" value="Data recovery" requir...	The field must be filled before the form can be submitted.
<label>Date <input type="date" name="date" required min="2026-09-11...	Date picker.
<label>Time <input type="time" name="time" required step="1800"></l...	Time picker.
<label>People <input type="number" name="people" min="1" max="10" v...	Numeric input with min, max and step.
<label>Name <input type="text" name="name" required autocomplete="n...	Tells the browser which saved value to offer (name, email, tel...).
<label>Phone <input type="tel" name="phone" required autocomplete="...	Telephone number; shows the phone keypad on mobiles.
<label><input type="checkbox" name="terms" required> I agree to the...	Checkbox: on or off.
<button type="submit">Confirm booking</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.
font-weight: 700;	Thickness of the text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
input:not([type="radio"]):not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
flex: 1 1 8rem;	The item can grow and shrink from the given basis.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.
background: var(--brand);	Background colour or image.

Check your work

- Radios share one name
- Date min prevents past dates
- Every control labelled
- Checkbox required works

Exercises

1. Show one fieldset at a time with :has() and radio state or JavaScript.
2. Add a summary panel that updates live.
3. Add a progress tracker on top.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 864: Booking form in three steps for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 2 | Files: index.html, styles.css

Brief

Build a longer form divided into three fieldsets: radio choice with prices, date/time/number inputs, and personal details with a required checkbox.

Learning goals

- Group related controls with fieldset and legend
- Use date, time, number and tel input types with min/max/step
- Use wrapping labels

Elements and CSS used

HTML elements	CSS features
form, fieldset, legend, label, input (radio, date, time, number, text, tel, checkbox), small, button	fieldset border/radius, legend, display: flex on label, margin-left: auto, :not() chains

Build guide

1. Write three fieldsets with legends numbered 1 to 3.
2. Step 1: radio buttons with the same name, each wrapped in a label with the price in <small>.
3. Step 2: date, time and number inputs with limits.
4. Step 3: text, tel and a required checkbox.
5. Grid the form and fieldsets.
6. Push prices right with margin-left: auto.

Project 864: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - Booking</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Book a service</h1>
    <form action="/book" method="post" class="wizard">
      <fieldset>
        <legend>1. Choose a service</legend>
    <label><input type="radio" name="item" value="Full grooming"
required> Full grooming <small>400 EGP</small></label>
    <label><input type="radio" name="item" value="Day boarding"
required> Day boarding <small>250 EGP</small></label>
    <label><input type="radio" name="item" value="Vaccination"
required> Vaccination <small>300 EGP</small></label>
    <label><input type="radio" name="item" value="Dog walking"
required> Dog walking <small>100 EGP</small></label>
      </fieldset>
      <fieldset>
        <legend>2. When</legend>
        <label>Date <input type="date" name="date" required min="2026-
09-11"></label>
        <label>Time <input type="time" name="time" required
step="1800"></label>
        <label>People <input type="number" name="people" min="1"
max="10" value="1"></label>
      </fieldset>
      <fieldset>
        <legend>3. Your details</legend>
        <label>Name <input type="text" name="name" required
autocomplete="name"></label>
        <label>Phone <input type="tel" name="phone" required
autocomplete="tel" inputmode="tel"></label>
        <label><input type="checkbox" name="terms" required> I agree
to the cancellation policy</label>
      </fieldset>
      <button type="submit">Confirm booking</button>
    </form>
  </main>
</body>
</html>
```

Project 864: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.wizard { display: grid; gap: 1.5rem; }
fieldset { border: 1px solid var(--line); border-radius: 12px;
padding: 1rem 1.25rem; display: grid; gap: .6rem; }
legend { font-weight: 700; color: var(--brand); padding: 0 .4rem; }
label { display: flex; align-items: center; gap: .5rem; flex-wrap:
wrap; }
label small { margin-left: auto; color: var(--muted); }
input:not([type="radio"]):not([type="checkbox"]) { padding: .5rem .
7rem; border: 1px solid #bbb; border-radius: 8px; font: inherit; flex:
 1 1 8rem; }
button { justify-self: start; padding: .8rem 1.6rem; border: 0;
border-radius: 999px; background: var(--brand); color: #fff; font:
inherit; }
```

Project 864 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - Booking</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Book a service	The main heading; only one per page.
<form action="/book" method="post" class="wizard">	A form; action is where the data goes, method how it is sent.
<fieldset>	Groups related form controls.
<legend>1. Choose a service</legend>	Caption for the fieldset.
<label><input type="radio" name="item" value="Full grooming" requir...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="item" value="Day boarding" require...	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="item" value="Vaccination" required...	A form control; its type decides what it looks like.
<label><input type="radio" name="item" value="Dog walking" required...	The field must be filled before the form can be submitted.
<label>Date <input type="date" name="date" required min="2026-09-11...	Date picker.
<label>Time <input type="time" name="time" required step="1800"></l...	Time picker.
<label>People <input type="number" name="people" min="1" max="10" v...	Numeric input with min, max and step.
<label>Name <input type="text" name="name" required autocomplete="n...	Tells the browser which saved value to offer (name, email, tel...).
<label>Phone <input type="tel" name="phone" required autocomplete="...	Telephone number; shows the phone keypad on mobiles.
<label><input type="checkbox" name="terms" required> I agree to the...	Checkbox: on or off.
<button type="submit">Confirm booking</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.
font-weight: 700;	Thickness of the text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
input:not([type="radio"]):not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
flex: 1 1 8rem;	The item can grow and shrink from the given basis.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.
background: var(--brand);	Background colour or image.

Check your work

- Radios share one name
- Date min prevents past dates
- Every control labelled
- Checkbox required works

Exercises

1. Show one fieldset at a time with :has() and radio state or JavaScript.
2. Add a summary panel that updates live.
3. Add a progress tracker on top.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 865: Booking form in three steps for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Build a longer form divided into three fieldsets: radio choice with prices, date/time/number inputs, and personal details with a required checkbox.

Learning goals

- Group related controls with fieldset and legend
- Use date, time, number and tel input types with min/max/step
- Use wrapping labels

Elements and CSS used

HTML elements	CSS features
form, fieldset, legend, label, input (radio, date, time, number, text, tel, checkbox), small, button	fieldset border/radius, legend, display: flex on label, margin-left: auto, :not() chains

Build guide

1. Write three fieldsets with legends numbered 1 to 3.
2. Step 1: radio buttons with the same name, each wrapped in a label with the price in <small>.
3. Step 2: date, time and number inputs with limits.
4. Step 3: text, tel and a required checkbox.
5. Grid the form and fieldsets.

6. Push prices right with margin-left: auto.

Project 865: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - Booking</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Book a lesson</h1>
    <form action="/book" method="post" class="wizard">
      <fieldset>
        <legend>1. Choose a lesson</legend>
    <label><input type="radio" name="item" value="Taster session"
required> Taster session <small>500 EGP</small></label>
    <label><input type="radio" name="item" value="Beginner course"
required> Beginner course <small>2200 EGP</small></label>
    <label><input type="radio" name="item" value="Racing clinic"
required> Racing clinic <small>1800 EGP</small></label>
    <label><input type="radio" name="item" value="Private lesson"
required> Private lesson <small>900 EGP</small></label>
      </fieldset>
      <fieldset>
        <legend>2. When</legend>
        <label>Date <input type="date" name="date" required min="2026-
09-11"></label>
        <label>Time <input type="time" name="time" required
step="1800"></label>
        <label>People <input type="number" name="people" min="1"
max="10" value="1"></label>
      </fieldset>
      <fieldset>
        <legend>3. Your details</legend>
        <label>Name <input type="text" name="name" required
autocomplete="name"></label>
        <label>Phone <input type="tel" name="phone" required
autocomplete="tel" inputmode="tel"></label>
        <label><input type="checkbox" name="terms" required> I agree
to the cancellation policy</label>
      </fieldset>
      <button type="submit">Confirm booking</button>
    </form>
  </main>
</body>
</html>
```

Project 865: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.wizard { display: grid; gap: 1.5rem; }
fieldset { border: 1px solid var(--line); border-radius: 12px;
padding: 1rem 1.25rem; display: grid; gap: .6rem; }
legend { font-weight: 700; color: var(--brand); padding: 0 .4rem; }
label { display: flex; align-items: center; gap: .5rem; flex-wrap:
wrap; }
label small { margin-left: auto; color: var(--muted); }
input:not([type="radio"]):not([type="checkbox"]) { padding: .5rem .
7rem; border: 1px solid #bbb; border-radius: 8px; font: inherit; flex:
 1 1 8rem; }
button { justify-self: start; padding: .8rem 1.6rem; border: 0;
border-radius: 999px; background: var(--brand); color: #fff; font:
inherit; }
```

Project 865 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - Booking</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Book a lesson	The main heading; only one per page.
<form action="/book" method="post" class="wizard">	A form; action is where the data goes, method how it is sent.
<fieldset>	Groups related form controls.
<legend>1. Choose a lesson</legend>	Caption for the fieldset.
<label><input type="radio" name="item" value="Taster session" requi...	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<label><input type="radio" name="item" value="Beginner course" requ...	Radio button: one choice from a group sharing the same name.
<label><input type="radio" name="item" value="Racing clinic" requir...	A form control; its type decides what it looks like.
<label><input type="radio" name="item" value="Private lesson" requi...	The field must be filled before the form can be submitted.
<label>Date <input type="date" name="date" required min="2026-09-11...	Date picker.
<label>Time <input type="time" name="time" required step="1800"></l...	Time picker.
<label>People <input type="number" name="people" min="1" max="10" v...	Numeric input with min, max and step.
<label>Name <input type="text" name="name" required autocomplete="n...	Tells the browser which saved value to offer (name, email, tel...).
<label>Phone <input type="tel" name="phone" required autocomplete="...	Telephone number; shows the phone keypad on mobiles.
<label><input type="checkbox" name="terms" required> I agree to the...	Checkbox: on or off.
<button type="submit">Confirm booking</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.
font-weight: 700;	Thickness of the text.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
input:not([type="radio"]):not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
flex: 1 1 8rem;	The item can grow and shrink from the given basis.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.
background: var(--brand);	Background colour or image.

Check your work

- Radios share one name
- Date min prevents past dates
- Every control labelled
- Checkbox required works

Exercises

1. Show one fieldset at a time with :has() and radio state or JavaScript.
2. Add a summary panel that updates live.
3. Add a progress tracker on top.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 866: Booking form in three steps for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Build a longer form divided into three fieldsets: radio choice with prices, date/time/number inputs, and personal details with a required checkbox.

Learning goals

- Group related controls with fieldset and legend
- Use date, time, number and tel input types with min/max/step
- Use wrapping labels

Elements and CSS used

HTML elements	CSS features
form, fieldset, legend, label, input (radio, date, time, number, text, tel, checkbox), small, button	fieldset border/radius, legend, display: flex on label, margin-left: auto, :not() chains

Build guide

1. Write three fieldsets with legends numbered 1 to 3.
2. Step 1: radio buttons with the same name, each wrapped in a label with the price in <small>.
3. Step 2: date, time and number inputs with limits.
4. Step 3: text, tel and a required checkbox.
5. Grid the form and fieldsets.

6. Push prices right with margin-left: auto.

Project 866: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - Booking</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Book a item</h1>
    <form action="/book" method="post" class="wizard">
      <fieldset>
        <legend>1. Choose a item</legend>
    <label><input type="radio" name="item" value="Lotus pendant"
required> Lotus pendant <small>650 EGP</small></label>
    <label><input type="radio" name="item" value="Brass cuff"
required> Brass cuff <small>420 EGP</small></label>
    <label><input type="radio" name="item" value="Bead earrings"
required> Bead earrings <small>180 EGP</small></label>
    <label><input type="radio" name="item" value="Ankh ring"
required> Ankh ring <small>300 EGP</small></label>
      </fieldset>
      <fieldset>
        <legend>2. When</legend>
        <label>Date <input type="date" name="date" required min="2026-
09-11"></label>
        <label>Time <input type="time" name="time" required
step="1800"></label>
        <label>People <input type="number" name="people" min="1"
max="10" value="1"></label>
      </fieldset>
      <fieldset>
        <legend>3. Your details</legend>
        <label>Name <input type="text" name="name" required
autocomplete="name"></label>
        <label>Phone <input type="tel" name="phone" required
autocomplete="tel" inputmode="tel"></label>
        <label><input type="checkbox" name="terms" required> I agree
to the cancellation policy</label>
      </fieldset>
      <button type="submit">Confirm booking</button>
    </form>
  </main>
</body>
</html>
```

Project 866: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.wizard { display: grid; gap: 1.5rem; }
fieldset { border: 1px solid var(--line); border-radius: 12px;
padding: 1rem 1.25rem; display: grid; gap: .6rem; }
legend { font-weight: 700; color: var(--brand); padding: 0 .4rem; }
label { display: flex; align-items: center; gap: .5rem; flex-wrap:
wrap; }
label small { margin-left: auto; color: var(--muted); }
input:not([type="radio"]):not([type="checkbox"]) { padding: .5rem .
7rem; border: 1px solid #bbb; border-radius: 8px; font: inherit; flex:
 1 1 8rem; }
button { justify-self: start; padding: .8rem 1.6rem; border: 0;
border-radius: 999px; background: var(--brand); color: #fff; font:
inherit; }
```

Project 866 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - Booking</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Book a item	The main heading; only one per page.
<form action="/book" method="post" class="wizard">	A form; action is where the data goes, method how it is sent.
<fieldset>	Groups related form controls.
<legend>1. Choose a item</legend>	Caption for the fieldset.
<label><input type="radio" name="item" value="Lotus pendant" requir...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="item" value="Brass cuff" required>...	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="item" value="Bead earrings" requir...	A form control; its type decides what it looks like.
<label><input type="radio" name="item" value="Ankh ring" required> ...	The field must be filled before the form can be submitted.
<label>Date <input type="date" name="date" required min="2026-09-11...	Date picker.
<label>Time <input type="time" name="time" required step="1800"></l...	Time picker.
<label>People <input type="number" name="people" min="1" max="10" v...	Numeric input with min, max and step.
<label>Name <input type="text" name="name" required autocomplete="n...	Tells the browser which saved value to offer (name, email, tel...).
<label>Phone <input type="tel" name="phone" required autocomplete="...	Telephone number; shows the phone keypad on mobiles.
<label><input type="checkbox" name="terms" required> I agree to the...	Checkbox: on or off.
<button type="submit">Confirm booking</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.
font-weight: 700;	Thickness of the text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
input:not([type="radio"]):not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
flex: 1 1 8rem;	The item can grow and shrink from the given basis.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.
background: var(--brand);	Background colour or image.

Check your work

- Radios share one name
- Date min prevents past dates
- Every control labelled
- Checkbox required works

Exercises

1. Show one fieldset at a time with :has() and radio state or JavaScript.
2. Add a summary panel that updates live.
3. Add a progress tracker on top.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 867: Booking form in three steps for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 2 | Files: index.html, styles.css

Brief

Build a longer form divided into three fieldsets: radio choice with prices, date/time/number inputs, and personal details with a required checkbox.

Learning goals

- Group related controls with fieldset and legend
- Use date, time, number and tel input types with min/max/step
- Use wrapping labels

Elements and CSS used

HTML elements	CSS features
form, fieldset, legend, label, input (radio, date, time, number, text, tel, checkbox), small, button	fieldset border/radius, legend, display: flex on label, margin-left: auto, :not() chains

Build guide

1. Write three fieldsets with legends numbered 1 to 3.
2. Step 1: radio buttons with the same name, each wrapped in a label with the price in <small>.
3. Step 2: date, time and number inputs with limits.
4. Step 3: text, tel and a required checkbox.
5. Grid the form and fieldsets.

6. Push prices right with margin-left: auto.

Project 867: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - Booking</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Book a workshop</h1>
    <form action="/book" method="post" class="wizard">
      <fieldset>
        <legend>1. Choose a workshop</legend>
    <label><input type="radio" name="item" value="Intro to the wheel"
required> Intro to the wheel <small>450 EGP</small></label>
    <label><input type="radio" name="item" value="Glazing day"
required> Glazing day <small>300 EGP</small></label>
    <label><input type="radio" name="item" value="Kids clay class"
required> Kids clay class <small>200 EGP</small></label>
    <label><input type="radio" name="item" value="Weekend retreat"
required> Weekend retreat <small>2500 EGP</small></label>
      </fieldset>
      <fieldset>
        <legend>2. When</legend>
        <label>Date <input type="date" name="date" required min="2026-
09-11"></label>
        <label>Time <input type="time" name="time" required
step="1800"></label>
        <label>People <input type="number" name="people" min="1"
max="10" value="1"></label>
      </fieldset>
      <fieldset>
        <legend>3. Your details</legend>
        <label>Name <input type="text" name="name" required
autocomplete="name"></label>
        <label>Phone <input type="tel" name="phone" required
autocomplete="tel" inputmode="tel"></label>
        <label><input type="checkbox" name="terms" required> I agree
to the cancellation policy</label>
      </fieldset>
      <button type="submit">Confirm booking</button>
    </form>
  </main>
</body>
</html>
```

Project 867: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.wizard { display: grid; gap: 1.5rem; }
fieldset { border: 1px solid var(--line); border-radius: 12px;
padding: 1rem 1.25rem; display: grid; gap: .6rem; }
legend { font-weight: 700; color: var(--brand); padding: 0 .4rem; }
label { display: flex; align-items: center; gap: .5rem; flex-wrap:
wrap; }
label small { margin-left: auto; color: var(--muted); }
input:not([type="radio"]):not([type="checkbox"]) { padding: .5rem .
7rem; border: 1px solid #bbb; border-radius: 8px; font: inherit; flex:
 1 1 8rem; }
button { justify-self: start; padding: .8rem 1.6rem; border: 0;
border-radius: 999px; background: var(--brand); color: #fff; font:
inherit; }
```

Project 867 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - Booking</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Book a workshop	The main heading; only one per page.
<form action="/book" method="post" class="wizard">	A form; action is where the data goes, method how it is sent.
<fieldset>	Groups related form controls.
<legend>1. Choose a workshop</legend>	Caption for the fieldset.
<label><input type="radio" name="item" value="Intro to the wheel" r...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="item" value="Glazing day" required...	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="item" value="Kids clay class" requ...	A form control; its type decides what it looks like.
<label><input type="radio" name="item" value="Weekend retreat" requ...	The field must be filled before the form can be submitted.
<label>Date <input type="date" name="date" required min="2026-09-11...	Date picker.
<label>Time <input type="time" name="time" required step="1800"></l...	Time picker.
<label>People <input type="number" name="people" min="1" max="10" v...	Numeric input with min, max and step.
<label>Name <input type="text" name="name" required autocomplete="n...	Tells the browser which saved value to offer (name, email, tel...).
<label>Phone <input type="tel" name="phone" required autocomplete="...	Telephone number; shows the phone keypad on mobiles.
<label><input type="checkbox" name="terms" required> I agree to the...	Checkbox: on or off.
<button type="submit">Confirm booking</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.
font-weight: 700;	Thickness of the text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
input:not([type="radio"]):not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
flex: 1 1 8rem;	The item can grow and shrink from the given basis.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.
background: var(--brand);	Background colour or image.

Check your work

- Radios share one name
- Date min prevents past dates
- Every control labelled
- Checkbox required works

Exercises

1. Show one fieldset at a time with :has() and radio state or JavaScript.
2. Add a summary panel that updates live.
3. Add a progress tracker on top.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 868: Booking form in three steps for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 2 | Files: index.html, styles.css

Brief

Build a longer form divided into three fieldsets: radio choice with prices, date/time/number inputs, and personal details with a required checkbox.

Learning goals

- Group related controls with fieldset and legend
- Use date, time, number and tel input types with min/max/step
- Use wrapping labels

Elements and CSS used

HTML elements	CSS features
form, fieldset, legend, label, input (radio, date, time, number, text, tel, checkbox), small, button	fieldset border/radius, legend, display: flex on label, margin-left: auto, :not() chains

Build guide

1. Write three fieldsets with legends numbered 1 to 3.
2. Step 1: radio buttons with the same name, each wrapped in a label with the price in <small>.
3. Step 2: date, time and number inputs with limits.
4. Step 3: text, tel and a required checkbox.
5. Grid the form and fieldsets.

6. Push prices right with margin-left: auto.

Project 868: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - Booking</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Book a treatment</h1>
    <form action="/book" method="post" class="wizard">
      <fieldset>
        <legend>1. Choose a treatment</legend>
    <label><input type="radio" name="item" value="Haircut and blow-
dry" required> Haircut and blow-dry <small>350 EGP</small></label>
    <label><input type="radio" name="item" value="Manicure" required>
Manicure <small>200 EGP</small></label>
    <label><input type="radio" name="item" value="Facial" required>
Facial <small>600 EGP</small></label>
    <label><input type="radio" name="item" value="Bridal package"
required> Bridal package <small>4500 EGP</small></label>
      </fieldset>
      <fieldset>
        <legend>2. When</legend>
        <label>Date <input type="date" name="date" required min="2026-
09-11"></label>
        <label>Time <input type="time" name="time" required
step="1800"></label>
        <label>People <input type="number" name="people" min="1"
max="10" value="1"></label>
      </fieldset>
      <fieldset>
        <legend>3. Your details</legend>
        <label>Name <input type="text" name="name" required
autocomplete="name"></label>
        <label>Phone <input type="tel" name="phone" required
autocomplete="tel" inputmode="tel"></label>
        <label><input type="checkbox" name="terms" required> I agree
to the cancellation policy</label>
      </fieldset>
      <button type="submit">Confirm booking</button>
    </form>
  </main>
</body>
</html>
```

Project 868: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.wizard { display: grid; gap: 1.5rem; }
fieldset { border: 1px solid var(--line); border-radius: 12px;
padding: 1rem 1.25rem; display: grid; gap: .6rem; }
legend { font-weight: 700; color: var(--brand); padding: 0 .4rem; }
label { display: flex; align-items: center; gap: .5rem; flex-wrap:
wrap; }
label small { margin-left: auto; color: var(--muted); }
input:not([type="radio"]):not([type="checkbox"]) { padding: .5rem .
7rem; border: 1px solid #bbb; border-radius: 8px; font: inherit; flex:
 1 1 8rem; }
button { justify-self: start; padding: .8rem 1.6rem; border: 0;
border-radius: 999px; background: var(--brand); color: #fff; font:
inherit; }
```

Project 868 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - Booking</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Book a treatment	The main heading; only one per page.
<form action="/book" method="post" class="wizard">	A form; action is where the data goes, method how it is sent.
<fieldset>	Groups related form controls.
<legend>1. Choose a treatment</legend>	Caption for the fieldset.
<label><input type="radio" name="item" value="Haircut and blow-dry"...	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<label><input type="radio" name="item" value="Manicure" required> M...	Radio button: one choice from a group sharing the same name.
<label><input type="radio" name="item" value="Facial" required> Fac...	A form control; its type decides what it looks like.
<label><input type="radio" name="item" value="Bridal package" requi...	The field must be filled before the form can be submitted.
<label>Date <input type="date" name="date" required min="2026-09-11...	Date picker.
<label>Time <input type="time" name="time" required step="1800"></l...	Time picker.
<label>People <input type="number" name="people" min="1" max="10" v...	Numeric input with min, max and step.
<label>Name <input type="text" name="name" required autocomplete="n...	Tells the browser which saved value to offer (name, email, tel...).
<label>Phone <input type="tel" name="phone" required autocomplete="...	Telephone number; shows the phone keypad on mobiles.
<label><input type="checkbox" name="terms" required> I agree to the...	Checkbox: on or off.
<button type="submit">Confirm booking</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.
font-weight: 700;	Thickness of the text.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
input:not([type="radio"]):not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
flex: 1 1 8rem;	The item can grow and shrink from the given basis.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.
background: var(--brand);	Background colour or image.

Check your work

- Radios share one name
- Date min prevents past dates
- Every control labelled
- Checkbox required works

Exercises

1. Show one fieldset at a time with :has() and radio state or JavaScript.
2. Add a summary panel that updates live.
3. Add a progress tracker on top.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 869: Booking form in three steps for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 2 | Files: index.html, styles.css

Brief

Build a longer form divided into three fieldsets: radio choice with prices, date/time/number inputs, and personal details with a required checkbox.

Learning goals

- Group related controls with fieldset and legend
- Use date, time, number and tel input types with min/max/step
- Use wrapping labels

Elements and CSS used

HTML elements	CSS features
form, fieldset, legend, label, input (radio, date, time, number, text, tel, checkbox), small, button	fieldset border/radius, legend, display: flex on label, margin-left: auto, :not() chains

Build guide

1. Write three fieldsets with legends numbered 1 to 3.
2. Step 1: radio buttons with the same name, each wrapped in a label with the price in <small>.
3. Step 2: date, time and number inputs with limits.
4. Step 3: text, tel and a required checkbox.
5. Grid the form and fieldsets.

6. Push prices right with margin-left: auto.

Project 869: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - Booking</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Book a service</h1>
    <form action="/book" method="post" class="wizard">
      <fieldset>
        <legend>1. Choose a service</legend>
    <label><input type="radio" name="item" value="Oil change"
required> Oil change <small>600 EGP</small></label>
    <label><input type="radio" name="item" value="Brake pads"
required> Brake pads <small>1400 EGP</small></label>
    <label><input type="radio" name="item" value="Air conditioning"
required> Air conditioning <small>900 EGP</small></label>
    <label><input type="radio" name="item" value="Pre-purchase
inspection" required> Pre-purchase inspection <small>750 EGP</small></
label>
      </fieldset>
      <fieldset>
        <legend>2. When</legend>
        <label>Date <input type="date" name="date" required min="2026-
09-11"></label>
        <label>Time <input type="time" name="time" required
step="1800"></label>
        <label>People <input type="number" name="people" min="1"
max="10" value="1"></label>
      </fieldset>
      <fieldset>
        <legend>3. Your details</legend>
        <label>Name <input type="text" name="name" required
autocomplete="name"></label>
        <label>Phone <input type="tel" name="phone" required
autocomplete="tel" inputmode="tel"></label>
        <label><input type="checkbox" name="terms" required> I agree
to the cancellation policy</label>
      </fieldset>
      <button type="submit">Confirm booking</button>
    </form>
  </main>
</body>
</html>
```

Project 869: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.wizard { display: grid; gap: 1.5rem; }
fieldset { border: 1px solid var(--line); border-radius: 12px;
padding: 1rem 1.25rem; display: grid; gap: .6rem; }
legend { font-weight: 700; color: var(--brand); padding: 0 .4rem; }
label { display: flex; align-items: center; gap: .5rem; flex-wrap:
wrap; }
label small { margin-left: auto; color: var(--muted); }
input:not([type="radio"]):not([type="checkbox"]) { padding: .5rem .
7rem; border: 1px solid #bbb; border-radius: 8px; font: inherit; flex:
 1 1 8rem; }
button { justify-self: start; padding: .8rem 1.6rem; border: 0;
border-radius: 999px; background: var(--brand); color: #fff; font:
inherit; }
```

Project 869 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - Booking</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Book a service	The main heading; only one per page.
<form action="/book" method="post" class="wizard">	A form; action is where the data goes, method how it is sent.
<fieldset>	Groups related form controls.
<legend>1. Choose a service</legend>	Caption for the fieldset.
<label><input type="radio" name="item" value="Oil change" required>...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="item" value="Brake pads" required>...	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="item" value="Air conditioning" req...	A form control; its type decides what it looks like.
<label><input type="radio" name="item" value="Pre-purchase inspecti...	The field must be filled before the form can be submitted.
<label>Date <input type="date" name="date" required min="2026-09-11...	Date picker.
<label>Time <input type="time" name="time" required step="1800"></l...	Time picker.
<label>People <input type="number" name="people" min="1" max="10" v...	Numeric input with min, max and step.
<label>Name <input type="text" name="name" required autocomplete="n...	Tells the browser which saved value to offer (name, email, tel...).
<label>Phone <input type="tel" name="phone" required autocomplete="...	Telephone number; shows the phone keypad on mobiles.
<label><input type="checkbox" name="terms" required> I agree to the...	Checkbox: on or off.
<button type="submit">Confirm booking</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.
font-weight: 700;	Thickness of the text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
input:not([type="radio"]):not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
flex: 1 1 8rem;	The item can grow and shrink from the given basis.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.
background: var(--brand);	Background colour or image.

Check your work

- Radios share one name
- Date min prevents past dates
- Every control labelled
- Checkbox required works

Exercises

1. Show one fieldset at a time with :has() and radio state or JavaScript.
2. Add a summary panel that updates live.
3. Add a progress tracker on top.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 870: Booking form in three steps for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 2 | Files: index.html, styles.css

Brief

Build a longer form divided into three fieldsets: radio choice with prices, date/time/number inputs, and personal details with a required checkbox.

Learning goals

- Group related controls with fieldset and legend
- Use date, time, number and tel input types with min/max/step
- Use wrapping labels

Elements and CSS used

HTML elements	CSS features
form, fieldset, legend, label, input (radio, date, time, number, text, tel, checkbox), small, button	fieldset border/radius, legend, display: flex on label, margin-left: auto, :not() chains

Build guide

1. Write three fieldsets with legends numbered 1 to 3.
2. Step 1: radio buttons with the same name, each wrapped in a label with the price in <small>.
3. Step 2: date, time and number inputs with limits.
4. Step 3: text, tel and a required checkbox.
5. Grid the form and fieldsets.

6. Push prices right with margin-left: auto.

Project 870: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - Booking</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Book a course</h1>
    <form action="/book" method="post" class="wizard">
      <fieldset>
        <legend>1. Choose a course</legend>
    <label><input type="radio" name="item" value="Oud for beginners"
required> Oud for beginners <small>1600 EGP</small></label>
    <label><input type="radio" name="item" value="Piano grade 1"
required> Piano grade 1 <small>1800 EGP</small></label>
    <label><input type="radio" name="item" value="Guitar chords"
required> Guitar chords <small>1400 EGP</small></label>
    <label><input type="radio" name="item" value="Voice coaching"
required> Voice coaching <small>1500 EGP</small></label>
      </fieldset>
      <fieldset>
        <legend>2. When</legend>
        <label>Date <input type="date" name="date" required min="2026-
09-11"></label>
        <label>Time <input type="time" name="time" required
step="1800"></label>
        <label>People <input type="number" name="people" min="1"
max="10" value="1"></label>
      </fieldset>
      <fieldset>
        <legend>3. Your details</legend>
        <label>Name <input type="text" name="name" required
autocomplete="name"></label>
        <label>Phone <input type="tel" name="phone" required
autocomplete="tel" inputmode="tel"></label>
        <label><input type="checkbox" name="terms" required> I agree
to the cancellation policy</label>
      </fieldset>
      <button type="submit">Confirm booking</button>
    </form>
  </main>
</body>
</html>
```

Project 870: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.wizard { display: grid; gap: 1.5rem; }
fieldset { border: 1px solid var(--line); border-radius: 12px;
padding: 1rem 1.25rem; display: grid; gap: .6rem; }
legend { font-weight: 700; color: var(--brand); padding: 0 .4rem; }
label { display: flex; align-items: center; gap: .5rem; flex-wrap:
wrap; }
label small { margin-left: auto; color: var(--muted); }
input:not([type="radio"]):not([type="checkbox"]) { padding: .5rem .
7rem; border: 1px solid #bbb; border-radius: 8px; font: inherit; flex:
 1 1 8rem; }
button { justify-self: start; padding: .8rem 1.6rem; border: 0;
border-radius: 999px; background: var(--brand); color: #fff; font:
inherit; }
```

Project 870 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - Booking</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Book a course	The main heading; only one per page.
<form action="/book" method="post" class="wizard">	A form; action is where the data goes, method how it is sent.
<fieldset>	Groups related form controls.
<legend>1. Choose a course</legend>	Caption for the fieldset.
<label><input type="radio" name="item" value="Oud for beginners" re...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="item" value="Piano grade 1" requir...	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="item" value="Guitar chords" requir...	A form control; its type decides what it looks like.
<label><input type="radio" name="item" value="Voice coaching" requi...	The field must be filled before the form can be submitted.
<label>Date <input type="date" name="date" required min="2026-09-11...	Date picker.
<label>Time <input type="time" name="time" required step="1800"></l...	Time picker.
<label>People <input type="number" name="people" min="1" max="10" v...	Numeric input with min, max and step.
<label>Name <input type="text" name="name" required autocomplete="n...	Tells the browser which saved value to offer (name, email, tel...).
<label>Phone <input type="tel" name="phone" required autocomplete="...	Telephone number; shows the phone keypad on mobiles.
<label><input type="checkbox" name="terms" required> I agree to the...	Checkbox: on or off.
<button type="submit">Confirm booking</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.
font-weight: 700;	Thickness of the text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
input:not([type="radio"]):not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
flex: 1 1 8rem;	The item can grow and shrink from the given basis.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.
background: var(--brand);	Background colour or image.

Check your work

- Radios share one name
- Date min prevents past dates
- Every control labelled
- Checkbox required works

Exercises

1. Show one fieldset at a time with :has() and radio state or JavaScript.
2. Add a summary panel that updates live.
3. Add a progress tracker on top.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 871: Booking form in three steps for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 2 | Files: index.html, styles.css

Brief

Build a longer form divided into three fieldsets: radio choice with prices, date/time/number inputs, and personal details with a required checkbox.

Learning goals

- Group related controls with fieldset and legend
- Use date, time, number and tel input types with min/max/step
- Use wrapping labels

Elements and CSS used

HTML elements	CSS features
form, fieldset, legend, label, input (radio, date, time, number, text, tel, checkbox), small, button	fieldset border/radius, legend, display: flex on label, margin-left: auto, :not() chains

Build guide

1. Write three fieldsets with legends numbered 1 to 3.
2. Step 1: radio buttons with the same name, each wrapped in a label with the price in <small>.
3. Step 2: date, time and number inputs with limits.
4. Step 3: text, tel and a required checkbox.
5. Grid the form and fieldsets.

6. Push prices right with margin-left: auto.

Project 871: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - Booking</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Book a dish</h1>
    <form action="/book" method="post" class="wizard">
      <fieldset>
        <legend>1. Choose a dish</legend>
    <label><input type="radio" name="item" value="Grilled sea bass"
required> Grilled sea bass <small>320 EGP</small></label>
    <label><input type="radio" name="item" value="Shrimp tagine"
required> Shrimp tagine <small>280 EGP</small></label>
    <label><input type="radio" name="item" value="Calamari" required>
Calamari <small>190 EGP</small></label>
    <label><input type="radio" name="item" value="Fish soup"
required> Fish soup <small>120 EGP</small></label>
      </fieldset>
      <fieldset>
        <legend>2. When</legend>
        <label>Date <input type="date" name="date" required min="2026-
09-11"></label>
        <label>Time <input type="time" name="time" required
step="1800"></label>
        <label>People <input type="number" name="people" min="1"
max="10" value="1"></label>
      </fieldset>
      <fieldset>
        <legend>3. Your details</legend>
        <label>Name <input type="text" name="name" required
autocomplete="name"></label>
        <label>Phone <input type="tel" name="phone" required
autocomplete="tel" inputmode="tel"></label>
        <label><input type="checkbox" name="terms" required> I agree
to the cancellation policy</label>
      </fieldset>
      <button type="submit">Confirm booking</button>
    </form>
  </main>
</body>
</html>
```

Project 871: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.wizard { display: grid; gap: 1.5rem; }
fieldset { border: 1px solid var(--line); border-radius: 12px;
padding: 1rem 1.25rem; display: grid; gap: .6rem; }
legend { font-weight: 700; color: var(--brand); padding: 0 .4rem; }
label { display: flex; align-items: center; gap: .5rem; flex-wrap:
wrap; }
label small { margin-left: auto; color: var(--muted); }
input:not([type="radio"]):not([type="checkbox"]) { padding: .5rem .
7rem; border: 1px solid #bbb; border-radius: 8px; font: inherit; flex:
 1 1 8rem; }
button { justify-self: start; padding: .8rem 1.6rem; border: 0;
border-radius: 999px; background: var(--brand); color: #fff; font:
inherit; }
```

Project 871 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - Booking</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Book a dish	The main heading; only one per page.
<form action="/book" method="post" class="wizard">	A form; action is where the data goes, method how it is sent.
<fieldset>	Groups related form controls.
<legend>1. Choose a dish</legend>	Caption for the fieldset.
<label><input type="radio" name="item" value="Grilled sea bass" req...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="item" value="Shrimp tagine" requir...	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="item" value="Calamari" required> C...	A form control; its type decides what it looks like.
<label><input type="radio" name="item" value="Fish soup" required> ...	The field must be filled before the form can be submitted.
<label>Date <input type="date" name="date" required min="2026-09-11...	Date picker.
<label>Time <input type="time" name="time" required step="1800"></l...	Time picker.
<label>People <input type="number" name="people" min="1" max="10" v...	Numeric input with min, max and step.
<label>Name <input type="text" name="name" required autocomplete="n...	Tells the browser which saved value to offer (name, email, tel...).
<label>Phone <input type="tel" name="phone" required autocomplete="...	Telephone number; shows the phone keypad on mobiles.
<label><input type="checkbox" name="terms" required> I agree to the...	Checkbox: on or off.
<button type="submit">Confirm booking</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.
font-weight: 700;	Thickness of the text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
input:not([type="radio"]):not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
flex: 1 1 8rem;	The item can grow and shrink from the given basis.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.
background: var(--brand);	Background colour or image.

Check your work

- Radios share one name
- Date min prevents past dates
- Every control labelled
- Checkbox required works

Exercises

1. Show one fieldset at a time with :has() and radio state or JavaScript.
2. Add a summary panel that updates live.
3. Add a progress tracker on top.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 872: Booking form in three steps for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 2 | Files: index.html, styles.css

Brief

Build a longer form divided into three fieldsets: radio choice with prices, date/time/number inputs, and personal details with a required checkbox.

Learning goals

- Group related controls with fieldset and legend
- Use date, time, number and tel input types with min/max/step
- Use wrapping labels

Elements and CSS used

HTML elements	CSS features
form, fieldset, legend, label, input (radio, date, time, number, text, tel, checkbox), small, button	fieldset border/radius, legend, display: flex on label, margin-left: auto, :not() chains

Build guide

1. Write three fieldsets with legends numbered 1 to 3.
2. Step 1: radio buttons with the same name, each wrapped in a label with the price in <small>.
3. Step 2: date, time and number inputs with limits.
4. Step 3: text, tel and a required checkbox.
5. Grid the form and fieldsets.

6. Push prices right with margin-left: auto.

Project 872: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - Booking</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Book a programme</h1>
    <form action="/book" method="post" class="wizard">
      <fieldset>
        <legend>1. Choose a programme</legend>
    <label><input type="radio" name="item" value="Story hour"
required> Story hour <small>Free</small></label>
    <label><input type="radio" name="item" value="Reading club"
required> Reading club <small>50 EGP per month</small></label>
    <label><input type="radio" name="item" value="Homework help"
required> Homework help <small>Free</small></label>
    <label><input type="radio" name="item" value="Summer challenge"
required> Summer challenge <small>Free</small></label>
      </fieldset>
      <fieldset>
        <legend>2. When</legend>
        <label>Date <input type="date" name="date" required min="2026-
09-11"></label>
        <label>Time <input type="time" name="time" required
step="1800"></label>
        <label>People <input type="number" name="people" min="1"
max="10" value="1"></label>
      </fieldset>
      <fieldset>
        <legend>3. Your details</legend>
        <label>Name <input type="text" name="name" required
autocomplete="name"></label>
        <label>Phone <input type="tel" name="phone" required
autocomplete="tel" inputmode="tel"></label>
        <label><input type="checkbox" name="terms" required> I agree
to the cancellation policy</label>
      </fieldset>
      <button type="submit">Confirm booking</button>
    </form>
  </main>
</body>
</html>
```

Project 872: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.wizard { display: grid; gap: 1.5rem; }
fieldset { border: 1px solid var(--line); border-radius: 12px;
padding: 1rem 1.25rem; display: grid; gap: .6rem; }
legend { font-weight: 700; color: var(--brand); padding: 0 .4rem; }
label { display: flex; align-items: center; gap: .5rem; flex-wrap:
wrap; }
label small { margin-left: auto; color: var(--muted); }
input:not([type="radio"]):not([type="checkbox"]) { padding: .5rem .
7rem; border: 1px solid #bbb; border-radius: 8px; font: inherit; flex:
 1 1 8rem; }
button { justify-self: start; padding: .8rem 1.6rem; border: 0;
border-radius: 999px; background: var(--brand); color: #fff; font:
inherit; }
```

Project 872 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - Booking</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Book a programme	The main heading; only one per page.
<form action="/book" method="post" class="wizard">	A form; action is where the data goes, method how it is sent.
<fieldset>	Groups related form controls.
<legend>1. Choose a programme</legend>	Caption for the fieldset.
<label><input type="radio" name="item" value="Story hour" required>...	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<label><input type="radio" name="item" value="Reading club" require...	Radio button: one choice from a group sharing the same name.
<label><input type="radio" name="item" value="Homework help" requir...	A form control; its type decides what it looks like.
<label><input type="radio" name="item" value="Summer challenge" req...	The field must be filled before the form can be submitted.
<label>Date <input type="date" name="date" required min="2026-09-11...	Date picker.
<label>Time <input type="time" name="time" required step="1800"></l...	Time picker.
<label>People <input type="number" name="people" min="1" max="10" v...	Numeric input with min, max and step.
<label>Name <input type="text" name="name" required autocomplete="n...	Tells the browser which saved value to offer (name, email, tel...).
<label>Phone <input type="tel" name="phone" required autocomplete="...	Telephone number; shows the phone keypad on mobiles.
<label><input type="checkbox" name="terms" required> I agree to the...	Checkbox: on or off.
<button type="submit">Confirm booking</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.
font-weight: 700;	Thickness of the text.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
input:not([type="radio"]):not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
flex: 1 1 8rem;	The item can grow and shrink from the given basis.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.
background: var(--brand);	Background colour or image.

Check your work

- Radios share one name
- Date min prevents past dates
- Every control labelled
- Checkbox required works

Exercises

1. Show one fieldset at a time with :has() and radio state or JavaScript.
2. Add a summary panel that updates live.
3. Add a progress tracker on top.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 873: Booking form in three steps for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Build a longer form divided into three fieldsets: radio choice with prices, date/time/number inputs, and personal details with a required checkbox.

Learning goals

- Group related controls with fieldset and legend
- Use date, time, number and tel input types with min/max/step
- Use wrapping labels

Elements and CSS used

HTML elements	CSS features
form, fieldset, legend, label, input (radio, date, time, number, text, tel, checkbox), small, button	fieldset border/radius, legend, display: flex on label, margin-left: auto, :not() chains

Build guide

1. Write three fieldsets with legends numbered 1 to 3.
2. Step 1: radio buttons with the same name, each wrapped in a label with the price in <small>.
3. Step 2: date, time and number inputs with limits.
4. Step 3: text, tel and a required checkbox.
5. Grid the form and fieldsets.

6. Push prices right with margin-left: auto.

Project 873: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - Booking</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Book a room</h1>
    <form action="/book" method="post" class="wizard">
      <fieldset>
        <legend>1. Choose a room</legend>
    <label><input type="radio" name="item" value="Garden room"
required> Garden room <small>900 EGP</small></label>
    <label><input type="radio" name="item" value="Nile view suite"
required> Nile view suite <small>1800 EGP</small></label>
    <label><input type="radio" name="item" value="Family room"
required> Family room <small>1500 EGP</small></label>
    <label><input type="radio" name="item" value="Rooftop dorm"
required> Rooftop dorm <small>300 EGP</small></label>
      </fieldset>
      <fieldset>
        <legend>2. When</legend>
        <label>Date <input type="date" name="date" required min="2026-
09-11"></label>
        <label>Time <input type="time" name="time" required
step="1800"></label>
        <label>People <input type="number" name="people" min="1"
max="10" value="1"></label>
      </fieldset>
      <fieldset>
        <legend>3. Your details</legend>
        <label>Name <input type="text" name="name" required
autocomplete="name"></label>
        <label>Phone <input type="tel" name="phone" required
autocomplete="tel" inputmode="tel"></label>
        <label><input type="checkbox" name="terms" required> I agree
to the cancellation policy</label>
      </fieldset>
      <button type="submit">Confirm booking</button>
    </form>
  </main>
</body>
</html>
```

Project 873: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.wizard { display: grid; gap: 1.5rem; }
fieldset { border: 1px solid var(--line); border-radius: 12px;
padding: 1rem 1.25rem; display: grid; gap: .6rem; }
legend { font-weight: 700; color: var(--brand); padding: 0 .4rem; }
label { display: flex; align-items: center; gap: .5rem; flex-wrap:
wrap; }
label small { margin-left: auto; color: var(--muted); }
input:not([type="radio"]):not([type="checkbox"]) { padding: .5rem .
7rem; border: 1px solid #bbb; border-radius: 8px; font: inherit; flex:
 1 1 8rem; }
button { justify-self: start; padding: .8rem 1.6rem; border: 0;
border-radius: 999px; background: var(--brand); color: #fff; font:
inherit; }
```

Project 873 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - Booking</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Book a room	The main heading; only one per page.
<form action="/book" method="post" class="wizard">	A form; action is where the data goes, method how it is sent.
<fieldset>	Groups related form controls.
<legend>1. Choose a room</legend>	Caption for the fieldset.
<label><input type="radio" name="item" value="Garden room" required...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="item" value="Nile view suite" requ...	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="item" value="Family room" required...	A form control; its type decides what it looks like.
<label><input type="radio" name="item" value="Rooftop dorm" require...	The field must be filled before the form can be submitted.
<label>Date <input type="date" name="date" required min="2026-09-11...	Date picker.
<label>Time <input type="time" name="time" required step="1800"></l...	Time picker.
<label>People <input type="number" name="people" min="1" max="10" v...	Numeric input with min, max and step.
<label>Name <input type="text" name="name" required autocomplete="n...	Tells the browser which saved value to offer (name, email, tel...).
<label>Phone <input type="tel" name="phone" required autocomplete="...	Telephone number; shows the phone keypad on mobiles.
<label><input type="checkbox" name="terms" required> I agree to the...	Checkbox: on or off.
<button type="submit">Confirm booking</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.
font-weight: 700;	Thickness of the text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
input:not([type="radio"]):not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
flex: 1 1 8rem;	The item can grow and shrink from the given basis.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.
background: var(--brand);	Background colour or image.

Check your work

- Radios share one name
- Date min prevents past dates
- Every control labelled
- Checkbox required works

Exercises

1. Show one fieldset at a time with :has() and radio state or JavaScript.
2. Add a summary panel that updates live.
3. Add a progress tracker on top.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 874: Booking form in three steps for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 2 | Files: index.html, styles.css

Brief

Build a longer form divided into three fieldsets: radio choice with prices, date/time/number inputs, and personal details with a required checkbox.

Learning goals

- Group related controls with fieldset and legend
- Use date, time, number and tel input types with min/max/step
- Use wrapping labels

Elements and CSS used

HTML elements	CSS features
form, fieldset, legend, label, input (radio, date, time, number, text, tel, checkbox), small, button	fieldset border/radius, legend, display: flex on label, margin-left: auto, :not() chains

Build guide

1. Write three fieldsets with legends numbered 1 to 3.
2. Step 1: radio buttons with the same name, each wrapped in a label with the price in <small>.
3. Step 2: date, time and number inputs with limits.
4. Step 3: text, tel and a required checkbox.
5. Grid the form and fieldsets.

6. Push prices right with margin-left: auto.

Project 874: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - Booking</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Book a bike</h1>
    <form action="/book" method="post" class="wizard">
      <fieldset>
        <legend>1. Choose a bike</legend>
    <label><input type="radio" name="item" value="City bike"
required> City bike <small>6500 EGP</small></label>
    <label><input type="radio" name="item" value="Mountain bike"
required> Mountain bike <small>11000 EGP</small></label>
    <label><input type="radio" name="item" value="Kids bike"
required> Kids bike <small>3200 EGP</small></label>
    <label><input type="radio" name="item" value="Tune-up" required>
Tune-up <small>250 EGP</small></label>
      </fieldset>
      <fieldset>
        <legend>2. When</legend>
        <label>Date <input type="date" name="date" required min="2026-
09-11"></label>
        <label>Time <input type="time" name="time" required
step="1800"></label>
        <label>People <input type="number" name="people" min="1"
max="10" value="1"></label>
      </fieldset>
      <fieldset>
        <legend>3. Your details</legend>
        <label>Name <input type="text" name="name" required
autocomplete="name"></label>
        <label>Phone <input type="tel" name="phone" required
autocomplete="tel" inputmode="tel"></label>
        <label><input type="checkbox" name="terms" required> I agree
to the cancellation policy</label>
      </fieldset>
      <button type="submit">Confirm booking</button>
    </form>
  </main>
</body>
</html>
```

Project 874: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.wizard { display: grid; gap: 1.5rem; }
fieldset { border: 1px solid var(--line); border-radius: 12px;
padding: 1rem 1.25rem; display: grid; gap: .6rem; }
legend { font-weight: 700; color: var(--brand); padding: 0 .4rem; }
label { display: flex; align-items: center; gap: .5rem; flex-wrap:
wrap; }
label small { margin-left: auto; color: var(--muted); }
input:not([type="radio"]):not([type="checkbox"]) { padding: .5rem .
7rem; border: 1px solid #bbb; border-radius: 8px; font: inherit; flex:
 1 1 8rem; }
button { justify-self: start; padding: .8rem 1.6rem; border: 0;
border-radius: 999px; background: var(--brand); color: #fff; font:
inherit; }
```

Project 874 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - Booking</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Book a bike	The main heading; only one per page.
<form action="/book" method="post" class="wizard">	A form; action is where the data goes, method how it is sent.
<fieldset>	Groups related form controls.
<legend>1. Choose a bike</legend>	Caption for the fieldset.
<label><input type="radio" name="item" value="City bike" required> ...	Text label for a control; for matches the control's id, or the label wraps the control.

Line	What it does
<label><input type="radio" name="item" value="Mountain bike" requir...	Radio button: one choice from a group sharing the same name.
<label><input type="radio" name="item" value="Kids bike" required> ...	A form control; its type decides what it looks like.
<label><input type="radio" name="item" value="Tune-up" required> Tu...	The field must be filled before the form can be submitted.
<label>Date <input type="date" name="date" required min="2026-09-11...	Date picker.
<label>Time <input type="time" name="time" required step="1800"></l...	Time picker.
<label>People <input type="number" name="people" min="1" max="10" v...	Numeric input with min, max and step.
<label>Name <input type="text" name="name" required autocomplete="n...	Tells the browser which saved value to offer (name, email, tel...).
<label>Phone <input type="tel" name="phone" required autocomplete="...	Telephone number; shows the phone keypad on mobiles.
<label><input type="checkbox" name="terms" required> I agree to the...	Checkbox: on or off.

Line	What it does
<button type="submit">Confirm booking</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.

Declaration	What it does
border-radius: 12px;	Rounds the corners.
font-weight: 700;	Thickness of the text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
input:not([type="radio"]):not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
flex: 1 1 8rem;	The item can grow and shrink from the given basis.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.
background: var(--brand);	Background colour or image.

Check your work

- Radios share one name
- Date min prevents past dates
- Every control labelled
- Checkbox required works

Exercises

1. Show one fieldset at a time with :has() and radio state or JavaScript.

2. Add a summary panel that updates live.
3. Add a progress tracker on top.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 875: Booking form in three steps for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 2 | Files: index.html, styles.css

Brief

Build a longer form divided into three fieldsets: radio choice with prices, date/time/number inputs, and personal details with a required checkbox.

Learning goals

- Group related controls with fieldset and legend
- Use date, time, number and tel input types with min/max/step
- Use wrapping labels

Elements and CSS used

HTML elements	CSS features
form, fieldset, legend, label, input (radio, date, time, number, text, tel, checkbox), small, button	fieldset border/radius, legend, display: flex on label, margin-left: auto, :not() chains

Build guide

1. Write three fieldsets with legends numbered 1 to 3.
2. Step 1: radio buttons with the same name, each wrapped in a label with the price in <small>.
3. Step 2: date, time and number inputs with limits.
4. Step 3: text, tel and a required checkbox.
5. Grid the form and fieldsets.

6. Push prices right with margin-left: auto.

Project 875: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - Booking</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Book a workshop</h1>
    <form action="/book" method="post" class="wizard">
      <fieldset>
        <legend>1. Choose a workshop</legend>
    <label><input type="radio" name="item" value="HTML weekend"
required> HTML weekend <small>Free</small></label>
    <label><input type="radio" name="item" value="CSS art" required>
CSS art <small>Free</small></label>
    <label><input type="radio" name="item" value="Scratch games"
required> Scratch games <small>Free</small></label>
    <label><input type="radio" name="item" value="Hackathon"
required> Hackathon <small>Free</small></label>
      </fieldset>
      <fieldset>
        <legend>2. When</legend>
        <label>Date <input type="date" name="date" required min="2026-
09-11"></label>
        <label>Time <input type="time" name="time" required
step="1800"></label>
        <label>People <input type="number" name="people" min="1"
max="10" value="1"></label>
      </fieldset>
      <fieldset>
        <legend>3. Your details</legend>
        <label>Name <input type="text" name="name" required
autocomplete="name"></label>
        <label>Phone <input type="tel" name="phone" required
autocomplete="tel" inputmode="tel"></label>
        <label><input type="checkbox" name="terms" required> I agree
to the cancellation policy</label>
      </fieldset>
      <button type="submit">Confirm booking</button>
    </form>
  </main>
</body>
</html>
```

Project 875: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.wizard { display: grid; gap: 1.5rem; }
fieldset { border: 1px solid var(--line); border-radius: 12px;
padding: 1rem 1.25rem; display: grid; gap: .6rem; }
legend { font-weight: 700; color: var(--brand); padding: 0 .4rem; }
label { display: flex; align-items: center; gap: .5rem; flex-wrap:
wrap; }
label small { margin-left: auto; color: var(--muted); }
input:not([type="radio"]):not([type="checkbox"]) { padding: .5rem .
7rem; border: 1px solid #bbb; border-radius: 8px; font: inherit; flex:
 1 1 8rem; }
button { justify-self: start; padding: .8rem 1.6rem; border: 0;
border-radius: 999px; background: var(--brand); color: #fff; font:
inherit; }
```

Project 875 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - Booking</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Book a workshop	The main heading; only one per page.
<form action="/book" method="post" class="wizard">	A form; action is where the data goes, method how it is sent.
<fieldset>	Groups related form controls.
<legend>1. Choose a workshop</legend>	Caption for the fieldset.
<label><input type="radio" name="item" value="HTML weekend" require...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="item" value="CSS art" required> CS...	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="item" value="Scratch games" requir...	A form control; its type decides what it looks like.
<label><input type="radio" name="item" value="Hackathon" required> ...	The field must be filled before the form can be submitted.
<label>Date <input type="date" name="date" required min="2026-09-11...	Date picker.
<label>Time <input type="time" name="time" required step="1800"></l...	Time picker.
<label>People <input type="number" name="people" min="1" max="10" v...	Numeric input with min, max and step.
<label>Name <input type="text" name="name" required autocomplete="n...	Tells the browser which saved value to offer (name, email, tel...).
<label>Phone <input type="tel" name="phone" required autocomplete="...	Telephone number; shows the phone keypad on mobiles.
<label><input type="checkbox" name="terms" required> I agree to the...	Checkbox: on or off.
<button type="submit">Confirm booking</button>	A clickable button; inside a form it submits by default.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 12px;	Rounds the corners.
font-weight: 700;	Thickness of the text.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
input:not([type="radio"]):not([type="checkbox"]) {	Excludes elements from a selector.
border: 1px solid #bbb;	The line around the element: width, style and colour.
font: inherit;	Makes form controls use the page font instead of the browser default.
flex: 1 1 8rem;	The item can grow and shrink from the given basis.
border: 0;	Removes the default border (for example on an iframe or button).
border-radius: 999px;	Fully rounded pill shape.
background: var(--brand);	Background colour or image.

Check your work

- Radios share one name
- Date min prevents past dates
- Every control labelled
- Checkbox required works

Exercises

1. Show one fieldset at a time with :has() and radio state or JavaScript.
2. Add a summary panel that updates live.
3. Add a progress tracker on top.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Video and audio page

Level 2 | 25 projects, one per theme

Embed a video with two source formats, poster image, English and Arabic caption tracks and a fallback link, plus an audio player with a transcript link.

Project 876: Video and audio page for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 2 | Files: index.html, styles.css

Brief

Embed a video with two source formats, poster image, English and Arabic caption tracks and a fallback link, plus an audio player with a transcript link.

Learning goals

- Provide multiple sources and captions
- Use preload and poster sensibly
- Keep media responsive with aspect-ratio

Elements and CSS used

HTML elements	CSS features
figure, video, source, track, p, a, figcaption, audio	aspect-ratio: 16 / 9, width: 100%, background, border-radius, max-width

Build guide

1. Write the video with controls, poster and dimensions.
2. Add WebM then MP4 sources.
3. Add caption tracks; mark one default.
4. Add fallback content inside the video.
5. Add the audio element and transcript link.
6. Make the video fluid.

Project 876: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Video tour</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Take a tour of Cairo Book Shop</h1>
    <figure class="video">
      <video controls preload="metadata" poster="images/poster.jpg"
width="1280" height="720">
        <source src="media/tour.webm" type="video/webm">
        <source src="media/tour.mp4" type="video/mp4">
        <track kind="captions" src="media/tour.en.vtt" srclang="en"
label="English" default>
        <track kind="captions" src="media/tour.ar.vtt" srclang="ar"
label="Arabic">
        <p>Your browser cannot play this video. <a href="media/tour.
mp4">Download it</a> instead.</p>
      </video>
      <figcaption>A two-minute walk through our Giza location with
Mohamed Khattab.</figcaption>
    </figure>
    <h2>Listen to our story</h2>
    <audio controls preload="none" src="media/story.mp3"></audio>
    <p><a href="media/story-transcript.html">Read the transcript</a></
p>
  </main>
</body>
</html>
```

Project 876: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.video { margin: 0; }
video { width: 100%; height: auto; aspect-ratio: 16 / 9; background:
#000; border-radius: 12px; }
figcaption { color: var(--muted); margin-top: .5rem; }
audio { width: 100%; max-width: 30rem; }
```

Project 876 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - Video tour</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Take a tour of Cairo Book Shop	The main heading; only one per page.
<figure class="video">	Self-contained media with an optional caption.
<video controls preload="metadata" poster="images/poster.jpg" width...	Video player; controls shows the built-in buttons.
<source src="media/tour.webm" type="video/webm">	One media source with its MIME type.
<track kind="captions" src="media/tour.en.vtt" srclang="en" label="...	Captions or subtitles file for media.

Line	What it does
<track kind="captions" src="media/tour.ar.vtt" srclang="ar" label="...	A table row.
Your browser cannot play this video. <a href="media/tour.mp4">Do...	A paragraph of text.
<figcaption>A two-minute walk through our Giza location with Mohame...	Caption for the figure.
Listen to our story	Second-level heading for a section.
<audio controls preload="none" src="media/story.mp3"></audio>	Audio player.
Read the transcript	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 16 / 9;	Keeps a fixed width-to-height ratio, reserving space before media loads.
background: #000;	Background colour or image.
border-radius: 12px;	Rounds the corners.

Check your work

- Captions toggle appears in the player
- Video never wider than container
- Fallback link present
- Audio has a transcript

Exercises

1. Add chapters with kind="chapters".
2. Add a custom play button overlay.
3. Lazy-load the video with loading="lazy" on an iframe embed instead.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 877: Video and audio page for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 2 | Files: index.html, styles.css

Brief

Embed a video with two source formats, poster image, English and Arabic caption tracks and a fallback link, plus an audio player with a transcript link.

Learning goals

- Provide multiple sources and captions
- Use preload and poster sensibly
- Keep media responsive with aspect-ratio

Elements and CSS used

HTML elements	CSS features
figure, video, source, track, p, a, figcaption, audio	aspect-ratio: 16 / 9, width: 100%, background, border-radius, max-width

Build guide

1. Write the video with controls, poster and dimensions.
2. Add WebM then MP4 sources.
3. Add caption tracks; mark one default.
4. Add fallback content inside the video.
5. Add the audio element and transcript link.
6. Make the video fluid.

Project 877: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - Video tour</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Take a tour of Nile Bakery</h1>
    <figure class="video">
      <video controls preload="metadata" poster="images/poster.jpg"
width="1280" height="720">
        <source src="media/tour.webm" type="video/webm">
        <source src="media/tour.mp4" type="video/mp4">
        <track kind="captions" src="media/tour.en.vtt" srclang="en"
label="English" default>
        <track kind="captions" src="media/tour.ar.vtt" srclang="ar"
label="Arabic">
        <p>Your browser cannot play this video. <a href="media/tour.
mp4">Download it</a> instead.</p>
      </video>
      <figcaption>A two-minute walk through our Cairo location with
Sara Adel.</figcaption>
    </figure>
    <h2>Listen to our story</h2>
    <audio controls preload="none" src="media/story.mp3"></audio>
    <p><a href="media/story-transcript.html">Read the transcript</a></
p>
  </main>
</body>
</html>
```

Project 877: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.video { margin: 0; }
video { width: 100%; height: auto; aspect-ratio: 16 / 9; background:
#000; border-radius: 12px; }
figcaption { color: var(--muted); margin-top: .5rem; }
audio { width: 100%; max-width: 30rem; }
```

Project 877 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - Video tour</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Take a tour of Nile Bakery	The main heading; only one per page.
<figure class="video">	Self-contained media with an optional caption.
<video controls preload="metadata" poster="images/poster.jpg" width...	Video player; controls shows the built-in buttons.
<source src="media/tour.webm" type="video/webm">	One media source with its MIME type.
<track kind="captions" src="media/tour.en.vtt" srclang="en" label="...	Captions or subtitles file for media.

Line	What it does
<track kind="captions" src="media/tour.ar.vtt" srclang="ar" label="...	A table row.
Your browser cannot play this video. <a href="media/tour.mp4">Do...	A paragraph of text.
<figcaption>A two-minute walk through our Cairo location with Sara ...	Caption for the figure.
Listen to our story	Second-level heading for a section.
<audio controls preload="none" src="media/story.mp3"></audio>	Audio player.
Read the transcript	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 16 / 9;	Keeps a fixed width-to-height ratio, reserving space before media loads.
background: #000;	Background colour or image.
border-radius: 12px;	Rounds the corners.

Check your work

- Captions toggle appears in the player
- Video never wider than container
- Fallback link present
- Audio has a transcript

Exercises

1. Add chapters with kind="chapters".
2. Add a custom play button overlay.
3. Lazy-load the video with loading="lazy" on an iframe embed instead.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 878: Video and audio page for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 2 | Files: index.html, styles.css

Brief

Embed a video with two source formats, poster image, English and Arabic caption tracks and a fallback link, plus an audio player with a transcript link.

Learning goals

- Provide multiple sources and captions
- Use preload and poster sensibly
- Keep media responsive with aspect-ratio

Elements and CSS used

HTML elements	CSS features
figure, video, source, track, p, a, figcaption, audio	aspect-ratio: 16 / 9, width: 100%, background, border-radius, max-width

Build guide

1. Write the video with controls, poster and dimensions.
2. Add WebM then MP4 sources.
3. Add caption tracks; mark one default.
4. Add fallback content inside the video.
5. Add the audio element and transcript link.
6. Make the video fluid.

Project 878: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - Video tour</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Take a tour of Pyramid Fitness</h1>
    <figure class="video">
      <video controls preload="metadata" poster="images/poster.jpg"
width="1280" height="720">
        <source src="media/tour.webm" type="video/webm">
        <source src="media/tour.mp4" type="video/mp4">
        <track kind="captions" src="media/tour.en.vtt" srclang="en"
label="English" default>
        <track kind="captions" src="media/tour.ar.vtt" srclang="ar"
label="Arabic">
        <p>Your browser cannot play this video. <a href="media/tour.
mp4">Download it</a> instead.</p>
      </video>
      <figcaption>A two-minute walk through our 6th of October
location with Omar Farouk.</figcaption>
    </figure>
    <h2>Listen to our story</h2>
    <audio controls preload="none" src="media/story.mp3"></audio>
    <p><a href="media/story-transcript.html">Read the transcript</a></
p>
  </main>
</body>
</html>
```

Project 878: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.video { margin: 0; }
video { width: 100%; height: auto; aspect-ratio: 16 / 9; background:
#000; border-radius: 12px; }
figcaption { color: var(--muted); margin-top: .5rem; }
audio { width: 100%; max-width: 30rem; }
```

Project 878 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - Video tour</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Take a tour of Pyramid Fitness	The main heading; only one per page.
<figure class="video">	Self-contained media with an optional caption.
<video controls preload="metadata" poster="images/poster.jpg" width...	Video player; controls shows the built-in buttons.
<source src="media/tour.webm" type="video/webm">	One media source with its MIME type.
<track kind="captions" src="media/tour.en.vtt" srclang="en" label="...	Captions or subtitles file for media.

Line	What it does
<track kind="captions" src="media/tour.ar.vtt" srclang="ar" label="...	A table row.
Your browser cannot play this video. <a href="media/tour.mp4">Do...	A paragraph of text.
<figcaption>A two-minute walk through our 6th of October location w...	Caption for the figure.
Listen to our story	Second-level heading for a section.
<audio controls preload="none" src="media/story.mp3"></audio>	Audio player.
Read the transcript	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 16 / 9;	Keeps a fixed width-to-height ratio, reserving space before media loads.
background: #000;	Background colour or image.
border-radius: 12px;	Rounds the corners.

Check your work

- Captions toggle appears in the player
- Video never wider than container
- Fallback link present
- Audio has a transcript

Exercises

1. Add chapters with kind="chapters".
2. Add a custom play button overlay.
3. Lazy-load the video with loading="lazy" on an iframe embed instead.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 879: Video and audio page for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 2 | Files: index.html, styles.css

Brief

Embed a video with two source formats, poster image, English and Arabic caption tracks and a fallback link, plus an audio player with a transcript link.

Learning goals

- Provide multiple sources and captions
- Use preload and poster sensibly
- Keep media responsive with aspect-ratio

Elements and CSS used

HTML elements	CSS features
figure, video, source, track, p, a, figcaption, audio	aspect-ratio: 16 / 9, width: 100%, background, border-radius, max-width

Build guide

1. Write the video with controls, poster and dimensions.
2. Add WebM then MP4 sources.
3. Add caption tracks; mark one default.
4. Add fallback content inside the video.
5. Add the audio element and transcript link.
6. Make the video fluid.

Project 879: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - Video tour</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Take a tour of Delta Dental Clinic</h1>
    <figure class="video">
      <video controls preload="metadata" poster="images/poster.jpg"
width="1280" height="720">
        <source src="media/tour.webm" type="video/webm">
        <source src="media/tour.mp4" type="video/mp4">
        <track kind="captions" src="media/tour.en.vtt" srclang="en"
label="English" default>
        <track kind="captions" src="media/tour.ar.vtt" srclang="ar"
label="Arabic">
        <p>Your browser cannot play this video. <a href="media/tour.
mp4">Download it</a> instead.</p>
      </video>
      <figcaption>A two-minute walk through our Mansoura location
with Dr. Hana Youssef.</figcaption>
    </figure>
    <h2>Listen to our story</h2>
    <audio controls preload="none" src="media/story.mp3"></audio>
    <p><a href="media/story-transcript.html">Read the transcript</a></
p>
  </main>
</body>
</html>
```

Project 879: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.video { margin: 0; }
video { width: 100%; height: auto; aspect-ratio: 16 / 9; background:
#000; border-radius: 12px; }
figcaption { color: var(--muted); margin-top: .5rem; }
audio { width: 100%; max-width: 30rem; }
```

Project 879 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - Video tour</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Take a tour of Delta Dental Clinic	The main heading; only one per page.
<figure class="video">	Self-contained media with an optional caption.
<video controls preload="metadata" poster="images/poster.jpg" width...	Video player; controls shows the built-in buttons.
<source src="media/tour.webm" type="video/webm">	One media source with its MIME type.
<track kind="captions" src="media/tour.en.vtt" srclang="en" label="...	Captions or subtitles file for media.

Line	What it does
<track kind="captions" src="media/tour.ar.vtt" srclang="ar" label="...	A table row.
Your browser cannot play this video. <a href="media/tour.mp4">Do...	A paragraph of text.
<figcaption>A two-minute walk through our Mansoura location with Dr...	Caption for the figure.
Listen to our story	Second-level heading for a section.
<audio controls preload="none" src="media/story.mp3"></audio>	Audio player.
Read the transcript	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 16 / 9;	Keeps a fixed width-to-height ratio, reserving space before media loads.
background: #000;	Background colour or image.
border-radius: 12px;	Rounds the corners.

Check your work

- Captions toggle appears in the player
- Video never wider than container
- Fallback link present
- Audio has a transcript

Exercises

1. Add chapters with kind="chapters".
2. Add a custom play button overlay.
3. Lazy-load the video with loading="lazy" on an iframe embed instead.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 880: Video and audio page for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 2 | Files: index.html, styles.css

Brief

Embed a video with two source formats, poster image, English and Arabic caption tracks and a fallback link, plus an audio player with a transcript link.

Learning goals

- Provide multiple sources and captions
- Use preload and poster sensibly
- Keep media responsive with aspect-ratio

Elements and CSS used

HTML elements	CSS features
figure, video, source, track, p, a, figcaption, audio	aspect-ratio: 16 / 9, width: 100%, background, border-radius, max-width

Build guide

1. Write the video with controls, poster and dimensions.
2. Add WebM then MP4 sources.
3. Add caption tracks; mark one default.
4. Add fallback content inside the video.
5. Add the audio element and transcript link.
6. Make the video fluid.

Project 880: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - Video tour</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Take a tour of Red Sea Travel</h1>
    <figure class="video">
      <video controls preload="metadata" poster="images/poster.jpg"
width="1280" height="720">
        <source src="media/tour.webm" type="video/webm">
        <source src="media/tour.mp4" type="video/mp4">
        <track kind="captions" src="media/tour.en.vtt" srclang="en"
label="English" default>
        <track kind="captions" src="media/tour.ar.vtt" srclang="ar"
label="Arabic">
        <p>Your browser cannot play this video. <a href="media/tour.
mp4">Download it</a> instead.</p>
      </video>
      <figcaption>A two-minute walk through our Hurghada location
with Laila Mansour.</figcaption>
    </figure>
    <h2>Listen to our story</h2>
    <audio controls preload="none" src="media/story.mp3"></audio>
    <p><a href="media/story-transcript.html">Read the transcript</a></
p>
  </main>
</body>
</html>
```

Project 880: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.video { margin: 0; }
video { width: 100%; height: auto; aspect-ratio: 16 / 9; background:
#000; border-radius: 12px; }
figcaption { color: var(--muted); margin-top: .5rem; }
audio { width: 100%; max-width: 30rem; }
```

Project 880 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - Video tour</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Take a tour of Red Sea Travel	The main heading; only one per page.
<figure class="video">	Self-contained media with an optional caption.
<video controls preload="metadata" poster="images/poster.jpg" width...	Video player; controls shows the built-in buttons.
<source src="media/tour.webm" type="video/webm">	One media source with its MIME type.
<track kind="captions" src="media/tour.en.vtt" srclang="en" label="...	Captions or subtitles file for media.

Line	What it does
<track kind="captions" src="media/tour.ar.vtt" srclang="ar" label="...	A table row.
Your browser cannot play this video. <a href="media/tour.mp4">Do...	A paragraph of text.
<figcaption>A two-minute walk through our Hurghada location with La...	Caption for the figure.
Listen to our story	Second-level heading for a section.
<audio controls preload="none" src="media/story.mp3"></audio>	Audio player.
Read the transcript	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 16 / 9;	Keeps a fixed width-to-height ratio, reserving space before media loads.
background: #000;	Background colour or image.
border-radius: 12px;	Rounds the corners.

Check your work

- Captions toggle appears in the player
- Video never wider than container
- Fallback link present
- Audio has a transcript

Exercises

1. Add chapters with kind="chapters".
2. Add a custom play button overlay.
3. Lazy-load the video with loading="lazy" on an iframe embed instead.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 881: Video and audio page for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Embed a video with two source formats, poster image, English and Arabic caption tracks and a fallback link, plus an audio player with a transcript link.

Learning goals

- Provide multiple sources and captions
- Use preload and poster sensibly
- Keep media responsive with aspect-ratio

Elements and CSS used

HTML elements	CSS features
figure, video, source, track, p, a, figcaption, audio	aspect-ratio: 16 / 9, width: 100%, background, border-radius, max-width

Build guide

1. Write the video with controls, poster and dimensions.
2. Add WebM then MP4 sources.
3. Add caption tracks; mark one default.
4. Add fallback content inside the video.
5. Add the audio element and transcript link.
6. Make the video fluid.

Project 881: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - Video tour</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Take a tour of Lotus Language School</h1>
    <figure class="video">
      <video controls preload="metadata" poster="images/poster.jpg"
width="1280" height="720">
        <source src="media/tour.webm" type="video/webm">
        <source src="media/tour.mp4" type="video/mp4">
        <track kind="captions" src="media/tour.en.vtt" srclang="en"
label="English" default>
        <track kind="captions" src="media/tour.ar.vtt" srclang="ar"
label="Arabic">
        <p>Your browser cannot play this video. <a href="media/tour.
mp4">Download it</a> instead.</p>
      </video>
      <figcaption>A two-minute walk through our Alexandria location
with Nour El Din.</figcaption>
    </figure>
    <h2>Listen to our story</h2>
    <audio controls preload="none" src="media/story.mp3"></audio>
    <p><a href="media/story-transcript.html">Read the transcript</a></
p>
  </main>
</body>
</html>
```

Project 881: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.video { margin: 0; }
video { width: 100%; height: auto; aspect-ratio: 16 / 9; background:
#000; border-radius: 12px; }
figcaption { color: var(--muted); margin-top: .5rem; }
audio { width: 100%; max-width: 30rem; }
```

Project 881 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - Video tour</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Take a tour of Lotus Language School	The main heading; only one per page.
<figure class="video">	Self-contained media with an optional caption.
<video controls preload="metadata" poster="images/poster.jpg" width...	Video player; controls shows the built-in buttons.
<source src="media/tour.webm" type="video/webm">	One media source with its MIME type.
<track kind="captions" src="media/tour.en.vtt" srclang="en" label="...	Captions or subtitles file for media.

Line	What it does
<track kind="captions" src="media/tour.ar.vtt" srclang="ar" label="...	A table row.
Your browser cannot play this video. <a href="media/tour.mp4">Do...	A paragraph of text.
<figcaption>A two-minute walk through our Alexandria location with ...	Caption for the figure.
Listen to our story	Second-level heading for a section.
<audio controls preload="none" src="media/story.mp3"></audio>	Audio player.
Read the transcript	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 16 / 9;	Keeps a fixed width-to-height ratio, reserving space before media loads.
background: #000;	Background colour or image.
border-radius: 12px;	Rounds the corners.

Check your work

- Captions toggle appears in the player
- Video never wider than container
- Fallback link present
- Audio has a transcript

Exercises

1. Add chapters with kind="chapters".
2. Add a custom play button overlay.
3. Lazy-load the video with loading="lazy" on an iframe embed instead.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 882: Video and audio page for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 2 | Files: index.html, styles.css

Brief

Embed a video with two source formats, poster image, English and Arabic caption tracks and a fallback link, plus an audio player with a transcript link.

Learning goals

- Provide multiple sources and captions
- Use preload and poster sensibly
- Keep media responsive with aspect-ratio

Elements and CSS used

HTML elements	CSS features
figure, video, source, track, p, a, figcaption, audio	aspect-ratio: 16 / 9, width: 100%, background, border-radius, max-width

Build guide

1. Write the video with controls, poster and dimensions.
2. Add WebM then MP4 sources.
3. Add caption tracks; mark one default.
4. Add fallback content inside the video.
5. Add the audio element and transcript link.
6. Make the video fluid.

Project 882: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - Video tour</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Take a tour of Green Leaf Cafe</h1>
    <figure class="video">
      <video controls preload="metadata" poster="images/poster.jpg"
width="1280" height="720">
        <source src="media/tour.webm" type="video/webm">
        <source src="media/tour.mp4" type="video/mp4">
        <track kind="captions" src="media/tour.en.vtt" srclang="en"
label="English" default>
        <track kind="captions" src="media/tour.ar.vtt" srclang="ar"
label="Arabic">
        <p>Your browser cannot play this video. <a href="media/tour.
mp4">Download it</a> instead.</p>
      </video>
      <figcaption>A two-minute walk through our Zamalek location with
Karim Said.</figcaption>
    </figure>
    <h2>Listen to our story</h2>
    <audio controls preload="none" src="media/story.mp3"></audio>
    <p><a href="media/story-transcript.html">Read the transcript</a></
p>
  </main>
</body>
</html>
```

Project 882: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.video { margin: 0; }
video { width: 100%; height: auto; aspect-ratio: 16 / 9; background:
#000; border-radius: 12px; }
figcaption { color: var(--muted); margin-top: .5rem; }
audio { width: 100%; max-width: 30rem; }
```

Project 882 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - Video tour</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Take a tour of Green Leaf Cafe	The main heading; only one per page.
<figure class="video">	Self-contained media with an optional caption.
<video controls preload="metadata" poster="images/poster.jpg" width...	Video player; controls shows the built-in buttons.
<source src="media/tour.webm" type="video/webm">	One media source with its MIME type.
<track kind="captions" src="media/tour.en.vtt" srclang="en" label="...	Captions or subtitles file for media.

Line	What it does
<track kind="captions" src="media/tour.ar.vtt" srclang="ar" label="...	A table row.
Your browser cannot play this video. <a href="media/tour.mp4">Do...	A paragraph of text.
<figcaption>A two-minute walk through our Zamalek location with Kar...	Caption for the figure.
Listen to our story	Second-level heading for a section.
<audio controls preload="none" src="media/story.mp3"></audio>	Audio player.
Read the transcript	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 16 / 9;	Keeps a fixed width-to-height ratio, reserving space before media loads.
background: #000;	Background colour or image.
border-radius: 12px;	Rounds the corners.

Check your work

- Captions toggle appears in the player
- Video never wider than container
- Fallback link present
- Audio has a transcript

Exercises

1. Add chapters with kind="chapters".
2. Add a custom play button overlay.
3. Lazy-load the video with loading="lazy" on an iframe embed instead.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 883: Video and audio page for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 2 | Files: index.html, styles.css

Brief

Embed a video with two source formats, poster image, English and Arabic caption tracks and a fallback link, plus an audio player with a transcript link.

Learning goals

- Provide multiple sources and captions
- Use preload and poster sensibly
- Keep media responsive with aspect-ratio

Elements and CSS used

HTML elements	CSS features
figure, video, source, track, p, a, figcaption, audio	aspect-ratio: 16 / 9, width: 100%, background, border-radius, max-width

Build guide

1. Write the video with controls, poster and dimensions.
2. Add WebM then MP4 sources.
3. Add caption tracks; mark one default.
4. Add fallback content inside the video.
5. Add the audio element and transcript link.
6. Make the video fluid.

Project 883: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - Video tour</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Take a tour of Sinai Trekking Club</h1>
    <figure class="video">
      <video controls preload="metadata" poster="images/poster.jpg"
width="1280" height="720">
        <source src="media/tour.webm" type="video/webm">
        <source src="media/tour.mp4" type="video/mp4">
        <track kind="captions" src="media/tour.en.vtt" srclang="en"
label="English" default>
        <track kind="captions" src="media/tour.ar.vtt" srclang="ar"
label="Arabic">
        <p>Your browser cannot play this video. <a href="media/tour.
mp4">Download it</a> instead.</p>
      </video>
      <figcaption>A two-minute walk through our Saint Catherine
location with Yara Hamdy.</figcaption>
    </figure>
    <h2>Listen to our story</h2>
    <audio controls preload="none" src="media/story.mp3"></audio>
    <p><a href="media/story-transcript.html">Read the transcript</a></
p>
  </main>
</body>
</html>
```

Project 883: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.video { margin: 0; }
video { width: 100%; height: auto; aspect-ratio: 16 / 9; background:
#000; border-radius: 12px; }
figcaption { color: var(--muted); margin-top: .5rem; }
audio { width: 100%; max-width: 30rem; }
```

Project 883 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - Video tour</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Take a tour of Sinai Trekking Club	The main heading; only one per page.
<figure class="video">	Self-contained media with an optional caption.
<video controls preload="metadata" poster="images/poster.jpg" width...	Video player; controls shows the built-in buttons.
<source src="media/tour.webm" type="video/webm">	One media source with its MIME type.
<track kind="captions" src="media/tour.en.vtt" srclang="en" label="...	Captions or subtitles file for media.

Line	What it does
<track kind="captions" src="media/tour.ar.vtt" srclang="ar" label="...	A table row.
Your browser cannot play this video. <a href="media/tour.mp4">Do...	A paragraph of text.
<figcaption>A two-minute walk through our Saint Catherine location ...	Caption for the figure.
Listen to our story	Second-level heading for a section.
<audio controls preload="none" src="media/story.mp3"></audio>	Audio player.
Read the transcript	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 16 / 9;	Keeps a fixed width-to-height ratio, reserving space before media loads.
background: #000;	Background colour or image.
border-radius: 12px;	Rounds the corners.

Check your work

- Captions toggle appears in the player
- Video never wider than container
- Fallback link present
- Audio has a transcript

Exercises

1. Add chapters with kind="chapters".
2. Add a custom play button overlay.
3. Lazy-load the video with loading="lazy" on an iframe embed instead.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 884: Video and audio page for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 2 | Files: index.html, styles.css

Brief

Embed a video with two source formats, poster image, English and Arabic caption tracks and a fallback link, plus an audio player with a transcript link.

Learning goals

- Provide multiple sources and captions
- Use preload and poster sensibly
- Keep media responsive with aspect-ratio

Elements and CSS used

HTML elements	CSS features
figure, video, source, track, p, a, figcaption, audio	aspect-ratio: 16 / 9, width: 100%, background, border-radius, max-width

Build guide

1. Write the video with controls, poster and dimensions.
2. Add WebM then MP4 sources.
3. Add caption tracks; mark one default.
4. Add fallback content inside the video.
5. Add the audio element and transcript link.
6. Make the video fluid.

Project 884: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - Video tour</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Take a tour of Horizon Photography</h1>
    <figure class="video">
      <video controls preload="metadata" poster="images/poster.jpg"
width="1280" height="720">
        <source src="media/tour.webm" type="video/webm">
        <source src="media/tour.mp4" type="video/mp4">
        <track kind="captions" src="media/tour.en.vtt" srclang="en"
label="English" default>
        <track kind="captions" src="media/tour.ar.vtt" srclang="ar"
label="Arabic">
        <p>Your browser cannot play this video. <a href="media/tour.
mp4">Download it</a> instead.</p>
      </video>
      <figcaption>A two-minute walk through our Maadi location with
Adham Nabil.</figcaption>
    </figure>
    <h2>Listen to our story</h2>
    <audio controls preload="none" src="media/story.mp3"></audio>
    <p><a href="media/story-transcript.html">Read the transcript</a></
p>
  </main>
</body>
</html>
```

Project 884: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.video { margin: 0; }
video { width: 100%; height: auto; aspect-ratio: 16 / 9; background:
#000; border-radius: 12px; }
figcaption { color: var(--muted); margin-top: .5rem; }
audio { width: 100%; max-width: 30rem; }
```

Project 884 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - Video tour</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Take a tour of Horizon Photography	The main heading; only one per page.
<figure class="video">	Self-contained media with an optional caption.
<video controls preload="metadata" poster="images/poster.jpg" width...	Video player; controls shows the built-in buttons.
<source src="media/tour.webm" type="video/webm">	One media source with its MIME type.
<track kind="captions" src="media/tour.en.vtt" srclang="en" label="...	Captions or subtitles file for media.

Line	What it does
<track kind="captions" src="media/tour.ar.vtt" srclang="ar" label="...	A table row.
Your browser cannot play this video. <a href="media/tour.mp4">Do...	A paragraph of text.
<figcaption>A two-minute walk through our Maadi location with Adham...	Caption for the figure.
Listen to our story	Second-level heading for a section.
<audio controls preload="none" src="media/story.mp3"></audio>	Audio player.
Read the transcript	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 16 / 9;	Keeps a fixed width-to-height ratio, reserving space before media loads.
background: #000;	Background colour or image.
border-radius: 12px;	Rounds the corners.

Check your work

- Captions toggle appears in the player
- Video never wider than container
- Fallback link present
- Audio has a transcript

Exercises

1. Add chapters with kind="chapters".
2. Add a custom play button overlay.
3. Lazy-load the video with loading="lazy" on an iframe embed instead.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 885: Video and audio page for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 2 | Files: index.html, styles.css

Brief

Embed a video with two source formats, poster image, English and Arabic caption tracks and a fallback link, plus an audio player with a transcript link.

Learning goals

- Provide multiple sources and captions
- Use preload and poster sensibly
- Keep media responsive with aspect-ratio

Elements and CSS used

HTML elements	CSS features
figure, video, source, track, p, a, figcaption, audio	aspect-ratio: 16 / 9, width: 100%, background, border-radius, max-width

Build guide

1. Write the video with controls, poster and dimensions.
2. Add WebM then MP4 sources.
3. Add caption tracks; mark one default.
4. Add fallback content inside the video.
5. Add the audio element and transcript link.
6. Make the video fluid.

Project 885: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - Video tour</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Take a tour of Papyrus Stationery</h1>
    <figure class="video">
      <video controls preload="metadata" poster="images/poster.jpg"
width="1280" height="720">
        <source src="media/tour.webm" type="video/webm">
        <source src="media/tour.mp4" type="video/mp4">
        <track kind="captions" src="media/tour.en.vtt" srclang="en"
label="English" default>
        <track kind="captions" src="media/tour.ar.vtt" srclang="ar"
label="Arabic">
        <p>Your browser cannot play this video. <a href="media/tour.
mp4">Download it</a> instead.</p>
      </video>
      <figcaption>A two-minute walk through our Heliopolis location
with Dina Fathy.</figcaption>
    </figure>
    <h2>Listen to our story</h2>
    <audio controls preload="none" src="media/story.mp3"></audio>
    <p><a href="media/story-transcript.html">Read the transcript</a></
p>
  </main>
</body>
</html>
```

Project 885: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.video { margin: 0; }
video { width: 100%; height: auto; aspect-ratio: 16 / 9; background:
#000; border-radius: 12px; }
figcaption { color: var(--muted); margin-top: .5rem; }
audio { width: 100%; max-width: 30rem; }
```

Project 885 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - Video tour</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Take a tour of Papyrus Stationery	The main heading; only one per page.
<figure class="video">	Self-contained media with an optional caption.
<video controls preload="metadata" poster="images/poster.jpg" width...	Video player; controls shows the built-in buttons.
<source src="media/tour.webm" type="video/webm">	One media source with its MIME type.
<track kind="captions" src="media/tour.en.vtt" srclang="en" label="...	Captions or subtitles file for media.

Line	What it does
<track kind="captions" src="media/tour.ar.vtt" srclang="ar" label="...	A table row.
Your browser cannot play this video. <a href="media/tour.mp4">Do...	A paragraph of text.
<figcaption>A two-minute walk through our Heliopolis location with ...	Caption for the figure.
Listen to our story	Second-level heading for a section.
<audio controls preload="none" src="media/story.mp3"></audio>	Audio player.
Read the transcript	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 16 / 9;	Keeps a fixed width-to-height ratio, reserving space before media loads.
background: #000;	Background colour or image.
border-radius: 12px;	Rounds the corners.

Check your work

- Captions toggle appears in the player
- Video never wider than container
- Fallback link present
- Audio has a transcript

Exercises

1. Add chapters with kind="chapters".
2. Add a custom play button overlay.
3. Lazy-load the video with loading="lazy" on an iframe embed instead.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 886: Video and audio page for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 2 | Files: index.html, styles.css

Brief

Embed a video with two source formats, poster image, English and Arabic caption tracks and a fallback link, plus an audio player with a transcript link.

Learning goals

- Provide multiple sources and captions
- Use preload and poster sensibly
- Keep media responsive with aspect-ratio

Elements and CSS used

HTML elements	CSS features
figure, video, source, track, p, a, figcaption, audio	aspect-ratio: 16 / 9, width: 100%, background, border-radius, max-width

Build guide

1. Write the video with controls, poster and dimensions.
2. Add WebM then MP4 sources.
3. Add caption tracks; mark one default.
4. Add fallback content inside the video.
5. Add the audio element and transcript link.
6. Make the video fluid.

Project 886: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - Video tour</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Take a tour of Oasis Plant Nursery</h1>
    <figure class="video">
      <video controls preload="metadata" poster="images/poster.jpg"
width="1280" height="720">
        <source src="media/tour.webm" type="video/webm">
        <source src="media/tour.mp4" type="video/mp4">
        <track kind="captions" src="media/tour.en.vtt" srclang="en"
label="English" default>
        <track kind="captions" src="media/tour.ar.vtt" srclang="ar"
label="Arabic">
        <p>Your browser cannot play this video. <a href="media/tour.
mp4">Download it</a> instead.</p>
      </video>
      <figcaption>A two-minute walk through our Sheikh Zayed location
with Hossam Ali.</figcaption>
    </figure>
    <h2>Listen to our story</h2>
    <audio controls preload="none" src="media/story.mp3"></audio>
    <p><a href="media/story-transcript.html">Read the transcript</a></
p>
  </main>
</body>
</html>
```

Project 886: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.video { margin: 0; }
video { width: 100%; height: auto; aspect-ratio: 16 / 9; background:
#000; border-radius: 12px; }
figcaption { color: var(--muted); margin-top: .5rem; }
audio { width: 100%; max-width: 30rem; }
```

Project 886 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - Video tour</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Take a tour of Oasis Plant Nursery	The main heading; only one per page.
<figure class="video">	Self-contained media with an optional caption.
<video controls preload="metadata" poster="images/poster.jpg" width...	Video player; controls shows the built-in buttons.
<source src="media/tour.webm" type="video/webm">	One media source with its MIME type.
<track kind="captions" src="media/tour.en.vtt" srclang="en" label="...	Captions or subtitles file for media.

Line	What it does
<track kind="captions" src="media/tour.ar.vtt" srclang="ar" label="...	A table row.
Your browser cannot play this video. <a href="media/tour.mp4">Do...	A paragraph of text.
<figcaption>A two-minute walk through our Sheikh Zayed location wit...	Caption for the figure.
Listen to our story	Second-level heading for a section.
<audio controls preload="none" src="media/story.mp3"></audio>	Audio player.
Read the transcript	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 16 / 9;	Keeps a fixed width-to-height ratio, reserving space before media loads.
background: #000;	Background colour or image.
border-radius: 12px;	Rounds the corners.

Check your work

- Captions toggle appears in the player
- Video never wider than container
- Fallback link present
- Audio has a transcript

Exercises

1. Add chapters with kind="chapters".
2. Add a custom play button overlay.
3. Lazy-load the video with loading="lazy" on an iframe embed instead.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 887: Video and audio page for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 2 | Files: index.html, styles.css

Brief

Embed a video with two source formats, poster image, English and Arabic caption tracks and a fallback link, plus an audio player with a transcript link.

Learning goals

- Provide multiple sources and captions
- Use preload and poster sensibly
- Keep media responsive with aspect-ratio

Elements and CSS used

HTML elements	CSS features
figure, video, source, track, p, a, figcaption, audio	aspect-ratio: 16 / 9, width: 100%, background, border-radius, max-width

Build guide

1. Write the video with controls, poster and dimensions.
2. Add WebM then MP4 sources.
3. Add caption tracks; mark one default.
4. Add fallback content inside the video.
5. Add the audio element and transcript link.
6. Make the video fluid.

Project 887: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - Video tour</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Take a tour of Cedar Furniture</h1>
    <figure class="video">
      <video controls preload="metadata" poster="images/poster.jpg"
width="1280" height="720">
        <source src="media/tour.webm" type="video/webm">
        <source src="media/tour.mp4" type="video/mp4">
        <track kind="captions" src="media/tour.en.vtt" srclang="en"
label="English" default>
        <track kind="captions" src="media/tour.ar.vtt" srclang="ar"
label="Arabic">
        <p>Your browser cannot play this video. <a href="media/tour.
mp4">Download it</a> instead.</p>
      </video>
      <figcaption>A two-minute walk through our Damietta location
with Tarek Lotfy.</figcaption>
    </figure>
    <h2>Listen to our story</h2>
    <audio controls preload="none" src="media/story.mp3"></audio>
    <p><a href="media/story-transcript.html">Read the transcript</a></
p>
  </main>
</body>
</html>
```

Project 887: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.video { margin: 0; }
video { width: 100%; height: auto; aspect-ratio: 16 / 9; background:
#000; border-radius: 12px; }
figcaption { color: var(--muted); margin-top: .5rem; }
audio { width: 100%; max-width: 30rem; }
```

Project 887 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - Video tour</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Take a tour of Cedar Furniture	The main heading; only one per page.
<figure class="video">	Self-contained media with an optional caption.
<video controls preload="metadata" poster="images/poster.jpg" width...	Video player; controls shows the built-in buttons.
<source src="media/tour.webm" type="video/webm">	One media source with its MIME type.
<track kind="captions" src="media/tour.en.vtt" srclang="en" label="...	Captions or subtitles file for media.

Line	What it does
<track kind="captions" src="media/tour.ar.vtt" srclang="ar" label="...	A table row.
Your browser cannot play this video. <a href="media/tour.mp4">Do...	A paragraph of text.
<figcaption>A two-minute walk through our Damietta location with Ta...	Caption for the figure.
Listen to our story	Second-level heading for a section.
<audio controls preload="none" src="media/story.mp3"></audio>	Audio player.
Read the transcript	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 16 / 9;	Keeps a fixed width-to-height ratio, reserving space before media loads.
background: #000;	Background colour or image.
border-radius: 12px;	Rounds the corners.

Check your work

- Captions toggle appears in the player
- Video never wider than container
- Fallback link present
- Audio has a transcript

Exercises

1. Add chapters with kind="chapters".
2. Add a custom play button overlay.
3. Lazy-load the video with loading="lazy" on an iframe embed instead.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 888: Video and audio page for Byte Repair

Theme: Byte Repair (Nasr City) | Level 2 | Files: index.html, styles.css

Brief

Embed a video with two source formats, poster image, English and Arabic caption tracks and a fallback link, plus an audio player with a transcript link.

Learning goals

- Provide multiple sources and captions
- Use preload and poster sensibly
- Keep media responsive with aspect-ratio

Elements and CSS used

HTML elements	CSS features
figure, video, source, track, p, a, figcaption, audio	aspect-ratio: 16 / 9, width: 100%, background, border-radius, max-width

Build guide

1. Write the video with controls, poster and dimensions.
2. Add WebM then MP4 sources.
3. Add caption tracks; mark one default.
4. Add fallback content inside the video.
5. Add the audio element and transcript link.
6. Make the video fluid.

Project 888: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - Video tour</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Take a tour of Byte Repair</h1>
    <figure class="video">
      <video controls preload="metadata" poster="images/poster.jpg"
width="1280" height="720">
        <source src="media/tour.webm" type="video/webm">
        <source src="media/tour.mp4" type="video/mp4">
        <track kind="captions" src="media/tour.en.vtt" srclang="en"
label="English" default>
        <track kind="captions" src="media/tour.ar.vtt" srclang="ar"
label="Arabic">
        <p>Your browser cannot play this video. <a href="media/tour.
mp4">Download it</a> instead.</p>
      </video>
      <figcaption>A two-minute walk through our Nasr City location
with Mostafa Gamal.</figcaption>
    </figure>
    <h2>Listen to our story</h2>
    <audio controls preload="none" src="media/story.mp3"></audio>
    <p><a href="media/story-transcript.html">Read the transcript</a></
p>
  </main>
</body>
</html>
```

Project 888: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.video { margin: 0; }
video { width: 100%; height: auto; aspect-ratio: 16 / 9; background:
#000; border-radius: 12px; }
figcaption { color: var(--muted); margin-top: .5rem; }
audio { width: 100%; max-width: 30rem; }
```

Project 888 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - Video tour</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Take a tour of Byte Repair	The main heading; only one per page.
<figure class="video">	Self-contained media with an optional caption.
<video controls preload="metadata" poster="images/poster.jpg" width...	Video player; controls shows the built-in buttons.
<source src="media/tour.webm" type="video/webm">	One media source with its MIME type.
<track kind="captions" src="media/tour.en.vtt" srclang="en" label="...	Captions or subtitles file for media.

Line	What it does
<track kind="captions" src="media/tour.ar.vtt" srclang="ar" label="...	A table row.
Your browser cannot play this video. <a href="media/tour.mp4">Do...	A paragraph of text.
<figcaption>A two-minute walk through our Nasr City location with M...	Caption for the figure.
Listen to our story	Second-level heading for a section.
<audio controls preload="none" src="media/story.mp3"></audio>	Audio player.
Read the transcript	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 16 / 9;	Keeps a fixed width-to-height ratio, reserving space before media loads.
background: #000;	Background colour or image.
border-radius: 12px;	Rounds the corners.

Check your work

- Captions toggle appears in the player
- Video never wider than container
- Fallback link present
- Audio has a transcript

Exercises

1. Add chapters with kind="chapters".
2. Add a custom play button overlay.
3. Lazy-load the video with loading="lazy" on an iframe embed instead.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 889: Video and audio page for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 2 | Files: index.html, styles.css

Brief

Embed a video with two source formats, poster image, English and Arabic caption tracks and a fallback link, plus an audio player with a transcript link.

Learning goals

- Provide multiple sources and captions
- Use preload and poster sensibly
- Keep media responsive with aspect-ratio

Elements and CSS used

HTML elements	CSS features
figure, video, source, track, p, a, figcaption, audio	aspect-ratio: 16 / 9, width: 100%, background, border-radius, max-width

Build guide

1. Write the video with controls, poster and dimensions.
2. Add WebM then MP4 sources.
3. Add caption tracks; mark one default.
4. Add fallback content inside the video.
5. Add the audio element and transcript link.
6. Make the video fluid.

Project 889: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - Video tour</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Take a tour of Sahara Pet Care</h1>
    <figure class="video">
      <video controls preload="metadata" poster="images/poster.jpg"
width="1280" height="720">
        <source src="media/tour.webm" type="video/webm">
        <source src="media/tour.mp4" type="video/mp4">
        <track kind="captions" src="media/tour.en.vtt" srclang="en"
label="English" default>
        <track kind="captions" src="media/tour.ar.vtt" srclang="ar"
label="Arabic">
        <p>Your browser cannot play this video. <a href="media/tour.
mp4">Download it</a> instead.</p>
      </video>
      <figcaption>A two-minute walk through our New Cairo location
with Rana Ibrahim.</figcaption>
    </figure>
    <h2>Listen to our story</h2>
    <audio controls preload="none" src="media/story.mp3"></audio>
    <p><a href="media/story-transcript.html">Read the transcript</a></
p>
  </main>
</body>
</html>
```

Project 889: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.video { margin: 0; }
video { width: 100%; height: auto; aspect-ratio: 16 / 9; background:
#000; border-radius: 12px; }
figcaption { color: var(--muted); margin-top: .5rem; }
audio { width: 100%; max-width: 30rem; }
```

Project 889 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - Video tour</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Take a tour of Sahara Pet Care	The main heading; only one per page.
<figure class="video">	Self-contained media with an optional caption.
<video controls preload="metadata" poster="images/poster.jpg" width...	Video player; controls shows the built-in buttons.
<source src="media/tour.webm" type="video/webm">	One media source with its MIME type.
<track kind="captions" src="media/tour.en.vtt" srclang="en" label="...	Captions or subtitles file for media.

Line	What it does
<track kind="captions" src="media/tour.ar.vtt" srclang="ar" label="...	A table row.
Your browser cannot play this video. <a href="media/tour.mp4">Do...	A paragraph of text.
<figcaption>A two-minute walk through our New Cairo location with R...	Caption for the figure.
Listen to our story	Second-level heading for a section.
<audio controls preload="none" src="media/story.mp3"></audio>	Audio player.
Read the transcript	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 16 / 9;	Keeps a fixed width-to-height ratio, reserving space before media loads.
background: #000;	Background colour or image.
border-radius: 12px;	Rounds the corners.

Check your work

- Captions toggle appears in the player
- Video never wider than container
- Fallback link present
- Audio has a transcript

Exercises

1. Add chapters with kind="chapters".
2. Add a custom play button overlay.
3. Lazy-load the video with loading="lazy" on an iframe embed instead.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 890: Video and audio page for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Embed a video with two source formats, poster image, English and Arabic caption tracks and a fallback link, plus an audio player with a transcript link.

Learning goals

- Provide multiple sources and captions
- Use preload and poster sensibly
- Keep media responsive with aspect-ratio

Elements and CSS used

HTML elements	CSS features
figure, video, source, track, p, a, figcaption, audio	aspect-ratio: 16 / 9, width: 100%, background, border-radius, max-width

Build guide

1. Write the video with controls, poster and dimensions.
2. Add WebM then MP4 sources.
3. Add caption tracks; mark one default.
4. Add fallback content inside the video.
5. Add the audio element and transcript link.
6. Make the video fluid.

Project 890: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - Video tour</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Take a tour of Alexandria Sailing School</h1>
    <figure class="video">
      <video controls preload="metadata" poster="images/poster.jpg"
width="1280" height="720">
        <source src="media/tour.webm" type="video/webm">
        <source src="media/tour.mp4" type="video/mp4">
        <track kind="captions" src="media/tour.en.vtt" srclang="en"
label="English" default>
        <track kind="captions" src="media/tour.ar.vtt" srclang="ar"
label="Arabic">
        <p>Your browser cannot play this video. <a href="media/tour.
mp4">Download it</a> instead.</p>
      </video>
      <figcaption>A two-minute walk through our Alexandria location
with Amr Selim.</figcaption>
    </figure>
    <h2>Listen to our story</h2>
    <audio controls preload="none" src="media/story.mp3"></audio>
    <p><a href="media/story-transcript.html">Read the transcript</a></
p>
  </main>
</body>
</html>
```

Project 890: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.video { margin: 0; }
video { width: 100%; height: auto; aspect-ratio: 16 / 9; background:
#000; border-radius: 12px; }
figcaption { color: var(--muted); margin-top: .5rem; }
audio { width: 100%; max-width: 30rem; }
```

Project 890 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - Video tour</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Take a tour of Alexandria Sailing School	The main heading; only one per page.
<figure class="video">	Self-contained media with an optional caption.
<video controls preload="metadata" poster="images/poster.jpg" width...	Video player; controls shows the built-in buttons.
<source src="media/tour.webm" type="video/webm">	One media source with its MIME type.
<track kind="captions" src="media/tour.en.vtt" srclang="en" label="...	Captions or subtitles file for media.

Line	What it does
<track kind="captions" src="media/tour.ar.vtt" srclang="ar" label="...	A table row.
Your browser cannot play this video. <a href="media/tour.mp4">Do...	A paragraph of text.
<figcaption>A two-minute walk through our Alexandria location with ...	Caption for the figure.
Listen to our story	Second-level heading for a section.
<audio controls preload="none" src="media/story.mp3"></audio>	Audio player.
Read the transcript	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 16 / 9;	Keeps a fixed width-to-height ratio, reserving space before media loads.
background: #000;	Background colour or image.
border-radius: 12px;	Rounds the corners.

Check your work

- Captions toggle appears in the player
- Video never wider than container
- Fallback link present
- Audio has a transcript

Exercises

1. Add chapters with kind="chapters".
2. Add a custom play button overlay.
3. Lazy-load the video with loading="lazy" on an iframe embed instead.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 891: Video and audio page for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Embed a video with two source formats, poster image, English and Arabic caption tracks and a fallback link, plus an audio player with a transcript link.

Learning goals

- Provide multiple sources and captions
- Use preload and poster sensibly
- Keep media responsive with aspect-ratio

Elements and CSS used

HTML elements	CSS features
figure, video, source, track, p, a, figcaption, audio	aspect-ratio: 16 / 9, width: 100%, background, border-radius, max-width

Build guide

1. Write the video with controls, poster and dimensions.
2. Add WebM then MP4 sources.
3. Add caption tracks; mark one default.
4. Add fallback content inside the video.
5. Add the audio element and transcript link.
6. Make the video fluid.

Project 891: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - Video tour</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Take a tour of Habiba Handmade Jewellery</h1>
    <figure class="video">
      <video controls preload="metadata" poster="images/poster.jpg"
width="1280" height="720">
        <source src="media/tour.webm" type="video/webm">
        <source src="media/tour.mp4" type="video/mp4">
        <track kind="captions" src="media/tour.en.vtt" srclang="en"
label="English" default>
        <track kind="captions" src="media/tour.ar.vtt" srclang="ar"
label="Arabic">
        <p>Your browser cannot play this video. <a href="media/tour.
mp4">Download it</a> instead.</p>
      </video>
      <figcaption>A two-minute walk through our Aswan location with
Habiba Saleh.</figcaption>
    </figure>
    <h2>Listen to our story</h2>
    <audio controls preload="none" src="media/story.mp3"></audio>
    <p><a href="media/story-transcript.html">Read the transcript</a></
p>
  </main>
</body>
</html>
```

Project 891: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.video { margin: 0; }
video { width: 100%; height: auto; aspect-ratio: 16 / 9; background:
#000; border-radius: 12px; }
figcaption { color: var(--muted); margin-top: .5rem; }
audio { width: 100%; max-width: 30rem; }
```

Project 891 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - Video tour</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Take a tour of Habiba Handmade Jewellery	The main heading; only one per page.
<figure class="video">	Self-contained media with an optional caption.
<video controls preload="metadata" poster="images/poster.jpg" width...	Video player; controls shows the built-in buttons.
<source src="media/tour.webm" type="video/webm">	One media source with its MIME type.
<track kind="captions" src="media/tour.en.vtt" srclang="en" label="...	Captions or subtitles file for media.

Line	What it does
<track kind="captions" src="media/tour.ar.vtt" srclang="ar" label="...	A table row.
Your browser cannot play this video. <a href="media/tour.mp4">Do...	A paragraph of text.
<figcaption>A two-minute walk through our Aswan location with Habib...	Caption for the figure.
Listen to our story	Second-level heading for a section.
<audio controls preload="none" src="media/story.mp3"></audio>	Audio player.
Read the transcript	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 16 / 9;	Keeps a fixed width-to-height ratio, reserving space before media loads.
background: #000;	Background colour or image.
border-radius: 12px;	Rounds the corners.

Check your work

- Captions toggle appears in the player
- Video never wider than container
- Fallback link present
- Audio has a transcript

Exercises

1. Add chapters with kind="chapters".
2. Add a custom play button overlay.
3. Lazy-load the video with loading="lazy" on an iframe embed instead.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 892: Video and audio page for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 2 | Files: index.html, styles.css

Brief

Embed a video with two source formats, poster image, English and Arabic caption tracks and a fallback link, plus an audio player with a transcript link.

Learning goals

- Provide multiple sources and captions
- Use preload and poster sensibly
- Keep media responsive with aspect-ratio

Elements and CSS used

HTML elements	CSS features
figure, video, source, track, p, a, figcaption, audio	aspect-ratio: 16 / 9, width: 100%, background, border-radius, max-width

Build guide

1. Write the video with controls, poster and dimensions.
2. Add WebM then MP4 sources.
3. Add caption tracks; mark one default.
4. Add fallback content inside the video.
5. Add the audio element and transcript link.
6. Make the video fluid.

Project 892: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - Video tour</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Take a tour of Fayoum Pottery Studio</h1>
    <figure class="video">
      <video controls preload="metadata" poster="images/poster.jpg"
width="1280" height="720">
        <source src="media/tour.webm" type="video/webm">
        <source src="media/tour.mp4" type="video/mp4">
        <track kind="captions" src="media/tour.en.vtt" srclang="en"
label="English" default>
        <track kind="captions" src="media/tour.ar.vtt" srclang="ar"
label="Arabic">
        <p>Your browser cannot play this video. <a href="media/tour.
mp4">Download it</a> instead.</p>
      </video>
      <figcaption>A two-minute walk through our Tunis Village
location with Ahmed Mahmoud.</figcaption>
    </figure>
    <h2>Listen to our story</h2>
    <audio controls preload="none" src="media/story.mp3"></audio>
    <p><a href="media/story-transcript.html">Read the transcript</a></
p>
  </main>
</body>
</html>
```

Project 892: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.video { margin: 0; }
video { width: 100%; height: auto; aspect-ratio: 16 / 9; background:
#000; border-radius: 12px; }
figcaption { color: var(--muted); margin-top: .5rem; }
audio { width: 100%; max-width: 30rem; }
```

Project 892 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - Video tour</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Take a tour of Fayoum Pottery Studio	The main heading; only one per page.
<figure class="video">	Self-contained media with an optional caption.
<video controls preload="metadata" poster="images/poster.jpg" width...	Video player; controls shows the built-in buttons.
<source src="media/tour.webm" type="video/webm">	One media source with its MIME type.
<track kind="captions" src="media/tour.en.vtt" srclang="en" label="...	Captions or subtitles file for media.

Line	What it does
<track kind="captions" src="media/tour.ar.vtt" srclang="ar" label="...	A table row.
Your browser cannot play this video. <a href="media/tour.mp4">Do...	A paragraph of text.
<figcaption>A two-minute walk through our Tunis Village location wi...	Caption for the figure.
Listen to our story	Second-level heading for a section.
<audio controls preload="none" src="media/story.mp3"></audio>	Audio player.
Read the transcript	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 16 / 9;	Keeps a fixed width-to-height ratio, reserving space before media loads.
background: #000;	Background colour or image.
border-radius: 12px;	Rounds the corners.

Check your work

- Captions toggle appears in the player
- Video never wider than container
- Fallback link present
- Audio has a transcript

Exercises

1. Add chapters with kind="chapters".
2. Add a custom play button overlay.
3. Lazy-load the video with loading="lazy" on an iframe embed instead.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 893: Video and audio page for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 2 | Files: index.html, styles.css

Brief

Embed a video with two source formats, poster image, English and Arabic caption tracks and a fallback link, plus an audio player with a transcript link.

Learning goals

- Provide multiple sources and captions
- Use preload and poster sensibly
- Keep media responsive with aspect-ratio

Elements and CSS used

HTML elements	CSS features
figure, video, source, track, p, a, figcaption, audio	aspect-ratio: 16 / 9, width: 100%, background, border-radius, max-width

Build guide

1. Write the video with controls, poster and dimensions.
2. Add WebM then MP4 sources.
3. Add caption tracks; mark one default.
4. Add fallback content inside the video.
5. Add the audio element and transcript link.
6. Make the video fluid.

Project 893: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - Video tour</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Take a tour of Cleopatra Beauty Salon</h1>
    <figure class="video">
      <video controls preload="metadata" poster="images/poster.jpg"
width="1280" height="720">
        <source src="media/tour.webm" type="video/webm">
        <source src="media/tour.mp4" type="video/mp4">
        <track kind="captions" src="media/tour.en.vtt" srclang="en"
label="English" default>
        <track kind="captions" src="media/tour.ar.vtt" srclang="ar"
label="Arabic">
        <p>Your browser cannot play this video. <a href="media/tour.
mp4">Download it</a> instead.</p>
      </video>
      <figcaption>A two-minute walk through our Dokki location with
Mariam Adel.</figcaption>
    </figure>
    <h2>Listen to our story</h2>
    <audio controls preload="none" src="media/story.mp3"></audio>
    <p><a href="media/story-transcript.html">Read the transcript</a></
p>
  </main>
</body>
</html>
```

Project 893: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.video { margin: 0; }
video { width: 100%; height: auto; aspect-ratio: 16 / 9; background:
#000; border-radius: 12px; }
figcaption { color: var(--muted); margin-top: .5rem; }
audio { width: 100%; max-width: 30rem; }
```

Project 893 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - Video tour</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Take a tour of Cleopatra Beauty Salon	The main heading; only one per page.
<figure class="video">	Self-contained media with an optional caption.
<video controls preload="metadata" poster="images/poster.jpg" width...	Video player; controls shows the built-in buttons.
<source src="media/tour.webm" type="video/webm">	One media source with its MIME type.
<track kind="captions" src="media/tour.en.vtt" srclang="en" label="...	Captions or subtitles file for media.

Line	What it does
<track kind="captions" src="media/tour.ar.vtt" srclang="ar" label="...	A table row.
Your browser cannot play this video. <a href="media/tour.mp4">Do...	A paragraph of text.
<figcaption>A two-minute walk through our Dokki location with Maria...	Caption for the figure.
Listen to our story	Second-level heading for a section.
<audio controls preload="none" src="media/story.mp3"></audio>	Audio player.
Read the transcript	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 16 / 9;	Keeps a fixed width-to-height ratio, reserving space before media loads.
background: #000;	Background colour or image.
border-radius: 12px;	Rounds the corners.

Check your work

- Captions toggle appears in the player
- Video never wider than container
- Fallback link present
- Audio has a transcript

Exercises

1. Add chapters with kind="chapters".
2. Add a custom play button overlay.
3. Lazy-load the video with loading="lazy" on an iframe embed instead.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 894: Video and audio page for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 2 | Files: index.html, styles.css

Brief

Embed a video with two source formats, poster image, English and Arabic caption tracks and a fallback link, plus an audio player with a transcript link.

Learning goals

- Provide multiple sources and captions
- Use preload and poster sensibly
- Keep media responsive with aspect-ratio

Elements and CSS used

HTML elements	CSS features
figure, video, source, track, p, a, figcaption, audio	aspect-ratio: 16 / 9, width: 100%, background, border-radius, max-width

Build guide

1. Write the video with controls, poster and dimensions.
2. Add WebM then MP4 sources.
3. Add caption tracks; mark one default.
4. Add fallback content inside the video.
5. Add the audio element and transcript link.
6. Make the video fluid.

Project 894: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - Video tour</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Take a tour of Suez Auto Service</h1>
    <figure class="video">
      <video controls preload="metadata" poster="images/poster.jpg"
width="1280" height="720">
        <source src="media/tour.webm" type="video/webm">
        <source src="media/tour.mp4" type="video/mp4">
        <track kind="captions" src="media/tour.en.vtt" srclang="en"
label="English" default>
        <track kind="captions" src="media/tour.ar.vtt" srclang="ar"
label="Arabic">
        <p>Your browser cannot play this video. <a href="media/tour.
mp4">Download it</a> instead.</p>
      </video>
      <figcaption>A two-minute walk through our Suez location with
Khaled Nasser.</figcaption>
    </figure>
    <h2>Listen to our story</h2>
    <audio controls preload="none" src="media/story.mp3"></audio>
    <p><a href="media/story-transcript.html">Read the transcript</a></
p>
  </main>
</body>
</html>
```

Project 894: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.video { margin: 0; }
video { width: 100%; height: auto; aspect-ratio: 16 / 9; background:
#000; border-radius: 12px; }
figcaption { color: var(--muted); margin-top: .5rem; }
audio { width: 100%; max-width: 30rem; }
```

Project 894 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - Video tour</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Take a tour of Suez Auto Service	The main heading; only one per page.
<figure class="video">	Self-contained media with an optional caption.
<video controls preload="metadata" poster="images/poster.jpg" width...	Video player; controls shows the built-in buttons.
<source src="media/tour.webm" type="video/webm">	One media source with its MIME type.
<track kind="captions" src="media/tour.en.vtt" srclang="en" label="...	Captions or subtitles file for media.

Line	What it does
<track kind="captions" src="media/tour.ar.vtt" srclang="ar" label="...	A table row.
Your browser cannot play this video. <a href="media/tour.mp4">Do...	A paragraph of text.
<figcaption>A two-minute walk through our Suez location with Khaled...	Caption for the figure.
Listen to our story	Second-level heading for a section.
<audio controls preload="none" src="media/story.mp3"></audio>	Audio player.
Read the transcript	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 16 / 9;	Keeps a fixed width-to-height ratio, reserving space before media loads.
background: #000;	Background colour or image.
border-radius: 12px;	Rounds the corners.

Check your work

- Captions toggle appears in the player
- Video never wider than container
- Fallback link present
- Audio has a transcript

Exercises

1. Add chapters with kind="chapters".
2. Add a custom play button overlay.
3. Lazy-load the video with loading="lazy" on an iframe embed instead.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 895: Video and audio page for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 2 | Files: index.html, styles.css

Brief

Embed a video with two source formats, poster image, English and Arabic caption tracks and a fallback link, plus an audio player with a transcript link.

Learning goals

- Provide multiple sources and captions
- Use preload and poster sensibly
- Keep media responsive with aspect-ratio

Elements and CSS used

HTML elements	CSS features
figure, video, source, track, p, a, figcaption, audio	aspect-ratio: 16 / 9, width: 100%, background, border-radius, max-width

Build guide

1. Write the video with controls, poster and dimensions.
2. Add WebM then MP4 sources.
3. Add caption tracks; mark one default.
4. Add fallback content inside the video.
5. Add the audio element and transcript link.
6. Make the video fluid.

Project 895: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - Video tour</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Take a tour of Luxor Music Academy</h1>
    <figure class="video">
      <video controls preload="metadata" poster="images/poster.jpg"
width="1280" height="720">
        <source src="media/tour.webm" type="video/webm">
        <source src="media/tour.mp4" type="video/mp4">
        <track kind="captions" src="media/tour.en.vtt" srclang="en"
label="English" default>
        <track kind="captions" src="media/tour.ar.vtt" srclang="ar"
label="Arabic">
        <p>Your browser cannot play this video. <a href="media/tour.
mp4">Download it</a> instead.</p>
      </video>
      <figcaption>A two-minute walk through our Luxor location with
Salma Ragab.</figcaption>
    </figure>
    <h2>Listen to our story</h2>
    <audio controls preload="none" src="media/story.mp3"></audio>
    <p><a href="media/story-transcript.html">Read the transcript</a></
p>
  </main>
</body>
</html>
```

Project 895: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.video { margin: 0; }
video { width: 100%; height: auto; aspect-ratio: 16 / 9; background:
#000; border-radius: 12px; }
figcaption { color: var(--muted); margin-top: .5rem; }
audio { width: 100%; max-width: 30rem; }
```

Project 895 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - Video tour</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Take a tour of Luxor Music Academy	The main heading; only one per page.
<figure class="video">	Self-contained media with an optional caption.
<video controls preload="metadata" poster="images/poster.jpg" width...	Video player; controls shows the built-in buttons.
<source src="media/tour.webm" type="video/webm">	One media source with its MIME type.
<track kind="captions" src="media/tour.en.vtt" srclang="en" label="...	Captions or subtitles file for media.

Line	What it does
<track kind="captions" src="media/tour.ar.vtt" srclang="ar" label="...	A table row.
Your browser cannot play this video. <a href="media/tour.mp4">Do...	A paragraph of text.
<figcaption>A two-minute walk through our Luxor location with Salma...	Caption for the figure.
Listen to our story	Second-level heading for a section.
<audio controls preload="none" src="media/story.mp3"></audio>	Audio player.
Read the transcript	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 16 / 9;	Keeps a fixed width-to-height ratio, reserving space before media loads.
background: #000;	Background colour or image.
border-radius: 12px;	Rounds the corners.

Check your work

- Captions toggle appears in the player
- Video never wider than container
- Fallback link present
- Audio has a transcript

Exercises

1. Add chapters with kind="chapters".
2. Add a custom play button overlay.
3. Lazy-load the video with loading="lazy" on an iframe embed instead.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 896: Video and audio page for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 2 | Files: index.html, styles.css

Brief

Embed a video with two source formats, poster image, English and Arabic caption tracks and a fallback link, plus an audio player with a transcript link.

Learning goals

- Provide multiple sources and captions
- Use preload and poster sensibly
- Keep media responsive with aspect-ratio

Elements and CSS used

HTML elements	CSS features
figure, video, source, track, p, a, figcaption, audio	aspect-ratio: 16 / 9, width: 100%, background, border-radius, max-width

Build guide

1. Write the video with controls, poster and dimensions.
2. Add WebM then MP4 sources.
3. Add caption tracks; mark one default.
4. Add fallback content inside the video.
5. Add the audio element and transcript link.
6. Make the video fluid.

Project 896: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - Video tour</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Take a tour of Port Said Seafood</h1>
    <figure class="video">
      <video controls preload="metadata" poster="images/poster.jpg"
width="1280" height="720">
        <source src="media/tour.webm" type="video/webm">
        <source src="media/tour.mp4" type="video/mp4">
        <track kind="captions" src="media/tour.en.vtt" srclang="en"
label="English" default>
        <track kind="captions" src="media/tour.ar.vtt" srclang="ar"
label="Arabic">
        <p>Your browser cannot play this video. <a href="media/tour.
mp4">Download it</a> instead.</p>
      </video>
      <figcaption>A two-minute walk through our Port Said location
with Sherif Wahba.</figcaption>
    </figure>
    <h2>Listen to our story</h2>
    <audio controls preload="none" src="media/story.mp3"></audio>
    <p><a href="media/story-transcript.html">Read the transcript</a></
p>
  </main>
</body>
</html>
```

Project 896: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.video { margin: 0; }
video { width: 100%; height: auto; aspect-ratio: 16 / 9; background:
#000; border-radius: 12px; }
figcaption { color: var(--muted); margin-top: .5rem; }
audio { width: 100%; max-width: 30rem; }
```

Project 896 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - Video tour</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Take a tour of Port Said Seafood	The main heading; only one per page.
<figure class="video">	Self-contained media with an optional caption.
<video controls preload="metadata" poster="images/poster.jpg" width...	Video player; controls shows the built-in buttons.
<source src="media/tour.webm" type="video/webm">	One media source with its MIME type.
<track kind="captions" src="media/tour.en.vtt" srclang="en" label="...	Captions or subtitles file for media.

Line	What it does
<track kind="captions" src="media/tour.ar.vtt" srclang="ar" label="...	A table row.
Your browser cannot play this video. <a href="media/tour.mp4">Do...	A paragraph of text.
<figcaption>A two-minute walk through our Port Said location with S...	Caption for the figure.
Listen to our story	Second-level heading for a section.
<audio controls preload="none" src="media/story.mp3"></audio>	Audio player.
Read the transcript	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 16 / 9;	Keeps a fixed width-to-height ratio, reserving space before media loads.
background: #000;	Background colour or image.
border-radius: 12px;	Rounds the corners.

Check your work

- Captions toggle appears in the player
- Video never wider than container
- Fallback link present
- Audio has a transcript

Exercises

1. Add chapters with kind="chapters".
2. Add a custom play button overlay.
3. Lazy-load the video with loading="lazy" on an iframe embed instead.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 897: Video and audio page for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 2 | Files: index.html, styles.css

Brief

Embed a video with two source formats, poster image, English and Arabic caption tracks and a fallback link, plus an audio player with a transcript link.

Learning goals

- Provide multiple sources and captions
- Use preload and poster sensibly
- Keep media responsive with aspect-ratio

Elements and CSS used

HTML elements	CSS features
figure, video, source, track, p, a, figcaption, audio	aspect-ratio: 16 / 9, width: 100%, background, border-radius, max-width

Build guide

1. Write the video with controls, poster and dimensions.
2. Add WebM then MP4 sources.
3. Add caption tracks; mark one default.
4. Add fallback content inside the video.
5. Add the audio element and transcript link.
6. Make the video fluid.

Project 897: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - Video tour</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Take a tour of Delta Kids Library</h1>
    <figure class="video">
      <video controls preload="metadata" poster="images/poster.jpg"
width="1280" height="720">
        <source src="media/tour.webm" type="video/webm">
        <source src="media/tour.mp4" type="video/mp4">
        <track kind="captions" src="media/tour.en.vtt" srclang="en"
label="English" default>
        <track kind="captions" src="media/tour.ar.vtt" srclang="ar"
label="Arabic">
        <p>Your browser cannot play this video. <a href="media/tour.
mp4">Download it</a> instead.</p>
      </video>
      <figcaption>A two-minute walk through our Tanta location with
Ghada Kamel.</figcaption>
    </figure>
    <h2>Listen to our story</h2>
    <audio controls preload="none" src="media/story.mp3"></audio>
    <p><a href="media/story-transcript.html">Read the transcript</a></
p>
  </main>
</body>
</html>
```

Project 897: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.video { margin: 0; }
video { width: 100%; height: auto; aspect-ratio: 16 / 9; background:
#000; border-radius: 12px; }
figcaption { color: var(--muted); margin-top: .5rem; }
audio { width: 100%; max-width: 30rem; }
```

Project 897 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - Video tour</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Take a tour of Delta Kids Library	The main heading; only one per page.
<figure class="video">	Self-contained media with an optional caption.
<video controls preload="metadata" poster="images/poster.jpg" width...	Video player; controls shows the built-in buttons.
<source src="media/tour.webm" type="video/webm">	One media source with its MIME type.
<track kind="captions" src="media/tour.en.vtt" srclang="en" label="...	Captions or subtitles file for media.

Line	What it does
<track kind="captions" src="media/tour.ar.vtt" srclang="ar" label="...	A table row.
Your browser cannot play this video. <a href="media/tour.mp4">Do...	A paragraph of text.
<figcaption>A two-minute walk through our Tanta location with Ghada...	Caption for the figure.
Listen to our story	Second-level heading for a section.
<audio controls preload="none" src="media/story.mp3"></audio>	Audio player.
Read the transcript	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 16 / 9;	Keeps a fixed width-to-height ratio, reserving space before media loads.
background: #000;	Background colour or image.
border-radius: 12px;	Rounds the corners.

Check your work

- Captions toggle appears in the player
- Video never wider than container
- Fallback link present
- Audio has a transcript

Exercises

1. Add chapters with kind="chapters".
2. Add a custom play button overlay.
3. Lazy-load the video with loading="lazy" on an iframe embed instead.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 898: Video and audio page for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Embed a video with two source formats, poster image, English and Arabic caption tracks and a fallback link, plus an audio player with a transcript link.

Learning goals

- Provide multiple sources and captions
- Use preload and poster sensibly
- Keep media responsive with aspect-ratio

Elements and CSS used

HTML elements	CSS features
figure, video, source, track, p, a, figcaption, audio	aspect-ratio: 16 / 9, width: 100%, background, border-radius, max-width

Build guide

1. Write the video with controls, poster and dimensions.
2. Add WebM then MP4 sources.
3. Add caption tracks; mark one default.
4. Add fallback content inside the video.
5. Add the audio element and transcript link.
6. Make the video fluid.

Project 898: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - Video tour</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Take a tour of Nubian Guest House</h1>
    <figure class="video">
      <video controls preload="metadata" poster="images/poster.jpg"
width="1280" height="720">
        <source src="media/tour.webm" type="video/webm">
        <source src="media/tour.mp4" type="video/mp4">
        <track kind="captions" src="media/tour.en.vtt" srclang="en"
label="English" default>
        <track kind="captions" src="media/tour.ar.vtt" srclang="ar"
label="Arabic">
        <p>Your browser cannot play this video. <a href="media/tour.
mp4">Download it</a> instead.</p>
      </video>
      <figcaption>A two-minute walk through our Aswan location with
Fatma Hassan.</figcaption>
    </figure>
    <h2>Listen to our story</h2>
    <audio controls preload="none" src="media/story.mp3"></audio>
    <p><a href="media/story-transcript.html">Read the transcript</a></
p>
  </main>
</body>
</html>
```

Project 898: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.video { margin: 0; }
video { width: 100%; height: auto; aspect-ratio: 16 / 9; background:
#000; border-radius: 12px; }
figcaption { color: var(--muted); margin-top: .5rem; }
audio { width: 100%; max-width: 30rem; }
```

Project 898 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - Video tour</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Take a tour of Nubian Guest House	The main heading; only one per page.
<figure class="video">	Self-contained media with an optional caption.
<video controls preload="metadata" poster="images/poster.jpg" width...	Video player; controls shows the built-in buttons.
<source src="media/tour.webm" type="video/webm">	One media source with its MIME type.
<track kind="captions" src="media/tour.en.vtt" srclang="en" label="...	Captions or subtitles file for media.

Line	What it does
<track kind="captions" src="media/tour.ar.vtt" srclang="ar" label="...	A table row.
Your browser cannot play this video. <a href="media/tour.mp4">Do...	A paragraph of text.
<figcaption>A two-minute walk through our Aswan location with Fatma...	Caption for the figure.
Listen to our story	Second-level heading for a section.
<audio controls preload="none" src="media/story.mp3"></audio>	Audio player.
Read the transcript	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 16 / 9;	Keeps a fixed width-to-height ratio, reserving space before media loads.
background: #000;	Background colour or image.
border-radius: 12px;	Rounds the corners.

Check your work

- Captions toggle appears in the player
- Video never wider than container
- Fallback link present
- Audio has a transcript

Exercises

1. Add chapters with kind="chapters".
2. Add a custom play button overlay.
3. Lazy-load the video with loading="lazy" on an iframe embed instead.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 899: Video and audio page for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 2 | Files: index.html, styles.css

Brief

Embed a video with two source formats, poster image, English and Arabic caption tracks and a fallback link, plus an audio player with a transcript link.

Learning goals

- Provide multiple sources and captions
- Use preload and poster sensibly
- Keep media responsive with aspect-ratio

Elements and CSS used

HTML elements	CSS features
figure, video, source, track, p, a, figcaption, audio	aspect-ratio: 16 / 9, width: 100%, background, border-radius, max-width

Build guide

1. Write the video with controls, poster and dimensions.
2. Add WebM then MP4 sources.
3. Add caption tracks; mark one default.
4. Add fallback content inside the video.
5. Add the audio element and transcript link.
6. Make the video fluid.

Project 899: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - Video tour</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Take a tour of Ismailia Cycling Store</h1>
    <figure class="video">
      <video controls preload="metadata" poster="images/poster.jpg"
width="1280" height="720">
        <source src="media/tour.webm" type="video/webm">
        <source src="media/tour.mp4" type="video/mp4">
        <track kind="captions" src="media/tour.en.vtt" srclang="en"
label="English" default>
        <track kind="captions" src="media/tour.ar.vtt" srclang="ar"
label="Arabic">
        <p>Your browser cannot play this video. <a href="media/tour.
mp4">Download it</a> instead.</p>
      </video>
      <figcaption>A two-minute walk through our Ismailia location
with Bassem Adly.</figcaption>
    </figure>
    <h2>Listen to our story</h2>
    <audio controls preload="none" src="media/story.mp3"></audio>
    <p><a href="media/story-transcript.html">Read the transcript</a></
p>
  </main>
</body>
</html>
```

Project 899: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.video { margin: 0; }
video { width: 100%; height: auto; aspect-ratio: 16 / 9; background:
#000; border-radius: 12px; }
figcaption { color: var(--muted); margin-top: .5rem; }
audio { width: 100%; max-width: 30rem; }
```

Project 899 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - Video tour</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Take a tour of Ismailia Cycling Store	The main heading; only one per page.
<figure class="video">	Self-contained media with an optional caption.
<video controls preload="metadata" poster="images/poster.jpg" width...	Video player; controls shows the built-in buttons.
<source src="media/tour.webm" type="video/webm">	One media source with its MIME type.
<track kind="captions" src="media/tour.en.vtt" srclang="en" label="...	Captions or subtitles file for media.

Line	What it does
<track kind="captions" src="media/tour.ar.vtt" srclang="ar" label="...	A table row.
Your browser cannot play this video. <a href="media/tour.mp4">Do...	A paragraph of text.
<figcaption>A two-minute walk through our Ismailia location with Ba...	Caption for the figure.
Listen to our story	Second-level heading for a section.
<audio controls preload="none" src="media/story.mp3"></audio>	Audio player.
Read the transcript	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 16 / 9;	Keeps a fixed width-to-height ratio, reserving space before media loads.
background: #000;	Background colour or image.
border-radius: 12px;	Rounds the corners.

Check your work

- Captions toggle appears in the player
- Video never wider than container
- Fallback link present
- Audio has a transcript

Exercises

1. Add chapters with kind="chapters".
2. Add a custom play button overlay.
3. Lazy-load the video with loading="lazy" on an iframe embed instead.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 900: Video and audio page for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 2 | Files: index.html, styles.css

Brief

Embed a video with two source formats, poster image, English and Arabic caption tracks and a fallback link, plus an audio player with a transcript link.

Learning goals

- Provide multiple sources and captions
- Use preload and poster sensibly
- Keep media responsive with aspect-ratio

Elements and CSS used

HTML elements	CSS features
figure, video, source, track, p, a, figcaption, audio	aspect-ratio: 16 / 9, width: 100%, background, border-radius, max-width

Build guide

1. Write the video with controls, poster and dimensions.
2. Add WebM then MP4 sources.
3. Add caption tracks; mark one default.
4. Add fallback content inside the video.
5. Add the audio element and transcript link.
6. Make the video fluid.

Project 900: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - Video tour</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Take a tour of Minya Coding Club</h1>
    <figure class="video">
      <video controls preload="metadata" poster="images/poster.jpg"
width="1280" height="720">
        <source src="media/tour.webm" type="video/webm">
        <source src="media/tour.mp4" type="video/mp4">
        <track kind="captions" src="media/tour.en.vtt" srclang="en"
label="English" default>
        <track kind="captions" src="media/tour.ar.vtt" srclang="ar"
label="Arabic">
        <p>Your browser cannot play this video. <a href="media/tour.
mp4">Download it</a> instead.</p>
      </video>
      <figcaption>A two-minute walk through our Minya location with
Youssef Hany.</figcaption>
    </figure>
    <h2>Listen to our story</h2>
    <audio controls preload="none" src="media/story.mp3"></audio>
    <p><a href="media/story-transcript.html">Read the transcript</a></
p>
  </main>
</body>
</html>
```

Project 900: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.video { margin: 0; }
video { width: 100%; height: auto; aspect-ratio: 16 / 9; background:
#000; border-radius: 12px; }
figcaption { color: var(--muted); margin-top: .5rem; }
audio { width: 100%; max-width: 30rem; }
```

Project 900 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - Video tour</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Take a tour of Minya Coding Club	The main heading; only one per page.
<figure class="video">	Self-contained media with an optional caption.
<video controls preload="metadata" poster="images/poster.jpg" width...	Video player; controls shows the built-in buttons.
<source src="media/tour.webm" type="video/webm">	One media source with its MIME type.
<track kind="captions" src="media/tour.en.vtt" srclang="en" label="...	Captions or subtitles file for media.

Line	What it does
<track kind="captions" src="media/tour.ar.vtt" srclang="ar" label="...	A table row.
Your browser cannot play this video. <a href="media/tour.mp4">Do...	A paragraph of text.
<figcaption>A two-minute walk through our Minya location with Youss...	Caption for the figure.
Listen to our story	Second-level heading for a section.
<audio controls preload="none" src="media/story.mp3"></audio>	Audio player.
Read the transcript	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.

Declaration	What it does
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 16 / 9;	Keeps a fixed width-to-height ratio, reserving space before media loads.
background: #000;	Background colour or image.
border-radius: 12px;	Rounds the corners.

Check your work

- Captions toggle appears in the player
- Video never wider than container
- Fallback link present
- Audio has a transcript

Exercises

1. Add chapters with kind="chapters".
2. Add a custom play button overlay.
3. Lazy-load the video with loading="lazy" on an iframe embed instead.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Product grid with clickable cards

Level 2 | 25 projects, one per theme

List all offers as equal-height cards where the whole card is clickable via a stretched link pseudo-element and the price sticks to the bottom.

Project 901: Product grid with clickable cards for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 2 | Files: index.html, styles.css

Brief

List all offers as equal-height cards where the whole card is clickable via a stretched link pseudo-element and the price sticks to the bottom.

Learning goals

- Make a whole card clickable accessibly (one link, stretched)
- Push an element to the bottom with margin-top: auto
- Lift cards on hover

Elements and CSS used

HTML elements	CSS features
article, img, div, h2, a, p	position: relative + ::after inset: 0, flex-direction: column, margin-top: auto, transition, translate

Build guide

1. Write one article per offer with image, heading link, text and price.
2. Grid with auto-fill.
3. Make card and body flex columns; body flex: 1.
4. Push price down with margin-top: auto.
5. Stretch the heading link over the card with ::after and inset: 0.

6. Add the hover lift.

Project 901: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - All books</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>All books</h1>
    <div class="grid">
      <article class="card">
        <img src="images/bookshop-1.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Learn HTML</a></h2>
          <p>From your first tag to a complete page.</p>
          <p class="price">120 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/bookshop-2.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">CSS in Practice</a></h2>
          <p>Layouts, colours and typography.</p>
          <p class="price">150 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/bookshop-3.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">JavaScript Basics</a></h2>
          <p>Make pages interactive.</p>
          <p class="price">180 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/bookshop-4.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Web Accessibility</a></h2>
          <p>Pages everyone can use.</p>
          <p class="price">95 EGP</p>
        </div>
```

```
      </article>
    </div>
  </main>
</body>
</html>
```

Project 901: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 70rem; margin: 2rem auto; padding: 0 1rem; }
.grid { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fill, minmax(15rem, 1fr)); }
.card { display: flex; flex-direction: column; border: 1px solid var(-
-line); border-radius: 14px; overflow: hidden; background: #fff;
position: relative; transition: box-shadow .2s, translate .2s; }
.card:hover { box-shadow: 0 12px 30px rgb(0 0 0 / 12%); translate: 0 -
3px; }
.card img { width: 100%; height: auto; aspect-ratio: 3 / 2; object-
fit: cover; }
.body { padding: 1rem 1.25rem; display: flex; flex-direction: column;
flex: 1; }
h2 { font-size: 1.1rem; margin: 0 0 .3rem; }
h2 a { color: inherit; text-decoration: none; }
h2 a::after { content: ""; position: absolute; inset: 0; }   /* whole
card clickable */
.body p { margin: 0 0 .5rem; color: var(--muted); }
.price { margin-top: auto !important; color: var(--brand); font-
weight: 700; }
```

Project 901 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - All books</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
All books	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/bookshop-1.jpg" alt="" width="600" height="400">	An image; alt describes it, width and height reserve space before it loads.
Learn HTML	Second-level heading for a section.
From your first tag to a complete page.	A paragraph of text.

Line	What it does
CSS in Practice	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 70rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(15rem, 1fr));	Defines the columns of the grid.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 14px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
background: #fff;	Background colour or image.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
transition: box-shadow .2s, translate .2s;	Soft shadow that lifts the element from the page.
.card:hover {	Applies while the pointer is over the element.
translate: 0 -3px;	Moves the element without affecting the layout of others.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
flex: 1;	All items share free space equally.
font-size: 1.1rem;	Size of the text.
text-decoration: none;	Removes the underline from links.

Declaration	What it does
h2 a::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
inset: 0;	Shorthand for top, right, bottom and left all zero: stretches over the parent.
font-weight: 700;	Thickness of the text.

Check your work

- Only one link per card (screen readers)
- Cards equal height in a row
- Price aligned at bottom
- Hover does not shift layout

Exercises

1. Add a filter bar with radio buttons and :has().
2. Add a 'new' badge.
3. Add a sort dropdown with JavaScript.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000

Field	Value
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 902: Product grid with clickable cards for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 2 | Files: index.html, styles.css

Brief

List all offers as equal-height cards where the whole card is clickable via a stretched link pseudo-element and the price sticks to the bottom.

Learning goals

- Make a whole card clickable accessibly (one link, stretched)
- Push an element to the bottom with margin-top: auto
- Lift cards on hover

Elements and CSS used

HTML elements	CSS features
article, img, div, h2, a, p	position: relative + ::after inset: 0, flex-direction: column, margin-top: auto, transition, translate

Build guide

1. Write one article per offer with image, heading link, text and price.
2. Grid with auto-fill.
3. Make card and body flex columns; body flex: 1.
4. Push price down with margin-top: auto.
5. Stretch the heading link over the card with ::after and inset: 0.
6. Add the hover lift.

Project 902: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - All pastries</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>All pastries</h1>
    <div class="grid">
      <article class="card">
        <img src="images/bakery-1.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Sourdough loaf</a></h2>
          <p>Slow fermented, crisp crust.</p>
          <p class="price">60 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/bakery-2.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Croissant</a></h2>
          <p>Butter, 27 layers.</p>
          <p class="price">35 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/bakery-3.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Date cookies</a></h2>
          <p>Traditional maamoul style.</p>
          <p class="price">80 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/bakery-4.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Baklava box</a></h2>
          <p>Pistachio and honey.</p>
          <p class="price">220 EGP</p>
        </div>
```

```
      </article>
    </div>
  </main>
</body>
</html>
```

Project 902: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 70rem; margin: 2rem auto; padding: 0 1rem; }
.grid { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fill, minmax(15rem, 1fr)); }
.card { display: flex; flex-direction: column; border: 1px solid var(-
-line); border-radius: 14px; overflow: hidden; background: #fff;
position: relative; transition: box-shadow .2s, translate .2s; }
.card:hover { box-shadow: 0 12px 30px rgb(0 0 0 / 12%); translate: 0 -
3px; }
.card img { width: 100%; height: auto; aspect-ratio: 3 / 2; object-
fit: cover; }
.body { padding: 1rem 1.25rem; display: flex; flex-direction: column;
flex: 1; }
h2 { font-size: 1.1rem; margin: 0 0 .3rem; }
h2 a { color: inherit; text-decoration: none; }
h2 a::after { content: ""; position: absolute; inset: 0; }   /* whole
card clickable */
.body p { margin: 0 0 .5rem; color: var(--muted); }
.price { margin-top: auto !important; color: var(--brand); font-
weight: 700; }
```

Project 902 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - All pastries</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
All pastries	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/bakery-1.jpg" alt="" width="600" height="400">	An image; alt describes it, width and height reserve space before it loads.
Sourdough loaf	Second-level heading for a section.
Slow fermented, crisp crust.	A paragraph of text.

Line	What it does
Croissant 	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 70rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(15rem, 1fr));	Defines the columns of the grid.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 14px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
background: #fff;	Background colour or image.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
transition: box-shadow .2s, translate .2s;	Soft shadow that lifts the element from the page.
.card:hover {	Applies while the pointer is over the element.
translate: 0 -3px;	Moves the element without affecting the layout of others.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
flex: 1;	All items share free space equally.
font-size: 1.1rem;	Size of the text.
text-decoration: none;	Removes the underline from links.

Declaration	What it does
h2 a::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
inset: 0;	Shorthand for top, right, bottom and left all zero: stretches over the parent.
font-weight: 700;	Thickness of the text.

Check your work

- Only one link per card (screen readers)
- Cards equal height in a row
- Price aligned at bottom
- Hover does not shift layout

Exercises

1. Add a filter bar with radio buttons and :has().
2. Add a 'new' badge.
3. Add a sort dropdown with JavaScript.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d

Field	Value
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 903: Product grid with clickable cards for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 2 | Files: index.html, styles.css

Brief

List all offers as equal-height cards where the whole card is clickable via a stretched link pseudo-element and the price sticks to the bottom.

Learning goals

- Make a whole card clickable accessibly (one link, stretched)
- Push an element to the bottom with margin-top: auto
- Lift cards on hover

Elements and CSS used

HTML elements	CSS features
article, img, div, h2, a, p	position: relative + ::after inset: 0, flex-direction: column, margin-top: auto, transition, translate

Build guide

1. Write one article per offer with image, heading link, text and price.
2. Grid with auto-fill.
3. Make card and body flex columns; body flex: 1.
4. Push price down with margin-top: auto.
5. Stretch the heading link over the card with ::after and inset: 0.

6. Add the hover lift.

Project 903: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - All classes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>All classes</h1>
    <div class="grid">
      <article class="card">
        <img src="images/gym-1.jpg" alt="" width="600" height="400">
        <div class="body">
          <h2><a href="#">Morning yoga</a></h2>
          <p>Flexibility and calm, 60 minutes.</p>
          <p class="price">100 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/gym-2.jpg" alt="" width="600" height="400">
        <div class="body">
          <h2><a href="#">Strength circuit</a></h2>
          <p>Full body, all levels.</p>
          <p class="price">120 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/gym-3.jpg" alt="" width="600" height="400">
        <div class="body">
          <h2><a href="#">Spinning</a></h2>
          <p>High energy cycling.</p>
          <p class="price">110 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/gym-4.jpg" alt="" width="600" height="400">
        <div class="body">
          <h2><a href="#">Personal training</a></h2>
          <p>One to one coaching.</p>
          <p class="price">350 EGP</p>
        </div>
      </article>
    </div>
  </main>
</body>
```

```
</html>
```

Project 903: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 70rem; margin: 2rem auto; padding: 0 1rem; }
.grid { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fill, minmax(15rem, 1fr)); }
.card { display: flex; flex-direction: column; border: 1px solid var(-
-line); border-radius: 14px; overflow: hidden; background: #fff;
position: relative; transition: box-shadow .2s, translate .2s; }
.card:hover { box-shadow: 0 12px 30px rgb(0 0 0 / 12%); translate: 0 -
3px; }
.card img { width: 100%; height: auto; aspect-ratio: 3 / 2; object-
fit: cover; }
.body { padding: 1rem 1.25rem; display: flex; flex-direction: column;
flex: 1; }
h2 { font-size: 1.1rem; margin: 0 0 .3rem; }
h2 a { color: inherit; text-decoration: none; }
h2 a::after { content: ""; position: absolute; inset: 0; }   /* whole
card clickable */
.body p { margin: 0 0 .5rem; color: var(--muted); }
.price { margin-top: auto !important; color: var(--brand); font-
weight: 700; }
```

Project 903 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - All classes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
All classes	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/gym-1.jpg" alt="" width="600" height="400">	An image; alt describes it, width and height reserve space before it loads.
Morning yoga	Second-level heading for a section.
Flexibility and calm, 60 minutes.	A paragraph of text.
Strength circuit	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 70rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(15rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.

Declaration	What it does
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 14px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
background: #fff;	Background colour or image.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
transition: box-shadow .2s, translate .2s;	Soft shadow that lifts the element from the page.
.card:hover {	Applies while the pointer is over the element.
translate: 0 -3px;	Moves the element without affecting the layout of others.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
flex: 1;	All items share free space equally.
font-size: 1.1rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
h2 a::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
inset: 0;	Shorthand for top, right, bottom and left all zero: stretches over the parent.
font-weight: 700;	Thickness of the text.

Check your work

- Only one link per card (screen readers)
- Cards equal height in a row
- Price aligned at bottom
- Hover does not shift layout

Exercises

1. Add a filter bar with radio buttons and :has().
2. Add a 'new' badge.
3. Add a sort dropdown with JavaScript.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 904: Product grid with clickable cards for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 2 | Files: index.html, styles.css

Brief

List all offers as equal-height cards where the whole card is clickable via a stretched link pseudo-element and the price sticks to the bottom.

Learning goals

- Make a whole card clickable accessibly (one link, stretched)
- Push an element to the bottom with margin-top: auto
- Lift cards on hover

Elements and CSS used

HTML elements	CSS features
article, img, div, h2, a, p	position: relative + ::after inset: 0, flex-direction: column, margin-top: auto, transition, translate

Build guide

1. Write one article per offer with image, heading link, text and price.
2. Grid with auto-fill.
3. Make card and body flex columns; body flex: 1.
4. Push price down with margin-top: auto.
5. Stretch the heading link over the card with ::after and inset: 0.

6. Add the hover lift.

Project 904: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - All services</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>All services</h1>
    <div class="grid">
      <article class="card">
        <img src="images/clinic-1.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Check-up</a></h2>
          <p>Examination and cleaning.</p>
          <p class="price">300 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/clinic-2.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Whitening</a></h2>
          <p>Brighter smile in one visit.</p>
          <p class="price">1500 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/clinic-3.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Filling</a></h2>
          <p>Tooth-coloured composite.</p>
          <p class="price">600 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/clinic-4.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Braces consultation</a></h2>
          <p>Plan your treatment.</p>
          <p class="price">Free</p>
        </div>
```

```
      </article>
    </div>
  </main>
</body>
</html>
```

Project 904: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 70rem; margin: 2rem auto; padding: 0 1rem; }
.grid { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fill, minmax(15rem, 1fr)); }
.card { display: flex; flex-direction: column; border: 1px solid var(-
-line); border-radius: 14px; overflow: hidden; background: #fff;
position: relative; transition: box-shadow .2s, translate .2s; }
.card:hover { box-shadow: 0 12px 30px rgb(0 0 0 / 12%); translate: 0 -
3px; }
.card img { width: 100%; height: auto; aspect-ratio: 3 / 2; object-
fit: cover; }
.body { padding: 1rem 1.25rem; display: flex; flex-direction: column;
flex: 1; }
h2 { font-size: 1.1rem; margin: 0 0 .3rem; }
h2 a { color: inherit; text-decoration: none; }
h2 a::after { content: ""; position: absolute; inset: 0; }   /* whole
card clickable */
.body p { margin: 0 0 .5rem; color: var(--muted); }
.price { margin-top: auto !important; color: var(--brand); font-
weight: 700; }
```

Project 904 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - All services</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
All services	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/clinic-1.jpg" alt="" width="600" height="400">	An image; alt describes it, width and height reserve space before it loads.
Check-up 	Second-level heading for a section.
Examination and cleaning.	A paragraph of text.

Line	What it does
Whitening 	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 70rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(15rem, 1fr));	Defines the columns of the grid.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 14px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
background: #fff;	Background colour or image.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
transition: box-shadow .2s, translate .2s;	Soft shadow that lifts the element from the page.
.card:hover {	Applies while the pointer is over the element.
translate: 0 -3px;	Moves the element without affecting the layout of others.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
flex: 1;	All items share free space equally.
font-size: 1.1rem;	Size of the text.
text-decoration: none;	Removes the underline from links.

Declaration	What it does
h2 a::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
inset: 0;	Shorthand for top, right, bottom and left all zero: stretches over the parent.
font-weight: 700;	Thickness of the text.

Check your work

- Only one link per card (screen readers)
- Cards equal height in a row
- Price aligned at bottom
- Hover does not shift layout

Exercises

1. Add a filter bar with radio buttons and :has().
2. Add a 'new' badge.
3. Add a sort dropdown with JavaScript.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8

Field	Value
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 905: Product grid with clickable cards for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 2 | Files: index.html, styles.css

Brief

List all offers as equal-height cards where the whole card is clickable via a stretched link pseudo-element and the price sticks to the bottom.

Learning goals

- Make a whole card clickable accessibly (one link, stretched)
- Push an element to the bottom with margin-top: auto
- Lift cards on hover

Elements and CSS used

HTML elements	CSS features
article, img, div, h2, a, p	position: relative + ::after inset: 0, flex-direction: column, margin-top: auto, transition, translate

Build guide

1. Write one article per offer with image, heading link, text and price.
2. Grid with auto-fill.
3. Make card and body flex columns; body flex: 1.
4. Push price down with margin-top: auto.
5. Stretch the heading link over the card with ::after and inset: 0.

6. Add the hover lift.

Project 905: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - All tours</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>All tours</h1>
    <div class="grid">
      <article class="card">
        <img src="images/travel-1.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Luxor day trip</a></h2>
          <p>Karnak, Valley of the Kings.</p>
          <p class="price">1200 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/travel-2.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Snorkelling</a></h2>
          <p>Giftun island reefs.</p>
          <p class="price">700 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/travel-3.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Desert safari</a></h2>
          <p>Quad bikes and Bedouin dinner.</p>
          <p class="price">900 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/travel-4.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Nile cruise</a></h2>
          <p>Three nights Aswan to Luxor.</p>
          <p class="price">6500 EGP</p>
        </div>
```

```
      </article>
    </div>
  </main>
</body>
</html>
```

Project 905: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 70rem; margin: 2rem auto; padding: 0 1rem; }
.grid { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fill, minmax(15rem, 1fr)); }
.card { display: flex; flex-direction: column; border: 1px solid var(-
-line); border-radius: 14px; overflow: hidden; background: #fff;
position: relative; transition: box-shadow .2s, translate .2s; }
.card:hover { box-shadow: 0 12px 30px rgb(0 0 0 / 12%); translate: 0 -
3px; }
.card img { width: 100%; height: auto; aspect-ratio: 3 / 2; object-
fit: cover; }
.body { padding: 1rem 1.25rem; display: flex; flex-direction: column;
flex: 1; }
h2 { font-size: 1.1rem; margin: 0 0 .3rem; }
h2 a { color: inherit; text-decoration: none; }
h2 a::after { content: ""; position: absolute; inset: 0; }   /* whole
card clickable */
.body p { margin: 0 0 .5rem; color: var(--muted); }
.price { margin-top: auto !important; color: var(--brand); font-
weight: 700; }
```

Project 905 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - All tours</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
All tours	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/travel-1.jpg" alt="" width="600" height="400">	An image; alt describes it, width and height reserve space before it loads.
Luxor day trip	Second-level heading for a section.
Karnak, Valley of the Kings.	A paragraph of text.

Line	What it does
Snorkelling	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 70rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(15rem, 1fr));	Defines the columns of the grid.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 14px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
background: #fff;	Background colour or image.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
transition: box-shadow .2s, translate .2s;	Soft shadow that lifts the element from the page.
.card:hover {	Applies while the pointer is over the element.
translate: 0 -3px;	Moves the element without affecting the layout of others.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
flex: 1;	All items share free space equally.
font-size: 1.1rem;	Size of the text.
text-decoration: none;	Removes the underline from links.

Declaration	What it does
h2 a::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
inset: 0;	Shorthand for top, right, bottom and left all zero: stretches over the parent.
font-weight: 700;	Thickness of the text.

Check your work

- Only one link per card (screen readers)
- Cards equal height in a row
- Price aligned at bottom
- Hover does not shift layout

Exercises

1. Add a filter bar with radio buttons and :has().
2. Add a 'new' badge.
3. Add a sort dropdown with JavaScript.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1

Field	Value
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 906: Product grid with clickable cards for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

List all offers as equal-height cards where the whole card is clickable via a stretched link pseudo-element and the price sticks to the bottom.

Learning goals

- Make a whole card clickable accessibly (one link, stretched)
- Push an element to the bottom with margin-top: auto
- Lift cards on hover

Elements and CSS used

HTML elements	CSS features
article, img, div, h2, a, p	position: relative + ::after inset: 0, flex-direction: column, margin-top: auto, transition, translate

Build guide

1. Write one article per offer with image, heading link, text and price.
2. Grid with auto-fill.
3. Make card and body flex columns; body flex: 1.
4. Push price down with margin-top: auto.
5. Stretch the heading link over the card with ::after and inset: 0.

6. Add the hover lift.

Project 906: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - All courses</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>All courses</h1>
    <div class="grid">
      <article class="card">
        <img src="images/school-1.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">English A1</a></h2>
          <p>Beginner, 8 weeks.</p>
          <p class="price">1800 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/school-2.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">French B1</a></h2>
          <p>Intermediate conversation.</p>
          <p class="price">2200 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/school-3.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">German A2</a></h2>
          <p>Grammar and speaking.</p>
          <p class="price">2000 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/school-4.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">IELTS preparation</a></h2>
          <p>Exam strategies.</p>
          <p class="price">3000 EGP</p>
        </div>
```

```
      </article>
    </div>
  </main>
</body>
</html>
```

Project 906: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 70rem; margin: 2rem auto; padding: 0 1rem; }
.grid { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fill, minmax(15rem, 1fr)); }
.card { display: flex; flex-direction: column; border: 1px solid var(-
-line); border-radius: 14px; overflow: hidden; background: #fff;
position: relative; transition: box-shadow .2s, translate .2s; }
.card:hover { box-shadow: 0 12px 30px rgb(0 0 0 / 12%); translate: 0 -
3px; }
.card img { width: 100%; height: auto; aspect-ratio: 3 / 2; object-
fit: cover; }
.body { padding: 1rem 1.25rem; display: flex; flex-direction: column;
flex: 1; }
h2 { font-size: 1.1rem; margin: 0 0 .3rem; }
h2 a { color: inherit; text-decoration: none; }
h2 a::after { content: ""; position: absolute; inset: 0; }   /* whole
card clickable */
.body p { margin: 0 0 .5rem; color: var(--muted); }
.price { margin-top: auto !important; color: var(--brand); font-
weight: 700; }
```

Project 906 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - All courses</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
All courses	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/school-1.jpg" alt="" width="600" height="400">	An image; alt describes it, width and height reserve space before it loads.
English A1	Second-level heading for a section.
Beginner, 8 weeks.	A paragraph of text.
French B1	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 70rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(15rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.

Declaration	What it does
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 14px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
background: #fff;	Background colour or image.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
transition: box-shadow .2s, translate .2s;	Soft shadow that lifts the element from the page.
.card:hover {	Applies while the pointer is over the element.
translate: 0 -3px;	Moves the element without affecting the layout of others.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
flex: 1;	All items share free space equally.
font-size: 1.1rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
h2 a::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
inset: 0;	Shorthand for top, right, bottom and left all zero: stretches over the parent.
font-weight: 700;	Thickness of the text.

Check your work

- Only one link per card (screen readers)
- Cards equal height in a row
- Price aligned at bottom
- Hover does not shift layout

Exercises

1. Add a filter bar with radio buttons and :has().
2. Add a 'new' badge.
3. Add a sort dropdown with JavaScript.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 907: Product grid with clickable cards for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 2 | Files: index.html, styles.css

Brief

List all offers as equal-height cards where the whole card is clickable via a stretched link pseudo-element and the price sticks to the bottom.

Learning goals

- Make a whole card clickable accessibly (one link, stretched)
- Push an element to the bottom with margin-top: auto
- Lift cards on hover

Elements and CSS used

HTML elements	CSS features
article, img, div, h2, a, p	position: relative + ::after inset: 0, flex-direction: column, margin-top: auto, transition, translate

Build guide

1. Write one article per offer with image, heading link, text and price.
2. Grid with auto-fill.
3. Make card and body flex columns; body flex: 1.
4. Push price down with margin-top: auto.
5. Stretch the heading link over the card with ::after and inset: 0.

6. Add the hover lift.

Project 907: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - All drinks</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>All drinks</h1>
    <div class="grid">
      <article class="card">
        <img src="images/cafe-1.jpg" alt="" width="600" height="400">
        <div class="body">
          <h2><a href="#">Flat white</a></h2>
          <p>Double shot, silky milk.</p>
          <p class="price">55 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/cafe-2.jpg" alt="" width="600" height="400">
        <div class="body">
          <h2><a href="#">Cold brew</a></h2>
          <p>18 hours steeped.</p>
          <p class="price">60 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/cafe-3.jpg" alt="" width="600" height="400">
        <div class="body">
          <h2><a href="#">Hibiscus iced tea</a></h2>
          <p>Karkade with mint.</p>
          <p class="price">40 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/cafe-4.jpg" alt="" width="600" height="400">
        <div class="body">
          <h2><a href="#">Cheesecake</a></h2>
          <p>Baked, with berries.</p>
          <p class="price">75 EGP</p>
        </div>
      </article>
    </div>
  </main>
</body>
```

```
</html>
```

Project 907: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 70rem; margin: 2rem auto; padding: 0 1rem; }
.grid { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fill, minmax(15rem, 1fr)); }
.card { display: flex; flex-direction: column; border: 1px solid var(-
-line); border-radius: 14px; overflow: hidden; background: #fff;
position: relative; transition: box-shadow .2s, translate .2s; }
.card:hover { box-shadow: 0 12px 30px rgb(0 0 0 / 12%); translate: 0 -
3px; }
.card img { width: 100%; height: auto; aspect-ratio: 3 / 2; object-
fit: cover; }
.body { padding: 1rem 1.25rem; display: flex; flex-direction: column;
flex: 1; }
h2 { font-size: 1.1rem; margin: 0 0 .3rem; }
h2 a { color: inherit; text-decoration: none; }
h2 a::after { content: ""; position: absolute; inset: 0; }   /* whole
card clickable */
.body p { margin: 0 0 .5rem; color: var(--muted); }
.price { margin-top: auto !important; color: var(--brand); font-
weight: 700; }
```

Project 907 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - All drinks</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
All drinks	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/cafe-1.jpg" alt="" width="600" height="400">	An image; alt describes it, width and height reserve space before it loads.
Flat white	Second-level heading for a section.
Double shot, silky milk.	A paragraph of text.
Cold brew	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 70rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(15rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.

Declaration	What it does
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 14px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
background: #fff;	Background colour or image.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
transition: box-shadow .2s, translate .2s;	Soft shadow that lifts the element from the page.
.card:hover {	Applies while the pointer is over the element.
translate: 0 -3px;	Moves the element without affecting the layout of others.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
flex: 1;	All items share free space equally.
font-size: 1.1rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
h2 a::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
inset: 0;	Shorthand for top, right, bottom and left all zero: stretches over the parent.
font-weight: 700;	Thickness of the text.

Check your work

- Only one link per card (screen readers)
- Cards equal height in a row
- Price aligned at bottom
- Hover does not shift layout

Exercises

1. Add a filter bar with radio buttons and :has().
2. Add a 'new' badge.
3. Add a sort dropdown with JavaScript.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 908: Product grid with clickable cards for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 2 | Files: index.html, styles.css

Brief

List all offers as equal-height cards where the whole card is clickable via a stretched link pseudo-element and the price sticks to the bottom.

Learning goals

- Make a whole card clickable accessibly (one link, stretched)
- Push an element to the bottom with margin-top: auto
- Lift cards on hover

Elements and CSS used

HTML elements	CSS features
article, img, div, h2, a, p	position: relative + ::after inset: 0, flex-direction: column, margin-top: auto, transition, translate

Build guide

1. Write one article per offer with image, heading link, text and price.
2. Grid with auto-fill.
3. Make card and body flex columns; body flex: 1.
4. Push price down with margin-top: auto.
5. Stretch the heading link over the card with ::after and inset: 0.

6. Add the hover lift.

Project 908: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - All hikes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>All hikes</h1>
    <div class="grid">
      <article class="card">
        <img src="images/trekking-1.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Mount Sinai sunrise</a></h2>
          <p>Night climb, 7 km.</p>
          <p class="price">400 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/trekking-2.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Blue Desert loop</a></h2>
          <p>Easy day walk.</p>
          <p class="price">250 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/trekking-3.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Wadi Gnai</a></h2>
          <p>Palms and pools.</p>
          <p class="price">300 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/trekking-4.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Three-day traverse</a></h2>
          <p>Camping under stars.</p>
          <p class="price">1900 EGP</p>
        </div>
```

```
      </article>
    </div>
  </main>
</body>
</html>
```

Project 908: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 70rem; margin: 2rem auto; padding: 0 1rem; }
.grid { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fill, minmax(15rem, 1fr)); }
.card { display: flex; flex-direction: column; border: 1px solid var(-
-line); border-radius: 14px; overflow: hidden; background: #fff;
position: relative; transition: box-shadow .2s, translate .2s; }
.card:hover { box-shadow: 0 12px 30px rgb(0 0 0 / 12%); translate: 0 -
3px; }
.card img { width: 100%; height: auto; aspect-ratio: 3 / 2; object-
fit: cover; }
.body { padding: 1rem 1.25rem; display: flex; flex-direction: column;
flex: 1; }
h2 { font-size: 1.1rem; margin: 0 0 .3rem; }
h2 a { color: inherit; text-decoration: none; }
h2 a::after { content: ""; position: absolute; inset: 0; }   /* whole
card clickable */
.body p { margin: 0 0 .5rem; color: var(--muted); }
.price { margin-top: auto !important; color: var(--brand); font-
weight: 700; }
```

Project 908 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - All hikes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
All hikes	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/trekking-1.jpg" alt="" width="600" height="400">	An image; alt describes it, width and height reserve space before it loads.
Mount Sinai sunrise	Second-level heading for a section.
Night climb, 7 km.	A paragraph of text.
Blue Desert loop	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 70rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(15rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.

Declaration	What it does
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 14px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
background: #fff;	Background colour or image.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
transition: box-shadow .2s, translate .2s;	Soft shadow that lifts the element from the page.
.card:hover {	Applies while the pointer is over the element.
translate: 0 -3px;	Moves the element without affecting the layout of others.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
flex: 1;	All items share free space equally.
font-size: 1.1rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
h2 a::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
inset: 0;	Shorthand for top, right, bottom and left all zero: stretches over the parent.
font-weight: 700;	Thickness of the text.

Check your work

- Only one link per card (screen readers)
- Cards equal height in a row
- Price aligned at bottom
- Hover does not shift layout

Exercises

1. Add a filter bar with radio buttons and :has().
2. Add a 'new' badge.
3. Add a sort dropdown with JavaScript.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 909: Product grid with clickable cards for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 2 | Files: index.html, styles.css

Brief

List all offers as equal-height cards where the whole card is clickable via a stretched link pseudo-element and the price sticks to the bottom.

Learning goals

- Make a whole card clickable accessibly (one link, stretched)
- Push an element to the bottom with margin-top: auto
- Lift cards on hover

Elements and CSS used

HTML elements	CSS features
article, img, div, h2, a, p	position: relative + ::after inset: 0, flex-direction: column, margin-top: auto, transition, translate

Build guide

1. Write one article per offer with image, heading link, text and price.
2. Grid with auto-fill.
3. Make card and body flex columns; body flex: 1.
4. Push price down with margin-top: auto.
5. Stretch the heading link over the card with ::after and inset: 0.

6. Add the hover lift.

Project 909: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - All sessions</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>All sessions</h1>
    <div class="grid">
      <article class="card">
        <img src="images/photo-1.jpg" alt="" width="600" height="400">
        <div class="body">
          <h2><a href="#">Portrait session</a></h2>
          <p>One hour, 20 edited photos.</p>
          <p class="price">1200 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/photo-2.jpg" alt="" width="600" height="400">
        <div class="body">
          <h2><a href="#">Wedding day</a></h2>
          <p>Full coverage, two photographers.</p>
          <p class="price">15000 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/photo-3.jpg" alt="" width="600" height="400">
        <div class="body">
          <h2><a href="#">Product shoot</a></h2>
          <p>White background, 10 items.</p>
          <p class="price">900 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/photo-4.jpg" alt="" width="600" height="400">
        <div class="body">
          <h2><a href="#">Family session</a></h2>
          <p>Outdoor, golden hour.</p>
          <p class="price">1500 EGP</p>
        </div>
      </article>
    </div>
  </main>
</body>
```

```
</html>
```

Project 909: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 70rem; margin: 2rem auto; padding: 0 1rem; }
.grid { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fill, minmax(15rem, 1fr)); }
.card { display: flex; flex-direction: column; border: 1px solid var(-
-line); border-radius: 14px; overflow: hidden; background: #fff;
position: relative; transition: box-shadow .2s, translate .2s; }
.card:hover { box-shadow: 0 12px 30px rgb(0 0 0 / 12%); translate: 0 -
3px; }
.card img { width: 100%; height: auto; aspect-ratio: 3 / 2; object-
fit: cover; }
.body { padding: 1rem 1.25rem; display: flex; flex-direction: column;
flex: 1; }
h2 { font-size: 1.1rem; margin: 0 0 .3rem; }
h2 a { color: inherit; text-decoration: none; }
h2 a::after { content: ""; position: absolute; inset: 0; }   /* whole
card clickable */
.body p { margin: 0 0 .5rem; color: var(--muted); }
.price { margin-top: auto !important; color: var(--brand); font-
weight: 700; }
```

Project 909 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - All sessions</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
All sessions	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/photo-1.jpg" alt="" width="600" height="400">	An image; alt describes it, width and height reserve space before it loads.
Portrait session	Second-level heading for a section.
One hour, 20 edited photos.	A paragraph of text.

Line	What it does
Wedding day	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 70rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(15rem, 1fr));	Defines the columns of the grid.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 14px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
background: #fff;	Background colour or image.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
transition: box-shadow .2s, translate .2s;	Soft shadow that lifts the element from the page.
.card:hover {	Applies while the pointer is over the element.
translate: 0 -3px;	Moves the element without affecting the layout of others.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
flex: 1;	All items share free space equally.
font-size: 1.1rem;	Size of the text.
text-decoration: none;	Removes the underline from links.

Declaration	What it does
h2 a::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
inset: 0;	Shorthand for top, right, bottom and left all zero: stretches over the parent.
font-weight: 700;	Thickness of the text.

Check your work

- Only one link per card (screen readers)
- Cards equal height in a row
- Price aligned at bottom
- Hover does not shift layout

Exercises

1. Add a filter bar with radio buttons and :has().
2. Add a 'new' badge.
3. Add a sort dropdown with JavaScript.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827

Field	Value
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 910: Product grid with clickable cards for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 2 | Files: index.html, styles.css

Brief

List all offers as equal-height cards where the whole card is clickable via a stretched link pseudo-element and the price sticks to the bottom.

Learning goals

- Make a whole card clickable accessibly (one link, stretched)
- Push an element to the bottom with margin-top: auto
- Lift cards on hover

Elements and CSS used

HTML elements	CSS features
article, img, div, h2, a, p	position: relative + ::after inset: 0, flex-direction: column, margin-top: auto, transition, translate

Build guide

1. Write one article per offer with image, heading link, text and price.
2. Grid with auto-fill.
3. Make card and body flex columns; body flex: 1.
4. Push price down with margin-top: auto.
5. Stretch the heading link over the card with ::after and inset: 0.

6. Add the hover lift.

Project 910: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - All products</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>All products</h1>
    <div class="grid">
      <article class="card">
        <img src="images/stationery-1.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Dotted notebook</a></h2>
          <p>A5, 160 pages.</p>
          <p class="price">140 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/stationery-2.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Fountain pen</a></h2>
          <p>Steel nib, refillable.</p>
          <p class="price">350 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/stationery-3.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Washi tape set</a></h2>
          <p>Six patterns.</p>
          <p class="price">90 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/stationery-4.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Desk planner</a></h2>
          <p>Weekly, undated.</p>
          <p class="price">110 EGP</p>
        </div>
```

```
      </article>
    </div>
  </main>
</body>
</html>
```

Project 910: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 70rem; margin: 2rem auto; padding: 0 1rem; }
.grid { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fill, minmax(15rem, 1fr)); }
.card { display: flex; flex-direction: column; border: 1px solid var(-
-line); border-radius: 14px; overflow: hidden; background: #fff;
position: relative; transition: box-shadow .2s, translate .2s; }
.card:hover { box-shadow: 0 12px 30px rgb(0 0 0 / 12%); translate: 0 -
3px; }
.card img { width: 100%; height: auto; aspect-ratio: 3 / 2; object-
fit: cover; }
.body { padding: 1rem 1.25rem; display: flex; flex-direction: column;
flex: 1; }
h2 { font-size: 1.1rem; margin: 0 0 .3rem; }
h2 a { color: inherit; text-decoration: none; }
h2 a::after { content: ""; position: absolute; inset: 0; }   /* whole
card clickable */
.body p { margin: 0 0 .5rem; color: var(--muted); }
.price { margin-top: auto !important; color: var(--brand); font-
weight: 700; }
```

Project 910 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - All products</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
All products	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/stationery-1.jpg" alt="" width="600" height="400">	An image; alt describes it, width and height reserve space before it loads.
Dotted notebook	Second-level heading for a section.
A5, 160 pages.	A paragraph of text.
Fountain pen	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 70rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(15rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.

Declaration	What it does
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 14px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
background: #fff;	Background colour or image.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
transition: box-shadow .2s, translate .2s;	Soft shadow that lifts the element from the page.
.card:hover {	Applies while the pointer is over the element.
translate: 0 -3px;	Moves the element without affecting the layout of others.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
flex: 1;	All items share free space equally.
font-size: 1.1rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
h2 a::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
inset: 0;	Shorthand for top, right, bottom and left all zero: stretches over the parent.
font-weight: 700;	Thickness of the text.

Check your work

- Only one link per card (screen readers)
- Cards equal height in a row
- Price aligned at bottom
- Hover does not shift layout

Exercises

1. Add a filter bar with radio buttons and :has().
2. Add a 'new' badge.
3. Add a sort dropdown with JavaScript.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 911: Product grid with clickable cards for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 2 | Files: index.html, styles.css

Brief

List all offers as equal-height cards where the whole card is clickable via a stretched link pseudo-element and the price sticks to the bottom.

Learning goals

- Make a whole card clickable accessibly (one link, stretched)
- Push an element to the bottom with margin-top: auto
- Lift cards on hover

Elements and CSS used

HTML elements	CSS features
article, img, div, h2, a, p	position: relative + ::after inset: 0, flex-direction: column, margin-top: auto, transition, translate

Build guide

1. Write one article per offer with image, heading link, text and price.
2. Grid with auto-fill.
3. Make card and body flex columns; body flex: 1.
4. Push price down with margin-top: auto.
5. Stretch the heading link over the card with ::after and inset: 0.

6. Add the hover lift.

Project 911: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - All plants</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>All plants</h1>
    <div class="grid">
      <article class="card">
        <img src="images/plants-1.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Monstera</a></h2>
          <p>Large leaves, easy care.</p>
          <p class="price">250 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/plants-2.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Snake plant</a></h2>
          <p>Survives anything.</p>
          <p class="price">120 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/plants-3.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Basil pot</a></h2>
          <p>Kitchen herb.</p>
          <p class="price">45 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/plants-4.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Olive tree</a></h2>
          <p>Balcony sized.</p>
          <p class="price">600 EGP</p>
        </div>
```

```
      </article>
    </div>
  </main>
</body>
</html>
```

Project 911: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 70rem; margin: 2rem auto; padding: 0 1rem; }
.grid { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fill, minmax(15rem, 1fr)); }
.card { display: flex; flex-direction: column; border: 1px solid var(-
-line); border-radius: 14px; overflow: hidden; background: #fff;
position: relative; transition: box-shadow .2s, translate .2s; }
.card:hover { box-shadow: 0 12px 30px rgb(0 0 0 / 12%); translate: 0 -
3px; }
.card img { width: 100%; height: auto; aspect-ratio: 3 / 2; object-
fit: cover; }
.body { padding: 1rem 1.25rem; display: flex; flex-direction: column;
flex: 1; }
h2 { font-size: 1.1rem; margin: 0 0 .3rem; }
h2 a { color: inherit; text-decoration: none; }
h2 a::after { content: ""; position: absolute; inset: 0; }   /* whole
card clickable */
.body p { margin: 0 0 .5rem; color: var(--muted); }
.price { margin-top: auto !important; color: var(--brand); font-
weight: 700; }
```

Project 911 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - All plants</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
All plants	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/plants-1.jpg" alt="" width="600" height="400">	An image; alt describes it, width and height reserve space before it loads.
Monstera 	Second-level heading for a section.
Large leaves, easy care.	A paragraph of text.

Line	What it does
Snake plant	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 70rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(15rem, 1fr));	Defines the columns of the grid.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 14px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
background: #fff;	Background colour or image.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
transition: box-shadow .2s, translate .2s;	Soft shadow that lifts the element from the page.
.card:hover {	Applies while the pointer is over the element.
translate: 0 -3px;	Moves the element without affecting the layout of others.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
flex: 1;	All items share free space equally.
font-size: 1.1rem;	Size of the text.
text-decoration: none;	Removes the underline from links.

Declaration	What it does
h2 a::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
inset: 0;	Shorthand for top, right, bottom and left all zero: stretches over the parent.
font-weight: 700;	Thickness of the text.

Check your work

- Only one link per card (screen readers)
- Cards equal height in a row
- Price aligned at bottom
- Hover does not shift layout

Exercises

1. Add a filter bar with radio buttons and :has().
2. Add a 'new' badge.
3. Add a sort dropdown with JavaScript.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d

Field	Value
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 912: Product grid with clickable cards for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 2 | Files: index.html, styles.css

Brief

List all offers as equal-height cards where the whole card is clickable via a stretched link pseudo-element and the price sticks to the bottom.

Learning goals

- Make a whole card clickable accessibly (one link, stretched)
- Push an element to the bottom with margin-top: auto
- Lift cards on hover

Elements and CSS used

HTML elements	CSS features
article, img, div, h2, a, p	position: relative + ::after inset: 0, flex-direction: column, margin-top: auto, transition, translate

Build guide

1. Write one article per offer with image, heading link, text and price.
2. Grid with auto-fill.
3. Make card and body flex columns; body flex: 1.
4. Push price down with margin-top: auto.
5. Stretch the heading link over the card with ::after and inset: 0.

6. Add the hover lift.

Project 912: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - All pieces</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>All pieces</h1>
    <div class="grid">
      <article class="card">
        <img src="images/furniture-1.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Oak dining table</a></h2>
          <p>Seats six.</p>
          <p class="price">9500 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/furniture-2.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Bookshelf</a></h2>
          <p>Five shelves, walnut.</p>
          <p class="price">4200 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/furniture-3.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Bedside table</a></h2>
          <p>One drawer.</p>
          <p class="price">1500 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/furniture-4.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Coffee table</a></h2>
          <p>Round, ash wood.</p>
          <p class="price">2800 EGP</p>
        </div>
```

```
      </article>
    </div>
  </main>
</body>
</html>
```

Project 912: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 70rem; margin: 2rem auto; padding: 0 1rem; }
.grid { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fill, minmax(15rem, 1fr)); }
.card { display: flex; flex-direction: column; border: 1px solid var(-
-line); border-radius: 14px; overflow: hidden; background: #fff;
position: relative; transition: box-shadow .2s, translate .2s; }
.card:hover { box-shadow: 0 12px 30px rgb(0 0 0 / 12%); translate: 0 -
3px; }
.card img { width: 100%; height: auto; aspect-ratio: 3 / 2; object-
fit: cover; }
.body { padding: 1rem 1.25rem; display: flex; flex-direction: column;
flex: 1; }
h2 { font-size: 1.1rem; margin: 0 0 .3rem; }
h2 a { color: inherit; text-decoration: none; }
h2 a::after { content: ""; position: absolute; inset: 0; }   /* whole
card clickable */
.body p { margin: 0 0 .5rem; color: var(--muted); }
.price { margin-top: auto !important; color: var(--brand); font-
weight: 700; }
```

Project 912 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - All pieces</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
All pieces	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/furniture-1.jpg" alt="" width="600" height="400">	An image; alt describes it, width and height reserve space before it loads.
Oak dining table	Second-level heading for a section.
Seats six.	A paragraph of text.
Bookshelf 	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 70rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(15rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.

Declaration	What it does
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 14px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
background: #fff;	Background colour or image.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
transition: box-shadow .2s, translate .2s;	Soft shadow that lifts the element from the page.
.card:hover {	Applies while the pointer is over the element.
translate: 0 -3px;	Moves the element without affecting the layout of others.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
flex: 1;	All items share free space equally.
font-size: 1.1rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
h2 a::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
inset: 0;	Shorthand for top, right, bottom and left all zero: stretches over the parent.
font-weight: 700;	Thickness of the text.

Check your work

- Only one link per card (screen readers)
- Cards equal height in a row
- Price aligned at bottom
- Hover does not shift layout

Exercises

1. Add a filter bar with radio buttons and :has().
2. Add a 'new' badge.
3. Add a sort dropdown with JavaScript.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 913: Product grid with clickable cards for Byte Repair

Theme: Byte Repair (Nasr City) | Level 2 | Files: index.html, styles.css

Brief

List all offers as equal-height cards where the whole card is clickable via a stretched link pseudo-element and the price sticks to the bottom.

Learning goals

- Make a whole card clickable accessibly (one link, stretched)
- Push an element to the bottom with margin-top: auto
- Lift cards on hover

Elements and CSS used

HTML elements	CSS features
article, img, div, h2, a, p	position: relative + ::after inset: 0, flex-direction: column, margin-top: auto, transition, translate

Build guide

1. Write one article per offer with image, heading link, text and price.
2. Grid with auto-fill.
3. Make card and body flex columns; body flex: 1.
4. Push price down with margin-top: auto.
5. Stretch the heading link over the card with ::after and inset: 0.
6. Add the hover lift.

Project 913: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - All repairs</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>All repairs</h1>
    <div class="grid">
      <article class="card">
        <img src="images/repair-1.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Screen replacement</a></h2>
          <p>Most phones, 1 hour.</p>
          <p class="price">From 800 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/repair-2.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Battery swap</a></h2>
          <p>Original cells.</p>
          <p class="price">From 500 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/repair-3.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Laptop cleaning</a></h2>
          <p>Fans and thermal paste.</p>
          <p class="price">350 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/repair-4.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Data recovery</a></h2>
          <p>Drives and cards.</p>
          <p class="price">From 1200 EGP</p>
        </div>
```

```
      </article>
    </div>
  </main>
</body>
</html>
```

Project 913: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 70rem; margin: 2rem auto; padding: 0 1rem; }
.grid { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fill, minmax(15rem, 1fr)); }
.card { display: flex; flex-direction: column; border: 1px solid var(-
-line); border-radius: 14px; overflow: hidden; background: #fff;
position: relative; transition: box-shadow .2s, translate .2s; }
.card:hover { box-shadow: 0 12px 30px rgb(0 0 0 / 12%); translate: 0 -
3px; }
.card img { width: 100%; height: auto; aspect-ratio: 3 / 2; object-
fit: cover; }
.body { padding: 1rem 1.25rem; display: flex; flex-direction: column;
flex: 1; }
h2 { font-size: 1.1rem; margin: 0 0 .3rem; }
h2 a { color: inherit; text-decoration: none; }
h2 a::after { content: ""; position: absolute; inset: 0; }   /* whole
card clickable */
.body p { margin: 0 0 .5rem; color: var(--muted); }
.price { margin-top: auto !important; color: var(--brand); font-
weight: 700; }
```

Project 913 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - All repairs</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
All repairs	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/repair-1.jpg" alt="" width="600" height="400">	An image; alt describes it, width and height reserve space before it loads.
Screen replacement	Second-level heading for a section.
Most phones, 1 hour.	A paragraph of text.
Battery swap	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 70rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(15rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.

Declaration	What it does
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 14px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
background: #fff;	Background colour or image.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
transition: box-shadow .2s, translate .2s;	Soft shadow that lifts the element from the page.
.card:hover {	Applies while the pointer is over the element.
translate: 0 -3px;	Moves the element without affecting the layout of others.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
flex: 1;	All items share free space equally.
font-size: 1.1rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
h2 a::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
inset: 0;	Shorthand for top, right, bottom and left all zero: stretches over the parent.
font-weight: 700;	Thickness of the text.

Check your work

- Only one link per card (screen readers)
- Cards equal height in a row
- Price aligned at bottom
- Hover does not shift layout

Exercises

1. Add a filter bar with radio buttons and :has().
2. Add a 'new' badge.
3. Add a sort dropdown with JavaScript.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 914: Product grid with clickable cards for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 2 | Files: index.html, styles.css

Brief

List all offers as equal-height cards where the whole card is clickable via a stretched link pseudo-element and the price sticks to the bottom.

Learning goals

- Make a whole card clickable accessibly (one link, stretched)
- Push an element to the bottom with margin-top: auto
- Lift cards on hover

Elements and CSS used

HTML elements	CSS features
article, img, div, h2, a, p	position: relative + ::after inset: 0, flex-direction: column, margin-top: auto, transition, translate

Build guide

1. Write one article per offer with image, heading link, text and price.
2. Grid with auto-fill.
3. Make card and body flex columns; body flex: 1.
4. Push price down with margin-top: auto.
5. Stretch the heading link over the card with ::after and inset: 0.

6. Add the hover lift.

Project 914: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - All services</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>All services</h1>
    <div class="grid">
      <article class="card">
        <img src="images/pets-1.jpg" alt="" width="600" height="400">
        <div class="body">
          <h2><a href="#">Full grooming</a></h2>
          <p>Bath, cut and nails.</p>
          <p class="price">400 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/pets-2.jpg" alt="" width="600" height="400">
        <div class="body">
          <h2><a href="#">Day boarding</a></h2>
          <p>Play and rest.</p>
          <p class="price">250 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/pets-3.jpg" alt="" width="600" height="400">
        <div class="body">
          <h2><a href="#">Vaccination</a></h2>
          <p>Annual boosters.</p>
          <p class="price">300 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/pets-4.jpg" alt="" width="600" height="400">
        <div class="body">
          <h2><a href="#">Dog walking</a></h2>
          <p>30 minutes.</p>
          <p class="price">100 EGP</p>
        </div>
      </article>
    </div>
  </main>
</body>
```

```
</html>
```

Project 914: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 70rem; margin: 2rem auto; padding: 0 1rem; }
.grid { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fill, minmax(15rem, 1fr)); }
.card { display: flex; flex-direction: column; border: 1px solid var(-
-line); border-radius: 14px; overflow: hidden; background: #fff;
position: relative; transition: box-shadow .2s, translate .2s; }
.card:hover { box-shadow: 0 12px 30px rgb(0 0 0 / 12%); translate: 0 -
3px; }
.card img { width: 100%; height: auto; aspect-ratio: 3 / 2; object-
fit: cover; }
.body { padding: 1rem 1.25rem; display: flex; flex-direction: column;
flex: 1; }
h2 { font-size: 1.1rem; margin: 0 0 .3rem; }
h2 a { color: inherit; text-decoration: none; }
h2 a::after { content: ""; position: absolute; inset: 0; }   /* whole
card clickable */
.body p { margin: 0 0 .5rem; color: var(--muted); }
.price { margin-top: auto !important; color: var(--brand); font-
weight: 700; }
```

Project 914 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - All services</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
All services	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/pets-1.jpg" alt="" width="600" height="400">	An image; alt describes it, width and height reserve space before it loads.
Full grooming	Second-level heading for a section.
Bath, cut and nails.	A paragraph of text.
Day boarding	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 70rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(15rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.

Declaration	What it does
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 14px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
background: #fff;	Background colour or image.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
transition: box-shadow .2s, translate .2s;	Soft shadow that lifts the element from the page.
.card:hover {	Applies while the pointer is over the element.
translate: 0 -3px;	Moves the element without affecting the layout of others.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
flex: 1;	All items share free space equally.
font-size: 1.1rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
h2 a::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
inset: 0;	Shorthand for top, right, bottom and left all zero: stretches over the parent.
font-weight: 700;	Thickness of the text.

Check your work

- Only one link per card (screen readers)
- Cards equal height in a row
- Price aligned at bottom
- Hover does not shift layout

Exercises

1. Add a filter bar with radio buttons and :has().
2. Add a 'new' badge.
3. Add a sort dropdown with JavaScript.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 915: Product grid with clickable cards for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

List all offers as equal-height cards where the whole card is clickable via a stretched link pseudo-element and the price sticks to the bottom.

Learning goals

- Make a whole card clickable accessibly (one link, stretched)
- Push an element to the bottom with margin-top: auto
- Lift cards on hover

Elements and CSS used

HTML elements	CSS features
article, img, div, h2, a, p	position: relative + ::after inset: 0, flex-direction: column, margin-top: auto, transition, translate

Build guide

1. Write one article per offer with image, heading link, text and price.
2. Grid with auto-fill.
3. Make card and body flex columns; body flex: 1.
4. Push price down with margin-top: auto.
5. Stretch the heading link over the card with ::after and inset: 0.

6. Add the hover lift.

Project 915: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - All lessons</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>All lessons</h1>
    <div class="grid">
      <article class="card">
        <img src="images/sailing-1.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Taster session</a></h2>
          <p>Two hours on the water.</p>
          <p class="price">500 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/sailing-2.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Beginner course</a></h2>
          <p>Five sessions.</p>
          <p class="price">2200 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/sailing-3.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Racing clinic</a></h2>
          <p>Tactics and trim.</p>
          <p class="price">1800 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/sailing-4.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Private lesson</a></h2>
          <p>One to one.</p>
          <p class="price">900 EGP</p>
        </div>
```

```
      </article>
    </div>
  </main>
</body>
</html>
```

Project 915: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 70rem; margin: 2rem auto; padding: 0 1rem; }
.grid { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fill, minmax(15rem, 1fr)); }
.card { display: flex; flex-direction: column; border: 1px solid var(-
-line); border-radius: 14px; overflow: hidden; background: #fff;
position: relative; transition: box-shadow .2s, translate .2s; }
.card:hover { box-shadow: 0 12px 30px rgb(0 0 0 / 12%); translate: 0 -
3px; }
.card img { width: 100%; height: auto; aspect-ratio: 3 / 2; object-
fit: cover; }
.body { padding: 1rem 1.25rem; display: flex; flex-direction: column;
flex: 1; }
h2 { font-size: 1.1rem; margin: 0 0 .3rem; }
h2 a { color: inherit; text-decoration: none; }
h2 a::after { content: ""; position: absolute; inset: 0; }   /* whole
card clickable */
.body p { margin: 0 0 .5rem; color: var(--muted); }
.price { margin-top: auto !important; color: var(--brand); font-
weight: 700; }
```

Project 915 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - All lessons</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
All lessons	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/sailing-1.jpg" alt="" width="600" height="400">	An image; alt describes it, width and height reserve space before it loads.
Taster session	Second-level heading for a section.
Two hours on the water.	A paragraph of text.

Line	What it does
Beginner course	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 70rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(15rem, 1fr));	Defines the columns of the grid.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 14px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
background: #fff;	Background colour or image.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
transition: box-shadow .2s, translate .2s;	Soft shadow that lifts the element from the page.
.card:hover {	Applies while the pointer is over the element.
translate: 0 -3px;	Moves the element without affecting the layout of others.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
flex: 1;	All items share free space equally.
font-size: 1.1rem;	Size of the text.
text-decoration: none;	Removes the underline from links.

Declaration	What it does
h2 a::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
inset: 0;	Shorthand for top, right, bottom and left all zero: stretches over the parent.
font-weight: 700;	Thickness of the text.

Check your work

- Only one link per card (screen readers)
- Cards equal height in a row
- Price aligned at bottom
- Hover does not shift layout

Exercises

1. Add a filter bar with radio buttons and :has().
2. Add a 'new' badge.
3. Add a sort dropdown with JavaScript.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af

Field	Value
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 916: Product grid with clickable cards for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 2 | Files: index.html, styles.css

Brief

List all offers as equal-height cards where the whole card is clickable via a stretched link pseudo-element and the price sticks to the bottom.

Learning goals

- Make a whole card clickable accessibly (one link, stretched)
- Push an element to the bottom with margin-top: auto
- Lift cards on hover

Elements and CSS used

HTML elements	CSS features
article, img, div, h2, a, p	position: relative + ::after inset: 0, flex-direction: column, margin-top: auto, transition, translate

Build guide

1. Write one article per offer with image, heading link, text and price.
2. Grid with auto-fill.
3. Make card and body flex columns; body flex: 1.
4. Push price down with margin-top: auto.
5. Stretch the heading link over the card with ::after and inset: 0.

6. Add the hover lift.

Project 916: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - All items</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>All items</h1>
    <div class="grid">
      <article class="card">
        <img src="images/jewellery-1.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Lotus pendant</a></h2>
          <p>Sterling silver.</p>
          <p class="price">650 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/jewellery-2.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Brass cuff</a></h2>
          <p>Hand engraved.</p>
          <p class="price">420 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/jewellery-3.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Bead earrings</a></h2>
          <p>Recycled glass.</p>
          <p class="price">180 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/jewellery-4.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Ankh ring</a></h2>
          <p>Adjustable.</p>
          <p class="price">300 EGP</p>
        </div>
```

```
      </article>
    </div>
  </main>
</body>
</html>
```

Project 916: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 70rem; margin: 2rem auto; padding: 0 1rem; }
.grid { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fill, minmax(15rem, 1fr)); }
.card { display: flex; flex-direction: column; border: 1px solid var(-
-line); border-radius: 14px; overflow: hidden; background: #fff;
position: relative; transition: box-shadow .2s, translate .2s; }
.card:hover { box-shadow: 0 12px 30px rgb(0 0 0 / 12%); translate: 0 -
3px; }
.card img { width: 100%; height: auto; aspect-ratio: 3 / 2; object-
fit: cover; }
.body { padding: 1rem 1.25rem; display: flex; flex-direction: column;
flex: 1; }
h2 { font-size: 1.1rem; margin: 0 0 .3rem; }
h2 a { color: inherit; text-decoration: none; }
h2 a::after { content: ""; position: absolute; inset: 0; }   /* whole
card clickable */
.body p { margin: 0 0 .5rem; color: var(--muted); }
.price { margin-top: auto !important; color: var(--brand); font-
weight: 700; }
```

Project 916 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - All items</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
All items	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/jewellery-1.jpg" alt="" width="600" height="400">	An image; alt describes it, width and height reserve space before it loads.
Lotus pendant	Second-level heading for a section.
Sterling silver.	A paragraph of text.
Brass cuff	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 70rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(15rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.

Declaration	What it does
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 14px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
background: #fff;	Background colour or image.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
transition: box-shadow .2s, translate .2s;	Soft shadow that lifts the element from the page.
.card:hover {	Applies while the pointer is over the element.
translate: 0 -3px;	Moves the element without affecting the layout of others.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
flex: 1;	All items share free space equally.
font-size: 1.1rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
h2 a::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
inset: 0;	Shorthand for top, right, bottom and left all zero: stretches over the parent.
font-weight: 700;	Thickness of the text.

Check your work

- Only one link per card (screen readers)
- Cards equal height in a row
- Price aligned at bottom
- Hover does not shift layout

Exercises

1. Add a filter bar with radio buttons and :has().
2. Add a 'new' badge.
3. Add a sort dropdown with JavaScript.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 917: Product grid with clickable cards for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 2 | Files: index.html, styles.css

Brief

List all offers as equal-height cards where the whole card is clickable via a stretched link pseudo-element and the price sticks to the bottom.

Learning goals

- Make a whole card clickable accessibly (one link, stretched)
- Push an element to the bottom with margin-top: auto
- Lift cards on hover

Elements and CSS used

HTML elements	CSS features
article, img, div, h2, a, p	position: relative + ::after inset: 0, flex-direction: column, margin-top: auto, transition, translate

Build guide

1. Write one article per offer with image, heading link, text and price.
2. Grid with auto-fill.
3. Make card and body flex columns; body flex: 1.
4. Push price down with margin-top: auto.
5. Stretch the heading link over the card with ::after and inset: 0.

6. Add the hover lift.

Project 917: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - All workshops</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>All workshops</h1>
    <div class="grid">
      <article class="card">
        <img src="images/pottery-1.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Intro to the wheel</a></h2>
          <p>Three hours, take home a bowl.</p>
          <p class="price">450 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/pottery-2.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Glazing day</a></h2>
          <p>Colour your pieces.</p>
          <p class="price">300 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/pottery-3.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Kids clay class</a></h2>
          <p>Ages 6 to 12.</p>
          <p class="price">200 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/pottery-4.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Weekend retreat</a></h2>
          <p>Two days with meals.</p>
          <p class="price">2500 EGP</p>
        </div>
```

```
      </article>
    </div>
  </main>
</body>
</html>
```

Project 917: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 70rem; margin: 2rem auto; padding: 0 1rem; }
.grid { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fill, minmax(15rem, 1fr)); }
.card { display: flex; flex-direction: column; border: 1px solid var(-
-line); border-radius: 14px; overflow: hidden; background: #fff;
position: relative; transition: box-shadow .2s, translate .2s; }
.card:hover { box-shadow: 0 12px 30px rgb(0 0 0 / 12%); translate: 0 -
3px; }
.card img { width: 100%; height: auto; aspect-ratio: 3 / 2; object-
fit: cover; }
.body { padding: 1rem 1.25rem; display: flex; flex-direction: column;
flex: 1; }
h2 { font-size: 1.1rem; margin: 0 0 .3rem; }
h2 a { color: inherit; text-decoration: none; }
h2 a::after { content: ""; position: absolute; inset: 0; }   /* whole
card clickable */
.body p { margin: 0 0 .5rem; color: var(--muted); }
.price { margin-top: auto !important; color: var(--brand); font-
weight: 700; }
```

Project 917 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - All workshops</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
All workshops	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/pottery-1.jpg" alt="" width="600" height="400">	An image; alt describes it, width and height reserve space before it loads.
Intro to the wheel	Second-level heading for a section.
Three hours, take home a bowl.	A paragraph of text.

Line	What it does
Glazing day	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 70rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(15rem, 1fr));	Defines the columns of the grid.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 14px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
background: #fff;	Background colour or image.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
transition: box-shadow .2s, translate .2s;	Soft shadow that lifts the element from the page.
.card:hover {	Applies while the pointer is over the element.
translate: 0 -3px;	Moves the element without affecting the layout of others.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
flex: 1;	All items share free space equally.
font-size: 1.1rem;	Size of the text.
text-decoration: none;	Removes the underline from links.

Declaration	What it does
h2 a::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
inset: 0;	Shorthand for top, right, bottom and left all zero: stretches over the parent.
font-weight: 700;	Thickness of the text.

Check your work

- Only one link per card (screen readers)
- Cards equal height in a row
- Price aligned at bottom
- Hover does not shift layout

Exercises

1. Add a filter bar with radio buttons and :has().
2. Add a 'new' badge.
3. Add a sort dropdown with JavaScript.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412

Field	Value
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 918: Product grid with clickable cards for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 2 | Files: index.html, styles.css

Brief

List all offers as equal-height cards where the whole card is clickable via a stretched link pseudo-element and the price sticks to the bottom.

Learning goals

- Make a whole card clickable accessibly (one link, stretched)
- Push an element to the bottom with margin-top: auto
- Lift cards on hover

Elements and CSS used

HTML elements	CSS features
article, img, div, h2, a, p	position: relative + ::after inset: 0, flex-direction: column, margin-top: auto, transition, translate

Build guide

1. Write one article per offer with image, heading link, text and price.
2. Grid with auto-fill.
3. Make card and body flex columns; body flex: 1.
4. Push price down with margin-top: auto.
5. Stretch the heading link over the card with ::after and inset: 0.

6. Add the hover lift.

Project 918: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - All treatments</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>All treatments</h1>
    <div class="grid">
      <article class="card">
        <img src="images/salon-1.jpg" alt="" width="600" height="400">
        <div class="body">
          <h2><a href="#">Haircut and blow-dry</a></h2>
          <p>Consultation included.</p>
          <p class="price">350 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/salon-2.jpg" alt="" width="600" height="400">
        <div class="body">
          <h2><a href="#">Manicure</a></h2>
          <p>Classic or gel.</p>
          <p class="price">200 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/salon-3.jpg" alt="" width="600" height="400">
        <div class="body">
          <h2><a href="#">Facial</a></h2>
          <p>Deep cleanse, 60 minutes.</p>
          <p class="price">600 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/salon-4.jpg" alt="" width="600" height="400">
        <div class="body">
          <h2><a href="#">Bridal package</a></h2>
          <p>Hair, make-up and nails.</p>
          <p class="price">4500 EGP</p>
        </div>
      </article>
    </div>
  </main>
</body>
```

```
</html>
```

Project 918: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 70rem; margin: 2rem auto; padding: 0 1rem; }
.grid { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fill, minmax(15rem, 1fr)); }
.card { display: flex; flex-direction: column; border: 1px solid var(-
-line); border-radius: 14px; overflow: hidden; background: #fff;
position: relative; transition: box-shadow .2s, translate .2s; }
.card:hover { box-shadow: 0 12px 30px rgb(0 0 0 / 12%); translate: 0 -
3px; }
.card img { width: 100%; height: auto; aspect-ratio: 3 / 2; object-
fit: cover; }
.body { padding: 1rem 1.25rem; display: flex; flex-direction: column;
flex: 1; }
h2 { font-size: 1.1rem; margin: 0 0 .3rem; }
h2 a { color: inherit; text-decoration: none; }
h2 a::after { content: ""; position: absolute; inset: 0; }   /* whole
card clickable */
.body p { margin: 0 0 .5rem; color: var(--muted); }
.price { margin-top: auto !important; color: var(--brand); font-
weight: 700; }
```

Project 918 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - All treatments</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
All treatments	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/salon-1.jpg" alt="" width="600" height="400">	An image; alt describes it, width and height reserve space before it loads.
Haircut and blow-dry	Second-level heading for a section.
Consultation included.	A paragraph of text.

Line	What it does
Manicure	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 70rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(15rem, 1fr));	Defines the columns of the grid.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 14px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
background: #fff;	Background colour or image.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
transition: box-shadow .2s, translate .2s;	Soft shadow that lifts the element from the page.
.card:hover {	Applies while the pointer is over the element.
translate: 0 -3px;	Moves the element without affecting the layout of others.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
flex: 1;	All items share free space equally.
font-size: 1.1rem;	Size of the text.
text-decoration: none;	Removes the underline from links.

Declaration	What it does
h2 a::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
inset: 0;	Shorthand for top, right, bottom and left all zero: stretches over the parent.
font-weight: 700;	Thickness of the text.

Check your work

- Only one link per card (screen readers)
- Cards equal height in a row
- Price aligned at bottom
- Hover does not shift layout

Exercises

1. Add a filter bar with radio buttons and :has().
2. Add a 'new' badge.
3. Add a sort dropdown with JavaScript.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777

Field	Value
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 919: Product grid with clickable cards for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 2 | Files: index.html, styles.css

Brief

List all offers as equal-height cards where the whole card is clickable via a stretched link pseudo-element and the price sticks to the bottom.

Learning goals

- Make a whole card clickable accessibly (one link, stretched)
- Push an element to the bottom with margin-top: auto
- Lift cards on hover

Elements and CSS used

HTML elements	CSS features
article, img, div, h2, a, p	position: relative + ::after inset: 0, flex-direction: column, margin-top: auto, transition, translate

Build guide

1. Write one article per offer with image, heading link, text and price.
2. Grid with auto-fill.
3. Make card and body flex columns; body flex: 1.
4. Push price down with margin-top: auto.
5. Stretch the heading link over the card with ::after and inset: 0.

6. Add the hover lift.

Project 919: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - All services</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>All services</h1>
    <div class="grid">
      <article class="card">
        <img src="images/auto-1.jpg" alt="" width="600" height="400">
        <div class="body">
          <h2><a href="#">Oil change</a></h2>
          <p>Filter included.</p>
          <p class="price">600 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/auto-2.jpg" alt="" width="600" height="400">
        <div class="body">
          <h2><a href="#">Brake pads</a></h2>
          <p>Front axle.</p>
          <p class="price">1400 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/auto-3.jpg" alt="" width="600" height="400">
        <div class="body">
          <h2><a href="#">Air conditioning</a></h2>
          <p>Recharge and check.</p>
          <p class="price">900 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/auto-4.jpg" alt="" width="600" height="400">
        <div class="body">
          <h2><a href="#">Pre-purchase inspection</a></h2>
          <p>120 point check.</p>
          <p class="price">750 EGP</p>
        </div>
      </article>
    </div>
  </main>
</body>
```

```
</html>
```

Project 919: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 70rem; margin: 2rem auto; padding: 0 1rem; }
.grid { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fill, minmax(15rem, 1fr)); }
.card { display: flex; flex-direction: column; border: 1px solid var(-
-line); border-radius: 14px; overflow: hidden; background: #fff;
position: relative; transition: box-shadow .2s, translate .2s; }
.card:hover { box-shadow: 0 12px 30px rgb(0 0 0 / 12%); translate: 0 -
3px; }
.card img { width: 100%; height: auto; aspect-ratio: 3 / 2; object-
fit: cover; }
.body { padding: 1rem 1.25rem; display: flex; flex-direction: column;
flex: 1; }
h2 { font-size: 1.1rem; margin: 0 0 .3rem; }
h2 a { color: inherit; text-decoration: none; }
h2 a::after { content: ""; position: absolute; inset: 0; }   /* whole
card clickable */
.body p { margin: 0 0 .5rem; color: var(--muted); }
.price { margin-top: auto !important; color: var(--brand); font-
weight: 700; }
```

Project 919 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - All services</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
All services	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/auto-1.jpg" alt="" width="600" height="400">	An image; alt describes it, width and height reserve space before it loads.
Oil change	Second-level heading for a section.
Filter included.	A paragraph of text.
Brake pads	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 70rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(15rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.

Declaration	What it does
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 14px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
background: #fff;	Background colour or image.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
transition: box-shadow .2s, translate .2s;	Soft shadow that lifts the element from the page.
.card:hover {	Applies while the pointer is over the element.
translate: 0 -3px;	Moves the element without affecting the layout of others.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
flex: 1;	All items share free space equally.
font-size: 1.1rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
h2 a::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
inset: 0;	Shorthand for top, right, bottom and left all zero: stretches over the parent.
font-weight: 700;	Thickness of the text.

Check your work

- Only one link per card (screen readers)
- Cards equal height in a row
- Price aligned at bottom
- Hover does not shift layout

Exercises

1. Add a filter bar with radio buttons and :has().
2. Add a 'new' badge.
3. Add a sort dropdown with JavaScript.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 920: Product grid with clickable cards for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 2 | Files: index.html, styles.css

Brief

List all offers as equal-height cards where the whole card is clickable via a stretched link pseudo-element and the price sticks to the bottom.

Learning goals

- Make a whole card clickable accessibly (one link, stretched)
- Push an element to the bottom with margin-top: auto
- Lift cards on hover

Elements and CSS used

HTML elements	CSS features
article, img, div, h2, a, p	position: relative + ::after inset: 0, flex-direction: column, margin-top: auto, transition, translate

Build guide

1. Write one article per offer with image, heading link, text and price.
2. Grid with auto-fill.
3. Make card and body flex columns; body flex: 1.
4. Push price down with margin-top: auto.
5. Stretch the heading link over the card with ::after and inset: 0.

6. Add the hover lift.

Project 920: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - All courses</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>All courses</h1>
    <div class="grid">
      <article class="card">
        <img src="images/music-1.jpg" alt="" width="600" height="400">
        <div class="body">
          <h2><a href="#">Oud for beginners</a></h2>
          <p>Eight weekly lessons.</p>
          <p class="price">1600 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/music-2.jpg" alt="" width="600" height="400">
        <div class="body">
          <h2><a href="#">Piano grade 1</a></h2>
          <p>Theory and practice.</p>
          <p class="price">1800 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/music-3.jpg" alt="" width="600" height="400">
        <div class="body">
          <h2><a href="#">Guitar chords</a></h2>
          <p>Play songs in a month.</p>
          <p class="price">1400 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/music-4.jpg" alt="" width="600" height="400">
        <div class="body">
          <h2><a href="#">Voice coaching</a></h2>
          <p>Breathing and range.</p>
          <p class="price">1500 EGP</p>
        </div>
      </article>
    </div>
  </main>
</body>
```

```
</html>
```

Project 920: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 70rem; margin: 2rem auto; padding: 0 1rem; }
.grid { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fill, minmax(15rem, 1fr)); }
.card { display: flex; flex-direction: column; border: 1px solid var(-
-line); border-radius: 14px; overflow: hidden; background: #fff;
position: relative; transition: box-shadow .2s, translate .2s; }
.card:hover { box-shadow: 0 12px 30px rgb(0 0 0 / 12%); translate: 0 -
3px; }
.card img { width: 100%; height: auto; aspect-ratio: 3 / 2; object-
fit: cover; }
.body { padding: 1rem 1.25rem; display: flex; flex-direction: column;
flex: 1; }
h2 { font-size: 1.1rem; margin: 0 0 .3rem; }
h2 a { color: inherit; text-decoration: none; }
h2 a::after { content: ""; position: absolute; inset: 0; }   /* whole
card clickable */
.body p { margin: 0 0 .5rem; color: var(--muted); }
.price { margin-top: auto !important; color: var(--brand); font-
weight: 700; }
```

Project 920 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - All courses</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
All courses	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/music-1.jpg" alt="" width="600" height="400">	An image; alt describes it, width and height reserve space before it loads.
Oud for beginners	Second-level heading for a section.
Eight weekly lessons.	A paragraph of text.

Line	What it does
Piano grade 1	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 70rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(15rem, 1fr));	Defines the columns of the grid.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 14px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
background: #fff;	Background colour or image.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
transition: box-shadow .2s, translate .2s;	Soft shadow that lifts the element from the page.
.card:hover {	Applies while the pointer is over the element.
translate: 0 -3px;	Moves the element without affecting the layout of others.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
flex: 1;	All items share free space equally.
font-size: 1.1rem;	Size of the text.
text-decoration: none;	Removes the underline from links.

Declaration	What it does
h2 a::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
inset: 0;	Shorthand for top, right, bottom and left all zero: stretches over the parent.
font-weight: 700;	Thickness of the text.

Check your work

- Only one link per card (screen readers)
- Cards equal height in a row
- Price aligned at bottom
- Hover does not shift layout

Exercises

1. Add a filter bar with radio buttons and :has().
2. Add a 'new' badge.
3. Add a sort dropdown with JavaScript.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95

Field	Value
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 921: Product grid with clickable cards for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 2 | Files: index.html, styles.css

Brief

List all offers as equal-height cards where the whole card is clickable via a stretched link pseudo-element and the price sticks to the bottom.

Learning goals

- Make a whole card clickable accessibly (one link, stretched)
- Push an element to the bottom with margin-top: auto
- Lift cards on hover

Elements and CSS used

HTML elements	CSS features
article, img, div, h2, a, p	position: relative + ::after inset: 0, flex-direction: column, margin-top: auto, transition, translate

Build guide

1. Write one article per offer with image, heading link, text and price.
2. Grid with auto-fill.
3. Make card and body flex columns; body flex: 1.
4. Push price down with margin-top: auto.
5. Stretch the heading link over the card with ::after and inset: 0.

6. Add the hover lift.

Project 921: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - All dishes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>All dishes</h1>
    <div class="grid">
      <article class="card">
        <img src="images/restaurant-1.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Grilled sea bass</a></h2>
          <p>With rice and salad.</p>
          <p class="price">320 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/restaurant-2.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Shrimp tagine</a></h2>
          <p>Tomato and garlic.</p>
          <p class="price">280 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/restaurant-3.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Calamari</a></h2>
          <p>Fried, with tahini.</p>
          <p class="price">190 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/restaurant-4.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Fish soup</a></h2>
          <p>Daily catch.</p>
          <p class="price">120 EGP</p>
        </div>
```

```
      </article>
    </div>
  </main>
</body>
</html>
```

Project 921: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 70rem; margin: 2rem auto; padding: 0 1rem; }
.grid { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fill, minmax(15rem, 1fr)); }
.card { display: flex; flex-direction: column; border: 1px solid var(-
-line); border-radius: 14px; overflow: hidden; background: #fff;
position: relative; transition: box-shadow .2s, translate .2s; }
.card:hover { box-shadow: 0 12px 30px rgb(0 0 0 / 12%); translate: 0 -
3px; }
.card img { width: 100%; height: auto; aspect-ratio: 3 / 2; object-
fit: cover; }
.body { padding: 1rem 1.25rem; display: flex; flex-direction: column;
flex: 1; }
h2 { font-size: 1.1rem; margin: 0 0 .3rem; }
h2 a { color: inherit; text-decoration: none; }
h2 a::after { content: ""; position: absolute; inset: 0; }   /* whole
card clickable */
.body p { margin: 0 0 .5rem; color: var(--muted); }
.price { margin-top: auto !important; color: var(--brand); font-
weight: 700; }
```

Project 921 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - All dishes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
All dishes	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/restaurant-1.jpg" alt="" width="600" height="400">	An image; alt describes it, width and height reserve space before it loads.
Grilled sea bass	Second-level heading for a section.
With rice and salad.	A paragraph of text.
Shrimp tagine	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 70rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(15rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.

Declaration	What it does
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 14px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
background: #fff;	Background colour or image.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
transition: box-shadow .2s, translate .2s;	Soft shadow that lifts the element from the page.
.card:hover {	Applies while the pointer is over the element.
translate: 0 -3px;	Moves the element without affecting the layout of others.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
flex: 1;	All items share free space equally.
font-size: 1.1rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
h2 a::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
inset: 0;	Shorthand for top, right, bottom and left all zero: stretches over the parent.
font-weight: 700;	Thickness of the text.

Check your work

- Only one link per card (screen readers)
- Cards equal height in a row
- Price aligned at bottom
- Hover does not shift layout

Exercises

1. Add a filter bar with radio buttons and :has().
2. Add a 'new' badge.
3. Add a sort dropdown with JavaScript.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 922: Product grid with clickable cards for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 2 | Files: index.html, styles.css

Brief

List all offers as equal-height cards where the whole card is clickable via a stretched link pseudo-element and the price sticks to the bottom.

Learning goals

- Make a whole card clickable accessibly (one link, stretched)
- Push an element to the bottom with margin-top: auto
- Lift cards on hover

Elements and CSS used

HTML elements	CSS features
article, img, div, h2, a, p	position: relative + ::after inset: 0, flex-direction: column, margin-top: auto, transition, translate

Build guide

1. Write one article per offer with image, heading link, text and price.
2. Grid with auto-fill.
3. Make card and body flex columns; body flex: 1.
4. Push price down with margin-top: auto.
5. Stretch the heading link over the card with ::after and inset: 0.

6. Add the hover lift.

Project 922: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - All programmes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>All programmes</h1>
    <div class="grid">
      <article class="card">
        <img src="images/library-1.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Story hour</a></h2>
          <p>Ages 3 to 6, Saturdays.</p>
          <p class="price">Free</p>
        </div>
      </article>
      <article class="card">
        <img src="images/library-2.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Reading club</a></h2>
          <p>Ages 7 to 11.</p>
          <p class="price">50 EGP per month</p>
        </div>
      </article>
      <article class="card">
        <img src="images/library-3.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Homework help</a></h2>
          <p>Weekday afternoons.</p>
          <p class="price">Free</p>
        </div>
      </article>
      <article class="card">
        <img src="images/library-4.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Summer challenge</a></h2>
          <p>Read ten books.</p>
          <p class="price">Free</p>
        </div>
```

```
      </article>
    </div>
  </main>
</body>
</html>
```

Project 922: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 70rem; margin: 2rem auto; padding: 0 1rem; }
.grid { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fill, minmax(15rem, 1fr)); }
.card { display: flex; flex-direction: column; border: 1px solid var(-
-line); border-radius: 14px; overflow: hidden; background: #fff;
position: relative; transition: box-shadow .2s, translate .2s; }
.card:hover { box-shadow: 0 12px 30px rgb(0 0 0 / 12%); translate: 0 -
3px; }
.card img { width: 100%; height: auto; aspect-ratio: 3 / 2; object-
fit: cover; }
.body { padding: 1rem 1.25rem; display: flex; flex-direction: column;
flex: 1; }
h2 { font-size: 1.1rem; margin: 0 0 .3rem; }
h2 a { color: inherit; text-decoration: none; }
h2 a::after { content: ""; position: absolute; inset: 0; }   /* whole
card clickable */
.body p { margin: 0 0 .5rem; color: var(--muted); }
.price { margin-top: auto !important; color: var(--brand); font-
weight: 700; }
```

Project 922 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - All programmes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
All programmes	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/library-1.jpg" alt="" width="600" height="400">	An image; alt describes it, width and height reserve space before it loads.
Story hour	Second-level heading for a section.
Ages 3 to 6, Saturdays.	A paragraph of text.

Line	What it does
Reading club	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 70rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(15rem, 1fr));	Defines the columns of the grid.

Declaration	What it does
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 14px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
background: #fff;	Background colour or image.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
transition: box-shadow .2s, translate .2s;	Soft shadow that lifts the element from the page.
.card:hover {	Applies while the pointer is over the element.
translate: 0 -3px;	Moves the element without affecting the layout of others.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
flex: 1;	All items share free space equally.
font-size: 1.1rem;	Size of the text.
text-decoration: none;	Removes the underline from links.

Declaration	What it does
h2 a::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
inset: 0;	Shorthand for top, right, bottom and left all zero: stretches over the parent.
font-weight: 700;	Thickness of the text.

Check your work

- Only one link per card (screen readers)
- Cards equal height in a row
- Price aligned at bottom
- Hover does not shift layout

Exercises

1. Add a filter bar with radio buttons and :has().
2. Add a 'new' badge.
3. Add a sort dropdown with JavaScript.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c

Field	Value
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 923: Product grid with clickable cards for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 2 | Files: index.html, styles.css

Brief

List all offers as equal-height cards where the whole card is clickable via a stretched link pseudo-element and the price sticks to the bottom.

Learning goals

- Make a whole card clickable accessibly (one link, stretched)
- Push an element to the bottom with margin-top: auto
- Lift cards on hover

Elements and CSS used

HTML elements	CSS features
article, img, div, h2, a, p	position: relative + ::after inset: 0, flex-direction: column, margin-top: auto, transition, translate

Build guide

1. Write one article per offer with image, heading link, text and price.
2. Grid with auto-fill.
3. Make card and body flex columns; body flex: 1.
4. Push price down with margin-top: auto.
5. Stretch the heading link over the card with ::after and inset: 0.

6. Add the hover lift.

Project 923: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - All rooms</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>All rooms</h1>
    <div class="grid">
      <article class="card">
        <img src="images/guesthouse-1.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Garden room</a></h2>
          <p>Double bed, shared terrace.</p>
          <p class="price">900 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/guesthouse-2.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Nile view suite</a></h2>
          <p>Balcony and breakfast.</p>
          <p class="price">1800 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/guesthouse-3.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Family room</a></h2>
          <p>Sleeps four.</p>
          <p class="price">1500 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/guesthouse-4.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Rooftop dorm</a></h2>
          <p>Budget beds.</p>
          <p class="price">300 EGP</p>
        </div>
```

```
      </article>
    </div>
  </main>
</body>
</html>
```

Project 923: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 70rem; margin: 2rem auto; padding: 0 1rem; }
.grid { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fill, minmax(15rem, 1fr)); }
.card { display: flex; flex-direction: column; border: 1px solid var(-
-line); border-radius: 14px; overflow: hidden; background: #fff;
position: relative; transition: box-shadow .2s, translate .2s; }
.card:hover { box-shadow: 0 12px 30px rgb(0 0 0 / 12%); translate: 0 -
3px; }
.card img { width: 100%; height: auto; aspect-ratio: 3 / 2; object-
fit: cover; }
.body { padding: 1rem 1.25rem; display: flex; flex-direction: column;
flex: 1; }
h2 { font-size: 1.1rem; margin: 0 0 .3rem; }
h2 a { color: inherit; text-decoration: none; }
h2 a::after { content: ""; position: absolute; inset: 0; }   /* whole
card clickable */
.body p { margin: 0 0 .5rem; color: var(--muted); }
.price { margin-top: auto !important; color: var(--brand); font-
weight: 700; }
```

Project 923 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - All rooms</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
All rooms	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/guesthouse-1.jpg" alt="" width="600" height="400">	An image; alt describes it, width and height reserve space before it loads.
Garden room	Second-level heading for a section.
Double bed, shared terrace.	A paragraph of text.
Nile view suite	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 70rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(15rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.

Declaration	What it does
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 14px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
background: #fff;	Background colour or image.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
transition: box-shadow .2s, translate .2s;	Soft shadow that lifts the element from the page.
.card:hover {	Applies while the pointer is over the element.
translate: 0 -3px;	Moves the element without affecting the layout of others.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
flex: 1;	All items share free space equally.
font-size: 1.1rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
h2 a::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
inset: 0;	Shorthand for top, right, bottom and left all zero: stretches over the parent.
font-weight: 700;	Thickness of the text.

Check your work

- Only one link per card (screen readers)
- Cards equal height in a row
- Price aligned at bottom
- Hover does not shift layout

Exercises

1. Add a filter bar with radio buttons and :has().
2. Add a 'new' badge.
3. Add a sort dropdown with JavaScript.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 924: Product grid with clickable cards for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 2 | Files: index.html, styles.css

Brief

List all offers as equal-height cards where the whole card is clickable via a stretched link pseudo-element and the price sticks to the bottom.

Learning goals

- Make a whole card clickable accessibly (one link, stretched)
- Push an element to the bottom with margin-top: auto
- Lift cards on hover

Elements and CSS used

HTML elements	CSS features
article, img, div, h2, a, p	position: relative + ::after inset: 0, flex-direction: column, margin-top: auto, transition, translate

Build guide

1. Write one article per offer with image, heading link, text and price.
2. Grid with auto-fill.
3. Make card and body flex columns; body flex: 1.
4. Push price down with margin-top: auto.
5. Stretch the heading link over the card with ::after and inset: 0.

6. Add the hover lift.

Project 924: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - All bikes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>All bikes</h1>
    <div class="grid">
      <article class="card">
        <img src="images/cycling-1.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">City bike</a></h2>
          <p>Seven gears, basket.</p>
          <p class="price">6500 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/cycling-2.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Mountain bike</a></h2>
          <p>Front suspension.</p>
          <p class="price">11000 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/cycling-3.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Kids bike</a></h2>
          <p>20 inch wheels.</p>
          <p class="price">3200 EGP</p>
        </div>
      </article>
      <article class="card">
        <img src="images/cycling-4.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Tune-up</a></h2>
          <p>Brakes, gears and true wheels.</p>
          <p class="price">250 EGP</p>
        </div>
```

```
      </article>
    </div>
  </main>
</body>
</html>
```

Project 924: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 70rem; margin: 2rem auto; padding: 0 1rem; }
.grid { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fill, minmax(15rem, 1fr)); }
.card { display: flex; flex-direction: column; border: 1px solid var(-
-line); border-radius: 14px; overflow: hidden; background: #fff;
position: relative; transition: box-shadow .2s, translate .2s; }
.card:hover { box-shadow: 0 12px 30px rgb(0 0 0 / 12%); translate: 0 -
3px; }
.card img { width: 100%; height: auto; aspect-ratio: 3 / 2; object-
fit: cover; }
.body { padding: 1rem 1.25rem; display: flex; flex-direction: column;
flex: 1; }
h2 { font-size: 1.1rem; margin: 0 0 .3rem; }
h2 a { color: inherit; text-decoration: none; }
h2 a::after { content: ""; position: absolute; inset: 0; }   /* whole
card clickable */
.body p { margin: 0 0 .5rem; color: var(--muted); }
.price { margin-top: auto !important; color: var(--brand); font-
weight: 700; }
```

Project 924 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - All bikes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
All bikes	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/cycling-1.jpg" alt="" width="600" height="400">	An image; alt describes it, width and height reserve space before it loads.
City bike	Second-level heading for a section.
Seven gears, basket.	A paragraph of text.
Mountain bike	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 70rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(15rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.

Declaration	What it does
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 14px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
background: #fff;	Background colour or image.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
transition: box-shadow .2s, translate .2s;	Soft shadow that lifts the element from the page.
.card:hover {	Applies while the pointer is over the element.
translate: 0 -3px;	Moves the element without affecting the layout of others.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
flex: 1;	All items share free space equally.
font-size: 1.1rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
h2 a::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
inset: 0;	Shorthand for top, right, bottom and left all zero: stretches over the parent.
font-weight: 700;	Thickness of the text.

Check your work

- Only one link per card (screen readers)
- Cards equal height in a row
- Price aligned at bottom
- Hover does not shift layout

Exercises

1. Add a filter bar with radio buttons and :has().
2. Add a 'new' badge.
3. Add a sort dropdown with JavaScript.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 925: Product grid with clickable cards for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 2 | Files: index.html, styles.css

Brief

List all offers as equal-height cards where the whole card is clickable via a stretched link pseudo-element and the price sticks to the bottom.

Learning goals

- Make a whole card clickable accessibly (one link, stretched)
- Push an element to the bottom with margin-top: auto
- Lift cards on hover

Elements and CSS used

HTML elements	CSS features
article, img, div, h2, a, p	position: relative + ::after inset: 0, flex-direction: column, margin-top: auto, transition, translate

Build guide

1. Write one article per offer with image, heading link, text and price.
2. Grid with auto-fill.
3. Make card and body flex columns; body flex: 1.
4. Push price down with margin-top: auto.
5. Stretch the heading link over the card with ::after and inset: 0.

6. Add the hover lift.

Project 925: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - All workshops</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>All workshops</h1>
    <div class="grid">
      <article class="card">
        <img src="images/coding-1.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">HTML weekend</a></h2>
          <p>Build your first page.</p>
          <p class="price">Free</p>
        </div>
      </article>
      <article class="card">
        <img src="images/coding-2.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">CSS art</a></h2>
          <p>Draw with code.</p>
          <p class="price">Free</p>
        </div>
      </article>
      <article class="card">
        <img src="images/coding-3.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Scratch games</a></h2>
          <p>Ages 10 to 13.</p>
          <p class="price">Free</p>
        </div>
      </article>
      <article class="card">
        <img src="images/coding-4.jpg" alt="" width="600"
height="400">
        <div class="body">
          <h2><a href="#">Hackathon</a></h2>
          <p>48 hours, teams of four.</p>
          <p class="price">Free</p>
        </div>
```

```
      </article>
    </div>
  </main>
</body>
</html>
```

Project 925: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 70rem; margin: 2rem auto; padding: 0 1rem; }
.grid { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fill, minmax(15rem, 1fr)); }
.card { display: flex; flex-direction: column; border: 1px solid var(-
-line); border-radius: 14px; overflow: hidden; background: #fff;
position: relative; transition: box-shadow .2s, translate .2s; }
.card:hover { box-shadow: 0 12px 30px rgb(0 0 0 / 12%); translate: 0 -
3px; }
.card img { width: 100%; height: auto; aspect-ratio: 3 / 2; object-
fit: cover; }
.body { padding: 1rem 1.25rem; display: flex; flex-direction: column;
flex: 1; }
h2 { font-size: 1.1rem; margin: 0 0 .3rem; }
h2 a { color: inherit; text-decoration: none; }
h2 a::after { content: ""; position: absolute; inset: 0; }   /* whole
card clickable */
.body p { margin: 0 0 .5rem; color: var(--muted); }
.price { margin-top: auto !important; color: var(--brand); font-
weight: 700; }
```

Project 925 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - All workshops</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
All workshops	The main heading; only one per page.
	Generic block container for grouping and layout.
<article class="card">	A self-contained piece: card, post, product.
<img src="images/coding-1.jpg" alt="" width="600" height="400">	An image; alt describes it, width and height reserve space before it loads.
HTML weekend	Second-level heading for a section.
Build your first page.	A paragraph of text.
CSS art	A hyperlink; href gives the destination.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 70rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fill, minmax(15rem, 1fr));	Defines the columns of the grid.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-direction: column;	Stacks flex items vertically.

Declaration	What it does
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 14px;	Rounds the corners.
overflow: hidden;	Clips content that sticks out, so images follow rounded corners.
background: #fff;	Background colour or image.
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
transition: box-shadow .2s, translate .2s;	Soft shadow that lifts the element from the page.
.card:hover {	Applies while the pointer is over the element.
translate: 0 -3px;	Moves the element without affecting the layout of others.
width: 100%;	Fills the container width.
height: auto;	Keeps the natural height, preserving image proportions.
aspect-ratio: 3 / 2;	Keeps a fixed width-to-height ratio, reserving space before media loads.
object-fit: cover;	Crops an image to fill its box while keeping its proportions.
flex: 1;	All items share free space equally.
font-size: 1.1rem;	Size of the text.
text-decoration: none;	Removes the underline from links.
h2 a::after {	Generated content inserted after the element's content.
content: "";	The text or empty string for a pseudo-element.

Declaration	What it does
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
inset: 0;	Shorthand for top, right, bottom and left all zero: stretches over the parent.
font-weight: 700;	Thickness of the text.

Check your work

- Only one link per card (screen readers)
- Cards equal height in a row
- Price aligned at bottom
- Hover does not shift layout

Exercises

1. Add a filter bar with radio buttons and :has().
2. Add a 'new' badge.
3. Add a sort dropdown with JavaScript.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Light and dark theme switcher

Level 3 | 25 projects, one per theme

Support the system colour scheme automatically and add a manual switch that sets a data attribute on the html element, all driven by custom properties.

Project 926: Light and dark theme switcher for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 3 | Files: index.html, styles.css

Brief

Support the system colour scheme automatically and add a manual switch that sets a data attribute on the html element, all driven by custom properties.

Learning goals

- Use prefers-color-scheme and color-scheme
- Theme with custom properties
- Override with a data attribute set by a few lines of JavaScript

Elements and CSS used

HTML elements	CSS features
fieldset, legend, label, input type=radio, section, script	custom properties, @media (prefers-color-scheme), [data-theme], color-scheme, transition

Build guide

1. Define light variables in :root and dark ones inside a prefers-color-scheme media query.
2. Add [data-theme] overrides.
3. Use the variables for background, colour and cards.
4. Add the radio group.

5. Add the script that copies the chosen value to html's data-theme.
6. Test with your OS in dark mode.

Project 926: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Themes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cairo Book Shop</h1>
    <p>This page follows your system theme and also lets you choose
one.</p>
    <fieldset class="theme">
      <legend>Theme</legend>
      <label><input type="radio" name="theme" value="auto" checked>
Auto</label>
      <label><input type="radio" name="theme" value="light"> Light</
label>
      <label><input type="radio" name="theme" value="dark"> Dark</
label>
    </fieldset>
    <section class="card">
      <h2>Learn HTML</h2>
      <p>From your first tag to a complete page. <a href="#">Read
more</a></p>
    </section>
  </main>
  <script>
    document.querySelectorAll('input[name=theme]').forEach(r => r.
addEventListener('change', e => {
      document.documentElement.dataset.theme = e.target.value;
    }));
  </script>
</body>
</html>
```

Project 926: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
:root { color-scheme: light dark; --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; }
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg:
```

```
#e5e7eb; --card: #1f2937; } }
:root[data-theme="light"] { --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; color-scheme: light; }
:root[data-theme="dark"]  { --bg: #111827; --fg: #e5e7eb; --card:
#1f2937; color-scheme: dark; }
body { background: var(--bg); color: var(--fg); transition:
background .3s, color .3s; }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.theme { display: flex; gap: 1rem; border: 1px solid var(--line);
border-radius: 10px; }
.card { background: var(--card); padding: 1.25rem; border-radius:
12px; margin-top: 1.5rem; }
a { color: var(--brand); }
```

Project 926 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - Themes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cairo Book Shop	The main heading; only one per page.
<p>This page follows your system theme and also lets you choose one...	A paragraph of text.
<fieldset class="theme">	Groups related form controls.
<legend>Theme</legend>	Caption for the fieldset.
<label><input type="radio" name="theme" value="auto" checked> Auto<...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="theme" value="light"> Light</label>	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="theme" value="dark"> Dark</label>	A form control; its type decides what it looks like.
<section class="card">	A thematic group of content, normally with its own heading.
Learn HTML	Second-level heading for a section.
<p>From your first tag to a complete page. <a href="#">Read more</a...	A hyperlink; href gives the destination.
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
color-scheme: light dark;	Tells the browser which colour schemes the page supports so native controls match.
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg: ...	Applies when the user's system is in dark mode.
:root[data-theme="light"] {	Attribute selector on a data attribute set by JavaScript.
background: var(--bg);	Background colour or image.
transition: background .3s, color .3s;	Animates property changes smoothly, for example on hover.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
border-radius: 12px;	The line around the element: width, style and colour.

Check your work

- Follows system setting by default
- Manual choice overrides
- Form controls also switch (color-scheme)
- Contrast good in both themes

Exercises

1. Remember the choice in localStorage.
2. Add a high-contrast theme.
3. Animate the switch with a view transition.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 927: Light and dark theme switcher for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 3 | Files: index.html, styles.css

Brief

Support the system colour scheme automatically and add a manual switch that sets a data attribute on the html element, all driven by custom properties.

Learning goals

- Use prefers-color-scheme and color-scheme
- Theme with custom properties
- Override with a data attribute set by a few lines of JavaScript

Elements and CSS used

HTML elements	CSS features
fieldset, legend, label, input type=radio, section, script	custom properties, @media (prefers-color-scheme), [data-theme], color-scheme, transition

Build guide

1. Define light variables in :root and dark ones inside a prefers-color-scheme media query.
2. Add [data-theme] overrides.
3. Use the variables for background, colour and cards.
4. Add the radio group.
5. Add the script that copies the chosen value to html's data-theme.

6. Test with your OS in dark mode.

Project 927: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - Themes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Nile Bakery</h1>
    <p>This page follows your system theme and also lets you choose
one.</p>
    <fieldset class="theme">
      <legend>Theme</legend>
      <label><input type="radio" name="theme" value="auto" checked>
Auto</label>
      <label><input type="radio" name="theme" value="light"> Light</
label>
      <label><input type="radio" name="theme" value="dark"> Dark</
label>
    </fieldset>
    <section class="card">
      <h2>Sourdough loaf</h2>
      <p>Slow fermented, crisp crust. <a href="#">Read more</a></p>
    </section>
  </main>
  <script>
    document.querySelectorAll('input[name=theme]').forEach(r => r.
addEventListener('change', e => {
      document.documentElement.dataset.theme = e.target.value;
    }));
  </script>
</body>
</html>
```

Project 927: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
:root { color-scheme: light dark; --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; }
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg:
#e5e7eb; --card: #1f2937; } }
```

```
:root[data-theme="light"] { --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; color-scheme: light; }
:root[data-theme="dark"]  { --bg: #111827; --fg: #e5e7eb; --card:
#1f2937; color-scheme: dark; }
body { background: var(--bg); color: var(--fg); transition:
background .3s, color .3s; }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.theme { display: flex; gap: 1rem; border: 1px solid var(--line);
border-radius: 10px; }
.card { background: var(--card); padding: 1.25rem; border-radius:
12px; margin-top: 1.5rem; }
a { color: var(--brand); }
```

Project 927 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - Themes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Nile Bakery	The main heading; only one per page.
<p>This page follows your system theme and also lets you choose one...	A paragraph of text.
<fieldset class="theme">	Groups related form controls.
<legend>Theme</legend>	Caption for the fieldset.
<label><input type="radio" name="theme" value="auto" checked> Auto<...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="theme" value="light"> Light</label>	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="theme" value="dark"> Dark</label>	A form control; its type decides what it looks like.
<section class="card">	A thematic group of content, normally with its own heading.
Sourdough loaf	Second-level heading for a section.
Slow fermented, crisp crust. Read more	A hyperlink; href gives the destination.
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
color-scheme: light dark;	Tells the browser which colour schemes the page supports so native controls match.
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg: ...	Applies when the user's system is in dark mode.
:root[data-theme="light"] {	Attribute selector on a data attribute set by JavaScript.
background: var(--bg);	Background colour or image.
transition: background .3s, color .3s;	Animates property changes smoothly, for example on hover.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
border-radius: 12px;	The line around the element: width, style and colour.

Check your work

- Follows system setting by default
- Manual choice overrides
- Form controls also switch (color-scheme)
- Contrast good in both themes

Exercises

1. Remember the choice in localStorage.
2. Add a high-contrast theme.
3. Animate the switch with a view transition.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 928: Light and dark theme switcher for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 3 | Files: index.html, styles.css

Brief

Support the system colour scheme automatically and add a manual switch that sets a data attribute on the html element, all driven by custom properties.

Learning goals

- Use prefers-color-scheme and color-scheme
- Theme with custom properties
- Override with a data attribute set by a few lines of JavaScript

Elements and CSS used

HTML elements	CSS features
fieldset, legend, label, input type=radio, section, script	custom properties, @media (prefers-color-scheme), [data-theme], color-scheme, transition

Build guide

1. Define light variables in :root and dark ones inside a prefers-color-scheme media query.
2. Add [data-theme] overrides.
3. Use the variables for background, colour and cards.
4. Add the radio group.

5. Add the script that copies the chosen value to html's data-theme.
6. Test with your OS in dark mode.

Project 928: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - Themes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Pyramid Fitness</h1>
    <p>This page follows your system theme and also lets you choose
one.</p>
    <fieldset class="theme">
      <legend>Theme</legend>
      <label><input type="radio" name="theme" value="auto" checked>
Auto</label>
      <label><input type="radio" name="theme" value="light"> Light</
label>
      <label><input type="radio" name="theme" value="dark"> Dark</
label>
    </fieldset>
    <section class="card">
      <h2>Morning yoga</h2>
      <p>Flexibility and calm, 60 minutes. <a href="#">Read more</a></
p>
    </section>
  </main>
  <script>
    document.querySelectorAll('input[name=theme]').forEach(r => r.
addEventListener('change', e => {
      document.documentElement.dataset.theme = e.target.value;
    }));
  </script>
</body>
</html>
```

Project 928: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
:root { color-scheme: light dark; --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; }
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg:
```

```
#e5e7eb; --card: #1f2937; } }
:root[data-theme="light"] { --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; color-scheme: light; }
:root[data-theme="dark"]  { --bg: #111827; --fg: #e5e7eb; --card:
#1f2937; color-scheme: dark; }
body { background: var(--bg); color: var(--fg); transition:
background .3s, color .3s; }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.theme { display: flex; gap: 1rem; border: 1px solid var(--line);
border-radius: 10px; }
.card { background: var(--card); padding: 1.25rem; border-radius:
12px; margin-top: 1.5rem; }
a { color: var(--brand); }
```

Project 928 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - Themes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Pyramid Fitness	The main heading; only one per page.
<p>This page follows your system theme and also lets you choose one...	A paragraph of text.
<fieldset class="theme">	Groups related form controls.
<legend>Theme</legend>	Caption for the fieldset.
<label><input type="radio" name="theme" value="auto" checked> Auto<...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="theme" value="light"> Light</label>	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="theme" value="dark"> Dark</label>	A form control; its type decides what it looks like.
<section class="card">	A thematic group of content, normally with its own heading.
Morning yoga	Second-level heading for a section.
Flexibility and calm, 60 minutes. Read more	A hyperlink; href gives the destination.
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
color-scheme: light dark;	Tells the browser which colour schemes the page supports so native controls match.
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg: ...	Applies when the user's system is in dark mode.
:root[data-theme="light"] {	Attribute selector on a data attribute set by JavaScript.
background: var(--bg);	Background colour or image.
transition: background .3s, color .3s;	Animates property changes smoothly, for example on hover.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
border-radius: 12px;	The line around the element: width, style and colour.

Check your work

- Follows system setting by default
- Manual choice overrides
- Form controls also switch (color-scheme)
- Contrast good in both themes

Exercises

1. Remember the choice in localStorage.
2. Add a high-contrast theme.
3. Animate the switch with a view transition.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 929: Light and dark theme switcher for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 3 | Files: index.html, styles.css

Brief

Support the system colour scheme automatically and add a manual switch that sets a data attribute on the html element, all driven by custom properties.

Learning goals

- Use prefers-color-scheme and color-scheme
- Theme with custom properties
- Override with a data attribute set by a few lines of JavaScript

Elements and CSS used

HTML elements	CSS features
fieldset, legend, label, input type=radio, section, script	custom properties, @media (prefers-color-scheme), [data-theme], color-scheme, transition

Build guide

1. Define light variables in :root and dark ones inside a prefers-color-scheme media query.
2. Add [data-theme] overrides.
3. Use the variables for background, colour and cards.
4. Add the radio group.

5. Add the script that copies the chosen value to html's data-theme.
6. Test with your OS in dark mode.

Project 929: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - Themes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Delta Dental Clinic</h1>
    <p>This page follows your system theme and also lets you choose
one.</p>
    <fieldset class="theme">
      <legend>Theme</legend>
      <label><input type="radio" name="theme" value="auto" checked>
Auto</label>
      <label><input type="radio" name="theme" value="light"> Light</
label>
      <label><input type="radio" name="theme" value="dark"> Dark</
label>
    </fieldset>
    <section class="card">
      <h2>Check-up</h2>
      <p>Examination and cleaning. <a href="#">Read more</a></p>
    </section>
  </main>
  <script>
    document.querySelectorAll('input[name=theme]').forEach(r => r.
addEventListener('change', e => {
      document.documentElement.dataset.theme = e.target.value;
    }));
  </script>
</body>
</html>
```

Project 929: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
:root { color-scheme: light dark; --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; }
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg:
#e5e7eb; --card: #1f2937; } }
```

```
:root[data-theme="light"] { --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; color-scheme: light; }
:root[data-theme="dark"]  { --bg: #111827; --fg: #e5e7eb; --card:
#1f2937; color-scheme: dark; }
body { background: var(--bg); color: var(--fg); transition:
background .3s, color .3s; }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.theme { display: flex; gap: 1rem; border: 1px solid var(--line);
border-radius: 10px; }
.card { background: var(--card); padding: 1.25rem; border-radius:
12px; margin-top: 1.5rem; }
a { color: var(--brand); }
```

Project 929 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - Themes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Delta Dental Clinic	The main heading; only one per page.
<p>This page follows your system theme and also lets you choose one...	A paragraph of text.
<fieldset class="theme">	Groups related form controls.
<legend>Theme</legend>	Caption for the fieldset.
<label><input type="radio" name="theme" value="auto" checked> Auto<...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="theme" value="light"> Light</label>	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="theme" value="dark"> Dark</label>	A form control; its type decides what it looks like.
<section class="card">	A thematic group of content, normally with its own heading.
Check-up	Second-level heading for a section.
Examination and cleaning. Read more	A hyperlink; href gives the destination.
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
color-scheme: light dark;	Tells the browser which colour schemes the page supports so native controls match.
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg: ...	Applies when the user's system is in dark mode.
:root[data-theme="light"] {	Attribute selector on a data attribute set by JavaScript.
background: var(--bg);	Background colour or image.
transition: background .3s, color .3s;	Animates property changes smoothly, for example on hover.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
border-radius: 12px;	The line around the element: width, style and colour.

Check your work

- Follows system setting by default
- Manual choice overrides
- Form controls also switch (color-scheme)
- Contrast good in both themes

Exercises

1. Remember the choice in localStorage.
2. Add a high-contrast theme.
3. Animate the switch with a view transition.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 930: Light and dark theme switcher for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 3 | Files: index.html, styles.css

Brief

Support the system colour scheme automatically and add a manual switch that sets a data attribute on the html element, all driven by custom properties.

Learning goals

- Use prefers-color-scheme and color-scheme
- Theme with custom properties
- Override with a data attribute set by a few lines of JavaScript

Elements and CSS used

HTML elements	CSS features
fieldset, legend, label, input type=radio, section, script	custom properties, @media (prefers-color-scheme), [data-theme], color-scheme, transition

Build guide

1. Define light variables in :root and dark ones inside a prefers-color-scheme media query.
2. Add [data-theme] overrides.
3. Use the variables for background, colour and cards.
4. Add the radio group.

5. Add the script that copies the chosen value to html's data-theme.
6. Test with your OS in dark mode.

Project 930: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - Themes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Red Sea Travel</h1>
    <p>This page follows your system theme and also lets you choose
one.</p>
    <fieldset class="theme">
      <legend>Theme</legend>
      <label><input type="radio" name="theme" value="auto" checked>
Auto</label>
      <label><input type="radio" name="theme" value="light"> Light</
label>
      <label><input type="radio" name="theme" value="dark"> Dark</
label>
    </fieldset>
    <section class="card">
      <h2>Luxor day trip</h2>
      <p>Karnak, Valley of the Kings. <a href="#">Read more</a></p>
    </section>
  </main>
  <script>
    document.querySelectorAll('input[name=theme]').forEach(r => r.
addEventListener('change', e => {
      document.documentElement.dataset.theme = e.target.value;
    }));
  </script>
</body>
</html>
```

Project 930: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
:root { color-scheme: light dark; --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; }
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg:
#e5e7eb; --card: #1f2937; } }
```

```
:root[data-theme="light"] { --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; color-scheme: light; }
:root[data-theme="dark"]  { --bg: #111827; --fg: #e5e7eb; --card:
#1f2937; color-scheme: dark; }
body { background: var(--bg); color: var(--fg); transition:
background .3s, color .3s; }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.theme { display: flex; gap: 1rem; border: 1px solid var(--line);
border-radius: 10px; }
.card { background: var(--card); padding: 1.25rem; border-radius:
12px; margin-top: 1.5rem; }
a { color: var(--brand); }
```

Project 930 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - Themes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Red Sea Travel	The main heading; only one per page.
<p>This page follows your system theme and also lets you choose one...	A paragraph of text.
<fieldset class="theme">	Groups related form controls.
<legend>Theme</legend>	Caption for the fieldset.
<label><input type="radio" name="theme" value="auto" checked> Auto<...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="theme" value="light"> Light</label>	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="theme" value="dark"> Dark</label>	A form control; its type decides what it looks like.
<section class="card">	A thematic group of content, normally with its own heading.
Luxor day trip	Second-level heading for a section.
Karnak, Valley of the Kings. Read more	A hyperlink; href gives the destination.
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
color-scheme: light dark;	Tells the browser which colour schemes the page supports so native controls match.
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg: ...	Applies when the user's system is in dark mode.
:root[data-theme="light"] {	Attribute selector on a data attribute set by JavaScript.
background: var(--bg);	Background colour or image.
transition: background .3s, color .3s;	Animates property changes smoothly, for example on hover.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
border-radius: 12px;	The line around the element: width, style and colour.

Check your work

- Follows system setting by default
- Manual choice overrides
- Form controls also switch (color-scheme)
- Contrast good in both themes

Exercises

1. Remember the choice in localStorage.
2. Add a high-contrast theme.
3. Animate the switch with a view transition.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 931: Light and dark theme switcher for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 3 | Files: index.html, styles.css

Brief

Support the system colour scheme automatically and add a manual switch that sets a data attribute on the html element, all driven by custom properties.

Learning goals

- Use prefers-color-scheme and color-scheme
- Theme with custom properties
- Override with a data attribute set by a few lines of JavaScript

Elements and CSS used

HTML elements	CSS features
fieldset, legend, label, input type=radio, section, script	custom properties, @media (prefers-color-scheme), [data-theme], color-scheme, transition

Build guide

1. Define light variables in :root and dark ones inside a prefers-color-scheme media query.
2. Add [data-theme] overrides.
3. Use the variables for background, colour and cards.
4. Add the radio group.

5. Add the script that copies the chosen value to html's data-theme.
6. Test with your OS in dark mode.

Project 931: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - Themes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Lotus Language School</h1>
    <p>This page follows your system theme and also lets you choose
one.</p>
    <fieldset class="theme">
      <legend>Theme</legend>
      <label><input type="radio" name="theme" value="auto" checked>
Auto</label>
      <label><input type="radio" name="theme" value="light"> Light</
label>
      <label><input type="radio" name="theme" value="dark"> Dark</
label>
    </fieldset>
    <section class="card">
      <h2>English A1</h2>
      <p>Beginner, 8 weeks. <a href="#">Read more</a></p>
    </section>
  </main>
  <script>
    document.querySelectorAll('input[name=theme]').forEach(r => r.
addEventListener('change', e => {
      document.documentElement.dataset.theme = e.target.value;
    }));
  </script>
</body>
</html>
```

Project 931: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
:root { color-scheme: light dark; --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; }
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg:
#e5e7eb; --card: #1f2937; } }
```

```
:root[data-theme="light"] { --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; color-scheme: light; }
:root[data-theme="dark"]  { --bg: #111827; --fg: #e5e7eb; --card:
#1f2937; color-scheme: dark; }
body { background: var(--bg); color: var(--fg); transition:
background .3s, color .3s; }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.theme { display: flex; gap: 1rem; border: 1px solid var(--line);
border-radius: 10px; }
.card { background: var(--card); padding: 1.25rem; border-radius:
12px; margin-top: 1.5rem; }
a { color: var(--brand); }
```

Project 931 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - Themes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Lotus Language School	The main heading; only one per page.
<p>This page follows your system theme and also lets you choose one...	A paragraph of text.
<fieldset class="theme">	Groups related form controls.
<legend>Theme</legend>	Caption for the fieldset.
<label><input type="radio" name="theme" value="auto" checked> Auto<...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="theme" value="light"> Light</label>	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="theme" value="dark"> Dark</label>	A form control; its type decides what it looks like.
<section class="card">	A thematic group of content, normally with its own heading.
English A1	Second-level heading for a section.
Beginner, 8 weeks. Read more	A hyperlink; href gives the destination.
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
color-scheme: light dark;	Tells the browser which colour schemes the page supports so native controls match.
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg: ...	Applies when the user's system is in dark mode.
:root[data-theme="light"] {	Attribute selector on a data attribute set by JavaScript.
background: var(--bg);	Background colour or image.
transition: background .3s, color .3s;	Animates property changes smoothly, for example on hover.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
border-radius: 12px;	The line around the element: width, style and colour.

Check your work

- Follows system setting by default
- Manual choice overrides
- Form controls also switch (color-scheme)
- Contrast good in both themes

Exercises

1. Remember the choice in localStorage.
2. Add a high-contrast theme.
3. Animate the switch with a view transition.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 932: Light and dark theme switcher for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 3 | Files: index.html, styles.css

Brief

Support the system colour scheme automatically and add a manual switch that sets a data attribute on the html element, all driven by custom properties.

Learning goals

- Use prefers-color-scheme and color-scheme
- Theme with custom properties
- Override with a data attribute set by a few lines of JavaScript

Elements and CSS used

HTML elements	CSS features
fieldset, legend, label, input type=radio, section, script	custom properties, @media (prefers-color-scheme), [data-theme], color-scheme, transition

Build guide

1. Define light variables in :root and dark ones inside a prefers-color-scheme media query.
2. Add [data-theme] overrides.
3. Use the variables for background, colour and cards.
4. Add the radio group.

5. Add the script that copies the chosen value to html's data-theme.
6. Test with your OS in dark mode.

Project 932: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - Themes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Green Leaf Cafe</h1>
    <p>This page follows your system theme and also lets you choose
one.</p>
    <fieldset class="theme">
      <legend>Theme</legend>
      <label><input type="radio" name="theme" value="auto" checked>
Auto</label>
      <label><input type="radio" name="theme" value="light"> Light</
label>
      <label><input type="radio" name="theme" value="dark"> Dark</
label>
    </fieldset>
    <section class="card">
      <h2>Flat white</h2>
      <p>Double shot, silky milk. <a href="#">Read more</a></p>
    </section>
  </main>
  <script>
    document.querySelectorAll('input[name=theme]').forEach(r => r.
addEventListener('change', e => {
      document.documentElement.dataset.theme = e.target.value;
    }));
  </script>
</body>
</html>
```

Project 932: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
:root { color-scheme: light dark; --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; }
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg:
#e5e7eb; --card: #1f2937; } }
```

```
:root[data-theme="light"] { --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; color-scheme: light; }
:root[data-theme="dark"]  { --bg: #111827; --fg: #e5e7eb; --card:
#1f2937; color-scheme: dark; }
body { background: var(--bg); color: var(--fg); transition:
background .3s, color .3s; }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.theme { display: flex; gap: 1rem; border: 1px solid var(--line);
border-radius: 10px; }
.card { background: var(--card); padding: 1.25rem; border-radius:
12px; margin-top: 1.5rem; }
a { color: var(--brand); }
```

Project 932 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - Themes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Green Leaf Cafe	The main heading; only one per page.
<p>This page follows your system theme and also lets you choose one...	A paragraph of text.
<fieldset class="theme">	Groups related form controls.
<legend>Theme</legend>	Caption for the fieldset.
<label><input type="radio" name="theme" value="auto" checked> Auto<...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="theme" value="light"> Light</label>	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="theme" value="dark"> Dark</label>	A form control; its type decides what it looks like.
<section class="card">	A thematic group of content, normally with its own heading.
Flat white	Second-level heading for a section.
Double shot, silky milk. Read more	A hyperlink; href gives the destination.
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
color-scheme: light dark;	Tells the browser which colour schemes the page supports so native controls match.
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg: ...	Applies when the user's system is in dark mode.
:root[data-theme="light"] {	Attribute selector on a data attribute set by JavaScript.
background: var(--bg);	Background colour or image.
transition: background .3s, color .3s;	Animates property changes smoothly, for example on hover.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
border-radius: 12px;	The line around the element: width, style and colour.

Check your work

- Follows system setting by default
- Manual choice overrides
- Form controls also switch (color-scheme)
- Contrast good in both themes

Exercises

1. Remember the choice in localStorage.
2. Add a high-contrast theme.
3. Animate the switch with a view transition.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 933: Light and dark theme switcher for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 3 | Files: index.html, styles.css

Brief

Support the system colour scheme automatically and add a manual switch that sets a data attribute on the html element, all driven by custom properties.

Learning goals

- Use prefers-color-scheme and color-scheme
- Theme with custom properties
- Override with a data attribute set by a few lines of JavaScript

Elements and CSS used

HTML elements	CSS features
fieldset, legend, label, input type=radio, section, script	custom properties, @media (prefers-color-scheme), [data-theme], color-scheme, transition

Build guide

1. Define light variables in :root and dark ones inside a prefers-color-scheme media query.
2. Add [data-theme] overrides.
3. Use the variables for background, colour and cards.
4. Add the radio group.

5. Add the script that copies the chosen value to html's data-theme.
6. Test with your OS in dark mode.

Project 933: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - Themes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Sinai Trekking Club</h1>
    <p>This page follows your system theme and also lets you choose
one.</p>
    <fieldset class="theme">
      <legend>Theme</legend>
      <label><input type="radio" name="theme" value="auto" checked>
Auto</label>
      <label><input type="radio" name="theme" value="light"> Light</
label>
      <label><input type="radio" name="theme" value="dark"> Dark</
label>
    </fieldset>
    <section class="card">
      <h2>Mount Sinai sunrise</h2>
      <p>Night climb, 7 km. <a href="#">Read more</a></p>
    </section>
  </main>
  <script>
    document.querySelectorAll('input[name=theme]').forEach(r => r.
addEventListener('change', e => {
      document.documentElement.dataset.theme = e.target.value;
    }));
  </script>
</body>
</html>
```

Project 933: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
:root { color-scheme: light dark; --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; }
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg:
#e5e7eb; --card: #1f2937; } }
```

```
:root[data-theme="light"] { --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; color-scheme: light; }
:root[data-theme="dark"]  { --bg: #111827; --fg: #e5e7eb; --card:
#1f2937; color-scheme: dark; }
body { background: var(--bg); color: var(--fg); transition:
background .3s, color .3s; }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.theme { display: flex; gap: 1rem; border: 1px solid var(--line);
border-radius: 10px; }
.card { background: var(--card); padding: 1.25rem; border-radius:
12px; margin-top: 1.5rem; }
a { color: var(--brand); }
```

Project 933 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - Themes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Sinai Trekking Club	The main heading; only one per page.
<p>This page follows your system theme and also lets you choose one...	A paragraph of text.
<fieldset class="theme">	Groups related form controls.
<legend>Theme</legend>	Caption for the fieldset.
<label><input type="radio" name="theme" value="auto" checked> Auto<...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="theme" value="light"> Light</label>	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="theme" value="dark"> Dark</label>	A form control; its type decides what it looks like.
<section class="card">	A thematic group of content, normally with its own heading.
Mount Sinai sunrise	Second-level heading for a section.
Night climb, 7 km. Read more	A hyperlink; href gives the destination.
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
color-scheme: light dark;	Tells the browser which colour schemes the page supports so native controls match.
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg: ...	Applies when the user's system is in dark mode.
:root[data-theme="light"] {	Attribute selector on a data attribute set by JavaScript.
background: var(--bg);	Background colour or image.
transition: background .3s, color .3s;	Animates property changes smoothly, for example on hover.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
border-radius: 12px;	The line around the element: width, style and colour.

Check your work

- Follows system setting by default
- Manual choice overrides
- Form controls also switch (color-scheme)
- Contrast good in both themes

Exercises

1. Remember the choice in localStorage.
2. Add a high-contrast theme.
3. Animate the switch with a view transition.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 934: Light and dark theme switcher for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 3 | Files: index.html, styles.css

Brief

Support the system colour scheme automatically and add a manual switch that sets a data attribute on the html element, all driven by custom properties.

Learning goals

- Use prefers-color-scheme and color-scheme
- Theme with custom properties
- Override with a data attribute set by a few lines of JavaScript

Elements and CSS used

HTML elements	CSS features
fieldset, legend, label, input type=radio, section, script	custom properties, @media (prefers-color-scheme), [data-theme], color-scheme, transition

Build guide

1. Define light variables in :root and dark ones inside a prefers-color-scheme media query.
2. Add [data-theme] overrides.
3. Use the variables for background, colour and cards.
4. Add the radio group.

5. Add the script that copies the chosen value to html's data-theme.
6. Test with your OS in dark mode.

Project 934: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - Themes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Horizon Photography</h1>
    <p>This page follows your system theme and also lets you choose
one.</p>
    <fieldset class="theme">
      <legend>Theme</legend>
      <label><input type="radio" name="theme" value="auto" checked>
Auto</label>
      <label><input type="radio" name="theme" value="light"> Light</
label>
      <label><input type="radio" name="theme" value="dark"> Dark</
label>
    </fieldset>
    <section class="card">
      <h2>Portrait session</h2>
      <p>One hour, 20 edited photos. <a href="#">Read more</a></p>
    </section>
  </main>
  <script>
    document.querySelectorAll('input[name=theme]').forEach(r => r.
addEventListener('change', e => {
      document.documentElement.dataset.theme = e.target.value;
    }));
  </script>
</body>
</html>
```

Project 934: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
:root { color-scheme: light dark; --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; }
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg:
#e5e7eb; --card: #1f2937; } }
```

```
:root[data-theme="light"] { --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; color-scheme: light; }
:root[data-theme="dark"]  { --bg: #111827; --fg: #e5e7eb; --card:
#1f2937; color-scheme: dark; }
body { background: var(--bg); color: var(--fg); transition:
background .3s, color .3s; }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.theme { display: flex; gap: 1rem; border: 1px solid var(--line);
border-radius: 10px; }
.card { background: var(--card); padding: 1.25rem; border-radius:
12px; margin-top: 1.5rem; }
a { color: var(--brand); }
```

Project 934 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - Themes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Horizon Photography	The main heading; only one per page.
<p>This page follows your system theme and also lets you choose one...	A paragraph of text.
<fieldset class="theme">	Groups related form controls.
<legend>Theme</legend>	Caption for the fieldset.
<label><input type="radio" name="theme" value="auto" checked> Auto<...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="theme" value="light"> Light</label>	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="theme" value="dark"> Dark</label>	A form control; its type decides what it looks like.
<section class="card">	A thematic group of content, normally with its own heading.
Portrait session	Second-level heading for a section.
One hour, 20 edited photos. Read more	A hyperlink; href gives the destination.
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
color-scheme: light dark;	Tells the browser which colour schemes the page supports so native controls match.
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg: ...	Applies when the user's system is in dark mode.
:root[data-theme="light"] {	Attribute selector on a data attribute set by JavaScript.
background: var(--bg);	Background colour or image.
transition: background .3s, color .3s;	Animates property changes smoothly, for example on hover.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
border-radius: 12px;	The line around the element: width, style and colour.

Check your work

- Follows system setting by default
- Manual choice overrides
- Form controls also switch (color-scheme)
- Contrast good in both themes

Exercises

1. Remember the choice in localStorage.
2. Add a high-contrast theme.
3. Animate the switch with a view transition.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 935: Light and dark theme switcher for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 3 | Files: index.html, styles.css

Brief

Support the system colour scheme automatically and add a manual switch that sets a data attribute on the html element, all driven by custom properties.

Learning goals

- Use prefers-color-scheme and color-scheme
- Theme with custom properties
- Override with a data attribute set by a few lines of JavaScript

Elements and CSS used

HTML elements	CSS features
fieldset, legend, label, input type=radio, section, script	custom properties, @media (prefers-color-scheme), [data-theme], color-scheme, transition

Build guide

1. Define light variables in :root and dark ones inside a prefers-color-scheme media query.
2. Add [data-theme] overrides.
3. Use the variables for background, colour and cards.
4. Add the radio group.

5. Add the script that copies the chosen value to html's data-theme.
6. Test with your OS in dark mode.

Project 935: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - Themes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Papyrus Stationery</h1>
    <p>This page follows your system theme and also lets you choose
one.</p>
    <fieldset class="theme">
      <legend>Theme</legend>
      <label><input type="radio" name="theme" value="auto" checked>
Auto</label>
      <label><input type="radio" name="theme" value="light"> Light</
label>
      <label><input type="radio" name="theme" value="dark"> Dark</
label>
    </fieldset>
    <section class="card">
      <h2>Dotted notebook</h2>
      <p>A5, 160 pages. <a href="#">Read more</a></p>
    </section>
  </main>
  <script>
    document.querySelectorAll('input[name=theme]').forEach(r => r.
addEventListener('change', e => {
      document.documentElement.dataset.theme = e.target.value;
    }));
  </script>
</body>
</html>
```

Project 935: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
:root { color-scheme: light dark; --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; }
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg:
#e5e7eb; --card: #1f2937; } }
```

```
:root[data-theme="light"] { --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; color-scheme: light; }
:root[data-theme="dark"]  { --bg: #111827; --fg: #e5e7eb; --card:
#1f2937; color-scheme: dark; }
body { background: var(--bg); color: var(--fg); transition:
background .3s, color .3s; }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.theme { display: flex; gap: 1rem; border: 1px solid var(--line);
border-radius: 10px; }
.card { background: var(--card); padding: 1.25rem; border-radius:
12px; margin-top: 1.5rem; }
a { color: var(--brand); }
```

Project 935 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - Themes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Papyrus Stationery	The main heading; only one per page.
<p>This page follows your system theme and also lets you choose one...	A paragraph of text.
<fieldset class="theme">	Groups related form controls.
<legend>Theme</legend>	Caption for the fieldset.
<label><input type="radio" name="theme" value="auto" checked> Auto<...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="theme" value="light"> Light</label>	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="theme" value="dark"> Dark</label>	A form control; its type decides what it looks like.
<section class="card">	A thematic group of content, normally with its own heading.
Dotted notebook	Second-level heading for a section.
A5, 160 pages. Read more	A hyperlink; href gives the destination.
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
color-scheme: light dark;	Tells the browser which colour schemes the page supports so native controls match.
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg: ...	Applies when the user's system is in dark mode.
:root[data-theme="light"] {	Attribute selector on a data attribute set by JavaScript.
background: var(--bg);	Background colour or image.
transition: background .3s, color .3s;	Animates property changes smoothly, for example on hover.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
border-radius: 12px;	The line around the element: width, style and colour.

Check your work

- Follows system setting by default
- Manual choice overrides
- Form controls also switch (color-scheme)
- Contrast good in both themes

Exercises

1. Remember the choice in localStorage.
2. Add a high-contrast theme.
3. Animate the switch with a view transition.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 936: Light and dark theme switcher for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 3 | Files: index.html, styles.css

Brief

Support the system colour scheme automatically and add a manual switch that sets a data attribute on the html element, all driven by custom properties.

Learning goals

- Use prefers-color-scheme and color-scheme
- Theme with custom properties
- Override with a data attribute set by a few lines of JavaScript

Elements and CSS used

HTML elements	CSS features
fieldset, legend, label, input type=radio, section, script	custom properties, @media (prefers-color-scheme), [data-theme], color-scheme, transition

Build guide

1. Define light variables in :root and dark ones inside a prefers-color-scheme media query.
2. Add [data-theme] overrides.
3. Use the variables for background, colour and cards.
4. Add the radio group.

5. Add the script that copies the chosen value to html's data-theme.
6. Test with your OS in dark mode.

Project 936: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - Themes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Oasis Plant Nursery</h1>
    <p>This page follows your system theme and also lets you choose
one.</p>
    <fieldset class="theme">
      <legend>Theme</legend>
      <label><input type="radio" name="theme" value="auto" checked>
Auto</label>
      <label><input type="radio" name="theme" value="light"> Light</
label>
      <label><input type="radio" name="theme" value="dark"> Dark</
label>
    </fieldset>
    <section class="card">
      <h2>Monstera</h2>
      <p>Large leaves, easy care. <a href="#">Read more</a></p>
    </section>
  </main>
  <script>
    document.querySelectorAll('input[name=theme]').forEach(r => r.
addEventListener('change', e => {
      document.documentElement.dataset.theme = e.target.value;
    }));
  </script>
</body>
</html>
```

Project 936: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
:root { color-scheme: light dark; --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; }
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg:
#e5e7eb; --card: #1f2937; } }
```

```
:root[data-theme="light"] { --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; color-scheme: light; }
:root[data-theme="dark"]  { --bg: #111827; --fg: #e5e7eb; --card:
#1f2937; color-scheme: dark; }
body { background: var(--bg); color: var(--fg); transition:
background .3s, color .3s; }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.theme { display: flex; gap: 1rem; border: 1px solid var(--line);
border-radius: 10px; }
.card { background: var(--card); padding: 1.25rem; border-radius:
12px; margin-top: 1.5rem; }
a { color: var(--brand); }
```

Project 936 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - Themes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Oasis Plant Nursery	The main heading; only one per page.
<p>This page follows your system theme and also lets you choose one...	A paragraph of text.
<fieldset class="theme">	Groups related form controls.
<legend>Theme</legend>	Caption for the fieldset.
<label><input type="radio" name="theme" value="auto" checked> Auto<...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="theme" value="light"> Light</label>	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="theme" value="dark"> Dark</label>	A form control; its type decides what it looks like.
<section class="card">	A thematic group of content, normally with its own heading.
Monstera	Second-level heading for a section.
Large leaves, easy care. Read more	A hyperlink; href gives the destination.
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
color-scheme: light dark;	Tells the browser which colour schemes the page supports so native controls match.
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg: ...	Applies when the user's system is in dark mode.
:root[data-theme="light"] {	Attribute selector on a data attribute set by JavaScript.
background: var(--bg);	Background colour or image.
transition: background .3s, color .3s;	Animates property changes smoothly, for example on hover.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
border-radius: 12px;	The line around the element: width, style and colour.

Check your work

- Follows system setting by default
- Manual choice overrides
- Form controls also switch (color-scheme)
- Contrast good in both themes

Exercises

1. Remember the choice in localStorage.
2. Add a high-contrast theme.
3. Animate the switch with a view transition.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 937: Light and dark theme switcher for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 3 | Files: index.html, styles.css

Brief

Support the system colour scheme automatically and add a manual switch that sets a data attribute on the html element, all driven by custom properties.

Learning goals

- Use prefers-color-scheme and color-scheme
- Theme with custom properties
- Override with a data attribute set by a few lines of JavaScript

Elements and CSS used

HTML elements	CSS features
fieldset, legend, label, input type=radio, section, script	custom properties, @media (prefers-color-scheme), [data-theme], color-scheme, transition

Build guide

1. Define light variables in :root and dark ones inside a prefers-color-scheme media query.
2. Add [data-theme] overrides.
3. Use the variables for background, colour and cards.
4. Add the radio group.

5. Add the script that copies the chosen value to html's data-theme.
6. Test with your OS in dark mode.

Project 937: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - Themes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cedar Furniture</h1>
    <p>This page follows your system theme and also lets you choose
one.</p>
    <fieldset class="theme">
      <legend>Theme</legend>
      <label><input type="radio" name="theme" value="auto" checked>
Auto</label>
      <label><input type="radio" name="theme" value="light"> Light</
label>
      <label><input type="radio" name="theme" value="dark"> Dark</
label>
    </fieldset>
    <section class="card">
      <h2>Oak dining table</h2>
      <p>Seats six. <a href="#">Read more</a></p>
    </section>
  </main>
  <script>
    document.querySelectorAll('input[name=theme]').forEach(r => r.
addEventListener('change', e => {
      document.documentElement.dataset.theme = e.target.value;
    }));
  </script>
</body>
</html>
```

Project 937: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
:root { color-scheme: light dark; --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; }
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg:
#e5e7eb; --card: #1f2937; } }
```

```
:root[data-theme="light"] { --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; color-scheme: light; }
:root[data-theme="dark"]  { --bg: #111827; --fg: #e5e7eb; --card:
#1f2937; color-scheme: dark; }
body { background: var(--bg); color: var(--fg); transition:
background .3s, color .3s; }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.theme { display: flex; gap: 1rem; border: 1px solid var(--line);
border-radius: 10px; }
.card { background: var(--card); padding: 1.25rem; border-radius:
12px; margin-top: 1.5rem; }
a { color: var(--brand); }
```

Project 937 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - Themes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cedar Furniture	The main heading; only one per page.
<p>This page follows your system theme and also lets you choose one...	A paragraph of text.
<fieldset class="theme">	Groups related form controls.
<legend>Theme</legend>	Caption for the fieldset.
<label><input type="radio" name="theme" value="auto" checked> Auto<...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="theme" value="light"> Light</label>	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="theme" value="dark"> Dark</label>	A form control; its type decides what it looks like.
<section class="card">	A thematic group of content, normally with its own heading.
Oak dining table	Second-level heading for a section.
Seats six. Read more	A hyperlink; href gives the destination.
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
color-scheme: light dark;	Tells the browser which colour schemes the page supports so native controls match.
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg: ...	Applies when the user's system is in dark mode.
:root[data-theme="light"] {	Attribute selector on a data attribute set by JavaScript.
background: var(--bg);	Background colour or image.
transition: background .3s, color .3s;	Animates property changes smoothly, for example on hover.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
border-radius: 12px;	The line around the element: width, style and colour.

Check your work

- Follows system setting by default
- Manual choice overrides
- Form controls also switch (color-scheme)
- Contrast good in both themes

Exercises

1. Remember the choice in localStorage.
2. Add a high-contrast theme.
3. Animate the switch with a view transition.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 938: Light and dark theme switcher for Byte Repair

Theme: Byte Repair (Nasr City) | Level 3 | Files: index.html, styles.css

Brief

Support the system colour scheme automatically and add a manual switch that sets a data attribute on the html element, all driven by custom properties.

Learning goals

- Use prefers-color-scheme and color-scheme
- Theme with custom properties
- Override with a data attribute set by a few lines of JavaScript

Elements and CSS used

HTML elements	CSS features
fieldset, legend, label, input type=radio, section, script	custom properties, @media (prefers-color-scheme), [data-theme], color-scheme, transition

Build guide

1. Define light variables in :root and dark ones inside a prefers-color-scheme media query.
2. Add [data-theme] overrides.
3. Use the variables for background, colour and cards.
4. Add the radio group.
5. Add the script that copies the chosen value to html's data-theme.

6. Test with your OS in dark mode.

Project 938: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - Themes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Byte Repair</h1>
    <p>This page follows your system theme and also lets you choose
one.</p>
    <fieldset class="theme">
      <legend>Theme</legend>
      <label><input type="radio" name="theme" value="auto" checked>
Auto</label>
      <label><input type="radio" name="theme" value="light"> Light</
label>
      <label><input type="radio" name="theme" value="dark"> Dark</
label>
    </fieldset>
    <section class="card">
      <h2>Screen replacement</h2>
      <p>Most phones, 1 hour. <a href="#">Read more</a></p>
    </section>
  </main>
  <script>
    document.querySelectorAll('input[name=theme]').forEach(r => r.
addEventListener('change', e => {
      document.documentElement.dataset.theme = e.target.value;
    }));
  </script>
</body>
</html>
```

Project 938: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
:root { color-scheme: light dark; --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; }
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg:
#e5e7eb; --card: #1f2937; } }
```

```
:root[data-theme="light"] { --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; color-scheme: light; }
:root[data-theme="dark"]  { --bg: #111827; --fg: #e5e7eb; --card:
#1f2937; color-scheme: dark; }
body { background: var(--bg); color: var(--fg); transition:
background .3s, color .3s; }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.theme { display: flex; gap: 1rem; border: 1px solid var(--line);
border-radius: 10px; }
.card { background: var(--card); padding: 1.25rem; border-radius:
12px; margin-top: 1.5rem; }
a { color: var(--brand); }
```

Project 938 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - Themes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Byte Repair	The main heading; only one per page.
<p>This page follows your system theme and also lets you choose one...	A paragraph of text.
<fieldset class="theme">	Groups related form controls.
<legend>Theme</legend>	Caption for the fieldset.
<label><input type="radio" name="theme" value="auto" checked> Auto<...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="theme" value="light"> Light</label>	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="theme" value="dark"> Dark</label>	A form control; its type decides what it looks like.
<section class="card">	A thematic group of content, normally with its own heading.
Screen replacement	Second-level heading for a section.
Most phones, 1 hour. Read more	A hyperlink; href gives the destination.
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
color-scheme: light dark;	Tells the browser which colour schemes the page supports so native controls match.
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg: ...	Applies when the user's system is in dark mode.
:root[data-theme="light"] {	Attribute selector on a data attribute set by JavaScript.
background: var(--bg);	Background colour or image.
transition: background .3s, color .3s;	Animates property changes smoothly, for example on hover.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
border-radius: 12px;	The line around the element: width, style and colour.

Check your work

- Follows system setting by default
- Manual choice overrides
- Form controls also switch (color-scheme)
- Contrast good in both themes

Exercises

1. Remember the choice in localStorage.
2. Add a high-contrast theme.
3. Animate the switch with a view transition.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 939: Light and dark theme switcher for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 3 | Files: index.html, styles.css

Brief

Support the system colour scheme automatically and add a manual switch that sets a data attribute on the html element, all driven by custom properties.

Learning goals

- Use prefers-color-scheme and color-scheme
- Theme with custom properties
- Override with a data attribute set by a few lines of JavaScript

Elements and CSS used

HTML elements	CSS features
fieldset, legend, label, input type=radio, section, script	custom properties, @media (prefers-color-scheme), [data-theme], color-scheme, transition

Build guide

1. Define light variables in :root and dark ones inside a prefers-color-scheme media query.
2. Add [data-theme] overrides.
3. Use the variables for background, colour and cards.
4. Add the radio group.

5. Add the script that copies the chosen value to html's data-theme.
6. Test with your OS in dark mode.

Project 939: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - Themes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Sahara Pet Care</h1>
    <p>This page follows your system theme and also lets you choose
one.</p>
    <fieldset class="theme">
      <legend>Theme</legend>
      <label><input type="radio" name="theme" value="auto" checked>
Auto</label>
      <label><input type="radio" name="theme" value="light"> Light</
label>
      <label><input type="radio" name="theme" value="dark"> Dark</
label>
    </fieldset>
    <section class="card">
      <h2>Full grooming</h2>
      <p>Bath, cut and nails. <a href="#">Read more</a></p>
    </section>
  </main>
  <script>
    document.querySelectorAll('input[name=theme]').forEach(r => r.
addEventListener('change', e => {
      document.documentElement.dataset.theme = e.target.value;
    }));
  </script>
</body>
</html>
```

Project 939: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
:root { color-scheme: light dark; --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; }
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg:
#e5e7eb; --card: #1f2937; } }
```

```
:root[data-theme="light"] { --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; color-scheme: light; }
:root[data-theme="dark"]  { --bg: #111827; --fg: #e5e7eb; --card:
#1f2937; color-scheme: dark; }
body { background: var(--bg); color: var(--fg); transition:
background .3s, color .3s; }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.theme { display: flex; gap: 1rem; border: 1px solid var(--line);
border-radius: 10px; }
.card { background: var(--card); padding: 1.25rem; border-radius:
12px; margin-top: 1.5rem; }
a { color: var(--brand); }
```

Project 939 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - Themes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Sahara Pet Care	The main heading; only one per page.
<p>This page follows your system theme and also lets you choose one...	A paragraph of text.
<fieldset class="theme">	Groups related form controls.
<legend>Theme</legend>	Caption for the fieldset.
<label><input type="radio" name="theme" value="auto" checked> Auto<...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="theme" value="light"> Light</label>	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="theme" value="dark"> Dark</label>	A form control; its type decides what it looks like.
<section class="card">	A thematic group of content, normally with its own heading.
Full grooming	Second-level heading for a section.
Bath, cut and nails. Read more	A hyperlink; href gives the destination.
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
color-scheme: light dark;	Tells the browser which colour schemes the page supports so native controls match.
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg: ...	Applies when the user's system is in dark mode.
:root[data-theme="light"] {	Attribute selector on a data attribute set by JavaScript.
background: var(--bg);	Background colour or image.
transition: background .3s, color .3s;	Animates property changes smoothly, for example on hover.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
border-radius: 12px;	The line around the element: width, style and colour.

Check your work

- Follows system setting by default
- Manual choice overrides
- Form controls also switch (color-scheme)
- Contrast good in both themes

Exercises

1. Remember the choice in localStorage.
2. Add a high-contrast theme.
3. Animate the switch with a view transition.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 940: Light and dark theme switcher for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 3 | Files: index.html, styles.css

Brief

Support the system colour scheme automatically and add a manual switch that sets a data attribute on the html element, all driven by custom properties.

Learning goals

- Use prefers-color-scheme and color-scheme
- Theme with custom properties
- Override with a data attribute set by a few lines of JavaScript

Elements and CSS used

HTML elements	CSS features
fieldset, legend, label, input type=radio, section, script	custom properties, @media (prefers-color-scheme), [data-theme], color-scheme, transition

Build guide

1. Define light variables in :root and dark ones inside a prefers-color-scheme media query.
2. Add [data-theme] overrides.
3. Use the variables for background, colour and cards.
4. Add the radio group.

5. Add the script that copies the chosen value to html's data-theme.
6. Test with your OS in dark mode.

Project 940: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - Themes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Alexandria Sailing School</h1>
    <p>This page follows your system theme and also lets you choose
one.</p>
    <fieldset class="theme">
      <legend>Theme</legend>
      <label><input type="radio" name="theme" value="auto" checked>
Auto</label>
      <label><input type="radio" name="theme" value="light"> Light</
label>
      <label><input type="radio" name="theme" value="dark"> Dark</
label>
    </fieldset>
    <section class="card">
      <h2>Taster session</h2>
      <p>Two hours on the water. <a href="#">Read more</a></p>
    </section>
  </main>
  <script>
    document.querySelectorAll('input[name=theme]').forEach(r => r.
addEventListener('change', e => {
      document.documentElement.dataset.theme = e.target.value;
    }));
  </script>
</body>
</html>
```

Project 940: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
:root { color-scheme: light dark; --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; }
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg:
#e5e7eb; --card: #1f2937; } }
```

```
:root[data-theme="light"] { --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; color-scheme: light; }
:root[data-theme="dark"]  { --bg: #111827; --fg: #e5e7eb; --card:
#1f2937; color-scheme: dark; }
body { background: var(--bg); color: var(--fg); transition:
background .3s, color .3s; }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.theme { display: flex; gap: 1rem; border: 1px solid var(--line);
border-radius: 10px; }
.card { background: var(--card); padding: 1.25rem; border-radius:
12px; margin-top: 1.5rem; }
a { color: var(--brand); }
```

Project 940 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - Themes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Alexandria Sailing School	The main heading; only one per page.
<p>This page follows your system theme and also lets you choose one...	A paragraph of text.
<fieldset class="theme">	Groups related form controls.
<legend>Theme</legend>	Caption for the fieldset.
<label><input type="radio" name="theme" value="auto" checked> Auto<...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="theme" value="light"> Light</label>	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="theme" value="dark"> Dark</label>	A form control; its type decides what it looks like.
<section class="card">	A thematic group of content, normally with its own heading.
Taster session	Second-level heading for a section.
Two hours on the water. Read more	A hyperlink; href gives the destination.
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
color-scheme: light dark;	Tells the browser which colour schemes the page supports so native controls match.
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg: ...	Applies when the user's system is in dark mode.
:root[data-theme="light"] {	Attribute selector on a data attribute set by JavaScript.
background: var(--bg);	Background colour or image.
transition: background .3s, color .3s;	Animates property changes smoothly, for example on hover.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
border-radius: 12px;	The line around the element: width, style and colour.

Check your work

- Follows system setting by default
- Manual choice overrides
- Form controls also switch (color-scheme)
- Contrast good in both themes

Exercises

1. Remember the choice in localStorage.
2. Add a high-contrast theme.
3. Animate the switch with a view transition.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 941: Light and dark theme switcher for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 3 | Files: index.html, styles.css

Brief

Support the system colour scheme automatically and add a manual switch that sets a data attribute on the html element, all driven by custom properties.

Learning goals

- Use prefers-color-scheme and color-scheme
- Theme with custom properties
- Override with a data attribute set by a few lines of JavaScript

Elements and CSS used

HTML elements	CSS features
fieldset, legend, label, input type=radio, section, script	custom properties, @media (prefers-color-scheme), [data-theme], color-scheme, transition

Build guide

1. Define light variables in :root and dark ones inside a prefers-color-scheme media query.
2. Add [data-theme] overrides.
3. Use the variables for background, colour and cards.
4. Add the radio group.

5. Add the script that copies the chosen value to html's data-theme.
6. Test with your OS in dark mode.

Project 941: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - Themes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Habiba Handmade Jewellery</h1>
    <p>This page follows your system theme and also lets you choose
one.</p>
    <fieldset class="theme">
      <legend>Theme</legend>
      <label><input type="radio" name="theme" value="auto" checked>
Auto</label>
      <label><input type="radio" name="theme" value="light"> Light</
label>
      <label><input type="radio" name="theme" value="dark"> Dark</
label>
    </fieldset>
    <section class="card">
      <h2>Lotus pendant</h2>
      <p>Sterling silver. <a href="#">Read more</a></p>
    </section>
  </main>
  <script>
    document.querySelectorAll('input[name=theme]').forEach(r => r.
addEventListener('change', e => {
      document.documentElement.dataset.theme = e.target.value;
    }));
  </script>
</body>
</html>
```

Project 941: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
:root { color-scheme: light dark; --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; }
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg:
#e5e7eb; --card: #1f2937; } }
```

```
:root[data-theme="light"] { --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; color-scheme: light; }
:root[data-theme="dark"]  { --bg: #111827; --fg: #e5e7eb; --card:
#1f2937; color-scheme: dark; }
body { background: var(--bg); color: var(--fg); transition:
background .3s, color .3s; }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.theme { display: flex; gap: 1rem; border: 1px solid var(--line);
border-radius: 10px; }
.card { background: var(--card); padding: 1.25rem; border-radius:
12px; margin-top: 1.5rem; }
a { color: var(--brand); }
```

Project 941 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - Themes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Habiba Handmade Jewellery	The main heading; only one per page.
<p>This page follows your system theme and also lets you choose one...	A paragraph of text.
<fieldset class="theme">	Groups related form controls.
<legend>Theme</legend>	Caption for the fieldset.
<label><input type="radio" name="theme" value="auto" checked> Auto<...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="theme" value="light"> Light</label>	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="theme" value="dark"> Dark</label>	A form control; its type decides what it looks like.
<section class="card">	A thematic group of content, normally with its own heading.
Lotus pendant	Second-level heading for a section.
Sterling silver. Read more	A hyperlink; href gives the destination.
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
color-scheme: light dark;	Tells the browser which colour schemes the page supports so native controls match.
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg: ...	Applies when the user's system is in dark mode.
:root[data-theme="light"] {	Attribute selector on a data attribute set by JavaScript.
background: var(--bg);	Background colour or image.
transition: background .3s, color .3s;	Animates property changes smoothly, for example on hover.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
border-radius: 12px;	The line around the element: width, style and colour.

Check your work

- Follows system setting by default
- Manual choice overrides
- Form controls also switch (color-scheme)
- Contrast good in both themes

Exercises

1. Remember the choice in localStorage.
2. Add a high-contrast theme.
3. Animate the switch with a view transition.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 942: Light and dark theme switcher for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 3 | Files: index.html, styles.css

Brief

Support the system colour scheme automatically and add a manual switch that sets a data attribute on the html element, all driven by custom properties.

Learning goals

- Use prefers-color-scheme and color-scheme
- Theme with custom properties
- Override with a data attribute set by a few lines of JavaScript

Elements and CSS used

HTML elements	CSS features
fieldset, legend, label, input type=radio, section, script	custom properties, @media (prefers-color-scheme), [data-theme], color-scheme, transition

Build guide

1. Define light variables in :root and dark ones inside a prefers-color-scheme media query.
2. Add [data-theme] overrides.
3. Use the variables for background, colour and cards.
4. Add the radio group.

5. Add the script that copies the chosen value to html's data-theme.
6. Test with your OS in dark mode.

Project 942: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - Themes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Fayoum Pottery Studio</h1>
    <p>This page follows your system theme and also lets you choose
one.</p>
    <fieldset class="theme">
      <legend>Theme</legend>
      <label><input type="radio" name="theme" value="auto" checked>
Auto</label>
      <label><input type="radio" name="theme" value="light"> Light</
label>
      <label><input type="radio" name="theme" value="dark"> Dark</
label>
    </fieldset>
    <section class="card">
      <h2>Intro to the wheel</h2>
      <p>Three hours, take home a bowl. <a href="#">Read more</a></p>
    </section>
  </main>
  <script>
    document.querySelectorAll('input[name=theme]').forEach(r => r.
addEventListener('change', e => {
      document.documentElement.dataset.theme = e.target.value;
    }));
  </script>
</body>
</html>
```

Project 942: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
:root { color-scheme: light dark; --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; }
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg:
#e5e7eb; --card: #1f2937; } }
```

```
:root[data-theme="light"] { --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; color-scheme: light; }
:root[data-theme="dark"]  { --bg: #111827; --fg: #e5e7eb; --card:
#1f2937; color-scheme: dark; }
body { background: var(--bg); color: var(--fg); transition:
background .3s, color .3s; }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.theme { display: flex; gap: 1rem; border: 1px solid var(--line);
border-radius: 10px; }
.card { background: var(--card); padding: 1.25rem; border-radius:
12px; margin-top: 1.5rem; }
a { color: var(--brand); }
```

Project 942 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - Themes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Fayoum Pottery Studio	The main heading; only one per page.
<p>This page follows your system theme and also lets you choose one...	A paragraph of text.
<fieldset class="theme">	Groups related form controls.
<legend>Theme</legend>	Caption for the fieldset.
<label><input type="radio" name="theme" value="auto" checked> Auto<...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="theme" value="light"> Light</label>	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="theme" value="dark"> Dark</label>	A form control; its type decides what it looks like.
<section class="card">	A thematic group of content, normally with its own heading.
Intro to the wheel	Second-level heading for a section.
Three hours, take home a bowl. Read more	A hyperlink; href gives the destination.
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
color-scheme: light dark;	Tells the browser which colour schemes the page supports so native controls match.
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg: ...	Applies when the user's system is in dark mode.
:root[data-theme="light"] {	Attribute selector on a data attribute set by JavaScript.
background: var(--bg);	Background colour or image.
transition: background .3s, color .3s;	Animates property changes smoothly, for example on hover.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
border-radius: 12px;	The line around the element: width, style and colour.

Check your work

- Follows system setting by default
- Manual choice overrides
- Form controls also switch (color-scheme)
- Contrast good in both themes

Exercises

1. Remember the choice in localStorage.
2. Add a high-contrast theme.
3. Animate the switch with a view transition.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 943: Light and dark theme switcher for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 3 | Files: index.html, styles.css

Brief

Support the system colour scheme automatically and add a manual switch that sets a data attribute on the html element, all driven by custom properties.

Learning goals

- Use prefers-color-scheme and color-scheme
- Theme with custom properties
- Override with a data attribute set by a few lines of JavaScript

Elements and CSS used

HTML elements	CSS features
fieldset, legend, label, input type=radio, section, script	custom properties, @media (prefers-color-scheme), [data-theme], color-scheme, transition

Build guide

1. Define light variables in :root and dark ones inside a prefers-color-scheme media query.
2. Add [data-theme] overrides.
3. Use the variables for background, colour and cards.
4. Add the radio group.

5. Add the script that copies the chosen value to html's data-theme.
6. Test with your OS in dark mode.

Project 943: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - Themes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cleopatra Beauty Salon</h1>
    <p>This page follows your system theme and also lets you choose
one.</p>
    <fieldset class="theme">
      <legend>Theme</legend>
      <label><input type="radio" name="theme" value="auto" checked>
Auto</label>
      <label><input type="radio" name="theme" value="light"> Light</
label>
      <label><input type="radio" name="theme" value="dark"> Dark</
label>
    </fieldset>
    <section class="card">
      <h2>Haircut and blow-dry</h2>
      <p>Consultation included. <a href="#">Read more</a></p>
    </section>
  </main>
  <script>
    document.querySelectorAll('input[name=theme]').forEach(r => r.
addEventListener('change', e => {
      document.documentElement.dataset.theme = e.target.value;
    }));
  </script>
</body>
</html>
```

Project 943: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
:root { color-scheme: light dark; --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; }
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg:
#e5e7eb; --card: #1f2937; } }
```

```
:root[data-theme="light"] { --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; color-scheme: light; }
:root[data-theme="dark"]  { --bg: #111827; --fg: #e5e7eb; --card:
#1f2937; color-scheme: dark; }
body { background: var(--bg); color: var(--fg); transition:
background .3s, color .3s; }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.theme { display: flex; gap: 1rem; border: 1px solid var(--line);
border-radius: 10px; }
.card { background: var(--card); padding: 1.25rem; border-radius:
12px; margin-top: 1.5rem; }
a { color: var(--brand); }
```

Project 943 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - Themes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cleopatra Beauty Salon	The main heading; only one per page.
<p>This page follows your system theme and also lets you choose one...	A paragraph of text.
<fieldset class="theme">	Groups related form controls.
<legend>Theme</legend>	Caption for the fieldset.
<label><input type="radio" name="theme" value="auto" checked> Auto<...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="theme" value="light"> Light</label>	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="theme" value="dark"> Dark</label>	A form control; its type decides what it looks like.
<section class="card">	A thematic group of content, normally with its own heading.
Haircut and blow-dry	Second-level heading for a section.
Consultation included. Read more	A hyperlink; href gives the destination.
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
color-scheme: light dark;	Tells the browser which colour schemes the page supports so native controls match.
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg: ...	Applies when the user's system is in dark mode.
:root[data-theme="light"] {	Attribute selector on a data attribute set by JavaScript.
background: var(--bg);	Background colour or image.
transition: background .3s, color .3s;	Animates property changes smoothly, for example on hover.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
border-radius: 12px;	The line around the element: width, style and colour.

Check your work

- Follows system setting by default
- Manual choice overrides
- Form controls also switch (color-scheme)
- Contrast good in both themes

Exercises

1. Remember the choice in localStorage.
2. Add a high-contrast theme.
3. Animate the switch with a view transition.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 944: Light and dark theme switcher for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 3 | Files: index.html, styles.css

Brief

Support the system colour scheme automatically and add a manual switch that sets a data attribute on the html element, all driven by custom properties.

Learning goals

- Use prefers-color-scheme and color-scheme
- Theme with custom properties
- Override with a data attribute set by a few lines of JavaScript

Elements and CSS used

HTML elements	CSS features
fieldset, legend, label, input type=radio, section, script	custom properties, @media (prefers-color-scheme), [data-theme], color-scheme, transition

Build guide

1. Define light variables in :root and dark ones inside a prefers-color-scheme media query.
2. Add [data-theme] overrides.
3. Use the variables for background, colour and cards.
4. Add the radio group.

5. Add the script that copies the chosen value to html's data-theme.
6. Test with your OS in dark mode.

Project 944: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - Themes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Suez Auto Service</h1>
    <p>This page follows your system theme and also lets you choose
one.</p>
    <fieldset class="theme">
      <legend>Theme</legend>
      <label><input type="radio" name="theme" value="auto" checked>
Auto</label>
      <label><input type="radio" name="theme" value="light"> Light</
label>
      <label><input type="radio" name="theme" value="dark"> Dark</
label>
    </fieldset>
    <section class="card">
      <h2>Oil change</h2>
      <p>Filter included. <a href="#">Read more</a></p>
    </section>
  </main>
  <script>
    document.querySelectorAll('input[name=theme]').forEach(r => r.
addEventListener('change', e => {
      document.documentElement.dataset.theme = e.target.value;
    }));
  </script>
</body>
</html>
```

Project 944: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
:root { color-scheme: light dark; --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; }
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg:
#e5e7eb; --card: #1f2937; } }
```

```
:root[data-theme="light"] { --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; color-scheme: light; }
:root[data-theme="dark"]  { --bg: #111827; --fg: #e5e7eb; --card:
#1f2937; color-scheme: dark; }
body { background: var(--bg); color: var(--fg); transition:
background .3s, color .3s; }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.theme { display: flex; gap: 1rem; border: 1px solid var(--line);
border-radius: 10px; }
.card { background: var(--card); padding: 1.25rem; border-radius:
12px; margin-top: 1.5rem; }
a { color: var(--brand); }
```

Project 944 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - Themes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Suez Auto Service	The main heading; only one per page.
<p>This page follows your system theme and also lets you choose one...	A paragraph of text.
<fieldset class="theme">	Groups related form controls.
<legend>Theme</legend>	Caption for the fieldset.
<label><input type="radio" name="theme" value="auto" checked> Auto<...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="theme" value="light"> Light</label>	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="theme" value="dark"> Dark</label>	A form control; its type decides what it looks like.
<section class="card">	A thematic group of content, normally with its own heading.
Oil change	Second-level heading for a section.
Filter included. Read more	A hyperlink; href gives the destination.
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
color-scheme: light dark;	Tells the browser which colour schemes the page supports so native controls match.
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg: ...	Applies when the user's system is in dark mode.
:root[data-theme="light"] {	Attribute selector on a data attribute set by JavaScript.
background: var(--bg);	Background colour or image.
transition: background .3s, color .3s;	Animates property changes smoothly, for example on hover.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
border-radius: 12px;	The line around the element: width, style and colour.

Check your work

- Follows system setting by default
- Manual choice overrides
- Form controls also switch (color-scheme)
- Contrast good in both themes

Exercises

1. Remember the choice in localStorage.
2. Add a high-contrast theme.
3. Animate the switch with a view transition.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 945: Light and dark theme switcher for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 3 | Files: index.html, styles.css

Brief

Support the system colour scheme automatically and add a manual switch that sets a data attribute on the html element, all driven by custom properties.

Learning goals

- Use prefers-color-scheme and color-scheme
- Theme with custom properties
- Override with a data attribute set by a few lines of JavaScript

Elements and CSS used

HTML elements	CSS features
fieldset, legend, label, input type=radio, section, script	custom properties, @media (prefers-color-scheme), [data-theme], color-scheme, transition

Build guide

1. Define light variables in :root and dark ones inside a prefers-color-scheme media query.
2. Add [data-theme] overrides.
3. Use the variables for background, colour and cards.
4. Add the radio group.

5. Add the script that copies the chosen value to html's data-theme.
6. Test with your OS in dark mode.

Project 945: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - Themes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Luxor Music Academy</h1>
    <p>This page follows your system theme and also lets you choose
one.</p>
    <fieldset class="theme">
      <legend>Theme</legend>
      <label><input type="radio" name="theme" value="auto" checked>
Auto</label>
      <label><input type="radio" name="theme" value="light"> Light</
label>
      <label><input type="radio" name="theme" value="dark"> Dark</
label>
    </fieldset>
    <section class="card">
      <h2>Oud for beginners</h2>
      <p>Eight weekly lessons. <a href="#">Read more</a></p>
    </section>
  </main>
  <script>
    document.querySelectorAll('input[name=theme]').forEach(r => r.
addEventListener('change', e => {
      document.documentElement.dataset.theme = e.target.value;
    }));
  </script>
</body>
</html>
```

Project 945: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
:root { color-scheme: light dark; --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; }
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg:
#e5e7eb; --card: #1f2937; } }
```

```
:root[data-theme="light"] { --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; color-scheme: light; }
:root[data-theme="dark"]  { --bg: #111827; --fg: #e5e7eb; --card:
#1f2937; color-scheme: dark; }
body { background: var(--bg); color: var(--fg); transition:
background .3s, color .3s; }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.theme { display: flex; gap: 1rem; border: 1px solid var(--line);
border-radius: 10px; }
.card { background: var(--card); padding: 1.25rem; border-radius:
12px; margin-top: 1.5rem; }
a { color: var(--brand); }
```

Project 945 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - Themes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Luxor Music Academy	The main heading; only one per page.
<p>This page follows your system theme and also lets you choose one...	A paragraph of text.
<fieldset class="theme">	Groups related form controls.
<legend>Theme</legend>	Caption for the fieldset.
<label><input type="radio" name="theme" value="auto" checked> Auto<...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="theme" value="light"> Light</label>	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="theme" value="dark"> Dark</label>	A form control; its type decides what it looks like.
<section class="card">	A thematic group of content, normally with its own heading.
Oud for beginners	Second-level heading for a section.
Eight weekly lessons. Read more	A hyperlink; href gives the destination.
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
color-scheme: light dark;	Tells the browser which colour schemes the page supports so native controls match.
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg: ...	Applies when the user's system is in dark mode.
:root[data-theme="light"] {	Attribute selector on a data attribute set by JavaScript.
background: var(--bg);	Background colour or image.
transition: background .3s, color .3s;	Animates property changes smoothly, for example on hover.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
border-radius: 12px;	The line around the element: width, style and colour.

Check your work

- Follows system setting by default
- Manual choice overrides
- Form controls also switch (color-scheme)
- Contrast good in both themes

Exercises

1. Remember the choice in localStorage.
2. Add a high-contrast theme.
3. Animate the switch with a view transition.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 946: Light and dark theme switcher for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 3 | Files: index.html, styles.css

Brief

Support the system colour scheme automatically and add a manual switch that sets a data attribute on the html element, all driven by custom properties.

Learning goals

- Use prefers-color-scheme and color-scheme
- Theme with custom properties
- Override with a data attribute set by a few lines of JavaScript

Elements and CSS used

HTML elements	CSS features
fieldset, legend, label, input type=radio, section, script	custom properties, @media (prefers-color-scheme), [data-theme], color-scheme, transition

Build guide

1. Define light variables in :root and dark ones inside a prefers-color-scheme media query.
2. Add [data-theme] overrides.
3. Use the variables for background, colour and cards.
4. Add the radio group.

5. Add the script that copies the chosen value to html's data-theme.
6. Test with your OS in dark mode.

Project 946: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - Themes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Port Said Seafood</h1>
    <p>This page follows your system theme and also lets you choose
one.</p>
    <fieldset class="theme">
      <legend>Theme</legend>
      <label><input type="radio" name="theme" value="auto" checked>
Auto</label>
      <label><input type="radio" name="theme" value="light"> Light</
label>
      <label><input type="radio" name="theme" value="dark"> Dark</
label>
    </fieldset>
    <section class="card">
      <h2>Grilled sea bass</h2>
      <p>With rice and salad. <a href="#">Read more</a></p>
    </section>
  </main>
  <script>
    document.querySelectorAll('input[name=theme]').forEach(r => r.
addEventListener('change', e => {
      document.documentElement.dataset.theme = e.target.value;
    }));
  </script>
</body>
</html>
```

Project 946: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
:root { color-scheme: light dark; --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; }
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg:
#e5e7eb; --card: #1f2937; } }
```

```
:root[data-theme="light"] { --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; color-scheme: light; }
:root[data-theme="dark"]  { --bg: #111827; --fg: #e5e7eb; --card:
#1f2937; color-scheme: dark; }
body { background: var(--bg); color: var(--fg); transition:
background .3s, color .3s; }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.theme { display: flex; gap: 1rem; border: 1px solid var(--line);
border-radius: 10px; }
.card { background: var(--card); padding: 1.25rem; border-radius:
12px; margin-top: 1.5rem; }
a { color: var(--brand); }
```

Project 946 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - Themes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Port Said Seafood	The main heading; only one per page.
<p>This page follows your system theme and also lets you choose one...	A paragraph of text.
<fieldset class="theme">	Groups related form controls.
<legend>Theme</legend>	Caption for the fieldset.
<label><input type="radio" name="theme" value="auto" checked> Auto<...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="theme" value="light"> Light</label>	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="theme" value="dark"> Dark</label>	A form control; its type decides what it looks like.
<section class="card">	A thematic group of content, normally with its own heading.
Grilled sea bass	Second-level heading for a section.
With rice and salad. Read more	A hyperlink; href gives the destination.
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
color-scheme: light dark;	Tells the browser which colour schemes the page supports so native controls match.
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg: ...	Applies when the user's system is in dark mode.
:root[data-theme="light"] {	Attribute selector on a data attribute set by JavaScript.
background: var(--bg);	Background colour or image.
transition: background .3s, color .3s;	Animates property changes smoothly, for example on hover.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
border-radius: 12px;	The line around the element: width, style and colour.

Check your work

- Follows system setting by default
- Manual choice overrides
- Form controls also switch (color-scheme)
- Contrast good in both themes

Exercises

1. Remember the choice in localStorage.
2. Add a high-contrast theme.
3. Animate the switch with a view transition.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 947: Light and dark theme switcher for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 3 | Files: index.html, styles.css

Brief

Support the system colour scheme automatically and add a manual switch that sets a data attribute on the html element, all driven by custom properties.

Learning goals

- Use prefers-color-scheme and color-scheme
- Theme with custom properties
- Override with a data attribute set by a few lines of JavaScript

Elements and CSS used

HTML elements	CSS features
fieldset, legend, label, input type=radio, section, script	custom properties, @media (prefers-color-scheme), [data-theme], color-scheme, transition

Build guide

1. Define light variables in :root and dark ones inside a prefers-color-scheme media query.
2. Add [data-theme] overrides.
3. Use the variables for background, colour and cards.
4. Add the radio group.

5. Add the script that copies the chosen value to html's data-theme.
6. Test with your OS in dark mode.

Project 947: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - Themes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Delta Kids Library</h1>
    <p>This page follows your system theme and also lets you choose
one.</p>
    <fieldset class="theme">
      <legend>Theme</legend>
      <label><input type="radio" name="theme" value="auto" checked>
Auto</label>
      <label><input type="radio" name="theme" value="light"> Light</
label>
      <label><input type="radio" name="theme" value="dark"> Dark</
label>
    </fieldset>
    <section class="card">
      <h2>Story hour</h2>
      <p>Ages 3 to 6, Saturdays. <a href="#">Read more</a></p>
    </section>
  </main>
  <script>
    document.querySelectorAll('input[name=theme]').forEach(r => r.
addEventListener('change', e => {
      document.documentElement.dataset.theme = e.target.value;
    }));
  </script>
</body>
</html>
```

Project 947: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
:root { color-scheme: light dark; --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; }
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg:
#e5e7eb; --card: #1f2937; } }
```

```
:root[data-theme="light"] { --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; color-scheme: light; }
:root[data-theme="dark"]  { --bg: #111827; --fg: #e5e7eb; --card:
#1f2937; color-scheme: dark; }
body { background: var(--bg); color: var(--fg); transition:
background .3s, color .3s; }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.theme { display: flex; gap: 1rem; border: 1px solid var(--line);
border-radius: 10px; }
.card { background: var(--card); padding: 1.25rem; border-radius:
12px; margin-top: 1.5rem; }
a { color: var(--brand); }
```

Project 947 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - Themes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Delta Kids Library	The main heading; only one per page.
<p>This page follows your system theme and also lets you choose one...	A paragraph of text.
<fieldset class="theme">	Groups related form controls.
<legend>Theme</legend>	Caption for the fieldset.
<label><input type="radio" name="theme" value="auto" checked> Auto<...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="theme" value="light"> Light</label>	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="theme" value="dark"> Dark</label>	A form control; its type decides what it looks like.
<section class="card">	A thematic group of content, normally with its own heading.
Story hour	Second-level heading for a section.
Ages 3 to 6, Saturdays. Read more	A hyperlink; href gives the destination.
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
color-scheme: light dark;	Tells the browser which colour schemes the page supports so native controls match.
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg: ...	Applies when the user's system is in dark mode.
:root[data-theme="light"] {	Attribute selector on a data attribute set by JavaScript.
background: var(--bg);	Background colour or image.
transition: background .3s, color .3s;	Animates property changes smoothly, for example on hover.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
border-radius: 12px;	The line around the element: width, style and colour.

Check your work

- Follows system setting by default
- Manual choice overrides
- Form controls also switch (color-scheme)
- Contrast good in both themes

Exercises

1. Remember the choice in localStorage.
2. Add a high-contrast theme.
3. Animate the switch with a view transition.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 948: Light and dark theme switcher for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 3 | Files: index.html, styles.css

Brief

Support the system colour scheme automatically and add a manual switch that sets a data attribute on the html element, all driven by custom properties.

Learning goals

- Use prefers-color-scheme and color-scheme
- Theme with custom properties
- Override with a data attribute set by a few lines of JavaScript

Elements and CSS used

HTML elements	CSS features
fieldset, legend, label, input type=radio, section, script	custom properties, @media (prefers-color-scheme), [data-theme], color-scheme, transition

Build guide

1. Define light variables in :root and dark ones inside a prefers-color-scheme media query.
2. Add [data-theme] overrides.
3. Use the variables for background, colour and cards.
4. Add the radio group.

5. Add the script that copies the chosen value to html's data-theme.
6. Test with your OS in dark mode.

Project 948: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - Themes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Nubian Guest House</h1>
    <p>This page follows your system theme and also lets you choose
one.</p>
    <fieldset class="theme">
      <legend>Theme</legend>
      <label><input type="radio" name="theme" value="auto" checked>
Auto</label>
      <label><input type="radio" name="theme" value="light"> Light</
label>
      <label><input type="radio" name="theme" value="dark"> Dark</
label>
    </fieldset>
    <section class="card">
      <h2>Garden room</h2>
      <p>Double bed, shared terrace. <a href="#">Read more</a></p>
    </section>
  </main>
  <script>
    document.querySelectorAll('input[name=theme]').forEach(r => r.
addEventListener('change', e => {
      document.documentElement.dataset.theme = e.target.value;
    }));
  </script>
</body>
</html>
```

Project 948: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
:root { color-scheme: light dark; --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; }
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg:
#e5e7eb; --card: #1f2937; } }
```

```
:root[data-theme="light"] { --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; color-scheme: light; }
:root[data-theme="dark"]  { --bg: #111827; --fg: #e5e7eb; --card:
#1f2937; color-scheme: dark; }
body { background: var(--bg); color: var(--fg); transition:
background .3s, color .3s; }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.theme { display: flex; gap: 1rem; border: 1px solid var(--line);
border-radius: 10px; }
.card { background: var(--card); padding: 1.25rem; border-radius:
12px; margin-top: 1.5rem; }
a { color: var(--brand); }
```

Project 948 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - Themes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Nubian Guest House	The main heading; only one per page.
<p>This page follows your system theme and also lets you choose one...	A paragraph of text.
<fieldset class="theme">	Groups related form controls.
<legend>Theme</legend>	Caption for the fieldset.
<label><input type="radio" name="theme" value="auto" checked> Auto<...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="theme" value="light"> Light</label>	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="theme" value="dark"> Dark</label>	A form control; its type decides what it looks like.
<section class="card">	A thematic group of content, normally with its own heading.
Garden room	Second-level heading for a section.
Double bed, shared terrace. Read more	A hyperlink; href gives the destination.
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
color-scheme: light dark;	Tells the browser which colour schemes the page supports so native controls match.
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg: ...	Applies when the user's system is in dark mode.
:root[data-theme="light"] {	Attribute selector on a data attribute set by JavaScript.
background: var(--bg);	Background colour or image.
transition: background .3s, color .3s;	Animates property changes smoothly, for example on hover.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
border-radius: 12px;	The line around the element: width, style and colour.

Check your work

- Follows system setting by default
- Manual choice overrides
- Form controls also switch (color-scheme)
- Contrast good in both themes

Exercises

1. Remember the choice in localStorage.
2. Add a high-contrast theme.
3. Animate the switch with a view transition.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 949: Light and dark theme switcher for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 3 | Files: index.html, styles.css

Brief

Support the system colour scheme automatically and add a manual switch that sets a data attribute on the html element, all driven by custom properties.

Learning goals

- Use prefers-color-scheme and color-scheme
- Theme with custom properties
- Override with a data attribute set by a few lines of JavaScript

Elements and CSS used

HTML elements	CSS features
fieldset, legend, label, input type=radio, section, script	custom properties, @media (prefers-color-scheme), [data-theme], color-scheme, transition

Build guide

1. Define light variables in :root and dark ones inside a prefers-color-scheme media query.
2. Add [data-theme] overrides.
3. Use the variables for background, colour and cards.
4. Add the radio group.

5. Add the script that copies the chosen value to html's data-theme.
6. Test with your OS in dark mode.

Project 949: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - Themes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Ismailia Cycling Store</h1>
    <p>This page follows your system theme and also lets you choose
one.</p>
    <fieldset class="theme">
      <legend>Theme</legend>
      <label><input type="radio" name="theme" value="auto" checked>
Auto</label>
      <label><input type="radio" name="theme" value="light"> Light</
label>
      <label><input type="radio" name="theme" value="dark"> Dark</
label>
    </fieldset>
    <section class="card">
      <h2>City bike</h2>
      <p>Seven gears, basket. <a href="#">Read more</a></p>
    </section>
  </main>
  <script>
    document.querySelectorAll('input[name=theme]').forEach(r => r.
addEventListener('change', e => {
      document.documentElement.dataset.theme = e.target.value;
    }));
  </script>
</body>
</html>
```

Project 949: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
:root { color-scheme: light dark; --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; }
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg:
#e5e7eb; --card: #1f2937; } }
```

```
:root[data-theme="light"] { --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; color-scheme: light; }
:root[data-theme="dark"]  { --bg: #111827; --fg: #e5e7eb; --card:
#1f2937; color-scheme: dark; }
body { background: var(--bg); color: var(--fg); transition:
background .3s, color .3s; }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.theme { display: flex; gap: 1rem; border: 1px solid var(--line);
border-radius: 10px; }
.card { background: var(--card); padding: 1.25rem; border-radius:
12px; margin-top: 1.5rem; }
a { color: var(--brand); }
```

Project 949 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - Themes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Ismailia Cycling Store	The main heading; only one per page.
<p>This page follows your system theme and also lets you choose one...	A paragraph of text.
<fieldset class="theme">	Groups related form controls.
<legend>Theme</legend>	Caption for the fieldset.
<label><input type="radio" name="theme" value="auto" checked> Auto<...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="theme" value="light"> Light</label>	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="theme" value="dark"> Dark</label>	A form control; its type decides what it looks like.
<section class="card">	A thematic group of content, normally with its own heading.
City bike	Second-level heading for a section.
Seven gears, basket. Read more	A hyperlink; href gives the destination.
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
color-scheme: light dark;	Tells the browser which colour schemes the page supports so native controls match.
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg: ...	Applies when the user's system is in dark mode.
:root[data-theme="light"] {	Attribute selector on a data attribute set by JavaScript.
background: var(--bg);	Background colour or image.
transition: background .3s, color .3s;	Animates property changes smoothly, for example on hover.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
border-radius: 12px;	The line around the element: width, style and colour.

Check your work

- Follows system setting by default
- Manual choice overrides
- Form controls also switch (color-scheme)
- Contrast good in both themes

Exercises

1. Remember the choice in localStorage.
2. Add a high-contrast theme.
3. Animate the switch with a view transition.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 950: Light and dark theme switcher for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 3 | Files: index.html, styles.css

Brief

Support the system colour scheme automatically and add a manual switch that sets a data attribute on the html element, all driven by custom properties.

Learning goals

- Use prefers-color-scheme and color-scheme
- Theme with custom properties
- Override with a data attribute set by a few lines of JavaScript

Elements and CSS used

HTML elements	CSS features
fieldset, legend, label, input type=radio, section, script	custom properties, @media (prefers-color-scheme), [data-theme], color-scheme, transition

Build guide

1. Define light variables in :root and dark ones inside a prefers-color-scheme media query.
2. Add [data-theme] overrides.
3. Use the variables for background, colour and cards.
4. Add the radio group.

5. Add the script that copies the chosen value to html's data-theme.
6. Test with your OS in dark mode.

Project 950: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - Themes</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Minya Coding Club</h1>
    <p>This page follows your system theme and also lets you choose
one.</p>
    <fieldset class="theme">
      <legend>Theme</legend>
      <label><input type="radio" name="theme" value="auto" checked>
Auto</label>
      <label><input type="radio" name="theme" value="light"> Light</
label>
      <label><input type="radio" name="theme" value="dark"> Dark</
label>
    </fieldset>
    <section class="card">
      <h2>HTML weekend</h2>
      <p>Build your first page. <a href="#">Read more</a></p>
    </section>
  </main>
  <script>
    document.querySelectorAll('input[name=theme]').forEach(r => r.
addEventListener('change', e => {
      document.documentElement.dataset.theme = e.target.value;
    }));
  </script>
</body>
</html>
```

Project 950: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
:root { color-scheme: light dark; --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; }
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg:
#e5e7eb; --card: #1f2937; } }
```

```
:root[data-theme="light"] { --bg: #fff; --fg: #1b2431; --card:
#f4f4f4; color-scheme: light; }
:root[data-theme="dark"]  { --bg: #111827; --fg: #e5e7eb; --card:
#1f2937; color-scheme: dark; }
body { background: var(--bg); color: var(--fg); transition:
background .3s, color .3s; }
main { max-width: 40rem; margin: 2rem auto; padding: 0 1rem; }
.theme { display: flex; gap: 1rem; border: 1px solid var(--line);
border-radius: 10px; }
.card { background: var(--card); padding: 1.25rem; border-radius:
12px; margin-top: 1.5rem; }
a { color: var(--brand); }
```

Project 950 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - Themes</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Minya Coding Club	The main heading; only one per page.
<p>This page follows your system theme and also lets you choose one...	A paragraph of text.
<fieldset class="theme">	Groups related form controls.
<legend>Theme</legend>	Caption for the fieldset.
<label><input type="radio" name="theme" value="auto" checked> Auto<...	Text label for a control; for matches the control's id, or the label wraps the control.
<label><input type="radio" name="theme" value="light"> Light</label>	Radio button: one choice from a group sharing the same name.

Line	What it does
<label><input type="radio" name="theme" value="dark"> Dark</label>	A form control; its type decides what it looks like.
<section class="card">	A thematic group of content, normally with its own heading.
HTML weekend	Second-level heading for a section.
Build your first page. Read more	A hyperlink; href gives the destination.
<script>	JavaScript; here only a few lines to open a dialog or switch a theme.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.

Declaration	What it does
color-scheme: light dark;	Tells the browser which colour schemes the page supports so native controls match.
@media (prefers-color-scheme: dark) { :root { --bg: #111827; --fg: ...	Applies when the user's system is in dark mode.
:root[data-theme="light"] {	Attribute selector on a data attribute set by JavaScript.
background: var(--bg);	Background colour or image.
transition: background .3s, color .3s;	Animates property changes smoothly, for example on hover.
max-width: 40rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: 1rem;	Space between grid or flex items without extra margins.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 10px;	Rounds the corners.
border-radius: 12px;	The line around the element: width, style and colour.

Check your work

- Follows system setting by default
- Manual choice overrides
- Form controls also switch (color-scheme)
- Contrast good in both themes

Exercises

1. Remember the choice in localStorage.
2. Add a high-contrast theme.
3. Animate the switch with a view transition.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Printable voucher

Level 2 | 25 projects, one per theme

Design a gift voucher that looks good on screen and prints cleanly: hide navigation, avoid page breaks, print link URLs and set page margins.

Project 951: Printable voucher for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 2 | Files: index.html, styles.css

Brief

Design a gift voucher that looks good on screen and prints cleanly: hide navigation, avoid page breaks, print link URLs and set page margins.

Learning goals

- Write @media print rules
- Use @page
- Trigger printing with a button

Elements and CSS used

HTML elements	CSS features
nav, a, button, article, h1, p, time, b	@media print, display: none, page-break-inside, attr(), @page, border: double

Build guide

1. Write the voucher article and a nav with a print button.
2. Style the voucher with a double border.
3. In @media print hide .no-print.
4. Prevent the voucher splitting across pages.
5. Print link hrefs after links.
6. Set @page margins and test with print preview.

Project 951: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Voucher</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav class="no-print"><a href="index.html">Back</a> &middot;
<button onclick="print()">Print this voucher</button></nav>
    <article class="voucher">
      <h1>Cairo Book Shop gift voucher</h1>
      <p class="amount">200 EGP</p>
      <p>Valid for any book until <time datetime="2027-09-11">11
September 2027</time>.</p>
      <p class="code">Code: <b>GIFT-BOOK-2026</b></p>
      <p class="small">Present this voucher in Giza. Not exchangeable
for cash.</p>
    </article>
  </main>
</body>
</html>
```

Project 951: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.voucher { border: 4px double var(--brand); padding: 2rem; text-align:
 center; border-radius: 8px; }
h1 { color: var(--brand); margin-top: 0; }
.amount { font-size: 3rem; font-weight: 800; margin: 0; }
.code { font-family: monospace; font-size: 1.2rem; background: var(--
accent); display: inline-block; padding: .4rem 1rem; }
.small { font-size: .8rem; color: var(--muted); }
@media print {
  .no-print { display: none; }
  body { margin: 0; }
  main { max-width: none; margin: 0; }
  .voucher { border-color: #000; page-break-inside: avoid; }
  a[href]::after { content: " (" attr(href) ")"; }
}
```

```
@page { margin: 2cm; }
```

Project 951 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - Voucher</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav class="no-print">Back · <butto...	A block of navigation links; aria-label names it for screen readers.
<article class="voucher">	A self-contained piece: card, post, product.
Cairo Book Shop gift voucher	The main heading; only one per page.
200 EGP	A paragraph of text.
Valid for any book until <time datetime="2027-09-11">11 Septembe...	A date or time; datetime holds the machine-readable value.

Line	What it does
Code: GIFT-BOOK-2026	Keyword or name drawn to attention without extra importance.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 4px double var(--brand);	Changes the visual order of a flex item without changing the source.
text-align: center;	Centres inline content such as text.
border-radius: 8px;	Rounds the corners.
font-size: 3rem;	Size of the text.

Declaration	What it does
font-weight: 800;	Thickness of the text.
background: var(--accent);	Background colour or image.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
@media print {	Applies only when printing.
display: none;	Removes the element from rendering completely.
border-color: #000;	The line around the element: width, style and colour.
a[href]::after {	Generated content inserted after the element's content.
content: " (" attr(href) ")";	The text or empty string for a pseudo-element.
@page { margin: 2cm; }	Sets the printed page margins.

Check your work

- Nav hidden in print
- Voucher on one page
- Black border when printed
- Print button works

Exercises

1. Add a barcode-like pattern with repeating-linear-gradient.
2. Add two vouchers per page with columns.
3. Add a QR code image.

Theme data for this project

Field	Value
Business	Cairo Book Shop

Field	Value
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 952: Printable voucher for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 2 | Files: index.html, styles.css

Brief

Design a gift voucher that looks good on screen and prints cleanly: hide navigation, avoid page breaks, print link URLs and set page margins.

Learning goals

- Write @media print rules
- Use @page
- Trigger printing with a button

Elements and CSS used

HTML elements	CSS features
nav, a, button, article, h1, p, time, b	@media print, display: none, page-break-inside, attr(), @page, border: double

Build guide

1. Write the voucher article and a nav with a print button.
2. Style the voucher with a double border.
3. In @media print hide .no-print.
4. Prevent the voucher splitting across pages.
5. Print link hrefs after links.
6. Set @page margins and test with print preview.

Project 952: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - Voucher</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav class="no-print"><a href="index.html">Back</a> &middot;
<button onclick="print()">Print this voucher</button></nav>
    <article class="voucher">
      <h1>Nile Bakery gift voucher</h1>
      <p class="amount">200 EGP</p>
      <p>Valid for any pastry until <time datetime="2027-09-11">11
September 2027</time>.</p>
      <p class="code">Code: <b>GIFT-BAKE-2026</b></p>
      <p class="small">Present this voucher in Cairo. Not
exchangeable for cash.</p>
    </article>
  </main>
</body>
</html>
```

Project 952: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.voucher { border: 4px double var(--brand); padding: 2rem; text-align:
 center; border-radius: 8px; }
h1 { color: var(--brand); margin-top: 0; }
.amount { font-size: 3rem; font-weight: 800; margin: 0; }
.code { font-family: monospace; font-size: 1.2rem; background: var(--
accent); display: inline-block; padding: .4rem 1rem; }
.small { font-size: .8rem; color: var(--muted); }
@media print {
  .no-print { display: none; }
  body { margin: 0; }
  main { max-width: none; margin: 0; }
  .voucher { border-color: #000; page-break-inside: avoid; }
  a[href]::after { content: " (" attr(href) ")"; }
}
```

```
@page { margin: 2cm; }
```

Project 952 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - Voucher</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav class="no-print">Back · <butto...	A block of navigation links; aria-label names it for screen readers.
<article class="voucher">	A self-contained piece: card, post, product.
Nile Bakery gift voucher	The main heading; only one per page.
200 EGP	A paragraph of text.
Valid for any pastry until <time datetime="2027-09-11">11 Septem...	A date or time; datetime holds the machine-readable value.

Line	What it does
Code: GIFT-BAKE-2026	Keyword or name drawn to attention without extra importance.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 4px double var(--brand);	Changes the visual order of a flex item without changing the source.
text-align: center;	Centres inline content such as text.
border-radius: 8px;	Rounds the corners.
font-size: 3rem;	Size of the text.

Declaration	What it does
font-weight: 800;	Thickness of the text.
background: var(--accent);	Background colour or image.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
@media print {	Applies only when printing.
display: none;	Removes the element from rendering completely.
border-color: #000;	The line around the element: width, style and colour.
a[href]::after {	Generated content inserted after the element's content.
content: " (" attr(href) ")";	The text or empty string for a pseudo-element.
@page { margin: 2cm; }	Sets the printed page margins.

Check your work

- Nav hidden in print
- Voucher on one page
- Black border when printed
- Print button works

Exercises

1. Add a barcode-like pattern with repeating-linear-gradient.
2. Add two vouchers per page with columns.
3. Add a QR code image.

Theme data for this project

Field	Value
Business	Nile Bakery

Field	Value
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 953: Printable voucher for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 2 | Files: index.html, styles.css

Brief

Design a gift voucher that looks good on screen and prints cleanly: hide navigation, avoid page breaks, print link URLs and set page margins.

Learning goals

- Write @media print rules
- Use @page
- Trigger printing with a button

Elements and CSS used

HTML elements	CSS features
nav, a, button, article, h1, p, time, b	@media print, display: none, page-break-inside, attr(), @page, border: double

Build guide

1. Write the voucher article and a nav with a print button.
2. Style the voucher with a double border.
3. In @media print hide .no-print.
4. Prevent the voucher splitting across pages.
5. Print link hrefs after links.
6. Set @page margins and test with print preview.

Project 953: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - Voucher</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav class="no-print"><a href="index.html">Back</a> &middot;
<button onclick="print()">Print this voucher</button></nav>
    <article class="voucher">
      <h1>Pyramid Fitness gift voucher</h1>
      <p class="amount">200 EGP</p>
      <p>Valid for any class until <time datetime="2027-09-11">11
September 2027</time>.</p>
      <p class="code">Code: <b>GIFT-GYM-2026</b></p>
      <p class="small">Present this voucher in 6th of October. Not
exchangeable for cash.</p>
    </article>
  </main>
</body>
</html>
```

Project 953: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.voucher { border: 4px double var(--brand); padding: 2rem; text-align:
 center; border-radius: 8px; }
h1 { color: var(--brand); margin-top: 0; }
.amount { font-size: 3rem; font-weight: 800; margin: 0; }
.code { font-family: monospace; font-size: 1.2rem; background: var(--
accent); display: inline-block; padding: .4rem 1rem; }
.small { font-size: .8rem; color: var(--muted); }
@media print {
  .no-print { display: none; }
  body { margin: 0; }
  main { max-width: none; margin: 0; }
  .voucher { border-color: #000; page-break-inside: avoid; }
  a[href]::after { content: " (" attr(href) ")"; }
}
```

```
@page { margin: 2cm; }
```

Project 953 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - Voucher</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav class="no-print">Back · <butto...	A block of navigation links; aria-label names it for screen readers.
<article class="voucher">	A self-contained piece: card, post, product.
Pyramid Fitness gift voucher	The main heading; only one per page.
200 EGP	A paragraph of text.
Valid for any class until <time datetime="2027-09-11">11 Septemb...	A date or time; datetime holds the machine-readable value.

Line	What it does
Code: GIFT-GYM-2026	Keyword or name drawn to attention without extra importance.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 4px double var(--brand);	Changes the visual order of a flex item without changing the source.
text-align: center;	Centres inline content such as text.
border-radius: 8px;	Rounds the corners.
font-size: 3rem;	Size of the text.

Declaration	What it does
font-weight: 800;	Thickness of the text.
background: var(--accent);	Background colour or image.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
@media print {	Applies only when printing.
display: none;	Removes the element from rendering completely.
border-color: #000;	The line around the element: width, style and colour.
a[href]::after {	Generated content inserted after the element's content.
content: " (" attr(href) ")";	The text or empty string for a pseudo-element.
@page { margin: 2cm; }	Sets the printed page margins.

Check your work

- Nav hidden in print
- Voucher on one page
- Black border when printed
- Print button works

Exercises

1. Add a barcode-like pattern with repeating-linear-gradient.
2. Add two vouchers per page with columns.
3. Add a QR code image.

Theme data for this project

Field	Value
Business	Pyramid Fitness

Field	Value
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 954: Printable voucher for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 2 | Files: index.html, styles.css

Brief

Design a gift voucher that looks good on screen and prints cleanly: hide navigation, avoid page breaks, print link URLs and set page margins.

Learning goals

- Write @media print rules
- Use @page
- Trigger printing with a button

Elements and CSS used

HTML elements	CSS features
nav, a, button, article, h1, p, time, b	@media print, display: none, page-break-inside, attr(), @page, border: double

Build guide

1. Write the voucher article and a nav with a print button.
2. Style the voucher with a double border.
3. In @media print hide .no-print.
4. Prevent the voucher splitting across pages.
5. Print link hrefs after links.
6. Set @page margins and test with print preview.

Project 954: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - Voucher</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav class="no-print"><a href="index.html">Back</a> &middot;
<button onclick="print()">Print this voucher</button></nav>
    <article class="voucher">
      <h1>Delta Dental Clinic gift voucher</h1>
      <p class="amount">200 EGP</p>
      <p>Valid for any service until <time datetime="2027-09-11">11
September 2027</time>.</p>
      <p class="code">Code: <b>GIFT-CLIN-2026</b></p>
      <p class="small">Present this voucher in Mansoura. Not
exchangeable for cash.</p>
    </article>
  </main>
</body>
</html>
```

Project 954: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.voucher { border: 4px double var(--brand); padding: 2rem; text-align:
 center; border-radius: 8px; }
h1 { color: var(--brand); margin-top: 0; }
.amount { font-size: 3rem; font-weight: 800; margin: 0; }
.code { font-family: monospace; font-size: 1.2rem; background: var(--
accent); display: inline-block; padding: .4rem 1rem; }
.small { font-size: .8rem; color: var(--muted); }
@media print {
  .no-print { display: none; }
  body { margin: 0; }
  main { max-width: none; margin: 0; }
  .voucher { border-color: #000; page-break-inside: avoid; }
  a[href]::after { content: " (" attr(href) ")"; }
}
```

```
@page { margin: 2cm; }
```

Project 954 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - Voucher</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav class="no-print">Back · <butto...	A block of navigation links; aria-label names it for screen readers.
<article class="voucher">	A self-contained piece: card, post, product.
Delta Dental Clinic gift voucher	The main heading; only one per page.
200 EGP	A paragraph of text.
Valid for any service until <time datetime="2027-09-11">11 Septe...	A date or time; datetime holds the machine-readable value.

Line	What it does
Code: GIFT-CLIN-2026	Keyword or name drawn to attention without extra importance.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 4px double var(--brand);	Changes the visual order of a flex item without changing the source.
text-align: center;	Centres inline content such as text.
border-radius: 8px;	Rounds the corners.
font-size: 3rem;	Size of the text.

Declaration	What it does
font-weight: 800;	Thickness of the text.
background: var(--accent);	Background colour or image.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
@media print {	Applies only when printing.
display: none;	Removes the element from rendering completely.
border-color: #000;	The line around the element: width, style and colour.
a[href]::after {	Generated content inserted after the element's content.
content: " (" attr(href) ")";	The text or empty string for a pseudo-element.
@page { margin: 2cm; }	Sets the printed page margins.

Check your work

- Nav hidden in print
- Voucher on one page
- Black border when printed
- Print button works

Exercises

1. Add a barcode-like pattern with repeating-linear-gradient.
2. Add two vouchers per page with columns.
3. Add a QR code image.

Theme data for this project

Field	Value
Business	Delta Dental Clinic

Field	Value
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 955: Printable voucher for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 2 | Files: index.html, styles.css

Brief

Design a gift voucher that looks good on screen and prints cleanly: hide navigation, avoid page breaks, print link URLs and set page margins.

Learning goals

- Write @media print rules
- Use @page
- Trigger printing with a button

Elements and CSS used

HTML elements	CSS features
nav, a, button, article, h1, p, time, b	@media print, display: none, page-break-inside, attr(), @page, border: double

Build guide

1. Write the voucher article and a nav with a print button.
2. Style the voucher with a double border.
3. In @media print hide .no-print.
4. Prevent the voucher splitting across pages.
5. Print link hrefs after links.
6. Set @page margins and test with print preview.

Project 955: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - Voucher</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav class="no-print"><a href="index.html">Back</a> &middot;
<button onclick="print()">Print this voucher</button></nav>
    <article class="voucher">
      <h1>Red Sea Travel gift voucher</h1>
      <p class="amount">200 EGP</p>
      <p>Valid for any tour until <time datetime="2027-09-11">11
September 2027</time>.</p>
      <p class="code">Code: <b>GIFT-TRAV-2026</b></p>
      <p class="small">Present this voucher in Hurghada. Not
exchangeable for cash.</p>
    </article>
  </main>
</body>
</html>
```

Project 955: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.voucher { border: 4px double var(--brand); padding: 2rem; text-align:
 center; border-radius: 8px; }
h1 { color: var(--brand); margin-top: 0; }
.amount { font-size: 3rem; font-weight: 800; margin: 0; }
.code { font-family: monospace; font-size: 1.2rem; background: var(--
accent); display: inline-block; padding: .4rem 1rem; }
.small { font-size: .8rem; color: var(--muted); }
@media print {
  .no-print { display: none; }
  body { margin: 0; }
  main { max-width: none; margin: 0; }
  .voucher { border-color: #000; page-break-inside: avoid; }
  a[href]::after { content: " (" attr(href) ")"; }
}
```

```
@page { margin: 2cm; }
```

Project 955 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - Voucher</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav class="no-print">Back · <butto...	A block of navigation links; aria-label names it for screen readers.
<article class="voucher">	A self-contained piece: card, post, product.
Red Sea Travel gift voucher	The main heading; only one per page.
200 EGP	A paragraph of text.
Valid for any tour until <time datetime="2027-09-11">11 Septembe...	A date or time; datetime holds the machine-readable value.

Line	What it does
Code: GIFT-TRAV-2026	Keyword or name drawn to attention without extra importance.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 4px double var(--brand);	Changes the visual order of a flex item without changing the source.
text-align: center;	Centres inline content such as text.
border-radius: 8px;	Rounds the corners.
font-size: 3rem;	Size of the text.

Declaration	What it does
font-weight: 800;	Thickness of the text.
background: var(--accent);	Background colour or image.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
@media print {	Applies only when printing.
display: none;	Removes the element from rendering completely.
border-color: #000;	The line around the element: width, style and colour.
a[href]::after {	Generated content inserted after the element's content.
content: " (" attr(href) ")";	The text or empty string for a pseudo-element.
@page { margin: 2cm; }	Sets the printed page margins.

Check your work

- Nav hidden in print
- Voucher on one page
- Black border when printed
- Print button works

Exercises

1. Add a barcode-like pattern with repeating-linear-gradient.
2. Add two vouchers per page with columns.
3. Add a QR code image.

Theme data for this project

Field	Value
Business	Red Sea Travel

Field	Value
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 956: Printable voucher for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Design a gift voucher that looks good on screen and prints cleanly: hide navigation, avoid page breaks, print link URLs and set page margins.

Learning goals

- Write @media print rules
- Use @page
- Trigger printing with a button

Elements and CSS used

HTML elements	CSS features
nav, a, button, article, h1, p, time, b	@media print, display: none, page-break-inside, attr(), @page, border: double

Build guide

1. Write the voucher article and a nav with a print button.
2. Style the voucher with a double border.
3. In @media print hide .no-print.
4. Prevent the voucher splitting across pages.
5. Print link hrefs after links.
6. Set @page margins and test with print preview.

Project 956: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - Voucher</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav class="no-print"><a href="index.html">Back</a> &middot;
<button onclick="print()">Print this voucher</button></nav>
    <article class="voucher">
      <h1>Lotus Language School gift voucher</h1>
      <p class="amount">200 EGP</p>
      <p>Valid for any course until <time datetime="2027-09-11">11
September 2027</time>.</p>
      <p class="code">Code: <b>GIFT-SCHO-2026</b></p>
      <p class="small">Present this voucher in Alexandria. Not
exchangeable for cash.</p>
    </article>
  </main>
</body>
</html>
```

Project 956: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.voucher { border: 4px double var(--brand); padding: 2rem; text-align:
 center; border-radius: 8px; }
h1 { color: var(--brand); margin-top: 0; }
.amount { font-size: 3rem; font-weight: 800; margin: 0; }
.code { font-family: monospace; font-size: 1.2rem; background: var(--
accent); display: inline-block; padding: .4rem 1rem; }
.small { font-size: .8rem; color: var(--muted); }
@media print {
  .no-print { display: none; }
  body { margin: 0; }
  main { max-width: none; margin: 0; }
  .voucher { border-color: #000; page-break-inside: avoid; }
  a[href]::after { content: " (" attr(href) ")"; }
}
```

```
@page { margin: 2cm; }
```

Project 956 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - Voucher</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav class="no-print">Back · <butto...	A block of navigation links; aria-label names it for screen readers.
<article class="voucher">	A self-contained piece: card, post, product.
Lotus Language School gift voucher	The main heading; only one per page.
200 EGP	A paragraph of text.
Valid for any course until <time datetime="2027-09-11">11 Septem...	A date or time; datetime holds the machine-readable value.

Line	What it does
Code: GIFT-SCHO-2026	Keyword or name drawn to attention without extra importance.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 4px double var(--brand);	Changes the visual order of a flex item without changing the source.
text-align: center;	Centres inline content such as text.
border-radius: 8px;	Rounds the corners.
font-size: 3rem;	Size of the text.

Declaration	What it does
font-weight: 800;	Thickness of the text.
background: var(--accent);	Background colour or image.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
@media print {	Applies only when printing.
display: none;	Removes the element from rendering completely.
border-color: #000;	The line around the element: width, style and colour.
a[href]::after {	Generated content inserted after the element's content.
content: " (" attr(href) ")";	The text or empty string for a pseudo-element.
@page { margin: 2cm; }	Sets the printed page margins.

Check your work

- Nav hidden in print
- Voucher on one page
- Black border when printed
- Print button works

Exercises

1. Add a barcode-like pattern with repeating-linear-gradient.
2. Add two vouchers per page with columns.
3. Add a QR code image.

Theme data for this project

Field	Value
Business	Lotus Language School

Field	Value
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 957: Printable voucher for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 2 | Files: index.html, styles.css

Brief

Design a gift voucher that looks good on screen and prints cleanly: hide navigation, avoid page breaks, print link URLs and set page margins.

Learning goals

- Write @media print rules
- Use @page
- Trigger printing with a button

Elements and CSS used

HTML elements	CSS features
nav, a, button, article, h1, p, time, b	@media print, display: none, page-break-inside, attr(), @page, border: double

Build guide

1. Write the voucher article and a nav with a print button.
2. Style the voucher with a double border.
3. In @media print hide .no-print.
4. Prevent the voucher splitting across pages.
5. Print link hrefs after links.
6. Set @page margins and test with print preview.

Project 957: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - Voucher</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav class="no-print"><a href="index.html">Back</a> &middot;
<button onclick="print()">Print this voucher</button></nav>
    <article class="voucher">
      <h1>Green Leaf Cafe gift voucher</h1>
      <p class="amount">200 EGP</p>
      <p>Valid for any drink until <time datetime="2027-09-11">11
September 2027</time>.</p>
      <p class="code">Code: <b>GIFT-CAFE-2026</b></p>
      <p class="small">Present this voucher in Zamalek. Not
exchangeable for cash.</p>
    </article>
  </main>
</body>
</html>
```

Project 957: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.voucher { border: 4px double var(--brand); padding: 2rem; text-align:
 center; border-radius: 8px; }
h1 { color: var(--brand); margin-top: 0; }
.amount { font-size: 3rem; font-weight: 800; margin: 0; }
.code { font-family: monospace; font-size: 1.2rem; background: var(--
accent); display: inline-block; padding: .4rem 1rem; }
.small { font-size: .8rem; color: var(--muted); }
@media print {
  .no-print { display: none; }
  body { margin: 0; }
  main { max-width: none; margin: 0; }
  .voucher { border-color: #000; page-break-inside: avoid; }
  a[href]::after { content: " (" attr(href) ")"; }
}
```

```
@page { margin: 2cm; }
```

Project 957 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - Voucher</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav class="no-print">Back · <butto...	A block of navigation links; aria-label names it for screen readers.
<article class="voucher">	A self-contained piece: card, post, product.
Green Leaf Cafe gift voucher	The main heading; only one per page.
200 EGP	A paragraph of text.
Valid for any drink until <time datetime="2027-09-11">11 Septemb...	A date or time; datetime holds the machine-readable value.

Line	What it does
Code: GIFT-CAFE-2026	Keyword or name drawn to attention without extra importance.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 4px double var(--brand);	Changes the visual order of a flex item without changing the source.
text-align: center;	Centres inline content such as text.
border-radius: 8px;	Rounds the corners.
font-size: 3rem;	Size of the text.

Declaration	What it does
font-weight: 800;	Thickness of the text.
background: var(--accent);	Background colour or image.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
@media print {	Applies only when printing.
display: none;	Removes the element from rendering completely.
border-color: #000;	The line around the element: width, style and colour.
a[href]::after {	Generated content inserted after the element's content.
content: " (" attr(href) ")";	The text or empty string for a pseudo-element.
@page { margin: 2cm; }	Sets the printed page margins.

Check your work

- Nav hidden in print
- Voucher on one page
- Black border when printed
- Print button works

Exercises

1. Add a barcode-like pattern with repeating-linear-gradient.
2. Add two vouchers per page with columns.
3. Add a QR code image.

Theme data for this project

Field	Value
Business	Green Leaf Cafe

Field	Value
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 958: Printable voucher for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 2 | Files: index.html, styles.css

Brief

Design a gift voucher that looks good on screen and prints cleanly: hide navigation, avoid page breaks, print link URLs and set page margins.

Learning goals

- Write @media print rules
- Use @page
- Trigger printing with a button

Elements and CSS used

HTML elements	CSS features
nav, a, button, article, h1, p, time, b	@media print, display: none, page-break-inside, attr(), @page, border: double

Build guide

1. Write the voucher article and a nav with a print button.
2. Style the voucher with a double border.
3. In @media print hide .no-print.
4. Prevent the voucher splitting across pages.
5. Print link hrefs after links.
6. Set @page margins and test with print preview.

Project 958: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - Voucher</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav class="no-print"><a href="index.html">Back</a> &middot;
<button onclick="print()">Print this voucher</button></nav>
    <article class="voucher">
      <h1>Sinai Trekking Club gift voucher</h1>
      <p class="amount">200 EGP</p>
      <p>Valid for any hike until <time datetime="2027-09-11">11
September 2027</time>.</p>
      <p class="code">Code: <b>GIFT-TREK-2026</b></p>
      <p class="small">Present this voucher in Saint Catherine. Not
exchangeable for cash.</p>
    </article>
  </main>
</body>
</html>
```

Project 958: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.voucher { border: 4px double var(--brand); padding: 2rem; text-align:
 center; border-radius: 8px; }
h1 { color: var(--brand); margin-top: 0; }
.amount { font-size: 3rem; font-weight: 800; margin: 0; }
.code { font-family: monospace; font-size: 1.2rem; background: var(--
accent); display: inline-block; padding: .4rem 1rem; }
.small { font-size: .8rem; color: var(--muted); }
@media print {
  .no-print { display: none; }
  body { margin: 0; }
  main { max-width: none; margin: 0; }
  .voucher { border-color: #000; page-break-inside: avoid; }
  a[href]::after { content: " (" attr(href) ")"; }
}
```

```
@page { margin: 2cm; }
```

Project 958 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - Voucher</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav class="no-print">Back · <butto...	A block of navigation links; aria-label names it for screen readers.
<article class="voucher">	A self-contained piece: card, post, product.
Sinai Trekking Club gift voucher	The main heading; only one per page.
200 EGP	A paragraph of text.
Valid for any hike until <time datetime="2027-09-11">11 Septembe...	A date or time; datetime holds the machine-readable value.

Line	What it does
Code: GIFT-TREK-2026	Keyword or name drawn to attention without extra importance.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 4px double var(--brand);	Changes the visual order of a flex item without changing the source.
text-align: center;	Centres inline content such as text.
border-radius: 8px;	Rounds the corners.
font-size: 3rem;	Size of the text.

Declaration	What it does
font-weight: 800;	Thickness of the text.
background: var(--accent);	Background colour or image.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
@media print {	Applies only when printing.
display: none;	Removes the element from rendering completely.
border-color: #000;	The line around the element: width, style and colour.
a[href]::after {	Generated content inserted after the element's content.
content: " (" attr(href) ")";	The text or empty string for a pseudo-element.
@page { margin: 2cm; }	Sets the printed page margins.

Check your work

- Nav hidden in print
- Voucher on one page
- Black border when printed
- Print button works

Exercises

1. Add a barcode-like pattern with repeating-linear-gradient.
2. Add two vouchers per page with columns.
3. Add a QR code image.

Theme data for this project

Field	Value
Business	Sinai Trekking Club

Field	Value
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 959: Printable voucher for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 2 | Files: index.html, styles.css

Brief

Design a gift voucher that looks good on screen and prints cleanly: hide navigation, avoid page breaks, print link URLs and set page margins.

Learning goals

- Write @media print rules
- Use @page
- Trigger printing with a button

Elements and CSS used

HTML elements	CSS features
nav, a, button, article, h1, p, time, b	@media print, display: none, page-break-inside, attr(), @page, border: double

Build guide

1. Write the voucher article and a nav with a print button.
2. Style the voucher with a double border.
3. In @media print hide .no-print.
4. Prevent the voucher splitting across pages.
5. Print link hrefs after links.
6. Set @page margins and test with print preview.

Project 959: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - Voucher</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav class="no-print"><a href="index.html">Back</a> &middot;
<button onclick="print()">Print this voucher</button></nav>
    <article class="voucher">
      <h1>Horizon Photography gift voucher</h1>
      <p class="amount">200 EGP</p>
      <p>Valid for any session until <time datetime="2027-09-11">11
September 2027</time>.</p>
      <p class="code">Code: <b>GIFT-PHOT-2026</b></p>
      <p class="small">Present this voucher in Maadi. Not
exchangeable for cash.</p>
    </article>
  </main>
</body>
</html>
```

Project 959: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.voucher { border: 4px double var(--brand); padding: 2rem; text-align:
 center; border-radius: 8px; }
h1 { color: var(--brand); margin-top: 0; }
.amount { font-size: 3rem; font-weight: 800; margin: 0; }
.code { font-family: monospace; font-size: 1.2rem; background: var(--
accent); display: inline-block; padding: .4rem 1rem; }
.small { font-size: .8rem; color: var(--muted); }
@media print {
  .no-print { display: none; }
  body { margin: 0; }
  main { max-width: none; margin: 0; }
  .voucher { border-color: #000; page-break-inside: avoid; }
  a[href]::after { content: " (" attr(href) ")"; }
}
```

```
@page { margin: 2cm; }
```

Project 959 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - Voucher</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav class="no-print">Back · <butto...	A block of navigation links; aria-label names it for screen readers.
<article class="voucher">	A self-contained piece: card, post, product.
Horizon Photography gift voucher	The main heading; only one per page.
200 EGP	A paragraph of text.
Valid for any session until <time datetime="2027-09-11">11 Septe...	A date or time; datetime holds the machine-readable value.

Line	What it does
Code: GIFT-PHOT-2026	Keyword or name drawn to attention without extra importance.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 4px double var(--brand);	Changes the visual order of a flex item without changing the source.
text-align: center;	Centres inline content such as text.
border-radius: 8px;	Rounds the corners.
font-size: 3rem;	Size of the text.

Declaration	What it does
font-weight: 800;	Thickness of the text.
background: var(--accent);	Background colour or image.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
@media print {	Applies only when printing.
display: none;	Removes the element from rendering completely.
border-color: #000;	The line around the element: width, style and colour.
a[href]::after {	Generated content inserted after the element's content.
content: " (" attr(href) ")";	The text or empty string for a pseudo-element.
@page { margin: 2cm; }	Sets the printed page margins.

Check your work

- Nav hidden in print
- Voucher on one page
- Black border when printed
- Print button works

Exercises

1. Add a barcode-like pattern with repeating-linear-gradient.
2. Add two vouchers per page with columns.
3. Add a QR code image.

Theme data for this project

Field	Value
Business	Horizon Photography

Field	Value
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 960: Printable voucher for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 2 | Files: index.html, styles.css

Brief

Design a gift voucher that looks good on screen and prints cleanly: hide navigation, avoid page breaks, print link URLs and set page margins.

Learning goals

- Write @media print rules
- Use @page
- Trigger printing with a button

Elements and CSS used

HTML elements	CSS features
nav, a, button, article, h1, p, time, b	@media print, display: none, page-break-inside, attr(), @page, border: double

Build guide

1. Write the voucher article and a nav with a print button.
2. Style the voucher with a double border.
3. In @media print hide .no-print.
4. Prevent the voucher splitting across pages.
5. Print link hrefs after links.
6. Set @page margins and test with print preview.

Project 960: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - Voucher</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav class="no-print"><a href="index.html">Back</a> &middot;
<button onclick="print()">Print this voucher</button></nav>
    <article class="voucher">
      <h1>Papyrus Stationery gift voucher</h1>
      <p class="amount">200 EGP</p>
      <p>Valid for any product until <time datetime="2027-09-11">11
September 2027</time>.</p>
      <p class="code">Code: <b>GIFT-STAT-2026</b></p>
      <p class="small">Present this voucher in Heliopolis. Not
exchangeable for cash.</p>
    </article>
  </main>
</body>
</html>
```

Project 960: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.voucher { border: 4px double var(--brand); padding: 2rem; text-align:
 center; border-radius: 8px; }
h1 { color: var(--brand); margin-top: 0; }
.amount { font-size: 3rem; font-weight: 800; margin: 0; }
.code { font-family: monospace; font-size: 1.2rem; background: var(--
accent); display: inline-block; padding: .4rem 1rem; }
.small { font-size: .8rem; color: var(--muted); }
@media print {
  .no-print { display: none; }
  body { margin: 0; }
  main { max-width: none; margin: 0; }
  .voucher { border-color: #000; page-break-inside: avoid; }
  a[href]::after { content: " (" attr(href) ")"; }
}
```

```
@page { margin: 2cm; }
```

Project 960 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - Voucher</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav class="no-print">Back · <butto...	A block of navigation links; aria-label names it for screen readers.
<article class="voucher">	A self-contained piece: card, post, product.
Papyrus Stationery gift voucher	The main heading; only one per page.
200 EGP	A paragraph of text.
Valid for any product until <time datetime="2027-09-11">11 Septe...	A date or time; datetime holds the machine-readable value.

Line	What it does
Code: GIFT-STAT-2026	Keyword or name drawn to attention without extra importance.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 4px double var(--brand);	Changes the visual order of a flex item without changing the source.
text-align: center;	Centres inline content such as text.
border-radius: 8px;	Rounds the corners.
font-size: 3rem;	Size of the text.

Declaration	What it does
font-weight: 800;	Thickness of the text.
background: var(--accent);	Background colour or image.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
@media print {	Applies only when printing.
display: none;	Removes the element from rendering completely.
border-color: #000;	The line around the element: width, style and colour.
a[href]::after {	Generated content inserted after the element's content.
content: " (" attr(href) ")";	The text or empty string for a pseudo-element.
@page { margin: 2cm; }	Sets the printed page margins.

Check your work

- Nav hidden in print
- Voucher on one page
- Black border when printed
- Print button works

Exercises

1. Add a barcode-like pattern with repeating-linear-gradient.
2. Add two vouchers per page with columns.
3. Add a QR code image.

Theme data for this project

Field	Value
Business	Papyrus Stationery

Field	Value
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 961: Printable voucher for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 2 | Files: index.html, styles.css

Brief

Design a gift voucher that looks good on screen and prints cleanly: hide navigation, avoid page breaks, print link URLs and set page margins.

Learning goals

- Write @media print rules
- Use @page
- Trigger printing with a button

Elements and CSS used

HTML elements	CSS features
nav, a, button, article, h1, p, time, b	@media print, display: none, page-break-inside, attr(), @page, border: double

Build guide

1. Write the voucher article and a nav with a print button.
2. Style the voucher with a double border.
3. In @media print hide .no-print.
4. Prevent the voucher splitting across pages.
5. Print link hrefs after links.
6. Set @page margins and test with print preview.

Project 961: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - Voucher</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav class="no-print"><a href="index.html">Back</a> &middot;
<button onclick="print()">Print this voucher</button></nav>
    <article class="voucher">
      <h1>Oasis Plant Nursery gift voucher</h1>
      <p class="amount">200 EGP</p>
      <p>Valid for any plant until <time datetime="2027-09-11">11
September 2027</time>.</p>
      <p class="code">Code: <b>GIFT-PLAN-2026</b></p>
      <p class="small">Present this voucher in Sheikh Zayed. Not
exchangeable for cash.</p>
    </article>
  </main>
</body>
</html>
```

Project 961: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.voucher { border: 4px double var(--brand); padding: 2rem; text-align:
 center; border-radius: 8px; }
h1 { color: var(--brand); margin-top: 0; }
.amount { font-size: 3rem; font-weight: 800; margin: 0; }
.code { font-family: monospace; font-size: 1.2rem; background: var(--
accent); display: inline-block; padding: .4rem 1rem; }
.small { font-size: .8rem; color: var(--muted); }
@media print {
  .no-print { display: none; }
  body { margin: 0; }
  main { max-width: none; margin: 0; }
  .voucher { border-color: #000; page-break-inside: avoid; }
  a[href]::after { content: " (" attr(href) ")"; }
}
```

```
@page { margin: 2cm; }
```

Project 961 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - Voucher</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav class="no-print">Back · <butto...	A block of navigation links; aria-label names it for screen readers.
<article class="voucher">	A self-contained piece: card, post, product.
Oasis Plant Nursery gift voucher	The main heading; only one per page.
200 EGP	A paragraph of text.
Valid for any plant until <time datetime="2027-09-11">11 Septemb...	A date or time; datetime holds the machine-readable value.

Line	What it does
Code: GIFT-PLAN-2026	Keyword or name drawn to attention without extra importance.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 4px double var(--brand);	Changes the visual order of a flex item without changing the source.
text-align: center;	Centres inline content such as text.
border-radius: 8px;	Rounds the corners.
font-size: 3rem;	Size of the text.

Declaration	What it does
font-weight: 800;	Thickness of the text.
background: var(--accent);	Background colour or image.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
@media print {	Applies only when printing.
display: none;	Removes the element from rendering completely.
border-color: #000;	The line around the element: width, style and colour.
a[href]::after {	Generated content inserted after the element's content.
content: " (" attr(href) ")";	The text or empty string for a pseudo-element.
@page { margin: 2cm; }	Sets the printed page margins.

Check your work

- Nav hidden in print
- Voucher on one page
- Black border when printed
- Print button works

Exercises

1. Add a barcode-like pattern with repeating-linear-gradient.
2. Add two vouchers per page with columns.
3. Add a QR code image.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery

Field	Value
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 962: Printable voucher for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 2 | Files: index.html, styles.css

Brief

Design a gift voucher that looks good on screen and prints cleanly: hide navigation, avoid page breaks, print link URLs and set page margins.

Learning goals

- Write @media print rules
- Use @page
- Trigger printing with a button

Elements and CSS used

HTML elements	CSS features
nav, a, button, article, h1, p, time, b	@media print, display: none, page-break-inside, attr(), @page, border: double

Build guide

1. Write the voucher article and a nav with a print button.
2. Style the voucher with a double border.
3. In @media print hide .no-print.
4. Prevent the voucher splitting across pages.
5. Print link hrefs after links.
6. Set @page margins and test with print preview.

Project 962: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - Voucher</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav class="no-print"><a href="index.html">Back</a> &middot;
<button onclick="print()">Print this voucher</button></nav>
    <article class="voucher">
      <h1>Cedar Furniture gift voucher</h1>
      <p class="amount">200 EGP</p>
      <p>Valid for any piece until <time datetime="2027-09-11">11
September 2027</time>.</p>
      <p class="code">Code: <b>GIFT-FURN-2026</b></p>
      <p class="small">Present this voucher in Damietta. Not
exchangeable for cash.</p>
    </article>
  </main>
</body>
</html>
```

Project 962: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.voucher { border: 4px double var(--brand); padding: 2rem; text-align:
 center; border-radius: 8px; }
h1 { color: var(--brand); margin-top: 0; }
.amount { font-size: 3rem; font-weight: 800; margin: 0; }
.code { font-family: monospace; font-size: 1.2rem; background: var(--
accent); display: inline-block; padding: .4rem 1rem; }
.small { font-size: .8rem; color: var(--muted); }
@media print {
  .no-print { display: none; }
  body { margin: 0; }
  main { max-width: none; margin: 0; }
  .voucher { border-color: #000; page-break-inside: avoid; }
  a[href]::after { content: " (" attr(href) ")"; }
}
```

```
@page { margin: 2cm; }
```

Project 962 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - Voucher</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav class="no-print">Back · <butto...	A block of navigation links; aria-label names it for screen readers.
<article class="voucher">	A self-contained piece: card, post, product.
Cedar Furniture gift voucher	The main heading; only one per page.
200 EGP	A paragraph of text.
Valid for any piece until <time datetime="2027-09-11">11 Septemb...	A date or time; datetime holds the machine-readable value.

Line	What it does
Code: GIFT-FURN-2026	Keyword or name drawn to attention without extra importance.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 4px double var(--brand);	Changes the visual order of a flex item without changing the source.
text-align: center;	Centres inline content such as text.
border-radius: 8px;	Rounds the corners.
font-size: 3rem;	Size of the text.

Declaration	What it does
font-weight: 800;	Thickness of the text.
background: var(--accent);	Background colour or image.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
@media print {	Applies only when printing.
display: none;	Removes the element from rendering completely.
border-color: #000;	The line around the element: width, style and colour.
a[href]::after {	Generated content inserted after the element's content.
content: " (" attr(href) ")";	The text or empty string for a pseudo-element.
@page { margin: 2cm; }	Sets the printed page margins.

Check your work

- Nav hidden in print
- Voucher on one page
- Black border when printed
- Print button works

Exercises

1. Add a barcode-like pattern with repeating-linear-gradient.
2. Add two vouchers per page with columns.
3. Add a QR code image.

Theme data for this project

Field	Value
Business	Cedar Furniture

Field	Value
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 963: Printable voucher for Byte Repair

Theme: Byte Repair (Nasr City) | Level 2 | Files: index.html, styles.css

Brief

Design a gift voucher that looks good on screen and prints cleanly: hide navigation, avoid page breaks, print link URLs and set page margins.

Learning goals

- Write @media print rules
- Use @page
- Trigger printing with a button

Elements and CSS used

HTML elements	CSS features
nav, a, button, article, h1, p, time, b	@media print, display: none, page-break-inside, attr(), @page, border: double

Build guide

1. Write the voucher article and a nav with a print button.
2. Style the voucher with a double border.
3. In @media print hide .no-print.
4. Prevent the voucher splitting across pages.
5. Print link hrefs after links.
6. Set @page margins and test with print preview.

Project 963: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - Voucher</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav class="no-print"><a href="index.html">Back</a> &middot;
<button onclick="print()">Print this voucher</button></nav>
    <article class="voucher">
      <h1>Byte Repair gift voucher</h1>
      <p class="amount">200 EGP</p>
      <p>Valid for any repair until <time datetime="2027-09-11">11
September 2027</time>.</p>
      <p class="code">Code: <b>GIFT-REPA-2026</b></p>
      <p class="small">Present this voucher in Nasr City. Not
exchangeable for cash.</p>
    </article>
  </main>
</body>
</html>
```

Project 963: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.voucher { border: 4px double var(--brand); padding: 2rem; text-align:
 center; border-radius: 8px; }
h1 { color: var(--brand); margin-top: 0; }
.amount { font-size: 3rem; font-weight: 800; margin: 0; }
.code { font-family: monospace; font-size: 1.2rem; background: var(--
accent); display: inline-block; padding: .4rem 1rem; }
.small { font-size: .8rem; color: var(--muted); }
@media print {
  .no-print { display: none; }
  body { margin: 0; }
  main { max-width: none; margin: 0; }
  .voucher { border-color: #000; page-break-inside: avoid; }
  a[href]::after { content: " (" attr(href) ")"; }
}
```

```
@page { margin: 2cm; }
```

Project 963 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - Voucher</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav class="no-print">Back · <butto...	A block of navigation links; aria-label names it for screen readers.
<article class="voucher">	A self-contained piece: card, post, product.
Byte Repair gift voucher	The main heading; only one per page.
200 EGP	A paragraph of text.
Valid for any repair until <time datetime="2027-09-11">11 Septem...	A date or time; datetime holds the machine-readable value.

Line	What it does
Code: GIFT-REPA-2026	Keyword or name drawn to attention without extra importance.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 4px double var(--brand);	Changes the visual order of a flex item without changing the source.
text-align: center;	Centres inline content such as text.
border-radius: 8px;	Rounds the corners.
font-size: 3rem;	Size of the text.

Declaration	What it does
font-weight: 800;	Thickness of the text.
background: var(--accent);	Background colour or image.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
@media print {	Applies only when printing.
display: none;	Removes the element from rendering completely.
border-color: #000;	The line around the element: width, style and colour.
a[href]::after {	Generated content inserted after the element's content.
content: " (" attr(href) ")";	The text or empty string for a pseudo-element.
@page { margin: 2cm; }	Sets the printed page margins.

Check your work

- Nav hidden in print
- Voucher on one page
- Black border when printed
- Print button works

Exercises

1. Add a barcode-like pattern with repeating-linear-gradient.
2. Add two vouchers per page with columns.
3. Add a QR code image.

Theme data for this project

Field	Value
Business	Byte Repair

Field	Value
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 964: Printable voucher for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 2 | Files: index.html, styles.css

Brief

Design a gift voucher that looks good on screen and prints cleanly: hide navigation, avoid page breaks, print link URLs and set page margins.

Learning goals

- Write @media print rules
- Use @page
- Trigger printing with a button

Elements and CSS used

HTML elements	CSS features
nav, a, button, article, h1, p, time, b	@media print, display: none, page-break-inside, attr(), @page, border: double

Build guide

1. Write the voucher article and a nav with a print button.
2. Style the voucher with a double border.
3. In @media print hide .no-print.
4. Prevent the voucher splitting across pages.
5. Print link hrefs after links.
6. Set @page margins and test with print preview.

Project 964: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - Voucher</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav class="no-print"><a href="index.html">Back</a> &middot;
<button onclick="print()">Print this voucher</button></nav>
    <article class="voucher">
      <h1>Sahara Pet Care gift voucher</h1>
      <p class="amount">200 EGP</p>
      <p>Valid for any service until <time datetime="2027-09-11">11
September 2027</time>.</p>
      <p class="code">Code: <b>GIFT-PETS-2026</b></p>
      <p class="small">Present this voucher in New Cairo. Not
exchangeable for cash.</p>
    </article>
  </main>
</body>
</html>
```

Project 964: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.voucher { border: 4px double var(--brand); padding: 2rem; text-align:
 center; border-radius: 8px; }
h1 { color: var(--brand); margin-top: 0; }
.amount { font-size: 3rem; font-weight: 800; margin: 0; }
.code { font-family: monospace; font-size: 1.2rem; background: var(--
accent); display: inline-block; padding: .4rem 1rem; }
.small { font-size: .8rem; color: var(--muted); }
@media print {
  .no-print { display: none; }
  body { margin: 0; }
  main { max-width: none; margin: 0; }
  .voucher { border-color: #000; page-break-inside: avoid; }
  a[href]::after { content: " (" attr(href) ")"; }
}
```

```
@page { margin: 2cm; }
```

Project 964 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - Voucher</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav class="no-print">Back · <butto...	A block of navigation links; aria-label names it for screen readers.
<article class="voucher">	A self-contained piece: card, post, product.
Sahara Pet Care gift voucher	The main heading; only one per page.
200 EGP	A paragraph of text.
Valid for any service until <time datetime="2027-09-11">11 Septe...	A date or time; datetime holds the machine-readable value.

Line	What it does
Code: GIFT-PETS-2026	Keyword or name drawn to attention without extra importance.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 4px double var(--brand);	Changes the visual order of a flex item without changing the source.
text-align: center;	Centres inline content such as text.
border-radius: 8px;	Rounds the corners.
font-size: 3rem;	Size of the text.

Declaration	What it does
font-weight: 800;	Thickness of the text.
background: var(--accent);	Background colour or image.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
@media print {	Applies only when printing.
display: none;	Removes the element from rendering completely.
border-color: #000;	The line around the element: width, style and colour.
a[href]::after {	Generated content inserted after the element's content.
content: " (" attr(href) ")";	The text or empty string for a pseudo-element.
@page { margin: 2cm; }	Sets the printed page margins.

Check your work

- Nav hidden in print
- Voucher on one page
- Black border when printed
- Print button works

Exercises

1. Add a barcode-like pattern with repeating-linear-gradient.
2. Add two vouchers per page with columns.
3. Add a QR code image.

Theme data for this project

Field	Value
Business	Sahara Pet Care

Field	Value
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 965: Printable voucher for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Design a gift voucher that looks good on screen and prints cleanly: hide navigation, avoid page breaks, print link URLs and set page margins.

Learning goals

- Write @media print rules
- Use @page
- Trigger printing with a button

Elements and CSS used

HTML elements	CSS features
nav, a, button, article, h1, p, time, b	@media print, display: none, page-break-inside, attr(), @page, border: double

Build guide

1. Write the voucher article and a nav with a print button.
2. Style the voucher with a double border.
3. In @media print hide .no-print.
4. Prevent the voucher splitting across pages.
5. Print link hrefs after links.
6. Set @page margins and test with print preview.

Project 965: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - Voucher</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav class="no-print"><a href="index.html">Back</a> &middot;
<button onclick="print()">Print this voucher</button></nav>
    <article class="voucher">
      <h1>Alexandria Sailing School gift voucher</h1>
      <p class="amount">200 EGP</p>
      <p>Valid for any lesson until <time datetime="2027-09-11">11
September 2027</time>.</p>
      <p class="code">Code: <b>GIFT-SAIL-2026</b></p>
      <p class="small">Present this voucher in Alexandria. Not
exchangeable for cash.</p>
    </article>
  </main>
</body>
</html>
```

Project 965: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.voucher { border: 4px double var(--brand); padding: 2rem; text-align:
 center; border-radius: 8px; }
h1 { color: var(--brand); margin-top: 0; }
.amount { font-size: 3rem; font-weight: 800; margin: 0; }
.code { font-family: monospace; font-size: 1.2rem; background: var(--
accent); display: inline-block; padding: .4rem 1rem; }
.small { font-size: .8rem; color: var(--muted); }
@media print {
  .no-print { display: none; }
  body { margin: 0; }
  main { max-width: none; margin: 0; }
  .voucher { border-color: #000; page-break-inside: avoid; }
  a[href]::after { content: " (" attr(href) ")"; }
}
```

```
@page { margin: 2cm; }
```

Project 965 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - Voucher</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav class="no-print">Back · <butto...	A block of navigation links; aria-label names it for screen readers.
<article class="voucher">	A self-contained piece: card, post, product.
Alexandria Sailing School gift voucher	The main heading; only one per page.
200 EGP	A paragraph of text.
Valid for any lesson until <time datetime="2027-09-11">11 Septem...	A date or time; datetime holds the machine-readable value.

Line	What it does
Code: GIFT-SAIL-2026	Keyword or name drawn to attention without extra importance.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 4px double var(--brand);	Changes the visual order of a flex item without changing the source.
text-align: center;	Centres inline content such as text.
border-radius: 8px;	Rounds the corners.
font-size: 3rem;	Size of the text.

Declaration	What it does
font-weight: 800;	Thickness of the text.
background: var(--accent);	Background colour or image.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
@media print {	Applies only when printing.
display: none;	Removes the element from rendering completely.
border-color: #000;	The line around the element: width, style and colour.
a[href]::after {	Generated content inserted after the element's content.
content: " (" attr(href) ")";	The text or empty string for a pseudo-element.
@page { margin: 2cm; }	Sets the printed page margins.

Check your work

- Nav hidden in print
- Voucher on one page
- Black border when printed
- Print button works

Exercises

1. Add a barcode-like pattern with repeating-linear-gradient.
2. Add two vouchers per page with columns.
3. Add a QR code image.

Theme data for this project

Field	Value
Business	Alexandria Sailing School

Field	Value
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 966: Printable voucher for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Design a gift voucher that looks good on screen and prints cleanly: hide navigation, avoid page breaks, print link URLs and set page margins.

Learning goals

- Write @media print rules
- Use @page
- Trigger printing with a button

Elements and CSS used

HTML elements	CSS features
nav, a, button, article, h1, p, time, b	@media print, display: none, page-break-inside, attr(), @page, border: double

Build guide

1. Write the voucher article and a nav with a print button.
2. Style the voucher with a double border.
3. In @media print hide .no-print.
4. Prevent the voucher splitting across pages.
5. Print link hrefs after links.
6. Set @page margins and test with print preview.

Project 966: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - Voucher</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav class="no-print"><a href="index.html">Back</a> &middot;
<button onclick="print()">Print this voucher</button></nav>
    <article class="voucher">
      <h1>Habiba Handmade Jewellery gift voucher</h1>
      <p class="amount">200 EGP</p>
      <p>Valid for any item until <time datetime="2027-09-11">11
September 2027</time>.</p>
      <p class="code">Code: <b>GIFT-JEWE-2026</b></p>
      <p class="small">Present this voucher in Aswan. Not
exchangeable for cash.</p>
    </article>
  </main>
</body>
</html>
```

Project 966: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.voucher { border: 4px double var(--brand); padding: 2rem; text-align:
 center; border-radius: 8px; }
h1 { color: var(--brand); margin-top: 0; }
.amount { font-size: 3rem; font-weight: 800; margin: 0; }
.code { font-family: monospace; font-size: 1.2rem; background: var(--
accent); display: inline-block; padding: .4rem 1rem; }
.small { font-size: .8rem; color: var(--muted); }
@media print {
  .no-print { display: none; }
  body { margin: 0; }
  main { max-width: none; margin: 0; }
  .voucher { border-color: #000; page-break-inside: avoid; }
  a[href]::after { content: " (" attr(href) ")"; }
}
```

```
@page { margin: 2cm; }
```

Project 966 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - Voucher</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav class="no-print">Back · <butto...	A block of navigation links; aria-label names it for screen readers.
<article class="voucher">	A self-contained piece: card, post, product.
Habiba Handmade Jewellery gift voucher	The main heading; only one per page.
200 EGP	A paragraph of text.
Valid for any item until <time datetime="2027-09-11">11 Septembe...	A date or time; datetime holds the machine-readable value.

Line	What it does
Code: GIFT-JEWE-2026	Keyword or name drawn to attention without extra importance.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 4px double var(--brand);	Changes the visual order of a flex item without changing the source.
text-align: center;	Centres inline content such as text.
border-radius: 8px;	Rounds the corners.
font-size: 3rem;	Size of the text.

Declaration	What it does
font-weight: 800;	Thickness of the text.
background: var(--accent);	Background colour or image.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
@media print {	Applies only when printing.
display: none;	Removes the element from rendering completely.
border-color: #000;	The line around the element: width, style and colour.
a[href]::after {	Generated content inserted after the element's content.
content: " (" attr(href) ")";	The text or empty string for a pseudo-element.
@page { margin: 2cm; }	Sets the printed page margins.

Check your work

- Nav hidden in print
- Voucher on one page
- Black border when printed
- Print button works

Exercises

1. Add a barcode-like pattern with repeating-linear-gradient.
2. Add two vouchers per page with columns.
3. Add a QR code image.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery

Field	Value
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 967: Printable voucher for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 2 | Files: index.html, styles.css

Brief

Design a gift voucher that looks good on screen and prints cleanly: hide navigation, avoid page breaks, print link URLs and set page margins.

Learning goals

- Write @media print rules
- Use @page
- Trigger printing with a button

Elements and CSS used

HTML elements	CSS features
nav, a, button, article, h1, p, time, b	@media print, display: none, page-break-inside, attr(), @page, border: double

Build guide

1. Write the voucher article and a nav with a print button.
2. Style the voucher with a double border.
3. In @media print hide .no-print.
4. Prevent the voucher splitting across pages.
5. Print link hrefs after links.
6. Set @page margins and test with print preview.

Project 967: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - Voucher</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav class="no-print"><a href="index.html">Back</a> &middot;
<button onclick="print()">Print this voucher</button></nav>
    <article class="voucher">
      <h1>Fayoum Pottery Studio gift voucher</h1>
      <p class="amount">200 EGP</p>
      <p>Valid for any workshop until <time datetime="2027-09-11">11
September 2027</time>.</p>
      <p class="code">Code: <b>GIFT-POTT-2026</b></p>
      <p class="small">Present this voucher in Tunis Village. Not
exchangeable for cash.</p>
    </article>
  </main>
</body>
</html>
```

Project 967: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.voucher { border: 4px double var(--brand); padding: 2rem; text-align:
 center; border-radius: 8px; }
h1 { color: var(--brand); margin-top: 0; }
.amount { font-size: 3rem; font-weight: 800; margin: 0; }
.code { font-family: monospace; font-size: 1.2rem; background: var(--
accent); display: inline-block; padding: .4rem 1rem; }
.small { font-size: .8rem; color: var(--muted); }
@media print {
  .no-print { display: none; }
  body { margin: 0; }
  main { max-width: none; margin: 0; }
  .voucher { border-color: #000; page-break-inside: avoid; }
  a[href]::after { content: " (" attr(href) ")"; }
}
```

```
@page { margin: 2cm; }
```

Project 967 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - Voucher</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav class="no-print">Back · <butto...	A block of navigation links; aria-label names it for screen readers.
<article class="voucher">	A self-contained piece: card, post, product.
Fayoum Pottery Studio gift voucher	The main heading; only one per page.
200 EGP	A paragraph of text.
Valid for any workshop until <time datetime="2027-09-11">11 Sept...	A date or time; datetime holds the machine-readable value.

Line	What it does
Code: GIFT-POTT-2026	Keyword or name drawn to attention without extra importance.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 4px double var(--brand);	Changes the visual order of a flex item without changing the source.
text-align: center;	Centres inline content such as text.
border-radius: 8px;	Rounds the corners.
font-size: 3rem;	Size of the text.

Declaration	What it does
font-weight: 800;	Thickness of the text.
background: var(--accent);	Background colour or image.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
@media print {	Applies only when printing.
display: none;	Removes the element from rendering completely.
border-color: #000;	The line around the element: width, style and colour.
a[href]::after {	Generated content inserted after the element's content.
content: " (" attr(href) ")";	The text or empty string for a pseudo-element.
@page { margin: 2cm; }	Sets the printed page margins.

Check your work

- Nav hidden in print
- Voucher on one page
- Black border when printed
- Print button works

Exercises

1. Add a barcode-like pattern with repeating-linear-gradient.
2. Add two vouchers per page with columns.
3. Add a QR code image.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio

Field	Value
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 968: Printable voucher for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 2 | Files: index.html, styles.css

Brief

Design a gift voucher that looks good on screen and prints cleanly: hide navigation, avoid page breaks, print link URLs and set page margins.

Learning goals

- Write @media print rules
- Use @page
- Trigger printing with a button

Elements and CSS used

HTML elements	CSS features
nav, a, button, article, h1, p, time, b	@media print, display: none, page-break-inside, attr(), @page, border: double

Build guide

1. Write the voucher article and a nav with a print button.
2. Style the voucher with a double border.
3. In @media print hide .no-print.
4. Prevent the voucher splitting across pages.
5. Print link hrefs after links.
6. Set @page margins and test with print preview.

Project 968: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - Voucher</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav class="no-print"><a href="index.html">Back</a> &middot;
<button onclick="print()">Print this voucher</button></nav>
    <article class="voucher">
      <h1>Cleopatra Beauty Salon gift voucher</h1>
      <p class="amount">200 EGP</p>
      <p>Valid for any treatment until <time datetime="2027-09-11">11
September 2027</time>.</p>
      <p class="code">Code: <b>GIFT-SALO-2026</b></p>
      <p class="small">Present this voucher in Dokki. Not
exchangeable for cash.</p>
    </article>
  </main>
</body>
</html>
```

Project 968: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.voucher { border: 4px double var(--brand); padding: 2rem; text-align:
 center; border-radius: 8px; }
h1 { color: var(--brand); margin-top: 0; }
.amount { font-size: 3rem; font-weight: 800; margin: 0; }
.code { font-family: monospace; font-size: 1.2rem; background: var(--
accent); display: inline-block; padding: .4rem 1rem; }
.small { font-size: .8rem; color: var(--muted); }
@media print {
  .no-print { display: none; }
  body { margin: 0; }
  main { max-width: none; margin: 0; }
  .voucher { border-color: #000; page-break-inside: avoid; }
  a[href]::after { content: " (" attr(href) ")"; }
}
```

```
@page { margin: 2cm; }
```

Project 968 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - Voucher</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav class="no-print">Back · <butto...	A block of navigation links; aria-label names it for screen readers.
<article class="voucher">	A self-contained piece: card, post, product.
Cleopatra Beauty Salon gift voucher	The main heading; only one per page.
200 EGP	A paragraph of text.
Valid for any treatment until <time datetime="2027-09-11">11 Sep...	A date or time; datetime holds the machine-readable value.

Line	What it does
Code: GIFT-SALO-2026	Keyword or name drawn to attention without extra importance.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 4px double var(--brand);	Changes the visual order of a flex item without changing the source.
text-align: center;	Centres inline content such as text.
border-radius: 8px;	Rounds the corners.
font-size: 3rem;	Size of the text.

Declaration	What it does
font-weight: 800;	Thickness of the text.
background: var(--accent);	Background colour or image.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
@media print {	Applies only when printing.
display: none;	Removes the element from rendering completely.
border-color: #000;	The line around the element: width, style and colour.
a[href]::after {	Generated content inserted after the element's content.
content: " (" attr(href) ")";	The text or empty string for a pseudo-element.
@page { margin: 2cm; }	Sets the printed page margins.

Check your work

- Nav hidden in print
- Voucher on one page
- Black border when printed
- Print button works

Exercises

1. Add a barcode-like pattern with repeating-linear-gradient.
2. Add two vouchers per page with columns.
3. Add a QR code image.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon

Field	Value
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 969: Printable voucher for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 2 | Files: index.html, styles.css

Brief

Design a gift voucher that looks good on screen and prints cleanly: hide navigation, avoid page breaks, print link URLs and set page margins.

Learning goals

- Write @media print rules
- Use @page
- Trigger printing with a button

Elements and CSS used

HTML elements	CSS features
nav, a, button, article, h1, p, time, b	@media print, display: none, page-break-inside, attr(), @page, border: double

Build guide

1. Write the voucher article and a nav with a print button.
2. Style the voucher with a double border.
3. In @media print hide .no-print.
4. Prevent the voucher splitting across pages.
5. Print link hrefs after links.
6. Set @page margins and test with print preview.

Project 969: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - Voucher</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav class="no-print"><a href="index.html">Back</a> &middot;
<button onclick="print()">Print this voucher</button></nav>
    <article class="voucher">
      <h1>Suez Auto Service gift voucher</h1>
      <p class="amount">200 EGP</p>
      <p>Valid for any service until <time datetime="2027-09-11">11
September 2027</time>.</p>
      <p class="code">Code: <b>GIFT-AUTO-2026</b></p>
      <p class="small">Present this voucher in Suez. Not exchangeable
for cash.</p>
    </article>
  </main>
</body>
</html>
```

Project 969: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.voucher { border: 4px double var(--brand); padding: 2rem; text-align:
 center; border-radius: 8px; }
h1 { color: var(--brand); margin-top: 0; }
.amount { font-size: 3rem; font-weight: 800; margin: 0; }
.code { font-family: monospace; font-size: 1.2rem; background: var(--
accent); display: inline-block; padding: .4rem 1rem; }
.small { font-size: .8rem; color: var(--muted); }
@media print {
  .no-print { display: none; }
  body { margin: 0; }
  main { max-width: none; margin: 0; }
  .voucher { border-color: #000; page-break-inside: avoid; }
  a[href]::after { content: " (" attr(href) ")"; }
}
```

```
@page { margin: 2cm; }
```

Project 969 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - Voucher</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav class="no-print">Back · <butto...	A block of navigation links; aria-label names it for screen readers.
<article class="voucher">	A self-contained piece: card, post, product.
Suez Auto Service gift voucher	The main heading; only one per page.
200 EGP	A paragraph of text.
Valid for any service until <time datetime="2027-09-11">11 Septe...	A date or time; datetime holds the machine-readable value.

Line	What it does
Code: GIFT-AUTO-2026	Keyword or name drawn to attention without extra importance.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 4px double var(--brand);	Changes the visual order of a flex item without changing the source.
text-align: center;	Centres inline content such as text.
border-radius: 8px;	Rounds the corners.
font-size: 3rem;	Size of the text.

Declaration	What it does
font-weight: 800;	Thickness of the text.
background: var(--accent);	Background colour or image.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
@media print {	Applies only when printing.
display: none;	Removes the element from rendering completely.
border-color: #000;	The line around the element: width, style and colour.
a[href]::after {	Generated content inserted after the element's content.
content: " (" attr(href) ")";	The text or empty string for a pseudo-element.
@page { margin: 2cm; }	Sets the printed page margins.

Check your work

- Nav hidden in print
- Voucher on one page
- Black border when printed
- Print button works

Exercises

1. Add a barcode-like pattern with repeating-linear-gradient.
2. Add two vouchers per page with columns.
3. Add a QR code image.

Theme data for this project

Field	Value
Business	Suez Auto Service

Field	Value
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 970: Printable voucher for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 2 | Files: index.html, styles.css

Brief

Design a gift voucher that looks good on screen and prints cleanly: hide navigation, avoid page breaks, print link URLs and set page margins.

Learning goals

- Write @media print rules
- Use @page
- Trigger printing with a button

Elements and CSS used

HTML elements	CSS features
nav, a, button, article, h1, p, time, b	@media print, display: none, page-break-inside, attr(), @page, border: double

Build guide

1. Write the voucher article and a nav with a print button.
2. Style the voucher with a double border.
3. In @media print hide .no-print.
4. Prevent the voucher splitting across pages.
5. Print link hrefs after links.
6. Set @page margins and test with print preview.

Project 970: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - Voucher</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav class="no-print"><a href="index.html">Back</a> &middot;
<button onclick="print()">Print this voucher</button></nav>
    <article class="voucher">
      <h1>Luxor Music Academy gift voucher</h1>
      <p class="amount">200 EGP</p>
      <p>Valid for any course until <time datetime="2027-09-11">11
September 2027</time>.</p>
      <p class="code">Code: <b>GIFT-MUSI-2026</b></p>
      <p class="small">Present this voucher in Luxor. Not
exchangeable for cash.</p>
    </article>
  </main>
</body>
</html>
```

Project 970: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.voucher { border: 4px double var(--brand); padding: 2rem; text-align:
 center; border-radius: 8px; }
h1 { color: var(--brand); margin-top: 0; }
.amount { font-size: 3rem; font-weight: 800; margin: 0; }
.code { font-family: monospace; font-size: 1.2rem; background: var(--
accent); display: inline-block; padding: .4rem 1rem; }
.small { font-size: .8rem; color: var(--muted); }
@media print {
  .no-print { display: none; }
  body { margin: 0; }
  main { max-width: none; margin: 0; }
  .voucher { border-color: #000; page-break-inside: avoid; }
  a[href]::after { content: " (" attr(href) ")"; }
}
```

```
@page { margin: 2cm; }
```

Project 970 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - Voucher</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav class="no-print">Back · <butto...	A block of navigation links; aria-label names it for screen readers.
<article class="voucher">	A self-contained piece: card, post, product.
Luxor Music Academy gift voucher	The main heading; only one per page.
200 EGP	A paragraph of text.
Valid for any course until <time datetime="2027-09-11">11 Septem...	A date or time; datetime holds the machine-readable value.

Line	What it does
Code: GIFT-MUSI-2026	Keyword or name drawn to attention without extra importance.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 4px double var(--brand);	Changes the visual order of a flex item without changing the source.
text-align: center;	Centres inline content such as text.
border-radius: 8px;	Rounds the corners.
font-size: 3rem;	Size of the text.

Declaration	What it does
font-weight: 800;	Thickness of the text.
background: var(--accent);	Background colour or image.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
@media print {	Applies only when printing.
display: none;	Removes the element from rendering completely.
border-color: #000;	The line around the element: width, style and colour.
a[href]::after {	Generated content inserted after the element's content.
content: " (" attr(href) ")";	The text or empty string for a pseudo-element.
@page { margin: 2cm; }	Sets the printed page margins.

Check your work

- Nav hidden in print
- Voucher on one page
- Black border when printed
- Print button works

Exercises

1. Add a barcode-like pattern with repeating-linear-gradient.
2. Add two vouchers per page with columns.
3. Add a QR code image.

Theme data for this project

Field	Value
Business	Luxor Music Academy

Field	Value
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 971: Printable voucher for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 2 | Files: index.html, styles.css

Brief

Design a gift voucher that looks good on screen and prints cleanly: hide navigation, avoid page breaks, print link URLs and set page margins.

Learning goals

- Write @media print rules
- Use @page
- Trigger printing with a button

Elements and CSS used

HTML elements	CSS features
nav, a, button, article, h1, p, time, b	@media print, display: none, page-break-inside, attr(), @page, border: double

Build guide

1. Write the voucher article and a nav with a print button.
2. Style the voucher with a double border.
3. In @media print hide .no-print.
4. Prevent the voucher splitting across pages.
5. Print link hrefs after links.
6. Set @page margins and test with print preview.

Project 971: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - Voucher</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav class="no-print"><a href="index.html">Back</a> &middot;
<button onclick="print()">Print this voucher</button></nav>
    <article class="voucher">
      <h1>Port Said Seafood gift voucher</h1>
      <p class="amount">200 EGP</p>
      <p>Valid for any dish until <time datetime="2027-09-11">11
September 2027</time>.</p>
      <p class="code">Code: <b>GIFT-REST-2026</b></p>
      <p class="small">Present this voucher in Port Said. Not
exchangeable for cash.</p>
    </article>
  </main>
</body>
</html>
```

Project 971: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.voucher { border: 4px double var(--brand); padding: 2rem; text-align:
 center; border-radius: 8px; }
h1 { color: var(--brand); margin-top: 0; }
.amount { font-size: 3rem; font-weight: 800; margin: 0; }
.code { font-family: monospace; font-size: 1.2rem; background: var(--
accent); display: inline-block; padding: .4rem 1rem; }
.small { font-size: .8rem; color: var(--muted); }
@media print {
  .no-print { display: none; }
  body { margin: 0; }
  main { max-width: none; margin: 0; }
  .voucher { border-color: #000; page-break-inside: avoid; }
  a[href]::after { content: " (" attr(href) ")"; }
}
```

```
@page { margin: 2cm; }
```

Project 971 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - Voucher</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav class="no-print">Back · <butto...	A block of navigation links; aria-label names it for screen readers.
<article class="voucher">	A self-contained piece: card, post, product.
Port Said Seafood gift voucher	The main heading; only one per page.
200 EGP	A paragraph of text.
Valid for any dish until <time datetime="2027-09-11">11 Septembe...	A date or time; datetime holds the machine-readable value.

Line	What it does
Code: GIFT-REST-2026	Keyword or name drawn to attention without extra importance.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 4px double var(--brand);	Changes the visual order of a flex item without changing the source.
text-align: center;	Centres inline content such as text.
border-radius: 8px;	Rounds the corners.
font-size: 3rem;	Size of the text.

Declaration	What it does
font-weight: 800;	Thickness of the text.
background: var(--accent);	Background colour or image.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
@media print {	Applies only when printing.
display: none;	Removes the element from rendering completely.
border-color: #000;	The line around the element: width, style and colour.
a[href]::after {	Generated content inserted after the element's content.
content: " (" attr(href) ")";	The text or empty string for a pseudo-element.
@page { margin: 2cm; }	Sets the printed page margins.

Check your work

- Nav hidden in print
- Voucher on one page
- Black border when printed
- Print button works

Exercises

1. Add a barcode-like pattern with repeating-linear-gradient.
2. Add two vouchers per page with columns.
3. Add a QR code image.

Theme data for this project

Field	Value
Business	Port Said Seafood

Field	Value
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 972: Printable voucher for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 2 | Files: index.html, styles.css

Brief

Design a gift voucher that looks good on screen and prints cleanly: hide navigation, avoid page breaks, print link URLs and set page margins.

Learning goals

- Write @media print rules
- Use @page
- Trigger printing with a button

Elements and CSS used

HTML elements	CSS features
nav, a, button, article, h1, p, time, b	@media print, display: none, page-break-inside, attr(), @page, border: double

Build guide

1. Write the voucher article and a nav with a print button.
2. Style the voucher with a double border.
3. In @media print hide .no-print.
4. Prevent the voucher splitting across pages.
5. Print link hrefs after links.
6. Set @page margins and test with print preview.

Project 972: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - Voucher</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav class="no-print"><a href="index.html">Back</a> &middot;
<button onclick="print()">Print this voucher</button></nav>
    <article class="voucher">
      <h1>Delta Kids Library gift voucher</h1>
      <p class="amount">200 EGP</p>
      <p>Valid for any programme until <time datetime="2027-09-11">11
September 2027</time>.</p>
      <p class="code">Code: <b>GIFT-LIBR-2026</b></p>
      <p class="small">Present this voucher in Tanta. Not
exchangeable for cash.</p>
    </article>
  </main>
</body>
</html>
```

Project 972: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.voucher { border: 4px double var(--brand); padding: 2rem; text-align:
 center; border-radius: 8px; }
h1 { color: var(--brand); margin-top: 0; }
.amount { font-size: 3rem; font-weight: 800; margin: 0; }
.code { font-family: monospace; font-size: 1.2rem; background: var(--
accent); display: inline-block; padding: .4rem 1rem; }
.small { font-size: .8rem; color: var(--muted); }
@media print {
  .no-print { display: none; }
  body { margin: 0; }
  main { max-width: none; margin: 0; }
  .voucher { border-color: #000; page-break-inside: avoid; }
  a[href]::after { content: " (" attr(href) ")"; }
}
```

```
@page { margin: 2cm; }
```

Project 972 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - Voucher</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav class="no-print">Back · <butto...	A block of navigation links; aria-label names it for screen readers.
<article class="voucher">	A self-contained piece: card, post, product.
Delta Kids Library gift voucher	The main heading; only one per page.
200 EGP	A paragraph of text.
Valid for any programme until <time datetime="2027-09-11">11 Sep...	A date or time; datetime holds the machine-readable value.

Line	What it does
Code: GIFT-LIBR-2026	Keyword or name drawn to attention without extra importance.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 4px double var(--brand);	Changes the visual order of a flex item without changing the source.
text-align: center;	Centres inline content such as text.
border-radius: 8px;	Rounds the corners.
font-size: 3rem;	Size of the text.

Declaration	What it does
font-weight: 800;	Thickness of the text.
background: var(--accent);	Background colour or image.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
@media print {	Applies only when printing.
display: none;	Removes the element from rendering completely.
border-color: #000;	The line around the element: width, style and colour.
a[href]::after {	Generated content inserted after the element's content.
content: " (" attr(href) ")";	The text or empty string for a pseudo-element.
@page { margin: 2cm; }	Sets the printed page margins.

Check your work

- Nav hidden in print
- Voucher on one page
- Black border when printed
- Print button works

Exercises

1. Add a barcode-like pattern with repeating-linear-gradient.
2. Add two vouchers per page with columns.
3. Add a QR code image.

Theme data for this project

Field	Value
Business	Delta Kids Library

Field	Value
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 973: Printable voucher for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Design a gift voucher that looks good on screen and prints cleanly: hide navigation, avoid page breaks, print link URLs and set page margins.

Learning goals

- Write @media print rules
- Use @page
- Trigger printing with a button

Elements and CSS used

HTML elements	CSS features
nav, a, button, article, h1, p, time, b	@media print, display: none, page-break-inside, attr(), @page, border: double

Build guide

1. Write the voucher article and a nav with a print button.
2. Style the voucher with a double border.
3. In @media print hide .no-print.
4. Prevent the voucher splitting across pages.
5. Print link hrefs after links.
6. Set @page margins and test with print preview.

Project 973: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - Voucher</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav class="no-print"><a href="index.html">Back</a> &middot;
<button onclick="print()">Print this voucher</button></nav>
    <article class="voucher">
      <h1>Nubian Guest House gift voucher</h1>
      <p class="amount">200 EGP</p>
      <p>Valid for any room until <time datetime="2027-09-11">11
September 2027</time>.</p>
      <p class="code">Code: <b>GIFT-GUES-2026</b></p>
      <p class="small">Present this voucher in Aswan. Not
exchangeable for cash.</p>
    </article>
  </main>
</body>
</html>
```

Project 973: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.voucher { border: 4px double var(--brand); padding: 2rem; text-align:
 center; border-radius: 8px; }
h1 { color: var(--brand); margin-top: 0; }
.amount { font-size: 3rem; font-weight: 800; margin: 0; }
.code { font-family: monospace; font-size: 1.2rem; background: var(--
accent); display: inline-block; padding: .4rem 1rem; }
.small { font-size: .8rem; color: var(--muted); }
@media print {
  .no-print { display: none; }
  body { margin: 0; }
  main { max-width: none; margin: 0; }
  .voucher { border-color: #000; page-break-inside: avoid; }
  a[href]::after { content: " (" attr(href) ")"; }
}
```

```
@page { margin: 2cm; }
```

Project 973 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - Voucher</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav class="no-print">Back · <butto...	A block of navigation links; aria-label names it for screen readers.
<article class="voucher">	A self-contained piece: card, post, product.
Nubian Guest House gift voucher	The main heading; only one per page.
200 EGP	A paragraph of text.
Valid for any room until <time datetime="2027-09-11">11 Septembe...	A date or time; datetime holds the machine-readable value.

Line	What it does
Code: GIFT-GUES-2026	Keyword or name drawn to attention without extra importance.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 4px double var(--brand);	Changes the visual order of a flex item without changing the source.
text-align: center;	Centres inline content such as text.
border-radius: 8px;	Rounds the corners.
font-size: 3rem;	Size of the text.

Declaration	What it does
font-weight: 800;	Thickness of the text.
background: var(--accent);	Background colour or image.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
@media print {	Applies only when printing.
display: none;	Removes the element from rendering completely.
border-color: #000;	The line around the element: width, style and colour.
a[href]::after {	Generated content inserted after the element's content.
content: " (" attr(href) ")";	The text or empty string for a pseudo-element.
@page { margin: 2cm; }	Sets the printed page margins.

Check your work

- Nav hidden in print
- Voucher on one page
- Black border when printed
- Print button works

Exercises

1. Add a barcode-like pattern with repeating-linear-gradient.
2. Add two vouchers per page with columns.
3. Add a QR code image.

Theme data for this project

Field	Value
Business	Nubian Guest House

Field	Value
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 974: Printable voucher for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 2 | Files: index.html, styles.css

Brief

Design a gift voucher that looks good on screen and prints cleanly: hide navigation, avoid page breaks, print link URLs and set page margins.

Learning goals

- Write @media print rules
- Use @page
- Trigger printing with a button

Elements and CSS used

HTML elements	CSS features
nav, a, button, article, h1, p, time, b	@media print, display: none, page-break-inside, attr(), @page, border: double

Build guide

1. Write the voucher article and a nav with a print button.
2. Style the voucher with a double border.
3. In @media print hide .no-print.
4. Prevent the voucher splitting across pages.
5. Print link hrefs after links.
6. Set @page margins and test with print preview.

Project 974: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - Voucher</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav class="no-print"><a href="index.html">Back</a> &middot;
<button onclick="print()">Print this voucher</button></nav>
    <article class="voucher">
      <h1>Ismailia Cycling Store gift voucher</h1>
      <p class="amount">200 EGP</p>
      <p>Valid for any bike until <time datetime="2027-09-11">11
September 2027</time>.</p>
      <p class="code">Code: <b>GIFT-CYCL-2026</b></p>
      <p class="small">Present this voucher in Ismailia. Not
exchangeable for cash.</p>
    </article>
  </main>
</body>
</html>
```

Project 974: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.voucher { border: 4px double var(--brand); padding: 2rem; text-align:
 center; border-radius: 8px; }
h1 { color: var(--brand); margin-top: 0; }
.amount { font-size: 3rem; font-weight: 800; margin: 0; }
.code { font-family: monospace; font-size: 1.2rem; background: var(--
accent); display: inline-block; padding: .4rem 1rem; }
.small { font-size: .8rem; color: var(--muted); }
@media print {
  .no-print { display: none; }
  body { margin: 0; }
  main { max-width: none; margin: 0; }
  .voucher { border-color: #000; page-break-inside: avoid; }
  a[href]::after { content: " (" attr(href) ")"; }
}
```

```
@page { margin: 2cm; }
```

Project 974 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - Voucher</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav class="no-print">Back · <butto...	A block of navigation links; aria-label names it for screen readers.
<article class="voucher">	A self-contained piece: card, post, product.
Ismailia Cycling Store gift voucher	The main heading; only one per page.
200 EGP	A paragraph of text.
Valid for any bike until <time datetime="2027-09-11">11 Septembe...	A date or time; datetime holds the machine-readable value.

Line	What it does
Code: GIFT-CYCL-2026	Keyword or name drawn to attention without extra importance.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 4px double var(--brand);	Changes the visual order of a flex item without changing the source.
text-align: center;	Centres inline content such as text.
border-radius: 8px;	Rounds the corners.
font-size: 3rem;	Size of the text.

Declaration	What it does
font-weight: 800;	Thickness of the text.
background: var(--accent);	Background colour or image.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
@media print {	Applies only when printing.
display: none;	Removes the element from rendering completely.
border-color: #000;	The line around the element: width, style and colour.
a[href]::after {	Generated content inserted after the element's content.
content: " (" attr(href) ")";	The text or empty string for a pseudo-element.
@page { margin: 2cm; }	Sets the printed page margins.

Check your work

- Nav hidden in print
- Voucher on one page
- Black border when printed
- Print button works

Exercises

1. Add a barcode-like pattern with repeating-linear-gradient.
2. Add two vouchers per page with columns.
3. Add a QR code image.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store

Field	Value
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 975: Printable voucher for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 2 | Files: index.html, styles.css

Brief

Design a gift voucher that looks good on screen and prints cleanly: hide navigation, avoid page breaks, print link URLs and set page margins.

Learning goals

- Write @media print rules
- Use @page
- Trigger printing with a button

Elements and CSS used

HTML elements	CSS features
nav, a, button, article, h1, p, time, b	@media print, display: none, page-break-inside, attr(), @page, border: double

Build guide

1. Write the voucher article and a nav with a print button.
2. Style the voucher with a double border.
3. In @media print hide .no-print.
4. Prevent the voucher splitting across pages.
5. Print link hrefs after links.
6. Set @page margins and test with print preview.

Project 975: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - Voucher</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <nav class="no-print"><a href="index.html">Back</a> &middot;
<button onclick="print()">Print this voucher</button></nav>
    <article class="voucher">
      <h1>Minya Coding Club gift voucher</h1>
      <p class="amount">200 EGP</p>
      <p>Valid for any workshop until <time datetime="2027-09-11">11
September 2027</time>.</p>
      <p class="code">Code: <b>GIFT-CODI-2026</b></p>
      <p class="small">Present this voucher in Minya. Not
exchangeable for cash.</p>
    </article>
  </main>
</body>
</html>
```

Project 975: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 36rem; margin: 2rem auto; padding: 0 1rem; }
.voucher { border: 4px double var(--brand); padding: 2rem; text-align:
 center; border-radius: 8px; }
h1 { color: var(--brand); margin-top: 0; }
.amount { font-size: 3rem; font-weight: 800; margin: 0; }
.code { font-family: monospace; font-size: 1.2rem; background: var(--
accent); display: inline-block; padding: .4rem 1rem; }
.small { font-size: .8rem; color: var(--muted); }
@media print {
  .no-print { display: none; }
  body { margin: 0; }
  main { max-width: none; margin: 0; }
  .voucher { border-color: #000; page-break-inside: avoid; }
  a[href]::after { content: " (" attr(href) ")"; }
}
```

```
@page { margin: 2cm; }
```

Project 975 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - Voucher</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<nav class="no-print">Back · <butto...	A block of navigation links; aria-label names it for screen readers.
<article class="voucher">	A self-contained piece: card, post, product.
Minya Coding Club gift voucher	The main heading; only one per page.
200 EGP	A paragraph of text.
Valid for any workshop until <time datetime="2027-09-11">11 Sept...	A date or time; datetime holds the machine-readable value.

Line	What it does
Code: GIFT-CODI-2026	Keyword or name drawn to attention without extra importance.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 36rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
border: 4px double var(--brand);	Changes the visual order of a flex item without changing the source.
text-align: center;	Centres inline content such as text.
border-radius: 8px;	Rounds the corners.
font-size: 3rem;	Size of the text.

Declaration	What it does
font-weight: 800;	Thickness of the text.
background: var(--accent);	Background colour or image.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
@media print {	Applies only when printing.
display: none;	Removes the element from rendering completely.
border-color: #000;	The line around the element: width, style and colour.
a[href]::after {	Generated content inserted after the element's content.
content: " (" attr(href) ")";	The text or empty string for a pseudo-element.
@page { margin: 2cm; }	Sets the printed page margins.

Check your work

- Nav hidden in print
- Voucher on one page
- Black border when printed
- Print button works

Exercises

1. Add a barcode-like pattern with repeating-linear-gradient.
2. Add two vouchers per page with columns.
3. Add a QR code image.

Theme data for this project

Field	Value
Business	Minya Coding Club

Field	Value
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Month calendar

Level 3 | 25 projects, one per theme

Draw a month grid as a table with fixed equal columns, tall cells, event labels that shrink to dots on phones and a highlighted Friday column.

Project 976: Month calendar for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 3 | Files: index.html, styles.css

Brief

Draw a month grid as a table with fixed equal columns, tall cells, event labels that shrink to dots on phones and a highlighted Friday column.

Learning goals

- Use table-layout: fixed for equal columns
- Use :last-child for a column
- Adapt content presentation with a media query

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, span	table-layout: fixed, vertical-align: top, height on td, :last-child, @media (max-width)

Build guide

1. Write the header row with day names starting Saturday.
2. Write the day cells in rows of seven, padding the first row with empty cells.
3. Add a span for event labels.
4. Fix the layout and set tall cells aligned top.
5. Colour the last column.
6. On narrow screens shrink event labels to dots.

Project 976: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - September</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cairo Book Shop calendar</h1>
    <table class="cal">
      <caption>September 2026</caption>
      <thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</
th><th>Wed</th><th>Thu</th><th>Fri</th></tr></thead>
      <tbody>
        <tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</
td><td class="event">5<span>book</span></td></tr>
        <tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</
td><td>11</td><td class="event">12<span>book</span></td></tr>
        <tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</
td><td>18</td><td class="event">19<span>book</span></td></tr>
        <tr><td>20</td><td>21</td><td>22</td><td>23</td><td>24</
td><td>25</td><td>26</td></tr>
        <tr><td>27</td><td>28</td><td>29</td><td>30</td><td></
td><td></td><td></td></tr>
      </tbody>
    </table>
  </main>
</body>
</html>
```

Project 976: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.cal { width: 100%; border-collapse: collapse; table-layout: fixed; }
caption { font-size: 1.3rem; font-weight: 700; padding: .5rem; }
th { padding: .5rem; background: var(--accent); }
td { height: 5rem; vertical-align: top; padding: .3rem; border: 1px
solid var(--line); font-size: .9rem; }
td span { display: block; margin-top: .3rem; background: var(--brand);
 color: #fff; font-size: .7rem; padding: .1rem .3rem; border-radius:
```

```
4px; }
th:last-child, td:last-child { color: var(--brand); }
@media (max-width: 600px) { td { height: 3rem; } td span { font-size:
0; height: .5rem; width: .5rem; border-radius: 50%; padding: 0; } }
```

Project 976 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - September</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cairo Book Shop calendar	The main heading; only one per page.
<table class="cal">	Tabular data in rows and columns.
<caption>September 2026</caption>	Title of the table.
<thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</th><th>Wed<...	Group of header rows.
<tbody>	Group of data rows.
<tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</td><td c...	A table row.

Line	What it does
<tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><...	A data cell.
<tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18<//...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.

Declaration	What it does
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
table-layout: fixed;	Columns get equal widths regardless of content; faster rendering.
font-size: 1.3rem;	Size of the text.
font-weight: 700;	Thickness of the text.
background: var(--accent);	Background colour or image.
vertical-align: top;	Aligns cell content to the top.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 4px;	Rounds the corners.
th:last-child, td:last-child {	The last child of its parent.
@media (max-width: 600px) { td { height: 3rem; } td span { font-siz...	Turns a square into a circle.

Check your work

- Seven cells in every row
- Columns equal width
- Events visible on mobile as dots
- Caption gives the month

Exercises

1. Generate the cells with JavaScript for any month.
2. Highlight today with a class.
3. Make cells links to day pages.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 977: Month calendar for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 3 | Files: index.html, styles.css

Brief

Draw a month grid as a table with fixed equal columns, tall cells, event labels that shrink to dots on phones and a highlighted Friday column.

Learning goals

- Use table-layout: fixed for equal columns
- Use :last-child for a column
- Adapt content presentation with a media query

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, span	table-layout: fixed, vertical-align: top, height on td, :last-child, @media (max-width)

Build guide

1. Write the header row with day names starting Saturday.
2. Write the day cells in rows of seven, padding the first row with empty cells.
3. Add a span for event labels.
4. Fix the layout and set tall cells aligned top.
5. Colour the last column.
6. On narrow screens shrink event labels to dots.

Project 977: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - September</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Nile Bakery calendar</h1>
    <table class="cal">
      <caption>September 2026</caption>
      <thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</
th><th>Wed</th><th>Thu</th><th>Fri</th></tr></thead>
      <tbody>
        <tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</
td><td class="event">5<span>pastry</span></td></tr>
        <tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</
td><td>11</td><td class="event">12<span>pastry</span></td></tr>
        <tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</
td><td>18</td><td class="event">19<span>pastry</span></td></tr>
        <tr><td>20</td><td>21</td><td>22</td><td>23</td><td>24</
td><td>25</td><td>26</td></tr>
        <tr><td>27</td><td>28</td><td>29</td><td>30</td><td></
td><td></td><td></td></tr>
      </tbody>
    </table>
  </main>
</body>
</html>
```

Project 977: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.cal { width: 100%; border-collapse: collapse; table-layout: fixed; }
caption { font-size: 1.3rem; font-weight: 700; padding: .5rem; }
th { padding: .5rem; background: var(--accent); }
td { height: 5rem; vertical-align: top; padding: .3rem; border: 1px
solid var(--line); font-size: .9rem; }
td span { display: block; margin-top: .3rem; background: var(--brand);
 color: #fff; font-size: .7rem; padding: .1rem .3rem; border-radius:
```

```
4px; }
th:last-child, td:last-child { color: var(--brand); }
@media (max-width: 600px) { td { height: 3rem; } td span { font-size:
0; height: .5rem; width: .5rem; border-radius: 50%; padding: 0; } }
```

Project 977 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - September</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Nile Bakery calendar	The main heading; only one per page.
<table class="cal">	Tabular data in rows and columns.
<caption>September 2026</caption>	Title of the table.
<thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</th><th>Wed<...	Group of header rows.
<tbody>	Group of data rows.
<tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</td><td c...	A table row.

Line	What it does
<tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><...	A data cell.
<tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18<//...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.

Declaration	What it does
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
table-layout: fixed;	Columns get equal widths regardless of content; faster rendering.
font-size: 1.3rem;	Size of the text.
font-weight: 700;	Thickness of the text.
background: var(--accent);	Background colour or image.
vertical-align: top;	Aligns cell content to the top.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 4px;	Rounds the corners.
th:last-child, td:last-child {	The last child of its parent.
@media (max-width: 600px) { td { height: 3rem; } td span { font-siz...	Turns a square into a circle.

Check your work

- Seven cells in every row
- Columns equal width
- Events visible on mobile as dots
- Caption gives the month

Exercises

1. Generate the cells with JavaScript for any month.
2. Highlight today with a class.
3. Make cells links to day pages.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 978: Month calendar for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 3 | Files: index.html, styles.css

Brief

Draw a month grid as a table with fixed equal columns, tall cells, event labels that shrink to dots on phones and a highlighted Friday column.

Learning goals

- Use table-layout: fixed for equal columns
- Use :last-child for a column
- Adapt content presentation with a media query

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, span	table-layout: fixed, vertical-align: top, height on td, :last-child, @media (max-width)

Build guide

1. Write the header row with day names starting Saturday.
2. Write the day cells in rows of seven, padding the first row with empty cells.
3. Add a span for event labels.
4. Fix the layout and set tall cells aligned top.
5. Colour the last column.
6. On narrow screens shrink event labels to dots.

Project 978: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - September</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Pyramid Fitness calendar</h1>
    <table class="cal">
      <caption>September 2026</caption>
      <thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</
th><th>Wed</th><th>Thu</th><th>Fri</th></tr></thead>
      <tbody>
        <tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</
td><td class="event">5<span>class</span></td></tr>
        <tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</
td><td>11</td><td class="event">12<span>class</span></td></tr>
        <tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</
td><td>18</td><td class="event">19<span>class</span></td></tr>
        <tr><td>20</td><td>21</td><td>22</td><td>23</td><td>24</
td><td>25</td><td>26</td></tr>
        <tr><td>27</td><td>28</td><td>29</td><td>30</td><td></
td><td></td><td></td></tr>
      </tbody>
    </table>
  </main>
</body>
</html>
```

Project 978: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.cal { width: 100%; border-collapse: collapse; table-layout: fixed; }
caption { font-size: 1.3rem; font-weight: 700; padding: .5rem; }
th { padding: .5rem; background: var(--accent); }
td { height: 5rem; vertical-align: top; padding: .3rem; border: 1px
solid var(--line); font-size: .9rem; }
td span { display: block; margin-top: .3rem; background: var(--brand);
 color: #fff; font-size: .7rem; padding: .1rem .3rem; border-radius:
```

```
4px; }
th:last-child, td:last-child { color: var(--brand); }
@media (max-width: 600px) { td { height: 3rem; } td span { font-size:
0; height: .5rem; width: .5rem; border-radius: 50%; padding: 0; } }
```

Project 978 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - September</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Pyramid Fitness calendar	The main heading; only one per page.
<table class="cal">	Tabular data in rows and columns.
<caption>September 2026</caption>	Title of the table.
<thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</th><th>Wed<...	Group of header rows.
<tbody>	Group of data rows.
<tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</td><td c...	A table row.

Line	What it does
<tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><...	A data cell.
<tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18<//...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.

Declaration	What it does
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
table-layout: fixed;	Columns get equal widths regardless of content; faster rendering.
font-size: 1.3rem;	Size of the text.
font-weight: 700;	Thickness of the text.
background: var(--accent);	Background colour or image.
vertical-align: top;	Aligns cell content to the top.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 4px;	Rounds the corners.
th:last-child, td:last-child {	The last child of its parent.
@media (max-width: 600px) { td { height: 3rem; } td span { font-siz...	Turns a square into a circle.

Check your work

- Seven cells in every row
- Columns equal width
- Events visible on mobile as dots
- Caption gives the month

Exercises

1. Generate the cells with JavaScript for any month.
2. Highlight today with a class.
3. Make cells links to day pages.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 979: Month calendar for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 3 | Files: index.html, styles.css

Brief

Draw a month grid as a table with fixed equal columns, tall cells, event labels that shrink to dots on phones and a highlighted Friday column.

Learning goals

- Use table-layout: fixed for equal columns
- Use :last-child for a column
- Adapt content presentation with a media query

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, span	table-layout: fixed, vertical-align: top, height on td, :last-child, @media (max-width)

Build guide

1. Write the header row with day names starting Saturday.
2. Write the day cells in rows of seven, padding the first row with empty cells.
3. Add a span for event labels.
4. Fix the layout and set tall cells aligned top.
5. Colour the last column.
6. On narrow screens shrink event labels to dots.

Project 979: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - September</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Delta Dental Clinic calendar</h1>
    <table class="cal">
      <caption>September 2026</caption>
      <thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</
th><th>Wed</th><th>Thu</th><th>Fri</th></tr></thead>
      <tbody>
        <tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</
td><td class="event">5<span>service</span></td></tr>
        <tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</
td><td>11</td><td class="event">12<span>service</span></td></tr>
        <tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</
td><td>18</td><td class="event">19<span>service</span></td></tr>
        <tr><td>20</td><td>21</td><td>22</td><td>23</td><td>24</
td><td>25</td><td>26</td></tr>
        <tr><td>27</td><td>28</td><td>29</td><td>30</td><td></
td><td></td><td></td></tr>
      </tbody>
    </table>
  </main>
</body>
</html>
```

Project 979: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.cal { width: 100%; border-collapse: collapse; table-layout: fixed; }
caption { font-size: 1.3rem; font-weight: 700; padding: .5rem; }
th { padding: .5rem; background: var(--accent); }
td { height: 5rem; vertical-align: top; padding: .3rem; border: 1px
solid var(--line); font-size: .9rem; }
td span { display: block; margin-top: .3rem; background: var(--brand);
 color: #fff; font-size: .7rem; padding: .1rem .3rem; border-radius:
```

```
4px; }
th:last-child, td:last-child { color: var(--brand); }
@media (max-width: 600px) { td { height: 3rem; } td span { font-size:
0; height: .5rem; width: .5rem; border-radius: 50%; padding: 0; } }
```

Project 979 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - September</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Delta Dental Clinic calendar	The main heading; only one per page.
<table class="cal">	Tabular data in rows and columns.
<caption>September 2026</caption>	Title of the table.
<thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</th><th>Wed<...	Group of header rows.
<tbody>	Group of data rows.
<tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</td><td c...	A table row.

Line	What it does
<tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><...	A data cell.
<tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18<//...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.

Declaration	What it does
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
table-layout: fixed;	Columns get equal widths regardless of content; faster rendering.
font-size: 1.3rem;	Size of the text.
font-weight: 700;	Thickness of the text.
background: var(--accent);	Background colour or image.
vertical-align: top;	Aligns cell content to the top.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 4px;	Rounds the corners.
th:last-child, td:last-child {	The last child of its parent.
@media (max-width: 600px) { td { height: 3rem; } td span { font-siz...	Turns a square into a circle.

Check your work

- Seven cells in every row
- Columns equal width
- Events visible on mobile as dots
- Caption gives the month

Exercises

1. Generate the cells with JavaScript for any month.
2. Highlight today with a class.
3. Make cells links to day pages.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 980: Month calendar for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 3 | Files: index.html, styles.css

Brief

Draw a month grid as a table with fixed equal columns, tall cells, event labels that shrink to dots on phones and a highlighted Friday column.

Learning goals

- Use table-layout: fixed for equal columns
- Use :last-child for a column
- Adapt content presentation with a media query

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, span	table-layout: fixed, vertical-align: top, height on td, :last-child, @media (max-width)

Build guide

1. Write the header row with day names starting Saturday.
2. Write the day cells in rows of seven, padding the first row with empty cells.
3. Add a span for event labels.
4. Fix the layout and set tall cells aligned top.
5. Colour the last column.
6. On narrow screens shrink event labels to dots.

Project 980: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - September</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Red Sea Travel calendar</h1>
    <table class="cal">
      <caption>September 2026</caption>
      <thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</
th><th>Wed</th><th>Thu</th><th>Fri</th></tr></thead>
      <tbody>
        <tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</
td><td class="event">5<span>tour</span></td></tr>
        <tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</
td><td>11</td><td class="event">12<span>tour</span></td></tr>
        <tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</
td><td>18</td><td class="event">19<span>tour</span></td></tr>
        <tr><td>20</td><td>21</td><td>22</td><td>23</td><td>24</
td><td>25</td><td>26</td></tr>
        <tr><td>27</td><td>28</td><td>29</td><td>30</td><td></
td><td></td><td></td></tr>
      </tbody>
    </table>
  </main>
</body>
</html>
```

Project 980: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.cal { width: 100%; border-collapse: collapse; table-layout: fixed; }
caption { font-size: 1.3rem; font-weight: 700; padding: .5rem; }
th { padding: .5rem; background: var(--accent); }
td { height: 5rem; vertical-align: top; padding: .3rem; border: 1px
solid var(--line); font-size: .9rem; }
td span { display: block; margin-top: .3rem; background: var(--brand);
 color: #fff; font-size: .7rem; padding: .1rem .3rem; border-radius:
```

```
4px; }
th:last-child, td:last-child { color: var(--brand); }
@media (max-width: 600px) { td { height: 3rem; } td span { font-size:
0; height: .5rem; width: .5rem; border-radius: 50%; padding: 0; } }
```

Project 980 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - September</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Red Sea Travel calendar	The main heading; only one per page.
<table class="cal">	Tabular data in rows and columns.
<caption>September 2026</caption>	Title of the table.
<thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</th><th>Wed<...	Group of header rows.
<tbody>	Group of data rows.
<tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</td><td c...	A table row.

Line	What it does
<tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><...	A data cell.
<tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18<//...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.

Declaration	What it does
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
table-layout: fixed;	Columns get equal widths regardless of content; faster rendering.
font-size: 1.3rem;	Size of the text.
font-weight: 700;	Thickness of the text.
background: var(--accent);	Background colour or image.
vertical-align: top;	Aligns cell content to the top.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 4px;	Rounds the corners.
th:last-child, td:last-child {	The last child of its parent.
@media (max-width: 600px) { td { height: 3rem; } td span { font-siz...	Turns a square into a circle.

Check your work

- Seven cells in every row
- Columns equal width
- Events visible on mobile as dots
- Caption gives the month

Exercises

1. Generate the cells with JavaScript for any month.
2. Highlight today with a class.
3. Make cells links to day pages.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 981: Month calendar for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 3 | Files: index.html, styles.css

Brief

Draw a month grid as a table with fixed equal columns, tall cells, event labels that shrink to dots on phones and a highlighted Friday column.

Learning goals

- Use table-layout: fixed for equal columns
- Use :last-child for a column
- Adapt content presentation with a media query

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, span	table-layout: fixed, vertical-align: top, height on td, :last-child, @media (max-width)

Build guide

1. Write the header row with day names starting Saturday.
2. Write the day cells in rows of seven, padding the first row with empty cells.
3. Add a span for event labels.
4. Fix the layout and set tall cells aligned top.
5. Colour the last column.
6. On narrow screens shrink event labels to dots.

Project 981: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - September</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Lotus Language School calendar</h1>
    <table class="cal">
      <caption>September 2026</caption>
      <thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</
th><th>Wed</th><th>Thu</th><th>Fri</th></tr></thead>
      <tbody>
        <tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</
td><td class="event">5<span>course</span></td></tr>
        <tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</
td><td>11</td><td class="event">12<span>course</span></td></tr>
        <tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</
td><td>18</td><td class="event">19<span>course</span></td></tr>
        <tr><td>20</td><td>21</td><td>22</td><td>23</td><td>24</
td><td>25</td><td>26</td></tr>
        <tr><td>27</td><td>28</td><td>29</td><td>30</td><td></
td><td></td><td></td></tr>
      </tbody>
    </table>
  </main>
</body>
</html>
```

Project 981: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.cal { width: 100%; border-collapse: collapse; table-layout: fixed; }
caption { font-size: 1.3rem; font-weight: 700; padding: .5rem; }
th { padding: .5rem; background: var(--accent); }
td { height: 5rem; vertical-align: top; padding: .3rem; border: 1px
solid var(--line); font-size: .9rem; }
td span { display: block; margin-top: .3rem; background: var(--brand);
 color: #fff; font-size: .7rem; padding: .1rem .3rem; border-radius:
```

```
4px; }
th:last-child, td:last-child { color: var(--brand); }
@media (max-width: 600px) { td { height: 3rem; } td span { font-size:
0; height: .5rem; width: .5rem; border-radius: 50%; padding: 0; } }
```

Project 981 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - September</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Lotus Language School calendar	The main heading; only one per page.
<table class="cal">	Tabular data in rows and columns.
<caption>September 2026</caption>	Title of the table.
<thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</th><th>Wed<...	Group of header rows.
<tbody>	Group of data rows.
<tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</td><td c...	A table row.

Line	What it does
<tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><...	A data cell.
<tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18<//...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.

Declaration	What it does
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
table-layout: fixed;	Columns get equal widths regardless of content; faster rendering.
font-size: 1.3rem;	Size of the text.
font-weight: 700;	Thickness of the text.
background: var(--accent);	Background colour or image.
vertical-align: top;	Aligns cell content to the top.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 4px;	Rounds the corners.
th:last-child, td:last-child {	The last child of its parent.
@media (max-width: 600px) { td { height: 3rem; } td span { font-siz...	Turns a square into a circle.

Check your work

- Seven cells in every row
- Columns equal width
- Events visible on mobile as dots
- Caption gives the month

Exercises

1. Generate the cells with JavaScript for any month.
2. Highlight today with a class.
3. Make cells links to day pages.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 982: Month calendar for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 3 | Files: index.html, styles.css

Brief

Draw a month grid as a table with fixed equal columns, tall cells, event labels that shrink to dots on phones and a highlighted Friday column.

Learning goals

- Use table-layout: fixed for equal columns
- Use :last-child for a column
- Adapt content presentation with a media query

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, span	table-layout: fixed, vertical-align: top, height on td, :last-child, @media (max-width)

Build guide

1. Write the header row with day names starting Saturday.
2. Write the day cells in rows of seven, padding the first row with empty cells.
3. Add a span for event labels.
4. Fix the layout and set tall cells aligned top.
5. Colour the last column.
6. On narrow screens shrink event labels to dots.

Project 982: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - September</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Green Leaf Cafe calendar</h1>
    <table class="cal">
      <caption>September 2026</caption>
      <thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</
th><th>Wed</th><th>Thu</th><th>Fri</th></tr></thead>
      <tbody>
        <tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</
td><td class="event">5<span>drink</span></td></tr>
        <tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</
td><td>11</td><td class="event">12<span>drink</span></td></tr>
        <tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</
td><td>18</td><td class="event">19<span>drink</span></td></tr>
        <tr><td>20</td><td>21</td><td>22</td><td>23</td><td>24</
td><td>25</td><td>26</td></tr>
        <tr><td>27</td><td>28</td><td>29</td><td>30</td><td></
td><td></td><td></td></tr>
      </tbody>
    </table>
  </main>
</body>
</html>
```

Project 982: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.cal { width: 100%; border-collapse: collapse; table-layout: fixed; }
caption { font-size: 1.3rem; font-weight: 700; padding: .5rem; }
th { padding: .5rem; background: var(--accent); }
td { height: 5rem; vertical-align: top; padding: .3rem; border: 1px
solid var(--line); font-size: .9rem; }
td span { display: block; margin-top: .3rem; background: var(--brand);
 color: #fff; font-size: .7rem; padding: .1rem .3rem; border-radius:
```

```
4px; }
th:last-child, td:last-child { color: var(--brand); }
@media (max-width: 600px) { td { height: 3rem; } td span { font-size:
0; height: .5rem; width: .5rem; border-radius: 50%; padding: 0; } }
```

Project 982 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - September</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Green Leaf Cafe calendar	The main heading; only one per page.
<table class="cal">	Tabular data in rows and columns.
<caption>September 2026</caption>	Title of the table.
<thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</th><th>Wed<...	Group of header rows.
<tbody>	Group of data rows.
<tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</td><td c...	A table row.

Line	What it does
<tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><...	A data cell.
<tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18<//...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.

Declaration	What it does
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
table-layout: fixed;	Columns get equal widths regardless of content; faster rendering.
font-size: 1.3rem;	Size of the text.
font-weight: 700;	Thickness of the text.
background: var(--accent);	Background colour or image.
vertical-align: top;	Aligns cell content to the top.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 4px;	Rounds the corners.
th:last-child, td:last-child {	The last child of its parent.
@media (max-width: 600px) { td { height: 3rem; } td span { font-siz...	Turns a square into a circle.

Check your work

- Seven cells in every row
- Columns equal width
- Events visible on mobile as dots
- Caption gives the month

Exercises

1. Generate the cells with JavaScript for any month.
2. Highlight today with a class.
3. Make cells links to day pages.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 983: Month calendar for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 3 | Files: index.html, styles.css

Brief

Draw a month grid as a table with fixed equal columns, tall cells, event labels that shrink to dots on phones and a highlighted Friday column.

Learning goals

- Use table-layout: fixed for equal columns
- Use :last-child for a column
- Adapt content presentation with a media query

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, span	table-layout: fixed, vertical-align: top, height on td, :last-child, @media (max-width)

Build guide

1. Write the header row with day names starting Saturday.
2. Write the day cells in rows of seven, padding the first row with empty cells.
3. Add a span for event labels.
4. Fix the layout and set tall cells aligned top.
5. Colour the last column.
6. On narrow screens shrink event labels to dots.

Project 983: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - September</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Sinai Trekking Club calendar</h1>
    <table class="cal">
      <caption>September 2026</caption>
      <thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</
th><th>Wed</th><th>Thu</th><th>Fri</th></tr></thead>
      <tbody>
        <tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</
td><td class="event">5<span>hike</span></td></tr>
        <tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</
td><td>11</td><td class="event">12<span>hike</span></td></tr>
        <tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</
td><td>18</td><td class="event">19<span>hike</span></td></tr>
        <tr><td>20</td><td>21</td><td>22</td><td>23</td><td>24</
td><td>25</td><td>26</td></tr>
        <tr><td>27</td><td>28</td><td>29</td><td>30</td><td></
td><td></td><td></td></tr>
      </tbody>
    </table>
  </main>
</body>
</html>
```

Project 983: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.cal { width: 100%; border-collapse: collapse; table-layout: fixed; }
caption { font-size: 1.3rem; font-weight: 700; padding: .5rem; }
th { padding: .5rem; background: var(--accent); }
td { height: 5rem; vertical-align: top; padding: .3rem; border: 1px
solid var(--line); font-size: .9rem; }
td span { display: block; margin-top: .3rem; background: var(--brand);
 color: #fff; font-size: .7rem; padding: .1rem .3rem; border-radius:
```

```
4px; }
th:last-child, td:last-child { color: var(--brand); }
@media (max-width: 600px) { td { height: 3rem; } td span { font-size:
0; height: .5rem; width: .5rem; border-radius: 50%; padding: 0; } }
```

Project 983 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - September</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Sinai Trekking Club calendar	The main heading; only one per page.
<table class="cal">	Tabular data in rows and columns.
<caption>September 2026</caption>	Title of the table.
<thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</th><th>Wed<...	Group of header rows.
<tbody>	Group of data rows.
<tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</td><td c...	A table row.

Line	What it does
<tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><...	A data cell.
<tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18<//...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.

Declaration	What it does
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
table-layout: fixed;	Columns get equal widths regardless of content; faster rendering.
font-size: 1.3rem;	Size of the text.
font-weight: 700;	Thickness of the text.
background: var(--accent);	Background colour or image.
vertical-align: top;	Aligns cell content to the top.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 4px;	Rounds the corners.
th:last-child, td:last-child {	The last child of its parent.
@media (max-width: 600px) { td { height: 3rem; } td span { font-siz...	Turns a square into a circle.

Check your work

- Seven cells in every row
- Columns equal width
- Events visible on mobile as dots
- Caption gives the month

Exercises

1. Generate the cells with JavaScript for any month.
2. Highlight today with a class.
3. Make cells links to day pages.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 984: Month calendar for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 3 | Files: index.html, styles.css

Brief

Draw a month grid as a table with fixed equal columns, tall cells, event labels that shrink to dots on phones and a highlighted Friday column.

Learning goals

- Use table-layout: fixed for equal columns
- Use :last-child for a column
- Adapt content presentation with a media query

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, span	table-layout: fixed, vertical-align: top, height on td, :last-child, @media (max-width)

Build guide

1. Write the header row with day names starting Saturday.
2. Write the day cells in rows of seven, padding the first row with empty cells.
3. Add a span for event labels.
4. Fix the layout and set tall cells aligned top.
5. Colour the last column.
6. On narrow screens shrink event labels to dots.

Project 984: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - September</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Horizon Photography calendar</h1>
    <table class="cal">
      <caption>September 2026</caption>
      <thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</
th><th>Wed</th><th>Thu</th><th>Fri</th></tr></thead>
      <tbody>
        <tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</
td><td class="event">5<span>session</span></td></tr>
        <tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</
td><td>11</td><td class="event">12<span>session</span></td></tr>
        <tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</
td><td>18</td><td class="event">19<span>session</span></td></tr>
        <tr><td>20</td><td>21</td><td>22</td><td>23</td><td>24</
td><td>25</td><td>26</td></tr>
        <tr><td>27</td><td>28</td><td>29</td><td>30</td><td></
td><td></td><td></td></tr>
      </tbody>
    </table>
  </main>
</body>
</html>
```

Project 984: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.cal { width: 100%; border-collapse: collapse; table-layout: fixed; }
caption { font-size: 1.3rem; font-weight: 700; padding: .5rem; }
th { padding: .5rem; background: var(--accent); }
td { height: 5rem; vertical-align: top; padding: .3rem; border: 1px
solid var(--line); font-size: .9rem; }
td span { display: block; margin-top: .3rem; background: var(--brand);
 color: #fff; font-size: .7rem; padding: .1rem .3rem; border-radius:
```

```
4px; }
th:last-child, td:last-child { color: var(--brand); }
@media (max-width: 600px) { td { height: 3rem; } td span { font-size:
0; height: .5rem; width: .5rem; border-radius: 50%; padding: 0; } }
```

Project 984 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - September</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Horizon Photography calendar	The main heading; only one per page.
<table class="cal">	Tabular data in rows and columns.
<caption>September 2026</caption>	Title of the table.
<thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</th><th>Wed<...	Group of header rows.
<tbody>	Group of data rows.
<tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</td><td c...	A table row.

Line	What it does
<tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><...	A data cell.
<tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18<//...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.

Declaration	What it does
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
table-layout: fixed;	Columns get equal widths regardless of content; faster rendering.
font-size: 1.3rem;	Size of the text.
font-weight: 700;	Thickness of the text.
background: var(--accent);	Background colour or image.
vertical-align: top;	Aligns cell content to the top.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 4px;	Rounds the corners.
th:last-child, td:last-child {	The last child of its parent.
@media (max-width: 600px) { td { height: 3rem; } td span { font-siz...	Turns a square into a circle.

Check your work

- Seven cells in every row
- Columns equal width
- Events visible on mobile as dots
- Caption gives the month

Exercises

1. Generate the cells with JavaScript for any month.
2. Highlight today with a class.
3. Make cells links to day pages.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 985: Month calendar for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 3 | Files: index.html, styles.css

Brief

Draw a month grid as a table with fixed equal columns, tall cells, event labels that shrink to dots on phones and a highlighted Friday column.

Learning goals

- Use table-layout: fixed for equal columns
- Use :last-child for a column
- Adapt content presentation with a media query

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, span	table-layout: fixed, vertical-align: top, height on td, :last-child, @media (max-width)

Build guide

1. Write the header row with day names starting Saturday.
2. Write the day cells in rows of seven, padding the first row with empty cells.
3. Add a span for event labels.
4. Fix the layout and set tall cells aligned top.
5. Colour the last column.
6. On narrow screens shrink event labels to dots.

Project 985: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - September</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Papyrus Stationery calendar</h1>
    <table class="cal">
      <caption>September 2026</caption>
      <thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</
th><th>Wed</th><th>Thu</th><th>Fri</th></tr></thead>
      <tbody>
        <tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</
td><td class="event">5<span>product</span></td></tr>
        <tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</
td><td>11</td><td class="event">12<span>product</span></td></tr>
        <tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</
td><td>18</td><td class="event">19<span>product</span></td></tr>
        <tr><td>20</td><td>21</td><td>22</td><td>23</td><td>24</
td><td>25</td><td>26</td></tr>
        <tr><td>27</td><td>28</td><td>29</td><td>30</td><td></
td><td></td><td></td></tr>
      </tbody>
    </table>
  </main>
</body>
</html>
```

Project 985: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.cal { width: 100%; border-collapse: collapse; table-layout: fixed; }
caption { font-size: 1.3rem; font-weight: 700; padding: .5rem; }
th { padding: .5rem; background: var(--accent); }
td { height: 5rem; vertical-align: top; padding: .3rem; border: 1px
solid var(--line); font-size: .9rem; }
td span { display: block; margin-top: .3rem; background: var(--brand);
 color: #fff; font-size: .7rem; padding: .1rem .3rem; border-radius:
```

```
4px; }
th:last-child, td:last-child { color: var(--brand); }
@media (max-width: 600px) { td { height: 3rem; } td span { font-size:
0; height: .5rem; width: .5rem; border-radius: 50%; padding: 0; } }
```

Project 985 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - September</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Papyrus Stationery calendar	The main heading; only one per page.
<table class="cal">	Tabular data in rows and columns.
<caption>September 2026</caption>	Title of the table.
<thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</th><th>Wed<...	Group of header rows.
<tbody>	Group of data rows.
<tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</td><td c...	A table row.

Line	What it does
<tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><...	A data cell.
<tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18<//...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.

Declaration	What it does
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
table-layout: fixed;	Columns get equal widths regardless of content; faster rendering.
font-size: 1.3rem;	Size of the text.
font-weight: 700;	Thickness of the text.
background: var(--accent);	Background colour or image.
vertical-align: top;	Aligns cell content to the top.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 4px;	Rounds the corners.
th:last-child, td:last-child {	The last child of its parent.
@media (max-width: 600px) { td { height: 3rem; } td span { font-siz...	Turns a square into a circle.

Check your work

- Seven cells in every row
- Columns equal width
- Events visible on mobile as dots
- Caption gives the month

Exercises

1. Generate the cells with JavaScript for any month.
2. Highlight today with a class.
3. Make cells links to day pages.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 986: Month calendar for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 3 | Files: index.html, styles.css

Brief

Draw a month grid as a table with fixed equal columns, tall cells, event labels that shrink to dots on phones and a highlighted Friday column.

Learning goals

- Use table-layout: fixed for equal columns
- Use :last-child for a column
- Adapt content presentation with a media query

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, span	table-layout: fixed, vertical-align: top, height on td, :last-child, @media (max-width)

Build guide

1. Write the header row with day names starting Saturday.
2. Write the day cells in rows of seven, padding the first row with empty cells.
3. Add a span for event labels.
4. Fix the layout and set tall cells aligned top.
5. Colour the last column.
6. On narrow screens shrink event labels to dots.

Project 986: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - September</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Oasis Plant Nursery calendar</h1>
    <table class="cal">
      <caption>September 2026</caption>
      <thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</
th><th>Wed</th><th>Thu</th><th>Fri</th></tr></thead>
      <tbody>
        <tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</
td><td class="event">5<span>plant</span></td></tr>
        <tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</
td><td>11</td><td class="event">12<span>plant</span></td></tr>
        <tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</
td><td>18</td><td class="event">19<span>plant</span></td></tr>
        <tr><td>20</td><td>21</td><td>22</td><td>23</td><td>24</
td><td>25</td><td>26</td></tr>
        <tr><td>27</td><td>28</td><td>29</td><td>30</td><td></
td><td></td><td></td></tr>
      </tbody>
    </table>
  </main>
</body>
</html>
```

Project 986: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.cal { width: 100%; border-collapse: collapse; table-layout: fixed; }
caption { font-size: 1.3rem; font-weight: 700; padding: .5rem; }
th { padding: .5rem; background: var(--accent); }
td { height: 5rem; vertical-align: top; padding: .3rem; border: 1px
solid var(--line); font-size: .9rem; }
td span { display: block; margin-top: .3rem; background: var(--brand);
 color: #fff; font-size: .7rem; padding: .1rem .3rem; border-radius:
```

```
4px; }
th:last-child, td:last-child { color: var(--brand); }
@media (max-width: 600px) { td { height: 3rem; } td span { font-size:
0; height: .5rem; width: .5rem; border-radius: 50%; padding: 0; } }
```

Project 986 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - September</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Oasis Plant Nursery calendar	The main heading; only one per page.
<table class="cal">	Tabular data in rows and columns.
<caption>September 2026</caption>	Title of the table.
<thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</th><th>Wed<...	Group of header rows.
<tbody>	Group of data rows.
<tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</td><td c...	A table row.

Line	What it does
<tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><...	A data cell.
<tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18<//...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.

Declaration	What it does
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
table-layout: fixed;	Columns get equal widths regardless of content; faster rendering.
font-size: 1.3rem;	Size of the text.
font-weight: 700;	Thickness of the text.
background: var(--accent);	Background colour or image.
vertical-align: top;	Aligns cell content to the top.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 4px;	Rounds the corners.
th:last-child, td:last-child {	The last child of its parent.
@media (max-width: 600px) { td { height: 3rem; } td span { font-siz...	Turns a square into a circle.

Check your work

- Seven cells in every row
- Columns equal width
- Events visible on mobile as dots
- Caption gives the month

Exercises

1. Generate the cells with JavaScript for any month.
2. Highlight today with a class.
3. Make cells links to day pages.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 987: Month calendar for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 3 | Files: index.html, styles.css

Brief

Draw a month grid as a table with fixed equal columns, tall cells, event labels that shrink to dots on phones and a highlighted Friday column.

Learning goals

- Use table-layout: fixed for equal columns
- Use :last-child for a column
- Adapt content presentation with a media query

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, span	table-layout: fixed, vertical-align: top, height on td, :last-child, @media (max-width)

Build guide

1. Write the header row with day names starting Saturday.
2. Write the day cells in rows of seven, padding the first row with empty cells.
3. Add a span for event labels.
4. Fix the layout and set tall cells aligned top.
5. Colour the last column.
6. On narrow screens shrink event labels to dots.

Project 987: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - September</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cedar Furniture calendar</h1>
    <table class="cal">
      <caption>September 2026</caption>
      <thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</
th><th>Wed</th><th>Thu</th><th>Fri</th></tr></thead>
      <tbody>
        <tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</
td><td class="event">5<span>piece</span></td></tr>
        <tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</
td><td>11</td><td class="event">12<span>piece</span></td></tr>
        <tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</
td><td>18</td><td class="event">19<span>piece</span></td></tr>
        <tr><td>20</td><td>21</td><td>22</td><td>23</td><td>24</
td><td>25</td><td>26</td></tr>
        <tr><td>27</td><td>28</td><td>29</td><td>30</td><td></
td><td></td><td></td></tr>
      </tbody>
    </table>
  </main>
</body>
</html>
```

Project 987: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.cal { width: 100%; border-collapse: collapse; table-layout: fixed; }
caption { font-size: 1.3rem; font-weight: 700; padding: .5rem; }
th { padding: .5rem; background: var(--accent); }
td { height: 5rem; vertical-align: top; padding: .3rem; border: 1px
solid var(--line); font-size: .9rem; }
td span { display: block; margin-top: .3rem; background: var(--brand);
 color: #fff; font-size: .7rem; padding: .1rem .3rem; border-radius:
```

```
4px; }
th:last-child, td:last-child { color: var(--brand); }
@media (max-width: 600px) { td { height: 3rem; } td span { font-size:
0; height: .5rem; width: .5rem; border-radius: 50%; padding: 0; } }
```

Project 987 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - September</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cedar Furniture calendar	The main heading; only one per page.
<table class="cal">	Tabular data in rows and columns.
<caption>September 2026</caption>	Title of the table.
<thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</th><th>Wed<...	Group of header rows.
<tbody>	Group of data rows.
<tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</td><td c...	A table row.

Line	What it does
<tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><...	A data cell.
<tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18<//...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.

Declaration	What it does
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
table-layout: fixed;	Columns get equal widths regardless of content; faster rendering.
font-size: 1.3rem;	Size of the text.
font-weight: 700;	Thickness of the text.
background: var(--accent);	Background colour or image.
vertical-align: top;	Aligns cell content to the top.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 4px;	Rounds the corners.
th:last-child, td:last-child {	The last child of its parent.
@media (max-width: 600px) { td { height: 3rem; } td span { font-siz...	Turns a square into a circle.

Check your work

- Seven cells in every row
- Columns equal width
- Events visible on mobile as dots
- Caption gives the month

Exercises

1. Generate the cells with JavaScript for any month.
2. Highlight today with a class.
3. Make cells links to day pages.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 988: Month calendar for Byte Repair

Theme: Byte Repair (Nasr City) | Level 3 | Files: index.html, styles.css

Brief

Draw a month grid as a table with fixed equal columns, tall cells, event labels that shrink to dots on phones and a highlighted Friday column.

Learning goals

- Use table-layout: fixed for equal columns
- Use :last-child for a column
- Adapt content presentation with a media query

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, span	table-layout: fixed, vertical-align: top, height on td, :last-child, @media (max-width)

Build guide

1. Write the header row with day names starting Saturday.
2. Write the day cells in rows of seven, padding the first row with empty cells.
3. Add a span for event labels.
4. Fix the layout and set tall cells aligned top.
5. Colour the last column.
6. On narrow screens shrink event labels to dots.

Project 988: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - September</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Byte Repair calendar</h1>
    <table class="cal">
      <caption>September 2026</caption>
      <thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</
th><th>Wed</th><th>Thu</th><th>Fri</th></tr></thead>
      <tbody>
        <tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</
td><td class="event">5<span>repair</span></td></tr>
        <tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</
td><td>11</td><td class="event">12<span>repair</span></td></tr>
        <tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</
td><td>18</td><td class="event">19<span>repair</span></td></tr>
        <tr><td>20</td><td>21</td><td>22</td><td>23</td><td>24</
td><td>25</td><td>26</td></tr>
        <tr><td>27</td><td>28</td><td>29</td><td>30</td><td></
td><td></td><td></td></tr>
      </tbody>
    </table>
  </main>
</body>
</html>
```

Project 988: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.cal { width: 100%; border-collapse: collapse; table-layout: fixed; }
caption { font-size: 1.3rem; font-weight: 700; padding: .5rem; }
th { padding: .5rem; background: var(--accent); }
td { height: 5rem; vertical-align: top; padding: .3rem; border: 1px
solid var(--line); font-size: .9rem; }
td span { display: block; margin-top: .3rem; background: var(--brand);
 color: #fff; font-size: .7rem; padding: .1rem .3rem; border-radius:
```

```
4px; }
th:last-child, td:last-child { color: var(--brand); }
@media (max-width: 600px) { td { height: 3rem; } td span { font-size:
0; height: .5rem; width: .5rem; border-radius: 50%; padding: 0; } }
```

Project 988 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - September</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Byte Repair calendar	The main heading; only one per page.
<table class="cal">	Tabular data in rows and columns.
<caption>September 2026</caption>	Title of the table.
<thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</th><th>Wed<...	Group of header rows.
<tbody>	Group of data rows.
<tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</td><td c...	A table row.

Line	What it does
<tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><...	A data cell.
<tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18<//...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.

Declaration	What it does
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
table-layout: fixed;	Columns get equal widths regardless of content; faster rendering.
font-size: 1.3rem;	Size of the text.
font-weight: 700;	Thickness of the text.
background: var(--accent);	Background colour or image.
vertical-align: top;	Aligns cell content to the top.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 4px;	Rounds the corners.
th:last-child, td:last-child {	The last child of its parent.
@media (max-width: 600px) { td { height: 3rem; } td span { font-siz...	Turns a square into a circle.

Check your work

- Seven cells in every row
- Columns equal width
- Events visible on mobile as dots
- Caption gives the month

Exercises

1. Generate the cells with JavaScript for any month.
2. Highlight today with a class.
3. Make cells links to day pages.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 989: Month calendar for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 3 | Files: index.html, styles.css

Brief

Draw a month grid as a table with fixed equal columns, tall cells, event labels that shrink to dots on phones and a highlighted Friday column.

Learning goals

- Use table-layout: fixed for equal columns
- Use :last-child for a column
- Adapt content presentation with a media query

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, span	table-layout: fixed, vertical-align: top, height on td, :last-child, @media (max-width)

Build guide

1. Write the header row with day names starting Saturday.
2. Write the day cells in rows of seven, padding the first row with empty cells.
3. Add a span for event labels.
4. Fix the layout and set tall cells aligned top.
5. Colour the last column.
6. On narrow screens shrink event labels to dots.

Project 989: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - September</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Sahara Pet Care calendar</h1>
    <table class="cal">
      <caption>September 2026</caption>
      <thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</
th><th>Wed</th><th>Thu</th><th>Fri</th></tr></thead>
      <tbody>
        <tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</
td><td class="event">5<span>service</span></td></tr>
        <tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</
td><td>11</td><td class="event">12<span>service</span></td></tr>
        <tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</
td><td>18</td><td class="event">19<span>service</span></td></tr>
        <tr><td>20</td><td>21</td><td>22</td><td>23</td><td>24</
td><td>25</td><td>26</td></tr>
        <tr><td>27</td><td>28</td><td>29</td><td>30</td><td></
td><td></td><td></td></tr>
      </tbody>
    </table>
  </main>
</body>
</html>
```

Project 989: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.cal { width: 100%; border-collapse: collapse; table-layout: fixed; }
caption { font-size: 1.3rem; font-weight: 700; padding: .5rem; }
th { padding: .5rem; background: var(--accent); }
td { height: 5rem; vertical-align: top; padding: .3rem; border: 1px
solid var(--line); font-size: .9rem; }
td span { display: block; margin-top: .3rem; background: var(--brand);
 color: #fff; font-size: .7rem; padding: .1rem .3rem; border-radius:
```

```
4px; }
th:last-child, td:last-child { color: var(--brand); }
@media (max-width: 600px) { td { height: 3rem; } td span { font-size:
0; height: .5rem; width: .5rem; border-radius: 50%; padding: 0; } }
```

Project 989 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - September</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Sahara Pet Care calendar	The main heading; only one per page.
<table class="cal">	Tabular data in rows and columns.
<caption>September 2026</caption>	Title of the table.
<thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</th><th>Wed<...	Group of header rows.
<tbody>	Group of data rows.
<tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</td><td c...	A table row.

Line	What it does
<tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><...	A data cell.
<tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18<//...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.

Declaration	What it does
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
table-layout: fixed;	Columns get equal widths regardless of content; faster rendering.
font-size: 1.3rem;	Size of the text.
font-weight: 700;	Thickness of the text.
background: var(--accent);	Background colour or image.
vertical-align: top;	Aligns cell content to the top.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 4px;	Rounds the corners.
th:last-child, td:last-child {	The last child of its parent.
@media (max-width: 600px) { td { height: 3rem; } td span { font-siz...	Turns a square into a circle.

Check your work

- Seven cells in every row
- Columns equal width
- Events visible on mobile as dots
- Caption gives the month

Exercises

1. Generate the cells with JavaScript for any month.
2. Highlight today with a class.
3. Make cells links to day pages.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 990: Month calendar for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 3 | Files: index.html, styles.css

Brief

Draw a month grid as a table with fixed equal columns, tall cells, event labels that shrink to dots on phones and a highlighted Friday column.

Learning goals

- Use table-layout: fixed for equal columns
- Use :last-child for a column
- Adapt content presentation with a media query

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, span	table-layout: fixed, vertical-align: top, height on td, :last-child, @media (max-width)

Build guide

1. Write the header row with day names starting Saturday.
2. Write the day cells in rows of seven, padding the first row with empty cells.
3. Add a span for event labels.
4. Fix the layout and set tall cells aligned top.
5. Colour the last column.
6. On narrow screens shrink event labels to dots.

Project 990: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - September</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Alexandria Sailing School calendar</h1>
    <table class="cal">
      <caption>September 2026</caption>
      <thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</
th><th>Wed</th><th>Thu</th><th>Fri</th></tr></thead>
      <tbody>
        <tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</
td><td class="event">5<span>lesson</span></td></tr>
        <tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</
td><td>11</td><td class="event">12<span>lesson</span></td></tr>
        <tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</
td><td>18</td><td class="event">19<span>lesson</span></td></tr>
        <tr><td>20</td><td>21</td><td>22</td><td>23</td><td>24</
td><td>25</td><td>26</td></tr>
        <tr><td>27</td><td>28</td><td>29</td><td>30</td><td></
td><td></td><td></td></tr>
      </tbody>
    </table>
  </main>
</body>
</html>
```

Project 990: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.cal { width: 100%; border-collapse: collapse; table-layout: fixed; }
caption { font-size: 1.3rem; font-weight: 700; padding: .5rem; }
th { padding: .5rem; background: var(--accent); }
td { height: 5rem; vertical-align: top; padding: .3rem; border: 1px
solid var(--line); font-size: .9rem; }
td span { display: block; margin-top: .3rem; background: var(--brand);
 color: #fff; font-size: .7rem; padding: .1rem .3rem; border-radius:
```

```
4px; }
th:last-child, td:last-child { color: var(--brand); }
@media (max-width: 600px) { td { height: 3rem; } td span { font-size:
0; height: .5rem; width: .5rem; border-radius: 50%; padding: 0; } }
```

Project 990 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - September</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Alexandria Sailing School calendar	The main heading; only one per page.
<table class="cal">	Tabular data in rows and columns.
<caption>September 2026</caption>	Title of the table.
<thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</th><th>Wed<...	Group of header rows.
<tbody>	Group of data rows.
<tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</td><td c...	A table row.

Line	What it does
<tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><...	A data cell.
<tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18<//...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.

Declaration	What it does
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
table-layout: fixed;	Columns get equal widths regardless of content; faster rendering.
font-size: 1.3rem;	Size of the text.
font-weight: 700;	Thickness of the text.
background: var(--accent);	Background colour or image.
vertical-align: top;	Aligns cell content to the top.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 4px;	Rounds the corners.
th:last-child, td:last-child {	The last child of its parent.
@media (max-width: 600px) { td { height: 3rem; } td span { font-siz...	Turns a square into a circle.

Check your work

- Seven cells in every row
- Columns equal width
- Events visible on mobile as dots
- Caption gives the month

Exercises

1. Generate the cells with JavaScript for any month.
2. Highlight today with a class.
3. Make cells links to day pages.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 991: Month calendar for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 3 | Files: index.html, styles.css

Brief

Draw a month grid as a table with fixed equal columns, tall cells, event labels that shrink to dots on phones and a highlighted Friday column.

Learning goals

- Use table-layout: fixed for equal columns
- Use :last-child for a column
- Adapt content presentation with a media query

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, span	table-layout: fixed, vertical-align: top, height on td, :last-child, @media (max-width)

Build guide

1. Write the header row with day names starting Saturday.
2. Write the day cells in rows of seven, padding the first row with empty cells.
3. Add a span for event labels.
4. Fix the layout and set tall cells aligned top.
5. Colour the last column.

6. On narrow screens shrink event labels to dots.

Project 991: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - September</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Habiba Handmade Jewellery calendar</h1>
    <table class="cal">
      <caption>September 2026</caption>
      <thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</
th><th>Wed</th><th>Thu</th><th>Fri</th></tr></thead>
      <tbody>
        <tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</
td><td class="event">5<span>item</span></td></tr>
        <tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</
td><td>11</td><td class="event">12<span>item</span></td></tr>
        <tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</
td><td>18</td><td class="event">19<span>item</span></td></tr>
        <tr><td>20</td><td>21</td><td>22</td><td>23</td><td>24</
td><td>25</td><td>26</td></tr>
        <tr><td>27</td><td>28</td><td>29</td><td>30</td><td></
td><td></td><td></td></tr>
      </tbody>
    </table>
  </main>
</body>
</html>
```

Project 991: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.cal { width: 100%; border-collapse: collapse; table-layout: fixed; }
caption { font-size: 1.3rem; font-weight: 700; padding: .5rem; }
th { padding: .5rem; background: var(--accent); }
td { height: 5rem; vertical-align: top; padding: .3rem; border: 1px
solid var(--line); font-size: .9rem; }
td span { display: block; margin-top: .3rem; background: var(--brand);
 color: #fff; font-size: .7rem; padding: .1rem .3rem; border-radius:
```

```
4px; }
th:last-child, td:last-child { color: var(--brand); }
@media (max-width: 600px) { td { height: 3rem; } td span { font-size:
0; height: .5rem; width: .5rem; border-radius: 50%; padding: 0; } }
```

Project 991 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - September</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Habiba Handmade Jewellery calendar	The main heading; only one per page.
<table class="cal">	Tabular data in rows and columns.
<caption>September 2026</caption>	Title of the table.
<thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</th><th>Wed<...	Group of header rows.
<tbody>	Group of data rows.
<tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</td><td c...	A table row.

Line	What it does
<tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><...	A data cell.
<tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18<//...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.

Declaration	What it does
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
table-layout: fixed;	Columns get equal widths regardless of content; faster rendering.
font-size: 1.3rem;	Size of the text.
font-weight: 700;	Thickness of the text.
background: var(--accent);	Background colour or image.
vertical-align: top;	Aligns cell content to the top.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 4px;	Rounds the corners.
th:last-child, td:last-child {	The last child of its parent.
@media (max-width: 600px) { td { height: 3rem; } td span { font-siz...	Turns a square into a circle.

Check your work

- Seven cells in every row
- Columns equal width
- Events visible on mobile as dots
- Caption gives the month

Exercises

1. Generate the cells with JavaScript for any month.
2. Highlight today with a class.
3. Make cells links to day pages.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 992: Month calendar for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 3 | Files: index.html, styles.css

Brief

Draw a month grid as a table with fixed equal columns, tall cells, event labels that shrink to dots on phones and a highlighted Friday column.

Learning goals

- Use table-layout: fixed for equal columns
- Use :last-child for a column
- Adapt content presentation with a media query

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, span	table-layout: fixed, vertical-align: top, height on td, :last-child, @media (max-width)

Build guide

1. Write the header row with day names starting Saturday.
2. Write the day cells in rows of seven, padding the first row with empty cells.
3. Add a span for event labels.
4. Fix the layout and set tall cells aligned top.
5. Colour the last column.
6. On narrow screens shrink event labels to dots.

Project 992: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - September</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Fayoum Pottery Studio calendar</h1>
    <table class="cal">
      <caption>September 2026</caption>
      <thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</
th><th>Wed</th><th>Thu</th><th>Fri</th></tr></thead>
      <tbody>
        <tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</
td><td class="event">5<span>workshop</span></td></tr>
        <tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</
td><td>11</td><td class="event">12<span>workshop</span></td></tr>
        <tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</
td><td>18</td><td class="event">19<span>workshop</span></td></tr>
        <tr><td>20</td><td>21</td><td>22</td><td>23</td><td>24</
td><td>25</td><td>26</td></tr>
        <tr><td>27</td><td>28</td><td>29</td><td>30</td><td></
td><td></td><td></td></tr>
      </tbody>
    </table>
  </main>
</body>
</html>
```

Project 992: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.cal { width: 100%; border-collapse: collapse; table-layout: fixed; }
caption { font-size: 1.3rem; font-weight: 700; padding: .5rem; }
th { padding: .5rem; background: var(--accent); }
td { height: 5rem; vertical-align: top; padding: .3rem; border: 1px
solid var(--line); font-size: .9rem; }
td span { display: block; margin-top: .3rem; background: var(--brand);
 color: #fff; font-size: .7rem; padding: .1rem .3rem; border-radius:
```

```
4px; }
th:last-child, td:last-child { color: var(--brand); }
@media (max-width: 600px) { td { height: 3rem; } td span { font-size:
0; height: .5rem; width: .5rem; border-radius: 50%; padding: 0; } }
```

Project 992 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - September</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Fayoum Pottery Studio calendar	The main heading; only one per page.
<table class="cal">	Tabular data in rows and columns.
<caption>September 2026</caption>	Title of the table.
<thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</th><th>Wed<...	Group of header rows.
<tbody>	Group of data rows.
<tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</td><td c...	A table row.

Line	What it does
<tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><...	A data cell.
<tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18<//...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.

Declaration	What it does
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
table-layout: fixed;	Columns get equal widths regardless of content; faster rendering.
font-size: 1.3rem;	Size of the text.
font-weight: 700;	Thickness of the text.
background: var(--accent);	Background colour or image.
vertical-align: top;	Aligns cell content to the top.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 4px;	Rounds the corners.
th:last-child, td:last-child {	The last child of its parent.
@media (max-width: 600px) { td { height: 3rem; } td span { font-siz...	Turns a square into a circle.

Check your work

- Seven cells in every row
- Columns equal width
- Events visible on mobile as dots
- Caption gives the month

Exercises

1. Generate the cells with JavaScript for any month.
2. Highlight today with a class.
3. Make cells links to day pages.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 993: Month calendar for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 3 | Files: index.html, styles.css

Brief

Draw a month grid as a table with fixed equal columns, tall cells, event labels that shrink to dots on phones and a highlighted Friday column.

Learning goals

- Use table-layout: fixed for equal columns
- Use :last-child for a column
- Adapt content presentation with a media query

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, span	table-layout: fixed, vertical-align: top, height on td, :last-child, @media (max-width)

Build guide

1. Write the header row with day names starting Saturday.
2. Write the day cells in rows of seven, padding the first row with empty cells.
3. Add a span for event labels.
4. Fix the layout and set tall cells aligned top.
5. Colour the last column.
6. On narrow screens shrink event labels to dots.

Project 993: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - September</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cleopatra Beauty Salon calendar</h1>
    <table class="cal">
      <caption>September 2026</caption>
      <thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</
th><th>Wed</th><th>Thu</th><th>Fri</th></tr></thead>
      <tbody>
        <tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</
td><td class="event">5<span>treatment</span></td></tr>
        <tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</
td><td>11</td><td class="event">12<span>treatment</span></td></tr>
        <tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</
td><td>18</td><td class="event">19<span>treatment</span></td></tr>
        <tr><td>20</td><td>21</td><td>22</td><td>23</td><td>24</
td><td>25</td><td>26</td></tr>
        <tr><td>27</td><td>28</td><td>29</td><td>30</td><td></
td><td></td><td></td></tr>
      </tbody>
    </table>
  </main>
</body>
</html>
```

Project 993: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.cal { width: 100%; border-collapse: collapse; table-layout: fixed; }
caption { font-size: 1.3rem; font-weight: 700; padding: .5rem; }
th { padding: .5rem; background: var(--accent); }
td { height: 5rem; vertical-align: top; padding: .3rem; border: 1px
solid var(--line); font-size: .9rem; }
td span { display: block; margin-top: .3rem; background: var(--brand);
 color: #fff; font-size: .7rem; padding: .1rem .3rem; border-radius:
```

```
4px; }
th:last-child, td:last-child { color: var(--brand); }
@media (max-width: 600px) { td { height: 3rem; } td span { font-size:
0; height: .5rem; width: .5rem; border-radius: 50%; padding: 0; } }
```

Project 993 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - September</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cleopatra Beauty Salon calendar	The main heading; only one per page.
<table class="cal">	Tabular data in rows and columns.
<caption>September 2026</caption>	Title of the table.
<thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</th><th>Wed<...	Group of header rows.
<tbody>	Group of data rows.
<tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</td><td c...	A table row.

Line	What it does
<tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><...	A data cell.
<tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18<//...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.

Declaration	What it does
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
table-layout: fixed;	Columns get equal widths regardless of content; faster rendering.
font-size: 1.3rem;	Size of the text.
font-weight: 700;	Thickness of the text.
background: var(--accent);	Background colour or image.
vertical-align: top;	Aligns cell content to the top.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 4px;	Rounds the corners.
th:last-child, td:last-child {	The last child of its parent.
@media (max-width: 600px) { td { height: 3rem; } td span { font-siz...	Turns a square into a circle.

Check your work

- Seven cells in every row
- Columns equal width
- Events visible on mobile as dots
- Caption gives the month

Exercises

1. Generate the cells with JavaScript for any month.
2. Highlight today with a class.
3. Make cells links to day pages.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 994: Month calendar for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 3 | Files: index.html, styles.css

Brief

Draw a month grid as a table with fixed equal columns, tall cells, event labels that shrink to dots on phones and a highlighted Friday column.

Learning goals

- Use table-layout: fixed for equal columns
- Use :last-child for a column
- Adapt content presentation with a media query

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, span	table-layout: fixed, vertical-align: top, height on td, :last-child, @media (max-width)

Build guide

1. Write the header row with day names starting Saturday.
2. Write the day cells in rows of seven, padding the first row with empty cells.
3. Add a span for event labels.
4. Fix the layout and set tall cells aligned top.
5. Colour the last column.
6. On narrow screens shrink event labels to dots.

Project 994: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - September</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Suez Auto Service calendar</h1>
    <table class="cal">
      <caption>September 2026</caption>
      <thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</
th><th>Wed</th><th>Thu</th><th>Fri</th></tr></thead>
      <tbody>
        <tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</
td><td class="event">5<span>service</span></td></tr>
        <tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</
td><td>11</td><td class="event">12<span>service</span></td></tr>
        <tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</
td><td>18</td><td class="event">19<span>service</span></td></tr>
        <tr><td>20</td><td>21</td><td>22</td><td>23</td><td>24</
td><td>25</td><td>26</td></tr>
        <tr><td>27</td><td>28</td><td>29</td><td>30</td><td></
td><td></td><td></td></tr>
      </tbody>
    </table>
  </main>
</body>
</html>
```

Project 994: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.cal { width: 100%; border-collapse: collapse; table-layout: fixed; }
caption { font-size: 1.3rem; font-weight: 700; padding: .5rem; }
th { padding: .5rem; background: var(--accent); }
td { height: 5rem; vertical-align: top; padding: .3rem; border: 1px
solid var(--line); font-size: .9rem; }
td span { display: block; margin-top: .3rem; background: var(--brand);
 color: #fff; font-size: .7rem; padding: .1rem .3rem; border-radius:
```

```
4px; }
th:last-child, td:last-child { color: var(--brand); }
@media (max-width: 600px) { td { height: 3rem; } td span { font-size:
0; height: .5rem; width: .5rem; border-radius: 50%; padding: 0; } }
```

Project 994 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - September</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Suez Auto Service calendar	The main heading; only one per page.
<table class="cal">	Tabular data in rows and columns.
<caption>September 2026</caption>	Title of the table.
<thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</th><th>Wed<...	Group of header rows.
<tbody>	Group of data rows.
<tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</td><td c...	A table row.

Line	What it does
<tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><...	A data cell.
<tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18<//...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.

Declaration	What it does
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
table-layout: fixed;	Columns get equal widths regardless of content; faster rendering.
font-size: 1.3rem;	Size of the text.
font-weight: 700;	Thickness of the text.
background: var(--accent);	Background colour or image.
vertical-align: top;	Aligns cell content to the top.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 4px;	Rounds the corners.
th:last-child, td:last-child {	The last child of its parent.
@media (max-width: 600px) { td { height: 3rem; } td span { font-siz...	Turns a square into a circle.

Check your work

- Seven cells in every row
- Columns equal width
- Events visible on mobile as dots
- Caption gives the month

Exercises

1. Generate the cells with JavaScript for any month.
2. Highlight today with a class.
3. Make cells links to day pages.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 995: Month calendar for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 3 | Files: index.html, styles.css

Brief

Draw a month grid as a table with fixed equal columns, tall cells, event labels that shrink to dots on phones and a highlighted Friday column.

Learning goals

- Use table-layout: fixed for equal columns
- Use :last-child for a column
- Adapt content presentation with a media query

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, span	table-layout: fixed, vertical-align: top, height on td, :last-child, @media (max-width)

Build guide

1. Write the header row with day names starting Saturday.
2. Write the day cells in rows of seven, padding the first row with empty cells.
3. Add a span for event labels.
4. Fix the layout and set tall cells aligned top.
5. Colour the last column.
6. On narrow screens shrink event labels to dots.

Project 995: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - September</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Luxor Music Academy calendar</h1>
    <table class="cal">
      <caption>September 2026</caption>
      <thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</
th><th>Wed</th><th>Thu</th><th>Fri</th></tr></thead>
      <tbody>
        <tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</
td><td class="event">5<span>course</span></td></tr>
        <tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</
td><td>11</td><td class="event">12<span>course</span></td></tr>
        <tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</
td><td>18</td><td class="event">19<span>course</span></td></tr>
        <tr><td>20</td><td>21</td><td>22</td><td>23</td><td>24</
td><td>25</td><td>26</td></tr>
        <tr><td>27</td><td>28</td><td>29</td><td>30</td><td></
td><td></td><td></td></tr>
      </tbody>
    </table>
  </main>
</body>
</html>
```

Project 995: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.cal { width: 100%; border-collapse: collapse; table-layout: fixed; }
caption { font-size: 1.3rem; font-weight: 700; padding: .5rem; }
th { padding: .5rem; background: var(--accent); }
td { height: 5rem; vertical-align: top; padding: .3rem; border: 1px
solid var(--line); font-size: .9rem; }
td span { display: block; margin-top: .3rem; background: var(--brand);
 color: #fff; font-size: .7rem; padding: .1rem .3rem; border-radius:
```

```
4px; }
th:last-child, td:last-child { color: var(--brand); }
@media (max-width: 600px) { td { height: 3rem; } td span { font-size:
0; height: .5rem; width: .5rem; border-radius: 50%; padding: 0; } }
```

Project 995 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - September</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Luxor Music Academy calendar	The main heading; only one per page.
<table class="cal">	Tabular data in rows and columns.
<caption>September 2026</caption>	Title of the table.
<thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</th><th>Wed<...	Group of header rows.
<tbody>	Group of data rows.
<tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</td><td c...	A table row.

Line	What it does
<tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><...	A data cell.
<tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18<//...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.

Declaration	What it does
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
table-layout: fixed;	Columns get equal widths regardless of content; faster rendering.
font-size: 1.3rem;	Size of the text.
font-weight: 700;	Thickness of the text.
background: var(--accent);	Background colour or image.
vertical-align: top;	Aligns cell content to the top.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 4px;	Rounds the corners.
th:last-child, td:last-child {	The last child of its parent.
@media (max-width: 600px) { td { height: 3rem; } td span { font-siz...	Turns a square into a circle.

Check your work

- Seven cells in every row
- Columns equal width
- Events visible on mobile as dots
- Caption gives the month

Exercises

1. Generate the cells with JavaScript for any month.
2. Highlight today with a class.
3. Make cells links to day pages.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 996: Month calendar for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 3 | Files: index.html, styles.css

Brief

Draw a month grid as a table with fixed equal columns, tall cells, event labels that shrink to dots on phones and a highlighted Friday column.

Learning goals

- Use table-layout: fixed for equal columns
- Use :last-child for a column
- Adapt content presentation with a media query

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, span	table-layout: fixed, vertical-align: top, height on td, :last-child, @media (max-width)

Build guide

1. Write the header row with day names starting Saturday.
2. Write the day cells in rows of seven, padding the first row with empty cells.
3. Add a span for event labels.
4. Fix the layout and set tall cells aligned top.
5. Colour the last column.
6. On narrow screens shrink event labels to dots.

Project 996: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - September</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Port Said Seafood calendar</h1>
    <table class="cal">
      <caption>September 2026</caption>
      <thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</
th><th>Wed</th><th>Thu</th><th>Fri</th></tr></thead>
      <tbody>
        <tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</
td><td class="event">5<span>dish</span></td></tr>
        <tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</
td><td>11</td><td class="event">12<span>dish</span></td></tr>
        <tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</
td><td>18</td><td class="event">19<span>dish</span></td></tr>
        <tr><td>20</td><td>21</td><td>22</td><td>23</td><td>24</
td><td>25</td><td>26</td></tr>
        <tr><td>27</td><td>28</td><td>29</td><td>30</td><td></
td><td></td><td></td></tr>
      </tbody>
    </table>
  </main>
</body>
</html>
```

Project 996: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.cal { width: 100%; border-collapse: collapse; table-layout: fixed; }
caption { font-size: 1.3rem; font-weight: 700; padding: .5rem; }
th { padding: .5rem; background: var(--accent); }
td { height: 5rem; vertical-align: top; padding: .3rem; border: 1px
solid var(--line); font-size: .9rem; }
td span { display: block; margin-top: .3rem; background: var(--brand);
 color: #fff; font-size: .7rem; padding: .1rem .3rem; border-radius:
```

```
4px; }
th:last-child, td:last-child { color: var(--brand); }
@media (max-width: 600px) { td { height: 3rem; } td span { font-size:
0; height: .5rem; width: .5rem; border-radius: 50%; padding: 0; } }
```

Project 996 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - September</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Port Said Seafood calendar	The main heading; only one per page.
<table class="cal">	Tabular data in rows and columns.
<caption>September 2026</caption>	Title of the table.
<thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</th><th>Wed<...	Group of header rows.
<tbody>	Group of data rows.
<tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</td><td c...	A table row.

Line	What it does
<tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><...	A data cell.
<tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18<//...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.

Declaration	What it does
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
table-layout: fixed;	Columns get equal widths regardless of content; faster rendering.
font-size: 1.3rem;	Size of the text.
font-weight: 700;	Thickness of the text.
background: var(--accent);	Background colour or image.
vertical-align: top;	Aligns cell content to the top.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 4px;	Rounds the corners.
th:last-child, td:last-child {	The last child of its parent.
@media (max-width: 600px) { td { height: 3rem; } td span { font-siz...	Turns a square into a circle.

Check your work

- Seven cells in every row
- Columns equal width
- Events visible on mobile as dots
- Caption gives the month

Exercises

1. Generate the cells with JavaScript for any month.
2. Highlight today with a class.
3. Make cells links to day pages.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 997: Month calendar for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 3 | Files: index.html, styles.css

Brief

Draw a month grid as a table with fixed equal columns, tall cells, event labels that shrink to dots on phones and a highlighted Friday column.

Learning goals

- Use table-layout: fixed for equal columns
- Use :last-child for a column
- Adapt content presentation with a media query

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, span	table-layout: fixed, vertical-align: top, height on td, :last-child, @media (max-width)

Build guide

1. Write the header row with day names starting Saturday.
2. Write the day cells in rows of seven, padding the first row with empty cells.
3. Add a span for event labels.
4. Fix the layout and set tall cells aligned top.
5. Colour the last column.
6. On narrow screens shrink event labels to dots.

Project 997: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - September</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Delta Kids Library calendar</h1>
    <table class="cal">
      <caption>September 2026</caption>
      <thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</
th><th>Wed</th><th>Thu</th><th>Fri</th></tr></thead>
      <tbody>
        <tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</
td><td class="event">5<span>programme</span></td></tr>
        <tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</
td><td>11</td><td class="event">12<span>programme</span></td></tr>
        <tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</
td><td>18</td><td class="event">19<span>programme</span></td></tr>
        <tr><td>20</td><td>21</td><td>22</td><td>23</td><td>24</
td><td>25</td><td>26</td></tr>
        <tr><td>27</td><td>28</td><td>29</td><td>30</td><td></
td><td></td><td></td></tr>
      </tbody>
    </table>
  </main>
</body>
</html>
```

Project 997: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.cal { width: 100%; border-collapse: collapse; table-layout: fixed; }
caption { font-size: 1.3rem; font-weight: 700; padding: .5rem; }
th { padding: .5rem; background: var(--accent); }
td { height: 5rem; vertical-align: top; padding: .3rem; border: 1px
solid var(--line); font-size: .9rem; }
td span { display: block; margin-top: .3rem; background: var(--brand);
 color: #fff; font-size: .7rem; padding: .1rem .3rem; border-radius:
```

```
4px; }
th:last-child, td:last-child { color: var(--brand); }
@media (max-width: 600px) { td { height: 3rem; } td span { font-size:
0; height: .5rem; width: .5rem; border-radius: 50%; padding: 0; } }
```

Project 997 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - September</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Delta Kids Library calendar	The main heading; only one per page.
<table class="cal">	Tabular data in rows and columns.
<caption>September 2026</caption>	Title of the table.
<thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</th><th>Wed<...	Group of header rows.
<tbody>	Group of data rows.
<tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</td><td c...	A table row.

Line	What it does
<tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><...	A data cell.
<tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18<//...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.

Declaration	What it does
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
table-layout: fixed;	Columns get equal widths regardless of content; faster rendering.
font-size: 1.3rem;	Size of the text.
font-weight: 700;	Thickness of the text.
background: var(--accent);	Background colour or image.
vertical-align: top;	Aligns cell content to the top.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 4px;	Rounds the corners.
th:last-child, td:last-child {	The last child of its parent.
@media (max-width: 600px) { td { height: 3rem; } td span { font-siz...	Turns a square into a circle.

Check your work

- Seven cells in every row
- Columns equal width
- Events visible on mobile as dots
- Caption gives the month

Exercises

1. Generate the cells with JavaScript for any month.
2. Highlight today with a class.
3. Make cells links to day pages.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 998: Month calendar for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 3 | Files: index.html, styles.css

Brief

Draw a month grid as a table with fixed equal columns, tall cells, event labels that shrink to dots on phones and a highlighted Friday column.

Learning goals

- Use table-layout: fixed for equal columns
- Use :last-child for a column
- Adapt content presentation with a media query

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, span	table-layout: fixed, vertical-align: top, height on td, :last-child, @media (max-width)

Build guide

1. Write the header row with day names starting Saturday.
2. Write the day cells in rows of seven, padding the first row with empty cells.
3. Add a span for event labels.
4. Fix the layout and set tall cells aligned top.
5. Colour the last column.
6. On narrow screens shrink event labels to dots.

Project 998: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - September</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Nubian Guest House calendar</h1>
    <table class="cal">
      <caption>September 2026</caption>
      <thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</
th><th>Wed</th><th>Thu</th><th>Fri</th></tr></thead>
      <tbody>
        <tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</
td><td class="event">5<span>room</span></td></tr>
        <tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</
td><td>11</td><td class="event">12<span>room</span></td></tr>
        <tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</
td><td>18</td><td class="event">19<span>room</span></td></tr>
        <tr><td>20</td><td>21</td><td>22</td><td>23</td><td>24</
td><td>25</td><td>26</td></tr>
        <tr><td>27</td><td>28</td><td>29</td><td>30</td><td></
td><td></td><td></td></tr>
      </tbody>
    </table>
  </main>
</body>
</html>
```

Project 998: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.cal { width: 100%; border-collapse: collapse; table-layout: fixed; }
caption { font-size: 1.3rem; font-weight: 700; padding: .5rem; }
th { padding: .5rem; background: var(--accent); }
td { height: 5rem; vertical-align: top; padding: .3rem; border: 1px
solid var(--line); font-size: .9rem; }
td span { display: block; margin-top: .3rem; background: var(--brand);
 color: #fff; font-size: .7rem; padding: .1rem .3rem; border-radius:
```

```
4px; }
th:last-child, td:last-child { color: var(--brand); }
@media (max-width: 600px) { td { height: 3rem; } td span { font-size:
0; height: .5rem; width: .5rem; border-radius: 50%; padding: 0; } }
```

Project 998 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - September</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Nubian Guest House calendar	The main heading; only one per page.
<table class="cal">	Tabular data in rows and columns.
<caption>September 2026</caption>	Title of the table.
<thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</th><th>Wed<...	Group of header rows.
<tbody>	Group of data rows.
<tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</td><td c...	A table row.

Line	What it does
<tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><...	A data cell.
<tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18<//...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.

Declaration	What it does
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
table-layout: fixed;	Columns get equal widths regardless of content; faster rendering.
font-size: 1.3rem;	Size of the text.
font-weight: 700;	Thickness of the text.
background: var(--accent);	Background colour or image.
vertical-align: top;	Aligns cell content to the top.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 4px;	Rounds the corners.
th:last-child, td:last-child {	The last child of its parent.
@media (max-width: 600px) { td { height: 3rem; } td span { font-siz...	Turns a square into a circle.

Check your work

- Seven cells in every row
- Columns equal width
- Events visible on mobile as dots
- Caption gives the month

Exercises

1. Generate the cells with JavaScript for any month.
2. Highlight today with a class.
3. Make cells links to day pages.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 999: Month calendar for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 3 | Files: index.html, styles.css

Brief

Draw a month grid as a table with fixed equal columns, tall cells, event labels that shrink to dots on phones and a highlighted Friday column.

Learning goals

- Use table-layout: fixed for equal columns
- Use :last-child for a column
- Adapt content presentation with a media query

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, span	table-layout: fixed, vertical-align: top, height on td, :last-child, @media (max-width)

Build guide

1. Write the header row with day names starting Saturday.
2. Write the day cells in rows of seven, padding the first row with empty cells.
3. Add a span for event labels.
4. Fix the layout and set tall cells aligned top.
5. Colour the last column.
6. On narrow screens shrink event labels to dots.

Project 999: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - September</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Ismailia Cycling Store calendar</h1>
    <table class="cal">
      <caption>September 2026</caption>
      <thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</
th><th>Wed</th><th>Thu</th><th>Fri</th></tr></thead>
      <tbody>
        <tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</
td><td class="event">5<span>bike</span></td></tr>
        <tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</
td><td>11</td><td class="event">12<span>bike</span></td></tr>
        <tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</
td><td>18</td><td class="event">19<span>bike</span></td></tr>
        <tr><td>20</td><td>21</td><td>22</td><td>23</td><td>24</
td><td>25</td><td>26</td></tr>
        <tr><td>27</td><td>28</td><td>29</td><td>30</td><td></
td><td></td><td></td></tr>
      </tbody>
    </table>
  </main>
</body>
</html>
```

Project 999: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.cal { width: 100%; border-collapse: collapse; table-layout: fixed; }
caption { font-size: 1.3rem; font-weight: 700; padding: .5rem; }
th { padding: .5rem; background: var(--accent); }
td { height: 5rem; vertical-align: top; padding: .3rem; border: 1px
solid var(--line); font-size: .9rem; }
td span { display: block; margin-top: .3rem; background: var(--brand);
 color: #fff; font-size: .7rem; padding: .1rem .3rem; border-radius:
```

```
4px; }
th:last-child, td:last-child { color: var(--brand); }
@media (max-width: 600px) { td { height: 3rem; } td span { font-size:
0; height: .5rem; width: .5rem; border-radius: 50%; padding: 0; } }
```

Project 999 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - September</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Ismailia Cycling Store calendar	The main heading; only one per page.
<table class="cal">	Tabular data in rows and columns.
<caption>September 2026</caption>	Title of the table.
<thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</th><th>Wed<...	Group of header rows.
<tbody>	Group of data rows.
<tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</td><td c...	A table row.

Line	What it does
<tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><...	A data cell.
<tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18<//...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.

Declaration	What it does
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
table-layout: fixed;	Columns get equal widths regardless of content; faster rendering.
font-size: 1.3rem;	Size of the text.
font-weight: 700;	Thickness of the text.
background: var(--accent);	Background colour or image.
vertical-align: top;	Aligns cell content to the top.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 4px;	Rounds the corners.
th:last-child, td:last-child {	The last child of its parent.
@media (max-width: 600px) { td { height: 3rem; } td span { font-siz...	Turns a square into a circle.

Check your work

- Seven cells in every row
- Columns equal width
- Events visible on mobile as dots
- Caption gives the month

Exercises

1. Generate the cells with JavaScript for any month.
2. Highlight today with a class.
3. Make cells links to day pages.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 1000: Month calendar for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 3 | Files: index.html, styles.css

Brief

Draw a month grid as a table with fixed equal columns, tall cells, event labels that shrink to dots on phones and a highlighted Friday column.

Learning goals

- Use table-layout: fixed for equal columns
- Use :last-child for a column
- Adapt content presentation with a media query

Elements and CSS used

HTML elements	CSS features
table, caption, thead, tbody, tr, th, td, span	table-layout: fixed, vertical-align: top, height on td, :last-child, @media (max-width)

Build guide

1. Write the header row with day names starting Saturday.
2. Write the day cells in rows of seven, padding the first row with empty cells.
3. Add a span for event labels.
4. Fix the layout and set tall cells aligned top.
5. Colour the last column.
6. On narrow screens shrink event labels to dots.

Project 1000: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - September</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Minya Coding Club calendar</h1>
    <table class="cal">
      <caption>September 2026</caption>
      <thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</
th><th>Wed</th><th>Thu</th><th>Fri</th></tr></thead>
      <tbody>
        <tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</
td><td class="event">5<span>workshop</span></td></tr>
        <tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</
td><td>11</td><td class="event">12<span>workshop</span></td></tr>
        <tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</
td><td>18</td><td class="event">19<span>workshop</span></td></tr>
        <tr><td>20</td><td>21</td><td>22</td><td>23</td><td>24</
td><td>25</td><td>26</td></tr>
        <tr><td>27</td><td>28</td><td>29</td><td>30</td><td></
td><td></td><td></td></tr>
      </tbody>
    </table>
  </main>
</body>
</html>
```

Project 1000: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 56rem; margin: 2rem auto; padding: 0 1rem; }
.cal { width: 100%; border-collapse: collapse; table-layout: fixed; }
caption { font-size: 1.3rem; font-weight: 700; padding: .5rem; }
th { padding: .5rem; background: var(--accent); }
td { height: 5rem; vertical-align: top; padding: .3rem; border: 1px
solid var(--line); font-size: .9rem; }
td span { display: block; margin-top: .3rem; background: var(--brand);
 color: #fff; font-size: .7rem; padding: .1rem .3rem; border-radius:
```

```
4px; }
th:last-child, td:last-child { color: var(--brand); }
@media (max-width: 600px) { td { height: 3rem; } td span { font-size:
0; height: .5rem; width: .5rem; border-radius: 50%; padding: 0; } }
```

Project 1000 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - September</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Minya Coding Club calendar	The main heading; only one per page.
<table class="cal">	Tabular data in rows and columns.
<caption>September 2026</caption>	Title of the table.
<thead><tr><th>Sat</th><th>Sun</th><th>Mon</th><th>Tue</th><th>Wed<...	Group of header rows.
<tbody>	Group of data rows.
<tr><td></td><td></td><td>1</td><td>2</td><td>3</td><td>4</td><td c...	A table row.

Line	What it does
<tr><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><...	A data cell.
<tr><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18<//...	Generic inline container for styling.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 56rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
width: 100%;	Fills the container width.

Declaration	What it does
border-collapse: collapse;	Merges adjacent table cell borders into single lines.
table-layout: fixed;	Columns get equal widths regardless of content; faster rendering.
font-size: 1.3rem;	Size of the text.
font-weight: 700;	Thickness of the text.
background: var(--accent);	Background colour or image.
vertical-align: top;	Aligns cell content to the top.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
display: block;	Element starts on a new line and fills the width (used on links and images).
border-radius: 4px;	Rounds the corners.
th:last-child, td:last-child {	The last child of its parent.
@media (max-width: 600px) { td { height: 3rem; } td span { font-siz...	Turns a square into a circle.

Check your work

- Seven cells in every row
- Columns equal width
- Events visible on mobile as dots
- Caption gives the month

Exercises

1. Generate the cells with JavaScript for any month.
2. Highlight today with a class.
3. Make cells links to day pages.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Responsive hamburger menu

Level 3 | 25 projects, one per theme

Build a navigation that is a horizontal bar on desktop and collapses behind a hamburger button on phones, toggled by a hidden checkbox and no JavaScript.

Project 1001: Responsive hamburger menu for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 3 | Files: index.html, styles.css

Brief

Build a navigation that is a horizontal bar on desktop and collapses behind a hamburger button on phones, toggled by a hidden checkbox and no JavaScript.

Learning goals

- Use the checkbox hack with :checked ~
- Switch layouts with a min-width media query
- Use flex-basis: 100% to wrap an item to its own line

Elements and CSS used

HTML elements	CSS features
header, input type=checkbox, label, nav, ul, li, a	:checked ~, flex-basis: 100%, display: none/block, @media (min-width), flex-wrap

Build guide

1. Write the header: logo, hidden checkbox, label as the burger, nav.
2. Mobile first: hide .menu; show when the checkbox is checked.
3. Make .menu take the full row with flex-basis: 100%.
4. At 700px hide the burger and always show the menu inline.
5. Style links for both modes.

6. Test with keyboard: Space on the focused label toggles the checkbox.

Project 1001: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Mobile menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="top">
    <a class="logo" href="index.html">Cairo Book Shop</a>
    <input type="checkbox" id="menu-toggle" class="toggle" hidden>
    <label for="menu-toggle" class="burger" aria-label="Open
menu">&#9776;</label>
    <nav class="menu" aria-label="Main">
      <ul>
        <li><a href="index.html">Home</a></li>
    <li><a href="#">Learn HTML</a></li>
    <li><a href="#">CSS in Practice</a></li>
    <li><a href="#">JavaScript Basics</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main><h1>Resize the window</h1><p>Below 700px the menu hides
behind a button.</p></main>
</body>
</html>
```

Project 1001: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.top { display: flex; align-items: center; justify-content: space-
between; flex-wrap: wrap; padding: .75rem 1rem; background: var(--
brand); color: #fff; }
.logo { color: #fff; text-decoration: none; font-weight: 700; }
.burger { font-size: 1.6rem; cursor: pointer; }
.menu { flex-basis: 100%; display: none; }
.toggle:checked ~ .menu { display: block; }
.menu ul { list-style: none; margin: .5rem 0 0; padding: 0; }
.menu a { display: block; padding: .6rem 0; color: #fff; text-
decoration: none; border-top: 1px solid rgb(255 255 255 / 25%); }
@media (min-width: 700px) {
```

```
  .burger { display: none; }
  .menu { display: block; flex-basis: auto; }
  .menu ul { display: flex; gap: .5rem; margin: 0; }
  .menu a { border: 0; padding: .5rem .8rem; border-radius: 6px; }
  .menu a:hover { background: rgb(255 255 255 / 20%); }
}
main { padding: 2rem 1rem; }
```

Project 1001 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - Mobile menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="top">	Introductory content: logo, title, navigation.
<input type="checkbox" id="menu-toggle" class="toggle" hidden>	Checkbox: on or off.
<label for="menu-toggle" class="burger" aria-label="Open menu">&#97...	Text label for a control; for matches the control's id, or the label wraps the control.
<nav class="menu" aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Learn HTML	One list item.

Line	What it does
<main><h1>Resize the window</h1><p>Below 700px the menu hides behin...	The unique content of this page; exactly one per page.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
padding: .75rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-decoration: none;	Removes the underline from links.
font-weight: 700;	Thickness of the text.
font-size: 1.6rem;	Size of the text.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
flex-basis: 100%;	The item takes a whole line, pushing the next items down.
display: none;	Removes the element from rendering completely.
.toggle:checked ~ .menu {	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
display: block;	Element starts on a new line and fills the width (used on links and images).
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid rgb(255 255 255 / 25%);	A top border used as an accent or separator.
@media (min-width: 700px) {	Applies from the given width upwards (mobile-first breakpoint).
gap: .5rem;	Space between grid or flex items without extra margins.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
.menu a:hover {	Applies while the pointer is over the element.

Check your work

- Menu opens and closes on mobile
- Burger hidden on desktop
- Label has an aria-label
- No horizontal scrollbar at 320px

Exercises

1. Animate the menu opening with grid-template-rows: 0fr to 1fr.
2. Rebuild with a <button> and aria-expanded using JavaScript.
3. Add a close (X) state to the burger icon.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 1002: Responsive hamburger menu for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 3 | Files: index.html, styles.css

Brief

Build a navigation that is a horizontal bar on desktop and collapses behind a hamburger button on phones, toggled by a hidden checkbox and no JavaScript.

Learning goals

- Use the checkbox hack with :checked ~
- Switch layouts with a min-width media query
- Use flex-basis: 100% to wrap an item to its own line

Elements and CSS used

HTML elements	CSS features
header, input type=checkbox, label, nav, ul, li, a	:checked ~, flex-basis: 100%, display: none/block, @media (min-width), flex-wrap

Build guide

1. Write the header: logo, hidden checkbox, label as the burger, nav.
2. Mobile first: hide .menu; show when the checkbox is checked.
3. Make .menu take the full row with flex-basis: 100%.
4. At 700px hide the burger and always show the menu inline.
5. Style links for both modes.

6. Test with keyboard: Space on the focused label toggles the checkbox.

Project 1002: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - Mobile menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="top">
    <a class="logo" href="index.html">Nile Bakery</a>
    <input type="checkbox" id="menu-toggle" class="toggle" hidden>
    <label for="menu-toggle" class="burger" aria-label="Open
menu">&#9776;</label>
    <nav class="menu" aria-label="Main">
      <ul>
        <li><a href="index.html">Home</a></li>
    <li><a href="#">Sourdough loaf</a></li>
    <li><a href="#">Croissant</a></li>
    <li><a href="#">Date cookies</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main><h1>Resize the window</h1><p>Below 700px the menu hides
behind a button.</p></main>
</body>
</html>
```

Project 1002: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.top { display: flex; align-items: center; justify-content: space-
between; flex-wrap: wrap; padding: .75rem 1rem; background: var(--
brand); color: #fff; }
.logo { color: #fff; text-decoration: none; font-weight: 700; }
.burger { font-size: 1.6rem; cursor: pointer; }
.menu { flex-basis: 100%; display: none; }
.toggle:checked ~ .menu { display: block; }
.menu ul { list-style: none; margin: .5rem 0 0; padding: 0; }
.menu a { display: block; padding: .6rem 0; color: #fff; text-
decoration: none; border-top: 1px solid rgb(255 255 255 / 25%); }
@media (min-width: 700px) {
```

```
  .burger { display: none; }
  .menu { display: block; flex-basis: auto; }
  .menu ul { display: flex; gap: .5rem; margin: 0; }
  .menu a { border: 0; padding: .5rem .8rem; border-radius: 6px; }
  .menu a:hover { background: rgb(255 255 255 / 20%); }
}
main { padding: 2rem 1rem; }
```

Project 1002 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - Mobile menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="top">	Introductory content: logo, title, navigation.
<input type="checkbox" id="menu-toggle" class="toggle" hidden>	Checkbox: on or off.
<label for="menu-toggle" class="burger" aria-label="Open menu">&#97...	Text label for a control; for matches the control's id, or the label wraps the control.
<nav class="menu" aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Sourdough loaf	One list item.

Line	What it does
<main><h1>Resize the window</h1><p>Below 700px the menu hides behin...	The unique content of this page; exactly one per page.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
padding: .75rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-decoration: none;	Removes the underline from links.
font-weight: 700;	Thickness of the text.
font-size: 1.6rem;	Size of the text.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
flex-basis: 100%;	The item takes a whole line, pushing the next items down.
display: none;	Removes the element from rendering completely.
.toggle:checked ~ .menu {	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
display: block;	Element starts on a new line and fills the width (used on links and images).
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid rgb(255 255 255 / 25%);	A top border used as an accent or separator.
@media (min-width: 700px) {	Applies from the given width upwards (mobile-first breakpoint).
gap: .5rem;	Space between grid or flex items without extra margins.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
.menu a:hover {	Applies while the pointer is over the element.

Check your work

- Menu opens and closes on mobile
- Burger hidden on desktop
- Label has an aria-label
- No horizontal scrollbar at 320px

Exercises

1. Animate the menu opening with grid-template-rows: 0fr to 1fr.
2. Rebuild with a <button> and aria-expanded using JavaScript.
3. Add a close (X) state to the burger icon.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 1003: Responsive hamburger menu for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 3 | Files: index.html, styles.css

Brief

Build a navigation that is a horizontal bar on desktop and collapses behind a hamburger button on phones, toggled by a hidden checkbox and no JavaScript.

Learning goals

- Use the checkbox hack with :checked ~
- Switch layouts with a min-width media query
- Use flex-basis: 100% to wrap an item to its own line

Elements and CSS used

HTML elements	CSS features
header, input type=checkbox, label, nav, ul, li, a	:checked ~, flex-basis: 100%, display: none/block, @media (min-width), flex-wrap

Build guide

1. Write the header: logo, hidden checkbox, label as the burger, nav.
2. Mobile first: hide .menu; show when the checkbox is checked.
3. Make .menu take the full row with flex-basis: 100%.
4. At 700px hide the burger and always show the menu inline.
5. Style links for both modes.

6. Test with keyboard: Space on the focused label toggles the checkbox.

Project 1003: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - Mobile menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="top">
    <a class="logo" href="index.html">Pyramid Fitness</a>
    <input type="checkbox" id="menu-toggle" class="toggle" hidden>
    <label for="menu-toggle" class="burger" aria-label="Open
menu">&#9776;</label>
    <nav class="menu" aria-label="Main">
      <ul>
        <li><a href="index.html">Home</a></li>
    <li><a href="#">Morning yoga</a></li>
    <li><a href="#">Strength circuit</a></li>
    <li><a href="#">Spinning</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main><h1>Resize the window</h1><p>Below 700px the menu hides
behind a button.</p></main>
</body>
</html>
```

Project 1003: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.top { display: flex; align-items: center; justify-content: space-
between; flex-wrap: wrap; padding: .75rem 1rem; background: var(--
brand); color: #fff; }
.logo { color: #fff; text-decoration: none; font-weight: 700; }
.burger { font-size: 1.6rem; cursor: pointer; }
.menu { flex-basis: 100%; display: none; }
.toggle:checked ~ .menu { display: block; }
.menu ul { list-style: none; margin: .5rem 0 0; padding: 0; }
.menu a { display: block; padding: .6rem 0; color: #fff; text-
decoration: none; border-top: 1px solid rgb(255 255 255 / 25%); }
@media (min-width: 700px) {
```

```
  .burger { display: none; }
  .menu { display: block; flex-basis: auto; }
  .menu ul { display: flex; gap: .5rem; margin: 0; }
  .menu a { border: 0; padding: .5rem .8rem; border-radius: 6px; }
  .menu a:hover { background: rgb(255 255 255 / 20%); }
}
main { padding: 2rem 1rem; }
```

Project 1003 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - Mobile menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="top">	Introductory content: logo, title, navigation.
<input type="checkbox" id="menu-toggle" class="toggle" hidden>	Checkbox: on or off.
<label for="menu-toggle" class="burger" aria-label="Open menu">&#97...	Text label for a control; for matches the control's id, or the label wraps the control.
<nav class="menu" aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Morning yoga	One list item.

Line	What it does
<main><h1>Resize the window</h1><p>Below 700px the menu hides behin...	The unique content of this page; exactly one per page.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
padding: .75rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-decoration: none;	Removes the underline from links.
font-weight: 700;	Thickness of the text.
font-size: 1.6rem;	Size of the text.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
flex-basis: 100%;	The item takes a whole line, pushing the next items down.
display: none;	Removes the element from rendering completely.
.toggle:checked ~ .menu {	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
display: block;	Element starts on a new line and fills the width (used on links and images).
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid rgb(255 255 255 / 25%);	A top border used as an accent or separator.
@media (min-width: 700px) {	Applies from the given width upwards (mobile-first breakpoint).
gap: .5rem;	Space between grid or flex items without extra margins.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
.menu a:hover {	Applies while the pointer is over the element.

Check your work

- Menu opens and closes on mobile
- Burger hidden on desktop
- Label has an aria-label
- No horizontal scrollbar at 320px

Exercises

1. Animate the menu opening with grid-template-rows: 0fr to 1fr.
2. Rebuild with a <button> and aria-expanded using JavaScript.
3. Add a close (X) state to the burger icon.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 1004: Responsive hamburger menu for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 3 | Files: index.html, styles.css

Brief

Build a navigation that is a horizontal bar on desktop and collapses behind a hamburger button on phones, toggled by a hidden checkbox and no JavaScript.

Learning goals

- Use the checkbox hack with :checked ~
- Switch layouts with a min-width media query
- Use flex-basis: 100% to wrap an item to its own line

Elements and CSS used

HTML elements	CSS features
header, input type=checkbox, label, nav, ul, li, a	:checked ~, flex-basis: 100%, display: none/block, @media (min-width), flex-wrap

Build guide

1. Write the header: logo, hidden checkbox, label as the burger, nav.
2. Mobile first: hide .menu; show when the checkbox is checked.
3. Make .menu take the full row with flex-basis: 100%.
4. At 700px hide the burger and always show the menu inline.
5. Style links for both modes.

6. Test with keyboard: Space on the focused label toggles the checkbox.

Project 1004: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - Mobile menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="top">
    <a class="logo" href="index.html">Delta Dental Clinic</a>
    <input type="checkbox" id="menu-toggle" class="toggle" hidden>
    <label for="menu-toggle" class="burger" aria-label="Open
menu">&#9776;</label>
    <nav class="menu" aria-label="Main">
      <ul>
        <li><a href="index.html">Home</a></li>
    <li><a href="#">Check-up</a></li>
    <li><a href="#">Whitening</a></li>
    <li><a href="#">Filling</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main><h1>Resize the window</h1><p>Below 700px the menu hides
behind a button.</p></main>
</body>
</html>
```

Project 1004: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.top { display: flex; align-items: center; justify-content: space-
between; flex-wrap: wrap; padding: .75rem 1rem; background: var(--
brand); color: #fff; }
.logo { color: #fff; text-decoration: none; font-weight: 700; }
.burger { font-size: 1.6rem; cursor: pointer; }
.menu { flex-basis: 100%; display: none; }
.toggle:checked ~ .menu { display: block; }
.menu ul { list-style: none; margin: .5rem 0 0; padding: 0; }
.menu a { display: block; padding: .6rem 0; color: #fff; text-
decoration: none; border-top: 1px solid rgb(255 255 255 / 25%); }
@media (min-width: 700px) {
```

```
  .burger { display: none; }
  .menu { display: block; flex-basis: auto; }
  .menu ul { display: flex; gap: .5rem; margin: 0; }
  .menu a { border: 0; padding: .5rem .8rem; border-radius: 6px; }
  .menu a:hover { background: rgb(255 255 255 / 20%); }
}
main { padding: 2rem 1rem; }
```

Project 1004 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - Mobile menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="top">	Introductory content: logo, title, navigation.
<input type="checkbox" id="menu-toggle" class="toggle" hidden>	Checkbox: on or off.
<label for="menu-toggle" class="burger" aria-label="Open menu">&#97...	Text label for a control; for matches the control's id, or the label wraps the control.
<nav class="menu" aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Check-up	One list item.

Line	What it does
<main><h1>Resize the window</h1><p>Below 700px the menu hides behin...	The unique content of this page; exactly one per page.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
padding: .75rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-decoration: none;	Removes the underline from links.
font-weight: 700;	Thickness of the text.
font-size: 1.6rem;	Size of the text.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
flex-basis: 100%;	The item takes a whole line, pushing the next items down.
display: none;	Removes the element from rendering completely.
.toggle:checked ~ .menu {	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
display: block;	Element starts on a new line and fills the width (used on links and images).
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid rgb(255 255 255 / 25%);	A top border used as an accent or separator.
@media (min-width: 700px) {	Applies from the given width upwards (mobile-first breakpoint).
gap: .5rem;	Space between grid or flex items without extra margins.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
.menu a:hover {	Applies while the pointer is over the element.

Check your work

- Menu opens and closes on mobile
- Burger hidden on desktop
- Label has an aria-label
- No horizontal scrollbar at 320px

Exercises

1. Animate the menu opening with grid-template-rows: 0fr to 1fr.
2. Rebuild with a <button> and aria-expanded using JavaScript.
3. Add a close (X) state to the burger icon.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 1005: Responsive hamburger menu for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 3 | Files: index.html, styles.css

Brief

Build a navigation that is a horizontal bar on desktop and collapses behind a hamburger button on phones, toggled by a hidden checkbox and no JavaScript.

Learning goals

- Use the checkbox hack with :checked ~
- Switch layouts with a min-width media query
- Use flex-basis: 100% to wrap an item to its own line

Elements and CSS used

HTML elements	CSS features
header, input type=checkbox, label, nav, ul, li, a	:checked ~, flex-basis: 100%, display: none/block, @media (min-width), flex-wrap

Build guide

1. Write the header: logo, hidden checkbox, label as the burger, nav.
2. Mobile first: hide .menu; show when the checkbox is checked.
3. Make .menu take the full row with flex-basis: 100%.
4. At 700px hide the burger and always show the menu inline.
5. Style links for both modes.

6. Test with keyboard: Space on the focused label toggles the checkbox.

Project 1005: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - Mobile menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="top">
    <a class="logo" href="index.html">Red Sea Travel</a>
    <input type="checkbox" id="menu-toggle" class="toggle" hidden>
    <label for="menu-toggle" class="burger" aria-label="Open
menu">&#9776;</label>
    <nav class="menu" aria-label="Main">
      <ul>
        <li><a href="index.html">Home</a></li>
    <li><a href="#">Luxor day trip</a></li>
    <li><a href="#">Snorkelling</a></li>
    <li><a href="#">Desert safari</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main><h1>Resize the window</h1><p>Below 700px the menu hides
behind a button.</p></main>
</body>
</html>
```

Project 1005: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.top { display: flex; align-items: center; justify-content: space-
between; flex-wrap: wrap; padding: .75rem 1rem; background: var(--
brand); color: #fff; }
.logo { color: #fff; text-decoration: none; font-weight: 700; }
.burger { font-size: 1.6rem; cursor: pointer; }
.menu { flex-basis: 100%; display: none; }
.toggle:checked ~ .menu { display: block; }
.menu ul { list-style: none; margin: .5rem 0 0; padding: 0; }
.menu a { display: block; padding: .6rem 0; color: #fff; text-
decoration: none; border-top: 1px solid rgb(255 255 255 / 25%); }
@media (min-width: 700px) {
```

```
  .burger { display: none; }
  .menu { display: block; flex-basis: auto; }
  .menu ul { display: flex; gap: .5rem; margin: 0; }
  .menu a { border: 0; padding: .5rem .8rem; border-radius: 6px; }
  .menu a:hover { background: rgb(255 255 255 / 20%); }
}
main { padding: 2rem 1rem; }
```

Project 1005 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - Mobile menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="top">	Introductory content: logo, title, navigation.
<input type="checkbox" id="menu-toggle" class="toggle" hidden>	Checkbox: on or off.
<label for="menu-toggle" class="burger" aria-label="Open menu">&#97...	Text label for a control; for matches the control's id, or the label wraps the control.
<nav class="menu" aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Luxor day trip	One list item.

Line	What it does
<main><h1>Resize the window</h1><p>Below 700px the menu hides behin...	The unique content of this page; exactly one per page.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
padding: .75rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-decoration: none;	Removes the underline from links.
font-weight: 700;	Thickness of the text.
font-size: 1.6rem;	Size of the text.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
flex-basis: 100%;	The item takes a whole line, pushing the next items down.
display: none;	Removes the element from rendering completely.
.toggle:checked ~ .menu {	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
display: block;	Element starts on a new line and fills the width (used on links and images).
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid rgb(255 255 255 / 25%);	A top border used as an accent or separator.
@media (min-width: 700px) {	Applies from the given width upwards (mobile-first breakpoint).
gap: .5rem;	Space between grid or flex items without extra margins.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
.menu a:hover {	Applies while the pointer is over the element.

Check your work

- Menu opens and closes on mobile
- Burger hidden on desktop
- Label has an aria-label
- No horizontal scrollbar at 320px

Exercises

1. Animate the menu opening with grid-template-rows: 0fr to 1fr.
2. Rebuild with a <button> and aria-expanded using JavaScript.
3. Add a close (X) state to the burger icon.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 1006: Responsive hamburger menu for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 3 | Files: index.html, styles.css

Brief

Build a navigation that is a horizontal bar on desktop and collapses behind a hamburger button on phones, toggled by a hidden checkbox and no JavaScript.

Learning goals

- Use the checkbox hack with :checked ~
- Switch layouts with a min-width media query
- Use flex-basis: 100% to wrap an item to its own line

Elements and CSS used

HTML elements	CSS features
header, input type=checkbox, label, nav, ul, li, a	:checked ~, flex-basis: 100%, display: none/block, @media (min-width), flex-wrap

Build guide

1. Write the header: logo, hidden checkbox, label as the burger, nav.
2. Mobile first: hide .menu; show when the checkbox is checked.
3. Make .menu take the full row with flex-basis: 100%.
4. At 700px hide the burger and always show the menu inline.
5. Style links for both modes.

6. Test with keyboard: Space on the focused label toggles the checkbox.

Project 1006: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - Mobile menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="top">
    <a class="logo" href="index.html">Lotus Language School</a>
    <input type="checkbox" id="menu-toggle" class="toggle" hidden>
    <label for="menu-toggle" class="burger" aria-label="Open
menu">&#9776;</label>
    <nav class="menu" aria-label="Main">
      <ul>
        <li><a href="index.html">Home</a></li>
    <li><a href="#">English A1</a></li>
    <li><a href="#">French B1</a></li>
    <li><a href="#">German A2</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main><h1>Resize the window</h1><p>Below 700px the menu hides
behind a button.</p></main>
</body>
</html>
```

Project 1006: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.top { display: flex; align-items: center; justify-content: space-
between; flex-wrap: wrap; padding: .75rem 1rem; background: var(--
brand); color: #fff; }
.logo { color: #fff; text-decoration: none; font-weight: 700; }
.burger { font-size: 1.6rem; cursor: pointer; }
.menu { flex-basis: 100%; display: none; }
.toggle:checked ~ .menu { display: block; }
.menu ul { list-style: none; margin: .5rem 0 0; padding: 0; }
.menu a { display: block; padding: .6rem 0; color: #fff; text-
decoration: none; border-top: 1px solid rgb(255 255 255 / 25%); }
@media (min-width: 700px) {
```

```
  .burger { display: none; }
  .menu { display: block; flex-basis: auto; }
  .menu ul { display: flex; gap: .5rem; margin: 0; }
  .menu a { border: 0; padding: .5rem .8rem; border-radius: 6px; }
  .menu a:hover { background: rgb(255 255 255 / 20%); }
}
main { padding: 2rem 1rem; }
```

Project 1006 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - Mobile menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="top">	Introductory content: logo, title, navigation.
<input type="checkbox" id="menu-toggle" class="toggle" hidden>	Checkbox: on or off.
<label for="menu-toggle" class="burger" aria-label="Open menu">&#97...	Text label for a control; for matches the control's id, or the label wraps the control.
<nav class="menu" aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
English A1	One list item.

Line	What it does
<main><h1>Resize the window</h1><p>Below 700px the menu hides behin...	The unique content of this page; exactly one per page.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
padding: .75rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-decoration: none;	Removes the underline from links.
font-weight: 700;	Thickness of the text.
font-size: 1.6rem;	Size of the text.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
flex-basis: 100%;	The item takes a whole line, pushing the next items down.
display: none;	Removes the element from rendering completely.
.toggle:checked ~ .menu {	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
display: block;	Element starts on a new line and fills the width (used on links and images).
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid rgb(255 255 255 / 25%);	A top border used as an accent or separator.
@media (min-width: 700px) {	Applies from the given width upwards (mobile-first breakpoint).
gap: .5rem;	Space between grid or flex items without extra margins.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
.menu a:hover {	Applies while the pointer is over the element.

Check your work

- Menu opens and closes on mobile
- Burger hidden on desktop
- Label has an aria-label
- No horizontal scrollbar at 320px

Exercises

1. Animate the menu opening with grid-template-rows: 0fr to 1fr.
2. Rebuild with a <button> and aria-expanded using JavaScript.
3. Add a close (X) state to the burger icon.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 1007: Responsive hamburger menu for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 3 | Files: index.html, styles.css

Brief

Build a navigation that is a horizontal bar on desktop and collapses behind a hamburger button on phones, toggled by a hidden checkbox and no JavaScript.

Learning goals

- Use the checkbox hack with :checked ~
- Switch layouts with a min-width media query
- Use flex-basis: 100% to wrap an item to its own line

Elements and CSS used

HTML elements	CSS features
header, input type=checkbox, label, nav, ul, li, a	:checked ~, flex-basis: 100%, display: none/block, @media (min-width), flex-wrap

Build guide

1. Write the header: logo, hidden checkbox, label as the burger, nav.
2. Mobile first: hide .menu; show when the checkbox is checked.
3. Make .menu take the full row with flex-basis: 100%.
4. At 700px hide the burger and always show the menu inline.
5. Style links for both modes.

6. Test with keyboard: Space on the focused label toggles the checkbox.

Project 1007: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - Mobile menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="top">
    <a class="logo" href="index.html">Green Leaf Cafe</a>
    <input type="checkbox" id="menu-toggle" class="toggle" hidden>
    <label for="menu-toggle" class="burger" aria-label="Open
menu">&#9776;</label>
    <nav class="menu" aria-label="Main">
      <ul>
        <li><a href="index.html">Home</a></li>
    <li><a href="#">Flat white</a></li>
    <li><a href="#">Cold brew</a></li>
    <li><a href="#">Hibiscus iced tea</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main><h1>Resize the window</h1><p>Below 700px the menu hides
behind a button.</p></main>
</body>
</html>
```

Project 1007: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.top { display: flex; align-items: center; justify-content: space-
between; flex-wrap: wrap; padding: .75rem 1rem; background: var(--
brand); color: #fff; }
.logo { color: #fff; text-decoration: none; font-weight: 700; }
.burger { font-size: 1.6rem; cursor: pointer; }
.menu { flex-basis: 100%; display: none; }
.toggle:checked ~ .menu { display: block; }
.menu ul { list-style: none; margin: .5rem 0 0; padding: 0; }
.menu a { display: block; padding: .6rem 0; color: #fff; text-
decoration: none; border-top: 1px solid rgb(255 255 255 / 25%); }
@media (min-width: 700px) {
```

```
  .burger { display: none; }
  .menu { display: block; flex-basis: auto; }
  .menu ul { display: flex; gap: .5rem; margin: 0; }
  .menu a { border: 0; padding: .5rem .8rem; border-radius: 6px; }
  .menu a:hover { background: rgb(255 255 255 / 20%); }
}
main { padding: 2rem 1rem; }
```

Project 1007 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - Mobile menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="top">	Introductory content: logo, title, navigation.
<input type="checkbox" id="menu-toggle" class="toggle" hidden>	Checkbox: on or off.
<label for="menu-toggle" class="burger" aria-label="Open menu">&#97...	Text label for a control; for matches the control's id, or the label wraps the control.
<nav class="menu" aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Flat white	One list item.

Line	What it does
<main><h1>Resize the window</h1><p>Below 700px the menu hides behin...	The unique content of this page; exactly one per page.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
padding: .75rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-decoration: none;	Removes the underline from links.
font-weight: 700;	Thickness of the text.
font-size: 1.6rem;	Size of the text.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
flex-basis: 100%;	The item takes a whole line, pushing the next items down.
display: none;	Removes the element from rendering completely.
.toggle:checked ~ .menu {	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
display: block;	Element starts on a new line and fills the width (used on links and images).
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid rgb(255 255 255 / 25%);	A top border used as an accent or separator.
@media (min-width: 700px) {	Applies from the given width upwards (mobile-first breakpoint).
gap: .5rem;	Space between grid or flex items without extra margins.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
.menu a:hover {	Applies while the pointer is over the element.

Check your work

- Menu opens and closes on mobile
- Burger hidden on desktop
- Label has an aria-label
- No horizontal scrollbar at 320px

Exercises

1. Animate the menu opening with grid-template-rows: 0fr to 1fr.
2. Rebuild with a <button> and aria-expanded using JavaScript.
3. Add a close (X) state to the burger icon.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 1008: Responsive hamburger menu for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 3 | Files: index.html, styles.css

Brief

Build a navigation that is a horizontal bar on desktop and collapses behind a hamburger button on phones, toggled by a hidden checkbox and no JavaScript.

Learning goals

- Use the checkbox hack with :checked ~
- Switch layouts with a min-width media query
- Use flex-basis: 100% to wrap an item to its own line

Elements and CSS used

HTML elements	CSS features
header, input type=checkbox, label, nav, ul, li, a	:checked ~, flex-basis: 100%, display: none/block, @media (min-width), flex-wrap

Build guide

1. Write the header: logo, hidden checkbox, label as the burger, nav.
2. Mobile first: hide .menu; show when the checkbox is checked.
3. Make .menu take the full row with flex-basis: 100%.
4. At 700px hide the burger and always show the menu inline.
5. Style links for both modes.

6. Test with keyboard: Space on the focused label toggles the checkbox.

Project 1008: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - Mobile menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="top">
    <a class="logo" href="index.html">Sinai Trekking Club</a>
    <input type="checkbox" id="menu-toggle" class="toggle" hidden>
    <label for="menu-toggle" class="burger" aria-label="Open
menu">&#9776;</label>
    <nav class="menu" aria-label="Main">
      <ul>
        <li><a href="index.html">Home</a></li>
    <li><a href="#">Mount Sinai sunrise</a></li>
    <li><a href="#">Blue Desert loop</a></li>
    <li><a href="#">Wadi Gnai</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main><h1>Resize the window</h1><p>Below 700px the menu hides
behind a button.</p></main>
</body>
</html>
```

Project 1008: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.top { display: flex; align-items: center; justify-content: space-
between; flex-wrap: wrap; padding: .75rem 1rem; background: var(--
brand); color: #fff; }
.logo { color: #fff; text-decoration: none; font-weight: 700; }
.burger { font-size: 1.6rem; cursor: pointer; }
.menu { flex-basis: 100%; display: none; }
.toggle:checked ~ .menu { display: block; }
.menu ul { list-style: none; margin: .5rem 0 0; padding: 0; }
.menu a { display: block; padding: .6rem 0; color: #fff; text-
decoration: none; border-top: 1px solid rgb(255 255 255 / 25%); }
@media (min-width: 700px) {
```

```
  .burger { display: none; }
  .menu { display: block; flex-basis: auto; }
  .menu ul { display: flex; gap: .5rem; margin: 0; }
  .menu a { border: 0; padding: .5rem .8rem; border-radius: 6px; }
  .menu a:hover { background: rgb(255 255 255 / 20%); }
}
main { padding: 2rem 1rem; }
```

Project 1008 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - Mobile menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="top">	Introductory content: logo, title, navigation.
<input type="checkbox" id="menu-toggle" class="toggle" hidden>	Checkbox: on or off.
<label for="menu-toggle" class="burger" aria-label="Open menu">&#97...	Text label for a control; for matches the control's id, or the label wraps the control.
<nav class="menu" aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Mount Sinai sunrise	One list item.

Line	What it does
<main><h1>Resize the window</h1><p>Below 700px the menu hides behin...	The unique content of this page; exactly one per page.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
padding: .75rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-decoration: none;	Removes the underline from links.
font-weight: 700;	Thickness of the text.
font-size: 1.6rem;	Size of the text.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
flex-basis: 100%;	The item takes a whole line, pushing the next items down.
display: none;	Removes the element from rendering completely.
.toggle:checked ~ .menu {	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
display: block;	Element starts on a new line and fills the width (used on links and images).
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid rgb(255 255 255 / 25%);	A top border used as an accent or separator.
@media (min-width: 700px) {	Applies from the given width upwards (mobile-first breakpoint).
gap: .5rem;	Space between grid or flex items without extra margins.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
.menu a:hover {	Applies while the pointer is over the element.

Check your work

- Menu opens and closes on mobile
- Burger hidden on desktop
- Label has an aria-label
- No horizontal scrollbar at 320px

Exercises

1. Animate the menu opening with grid-template-rows: 0fr to 1fr.
2. Rebuild with a <button> and aria-expanded using JavaScript.
3. Add a close (X) state to the burger icon.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 1009: Responsive hamburger menu for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 3 | Files: index.html, styles.css

Brief

Build a navigation that is a horizontal bar on desktop and collapses behind a hamburger button on phones, toggled by a hidden checkbox and no JavaScript.

Learning goals

- Use the checkbox hack with :checked ~
- Switch layouts with a min-width media query
- Use flex-basis: 100% to wrap an item to its own line

Elements and CSS used

HTML elements	CSS features
header, input type=checkbox, label, nav, ul, li, a	:checked ~, flex-basis: 100%, display: none/block, @media (min-width), flex-wrap

Build guide

1. Write the header: logo, hidden checkbox, label as the burger, nav.
2. Mobile first: hide .menu; show when the checkbox is checked.
3. Make .menu take the full row with flex-basis: 100%.
4. At 700px hide the burger and always show the menu inline.
5. Style links for both modes.

6. Test with keyboard: Space on the focused label toggles the checkbox.

Project 1009: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - Mobile menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="top">
    <a class="logo" href="index.html">Horizon Photography</a>
    <input type="checkbox" id="menu-toggle" class="toggle" hidden>
    <label for="menu-toggle" class="burger" aria-label="Open
menu">&#9776;</label>
    <nav class="menu" aria-label="Main">
      <ul>
        <li><a href="index.html">Home</a></li>
    <li><a href="#">Portrait session</a></li>
    <li><a href="#">Wedding day</a></li>
    <li><a href="#">Product shoot</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main><h1>Resize the window</h1><p>Below 700px the menu hides
behind a button.</p></main>
</body>
</html>
```

Project 1009: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.top { display: flex; align-items: center; justify-content: space-
between; flex-wrap: wrap; padding: .75rem 1rem; background: var(--
brand); color: #fff; }
.logo { color: #fff; text-decoration: none; font-weight: 700; }
.burger { font-size: 1.6rem; cursor: pointer; }
.menu { flex-basis: 100%; display: none; }
.toggle:checked ~ .menu { display: block; }
.menu ul { list-style: none; margin: .5rem 0 0; padding: 0; }
.menu a { display: block; padding: .6rem 0; color: #fff; text-
decoration: none; border-top: 1px solid rgb(255 255 255 / 25%); }
@media (min-width: 700px) {
```

```
  .burger { display: none; }
  .menu { display: block; flex-basis: auto; }
  .menu ul { display: flex; gap: .5rem; margin: 0; }
  .menu a { border: 0; padding: .5rem .8rem; border-radius: 6px; }
  .menu a:hover { background: rgb(255 255 255 / 20%); }
}
main { padding: 2rem 1rem; }
```

Project 1009 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - Mobile menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="top">	Introductory content: logo, title, navigation.
<input type="checkbox" id="menu-toggle" class="toggle" hidden>	Checkbox: on or off.
<label for="menu-toggle" class="burger" aria-label="Open menu">&#97...	Text label for a control; for matches the control's id, or the label wraps the control.
<nav class="menu" aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Portrait session	One list item.

Line	What it does
<main><h1>Resize the window</h1><p>Below 700px the menu hides behin...	The unique content of this page; exactly one per page.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
padding: .75rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-decoration: none;	Removes the underline from links.
font-weight: 700;	Thickness of the text.
font-size: 1.6rem;	Size of the text.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
flex-basis: 100%;	The item takes a whole line, pushing the next items down.
display: none;	Removes the element from rendering completely.
.toggle:checked ~ .menu {	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
display: block;	Element starts on a new line and fills the width (used on links and images).
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid rgb(255 255 255 / 25%);	A top border used as an accent or separator.
@media (min-width: 700px) {	Applies from the given width upwards (mobile-first breakpoint).
gap: .5rem;	Space between grid or flex items without extra margins.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
.menu a:hover {	Applies while the pointer is over the element.

Check your work

- Menu opens and closes on mobile
- Burger hidden on desktop
- Label has an aria-label
- No horizontal scrollbar at 320px

Exercises

1. Animate the menu opening with grid-template-rows: 0fr to 1fr.
2. Rebuild with a <button> and aria-expanded using JavaScript.
3. Add a close (X) state to the burger icon.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 1010: Responsive hamburger menu for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 3 | Files: index.html, styles.css

Brief

Build a navigation that is a horizontal bar on desktop and collapses behind a hamburger button on phones, toggled by a hidden checkbox and no JavaScript.

Learning goals

- Use the checkbox hack with :checked ~
- Switch layouts with a min-width media query
- Use flex-basis: 100% to wrap an item to its own line

Elements and CSS used

HTML elements	CSS features
header, input type=checkbox, label, nav, ul, li, a	:checked ~, flex-basis: 100%, display: none/block, @media (min-width), flex-wrap

Build guide

1. Write the header: logo, hidden checkbox, label as the burger, nav.
2. Mobile first: hide .menu; show when the checkbox is checked.
3. Make .menu take the full row with flex-basis: 100%.
4. At 700px hide the burger and always show the menu inline.
5. Style links for both modes.

6. Test with keyboard: Space on the focused label toggles the checkbox.

Project 1010: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - Mobile menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="top">
    <a class="logo" href="index.html">Papyrus Stationery</a>
    <input type="checkbox" id="menu-toggle" class="toggle" hidden>
    <label for="menu-toggle" class="burger" aria-label="Open
menu">&#9776;</label>
    <nav class="menu" aria-label="Main">
      <ul>
        <li><a href="index.html">Home</a></li>
    <li><a href="#">Dotted notebook</a></li>
    <li><a href="#">Fountain pen</a></li>
    <li><a href="#">Washi tape set</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main><h1>Resize the window</h1><p>Below 700px the menu hides
behind a button.</p></main>
</body>
</html>
```

Project 1010: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.top { display: flex; align-items: center; justify-content: space-
between; flex-wrap: wrap; padding: .75rem 1rem; background: var(--
brand); color: #fff; }
.logo { color: #fff; text-decoration: none; font-weight: 700; }
.burger { font-size: 1.6rem; cursor: pointer; }
.menu { flex-basis: 100%; display: none; }
.toggle:checked ~ .menu { display: block; }
.menu ul { list-style: none; margin: .5rem 0 0; padding: 0; }
.menu a { display: block; padding: .6rem 0; color: #fff; text-
decoration: none; border-top: 1px solid rgb(255 255 255 / 25%); }
@media (min-width: 700px) {
```

```
  .burger { display: none; }
  .menu { display: block; flex-basis: auto; }
  .menu ul { display: flex; gap: .5rem; margin: 0; }
  .menu a { border: 0; padding: .5rem .8rem; border-radius: 6px; }
  .menu a:hover { background: rgb(255 255 255 / 20%); }
}
main { padding: 2rem 1rem; }
```

Project 1010 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - Mobile menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="top">	Introductory content: logo, title, navigation.
<input type="checkbox" id="menu-toggle" class="toggle" hidden>	Checkbox: on or off.
<label for="menu-toggle" class="burger" aria-label="Open menu">&#97...	Text label for a control; for matches the control's id, or the label wraps the control.
<nav class="menu" aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Dotted notebook	One list item.

Line	What it does
<main><h1>Resize the window</h1><p>Below 700px the menu hides behin...	The unique content of this page; exactly one per page.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
padding: .75rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-decoration: none;	Removes the underline from links.
font-weight: 700;	Thickness of the text.
font-size: 1.6rem;	Size of the text.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
flex-basis: 100%;	The item takes a whole line, pushing the next items down.
display: none;	Removes the element from rendering completely.
.toggle:checked ~ .menu {	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
display: block;	Element starts on a new line and fills the width (used on links and images).
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid rgb(255 255 255 / 25%);	A top border used as an accent or separator.
@media (min-width: 700px) {	Applies from the given width upwards (mobile-first breakpoint).
gap: .5rem;	Space between grid or flex items without extra margins.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
.menu a:hover {	Applies while the pointer is over the element.

Check your work

- Menu opens and closes on mobile
- Burger hidden on desktop
- Label has an aria-label
- No horizontal scrollbar at 320px

Exercises

1. Animate the menu opening with grid-template-rows: 0fr to 1fr.
2. Rebuild with a <button> and aria-expanded using JavaScript.
3. Add a close (X) state to the burger icon.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 1011: Responsive hamburger menu for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 3 | Files: index.html, styles.css

Brief

Build a navigation that is a horizontal bar on desktop and collapses behind a hamburger button on phones, toggled by a hidden checkbox and no JavaScript.

Learning goals

- Use the checkbox hack with :checked ~
- Switch layouts with a min-width media query
- Use flex-basis: 100% to wrap an item to its own line

Elements and CSS used

HTML elements	CSS features
header, input type=checkbox, label, nav, ul, li, a	:checked ~, flex-basis: 100%, display: none/block, @media (min-width), flex-wrap

Build guide

1. Write the header: logo, hidden checkbox, label as the burger, nav.
2. Mobile first: hide .menu; show when the checkbox is checked.
3. Make .menu take the full row with flex-basis: 100%.
4. At 700px hide the burger and always show the menu inline.
5. Style links for both modes.

6. Test with keyboard: Space on the focused label toggles the checkbox.

Project 1011: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - Mobile menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="top">
    <a class="logo" href="index.html">Oasis Plant Nursery</a>
    <input type="checkbox" id="menu-toggle" class="toggle" hidden>
    <label for="menu-toggle" class="burger" aria-label="Open
menu">&#9776;</label>
    <nav class="menu" aria-label="Main">
      <ul>
        <li><a href="index.html">Home</a></li>
    <li><a href="#">Monstera</a></li>
    <li><a href="#">Snake plant</a></li>
    <li><a href="#">Basil pot</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main><h1>Resize the window</h1><p>Below 700px the menu hides
behind a button.</p></main>
</body>
</html>
```

Project 1011: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.top { display: flex; align-items: center; justify-content: space-
between; flex-wrap: wrap; padding: .75rem 1rem; background: var(--
brand); color: #fff; }
.logo { color: #fff; text-decoration: none; font-weight: 700; }
.burger { font-size: 1.6rem; cursor: pointer; }
.menu { flex-basis: 100%; display: none; }
.toggle:checked ~ .menu { display: block; }
.menu ul { list-style: none; margin: .5rem 0 0; padding: 0; }
.menu a { display: block; padding: .6rem 0; color: #fff; text-
decoration: none; border-top: 1px solid rgb(255 255 255 / 25%); }
@media (min-width: 700px) {
```

```
  .burger { display: none; }
  .menu { display: block; flex-basis: auto; }
  .menu ul { display: flex; gap: .5rem; margin: 0; }
  .menu a { border: 0; padding: .5rem .8rem; border-radius: 6px; }
  .menu a:hover { background: rgb(255 255 255 / 20%); }
}
main { padding: 2rem 1rem; }
```

Project 1011 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - Mobile menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="top">	Introductory content: logo, title, navigation.
<input type="checkbox" id="menu-toggle" class="toggle" hidden>	Checkbox: on or off.
<label for="menu-toggle" class="burger" aria-label="Open menu">&#97...	Text label for a control; for matches the control's id, or the label wraps the control.
<nav class="menu" aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Monstera	One list item.

Line	What it does
<main><h1>Resize the window</h1><p>Below 700px the menu hides behin...	The unique content of this page; exactly one per page.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
padding: .75rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-decoration: none;	Removes the underline from links.
font-weight: 700;	Thickness of the text.
font-size: 1.6rem;	Size of the text.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
flex-basis: 100%;	The item takes a whole line, pushing the next items down.
display: none;	Removes the element from rendering completely.
.toggle:checked ~ .menu {	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
display: block;	Element starts on a new line and fills the width (used on links and images).
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid rgb(255 255 255 / 25%);	A top border used as an accent or separator.
@media (min-width: 700px) {	Applies from the given width upwards (mobile-first breakpoint).
gap: .5rem;	Space between grid or flex items without extra margins.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
.menu a:hover {	Applies while the pointer is over the element.

Check your work

- Menu opens and closes on mobile
- Burger hidden on desktop
- Label has an aria-label
- No horizontal scrollbar at 320px

Exercises

1. Animate the menu opening with grid-template-rows: 0fr to 1fr.
2. Rebuild with a <button> and aria-expanded using JavaScript.
3. Add a close (X) state to the burger icon.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 1012: Responsive hamburger menu for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 3 | Files: index.html, styles.css

Brief

Build a navigation that is a horizontal bar on desktop and collapses behind a hamburger button on phones, toggled by a hidden checkbox and no JavaScript.

Learning goals

- Use the checkbox hack with :checked ~
- Switch layouts with a min-width media query
- Use flex-basis: 100% to wrap an item to its own line

Elements and CSS used

HTML elements	CSS features
header, input type=checkbox, label, nav, ul, li, a	:checked ~, flex-basis: 100%, display: none/block, @media (min-width), flex-wrap

Build guide

1. Write the header: logo, hidden checkbox, label as the burger, nav.
2. Mobile first: hide .menu; show when the checkbox is checked.
3. Make .menu take the full row with flex-basis: 100%.
4. At 700px hide the burger and always show the menu inline.
5. Style links for both modes.

6. Test with keyboard: Space on the focused label toggles the checkbox.

Project 1012: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - Mobile menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="top">
    <a class="logo" href="index.html">Cedar Furniture</a>
    <input type="checkbox" id="menu-toggle" class="toggle" hidden>
    <label for="menu-toggle" class="burger" aria-label="Open
menu">&#9776;</label>
    <nav class="menu" aria-label="Main">
      <ul>
        <li><a href="index.html">Home</a></li>
    <li><a href="#">Oak dining table</a></li>
    <li><a href="#">Bookshelf</a></li>
    <li><a href="#">Bedside table</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main><h1>Resize the window</h1><p>Below 700px the menu hides
behind a button.</p></main>
</body>
</html>
```

Project 1012: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.top { display: flex; align-items: center; justify-content: space-
between; flex-wrap: wrap; padding: .75rem 1rem; background: var(--
brand); color: #fff; }
.logo { color: #fff; text-decoration: none; font-weight: 700; }
.burger { font-size: 1.6rem; cursor: pointer; }
.menu { flex-basis: 100%; display: none; }
.toggle:checked ~ .menu { display: block; }
.menu ul { list-style: none; margin: .5rem 0 0; padding: 0; }
.menu a { display: block; padding: .6rem 0; color: #fff; text-
decoration: none; border-top: 1px solid rgb(255 255 255 / 25%); }
@media (min-width: 700px) {
```

```
  .burger { display: none; }
  .menu { display: block; flex-basis: auto; }
  .menu ul { display: flex; gap: .5rem; margin: 0; }
  .menu a { border: 0; padding: .5rem .8rem; border-radius: 6px; }
  .menu a:hover { background: rgb(255 255 255 / 20%); }
}
main { padding: 2rem 1rem; }
```

Project 1012 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - Mobile menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="top">	Introductory content: logo, title, navigation.
<input type="checkbox" id="menu-toggle" class="toggle" hidden>	Checkbox: on or off.
<label for="menu-toggle" class="burger" aria-label="Open menu">&#97...	Text label for a control; for matches the control's id, or the label wraps the control.
<nav class="menu" aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Oak dining table	One list item.

Line	What it does
<main><h1>Resize the window</h1><p>Below 700px the menu hides behin...	The unique content of this page; exactly one per page.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
padding: .75rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-decoration: none;	Removes the underline from links.
font-weight: 700;	Thickness of the text.
font-size: 1.6rem;	Size of the text.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
flex-basis: 100%;	The item takes a whole line, pushing the next items down.
display: none;	Removes the element from rendering completely.
.toggle:checked ~ .menu {	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
display: block;	Element starts on a new line and fills the width (used on links and images).
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid rgb(255 255 255 / 25%);	A top border used as an accent or separator.
@media (min-width: 700px) {	Applies from the given width upwards (mobile-first breakpoint).
gap: .5rem;	Space between grid or flex items without extra margins.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
.menu a:hover {	Applies while the pointer is over the element.

Check your work

- Menu opens and closes on mobile
- Burger hidden on desktop
- Label has an aria-label
- No horizontal scrollbar at 320px

Exercises

1. Animate the menu opening with grid-template-rows: 0fr to 1fr.
2. Rebuild with a <button> and aria-expanded using JavaScript.
3. Add a close (X) state to the burger icon.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 1013: Responsive hamburger menu for Byte Repair

Theme: Byte Repair (Nasr City) | Level 3 | Files: index.html, styles.css

Brief

Build a navigation that is a horizontal bar on desktop and collapses behind a hamburger button on phones, toggled by a hidden checkbox and no JavaScript.

Learning goals

- Use the checkbox hack with :checked ~
- Switch layouts with a min-width media query
- Use flex-basis: 100% to wrap an item to its own line

Elements and CSS used

HTML elements	CSS features
header, input type=checkbox, label, nav, ul, li, a	:checked ~, flex-basis: 100%, display: none/block, @media (min-width), flex-wrap

Build guide

1. Write the header: logo, hidden checkbox, label as the burger, nav.
2. Mobile first: hide .menu; show when the checkbox is checked.
3. Make .menu take the full row with flex-basis: 100%.
4. At 700px hide the burger and always show the menu inline.
5. Style links for both modes.

6. Test with keyboard: Space on the focused label toggles the checkbox.

Project 1013: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - Mobile menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="top">
    <a class="logo" href="index.html">Byte Repair</a>
    <input type="checkbox" id="menu-toggle" class="toggle" hidden>
    <label for="menu-toggle" class="burger" aria-label="Open
menu">&#9776;</label>
    <nav class="menu" aria-label="Main">
      <ul>
        <li><a href="index.html">Home</a></li>
    <li><a href="#">Screen replacement</a></li>
    <li><a href="#">Battery swap</a></li>
    <li><a href="#">Laptop cleaning</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main><h1>Resize the window</h1><p>Below 700px the menu hides
behind a button.</p></main>
</body>
</html>
```

Project 1013: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.top { display: flex; align-items: center; justify-content: space-
between; flex-wrap: wrap; padding: .75rem 1rem; background: var(--
brand); color: #fff; }
.logo { color: #fff; text-decoration: none; font-weight: 700; }
.burger { font-size: 1.6rem; cursor: pointer; }
.menu { flex-basis: 100%; display: none; }
.toggle:checked ~ .menu { display: block; }
.menu ul { list-style: none; margin: .5rem 0 0; padding: 0; }
.menu a { display: block; padding: .6rem 0; color: #fff; text-
decoration: none; border-top: 1px solid rgb(255 255 255 / 25%); }
@media (min-width: 700px) {
```

```
  .burger { display: none; }
  .menu { display: block; flex-basis: auto; }
  .menu ul { display: flex; gap: .5rem; margin: 0; }
  .menu a { border: 0; padding: .5rem .8rem; border-radius: 6px; }
  .menu a:hover { background: rgb(255 255 255 / 20%); }
}
main { padding: 2rem 1rem; }
```

Project 1013 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - Mobile menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="top">	Introductory content: logo, title, navigation.
<input type="checkbox" id="menu-toggle" class="toggle" hidden>	Checkbox: on or off.
<label for="menu-toggle" class="burger" aria-label="Open menu">&#97...	Text label for a control; for matches the control's id, or the label wraps the control.
<nav class="menu" aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Screen replacement	One list item.

Line	What it does
<main><h1>Resize the window</h1><p>Below 700px the menu hides behin...	The unique content of this page; exactly one per page.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
padding: .75rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-decoration: none;	Removes the underline from links.
font-weight: 700;	Thickness of the text.
font-size: 1.6rem;	Size of the text.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
flex-basis: 100%;	The item takes a whole line, pushing the next items down.
display: none;	Removes the element from rendering completely.
.toggle:checked ~ .menu {	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
display: block;	Element starts on a new line and fills the width (used on links and images).
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid rgb(255 255 255 / 25%);	A top border used as an accent or separator.
@media (min-width: 700px) {	Applies from the given width upwards (mobile-first breakpoint).
gap: .5rem;	Space between grid or flex items without extra margins.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
.menu a:hover {	Applies while the pointer is over the element.

Check your work

- Menu opens and closes on mobile
- Burger hidden on desktop
- Label has an aria-label
- No horizontal scrollbar at 320px

Exercises

1. Animate the menu opening with grid-template-rows: 0fr to 1fr.
2. Rebuild with a <button> and aria-expanded using JavaScript.
3. Add a close (X) state to the burger icon.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 1014: Responsive hamburger menu for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 3 | Files: index.html, styles.css

Brief

Build a navigation that is a horizontal bar on desktop and collapses behind a hamburger button on phones, toggled by a hidden checkbox and no JavaScript.

Learning goals

- Use the checkbox hack with :checked ~
- Switch layouts with a min-width media query
- Use flex-basis: 100% to wrap an item to its own line

Elements and CSS used

HTML elements	CSS features
header, input type=checkbox, label, nav, ul, li, a	:checked ~, flex-basis: 100%, display: none/block, @media (min-width), flex-wrap

Build guide

1. Write the header: logo, hidden checkbox, label as the burger, nav.
2. Mobile first: hide .menu; show when the checkbox is checked.
3. Make .menu take the full row with flex-basis: 100%.
4. At 700px hide the burger and always show the menu inline.
5. Style links for both modes.

6. Test with keyboard: Space on the focused label toggles the checkbox.

Project 1014: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - Mobile menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="top">
    <a class="logo" href="index.html">Sahara Pet Care</a>
    <input type="checkbox" id="menu-toggle" class="toggle" hidden>
    <label for="menu-toggle" class="burger" aria-label="Open
menu">&#9776;</label>
    <nav class="menu" aria-label="Main">
      <ul>
        <li><a href="index.html">Home</a></li>
    <li><a href="#">Full grooming</a></li>
    <li><a href="#">Day boarding</a></li>
    <li><a href="#">Vaccination</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main><h1>Resize the window</h1><p>Below 700px the menu hides
behind a button.</p></main>
</body>
</html>
```

Project 1014: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.top { display: flex; align-items: center; justify-content: space-
between; flex-wrap: wrap; padding: .75rem 1rem; background: var(--
brand); color: #fff; }
.logo { color: #fff; text-decoration: none; font-weight: 700; }
.burger { font-size: 1.6rem; cursor: pointer; }
.menu { flex-basis: 100%; display: none; }
.toggle:checked ~ .menu { display: block; }
.menu ul { list-style: none; margin: .5rem 0 0; padding: 0; }
.menu a { display: block; padding: .6rem 0; color: #fff; text-
decoration: none; border-top: 1px solid rgb(255 255 255 / 25%); }
@media (min-width: 700px) {
```

```
  .burger { display: none; }
  .menu { display: block; flex-basis: auto; }
  .menu ul { display: flex; gap: .5rem; margin: 0; }
  .menu a { border: 0; padding: .5rem .8rem; border-radius: 6px; }
  .menu a:hover { background: rgb(255 255 255 / 20%); }
}
main { padding: 2rem 1rem; }
```

Project 1014 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - Mobile menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="top">	Introductory content: logo, title, navigation.
<input type="checkbox" id="menu-toggle" class="toggle" hidden>	Checkbox: on or off.
<label for="menu-toggle" class="burger" aria-label="Open menu">&#97...	Text label for a control; for matches the control's id, or the label wraps the control.
<nav class="menu" aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Full grooming	One list item.

Line	What it does
<main><h1>Resize the window</h1><p>Below 700px the menu hides behin...	The unique content of this page; exactly one per page.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
padding: .75rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-decoration: none;	Removes the underline from links.
font-weight: 700;	Thickness of the text.
font-size: 1.6rem;	Size of the text.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
flex-basis: 100%;	The item takes a whole line, pushing the next items down.
display: none;	Removes the element from rendering completely.
.toggle:checked ~ .menu {	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
display: block;	Element starts on a new line and fills the width (used on links and images).
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid rgb(255 255 255 / 25%);	A top border used as an accent or separator.
@media (min-width: 700px) {	Applies from the given width upwards (mobile-first breakpoint).
gap: .5rem;	Space between grid or flex items without extra margins.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
.menu a:hover {	Applies while the pointer is over the element.

Check your work

- Menu opens and closes on mobile
- Burger hidden on desktop
- Label has an aria-label
- No horizontal scrollbar at 320px

Exercises

1. Animate the menu opening with grid-template-rows: 0fr to 1fr.
2. Rebuild with a <button> and aria-expanded using JavaScript.
3. Add a close (X) state to the burger icon.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 1015: Responsive hamburger menu for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 3 | Files: index.html, styles.css

Brief

Build a navigation that is a horizontal bar on desktop and collapses behind a hamburger button on phones, toggled by a hidden checkbox and no JavaScript.

Learning goals

- Use the checkbox hack with :checked ~
- Switch layouts with a min-width media query
- Use flex-basis: 100% to wrap an item to its own line

Elements and CSS used

HTML elements	CSS features
header, input type=checkbox, label, nav, ul, li, a	:checked ~, flex-basis: 100%, display: none/block, @media (min-width), flex-wrap

Build guide

1. Write the header: logo, hidden checkbox, label as the burger, nav.
2. Mobile first: hide .menu; show when the checkbox is checked.
3. Make .menu take the full row with flex-basis: 100%.
4. At 700px hide the burger and always show the menu inline.
5. Style links for both modes.

6. Test with keyboard: Space on the focused label toggles the checkbox.

Project 1015: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - Mobile menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="top">
    <a class="logo" href="index.html">Alexandria Sailing School</a>
    <input type="checkbox" id="menu-toggle" class="toggle" hidden>
    <label for="menu-toggle" class="burger" aria-label="Open
menu">&#9776;</label>
    <nav class="menu" aria-label="Main">
      <ul>
        <li><a href="index.html">Home</a></li>
    <li><a href="#">Taster session</a></li>
    <li><a href="#">Beginner course</a></li>
    <li><a href="#">Racing clinic</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main><h1>Resize the window</h1><p>Below 700px the menu hides
behind a button.</p></main>
</body>
</html>
```

Project 1015: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.top { display: flex; align-items: center; justify-content: space-
between; flex-wrap: wrap; padding: .75rem 1rem; background: var(--
brand); color: #fff; }
.logo { color: #fff; text-decoration: none; font-weight: 700; }
.burger { font-size: 1.6rem; cursor: pointer; }
.menu { flex-basis: 100%; display: none; }
.toggle:checked ~ .menu { display: block; }
.menu ul { list-style: none; margin: .5rem 0 0; padding: 0; }
.menu a { display: block; padding: .6rem 0; color: #fff; text-
decoration: none; border-top: 1px solid rgb(255 255 255 / 25%); }
@media (min-width: 700px) {
```

```
  .burger { display: none; }
  .menu { display: block; flex-basis: auto; }
  .menu ul { display: flex; gap: .5rem; margin: 0; }
  .menu a { border: 0; padding: .5rem .8rem; border-radius: 6px; }
  .menu a:hover { background: rgb(255 255 255 / 20%); }
}
main { padding: 2rem 1rem; }
```

Project 1015 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - Mobile menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="top">	Introductory content: logo, title, navigation.
<input type="checkbox" id="menu-toggle" class="toggle" hidden>	Checkbox: on or off.
<label for="menu-toggle" class="burger" aria-label="Open menu">&#97...	Text label for a control; for matches the control's id, or the label wraps the control.
<nav class="menu" aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Taster session	One list item.

Line	What it does
<main><h1>Resize the window</h1><p>Below 700px the menu hides behin...	The unique content of this page; exactly one per page.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
padding: .75rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-decoration: none;	Removes the underline from links.
font-weight: 700;	Thickness of the text.
font-size: 1.6rem;	Size of the text.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
flex-basis: 100%;	The item takes a whole line, pushing the next items down.
display: none;	Removes the element from rendering completely.
.toggle:checked ~ .menu {	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
display: block;	Element starts on a new line and fills the width (used on links and images).
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid rgb(255 255 255 / 25%);	A top border used as an accent or separator.
@media (min-width: 700px) {	Applies from the given width upwards (mobile-first breakpoint).
gap: .5rem;	Space between grid or flex items without extra margins.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
.menu a:hover {	Applies while the pointer is over the element.

Check your work

- Menu opens and closes on mobile
- Burger hidden on desktop
- Label has an aria-label
- No horizontal scrollbar at 320px

Exercises

1. Animate the menu opening with grid-template-rows: 0fr to 1fr.
2. Rebuild with a <button> and aria-expanded using JavaScript.
3. Add a close (X) state to the burger icon.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 1016: Responsive hamburger menu for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 3 | Files: index.html, styles.css

Brief

Build a navigation that is a horizontal bar on desktop and collapses behind a hamburger button on phones, toggled by a hidden checkbox and no JavaScript.

Learning goals

- Use the checkbox hack with :checked ~
- Switch layouts with a min-width media query
- Use flex-basis: 100% to wrap an item to its own line

Elements and CSS used

HTML elements	CSS features
header, input type=checkbox, label, nav, ul, li, a	:checked ~, flex-basis: 100%, display: none/block, @media (min-width), flex-wrap

Build guide

1. Write the header: logo, hidden checkbox, label as the burger, nav.
2. Mobile first: hide .menu; show when the checkbox is checked.
3. Make .menu take the full row with flex-basis: 100%.
4. At 700px hide the burger and always show the menu inline.
5. Style links for both modes.

6. Test with keyboard: Space on the focused label toggles the checkbox.

Project 1016: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - Mobile menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="top">
    <a class="logo" href="index.html">Habiba Handmade Jewellery</a>
    <input type="checkbox" id="menu-toggle" class="toggle" hidden>
    <label for="menu-toggle" class="burger" aria-label="Open
menu">&#9776;</label>
    <nav class="menu" aria-label="Main">
      <ul>
        <li><a href="index.html">Home</a></li>
    <li><a href="#">Lotus pendant</a></li>
    <li><a href="#">Brass cuff</a></li>
    <li><a href="#">Bead earrings</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main><h1>Resize the window</h1><p>Below 700px the menu hides
behind a button.</p></main>
</body>
</html>
```

Project 1016: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.top { display: flex; align-items: center; justify-content: space-
between; flex-wrap: wrap; padding: .75rem 1rem; background: var(--
brand); color: #fff; }
.logo { color: #fff; text-decoration: none; font-weight: 700; }
.burger { font-size: 1.6rem; cursor: pointer; }
.menu { flex-basis: 100%; display: none; }
.toggle:checked ~ .menu { display: block; }
.menu ul { list-style: none; margin: .5rem 0 0; padding: 0; }
.menu a { display: block; padding: .6rem 0; color: #fff; text-
decoration: none; border-top: 1px solid rgb(255 255 255 / 25%); }
@media (min-width: 700px) {
```

```
  .burger { display: none; }
  .menu { display: block; flex-basis: auto; }
  .menu ul { display: flex; gap: .5rem; margin: 0; }
  .menu a { border: 0; padding: .5rem .8rem; border-radius: 6px; }
  .menu a:hover { background: rgb(255 255 255 / 20%); }
}
main { padding: 2rem 1rem; }
```

Project 1016 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - Mobile menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="top">	Introductory content: logo, title, navigation.
<input type="checkbox" id="menu-toggle" class="toggle" hidden>	Checkbox: on or off.
<label for="menu-toggle" class="burger" aria-label="Open menu">&#97...	Text label for a control; for matches the control's id, or the label wraps the control.
<nav class="menu" aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.

Line	What it does
Lotus pendant	One list item.
<main><h1>Resize the window</h1><p>Below 700px the menu hides behin...	The unique content of this page; exactly one per page.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.

Declaration	What it does
padding: .75rem 1rem;	Space inside the element between its border and content.
background: var(--brand);	Background colour or image.
text-decoration: none;	Removes the underline from links.
font-weight: 700;	Thickness of the text.
font-size: 1.6rem;	Size of the text.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
flex-basis: 100%;	The item takes a whole line, pushing the next items down.
display: none;	Removes the element from rendering completely.
.toggle:checked ~ .menu {	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
display: block;	Element starts on a new line and fills the width (used on links and images).
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid rgb(255 255 255 / 25%);	A top border used as an accent or separator.
@media (min-width: 700px) {	Applies from the given width upwards (mobile-first breakpoint).
gap: .5rem;	Space between grid or flex items without extra margins.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
.menu a:hover {	Applies while the pointer is over the element.

Check your work

- Menu opens and closes on mobile
- Burger hidden on desktop
- Label has an aria-label
- No horizontal scrollbar at 320px

Exercises

1. Animate the menu opening with grid-template-rows: 0fr to 1fr.
2. Rebuild with a <button> and aria-expanded using JavaScript.
3. Add a close (X) state to the burger icon.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 1017: Responsive hamburger menu for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 3 | Files: index.html, styles.css

Brief

Build a navigation that is a horizontal bar on desktop and collapses behind a hamburger button on phones, toggled by a hidden checkbox and no JavaScript.

Learning goals

- Use the checkbox hack with :checked ~
- Switch layouts with a min-width media query
- Use flex-basis: 100% to wrap an item to its own line

Elements and CSS used

HTML elements	CSS features
header, input type=checkbox, label, nav, ul, li, a	:checked ~, flex-basis: 100%, display: none/block, @media (min-width), flex-wrap

Build guide

1. Write the header: logo, hidden checkbox, label as the burger, nav.
2. Mobile first: hide .menu; show when the checkbox is checked.
3. Make .menu take the full row with flex-basis: 100%.
4. At 700px hide the burger and always show the menu inline.
5. Style links for both modes.

6. Test with keyboard: Space on the focused label toggles the checkbox.

Project 1017: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - Mobile menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="top">
    <a class="logo" href="index.html">Fayoum Pottery Studio</a>
    <input type="checkbox" id="menu-toggle" class="toggle" hidden>
    <label for="menu-toggle" class="burger" aria-label="Open
menu">&#9776;</label>
    <nav class="menu" aria-label="Main">
      <ul>
        <li><a href="index.html">Home</a></li>
    <li><a href="#">Intro to the wheel</a></li>
    <li><a href="#">Glazing day</a></li>
    <li><a href="#">Kids clay class</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main><h1>Resize the window</h1><p>Below 700px the menu hides
behind a button.</p></main>
</body>
</html>
```

Project 1017: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.top { display: flex; align-items: center; justify-content: space-
between; flex-wrap: wrap; padding: .75rem 1rem; background: var(--
brand); color: #fff; }
.logo { color: #fff; text-decoration: none; font-weight: 700; }
.burger { font-size: 1.6rem; cursor: pointer; }
.menu { flex-basis: 100%; display: none; }
.toggle:checked ~ .menu { display: block; }
.menu ul { list-style: none; margin: .5rem 0 0; padding: 0; }
.menu a { display: block; padding: .6rem 0; color: #fff; text-
decoration: none; border-top: 1px solid rgb(255 255 255 / 25%); }
@media (min-width: 700px) {
```

```
  .burger { display: none; }
  .menu { display: block; flex-basis: auto; }
  .menu ul { display: flex; gap: .5rem; margin: 0; }
  .menu a { border: 0; padding: .5rem .8rem; border-radius: 6px; }
  .menu a:hover { background: rgb(255 255 255 / 20%); }
}
main { padding: 2rem 1rem; }
```

Project 1017 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - Mobile menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="top">	Introductory content: logo, title, navigation.
<input type="checkbox" id="menu-toggle" class="toggle" hidden>	Checkbox: on or off.
<label for="menu-toggle" class="burger" aria-label="Open menu">&#97...	Text label for a control; for matches the control's id, or the label wraps the control.
<nav class="menu" aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Intro to the wheel	One list item.

Line	What it does
<main><h1>Resize the window</h1><p>Below 700px the menu hides behin...	The unique content of this page; exactly one per page.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
padding: .75rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-decoration: none;	Removes the underline from links.
font-weight: 700;	Thickness of the text.
font-size: 1.6rem;	Size of the text.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
flex-basis: 100%;	The item takes a whole line, pushing the next items down.
display: none;	Removes the element from rendering completely.
.toggle:checked ~ .menu {	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
display: block;	Element starts on a new line and fills the width (used on links and images).
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid rgb(255 255 255 / 25%);	A top border used as an accent or separator.
@media (min-width: 700px) {	Applies from the given width upwards (mobile-first breakpoint).
gap: .5rem;	Space between grid or flex items without extra margins.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
.menu a:hover {	Applies while the pointer is over the element.

Check your work

- Menu opens and closes on mobile
- Burger hidden on desktop
- Label has an aria-label
- No horizontal scrollbar at 320px

Exercises

1. Animate the menu opening with grid-template-rows: 0fr to 1fr.
2. Rebuild with a <button> and aria-expanded using JavaScript.
3. Add a close (X) state to the burger icon.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 1018: Responsive hamburger menu for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 3 | Files: index.html, styles.css

Brief

Build a navigation that is a horizontal bar on desktop and collapses behind a hamburger button on phones, toggled by a hidden checkbox and no JavaScript.

Learning goals

- Use the checkbox hack with :checked ~
- Switch layouts with a min-width media query
- Use flex-basis: 100% to wrap an item to its own line

Elements and CSS used

HTML elements	CSS features
header, input type=checkbox, label, nav, ul, li, a	:checked ~, flex-basis: 100%, display: none/block, @media (min-width), flex-wrap

Build guide

1. Write the header: logo, hidden checkbox, label as the burger, nav.
2. Mobile first: hide .menu; show when the checkbox is checked.
3. Make .menu take the full row with flex-basis: 100%.
4. At 700px hide the burger and always show the menu inline.
5. Style links for both modes.

6. Test with keyboard: Space on the focused label toggles the checkbox.

Project 1018: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - Mobile menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="top">
    <a class="logo" href="index.html">Cleopatra Beauty Salon</a>
    <input type="checkbox" id="menu-toggle" class="toggle" hidden>
    <label for="menu-toggle" class="burger" aria-label="Open
menu">&#9776;</label>
    <nav class="menu" aria-label="Main">
      <ul>
        <li><a href="index.html">Home</a></li>
    <li><a href="#">Haircut and blow-dry</a></li>
    <li><a href="#">Manicure</a></li>
    <li><a href="#">Facial</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main><h1>Resize the window</h1><p>Below 700px the menu hides
behind a button.</p></main>
</body>
</html>
```

Project 1018: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.top { display: flex; align-items: center; justify-content: space-
between; flex-wrap: wrap; padding: .75rem 1rem; background: var(--
brand); color: #fff; }
.logo { color: #fff; text-decoration: none; font-weight: 700; }
.burger { font-size: 1.6rem; cursor: pointer; }
.menu { flex-basis: 100%; display: none; }
.toggle:checked ~ .menu { display: block; }
.menu ul { list-style: none; margin: .5rem 0 0; padding: 0; }
.menu a { display: block; padding: .6rem 0; color: #fff; text-
decoration: none; border-top: 1px solid rgb(255 255 255 / 25%); }
@media (min-width: 700px) {
```

```
  .burger { display: none; }
  .menu { display: block; flex-basis: auto; }
  .menu ul { display: flex; gap: .5rem; margin: 0; }
  .menu a { border: 0; padding: .5rem .8rem; border-radius: 6px; }
  .menu a:hover { background: rgb(255 255 255 / 20%); }
}
main { padding: 2rem 1rem; }
```

Project 1018 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - Mobile menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="top">	Introductory content: logo, title, navigation.
<input type="checkbox" id="menu-toggle" class="toggle" hidden>	Checkbox: on or off.
<label for="menu-toggle" class="burger" aria-label="Open menu">&#97...	Text label for a control; for matches the control's id, or the label wraps the control.
<nav class="menu" aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Haircut and blow-dry	One list item.

Line	What it does
<main><h1>Resize the window</h1><p>Below 700px the menu hides behin...	The unique content of this page; exactly one per page.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
padding: .75rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-decoration: none;	Removes the underline from links.
font-weight: 700;	Thickness of the text.
font-size: 1.6rem;	Size of the text.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
flex-basis: 100%;	The item takes a whole line, pushing the next items down.
display: none;	Removes the element from rendering completely.
.toggle:checked ~ .menu {	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
display: block;	Element starts on a new line and fills the width (used on links and images).
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid rgb(255 255 255 / 25%);	A top border used as an accent or separator.
@media (min-width: 700px) {	Applies from the given width upwards (mobile-first breakpoint).
gap: .5rem;	Space between grid or flex items without extra margins.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
.menu a:hover {	Applies while the pointer is over the element.

Check your work

- Menu opens and closes on mobile
- Burger hidden on desktop
- Label has an aria-label
- No horizontal scrollbar at 320px

Exercises

1. Animate the menu opening with grid-template-rows: 0fr to 1fr.
2. Rebuild with a <button> and aria-expanded using JavaScript.
3. Add a close (X) state to the burger icon.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 1019: Responsive hamburger menu for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 3 | Files: index.html, styles.css

Brief

Build a navigation that is a horizontal bar on desktop and collapses behind a hamburger button on phones, toggled by a hidden checkbox and no JavaScript.

Learning goals

- Use the checkbox hack with :checked ~
- Switch layouts with a min-width media query
- Use flex-basis: 100% to wrap an item to its own line

Elements and CSS used

HTML elements	CSS features
header, input type=checkbox, label, nav, ul, li, a	:checked ~, flex-basis: 100%, display: none/block, @media (min-width), flex-wrap

Build guide

1. Write the header: logo, hidden checkbox, label as the burger, nav.
2. Mobile first: hide .menu; show when the checkbox is checked.
3. Make .menu take the full row with flex-basis: 100%.
4. At 700px hide the burger and always show the menu inline.
5. Style links for both modes.

6. Test with keyboard: Space on the focused label toggles the checkbox.

Project 1019: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - Mobile menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="top">
    <a class="logo" href="index.html">Suez Auto Service</a>
    <input type="checkbox" id="menu-toggle" class="toggle" hidden>
    <label for="menu-toggle" class="burger" aria-label="Open
menu">&#9776;</label>
    <nav class="menu" aria-label="Main">
      <ul>
        <li><a href="index.html">Home</a></li>
    <li><a href="#">Oil change</a></li>
    <li><a href="#">Brake pads</a></li>
    <li><a href="#">Air conditioning</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main><h1>Resize the window</h1><p>Below 700px the menu hides
behind a button.</p></main>
</body>
</html>
```

Project 1019: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.top { display: flex; align-items: center; justify-content: space-
between; flex-wrap: wrap; padding: .75rem 1rem; background: var(--
brand); color: #fff; }
.logo { color: #fff; text-decoration: none; font-weight: 700; }
.burger { font-size: 1.6rem; cursor: pointer; }
.menu { flex-basis: 100%; display: none; }
.toggle:checked ~ .menu { display: block; }
.menu ul { list-style: none; margin: .5rem 0 0; padding: 0; }
.menu a { display: block; padding: .6rem 0; color: #fff; text-
decoration: none; border-top: 1px solid rgb(255 255 255 / 25%); }
@media (min-width: 700px) {
```

```
  .burger { display: none; }
  .menu { display: block; flex-basis: auto; }
  .menu ul { display: flex; gap: .5rem; margin: 0; }
  .menu a { border: 0; padding: .5rem .8rem; border-radius: 6px; }
  .menu a:hover { background: rgb(255 255 255 / 20%); }
}
main { padding: 2rem 1rem; }
```

Project 1019 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - Mobile menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="top">	Introductory content: logo, title, navigation.
<input type="checkbox" id="menu-toggle" class="toggle" hidden>	Checkbox: on or off.
<label for="menu-toggle" class="burger" aria-label="Open menu">&#97...	Text label for a control; for matches the control's id, or the label wraps the control.
<nav class="menu" aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Oil change	One list item.

Line	What it does
<main><h1>Resize the window</h1><p>Below 700px the menu hides behin...	The unique content of this page; exactly one per page.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
padding: .75rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-decoration: none;	Removes the underline from links.
font-weight: 700;	Thickness of the text.
font-size: 1.6rem;	Size of the text.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
flex-basis: 100%;	The item takes a whole line, pushing the next items down.
display: none;	Removes the element from rendering completely.
.toggle:checked ~ .menu {	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
display: block;	Element starts on a new line and fills the width (used on links and images).
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid rgb(255 255 255 / 25%);	A top border used as an accent or separator.
@media (min-width: 700px) {	Applies from the given width upwards (mobile-first breakpoint).
gap: .5rem;	Space between grid or flex items without extra margins.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
.menu a:hover {	Applies while the pointer is over the element.

Check your work

- Menu opens and closes on mobile
- Burger hidden on desktop
- Label has an aria-label
- No horizontal scrollbar at 320px

Exercises

1. Animate the menu opening with grid-template-rows: 0fr to 1fr.
2. Rebuild with a <button> and aria-expanded using JavaScript.
3. Add a close (X) state to the burger icon.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 1020: Responsive hamburger menu for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 3 | Files: index.html, styles.css

Brief

Build a navigation that is a horizontal bar on desktop and collapses behind a hamburger button on phones, toggled by a hidden checkbox and no JavaScript.

Learning goals

- Use the checkbox hack with :checked ~
- Switch layouts with a min-width media query
- Use flex-basis: 100% to wrap an item to its own line

Elements and CSS used

HTML elements	CSS features
header, input type=checkbox, label, nav, ul, li, a	:checked ~, flex-basis: 100%, display: none/block, @media (min-width), flex-wrap

Build guide

1. Write the header: logo, hidden checkbox, label as the burger, nav.
2. Mobile first: hide .menu; show when the checkbox is checked.
3. Make .menu take the full row with flex-basis: 100%.
4. At 700px hide the burger and always show the menu inline.
5. Style links for both modes.

6. Test with keyboard: Space on the focused label toggles the checkbox.

Project 1020: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - Mobile menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="top">
    <a class="logo" href="index.html">Luxor Music Academy</a>
    <input type="checkbox" id="menu-toggle" class="toggle" hidden>
    <label for="menu-toggle" class="burger" aria-label="Open
menu">&#9776;</label>
    <nav class="menu" aria-label="Main">
      <ul>
        <li><a href="index.html">Home</a></li>
    <li><a href="#">Oud for beginners</a></li>
    <li><a href="#">Piano grade 1</a></li>
    <li><a href="#">Guitar chords</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main><h1>Resize the window</h1><p>Below 700px the menu hides
behind a button.</p></main>
</body>
</html>
```

Project 1020: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.top { display: flex; align-items: center; justify-content: space-
between; flex-wrap: wrap; padding: .75rem 1rem; background: var(--
brand); color: #fff; }
.logo { color: #fff; text-decoration: none; font-weight: 700; }
.burger { font-size: 1.6rem; cursor: pointer; }
.menu { flex-basis: 100%; display: none; }
.toggle:checked ~ .menu { display: block; }
.menu ul { list-style: none; margin: .5rem 0 0; padding: 0; }
.menu a { display: block; padding: .6rem 0; color: #fff; text-
decoration: none; border-top: 1px solid rgb(255 255 255 / 25%); }
@media (min-width: 700px) {
```

```
  .burger { display: none; }
  .menu { display: block; flex-basis: auto; }
  .menu ul { display: flex; gap: .5rem; margin: 0; }
  .menu a { border: 0; padding: .5rem .8rem; border-radius: 6px; }
  .menu a:hover { background: rgb(255 255 255 / 20%); }
}
main { padding: 2rem 1rem; }
```

Project 1020 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - Mobile menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="top">	Introductory content: logo, title, navigation.
<input type="checkbox" id="menu-toggle" class="toggle" hidden>	Checkbox: on or off.
<label for="menu-toggle" class="burger" aria-label="Open menu">&#97...	Text label for a control; for matches the control's id, or the label wraps the control.
<nav class="menu" aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Oud for beginners	One list item.

Line	What it does
<main><h1>Resize the window</h1><p>Below 700px the menu hides behin...	The unique content of this page; exactly one per page.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
padding: .75rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-decoration: none;	Removes the underline from links.
font-weight: 700;	Thickness of the text.
font-size: 1.6rem;	Size of the text.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
flex-basis: 100%;	The item takes a whole line, pushing the next items down.
display: none;	Removes the element from rendering completely.
.toggle:checked ~ .menu {	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
display: block;	Element starts on a new line and fills the width (used on links and images).
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid rgb(255 255 255 / 25%);	A top border used as an accent or separator.
@media (min-width: 700px) {	Applies from the given width upwards (mobile-first breakpoint).
gap: .5rem;	Space between grid or flex items without extra margins.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
.menu a:hover {	Applies while the pointer is over the element.

Check your work

- Menu opens and closes on mobile
- Burger hidden on desktop
- Label has an aria-label
- No horizontal scrollbar at 320px

Exercises

1. Animate the menu opening with grid-template-rows: 0fr to 1fr.
2. Rebuild with a <button> and aria-expanded using JavaScript.
3. Add a close (X) state to the burger icon.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 1021: Responsive hamburger menu for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 3 | Files: index.html, styles.css

Brief

Build a navigation that is a horizontal bar on desktop and collapses behind a hamburger button on phones, toggled by a hidden checkbox and no JavaScript.

Learning goals

- Use the checkbox hack with :checked ~
- Switch layouts with a min-width media query
- Use flex-basis: 100% to wrap an item to its own line

Elements and CSS used

HTML elements	CSS features
header, input type=checkbox, label, nav, ul, li, a	:checked ~, flex-basis: 100%, display: none/block, @media (min-width), flex-wrap

Build guide

1. Write the header: logo, hidden checkbox, label as the burger, nav.
2. Mobile first: hide .menu; show when the checkbox is checked.
3. Make .menu take the full row with flex-basis: 100%.
4. At 700px hide the burger and always show the menu inline.
5. Style links for both modes.

6. Test with keyboard: Space on the focused label toggles the checkbox.

Project 1021: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - Mobile menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="top">
    <a class="logo" href="index.html">Port Said Seafood</a>
    <input type="checkbox" id="menu-toggle" class="toggle" hidden>
    <label for="menu-toggle" class="burger" aria-label="Open
menu">&#9776;</label>
    <nav class="menu" aria-label="Main">
      <ul>
        <li><a href="index.html">Home</a></li>
    <li><a href="#">Grilled sea bass</a></li>
    <li><a href="#">Shrimp tagine</a></li>
    <li><a href="#">Calamari</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main><h1>Resize the window</h1><p>Below 700px the menu hides
behind a button.</p></main>
</body>
</html>
```

Project 1021: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.top { display: flex; align-items: center; justify-content: space-
between; flex-wrap: wrap; padding: .75rem 1rem; background: var(--
brand); color: #fff; }
.logo { color: #fff; text-decoration: none; font-weight: 700; }
.burger { font-size: 1.6rem; cursor: pointer; }
.menu { flex-basis: 100%; display: none; }
.toggle:checked ~ .menu { display: block; }
.menu ul { list-style: none; margin: .5rem 0 0; padding: 0; }
.menu a { display: block; padding: .6rem 0; color: #fff; text-
decoration: none; border-top: 1px solid rgb(255 255 255 / 25%); }
@media (min-width: 700px) {
```

```
  .burger { display: none; }
  .menu { display: block; flex-basis: auto; }
  .menu ul { display: flex; gap: .5rem; margin: 0; }
  .menu a { border: 0; padding: .5rem .8rem; border-radius: 6px; }
  .menu a:hover { background: rgb(255 255 255 / 20%); }
}
main { padding: 2rem 1rem; }
```

Project 1021 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - Mobile menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="top">	Introductory content: logo, title, navigation.
<input type="checkbox" id="menu-toggle" class="toggle" hidden>	Checkbox: on or off.
<label for="menu-toggle" class="burger" aria-label="Open menu">&#97...	Text label for a control; for matches the control's id, or the label wraps the control.
<nav class="menu" aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Grilled sea bass	One list item.

Line	What it does
<main><h1>Resize the window</h1><p>Below 700px the menu hides behin...	The unique content of this page; exactly one per page.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
padding: .75rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-decoration: none;	Removes the underline from links.
font-weight: 700;	Thickness of the text.
font-size: 1.6rem;	Size of the text.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
flex-basis: 100%;	The item takes a whole line, pushing the next items down.
display: none;	Removes the element from rendering completely.
.toggle:checked ~ .menu {	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
display: block;	Element starts on a new line and fills the width (used on links and images).
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid rgb(255 255 255 / 25%);	A top border used as an accent or separator.
@media (min-width: 700px) {	Applies from the given width upwards (mobile-first breakpoint).
gap: .5rem;	Space between grid or flex items without extra margins.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
.menu a:hover {	Applies while the pointer is over the element.

Check your work

- Menu opens and closes on mobile
- Burger hidden on desktop
- Label has an aria-label
- No horizontal scrollbar at 320px

Exercises

1. Animate the menu opening with grid-template-rows: 0fr to 1fr.
2. Rebuild with a <button> and aria-expanded using JavaScript.
3. Add a close (X) state to the burger icon.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 1022: Responsive hamburger menu for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 3 | Files: index.html, styles.css

Brief

Build a navigation that is a horizontal bar on desktop and collapses behind a hamburger button on phones, toggled by a hidden checkbox and no JavaScript.

Learning goals

- Use the checkbox hack with :checked ~
- Switch layouts with a min-width media query
- Use flex-basis: 100% to wrap an item to its own line

Elements and CSS used

HTML elements	CSS features
header, input type=checkbox, label, nav, ul, li, a	:checked ~, flex-basis: 100%, display: none/block, @media (min-width), flex-wrap

Build guide

1. Write the header: logo, hidden checkbox, label as the burger, nav.
2. Mobile first: hide .menu; show when the checkbox is checked.
3. Make .menu take the full row with flex-basis: 100%.
4. At 700px hide the burger and always show the menu inline.
5. Style links for both modes.

6. Test with keyboard: Space on the focused label toggles the checkbox.

Project 1022: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - Mobile menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="top">
    <a class="logo" href="index.html">Delta Kids Library</a>
    <input type="checkbox" id="menu-toggle" class="toggle" hidden>
    <label for="menu-toggle" class="burger" aria-label="Open
menu">&#9776;</label>
    <nav class="menu" aria-label="Main">
      <ul>
        <li><a href="index.html">Home</a></li>
    <li><a href="#">Story hour</a></li>
    <li><a href="#">Reading club</a></li>
    <li><a href="#">Homework help</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main><h1>Resize the window</h1><p>Below 700px the menu hides
behind a button.</p></main>
</body>
</html>
```

Project 1022: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.top { display: flex; align-items: center; justify-content: space-
between; flex-wrap: wrap; padding: .75rem 1rem; background: var(--
brand); color: #fff; }
.logo { color: #fff; text-decoration: none; font-weight: 700; }
.burger { font-size: 1.6rem; cursor: pointer; }
.menu { flex-basis: 100%; display: none; }
.toggle:checked ~ .menu { display: block; }
.menu ul { list-style: none; margin: .5rem 0 0; padding: 0; }
.menu a { display: block; padding: .6rem 0; color: #fff; text-
decoration: none; border-top: 1px solid rgb(255 255 255 / 25%); }
@media (min-width: 700px) {
```

```
  .burger { display: none; }
  .menu { display: block; flex-basis: auto; }
  .menu ul { display: flex; gap: .5rem; margin: 0; }
  .menu a { border: 0; padding: .5rem .8rem; border-radius: 6px; }
  .menu a:hover { background: rgb(255 255 255 / 20%); }
}
main { padding: 2rem 1rem; }
```

Project 1022 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - Mobile menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="top">	Introductory content: logo, title, navigation.
<input type="checkbox" id="menu-toggle" class="toggle" hidden>	Checkbox: on or off.
<label for="menu-toggle" class="burger" aria-label="Open menu">&#97...	Text label for a control; for matches the control's id, or the label wraps the control.
<nav class="menu" aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Story hour	One list item.

Line	What it does
<main><h1>Resize the window</h1><p>Below 700px the menu hides behin...	The unique content of this page; exactly one per page.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
padding: .75rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-decoration: none;	Removes the underline from links.
font-weight: 700;	Thickness of the text.
font-size: 1.6rem;	Size of the text.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
flex-basis: 100%;	The item takes a whole line, pushing the next items down.
display: none;	Removes the element from rendering completely.
.toggle:checked ~ .menu {	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
display: block;	Element starts on a new line and fills the width (used on links and images).
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid rgb(255 255 255 / 25%);	A top border used as an accent or separator.
@media (min-width: 700px) {	Applies from the given width upwards (mobile-first breakpoint).
gap: .5rem;	Space between grid or flex items without extra margins.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
.menu a:hover {	Applies while the pointer is over the element.

Check your work

- Menu opens and closes on mobile
- Burger hidden on desktop
- Label has an aria-label
- No horizontal scrollbar at 320px

Exercises

1. Animate the menu opening with grid-template-rows: 0fr to 1fr.
2. Rebuild with a <button> and aria-expanded using JavaScript.
3. Add a close (X) state to the burger icon.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 1023: Responsive hamburger menu for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 3 | Files: index.html, styles.css

Brief

Build a navigation that is a horizontal bar on desktop and collapses behind a hamburger button on phones, toggled by a hidden checkbox and no JavaScript.

Learning goals

- Use the checkbox hack with :checked ~
- Switch layouts with a min-width media query
- Use flex-basis: 100% to wrap an item to its own line

Elements and CSS used

HTML elements	CSS features
header, input type=checkbox, label, nav, ul, li, a	:checked ~, flex-basis: 100%, display: none/block, @media (min-width), flex-wrap

Build guide

1. Write the header: logo, hidden checkbox, label as the burger, nav.
2. Mobile first: hide .menu; show when the checkbox is checked.
3. Make .menu take the full row with flex-basis: 100%.
4. At 700px hide the burger and always show the menu inline.
5. Style links for both modes.

6. Test with keyboard: Space on the focused label toggles the checkbox.

Project 1023: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - Mobile menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="top">
    <a class="logo" href="index.html">Nubian Guest House</a>
    <input type="checkbox" id="menu-toggle" class="toggle" hidden>
    <label for="menu-toggle" class="burger" aria-label="Open
menu">&#9776;</label>
    <nav class="menu" aria-label="Main">
      <ul>
        <li><a href="index.html">Home</a></li>
    <li><a href="#">Garden room</a></li>
    <li><a href="#">Nile view suite</a></li>
    <li><a href="#">Family room</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main><h1>Resize the window</h1><p>Below 700px the menu hides
behind a button.</p></main>
</body>
</html>
```

Project 1023: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.top { display: flex; align-items: center; justify-content: space-
between; flex-wrap: wrap; padding: .75rem 1rem; background: var(--
brand); color: #fff; }
.logo { color: #fff; text-decoration: none; font-weight: 700; }
.burger { font-size: 1.6rem; cursor: pointer; }
.menu { flex-basis: 100%; display: none; }
.toggle:checked ~ .menu { display: block; }
.menu ul { list-style: none; margin: .5rem 0 0; padding: 0; }
.menu a { display: block; padding: .6rem 0; color: #fff; text-
decoration: none; border-top: 1px solid rgb(255 255 255 / 25%); }
@media (min-width: 700px) {
```

```
  .burger { display: none; }
  .menu { display: block; flex-basis: auto; }
  .menu ul { display: flex; gap: .5rem; margin: 0; }
  .menu a { border: 0; padding: .5rem .8rem; border-radius: 6px; }
  .menu a:hover { background: rgb(255 255 255 / 20%); }
}
main { padding: 2rem 1rem; }
```

Project 1023 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - Mobile menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="top">	Introductory content: logo, title, navigation.
<input type="checkbox" id="menu-toggle" class="toggle" hidden>	Checkbox: on or off.
<label for="menu-toggle" class="burger" aria-label="Open menu">&#97...	Text label for a control; for matches the control's id, or the label wraps the control.
<nav class="menu" aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
Garden room	One list item.

Line	What it does
<main><h1>Resize the window</h1><p>Below 700px the menu hides behin...	The unique content of this page; exactly one per page.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
padding: .75rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-decoration: none;	Removes the underline from links.
font-weight: 700;	Thickness of the text.
font-size: 1.6rem;	Size of the text.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
flex-basis: 100%;	The item takes a whole line, pushing the next items down.
display: none;	Removes the element from rendering completely.
.toggle:checked ~ .menu {	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
display: block;	Element starts on a new line and fills the width (used on links and images).
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid rgb(255 255 255 / 25%);	A top border used as an accent or separator.
@media (min-width: 700px) {	Applies from the given width upwards (mobile-first breakpoint).
gap: .5rem;	Space between grid or flex items without extra margins.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
.menu a:hover {	Applies while the pointer is over the element.

Check your work

- Menu opens and closes on mobile
- Burger hidden on desktop
- Label has an aria-label
- No horizontal scrollbar at 320px

Exercises

1. Animate the menu opening with grid-template-rows: 0fr to 1fr.
2. Rebuild with a <button> and aria-expanded using JavaScript.
3. Add a close (X) state to the burger icon.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 1024: Responsive hamburger menu for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 3 | Files: index.html, styles.css

Brief

Build a navigation that is a horizontal bar on desktop and collapses behind a hamburger button on phones, toggled by a hidden checkbox and no JavaScript.

Learning goals

- Use the checkbox hack with :checked ~
- Switch layouts with a min-width media query
- Use flex-basis: 100% to wrap an item to its own line

Elements and CSS used

HTML elements	CSS features
header, input type=checkbox, label, nav, ul, li, a	:checked ~, flex-basis: 100%, display: none/block, @media (min-width), flex-wrap

Build guide

1. Write the header: logo, hidden checkbox, label as the burger, nav.
2. Mobile first: hide .menu; show when the checkbox is checked.
3. Make .menu take the full row with flex-basis: 100%.
4. At 700px hide the burger and always show the menu inline.
5. Style links for both modes.

6. Test with keyboard: Space on the focused label toggles the checkbox.

Project 1024: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - Mobile menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="top">
    <a class="logo" href="index.html">Ismailia Cycling Store</a>
    <input type="checkbox" id="menu-toggle" class="toggle" hidden>
    <label for="menu-toggle" class="burger" aria-label="Open
menu">&#9776;</label>
    <nav class="menu" aria-label="Main">
      <ul>
        <li><a href="index.html">Home</a></li>
    <li><a href="#">City bike</a></li>
    <li><a href="#">Mountain bike</a></li>
    <li><a href="#">Kids bike</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main><h1>Resize the window</h1><p>Below 700px the menu hides
behind a button.</p></main>
</body>
</html>
```

Project 1024: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.top { display: flex; align-items: center; justify-content: space-
between; flex-wrap: wrap; padding: .75rem 1rem; background: var(--
brand); color: #fff; }
.logo { color: #fff; text-decoration: none; font-weight: 700; }
.burger { font-size: 1.6rem; cursor: pointer; }
.menu { flex-basis: 100%; display: none; }
.toggle:checked ~ .menu { display: block; }
.menu ul { list-style: none; margin: .5rem 0 0; padding: 0; }
.menu a { display: block; padding: .6rem 0; color: #fff; text-
decoration: none; border-top: 1px solid rgb(255 255 255 / 25%); }
@media (min-width: 700px) {
```

```
  .burger { display: none; }
  .menu { display: block; flex-basis: auto; }
  .menu ul { display: flex; gap: .5rem; margin: 0; }
  .menu a { border: 0; padding: .5rem .8rem; border-radius: 6px; }
  .menu a:hover { background: rgb(255 255 255 / 20%); }
}
main { padding: 2rem 1rem; }
```

Project 1024 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - Mobile menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="top">	Introductory content: logo, title, navigation.
<input type="checkbox" id="menu-toggle" class="toggle" hidden>	Checkbox: on or off.
<label for="menu-toggle" class="burger" aria-label="Open menu">&#97...	Text label for a control; for matches the control's id, or the label wraps the control.
<nav class="menu" aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
City bike	One list item.

Line	What it does
<main><h1>Resize the window</h1><p>Below 700px the menu hides behin...	The unique content of this page; exactly one per page.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
padding: .75rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-decoration: none;	Removes the underline from links.
font-weight: 700;	Thickness of the text.
font-size: 1.6rem;	Size of the text.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
flex-basis: 100%;	The item takes a whole line, pushing the next items down.
display: none;	Removes the element from rendering completely.
.toggle:checked ~ .menu {	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
display: block;	Element starts on a new line and fills the width (used on links and images).
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid rgb(255 255 255 / 25%);	A top border used as an accent or separator.
@media (min-width: 700px) {	Applies from the given width upwards (mobile-first breakpoint).
gap: .5rem;	Space between grid or flex items without extra margins.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
.menu a:hover {	Applies while the pointer is over the element.

Check your work

- Menu opens and closes on mobile
- Burger hidden on desktop
- Label has an aria-label
- No horizontal scrollbar at 320px

Exercises

1. Animate the menu opening with grid-template-rows: 0fr to 1fr.
2. Rebuild with a <button> and aria-expanded using JavaScript.
3. Add a close (X) state to the burger icon.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 1025: Responsive hamburger menu for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 3 | Files: index.html, styles.css

Brief

Build a navigation that is a horizontal bar on desktop and collapses behind a hamburger button on phones, toggled by a hidden checkbox and no JavaScript.

Learning goals

- Use the checkbox hack with :checked ~
- Switch layouts with a min-width media query
- Use flex-basis: 100% to wrap an item to its own line

Elements and CSS used

HTML elements	CSS features
header, input type=checkbox, label, nav, ul, li, a	:checked ~, flex-basis: 100%, display: none/block, @media (min-width), flex-wrap

Build guide

1. Write the header: logo, hidden checkbox, label as the burger, nav.
2. Mobile first: hide .menu; show when the checkbox is checked.
3. Make .menu take the full row with flex-basis: 100%.
4. At 700px hide the burger and always show the menu inline.
5. Style links for both modes.

6. Test with keyboard: Space on the focused label toggles the checkbox.

Project 1025: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - Mobile menu</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <header class="top">
    <a class="logo" href="index.html">Minya Coding Club</a>
    <input type="checkbox" id="menu-toggle" class="toggle" hidden>
    <label for="menu-toggle" class="burger" aria-label="Open
menu">&#9776;</label>
    <nav class="menu" aria-label="Main">
      <ul>
        <li><a href="index.html">Home</a></li>
    <li><a href="#">HTML weekend</a></li>
    <li><a href="#">CSS art</a></li>
    <li><a href="#">Scratch games</a></li>
        <li><a href="contact.html">Contact</a></li>
      </ul>
    </nav>
  </header>
  <main><h1>Resize the window</h1><p>Below 700px the menu hides
behind a button.</p></main>
</body>
</html>
```

Project 1025: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.top { display: flex; align-items: center; justify-content: space-
between; flex-wrap: wrap; padding: .75rem 1rem; background: var(--
brand); color: #fff; }
.logo { color: #fff; text-decoration: none; font-weight: 700; }
.burger { font-size: 1.6rem; cursor: pointer; }
.menu { flex-basis: 100%; display: none; }
.toggle:checked ~ .menu { display: block; }
.menu ul { list-style: none; margin: .5rem 0 0; padding: 0; }
.menu a { display: block; padding: .6rem 0; color: #fff; text-
decoration: none; border-top: 1px solid rgb(255 255 255 / 25%); }
@media (min-width: 700px) {
```

```
  .burger { display: none; }
  .menu { display: block; flex-basis: auto; }
  .menu ul { display: flex; gap: .5rem; margin: 0; }
  .menu a { border: 0; padding: .5rem .8rem; border-radius: 6px; }
  .menu a:hover { background: rgb(255 255 255 / 20%); }
}
main { padding: 2rem 1rem; }
```

Project 1025 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - Mobile menu</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="top">	Introductory content: logo, title, navigation.
<input type="checkbox" id="menu-toggle" class="toggle" hidden>	Checkbox: on or off.
<label for="menu-toggle" class="burger" aria-label="Open menu">&#97...	Text label for a control; for matches the control's id, or the label wraps the control.
<nav class="menu" aria-label="Main">	A block of navigation links; aria-label names it for screen readers.
	Unordered (bulleted) list.
Home	A hyperlink; href gives the destination.
HTML weekend	One list item.

Line	What it does
<main><h1>Resize the window</h1><p>Below 700px the menu hides behin...	The unique content of this page; exactly one per page.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
display: flex;	Turns the element into a flex container (one-dimensional layout).
align-items: center;	Centres items on the cross axis.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
padding: .75rem 1rem;	Space inside the element between its border and content.

Declaration	What it does
background: var(--brand);	Background colour or image.
text-decoration: none;	Removes the underline from links.
font-weight: 700;	Thickness of the text.
font-size: 1.6rem;	Size of the text.
cursor: pointer;	Shows the hand cursor to indicate something clickable.
flex-basis: 100%;	The item takes a whole line, pushing the next items down.
display: none;	Removes the element from rendering completely.
.toggle:checked ~ .menu {	Applies to a checked radio or checkbox; combined with ~ it drives CSS-only widgets.
display: block;	Element starts on a new line and fills the width (used on links and images).
list-style: none;	Removes bullets or numbers from a list.
border-top: 1px solid rgb(255 255 255 / 25%);	A top border used as an accent or separator.
@media (min-width: 700px) {	Applies from the given width upwards (mobile-first breakpoint).
gap: .5rem;	Space between grid or flex items without extra margins.
border: 0;	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
.menu a:hover {	Applies while the pointer is over the element.

Check your work

- Menu opens and closes on mobile
- Burger hidden on desktop
- Label has an aria-label
- No horizontal scrollbar at 320px

Exercises

1. Animate the menu opening with grid-template-rows: 0fr to 1fr.
2. Rebuild with a <button> and aria-expanded using JavaScript.
3. Add a close (X) state to the burger icon.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Glossary with letter navigation

Level 2 | 25 projects, one per theme

Build an A-Z glossary using description lists grouped under letter headings, a sticky letter navigation and highlighted :target entries.

Project 1026: Glossary with letter navigation for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 2 | Files: index.html, styles.css

Brief

Build an A-Z glossary using description lists grouped under letter headings, a sticky letter navigation and highlighted :target entries.

Learning goals

- Group dl entries under sections with ids
- Use :target to highlight a linked term
- Prevent sticky headers from hiding anchors with scroll-margin-top

Elements and CSS used

HTML elements	CSS features
nav, a, section, h2, dl, dt, dd	position: sticky, :target, scroll-margin-top, place-items, flex-wrap

Build guide

1. Sort terms alphabetically and group by first letter.
2. Write one section per letter with an id and a dl.
3. Give each dt an id from its name.
4. Write the letter nav with fragment links.
5. Make the nav sticky.

6. Add scroll-margin-top so targets are not hidden under the nav; highlight :target.

Project 1026: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Glossary</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cairo Book Shop glossary</h1>
    <nav class="letters" aria-label="Jump to letter"><a href="#B">B</
a><a href="#C">C</a><a href="#J">J</a><a href="#L">L</a><a
href="#V">V</a><a href="#W">W</a></nav>
    <section id="B">
      <h2>B</h2>
      <dl>
        <dt id="booking">Booking</dt><dd>Reserving a book in advance..
</dd>
      </dl>
    </section>
    <section id="C">
      <h2>C</h2>
      <dl>
        <dt id="css-in-practice">CSS in Practice</dt><dd>Layouts,
colours and typography.</dd>
      </dl>
    </section>
    <section id="J">
      <h2>J</h2>
      <dl>
        <dt id="javascript-basics">JavaScript Basics</dt><dd>Make
pages interactive.</dd>
      </dl>
    </section>
    <section id="L">
      <h2>L</h2>
      <dl>
        <dt id="learn-html">Learn HTML</dt><dd>From your first tag to
a complete page.</dd>
      </dl>
    </section>
    <section id="V">
      <h2>V</h2>
      <dl>
        <dt id="voucher">Voucher</dt><dd>A prepaid code exchangeable
for services..</dd>
```

```
      </dl>
    </section>
    <section id="W">
      <h2>W</h2>
      <dl>
        <dt id="web-accessibility">Web Accessibility</dt><dd>Pages
everyone can use.</dd>
      </dl>
    </section>
  </main>
</body>
</html>
```

Project 1026: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.letters { display: flex; gap: .4rem; flex-wrap: wrap; position:
sticky; top: 0; background: #fff; padding: .5rem 0; }
.letters a { width: 2rem; height: 2rem; display: grid; place-items:
center; border: 1px solid var(--line); border-radius: 6px; text-
decoration: none; color: var(--ink); }
h2 { color: var(--brand); border-bottom: 2px solid var(--accent);
scroll-margin-top: 4rem; }
dt { font-weight: 700; margin-top: .8rem; scroll-margin-top: 4rem; }
dt:target { background: #fff3b0; }
dd { margin: 0; color: var(--muted); }
```

Project 1026 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - Glossary</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cairo Book Shop glossary	The main heading; only one per page.
<nav class="letters" aria-label="Jump to letter">B...	A block of navigation links; aria-label names it for screen readers.
<section id="B">	A thematic group of content, normally with its own heading.
B	Second-level heading for a section.
<dl>	Description list of term / description pairs.
<dt id="booking">Booking</dt><dd>Reserving a book in advance..</dd>	A term (name) in a description list.

Line	What it does
<dt id="css-in-practice">CSS in Practice</dt><dd>Layouts, colours a...	The description of the preceding term.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .4rem;	Space between grid or flex items without extra margins.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
background: #fff;	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
border-bottom: 2px solid var(--accent);	A bottom border used as a separator line.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.
font-weight: 700;	Thickness of the text.
dt:target {	Applies to the element whose id matches the URL fragment.

Check your work

- Letter links jump correctly
- Target term highlighted
- Headings not hidden under sticky bar
- dt/dd pairs valid

Exercises

1. Add a live filter input with JavaScript.
2. Link terms to each other with <a href="#term">.

3. Add <dfn> around each term.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 1027: Glossary with letter navigation for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 2 | Files: index.html, styles.css

Brief

Build an A-Z glossary using description lists grouped under letter headings, a sticky letter navigation and highlighted :target entries.

Learning goals

- Group dl entries under sections with ids
- Use :target to highlight a linked term
- Prevent sticky headers from hiding anchors with scroll-margin-top

Elements and CSS used

HTML elements	CSS features
nav, a, section, h2, dl, dt, dd	position: sticky, :target, scroll-margin-top, place-items, flex-wrap

Build guide

1. Sort terms alphabetically and group by first letter.
2. Write one section per letter with an id and a dl.
3. Give each dt an id from its name.
4. Write the letter nav with fragment links.
5. Make the nav sticky.

6. Add scroll-margin-top so targets are not hidden under the nav; highlight :target.

Project 1027: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - Glossary</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Nile Bakery glossary</h1>
    <nav class="letters" aria-label="Jump to letter"><a href="#B">B</
a><a href="#C">C</a><a href="#D">D</a><a href="#S">S</a><a
href="#V">V</a></nav>
    <section id="B">
      <h2>B</h2>
      <dl>
        <dt id="baklava-box">Baklava box</dt><dd>Pistachio and honey.
</dd>
        <dt id="booking">Booking</dt><dd>Reserving a pastry in
advance..</dd>
      </dl>
    </section>
    <section id="C">
      <h2>C</h2>
      <dl>
        <dt id="croissant">Croissant</dt><dd>Butter, 27 layers.</dd>
      </dl>
    </section>
    <section id="D">
      <h2>D</h2>
      <dl>
        <dt id="date-cookies">Date cookies</dt><dd>Traditional
maamoul style.</dd>
      </dl>
    </section>
    <section id="S">
      <h2>S</h2>
      <dl>
        <dt id="sourdough-loaf">Sourdough loaf</dt><dd>Slow fermented,
 crisp crust.</dd>
      </dl>
    </section>
    <section id="V">
      <h2>V</h2>
      <dl>
        <dt id="voucher">Voucher</dt><dd>A prepaid code exchangeable
```

```
for services..</dd>
      </dl>
    </section>
  </main>
</body>
</html>
```

Project 1027: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.letters { display: flex; gap: .4rem; flex-wrap: wrap; position:
sticky; top: 0; background: #fff; padding: .5rem 0; }
.letters a { width: 2rem; height: 2rem; display: grid; place-items:
center; border: 1px solid var(--line); border-radius: 6px; text-
decoration: none; color: var(--ink); }
h2 { color: var(--brand); border-bottom: 2px solid var(--accent);
scroll-margin-top: 4rem; }
dt { font-weight: 700; margin-top: .8rem; scroll-margin-top: 4rem; }
dt:target { background: #fff3b0; }
dd { margin: 0; color: var(--muted); }
```

Project 1027 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - Glossary</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Nile Bakery glossary	The main heading; only one per page.
<nav class="letters" aria-label="Jump to letter">B...	A block of navigation links; aria-label names it for screen readers.
<section id="B">	A thematic group of content, normally with its own heading.
B	Second-level heading for a section.
<dl>	Description list of term / description pairs.
<dt id="baklava-box">Baklava box</dt><dd>Pistachio and honey.</dd>	A term (name) in a description list.

Line	What it does
<dt id="booking">Booking</dt><dd>Reserving a pastry in advance..</dd>	The description of the preceding term.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .4rem;	Space between grid or flex items without extra margins.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
background: #fff;	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
border-bottom: 2px solid var(--accent);	A bottom border used as a separator line.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.
font-weight: 700;	Thickness of the text.
dt:target {	Applies to the element whose id matches the URL fragment.

Check your work

- Letter links jump correctly
- Target term highlighted
- Headings not hidden under sticky bar
- dt/dd pairs valid

Exercises

1. Add a live filter input with JavaScript.
2. Link terms to each other with <a href="#term">.

3. Add <dfn> around each term.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 1028: Glossary with letter navigation for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 2 | Files: index.html, styles.css

Brief

Build an A-Z glossary using description lists grouped under letter headings, a sticky letter navigation and highlighted :target entries.

Learning goals

- Group dl entries under sections with ids
- Use :target to highlight a linked term
- Prevent sticky headers from hiding anchors with scroll-margin-top

Elements and CSS used

HTML elements	CSS features
nav, a, section, h2, dl, dt, dd	position: sticky, :target, scroll-margin-top, place-items, flex-wrap

Build guide

1. Sort terms alphabetically and group by first letter.
2. Write one section per letter with an id and a dl.
3. Give each dt an id from its name.
4. Write the letter nav with fragment links.
5. Make the nav sticky.

6. Add scroll-margin-top so targets are not hidden under the nav; highlight :target.

Project 1028: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - Glossary</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Pyramid Fitness glossary</h1>
    <nav class="letters" aria-label="Jump to letter"><a href="#B">B</
a><a href="#M">M</a><a href="#P">P</a><a href="#S">S</a><a
href="#V">V</a></nav>
    <section id="B">
      <h2>B</h2>
      <dl>
        <dt id="booking">Booking</dt><dd>Reserving a class in advance.
.</dd>
      </dl>
    </section>
    <section id="M">
      <h2>M</h2>
      <dl>
        <dt id="morning-yoga">Morning yoga</dt><dd>Flexibility and
calm, 60 minutes.</dd>
      </dl>
    </section>
    <section id="P">
      <h2>P</h2>
      <dl>
        <dt id="personal-training">Personal training</dt><dd>One to
one coaching.</dd>
      </dl>
    </section>
    <section id="S">
      <h2>S</h2>
      <dl>
        <dt id="spinning">Spinning</dt><dd>High energy cycling.</dd>
        <dt id="strength-circuit">Strength circuit</dt><dd>Full body,
all levels.</dd>
      </dl>
    </section>
    <section id="V">
      <h2>V</h2>
      <dl>
        <dt id="voucher">Voucher</dt><dd>A prepaid code exchangeable
```

```
for services..</dd>
      </dl>
    </section>
  </main>
</body>
</html>
```

Project 1028: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.letters { display: flex; gap: .4rem; flex-wrap: wrap; position:
sticky; top: 0; background: #fff; padding: .5rem 0; }
.letters a { width: 2rem; height: 2rem; display: grid; place-items:
center; border: 1px solid var(--line); border-radius: 6px; text-
decoration: none; color: var(--ink); }
h2 { color: var(--brand); border-bottom: 2px solid var(--accent);
scroll-margin-top: 4rem; }
dt { font-weight: 700; margin-top: .8rem; scroll-margin-top: 4rem; }
dt:target { background: #fff3b0; }
dd { margin: 0; color: var(--muted); }
```

Project 1028 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - Glossary</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Pyramid Fitness glossary	The main heading; only one per page.
<nav class="letters" aria-label="Jump to letter">B...	A block of navigation links; aria-label names it for screen readers.
<section id="B">	A thematic group of content, normally with its own heading.
B	Second-level heading for a section.
<dl>	Description list of term / description pairs.
<dt id="booking">Booking</dt><dd>Reserving a class in advance..</dd>	A term (name) in a description list.

Line	What it does
<dt id="morning-yoga">Morning yoga</dt><dd>Flexibility and calm, 60...	The description of the preceding term.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .4rem;	Space between grid or flex items without extra margins.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
background: #fff;	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
border-bottom: 2px solid var(--accent);	A bottom border used as a separator line.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.
font-weight: 700;	Thickness of the text.
dt:target {	Applies to the element whose id matches the URL fragment.

Check your work

- Letter links jump correctly
- Target term highlighted
- Headings not hidden under sticky bar
- dt/dd pairs valid

Exercises

1. Add a live filter input with JavaScript.
2. Link terms to each other with <a href="#term">.

3. Add <dfn> around each term.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 1029: Glossary with letter navigation for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 2 | Files: index.html, styles.css

Brief

Build an A-Z glossary using description lists grouped under letter headings, a sticky letter navigation and highlighted :target entries.

Learning goals

- Group dl entries under sections with ids
- Use :target to highlight a linked term
- Prevent sticky headers from hiding anchors with scroll-margin-top

Elements and CSS used

HTML elements	CSS features
nav, a, section, h2, dl, dt, dd	position: sticky, :target, scroll-margin-top, place-items, flex-wrap

Build guide

1. Sort terms alphabetically and group by first letter.
2. Write one section per letter with an id and a dl.
3. Give each dt an id from its name.
4. Write the letter nav with fragment links.
5. Make the nav sticky.

6. Add scroll-margin-top so targets are not hidden under the nav; highlight :target.

Project 1029: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - Glossary</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Delta Dental Clinic glossary</h1>
    <nav class="letters" aria-label="Jump to letter"><a href="#B">B</
a><a href="#C">C</a><a href="#F">F</a><a href="#V">V</a><a
href="#W">W</a></nav>
    <section id="B">
      <h2>B</h2>
      <dl>
        <dt id="booking">Booking</dt><dd>Reserving a service in
advance..</dd>
        <dt id="braces-consultation">Braces consultation</dt><dd>Plan
your treatment.</dd>
      </dl>
    </section>
    <section id="C">
      <h2>C</h2>
      <dl>
        <dt id="check-up">Check-up</dt><dd>Examination and cleaning.</
dd>
      </dl>
    </section>
    <section id="F">
      <h2>F</h2>
      <dl>
        <dt id="filling">Filling</dt><dd>Tooth-coloured composite.</
dd>
      </dl>
    </section>
    <section id="V">
      <h2>V</h2>
      <dl>
        <dt id="voucher">Voucher</dt><dd>A prepaid code exchangeable
for services..</dd>
      </dl>
    </section>
    <section id="W">
      <h2>W</h2>
      <dl>
```

```
        <dt id="whitening">Whitening</dt><dd>Brighter smile in one
visit.</dd>
      </dl>
    </section>
  </main>
</body>
</html>
```

Project 1029: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.letters { display: flex; gap: .4rem; flex-wrap: wrap; position:
sticky; top: 0; background: #fff; padding: .5rem 0; }
.letters a { width: 2rem; height: 2rem; display: grid; place-items:
center; border: 1px solid var(--line); border-radius: 6px; text-
decoration: none; color: var(--ink); }
h2 { color: var(--brand); border-bottom: 2px solid var(--accent);
scroll-margin-top: 4rem; }
dt { font-weight: 700; margin-top: .8rem; scroll-margin-top: 4rem; }
dt:target { background: #fff3b0; }
dd { margin: 0; color: var(--muted); }
```

Project 1029 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - Glossary</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Delta Dental Clinic glossary	The main heading; only one per page.
<nav class="letters" aria-label="Jump to letter">B...	A block of navigation links; aria-label names it for screen readers.
<section id="B">	A thematic group of content, normally with its own heading.
B	Second-level heading for a section.
<dl>	Description list of term / description pairs.
<dt id="booking">Booking</dt><dd>Reserving a service in advance..</dd>	A term (name) in a description list.

Line	What it does
<dt id="braces-consultation">Braces consultation</dt><dd>Plan your ...	The description of the preceding term.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .4rem;	Space between grid or flex items without extra margins.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
background: #fff;	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
border-bottom: 2px solid var(--accent);	A bottom border used as a separator line.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.
font-weight: 700;	Thickness of the text.
dt:target {	Applies to the element whose id matches the URL fragment.

Check your work

- Letter links jump correctly
- Target term highlighted
- Headings not hidden under sticky bar
- dt/dd pairs valid

Exercises

1. Add a live filter input with JavaScript.
2. Link terms to each other with <a href="#term">.

3. Add <dfn> around each term.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 1030: Glossary with letter navigation for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 2 | Files: index.html, styles.css

Brief

Build an A-Z glossary using description lists grouped under letter headings, a sticky letter navigation and highlighted :target entries.

Learning goals

- Group dl entries under sections with ids
- Use :target to highlight a linked term
- Prevent sticky headers from hiding anchors with scroll-margin-top

Elements and CSS used

HTML elements	CSS features
nav, a, section, h2, dl, dt, dd	position: sticky, :target, scroll-margin-top, place-items, flex-wrap

Build guide

1. Sort terms alphabetically and group by first letter.
2. Write one section per letter with an id and a dl.
3. Give each dt an id from its name.
4. Write the letter nav with fragment links.
5. Make the nav sticky.

6. Add scroll-margin-top so targets are not hidden under the nav; highlight :target.

Project 1030: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - Glossary</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Red Sea Travel glossary</h1>
    <nav class="letters" aria-label="Jump to letter"><a href="#B">B</
a><a href="#D">D</a><a href="#L">L</a><a href="#N">N</a><a
href="#S">S</a><a href="#V">V</a></nav>
    <section id="B">
      <h2>B</h2>
      <dl>
        <dt id="booking">Booking</dt><dd>Reserving a tour in advance..
</dd>
      </dl>
    </section>
    <section id="D">
      <h2>D</h2>
      <dl>
        <dt id="desert-safari">Desert safari</dt><dd>Quad bikes and
Bedouin dinner.</dd>
      </dl>
    </section>
    <section id="L">
      <h2>L</h2>
      <dl>
        <dt id="luxor-day-trip">Luxor day trip</dt><dd>Karnak, Valley
of the Kings.</dd>
      </dl>
    </section>
    <section id="N">
      <h2>N</h2>
      <dl>
        <dt id="nile-cruise">Nile cruise</dt><dd>Three nights Aswan
to Luxor.</dd>
      </dl>
    </section>
    <section id="S">
      <h2>S</h2>
      <dl>
        <dt id="snorkelling">Snorkelling</dt><dd>Giftun island reefs.
</dd>
```

```
      </dl>
    </section>
    <section id="V">
      <h2>V</h2>
      <dl>
        <dt id="voucher">Voucher</dt><dd>A prepaid code exchangeable
for services..</dd>
      </dl>
    </section>
  </main>
</body>
</html>
```

Project 1030: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.letters { display: flex; gap: .4rem; flex-wrap: wrap; position:
sticky; top: 0; background: #fff; padding: .5rem 0; }
.letters a { width: 2rem; height: 2rem; display: grid; place-items:
center; border: 1px solid var(--line); border-radius: 6px; text-
decoration: none; color: var(--ink); }
h2 { color: var(--brand); border-bottom: 2px solid var(--accent);
scroll-margin-top: 4rem; }
dt { font-weight: 700; margin-top: .8rem; scroll-margin-top: 4rem; }
dt:target { background: #fff3b0; }
dd { margin: 0; color: var(--muted); }
```

Project 1030 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - Glossary</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Red Sea Travel glossary	The main heading; only one per page.
<nav class="letters" aria-label="Jump to letter">B...	A block of navigation links; aria-label names it for screen readers.
<section id="B">	A thematic group of content, normally with its own heading.
B	Second-level heading for a section.
<dl>	Description list of term / description pairs.
<dt id="booking">Booking</dt><dd>Reserving a tour in advance..</dd>	A term (name) in a description list.

Line	What it does
<dt id="desert-safari">Desert safari</dt><dd>Quad bikes and Bedouin...	The description of the preceding term.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .4rem;	Space between grid or flex items without extra margins.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
background: #fff;	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
border-bottom: 2px solid var(--accent);	A bottom border used as a separator line.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.
font-weight: 700;	Thickness of the text.
dt:target {	Applies to the element whose id matches the URL fragment.

Check your work

- Letter links jump correctly
- Target term highlighted
- Headings not hidden under sticky bar
- dt/dd pairs valid

Exercises

1. Add a live filter input with JavaScript.
2. Link terms to each other with <a href="#term">.

3. Add <dfn> around each term.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 1031: Glossary with letter navigation for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Build an A-Z glossary using description lists grouped under letter headings, a sticky letter navigation and highlighted :target entries.

Learning goals

- Group dl entries under sections with ids
- Use :target to highlight a linked term
- Prevent sticky headers from hiding anchors with scroll-margin-top

Elements and CSS used

HTML elements	CSS features
nav, a, section, h2, dl, dt, dd	position: sticky, :target, scroll-margin-top, place-items, flex-wrap

Build guide

1. Sort terms alphabetically and group by first letter.
2. Write one section per letter with an id and a dl.
3. Give each dt an id from its name.
4. Write the letter nav with fragment links.
5. Make the nav sticky.

6. Add scroll-margin-top so targets are not hidden under the nav; highlight :target.

Project 1031: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - Glossary</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Lotus Language School glossary</h1>
    <nav class="letters" aria-label="Jump to letter"><a href="#B">B</
a><a href="#E">E</a><a href="#F">F</a><a href="#G">G</a><a
href="#I">I</a><a href="#V">V</a></nav>
    <section id="B">
      <h2>B</h2>
      <dl>
        <dt id="booking">Booking</dt><dd>Reserving a course in
advance..</dd>
      </dl>
    </section>
    <section id="E">
      <h2>E</h2>
      <dl>
        <dt id="english-a1">English A1</dt><dd>Beginner, 8 weeks.</dd>
      </dl>
    </section>
    <section id="F">
      <h2>F</h2>
      <dl>
        <dt id="french-b1">French B1</dt><dd>Intermediate
conversation.</dd>
      </dl>
    </section>
    <section id="G">
      <h2>G</h2>
      <dl>
        <dt id="german-a2">German A2</dt><dd>Grammar and speaking.</
dd>
      </dl>
    </section>
    <section id="I">
      <h2>I</h2>
      <dl>
        <dt id="ielts-preparation">IELTS preparation</dt><dd>Exam
strategies.</dd>
      </dl>
```

```
    </section>
    <section id="V">
      <h2>V</h2>
      <dl>
        <dt id="voucher">Voucher</dt><dd>A prepaid code exchangeable
for services..</dd>
      </dl>
    </section>
  </main>
</body>
</html>
```

Project 1031: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.letters { display: flex; gap: .4rem; flex-wrap: wrap; position:
sticky; top: 0; background: #fff; padding: .5rem 0; }
.letters a { width: 2rem; height: 2rem; display: grid; place-items:
center; border: 1px solid var(--line); border-radius: 6px; text-
decoration: none; color: var(--ink); }
h2 { color: var(--brand); border-bottom: 2px solid var(--accent);
scroll-margin-top: 4rem; }
dt { font-weight: 700; margin-top: .8rem; scroll-margin-top: 4rem; }
dt:target { background: #fff3b0; }
dd { margin: 0; color: var(--muted); }
```

Project 1031 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - Glossary</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Lotus Language School glossary	The main heading; only one per page.
<nav class="letters" aria-label="Jump to letter">B...	A block of navigation links; aria-label names it for screen readers.
<section id="B">	A thematic group of content, normally with its own heading.
B	Second-level heading for a section.
<dl>	Description list of term / description pairs.
<dt id="booking">Booking</dt><dd>Reserving a course in advance..</dd>	A term (name) in a description list.

Line	What it does
<dt id="english-a1">English A1</dt><dd>Beginner, 8 weeks.</dd>	The description of the preceding term.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .4rem;	Space between grid or flex items without extra margins.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
background: #fff;	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
border-bottom: 2px solid var(--accent);	A bottom border used as a separator line.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.
font-weight: 700;	Thickness of the text.
dt:target {	Applies to the element whose id matches the URL fragment.

Check your work

- Letter links jump correctly
- Target term highlighted
- Headings not hidden under sticky bar
- dt/dd pairs valid

Exercises

1. Add a live filter input with JavaScript.
2. Link terms to each other with <a href="#term">.

3. Add <dfn> around each term.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 1032: Glossary with letter navigation for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 2 | Files: index.html, styles.css

Brief

Build an A-Z glossary using description lists grouped under letter headings, a sticky letter navigation and highlighted :target entries.

Learning goals

- Group dl entries under sections with ids
- Use :target to highlight a linked term
- Prevent sticky headers from hiding anchors with scroll-margin-top

Elements and CSS used

HTML elements	CSS features
nav, a, section, h2, dl, dt, dd	position: sticky, :target, scroll-margin-top, place-items, flex-wrap

Build guide

1. Sort terms alphabetically and group by first letter.
2. Write one section per letter with an id and a dl.
3. Give each dt an id from its name.
4. Write the letter nav with fragment links.
5. Make the nav sticky.

6. Add scroll-margin-top so targets are not hidden under the nav; highlight :target.

Project 1032: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - Glossary</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Green Leaf Cafe glossary</h1>
    <nav class="letters" aria-label="Jump to letter"><a href="#B">B</
a><a href="#C">C</a><a href="#F">F</a><a href="#H">H</a><a
href="#V">V</a></nav>
    <section id="B">
      <h2>B</h2>
      <dl>
        <dt id="booking">Booking</dt><dd>Reserving a drink in advance.
.</dd>
      </dl>
    </section>
    <section id="C">
      <h2>C</h2>
      <dl>
        <dt id="cheesecake">Cheesecake</dt><dd>Baked, with berries.</
dd>
        <dt id="cold-brew">Cold brew</dt><dd>18 hours steeped.</dd>
      </dl>
    </section>
    <section id="F">
      <h2>F</h2>
      <dl>
        <dt id="flat-white">Flat white</dt><dd>Double shot, silky
milk.</dd>
      </dl>
    </section>
    <section id="H">
      <h2>H</h2>
      <dl>
        <dt id="hibiscus-iced-tea">Hibiscus iced tea</dt><dd>Karkade
with mint.</dd>
      </dl>
    </section>
    <section id="V">
      <h2>V</h2>
      <dl>
        <dt id="voucher">Voucher</dt><dd>A prepaid code exchangeable
```

```
for services..</dd>
      </dl>
    </section>
  </main>
</body>
</html>
```

Project 1032: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.letters { display: flex; gap: .4rem; flex-wrap: wrap; position:
sticky; top: 0; background: #fff; padding: .5rem 0; }
.letters a { width: 2rem; height: 2rem; display: grid; place-items:
center; border: 1px solid var(--line); border-radius: 6px; text-
decoration: none; color: var(--ink); }
h2 { color: var(--brand); border-bottom: 2px solid var(--accent);
scroll-margin-top: 4rem; }
dt { font-weight: 700; margin-top: .8rem; scroll-margin-top: 4rem; }
dt:target { background: #fff3b0; }
dd { margin: 0; color: var(--muted); }
```

Project 1032 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - Glossary</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Green Leaf Cafe glossary	The main heading; only one per page.
<nav class="letters" aria-label="Jump to letter">B...	A block of navigation links; aria-label names it for screen readers.
<section id="B">	A thematic group of content, normally with its own heading.
B	Second-level heading for a section.
<dl>	Description list of term / description pairs.
<dt id="booking">Booking</dt><dd>Reserving a drink in advance..</dd>	A term (name) in a description list.

Line	What it does
<dt id="cheesecake">Cheesecake</dt><dd>Baked, with berries.</dd>	The description of the preceding term.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .4rem;	Space between grid or flex items without extra margins.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
background: #fff;	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
border-bottom: 2px solid var(--accent);	A bottom border used as a separator line.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.
font-weight: 700;	Thickness of the text.
dt:target {	Applies to the element whose id matches the URL fragment.

Check your work

- Letter links jump correctly
- Target term highlighted
- Headings not hidden under sticky bar
- dt/dd pairs valid

Exercises

1. Add a live filter input with JavaScript.
2. Link terms to each other with <a href="#term">.

3. Add <dfn> around each term.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 1033: Glossary with letter navigation for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 2 | Files: index.html, styles.css

Brief

Build an A-Z glossary using description lists grouped under letter headings, a sticky letter navigation and highlighted :target entries.

Learning goals

- Group dl entries under sections with ids
- Use :target to highlight a linked term
- Prevent sticky headers from hiding anchors with scroll-margin-top

Elements and CSS used

HTML elements	CSS features
nav, a, section, h2, dl, dt, dd	position: sticky, :target, scroll-margin-top, place-items, flex-wrap

Build guide

1. Sort terms alphabetically and group by first letter.
2. Write one section per letter with an id and a dl.
3. Give each dt an id from its name.
4. Write the letter nav with fragment links.
5. Make the nav sticky.

6. Add scroll-margin-top so targets are not hidden under the nav; highlight :target.

Project 1033: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - Glossary</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Sinai Trekking Club glossary</h1>
    <nav class="letters" aria-label="Jump to letter"><a href="#B">B</
a><a href="#M">M</a><a href="#T">T</a><a href="#V">V</a><a
href="#W">W</a></nav>
    <section id="B">
      <h2>B</h2>
      <dl>
        <dt id="blue-desert-loop">Blue Desert loop</dt><dd>Easy day
walk.</dd>
        <dt id="booking">Booking</dt><dd>Reserving a hike in advance..
</dd>
      </dl>
    </section>
    <section id="M">
      <h2>M</h2>
      <dl>
        <dt id="mount-sinai-sunrise">Mount Sinai sunrise</
dt><dd>Night climb, 7 km.</dd>
      </dl>
    </section>
    <section id="T">
      <h2>T</h2>
      <dl>
        <dt id="three-day-traverse">Three-day traverse</
dt><dd>Camping under stars.</dd>
      </dl>
    </section>
    <section id="V">
      <h2>V</h2>
      <dl>
        <dt id="voucher">Voucher</dt><dd>A prepaid code exchangeable
for services..</dd>
      </dl>
    </section>
    <section id="W">
      <h2>W</h2>
      <dl>
```

```
        <dt id="wadi-gnai">Wadi Gnai</dt><dd>Palms and pools.</dd>
      </dl>
    </section>
  </main>
</body>
</html>
```

Project 1033: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.letters { display: flex; gap: .4rem; flex-wrap: wrap; position:
sticky; top: 0; background: #fff; padding: .5rem 0; }
.letters a { width: 2rem; height: 2rem; display: grid; place-items:
center; border: 1px solid var(--line); border-radius: 6px; text-
decoration: none; color: var(--ink); }
h2 { color: var(--brand); border-bottom: 2px solid var(--accent);
scroll-margin-top: 4rem; }
dt { font-weight: 700; margin-top: .8rem; scroll-margin-top: 4rem; }
dt:target { background: #fff3b0; }
dd { margin: 0; color: var(--muted); }
```

Project 1033 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - Glossary</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Sinai Trekking Club glossary	The main heading; only one per page.
<nav class="letters" aria-label="Jump to letter">B...	A block of navigation links; aria-label names it for screen readers.
<section id="B">	A thematic group of content, normally with its own heading.
B	Second-level heading for a section.
<dl>	Description list of term / description pairs.
<dt id="blue-desert-loop">Blue Desert loop</dt><dd>Easy day walk.</dd>	A term (name) in a description list.

Line	What it does
<dt id="booking">Booking</dt><dd>Reserving a hike in advance..</dd>	The description of the preceding term.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .4rem;	Space between grid or flex items without extra margins.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
background: #fff;	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
border-bottom: 2px solid var(--accent);	A bottom border used as a separator line.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.
font-weight: 700;	Thickness of the text.
dt:target {	Applies to the element whose id matches the URL fragment.

Check your work

- Letter links jump correctly
- Target term highlighted
- Headings not hidden under sticky bar
- dt/dd pairs valid

Exercises

1. Add a live filter input with JavaScript.
2. Link terms to each other with <a href="#term">.

3. Add <dfn> around each term.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 1034: Glossary with letter navigation for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 2 | Files: index.html, styles.css

Brief

Build an A-Z glossary using description lists grouped under letter headings, a sticky letter navigation and highlighted :target entries.

Learning goals

- Group dl entries under sections with ids
- Use :target to highlight a linked term
- Prevent sticky headers from hiding anchors with scroll-margin-top

Elements and CSS used

HTML elements	CSS features
nav, a, section, h2, dl, dt, dd	position: sticky, :target, scroll-margin-top, place-items, flex-wrap

Build guide

1. Sort terms alphabetically and group by first letter.
2. Write one section per letter with an id and a dl.
3. Give each dt an id from its name.
4. Write the letter nav with fragment links.
5. Make the nav sticky.

6. Add scroll-margin-top so targets are not hidden under the nav; highlight :target.

Project 1034: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - Glossary</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Horizon Photography glossary</h1>
    <nav class="letters" aria-label="Jump to letter"><a href="#B">B</
a><a href="#F">F</a><a href="#P">P</a><a href="#V">V</a><a
href="#W">W</a></nav>
    <section id="B">
      <h2>B</h2>
      <dl>
        <dt id="booking">Booking</dt><dd>Reserving a session in
advance..</dd>
      </dl>
    </section>
    <section id="F">
      <h2>F</h2>
      <dl>
        <dt id="family-session">Family session</dt><dd>Outdoor,
golden hour.</dd>
      </dl>
    </section>
    <section id="P">
      <h2>P</h2>
      <dl>
        <dt id="portrait-session">Portrait session</dt><dd>One hour,
20 edited photos.</dd>
        <dt id="product-shoot">Product shoot</dt><dd>White background,
 10 items.</dd>
      </dl>
    </section>
    <section id="V">
      <h2>V</h2>
      <dl>
        <dt id="voucher">Voucher</dt><dd>A prepaid code exchangeable
for services..</dd>
      </dl>
    </section>
    <section id="W">
      <h2>W</h2>
      <dl>
```

```
        <dt id="wedding-day">Wedding day</dt><dd>Full coverage, two
photographers.</dd>
      </dl>
    </section>
  </main>
</body>
</html>
```

Project 1034: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.letters { display: flex; gap: .4rem; flex-wrap: wrap; position:
sticky; top: 0; background: #fff; padding: .5rem 0; }
.letters a { width: 2rem; height: 2rem; display: grid; place-items:
center; border: 1px solid var(--line); border-radius: 6px; text-
decoration: none; color: var(--ink); }
h2 { color: var(--brand); border-bottom: 2px solid var(--accent);
scroll-margin-top: 4rem; }
dt { font-weight: 700; margin-top: .8rem; scroll-margin-top: 4rem; }
dt:target { background: #fff3b0; }
dd { margin: 0; color: var(--muted); }
```

Project 1034 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - Glossary</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Horizon Photography glossary	The main heading; only one per page.
<nav class="letters" aria-label="Jump to letter">B...	A block of navigation links; aria-label names it for screen readers.
<section id="B">	A thematic group of content, normally with its own heading.
B	Second-level heading for a section.
<dl>	Description list of term / description pairs.
<dt id="booking">Booking</dt><dd>Reserving a session in advance..</dd>	A term (name) in a description list.

Line	What it does
<dt id="family-session">Family session</dt><dd>Outdoor, golden hour...	The description of the preceding term.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .4rem;	Space between grid or flex items without extra margins.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
background: #fff;	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
border-bottom: 2px solid var(--accent);	A bottom border used as a separator line.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.
font-weight: 700;	Thickness of the text.
dt:target {	Applies to the element whose id matches the URL fragment.

Check your work

- Letter links jump correctly
- Target term highlighted
- Headings not hidden under sticky bar
- dt/dd pairs valid

Exercises

1. Add a live filter input with JavaScript.
2. Link terms to each other with <a href="#term">.

3. Add <dfn> around each term.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 1035: Glossary with letter navigation for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 2 | Files: index.html, styles.css

Brief

Build an A-Z glossary using description lists grouped under letter headings, a sticky letter navigation and highlighted :target entries.

Learning goals

- Group dl entries under sections with ids
- Use :target to highlight a linked term
- Prevent sticky headers from hiding anchors with scroll-margin-top

Elements and CSS used

HTML elements	CSS features
nav, a, section, h2, dl, dt, dd	position: sticky, :target, scroll-margin-top, place-items, flex-wrap

Build guide

1. Sort terms alphabetically and group by first letter.
2. Write one section per letter with an id and a dl.
3. Give each dt an id from its name.
4. Write the letter nav with fragment links.
5. Make the nav sticky.

6. Add scroll-margin-top so targets are not hidden under the nav; highlight :target.

Project 1035: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - Glossary</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Papyrus Stationery glossary</h1>
    <nav class="letters" aria-label="Jump to letter"><a href="#B">B</
a><a href="#D">D</a><a href="#F">F</a><a href="#V">V</a><a
href="#W">W</a></nav>
    <section id="B">
      <h2>B</h2>
      <dl>
        <dt id="booking">Booking</dt><dd>Reserving a product in
advance..</dd>
      </dl>
    </section>
    <section id="D">
      <h2>D</h2>
      <dl>
        <dt id="desk-planner">Desk planner</dt><dd>Weekly, undated.</
dd>
        <dt id="dotted-notebook">Dotted notebook</dt><dd>A5, 160
pages.</dd>
      </dl>
    </section>
    <section id="F">
      <h2>F</h2>
      <dl>
        <dt id="fountain-pen">Fountain pen</dt><dd>Steel nib,
refillable.</dd>
      </dl>
    </section>
    <section id="V">
      <h2>V</h2>
      <dl>
        <dt id="voucher">Voucher</dt><dd>A prepaid code exchangeable
for services..</dd>
      </dl>
    </section>
    <section id="W">
      <h2>W</h2>
      <dl>
```

```
        <dt id="washi-tape-set">Washi tape set</dt><dd>Six patterns.</
dd>
      </dl>
    </section>
  </main>
</body>
</html>
```

Project 1035: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.letters { display: flex; gap: .4rem; flex-wrap: wrap; position:
sticky; top: 0; background: #fff; padding: .5rem 0; }
.letters a { width: 2rem; height: 2rem; display: grid; place-items:
center; border: 1px solid var(--line); border-radius: 6px; text-
decoration: none; color: var(--ink); }
h2 { color: var(--brand); border-bottom: 2px solid var(--accent);
scroll-margin-top: 4rem; }
dt { font-weight: 700; margin-top: .8rem; scroll-margin-top: 4rem; }
dt:target { background: #fff3b0; }
dd { margin: 0; color: var(--muted); }
```

Project 1035 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - Glossary</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Papyrus Stationery glossary	The main heading; only one per page.
<nav class="letters" aria-label="Jump to letter">B...	A block of navigation links; aria-label names it for screen readers.
<section id="B">	A thematic group of content, normally with its own heading.
B	Second-level heading for a section.
<dl>	Description list of term / description pairs.
<dt id="booking">Booking</dt><dd>Reserving a product in advance..</dd>	A term (name) in a description list.

Line	What it does
<dt id="desk-planner">Desk planner</dt><dd>Weekly, undated.</dd>	The description of the preceding term.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .4rem;	Space between grid or flex items without extra margins.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
background: #fff;	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
border-bottom: 2px solid var(--accent);	A bottom border used as a separator line.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.
font-weight: 700;	Thickness of the text.
dt:target {	Applies to the element whose id matches the URL fragment.

Check your work

- Letter links jump correctly
- Target term highlighted
- Headings not hidden under sticky bar
- dt/dd pairs valid

Exercises

1. Add a live filter input with JavaScript.
2. Link terms to each other with <a href="#term">.

3. Add <dfn> around each term.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 1036: Glossary with letter navigation for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 2 | Files: index.html, styles.css

Brief

Build an A-Z glossary using description lists grouped under letter headings, a sticky letter navigation and highlighted :target entries.

Learning goals

- Group dl entries under sections with ids
- Use :target to highlight a linked term
- Prevent sticky headers from hiding anchors with scroll-margin-top

Elements and CSS used

HTML elements	CSS features
nav, a, section, h2, dl, dt, dd	position: sticky, :target, scroll-margin-top, place-items, flex-wrap

Build guide

1. Sort terms alphabetically and group by first letter.
2. Write one section per letter with an id and a dl.
3. Give each dt an id from its name.
4. Write the letter nav with fragment links.
5. Make the nav sticky.

6. Add scroll-margin-top so targets are not hidden under the nav; highlight :target.

Project 1036: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - Glossary</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Oasis Plant Nursery glossary</h1>
    <nav class="letters" aria-label="Jump to letter"><a href="#B">B</
a><a href="#M">M</a><a href="#O">O</a><a href="#S">S</a><a
href="#V">V</a></nav>
    <section id="B">
      <h2>B</h2>
      <dl>
        <dt id="basil-pot">Basil pot</dt><dd>Kitchen herb.</dd>
        <dt id="booking">Booking</dt><dd>Reserving a plant in advance.
.</dd>
      </dl>
    </section>
    <section id="M">
      <h2>M</h2>
      <dl>
        <dt id="monstera">Monstera</dt><dd>Large leaves, easy care.</
dd>
      </dl>
    </section>
    <section id="O">
      <h2>O</h2>
      <dl>
        <dt id="olive-tree">Olive tree</dt><dd>Balcony sized.</dd>
      </dl>
    </section>
    <section id="S">
      <h2>S</h2>
      <dl>
        <dt id="snake-plant">Snake plant</dt><dd>Survives anything.</
dd>
      </dl>
    </section>
    <section id="V">
      <h2>V</h2>
      <dl>
        <dt id="voucher">Voucher</dt><dd>A prepaid code exchangeable
for services..</dd>
```

```
      </dl>
    </section>
  </main>
</body>
</html>
```

Project 1036: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.letters { display: flex; gap: .4rem; flex-wrap: wrap; position:
sticky; top: 0; background: #fff; padding: .5rem 0; }
.letters a { width: 2rem; height: 2rem; display: grid; place-items:
center; border: 1px solid var(--line); border-radius: 6px; text-
decoration: none; color: var(--ink); }
h2 { color: var(--brand); border-bottom: 2px solid var(--accent);
scroll-margin-top: 4rem; }
dt { font-weight: 700; margin-top: .8rem; scroll-margin-top: 4rem; }
dt:target { background: #fff3b0; }
dd { margin: 0; color: var(--muted); }
```

Project 1036 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - Glossary</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Oasis Plant Nursery glossary	The main heading; only one per page.
<nav class="letters" aria-label="Jump to letter">B...	A block of navigation links; aria-label names it for screen readers.
<section id="B">	A thematic group of content, normally with its own heading.
B	Second-level heading for a section.
<dl>	Description list of term / description pairs.
<dt id="basil-pot">Basil pot</dt><dd>Kitchen herb.</dd>	A term (name) in a description list.

Line	What it does
<dt id="booking">Booking</dt><dd>Reserving a plant in advance..</dd>	The description of the preceding term.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .4rem;	Space between grid or flex items without extra margins.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
background: #fff;	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
border-bottom: 2px solid var(--accent);	A bottom border used as a separator line.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.
font-weight: 700;	Thickness of the text.
dt:target {	Applies to the element whose id matches the URL fragment.

Check your work

- Letter links jump correctly
- Target term highlighted
- Headings not hidden under sticky bar
- dt/dd pairs valid

Exercises

1. Add a live filter input with JavaScript.
2. Link terms to each other with <a href="#term">.

3. Add <dfn> around each term.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 1037: Glossary with letter navigation for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 2 | Files: index.html, styles.css

Brief

Build an A-Z glossary using description lists grouped under letter headings, a sticky letter navigation and highlighted :target entries.

Learning goals

- Group dl entries under sections with ids
- Use :target to highlight a linked term
- Prevent sticky headers from hiding anchors with scroll-margin-top

Elements and CSS used

HTML elements	CSS features
nav, a, section, h2, dl, dt, dd	position: sticky, :target, scroll-margin-top, place-items, flex-wrap

Build guide

1. Sort terms alphabetically and group by first letter.
2. Write one section per letter with an id and a dl.
3. Give each dt an id from its name.
4. Write the letter nav with fragment links.
5. Make the nav sticky.

6. Add scroll-margin-top so targets are not hidden under the nav; highlight :target.

Project 1037: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - Glossary</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cedar Furniture glossary</h1>
    <nav class="letters" aria-label="Jump to letter"><a href="#B">B</
a><a href="#C">C</a><a href="#O">O</a><a href="#V">V</a></nav>
    <section id="B">
      <h2>B</h2>
      <dl>
        <dt id="bedside-table">Bedside table</dt><dd>One drawer.</dd>
        <dt id="booking">Booking</dt><dd>Reserving a piece in advance.
.</dd>
        <dt id="bookshelf">Bookshelf</dt><dd>Five shelves, walnut.</
dd>
      </dl>
    </section>
    <section id="C">
      <h2>C</h2>
      <dl>
        <dt id="coffee-table">Coffee table</dt><dd>Round, ash wood.</
dd>
      </dl>
    </section>
    <section id="O">
      <h2>O</h2>
      <dl>
        <dt id="oak-dining-table">Oak dining table</dt><dd>Seats six.
</dd>
      </dl>
    </section>
    <section id="V">
      <h2>V</h2>
      <dl>
        <dt id="voucher">Voucher</dt><dd>A prepaid code exchangeable
for services..</dd>
      </dl>
    </section>
  </main>
</body>
</html>
```

Project 1037: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.letters { display: flex; gap: .4rem; flex-wrap: wrap; position:
sticky; top: 0; background: #fff; padding: .5rem 0; }
.letters a { width: 2rem; height: 2rem; display: grid; place-items:
center; border: 1px solid var(--line); border-radius: 6px; text-
decoration: none; color: var(--ink); }
h2 { color: var(--brand); border-bottom: 2px solid var(--accent);
scroll-margin-top: 4rem; }
dt { font-weight: 700; margin-top: .8rem; scroll-margin-top: 4rem; }
dt:target { background: #fff3b0; }
dd { margin: 0; color: var(--muted); }
```

Project 1037 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - Glossary</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cedar Furniture glossary	The main heading; only one per page.
<nav class="letters" aria-label="Jump to letter">B...	A block of navigation links; aria-label names it for screen readers.
<section id="B">	A thematic group of content, normally with its own heading.
B	Second-level heading for a section.
<dl>	Description list of term / description pairs.
<dt id="bedside-table">Bedside table</dt><dd>One drawer.</dd>	A term (name) in a description list.

Line	What it does
<dt id="booking">Booking</dt><dd>Reserving a piece in advance..</dd>	The description of the preceding term.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .4rem;	Space between grid or flex items without extra margins.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
background: #fff;	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
border-bottom: 2px solid var(--accent);	A bottom border used as a separator line.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.
font-weight: 700;	Thickness of the text.
dt:target {	Applies to the element whose id matches the URL fragment.

Check your work

- Letter links jump correctly
- Target term highlighted
- Headings not hidden under sticky bar
- dt/dd pairs valid

Exercises

1. Add a live filter input with JavaScript.
2. Link terms to each other with <a href="#term">.

3. Add <dfn> around each term.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 1038: Glossary with letter navigation for Byte Repair

Theme: Byte Repair (Nasr City) | Level 2 | Files: index.html, styles.css

Brief

Build an A-Z glossary using description lists grouped under letter headings, a sticky letter navigation and highlighted :target entries.

Learning goals

- Group dl entries under sections with ids
- Use :target to highlight a linked term
- Prevent sticky headers from hiding anchors with scroll-margin-top

Elements and CSS used

HTML elements	CSS features
nav, a, section, h2, dl, dt, dd	position: sticky, :target, scroll-margin-top, place-items, flex-wrap

Build guide

1. Sort terms alphabetically and group by first letter.
2. Write one section per letter with an id and a dl.
3. Give each dt an id from its name.
4. Write the letter nav with fragment links.
5. Make the nav sticky.

6. Add scroll-margin-top so targets are not hidden under the nav; highlight :target.

Project 1038: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - Glossary</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Byte Repair glossary</h1>
    <nav class="letters" aria-label="Jump to letter"><a href="#B">B</
a><a href="#D">D</a><a href="#L">L</a><a href="#S">S</a><a
href="#V">V</a></nav>
    <section id="B">
      <h2>B</h2>
      <dl>
        <dt id="battery-swap">Battery swap</dt><dd>Original cells.</
dd>
        <dt id="booking">Booking</dt><dd>Reserving a repair in
advance..</dd>
      </dl>
    </section>
    <section id="D">
      <h2>D</h2>
      <dl>
        <dt id="data-recovery">Data recovery</dt><dd>Drives and cards.
</dd>
      </dl>
    </section>
    <section id="L">
      <h2>L</h2>
      <dl>
        <dt id="laptop-cleaning">Laptop cleaning</dt><dd>Fans and
thermal paste.</dd>
      </dl>
    </section>
    <section id="S">
      <h2>S</h2>
      <dl>
        <dt id="screen-replacement">Screen replacement</dt><dd>Most
phones, 1 hour.</dd>
      </dl>
    </section>
    <section id="V">
      <h2>V</h2>
      <dl>
```

```
        <dt id="voucher">Voucher</dt><dd>A prepaid code exchangeable
for services..</dd>
      </dl>
    </section>
  </main>
</body>
</html>
```

Project 1038: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.letters { display: flex; gap: .4rem; flex-wrap: wrap; position:
sticky; top: 0; background: #fff; padding: .5rem 0; }
.letters a { width: 2rem; height: 2rem; display: grid; place-items:
center; border: 1px solid var(--line); border-radius: 6px; text-
decoration: none; color: var(--ink); }
h2 { color: var(--brand); border-bottom: 2px solid var(--accent);
scroll-margin-top: 4rem; }
dt { font-weight: 700; margin-top: .8rem; scroll-margin-top: 4rem; }
dt:target { background: #fff3b0; }
dd { margin: 0; color: var(--muted); }
```

Project 1038 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - Glossary</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Byte Repair glossary	The main heading; only one per page.
<nav class="letters" aria-label="Jump to letter">B...	A block of navigation links; aria-label names it for screen readers.
<section id="B">	A thematic group of content, normally with its own heading.
B	Second-level heading for a section.
<dl>	Description list of term / description pairs.
<dt id="battery-swap">Battery swap</dt><dd>Original cells.</dd>	A term (name) in a description list.

Line	What it does
<dt id="booking">Booking</dt><dd>Reserving a repair in advance..</dd>	The description of the preceding term.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .4rem;	Space between grid or flex items without extra margins.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
background: #fff;	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
border-bottom: 2px solid var(--accent);	A bottom border used as a separator line.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.
font-weight: 700;	Thickness of the text.
dt:target {	Applies to the element whose id matches the URL fragment.

Check your work

- Letter links jump correctly
- Target term highlighted
- Headings not hidden under sticky bar
- dt/dd pairs valid

Exercises

1. Add a live filter input with JavaScript.
2. Link terms to each other with <a href="#term">.

3. Add <dfn> around each term.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 1039: Glossary with letter navigation for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 2 | Files: index.html, styles.css

Brief

Build an A-Z glossary using description lists grouped under letter headings, a sticky letter navigation and highlighted :target entries.

Learning goals

- Group dl entries under sections with ids
- Use :target to highlight a linked term
- Prevent sticky headers from hiding anchors with scroll-margin-top

Elements and CSS used

HTML elements	CSS features
nav, a, section, h2, dl, dt, dd	position: sticky, :target, scroll-margin-top, place-items, flex-wrap

Build guide

1. Sort terms alphabetically and group by first letter.
2. Write one section per letter with an id and a dl.
3. Give each dt an id from its name.
4. Write the letter nav with fragment links.
5. Make the nav sticky.

6. Add scroll-margin-top so targets are not hidden under the nav; highlight :target.

Project 1039: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - Glossary</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Sahara Pet Care glossary</h1>
    <nav class="letters" aria-label="Jump to letter"><a href="#B">B</
a><a href="#D">D</a><a href="#F">F</a><a href="#V">V</a></nav>
    <section id="B">
      <h2>B</h2>
      <dl>
        <dt id="booking">Booking</dt><dd>Reserving a service in
advance..</dd>
      </dl>
    </section>
    <section id="D">
      <h2>D</h2>
      <dl>
        <dt id="day-boarding">Day boarding</dt><dd>Play and rest.</dd>
        <dt id="dog-walking">Dog walking</dt><dd>30 minutes.</dd>
      </dl>
    </section>
    <section id="F">
      <h2>F</h2>
      <dl>
        <dt id="full-grooming">Full grooming</dt><dd>Bath, cut and
nails.</dd>
      </dl>
    </section>
    <section id="V">
      <h2>V</h2>
      <dl>
        <dt id="vaccination">Vaccination</dt><dd>Annual boosters.</dd>
        <dt id="voucher">Voucher</dt><dd>A prepaid code exchangeable
for services..</dd>
      </dl>
    </section>
  </main>
</body>
</html>
```

Project 1039: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.letters { display: flex; gap: .4rem; flex-wrap: wrap; position:
sticky; top: 0; background: #fff; padding: .5rem 0; }
.letters a { width: 2rem; height: 2rem; display: grid; place-items:
center; border: 1px solid var(--line); border-radius: 6px; text-
decoration: none; color: var(--ink); }
h2 { color: var(--brand); border-bottom: 2px solid var(--accent);
scroll-margin-top: 4rem; }
dt { font-weight: 700; margin-top: .8rem; scroll-margin-top: 4rem; }
dt:target { background: #fff3b0; }
dd { margin: 0; color: var(--muted); }
```

Project 1039 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - Glossary</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Sahara Pet Care glossary	The main heading; only one per page.
<nav class="letters" aria-label="Jump to letter">B...	A block of navigation links; aria-label names it for screen readers.
<section id="B">	A thematic group of content, normally with its own heading.
B	Second-level heading for a section.
<dl>	Description list of term / description pairs.
<dt id="booking">Booking</dt><dd>Reserving a service in advance..</dd>	A term (name) in a description list.

Line	What it does
<dt id="day-boarding">Day boarding</dt><dd>Play and rest.</dd>	The description of the preceding term.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .4rem;	Space between grid or flex items without extra margins.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
background: #fff;	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
border-bottom: 2px solid var(--accent);	A bottom border used as a separator line.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.
font-weight: 700;	Thickness of the text.
dt:target {	Applies to the element whose id matches the URL fragment.

Check your work

- Letter links jump correctly
- Target term highlighted
- Headings not hidden under sticky bar
- dt/dd pairs valid

Exercises

1. Add a live filter input with JavaScript.
2. Link terms to each other with <a href="#term">.

3. Add <dfn> around each term.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 1040: Glossary with letter navigation for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Build an A-Z glossary using description lists grouped under letter headings, a sticky letter navigation and highlighted :target entries.

Learning goals

- Group dl entries under sections with ids
- Use :target to highlight a linked term
- Prevent sticky headers from hiding anchors with scroll-margin-top

Elements and CSS used

HTML elements	CSS features
nav, a, section, h2, dl, dt, dd	position: sticky, :target, scroll-margin-top, place-items, flex-wrap

Build guide

1. Sort terms alphabetically and group by first letter.
2. Write one section per letter with an id and a dl.
3. Give each dt an id from its name.
4. Write the letter nav with fragment links.
5. Make the nav sticky.

6. Add scroll-margin-top so targets are not hidden under the nav; highlight :target.

Project 1040: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - Glossary</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Alexandria Sailing School glossary</h1>
    <nav class="letters" aria-label="Jump to letter"><a href="#B">B</
a><a href="#P">P</a><a href="#R">R</a><a href="#T">T</a><a
href="#V">V</a></nav>
    <section id="B">
      <h2>B</h2>
      <dl>
        <dt id="beginner-course">Beginner course</dt><dd>Five
sessions.</dd>
        <dt id="booking">Booking</dt><dd>Reserving a lesson in
advance..</dd>
      </dl>
    </section>
    <section id="P">
      <h2>P</h2>
      <dl>
        <dt id="private-lesson">Private lesson</dt><dd>One to one.</
dd>
      </dl>
    </section>
    <section id="R">
      <h2>R</h2>
      <dl>
        <dt id="racing-clinic">Racing clinic</dt><dd>Tactics and trim.
</dd>
      </dl>
    </section>
    <section id="T">
      <h2>T</h2>
      <dl>
        <dt id="taster-session">Taster session</dt><dd>Two hours on
the water.</dd>
      </dl>
    </section>
    <section id="V">
      <h2>V</h2>
      <dl>
```

```
        <dt id="voucher">Voucher</dt><dd>A prepaid code exchangeable
for services..</dd>
      </dl>
    </section>
  </main>
</body>
</html>
```

Project 1040: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.letters { display: flex; gap: .4rem; flex-wrap: wrap; position:
sticky; top: 0; background: #fff; padding: .5rem 0; }
.letters a { width: 2rem; height: 2rem; display: grid; place-items:
center; border: 1px solid var(--line); border-radius: 6px; text-
decoration: none; color: var(--ink); }
h2 { color: var(--brand); border-bottom: 2px solid var(--accent);
scroll-margin-top: 4rem; }
dt { font-weight: 700; margin-top: .8rem; scroll-margin-top: 4rem; }
dt:target { background: #fff3b0; }
dd { margin: 0; color: var(--muted); }
```

Project 1040 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - Glossary</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Alexandria Sailing School glossary	The main heading; only one per page.
<nav class="letters" aria-label="Jump to letter">B...	A block of navigation links; aria-label names it for screen readers.
<section id="B">	A thematic group of content, normally with its own heading.
B	Second-level heading for a section.
<dl>	Description list of term / description pairs.
<dt id="beginner-course">Beginner course</dt><dd>Five sessions.</dd>	A term (name) in a description list.

Line	What it does
<dt id="booking">Booking</dt><dd>Reserving a lesson in advance..</dd>	The description of the preceding term.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .4rem;	Space between grid or flex items without extra margins.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
background: #fff;	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
border-bottom: 2px solid var(--accent);	A bottom border used as a separator line.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.
font-weight: 700;	Thickness of the text.
dt:target {	Applies to the element whose id matches the URL fragment.

Check your work

- Letter links jump correctly
- Target term highlighted
- Headings not hidden under sticky bar
- dt/dd pairs valid

Exercises

1. Add a live filter input with JavaScript.
2. Link terms to each other with <a href="#term">.

3. Add <dfn> around each term.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 1041: Glossary with letter navigation for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Build an A-Z glossary using description lists grouped under letter headings, a sticky letter navigation and highlighted :target entries.

Learning goals

- Group dl entries under sections with ids
- Use :target to highlight a linked term
- Prevent sticky headers from hiding anchors with scroll-margin-top

Elements and CSS used

HTML elements	CSS features
nav, a, section, h2, dl, dt, dd	position: sticky, :target, scroll-margin-top, place-items, flex-wrap

Build guide

1. Sort terms alphabetically and group by first letter.
2. Write one section per letter with an id and a dl.
3. Give each dt an id from its name.
4. Write the letter nav with fragment links.
5. Make the nav sticky.

6. Add scroll-margin-top so targets are not hidden under the nav; highlight :target.

Project 1041: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - Glossary</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Habiba Handmade Jewellery glossary</h1>
    <nav class="letters" aria-label="Jump to letter"><a href="#A">A</
a><a href="#B">B</a><a href="#L">L</a><a href="#V">V</a></nav>
    <section id="A">
      <h2>A</h2>
      <dl>
        <dt id="ankh-ring">Ankh ring</dt><dd>Adjustable.</dd>
      </dl>
    </section>
    <section id="B">
      <h2>B</h2>
      <dl>
        <dt id="bead-earrings">Bead earrings</dt><dd>Recycled glass.</
dd>
        <dt id="booking">Booking</dt><dd>Reserving a item in advance..
</dd>
        <dt id="brass-cuff">Brass cuff</dt><dd>Hand engraved.</dd>
      </dl>
    </section>
    <section id="L">
      <h2>L</h2>
      <dl>
        <dt id="lotus-pendant">Lotus pendant</dt><dd>Sterling silver.
</dd>
      </dl>
    </section>
    <section id="V">
      <h2>V</h2>
      <dl>
        <dt id="voucher">Voucher</dt><dd>A prepaid code exchangeable
for services..</dd>
      </dl>
    </section>
  </main>
</body>
</html>
```

Project 1041: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.letters { display: flex; gap: .4rem; flex-wrap: wrap; position:
sticky; top: 0; background: #fff; padding: .5rem 0; }
.letters a { width: 2rem; height: 2rem; display: grid; place-items:
center; border: 1px solid var(--line); border-radius: 6px; text-
decoration: none; color: var(--ink); }
h2 { color: var(--brand); border-bottom: 2px solid var(--accent);
scroll-margin-top: 4rem; }
dt { font-weight: 700; margin-top: .8rem; scroll-margin-top: 4rem; }
dt:target { background: #fff3b0; }
dd { margin: 0; color: var(--muted); }
```

Project 1041 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - Glossary</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Habiba Handmade Jewellery glossary	The main heading; only one per page.
<nav class="letters" aria-label="Jump to letter">A...	A block of navigation links; aria-label names it for screen readers.
<section id="A">	A thematic group of content, normally with its own heading.
A	Second-level heading for a section.
<dl>	Description list of term / description pairs.
<dt id="ankh-ring">Ankh ring </dt><dd>Adjustable.</dd>	A term (name) in a description list.

Line	What it does
<dt id="bead-earrings">Bead earrings</dt><dd>Recycled glass.</dd>	The description of the preceding term.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .4rem;	Space between grid or flex items without extra margins.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
background: #fff;	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
border-bottom: 2px solid var(--accent);	A bottom border used as a separator line.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.
font-weight: 700;	Thickness of the text.
dt:target {	Applies to the element whose id matches the URL fragment.

Check your work

- Letter links jump correctly
- Target term highlighted
- Headings not hidden under sticky bar
- dt/dd pairs valid

Exercises

1. Add a live filter input with JavaScript.
2. Link terms to each other with <a href="#term">.

3. Add <dfn> around each term.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 1042: Glossary with letter navigation for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 2 | Files: index.html, styles.css

Brief

Build an A-Z glossary using description lists grouped under letter headings, a sticky letter navigation and highlighted :target entries.

Learning goals

- Group dl entries under sections with ids
- Use :target to highlight a linked term
- Prevent sticky headers from hiding anchors with scroll-margin-top

Elements and CSS used

HTML elements	CSS features
nav, a, section, h2, dl, dt, dd	position: sticky, :target, scroll-margin-top, place-items, flex-wrap

Build guide

1. Sort terms alphabetically and group by first letter.
2. Write one section per letter with an id and a dl.
3. Give each dt an id from its name.
4. Write the letter nav with fragment links.
5. Make the nav sticky.

6. Add scroll-margin-top so targets are not hidden under the nav; highlight :target.

Project 1042: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - Glossary</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Fayoum Pottery Studio glossary</h1>
    <nav class="letters" aria-label="Jump to letter"><a href="#B">B</
a><a href="#G">G</a><a href="#I">I</a><a href="#K">K</a><a
href="#V">V</a><a href="#W">W</a></nav>
    <section id="B">
      <h2>B</h2>
      <dl>
        <dt id="booking">Booking</dt><dd>Reserving a workshop in
advance..</dd>
      </dl>
    </section>
    <section id="G">
      <h2>G</h2>
      <dl>
        <dt id="glazing-day">Glazing day</dt><dd>Colour your pieces.</
dd>
      </dl>
    </section>
    <section id="I">
      <h2>I</h2>
      <dl>
        <dt id="intro-to-the-wheel">Intro to the wheel</dt><dd>Three
hours, take home a bowl.</dd>
      </dl>
    </section>
    <section id="K">
      <h2>K</h2>
      <dl>
        <dt id="kids-clay-class">Kids clay class</dt><dd>Ages 6 to 12.
</dd>
      </dl>
    </section>
    <section id="V">
      <h2>V</h2>
      <dl>
        <dt id="voucher">Voucher</dt><dd>A prepaid code exchangeable
for services..</dd>
```

```
      </dl>
    </section>
    <section id="W">
      <h2>W</h2>
      <dl>
        <dt id="weekend-retreat">Weekend retreat</dt><dd>Two days
with meals.</dd>
      </dl>
    </section>
  </main>
</body>
</html>
```

Project 1042: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.letters { display: flex; gap: .4rem; flex-wrap: wrap; position:
sticky; top: 0; background: #fff; padding: .5rem 0; }
.letters a { width: 2rem; height: 2rem; display: grid; place-items:
center; border: 1px solid var(--line); border-radius: 6px; text-
decoration: none; color: var(--ink); }
h2 { color: var(--brand); border-bottom: 2px solid var(--accent);
scroll-margin-top: 4rem; }
dt { font-weight: 700; margin-top: .8rem; scroll-margin-top: 4rem; }
dt:target { background: #fff3b0; }
dd { margin: 0; color: var(--muted); }
```

Project 1042 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - Glossary</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Fayoum Pottery Studio glossary	The main heading; only one per page.
<nav class="letters" aria-label="Jump to letter">B...	A block of navigation links; aria-label names it for screen readers.
<section id="B">	A thematic group of content, normally with its own heading.
B	Second-level heading for a section.
<dl>	Description list of term / description pairs.
<dt id="booking">Booking</dt><dd>Reserving a workshop in advance..<...	A term (name) in a description list.

Line	What it does
<dt id="glazing-day">Glazing day</dt><dd>Colour your pieces.</dd>	The description of the preceding term.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .4rem;	Space between grid or flex items without extra margins.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
background: #fff;	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
border-bottom: 2px solid var(--accent);	A bottom border used as a separator line.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.
font-weight: 700;	Thickness of the text.
dt:target {	Applies to the element whose id matches the URL fragment.

Check your work

- Letter links jump correctly
- Target term highlighted
- Headings not hidden under sticky bar
- dt/dd pairs valid

Exercises

1. Add a live filter input with JavaScript.
2. Link terms to each other with <a href="#term">.

3. Add <dfn> around each term.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 1043: Glossary with letter navigation for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 2 | Files: index.html, styles.css

Brief

Build an A-Z glossary using description lists grouped under letter headings, a sticky letter navigation and highlighted :target entries.

Learning goals

- Group dl entries under sections with ids
- Use :target to highlight a linked term
- Prevent sticky headers from hiding anchors with scroll-margin-top

Elements and CSS used

HTML elements	CSS features
nav, a, section, h2, dl, dt, dd	position: sticky, :target, scroll-margin-top, place-items, flex-wrap

Build guide

1. Sort terms alphabetically and group by first letter.
2. Write one section per letter with an id and a dl.
3. Give each dt an id from its name.
4. Write the letter nav with fragment links.
5. Make the nav sticky.

6. Add scroll-margin-top so targets are not hidden under the nav; highlight :target.

Project 1043: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - Glossary</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Cleopatra Beauty Salon glossary</h1>
    <nav class="letters" aria-label="Jump to letter"><a href="#B">B</
a><a href="#F">F</a><a href="#H">H</a><a href="#M">M</a><a
href="#V">V</a></nav>
    <section id="B">
      <h2>B</h2>
      <dl>
        <dt id="booking">Booking</dt><dd>Reserving a treatment in
advance..</dd>
        <dt id="bridal-package">Bridal package</dt><dd>Hair, make-up
and nails.</dd>
      </dl>
    </section>
    <section id="F">
      <h2>F</h2>
      <dl>
        <dt id="facial">Facial</dt><dd>Deep cleanse, 60 minutes.</dd>
      </dl>
    </section>
    <section id="H">
      <h2>H</h2>
      <dl>
        <dt id="haircut-and-blow-dry">Haircut and blow-dry</
dt><dd>Consultation included.</dd>
      </dl>
    </section>
    <section id="M">
      <h2>M</h2>
      <dl>
        <dt id="manicure">Manicure</dt><dd>Classic or gel.</dd>
      </dl>
    </section>
    <section id="V">
      <h2>V</h2>
      <dl>
        <dt id="voucher">Voucher</dt><dd>A prepaid code exchangeable
for services..</dd>
```

```
      </dl>
    </section>
  </main>
</body>
</html>
```

Project 1043: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.letters { display: flex; gap: .4rem; flex-wrap: wrap; position:
sticky; top: 0; background: #fff; padding: .5rem 0; }
.letters a { width: 2rem; height: 2rem; display: grid; place-items:
center; border: 1px solid var(--line); border-radius: 6px; text-
decoration: none; color: var(--ink); }
h2 { color: var(--brand); border-bottom: 2px solid var(--accent);
scroll-margin-top: 4rem; }
dt { font-weight: 700; margin-top: .8rem; scroll-margin-top: 4rem; }
dt:target { background: #fff3b0; }
dd { margin: 0; color: var(--muted); }
```

Project 1043 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - Glossary</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Cleopatra Beauty Salon glossary	The main heading; only one per page.
<nav class="letters" aria-label="Jump to letter">B...	A block of navigation links; aria-label names it for screen readers.
<section id="B">	A thematic group of content, normally with its own heading.
B	Second-level heading for a section.
<dl>	Description list of term / description pairs.
<dt id="booking">Booking</dt><dd>Reserving a treatment in advance.....	A term (name) in a description list.

Line	What it does
<dt id="bridal-package">Bridal package</dt><dd>Hair, make-up and na...	The description of the preceding term.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .4rem;	Space between grid or flex items without extra margins.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
background: #fff;	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
border-bottom: 2px solid var(--accent);	A bottom border used as a separator line.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.
font-weight: 700;	Thickness of the text.
dt:target {	Applies to the element whose id matches the URL fragment.

Check your work

- Letter links jump correctly
- Target term highlighted
- Headings not hidden under sticky bar
- dt/dd pairs valid

Exercises

1. Add a live filter input with JavaScript.
2. Link terms to each other with <a href="#term">.

3. Add <dfn> around each term.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 1044: Glossary with letter navigation for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 2 | Files: index.html, styles.css

Brief

Build an A-Z glossary using description lists grouped under letter headings, a sticky letter navigation and highlighted :target entries.

Learning goals

- Group dl entries under sections with ids
- Use :target to highlight a linked term
- Prevent sticky headers from hiding anchors with scroll-margin-top

Elements and CSS used

HTML elements	CSS features
nav, a, section, h2, dl, dt, dd	position: sticky, :target, scroll-margin-top, place-items, flex-wrap

Build guide

1. Sort terms alphabetically and group by first letter.
2. Write one section per letter with an id and a dl.
3. Give each dt an id from its name.
4. Write the letter nav with fragment links.
5. Make the nav sticky.

6. Add scroll-margin-top so targets are not hidden under the nav; highlight :target.

Project 1044: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - Glossary</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Suez Auto Service glossary</h1>
    <nav class="letters" aria-label="Jump to letter"><a href="#A">A</
a><a href="#B">B</a><a href="#O">O</a><a href="#P">P</a><a
href="#V">V</a></nav>
    <section id="A">
      <h2>A</h2>
      <dl>
        <dt id="air-conditioning">Air conditioning</dt><dd>Recharge
and check.</dd>
      </dl>
    </section>
    <section id="B">
      <h2>B</h2>
      <dl>
        <dt id="booking">Booking</dt><dd>Reserving a service in
advance..</dd>
        <dt id="brake-pads">Brake pads</dt><dd>Front axle.</dd>
      </dl>
    </section>
    <section id="O">
      <h2>O</h2>
      <dl>
        <dt id="oil-change">Oil change</dt><dd>Filter included.</dd>
      </dl>
    </section>
    <section id="P">
      <h2>P</h2>
      <dl>
        <dt id="pre-purchase-inspection">Pre-purchase inspection</
dt><dd>120 point check.</dd>
      </dl>
    </section>
    <section id="V">
      <h2>V</h2>
      <dl>
        <dt id="voucher">Voucher</dt><dd>A prepaid code exchangeable
for services..</dd>
```

```
      </dl>
    </section>
  </main>
</body>
</html>
```

Project 1044: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.letters { display: flex; gap: .4rem; flex-wrap: wrap; position:
sticky; top: 0; background: #fff; padding: .5rem 0; }
.letters a { width: 2rem; height: 2rem; display: grid; place-items:
center; border: 1px solid var(--line); border-radius: 6px; text-
decoration: none; color: var(--ink); }
h2 { color: var(--brand); border-bottom: 2px solid var(--accent);
scroll-margin-top: 4rem; }
dt { font-weight: 700; margin-top: .8rem; scroll-margin-top: 4rem; }
dt:target { background: #fff3b0; }
dd { margin: 0; color: var(--muted); }
```

Project 1044 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - Glossary</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Suez Auto Service glossary	The main heading; only one per page.
<nav class="letters" aria-label="Jump to letter">A...	A block of navigation links; aria-label names it for screen readers.
<section id="A">	A thematic group of content, normally with its own heading.
A	Second-level heading for a section.
<dl>	Description list of term / description pairs.
<dt id="air-conditioning">Air conditioning</dt><dd>Recharge and che...	A term (name) in a description list.

Line	What it does
<dt id="booking">Booking</dt><dd>Reserving a service in advance..</dd>	The description of the preceding term.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .4rem;	Space between grid or flex items without extra margins.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
background: #fff;	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
border-bottom: 2px solid var(--accent);	A bottom border used as a separator line.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.
font-weight: 700;	Thickness of the text.
dt:target {	Applies to the element whose id matches the URL fragment.

Check your work

- Letter links jump correctly
- Target term highlighted
- Headings not hidden under sticky bar
- dt/dd pairs valid

Exercises

1. Add a live filter input with JavaScript.
2. Link terms to each other with <a href="#term">.

3. Add <dfn> around each term.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 1045: Glossary with letter navigation for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 2 | Files: index.html, styles.css

Brief

Build an A-Z glossary using description lists grouped under letter headings, a sticky letter navigation and highlighted :target entries.

Learning goals

- Group dl entries under sections with ids
- Use :target to highlight a linked term
- Prevent sticky headers from hiding anchors with scroll-margin-top

Elements and CSS used

HTML elements	CSS features
nav, a, section, h2, dl, dt, dd	position: sticky, :target, scroll-margin-top, place-items, flex-wrap

Build guide

1. Sort terms alphabetically and group by first letter.
2. Write one section per letter with an id and a dl.
3. Give each dt an id from its name.
4. Write the letter nav with fragment links.
5. Make the nav sticky.

6. Add scroll-margin-top so targets are not hidden under the nav; highlight :target.

Project 1045: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - Glossary</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Luxor Music Academy glossary</h1>
    <nav class="letters" aria-label="Jump to letter"><a href="#B">B</
a><a href="#G">G</a><a href="#O">O</a><a href="#P">P</a><a
href="#V">V</a></nav>
    <section id="B">
      <h2>B</h2>
      <dl>
        <dt id="booking">Booking</dt><dd>Reserving a course in
advance..</dd>
      </dl>
    </section>
    <section id="G">
      <h2>G</h2>
      <dl>
        <dt id="guitar-chords">Guitar chords</dt><dd>Play songs in a
month.</dd>
      </dl>
    </section>
    <section id="O">
      <h2>O</h2>
      <dl>
        <dt id="oud-for-beginners">Oud for beginners</dt><dd>Eight
weekly lessons.</dd>
      </dl>
    </section>
    <section id="P">
      <h2>P</h2>
      <dl>
        <dt id="piano-grade-1">Piano grade 1</dt><dd>Theory and
practice.</dd>
      </dl>
    </section>
    <section id="V">
      <h2>V</h2>
      <dl>
        <dt id="voice-coaching">Voice coaching</dt><dd>Breathing and
range.</dd>
```

```
        <dt id="voucher">Voucher</dt><dd>A prepaid code exchangeable
for services..</dd>
      </dl>
    </section>
  </main>
</body>
</html>
```

Project 1045: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.letters { display: flex; gap: .4rem; flex-wrap: wrap; position:
sticky; top: 0; background: #fff; padding: .5rem 0; }
.letters a { width: 2rem; height: 2rem; display: grid; place-items:
center; border: 1px solid var(--line); border-radius: 6px; text-
decoration: none; color: var(--ink); }
h2 { color: var(--brand); border-bottom: 2px solid var(--accent);
scroll-margin-top: 4rem; }
dt { font-weight: 700; margin-top: .8rem; scroll-margin-top: 4rem; }
dt:target { background: #fff3b0; }
dd { margin: 0; color: var(--muted); }
```

Project 1045 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - Glossary</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Luxor Music Academy glossary	The main heading; only one per page.
<nav class="letters" aria-label="Jump to letter">B...	A block of navigation links; aria-label names it for screen readers.
<section id="B">	A thematic group of content, normally with its own heading.
B	Second-level heading for a section.
<dl>	Description list of term / description pairs.
<dt id="booking">Booking</dt><dd>Reserving a course in advance..</dd>	A term (name) in a description list.

Line	What it does
<dt id="guitar-chords">Guitar chords</dt><dd>Play songs in a month....	The description of the preceding term.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .4rem;	Space between grid or flex items without extra margins.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
background: #fff;	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
border-bottom: 2px solid var(--accent);	A bottom border used as a separator line.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.
font-weight: 700;	Thickness of the text.
dt:target {	Applies to the element whose id matches the URL fragment.

Check your work

- Letter links jump correctly
- Target term highlighted
- Headings not hidden under sticky bar
- dt/dd pairs valid

Exercises

1. Add a live filter input with JavaScript.
2. Link terms to each other with <a href="#term">.

3. Add <dfn> around each term.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 1046: Glossary with letter navigation for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 2 | Files: index.html, styles.css

Brief

Build an A-Z glossary using description lists grouped under letter headings, a sticky letter navigation and highlighted :target entries.

Learning goals

- Group dl entries under sections with ids
- Use :target to highlight a linked term
- Prevent sticky headers from hiding anchors with scroll-margin-top

Elements and CSS used

HTML elements	CSS features
nav, a, section, h2, dl, dt, dd	position: sticky, :target, scroll-margin-top, place-items, flex-wrap

Build guide

1. Sort terms alphabetically and group by first letter.
2. Write one section per letter with an id and a dl.
3. Give each dt an id from its name.
4. Write the letter nav with fragment links.
5. Make the nav sticky.

6. Add scroll-margin-top so targets are not hidden under the nav; highlight :target.

Project 1046: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - Glossary</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Port Said Seafood glossary</h1>
    <nav class="letters" aria-label="Jump to letter"><a href="#B">B</
a><a href="#C">C</a><a href="#F">F</a><a href="#G">G</a><a
href="#S">S</a><a href="#V">V</a></nav>
    <section id="B">
      <h2>B</h2>
      <dl>
        <dt id="booking">Booking</dt><dd>Reserving a dish in advance..
</dd>
      </dl>
    </section>
    <section id="C">
      <h2>C</h2>
      <dl>
        <dt id="calamari">Calamari</dt><dd>Fried, with tahini.</dd>
      </dl>
    </section>
    <section id="F">
      <h2>F</h2>
      <dl>
        <dt id="fish-soup">Fish soup</dt><dd>Daily catch.</dd>
      </dl>
    </section>
    <section id="G">
      <h2>G</h2>
      <dl>
        <dt id="grilled-sea-bass">Grilled sea bass</dt><dd>With rice
and salad.</dd>
      </dl>
    </section>
    <section id="S">
      <h2>S</h2>
      <dl>
        <dt id="shrimp-tagine">Shrimp tagine</dt><dd>Tomato and
garlic.</dd>
      </dl>
    </section>
```

```
    <section id="V">
      <h2>V</h2>
      <dl>
        <dt id="voucher">Voucher</dt><dd>A prepaid code exchangeable
for services..</dd>
      </dl>
    </section>
  </main>
</body>
</html>
```

Project 1046: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.letters { display: flex; gap: .4rem; flex-wrap: wrap; position:
sticky; top: 0; background: #fff; padding: .5rem 0; }
.letters a { width: 2rem; height: 2rem; display: grid; place-items:
center; border: 1px solid var(--line); border-radius: 6px; text-
decoration: none; color: var(--ink); }
h2 { color: var(--brand); border-bottom: 2px solid var(--accent);
scroll-margin-top: 4rem; }
dt { font-weight: 700; margin-top: .8rem; scroll-margin-top: 4rem; }
dt:target { background: #fff3b0; }
dd { margin: 0; color: var(--muted); }
```

Project 1046 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - Glossary</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Port Said Seafood glossary	The main heading; only one per page.
<nav class="letters" aria-label="Jump to letter">B...	A block of navigation links; aria-label names it for screen readers.
<section id="B">	A thematic group of content, normally with its own heading.
B	Second-level heading for a section.
<dl>	Description list of term / description pairs.
<dt id="booking">Booking</dt><dd>Reserving a dish in advance..</dd>	A term (name) in a description list.

Line	What it does
<dt id="calamari">Calamari</dt><dd>Fried, with tahini.</dd>	The description of the preceding term.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .4rem;	Space between grid or flex items without extra margins.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
background: #fff;	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
border-bottom: 2px solid var(--accent);	A bottom border used as a separator line.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.
font-weight: 700;	Thickness of the text.
dt:target {	Applies to the element whose id matches the URL fragment.

Check your work

- Letter links jump correctly
- Target term highlighted
- Headings not hidden under sticky bar
- dt/dd pairs valid

Exercises

1. Add a live filter input with JavaScript.
2. Link terms to each other with <a href="#term">.

3. Add <dfn> around each term.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 1047: Glossary with letter navigation for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 2 | Files: index.html, styles.css

Brief

Build an A-Z glossary using description lists grouped under letter headings, a sticky letter navigation and highlighted :target entries.

Learning goals

- Group dl entries under sections with ids
- Use :target to highlight a linked term
- Prevent sticky headers from hiding anchors with scroll-margin-top

Elements and CSS used

HTML elements	CSS features
nav, a, section, h2, dl, dt, dd	position: sticky, :target, scroll-margin-top, place-items, flex-wrap

Build guide

1. Sort terms alphabetically and group by first letter.
2. Write one section per letter with an id and a dl.
3. Give each dt an id from its name.
4. Write the letter nav with fragment links.
5. Make the nav sticky.

6. Add scroll-margin-top so targets are not hidden under the nav; highlight :target.

Project 1047: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - Glossary</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Delta Kids Library glossary</h1>
    <nav class="letters" aria-label="Jump to letter"><a href="#B">B</
a><a href="#H">H</a><a href="#R">R</a><a href="#S">S</a><a
href="#V">V</a></nav>
    <section id="B">
      <h2>B</h2>
      <dl>
        <dt id="booking">Booking</dt><dd>Reserving a programme in
advance..</dd>
      </dl>
    </section>
    <section id="H">
      <h2>H</h2>
      <dl>
        <dt id="homework-help">Homework help</dt><dd>Weekday
afternoons.</dd>
      </dl>
    </section>
    <section id="R">
      <h2>R</h2>
      <dl>
        <dt id="reading-club">Reading club</dt><dd>Ages 7 to 11.</dd>
      </dl>
    </section>
    <section id="S">
      <h2>S</h2>
      <dl>
        <dt id="story-hour">Story hour</dt><dd>Ages 3 to 6, Saturdays.
</dd>
        <dt id="summer-challenge">Summer challenge</dt><dd>Read ten
books.</dd>
      </dl>
    </section>
    <section id="V">
      <h2>V</h2>
      <dl>
        <dt id="voucher">Voucher</dt><dd>A prepaid code exchangeable
```

```
for services..</dd>
      </dl>
    </section>
  </main>
</body>
</html>
```

Project 1047: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.letters { display: flex; gap: .4rem; flex-wrap: wrap; position:
sticky; top: 0; background: #fff; padding: .5rem 0; }
.letters a { width: 2rem; height: 2rem; display: grid; place-items:
center; border: 1px solid var(--line); border-radius: 6px; text-
decoration: none; color: var(--ink); }
h2 { color: var(--brand); border-bottom: 2px solid var(--accent);
scroll-margin-top: 4rem; }
dt { font-weight: 700; margin-top: .8rem; scroll-margin-top: 4rem; }
dt:target { background: #fff3b0; }
dd { margin: 0; color: var(--muted); }
```

Project 1047 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - Glossary</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Delta Kids Library glossary	The main heading; only one per page.
<nav class="letters" aria-label="Jump to letter">B...	A block of navigation links; aria-label names it for screen readers.
<section id="B">	A thematic group of content, normally with its own heading.
B	Second-level heading for a section.
<dl>	Description list of term / description pairs.
<dt id="booking">Booking</dt><dd>Reserving a programme in advance.....	A term (name) in a description list.

Line	What it does
<dt id="homework-help">Homework help</dt><dd>Weekday afternoons.</dd>	The description of the preceding term.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .4rem;	Space between grid or flex items without extra margins.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
background: #fff;	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
border-bottom: 2px solid var(--accent);	A bottom border used as a separator line.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.
font-weight: 700;	Thickness of the text.
dt:target {	Applies to the element whose id matches the URL fragment.

Check your work

- Letter links jump correctly
- Target term highlighted
- Headings not hidden under sticky bar
- dt/dd pairs valid

Exercises

1. Add a live filter input with JavaScript.
2. Link terms to each other with <a href="#term">.

3. Add <dfn> around each term.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 1048: Glossary with letter navigation for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Build an A-Z glossary using description lists grouped under letter headings, a sticky letter navigation and highlighted :target entries.

Learning goals

- Group dl entries under sections with ids
- Use :target to highlight a linked term
- Prevent sticky headers from hiding anchors with scroll-margin-top

Elements and CSS used

HTML elements	CSS features
nav, a, section, h2, dl, dt, dd	position: sticky, :target, scroll-margin-top, place-items, flex-wrap

Build guide

1. Sort terms alphabetically and group by first letter.
2. Write one section per letter with an id and a dl.
3. Give each dt an id from its name.
4. Write the letter nav with fragment links.
5. Make the nav sticky.

6. Add scroll-margin-top so targets are not hidden under the nav; highlight :target.

Project 1048: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - Glossary</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Nubian Guest House glossary</h1>
    <nav class="letters" aria-label="Jump to letter"><a href="#B">B</
a><a href="#F">F</a><a href="#G">G</a><a href="#N">N</a><a
href="#R">R</a><a href="#V">V</a></nav>
    <section id="B">
      <h2>B</h2>
      <dl>
        <dt id="booking">Booking</dt><dd>Reserving a room in advance..
</dd>
      </dl>
    </section>
    <section id="F">
      <h2>F</h2>
      <dl>
        <dt id="family-room">Family room</dt><dd>Sleeps four.</dd>
      </dl>
    </section>
    <section id="G">
      <h2>G</h2>
      <dl>
        <dt id="garden-room">Garden room</dt><dd>Double bed, shared
terrace.</dd>
      </dl>
    </section>
    <section id="N">
      <h2>N</h2>
      <dl>
        <dt id="nile-view-suite">Nile view suite</dt><dd>Balcony and
breakfast.</dd>
      </dl>
    </section>
    <section id="R">
      <h2>R</h2>
      <dl>
        <dt id="rooftop-dorm">Rooftop dorm</dt><dd>Budget beds.</dd>
      </dl>
    </section>
```

```
    <section id="V">
      <h2>V</h2>
      <dl>
        <dt id="voucher">Voucher</dt><dd>A prepaid code exchangeable
for services..</dd>
      </dl>
    </section>
  </main>
</body>
</html>
```

Project 1048: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.letters { display: flex; gap: .4rem; flex-wrap: wrap; position:
sticky; top: 0; background: #fff; padding: .5rem 0; }
.letters a { width: 2rem; height: 2rem; display: grid; place-items:
center; border: 1px solid var(--line); border-radius: 6px; text-
decoration: none; color: var(--ink); }
h2 { color: var(--brand); border-bottom: 2px solid var(--accent);
scroll-margin-top: 4rem; }
dt { font-weight: 700; margin-top: .8rem; scroll-margin-top: 4rem; }
dt:target { background: #fff3b0; }
dd { margin: 0; color: var(--muted); }
```

Project 1048 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - Glossary</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Nubian Guest House glossary	The main heading; only one per page.
<nav class="letters" aria-label="Jump to letter">B...	A block of navigation links; aria-label names it for screen readers.
<section id="B">	A thematic group of content, normally with its own heading.
B	Second-level heading for a section.
<dl>	Description list of term / description pairs.
<dt id="booking">Booking</dt><dd>Reserving a room in advance..</dd>	A term (name) in a description list.

Line	What it does
<dt id="family-room">Family room</dt><dd>Sleeps four.</dd>	The description of the preceding term.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .4rem;	Space between grid or flex items without extra margins.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
background: #fff;	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
border-bottom: 2px solid var(--accent);	A bottom border used as a separator line.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.
font-weight: 700;	Thickness of the text.
dt:target {	Applies to the element whose id matches the URL fragment.

Check your work

- Letter links jump correctly
- Target term highlighted
- Headings not hidden under sticky bar
- dt/dd pairs valid

Exercises

1. Add a live filter input with JavaScript.
2. Link terms to each other with <a href="#term">.

3. Add <dfn> around each term.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 1049: Glossary with letter navigation for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 2 | Files: index.html, styles.css

Brief

Build an A-Z glossary using description lists grouped under letter headings, a sticky letter navigation and highlighted :target entries.

Learning goals

- Group dl entries under sections with ids
- Use :target to highlight a linked term
- Prevent sticky headers from hiding anchors with scroll-margin-top

Elements and CSS used

HTML elements	CSS features
nav, a, section, h2, dl, dt, dd	position: sticky, :target, scroll-margin-top, place-items, flex-wrap

Build guide

1. Sort terms alphabetically and group by first letter.
2. Write one section per letter with an id and a dl.
3. Give each dt an id from its name.
4. Write the letter nav with fragment links.
5. Make the nav sticky.

6. Add scroll-margin-top so targets are not hidden under the nav; highlight :target.

Project 1049: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - Glossary</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Ismailia Cycling Store glossary</h1>
    <nav class="letters" aria-label="Jump to letter"><a href="#B">B</
a><a href="#C">C</a><a href="#K">K</a><a href="#M">M</a><a
href="#T">T</a><a href="#V">V</a></nav>
    <section id="B">
      <h2>B</h2>
      <dl>
        <dt id="booking">Booking</dt><dd>Reserving a bike in advance..
</dd>
      </dl>
    </section>
    <section id="C">
      <h2>C</h2>
      <dl>
        <dt id="city-bike">City bike</dt><dd>Seven gears, basket.</dd>
      </dl>
    </section>
    <section id="K">
      <h2>K</h2>
      <dl>
        <dt id="kids-bike">Kids bike</dt><dd>20 inch wheels.</dd>
      </dl>
    </section>
    <section id="M">
      <h2>M</h2>
      <dl>
        <dt id="mountain-bike">Mountain bike</dt><dd>Front suspension.
</dd>
      </dl>
    </section>
    <section id="T">
      <h2>T</h2>
      <dl>
        <dt id="tune-up">Tune-up</dt><dd>Brakes, gears and true
wheels.</dd>
      </dl>
    </section>
```

```
    <section id="V">
      <h2>V</h2>
      <dl>
        <dt id="voucher">Voucher</dt><dd>A prepaid code exchangeable
for services..</dd>
      </dl>
    </section>
  </main>
</body>
</html>
```

Project 1049: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.letters { display: flex; gap: .4rem; flex-wrap: wrap; position:
sticky; top: 0; background: #fff; padding: .5rem 0; }
.letters a { width: 2rem; height: 2rem; display: grid; place-items:
center; border: 1px solid var(--line); border-radius: 6px; text-
decoration: none; color: var(--ink); }
h2 { color: var(--brand); border-bottom: 2px solid var(--accent);
scroll-margin-top: 4rem; }
dt { font-weight: 700; margin-top: .8rem; scroll-margin-top: 4rem; }
dt:target { background: #fff3b0; }
dd { margin: 0; color: var(--muted); }
```

Project 1049 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - Glossary</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Ismailia Cycling Store glossary	The main heading; only one per page.
<nav class="letters" aria-label="Jump to letter">B...	A block of navigation links; aria-label names it for screen readers.
<section id="B">	A thematic group of content, normally with its own heading.
B	Second-level heading for a section.
<dl>	Description list of term / description pairs.
<dt id="booking">Booking</dt><dd>Reserving a bike in advance..</dd>	A term (name) in a description list.

Line	What it does
<dt id="city-bike">City bike</dt><dd>Seven gears, basket.</dd>	The description of the preceding term.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .4rem;	Space between grid or flex items without extra margins.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
background: #fff;	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
border-bottom: 2px solid var(--accent);	A bottom border used as a separator line.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.
font-weight: 700;	Thickness of the text.
dt:target {	Applies to the element whose id matches the URL fragment.

Check your work

- Letter links jump correctly
- Target term highlighted
- Headings not hidden under sticky bar
- dt/dd pairs valid

Exercises

1. Add a live filter input with JavaScript.
2. Link terms to each other with <a href="#term">.

3. Add <dfn> around each term.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 1050: Glossary with letter navigation for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 2 | Files: index.html, styles.css

Brief

Build an A-Z glossary using description lists grouped under letter headings, a sticky letter navigation and highlighted :target entries.

Learning goals

- Group dl entries under sections with ids
- Use :target to highlight a linked term
- Prevent sticky headers from hiding anchors with scroll-margin-top

Elements and CSS used

HTML elements	CSS features
nav, a, section, h2, dl, dt, dd	position: sticky, :target, scroll-margin-top, place-items, flex-wrap

Build guide

1. Sort terms alphabetically and group by first letter.
2. Write one section per letter with an id and a dl.
3. Give each dt an id from its name.
4. Write the letter nav with fragment links.
5. Make the nav sticky.

6. Add scroll-margin-top so targets are not hidden under the nav; highlight :target.

Project 1050: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - Glossary</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Minya Coding Club glossary</h1>
    <nav class="letters" aria-label="Jump to letter"><a href="#B">B</
a><a href="#C">C</a><a href="#H">H</a><a href="#S">S</a><a
href="#V">V</a></nav>
    <section id="B">
      <h2>B</h2>
      <dl>
        <dt id="booking">Booking</dt><dd>Reserving a workshop in
advance..</dd>
      </dl>
    </section>
    <section id="C">
      <h2>C</h2>
      <dl>
        <dt id="css-art">CSS art</dt><dd>Draw with code.</dd>
      </dl>
    </section>
    <section id="H">
      <h2>H</h2>
      <dl>
        <dt id="html-weekend">HTML weekend</dt><dd>Build your first
page.</dd>
        <dt id="hackathon">Hackathon</dt><dd>48 hours, teams of four.
</dd>
      </dl>
    </section>
    <section id="S">
      <h2>S</h2>
      <dl>
        <dt id="scratch-games">Scratch games</dt><dd>Ages 10 to 13.</
dd>
      </dl>
    </section>
    <section id="V">
      <h2>V</h2>
      <dl>
        <dt id="voucher">Voucher</dt><dd>A prepaid code exchangeable
```

```
for services..</dd>
      </dl>
    </section>
  </main>
</body>
</html>
```

Project 1050: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.letters { display: flex; gap: .4rem; flex-wrap: wrap; position:
sticky; top: 0; background: #fff; padding: .5rem 0; }
.letters a { width: 2rem; height: 2rem; display: grid; place-items:
center; border: 1px solid var(--line); border-radius: 6px; text-
decoration: none; color: var(--ink); }
h2 { color: var(--brand); border-bottom: 2px solid var(--accent);
scroll-margin-top: 4rem; }
dt { font-weight: 700; margin-top: .8rem; scroll-margin-top: 4rem; }
dt:target { background: #fff3b0; }
dd { margin: 0; color: var(--muted); }
```

Project 1050 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - Glossary</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Minya Coding Club glossary	The main heading; only one per page.
<nav class="letters" aria-label="Jump to letter">B...	A block of navigation links; aria-label names it for screen readers.
<section id="B">	A thematic group of content, normally with its own heading.
B	Second-level heading for a section.
<dl>	Description list of term / description pairs.
<dt id="booking">Booking</dt><dd>Reserving a workshop in advance..<...	A term (name) in a description list.

Line	What it does
<dt id="css-art">CSS art</dt><dd>Draw with code.</dd>	The description of the preceding term.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
display: flex;	Turns the element into a flex container (one-dimensional layout).
gap: .4rem;	Space between grid or flex items without extra margins.

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
background: #fff;	Background colour or image.
display: grid;	Turns the element into a grid container.
place-items: center;	Centres items horizontally and vertically in a grid.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 6px;	Rounds the corners.
text-decoration: none;	Removes the underline from links.
border-bottom: 2px solid var(--accent);	A bottom border used as a separator line.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.
font-weight: 700;	Thickness of the text.
dt:target {	Applies to the element whose id matches the URL fragment.

Check your work

- Letter links jump correctly
- Target term highlighted
- Headings not hidden under sticky bar
- dt/dd pairs valid

Exercises

1. Add a live filter input with JavaScript.
2. Link terms to each other with <a href="#term">.

3. Add <dfn> around each term.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Pricing plans comparison

Level 2 | 25 projects, one per theme

Present three packages side by side with a highlighted, slightly enlarged middle plan, a 'most popular' ribbon and tick/cross feature lists.

Project 1051: Pricing plans comparison for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 2 | Files: index.html, styles.css

Brief

Present three packages side by side with a highlighted, slightly enlarged middle plan, a 'most popular' ribbon and tick/cross feature lists.

Learning goals

- Emphasise one card with transform: scale and a border
- Position a ribbon over the card edge
- Use ::before glyphs for ticks and crosses

Elements and CSS used

HTML elements	CSS features
section, h2, p, ul, li, a	transform: scale(), position: absolute + translate, align-items: start, ::before content, box-shadow

Build guide

1. Write three .plan sections; give the middle one the featured class and a ribbon p.
2. Grid the plans and align them to the start.
3. Scale the featured plan and add a shadow.
4. Position the ribbon at the top centre.
5. Add ticks with ::before; crosses for .no items.
6. Style the buttons.

Project 1051: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Compare plans</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Compare our packages</h1>
    <div class="plans">
      <section class="plan">
        <h2>Basic</h2>
        <p class="price">120 EGP</p>
        <ul><li>One book</li><li>Email support</li><li class="no">No
priority booking</li></ul>
        <a class="btn" href="#">Choose Basic</a>
      </section>
      <section class="plan featured">
        <p class="ribbon">Most popular</p>
        <h2>Standard</h2>
        <p class="price">150 EGP</p>
        <ul><li>Three books</li><li>Phone support</li><li>Priority
booking</li></ul>
        <a class="btn" href="#">Choose Standard</a>
      </section>
      <section class="plan">
        <h2>Premium</h2>
        <p class="price">95 EGP</p>
        <ul><li>Unlimited books</li><li>Personal advisor</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Premium</a>
      </section>
    </div>
  </main>
</body>
</html>
```

Project 1051: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; text-
```

```
align: center; }
.plans { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(15rem, 1fr)); align-items: start; }
.plan { position: relative; border: 1px solid var(--line); border-
radius: 16px; padding: 2rem 1.5rem; background: #fff; }
.featured { border: 2px solid var(--brand); transform: scale(1.04);
box-shadow: 0 16px 40px rgb(0 0 0 / 12%); }
.ribbon { position: absolute; top: -.8rem; left: 50%; translate: -50%
0; background: var(--brand); color: #fff; font-size: .75rem; padding:
.2rem .8rem; border-radius: 999px; margin: 0; }
.price { font-size: 2rem; font-weight: 800; margin: .5rem 0 1rem; }
ul { list-style: none; padding: 0; text-align: left; }
li { padding: .4rem 0; border-bottom: 1px solid var(--accent); }
li::before { content: "\2713 "; color: var(--brand); }
li.no { color: var(--muted); }
li.no::before { content: "\2717 "; color: #999; }
.btn { display: block; margin-top: 1.5rem; padding: .7rem; border-
radius: 999px; background: var(--brand); color: #fff; text-decoration:
 none; }
```

Project 1051 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - Compare plans</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Compare our packages	The main heading; only one per page.
	Generic block container for grouping and layout.
<section class="plan">	A thematic group of content, normally with its own heading.
Basic	Second-level heading for a section.
120 EGP	A paragraph of text.
- One book - Email support <li class="no">No priori...	Unordered (bulleted) list.

Line	What it does
Choose Basic	A link styled as a button; it navigates, so it is a link and not a <button>.
- Three books - Phone support - Priority booking<...	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(15rem, 1fr));	Defines the columns of the grid.
align-items: start;	Aligns items to the start of the cross axis (no stretching).
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 16px;	Rounds the corners.
background: #fff;	Background colour or image.
border: 2px solid var(--brand);	The line around the element: width, style and colour.
transform: scale(1.04);	Enlarges or shrinks the element visually.
box-shadow: 0 16px 40px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
font-size: .75rem;	Size of the text.
border-radius: 999px;	Fully rounded pill shape.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--accent);	A bottom border used as a separator line.

Declaration	What it does
content: "\2713 ";	The text or empty string for a pseudo-element.
display: block;	Element starts on a new line and fills the width (used on links and images).
text-decoration: none;	Removes the underline from links.

Check your work

- Ribbon centred
- Scaled card does not overlap on narrow screens (stacking)
- Features left-aligned
- Prices large and clear

Exercises

1. Add a monthly/yearly toggle with :checked.
2. Convert to a comparison table for many features.
3. Animate the featured card on hover.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 1052: Pricing plans comparison for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 2 | Files: index.html, styles.css

Brief

Present three packages side by side with a highlighted, slightly enlarged middle plan, a 'most popular' ribbon and tick/cross feature lists.

Learning goals

- Emphasise one card with transform: scale and a border
- Position a ribbon over the card edge
- Use ::before glyphs for ticks and crosses

Elements and CSS used

HTML elements	CSS features
section, h2, p, ul, li, a	transform: scale(), position: absolute + translate, align-items: start, ::before content, box-shadow

Build guide

1. Write three .plan sections; give the middle one the featured class and a ribbon p.
2. Grid the plans and align them to the start.
3. Scale the featured plan and add a shadow.
4. Position the ribbon at the top centre.
5. Add ticks with ::before; crosses for .no items.
6. Style the buttons.

Project 1052: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - Compare plans</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Compare our packages</h1>
    <div class="plans">
      <section class="plan">
        <h2>Basic</h2>
        <p class="price">60 EGP</p>
        <ul><li>One pastry</li><li>Email support</li><li
class="no">No priority booking</li></ul>
        <a class="btn" href="#">Choose Basic</a>
      </section>
      <section class="plan featured">
        <p class="ribbon">Most popular</p>
        <h2>Standard</h2>
        <p class="price">35 EGP</p>
        <ul><li>Three pastries</li><li>Phone support</li><li>Priority
booking</li></ul>
        <a class="btn" href="#">Choose Standard</a>
      </section>
      <section class="plan">
        <h2>Premium</h2>
        <p class="price">220 EGP</p>
        <ul><li>Unlimited pastries</li><li>Personal advisor</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Premium</a>
      </section>
    </div>
  </main>
</body>
</html>
```

Project 1052: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; text-
```

```
align: center; }
.plans { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(15rem, 1fr)); align-items: start; }
.plan { position: relative; border: 1px solid var(--line); border-
radius: 16px; padding: 2rem 1.5rem; background: #fff; }
.featured { border: 2px solid var(--brand); transform: scale(1.04);
box-shadow: 0 16px 40px rgb(0 0 0 / 12%); }
.ribbon { position: absolute; top: -.8rem; left: 50%; translate: -50%
0; background: var(--brand); color: #fff; font-size: .75rem; padding:
.2rem .8rem; border-radius: 999px; margin: 0; }
.price { font-size: 2rem; font-weight: 800; margin: .5rem 0 1rem; }
ul { list-style: none; padding: 0; text-align: left; }
li { padding: .4rem 0; border-bottom: 1px solid var(--accent); }
li::before { content: "\2713 "; color: var(--brand); }
li.no { color: var(--muted); }
li.no::before { content: "\2717 "; color: #999; }
.btn { display: block; margin-top: 1.5rem; padding: .7rem; border-
radius: 999px; background: var(--brand); color: #fff; text-decoration:
 none; }
```

Project 1052 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - Compare plans</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Compare our packages	The main heading; only one per page.
	Generic block container for grouping and layout.
<section class="plan">	A thematic group of content, normally with its own heading.
Basic	Second-level heading for a section.
60 EGP	A paragraph of text.
- One pastry - Email support <li class="no">No prio...	Unordered (bulleted) list.

Line	What it does
Choose Basic	A link styled as a button; it navigates, so it is a link and not a <button>.
- Three pastries - Phone support - Priority booki...	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(15rem, 1fr));	Defines the columns of the grid.
align-items: start;	Aligns items to the start of the cross axis (no stretching).
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 16px;	Rounds the corners.
background: #fff;	Background colour or image.
border: 2px solid var(--brand);	The line around the element: width, style and colour.
transform: scale(1.04);	Enlarges or shrinks the element visually.
box-shadow: 0 16px 40px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
font-size: .75rem;	Size of the text.
border-radius: 999px;	Fully rounded pill shape.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--accent);	A bottom border used as a separator line.

Declaration	What it does
content: "\2713 ";	The text or empty string for a pseudo-element.
display: block;	Element starts on a new line and fills the width (used on links and images).
text-decoration: none;	Removes the underline from links.

Check your work

- Ribbon centred
- Scaled card does not overlap on narrow screens (stacking)
- Features left-aligned
- Prices large and clear

Exercises

1. Add a monthly/yearly toggle with :checked.
2. Convert to a comparison table for many features.
3. Animate the featured card on hover.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 1053: Pricing plans comparison for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 2 | Files: index.html, styles.css

Brief

Present three packages side by side with a highlighted, slightly enlarged middle plan, a 'most popular' ribbon and tick/cross feature lists.

Learning goals

- Emphasise one card with transform: scale and a border
- Position a ribbon over the card edge
- Use ::before glyphs for ticks and crosses

Elements and CSS used

HTML elements	CSS features
section, h2, p, ul, li, a	transform: scale(), position: absolute + translate, align-items: start, ::before content, box-shadow

Build guide

1. Write three .plan sections; give the middle one the featured class and a ribbon p.
2. Grid the plans and align them to the start.
3. Scale the featured plan and add a shadow.
4. Position the ribbon at the top centre.
5. Add ticks with ::before; crosses for .no items.

6. Style the buttons.

Project 1053: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - Compare plans</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Compare our packages</h1>
    <div class="plans">
      <section class="plan">
        <h2>Basic</h2>
        <p class="price">100 EGP</p>
        <ul><li>One class</li><li>Email support</li><li class="no">No
priority booking</li></ul>
        <a class="btn" href="#">Choose Basic</a>
      </section>
      <section class="plan featured">
        <p class="ribbon">Most popular</p>
        <h2>Standard</h2>
        <p class="price">120 EGP</p>
        <ul><li>Three classes</li><li>Phone support</li><li>Priority
booking</li></ul>
        <a class="btn" href="#">Choose Standard</a>
      </section>
      <section class="plan">
        <h2>Premium</h2>
        <p class="price">350 EGP</p>
        <ul><li>Unlimited classes</li><li>Personal advisor</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Premium</a>
      </section>
    </div>
  </main>
</body>
</html>
```

Project 1053: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; text-
```

```
align: center; }
.plans { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(15rem, 1fr)); align-items: start; }
.plan { position: relative; border: 1px solid var(--line); border-
radius: 16px; padding: 2rem 1.5rem; background: #fff; }
.featured { border: 2px solid var(--brand); transform: scale(1.04);
box-shadow: 0 16px 40px rgb(0 0 0 / 12%); }
.ribbon { position: absolute; top: -.8rem; left: 50%; translate: -50%
0; background: var(--brand); color: #fff; font-size: .75rem; padding:
.2rem .8rem; border-radius: 999px; margin: 0; }
.price { font-size: 2rem; font-weight: 800; margin: .5rem 0 1rem; }
ul { list-style: none; padding: 0; text-align: left; }
li { padding: .4rem 0; border-bottom: 1px solid var(--accent); }
li::before { content: "\2713 "; color: var(--brand); }
li.no { color: var(--muted); }
li.no::before { content: "\2717 "; color: #999; }
.btn { display: block; margin-top: 1.5rem; padding: .7rem; border-
radius: 999px; background: var(--brand); color: #fff; text-decoration:
 none; }
```

Project 1053 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - Compare plans</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Compare our packages	The main heading; only one per page.
	Generic block container for grouping and layout.
<section class="plan">	A thematic group of content, normally with its own heading.
Basic	Second-level heading for a section.
100 EGP	A paragraph of text.
- One class - Email support <li class="no">No prior…	Unordered (bulleted) list.

Line	What it does
Choose Basic	A link styled as a button; it navigates, so it is a link and not a <button>.
- Three classes - Phone support - Priority bookin...	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(15rem, 1fr));	Defines the columns of the grid.
align-items: start;	Aligns items to the start of the cross axis (no stretching).
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 16px;	Rounds the corners.
background: #fff;	Background colour or image.
border: 2px solid var(--brand);	The line around the element: width, style and colour.
transform: scale(1.04);	Enlarges or shrinks the element visually.
box-shadow: 0 16px 40px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
font-size: .75rem;	Size of the text.
border-radius: 999px;	Fully rounded pill shape.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--accent);	A bottom border used as a separator line.

Declaration	What it does
content: "\2713 ";	The text or empty string for a pseudo-element.
display: block;	Element starts on a new line and fills the width (used on links and images).
text-decoration: none;	Removes the underline from links.

Check your work

- Ribbon centred
- Scaled card does not overlap on narrow screens (stacking)
- Features left-aligned
- Prices large and clear

Exercises

1. Add a monthly/yearly toggle with :checked.
2. Convert to a comparison table for many features.
3. Animate the featured card on hover.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 1054: Pricing plans comparison for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 2 | Files: index.html, styles.css

Brief

Present three packages side by side with a highlighted, slightly enlarged middle plan, a 'most popular' ribbon and tick/cross feature lists.

Learning goals

- Emphasise one card with transform: scale and a border
- Position a ribbon over the card edge
- Use ::before glyphs for ticks and crosses

Elements and CSS used

HTML elements	CSS features
section, h2, p, ul, li, a	transform: scale(), position: absolute + translate, align-items: start, ::before content, box-shadow

Build guide

1. Write three .plan sections; give the middle one the featured class and a ribbon p.
2. Grid the plans and align them to the start.
3. Scale the featured plan and add a shadow.
4. Position the ribbon at the top centre.
5. Add ticks with ::before; crosses for .no items.
6. Style the buttons.

Project 1054: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - Compare plans</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Compare our packages</h1>
    <div class="plans">
      <section class="plan">
        <h2>Basic</h2>
        <p class="price">300 EGP</p>
        <ul><li>One service</li><li>Email support</li><li
class="no">No priority booking</li></ul>
        <a class="btn" href="#">Choose Basic</a>
      </section>
      <section class="plan featured">
        <p class="ribbon">Most popular</p>
        <h2>Standard</h2>
        <p class="price">1500 EGP</p>
        <ul><li>Three services</li><li>Phone support</li><li>Priority
booking</li></ul>
        <a class="btn" href="#">Choose Standard</a>
      </section>
      <section class="plan">
        <h2>Premium</h2>
        <p class="price">Free</p>
        <ul><li>Unlimited services</li><li>Personal advisor</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Premium</a>
      </section>
    </div>
  </main>
</body>
</html>
```

Project 1054: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; text-
```

```
align: center; }
.plans { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(15rem, 1fr)); align-items: start; }
.plan { position: relative; border: 1px solid var(--line); border-
radius: 16px; padding: 2rem 1.5rem; background: #fff; }
.featured { border: 2px solid var(--brand); transform: scale(1.04);
box-shadow: 0 16px 40px rgb(0 0 0 / 12%); }
.ribbon { position: absolute; top: -.8rem; left: 50%; translate: -50%
0; background: var(--brand); color: #fff; font-size: .75rem; padding:
.2rem .8rem; border-radius: 999px; margin: 0; }
.price { font-size: 2rem; font-weight: 800; margin: .5rem 0 1rem; }
ul { list-style: none; padding: 0; text-align: left; }
li { padding: .4rem 0; border-bottom: 1px solid var(--accent); }
li::before { content: "\2713 "; color: var(--brand); }
li.no { color: var(--muted); }
li.no::before { content: "\2717 "; color: #999; }
.btn { display: block; margin-top: 1.5rem; padding: .7rem; border-
radius: 999px; background: var(--brand); color: #fff; text-decoration:
 none; }
```

Project 1054 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - Compare plans</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Compare our packages	The main heading; only one per page.
	Generic block container for grouping and layout.
<section class="plan">	A thematic group of content, normally with its own heading.
Basic	Second-level heading for a section.
300 EGP	A paragraph of text.
- One service - Email support <li class="no">No pri...	Unordered (bulleted) list.

Line	What it does
Choose Basic	A link styled as a button; it navigates, so it is a link and not a <button>.
- Three services - Phone support - Priority booki...	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(15rem, 1fr));	Defines the columns of the grid.
align-items: start;	Aligns items to the start of the cross axis (no stretching).
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 16px;	Rounds the corners.
background: #fff;	Background colour or image.
border: 2px solid var(--brand);	The line around the element: width, style and colour.
transform: scale(1.04);	Enlarges or shrinks the element visually.
box-shadow: 0 16px 40px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
font-size: .75rem;	Size of the text.
border-radius: 999px;	Fully rounded pill shape.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--accent);	A bottom border used as a separator line.

Declaration	What it does
content: "\2713 ";	The text or empty string for a pseudo-element.
display: block;	Element starts on a new line and fills the width (used on links and images).
text-decoration: none;	Removes the underline from links.

Check your work

- Ribbon centred
- Scaled card does not overlap on narrow screens (stacking)
- Features left-aligned
- Prices large and clear

Exercises

1. Add a monthly/yearly toggle with :checked.
2. Convert to a comparison table for many features.
3. Animate the featured card on hover.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 1055: Pricing plans comparison for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 2 | Files: index.html, styles.css

Brief

Present three packages side by side with a highlighted, slightly enlarged middle plan, a 'most popular' ribbon and tick/cross feature lists.

Learning goals

- Emphasise one card with transform: scale and a border
- Position a ribbon over the card edge
- Use ::before glyphs for ticks and crosses

Elements and CSS used

HTML elements	CSS features
section, h2, p, ul, li, a	transform: scale(), position: absolute + translate, align-items: start, ::before content, box-shadow

Build guide

1. Write three .plan sections; give the middle one the featured class and a ribbon p.
2. Grid the plans and align them to the start.
3. Scale the featured plan and add a shadow.
4. Position the ribbon at the top centre.
5. Add ticks with ::before; crosses for .no items.
6. Style the buttons.

Project 1055: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - Compare plans</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Compare our packages</h1>
    <div class="plans">
      <section class="plan">
        <h2>Basic</h2>
        <p class="price">1200 EGP</p>
        <ul><li>One tour</li><li>Email support</li><li class="no">No
priority booking</li></ul>
        <a class="btn" href="#">Choose Basic</a>
      </section>
      <section class="plan featured">
        <p class="ribbon">Most popular</p>
        <h2>Standard</h2>
        <p class="price">700 EGP</p>
        <ul><li>Three tours</li><li>Phone support</li><li>Priority
booking</li></ul>
        <a class="btn" href="#">Choose Standard</a>
      </section>
      <section class="plan">
        <h2>Premium</h2>
        <p class="price">6500 EGP</p>
        <ul><li>Unlimited tours</li><li>Personal advisor</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Premium</a>
      </section>
    </div>
  </main>
</body>
</html>
```

Project 1055: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; text-
```

```
align: center; }
.plans { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(15rem, 1fr)); align-items: start; }
.plan { position: relative; border: 1px solid var(--line); border-
radius: 16px; padding: 2rem 1.5rem; background: #fff; }
.featured { border: 2px solid var(--brand); transform: scale(1.04);
box-shadow: 0 16px 40px rgb(0 0 0 / 12%); }
.ribbon { position: absolute; top: -.8rem; left: 50%; translate: -50%
0; background: var(--brand); color: #fff; font-size: .75rem; padding:
.2rem .8rem; border-radius: 999px; margin: 0; }
.price { font-size: 2rem; font-weight: 800; margin: .5rem 0 1rem; }
ul { list-style: none; padding: 0; text-align: left; }
li { padding: .4rem 0; border-bottom: 1px solid var(--accent); }
li::before { content: "\2713 "; color: var(--brand); }
li.no { color: var(--muted); }
li.no::before { content: "\2717 "; color: #999; }
.btn { display: block; margin-top: 1.5rem; padding: .7rem; border-
radius: 999px; background: var(--brand); color: #fff; text-decoration:
 none; }
```

Project 1055 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - Compare plans</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Compare our packages	The main heading; only one per page.
	Generic block container for grouping and layout.
<section class="plan">	A thematic group of content, normally with its own heading.
Basic	Second-level heading for a section.
1200 EGP	A paragraph of text.
- One tour - Email support <li class="no">No priori...	Unordered (bulleted) list.

Line	What it does
Choose Basic	A link styled as a button; it navigates, so it is a link and not a <button>.
- Three tours - Phone support - Priority booking<...	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(15rem, 1fr));	Defines the columns of the grid.
align-items: start;	Aligns items to the start of the cross axis (no stretching).
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 16px;	Rounds the corners.
background: #fff;	Background colour or image.
border: 2px solid var(--brand);	The line around the element: width, style and colour.
transform: scale(1.04);	Enlarges or shrinks the element visually.
box-shadow: 0 16px 40px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
font-size: .75rem;	Size of the text.
border-radius: 999px;	Fully rounded pill shape.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--accent);	A bottom border used as a separator line.

Declaration	What it does
content: "\2713 ";	The text or empty string for a pseudo-element.
display: block;	Element starts on a new line and fills the width (used on links and images).
text-decoration: none;	Removes the underline from links.

Check your work

- Ribbon centred
- Scaled card does not overlap on narrow screens (stacking)
- Features left-aligned
- Prices large and clear

Exercises

1. Add a monthly/yearly toggle with :checked.
2. Convert to a comparison table for many features.
3. Animate the featured card on hover.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 1056: Pricing plans comparison for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Present three packages side by side with a highlighted, slightly enlarged middle plan, a 'most popular' ribbon and tick/cross feature lists.

Learning goals

- Emphasise one card with transform: scale and a border
- Position a ribbon over the card edge
- Use ::before glyphs for ticks and crosses

Elements and CSS used

HTML elements	CSS features
section, h2, p, ul, li, a	transform: scale(), position: absolute + translate, align-items: start, ::before content, box-shadow

Build guide

1. Write three .plan sections; give the middle one the featured class and a ribbon p.
2. Grid the plans and align them to the start.
3. Scale the featured plan and add a shadow.
4. Position the ribbon at the top centre.
5. Add ticks with ::before; crosses for .no items.

6. Style the buttons.

Project 1056: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - Compare plans</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Compare our packages</h1>
    <div class="plans">
      <section class="plan">
        <h2>Basic</h2>
        <p class="price">1800 EGP</p>
        <ul><li>One course</li><li>Email support</li><li
class="no">No priority booking</li></ul>
        <a class="btn" href="#">Choose Basic</a>
      </section>
      <section class="plan featured">
        <p class="ribbon">Most popular</p>
        <h2>Standard</h2>
        <p class="price">2200 EGP</p>
        <ul><li>Three courses</li><li>Phone support</li><li>Priority
booking</li></ul>
        <a class="btn" href="#">Choose Standard</a>
      </section>
      <section class="plan">
        <h2>Premium</h2>
        <p class="price">3000 EGP</p>
        <ul><li>Unlimited courses</li><li>Personal advisor</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Premium</a>
      </section>
    </div>
  </main>
</body>
</html>
```

Project 1056: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; text-
```

```
align: center; }
.plans { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(15rem, 1fr)); align-items: start; }
.plan { position: relative; border: 1px solid var(--line); border-
radius: 16px; padding: 2rem 1.5rem; background: #fff; }
.featured { border: 2px solid var(--brand); transform: scale(1.04);
box-shadow: 0 16px 40px rgb(0 0 0 / 12%); }
.ribbon { position: absolute; top: -.8rem; left: 50%; translate: -50%
0; background: var(--brand); color: #fff; font-size: .75rem; padding:
.2rem .8rem; border-radius: 999px; margin: 0; }
.price { font-size: 2rem; font-weight: 800; margin: .5rem 0 1rem; }
ul { list-style: none; padding: 0; text-align: left; }
li { padding: .4rem 0; border-bottom: 1px solid var(--accent); }
li::before { content: "\2713 "; color: var(--brand); }
li.no { color: var(--muted); }
li.no::before { content: "\2717 "; color: #999; }
.btn { display: block; margin-top: 1.5rem; padding: .7rem; border-
radius: 999px; background: var(--brand); color: #fff; text-decoration:
 none; }
```

Project 1056 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - Compare plans</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Compare our packages	The main heading; only one per page.
	Generic block container for grouping and layout.
<section class="plan">	A thematic group of content, normally with its own heading.
Basic	Second-level heading for a section.
1800 EGP	A paragraph of text.
- One course - Email support <li class="no">No prio...	Unordered (bulleted) list.

Line	What it does
Choose Basic	A link styled as a button; it navigates, so it is a link and not a <button>.
- Three courses - Phone support - Priority bookin...	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(15rem, 1fr));	Defines the columns of the grid.
align-items: start;	Aligns items to the start of the cross axis (no stretching).
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 16px;	Rounds the corners.
background: #fff;	Background colour or image.
border: 2px solid var(--brand);	The line around the element: width, style and colour.
transform: scale(1.04);	Enlarges or shrinks the element visually.
box-shadow: 0 16px 40px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
font-size: .75rem;	Size of the text.
border-radius: 999px;	Fully rounded pill shape.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--accent);	A bottom border used as a separator line.

Declaration	What it does
content: "\2713 ";	The text or empty string for a pseudo-element.
display: block;	Element starts on a new line and fills the width (used on links and images).
text-decoration: none;	Removes the underline from links.

Check your work

- Ribbon centred
- Scaled card does not overlap on narrow screens (stacking)
- Features left-aligned
- Prices large and clear

Exercises

1. Add a monthly/yearly toggle with :checked.
2. Convert to a comparison table for many features.
3. Animate the featured card on hover.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 1057: Pricing plans comparison for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 2 | Files: index.html, styles.css

Brief

Present three packages side by side with a highlighted, slightly enlarged middle plan, a 'most popular' ribbon and tick/cross feature lists.

Learning goals

- Emphasise one card with transform: scale and a border
- Position a ribbon over the card edge
- Use ::before glyphs for ticks and crosses

Elements and CSS used

HTML elements	CSS features
section, h2, p, ul, li, a	transform: scale(), position: absolute + translate, align-items: start, ::before content, box-shadow

Build guide

1. Write three .plan sections; give the middle one the featured class and a ribbon p.
2. Grid the plans and align them to the start.
3. Scale the featured plan and add a shadow.
4. Position the ribbon at the top centre.
5. Add ticks with ::before; crosses for .no items.
6. Style the buttons.

Project 1057: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - Compare plans</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Compare our packages</h1>
    <div class="plans">
      <section class="plan">
        <h2>Basic</h2>
        <p class="price">55 EGP</p>
        <ul><li>One drink</li><li>Email support</li><li class="no">No
priority booking</li></ul>
        <a class="btn" href="#">Choose Basic</a>
      </section>
      <section class="plan featured">
        <p class="ribbon">Most popular</p>
        <h2>Standard</h2>
        <p class="price">60 EGP</p>
        <ul><li>Three drinks</li><li>Phone support</li><li>Priority
booking</li></ul>
        <a class="btn" href="#">Choose Standard</a>
      </section>
      <section class="plan">
        <h2>Premium</h2>
        <p class="price">75 EGP</p>
        <ul><li>Unlimited drinks</li><li>Personal advisor</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Premium</a>
      </section>
    </div>
  </main>
</body>
</html>
```

Project 1057: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; text-
```

```
align: center; }
.plans { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(15rem, 1fr)); align-items: start; }
.plan { position: relative; border: 1px solid var(--line); border-
radius: 16px; padding: 2rem 1.5rem; background: #fff; }
.featured { border: 2px solid var(--brand); transform: scale(1.04);
box-shadow: 0 16px 40px rgb(0 0 0 / 12%); }
.ribbon { position: absolute; top: -.8rem; left: 50%; translate: -50%
0; background: var(--brand); color: #fff; font-size: .75rem; padding:
.2rem .8rem; border-radius: 999px; margin: 0; }
.price { font-size: 2rem; font-weight: 800; margin: .5rem 0 1rem; }
ul { list-style: none; padding: 0; text-align: left; }
li { padding: .4rem 0; border-bottom: 1px solid var(--accent); }
li::before { content: "\2713 "; color: var(--brand); }
li.no { color: var(--muted); }
li.no::before { content: "\2717 "; color: #999; }
.btn { display: block; margin-top: 1.5rem; padding: .7rem; border-
radius: 999px; background: var(--brand); color: #fff; text-decoration:
 none; }
```

Project 1057 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - Compare plans</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Compare our packages	The main heading; only one per page.
	Generic block container for grouping and layout.
<section class="plan">	A thematic group of content, normally with its own heading.
Basic	Second-level heading for a section.
55 EGP	A paragraph of text.
- One drink - Email support <li class="no">No prior…	Unordered (bulleted) list.

Line	What it does
Choose Basic	A link styled as a button; it navigates, so it is a link and not a <button>.
- Three drinks - Phone support - Priority booking...	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(15rem, 1fr));	Defines the columns of the grid.
align-items: start;	Aligns items to the start of the cross axis (no stretching).
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 16px;	Rounds the corners.
background: #fff;	Background colour or image.
border: 2px solid var(--brand);	The line around the element: width, style and colour.
transform: scale(1.04);	Enlarges or shrinks the element visually.
box-shadow: 0 16px 40px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
font-size: .75rem;	Size of the text.
border-radius: 999px;	Fully rounded pill shape.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--accent);	A bottom border used as a separator line.

Declaration	What it does
content: "\2713 ";	The text or empty string for a pseudo-element.
display: block;	Element starts on a new line and fills the width (used on links and images).
text-decoration: none;	Removes the underline from links.

Check your work

- Ribbon centred
- Scaled card does not overlap on narrow screens (stacking)
- Features left-aligned
- Prices large and clear

Exercises

1. Add a monthly/yearly toggle with :checked.
2. Convert to a comparison table for many features.
3. Animate the featured card on hover.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 1058: Pricing plans comparison for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 2 | Files: index.html, styles.css

Brief

Present three packages side by side with a highlighted, slightly enlarged middle plan, a 'most popular' ribbon and tick/cross feature lists.

Learning goals

- Emphasise one card with transform: scale and a border
- Position a ribbon over the card edge
- Use ::before glyphs for ticks and crosses

Elements and CSS used

HTML elements	CSS features
section, h2, p, ul, li, a	transform: scale(), position: absolute + translate, align-items: start, ::before content, box-shadow

Build guide

1. Write three .plan sections; give the middle one the featured class and a ribbon p.
2. Grid the plans and align them to the start.
3. Scale the featured plan and add a shadow.
4. Position the ribbon at the top centre.
5. Add ticks with ::before; crosses for .no items.

6. Style the buttons.

Project 1058: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - Compare plans</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Compare our packages</h1>
    <div class="plans">
      <section class="plan">
        <h2>Basic</h2>
        <p class="price">400 EGP</p>
        <ul><li>One hike</li><li>Email support</li><li class="no">No
priority booking</li></ul>
        <a class="btn" href="#">Choose Basic</a>
      </section>
      <section class="plan featured">
        <p class="ribbon">Most popular</p>
        <h2>Standard</h2>
        <p class="price">250 EGP</p>
        <ul><li>Three hikes</li><li>Phone support</li><li>Priority
booking</li></ul>
        <a class="btn" href="#">Choose Standard</a>
      </section>
      <section class="plan">
        <h2>Premium</h2>
        <p class="price">1900 EGP</p>
        <ul><li>Unlimited hikes</li><li>Personal advisor</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Premium</a>
      </section>
    </div>
  </main>
</body>
</html>
```

Project 1058: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; text-
```

```
align: center; }
.plans { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(15rem, 1fr)); align-items: start; }
.plan { position: relative; border: 1px solid var(--line); border-
radius: 16px; padding: 2rem 1.5rem; background: #fff; }
.featured { border: 2px solid var(--brand); transform: scale(1.04);
box-shadow: 0 16px 40px rgb(0 0 0 / 12%); }
.ribbon { position: absolute; top: -.8rem; left: 50%; translate: -50%
0; background: var(--brand); color: #fff; font-size: .75rem; padding:
.2rem .8rem; border-radius: 999px; margin: 0; }
.price { font-size: 2rem; font-weight: 800; margin: .5rem 0 1rem; }
ul { list-style: none; padding: 0; text-align: left; }
li { padding: .4rem 0; border-bottom: 1px solid var(--accent); }
li::before { content: "\2713 "; color: var(--brand); }
li.no { color: var(--muted); }
li.no::before { content: "\2717 "; color: #999; }
.btn { display: block; margin-top: 1.5rem; padding: .7rem; border-
radius: 999px; background: var(--brand); color: #fff; text-decoration:
 none; }
```

Project 1058 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - Compare plans</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Compare our packages	The main heading; only one per page.
	Generic block container for grouping and layout.
<section class="plan">	A thematic group of content, normally with its own heading.
Basic	Second-level heading for a section.
400 EGP	A paragraph of text.
- One hike - Email support <li class="no">No priori...	Unordered (bulleted) list.

Line	What it does
Choose Basic	A link styled as a button; it navigates, so it is a link and not a <button>.
- Three hikes - Phone support - Priority booking<...	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(15rem, 1fr));	Defines the columns of the grid.
align-items: start;	Aligns items to the start of the cross axis (no stretching).
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 16px;	Rounds the corners.
background: #fff;	Background colour or image.
border: 2px solid var(--brand);	The line around the element: width, style and colour.
transform: scale(1.04);	Enlarges or shrinks the element visually.
box-shadow: 0 16px 40px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
font-size: .75rem;	Size of the text.
border-radius: 999px;	Fully rounded pill shape.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--accent);	A bottom border used as a separator line.

Declaration	What it does
content: "\2713 ";	The text or empty string for a pseudo-element.
display: block;	Element starts on a new line and fills the width (used on links and images).
text-decoration: none;	Removes the underline from links.

Check your work

- Ribbon centred
- Scaled card does not overlap on narrow screens (stacking)
- Features left-aligned
- Prices large and clear

Exercises

1. Add a monthly/yearly toggle with :checked.
2. Convert to a comparison table for many features.
3. Animate the featured card on hover.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 1059: Pricing plans comparison for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 2 | Files: index.html, styles.css

Brief

Present three packages side by side with a highlighted, slightly enlarged middle plan, a 'most popular' ribbon and tick/cross feature lists.

Learning goals

- Emphasise one card with transform: scale and a border
- Position a ribbon over the card edge
- Use ::before glyphs for ticks and crosses

Elements and CSS used

HTML elements	CSS features
section, h2, p, ul, li, a	transform: scale(), position: absolute + translate, align-items: start, ::before content, box-shadow

Build guide

1. Write three .plan sections; give the middle one the featured class and a ribbon p.
2. Grid the plans and align them to the start.
3. Scale the featured plan and add a shadow.
4. Position the ribbon at the top centre.
5. Add ticks with ::before; crosses for .no items.
6. Style the buttons.

Project 1059: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - Compare plans</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Compare our packages</h1>
    <div class="plans">
      <section class="plan">
        <h2>Basic</h2>
        <p class="price">1200 EGP</p>
        <ul><li>One session</li><li>Email support</li><li
class="no">No priority booking</li></ul>
        <a class="btn" href="#">Choose Basic</a>
      </section>
      <section class="plan featured">
        <p class="ribbon">Most popular</p>
        <h2>Standard</h2>
        <p class="price">15000 EGP</p>
        <ul><li>Three sessions</li><li>Phone support</li><li>Priority
booking</li></ul>
        <a class="btn" href="#">Choose Standard</a>
      </section>
      <section class="plan">
        <h2>Premium</h2>
        <p class="price">1500 EGP</p>
        <ul><li>Unlimited sessions</li><li>Personal advisor</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Premium</a>
      </section>
    </div>
  </main>
</body>
</html>
```

Project 1059: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; text-
```

```
align: center; }
.plans { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(15rem, 1fr)); align-items: start; }
.plan { position: relative; border: 1px solid var(--line); border-
radius: 16px; padding: 2rem 1.5rem; background: #fff; }
.featured { border: 2px solid var(--brand); transform: scale(1.04);
box-shadow: 0 16px 40px rgb(0 0 0 / 12%); }
.ribbon { position: absolute; top: -.8rem; left: 50%; translate: -50%
0; background: var(--brand); color: #fff; font-size: .75rem; padding:
.2rem .8rem; border-radius: 999px; margin: 0; }
.price { font-size: 2rem; font-weight: 800; margin: .5rem 0 1rem; }
ul { list-style: none; padding: 0; text-align: left; }
li { padding: .4rem 0; border-bottom: 1px solid var(--accent); }
li::before { content: "\2713 "; color: var(--brand); }
li.no { color: var(--muted); }
li.no::before { content: "\2717 "; color: #999; }
.btn { display: block; margin-top: 1.5rem; padding: .7rem; border-
radius: 999px; background: var(--brand); color: #fff; text-decoration:
 none; }
```

Project 1059 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - Compare plans</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Compare our packages	The main heading; only one per page.
	Generic block container for grouping and layout.
<section class="plan">	A thematic group of content, normally with its own heading.
Basic	Second-level heading for a section.
1200 EGP	A paragraph of text.
- One session - Email support <li class="no">No pri...	Unordered (bulleted) list.

Line	What it does
Choose Basic	A link styled as a button; it navigates, so it is a link and not a <button>.
- Three sessions - Phone support - Priority booki...	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(15rem, 1fr));	Defines the columns of the grid.
align-items: start;	Aligns items to the start of the cross axis (no stretching).
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 16px;	Rounds the corners.
background: #fff;	Background colour or image.
border: 2px solid var(--brand);	The line around the element: width, style and colour.
transform: scale(1.04);	Enlarges or shrinks the element visually.
box-shadow: 0 16px 40px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
font-size: .75rem;	Size of the text.
border-radius: 999px;	Fully rounded pill shape.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--accent);	A bottom border used as a separator line.

Declaration	What it does
content: "\2713 ";	The text or empty string for a pseudo-element.
display: block;	Element starts on a new line and fills the width (used on links and images).
text-decoration: none;	Removes the underline from links.

Check your work

- Ribbon centred
- Scaled card does not overlap on narrow screens (stacking)
- Features left-aligned
- Prices large and clear

Exercises

1. Add a monthly/yearly toggle with :checked.
2. Convert to a comparison table for many features.
3. Animate the featured card on hover.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 1060: Pricing plans comparison for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 2 | Files: index.html, styles.css

Brief

Present three packages side by side with a highlighted, slightly enlarged middle plan, a 'most popular' ribbon and tick/cross feature lists.

Learning goals

- Emphasise one card with transform: scale and a border
- Position a ribbon over the card edge
- Use ::before glyphs for ticks and crosses

Elements and CSS used

HTML elements	CSS features
section, h2, p, ul, li, a	transform: scale(), position: absolute + translate, align-items: start, ::before content, box-shadow

Build guide

1. Write three .plan sections; give the middle one the featured class and a ribbon p.
2. Grid the plans and align them to the start.
3. Scale the featured plan and add a shadow.
4. Position the ribbon at the top centre.
5. Add ticks with ::before; crosses for .no items.
6. Style the buttons.

Project 1060: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - Compare plans</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Compare our packages</h1>
    <div class="plans">
      <section class="plan">
        <h2>Basic</h2>
        <p class="price">140 EGP</p>
        <ul><li>One product</li><li>Email support</li><li
class="no">No priority booking</li></ul>
        <a class="btn" href="#">Choose Basic</a>
      </section>
      <section class="plan featured">
        <p class="ribbon">Most popular</p>
        <h2>Standard</h2>
        <p class="price">350 EGP</p>
        <ul><li>Three products</li><li>Phone support</li><li>Priority
booking</li></ul>
        <a class="btn" href="#">Choose Standard</a>
      </section>
      <section class="plan">
        <h2>Premium</h2>
        <p class="price">110 EGP</p>
        <ul><li>Unlimited products</li><li>Personal advisor</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Premium</a>
      </section>
    </div>
  </main>
</body>
</html>
```

Project 1060: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; text-
```

```
align: center; }
.plans { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(15rem, 1fr)); align-items: start; }
.plan { position: relative; border: 1px solid var(--line); border-
radius: 16px; padding: 2rem 1.5rem; background: #fff; }
.featured { border: 2px solid var(--brand); transform: scale(1.04);
box-shadow: 0 16px 40px rgb(0 0 0 / 12%); }
.ribbon { position: absolute; top: -.8rem; left: 50%; translate: -50%
0; background: var(--brand); color: #fff; font-size: .75rem; padding:
.2rem .8rem; border-radius: 999px; margin: 0; }
.price { font-size: 2rem; font-weight: 800; margin: .5rem 0 1rem; }
ul { list-style: none; padding: 0; text-align: left; }
li { padding: .4rem 0; border-bottom: 1px solid var(--accent); }
li::before { content: "\2713 "; color: var(--brand); }
li.no { color: var(--muted); }
li.no::before { content: "\2717 "; color: #999; }
.btn { display: block; margin-top: 1.5rem; padding: .7rem; border-
radius: 999px; background: var(--brand); color: #fff; text-decoration:
 none; }
```

Project 1060 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - Compare plans</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Compare our packages	The main heading; only one per page.
	Generic block container for grouping and layout.
<section class="plan">	A thematic group of content, normally with its own heading.
Basic	Second-level heading for a section.
140 EGP	A paragraph of text.
- One product - Email support <li class="no">No pri...	Unordered (bulleted) list.

Line	What it does
Choose Basic	A link styled as a button; it navigates, so it is a link and not a <button>.
- Three products - Phone support - Priority booki...	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(15rem, 1fr));	Defines the columns of the grid.
align-items: start;	Aligns items to the start of the cross axis (no stretching).
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 16px;	Rounds the corners.
background: #fff;	Background colour or image.
border: 2px solid var(--brand);	The line around the element: width, style and colour.
transform: scale(1.04);	Enlarges or shrinks the element visually.
box-shadow: 0 16px 40px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
font-size: .75rem;	Size of the text.
border-radius: 999px;	Fully rounded pill shape.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--accent);	A bottom border used as a separator line.

Declaration	What it does
content: "\2713 ";	The text or empty string for a pseudo-element.
display: block;	Element starts on a new line and fills the width (used on links and images).
text-decoration: none;	Removes the underline from links.

Check your work

- Ribbon centred
- Scaled card does not overlap on narrow screens (stacking)
- Features left-aligned
- Prices large and clear

Exercises

1. Add a monthly/yearly toggle with :checked.
2. Convert to a comparison table for many features.
3. Animate the featured card on hover.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 1061: Pricing plans comparison for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 2 | Files: index.html, styles.css

Brief

Present three packages side by side with a highlighted, slightly enlarged middle plan, a 'most popular' ribbon and tick/cross feature lists.

Learning goals

- Emphasise one card with transform: scale and a border
- Position a ribbon over the card edge
- Use ::before glyphs for ticks and crosses

Elements and CSS used

HTML elements	CSS features
section, h2, p, ul, li, a	transform: scale(), position: absolute + translate, align-items: start, ::before content, box-shadow

Build guide

1. Write three .plan sections; give the middle one the featured class and a ribbon p.
2. Grid the plans and align them to the start.
3. Scale the featured plan and add a shadow.
4. Position the ribbon at the top centre.
5. Add ticks with ::before; crosses for .no items.

6. Style the buttons.

Project 1061: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - Compare plans</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Compare our packages</h1>
    <div class="plans">
      <section class="plan">
        <h2>Basic</h2>
        <p class="price">250 EGP</p>
        <ul><li>One plant</li><li>Email support</li><li class="no">No
priority booking</li></ul>
        <a class="btn" href="#">Choose Basic</a>
      </section>
      <section class="plan featured">
        <p class="ribbon">Most popular</p>
        <h2>Standard</h2>
        <p class="price">120 EGP</p>
        <ul><li>Three plants</li><li>Phone support</li><li>Priority
booking</li></ul>
        <a class="btn" href="#">Choose Standard</a>
      </section>
      <section class="plan">
        <h2>Premium</h2>
        <p class="price">600 EGP</p>
        <ul><li>Unlimited plants</li><li>Personal advisor</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Premium</a>
      </section>
    </div>
  </main>
</body>
</html>
```

Project 1061: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; text-
```

```
align: center; }
.plans { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(15rem, 1fr)); align-items: start; }
.plan { position: relative; border: 1px solid var(--line); border-
radius: 16px; padding: 2rem 1.5rem; background: #fff; }
.featured { border: 2px solid var(--brand); transform: scale(1.04);
box-shadow: 0 16px 40px rgb(0 0 0 / 12%); }
.ribbon { position: absolute; top: -.8rem; left: 50%; translate: -50%
0; background: var(--brand); color: #fff; font-size: .75rem; padding:
.2rem .8rem; border-radius: 999px; margin: 0; }
.price { font-size: 2rem; font-weight: 800; margin: .5rem 0 1rem; }
ul { list-style: none; padding: 0; text-align: left; }
li { padding: .4rem 0; border-bottom: 1px solid var(--accent); }
li::before { content: "\2713 "; color: var(--brand); }
li.no { color: var(--muted); }
li.no::before { content: "\2717 "; color: #999; }
.btn { display: block; margin-top: 1.5rem; padding: .7rem; border-
radius: 999px; background: var(--brand); color: #fff; text-decoration:
 none; }
```

Project 1061 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - Compare plans</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Compare our packages	The main heading; only one per page.
	Generic block container for grouping and layout.
<section class="plan">	A thematic group of content, normally with its own heading.
Basic	Second-level heading for a section.
250 EGP	A paragraph of text.
- One plant - Email support <li class="no">No prior…	Unordered (bulleted) list.

Line	What it does
Choose Basic	A link styled as a button; it navigates, so it is a link and not a <button>.
- Three plants - Phone support - Priority booking...	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(15rem, 1fr));	Defines the columns of the grid.
align-items: start;	Aligns items to the start of the cross axis (no stretching).
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 16px;	Rounds the corners.
background: #fff;	Background colour or image.
border: 2px solid var(--brand);	The line around the element: width, style and colour.
transform: scale(1.04);	Enlarges or shrinks the element visually.
box-shadow: 0 16px 40px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
font-size: .75rem;	Size of the text.
border-radius: 999px;	Fully rounded pill shape.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--accent);	A bottom border used as a separator line.

Declaration	What it does
content: "\2713 ";	The text or empty string for a pseudo-element.
display: block;	Element starts on a new line and fills the width (used on links and images).
text-decoration: none;	Removes the underline from links.

Check your work

- Ribbon centred
- Scaled card does not overlap on narrow screens (stacking)
- Features left-aligned
- Prices large and clear

Exercises

1. Add a monthly/yearly toggle with :checked.
2. Convert to a comparison table for many features.
3. Animate the featured card on hover.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 1062: Pricing plans comparison for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 2 | Files: index.html, styles.css

Brief

Present three packages side by side with a highlighted, slightly enlarged middle plan, a 'most popular' ribbon and tick/cross feature lists.

Learning goals

- Emphasise one card with transform: scale and a border
- Position a ribbon over the card edge
- Use ::before glyphs for ticks and crosses

Elements and CSS used

HTML elements	CSS features
section, h2, p, ul, li, a	transform: scale(), position: absolute + translate, align-items: start, ::before content, box-shadow

Build guide

1. Write three .plan sections; give the middle one the featured class and a ribbon p.
2. Grid the plans and align them to the start.
3. Scale the featured plan and add a shadow.
4. Position the ribbon at the top centre.
5. Add ticks with ::before; crosses for .no items.
6. Style the buttons.

Project 1062: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - Compare plans</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Compare our packages</h1>
    <div class="plans">
      <section class="plan">
        <h2>Basic</h2>
        <p class="price">9500 EGP</p>
        <ul><li>One piece</li><li>Email support</li><li class="no">No
priority booking</li></ul>
        <a class="btn" href="#">Choose Basic</a>
      </section>
      <section class="plan featured">
        <p class="ribbon">Most popular</p>
        <h2>Standard</h2>
        <p class="price">4200 EGP</p>
        <ul><li>Three pieces</li><li>Phone support</li><li>Priority
booking</li></ul>
        <a class="btn" href="#">Choose Standard</a>
      </section>
      <section class="plan">
        <h2>Premium</h2>
        <p class="price">2800 EGP</p>
        <ul><li>Unlimited pieces</li><li>Personal advisor</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Premium</a>
      </section>
    </div>
  </main>
</body>
</html>
```

Project 1062: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; text-
```

```
align: center; }
.plans { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(15rem, 1fr)); align-items: start; }
.plan { position: relative; border: 1px solid var(--line); border-
radius: 16px; padding: 2rem 1.5rem; background: #fff; }
.featured { border: 2px solid var(--brand); transform: scale(1.04);
box-shadow: 0 16px 40px rgb(0 0 0 / 12%); }
.ribbon { position: absolute; top: -.8rem; left: 50%; translate: -50%
0; background: var(--brand); color: #fff; font-size: .75rem; padding:
.2rem .8rem; border-radius: 999px; margin: 0; }
.price { font-size: 2rem; font-weight: 800; margin: .5rem 0 1rem; }
ul { list-style: none; padding: 0; text-align: left; }
li { padding: .4rem 0; border-bottom: 1px solid var(--accent); }
li::before { content: "\2713 "; color: var(--brand); }
li.no { color: var(--muted); }
li.no::before { content: "\2717 "; color: #999; }
.btn { display: block; margin-top: 1.5rem; padding: .7rem; border-
radius: 999px; background: var(--brand); color: #fff; text-decoration:
 none; }
```

Project 1062 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - Compare plans</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Compare our packages	The main heading; only one per page.
	Generic block container for grouping and layout.
<section class="plan">	A thematic group of content, normally with its own heading.
Basic	Second-level heading for a section.
9500 EGP	A paragraph of text.
- One piece - Email support <li class="no">No prior…	Unordered (bulleted) list.

Line	What it does
Choose Basic	A link styled as a button; it navigates, so it is a link and not a <button>.
- Three pieces - Phone support - Priority booking...	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(15rem, 1fr));	Defines the columns of the grid.
align-items: start;	Aligns items to the start of the cross axis (no stretching).
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 16px;	Rounds the corners.
background: #fff;	Background colour or image.
border: 2px solid var(--brand);	The line around the element: width, style and colour.
transform: scale(1.04);	Enlarges or shrinks the element visually.
box-shadow: 0 16px 40px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
font-size: .75rem;	Size of the text.
border-radius: 999px;	Fully rounded pill shape.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--accent);	A bottom border used as a separator line.

Declaration	What it does
content: "\2713 ";	The text or empty string for a pseudo-element.
display: block;	Element starts on a new line and fills the width (used on links and images).
text-decoration: none;	Removes the underline from links.

Check your work

- Ribbon centred
- Scaled card does not overlap on narrow screens (stacking)
- Features left-aligned
- Prices large and clear

Exercises

1. Add a monthly/yearly toggle with :checked.
2. Convert to a comparison table for many features.
3. Animate the featured card on hover.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 1063: Pricing plans comparison for Byte Repair

Theme: Byte Repair (Nasr City) | Level 2 | Files: index.html, styles.css

Brief

Present three packages side by side with a highlighted, slightly enlarged middle plan, a 'most popular' ribbon and tick/cross feature lists.

Learning goals

- Emphasise one card with transform: scale and a border
- Position a ribbon over the card edge
- Use ::before glyphs for ticks and crosses

Elements and CSS used

HTML elements	CSS features
section, h2, p, ul, li, a	transform: scale(), position: absolute + translate, align-items: start, ::before content, box-shadow

Build guide

1. Write three .plan sections; give the middle one the featured class and a ribbon p.
2. Grid the plans and align them to the start.
3. Scale the featured plan and add a shadow.
4. Position the ribbon at the top centre.
5. Add ticks with ::before; crosses for .no items.
6. Style the buttons.

Project 1063: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - Compare plans</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Compare our packages</h1>
    <div class="plans">
      <section class="plan">
        <h2>Basic</h2>
        <p class="price">From 800 EGP</p>
        <ul><li>One repair</li><li>Email support</li><li
class="no">No priority booking</li></ul>
        <a class="btn" href="#">Choose Basic</a>
      </section>
      <section class="plan featured">
        <p class="ribbon">Most popular</p>
        <h2>Standard</h2>
        <p class="price">From 500 EGP</p>
        <ul><li>Three repairs</li><li>Phone support</li><li>Priority
booking</li></ul>
        <a class="btn" href="#">Choose Standard</a>
      </section>
      <section class="plan">
        <h2>Premium</h2>
        <p class="price">From 1200 EGP</p>
        <ul><li>Unlimited repairs</li><li>Personal advisor</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Premium</a>
      </section>
    </div>
  </main>
</body>
</html>
```

Project 1063: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; text-
```

```
align: center; }
.plans { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(15rem, 1fr)); align-items: start; }
.plan { position: relative; border: 1px solid var(--line); border-
radius: 16px; padding: 2rem 1.5rem; background: #fff; }
.featured { border: 2px solid var(--brand); transform: scale(1.04);
box-shadow: 0 16px 40px rgb(0 0 0 / 12%); }
.ribbon { position: absolute; top: -.8rem; left: 50%; translate: -50%
0; background: var(--brand); color: #fff; font-size: .75rem; padding:
.2rem .8rem; border-radius: 999px; margin: 0; }
.price { font-size: 2rem; font-weight: 800; margin: .5rem 0 1rem; }
ul { list-style: none; padding: 0; text-align: left; }
li { padding: .4rem 0; border-bottom: 1px solid var(--accent); }
li::before { content: "\2713 "; color: var(--brand); }
li.no { color: var(--muted); }
li.no::before { content: "\2717 "; color: #999; }
.btn { display: block; margin-top: 1.5rem; padding: .7rem; border-
radius: 999px; background: var(--brand); color: #fff; text-decoration:
 none; }
```

Project 1063 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - Compare plans</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Compare our packages	The main heading; only one per page.
	Generic block container for grouping and layout.
<section class="plan">	A thematic group of content, normally with its own heading.
Basic	Second-level heading for a section.
From 800 EGP	A paragraph of text.
- One repair - Email support <li class="no">No prio...	Unordered (bulleted) list.

Line	What it does
Choose Basic	A link styled as a button; it navigates, so it is a link and not a <button>.
- Three repairs - Phone support - Priority bookin...	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(15rem, 1fr));	Defines the columns of the grid.
align-items: start;	Aligns items to the start of the cross axis (no stretching).
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 16px;	Rounds the corners.
background: #fff;	Background colour or image.
border: 2px solid var(--brand);	The line around the element: width, style and colour.
transform: scale(1.04);	Enlarges or shrinks the element visually.
box-shadow: 0 16px 40px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
font-size: .75rem;	Size of the text.
border-radius: 999px;	Fully rounded pill shape.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--accent);	A bottom border used as a separator line.

Declaration	What it does
content: "\2713 ";	The text or empty string for a pseudo-element.
display: block;	Element starts on a new line and fills the width (used on links and images).
text-decoration: none;	Removes the underline from links.

Check your work

- Ribbon centred
- Scaled card does not overlap on narrow screens (stacking)
- Features left-aligned
- Prices large and clear

Exercises

1. Add a monthly/yearly toggle with :checked.
2. Convert to a comparison table for many features.
3. Animate the featured card on hover.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 1064: Pricing plans comparison for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 2 | Files: index.html, styles.css

Brief

Present three packages side by side with a highlighted, slightly enlarged middle plan, a 'most popular' ribbon and tick/cross feature lists.

Learning goals

- Emphasise one card with transform: scale and a border
- Position a ribbon over the card edge
- Use ::before glyphs for ticks and crosses

Elements and CSS used

HTML elements	CSS features
section, h2, p, ul, li, a	transform: scale(), position: absolute + translate, align-items: start, ::before content, box-shadow

Build guide

1. Write three .plan sections; give the middle one the featured class and a ribbon p.
2. Grid the plans and align them to the start.
3. Scale the featured plan and add a shadow.
4. Position the ribbon at the top centre.
5. Add ticks with ::before; crosses for .no items.
6. Style the buttons.

Project 1064: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - Compare plans</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Compare our packages</h1>
    <div class="plans">
      <section class="plan">
        <h2>Basic</h2>
        <p class="price">400 EGP</p>
        <ul><li>One service</li><li>Email support</li><li
class="no">No priority booking</li></ul>
        <a class="btn" href="#">Choose Basic</a>
      </section>
      <section class="plan featured">
        <p class="ribbon">Most popular</p>
        <h2>Standard</h2>
        <p class="price">250 EGP</p>
        <ul><li>Three services</li><li>Phone support</li><li>Priority
booking</li></ul>
        <a class="btn" href="#">Choose Standard</a>
      </section>
      <section class="plan">
        <h2>Premium</h2>
        <p class="price">100 EGP</p>
        <ul><li>Unlimited services</li><li>Personal advisor</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Premium</a>
      </section>
    </div>
  </main>
</body>
</html>
```

Project 1064: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; text-
```

```
align: center; }
.plans { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(15rem, 1fr)); align-items: start; }
.plan { position: relative; border: 1px solid var(--line); border-
radius: 16px; padding: 2rem 1.5rem; background: #fff; }
.featured { border: 2px solid var(--brand); transform: scale(1.04);
box-shadow: 0 16px 40px rgb(0 0 0 / 12%); }
.ribbon { position: absolute; top: -.8rem; left: 50%; translate: -50%
0; background: var(--brand); color: #fff; font-size: .75rem; padding:
.2rem .8rem; border-radius: 999px; margin: 0; }
.price { font-size: 2rem; font-weight: 800; margin: .5rem 0 1rem; }
ul { list-style: none; padding: 0; text-align: left; }
li { padding: .4rem 0; border-bottom: 1px solid var(--accent); }
li::before { content: "\2713 "; color: var(--brand); }
li.no { color: var(--muted); }
li.no::before { content: "\2717 "; color: #999; }
.btn { display: block; margin-top: 1.5rem; padding: .7rem; border-
radius: 999px; background: var(--brand); color: #fff; text-decoration:
 none; }
```

Project 1064 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - Compare plans</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Compare our packages	The main heading; only one per page.
	Generic block container for grouping and layout.
<section class="plan">	A thematic group of content, normally with its own heading.
Basic	Second-level heading for a section.
400 EGP	A paragraph of text.
- One service - Email support <li class="no">No pri...	Unordered (bulleted) list.

Line	What it does
Choose Basic	A link styled as a button; it navigates, so it is a link and not a <button>.
- Three services - Phone support - Priority booki...	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(15rem, 1fr));	Defines the columns of the grid.
align-items: start;	Aligns items to the start of the cross axis (no stretching).
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 16px;	Rounds the corners.
background: #fff;	Background colour or image.
border: 2px solid var(--brand);	The line around the element: width, style and colour.
transform: scale(1.04);	Enlarges or shrinks the element visually.
box-shadow: 0 16px 40px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
font-size: .75rem;	Size of the text.
border-radius: 999px;	Fully rounded pill shape.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--accent);	A bottom border used as a separator line.

Declaration	What it does
content: "\2713 ";	The text or empty string for a pseudo-element.
display: block;	Element starts on a new line and fills the width (used on links and images).
text-decoration: none;	Removes the underline from links.

Check your work

- Ribbon centred
- Scaled card does not overlap on narrow screens (stacking)
- Features left-aligned
- Prices large and clear

Exercises

1. Add a monthly/yearly toggle with :checked.
2. Convert to a comparison table for many features.
3. Animate the featured card on hover.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 1065: Pricing plans comparison for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Present three packages side by side with a highlighted, slightly enlarged middle plan, a 'most popular' ribbon and tick/cross feature lists.

Learning goals

- Emphasise one card with transform: scale and a border
- Position a ribbon over the card edge
- Use ::before glyphs for ticks and crosses

Elements and CSS used

HTML elements	CSS features
section, h2, p, ul, li, a	transform: scale(), position: absolute + translate, align-items: start, ::before content, box-shadow

Build guide

1. Write three .plan sections; give the middle one the featured class and a ribbon p.
2. Grid the plans and align them to the start.
3. Scale the featured plan and add a shadow.
4. Position the ribbon at the top centre.
5. Add ticks with ::before; crosses for .no items.

6. Style the buttons.

Project 1065: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - Compare plans</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Compare our packages</h1>
    <div class="plans">
      <section class="plan">
        <h2>Basic</h2>
        <p class="price">500 EGP</p>
        <ul><li>One lesson</li><li>Email support</li><li
class="no">No priority booking</li></ul>
        <a class="btn" href="#">Choose Basic</a>
      </section>
      <section class="plan featured">
        <p class="ribbon">Most popular</p>
        <h2>Standard</h2>
        <p class="price">2200 EGP</p>
        <ul><li>Three lessons</li><li>Phone support</li><li>Priority
booking</li></ul>
        <a class="btn" href="#">Choose Standard</a>
      </section>
      <section class="plan">
        <h2>Premium</h2>
        <p class="price">900 EGP</p>
        <ul><li>Unlimited lessons</li><li>Personal advisor</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Premium</a>
      </section>
    </div>
  </main>
</body>
</html>
```

Project 1065: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; text-
```

```
align: center; }
.plans { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(15rem, 1fr)); align-items: start; }
.plan { position: relative; border: 1px solid var(--line); border-
radius: 16px; padding: 2rem 1.5rem; background: #fff; }
.featured { border: 2px solid var(--brand); transform: scale(1.04);
box-shadow: 0 16px 40px rgb(0 0 0 / 12%); }
.ribbon { position: absolute; top: -.8rem; left: 50%; translate: -50%
0; background: var(--brand); color: #fff; font-size: .75rem; padding:
.2rem .8rem; border-radius: 999px; margin: 0; }
.price { font-size: 2rem; font-weight: 800; margin: .5rem 0 1rem; }
ul { list-style: none; padding: 0; text-align: left; }
li { padding: .4rem 0; border-bottom: 1px solid var(--accent); }
li::before { content: "\2713 "; color: var(--brand); }
li.no { color: var(--muted); }
li.no::before { content: "\2717 "; color: #999; }
.btn { display: block; margin-top: 1.5rem; padding: .7rem; border-
radius: 999px; background: var(--brand); color: #fff; text-decoration:
 none; }
```

Project 1065 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - Compare plans</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Compare our packages	The main heading; only one per page.
	Generic block container for grouping and layout.
<section class="plan">	A thematic group of content, normally with its own heading.
Basic	Second-level heading for a section.
500 EGP	A paragraph of text.

Line	What it does
- One lesson - Email support <li class="no">No prio...	Unordered (bulleted) list.
Choose Basic	A link styled as a button; it navigates, so it is a link and not a <button>.
- Three lessons - Phone support - Priority bookin...	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(15rem, 1fr));	Defines the columns of the grid.
align-items: start;	Aligns items to the start of the cross axis (no stretching).
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 16px;	Rounds the corners.
background: #fff;	Background colour or image.
border: 2px solid var(--brand);	The line around the element: width, style and colour.
transform: scale(1.04);	Enlarges or shrinks the element visually.
box-shadow: 0 16px 40px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
font-size: .75rem;	Size of the text.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--accent);	A bottom border used as a separator line.
content: "\2713 ";	The text or empty string for a pseudo-element.
display: block;	Element starts on a new line and fills the width (used on links and images).
text-decoration: none;	Removes the underline from links.

Check your work

- Ribbon centred
- Scaled card does not overlap on narrow screens (stacking)
- Features left-aligned
- Prices large and clear

Exercises

1. Add a monthly/yearly toggle with :checked.
2. Convert to a comparison table for many features.
3. Animate the featured card on hover.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af

Field	Value
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 1066: Pricing plans comparison for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Present three packages side by side with a highlighted, slightly enlarged middle plan, a 'most popular' ribbon and tick/cross feature lists.

Learning goals

- Emphasise one card with transform: scale and a border
- Position a ribbon over the card edge
- Use ::before glyphs for ticks and crosses

Elements and CSS used

HTML elements	CSS features
section, h2, p, ul, li, a	transform: scale(), position: absolute + translate, align-items: start, ::before content, box-shadow

Build guide

1. Write three .plan sections; give the middle one the featured class and a ribbon p.
2. Grid the plans and align them to the start.
3. Scale the featured plan and add a shadow.
4. Position the ribbon at the top centre.
5. Add ticks with ::before; crosses for .no items.

6. Style the buttons.

Project 1066: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - Compare plans</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Compare our packages</h1>
    <div class="plans">
      <section class="plan">
        <h2>Basic</h2>
        <p class="price">650 EGP</p>
        <ul><li>One item</li><li>Email support</li><li class="no">No
priority booking</li></ul>
        <a class="btn" href="#">Choose Basic</a>
      </section>
      <section class="plan featured">
        <p class="ribbon">Most popular</p>
        <h2>Standard</h2>
        <p class="price">420 EGP</p>
        <ul><li>Three items</li><li>Phone support</li><li>Priority
booking</li></ul>
        <a class="btn" href="#">Choose Standard</a>
      </section>
      <section class="plan">
        <h2>Premium</h2>
        <p class="price">300 EGP</p>
        <ul><li>Unlimited items</li><li>Personal advisor</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Premium</a>
      </section>
    </div>
  </main>
</body>
</html>
```

Project 1066: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; text-
```

```
align: center; }
.plans { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(15rem, 1fr)); align-items: start; }
.plan { position: relative; border: 1px solid var(--line); border-
radius: 16px; padding: 2rem 1.5rem; background: #fff; }
.featured { border: 2px solid var(--brand); transform: scale(1.04);
box-shadow: 0 16px 40px rgb(0 0 0 / 12%); }
.ribbon { position: absolute; top: -.8rem; left: 50%; translate: -50%
0; background: var(--brand); color: #fff; font-size: .75rem; padding:
.2rem .8rem; border-radius: 999px; margin: 0; }
.price { font-size: 2rem; font-weight: 800; margin: .5rem 0 1rem; }
ul { list-style: none; padding: 0; text-align: left; }
li { padding: .4rem 0; border-bottom: 1px solid var(--accent); }
li::before { content: "\2713 "; color: var(--brand); }
li.no { color: var(--muted); }
li.no::before { content: "\2717 "; color: #999; }
.btn { display: block; margin-top: 1.5rem; padding: .7rem; border-
radius: 999px; background: var(--brand); color: #fff; text-decoration:
 none; }
```

Project 1066 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - Compare plans</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Compare our packages	The main heading; only one per page.
	Generic block container for grouping and layout.
<section class="plan">	A thematic group of content, normally with its own heading.
Basic	Second-level heading for a section.
650 EGP	A paragraph of text.

Line	What it does
- One item - Email support <li class="no">No priori...	Unordered (bulleted) list.
Choose Basic	A link styled as a button; it navigates, so it is a link and not a <button>.
- Three items - Phone support - Priority booking<...	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(15rem, 1fr));	Defines the columns of the grid.
align-items: start;	Aligns items to the start of the cross axis (no stretching).
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 16px;	Rounds the corners.
background: #fff;	Background colour or image.
border: 2px solid var(--brand);	The line around the element: width, style and colour.
transform: scale(1.04);	Enlarges or shrinks the element visually.
box-shadow: 0 16px 40px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
font-size: .75rem;	Size of the text.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--accent);	A bottom border used as a separator line.
content: "\2713 ";	The text or empty string for a pseudo-element.
display: block;	Element starts on a new line and fills the width (used on links and images).
text-decoration: none;	Removes the underline from links.

Check your work

- Ribbon centred
- Scaled card does not overlap on narrow screens (stacking)
- Features left-aligned
- Prices large and clear

Exercises

1. Add a monthly/yearly toggle with :checked.
2. Convert to a comparison table for many features.
3. Animate the featured card on hover.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207

Field	Value
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 1067: Pricing plans comparison for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 2 | Files: index.html, styles.css

Brief

Present three packages side by side with a highlighted, slightly enlarged middle plan, a 'most popular' ribbon and tick/cross feature lists.

Learning goals

- Emphasise one card with transform: scale and a border
- Position a ribbon over the card edge
- Use ::before glyphs for ticks and crosses

Elements and CSS used

HTML elements	CSS features
section, h2, p, ul, li, a	transform: scale(), position: absolute + translate, align-items: start, ::before content, box-shadow

Build guide

1. Write three .plan sections; give the middle one the featured class and a ribbon p.
2. Grid the plans and align them to the start.
3. Scale the featured plan and add a shadow.
4. Position the ribbon at the top centre.
5. Add ticks with ::before; crosses for .no items.

6. Style the buttons.

Project 1067: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - Compare plans</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Compare our packages</h1>
    <div class="plans">
      <section class="plan">
        <h2>Basic</h2>
        <p class="price">450 EGP</p>
        <ul><li>One workshop</li><li>Email support</li><li
class="no">No priority booking</li></ul>
        <a class="btn" href="#">Choose Basic</a>
      </section>
      <section class="plan featured">
        <p class="ribbon">Most popular</p>
        <h2>Standard</h2>
        <p class="price">300 EGP</p>
        <ul><li>Three workshops</li><li>Phone support</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Standard</a>
      </section>
      <section class="plan">
        <h2>Premium</h2>
        <p class="price">2500 EGP</p>
        <ul><li>Unlimited workshops</li><li>Personal advisor</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Premium</a>
      </section>
    </div>
  </main>
</body>
</html>
```

Project 1067: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; text-
```

```
align: center; }
.plans { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(15rem, 1fr)); align-items: start; }
.plan { position: relative; border: 1px solid var(--line); border-
radius: 16px; padding: 2rem 1.5rem; background: #fff; }
.featured { border: 2px solid var(--brand); transform: scale(1.04);
box-shadow: 0 16px 40px rgb(0 0 0 / 12%); }
.ribbon { position: absolute; top: -.8rem; left: 50%; translate: -50%
0; background: var(--brand); color: #fff; font-size: .75rem; padding:
.2rem .8rem; border-radius: 999px; margin: 0; }
.price { font-size: 2rem; font-weight: 800; margin: .5rem 0 1rem; }
ul { list-style: none; padding: 0; text-align: left; }
li { padding: .4rem 0; border-bottom: 1px solid var(--accent); }
li::before { content: "\2713 "; color: var(--brand); }
li.no { color: var(--muted); }
li.no::before { content: "\2717 "; color: #999; }
.btn { display: block; margin-top: 1.5rem; padding: .7rem; border-
radius: 999px; background: var(--brand); color: #fff; text-decoration:
 none; }
```

Project 1067 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - Compare plans</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Compare our packages	The main heading; only one per page.
	Generic block container for grouping and layout.
<section class="plan">	A thematic group of content, normally with its own heading.
Basic	Second-level heading for a section.
450 EGP	A paragraph of text.
- One workshop - Email support <li class="no">No pr...	Unordered (bulleted) list.

Line	What it does
Choose Basic	A link styled as a button; it navigates, so it is a link and not a <button>.
- Three workshops - Phone support - Priority book...	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(15rem, 1fr));	Defines the columns of the grid.
align-items: start;	Aligns items to the start of the cross axis (no stretching).
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 16px;	Rounds the corners.
background: #fff;	Background colour or image.
border: 2px solid var(--brand);	The line around the element: width, style and colour.
transform: scale(1.04);	Enlarges or shrinks the element visually.
box-shadow: 0 16px 40px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
font-size: .75rem;	Size of the text.
border-radius: 999px;	Fully rounded pill shape.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--accent);	A bottom border used as a separator line.

Declaration	What it does
content: "\2713 ";	The text or empty string for a pseudo-element.
display: block;	Element starts on a new line and fills the width (used on links and images).
text-decoration: none;	Removes the underline from links.

Check your work

- Ribbon centred
- Scaled card does not overlap on narrow screens (stacking)
- Features left-aligned
- Prices large and clear

Exercises

1. Add a monthly/yearly toggle with :checked.
2. Convert to a comparison table for many features.
3. Animate the featured card on hover.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 1068: Pricing plans comparison for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 2 | Files: index.html, styles.css

Brief

Present three packages side by side with a highlighted, slightly enlarged middle plan, a 'most popular' ribbon and tick/cross feature lists.

Learning goals

- Emphasise one card with transform: scale and a border
- Position a ribbon over the card edge
- Use ::before glyphs for ticks and crosses

Elements and CSS used

HTML elements	CSS features
section, h2, p, ul, li, a	transform: scale(), position: absolute + translate, align-items: start, ::before content, box-shadow

Build guide

1. Write three .plan sections; give the middle one the featured class and a ribbon p.
2. Grid the plans and align them to the start.
3. Scale the featured plan and add a shadow.
4. Position the ribbon at the top centre.
5. Add ticks with ::before; crosses for .no items.

6. Style the buttons.

Project 1068: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - Compare plans</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Compare our packages</h1>
    <div class="plans">
      <section class="plan">
        <h2>Basic</h2>
        <p class="price">350 EGP</p>
        <ul><li>One treatment</li><li>Email support</li><li
class="no">No priority booking</li></ul>
        <a class="btn" href="#">Choose Basic</a>
      </section>
      <section class="plan featured">
        <p class="ribbon">Most popular</p>
        <h2>Standard</h2>
        <p class="price">200 EGP</p>
        <ul><li>Three treatments</li><li>Phone support</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Standard</a>
      </section>
      <section class="plan">
        <h2>Premium</h2>
        <p class="price">4500 EGP</p>
        <ul><li>Unlimited treatments</li><li>Personal advisor</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Premium</a>
      </section>
    </div>
  </main>
</body>
</html>
```

Project 1068: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; text-
```

```
align: center; }
.plans { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(15rem, 1fr)); align-items: start; }
.plan { position: relative; border: 1px solid var(--line); border-
radius: 16px; padding: 2rem 1.5rem; background: #fff; }
.featured { border: 2px solid var(--brand); transform: scale(1.04);
box-shadow: 0 16px 40px rgb(0 0 0 / 12%); }
.ribbon { position: absolute; top: -.8rem; left: 50%; translate: -50%
0; background: var(--brand); color: #fff; font-size: .75rem; padding:
.2rem .8rem; border-radius: 999px; margin: 0; }
.price { font-size: 2rem; font-weight: 800; margin: .5rem 0 1rem; }
ul { list-style: none; padding: 0; text-align: left; }
li { padding: .4rem 0; border-bottom: 1px solid var(--accent); }
li::before { content: "\2713 "; color: var(--brand); }
li.no { color: var(--muted); }
li.no::before { content: "\2717 "; color: #999; }
.btn { display: block; margin-top: 1.5rem; padding: .7rem; border-
radius: 999px; background: var(--brand); color: #fff; text-decoration:
 none; }
```

Project 1068 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - Compare plans</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Compare our packages	The main heading; only one per page.
	Generic block container for grouping and layout.
<section class="plan">	A thematic group of content, normally with its own heading.
Basic	Second-level heading for a section.
350 EGP	A paragraph of text.
- One treatment - Email support <li class="no">No p...	Unordered (bulleted) list.

Line	What it does
Choose Basic	A link styled as a button; it navigates, so it is a link and not a <button>.
- Three treatments - Phone support - Priority boo...	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(15rem, 1fr));	Defines the columns of the grid.
align-items: start;	Aligns items to the start of the cross axis (no stretching).
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 16px;	Rounds the corners.
background: #fff;	Background colour or image.
border: 2px solid var(--brand);	The line around the element: width, style and colour.
transform: scale(1.04);	Enlarges or shrinks the element visually.
box-shadow: 0 16px 40px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
font-size: .75rem;	Size of the text.
border-radius: 999px;	Fully rounded pill shape.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--accent);	A bottom border used as a separator line.

Declaration	What it does
content: "\2713 ";	The text or empty string for a pseudo-element.
display: block;	Element starts on a new line and fills the width (used on links and images).
text-decoration: none;	Removes the underline from links.

Check your work

- Ribbon centred
- Scaled card does not overlap on narrow screens (stacking)
- Features left-aligned
- Prices large and clear

Exercises

1. Add a monthly/yearly toggle with :checked.
2. Convert to a comparison table for many features.
3. Animate the featured card on hover.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 1069: Pricing plans comparison for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 2 | Files: index.html, styles.css

Brief

Present three packages side by side with a highlighted, slightly enlarged middle plan, a 'most popular' ribbon and tick/cross feature lists.

Learning goals

- Emphasise one card with transform: scale and a border
- Position a ribbon over the card edge
- Use ::before glyphs for ticks and crosses

Elements and CSS used

HTML elements	CSS features
section, h2, p, ul, li, a	transform: scale(), position: absolute + translate, align-items: start, ::before content, box-shadow

Build guide

1. Write three .plan sections; give the middle one the featured class and a ribbon p.
2. Grid the plans and align them to the start.
3. Scale the featured plan and add a shadow.
4. Position the ribbon at the top centre.
5. Add ticks with ::before; crosses for .no items.
6. Style the buttons.

Project 1069: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - Compare plans</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Compare our packages</h1>
    <div class="plans">
      <section class="plan">
        <h2>Basic</h2>
        <p class="price">600 EGP</p>
        <ul><li>One service</li><li>Email support</li><li
class="no">No priority booking</li></ul>
        <a class="btn" href="#">Choose Basic</a>
      </section>
      <section class="plan featured">
        <p class="ribbon">Most popular</p>
        <h2>Standard</h2>
        <p class="price">1400 EGP</p>
        <ul><li>Three services</li><li>Phone support</li><li>Priority
booking</li></ul>
        <a class="btn" href="#">Choose Standard</a>
      </section>
      <section class="plan">
        <h2>Premium</h2>
        <p class="price">750 EGP</p>
        <ul><li>Unlimited services</li><li>Personal advisor</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Premium</a>
      </section>
    </div>
  </main>
</body>
</html>
```

Project 1069: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; text-
```

```
align: center; }
.plans { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(15rem, 1fr)); align-items: start; }
.plan { position: relative; border: 1px solid var(--line); border-
radius: 16px; padding: 2rem 1.5rem; background: #fff; }
.featured { border: 2px solid var(--brand); transform: scale(1.04);
box-shadow: 0 16px 40px rgb(0 0 0 / 12%); }
.ribbon { position: absolute; top: -.8rem; left: 50%; translate: -50%
0; background: var(--brand); color: #fff; font-size: .75rem; padding:
.2rem .8rem; border-radius: 999px; margin: 0; }
.price { font-size: 2rem; font-weight: 800; margin: .5rem 0 1rem; }
ul { list-style: none; padding: 0; text-align: left; }
li { padding: .4rem 0; border-bottom: 1px solid var(--accent); }
li::before { content: "\2713 "; color: var(--brand); }
li.no { color: var(--muted); }
li.no::before { content: "\2717 "; color: #999; }
.btn { display: block; margin-top: 1.5rem; padding: .7rem; border-
radius: 999px; background: var(--brand); color: #fff; text-decoration:
 none; }
```

Project 1069 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - Compare plans</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Compare our packages	The main heading; only one per page.
	Generic block container for grouping and layout.
<section class="plan">	A thematic group of content, normally with its own heading.
Basic	Second-level heading for a section.
600 EGP	A paragraph of text.
- One service - Email support <li class="no">No pri...	Unordered (bulleted) list.

Line	What it does
Choose Basic	A link styled as a button; it navigates, so it is a link and not a <button>.
- Three services - Phone support - Priority booki...	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(15rem, 1fr));	Defines the columns of the grid.
align-items: start;	Aligns items to the start of the cross axis (no stretching).
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 16px;	Rounds the corners.
background: #fff;	Background colour or image.
border: 2px solid var(--brand);	The line around the element: width, style and colour.
transform: scale(1.04);	Enlarges or shrinks the element visually.
box-shadow: 0 16px 40px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
font-size: .75rem;	Size of the text.
border-radius: 999px;	Fully rounded pill shape.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--accent);	A bottom border used as a separator line.

Declaration	What it does
content: "\2713 ";	The text or empty string for a pseudo-element.
display: block;	Element starts on a new line and fills the width (used on links and images).
text-decoration: none;	Removes the underline from links.

Check your work

- Ribbon centred
- Scaled card does not overlap on narrow screens (stacking)
- Features left-aligned
- Prices large and clear

Exercises

1. Add a monthly/yearly toggle with :checked.
2. Convert to a comparison table for many features.
3. Animate the featured card on hover.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 1070: Pricing plans comparison for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 2 | Files: index.html, styles.css

Brief

Present three packages side by side with a highlighted, slightly enlarged middle plan, a 'most popular' ribbon and tick/cross feature lists.

Learning goals

- Emphasise one card with transform: scale and a border
- Position a ribbon over the card edge
- Use ::before glyphs for ticks and crosses

Elements and CSS used

HTML elements	CSS features
section, h2, p, ul, li, a	transform: scale(), position: absolute + translate, align-items: start, ::before content, box-shadow

Build guide

1. Write three .plan sections; give the middle one the featured class and a ribbon p.
2. Grid the plans and align them to the start.
3. Scale the featured plan and add a shadow.
4. Position the ribbon at the top centre.
5. Add ticks with ::before; crosses for .no items.
6. Style the buttons.

Project 1070: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - Compare plans</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Compare our packages</h1>
    <div class="plans">
      <section class="plan">
        <h2>Basic</h2>
        <p class="price">1600 EGP</p>
        <ul><li>One course</li><li>Email support</li><li
class="no">No priority booking</li></ul>
        <a class="btn" href="#">Choose Basic</a>
      </section>
      <section class="plan featured">
        <p class="ribbon">Most popular</p>
        <h2>Standard</h2>
        <p class="price">1800 EGP</p>
        <ul><li>Three courses</li><li>Phone support</li><li>Priority
booking</li></ul>
        <a class="btn" href="#">Choose Standard</a>
      </section>
      <section class="plan">
        <h2>Premium</h2>
        <p class="price">1500 EGP</p>
        <ul><li>Unlimited courses</li><li>Personal advisor</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Premium</a>
      </section>
    </div>
  </main>
</body>
</html>
```

Project 1070: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; text-
```

```
align: center; }
.plans { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(15rem, 1fr)); align-items: start; }
.plan { position: relative; border: 1px solid var(--line); border-
radius: 16px; padding: 2rem 1.5rem; background: #fff; }
.featured { border: 2px solid var(--brand); transform: scale(1.04);
box-shadow: 0 16px 40px rgb(0 0 0 / 12%); }
.ribbon { position: absolute; top: -.8rem; left: 50%; translate: -50%
0; background: var(--brand); color: #fff; font-size: .75rem; padding:
.2rem .8rem; border-radius: 999px; margin: 0; }
.price { font-size: 2rem; font-weight: 800; margin: .5rem 0 1rem; }
ul { list-style: none; padding: 0; text-align: left; }
li { padding: .4rem 0; border-bottom: 1px solid var(--accent); }
li::before { content: "\2713 "; color: var(--brand); }
li.no { color: var(--muted); }
li.no::before { content: "\2717 "; color: #999; }
.btn { display: block; margin-top: 1.5rem; padding: .7rem; border-
radius: 999px; background: var(--brand); color: #fff; text-decoration:
 none; }
```

Project 1070 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - Compare plans</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Compare our packages	The main heading; only one per page.
	Generic block container for grouping and layout.
<section class="plan">	A thematic group of content, normally with its own heading.
Basic	Second-level heading for a section.
1600 EGP	A paragraph of text.
- One course - Email support <li class="no">No prio...	Unordered (bulleted) list.

Line	What it does
Choose Basic	A link styled as a button; it navigates, so it is a link and not a <button>.
- Three courses - Phone support - Priority bookin...	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(15rem, 1fr));	Defines the columns of the grid.
align-items: start;	Aligns items to the start of the cross axis (no stretching).
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 16px;	Rounds the corners.
background: #fff;	Background colour or image.
border: 2px solid var(--brand);	The line around the element: width, style and colour.
transform: scale(1.04);	Enlarges or shrinks the element visually.
box-shadow: 0 16px 40px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
font-size: .75rem;	Size of the text.
border-radius: 999px;	Fully rounded pill shape.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--accent);	A bottom border used as a separator line.

Declaration	What it does
content: "\2713 ";	The text or empty string for a pseudo-element.
display: block;	Element starts on a new line and fills the width (used on links and images).
text-decoration: none;	Removes the underline from links.

Check your work

- Ribbon centred
- Scaled card does not overlap on narrow screens (stacking)
- Features left-aligned
- Prices large and clear

Exercises

1. Add a monthly/yearly toggle with :checked.
2. Convert to a comparison table for many features.
3. Animate the featured card on hover.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 1071: Pricing plans comparison for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 2 | Files: index.html, styles.css

Brief

Present three packages side by side with a highlighted, slightly enlarged middle plan, a 'most popular' ribbon and tick/cross feature lists.

Learning goals

- Emphasise one card with transform: scale and a border
- Position a ribbon over the card edge
- Use ::before glyphs for ticks and crosses

Elements and CSS used

HTML elements	CSS features
section, h2, p, ul, li, a	transform: scale(), position: absolute + translate, align-items: start, ::before content, box-shadow

Build guide

1. Write three .plan sections; give the middle one the featured class and a ribbon p.
2. Grid the plans and align them to the start.
3. Scale the featured plan and add a shadow.
4. Position the ribbon at the top centre.
5. Add ticks with ::before; crosses for .no items.
6. Style the buttons.

Project 1071: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - Compare plans</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Compare our packages</h1>
    <div class="plans">
      <section class="plan">
        <h2>Basic</h2>
        <p class="price">320 EGP</p>
        <ul><li>One dish</li><li>Email support</li><li class="no">No
priority booking</li></ul>
        <a class="btn" href="#">Choose Basic</a>
      </section>
      <section class="plan featured">
        <p class="ribbon">Most popular</p>
        <h2>Standard</h2>
        <p class="price">280 EGP</p>
        <ul><li>Three dishes</li><li>Phone support</li><li>Priority
booking</li></ul>
        <a class="btn" href="#">Choose Standard</a>
      </section>
      <section class="plan">
        <h2>Premium</h2>
        <p class="price">120 EGP</p>
        <ul><li>Unlimited dishes</li><li>Personal advisor</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Premium</a>
      </section>
    </div>
  </main>
</body>
</html>
```

Project 1071: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; text-
```

```
align: center; }
.plans { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(15rem, 1fr)); align-items: start; }
.plan { position: relative; border: 1px solid var(--line); border-
radius: 16px; padding: 2rem 1.5rem; background: #fff; }
.featured { border: 2px solid var(--brand); transform: scale(1.04);
box-shadow: 0 16px 40px rgb(0 0 0 / 12%); }
.ribbon { position: absolute; top: -.8rem; left: 50%; translate: -50%
0; background: var(--brand); color: #fff; font-size: .75rem; padding:
.2rem .8rem; border-radius: 999px; margin: 0; }
.price { font-size: 2rem; font-weight: 800; margin: .5rem 0 1rem; }
ul { list-style: none; padding: 0; text-align: left; }
li { padding: .4rem 0; border-bottom: 1px solid var(--accent); }
li::before { content: "\2713 "; color: var(--brand); }
li.no { color: var(--muted); }
li.no::before { content: "\2717 "; color: #999; }
.btn { display: block; margin-top: 1.5rem; padding: .7rem; border-
radius: 999px; background: var(--brand); color: #fff; text-decoration:
 none; }
```

Project 1071 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - Compare plans</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Compare our packages	The main heading; only one per page.
	Generic block container for grouping and layout.
<section class="plan">	A thematic group of content, normally with its own heading.
Basic	Second-level heading for a section.
320 EGP	A paragraph of text.
- One dish - Email support <li class="no">No priori...	Unordered (bulleted) list.

Line	What it does
Choose Basic	A link styled as a button; it navigates, so it is a link and not a <button>.
- Three dishes - Phone support - Priority booking...	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(15rem, 1fr));	Defines the columns of the grid.
align-items: start;	Aligns items to the start of the cross axis (no stretching).
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 16px;	Rounds the corners.
background: #fff;	Background colour or image.
border: 2px solid var(--brand);	The line around the element: width, style and colour.
transform: scale(1.04);	Enlarges or shrinks the element visually.
box-shadow: 0 16px 40px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
font-size: .75rem;	Size of the text.
border-radius: 999px;	Fully rounded pill shape.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--accent);	A bottom border used as a separator line.

Declaration	What it does
content: "\2713 ";	The text or empty string for a pseudo-element.
display: block;	Element starts on a new line and fills the width (used on links and images).
text-decoration: none;	Removes the underline from links.

Check your work

- Ribbon centred
- Scaled card does not overlap on narrow screens (stacking)
- Features left-aligned
- Prices large and clear

Exercises

1. Add a monthly/yearly toggle with :checked.
2. Convert to a comparison table for many features.
3. Animate the featured card on hover.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 1072: Pricing plans comparison for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 2 | Files: index.html, styles.css

Brief

Present three packages side by side with a highlighted, slightly enlarged middle plan, a 'most popular' ribbon and tick/cross feature lists.

Learning goals

- Emphasise one card with transform: scale and a border
- Position a ribbon over the card edge
- Use ::before glyphs for ticks and crosses

Elements and CSS used

HTML elements	CSS features
section, h2, p, ul, li, a	transform: scale(), position: absolute + translate, align-items: start, ::before content, box-shadow

Build guide

1. Write three .plan sections; give the middle one the featured class and a ribbon p.
2. Grid the plans and align them to the start.
3. Scale the featured plan and add a shadow.
4. Position the ribbon at the top centre.
5. Add ticks with ::before; crosses for .no items.
6. Style the buttons.

Project 1072: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - Compare plans</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Compare our packages</h1>
    <div class="plans">
      <section class="plan">
        <h2>Basic</h2>
        <p class="price">Free</p>
        <ul><li>One programme</li><li>Email support</li><li
class="no">No priority booking</li></ul>
        <a class="btn" href="#">Choose Basic</a>
      </section>
      <section class="plan featured">
        <p class="ribbon">Most popular</p>
        <h2>Standard</h2>
        <p class="price">50 EGP per month</p>
        <ul><li>Three programmes</li><li>Phone support</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Standard</a>
      </section>
      <section class="plan">
        <h2>Premium</h2>
        <p class="price">Free</p>
        <ul><li>Unlimited programmes</li><li>Personal advisor</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Premium</a>
      </section>
    </div>
  </main>
</body>
</html>
```

Project 1072: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; text-
```

```
align: center; }
.plans { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(15rem, 1fr)); align-items: start; }
.plan { position: relative; border: 1px solid var(--line); border-
radius: 16px; padding: 2rem 1.5rem; background: #fff; }
.featured { border: 2px solid var(--brand); transform: scale(1.04);
box-shadow: 0 16px 40px rgb(0 0 0 / 12%); }
.ribbon { position: absolute; top: -.8rem; left: 50%; translate: -50%
0; background: var(--brand); color: #fff; font-size: .75rem; padding:
.2rem .8rem; border-radius: 999px; margin: 0; }
.price { font-size: 2rem; font-weight: 800; margin: .5rem 0 1rem; }
ul { list-style: none; padding: 0; text-align: left; }
li { padding: .4rem 0; border-bottom: 1px solid var(--accent); }
li::before { content: "\2713 "; color: var(--brand); }
li.no { color: var(--muted); }
li.no::before { content: "\2717 "; color: #999; }
.btn { display: block; margin-top: 1.5rem; padding: .7rem; border-
radius: 999px; background: var(--brand); color: #fff; text-decoration:
 none; }
```

Project 1072 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - Compare plans</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Compare our packages	The main heading; only one per page.
	Generic block container for grouping and layout.
<section class="plan">	A thematic group of content, normally with its own heading.
Basic	Second-level heading for a section.
Free	A paragraph of text.
- One programme - Email support <li class="no">No p...	Unordered (bulleted) list.

Line	What it does
Choose Basic	A link styled as a button; it navigates, so it is a link and not a <button>.
- Three programmes - Phone support - Priority boo...	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(15rem, 1fr));	Defines the columns of the grid.
align-items: start;	Aligns items to the start of the cross axis (no stretching).
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 16px;	Rounds the corners.
background: #fff;	Background colour or image.
border: 2px solid var(--brand);	The line around the element: width, style and colour.
transform: scale(1.04);	Enlarges or shrinks the element visually.
box-shadow: 0 16px 40px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
font-size: .75rem;	Size of the text.
border-radius: 999px;	Fully rounded pill shape.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--accent);	A bottom border used as a separator line.

Declaration	What it does
content: "\2713 ";	The text or empty string for a pseudo-element.
display: block;	Element starts on a new line and fills the width (used on links and images).
text-decoration: none;	Removes the underline from links.

Check your work

- Ribbon centred
- Scaled card does not overlap on narrow screens (stacking)
- Features left-aligned
- Prices large and clear

Exercises

1. Add a monthly/yearly toggle with :checked.
2. Convert to a comparison table for many features.
3. Animate the featured card on hover.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 1073: Pricing plans comparison for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Present three packages side by side with a highlighted, slightly enlarged middle plan, a 'most popular' ribbon and tick/cross feature lists.

Learning goals

- Emphasise one card with transform: scale and a border
- Position a ribbon over the card edge
- Use ::before glyphs for ticks and crosses

Elements and CSS used

HTML elements	CSS features
section, h2, p, ul, li, a	transform: scale(), position: absolute + translate, align-items: start, ::before content, box-shadow

Build guide

1. Write three .plan sections; give the middle one the featured class and a ribbon p.
2. Grid the plans and align them to the start.
3. Scale the featured plan and add a shadow.
4. Position the ribbon at the top centre.
5. Add ticks with ::before; crosses for .no items.
6. Style the buttons.

Project 1073: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - Compare plans</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Compare our packages</h1>
    <div class="plans">
      <section class="plan">
        <h2>Basic</h2>
        <p class="price">900 EGP</p>
        <ul><li>One room</li><li>Email support</li><li class="no">No
priority booking</li></ul>
        <a class="btn" href="#">Choose Basic</a>
      </section>
      <section class="plan featured">
        <p class="ribbon">Most popular</p>
        <h2>Standard</h2>
        <p class="price">1800 EGP</p>
        <ul><li>Three rooms</li><li>Phone support</li><li>Priority
booking</li></ul>
        <a class="btn" href="#">Choose Standard</a>
      </section>
      <section class="plan">
        <h2>Premium</h2>
        <p class="price">300 EGP</p>
        <ul><li>Unlimited rooms</li><li>Personal advisor</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Premium</a>
      </section>
    </div>
  </main>
</body>
</html>
```

Project 1073: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; text-
```

```
align: center; }
.plans { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(15rem, 1fr)); align-items: start; }
.plan { position: relative; border: 1px solid var(--line); border-
radius: 16px; padding: 2rem 1.5rem; background: #fff; }
.featured { border: 2px solid var(--brand); transform: scale(1.04);
box-shadow: 0 16px 40px rgb(0 0 0 / 12%); }
.ribbon { position: absolute; top: -.8rem; left: 50%; translate: -50%
0; background: var(--brand); color: #fff; font-size: .75rem; padding:
.2rem .8rem; border-radius: 999px; margin: 0; }
.price { font-size: 2rem; font-weight: 800; margin: .5rem 0 1rem; }
ul { list-style: none; padding: 0; text-align: left; }
li { padding: .4rem 0; border-bottom: 1px solid var(--accent); }
li::before { content: "\2713 "; color: var(--brand); }
li.no { color: var(--muted); }
li.no::before { content: "\2717 "; color: #999; }
.btn { display: block; margin-top: 1.5rem; padding: .7rem; border-
radius: 999px; background: var(--brand); color: #fff; text-decoration:
 none; }
```

Project 1073 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - Compare plans</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Compare our packages	The main heading; only one per page.
	Generic block container for grouping and layout.
<section class="plan">	A thematic group of content, normally with its own heading.
Basic	Second-level heading for a section.
900 EGP	A paragraph of text.
- One room - Email support <li class="no">No priori...	Unordered (bulleted) list.

Line	What it does
Choose Basic	A link styled as a button; it navigates, so it is a link and not a <button>.
- Three rooms - Phone support - Priority booking<...	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(15rem, 1fr));	Defines the columns of the grid.
align-items: start;	Aligns items to the start of the cross axis (no stretching).
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 16px;	Rounds the corners.
background: #fff;	Background colour or image.
border: 2px solid var(--brand);	The line around the element: width, style and colour.
transform: scale(1.04);	Enlarges or shrinks the element visually.
box-shadow: 0 16px 40px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
font-size: .75rem;	Size of the text.
border-radius: 999px;	Fully rounded pill shape.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--accent);	A bottom border used as a separator line.

Declaration	What it does
content: "\2713 ";	The text or empty string for a pseudo-element.
display: block;	Element starts on a new line and fills the width (used on links and images).
text-decoration: none;	Removes the underline from links.

Check your work

- Ribbon centred
- Scaled card does not overlap on narrow screens (stacking)
- Features left-aligned
- Prices large and clear

Exercises

1. Add a monthly/yearly toggle with :checked.
2. Convert to a comparison table for many features.
3. Animate the featured card on hover.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 1074: Pricing plans comparison for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 2 | Files: index.html, styles.css

Brief

Present three packages side by side with a highlighted, slightly enlarged middle plan, a 'most popular' ribbon and tick/cross feature lists.

Learning goals

- Emphasise one card with transform: scale and a border
- Position a ribbon over the card edge
- Use ::before glyphs for ticks and crosses

Elements and CSS used

HTML elements	CSS features
section, h2, p, ul, li, a	transform: scale(), position: absolute + translate, align-items: start, ::before content, box-shadow

Build guide

1. Write three .plan sections; give the middle one the featured class and a ribbon p.
2. Grid the plans and align them to the start.
3. Scale the featured plan and add a shadow.
4. Position the ribbon at the top centre.
5. Add ticks with ::before; crosses for .no items.

6. Style the buttons.

Project 1074: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - Compare plans</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Compare our packages</h1>
    <div class="plans">
      <section class="plan">
        <h2>Basic</h2>
        <p class="price">6500 EGP</p>
        <ul><li>One bike</li><li>Email support</li><li class="no">No
priority booking</li></ul>
        <a class="btn" href="#">Choose Basic</a>
      </section>
      <section class="plan featured">
        <p class="ribbon">Most popular</p>
        <h2>Standard</h2>
        <p class="price">11000 EGP</p>
        <ul><li>Three bikes</li><li>Phone support</li><li>Priority
booking</li></ul>
        <a class="btn" href="#">Choose Standard</a>
      </section>
      <section class="plan">
        <h2>Premium</h2>
        <p class="price">250 EGP</p>
        <ul><li>Unlimited bikes</li><li>Personal advisor</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Premium</a>
      </section>
    </div>
  </main>
</body>
</html>
```

Project 1074: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; text-
```

```
align: center; }
.plans { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(15rem, 1fr)); align-items: start; }
.plan { position: relative; border: 1px solid var(--line); border-
radius: 16px; padding: 2rem 1.5rem; background: #fff; }
.featured { border: 2px solid var(--brand); transform: scale(1.04);
box-shadow: 0 16px 40px rgb(0 0 0 / 12%); }
.ribbon { position: absolute; top: -.8rem; left: 50%; translate: -50%
0; background: var(--brand); color: #fff; font-size: .75rem; padding:
.2rem .8rem; border-radius: 999px; margin: 0; }
.price { font-size: 2rem; font-weight: 800; margin: .5rem 0 1rem; }
ul { list-style: none; padding: 0; text-align: left; }
li { padding: .4rem 0; border-bottom: 1px solid var(--accent); }
li::before { content: "\2713 "; color: var(--brand); }
li.no { color: var(--muted); }
li.no::before { content: "\2717 "; color: #999; }
.btn { display: block; margin-top: 1.5rem; padding: .7rem; border-
radius: 999px; background: var(--brand); color: #fff; text-decoration:
 none; }
```

Project 1074 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - Compare plans</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Compare our packages	The main heading; only one per page.
	Generic block container for grouping and layout.
<section class="plan">	A thematic group of content, normally with its own heading.
Basic	Second-level heading for a section.
6500 EGP	A paragraph of text.
- One bike - Email support <li class="no">No priori...	Unordered (bulleted) list.

Line	What it does
Choose Basic	A link styled as a button; it navigates, so it is a link and not a <button>.
- Three bikes - Phone support - Priority booking<...	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(15rem, 1fr));	Defines the columns of the grid.
align-items: start;	Aligns items to the start of the cross axis (no stretching).
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 16px;	Rounds the corners.
background: #fff;	Background colour or image.
border: 2px solid var(--brand);	The line around the element: width, style and colour.
transform: scale(1.04);	Enlarges or shrinks the element visually.
box-shadow: 0 16px 40px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
font-size: .75rem;	Size of the text.
border-radius: 999px;	Fully rounded pill shape.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--accent);	A bottom border used as a separator line.

Declaration	What it does
content: "\2713 ";	The text or empty string for a pseudo-element.
display: block;	Element starts on a new line and fills the width (used on links and images).
text-decoration: none;	Removes the underline from links.

Check your work

- Ribbon centred
- Scaled card does not overlap on narrow screens (stacking)
- Features left-aligned
- Prices large and clear

Exercises

1. Add a monthly/yearly toggle with :checked.
2. Convert to a comparison table for many features.
3. Animate the featured card on hover.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 1075: Pricing plans comparison for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 2 | Files: index.html, styles.css

Brief

Present three packages side by side with a highlighted, slightly enlarged middle plan, a 'most popular' ribbon and tick/cross feature lists.

Learning goals

- Emphasise one card with transform: scale and a border
- Position a ribbon over the card edge
- Use ::before glyphs for ticks and crosses

Elements and CSS used

HTML elements	CSS features
section, h2, p, ul, li, a	transform: scale(), position: absolute + translate, align-items: start, ::before content, box-shadow

Build guide

1. Write three .plan sections; give the middle one the featured class and a ribbon p.
2. Grid the plans and align them to the start.
3. Scale the featured plan and add a shadow.
4. Position the ribbon at the top centre.
5. Add ticks with ::before; crosses for .no items.
6. Style the buttons.

Project 1075: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - Compare plans</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <h1>Compare our packages</h1>
    <div class="plans">
      <section class="plan">
        <h2>Basic</h2>
        <p class="price">Free</p>
        <ul><li>One workshop</li><li>Email support</li><li
class="no">No priority booking</li></ul>
        <a class="btn" href="#">Choose Basic</a>
      </section>
      <section class="plan featured">
        <p class="ribbon">Most popular</p>
        <h2>Standard</h2>
        <p class="price">Free</p>
        <ul><li>Three workshops</li><li>Phone support</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Standard</a>
      </section>
      <section class="plan">
        <h2>Premium</h2>
        <p class="price">Free</p>
        <ul><li>Unlimited workshops</li><li>Personal advisor</
li><li>Priority booking</li></ul>
        <a class="btn" href="#">Choose Premium</a>
      </section>
    </div>
  </main>
</body>
</html>
```

Project 1075: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 64rem; margin: 2rem auto; padding: 0 1rem; text-
```

```
align: center; }
.plans { display: grid; gap: 1.5rem; grid-template-columns: repeat(
auto-fit, minmax(15rem, 1fr)); align-items: start; }
.plan { position: relative; border: 1px solid var(--line); border-
radius: 16px; padding: 2rem 1.5rem; background: #fff; }
.featured { border: 2px solid var(--brand); transform: scale(1.04);
box-shadow: 0 16px 40px rgb(0 0 0 / 12%); }
.ribbon { position: absolute; top: -.8rem; left: 50%; translate: -50%
0; background: var(--brand); color: #fff; font-size: .75rem; padding:
.2rem .8rem; border-radius: 999px; margin: 0; }
.price { font-size: 2rem; font-weight: 800; margin: .5rem 0 1rem; }
ul { list-style: none; padding: 0; text-align: left; }
li { padding: .4rem 0; border-bottom: 1px solid var(--accent); }
li::before { content: "\2713 "; color: var(--brand); }
li.no { color: var(--muted); }
li.no::before { content: "\2717 "; color: #999; }
.btn { display: block; margin-top: 1.5rem; padding: .7rem; border-
radius: 999px; background: var(--brand); color: #fff; text-decoration:
 none; }
```

Project 1075 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - Compare plans</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
Compare our packages	The main heading; only one per page.
	Generic block container for grouping and layout.
<section class="plan">	A thematic group of content, normally with its own heading.
Basic	Second-level heading for a section.
Free	A paragraph of text.
- One workshop - Email support <li class="no">No pr...	Unordered (bulleted) list.

Line	What it does
Choose Basic	A link styled as a button; it navigates, so it is a link and not a <button>.
- Three workshops - Phone support - Priority book...	One list item.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 64rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
text-align: center;	Centres inline content such as text.
display: grid;	Turns the element into a grid container.

Declaration	What it does
gap: 1.5rem;	Space between grid or flex items without extra margins.
grid-template-columns: repeat(auto-fit, minmax(15rem, 1fr));	Defines the columns of the grid.
align-items: start;	Aligns items to the start of the cross axis (no stretching).
position: relative;	Keeps normal flow but becomes the reference for absolutely positioned children.
border: 1px solid var(--line);	Changes the visual order of a flex item without changing the source.
border-radius: 16px;	Rounds the corners.
background: #fff;	Background colour or image.
border: 2px solid var(--brand);	The line around the element: width, style and colour.
transform: scale(1.04);	Enlarges or shrinks the element visually.
box-shadow: 0 16px 40px rgb(0 0 0 / 12%);	Soft shadow that lifts the element from the page.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
translate: -50% 0;	Moves the element without affecting the layout of others.
font-size: .75rem;	Size of the text.
border-radius: 999px;	Fully rounded pill shape.
font-weight: 800;	Thickness of the text.
list-style: none;	Removes bullets or numbers from a list.
border-bottom: 1px solid var(--accent);	A bottom border used as a separator line.

Declaration	What it does
content: "\2713 ";	The text or empty string for a pseudo-element.
display: block;	Element starts on a new line and fills the width (used on links and images).
text-decoration: none;	Removes the underline from links.

Check your work

- Ribbon centred
- Scaled card does not overlap on narrow screens (stacking)
- Features left-aligned
- Prices large and clear

Exercises

1. Add a monthly/yearly toggle with :checked.
2. Convert to a comparison table for many features.
3. Animate the featured card on hover.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Step-by-step how-to page

Level 2 | 25 projects, one per theme

Write a tutorial page with a 'you will need' box and numbered steps where each number is a large circle generated by CSS counters inside a grid row.

Project 1076: Step-by-step how-to page for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 2 | Files: index.html, styles.css

Brief

Write a tutorial page with a 'you will need' box and numbered steps where each number is a large circle generated by CSS counters inside a grid row.

Learning goals

- Use headings inside list items
- Generate step numbers with counters
- Use a two-column grid per list item with the ::before in the first column

Elements and CSS used

HTML elements	CSS features
article, h1, p, section, h2, ul, ol, li, h3	counter-reset/increment, grid-template-columns: 3rem 1fr, grid-row: 1 / 3, grid-column: 2, border-radius: 50%

Build guide

1. Write the article with lead and 'You will need' section.
2. Write the ol; each li has an h3 and a p.
3. Remove list numbers and reset a counter.
4. Make each li a grid of two columns.
5. Put the counter in ::before spanning two rows.

6. Place h3 and p in column two.

Project 1076: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>How we make Learn HTML - Cairo Book Shop</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="howto">
      <h1>How we make Learn HTML</h1>
      <p class="lead">From your first tag to a complete page. Here is
the process, step by step, from Mohamed Khattab.</p>
      <section class="need">
        <h2>You will need</h2>
        <ul>
          <li>Time: about 2 hours</li>
          <li>Skill level: beginner</li>
          <li>Cost: around 120 EGP</li>
        </ul>
      </section>
      <h2>Steps</h2>
      <ol class="steps">
        <li><h3>Prepare</h3><p>Gather everything and read the whole
process once.</p></li>
        <li><h3>Start</h3><p>Begin slowly; the first step sets the
quality of the rest.</p></li>
        <li><h3>Check</h3><p>Compare against our standard. Adjust if
needed.</p></li>
        <li><h3>Finish</h3><p>Rest, present and enjoy your book.</p></
li>
      </ol>
    </article>
  </main>
</body>
</html>
```

Project 1076: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.lead { font-size: 1.2rem; color: var(--muted); }
```

```
.need { background: var(--accent); padding: 1rem 1.5rem; border-
radius: 12px; }
.need h2 { margin-top: 0; font-size: 1rem; text-transform: uppercase;
letter-spacing: .05em; }
.steps { list-style: none; padding: 0; counter-reset: step; }
.steps li { counter-increment: step; display: grid; grid-template-
columns: 3rem 1fr; gap: 0 1rem; padding: 1rem 0; border-bottom: 1px
solid var(--line); }
.steps li::before { content: counter(step); grid-row: 1 / 3; width:
3rem; height: 3rem; border-radius: 50%; background: var(--brand);
color: #fff; display: grid; place-items: center; font-weight: 800;
font-size: 1.2rem; }
.steps h3 { margin: 0; grid-column: 2; }
.steps p { margin: .2rem 0 0; grid-column: 2; color: var(--muted); }
```

Project 1076 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>How we make Learn HTML - Cairo Book Shop</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="howto">	A self-contained piece: card, post, product.
How we make Learn HTML	The main heading; only one per page.
<p class="lead">From your first tag to a complete page. Here is the...	A paragraph of text.
<section class="need">	A thematic group of content, normally with its own heading.
You will need	Second-level heading for a section.
	Unordered (bulleted) list.
Time: about 2 hours	One list item.

Line	What it does
<ol class="steps">	Ordered (numbered) list; the order matters.
<h3>Prepare</h3><p>Gather everything and read the whole process...	Third-level heading, inside an h2 section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.2rem;	Size of the text.
background: var(--accent);	Background colour or image.

Declaration	What it does
border-radius: 12px;	Rounds the corners.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
counter-reset: step;	Starts a CSS counter.
counter-increment: step;	Adds one to the counter for each matching element.
display: grid;	Turns the element into a grid container.
grid-template-columns: 3rem 1fr;	Defines the columns of the grid.
gap: 0 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
content: counter(step);	The text or empty string for a pseudo-element.
border-radius: 50%;	Turns a square into a circle.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 800;	Thickness of the text.

Check your work

- Numbers generated, list still an ol
- Headings inside li are h3
- Circle stays aligned with the heading
- Readable width

Exercises

1. Add images to steps.
2. Add a 'mark as done' checkbox per step with :has() styling.
3. Add schema.org HowTo microdata.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 1077: Step-by-step how-to page for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 2 | Files: index.html, styles.css

Brief

Write a tutorial page with a 'you will need' box and numbered steps where each number is a large circle generated by CSS counters inside a grid row.

Learning goals

- Use headings inside list items
- Generate step numbers with counters
- Use a two-column grid per list item with the ::before in the first column

Elements and CSS used

HTML elements	CSS features
article, h1, p, section, h2, ul, ol, li, h3	counter-reset/increment, grid-template-columns: 3rem 1fr, grid-row: 1 / 3, grid-column: 2, border-radius: 50%

Build guide

1. Write the article with lead and 'You will need' section.
2. Write the ol; each li has an h3 and a p.
3. Remove list numbers and reset a counter.
4. Make each li a grid of two columns.
5. Put the counter in ::before spanning two rows.
6. Place h3 and p in column two.

Project 1077: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>How we make Sourdough loaf - Nile Bakery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="howto">
      <h1>How we make Sourdough loaf</h1>
      <p class="lead">Slow fermented, crisp crust. Here is the
process, step by step, from Sara Adel.</p>
      <section class="need">
        <h2>You will need</h2>
        <ul>
          <li>Time: about 2 hours</li>
          <li>Skill level: beginner</li>
          <li>Cost: around 60 EGP</li>
        </ul>
      </section>
      <h2>Steps</h2>
      <ol class="steps">
        <li><h3>Prepare</h3><p>Gather everything and read the whole
process once.</p></li>
        <li><h3>Start</h3><p>Begin slowly; the first step sets the
quality of the rest.</p></li>
        <li><h3>Check</h3><p>Compare against our standard. Adjust if
needed.</p></li>
        <li><h3>Finish</h3><p>Rest, present and enjoy your pastry.</
p></li>
      </ol>
    </article>
  </main>
</body>
</html>
```

Project 1077: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.lead { font-size: 1.2rem; color: var(--muted); }
```

```
.need { background: var(--accent); padding: 1rem 1.5rem; border-
radius: 12px; }
.need h2 { margin-top: 0; font-size: 1rem; text-transform: uppercase;
letter-spacing: .05em; }
.steps { list-style: none; padding: 0; counter-reset: step; }
.steps li { counter-increment: step; display: grid; grid-template-
columns: 3rem 1fr; gap: 0 1rem; padding: 1rem 0; border-bottom: 1px
solid var(--line); }
.steps li::before { content: counter(step); grid-row: 1 / 3; width:
3rem; height: 3rem; border-radius: 50%; background: var(--brand);
color: #fff; display: grid; place-items: center; font-weight: 800;
font-size: 1.2rem; }
.steps h3 { margin: 0; grid-column: 2; }
.steps p { margin: .2rem 0 0; grid-column: 2; color: var(--muted); }
```

Project 1077 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>How we make Sourdough loaf - Nile Bakery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="howto">	A self-contained piece: card, post, product.
How we make Sourdough loaf	The main heading; only one per page.
<p class="lead">Slow fermented, crisp crust. Here is the process, s...	A paragraph of text.
<section class="need">	A thematic group of content, normally with its own heading.
You will need	Second-level heading for a section.
	Unordered (bulleted) list.
Time: about 2 hours	One list item.

Line	What it does
<ol class="steps">	Ordered (numbered) list; the order matters.
<h3>Prepare</h3><p>Gather everything and read the whole process...	Third-level heading, inside an h2 section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.2rem;	Size of the text.
background: var(--accent);	Background colour or image.

Declaration	What it does
border-radius: 12px;	Rounds the corners.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
counter-reset: step;	Starts a CSS counter.
counter-increment: step;	Adds one to the counter for each matching element.
display: grid;	Turns the element into a grid container.
grid-template-columns: 3rem 1fr;	Defines the columns of the grid.
gap: 0 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
content: counter(step);	The text or empty string for a pseudo-element.
border-radius: 50%;	Turns a square into a circle.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 800;	Thickness of the text.

Check your work

- Numbers generated, list still an ol
- Headings inside li are h3
- Circle stays aligned with the heading
- Readable width

Exercises

1. Add images to steps.
2. Add a 'mark as done' checkbox per step with :has() styling.
3. Add schema.org HowTo microdata.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 1078: Step-by-step how-to page for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 2 | Files: index.html, styles.css

Brief

Write a tutorial page with a 'you will need' box and numbered steps where each number is a large circle generated by CSS counters inside a grid row.

Learning goals

- Use headings inside list items
- Generate step numbers with counters
- Use a two-column grid per list item with the ::before in the first column

Elements and CSS used

HTML elements	CSS features
article, h1, p, section, h2, ul, ol, li, h3	counter-reset/increment, grid-template-columns: 3rem 1fr, grid-row: 1 / 3, grid-column: 2, border-radius: 50%

Build guide

1. Write the article with lead and 'You will need' section.
2. Write the ol; each li has an h3 and a p.
3. Remove list numbers and reset a counter.
4. Make each li a grid of two columns.
5. Put the counter in ::before spanning two rows.

6. Place h3 and p in column two.

Project 1078: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>How we make Morning yoga - Pyramid Fitness</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="howto">
      <h1>How we make Morning yoga</h1>
      <p class="lead">Flexibility and calm, 60 minutes. Here is the
process, step by step, from Omar Farouk.</p>
      <section class="need">
        <h2>You will need</h2>
        <ul>
          <li>Time: about 2 hours</li>
          <li>Skill level: beginner</li>
          <li>Cost: around 100 EGP</li>
        </ul>
      </section>
      <h2>Steps</h2>
      <ol class="steps">
        <li><h3>Prepare</h3><p>Gather everything and read the whole
process once.</p></li>
        <li><h3>Start</h3><p>Begin slowly; the first step sets the
quality of the rest.</p></li>
        <li><h3>Check</h3><p>Compare against our standard. Adjust if
needed.</p></li>
        <li><h3>Finish</h3><p>Rest, present and enjoy your class.</
p></li>
      </ol>
    </article>
  </main>
</body>
</html>
```

Project 1078: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.lead { font-size: 1.2rem; color: var(--muted); }
```

```
.need { background: var(--accent); padding: 1rem 1.5rem; border-
radius: 12px; }
.need h2 { margin-top: 0; font-size: 1rem; text-transform: uppercase;
letter-spacing: .05em; }
.steps { list-style: none; padding: 0; counter-reset: step; }
.steps li { counter-increment: step; display: grid; grid-template-
columns: 3rem 1fr; gap: 0 1rem; padding: 1rem 0; border-bottom: 1px
solid var(--line); }
.steps li::before { content: counter(step); grid-row: 1 / 3; width:
3rem; height: 3rem; border-radius: 50%; background: var(--brand);
color: #fff; display: grid; place-items: center; font-weight: 800;
font-size: 1.2rem; }
.steps h3 { margin: 0; grid-column: 2; }
.steps p { margin: .2rem 0 0; grid-column: 2; color: var(--muted); }
```

Project 1078 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>How we make Morning yoga - Pyramid Fitness</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="howto">	A self-contained piece: card, post, product.
How we make Morning yoga	The main heading; only one per page.
<p class="lead">Flexibility and calm, 60 minutes. Here is the proce...	A paragraph of text.
<section class="need">	A thematic group of content, normally with its own heading.
You will need	Second-level heading for a section.
	Unordered (bulleted) list.
Time: about 2 hours	One list item.

Line	What it does
<ol class="steps">	Ordered (numbered) list; the order matters.
<h3>Prepare</h3><p>Gather everything and read the whole process...	Third-level heading, inside an h2 section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.2rem;	Size of the text.
background: var(--accent);	Background colour or image.

Declaration	What it does
border-radius: 12px;	Rounds the corners.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
counter-reset: step;	Starts a CSS counter.
counter-increment: step;	Adds one to the counter for each matching element.
display: grid;	Turns the element into a grid container.
grid-template-columns: 3rem 1fr;	Defines the columns of the grid.
gap: 0 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
content: counter(step);	The text or empty string for a pseudo-element.
border-radius: 50%;	Turns a square into a circle.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 800;	Thickness of the text.

Check your work

- Numbers generated, list still an ol
- Headings inside li are h3
- Circle stays aligned with the heading
- Readable width

Exercises

1. Add images to steps.
2. Add a 'mark as done' checkbox per step with :has() styling.
3. Add schema.org HowTo microdata.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 1079: Step-by-step how-to page for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 2 | Files: index.html, styles.css

Brief

Write a tutorial page with a 'you will need' box and numbered steps where each number is a large circle generated by CSS counters inside a grid row.

Learning goals

- Use headings inside list items
- Generate step numbers with counters
- Use a two-column grid per list item with the ::before in the first column

Elements and CSS used

HTML elements	CSS features
article, h1, p, section, h2, ul, ol, li, h3	counter-reset/increment, grid-template-columns: 3rem 1fr, grid-row: 1 / 3, grid-column: 2, border-radius: 50%

Build guide

1. Write the article with lead and 'You will need' section.
2. Write the ol; each li has an h3 and a p.
3. Remove list numbers and reset a counter.
4. Make each li a grid of two columns.
5. Put the counter in ::before spanning two rows.

6. Place h3 and p in column two.

Project 1079: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>How we make Check-up - Delta Dental Clinic</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="howto">
      <h1>How we make Check-up</h1>
      <p class="lead">Examination and cleaning. Here is the process,
step by step, from Dr. Hana Youssef.</p>
      <section class="need">
        <h2>You will need</h2>
        <ul>
          <li>Time: about 2 hours</li>
          <li>Skill level: beginner</li>
          <li>Cost: around 300 EGP</li>
        </ul>
      </section>
      <h2>Steps</h2>
      <ol class="steps">
        <li><h3>Prepare</h3><p>Gather everything and read the whole
process once.</p></li>
        <li><h3>Start</h3><p>Begin slowly; the first step sets the
quality of the rest.</p></li>
        <li><h3>Check</h3><p>Compare against our standard. Adjust if
needed.</p></li>
        <li><h3>Finish</h3><p>Rest, present and enjoy your service.</
p></li>
      </ol>
    </article>
  </main>
</body>
</html>
```

Project 1079: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.lead { font-size: 1.2rem; color: var(--muted); }
```

```
.need { background: var(--accent); padding: 1rem 1.5rem; border-
radius: 12px; }
.need h2 { margin-top: 0; font-size: 1rem; text-transform: uppercase;
letter-spacing: .05em; }
.steps { list-style: none; padding: 0; counter-reset: step; }
.steps li { counter-increment: step; display: grid; grid-template-
columns: 3rem 1fr; gap: 0 1rem; padding: 1rem 0; border-bottom: 1px
solid var(--line); }
.steps li::before { content: counter(step); grid-row: 1 / 3; width:
3rem; height: 3rem; border-radius: 50%; background: var(--brand);
color: #fff; display: grid; place-items: center; font-weight: 800;
font-size: 1.2rem; }
.steps h3 { margin: 0; grid-column: 2; }
.steps p { margin: .2rem 0 0; grid-column: 2; color: var(--muted); }
```

Project 1079 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>How we make Check-up - Delta Dental Clinic</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="howto">	A self-contained piece: card, post, product.
How we make Check-up	The main heading; only one per page.
<p class="lead">Examination and cleaning. Here is the process, step…	A paragraph of text.
<section class="need">	A thematic group of content, normally with its own heading.
You will need	Second-level heading for a section.
	Unordered (bulleted) list.
Time: about 2 hours	One list item.

Line	What it does
<ol class="steps">	Ordered (numbered) list; the order matters.
<h3>Prepare</h3><p>Gather everything and read the whole process...	Third-level heading, inside an h2 section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.2rem;	Size of the text.
background: var(--accent);	Background colour or image.

Declaration	What it does
border-radius: 12px;	Rounds the corners.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
counter-reset: step;	Starts a CSS counter.
counter-increment: step;	Adds one to the counter for each matching element.
display: grid;	Turns the element into a grid container.
grid-template-columns: 3rem 1fr;	Defines the columns of the grid.
gap: 0 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
content: counter(step);	The text or empty string for a pseudo-element.
border-radius: 50%;	Turns a square into a circle.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 800;	Thickness of the text.

Check your work

- Numbers generated, list still an ol
- Headings inside li are h3
- Circle stays aligned with the heading
- Readable width

Exercises

1. Add images to steps.
2. Add a 'mark as done' checkbox per step with :has() styling.
3. Add schema.org HowTo microdata.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 1080: Step-by-step how-to page for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 2 | Files: index.html, styles.css

Brief

Write a tutorial page with a 'you will need' box and numbered steps where each number is a large circle generated by CSS counters inside a grid row.

Learning goals

- Use headings inside list items
- Generate step numbers with counters
- Use a two-column grid per list item with the ::before in the first column

Elements and CSS used

HTML elements	CSS features
article, h1, p, section, h2, ul, ol, li, h3	counter-reset/increment, grid-template-columns: 3rem 1fr, grid-row: 1 / 3, grid-column: 2, border-radius: 50%

Build guide

1. Write the article with lead and 'You will need' section.
2. Write the ol; each li has an h3 and a p.
3. Remove list numbers and reset a counter.
4. Make each li a grid of two columns.
5. Put the counter in ::before spanning two rows.
6. Place h3 and p in column two.

Project 1080: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>How we make Luxor day trip - Red Sea Travel</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="howto">
      <h1>How we make Luxor day trip</h1>
      <p class="lead">Karnak, Valley of the Kings. Here is the
process, step by step, from Laila Mansour.</p>
      <section class="need">
        <h2>You will need</h2>
        <ul>
          <li>Time: about 2 hours</li>
          <li>Skill level: beginner</li>
          <li>Cost: around 1200 EGP</li>
        </ul>
      </section>
      <h2>Steps</h2>
      <ol class="steps">
        <li><h3>Prepare</h3><p>Gather everything and read the whole
process once.</p></li>
        <li><h3>Start</h3><p>Begin slowly; the first step sets the
quality of the rest.</p></li>
        <li><h3>Check</h3><p>Compare against our standard. Adjust if
needed.</p></li>
        <li><h3>Finish</h3><p>Rest, present and enjoy your tour.</p></
li>
      </ol>
    </article>
  </main>
</body>
</html>
```

Project 1080: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.lead { font-size: 1.2rem; color: var(--muted); }
```

```
.need { background: var(--accent); padding: 1rem 1.5rem; border-
radius: 12px; }
.need h2 { margin-top: 0; font-size: 1rem; text-transform: uppercase;
letter-spacing: .05em; }
.steps { list-style: none; padding: 0; counter-reset: step; }
.steps li { counter-increment: step; display: grid; grid-template-
columns: 3rem 1fr; gap: 0 1rem; padding: 1rem 0; border-bottom: 1px
solid var(--line); }
.steps li::before { content: counter(step); grid-row: 1 / 3; width:
3rem; height: 3rem; border-radius: 50%; background: var(--brand);
color: #fff; display: grid; place-items: center; font-weight: 800;
font-size: 1.2rem; }
.steps h3 { margin: 0; grid-column: 2; }
.steps p { margin: .2rem 0 0; grid-column: 2; color: var(--muted); }
```

Project 1080 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>How we make Luxor day trip - Red Sea Travel</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="howto">	A self-contained piece: card, post, product.
How we make Luxor day trip	The main heading; only one per page.
<p class="lead">Karnak, Valley of the Kings. Here is the process, s...	A paragraph of text.
<section class="need">	A thematic group of content, normally with its own heading.
You will need	Second-level heading for a section.
	Unordered (bulleted) list.
Time: about 2 hours	One list item.

Line	What it does
<ol class="steps">	Ordered (numbered) list; the order matters.
<h3>Prepare</h3><p>Gather everything and read the whole process...	Third-level heading, inside an h2 section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.2rem;	Size of the text.
background: var(--accent);	Background colour or image.

Declaration	What it does
border-radius: 12px;	Rounds the corners.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
counter-reset: step;	Starts a CSS counter.
counter-increment: step;	Adds one to the counter for each matching element.
display: grid;	Turns the element into a grid container.
grid-template-columns: 3rem 1fr;	Defines the columns of the grid.
gap: 0 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
content: counter(step);	The text or empty string for a pseudo-element.
border-radius: 50%;	Turns a square into a circle.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 800;	Thickness of the text.

Check your work

- Numbers generated, list still an ol
- Headings inside li are h3
- Circle stays aligned with the heading
- Readable width

Exercises

1. Add images to steps.
2. Add a 'mark as done' checkbox per step with :has() styling.
3. Add schema.org HowTo microdata.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 1081: Step-by-step how-to page for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Write a tutorial page with a 'you will need' box and numbered steps where each number is a large circle generated by CSS counters inside a grid row.

Learning goals

- Use headings inside list items
- Generate step numbers with counters
- Use a two-column grid per list item with the ::before in the first column

Elements and CSS used

HTML elements	CSS features
article, h1, p, section, h2, ul, ol, li, h3	counter-reset/increment, grid-template-columns: 3rem 1fr, grid-row: 1 / 3, grid-column: 2, border-radius: 50%

Build guide

1. Write the article with lead and 'You will need' section.
2. Write the ol; each li has an h3 and a p.
3. Remove list numbers and reset a counter.
4. Make each li a grid of two columns.
5. Put the counter in ::before spanning two rows.

6. Place h3 and p in column two.

Project 1081: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>How we make English A1 - Lotus Language School</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="howto">
      <h1>How we make English A1</h1>
      <p class="lead">Beginner, 8 weeks. Here is the process, step by
step, from Nour El Din.</p>
      <section class="need">
        <h2>You will need</h2>
        <ul>
          <li>Time: about 2 hours</li>
          <li>Skill level: beginner</li>
          <li>Cost: around 1800 EGP</li>
        </ul>
      </section>
      <h2>Steps</h2>
      <ol class="steps">
        <li><h3>Prepare</h3><p>Gather everything and read the whole
process once.</p></li>
        <li><h3>Start</h3><p>Begin slowly; the first step sets the
quality of the rest.</p></li>
        <li><h3>Check</h3><p>Compare against our standard. Adjust if
needed.</p></li>
        <li><h3>Finish</h3><p>Rest, present and enjoy your course.</
p></li>
      </ol>
    </article>
  </main>
</body>
</html>
```

Project 1081: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.lead { font-size: 1.2rem; color: var(--muted); }
```

```
.need { background: var(--accent); padding: 1rem 1.5rem; border-
radius: 12px; }
.need h2 { margin-top: 0; font-size: 1rem; text-transform: uppercase;
letter-spacing: .05em; }
.steps { list-style: none; padding: 0; counter-reset: step; }
.steps li { counter-increment: step; display: grid; grid-template-
columns: 3rem 1fr; gap: 0 1rem; padding: 1rem 0; border-bottom: 1px
solid var(--line); }
.steps li::before { content: counter(step); grid-row: 1 / 3; width:
3rem; height: 3rem; border-radius: 50%; background: var(--brand);
color: #fff; display: grid; place-items: center; font-weight: 800;
font-size: 1.2rem; }
.steps h3 { margin: 0; grid-column: 2; }
.steps p { margin: .2rem 0 0; grid-column: 2; color: var(--muted); }
```

Project 1081 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>How we make English A1 - Lotus Language School</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="howto">	A self-contained piece: card, post, product.
How we make English A1	The main heading; only one per page.
<p class="lead">Beginner, 8 weeks. Here is the process, step by ste...	A paragraph of text.
<section class="need">	A thematic group of content, normally with its own heading.
You will need	Second-level heading for a section.
	Unordered (bulleted) list.
Time: about 2 hours	One list item.

Line	What it does
<ol class="steps">	Ordered (numbered) list; the order matters.
<h3>Prepare</h3><p>Gather everything and read the whole process...	Third-level heading, inside an h2 section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.2rem;	Size of the text.
background: var(--accent);	Background colour or image.

Declaration	What it does
border-radius: 12px;	Rounds the corners.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
counter-reset: step;	Starts a CSS counter.
counter-increment: step;	Adds one to the counter for each matching element.
display: grid;	Turns the element into a grid container.
grid-template-columns: 3rem 1fr;	Defines the columns of the grid.
gap: 0 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
content: counter(step);	The text or empty string for a pseudo-element.
border-radius: 50%;	Turns a square into a circle.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 800;	Thickness of the text.

Check your work

- Numbers generated, list still an ol
- Headings inside li are h3
- Circle stays aligned with the heading
- Readable width

Exercises

1. Add images to steps.
2. Add a 'mark as done' checkbox per step with :has() styling.
3. Add schema.org HowTo microdata.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 1082: Step-by-step how-to page for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 2 | Files: index.html, styles.css

Brief

Write a tutorial page with a 'you will need' box and numbered steps where each number is a large circle generated by CSS counters inside a grid row.

Learning goals

- Use headings inside list items
- Generate step numbers with counters
- Use a two-column grid per list item with the ::before in the first column

Elements and CSS used

HTML elements	CSS features
article, h1, p, section, h2, ul, ol, li, h3	counter-reset/increment, grid-template-columns: 3rem 1fr, grid-row: 1 / 3, grid-column: 2, border-radius: 50%

Build guide

1. Write the article with lead and 'You will need' section.
2. Write the ol; each li has an h3 and a p.
3. Remove list numbers and reset a counter.
4. Make each li a grid of two columns.
5. Put the counter in ::before spanning two rows.

6. Place h3 and p in column two.

Project 1082: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>How we make Flat white - Green Leaf Cafe</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="howto">
      <h1>How we make Flat white</h1>
      <p class="lead">Double shot, silky milk. Here is the process,
step by step, from Karim Said.</p>
      <section class="need">
        <h2>You will need</h2>
        <ul>
          <li>Time: about 2 hours</li>
          <li>Skill level: beginner</li>
          <li>Cost: around 55 EGP</li>
        </ul>
      </section>
      <h2>Steps</h2>
      <ol class="steps">
        <li><h3>Prepare</h3><p>Gather everything and read the whole
process once.</p></li>
        <li><h3>Start</h3><p>Begin slowly; the first step sets the
quality of the rest.</p></li>
        <li><h3>Check</h3><p>Compare against our standard. Adjust if
needed.</p></li>
        <li><h3>Finish</h3><p>Rest, present and enjoy your drink.</
p></li>
      </ol>
    </article>
  </main>
</body>
</html>
```

Project 1082: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.lead { font-size: 1.2rem; color: var(--muted); }
```

```
.need { background: var(--accent); padding: 1rem 1.5rem; border-
radius: 12px; }
.need h2 { margin-top: 0; font-size: 1rem; text-transform: uppercase;
letter-spacing: .05em; }
.steps { list-style: none; padding: 0; counter-reset: step; }
.steps li { counter-increment: step; display: grid; grid-template-
columns: 3rem 1fr; gap: 0 1rem; padding: 1rem 0; border-bottom: 1px
solid var(--line); }
.steps li::before { content: counter(step); grid-row: 1 / 3; width:
3rem; height: 3rem; border-radius: 50%; background: var(--brand);
color: #fff; display: grid; place-items: center; font-weight: 800;
font-size: 1.2rem; }
.steps h3 { margin: 0; grid-column: 2; }
.steps p { margin: .2rem 0 0; grid-column: 2; color: var(--muted); }
```

Project 1082 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>How we make Flat white - Green Leaf Cafe</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="howto">	A self-contained piece: card, post, product.
How we make Flat white	The main heading; only one per page.
<p class="lead">Double shot, silky milk. Here is the process, step ...	A paragraph of text.
<section class="need">	A thematic group of content, normally with its own heading.
You will need	Second-level heading for a section.
	Unordered (bulleted) list.
Time: about 2 hours	One list item.

Line	What it does
<ol class="steps">	Ordered (numbered) list; the order matters.
<h3>Prepare</h3><p>Gather everything and read the whole process...	Third-level heading, inside an h2 section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.2rem;	Size of the text.
background: var(--accent);	Background colour or image.

Declaration	What it does
border-radius: 12px;	Rounds the corners.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
counter-reset: step;	Starts a CSS counter.
counter-increment: step;	Adds one to the counter for each matching element.
display: grid;	Turns the element into a grid container.
grid-template-columns: 3rem 1fr;	Defines the columns of the grid.
gap: 0 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
content: counter(step);	The text or empty string for a pseudo-element.
border-radius: 50%;	Turns a square into a circle.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 800;	Thickness of the text.

Check your work

- Numbers generated, list still an ol
- Headings inside li are h3
- Circle stays aligned with the heading
- Readable width

Exercises

1. Add images to steps.
2. Add a 'mark as done' checkbox per step with :has() styling.
3. Add schema.org HowTo microdata.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 1083: Step-by-step how-to page for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 2 | Files: index.html, styles.css

Brief

Write a tutorial page with a 'you will need' box and numbered steps where each number is a large circle generated by CSS counters inside a grid row.

Learning goals

- Use headings inside list items
- Generate step numbers with counters
- Use a two-column grid per list item with the ::before in the first column

Elements and CSS used

HTML elements	CSS features
article, h1, p, section, h2, ul, ol, li, h3	counter-reset/increment, grid-template-columns: 3rem 1fr, grid-row: 1 / 3, grid-column: 2, border-radius: 50%

Build guide

1. Write the article with lead and 'You will need' section.
2. Write the ol; each li has an h3 and a p.
3. Remove list numbers and reset a counter.
4. Make each li a grid of two columns.
5. Put the counter in ::before spanning two rows.

6. Place h3 and p in column two.

Project 1083: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>How we make Mount Sinai sunrise - Sinai Trekking Club</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="howto">
      <h1>How we make Mount Sinai sunrise</h1>
      <p class="lead">Night climb, 7 km. Here is the process, step by
step, from Yara Hamdy.</p>
      <section class="need">
        <h2>You will need</h2>
        <ul>
          <li>Time: about 2 hours</li>
          <li>Skill level: beginner</li>
          <li>Cost: around 400 EGP</li>
        </ul>
      </section>
      <h2>Steps</h2>
      <ol class="steps">
        <li><h3>Prepare</h3><p>Gather everything and read the whole
process once.</p></li>
        <li><h3>Start</h3><p>Begin slowly; the first step sets the
quality of the rest.</p></li>
        <li><h3>Check</h3><p>Compare against our standard. Adjust if
needed.</p></li>
        <li><h3>Finish</h3><p>Rest, present and enjoy your hike.</p></
li>
      </ol>
    </article>
  </main>
</body>
</html>
```

Project 1083: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.lead { font-size: 1.2rem; color: var(--muted); }
```

```
.need { background: var(--accent); padding: 1rem 1.5rem; border-
radius: 12px; }
.need h2 { margin-top: 0; font-size: 1rem; text-transform: uppercase;
letter-spacing: .05em; }
.steps { list-style: none; padding: 0; counter-reset: step; }
.steps li { counter-increment: step; display: grid; grid-template-
columns: 3rem 1fr; gap: 0 1rem; padding: 1rem 0; border-bottom: 1px
solid var(--line); }
.steps li::before { content: counter(step); grid-row: 1 / 3; width:
3rem; height: 3rem; border-radius: 50%; background: var(--brand);
color: #fff; display: grid; place-items: center; font-weight: 800;
font-size: 1.2rem; }
.steps h3 { margin: 0; grid-column: 2; }
.steps p { margin: .2rem 0 0; grid-column: 2; color: var(--muted); }
```

Project 1083 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>How we make Mount Sinai sunrise - Sinai Trekking Club</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="howto">	A self-contained piece: card, post, product.
How we make Mount Sinai sunrise	The main heading; only one per page.
<p class="lead">Night climb, 7 km. Here is the process, step by ste…	A paragraph of text.
<section class="need">	A thematic group of content, normally with its own heading.
You will need	Second-level heading for a section.
	Unordered (bulleted) list.
Time: about 2 hours	One list item.

Line	What it does
<ol class="steps">	Ordered (numbered) list; the order matters.
<h3>Prepare</h3><p>Gather everything and read the whole process...	Third-level heading, inside an h2 section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.2rem;	Size of the text.
background: var(--accent);	Background colour or image.

Declaration	What it does
border-radius: 12px;	Rounds the corners.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
counter-reset: step;	Starts a CSS counter.
counter-increment: step;	Adds one to the counter for each matching element.
display: grid;	Turns the element into a grid container.
grid-template-columns: 3rem 1fr;	Defines the columns of the grid.
gap: 0 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
content: counter(step);	The text or empty string for a pseudo-element.
border-radius: 50%;	Turns a square into a circle.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 800;	Thickness of the text.

Check your work

- Numbers generated, list still an ol
- Headings inside li are h3
- Circle stays aligned with the heading
- Readable width

Exercises

1. Add images to steps.
2. Add a 'mark as done' checkbox per step with :has() styling.
3. Add schema.org HowTo microdata.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 1084: Step-by-step how-to page for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 2 | Files: index.html, styles.css

Brief

Write a tutorial page with a 'you will need' box and numbered steps where each number is a large circle generated by CSS counters inside a grid row.

Learning goals

- Use headings inside list items
- Generate step numbers with counters
- Use a two-column grid per list item with the ::before in the first column

Elements and CSS used

HTML elements	CSS features
article, h1, p, section, h2, ul, ol, li, h3	counter-reset/increment, grid-template-columns: 3rem 1fr, grid-row: 1 / 3, grid-column: 2, border-radius: 50%

Build guide

1. Write the article with lead and 'You will need' section.
2. Write the ol; each li has an h3 and a p.
3. Remove list numbers and reset a counter.
4. Make each li a grid of two columns.
5. Put the counter in ::before spanning two rows.

6. Place h3 and p in column two.

Project 1084: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>How we make Portrait session - Horizon Photography</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="howto">
      <h1>How we make Portrait session</h1>
      <p class="lead">One hour, 20 edited photos. Here is the process,
 step by step, from Adham Nabil.</p>
      <section class="need">
        <h2>You will need</h2>
        <ul>
          <li>Time: about 2 hours</li>
          <li>Skill level: beginner</li>
          <li>Cost: around 1200 EGP</li>
        </ul>
      </section>
      <h2>Steps</h2>
      <ol class="steps">
        <li><h3>Prepare</h3><p>Gather everything and read the whole
process once.</p></li>
        <li><h3>Start</h3><p>Begin slowly; the first step sets the
quality of the rest.</p></li>
        <li><h3>Check</h3><p>Compare against our standard. Adjust if
needed.</p></li>
        <li><h3>Finish</h3><p>Rest, present and enjoy your session.</
p></li>
      </ol>
    </article>
  </main>
</body>
</html>
```

Project 1084: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.lead { font-size: 1.2rem; color: var(--muted); }
```

```
.need { background: var(--accent); padding: 1rem 1.5rem; border-
radius: 12px; }
.need h2 { margin-top: 0; font-size: 1rem; text-transform: uppercase;
letter-spacing: .05em; }
.steps { list-style: none; padding: 0; counter-reset: step; }
.steps li { counter-increment: step; display: grid; grid-template-
columns: 3rem 1fr; gap: 0 1rem; padding: 1rem 0; border-bottom: 1px
solid var(--line); }
.steps li::before { content: counter(step); grid-row: 1 / 3; width:
3rem; height: 3rem; border-radius: 50%; background: var(--brand);
color: #fff; display: grid; place-items: center; font-weight: 800;
font-size: 1.2rem; }
.steps h3 { margin: 0; grid-column: 2; }
.steps p { margin: .2rem 0 0; grid-column: 2; color: var(--muted); }
```

Project 1084 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>How we make Portrait session - Horizon Photography</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="howto">	A self-contained piece: card, post, product.
How we make Portrait session	The main heading; only one per page.
<p class="lead">One hour, 20 edited photos. Here is the process, st...	A paragraph of text.
<section class="need">	A thematic group of content, normally with its own heading.
You will need	Second-level heading for a section.
	Unordered (bulleted) list.
Time: about 2 hours	One list item.

Line	What it does
<ol class="steps">	Ordered (numbered) list; the order matters.
<h3>Prepare</h3><p>Gather everything and read the whole process...	Third-level heading, inside an h2 section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.2rem;	Size of the text.
background: var(--accent);	Background colour or image.

Declaration	What it does
border-radius: 12px;	Rounds the corners.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
counter-reset: step;	Starts a CSS counter.
counter-increment: step;	Adds one to the counter for each matching element.
display: grid;	Turns the element into a grid container.
grid-template-columns: 3rem 1fr;	Defines the columns of the grid.
gap: 0 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
content: counter(step);	The text or empty string for a pseudo-element.
border-radius: 50%;	Turns a square into a circle.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 800;	Thickness of the text.

Check your work

- Numbers generated, list still an ol
- Headings inside li are h3
- Circle stays aligned with the heading
- Readable width

Exercises

1. Add images to steps.
2. Add a 'mark as done' checkbox per step with :has() styling.
3. Add schema.org HowTo microdata.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 1085: Step-by-step how-to page for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 2 | Files: index.html, styles.css

Brief

Write a tutorial page with a 'you will need' box and numbered steps where each number is a large circle generated by CSS counters inside a grid row.

Learning goals

- Use headings inside list items
- Generate step numbers with counters
- Use a two-column grid per list item with the ::before in the first column

Elements and CSS used

HTML elements	CSS features
article, h1, p, section, h2, ul, ol, li, h3	counter-reset/increment, grid-template-columns: 3rem 1fr, grid-row: 1 / 3, grid-column: 2, border-radius: 50%

Build guide

1. Write the article with lead and 'You will need' section.
2. Write the ol; each li has an h3 and a p.
3. Remove list numbers and reset a counter.
4. Make each li a grid of two columns.
5. Put the counter in ::before spanning two rows.

6. Place h3 and p in column two.

Project 1085: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>How we make Dotted notebook - Papyrus Stationery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="howto">
      <h1>How we make Dotted notebook</h1>
      <p class="lead">A5, 160 pages. Here is the process, step by
step, from Dina Fathy.</p>
      <section class="need">
        <h2>You will need</h2>
        <ul>
          <li>Time: about 2 hours</li>
          <li>Skill level: beginner</li>
          <li>Cost: around 140 EGP</li>
        </ul>
      </section>
      <h2>Steps</h2>
      <ol class="steps">
        <li><h3>Prepare</h3><p>Gather everything and read the whole
process once.</p></li>
        <li><h3>Start</h3><p>Begin slowly; the first step sets the
quality of the rest.</p></li>
        <li><h3>Check</h3><p>Compare against our standard. Adjust if
needed.</p></li>
        <li><h3>Finish</h3><p>Rest, present and enjoy your product.</
p></li>
      </ol>
    </article>
  </main>
</body>
</html>
```

Project 1085: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.lead { font-size: 1.2rem; color: var(--muted); }
```

```
.need { background: var(--accent); padding: 1rem 1.5rem; border-
radius: 12px; }
.need h2 { margin-top: 0; font-size: 1rem; text-transform: uppercase;
letter-spacing: .05em; }
.steps { list-style: none; padding: 0; counter-reset: step; }
.steps li { counter-increment: step; display: grid; grid-template-
columns: 3rem 1fr; gap: 0 1rem; padding: 1rem 0; border-bottom: 1px
solid var(--line); }
.steps li::before { content: counter(step); grid-row: 1 / 3; width:
3rem; height: 3rem; border-radius: 50%; background: var(--brand);
color: #fff; display: grid; place-items: center; font-weight: 800;
font-size: 1.2rem; }
.steps h3 { margin: 0; grid-column: 2; }
.steps p { margin: .2rem 0 0; grid-column: 2; color: var(--muted); }
```

Project 1085 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>How we make Dotted notebook - Papyrus Stationery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="howto">	A self-contained piece: card, post, product.
How we make Dotted notebook	The main heading; only one per page.
<p class="lead">A5, 160 pages. Here is the process, step by step, f...	A paragraph of text.
<section class="need">	A thematic group of content, normally with its own heading.
You will need	Second-level heading for a section.
	Unordered (bulleted) list.
Time: about 2 hours	One list item.

Line	What it does
<ol class="steps">	Ordered (numbered) list; the order matters.
<h3>Prepare</h3><p>Gather everything and read the whole process...	Third-level heading, inside an h2 section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.2rem;	Size of the text.
background: var(--accent);	Background colour or image.

Declaration	What it does
border-radius: 12px;	Rounds the corners.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
counter-reset: step;	Starts a CSS counter.
counter-increment: step;	Adds one to the counter for each matching element.
display: grid;	Turns the element into a grid container.
grid-template-columns: 3rem 1fr;	Defines the columns of the grid.
gap: 0 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
content: counter(step);	The text or empty string for a pseudo-element.
border-radius: 50%;	Turns a square into a circle.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 800;	Thickness of the text.

Check your work

- Numbers generated, list still an ol
- Headings inside li are h3
- Circle stays aligned with the heading
- Readable width

Exercises

1. Add images to steps.
2. Add a 'mark as done' checkbox per step with :has() styling.
3. Add schema.org HowTo microdata.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 1086: Step-by-step how-to page for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 2 | Files: index.html, styles.css

Brief

Write a tutorial page with a 'you will need' box and numbered steps where each number is a large circle generated by CSS counters inside a grid row.

Learning goals

- Use headings inside list items
- Generate step numbers with counters
- Use a two-column grid per list item with the ::before in the first column

Elements and CSS used

HTML elements	CSS features
article, h1, p, section, h2, ul, ol, li, h3	counter-reset/increment, grid-template-columns: 3rem 1fr, grid-row: 1 / 3, grid-column: 2, border-radius: 50%

Build guide

1. Write the article with lead and 'You will need' section.
2. Write the ol; each li has an h3 and a p.
3. Remove list numbers and reset a counter.
4. Make each li a grid of two columns.
5. Put the counter in ::before spanning two rows.

6. Place h3 and p in column two.

Project 1086: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>How we make Monstera - Oasis Plant Nursery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="howto">
      <h1>How we make Monstera</h1>
      <p class="lead">Large leaves, easy care. Here is the process,
step by step, from Hossam Ali.</p>
      <section class="need">
        <h2>You will need</h2>
        <ul>
          <li>Time: about 2 hours</li>
          <li>Skill level: beginner</li>
          <li>Cost: around 250 EGP</li>
        </ul>
      </section>
      <h2>Steps</h2>
      <ol class="steps">
        <li><h3>Prepare</h3><p>Gather everything and read the whole
process once.</p></li>
        <li><h3>Start</h3><p>Begin slowly; the first step sets the
quality of the rest.</p></li>
        <li><h3>Check</h3><p>Compare against our standard. Adjust if
needed.</p></li>
        <li><h3>Finish</h3><p>Rest, present and enjoy your plant.</
p></li>
      </ol>
    </article>
  </main>
</body>
</html>
```

Project 1086: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.lead { font-size: 1.2rem; color: var(--muted); }
```

```
.need { background: var(--accent); padding: 1rem 1.5rem; border-
radius: 12px; }
.need h2 { margin-top: 0; font-size: 1rem; text-transform: uppercase;
letter-spacing: .05em; }
.steps { list-style: none; padding: 0; counter-reset: step; }
.steps li { counter-increment: step; display: grid; grid-template-
columns: 3rem 1fr; gap: 0 1rem; padding: 1rem 0; border-bottom: 1px
solid var(--line); }
.steps li::before { content: counter(step); grid-row: 1 / 3; width:
3rem; height: 3rem; border-radius: 50%; background: var(--brand);
color: #fff; display: grid; place-items: center; font-weight: 800;
font-size: 1.2rem; }
.steps h3 { margin: 0; grid-column: 2; }
.steps p { margin: .2rem 0 0; grid-column: 2; color: var(--muted); }
```

Project 1086 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>How we make Monstera - Oasis Plant Nursery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="howto">	A self-contained piece: card, post, product.
How we make Monstera	The main heading; only one per page.
<p class="lead">Large leaves, easy care. Here is the process, step ...	A paragraph of text.
<section class="need">	A thematic group of content, normally with its own heading.
You will need	Second-level heading for a section.
	Unordered (bulleted) list.
Time: about 2 hours	One list item.

Line	What it does
<ol class="steps">	Ordered (numbered) list; the order matters.
<h3>Prepare</h3><p>Gather everything and read the whole process...	Third-level heading, inside an h2 section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.2rem;	Size of the text.
background: var(--accent);	Background colour or image.

Declaration	What it does
border-radius: 12px;	Rounds the corners.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
counter-reset: step;	Starts a CSS counter.
counter-increment: step;	Adds one to the counter for each matching element.
display: grid;	Turns the element into a grid container.
grid-template-columns: 3rem 1fr;	Defines the columns of the grid.
gap: 0 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
content: counter(step);	The text or empty string for a pseudo-element.
border-radius: 50%;	Turns a square into a circle.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 800;	Thickness of the text.

Check your work

- Numbers generated, list still an ol
- Headings inside li are h3
- Circle stays aligned with the heading
- Readable width

Exercises

1. Add images to steps.
2. Add a 'mark as done' checkbox per step with :has() styling.
3. Add schema.org HowTo microdata.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 1087: Step-by-step how-to page for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 2 | Files: index.html, styles.css

Brief

Write a tutorial page with a 'you will need' box and numbered steps where each number is a large circle generated by CSS counters inside a grid row.

Learning goals

- Use headings inside list items
- Generate step numbers with counters
- Use a two-column grid per list item with the ::before in the first column

Elements and CSS used

HTML elements	CSS features
article, h1, p, section, h2, ul, ol, li, h3	counter-reset/increment, grid-template-columns: 3rem 1fr, grid-row: 1 / 3, grid-column: 2, border-radius: 50%

Build guide

1. Write the article with lead and 'You will need' section.
2. Write the ol; each li has an h3 and a p.
3. Remove list numbers and reset a counter.
4. Make each li a grid of two columns.
5. Put the counter in ::before spanning two rows.

6. Place h3 and p in column two.

Project 1087: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>How we make Oak dining table - Cedar Furniture</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="howto">
      <h1>How we make Oak dining table</h1>
      <p class="lead">Seats six. Here is the process, step by step,
from Tarek Lotfy.</p>
      <section class="need">
        <h2>You will need</h2>
        <ul>
          <li>Time: about 2 hours</li>
          <li>Skill level: beginner</li>
          <li>Cost: around 9500 EGP</li>
        </ul>
      </section>
      <h2>Steps</h2>
      <ol class="steps">
        <li><h3>Prepare</h3><p>Gather everything and read the whole
process once.</p></li>
        <li><h3>Start</h3><p>Begin slowly; the first step sets the
quality of the rest.</p></li>
        <li><h3>Check</h3><p>Compare against our standard. Adjust if
needed.</p></li>
        <li><h3>Finish</h3><p>Rest, present and enjoy your piece.</
p></li>
      </ol>
    </article>
  </main>
</body>
</html>
```

Project 1087: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.lead { font-size: 1.2rem; color: var(--muted); }
```

```
.need { background: var(--accent); padding: 1rem 1.5rem; border-
radius: 12px; }
.need h2 { margin-top: 0; font-size: 1rem; text-transform: uppercase;
letter-spacing: .05em; }
.steps { list-style: none; padding: 0; counter-reset: step; }
.steps li { counter-increment: step; display: grid; grid-template-
columns: 3rem 1fr; gap: 0 1rem; padding: 1rem 0; border-bottom: 1px
solid var(--line); }
.steps li::before { content: counter(step); grid-row: 1 / 3; width:
3rem; height: 3rem; border-radius: 50%; background: var(--brand);
color: #fff; display: grid; place-items: center; font-weight: 800;
font-size: 1.2rem; }
.steps h3 { margin: 0; grid-column: 2; }
.steps p { margin: .2rem 0 0; grid-column: 2; color: var(--muted); }
```

Project 1087 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>How we make Oak dining table - Cedar Furniture</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="howto">	A self-contained piece: card, post, product.
How we make Oak dining table	The main heading; only one per page.
<p class="lead">Seats six. Here is the process, step by step, from ...	A paragraph of text.
<section class="need">	A thematic group of content, normally with its own heading.
You will need	Second-level heading for a section.
	Unordered (bulleted) list.
Time: about 2 hours	One list item.

Line	What it does
<ol class="steps">	Ordered (numbered) list; the order matters.
<h3>Prepare</h3><p>Gather everything and read the whole process...	Third-level heading, inside an h2 section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.2rem;	Size of the text.
background: var(--accent);	Background colour or image.

Declaration	What it does
border-radius: 12px;	Rounds the corners.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
counter-reset: step;	Starts a CSS counter.
counter-increment: step;	Adds one to the counter for each matching element.
display: grid;	Turns the element into a grid container.
grid-template-columns: 3rem 1fr;	Defines the columns of the grid.
gap: 0 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
content: counter(step);	The text or empty string for a pseudo-element.
border-radius: 50%;	Turns a square into a circle.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 800;	Thickness of the text.

Check your work

- Numbers generated, list still an ol
- Headings inside li are h3
- Circle stays aligned with the heading
- Readable width

Exercises

1. Add images to steps.
2. Add a 'mark as done' checkbox per step with :has() styling.
3. Add schema.org HowTo microdata.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 1088: Step-by-step how-to page for Byte Repair

Theme: Byte Repair (Nasr City) | Level 2 | Files: index.html, styles.css

Brief

Write a tutorial page with a 'you will need' box and numbered steps where each number is a large circle generated by CSS counters inside a grid row.

Learning goals

- Use headings inside list items
- Generate step numbers with counters
- Use a two-column grid per list item with the ::before in the first column

Elements and CSS used

HTML elements	CSS features
article, h1, p, section, h2, ul, ol, li, h3	counter-reset/increment, grid-template-columns: 3rem 1fr, grid-row: 1 / 3, grid-column: 2, border-radius: 50%

Build guide

1. Write the article with lead and 'You will need' section.
2. Write the ol; each li has an h3 and a p.
3. Remove list numbers and reset a counter.
4. Make each li a grid of two columns.
5. Put the counter in ::before spanning two rows.
6. Place h3 and p in column two.

Project 1088: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>How we make Screen replacement - Byte Repair</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="howto">
      <h1>How we make Screen replacement</h1>
      <p class="lead">Most phones, 1 hour. Here is the process, step
by step, from Mostafa Gamal.</p>
      <section class="need">
        <h2>You will need</h2>
        <ul>
          <li>Time: about 2 hours</li>
          <li>Skill level: beginner</li>
          <li>Cost: around From 800 EGP</li>
        </ul>
      </section>
      <h2>Steps</h2>
      <ol class="steps">
        <li><h3>Prepare</h3><p>Gather everything and read the whole
process once.</p></li>
        <li><h3>Start</h3><p>Begin slowly; the first step sets the
quality of the rest.</p></li>
        <li><h3>Check</h3><p>Compare against our standard. Adjust if
needed.</p></li>
        <li><h3>Finish</h3><p>Rest, present and enjoy your repair.</
p></li>
      </ol>
    </article>
  </main>
</body>
</html>
```

Project 1088: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.lead { font-size: 1.2rem; color: var(--muted); }
```

```
.need { background: var(--accent); padding: 1rem 1.5rem; border-
radius: 12px; }
.need h2 { margin-top: 0; font-size: 1rem; text-transform: uppercase;
letter-spacing: .05em; }
.steps { list-style: none; padding: 0; counter-reset: step; }
.steps li { counter-increment: step; display: grid; grid-template-
columns: 3rem 1fr; gap: 0 1rem; padding: 1rem 0; border-bottom: 1px
solid var(--line); }
.steps li::before { content: counter(step); grid-row: 1 / 3; width:
3rem; height: 3rem; border-radius: 50%; background: var(--brand);
color: #fff; display: grid; place-items: center; font-weight: 800;
font-size: 1.2rem; }
.steps h3 { margin: 0; grid-column: 2; }
.steps p { margin: .2rem 0 0; grid-column: 2; color: var(--muted); }
```

Project 1088 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>How we make Screen replacement - Byte Repair</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="howto">	A self-contained piece: card, post, product.
How we make Screen replacement	The main heading; only one per page.
<p class="lead">Most phones, 1 hour. Here is the process, step by s...	A paragraph of text.
<section class="need">	A thematic group of content, normally with its own heading.
You will need	Second-level heading for a section.
	Unordered (bulleted) list.
Time: about 2 hours	One list item.

Line	What it does
<ol class="steps">	Ordered (numbered) list; the order matters.
<h3>Prepare</h3><p>Gather everything and read the whole process...	Third-level heading, inside an h2 section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.2rem;	Size of the text.
background: var(--accent);	Background colour or image.

Declaration	What it does
border-radius: 12px;	Rounds the corners.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
counter-reset: step;	Starts a CSS counter.
counter-increment: step;	Adds one to the counter for each matching element.
display: grid;	Turns the element into a grid container.
grid-template-columns: 3rem 1fr;	Defines the columns of the grid.
gap: 0 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
content: counter(step);	The text or empty string for a pseudo-element.
border-radius: 50%;	Turns a square into a circle.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 800;	Thickness of the text.

Check your work

- Numbers generated, list still an ol
- Headings inside li are h3
- Circle stays aligned with the heading
- Readable width

Exercises

1. Add images to steps.
2. Add a 'mark as done' checkbox per step with :has() styling.
3. Add schema.org HowTo microdata.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 1089: Step-by-step how-to page for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 2 | Files: index.html, styles.css

Brief

Write a tutorial page with a 'you will need' box and numbered steps where each number is a large circle generated by CSS counters inside a grid row.

Learning goals

- Use headings inside list items
- Generate step numbers with counters
- Use a two-column grid per list item with the ::before in the first column

Elements and CSS used

HTML elements	CSS features
article, h1, p, section, h2, ul, ol, li, h3	counter-reset/increment, grid-template-columns: 3rem 1fr, grid-row: 1 / 3, grid-column: 2, border-radius: 50%

Build guide

1. Write the article with lead and 'You will need' section.
2. Write the ol; each li has an h3 and a p.
3. Remove list numbers and reset a counter.
4. Make each li a grid of two columns.
5. Put the counter in ::before spanning two rows.

6. Place h3 and p in column two.

Project 1089: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>How we make Full grooming - Sahara Pet Care</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="howto">
      <h1>How we make Full grooming</h1>
      <p class="lead">Bath, cut and nails. Here is the process, step
by step, from Rana Ibrahim.</p>
      <section class="need">
        <h2>You will need</h2>
        <ul>
          <li>Time: about 2 hours</li>
          <li>Skill level: beginner</li>
          <li>Cost: around 400 EGP</li>
        </ul>
      </section>
      <h2>Steps</h2>
      <ol class="steps">
        <li><h3>Prepare</h3><p>Gather everything and read the whole
process once.</p></li>
        <li><h3>Start</h3><p>Begin slowly; the first step sets the
quality of the rest.</p></li>
        <li><h3>Check</h3><p>Compare against our standard. Adjust if
needed.</p></li>
        <li><h3>Finish</h3><p>Rest, present and enjoy your service.</
p></li>
      </ol>
    </article>
  </main>
</body>
</html>
```

Project 1089: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.lead { font-size: 1.2rem; color: var(--muted); }
```

```
.need { background: var(--accent); padding: 1rem 1.5rem; border-
radius: 12px; }
.need h2 { margin-top: 0; font-size: 1rem; text-transform: uppercase;
letter-spacing: .05em; }
.steps { list-style: none; padding: 0; counter-reset: step; }
.steps li { counter-increment: step; display: grid; grid-template-
columns: 3rem 1fr; gap: 0 1rem; padding: 1rem 0; border-bottom: 1px
solid var(--line); }
.steps li::before { content: counter(step); grid-row: 1 / 3; width:
3rem; height: 3rem; border-radius: 50%; background: var(--brand);
color: #fff; display: grid; place-items: center; font-weight: 800;
font-size: 1.2rem; }
.steps h3 { margin: 0; grid-column: 2; }
.steps p { margin: .2rem 0 0; grid-column: 2; color: var(--muted); }
```

Project 1089 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>How we make Full grooming - Sahara Pet Care</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="howto">	A self-contained piece: card, post, product.
How we make Full grooming	The main heading; only one per page.
<p class="lead">Bath, cut and nails. Here is the process, step by s...	A paragraph of text.
<section class="need">	A thematic group of content, normally with its own heading.
You will need	Second-level heading for a section.
	Unordered (bulleted) list.
Time: about 2 hours	One list item.

Line	What it does
<ol class="steps">	Ordered (numbered) list; the order matters.
<h3>Prepare</h3><p>Gather everything and read the whole process...	Third-level heading, inside an h2 section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.2rem;	Size of the text.
background: var(--accent);	Background colour or image.

Declaration	What it does
border-radius: 12px;	Rounds the corners.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
counter-reset: step;	Starts a CSS counter.
counter-increment: step;	Adds one to the counter for each matching element.
display: grid;	Turns the element into a grid container.
grid-template-columns: 3rem 1fr;	Defines the columns of the grid.
gap: 0 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
content: counter(step);	The text or empty string for a pseudo-element.
border-radius: 50%;	Turns a square into a circle.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 800;	Thickness of the text.

Check your work

- Numbers generated, list still an ol
- Headings inside li are h3
- Circle stays aligned with the heading
- Readable width

Exercises

1. Add images to steps.
2. Add a 'mark as done' checkbox per step with :has() styling.
3. Add schema.org HowTo microdata.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 1090: Step-by-step how-to page for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 2 | Files: index.html, styles.css

Brief

Write a tutorial page with a 'you will need' box and numbered steps where each number is a large circle generated by CSS counters inside a grid row.

Learning goals

- Use headings inside list items
- Generate step numbers with counters
- Use a two-column grid per list item with the ::before in the first column

Elements and CSS used

HTML elements	CSS features
article, h1, p, section, h2, ul, ol, li, h3	counter-reset/increment, grid-template-columns: 3rem 1fr, grid-row: 1 / 3, grid-column: 2, border-radius: 50%

Build guide

1. Write the article with lead and 'You will need' section.
2. Write the ol; each li has an h3 and a p.
3. Remove list numbers and reset a counter.
4. Make each li a grid of two columns.
5. Put the counter in ::before spanning two rows.

6. Place h3 and p in column two.

Project 1090: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>How we make Taster session - Alexandria Sailing School</
title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="howto">
      <h1>How we make Taster session</h1>
      <p class="lead">Two hours on the water. Here is the process,
step by step, from Amr Selim.</p>
      <section class="need">
        <h2>You will need</h2>
        <ul>
          <li>Time: about 2 hours</li>
          <li>Skill level: beginner</li>
          <li>Cost: around 500 EGP</li>
        </ul>
      </section>
      <h2>Steps</h2>
      <ol class="steps">
        <li><h3>Prepare</h3><p>Gather everything and read the whole
process once.</p></li>
        <li><h3>Start</h3><p>Begin slowly; the first step sets the
quality of the rest.</p></li>
        <li><h3>Check</h3><p>Compare against our standard. Adjust if
needed.</p></li>
        <li><h3>Finish</h3><p>Rest, present and enjoy your lesson.</
p></li>
      </ol>
    </article>
  </main>
</body>
</html>
```

Project 1090: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
```

```
.lead { font-size: 1.2rem; color: var(--muted); }
.need { background: var(--accent); padding: 1rem 1.5rem; border-
radius: 12px; }
.need h2 { margin-top: 0; font-size: 1rem; text-transform: uppercase;
letter-spacing: .05em; }
.steps { list-style: none; padding: 0; counter-reset: step; }
.steps li { counter-increment: step; display: grid; grid-template-
columns: 3rem 1fr; gap: 0 1rem; padding: 1rem 0; border-bottom: 1px
solid var(--line); }
.steps li::before { content: counter(step); grid-row: 1 / 3; width:
3rem; height: 3rem; border-radius: 50%; background: var(--brand);
color: #fff; display: grid; place-items: center; font-weight: 800;
font-size: 1.2rem; }
.steps h3 { margin: 0; grid-column: 2; }
.steps p { margin: .2rem 0 0; grid-column: 2; color: var(--muted); }
```

Project 1090 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>How we make Taster session - Alexandria Sailing School</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="howto">	A self-contained piece: card, post, product.
How we make Taster session	The main heading; only one per page.
<p class="lead">Two hours on the water. Here is the process, step b...	A paragraph of text.
<section class="need">	A thematic group of content, normally with its own heading.
You will need	Second-level heading for a section.
	Unordered (bulleted) list.
Time: about 2 hours	One list item.

Line	What it does
<ol class="steps">	Ordered (numbered) list; the order matters.
<h3>Prepare</h3><p>Gather everything and read the whole process...	Third-level heading, inside an h2 section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.2rem;	Size of the text.
background: var(--accent);	Background colour or image.

Declaration	What it does
border-radius: 12px;	Rounds the corners.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
counter-reset: step;	Starts a CSS counter.
counter-increment: step;	Adds one to the counter for each matching element.
display: grid;	Turns the element into a grid container.
grid-template-columns: 3rem 1fr;	Defines the columns of the grid.
gap: 0 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
content: counter(step);	The text or empty string for a pseudo-element.
border-radius: 50%;	Turns a square into a circle.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 800;	Thickness of the text.

Check your work

- Numbers generated, list still an ol
- Headings inside li are h3
- Circle stays aligned with the heading
- Readable width

Exercises

1. Add images to steps.
2. Add a 'mark as done' checkbox per step with :has() styling.
3. Add schema.org HowTo microdata.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 1091: Step-by-step how-to page for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Write a tutorial page with a 'you will need' box and numbered steps where each number is a large circle generated by CSS counters inside a grid row.

Learning goals

- Use headings inside list items
- Generate step numbers with counters
- Use a two-column grid per list item with the ::before in the first column

Elements and CSS used

HTML elements	CSS features
article, h1, p, section, h2, ul, ol, li, h3	counter-reset/increment, grid-template-columns: 3rem 1fr, grid-row: 1 / 3, grid-column: 2, border-radius: 50%

Build guide

1. Write the article with lead and 'You will need' section.
2. Write the ol; each li has an h3 and a p.
3. Remove list numbers and reset a counter.
4. Make each li a grid of two columns.
5. Put the counter in ::before spanning two rows.

6. Place h3 and p in column two.

Project 1091: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>How we make Lotus pendant - Habiba Handmade Jewellery</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="howto">
      <h1>How we make Lotus pendant</h1>
      <p class="lead">Sterling silver. Here is the process, step by
step, from Habiba Saleh.</p>
      <section class="need">
        <h2>You will need</h2>
        <ul>
          <li>Time: about 2 hours</li>
          <li>Skill level: beginner</li>
          <li>Cost: around 650 EGP</li>
        </ul>
      </section>
      <h2>Steps</h2>
      <ol class="steps">
        <li><h3>Prepare</h3><p>Gather everything and read the whole
process once.</p></li>
        <li><h3>Start</h3><p>Begin slowly; the first step sets the
quality of the rest.</p></li>
        <li><h3>Check</h3><p>Compare against our standard. Adjust if
needed.</p></li>
        <li><h3>Finish</h3><p>Rest, present and enjoy your item.</p></
li>
      </ol>
    </article>
  </main>
</body>
</html>
```

Project 1091: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.lead { font-size: 1.2rem; color: var(--muted); }
```

```
.need { background: var(--accent); padding: 1rem 1.5rem; border-
radius: 12px; }
.need h2 { margin-top: 0; font-size: 1rem; text-transform: uppercase;
letter-spacing: .05em; }
.steps { list-style: none; padding: 0; counter-reset: step; }
.steps li { counter-increment: step; display: grid; grid-template-
columns: 3rem 1fr; gap: 0 1rem; padding: 1rem 0; border-bottom: 1px
solid var(--line); }
.steps li::before { content: counter(step); grid-row: 1 / 3; width:
3rem; height: 3rem; border-radius: 50%; background: var(--brand);
color: #fff; display: grid; place-items: center; font-weight: 800;
font-size: 1.2rem; }
.steps h3 { margin: 0; grid-column: 2; }
.steps p { margin: .2rem 0 0; grid-column: 2; color: var(--muted); }
```

Project 1091 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>How we make Lotus pendant - Habiba Handmade Jewellery</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="howto">	A self-contained piece: card, post, product.
How we make Lotus pendant	The main heading; only one per page.
<p class="lead">Sterling silver. Here is the process, step by step,...	A paragraph of text.
<section class="need">	A thematic group of content, normally with its own heading.
You will need	Second-level heading for a section.
	Unordered (bulleted) list.
Time: about 2 hours	One list item.

Line	What it does
<ol class="steps">	Ordered (numbered) list; the order matters.
<h3>Prepare</h3><p>Gather everything and read the whole process...	Third-level heading, inside an h2 section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.2rem;	Size of the text.
background: var(--accent);	Background colour or image.

Declaration	What it does
border-radius: 12px;	Rounds the corners.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
counter-reset: step;	Starts a CSS counter.
counter-increment: step;	Adds one to the counter for each matching element.
display: grid;	Turns the element into a grid container.
grid-template-columns: 3rem 1fr;	Defines the columns of the grid.
gap: 0 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
content: counter(step);	The text or empty string for a pseudo-element.
border-radius: 50%;	Turns a square into a circle.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 800;	Thickness of the text.

Check your work

- Numbers generated, list still an ol
- Headings inside li are h3
- Circle stays aligned with the heading
- Readable width

Exercises

1. Add images to steps.
2. Add a 'mark as done' checkbox per step with :has() styling.
3. Add schema.org HowTo microdata.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 1092: Step-by-step how-to page for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 2 | Files: index.html, styles.css

Brief

Write a tutorial page with a 'you will need' box and numbered steps where each number is a large circle generated by CSS counters inside a grid row.

Learning goals

- Use headings inside list items
- Generate step numbers with counters
- Use a two-column grid per list item with the ::before in the first column

Elements and CSS used

HTML elements	CSS features
article, h1, p, section, h2, ul, ol, li, h3	counter-reset/increment, grid-template-columns: 3rem 1fr, grid-row: 1 / 3, grid-column: 2, border-radius: 50%

Build guide

1. Write the article with lead and 'You will need' section.
2. Write the ol; each li has an h3 and a p.
3. Remove list numbers and reset a counter.
4. Make each li a grid of two columns.
5. Put the counter in ::before spanning two rows.

6. Place h3 and p in column two.

Project 1092: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>How we make Intro to the wheel - Fayoum Pottery Studio</
title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="howto">
      <h1>How we make Intro to the wheel</h1>
      <p class="lead">Three hours, take home a bowl. Here is the
process, step by step, from Ahmed Mahmoud.</p>
      <section class="need">
        <h2>You will need</h2>
        <ul>
          <li>Time: about 2 hours</li>
          <li>Skill level: beginner</li>
          <li>Cost: around 450 EGP</li>
        </ul>
      </section>
      <h2>Steps</h2>
      <ol class="steps">
        <li><h3>Prepare</h3><p>Gather everything and read the whole
process once.</p></li>
        <li><h3>Start</h3><p>Begin slowly; the first step sets the
quality of the rest.</p></li>
        <li><h3>Check</h3><p>Compare against our standard. Adjust if
needed.</p></li>
        <li><h3>Finish</h3><p>Rest, present and enjoy your workshop.</
p></li>
      </ol>
    </article>
  </main>
</body>
</html>
```

Project 1092: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
```

```
.lead { font-size: 1.2rem; color: var(--muted); }
.need { background: var(--accent); padding: 1rem 1.5rem; border-
radius: 12px; }
.need h2 { margin-top: 0; font-size: 1rem; text-transform: uppercase;
letter-spacing: .05em; }
.steps { list-style: none; padding: 0; counter-reset: step; }
.steps li { counter-increment: step; display: grid; grid-template-
columns: 3rem 1fr; gap: 0 1rem; padding: 1rem 0; border-bottom: 1px
solid var(--line); }
.steps li::before { content: counter(step); grid-row: 1 / 3; width:
3rem; height: 3rem; border-radius: 50%; background: var(--brand);
color: #fff; display: grid; place-items: center; font-weight: 800;
font-size: 1.2rem; }
.steps h3 { margin: 0; grid-column: 2; }
.steps p { margin: .2rem 0 0; grid-column: 2; color: var(--muted); }
```

Project 1092 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>How we make Intro to the wheel - Fayoum Pottery Studio</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="howto">	A self-contained piece: card, post, product.
How we make Intro to the wheel	The main heading; only one per page.
<p class="lead">Three hours, take home a bowl. Here is the process,...	A paragraph of text.
<section class="need">	A thematic group of content, normally with its own heading.
You will need	Second-level heading for a section.
	Unordered (bulleted) list.
Time: about 2 hours	One list item.

Line	What it does
<ol class="steps">	Ordered (numbered) list; the order matters.
<h3>Prepare</h3><p>Gather everything and read the whole process...	Third-level heading, inside an h2 section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.2rem;	Size of the text.
background: var(--accent);	Background colour or image.

Declaration	What it does
border-radius: 12px;	Rounds the corners.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
counter-reset: step;	Starts a CSS counter.
counter-increment: step;	Adds one to the counter for each matching element.
display: grid;	Turns the element into a grid container.
grid-template-columns: 3rem 1fr;	Defines the columns of the grid.
gap: 0 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
content: counter(step);	The text or empty string for a pseudo-element.
border-radius: 50%;	Turns a square into a circle.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 800;	Thickness of the text.

Check your work

- Numbers generated, list still an ol
- Headings inside li are h3
- Circle stays aligned with the heading
- Readable width

Exercises

1. Add images to steps.
2. Add a 'mark as done' checkbox per step with :has() styling.
3. Add schema.org HowTo microdata.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 1093: Step-by-step how-to page for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 2 | Files: index.html, styles.css

Brief

Write a tutorial page with a 'you will need' box and numbered steps where each number is a large circle generated by CSS counters inside a grid row.

Learning goals

- Use headings inside list items
- Generate step numbers with counters
- Use a two-column grid per list item with the ::before in the first column

Elements and CSS used

HTML elements	CSS features
article, h1, p, section, h2, ul, ol, li, h3	counter-reset/increment, grid-template-columns: 3rem 1fr, grid-row: 1 / 3, grid-column: 2, border-radius: 50%

Build guide

1. Write the article with lead and 'You will need' section.
2. Write the ol; each li has an h3 and a p.
3. Remove list numbers and reset a counter.
4. Make each li a grid of two columns.
5. Put the counter in ::before spanning two rows.

6. Place h3 and p in column two.

Project 1093: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>How we make Haircut and blow-dry - Cleopatra Beauty Salon</
title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="howto">
      <h1>How we make Haircut and blow-dry</h1>
      <p class="lead">Consultation included. Here is the process,
step by step, from Mariam Adel.</p>
      <section class="need">
        <h2>You will need</h2>
        <ul>
          <li>Time: about 2 hours</li>
          <li>Skill level: beginner</li>
          <li>Cost: around 350 EGP</li>
        </ul>
      </section>
      <h2>Steps</h2>
      <ol class="steps">
        <li><h3>Prepare</h3><p>Gather everything and read the whole
process once.</p></li>
        <li><h3>Start</h3><p>Begin slowly; the first step sets the
quality of the rest.</p></li>
        <li><h3>Check</h3><p>Compare against our standard. Adjust if
needed.</p></li>
        <li><h3>Finish</h3><p>Rest, present and enjoy your treatment.
</p></li>
      </ol>
    </article>
  </main>
</body>
</html>
```

Project 1093: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
```

```
.lead { font-size: 1.2rem; color: var(--muted); }
.need { background: var(--accent); padding: 1rem 1.5rem; border-
radius: 12px; }
.need h2 { margin-top: 0; font-size: 1rem; text-transform: uppercase;
letter-spacing: .05em; }
.steps { list-style: none; padding: 0; counter-reset: step; }
.steps li { counter-increment: step; display: grid; grid-template-
columns: 3rem 1fr; gap: 0 1rem; padding: 1rem 0; border-bottom: 1px
solid var(--line); }
.steps li::before { content: counter(step); grid-row: 1 / 3; width:
3rem; height: 3rem; border-radius: 50%; background: var(--brand);
color: #fff; display: grid; place-items: center; font-weight: 800;
font-size: 1.2rem; }
.steps h3 { margin: 0; grid-column: 2; }
.steps p { margin: .2rem 0 0; grid-column: 2; color: var(--muted); }
```

Project 1093 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>How we make Haircut and blow-dry - Cleopatra Beauty Salon</t...	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="howto">	A self-contained piece: card, post, product.
How we make Haircut and blow-dry	The main heading; only one per page.
<p class="lead">Consultation included. Here is the process, step by...	A paragraph of text.
<section class="need">	A thematic group of content, normally with its own heading.
You will need	Second-level heading for a section.
	Unordered (bulleted) list.
Time: about 2 hours	One list item.

Line	What it does
<ol class="steps">	Ordered (numbered) list; the order matters.
<h3>Prepare</h3><p>Gather everything and read the whole process...	Third-level heading, inside an h2 section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.2rem;	Size of the text.
background: var(--accent);	Background colour or image.

Declaration	What it does
border-radius: 12px;	Rounds the corners.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
counter-reset: step;	Starts a CSS counter.
counter-increment: step;	Adds one to the counter for each matching element.
display: grid;	Turns the element into a grid container.
grid-template-columns: 3rem 1fr;	Defines the columns of the grid.
gap: 0 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
content: counter(step);	The text or empty string for a pseudo-element.
border-radius: 50%;	Turns a square into a circle.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 800;	Thickness of the text.

Check your work

- Numbers generated, list still an ol
- Headings inside li are h3
- Circle stays aligned with the heading
- Readable width

Exercises

1. Add images to steps.
2. Add a 'mark as done' checkbox per step with :has() styling.
3. Add schema.org HowTo microdata.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 1094: Step-by-step how-to page for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 2 | Files: index.html, styles.css

Brief

Write a tutorial page with a 'you will need' box and numbered steps where each number is a large circle generated by CSS counters inside a grid row.

Learning goals

- Use headings inside list items
- Generate step numbers with counters
- Use a two-column grid per list item with the ::before in the first column

Elements and CSS used

HTML elements	CSS features
article, h1, p, section, h2, ul, ol, li, h3	counter-reset/increment, grid-template-columns: 3rem 1fr, grid-row: 1 / 3, grid-column: 2, border-radius: 50%

Build guide

1. Write the article with lead and 'You will need' section.
2. Write the ol; each li has an h3 and a p.
3. Remove list numbers and reset a counter.
4. Make each li a grid of two columns.
5. Put the counter in ::before spanning two rows.

6. Place h3 and p in column two.

Project 1094: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>How we make Oil change - Suez Auto Service</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="howto">
      <h1>How we make Oil change</h1>
      <p class="lead">Filter included. Here is the process, step by
step, from Khaled Nasser.</p>
      <section class="need">
        <h2>You will need</h2>
        <ul>
          <li>Time: about 2 hours</li>
          <li>Skill level: beginner</li>
          <li>Cost: around 600 EGP</li>
        </ul>
      </section>
      <h2>Steps</h2>
      <ol class="steps">
        <li><h3>Prepare</h3><p>Gather everything and read the whole
process once.</p></li>
        <li><h3>Start</h3><p>Begin slowly; the first step sets the
quality of the rest.</p></li>
        <li><h3>Check</h3><p>Compare against our standard. Adjust if
needed.</p></li>
        <li><h3>Finish</h3><p>Rest, present and enjoy your service.</
p></li>
      </ol>
    </article>
  </main>
</body>
</html>
```

Project 1094: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.lead { font-size: 1.2rem; color: var(--muted); }
```

```
.need { background: var(--accent); padding: 1rem 1.5rem; border-
radius: 12px; }
.need h2 { margin-top: 0; font-size: 1rem; text-transform: uppercase;
letter-spacing: .05em; }
.steps { list-style: none; padding: 0; counter-reset: step; }
.steps li { counter-increment: step; display: grid; grid-template-
columns: 3rem 1fr; gap: 0 1rem; padding: 1rem 0; border-bottom: 1px
solid var(--line); }
.steps li::before { content: counter(step); grid-row: 1 / 3; width:
3rem; height: 3rem; border-radius: 50%; background: var(--brand);
color: #fff; display: grid; place-items: center; font-weight: 800;
font-size: 1.2rem; }
.steps h3 { margin: 0; grid-column: 2; }
.steps p { margin: .2rem 0 0; grid-column: 2; color: var(--muted); }
```

Project 1094 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>How we make Oil change - Suez Auto Service</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="howto">	A self-contained piece: card, post, product.
How we make Oil change	The main heading; only one per page.
<p class="lead">Filter included. Here is the process, step by step,...	A paragraph of text.
<section class="need">	A thematic group of content, normally with its own heading.
You will need	Second-level heading for a section.
	Unordered (bulleted) list.
Time: about 2 hours	One list item.

Line	What it does
<ol class="steps">	Ordered (numbered) list; the order matters.
<h3>Prepare</h3><p>Gather everything and read the whole process...	Third-level heading, inside an h2 section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.2rem;	Size of the text.
background: var(--accent);	Background colour or image.

Declaration	What it does
border-radius: 12px;	Rounds the corners.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
counter-reset: step;	Starts a CSS counter.
counter-increment: step;	Adds one to the counter for each matching element.
display: grid;	Turns the element into a grid container.
grid-template-columns: 3rem 1fr;	Defines the columns of the grid.
gap: 0 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
content: counter(step);	The text or empty string for a pseudo-element.
border-radius: 50%;	Turns a square into a circle.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 800;	Thickness of the text.

Check your work

- Numbers generated, list still an ol
- Headings inside li are h3
- Circle stays aligned with the heading
- Readable width

Exercises

1. Add images to steps.
2. Add a 'mark as done' checkbox per step with :has() styling.
3. Add schema.org HowTo microdata.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 1095: Step-by-step how-to page for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 2 | Files: index.html, styles.css

Brief

Write a tutorial page with a 'you will need' box and numbered steps where each number is a large circle generated by CSS counters inside a grid row.

Learning goals

- Use headings inside list items
- Generate step numbers with counters
- Use a two-column grid per list item with the ::before in the first column

Elements and CSS used

HTML elements	CSS features
article, h1, p, section, h2, ul, ol, li, h3	counter-reset/increment, grid-template-columns: 3rem 1fr, grid-row: 1 / 3, grid-column: 2, border-radius: 50%

Build guide

1. Write the article with lead and 'You will need' section.
2. Write the ol; each li has an h3 and a p.
3. Remove list numbers and reset a counter.
4. Make each li a grid of two columns.
5. Put the counter in ::before spanning two rows.

6. Place h3 and p in column two.

Project 1095: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>How we make Oud for beginners - Luxor Music Academy</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="howto">
      <h1>How we make Oud for beginners</h1>
      <p class="lead">Eight weekly lessons. Here is the process, step
by step, from Salma Ragab.</p>
      <section class="need">
        <h2>You will need</h2>
        <ul>
          <li>Time: about 2 hours</li>
          <li>Skill level: beginner</li>
          <li>Cost: around 1600 EGP</li>
        </ul>
      </section>
      <h2>Steps</h2>
      <ol class="steps">
        <li><h3>Prepare</h3><p>Gather everything and read the whole
process once.</p></li>
        <li><h3>Start</h3><p>Begin slowly; the first step sets the
quality of the rest.</p></li>
        <li><h3>Check</h3><p>Compare against our standard. Adjust if
needed.</p></li>
        <li><h3>Finish</h3><p>Rest, present and enjoy your course.</
p></li>
      </ol>
    </article>
  </main>
</body>
</html>
```

Project 1095: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.lead { font-size: 1.2rem; color: var(--muted); }
```

```
.need { background: var(--accent); padding: 1rem 1.5rem; border-
radius: 12px; }
.need h2 { margin-top: 0; font-size: 1rem; text-transform: uppercase;
letter-spacing: .05em; }
.steps { list-style: none; padding: 0; counter-reset: step; }
.steps li { counter-increment: step; display: grid; grid-template-
columns: 3rem 1fr; gap: 0 1rem; padding: 1rem 0; border-bottom: 1px
solid var(--line); }
.steps li::before { content: counter(step); grid-row: 1 / 3; width:
3rem; height: 3rem; border-radius: 50%; background: var(--brand);
color: #fff; display: grid; place-items: center; font-weight: 800;
font-size: 1.2rem; }
.steps h3 { margin: 0; grid-column: 2; }
.steps p { margin: .2rem 0 0; grid-column: 2; color: var(--muted); }
```

Project 1095 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>How we make Oud for beginners - Luxor Music Academy</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="howto">	A self-contained piece: card, post, product.
How we make Oud for beginners	The main heading; only one per page.
<p class="lead">Eight weekly lessons. Here is the process, step by ...	A paragraph of text.
<section class="need">	A thematic group of content, normally with its own heading.
You will need	Second-level heading for a section.
	Unordered (bulleted) list.
Time: about 2 hours	One list item.

Line	What it does
<ol class="steps">	Ordered (numbered) list; the order matters.
<h3>Prepare</h3><p>Gather everything and read the whole process...	Third-level heading, inside an h2 section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.2rem;	Size of the text.
background: var(--accent);	Background colour or image.

Declaration	What it does
border-radius: 12px;	Rounds the corners.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
counter-reset: step;	Starts a CSS counter.
counter-increment: step;	Adds one to the counter for each matching element.
display: grid;	Turns the element into a grid container.
grid-template-columns: 3rem 1fr;	Defines the columns of the grid.
gap: 0 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
content: counter(step);	The text or empty string for a pseudo-element.
border-radius: 50%;	Turns a square into a circle.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 800;	Thickness of the text.

Check your work

- Numbers generated, list still an ol
- Headings inside li are h3
- Circle stays aligned with the heading
- Readable width

Exercises

1. Add images to steps.
2. Add a 'mark as done' checkbox per step with :has() styling.
3. Add schema.org HowTo microdata.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 1096: Step-by-step how-to page for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 2 | Files: index.html, styles.css

Brief

Write a tutorial page with a 'you will need' box and numbered steps where each number is a large circle generated by CSS counters inside a grid row.

Learning goals

- Use headings inside list items
- Generate step numbers with counters
- Use a two-column grid per list item with the ::before in the first column

Elements and CSS used

HTML elements	CSS features
article, h1, p, section, h2, ul, ol, li, h3	counter-reset/increment, grid-template-columns: 3rem 1fr, grid-row: 1 / 3, grid-column: 2, border-radius: 50%

Build guide

1. Write the article with lead and 'You will need' section.
2. Write the ol; each li has an h3 and a p.
3. Remove list numbers and reset a counter.
4. Make each li a grid of two columns.
5. Put the counter in ::before spanning two rows.

6. Place h3 and p in column two.

Project 1096: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>How we make Grilled sea bass - Port Said Seafood</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="howto">
      <h1>How we make Grilled sea bass</h1>
      <p class="lead">With rice and salad. Here is the process, step
by step, from Sherif Wahba.</p>
      <section class="need">
        <h2>You will need</h2>
        <ul>
          <li>Time: about 2 hours</li>
          <li>Skill level: beginner</li>
          <li>Cost: around 320 EGP</li>
        </ul>
      </section>
      <h2>Steps</h2>
      <ol class="steps">
        <li><h3>Prepare</h3><p>Gather everything and read the whole
process once.</p></li>
        <li><h3>Start</h3><p>Begin slowly; the first step sets the
quality of the rest.</p></li>
        <li><h3>Check</h3><p>Compare against our standard. Adjust if
needed.</p></li>
        <li><h3>Finish</h3><p>Rest, present and enjoy your dish.</p></
li>
      </ol>
    </article>
  </main>
</body>
</html>
```

Project 1096: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.lead { font-size: 1.2rem; color: var(--muted); }
```

```
.need { background: var(--accent); padding: 1rem 1.5rem; border-
radius: 12px; }
.need h2 { margin-top: 0; font-size: 1rem; text-transform: uppercase;
letter-spacing: .05em; }
.steps { list-style: none; padding: 0; counter-reset: step; }
.steps li { counter-increment: step; display: grid; grid-template-
columns: 3rem 1fr; gap: 0 1rem; padding: 1rem 0; border-bottom: 1px
solid var(--line); }
.steps li::before { content: counter(step); grid-row: 1 / 3; width:
3rem; height: 3rem; border-radius: 50%; background: var(--brand);
color: #fff; display: grid; place-items: center; font-weight: 800;
font-size: 1.2rem; }
.steps h3 { margin: 0; grid-column: 2; }
.steps p { margin: .2rem 0 0; grid-column: 2; color: var(--muted); }
```

Project 1096 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>How we make Grilled sea bass - Port Said Seafood</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="howto">	A self-contained piece: card, post, product.
How we make Grilled sea bass	The main heading; only one per page.
<p class="lead">With rice and salad. Here is the process, step by s…	A paragraph of text.
<section class="need">	A thematic group of content, normally with its own heading.
You will need	Second-level heading for a section.
	Unordered (bulleted) list.
Time: about 2 hours	One list item.

Line	What it does
<ol class="steps">	Ordered (numbered) list; the order matters.
<h3>Prepare</h3><p>Gather everything and read the whole process...	Third-level heading, inside an h2 section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.2rem;	Size of the text.
background: var(--accent);	Background colour or image.

Declaration	What it does
border-radius: 12px;	Rounds the corners.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
counter-reset: step;	Starts a CSS counter.
counter-increment: step;	Adds one to the counter for each matching element.
display: grid;	Turns the element into a grid container.
grid-template-columns: 3rem 1fr;	Defines the columns of the grid.
gap: 0 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
content: counter(step);	The text or empty string for a pseudo-element.
border-radius: 50%;	Turns a square into a circle.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 800;	Thickness of the text.

Check your work

- Numbers generated, list still an ol
- Headings inside li are h3
- Circle stays aligned with the heading
- Readable width

Exercises

1. Add images to steps.
2. Add a 'mark as done' checkbox per step with :has() styling.
3. Add schema.org HowTo microdata.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 1097: Step-by-step how-to page for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 2 | Files: index.html, styles.css

Brief

Write a tutorial page with a 'you will need' box and numbered steps where each number is a large circle generated by CSS counters inside a grid row.

Learning goals

- Use headings inside list items
- Generate step numbers with counters
- Use a two-column grid per list item with the ::before in the first column

Elements and CSS used

HTML elements	CSS features
article, h1, p, section, h2, ul, ol, li, h3	counter-reset/increment, grid-template-columns: 3rem 1fr, grid-row: 1 / 3, grid-column: 2, border-radius: 50%

Build guide

1. Write the article with lead and 'You will need' section.
2. Write the ol; each li has an h3 and a p.
3. Remove list numbers and reset a counter.
4. Make each li a grid of two columns.
5. Put the counter in ::before spanning two rows.

6. Place h3 and p in column two.

Project 1097: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>How we make Story hour - Delta Kids Library</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="howto">
      <h1>How we make Story hour</h1>
      <p class="lead">Ages 3 to 6, Saturdays. Here is the process,
step by step, from Ghada Kamel.</p>
      <section class="need">
        <h2>You will need</h2>
        <ul>
          <li>Time: about 2 hours</li>
          <li>Skill level: beginner</li>
          <li>Cost: around Free</li>
        </ul>
      </section>
      <h2>Steps</h2>
      <ol class="steps">
        <li><h3>Prepare</h3><p>Gather everything and read the whole
process once.</p></li>
        <li><h3>Start</h3><p>Begin slowly; the first step sets the
quality of the rest.</p></li>
        <li><h3>Check</h3><p>Compare against our standard. Adjust if
needed.</p></li>
        <li><h3>Finish</h3><p>Rest, present and enjoy your programme.
</p></li>
      </ol>
    </article>
  </main>
</body>
</html>
```

Project 1097: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.lead { font-size: 1.2rem; color: var(--muted); }
```

```
.need { background: var(--accent); padding: 1rem 1.5rem; border-
radius: 12px; }
.need h2 { margin-top: 0; font-size: 1rem; text-transform: uppercase;
letter-spacing: .05em; }
.steps { list-style: none; padding: 0; counter-reset: step; }
.steps li { counter-increment: step; display: grid; grid-template-
columns: 3rem 1fr; gap: 0 1rem; padding: 1rem 0; border-bottom: 1px
solid var(--line); }
.steps li::before { content: counter(step); grid-row: 1 / 3; width:
3rem; height: 3rem; border-radius: 50%; background: var(--brand);
color: #fff; display: grid; place-items: center; font-weight: 800;
font-size: 1.2rem; }
.steps h3 { margin: 0; grid-column: 2; }
.steps p { margin: .2rem 0 0; grid-column: 2; color: var(--muted); }
```

Project 1097 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>How we make Story hour - Delta Kids Library</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="howto">	A self-contained piece: card, post, product.
How we make Story hour	The main heading; only one per page.
<p class="lead">Ages 3 to 6, Saturdays. Here is the process, step b...	A paragraph of text.
<section class="need">	A thematic group of content, normally with its own heading.
You will need	Second-level heading for a section.
	Unordered (bulleted) list.
Time: about 2 hours	One list item.

Line	What it does
<ol class="steps">	Ordered (numbered) list; the order matters.
<h3>Prepare</h3><p>Gather everything and read the whole process...	Third-level heading, inside an h2 section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.2rem;	Size of the text.
background: var(--accent);	Background colour or image.

Declaration	What it does
border-radius: 12px;	Rounds the corners.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
counter-reset: step;	Starts a CSS counter.
counter-increment: step;	Adds one to the counter for each matching element.
display: grid;	Turns the element into a grid container.
grid-template-columns: 3rem 1fr;	Defines the columns of the grid.
gap: 0 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
content: counter(step);	The text or empty string for a pseudo-element.
border-radius: 50%;	Turns a square into a circle.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 800;	Thickness of the text.

Check your work

- Numbers generated, list still an ol
- Headings inside li are h3
- Circle stays aligned with the heading
- Readable width

Exercises

1. Add images to steps.
2. Add a 'mark as done' checkbox per step with :has() styling.
3. Add schema.org HowTo microdata.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 1098: Step-by-step how-to page for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 2 | Files: index.html, styles.css

Brief

Write a tutorial page with a 'you will need' box and numbered steps where each number is a large circle generated by CSS counters inside a grid row.

Learning goals

- Use headings inside list items
- Generate step numbers with counters
- Use a two-column grid per list item with the ::before in the first column

Elements and CSS used

HTML elements	CSS features
article, h1, p, section, h2, ul, ol, li, h3	counter-reset/increment, grid-template-columns: 3rem 1fr, grid-row: 1 / 3, grid-column: 2, border-radius: 50%

Build guide

1. Write the article with lead and 'You will need' section.
2. Write the ol; each li has an h3 and a p.
3. Remove list numbers and reset a counter.
4. Make each li a grid of two columns.
5. Put the counter in ::before spanning two rows.

6. Place h3 and p in column two.

Project 1098: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>How we make Garden room - Nubian Guest House</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="howto">
      <h1>How we make Garden room</h1>
      <p class="lead">Double bed, shared terrace. Here is the process,
 step by step, from Fatma Hassan.</p>
      <section class="need">
        <h2>You will need</h2>
        <ul>
          <li>Time: about 2 hours</li>
          <li>Skill level: beginner</li>
          <li>Cost: around 900 EGP</li>
        </ul>
      </section>
      <h2>Steps</h2>
      <ol class="steps">
        <li><h3>Prepare</h3><p>Gather everything and read the whole
process once.</p></li>
        <li><h3>Start</h3><p>Begin slowly; the first step sets the
quality of the rest.</p></li>
        <li><h3>Check</h3><p>Compare against our standard. Adjust if
needed.</p></li>
        <li><h3>Finish</h3><p>Rest, present and enjoy your room.</p></
li>
      </ol>
    </article>
  </main>
</body>
</html>
```

Project 1098: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.lead { font-size: 1.2rem; color: var(--muted); }
```

```
.need { background: var(--accent); padding: 1rem 1.5rem; border-
radius: 12px; }
.need h2 { margin-top: 0; font-size: 1rem; text-transform: uppercase;
letter-spacing: .05em; }
.steps { list-style: none; padding: 0; counter-reset: step; }
.steps li { counter-increment: step; display: grid; grid-template-
columns: 3rem 1fr; gap: 0 1rem; padding: 1rem 0; border-bottom: 1px
solid var(--line); }
.steps li::before { content: counter(step); grid-row: 1 / 3; width:
3rem; height: 3rem; border-radius: 50%; background: var(--brand);
color: #fff; display: grid; place-items: center; font-weight: 800;
font-size: 1.2rem; }
.steps h3 { margin: 0; grid-column: 2; }
.steps p { margin: .2rem 0 0; grid-column: 2; color: var(--muted); }
```

Project 1098 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>How we make Garden room - Nubian Guest House</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="howto">	A self-contained piece: card, post, product.
How we make Garden room	The main heading; only one per page.
<p class="lead">Double bed, shared terrace. Here is the process, st...	A paragraph of text.
<section class="need">	A thematic group of content, normally with its own heading.
You will need	Second-level heading for a section.
	Unordered (bulleted) list.
Time: about 2 hours	One list item.

Line	What it does
<ol class="steps">	Ordered (numbered) list; the order matters.
<h3>Prepare</h3><p>Gather everything and read the whole process...	Third-level heading, inside an h2 section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.2rem;	Size of the text.
background: var(--accent);	Background colour or image.

Declaration	What it does
border-radius: 12px;	Rounds the corners.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
counter-reset: step;	Starts a CSS counter.
counter-increment: step;	Adds one to the counter for each matching element.
display: grid;	Turns the element into a grid container.
grid-template-columns: 3rem 1fr;	Defines the columns of the grid.
gap: 0 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
content: counter(step);	The text or empty string for a pseudo-element.
border-radius: 50%;	Turns a square into a circle.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 800;	Thickness of the text.

Check your work

- Numbers generated, list still an ol
- Headings inside li are h3
- Circle stays aligned with the heading
- Readable width

Exercises

1. Add images to steps.
2. Add a 'mark as done' checkbox per step with :has() styling.
3. Add schema.org HowTo microdata.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 1099: Step-by-step how-to page for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 2 | Files: index.html, styles.css

Brief

Write a tutorial page with a 'you will need' box and numbered steps where each number is a large circle generated by CSS counters inside a grid row.

Learning goals

- Use headings inside list items
- Generate step numbers with counters
- Use a two-column grid per list item with the ::before in the first column

Elements and CSS used

HTML elements	CSS features
article, h1, p, section, h2, ul, ol, li, h3	counter-reset/increment, grid-template-columns: 3rem 1fr, grid-row: 1 / 3, grid-column: 2, border-radius: 50%

Build guide

1. Write the article with lead and 'You will need' section.
2. Write the ol; each li has an h3 and a p.
3. Remove list numbers and reset a counter.
4. Make each li a grid of two columns.
5. Put the counter in ::before spanning two rows.

6. Place h3 and p in column two.

Project 1099: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>How we make City bike - Ismailia Cycling Store</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="howto">
      <h1>How we make City bike</h1>
      <p class="lead">Seven gears, basket. Here is the process, step
by step, from Bassem Adly.</p>
      <section class="need">
        <h2>You will need</h2>
        <ul>
          <li>Time: about 2 hours</li>
          <li>Skill level: beginner</li>
          <li>Cost: around 6500 EGP</li>
        </ul>
      </section>
      <h2>Steps</h2>
      <ol class="steps">
        <li><h3>Prepare</h3><p>Gather everything and read the whole
process once.</p></li>
        <li><h3>Start</h3><p>Begin slowly; the first step sets the
quality of the rest.</p></li>
        <li><h3>Check</h3><p>Compare against our standard. Adjust if
needed.</p></li>
        <li><h3>Finish</h3><p>Rest, present and enjoy your bike.</p></
li>
      </ol>
    </article>
  </main>
</body>
</html>
```

Project 1099: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.lead { font-size: 1.2rem; color: var(--muted); }
```

```
.need { background: var(--accent); padding: 1rem 1.5rem; border-
radius: 12px; }
.need h2 { margin-top: 0; font-size: 1rem; text-transform: uppercase;
letter-spacing: .05em; }
.steps { list-style: none; padding: 0; counter-reset: step; }
.steps li { counter-increment: step; display: grid; grid-template-
columns: 3rem 1fr; gap: 0 1rem; padding: 1rem 0; border-bottom: 1px
solid var(--line); }
.steps li::before { content: counter(step); grid-row: 1 / 3; width:
3rem; height: 3rem; border-radius: 50%; background: var(--brand);
color: #fff; display: grid; place-items: center; font-weight: 800;
font-size: 1.2rem; }
.steps h3 { margin: 0; grid-column: 2; }
.steps p { margin: .2rem 0 0; grid-column: 2; color: var(--muted); }
```

Project 1099 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>How we make City bike - Ismailia Cycling Store</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="howto">	A self-contained piece: card, post, product.
How we make City bike	The main heading; only one per page.
<p class="lead">Seven gears, basket. Here is the process, step by s...	A paragraph of text.
<section class="need">	A thematic group of content, normally with its own heading.
You will need	Second-level heading for a section.
	Unordered (bulleted) list.
Time: about 2 hours	One list item.

Line	What it does
<ol class="steps">	Ordered (numbered) list; the order matters.
<h3>Prepare</h3><p>Gather everything and read the whole process...	Third-level heading, inside an h2 section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.2rem;	Size of the text.
background: var(--accent);	Background colour or image.

Declaration	What it does
border-radius: 12px;	Rounds the corners.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
counter-reset: step;	Starts a CSS counter.
counter-increment: step;	Adds one to the counter for each matching element.
display: grid;	Turns the element into a grid container.
grid-template-columns: 3rem 1fr;	Defines the columns of the grid.
gap: 0 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
content: counter(step);	The text or empty string for a pseudo-element.
border-radius: 50%;	Turns a square into a circle.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 800;	Thickness of the text.

Check your work

- Numbers generated, list still an ol
- Headings inside li are h3
- Circle stays aligned with the heading
- Readable width

Exercises

1. Add images to steps.
2. Add a 'mark as done' checkbox per step with :has() styling.
3. Add schema.org HowTo microdata.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 1100: Step-by-step how-to page for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 2 | Files: index.html, styles.css

Brief

Write a tutorial page with a 'you will need' box and numbered steps where each number is a large circle generated by CSS counters inside a grid row.

Learning goals

- Use headings inside list items
- Generate step numbers with counters
- Use a two-column grid per list item with the ::before in the first column

Elements and CSS used

HTML elements	CSS features
article, h1, p, section, h2, ul, ol, li, h3	counter-reset/increment, grid-template-columns: 3rem 1fr, grid-row: 1 / 3, grid-column: 2, border-radius: 50%

Build guide

1. Write the article with lead and 'You will need' section.
2. Write the ol; each li has an h3 and a p.
3. Remove list numbers and reset a counter.
4. Make each li a grid of two columns.
5. Put the counter in ::before spanning two rows.

6. Place h3 and p in column two.

Project 1100: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>How we make HTML weekend - Minya Coding Club</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <main>
    <article class="howto">
      <h1>How we make HTML weekend</h1>
      <p class="lead">Build your first page. Here is the process,
step by step, from Youssef Hany.</p>
      <section class="need">
        <h2>You will need</h2>
        <ul>
          <li>Time: about 2 hours</li>
          <li>Skill level: beginner</li>
          <li>Cost: around Free</li>
        </ul>
      </section>
      <h2>Steps</h2>
      <ol class="steps">
        <li><h3>Prepare</h3><p>Gather everything and read the whole
process once.</p></li>
        <li><h3>Start</h3><p>Begin slowly; the first step sets the
quality of the rest.</p></li>
        <li><h3>Check</h3><p>Compare against our standard. Adjust if
needed.</p></li>
        <li><h3>Finish</h3><p>Rest, present and enjoy your workshop.</
p></li>
      </ol>
    </article>
  </main>
</body>
</html>
```

Project 1100: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
main { max-width: 44rem; margin: 2rem auto; padding: 0 1rem; }
.lead { font-size: 1.2rem; color: var(--muted); }
```

```
.need { background: var(--accent); padding: 1rem 1.5rem; border-
radius: 12px; }
.need h2 { margin-top: 0; font-size: 1rem; text-transform: uppercase;
letter-spacing: .05em; }
.steps { list-style: none; padding: 0; counter-reset: step; }
.steps li { counter-increment: step; display: grid; grid-template-
columns: 3rem 1fr; gap: 0 1rem; padding: 1rem 0; border-bottom: 1px
solid var(--line); }
.steps li::before { content: counter(step); grid-row: 1 / 3; width:
3rem; height: 3rem; border-radius: 50%; background: var(--brand);
color: #fff; display: grid; place-items: center; font-weight: 800;
font-size: 1.2rem; }
.steps h3 { margin: 0; grid-column: 2; }
.steps p { margin: .2rem 0 0; grid-column: 2; color: var(--muted); }
```

Project 1100 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>How we make HTML weekend - Minya Coding Club</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<main>	The unique content of this page; exactly one per page.
<article class="howto">	A self-contained piece: card, post, product.
How we make HTML weekend	The main heading; only one per page.
<p class="lead">Build your first page. Here is the process, step by…	A paragraph of text.
<section class="need">	A thematic group of content, normally with its own heading.
You will need	Second-level heading for a section.
	Unordered (bulleted) list.
Time: about 2 hours	One list item.

Line	What it does
<ol class="steps">	Ordered (numbered) list; the order matters.
<h3>Prepare</h3><p>Gather everything and read the whole process...	Third-level heading, inside an h2 section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
max-width: 44rem;	Limits how wide the element can grow, keeping lines readable.
padding: 0 1rem;	Space inside the element between its border and content.
font-size: 1.2rem;	Size of the text.
background: var(--accent);	Background colour or image.

Declaration	What it does
border-radius: 12px;	Rounds the corners.
text-transform: uppercase;	Displays text in capitals without changing the HTML.
letter-spacing: .05em;	Adds space between letters; useful for small capitals.
list-style: none;	Removes bullets or numbers from a list.
counter-reset: step;	Starts a CSS counter.
counter-increment: step;	Adds one to the counter for each matching element.
display: grid;	Turns the element into a grid container.
grid-template-columns: 3rem 1fr;	Defines the columns of the grid.
gap: 0 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
content: counter(step);	The text or empty string for a pseudo-element.
border-radius: 50%;	Turns a square into a circle.
place-items: center;	Centres items horizontally and vertically in a grid.
font-weight: 800;	Thickness of the text.

Check your work

- Numbers generated, list still an ol
- Headings inside li are h3
- Circle stays aligned with the heading
- Readable width

Exercises

1. Add images to steps.
2. Add a 'mark as done' checkbox per step with :has() styling.
3. Add schema.org HowTo microdata.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)

Project type: Complete one-page website

Level 3 | 25 projects, one per theme

Combine everything into a single-page site: skip link, sticky header with anchor navigation, hero, offers grid, about with details, contact form and footer.

Project 1101: Complete one-page website for Cairo Book Shop

Theme: Cairo Book Shop (Giza) | Level 3 | Files: index.html, styles.css

Brief

Combine everything into a single-page site: skip link, sticky header with anchor navigation, hero, offers grid, about with details, contact form and footer.

Learning goals

- Assemble a full page from components
- Use in-page anchor navigation with scroll-margin-top
- Provide a skip link

Elements and CSS used

HTML elements	CSS features
a.skip, header, nav, main, section, h1-h3, article, details, summary, form, label, input, textarea, button, footer	position: sticky, z-index, scroll-margin-top, grid auto-fit, clamp(), focus styles for skip link

Build guide

1. Write the skeleton with four sections that have ids.
2. Add the sticky header with links to those ids.
3. Add a skip link as the first element in body.
4. Style the hero, grid, about and form.
5. Add scroll-margin-top to h2 so anchors are not hidden by the header.

6. Validate the whole page and test keyboard navigation.

Project 1101: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cairo Book Shop - Complete site</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <a class="skip" href="#main">Skip to content</a>
  <header class="site-header">
    <a class="logo" href="index.html">Cairo Book Shop</a>
    <nav aria-label="Main"><ul class="nav">
      <li><a href="#offers">Books</a></li><li><a href="#about">About</
a></li><li><a href="#contact">Contact</a></li>
    </ul></nav>
  </header>
  <main id="main">
    <section class="hero">
      <h1>PDF and printed books about web development</h1>
      <p>Welcome to Cairo Book Shop in Giza.</p>
      <a class="btn" href="#offers">Explore</a>
    </section>
    <section id="offers" class="wrap">
      <h2>Our books</h2>
      <div class="grid">
        <article class="card"><h3>Learn HTML</h3><p>From your first
tag to a complete page.</p><p class="price">120 EGP</p></article>
        <article class="card"><h3>CSS in Practice</h3><p>Layouts,
colours and typography.</p><p class="price">150 EGP</p></article>
        <article class="card"><h3>JavaScript Basics</h3><p>Make pages
interactive.</p><p class="price">180 EGP</p></article>
        <article class="card"><h3>Web Accessibility</h3><p>Pages
everyone can use.</p><p class="price">95 EGP</p></article>
      </div>
    </section>
    <section id="about" class="wrap about">
      <h2>About us</h2>
      <p>Founded by Mohamed Khattab. PDF and printed books about web
development.</p>
      <details><summary>Opening hours</summary><p>Saturday to
Thursday 10:00 to 22:00, Friday 14:00 to 22:00.</p></details>
    </section>
    <section id="contact" class="wrap">
      <h2>Contact</h2>
      <form action="/contact" method="post" class="form">
        <label for="n">Name</label><input id="n" name="name" required>
```

```
        <label for="e">Email</label><input id="e" name="email"
type="email" required>
        <label for="m">Message</label><textarea id="m" name="message"
rows="4" required></textarea>
        <button>Send</button>
      </form>
    </section>
  </main>
  <footer class="site-footer"><p>&copy; 2026 Cairo Book Shop &middot;
<a href="#main">Back to top</a></p></footer>
</body>
</html>
```

Project 1101: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b90000; --accent: #f4f1ea; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.skip { position: absolute; left: -999px; } .skip:focus { left: 1rem;
top: 1rem; background: #fff; padding: .5rem; z-index: 100; }
.site-header { position: sticky; top: 0; z-index: 10; display: flex;
flex-wrap: wrap; justify-content: space-between; align-items: center;
gap: .5rem 1rem; padding: .75rem 1rem; background: #fff; border-
bottom: 1px solid var(--line); }
.logo { font-weight: 800; color: var(--brand); text-decoration: none;
}
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { padding: .4rem .8rem; border-radius: 6px; text-decoration:
none; color: var(--ink); }
.nav a:hover { background: var(--accent); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(1.8rem, 5vw, 3rem); }
.btn { display: inline-block; padding: .7rem 1.4rem; border-radius:
999px; background: #fff; color: var(--brand); text-decoration: none;
font-weight: 700; }
.wrap { max-width: 60rem; margin: 0 auto; padding: 3rem 1rem; }
.grid { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(13rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
.price { font-weight: 700; color: var(--brand); }
.about { background: #fafafa; }
details { margin-top: 1rem; } summary { cursor: pointer; font-weight:
600; }
```

```
.form { display: grid; gap: .4rem; max-width: 30rem; }
.form label { font-weight: 600; margin-top: .6rem; }
.form input, .form textarea { padding: .6rem; border: 1px solid #bbb;
border-radius: 8px; font: inherit; }
.form button { justify-self: start; margin-top: 1rem; padding: .7rem
1.4rem; border: 0; border-radius: 999px; background: var(--brand);
color: #fff; font: inherit; }
.site-footer { text-align: center; padding: 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
h2 { scroll-margin-top: 4rem; }
```

Project 1101 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cairo Book Shop - Complete site</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main"><ul class="nav">	A block of navigation links; aria-label names it for screen readers.
Books About<...	A hyperlink; href gives the destination.
<main id="main">	The unique content of this page; exactly one per page.
<section class="hero">	A thematic group of content, normally with its own heading.
PDF and printed books about web development	The main heading; only one per page.
Welcome to Cairo Book Shop in Giza.	A paragraph of text.

Line	What it does
Explore	A link styled as a button; it navigates, so it is a link and not a <button>.
Our books	Second-level heading for a section.
	Generic block container for grouping and layout.
<article class="card"><h3>Learn HTML</h3><p>From your first tag to ...	A self-contained piece: card, post, product.
<article class="card"><h3>CSS in Practice</h3><p>Layouts, colours a...	Third-level heading, inside an h2 section.
<details><summary>Opening hours</summary><p>Saturday to Thursday 10...	Disclosure widget that can be opened and closed.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
<label for="n">Name</label><input id="n" name="name" required>	Text label for a control; for matches the control's id, or the label wraps the control.
<label for="e">Email</label><input id="e" name="email" type="email"...	Email field: validated automatically and shows the @ keyboard on phones.
<label for="m">Message</label><textarea id="m" name="message" rows=...	Multi-line text field.
<button>Send</button>	A clickable button; inside a form it submits by default.

Line	What it does
<footer class="site-footer"><p>© 2026 Cairo Book Shop ·...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b90000;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: #fff;	Background colour or image.
padding: .5rem;	Space inside the element between its border and content.
z-index: 100;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
align-items: center;	Centres items on the cross axis.
gap: .5rem 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-weight: 800;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
border-radius: 6px;	Rounds the corners.
.nav a:hover {	Applies while the pointer is over the element.
text-align: center;	Centres inline content such as text.
font-size: clamp(1.8rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
grid-template-columns: repeat(auto-fit, minmax(13rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	The line around the element: width, style and colour.
} summary { cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-top: 1px solid var(--line);	A top border used as an accent or separator.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.

Check your work

- Skip link appears on first Tab
- Anchor links land below the sticky header
- One h1
- Form fully labelled
- Passes the W3C validator

Exercises

1. Add smooth scrolling with scroll-behavior: smooth (respecting reduced motion).
2. Add an Arabic RTL version.
3. Split into multiple pages with a shared stylesheet.

Theme data for this project

Field	Value
Business	Cairo Book Shop
Tagline	PDF and printed books about web development
City	Giza
Owner	Mohamed Khattab
Brand colour	#b90000
Accent colour	#f4f1ea
Offers	Learn HTML (120 EGP); CSS in Practice (150 EGP); JavaScript Basics (180 EGP); Web Accessibility (95 EGP)

Project 1102: Complete one-page website for Nile Bakery

Theme: Nile Bakery (Cairo) | Level 3 | Files: index.html, styles.css

Brief

Combine everything into a single-page site: skip link, sticky header with anchor navigation, hero, offers grid, about with details, contact form and footer.

Learning goals

- Assemble a full page from components
- Use in-page anchor navigation with scroll-margin-top
- Provide a skip link

Elements and CSS used

HTML elements	CSS features
a.skip, header, nav, main, section, h1-h3, article, details, summary, form, label, input, textarea, button, footer	position: sticky, z-index, scroll-margin-top, grid auto-fit, clamp(), focus styles for skip link

Build guide

1. Write the skeleton with four sections that have ids.
2. Add the sticky header with links to those ids.
3. Add a skip link as the first element in body.
4. Style the hero, grid, about and form.
5. Add scroll-margin-top to h2 so anchors are not hidden by the header.

6. Validate the whole page and test keyboard navigation.

Project 1102: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nile Bakery - Complete site</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <a class="skip" href="#main">Skip to content</a>
  <header class="site-header">
    <a class="logo" href="index.html">Nile Bakery</a>
    <nav aria-label="Main"><ul class="nav">
      <li><a href="#offers">Pastries</a></li><li><a
href="#about">About</a></li><li><a href="#contact">Contact</a></li>
    </ul></nav>
  </header>
  <main id="main">
    <section class="hero">
      <h1>Fresh bread and pastries every morning</h1>
      <p>Welcome to Nile Bakery in Cairo.</p>
      <a class="btn" href="#offers">Explore</a>
    </section>
    <section id="offers" class="wrap">
      <h2>Our pastries</h2>
      <div class="grid">
        <article class="card"><h3>Sourdough loaf</h3><p>Slow
fermented, crisp crust.</p><p class="price">60 EGP</p></article>
        <article class="card"><h3>Croissant</h3><p>Butter, 27 layers.
</p><p class="price">35 EGP</p></article>
        <article class="card"><h3>Date cookies</h3><p>Traditional
maamoul style.</p><p class="price">80 EGP</p></article>
        <article class="card"><h3>Baklava box</h3><p>Pistachio and
honey.</p><p class="price">220 EGP</p></article>
      </div>
    </section>
    <section id="about" class="wrap about">
      <h2>About us</h2>
      <p>Founded by Sara Adel. Fresh bread and pastries every morning.
</p>
      <details><summary>Opening hours</summary><p>Saturday to
Thursday 10:00 to 22:00, Friday 14:00 to 22:00.</p></details>
    </section>
    <section id="contact" class="wrap">
      <h2>Contact</h2>
      <form action="/contact" method="post" class="form">
        <label for="n">Name</label><input id="n" name="name" required>
```

```
        <label for="e">Email</label><input id="e" name="email"
type="email" required>
        <label for="m">Message</label><textarea id="m" name="message"
rows="4" required></textarea>
        <button>Send</button>
      </form>
    </section>
  </main>
  <footer class="site-footer"><p>&copy; 2026 Nile Bakery &middot; <a
href="#main">Back to top</a></p></footer>
</body>
</html>
```

Project 1102: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a0522d; --accent: #fff6ec; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.skip { position: absolute; left: -999px; } .skip:focus { left: 1rem;
top: 1rem; background: #fff; padding: .5rem; z-index: 100; }
.site-header { position: sticky; top: 0; z-index: 10; display: flex;
flex-wrap: wrap; justify-content: space-between; align-items: center;
gap: .5rem 1rem; padding: .75rem 1rem; background: #fff; border-
bottom: 1px solid var(--line); }
.logo { font-weight: 800; color: var(--brand); text-decoration: none;
}
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { padding: .4rem .8rem; border-radius: 6px; text-decoration:
none; color: var(--ink); }
.nav a:hover { background: var(--accent); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(1.8rem, 5vw, 3rem); }
.btn { display: inline-block; padding: .7rem 1.4rem; border-radius:
999px; background: #fff; color: var(--brand); text-decoration: none;
font-weight: 700; }
.wrap { max-width: 60rem; margin: 0 auto; padding: 3rem 1rem; }
.grid { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(13rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
.price { font-weight: 700; color: var(--brand); }
.about { background: #fafafa; }
details { margin-top: 1rem; } summary { cursor: pointer; font-weight:
600; }
```

```
.form { display: grid; gap: .4rem; max-width: 30rem; }
.form label { font-weight: 600; margin-top: .6rem; }
.form input, .form textarea { padding: .6rem; border: 1px solid #bbb;
border-radius: 8px; font: inherit; }
.form button { justify-self: start; margin-top: 1rem; padding: .7rem
1.4rem; border: 0; border-radius: 999px; background: var(--brand);
color: #fff; font: inherit; }
.site-footer { text-align: center; padding: 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
h2 { scroll-margin-top: 4rem; }
```

Project 1102 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nile Bakery - Complete site</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main"><ul class="nav">	A block of navigation links; aria-label names it for screen readers.
Pastries <a href="#about">About<//...	A hyperlink; href gives the destination.
<main id="main">	The unique content of this page; exactly one per page.
<section class="hero">	A thematic group of content, normally with its own heading.
Fresh bread and pastries every morning	The main heading; only one per page.
Welcome to Nile Bakery in Cairo.	A paragraph of text.

Line	What it does
Explore	A link styled as a button; it navigates, so it is a link and not a <button>.
Our pastries	Second-level heading for a section.
	Generic block container for grouping and layout.
<article class="card"> Sourdough loaf Slow fermented, cri...	A self-contained piece: card, post, product.
<article class="card"> Croissant Butter, 27 layers. <p...	Third-level heading, inside an h2 section.
<details><summary>Opening hours</summary> Saturday to Thursday 10...	Disclosure widget that can be opened and closed.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
<label for="n">Name</label><input id="n" name="name" required>	Text label for a control; for matches the control's id, or the label wraps the control.
<label for="e">Email</label><input id="e" name="email" type="email"...	Email field: validated automatically and shows the @ keyboard on phones.
<label for="m">Message</label><textarea id="m" name="message" rows=...	Multi-line text field.
<button>Send</button>	A clickable button; inside a form it submits by default.
<footer class="site-footer"> © 2026 Nile Bakery · <a ...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a0522d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: #fff;	Background colour or image.
padding: .5rem;	Space inside the element between its border and content.
z-index: 100;	Stacking order for positioned elements; higher is on top.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
align-items: center;	Centres items on the cross axis.
gap: .5rem 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-weight: 800;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
border-radius: 6px;	Rounds the corners.
.nav a:hover {	Applies while the pointer is over the element.
text-align: center;	Centres inline content such as text.
font-size: clamp(1.8rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.

Declaration	What it does
grid-template-columns: repeat(auto-fit, minmax(13rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	The line around the element: width, style and colour.
} summary { cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-top: 1px solid var(--line);	A top border used as an accent or separator.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.

Check your work

- Skip link appears on first Tab
- Anchor links land below the sticky header
- One h1
- Form fully labelled
- Passes the W3C validator

Exercises

1. Add smooth scrolling with scroll-behavior: smooth (respecting reduced motion).
2. Add an Arabic RTL version.
3. Split into multiple pages with a shared stylesheet.

Theme data for this project

Field	Value
Business	Nile Bakery
Tagline	Fresh bread and pastries every morning
City	Cairo
Owner	Sara Adel
Brand colour	#a0522d
Accent colour	#fff6ec
Offers	Sourdough loaf (60 EGP); Croissant (35 EGP); Date cookies (80 EGP); Baklava box (220 EGP)

Project 1103: Complete one-page website for Pyramid Fitness

Theme: Pyramid Fitness (6th of October) | Level 3 | Files: index.html, styles.css

Brief

Combine everything into a single-page site: skip link, sticky header with anchor navigation, hero, offers grid, about with details, contact form and footer.

Learning goals

- Assemble a full page from components
- Use in-page anchor navigation with scroll-margin-top
- Provide a skip link

Elements and CSS used

HTML elements	CSS features
a.skip, header, nav, main, section, h1-h3, article, details, summary, form, label, input, textarea, button, footer	position: sticky, z-index, scroll-margin-top, grid auto-fit, clamp(), focus styles for skip link

Build guide

1. Write the skeleton with four sections that have ids.
2. Add the sticky header with links to those ids.
3. Add a skip link as the first element in body.
4. Style the hero, grid, about and form.
5. Add scroll-margin-top to h2 so anchors are not hidden by the header.

6. Validate the whole page and test keyboard navigation.

Project 1103: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Pyramid Fitness - Complete site</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <a class="skip" href="#main">Skip to content</a>
  <header class="site-header">
    <a class="logo" href="index.html">Pyramid Fitness</a>
    <nav aria-label="Main"><ul class="nav">
      <li><a href="#offers">Classes</a></li><li><a
href="#about">About</a></li><li><a href="#contact">Contact</a></li>
    </ul></nav>
  </header>
  <main id="main">
    <section class="hero">
      <h1>Train smarter, feel stronger</h1>
      <p>Welcome to Pyramid Fitness in 6th of October.</p>
      <a class="btn" href="#offers">Explore</a>
    </section>
    <section id="offers" class="wrap">
      <h2>Our classes</h2>
      <div class="grid">
        <article class="card"><h3>Morning yoga</h3><p>Flexibility and
calm, 60 minutes.</p><p class="price">100 EGP</p></article>
        <article class="card"><h3>Strength circuit</h3><p>Full body,
all levels.</p><p class="price">120 EGP</p></article>
        <article class="card"><h3>Spinning</h3><p>High energy cycling.
</p><p class="price">110 EGP</p></article>
        <article class="card"><h3>Personal training</h3><p>One to one
coaching.</p><p class="price">350 EGP</p></article>
      </div>
    </section>
    <section id="about" class="wrap about">
      <h2>About us</h2>
      <p>Founded by Omar Farouk. Train smarter, feel stronger.</p>
      <details><summary>Opening hours</summary><p>Saturday to
Thursday 10:00 to 22:00, Friday 14:00 to 22:00.</p></details>
    </section>
    <section id="contact" class="wrap">
      <h2>Contact</h2>
      <form action="/contact" method="post" class="form">
        <label for="n">Name</label><input id="n" name="name" required>
        <label for="e">Email</label><input id="e" name="email"
```

```
type="email" required>
        <label for="m">Message</label><textarea id="m" name="message"
rows="4" required></textarea>
        <button>Send</button>
      </form>
    </section>
  </main>
  <footer class="site-footer"><p>&copy; 2026 Pyramid Fitness &middot;
<a href="#main">Back to top</a></p></footer>
</body>
</html>
```

Project 1103: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0f766e; --accent: #ecfdf5; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.skip { position: absolute; left: -999px; } .skip:focus { left: 1rem;
top: 1rem; background: #fff; padding: .5rem; z-index: 100; }
.site-header { position: sticky; top: 0; z-index: 10; display: flex;
flex-wrap: wrap; justify-content: space-between; align-items: center;
gap: .5rem 1rem; padding: .75rem 1rem; background: #fff; border-
bottom: 1px solid var(--line); }
.logo { font-weight: 800; color: var(--brand); text-decoration: none;
}
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { padding: .4rem .8rem; border-radius: 6px; text-decoration:
none; color: var(--ink); }
.nav a:hover { background: var(--accent); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(1.8rem, 5vw, 3rem); }
.btn { display: inline-block; padding: .7rem 1.4rem; border-radius:
999px; background: #fff; color: var(--brand); text-decoration: none;
font-weight: 700; }
.wrap { max-width: 60rem; margin: 0 auto; padding: 3rem 1rem; }
.grid { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(13rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
.price { font-weight: 700; color: var(--brand); }
.about { background: #fafafa; }
details { margin-top: 1rem; } summary { cursor: pointer; font-weight:
600; }
.form { display: grid; gap: .4rem; max-width: 30rem; }
```

```
.form label { font-weight: 600; margin-top: .6rem; }
.form input, .form textarea { padding: .6rem; border: 1px solid #bbb;
border-radius: 8px; font: inherit; }
.form button { justify-self: start; margin-top: 1rem; padding: .7rem
1.4rem; border: 0; border-radius: 999px; background: var(--brand);
color: #fff; font: inherit; }
.site-footer { text-align: center; padding: 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
h2 { scroll-margin-top: 4rem; }
```

Project 1103 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Pyramid Fitness - Complete site</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main"><ul class="nav">	A block of navigation links; aria-label names it for screen readers.
Classes <a href="#about">About</a...	A hyperlink; href gives the destination.
<main id="main">	The unique content of this page; exactly one per page.
<section class="hero">	A thematic group of content, normally with its own heading.
Train smarter, feel stronger	The main heading; only one per page.
Welcome to Pyramid Fitness in 6th of October.	A paragraph of text.

Line	What it does
Explore	A link styled as a button; it navigates, so it is a link and not a <button>.
Our classes	Second-level heading for a section.
	Generic block container for grouping and layout.
<article class="card"><h3>Morning yoga</h3><p>Flexibility and calm,...	A self-contained piece: card, post, product.
<article class="card"><h3>Strength circuit</h3><p>Full body, all le...	Third-level heading, inside an h2 section.
<details><summary>Opening hours</summary><p>Saturday to Thursday 10...	Disclosure widget that can be opened and closed.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
<label for="n">Name</label><input id="n" name="name" required>	Text label for a control; for matches the control's id, or the label wraps the control.
<label for="e">Email</label><input id="e" name="email" type="email"...	Email field: validated automatically and shows the @ keyboard on phones.
<label for="m">Message</label><textarea id="m" name="message" rows=...	Multi-line text field.
<button>Send</button>	A clickable button; inside a form it submits by default.

Line	What it does
<footer class="site-footer"><p>© 2026 Pyramid Fitness ·...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0f766e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: #fff;	Background colour or image.
padding: .5rem;	Space inside the element between its border and content.
z-index: 100;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
align-items: center;	Centres items on the cross axis.
gap: .5rem 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-weight: 800;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
border-radius: 6px;	Rounds the corners.
.nav a:hover {	Applies while the pointer is over the element.
text-align: center;	Centres inline content such as text.
font-size: clamp(1.8rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
grid-template-columns: repeat(auto-fit, minmax(13rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	The line around the element: width, style and colour.
} summary { cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-top: 1px solid var(--line);	A top border used as an accent or separator.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.

Check your work

- Skip link appears on first Tab
- Anchor links land below the sticky header
- One h1
- Form fully labelled
- Passes the W3C validator

Exercises

1. Add smooth scrolling with scroll-behavior: smooth (respecting reduced motion).
2. Add an Arabic RTL version.
3. Split into multiple pages with a shared stylesheet.

Theme data for this project

Field	Value
Business	Pyramid Fitness
Tagline	Train smarter, feel stronger
City	6th of October
Owner	Omar Farouk
Brand colour	#0f766e
Accent colour	#ecfdf5
Offers	Morning yoga (100 EGP); Strength circuit (120 EGP); Spinning (110 EGP); Personal training (350 EGP)

Project 1104: Complete one-page website for Delta Dental Clinic

Theme: Delta Dental Clinic (Mansoura) | Level 3 | Files: index.html, styles.css

Brief

Combine everything into a single-page site: skip link, sticky header with anchor navigation, hero, offers grid, about with details, contact form and footer.

Learning goals

- Assemble a full page from components
- Use in-page anchor navigation with scroll-margin-top
- Provide a skip link

Elements and CSS used

HTML elements	CSS features
a.skip, header, nav, main, section, h1-h3, article, details, summary, form, label, input, textarea, button, footer	position: sticky, z-index, scroll-margin-top, grid auto-fit, clamp(), focus styles for skip link

Build guide

1. Write the skeleton with four sections that have ids.
2. Add the sticky header with links to those ids.
3. Add a skip link as the first element in body.
4. Style the hero, grid, about and form.
5. Add scroll-margin-top to h2 so anchors are not hidden by the header.

6. Validate the whole page and test keyboard navigation.

Project 1104: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Dental Clinic - Complete site</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <a class="skip" href="#main">Skip to content</a>
  <header class="site-header">
    <a class="logo" href="index.html">Delta Dental Clinic</a>
    <nav aria-label="Main"><ul class="nav">
      <li><a href="#offers">Services</a></li><li><a
href="#about">About</a></li><li><a href="#contact">Contact</a></li>
    </ul></nav>
  </header>
  <main id="main">
    <section class="hero">
      <h1>Gentle care for the whole family</h1>
      <p>Welcome to Delta Dental Clinic in Mansoura.</p>
      <a class="btn" href="#offers">Explore</a>
    </section>
    <section id="offers" class="wrap">
      <h2>Our services</h2>
      <div class="grid">
        <article class="card"><h3>Check-up</h3><p>Examination and
cleaning.</p><p class="price">300 EGP</p></article>
        <article class="card"><h3>Whitening</h3><p>Brighter smile in
one visit.</p><p class="price">1500 EGP</p></article>
        <article class="card"><h3>Filling</h3><p>Tooth-coloured
composite.</p><p class="price">600 EGP</p></article>
        <article class="card"><h3>Braces consultation</h3><p>Plan
your treatment.</p><p class="price">Free</p></article>
      </div>
    </section>
    <section id="about" class="wrap about">
      <h2>About us</h2>
      <p>Founded by Dr. Hana Youssef. Gentle care for the whole
family.</p>
      <details><summary>Opening hours</summary><p>Saturday to
Thursday 10:00 to 22:00, Friday 14:00 to 22:00.</p></details>
    </section>
    <section id="contact" class="wrap">
      <h2>Contact</h2>
      <form action="/contact" method="post" class="form">
        <label for="n">Name</label><input id="n" name="name" required>
```

```
        <label for="e">Email</label><input id="e" name="email"
type="email" required>
        <label for="m">Message</label><textarea id="m" name="message"
rows="4" required></textarea>
        <button>Send</button>
      </form>
    </section>
  </main>
  <footer class="site-footer"><p>&copy; 2026 Delta Dental Clinic
&middot; <a href="#main">Back to top</a></p></footer>
</body>
</html>
```

Project 1104: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1d4ed8; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.skip { position: absolute; left: -999px; } .skip:focus { left: 1rem;
top: 1rem; background: #fff; padding: .5rem; z-index: 100; }
.site-header { position: sticky; top: 0; z-index: 10; display: flex;
flex-wrap: wrap; justify-content: space-between; align-items: center;
gap: .5rem 1rem; padding: .75rem 1rem; background: #fff; border-
bottom: 1px solid var(--line); }
.logo { font-weight: 800; color: var(--brand); text-decoration: none;
}
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { padding: .4rem .8rem; border-radius: 6px; text-decoration:
none; color: var(--ink); }
.nav a:hover { background: var(--accent); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(1.8rem, 5vw, 3rem); }
.btn { display: inline-block; padding: .7rem 1.4rem; border-radius:
999px; background: #fff; color: var(--brand); text-decoration: none;
font-weight: 700; }
.wrap { max-width: 60rem; margin: 0 auto; padding: 3rem 1rem; }
.grid { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(13rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
.price { font-weight: 700; color: var(--brand); }
.about { background: #fafafa; }
details { margin-top: 1rem; } summary { cursor: pointer; font-weight:
600; }
```

```
.form { display: grid; gap: .4rem; max-width: 30rem; }
.form label { font-weight: 600; margin-top: .6rem; }
.form input, .form textarea { padding: .6rem; border: 1px solid #bbb;
border-radius: 8px; font: inherit; }
.form button { justify-self: start; margin-top: 1rem; padding: .7rem
1.4rem; border: 0; border-radius: 999px; background: var(--brand);
color: #fff; font: inherit; }
.site-footer { text-align: center; padding: 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
h2 { scroll-margin-top: 4rem; }
```

Project 1104 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Dental Clinic - Complete site</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main"><ul class="nav">	A block of navigation links; aria-label names it for screen readers.
Services <a href="#about">About<//...	A hyperlink; href gives the destination.
<main id="main">	The unique content of this page; exactly one per page.
<section class="hero">	A thematic group of content, normally with its own heading.
Gentle care for the whole family	The main heading; only one per page.
Welcome to Delta Dental Clinic in Mansoura.	A paragraph of text.

Line	What it does
Explore	A link styled as a button; it navigates, so it is a link and not a <button>.
Our services	Second-level heading for a section.
	Generic block container for grouping and layout.
<article class="card"><h3>Check-up</h3><p>Examination and cleaning....	A self-contained piece: card, post, product.
<article class="card"><h3>Whitening</h3><p>Brighter smile in one vi...	Third-level heading, inside an h2 section.
<details><summary>Opening hours</summary><p>Saturday to Thursday 10...	Disclosure widget that can be opened and closed.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
<label for="n">Name</label><input id="n" name="name" required>	Text label for a control; for matches the control's id, or the label wraps the control.
<label for="e">Email</label><input id="e" name="email" type="email"...	Email field: validated automatically and shows the @ keyboard on phones.
<label for="m">Message</label><textarea id="m" name="message" rows=...	Multi-line text field.
<button>Send</button>	A clickable button; inside a form it submits by default.
<footer class="site-footer"><p>© 2026 Delta Dental Clinic &mid...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1d4ed8;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: #fff;	Background colour or image.
padding: .5rem;	Space inside the element between its border and content.
z-index: 100;	Stacking order for positioned elements; higher is on top.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
display: flex;	Turns the element into a flex container (one-dimensional layout).

Declaration	What it does
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
align-items: center;	Centres items on the cross axis.
gap: .5rem 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-weight: 800;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
border-radius: 6px;	Rounds the corners.
.nav a:hover {	Applies while the pointer is over the element.
text-align: center;	Centres inline content such as text.
font-size: clamp(1.8rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.

Declaration	What it does
grid-template-columns: repeat(auto-fit, minmax(13rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	The line around the element: width, style and colour.
} summary { cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-top: 1px solid var(--line);	A top border used as an accent or separator.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.

Check your work

- Skip link appears on first Tab
- Anchor links land below the sticky header
- One h1
- Form fully labelled
- Passes the W3C validator

Exercises

1. Add smooth scrolling with scroll-behavior: smooth (respecting reduced motion).
2. Add an Arabic RTL version.
3. Split into multiple pages with a shared stylesheet.

Theme data for this project

Field	Value
Business	Delta Dental Clinic
Tagline	Gentle care for the whole family
City	Mansoura
Owner	Dr. Hana Youssef
Brand colour	#1d4ed8
Accent colour	#eff6ff
Offers	Check-up (300 EGP); Whitening (1500 EGP); Filling (600 EGP); Braces consultation (Free)

Project 1105: Complete one-page website for Red Sea Travel

Theme: Red Sea Travel (Hurghada) | Level 3 | Files: index.html, styles.css

Brief

Combine everything into a single-page site: skip link, sticky header with anchor navigation, hero, offers grid, about with details, contact form and footer.

Learning goals

- Assemble a full page from components
- Use in-page anchor navigation with scroll-margin-top
- Provide a skip link

Elements and CSS used

HTML elements	CSS features
a.skip, header, nav, main, section, h1-h3, article, details, summary, form, label, input, textarea, button, footer	position: sticky, z-index, scroll-margin-top, grid auto-fit, clamp(), focus styles for skip link

Build guide

1. Write the skeleton with four sections that have ids.
2. Add the sticky header with links to those ids.
3. Add a skip link as the first element in body.
4. Style the hero, grid, about and form.
5. Add scroll-margin-top to h2 so anchors are not hidden by the header.

6. Validate the whole page and test keyboard navigation.

Project 1105: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Red Sea Travel - Complete site</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <a class="skip" href="#main">Skip to content</a>
  <header class="site-header">
    <a class="logo" href="index.html">Red Sea Travel</a>
    <nav aria-label="Main"><ul class="nav">
      <li><a href="#offers">Tours</a></li><li><a href="#about">About</
a></li><li><a href="#contact">Contact</a></li>
    </ul></nav>
  </header>
  <main id="main">
    <section class="hero">
      <h1>Discover Egypt from desert to reef</h1>
      <p>Welcome to Red Sea Travel in Hurghada.</p>
      <a class="btn" href="#offers">Explore</a>
    </section>
    <section id="offers" class="wrap">
      <h2>Our tours</h2>
      <div class="grid">
        <article class="card"><h3>Luxor day trip</h3><p>Karnak,
Valley of the Kings.</p><p class="price">1200 EGP</p></article>
        <article class="card"><h3>Snorkelling</h3><p>Giftun island
reefs.</p><p class="price">700 EGP</p></article>
        <article class="card"><h3>Desert safari</h3><p>Quad bikes and
Bedouin dinner.</p><p class="price">900 EGP</p></article>
        <article class="card"><h3>Nile cruise</h3><p>Three nights
Aswan to Luxor.</p><p class="price">6500 EGP</p></article>
      </div>
    </section>
    <section id="about" class="wrap about">
      <h2>About us</h2>
      <p>Founded by Laila Mansour. Discover Egypt from desert to reef.
</p>
      <details><summary>Opening hours</summary><p>Saturday to
Thursday 10:00 to 22:00, Friday 14:00 to 22:00.</p></details>
    </section>
    <section id="contact" class="wrap">
      <h2>Contact</h2>
      <form action="/contact" method="post" class="form">
        <label for="n">Name</label><input id="n" name="name" required>
```

```
        <label for="e">Email</label><input id="e" name="email"
type="email" required>
        <label for="m">Message</label><textarea id="m" name="message"
rows="4" required></textarea>
        <button>Send</button>
      </form>
    </section>
  </main>
  <footer class="site-footer"><p>&copy; 2026 Red Sea Travel &middot;
<a href="#main">Back to top</a></p></footer>
</body>
</html>
```

Project 1105: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0369a1; --accent: #f0f9ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.skip { position: absolute; left: -999px; } .skip:focus { left: 1rem;
top: 1rem; background: #fff; padding: .5rem; z-index: 100; }
.site-header { position: sticky; top: 0; z-index: 10; display: flex;
flex-wrap: wrap; justify-content: space-between; align-items: center;
gap: .5rem 1rem; padding: .75rem 1rem; background: #fff; border-
bottom: 1px solid var(--line); }
.logo { font-weight: 800; color: var(--brand); text-decoration: none;
}
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { padding: .4rem .8rem; border-radius: 6px; text-decoration:
none; color: var(--ink); }
.nav a:hover { background: var(--accent); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(1.8rem, 5vw, 3rem); }
.btn { display: inline-block; padding: .7rem 1.4rem; border-radius:
999px; background: #fff; color: var(--brand); text-decoration: none;
font-weight: 700; }
.wrap { max-width: 60rem; margin: 0 auto; padding: 3rem 1rem; }
.grid { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(13rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
.price { font-weight: 700; color: var(--brand); }
.about { background: #fafafa; }
details { margin-top: 1rem; } summary { cursor: pointer; font-weight:
600; }
```

```
.form { display: grid; gap: .4rem; max-width: 30rem; }
.form label { font-weight: 600; margin-top: .6rem; }
.form input, .form textarea { padding: .6rem; border: 1px solid #bbb;
border-radius: 8px; font: inherit; }
.form button { justify-self: start; margin-top: 1rem; padding: .7rem
1.4rem; border: 0; border-radius: 999px; background: var(--brand);
color: #fff; font: inherit; }
.site-footer { text-align: center; padding: 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
h2 { scroll-margin-top: 4rem; }
```

Project 1105 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Red Sea Travel - Complete site</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main"><ul class="nav">	A block of navigation links; aria-label names it for screen readers.
Tours About<...	A hyperlink; href gives the destination.
<main id="main">	The unique content of this page; exactly one per page.
<section class="hero">	A thematic group of content, normally with its own heading.
Discover Egypt from desert to reef	The main heading; only one per page.
Welcome to Red Sea Travel in Hurghada.	A paragraph of text.

Line	What it does
Explore	A link styled as a button; it navigates, so it is a link and not a <button>.
Our tours	Second-level heading for a section.
	Generic block container for grouping and layout.
<article class="card"><h3>Luxor day trip</h3><p>Karnak, Valley of t...	A self-contained piece: card, post, product.
<article class="card"><h3>Snorkelling</h3><p>Giftun island reefs.<//...	Third-level heading, inside an h2 section.
<details><summary>Opening hours</summary><p>Saturday to Thursday 10...	Disclosure widget that can be opened and closed.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
<label for="n">Name</label><input id="n" name="name" required>	Text label for a control; for matches the control's id, or the label wraps the control.
<label for="e">Email</label><input id="e" name="email" type="email"...	Email field: validated automatically and shows the @ keyboard on phones.
<label for="m">Message</label><textarea id="m" name="message" rows=...	Multi-line text field.
<button>Send</button>	A clickable button; inside a form it submits by default.

Line	What it does
<footer class="site-footer"><p>© 2026 Red Sea Travel · ...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0369a1;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: #fff;	Background colour or image.
padding: .5rem;	Space inside the element between its border and content.
z-index: 100;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
align-items: center;	Centres items on the cross axis.
gap: .5rem 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-weight: 800;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
border-radius: 6px;	Rounds the corners.
.nav a:hover {	Applies while the pointer is over the element.
text-align: center;	Centres inline content such as text.
font-size: clamp(1.8rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
grid-template-columns: repeat(auto-fit, minmax(13rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	The line around the element: width, style and colour.
} summary { cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-top: 1px solid var(--line);	A top border used as an accent or separator.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.

Check your work

- Skip link appears on first Tab
- Anchor links land below the sticky header
- One h1
- Form fully labelled
- Passes the W3C validator

Exercises

1. Add smooth scrolling with scroll-behavior: smooth (respecting reduced motion).
2. Add an Arabic RTL version.
3. Split into multiple pages with a shared stylesheet.

Theme data for this project

Field	Value
Business	Red Sea Travel
Tagline	Discover Egypt from desert to reef
City	Hurghada
Owner	Laila Mansour
Brand colour	#0369a1
Accent colour	#f0f9ff
Offers	Luxor day trip (1200 EGP); Snorkelling (700 EGP); Desert safari (900 EGP); Nile cruise (6500 EGP)

Project 1106: Complete one-page website for Lotus Language School

Theme: Lotus Language School (Alexandria) | Level 3 | Files: index.html, styles.css

Brief

Combine everything into a single-page site: skip link, sticky header with anchor navigation, hero, offers grid, about with details, contact form and footer.

Learning goals

- Assemble a full page from components
- Use in-page anchor navigation with scroll-margin-top
- Provide a skip link

Elements and CSS used

HTML elements	CSS features
a.skip, header, nav, main, section, h1-h3, article, details, summary, form, label, input, textarea, button, footer	position: sticky, z-index, scroll-margin-top, grid auto-fit, clamp(), focus styles for skip link

Build guide

1. Write the skeleton with four sections that have ids.
2. Add the sticky header with links to those ids.
3. Add a skip link as the first element in body.
4. Style the hero, grid, about and form.
5. Add scroll-margin-top to h2 so anchors are not hidden by the header.

6. Validate the whole page and test keyboard navigation.

Project 1106: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Lotus Language School - Complete site</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <a class="skip" href="#main">Skip to content</a>
  <header class="site-header">
    <a class="logo" href="index.html">Lotus Language School</a>
    <nav aria-label="Main"><ul class="nav">
      <li><a href="#offers">Courses</a></li><li><a
href="#about">About</a></li><li><a href="#contact">Contact</a></li>
    </ul></nav>
  </header>
  <main id="main">
    <section class="hero">
      <h1>Learn English, French and German in small groups</h1>
      <p>Welcome to Lotus Language School in Alexandria.</p>
      <a class="btn" href="#offers">Explore</a>
    </section>
    <section id="offers" class="wrap">
      <h2>Our courses</h2>
      <div class="grid">
        <article class="card"><h3>English A1</h3><p>Beginner, 8 weeks.
</p><p class="price">1800 EGP</p></article>
        <article class="card"><h3>French B1</h3><p>Intermediate
conversation.</p><p class="price">2200 EGP</p></article>
        <article class="card"><h3>German A2</h3><p>Grammar and
speaking.</p><p class="price">2000 EGP</p></article>
        <article class="card"><h3>IELTS preparation</h3><p>Exam
strategies.</p><p class="price">3000 EGP</p></article>
      </div>
    </section>
    <section id="about" class="wrap about">
      <h2>About us</h2>
      <p>Founded by Nour El Din. Learn English, French and German in
small groups.</p>
      <details><summary>Opening hours</summary><p>Saturday to
Thursday 10:00 to 22:00, Friday 14:00 to 22:00.</p></details>
    </section>
    <section id="contact" class="wrap">
      <h2>Contact</h2>
      <form action="/contact" method="post" class="form">
        <label for="n">Name</label><input id="n" name="name" required>
```

```
        <label for="e">Email</label><input id="e" name="email"
type="email" required>
        <label for="m">Message</label><textarea id="m" name="message"
rows="4" required></textarea>
        <button>Send</button>
      </form>
    </section>
  </main>
  <footer class="site-footer"><p>&copy; 2026 Lotus Language School
&middot; <a href="#main">Back to top</a></p></footer>
</body>
</html>
```

Project 1106: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #7c3aed; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.skip { position: absolute; left: -999px; } .skip:focus { left: 1rem;
top: 1rem; background: #fff; padding: .5rem; z-index: 100; }
.site-header { position: sticky; top: 0; z-index: 10; display: flex;
flex-wrap: wrap; justify-content: space-between; align-items: center;
gap: .5rem 1rem; padding: .75rem 1rem; background: #fff; border-
bottom: 1px solid var(--line); }
.logo { font-weight: 800; color: var(--brand); text-decoration: none;
}
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { padding: .4rem .8rem; border-radius: 6px; text-decoration:
none; color: var(--ink); }
.nav a:hover { background: var(--accent); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(1.8rem, 5vw, 3rem); }
.btn { display: inline-block; padding: .7rem 1.4rem; border-radius:
999px; background: #fff; color: var(--brand); text-decoration: none;
font-weight: 700; }
.wrap { max-width: 60rem; margin: 0 auto; padding: 3rem 1rem; }
.grid { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(13rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
.price { font-weight: 700; color: var(--brand); }
.about { background: #fafafa; }
details { margin-top: 1rem; } summary { cursor: pointer; font-weight:
600; }
```

```
.form { display: grid; gap: .4rem; max-width: 30rem; }
.form label { font-weight: 600; margin-top: .6rem; }
.form input, .form textarea { padding: .6rem; border: 1px solid #bbb;
border-radius: 8px; font: inherit; }
.form button { justify-self: start; margin-top: 1rem; padding: .7rem
1.4rem; border: 0; border-radius: 999px; background: var(--brand);
color: #fff; font: inherit; }
.site-footer { text-align: center; padding: 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
h2 { scroll-margin-top: 4rem; }
```

Project 1106 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Lotus Language School - Complete site</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main"><ul class="nav">	A block of navigation links; aria-label names it for screen readers.
Courses <a href="#about">About</a...	A hyperlink; href gives the destination.
<main id="main">	The unique content of this page; exactly one per page.
<section class="hero">	A thematic group of content, normally with its own heading.
Learn English, French and German in small groups	The main heading; only one per page.

Line	What it does
Welcome to Lotus Language School in Alexandria.	A paragraph of text.
Explore	A link styled as a button; it navigates, so it is a link and not a <button>.
Our courses	Second-level heading for a section.
	Generic block container for grouping and layout.
<article class="card"> English A1 Beginner, 8 weeks. <...	A self-contained piece: card, post, product.
<article class="card"> French B1 Intermediate conversatio...	Third-level heading, inside an h2 section.
<details><summary>Opening hours</summary> Saturday to Thursday 10...	Disclosure widget that can be opened and closed.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
<label for="n">Name</label><input id="n" name="name" required>	Text label for a control; for matches the control's id, or the label wraps the control.
<label for="e">Email</label><input id="e" name="email" type="email"...	Email field: validated automatically and shows the @ keyboard on phones.
<label for="m">Message</label><textarea id="m" name="message" rows=...	Multi-line text field.

Line	What it does
<button>Send</button>	A clickable button; inside a form it submits by default.
<footer class="site-footer"><p>© 2026 Lotus Language School &m...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #7c3aed;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: #fff;	Background colour or image.
padding: .5rem;	Space inside the element between its border and content.

Declaration	What it does
z-index: 100;	Stacking order for positioned elements; higher is on top.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
align-items: center;	Centres items on the cross axis.
gap: .5rem 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-weight: 800;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
border-radius: 6px;	Rounds the corners.
.nav a:hover {	Applies while the pointer is over the element.
text-align: center;	Centres inline content such as text.
font-size: clamp(1.8rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
grid-template-columns: repeat(auto-fit, minmax(13rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	The line around the element: width, style and colour.
} summary { cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-top: 1px solid var(--line);	A top border used as an accent or separator.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.

Check your work

- Skip link appears on first Tab
- Anchor links land below the sticky header
- One h1
- Form fully labelled
- Passes the W3C validator

Exercises

1. Add smooth scrolling with scroll-behavior: smooth (respecting reduced motion).
2. Add an Arabic RTL version.
3. Split into multiple pages with a shared stylesheet.

Theme data for this project

Field	Value
Business	Lotus Language School
Tagline	Learn English, French and German in small groups
City	Alexandria
Owner	Nour El Din
Brand colour	#7c3aed
Accent colour	#f5f3ff
Offers	English A1 (1800 EGP); French B1 (2200 EGP); German A2 (2000 EGP); IELTS preparation (3000 EGP)

Project 1107: Complete one-page website for Green Leaf Cafe

Theme: Green Leaf Cafe (Zamalek) | Level 3 | Files: index.html, styles.css

Brief

Combine everything into a single-page site: skip link, sticky header with anchor navigation, hero, offers grid, about with details, contact form and footer.

Learning goals

- Assemble a full page from components
- Use in-page anchor navigation with scroll-margin-top
- Provide a skip link

Elements and CSS used

HTML elements	CSS features
a.skip, header, nav, main, section, h1-h3, article, details, summary, form, label, input, textarea, button, footer	position: sticky, z-index, scroll-margin-top, grid auto-fit, clamp(), focus styles for skip link

Build guide

1. Write the skeleton with four sections that have ids.
2. Add the sticky header with links to those ids.
3. Add a skip link as the first element in body.
4. Style the hero, grid, about and form.
5. Add scroll-margin-top to h2 so anchors are not hidden by the header.

6. Validate the whole page and test keyboard navigation.

Project 1107: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Green Leaf Cafe - Complete site</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <a class="skip" href="#main">Skip to content</a>
  <header class="site-header">
    <a class="logo" href="index.html">Green Leaf Cafe</a>
    <nav aria-label="Main"><ul class="nav">
      <li><a href="#offers">Drinks</a></li><li><a
href="#about">About</a></li><li><a href="#contact">Contact</a></li>
    </ul></nav>
  </header>
  <main id="main">
    <section class="hero">
      <h1>Specialty coffee and quiet corners</h1>
      <p>Welcome to Green Leaf Cafe in Zamalek.</p>
      <a class="btn" href="#offers">Explore</a>
    </section>
    <section id="offers" class="wrap">
      <h2>Our drinks</h2>
      <div class="grid">
        <article class="card"><h3>Flat white</h3><p>Double shot,
silky milk.</p><p class="price">55 EGP</p></article>
        <article class="card"><h3>Cold brew</h3><p>18 hours steeped.</
p><p class="price">60 EGP</p></article>
        <article class="card"><h3>Hibiscus iced tea</h3><p>Karkade
with mint.</p><p class="price">40 EGP</p></article>
        <article class="card"><h3>Cheesecake</h3><p>Baked, with
berries.</p><p class="price">75 EGP</p></article>
      </div>
    </section>
    <section id="about" class="wrap about">
      <h2>About us</h2>
      <p>Founded by Karim Said. Specialty coffee and quiet corners.</
p>
      <details><summary>Opening hours</summary><p>Saturday to
Thursday 10:00 to 22:00, Friday 14:00 to 22:00.</p></details>
    </section>
    <section id="contact" class="wrap">
      <h2>Contact</h2>
      <form action="/contact" method="post" class="form">
        <label for="n">Name</label><input id="n" name="name" required>
```

```
        <label for="e">Email</label><input id="e" name="email"
type="email" required>
        <label for="m">Message</label><textarea id="m" name="message"
rows="4" required></textarea>
        <button>Send</button>
      </form>
    </section>
  </main>
  <footer class="site-footer"><p>&copy; 2026 Green Leaf Cafe &middot;
<a href="#main">Back to top</a></p></footer>
</body>
</html>
```

Project 1107: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #166534; --accent: #f0fdf4; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.skip { position: absolute; left: -999px; } .skip:focus { left: 1rem;
top: 1rem; background: #fff; padding: .5rem; z-index: 100; }
.site-header { position: sticky; top: 0; z-index: 10; display: flex;
flex-wrap: wrap; justify-content: space-between; align-items: center;
gap: .5rem 1rem; padding: .75rem 1rem; background: #fff; border-
bottom: 1px solid var(--line); }
.logo { font-weight: 800; color: var(--brand); text-decoration: none;
}
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { padding: .4rem .8rem; border-radius: 6px; text-decoration:
none; color: var(--ink); }
.nav a:hover { background: var(--accent); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(1.8rem, 5vw, 3rem); }
.btn { display: inline-block; padding: .7rem 1.4rem; border-radius:
999px; background: #fff; color: var(--brand); text-decoration: none;
font-weight: 700; }
.wrap { max-width: 60rem; margin: 0 auto; padding: 3rem 1rem; }
.grid { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(13rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
.price { font-weight: 700; color: var(--brand); }
.about { background: #fafafa; }
details { margin-top: 1rem; } summary { cursor: pointer; font-weight:
600; }
```

```
.form { display: grid; gap: .4rem; max-width: 30rem; }
.form label { font-weight: 600; margin-top: .6rem; }
.form input, .form textarea { padding: .6rem; border: 1px solid #bbb;
border-radius: 8px; font: inherit; }
.form button { justify-self: start; margin-top: 1rem; padding: .7rem
1.4rem; border: 0; border-radius: 999px; background: var(--brand);
color: #fff; font: inherit; }
.site-footer { text-align: center; padding: 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
h2 { scroll-margin-top: 4rem; }
```

Project 1107 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Green Leaf Cafe - Complete site</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main"><ul class="nav">	A block of navigation links; aria-label names it for screen readers.
Drinks About...	A hyperlink; href gives the destination.
<main id="main">	The unique content of this page; exactly one per page.
<section class="hero">	A thematic group of content, normally with its own heading.
Specialty coffee and quiet corners	The main heading; only one per page.
Welcome to Green Leaf Cafe in Zamalek.	A paragraph of text.

Line	What it does
Explore	A link styled as a button; it navigates, so it is a link and not a <button>.
Our drinks	Second-level heading for a section.
	Generic block container for grouping and layout.
<article class="card"> Flat white Double shot, silky milk...	A self-contained piece: card, post, product.
<article class="card"> Cold brew 18 hours steeped. <p ...	Third-level heading, inside an h2 section.
<details><summary>Opening hours</summary> Saturday to Thursday 10...	Disclosure widget that can be opened and closed.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
<label for="n">Name</label><input id="n" name="name" required>	Text label for a control; for matches the control's id, or the label wraps the control.
<label for="e">Email</label><input id="e" name="email" type="email"...	Email field: validated automatically and shows the @ keyboard on phones.
<label for="m">Message</label><textarea id="m" name="message" rows=...	Multi-line text field.
<button>Send</button>	A clickable button; inside a form it submits by default.

Line	What it does
<footer class="site-footer"><p>© 2026 Green Leaf Cafe ·...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #166534;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: #fff;	Background colour or image.
padding: .5rem;	Space inside the element between its border and content.
z-index: 100;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
align-items: center;	Centres items on the cross axis.
gap: .5rem 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-weight: 800;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
border-radius: 6px;	Rounds the corners.
.nav a:hover {	Applies while the pointer is over the element.
text-align: center;	Centres inline content such as text.
font-size: clamp(1.8rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
grid-template-columns: repeat(auto-fit, minmax(13rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	The line around the element: width, style and colour.
} summary { cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-top: 1px solid var(--line);	A top border used as an accent or separator.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.

Check your work

- Skip link appears on first Tab
- Anchor links land below the sticky header
- One h1
- Form fully labelled
- Passes the W3C validator

Exercises

1. Add smooth scrolling with scroll-behavior: smooth (respecting reduced motion).
2. Add an Arabic RTL version.
3. Split into multiple pages with a shared stylesheet.

Theme data for this project

Field	Value
Business	Green Leaf Cafe
Tagline	Specialty coffee and quiet corners
City	Zamalek
Owner	Karim Said
Brand colour	#166534
Accent colour	#f0fdf4
Offers	Flat white (55 EGP); Cold brew (60 EGP); Hibiscus iced tea (40 EGP); Cheesecake (75 EGP)

Project 1108: Complete one-page website for Sinai Trekking Club

Theme: Sinai Trekking Club (Saint Catherine) | Level 3 | Files: index.html, styles.css

Brief

Combine everything into a single-page site: skip link, sticky header with anchor navigation, hero, offers grid, about with details, contact form and footer.

Learning goals

- Assemble a full page from components
- Use in-page anchor navigation with scroll-margin-top
- Provide a skip link

Elements and CSS used

HTML elements	CSS features
a.skip, header, nav, main, section, h1-h3, article, details, summary, form, label, input, textarea, button, footer	position: sticky, z-index, scroll-margin-top, grid auto-fit, clamp(), focus styles for skip link

Build guide

1. Write the skeleton with four sections that have ids.
2. Add the sticky header with links to those ids.
3. Add a skip link as the first element in body.
4. Style the hero, grid, about and form.
5. Add scroll-margin-top to h2 so anchors are not hidden by the header.

6. Validate the whole page and test keyboard navigation.

Project 1108: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sinai Trekking Club - Complete site</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <a class="skip" href="#main">Skip to content</a>
  <header class="site-header">
    <a class="logo" href="index.html">Sinai Trekking Club</a>
    <nav aria-label="Main"><ul class="nav">
      <li><a href="#offers">Hikes</a></li><li><a href="#about">About</
a></li><li><a href="#contact">Contact</a></li>
    </ul></nav>
  </header>
  <main id="main">
    <section class="hero">
      <h1>Guided mountain walks for every level</h1>
      <p>Welcome to Sinai Trekking Club in Saint Catherine.</p>
      <a class="btn" href="#offers">Explore</a>
    </section>
    <section id="offers" class="wrap">
      <h2>Our hikes</h2>
      <div class="grid">
        <article class="card"><h3>Mount Sinai sunrise</h3><p>Night
climb, 7 km.</p><p class="price">400 EGP</p></article>
        <article class="card"><h3>Blue Desert loop</h3><p>Easy day
walk.</p><p class="price">250 EGP</p></article>
        <article class="card"><h3>Wadi Gnai</h3><p>Palms and pools.</
p><p class="price">300 EGP</p></article>
        <article class="card"><h3>Three-day traverse</h3><p>Camping
under stars.</p><p class="price">1900 EGP</p></article>
      </div>
    </section>
    <section id="about" class="wrap about">
      <h2>About us</h2>
      <p>Founded by Yara Hamdy. Guided mountain walks for every level.
</p>
      <details><summary>Opening hours</summary><p>Saturday to
Thursday 10:00 to 22:00, Friday 14:00 to 22:00.</p></details>
    </section>
    <section id="contact" class="wrap">
      <h2>Contact</h2>
      <form action="/contact" method="post" class="form">
        <label for="n">Name</label><input id="n" name="name" required>
```

```
        <label for="e">Email</label><input id="e" name="email"
type="email" required>
        <label for="m">Message</label><textarea id="m" name="message"
rows="4" required></textarea>
        <button>Send</button>
      </form>
    </section>
  </main>
  <footer class="site-footer"><p>&copy; 2026 Sinai Trekking Club
&middot; <a href="#main">Back to top</a></p></footer>
</body>
</html>
```

Project 1108: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #92400e; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.skip { position: absolute; left: -999px; } .skip:focus { left: 1rem;
top: 1rem; background: #fff; padding: .5rem; z-index: 100; }
.site-header { position: sticky; top: 0; z-index: 10; display: flex;
flex-wrap: wrap; justify-content: space-between; align-items: center;
gap: .5rem 1rem; padding: .75rem 1rem; background: #fff; border-
bottom: 1px solid var(--line); }
.logo { font-weight: 800; color: var(--brand); text-decoration: none;
}
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { padding: .4rem .8rem; border-radius: 6px; text-decoration:
none; color: var(--ink); }
.nav a:hover { background: var(--accent); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(1.8rem, 5vw, 3rem); }
.btn { display: inline-block; padding: .7rem 1.4rem; border-radius:
999px; background: #fff; color: var(--brand); text-decoration: none;
font-weight: 700; }
.wrap { max-width: 60rem; margin: 0 auto; padding: 3rem 1rem; }
.grid { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(13rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
.price { font-weight: 700; color: var(--brand); }
.about { background: #fafafa; }
details { margin-top: 1rem; } summary { cursor: pointer; font-weight:
600; }
```

```
.form { display: grid; gap: .4rem; max-width: 30rem; }
.form label { font-weight: 600; margin-top: .6rem; }
.form input, .form textarea { padding: .6rem; border: 1px solid #bbb;
border-radius: 8px; font: inherit; }
.form button { justify-self: start; margin-top: 1rem; padding: .7rem
1.4rem; border: 0; border-radius: 999px; background: var(--brand);
color: #fff; font: inherit; }
.site-footer { text-align: center; padding: 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
h2 { scroll-margin-top: 4rem; }
```

Project 1108 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sinai Trekking Club - Complete site</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main"><ul class="nav">	A block of navigation links; aria-label names it for screen readers.
Hikes About<...	A hyperlink; href gives the destination.
<main id="main">	The unique content of this page; exactly one per page.
<section class="hero">	A thematic group of content, normally with its own heading.
Guided mountain walks for every level	The main heading; only one per page.
Welcome to Sinai Trekking Club in Saint Catherine.	A paragraph of text.

Line	What it does
Explore	A link styled as a button; it navigates, so it is a link and not a <button>.
Our hikes	Second-level heading for a section.
	Generic block container for grouping and layout.
<article class="card"><h3>Mount Sinai sunrise</h3><p>Night climb, 7...	A self-contained piece: card, post, product.
<article class="card"><h3>Blue Desert loop</h3><p>Easy day walk.</p...	Third-level heading, inside an h2 section.
<details><summary>Opening hours</summary><p>Saturday to Thursday 10...	Disclosure widget that can be opened and closed.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
<label for="n">Name</label><input id="n" name="name" required>	Text label for a control; for matches the control's id, or the label wraps the control.
<label for="e">Email</label><input id="e" name="email" type="email"...	Email field: validated automatically and shows the @ keyboard on phones.
<label for="m">Message</label><textarea id="m" name="message" rows=...	Multi-line text field.
<button>Send</button>	A clickable button; inside a form it submits by default.

Line	What it does
<footer class="site-footer"><p>© 2026 Sinai Trekking Club &mid...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #92400e;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: #fff;	Background colour or image.
padding: .5rem;	Space inside the element between its border and content.
z-index: 100;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
align-items: center;	Centres items on the cross axis.
gap: .5rem 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-weight: 800;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
border-radius: 6px;	Rounds the corners.
.nav a:hover {	Applies while the pointer is over the element.
text-align: center;	Centres inline content such as text.
font-size: clamp(1.8rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
grid-template-columns: repeat(auto-fit, minmax(13rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	The line around the element: width, style and colour.
} summary { cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-top: 1px solid var(--line);	A top border used as an accent or separator.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.

Check your work

- Skip link appears on first Tab
- Anchor links land below the sticky header
- One h1
- Form fully labelled
- Passes the W3C validator

Exercises

1. Add smooth scrolling with scroll-behavior: smooth (respecting reduced motion).
2. Add an Arabic RTL version.
3. Split into multiple pages with a shared stylesheet.

Theme data for this project

Field	Value
Business	Sinai Trekking Club
Tagline	Guided mountain walks for every level
City	Saint Catherine
Owner	Yara Hamdy
Brand colour	#92400e
Accent colour	#fffbeb
Offers	Mount Sinai sunrise (400 EGP); Blue Desert loop (250 EGP); Wadi Gnai (300 EGP); Three-day traverse (1900 EGP)

Project 1109: Complete one-page website for Horizon Photography

Theme: Horizon Photography (Maadi) | Level 3 | Files: index.html, styles.css

Brief

Combine everything into a single-page site: skip link, sticky header with anchor navigation, hero, offers grid, about with details, contact form and footer.

Learning goals

- Assemble a full page from components
- Use in-page anchor navigation with scroll-margin-top
- Provide a skip link

Elements and CSS used

HTML elements	CSS features
a.skip, header, nav, main, section, h1-h3, article, details, summary, form, label, input, textarea, button, footer	position: sticky, z-index, scroll-margin-top, grid auto-fit, clamp(), focus styles for skip link

Build guide

1. Write the skeleton with four sections that have ids.
2. Add the sticky header with links to those ids.
3. Add a skip link as the first element in body.
4. Style the hero, grid, about and form.
5. Add scroll-margin-top to h2 so anchors are not hidden by the header.

6. Validate the whole page and test keyboard navigation.

Project 1109: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Horizon Photography - Complete site</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <a class="skip" href="#main">Skip to content</a>
  <header class="site-header">
    <a class="logo" href="index.html">Horizon Photography</a>
    <nav aria-label="Main"><ul class="nav">
      <li><a href="#offers">Sessions</a></li><li><a
href="#about">About</a></li><li><a href="#contact">Contact</a></li>
    </ul></nav>
  </header>
  <main id="main">
    <section class="hero">
      <h1>Portraits, weddings and product photography</h1>
      <p>Welcome to Horizon Photography in Maadi.</p>
      <a class="btn" href="#offers">Explore</a>
    </section>
    <section id="offers" class="wrap">
      <h2>Our sessions</h2>
      <div class="grid">
        <article class="card"><h3>Portrait session</h3><p>One hour,
20 edited photos.</p><p class="price">1200 EGP</p></article>
        <article class="card"><h3>Wedding day</h3><p>Full coverage,
two photographers.</p><p class="price">15000 EGP</p></article>
        <article class="card"><h3>Product shoot</h3><p>White
background, 10 items.</p><p class="price">900 EGP</p></article>
        <article class="card"><h3>Family session</h3><p>Outdoor,
golden hour.</p><p class="price">1500 EGP</p></article>
      </div>
    </section>
    <section id="about" class="wrap about">
      <h2>About us</h2>
      <p>Founded by Adham Nabil. Portraits, weddings and product
photography.</p>
      <details><summary>Opening hours</summary><p>Saturday to
Thursday 10:00 to 22:00, Friday 14:00 to 22:00.</p></details>
    </section>
    <section id="contact" class="wrap">
      <h2>Contact</h2>
      <form action="/contact" method="post" class="form">
        <label for="n">Name</label><input id="n" name="name" required>
```

```
        <label for="e">Email</label><input id="e" name="email"
type="email" required>
        <label for="m">Message</label><textarea id="m" name="message"
rows="4" required></textarea>
        <button>Send</button>
      </form>
    </section>
  </main>
  <footer class="site-footer"><p>&copy; 2026 Horizon Photography
&middot; <a href="#main">Back to top</a></p></footer>
</body>
</html>
```

Project 1109: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #111827; --accent: #f3f4f6; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.skip { position: absolute; left: -999px; } .skip:focus { left: 1rem;
top: 1rem; background: #fff; padding: .5rem; z-index: 100; }
.site-header { position: sticky; top: 0; z-index: 10; display: flex;
flex-wrap: wrap; justify-content: space-between; align-items: center;
gap: .5rem 1rem; padding: .75rem 1rem; background: #fff; border-
bottom: 1px solid var(--line); }
.logo { font-weight: 800; color: var(--brand); text-decoration: none;
}
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { padding: .4rem .8rem; border-radius: 6px; text-decoration:
none; color: var(--ink); }
.nav a:hover { background: var(--accent); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(1.8rem, 5vw, 3rem); }
.btn { display: inline-block; padding: .7rem 1.4rem; border-radius:
999px; background: #fff; color: var(--brand); text-decoration: none;
font-weight: 700; }
.wrap { max-width: 60rem; margin: 0 auto; padding: 3rem 1rem; }
.grid { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(13rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
.price { font-weight: 700; color: var(--brand); }
.about { background: #fafafa; }
details { margin-top: 1rem; } summary { cursor: pointer; font-weight:
600; }
```

```
.form { display: grid; gap: .4rem; max-width: 30rem; }
.form label { font-weight: 600; margin-top: .6rem; }
.form input, .form textarea { padding: .6rem; border: 1px solid #bbb;
border-radius: 8px; font: inherit; }
.form button { justify-self: start; margin-top: 1rem; padding: .7rem
1.4rem; border: 0; border-radius: 999px; background: var(--brand);
color: #fff; font: inherit; }
.site-footer { text-align: center; padding: 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
h2 { scroll-margin-top: 4rem; }
```

Project 1109 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Horizon Photography - Complete site</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main"><ul class="nav">	A block of navigation links; aria-label names it for screen readers.
Sessions <a href="#about">About<//...	A hyperlink; href gives the destination.
<main id="main">	The unique content of this page; exactly one per page.
<section class="hero">	A thematic group of content, normally with its own heading.
Portraits, weddings and product photography	The main heading; only one per page.
Welcome to Horizon Photography in Maadi.	A paragraph of text.

Line	What it does
Explore	A link styled as a button; it navigates, so it is a link and not a <button>.
Our sessions	Second-level heading for a section.
	Generic block container for grouping and layout.
<article class="card"><h3>Portrait session</h3><p>One hour, 20 edit...	A self-contained piece: card, post, product.
<article class="card"><h3>Wedding day</h3><p>Full coverage, two pho...	Third-level heading, inside an h2 section.
<details><summary>Opening hours</summary><p>Saturday to Thursday 10...	Disclosure widget that can be opened and closed.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
<label for="n">Name</label><input id="n" name="name" required>	Text label for a control; for matches the control's id, or the label wraps the control.
<label for="e">Email</label><input id="e" name="email" type="email"...	Email field: validated automatically and shows the @ keyboard on phones.
<label for="m">Message</label><textarea id="m" name="message" rows=...	Multi-line text field.
<button>Send</button>	A clickable button; inside a form it submits by default.

Line	What it does
<footer class="site-footer"><p>© 2026 Horizon Photography &mid...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #111827;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: #fff;	Background colour or image.
padding: .5rem;	Space inside the element between its border and content.
z-index: 100;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
align-items: center;	Centres items on the cross axis.
gap: .5rem 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-weight: 800;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
border-radius: 6px;	Rounds the corners.
.nav a:hover {	Applies while the pointer is over the element.
text-align: center;	Centres inline content such as text.
font-size: clamp(1.8rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
grid-template-columns: repeat(auto-fit, minmax(13rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	The line around the element: width, style and colour.
} summary { cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-top: 1px solid var(--line);	A top border used as an accent or separator.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.

Check your work

- Skip link appears on first Tab
- Anchor links land below the sticky header
- One h1
- Form fully labelled
- Passes the W3C validator

Exercises

1. Add smooth scrolling with scroll-behavior: smooth (respecting reduced motion).
2. Add an Arabic RTL version.
3. Split into multiple pages with a shared stylesheet.

Theme data for this project

Field	Value
Business	Horizon Photography
Tagline	Portraits, weddings and product photography
City	Maadi
Owner	Adham Nabil
Brand colour	#111827
Accent colour	#f3f4f6
Offers	Portrait session (1200 EGP); Wedding day (15000 EGP); Product shoot (900 EGP); Family session (1500 EGP)

Project 1110: Complete one-page website for Papyrus Stationery

Theme: Papyrus Stationery (Heliopolis) | Level 3 | Files: index.html, styles.css

Brief

Combine everything into a single-page site: skip link, sticky header with anchor navigation, hero, offers grid, about with details, contact form and footer.

Learning goals

- Assemble a full page from components
- Use in-page anchor navigation with scroll-margin-top
- Provide a skip link

Elements and CSS used

HTML elements	CSS features
a.skip, header, nav, main, section, h1-h3, article, details, summary, form, label, input, textarea, button, footer	position: sticky, z-index, scroll-margin-top, grid auto-fit, clamp(), focus styles for skip link

Build guide

1. Write the skeleton with four sections that have ids.
2. Add the sticky header with links to those ids.
3. Add a skip link as the first element in body.
4. Style the hero, grid, about and form.
5. Add scroll-margin-top to h2 so anchors are not hidden by the header.

6. Validate the whole page and test keyboard navigation.

Project 1110: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Papyrus Stationery - Complete site</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <a class="skip" href="#main">Skip to content</a>
  <header class="site-header">
    <a class="logo" href="index.html">Papyrus Stationery</a>
    <nav aria-label="Main"><ul class="nav">
      <li><a href="#offers">Products</a></li><li><a
href="#about">About</a></li><li><a href="#contact">Contact</a></li>
    </ul></nav>
  </header>
  <main id="main">
    <section class="hero">
      <h1>Notebooks, pens and paper made in Egypt</h1>
      <p>Welcome to Papyrus Stationery in Heliopolis.</p>
      <a class="btn" href="#offers">Explore</a>
    </section>
    <section id="offers" class="wrap">
      <h2>Our products</h2>
      <div class="grid">
        <article class="card"><h3>Dotted notebook</h3><p>A5, 160
pages.</p><p class="price">140 EGP</p></article>
        <article class="card"><h3>Fountain pen</h3><p>Steel nib,
refillable.</p><p class="price">350 EGP</p></article>
        <article class="card"><h3>Washi tape set</h3><p>Six patterns.
</p><p class="price">90 EGP</p></article>
        <article class="card"><h3>Desk planner</h3><p>Weekly, undated.
</p><p class="price">110 EGP</p></article>
      </div>
    </section>
    <section id="about" class="wrap about">
      <h2>About us</h2>
      <p>Founded by Dina Fathy. Notebooks, pens and paper made in
Egypt.</p>
      <details><summary>Opening hours</summary><p>Saturday to
Thursday 10:00 to 22:00, Friday 14:00 to 22:00.</p></details>
    </section>
    <section id="contact" class="wrap">
      <h2>Contact</h2>
      <form action="/contact" method="post" class="form">
        <label for="n">Name</label><input id="n" name="name" required>
```

```
        <label for="e">Email</label><input id="e" name="email"
type="email" required>
        <label for="m">Message</label><textarea id="m" name="message"
rows="4" required></textarea>
        <button>Send</button>
      </form>
    </section>
  </main>
  <footer class="site-footer"><p>&copy; 2026 Papyrus Stationery
&middot; <a href="#main">Back to top</a></p></footer>
</body>
</html>
```

Project 1110: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #be185d; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.skip { position: absolute; left: -999px; } .skip:focus { left: 1rem;
top: 1rem; background: #fff; padding: .5rem; z-index: 100; }
.site-header { position: sticky; top: 0; z-index: 10; display: flex;
flex-wrap: wrap; justify-content: space-between; align-items: center;
gap: .5rem 1rem; padding: .75rem 1rem; background: #fff; border-
bottom: 1px solid var(--line); }
.logo { font-weight: 800; color: var(--brand); text-decoration: none;
}
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { padding: .4rem .8rem; border-radius: 6px; text-decoration:
none; color: var(--ink); }
.nav a:hover { background: var(--accent); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(1.8rem, 5vw, 3rem); }
.btn { display: inline-block; padding: .7rem 1.4rem; border-radius:
999px; background: #fff; color: var(--brand); text-decoration: none;
font-weight: 700; }
.wrap { max-width: 60rem; margin: 0 auto; padding: 3rem 1rem; }
.grid { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(13rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
.price { font-weight: 700; color: var(--brand); }
.about { background: #fafafa; }
details { margin-top: 1rem; } summary { cursor: pointer; font-weight:
600; }
```

```
.form { display: grid; gap: .4rem; max-width: 30rem; }
.form label { font-weight: 600; margin-top: .6rem; }
.form input, .form textarea { padding: .6rem; border: 1px solid #bbb;
border-radius: 8px; font: inherit; }
.form button { justify-self: start; margin-top: 1rem; padding: .7rem
1.4rem; border: 0; border-radius: 999px; background: var(--brand);
color: #fff; font: inherit; }
.site-footer { text-align: center; padding: 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
h2 { scroll-margin-top: 4rem; }
```

Project 1110 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Papyrus Stationery - Complete site</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main"><ul class="nav">	A block of navigation links; aria-label names it for screen readers.
Products <a href="#about">About<//...	A hyperlink; href gives the destination.
<main id="main">	The unique content of this page; exactly one per page.
<section class="hero">	A thematic group of content, normally with its own heading.
Notebooks, pens and paper made in Egypt	The main heading; only one per page.
Welcome to Papyrus Stationery in Heliopolis.	A paragraph of text.

Line	What it does
Explore	A link styled as a button; it navigates, so it is a link and not a <button>.
Our products	Second-level heading for a section.
	Generic block container for grouping and layout.
<article class="card"> Dotted notebook A5, 160 pages. ...	A self-contained piece: card, post, product.
<article class="card"> Fountain pen Steel nib, refillable...	Third-level heading, inside an h2 section.
<details><summary>Opening hours</summary> Saturday to Thursday 10...	Disclosure widget that can be opened and closed.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
<label for="n">Name</label><input id="n" name="name" required>	Text label for a control; for matches the control's id, or the label wraps the control.
<label for="e">Email</label><input id="e" name="email" type="email"...	Email field: validated automatically and shows the @ keyboard on phones.
<label for="m">Message</label><textarea id="m" name="message" rows=...	Multi-line text field.
<button>Send</button>	A clickable button; inside a form it submits by default.

Line	What it does
<footer class="site-footer"><p>© 2026 Papyrus Stationery &midd...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #be185d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: #fff;	Background colour or image.
padding: .5rem;	Space inside the element between its border and content.
z-index: 100;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
align-items: center;	Centres items on the cross axis.
gap: .5rem 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-weight: 800;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
border-radius: 6px;	Rounds the corners.
.nav a:hover {	Applies while the pointer is over the element.
text-align: center;	Centres inline content such as text.
font-size: clamp(1.8rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
grid-template-columns: repeat(auto-fit, minmax(13rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	The line around the element: width, style and colour.
} summary { cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-top: 1px solid var(--line);	A top border used as an accent or separator.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.

Check your work

- Skip link appears on first Tab
- Anchor links land below the sticky header
- One h1
- Form fully labelled
- Passes the W3C validator

Exercises

1. Add smooth scrolling with scroll-behavior: smooth (respecting reduced motion).
2. Add an Arabic RTL version.
3. Split into multiple pages with a shared stylesheet.

Theme data for this project

Field	Value
Business	Papyrus Stationery
Tagline	Notebooks, pens and paper made in Egypt
City	Heliopolis
Owner	Dina Fathy
Brand colour	#be185d
Accent colour	#fdf2f8
Offers	Dotted notebook (140 EGP); Fountain pen (350 EGP); Washi tape set (90 EGP); Desk planner (110 EGP)

Project 1111: Complete one-page website for Oasis Plant Nursery

Theme: Oasis Plant Nursery (Sheikh Zayed) | Level 3 | Files: index.html, styles.css

Brief

Combine everything into a single-page site: skip link, sticky header with anchor navigation, hero, offers grid, about with details, contact form and footer.

Learning goals

- Assemble a full page from components
- Use in-page anchor navigation with scroll-margin-top
- Provide a skip link

Elements and CSS used

HTML elements	CSS features
a.skip, header, nav, main, section, h1-h3, article, details, summary, form, label, input, textarea, button, footer	position: sticky, z-index, scroll-margin-top, grid auto-fit, clamp(), focus styles for skip link

Build guide

1. Write the skeleton with four sections that have ids.
2. Add the sticky header with links to those ids.
3. Add a skip link as the first element in body.
4. Style the hero, grid, about and form.
5. Add scroll-margin-top to h2 so anchors are not hidden by the header.

6. Validate the whole page and test keyboard navigation.

Project 1111: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Oasis Plant Nursery - Complete site</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <a class="skip" href="#main">Skip to content</a>
  <header class="site-header">
    <a class="logo" href="index.html">Oasis Plant Nursery</a>
    <nav aria-label="Main"><ul class="nav">
      <li><a href="#offers">Plants</a></li><li><a
href="#about">About</a></li><li><a href="#contact">Contact</a></li>
    </ul></nav>
  </header>
  <main id="main">
    <section class="hero">
      <h1>Indoor plants and gardening advice</h1>
      <p>Welcome to Oasis Plant Nursery in Sheikh Zayed.</p>
      <a class="btn" href="#offers">Explore</a>
    </section>
    <section id="offers" class="wrap">
      <h2>Our plants</h2>
      <div class="grid">
        <article class="card"><h3>Monstera</h3><p>Large leaves, easy
care.</p><p class="price">250 EGP</p></article>
        <article class="card"><h3>Snake plant</h3><p>Survives
anything.</p><p class="price">120 EGP</p></article>
        <article class="card"><h3>Basil pot</h3><p>Kitchen herb.</
p><p class="price">45 EGP</p></article>
        <article class="card"><h3>Olive tree</h3><p>Balcony sized.</
p><p class="price">600 EGP</p></article>
      </div>
    </section>
    <section id="about" class="wrap about">
      <h2>About us</h2>
      <p>Founded by Hossam Ali. Indoor plants and gardening advice.</
p>
      <details><summary>Opening hours</summary><p>Saturday to
Thursday 10:00 to 22:00, Friday 14:00 to 22:00.</p></details>
    </section>
    <section id="contact" class="wrap">
      <h2>Contact</h2>
      <form action="/contact" method="post" class="form">
        <label for="n">Name</label><input id="n" name="name" required>
```

```
        <label for="e">Email</label><input id="e" name="email"
type="email" required>
        <label for="m">Message</label><textarea id="m" name="message"
rows="4" required></textarea>
        <button>Send</button>
      </form>
    </section>
  </main>
  <footer class="site-footer"><p>&copy; 2026 Oasis Plant Nursery
&middot; <a href="#main">Back to top</a></p></footer>
</body>
</html>
```

Project 1111: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #15803d; --accent: #f7fee7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.skip { position: absolute; left: -999px; } .skip:focus { left: 1rem;
top: 1rem; background: #fff; padding: .5rem; z-index: 100; }
.site-header { position: sticky; top: 0; z-index: 10; display: flex;
flex-wrap: wrap; justify-content: space-between; align-items: center;
gap: .5rem 1rem; padding: .75rem 1rem; background: #fff; border-
bottom: 1px solid var(--line); }
.logo { font-weight: 800; color: var(--brand); text-decoration: none;
}
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { padding: .4rem .8rem; border-radius: 6px; text-decoration:
none; color: var(--ink); }
.nav a:hover { background: var(--accent); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(1.8rem, 5vw, 3rem); }
.btn { display: inline-block; padding: .7rem 1.4rem; border-radius:
999px; background: #fff; color: var(--brand); text-decoration: none;
font-weight: 700; }
.wrap { max-width: 60rem; margin: 0 auto; padding: 3rem 1rem; }
.grid { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(13rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
.price { font-weight: 700; color: var(--brand); }
.about { background: #fafafa; }
details { margin-top: 1rem; } summary { cursor: pointer; font-weight:
600; }
```

```
.form { display: grid; gap: .4rem; max-width: 30rem; }
.form label { font-weight: 600; margin-top: .6rem; }
.form input, .form textarea { padding: .6rem; border: 1px solid #bbb;
border-radius: 8px; font: inherit; }
.form button { justify-self: start; margin-top: 1rem; padding: .7rem
1.4rem; border: 0; border-radius: 999px; background: var(--brand);
color: #fff; font: inherit; }
.site-footer { text-align: center; padding: 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
h2 { scroll-margin-top: 4rem; }
```

Project 1111 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Oasis Plant Nursery - Complete site</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main"><ul class="nav">	A block of navigation links; aria-label names it for screen readers.
Plants About...	A hyperlink; href gives the destination.
<main id="main">	The unique content of this page; exactly one per page.
<section class="hero">	A thematic group of content, normally with its own heading.
Indoor plants and gardening advice	The main heading; only one per page.
Welcome to Oasis Plant Nursery in Sheikh Zayed.	A paragraph of text.

Line	What it does
Explore	A link styled as a button; it navigates, so it is a link and not a <button>.
Our plants	Second-level heading for a section.
	Generic block container for grouping and layout.
<article class="card"> Monstera Large leaves, easy care.<...	A self-contained piece: card, post, product.
<article class="card"> Snake plant Survives anything. ...	Third-level heading, inside an h2 section.
<details><summary>Opening hours</summary> Saturday to Thursday 10...	Disclosure widget that can be opened and closed.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
<label for="n">Name</label><input id="n" name="name" required>	Text label for a control; for matches the control's id, or the label wraps the control.
<label for="e">Email</label><input id="e" name="email" type="email"...	Email field: validated automatically and shows the @ keyboard on phones.
<label for="m">Message</label><textarea id="m" name="message" rows=...	Multi-line text field.
<button>Send</button>	A clickable button; inside a form it submits by default.

Line	What it does
<footer class="site-footer"><p>© 2026 Oasis Plant Nursery &mid...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #15803d;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: #fff;	Background colour or image.
padding: .5rem;	Space inside the element between its border and content.
z-index: 100;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
align-items: center;	Centres items on the cross axis.
gap: .5rem 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-weight: 800;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
border-radius: 6px;	Rounds the corners.
.nav a:hover {	Applies while the pointer is over the element.
text-align: center;	Centres inline content such as text.
font-size: clamp(1.8rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
grid-template-columns: repeat(auto-fit, minmax(13rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	The line around the element: width, style and colour.
} summary { cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-top: 1px solid var(--line);	A top border used as an accent or separator.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.

Check your work

- Skip link appears on first Tab
- Anchor links land below the sticky header
- One h1
- Form fully labelled
- Passes the W3C validator

Exercises

1. Add smooth scrolling with scroll-behavior: smooth (respecting reduced motion).
2. Add an Arabic RTL version.
3. Split into multiple pages with a shared stylesheet.

Theme data for this project

Field	Value
Business	Oasis Plant Nursery
Tagline	Indoor plants and gardening advice
City	Sheikh Zayed
Owner	Hossam Ali
Brand colour	#15803d
Accent colour	#f7fee7
Offers	Monstera (250 EGP); Snake plant (120 EGP); Basil pot (45 EGP); Olive tree (600 EGP)

Project 1112: Complete one-page website for Cedar Furniture

Theme: Cedar Furniture (Damietta) | Level 3 | Files: index.html, styles.css

Brief

Combine everything into a single-page site: skip link, sticky header with anchor navigation, hero, offers grid, about with details, contact form and footer.

Learning goals

- Assemble a full page from components
- Use in-page anchor navigation with scroll-margin-top
- Provide a skip link

Elements and CSS used

HTML elements	CSS features
a.skip, header, nav, main, section, h1-h3, article, details, summary, form, label, input, textarea, button, footer	position: sticky, z-index, scroll-margin-top, grid auto-fit, clamp(), focus styles for skip link

Build guide

1. Write the skeleton with four sections that have ids.
2. Add the sticky header with links to those ids.
3. Add a skip link as the first element in body.
4. Style the hero, grid, about and form.
5. Add scroll-margin-top to h2 so anchors are not hidden by the header.

6. Validate the whole page and test keyboard navigation.

Project 1112: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cedar Furniture - Complete site</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <a class="skip" href="#main">Skip to content</a>
  <header class="site-header">
    <a class="logo" href="index.html">Cedar Furniture</a>
    <nav aria-label="Main"><ul class="nav">
      <li><a href="#offers">Pieces</a></li><li><a
href="#about">About</a></li><li><a href="#contact">Contact</a></li>
    </ul></nav>
  </header>
  <main id="main">
    <section class="hero">
      <h1>Solid wood furniture made to order</h1>
      <p>Welcome to Cedar Furniture in Damietta.</p>
      <a class="btn" href="#offers">Explore</a>
    </section>
    <section id="offers" class="wrap">
      <h2>Our pieces</h2>
      <div class="grid">
        <article class="card"><h3>Oak dining table</h3><p>Seats six.</
p><p class="price">9500 EGP</p></article>
        <article class="card"><h3>Bookshelf</h3><p>Five shelves,
walnut.</p><p class="price">4200 EGP</p></article>
        <article class="card"><h3>Bedside table</h3><p>One drawer.</
p><p class="price">1500 EGP</p></article>
        <article class="card"><h3>Coffee table</h3><p>Round, ash wood.
</p><p class="price">2800 EGP</p></article>
      </div>
    </section>
    <section id="about" class="wrap about">
      <h2>About us</h2>
      <p>Founded by Tarek Lotfy. Solid wood furniture made to order.</
p>
      <details><summary>Opening hours</summary><p>Saturday to
Thursday 10:00 to 22:00, Friday 14:00 to 22:00.</p></details>
    </section>
    <section id="contact" class="wrap">
      <h2>Contact</h2>
      <form action="/contact" method="post" class="form">
        <label for="n">Name</label><input id="n" name="name" required>
```

```
        <label for="e">Email</label><input id="e" name="email"
type="email" required>
        <label for="m">Message</label><textarea id="m" name="message"
rows="4" required></textarea>
        <button>Send</button>
      </form>
    </section>
  </main>
  <footer class="site-footer"><p>&copy; 2026 Cedar Furniture &middot;
<a href="#main">Back to top</a></p></footer>
</body>
</html>
```

Project 1112: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #78350f; --accent: #fef3c7; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.skip { position: absolute; left: -999px; } .skip:focus { left: 1rem;
top: 1rem; background: #fff; padding: .5rem; z-index: 100; }
.site-header { position: sticky; top: 0; z-index: 10; display: flex;
flex-wrap: wrap; justify-content: space-between; align-items: center;
gap: .5rem 1rem; padding: .75rem 1rem; background: #fff; border-
bottom: 1px solid var(--line); }
.logo { font-weight: 800; color: var(--brand); text-decoration: none;
}
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { padding: .4rem .8rem; border-radius: 6px; text-decoration:
none; color: var(--ink); }
.nav a:hover { background: var(--accent); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(1.8rem, 5vw, 3rem); }
.btn { display: inline-block; padding: .7rem 1.4rem; border-radius:
999px; background: #fff; color: var(--brand); text-decoration: none;
font-weight: 700; }
.wrap { max-width: 60rem; margin: 0 auto; padding: 3rem 1rem; }
.grid { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(13rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
.price { font-weight: 700; color: var(--brand); }
.about { background: #fafafa; }
details { margin-top: 1rem; } summary { cursor: pointer; font-weight:
600; }
```

```
.form { display: grid; gap: .4rem; max-width: 30rem; }
.form label { font-weight: 600; margin-top: .6rem; }
.form input, .form textarea { padding: .6rem; border: 1px solid #bbb;
border-radius: 8px; font: inherit; }
.form button { justify-self: start; margin-top: 1rem; padding: .7rem
1.4rem; border: 0; border-radius: 999px; background: var(--brand);
color: #fff; font: inherit; }
.site-footer { text-align: center; padding: 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
h2 { scroll-margin-top: 4rem; }
```

Project 1112 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cedar Furniture - Complete site</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main"><ul class="nav">	A block of navigation links; aria-label names it for screen readers.
Pieces About...	A hyperlink; href gives the destination.
<main id="main">	The unique content of this page; exactly one per page.
<section class="hero">	A thematic group of content, normally with its own heading.
Solid wood furniture made to order	The main heading; only one per page.
Welcome to Cedar Furniture in Damietta.	A paragraph of text.

Line	What it does
Explore	A link styled as a button; it navigates, so it is a link and not a <button>.
Our pieces	Second-level heading for a section.
	Generic block container for grouping and layout.
<article class="card"> Oak dining table Seats six. <p ...	A self-contained piece: card, post, product.
<article class="card"> Bookshelf Five shelves, walnut.</p...	Third-level heading, inside an h2 section.
<details><summary>Opening hours</summary> Saturday to Thursday 10...	Disclosure widget that can be opened and closed.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
<label for="n">Name</label><input id="n" name="name" required>	Text label for a control; for matches the control's id, or the label wraps the control.
<label for="e">Email</label><input id="e" name="email" type="email"...	Email field: validated automatically and shows the @ keyboard on phones.
<label for="m">Message</label><textarea id="m" name="message" rows=...	Multi-line text field.
<button>Send</button>	A clickable button; inside a form it submits by default.

Line	What it does
<footer class="site-footer"><p>© 2026 Cedar Furniture ·...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #78350f;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: #fff;	Background colour or image.
padding: .5rem;	Space inside the element between its border and content.
z-index: 100;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
align-items: center;	Centres items on the cross axis.
gap: .5rem 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-weight: 800;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
border-radius: 6px;	Rounds the corners.
.nav a:hover {	Applies while the pointer is over the element.
text-align: center;	Centres inline content such as text.
font-size: clamp(1.8rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
grid-template-columns: repeat(auto-fit, minmax(13rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	The line around the element: width, style and colour.
} summary { cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-top: 1px solid var(--line);	A top border used as an accent or separator.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.

Check your work

- Skip link appears on first Tab
- Anchor links land below the sticky header
- One h1
- Form fully labelled
- Passes the W3C validator

Exercises

1. Add smooth scrolling with scroll-behavior: smooth (respecting reduced motion).
2. Add an Arabic RTL version.
3. Split into multiple pages with a shared stylesheet.

Theme data for this project

Field	Value
Business	Cedar Furniture
Tagline	Solid wood furniture made to order
City	Damietta
Owner	Tarek Lotfy
Brand colour	#78350f
Accent colour	#fef3c7
Offers	Oak dining table (9500 EGP); Bookshelf (4200 EGP); Bedside table (1500 EGP); Coffee table (2800 EGP)

Project 1113: Complete one-page website for Byte Repair

Theme: Byte Repair (Nasr City) | Level 3 | Files: index.html, styles.css

Brief

Combine everything into a single-page site: skip link, sticky header with anchor navigation, hero, offers grid, about with details, contact form and footer.

Learning goals

- Assemble a full page from components
- Use in-page anchor navigation with scroll-margin-top
- Provide a skip link

Elements and CSS used

HTML elements	CSS features
a.skip, header, nav, main, section, h1-h3, article, details, summary, form, label, input, textarea, button, footer	position: sticky, z-index, scroll-margin-top, grid auto-fit, clamp(), focus styles for skip link

Build guide

1. Write the skeleton with four sections that have ids.
2. Add the sticky header with links to those ids.
3. Add a skip link as the first element in body.
4. Style the hero, grid, about and form.
5. Add scroll-margin-top to h2 so anchors are not hidden by the header.

6. Validate the whole page and test keyboard navigation.

Project 1113: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Byte Repair - Complete site</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <a class="skip" href="#main">Skip to content</a>
  <header class="site-header">
    <a class="logo" href="index.html">Byte Repair</a>
    <nav aria-label="Main"><ul class="nav">
      <li><a href="#offers">Repairs</a></li><li><a
href="#about">About</a></li><li><a href="#contact">Contact</a></li>
    </ul></nav>
  </header>
  <main id="main">
    <section class="hero">
      <h1>Phone and laptop repairs while you wait</h1>
      <p>Welcome to Byte Repair in Nasr City.</p>
      <a class="btn" href="#offers">Explore</a>
    </section>
    <section id="offers" class="wrap">
      <h2>Our repairs</h2>
      <div class="grid">
        <article class="card"><h3>Screen replacement</h3><p>Most
phones, 1 hour.</p><p class="price">From 800 EGP</p></article>
        <article class="card"><h3>Battery swap</h3><p>Original cells.
</p><p class="price">From 500 EGP</p></article>
        <article class="card"><h3>Laptop cleaning</h3><p>Fans and
thermal paste.</p><p class="price">350 EGP</p></article>
        <article class="card"><h3>Data recovery</h3><p>Drives and
cards.</p><p class="price">From 1200 EGP</p></article>
      </div>
    </section>
    <section id="about" class="wrap about">
      <h2>About us</h2>
      <p>Founded by Mostafa Gamal. Phone and laptop repairs while you
wait.</p>
      <details><summary>Opening hours</summary><p>Saturday to
Thursday 10:00 to 22:00, Friday 14:00 to 22:00.</p></details>
    </section>
    <section id="contact" class="wrap">
      <h2>Contact</h2>
      <form action="/contact" method="post" class="form">
        <label for="n">Name</label><input id="n" name="name" required>
```

```
        <label for="e">Email</label><input id="e" name="email"
type="email" required>
        <label for="m">Message</label><textarea id="m" name="message"
rows="4" required></textarea>
        <button>Send</button>
      </form>
    </section>
  </main>
  <footer class="site-footer"><p>&copy; 2026 Byte Repair &middot; <a
href="#main">Back to top</a></p></footer>
</body>
</html>
```

Project 1113: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0891b2; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.skip { position: absolute; left: -999px; } .skip:focus { left: 1rem;
top: 1rem; background: #fff; padding: .5rem; z-index: 100; }
.site-header { position: sticky; top: 0; z-index: 10; display: flex;
flex-wrap: wrap; justify-content: space-between; align-items: center;
gap: .5rem 1rem; padding: .75rem 1rem; background: #fff; border-
bottom: 1px solid var(--line); }
.logo { font-weight: 800; color: var(--brand); text-decoration: none;
}
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { padding: .4rem .8rem; border-radius: 6px; text-decoration:
none; color: var(--ink); }
.nav a:hover { background: var(--accent); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(1.8rem, 5vw, 3rem); }
.btn { display: inline-block; padding: .7rem 1.4rem; border-radius:
999px; background: #fff; color: var(--brand); text-decoration: none;
font-weight: 700; }
.wrap { max-width: 60rem; margin: 0 auto; padding: 3rem 1rem; }
.grid { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(13rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
.price { font-weight: 700; color: var(--brand); }
.about { background: #fafafa; }
details { margin-top: 1rem; } summary { cursor: pointer; font-weight:
600; }
```

```
.form { display: grid; gap: .4rem; max-width: 30rem; }
.form label { font-weight: 600; margin-top: .6rem; }
.form input, .form textarea { padding: .6rem; border: 1px solid #bbb;
border-radius: 8px; font: inherit; }
.form button { justify-self: start; margin-top: 1rem; padding: .7rem
1.4rem; border: 0; border-radius: 999px; background: var(--brand);
color: #fff; font: inherit; }
.site-footer { text-align: center; padding: 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
h2 { scroll-margin-top: 4rem; }
```

Project 1113 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Byte Repair - Complete site</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main"><ul class="nav">	A block of navigation links; aria-label names it for screen readers.
Repairs <a href="#about">About</a...	A hyperlink; href gives the destination.
<main id="main">	The unique content of this page; exactly one per page.
<section class="hero">	A thematic group of content, normally with its own heading.
Phone and laptop repairs while you wait	The main heading; only one per page.
Welcome to Byte Repair in Nasr City.	A paragraph of text.

Line	What it does
Explore	A link styled as a button; it navigates, so it is a link and not a <button>.
Our repairs	Second-level heading for a section.
	Generic block container for grouping and layout.
<article class="card"> Screen replacement Most phones, 1 ...	A self-contained piece: card, post, product.
<article class="card"> Battery swap Original cells. <p...	Third-level heading, inside an h2 section.
<details><summary>Opening hours</summary> Saturday to Thursday 10...	Disclosure widget that can be opened and closed.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
<label for="n">Name</label><input id="n" name="name" required>	Text label for a control; for matches the control's id, or the label wraps the control.
<label for="e">Email</label><input id="e" name="email" type="email"...	Email field: validated automatically and shows the @ keyboard on phones.
<label for="m">Message</label><textarea id="m" name="message" rows=...	Multi-line text field.
<button>Send</button>	A clickable button; inside a form it submits by default.

Line	What it does
<footer class="site-footer"><p>© 2026 Byte Repair · <a ...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0891b2;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: #fff;	Background colour or image.
padding: .5rem;	Space inside the element between its border and content.
z-index: 100;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
align-items: center;	Centres items on the cross axis.
gap: .5rem 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-weight: 800;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
border-radius: 6px;	Rounds the corners.
.nav a:hover {	Applies while the pointer is over the element.
text-align: center;	Centres inline content such as text.
font-size: clamp(1.8rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
grid-template-columns: repeat(auto-fit, minmax(13rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	The line around the element: width, style and colour.
} summary { cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-top: 1px solid var(--line);	A top border used as an accent or separator.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.

Check your work

- Skip link appears on first Tab
- Anchor links land below the sticky header
- One h1
- Form fully labelled
- Passes the W3C validator

Exercises

1. Add smooth scrolling with scroll-behavior: smooth (respecting reduced motion).
2. Add an Arabic RTL version.
3. Split into multiple pages with a shared stylesheet.

Theme data for this project

Field	Value
Business	Byte Repair
Tagline	Phone and laptop repairs while you wait
City	Nasr City
Owner	Mostafa Gamal
Brand colour	#0891b2
Accent colour	#ecfeff
Offers	Screen replacement (From 800 EGP); Battery swap (From 500 EGP); Laptop cleaning (350 EGP); Data recovery (From 1200 EGP)

Project 1114: Complete one-page website for Sahara Pet Care

Theme: Sahara Pet Care (New Cairo) | Level 3 | Files: index.html, styles.css

Brief

Combine everything into a single-page site: skip link, sticky header with anchor navigation, hero, offers grid, about with details, contact form and footer.

Learning goals

- Assemble a full page from components
- Use in-page anchor navigation with scroll-margin-top
- Provide a skip link

Elements and CSS used

HTML elements	CSS features
a.skip, header, nav, main, section, h1-h3, article, details, summary, form, label, input, textarea, button, footer	position: sticky, z-index, scroll-margin-top, grid auto-fit, clamp(), focus styles for skip link

Build guide

1. Write the skeleton with four sections that have ids.
2. Add the sticky header with links to those ids.
3. Add a skip link as the first element in body.
4. Style the hero, grid, about and form.
5. Add scroll-margin-top to h2 so anchors are not hidden by the header.

6. Validate the whole page and test keyboard navigation.

Project 1114: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Sahara Pet Care - Complete site</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <a class="skip" href="#main">Skip to content</a>
  <header class="site-header">
    <a class="logo" href="index.html">Sahara Pet Care</a>
    <nav aria-label="Main"><ul class="nav">
      <li><a href="#offers">Services</a></li><li><a
href="#about">About</a></li><li><a href="#contact">Contact</a></li>
    </ul></nav>
  </header>
  <main id="main">
    <section class="hero">
      <h1>Grooming, boarding and vet visits</h1>
      <p>Welcome to Sahara Pet Care in New Cairo.</p>
      <a class="btn" href="#offers">Explore</a>
    </section>
    <section id="offers" class="wrap">
      <h2>Our services</h2>
      <div class="grid">
        <article class="card"><h3>Full grooming</h3><p>Bath, cut and
nails.</p><p class="price">400 EGP</p></article>
        <article class="card"><h3>Day boarding</h3><p>Play and rest.</
p><p class="price">250 EGP</p></article>
        <article class="card"><h3>Vaccination</h3><p>Annual boosters.
</p><p class="price">300 EGP</p></article>
        <article class="card"><h3>Dog walking</h3><p>30 minutes.</
p><p class="price">100 EGP</p></article>
      </div>
    </section>
    <section id="about" class="wrap about">
      <h2>About us</h2>
      <p>Founded by Rana Ibrahim. Grooming, boarding and vet visits.</
p>
      <details><summary>Opening hours</summary><p>Saturday to
Thursday 10:00 to 22:00, Friday 14:00 to 22:00.</p></details>
    </section>
    <section id="contact" class="wrap">
      <h2>Contact</h2>
      <form action="/contact" method="post" class="form">
        <label for="n">Name</label><input id="n" name="name" required>
```

```
        <label for="e">Email</label><input id="e" name="email"
type="email" required>
        <label for="m">Message</label><textarea id="m" name="message"
rows="4" required></textarea>
        <button>Send</button>
      </form>
    </section>
  </main>
  <footer class="site-footer"><p>&copy; 2026 Sahara Pet Care &middot;
<a href="#main">Back to top</a></p></footer>
</body>
</html>
```

Project 1114: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #c2410c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.skip { position: absolute; left: -999px; } .skip:focus { left: 1rem;
top: 1rem; background: #fff; padding: .5rem; z-index: 100; }
.site-header { position: sticky; top: 0; z-index: 10; display: flex;
flex-wrap: wrap; justify-content: space-between; align-items: center;
gap: .5rem 1rem; padding: .75rem 1rem; background: #fff; border-
bottom: 1px solid var(--line); }
.logo { font-weight: 800; color: var(--brand); text-decoration: none;
}
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { padding: .4rem .8rem; border-radius: 6px; text-decoration:
none; color: var(--ink); }
.nav a:hover { background: var(--accent); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(1.8rem, 5vw, 3rem); }
.btn { display: inline-block; padding: .7rem 1.4rem; border-radius:
999px; background: #fff; color: var(--brand); text-decoration: none;
font-weight: 700; }
.wrap { max-width: 60rem; margin: 0 auto; padding: 3rem 1rem; }
.grid { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(13rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
.price { font-weight: 700; color: var(--brand); }
.about { background: #fafafa; }
details { margin-top: 1rem; } summary { cursor: pointer; font-weight:
600; }
```

```
.form { display: grid; gap: .4rem; max-width: 30rem; }
.form label { font-weight: 600; margin-top: .6rem; }
.form input, .form textarea { padding: .6rem; border: 1px solid #bbb;
border-radius: 8px; font: inherit; }
.form button { justify-self: start; margin-top: 1rem; padding: .7rem
1.4rem; border: 0; border-radius: 999px; background: var(--brand);
color: #fff; font: inherit; }
.site-footer { text-align: center; padding: 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
h2 { scroll-margin-top: 4rem; }
```

Project 1114 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Sahara Pet Care - Complete site</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main"><ul class="nav">	A block of navigation links; aria-label names it for screen readers.
Services <a href="#about">About<//...	A hyperlink; href gives the destination.
<main id="main">	The unique content of this page; exactly one per page.
<section class="hero">	A thematic group of content, normally with its own heading.
Grooming, boarding and vet visits	The main heading; only one per page.
Welcome to Sahara Pet Care in New Cairo.	A paragraph of text.

Line	What it does
Explore	A link styled as a button; it navigates, so it is a link and not a <button>.
Our services	Second-level heading for a section.
	Generic block container for grouping and layout.
<article class="card"> Full grooming Bath, cut and nails....	A self-contained piece: card, post, product.
<article class="card"> Day boarding Play and rest. <p ...	Third-level heading, inside an h2 section.
<details><summary>Opening hours</summary> Saturday to Thursday 10...	Disclosure widget that can be opened and closed.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
<label for="n">Name</label><input id="n" name="name" required>	Text label for a control; for matches the control's id, or the label wraps the control.
<label for="e">Email</label><input id="e" name="email" type="email"...	Email field: validated automatically and shows the @ keyboard on phones.
<label for="m">Message</label><textarea id="m" name="message" rows=...	Multi-line text field.
<button>Send</button>	A clickable button; inside a form it submits by default.

Line	What it does
<footer class="site-footer"><p>© 2026 Sahara Pet Care ·...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #c2410c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: #fff;	Background colour or image.
padding: .5rem;	Space inside the element between its border and content.
z-index: 100;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
align-items: center;	Centres items on the cross axis.
gap: .5rem 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-weight: 800;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
border-radius: 6px;	Rounds the corners.
.nav a:hover {	Applies while the pointer is over the element.
text-align: center;	Centres inline content such as text.
font-size: clamp(1.8rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
grid-template-columns: repeat(auto-fit, minmax(13rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	The line around the element: width, style and colour.
} summary { cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-top: 1px solid var(--line);	A top border used as an accent or separator.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.

Check your work

- Skip link appears on first Tab
- Anchor links land below the sticky header
- One h1
- Form fully labelled
- Passes the W3C validator

Exercises

1. Add smooth scrolling with scroll-behavior: smooth (respecting reduced motion).
2. Add an Arabic RTL version.
3. Split into multiple pages with a shared stylesheet.

Theme data for this project

Field	Value
Business	Sahara Pet Care
Tagline	Grooming, boarding and vet visits
City	New Cairo
Owner	Rana Ibrahim
Brand colour	#c2410c
Accent colour	#fff7ed
Offers	Full grooming (400 EGP); Day boarding (250 EGP); Vaccination (300 EGP); Dog walking (100 EGP)

Project 1115: Complete one-page website for Alexandria Sailing School

Theme: Alexandria Sailing School (Alexandria) | Level 3 | Files: index.html, styles.css

Brief

Combine everything into a single-page site: skip link, sticky header with anchor navigation, hero, offers grid, about with details, contact form and footer.

Learning goals

- Assemble a full page from components
- Use in-page anchor navigation with scroll-margin-top
- Provide a skip link

Elements and CSS used

HTML elements	CSS features
a.skip, header, nav, main, section, h1-h3, article, details, summary, form, label, input, textarea, button, footer	position: sticky, z-index, scroll-margin-top, grid auto-fit, clamp(), focus styles for skip link

Build guide

1. Write the skeleton with four sections that have ids.
2. Add the sticky header with links to those ids.
3. Add a skip link as the first element in body.
4. Style the hero, grid, about and form.
5. Add scroll-margin-top to h2 so anchors are not hidden by the header.

6. Validate the whole page and test keyboard navigation.

Project 1115: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Alexandria Sailing School - Complete site</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <a class="skip" href="#main">Skip to content</a>
  <header class="site-header">
    <a class="logo" href="index.html">Alexandria Sailing School</a>
    <nav aria-label="Main"><ul class="nav">
      <li><a href="#offers">Lessons</a></li><li><a
href="#about">About</a></li><li><a href="#contact">Contact</a></li>
    </ul></nav>
  </header>
  <main id="main">
    <section class="hero">
      <h1>Learn to sail on the Mediterranean</h1>
      <p>Welcome to Alexandria Sailing School in Alexandria.</p>
      <a class="btn" href="#offers">Explore</a>
    </section>
    <section id="offers" class="wrap">
      <h2>Our lessons</h2>
      <div class="grid">
        <article class="card"><h3>Taster session</h3><p>Two hours on
the water.</p><p class="price">500 EGP</p></article>
        <article class="card"><h3>Beginner course</h3><p>Five
sessions.</p><p class="price">2200 EGP</p></article>
        <article class="card"><h3>Racing clinic</h3><p>Tactics and
trim.</p><p class="price">1800 EGP</p></article>
        <article class="card"><h3>Private lesson</h3><p>One to one.</
p><p class="price">900 EGP</p></article>
      </div>
    </section>
    <section id="about" class="wrap about">
      <h2>About us</h2>
      <p>Founded by Amr Selim. Learn to sail on the Mediterranean.</p>
      <details><summary>Opening hours</summary><p>Saturday to
Thursday 10:00 to 22:00, Friday 14:00 to 22:00.</p></details>
    </section>
    <section id="contact" class="wrap">
      <h2>Contact</h2>
      <form action="/contact" method="post" class="form">
        <label for="n">Name</label><input id="n" name="name" required>
        <label for="e">Email</label><input id="e" name="email"
```

```
type="email" required>
        <label for="m">Message</label><textarea id="m" name="message"
rows="4" required></textarea>
        <button>Send</button>
      </form>
    </section>
  </main>
  <footer class="site-footer"><p>&copy; 2026 Alexandria Sailing
School &middot; <a href="#main">Back to top</a></p></footer>
</body>
</html>
```

Project 1115: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #1e40af; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.skip { position: absolute; left: -999px; } .skip:focus { left: 1rem;
top: 1rem; background: #fff; padding: .5rem; z-index: 100; }
.site-header { position: sticky; top: 0; z-index: 10; display: flex;
flex-wrap: wrap; justify-content: space-between; align-items: center;
gap: .5rem 1rem; padding: .75rem 1rem; background: #fff; border-
bottom: 1px solid var(--line); }
.logo { font-weight: 800; color: var(--brand); text-decoration: none;
}
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { padding: .4rem .8rem; border-radius: 6px; text-decoration:
none; color: var(--ink); }
.nav a:hover { background: var(--accent); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(1.8rem, 5vw, 3rem); }
.btn { display: inline-block; padding: .7rem 1.4rem; border-radius:
999px; background: #fff; color: var(--brand); text-decoration: none;
font-weight: 700; }
.wrap { max-width: 60rem; margin: 0 auto; padding: 3rem 1rem; }
.grid { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(13rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
.price { font-weight: 700; color: var(--brand); }
.about { background: #fafafa; }
details { margin-top: 1rem; } summary { cursor: pointer; font-weight:
600; }
.form { display: grid; gap: .4rem; max-width: 30rem; }
```

```
.form label { font-weight: 600; margin-top: .6rem; }
.form input, .form textarea { padding: .6rem; border: 1px solid #bbb;
border-radius: 8px; font: inherit; }
.form button { justify-self: start; margin-top: 1rem; padding: .7rem
1.4rem; border: 0; border-radius: 999px; background: var(--brand);
color: #fff; font: inherit; }
.site-footer { text-align: center; padding: 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
h2 { scroll-margin-top: 4rem; }
```

Project 1115 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Alexandria Sailing School - Complete site</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main"><ul class="nav">	A block of navigation links; aria-label names it for screen readers.
Lessons <a href="#about">About</a...	A hyperlink; href gives the destination.
<main id="main">	The unique content of this page; exactly one per page.
<section class="hero">	A thematic group of content, normally with its own heading.
Learn to sail on the Mediterranean	The main heading; only one per page.
Welcome to Alexandria Sailing School in Alexandria.	A paragraph of text.

Line	What it does
Explore	A link styled as a button; it navigates, so it is a link and not a <button>.
Our lessons	Second-level heading for a section.
	Generic block container for grouping and layout.
<article class="card"> Taster session Two hours on the wa...	A self-contained piece: card, post, product.
<article class="card"> Beginner course Five sessions. ...	Third-level heading, inside an h2 section.
<details><summary>Opening hours</summary> Saturday to Thursday 10...	Disclosure widget that can be opened and closed.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
<label for="n">Name</label><input id="n" name="name" required>	Text label for a control; for matches the control's id, or the label wraps the control.
<label for="e">Email</label><input id="e" name="email" type="email"...	Email field: validated automatically and shows the @ keyboard on phones.
<label for="m">Message</label><textarea id="m" name="message" rows=...	Multi-line text field.
<button>Send</button>	A clickable button; inside a form it submits by default.

Line	What it does
<footer class="site-footer"><p>© 2026 Alexandria Sailing Schoo...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #1e40af;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: #fff;	Background colour or image.
padding: .5rem;	Space inside the element between its border and content.
z-index: 100;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
align-items: center;	Centres items on the cross axis.
gap: .5rem 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-weight: 800;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
border-radius: 6px;	Rounds the corners.
.nav a:hover {	Applies while the pointer is over the element.
text-align: center;	Centres inline content such as text.
font-size: clamp(1.8rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
grid-template-columns: repeat(auto-fit, minmax(13rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	The line around the element: width, style and colour.
} summary { cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-top: 1px solid var(--line);	A top border used as an accent or separator.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.

Check your work

- Skip link appears on first Tab
- Anchor links land below the sticky header
- One h1
- Form fully labelled
- Passes the W3C validator

Exercises

1. Add smooth scrolling with scroll-behavior: smooth (respecting reduced motion).
2. Add an Arabic RTL version.
3. Split into multiple pages with a shared stylesheet.

Theme data for this project

Field	Value
Business	Alexandria Sailing School
Tagline	Learn to sail on the Mediterranean
City	Alexandria
Owner	Amr Selim
Brand colour	#1e40af
Accent colour	#eff6ff
Offers	Taster session (500 EGP); Beginner course (2200 EGP); Racing clinic (1800 EGP); Private lesson (900 EGP)

Project 1116: Complete one-page website for Habiba Handmade Jewellery

Theme: Habiba Handmade Jewellery (Aswan) | Level 3 | Files: index.html, styles.css

Brief

Combine everything into a single-page site: skip link, sticky header with anchor navigation, hero, offers grid, about with details, contact form and footer.

Learning goals

- Assemble a full page from components
- Use in-page anchor navigation with scroll-margin-top
- Provide a skip link

Elements and CSS used

HTML elements	CSS features
a.skip, header, nav, main, section, h1-h3, article, details, summary, form, label, input, textarea, button, footer	position: sticky, z-index, scroll-margin-top, grid auto-fit, clamp(), focus styles for skip link

Build guide

1. Write the skeleton with four sections that have ids.
2. Add the sticky header with links to those ids.
3. Add a skip link as the first element in body.
4. Style the hero, grid, about and form.
5. Add scroll-margin-top to h2 so anchors are not hidden by the header.

6. Validate the whole page and test keyboard navigation.

Project 1116: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Habiba Handmade Jewellery - Complete site</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <a class="skip" href="#main">Skip to content</a>
  <header class="site-header">
    <a class="logo" href="index.html">Habiba Handmade Jewellery</a>
    <nav aria-label="Main"><ul class="nav">
      <li><a href="#offers">Items</a></li><li><a href="#about">About</
a></li><li><a href="#contact">Contact</a></li>
    </ul></nav>
  </header>
  <main id="main">
    <section class="hero">
      <h1>Silver and brass pieces inspired by Nubia</h1>
      <p>Welcome to Habiba Handmade Jewellery in Aswan.</p>
      <a class="btn" href="#offers">Explore</a>
    </section>
    <section id="offers" class="wrap">
      <h2>Our items</h2>
      <div class="grid">
        <article class="card"><h3>Lotus pendant</h3><p>Sterling
silver.</p><p class="price">650 EGP</p></article>
        <article class="card"><h3>Brass cuff</h3><p>Hand engraved.</
p><p class="price">420 EGP</p></article>
        <article class="card"><h3>Bead earrings</h3><p>Recycled glass.
</p><p class="price">180 EGP</p></article>
        <article class="card"><h3>Ankh ring</h3><p>Adjustable.</p><p
class="price">300 EGP</p></article>
      </div>
    </section>
    <section id="about" class="wrap about">
      <h2>About us</h2>
      <p>Founded by Habiba Saleh. Silver and brass pieces inspired by
Nubia.</p>
      <details><summary>Opening hours</summary><p>Saturday to
Thursday 10:00 to 22:00, Friday 14:00 to 22:00.</p></details>
    </section>
    <section id="contact" class="wrap">
      <h2>Contact</h2>
      <form action="/contact" method="post" class="form">
        <label for="n">Name</label><input id="n" name="name" required>
```

```
        <label for="e">Email</label><input id="e" name="email"
type="email" required>
        <label for="m">Message</label><textarea id="m" name="message"
rows="4" required></textarea>
        <button>Send</button>
      </form>
    </section>
  </main>
  <footer class="site-footer"><p>&copy; 2026 Habiba Handmade
Jewellery &middot; <a href="#main">Back to top</a></p></footer>
</body>
</html>
```

Project 1116: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #a16207; --accent: #fefce8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.skip { position: absolute; left: -999px; } .skip:focus { left: 1rem;
top: 1rem; background: #fff; padding: .5rem; z-index: 100; }
.site-header { position: sticky; top: 0; z-index: 10; display: flex;
flex-wrap: wrap; justify-content: space-between; align-items: center;
gap: .5rem 1rem; padding: .75rem 1rem; background: #fff; border-
bottom: 1px solid var(--line); }
.logo { font-weight: 800; color: var(--brand); text-decoration: none;
}
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { padding: .4rem .8rem; border-radius: 6px; text-decoration:
none; color: var(--ink); }
.nav a:hover { background: var(--accent); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(1.8rem, 5vw, 3rem); }
.btn { display: inline-block; padding: .7rem 1.4rem; border-radius:
999px; background: #fff; color: var(--brand); text-decoration: none;
font-weight: 700; }
.wrap { max-width: 60rem; margin: 0 auto; padding: 3rem 1rem; }
.grid { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(13rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
.price { font-weight: 700; color: var(--brand); }
.about { background: #fafafa; }
details { margin-top: 1rem; } summary { cursor: pointer; font-weight:
600; }
```

```
.form { display: grid; gap: .4rem; max-width: 30rem; }
.form label { font-weight: 600; margin-top: .6rem; }
.form input, .form textarea { padding: .6rem; border: 1px solid #bbb;
border-radius: 8px; font: inherit; }
.form button { justify-self: start; margin-top: 1rem; padding: .7rem
1.4rem; border: 0; border-radius: 999px; background: var(--brand);
color: #fff; font: inherit; }
.site-footer { text-align: center; padding: 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
h2 { scroll-margin-top: 4rem; }
```

Project 1116 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Habiba Handmade Jewellery - Complete site</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main"><ul class="nav">	A block of navigation links; aria-label names it for screen readers.
Items About<...	A hyperlink; href gives the destination.
<main id="main">	The unique content of this page; exactly one per page.
<section class="hero">	A thematic group of content, normally with its own heading.
Silver and brass pieces inspired by Nubia	The main heading; only one per page.

Line	What it does
Welcome to Habiba Handmade Jewellery in Aswan.	A paragraph of text.
Explore	A link styled as a button; it navigates, so it is a link and not a <button>.
Our items	Second-level heading for a section.
	Generic block container for grouping and layout.
<article class="card"> Lotus pendant Sterling silver. ...	A self-contained piece: card, post, product.
<article class="card"> Brass cuff Hand engraved. <p cl...	Third-level heading, inside an h2 section.
<details><summary>Opening hours</summary> Saturday to Thursday 10...	Disclosure widget that can be opened and closed.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
<label for="n">Name</label><input id="n" name="name" required>	Text label for a control; for matches the control's id, or the label wraps the control.
<label for="e">Email</label><input id="e" name="email" type="email"...	Email field: validated automatically and shows the @ keyboard on phones.
<label for="m">Message</label><textarea id="m" name="message" rows=...	Multi-line text field.

Line	What it does
<button>Send</button>	A clickable button; inside a form it submits by default.
<footer class="site-footer"><p>© 2026 Habiba Handmade Jeweller...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #a16207;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: #fff;	Background colour or image.
padding: .5rem;	Space inside the element between its border and content.

Declaration	What it does
z-index: 100;	Stacking order for positioned elements; higher is on top.
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
align-items: center;	Centres items on the cross axis.
gap: .5rem 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-weight: 800;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
border-radius: 6px;	Rounds the corners.
.nav a:hover {	Applies while the pointer is over the element.
text-align: center;	Centres inline content such as text.
font-size: clamp(1.8rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.

Declaration	What it does
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
grid-template-columns: repeat(auto-fit, minmax(13rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	The line around the element: width, style and colour.
} summary { cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-top: 1px solid var(--line);	A top border used as an accent or separator.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.

Check your work

- Skip link appears on first Tab
- Anchor links land below the sticky header
- One h1
- Form fully labelled
- Passes the W3C validator

Exercises

1. Add smooth scrolling with scroll-behavior: smooth (respecting reduced motion).
2. Add an Arabic RTL version.
3. Split into multiple pages with a shared stylesheet.

Theme data for this project

Field	Value
Business	Habiba Handmade Jewellery
Tagline	Silver and brass pieces inspired by Nubia
City	Aswan
Owner	Habiba Saleh
Brand colour	#a16207
Accent colour	#fefce8
Offers	Lotus pendant (650 EGP); Brass cuff (420 EGP); Bead earrings (180 EGP); Ankh ring (300 EGP)

Project 1117: Complete one-page website for Fayoum Pottery Studio

Theme: Fayoum Pottery Studio (Tunis Village) | Level 3 | Files: index.html, styles.css

Brief

Combine everything into a single-page site: skip link, sticky header with anchor navigation, hero, offers grid, about with details, contact form and footer.

Learning goals

- Assemble a full page from components
- Use in-page anchor navigation with scroll-margin-top
- Provide a skip link

Elements and CSS used

HTML elements	CSS features
a.skip, header, nav, main, section, h1-h3, article, details, summary, form, label, input, textarea, button, footer	position: sticky, z-index, scroll-margin-top, grid auto-fit, clamp(), focus styles for skip link

Build guide

1. Write the skeleton with four sections that have ids.
2. Add the sticky header with links to those ids.
3. Add a skip link as the first element in body.
4. Style the hero, grid, about and form.
5. Add scroll-margin-top to h2 so anchors are not hidden by the header.

6. Validate the whole page and test keyboard navigation.

Project 1117: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Fayoum Pottery Studio - Complete site</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <a class="skip" href="#main">Skip to content</a>
  <header class="site-header">
    <a class="logo" href="index.html">Fayoum Pottery Studio</a>
    <nav aria-label="Main"><ul class="nav">
      <li><a href="#offers">Workshops</a></li><li><a
href="#about">About</a></li><li><a href="#contact">Contact</a></li>
    </ul></nav>
  </header>
  <main id="main">
    <section class="hero">
      <h1>Wheel throwing and glazing classes</h1>
      <p>Welcome to Fayoum Pottery Studio in Tunis Village.</p>
      <a class="btn" href="#offers">Explore</a>
    </section>
    <section id="offers" class="wrap">
      <h2>Our workshops</h2>
      <div class="grid">
        <article class="card"><h3>Intro to the wheel</h3><p>Three
hours, take home a bowl.</p><p class="price">450 EGP</p></article>
        <article class="card"><h3>Glazing day</h3><p>Colour your
pieces.</p><p class="price">300 EGP</p></article>
        <article class="card"><h3>Kids clay class</h3><p>Ages 6 to 12.
</p><p class="price">200 EGP</p></article>
        <article class="card"><h3>Weekend retreat</h3><p>Two days
with meals.</p><p class="price">2500 EGP</p></article>
      </div>
    </section>
    <section id="about" class="wrap about">
      <h2>About us</h2>
      <p>Founded by Ahmed Mahmoud. Wheel throwing and glazing classes.
</p>
      <details><summary>Opening hours</summary><p>Saturday to
Thursday 10:00 to 22:00, Friday 14:00 to 22:00.</p></details>
    </section>
    <section id="contact" class="wrap">
      <h2>Contact</h2>
      <form action="/contact" method="post" class="form">
        <label for="n">Name</label><input id="n" name="name" required>
```

```
        <label for="e">Email</label><input id="e" name="email"
type="email" required>
        <label for="m">Message</label><textarea id="m" name="message"
rows="4" required></textarea>
        <button>Send</button>
      </form>
    </section>
  </main>
  <footer class="site-footer"><p>&copy; 2026 Fayoum Pottery Studio
&middot; <a href="#main">Back to top</a></p></footer>
</body>
</html>
```

Project 1117: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #9a3412; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.skip { position: absolute; left: -999px; } .skip:focus { left: 1rem;
top: 1rem; background: #fff; padding: .5rem; z-index: 100; }
.site-header { position: sticky; top: 0; z-index: 10; display: flex;
flex-wrap: wrap; justify-content: space-between; align-items: center;
gap: .5rem 1rem; padding: .75rem 1rem; background: #fff; border-
bottom: 1px solid var(--line); }
.logo { font-weight: 800; color: var(--brand); text-decoration: none;
}
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { padding: .4rem .8rem; border-radius: 6px; text-decoration:
none; color: var(--ink); }
.nav a:hover { background: var(--accent); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(1.8rem, 5vw, 3rem); }
.btn { display: inline-block; padding: .7rem 1.4rem; border-radius:
999px; background: #fff; color: var(--brand); text-decoration: none;
font-weight: 700; }
.wrap { max-width: 60rem; margin: 0 auto; padding: 3rem 1rem; }
.grid { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(13rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
.price { font-weight: 700; color: var(--brand); }
.about { background: #fafafa; }
details { margin-top: 1rem; } summary { cursor: pointer; font-weight:
600; }
```

```
.form { display: grid; gap: .4rem; max-width: 30rem; }
.form label { font-weight: 600; margin-top: .6rem; }
.form input, .form textarea { padding: .6rem; border: 1px solid #bbb;
border-radius: 8px; font: inherit; }
.form button { justify-self: start; margin-top: 1rem; padding: .7rem
1.4rem; border: 0; border-radius: 999px; background: var(--brand);
color: #fff; font: inherit; }
.site-footer { text-align: center; padding: 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
h2 { scroll-margin-top: 4rem; }
```

Project 1117 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Fayoum Pottery Studio - Complete site</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main"><ul class="nav">	A block of navigation links; aria-label names it for screen readers.
Workshops <a href="#about">About<...	A hyperlink; href gives the destination.
<main id="main">	The unique content of this page; exactly one per page.
<section class="hero">	A thematic group of content, normally with its own heading.
Wheel throwing and glazing classes	The main heading; only one per page.
Welcome to Fayoum Pottery Studio in Tunis Village.	A paragraph of text.

Line	What it does
Explore	A link styled as a button; it navigates, so it is a link and not a <button>.
Our workshops	Second-level heading for a section.
	Generic block container for grouping and layout.
<article class="card"><h3>Intro to the wheel</h3><p>Three hours, ta...	A self-contained piece: card, post, product.
<article class="card"><h3>Glazing day</h3><p>Colour your pieces.</p...	Third-level heading, inside an h2 section.
<details><summary>Opening hours</summary><p>Saturday to Thursday 10...	Disclosure widget that can be opened and closed.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
<label for="n">Name</label><input id="n" name="name" required>	Text label for a control; for matches the control's id, or the label wraps the control.
<label for="e">Email</label><input id="e" name="email" type="email"...	Email field: validated automatically and shows the @ keyboard on phones.
<label for="m">Message</label><textarea id="m" name="message" rows=...	Multi-line text field.
<button>Send</button>	A clickable button; inside a form it submits by default.

Line	What it does
<footer class="site-footer"><p>© 2026 Fayoum Pottery Studio &m...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #9a3412;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: #fff;	Background colour or image.
padding: .5rem;	Space inside the element between its border and content.
z-index: 100;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
align-items: center;	Centres items on the cross axis.
gap: .5rem 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-weight: 800;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
border-radius: 6px;	Rounds the corners.
.nav a:hover {	Applies while the pointer is over the element.
text-align: center;	Centres inline content such as text.
font-size: clamp(1.8rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
grid-template-columns: repeat(auto-fit, minmax(13rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	The line around the element: width, style and colour.
} summary { cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-top: 1px solid var(--line);	A top border used as an accent or separator.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.

Check your work

- Skip link appears on first Tab
- Anchor links land below the sticky header
- One h1
- Form fully labelled
- Passes the W3C validator

Exercises

1. Add smooth scrolling with scroll-behavior: smooth (respecting reduced motion).
2. Add an Arabic RTL version.
3. Split into multiple pages with a shared stylesheet.

Theme data for this project

Field	Value
Business	Fayoum Pottery Studio
Tagline	Wheel throwing and glazing classes
City	Tunis Village
Owner	Ahmed Mahmoud
Brand colour	#9a3412
Accent colour	#fff7ed
Offers	Intro to the wheel (450 EGP); Glazing day (300 EGP); Kids clay class (200 EGP); Weekend retreat (2500 EGP)

Project 1118: Complete one-page website for Cleopatra Beauty Salon

Theme: Cleopatra Beauty Salon (Dokki) | Level 3 | Files: index.html, styles.css

Brief

Combine everything into a single-page site: skip link, sticky header with anchor navigation, hero, offers grid, about with details, contact form and footer.

Learning goals

- Assemble a full page from components
- Use in-page anchor navigation with scroll-margin-top
- Provide a skip link

Elements and CSS used

HTML elements	CSS features
a.skip, header, nav, main, section, h1-h3, article, details, summary, form, label, input, textarea, button, footer	position: sticky, z-index, scroll-margin-top, grid auto-fit, clamp(), focus styles for skip link

Build guide

1. Write the skeleton with four sections that have ids.
2. Add the sticky header with links to those ids.
3. Add a skip link as the first element in body.
4. Style the hero, grid, about and form.
5. Add scroll-margin-top to h2 so anchors are not hidden by the header.

6. Validate the whole page and test keyboard navigation.

Project 1118: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Cleopatra Beauty Salon - Complete site</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <a class="skip" href="#main">Skip to content</a>
  <header class="site-header">
    <a class="logo" href="index.html">Cleopatra Beauty Salon</a>
    <nav aria-label="Main"><ul class="nav">
      <li><a href="#offers">Treatments</a></li><li><a
href="#about">About</a></li><li><a href="#contact">Contact</a></li>
    </ul></nav>
  </header>
  <main id="main">
    <section class="hero">
      <h1>Hair, nails and skin care</h1>
      <p>Welcome to Cleopatra Beauty Salon in Dokki.</p>
      <a class="btn" href="#offers">Explore</a>
    </section>
    <section id="offers" class="wrap">
      <h2>Our treatments</h2>
      <div class="grid">
        <article class="card"><h3>Haircut and blow-dry</
h3><p>Consultation included.</p><p class="price">350 EGP</p></article>
        <article class="card"><h3>Manicure</h3><p>Classic or gel.</
p><p class="price">200 EGP</p></article>
        <article class="card"><h3>Facial</h3><p>Deep cleanse, 60
minutes.</p><p class="price">600 EGP</p></article>
        <article class="card"><h3>Bridal package</h3><p>Hair, make-up
and nails.</p><p class="price">4500 EGP</p></article>
      </div>
    </section>
    <section id="about" class="wrap about">
      <h2>About us</h2>
      <p>Founded by Mariam Adel. Hair, nails and skin care.</p>
      <details><summary>Opening hours</summary><p>Saturday to
Thursday 10:00 to 22:00, Friday 14:00 to 22:00.</p></details>
    </section>
    <section id="contact" class="wrap">
      <h2>Contact</h2>
      <form action="/contact" method="post" class="form">
        <label for="n">Name</label><input id="n" name="name" required>
        <label for="e">Email</label><input id="e" name="email"
```

```
type="email" required>
        <label for="m">Message</label><textarea id="m" name="message"
rows="4" required></textarea>
        <button>Send</button>
      </form>
    </section>
  </main>
  <footer class="site-footer"><p>&copy; 2026 Cleopatra Beauty Salon
&middot; <a href="#main">Back to top</a></p></footer>
</body>
</html>
```

Project 1118: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #db2777; --accent: #fdf2f8; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.skip { position: absolute; left: -999px; } .skip:focus { left: 1rem;
top: 1rem; background: #fff; padding: .5rem; z-index: 100; }
.site-header { position: sticky; top: 0; z-index: 10; display: flex;
flex-wrap: wrap; justify-content: space-between; align-items: center;
gap: .5rem 1rem; padding: .75rem 1rem; background: #fff; border-
bottom: 1px solid var(--line); }
.logo { font-weight: 800; color: var(--brand); text-decoration: none;
}
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { padding: .4rem .8rem; border-radius: 6px; text-decoration:
none; color: var(--ink); }
.nav a:hover { background: var(--accent); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(1.8rem, 5vw, 3rem); }
.btn { display: inline-block; padding: .7rem 1.4rem; border-radius:
999px; background: #fff; color: var(--brand); text-decoration: none;
font-weight: 700; }
.wrap { max-width: 60rem; margin: 0 auto; padding: 3rem 1rem; }
.grid { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(13rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
.price { font-weight: 700; color: var(--brand); }
.about { background: #fafafa; }
details { margin-top: 1rem; } summary { cursor: pointer; font-weight:
600; }
.form { display: grid; gap: .4rem; max-width: 30rem; }
```

```
.form label { font-weight: 600; margin-top: .6rem; }
.form input, .form textarea { padding: .6rem; border: 1px solid #bbb;
border-radius: 8px; font: inherit; }
.form button { justify-self: start; margin-top: 1rem; padding: .7rem
1.4rem; border: 0; border-radius: 999px; background: var(--brand);
color: #fff; font: inherit; }
.site-footer { text-align: center; padding: 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
h2 { scroll-margin-top: 4rem; }
```

Project 1118 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Cleopatra Beauty Salon - Complete site</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main"><ul class="nav">	A block of navigation links; aria-label names it for screen readers.
Treatments <a href="#about">About...	A hyperlink; href gives the destination.
<main id="main">	The unique content of this page; exactly one per page.
<section class="hero">	A thematic group of content, normally with its own heading.
Hair, nails and skin care	The main heading; only one per page.
Welcome to Cleopatra Beauty Salon in Dokki.	A paragraph of text.

Line	What it does
Explore	A link styled as a button; it navigates, so it is a link and not a <button>.
Our treatments	Second-level heading for a section.
	Generic block container for grouping and layout.
<article class="card"> Haircut and blow-dry Consultation ...	A self-contained piece: card, post, product.
<article class="card"> Manicure Classic or gel. <p cla...	Third-level heading, inside an h2 section.
<details><summary>Opening hours</summary> Saturday to Thursday 10...	Disclosure widget that can be opened and closed.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
<label for="n">Name</label><input id="n" name="name" required>	Text label for a control; for matches the control's id, or the label wraps the control.
<label for="e">Email</label><input id="e" name="email" type="email"...	Email field: validated automatically and shows the @ keyboard on phones.
<label for="m">Message</label><textarea id="m" name="message" rows=...	Multi-line text field.
<button>Send</button>	A clickable button; inside a form it submits by default.

Line	What it does
<footer class="site-footer"><p>© 2026 Cleopatra Beauty Salon &...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #db2777;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: #fff;	Background colour or image.
padding: .5rem;	Space inside the element between its border and content.
z-index: 100;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
align-items: center;	Centres items on the cross axis.
gap: .5rem 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-weight: 800;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
border-radius: 6px;	Rounds the corners.
.nav a:hover {	Applies while the pointer is over the element.
text-align: center;	Centres inline content such as text.
font-size: clamp(1.8rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
grid-template-columns: repeat(auto-fit, minmax(13rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	The line around the element: width, style and colour.
} summary { cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-top: 1px solid var(--line);	A top border used as an accent or separator.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.

Check your work

- Skip link appears on first Tab
- Anchor links land below the sticky header
- One h1
- Form fully labelled
- Passes the W3C validator

Exercises

1. Add smooth scrolling with scroll-behavior: smooth (respecting reduced motion).
2. Add an Arabic RTL version.
3. Split into multiple pages with a shared stylesheet.

Theme data for this project

Field	Value
Business	Cleopatra Beauty Salon
Tagline	Hair, nails and skin care
City	Dokki
Owner	Mariam Adel
Brand colour	#db2777
Accent colour	#fdf2f8
Offers	Haircut and blow-dry (350 EGP); Manicure (200 EGP); Facial (600 EGP); Bridal package (4500 EGP)

Project 1119: Complete one-page website for Suez Auto Service

Theme: Suez Auto Service (Suez) | Level 3 | Files: index.html, styles.css

Brief

Combine everything into a single-page site: skip link, sticky header with anchor navigation, hero, offers grid, about with details, contact form and footer.

Learning goals

- Assemble a full page from components
- Use in-page anchor navigation with scroll-margin-top
- Provide a skip link

Elements and CSS used

HTML elements	CSS features
a.skip, header, nav, main, section, h1-h3, article, details, summary, form, label, input, textarea, button, footer	position: sticky, z-index, scroll-margin-top, grid auto-fit, clamp(), focus styles for skip link

Build guide

1. Write the skeleton with four sections that have ids.
2. Add the sticky header with links to those ids.
3. Add a skip link as the first element in body.
4. Style the hero, grid, about and form.
5. Add scroll-margin-top to h2 so anchors are not hidden by the header.

6. Validate the whole page and test keyboard navigation.

Project 1119: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Suez Auto Service - Complete site</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <a class="skip" href="#main">Skip to content</a>
  <header class="site-header">
    <a class="logo" href="index.html">Suez Auto Service</a>
    <nav aria-label="Main"><ul class="nav">
      <li><a href="#offers">Services</a></li><li><a
href="#about">About</a></li><li><a href="#contact">Contact</a></li>
    </ul></nav>
  </header>
  <main id="main">
    <section class="hero">
      <h1>Honest car servicing and repairs</h1>
      <p>Welcome to Suez Auto Service in Suez.</p>
      <a class="btn" href="#offers">Explore</a>
    </section>
    <section id="offers" class="wrap">
      <h2>Our services</h2>
      <div class="grid">
        <article class="card"><h3>Oil change</h3><p>Filter included.</
p><p class="price">600 EGP</p></article>
        <article class="card"><h3>Brake pads</h3><p>Front axle.</p><p
class="price">1400 EGP</p></article>
        <article class="card"><h3>Air conditioning</h3><p>Recharge
and check.</p><p class="price">900 EGP</p></article>
        <article class="card"><h3>Pre-purchase inspection</h3><p>120
point check.</p><p class="price">750 EGP</p></article>
      </div>
    </section>
    <section id="about" class="wrap about">
      <h2>About us</h2>
      <p>Founded by Khaled Nasser. Honest car servicing and repairs.</
p>
      <details><summary>Opening hours</summary><p>Saturday to
Thursday 10:00 to 22:00, Friday 14:00 to 22:00.</p></details>
    </section>
    <section id="contact" class="wrap">
      <h2>Contact</h2>
      <form action="/contact" method="post" class="form">
        <label for="n">Name</label><input id="n" name="name" required>
```

```
        <label for="e">Email</label><input id="e" name="email"
type="email" required>
        <label for="m">Message</label><textarea id="m" name="message"
rows="4" required></textarea>
        <button>Send</button>
      </form>
    </section>
  </main>
  <footer class="site-footer"><p>&copy; 2026 Suez Auto Service
&middot; <a href="#main">Back to top</a></p></footer>
</body>
</html>
```

Project 1119: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #374151; --accent: #f9fafb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.skip { position: absolute; left: -999px; } .skip:focus { left: 1rem;
top: 1rem; background: #fff; padding: .5rem; z-index: 100; }
.site-header { position: sticky; top: 0; z-index: 10; display: flex;
flex-wrap: wrap; justify-content: space-between; align-items: center;
gap: .5rem 1rem; padding: .75rem 1rem; background: #fff; border-
bottom: 1px solid var(--line); }
.logo { font-weight: 800; color: var(--brand); text-decoration: none;
}
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { padding: .4rem .8rem; border-radius: 6px; text-decoration:
none; color: var(--ink); }
.nav a:hover { background: var(--accent); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(1.8rem, 5vw, 3rem); }
.btn { display: inline-block; padding: .7rem 1.4rem; border-radius:
999px; background: #fff; color: var(--brand); text-decoration: none;
font-weight: 700; }
.wrap { max-width: 60rem; margin: 0 auto; padding: 3rem 1rem; }
.grid { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(13rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
.price { font-weight: 700; color: var(--brand); }
.about { background: #fafafa; }
details { margin-top: 1rem; } summary { cursor: pointer; font-weight:
600; }
```

```
.form { display: grid; gap: .4rem; max-width: 30rem; }
.form label { font-weight: 600; margin-top: .6rem; }
.form input, .form textarea { padding: .6rem; border: 1px solid #bbb;
border-radius: 8px; font: inherit; }
.form button { justify-self: start; margin-top: 1rem; padding: .7rem
1.4rem; border: 0; border-radius: 999px; background: var(--brand);
color: #fff; font: inherit; }
.site-footer { text-align: center; padding: 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
h2 { scroll-margin-top: 4rem; }
```

Project 1119 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Suez Auto Service - Complete site</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main"><ul class="nav">	A block of navigation links; aria-label names it for screen readers.
Services <a href="#about">About<//...	A hyperlink; href gives the destination.
<main id="main">	The unique content of this page; exactly one per page.
<section class="hero">	A thematic group of content, normally with its own heading.
Honest car servicing and repairs	The main heading; only one per page.
Welcome to Suez Auto Service in Suez.	A paragraph of text.

Line	What it does
Explore	A link styled as a button; it navigates, so it is a link and not a <button>.
Our services	Second-level heading for a section.
	Generic block container for grouping and layout.
<article class="card"> Oil change Filter included. <p ...	A self-contained piece: card, post, product.
<article class="card"> Brake pads Front axle. <p class...	Third-level heading, inside an h2 section.
<details><summary>Opening hours</summary> Saturday to Thursday 10...	Disclosure widget that can be opened and closed.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
<label for="n">Name</label><input id="n" name="name" required>	Text label for a control; for matches the control's id, or the label wraps the control.
<label for="e">Email</label><input id="e" name="email" type="email"...	Email field: validated automatically and shows the @ keyboard on phones.
<label for="m">Message</label><textarea id="m" name="message" rows=...	Multi-line text field.
<button>Send</button>	A clickable button; inside a form it submits by default.

Line	What it does
<footer class="site-footer"><p>© 2026 Suez Auto Service &middo...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #374151;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: #fff;	Background colour or image.
padding: .5rem;	Space inside the element between its border and content.
z-index: 100;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
align-items: center;	Centres items on the cross axis.
gap: .5rem 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-weight: 800;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
border-radius: 6px;	Rounds the corners.
.nav a:hover {	Applies while the pointer is over the element.
text-align: center;	Centres inline content such as text.
font-size: clamp(1.8rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
grid-template-columns: repeat(auto-fit, minmax(13rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	The line around the element: width, style and colour.
} summary { cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-top: 1px solid var(--line);	A top border used as an accent or separator.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.

Check your work

- Skip link appears on first Tab
- Anchor links land below the sticky header
- One h1
- Form fully labelled
- Passes the W3C validator

Exercises

1. Add smooth scrolling with scroll-behavior: smooth (respecting reduced motion).
2. Add an Arabic RTL version.
3. Split into multiple pages with a shared stylesheet.

Theme data for this project

Field	Value
Business	Suez Auto Service
Tagline	Honest car servicing and repairs
City	Suez
Owner	Khaled Nasser
Brand colour	#374151
Accent colour	#f9fafb
Offers	Oil change (600 EGP); Brake pads (1400 EGP); Air conditioning (900 EGP); Pre-purchase inspection (750 EGP)

Project 1120: Complete one-page website for Luxor Music Academy

Theme: Luxor Music Academy (Luxor) | Level 3 | Files: index.html, styles.css

Brief

Combine everything into a single-page site: skip link, sticky header with anchor navigation, hero, offers grid, about with details, contact form and footer.

Learning goals

- Assemble a full page from components
- Use in-page anchor navigation with scroll-margin-top
- Provide a skip link

Elements and CSS used

HTML elements	CSS features
a.skip, header, nav, main, section, h1-h3, article, details, summary, form, label, input, textarea, button, footer	position: sticky, z-index, scroll-margin-top, grid auto-fit, clamp(), focus styles for skip link

Build guide

1. Write the skeleton with four sections that have ids.
2. Add the sticky header with links to those ids.
3. Add a skip link as the first element in body.
4. Style the hero, grid, about and form.
5. Add scroll-margin-top to h2 so anchors are not hidden by the header.

6. Validate the whole page and test keyboard navigation.

Project 1120: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Luxor Music Academy - Complete site</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <a class="skip" href="#main">Skip to content</a>
  <header class="site-header">
    <a class="logo" href="index.html">Luxor Music Academy</a>
    <nav aria-label="Main"><ul class="nav">
      <li><a href="#offers">Courses</a></li><li><a
href="#about">About</a></li><li><a href="#contact">Contact</a></li>
    </ul></nav>
  </header>
  <main id="main">
    <section class="hero">
      <h1>Oud, piano, guitar and voice lessons</h1>
      <p>Welcome to Luxor Music Academy in Luxor.</p>
      <a class="btn" href="#offers">Explore</a>
    </section>
    <section id="offers" class="wrap">
      <h2>Our courses</h2>
      <div class="grid">
        <article class="card"><h3>Oud for beginners</h3><p>Eight
weekly lessons.</p><p class="price">1600 EGP</p></article>
        <article class="card"><h3>Piano grade 1</h3><p>Theory and
practice.</p><p class="price">1800 EGP</p></article>
        <article class="card"><h3>Guitar chords</h3><p>Play songs in
a month.</p><p class="price">1400 EGP</p></article>
        <article class="card"><h3>Voice coaching</h3><p>Breathing and
range.</p><p class="price">1500 EGP</p></article>
      </div>
    </section>
    <section id="about" class="wrap about">
      <h2>About us</h2>
      <p>Founded by Salma Ragab. Oud, piano, guitar and voice lessons.
</p>
      <details><summary>Opening hours</summary><p>Saturday to
Thursday 10:00 to 22:00, Friday 14:00 to 22:00.</p></details>
    </section>
    <section id="contact" class="wrap">
      <h2>Contact</h2>
      <form action="/contact" method="post" class="form">
        <label for="n">Name</label><input id="n" name="name" required>
```

```
        <label for="e">Email</label><input id="e" name="email"
type="email" required>
        <label for="m">Message</label><textarea id="m" name="message"
rows="4" required></textarea>
        <button>Send</button>
      </form>
    </section>
  </main>
  <footer class="site-footer"><p>&copy; 2026 Luxor Music Academy
&middot; <a href="#main">Back to top</a></p></footer>
</body>
</html>
```

Project 1120: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #4c1d95; --accent: #f5f3ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.skip { position: absolute; left: -999px; } .skip:focus { left: 1rem;
top: 1rem; background: #fff; padding: .5rem; z-index: 100; }
.site-header { position: sticky; top: 0; z-index: 10; display: flex;
flex-wrap: wrap; justify-content: space-between; align-items: center;
gap: .5rem 1rem; padding: .75rem 1rem; background: #fff; border-
bottom: 1px solid var(--line); }
.logo { font-weight: 800; color: var(--brand); text-decoration: none;
}
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { padding: .4rem .8rem; border-radius: 6px; text-decoration:
none; color: var(--ink); }
.nav a:hover { background: var(--accent); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(1.8rem, 5vw, 3rem); }
.btn { display: inline-block; padding: .7rem 1.4rem; border-radius:
999px; background: #fff; color: var(--brand); text-decoration: none;
font-weight: 700; }
.wrap { max-width: 60rem; margin: 0 auto; padding: 3rem 1rem; }
.grid { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(13rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
.price { font-weight: 700; color: var(--brand); }
.about { background: #fafafa; }
details { margin-top: 1rem; } summary { cursor: pointer; font-weight:
600; }
```

```
.form { display: grid; gap: .4rem; max-width: 30rem; }
.form label { font-weight: 600; margin-top: .6rem; }
.form input, .form textarea { padding: .6rem; border: 1px solid #bbb;
border-radius: 8px; font: inherit; }
.form button { justify-self: start; margin-top: 1rem; padding: .7rem
1.4rem; border: 0; border-radius: 999px; background: var(--brand);
color: #fff; font: inherit; }
.site-footer { text-align: center; padding: 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
h2 { scroll-margin-top: 4rem; }
```

Project 1120 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Luxor Music Academy - Complete site</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main"><ul class="nav">	A block of navigation links; aria-label names it for screen readers.
Courses <a href="#about">About</a...	A hyperlink; href gives the destination.
<main id="main">	The unique content of this page; exactly one per page.
<section class="hero">	A thematic group of content, normally with its own heading.
Oud, piano, guitar and voice lessons	The main heading; only one per page.
Welcome to Luxor Music Academy in Luxor.	A paragraph of text.

Line	What it does
Explore	A link styled as a button; it navigates, so it is a link and not a <button>.
Our courses	Second-level heading for a section.
	Generic block container for grouping and layout.
<article class="card"><h3>Oud for beginners</h3><p>Eight weekly les...	A self-contained piece: card, post, product.
<article class="card"><h3>Piano grade 1</h3><p>Theory and practice....	Third-level heading, inside an h2 section.
<details><summary>Opening hours</summary><p>Saturday to Thursday 10...	Disclosure widget that can be opened and closed.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
<label for="n">Name</label><input id="n" name="name" required>	Text label for a control; for matches the control's id, or the label wraps the control.
<label for="e">Email</label><input id="e" name="email" type="email"...	Email field: validated automatically and shows the @ keyboard on phones.
<label for="m">Message</label><textarea id="m" name="message" rows=...	Multi-line text field.
<button>Send</button>	A clickable button; inside a form it submits by default.

Line	What it does
<footer class="site-footer"><p>© 2026 Luxor Music Academy &mid...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #4c1d95;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: #fff;	Background colour or image.
padding: .5rem;	Space inside the element between its border and content.
z-index: 100;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
align-items: center;	Centres items on the cross axis.
gap: .5rem 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-weight: 800;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
border-radius: 6px;	Rounds the corners.
.nav a:hover {	Applies while the pointer is over the element.
text-align: center;	Centres inline content such as text.
font-size: clamp(1.8rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
grid-template-columns: repeat(auto-fit, minmax(13rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	The line around the element: width, style and colour.
} summary { cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-top: 1px solid var(--line);	A top border used as an accent or separator.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.

Check your work

- Skip link appears on first Tab
- Anchor links land below the sticky header
- One h1
- Form fully labelled
- Passes the W3C validator

Exercises

1. Add smooth scrolling with scroll-behavior: smooth (respecting reduced motion).
2. Add an Arabic RTL version.
3. Split into multiple pages with a shared stylesheet.

Theme data for this project

Field	Value
Business	Luxor Music Academy
Tagline	Oud, piano, guitar and voice lessons
City	Luxor
Owner	Salma Ragab
Brand colour	#4c1d95
Accent colour	#f5f3ff
Offers	Oud for beginners (1600 EGP); Piano grade 1 (1800 EGP); Guitar chords (1400 EGP); Voice coaching (1500 EGP)

Project 1121: Complete one-page website for Port Said Seafood

Theme: Port Said Seafood (Port Said) | Level 3 | Files: index.html, styles.css

Brief

Combine everything into a single-page site: skip link, sticky header with anchor navigation, hero, offers grid, about with details, contact form and footer.

Learning goals

- Assemble a full page from components
- Use in-page anchor navigation with scroll-margin-top
- Provide a skip link

Elements and CSS used

HTML elements	CSS features
a.skip, header, nav, main, section, h1-h3, article, details, summary, form, label, input, textarea, button, footer	position: sticky, z-index, scroll-margin-top, grid auto-fit, clamp(), focus styles for skip link

Build guide

1. Write the skeleton with four sections that have ids.
2. Add the sticky header with links to those ids.
3. Add a skip link as the first element in body.
4. Style the hero, grid, about and form.
5. Add scroll-margin-top to h2 so anchors are not hidden by the header.

6. Validate the whole page and test keyboard navigation.

Project 1121: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Port Said Seafood - Complete site</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <a class="skip" href="#main">Skip to content</a>
  <header class="site-header">
    <a class="logo" href="index.html">Port Said Seafood</a>
    <nav aria-label="Main"><ul class="nav">
      <li><a href="#offers">Dishes</a></li><li><a
href="#about">About</a></li><li><a href="#contact">Contact</a></li>
    </ul></nav>
  </header>
  <main id="main">
    <section class="hero">
      <h1>Grilled fish straight from the boats</h1>
      <p>Welcome to Port Said Seafood in Port Said.</p>
      <a class="btn" href="#offers">Explore</a>
    </section>
    <section id="offers" class="wrap">
      <h2>Our dishes</h2>
      <div class="grid">
        <article class="card"><h3>Grilled sea bass</h3><p>With rice
and salad.</p><p class="price">320 EGP</p></article>
        <article class="card"><h3>Shrimp tagine</h3><p>Tomato and
garlic.</p><p class="price">280 EGP</p></article>
        <article class="card"><h3>Calamari</h3><p>Fried, with tahini.
</p><p class="price">190 EGP</p></article>
        <article class="card"><h3>Fish soup</h3><p>Daily catch.</p><p
class="price">120 EGP</p></article>
      </div>
    </section>
    <section id="about" class="wrap about">
      <h2>About us</h2>
      <p>Founded by Sherif Wahba. Grilled fish straight from the
boats.</p>
      <details><summary>Opening hours</summary><p>Saturday to
Thursday 10:00 to 22:00, Friday 14:00 to 22:00.</p></details>
    </section>
    <section id="contact" class="wrap">
      <h2>Contact</h2>
      <form action="/contact" method="post" class="form">
        <label for="n">Name</label><input id="n" name="name" required>
```

```
        <label for="e">Email</label><input id="e" name="email"
type="email" required>
        <label for="m">Message</label><textarea id="m" name="message"
rows="4" required></textarea>
        <button>Send</button>
      </form>
    </section>
  </main>
  <footer class="site-footer"><p>&copy; 2026 Port Said Seafood
&middot; <a href="#main">Back to top</a></p></footer>
</body>
</html>
```

Project 1121: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #0e7490; --accent: #ecfeff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.skip { position: absolute; left: -999px; } .skip:focus { left: 1rem;
top: 1rem; background: #fff; padding: .5rem; z-index: 100; }
.site-header { position: sticky; top: 0; z-index: 10; display: flex;
flex-wrap: wrap; justify-content: space-between; align-items: center;
gap: .5rem 1rem; padding: .75rem 1rem; background: #fff; border-
bottom: 1px solid var(--line); }
.logo { font-weight: 800; color: var(--brand); text-decoration: none;
}
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { padding: .4rem .8rem; border-radius: 6px; text-decoration:
none; color: var(--ink); }
.nav a:hover { background: var(--accent); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(1.8rem, 5vw, 3rem); }
.btn { display: inline-block; padding: .7rem 1.4rem; border-radius:
999px; background: #fff; color: var(--brand); text-decoration: none;
font-weight: 700; }
.wrap { max-width: 60rem; margin: 0 auto; padding: 3rem 1rem; }
.grid { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(13rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
.price { font-weight: 700; color: var(--brand); }
.about { background: #fafafa; }
details { margin-top: 1rem; } summary { cursor: pointer; font-weight:
600; }
```

```
.form { display: grid; gap: .4rem; max-width: 30rem; }
.form label { font-weight: 600; margin-top: .6rem; }
.form input, .form textarea { padding: .6rem; border: 1px solid #bbb;
border-radius: 8px; font: inherit; }
.form button { justify-self: start; margin-top: 1rem; padding: .7rem
1.4rem; border: 0; border-radius: 999px; background: var(--brand);
color: #fff; font: inherit; }
.site-footer { text-align: center; padding: 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
h2 { scroll-margin-top: 4rem; }
```

Project 1121 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Port Said Seafood - Complete site</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main"><ul class="nav">	A block of navigation links; aria-label names it for screen readers.
Dishes About...	A hyperlink; href gives the destination.
<main id="main">	The unique content of this page; exactly one per page.
<section class="hero">	A thematic group of content, normally with its own heading.
Grilled fish straight from the boats	The main heading; only one per page.
Welcome to Port Said Seafood in Port Said.	A paragraph of text.

Line	What it does
Explore	A link styled as a button; it navigates, so it is a link and not a <button>.
Our dishes	Second-level heading for a section.
	Generic block container for grouping and layout.
<article class="card"><h3>Grilled sea bass</h3><p>With rice and sal...	A self-contained piece: card, post, product.
<article class="card"><h3>Shrimp tagine</h3><p>Tomato and garlic.<//...	Third-level heading, inside an h2 section.
<details><summary>Opening hours</summary><p>Saturday to Thursday 10...	Disclosure widget that can be opened and closed.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
<label for="n">Name</label><input id="n" name="name" required>	Text label for a control; for matches the control's id, or the label wraps the control.
<label for="e">Email</label><input id="e" name="email" type="email"...	Email field: validated automatically and shows the @ keyboard on phones.
<label for="m">Message</label><textarea id="m" name="message" rows=...	Multi-line text field.
<button>Send</button>	A clickable button; inside a form it submits by default.

Line	What it does
<footer class="site-footer"><p>© 2026 Port Said Seafood &middo...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #0e7490;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: #fff;	Background colour or image.
padding: .5rem;	Space inside the element between its border and content.
z-index: 100;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
align-items: center;	Centres items on the cross axis.
gap: .5rem 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-weight: 800;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
border-radius: 6px;	Rounds the corners.
.nav a:hover {	Applies while the pointer is over the element.
text-align: center;	Centres inline content such as text.
font-size: clamp(1.8rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
grid-template-columns: repeat(auto-fit, minmax(13rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	The line around the element: width, style and colour.
} summary { cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-top: 1px solid var(--line);	A top border used as an accent or separator.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.

Check your work

- Skip link appears on first Tab
- Anchor links land below the sticky header
- One h1
- Form fully labelled
- Passes the W3C validator

Exercises

1. Add smooth scrolling with scroll-behavior: smooth (respecting reduced motion).
2. Add an Arabic RTL version.
3. Split into multiple pages with a shared stylesheet.

Theme data for this project

Field	Value
Business	Port Said Seafood
Tagline	Grilled fish straight from the boats
City	Port Said
Owner	Sherif Wahba
Brand colour	#0e7490
Accent colour	#ecfeff
Offers	Grilled sea bass (320 EGP); Shrimp tagine (280 EGP); Calamari (190 EGP); Fish soup (120 EGP)

Project 1122: Complete one-page website for Delta Kids Library

Theme: Delta Kids Library (Tanta) | Level 3 | Files: index.html, styles.css

Brief

Combine everything into a single-page site: skip link, sticky header with anchor navigation, hero, offers grid, about with details, contact form and footer.

Learning goals

- Assemble a full page from components
- Use in-page anchor navigation with scroll-margin-top
- Provide a skip link

Elements and CSS used

HTML elements	CSS features
a.skip, header, nav, main, section, h1-h3, article, details, summary, form, label, input, textarea, button, footer	position: sticky, z-index, scroll-margin-top, grid auto-fit, clamp(), focus styles for skip link

Build guide

1. Write the skeleton with four sections that have ids.
2. Add the sticky header with links to those ids.
3. Add a skip link as the first element in body.
4. Style the hero, grid, about and form.
5. Add scroll-margin-top to h2 so anchors are not hidden by the header.

6. Validate the whole page and test keyboard navigation.

Project 1122: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Delta Kids Library - Complete site</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <a class="skip" href="#main">Skip to content</a>
  <header class="site-header">
    <a class="logo" href="index.html">Delta Kids Library</a>
    <nav aria-label="Main"><ul class="nav">
      <li><a href="#offers">Programmes</a></li><li><a
href="#about">About</a></li><li><a href="#contact">Contact</a></li>
    </ul></nav>
  </header>
  <main id="main">
    <section class="hero">
      <h1>Stories, reading clubs and homework help</h1>
      <p>Welcome to Delta Kids Library in Tanta.</p>
      <a class="btn" href="#offers">Explore</a>
    </section>
    <section id="offers" class="wrap">
      <h2>Our programmes</h2>
      <div class="grid">
        <article class="card"><h3>Story hour</h3><p>Ages 3 to 6,
Saturdays.</p><p class="price">Free</p></article>
        <article class="card"><h3>Reading club</h3><p>Ages 7 to 11.</
p><p class="price">50 EGP per month</p></article>
        <article class="card"><h3>Homework help</h3><p>Weekday
afternoons.</p><p class="price">Free</p></article>
        <article class="card"><h3>Summer challenge</h3><p>Read ten
books.</p><p class="price">Free</p></article>
      </div>
    </section>
    <section id="about" class="wrap about">
      <h2>About us</h2>
      <p>Founded by Ghada Kamel. Stories, reading clubs and homework
help.</p>
      <details><summary>Opening hours</summary><p>Saturday to
Thursday 10:00 to 22:00, Friday 14:00 to 22:00.</p></details>
    </section>
    <section id="contact" class="wrap">
      <h2>Contact</h2>
      <form action="/contact" method="post" class="form">
        <label for="n">Name</label><input id="n" name="name" required>
```

```
        <label for="e">Email</label><input id="e" name="email"
type="email" required>
        <label for="m">Message</label><textarea id="m" name="message"
rows="4" required></textarea>
        <button>Send</button>
      </form>
    </section>
  </main>
  <footer class="site-footer"><p>&copy; 2026 Delta Kids Library
&middot; <a href="#main">Back to top</a></p></footer>
</body>
</html>
```

Project 1122: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #ea580c; --accent: #fff7ed; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.skip { position: absolute; left: -999px; } .skip:focus { left: 1rem;
top: 1rem; background: #fff; padding: .5rem; z-index: 100; }
.site-header { position: sticky; top: 0; z-index: 10; display: flex;
flex-wrap: wrap; justify-content: space-between; align-items: center;
gap: .5rem 1rem; padding: .75rem 1rem; background: #fff; border-
bottom: 1px solid var(--line); }
.logo { font-weight: 800; color: var(--brand); text-decoration: none;
}
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { padding: .4rem .8rem; border-radius: 6px; text-decoration:
none; color: var(--ink); }
.nav a:hover { background: var(--accent); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(1.8rem, 5vw, 3rem); }
.btn { display: inline-block; padding: .7rem 1.4rem; border-radius:
999px; background: #fff; color: var(--brand); text-decoration: none;
font-weight: 700; }
.wrap { max-width: 60rem; margin: 0 auto; padding: 3rem 1rem; }
.grid { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(13rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
.price { font-weight: 700; color: var(--brand); }
.about { background: #fafafa; }
details { margin-top: 1rem; } summary { cursor: pointer; font-weight:
600; }
```

```
.form { display: grid; gap: .4rem; max-width: 30rem; }
.form label { font-weight: 600; margin-top: .6rem; }
.form input, .form textarea { padding: .6rem; border: 1px solid #bbb;
border-radius: 8px; font: inherit; }
.form button { justify-self: start; margin-top: 1rem; padding: .7rem
1.4rem; border: 0; border-radius: 999px; background: var(--brand);
color: #fff; font: inherit; }
.site-footer { text-align: center; padding: 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
h2 { scroll-margin-top: 4rem; }
```

Project 1122 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Delta Kids Library - Complete site</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main"><ul class="nav">	A block of navigation links; aria-label names it for screen readers.
Programmes <a href="#about">About...	A hyperlink; href gives the destination.
<main id="main">	The unique content of this page; exactly one per page.
<section class="hero">	A thematic group of content, normally with its own heading.
Stories, reading clubs and homework help	The main heading; only one per page.
Welcome to Delta Kids Library in Tanta.	A paragraph of text.

Line	What it does
Explore	A link styled as a button; it navigates, so it is a link and not a <button>.
Our programmes	Second-level heading for a section.
	Generic block container for grouping and layout.
<article class="card"> Story hour Ages 3 to 6, Saturdays....	A self-contained piece: card, post, product.
<article class="card"> Reading club Ages 7 to 11. <p c...	Third-level heading, inside an h2 section.
<details><summary>Opening hours</summary> Saturday to Thursday 10...	Disclosure widget that can be opened and closed.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
<label for="n">Name</label><input id="n" name="name" required>	Text label for a control; for matches the control's id, or the label wraps the control.
<label for="e">Email</label><input id="e" name="email" type="email"...	Email field: validated automatically and shows the @ keyboard on phones.
<label for="m">Message</label><textarea id="m" name="message" rows=...	Multi-line text field.
<button>Send</button>	A clickable button; inside a form it submits by default.

Line	What it does
<footer class="site-footer"><p>© 2026 Delta Kids Library &midd...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #ea580c;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: #fff;	Background colour or image.
padding: .5rem;	Space inside the element between its border and content.
z-index: 100;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
align-items: center;	Centres items on the cross axis.
gap: .5rem 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-weight: 800;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
border-radius: 6px;	Rounds the corners.
.nav a:hover {	Applies while the pointer is over the element.
text-align: center;	Centres inline content such as text.
font-size: clamp(1.8rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
grid-template-columns: repeat(auto-fit, minmax(13rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	The line around the element: width, style and colour.
} summary { cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-top: 1px solid var(--line);	A top border used as an accent or separator.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.

Check your work

- Skip link appears on first Tab
- Anchor links land below the sticky header
- One h1
- Form fully labelled
- Passes the W3C validator

Exercises

1. Add smooth scrolling with scroll-behavior: smooth (respecting reduced motion).
2. Add an Arabic RTL version.
3. Split into multiple pages with a shared stylesheet.

Theme data for this project

Field	Value
Business	Delta Kids Library
Tagline	Stories, reading clubs and homework help
City	Tanta
Owner	Ghada Kamel
Brand colour	#ea580c
Accent colour	#fff7ed
Offers	Story hour (Free); Reading club (50 EGP per month); Homework help (Free); Summer challenge (Free)

Project 1123: Complete one-page website for Nubian Guest House

Theme: Nubian Guest House (Aswan) | Level 3 | Files: index.html, styles.css

Brief

Combine everything into a single-page site: skip link, sticky header with anchor navigation, hero, offers grid, about with details, contact form and footer.

Learning goals

- Assemble a full page from components
- Use in-page anchor navigation with scroll-margin-top
- Provide a skip link

Elements and CSS used

HTML elements	CSS features
a.skip, header, nav, main, section, h1-h3, article, details, summary, form, label, input, textarea, button, footer	position: sticky, z-index, scroll-margin-top, grid auto-fit, clamp(), focus styles for skip link

Build guide

1. Write the skeleton with four sections that have ids.
2. Add the sticky header with links to those ids.
3. Add a skip link as the first element in body.
4. Style the hero, grid, about and form.
5. Add scroll-margin-top to h2 so anchors are not hidden by the header.

6. Validate the whole page and test keyboard navigation.

Project 1123: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Nubian Guest House - Complete site</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <a class="skip" href="#main">Skip to content</a>
  <header class="site-header">
    <a class="logo" href="index.html">Nubian Guest House</a>
    <nav aria-label="Main"><ul class="nav">
      <li><a href="#offers">Rooms</a></li><li><a href="#about">About</
a></li><li><a href="#contact">Contact</a></li>
    </ul></nav>
  </header>
  <main id="main">
    <section class="hero">
      <h1>Colourful rooms on the west bank of the Nile</h1>
      <p>Welcome to Nubian Guest House in Aswan.</p>
      <a class="btn" href="#offers">Explore</a>
    </section>
    <section id="offers" class="wrap">
      <h2>Our rooms</h2>
      <div class="grid">
        <article class="card"><h3>Garden room</h3><p>Double bed,
shared terrace.</p><p class="price">900 EGP</p></article>
        <article class="card"><h3>Nile view suite</h3><p>Balcony and
breakfast.</p><p class="price">1800 EGP</p></article>
        <article class="card"><h3>Family room</h3><p>Sleeps four.</
p><p class="price">1500 EGP</p></article>
        <article class="card"><h3>Rooftop dorm</h3><p>Budget beds.</
p><p class="price">300 EGP</p></article>
      </div>
    </section>
    <section id="about" class="wrap about">
      <h2>About us</h2>
      <p>Founded by Fatma Hassan. Colourful rooms on the west bank of
the Nile.</p>
      <details><summary>Opening hours</summary><p>Saturday to
Thursday 10:00 to 22:00, Friday 14:00 to 22:00.</p></details>
    </section>
    <section id="contact" class="wrap">
      <h2>Contact</h2>
      <form action="/contact" method="post" class="form">
        <label for="n">Name</label><input id="n" name="name" required>
```

```
        <label for="e">Email</label><input id="e" name="email"
type="email" required>
        <label for="m">Message</label><textarea id="m" name="message"
rows="4" required></textarea>
        <button>Send</button>
      </form>
    </section>
  </main>
  <footer class="site-footer"><p>&copy; 2026 Nubian Guest House
&middot; <a href="#main">Back to top</a></p></footer>
</body>
</html>
```

Project 1123: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #b45309; --accent: #fffbeb; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.skip { position: absolute; left: -999px; } .skip:focus { left: 1rem;
top: 1rem; background: #fff; padding: .5rem; z-index: 100; }
.site-header { position: sticky; top: 0; z-index: 10; display: flex;
flex-wrap: wrap; justify-content: space-between; align-items: center;
gap: .5rem 1rem; padding: .75rem 1rem; background: #fff; border-
bottom: 1px solid var(--line); }
.logo { font-weight: 800; color: var(--brand); text-decoration: none;
}
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { padding: .4rem .8rem; border-radius: 6px; text-decoration:
none; color: var(--ink); }
.nav a:hover { background: var(--accent); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(1.8rem, 5vw, 3rem); }
.btn { display: inline-block; padding: .7rem 1.4rem; border-radius:
999px; background: #fff; color: var(--brand); text-decoration: none;
font-weight: 700; }
.wrap { max-width: 60rem; margin: 0 auto; padding: 3rem 1rem; }
.grid { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(13rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
.price { font-weight: 700; color: var(--brand); }
.about { background: #fafafa; }
details { margin-top: 1rem; } summary { cursor: pointer; font-weight:
600; }
```

```
.form { display: grid; gap: .4rem; max-width: 30rem; }
.form label { font-weight: 600; margin-top: .6rem; }
.form input, .form textarea { padding: .6rem; border: 1px solid #bbb;
border-radius: 8px; font: inherit; }
.form button { justify-self: start; margin-top: 1rem; padding: .7rem
1.4rem; border: 0; border-radius: 999px; background: var(--brand);
color: #fff; font: inherit; }
.site-footer { text-align: center; padding: 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
h2 { scroll-margin-top: 4rem; }
```

Project 1123 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Nubian Guest House - Complete site</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main"><ul class="nav">	A block of navigation links; aria-label names it for screen readers.
Rooms About<…	A hyperlink; href gives the destination.
<main id="main">	The unique content of this page; exactly one per page.
<section class="hero">	A thematic group of content, normally with its own heading.
Colourful rooms on the west bank of the Nile	The main heading; only one per page.
Welcome to Nubian Guest House in Aswan.	A paragraph of text.

Line	What it does
Explore	A link styled as a button; it navigates, so it is a link and not a <button>.
Our rooms	Second-level heading for a section.
	Generic block container for grouping and layout.
<article class="card"><h3>Garden room</h3><p>Double bed, shared ter...	A self-contained piece: card, post, product.
<article class="card"><h3>Nile view suite</h3><p>Balcony and breakf...	Third-level heading, inside an h2 section.
<details><summary>Opening hours</summary><p>Saturday to Thursday 10...	Disclosure widget that can be opened and closed.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
<label for="n">Name</label><input id="n" name="name" required>	Text label for a control; for matches the control's id, or the label wraps the control.
<label for="e">Email</label><input id="e" name="email" type="email"...	Email field: validated automatically and shows the @ keyboard on phones.
<label for="m">Message</label><textarea id="m" name="message" rows=...	Multi-line text field.
<button>Send</button>	A clickable button; inside a form it submits by default.

Line	What it does
<footer class="site-footer"><p>© 2026 Nubian Guest House &midd...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #b45309;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: #fff;	Background colour or image.
padding: .5rem;	Space inside the element between its border and content.
z-index: 100;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
align-items: center;	Centres items on the cross axis.
gap: .5rem 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-weight: 800;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
border-radius: 6px;	Rounds the corners.
.nav a:hover {	Applies while the pointer is over the element.
text-align: center;	Centres inline content such as text.
font-size: clamp(1.8rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
grid-template-columns: repeat(auto-fit, minmax(13rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	The line around the element: width, style and colour.
} summary { cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-top: 1px solid var(--line);	A top border used as an accent or separator.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.

Check your work

- Skip link appears on first Tab
- Anchor links land below the sticky header
- One h1
- Form fully labelled
- Passes the W3C validator

Exercises

1. Add smooth scrolling with scroll-behavior: smooth (respecting reduced motion).
2. Add an Arabic RTL version.
3. Split into multiple pages with a shared stylesheet.

Theme data for this project

Field	Value
Business	Nubian Guest House
Tagline	Colourful rooms on the west bank of the Nile
City	Aswan
Owner	Fatma Hassan
Brand colour	#b45309
Accent colour	#fffbeb
Offers	Garden room (900 EGP); Nile view suite (1800 EGP); Family room (1500 EGP); Rooftop dorm (300 EGP)

Project 1124: Complete one-page website for Ismailia Cycling Store

Theme: Ismailia Cycling Store (Ismailia) | Level 3 | Files: index.html, styles.css

Brief

Combine everything into a single-page site: skip link, sticky header with anchor navigation, hero, offers grid, about with details, contact form and footer.

Learning goals

- Assemble a full page from components
- Use in-page anchor navigation with scroll-margin-top
- Provide a skip link

Elements and CSS used

HTML elements	CSS features
a.skip, header, nav, main, section, h1-h3, article, details, summary, form, label, input, textarea, button, footer	position: sticky, z-index, scroll-margin-top, grid auto-fit, clamp(), focus styles for skip link

Build guide

1. Write the skeleton with four sections that have ids.
2. Add the sticky header with links to those ids.
3. Add a skip link as the first element in body.
4. Style the hero, grid, about and form.
5. Add scroll-margin-top to h2 so anchors are not hidden by the header.

6. Validate the whole page and test keyboard navigation.

Project 1124: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Ismailia Cycling Store - Complete site</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <a class="skip" href="#main">Skip to content</a>
  <header class="site-header">
    <a class="logo" href="index.html">Ismailia Cycling Store</a>
    <nav aria-label="Main"><ul class="nav">
      <li><a href="#offers">Bikes</a></li><li><a href="#about">About</
a></li><li><a href="#contact">Contact</a></li>
    </ul></nav>
  </header>
  <main id="main">
    <section class="hero">
      <h1>Bikes, parts and Friday group rides</h1>
      <p>Welcome to Ismailia Cycling Store in Ismailia.</p>
      <a class="btn" href="#offers">Explore</a>
    </section>
    <section id="offers" class="wrap">
      <h2>Our bikes</h2>
      <div class="grid">
        <article class="card"><h3>City bike</h3><p>Seven gears,
basket.</p><p class="price">6500 EGP</p></article>
        <article class="card"><h3>Mountain bike</h3><p>Front
suspension.</p><p class="price">11000 EGP</p></article>
        <article class="card"><h3>Kids bike</h3><p>20 inch wheels.</
p><p class="price">3200 EGP</p></article>
        <article class="card"><h3>Tune-up</h3><p>Brakes, gears and
true wheels.</p><p class="price">250 EGP</p></article>
      </div>
    </section>
    <section id="about" class="wrap about">
      <h2>About us</h2>
      <p>Founded by Bassem Adly. Bikes, parts and Friday group rides.
</p>
      <details><summary>Opening hours</summary><p>Saturday to
Thursday 10:00 to 22:00, Friday 14:00 to 22:00.</p></details>
    </section>
    <section id="contact" class="wrap">
      <h2>Contact</h2>
      <form action="/contact" method="post" class="form">
        <label for="n">Name</label><input id="n" name="name" required>
```

```
        <label for="e">Email</label><input id="e" name="email"
type="email" required>
        <label for="m">Message</label><textarea id="m" name="message"
rows="4" required></textarea>
        <button>Send</button>
      </form>
    </section>
  </main>
  <footer class="site-footer"><p>&copy; 2026 Ismailia Cycling Store
&middot; <a href="#main">Back to top</a></p></footer>
</body>
</html>
```

Project 1124: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #dc2626; --accent: #fef2f2; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.skip { position: absolute; left: -999px; } .skip:focus { left: 1rem;
top: 1rem; background: #fff; padding: .5rem; z-index: 100; }
.site-header { position: sticky; top: 0; z-index: 10; display: flex;
flex-wrap: wrap; justify-content: space-between; align-items: center;
gap: .5rem 1rem; padding: .75rem 1rem; background: #fff; border-
bottom: 1px solid var(--line); }
.logo { font-weight: 800; color: var(--brand); text-decoration: none;
}
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { padding: .4rem .8rem; border-radius: 6px; text-decoration:
none; color: var(--ink); }
.nav a:hover { background: var(--accent); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(1.8rem, 5vw, 3rem); }
.btn { display: inline-block; padding: .7rem 1.4rem; border-radius:
999px; background: #fff; color: var(--brand); text-decoration: none;
font-weight: 700; }
.wrap { max-width: 60rem; margin: 0 auto; padding: 3rem 1rem; }
.grid { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(13rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
.price { font-weight: 700; color: var(--brand); }
.about { background: #fafafa; }
details { margin-top: 1rem; } summary { cursor: pointer; font-weight:
600; }
```

```
.form { display: grid; gap: .4rem; max-width: 30rem; }
.form label { font-weight: 600; margin-top: .6rem; }
.form input, .form textarea { padding: .6rem; border: 1px solid #bbb;
border-radius: 8px; font: inherit; }
.form button { justify-self: start; margin-top: 1rem; padding: .7rem
1.4rem; border: 0; border-radius: 999px; background: var(--brand);
color: #fff; font: inherit; }
.site-footer { text-align: center; padding: 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
h2 { scroll-margin-top: 4rem; }
```

Project 1124 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Ismailia Cycling Store - Complete site</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main"><ul class="nav">	A block of navigation links; aria-label names it for screen readers.
Bikes About<...	A hyperlink; href gives the destination.
<main id="main">	The unique content of this page; exactly one per page.
<section class="hero">	A thematic group of content, normally with its own heading.
Bikes, parts and Friday group rides	The main heading; only one per page.
Welcome to Ismailia Cycling Store in Ismailia.	A paragraph of text.

Line	What it does
Explore	A link styled as a button; it navigates, so it is a link and not a <button>.
Our bikes	Second-level heading for a section.
	Generic block container for grouping and layout.
<article class="card"> City bike Seven gears, basket. …	A self-contained piece: card, post, product.
<article class="card"> Mountain bike Front suspension.</p…	Third-level heading, inside an h2 section.
<details><summary>Opening hours</summary> Saturday to Thursday 10…	Disclosure widget that can be opened and closed.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
<label for="n">Name</label><input id="n" name="name" required>	Text label for a control; for matches the control's id, or the label wraps the control.
<label for="e">Email</label><input id="e" name="email" type="email"…	Email field: validated automatically and shows the @ keyboard on phones.
<label for="m">Message</label><textarea id="m" name="message" rows=…	Multi-line text field.
<button>Send</button>	A clickable button; inside a form it submits by default.

Line	What it does
<footer class="site-footer"><p>© 2026 Ismailia Cycling Store &...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #dc2626;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: #fff;	Background colour or image.
padding: .5rem;	Space inside the element between its border and content.
z-index: 100;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
align-items: center;	Centres items on the cross axis.
gap: .5rem 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-weight: 800;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
border-radius: 6px;	Rounds the corners.
.nav a:hover {	Applies while the pointer is over the element.
text-align: center;	Centres inline content such as text.
font-size: clamp(1.8rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
grid-template-columns: repeat(auto-fit, minmax(13rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	The line around the element: width, style and colour.
} summary { cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-top: 1px solid var(--line);	A top border used as an accent or separator.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.

Check your work

- Skip link appears on first Tab
- Anchor links land below the sticky header
- One h1
- Form fully labelled
- Passes the W3C validator

Exercises

1. Add smooth scrolling with scroll-behavior: smooth (respecting reduced motion).
2. Add an Arabic RTL version.
3. Split into multiple pages with a shared stylesheet.

Theme data for this project

Field	Value
Business	Ismailia Cycling Store
Tagline	Bikes, parts and Friday group rides
City	Ismailia
Owner	Bassem Adly
Brand colour	#dc2626
Accent colour	#fef2f2
Offers	City bike (6500 EGP); Mountain bike (11000 EGP); Kids bike (3200 EGP); Tune-up (250 EGP)

Project 1125: Complete one-page website for Minya Coding Club

Theme: Minya Coding Club (Minya) | Level 3 | Files: index.html, styles.css

Brief

Combine everything into a single-page site: skip link, sticky header with anchor navigation, hero, offers grid, about with details, contact form and footer.

Learning goals

- Assemble a full page from components
- Use in-page anchor navigation with scroll-margin-top
- Provide a skip link

Elements and CSS used

HTML elements	CSS features
a.skip, header, nav, main, section, h1-h3, article, details, summary, form, label, input, textarea, button, footer	position: sticky, z-index, scroll-margin-top, grid auto-fit, clamp(), focus styles for skip link

Build guide

1. Write the skeleton with four sections that have ids.
2. Add the sticky header with links to those ids.
3. Add a skip link as the first element in body.
4. Style the hero, grid, about and form.
5. Add scroll-margin-top to h2 so anchors are not hidden by the header.

6. Validate the whole page and test keyboard navigation.

Project 1125: index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Minya Coding Club - Complete site</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>
  <a class="skip" href="#main">Skip to content</a>
  <header class="site-header">
    <a class="logo" href="index.html">Minya Coding Club</a>
    <nav aria-label="Main"><ul class="nav">
      <li><a href="#offers">Workshops</a></li><li><a
href="#about">About</a></li><li><a href="#contact">Contact</a></li>
    </ul></nav>
  </header>
  <main id="main">
    <section class="hero">
      <h1>Free weekend coding for teenagers</h1>
      <p>Welcome to Minya Coding Club in Minya.</p>
      <a class="btn" href="#offers">Explore</a>
    </section>
    <section id="offers" class="wrap">
      <h2>Our workshops</h2>
      <div class="grid">
        <article class="card"><h3>HTML weekend</h3><p>Build your
first page.</p><p class="price">Free</p></article>
        <article class="card"><h3>CSS art</h3><p>Draw with code.</
p><p class="price">Free</p></article>
        <article class="card"><h3>Scratch games</h3><p>Ages 10 to 13.
</p><p class="price">Free</p></article>
        <article class="card"><h3>Hackathon</h3><p>48 hours, teams of
four.</p><p class="price">Free</p></article>
      </div>
    </section>
    <section id="about" class="wrap about">
      <h2>About us</h2>
      <p>Founded by Youssef Hany. Free weekend coding for teenagers.</
p>
      <details><summary>Opening hours</summary><p>Saturday to
Thursday 10:00 to 22:00, Friday 14:00 to 22:00.</p></details>
    </section>
    <section id="contact" class="wrap">
      <h2>Contact</h2>
      <form action="/contact" method="post" class="form">
        <label for="n">Name</label><input id="n" name="name" required>
```

```
        <label for="e">Email</label><input id="e" name="email"
type="email" required>
        <label for="m">Message</label><textarea id="m" name="message"
rows="4" required></textarea>
        <button>Send</button>
      </form>
    </section>
  </main>
  <footer class="site-footer"><p>&copy; 2026 Minya Coding Club
&middot; <a href="#main">Back to top</a></p></footer>
</body>
</html>
```

Project 1125: styles.css

```
*, *::before, *::after { box-sizing: border-box; }
:root { --brand: #2563eb; --accent: #eff6ff; --ink: #1b2431; --muted:
#5b6472; --line: #d9d9d9; }
body { margin: 0; font-family: system-ui, Arial, sans-serif; line-
height: 1.6; color: var(--ink); }
.skip { position: absolute; left: -999px; } .skip:focus { left: 1rem;
top: 1rem; background: #fff; padding: .5rem; z-index: 100; }
.site-header { position: sticky; top: 0; z-index: 10; display: flex;
flex-wrap: wrap; justify-content: space-between; align-items: center;
gap: .5rem 1rem; padding: .75rem 1rem; background: #fff; border-
bottom: 1px solid var(--line); }
.logo { font-weight: 800; color: var(--brand); text-decoration: none;
}
.nav { display: flex; gap: .25rem; list-style: none; margin: 0;
padding: 0; }
.nav a { padding: .4rem .8rem; border-radius: 6px; text-decoration:
none; color: var(--ink); }
.nav a:hover { background: var(--accent); }
.hero { background: var(--brand); color: #fff; text-align: center;
padding: 4rem 1rem; }
.hero h1 { margin: 0 0 .5rem; font-size: clamp(1.8rem, 5vw, 3rem); }
.btn { display: inline-block; padding: .7rem 1.4rem; border-radius:
999px; background: #fff; color: var(--brand); text-decoration: none;
font-weight: 700; }
.wrap { max-width: 60rem; margin: 0 auto; padding: 3rem 1rem; }
.grid { display: grid; gap: 1rem; grid-template-columns: repeat(auto-
fit, minmax(13rem, 1fr)); }
.card { background: var(--accent); padding: 1.25rem; border-radius:
12px; }
.card h3 { margin-top: 0; }
.price { font-weight: 700; color: var(--brand); }
.about { background: #fafafa; }
details { margin-top: 1rem; } summary { cursor: pointer; font-weight:
600; }
```

```
.form { display: grid; gap: .4rem; max-width: 30rem; }
.form label { font-weight: 600; margin-top: .6rem; }
.form input, .form textarea { padding: .6rem; border: 1px solid #bbb;
border-radius: 8px; font: inherit; }
.form button { justify-self: start; margin-top: 1rem; padding: .7rem
1.4rem; border: 0; border-radius: 999px; background: var(--brand);
color: #fff; font: inherit; }
.site-footer { text-align: center; padding: 1.5rem; border-top: 1px
solid var(--line); color: var(--muted); }
h2 { scroll-margin-top: 4rem; }
```

Project 1125 explained line by line

The important lines of index.html

Line	What it does
<!DOCTYPE html>	Declares modern HTML so the browser renders in standards mode.
<html lang="en">	Root element; lang tells screen readers and search engines the page language.
<meta charset="utf-8">	Character encoding: makes Arabic, accents and symbols display correctly.
<meta name="viewport" content="width=device-width, initial-scale=1">	Makes the page use the real device width on phones.
<title>Minya Coding Club - Complete site</title>	Text shown in the browser tab and search results.
<link rel="stylesheet" href="styles.css">	Loads the external CSS file styles.css.
<header class="site-header">	Introductory content: logo, title, navigation.
<nav aria-label="Main"><ul class="nav">	A block of navigation links; aria-label names it for screen readers.
Workshops <a href="#about">About<...	A hyperlink; href gives the destination.
<main id="main">	The unique content of this page; exactly one per page.
<section class="hero">	A thematic group of content, normally with its own heading.
Free weekend coding for teenagers	The main heading; only one per page.
Welcome to Minya Coding Club in Minya.	A paragraph of text.

Line	What it does
Explore	A link styled as a button; it navigates, so it is a link and not a <button>.
Our workshops	Second-level heading for a section.
	Generic block container for grouping and layout.
<article class="card"> HTML weekend Build your first page...	A self-contained piece: card, post, product.
<article class="card"> CSS art Draw with code. <p clas...	Third-level heading, inside an h2 section.
<details><summary>Opening hours</summary> Saturday to Thursday 10...	Disclosure widget that can be opened and closed.
<form action="/contact" method="post" class="form">	A form; action is where the data goes, method how it is sent.
<label for="n">Name</label><input id="n" name="name" required>	Text label for a control; for matches the control's id, or the label wraps the control.
<label for="e">Email</label><input id="e" name="email" type="email"...	Email field: validated automatically and shows the @ keyboard on phones.
<label for="m">Message</label><textarea id="m" name="message" rows=...	Multi-line text field.
<button>Send</button>	A clickable button; inside a form it submits by default.

Line	What it does
<footer class="site-footer"><p>© 2026 Minya Coding Club &middo...	Footer of the page or of a section.

The important declarations of styles.css

Declaration	What it does
*, *::before, *::after {	Generated content inserted before the element's content (decorations, numbers, lines).
box-sizing: border-box;	Width and height include padding and border, which makes sizing predictable.
:root {	Custom properties (variables) defined on the root so every element can use them.
--brand: #2563eb;	The brand colour variable; change it once and every use follows.
margin: 0;	Space outside the element.
font-family: system-ui, Arial, sans-serif;	The typeface stack: preferred font first, fallbacks after.
line-height: 1.6;	Space between lines; 1.5 to 1.7 is comfortable for body text.
color: var(--ink);	Text colour.
position: absolute;	Removes the element from flow and positions it relative to the nearest positioned ancestor.
background: #fff;	Background colour or image.
padding: .5rem;	Space inside the element between its border and content.
z-index: 100;	Stacking order for positioned elements; higher is on top.

Declaration	What it does
position: sticky;	Scrolls normally until it reaches the given offset, then sticks.
display: flex;	Turns the element into a flex container (one-dimensional layout).
flex-wrap: wrap;	Allows flex items to move to a new line when they do not fit.
justify-content: space-between;	Spreads items so the first touches the start and the last the end.
align-items: center;	Centres items on the cross axis.
gap: .5rem 1rem;	Space between grid or flex items without extra margins.
border-bottom: 1px solid var(--line);	A bottom border used as a separator line.
font-weight: 800;	Thickness of the text.
text-decoration: none;	Removes the underline from links.
list-style: none;	Removes bullets or numbers from a list.
border-radius: 6px;	Rounds the corners.
.nav a:hover {	Applies while the pointer is over the element.
text-align: center;	Centres inline content such as text.
font-size: clamp(1.8rem, 5vw, 3rem);	A fluid value between a minimum and a maximum, based on the middle expression.
display: inline-block;	Flows in text but accepts width, height and vertical padding.
border-radius: 999px;	Fully rounded pill shape.
max-width: 60rem;	Limits how wide the element can grow, keeping lines readable.

Declaration	What it does
margin: 0 auto;	Centres a block horizontally: zero top/bottom, automatic left/right.
display: grid;	Turns the element into a grid container.
grid-template-columns: repeat(auto-fit, minmax(13rem, 1fr));	Defines the columns of the grid.
border-radius: 12px;	The line around the element: width, style and colour.
} summary { cursor: pointer;	Shows the hand cursor to indicate something clickable.
border: 1px solid #bbb;	Changes the visual order of a flex item without changing the source.
font: inherit;	Makes form controls use the page font instead of the browser default.
border: 0;	Removes the default border (for example on an iframe or button).
border-top: 1px solid var(--line);	A top border used as an accent or separator.
scroll-margin-top: 4rem;	Leaves room above an anchor target so a sticky header does not cover it.

Check your work

- Skip link appears on first Tab
- Anchor links land below the sticky header
- One h1
- Form fully labelled
- Passes the W3C validator

Exercises

1. Add smooth scrolling with scroll-behavior: smooth (respecting reduced motion).
2. Add an Arabic RTL version.
3. Split into multiple pages with a shared stylesheet.

Theme data for this project

Field	Value
Business	Minya Coding Club
Tagline	Free weekend coding for teenagers
City	Minya
Owner	Youssef Hany
Brand colour	#2563eb
Accent colour	#eff6ff
Offers	HTML weekend (Free); CSS art (Free); Scratch games (Free); Hackathon (Free)