



# Features and Scale Space


Chetan Arora

Disclaimer: The contents of these slides are taken from various publicly available resources such as research papers, talks and lectures. To be used for the purpose of classroom teaching, and academic dissemination only.




# Harris Corner Detector: Invariances

- Translation Invariant?



- Rotation Invariant?



- Scale Invariant?

- Illumination Invariant?

# **Image Pyramids**



# Recall: Cascaded Convolutions

$$\begin{bmatrix} 1 & 1 \end{bmatrix}^n$$

$$\begin{bmatrix} 1 & 1 \end{bmatrix}$$

$$\begin{bmatrix} 1 & 2 & 1 \end{bmatrix}$$

$$\begin{bmatrix} 1 & 3 & 3 & 1 \end{bmatrix}$$

$$\begin{bmatrix} 1 & 4 & 6 & 4 & 1 \end{bmatrix}$$



# Interesting Aside

$$\begin{bmatrix} 1 & 1 \end{bmatrix}^n$$

$$\begin{bmatrix} 1 & 1 \end{bmatrix}$$

$$\begin{bmatrix} 1 & 2 & 1 \end{bmatrix}$$

$$\begin{bmatrix} 1 & 3 & 3 & 1 \end{bmatrix}$$

$$\begin{bmatrix} 1 & 4 & 6 & 4 & 1 \end{bmatrix}$$

$$a_{nr} = \frac{n!}{r! (n-r)!} = \binom{n}{r}$$

$n$  = number of elements in the filter minus 1

$r$  = position of element in the filters (starting at 0)



# Interesting Aside


$$\frac{1}{2} [1 \quad 1]^n$$

$$\frac{1}{2} [1 \quad 1]$$

$$\frac{1}{4} [1 \quad 2 \quad 1]$$

$$\frac{1}{8} [1 \quad 3 \quad 3 \quad 1]$$

$$\frac{1}{16} [1 \quad 4 \quad 6 \quad 4 \quad 1]$$



$$\frac{1}{4} [1 \quad 2 \quad 1]$$

approximates Gaussian with  $\sigma = \frac{1}{\sqrt{2}}$

$$\frac{1}{16} [1 \quad 4 \quad 6 \quad 4 \quad 1]$$

approximates Gaussian with  $\sigma = 1$

**Why?**



# Interesting Aside

## Fun facts:

- The distribution of the sum of two random variables  $X + Y$  is the convolution of their two distributions. **Why?**
- Recall Convolution:  $(f * g)(z) = \int_{-\infty}^{\infty} f(x)g(z - x)dx$
- $z = x + y \Rightarrow y = z - x$
- $p_{X+Y}(z) = \int_{-\infty}^{\infty} p_y(z - x) p_x(x) dx$



# Interesting Aside

$X: G_{\sigma_1}(x)$  and  $Y: G_{\sigma_2}(y)$

$$G_\sigma(x + y) = (G_{\sigma_1} * G_{\sigma_2})(z)$$

$$\sigma^2 = \sigma_1^2 + \sigma_2^2$$

$$\frac{1}{4} [1 \quad 2 \quad 1]$$

approximates Gaussian with  $\sigma = \frac{1}{\sqrt{2}}$

$$\frac{1}{16} [1 \quad 4 \quad 6 \quad 4 \quad 1]$$

approximates Gaussian with  $\sigma = 1$



Chetan Arora

Department of Computer Science and Engineering, IIT Delhi

# Gaussian Smoothing at Different Scales



$$\sigma = 3$$




$$\sigma = 10$$



# Subsampling


- A large amount of smoothing reduces the rate of change of neighboring pixels (frequency of features) in the image.
- We do not need to keep all the pixels around. Can progressively reduce the number of pixels as we smooth more and more.
- Leads to a “pyramid” representation if we ‘subsample’ at each level.





# Gaussian Pyramid

- Synthesis: Smooth image with a Gaussian. Downsample. Repeat.











Chetan Arora

Department of Computer Science and Engineering, IIT Delhi

# Smaller Image → Lower Resolution





# Interesting Aside

- Subsampling without prior blurring is a bad idea (introduces aliasing)!



Downsampled



Blurred and  
Downsampled



# Interesting Aside

- Subsampling without prior blurring is a bad idea (introduces aliasing)!



Downsampled

Blurred and  
Downsampled



# Interesting Aside

- Subsampling without prior blurring is a bad idea (introduces aliasing)!



Downsampled

Blurred and  
Downsampled



# What is Aliasing?

- A digital photograph of a striped shirt, or a brick wall (shown above) with high frequencies, with small distance between the stripes/bricks, can cause aliasing of the shirt/wall when it is sampled by the camera's image sensor. The aliasing appears as a moiré pattern.
- The “solution” to higher sampling in the spatial domain for this case would be to move closer to the shirt, use a higher resolution sensor, or to optically blur the image before acquiring it with the sensor.





Image source: Wikipedia




# What is Aliasing?



The samples of two sine waves can be identical when at least one of them is at a frequency above half the sample rate.




# Constructing Gaussian Pyramid





# Upsampling




**How to fill in the empty values?**

- Interpolation:
  - Initially set empty pixels to zero
  - Convolve upsampled image with a Gaussian filter.
  - E.g. 5x5 kernel with sigma = 1.
  - Must also multiply by 4. **Why?**



# Scale Space

- Different scales are appropriate for describing different objects in the image
- We do not know the correct scale/size ahead of time.
- Image Pyramids are a useful representation for multi-resolution analysis of images.



# **Laplacian of Gaussian (LoG)**



# Recall: Second Derivative

$$\frac{\partial}{\partial x} f(i, j) \cong f(i, j) - f(i - 1, j)$$

$$\frac{\partial}{\partial y} f(i, j) \cong f(i, j) - f(i, j - 1)$$

$$\frac{\partial^2}{\partial x^2} f(i, j) \cong \frac{\partial}{\partial x} f(i + 1, j) - \frac{\partial}{\partial x} f(i, j)$$

$$= f(i - 1, j) + f(i + 1, j) - 2f(i, j)$$

$$\begin{bmatrix} 1 & -1 \end{bmatrix}$$

$$\begin{bmatrix} 1 \\ -1 \end{bmatrix}$$

$$\begin{bmatrix} 1 & -1 \end{bmatrix} * \begin{bmatrix} 1 & -1 \end{bmatrix}$$

$$= [1 \quad -2 \quad 1]$$



# Recall: Laplacian

Equation:



$$\nabla^2 f = \frac{\partial}{\partial x^2} f + \frac{\partial}{\partial y^2} f$$

Convolution:

$$[1 \quad -2 \quad 1] + \begin{bmatrix} 1 \\ -2 \\ 1 \end{bmatrix} = \begin{bmatrix} 0 & 1 & 0 \\ 1 & -4 & 1 \\ 0 & 1 & 0 \end{bmatrix}$$



# Recall: Effect of Noise on Derivatives





# Recall: Zero Crossing After Smoothing

Input

Laplacian after increasingly strong smoothing



Image → Gaussian → Laplacian → Output



# LoG Filter


Image  $\rightarrow$  Gaussian  $\rightarrow$  Laplacian  $\rightarrow$  Output

$$\nabla^2(f * G)(x) \equiv (\nabla^2 G * f)(x)$$


Laplacian of Gaussian  
(LoG) Filter




# LoG Filter



$$G(x)$$




$$G'(x)$$




$$-G''(x)$$



# LoG Filter




2D  
→





# Blob Detection using LoG

- How can an edge finder be used to find blobs in an image?




Lindeberg. IJCV 1998.  
Feature detection with automatic scale selection



# Blob Detection using LoG


## Key Idea

- Cross correlation with a flipped filter (in a convolution) can be viewed as comparing a little “picture” of what you want to find against all local regions in the image.



**Maximum response**

Dark blob on light background




**Maximum response**

Vertical edge; lighter on left




# Blob Detection using LoG






# Blob Detection using LoG

- Scale of blob (size ; radius in pixels) is determined by the sigma parameter of the LoG filter.



$\text{LoG } \sigma = 2$




$\text{LoG } \sigma = 10$



Chetan Arora



Department of Computer Science and Engineering, IIT Delhi

# Local Scale Space Maxima





# Local Scale Space Maxima





Characteristic scale



# Blob Detection using LoG

- Blobs are detected as local extrema in space and scale, within the LoG scale-space volume.




Lindeberg. IJCV 1998.  
Feature detection with automatic scale selection



Chetan Arora

Department of Computer Science and Engineering, IIT Delhi

# Gesture Recognition via Blob Detection




Lars Bretzner, Ivan Laptev, and Tony Lindeberg. Automatic Face and Gesture Recognition, 2002  
Hand Gesture Recognition using Multi-Scale Colour Features, Hierarchical Models and Particle Filtering



# LoG → DoG


- LoG can be approximate by a Difference of two Gaussians (DoG) at different scales.





# Laplacian Pyramids

Store only these




# **Scale Invariant Detectors**



# Scale Invariant Detectors


## Harris-Laplacian

- Find local maximum of:
  - Harris corner detector in space (image coordinates)
  - Select points which are also maxima of Laplacian in scale





## SIFT

- Find local maximum of:
  - Difference of Gaussians in space and scale






# Difference of Gaussians





# Scale Space Extrema

- Choose all extrema within  $3 \times 3 \times 3$  neighborhood.






**X is selected if it's response is larger or smaller than all 26 neighbors**

# **Rotation Invariant Matching (Descriptors)**




# What is Rotation Invariant Matching?





# Rotation Invariance: Key Idea

- We are given a keypoint and its scale from DoG
- Select a characteristic orientation for the keypoint (based on the most prominent gradient there)
- Describe all features **relative** to this orientation
- Causes descriptor to be rotation invariant!
  - If the keypoint is rotated in another image, the descriptor will be the same, since it is **relative** to the characteristic orientation






# SIFT Descriptor


- Use the blurred image associated with the keypoint's scale
- Take image gradients over the keypoint neighborhood.
- To become rotation invariant, rotate the gradient directions by keypoint orientation.
- We could have rotated the whole image as well (slower)

Rotate Gradient Directions






# SIFT Descriptor






# SIFT Descriptor



- SIFT uses 8 orientation bins per histogram, and a  $4 \times 4$  histogram array, yielding  $8 \times 4 \times 4 = 128$  numbers, for a  $16 \times 16$  window.
- A SIFT descriptor is a 128 dimensional vector, invariant to rotation (we rotated the gradients) and scale (worked with the scaled image from DoG).
- Use Euclidean distance between the two descriptor vectors to match.



# SIFT Descriptor: Illumination Robustness



- SIFT descriptor is made of gradients. Invariant to small changes in brightness
- A higher-contrast in an image increases the magnitude of gradients linearly. To correct for contrast changes, normalize the vector (unit magnitude)
- Large gradients from 3D illumination effects effect robustness. Clamp all values in the vector to be  $\leq 0.2$ . Then normalize the vector again.



# Histogram of Oriented Gradients

- Local object appearance and shape can often be characterized rather well by the distribution of local intensity gradients or edge directions.

