

Tables (6)

Name	Type	Schema
tblatx		CREATE TABLE "tblatx" (`atx_d_rowid` INTEGER NOT NULL, `atx_e_rowid` INTEGER NOT NULL)
atx_d_rowid	INTEGER	"atx_d_rowid" INTEGER NOT NULL
atx_e_rowid	INTEGER	"atx_e_rowid" INTEGER NOT NULL
tblcqry		CREATE TABLE tblcqry (name text, query text, date text)
name	text	"name" text
query	text	"query" text
date	text	"date" text
tblldonation		CREATE TABLE "tblldonation" (`member_rowid` INTEGER NOT NULL, `event_rowid` INTEGER NOT NULL, `amount_paid` REAL NOT NULL DEFAULT 0, `in_mem_honor` TEXT, `ackno_donor` TEXT, `ackno_honoree` TEXT, `remarks` TEXT, `last_update` TEXT, `sa_donated` INTEGER DEFAULT 0, `sponsor` INTEGER DEFAULT 0, `attended` INTEGER, `sa_amount` NUMERIC, `goodybag` INTEGER, `misc` INTEGER)
member_rowid	INTEGER	"member_rowid" INTEGER NOT NULL
event_rowid	INTEGER	"event_rowid" INTEGER NOT NULL
amount_paid	REAL	"amount_paid" REAL NOT NULL DEFAULT 0
in_mem_honor	TEXT	"in_mem_honor" TEXT
ackno_donor	TEXT	"ackno_donor" TEXT
ackno_honoree	TEXT	"ackno_honoree" TEXT
remarks	TEXT	"remarks" TEXT
last_update	TEXT	"last_update" TEXT
sa_donated	INTEGER	"sa_donated" INTEGER DEFAULT 0
sponsor	INTEGER	"sponsor" INTEGER DEFAULT 0
attended	INTEGER	"attended" INTEGER
sa_amount	NUMERIC	"sa_amount" NUMERIC
goodybag	INTEGER	"goodybag" INTEGER
misc	INTEGER	"misc" INTEGER
tblldonor		CREATE TABLE "tblldonor" (`first_name` TEXT NOT NULL, `last_name` TEXT, `street` TEXT, `city` TEXT, `state` TEXT, `zip` TEXT, `email_addr` TEXT, `phone_nbr` TEXT, `date_added` TEXT, `source` TEXT, `remarks` TEXT, `old_donations` TEXT, `status` INTEGER DEFAULT 0, `int_x1` INTEGER DEFAULT 0, `int_x2` INTEGER DEFAULT 0, `int_x3` INTEGER DEFAULT 0, `int_x4` INTEGER DEFAULT 0, `int_x5` INTEGER DEFAULT 0, `int_x6` INTEGER DEFAULT 0, `int_x7` INTEGER DEFAULT 0, `int_x8` INTEGER DEFAULT 0, `int_x9` INTEGER DEFAULT 0, `int_x10` INTEGER DEFAULT 0, `int_x11` INTEGER DEFAULT 0, `int_x12` INTEGER DEFAULT 0, `busn_name` TEXT, `phone_nbr_2` TEXT, `email2` TEXT)
first_name	TEXT	"first_name" TEXT NOT NULL
last_name	TEXT	"last_name" TEXT
street	TEXT	"street" TEXT

Name	Type	Schema
city	TEXT	"city" TEXT
state	TEXT	"state" TEXT
zip	TEXT	"zip" TEXT
email_addr	TEXT	"email_addr" TEXT
phone_nbr	TEXT	"phone_nbr" TEXT
date_added	TEXT	"date_added" TEXT
source	TEXT	"source" TEXT
remarks	TEXT	"remarks" TEXT
old_donations	TEXT	"old_donations" TEXT
status	INTEGER	"status" INTEGER DEFAULT 0
int_x1	INTEGER	"int_x1" INTEGER DEFAULT 0
int_x2	INTEGER	"int_x2" INTEGER DEFAULT 0
int_x3	INTEGER	"int_x3" INTEGER DEFAULT 0
int_x4	INTEGER	"int_x4" INTEGER DEFAULT 0
int_x5	INTEGER	"int_x5" INTEGER DEFAULT 0
int_x6	INTEGER	"int_x6" INTEGER DEFAULT 0
int_x7	INTEGER	"int_x7" INTEGER DEFAULT 0
int_x8	INTEGER	"int_x8" INTEGER DEFAULT 0
int_x9	INTEGER	"int_x9" INTEGER DEFAULT 0
int_x10	INTEGER	"int_x10" INTEGER DEFAULT 0
int_x11	INTEGER	"int_x11" INTEGER DEFAULT 0
int_x12	INTEGER	"int_x12" INTEGER DEFAULT 0
busn_name	TEXT	"busn_name" TEXT
phone_nbr_2	TEXT	"phone_nbr_2" TEXT
email2	TEXT	"email2" TEXT
tblevent		CREATE TABLE tblevent (event_name TEXT NOT NULL, event_date TEXT NOT NULL, event_type INTEGER DEFAULT 0, event_remarks TEXT , yrseq INTEGER)
event_name	TEXT	"event_name" TEXT NOT NULL
event_date	TEXT	"event_date" TEXT NOT NULL
event_type	INTEGER	"event_type" INTEGER DEFAULT 0
event_remarks	TEXT	"event_remarks" TEXT
yrseq	INTEGER	"yrseq" INTEGER
tmptbl		CREATE TABLE tmptbl(member_rowid INT,tot)
member_rowid	INT	"member_rowid" INT
tot	TEXT	"tot" TEXT

Indices (0)

Name	Type	Schema
------	------	--------

Views (0)

Name	Type	Schema
------	------	--------

Triggers (0)

Name	Type	Schema
------	------	--------