\hypersetup{colorlinks}
\newrevisor{manuel}{violet!75}
\newrevisor{maria}{blue}
\newrevisor{peter}{green!80!black}[red]
\begin{document}
\thispagestyle{empty}
This is \manuel{text−to−be−deleted}{text−to−be−added}.\MANUEL{This is a note}
\footnote{This is a footnote.\MANUEL∗{this is a note in the footnote}}

This is \maria{text−to−be−deleted}{text−to−be−added}.\MARIA{This is a note}
\footnote{This is a footnote.\MARIA∗{this is a note in the footnote}}

This is \peter{text−to−be−deleted}{text−to−be−added}.\PETER{This is a note}
\footnote{This is a footnote.\PETER∗{this is a note in the footnote}}

\begin{figure}[h!]
  \centering
  A FIGURE
  \caption{Caption \manuel{and}{with} \PETER{not inline}\MANUEL∗{an inline note}}
\end{figure}

\section[test]{A note in a \peter{chapter}{section} \MANUEL∗{inline sorry!} \PETER{fixed}}

Some math:
\begin{equation}
  E = \maria{n}{m}c^{\peter{3}{2}} \MANUEL∗{Is this correct?}\MARIA{Sure!}
\end{equation}

\MARIA∗{A long note with some bullet points:
  \begin{itemize}
  \item Do 1
  \item Do 2
    \item Profit!
    \end{itemize}
  }
\end{document}

This is ~~text-to-be-deleted~~text-to-be-added.[1] [2]
This is ~~text-to-be-deleted~~text-to-be-added.[3] [4]
This is ~~text-to-be-deleted~~text-to-be-added.[5] [6]

A FIGURE

Figure 1: Caption ~~and~~with [7][MANUEL: an inline note]

1 A note in a ~~chapter~~section [MANUEL: inline sorry!]
[8]

Some math:

$$E = \not{m}mc^{3\,2}[\text{MANUEL: Is this correct?}]^{9}$$ (1)

[MARIA: A long note with some bullet points:

- Do 1
- Do 2
- Profit!

]

---

[1][MANUEL: This is a note]
[2]This is a footnote.[MANUEL: this is a note in the footnote]
[3][MARIA: This is a note]
[4]This is a footnote.[MARIA: this is a note in the footnote]
[5][PETER: This is a note]
[6]This is a footnote.[PETER: this is a note in the footnote]
[8][PETER: fixed]
[9][MARIA: Sure!]

Same as above but with option `hide=after`

\usepackage[hide=after]{newrevisor}

This is text-to-be-deleted. [1]
This is text-to-be-deleted. [2]
This is text-to-be-deleted. [3]

A FIGURE

Figure 1: Caption and

1   A note in a chapter

Some math:
$$E = nc^3 \tag{1}$$

---

[1]This is a footnote.
[2]This is a footnote.
[3]This is a footnote.

Same as above but with option `hide=before`

\usepackage[hide=before]{newrevisor}

This is text-to-be-added. [1]
This is text-to-be-added. [2]
This is text-to-be-added. [3]

A FIGURE

Figure 1: Caption with

1 A note in a section

Some math:
$$E = mc^2 \tag{1}$$

---

[1]This is a footnote.
[2]This is a footnote.
[3]This is a footnote.

usepackage[todonotes]{newrevisor}

This is ~~text-to-be-deleted~~text-to-be-added. [1]

> **MANUEL**: This is a note

This is ~~text-to-be-deleted~~text-to-be-added. [2]

> **MARIA**: This is a note

This is ~~text-to-be-deleted~~text-to-be-added. [3]

> **PETER**: This is a note

A FIGURE

Figure 1: Caption ~~and~~with

> **PETER**: not inline

> **MANUEL**: an inline note

1 A note in a ~~chapter~~section

> **MANUEL**: inline sorry!

> **PETER**: fixed

Some math:

$$E = \not{n}mc^{32} \tag{1}$$

> **MANUEL**: Is this correct?

> **MARIA**: Sure!

> **MARIA**: A long note with some bullet points:
> - Do 1
> - Do 2
> - Profit!

---

[1]This is a footnote.

> **MANUEL**: this is a note in the footnote

[2]This is a footnote.

> **MARIA**: this is a note in the footnote

[3]This is a footnote.

> **PETER**: this is a note in the footnote