```latex
\newrevisor{manuel}{violet!75}
\newrevisor{maria}{blue}
\newrevisor{peter}{green!80!black}[red]
\begin{document}
\thispagestyle{empty}
\listofrevisions%
\section{Main document}

This is \manuel{text-to-be-deleted}{text-to-be-added}.\MANUEL{This is a note}
\footnote{This is a footnote.\MANUEL*{this is a note in the footnote}}

This is \maria{text-to-be-deleted}{text-to-be-added}.\MARIA{This is a note}
\footnote{This is a footnote.\MARIA*{this is a note in the footnote}}

This is \peter{text-to-be-deleted}{text-to-be-added}.\PETER{This is a note}
\footnote{This is a footnote.\PETER*{this is a note in the footnote}}

\peter{Old line 1\par Old line 2}{New line 1\par New line 2}

\begin{figure}[h!]
  \centering
  A FIGURE
  \caption{Caption \manuel{and}{with} \PETER{not inline}\MANUEL*{an inline note}}
\end{figure}

\section[test]{A note in a \peter{chapter}{section} \MANUEL*{inline sorry!} \PETER{fixed}}

Some math:
\begin{equation}
  E = \maria{n}{m}c^{\peter{3}{2}} \MANUEL*{Is this correct?}\MARIA{Sure!}
\end{equation}

\MARIA*{A long note with some bullet points:
  \begin{itemize}
  \item Do 1
  \item Do 2
    \item Profit!
    \end{itemize}
  }
\end{document}
```

```
\usepackage{newrevisor}
\input{example-common}
```

List of revisions

1 Main document

This is ~~text-to-be-deleted~~text-to-be-added.[1] [2]
This is ~~text-to-be-deleted~~text-to-be-added.[3] [4]
This is ~~text-to-be-deleted~~text-to-be-added.[5] [6]
~~Old line 1~~
~~Old line 2~~New line 1
New line 2

A FIGURE

Figure 1: Caption ~~and~~with **[PETER: not inline]**[MANUEL: an inline note]

---

[1][MANUEL: This is a note]
[2]This is a footnote.[MANUEL: this is a note in the footnote]
[3][MARIA: This is a note]
[4]This is a footnote.[MARIA: this is a note in the footnote]
[5][PETER: This is a note]
[6]This is a footnote.[PETER: this is a note in the footnote]

2 A note in a ~~chapter~~section [MANUEL: inline sorry!]
  7

Some math:
$$E = \not{n}mc^{32}\text{[MANUEL: Is this correct?]}^8 \tag{1}$$

[MARIA: A long note with some bullet points:
- Do 1
- Do 2
- Profit!
]

---

[7][PETER: fixed]
[8][MARIA: Sure!]

Same as above but with option `hide=after`

`\usepackage[hide=after]{newrevisor}`

---

1 Main document

This is text-to-be-deleted. [1]
    This is text-to-be-deleted. [2]
    This is text-to-be-deleted. [3]
    Old line 1
    Old line 2

<div align="center">

A FIGURE

Figure 1: Caption and

</div>

2 A note in a chapter

Some math:

$$E = nc^3 \tag{1}$$

---

[1] This is a footnote.
[2] This is a footnote.
[3] This is a footnote.

Same as above but with option `hide=before`

```latex
\usepackage[hide=before]{newrevisor}
```

---

1 Main document

This is text-to-be-added. [1]
   This is text-to-be-added. [2]
   This is text-to-be-added. [3]
   New line 1
   New line 2

<div align="center">

A FIGURE

Figure 1: Caption with

</div>

2 A note in a section

Some math:

$$E = mc^2 \tag{1}$$

---

[1] This is a footnote.
[2] This is a footnote.
[3] This is a footnote.

With option `todonotes`

`\usepackage[todonotes]{newrevisor}`

List of revisions

1 Main document

This is ~~text-to-be-deleted~~text-to-be-added. [1]

    This is ~~text-to-be-deleted~~text-to-be-added. [2]

    This is ~~text-to-be-deleted~~text-to-be-added. [3]

~~Old line 1~~

~~Old line 2~~New line 1

New line 2

MANUEL: This is a note

MARIA: This is a note

PETER: This is a note

A FIGURE

---

[1]This is a footnote.
MANUEL: this is a note in the footnote

[2]This is a footnote.
MARIA: this is a note in the footnote

[3]This is a footnote.
PETER: this is a note in the footnote

Figure 1: Caption ~~and~~with

> **PETER**: not inline

> **MANUEL**: an inline note

2 A note in a ~~chapter~~section

> **MANUEL**: inline sorry!

> **PETER**: fixed

Some math:

$$E = \cancel{n}mc^{\cancel{3}2} \tag{1}$$

> **MANUEL**: Is this correct?

> **MARIA**: Sure!

> **MARIA**: A long note with some bullet points:
> - Do 1
> - Do 2
> - Profit!