Running the eDNAVisualJointModel re-runs on stats3

EJ45

2026-10-25

Quick orientation

These are the re-runs that the move to the 35°N study domain needed (ROADMAP_2026-10-06, 6.0; the remaining ones are in ROADMAP_2026-10-21, section 3). As with the FinWhale pipeline, the cleanest set-up is **SSH + tmux**: every job is a non-interactive `Rscript` that writes files.

> **Now (2026-10-26): the real-data fits and the seed-1 demonstration.** Stop any old session, update to branch `claude/replicates`, run `compile` (Part 6, "Getting ready"), then launch the real-data fits (`stage 6`, three jobs) and seed 1's joint and free-conversion fits (two jobs): 20 cores, up to about a day. None needs stage 1 or the private data. **The tier-1 replicates (seeds 2–5) wait until later this week**; their steps are in Part 6, "The tier-1 replicates". Everything else in this guide is the earlier set-up and still applies.

stats3 specs (from the IT FAQ): Intel i9-13900K with 24 physical cores and 32 hyperthreads, 128 GB RAM, RAID-1 NVMe (`/fast_raid`) and HDD (`/local_raid`).

Each Stan chain uses one core, and a fit runs 2–4 chains. No fit uses within-chain threading, so a single fit never uses more than 4 cores. Memory is not a constraint (the largest arrays are tens of MB per fit), so **cores are the budget: keep the total at or below 24.** Hyperthreads add little for Stan.

One script, `tools/stats3_reruns.sh`, runs everything. It groups the re-runs into five **stages**, with one tmux window and one log (`logs/<job>.log`) per job. Every job runs under `nice` and stops at its first failing step.

Stage	Jobs	Cores	Rough time
1	`prep`: real data (`01_load_muri.r`, `02_check_muri.r`), smoke test, `tests/visual_detection.R`, compile every model	2	about 1 h
2	HSGP4eDNA 2-D validation (4 jobs), visual validation (normal and sea state), joint simulator check	23	hours; `hsgp_bathysp_depthspref` 1–2 days
3	Joint comparison: modes `visual`, `edna`, `joint`, `joint_conv` (4 chains each) for every seed in `CMP_SEEDS` (default `"2 3"`); with `CMP_SEA=1` the sea-state version (the replicates; Part 6)	16 per seed (+12 for the without-Beaufort contrast)	about 6–8 h each (`visual` about 1 h)
4	Explainer fits: simulated eDNA and visual, real visual (budget 800 and 1600, both species)	14	about 1–3 h each
5	`finish`: comparison tables and `joint_compare_s<seed>.png` for every seed with fits, the remaining explainer figures	1	minutes

The real eDNA explainer fit (`expl_edna_real`) is in no stage. Its data are

in (Ct per well, the hake standards, volumes, dilutions and target depths; ROADMAP_2026-10-21, section 5) and the joint model can use them, but the job's script (`docs/explainer/04_fit_edna_real.R`) still runs the earlier metabarcoding-only fit. Don't launch it until that script is rewritten (ROADMAP_2026-10-21, section 5 item 7).

The times are estimates. The budget is now 800 functions and the domain is larger, which roughly doubles the old run times. `bathysp_depthspref` (1185 bottles) took 15 h on the old set-up. The whole list is about 280 core-hours, or about 2 days of wall time on stats3.

Stage 1 must finish first, because it checks the real data and compiles every Stan model. Stages 2 to 4 each need only stage 1, and stage 5 needs 3 and 4.

Part 1: Connect to stats3 (every session)

This is the same as for FinWhale. From a Mac terminal:

```
ssh -J ej45@jump.st-andrews.ac.uk ej45@maths-stats3.st-andrews.ac.uk
```

With the `~/.ssh/config` block from the FinWhale guide, this is just `ssh stats3`. Work on the fast disk:

```
cd /fast_raid/ej45
```

Part 2: SSH keys (optional, one time)

If you already set up keys and the `jump` / `stats3` hosts for FinWhale, skip this. Otherwise, follow Part 2 of the FinWhale guide:

- `ssh-keygen`;
- `ssh-copy-id` to both hops;
- the `Host jump` / `Host stats3` block in `~/.ssh/config`.

The `scp` and `rsync` commands below use the `stats3` alias. Without it, give the full host name and the jump host:

```
scp -J ej45@jump.st-andrews.ac.uk FILES \
    ej45@maths-stats3.st-andrews.ac.uk:/fast_raid/ej45/...
rsync -av -e 'ssh -J ej45@jump.st-andrews.ac.uk' \
    ej45@maths-stats3.st-andrews.ac.uk:/fast_raid/ej45/... DEST/
```

Part 3: Clone the repo and its submodule (one time)

On stats3:

```
cd /fast_raid/ej45
git clone --recurse-submodules https://github.com/MMARINeDNA/eDNAVisualJointModel.git
cd eDNAVisualJointModel
git submodule status        # external/HSGP4eDNA should show v1.5-48-g5515a04 (v1.12)
```

eDNAVisualJointModel is public, but its submodule **HSGP4eDNA is private**. So the clone asks for a GitHub username and a **personal access token** (not your password). Create one at github.com → Settings → Developer settings → Personal access tokens:

- a fine-grained token: set *Resource owner* to `MMARINeDNA` and give it read access to `Contents`;
- or a classic token with the `repo` scope.

To avoid pasting the token on every pull, keep it in memory for a day:

```
git config --global credential.helper 'cache --timeout=86400'
```

To update later: `git pull && git submodule update --init`.

Part 4: Copy the private input data (only for `prep` and real-data jobs)

The raw MURI files are **not in the repo**, because the repo is public, and `.gitignore` keeps them out. Only the real-data loader (`R/01_load_muri.r`) and its check (`R/02_check_muri.r`) read them, so only `prep` (stage 1) needs them. Everything else, the replicates included, uses simulations or the tracked, derived `data/processed/muri_{edna,visual}.rds` and `qpcr_standard_curves.rds`.

The loader now reads four private files (from 2026-10-21): the qPCR lab's `qPCR_2019A.rds`, the compiled metabarcoding table `M3_compiled_taxon_table_wide.csv`, the sample metadata `Hake_2019_metadata.csv`, and `SITEINFO_CCE_2018_Pp_Lo_Mn.csv` (perpendicular distances). `MV1_MURI_df.csv` is no longer used. From a **Mac terminal in your main checkout**, which has them:

```
cd /Users/ej45/Documents/MMARINeDNA/eDNAVisualJointModel
scp data/qPCR_2019A.rds data/M3_compiled_taxon_table_wide.csv \
    data/Hake_2019_metadata.csv data/SITEINFO_CCE_2018_Pp_Lo_Mn.csv \
    stats3:/fast_raid/ej45/eDNAVisualJointModel/data/
```

Then check on stats3 with `ls -lh /fast_raid/ej45/eDNAVisualJointModel/data/`. If a file is missing, the `prep` job stops with a message pointing here.

Bathymetry. On its first run, the loader downloads ETOPO 2022 bathymetry from NOAA (via `marmap`, a few MB) and caches it as `data/processed/etopo2022_60s_cce.rds`. If stats3 cannot reach NOAA, copy the cache across from a checkout that has one. The `stan-data-formatting` worktree does:

```
cd /Users/ej45/Documents/MMARINeDNA/eDNAVisualJointModel/.claude/worktrees
scp stan-data-formatting-61936f/data/processed/etopo2022_60s_cce.rds \
    stats3:/fast_raid/ej45/eDNAVisualJointModel/data/processed/
```

Part 5: R packages and CmdStan (one time)

Check R with `R --version`. The Mac runs R 4.5.2; 4.3 or later should be fine. Then:

```
cd /fast_raid/ej45/eDNAVisualJointModel
R
```

In R:

```
install.packages(c(
  "tidyverse", "posterior", "patchwork", "viridis", "bayesplot", "loo",
  "gridExtra", "data.table", "jsonlite", "sf", "terra", "marmap"
))
install.packages("cmdstanr",
  repos = c("https://stan-dev.r-universe.dev", getOption("repos")))

cmdstanr::check_cmdstan_toolchain(fix = TRUE)
cmdstanr::install_cmdstan(dir = "/fast_raid/ej45/cmdstan",
                          version = "2.38.0", cores = 8)   # same CmdStan as the Mac
cmdstanr::cmdstan_path()        # copy this path
quit(save = "no")
```

Packages install into `/local_raid/ej45/R/library` through the `.Rprofile` IT set up. `sf` and `terra` build against GDAL, GEOS and PROJ; if they fail with a missing-library error, ask maths-tech-support. The CmdStan build takes 5–10 minutes.

Point cmdstanr at CmdStan for every session (use the path printed above):

```
echo 'CMDSTAN=/fast_raid/ej45/cmdstan/cmdstan-2.38.0' >> ~/.Renviron
Rscript -e 'cmdstanr::cmdstan_version()'    # should print 2.38.0
```

Part 6: Run the re-runs inside tmux

The script creates the tmux session (`reruns`) itself. Start with the overview, then stage 1:

```
cd /fast_raid/ej45/eDNAVisualJointModel
tools/stats3_reruns.sh list
tools/stats3_reruns.sh stage 1
tools/stats3_reruns.sh status       # repeat until prep says DONE (about 1 h)
```

`prep` reruns the loader, so the log should say each processed object **matches the committed copy**. If one differs, stop and look before going on. The smoke test's 44 checks must pass. If `prep` says `FAILED`, read `logs/prep.log`. Simulation-only work (the replicates below) can skip `prep` and run the much shorter `compile` job instead.

Getting ready (now)

Steps 1–3 below (stop old jobs, update the checkout, `compile`) are needed before **any** of the new jobs. Then launch, together (20 cores):

```
tools/stats3_reruns.sh stage 6                        # the real-data fits (see "The real-da
tools/stats3_reruns.sh launch cmpsea_s1_joint         # seed 1 demonstration: joint
tools/stats3_reruns.sh launch cmpsea_s1_joint_conv    # seed 1: joint with free conversion fa
tools/stats3_reruns.sh status
```

The seed-1 demonstration is the idealised simulation (sea state; NB counts; HSGP4eDNA v1.12) fitted four ways. Its eDNA-only and visual-only fits are done on the Mac (`outputs/joint/compare_sea_s1/`); these two jobs re-run the joint and free-conversion fits with the bound on the NB parameter (about 6–8 hours each). Pull `outputs/joint/compare_sea_s1/` back when they end (Part 9) and Claude rebuilds the seed-1 table and figure.

Steps 4–6 are for the replicates, later this week; seed 1 is then done, so the waves start with seed 2.

The tier-1 replicates (later this week)

The sea-state joint comparison for seeds 1–5: each seed simulated with segment Beaufort and fitted eDNA-only, visual-only, joint and joint with free conversion factors, all with the Beaufort covariate; seeds 1 and 2 also without it, for contrast. The fits use the settings that are now `R/compare_joint.r`'s defaults: negative-binomial segment counts for both cetaceans, non-centred junk noise and `adapt_delta = 0.9`, with the NB parameter bounded (`inv_sqrt_phi_nb >= 0.01`). Seed 1 with the covariate is done first (above); the rest are 22 jobs of 4 chains each.

1. Connect and stop anything left from an earlier launch. If yesterday's stage-3 jobs are running, they use the model without the NB bound and can get stuck (Part 8):

```
ssh stats3
cd /fast_raid/ej45/eDNAVisualJointModel
tools/stats3_reruns.sh status
tmux kill-session -t reruns          # only if jobs from an earlier launch are running
```

2. Update the checkout to the branch with the replicate settings (until it is merged into `main`) and the HSGP4eDNA v1.12 submodule:

```
git fetch
git checkout claude/replicates
git pull
git submodule update --init
git log --oneline -3                 # the latest should be the guide update of 2026-10-26 or
                                     # (it must include 0a5a894, the real-data fits, and e0ed
git submodule status                 # v1.5-48-g5515a04
```

3. Compile the models once (a few minutes; the Stan files changed). Without this, every job of a wave would compile the joint model at the same moment. Everything on the branch was checked on the Mac on 2026-10-26: the smoke test, the exactness tests, and each job type (`cmpsea_*`, `cmpseanobft_*`, `jreal_*`) run through this script with tiny chains.

```
tools/stats3_reruns.sh run compile  # ends with "DONE compile"
```

4. Launch the jobs in waves, keeping to about 24 cores. A seed's four jobs use 16 cores; its visual-only job ends after about an hour, the other three take about 6–8 hours. Check `uptime` before each wave and start the next one when the previous wave's long jobs end.

Wave	Command	Jobs	Cores
1	`CMP_SEA=1 CMP_NOBFT=0 CMP_SEEDS="2 3" tools/stats3_reruns.sh stage 3`	seeds 2–3, with the covariate	32 for the first hour, then 24
2	`CMP_SEA=1 CMP_NOBFT=0 CMP_SEEDS="4 5" tools/stats3_reruns.sh stage 3`	seeds 4–5	32, then 24
3	`for s in 1 2; do for m in visual joint joint_conv; do tools/stats3_reruns.sh launch cmpseanobft_s${s}_$m; done; done`	seeds 1–2 without the covariate	24, then 16

Seed 1 with the covariate is done by then (the two jobs above and the Mac's fits), so it is not in the waves. That is about a day in all. Results go to `outputs/joint/compare_sea_s<seed>/` and `compare_sea_nobft_s<seed>/` (one `fit_<mode>.rds` per job).

5. Check on them (Part 7). Each job's log ends with a line like `joint: 465 min | divergences 0 | treedepth 0 | max Rhat 1.06`. A visual-only job still in warmup after about 2 hours is the stuck-chain problem (Part 8).

6. Pull the results back when all 22 are done (Part 9, the replicates block) and ask Claude for the summary table across seeds.

The real-data fits (stage 6, from 2026-10-26)

The joint model on the real 2019 eDNA and 2018 visual data (`R/fit_joint_real.r`; ROADMAP_2026-10-21, section 5 item 7). Three jobs of 4 chains, 1000 warmup and 1000 draws each:

Job	Fit
`jreal_edna`	eDNA only: the real eDNA fit, with Ct and per-plate qPCR curves estimated from the 659 standards, the dilution offsets, per-bottle volumes and the sampling-depth smooth
`jreal_visual`	visual only, on the same basis and priors (humpback hazard-rate + group size; PWSD half-normal + group size + Beaufort + visibility; NB counts for both)
`jreal_joint_conv`	both sources, the cetaceans' eDNA conversion factors estimated (the real ones are unknown)

They read only the tracked `data/processed/` objects, so they need `compile` but not `prep` or the private data. After steps 1–3 above:

```
tools/stats3_reruns.sh stage 6
tools/stats3_reruns.sh status          # the three jreal_* jobs
```

Expect roughly half a day for `jreal_edna` and up to a day for `jreal_joint_conv`; `jreal_visual` takes about an hour. These are the first fits of the full model to the real data, so check each log's final line (divergences, max Rhat) and tell Claude about anything odd before relying on them. Results go to `outputs/joint/real/` (`fit_<mode>.rds`, and `real_{runs,params,floor}.csv` over the modes found); pull them back with the replicates (`outputs/joint/`). After the jobs end, rebuild the tables over all three modes with `MODES= Rscript R/fit_joint_real.r`.

Other stage-3 runs

The plain (calm-sea) comparison, as before:

For the presentation, launch the joint comparison next. With the default `CMP_SEEDS="2 3"` it runs 8 jobs (32 chains for the first half hour, 24 once the two visual-only fits end), and should finish overnight:

```
tools/stats3_reruns.sh stage 3                    # seeds 2 and 3
CMP_SEEDS="4 5" tools/stats3_reruns.sh stage 3    # second wave, once the first is done
CMP_SEEDS="1" tools/stats3_reruns.sh stage 3      # seed 1 (needs the data-based start)
```

Sea-state comparison: `CMP_SEA=1` runs the four modes with the Beaufort covariate and, unless `CMP_NOBFT=0`, the three visual modes without it (28 cores per seed); the replicates above use it.

A single fit can be relaunched by name, e.g. `tools/stats3_reruns.sh launch cmp_s3_joint`. The tables and figure for a seed are rebuilt by `finish` (stage 5); for the presentation it is quicker to pull `outputs/joint/` back to the Mac (Part 9) and build them there.

The rest, after the presentation. Stage 2 is the full validation; it takes the longest:

```
tools/stats3_reruns.sh stage 2
```

It uses 23 cores. Its visual and joint-simulator jobs finish within hours, as do three of the four HSGP4eDNA jobs; `hsgp_bathysp_depthspref` (3 cores) runs for 1–2 days. Launch stage 4 when about 14 cores are free, and stage 5 once stages 3 and 4 are done:

```
tools/stats3_reruns.sh stage 4
tools/stats3_reruns.sh stage 5
```

Before launching a stage, check `uptime` (load average) or `htop`. Hold the stage back if other users are busy.

To watch a job: `tmux attach -t reruns`, then `Ctrl-b w` to pick a window. To detach, press `Ctrl-b d`; the jobs keep running after you log out. A finished job's window stays open at a shell prompt.

To re-run one job, e.g. after a failure:

```
tools/stats3_reruns.sh launch hsgp_bathygp_surface
```

What each job writes (git-ignored unless marked *tracked*):

Job	Output
`prep`	`data/processed/muri_{edna,visual}.rds` (*tracked*; should be unchanged), `outputs/smoke/`
`hsgp_*`	`external/HSGP4eDNA/outputs/<scenario>/` (fit summary, recovery CSV and PDF)
`visual_val`, `visual_val_sea`	`outputs/visual/validation/`, `outputs/visual/validation_seastate/`
`joint_sim`	`outputs/joint_sim/validation/`
`cmp_s<seed>_<mode>`	`outputs/joint/compare_s<seed>/fit_<mode>.rds`
`expl_*`	`outputs/explainer/`, `docs/figures/*.png` (*tracked*)

Job	Output
`finish`	`outputs/joint/compare_s<seed>/compare_*.csv`, `docs/figures/joint_compare_s<seed>.png` and the remaining explainer figures

Part 7: Check progress

From the Mac, without attaching:

```
ssh stats3 'cd /fast_raid/ej45/eDNAVisualJointModel && tools/stats3_reruns.sh status'
ssh stats3 'tail -n 30 /fast_raid/ej45/eDNAVisualJointModel/logs/visual_val.log'
```

Stan writes each chain's progress to the log (`Chain 2 Iteration: 400 / 1600`). The fit scripts print divergences, max Rhat and the run time when a fit ends, and warn when Rhat is above 1.05.

Part 8: If something goes wrong

- **A job says `FAILED`.** The end of its log has the R error. Fix the cause, then run `launch <job>` again. Other jobs carry on.
- **A model compile error in a stage 2–4 job** means `prep` did not finish. Run it first.
- **`tests/visual_detection.R` recompiles the visual model.** It runs inside `prep`, so don't relaunch `prep` while visual fits are running.
- **Stopping jobs.** To stop one, attach, pick its window and press `Ctrl-c`. To stop everything, run `tmux kill-session -t reruns`.
- **A fit stuck in warmup for hours** (no `Iteration: ... (Sampling)` lines; seen on 2026-10-24 in a visual-only fit) was the NB parameter running off to 0 on near-Poisson sightings. The bound in commit `e0ed941` fixes it; check `git log` shows it, run `compile`, and relaunch the job by name.
- **Two jobs compiling at once** can leave a broken executable. Run `tools/stats3_reruns.sh run compile` before a wave whenever the Stan files have changed.

Part 9: Pull results back to the Mac

Leave the CmdStan chain CSVs on stats3. They can be about 330 MB per chain, and the fits keep what they need in `.rds` summaries. In your main checkout, on an up-to-date `main` with a clean tree:

```
cd /Users/ej45/Documents/MMARINeDNA/eDNAVisualJointModel
git switch main && git pull && git submodule update --init
R=stats3:/fast_raid/ej45/eDNAVisualJointModel
X="--exclude=*-202[0-9]*-[0-9]-*.csv"      # CmdStan chain CSVs
```

```
rsync -av "$X" $R/outputs/ outputs/
rsync -av "$X" $R/external/HSGP4eDNA/outputs/ external/HSGP4eDNA/outputs/
rsync -av $R/docs/figures/ docs/figures/
rsync -av $R/logs/ logs/
```

For the replicates, only the joint comparison is needed, which is small (summaries only). Into the session's worktree or any checkout:

```
rsync -av "$X" $R/outputs/joint/ outputs/joint/
rsync -av $R/logs/ logs/
```

Seed 1's earlier Mac runs are kept on the Mac as `outputs/joint/compare_sea_s1_v15/` (v1.5). In `compare_sea_s1/` the pull replaces the joint and free-conversion fits (made before the NB bound) and keeps the Mac's eDNA-only and visual-only fits (rsync deletes nothing); its tables then cover only stats3's two modes, so rebuild them over all four on the Mac with `SEA_STATE=1 SEED=1 MODES= Rscript R/compare_joint.r` (or ask Claude).

`docs/figures/*.png` then shows up as changed in `git status`. `data/processed/` is not copied back, because `prep` checked that it matches `main`.

Then ask Claude to do three things:

- rebuild the tables: the HSGP4eDNA README §4 (and a v1.5.x release), this README's results and ROADMAP_2026-10-21;
- rewrite the explainer's numbers, and re-render it locally with `quarto render docs/explainer.md --to html --embed-resources`;
- open the PRs.

TL;DR for repeat sessions

```
ssh stats3
cd /fast_raid/ej45/eDNAVisualJointModel
tools/stats3_reruns.sh status        # what is done, running or failed
tools/stats3_reruns.sh run compile   # after a git pull that changed Stan files
tools/stats3_reruns.sh stage <n>     # launch the next stage (replicates: Part 6 waves; rea
tmux attach -t reruns                # Ctrl-b w to pick a window, Ctrl-b d to detach
exit
```

Then the `rsync` block in Part 9 from the Mac.