



```
# **GROUP NUMBER: 6442**
```

GROUP NUMBER: 6442

MScFE 652 RISK MANAGEMENT

Group Work Project # 2

Tasks

✓ Step 1

Toy example for Baum-Welch algorithm:

Let,

S be the two states = {1,2}

O be the two observations = {A,B}

O be the observation sequence = {A,B,A}

```
import numpy as np

def forward(obs_seq, A, B, pi):
    N = A.shape[0]
    T = len(obs_seq)
    alpha = np.zeros((T, N))

    alpha[0, :] = pi * B[:, obs_seq[0]]

    for t in range(1, T):
        for j in range(N):
            alpha[t, j] = np.dot(alpha[t-1, :], A[:, j]) * B[j, obs_seq[t]]

    return alpha

def backward(obs_seq, A, B):
    N = A.shape[0]
```

```

T = len(obs_seq)
beta = np.zeros((T, N))

beta[T-1, :] = 1

for t in range(T-2, -1, -1):
    for i in range(N):
        beta[t, i] = np.sum(A[i, :] * B[:, obs_seq[t+1]] * beta[t+1, :])

return beta

def baum_welch(obs_seq, A, B, pi, max_iter=100, tol=1e-6):
    N = A.shape[0]
    M = B.shape[1]
    T = len(obs_seq)

    for _ in range(max_iter):
        alpha = forward(obs_seq, A, B, pi)
        beta = backward(obs_seq, A, B)

        xi = np.zeros((T-1, N, N))
        for t in range(T-1):
            denominator = np.dot(np.dot(alpha[t, :].T, A) * B[:, obs_seq[t+1]].T, beta[t+1, :])
            for i in range(N):
                numerator = alpha[t, i] * A[i, :] * B[:, obs_seq[t+1]].T * beta[t+1, i]
                xi[t, i, :] = numerator / denominator

        gamma = np.sum(xi, axis=2)
        gamma = np.vstack((gamma, np.sum(xi[T-2, :, :], axis=0)))

        new_pi = gamma[0, :]
        new_A = np.sum(xi, axis=0) / np.sum(gamma[:-1, :], axis=0).reshape(-1, 1)
        new_B = np.zeros((N, M))

        for j in range(M):
            mask = obs_seq == j
            new_B[:, j] = np.sum(gamma[mask, :], axis=0) / np.sum(gamma, axis=0)

        if np.max(abs(A - new_A)) < tol and np.max(abs(B - new_B)) < tol and np.max(abs(pi - new_pi)) < tol:
            break

        A, B, pi = new_A, new_B, new_pi

    return A, B, pi

# Toy example
obs_seq = np.array([0, 1, 0]) # A = 0, B = 1
A = np.array([[0.7, 0.3], [0.4, 0.6]])
B = np.array([[0.5, 0.5], [0.6, 0.4]])
pi = np.array([0.6, 0.4])

```

```
A, B, pi = baum_welch(obs_seq, A, B, pi)
```

```
print("Updated A:", A)
print("Updated B:", B)
print("Updated pi:", pi)
```

```
Updated A: [[5.28642688e-10 9.99999999e-01]
 [1.00000000e+00 3.82364337e-62]]
Updated B: [[5.28642688e-10 9.99999999e-01]
 [1.00000000e+00 3.34087122e-44]]
Updated pi: [3.85651997e-20 1.00000000e+00]
```

✓ Step 2

```
%%writefile dthmm.pyx
"""
Discrete-time hidden Markov model class
"""

#
# Authors: Lukas Lopatovsky, Mai 2017
#

import numpy
import random
cimport numpy
cimport cython

#cython: wraparound=False
#cython: boundscheck=False
#cython: nonecheck=False

ctypedef numpy.float64_t float_t
ctypedef numpy.int64_t int_t

cdef class DtHMM:

    """Parameters _loga, _logb, _logpi are log likelihoods to avoid underflow."""
    cdef numpy.ndarray _loga
    cdef numpy.ndarray _logb
    cdef numpy.ndarray _logpi

    @property
    def a(self):
        return numpy.exp( self._loga )
```

```

@property
def b(self):
    return numpy.exp( self._logb )

@property
def pi(self):
    return numpy.exp( self._logpi )

@property
def params( self ):
    return( self.a, self.b, self.pi )

def __init__(self, A,B,Pi):
    """Initialize the DtHMM by given parameters.
    A : (n,n) ndarray
        transition probabilities matrix for (n) hidden states
    B : (n,m) ndarray
        probability matrix of (m) observation symbols being emitted by (n) hidden
    Pi : (n) ndarray
        vector of initial probabilities
    """
    numpy.seterr( divide = 'ignore' ) #ignore warnings, when working with log(0)
    self.set_params( A,B,Pi )

@classmethod
def from_file( cls, path ):
    """Initialize the class by reading parameters from file"""
    return cls( *DtHMM.get_params_from_file(path) )

@classmethod
def random( cls, s, o ):
    """Initialize the class by random parameters of 's' hidden states and 'o' output
    return cls( *DtHMM.get_random_params( s, o ) )

def set_params( self, A, B, Pi):
    """Set parameters as their logs to avoid underflow"""
    self._loga = numpy.log(A)
    self._logb = numpy.log(B)
    self._logpi = numpy.log(Pi)

def set_params_from_file( self, path ):
    """Set parameters by reading them from file"""
    self.set_params( *DtHMM.get_params_from_file(path) )

def set_params_random( self, s, o ):
    """Set parameters by random. Size of 's' hidden states and 'o' output variable
    self.set_params( *DtHMM.get_random_params( s, o ) )

def save_params( self, path ):
    """Save parameters in the file given by 'path'"""

```

```

        Save parameters in the file given by path
    numpy.savez( path, a=self.a, b=self.b, pi=self.pi )

    @staticmethod
    def get_params_from_file( path ):
        """Get parameters by reading them from .npz file"""
        npz = numpy.load( path )
        return ( npz['a'], npz['b'], npz['pi'] )

    @staticmethod
    def get_random_vector( s ):
        """Generate random vector of size (s), with all values summing to one"""
        vec = numpy.random.random(s)
        return vec / numpy.sum(vec)

    @staticmethod
    def get_random_params( s, o ):
        """Generate random parameters A,B and Pi, for number of hidden states (s) and

        a = numpy.empty( [s,s] )
        b = numpy.empty( [s,o] )
        pi = numpy.empty( s )

        for i in range( a.shape[0] ):
            a[i,:] = DtHMM.get_random_vector(s)
        for i in range( b.shape[0]):
            b[i,:] = DtHMM.get_random_vector(o)
        pi = DtHMM.get_random_vector(s)

        return(a,b,pi)

    def generate(self, size ):
        """Randomly generate a sequence of states and emissions from model parameters.
        a = numpy.exp( self._loga )
        b = numpy.exp( self._logb )
        pi = numpy.exp( self._logpi )

        states = numpy.empty(size,dtype=int)
        emissions = numpy.empty(size,dtype=int)
        current_state = numpy.random.choice( pi.shape[0], 1, p= pi)
        for i in range(size):
            states[i] = current_state
            emissions[i] = numpy.random.choice( b.shape[1],1, p = b[ current_state,:])
            current_state = numpy.random.choice( a.shape[1],1, p = a[ current_state,:])
        return ( states, emissions )

    def generate_data(self, size, **kargs ):
        """Generate multiple sequences of states and emissions from model parameters
        size = ( number of sequences, length of sequences )
        **kargs: times=True : return also equidistant sequence of times

```

```

"""
e = numpy.empty( size, dtype=int )
t = numpy.empty( size, dtype=int )
s = numpy.empty( size, dtype=int )
for i in range( size[0] ):
    s[i],e[i] = self.generate( size[1] )
    t[i] = numpy.arange( size[1] )

if ('times' in kargs) and kargs['times'] == True:
    return(t,s,e)

return (s,e)

cdef float_t emission_estimate(self, numpy.ndarray[int_t, ndim=1] emissions ):
    """From given emission sequence calculate the likelihood estimation given mode
    return self.log_sum( self.forward( emissions )[-1,:] )

cdef float_t data_estimate( self, emissions):
    """From the set of given emission sequences in the data calculate their likeli
    Emission sequences can be given as numpy matrix or list of numpy vectors
    """

    cdef numpy.ndarray[int_t, ndim=1] row
    cdef float_t sm = 0

    for row in emissions:
        sm += self.emission_estimate( row )
    return sm

cdef float_t full_data_estimate( self, state_seqs, emissions ):
    """From the set of given state and emission sequences in the data calculate th
    Emission and state sequences can be given as numpy matrix or list of numpy
    """
    cdef numpy.ndarray[int_t, ndim=1] e,s
    cdef float_t sm = 0

    for s,e in zip( state_seqs, emissions ):
        sm += self.estimate( s, e )
    return sm

cdef float_t estimate(self, numpy.ndarray[int_t, ndim=1] states, numpy.ndarray[ir
    """Calculate the probability of state and emission sequence given the current
    Return logarithmus of probabilities.
    """
    cdef numpy.ndarray[float_t, ndim=2] loga = self._loga
    cdef numpy.ndarray[float_t, ndim=2] logb = self._logb
    cdef numpy.ndarray[float_t, ndim=1] logpi = self._logpi
    cdef int i, s, size, states_num
    cdef float_t prob #it is log probability

    size = emissions.shape[0]

```

```

size = emissions.shape[0]
states_num = self._loga.shape[0]

prob = logpi[ states[0] ] + logb[ states[0], int(emissions[0]) ]

for i in range(1,size):
    prob += loga[states[i-1],states[i]]
    prob += logb[states[i],int(emissions[i])]

return prob

cpdef numpy.ndarray[float_t, ndim=2] forward(self, numpy.ndarray[int_t, ndim=1] en
    """From emission sequence calculate the forward variables (alpha) given model
    Return logarithmus of probabilities.
    """
    cdef numpy.ndarray[float_t, ndim=2] loga = self._loga
    cdef numpy.ndarray[float_t, ndim=2] logb = self._logb
    cdef numpy.ndarray[float_t, ndim=1] logpi = self._logpi
    cdef int i, s, size, states_num,

    size = emissions.shape[0]
    states_num = self._loga.shape[0]
    cdef numpy.ndarray[float_t, ndim=2] alpha = numpy.empty( (size,states_num), dt

    alpha[0,:] = logpi + logb[:, int(emissions[0]) ]
    for i in range(1,size):
        for s in range(states_num):

            alpha[i,s] = self.log_sum( alpha[i-1,:]+ loga[:,s] )

            alpha[i,:] = alpha[i,:] + logb[:, int(emissions[i]) ]

    return alpha

cpdef numpy.ndarray[float_t, ndim=2] backward(self, numpy.ndarray[int_t, ndim=1] e
    """From emission sequence calculate the backward variables beta) given model p
    Return logarithmus of probabilities.
    """
    cdef numpy.ndarray[float_t, ndim=2] loga = self._loga
    cdef numpy.ndarray[float_t, ndim=2] logb = self._logb
    cdef numpy.ndarray[float_t, ndim=1] logpi = self._logpi
    cdef int i, s, size, states_num

    size = emissions.shape[0]
    states_num = self._loga.shape[0]
    cdef numpy.ndarray[float_t, ndim=2] beta = numpy.empty( (size,states_num), dt

    beta[-1,:] = 0 #log(1) = 0
    for i in range(size-2, -1,-1):
        for s in range(states_num):

```

```

        beta[i,s] = self.log_sum( beta[i+1,:] + loga[s,:] + logb[:, int(emissi

return beta

cpdef viterbi(self, numpy.ndarray[int_t, ndim=1] e_seq):
    """
    From given emission sequence and parameters calculate the most likely state sequence
    Parameters
    -----
    e_seq: ndarray, int
            observation (emission) symbols sequence
    Returns
    -----
    (max_p, path) : max_p: probability of the most likely state sequence
                   path: most likely state sequence

    """

    cdef numpy.ndarray[float_t, ndim=2] loga = self._loga
    cdef numpy.ndarray[float_t, ndim=2] logb = self._logb
    cdef numpy.ndarray[float_t, ndim=1] logpi = self._logpi
    cdef int i, s, size, states_num,
    cdef float_t max_p

    size = e_seq.shape[0]
    states_num = self._loga.shape[0]
    cdef numpy.ndarray[float_t, ndim=2] delta = numpy.empty( (size,states_num), dt
    cdef numpy.ndarray[int_t, ndim=2] psi = numpy.empty( (size,states_num), dtype=

    delta[0,:] = logpi + logb[:, int(e_seq[0])] ]
    psi[0,:] = 0
    for i in range(1,size):
        for s in range(states_num):

            delta[i,s] = delta[i-1,0] + loga[0,s]
            psi[i,s] = 0

            for r in range(1,states_num):
                if delta[i,s] < delta[i-1,r] + loga[r,s]:
                    delta[i,s] = delta[i-1,r] + loga[r,s]
                    psi[i,s] = r

            delta[i,s] += logb[s,e_seq[i]]

    max_p = delta[-1,0]

    p = 0

    for s in range(1,states_num):
        if max_p < delta[-1,s]:
            max_p = delta[-1,s]

```



```

        max_p = vec[0]
        p = s

    cdef numpy.ndarray[int_t, ndim=1] path = numpy.full( size, 0, dtype=int )

    for i in range(size-1,-1,-1):
        path[i] = p
        p = psi[i,p]

    return ( max_p, path )

cpdef float_t log_sum(self, numpy.ndarray[float_t, ndim=1] vec ):
    """Count sum of items in vec, that contain logarithmic probabilities using log-
    cdef float_t max_p          # faster for:  max_p = numpy.amax( vec )
    cdef int i                  #
    max_p = vec[0]              #
    for i in range(1,vec.shape[0]): #
        if max_p < vec[i] : max_p = vec[i] #

    if numpy.isinf( max_p ): return max_p #to avoid nan in (inf-inf)

    return max_p + numpy.log( numpy.sum( numpy.exp( vec - max_p ) ) )

cpdef float_t log_sum_elem(self, float_t x, float_t y ):
    """Count sum of two items, that contain logarithmic probabilities using log-sum
    cdef float_t max_p
    if x > y: max_p = x
    else    : max_p = y

    if numpy.isinf( max_p ): return max_p #to avoid nan in (inf-inf)

    return max_p + numpy.log( numpy.exp( x - max_p ) + numpy.exp( y - max_p ) )

cpdef numpy.ndarray[float_t, ndim=2] single_state_prob( self, numpy.ndarray[float_t,
    """Given forward and backward variables, count the probability for any state i
    cdef numpy.ndarray[float_t, ndim=2] gamma
    cdef float_t max_p, log_sum

    gamma = alpha + beta
    for i in range(gamma.shape[0]):
        gamma[i] -= self.log_sum(gamma[i])

    return gamma

cpdef numpy.ndarray[float_t, ndim=3] double_state_prob( self, numpy.ndarray[float_t,
    numpy.ndarray[float_t,
    numpy.ndarray[int_t,
    """Given forward and backward variables, count the probability for transition
    cdef numpy.ndarray[float_t, ndim=3] ksi = numpy.empty( (alpha.shape[0]-1,alpha
    cdef numpy.ndarray[float_t, ndim=2] loga = self._loga #Such declaration make
    cdef numpy.ndarray[float_t, ndim=2] logb = self._logb

```

```

for t in range( ksi.shape[0]):
    for i in range( ksi.shape[1]):
        for j in range( ksi.shape[2]):
            ksi[t,i,j] = alpha[t,i] + loga[i,j] + logb[j, emissions[t+1] ] + t
            ksi[t,:,:] -= self.log_sum( ksi[t,:,:].flatten() )

return ksi #Note: actually for use in Baum welch algorithm, it wouldn't need

cdef _seqs_check( self, seqs, num , error_string ):

    mx = 0
    for s in seqs:
        mx = max( mx, numpy.max(s) )
    if mx >= num:
        raise ValueError( error_string, mx+1," vs ", num )

cpdef maximum_likelihood_estimation( self, s_seqs, e_seqs ):
    """
    Given dataset of state and emission sequences estimate the most likely paramet
    Parameters
    -----
    s_seqs : 2D ndarray or list of ndarrays, int
              hidden states sequences
    e_seqs:  2D ndarray or list of ndarrays, int
              observation (emission) symbols sequences
    """

    self._seqs_check( s_seqs, self._logb.shape[0], "Data has more hidden states t
    self._seqs_check( e_seqs, self._logb.shape[1], "Data has more observation syn

    cdef numpy.ndarray[int_t, ndim=1] sum_0, sum_last, sum_all, ss, es
    cdef numpy.ndarray[int_t, ndim=2] sum_move, sum_emit

    cdef int s_num = self._logb.shape[0] #number of states
    cdef int o_num = self._logb.shape[1] #number of possible observation symbols
    cdef int seq_num,it

    if isinstance(s_seqs, list): seq_num = len(s_seqs) #list of numpy vectors
    else: seq_num = s_seqs.shape[0]

    sum_0 = numpy.zeros ( s_num , dtype=numpy.int64)
    sum_last = numpy.zeros ( s_num , dtype=numpy.int64)
    sum_all = numpy.zeros ( s_num , dtype=numpy.int64)
    sum_move = numpy.zeros( (s_num,s_num) , dtype=numpy.int64)
    sum_emit = numpy.zeros( (s_num,o_num) , dtype=numpy.int64)

    for ss,es in zip( s_seqs, e_seqs):

```

```

sum_0[ss[0]]+= 1
sum_all[ss[0]]+= 1
sum_emit[ ss[0], es[0] ]+=1
sum_last[ ss[-1] ]+=1

for it in range(1, ss.size ):

    sum_all[ ss[it] ]+=1
    sum_move[ ss[it-1], ss[it] ]+=1
    sum_emit[ ss[it], es[it] ]+=1

self._logpi = numpy.log( sum_0 / seq_num )
self._loga = numpy.log( (sum_move.T / (sum_all-sum_last ) ).T )
self._logb = numpy.log( (sum_emit.T / sum_all).T )

cpdef states_confidence( self, e_seq ):
    """Given emission sequence, return probabilities that emission is generated by
    return self.single_state_prob( self.forward ( e_seq ), self.backward( e_seq )

def baum_welch( self, e_seqs, iterations = 10, **kwargs ):
    """
    Estimate parameters by Baum-Welch algorithm

    Parameters
    -----
    e_seqs:  2D ndarray or list of ndarrays
              observation (emission) symbols sequences
    iterations: Optional[int]
              number of algorithm iterations
    **est :   boolean
              if True return the vector of estimations for every iteration
              default: False

    Returns
    -----
    graph : (iterations + 1) ndarray
            if **est== True
            None otherwise

    References
    -----
    .. [1] Rabiner, L. R.: A tutorial on hidden Markov models and selected applic-
           ations in speech recognition. Proceedings of the IEEE, volume 77, no. 2
           1989: pp. 257-286.
    """
    if 'est' in kwargs:
        if kwargs['est'] == True:
            return self._baum_welch( e_seqs, True, iterations )

    self._baum_welch( e_seqs, False, iterations )

cpdef _baum_welch(self, data, int est, iterations = 10 ):
    """

```

```

"""
Estimate parameters by Baum-Welch algorithm.
Called internally by baum_welch function.
"""

self._seqs_check( data, self._logb.shape[1], "Data has more observation symbols than possible observation symbols")

cdef numpy.ndarray[float_t, ndim=1] gamma_sum, pi_sum, gamma_full_sum, gamma_part_sum
cdef numpy.ndarray[int_t, ndim=1] row
cdef numpy.ndarray[float_t, ndim=2] alpha, beta, gamma, ksi_sum, obs_sum
cdef numpy.ndarray[float_t, ndim=3] ksi

cdef int s_num = self._logb.shape[0] #number of states
cdef int o_num = self._logb.shape[1] #number of possible observation symbols
cdef int i,j,t,it, seq_num

if isinstance(data, list): seq_num = len(data) #list of numpy vectors
else: seq_num = data.shape[0] #numpy matrix

if est:
    graph = numpy.zeros(iterations+1)

for it in range( iterations ):

    print("iteration ", it+1, "/", iterations )

    ksi_sum = numpy.full( ( s_num, s_num ) , numpy.log(0), dtype=numpy.float64 )
    obs_sum = numpy.full( ( s_num, o_num ) , numpy.log(0), dtype=numpy.float64 )
    pi_sum = numpy.full( s_num , numpy.log(0), dtype=numpy.float64 )
    gamma_part_sum = numpy.full( s_num , numpy.log(0), dtype=numpy.float64 )
    gamma_full_sum = numpy.full( s_num , numpy.log(0), dtype=numpy.float64 )
    gamma_sum = numpy.empty( s_num , dtype=numpy.float64 )

    for row in data:

        alpha = self.forward ( row )
        beta = self.backward( row )

        gamma = self.single_state_prob( alpha, beta )
        ksi = self.double_state_prob( alpha, beta, row )

        if est:
            graph[it] += self.log_sum( alpha[-1,:] )

    #expected number of being in state i in time 0
    for i in range( s_num ):

```

```

pi_sum[i] = self.log_sum_elem( pi_sum[i], gamma[0,i] )

#expected number of transition from i to j
for i in range( s_num ):
    for j in range( s_num ):
        ksi_sum[i,j] = self.log_sum_elem( ksi_sum[i,j], self.log_sum(

#expected number of transition from state i
for i in range( s_num ):
    gamma_sum[i] = self.log_sum( gamma[:-1,i] )

#sum gamma to the whole dataset array
for i in range ( s_num ):
    gamma_part_sum[i] = self.log_sum_elem( gamma_part_sum[i], gamma_su

#expected number of visiting state i and observing symbol v
for t in range( row.shape[0] ):
    for i in range( s_num ):
        obs_sum[i,row[t]] = self.log_sum_elem( obs_sum[i,row[t]], gamm

#expected number of visiting state i
for i in range( s_num ): #full length sum
    gamma_sum[i] = self.log_sum_elem( gamma_sum[i], gamma[-1,i] )

#sum gamma to the whole dataset array
for i in range ( s_num ):
    gamma_full_sum[i] = self.log_sum_elem( gamma_full_sum[i], gamma_su

#Update parameters:

#initial probabilities estimation
self._logpi = pi_sum - numpy.log( seq_num ) #average
#transition matrix estimation
self._loga = (ksi_sum.T - gamma_part_sum).T
#observation symbol emission probabilities estimation
self._logb = (obs_sum.T - gamma_full_sum).T

if est:
    graph[iterations] = self.data_estimate( data)
    return graph

def meow(self):
    """Make the DtHMM to meow"""
    print('meow!')

def main():
    my_hmm = DtHMM()
    ..

```

```
my_hmm.meow()

if __name__ == "__main__":
    main()

    Overwriting dthmm.pyx

%%writefile setup.py
from setuptools import setup, Extension
from Cython.Build import cythonize
import numpy

extensions = [
    Extension(
        "dthmm",
        ["dthmm.pyx"],
        include_dirs=[numpy.get_include()],
        define_macros=[("NPY_NO_DEPRECATED_API", "NPY_1_7_API_VERSION")],
    )
]

setup(
    name="dthmm",
    ext_modules=cythonize(extensions),
)

    Overwriting setup.py

%%writefile art.py
import dthmm
import matplotlib.pyplot as plt
import matplotlib.cm as cm
import numpy
import scipy.linalg

import pandas as pd
from IPython.display import display

def print_parameters( hmm ):

    print("Initial probabilities ( $\pi$ ) :")
    display( pd.DataFrame(hmm.pi) )

    if hasattr(hmm, 'a'):
        print("Transition probabilities matrix (A):")
        display( pd.DataFrame(hmm.a) )

    else:
        print("Transition rate matrix (O):")
```

```

display( pd.DataFrame(hmm.q) )
print("Transition probabilities for one time unit :")
display( pd.DataFrame( scipy.linalg.expm(hmm.q) ) )

print("Emission probabilities matrix (B):")
display( pd.DataFrame(hmm.b) )

def plot_hmm( s_seq, e_seq, **kargs ):

    n = e_seq.shape[0]

    if 'time' in kargs:
        X = kargs['time']
    else:
        X = numpy.arange(n)
    Y0 = numpy.zeros(n)
    Y1 = numpy.ones(n)

    fig, ax = plt.subplots()

    ax.set_aspect('equal')

    plt.xlim( numpy.amin(X)-1, numpy.amax(X)+1 ), plt.xticks([])
    plt.ylim(-2,3), plt.yticks([])

    e_num = numpy.amax( e_seq )+1
    s_num = numpy.amax( s_seq )+1

    last_time = X[0] - 1;

    for (x,y,c) in zip(X,Y1,s_seq):
        plt.annotate( c , xy=(x, y), xycoords='data', xytext=(-5, -5), textcoords='offsetpoints',
            ax.add_artist(plt.Circle((x, y), 0.3, color=cm.gnuplot( c/s_num ), alpha=0.4))
        ax.arrow( last_time +0.3, y, -0.7+(x-last_time), 0, head_width=0.35, head_length=0.1, fc='k', ec='k')
        ax.arrow(x, y-0.3, 0, -0.3, head_width=0.35, head_length=0.1, fc='k', ec='k')
        last_time = x

    for (x,y,c) in zip(X,Y0,e_seq):
        ax.add_artist(plt.Circle((x, y), 0.3, color=cm.gnuplot( 0.9*c/e_num + 0.1), alpha=0.4))
        plt.annotate( c , xy=(x, y), xycoords='data', xytext=(-5, -5), textcoords='offsetpoints')

    plt.show()

Overwriting art.py

!pip install fredapi
!pip install hmms
!pip install cython
!python setup.py build_ext --inplace

```

Collecting fredapi

Downloading fredapi-0.5.2-py3-none-any.whl (11 kB)

Requirement already satisfied: pandas in /usr/local/lib/python3.10/dist-packages (

Requirement already satisfied: python-dateutil>=2.8.2 in /usr/local/lib/python3.10/

Requirement already satisfied: pytz>=2020.1 in /usr/local/lib/python3.10/dist-pack

Requirement already satisfied: tzdata>=2022.1 in /usr/local/lib/python3.10/dist-pa

Requirement already satisfied: numpy>=1.21.0 in /usr/local/lib/python3.10/dist-pac

Requirement already satisfied: six>=1.5 in /usr/local/lib/python3.10/dist-packages

Installing collected packages: fredapi

Successfully installed fredapi-0.5.2

Collecting hmms

Downloading hmms-0.2.3.tar.gz (524 kB)

524.8/524.8 kB 3.5 MB/s eta 0:00:00

Preparing metadata (setup.py) ... done

Requirement already satisfied: Cython in /usr/local/lib/python3.10/dist-packages (

Requirement already satisfied: NumPy in /usr/local/lib/python3.10/dist-packages (f

Requirement already satisfied: ipython in /usr/local/lib/python3.10/dist-packages

Requirement already satisfied: matplotlib in /usr/local/lib/python3.10/dist-packag

Requirement already satisfied: pandas in /usr/local/lib/python3.10/dist-packages (

Requirement already satisfied: scipy in /usr/local/lib/python3.10/dist-packages (f

Requirement already satisfied: setuptools>=18.5 in /usr/local/lib/python3.10/dist-

Collecting jedi>=0.16 (from ipython->hmms)

Downloading jedi-0.19.1-py2.py3-none-any.whl (1.6 MB)

1.6/1.6 MB 22.7 MB/s eta 0:00:00

Requirement already satisfied: decorator in /usr/local/lib/python3.10/dist-package

Requirement already satisfied: pickleshare in /usr/local/lib/python3.10/dist-packa

Requirement already satisfied: traitlets>=4.2 in /usr/local/lib/python3.10/dist-pa

Requirement already satisfied: prompt-toolkit!=3.0.0,!<3.0.1,<3.1.0,>=2.0.0 in /us

Requirement already satisfied: pygments in /usr/local/lib/python3.10/dist-packages

Requirement already satisfied: backcall in /usr/local/lib/python3.10/dist-packages

Requirement already satisfied: matplotlib-inline in /usr/local/lib/python3.10/dist

Requirement already satisfied: pexpect>4.3 in /usr/local/lib/python3.10/dist-packa

Requirement already satisfied: contourpy>=1.0.1 in /usr/local/lib/python3.10/dist-

Requirement already satisfied: cycycler>=0.10 in /usr/local/lib/python3.10/dist-pack

Requirement already satisfied: fonttools>=4.22.0 in /usr/local/lib/python3.10/dist

Requirement already satisfied: kiwisolver>=1.0.1 in /usr/local/lib/python3.10/dist

Requirement already satisfied: packaging>=20.0 in /usr/local/lib/python3.10/dist-p

Requirement already satisfied: pillow>=6.2.0 in /usr/local/lib/python3.10/dist-pac

Requirement already satisfied: pyparsing>=2.3.1 in /usr/local/lib/python3.10/dist-

Requirement already satisfied: python-dateutil>=2.7 in /usr/local/lib/python3.10/c

Requirement already satisfied: pytz>=2020.1 in /usr/local/lib/python3.10/dist-pack

Requirement already satisfied: tzdata>=2022.1 in /usr/local/lib/python3.10/dist-pa

Requirement already satisfied: parso<0.9.0,>=0.8.3 in /usr/local/lib/python3.10/di

Requirement already satisfied: ptyprocess>=0.5 in /usr/local/lib/python3.10/dist-p

Requirement already satisfied: wcwidth in /usr/local/lib/python3.10/dist-packages

Requirement already satisfied: six>=1.5 in /usr/local/lib/python3.10/dist-packages

Building wheels for collected packages: hmms

Building wheel for hmms (setup.py) ... done

Created wheel for hmms: filename=hmms-0.2.3-cp310-cp310-linux_x86_64.whl size=21

Stored in directory: /root/.cache/pip/wheels/aa/6f/a4/1dbae244341f24881dce9465aa

Successfully built hmms

Installing collected packages: jedi, hmms

Successfully installed hmms-0.2.3 jedi-0.19.1

Requirement already satisfied: cython in /usr/local/lib/python3.10/dist-packages (

python3: can't open file '/content/setup.py': [Errno 2] No such file or directory


```

import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
import hmms
from matplotlib.colors import ListedColormap, BoundaryNorm
import matplotlib.dates as mdates
import matplotlib.patches as mpatches
from matplotlib.collections import LineCollection

import dthmm as hmms
from art import print_parameters, plot_hmm

import warnings
warnings.filterwarnings('ignore')

from fredapi import Fred
# FRED API key
fred_key = "f9c22fca078ece81a7a2ac6fba29b8a9";
# Initiates a session with the FRED datacenter to recieve datasets
fred = Fred(api_key=fred_key);
# Retrieve data from FRED API
fred_data = pd.DataFrame(fred.get_series('WTISPLC'), columns=['WTISPLC'])
fred_data.head()

```


	WTISPLC
1946-01-01	1.17
1946-02-01	1.17
1946-03-01	1.17
1946-04-01	1.27
1946-05-01	1.27


```

data_2000 = fred_data[fred_data.index > '2000-01-01']
data_2000.plot()

```

<Axes: >





```

price = data_2000['WTISPLC'];
# The first value is NaN as there is not a previous month to compare with
price_diff = price.diff()[1:];

# Replacing the change with 1 if positive, else 0
e_seq = np.array(price_diff.apply(lambda x: 1 if x > 0 else 0).values);

# Initialize a discrete-time Hidden Markov Model (HMM) with random parameters
# The model is configured with 3 hidden states and 2 observation symbols.
dhmm_r = hmms.DtHMM.random(3 , 2);

# Ensure e_seq is a 2D array (n_samples, 1)
e_seq = e_seq.reshape(1, -1) # Single sequence with length n_samples

# Train the Hidden Markov Model (HMM) using the Baum-Welch algorithm with a maximum of
dhmm_r.baum_welch(e_seq, 100); # 100 iterations

# Apply the Viterbi algorithm to find the most probable sequence of hidden states
( log_prob, s_seq ) = dhmm_r.viterbi(np.concatenate(e_seq).ravel());

# Add price
price_plot = pd.DataFrame(price[1:], index=price[1:].index)

# Add a column representing the regime
price_plot['Regime'] = s_seq

# Add a column representing the increase or decrease in price
price_plot['diff'] = price_diff

# Get means of all assigned states
means = price_plot.groupby(['Regime'])['diff'].mean()

# Obtain lists to sort regimes by their mean price differences

```

```
# Obtain lists to sort regimes by their mean price differences
lst_1 = means.index.tolist()
lst_2 = means.sort_values().index.tolist()

# Create a mapping from sorted regimes to original regimes
map_regimes = dict(zip(lst_2, lst_1))

# Apply the mapping to the 'Regime' column
price_plot['Regime'] = price_plot['Regime'].map(map_regimes)

# Plotting
fig, ax1 = plt.subplots(figsize=(20, 8))
ax1.plot(price_plot['WTISPLC'])

# Make 0 (Bear) - red, 1 (Stagnant) - blue, 2 (Bull) - green
cmap = ListedColormap(['r', 'b', 'g'], 'indexed')
norm = BoundaryNorm(range(3 + 1), cmap.N)

# Convert index to matplotlib date format
inxval = mdates.date2num(price_plot['WTISPLC'].index.to_pydatetime())
points = np.array([inxval, price_plot['WTISPLC']]).T.reshape(-1, 1, 2)
segments = np.concatenate([points[:-1], points[1:]], axis=1)

# Create a line collection with the segments and add it to the plot
lc = LineCollection(segments, cmap=cmap, norm=norm)
lc.set_array(price_plot['Regime'])
plt.gca().add_collection(lc)

# Set x and y limits
plt.xlim(price_plot['WTISPLC'].index.min(), price_plot['WTISPLC'].index.max())
plt.ylim(price_plot['WTISPLC'].min() - 10, price_plot['WTISPLC'].max() + 10) # Added

# Create legend patches
r_patch = mpatches.Patch(color='red', label='Bear')
g_patch = mpatches.Patch(color='green', label='Bull')
b_patch = mpatches.Patch(color='blue', label='Stagnant')

# Add legend
plt.legend(handles=[r_patch, g_patch, b_patch])


# Add title
plt.title(f'Regime Analysis for WTISPLC')

plt.show()

iteration 1 / 100
iteration 2 / 100
iteration 3 / 100
iteration 4 / 100
iteration 5 / 100
iteration 6 / 100
iteration 7 / 100
```

```
iteration 8 / 100
iteration 9 / 100
iteration 10 / 100
iteration 11 / 100
iteration 12 / 100
iteration 13 / 100
iteration 14 / 100
iteration 15 / 100
iteration 16 / 100
iteration 17 / 100
iteration 18 / 100
iteration 19 / 100
iteration 20 / 100
iteration 21 / 100
iteration 22 / 100
iteration 23 / 100
iteration 24 / 100
iteration 25 / 100
iteration 26 / 100
iteration 27 / 100
iteration 28 / 100
iteration 29 / 100
iteration 30 / 100
iteration 31 / 100
iteration 32 / 100
iteration 33 / 100
iteration 34 / 100
iteration 35 / 100
iteration 36 / 100
iteration 37 / 100
iteration 38 / 100
iteration 39 / 100
iteration 40 / 100
iteration 41 / 100
iteration 42 / 100
iteration 43 / 100
iteration 44 / 100
iteration 45 / 100
iteration 46 / 100
iteration 47 / 100
iteration 48 / 100
iteration 49 / 100
iteration 50 / 100
iteration 51 / 100
iteration 52 / 100
iteration 53 / 100
iteration 54 / 100
iteration 55 / 100
iteration 56 / 100
iteration 57 / 100
iteration 58 / 100
iteration 59 / 100
iteration 60 / 100
iteration 61 / 100
```

```
iteration 62 / 100
iteration 63 / 100
iteration 64 / 100
iteration 65 / 100
iteration 66 / 100
iteration 67 / 100
iteration 68 / 100
iteration 69 / 100
iteration 70 / 100
iteration 71 / 100
iteration 72 / 100
iteration 73 / 100
iteration 74 / 100
iteration 75 / 100
iteration 76 / 100
iteration 77 / 100
iteration 78 / 100
iteration 79 / 100
iteration 80 / 100
iteration 81 / 100
iteration 82 / 100
iteration 83 / 100
iteration 84 / 100
iteration 85 / 100
iteration 86 / 100
iteration 87 / 100
iteration 88 / 100
iteration 89 / 100
iteration 90 / 100
iteration 91 / 100
iteration 92 / 100
iteration 93 / 100
iteration 94 / 100
iteration 95 / 100
iteration 96 / 100
iteration 97 / 100
iteration 98 / 100
iteration 99 / 100
iteration 100 / 100
```



The above plot shows the period of bear regimes with red color, bull regimes with green color and stagnant regimes with blue color.

✓ Step 9

In order to implement the minimal working example of a hill climb search for learning Bayesian Network, the provided example in the thesis is followed on the combined data of macroeconomic and financial datasets that we have and the pgmpy library is used.

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
from collections import Counter
import statsmodels.api as sm
from scipy import stats
from statsmodels.tsa.stattools import kpss, adfuller
from statsmodels.graphics.tsaplots import plot_acf, plot_pacf
from statsmodels.stats.diagnostic import acorr_ljungbox

from fredapi import Fred
# FRED API key
fred_key = "f9c22fca078ece81a7a2ac6fba29b8a9";
# Initiates a session with the FRED datacenter to receive datasets
fred = Fred(api_key=fred_key);
# Retrieve data from FRED API
fred_data = pd.DataFrame(fred.get_series('WTISPLC'), columns=['WTISPLC'])

datasets_fred = [
    'WTISPLC',      # Spot Crude Oil Price: West Texas Intermediate (WTI) (WTISPLC)
    'CPIENGSL',    # Consumer Price Index for All Urban Consumers: Energy in U.S. City Average
    'CAPG211S',    # Industrial Capacity: Mining: Oil and Gas Extraction (NAICS = 211)
    'CAPUTLG211S', # Capacity Utilization: Mining: Oil and Gas Extraction (NAICS = 211)
    'IPG211S',     # Industrial Production Index: Mining: Oil and Gas Extraction (NAICS = 211)
    'INDPRO',      # Industrial Production: Total Index
    'IPN213111N',  # Industrial Production: Mining: Drilling Oil and Gas Wells
    'PCU211211',   # Producer Price Index: Mining: Oil and Gas Extraction (NAICS = 211)
];
```

```
data_frames = []; # List of dataframes to be concatenated

# Adding FRED datasets
for series_id in datasets_fred:
    # Get series from FRED
    df = pd.DataFrame(fred.get_series(series_id), columns=[series_id]);
    data_frames.append(df);

macro_data = pd.concat(data_frames, axis=1)
#macro_data = macro_data[macro_data.index > '2000-01-01']

financial_datasets_fred = [
'DEXCAUS', #Canadian dollar to US dollar exchange rate
'VIXCLS', #CBOE Volatility Index
'DCOILWTICO', #WTI Crude oil futures
'DCOILBRETEU', #Brent crude oil futures
'SP500', #S&P500 Index
];

finan_data_frames = []; # List of dataframes to be concatenated

# Adding FRED datasets
for series_id in financial_datasets_fred:
    # Get series from FRED
    df = pd.DataFrame(fred.get_series(series_id), columns=[series_id]);
    finan_data_frames.append(df);

fin_data = pd.concat(finan_data_frames, axis=1)
#fin_data = data_merge[fin_data.index > '2000-01-01']

data = pd.merge(macro_data, fin_data, left_index=True, right_index=True)
data.head()
```

	WTISPLC	CPIENGL	CAPG211S	CAPUTLG211S	IPG211S	INDPRO	IPN213111N
1971-02-01	3.56	26.2	NaN	NaN	NaN	37.4386	NaN
1971-03-01	3.56	26.2	NaN	NaN	NaN	37.3980	NaN
1971-04-01	3.56	26.1	NaN	NaN	NaN	37.6080	NaN
1971-06-01	3.56	26.3	NaN	NaN	NaN	37.9574	NaN
1971-07-01	3.56	26.3	NaN	NaN	NaN	37.8472	NaN

```
!pip install pgmpy
Collecting pgmpy
  Downloading pgmpy-0.1.25-py3-none-any.whl (2.0 MB)
    _____ 2.0/2.0 MB 9.1 MB/s eta 0:00:00
Requirement already satisfied: networkx in /usr/local/lib/python3.10/dist-packages
```

```

Requirement already satisfied: numpy in /usr/local/lib/python3.10/dist-packages (f
Requirement already satisfied: scipy in /usr/local/lib/python3.10/dist-packages (f
Requirement already satisfied: scikit-learn in /usr/local/lib/python3.10/dist-pack
Requirement already satisfied: pandas in /usr/local/lib/python3.10/dist-packages (
Requirement already satisfied: pyparsing in /usr/local/lib/python3.10/dist-package
Requirement already satisfied: torch in /usr/local/lib/python3.10/dist-packages (f
Requirement already satisfied: statsmodels in /usr/local/lib/python3.10/dist-packa
Requirement already satisfied: tqdm in /usr/local/lib/python3.10/dist-packages (fr
Requirement already satisfied: joblib in /usr/local/lib/python3.10/dist-packages (
Requirement already satisfied: opt-einsum in /usr/local/lib/python3.10/dist-packag
Requirement already satisfied: python-dateutil>=2.8.2 in /usr/local/lib/python3.10
Requirement already satisfied: pytz>=2020.1 in /usr/local/lib/python3.10/dist-pack
Requirement already satisfied: tzdata>=2022.1 in /usr/local/lib/python3.10/dist-pa
Requirement already satisfied: threadpoolctl>=2.0.0 in /usr/local/lib/python3.10/c
Requirement already satisfied: patsy>=0.5.6 in /usr/local/lib/python3.10/dist-pack
Requirement already satisfied: packaging>=21.3 in /usr/local/lib/python3.10/dist-p
Requirement already satisfied: filelock in /usr/local/lib/python3.10/dist-packages
Requirement already satisfied: typing-extensions>=4.8.0 in /usr/local/lib/python3.
Requirement already satisfied: sympy in /usr/local/lib/python3.10/dist-packages (f
Requirement already satisfied: jinja2 in /usr/local/lib/python3.10/dist-packages (
Requirement already satisfied: fsspec in /usr/local/lib/python3.10/dist-packages (
Collecting nvidia-cuda-nvrtc-cu12==12.1.105 (from torch->pgmpy)
  Using cached nvidia_cuda_nvrtc_cu12-12.1.105-py3-none-manylinux1_x86_64.whl (23.
Collecting nvidia-cuda-runtime-cu12==12.1.105 (from torch->pgmpy)
  Using cached nvidia_cuda_runtime_cu12-12.1.105-py3-none-manylinux1_x86_64.whl (8
Collecting nvidia-cuda-cupti-cu12==12.1.105 (from torch->pgmpy)
  Using cached nvidia_cuda_cupti_cu12-12.1.105-py3-none-manylinux1_x86_64.whl (14.
Collecting nvidia-cudnn-cu12==8.9.2.26 (from torch->pgmpy)
  Using cached nvidia_cudnn_cu12-8.9.2.26-py3-none-manylinux1_x86_64.whl (731.7 ME
Collecting nvidia-cublas-cu12==12.1.3.1 (from torch->pgmpy)
  Using cached nvidia_cublas_cu12-12.1.3.1-py3-none-manylinux1_x86_64.whl (410.6 M
Collecting nvidia-cufft-cu12==11.0.2.54 (from torch->pgmpy)
  Using cached nvidia_cufft_cu12-11.0.2.54-py3-none-manylinux1_x86_64.whl (121.6 M
Collecting nvidia-curand-cu12==10.3.2.106 (from torch->pgmpy)
  Using cached nvidia_curand_cu12-10.3.2.106-py3-none-manylinux1_x86_64.whl (56.5
Collecting nvidia-cusolver-cu12==11.4.5.107 (from torch->pgmpy)
  Using cached nvidia_cusolver_cu12-11.4.5.107-py3-none-manylinux1_x86_64.whl (124
Collecting nvidia-cuspars-cu12==12.1.0.106 (from torch->pgmpy)
  Using cached nvidia_cuspars-cu12-12.1.0.106-py3-none-manylinux1_x86_64.whl (196
Collecting nvidia-nccl-cu12==2.20.5 (from torch->pgmpy)
  Using cached nvidia_nccl_cu12-2.20.5-py3-none-manylinux2014_x86_64.whl (176.2 ME
Collecting nvidia-nvtx-cu12==12.1.105 (from torch->pgmpy)
  Using cached nvidia_nvtx_cu12-12.1.105-py3-none-manylinux1_x86_64.whl (99 kB)
Requirement already satisfied: triton==2.3.1 in /usr/local/lib/python3.10/dist-pac
Collecting nvidia-nvjitlink-cu12 (from nvidia-cusolver-cu12==11.4.5.107->torch->pg
  Downloading nvidia_nvjitlink_cu12-12.5.82-py3-none-manylinux2014_x86_64.whl (21.
      21.3/21.3 MB 47.2 MB/s eta 0:00:00
Requirement already satisfied: six in /usr/local/lib/python3.10/dist-packages (fr
Requirement already satisfied: MarkupSafe>=2.0 in /usr/local/lib/python3.10/dist-p
Requirement already satisfied: mpmath<1.4,>=1.1.0 in /usr/local/lib/python3.10/dis
Installing collected packages: nvidia-nvtx-cu12, nvidia-nvjitlink-cu12, nvidia-nc
Successfully installed nvidia-cublas-cu12-12.1.3.1 nvidia-cuda-cupti-cu12-12.1.105

```

```
import pandas as pd
```

```
from sklearn.models import BayesianModel
```



```

from pgmpy.models import BayesianModel
from pgmpy.estimators import HillClimbSearch, BayesianEstimator, K2Score
import networkx as nx
import matplotlib.pyplot as plt
from fredapi import Fred

# Drop rows with missing values
data.dropna(inplace=True)

# Discretize the data for HMM
combined_data_diff = data.diff().dropna()
discretized_data = combined_data_diff.applymap(lambda x: 1 if x > 0 else 0)

# Load the discretized training data
train_data = discretized_data

# Hill Climbing Search Implementation
hc = HillClimbSearch(train_data)

# Expert knowledge model initialization
expert = BayesianModel()
expert.add_nodes_from(datasets_fred + financial_datasets_fred)
expert.add_edges_from([
    ('WTISPLC', 'DEXCAUS'),      # Example edges, replace with actual expert knowledge
    ('CPIENGSL', 'VIXCLS'),
    ('CAPG211S', 'DCOILWTICO'),
    ('CAPUTLG211S', 'SP500'),
    ('IPG211S', 'DCOILBRETEU'),
    ('INDPRO', 'SP500'),
    ('IPN213111N', 'WTISPLC'),
    ('PCU211211', 'WTISPLC'),
])

# Perform Hill Climbing search and create a BayesianModel from the estimated DAG
model_structure = hc.estimate(scoring_method=K2Score(train_data)) # Estimate the DAG st
model = BayesianModel(model_structure.edges()) # Create a BayesianModel from the DAG

# Fit the model to training data
model.fit(train_data, state_names=dict(map(lambda e: (e, [0, 1, 2]), datasets_fred + fi

# Visualize the learned Bayesian Network
G = nx.Graph()
G.add_edges_from(model.edges())
pos = nx.spring_layout(G)
nx.draw_networkx_nodes(G, pos, node_size=10)
nx.draw_networkx_edges(G, pos, arrows=True)
plt.figure(5, figsize=(20, 10))
plt.show()


```

WARNING:pgmpy:BayesianModel has been renamed to BayesianNetwork. Please use Bayesi

0%

20/1000000 [00:00<9:41:39, 28.65it/s]

WARNING:pgmpy:BayesianModel has been renamed to BayesianNetwork. Please use Bayesi



<Figure size 2000x1000 with 0 Axes>

In the above plot, the nodes represent the variables of the dataset and edges represent the dependencies between them. Here, the nodes with many connections can be the key variables. Now, the model has been fitted using the hill climb search and inferences can be made using forecasts as evidence.

