


TO BE COMPLETED AND RETURNED BY THE SELLER

Technical Compliance Checklist

Winding Machines · Soft Winding · Hard Winding · Sewing Thread



- Mark **YES** or **NO** on every line. Leave none blank.
- **YES** = the machine offered meets the requirement in full, as stated. Anything partial or conditional is **NO**.
- Explain every **NO** in *Remarks*, stating what is offered instead.

Company		Contact	
Offer ref.		Date	

SECTION A — Electrical Supply all three machines

#	REQUIREMENT	YES	NO	REMARKS / OBSERVATIONS
A1	Electrical supply: 3PH 380–440 V AC or 1PH 220–230 V AC , with PE and N.	☐	☐	
A2	Supply frequency: 50 Hz .	☐	☐	

SECTION B — Soft Winding Machine 48 spindles

#	REQUIREMENT	YES	NO	REMARKS / OBSERVATIONS
B1	48 winding spindles .	☐	☐	
B2	Yarn range: cotton 10/1–50/1 and 20/2–100/2 ; spun polyester 20/2–60/2 SSP ; filament polyester 50 D–300 D .	☐	☐	

#	REQUIREMENT	YES	NO	REMARKS / OBSERVATIONS
B3	Finished package: 160 mm diameter, 1 kg.	☐	☐	
B4	Package density: 0.30–0.35 g/cm³ for cotton, 0.35–0.40 g/cm³ for polyester.	☐	☐	
B5	Winding speed: up to 1 000 m/min.	☐	☐	
B6	Bobbin: 160.40 mm overall (143.00 mm body), ends 10.40 / 7.00 mm, diameters 54.70 / 49.60 / 43.15 mm and 43.15 / 48.80 / 52.90 mm.	☐	☐	

SECTION C — Hard Winding Machine 60 spindles

#	REQUIREMENT	YES	NO	REMARKS / OBSERVATIONS
C1	60 winding spindles.	☐	☐	
C2	Yarn range: cotton 10/1–50/1 and 20/2–100/2 .	☐	☐	
C3	Finished cone: 150 mm top diameter, 180 mm bottom diameter, 155 mm height, 1 kg.	☐	☐	
C4	Package hardness / density: 0.40–0.50 g/cm³.	☐	☐	
C5	Winding speed: up to 1 000 m/min.	☐	☐	
C6	Bobbin: conical, 173.00 mm overall, large end 71.00 / 67.00 mm, small end 37.00 / 26.00 mm.	☐	☐	

SECTION D — Sewing Thread Machine 48 spindles

#	REQUIREMENT	YES	NO	REMARKS / OBSERVATIONS
D1	48 winding spindles.	☐	☐	
D2	Yarn range: spun polyester 20/2–100/2 SSP and 16/3–80/3 SSP.	☐	☐	
D3	Thread length / weight: 4 000 m per 100 g at count 50/2 spun.	☐	☐	
D4	Winding speed: up to 1 400 rpm.	☐	☐	
D5	Yarn tension control provided.	☐	☐	
D6	Automatic doffing and feeding provided.	☐	☐	
D7	Bobbin: conical, 114.00 mm overall, large end 38.00 / 35.00 mm, small end 28.00 / 12.60 mm.	☐	☐	

SECTION E — Declaration to be completed last

I confirm that the 21 responses above accurately describe the machines offered, and that every **NO** is explained in the corresponding Remarks field.

Name		Position	
Signature		Date	

Note

Requirements are taken from the consolidated document “Winding Machine Technical Specification — Soft Winding, Hard Winding & Sewing Thread”. Technical scope only; commercial terms are not covered by this checklist.