A-Lite: a spatial queue model for Bailey Hall

Mechanism audit, mathematical specification and comparative experiments

---

Abstract

This report tests whether a spatial queue representation can remove unsupported microscopic detail while retaining the full audience, original graph, finite passage storage, physical gate capacities, heterogeneous response and imperfect guidance. Numerical corrections, individual ablations, operational optimization and calibration changes are evaluated separately. Original Model A remains the benchmark. Independent confirmation, failures, time-step sensitivity and the effects lost by simplification determine the recommendation.

Study	Bailey Hall, full-house evacuation
Audience	1,329 occupants, including three wheelchair users
Base revision	Mateus, `3e4bcf0`, 8 November 2026, 04:20:42 EST
Report date	8 November 2026
Scope	Research model; assumptions and calibration limits stated explicitly

Contents

1 Movement mechanisms: evidence and simplification 1

2 Behavioral mechanisms: evidence and simplification 1

3 Spatial queues and travel 2

4 Service, counterflow and conservation 3

5 Response, route choice and visibility 4

6 Essential parameters and reproducible choice weights 4

7 Numerical artifacts and isolated verification 5

8 Progressive ablations in original A 6

9 Guidance, visibility and operational search 7

10 Independent confirmation and transfer 8

11 Last-person delays, queues and exit utilization 9

12 Blocked-door and physical sensitivities 10

13 Time-step sensitivity and runtime 11

14 Changes and reproduction 12

15 Recommendation and answers 13

References 14

Independent confirmation: A-Lite 191.4 s [188.3, 194.6]; the mean 180-second target was not achieved. All forty A-Lite audiences cleared; six cleared by 180 s. The same guidance gives 259.0 s in A and 166.4 s in B. These are model-dependent predictions, not estimates to average together.

The reference is Mateus's 8 November 2026, 04:20:42 EST commit `3e4bcf0`. The previous source was saved before this extension. Original A remains available when optional switches are absent. Every new operational finalist has **no barriers**, retains 1,329 people and three wheelchair users, and uses unchanged geometry, gate rates, body-size/speed/response distributions and imperfect compliance. A-Lite deliberately simplifies group motion; that structural change is not an operational achievement.

The companion **MODEL_GUIDE.pdf** develops the full model ladder and shared mathematics. This report specifies A-Lite, audits mechanisms and reports verification and experiments. Historical panel-based winners remain in **RESULTS_AND_CHANGES.pdf**; they are not proposed egress installations.

1 Movement mechanisms: evidence and simplification

Table 1: Movement mechanisms: evidence and simplification.

Mechanism	Classification and calibration	A-Lite treatment; information lost
1,329 audience, three wheelchairs, three seating levels	Bailey-specific problem specification	Retain all people and sampled traits; no occupancy reduction
268 nodes, 384 links, widths, slopes, exit connectivity	Bailey-specific reconstruction; many dimensions approximate	Retain every original link and distance; no contraction or new path
Accessibility, one-way links, closures	Bailey-specific requirements represented by graph attributes	Retain restrictions and discovery; a graph check does not establish installation compliance
Following gap and H=0.7 s	Empirically supported mechanism; generic coefficient [R4, R19]	Replace microscopic speed adjustment by the same representative rate J=v/(d+vH); lose individual gap trajectories
Acceleration relaxation, tau=0.5 s	Generic assumption, not calibrated to Bailey	Constant transit speed; no startup acceleration or braking waveform. Tested separately in A
Row cap 0.45, squeeze 0.20 m/s, 0.38 m obstruction lookahead	Literature supports row constraints; squeeze speed and detection distance generic [R18]	Seat-to-end distance / capped speed plus finite row storage and end service; lose seated obstruction and passing awareness cues
Random zipper priority, impatience bonus, lateral gap checks	Generic implementation of merging	FIFO among ready lane heads, shared downstream storage; lose body-level merge negotiation
Counterflow friction, lane changes, timed squeeze relief	Opposing-flow effects supported; exact rules generic	Directional capacity sharing and conservative slot exchanges; lose friction waves, body contacts and spontaneous lane formation

2 Behavioral mechanisms: evidence and simplification

Table 2: Behavioral mechanisms: evidence and simplification.

Mechanism	Classification and calibration	Decision and loss
Heterogeneous free speed, elderly mix and body size	Empirically supported heterogeneity; Bailey values assumed	Retain sampled attributes; radius affects reference capacity and exchange feasibility, not collision simulation
Lognormal recognition, response, preparation	Empirically supported distribution family; local parameters generic [R5]	Retain draws and state transitions. Their computational cost is small; removing them would change the problem
Neighbor awareness and phase-clock acceleration	Social response supported; exact coefficients generic	Retain for comparability; row passing no longer supplies an extra awareness cue
Group readiness, common destination and pace	Empirically supported effects; waiting/cohesion thresholds generic [R13, R14]	Retain readiness/90 s timeout, leader destination, slowest member's free pace; remove spatial lag stops and distance-triggered breakup
Persistent Gumbel tastes and familiar-exit preference	Empirically supported discrete-choice family [R3]; weights uncalibrated	Retain stable preferences, imperfect guidance acceptance and locally visible queues; no perfect shortest-path obedience
Urgency, trust, belief decay, event cooldown	Generic hypotheses; potentially unnecessary without calibration	Compare with existing on/off switch. Prefer the simpler state when performance and robustness support it
Route commitment and occasional reconsideration	Route revision observed, but exact thresholds generic [R7]	Retain existing routing for controlled movement comparisons; invalidate exhausted paths before inertia is applied
Manager hearing, activation and radio	Empirical mechanisms; Bailey hearing/reach values assumed	Retain imperfect hearing and activation, actual post coordinates and acoustic approximation; staff bodies are still absent
LEDs and pre-announcement	Supported interventions; separate detection and acceptance probabilities assumed [R8, R9]	Prefer fixed, visibility-limited public signs; retain incomplete adoption. No brightness or head-occlusion calibration
Adaptive staff/partial FCFS controller	Research-supported optimization family [R10]; global information in partial mode is a strong assumption	Compare static and zone control; partial forecasts tested in A, not asserted equivalent in Lite
Storage and service credit	Conservation is essential; 4.5 persons/m^2 and minimum link slots generic	Count every person in each original link, including transit and waiting. No 30 s capacity bypass
Falls, contact pressure, smoke tenability	Stress approximations or absent mechanisms	A-Lite rejects falls and separated-group stress; it is not an injury, fire or rescue simulator

3 Spatial queues and travel

For link e, let L be walking length, w width, l lane count and g the drawing-length/walking-length ratio. A-Lite retains A's lane count and all original graph nodes. Each directed lane has a FIFO queue. At entry, choose the least occupied available lane; opposing traffic uses A's allowed-lane count. Different lanes can proceed concurrently. Within a passage lane, a later entrant cannot leave before an earlier one. Row occupants join their selected row-end queue in predicted arrival order because their origins differ along the row.

$$
\begin{aligned}
v_{i,e} &= \min\left(v_i, \min_{j \in \text{group}(i)} v_j\right) f_{\text{env}} f_{\text{stair}} \\
v_{i,\text{row}} &= \min(v_{i,e}, v_{\text{row}}) \\
a_{i,e} &= \text{entry}_{i,e} + \frac{L_e - s_{i,\text{entry}}}{v_{i,e}}
\end{aligned}
\tag{L1}
$$

The group minimum is omitted for ungrouped people or the separately configured meet-outside scenario. Stair ascent/descent ratios and the outdoor factor remain individual. Nonzero response precedes entry. A-Lite does not apply A's extra spatial cohesion stop or break groups according to Euclidean separation. This is a structural simplification, not unchanged group mechanics.

An agent travels by a clock until a_i,e, then waits for service and downstream storage. Interpolated coordinates place it on its actual link for signs, staff reach and regional occupancy. Queue positions are drawn back along their lane. These coordinates do not establish collision-free body packing or accurate sub-link density.

$$
\begin{aligned}
J_e &= \frac{l_e v_{\text{rep},e}}{2r_{\text{mean}} + v_{\text{rep},e} H} \\
S_e &= \max(l_e, \lfloor \rho_{\max} L_e g_e w_e \rfloor), \quad S_{\text{row}} = \max\left(1, \left\lfloor \frac{L_{\text{row}}}{2r_{\text{mean}}} \right\rfloor\right)
\end{aligned}
\tag{L2}
$$

The representative rate uses the inherited 1.2 m/s, H=0.7 s and mean radius 0.22 m; stairs use the inherited representative stair ratio. Actual travel still uses individual speeds. Door and stair entries also require their unchanged gate capacity C from the main guide. Multiple limits can bind, but no nominal physical rate is multiplied upward. Minimum lane slots mean S is not everywhere exactly floor(ρA), particularly on very short links.

4 Service, counterflow and conservation

With N_e,+ and N_e,− people currently occupying a passage, divide its service between directions by their demand shares. Empty passages accumulate no new discharge credit. Each row end is a separate service resource: people leaving opposite ends generally drain different row portions, so row-end capacities are not halved simply because both ends are used.

$$
\begin{aligned}
\alpha_{e,d} &= \frac{N_{e,d}}{N_{e,+} + N_{e,-}}, & C_{e,d} &= \alpha_{e,d} J_e \\
b^*_{e,d} &= b_{e,d} + C_{e,d} \Delta t, & n_{e,d} &\le \lfloor b^*_{e,d} \rfloor \\
b'_{e,d} &= \min(1, b^*_{e,d} - n_{e,d})
\end{aligned}
\tag{L3}
$$

One initial person of credit is allowed per direction. Hence cumulative passage discharges in both directions cannot exceed the integrated shared rate plus two initial persons. Idle credit is bounded after admissions; no long idle period earns a burst. The same inherited gate token account enforces exterior and stair admission, with conservative service integration enabled.

$$
\begin{gathered}
N'_e = N_e + \text{admissions}_e - \text{departures}_e, \quad 0 \le N'_e \le S_e \\
\text{admit } i \text{ to } e \text{ only if open, accessible to } i, \text{ and } N_e < S_e
\end{gathered}
\tag{L4}
$$

A reversal on the same link does not add occupancy. Two opposing queue heads may exchange slots at their common junction only when both have completed travel, both have discharge credit, any gate credits are

available, and the two body diameters fit the narrower link. Remove both before adding either. Counts and service are conserved; this is not a permission to overfill storage after waiting. Unresolved queues remain failures. The rule represents passing in an aggregate queue model, not proven collision-free trajectories.

Finite-storage pedestrian networks are supported as a modelling family by Guo, Huang and Wong (2011) [L-R1]. Restricted queues can produce representational deadlocks, including ones that swapping customers resolves, as discussed by Palmer, Harper and Knight (2018) [L-R2]. Neither paper calibrates this particular Bailey hybrid or its exchange rule.

5 Response, route choice and visibility

The original population's lognormal recognition/response/preparation draws, local social clocks and readiness waiting remain. The primary endpoint is still the last of all 1,329 people crossing an exterior boundary; assisted travel to street level is reported separately. Leaving a door and reaching the street are distinct route stages. An exhausted indoor route must be invalidated before selecting its continuation, otherwise a zero-length old path can defeat the route-inertia threshold.

$$\begin{aligned} c_{i,e} &= \text{walk}_{i,e} + \text{visibleQueueCost}_{i,e} + \text{opposingCost}_{i,e} + \text{ropeCost}_e \\ U_{i,g} &= -w_T \frac{T_{i,g}}{30} + w_F F_g + w_S S_{i,g} + 3 w_G G_{i,g} + w_I I_{\text{current}} + \varepsilon_{i,g} \\ \varepsilon_{i,g} &\sim \text{Gumbel}(0,1) \quad \text{(once per person and exit)} \end{aligned} \tag{L5}$$

These are the existing A equations, not a fresh parameter fit. Choice is restricted to known exits and accessible/open routes, with imperfect acceptance of staff, pre-announcement and signs. Persistent tastes mean the softmax formula describes the cross-sectional random-utility construction, not an independent redraw at every junction. Adaptive urgency/trust/memory can be switched off while preserving this simpler choice model.

Spatial signs retain floor, distance, facing and drawn wall/column occlusion. Manager reach is evaluated using the original graph and room approximation. A-Lite thus differs from B in its uncontracted spatial links, finite storage accounting for all transit, lane-level FIFO, row occupancy, queue location, and conservative opposing-slot exchanges. It is not B with a new label. It also retains more A behavior than a minimal queue network; the audit identifies which mechanisms still need calibration.

6 Essential parameters and reproducible choice weights

The primary tone-alarm population uses independent standard-normal draws for speed, recognition, response and preparation; the repeated Z notation below denotes the appropriate draw, not a single shared variate. With age factor f=0.78 for the sampled 25% elderly share and f=1 otherwise, speed is clipped to [0.5,2.0] m/s; wheelchair speed is 0.8. Recognition and response have log-scale sigma 0.6. Preparation is a 50:50 mixture, preserving a short nonzero preparation phase even without belongings.

$$\begin{aligned} v_i &= \text{clip}[f(1.2 + 0.25Z), 0.5, 2.0] \\ \tau_{\text{rec}} &= 6e^{0.6Z}, \qquad \tau_{\text{response}} = m_i e^{0.6Z} \\ m_i &= 14 L_{\text{level}} \exp\left[0.04 \min(d_{\text{aisle}}, 15) + 0.05 \frac{d_{\text{door}}}{10} - 0.15 I_{\text{familiar}}\right] \\ \tau_{\text{prepare}} &= \begin{cases} 6e^{0.6Z}, & \text{probability } 0.5, \\ 1.5e^{0.3Z}, & \text{otherwise.} \end{cases} \end{aligned} \tag{L6}$$

L_level is 1 for orchestra/mezzanine and 1.1 for balcony. Recognition and response clocks advance at $1+1.5\varphi$; preparation advances at 1. Here φ is nearby moving share plus half preparing/standing share. Additional awareness uses the implemented first-order probability $0.4\varphi\Delta t$. Staff activation is lognormal with median 10 s, sigma 0.5; hearing uses $1-\exp(-0.35)$ each second within eligible reach. Acceptance remains 0.8 before adaptive trust, preassignment reach/adoption 0.6/0.7, and LED notice/adoption 0.9/0.7. These numerical choices are inherited assumptions.

Table 3: Essential parameters and reproducible choice weights.

Type (population share)	T	Q	F	S	G	I	Replan
Shortest (0.20)	2.4	1.2	0.3	0.3	1.0	0.8	0.8
Habitual (0.35)	0.6	0.3	2.8	0.5	0.8	1.5	0.15
Follower (0.25)	0.8	0.4	0.9	2.8	1.0	1.0	0.5
Queue avoider (0.10)	1.4	2.8	0.4	0.2	1.0	0.6	0.9
Cooperative (0.05)	1.0	0.8	1.0	1.0	1.6	1.2	0.3
Impatient (0.05)	2.2	0.8	0.5	0.5	0.6	0.6	0.7

T/Q/F/S/G/I weight time, queues, familiarity, social choice, guidance and inertia in (L5); Replan is the probability of reconsidering at an eligible junction. They are uncalibrated qualitative orderings, retained to isolate movement changes. Queue cost is (Q/T) times visible Q_e/C_e with inherited narrow-door aversion; no perceived cost is added to physical travel time. Route inertia requires improvement above max(8 s,15% of remaining cost).

Gate capacity is $q\times\max(0.4,w-2b)\times0.97\times$environment$\times$urgency factor: q=1.3 for doors or 1.0 for stairs; b=0.15 or 0.09 m. Divided stairs apply boundary loss to each lane. The unchanged urgency factor is $(1+0.15u)[1-0.45\ \max(0,(u\times\text{meanImpatience}-0.35)/0.65)^2]$, with u=0.6. All complete configurations and the original population generator are saved; none of these weights is fitted to the 180-second target.

7 Numerical artifacts and isolated verification

A carried displacement across a link boundary but discarded the carry from stored velocity. An empty 12 m path took 10.1 s as one link and 13.7 s as 24 links. Including admitted carry restores 10.0–10.1 s without increasing free speed. At most one boundary is traversed per step, so very short links remain a discretization limitation.

A's following law used the leader's already-updated position. A paced platoon discharged at 1.0345 persons/s at a 0.1 s step, versus the intended 0.9375. Start-of-step positions restore 0.9375 at steps 0.1, 0.05 and 0.025 s. Correcting this optimistic artifact can slow a whole-building run.

An exhausted indoor route could retain zero remaining cost after an exterior crossing and prevent continuation toward street safety. Invalidating a path that lacks the current node before applying route inertia fixes this demonstrated failure. It is mandatory in Lite and optional in A; it does not alter the exterior reporting boundary.

Tests cover corridor FIFO, row distance, sustained door/stair service, simultaneous merges, opposing slot exchange, parallel lanes, every-step storage and population conservation, identical audience draws, wheelchair accessibility and blocked-door discovery. Each Lite direction's cumulative discharge is bounded by integrated service plus one initial person. No timed storage overflow is permitted. These are implementation checks, not Bailey calibration; aggregate queue coordinates do not prove collision-free body trajectories.




Figure 1: Empty-link segmentation and saturated following expose numerical artifacts with opposite effects.

The previous conservative gate integration preserves fractional service after admission. It is isolated from these new corrections. Queue costs and predicted waits affect route preferences; they are not added again to physical travel time. Original A permits multiple admissions at a junction: gaps, lanes and service constrain admission, not a blanket one-person-per-node rule.

8 Progressive ablations in original A

Four common training audiences test individual mechanisms before combining them. The control uses the refined A guidance with historical panels removed. Invalid early Lite prototypes are excluded from all final-model conclusions.

Table 4: Progressive ablations in original A.

Variant	Class	Mean s	Difference s
Open-route control	Guidance	236.4	0.0
Boundary velocity	Numerical	238.3	1.9
Synchronous headway	Numerical	245.0	8.6
Both corrections	Numerical	237.6	1.2
Instant acceleration	Structural	216.6	-19.8
Remove seated squeeze	Structural	242.4	6.0
FIFO merge priority	Structural	237.4	1.0
Group pace without spatial lag	Structural	231.3	-5.1
Adaptive individual state on	Behavioral	257.5	21.1
Legacy fixed staff	Guidance + hearing	245.4	9.0
Combined structural switches	Structural	216.0	-20.4

Acceleration removal produced the strongest individual improvement in this screen. Removing seated squeeze or random merging did not improve mean time. Static legacy staff also changes the hearing/version model, so it does not isolate redirection. All numerical corrections together gave 238.5 s; adding instant acceleration gave 207.9 s; adding all structural switches gave 212.3 s. Interactions cannot be obtained by adding individual effects.

A new partial-controller guard forecasts opposing intended-path arrivals over 10 or 20 s, retaining the chained-FCFS predictor. Four-audience means were 248.2 and 235.8 s versus control 236.4 s. Global intended-route knowledge remains an inherited strong assumption. No clear transferable benefit justified selecting this controller.

9 Guidance, visibility and operational search

The final per-lane FIFO model uses four common training audiences below. The first group shares the A-derived open-route plan. B-derived plans are separate candidates: cross-plan differences are not channel-only effects.

Table 5: Guidance, visibility and operational search.

Training configuration	Lite mean s	Incomplete
no-guidance	298.6	0/4
existing	254.9	0/4
staff	236.4	0/4
preassign	259.4	0/4
led	290.2	0/4
staff-led	229.3	0/4
combined	228.0	0/4
static-combined	242.6	0/4
group-consistent	224.8	0/4
visible-signs	224.6	0/4
B-visible	195.4	0/4
B-static	193.9	0/4

Abstract LEDs know each original seat block. Spatial signs carry fixed public messages and require range, facing angle and optionally clear sight through walls/columns/panels. Their notice/adoption values 0.9/0.7 are Bailey assumptions, not a decomposition of a trial's combined 66% redirection outcome [R8, R9]. More information did not consistently shorten evacuation.

`staticPlan` keeps instructions fixed under congestion but retains acoustic reach, manager-specific hearing and closure overrides. Static acoustic and adaptive zone policies both gave 201.8 s; legacy fixed staff gave 193.9 s. Removing LEDs from the acoustic policy gave 193.1 s. The selected Lite policy therefore uses staff plus preassignment, no LED, no barrier, and adaptive individual state off. Imperfect instruction acceptance and persistent route preferences remain.

Coverage with 6, 10, 12 and 18 staff gave 211.1, 204.4, 195.6 and 188.6 s on four audiences. Extra staff are an explicit resource. Staff bodies and their own evacuation are absent from the inherited audience model; placements are graph-based candidates, not surveyed installations.

Three final-formulation coordinate searches each evaluated 77 block plans on four audiences. A visible-sign plan improved 193.9 to 187.9 s; a ten-staff/no-LED plan 193.1 to 185.4 s; an eighteen-staff plan 188.6 to 186.3 s. Every trial is retained. Twelve training audiences then selected the optimized no-LED plan with eighteen coverage posts, mean 189.1 s. The 44-block plan was frozen before independent evaluation. Search does not prove a global optimum.

10 Independent confirmation and transfer

Training uses base seed 9001; forty fresh confirmation audiences use 20261109. The frozen configuration and timestamp are in `selection.json`. All failures remain. An unresolved audience makes the unconditional full-house mean unresolved. Median and p95 here describe last-person times across runs, not individual exit times.

Table 6: Independent confirmation and transfer.

Configuration / model	Mean [95% CI], s	Median / p95, s	SD, s	≤180	Failures
original-0420 / A	263.6 [259.9, 267.4]	263.1 / 283.3	11.6	0/40	0
original-0420 / B	227.1 [221.8, 232.3]	222.2 / 254.6	16.4	0/40	0
guidance-open / A	239.0 [235.6, 242.3]	236.2 / 258.0	10.5	0/40	0
numerically-corrected / A	Unresolved	—	—	0/40	1
corrected-instant / A	211.0 [207.5, 214.5]	209.9 / 227.3	10.9	0/40	0
best-lite / A	259.0 [254.7, 263.4]	258.8 / 279.3	13.6	0/40	0
best-lite / B	166.4 [163.2, 169.7]	165.9 / 177.6	10.1	38/40	0
best-lite / Lite	191.4 [188.3, 194.6]	191.1 / 208.9	9.8	6/40	0
ten-staff-lite / Lite	197.6 [194.2, 201.1]	198.2 / 215.4	10.8	0/40	0

Same-policy Lite minus A is **-67.6 s [-73.2, -62.0]**. This includes movement/group simplification and feedback on starts and choices, not just microscopic friction. Eighteen versus ten staff in Lite gives **-6.2 s [-10.9, -1.5]**. A-specific open-route guidance versus original A gives **-24.7 s [-29.2, -20.1]**.

Lite's 6/40 completion-within-180 fraction has Wilson interval [0.071, 0.291]; B's 38/40 has [0.835, 0.986]. Every complete A variant has zero passes. The Lite policy transfers poorly to A: 259.0 s versus 239.0 s for A-specific guidance. A model-specific winner is not a robust cross-model policy.

All-corrections A fails on seed 1902007568 with 36 people inside. Its 230.9 s mean over the other 39 audiences is completion-conditioned, not a successful full-house mean. The saved failure state shows stalled east orchestra aisles/rows with opposing destinations and two people not on a link. Fixing isolated numerical artifacts does not establish freedom from spatial gridlock; defaults remain unchanged.




Figure 2: Independent mean clearance and 95% intervals. The unresolved corrected-A row remains in the table, without a finite point on this chart.




Figure 3: Mean people remaining under original A and the same finalist policy in A, Lite and B.

11 Last-person delays, queues and exit utilization

Read-only instrumentation records every movement step, state/link/route changes and gate series. Observer-detached replay produces identical per-person starts, exterior exits, safety times and route switches. Final-50 trajectories are gzip JSON with position, lane, velocity, group cap and blocking time. Constraint-active durations overlap and cannot be added as causal delays.

For seed 1294506412, historical refined A clears at 223.8 s. At 180 s, 241 remain: zero in seating/rows, 16 aisles, 89 corridors, 39 stairs and 97 other links; 50 are in exterior queues (a subset). The final 50 start at mean 41.7 s, experience 17.4 stop episodes each and a maximum continuous stop of 66.7 s. Following limits are active for mean 97.9 s and acceleration limits for 96.3 s. The late tail is downstream, not solely delayed seating response.

On the Lite-selected policy and that seed, A clears at 285.5 s versus Lite 192.5 s; first exits are 22.3 and 20.8 s. At 180 s A retains 280 people (zero rows, 13 aisles, 83 corridors, 77 stairs, 107 other), Lite nine. Final-50 mean starts are 39.2 and 24.3 s; membership differs, and local social feedback changes realized readiness without changing sampled response distributions. Stop episodes average 18.1 and 13.8; maxima are 65.6 and 98.2 s. Lite still has substantial queue waiting.

Table 7: Last-person delays, queues and exit utilization.

Model	Peak regional density	Mean exposure	Mean largest gate queue	Mean inside at 180
A	4.4	29.1	116.4	272.0
B	5.3	16.1	33.2	0.1
Lite	4.2	18.2	39.1	10.3

Density is persons/m^2. Exposure is mean integrated excess above 2 persons/m^2, in persons·s/m^2 per occupant. Peak is the maximum over regions, times and runs. Gate queues count people targeting gates, not all internal waiting. Local density differs in resolution: sub-link in A, original whole links in Lite, contracted edges in B. Shared geographic regional density is more directly comparable. No density is interpreted as an injury threshold.

Table 8: Last-person delays, queues and exit utilization.

Exit group	A mean people	Lite mean people	B mean people
FOYER	528.0	532.7	547.2
PORTICO_W	285.5	286.8	286.8
PORTICO_E	290.0	288.9	284.0
STAGE_W	67.8	65.9	63.5
STAGE_E	56.5	54.9	53.5
BAL_NW	57.3	56.5	52.7
BAL_NE	43.8	43.5	41.5

Similar exit shares despite different clearance curves show that information about unused exits alone does not explain the discrepancy. Lite accumulates mean 50.6 s of queue waiting per person; the mean maximum individual wait is 152.8 s. These totals include outdoor continuation. Group readiness remains; additional spatial cohesion stops and distance-based breakup are removed.

Mean all-person street safety under the plan is 287.6 s in A and 235.3 s in Lite. B does not supply a finite assisted street-safety endpoint. All three include wheelchair users in building clearance.

Table 9: Last-person delays, queues and exit utilization.

Trace model	Peak 5-s exterior admissions/s	Whole-run exterior utilization	Largest gate queue
A	9.8	21.9%	123
Lite	13.4	32.4%	44

Utilization divides admissions by integrated nominal exterior capacity while anyone remains inside. Unused capacity includes periods without upstream supply and is not all avoidable waste. Peaks measure door admission, not the exterior-boundary crossing endpoint. Raw gate series retain the detailed resource-by-resource evidence.

12 Blocked-door and physical sensitivities

F3 is closed from the start, using inherited discovery and manager communication. Twelve new audiences, base 20261110, are paired with an open-door case. Static staff retains closure overrides. This stress scenario is not an intervention for reaching 180.

Table 10: Blocked-door and physical sensitivities.

Model	Open mean s	Blocked mean s	Paired difference [95% CI] s	Incomplete
A	262.1	271.3	9.2 [3.7, 14.7]	0/12
B	165.0	170.2	5.2 [-7.0, 17.5]	0/12
Lite	191.4	192.1	0.7 [-7.6, 8.9]	0/12

The required six-cell physical sensitivity grid uses twelve common training audiences and the same open-route A-derived guidance. Headway changes assumed passage capacity; row speed changes travel. These are calibration hypotheses, not operational gains [R4, R18, R19].

Table 11: Blocked-door and physical sensitivities.

Headway / row speed case	A mean s	Lite mean s
H0.7-row0.45	235.6	223.8
H0.6-row0.45	232.3	216.9
H0.5-row0.45	233.8	213.5
H0.7-row0.6	235.1	223.6
H0.6-row0.6	230.9	217.4
H0.5-row0.6	235.0	219.6

Under the selected Lite policy, H=0.7 s gives 189.1 s on twelve training audiences, H=0.6 gives 198.9 s and H=0.5 gives 192.1 s, with row speed unchanged. Rates alter queue information and subsequent routes, so full-building time need not improve monotonically. No tested alternative reaches 180; these results do not justify lowering congestion merely to force a pass.

13 Time-step sensitivity and runtime

A three-audience check retains the frozen policy. Nominal service tests converge, while the full behavioral system can change ordering, event timing and subsequent random decisions as the step changes. Matching audience seeds therefore does not guarantee identical later choices.

Table 12: Time-step sensitivity and runtime.

Model	Step 0.10: mean s	Step 0.05: mean s	Step 0.025: mean s
A	264.9	261.9	273.6
A-corrected	221.5	231.2	228.8
Lite	181.8	192.6	196.2

The small Lite sample did not establish convergence. The frozen policy was therefore also evaluated at finer steps on the same forty independent confirmation audiences. This is a robustness check after selection, not optimization over step size.

Table 13: Time-step sensitivity and runtime.

Step s	Lite mean s	95% CI	Paired difference vs 0.10 s
0.10	191.4	[188.3, 194.6]	reference
0.05	193.0	[188.5, 197.5]	1.5 [-3.6, 6.6]
0.025	188.7	[186.2, 191.2]	-2.7 [-5.8, 0.4]

These results quantify whole-model sensitivity. A saturated-service unit test does not establish convergence of adaptive evacuation outcomes. A favorable discretization must not be promoted as an operational improvement.

Runtime is measured after the main jobs, in one process with one warm-up per model and three matched audiences in rotating model order. It includes construction and simulation, excluding serialization. Lite averages about 1.15 times faster than A here, a modest runtime benefit; B is about twice as fast as A. Shared routing and guidance still consume work. Contended exploratory worker timings are retained but not used for speedup claims.

Table 14: Time-step sensitivity and runtime.

Model	Mean wall time ms	Median ms
A	2258.7	2254.8
B	1124.9	1091.8
Lite	1958.9	1894.4

14 Changes and reproduction

The earlier full suite passed 144 tests in 11 files. The final focused run passed 50 tests in three files, including a new blocked-door Lite regression and stronger every-step conservation assertions (145 total tests are now defined). Exact counts and build output are saved in `final-focused-tests.log` and `final-build.log`. Geometry and source hashes are in `verification.json`. All changes remain uncommitted.

Table 15: Changes and reproduction.

Component	Change and purpose
`LiteSimulation.ts`, `LiteMovement.ts`	Separate original-graph FIFO movement, strict storage, directional service, simpler group motion and density reporting
`Movement.ts`, `Routing.ts`, `Params.ts`	Optional numerical corrections and individual structural switches; original absent-flag behavior retained
`SimulationEngine.ts`, `MovementObserver.ts`	Optional movement factory and read-only diagnostic hooks; exact observer replay
`ManagerPolicy.ts`, `Guidance.ts`	Static acoustic staff policy and intended-counterflow forecast guard
Pool, optimizer and study scripts	A/B/Lite runs, complete configs, seeds, failures, source snapshots and final-50 trajectories
Movement/adaptive tests	Flow, storage, population, accessibility, closures, numerical counterexamples and guidance behavior
LaTeX pipeline	Editable sources, native mathematics, vector figures, cross-references and bibliography

Large raw records are losslessly compressed on GitHub. Run `python3scripts/restore-research-data.py` before using an analysis script that expects original JSON paths. Small runnable configurations and comparison CSVs remain uncompressed. The Python report builders read either format directly.

From `mateus-0420` with Node 22:

```
node--importtsxscripts/run-lite.ts--configresults/lite-study/best-config.json--seed1294506412--outresults/lite-study/reproduced.json
node--importtsxscripts/lite-study.ts--casesresults/lite-study/confirmation-cases.json--outresults/lite-study/reproduced-confirmation.json--seed20261109--runs40--workers3
```

```
node--importtsxscripts/lite-convergence.ts
npmtest
npmrunbuild
python3scripts/build-latex-docs.py--compile
python3scripts/check-research-pdfs.py
```

The generated `latex` directory is self-contained: compile its `.tex` files using Tectonic or XeLaTeX. The first Tectonic run may fetch TeX packages. Generation requires Python/PyMuPDF; plots use Matplotlib. Fonts and vector equations are embedded. The study README identifies the retained final-model evidence; superseded prototypes are excluded from the published branch. Each final dataset includes configuration, seeds, source hash identifying an exact shared snapshot in `results/source-snapshots`. Every optimizer evaluation is retained.

15 Recommendation and answers

Is A overcomplicated relative to evidence? Several microscopic and adaptive psychological rules use generic coefficients. More detail does not establish more realism. A remains valuable for exposing lane ordering, seated obstruction and spatial group interactions that queue models omit.

Which restrictions are unnecessary? Discarded admitted carry and invalid exhausted routes are demonstrated implementation artifacts. Acceleration is the strongest tested structural restriction; removing it is not a physical correction. Headway is a meaningful capacity mechanism, and its old discretization was optimistic. Removing seat squeezing or merge randomness did not consistently help. Group behavior cannot simply be deleted to claim success.

Why is B faster? It contracts walking links, aggregates seatway/lane travel, omits detailed spatial cohesion stops and retains optimistic receiving-storage/30-second relief. It still has heterogeneous response, preferences and group pace. Similar exit shares with very different clearance show that flow representation matters. Its under-180 result does not validate real Bailey performance.

Is Lite more credible? It is verified for stated population, storage and service invariants, not empirically validated. It retains the original spatial links and strict storage absent in B while omitting body-level interactions in A. This makes assumptions easier to inspect, not automatically more accurate. Queue coordinates cannot support contact-force, crush-injury or detailed body-level density claims.

Which model should be primary? Use A-Lite as the transparent operational-comparison model, original A as a required structural stress comparison, and B as an aggregate cross-check. Report time-step sensitivity and calibration uncertainty alongside results. The chosen Lite policy's poor transfer to A prevents calling it a robust building-wide solution. Corrected instant-acceleration A remains a structural sensitivity, not a validated replacement.

Was 180 achieved defensibly? Original A and Lite did not meet the independent mean target. The strongest complete new spatial-A alternative is 211.0 s after optional numerical fixes plus simplified acceleration. New open-route guidance alone gives 239.0 s. The historical 231.2 s A result used panels and is not a current installation recommendation. Lite gives 191.4 s at its nominal step; B gives 166.4 s under the same policy. No occupancy, response, compliance, geometry or physical rate was secretly changed. Finite search does not prove no better policy exists.

What would improve evidence for judges? Survey usable widths and visibility; measure seatway, aisle, stair and door trajectories/flow; observe group separation, response and actual staff/sign reach; compare with a suitable drill. These data could choose between model families and justify coefficients. Literature supports mechanisms, not venue-specific numerical validation. The defensible contribution is a transparent, reproducible comparison with explicit limits.

References

[R4] Seyfried, A., Steffen, B., Klingsch, W. & Boltes, M. (2005). *The fundamental diagram of pedestrian movement revisited.* Author manuscript. Experimental spacing–speed relation; does not calibrate Bailey's exact headway. Historical density-law source: Weidmann (1993), *Transporttechnik der Fussgänger*, IVT report 90 (institutional copy).

[R19] Johansson, A. (2009). *Constant-net-time headway as a key mechanism behind pedestrian flow dynamics.* Physical Review E 80, 026120. Author manuscript, DOI. Provides a mechanism and empirical comparison for net headway, not a venue-specific replacement parameter.

[R18] Spearpoint, M. & Xiang, X. (2011). *Calculating evacuation times from lecture theatre type rooms using a network model.* Fire Safety Science 10, 599–612. Primary paper, DOI. Campus trials supported constrained network modelling and found row-speed reduction could overpredict time. Their mostly young, familiar audience is not Bailey's mixed population.

[R5] Hopkin, C.G., Galea, E.R. & Deere, S.J. (2015). *A study of response behaviour in a theatre during a live performance.* Human Behaviour in Fire, pp. 385–398. Author manuscript. Unannounced theatre response data; precursor to the 2017 journal study DOI.

[R13] Moussaïd, M., Perozo, N., Garnier, S., Helbing, D. & Theraulaz, G. (2010). *The walking behaviour of pedestrian social groups and its impact on crowd dynamics.* PLOS ONE 5:e10047. Article.

[R14] Haghani, M., Sarvi, M., Shahhoseini, Z. & Boltes, M. (2019). *Dynamics of social groups' decision-making in evacuations*. Transportation Research Part C. Primary article. Supports investigating coordinated messages; exact operational rule remains a study assumption.

[R3] Train, K. (2009). *Discrete Choice Methods with Simulation*, second edition, chapter 3. Author-hosted chapter. Gumbel random utilities and logit; persistent tastes require the interpretation explained in the Model Guide route-choice section.

[R7] Liao, W., Kemloh Wagoum, A.U. & Bode, N.W.F. (2017). *Route choice in pedestrians: determinants for initial choices and revising decisions.* Journal of the Royal Society Interface. Author manuscript. Experimental initial allocation and relatively infrequent route changes.

[R8] Galea, E.R., Xie, H., Deere, S., Cooney, D. & Filippidis, L. (2017). *Evaluating the effectiveness of an improved active dynamic signage system using full scale evacuation trials.* Fire Safety Journal 91, 908–917. Author repository. Combined-signage/voice outcome; not independent Bailey detection and compliance parameters.

[R9] Filippidis and colleagues, *Visibility catchment area of exits and signs.* Research group description; related IAFSS paper, 2008. Motivates geometric eligibility before behavioral notice.

[R10] López-Carmona, M.A. & Paricio García, Á. (2021). *CellEVAC: an adaptive guidance system for crowd evacuation through behavioral optimization.* Safety Science. Author manuscript. Simulation-optimization precedent; its movement model and performance are not substituted for Mateus's.

[L-R1] Guo, R.-Y., Huang, H.-J. & Wong, S.C. (2011). *Collection, spillback, and dissipation in pedestrian evacuation: A network-based method.* Transportation Research Part B 45, 490–506. Author/institutional manuscript, DOI. Supports finite-storage spatial-flow modelling; its hexagonal-cell model is not this implementation.

[L-R2] Palmer, G.I., Harper, P.R. & Knight, V.A. (2018). *Modelling deadlock in open restricted queueing networks.* European Journal of Operational Research 266, 609–621. Author manuscript, DOI. Queue deadlock and model interpretation; no claim of pedestrian passing calibration.