

Lecture

# Foundations of Artificial Intelligence

## Part 5 – Informed Search

Dr. Mohsen Mesgar

Universität Duisburg-Essen

---

# Organization

- **Exam**
  - **Questions:** English **AND** German.
  - **Answers:** English **OR** German (**you can choose only one language**).
  - **Dictionary:** is allowed (only hard copy).
  - **Anmeldephase** läuft vom **02.05.2022** bis **13.05.2022**.
- **Homework:**
  - There are German and English versions of homework.
  - You can **do your homework** in **German**.

# Recall ...

## Search strategies

- **Breadth**-First Search (BFS),
- **Depth**-First Search (DFS),
- **Iterative** Deepening Search (IDS)

## Parameters:


- **b**: maximum **branching factor** of the search tree
- **d**: **depth** of the **optimal solution**
- **m**: **maximum depth** of the tree (may be  $\infty$ )

## O Notation

- Introduction





## Evaluation of search strategies

- **completeness**
- **optimality**
- time complexity
- space complexity



# Evaluation of search strategies


Search strategies are compared along the following dimensions

- completeness: 
- optimality: 
-  **time complexity:** How long does the search take?
-  **space complexity:** How much memory does the search need?

# Time complexity of BFS

**Time complexity:** number of nodes that need to be generated

- depth 0  $\rightarrow$  1 node
  - depth 1  $\rightarrow$  max  $b$  nodes
  - depth 2  $\rightarrow$  max  $b * b = b^2$  nodes
  - depth  $d \rightarrow$  max  $b^d$  nodes (goal state is here)
  - depth  $d+1 \rightarrow$  max  $b^{d+1}$  nodes
- **b**: maximum branching factor of the search tree
  - **d**: **depth of the optimal solution**
  - **m**: maximum depth of the state space (may be  $\infty$ )



- Total:  $1 + b + b^2 + b^3 \dots + b^d + b^{d+1} \rightarrow O(b^{d+1})$

# Time complexity of DFS


**Time complexity:** number of nodes that need to be generated

- follows each path until maximum depth  $m$

$$\rightarrow O(b^m)$$

- terrible if  $m$  much larger than  $d$

- **b**: maximum branching factor of the search tree
- **d**: depth of the optimal solution
- **m**: maximum depth of the state space (may be  $\infty$ )




# Time complexity of IDS

**Time complexity:** number of nodes that need to be generated

- $m$  never goes beyond  $d$


→  $O(b^d)$

- **b**: maximum branching factor of the search tree
- **d**: depth of the optimal solution
- **m**: maximum depth of the state space (may be  $\infty$ )



# Space complexity of BFS


- **Space complexity:** maximum number of nodes in memory
  - all nodes in a level should remain in memory
    - $O(b^{d+1})$






# Space complexity of DFS

- **Space complexity:** maximum number of nodes in memory
- only nodes in current path and their unexpanded siblings need to be stored  
→  $O(bm)$



# Space complexity of IDS

- **Space complexity:** maximum number of nodes in memory
- only nodes in **current path** and **their unexpanded siblings** need to be stored  
→  $O(bd)$



# Performance review summary

- Iterative deepening search uses only **linear space** and not much more time than other **uninformed algorithms**



	BFS	DFS	IDS
Complete?	Yes	No	Yes
Optimal?	Yes	No	Yes
Time complexity	$b^{d+1}$	$b^m$	$b^d$
Space complexity	$b^{d+1}$	$bm$	$bd$

# Any open questions?



# Where are we?

- ✶ Intelligence ✓
- ✶ Agents ✓
- ✶ Search
  - ✶ Uninformed ✓
  - ✶ **Informed**
  - ✶ Local

# In this lecture, you learn ...

- **Informed search algorithms using heuristics**
  - Greedy **best-first** search
  - A\* search
- **Heuristics**
  - Admissible
  - Consistent
  - How do we define and choose a good heuristic?

---

**Today**


---

# Informed Search

# Motivation

**Uninformed** search algorithms are **inefficient**

- they expand far **too many unpromising paths**



- average solution depth = 22
- BFS expands about  $3.1 \times 10^{10}$  nodes until depth 22
- Can we make it more efficient?



# Idea ...

- Instead of **randomly expanding nodes in a level**, ...
  - expand the **most promising node first**
  - How do we determine which node is the most promising one?
- **heuristics**

# Heuristics

Heuristics are **experience-based approximations** for solving a problem

- **Rule of thumb**
- **Heuristics may go wrong!**




# Heuristics

In tree-search algorithms, **a heuristic is a function  $f(n)$  for each node  $n$**

- it estimates **the ‘desirability’ of the node's state**

# Getting informed

Straight line distances between cities



Straight line distances (SLD) to the goal state


Arad	366	Mehadia	241
Bucharest	0	Neamt	234
Craiova	160	Oradea	380
Drobeta	242	Pitesti	100
Eforie	161	Rimnicu Vilcea	193
Fagaras	176	Sibiu	253
Giurgiu	77	Timisoara	329
Hirsova	151	Urziceni	80
Iasi	226	Vaslui	199
Lugoj	244	Zerind	374

# Let's refer to city names by their first letters

<b>Arad</b>	366	<b>Mehadia</b>	241
<b>Bucharest</b>	0	<b>Neamt</b>	234
<b>Craiova</b>	160	<b>Oradea</b>	380
<b>Drobeta</b>	242	<b>Pitesti</b>	100
<b>Eforie</b>	161	<b>Rimnicu Vilcea</b>	193
<b>Fagaras</b>	176	<b>Sibiu</b>	253
<b>Giurgiu</b>	77	<b>Timisoara</b>	329
<b>Hirsova</b>	151	<b>Urziceni</b>	80
<b>Iasi</b>	226	<b>Vaslui</b>	199
<b>Lugoj</b>	244	<b>Zerind</b>	374

# Let's refer to city names by their first letters

Arad	366	Mehadia	241
Bucharest	0	Neamt	234
Craiova	160	Oradea	380
Drobeta	242	Pitesti	100
Eforie	161	Rimnicu Vilcea	193
Fagaras	176	Sibiu	253
Giurgiu	77	Timisoara	329
Hirsova	151	Urziceni	80
Iasi	226	Vaslui	199
Lugoj	244	Zerind	374



A	366	M	241
B	0	N	234
C	160	O	380
D	242	P	100
E	161	R	193
F	176	S	253
G	77	T	329
H	151	U	80
I	226	V	199
L	244	Z	374

---

**Today**

UNIVERSITÄT  
DUISBURG  
ESSEN

*Offen im Denken*

---

# Greedy Best- First Search

# Greedy Best-first search

Heuristic function  $f(n) = h(n)$

- $h(n)$ : goal-oriented heuristic that estimates the cost from node  $n$  to the goal

**Greedy Best-first search expands** the node that **appears to be nearest to the goal** —> **It has the minimum cost**



**Example:**  $h_{SLD}(n)$  = **S**traight **L**ine **D**istance from  $n$  to Bucharest



# Greedy best-first search


**Example:**  $h_{\text{SLD}}(n)$  = **S**traight **L**ine **D**istance from **n** to Bucharest

A	366	M	241
B	0	N	234
C	160	O	380
D	242	P	100
E	161	R	193
F	176	S	253
G	77	T	329
H	151	U	80
I	226	V	199
L	244	Z	374




# Example: Greedy best-first search

Example:  $h_{\text{SLD}}(n)$  = straight-line distance from  $n$  to Bucharest




# Example: Greedy best-first search

Example:  $h_{\text{SLD}}(n)$  = straight-line distance from  $n$  to Bucharest



# Example: Greedy best-first search


Example:  $h_{\text{SLD}}(n)$  = straight-line distance from  $n$  to Bucharest



$A \rightarrow S \rightarrow F \rightarrow B$

# Here is the solution


$A \rightarrow S \rightarrow F \rightarrow B$



# Here is the solution

$A \rightarrow S \rightarrow F \rightarrow B$

What is the cost of this path (solution)?




# Here is the solution

$A \rightarrow S \rightarrow F \rightarrow B$

What is the cost of this path (solution)?

$140 + 99 + 211 = 450$




# Here is the solution

$A \rightarrow S \rightarrow F \rightarrow B$

What is the cost of this path (solution)?

$$140 + 99 + 211 = 450$$

Can you find another path with a lower cost?





# Here is the solution

$A \rightarrow S \rightarrow F \rightarrow B$


What is the cost of this path (solution)?

$$140 + 99 + 211 = 450$$

Can you find another path with a lower cost?



$A \rightarrow S \rightarrow R \rightarrow P \rightarrow B$

$$140 + 80 + 97 + 101 = 418$$





# Another example

Find a path from **Iasi (I)** to **Fagaras (F)** (with greedy best-first search)



# Loops in greedy best-first search

Find a path from Iasi to Fagaras (with greedy best-first search)



# Properties of greedy best-first search

**Completeness:** Do we always **find a solution** if one exists?

- **No** → can get stuck in loops
- complete in finite state space **if we check for repeated states**

**Optimality:** Do we always find **an optimal solution**?

- **No:** the path **Arad -> Sibiu -> Fagaras -> Bucharest** is not optimal

**Time complexity:**

- **$O(b^m)$ , like DFS**
- optimal case: best choice in each step → only  $d$  steps
- a good heuristic improves chances for encountering optimal case

**Space Complexity**

- has to keep all nodes in memory → same complexity as best-first search

# A\* Search

# A\* search



## Idea

- **avoid expanding paths** that are **already expensive**  
→ **evaluate complete path cost** (not only the cost to reach goal)

Heuristic function  $f(n) = g(n) + h(n)$



- $g(n)$  = **real cost** to reach node  $n$  from source
- $h(n)$  = estimated cost **to get from  $n$  to goal  $G$**
- $f(n)$  = **estimated cost of path to goal via  $n$**

# A\* search



A	366	M	241
B	0	N	234
C	160	O	380
D	242	P	100
E	161	R	193
F	176	S	253
G	77	T	329
H	151	U	80
I	226	V	199
L	244	Z	374



# A\* search



A	366	M	241
B	0	N	234
C	160	O	380
D	242	P	100
E	161	R	193
F	176	S	253
G	77	T	329
H	151	U	80
I	226	V	199
L	244	Z	374




# A\* search




A	366	M	241
B	0	N	234
C	160	O	380
D	242	P	100
E	161	R	193
F	176	S	253
G	77	T	329
H	151	U	80
I	226	V	199
L	244	Z	374

# A\* search



R (Rimnicu Vilcea) will be expanded because it has the lowest value for  $f(n)$ .


# A\* search




A\* search has found one possible path ...

But: A\* expands P next  
Greedy search would **not** do that.

# A\* search



# Avoiding loops in A\* search: Find a path from Iasi to Fagaras




City 1	City 2	SLD
I	F	154
N	F	103
V	F	142
U	F	205
Bucharest	F	176

City 1	City 2	Cost
I	N	87
I	V	92
V	U	142
U	Bucharest	85
Bucharest	F	211

# Avoiding loops in A\* search: Find a path from Iasi to Fagaras

City 1	City 2	SLD
I	F	154
N	F	103
V	F	142
U	F	205
Bucharest	F	176




City 1	City 2	Cost
I	N	87
I	V	92
V	U	142
U	Bucharest	85
Bucharest	F	211

**Always expand the node with the lowest value of the h function**

# Avoiding loops in A\* search: Find a path from Iasi to Fagaras

City 1	City 2	SLD
I	F	154
N	F	103
V	F	142
U	F	205
Bucharest	F	176




City 1	City 2	Cost
I	N	87
I	V	92
V	U	142
U	Bucharest	85
Bucharest	F	211

# Avoiding loops with A\* search: Find a path from Iasi to Fagaras

City 1	City 2	SLD
I	F	154
N	F	103
V	F	142
U	F	205
Bucharest	F	176

City 1	City 2	Cost
I	N	87
I	V	92
V	U	142
U	Bucharest	85
Bucharest	F	211






# Avoiding loops in A\* search: Find a path from Iasi to Fagaras

City 1	City 2	SLD
I	F	154
N	F	103
V	F	142
U	F	205
Bucharest	F	176

City 1	City 2	Cost
I	N	87
I	V	92
V	U	142
U	Bucharest	85
Bucharest	F	211




We skip irrelevant nodes to keep the visualization readable.


# Avoiding loops in A\* search: Find a path from Iasi to Fagaras

City 1	City 2	SLD
I	F	154
N	F	103
V	F	142
U	F	205
Bucharest	F	176

City 1	City 2	Cost
I	N	87
I	V	92
V	U	142
U	Bucharest	85
Bucharest	F	211




# Avoiding loops in A\* search: Find a path from Iasi to Fagaras




# Avoiding loops in A\* search: Find a path from Iasi to Fagaras

City 1	City 2	SLD
I	F	154
N	F	103
V	F	142
U	F	205
Bucharest	F	176

City 1	City 2	Cost
I	N	87
I	V	92
V	U	142
U	Bucharest	85
Bucharest	F	211




# Avoiding loops in A\* search: Find a path from Iasi to Fagaras




## Avoiding loops in A\* search: Find a path from Iasi to Fagaras

City 1	City 2	SLD
I	F	154
N	F	103
V	F	142
U	F	205
Bucharest	F	176


City 1	City 2	Cost
I	N	87
I	V	92
V	U	142
U	Bucharest	85
Bucharest	F	211



# Avoiding loops in A\* search: Find a path from Iasi to Fagaras



# Avoiding loops in A\* search: Find a path from Iasi to Fagaras







# Avoiding loops in A\* search: Find a path from Iasi to Fagaras

City 1	City 2	SLD
I	F	154
N	F	103
V	F	142
U	F	205
Bucharest	F	176

City 1	City 2	Cost
I	N	87
I	V	92
V	U	142
U	Bucharest	85
Bucharest	F	211



# Avoiding loops in A\* search: Find a path from Iasi to Fagaras



# Properties of A\*

## Completeness

- **Yes**, unless there are infinitely many nodes with  $f(n) < f(\text{Goal})$

## Optimality

- depends **on the heuristic**  $h(n)$

## Time Complexity

- **the number of nodes grows exponentially** unless the error between the true cost  $h^*(n)$  and the heuristic  $h(n)$  grows logarithmically.

$$|h(n) - h^*(n)| \leq O(\log h^*(n))$$

## Space Complexity

- **has to keep all nodes in memory, typically the main problem with A\***

# Addressing the space problem

- High memory consumption is the main problem with  $A^*$  → **memory-bounded algorithms**
- **Iterative-deepening  $A^*$** 
  - like iterative deepening search
  - iteratively increase limit of the function ( $f = g + h$ )
- **Recursive BFS**
  - recursive algorithm that attempts to mimic standard BFS with linear space
  - keeps track of the cost of the best alternative path available from any ancestor of the current node
- **(Simple) memory-bounded  $A^*$** 
  - drop the worst leaf node when memory is full

---

**Today**

---

# Heuristics

# Admissible heuristics

A heuristic  $h(n)$  is **admissible**

- if it **never overestimates** the **true cost**  $h^*(n)$

$$\forall n: h(n) \leq h^*(n)$$


## Consistent heuristics

A heuristic  $h(n)$  is **consistent**

- if **the estimated cost from  $n$  to the goal** is always less than the sum of **the path cost to any successor  $n'$  of  $n$**  and **the estimated cost from  $n'$  to the goal**.

$$\forall n: h(n) \leq c(n, a, n') + h(n')$$

→ Triangle inequality



# Properties of heuristics for searching

- Every **consistent** heuristic is **admissible**.
- The reverse case is not always true (it rarely occurs).



# Properties of A\*

## Completeness

- **Yes**, unless there are infinitely many nodes with  $f(n) < f(\text{Goal})$

## Optimality

- if  $h(n)$  is **consistent**

## Time Complexity

- the number of nodes grows exponentially unless the error between the true cost  $h^*(n)$  and the heuristic  $h(n)$  grows only logarithmically.

$$|h(n) - h^*(n)| \leq O(\log h^*(n))$$

## Space Complexity


- has to keep all nodes in memory, typically the main problem with A\*

# How do we define a good heuristic?

# Try to relax the problem

- A problem with a **fewer restrictions** on the **environment** is called **a relaxed problem**.
- The **cost of an optimal solution to a relaxed problem** is an **admissible heuristic** for the **original problem**.

# Admissible heuristic for the 8-puzzle?



# Admissible heuristic for the 8-puzzle

- **Relax** the rules of the **8-puzzle** so that **a tile can move anywhere**  
→  $h_{\text{MIS}}(n)$  = **number of misplaced tiles**
- **Relax** the rules of the **8-puzzle** so that **a tile can move to any adjacent square (not only empty ones)**,  
→  $h_{\text{MAN}}(n)$  = **Manhattan distance of each tile to its final position (summed up)**

# Admissible heuristics for 8-puzzle

$h_{\text{MIS}}(n)$  = number of **misplaced tiles**

- **admissible** because **each misplaced tile must be moved at least once**

$h_{\text{MAN}}(n)$  = **Manhattan distance to final position (summed up over all tiles)**

- **admissible** because this is **the minimum distance of each tile to its target square**

7	2	4
5		6
8	3	1
Start State		
	1	2
3	4	5
6	7	8
Goal State		

$$h_{\text{MIS}}(\text{start}) = 8$$

$$h_{\text{MAN}}(\text{start}) = 18$$

$$h^*(\text{start}) = 26$$

# Which admissible $h$ to choose?

If two heuristics are **admissible**, choose the one that **dominates the other one**.

Consider two **admissible** heuristics  $h_1$  and  $h_2$  :

$h_2$  **dominates**  $h_1$  if  $h_2$  always estimates higher or equal costs than  $h_1$

# What if more than one admissible h exist

7	2	4
5		6
8	3	1

Start State

	1	2
3	4	5
6	7	8

Goal State

$$h_{\text{MIS}}(\text{start}) = 8$$

$$h_{\text{MAN}}(\text{start}) = 18$$

$$h^*(\text{start}) = 26$$

- $h_{\text{MAN}}$  dominates  $h_{\text{MIS}}$  because both are admissible and each misplaced tile needs to be replaced at least once.
- The dominating heuristic is better because it will be closer to the true cost  $h^*$ .




# Pattern databases

Admissible heuristics can also be derived from the solution cost of a sub-problem of a given problem

- this cost is a lower bound on the cost of the real problem


A pattern database (PDB) is a heuristic function implemented as a lookup table that stores the lengths of optimal solutions for subproblem instances.



# Pattern databases

Constructed once for all by searching backwards from the goal and recording every possible pattern

Example: store exact solution costs for solving 4 tiles of the 8-puzzle




# Pattern databases for chess

- Storing patterns from the start is infeasible.

Depth	Nodes
0	1
1	20
2	400
3	8,902
4	197,281
5	4,865,609
6	119,060,324
7	3,195,901,860
8	84,998,978,956
9	2,439,530,234,167
10	69,352,859,712,417
11	2,097,651,003,696,806
12	62,854,969,236,701,747
13	1,981,066,775,000,396,239
14	61,885,021,521,585,529,237
15	2,015,099,950,053,364,471,960

- Storing patterns by looking at the end?
- 2012: database complete for all moves for seven remaining chess pieces
- 140 terabyte



Move	Value
Kc6	Win in 5
Qa6+	Win in 5
Qc6+	Win in 8
Qg6	Win in 8
Qa5+	Win in 8
Qc5	Win in 9
Ke5	Win in 10
Kd4	Win in 10
Qg1	Win in 10
Ke6	Win in 11
Qf2	Win in 13
Ke4	Win in 14
Qd4	Win in 16
Kc5	Draw
Qxb5	Draw
Qe6	Lose in 28
Qf6	Lose in 15
Qb6	Lose in 15

☒ White to move  
☐ Black to move

# Summary

- **Informed search algorithms using heuristics**
  - Greedy **best**-first search ✓
  - A\* search ✓
- **Heuristics**
  - Admissible ✓
  - Consistent ✓
  - How do we define and choose a good heuristic? ✓

# Readings

## Mandatory

- Russell & Norvig:  
*Informed (Heuristic) Search Strategies*  
3.5.1 & 3.5.2, p. 92-102

## Optional

- Rest of 3.5

