Computer Science

Full Study Notes

Table of Contents

1. Computer Architecture 4
   1.1. Introduction 4
   1.2. CPU 4
      1.2.1. ALU 4
      1.2.2. CU 4
      1.2.3. CPU Characteristics 4
   1.3. Memory 4
      1.3.1. RAM 5
      1.3.2. HDD 5
   1.4. Converting data sizes (Decimal System - SI) 5
   1.5. Number Systems 6
      1.5.1. Base-10 6
      1.5.2. Base-2 6
      1.5.3. Relationship between base-2 and base-10 6
         1.5.3.1. Converting from Base-10 to Base-2 6
         1.5.3.2. Converting from Base-2 to Base-10 6
   1.6. Logic gates 7
      1.6.1. Introduction 7
      1.6.2. NOT 7
      1.6.3. AND 7
      1.6.4. NAND 7
         1.6.4.1. De Morgan's Law 8
      1.6.5. OR 8
      1.6.6. NOR 8
         1.6.6.1. De Morgan's Law 8
      1.6.7. XOR 8
2. Python 10
   2.1. Introduction 10
   2.2. Data Types 11
   2.3. Variables 11
   2.4. Operators 11
      2.4.1. Arithmetic operators 11
      2.4.2. Comparison operators 12
      2.4.3. Logical Operators On A Truth Table 12
      2.4.4. Membership Operators 12
      2.4.5. Bitshift operators 12
      2.4.6. Operation + Assignment By Examples 13
   2.5. Loops 13
      2.5.1. A visual 13
      2.5.2. Example: Using lists to match two n-length lists 14
      2.5.3. Using lists without the range function 14
   2.6. Functions 14
      2.6.1. A visual 15
      2.6.2. Parameters & Arguments 15
      2.6.3. Returning Values 15

2.6.4. Deterministic & Pure function 15
2.6.5. Using functions to calculate the hypotenuse of a right triangle ABC 15
2.6.6. Functions to be aware of 16
2.6.6.1. print 16
2.6.6.2. int 16
2.6.6.3. range 16
2.7. Control Flow 16
2.7.1. A visual 16
2.7.2. If statements 16
2.7.3. Else statements 17
2.7.4. Using control flow to categorize age 17
2.8. Try it yourself 17
3. Complexity Theory 18
3.1. What is an algorithm? 18
3.1.1. Example: Sequential Search 18
3.1.2. Example: Binary Search 19
3.2. Time vs Space complexity? 20
3.2.1. Big-O complexity graph 20
3.2.2. Definition 20
3.2.2.1. Explanation 20
3.2.3. Ways of analyzing an algorithm and determine $f(n)$ 22
3.2.3.1. Pre-requisites 22
3.2.3.2. Analysis 23
3.2.4. Ways of proving $f(n) = O(g(n))$ 25
3.2.5. Why is knowing the time complexity of an algorithm important? 26
4. Miscellaneous 27
4.1. Cache 27
4.1.1. The client-server model 27
4.1.1.1. The client 27
4.1.1.2. The server 27
4.1.1.3. Illustration 28
4.1.1.4. The caching of client-server models 28
4.1.2. In the context of a CPU 29
4.1.2.1. CPU cache levels 30
4.1.3. Summary 30
5. Exam studying methodology 30

1. Computer Architecture

1.1. Introduction

Computer architecture is the structure of a computer system made from component parts.

1.2. CPU

- The CPU (**C**entral-**P**rocessing-**U**nit).
- It consists of many smaller units that handle different things, but in the explanation we will take, it will only contain an ALU 1.2.1 and a CU 1.2.2, both of their explanations will be simplified.
- It's essentially the brain of the computer, handling all the computation (we can call them tasks) that happen on the computer.



Figure 1: A physical CPU

,

1.2.1. ALU

- The ALU (**A**rithmetic-**L**ogic-**U**nit) is a component/unit of the CPU 1.2
- It handles all the arithmetic (addition, subtraction, division, multiplication, etc...)
- All the operations that happen inside the ALU are in base-2

1.2.2. CU

- The CU (**C**ontrol-**U**nit) is a component/unit of the CPU 1.2
- It will manage and execute instructions.
- For now, we will think of instructions as operations needed to perform certain actions on the computer (adding two numbers, opening an app, etc...)

1.2.3. CPU Characteristics

- A CPU has a clock speed: the speed at which cycles will execute, and it is a frequency.
- $1\text{GHz} = 1 * 10^9$ Hz

1.3. Memory

> Memory in the context of a computer system is the place where "data" will be stored. Data can be for example: images, text, files, Variables 2.3, etc...

We will discuss:

- Two types of memory: Primary Memory and Secondary Memory
- Data units: bit, byte, KB, MB, GB

Primary Memory	Secondary Memory
Fast access speed	Slower access speed
Volatile (data lost on restart)	Non-volatile (data persists)
Example: **RAM**	Example: **HDD, SSD**
Used for active tasks	Used for long-term storage

1.3.1. RAM

- RAM (**R**andom-**A**ccess-**M**emory) is a type of memory.
- RAM is primary memory.




Figure 2: A physical stick of RAM

,

1.3.2. HDD

- HDD (Hard-Disk-Drive) is a type of memory.
- HDD is secondary-memory.



Figure 3: An HDD

1.4. Converting data sizes (Decimal System - SI)

Unit	Conversion
Bit	Smallest data unit
Byte	1 byte = 8 bits
Kilobyte (KB)	1 KB = 1,000 bytes
Megabyte (MB)	1 MB = 1,000 KB
Gigabyte (GB)	1 GB = 1,000 MB

1.5. Number Systems

1.5.1. Base-10

- Base-10 is the number system we humans use.
- It's made up of 10 digits, digits from (0 to 9): 0, 1, 2, 3, 4, 5, 6, 7, 8, 9.
- Any other number is made up from these `10` digits.

1.5.2. Base-2

- Base-2 is the number system computers use.
- It's made up of two digits: `0` and `1`.
- Any other number is made up from these `2` digits.

1.5.3. Relationship between base-2 and base-10

Numbers can be converted to-and-back from base-2 to base-10.

1.5.3.1. Converting from Base-10 to Base-2

Example: Convert $(75)_{10}$ to binary

Step 1: Make a table.

Step 2: Divide 75 by 2 repeatedly.

Step 3: If the number is a decimal, take everything before the decimal and assign it the bit `1`; if the number is a whole number, write the number as is and assign it the bit `0`.

Step 4: Construct the number by reading the bits from bottom to top.

Step 5: If the number is now less than 1, record it, and stop.

number	index	bit
37	0	1
18	1	1
9	2	0
4	3	1
2	4	0
1	5	0
$\frac{1}{2}$	6	1

Table 1: Table for converting 75 to base-2.

1.5.3.2. Converting from Base-2 to Base-10

We will take the same example as above and in Table 1, and we will use the indexes to remake the base-10 number.

we had $(75)_{10} = (1001011)_2$

We need to only consider the "1"s and their indexes as shown in Figure 4

$(1001011)_2 = (2^0 + 2^1 + 2^3 + 2^6)_{10} = (75)_{10}$




Figure 4: The 1's and their indexes.

1.6. Logic gates

1.6.1. Introduction

A logic gate is a device that performs a boolean function (logical operation). It is the smallest unit of computation in a CPU 1.2.

In this section, we will think of each logic gate as a device that has one or two inputs (NOT has one, all the others have two) and one output.

The primitive logic gates are: NOT, AND, OR.

From these we can build the derived gates: NAND, NOR, XOR. NAND and NOR are also called *universal* gates, because any other gate can be built using only NAND gates (or only NOR gates).

1.6.2. NOT

A NOT gate can be represented by the following table:

I_1	O_1
0	1
1	0




Figure 5: NOT

- The **NOT** gate outputs the complement of A, meaning 0 if A is 1, and 1 if A is 0.
- We will denote the operation: $\neg A = O_1$
- We can also denote the operation with a bar: $\overline{A} = O_1$
- **Double Negation:** $\neg(\neg A) \equiv A$

1.6.3. AND

An AND gate can be represented by the following table:

I_1	I_2	O_1
0	0	0
0	1	0
1	0	0
1	1	1



Figure 6: AND

- The **AND** gate outputs 0 for all pairs of (I_1, I_2), except when both **A** AND **B** are 1.
- We will denote the operation: $A \wedge B = O_1$
- **Contradiction:** $I_1 \wedge \neg I_1 = 0$

1.6.4. NAND

A NAND gate can be represented by the following table:

I_1	I_2	O_1
0	0	1
0	1	1
1	0	1
1	1	0



Figure 7: NAND

- The **NAND** gate outputs the opposite of what an AND gate would produce for a pair (I_1, I_2).

- We will denote the operation: $\neg(A \wedge B) = O_1$

1.6.4.1. De Morgan's Law

$\neg(A \wedge B) \equiv \neg A \vee \neg B$

1.6.5. OR

An OR gate can be represented by the following table:

I_1	I_2	O_1
0	0	0
0	1	1
1	0	1
1	1	1




Figure 8: OR

- The **OR** gate outputs 1 if $\boldsymbol{I_1}$ OR $\boldsymbol{I_2}$ (or both) is 1, and 0 only when both are 0.
- We will denote the operation: $A \vee B = O_1$

Tautology: $I_1 \vee \neg I_1 \equiv 1$

1.6.6. NOR

A NOR gate can be represented by the following table:

I_1	I_2	O_1
0	0	1
0	1	0
1	0	0
1	1	0



Figure 9: NOR

- The **NOR** gate outputs the opposite of what an OR gate would produce for a pair (I_1, I_2), meaning it outputs 1 only when both **A** and **B** are 0.
- We will denote the operation: $\neg(A \vee B) = O_1$

1.6.6.1. De Morgan's Law

$\neg(A \vee B) \equiv \neg A \wedge \neg B$

1.6.7. XOR

An XOR (exclusive OR) gate can be represented by the following table:

I_1	I_2	O_1
0	0	0
0	1	1
1	0	1
1	1	0



Figure 10: XOR

- The **XOR** gate outputs 1 when **A** and **B** are different, and 0 when they are the same. Unlike OR, it outputs 0 when both inputs are 1.
- We will denote the operation: $A \oplus B = O_1$




Figure 11: Image of a 4-bit Computer built with logic-gates

2. Python

2.1. Introduction

> **Definition: Python is a “high-level”, “interpreted”, “general-purpose” scripting language.**

Characteristic	Explanation
High-Level	Built on many lower-level abstractions. Python provides an easy-to-use language by building upon harder programming concepts and technologies.
Interpreted	An external program (the interpreter) reads and executes instructions line by line. Unlike compiled languages, Python code is interpreted at runtime.
General-Purpose	Can be used for most use-cases. Python is versatile: web development, data science, automation, etc.
Sequential	Executes instructions from top to bottom by default.
Imperative	Uses imperative programming style to maintain state.




Figure 12: Compiled languages process.




Figure 13: Abstractions.

2.2. Data Types

Type	Description & Examples
`int`	Integer - a whole number. Examples: `10`, `25`, `300`, `-5`
`float`	Decimal number. Examples: `52.6`, `19.3`, `1.0`, `5.0`
`bool`	Boolean - either `True` or `False`
`str`	String - sequence of characters. Examples: `"Hello"`, `"Text"`, `""`
`list`	Sequence of elements. Example: `[10, 5.2, 9.8]` Lists are heterogeneous and 0-indexed
`dict`	Dictionary - key-value store. Example: `{"name": "John", "age": 30}` Access: `person["name"]` ⟶ `"John"`
`None`	Represents a null value

2.3. Variables

Variables in Python are **mutable** (can change) and **dynamically typed** (no specific type restriction).

examples:

```
name = "Johnny"
johnny_age = 20
grades = [10, 5.2, 9.8, 12.5, 13.2]
person = {"name": "Johnny", "age": johnny_age}
```

2.4. Operators

2.4.1. Arithmetic operators

Operator	Name	Example
+	Addition	`10 + 5 = 15`
-	Subtraction	`10 - 5 = 5`
*****	Multiplication	`10 * 5 = 50`
/	Division	`10 / 5 = 2.0`
******	Exponentiation	`3 ** 4 = 3 * 3 * 3 * 3 = 81`

Important: Division always returns a float: `int / int → float`

2.4.2. Comparison operators

Operator	Name	Result
==	Equality	`10 == 10` ⟶ `True`
!=	Inequality	`10 != 5` ⟶ `True`
>	Greater than	`10 > 5` ⟶ `True`
<	Less than	`10 < 5` ⟶ `False`
>=	Greater or equal	`10 >= 10` ⟶ `True`
<=	Less or equal	`5 <= 10` ⟶ `True`

2.4.3. Logical Operators On A Truth Table

p	q	Conjunction p **and** q $p \wedge q$	Disjunction p **or** q $p \vee q$	Negation **not** p $\neg p$	Negation **not** q $\neg q$
True	True	True	True	False	False
True	False	False	True	False	True
False	True	False	True	True	False
False	False	False	False	True	True

2.4.4. Membership Operators

Operator	Explanation	Example
`in`	Used to check if a certain key is inside a dictionary, returns a bool	`"name" in {"name": "John"}` ⟶ `True` because key "name" exists in the dict `"age" in {"name": "John"}` ⟶ `False` because key "age" does not exist in the dict
`not in`	Used to check if a certain key is not inside a dictionary, returns a bool	`"name" not in {"name": "John"}` ⟶ `False` because key "name" exists in the dict `"age" not in {"name": "John"}` ⟶ `True` because key "age" does not exist in the dict

2.4.5. Bitshift operators

- 9 .) Left-bitshift (<<): `x << n`, where `x` and `n` are `ints`, will shift the bits of `x` by `n` zeroes and return the base-10 `int`.

Example:

- `5 << 2`:
- We convert 5 to base-2: $(5)_{10} = (101)_2$.
- And left shift by 2: `(10100)` (We added two zeroes.)
- Now if we convert back to base-10, the number becomes: $2^2 + 2^4 = 20$.

- 10 .) Right-bitshift (>>): The opposite procedure of left-bitshift.

Example:
- `5 >> 2`
- If we convert 5 to base-2: $(5)_{10} = (101)_2$.
- And right shift by 2: `(001)`, (The `01` that was there moved to somewhere that doesn't exist.)
- Now we convert back to base-10, the number becomes: $2^0 = 1$.




Figure 14: Right bitshift

2.4.6. Operation + Assignment By Examples

All the arithmetic, and bitshift operators have an assignment equivalent used to modify variables.

```
# We will declare these variables for example purposes
first_number = 10
second_number = 5
first_string = "John"
second_string = "Johnny"

first_string += " Jason" # first_string will be "John Jason" after that, because "John"
+ " Jason" = "John Jason".
second_number -= 6 # second_number will be -1 after that, because 5 - 6 = -1.
second_number *= -2 # second_number will be 2 after that, because (-1)(-2) = 2.
first_number /= 5 # first_number will be 2.0 after that, because 10 / 5 = 2.0.
first_number = 5 # first_number will be 5 after that, normal assignment.
first_number <<= 2 # first_number will be 20 after that, because 5 << 2 = 20
first_number >>= 3 # first_number will be 2 after that, because 20 >> 3 is 2.
```

2.5. Loops

Loops are used for repeated actions.

2.5.1. A visual

```
accumulator = 0 # A variable that accumulates

for current_number in range(0, 10): # A loop over the range 0 to 10 (10 exclusive), and
current_number is the current value from the range
  accumulator += current_number # Mutating accumulator and adding current_number to it
```

After this, `accumulator` will be $0 + 1 + 2 + 3 + 4 + 5 + 6 + 7 + 8 + 9 = 45$.

2.5.2. Example: Using lists to match two n-length lists

```
names  = ["John", "Johnnathan", "Jay", "Jane", "Jake"] # List of n names
grades = [9, 7.5, 6, 3.5, 6] # List of n grades
n      = 5

for i in range(0, n): # Looping n times
  name = names[i] # Accessing the i-th name from the names list
  grade = str(grades[i]) # Accessing the i-th grade from the grades list, and converting
it to a string
  print(name + " has a grade of " + grade) # Concatenating (Adding) the strings together
to make a sentence, here we see why we turned grade into a "str", because str + int and
str + float is not possible
```

The output is as shown below:

```
John has a grade of 9
Johnnathan has a grade of 7.5
Jay has a grade of 6
Jane has a grade of 3.5
Jake has a grade of 6
```

2.5.3. Using lists without the range function

Until now, we are still using the `range` function, but are **iterable** by default. An iterator allows any object to be **iterated over** by a loop. Let's compare:

```
nums = [1,2,3,4,5]
n = 5

for i in range(0, n):
  print(nums[i])
```

Code 1: Looping over lists with range

```
nums = [1,2,3,4,5]

for num in nums:
  print(num)
```

Code 2: Looping over lists with the list's iterative property

2.6. Functions

Functions should be thought of as machines that take an input and give us an output.



Figure 15: Function diagram

2.6.1. A visual

```
def add(x, y):
  return x + y
```

Code 3: A function that adds two numbers, x and y.

Now, to use this function we just **defined**, we will need to **call** it, as such:

```
result = add(10, 5)
print(result)
```

Code 4: Calling the function add

The output of result will now be `15`, since the function handled the addition of `x` and `y`, and `x` was `10`, and `y` was `5`.

2.6.2. Parameters & Arguments

- The parameters of a function is what we label the inputs. Consider Code 3, the parameters of that function are `x` and `y`.
- The arguments of a function is what is supplied for the labels of the inputs. Consider Code 4, the arguments are `10` and `5`.

2.6.3. Returning Values

The **return value** of a function is what the function outputs. Taking as example Code 3, the return value can be described as `x + y`, or also the sum of its inputs.

The return value is also what comes after the **return** keyword.

2.6.4. Deterministic & Pure function

Function Characteristic	Definition
Deterministic Function	A deterministic function is a function that returns the same outputs for the same inputs, and has no randomness in the determination of future states.
Pure Function	A pure function is a function that obeys two properties: • It is deterministic • The function has no side effect, meaning no mutation of non-local variables.

2.6.5. Using functions to calculate the hypotenuse of a right triangle ABC

```
def calculate_hypotenuse(AB, AC):
  BC = (AB**2 + AC ** 2) ** 0.5
  return BC
```

We can describe this function as follows:

- This function is called `calculate_hypotenuse`.
- It takes two parameters: AB and AC, which are supposed to be either ints or floats.
- It returns the hypotenuse of the triangle ABC.

2.6.6. Functions to be aware of

2.6.6.1. print

Output to the standard output (simplified).

```
>>> print("Hello World")
--> Hello World
```

2.6.6.2. int

> **Returns an integer constructed from a number or a string.**

```
int(123.45) # 123
int("123") # 123
int("01110011", base=2) # 115
```

2.6.6.3. range

Range is technically a *class* not a function, but we will refer to it as a function. We will consider valid arguments to be integers.

Refer to Loops 2.5 to know how to use it.

2.7. Control Flow

Control flow describes how execution progresses from one command to the next.

2.7.1. A visual

```
your_age = 15
adult_age = 18

if your_age >= adult_age:
  print("You are an adult")
else:
  print("You are a minor")
```

Code 5: Control flow, if and else.

In the code above, we have two variables, `your_age` and `adult_age`.

We first compare `your_age` and `adult_age` using `>=` (Bigger than or equal to), which returns a bool type, this bool type is then considered by the **if** statement before it, and accordingly, the **branch** below if (the truthy-case branch) will be executed, otherwise, we are handling it with an **else** statement.

2.7.2. If statements

if executes it's branch if the statement given to it is a truthy value, a **truthy** value is a value that is not **falsy**.

Some **falsy** values in Python are: `None`, `0` and `False`

truthy values evaluate to **True** booleans, and **falsy** values evaluate to **False** booleans.

The structure of an **if statement** looks as such:

```
if boolean:
  branch instructions
```

2.7.3. Else statements

else statements are chained with **if** statements, and are executed in case the previous **if statement** turns out to be falsy, the structure is as such:

```
if boolean:
  branch instructions
else:
  branch instructions
```

One thing possible with **else** statements is chaining them with if statements, as such:

```
if boolean:
  branch instructions
elif boolean:
  branch instructions
elif boolean:
  branch instructions
else:
  branch instructions
```

Here, we have an if statement, chained with else statements, and a default case.

2.7.4. Using control flow to categorize age

```
age = 30

if age >= 60:
    print("You're a senior!")
elif age >= 40:
    print("You're an adult!")
elif age >= 20:
    print("You're a young adult!")
elif age >= 13:
    print("You're a teenager!")
elif age >= 3:
    print("You're a child!")
else:
    print("You're an infant!")
```

2.8. Try it yourself

You can go to the website: https://www.programiz.com/python-programming/online-compiler/, and follow everything each step of the way.

3. Complexity Theory

Complexity theory studies the relationship between an algorithm and the resource it takes.

3.1. What is an algorithm?

A computer algorithm is a sequence of steps a computer will take to achieve a particular outcome.

3.1.1. Example: Sequential Search

Given a sorted array A of length n, $(A_0 \leq A_1 \leq A_2 \leq ... \leq A_{n-1})$, and a number K, $K \in A$ sequential search is an algorithm that will go through each index in the array one by one, starting with 0, and stops when it finds the element K in the array and return it's position.

For example, if I have the array $A = [1, 5, 9, 12, 60, 110, 120, 121, 500, 505]$ and the number $K = 60$, sequential search will start checking in order:

- Is $A_0 = 60$? No, keep going.
- Is $A_1 = 60$? No, keep going.

...

- Is $A_4 = 60$? Yes, return 4, the desired position.
- This algorithm has a time complexity of $O(n)$, where $n = \text{length of the array}$, we will explain why later, but intuitively, we can think it is $O(n)$ because if the number K was at the end of the array(worst case scenario), it will take n steps to find K




Figure 16: Sequential Search Diagram




Figure 17: Sequential Search Array

3.1.2. Example: Binary Search

For binary search, we will consider the **sorted** 10-length array $A = [-5, -2, 0, 1, 2, 4, 5, 6, 7, 10]$ and $K = 7$, and we will start with low = 0, and high = 9, at each point, we will then repeatedly take midpoint $=$ low $+ \left\lfloor \frac{\text{high} - \text{low}}{2} \right\rfloor$, and call that point M, if $A_m > K$, then K is positioned before position m (the array is sorted), so we will take the left half, otherwise if $A_m < K$, then K is positioned after the position m, so we will take the right half, and repeat.

- This algorithm has $O(\log_2 n)$, but is written as simply $O(\log n)$ because 2 is a constant term we don't usually consider, this is because at each step in the algorithm, we cut the amount of work we have to do by half.




Figure 18: Binary Search Diagram




Figure 19: Binary Search Array

3.2. Time vs Space complexity?

- Time complexity describes how the execution time(number of steps) of an algorithm grows as the size of it's input grows.
- Space complexity describes how much more space an algorithm will take as the size of it's input grows.

In this course we will only be interested in time complexity.

3.2.1. Big-O complexity graph




Figure 20: Big-O Complexity Chart

These are the standard time complexities we usually encounter, but we will only talk about $O(1)$, $O(n)$ and $O(n^2)$, it is important to note here that $n \geq 0$, and no negative input size exists.

3.2.2. Definition

$$f(n) = O(g(n)) \Leftrightarrow \exists c > 0, \exists n_0 > 0, \text{such that}$$
$$f(n) \leq c * g(n) \quad \forall n \geq n_0$$

$f(n)$ is $O(g(n))$ if there exists a $c > 0$ and an $n_0 > 0$, such that $f(n) \leq c * g(n)$ for all values of $n \geq n_0$

3.2.2.1. Explanation

Big-O describes the "upper-bound" of time an algorithm can take. Therefore, Big-O has $f(n)$ always at most $c * g(n)$ for all $n \geq n_0$.

There exists other complexity-notations:

Notation	Symbol	Meaning
Big-O	O	Upper Bound
Little-o	o	Strict upper bound
Big-Omega	Ω	Lower bound
Little-omega	ω	Strict lower bound
Big-Theta	Θ	Upper + Lower bound

The following would be true for Big-O, but not for little-o:

$$x^2 \in O(x^2)$$

$$x^2 \in O(x^2 + x)$$

$$x^2 \in O(200x^2)$$

We will only be responsible for **Big-O** in this course.

A tip: You can look at the highest degree of the function, and already be aware of what time complexity it is .

3.2.3. Ways of analyzing an algorithm and determine $f(n)$

3.2.3.1. Pre-requisites

- $\lfloor 5,8 \rfloor$ = lowest integer below 5,8 = 5
- $\log_b c = a$:

$$b^a = c$$

example: $\log_2 8 = 3$

$$2^3 = 8$$

The log of base b and input c yields what exponent we need for b to equal c

- $$\log_b(b^x) = x$$
- $$\log\left(\frac{a}{b}\right) = \log a - \log b$$
- $$\log_{b_1} c = \frac{\log_{b_2} c}{\log_{b_2} b_1} = \left(\frac{1}{\log_{b_2} b_1}\right) \log_{b_2} c$$
- $$\sum_{i=1}^{k} c = c * k$$
- $$\sum_{i=1}^{k} i = 1 + 2 + 3 + ... + k = \frac{k(k+1)}{2}$$
- $$\sum_{i=1}^{n} (n - i) = (n-1) + (n-2) + (n-3) + ... + 1 + 0 = \frac{k(k-1)}{2}$$

Proof:

$$S = 1 + 2 + ... + (n-2) + (n-1)$$

$$S = (n-1) + (n-2) + ... + 2 + 1$$

Add S and the flipped S together, there is going to be $n - 1$ terms in total:

$$2S = \underbrace{n + n + n + ... + n}_{n-1 \text{ terms from 1 to n}}$$

Factor out $n - 1$

$$2S = n(n-1)$$

$$S = \frac{n(n-1)}{2}$$

- $$\sum_{i=1}^{k} \frac{n}{2^i} = \frac{n}{1} + \frac{n}{2} + \frac{n}{4} + \frac{n}{8} + ... + \frac{n}{2^k}$$

3.2.3.2. Analysis

First concept: In time complexity Big-O notation, we ignore constant factors and lower order terms:

$O(2n) = O(n)$, 2 is a constant factors
$O(3n^2) = O(n^2)$ 3 is a constant factors
$O(3n^2 + n) = O(n^2)$ We ignore constant factors and lower order terms
$O(\log_2 n) = O(\log n)$ Any logarithm base change differs by a constant factor(see pre-requisites)
$O(5) = O(1)$

Example algorithm 1: Algorithm 1 takes an input N, and will give me back that input N as it is, no matter the N, the algorithm will take number of steps $= 1$

It is therefore $O(1)$

Example algorithm 2: Algorithm 2 takes an array L of length N and will sum the elements of the array together, so for example, for $L = [1, 5, 2, 4, 6, 1]$, output $= 1 + 5 + 2 + 4 + 6 + 1 = 19$, it took 6 steps (length of array is $N = 6$)

The number of steps this algorithm will take is: steps $= N$, exactly N steps, each step consists of adding the number at L_k to a accumulation variable S, so the amount of work at each step is 1, $O(1)$, $S \mathrel{+}= L_k$

The amounts of steps are:

$$\sum_{i=1}^{N} 1 = N * 1 = N$$

It is therefore $O(N)$, N steps

Note: The 1 here represents the amount of work at each iteration (adding to the accumulation), which is just one step.

Example algorithm 3: Algorithm 3 takes a list L of length N, and tries to find the position of two elements (i, j), $i < j$ such that: $L[i] + L[j] = K$, where K is a target sum given.

It will do that in the following way:

- Go over each element in the list, at position i
- At position i, check all the elements infront of i, that have index j, and check if $L[i] + L[j] = K$
- If not, go to the next i

For example, if $K = 10$ and $L = [2, 5, 0, 3, 5]$

- **Starting at $i = 0$:** , We will check all elements that have position $j \geq i + 1 = 1$, but no elements would be found, because there exists no elements in this list such that $L[0] = 2$ adds with another number $L[j]$ such that $2 + L[j] = 10$
- **Trying $i = 1$:** , we would have $L[1] = 5$, then check all elements that have position $j \geq i + 1 = 2$, you would find that $L[1] + L[4] = 5 + 5 = 10 = K$, so we found it, if we didnt end up finding it, then we would try $i = 2$

The steps taken by the algorithm at the worst case are:

$$\sum_{i=0}^{N-1}(N - 1 - i) = (N - 1) + (N - 2) + ... + 1 + 0 = \frac{N(N-1)}{2} = \frac{N^2 - N}{2}$$

It is therefore $O\left(\frac{N^2-N}{2}\right)$, ignoring constant factors: $O(N^2)$

Note: It is the sum of $(N - 1 - n)$ steps because at each step i, we will end up doing $N - 1 - i$ steps, which is the length of the elements after i, when we took $i = 0$ for example, we ended up checking all $j \geq 1$, which was $N - 1$ elements, or with $i = 1$, we checked all $j \geq 2$, which was $N - 2$ elements.

Example algorithm 4: This algorithm will be Binary Search 18, we stated that at each iteration, the number of elements in binary search is cut by half, meaning that at step k, elements $= \frac{N}{2^k}$, where N is the length of the array.

Visualization: If we start with an array of length 12, after two iterations, cutting the array by half twice, there will be $\frac{12}{2^2} = 3$ elements

Since k is the number of steps, and we want to know the number of steps, and we also know that the algorithm stops when there is **1** last element:

$$\text{elements left} = 1$$

$$\frac{N}{2^k} = 1$$

$$N = 2^k$$

$$\log_2(N) = \log_2\left(2^k\right)$$

$$\log_2(N) = k$$

$$\text{steps} = k = \log_2(N)$$

It is therefore $O(\log_2 N)$, ignoring constant factor and lowest-order term:

$O(\log N)$

Extra note: log_2 N is only an integer when N is a power of 2. So the exact worst case scenario steps comes down to: steps $= \lfloor \log_2 N \rfloor + 1$

3.2.4. Ways of proving $f(n) = O(g(n))$

Substitution	Rebuilding
• If we want to prove $f(n) = n^2 + 5n + 3 = O(n^2)$ • We identify $g(n) = n^2$ We will need, by definition: $n^2 + 5n + 3 \leq c * g(n)$ $n^2 + 5n + 3 \leq c * n^2$ • For all $n \geq 1$, we have: $n \leq n^2$ $5n \leq 5n^2$ $3 \leq 3n^2$ • And since these are all bigger than the terms in $f(n)$, we can say: $n^2 + 5n + 3 \leq n^2 + 5n^2 + 3n^2$ $n^2 + 5n + 3 \leq 9n^2$ • So using $c = 9$ and $n_0 = 1$, we got a solution.	• If we want to prove $f(n) = n^2 + 5n + 3 = O(n^2)$ • We will take: $n_0 = 5$ $n \geq n_0$ $n \geq 5$ $5 \leq n$ • Multiplying by n, we get the middle term: $5n \leq n^2$ • For the constant term, since $n \geq 5$ we have $3 \leq n$, and $n \leq n^2$, so: $3 \leq n^2$ • And we replace: $n^2 + 5n + 3 \leq n^2 + n^2 + n^2$ $n^2 + 5n + 3 \leq 3n^2$ So using $c = 3$ and $n_0 = 5$, we got a solution.

3.2.5. Why is knowing the time complexity of an algorithm important?

Let's imagine a sorted array A like we did before, and let's say that array has a length of $N = 10^9$ (1 billion elements).

Using **sequential search** $O(n)$, would mean an upper-bound of operations $= o = 10^9$ operations (billion operations), to estimate how long that takes, we count CPU cycles per micro-operation:

Operation	Theoretical CPU Cycles
Load $A[i]$ from memory	1
Compare $A[i] == K$	1
Branch on result (if true stop, if false continue)	1
Increment i	1
Check if $i < n$ and branch	1

These are $c \approx 5$ cycles, and the time for the n operations in relation with clock speed and 5-cycles:

$$T(o) = \frac{\text{cycle count} * \text{operation count}}{\text{Clock Speed Frequency}} = \frac{5o}{f}$$

Where f is the clock-speed of the CPU (the speed of operation cycling) in "Hz". and o is the operation count. If we consider a theoretical CPU of clock speed 0.295 GHz (Same speed as a PlayStation 2).

$$T(o) = T(10^9) = \frac{5(10^9)}{(0.295)(10^9)} \approx 16.94 \text{ s}$$

It would take 16.94 seconds on a 0.295GHz CPU to execute the algorithm.

On the other hand, if we considered **binary search** instead with: $N = 10^9$, we would have an upper bound of:

$$o' = \log_2 N = \log_2 10^9 \approx 30$$

And so:

$$T(o') = T(\log_2 N) = \frac{5(\log_2 10^9)}{(0.295)(10^9)} \approx 5 * 10^{-7} \text{ s} \approx 0.0000005 \text{ s}$$

Comparing the two times: $\frac{T(o)}{T(o')} = \frac{16.94}{5*10^{-7}} \approx 33880000$, that's 33 million times faster. Now, realistically, there is one more operation cycle binary search does (calculating the midpoint), but I have omitted that in this calculation. This improvement in runtime cost is an **asymptotic improvement**

If I were to consider the actual CPU cycles per operations of binary search, the result would be like:

$$T_{\text{seq}}(o) = \frac{5o}{f} \qquad T_{\text{bin}}(o) = \frac{6o}{f}$$

$T_{\text{seq}}(o) = T_{\text{seq}}(10^9) = \frac{5(10^9)}{(0.295)(10^9)} \approx 16.94 \text{ s}$ $T_{\text{bin}}(o') = T_{\text{bin}}(\log_2 N) = \frac{6(\log_2 10^9)}{(0.295)(10^9)} \approx 0.0000006 \text{ s}$

(T_{bin} has 6 cycles per operation, one extra for calculating the mid-point)

Which still, isn't a big difference from the original estimation.

4. Miscellaneous

4.1. Cache

A cache is a place of storage of temporary information that get added(**inserted**) and removed (**evicted**) based on certain criteria, the criteria to add information in the cache is called an **insertion policy**, and the policy to remove something from the cache is called an **eviction policy**, this mechanism is mainly used for performance reasons.

- **TikTok example scenario** : A TikTok video is stored in the US, and you amongst other Lebanese people watch that video really often on their phones, TikTok might consider that fact, and decide to insert the video in a cache (the placement of storage) that is closer to Lebanon, that way when people want to go watch that video, it goes and gets that video information from somewhere closer, resulting in faster speeds.

4.1.1. The client-server model

The client server model is made up of two components, the: the client, and the server, and focuses on the relationship and communication that happens between these two components.

4.1.1.1. The client

The client (also the consumer in this relationship), will consume information, this can be for example: you watching TikTok on your phone, the client is your phone.

4.1.1.2. The server

The server (the producer in this relationship), will produce and send information to the client, in the example of TikTok, the TikTok **servers** will send out the video information (title, description, comments, likes, reposts, video buffer, etc...) to your phone.

4.1.1.3. Illustration



Figure 22: The client-server model

4.1.1.4. The caching of client-server models

Usually caching in the client-server model is based on geographical location, for this, you can imagine TikTok example scenario 21, let's first look at the figure Figure 23



Figure 23: Cache added on a standard client-server-model

Here, the TikTok system notices that multiple people, close to each other geographically, are watching the same video very frequently, so by nature, to satisfy those people's need for performance, the system decided to implement a cache, so instead of every time having to get the video information from New York, America, the information is gathered from Paris, France, resulting in a shorter response time, naturally data is only needed to be cached once, and is only cached again if it is evicted, so for example, after some amount of time, the system might decide: "There's no one watching this, let me free up space and free it from the cache."

4.1.2. In the context of a CPU

We can also apply the idea of a cache inside a CPU, we have said before that a Compiler 12 turns normal code into CPU code (more commonly called machine code), this machine will have to actually **consume** this code to do something meaningful with it, so a execution process without a cache might look like Figure 24, but with a cache implemented, might be like Figure 25, internally.




Figure 24: CPU without cache




Figure 25: CPU with cache

4.1.2.1. CPU cache levels

In modern systems, usually CPUs have 3 cache levels, L1 cache, L2 cache and L3 cache, when the CPU can't find information in the L1 cache, it will go to the L2, if it can't find in the L2 it will go to L3, if it's not in the L3 it will go to primary memory, if it's not in primary memory it will go to secondary memory. When something isn't found in a particular cache, it is called a **cache miss**, otherwise it's a **cache hit**.

In summary, CPU caches improve performance, but add complexity on an existing system.

4.1.3. Summary

A cache is an Abstracted-Performance Layer 13 that is usually implemented between a producer and a consumer, a sender and a receiver, and emitter and a subscriber, that stores information temporary in a way that can be accessed faster for that consumer, such that there are performance gains.

5. Exam studying methodology

- Focus on understanding the concepts before memorizing them, there's not even the need to memorize them.
- 20% of the effort yields 80% of the outcome, don't try and nail all the details, just focus on the most important things.
- Focus on the English parts of things and try to explain things to yourself and other people to see if you understand.
- Regarding Python, you can try everything each step of the way, read Try it yourself 2.8

Good Luck! I want good grades.

Author: Michael Salloum