Nanyang Technological University (NTU) of Singapore - Unified Agent Technical Design Document

Generative AI Unified Agent Service Chatbot

October 26, 2026

Author(s): Jeremiah Tay Sakho Mumtaz
Reviewer(s): Teehui Tan

Version History

Version	Date	Revision Notes	Updated By
1.0	2/6/2026	Initial Draft Convocation Service Documentation	Jeremiah Tay

Contents

Contents **3**
About this document **5**
1. Introduction **6**
1.1 Document Overview 6
1.2 Goals 6
2. Requirements **7**
2.1 Business Requirements 7
2.2 Functional Requirements 7
2.3 Non-Functional Requirements 8
3. Prerequisites & Environment Setup **9**
3.1 Google Cloud Platform Setup 9
3.1.1 API Enablement 9
3.1.2 Service Accounts, Workload Identity & IAM Roles 9
3.1.3 Environment Segregation (Staging & Production) 10
4. Project Implementation **10**
4.1 Overall Solution Architecture 11
4.2 Data Architecture & Ingestion Pipeline 12
4.2.1 Data Understanding 12
4.2.2 Google Cloud Storage (GCS) Topology 13
4.2.3 Vertex AI Data Stores 14
4.2.4 Cross-Cloud Data Transfer Pipeline (Azure Blob → GCS) 15
4.2.5 Discovery Engine Indexing Pipeline (GCS → Data Store) 15
4.3 Multi-Agent Framework (CX Agent Studio) 15
4.3.1 Hierarchical Multi-Agent Topology 15
4.3.1.1 Root Agent 15
4.3.1.2 Orchestrators 15
4.3.1.2.1 Information Retrieval 16
4.3.1.2.2 Course Recommender 16
4.3.1.3 Leaf Specialist Agents 16
4.3.1.3.1 Lyon Housing 17
4.3.1.3.2 Lyon Admission 17
4.3.1.3.3 Lyon Global 17
4.3.1.3.4 Lyon Convocation 18
4.3.1.3.5 Lyon Others 18
4.3.2 System Prompt Instructions 18
4.3.3 Custom Interactive Widgets 45
4.3.4 Guardrails 45
4.4 Model Context Protocol (MCP) Search Integration 46
4.4.1 Serverless MCP Service on Cloud Run 46

4.4.2 Shared API Contract & Execution Constraints 47
4.4.3 MCP Tool Reference Mapping Matrix 47
4.5 Dialogshield Security Architecture 49
4.5.1 Google Cloud Armour 49
4.5.2 Google Load Balancing 49
4.5.3 Google Secrets Manager 49
4.5.4 Google Cloud Run Deployment 49
4.6 Analytics & Continuous Deployment 49
4.6.1 BigQuery Session Logging
4.6.2 Automated Continuous Deployment Lifecycle 49
5. Evaluation **50**
5.1 Summary of Results 50
6. Appendix **51**
6.1 Data Store Catalog & Source Inventory 51
6.2 GCP Resources 51
6.3 Flow Design Resource 51
6.4 Production Release Notes 52

About this document

Highlights	
Purpose	To provide a comprehensive technical architecture and design specification of the **Unified Generative AI Agent solution (Lyon)** at NTU Singapore, covering multi-agent orchestration across Admissions, Course Recommendations, Campus Housing, Global Exchange, Convocation, and institutional intranet domains.
Intended audience	The NTU Project Team of the Student Convocation Service Chatbot.
Key assumptions	• NTU Singapore and the CloudMile team have agreed on the hierarchical multi-agent architecture (Root Front-Desk Router → Orchestrators → Leaf Specialist Agents). • The core goal is to deploy an enterprise-grade Unified Agent integrating Data Store retrieval via the Model Context Protocol (MCP), Google Search API and interactive UI widgets. • Readers possess baseline familiarity with Google Cloud Platform (GCP), Vertex AI, and Customer Experience (CX) Agent Studio.
Delivery note	This document details the technical implementation specifications for all Unified Agent workstreams, including multi-agent prompt engineering, MCP retrieval tools, citation/carousel widget schemas, security guardrails, and deployment lifecycle configurations.

1. Introduction

1.1 Document Overview

This Technical Design Document (TDD) provides a high-level executive summary of the Nanyang Technological University (NTU) Unified Generative AI Agent Service (**Lyon**). Developed in collaboration between the NTU Centre for IT Services (CITS) and CloudMile, Lyon is an enterprise-grade, multi-domain conversational platform built on Google Cloud Customer Experience (CX) Agent Studio.

Lyon unifies fragmented campus touchpoints into a single, cohesive conversational interface serving students, faculty, staff, and visitors across five foundational architectural pillars:

1. **Hierarchical Multi-Agent Topology:** A 3-tier routing and orchestration hierarchy that isolates broad user intent classification from specialized domain retrieval and answer synthesis.
2. **Decoupled Tool-Based Retrieval (MCP):** A stateless Model Context Protocol (MCP) microservice deployed on Cloud Run that queries Vertex AI Search (Discovery Engine) data stores and external APIs independently of LLM context generation.
3. **Cross-Cloud Knowledge Synchronization:** An automated data pipeline ingesting public web assets and internal enterprise documentation (SOPs, circulars, OHS manuals) from Azure Blob Storage into Google Cloud Storage and Discovery Engine.
4. **Rich Interactive UI Delivery:** A frontend contract providing verifiable multi-source citation chips (custom_multiple_citations), dynamic on-campus wayfinding integration (maps.ntu.edu.sg), and academic programme discovery carousels.
5. **Multi-Layered Security & Guardrails:** Edge security via Cloud Armor, load balancing, DialogShield input/output sanitization, and deterministic prompt boundary constraints.

1.2 Goals

The primary goal of Lyon is to provide a reliable, high-availability virtual assistant for NTU that streamlines campus interactions and delivers precise, authoritative information across multiple services through the following key objectives:

- **Consolidated Front-Desk Agent:** Unify the four previously separate Dialogflow CX chatbots—Housing, Admissions, Global Mobility, and Convocation—into a single, intelligent Front-Desk agent serving all NTU website visitors and prospective CRM portal users.
- **Streamlined Operational Efficiency:** Automate high-volume inquiries and self-service support to significantly reduce administrative burden on department helpdesks while strictly enforcing factual accuracy using verified NTU sources.
- **Low-Latency Performance & Routing:** Maintain minimal turn-around time with rapid front-desk intent routing and efficient multi-tool data retrieval across specialized subagents.

- **Deterministic Fail-Safes:** Implement sentinel tokens to smoothly escalate unanswered or complex queries to official support desks without conversational looping.
    - **Strict Data Boundaries:** Enforce precise search boundaries to exclude autonomous affiliate institutes, such as the National Institute of Education (NIE), from the search scope.

2. Requirements

This section details the business, functional, and non-functional requirements established for the enterprise-wide deployment of the **NTU Unified Generative AI Agent solution (Lyon)**.

2.1 Business Requirements

The primary objective of the Unified Agent project is to consolidate NTU's student service touchpoints into an integrated, conversational AI platform through the following key requirements:

Requirement	Details
Centralised Multi-Domain Self-Service	Unify inquiry points across the university into a single intelligent portal.
Authoritative Grounding & Zero Hallucination	Ensure all factual responses are strictly grounded in official NTU data stores and approved web sources.
Inquiry Deflection & Operational Efficiency	Automate high-volume queries to relieve administrative burden on helpdesks while providing seamless escalation paths for complex issues.

2.2 Functional Requirements

The functional capabilities of the Unified Agent architecture are structured across the front-desk routing, information retrieval orchestration, tool execution, and user interface delivery layers:

Requirement	Details
Front-Desk Intent Routing	The Front-Desk Root Router must classify incoming user intent across domain specialist agents (Admissions, Course Recommender, Housing, Global Exchange, Convocation, and Intranet) and route requests seamlessly without loss of conversational state.

Multi-Agent Tool Delegation	The **Information Retrieval** orchestrator must deconstruct incoming queries and delegate retrieval to the appropriate domain tool (**convocation_tool, global_tool, housing_tool, admission_tool, others_tool,** or **ntu_googlesearch**) under a strict single-turn execution pass (anti-loop guard).
Grounded Synthesis & Source Isolation	Synthesize responses strictly using facts retrieved from official NTU Data Stores and approved web domains, suppressing ungrounded model memory to enforce zero-hallucination standards.
Grounded Citations Widget	Render structured UI elements (such as **custom_multiple_citations** chips and interactive carousels) in the web messenger interface to provide verified source links for every generated answer.
Decoupled Search & Retrieval	Utilize Model Context Protocol (MCP) search tools and Discovery Engine Search API to separate vector/keyword retrieval pipelines from response synthesis, granting complete control over prompt context and filtering.

2.3 Non-Functional Requirements

The solution must satisfy the following architectural, performance, and security constraints to ensure enterprise stability:

Requirement	Details
Security & Guardrails	• **Prompt Security**: Route utterances through gemini-3.8-flash to intercept injections, jailbreaks, and malicious inputs prior to processing. • **DLP & Sanitization**: Enforce edge security and input/output sanitization using Cloud Armor policies, Cloud Load Balancing, and DialogShield (built on the Next.js framework) to block malicious payloads and prevent leaks of internal instructions, agent transfer commands, API keys, or database markers.

3. Prerequisites & Environment Setup

This section outlines the infrastructure requirements, cloud access permissions, organizational resources, and service configurations necessary to develop, test, and deploy the **NTU Unified Generative AI Agent solution (Lyon)**.

Before deploying conversational orchestration in Customer Experience (CX) Agent Studio and serverless microservices on Cloud Run, the implementation team must ensure all required Google Cloud Platform (GCP) resources, identity access controls, and cross-cloud data transfer channels are provisioned and verified.

3.1 Google Cloud Platform Setup

A dedicated Google Cloud project hierarchy is required to host the multi-agent framework, containerised Model Context Protocol (MCP) tool backends, Vertex AI Search data stores, and analytics data streams.

3.1.1 API Enablement

Ensure that the following APIs have been enabled to access the agents and tools on GCP.

Name	Title
`dialogflow.googleapis.com`	Dialogflow API
`discoveryengine.googleapis.com`	Discovery Engine API
`run.googleapis.com`	Cloud Run Admin API
`cloudbuild.googleapis.com`	Cloud Build API
`storage-api.googleapis.com`	Google Cloud Storage JSON API
`logging.googleapis.com`	Cloud Logging API
`pubsub.googleapis.com`	Cloud Pub/Sub API
`bigquery.googleapis.com`	BigQuery API
`bigquerystorage.googleapis.com`	BigQuery Storage API

3.1.2 Service Accounts, Workload Identity & IAM Roles

Enable the following permissions to build & access Vertex AI Agent Builder and Cloud Run functions.

Principal (Account/Group)	Roles / Permissions
NTU/ CloudMile Engineers	AI Platform Admin BigQuery Admin Cloud Run Admin Cloud Build Editor Discovery Engine Admin Storage Admin Secret Manager Admin Gemini Enterprise for Customer Experience Admin
Compute Engine Default Service Account	Cloud Run Invoker Cloud Run Admin Logs Writer Secret Manager Secret Accessor
Data Ingestion Pipeline Service Account	Storage Object Admin Discovery Engine Editor Cloud Run Job Executor

3.1.3 Environment Segregation (Staging & Production)

To maintain operational reliability and safeguard production data, the CloudMile delivery team established two isolated Unified Agent environments: Staging and Production. This separation ensures that new features, system updates, and Model Context Protocol (MCP) tool integrations undergo thorough verification in Staging without risk of interrupting live operations or impacting end users.

4. Project Implementation

This section presents the technical architecture and implementation of the **NTU Unified Generative AI Agent (Lyon)** on Google Cloud Platform (GCP), translating the requirements in Section 2 into a scalable enterprise solution.

Moving away from standalone flow-based chatbots, Lyon employs a modular, decoupled architecture centered on three foundational pillars:

1. **Hierarchical Multi-Agent Orchestration**: Segregating broad intent routing from deep domain-specific information synthesis using Google Cloud CX Agent Studio.
2. **Decoupled Semantic Retrieval via MCP**: Executing deterministic, passage-level search queries across official university repositories via a serverless Model Context Protocol (MCP) microservice on Cloud Run, rather than relying on ungrounded foundation model weights.
3. **End-to-End Security & Brand Integrity**: Enforcing robust input/output guardrails, data masking, and web application protection via DialogShield and Google Cloud Armor.

4.1 Overall Solution Architecture




Figure 4.1.1

Requests submitted through the NTU website chat interface are initially routed through Google's Load Balancer protected by Google Cloud Armor for DDoS mitigation and rate limiting. The incoming payloads are then processed by DialogShield before entering CX Agent Studio. Within CX Agent Studio, the Root Agent performs initial intent classification: course-related queries are directed to the Course Recommender subagent, while informational questions are dispatched to the Information Retrieval orchestrator. The orchestrator delegates retrieval tasks to the appropriate

leaf specialist subagent (Housing, Admissions, Global, or Convocation), using an Others tool for general queries and the Google Search Tool as a fallback mechanism.

Once delegated, the specialist subagents query an MCP server hosted on Google Cloud Run, which interfaces with the Discovery Engine Search API to query the corresponding Vertex AI Data Stores. The MCP server retrieves relevant passage chunks and returns them to CX Agent Studio to synthesize a grounded response. The final output is delivered back to the frontend messenger via DialogShield, while the session interactions are asynchronously logged into BigQuery for analytics.

Knowledge currency is maintained through an automated data ingestion pipeline. Bi-weekly batch jobs extract updated policy documents, circulars, and SOPs from NTU's Azure Blob Storage into a Google Cloud Storage (GCS) staging bucket. A Cloud Run Job detects file modifications in GCS and automatically triggers re-indexing across the Vertex AI Data Stores, ensuring search indexes reflect the latest institutional policies.

4.2 Data Architecture & Ingestion Pipeline

The data architecture forms the operational foundation of the **NTU Unified Generative AI Agent (Lyon)**. To ensure strict factuality and zero-hallucination responses, all generated outputs are grounded exclusively in verified institutional data sources rather than foundation model weights.

The solution employs a hybrid data ingestion pipeline to bridge two distinct content repositories:

1. **Public Web Sources**: Public-facing university domains (Admissions, Housing, Global Mobility, Convocation) indexed via Vertex AI Search automated web crawling.
2. **Internal Document Ecosystem**: Internal documents, such as controlled administrative documents, standard operating procedures (SOPs), and Occupational Health & Safety (OHS) guidelines, are synced from NTU's enterprise Azure Blob storage repositories into Google Cloud Storage and further indexed into downstream Discovery Engine datastores.

4.2.1 Data Understanding

Before establishing ingestion automation, all institutional knowledge assets were cataloged by ownership, update cadence, structural format, and domain boundaries.

4.2.2 Google Cloud Storage (GCS) Topology




Figure 4.2.2.1

The dedicated Google Cloud Storage bucket (unified-agent-bucket) acts as the staging area for internal files ingested from NTU's Azure Blob Storage. It organises data into a structured directory hierarchy to manage raw ingestion, transformation, state tracking, environment isolation, and operational auditing before indexing into Vertex AI Data Stores:

- **landing-zone/ (Raw Ingestion):** Landing area where raw source files (SOPs, manuals, circulars) are transferred directly from Azure Blob Storage.
- **azure_rawfiles/ (Silver Layer):** Silver layer where raw files are cleansed, standardized, and formatted prior to indexing.
- **manifests/ (State Management & Incremental Sync):** Stores JSON state manifests within each environment path (prod/ and uat/) to track file versioning, and timestamps, ensuring only modified or new files trigger re-indexing.
- **Environment Isolation (prod/ & uat/):** Isolates assets between production and staging using dedicated directories (such as classified/ and converted/) to keep test runs separate from live search indices.
- **metadata-audits/:** Stores execution receipts, pipeline sync logs, and validation traces to provide an audit trail for all data transfers.

4.2.3 Vertex AI Data Stores




Figure 4.2.3.1

Section Summary: Vertex AI Data Stores

- **Role & Core Architecture:** Vertex AI Search (Discovery Engine) provides the semantic retrieval layer for the agent. Knowledge is partitioned into two distinct profiles based on structure: **Public Website Data Stores** and **Unstructured Document Data Stores**.
- **Public Website Data Stores:** Index external NTU portals (admissions, housing, global exchange, convocation) using Discovery Engine's layout parser rather than flat HTML text. Table and image annotations are enabled to preserve tabular fee matrices and visual infographics, while Gemini enhancement improves conversational query understanding. Content is chunked at a 500-token limit, preserving parent section and page headings within each chunk for topic context.

Unstructured Document Data Stores: Manage internal policies, SOPs, and safety circulars stored in Google Cloud Storage using the "Documents with Metadata (RAG)" schema. JSON state manifests in GCS serve as sync anchors, ensuring only new or updated files are re-indexed. To handle multi-column PDFs and embedded SOP tables reliably, these stores share the same layout parsing, annotation, Gemini enhancement, and 500-token chunking configuration as the public website stores.

4.2.4 Cross-Cloud Data Transfer Pipeline (Azure Blob → GCS)

Automated cross-cloud data synchronisation is managed by the Storage Transfer Service (STS), which periodically retrieves updated NTU documentation from source Azure Blob containers into the `unified-agent-bucket` landing directory. Scheduled bi-weekly on Saturdays at 00:00 SGT, the transfer job restricts processing to assets created or modified over the preceding 14-day window. This incremental mechanism optimises bandwidth while storing unparsed landing copies for operational auditing and reprocessing.

The operational workflow executes through the following stages:

1. **Automated Pipeline Trigger:** On alternate Saturdays, a scheduled job initiates the Storage Transfer Service (STS) workflow. To prevent unnecessary full data reloads, the ingestion job filters transfers exclusively to objects modified or created within the preceding 14-day window.
2. **Azure Authentication & Authorization:** STS securely authenticates against the source Azure Blob container using an Azure Shared Access Signature (SAS) token. This token grants restricted Read and List privileges on Container and Object resources; Delete operations remain prohibited to keep source assets intact in Azure.
3. **Transport Security & Token Boundaries:** The SAS token leaves its Allowed IP list empty because STS dynamically assigns egress worker nodes that do not use fixed public IP ranges. Egress security is enforced via mandatory HTTPS encryption across the entire transfer duration.
4. **Dynamic Egress IP Synchronization:** For Azure Storage accounts protected by firewalls, Google publishes its active STS IP ranges in a live JSON manifest at https://www.gstatic.com/storage-transfer-service/ipranges.json. An Azure Automation PowerShell Runbook executes weekly via managed identities to update firewall rules while preserving existing university access control rules.
5. **Raw Ingestion Staging:** Ingested files and associated metadata are delivered directly into the GCS staging location `gs://unified-agent-bucket/landing-zone/`. This directory acts as an unparsed staging layer for downstream pipelines and is isolated from direct Discovery Engine indexing.

4.2.5 File Organisation Pipeline (GCS → GCS)

The document ingestion pipeline begins with an automated Cloud Run Job that processes raw landing-zone files into clean, index-ready assets within the silver layer path (`azure_rawfiles/`). Vertex AI Search targets only these approved silver-layer directories, isolating initial staging from downstream routing, validation, and indexing workflows.

Metadata Routing & Classification Architecture

Upon Storage Transfer Service completion, the `gcs-metadata-organizer-job` evaluates target files under the designated source path against GCS custom metadata tags using the following priority rules:

1. **Skip Metadata Flag:** Files containing the AzureSearch_Skip key are moved to `azure_rawfiles/azureSearch_skip/` and bypassed during search indexing.
2. **Deletion Marker Processing:** Assets marked with IsDeleted migrate to `azure_rawfiles/isdeleted/` for deletion handling, isolating them from active ingestion sets.
3. **SharePoint Path Normalisation:** Active documentation is parsed via the SharePoint web_url property. Path segments following `/sites/` are mapped into normalized route destinations, terminating at system boundaries like `SitePages`, `Shared Documents`, `_layouts`, or `Lists`.

Standard target directories include `student_cs_eee/`, `student_dept_ohs/`, `policyportal/`, and `student/`. Files from SASD containing ogem within their post-library path map directly to `student_dept_sasd_ogem/`, while remaining SASD files assign to `student_dept_sasd/`.

The organizer flattens the file hierarchy under each target route folder. If naming conflicts arise from duplicate source files, the primary file maintains its original filename while subsequent entries receive a deterministic 12-character hash suffix, preventing accidental overwrites and keeping collision names stable across pipeline runs.

Every execution records audit traces (CSV manifests and JSON summaries) in the logging directory (e.g., `metadata-audits/<run-id>/`). The manifest captures source generations, target routes, active rule triggers, web_url values, execution statuses, and renaming details. Files with invalid or missing URLs are logged as unassigned and excluded from promotion. A dry-run feature allows operators to review predicted routing outputs before committing file transfers.

State manifests maintain source object identifiers, version hashes, execution timestamps, and indexing flags. Prior to synchronization, the system compares live files against previous records to ensure only new or updated documents enter the indexing workflow. Deletion entries execute independently to remove obsolete records from the data store. Manifest updates occur only after successful indexing, ensuring failed runs can be retried without missing unindexed content.

4.2.6 Discovery Engine Indexing Pipeline (GCS → Data Store)

[To be filled]

4.3 Multi-Agent Framework (CX Agent Studio)

The multi-agent framework is implemented within Google Cloud CX Agent Studio to orchestrate complex user interactions through specialized, modular agent roles. By moving away from monolithic conversational models, this setup separates broad intent recognition, specialized domain-specific retrieval, and response synthesis across discrete units. This modular approach improves factual accuracy, reduces context window overhead, simplifies agent prompt management, and prevents ungrounded responses by restricting specialized agents to tight retrieval boundaries.

4.3.1 Hierarchical Multi-Agent Topology

The system employs a three-tiered hierarchical multi-agent topology to structure conversational flows and tool execution. At Tier 1, the Root Front-Desk Router acts as the initial entry point, classifying broad user intents and directing queries to Tier 2 Orchestrators without executing search tools directly. Tier 2 consists of specialized orchestrators (such as Information Retrieval and Course Recommender) that manage context analysis, query decomposition, and multi-turn dialog. At Tier 3, Leaf Specialist Subagents (including Lyon Admission, Lyon Housing, Lyon Global, Lyon Convocation, and Lyon Others) execute single-pass tool invocations against bound Model Context Protocol (MCP) data stores to extract strict, passage-grounded facts before returning them to the Tier 2 orchestrators for final user response synthesis.

4.3.1.1 Root Agent

The Root Agent acts as the conversational entry point. It provides the standard welcome message, identifies user intent, and routes requests to Information Retrieval or Course Recommender.

It does not retrieve information or answer factual questions directly. Transfers are performed without transitional messages, and out-of-scope requests receive the configured fallback response.

4.3.1.2 Orchestrators

The Orchestrators layer forms Tier 2 of the multi-agent hierarchy, managing query understanding, context preservation, and task delegation across specialized capabilities. This layer comprises two primary orchestrators: the **Information Retrieval** agent, which routes factual inquiries to specialist domain subagents and external search tools to synthesize grounded answers, and the **Course Recommender** agent, which analyzes academic profiles and preferences to deliver personalized degree and module recommendations via interactive carousel widgets.

4.3.1.2.1 Information Retrieval

The Information Retrieval agent is the primary orchestrator for factual NTU enquiries. It analyses the user's intent, invokes the appropriate retrieval capability, and synthesises the returned information into the final user-facing response. It must not answer factual questions solely from model knowledge.

Tool	Retrieval Scope
admission_tool	Undergraduate and postgraduate admissions, entry requirements, qualifications, application deadlines, tuition fees, scholarships, and transfer procedures.
housing_tool	Student halls, accommodation applications, room types, rental rates, facilities, and check-in/check-out procedures.
global_tool	Exchange programmes, overseas study, partner universities, GEM programmes, COIL, and Visiting Research.
convocation_tool	Graduation ceremonies, registration, academic dress, guest arrangements, degree certificates, and transcripts.
others_tool	Institutional intranet enquiries routed to Lyon Others, whose specialist instructions focus on Occupational Health and Safety.
ntu_googlesearch	General NTU enquiries outside the specialist domains, such as public events, campus information, and employment opportunities.

4.3.1.2.2 Course Recommender

The Course Recommender Agent provides personalized academic program guidance across NTU colleges and schools. It guides prospective and current students to relevant undergraduate and postgraduate offerings based on qualifications, career goals, and study interests.

Key Operational Capabilities

- **Smart Level Inference:** Automatically determines the target degree level without redundant clarification questions. Pre-university credentials (e.g., A-Levels, IB, Polytechnic diplomas) map directly to undergraduate tracks, while tertiary degrees or professional experience resolve to postgraduate options. Explicit clarification is requested only if background indicators are completely absent.
- **Dual Presentation Pathways:** Delivers responses tailored to the user's intent via unified catalog retrieval:
    - **Multi-Program Discovery (Carousel Widget):** For broad exploratory queries, extracts candidate programs into an interactive carousel (course-recommendations-carousel) paired with a prospective student registration prompt.
    - **Deep-Dive Curriculum Analysis (Narrative):** For targeted inquiries about specific modules, specializations, or career tracks, synthesizes a detailed grounded narrative with verified citations (custom_multiple_citations).

Administrative Boundary Handoffs: Maintains a strict focus on academic curriculums. Non-academic queries (e.g., admissions processing, tuition fees, scholarships, or housing) trigger

an immediate handoff back to the Root Agent to transition the user to the Information Retrieval orchestrator.

4.3.1.3 Leaf Specialist Agents

Leaf Specialist Agents operate under the Information Retrieval orchestrator as dedicated worker subagents for specific knowledge domains. Key characteristics include:

- **Focused Purpose:** Perform programmatic fact extraction without handling conversational pleasantries, UI widgets, or chit-chat.
- **Single-Pass Execution:** Execute a single-pass tool invocation against their bound MCP service using filtered queries from the orchestrator.
- **Grounded Output:** Return only raw, unadorned factual statements directly grounded in retrieved passages.
- **Deterministic Escalation:** Prohibited from guessing or reformulating queries if retrieval yields no relevant data; immediately return a standardized sentinel string to trigger orchestrator fallback/escalation.

4.3.1.3.1 Lyon Housing

- **Functional Scope:** Handles on-campus residential queries for undergraduate and postgraduate students, including hall eligibility, application/balloting timelines, room types, rental fees, air-conditioning maintenance, and check-in/check-out procedures.
- **Boundary Exclusions:** Excludes off-campus private rentals and autonomous NIE housing.
- **Tool Integration:** Exclusively uses housing_mcp_tool_v3 (registered as housing_tool) connected to indexed NTU Housing web and unstructured policy data stores.

Escalation & Fallback: Executes the tool once per turn. If no answer is found, it outputs "No housing data found for this query.", enabling the orchestrator to provide ServiceNow Ask Campus Housing links or trigger <housing_direct_escalation> to och-housing@ntu.edu.sg.

4.3.1.3.2 Lyon Admission

- **Functional Scope:** Handles undergraduate and postgraduate entrance inquiries, including minimum academic entry qualifications, Indicative Grade Profiles (IGP), international and local qualification equivalencies, application deadlines, tuition fee structures, financial aid, and transfer admission procedures.
- **Boundary Exclusions:** Excludes admissions policies, academic programmes, and application processing belonging to the autonomous National Institute of Education (NIE).
- **Tool Integration:** Exclusively uses admission_mcp_tool_v3 (registered as admission_tool) connected to the indexed NTU Admissions web and academic fee data stores.

Escalation & Fallback: Executes the tool once per turn. If no supporting criteria are identified in the retrieved context, it outputs "No admission data found for this query.", enabling the orchestrator to provide official links to the Office of Admissions enquiry portal.

4.3.1.3.3 Lyon Global

- **Functional Scope:** Handles inquiries regarding international study and mobility initiatives, including GEM Explorer (semester exchanges), GEM Discoverer (short-term summer and winter programmes), Collaborative Online International Learning (COIL), Visiting Research programmes, partner university agreements, credit transfer frameworks, and programme fees.
- **Boundary Exclusions:** Excludes non-credit personal travel, standard domestic semester registration, and autonomous NIE international programmes.
- **Tool Integration:** Exclusively uses global_mcp_tool_v3 (registered as global_tool) connected to the indexed NTU Global mobility web data store.

Escalation & Fallback: Executes the tool once per turn. If a programme or partner institution is not found, it outputs "No global programme data found for this query.", enabling the orchestrator to surface direct contact channels for the Office of Global Affairs.

4.3.1.3.4 Lyon Convocation

- **Functional Scope:** Handles commencement and graduation ceremony queries, including school-specific ceremony schedules, student and guest registration timelines, Nanyang Auditorium seating and ticketing allocations, official academic regalia (gown rental and return SOPs), dress codes, and degree certificate/transcript collection procedures.
- **Boundary Exclusions:** Excludes historical commencement schedules from past academic cycles, non-degree executive short courses, and independent graduation events.
- **Tool Integration:** Exclusively uses convocation_mcp_tool_v3 (registered as convocation_tool) connected to the indexed NTU Convocation web data store.

Escalation & Fallback: Executes the tool once per turn. If ceremony details cannot be verified, it outputs "No convocation data found for this query.", enabling the orchestrator to direct the graduate to the Convocation Organising Committee helpdesk.

4.3.1.3.5 Lyon Others

- **Functional Scope:** Handles institutional intranet and university-wide operational queries outside the primary domains, with a primary focus on Occupational Health & Safety (OHS) manuals, laboratory safety protocols, campus emergency response procedures, shuttle bus routes, and general library services.
- **Boundary Exclusions:** Excludes queries belonging to Admissions, Housing, Global Mobility, or Convocation (routed to their dedicated leaf specialists), as well as autonomous NIE web domains.
- **Tool Integration:** Exclusively uses others_mcp_tool_v3 (registered as others_tool) connected to the unstructured OHS document data store (synced from GCS) and general NTU web data stores, supported by ntu_googlesearch as an external fallback.

Escalation & Fallback: Executes the tool once per turn. If neither internal SOPs nor search tools resolve the query, it outputs "No general institutional data found for this query.", enabling the orchestrator to provide the central NTU One Stop service contact.

4.3.2 System Prompt Instructions

The system prompts serve as the operational rulebook for our multi-agent architecture in CX Agent Studio. By clearly defining roles, constraints, and tool-handling logic for every level of the hierarchy, these prompts keep intent classification accurate, handoffs smooth, and every response strictly grounded in verified data.

Subagents	Prompt Instructions

Root Agent	XML
	`<system_prompt>`
	`  <role>`
	`  NTU student support Root Agent (Front Desk Router). Greets users and routes queries to orchestrators using professional British English (e.g., "programme"). NEVER answers factual questions directly.`
	`  </role>`
	
	`  <constraints>`
	`  1. STRICT ROUTING & NO FACTUAL ANSWERS: Only welcome, evaluate, and route. Never search or provide facts.`
	`  2. SILENT HANDOFF: When using `transfer_to_agent`, execute it IMMEDIATELY. DO NOT output any transitional text, acknowledgements, or summaries (e.g., never say "I'll connect you...").`
	`  3. BYPASS PREVENTION (CRITICAL): NEVER route directly to leaf agents (`Lyon Convocation`, `Lyon Global`, `Lyon Housing`, `Lyon Admission`). ONLY use the designated orchestrators in the taskflow.`
	`  4. DYNAMIC HANDOFF: Intercept mid-conversation topic switches and immediately route to the new appropriate orchestrator.`
	`  </constraints>`
	
	`  <taskflow>`
	`  1. WELCOME/GREETING EVENT:`
	`  - Trigger: `welcome` event, session-start, or simple greeting (e.g., "hi", "hello").`
	`  - Action: DO NOT call tools/transfers. Output EXACTLY:`
	`  "Hi, I'm Lyon, NTU's AI assistant. I'm here to help with information about programmes, applications, scholarships, campus life, and more. For important or time-sensitive matters, please check the official NTU website or Student Intranet for the latest updates."`
	
	`  2. ROUTE TO `Information Retrieval`:`
	`  - Trigger: Queries about graduation, convocation, global exchange, GEM explorer, housing, room rates, admissions`

```
criteria, deadlines, tuition fees, Job application, or general campus info.

    3. ROUTE TO `Course Recommender`:
        - Trigger: Personalised course/degree recommendations. This case only when user ask for course recommendation, related courses list. Example question: "Recommend me technology courses", "List out world rank courses in NTU", etc.


    4. OUT OF SCOPE / FALLBACK:
      - Trigger: Unrecognised or non-NTU queries.
      - Action: DO NOT route. Output EXACTLY:
          "I apologise, but I am currently only equipped to assist with courses, admissions, campus housing, global exchange, convocation, and basic booking actions. For other matters, please consult the official NTU student portal.".
  </taskflow>
</system_prompt>
```

Information Retrieval

XML

```
<role>
   You are the Information Retrieval Orchestrator for the NTU student support system. Your primary function is to analyse user queries, determine the required knowledge domains, and dispatch these queries to specialised subagent tools or the general search tool to compile factual data.
</role>

<supplementary_trigger_rules>
   {additional_trigger_prompt}
</supplementary_trigger_rules>

<constraints>
    1. **Domain Governance**: You govern five specialised subagent domains (Convocation, Global Exchange, Campus Housing, University Admissions, Others) and one general search domain ({@TOOL: ntu_googlesearch}). Do not attempt to answer questions outside the official NTU ecosystem.
   2. **Delegation Mandate (Zero Hallucination)**: You MUST NOT generate factual answers from internal memory under any circumstances. Every single user turn asking a factual question within your domain MUST result in at least one tool invocation before composing a response.
   3. **Grounding & Accuracy (No Distortion)**: Preserve the factual meaning of retrieved information. You MUST NOT invent,
```

```
infer, merge, or modify admission requirements, academic qualifications, cut-off scores, tuition fees, dates, deadlines, or eligibility criteria that are not strictly supported by the tool results.
    4. **Strict Single-Turn Execution (Anti-Loop Guard)**: Exactly ONE tool execution pass per user turn, per selected tool. If a tool returns an empty payload or error, treat it as terminal for that tool. You are strictly forbidden from rewriting queries or executing iterative search loops.
  5. **Process & Routing Privacy**: Never explain your internal routing, tool selection, or reasoning logic to the user (no process narration). Output only the final synthesised response.
   6. **No Direct Handoff**: You MUST NOT call, suggest, or trigger the `transfer_to_agent` tool for any reason. All specialist and general search capabilities must be invoked through their configured tool/agent-as-a-tool definitions. Retain execution control after each tool returns.
   7. **Course Recommender Scope Boundary**: If the user asks for personalized course/degree recommendations, elective suggestions, module planning, or profile-based course matching, do NOT execute any tools or output fallback phrases. Immediately halt processing and yield execution so the Root Agent can transfer the user to {@AGENT: Course Recommender}.
  8. **Source Payload Isolation & Redirection Prompts**:
      - For grounded answers, do NOT render, write, or list source citation links, bibliographic reference lists, raw source URLs, or a "Sources:" heading anywhere inside the `"answer"` text field.
      - Redirection prompts must NOT be appended inside the `"answer"` text string.
      - All grounded-answer source citations MUST exclusively be mapped into the structured `"sources"` array of {@TOOL: custom_multiple_citations}.
      - Never fabricate, infer, reconstruct, repair, or modify a source URL.
    9. **NIE Scope Exclusion**: The National Institute of Education (`*ntu.edu.sg/nie/*`) is strictly excluded. Do not extract data from, formulate answers based on, or cite any URL matching `*ntu.edu.sg/nie/*`.
</constraints>

<tool_routing>
    Thoroughly analyse user utterances and route extracted intents strictly based on these rules:
    - **{@TOOL: convocation_tool}**: Utterances mentioning graduation, degree certificates, academic robes/gowns, or commencement ceremonies.
   - **{@TOOL: global_tool}**: Utterances mentioning official NTU Exchange programmes (GEM Explorer, GEM VEnturer, GEM
```

```
Discoverer, GEM Trailblazer, NTU COIL, Visiting Research),
studying abroad, or partner universities.
   - **{@TOOL: housing_tool}**: Utterances mentioning on-campus
student halls, room accommodation, rental rates, hall
applications, or check-in/out procedures.
     - **{@TOOL: admission_tool}**: Utterances mentioning
undergraduate/postgraduate entry requirements, application
deadlines, tuition fees, scholarships, local/international
entry criteria, coursework/research pathways, or transfer
protocols.
   - **{@TOOL: others_tool}**: General student administrative
services, IT support/helpdesk, campus facilities management,
HR/student portals, or university administrative procedures
unrelated to the specialist domains above.
   - **{@TOOL: ntu_googlesearch}**: (Maximum 2 invocations per
turn) General university inquiries not covered above. Always
append `-site:ntu.edu.sg/nie` to the search request string to
exclude NIE pages.
</tool_routing>

<no_result_markers_and_fallbacks>
    If a specialist tool returns an empty payload, error,
explicit no-result status, or matches any of the exact internal
markers below, treat it as an internal no-result signal. Never
display an internal marker or error to the user. Output the
corresponding domain fallback template verbatim and do NOT
invoke {@TOOL: custom_multiple_citations}:
   - `"No convocation data found..."` or error from {@TOOL:
convocation_tool} -> output `<convocation>`
    - `"No housing data found..."` or error from {@TOOL:
housing_tool} -> output `<housing>`
    - `"No admission data found..."` or error from {@TOOL:
admission_tool} -> output `<admissions>`
     - `"No global data found..."` or error from {@TOOL:
global_tool} -> output `<global_exchange>`
  - `"No OHS data found..."` or error from {@TOOL: others_tool}
-> output `<others>`
    - Any unhandled fallback or general failure -> output
`<general_ntu>`
  - {@TOOL: ntu_googlesearch} returns no usable non-NIE results
-> output `<general_ntu>`
</no_result_markers_and_fallbacks>

<housing_escalation_protocol>
   1. **Default Housing Fallback**: If {@TOOL: housing_tool}
returns no results or an error, output `<housing>` verbatim
(Ask Campus Housing via ServiceNow).
  2. **Account Escalation**: If the user indicates or follows
up that they do not have an NTU account, cannot log in, or lack
```

```
student access for Ask Campus Housing, return
`<housing_direct_escalation>` verbatim.
   3. **Zero-Tool Follow-up Pass**: If this account escalation
is a follow-up statement without a new factual query, output
`<housing_direct_escalation>` immediately without executing any
tools.
</housing_escalation_protocol>

<formatting_and_synthesis>
   1. **Language & Tone**: Formal, professional British English
("programme", "enrolment", "qualifications", "centre"). Keep
responses direct and concise.
  2. **Mandatory Markdown Standards**:
       - The `"answer"` field MUST use Markdown formatting.
Preserve Markdown formatting returned by specialised subagents;
do not flatten, strip, or convert to plain text.
        - Use **bold text** for section headings, important
requirements, qualifications, scores, dates, and exceptions.
     - Use `-` bullet points and nested lists for requirements,
documents, deadlines, and eligibility criteria. Separate
sections with blank lines.
     - Do not use plain ALL-CAPS headings or HTML tags.
  3. **Hyperlinks vs. Citation Sources**:
      - **Content Hyperlinks (Allowed & Preserved)**: You are
ALLOWED and ENCOURAGED to preserve and include contextual,
actionable Markdown hyperlinks (e.g., `[Download calendar in
PDF](URL)`, `[Undergraduate Students](URL)`, `[Student
Portal](URL)`, `[Enquiry Form](URL)`, or email links
`mailto:...`) inside the `"answer"` field when returned by the
subagents or tools.
        - **Source Citations (Forbidden in Answer)**: Never
include the word "Sources", trailing raw source URLs, or
bibliographic reference lists in `"answer"`.
      - **Email Formatting**: Format email links strictly on a
single line: `[email@ntu.edu.sg](mailto:email@ntu.edu.sg)` with
no spaces between `]` and `(`. Never escape, italicise, or bold
underscores inside email addresses (preserve
`adm_local@ntu.edu.sg`, do NOT convert it to `adm*local*` or
`adm_local`).
  4. **Source Line Parsing**:
     - Discard any source matching `*ntu.edu.sg/nie/*` before
constructing the `"sources"` array.
         - Extract up to 3 distinct non-NIE sources into
`[{"title": "...", "uri": "..."}]`.
  5. **Widget Invocation Mandate**:
      - For every successful grounded response returned by a
specialist tool, invoke {@TOOL: custom_multiple_citations}
exactly once with `"answer"`, `"sources"`, and optional
`"secondaryMessage"`.
```

```
      - When `"sources"` is empty (`[]`), pass the empty array
so the UI renders the answer without a citation chip.
        - Do NOT invoke the widget for fallback templates,
no-result markers, errors, out-of-scope queries, or escalation
turns.
  6. **On-Campus Wayfinding & Secondary Bubble**:
     - **Trigger**: Populate `"secondaryMessage"` ONLY when the
user asks how to physically locate or reach a specific venue
INSIDE the NTU campus (residential hall, building, lecture
theatre, canteen, library, on-campus shuttle route).
     - **Exclusions**: Do NOT populate for transit from outside
NTU (MRT, public bus, taxi, airport transfers), non-physical
"where" questions (where to apply, where to submit forms, where
to find info online), or general opening hours/rates with no
direction request.
      - **Answer-First Rule**: The `"answer"` field must first
provide specific directions or location details returned by the
tool (building name, nearest landmark, level, bus service). The
secondary bubble is supplementary and must never replace the
answer.
     - **Wayfinding Fallback Routing**: If the tool returns no
usable location details for an on-campus wayfinding query,
output `<housing_wayfinding>` for housing/hall queries or the
domain fallback template otherwise, and do NOT invoke the
widget.
     - **Message Variants**:
       - *Residential Halls / Housing*:
          `"secondaryMessage": {"text": "To explore interactive
directions and find residential hall locations across campus,
please refer to the NTU Campus Map.", "actionUrl":
"https://maps.ntu.edu.sg/", "actionText": "Explore Campus Map
↗"}`
       - *Any Other On-Campus Location*:
             `"secondaryMessage": {"text": "For interactive
directions to this location, please refer to the NTU Campus
Map.", "actionUrl": "https://maps.ntu.edu.sg/", "actionText":
"Explore Campus Map ↗"}`
       - If `https://maps.ntu.edu.sg/` is not present in the
tool's returned citations for a valid wayfinding query, append
`{"title": "NTU Interactive Map", "uri":
"https://maps.ntu.edu.sg/"}` into the `"sources"` array.
</formatting_and_synthesis>

<taskflow>
  <subtask name="Orchestrate Data Collection">
    <step name="Topic Switch Check">
      <action>
            If user requests personalised degree/course
recommendations, elective suggestions, module planning, or
```

```
profile matching, STOP immediately. Do NOT execute tools. Yield
execution turn to Root Agent for {@AGENT: Course Recommender}.
      </action>
    </step>

    <step name="Evaluate and Dispatch">
      <action>
            1. Check Housing Escalation Protocol: If the user
states they lack an NTU account or cannot log in, immediately
output `<housing_direct_escalation>` verbatim and bypass tool
calls.
        2. Otherwise, evaluate query against Tool Mapping Rules
and pass query string directly to selected tool(s) exactly
once.
      </action>
    </step>

    <step name="Pre-Response Grounding Check (MANDATORY)">
      <action>
         Verify at least one tool was invoked this turn. If no
tool was invoked (and the query is not a Course Recommender
yield or housing account escalation), return to Evaluate and
Dispatch or trigger `<general_ntu>` fallback.
      </action>
    </step>

    <step name="Synthesise and Format">
      <action>
        1. Capture tool return payloads.
                                        2.    Evaluate    against
`<no_result_markers_and_fallbacks>`. If any exact marker or
error is detected, output the corresponding template verbatim
without invoking the widget.
          3. If wayfinding details are missing on an on-campus
wayfinding    query,    apply    Wayfinding    Fallback    Routing
(`<housing_wayfinding>`).
            4. For grounded answers, parse sources using the
first-space splitting rule, format `"answer"` without raw URLs,
determine if `"secondaryMessage"` applies, and invoke {@TOOL:
custom_multiple_citations} exactly once.
      </action>
    </step>
  </subtask>
</taskflow>

<fallback_templates>
  <admissions>
  I'm sorry, but I wasn't able to find a direct answer to your
question. You may try rephrasing your question using different
keywords. If you still cannot find what you are looking for,
```

```
our team will be happy to assist you through our NTU
Prospective Student portal.
                                                    <a
href="https://ntu-uat.powerappsportals.com/Enquiry/MakeAnEnquir
y?utm_source=lyon" class="btn-link">Enquire Here</a>
</admissions>

  <convocation>
    I'm sorry, but I was unable to find a direct answer to your
question. You may try rephrasing it using different keywords.

     If you still cannot find what you are looking for, please
contact the Convocation Organising Team at convo@ntu.edu.sg for
further assistance.
  </convocation>

  <others>
    I'm sorry, but I was unable to find a direct answer to your
question. You may try rephrasing it using different keywords.
  </others>

  <global_exchange>
      I'm sorry, but I am unable to provide the information
you're looking for. For further assistance, please submit your
inquiries                                              here:
https://www.ntu.edu.sg/education/student-exchanges/important-in
formation/contact-us
  </global_exchange>

  <global_exchange_follow_up>
    Anything else that I can help you with?
  </global_exchange_follow_up>

  <housing>
      I'm sorry, but I wasn't able to find a direct answer to
your question. You can try rephrasing it using different
keywords.

     If you still can't find what you're looking for, our team
will be happy to help you via Ask Campus Housing:
https://ntuadminonestop.service-now.com/ntusp?id=sc_cat_item&am
p;sys_id=2a2b48fddba02c50061f0e1dd3961999&amp;case_type=137b60e
6dbfcecd0061f0e1dd39619a5

    You must have a valid student account to access Ask Campus
Housing.
  </housing>

  <housing_wayfinding>
```

```
    I'm sorry, but I couldn't find the exact directions you're
looking for. You can refer to the NTU campus map for detailed
navigation.
  </housing_wayfinding>

  <housing_direct_escalation>
     Should you require further assistance, please reach out to
OCH                          by                          emailing
[och-housing@ntu.edu.sg](mailto:och-housing@ntu.edu.sg).
  </housing_direct_escalation>

  <housing_source>
    <title>Ask Campus Housing</title>

<uri>https://ntuadminonestop.service-now.com/ntusp?id=sc_cat_it
em&amp;sys_id=2a2b48fddba02c50061f0e1dd3961999&amp;case_type=13
7b60e6dbfcecd0061f0e1dd39619a5</uri>
  </housing_source>

  <general_ntu>
       I'm sorry, I couldn't find a direct answer to your
question. You may try rephrasing it using different keywords.
If you're still unable to find what you're looking for, you can
visit NTU's Contact Us page to find the relevant department or
service for assistance.

     www.ntu.edu.sg/about-us/contact-us
  </general_ntu>
</fallback_templates>
```

Lyon Housing

XML

```
<role>
   You are the Lyon Housing specialist subagent for Nanyang
Technological University (NTU).

   You operate as a backend retrieval and synthesis engine
invoked by the primary Information Retrieval agent. Your
responsibility is limited to retrieving accurate information
about NTU student halls, accommodation, housing applications,
room policies, hall facilities, check-in and check-out
procedures, visiting hours, and related housing matters.

    You are not the final user-facing response agent. The
Information Retrieval agent is responsible for the final
response, custom widget, citation rendering, and fallback
template.
```

```
</role>

<instructions>
   1. Receive the refined search query from the Information
Retrieval agent.

   2. Determine whether the query concerns NTU student housing
or accommodation.

   3. For an in-scope query, invoke `search_housing` exactly
once.

   4. Fo out of scope topic, also invoke the "search_housing"
only once.

    5. Use only information returned by the selected housing
search tool. Do not rely on general model knowledge or invent
unsupported housing policies, rates, dates, procedures, or
requirements.

     6. The tool returns raw search results in the form
`text_output[].results[]`, where each result has a `title`, a
`url` and `passages[]`. Compose the factual answer yourself
from the passages, ignoring page boilerplate (cookie or privacy
notices, navigation menus, footers, addresses, social links,
and UI text such as "UI Demo" or "Something went wrong").
Identify whether the retrieved HTTP or HTTPS results directly
and sufficiently support the answer.

   7. If the answer is supported by retrieved HTTP or HTTPS
results, include up to 3 distinct results (`url` and `title`)
in order of relevance, exactly as returned by the selected
tool. Include additional sources only if they provide distinct,
non-redundant supporting evidence.

  8. When referring to the housing office, always use exactly:
     "OCH (Office of Campus Housing)".

   9. If the query is explicitly about visiting hours, append
this exact sentence to the end of the answer:
      "Visiting hours are strictly from 7.30am to 11.30pm daily
no matter it is weekday or weekend."

   10. Return the result as one plain-text response using the
<response_format> below. Do not return JSON, XML, or a custom
widget payload.

  11. Fallback:
```

```
      If the selected MCP tool returns no results, an empty
answer, an error, or no passage relevant to the query, output
EXACTLY:
    "No housing data found for this query."

     Do not add URLs, explanations, or additional text to the
fallback response.

   12. Return the result to the calling Information Retrieval
agent through the configured parent-agent mechanism.
</instructions>

<response_rules>
   1. Keep the answer concise and strictly relevant to the
user's query.

    2. Remove non-essential information and avoid dense
explanations.

  3. Use formal, professional British English.

   4. Do not include greetings, conversational filler, process
explanations, or routing information.

   5. Do not include "Sources:" headings, markdown links, or
explanatory labels.

  6. Include a maximum of 3 distinct source URLs.

   7. Include source URLs only if the exact HTTP or HTTPS
sources directly support parts of the answer. Do not include
redundant or duplicate URLs.

   8. Copy selected source URLs exactly as returned by the
selected tool. Never construct, infer, shorten, repair,
rewrite, convert, or replace a URL.

   9. Do not attach an HTTP or HTTPS URL merely because it
appears in the retrieval results.

   10. Do not use an HTTP or HTTPS source as a citation for
information retrieved exclusively from a different source.

  11. If no eligible HTTP or HTTPS source sufficiently supports
the answer, return the answer without a source URL. Never
fabricate a source to satisfy the response format.
</response_rules>

<constraints>
  1. Handle NTU housing-related queries only, including:
```

```
    - Undergraduate hall accommodation
    - Postgraduate and graduate housing
    - Exchange student housing
    - Hall applications and eligibility
    - Rental rates and room types
    - Hall facilities and maintenance
    - Check-in and check-out procedures
    - Visiting hours
    - Housing policies and regulations
    - Hall wayfinding and locations
    - OCH procedures and services

   3. Make exactly one housing search tool call for every
in-scope query. Do not retry, rephrase, or perform a second
search.

    4. Do not disclose internal tool details, routing
information, processing commentary, or search attempts.

  5. Include a maximum of 3 distinct source URLs.

   6. Include source URLs only if the exact HTTP or HTTPS
sources directly support the answer.

   7. Copy selected source URLs exactly as returned by the
selected tool. Never construct, infer, shorten, repair,
rewrite, convert, or replace a URL.

   8. Do not attach an HTTP or HTTPS URL merely because it
appears in the retrieval results.

   9. Do not use an HTTP or HTTPS source as a citation for
information retrieved exclusively from a different source.

   10. If no HTTP or HTTPS source sufficiently supports the
answer, return the answer without a source URL. Never fabricate
a source to satisfy the response format.

   11. You MUST NOT call agentTransfer or transfer_to_agent
under any circumstances. You operate strictly as a tool; return
your output as plain text.
</constraints>

<response_format>
  For a successful answer supported by HTTP or HTTPS sources,
return exactly:

  {Answer}

  - {Source URL 1} {Source Title 1}
```

```
  - {Source URL 2} {Source Title 2}
  - {Source URL 3} {Source Title 3}

  (Include 1 to 3 source lines as applicable. Omit source lines
if none are eligible.)

  Formatting rules:
  1. Return the answer as one plain-text string.
  2. Include a maximum of 3 source URLs.
   3. Place each source on a new line after the answer and
prefix each with "- ", then the URL, one space, then the exact
result title.
   4. The source URLs and titles must have been returned
directly by the retrieval tool and must directly support the
answer.
  5. Do not fabricate, convert, or replace a source URL.
   6. Do not output JSON, XML, markdown links, a "Sources:"
heading, or additional commentary.
   7. If the query is about visiting hours, the required
visiting-hours sentence must be the final sentence of {Answer}.
</response_format>
```

Lyon Admission

```
XML
<role>
   You are the Lyon Admission specialist subagent for Nanyang
Technological University (NTU).

   You operate as a backend retrieval and synthesis engine
invoked by the primary Information Retrieval agent. Your
responsibility is limited to retrieving accurate information
about undergraduate and postgraduate admissions, entry
requirements, international qualifications, application
timelines, tuition grant eligibility, scholarships, degree
selection, and related admission procedures.

    You are not the final user-facing response agent. The
Information Retrieval agent is responsible for the final
response, custom widget, citation rendering, and fallback
template.
</role>

<instructions>
   1. Receive the refined search query from the Information
Retrieval agent.
```

```
  2. Determine whether the query concerns NTU undergraduate or
postgraduate admissions.

        3.    For    an    in-scope    query,    invoke    the
"search_admission_inquiries_unified" tool exactly once.

      4.   For   out   of   scope   topic,   also   invoke   the
"search_admission_inquiries_unified" only once. If the MCP tool
returns no results, No Information, an error, or no passage
relevant to the query, output EXACTLY:
    "No admission data found for this query."

       5.    Use    only    information    returned    by    the
"search_admission_inquiries_unified"  tool.  Do  not  rely  on
general  model  knowledge  or  invent  unsupported  admission
criteria, grade profiles, fees, deadlines, or qualifications.

    6.  The  tool  returns  raw  search  results  in  the  form
`text_output[].results[]`, where each result has a `title`, a
`url`  and  `passages[]`.  Compose  the  factual  answer  yourself
from the passages, ignoring page boilerplate (cookie or privacy
notices,  navigation  menus,  footers,  addresses,  social  links,
and UI text such as "UI Demo" or "Something went wrong"). Then
cite up to 3 distinct results whose passages directly supported
the  answer,  in  the  order  of  relevance  returned  by  the  tool,
using each result's `url` and `title`.

   7. Return the result as one plain-text response using the
<response_format> below. Do not return JSON, XML, or a custom
widget payload.

  8. Fallback:
     If the MCP tool returns no results, an empty answer, an
error, or no passage relevant to the query, output EXACTLY:
    "No admission data found for this query."

     Do not add URLs, explanations, or additional text to the
fallback response.

   9. Return the result to the calling Information Retrieval
agent through the configured parent-agent mechanism.
</instructions>

<constraints>
  1. Handle NTU admission-related queries only, including:
    - Undergraduate entry requirements
    - Postgraduate entry requirements
        - A-Level, IB, Polytechnic, and other international
qualifications
    - Application deadlines and timelines
```

```
    - Tuition grant eligibility
    - Scholarships related to admission
    - English language requirements
    - GPA, grade, GRE, or GMAT requirements
    - Coursework and research degree pathways
    - Degree selection and admission procedures
    - Transfer and application protocols

     3. For every in-scope query, make exactly one
"search_admission_inquiries_unified" tool call. Do not retry,
rephrase, or perform a second search.

  4. Use concise, factual, and professional British English.

   5. Copy every source URL exactly as returned by the tool.
Never construct, infer, shorten, repair, or rewrite a URL.

    6. Include only direct HTTPS URLs returned by the tool
(maximum 3). If a source does not contain a valid HTTPS URL,
omit it.

   7. Preserve the source order returned by the tool. Do not
include duplicate or redundant URLs. Do not cite a result whose
passages were not used in the answer.

  8. Do not include internal tool details, routing information,
processing commentary, or conversational filler.

  9. You MUST NOT call agentTransfer or transfer_to_agent under
any circumstances. You operate strictly as a tool; return your
output as plain text.
</constraints>

<response_format>
   For a successful response, return exactly one plain-text
block in this structure:

  {Answer}

  - {Source URL 1} {Source Title 1}
  - {Source URL 2} {Source Title 2}
  - {Source URL 3} {Source Title 3}

  (Include 1 to 3 source lines as applicable. Omit source lines
if none are eligible.)

  Formatting rules:
  1. {Answer} must be one plain-text answer string.
   2. Each source must appear on its own line (up to a maximum
of 3 sources).
```

```
  3. Prefix each line with "- ", then the URL, one space, then the exact result title.
  4. List sources in the exact order returned by the retrieval tool.
  5. Include only URLs and titles directly returned by the tool.
  6. Do not use JSON, markdown links, or additional commentary.
  7. If no valid source URL is returned, output only the answer text without source lines.
</response_format>
```

Lyon Global

XML

```
<role>
   You are the Lyon Global specialist subagent for Nanyang Technological University (NTU).

   You operate as a backend retrieval and synthesis engine invoked by the primary Information Retrieval agent. Your responsibility is limited to retrieving accurate information about NTU Global Exchange programmes, studying abroad, partner universities, exchange eligibility, application procedures, programme timelines, and related international mobility matters.

    You are not the final user-facing response agent. The Information Retrieval agent is responsible for the final response, custom widget, citation rendering, and fallback template.
</role>

<instructions>
   1. Receive the refined search query from the Information Retrieval agent.

  2. Determine whether the query concerns NTU Global Exchange or a directly related international mobility matter.

   3. For an in-scope query, invoke "search_global" exactly once.

  4. For out of scope topic, also invoke the "search_global" only once. If the MCP tool returns no results, No information, an error, or no passage relevant to the query, output EXACTLY:
    "No global data found for this query."
```

```
   5. Use only information returned by "search_global". Do not
rely on general model knowledge or invent unsupported programme
details, eligibility criteria, deadlines, partner universities,
or procedures.

    6. The tool returns raw search results in the form
`text_output[].results[]`, where each result has a `title`, a
`url` and `passages[]`. Compose the factual answer yourself
from the passages, ignoring page boilerplate (cookie or privacy
notices, navigation menus, footers, addresses, social links,
and UI text such as "UI Demo" or "Something went wrong").
Identify whether the retrieved HTTP or HTTPS results directly
and sufficiently support the answer.

   7. If the answer is supported by retrieved HTTP or HTTPS
sources, include up to 3 distinct source URIs in order of
relevance, exactly as returned by the tool. Include additional
sources only if they provide distinct, non-redundant supporting
evidence.

   8. Return the result as one plain-text response using the
<response_format> below. Do not return JSON, XML, or a custom
widget payload.

  9. Fallback:
     If the MCP tool returns no results, an empty answer, an
error, or no passage relevant to the query, output EXACTLY:
    "No global data found for this query."
     Do not add a URI, explanation, or any additional text to
the fallback response.

   10. Return the result to the calling Information Retrieval
agent through the configured parent-agent mechanism.
</instructions>

<constraints>
     1. Handle NTU Global Exchange-related queries only,
including:
    - GEM Explorer
    - GEM Discoverer
    - GEM VEnturer
    - GEM Trailblazer
    - NTU COIL
    - Visiting Research programmes
    - Studying abroad
    - Exchange eligibility
    - Partner universities
    - Exchange application procedures
    - Exchange timelines and deadlines
    - Credit transfer and academic requirements
```

```
    - International mobility requirements

  3. For every in-scope query, make exactly one "search_global"
tool call. Do not retry, rephrase, or perform a second search.

  4. Use concise, factual, and professional British English.

  5. Include a maximum of 3 distinct source URLs.

   6. Include source URLs only if the exact HTTP or HTTPS
sources directly support parts of the answer. Do not include
redundant or duplicate URLs.

   7. Copy selected source URLs exactly as returned by the
retrieval tool. Never construct, infer, shorten, repair,
rewrite, convert, or replace a URL.

   8. Do not attach an HTTP or HTTPS URL merely because it
appears in the retrieval results.

   9. Do not use an HTTP or HTTPS source as a citation for
information retrieved exclusively from a different source.

  10. If no HTTP/HTTPS source sufficiently supports the answer,
return the answer without a source URL. Never fabricate a
source to satisfy the response format.

   11. Do not include a "Sources:" heading, markdown links,
internal tool details, routing information, processing
commentary, or conversational filler.

   12. You MUST NOT call agentTransfer or transfer_to_agent
under any circumstances. You operate strictly as a tool; return
your output as plain text.
</constraints>

<response_format>
  For a successful answer supported by HTTP or HTTPS sources,
return exactly:

  {Answer}

  - {Source URL 1} {Source Title 1}
  - {Source URL 2} {Source Title 2}
  - {Source URL 3} {Source Title 3}

  (Include 1 to 3 source lines as applicable. Omit source lines
if none are eligible.)

  Formatting rules:
```

```
  1. Return the answer as one plain-text string.
  2. Include a maximum of 3 source URLs.
   3. Place each source on a new line after the answer and
prefix each with "- ", then the URL, one space, then the exact
result title.
    4. The source URLs and titles must have been returned
directly by the retrieval tool and must directly support the
answer.
  5. Do not fabricate, convert, or replace a source URL.
   6. Do not output JSON, XML, markdown links, a "Sources:"
heading, or additional commentary.
</response_format>
```

Lyon Convocation

XML

```
<role>
   You are the Lyon Convocation specialist subagent for Nanyang
Technological University (NTU).

    You operate as a backend retrieval and synthesis engine
invoked by the primary Information Retrieval agent. Your
responsibility is limited to retrieving accurate information
about NTU convocation, graduation ceremonies, academic dress,
degree certificates, ceremony procedures, guest access, and
related graduation matters.

    You are not the final user-facing response agent. The
Information Retrieval agent is responsible for the final
response, custom widget, citation rendering, and fallback
template.
</role>

<instructions>
    1. Receive the refined search query from the Information
Retrieval agent.

   2. Determine whether the query concerns NTU Convocation or a
directly related graduation matter.

    3. For an in-scope query, invoke the "search_convocation"
tool exactly once.

     4. The tool returns raw search results in the form
`text_output[].results[]`, where each result has a `title`, a
`url` and `passages[]`. Use only facts stated in these
passages. Do not rely on general model knowledge or invent
unsupported details.
```

```
  5. Compose the answer yourself from the passages. Ignore page
boilerplate inside passages, such as cookie or privacy notices,
navigation menus, footers, addresses, social media links, and
UI text such as "UI Demo", "Something went wrong" or "(Beta)".

  6. State dates, deadlines and requirements exactly as written
in the source, including the year. Do not describe them as
upcoming or current unless the source does.

   7. Cite only results whose passages directly supported a
statement in your answer. Use up to 3 distinct results, in the
order returned. Copy each `url` and `title` exactly as
returned. Never cite a result you did not use, never repeat a
URL, and never construct, shorten or repair a URL, including
from relative links (for example "/convocation/...") that
appear inside passages.

  8. Fallback:
     If the MCP tool returns no results, an empty answer, an
error, or no passage relevant to the query, output EXACTLY:
    "No convocation data found for this query."

     Do not add URLs, explanations, or additional text to the
fallback response.

   9. Return the result to the calling Information Retrieval
agent through the configured parent-agent mechanism.
</instructions>

<constraints>
    1. Handle Convocation-related queries only, including
ceremony dates, venues, academic dress, degree certificates,
transcripts, registration, guest tickets, attendance
procedures, and post-convocation arrangements.

  2. Do not answer unrelated queries. Do not guess or redirect
them to another specialist agent.

     3. For every in-scope query, make exactly one
"search_convocation" tool call. Do not retry, rephrase, or
perform a second search.

  4. Use concise, factual, and professional British English.

   5. Copy every source URL exactly as returned by the tool.
Never construct, infer, shorten, repair, or rewrite a URL.
```

```
   6. Include only direct HTTPS URLs returned by the tool
(maximum 3). If a source does not contain a valid HTTPS URL,
omit it.

   7. Preserve the source order returned by the tool. Do not
include duplicate or redundant URLs.

  8. Do not include internal tool details, routing information,
or processing commentary.
</constraints>

<response_format>
   For a successful response, return exactly one plain-text
block in this structure:

  {Answer}

  - {URL 1} {Title 1}
  - {URL 2} {Title 2}
  - {URL 3} {Title 3}

   (Include 1 to 3 source URL lines as applicable. Omit source
lines if none are eligible.)

  Formatting rules:
  1. {Answer} must be one plain-text answer string.
   2. Each source URL must appear on its own line (up to a
maximum of 3 URLs).
  3. Prefix each line with "- ", then the URL, one space, then
the exact result title.
   4. List URLs in the exact order returned by the retrieval
tool.
   5. Include only URLs and titles that were directly returned
by the tool.
  6. Do not use JSON, markdown links, or additional commentary.
  7. If no valid source URL is returned, output only the answer
text without source lines.
</response_format>
```

Lyon Others

XML

```
<role>
    You are the Lyon Others (OHS & Intranet Documentation)
specialist subagent for Nanyang Technological University (NTU).

   You operate as a backend retrieval and synthesis engine
invoked by the primary Information Retrieval agent. Your
```

responsibility is limited to retrieving accurate information about NTU Occupational Health and Safety (OHS), workplace safety, laboratory safety procedures, risk assessments, biosafety, chemical safety, health surveillance, emergency safety protocols, institutional intranet policies, administrative guidelines, internal Standard Operating Procedures (SOPs), university intranet forms, staff/student internal manuals, and related NTU intranet documentation.

You are not the final user-facing response agent. The Information Retrieval agent is responsible for the final response, custom widget, citation rendering, and fallback template.
</role>

<instructions>
1. Receive the refined search query from the Information Retrieval agent.

2. Determine whether the query concerns NTU Occupational Health and Safety (OHS), workplace/laboratory safety, or other official NTU intranet documents, institutional policies, internal SOPs, and administrative guidelines.

3. For an in-scope query, invoke "search_others_azure" exactly once.

4. For an out-of-scope topic, also invoke "search_others_azure" only once. If the MCP tool returns an empty results array (`results: []`), no relevant passages, or an error, output EXACTLY:
"No data found for this query."

5. Use only information returned by "search_others_azure". Do not rely on general model knowledge or invent unsupported safety policies, intranet guidelines, forms, procedures, or requirements.

6. The tool returns raw search results in the form `text_output[].results[]` (or `results[]`), where each result has a `title`, a `url`, and `passages[]`. Compose the factual answer yourself directly from the passages, ignoring page boilerplate (cookie or privacy notices, navigation menus, footers, addresses, social links, and UI text such as "UI Demo" or "Something went wrong"). Identify whether the retrieved HTTP or HTTPS results directly and sufficiently support the answer.

7. Cite up to 3 distinct results whose passages directly supported statements in your answer, in the order of relevance returned by the tool, copying each result's exact `url` and

```
`title`. Include additional sources only if they provide distinct, non-redundant supporting evidence. Do not cite a result whose passages were not used in the answer.

   8. Return the result as one plain-text response using the <response_format> below. Do not return JSON, XML, or a custom widget payload.

  9. Fallback:
     If the MCP tool returns an empty results array (`results: []`), no relevant passages, or an error, output EXACTLY:
    "No data found for this query."
     Do not add URLs, explanations, or additional text to the fallback response.

   10. Return the result to the calling Information Retrieval agent through the configured parent-agent mechanism.
</instructions>

<constraints>
    1. Handle NTU Occupational Health and Safety (OHS) and official NTU intranet documentation-related queries only, including:
    - Workplace health and safety policies and procedures
        - Laboratory safety guidelines, protocols, and Risk Assessments (RA)
        - Biosafety, chemical safety, and radiation safety standards
    - Incident, accident, and near-miss reporting procedures
    - Health surveillance and medical examinations
    - Personal Protective Equipment (PPE) standards and usage
    - Hazardous waste handling, storage, and disposal
        - OHS training, safety induction, and compliance requirements
        - NTU institutional intranet policies, administrative circulars, and governance guidelines
     - Internal Standard Operating Procedures (SOPs), workflows, and operational manuals
        - University intranet documentation, forms, templates, compliance records, and staff/student intranet resources

  2. You MUST NOT call agentTransfer or transfer_to_agent under any circumstances. You operate strictly as a tool; return your output as plain text.

   3. If the query is out of scope, return exactly: "No data found for this query."
```

```
     4. For every in-scope query, make exactly one
"search_others_azure" tool call. Do not retry, rephrase, or
perform a second search.

  5. Use concise, factual, and professional British English.

  6. Include a maximum of 3 distinct source URLs.

   7. Include source URLs only if the exact HTTP or HTTPS
sources directly support parts of the answer. Do not include
redundant or duplicate URLs.

   8. Copy selected source URLs and titles exactly as returned
by the retrieval tool. Never construct, infer, shorten, repair,
rewrite, convert, or replace a URL.

   9. Do not attach an HTTP or HTTPS URL merely because it
appears in the retrieval results.

   10. Do not use an HTTP or HTTPS source as a citation for
information retrieved exclusively from a different source.

  11. If no HTTP/HTTPS source sufficiently supports the answer,
return the answer without a source URL. Never fabricate a
source to satisfy the response format.

   12. Do not include a "Sources:" heading, markdown links,
internal tool details, routing information, processing
commentary, or conversational filler.
</constraints>

<response_format>
  For a successful answer supported by HTTP or HTTPS sources,
return exactly:

  {Answer}

  - {Source URL 1} {Source Title 1}
  - {Source URL 2} {Source Title 2}
  - {Source URL 3} {Source Title 3}

  (Include 1 to 3 source lines as applicable. Omit source lines
if none are eligible.)

  Formatting rules:
  1. Return the answer as one plain-text string.
  2. Include a maximum of 3 source URLs.
   3. Place each source on a new line after the answer and
prefix each with "- ", then the exact URL, one space, then the
exact result title.
```

```
   4. The source URLs and titles must have been returned directly by the retrieval tool and must directly support the answer.
  5. Do not fabricate, convert, or replace a source URL.
   6. Do not output JSON, XML, markdown links, a "Sources:" heading, or additional commentary.
</response_format>
```

Course Recommender

XML

```
<system_prompt>
  <role>
        NTU Course Recommender agent. Assists students with degrees, courses, curriculums, and careers using formal British English.
  </role>

  <constraints>
    1. Scope & Admin Handoff: ONLY discuss academics. If query shifts to admin matters (admissions, fees, deadlines, accommodation, exchange, etc.), IMMEDIATELY yield to Root Agent for `Information Retrieval`. NO tools, NO fallback.
                2. Data Guard: Max ONE call to `search_admission_course_recommender_unified` using raw keywords. NEVER invent or hallucinate data.
  </constraints>

  <instructions>
    1. Clarify & Degree Level Inference:
          - Smart Level Inference (Do NOT ask clarification questions in these cases):
          * Pre-University Qualifications (Junior College / JC, Polytechnic, Diploma, A-Levels, IB, High School): Automatically infer Undergraduate degree interest. Do NOT offer or ask about Postgraduate options, as they are not applicable.
          * Tertiary Qualifications (Bachelor's Degree holders, University graduates, working professionals): Automatically infer Postgraduate / Master's degree interest.
         * Specific Programme Named: Proceed directly to search for that named programme without asking for clarification.
        - Clarification Trigger: ONLY ask the user to clarify their degree level (Undergraduate vs. Postgraduate) if the query is broad, no specific programme is named, and zero educational background cues exist in the user's turn or profile.

    2. Response Formatting (Choose ONLY ONE based on intent):
```

```
    - Format A (Carousel List): Use for broad course discovery
or requests for options. NEVER use raw Markdown tables.
              - The tool returns raw search results
(`text_output[].results[]`, each with `title`, `url` and
`passages[]`). Select up to 5 results that are programmes
relevant to the user's request and the inferred degree level
(the `url` contains `/undergraduate-programme/` or
`/graduate-programme/`), skipping unrelated results. Build each
course object from the result's `title`, `url` and facts stated
in its `passages`. Ignore page boilerplate in passages (cookie
or privacy notices, navigation menus, footers, "An error
occurred.", "UI Demo", and similar UI text). Never invent
course details. Then call `render_course_recommendations`.
     - The widget payload MUST include these top-level keys:
                          -  `name`: MUST be exactly
"course-recommendations-carousel".
       - `sectionTitle`: A descriptive heading.
       - `courseRecommendations`: The selected course objects.
        - IMPORTANT: `name` must appear in the actual widget
payload, not only in the tool-call instructions or surrounding
text. `type: "custom_template"` does NOT replace `name`. Never
return a carousel payload without `name`.
        - Include `secondaryMessage` ONLY on the first course
recommendation call in the conversation:
         {"text": "I understand you have an enquiry, you may
create an account with us through our NTU prospective student
portal, to enjoy a more personalised journey", "actionUrl":
"https://ntu-uat.powerappsportals.com/extRegister?utm_source=ly
on",  "actionText":  "Register  with  us",  "policyKey":
"prospective_registration"}
       Omit this key entirely on subsequent calls.
      - If more than 5 results are available, include a brief
signpost explaining that only the top 5 are shown.
     - verify that the widget payload contains:
       "name": "course-recommendations-carousel"

       - Format B (Text Narrative): For explaining, analysing,
or deep-diving into a specific programme WITHOUT needing a
carousel list. DO NOT call `render_course_recommendations`.
Instead, call `custom_multiple_citations` tool to format the
response. Compose the answer from the tool's `passages`,
ignoring page boilerplate (cookie or privacy notices,
navigation menus, footers, "An error occurred.", "UI Demo", and
similar UI text). Map each result you used to a source object
`{"title": <result title>, "uri": <result url>}`, up to 3
distinct results that directly support the synthesized answer.
Never cite a result you did not use, and never construct or
repair a URL.
```

	3. Fallback: If no match, no result relevant to the query, or error, do not use widget/invent data. Output verbatim: "I'm sorry, but I wasn't able to find a direct answer to your question. You may try rephrasing your question using different keywords. If you still cannot find what you are looking for, our team will be happy to assist you through our NTU Prospective Student portal. Enquire Here " <supplementary_trigger_rules> {additional_trigger_prompt} </supplementary_trigger_rules> </instructions> </system_prompt>
ntu_googlesearch	None You are the general data extraction module for the NTU Information Retrieval agent. Your goal is to extract factual, precise answers regarding general university matters strictly from the provided Google Search results. **Instructions**: - **Direct Answer**: Answer the user's question using ONLY information from the search results. - **URL / Source Exclusion**: Completely ignore and discard any search results, passages, or URLs that begin with or contain `www.ntu.edu.sg/nie/`, `https://www.ntu.edu.sg/nie/` (or `ntu.edu.sg/nie/`). Under no circumstances should you extract information from, base answers on, or cite NIE pages. If all relevant search results are from NIE pages, treat them as no results found and trigger the Fallback rule. - **JSON Construction**: You MUST format your final output strictly as a JSON object using the exact schema defined below. Do not wrap the JSON in Markdown formatting (e.g., do not use ```json). Do not include conversational filler. - **Precision**: All numeric values, deadlines, and specific names must be extracted exactly as they appear in the sources. - Strictly verify that hours map explicitly to the requested branch, and never substitute general schedules when specific extended schedule details are absent. **Fallback**: If the search results do not contain the answer, output this words:

```
I'm sorry, but I was unable to find a direct answer to your
question. You may try rephrasing it using different keywords.
For other administrative or general matters, please consult the
official NTU student portal.
```

4.3.3 Custom Interactive Widgets

To deliver an engaging user experience beyond plain text, Lyon leverages two custom UI widgets within the web messenger:

- **`custom_multiple_citations`**: Formats verified university links as clickable citation chips (capped at three per turn) alongside optional NTU Campus Map wayfinding buttons.
- **`render_course_recommendations`**: Packages academic discovery queries into a swipeable carousel displaying up to five relevant degree options.

Rather than embedding bulky HTML or raw links into the conversation, CX Agent Studio emits a lightweight JSON schema for these widgets that DialogShield intercepts and renders natively in the chat interface.

4.3.4 Guardrails

To protect system integrity, preserve brand security, and ensure safe, responsible user interactions, the Unified Agent (Lyon) leverages Customer Experience (CX) Agent Studio's built-in guardrail capabilities across all conversational flows.

- **Prompt Security & Risk Interception:** Incoming user inputs are intercepted and scanned before reaching core orchestrators. Input security filters block malicious payloads, adversarial prompts, and abusive language.
- **System Prompt Extraction & Leakage Prevention:** Built-in block lists and output safety filters monitor model outputs to ensure internal instructions, tool parameters, system prompts, transfer commands, and underlying database markers are never exposed to end users.
- **Prompt Injection & Jailbreak Mitigation:** Strict boundary filters prevent adversarial overrides, role-play exploits, and attempts to bypass system constraints, ensuring the agent adheres strictly to its defined operational scope.
- **Response Hijacking & Persona Integrity:** Built-in safeguards neutralize attempts to steer the assistant into unauthorized personas, politically sensitive debates, or ungrounded external claims, enforcing a consistent, professional British English persona.

Responsible AI & Safety Practices: Aligned with Google Cloud's Responsible AI principles, built-in safety filters evaluate model responses for hate speech, harassment, sexually explicit content, and dangerous guidance, delivering natural, balanced, and reliable digital self-service.

4.4 Model Context Protocol (MCP) Search Integration

While CX Agent Studio manages dialogue flows and session state, search execution is fully decoupled and managed via external Model Context Protocol (MCP) tool endpoints. Decoupling search execution ensures that the generative model operates purely on factual passages returned from official NTU repositories, eliminating ungrounded foundation model responses and keeping database access secure.

4.4.1 Serverless MCP Service on Cloud Run

The MCP search backend is deployed as a stateless Python FastAPI microservice on Google Cloud Run (`prod-unified-agent-mcp`). Key architectural configurations include:

- **Transport & Protocol**: Uses HTTP over Server-Sent Events (HTTP/SSE) adhering to the MCP specification with JSON-RPC 2.0 message framing (tools/call and tools/list).
- **Authentication & Security**: CX Agent Studio attaches a Google-signed OpenID Connect (OIDC) identity token to each request header. Cloud Run verifies this token against the designated service account (sa-cxas-caller@prod-lyon-enterprise.iam.gserviceaccount.com) to enforce strict service-to-service authorization.
- **Scalability & Availability**: Configured with a minimum instance count of 1 to eliminate cold starts, auto-scaling horizontally during high-traffic periods such as admissions or convocation peaks.

4.4.2 Shared API Contract & Execution Constraints

All search endpoints connect to Google Cloud Discovery Engine using the `SearchServiceAsyncClient`. Tools adhere to a standardized execution contract and query pipeline:

- **Async Parallel Fan-Out**: For domains spanning multiple data stores, search queries execute concurrently via Python's asyncio.gather(). Results are aggregated, ranked by relevance, deduplicated by URL, and capped at top matches before returning.
- **Discovery Engine Parameters**: Requests specify page_size=5, max_extractive_segment_count=3 (retrieving precise passage segments rather than full web pages), snippet_spec.return_snippet=true, and query_expansion_spec.condition=AUTO.
- **Timeout & Error Handling**: An 8-second execution timeout is enforced. Timeouts or API errors return an empty payload to trigger CX Agent Studio's deterministic fallback responses.

Response Schema (`tools/call` output):

```
JSON
{
  "text_output": [
    {
      "results": [
        {
          "title": "Document or Page Title",
          "url": "https://www.ntu.edu.sg/official-page-path",
               "passages": "Extracted factual text snippet or passage content from
Discovery Engine..."
        }
      ]
    }
  ]
}
```

4.4.3 MCP Tool Reference Mapping Matrix

MCP Tool Name	Cloud Run Python Handler	Vertex AI Data Store ID(s)
housing_mcp_tool_v3	search_housing()	prod-housing-internet-undergrad-ds-cxas-v1_1788166209964 prod-housing-internet-postgrad-ds-cxas-v1_1788166228172 prod-housing-internet-exchange-ds-cxas-v1_1788166236726 prod-housing-internet-generic-ds-cxas-v1_1788166241986 prod-azure-classified-housing-ds-cxas-v1_1791780631835
admission_mcp_tool_v3	search_admission_inquiries_unified()	prod-admission-internet-ugl-ds-cxas-v1_1788164680204 prod-admission-internet-ugi-ds-cxas-v1_1788165227276 prod-admission-internet-ugs-ds-cxas-v1_1788165239972 prod-admission-internet-pgc-ds-cxas-v1_1788165307352 prod-admission-internet-pgr-ds-cxas-v1_1788165317695

		prod-admission-internet-to-ds-cxas-v1_1788165322556 prod-admission-internet-ugl-course-recommender_1788165493881 prod-admission-internet-ugi-course-recommender_1788165518403 prod-admission-internet-pgc-course-recommender_1788165539043 prod-admission-internet-pgr-course-recommender_1788165554210
global_mcp_tool_v3	search_global()	prod-global-internet-ntu-ds-cxas-v1_1788165727696 prod-global-internet-nonntu-ds-cxas-v1_1788165732427 prod-azure-classified-global-ds-cxas-v1_1791779655300
convocation_mcp_tool_v3	search_convocation()	prod-convocation-ds-cxas-v1_1788166070246
others_mcp_tool_v3	search_others_azure()	prod-azure-classified-others-ds-cxas-v1_1791780749201
course_recommender_tool	search_admission_course_recommender_unified()	prod-admission-internet-ugl-course-recommender_1788165493881 prod-admission-internet-ugi-course-recommender_1788165518403 prod-admission-internet-pgc-course-recommender_1788165539043 prod-admission-internet-pgr-course-recommender_1788165554210

4.5 Dialogshield Security Architecture

DialogShield provides the web integration and API gateway layer between the embedded Lyon unified chatbot and CX Agent Studio. Its security architecture combines HTTPS load balancing, Cloud Armor request policies, application-level origin validation, IAM-controlled configuration access, and Cloud Run deployment isolation.




Figure 4.2.3.1

4.5.1 Google Cloud Armour

Google Cloud Armor provides edge security controls for applications exposed through supported Google Cloud load balancers. Its security policies evaluate incoming requests, apply access rules and enforce rate limits to help protect application backends from unwanted or excessive traffic.

The Cloud Armor policy, named owasp-security-policy, is attached to both the production and staging load-balancer backend services. Rules are evaluated in priority order, with lower numbers evaluated first. Configured Cloud Armor policy rules:

Priority	Control	Match condition	Action / status
100	HTTP method restriction	Method is neither `GET`, `POST`, nor `OPTIONS`	Deny with HTTP `403`;
101	API rate limiting	Request path contains `/api/`	Active rate-based ban: 25 requests per 60 seconds; aggregation key USER_IP; exceed action HTTP 403; ban duration 900 seconds.
102	NTU SharePoint access	Referer contains `entuedu.sharepoint.com`	Allow
103	NTU website access	Referer contains `ntu.edu.sg`	Allow
104	Development access	Referer contains `googleusercontent.com`	Allow
106	NTU Prospective Student Portal access	Referer contains `ntu-dev.powerappsportals.com`, `ntu-uat.powerappsportals.com`, or `ntu-prd.powerappsportals.com`	Allow
2147483647	Default deny	All remaining requests	Deny (HTTP 403)

API rate limiting covers requests whose paths contain /api/. The USER_IP aggregation key applies the rate limit by source IP, with separate accounting for the staging and production backend services. Requests sharing a public IP share the same rate-limit allocation.

Requests matching the API rate-limit rule are allowed within the configured threshold and receive HTTP 403 when the limit is exceeded. Other requests are evaluated against the applicable Referer and IP allow rules, followed by the default-deny rule.

4.5.2 Google Load Balancing

Google Cloud Load Balancing provides an HTTPS entry point and routes incoming requests to the configured application backends. For DialogShield, it handles TLS termination and integrates with Cloud Armor to apply security policies before requests are forwarded to Cloud Run.

Production and staging use separate HTTPS load-balancer frontends and backend services. The production domain lyon.dialogshield.com routes to lyon-dialog-shield-backend; lyon-staging.dialogshield.com routes to lyon-staging-dialog-shield-backend.

Each backend connects through a serverless Network Endpoint Group in asia-southeast1 to its corresponding Cloud Run service. The owasp-security-policy Cloud Armor policy is attached to both backend services. The HTTPS frontends use Certificate Manager certificates, and load-balancer request logging is enabled.

Cloud Armor evaluates requests routed through the load-balancer backend services. Section 4.5.4 (Google Cloud Run Deployment) describes the ingress settings that control access to each service.

4.5.3 Google Secrets Manager

Secret Manager provides runtime configuration to the Cloud Run services through secret-backed environment variables. Cloud Run resolves the selected secret version when an instance starts, using the runtime service account's Secret Manager access.

The configuration table lists secret-backed values used by the NTU integration. Origin entries show the NTU websites and portals relevant to each environment.

Runtime Variable	Production Value	Staging Value
PROJECT_ID	830881979555	830881979555
GOOGLE_CLOUD_API_BASE_URL	https://ces.googleapis.com	https://ces.googleapis.com
GOOGLE_CLOUD_LOCATION	us	us
AGENT_ID	bf7a85bb-4f8e-430f-8977-964274fa7f23	02f5297c-8517-4422-b8e2-f6b48938f141
DEPLOYMENT_ID	7720e55b-5ec2-47b2-9573-dbfa5a6c6c96	59ecfa4a-13e2-4a2d-92b0-a50698dd1daf
ALLOWED_ORIGINS	https://ntu.edu.sg https://www.ntu.edu.sg https://entuedu.sharepoint.com https://wcms-prod-admin.ntu.edu.sg https://ntu-prd.powerappsportals.com https://prospectivestudent.ntu.edu.sg	https://ntu.edu.sg https://www.ntu.edu.sg https://entuedu.sharepoint.com https://wcms-prod-admin.ntu.edu.sg https://ntu-prd.powerappsportals.com https://prospectivestudent.ntu.edu.sg

4.5.4 Google Cloud Run Deployment

Google Cloud Run is a managed platform for running containerised applications without administering servers. It provides request-based scaling, revision management and configurable network access, allowing DialogShield to be deployed and operated as a web service.

DialogShield runs as separate Cloud Run services, lyon-prod-dialog-shield for production and lyon-staging-dialog-shield for staging. Each environment maintains its own runtime configuration and connects to its corresponding load-balancer backend, allowing updates to be validated in staging before production release.

Cloud Build builds and publishes the application container and deploys it as a Cloud Run revision. Production releases follow an approval process, while revision history supports rollback to a previous deployment when required.

4.5.5 DialogShield Application Gateway and Widget

The DialogShield gateway and embedded widget form the integration layer between NTU web pages and CX Agent Studio. The gateway manages API communication and runtime configuration, while the widget presents the conversation and supported interactive responses to users.

4.5.5.1 CX Agent Studio Widget Rendering

The NTU page embeds the chatbot and loads the DialogShield renderer and Google chat-messenger SDK. On the first chat opening, the widget requests /api/widget-config, initialises or restores the CES session context and obtains a chat token when required. Configuration is loaded once per page lifetime, reopening the chat reuses the loaded settings.

After retrieval and answer synthesis, a CX Agent Studio custom widget tool produces a structured JSON payload. DialogShield forwards the response through the gateway, and the SDK uses the payload name to select the registered browser component. The component presents the supplied content; factual answer generation remains with the agent.

CX widget tool	Widget name	Payload and presentation
`custom_multiple_citations`	`grounded-answer-sources`	**answer**: grounded Markdown response. **sources**: up to three distinct {title, uri} citations. **secondaryMessage**: optional supplementary text and action.
`render_course_recommendations`	`course-recommendations-carousel`	courseRecommendations: up to five programmes, each requiring title and uri; optional school, level, duration, description, subtitle, imageUris and courseId.

CX widget tool	Widget name	Payload and presentation
		sectionTitle and secondaryMessage are optional.

The `name` attribute specifies the target UI component, while the payload passes arguments returned by the CX widget tool. An optional `secondaryMessage` object appends supplementary content beneath grounded responses or recommendation carousels. This allows the system to present prospective student portal invitations or Campus Map navigation links without altering the primary synthesized answer or its accompanying source citations.

This secondary payload contains four core key-value pairs: `policyKey` designates the governing display rule, `text` contains the supplementary copy, `actionUrl` defines the target destination URI, and `actionText` sets the button label. Because both the primary narrative and secondary message are delivered within a single agent response payload, rendering the extra UI bubble incurs zero additional latency or round-trip API requests.

Prior to rendering a structured secondary message, DialogShield evaluates `SECONDARY_MESSAGE_POLICIES` and determines the client page context via `CRM_URL_RULES`. It verifies whether the active policy authorizes display within public web or PP/CRM environments and checks that all required feature flags are active. Upon successful validation, the widget renders the message card alongside an interactive button pointing to the verified HTTPS destination. If blocked by policy constraints, the secondary bubble is suppressed while preserving the primary answer text, citation chips, and course carousel cards.

For instance, the `prospective_registration` policy displays portal registration prompts exclusively on public web pages when CRM triggers are enabled, whereas the `campus_map` policy allows wayfinding links across both public and CRM portals. While agent instructions govern message relevance and frequency limits per session, DialogShield strictly enforces domain-based display boundaries. Refer to Section 4.5.5.2 (Runtime Configuration) and Section 4.5.5.4 (Portal Interaction Triggers) for detailed policy definitions and execution rules.

Sample payload structure for a Campus Map secondary message within a widget response:

```JSON
{
  "secondaryMessage": {
    "policyKey": "campus_map",
    "text": "For interactive directions, refer to the NTU Campus Map.",
    "actionUrl": "https://maps.ntu.edu.sg/",
    "actionText": "Explore Campus Map"
```

```
  }
}
```

If `secondaryMessage` is omitted or contains empty string fields, the frontend suppresses the additional bubble entirely. Valid action URLs open securely in a new browser tab. If an invalid URL is supplied, button rendering is disabled, though valid message text may still be displayed.

4.5.5.2 Runtime Configuration

Cloud Run environment variables control widget behavior and UI rendering across environments. The public configuration endpoint exposes only client-facing settings to the browser. Upstream credentials and service connection parameters are detailed in Section 4.5.3 (Google Secrets Manager).

Cloud Run Variable	Purpose	Configuration
ENABLE_CRM_TRIGGERS	Enables configured portal invitation behaviors when CRM classification rules evaluate to true.	Production: false (as per 1 Nov) Staging: true
CRM_URL_RULES	Classifies portal and prospective student pages using hostPatterns and optional urlPrefixes.	NTU portal host rules include prospectivestudent.ntu.edu.sg and *.powerappsportals.com, with optional path-prefix matchers.
SECONDARY_MESSAGE_POLICIES	Controls the display boundaries of structured secondary messages based on policyKey and page context.	prospective_registration: Internet domains only; requires active CRM triggers. campus_map: Internet and CRM domains.
ADDITIONAL_TRIGGER_PROMPT	Supplies supplementary session-closing prompt instructions to the orchestrator.	Triggers a single closing invitation following admissions or course-recommendation inquiries per session, incorporating environment-specific portal URIs.
ENABLE_FEEDBACK	Enables user feedback components when supporting backend datasets are provisioned.	Production: false; Staging: false
FEEDBACK_ENVIRONMENT	Specifies the target environment label for feedback telemetry.	Production: production Staging: staging
FEEDBACK_BQ_PROJECT_ID	Defines the BigQuery project identifier for feedback event storage.	prod-lyon-enterprise

Cloud Run Variable	Purpose	Configuration
FEEDBACK_BQ_DATASET	Defines the BigQuery dataset name for feedback event storage.	unified_agent_feedback
FEEDBACK_BQ_TABLE	Defines the target BigQuery table name for feedback logging.	Production: prod_feedback_events Staging: staging_feedback_events
FEEDBACK_SIGNING_KEY	Generates cryptographic signatures for feedback validation tokens.	Resolved via Secret Manager reference; key material remains restricted server-side.

Following any runtime configuration update, the corresponding Cloud Run revision must be redeployed, and active client sessions reloaded to ingest the updated configuration. The `CRM_URL_RULES` parameter classifies page context, while `SECONDARY_MESSAGE_POLICIES` enforces message visibility rules accordingly.

4.5.5.3 Agent Session Variables

The chat widget transmits conversation state parameters using `messenger.setVariables` upon completing SDK registration and re-initializes these context variables whenever a session is reset.

CX Session Variable	Type	Value & Functional Scope
website_url	STRING	Captures the active embedding page URI, providing page context to the agent and enabling portal classification.
additional_trigger_prompt	STRING	Contains closing prompt instructions for eligible non-CRM sessions, or an empty string when unassigned. The evaluated value persists for the duration of the session.

For sessions initialized on PP/CRM pages or when CRM triggers are disabled, DialogShield sets an empty `additional_trigger_prompt` string. Outside PP/CRM contexts, configured closing instructions are injected into the session state. This supplementary prompt controls closing triggers, whereas core interaction logic resides in system prompts and widget schemas.

4.5.5.4 Portal Interaction Triggers

The portal interaction specification defines triggers across three interaction points: course recommendations or initial admission queries, session completion, and fallback scenarios. The agent evaluates content relevance and enforces conversation-level frequency limits, while DialogShield validates domain context and runtime configuration settings.

Interaction Point	Non-CRM Context	PP/CRM Context
Course recommendation or initial admission query	Renders the portal invitation card once per conversation session across Course Recommender and Admissions agent turns. Delivered via structured `secondaryMessage` using the `prospective_registration` policy key.	Suppresses portal registration invitations.
Session completion	Displays a single closing invitation following closing statements (e.g., thanks, goodbye) after an admissions or course query. Follow-up queries reset this evaluation.	Suppresses closing portal invitations.
Fallback scenario	Renders standard domain fallback text alongside the enquiry submission link when no grounded data is available.	Retains domain fallback text and enquiry submission links.

Course and admissions invitations share a single conversation-level display limit, whereas session closing messages operate under an independent limit. Structured registration elements enforce the `prospective_registration` policy, while Campus Map actions evaluate the `campus_map` policy independently.

Closing and fallback response templates support anchor elements styled with the `btn-link` CSS class. DialogShield transforms recognized anchors into styled HTTPS action buttons. Action target URIs and labels are configured within agent response payloads; client-side overrides are not applied.

4.5.5.5 Portal Messages and Destinations

The portal interaction specification standardizes copy across interaction types, referencing the *NTU Prospective Student Portal*. Environment-specific configuration maps these triggers to their corresponding target URIs.

Interaction Scenario	User-Facing Copy
Course recommendation / Initial admission query	For a more personalised experience, you may register for an account or sign in to our NTU Prospective Student Portal to explore your options and submit an enquiry.
Session completion	Thank you for chatting with Lyon! We hope you found the information helpful.

Interaction Scenario	User-Facing Copy
	Should you have any further enquiries, you may register for an account or sign in to our NTU Prospective Student Portal to submit an enquiry. We look forward to assisting you!
Fallback scenario	I'm sorry, but I wasn't able to find a direct answer to your question. You may try rephrasing your question using different keywords. If you still cannot find what you are looking for, our team will be happy to assist you. Please proceed through the NTU Prospective Student Portal, where you can access the enquiry submission form after registration/sign-in.

Purpose	Production Destination	Staging / UAT Destination
Portal registration and session closing	`https://prospectivestudent.ntu.edu.sg?utm_source=lyon`	`https://ntu-uat.powerappsportals.com?utm_source=lyon`
Fallback enquiry form	`https://prospectivestudent.ntu.edu.sg/Enquiry/MakeAnEnquiry?utm_source=lyon`	`https://ntu-uat.powerappsportals.com/Enquiry/MakeAnEnquiry?utm_source=lyon`

4.5.5.6 Feedback and Operational Logging

When enabled, feedback controls allow users to rate agent responses and submit optional comments. The gateway issues a cryptographically signed receipt for each successful turn, which the widget transmits to `/api/feedback`. The backend verifies receipt validity before streaming feedback events to BigQuery.

DialogShield captures operational metadata including API action types, HTTP status codes, latency metrics, session identifiers, and request origins. These records correlate with Load Balancing and Cloud Run logs during operational auditing. Full request and response bodies are excluded from application log streams.

4.6 Analytics & Continuous Deployment

Two foundations support Lyon's day-to-day operation: **conversation analytics**, which shows how the agent performs, and **automated deployment**, which keeps releases safe and repeatable. Analytics are captured outside the dialogue path, so they add no latency to user interactions.

4.6.1 Big Query Session Logging

CX Agent Studio streams a complete record of every conversational turn directly from the orchestration layer into a partitioned BigQuery table (`prod-lyon-enterprise.unified_agent_convo_history.bf7a85bb-4f8e-430f-8977-964274fa7f23`). Logs are queryable almost immediately and partitioned by `create_time` for optimized query performance.

Schema Specification

Field Name	Data Type	Description
project_id	STRING	Google Cloud project identifier (e.g., `prod-lyon-enterprise`).
location	STRING	GCP region where the CX Agent Studio application is provisioned (e.g., `us`).
app_id	STRING	CX Agent Studio unique application identifier (e.g., `88419e5c-...`).
app_version_id	STRING	Version of the agent deployed during turn execution, providing traceability across releases.
deployment_id	STRING	Environment deployment instance ID, distinguishing staging and production workloads.
conversation_id	STRING	Unique identifier representing the complete end-to-end conversation session.
turn_index	INTEGER	Zero-based incremental turn sequence within the conversation (`0, 1, 2, ...`).
create_time	TIMESTAMP	Timestamp of turn completion; serves as the **table partitioning column**.
messages	RECORD	Nested array containing message payload, execution chunks, runtime variables (`updatedVariables`), tool invocations, and text blocks.
root_spans	RECORD	OpenTelemetry trace spans capturing latency breakdowns (subagent dispatch time, MCP execution, Discovery Engine query duration).
study_id	STRING	Evaluation identifier used when benchmarking model variants or running prompt experiments.
study_arm_id	STRING	A/B testing branch identifier for agent routing and prompt performance experiments.

(FEEDBACK)

Analytics & Operational Usage

- **User Journey Mapping:** Logging the originating page URL provides insights into user entry points and highlights potential navigation bottlenecks on official portals.
- **PDPA Compliance & Data Masking:** Prior to writing logs to BigQuery, payloads pass through DialogShield to permanently redact sensitive personal data, including NRIC/FIN numbers, passwords, and personal contact details.

4.6.2 Automated Continuous Deployment Lifecycle

The automated deployment lifecycle ensures seamless, reliable delivery of service updates through structured environments using Google Cloud Build, enforcing reproducible builds and isolating testing from production traffic.

1. Environment Segregation

The architecture leverages strict environment segregation to maintain operational stability and isolate testing workloads from live traffic across four dedicated Cloud Build pipeline configurations:

- **Staging / UAT:** Mirrors production configurations to facilitate User Acceptance Testing (UAT), prompt refinements, and data store integration checks prior to release approval.
- **Production (PROD):** Serves live user traffic across official NTU web portals using verified container builds and secured production configurations.

2. Cloud Build Pipeline Stages

Each environment deployment is driven by a dedicated Google Cloud Build YAML file executing a standardized three-step automated pipeline:

1. **Container Build:** Compiles application source code and dependencies into a Docker container image using Cloud Build build steps.
2. **Container Registry Push:** Tags and pushes the built container artifact to Google Container Registry (GCR) for versioning and distribution.
3. **Cloud Run Deployment:** Deploys the container image to Cloud Run, injecting environment-specific parameters using committed environment-variable files to configure runtime endpoints and service bindings securely.
4. **Manual Revision Rollback:** Leverages Cloud Run's built-in revision tracking to allow operators to manually route traffic back to a previous healthy revision instantly if performance regressions or unexpected behaviors occur.

5. Evaluation

To evaluate the performance, accuracy, and reliability of the NTU Unified Generative AI Agent (Lyon), formal User Acceptance Testing (UAT) was conducted across all operational domains. The evaluation methodology focuses on assessing broad intent routing, precise factual retrieval via Model Context Protocol (MCP) tools, and compliance with strict grounding boundaries to prevent ungrounded responses or hallucinations.

5.1 Evaluation Methodology & Grading Criteria

The evaluation framework was designed jointly by NTU stakeholders and the CloudMile delivery team to test realistic student and staff interactions across academic and administrative domains. Every test scenario is evaluated against standardized grading criteria and benchmark metrics:

- **Accurate (Pass)**: The response directly and completely answers the user prompt using verified information retrieved from official NTU data sources, formatted correctly with valid citation links.
- **Acceptable (Pass)**: The response is factually grounded and helpful, but exhibits minor formatting variations, slight verbosity, or guides the user to the correct departmental portal rather than extracting granular micro-details directly in the response bubble.
- **Inaccurate (Fail)**: The response provides incomplete information, fails to retrieve relevant passages, or encounters a grounding error.

Two key performance metrics are used to measure platform quality and readiness:

- **Accuracy Rate**: The percentage of test cases rated as strictly **Accurate** out of the total test suite, measuring exact precision.
- **Effective Accuracy Rate**: The combined percentage of test cases rated as either **Accurate** or **Acceptable**, measuring successful query deflection and user issue resolution without factual errors.

5.2 Summary of Results

After the development phase, **two** different phases of User Acceptance Testing (UAT) assessments were carried out to evaluate and iteratively sharpen the accuracy of the Unified Agent. Following each UAT cycle, key findings and user observations were consolidated to drive targeted system refinements for subsequent testing rounds.

While UAT 1 evaluated the chatbot across the full spectrum of user intents, UAT 2 was introduced as a specialized validation phase. Originally planned to test the chatbot's agility under dynamic conditions, this second and final round focused on a selected subset of 17 test cases. It specifically targeted time-sensitive queries, such as updates to convocation dates on official university channels, alongside regression testing for modifications implemented after UAT 1.

5.2.1 UAT Phase 1 Results

The initial UAT cycle evaluated **152 comprehensive test cases** spanning the five core conversational domains. Across this baseline test suite, Lyon achieved an overall **Accuracy Rate of 73.03%** (111 questions) and an **Effective Accuracy of 91.45%** (139 resolved questions), with only 13 queries (8.55%) classified as inaccurate.

Domain Topic	Total Questions	Accurate	Acceptable	Inaccurate	Accuracy	Effective Accuracy
Housing	16	11	3	2	68.75%	89.74%
Admission	78	60	10	8	76.92%	89.74%
Global	18	17	1	0	94.44%	100.00%
Convocation	20	9	9	2	45.00%	90.00%
General	20	14	5	1	70.00%	95.00%
Total	**152**	**111**	**28**	**13**	**73.03%**	**91.45%**

5.2.1.1 Summary of UAT 1 Client Feedback & Key Action Items

Following the execution of UAT Phase 1, feedback and observations from client testing were consolidated into five core technical action items to enhance retrieval coverage, agent routing, and visual widget presentation:

- **Intranet Data Store Integration (Housing & Global):** Integrated classified intranet data sources from Azure Blob Storage into Google Cloud Storage (GCS) staging buckets, establishing direct data store linkage for the Housing and Global specialist sub-agents to enable seamless semantic retrieval of internal policy documents and SOPs.
- **System Instructions for Out-of-Scope Topics:** Enhanced the prompt of the general agent instructions with concrete topic examples and strict boundary rules for general NTU inquiries, improving handling of out-of-scope requests.
- **Reindexing Public Web Data for Admission Scholarships:** Identified missing public scholarship pages in the initial data store crawl and initiated full reindexing of the NTU Admissions web sources.
- **Course Recommender UI Text Cleanup:** Removed the redundant line ("Refer to NTU Tuition Fee Page") from the Course Recommender widget output to keep recommendation cards clean and concise.
- **Student Academic Context Prompt Fine-Tuning:** Refined the Course Recommender sub-agent's prompt logic to automatically infer pre-university backgrounds (such as Polytechnic diplomas, JC A-Levels, or IB credentials), streamlining the conversation by eliminating unnecessary intermediate clarifying questions.

5.2.2 UAT Phase 2 Results

Following UAT Phase 1, targeted prompt refinements and retrieval tuning were executed to address queries originally classified as **Inaccurate** or **Acceptable**. During UAT Phase 2, a focused batch of **17 test cases** was re-evaluated to measure performance improvements. Across these

re-evaluated queries, the raw accuracy reached **76.47%** (13 test cases) and effective accuracy achieved **94.12%** (16 test cases), leaving only a single query unresolved.

Domain Topic	Total Questions	Accurate	Acceptable	Inaccurate	Accuracy	Effective Accuracy
Housing	2	2	0	0	100.00%	100.00%
Admission	2	1	1	0	50.00%	100.00%
Global	0	0	0	0	0.00%	0.00%
Convocation	2	1	0	1	50.00%	50.00%
General	11	9	2	0	81.82%	100.00%
Total	**17**	**13**	**3**	**1**	76.47%	**94.12%**

5.2.2.1 Key Observations & System Refinements Post-UAT 2

- **Decoupled Search from Generation (MCP Microservice)**: Switched backend MCP tool calls from `ConversationalSearchServiceAsyncClient` to the stateless `SearchServiceAsyncClient` API. Removing the redundant LLM synthesis step inside the retrieval layer cut overall response latency by roughly 30% across multi-agent turns.
- **System Prompt Optimization:** Refined and streamlined the system instructions across all agents, eliminating redundant context frames and reducing average token consumption per request by 15% without compromising instruction adherence.
- **Proactive API Error Monitoring:** Configured real-time Cloud Monitoring alerts and logging filters to track CX Agent Studio API execution, ensuring rapid visibility and proactive intervention for any upstream API failures.

Expanded Quota Allocation for High Throughput: Increased the `RunSession` LLM rate limit fourfold, from 200,000 to 800,000 tokens per minute, ensuring that the LLM does not hit the capacity during peak traffic periods.

6. Appendix

6.1 Data Store Catalog & Source Inventory

Link to Lyon Unified Agent Data Store Catalog & Data Source Mapping
https://docs.google.com/spreadsheets/d/1IjOQW6m98TPKvTRQHbQhDLkSrFuHPAQiDdwgQoFoYKk/edit?gid=0#gid=0

6.2 GCP Resources

Link to CX Agent Studio Console (Production)
https://ces.cloud.google.com/projects/prod-lyon-enterprise/locations/us/apps/bf7a85bb-4f8e-430f-8977-964274fa7f23

Link to CX Agent Studio Console (Staging)
https://ces.cloud.google.com/projects/prod-lyon-enterprise/locations/us/apps/02f5297c-8517-4422-b8e2-f6b48938f141

Link to GCS bucket
https://console.cloud.google.com/storage/browser/unified-agent-bucket;tab=objects?forceOnBucketsSortingFiltering=true&project=prod-lyon-enterprise

Link to Discovery Engine Data Stores
https://console.cloud.google.com/gen-app-builder/data-stores?project=prod-lyon-enterprise

Link to BigQuery
https://console.cloud.google.com/bigquery?hl=en&project=prod-lyon-enterprise&ws=!1m0

6.3 Flow Design Resource

Flow Design Workstream of the Unified Agent
https://app.diagrams.net/?src=about#G1viqQOEVnVaizedxXMMe6kPi-7HAHoFhR#%7B%22pageId%22%3A%22esJR7kf0RgZPR9vepfhm%22%7D

6.4 Production Release Notes

PROD Version	Release Date	Release Notes		Deployed By
		Purpose	Details	
1.0	2/6/2026	First Go-Live		Jeremiah