

CPSC354_FA22_Project

November 29, 2022

```
[1]: # code, run by pressing "run" button to the left of this comment

# import necessary packages
from plotnine import *
import pandas as pd
import warnings
from sklearn.linear_model import LinearRegression, LogisticRegression, Ridge, Lasso
from sklearn.linear_model import RidgeCV, LassoCV
from sklearn.metrics import r2_score, mean_squared_error, mean_absolute_error
from sklearn.preprocessing import StandardScaler
from sklearn.model_selection import train_test_split # simple TT split cv
import numpy as np
from sklearn.neighbors import NearestNeighbors

from sklearn.cluster import AgglomerativeClustering

from sklearn.cluster import DBSCAN
from sklearn.cluster import KMeans
from sklearn.mixture import GaussianMixture

from sklearn.metrics import silhouette_score

# make sure you have these to make dendrograms!-----
import scipy.cluster.hierarchy as sch
from matplotlib import pyplot as plt
#-----

warnings.filterwarnings('ignore')
%precision %.7g
%matplotlib inline
```

```
[2]: # code, run by pressing "run" button to the left of this comment

# import data and check for missing rows
```

```
data = pd.read_csv("https://raw.githubusercontent.com/MNGSunday/
↳PublicData_for_CPSC354/main/LanguageRepositories_Nov2022.csv",
↳encoding='windows-1254')
print("Missing data per column: ")
print(data.isna().sum())
print("Original data frame size: ", len(data), " rows")
```

```
Missing data per column:
Repository Language      0
Active Repositories      0
Total Pushes             0
Pushes Per Repository    0
New Forks Per Repository 0
Opened Issues Per Repository
New Watchers Per Repository
Appeared In Year         0
dtype: int64
Original data frame size: 30 rows
```

1 Q1.

(Linear Regression) When predicting when the year a particular Programming Language was released, which predictors (Active Repositories, Total Pushes, Total Pushes, Pushes Per Repository, New Forks Per Repository, Opened Issues Per Repository, and New Watchers Per Repository) improves the accuracy of the model's prediction when excluded from the model? What does this suggest about the nature of the Programming Languages used in GitHub repositories?

```
[3]: # code, run by pressing "run" button to the left of this comment

# Preview of the first five lines of the dataset
data.head()
```

```
[3]:  Repository Language  Active Repositories  Total Pushes  \
0      JavaScript      323938      3461415
1           Java      222852      2323315
2         Python      164852      1654226
3           CSS      164585      1810013
4           PHP      138771      1391467

      Pushes Per Repository  New Forks Per Repository  \
0           10.69           3.87
1           10.43           3.48
2           10.03           2.87
3           11.00           4.91
4           10.03           2.78
```

	Opened Issues Per Repository	New Watchers Per Repository	Appeared In Year
0	6.10	9.66	1995
1	6.67	6.24	1995
2	6.32	5.72	1991
3	5.24	9.33	1996
4	5.87	4.76	1995

```
[4]: # code, run by pressing "run" button to the left of this comment

# Linear Regression model containing all of the predictor variables
predictors_all = ["Active Repositories", "Total Pushes", "Pushes Per Repository",
                  "New Forks Per Repository", "Opened Issues Per Repository",
                  "New Watchers Per Repository"]

outcome = data[["Appeared In Year"]]

# Randomly split the data to use 80% of the data for training and 20% for testing for model validation
x_train, x_test, y_train, y_test = train_test_split(data[predictors_all], outcome,
                                                    test_size= 0.2,
                                                    random_state = 40)

# Z-score predictor variables for both training and testing data
z = StandardScaler()
x_train[predictors_all] = z.fit_transform(x_train[predictors_all])
x_test[predictors_all] = z.transform(x_test[predictors_all])

# Linear Regression Model for model containing all predictor variables
lr_all = LinearRegression()
lr_all.fit(x_train[predictors_all], y_train)

# Print out Mean Squared Error and R2-Score for Testing and Training data
print("For the Linear Regression Model containing all variables...")
print("Training data R2 Score:", r2_score(y_train, lr_all.predict(x_train[predictors_all])))
print("Training data Mean Squared Error Score:", mean_squared_error(y_train, lr_all.predict(x_train[predictors_all])))

print("\n")

print("Testing data R2 Score:", r2_score(y_test, lr_all.predict(x_test[predictors_all])))
print("Training data Mean Squared Error Score: ", mean_squared_error(y_test, lr_all.predict(x_test[predictors_all])))
```

For the Linear Regression Model containing all variables...
Training data R2 Score: 0.16331385155948508
Training data Mean Squared Error Score: 105.21183058627594

Testing data R2 Score: 0.4232737382895424
Training data Mean Squared Error Score: 80.82177750914607

```
[5]: # code, run by pressing "run" button to the left of this comment

# Linear Regression model excluding Number of Active Repositories
exclude_active = ["Total Pushes", "Pushes Per Repository",
                  "New Forks Per Repository", "Opened Issues Per Repository",
                  "New Watchers Per Repository"]

# Linear Regression Model for model excluding Number of Active Repositories
lr_no_active = LinearRegression()
lr_no_active.fit(x_train[exclude_active], y_train)

# Print out Mean Squared Error and R2-Score for Testing and Training data
print("For the Linear Regression Model excluding Number of Active Repositories..")
print("Training data R2 Score:", r2_score(y_train, lr_no_active.
    ↪predict(x_train[exclude_active])))
print("Training data Mean Squared Error Score:", mean_squared_error(y_train,
    ↪lr_no_active.predict(x_train[exclude_active])))

print("\n")

print("Testing data R2 Score:", r2_score(y_test, lr_no_active.
    ↪predict(x_test[exclude_active])))
print("Training data Mean Squared Error Score: ", mean_squared_error(y_test,
    ↪lr_no_active.predict(x_test[exclude_active])))
```

For the Linear Regression Model excluding Number of Active Repositories...
Training data R2 Score: 0.14928609973685336
Training data Mean Squared Error Score: 106.97579602423606

Testing data R2 Score: 0.42825473624864563
Training data Mean Squared Error Score: 80.12374598959953

```
[6]: # code, run by pressing "run" button to the left of this comment

# Linear Regression model excluding Number of Total Pushes
exclude_push_total = ["Active Repositories", "Pushes Per Repository",
                     "New Forks Per Repository", "Opened Issues Per Repository",
```

```

        "New Watchers Per Repository"]

# Linear Regression Model for model excluding Number of Total Pushes
lr_no_push_total = LinearRegression()
lr_no_push_total.fit(x_train[exclude_push_total], y_train)

# Print out Mean Squared Error and R2-Score for Testing and Training data
print("For the Linear Regression Model excluding Number of Total Pushes...")
print("Training data R2 Score:", r2_score(y_train, lr_no_push_total.
    ↪predict(x_train[exclude_push_total])))
print("Training data Mean Squared Error Score:", mean_squared_error(y_train,
    ↪lr_no_push_total.predict(x_train[exclude_push_total])))

print("\n")

print("Testing data R2 Score:", r2_score(y_test, lr_no_push_total.
    ↪predict(x_test[exclude_push_total])))
print("Training data Mean Squared Error Score: ", mean_squared_error(y_test,
    ↪lr_no_push_total.predict(x_test[exclude_push_total])))

```

For the Linear Regression Model excluding Number of Total Pushes...

Training data R2 Score: 0.15172857789930394

Training data Mean Squared Error Score: 106.66865863572139

Testing data R2 Score: 0.4230374299603413

Training data Mean Squared Error Score: 80.8548934958355

```

[7]: # code, run by pressing "run" button to the left of this comment

# Linear Regression model excluding Number of Pushes per Repository
exclude_repository_pushes = ["Active Repositories", "Total Pushes",
    "New Forks Per Repository", "Opened Issues Per Repository",
    "New Watchers Per Repository"]

# Linear Regression Model for model excluding Number of Pushes per Repository
lr_no_repository_pushes = LinearRegression()
lr_no_repository_pushes.fit(x_train[exclude_repository_pushes], y_train)

# Print out Mean Squared Error and R2-Score for Testing and Training data
print("For the Linear Regression Model excluding Number of Pushes Per
    ↪Repository...")
print("Training data R2 Score:", r2_score(y_train, lr_no_repository_pushes.
    ↪predict(x_train[exclude_repository_pushes])))
print("Training data Mean Squared Error Score:", mean_squared_error(y_train,
    ↪lr_no_repository_pushes.predict(x_train[exclude_repository_pushes])))

```

```

print("\n")

print("Testing data R2 Score:", r2_score(y_test, lr_no_repository_pushes.
    ↪predict(x_test[exclude_repository_pushes])))
print("Training data Mean Squared Error Score: ", mean_squared_error(y_test,
    ↪lr_no_repository_pushes.predict(x_test[exclude_repository_pushes])))

```

For the Linear Regression Model excluding Number of Pushes Per Repository...

Training data R2 Score: 0.15398523175241896

Training data Mean Squared Error Score: 106.384888331494

Testing data R2 Score: 0.3429048737808713

Training data Mean Squared Error Score: 92.0845808826529

```

[8]: # code, run by pressing "run" button to the left of this comment

# Linear Regression model excluding Number of Forks Per Repository
exclude_forks = ["Active Repositories", "Total Pushes", "Pushes Per Repository",
    ↪"Opened Issues Per Repository", "New Watchers Per Repository"]

# Linear Regression Model for model excluding Number of Forks Per Repository
lr_no_forks = LinearRegression()
lr_no_forks.fit(x_train[exclude_forks], y_train)

# Print out Mean Squared Error and R2-Score for Testing and Training data
print("For the Linear Regression Model excluding Number of Forks Per Repository.
    ↪..")
print("Training data R2 Score:", r2_score(y_train, lr_no_forks.
    ↪predict(x_train[exclude_forks])))
print("Training data Mean Squared Error Score:", mean_squared_error(y_train,
    ↪lr_no_forks.predict(x_train[exclude_forks])))

print("\n")

print("Testing data R2 Score:", r2_score(y_test, lr_no_forks.
    ↪predict(x_test[exclude_forks])))
print("Training data Mean Squared Error Score: ", mean_squared_error(y_test,
    ↪lr_no_forks.predict(x_test[exclude_forks])))

```

For the Linear Regression Model excluding Number of Forks Per Repository...

Training data R2 Score: 0.1632898597934973

Training data Mean Squared Error Score: 105.21484750919653

Testing data R2 Score: 0.4237568659311758

Training data Mean Squared Error Score: 80.75407253825607

```
[9]: # code, run by pressing "run" button to the left of this comment

# Linear Regression model excluding Number of Opened Issues Per Repository
exclude_issues = ["Active Repositories", "Total Pushes", "Pushes Per Repository",
                  "New Forks Per Repository", "New Watchers Per Repository"]

# Linear Regression Model for model excluding Number of Opened Issues Per Repository
lr_no_issues = LinearRegression()
lr_no_issues.fit(x_train[exclude_issues], y_train)

# Print out Mean Squared Error and R2-Score for Testing and Training data
print("For the Linear Regression Model excluding Number of Opened Issues Per Repository...")
print("Training data R2 Score:", r2_score(y_train, lr_no_issues.predict(x_train[exclude_issues])))
print("Training data Mean Squared Error Score:", mean_squared_error(y_train, lr_no_issues.predict(x_train[exclude_issues])))

print("\n")

print("Testing data R2 Score:", r2_score(y_test, lr_no_issues.predict(x_test[exclude_issues])))
print("Training data Mean Squared Error Score: ", mean_squared_error(y_test, lr_no_issues.predict(x_test[exclude_issues])))
```

For the Linear Regression Model excluding Number of Opened Issues Per Repository...

Training data R2 Score: 0.16289020662991227

Training data Mean Squared Error Score: 105.26510320067506

Testing data R2 Score: 0.43602910973274733

Training data Mean Squared Error Score: 79.03425392773026

```
[10]: # code, run by pressing "run" button to the left of this comment

# Linear Regression model excluding Number of New Watchers Per Repository
exclude_watchers = ["Active Repositories", "Total Pushes", "Pushes Per Repository",
                   "New Forks Per Repository", "Opened Issues Per Repository"]

# Linear Regression Model for model excluding Number of New Watchers Per Repository
lr_no_watchers = LinearRegression()
lr_no_watchers.fit(x_train[exclude_watchers], y_train)
```

```

# Print out Mean Squared Error and R2-Score for Testing and Training data
print("For the Linear Regression Model excluding Number of New Watchers Per_
↪Repository...")
print("Training data R2 Score:", r2_score(y_train, lr_no_watchers.
↪predict(x_train[exclude_watchers])))
print("Training data Mean Squared Error Score:", mean_squared_error(y_train,
↪lr_no_watchers.predict(x_train[exclude_watchers])))

print("\n")

print("Testing data R2 Score:", r2_score(y_test, lr_no_watchers.
↪predict(x_test[exclude_watchers])))
print("Training data Mean Squared Error Score: ", mean_squared_error(y_test,
↪lr_no_watchers.predict(x_test[exclude_watchers])))

```

For the Linear Regression Model excluding Number of New Watchers Per Repository...

Training data R2 Score: 0.07326075328163195

Training data Mean Squared Error Score: 116.53585135253145

Testing data R2 Score: 0.15754222250650884

Training data Mean Squared Error Score: 118.06109687374065

2 Q2.

(Clustering) When considering the number of Opened Issues Per Repository and the number of New Watchers Per Repository, what clusters emerge? What can be said about those clusters? What percentage of those clusters contain Programming Languages that were released prior to 1993?

```

[11]: # code, run by pressing "run" button to the left of this comment

# Copy of the Programming Languages Dataset specifically for this clustering_
↪section

cluster_data = pd.read_csv("https://raw.githubusercontent.com/MNGSunday/
↪PublicData_for_CPSC354/main/LanguageRepositories_Nov2022.csv",
↪encoding='windows-1254')

```

```

[12]: # code, run by pressing "run" button to the left of this comment

# Establish and Z-Score variables for copy of the dataset for the clustering_
↪section

important_variables = ["Repository Language", "Opened Issues Per Repository",

```



```

        "New Watchers Per Repository", "Appeared In Year"]
cluster_variables = ["Opened Issues Per Repository", "New Watchers Per_
↪Repository"]

zCluster = cluster_data[important_variables]

# Z-Score the variables used for the Clustering Model
cluster_z = StandardScaler()
cluster_z.fit(zCluster[cluster_variables])
zCluster[cluster_variables] = cluster_z.transform(zCluster[cluster_variables])


```

```

[13]: # code, run by pressing "run" button to the left of this comment

# General Scatterplot Diagram for Opened Issues Per Repository vs
# New Watchers Per Repository without Clustering
(ggplot(zCluster, aes(x = "Opened Issues Per Repository",
        y = "New Watchers Per Repository")) + geom_point() +
    theme_minimal() + theme(panel_grid_major = element_blank()) +
    labs(x = "Number of Opened Issues Per Repository", y = "Number of Watchers Per_
↪Repository",
        title = "Opened Issues vs New Watchers Per Repository"))

```



[13]: <ggplot: (8793432854977)>

In this section, the assumptions of different clustering algorithms is discussed and is used to assess which clustering algorithms would work the best and the worst with the above scatterplots.

The **KMeans** algorithm is a rather simple clustering method that attempts to find K centroids in the data, where K is a number either decided by the user or randomly generated. In turn, the algorithm attempts to run until the points assigned to each cluster do not change or the location of the centroid in each cluster does not significantly change. **KMeans** also assumes that the variance of each predictor in each cluster is consistent, which would mean that the **KMeans** algorithm would be most effective on spherical-shaped clusters of data, which does not appear to be very present in the above scatterplots. Because of this, **KMeans** would likely not be a good choice of clustering algorithm for this data.

The **Gaussian Mixture Models (EM)** model, while similar to the **KMeans** model, assumes that there are multiple normal distributions within the data, where such distributions are used to determine the clusters in the data. Unlike **KMeans**, **EM** assumes that the variance of each predictor in the cluster is different, meaning that the **EM** model would be most effective for elliptical or spherical shaped clusters of data. While this can be effective for the above scatterplots, **EM** is susceptible to including "noise" data points in its clusters, which can potentially throw off the calculation of each cluster in the data. While a better option than **KMeans**, **EM** might not be a good choice of clustering model for the data.

The **DBSCAN** clustering algorithm does not make any assumptions about the potential shape of clusters within the data, which already makes it a better option than **KMeans** and **EM** due to its assumptions about the variance of each predictor within said clusters. In addition to this, **DBSCAN** also ignores "noise" points, which are essentially outlier points, which the two previous algorithms are susceptible to as they attempt to use every point of data. The major downside of **DBSCAN** are clusters that are extremely close to each other, as the points of such clusters may overlap and data sets in which the clusters have different densities. While this does appear to be present due to the large group of points towards the bottom left of the above scatterplot, **DBSCAN** appears to be best choice of clustering model for the data so far.

The **Hierarchical Clustering** model assumes that there exists an inherent hierarchical relationship. This is accomplished through generating clusters through determining how close each data point is to each other, and determining what points to "link" together based on the distances between each point. **Hierarchical Clustering** is susceptible to overlapping clusters, which as mentioned with **DBSCAN** appears to potentially exist within the bottom left corner of the scatterplot. In addition to this, the model also attempts to use all data points when determining the clusters, which makes the model also susceptible to noise. Because of this, although also a good choice, I would not consider **Hierarchical Clustering** to be the better choice of clustering model for the data over **DBSCAN**.

With this in mind, the two potentially best options for clustering models would be the **DB-SCAN** followed by the **Hierarchical Clustering** models.


```
[14]: # code, run by pressing "run" button to the left of this comment

# Determining epsilon for DBSCAN
mins = 5
nn = NearestNeighbors(n_neighbors= mins + 1)
nn.fit(zCluster[cluster_variables])

distances, neighbors = nn.kneighbors(zCluster[cluster_variables])
distances = np.sort(distances[:, mins], axis = 0)

distances_df = pd.DataFrame({"distances": distances,
                             "index": list(range(0, len(distances)))})
plt = (ggplot(distances_df, aes(x = "index", y = "distances")) +
       geom_line(color = "white", size = 2) + theme_minimal() +
       labs(title = "Elbow Method for Choosing eps") +
       theme(panel_grid_minor = element_blank(),
             rect = element_rect(fill = "#202124ff"),
             axis_text = element_text(color = "white"),
             axis_title = element_text(color = "white"),
             plot_title = element_text(color = "white"),
             panel_border = element_line(color = "darkgray"),
             plot_background = element_rect(fill = "#202124ff")
       ))
ggsave(plot=plt, filename='elbow.png', dpi=300)

plt
```



[14]: <ggplot: (8793431652665)>

3 Notice About how Epsilon for DBSCAN is Determined:

Based on the Dendrogram (shown above) based on a specific minimum number of neighboring points to determine a cluster, the Epsilon value used for DBSCAN Clustering is determined by the y-value of the "Elbow" of the Dendrogram graph, right before the graph rapidly shoots upwards.

```
[15]: # code, run by pressing "run" button to the left of this comment

# According to the model, with 5 min neighbors, best epsilon is around 1.036
db_model = DBSCAN(eps = 1.036, min_samples = 5).fit(zCluster[cluster_variables])

labsList = ["Noise"]
labsList = labsList + ["Cluster " + str(i) for i in range(1, len(set(db_model.
    ↳ labels_)))]

zCluster["assignments"] = db_model.labels_
```

```

# only clustered data points
db_clustered = zCluster.loc[(zCluster.assignments >= 0)]

# Could not get a silhouette score for only the clustered points as DBSCAN had
↳ only
# determined that one cluster exists within the data and decided that the rest
↳ of
# the data points are considered noise.

# Overall Data (Clustering in Regards to all points Including Noise)
print("Silhouette score for DBSCAN for overall data",
      silhouette_score(zCluster[cluster_variables], zCluster["assignments"]))

```

Silhouette score for DBSCAN for overall data 0.5333313784438912


```

[16]: # code, run by pressing "run" button to the left of this comment

# DBSCAN Clustering Scatterplot for Opened Issues Per Repository vs
# New Watchers Per Repository
(ggplot(zCluster, aes(x = "Opened Issues Per Repository", y = "New Watchers Per
↳ Repository",
                      color = "factor(assignments)")) + geom_point() +
 theme_minimal() + scale_color_discrete(name = "Cluster Assignment",
                      labels = labsList) +
 theme(panel_grid_major = element_blank()) +
 labs(x = "Number of Opened Issues Per Repository", y = "Number of New Watchers
↳ Per Repository",
      title = "Opened Issues vs New Watchers Per Repository (DBSCAN Clusters)"))

```

Opened Issues vs New Watchers Per Repository (DBSCAN Clusters)



[16]: <ggplot: (8793431524489)>

```
[17]: # code, run by pressing "run" button to the left of this comment

# Create a column to determine whether a Programming Language has been released
# prior to 1993
zCluster["Released Prior to 1993"] = zCluster["Appeared In Year"] <= 1993
# Determining percentage of DBSCAN Cluster
dbscan_cluster = zCluster.loc[zCluster["assignments"] == 0]
dbscan_noise = zCluster.loc[zCluster["assignments"] == -1]
```

```
[18]: # code, run by pressing "run" button to the left of this comment

# Calculating percentage of Programming Languages Appearing in DBScan Cluster
# Prior to 1993
DB_before_1993 = dbscan_cluster.loc[dbscan_cluster["Released Prior to 1993"]]
print("Total Number of Programming Languages in DBScan Cluster: ",
      len(dbscan_cluster))
print("Total Number of Programming Languages in DBScan Cluster that were
      Released Prior to 1993: ", len(DB_before_1993))
print("Percentage of Programming Languages in DBScan Cluster Released Prior to
      1993: ",
      len(DB_before_1993) / len(dbscan_cluster) * 100, "%")
print("Languages in DBScan Cluster that were Released Prior to 1993: ")
print(DB_before_1993["Repository Language"].to_string(index=False))
```

Total Number of Programming Languages in DBScan Cluster: 27
 Total Number of Programming Languages in DBScan Cluster that were Released Prior to 1993: 13
 Percentage of Programming Languages in DBScan Cluster Released Prior to 1993: 48.148148148148145 %
 Languages in DBScan Cluster that were Released Prior to 1993:

- Python
- C
- Shell
- Objective-C
- R
- VimL
- Perl
- TeX
- Emacs Lisp
- Haskell
- Lua
- Matlab
- Makefile

```
[19]: # code, run by pressing "run" button to the left of this comment

# Calculating percentage of Programming Languages in DBScan Cluster Appearing
↳After 1993
DB_after_1993 = dbscan_cluster.loc[dbscan_cluster["Released Prior to 1993"] ==
↳False]
print("Total Number of Programming Languages in DBScan Cluster: ",
↳len(dbscan_cluster))
print("Total Number of Programming Languages in DBScan Cluster that were
↳Released After to 1993: ", len(DB_after_1993))
print("Percentage of Programming Languages in DBScan Cluster Released After to
↳1993: ",
      len(DB_after_1993) / len(dbscan_cluster) * 100, "%")
print("Languages in DBScan Cluster that were Released After 1993: ")
print(DB_after_1993["Repository Language"].to_string(index=False))
```

Total Number of Programming Languages in DBScan Cluster: 27
 Total Number of Programming Languages in DBScan Cluster that were Released After to 1993: 14
 Percentage of Programming Languages in DBScan Cluster Released After to 1993: 51.85185185185185 %
 Languages in DBScan Cluster that were Released After 1993:

- JavaScript
- Java
- CSS
- PHP
- Ruby

C#
Go
CoffeeScript
Scala
Clojure
Arduino
Groovy
Puppet
PowerShell

[20]: *# code, run by pressing "run" button to the left of this comment*

```
# Calculating percentage of Programming Languages in Noise Cluster Appearing  
→Prior to 1993  
DB_noise_before_1993 = dbscan_noise.loc[dbscan_noise["Released Prior to 1993"]  
print("Total Number of Programming Languages in DBScan Cluster: ",  
      len(dbscan_noise))  
print("Total Number of Programming Languages in DBScan Cluster that were"  
      Released Prior to 1993: ",  
      len(DB_noise_before_1993))  
print("Percentage of Programming Languages in DBScan Cluster Released Prior to"  
      1993: ",  
      len(DB_noise_before_1993) / len(dbscan_noise) * 100, "%")  
print("Languages in DBScan Noise Cluster that were Released Prior to 1993: ")  
print(DB_noise_before_1993["Repository Language"].to_string(index=False))
```

Total Number of Programming Languages in DBScan Cluster: 3
Total Number of Programming Languages in DBScan Cluster that were Released Prior
to 1993: 1
Percentage of Programming Languages in DBScan Cluster Released Prior to 1993:
33.33333333333333 %
Languages in DBScan Noise Cluster that were Released Prior to 1993:
C++

[21]: *# code, run by pressing "run" button to the left of this comment*

```
# Calculating percentage of Programming Languages in Noise Cluster Appearing  
→After 1993  
DB_noise_after_1993 = dbscan_noise.loc[dbscan_noise["Released Prior to 1993"]  
      == False]  
print("Total Number of Programming Languages in DBScan Cluster: ",  
      len(dbscan_noise))  
print("Total Number of Programming Languages in DBScan Cluster that were"  
      Released Prior to 1993: ",  
      len(DB_noise_after_1993))  
print("Percentage of Programming Languages in DBScan Cluster Released Prior to"  
      1993: ",
```



```

len(DB_noise_after_1993) / len(dbscan_noise) * 100, "%")
print("Languages in DBScan Noise Cluster that were Released Prior to 1993: ")
print(DB_noise_after_1993["Repository Language"].to_string(index=False))

```


Total Number of Programming Languages in DBScan Cluster: 3
Total Number of Programming Languages in DBScan Cluster that were Released Prior to 1993: 2
Percentage of Programming Languages in DBScan Cluster Released Prior to 1993: 66.66666666666666 %
Languages in DBScan Noise Cluster that were Released Prior to 1993:
Swift
Rust

```

[22]: # code, run by pressing "run" button to the left of this comment

# Ward Linkage Dendrogram for Determining Hierarchical Clustering Linkage
↳ Criteria
hac_ward = AgglomerativeClustering(affinity = "euclidean",
                                   linkage = "ward")
hac_ward.fit(cluster_data[cluster_variables])
dendro_ward = sch.dendrogram(sch.linkage(cluster_data[cluster_variables],
                                         method='ward'))

```




```

[23]: # code, run by pressing "run" button to the left of this comment


```

```
# Average Linkage Dendrogram for Determining Hierarchical Clustering Linkage
↪ Criteria
hac_avg = AgglomerativeClustering(affinity = "euclidean",
                                   linkage = "average")
hac_avg.fit(cluster_data[cluster_variables])
dendro_avg = sch.dendrogram(sch.linkage(cluster_data[cluster_variables],
                                         method='average'))
```




```
[24]: # code, run by pressing "run" button to the left of this comment

# Single Linkage Dendrogram for Determining Hierarchical Clustering Linkage
↪ Criteria
hac_single = AgglomerativeClustering(affinity = "euclidean",
                                      linkage = "single")
hac_single.fit(cluster_data[cluster_variables])
dendro_single = sch.dendrogram(sch.linkage(cluster_data[cluster_variables],
                                             method='single'))
```



```
[25]: # code, run by pressing "run" button to the left of this comment

# Complete Linkage Dendrogram for Determining Hierarchical Clustering Linkage
→Criteria
hac_complete = AgglomerativeClustering(affinity = "euclidean",
                                       linkage = "complete")
hac_complete.fit(cluster_data[cluster_variables])
dendro_complete = sch.dendrogram(sch.linkage(cluster_data[cluster_variables],
                                             method='complete'))
```




```
[26]: # code, run by pressing "run" button to the left of this comment

# Performing Heirarchal Clustering using Complete Linkage as the criteria for
→clusters
hac = AgglomerativeClustering(n_clusters = 3,
                              affinity = "euclidean",
                              linkage = "complete")
hac.fit(zCluster[cluster_variables])
membership = hac.labels_
print("Hierarchical Clustering Silhouette Score: ",
      silhouette_score(zCluster[cluster_variables], membership))
```

Hierarchical Clustering Silhouette Score: 0.46871360964179304

```
[27]: # code, run by pressing "run" button to the left of this comment

# General Scatterplot with Heirarchal Clustering using Complete Linkage
zCluster["cluster3"] = membership
(ggplot(zCluster, aes(x = "Opened Issues Per Repository",
                      y = "New Watchers Per Repository")) +
  geom_point(aes(color = "factor(cluster3)")) + theme_minimal() +
  theme(panel_grid_major = element_blank()) +
  labs(x = "Annual Income (in USD)", y = "Gaps in Resume (in Months)",
       title = "Annual Income vs Resume Gaps"))
```



[27]: <ggplot: (8793428632697)>

[28]: # code, run by pressing "run" button to the left of this comment

```
# Creating sub-DataFrames for each of the clusters
cluster_zero = zCluster.loc[zCluster["cluster3"] == 0]
cluster_one = zCluster.loc[zCluster["cluster3"] == 1]
cluster_two = zCluster.loc[zCluster["cluster3"] == 2]
```

[29]: # code, run by pressing "run" button to the left of this comment

```
# Calculating percentage of Programming Languages Appearing in Cluster Zero
↳ Prior to 1993
C0_before_1993 = cluster_zero.loc[cluster_zero["Released Prior to 1993"]]
print("Total Number of Programming Languages in Cluster Zero: ",
      ↳ len(cluster_zero))
print("Total Number of Programming Languages in Cluster Zero that were Released
      ↳ Prior to 1993: ", len(C0_before_1993))
print("Percentage of Programming Languages in Cluster Zero Released Prior to
      ↳ 1993: ",
      len(C0_before_1993) / len(cluster_zero) * 100, "%")
print("Languages in Cluster Zero that were Released Prior to 1993: ")
print(C0_before_1993["Repository Language"].to_string(index=False))
```

Total Number of Programming Languages in Cluster Zero: 23
 Total Number of Programming Languages in Cluster Zero that were Released Prior to 1993: 12
 Percentage of Programming Languages in Cluster Zero Released Prior to 1993: 52.17391304347826 %
 Languages in Cluster Zero that were Released Prior to 1993:

- Python
- C
- Shell
- R
- VimL
- Perl
- TeX
- Emacs Lisp
- Haskell
- Lua
- Matlab
- Makefile

```
[30]: # code, run by pressing "run" button to the left of this comment

# Calculating percentage of Programming Languages Appearing in Cluster Zero
# After 1993
C0_after_1993 = cluster_zero.loc[cluster_zero["Released Prior to 1993"] ==
# False]
print("Total Number of Programming Languages in Cluster Zero: ",
# len(cluster_zero))
print("Total Number of Programming Languages in Cluster Zero that were Released
# After 1993: ", len(C0_after_1993))
print("Percentage of Programming Languages in Cluster Zero Released After 1993:
# ",
      len(C0_after_1993) / len(cluster_zero) * 100, "%")
print("Languages in Cluster Zero that were Released After 1993: ")
print(C0_after_1993["Repository Language"].to_string(index=False))
```

Total Number of Programming Languages in Cluster Zero: 23
 Total Number of Programming Languages in Cluster Zero that were Released After 1993: 11
 Percentage of Programming Languages in Cluster Zero Released After 1993: 47.82608695652174 %
 Languages in Cluster Zero that were Released After 1993:

- Java
- PHP
- Ruby
- C#
- CoffeeScript
- Scala

Clojure
Arduino
Groovy
Puppet
PowerShell

```
[31]: # code, run by pressing "run" button to the left of this comment

# Calculating percentage of Programming Languages Appearing in Cluster One
↳Prior to 1993
C1_before_1993 = cluster_one.loc[cluster_one["Released Prior to 1993"]]
print("Total Number of Programming Languages in Cluster One: ",
↳len(cluster_one))
print("Total Number of Programming Languages in Cluster One that were Released
↳Prior to 1993: ", len(C1_before_1993))
print("Percentage of Programming Languages in Cluster One Released Prior to
↳1993: ",
      len(C1_before_1993) / len(cluster_one) * 100, "%")
print("Languages in Cluster One that were Released Prior to 1993: ")
print(C1_before_1993["Repository Language"].to_string(index=False))
```

```
Total Number of Programming Languages in Cluster One: 2
Total Number of Programming Languages in Cluster One that were Released Prior to
1993: 1
Percentage of Programming Languages in Cluster One Released Prior to 1993: 50.0
%
Languages in Cluster One that were Released Prior to 1993:
C++
```

```
[32]: # code, run by pressing "run" button to the left of this comment

# Calculating percentage of Programming Languages Appearing in Cluster One
↳After 1993
C1_after_1993 = cluster_one.loc[cluster_one["Released Prior to 1993"] == False]
print("Total Number of Programming Languages in Cluster One: ",
↳len(cluster_one))
print("Total Number of Programming Languages in Cluster One that were Released
↳After 1993: ", len(C1_after_1993))
print("Percentage of Programming Languages in Cluster One Released After 1993:
↳",
      len(C1_after_1993) / len(cluster_one) * 100, "%")
print("Languages in Cluster One that were Released After 1993: ")
print(C1_after_1993["Repository Language"].to_string(index=False))
```

```
Total Number of Programming Languages in Cluster One: 2
Total Number of Programming Languages in Cluster One that were Released After
1993: 1
```

Percentage of Programming Languages in Cluster One Released After 1993: 50.0 %
Languages in Cluster One that were Released After 1993:
Rust

```
[33]: # code, run by pressing "run" button to the left of this comment

# Calculating percentage of Programming Languages Appearing in Cluster Two
→Prior to 1993
C2_before_1993 = cluster_two.loc[cluster_two["Released Prior to 1993"]]
print("Total Number of Programming Languages in Cluster Two: ",
→len(cluster_two))
print("Total Number of Programming Languages in Cluster Two that were Released
→Prior to 1993: ", len(C2_before_1993))
print("Percentage of Programming Languages in Cluster Two Released Prior to
→1993: ",
      len(C2_before_1993) / len(cluster_two) * 100, "%")
print("Languages in Cluster Two that were Released Prior to 1993: ")
print(C2_before_1993["Repository Language"].to_string(index=False))
```

Total Number of Programming Languages in Cluster Two: 5
Total Number of Programming Languages in Cluster Two that were Released Prior to 1993: 1
Percentage of Programming Languages in Cluster Two Released Prior to 1993: 20.0 %
Languages in Cluster Two that were Released Prior to 1993:
Objective-C

```
[34]: # code, run by pressing "run" button to the left of this comment

# Calculating percentage of Programming Languages Appearing in Cluster Two
→After 1993
C2_after_1993 = cluster_two.loc[cluster_two["Released Prior to 1993"] == False]
print("Total Number of Programming Languages in Cluster Two: ",
→len(cluster_two))
print("Total Number of Programming Languages in Cluster Two that were Released
→After 1993: ", len(C2_after_1993))
print("Percentage of Programming Languages in Cluster Two Released After 1993:
→",
      len(C2_after_1993) / len(cluster_two) * 100, "%")
print("Languages in Cluster Two that were Released After 1993: ")
print(C2_after_1993["Repository Language"].to_string(index=False))
```

Total Number of Programming Languages in Cluster Two: 5
Total Number of Programming Languages in Cluster Two that were Released After 1993: 4
Percentage of Programming Languages in Cluster Two Released After 1993: 80.0 %
Languages in Cluster Two that were Released After 1993:

JavaScript
CSS
Go
Swift

4 Q3.

(Feature Reduction) Apply LASSO to the Linear Regression model created in Question 1 and based on the variables that LASSO determines to have a coefficient, create another Linear Regression model. How did this effect the original model? What does this tell you about the GitHub data regarding Programming Languages used in GitHub repositories?

```
[36]: # code, run by pressing "run" button to the left of this comment

# Manual Method of Applying LASSO, which involves choosing the variables to
# →exclude
# based on the LASSO coefficients of each of the variables used in the original
# Linear Regression model

# Determining alpha value to use for LASSO
lsr_alpha = LassoCV(cv = 5).fit(x_train[predictors_all],
                                y_train["Appeared In Year"])
print("The alpha to use for LASSO is: ", lsr_alpha.alpha_)
```

The alpha to use for LASSO is: 3.456872390218585

5 Warning Notice Note

The *Convergence Warning* notification from the manual alpha-selection for LASSO is a likely result from having too little of a dataset to work with.

```
[37]: # code, run by pressing "run" button to the left of this comment

logistic_co = lr_all.coef_[0]

# Create Lasso Model and get its Coefficients
lasso = Lasso(alpha = lsr_alpha.alpha_, fit_intercept = True,
              tol=0.000001, max_iter = 100000)

lasso.fit(x_train[predictors_all], y_train["Appeared In Year"])
lasso_co = lasso.coef_
conames = ["Active", "Pushes", "Pushes/Repository",
           "New Forks", "Issues",
           "New Watchers"] * 2
# Create the dataframe to use to graph the comparison between the coefficients
```

```

# for each variable as determined by Logistic Regression and LASSO
model_coefs = np.concatenate([logistic_co,lasso_co])
model = np.repeat(np.array(["Linear", "LASSO"]), [6,6], axis=0)

compare_df = pd.DataFrame({"conames": conames, "coefs": model_coefs, "model":_
↪model})
compare_df["Odds Coefs"] = np.exp(compare_df["coefs"])
compare_df

```

```

[37]:

```

	conames	coefs	model	Odds Coefs
0	Active	-1.638289e+01	Linear	7.673617e-08
1	Pushes	1.521883e+01	Linear	4.068699e+06
2	Pushes/Repository	-2.143425e+00	Linear	1.172526e-01
3	New Forks	7.167881e-02	Linear	1.074310e+00
4	Issues	-3.853283e-01	Linear	6.802273e-01
5	New Watchers	3.962142e+00	Linear	5.256982e+01
6	Active	-0.000000e+00	LASSO	1.000000e+00
7	Pushes	-0.000000e+00	LASSO	1.000000e+00
8	Pushes/Repository	-0.000000e+00	LASSO	1.000000e+00
9	New Forks	0.000000e+00	LASSO	1.000000e+00
10	Issues	-0.000000e+00	LASSO	1.000000e+00
11	New Watchers	1.184238e-15	LASSO	1.000000e+00


```

[38]: # code, run by pressing "run" button to the left of this comment

# Boxplot comparing the coefficients of variables between Logistic and LASSO_
↪model

(ggplot(compare_df, aes(x = "conames", y = "coefs", fill = "model")) +
geom_boxplot() + ggtitle("All Coefficients of Each Variable") +
  theme(axis_text_x = element_text(angle = 75)) +
  theme_minimal())

```



[38]: <ggplot: (8793428663293)>

```
[40]: # code, run by pressing "run" button to the left of this comment

# Creating a new Logistic Model based on variables with non-zero LASSO
↪ Coefficients
lasso_var = ["New Watchers Per Repository"]
lr_lasso = LinearRegression()
lr_lasso.fit(x_train[lasso_var], y_train["Appeared In Year"])

lasso_trained = lr_lasso.predict(x_train[lasso_var])
lasso_predicted = lr_lasso.predict(x_test[lasso_var])

# Print out Mean Squared Error and R2-Score for Testing and Training data
print("For the Linear Regression Model with only New Watchers Per Repository...
↪")
print("Lasso Training data R2 Score:",
      r2_score(y_train, lasso_trained))
print("Lasso Training data Mean Squared Error Score:",
      mean_squared_error(y_train, lasso_trained))

print("\n")
```

```
print("Lasso Testing data R2 Score:",
      r2_score(y_test, lasso_predicted))
print("Lasso Training data Mean Squared Error Score: ",
      mean_squared_error(y_test, lasso_predicted))
```

For the Linear Regression Model with only New Watchers Per Repository...
 Lasso Training data R2 Score: 0.09503086844057518
 Lasso Training data Mean Squared Error Score: 113.79829716663316

Lasso Testing data R2 Score: 0.3530214194316901
 Lasso Training data Mean Squared Error Score: 90.66685941575344

```
[42]: # code, run by pressing "run" button to the left of this comment

# Using the automatic application of LASSO, in which we do not know which
# variables have been used or excluded from the new Linear Regression Model

lsr_tune = LassoCV(cv = 5).fit(x_train[predictors_all], y_train["Appeared In_
↪Year"])

# Print out Mean Squared Error and R2-Score for Testing and Training data
print("For the Linear Regression Model excluding Number of Opened Issues Per_
↪Repository...")
print("Lasso Training data R2 Score:",
      r2_score(y_train, lsr_tune.predict(x_train[predictors_all])))
print("Lasso Training data Mean Squared Error Score:",
      mean_squared_error(y_train, lsr_tune.predict(x_train[predictors_all])))

print("\n")

print("Lasso Testing data R2 Score:",
      r2_score(y_test, lsr_tune.predict(x_test[predictors_all])))
print("Lasso Training data Mean Squared Error Score: ",
      mean_squared_error(y_test, lsr_tune.predict(x_test[predictors_all])))

print("\n" + str(lsr_tune.alpha_) + " was chosen as the alpha for LASSO.")
```

For the Linear Regression Model excluding Number of Opened Issues Per Repository...
 Lasso Training data R2 Score: 0.0
 Lasso Training data Mean Squared Error Score: 125.7482638888889

Lasso Testing data R2 Score: -0.011905351833497058
 Lasso Training data Mean Squared Error Score: 141.80729166666646

3.456872390218585 was chosen as the alpha for LASSO.

```
[ ]: # code, only run for PDF export purposes. Mostly irrelevant to the actual coding
# aspect of the final project.

# The following code is specifically for creating a PDF containing the outputs
→ of
# the notebook as a PDF, do not run for general testing

# doesn't show this cells output when downloading PDF
!pip install gwpy &> /dev/null

# installing necessary files
!apt-get install texlive texlive-xetex texlive-latex-extra pandoc
!sudo apt-get update
!sudo apt-get install texlive-xetex texlive-fonts-recommended
→ texlive-plain-generic

# installing pypandoc
!pip install pypandoc

# connecting to google drive
from google.colab import drive
drive.mount('/content/drive')

# copying your file over.
!cp "drive/My Drive/Colab Notebooks/CPSC354_FA22_Project.ipynb" ./

# converting file to PDF, should appear under "Files" tab in the left sidebar.
!jupyter nbconvert --to PDF "CPSC354_FA22_Project.ipynb"
```

Reading package lists... Done

Building dependency tree

Reading state information... Done

pandoc is already the newest version (1.19.2.4~dfsg-1build4).

pandoc set to manually installed.

The following package was automatically installed and is no longer required:

libnvidia-common-460

Use 'apt autoremove' to remove it.

The following additional packages will be installed:

fonts-droid-fallback fonts-lato fonts-lmodern fonts-noto-mono fonts-texgyre
javascript-common libcupsfilters1 libcupsimage2 libgs9 libgs9-common
libijs-0.35 libjbig2dec0 libjs-jquery libkpathsea6 libpotrace0 libptexenc1
libruby2.5 libsynchronet1 libtexlua52 libtexluajit2 libzip-0-13 lmodern
poppler-data preview-latex-style rake ruby ruby-did-you-mean ruby-minitest
ruby-net-telnet ruby-power-assert ruby-test-unit ruby2.5

rubygems-integration tlutils tex-common tex-gyre texlive-base
texlive-binaries texlive-fonts-recommended texlive-latex-base
texlive-latex-recommended texlive-pictures texlive-plain-generic tipa

Suggested packages:

fonts-noto apache2 | lighttpd | httpd poppler-utils ghostscript
fonts-japanese-mincho | fonts-ipafont-mincho fonts-japanese-gothic
| fonts-ipafont-gothic fonts-arphic-ukai fonts-arphic-uming fonts-nanum ri
ruby-dev bundler debhelper gv | postscript-viewer perl-tk xpdf-reader
| pdf-viewer texlive-fonts-recommended-doc texlive-latex-base-doc
python-pygments icc-profiles libfile-which-perl
libspreadsheet-parseexcel-perl texlive-latex-extra-doc
texlive-latex-recommended-doc texlive-pstricks dot2tex prerex ruby-tcltk
| libtcltk-ruby texlive-pictures-doc vprerex

The following NEW packages will be installed:

fonts-droid-fallback fonts-lato fonts-lmodern fonts-noto-mono fonts-texgyre
javascript-common libcupsfilters1 libcupsimage2 libgs9 libgs9-common
libijs-0.35 libjbig2dec0 libjs-jquery libkpathsea6 libpotrace0 libptexenc1
libruby2.5 libsynchronet1 libtexlua52 libtexluajit2 libzip-0-13 lmodern
poppler-data preview-latex-style rake ruby ruby-did-you-mean ruby-minitest
ruby-net-telnet ruby-power-assert ruby-test-unit ruby2.5
rubygems-integration tlutils tex-common tex-gyre texlive texlive-base
texlive-binaries texlive-fonts-recommended texlive-latex-base
texlive-latex-extra texlive-latex-recommended texlive-pictures
texlive-plain-generic texlive-xetex tipa

0 upgraded, 47 newly installed, 0 to remove and 5 not upgraded.

Need to get 146 MB of archives.

After this operation, 460 MB of additional disk space will be used.

Get:1 <http://archive.ubuntu.com/ubuntu bionic/main amd64 fonts-droid-fallback>
all 1:6.0.1r16-1.1 [1,805 kB]

Get:2 <http://archive.ubuntu.com/ubuntu bionic/main amd64 fonts-lato> all 2.0-2
[2,698 kB]

Get:3 <http://archive.ubuntu.com/ubuntu bionic/main amd64 poppler-data> all
0.4.8-2 [1,479 kB]

Get:4 <http://archive.ubuntu.com/ubuntu bionic/main amd64 tex-common> all 6.09
[33.0 kB]

Get:5 <http://archive.ubuntu.com/ubuntu bionic/main amd64 fonts-lmodern> all
2.004.5-3 [4,551 kB]

Get:6 <http://archive.ubuntu.com/ubuntu bionic/main amd64 fonts-noto-mono> all
20171026-2 [75.5 kB]

Get:7 <http://archive.ubuntu.com/ubuntu bionic/universe amd64 fonts-texgyre> all
20160520-1 [8,761 kB]

Get:8 <http://archive.ubuntu.com/ubuntu bionic/main amd64 javascript-common> all
11 [6,066 B]

Get:9 <http://archive.ubuntu.com/ubuntu bionic-updates/main amd64 libcupsfilters1>
amd64 1.20.2-0ubuntu3.1 [108 kB]

Get:10 <http://archive.ubuntu.com/ubuntu bionic-updates/main amd64 libcupsimage2>
amd64 2.2.7-1ubuntu2.9 [18.6 kB]

Get:11 <http://archive.ubuntu.com/ubuntu bionic/main amd64 libijs-0.35> amd64

0.35-13 [15.5 kB]
 Get:12 <http://archive.ubuntu.com/ubuntu> bionic/main amd64 libjbig2dec0 amd64
 0.13-6 [55.9 kB]
 Get:13 <http://archive.ubuntu.com/ubuntu> bionic-updates/main amd64 libgs9-common
 all 9.26~dfsg+0-0ubuntu0.18.04.17 [5,092 kB]
 Get:14 <http://archive.ubuntu.com/ubuntu> bionic-updates/main amd64 libgs9 amd64
 9.26~dfsg+0-0ubuntu0.18.04.17 [2,267 kB]
 Get:15 <http://archive.ubuntu.com/ubuntu> bionic/main amd64 libjs-jquery all
 3.2.1-1 [152 kB]
 Get:16 <http://archive.ubuntu.com/ubuntu> bionic-updates/main amd64 libkpathsea6
 amd64 2017.20170613.44572-8ubuntu0.1 [54.9 kB]
 Get:17 <http://archive.ubuntu.com/ubuntu> bionic/main amd64 libpotrace0 amd64
 1.14-2 [17.4 kB]
 Get:18 <http://archive.ubuntu.com/ubuntu> bionic-updates/main amd64 libptexenc1
 amd64 2017.20170613.44572-8ubuntu0.1 [34.5 kB]
 Get:19 <http://archive.ubuntu.com/ubuntu> bionic/main amd64 rubygems-integration
 all 1.11 [4,994 B]
 Get:20 <http://archive.ubuntu.com/ubuntu> bionic-updates/main amd64 ruby2.5 amd64
 2.5.1-1ubuntu1.12 [48.6 kB]
 Get:21 <http://archive.ubuntu.com/ubuntu> bionic/main amd64 ruby amd64 1:2.5.1
 [5,712 B]
 Get:22 <http://archive.ubuntu.com/ubuntu> bionic-updates/main amd64 rake all
 12.3.1-1ubuntu0.1 [44.9 kB]
 Get:23 <http://archive.ubuntu.com/ubuntu> bionic/main amd64 ruby-did-you-mean all
 1.2.0-2 [9,700 B]
 Get:24 <http://archive.ubuntu.com/ubuntu> bionic/main amd64 ruby-minitest all
 5.10.3-1 [38.6 kB]
 Get:25 <http://archive.ubuntu.com/ubuntu> bionic/main amd64 ruby-net-telnet all
 0.1.1-2 [12.6 kB]
 Get:26 <http://archive.ubuntu.com/ubuntu> bionic/main amd64 ruby-power-assert all
 0.3.0-1 [7,952 B]
 Get:27 <http://archive.ubuntu.com/ubuntu> bionic/main amd64 ruby-test-unit all
 3.2.5-1 [61.1 kB]
 Get:28 <http://archive.ubuntu.com/ubuntu> bionic-updates/main amd64 libruby2.5
 amd64 2.5.1-1ubuntu1.12 [3,073 kB]
 Get:29 <http://archive.ubuntu.com/ubuntu> bionic-updates/main amd64 libsyntax1
 amd64 2017.20170613.44572-8ubuntu0.1 [41.4 kB]
 Get:30 <http://archive.ubuntu.com/ubuntu> bionic-updates/main amd64 libtexlua52
 amd64 2017.20170613.44572-8ubuntu0.1 [91.2 kB]
 Get:31 <http://archive.ubuntu.com/ubuntu> bionic-updates/main amd64 libtexluajit2
 amd64 2017.20170613.44572-8ubuntu0.1 [230 kB]
 Get:32 <http://archive.ubuntu.com/ubuntu> bionic-updates/main amd64 libzip-0-13
 amd64 0.13.62-3.1ubuntu0.18.04.1 [26.0 kB]
 Get:33 <http://archive.ubuntu.com/ubuntu> bionic/main amd64 lmodern all 2.004.5-3
 [9,631 kB]
 Get:34 <http://archive.ubuntu.com/ubuntu> bionic/main amd64 preview-latex-style
 all 11.91-1ubuntu1 [185 kB]
 Get:35 <http://archive.ubuntu.com/ubuntu> bionic/main amd64 tiutils amd64 1.41-2

```

[56.0 kB]
Get:36 http://archive.ubuntu.com/ubuntu bionic/universe amd64 tex-gyre all
20160520-1 [4,998 kB]
Get:37 http://archive.ubuntu.com/ubuntu bionic-updates/main amd64 texlive-
binaries amd64 2017.20170613.44572-8ubuntu0.1 [8,179 kB]
Get:38 http://archive.ubuntu.com/ubuntu bionic/main amd64 texlive-base all
2017.20180305-1 [18.7 MB]
Get:39 http://archive.ubuntu.com/ubuntu bionic/universe amd64 texlive-fonts-
recommended all 2017.20180305-1 [5,262 kB]
Get:40 http://archive.ubuntu.com/ubuntu bionic/main amd64 texlive-latex-base all
2017.20180305-1 [951 kB]
Get:41 http://archive.ubuntu.com/ubuntu bionic/main amd64 texlive-latex-
recommended all 2017.20180305-1 [14.9 MB]
Get:42 http://archive.ubuntu.com/ubuntu bionic/universe amd64 texlive all
2017.20180305-1 [14.4 kB]
Get:43 http://archive.ubuntu.com/ubuntu bionic/universe amd64 texlive-pictures
all 2017.20180305-1 [4,026 kB]
Get:44 http://archive.ubuntu.com/ubuntu bionic/universe amd64 texlive-latex-
extra all 2017.20180305-2 [10.6 MB]
Get:45 http://archive.ubuntu.com/ubuntu bionic/universe amd64 texlive-plain-
generic all 2017.20180305-2 [23.6 MB]
Get:46 http://archive.ubuntu.com/ubuntu bionic/universe amd64 tipa all 2:1.3-20
[2,978 kB]
Get:47 http://archive.ubuntu.com/ubuntu bionic/universe amd64 texlive-xetex all
2017.20180305-1 [10.7 MB]
Fetched 146 MB in 4s (35.1 MB/s)
Extracting templates from packages: 100%
Preconfiguring packages ...
Selecting previously unselected package fonts-droid-fallback.
(Reading database ... 123991 files and directories currently installed.)
Preparing to unpack .../00-fonts-droid-fallback_1%3a6.0.1r16-1.1_all.deb ...
Unpacking fonts-droid-fallback (1:6.0.1r16-1.1) ...
Selecting previously unselected package fonts-lato.
Preparing to unpack .../01-fonts-lato_2.0-2_all.deb ...
Unpacking fonts-lato (2.0-2) ...
Selecting previously unselected package poppler-data.
Preparing to unpack .../02-poppler-data_0.4.8-2_all.deb ...
Unpacking poppler-data (0.4.8-2) ...
Selecting previously unselected package tex-common.
Preparing to unpack .../03-tex-common_6.09_all.deb ...
Unpacking tex-common (6.09) ...
Selecting previously unselected package fonts-lmodern.
Preparing to unpack .../04-fonts-lmodern_2.004.5-3_all.deb ...
Unpacking fonts-lmodern (2.004.5-3) ...
Selecting previously unselected package fonts-noto-mono.
Preparing to unpack .../05-fonts-noto-mono_20171026-2_all.deb ...
Unpacking fonts-noto-mono (20171026-2) ...
Selecting previously unselected package fonts-texgyre.

```



```

Preparing to unpack .../06-fonts-texgyre_20160520-1_all.deb ...
Unpacking fonts-texgyre (20160520-1) ...
Selecting previously unselected package javascript-common.
Preparing to unpack .../07-javascript-common_11_all.deb ...
Unpacking javascript-common (11) ...
Selecting previously unselected package libcupsfilters1:amd64.
Preparing to unpack .../08-libcupsfilters1_1.20.2-0ubuntu3.1_amd64.deb ...
Unpacking libcupsfilters1:amd64 (1.20.2-0ubuntu3.1) ...
Selecting previously unselected package libcupsimage2:amd64.
Preparing to unpack .../09-libcupsimage2_2.2.7-1ubuntu2.9_amd64.deb ...
Unpacking libcupsimage2:amd64 (2.2.7-1ubuntu2.9) ...
Selecting previously unselected package libijs-0.35:amd64.
Preparing to unpack .../10-libijs-0.35_0.35-13_amd64.deb ...
Unpacking libijs-0.35:amd64 (0.35-13) ...
Selecting previously unselected package libjbig2dec0:amd64.
Preparing to unpack .../11-libjbig2dec0_0.13-6_amd64.deb ...
Unpacking libjbig2dec0:amd64 (0.13-6) ...
Selecting previously unselected package libgs9-common.
Preparing to unpack .../12-libgs9-common_9.26~dfsg+0-0ubuntu0.18.04.17_all.deb
...
Unpacking libgs9-common (9.26~dfsg+0-0ubuntu0.18.04.17) ...
Selecting previously unselected package libgs9:amd64.
Preparing to unpack .../13-libgs9_9.26~dfsg+0-0ubuntu0.18.04.17_amd64.deb ...
Unpacking libgs9:amd64 (9.26~dfsg+0-0ubuntu0.18.04.17) ...
Selecting previously unselected package libjs-jquery.
Preparing to unpack .../14-libjs-jquery_3.2.1-1_all.deb ...
Unpacking libjs-jquery (3.2.1-1) ...
Selecting previously unselected package libkpathsea6:amd64.
Preparing to unpack .../15-libkpathsea6_2017.20170613.44572-8ubuntu0.1_amd64.deb
...
Unpacking libkpathsea6:amd64 (2017.20170613.44572-8ubuntu0.1) ...
Selecting previously unselected package libpotrace0.
Preparing to unpack .../16-libpotrace0_1.14-2_amd64.deb ...
Unpacking libpotrace0 (1.14-2) ...
Selecting previously unselected package libptexenc1:amd64.
Preparing to unpack .../17-libptexenc1_2017.20170613.44572-8ubuntu0.1_amd64.deb
...
Unpacking libptexenc1:amd64 (2017.20170613.44572-8ubuntu0.1) ...
Selecting previously unselected package rubygems-integration.
Preparing to unpack .../18-rubygems-integration_1.11_all.deb ...
Unpacking rubygems-integration (1.11) ...
Selecting previously unselected package ruby2.5.
Preparing to unpack .../19-ruby2.5_2.5.1-1ubuntu1.12_amd64.deb ...
Unpacking ruby2.5 (2.5.1-1ubuntu1.12) ...
Selecting previously unselected package ruby.
Preparing to unpack .../20-ruby_1%3a2.5.1_amd64.deb ...
Unpacking ruby (1:2.5.1) ...
Selecting previously unselected package rake.

```

```

Preparing to unpack .../21-rake_12.3.1-1ubuntu0.1_all.deb ...
Unpacking rake (12.3.1-1ubuntu0.1) ...
Selecting previously unselected package ruby-did-you-mean.
Preparing to unpack .../22-ruby-did-you-mean_1.2.0-2_all.deb ...
Unpacking ruby-did-you-mean (1.2.0-2) ...
Selecting previously unselected package ruby-minitest.
Preparing to unpack .../23-ruby-minitest_5.10.3-1_all.deb ...
Unpacking ruby-minitest (5.10.3-1) ...
Selecting previously unselected package ruby-net-telnet.
Preparing to unpack .../24-ruby-net-telnet_0.1.1-2_all.deb ...
Unpacking ruby-net-telnet (0.1.1-2) ...
Selecting previously unselected package ruby-power-assert.
Preparing to unpack .../25-ruby-power-assert_0.3.0-1_all.deb ...
Unpacking ruby-power-assert (0.3.0-1) ...
Selecting previously unselected package ruby-test-unit.
Preparing to unpack .../26-ruby-test-unit_3.2.5-1_all.deb ...
Unpacking ruby-test-unit (3.2.5-1) ...
Selecting previously unselected package libruby2.5:amd64.
Preparing to unpack .../27-libruby2.5_2.5.1-1ubuntu1.12_amd64.deb ...
Unpacking libruby2.5:amd64 (2.5.1-1ubuntu1.12) ...
Selecting previously unselected package libsyntax1:amd64.
Preparing to unpack .../28-libsyntax1_2017.20170613.44572-8ubuntu0.1_amd64.deb
...
Unpacking libsyntax1:amd64 (2017.20170613.44572-8ubuntu0.1) ...
Selecting previously unselected package libtexlua52:amd64.
Preparing to unpack .../29-libtexlua52_2017.20170613.44572-8ubuntu0.1_amd64.deb
...
Unpacking libtexlua52:amd64 (2017.20170613.44572-8ubuntu0.1) ...
Selecting previously unselected package libtexlua52:amd64.
Preparing to unpack
.../30-libtexlua52_2017.20170613.44572-8ubuntu0.1_amd64.deb ...
Unpacking libtexlua52:amd64 (2017.20170613.44572-8ubuntu0.1) ...
Selecting previously unselected package libzip-0-13:amd64.
Preparing to unpack .../31-libzip-0-13_0.13.62-3.1ubuntu0.18.04.1_amd64.deb ...
Unpacking libzip-0-13:amd64 (0.13.62-3.1ubuntu0.18.04.1) ...
Selecting previously unselected package lmodern.
Preparing to unpack .../32-lmodern_2.004.5-3_all.deb ...
Unpacking lmodern (2.004.5-3) ...
Selecting previously unselected package preview-latex-style.
Preparing to unpack .../33-preview-latex-style_11.91-1ubuntu1_all.deb ...
Unpacking preview-latex-style (11.91-1ubuntu1) ...
Selecting previously unselected package t1utils.
Preparing to unpack .../34-t1utils_1.41-2_amd64.deb ...
Unpacking t1utils (1.41-2) ...
Selecting previously unselected package tex-gyre.
Preparing to unpack .../35-tex-gyre_20160520-1_all.deb ...
Unpacking tex-gyre (20160520-1) ...
Selecting previously unselected package texlive-binaries.

```

```

Preparing to unpack .../36-texlive-
binaries_2017.20170613.44572-8ubuntu0.1_amd64.deb ...
Unpacking texlive-binaries (2017.20170613.44572-8ubuntu0.1) ...
Selecting previously unselected package texlive-base.
Preparing to unpack .../37-texlive-base_2017.20180305-1_all.deb ...
Unpacking texlive-base (2017.20180305-1) ...
Selecting previously unselected package texlive-fonts-recommended.
Preparing to unpack .../38-texlive-fonts-recommended_2017.20180305-1_all.deb ...
Unpacking texlive-fonts-recommended (2017.20180305-1) ...
Selecting previously unselected package texlive-latex-base.
Preparing to unpack .../39-texlive-latex-base_2017.20180305-1_all.deb ...
Unpacking texlive-latex-base (2017.20180305-1) ...
Selecting previously unselected package texlive-latex-recommended.
Preparing to unpack .../40-texlive-latex-recommended_2017.20180305-1_all.deb ...
Unpacking texlive-latex-recommended (2017.20180305-1) ...
Selecting previously unselected package texlive.
Preparing to unpack .../41-texlive_2017.20180305-1_all.deb ...
Unpacking texlive (2017.20180305-1) ...
Selecting previously unselected package texlive-pictures.
Preparing to unpack .../42-texlive-pictures_2017.20180305-1_all.deb ...
Unpacking texlive-pictures (2017.20180305-1) ...
Selecting previously unselected package texlive-latex-extra.
Preparing to unpack .../43-texlive-latex-extra_2017.20180305-2_all.deb ...
Unpacking texlive-latex-extra (2017.20180305-2) ...
Selecting previously unselected package texlive-plain-generic.
Preparing to unpack .../44-texlive-plain-generic_2017.20180305-2_all.deb ...
Unpacking texlive-plain-generic (2017.20180305-2) ...
Selecting previously unselected package tipa.
Preparing to unpack .../45-tipa_2%3a1.3-20_all.deb ...
Unpacking tipa (2:1.3-20) ...
Selecting previously unselected package texlive-xetex.
Preparing to unpack .../46-texlive-xetex_2017.20180305-1_all.deb ...
Unpacking texlive-xetex (2017.20180305-1) ...
Setting up libgs9-common (9.26~dfsg+0-0ubuntu0.18.04.17) ...
Setting up libkpathsea6:amd64 (2017.20170613.44572-8ubuntu0.1) ...
Setting up libjs-jquery (3.2.1-1) ...
Setting up libtexlua52:amd64 (2017.20170613.44572-8ubuntu0.1) ...
Setting up fonts-droid-fallback (1:6.0.1r16-1.1) ...
Setting up libsynctex1:amd64 (2017.20170613.44572-8ubuntu0.1) ...
Setting up libptexenc1:amd64 (2017.20170613.44572-8ubuntu0.1) ...
Setting up tex-common (6.09) ...
update-language: texlive-base not installed and configured, doing nothing!
Setting up poppler-data (0.4.8-2) ...
Setting up tex-gyre (20160520-1) ...
Setting up preview-latex-style (11.91-1ubuntu1) ...
Setting up fonts-texgyre (20160520-1) ...
Setting up fonts-noto-mono (20171026-2) ...
Setting up fonts-lato (2.0-2) ...

```

```

Setting up libcupsfilters1:amd64 (1.20.2-0ubuntu3.1) ...
Setting up libcupsimage2:amd64 (2.2.7-1ubuntu2.9) ...
Setting up libjbig2dec0:amd64 (0.13-6) ...
Setting up ruby-did-you-mean (1.2.0-2) ...
Setting up tlutils (1.41-2) ...
Setting up ruby-net-telnet (0.1.1-2) ...
Setting up libijs-0.35:amd64 (0.35-13) ...
Setting up rubygems-integration (1.11) ...
Setting up libpotrace0 (1.14-2) ...
Setting up javascript-common (11) ...
Setting up ruby-minitest (5.10.3-1) ...
Setting up libzip-0-13:amd64 (0.13.62-3.1ubuntu0.18.04.1) ...
Setting up libgs9:amd64 (9.26~dfsg+0-0ubuntu0.18.04.17) ...
Setting up libtexluajit2:amd64 (2017.20170613.44572-8ubuntu0.1) ...
Setting up fonts-lmodern (2.004.5-3) ...
Setting up ruby-power-assert (0.3.0-1) ...
Setting up texlive-binaries (2017.20170613.44572-8ubuntu0.1) ...
update-alternatives: using /usr/bin/xdvi-xaw to provide /usr/bin/xdvi.bin
(xdvi.bin) in auto mode
update-alternatives: using /usr/bin/bibtex.original to provide /usr/bin/bibtex
(bibtex) in auto mode
Setting up texlive-base (2017.20180305-1) ...
mktexlsr: Updating /var/lib/texmf/ls-R-TEXLIVEDIST...
mktexlsr: Updating /var/lib/texmf/ls-R-TEXMFMAIN...
mktexlsr: Updating /var/lib/texmf/ls-R...
mktexlsr: Done.
tl-paper: setting paper size for dvips to a4:
/var/lib/texmf/dvips/config/config-paper.ps
tl-paper: setting paper size for dvipdfmx to a4:
/var/lib/texmf/dvipdfmx/dvipdfmx-paper.cfg
tl-paper: setting paper size for xdvi to a4: /var/lib/texmf/xdvi/XDvi-paper
tl-paper: setting paper size for pdftex to a4:
/var/lib/texmf/tex/generic/config/pdftexconfig.tex
Setting up texlive-fonts-recommended (2017.20180305-1) ...
Setting up texlive-plain-generic (2017.20180305-2) ...
Setting up texlive-latex-base (2017.20180305-1) ...
Setting up lmodern (2.004.5-3) ...
Setting up texlive-latex-recommended (2017.20180305-1) ...
Setting up texlive-pictures (2017.20180305-1) ...
Setting up tipa (2:1.3-20) ...
Regenerating '/var/lib/texmf/fmtutil.cnf-DEBIAN'... done.
Regenerating '/var/lib/texmf/fmtutil.cnf-TEXLIVEDIST'... done.
update-fmtutil has updated the following file(s):
    /var/lib/texmf/fmtutil.cnf-DEBIAN
    /var/lib/texmf/fmtutil.cnf-TEXLIVEDIST
If you want to activate the changes in the above file(s),
you should run fmtutil-sys or fmtutil.
Setting up texlive (2017.20180305-1) ...

```

```

Setting up texlive-latex-extra (2017.20180305-2) ...
Setting up texlive-xetex (2017.20180305-1) ...
Setting up ruby2.5 (2.5.1-1ubuntu1.12) ...
Setting up ruby (1:2.5.1) ...
Setting up ruby-test-unit (3.2.5-1) ...
Setting up rake (12.3.1-1ubuntu0.1) ...
Setting up libruby2.5:amd64 (2.5.1-1ubuntu1.12) ...
Processing triggers for mime-support (3.60ubuntu1) ...
Processing triggers for libc-bin (2.27-3ubuntu1.6) ...
Processing triggers for man-db (2.8.3-2ubuntu0.1) ...
Processing triggers for fontconfig (2.12.6-0ubuntu2) ...
Processing triggers for tex-common (6.09) ...
Running updmap-sys. This may take some time... done.
Running mktexlsr /var/lib/texmf ... done.
Building format(s) --all.
    This may take some time... done.
Get:1 https://cloud.r-project.org/bin/linux/ubuntu bionic-cran40/ InRelease
[3,626 B]
Ign:2 https://developer.download.nvidia.com/compute/machine-
learning/repos/ubuntu1804/x86_64 InRelease
Get:3 https://developer.download.nvidia.com/compute/cuda/repos/ubuntu1804/x86_64
InRelease [1,581 B]
Hit:4 https://developer.download.nvidia.com/compute/machine-
learning/repos/ubuntu1804/x86_64 Release
Get:5 http://security.ubuntu.com/ubuntu bionic-security InRelease [88.7 kB]
Hit:6 http://archive.ubuntu.com/ubuntu bionic InRelease
Get:7 https://developer.download.nvidia.com/compute/cuda/repos/ubuntu1804/x86_64
Packages [1,038 kB]
Get:8 http://archive.ubuntu.com/ubuntu bionic-updates InRelease [88.7 kB]
Hit:10 http://ppa.launchpad.net/c2d4u.team/c2d4u4.0+/ubuntu bionic InRelease
Get:11 http://archive.ubuntu.com/ubuntu bionic-backports InRelease [83.3 kB]
Hit:12 http://ppa.launchpad.net/cran/libgit2/ubuntu bionic InRelease
Get:13 http://security.ubuntu.com/ubuntu bionic-security/restricted amd64
Packages [1,262 kB]
Get:14 http://archive.ubuntu.com/ubuntu bionic-updates/restricted amd64 Packages
[1,303 kB]
Hit:15 http://ppa.launchpad.net/deadsnakes/ppa/ubuntu bionic InRelease
Get:16 http://security.ubuntu.com/ubuntu bionic-security/universe amd64 Packages
[1,563 kB]
Get:17 http://archive.ubuntu.com/ubuntu bionic-updates/universe amd64 Packages
[2,338 kB]
Get:18 http://security.ubuntu.com/ubuntu bionic-security/main amd64 Packages
[3,071 kB]
Get:19 http://archive.ubuntu.com/ubuntu bionic-updates/main amd64 Packages
[3,497 kB]
Get:20 http://ppa.launchpad.net/graphics-drivers/ppa/ubuntu bionic InRelease
[21.3 kB]
Get:21 http://ppa.launchpad.net/graphics-drivers/ppa/ubuntu bionic/main amd64

```

```
Packages [38.5 kB]
Fetched 14.4 MB in 2s (8,283 kB/s)
Reading package lists... Done
Reading package lists... Done
Building dependency tree
Reading state information... Done
texlive-fonts-recommended is already the newest version (2017.20180305-1).
texlive-fonts-recommended set to manually installed.
texlive-plain-generic is already the newest version (2017.20180305-2).
texlive-plain-generic set to manually installed.
texlive-xetex is already the newest version (2017.20180305-1).
The following package was automatically installed and is no longer required:
  libnvidia-common-460
Use 'sudo apt autoremove' to remove it.
0 upgraded, 0 newly installed, 0 to remove and 15 not upgraded.
Looking in indexes: https://pypi.org/simple, https://us-python.pkg.dev/colab-
wheels/public/simple/
Collecting py pandoc
  Downloading py pandoc-1.10-py3-none-any.whl (20 kB)
Installing collected packages: py pandoc
Successfully installed py pandoc-1.10
```