

# Scalable Rendering for Graphics and Game Engines

Antonio Chica Calaf  
[achica@cs.upc.edu](mailto:achica@cs.upc.edu)

Marc Comino Trinidad  
[mcomino@cs.upc.edu](mailto:mcomino@cs.upc.edu)

## LEGACY OPENGL


### CPU

```
// Render Time
glBegin(GL_TRIANGLES);
  glVertex3fv(v0);
  glVertex3fv(v1);
  glVertex3fv(v2);

  glVertex3fv(v0);
  glVertex3fv(v2);
  glVertex3fv(v3);
glEnd();
```

### GPU

// Render Time  
Receives 9 x F floats.



## VERTEX ARRAYS

### CPU

```
// Render Time
GLfloat vertices[] = {v0, v1, v2, v3};
GLubyte indices[] = {0,1,2,0,2,3};

glEnableClientState(GL_VERTEX_ARRAY);
glVertexPointer(3, GL_FLOAT, 0, vertices);

glDrawElements(GL_TRIANGLES, 6,
  GL_UNSIGNED_BYTE, indices);

glDisableClientState(GL_VERTEX_ARRAY);
```

### GPU

// Render Time  
Receives 3 x V floats and 3 x F integers.

VERTEX BUFFER OBJECTS	
CPU	GPU
<pre> // Initialization Time GLuint vbo_v_id, vbo_n_id, faces_id;  glGenBuffers(1, &amp;vbo_v_id); glBindBuffer(GL_ARRAY_BUFFER, vbo_v_id); glBufferData(GL_ARRAY_BUFFER, dataSize, vertices, GL_STATIC_DRAW);  glGenBuffers(1, &amp;vbo_n_id); glBindBuffer(GL_ARRAY_BUFFER, vbo_n_id); glBufferData(GL_ARRAY_BUFFER, dataSize, normals, GL_STATIC_DRAW);  glGenBuffers(1, &amp;faces_id); glBindBuffer(GL_ELEMENT_ARRAY_BUFFER, faces_id); glBufferData(GL_ELEMENT_ARRAY_BUFFER, dataSize, indices, GL_STATIC_DRAW);  // Render Time glBindBuffer(GL_ARRAY_BUFFER, vbo_v_id); glVertexAttribPointer(3, GL_FLOAT, 0, 0); glEnableClientState(GL_VERTEX_ARRAY);  glBindBuffer(GL_ARRAY_BUFFER, vbo_n_id); glNormalPointer(3, GL_FLOAT, 0, 0); glEnableClientState(GL_NORMAL_ARRAY);  glBindBuffer(GL_ELEMENT_ARRAY_BUFFER, faces_id)  glDrawElements(GL_TRIANGLES, 6, GL_UNSIGNED_BYTE, 0);  glDisableClientState(GL_VERTEX_ARRAY); glDisableClientState(GL_NORMAL_ARRAY);  glBindBuffer(GL_ARRAY_BUFFER, 0); glBindBuffer(GL_ELEMENT_ARRAY_BUFFER, 0); </pre>	<pre> // Initialization Time Receives and <b>stores</b> 3 x V floats and 3 x F integers.. Optionally receives and <b>stores</b> 3 x V for each additional attribute. </pre>

VERTEX ARRAY OBJECTS	
CPU	GPU
<pre>// Initialization Time GLfloat data[] = {v0, n0, v1, n1, v2, n2, v3, n3}; GLuint vbo_id;  glGenBuffers(1, &amp;vbo_id); glBindBuffer(GL_ARRAY_BUFFER, vbo_id); glBufferData(GL_ARRAY_BUFFER, dataSize, data, GL_STATIC_DRAW);  GLuint vao_id; glGenVertexArrays(1, &amp;vao_id); glBindVertexArray(vao_id); glVertexAttribPointer(0, 3, GL_FLOAT, GL_FALSE, dataSize, 0, 0); glEnableVertexAttribArray(0);  glBindVertexArray(vao_id); glVertexAttribPointer(1, 3, GL_FLOAT, GL_FALSE, dataSize, stride, offset); glEnableVertexAttribArray(1);  glBindVertexArray(0); glBindBuffer(GL_ARRAY_BUFFER, vbo_id);  // Render Time glBindVertexArray(vao_id); glBindBuffer(GL_ELEMENT_ARRAY_BUFFER, faces_id);  glDrawElements(GL_TRIANGLES, 6, GL_UNSIGNED_BYTE, 0);  glBindBuffer(GL_ELEMENT_ARRAY_BUFFER, 0); glBindVertexArray(GL_ARRAY_BUFFER, 0);</pre>	<pre>// Initialization Time Receives and <b>stores</b> 3 x V floats and 3 x F integers.. Optionally receives and <b>stores</b> 3 x V for each additional attribute.</pre>

## MORE RESOURCES:

<https://learnopengl.com/Model-Loading/Mesh>

[http://www.songho.ca/opengl/gl\\_vertexarray.html](http://www.songho.ca/opengl/gl_vertexarray.html)

[http://www.songho.ca/opengl/gl\\_vbo.html](http://www.songho.ca/opengl/gl_vbo.html)

[https://www.khronos.org/opengl/wiki/Vertex\\_Specification#Vertex\\_Array\\_Object](https://www.khronos.org/opengl/wiki/Vertex_Specification#Vertex_Array_Object)